

# [MS-ACCDT]: Access Template File Format

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Major	Updated and revised the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Minor	Updated the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.05	Minor	Clarified the meaning of the technical content.
12/17/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	1.6	Minor	Clarified the meaning of the technical content.
04/11/2012	1.6	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	1.6	No change	No changes to the meaning, language, or formatting of the technical content.
09/12/2012	1.6	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	1.7	Minor	Clarified the meaning of the technical content.
02/11/2013	1.7	No change	No changes to the meaning, language, or formatting of the technical content.
07/30/2013	1.8	Minor	Clarified the meaning of the technical content.
11/18/2013	1.9	Minor	Clarified the meaning of the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
02/10/2014	1.9.1	Editorial	Changed language and formatting in the technical content.
04/30/2014	1.10	Minor	Clarified the meaning of the technical content.

# Table of Contents

<b>1 Introduction</b>	<b>6</b>
1.1 Glossary	6
1.2 References	6
1.2.1 Normative References	6
1.2.2 Informative References	7
1.3 Structure Overview (Synopsis)	7
1.4 Relationship to Protocols and Other Structures	8
1.5 Applicability Statement	8
1.6 Versioning and Localization	8
1.7 Vendor-Extensible Fields	9
<b>2 Structures</b>	<b>10</b>
2.1 File Structure	10
2.1.1 Package	10
2.1.2 Part	10
2.1.3 Relationship	10
2.1.4 Part Enumeration	11
2.1.4.1 Application Properties	12
2.1.4.2 Data Macro	12
2.1.4.3 File Properties, Core	13
2.1.4.4 Form	13
2.1.4.5 Icon	13
2.1.4.6 Image	14
2.1.4.7 Image Cluster	14
2.1.4.8 Instantiation Form	15
2.1.4.9 Legacy Application Properties	15
2.1.4.10 Linked Table	15
2.1.4.11 List Definition	15
2.1.4.12 Macro	16
2.1.4.13 Navigation Pane	16
2.1.4.14 Object	16
2.1.4.15 Object Metadata	17
2.1.4.16 Object Properties	17
2.1.4.17 Preview Image	17
2.1.4.18 Query	18
2.1.4.19 Relationship	18
2.1.4.20 Report	18
2.1.4.21 Resource	19
2.1.4.22 Table Data	19
2.1.4.23 Template Metadata	19
2.1.4.24 Theme	19
2.1.4.25 Variation	20
2.1.4.26 Visual Basic References	20
2.2 Template Metadata	20
2.2.1 Global Elements	20
2.2.1.1 Template	20
2.2.2 Global Attributes	20
2.2.3 Complex Types	21
2.2.3.1 CT_Template	21
2.2.4 Simple Types	22

2.3	Object Metadata .....	22
2.3.1	Global Elements .....	22
2.3.1.1	AccessObject.....	22
2.3.2	Global Attributes .....	22
2.3.3	Complex Types .....	22
2.3.3.1	CT_NameMap.....	22
2.3.3.2	CT_AccessObject .....	22
2.3.4	Simple Types .....	23
2.3.4.1	ST_Type.....	23
2.4	List Schema .....	24
2.4.1	Add Calculated Fields .....	24
2.4.2	Add Fields .....	24
2.4.3	Add List .....	25
2.4.4	Field Properties .....	25
2.4.5	List Properties.....	25
2.5	List Data.....	25
2.5.1	Data Instance .....	25
2.5.2	Schema .....	25
<b>3</b>	<b>Structure Examples .....</b>	<b>26</b>
3.1	List Schema .....	26
3.2	List Data.....	29
3.3	Images.....	33
<b>4</b>	<b>Security.....</b>	<b>35</b>
4.1	Security Considerations for Implementers.....	35
4.2	Index of Security Fields .....	35
<b>5</b>	<b>Appendix A: Full XML Schemas.....</b>	<b>36</b>
5.1	<a href="http://schemas.microsoft.com/office/access/2005/04/template/start">http://schemas.microsoft.com/office/access/2005/04/template/start</a> Schema .....	36
5.2	<a href="http://schemas.microsoft.com/office/access/2005/04/template/object-metadata">http://schemas.microsoft.com/office/access/2005/04/template/object-metadata</a> Schema .....	36
<b>6</b>	<b>Appendix B: Product Behavior .....</b>	<b>38</b>
<b>7</b>	<b>Change Tracking.....</b>	<b>39</b>
<b>8</b>	<b>Index .....</b>	<b>41</b>

# 1 Introduction

The Access Template File Format specifies the Access Template File Format (.accdt). This File Format is a collection of structures used to define a database application. These structures can include schemas for storing data, the data to be stored, layout descriptions for views of the data, actions controlling workflow, and metadata describing the database application as a whole.

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

### **Augmented Backus-Naur Form (ABNF)**

The following terms are defined in [\[MS-OFCGLOS\]](#):

**database application**  
**database object**  
**field**  
**list**  
**list item**  
**sort order**

The following terms are specific to this document:

**calculated field:** A user-defined field that can perform calculations by using the contents of other fields.

**database template:** A file that contains the data and component descriptions that are needed to create or instantiate a database application.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[ISO/IEC-29500-1] International Organization for Standardization, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 1: Fundamentals and Markup Language Reference", ISO/IEC 29500-1:2008, [http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=51463](http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=51463)

[ISO/IEC-29500-2] International Organization for Standardization, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 2: Open Packaging Conventions", ISO/IEC 29500-2:2008, [http://www.iso.org/iso/catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=51459](http://www.iso.org/iso/catalogue/catalogue_tc/catalogue_detail.htm?csnumber=51459)

[MS-ASWS] Microsoft Corporation, "[Access Services Protocol](#)".

[MS-AXL] Microsoft Corporation, "[Access Application Transfer Protocol Structure Specification](#)".

[MS-LISTSWS] Microsoft Corporation, "[Lists Web Service Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC4234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 4234, October 2005, <http://www.ietf.org/rfc/rfc4234.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

[XMLSCHEMA1] Thompson, H.S., Beech, D., Maloney, M., and Mendelsohn, N., Eds., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., and Malhotra, A., Eds., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

### 1.2.2 Informative References

[ISO/IEC-29500-3] International Organization for Standardization, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 3: Markup Compatibility and Extensibility", ISO/IEC 29500-3:2008, [http://www.iso.org/iso/catalogue\\_detail?csnumber=51461](http://www.iso.org/iso/catalogue_detail?csnumber=51461)

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFGLGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

### 1.3 Structure Overview (Synopsis)

This document specifies the format of a **database template** used to create an instance of a **database application**. The database template data is contained in a ZIP **package** (section [2.1.1](#)) conforming to Open Packaging Conventions as specified in [\[ISO/IEC-29500-2\]](#). Individual files stored in the ZIP package (section [2.1.1](#)) called **parts** (section [2.1.2](#)) contain information about the structure and content of the resulting database application. The parts include definitions of the **database objects**, data to be populated, and properties of the resulting database application. Note that the contents of many of the parts (section [2.1.2](#)) described in this document are the same as those used by the MSysASO **list (1)** as described in [\[MS-ASWS\]](#) section 3.1.1.1.1.

The document is organized as follows:

Section [2](#) of this documentation contains an overview of high-level concepts that are followed by more detailed concepts. Section [2.1](#) specifies higher-level concepts that are required to understand the remainder of the documentation, and should be read before reading the remainder of section [2](#).

Section [2.1](#) specifies the structure and concepts that are used to organize and structure the file itself. Subsection [2.1.4](#) further specifies the valid **parts** (section [2.1.2](#)) allowed within this **package** (section [2.1.1](#)).

Section [2.2](#) specifies the details of structures that contain metadata associated with the database template.

Section [2.3](#) specifies the details of structures that contain metadata associated with individual database objects.

Section [2.4](#) specifies the details of structures used for creating lists (1).

Section [2.5](#) specifies the details of structures that contain data to be populated in the resulting database application.

Section [3](#) provides specific examples intended to illustrate the concepts and elements of this file format.

Section [4](#) discusses security considerations relating to files of the type specified by the document.

Section [6](#) is a list of application-specific behavior. It is not intended to be read alone, but rather to be understood in the context of specifications in section [2](#). Specifications in section [2](#) provide links to the relevant items in section [6](#).

## 1.4 Relationship to Protocols and Other Structures

The Access Template File Format is a package containing a set of related parts as specified by [\[ISO/IEC-29500-2\]](#). It is dependent on the structures defined in the following references:

- [\[MS-AXL\]](#) for the persistence format for database objects.
- [\[MS-LISTSWS\]](#) for the persistence format for list (1) definitions. **[MS-LISTSWS]** describes a SOAP protocol; the Access Template File Format contains a set of persisted SOAP commands defined by this protocol that can be issued to create a list with a particular schema. Section [2.4](#) describes this relationship in detail.
- [\[XMLSCHEMA2\]](#) for the persistence format for list (1) data.
- [\[MS-ASWS\]](#) for the persistence format of version-related values, as described in Section [2.2.3.1](#).

## 1.5 Applicability Statement

This document specifies a persistence format for database applications, which can include structures for storing data, the data to be stored, layout descriptions for views of the data, actions to control workflow, and metadata to describe the database application as a whole. This persistence format is applicable for persistence of applications based on storing data in tables, including views and logic to control workflow.

This persistence format is applicable for use as a stand-alone document.

This persistence format provides interoperability with applications that create or read documents conforming to this structure.

## 1.6 Versioning and Localization

This document covers versioning issues in the following areas:



**Structure Versions:** There is only one version of the Access Template File Format (.accdt) Specification.

**Localization:** The structure of the Access Template File Format (.accdt) contains no locale-dependent information.

## 1.7 Vendor-Extensible Fields

This persistence format can be extended by storing information in parts not specified in section 2. Implementations are not required to preserve or remove additional parts when modifying an existing document. Implementations can extend the XML as specified by [\[ISO/IEC-29500-3\]](#).

## 2 Structures

### 2.1 File Structure

This section specifies the overall structure of a file that conforms to this specification.

A file of the type specified by this document is a **package** (section [2.1.1](#)) that contains a collection of related **parts** (section [2.1.2](#)). **Parts** contain information about the contents of a database application, including database objects, associated metadata, and the structure of the **package**. **Parts** contain information stored using XML, text, and binary formats.

#### 2.1.1 Package

A file of the type specified by this document is a package that is a ZIP archive that conforms to the Open Packaging Conventions as specified in [\[ISO/IEC-29500-2\]](#), the further packaging restrictions specified in [\[ISO/IEC-29500-1\]](#) section 9, and this specification.

A file of the type specified by this document MUST contain one **Template Metadata** (section [2.1.4.23](#)) part, and that **part** (section [2.1.2](#)) MUST be the target of a **relationship** (section [2.1.3](#)) in the package relationship **part**. The **Template Metadata** part is the main or starting **part** in a file of the type specified by this document.

#### 2.1.2 Part

A part is a stream of bytes as specified in [\[ISO/IEC-29500-2\]](#) section 9.1. Each part has an associated content type that specifies the nature and type of content stored in the part. Parts store information in binary, XML, and text formats. The valid parts, valid content types, and required **relationships** (section [2.1.3](#)) between all parts in a **package** (section [2.1.1](#)) are specified in **Part Enumeration** (section [2.1.4](#)).

This document uses **Augmented Backus-Naur Form (ABNF)** as specified in [\[RFC5234\]](#) to specify the content of the **List Definition** (section [2.1.4.11](#)) and **Table Data** (section [2.1.4.22](#)) parts.

#### 2.1.3 Relationship

A relationship specifies a connection between a source and a target resource as specified in [\[ISO/IEC-29500-2\]](#) section 9.3. Relationship identifiers are used in binary, XML, and text **part** (section [2.1.2](#)) content to reference unique relationship elements in relationship **parts** that in turn target other resources. There are several different types of relationships:

- A package relationship is a relationship where the target is a **part** and the source is the **package** (section [2.1.1](#)) as a whole.
- A part-to-part relationship is a relationship where the target is a **part** and the source is a **part** in the **package**.
- An explicit relationship is a relationship where a resource is referenced from the contents of a source **part** by referencing a relationship element by the value of its **ID** attribute, specified in [\[ISO/IEC-29500-2\]](#) section 9.3.2.
- An implicit relationship is a relationship that is not explicit.
- An internal relationship is a relationship where the target is a **part** in the **package**.

- An external relationship is a relationship where the target is an external resource not in the **package**.

## 2.1.4 Part Enumeration

This section specifies the parts of the Access Template File Format (.accdt) package. Refer to the sections **Package** (section [2.1.1](#)), **Part** (section [2.1.2](#)), and **Relationship** (section [2.1.3](#)) for information about packages, parts, and **relationships**, including the **package relationship part**.

**Parts** and their **relationships** are summarized in the following table.

Part	Relationship Target of
<b>Application Properties</b> (section <a href="#">2.1.4.1</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Data Macro</b> (section <a href="#">2.1.4.2</a> )	<b>List Definition</b> (section <a href="#">2.1.4.11</a> ), <b>Object</b> (section <a href="#">2.1.4.14</a> )
<b>File Properties, Core</b> (section <a href="#">2.1.4.3</a> )	<b>Package</b> (section <a href="#">2.1.1</a> )
<b>Form</b> (section <a href="#">2.1.4.4</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Icon</b> (section <a href="#">2.1.4.5</a> )	<b>Package</b> (section <a href="#">2.1.1</a> )
<b>Image</b> (section <a href="#">2.1.4.6</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Image Cluster</b> (section <a href="#">2.1.4.7</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Instantiation Form</b> (section <a href="#">2.1.4.8</a> )	<b>Package</b> (section <a href="#">2.1.1</a> )
<b>Legacy Application Properties</b> (section <a href="#">2.1.4.9</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Linked Table</b> (section <a href="#">2.1.4.10</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>List Definition</b> (section <a href="#">2.1.4.11</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Macro</b> (section <a href="#">2.1.4.12</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Navigation Pane</b> (section <a href="#">2.1.4.13</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Object</b> (section <a href="#">2.1.4.14</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Object Metadata</b> (section <a href="#">2.1.4.15</a> )	<b>Form</b> (section <a href="#">2.1.4.4</a> ), <b>Linked Table</b> (section <a href="#">2.1.4.10</a> ), <b>List Definition</b> (section <a href="#">2.1.4.11</a> ), <b>Macro</b> (section <a href="#">2.1.4.12</a> ), <b>Object</b> (section <a href="#">2.1.4.14</a> ), <b>Query</b> (section <a href="#">2.1.4.18</a> ), <b>Report</b> (section <a href="#">2.1.4.20</a> )
<b>Object Properties</b> (section <a href="#">2.1.4.16</a> )	<b>Form</b> (section <a href="#">2.1.4.4</a> ), <b>List Definition</b> (section <a href="#">2.1.4.11</a> ), <b>Query</b> (section <a href="#">2.1.4.18</a> ), <b>Report</b> (section <a href="#">2.1.4.20</a> )
<b>Preview Image</b> (section <a href="#">2.1.4.17</a> )	<b>Package</b> (section <a href="#">2.1.1</a> )

Part	Relationship Target of
<b>Query</b> (section <a href="#">2.1.4.18</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Relationship</b> (section <a href="#">2.1.4.19</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Report</b> (section <a href="#">2.1.4.20</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Resource</b> (section <a href="#">2.1.4.21</a> )	<b>Image</b> (section <a href="#">2.1.4.6</a> ), <b>Image Cluster</b> (section <a href="#">2.1.4.7</a> ), <b>Theme</b> (section <a href="#">2.1.4.24</a> )
<b>Table Data</b> (section <a href="#">2.1.4.22</a> )	<b>List Definition</b> (section <a href="#">2.1.4.11</a> ), <b>Object</b> (section <a href="#">2.1.4.14</a> )
<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )	<b>Package</b> (section <a href="#">2.1.1</a> )
<b>Theme</b> (section <a href="#">2.1.4.24</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )
<b>Variation</b> (section <a href="#">2.1.4.25</a> )	<b>Form</b> (section <a href="#">2.1.4.4</a> ), <b>Linked Table</b> (section <a href="#">2.1.4.10</a> ), <b>List Definition</b> (section <a href="#">2.1.4.11</a> ), <b>Macro</b> (section <a href="#">2.1.4.12</a> ), <b>Object</b> (section <a href="#">2.1.4.14</a> ), <b>Query</b> (section <a href="#">2.1.4.18</a> ), <b>Report</b> (section <a href="#">2.1.4.20</a> )
<b>Visual Basic References</b> (section <a href="#">2.1.4.26</a> )	<b>Template Metadata</b> (section <a href="#">2.1.4.23</a> )

In the following sections, Content type is as specified in [\[ISO/IEC-29500-2\]](#) section 9.1.2 and Relationship type is as specified in [\[ISO/IEC-29500-2\]](#) section 9.3.2

### 2.1.4.1 Application Properties

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/Properties">http://schemas.microsoft.com/office/2007/relationships/Properties</a>

An instance of this part type specifies properties of the database application.

An **Application Properties** part MUST be the target of exactly one explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

The content associated with this part begins with the Application element as specified by [\[MS-AXL\]](#) section 2.2.1.1.

### 2.1.4.2 Data Macro

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/DataMacros">http://schemas.microsoft.com/office/2007/relationships/DataMacros</a>

An instance of this part type contains definitions for the data macros, as specified by [\[MS-AXL\]](#) section 2.1.3.2, that are associated with a list (1).

A **Data Macro** part MUST be the target of an explicit relationship from a **List Definition** (section [2.1.4.11](#)) or **Object** (section [2.1.4.14](#)) part.

The content associated with this part begins with the **DataMacros** element as specified by [\[MS-AXL\]](#) section 2.2.1.5.

### 2.1.4.3 File Properties, Core

This part is specified in [\[ISO/IEC-29500-1\]](#) section 15.2.12.1. The content associated with this part is specified in [\[ISO/IEC-29500-2\]](#) section 11.

### 2.1.4.4 Form

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/Form">http://schemas.microsoft.com/office/2007/relationships/Form</a>

An instance of this part type contains the definition for a single form as specified by [\[MS-AXL\]](#) section 2.1.2.

A **Form** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

A **Form** part MUST have an explicit relationship to exactly one **Object Metadata** part (section [2.1.4.15](#)).

A **Form** part MUST have an explicit relationship to exactly one **Object Properties** part (section [2.1.4.16](#)).

The content associated with this part begins with the **View** element as specified by [\[MS-AXL\]](#) section 2.2.1.7.

### 2.1.4.5 Icon

Content type	Relationship type
Image/unknown Image/bmp Image/gif Image/png Image/tiff Image/xbm Image/x-icon Image/x-pcx Image/x-pcz Image/x-emz Image/x-wmz Image/jpeg Image/x-emf Image/x-wmf	<a href="http://schemas.microsoft.com/office/2007/relationships/icon-image">http://schemas.microsoft.com/office/2007/relationships/icon-image</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

An **Icon** part MUST be the target of an explicit relationship from the **Package** part (section [2.1.1](#)).

### 2.1.4.6 Image

Content type	Relationship type
Image/unknown Image/bmp Image/gif Image/png Image/tiff Image/xbm Image/x-icon Image/x-pcx Image/x-pcz Image/x-emz Image/x-wmz Image/jpeg Image/x-emf Image/x-wmf	<a href="http://schemas.microsoft.com/office/2007/relationships/shared-image">http://schemas.microsoft.com/office/2007/relationships/shared-image</a>

An instance of this part type contains an image to be used as a Shared Image as specified by [\[MS-AXL\]](#) section 2.1.6.

An **Image** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

An **Image** part MUST have an explicit relationship to exactly one **Resource** part (section [2.1.4.21](#)).

### 2.1.4.7 Image Cluster

Content type	Relationship type
Image/unknown Image/bmp Image/gif Image/png Image/tiff Image/xbm Image/x-icon Image/x-pcx Image/x-pcz Image/x-emz Image/x-wmz Image/jpeg Image/x-emf Image/x-wmf	<a href="http://schemas.microsoft.com/office/2007/relationships/image-cluster">http://schemas.microsoft.com/office/2007/relationships/image-cluster</a>

An instance of this part type contains an image cluster to be used as a Shared Image as specified by [\[MS-AXL\]](#) section 2.1.6. An **Image Cluster** part is a composite image where specific portions of the image are used by forms in the database application as specified by [\[MS-AXL\]](#) sections [2.3.4.77](#), [2.3.4.78](#) and [2.3.4.79](#).

An **Image Cluster** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

An **Image Cluster** part MUST have an explicit relationship to exactly one **Resource** part (section [2.1.4.21](#)).

#### 2.1.4.8 Instantiation Form

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/instantiation-form">http://schemas.microsoft.com/office/2007/relationships/instantiation-form</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

An **Instantiation Form** part MUST be the target of an explicit relationship from the **Package** part (section [2.1.1](#)).

#### 2.1.4.9 Legacy Application Properties

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/access/2005/04/template/properties">http://schemas.microsoft.com/office/access/2005/04/template/properties</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

A **Legacy Application Properties** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

#### 2.1.4.10 Linked Table

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/Link">http://schemas.microsoft.com/office/2007/relationships/Link</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

A **Linked Table** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

A **Linked Table** part MUST have an explicit relationship to exactly one **Object Metadata** part (section [2.1.4.15](#)).

#### 2.1.4.11 List Definition

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/ListInstanceDefinition">http://schemas.microsoft.com/office/2007/relationships/ListInstanceDefinition</a>

An instance of this part type contains the definition for a single list (1).

A **List Definition** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

A **List Definition** part MUST have an explicit relationship to exactly one **Object Metadata** part (section [2.1.4.15](#)).

A **List Definition** part MUST have an explicit relationship to exactly one **Object Properties** part (section [2.1.4.16](#)).

The content associated with this part is specified by **List Schema** (section [2.4](#)).

#### 2.1.4.12 Macro

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/Macro">http://schemas.microsoft.com/office/2007/relationships/Macro</a>

An instance of this part type contains the definition for a single standalone User Interface Macro as specified by [\[MS-AXL\]](#) section 2.1.3.1.

A **Macro** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)) part.

A **Macro** part MUST have an explicit relationship to exactly one **Object Metadata** part (section [2.1.4.15](#)).

The content associated with this part begins with the **UserInterfaceMacro** element as specified by [\[MS-AXL\]](#) section 2.2.1.6

#### 2.1.4.13 Navigation Pane

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/access/2005/04/template/nav-pane">http://schemas.microsoft.com/office/access/2005/04/template/nav-pane</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

A **Navigation Pane** part MUST be the target of exactly one explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

#### 2.1.4.14 Object

Content type	Relationship type
Text/xml Text/plain	<a href="http://schemas.microsoft.com/office/access/2005/04/template/object">http://schemas.microsoft.com/office/access/2005/04/template/object</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

An **Object** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

An **Object** part MUST have an explicit relationship to exactly one **Object Metadata** part (section [2.1.4.15](#)).



### 2.1.4.15 Object Metadata

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/access/2005/04/template/object-metadata">http://schemas.microsoft.com/office/access/2005/04/template/object-metadata</a>

An instance of this part type contains the definition of the metadata associated with a single object.

An **Object Metadata** part MUST be the target of an explicit relationship from a **Form** (section [2.1.4.4](#)), **Linked Table** (section [2.1.4.10](#)), **List Definition** (section [2.1.4.11](#)), **Macro** (section [2.1.4.12](#)), **Object** (section [2.1.4.14](#)), **Query** (section [2.1.4.18](#)), or **Report** (section [2.1.4.20](#)) part.

The content associated with this part is specified by section [2.3](#).

### 2.1.4.16 Object Properties

Content type	Relationship type
application/vnd-ms-access.objectproperties+xml	<a href="http://schemas.microsoft.com/office/2007/relationships/ObjectProperties">http://schemas.microsoft.com/office/2007/relationships/ObjectProperties</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

An **Object Properties** part MUST be the target of an explicit relationship from a **Form** (section [2.1.4.4](#)), **List Definition** (section [2.1.4.11](#)), **Query** (section [2.1.4.18](#)), or **Report** (section [2.1.4.20](#)) part.

### 2.1.4.17 Preview Image

Content type	Relationship type
Image/unknown Image/bmp Image/gif Image/png Image/tiff Image/xbm Image/x-icon Image/x-pcx Image/x-pcz Image/x-emz Image/x-wmz Image/jpeg Image/x-emf Image/x-wmf	<a href="http://schemas.microsoft.com/office/access/2005/04/template/preview-image">http://schemas.microsoft.com/office/access/2005/04/template/preview-image</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

A **Preview Image** part MUST be the target of an explicit relationship from the **Package** (section [2.1.1](#)) part.

#### 2.1.4.18 Query

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/Query">http://schemas.microsoft.com/office/2007/relationships/Query</a>

An instance of this part type contains the definition for a single query as specified by [\[MS-AXL\]](#) section 2.1.4.

A **Query** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

A **Query** part MUST have an explicit relationship to exactly one **Object Metadata** part (section [2.1.4.15](#)).

A **Query** part MUST have an explicit relationship to exactly one **Object Properties** part (section [2.1.4.16](#)).

The content associated with this part begins with the **Query** element as specified by [\[MS-AXL\]](#) section 2.2.1.2.

#### 2.1.4.19 Relationship

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/access/2005/04/template/relationships">http://schemas.microsoft.com/office/access/2005/04/template/relationships</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

A **Relationship** part MUST be the target of exactly one explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

#### 2.1.4.20 Report

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/2007/relationships/Report">http://schemas.microsoft.com/office/2007/relationships/Report</a>

An instance of this part type contains the definition for a single report as specified by [\[MS-AXL\]](#) section 2.1.5.

A **Report** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)) part.

A **Report** part MUST have an explicit relationship to exactly one **Object Metadata** part (section [2.1.4.15](#)).

A **Report** part MUST have an explicit relationship to exactly one **Object Properties** part (section [2.1.4.16](#)).

The content associated with this part begins with the **Report** element as specified by [\[MS-AXL\]](#) section 2.4.1.1.

### 2.1.4.21 Resource

Content type	Relationship type
Text/plain	http://schemas.microsoft.com/office/2007/relationships/resource-name

An instance of this part type contains the name of a shared resource, which uniquely identifies the resource in the template. A **Resource** part MUST be the target of an explicit relationship from an **Image** (section [2.1.4.6](#)), **Image Cluster** (section [2.1.4.7](#)), or **Theme** (section [2.1.4.24](#)) part. This file MUST contain a single line that is the name of the **shared resource** used by the database application. The combination of a shared resource's name and its parent part type (**Image**, **Image Cluster**, or **Theme**) MUST be unique within the database application.

The resource name MUST NOT be longer than 64 characters and MUST NOT contain any of the following characters:

! ` [ ] ; . ~ # % & \* { } \ : < > ? / |"

### 2.1.4.22 Table Data

Content type	Relationship type
Application/xml	http://schemas.microsoft.com/office/access/2005/04/template/table-data

An instance of this part defines the schema associated with the table and the data contained in the table.

A **Table Data** part MUST be the target of an explicit relationship from a **List Definition** (section [2.1.4.11](#)) or **Object** (section [2.1.4.14](#)) part.

The content associated with this part is specified by **List Data** (section [2.5](#)).

### 2.1.4.23 Template Metadata

Content type	Relationship type
Text/xml	http://schemas.microsoft.com/office/access/2005/04/template/start

An instance of this part type contains the template-level metadata for the current file.

A **Template Metadata** part MUST be the target of exactly one explicit relationship from the **Package** part (section [2.1.1](#)).

The content associated with this part is specified by **Template Metadata** (section [2.2](#)).

### 2.1.4.24 Theme

Content type	Relationship type
application/vnd.ms-officetheme	http://schemas.microsoft.com/office/2007/relationships/shared-theme

An instance of this part type contains display details for a single display theme.

A **Theme** part MUST be the target of an explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

A **Theme** part MUST have an explicit relationship to exactly one **Resource** part (section [2.1.4.21](#)).

The contents of this part MUST be a ZIP archive that conforms to the Open Packaging Conventions as specified in [\[ISO/IEC-29500-2\]](#), and the further packaging restrictions specified in [\[ISO/IEC-29500-1\]](#) section 9. This ZIP archive MUST contain at least one **Theme** part as specified by [\[ISO/IEC-29500-1\]](#) section 14.2.7.

### 2.1.4.25 Variation

Content type	Relationship type
Text/xml Text/plain	<a href="http://schemas.microsoft.com/office/access/2005/04/template/variation">http://schemas.microsoft.com/office/access/2005/04/template/variation</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

A **Variation** part MUST be the target of an explicit relationship from a **Form** (section [2.1.4.4](#)), **Linked Table** (section [2.1.4.10](#)), **List Definition** (section [2.1.4.11](#)), **Macro** (section [2.1.4.12](#)), **Object** (section [2.1.4.14](#)), **Query** (section [2.1.4.18](#)), or **Report** (section [2.1.4.20](#)) part.

### 2.1.4.26 Visual Basic References

Content type	Relationship type
Application/xml	<a href="http://schemas.microsoft.com/office/access/2005/04/template/vba-references">http://schemas.microsoft.com/office/access/2005/04/template/vba-references</a>

An instance of this part type can have any content such that the part remains valid for the given content type.

A **Visual Basic References** part MUST be the target of exactly one explicit relationship from the **Template Metadata** part (section [2.1.4.23](#)).

## 2.2 Template Metadata

### 2.2.1 Global Elements

#### 2.2.1.1 Template

*Target namespace:* <http://schemas.microsoft.com/office/access/2005/04/template/start>

A **CT\_Template** element (section [2.2.3.1](#)).

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="Template" type="CT_Template"/>
```

#### 2.2.2 Global Attributes

None.

## 2.2.3 Complex Types

### 2.2.3.1 CT\_Template

*Target namespace:* <http://schemas.microsoft.com/office/access/2005/04/template/start>

*Referenced by:* [Template](#)

Metadata for the template described by the current file.

*Child Elements:*

**TemplateFormat:** MUST be ignored.

**FlipRightToLeft:** MUST be ignored.

**PerformLocalizationFixup:** MUST be ignored.

**CollatingOrder:** An unsignedInt [\[XMLSCHEMA2\]](#) element that specifies the locale to be used for the **sort order (1)**.

**DataLocale:** An unsignedInt [\[XMLSCHEMA2\]](#) element that specifies the locale to be used for formatting data.

**UILocale:** An unsignedInt [\[XMLSCHEMA2\]](#) element that specifies the locale to be used for displaying the template in the user interface.

**RequiredAccessVersion:** A string [\[XMLSCHEMA2\]](#) element that specifies the version of the template. This element MUST be set to 12 or 14.

**AccessServicesVersion:** A string [\[XMLSCHEMA2\]](#) element that is used to determine the target namespace for Xml in parts of this template that are defined by schemas in [\[MS-AXL\]](#). The format of this string MUST follow the ABNF [\[RFC4234\]](#) specified by [\[MS-ASWS\]](#) section 3.1.1.2. The target namespaces that are used based on its value MUST be those specified by [\[MS-ASWS\]](#) section 3.1.1.2.

**Type:** MUST be ignored.

**PerformFontFixup:** MUST be ignored.

**VariationIdentifier:** MUST be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_Template">
  <xsd:sequence>
    <xsd:element name="TemplateFormat" type="xsd:unsignedInt" minOccurs="0"/>
    <xsd:element name="FlipRightToLeft" type="xsd:unsignedInt"/>
    <xsd:element name="PerformLocalizationFixup" type="xsd:unsignedInt"/>
    <xsd:element name="CollatingOrder" type="xsd:unsignedInt" minOccurs="0"/>
    <xsd:element name="DataLocale" type="xsd:unsignedInt" minOccurs="0"/>
    <xsd:element name="UILocale" type="xsd:unsignedInt" minOccurs="0"/>
    <xsd:element name="RequiredAccessVersion" type="xsd:string"/>
    <xsd:element name="AccessServicesVersion" type="xsd:string"/>
    <xsd:element name="Type" type="xsd:string"/>
    <xsd:element name="PerformFontFixup" type="xsd:unsignedInt" minOccurs="0"/>
    <xsd:element name="VariationIdentifier" type="xsd:string" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>
```

```
</xsd:sequence>
</xsd:complexType>
```

## 2.2.4 Simple Types

None.

## 2.3 Object Metadata

### 2.3.1 Global Elements

#### 2.3.1.1 AccessObject

*Target namespace:* <http://schemas.microsoft.com/office/access/2005/04/template/object-metadata>

A **CT\_AccessObject** element (section [2.3.3.2](#)) that specifies a database object.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xsd:element name="AccessObject" type="CT_AccessObject"/>
```

#### 2.3.2 Global Attributes

None.

### 2.3.3 Complex Types

#### 2.3.3.1 CT\_NameMap

*Target namespace:* <http://schemas.microsoft.com/office/access/2005/04/template/object-metadata>

*Referenced by:* [CT\\_AccessObject](#)

MUST be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_NameMap">
  <xsd:sequence>
    <xsd:any maxOccurs="unbounded"/>
  </xsd:sequence>
</xsd:complexType>
```

#### 2.3.3.2 CT\_AccessObject

*Target namespace:* <http://schemas.microsoft.com/office/access/2005/04/template/object-metadata>

*Referenced by:* [AccessObject](#)

Specifies an object in a database application, such as a form or a report.

*Child Elements:*

**Type:** An **ST\_Type** element (section [2.3.4.1](#)) that specifies the type of the object.

**Name:** A string [\[XMLSCHEMA2\]](#) element that specifies the name of the object. This value **MUST** conform to the restrictions of a **ST\_ObjectName** simple type as specified by [\[MS-AXL\]](#) section 2.2.4.1.

**NameMap:** **MUST** be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xsd:complexType name="CT_AccessObject">
  <xsd:sequence>
    <xsd:element name="Type" type="ST_Type"/>
    <xsd:element name="Name" type="xsd:string"/>
    <xsd:element name="NameMap" type="CT_NameMap" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>
```

## 2.3.4 Simple Types

### 2.3.4.1 ST\_Type

*Target namespace:* <http://schemas.microsoft.com/office/access/2005/04/template/object-metadata>

*Referenced by:* [CT\\_AccessObject](#)

Specifies the type of object contained within the related part.

Value	Meaning
Table	The part associated with the current <b>Object Metadata</b> part (section <a href="#">2.1.4.15</a> ) describes a tabular data.
Link	The part associated with the current <b>Object Metadata</b> part describes a connection to an external data source.
SQLLink	The part associated with the current <b>Object Metadata</b> part describes a connection to a SQL database.
Query	The part associated with the current <b>Object Metadata</b> part describes a query.
Form	The part associated with the current <b>Object Metadata</b> part describes a form.
Report	The part associated with the current <b>Object Metadata</b> part describes a report.
Macro	The part associated with the current <b>Object Metadata</b> part describes a workflow.
Module	The part associated with the current <b>Object Metadata</b> part describes a programming language source code.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xsd:simpleType name="ST_Type">
```

```

<xsd:restriction base="xsd:string">
  <xsd:enumeration value="Table"/>
  <xsd:enumeration value="Link"/>
  <xsd:enumeration value="SQLLink"/>
  <xsd:enumeration value="Query"/>
  <xsd:enumeration value="Form"/>
  <xsd:enumeration value="Report"/>
  <xsd:enumeration value="Macro"/>
  <xsd:enumeration value="Module"/>
</xsd:restriction>
</xsd:simpleType>

```

## 2.4 List Schema

The **List Schema** is determined by a series of SOAP requests made to the **Lists** web service as specified by [\[MS-LISTSWS\]](#). The requests are appended together and stored in the **List Definition** part (section [2.1.4.11](#)).

The **List Schema** MUST contain only **AddList** requests, as specified by [\[MS-LISTSWS\]](#) section 3.1.4.3, and **UpdateList** requests, as specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.

The **List Schema** MUST contain at least one **AddList** request. Each **UpdateList** request MUST contain a **listProperties** element, **newFields** element, and **updateFields** element, in that order, as specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.2.1.

The format of the **List Schema** SHOULD conform to the following ABNF [\[RFC5234\]](#) grammar:

```

LISTSCHEMADEF = ROOT-OPEN-TAG AddList AddFields AddCalcFields ListProperties
FieldProperties ROOT-CLOSE-TAG
ROOT-OPEN-TAG = "<Root>"
ROOT-CLOSE-TAG = "</Root>"

```

### 2.4.1 Add Calculated Fields

This element is a SOAP request to add **calculated fields** to the list (1) created in **AddList** (section [2.4.3](#)) by calling the **UpdateList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.

Each **field (3)** to be added MUST have an entry under the **newFields** element as specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.2.1.

### 2.4.2 Add Fields

The **Add Fields** element is a SOAP request to add fields (3) to the list (1) created in **AddList** (section [2.4.3](#)) by calling the **UpdateList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.30. It also modifies fields (3) that were created by default in the list (1) as specified by the **templateID** in **AddList**.

Each field (3) to be added MUST have an entry under the **newFields** element as specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.2.1, with the exception of fields (3) specified under the **AddCalcFields** (section [2.4.1](#)) element.

Each field (3) to be modified MUST have an entry under the **updateFields** element.



### 2.4.3 Add List

The **Add List** element is a SOAP request that creates a new list (1) by calling the **AddList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.3.

The **listName** and **templateID** elements MUST be specified. All other values are ignored.

### 2.4.4 Field Properties

The **Field Properties** element is a SOAP request to modify the properties of fields (3) in the list (1) created in **AddList** (section [2.4.3](#)) by calling the **UpdateList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.

Each field (3) to be modified MUST have an entry under the **updateFields** element.

### 2.4.5 List Properties

The **List Properties** element is a SOAP request to modify properties of the list (1) created in **AddList** (section [2.4.3](#)) by calling the **UpdateList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.30. Any properties of the list (1) not set during **AddList** MUST be set as part of this request.

## 2.5 List Data

**List Data** describes a set of **list items** for a particular list (1) schema as XML. This XML contains an inline schema that describes the shape of the list items. When **List Data** is used as the contents of a **Table Data** part (section [2.1.4.22](#)), the schema included in this XML MUST describe the same list items as the **List Schema** in the related **List Definition** part (section [2.1.4.11](#)).

The format of this XML MUST conform to the following ABNF [\[RFC5234\]](#) grammar:

```
LISTDATADEF = ROOT-OPEN-TAG SCHEMA DATAINSTANCE ROOT-CLOSE-TAG
ROOT-OPEN-TAG = "<root xmlns:xsd=\"\" SCHEMA-NAMESPACE \"\" xmlns:od=\"\"          OD-NAMESPACE
\"\">"
SCHEMA-NAMESPACE = "http://www.w3.org/2001/XMLSchema"
OD-NAMESPACE = "urn:schemas-microsoft-com:officedata"
ROOT-CLOSE-TAG = "</root>"
```

### 2.5.1 Data Instance

**Data Instance** is XML that describes the data contained in the list (1). This XML MUST be an XML document that conforms to the schema specified by the **Schema** section (section [2.5.2](#)). Each child element of the **Data Instance** SHOULD represent a single list item in the list (1).

### 2.5.2 Schema

**Schema** MUST be an XML Schema Definition (XSD), as specified by [\[XMLSCHEMA2\]](#), that defines the schema of the **Data Instance** (section [2.5.1](#)). The elements and attributes corresponding to the namespace "urn:schemas-microsoft-com:officedata" MUST be ignored.

## 3 Structure Examples

### 3.1 List Schema

The following example uses the contents of a **List Definition** part (section [2.1.4.11](#)) to create a list (1) called Contacts with the following fields (3):

- **ID** (A field (3) of data type **Autonumber**)
- **Company** (A field (3) of data type **Text**)
- Last Name (A field (3) of data type **Text**)
- First Name (A field (3) of data type **Text**)

The **List Schema** (section [2.4](#)) is a collection of SOAP calls of the following form:

```
LISTSCHEMADEF = ROOT-OPEN-TAG AddList AddFields AddCalcFields ListProperties  
FieldProperties ROOT-CLOSE-TAG
```

The ROOT-OPEN-TAG is as follows:

```
<Root>
```

The ROOT-CLOSE-TAG is as follows:

```
</Root>
```

**AddList** (section [2.4.3](#)) consists of the following SOAP request that creates a list (1) named Contacts by calling the **AddList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.3.

```
<Envelope xmlns="http://schemas.xmlsoap.org/soap/envelope/">  
  <Body>  
    <AddList xmlns="http://schemas.microsoft.com/sharepoint/soap/">  
      <listName>Contacts</listName>  
      <description/>  
      <templateID>105</templateID>  
    </AddList>  
  </Body>  
</Envelope>
```

**AddFields** (section [2.4.2](#)) consists of the following SOAP request that adds fields (3) to the list (1) by calling the **UpdateList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.

```
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"  
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"  
  xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">  
  <soap:Body>  
    <UpdateList xmlns="http://schemas.microsoft.com/sharepoint/soap/">  
      <listName>{BC5B1011-A346-43D8-A949-A99C845DEF26}</listName>  
      <listProperties>
```

```

        <List EnableAttachments="FALSE" CalculatedFieldBehavior="PreserveEmptyValues"
EnforceDataValidation="TRUE"/>
    </listProperties>
    <newFields>
        <Fields>
            <Method ID="10" AddToView="">
                <Field DisplayName="Company" Type="Text">
                    <ValidationDisplayNames/>
                </Field>
            </Method>
            <Method ID="11" AddToView="">
                <Field DisplayName="Last Name" Type="Text">
                    <ValidationDisplayNames/>
                </Field>
            </Method>
            <Method ID="12" AddToView="">
                <Field DisplayName="First Name" Type="Text">
                    <ValidationDisplayNames/>
                </Field>
            </Method>
            <Method ID="13" AddToView="">
                <Field DisplayName="_OldID" Type="Number" Decimals="0">
                    <ValidationDisplayNames/>
                </Field>
            </Method>
        </Fields>
    </newFields>
    <updateFields>
        <Fields>
            <Method ID="14">
                <Field Type="Text" Calculated="FALSE" Name="Title"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="Title" ColName="nvarchar1"
DisplayName="SharePointTitle" Hidden="TRUE" FromBaseType="FALSE" Required="FALSE">
                    <ValidationDisplayNames/>
                </Field>
            </Method>
            <Method ID="15">
                <Field Type="Counter" Calculated="FALSE" ColName="tp_ID" RowOrdinal="0"
ReadOnly="TRUE" Name="ID" PrimaryKey="TRUE"
SourceID="http://schemas.microsoft.com/sharepoint/v3" StaticName="ID" FromBaseType="TRUE"
DisplayName="ID">
                    <ValidationDisplayNames/>
                </Field>
            </Method>
        </Fields>
    </updateFields>
    <deleteFields>
        <Fields>
        </Fields>
    </deleteFields>
    <listVersion>0</listVersion>
</UpdateList>
</soap:Body>
</soap:Envelope>

```

In this example, the `_OLDID`, `Company`, `Last Name` and `First Name` fields (3) each have an entry under the **newFields** element. There is also an entry under the **updateFields** element for each field (3) in the list (1) that is created with template identifier 105.

The **ListName** element contains an arbitrary GUID for the list (1) name. It is assumed that all requests to the **List** service are intended to work on the list (1) created by the **AddList** request.

**AddCalcFields** (section [2.4.1](#)) is not present because the list (1) in this example does not contain any calculated columns.

**ListProperties** (section [2.4.5](#)) consists of the following SOAP request which modifies fields (3) in the list (1) by calling the **UpdateList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.

```
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <UpdateList xmlns="http://schemas.microsoft.com/sharepoint/soap/">
      <listName>{BC5B1011-A346-43D8-A949-A99C845DEF26}</listName>
      <listProperties>
        <List Direction="ltr"/>
      </listProperties>
      <newFields>
        <Fields>
        </Fields>
      </newFields>
      <updateFields>
        <Fields>
        </Fields>
      </updateFields>
      <deleteFields>
        <Fields>
        </Fields>
      </deleteFields>
      <listVersion>0</listVersion>
    </UpdateList>
  </soap:Body>
</soap:Envelope>
```

The **List Direction** property is set to "ltr" for the list (1). None of the fields (3) are modified; hence there is no field (3) entry under the **updateFields** element.

The **Field Properties** (section [2.4.4](#)) consists of the following SOAP request which modifies properties of the list (1) by calling the **UpdateList** method of the **Lists** web service specified by [\[MS-LISTSWS\]](#) section 3.1.4.30.

```
<soap:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
  <soap:Body>
    <UpdateList xmlns="http://schemas.microsoft.com/sharepoint/soap/">
      <listName>{BC5B1011-A346-43D8-A949-A99C845DEF26}</listName>
      <listProperties>
        <List/>
      </listProperties>
      <newFields>
        <Fields>
        </Fields>
      </newFields>
      <updateFields>
```

```

<Fields>
  <Method ID="16">
    <Field DisplayName="Company" Type="Text" MaxLength="50">
      <ValidationDisplayNames/>
    </Field>
  </Method>
  <Method ID="17">
    <Field DisplayName="Last Name" Type="Text" MaxLength="50">
      <ValidationDisplayNames/>
    </Field>
  </Method>
  <Method ID="18">
    <Field DisplayName="First Name" Type="Text" MaxLength="50">
      <ValidationDisplayNames/>
    </Field>
  </Method>
</Fields>
</updateFields>
<deleteFields>
  <Fields>
  </Fields>
</deleteFields>
<listVersion>0</listVersion>
</UpdateList>
</soap:Body>
</soap:Envelope>

```

The **Type** property is set to "Text" and the **MaxLength** property is set to "50" for the **Company**, **Last Name** and **First Name** fields (3).

All these requests are appended together and stored in the **List Definition** part (section [2.1.4.11](#)).

### 3.2 List Data

In this example, the following is assumed.

When the template is instantiated, a database application is created that contains a list (1) called Contacts, with the following fields (3) and sample data.

ID	Company	Last Name	First Name
1	Contoso	John	Smith
2	Contoso	Jane	Doe

The **List Data** element (section [2.5](#)) is of the following form:

```
LISTDATADEF = ROOT-OPEN-TAG SCHEMA DATAINSTANCE ROOT-CLOSE-TAG
```

The ROOT-OPEN-TAG is as follows:

```
<root xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:od="urn:schemas-microsoft-com:officedata">
```

The ROOT-CLOSE-TAG is as follows:

```
</root>
```

The **SCHEMA** (section [2.5.2](#)) XML is an XSD that defines the schema of the list (1) is as follows:

```
<xsd:schema>
  <xsd:element name="dataroot">
    <xsd:complexType>
      <xsd:sequence>
        <xsd:element ref="Contacts" minOccurs="0" maxOccurs="unbounded"/>
      </xsd:sequence>
      <xsd:attribute name="generated" type="xsd:dateTime"/>
    </xsd:complexType>
  </xsd:element>
  <xsd:element name="Contacts">
    <xsd:annotation>
      <xsd:appinfo />
    </xsd:annotation>
    <xsd:complexType>
      <xsd:sequence>
        <xsd:element name="ID" minOccurs="1" type="xsd:int">
          <xsd:annotation>
            <xsd:appinfo />
          </xsd:annotation>
        </xsd:element>
        <xsd:element name="Company" minOccurs="0">
          <xsd:annotation>
            <xsd:appinfo />
          </xsd:annotation>
          <xsd:simpleType>
            <xsd:restriction base="xsd:string">
              <xsd:maxLength value="50"/>
            </xsd:restriction>
          </xsd:simpleType>
        </xsd:element>
        <xsd:element name="Last_x0020_Name" minOccurs="0">
          <xsd:annotation>
            <xsd:appinfo />
          </xsd:annotation>
          <xsd:simpleType>
            <xsd:restriction base="xsd:string">
              <xsd:maxLength value="50"/>
            </xsd:restriction>
          </xsd:simpleType>
        </xsd:element>
        <xsd:element name="First_x0020_Name" minOccurs="0">
          <xsd:annotation>
            <xsd:appinfo />
          </xsd:annotation>
          <xsd:simpleType>
            <xsd:restriction base="xsd:string">
              <xsd:maxLength value="50"/>
            </xsd:restriction>
          </xsd:simpleType>
        </xsd:element>
      </xsd:sequence>
    </xsd:complexType>
  </xsd:element>
</xsd:schema>
```

```
</xsd:element>
</xsd:schema>
```

Note that the following elements and attributes corresponding to the namespace "urn:schemas-microsoft-com:officedata" are ignored.

```
<od:index index-name="Company" index-key="Company " primary="no" unique="no" clustered="no"
order="asc"/>
<od:index index-name="First Name" index-key="First_x0020_Name " primary="no" unique="no"
clustered="no" order="asc"/>
<od:index index-name="Last Name" index-key="Last_x0020_Name " primary="no" unique="no"
clustered="no" order="asc"/>
<od:index index-name="PrimaryKey" index-key="ID " primary="yes" unique="yes" clustered="no"
order="asc"/>
<od:tableProperty name="Orientation" type="2" value="0"/>
<od:tableProperty name="OrderByOn" type="1" value="0"/>
<od:tableProperty name="DefaultView" type="2" value="2"/>
<od:tableProperty name="WSSTemplateID" type="3" value="105"/>
<od:tableProperty name="TotalsRow" type="1" value="0"/>
<od:tableProperty name="FilterOnLoad" type="1" value="0"/>
<od:tableProperty name="OrderByOnLoad" type="1" value="1"/>
<od:tableProperty name="DisplayViewsOnSharePointSite" type="2" value="1"/>
<od:tableProperty name="StarColumnHidden" type="1" value="0"/>
<od:tableProperty name="HideNewField" type="1" value="0"/>
<od:tableProperty name="NameMap" type="11"
value="CswOVQAAAAATEHe+VQ/oRowbCBVNjaoaAAAAAClEms2geNAAAAAAAAAAAAABDAG8A
bgB0AGEAYwB0AHMAAAAAAAAAAeMjPgNpkFEOIk4IGF6kygAcAAAAATEHe+VQ/oRowb
CBVNjaoaSQBEAAAAAAAAAAS3eiieomNGsks5h00T0EMHAAAAExB3v1UP6EaMGwgV
TY2qGkMAbwBtAHAAYQBuaHkAAAAAAAAAqeqqJhCDiUqnFm4HUasmhgcAAAAATEHe+
VQ/oRowbCBVNjaoaTABhAHMadaAgAE4AYQBtAGUAAAAAAAAAovBS5cL12E2owB8/
WqhFVgcAAAAATEHe+VQ/oRowbCBVNjaoaRgBpAHIAcwb0ACAATgBhAG0AZQAAAAAA
AAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAAA==
"/>
<od:tableProperty name="SubdatasheetName" type="10" value="[Auto]"/>
<od:tableProperty name="GUID" type="9" value="ExB3v1UP6EaMGwgVTY2qGg==
"/>
<od:tableProperty name="BackTint" type="6" value="100"/>
<od:tableProperty name="BackShade" type="6" value="100"/>
<od:tableProperty name="ThemeFontIndex" type="4" value="-1"/>
<od:tableProperty name="AlternateBackThemeColorIndex" type="4" value="-1"/>
<od:tableProperty name="AlternateBackTint" type="6" value="100"/>
<od:tableProperty name="AlternateBackShade" type="6" value="100"/>
<od:tableProperty name="ReadOnlyWhenDisconnected" type="1" value="0"/>
<od:tableProperty name="WaitForPostProcessing" type="1" value="0"/>
<od:tableProperty name="DatasheetGridlinesThemeColorIndex" type="4" value="-1"/>
<od:tableProperty name="DatasheetGridlinesTint" type="6" value="100"/>
<od:tableProperty name="DatasheetGridlinesShade" type="6" value="100"/>
<od:tableProperty name="DatasheetForeThemeColorIndex" type="4" value="-1"/>
<od:tableProperty name="DatasheetForeTint" type="6" value="100"/>
<od:tableProperty name="DatasheetForeShade" type="6" value="100"/>
<od:tableProperty name="PublishToWeb" type="2" value="2"/>

<od:fieldProperty name="ColumnWidth" type="3" value="960"/>
<od:fieldProperty name="ColumnOrder" type="3" value="1"/>
<od:fieldProperty name="ColumnHidden" type="1" value="0"/>
<od:fieldProperty name="WSSFieldID" type="10" value="ID"/>
<od:fieldProperty name="AggregateType" type="4" value="-1"/>
<od:fieldProperty name="RowSourceType" type="10" value="Table/Query"/>
```

```

<od:fieldProperty name="BoundColumn" type="3" value="1"/>
<od:fieldProperty name="ColumnCount" type="3" value="1"/>
<od:fieldProperty name="ColumnHeads" type="1" value="0"/>
<od:fieldProperty name="AllowValueListEdits" type="1" value="0"/>
<od:fieldProperty name="TextAlign" type="2" value="0"/>
<od:fieldProperty name="ShowOnlyRowSourceValues" type="1" value="0"/>
<od:fieldProperty name="GUID" type="9" value="eMJpgNpkFEOIk4IGF6kygA=="
"/>
<od:fieldProperty name="ResultType" type="2" value="0"/>

<od:fieldProperty name="ColumnWidth" type="3" value="-1"/>
<od:fieldProperty name="ColumnOrder" type="3" value="0"/>
<od:fieldProperty name="ColumnHidden" type="1" value="0"/>
<od:fieldProperty name="Required" type="1" value="0"/>
<od:fieldProperty name="AllowZeroLength" type="1" value="0"/>
<od:fieldProperty name="DisplayControl" type="3" value="109"/>
<od:fieldProperty name="IMEMode" type="2" value="0"/>
<od:fieldProperty name="IMESentenceMode" type="2" value="0"/>
<od:fieldProperty name="UnicodeCompression" type="1" value="1"/>
<od:fieldProperty name="TextAlign" type="2" value="0"/>
<od:fieldProperty name="AggregateType" type="4" value="-1"/>
<od:fieldProperty name="WSSFieldID" type="10" value="Company"/>
<od:fieldProperty name="GUID" type="9" value="BLd6KJ6iY0aySzmE7RPQW=="
"/>
<od:fieldProperty name="ResultType" type="2" value="0"/>

<od:fieldProperty name="ColumnWidth" type="3" value="-1"/>
<od:fieldProperty name="ColumnOrder" type="3" value="0"/>
<od:fieldProperty name="ColumnHidden" type="1" value="0"/>
<od:fieldProperty name="Required" type="1" value="0"/>
<od:fieldProperty name="AllowZeroLength" type="1" value="0"/>
<od:fieldProperty name="DisplayControl" type="3" value="109"/>
<od:fieldProperty name="IMEMode" type="2" value="0"/>
<od:fieldProperty name="IMESentenceMode" type="2" value="0"/>
<od:fieldProperty name="UnicodeCompression" type="1" value="1"/>
<od:fieldProperty name="TextAlign" type="2" value="0"/>
<od:fieldProperty name="AggregateType" type="4" value="-1"/>
<od:fieldProperty name="WSSFieldID" type="10" value="Title"/>
<od:fieldProperty name="GUID" type="9" value="qeqqJhCDiUqnFm4HUasmhg=="
"/>

<od:fieldProperty name="ColumnWidth" type="3" value="-1"/>
<od:fieldProperty name="ColumnOrder" type="3" value="0"/>
<od:fieldProperty name="ColumnHidden" type="1" value="0"/>
<od:fieldProperty name="Required" type="1" value="0"/>
<od:fieldProperty name="AllowZeroLength" type="1" value="0"/>
<od:fieldProperty name="DisplayControl" type="3" value="109"/>
<od:fieldProperty name="IMEMode" type="2" value="0"/>
<od:fieldProperty name="IMESentenceMode" type="2" value="0"/>
<od:fieldProperty name="UnicodeCompression" type="1" value="1"/>
<od:fieldProperty name="TextAlign" type="2" value="0"/>
<od:fieldProperty name="AggregateType" type="4" value="-1"/>
<od:fieldProperty name="WSSFieldID" type="10" value="FirstName"/>
<od:fieldProperty name="GUID" type="9" value="ovBS5cLl2E2owB8/WqhFVg=="
"/>
<od:fieldProperty name="ResultType" type="2" value="0"/>

```

The **Data Instance** (section [2.5.1](#)) XML that describes the data contained in the list (1) is as follows:



```

<dataroot xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" generated="2009-05-
14T12:06:59">
  <Contacts>
    <ID>1</ID>
    <Company>Contoso</Company>
    <Last_x0020_Name>John</Last_x0020_Name>
    <First_x0020_Name>Smith</First_x0020_Name>
  </Contacts>
  <Contacts>
    <ID>2</ID>
    <Company>Contoso</Company>
    <Last_x0020_Name>Jane</Last_x0020_Name>
    <First_x0020_Name>Doe</First_x0020_Name>
  </Contacts>
</dataroot>

```

Note that the preceding XML is an instance of the schema of the list (1) as specified by the **Schema**.

### 3.3 Images

In this example, the database template contains a definition of **Form** ([\[MS-AXL\]](#) section 2.1.2) that contains a **Shared Image** ([\[MS-AXL\]](#) section 2.1.6) of type **Image** (section [2.1.4.6](#)).

The following figure shows the **Image** in the **Form**:



**Figure 1: Shared Resource Image in Form**

The following **Image** exists with the file name FormLogo-2-name.jpg:



**Figure 2: Image FormLogo-2-name.jpg**

A **Resource** part (section [2.1.4.21](#)) named FormLogo-2-name.txt contains the name of the shared resource **Image**. The contents of FormLogo-2-name.txt are as follows:

Form Logo

The **Template Metadata** (section [2.2](#)) **Part** (section [2.1.2](#)) contains an entry in **Relationship** (section [2.1.4.19](#)) **Part** called `template.xml.rels`, where `FormLogo-2-name.jpg` is the target. The XML for the **Relationship** is as follows:

```
<Relationship Id="FormLogo-2"  
Type="http://schemas.microsoft.com/office/2007/relationships/shared-image"  
Target="database/resources/FormLogo-2.jpg" />
```

The **Resource Part** contains an entry in **Relationship Part** called `FormLogo-2.jpg.rels`, where `FormLogo-2-name.txt` is the target. The XML for the **Relationship** is as follows:

```
<Relationship Id="name"  
Type="http://schemas.microsoft.com/office/2007/relationships/resource-name" Target="FormLogo-  
2-name.txt" />
```

## **4 Security**

### **4.1 Security Considerations for Implementers**

None.

### **4.2 Index of Security Fields**

None.

## 5 Appendix A: Full XML Schemas

For ease of implementation, the following sections provide the full syntax for this protocol.

Schema name	prefix	Section
<a href="http://schemas.microsoft.com/office/access/2005/04/template/start">http://schemas.microsoft.com/office/access/2005/04/template/start</a>	Unassigned	Section <a href="#">5.1</a>
<a href="http://schemas.microsoft.com/office/access/2005/04/template/object-metadata">http://schemas.microsoft.com/office/access/2005/04/template/object-metadata</a>	Unassigned	Section <a href="#">5.2</a>

### 5.1 <http://schemas.microsoft.com/office/access/2005/04/template/start> Schema

```
<xsd:schema
  targetNamespace="http://schemas.microsoft.com/office/access/2005/04/template/start"
  xmlns="http://schemas.microsoft.com/office/access/2005/04/template/start"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">
  <xsd:complexType name="CT_Template">
    <xsd:sequence>
      <xsd:element name="TemplateFormat" type="xsd:unsignedInt" minOccurs="0" />
      <xsd:element name="FlipRightToLeft" type="xsd:unsignedInt" />
      <xsd:element name="PerformLocalizationFixup" type="xsd:unsignedInt" />
      <xsd:element name="CollatingOrder" type="xsd:unsignedInt" minOccurs="0" />
      <xsd:element name="DataLocale" type="xsd:unsignedInt" minOccurs="0" />
      <xsd:element name="UILocale" type="xsd:unsignedInt" minOccurs="0" />
      <xsd:element name="RequiredAccessVersion" type="xsd:string" />
      <xsd:element name="AccessServicesVersion" type="xsd:string" />
      <xsd:element name="Type" type="xsd:string" />
      <xsd:element name="PerformFontFixup" type="xsd:unsignedInt" minOccurs="0" />
      <xsd:element name="VariationIdentifier" type="xsd:string" minOccurs="0" />
    </xsd:sequence>
  </xsd:complexType>
  <xsd:element name="Template" type="CT_Template" />
</xsd:schema>
```

### 5.2 <http://schemas.microsoft.com/office/access/2005/04/template/object-metadata> Schema

```
<xsd:schema
  targetNamespace="http://schemas.microsoft.com/office/access/2005/04/template/object-metadata"
  xmlns="http://schemas.microsoft.com/office/access/2005/04/template/object-metadata"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  elementFormDefault="qualified">
  <xsd:simpleType name="ST_Type">
    <xsd:restriction base="xsd:string">
      <xsd:enumeration value="Table" />
      <xsd:enumeration value="Link" />
      <xsd:enumeration value="SQLLink" />
      <xsd:enumeration value="Query" />
      <xsd:enumeration value="Form" />
      <xsd:enumeration value="Report" />
      <xsd:enumeration value="Macro" />
    </xsd:restriction>
  </xsd:simpleType>
</xsd:schema>
```

```
    <xsd:enumeration value="Module" />
  </xsd:restriction>
</xsd:simpleType>
<xsd:complexType name="CT_NameMap">
  <xsd:sequence>
    <xsd:any maxOccurs="unbounded" />
  </xsd:sequence>
</xsd:complexType>
<xsd:complexType name="CT_AccessObject">
  <xsd:sequence>
    <xsd:element name="Type" type="ST_Type" />
    <xsd:element name="Name" type="xsd:string" />
    <xsd:element name="NameMap" type="CT_NameMap" minOccurs="0" />
  </xsd:sequence>
</xsd:complexType>
<xsd:element name="AccessObject" type="CT_AccessObject" />
</xsd:schema>
```

## 6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Access 2010
- Microsoft SharePoint Server 2010
- Microsoft Access 2013
- Microsoft SharePoint Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 7 Change Tracking

This section identifies changes that were made to the [MS-ACCDT] protocol document between the February 2014 and April 2014 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">2.2.3.1 CT Template</a>	In the schema fragment, changed the type of the AccessServicesVersion element from "CT_AccessServicesVersion" to "xsd:string".	N	Content updated.



## 8 Index

[/template/object-metadata schema](#) 36  
[/template/start schema](#) 36

### A

[AccessObject global element](#) 22  
[Add calculated fields list schema](#) 24  
[Add fields list schema](#) 24  
[Add list list schema](#) 25  
[Applicability](#) 8  
[Application properties part enumeration](#) 12

### C

[Change tracking](#) 39  
Complex types ([section 2.2.3](#) 21, [section 2.3.3](#) 22)  
    [CT AccessObject](#) 22  
    [CT NameMap](#) 22  
    [CT Template](#) 21  
[CT AccessObject complex type](#) 22  
[CT NameMap complex type](#) 22  
[CT Template complex type](#) 21

### D

[Data instance list data](#) 25  
[Data macro part enumeration](#) 12

### E

Examples  
    [Images](#) 33  
    [List Data](#) 29  
    [List Schema](#) 26

### F

[Field properties list schema](#) 25  
[Fields - security index](#) 35  
[Fields - vendor-extensible](#) 9  
File properties  
    [core part enumeration](#) 13  
[File structure](#) 10  
    [package](#) 10  
    [part](#) 10  
    [part enumeration](#) 11  
    [relationship](#) 10  
[Form part enumeration](#) 13  
[Full XML schema](#) 36

### G

Global attributes ([section 2.2.2](#) 20, [section 2.3.2](#) 22)  
Global elements ([section 2.2.1](#) 20, [section 2.3.1](#) 22)  
    [AccessObject](#) 22  
    [template](#) 20  
[Glossary](#) 6

### I

[Icon part enumeration](#) 13  
[Image cluster part enumeration](#) 14  
[Image part enumeration](#) 14  
[Images example](#) 33  
[Implementer - security considerations](#) 35  
[Index of security fields](#) 35  
[Informative references](#) 7  
[Instantiation form part enumeration](#) 15  
[Introduction](#) 6

### L

[Legacy application properties part enumeration](#) 15  
[Linked table part enumeration](#) 15  
[List data](#) 25  
    [data instance](#) 25  
    [schema](#) 25  
[List Data example](#) 29  
[List definition part enumeration](#) 15  
[List properties list schema](#) 25  
[List schema](#) 24  
    [add calculated fields](#) 24  
    [add fields](#) 24  
    [add list](#) 25  
    [field properties](#) 25  
    [list properties](#) 25  
[List Schema example](#) 26  
[Localization](#) 8

### M

[Macro part enumeration](#) 16

### N

[Navigation pane part enumeration](#) 16  
[Normative references](#) 6

### O

[Object metadata](#) 22  
    [complex types](#) 22  
    [global attributes](#) 22  
    [global elements](#) 22  
    [simple types](#) 23  
[Object metadata part enumeration](#) 17  
[Object part enumeration](#) 16  
[Object properties part enumeration](#) 17  
[Overview \(synopsis\)](#) 7

### P

[Package structure](#) 10  
Part enumeration  
    [application properties](#) 12

- [data macro](#) 12
- file properties
  - [core](#) 13
- [form](#) 13
- [icon](#) 13
- [image](#) 14
- [imaged cluster](#) 14
- [instantiation form](#) 15
- [legacy application properties](#) 15
- [linked table](#) 15
- [list definition](#) 15
- [macro](#) 16
- [navigation pane](#) 16
- [object](#) 16
- [object metadata](#) 17
- [object properties](#) 17
- [preview image](#) 17
- [query](#) 18
- [relationship](#) 18
- [report](#) 18
- [resource](#) 19
- [table data](#) 19
- [template metadata](#) 19
- [theme](#) 19
- [variation](#) 20
- [visual basic references](#) 20
- [Part enumeration structure](#) 11
- [Part structure](#) 10
- [Preview image part enumeration](#) 17
- [Product behavior](#) 38

## Q

- [Query part enumeration](#) 18

## R

- [References](#) 6
  - [informative](#) 7
  - [normative](#) 6
- [Relationship part enumeration](#) 18
- [Relationship structure](#) 10
- [Relationship to protocols and other structures](#) 8
- [Report part enumeration](#) 18
- [Resource part enumeration](#) 19

## S

- [Schema list data](#) 25
- Security
  - [field index](#) 35
  - [implementer considerations](#) 35
- Simple types ([section 2.2.4](#) 22, [section 2.3.4](#) 23)
  - [ST\\_Type](#) 23
- [ST\\_Type simple type](#) 23
- Structures
  - [file structure](#) 10
  - [list data](#) 25
  - [list schema](#) 24
  - [object metadata](#) 22
  - [template metadata](#) 20

## T

- [Table data part enumeration](#) 19
- [Template global element](#) 20
- [Template metadata](#) 20
  - [complex types](#) 21
  - [global attributes](#) 20
  - [global elements](#) 20
  - [simple types](#) 22
- [Template metadata part enumeration](#) 19
- [Theme part enumeration](#) 19
- [Tracking changes](#) 39

## V

- [Variation part enumeration](#) 20
- [Vendor-extensible fields](#) 9
- [Versioning](#) 8
- [Visual basic references part enumeration](#) 20

## X

- [XML schema](#) 36
- XML schemas
  - [.../template/object-metadata](#) 36
  - [.../template/start](#) 36