

[MS-ASAIRS]: ActiveSync AirSyncBase Namespace Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
12/03/2008	1.0	Major	Initial Release.
03/04/2009	1.0.1	Editorial	Revised and edited technical content.
04/10/2009	2.0	Major	Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	3.0.2	Editorial	Updated the technical content.
05/05/2010	4.0.0	Major	Updated and revised the technical content.
08/04/2010	5.0	Major	Significantly changed the technical content.
11/03/2010	6.0	Major	Significantly changed the technical content.
03/18/2011	7.0	Major	Significantly changed the technical content.
08/05/2011	7.1	Minor	Clarified the meaning of the technical content.
10/07/2011	7.2	Minor	Clarified the meaning of the technical content.
01/20/2012	8.0	Major	Significantly changed the technical content.
04/27/2012	8.1	Minor	Clarified the meaning of the technical content.
07/16/2012	9.0	Major	Significantly changed the technical content.

Table of Contents

1 Introduction	5
1.1 Glossary	5
1.2 References	5
1.2.1 Normative References	5
1.2.2 Informative References	6
1.3 Overview	6
1.4 Relationship to Other Protocols	6
1.5 Prerequisites/Preconditions	7
1.6 Applicability Statement	7
1.7 Versioning and Capability Negotiation	7
1.8 Vendor-Extensible Fields	7
1.9 Standards Assignments	7
2 Messages	8
2.1 Transport	8
2.2 Message Syntax	8
2.2.1 Namespaces	10
2.2.2 Elements	10
2.2.2.1 AllOrNone	12
2.2.2.1.1 AllOrNone (BodyPartPreference)	12
2.2.2.1.2 AllOrNone (BodyPreference)	13
2.2.2.2 Attachment	14
2.2.2.3 Attachments	14
2.2.2.4 Body	14
2.2.2.5 BodyPart	15
2.2.2.6 BodyPartPreference	15
2.2.2.7 BodyPreference	16
2.2.2.8 ContentId	16
2.2.2.9 ContentLocation	17
2.2.2.10 Data	17
2.2.2.10.1 Data (Body)	17
2.2.2.10.2 Data (BodyPart)	17
2.2.2.11 DisplayName	18
2.2.2.12 EstimatedDataSize	18
2.2.2.12.1 EstimatedDataSize (Attachment)	18
2.2.2.12.2 EstimatedDataSize (Body)	18
2.2.2.12.3 EstimatedDataSize (BodyPart)	18
2.2.2.13 FileReference	19
2.2.2.13.1 FileReference (Attachment)	19
2.2.2.13.2 FileReference (Fetch)	19
2.2.2.14 IsInline	19
2.2.2.15 Method	19
2.2.2.16 NativeBodyType	20
2.2.2.17 Part	20
2.2.2.18 Preview	20
2.2.2.18.1 Preview (Body)	21
2.2.2.18.2 Preview (BodyPart)	21
2.2.2.18.3 Preview (BodyPartPreference)	21
2.2.2.18.4 Preview (BodyPreference)	21
2.2.2.19 Status	22

2.2.2.20	Truncated	22
2.2.2.20.1	Truncated (Body)	22
2.2.2.20.2	Truncated (BodyPart).....	22
2.2.2.21	TruncationSize.....	22
2.2.2.21.1	TruncationSize (BodyPartPreference)	23
2.2.2.21.2	TruncationSize (BodyPreference).....	23
2.2.2.22	Type	23
2.2.2.22.1	Type (Body).....	23
2.2.2.22.2	Type (BodyPart).....	24
2.2.2.22.3	Type (BodyPartPreference)	24
2.2.2.22.4	Type (BodyPreference).....	24
2.2.3	Groups.....	24
2.2.3.1	TopLevelSchemaProps.....	24
3	Protocol Details	25
3.1	Client Details.....	25
3.1.1	Abstract Data Model	25
3.1.2	Timers	25
3.1.3	Initialization	25
3.1.4	Higher-Layer Triggered Events.....	25
3.1.5	Message Processing Events and Sequencing Rules.....	25
3.1.5.1	Commands	25
3.1.5.1.1	ItemOperations.....	25
3.1.5.1.2	Search.....	26
3.1.5.1.3	Sync.....	26
3.1.6	Timer Events	26
3.1.7	Other Local Events	27
3.2	Server Details	27
3.2.1	Abstract Data Model	27
3.2.2	Timers	27
3.2.3	Initialization	27
3.2.4	Higher-Layer Triggered Events.....	27
3.2.5	Message Processing Events and Sequencing Rules.....	27
3.2.5.1	Validating XML	27
3.2.5.2	Commands	27
3.2.5.2.1	ItemOperations.....	28
3.2.5.2.2	Search.....	28
3.2.5.2.3	Sync.....	29
3.2.6	Timer Events	30
3.2.7	Other Local Events	30
4	Protocol Examples.....	31
5	Security.....	32
5.1	Security Considerations for Implementers.....	32
5.2	Index of Security Parameters	32
6	Appendix A: Product Behavior	33
7	Change Tracking.....	34
8	Index	36

1 Introduction

The ActiveSync AirSyncBase Namespace Protocol describes the elements in the AirSyncBase namespace, which are used by the commands specified in [\[MS-ASCMD\]](#) to identify the size, type, and content of the data sent by and returned to the client. The AirSyncBase namespace contains elements used in both request and response command messages.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Unicode

The following terms are defined in [\[MS-OXGLOS\]](#):

Attachment object
attachments table
base64 encoding
calendar
Hypertext Markup Language (HTML)
message body
Message object
message part
Object Linking and Embedding (OLE)
plain text
Rich Text Format (RTF)
store
Uniform Resource Identifier (URI)
XML namespace
XML schema
XML schema definition (XSD)

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site,

<http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-ASCMD] Microsoft Corporation, "[ActiveSync Command Reference Protocol Specification](#)".

[MS-ASDTYPE] Microsoft Corporation, "[ActiveSync Data Types](#)".

[MS-AEMAIL] Microsoft Corporation, "[ActiveSync E-Mail Class Protocol Specification](#)".

[MS-ASHTTP] Microsoft Corporation, "[ActiveSync HTTP Protocol Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

1.2.2 Informative References

[MS-ASCAL] Microsoft Corporation, "[ActiveSync Calendar Class Protocol Specification](#)".

[MS-ASCNTC] Microsoft Corporation, "[ActiveSync Contact Class Protocol Specification](#)".

[MS-ASCON] Microsoft Corporation, "[ActiveSync Conversations Protocol Specification](#)".

[MS-ASDOC] Microsoft Corporation, "[ActiveSync Document Class Protocol Specification](#)".

[MS-ASMS] Microsoft Corporation, "[ActiveSync Short Message Service Protocol Specification](#)".

[MS-ASNOTE] Microsoft Corporation, "[ActiveSync Notes Class Protocol Specification](#)".

[MS-ASRM] Microsoft Corporation, "[ActiveSync Rights Management Protocol Specification](#)".

[MS-ASTASK] Microsoft Corporation, "[ActiveSync Tasks Class Protocol Specification](#)".

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

1.3 Overview

The elements specified in the AirSyncBase namespace are used by multiple ActiveSync commands to identify the size, type, and content of data sent by and returned to the client. In order to use the elements in the AirSyncBase namespace, the namespace and elements are included in the command request and response messages as specified in this document.

1.4 Relationship to Other Protocols

The AirSyncBase namespace is used by the following protocols.

- ActiveSync Calendar Class Protocol, described in [\[MS-ASCAL\]](#)
- ActiveSync Command Reference Protocol, described in [\[MS-ASCMD\]](#)

- ActiveSync Contact Class Protocol, described in [\[MS-ASCNTC\]](#)
- ActiveSync Conversations Protocol, described in [\[MS-ASCON\]](#)
- ActiveSync Document Class Protocol, described in [\[MS-ASDOC\]](#)
- ActiveSync E-mail Class Protocol, described in [\[MS-ASEMAIL\]](#)
- ActiveSync Short Message Service Protocol, described in [\[MS-ASMS\]](#)
- ActiveSync Notes Class Protocol, described in [\[MS-ASNOTE\]](#)
- ActiveSync Rights Management Protocol, described in [\[MS-ASRM\]](#)
- ActiveSync Tasks Class Protocol, described in [\[MS-ASTASK\]](#)

The elements in this specification use data types specified in [\[MS-ASDTYPE\]](#).

1.5 Prerequisites/Preconditions

To use the elements in the AirSyncBase namespace, include the namespace in the command request. The namespace is included by adding the following to the command request:

```
<CommandName xmlns:airsyncbase="ClassName:">
```

For a complete example, see [\[MS-ASCMD\]](#) section 4.10.1.1.

1.6 Applicability Statement

This specification applies to the **ItemOperations**, **Search**, and **Sync** commands, as specified in [\[MS-ASCMD\]](#).

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

The **Type** element can be extended to include custom message types. For more details, see section [2.2.2.22.4](#).

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The elements specified in the following sections are sent and received by using the **ItemOperations**, **Search**, and **Sync** commands, as specified in [\[MS-ASCMD\]](#).

2.2 Message Syntax

The AirSyncBase namespace adheres to the following **XML schema definition (XSD)**, using the mechanisms specified in [\[XMLNS\]](#) and [\[XMLSCHEMA1\]](#):

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema
  attributeFormDefault="unqualified"
  xmlns:airsyncbase="AirSyncBase:"
  xmlns:email2="Email2:"
  xmlns:itemoperations="ItemOperations:"
  elementFormDefault="qualified"
  targetNamespace="AirSyncBase:"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns="AirSyncBase:">

  <xs:element name="FileReference" type="xs:string" />
  <xs:element name="BodyPreference">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="Type" type="xs:unsignedByte" />
        <xs:element name="TruncationSize" minOccurs="0" type="xs:unsignedInt" />
        <xs:element name="AllOrNone" minOccurs="0" type="xs:boolean"/>
        <xs:element name="Preview" minOccurs="0">
          <xs:simpleType>
            <xs:restriction base="xs:unsignedInt">
              <xs:minInclusive value="0"/>
              <xs:maxInclusive value="255"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="BodyPartPreference">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="Type">
          <xs:simpleType>
            <xs:restriction base="xs:unsignedByte">
              <xs:minInclusive value="1"/>
              <xs:maxInclusive value="4"/>
            </xs:restriction>
          </xs:simpleType>
        </xs:element>
        <xs:element name="TruncationSize" minOccurs="0" type="xs:unsignedInt" />
        <xs:element name="AllOrNone" minOccurs="0" type="xs:boolean"/>
        <xs:element name="Preview" minOccurs="0">
          <xs:simpleType>
            <xs:restriction base="xs:unsignedInt">
```



```

        <xs:minInclusive value="0"/>
        <xs:maxInclusive value="255"/>
    </xs:restriction>
</xs:simpleType>
</xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="Body">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Type" type="xs:unsignedByte" />
            <xs:element name="EstimatedDataSize" type="xs:unsignedInt" minOccurs="0"/>
            <xs:element name="Truncated" minOccurs="0" type="xs:boolean"/>
            <xs:element name="Data" minOccurs="0" type="xs:string" />
            <xs:element name="Preview" minOccurs="0" type="xs:string" />
            <xs:element ref="itemoperations:Part" minOccurs="0" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="BodyPart">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Status" type="xs:unsignedByte" />
            <xs:element name="Type" type="xs:unsignedByte" />
            <xs:element name="EstimatedDataSize" type="xs:unsignedInt" />
            <xs:element name="Truncated" minOccurs="0" type="xs:boolean"/>
            <xs:element name="Data" minOccurs="0" type="xs:string" />
            <xs:element name="Preview" minOccurs="0" type="xs:string" />
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:element name="Attachments">
    <xs:complexType>
        <xs:sequence>
            <xs:element name="Attachment">
                <xs:complexType>
                    <xs:all>
                        <xs:element name="DisplayName" type="xs:string" minOccurs="0"/>
                        <xs:element name="FileReference" type="xs:string" />
                        <xs:element name="Method" type="xs:unsignedByte" />
                        <xs:element name="EstimatedDataSize" type="xs:unsignedInt" />
                        <xs:element name="ContentId" type="xs:string" minOccurs="0" />
                        <xs:element name="ContentLocation" type="xs:string"
minOccurs="0"/>
                        <xs:element name="IsInline" minOccurs="0" type="xs:boolean"/>
                        <xs:element ref="email2:UmAttDuration" minOccurs="0" />
                        <xs:element ref="email2:UmAttOrder" minOccurs="0" />
                    </xs:all>
                </xs:complexType>
            </xs:element>
        </xs:sequence>
    </xs:complexType>
</xs:element>
<xs:complexType name="EmptyTag"/>
<xs:element name="NativeBodyType" type="xs:unsignedByte" />
<xs:group name="TopLevelSchemaProps">
    <xs:sequence>
        <xs:choice maxOccurs="unbounded">

```

```

<xs:element name="Body" type="airsynbase:EmptyTag"/>
<xs:element name="BodyPart" type="airsynbase:EmptyTag"/>
<xs:element name="Attachments" type="airsynbase:EmptyTag"/>
</xs:choice>
</xs:sequence>
</xs:group>
</xs:schema>

```

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
None	AirSyncBase	
airsync	AirSync	[MS-ASCMD] section 2.2.2.19
email2	Email2	[MS-AEMAIL] section 2.2
itemoperations	ItemOperations	[MS-ASCMD] section 2.2.2.8
search	Search	[MS-ASCMD] section 2.2.2.14
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1]

2.2.2 Elements

The following table summarizes the set of common **XML schema** element definitions defined by this specification. XML schema element definitions that are specific to a particular operation are described with the operation.

Element name	Description
FileReference (section 2.2.2.13.2)	A unique identifier that is assigned by the server to each attachment to a message.
BodyPreference (section 2.2.2.7)	A collection of elements that sets the preference information related to the type and size of information that is returned from searching, synchronizing, or fetching.
Type (section 2.2.2.22.4)	The preferred format type of the body content of the item.
TruncationSize (section 2.2.2.21.2)	Specifies the size, in bytes, of the content that the client wants to search, synchronize, or fetch.
AllOrNone (section 2.2.2.1.2)	Specifies whether to search, synchronize, or retrieve all or none of the content based on the TruncationSize element.
Preview (section 2.2.2.18.4)	The preferred length of the message preview to be returned to the client.
BodyPartPreference (section 2.2.2.6)	A collection of elements that sets the preference information related to the type and size of information that is returned from searching,

Element name	Description
	synchronizing, or fetching a BodyPart .
Type (section 2.2.2.22.3)	The preferred format type of the body part content of the item.
TruncationSize (section 2.2.2.21.1)	Specifies the size, in bytes, of the content that the client wants to search, synchronize, or fetch.
AllOrNone (section 2.2.2.1.1)	Specifies whether to search, synchronize, or retrieve all or none of the content based on the TruncationSize element.
Preview (section 2.2.2.18.3)	The preferred length of the message preview to be returned to the client.
Body (section 2.2.2.4)	A collection of elements that specifies a free-form, variable-length data field associated with a stored item on the server.
Type (section 2.2.2.22.1)	The format type of the body content of the item.
EstimatedDataSize (section 2.2.2.12.2)	An informational estimate of the size of the data associated with the item's Body element.
Truncated (section 2.2.2.20.1)	Specifies whether the body of the item has been truncated according to the BodyPreference element indicated by the client.
Data (section 2.2.2.10.1)	The body of the calendar item, contact, document, e-mail, or task.
Preview (section 2.2.2.18.1)	The length of the message preview to be returned to the client.
Part (section 2.2.2.17)	The integer index into the metadata of the multipart response.
BodyPart (section 2.2.2.5)	A collection of elements that contains the message part of the body of an e-mail.
Status (section 2.2.2.19)	The status of the Data element within the BodyPart response.
Type (section 2.2.2.22.2)	The format type of the body part content of the item.
EstimatedDataSize (section 2.2.2.12.3)	An informational estimate of the size of the data associated with the item's BodyPart element.
Truncated (section 2.2.2.20.2)	Specifies whether the body of the item has been truncated according to the BodyPartPreference element indicated by the client.
Data (section 2.2.2.10.2)	The body part of the calendar item, contact, document, e-mail, note, or task.
Preview (section 2.2.2.18.2)	The length of the message preview to be returned to the client.
Attachments (section 2.2.2.3)	A collection of elements that contains one or more attachment items.
Attachment (section 2.2.2.2)	Specifies the attachment information for a single attachment item.
DisplayName (section 2.2.2.11)	The display name of the attachment.
FileReference (section 2.2.2.10)	The location of an item on the server to retrieve.

Element name	Description
2.2.2.13.1)	
Method (section 2.2.2.15)	Identifies the method in which the attachment was attached.
EstimatedDataSize (section 2.2.2.12.1)	An informational estimate of the size of the data associated with the attachment.
ContentId (section 2.2.2.8)	Contains the unique object ID for an attachment.
ContentLocation (section 2.2.2.9)	Contains the relative URI for an attachment, which is used to match a reference to an inline attachment in an HTML message to the attachment in the attachments table .
IsInline (section 2.2.2.14)	Specifies whether the attachment is embedded in the message.
NativeBodyType (section 2.2.2.16)	The original format type of the item.

2.2.2.1 AllOrNone

The **AllOrNone** element is a child element of the **BodyPartPreference** element (section [2.2.2.6](#)) and the **BodyPreference** element (section [2.2.2.7](#)) that specifies whether to search, synchronize, or retrieve all or none of the content based on the **TruncationSize** element (section [2.2.2.21](#)).

The value of this element is a **boolean** value ([\[MS-ASDTYPE\]](#) section 2.1). When the value is set to 1 (TRUE) and the content has not been truncated, all of the content is searched, synchronized, or retrieved. When the value is set to 1 (TRUE) and the content has been truncated, the content is not searched, synchronized, or retrieved. When the value is set to 0 (FALSE), the truncated or nontruncated content is searched, synchronized, or retrieved.

2.2.2.1.1 AllOrNone (BodyPartPreference)

The **AllOrNone** element is an optional child element of the **BodyPartPreference** element (section [2.2.2.6](#)). A command request **MUST** have a maximum of 1 **AllOrNone** element per **BodyPartPreference** element. If the **AllOrNone** element is not included in the request, the truncated or nontruncated content is searched, synchronized, or retrieved as if the value was set to 0 (FALSE). The **AllOrNone** element **MUST NOT** be used in command responses.

This element **MUST** be ignored if the **TruncationSize** element is not included.

A client can include multiple **BodyPartPreference** elements in a command request with different values for the **Type** element (section [2.2.2.22.3](#)). By default, the server returns the data truncated to the size requested by **TruncationSize** for the **Type** element that matches the native storage format of the item's **Body** element (section [2.2.2.4](#)). But, if the client also includes the **AllOrNone** element with a value of 1 (TRUE) along with the **TruncationSize** element, it is instructing the server not to return a truncated response for that type when the size (in bytes) of the available data exceeds the value of the **TruncationSize** element. For example, a client can use these two elements to signify that it cannot process partial **Rich Text Format (RTF)** data (a **Type** element value of 3). In this case, if the client has specified multiple **BodyPartPreference** elements, the server selects the next **BodyPartPreference** element that will return the maximum amount of body text to the client. Assume that the client specifies two **BodyPartPreference** elements:

```
<airsyncbase:BodyPartPreference>
  <airsyncbase:Type>2</airsyncbase:Type>
  <airsyncbase:AllOrNone>1</airsyncbase:AllOrNone>
```

```

    <airsynbase:TruncationSize>50</airsynbase:TruncationSize>
  </airsynbase:BodyPartPreference>

  <airsynbase:BodyPartPreference>
    <airsynbase:Type>1</airsynbase:Type>
    <airsynbase:TruncationSize>50</airsynbase:TruncationSize>
  </airsynbase:BodyPartPreference>

```

The first **BodyPartPreference** element requests an HTML body, but only if the body size is less than 50 bytes. The second requests an element in **plain text** format. If the client requests a text body whose native format is HTML, and the size of the data exceeds 50 bytes, the server converts the body to plain text and returns the first 50 bytes of plain text data.

2.2.2.1.2 AllOrNone (BodyPreference)

The **AllOrNone** element is an optional child element of the **BodyPreference** element (section [2.2.2.7](#)). A command request **MUST** have a maximum of 1 **AllOrNone** element per **BodyPreference** element. If the **AllOrNone** element is not included in the request, then the truncated or non-truncated content is searched, synchronized, or retrieved as if the value was set to 0 (FALSE). The **AllOrNone** element **MUST NOT** be used in command responses.

This element **MUST** be ignored if the **TruncationSize** element is not included.

A client can include multiple **BodyPreference** elements in a command request with different values for the **Type** element (section [2.2.2.22.4](#)). By default, the server returns the data truncated to the size requested by **TruncationSize** for the **Type** element that matches the native storage format of the item's **Body** element (section [2.2.2.4](#)). But, if the client also includes the **AllOrNone** element with a value of 1 (TRUE) along with the **TruncationSize** element, it is instructing the server not to return a truncated response for that type when the size (in bytes) of the available data exceeds the value of the **TruncationSize** element. For example, a client can use these two elements to signify that it cannot process partial Rich Text Format (RTF) data (a **Type** element value of 3). In this case, if the client has specified multiple **BodyPreference** elements, the server selects the next **BodyPreference** element that will return the maximum amount of body text to the client. Assume that the client specifies two **BodyPreference** elements.

```

  <airsynbase:BodyPreference>
    <airsynbase:Type>2</airsynbase:Type>
    <airsynbase:AllOrNone>1</airsynbase:AllOrNone>
    <airsynbase:TruncationSize>50</airsynbase:TruncationSize>
  </airsynbase:BodyPreference>

  <airsynbase:BodyPreference>
    <airsynbase:Type>1</airsynbase:Type>
    <airsynbase:TruncationSize>50</airsynbase:TruncationSize>
  </airsynbase:BodyPreference>

```

The first **BodyPreference** element requests an HTML body, but only if the body size is less than 50 bytes. The second requests an element in plain text format. If the client requests a text body whose native format is HTML, and the size of the data exceeds 50 bytes, the server converts the body to plain text and returns the first 50 bytes of plain text data.

2.2.2.2 Attachment

The **Attachment** element is a required child element of the **Attachments** element (section [2.2.2.3](#)) and specifies the attachment information for a single attachment item.

Command requests MUST NOT include the **Attachment** element.

The **Attachment** element has the following child elements in any order (elements noted as optional can be in the response):

- **DisplayName** (section [2.2.2.11](#)). This element is optional.
- **FileReference** (section [2.2.2.13.1](#)). This element is required.
- **Method** (section [2.2.2.15](#)). This element is required.
- **EstimatedDataSize** (section [2.2.2.12.1](#)). This element is required.
- **ContentId** (section [2.2.2.8](#)). This element is optional.
- **ContentLocation** (section [2.2.2.9](#)). This element is optional.
- **IsInline** (section [2.2.2.14](#)). This element is optional.
- **email2:UmAttDuration** ([\[MS-ASEMAIL\]](#) section 2.2.2.69). This element is optional.
- **email2:UmAttOrder** ([\[MS-ASEMAIL\]](#) section 2.2.2.70). This element is optional.

2.2.2.3 Attachments

The **Attachments** element is an optional child element of the **Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128) in the **ItemOperations** command response that contains one or more attachment items.

There is no limit on the number of **Attachments** elements in a command response. Command requests MUST NOT include the **Attachments** element.

The **Attachments** element has the following child elements:

- **Attachment** (section [2.2.2.2](#)): At least one instance of this element is required.

2.2.2.4 Body

The **Body** element is an optional child element of the **airsync:ApplicationData** element (as specified in [\[MS-ASCMD\]](#) section 2.2.3.11) that specifies a free-form, variable-length data field associated with a stored item on the server. Examples include, but are not limited to, the body of an e-mail message and the Notes field in a contact. The **Body** element MUST be included in a response message whenever a content class has changes or new items.

The **Body** element is a container ([\[MS-ASDTYPE\]](#) section 2.2).

There is no limit on the number of **Body** elements in a command response. When included in a command response, the **Body** element indicates the existence of one or more variable-length fields of data associated with the item. Command requests can include the **Body** element.

In a response, the **Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128) MUST be the parent element of the **Body** element for **ItemOperations** commands with the **Fetch** sub-element ([\[MS-](#)

[ASCMD](#)] section 2.2.3.63). For all other command responses, the **airsync:ApplicationData** element MUST be the parent element of the **Body** element.

The **Body** element, if present, has the following required and optional child elements in this order:

- **Type** (section [2.2.2.22.1](#)): This element is required.
- **EstimatedDataSize** (section [2.2.2.12.2](#)): This element is optional.
- **Truncated** (section [2.2.2.20.1](#)). This element has no effect in a command request and is optional in the response.
- **Data** (section [2.2.2.10.1](#)): This element is optional.
- **Part** (section [2.2.2.17](#)): This element is optional.
- **Preview** (section [2.2.2.18.1](#)): This element is optional.

2.2.2.5 BodyPart

The **BodyPart** element is an optional child element of the **airsync:ApplicationData** element that specifies details about the message part of an e-mail in a response. The **BodyPart** element MUST be included in a command response when the **BodyPartPreference** element (section [2.2.2.6](#)) is specified in a request.

The **BodyPart** element is a container ([\[MS-ASDTYPE\]](#) section 2.2).

There is no limit on the number of **BodyPart** elements in a command response. Command requests MUST NOT include the **BodyPart** element.

In a response, the **airsync:ApplicationData** element MUST be the parent element of the **BodyPart** element.

The **BodyPart** element, if present, MUST have its required and optional child elements in the following order:

- **Status** (section [2.2.2.19](#)). This element is required.
- **Type** (section [2.2.2.22.2](#)). This element is required.
- **EstimatedDataSize** (section [2.2.2.12.3](#)). This element is required.
- **Truncated** (section [2.2.2.20.2](#)). This element is optional.
- **Data** (section [2.2.2.10.2](#)). This element is optional.
- **Preview** (section [2.2.2.18.2](#)). This element is optional.

2.2.2.6 BodyPartPreference

The **BodyPartPreference** element is an optional [<1>](#) container (as specified in [\[MS-ASDTYPE\]](#) section 2.2) element that sets preference information related to the type and size of information that is returned from searching, synchronizing, or fetching a message part.

A command response MUST NOT include a **BodyPartPreference** element. Command requests can include the **BodyPartPreference** element.

In a request, the **Options** element MUST be the parent element of the **BodyPartPreference** element. The **BodyPartPreference** element, if present, MUST have the following required and optional child elements in the following order:

- **Type** (section [2.2.2.22.3](#)). This element is required.
- **TruncationSize** (section [2.2.2.21.1](#)). This element is optional.
- **AllOrNone** (section [2.2.2.1.1](#)). This element is optional.
- **Preview** (section [2.2.2.18.3](#)). This element is optional.

The contents of the **Options** element specify preferences for all of the content that the user is interested in searching, synchronizing, or retrieving. These preferences are set on a per-request basis and override any stored information. Because this information is required to process every request, the information can be persisted on the server if network load is a concern.

There MUST be one explicit **BodyPartPreference** element for each **Type** value specified in the set of preferences in order to request a **BodyPart** element (section [2.2.2.5](#)) of that **Type** in the response.

2.2.2.7 BodyPreference

The **BodyPreference** element is an optional container (as specified in [\[MS-ASDTYPE\]](#) section 2.2) element that sets preference information related to the type and size of information that is returned from searching, synchronizing, or fetching.

A command response MUST NOT include the **BodyPreference** element. Command requests can include the **BodyPreference** element.

The **BodyPreference** element, if present, has the following child elements in this order:

- **Type** (section [2.2.2.22.4](#)). This element is required.
- **TruncationSize** (section [2.2.2.21.2](#)). This element is optional.
- **AllOrNone** (section [2.2.2.1.2](#)). This element is optional.
- **Preview** (section [2.2.2.18.4](#)). This element is optional.

The contents of the **airsync:Options**, **itemoperations:Options**, or **search:Options** element specify preferences for all of the content that the user is interested in searching, synchronizing, or retrieving. These preferences are persisted by the server from request to request for the specified client, and can be changed by the inclusion of an **airsync:Options** element in any subsequent request.

A request MUST NOT contain more than one **BodyPreference** element for each allowable value of the **Type** element.

2.2.2.8 ContentId

The **ContentId** element is an optional child element of the **Attachment** element (section [2.2.2.2](#)) that contains the unique object ID for an attachment. This element is provided for informational purposes only and can be ignored by the client.

The value of this element is a **string** value ([\[MS-ASDTYPE\]](#) section 2.6).

A command response MUST have a maximum of one **ContentId** element per **Attachment** element.

The **ContentId** element MUST have no child elements.

2.2.2.9 ContentLocation

The **ContentLocation** element is an optional child element of the **Attachment** element (section [2.2.2.2](#)) that contains the relative URI for an attachment, and is used to match a reference to an inline attachment in an HTML message to the attachment in the attachments table.

The value of this element is a **string** ([\[MS-ASDTYPE\]](#) section 2.6) value.

A command response MUST have a maximum of one **ContentLocation** element per **Attachment** element.

The **ContentLocation** element MUST have no child elements.

2.2.2.10 Data

The **Data** element is a child element of the **Body** element (section [2.2.2.4](#)) and the **BodyPart** element (section [2.2.2.5](#)) that contains the data of the **message body (2)** or the message part of the calendar item, contact, document, e-mail, or task.

The value of this element is a **string** ([\[MS-ASDTYPE\]](#) section 2.6).

2.2.2.10.1 Data (Body)

The **Data** element is an optional child element of the **Body** element (section [2.2.2.4](#)). A command response MUST have a maximum of one **Data** element within each returned **Body** element. Command requests MAY include the **Data** element. This element MUST NOT be present in multipart responses, as specified in [\[MS-ASCMD\]](#) section 2.2.2.8.1.

In a response, the **Data** element MUST have no child elements.

The content of the **Data** element is returned as a **string** in the format that is specified by the **Type** element (section [2.2.2.22.1](#)). If the value of the **Type** element is 3 (RTF), the value of the **Data** element is encoded using **base64 encoding**.

If the **Truncated** element (section [2.2.2.20.1](#)) is included in the response, the data in the **Data** element is truncated. The **EstimatedDataSize** element (section [2.2.2.12.2](#)) provides a rough estimation of the actual size of the complete content of the **Data string**.

2.2.2.10.2 Data (BodyPart)

The **Data** element is an optional child element of the **BodyPart** element (section [2.2.2.5](#)). A command response MUST have a maximum of one **Data** element within each returned **BodyPart** element. Command requests MAY include the **Data** element.

In a response, the **Data** element MUST have no child elements.

The content of the **Data** element is returned as a **string** in the format that is specified by the **Type** element (section [2.2.2.22.2](#)). If the value of the **Type** element is 3 (RTF), the value of the **Data** element is encoded using base64 encoding.

If the **Truncated** element (section [2.2.2.20.2](#)) is included in the response, then the data in the **Data** element is truncated. The **EstimatedDataSize** element (section [2.2.2.12.3](#)) provides a rough estimation of the actual size of the complete content of the **Data string**.

2.2.2.11 DisplayName

The **DisplayName** element is an optional child element of the **Attachment** element (section [2.2.2.2](#)) that specifies the display name of the attachment.

The value of this element is a **string** value ([\[MS-ASDTYPE\]](#) section 2.6).

A command response MUST have a maximum of one **DisplayName** element per **Attachment** element.

The **DisplayName** element MUST have no child elements.

2.2.2.12 EstimatedDataSize

The **EstimatedDataSize** element is a child element of the **Attachment** element (section [2.2.2.2](#)), the **Body** element (section [2.2.2.4](#)), and the **BodyPart** element (section [2.2.2.5](#)) that provides an informational estimate of the size of the data associated with the parent element.

The value of this element is an **integer** value ([\[MS-ASDTYPE\]](#) section 2.5).

The **EstimatedDataSize** value represents an estimate of the original size of the content in the **store** and is specified in bytes. This number is only an estimate, and the actual size of the content when fetched can differ based on the content filtering rules applied.

2.2.2.12.1 EstimatedDataSize (Attachment)

The **EstimatedDataSize** element is required child element of the **Attachment** element (section [2.2.2.2](#)).

A command response MUST have a maximum of one **EstimatedDataSize** element per **Attachment** element.

The **EstimatedDataSize** element MUST have no child elements.

2.2.2.12.2 EstimatedDataSize (Body)

The **EstimatedDataSize** element is an optional child element of the **Body** element (section [2.2.2.4](#)). The **EstimatedDataSize** element SHOULD be included in a response message whenever the **Truncated** element is set to TRUE.

A command response MUST have a maximum of one **EstimatedDataSize** element per **Body** element.

The **EstimatedDataSize** element MUST have no child elements.

2.2.2.12.3 EstimatedDataSize (BodyPart)

The **EstimatedDataSize** element is a required child element of the **BodyPart** element (section [2.2.2.5](#)). The **EstimatedDataSize** element SHOULD be included in a response message whenever the **Truncated** element is set to TRUE.

A command response MUST have a maximum of one **EstimatedDataSize** element per **BodyPart** element. The **EstimatedDataSize** element MUST have no child elements.

2.2.2.13 FileReference

The **FileReference** element is a child element of the **itemoperations:Fetch** element ([\[MS-ASCMD\]](#) section 2.2.3.63.1) and the **Attachment** element (section [2.2.2.2](#)).

The value of this element is a **string** value ([\[MS-ASDTYPE\]](#) section 2.6).

2.2.2.13.1 FileReference (Attachment)

The **FileReference** element is a required child element of the **Attachment** element (section [2.2.2.2](#)) that specifies the location of an item on the server to retrieve.

2.2.2.13.2 FileReference (Fetch)

In an **ItemOperations** command request (as specified in [\[MS-ASCMD\]](#) section 2.2.2.8), the **FileReference** element is an optional child element of the **itemoperations:Fetch** element (as specified in [\[MS-ASCMD\]](#) section 2.2.3.63.1). The **FileReference** element specifies a unique identifier that is assigned by the server to each **Attachment object** to a **Message object**.

If the client includes a zero-length string for the value of this element in an **ItemOperations** command request, the server responds with a protocol status error of 15.

The **FileReference** element MUST have no child elements.

2.2.2.14 IsInline

The **IsInline** element is an optional child element of the **Attachment** element (section [2.2.2.2](#)) that specifies whether the attachment is embedded in the message.

The value of this element is a **boolean** value ([\[MS-ASDTYPE\]](#) section 2.1).

A command response MUST have a maximum of one **IsInline** element per **Attachment** element.

The **IsInline** element MUST have no child elements.

2.2.2.15 Method

The **Method** element is a required child element of the **Attachment** element (section [2.2.2.2](#)) that identifies the method in which the attachment was attached.

The value of this element is an **enumeration** value ([\[MS-ASDTYPE\]](#) section 2.4).

A command response MUST have a maximum of one **Method** element per **Attachment** element.

The **Method** element MUST have no child elements.

The following table defines the valid values of the **Method** enumeration.

Value	Meaning	Notes
1	Normal attachment	The attachment is a normal attachment. This is the most common value.

Value	Meaning	Notes
2	Reserved	Do not use.
3	Reserved	Do not use.
4	Reserved	Do not use.
5	Embedded message	Indicates that the attachment is an e-mail message, and that the attachment file has an .eml extension.
6	Attach OLE	Indicates that the attachment is an embedded Object Linking and Embedding (OLE) object, such as an inline image.

2.2.2.16 NativeBodyType

The **NativeBodyType** element is a required child element of the **airsync:ApplicationData** element ([\[MS-ASCMD\]](#)) in the **Sync** command that specifies the original format type of the item.

The value of this element is an **enumeration** value ([\[MS-ASDTYPE\]](#) section 2.4).

A command response **MUST** have a maximum of one **NativeBodyType** element per **airsync:ApplicationData** element. Command requests **MAY** include the **NativeBodyType** element.

The **NativeBodyType** element **MUST** have no child elements.

The following table defines the valid values of the **NativeBodyType** enumeration.

Enumeration value	Description
1	Plain text
2	HTML
3	RTF

The **NativeBodyType** and **Type** elements have the same value unless the server has modified the format of the body to match the client's request. The client can specify a preferred body format by using the **Type** element of a **Search** or **Sync** command request.

2.2.2.17 Part

The **Part** element ([\[MS-ASCMD\]](#) section 2.2.3.120) is an optional child element of the **Body** element (section [2.2.2.4](#)) that contains an integer index into the metadata of the multipart response. This element **MUST** be present in multipart responses, as specified in [\[MS-ASCMD\]](#) section 2.2.2.8.1. This element **MUST NOT** be present in requests or non-multipart responses.

The value of this element is an **integer** ([\[MS-ASDTYPE\]](#) section 2.5).

2.2.2.18 Preview

The **Preview** element is a child element of the **Body** element (section [2.2.2.4](#)), the **BodyPart** element (section [2.2.2.5](#)), the **BodyPartPreference** element (section [2.2.2.6](#)), and the **BodyPreference** element (section [2.2.2.6](#)).

2.2.2.18.1 Preview (Body)

The **Preview** element is an optional [<2>](#) child element of the **Body** element (section [2.2.2.4](#)) that contains the **Unicode** plain text message or message part preview returned to the client.

The value of this element is a **string** ([\[MS-ASDTYPE\]](#) section 2.6). The **Preview** element in a response **MUST** contain no more than the number of characters specified in the request.

Command responses **MUST** have a maximum of one **Preview** element per **Body** element.

The **Preview** element **MUST** have no child elements.

2.2.2.18.2 Preview (BodyPart)

The **Preview** element is an optional [<3>](#) child element of the **BodyPart** element (section [2.2.2.5](#)) that contains the Unicode plain text message or message part preview returned to the client.

The value of this element is a **string** ([\[MS-ASDTYPE\]](#) section 2.6). The **Preview** element in a response **MUST** contain no more than the number of characters specified in the request. The **Preview** element **MUST** be present in a command response if a **BodyPartPreference** element (section [2.2.2.6](#)) in the request included a **Preview** element and the server can honor the request.

Command responses **MUST** have a maximum of one **Preview** element per **BodyPart** element.

The **Preview** element **MUST** have no child elements.

2.2.2.18.3 Preview (BodyPartPreference)

The **Preview** element is an optional child element of the **BodyPartPreference** element (section [2.2.2.6](#)) that specifies the maximum length of the Unicode plain text message or message part preview to be returned to the client.

The value of this element is an **integer** value ([\[MS-ASDTYPE\]](#) section 2.5). This element **MUST** have a value set from 0 to 255, inclusive.

A command request **MUST** have a maximum of one **Preview** element per **BodyPartPreference** element.

The **Preview** element **MUST** have no child elements.

2.2.2.18.4 Preview (BodyPreference)

The **Preview** element is an optional [<4>](#) child element of the **BodyPreference** element (section [2.2.2.7](#)) that specifies the maximum length of the Unicode plain text message or message part preview to be returned to the client.

The value of this element is an **integer** value (as specified in [\[MS-ASDTYPE\]](#) section 2.5). This element **MUST** have a value set from 0 to 255, inclusive.

A command request **MUST** have a maximum of one **Preview** element per **BodyPreference** element.

The **Preview** element **MUST** have no child elements.

2.2.2.19 Status

The **Status** element is a child of the **BodyPart** element (section [2.2.2.5](#)) that indicates the success or failure of the response in returning **Data** element content (section [2.2.2.10.2](#)) given the **BodyPartPreference** element settings (section [2.2.2.6](#)) in the request.

The following table lists valid values for the **Status** element.

Value	Meaning
1	Success.
176	The message part is too large.

2.2.2.20 Truncated

The **Truncated** element is a child element of the **Body** element (section [2.2.2.4](#)) and the **BodyPart** element (section [2.2.2.5](#)). The value of this element is a **boolean** value ([\[MS-ASDTYPE\]](#) section 2.1) that specified whether the body or body part has been truncated.

2.2.2.20.1 Truncated (Body)

The **Truncated** element is an optional child element of the **Body** element (section [2.2.2.4](#)) that specifies whether the body of the item has been truncated according to the **BodyPreference** element (section [2.2.2.7](#)) indicated by the client.

If the value is TRUE, then the body of the item has been truncated. If the value is FALSE, or there is no **Truncated** element, then the body of the item has not been truncated.

If a **Truncated** element is included in a command request, then it is ignored by the server.

A command response MUST have a maximum of one **Truncated** element per **Body** element.

2.2.2.20.2 Truncated (BodyPart)

The **Truncated** element is an optional child element of the **BodyPart** element (section [2.2.2.5](#)) that specifies whether the body of the item has been truncated according to the **BodyPartPreference** element (section [2.2.2.6](#)) indicated by the client.

If the value is TRUE, then the body of the item has been truncated. If the value is FALSE, or there is no **Truncated** element, then the body of the item has not been truncated.

If a **Truncated** element is included in a command request, it is ignored by the server.

A command response MUST have a maximum of one **Truncated** element per **BodyPart** element.

2.2.2.21 TruncationSize

The **TruncationSize** element is a child element of the **BodyPartPreference** element (section [2.2.2.6](#)) and the **BodyPreference** element (section [2.2.2.7](#)). The value of this element is an **integer** value ([\[MS-ASDTYPE\]](#) section 2.5) that specifies the size, in bytes, of the content that the user wants to **Search**, **Synchronize**, or **Fetch**.

2.2.2.21.1 TruncationSize (BodyPartPreference)

The **TruncationSize** element is an optional child element of the **BodyPartPreference** element (section [2.2.2.6](#)).

A command request **MUST** have a maximum of one **TruncationSize** element per **BodyPartPreference** element.

Command responses **MUST NOT** include the **TruncationSize** element.

The **TruncationSize** element **MUST** have no child elements.

The maximum value for **TruncationSize** is 4,294,967,295. If the **TruncationSize** element is absent, the entire content is used for the request.

2.2.2.21.2 TruncationSize (BodyPreference)

The **TruncationSize** element is an optional child element of the **BodyPreference** type (section [2.2.2.7](#)).

A command request **MUST** have a maximum of one **TruncationSize** element per **BodyPreference** element.

Command responses **MUST NOT** include the **TruncationSize** element.

The **TruncationSize** element **MUST** have no child elements.

The maximum value for **TruncationSize** is 4,294,967,295. If the **TruncationSize** element is absent, the entire content is used for the request.

2.2.2.22 Type

The **Type** element is a child element of the **Body** element (section [2.2.2.4](#)), the **BodyPart** element (section [2.2.2.5](#)), the **BodyPartPreference** element (section [2.2.2.6](#)), and the **BodyPreference** element (section [2.2.2.7](#)). The value of this element is an **enumeration** value ([\[MS-ASDTYPE\]](#) section 2.4) that indicates the format type of the body content of the item.

The following table defines the valid values of the **Type** enumeration.

Enumeration value	Description
1	Plain text
2	HTML
3	RTF
4	MIME

2.2.2.22.1 Type (Body)

The **Type** element is a required element of the **Body** element (section [2.2.2.4](#)).

A command request or response **MUST** have a maximum of one **Type** element per **Body** element.

The **Type** element **MUST** have no child elements.

2.2.2.22.2 Type (BodyPart)

The **Type** element is a required child element of the **BodyPart** element (section [2.2.2.5](#)).

A command request or response MUST have a maximum of one **Type** element per **BodyPart** element.

The **Type** element MUST have no child elements.

2.2.2.22.3 Type (BodyPartPreference)

The **Type** element is a required child element of the **BodyPartPreference** element (section [2.2.2.6](#)).

A command request or response MUST have a maximum of one **Type** element per **BodyPartPreference** element.

The **Type** element MUST have no child elements.

Only a value of 2 (HTML) SHOULD be used in the **Type** element of a **BodyPartPreference** element.

2.2.2.22.4 Type (BodyPreference)

The **Type** element is a required child element of the **BodyPreference** element (section [2.2.2.7](#)).

A command request or response MUST have a maximum of one **Type** element per **BodyPreference** element.

The **Type** element MUST have no child elements.

2.2.3 Groups

The following table summarizes the set of common XML schema group definitions defined by this specification. XML schema groups that are specific to a particular operation are described with the operation.

Group	Description
TopLevelSchemaProps	Identifies the Body element (section 2.2.2.4), BodyPart element (section 2.2.2.5), and the Attachments element (section 2.2.2.3) as being part of the TopLevelSchemaProps group.

2.2.3.1 TopLevelSchemaProps

The **TopLevelSchemaProps** group identifies the **Body** element (section [2.2.2.4](#)), the **BodyPart** element (section [2.2.2.5](#)), and the **Attachments** element (section [2.2.2.3](#)) as being part of the **TopLevelSchemaProps** group. The **TopLevelSchemaProps** group is used by the **ItemOperations** command request specified in [\[MS-ASCMD\]](#) section 2.2.2.8.2.

3 Protocol Details

3.1 Client Details

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

3.1.5.1 Commands

The following table lists the commands that use the XML elements specified by this protocol.

Command	Description
ItemOperations	Retrieves an item from the server.
Search	Searches the server for items that match the specified criteria.
Sync	Synchronizes changes in a collections set between the client and the server.

3.1.5.1.1 ItemOperations

The request message for the **ItemOperations** command can include the following elements:

- **FileReference** (section [2.2.2.13.2](#))
- **BodyPreference** (section [2.2.2.7](#))
 - **Type** (section [2.2.2.22.4](#))
 - **TruncationSize** (section [2.2.2.21.2](#))
 - **AllOrNone** (section [2.2.2.1.2](#))
- **BodyPartPreference** (section [2.2.2.6](#))
 - **Type** (section [2.2.2.22.3](#))
 - **TruncationSize** (section [2.2.2.21.1](#))
 - **AllOrNone** (section [2.2.2.1.1](#))

3.1.5.1.2 Search

The request message for the **Search** command can include the following elements and types:

- **BodyPreference** (section [2.2.2.7](#))
 - **Type** (section [2.2.2.22.4](#))
 - **TruncationSize** (section [2.2.2.21.2](#))
 - **AllOrNone** (section [2.2.2.1.2](#))
- **BodyPartPreference** (section [2.2.2.6](#))
 - **Type** (section [2.2.2.22.3](#))
 - **TruncationSize** (section [2.2.2.21.1](#))
 - **AllOrNone** (section [2.2.2.1.1](#))

3.1.5.1.3 Sync

The request message for the **Sync** command can include the following elements and types:

- **BodyPreference** (section [2.2.2.7](#))
 - **Type** (section [2.2.2.22.4](#))
 - **TruncationSize** (section [2.2.2.21.2](#))
 - **AllOrNone** (section [2.2.2.1.2](#))
 - **Preview** (section [2.2.2.18.3](#))
- **BodyPartPreference** (section [2.2.2.6](#))
 - **Type** (section [2.2.2.22.3](#))
 - **TruncationSize** (section [2.2.2.21.1](#))
 - **AllOrNone** (section [2.2.2.1.1](#))
 - **Preview** (section [2.2.2.18.3](#))
- **Attachments** (section [2.2.2.3](#))
 - **Attachment** (section [2.2.2.2](#))
 - **FileReference** (section [2.2.2.13.1](#))
 - **Method** (section [2.2.2.15](#))
 - **EstimatedDataSize** (section [2.2.2.12.1](#))

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Server Details

3.2.1 Abstract Data Model

None.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

None.

3.2.5 Message Processing Events and Sequencing Rules

3.2.5.1 Validating XML

When the server receives an **ItemOperations**, **Search**, or **Sync** command, it SHOULD check any of the XML elements specified in section 2.2.2 that are present in the command's XML body to ensure they comply with the requirements regarding data type, number of instances, order, and placement in the XML hierarchy. Unless specified in the following table, if an element does not meet the requirements specified for that element, the server SHOULD return protocol status error 2 for an **ItemOperations** command (as specified in [MS-ASCMD] section 2.2.2.8) or a **Search** command (as specified in [MS-ASCMD] section 2.2.2.14), and protocol status error 6 for a **Sync** command (as specified in [MS-ASCMD] section 2.2.2.19).

Element name	Condition	Protocol Status Error
BodyPreference (section 2.2.2.7)	Child elements are not in the correct order.	4 (for Sync command)
BodyPreference	Multiple BodyPreference elements are present with the same value in the Type child element	4 (for Sync command)
AllOrNone (section 2.2.2.1.2)	The AllOrNone element is not of type boolean .	4 (for Sync command)
AllOrNone	Multiple AllOrNone elements in a single BodyPreference element.	4 (for Sync command)

3.2.5.2 Commands

The following table lists the commands that use the XML elements specified by this protocol.

Command	Description
ItemOperations	Retrieves an item from the server.
Search	Searches the server for items that match the specified criteria.
Sync	Synchronizes changes in a collections set between the client and the server.

The server SHOULD process commands as specified in [\[MS-ASCMD\]](#). The server SHOULD modify responses based on the elements specified in section [2.2.2](#) as specified for each element.

3.2.5.2.1 ItemOperations

The response message for the **ItemOperations** command can include the following:

- **Body** (section [2.2.2.4](#))
 - **Type** (section [2.2.2.22.1](#))
 - **EstimatedDataSize** (section [2.2.2.12.2](#))
 - **Truncated** (section [2.2.2.20.1](#))
 - **Data** (section [2.2.2.10.1](#))
 - **Preview** (section [2.2.2.18.1](#))
- **BodyPart** (section [2.2.2.5](#))
 - **Status** (section [2.2.2.19](#))
 - **Type** (section [2.2.2.22.2](#))
 - **EstimatedDataSize** (section [2.2.2.12.3](#))
 - **Truncated** (section [2.2.2.20.2](#))
 - **Data** (section [2.2.2.10.2](#))
 - **Preview** (section [2.2.2.18.2](#))

3.2.5.2.2 Search

The response message for the **Search** command can include the following:

- **Attachments** (section [2.2.2.3](#))
 - **Attachment** (section [2.2.2.2](#))
 - **DisplayName** (section [2.2.2.11](#))
 - **FileReference** (section [2.2.2.13.1](#))
 - **Method** (section [2.2.2.15](#))
 - **EstimatedDataSize** (section [2.2.2.12.1](#))
 - **ContentId** (section [2.2.2.8](#))

- **ContentLocation** (section [2.2.2.9](#))
- **IsInline** (section [2.2.2.14](#))
- **Body** (section [2.2.2.4](#))
 - **Type** (section [2.2.2.22.1](#))
 - **EstimatedDataSize** (section [2.2.2.12.2](#))
 - **Truncated** (section [2.2.2.20.1](#))
 - **Data** (section [2.2.2.10.1](#))
 - **Preview** (section [2.2.2.18.1](#))
- **BodyPart** (section [2.2.2.5](#))
 - **Status** (section [2.2.2.19](#))
 - **Type** (section [2.2.2.22.2](#))
 - **EstimatedDataSize** (section [2.2.2.12.3](#))
 - **Truncated** (section [2.2.2.20.2](#))
 - **Data** (section [2.2.2.10.2](#))
 - **Preview** (section [2.2.2.18.2](#))

3.2.5.2.3 Sync

The response message for the **Sync** command can include the following:

- **Attachments** (section [2.2.2.3](#))
 - **Attachment** (section [2.2.2.2](#))
 - **DisplayName** (section [2.2.2.11](#))
 - **FileReference** (section [2.2.2.13.1](#))
 - **Method** (section [2.2.2.15](#))
 - **EstimatedDataSize** (section [2.2.2.12.1](#))
 - **ContentId** (section [2.2.2.8](#))
 - **ContentLocation** (section [2.2.2.9](#))
 - **IsInline** (section [2.2.2.14](#))
- **Body** (section [2.2.2.4](#))
 - **Type** (section [2.2.2.22.1](#))
 - **Truncated** (section [2.2.2.20.1](#))
 - **Data** (section [2.2.2.10.1](#))

- **BodyPart** (section [2.2.2.5](#))
 - **Type** (section [2.2.2.22.2](#))
 - **Truncated** (section [2.2.2.20.2](#))
 - **Data** (section [2.2.2.10.2](#))
- **NativeBodyType** (section [2.2.2.16](#))

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

4 Protocol Examples

For examples of the **Search** command using this protocol, see [\[MS-ASCMD\]](#) section 4.11. For examples of the **ItemOperations** command using this protocol, see [\[MS-ASCMD\]](#) section 4.10.2 and [\[MS-ASCMD\]](#) section 4.10.4. For examples of the **Sync** command using this protocol, see [\[MS-ASCMD\]](#) section 4.5.7.

Preliminary

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

Preliminary

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2007 Service Pack 1 (SP1)
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 2013 Preview
- Windows® Communication Apps

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

<1> [Section 2.2.2.6](#): The **BodyPartPreference** element is not supported when the **MS-ASProtocolVersion** header, as specified in [\[MS-ASHTTP\]](#) section 2.2.1.1.2.4, is set to 12.1 or 14.0.

<2> [Section 2.2.2.18.1](#): The **Preview** element is not supported when the **MS-ASProtocolVersion** header is set to 12.1.

<3> [Section 2.2.2.18.2](#): The **Preview** element is not supported when the **MS-ASProtocolVersion** header is set to 12.1.

<4> [Section 2.2.2.18.4](#): The **Preview** element is not supported when the **MS-ASProtocolVersion** header is set to 12.1.

7 Change Tracking

This section identifies changes that were made to the [MS-ASAIRS] protocol document between the April 2012 and July 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
1.4 Relationship to Other Protocols	Revised description of protocols that use the AirSyncBase namespace.	N	Content updated.
2.2.2.1.1 AllOrNone (BodyPartPreference)	Clarified that the AllOrNone element is set to 1 (TRUE) to indicate the server does not return a truncated response.	N	Content updated.
2.2.2.1.2 AllOrNone (BodyPreference)	Clarified that the AllOrNone element is set to 1 (TRUE) to indicate the server does not return a truncated response.	N	Content updated.
2.2.2.2 Attachment	Revised description of child elements.	N	Content updated.
2.2.2.4 Body	Added reference for the airsinc:ApplicationData element.	N	Content updated.
2.2.2.5 BodyPart	Removed reference for the airsinc:ApplicationData element.	N	Content updated.
2.2.3.1 TopLevelSchemaProps	Added reference to the ItemOperations command that uses the TopLevelSchemaProps group.	N	Content updated.
3.2.5.1 Validating XML	Added status error for the Search command.	N	Content updated.
6 Appendix A: Product Behavior	Added Windows Communication Apps to the list of products.	Y	Content updated.

8 Index

A

Abstract data model
[client](#) 25
[server](#) 27
[Applicability](#) 7

C

[Capability negotiation](#) 7
[Change tracking](#) 34
Client
[abstract data model](#) 25
[higher-layer triggered events](#) 25
[initialization](#) 25
[other local events](#) 27
[timer events](#) 26
[timers](#) 25

D

Data model - abstract
[client](#) 25
[server](#) 27

E

[Elements message](#) 10

F

[Fields - vendor-extensible](#) 7

G

[Glossary](#) 5
[Groups message](#) 24

H

Higher-layer triggered events
[client](#) 25
[server](#) 27

I

[Implementer - security considerations](#) 32
[Index of security parameters](#) 32
[Informative references](#) 6
Initialization
[client](#) 25
[server](#) 27
[Introduction](#) 5

M

Messages
[Elements](#) 10

[Groups](#) 24
[Namespaces](#) 10
[transport](#) 8

N

[Namespaces message](#) 10
[Normative references](#) 5

O

Other local events
[client](#) 27
[server](#) 30
[Overview \(synopsis\)](#) 6

P

[Parameters - security index](#) 32
[Preconditions](#) 7
[Prerequisites](#) 7
[Product behavior](#) 33

R

[References](#) 5
[informative](#) 6
[normative](#) 5
[Relationship to other protocols](#) 6

S

Security
[implementer considerations](#) 32
[parameter index](#) 32
Server
[abstract data model](#) 27
[higher-layer triggered events](#) 27
[initialization](#) 27
[other local events](#) 30
[timer events](#) 30
[timers](#) 27
[Standards assignments](#) 7

T

Timer events
[client](#) 26
[server](#) 30
Timers
[client](#) 25
[server](#) 27
[Tracking changes](#) 34
[Transport](#) 8
Triggered events - higher-layer
[client](#) 25
[server](#) 27

v

[Vendor-extensible fields](#) 7
[Versioning](#) 7

Preliminary