

[MS-ASDOC]: ActiveSync Document Class Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final

documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

| Date | Revision History | Revision Class | Comments |
|------------|------------------|----------------|--|
| 12/03/2008 | 1.0.0 | Major | Initial Release. |
| 02/04/2009 | 1.0.1 | Editorial | Revised and edited technical content. |
| 03/04/2009 | 1.0.2 | Editorial | Revised and edited technical content. |
| 04/10/2009 | 2.0.0 | Major | Updated applicable product releases. |
| 07/15/2009 | 3.0.0 | Major | Revised and edited for technical content. |
| 11/04/2009 | 4.0.0 | Major | Updated and revised the technical content. |
| 02/10/2010 | 5.0.0 | Major | Updated and revised the technical content. |
| 05/05/2010 | 6.0.0 | Major | Updated and revised the technical content. |
| 08/04/2010 | 7.0 | Major | Significantly changed the technical content. |
| 11/03/2010 | 7.1 | Minor | Clarified the meaning of the technical content. |
| 03/18/2011 | 7.2 | Minor | Clarified the meaning of the technical content. |
| 08/05/2011 | 8.0 | Major | Significantly changed the technical content. |
| 10/07/2011 | 8.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 01/20/2012 | 9.0 | Major | Significantly changed the technical content. |
| 04/27/2012 | 9.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 07/16/2012 | 9.0 | No change | No changes to the meaning, language, or formatting of the technical content. |

Table of Contents

| | |
|--|-----------|
| 1 Introduction | 5 |
| 1.1 Glossary | 5 |
| 1.2 References | 5 |
| 1.2.1 Normative References | 5 |
| 1.2.2 Informative References | 6 |
| 1.3 Overview | 6 |
| 1.4 Relationship to Other Protocols | 6 |
| 1.5 Prerequisites/Preconditions | 6 |
| 1.6 Applicability Statement | 6 |
| 1.7 Versioning and Capability Negotiation | 6 |
| 1.8 Vendor-Extensible Fields | 7 |
| 1.9 Standards Assignments | 7 |
| 2 Messages | 8 |
| 2.1 Transport | 8 |
| 2.2 Message Syntax | 8 |
| 2.2.1 Namespaces | 8 |
| 2.2.2 Elements | 9 |
| 2.2.2.1 ContentLength | 9 |
| 2.2.2.2 ContentType | 9 |
| 2.2.2.3 CreationDate | 10 |
| 2.2.2.4 DisplayName | 10 |
| 2.2.2.5 IsFolder | 10 |
| 2.2.2.6 IsHidden | 10 |
| 2.2.2.7 LastModifiedDate | 11 |
| 2.2.2.8 LinkId | 11 |
| 3 Protocol Details | 12 |
| 3.1 Client Details | 12 |
| 3.1.1 Abstract Data Model | 12 |
| 3.1.2 Timers | 12 |
| 3.1.3 Initialization | 12 |
| 3.1.4 Higher-Layer Triggered Events | 12 |
| 3.1.4.1 Searching for Documents | 12 |
| 3.1.4.2 Requesting Details for Specific Documents | 12 |
| 3.1.4.3 Requesting the Document Body from the Server | 12 |
| 3.1.5 Message Processing Events and Sequencing Rules | 13 |
| 3.1.5.1 ItemOperations Command Request | 13 |
| 3.1.5.2 Search Command Request | 13 |
| 3.1.6 Timer Events | 13 |
| 3.1.7 Other Local Events | 13 |
| 3.2 Server Details | 13 |
| 3.2.1 Abstract Data Model | 13 |
| 3.2.2 Timers | 14 |
| 3.2.3 Initialization | 14 |
| 3.2.4 Higher-Layered Triggered Events | 14 |
| 3.2.4.1 Searching for Documents | 14 |
| 3.2.4.2 Retrieving Details for Specific Documents | 14 |
| 3.2.4.3 Retrieving the Document Body | 14 |
| 3.2.5 Message Processing Events and Sequencing Rules | 14 |

| | | |
|----------|---|-----------|
| 3.2.5.1 | ItemOperations Command Response | 14 |
| 3.2.5.2 | Search Command Response | 15 |
| 3.2.6 | Timer Events | 15 |
| 3.2.7 | Other Local Events | 15 |
| 4 | Protocol Examples | 16 |
| 4.1 | Searching for a Document by LinkId | 16 |
| 4.2 | Retrieving the Text of a Document by Using the ItemOperations Command | 17 |
| 4.3 | Browsing a Document Folder | 17 |
| 5 | Security | 20 |
| 5.1 | Security Considerations for Implementers | 20 |
| 5.2 | Index of Security Parameters | 20 |
| 6 | Appendix A: Product Behavior | 21 |
| 7 | Change Tracking | 22 |
| 8 | Index | 23 |

1 Introduction

The ActiveSync Document Class Protocol supports accessing documents stored in a web-based team collaboration environment and on file shares specified using **Universal Naming Convention (UNC)** paths. This protocol enables the communication of document data between a mobile device and the server in the ActiveSync protocol.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Coordinated Universal Time (UTC)
Universal Naming Convention (UNC)
XML

The following terms are defined in [\[MS-OXGLOS\]](#):

base64 encoding
header
Multipurpose Internet Mail Extensions (MIME)
Uniform Resource Identifier (URI)
Wireless Application Protocol (WAP) Binary XML (WBXML)
XML namespace
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-ASAIRS] Microsoft Corporation, "[ActiveSync AirSyncBase Namespace Protocol Specification](#)".

[MS-ASCMD] Microsoft Corporation, "[ActiveSync Command Reference Protocol Specification](#)".

[MS-ASDTYPE] Microsoft Corporation, "[ActiveSync Data Types](#)".

[MS-ASWBXML] Microsoft Corporation, "[ActiveSync WAP Binary XML \(WBXML\) Algorithm](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[XML] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Fourth Edition)", W3C Recommendation, August 2006, <http://www.w3.org/TR/2006/REC-xml-20060816/>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

1.3 Overview

This protocol describes the **XML** representation of documents that is used for client and server communication as described in [\[MS-ASCMD\]](#). The document data is included in protocol command requests when document data is being sent from the client to the server, and is included in protocol command responses when document data is returned from the server to the client.

1.4 Relationship to Other Protocols

This protocol describes the XML representation of documents that is used by the command requests and responses that are described in [\[MS-ASCMD\]](#). The protocol governing the transmission of these commands between the client and the server is described in [\[MS-ASCMD\]](#). The **Wireless Application Protocol (WAP) Binary XML (WBXML)**, as described in [\[MS-ASWBXML\]](#), is used to transmit the XML markup that constitutes the request body and the response body.

All simple data types in this document conform to the data type definitions that are described in [\[MS-ASDTYPE\]](#).

1.5 Prerequisites/Preconditions

None.

1.6 Applicability Statement

This protocol describes a set of elements that is used to communicate document data when using the commands described in [\[MS-ASCMD\]](#). This set of elements is applicable when communicating document data such as the document's name, location, estimated size, and visibility between a mobile device and a server. These elements are not applicable when sending calendar, e-mail, note, contact, or task data between a mobile device and a server.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

Preliminary

2 Messages

2.1 Transport

This protocol consists of a series of XML elements that are embedded inside of a command request or command response, as specified in [\[MS-ASCMD\]](#).

The XML markup that constitutes the request body or the response body that is transmitted between the client and the server uses Wireless Application Protocol (WAP) Binary XML (WBXML), as specified in [\[MS-ASWBXML\]](#).

2.2 Message Syntax

The markup that is used by this protocol MUST be well-formed XML, as specified in [\[XML\]](#).

This protocol defines **XML schema** elements for the **Document** class, which represents a document. The XML schema definition for the **Document** class is as follows, in accordance with the rules specified in [\[XMLSCHEMA1\]](#).

```
<?xml version="1.0" ?><xs:schema xmlns:tns="DocumentLibrary:"  
  attributeFormDefault="unqualified" elementFormDefault="qualified"  
  targetNamespace="DocumentLibrary:" xmlns:xs="http://www.w3.org/2001/XMLSchema"  
  xmlns:airsynibase="AirSyncBase:">  
  <xs:import namespace="AirSyncBase" />  
  <xs:element name="LinkId" type="xs:string" />  
  <xs:element name="DisplayName" type="xs:string" />  
  <xs:element name="IsFolder" type="xs:unsignedByte" />  
  <xs:element name="CreationDate" type="xs:dateTime" />  
  <xs:element name="LastModifiedDate" type="xs:dateTime" />  
  <xs:element name="IsHidden" type="xs:unsignedByte" />  
  <xs:element name="ContentLength" type="xs:unsignedByte" />  
  <xs:element name="ContentType" type="xs:unsignedByte" />  
</xs:schema>
```

2.2.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and is not significant for interoperability.

| Prefix | Namespace URI | Reference |
|----------------|---|---|
| (none) | DocumentLibrary | |
| airsynibase | AirSyncBase | [MS-ASAIRS] |
| itemoperations | ItemOperations | [MS-ASCMD] section 2.2.2.8 |
| search | Search | [MS-ASCMD] section 2.2.2.14 |
| xs | http://www.w3.org/2001/XMLSchema | [XMLSCHEMA1] |

2.2.2 Elements

Elements of the **Document** class are defined in two namespaces: **DocumentLibrary** and **AirSyncBase**. All **Document** class elements are specified in this document. However, elements defined in the **AirSyncBase** namespace are further specified in [\[MS-ASAIRS\]](#).

The following table summarizes the set of common XML schema element definitions defined by this specification. For details about how these elements are used by a particular operation, see sections [3.1.5.1](#), [3.1.5.2](#), [3.2.5.1](#), and [3.2.5.2](#).

| Element name | Description |
|--|---|
| LinkId (section 2.2.2.8) | The link to the document, specified as a Uniform Resource Identifier (URI) . |
| DisplayName (section 2.2.2.4) | The name of the document, as displayed by the client. |
| IsFolder (section 2.2.2.5) | Specifies whether the item is a folder or a document. |
| CreationDate (section 2.2.2.3) | The date and time when the document was first created. |
| LastModifiedDate (section 2.2.2.7) | The date and time when the document or its properties was last modified. |
| IsHidden (section 2.2.2.6) | Specifies whether this is a hidden object. |
| ContentLength (section 2.2.2.1) | The estimated size of the document, in bytes. |
| ContentType (section 2.2.2.2) | The Multipurpose Internet Mail Extensions (MIME) type of the binary-encoded content or content encoded with base64 encoding . |

2.2.2.1 ContentLength

The **ContentLength** element is a required child element of the **search:Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128.2) for **Document** class items in a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2) that specifies the estimated size, in bytes, of the document. For more details about the **Search** command response for **Document** class items, see section [3.2.5.2](#).

The value of this element is an **unsignedByte** data type, as specified in [\[MS-ASDTYPE\]](#) section 2.7.

Because documents accessed by using the ActiveSync protocol can be shared across a network, it is possible that the value of the **ContentLength** element will differ between the time the document description is retrieved and the time the document is accessed.

2.2.2.2 ContentType

The **ContentType** element is a required child element of the **search:Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128.2) for **Document** class items in a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2) that specifies the MIME type of the binary-encoded content or document encoded with base64 encoding, if known. For more details about the **Search** command response for **Document** class items, see section [3.2.5.2](#).

The value of this element is an **unsignedByte** data type, as specified in [\[MS-ASDTYPE\]](#) section 2.7.

2.2.2.3 CreationDate

The **CreationDate** element is a required child element of the **search:Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128.2) for **Document** class items in a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2) that specifies the date and time when the document was created. For more details about the **Search** command response for **Document** class items, see section [3.2.5.2](#).

The value of this element is a **datetime** data type in **Coordinated Universal Time (UTC)** format, as specified in [\[MS-ASDTYPE\]](#) section 2.3.

2.2.2.4 DisplayName

The **DisplayName** element is a required child element of the **search:Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128.2) for **Document** class items in a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2) that specifies the name of the document as it is displayed to the user. For more details about the **Search** command response for **Document** class items, see section [3.2.5.2](#).

The value of this element is a **string** data type, as specified in [\[MS-ASDTYPE\]](#) section 2.6.

2.2.2.5 IsFolder

The **IsFolder** element is a required child element of the **search:Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128.2) for **Document** class items in a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2) that specifies whether the item is a folder. For more details about the **Search** command response for **Document** class items, see section [3.2.5.2](#).

The value of this element is an **unsignedByte** data type, as specified in [\[MS-ASDTYPE\]](#) section 2.7. Valid values for this element are as follows.

| Value | Meaning |
|-------|---------------------------|
| 0 | The item is not a folder. |
| 1 | The item is a folder. |

2.2.2.6 IsHidden

The **IsHidden** element is a required child element of the **search:Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128.2) for **Document** class items in a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2) that specifies whether the document or folder is a hidden object. For more details about the **Search** command response for **Document** class items, see section [3.2.5.2](#).

The value of this element is an **unsignedByte** data type, as specified in [\[MS-ASDTYPE\]](#) section 2.7. The value of the **IsHidden** element MUST be one of the following values.

| Value | Meaning |
|-------|---------------------------------------|
| 0 | The document or folder is not hidden. |
| 1 | The document or folder is hidden. |

2.2.2.7 LastModifiedDate

The **LastModifiedDate** element is a required child element of the **search:Properties** element ([MS-ASCMD] section 2.2.3.128.2) for **Document** class items in a **Search** command response ([MS-ASCMD] section 2.2.2.14.2) that specifies the date and time that the document or its properties was last modified. For more details about the **Search** command response for **Document** class items, see section [3.2.5.2](#).

The value of this element is a **datetime** data type in **UTC** format, as specified in [MS-ASDTYPE] section 2.3.

2.2.2.8 LinkId

The **LinkId** element specifies the link to the document in the form of a URI. It is a required child element of the **itemoperations:Fetch** element ([MS-ASCMD] section 2.2.3.63.1) for **Document** class items in an **ItemOperations** command request ([MS-ASCMD] section 2.2.2.8.2) and an **ItemOperations** command response ([MS-ASCMD] section 2.2.2.8.3), a required child element of the **search:EqualTo** element ([MS-ASCMD] section 2.2.3.59) for **Document** class items in a **Search** command request ([MS-ASCMD] section 2.2.2.14.1), and a required child element of the **search:Properties** element ([MS-ASCMD] section 2.2.3.128.2) for **Document** class items in a **Search** command response ([MS-ASCMD] section 2.2.2.14.2).

For more details about how the **LinkId** element is used by the **ItemOperations** command request, the **Search** command request, the **ItemOperations** command response, and the **Search** command response, see sections [3.1.5.1](#), [3.1.5.2](#), [3.2.5.1](#), and [3.2.5.2](#), respectively.

3 Protocol Details

3.1 Client Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

Document class: A structured XML text block that adheres to the XML schema defined in section [2.2](#). It is returned by the server as part of a full XML response to the client command requests specified in section [3.1.5](#).

Command request: A WBXML formatted message that adheres to the command schemas specified in [\[MS-ASCMD\]](#).

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

3.1.4.1 Searching for Documents

The client searches for **Document** class data on a server by sending a **Search** command request ([\[MS-ASCMD\]](#) section 2.2.2.14.1) to the server.

3.1.4.2 Requesting Details for Specific Documents

The client requests **Document** class data for one or more individual documents by sending an **ItemOperations** command request ([\[MS-ASCMD\]](#) section 2.2.2.8.2) to the server that contains one or more **itemoperations:Fetch** elements ([\[MS-ASCMD\]](#) section 2.2.3.63.1).

3.1.4.3 Requesting the Document Body from the Server

Because the body of the document is not returned as part of the **Document** class data, the client submits the value of the **LinkID** element (section [2.2.2.8](#)) in a separate **ItemOperations** command request ([\[MS-ASCMD\]](#) section 2.2.2.8.2) to obtain the body of the document. The body of the document is returned as either text encoded with base64 encoding in the **itemoperations:Data** element ([\[MS-ASCMD\]](#) section 2.2.3.39.1) of the **ItemOperations** command response ([\[MS-ASCMD\]](#) section 2.2.2.8.3) or as binary data, depending on the content type that the client requested. For details about how the client requests a particular content type in an **ItemOperations** command request, see section [3.1.5.1](#).

3.1.5 Message Processing Events and Sequencing Rules

The following sections define how various elements of the **Document** class are used in the context of specific ActiveSync commands. For more details about the commands themselves, see [\[MS-ASCMD\]](#).

3.1.5.1 ItemOperations Command Request

A client uses an **ItemOperations** command request ([\[MS-ASCMD\]](#) section 2.2.2.8.2) that contains one or more **itemoperations:Fetch** elements ([\[MS-ASCMD\]](#) section 2.2.3.63.1) to retrieve data from the server for one or more individual documents.

The **LinkId** element (section [2.2.2.8](#)) is the only **Document** class element that can be included in an **ItemOperations** command request. The **LinkId** element is transmitted as a child element of the **itemoperations:Fetch** element ([\[MS-ASCMD\]](#) section 2.2.3.63.1).

A client can use the HTTP **header (2) MS-ASAcceptMultiPart: T** to specify that the server returns the document data in multipart binary format. If this header is not used, the document data is returned as text. For more details about this header (2), see [\[MS-ASCMD\]](#) section 2.2.2.8.1.

The **ItemOperations** command is specified in [\[MS-ASCMD\]](#) section 2.2.2.8.

3.1.5.2 Search Command Request

A client uses the **Search** command request ([\[MS-ASCMD\]](#) section 2.2.2.14.1) to retrieve **Document** class items that match the criteria specified by the client.

The **LinkId** element (section [2.2.2.8](#)) is a required element in a **Search** command request, and is transmitted as a child element of the **search:EqualTo** element ([\[MS-ASCMD\]](#) section 2.2.3.59). The **search:Value** element ([\[MS-ASCMD\]](#) section 2.2.3.180) can also be included as a child of the **search:EqualTo** element. The value of the **search:Value** element is a string that describes the Universal Naming Convention (UNC) path of a file on a file share. A full example of this usage is provided in [\[MS-ASCMD\]](#) section 4.22.1.

If the **LinkId** element is not included in a **Search** command request, then the server MUST respond with protocol error 2.

The **Search** command is specified in [\[MS-ASCMD\]](#) section 2.2.2.14.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Server Details

3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations

adhere to this model as long as their external behavior is consistent with that described in this document.

Document class: A structured XML text block that adheres to the XML schema defined in section [2.2](#). It is returned by the server as part of a full XML response to the client command requests specified in section [3.1.5](#).

Command response: A WBXML formatted message that adheres to the command schemas specified in [\[MS-ASCMD\]](#).

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layered Triggered Events

3.2.4.1 Searching for Documents

Searching for **Document** class data is initiated by the client, as specified in section [3.1.4.1](#). The server responds with a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2).

3.2.4.2 Retrieving Details for Specific Documents

Retrieval of **Document** class data for one or more individual documents is initiated by the client, as specified in section [3.1.4.2](#). The server responds with an **ItemOperations** command response ([\[MS-ASCMD\]](#) section 2.2.2.8.3).

3.2.4.3 Retrieving the Document Body

Retrieval of the body of a document is initiated by the client, as specified in section [3.1.4.3](#). The server responds with an **ItemOperations** command response ([\[MS-ASCMD\]](#) section 2.2.2.8.3), which returns the body of the document either as text encoded with base64 encoding in the **itemoperations:Data** element ([\[MS-ASCMD\]](#) section 2.2.2.8.3) of the response or as binary text in multiple parts if the command request was a multi-part request.

3.2.5 Message Processing Events and Sequencing Rules

The following sections define how various elements of the **Document** class are used in the context of specific commands. For more details about the commands themselves, see [\[MS-ASCMD\]](#).

3.2.5.1 ItemOperations Command Response

When a client uses an **ItemOperations** command request ([\[MS-ASCMD\]](#) section 2.2.2.8.2) to retrieve data from the server for one or more individual documents, as specified in section [3.1.5.1](#), the server responds with an **ItemOperations** command response ([\[MS-ASCMD\]](#) section 2.2.2.8.3).

The server MUST return a **Document** class XML block for every item that matches the criteria specified in the client command request. The server can return zero or more **Document** class blocks in its response, depending on how many document items match the criteria specified in the client command request.

The **LinkId** element (section [2.2.2.8](#)) is the only **Document** class element returned in an **ItemOperations** command response. The **LinkId** element is transmitted as a child element of the **ItemOperations:Fetch** element ([\[MS-ASCMD\]](#) section 2.2.3.63.1).

If an **ItemOperations** command request for the body of the document was made using the **MS-ASAcceptMultiPart: T** header (2), then the server MUST respond by providing the document body as binary data in multiple parts. Otherwise, the server MUST transmit the document as data encoded with base64 encoding within the **itemoperations:Data** element ([\[MS-ASCMD\]](#) section 2.2.3.39.1) of the **ItemOperations** command response. For more details about content delivery for documents, see [\[MS-ASCMD\]](#) section 2.2.2.8.1.

The **ItemOperations** command is specified in [\[MS-ASCMD\]](#) section 2.2.2.8.

3.2.5.2 Search Command Response

When a client uses the **Search** command request ([\[MS-ASCMD\]](#) section 2.2.2.14.1) to retrieve **Document** class items that match the criteria specified by the client, as specified in section [3.1.5.2](#), the server responds with a **Search** command response ([\[MS-ASCMD\]](#) section 2.2.2.14.2).

The server MUST return a **Document** class XML block for every item that matches the criteria specified in the client command request. The server can return zero or more **Document** class blocks in its response, depending on how many document items match the criteria specified in the client command request.

Any of the elements for the **Document** class, as specified in section [2.2.2](#), can be included in a **Search** command response. **Document** class elements are returned as child elements of the **search:Properties** element ([\[MS-ASCMD\]](#) section 2.2.3.128) in a **Search** command response.

The **Search** command is specified in [\[MS-ASCMD\]](#) section 2.2.2.14.

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

4 Protocol Examples

4.1 Searching for a Document by LinkId

The following example demonstrates a client request to search for a document by using the specified **LinkId** element (section [2.2.2.8](#)) value (which in this example is the UNC path of the document), and the server response.

Request:

```
<?xml version="1.0" encoding="utf-8"?>
<Search xmlns="Search:" xmlns:A="DocumentLibrary:">
  <Store>
    <Name>DocumentLibrary</Name>
    <Query>
      <EqualTo>
        <A:LinkId/>
        <Value>\\EXCH-D-810\DocumentShare\document.txt</Value>
      </EqualTo>
    </Query>
    <Options>
      <Range>0-999</Range>
    </Options>
  </Store>
</Search>
```

Response:

```
<?xml version="1.0" encoding="utf-8"?>
<Search
xmlns:documentlibrary="DocumentLibrary:" >
  <Status>1 Success</Status>
  <Response>
    <Store>
      <Status>1 Success</Status>
      <Result>
        <Properties>
          <documentlibrary:LinkId>\\exch-d-
810\DocumentShare\document.txt</documentlibrary:LinkId>
          <documentlibrary:DisplayName>document.txt</documentlibrary:DisplayName>
          <documentlibrary:IsFolder>0</documentlibrary:IsFolder>
          <documentlibrary:CreationDate>2009-11-
11T17:07:08.156Z</documentlibrary:CreationDate>
          <documentlibrary:LastModifiedDate>2009-11-
11T17:07:17.613Z</documentlibrary:LastModifiedDate>
          <documentlibrary:IsHidden>0</documentlibrary:IsHidden>
          <documentlibrary:ContentLength>13</documentlibrary:ContentLength>
          <documentlibrary:ContentType>text/plain</documentlibrary:ContentType>
        </Properties>
      </Result>
      <Range>0-0</Range>
      <Total>1</Total>
    </Store>
  </Response>
</Search>
```


4.2 Retrieving the Text of a Document by Using the ItemOperations Command

The following example demonstrates a client request to retrieve the data for a document by using the **ItemOperations** command ([\[MS-ASCMD\]](#) section 2.2.2.8), and the server response. In the XML response below, the value of the **itemoperations:Data** element ([\[MS-ASCMD\]](#) section 2.2.3.39.1) has been truncated for the sake of brevity.

Request:

```
<?xml version="1.0" encoding="utf-8"?>
<ItemOperations xmlns:documentlibrary="DocumentLibrary:" xmlns="ItemOperations:">
  <Fetch>
    <Store>DocumentLibrary</Store>
    <documentlibrary:LinkId>\\EXCH-D-810\DocumentShare\Word
Document.docx</documentlibrary:LinkId>
  </Fetch>
</ItemOperations>
```

Response:

```
<?xml version="1.0" encoding="utf-8"?>
<ItemOperations
xmlns:documentlibrary="DocumentLibrary:"
>
  <Status>1</Status>
  <Response>
    <Fetch>
      <Status>1</Status>
      <documentlibrary:LinkId>\\EXCH-D-810\DocumentShare\Word
Document.docx</documentlibrary:LinkId>
      <Properties>
        <Data>UEsDBBQABgAIAAAAIQDd/+ImYzsKNchci+VLqQHEkJU4+RzBv1jKu6vsvf0VwOamabaWQ1pZ+9AtcdYN1/WD103G
n4KZu/Yy4kVyAdhb9kuYipsSc
ZyjWop9SwabDDPJZ2RYqwkNuBpotX1RP9fi46FLAmhCYnP83x1nANaXg902aJ5x687HyFZLBZ9e/tDg7MvaD4BAAD//wM
AUEsDBBQABgAIAAAAIQDWZLNR
+gAAADEDAACAAgBd29yZC9fcmVscy9kb2N1bWVudC54bWwucmVscyCiBAEooAABAAAAAAAAAAAAAAAAAAAAAAAAAAAA
AAAAAAAAAAAAAAAA...</Data>
        <Version>2009-11-11T19:15:45.177Z</Version>
      </Properties>
    </Fetch>
  </Response>
</ItemOperations>
```

4.3 Browsing a Document Folder

The following example demonstrates how a client can use the **Search** command request ([\[MS-ASCMD\]](#) section 2.2.2.14.1) to browse a folder on a remote share. The client submits a request for a folder to view, and the server responds with a list of the folder's contents.

Request:

```
<?xml version="1.0" encoding="utf-8"?>
<Search xmlns="Search:" xmlns:documentlibrary="DocumentLibrary:">
  <Store>
    <Name>DocumentLibrary</Name>
```

```

<Query>
  <EqualTo>
    <documentlibrary:LinkId/>
    <Value>\\myserver\myshare</Value>
  </EqualTo>
</Query>
<Options>
  <Range>0-999</Range>
</Options>
</Store>
</Search>

```

Response:

```

<?xml version="1.0" encoding="utf-8"?>
<Search xmlns="Search:" xmlns:documentlibrary="DocumentLibrary:">
  <Status>1</Status>
  <Response>
    <Store>
      <Status>1</Status>
      <Result>
        <Properties>
          <documentlibrary:LinkId/>\\myserver\myshare</documentlibrary:LinkId>
          <documentlibrary:DisplayName>d$</documentlibrary:DisplayName>
          <documentlibrary:IsFolder>1</documentlibrary:IsFolder>
          <documentlibrary:CreationDate>2007-10-
02T00:34:28.686Z</documentlibrary:CreationDate>
          <documentlibrary:LastModifiedDate>2009-11-
13T21:48:20.919Z</documentlibrary:LastModifiedDate>
          <documentlibrary:IsHidden>1</documentlibrary:IsHidden>
        </Properties>
      </Result>
      <Result>
        <Properties>
          <documentlibrary:LinkId/>\\myserver\myshare\blah.txt</documentlibrary:LinkId>
          <documentlibrary:DisplayName>blah.txt</documentlibrary:DisplayName>
          <documentlibrary:IsFolder>0</documentlibrary:IsFolder>
          <documentlibrary:CreationDate>2007-10-
02T18:26:52.265Z</documentlibrary:CreationDate>
          <documentlibrary:LastModifiedDate>2009-04-
02T02:57:55.843Z</documentlibrary:LastModifiedDate>
          <documentlibrary:IsHidden>1</documentlibrary:IsHidden>
        </Properties>
      </Result>
      <Result>
        <Properties>
          <documentlibrary:LinkId/>\\myserver\myshare\foo</documentlibrary:LinkId>
          <documentlibrary:DisplayName>foo</documentlibrary:DisplayName>
          <documentlibrary:IsFolder>1</documentlibrary:IsFolder>
          <documentlibrary:CreationDate>2009-10-
13T00:43:44.660Z</documentlibrary:CreationDate>
          <documentlibrary:LastModifiedDate>2009-10-
13T00:46:17.421Z</documentlibrary:LastModifiedDate>
          <documentlibrary:IsHidden>0</documentlibrary:IsHidden>
        </Properties>
      </Result>
      <Range>0-2</Range>
      <Total>3</Total>

```

```
</Store>  
</Response>  
</Search>
```

Preliminary

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

Preliminary

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2007 Service Pack 1 (SP1)
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 2013 Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

Preliminary

8 Index

A

Abstract data model
[client](#) 12
[server](#) 13
[Applicability](#) 6

C

[Capability negotiation](#) 6
[Change tracking](#) 22
Client
[abstract data model](#) 12
[initialization](#) 12
[message processing](#) 13
[other local events](#) 13
[sequencing rules](#) 13
[timer events](#) 13
[timers](#) 12

D

Data model - abstract
[client](#) 12
[server](#) 13

E

Elements
[ContentLength](#) 9
[ContentType](#) 9
[CreationDate](#) 10
[DisplayName](#) 10
[IsFolder](#) 10
[IsHidden](#) 10
[LastModifiedDate](#) 11
[LinkId](#) 11
[Elements message](#) 9
Examples
[browsing a document folder](#) 17
[retrieving the text of a document](#) 17
[searching for a document by LinkId](#) 16

F

[Fields - vendor-extensible](#) 7

G

[Glossary](#) 5

I

[Implementer - security considerations](#) 20
[Index of security parameters](#) 20
[Informative references](#) 6
Initialization
[client](#) 12
[server](#) 14

[Introduction](#) 5

M

Message processing
[client](#) 13
[server](#) 14
Messages
[Elements](#) 9
[Namespaces](#) 8
[syntax](#) 8
[transport](#) 8

N

[Namespaces message](#) 8
[Normative references](#) 5

O

Other local events
[client](#) 13
[server](#) 15
[Overview \(synopsis\)](#) 6

P

[Parameters - security index](#) 20
[Preconditions](#) 6
[Prerequisites](#) 6
[Product behavior](#) 21

R

[References](#) 5
[informative](#) 6
[normative](#) 5
[Relationship to other protocols](#) 6

S

Security
[implementer considerations](#) 20
[parameter index](#) 20
Sequencing rules
[client](#) 13
[server](#) 14
Server
[abstract data model](#) 13
[initialization](#) 14
[message processing](#) 14
[other local events](#) 15
[sequencing rules](#) 14
[timer events](#) 15
[timers](#) 14
[Standards assignments](#) 7

T

Timer events
[client](#) 13
[server](#) 15
Timers
[client](#) 12
[server](#) 14
[Tracking changes](#) 22
[Transport](#) 8

V

[Vendor-extensible fields](#) 7
[Versioning](#) 6

Preliminary