

[MS-ASMS]: ActiveSync Short Message Service Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplq@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
04/10/2009	0.1		Initial Availability.
07/15/2009	1.0	Major	Revised and edited for technical content.
11/04/2009	2.0.0	Major	Updated and revised the technical content.

Table of Contents

1 Introduction	5
1.1 Glossary.....	5
1.2 References.....	5
1.2.1 Normative References	5
1.2.2 Informative References	6
1.3 Protocol Overview	6
1.4 Relationship to Other Protocols.....	6
1.5 Prerequisites/Preconditions.....	6
1.6 Applicability Statement.....	6
1.7 Versioning and Capability Negotiation.....	6
1.8 Vendor-Extensible Fields	6
1.9 Standards Assignments	7
2 Messages	8
2.1 Transport.....	8
2.2 Message Syntax.....	8
2.2.1 Complex Types.....	9
2.2.2 Elements.....	9
2.2.2.1 SMS Class	10
2.2.2.1.1 From.....	10
2.2.2.1.2 DateReceived.....	10
2.2.2.1.3 To.....	10
2.2.2.2 Other Elements	11
2.2.2.2.1 Class (as Child of Options)	11
2.2.2.2.2 Class (as Child of Add, Change, or Delete).....	11
2.2.2.2.3 DeviceInformation.Set.EnableOutboundSMS.....	11
3 Protocol Details.....	12
3.1 Client Details.....	12
3.1.1 Abstract Data Model.....	12
3.1.2 Timers	12
3.1.3 Initialization	12
3.1.4 Higher-Layer Triggered Events	12
3.1.4.1 Synchronizing SMS Items.....	12
3.1.4.1.1 Options	12
3.1.4.1.1.1 Sticky Options.....	13
3.1.4.1.1.2 Filtering	13
3.1.4.1.2 Making Changes Involving SMS Items	13
3.1.4.1.3 Special Case for Synchronization of Outbox	13
3.1.4.2 Estimating the Number of Changes.....	13
3.1.4.3 Provisioning for Relay of Outbound SMS Messages.....	14
3.1.5 Message Processing Events and Sequencing Rules	14
3.1.5.1 Sending Outbound SMS Messages	14
3.1.6 Timer Events.....	15
3.1.7 Other Local Events	15
3.2 Server Details.....	15
3.2.1 Abstract Data Model.....	15
3.2.2 Timers	15
3.2.3 Initialization	15
3.2.4 Higher-Layer Triggered Events	15

3.2.5	Message Processing Events and Sequencing Rules	15
3.2.5.1	Processing a Sync Request	15
3.2.5.2	Processing a GetItemEstimate Request	16
3.2.5.3	Processing a Settings Request	16
3.2.6	Timer Events	16
3.2.7	Other Local Events	16
4	Protocol Examples	17
4.1	Synchronizing E-Mail Items and SMS Items	17
4.2	Synchronizing Only SMS Items	17
4.3	SMS Message Added By the Server	18
4.4	Enabling Outbound SMS Messages	19
5	Security	20
5.1	Security Considerations for Implementers	20
5.2	Index of Security Parameters	20
6	Appendix A: Product Behavior	21
7	Change Tracking	22
8	Index	25

1 Introduction

This document specifies the ActiveSync **Short Message Service (SMS)** protocol, which is an **XML**-based format that provides the mechanisms for a mobile device to synchronize SMS messages with the server and for the server to send SMS messages through the mobile device.

1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

class
code page
conversation
conversation ID
conversation index
Coordinated Universal Time (UTC)
MIME
non-delivery report (NDR)
Short Message Service (SMS)
WAP Binary XML (WBXML)
XML
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-ASAIRS] Microsoft Corporation, "[ActiveSync AirSyncBase Namespace Protocol Specification](#)", December 2008.

[MS-ASCMD] Microsoft Corporation, "[ActiveSync Command Reference Protocol Specification](#)", December 2008.

[MS-ASDTYPE] Microsoft Corporation, "[ActiveSync Data Types](#)", December 2008.

[MS-ASEMAIL] Microsoft Corporation, "[ActiveSync E-Mail Class Protocol Specification](#)", December 2008.

[MS-ASWBXML] Microsoft Corporation, "[ActiveSync WAP Binary XML \(WBXML\) Protocol Specification](#)", December 2008.

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", June 2008.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

[XML] Bray, T., et al., "Extensible Markup Language (XML) 1.0 (Fifth Edition)", <http://www.w3.org/TR/REC-xml/>.

1.2.2 Informative References

None.

1.3 Protocol Overview

The ActiveSync Short Message Service (SMS) protocol is an XML-based format that is used to do the following:

- Enable a mobile device to synchronize SMS messages with the server.
- Provision the server to send outgoing SMS messages through the mobile device.

The protocol also includes XML elements to represent SMS message data. The SMS data is included in protocol command requests when SMS data is being sent from the client to the server, and is included in protocol command responses when SMS data is retrieved from the server. SMS data includes some of the same header information as e-mail data (for details about the E-mail **class**, see [\[MS-ASEMAIL\]](#)) such as to and from, as well as body, flag, and importance.

1.4 Relationship to Other Protocols

The ActiveSync Short Message Service (SMS) protocol consists of a series of XML elements that are embedded inside a command request or a command response. For details about command requests and responses, see [\[MS-ASCMD\]](#). The **WAP Binary XML (WBXML)**, specified in [\[MS-ASWBXML\]](#), is used to transmit the XML markup that constitutes the request body and the response body.

The ActiveSync Short Message Service (SMS) protocol defines elements and complex types according to the data type definitions that are specified in [\[MS-ASDTYPE\]](#). The E-mail **code page**, specified in [\[MS-ASWBXML\]](#) section 2.2.1.2.3, is used to encapsulate the SMS class data.

1.5 Prerequisites/Preconditions

None.

1.6 Applicability Statement

The ActiveSync Short Message Service (SMS) protocol is applicable for mobile devices that need to synchronize SMS messages with the server and want to allow the server to use it for relaying outbound SMS messages.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The ActiveSync Short Message Service (SMS) protocol consists of a series of XML elements that are embedded inside a command request or a command response. The XML markup that constitutes the request body or the response body is transmitted between client and server by using WAP Binary XML (WBXML), as specified in [\[MS-ASWBXML\]](#).

The mobile device uses standard mobile network protocols, such as GSM and CDMA, to send outbound SMS messages.

2.2 Message Syntax

The XML markup that is used by the ActiveSync Short Message Service (SMS) protocol MUST be well-formed XML, as specified in [\[XML\]](#). The XML elements are embedded inside a command request or command response. For details about command requests and responses, see [\[MS-ASCMD\]](#).

The complex types and elements of the ActiveSync Short Message Service (SMS) protocol are defined in four namespaces: **AirSync**, **Email**, **AirSyncBase**, and **Settings**. The **XML schema** definition for the SMS class is as follows. This schema represents the full set of data that is returned by the server in a **Sync** command response.

```
<?xml version="1.0" ?>
<xs:schema xmlns:tns="EMAIL:" attributeFormDefault="unqualified"
  elementFormDefault="qualified"
  targetNamespace="EMAIL:" xmlns:xs="http://www.w3.org/2001/XMLSchema" xmlns:A="AirSyncBase:">
  <xs:import namespace="AirSyncBase" />
  <xs:element name="To" type="xs:string" />
  <xs:element name="From" type="xs:string" />
  <xs:element name="DateReceived" type="xs:dateTime" />
  <xs:element name="Importance" type="xs:unsignedByte" />
  <xs:element name="Read" type="xs:unsignedByte" />
  <xs:element name="Body" type="A:Body" />
  <xs:element name="InternetCPID" type="xs:string" />
  <xs:element name="Flag">
    <xs:complexType>
      <xs:sequence>
        <xs:element name="Subject" type="xs:string" />
        <xs:element name="Status" type="xs:unsignedByte" />
        <xs:element name="FlagType" type="xs:string" />
        <xs:element name="DateCompleted" type="xs:dateTime" />
        <xs:element name="CompleteTime" type="xs:dateTime" />
        <xs:element name="StartDate" type="xs:dateTime" />
        <xs:element name="DueDate" type="xs:dateTime" />
        <xs:element name="UTCStartDate" type="xs:dateTime" />
        <xs:element name="UTCEndDate" type="xs:dateTime" />
        <xs:element name="ReminderSet" type="xs:unsignedByte" />
        <xs:element name="ReminderTime" type="xs:dateTime" />
        <xs:element name="OrdinalDate" type="xs:dateTime" />
        <xs:element name="SubOrdinalDate" type="xs:dateTime" />
      </xs:sequence>
    </xs:complexType>
  </xs:element>
  <xs:element name="ConversationId" type="xs:string" />
  <xs:element name="ConversationIndex" type="xs:string" />
</xs:schema>
```


</xs:schema>

2.2.1 Complex Types

The following table summarizes the set of common XML schema complex types that are defined by the SMS class in the **Email** and **AirSyncBase** namespaces. These complex types are used to specify SMS data. For more details about these complex types, see [\[MS-AEMAIL\]](#) section 2.2.1.

Complex Type	Description
Body	A description of the body text, along with its data.
Flag	The flag that is associated with the item, along with its current status.

2.2.2 Elements

Elements MUST NOT have child elements in either the command request or response.

The following table summarizes the set of common XML schema elements that are defined by this specification for use in the **GetItemEstimate** command, **Sync** command, or **Settings** command.

Element	Description
Class (as child of Options)	Specifies the class to which the options apply in a GetItemEstimate command request or a Sync command request.
Class (as child of Add , Change , or Delete)	Specifies the class to which the Add , Change , or Delete operation applies in a Sync command request or response.
DeviceInformation.Set.EnableOutboundSMS	Used in a Settings command request to enable or disable the sending of outbound SMS messages through a mobile device.

The following table summarizes the set of common XML schema elements that are defined by the SMS class in the **Email** namespace. These elements are used to specify SMS data. The semantics for all these elements, except **To**, **From**, and **DateReceived**, are the same for both the SMS class and the E-mail class. The **To**, **From**, and **DateReceived** elements for the SMS class are further specified in [2.2.2.1](#) of this document. For more details about all the other elements, see [\[MS-AEMAIL\]](#) section 2.2.2.

Element	Description
To	The list of recipients.
From	The e-mail address of the individual who sent the message.
DateReceived	The date and time that the message was received by the device.
Importance	The importance of the message, as determined by the sender.
Read	Specifies whether the message has been read.
InternetCPID	The original code page ID from the MIME message representation of the SMS

Element	Description
	item.
Flag.Subject	The subject of the flag as it would appear in a task list.
Flag.Status	The current status of the flag.
Flag.FlagType	The value of the Flag To: follow up field.
Flag.DateCompleted	The date on which the flagged item was completed.
Flag.CompleteTime	The time at which the flagged item was marked as finished.
Flag.StartDate	The start date of the flagged item.
Flag.DueDate	The due date of the flagged item.
Flag.UTCStartDate	The Coordinated Universal Time (UTC) value of the local StartDate .
Flag.UCCEndDate	The UTC value of the local DueDate .
Flag.ReminderSet	Identifies whether a reminder has been set for this flagged item.
Flag.ReminderTime	The date and time that the reminder is supposed to occur.
Flag.OrdinalDate	The time at which the client set the flag.
Flag.SubOrdinalDate	A string used to sort items.
ConversationId	Specifies the conversation ID for an SMS item.
ConversationIndex	Specifies the conversation index for an SMS item.

2.2.2.1 SMS Class

2.2.2.1.1 From

The **From** element is an optional element that specifies the individual who sent the SMS item.

The value of this element is a **string** type, as specified in [\[MS-ASDTYPE\]](#) section 2.1. The format of the string is as follows, including the quotes and square brackets:

"Sender's Name" [MOBILE:Sender's phone number]

Sender's Name specifies the name of the sender and is optional. *Sender's phone number* specifies the mobile telephone number of the sender.

2.2.2.1.2 DateReceived

The **DateReceived** element is an optional element that specifies the date and time when the SMS item is sent, if the item is in the Sent Items folder.

The value of this element is a **date/time** type, as specified in [\[MS-ASDTYPE\]](#) section 2.6.

2.2.2.1.3 To

The **To** element is an optional element that specifies the list of primary recipients

The value of this element is a **string** type, as specified in [\[MS-ASDTYPE\]](#) section 2.1. The value comprises one or more e-mail addresses. If there are multiple e-mail addresses, then they are separated by commas.

2.2.2.2 Other Elements

2.2.2.2.1 Class (as Child of Options)

The options Class element is an optional child element of the **Options** element in the **GetItemEstimate** command request or the **Sync** command request. It specifies the class to which the options apply. For SMS items, the value is "SMS".

2.2.2.2.2 Class (as Child of Add, Change, or Delete)

The Class element is an optional child element of the **Add**, **Change**, or **Delete** element in the **Sync** command. The class element is used in the **Sync** command as follows:

- In the **Sync** command response from the server to add, change, or delete an SMS item.
- In the **Sync** command request from the client to add an SMS item.

The class element specifies the class to which the **Add**, **Change**, or **Delete** operation applies in a **Sync** command request or response. For SMS items, the value is "SMS".

2.2.2.2.3 DeviceInformation.Set.EnableOutboundSMS

The **DeviceInformation.Set.EnableOutboundSMS** element is optional. This element is used in a **Settings** command request to provision the server for sending outbound SMS messages through the mobile device. Outbound SMS messages are sent only through mobile devices that enable it.

If this element is set to 1, the mobile device can be used to send outbound SMS messages. If this element is set to 0, the mobile device will not be used to send outbound SMS messages. Devices that were previously enabled, but no longer want to act as SMS transport agents for the server, can reset the property to zero on the server by sending a **Settings** command request with the **DeviceInformation.Set.EnableOutboundSMS** element set to 0.

3 Protocol Details

3.1 Client Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

SMS class: A set of complex types and elements that specifies an SMS item. SMS class data is included in command requests that are sent to the server when SMS items need to be retrieved or synchronized.

Command request: A WBXML-formatted message that adheres to the command schemas specified in [\[MS-ASCMD\]](#).

Relay of outbound SMS messages: The server can use a mobile device client to relay outbound SMS messages if the mobile device client has provisioned the server to do so.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

3.1.4.1 Synchronizing SMS Items

A client initiates synchronization of data with the server by sending a **Sync** command request to the server. The **Sync** command request synchronizes the client's data with the data currently stored by the server. Synchronization of SMS items is allowed only on Inbox, Outbox, and Sent Items collections.

The **Sync** command request is further specified in [\[MS-ASCMD\]](#) section 2.2.1.19.1.

3.1.4.1.1 Options

If the client wants to synchronize SMS items for a given folder, the **Options** block of the **Sync** request includes the class element set to the value "SMS". If the class element is not included in the **Options** block, that set of options applies to the default class of the given folder, in which case, only the items of the default type for the given folder are synchronized. If no **Options** block is included in the **Sync** request, only items of the default class for the given folder are synchronized.

A maximum of two **Options** blocks are allowed within a collection block, namely one for the default class of the given folder and one for SMS items (class is set to "SMS" to indicate SMS items).

SMS items can only be synchronized within folders that natively contain e-mail messages.

For more details about the class element for **Options**, see section [2.2.2.2.1](#).

3.1.4.1.1.1 Sticky Options

Sticky options, which allow a client to send requests that direct the server to use the previous set of options, are supported. As a result of this, the client **MUST** send all sets of options if any option has changed. For example, if the truncation limit has increased for SMS items and the client is synchronizing both SMS items and e-mail items for a given folder, the **Sync** request **MUST** include two **Options** blocks. If one set of options is omitted from the request, the server presumes that the item type that corresponds to the missing set of options is no longer desired and soft-deletes are issued for the items of that type.

3.1.4.1.1.2 Filtering

SMS items can be filtered. The same filter values (0 through 5) that are used to filter e-mail items are also used to filter SMS items.

3.1.4.1.2 Making Changes Involving SMS Items

SMS items can be changed (updated) or deleted the same way that e-mail items are changed or deleted. SMS items can also be added. When an SMS item is added, changed, or deleted, the client sends a **Sync** command request that includes the **Add**, **Change**, or **Delete** types, respectively.

The SMS data is specified in the SMS class complex types and elements, which **MUST** be children of the **ApplicationData** type, as specified in [\[MS-ASCMD\]](#) section 2.2.1.19.1.7. The following restrictions apply:

- **Sync** request with **Add**: The conversation ID and conversation index cannot be sent to the server by clients when adding an SMS item to the server; the conversation ID and conversation index, specified in the **ConversationId** and **ConversationIndex** elements, respectively, are returned by the server in the **Sync** command response along with the server ID for the SMS item that was added.
- **Sync** request with **Change**: The client is allowed to update only the read status and the flags of an SMS item. Therefore, only the **Read** element and child elements of the **Flag** type can be specified as part of the **Change** type in the **Sync** command request.

See [2.2](#) for details about the SMS class complex types and elements. For more details about the **Add**, **Change**, or **Delete** types in the **Sync** command request, see [\[MS-ASCMD\]](#) section 2.2.1.19.1.

3.1.4.1.3 Special Case for Synchronization of Outbox

When a mobile device is enabled to send an outbound SMS message, the mobile device **MUST** synchronize the SMS items in the user's Outbox. It **SHOULD** do so at regular, short intervals (about every 15 minutes) or leverage hanging synchronization to provide the user with the best experience in sending SMS items.

The **Sync** command response is further specified in [\[MS-ASCMD\]](#) section 2.2.1.19.2.

3.1.4.2 Estimating the Number of Changes

The client sends a **GetItemEstimate** command request to the server to get an estimate of the number of changes (resulting from add, change, and delete operations) to SMS items for a given e-mail folder. The estimate will include changes to SMS items for that e-mail folder only if the request includes an **Options** block with the **Class** element set to "SMS".

A maximum of two **Options** blocks are allowed within a **Collection** block, namely one for the default class of the given folder and one for SMS items (**Class** element is set to "SMS" to indicate an

SMS item). An SMS **Options** block can be included only within a collection block that specifies one of the following folders:

- Inbox
- Outbox
- Sent Items

For more details about the **Class** element for **Options**, see section [2.2.2.2.1](#). The **GetItemEstimate** command request is further specified in [\[MS-ASCMD\]](#) section 2.2.1.7.1.

3.1.4.3 Provisioning for Relay of Outbound SMS Messages

The client sends a **Settings** command request to provision the server for sending outbound SMS messages through the mobile device. Outbound SMS messages are sent only through mobile devices that enable it. To enable outbound SMS messages, the following elements are included as children of the **Set** element in the **DeviceInformation** block of the **Settings** command request:

- **EnableOutboundSMS**, set to 1. See section [2.2.2.2.3](#).
- **PhoneNumber**, specifying the mobile device's telephone number.

To disable outbound SMS, the **EnableOutboundSMS** element is set to 0. In this case, the **PhoneNumber** element is not needed.

For more details about the **EnableOutboundSMS** element, see section [2.2.2.2.3](#). For more details about the **Settings** command request, see [\[MS-ASCMD\]](#) section 2.2.1.16.1.

3.1.5 Message Processing Events and Sequencing Rules

3.1.5.1 Sending Outbound SMS Messages

The mobile device performs the following tasks to send an outgoing SMS message:

1. The client MUST synchronize the SMS items in the user's Outbox. See section [3.1.4.1](#) for details about synchronizing SMS items. Any SMS items that the server adds to the Outbox folder are outgoing SMS messages. It is important that the client either synchronize the Outbox at regular, short intervals (about every 15 minutes) or retrieve the outgoing SMS items by using hanging synchronization. Doing so allows the client to send SMS items in the shortest possible interval.
2. The client MUST send the outgoing SMS items via the mobile device's wireless network. The client sends the given SMS item to all of the mobile recipients provided by the server. The client MUST logically split the item's body as necessary to comply with its network and MUST enable the reassembling of the body on the receiver's phone.
3. If a problem occurs with the message delivery, the client SHOULD generate a **non-delivery report (NDR)** and post it in the user's Inbox by sending a **Sync** request that includes the **Add** type. See section [3.1.4.1.2](#) for details about adding SMS items to a folder.
4. The client MUST delete the outgoing SMS items by sending a **Sync** request that includes the **Delete** type. See section [3.1.4.1.2](#) for details about deleting SMS items from a folder.

For more details about synchronization processing and sequencing, see [\[MS-ASCMD\]](#) sections [3.1.5.2](#) and [3.1.5.3](#)

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Server Details

3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

SMS class: A set of complex types and elements that specifies an SMS item. SMS class data is included in command requests that are sent to the server when SMS items need to be retrieved or synchronized.

Command response: A WBXML-formatted message that adheres to the command schemas specified in [\[MS-ASCMD\]](#). The server can return zero or more SMS class blocks in its command response, depending on how many SMS items match the criteria specified in the client's command request. The server **MUST** return an SMS class XML block for every SMS item that matches the criteria specified in the client command request.

Relay of outbound SMS messages: The server can use a mobile device client to relay outbound SMS messages if the mobile device client has provisioned the server to do so.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

None.

3.2.5 Message Processing Events and Sequencing Rules

3.2.5.1 Processing a Sync Request

Synchronization of SMS items is initiated by the client, as specified in section [3.1.4.1](#). The server responds with a **Sync** command response. To send SMS class data back to the client, the server includes an **ApplicationData** type in the **Sync** command response. The SMS class data is specified in the SMS class complex types and elements (section [2.2](#)), which **MUST** be children of the **ApplicationData** type, as specified in [\[MS-ASCMD\]](#) section 2.2.1.19.2.2.

The server **MUST NOT** send SMS items to the client if the client did not request them.

The server returns status code 4 (protocol error) in the **Sync** command response for the following situations:

- The **Sync** command request includes more than two **Options** blocks
- The **Sync** command request includes an **Options** block that specifies a class other than "SMS" or "Email"
- The **Sync** command request includes an **Options** block for a collection that is not Inbox, Outbox, or Sent Items.

The **Sync** command response is further specified in [\[MS-ASCMD\]](#) section 2.2.1.19.2. For more details about synchronization processing and sequencing, see [\[MS-ASCMD\]](#) sections [3.1.5.2](#) and [3.1.5.3](#)

3.2.5.2 Processing a GetItemEstimate Request

The client sends a **GetItemEstimate** command request, as specified in section [3.1.4.2](#). The server sends a **GetItemEstimate** command response with an estimate of the total number of changes (resulting from add, change, and delete operations) for a given folder. The estimate includes the changes to items of the class types specified in the request. The estimate includes changes to SMS items for the specified e-mail folders only if the request includes an **Options** block with the class element set to "SMS".

The **GetItemEstimate** command response is further specified in [\[MS-ASCMD\]](#) section 2.2.1.7.2.

3.2.5.3 Processing a Settings Request

The client sends a **Settings** command request, as specified in [3.1.4.3](#). If the **Settings** command request includes the **EnableOutboundSMS** element set to 1 and no telephone number is specified for the mobile device, the server returns status code 5 (invalid arguments) in the **Settings** command response.

If the **Settings** command request indicates that the mobile device can be used to send outbound SMS messages, the server SHOULD propagate the mobile device's outbound SMS state to all clients of the server, allowing any of these clients to send SMS items via the given mobile device.

The **Settings** command response is further specified in [\[MS-ASCMD\]](#) section 2.2.1.16.2.

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

4 Protocol Examples

4.1 Synchronizing E-Mail Items and SMS Items

The following is an example of how the options are specified when the client wants to synchronize e-mail items and SMS items.

Client's **Sync** command request:

```
<?xml version="1.0" encoding="utf-8"?>
<Sync xmlns="AirSync:" xmlns:A="AirSyncBase:" xmlns:B="POOMMAIL:" xmlns:C="POOMTASKS:">
  <Collections>
    <Collection>
      <SyncKey>601771687</SyncKey>
      <CollectionId>15</CollectionId>
      <DeletesAsMoves/>
      <GetChanges/>
      <WindowSize>100</WindowSize>
      <Options>
        <Class>SMS</Class>
        <FilterType>0</FilterType>
        <A:BodyPreference>
          <A:Type>1</A:Type>
          <A:TruncationSize>102400</A:TruncationSize>
        </A:BodyPreference>
      </Options>
      <Options>
        <FilterType>2</FilterType>
        <A:BodyPreference><A:Type>1</A:Type></A:BodyPreference>
        <A:BodyPreference><A:Type>2</A:Type></A:BodyPreference>
        <A:BodyPreference>
          <A:Type>4</A:Type>
          <A:TruncationSize>102400</A:TruncationSize>
        </A:BodyPreference>
        <MIMESupport>0</MIMESupport>
        <Conflict>1</Conflict>
      </Options>
      <Commands>
        ...
      </Commands>
    </Collection>
  </Collections>
</Sync>
```

4.2 Synchronizing Only SMS Items

The following is an example of a how the options are specified when the client wants to synchronize only SMS items.

Client's **Sync** command request:

```
<?xml version="1.0" encoding="utf-8"?>
<Sync xmlns="AirSync:" xmlns:A="AirSyncBase:" xmlns:B="POOMMAIL:" xmlns:C="POOMTASKS:">
  <Collections>
    <Collection>
      <SyncKey>601771687</SyncKey>
```

```

    <CollectionId>15</CollectionId>
    <DeletesAsMoves/>
    <GetChanges/>
    <WindowSize>100</WindowSize>
    <Options>
      <Class>SMS</Class>
      <FilterType>0</FilterType>
      <A:BodyPreference>
        <A:Type>1</A:Type>
        <A:TruncationSize>102400</A:TruncationSize>
      </A:BodyPreference>
    </Options>
    <Commands>
      ...
    </Commands>
  </Collection>
</Collections>
</Sync>

```

4.3 SMS Message Added By the Server

The following is an example of an SMS item being added by the server to the client. Note that the SMS class data is included within the **ApplicationData** node, whereas the class of the item is specified by the **Class** element in the **Add** node.

Server's **Sync** command response:

```

<?xml version="1.0" encoding="utf-8"?>
<Sync xmlns="AirSync:" xmlns:A="AirSyncBase:" xmlns:B="POOMMAIL:" xmlns:C="POOMMAIL2:" >
  <Collections>
    <Collection>
      <SyncKey>525665452</SyncKey>
      <CollectionId>55</CollectionId>
      <Status>1</Status>
      <Commands>
        <Add>
          <Class>SMS</Class>
          <ServerId>55:11</ServerId>
          <ApplicationData>
            <B:To>"14255550143" [MOBILE:14255550143]</B:To>
            <B:From>"14255550123" [MOBILE:+14255550123]</B:From>
            <B:DateReceived>2009-01-08T00:14:36.000Z</B:DateReceived>
            <B:Importance>1</B:Importance>
            <B:Read>0</B:Read>
            <A:Body>
              <A:Type>1</A:Type>
              <A:EstimatedDataSize>29</A:EstimatedDataSize>
              <A:Data>Make sure you get some rest!
            </A:Data>
          </ApplicationData>
        </Add>
      </Commands>
    </Collection>
  </Collections>

```

```
</Collection>
</Collections>
</Sync>
```

4.4 Enabling Outbound SMS Messages

The following example shows how a mobile-device client enables the server to use that mobile-device client for relaying outbound SMS messages.

Mobile-device client's **Settings** command request:

```
<?xml version="1.0" encoding="utf-8"?>
<Settings xmlns="Settings:">
  <DeviceInformation>
    <Set>
      <Model>Manufacturer-Name-Number</Model>
      <IMEI>123456789012345</IMEI>
      <FriendlyName>My PPC Phone</FriendlyName>
      <OS>PPC</OS>
      <Language>us-EN</Language>
      <PhoneNumber>206-555-0112</PhoneNumber>
      <EnableOutboundSMS>1</EnableOutboundSMS>
      <MobileOperator>T-Mojo</MobileOperator>
    </Set>
  </DeviceInformation>
</Settings>
```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following product versions. References to product versions include released service packs.

- Microsoft Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

7 Change Tracking

This section identifies changes made to [MS-ASMS] protocol documentation between July 2009 and November 2009 releases. Changes are classed as major, minor, or editorial.

Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- A protocol is deprecated.
- The removal of a document from the documentation set.
- Changes made for template compliance.

Minor changes do not affect protocol interoperability or implementation. Examples are updates to fix technical accuracy or ambiguity at the sentence, paragraph, or table level.

Editorial changes apply to grammatical, formatting, and style issues.

No changes means that the document is identical to its last release.

Major and minor changes can be described further using the following revision types:

- New content added.
- Content update.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.

- Content removed for template compliance.
- Obsolete document removed.

Editorial changes always have the revision type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

Protocol syntax refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.

Protocol revision refers to changes made to a protocol that affect the bits that are sent over the wire.

Changes are listed in the following table. If you need further information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
1.1 Glossary	51499 Added external glossary term.	N	Content update.
1.4 Relationship to Other Protocols	51477 Added information about the protocol's data types and reference to the related document.	N	New content added.
2.2 Message Syntax	Removed the term tag from "Short Message Service" in each instance where it is used as part of the protocol name.	N	Editorially updated.
2.2.2 Elements	Revised description of the DateReceived element.	N	Content update.
2.2.2.1.1 From	Added reference for more details about the string data type.	N	Content update.
2.2.2.1.1 From	51482 Revised the description of the string's format.	N	Content update.
2.2.2.1.3 To	Added new topic.	Y	New content added.
3.1.4.1 Synchronizing SMS Items	52826 Specified which collections the client is allowed to synchronize.	N	Content update.
3.1.4.1.2 Making Changes Involving SMS Items	Specified restrictions and revised content for clarity.	Y	Content update.
3.1.4.1.3 Special Case for Synchronization of Outbox	51500 Specified frequency for synchronization of outbox.	N	Content update.
3.1.4.2	Added restriction regarding the Options block.	N	Content

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
Estimating the Number of Changes			update.
3.1.5.1 Sending Outbound SMS Messages	Revised process for sending outbound SMS messages.	Y	Content update.
3.1.5.1 Sending Outbound SMS Messages	51498 Provided reference regarding where to find more details about synchronization processing and sequencing.	N	Content update.
3.2.5.1 Processing a Sync Request	Clarified cases in which the server returns a status code 4 (protocol error).	Y	Content update.
3.2.5.1 Processing a Sync Request	51498 Provided reference regarding where to find more details about synchronization processing and sequencing.	N	Content update.
3.2.5.3 Processing a Settings Request	Revised statement to include the normative term "SHOULD".	N	Content update.
4.3 SMS Message Added By the Server	51501 Revised explanation to match example.	N	Content update.
4.4 Enabling Outbound SMS Messages	51501 Revised explanation to clarify what the example is demonstrating.	N	Content update.

8 Index

A

[Applicability](#) 6

C

[Capability negotiation](#) 6

[Change tracking](#) 22

Client

[overview](#) 12

E

Examples

[overview](#) 17

F

[Fields – vendor-extensible](#) 6

G

[Glossary](#) 5

I

[Implementer – security considerations](#) 20

[Index of security parameters](#) 20

[Informative references](#) 6

[Introduction](#) 5

M

Messages

[overview](#) 8

[transport](#) 8

N

[Normative references](#) 5

O

[Overview \(synopsis\)](#) 6

P

[Parameters – security index](#) 20

[Preconditions](#) 6

[Prerequisites](#) 6

[Product behavior](#) 21

R

References

[informative](#) 6

[normative](#) 5

[Relationship to other protocols](#) 6

S

Security

[implementer considerations](#) 20

[overview](#) 20

[parameter index](#) 20

Server

[overview](#) 15

[Standards Assignments](#) 7

T

[Tracking changes](#) 22

[Transport](#) 8

V

[Vendor-extensible fields](#) 6

[Versioning](#) 6