

[MS-ASWBXML]: Exchange ActiveSync: WAP Binary XML (WBXML) Algorithm

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

| Date | Revision History | Revision Class | Comments |
|------------|------------------|----------------|--|
| 12/03/2008 | 1.0.0 | Major | Initial Release. |
| 04/10/2009 | 2.0.0 | Major | Updated technical content and applicable product releases. |
| 07/15/2009 | 3.0.0 | Major | Revised and edited for technical content. |
| 11/04/2009 | 4.0.0 | Major | Updated and revised the technical content. |
| 02/10/2010 | 5.0.0 | Major | Updated and revised the technical content. |
| 05/05/2010 | 6.0.0 | Major | Updated and revised the technical content. |
| 08/04/2010 | 7.0 | Major | Significantly changed the technical content. |
| 11/03/2010 | 8.0 | Major | Significantly changed the technical content. |
| 03/18/2011 | 8.1 | Minor | Clarified the meaning of the technical content. |
| 08/05/2011 | 9.0 | Major | Significantly changed the technical content. |
| 10/07/2011 | 10.0 | Major | Significantly changed the technical content. |
| 01/20/2012 | 11.0 | Major | Significantly changed the technical content. |
| 04/27/2012 | 11.1 | Minor | Clarified the meaning of the technical content. |
| 07/16/2012 | 12.0 | Major | Significantly changed the technical content. |
| 10/08/2012 | 12.1 | Minor | Clarified the meaning of the technical content. |
| 02/11/2013 | 12.1 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 07/26/2013 | 13.0 | Major | Significantly changed the technical content. |
| 11/18/2013 | 13.0 | No change | No changes to the meaning, language, or formatting of the technical content. |
| 02/10/2014 | 13.0 | No change | No changes to the meaning, language, or formatting of the technical content. |

Table of Contents

| | | |
|------------|---|-----------|
| 1 | Introduction | 5 |
| 1.1 | Glossary | 5 |
| 1.2 | References | 5 |
| 1.2.1 | Normative References | 5 |
| 1.2.2 | Informative References | 6 |
| 1.3 | Overview | 6 |
| 1.4 | Relationship to Protocols and Other Algorithms..... | 6 |
| 1.5 | Applicability Statement..... | 7 |
| 1.6 | Standards Assignments | 7 |
| 2 | Algorithm Details | 9 |
| 2.1 | ActiveSync WBXML Algorithm Details | 9 |
| 2.1.1 | Abstract Data Model | 9 |
| 2.1.2 | Initialization | 9 |
| 2.1.2.1 | Code Pages | 9 |
| 2.1.2.1.1 | Code Page 0: AirSync | 10 |
| 2.1.2.1.2 | Code Page 1: Contacts..... | 11 |
| 2.1.2.1.3 | Code Page 2: Email | 13 |
| 2.1.2.1.4 | Code Page 3: AirNotify..... | 15 |
| 2.1.2.1.5 | Code Page 4: Calendar | 15 |
| 2.1.2.1.6 | Code Page 5: Move | 16 |
| 2.1.2.1.7 | Code Page 6: GetItemEstimate | 17 |
| 2.1.2.1.8 | Code Page 7: FolderHierarchy | 17 |
| 2.1.2.1.9 | Code Page 8: MeetingResponse | 18 |
| 2.1.2.1.10 | Code Page 9: Tasks | 18 |
| 2.1.2.1.11 | Code Page 10: ResolveRecipients | 19 |
| 2.1.2.1.12 | Code Page 11: ValidateCert | 20 |
| 2.1.2.1.13 | Code Page 12: Contacts2 | 21 |
| 2.1.2.1.14 | Code Page 13: Ping | 21 |
| 2.1.2.1.15 | Code Page 14: Provision..... | 22 |
| 2.1.2.1.16 | Code Page 15: Search..... | 24 |
| 2.1.2.1.17 | Code Page 16: GAL..... | 25 |
| 2.1.2.1.18 | Code Page 17: AirSyncBase | 25 |
| 2.1.2.1.19 | Code Page 18: Settings..... | 26 |
| 2.1.2.1.20 | Code Page 19: DocumentLibrary | 27 |
| 2.1.2.1.21 | Code Page 20: ItemOperations | 28 |
| 2.1.2.1.22 | Code Page 21: ComposeMail | 29 |
| 2.1.2.1.23 | Code Page 22: Email2 | 29 |
| 2.1.2.1.24 | Code Page 23: Notes | 30 |
| 2.1.2.1.25 | Code Page 24: RightsManagement..... | 30 |
| 2.1.3 | Processing Rules | 31 |
| 3 | Algorithm Examples | 32 |
| 4 | Security..... | 36 |
| 4.1 | Security Considerations for Implementers..... | 36 |
| 4.2 | Index of Security Parameters | 36 |
| 5 | Appendix A: Product Behavior | 37 |
| 6 | Change Tracking..... | 41 |

1 Introduction

The Exchange ActiveSync: WAP Binary XML (WBXML) Algorithm incorporates **Wireless Application Protocol (WAP) Binary XML (WBXML)** functionality into the ActiveSync protocols by mapping ActiveSync **XML schema** elements to numeric code page values. This enables ActiveSync clients to encode **XML** requests into WBXML for transmission to an ActiveSync server.

Section 2 of this specification is normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Section 1.6 is also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Hypertext Transfer Protocol (HTTP)
Secure Sockets Layer (SSL)
XML
XML namespace

The following terms are defined in [\[MS-OXGLOS\]](#):

contact
WBXML code page
Wireless Application Protocol (WAP) Binary XML (WBXML)
XML schema

The following terms are specific to this document:

WBXML token: A single-byte code that represents a specific XML tag.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[MS-ASCMD] Microsoft Corporation, "[Exchange ActiveSync: Command Reference Protocol](#)".

[MS-ASHTTP] Microsoft Corporation, "[Exchange ActiveSync: HTTP Protocol](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[WBXML1.2] Martin, B., and Jano, B., Eds., "WAP Binary XML Content Format", W3C Note, June 1999, <http://www.w3.org/1999/06/NOTE-wbxml-19990624>

1.2.2 Informative References

- [MS-ASAIRS] Microsoft Corporation, "[Exchange ActiveSync: AirSyncBase Namespace Protocol](#)".
- [MS-ASCAL] Microsoft Corporation, "[Exchange ActiveSync: Calendar Class Protocol](#)".
- [MS-ASCNTC] Microsoft Corporation, "[Exchange ActiveSync: Contact Class Protocol](#)".
- [MS-ASEMAIL] Microsoft Corporation, "[Exchange ActiveSync: Email Class Protocol](#)".
- [MS-ASNOTE] Microsoft Corporation, "[Exchange ActiveSync: Notes Class Protocol](#)".
- [MS-ASPROV] Microsoft Corporation, "[Exchange ActiveSync: Provisioning Protocol](#)".
- [MS-ASRM] Microsoft Corporation, "[Exchange ActiveSync: Rights Management Protocol](#)".
- [MS-ASTASK] Microsoft Corporation, "[Exchange ActiveSync: Tasks Class Protocol](#)".
- [MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".
- [MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".
- [MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

1.3 Overview

This algorithm maps ActiveSync XML schema elements to numeric code page values for use by the ActiveSync protocols, enabling ActiveSync clients to encode WBXML requests for transmission to an ActiveSync server.

This algorithm provides **WBXML tokens** and **WBXML code pages** that allow clients and servers to compress the XML tags in request and response messages. WBXML code pages are hard-coded on the server and cannot be changed by the client. The WBXML code pages correspond to **XML namespaces**.

1.4 Relationship to Protocols and Other Algorithms

The XML namespaces that are used by this algorithm are described in the ActiveSync protocol specifications, as shown in the following table.

The WBXML code page numbers in the table are listed in decimal format.

| WBXML code page | Specification |
|------------------------------------|---|
| WBXML code page 0: AirSync | [MS-ASCMD] section 2.2.2.19 |
| WBXML code page 1: Contacts | [MS-ASCNTC] |
| WBXML code page 2: Email | [MS-ASEMAIL] |
| WBXML code page 3: AirNotify | (no longer used) |
| WBXML code page 4: Calendar | [MS-ASCAL] |
| WBXML code page 5: Move | [MS-ASCMD] section 2.2.2.10 |
| WBXML code page 6: GetItemEstimate | [MS-ASCMD] section 2.2.2.7 |

| WBXML code page | Specification |
|---------------------------------------|---|
| WBXML code page 7: FolderHierarchy | [MS-ASCMD] sections 2.2.2.2 , 2.2.2.3 , 2.2.2.4 , and 2.2.2.5 |
| WBXML code page 8: MeetingResponse | [MS-ASCMD] section 2.2.2.9 |
| WBXML code page 9: Tasks | [MS-ASTASK] |
| WBXML code page 10: ResolveRecipients | [MS-ASCMD] section 2.2.2.13 |
| WBXML code page 11: ValidateCert | [MS-ASCMD] section 2.2.2.20 |
| WBXML code page 12: Contacts2 | [MS-ASCNTC] |
| WBXML code page 13: Ping | [MS-ASCMD] section 2.2.2.11 |
| WBXML code page 14: Provision | [MS-ASPROV] |
| WBXML code page 15: Search | [MS-ASCMD] section 2.2.2.14 |
| WBXML code page 16: GAL | [MS-ASCMD] sections 2.2.2.13 and 2.2.2.14 |
| WBXML code page 17: AirSyncBase | [MS-ASAIRS] |
| WBXML code page 18: Settings | [MS-ASCMD] section 2.2.2.16 |
| WBXML code page 19: DocumentLibrary | [MS-ASCMD] sections 2.2.2.8 and 2.2.2.14 |
| WBXML code page 20: ItemOperations | [MS-ASCMD] sections 2.2.2.8 |
| WBXML code page 21: ComposeMail | [MS-ASCMD] sections 2.2.2.15 , 2.2.2.17 , and 2.2.2.18 |
| WBXML code page 22: Email2 | [MS-ASEMAIL] |
| WBXML code page 23: Notes | [MS-ASNOTE] |
| WBXML code page 24: Rights Management | [MS-ASRM] |

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

1.5 Applicability Statement

WBXML is used as a compact transmission format for mobile clients, which typically have little memory and bandwidth. WBXML encoding of XML tags is appropriate for all messages sent and received by using the ActiveSync protocols.

1.6 Standards Assignments

This algorithm uses the global WBXML tokens listed in the following table.

| Token name | Token | Reference |
|-------------|-------|----------------------------|
| SWITCH_PAGE | 0 | [WBXML1.2] |
| END | 1 | [WBXML1.2] |
| ENTITY | 2 | [WBXML1.2] |

| Token name | Token | Reference |
|-------------------|--------------|----------------------------|
| STR_I | 3 | [WBXML1.2] |
| LITERAL | 4 | [WBXML1.2] |
| EXT_I_0 | 40 | [WBXML1.2] |
| EXT_I_1 | 41 | [WBXML1.2] |
| EXT_I_2 | 42 | [WBXML1.2] |
| PI | 43 | [WBXML1.2] |
| LITERAL_C | 44 | [WBXML1.2] |
| EXT_T_0 | 80 | [WBXML1.2] |
| EXT_T_1 | 81 | [WBXML1.2] |
| EXT_T_2 | 82 | [WBXML1.2] |
| STR_T | 83 | [WBXML1.2] |
| LITERAL_A | 84 | [WBXML1.2] |
| EXT_0 | C0 | [WBXML1.2] |
| EXT_1 | C1 | [WBXML1.2] |
| EXT_2 | C2 | [WBXML1.2] |
| OPAQUE | C3 | [WBXML1.2] |
| LITERAL_AC | C4 | [WBXML1.2] |

2 Algorithm Details

2.1 ActiveSync WBXML Algorithm Details

ActiveSync messages are transported as HTTP **POST** messages, as specified in [\[MS-ASHTTP\]](#), where the body of the message contains WBXML formatted data. The WBXML data encodes the XML required by the command being communicated in the message. The ActiveSync commands are specified in [\[MS-ASCMD\]](#).

This section specifies the algorithm to encode XML request and response messages into WBXML format and to decode WBXML data into XML request and response messages. This algorithm is used by clients and servers.

2.1.1 Abstract Data Model

None.

2.1.2 Initialization

The XML tags in both request and response messages are encoded by using WBXML tokenization, as specified in [\[WBXML1.2\]](#). WBXML uses WBXML code pages to map XML tags to WBXML tokens. WBXML parsers MUST use the WBXML code pages specified in the following sections.

2.1.2.1 Code Pages

This algorithm supports the following WBXML code pages.

| Code page | XML namespace |
|-----------|-------------------|
| 0 | AirSync |
| 1 | Contacts |
| 2 | Email |
| 3 | AirNotify |
| 4 | Calendar |
| 5 | Move |
| 6 | GetItemEstimate |
| 7 | FolderHierarchy |
| 8 | MeetingResponse |
| 9 | Tasks |
| 10 | ResolveRecipients |
| 11 | ValidateCert |
| 12 | Contacts2 |
| 13 | Ping |

| Code page | XML namespace |
|------------------|----------------------|
| 14 | Provision |
| 15 | Search |
| 16 | Gal |
| 17 | AirSyncBase |
| 18 | Settings |
| 19 | DocumentLibrary |
| 20 | ItemOperations |
| 21 | ComposeMail |
| 22 | Email2 |
| 23 | Notes |
| 24 | RightsManagement |

2.1.2.1.1 Code Page 0: AirSync

The tags and tokens in WBXML code page 0 are listed in the following table.

| Tag name | Token |
|----------------------|--------------|
| Sync | 0x05 |
| Responses | 0x06 |
| Add | 0x07 |
| Change | 0x08 |
| Delete | 0x09 |
| Fetch | 0x0A |
| SyncKey | 0x0B |
| ClientId | 0x0C |
| ServerId | 0x0D |
| Status | 0x0E |
| Collection | 0x0F |
| Class | 0x10 |
| CollectionId | 0x12 |
| GetChanges | 0x13 |
| MoreAvailable | 0x14 |

| Tag name | Token |
|-----------------------------------|-------|
| WindowSize | 0x15 |
| Commands | 0x16 |
| Options | 0x17 |
| FilterType | 0x18 |
| Conflict | 0x1B |
| Collections | 0x1C |
| ApplicationData | 0x1D |
| DeletesAsMoves | 0x1E |
| Supported | 0x20 |
| SoftDelete | 0x21 |
| MIMESupport | 0x22 |
| MIMETruncation | 0x23 |
| Wait | 0x24 |
| Limit | 0x25 |
| Partial | 0x26 |
| ConversationMode<1> | 0x27 |
| MaxItems<2> | 0x28 |
| HeartbeatInterval<3> | 0x29 |

2.1.2.1.2 Code Page 1: Contacts

The tags and tokens in WBXML code page 1 are listed in the following table.

| Tag name | Token |
|----------------------------------|-------|
| Anniversary | 0x05 |
| AssistantName | 0x06 |
| AssistantPhoneNumber | 0x07 |
| Birthday | 0x08 |
| Business2PhoneNumber | 0x0C |
| BusinessAddressCity | 0x0D |
| BusinessAddressCountry | 0x0E |
| BusinessAddressPostalCode | 0x0F |

| Tag name | Token |
|------------------------------|--------------|
| BusinessAddressState | 0x10 |
| BusinessAddressStreet | 0x11 |
| BusinessFaxNumber | 0x12 |
| BusinessPhoneNumber | 0x13 |
| CarPhoneNumber | 0x14 |
| Categories | 0x15 |
| Category | 0x16 |
| Children | 0x17 |
| Child | 0x18 |
| CompanyName | 0x19 |
| Department | 0x1A |
| Email1Address | 0x1B |
| Email2Address | 0x1C |
| Email3Address | 0x1D |
| FileAs | 0x1E |
| FirstName | 0x1F |
| Home2PhoneNumber | 0x20 |
| HomeAddressCity | 0x21 |
| HomeAddressCountry | 0x22 |
| HomeAddressPostalCode | 0x23 |
| HomeAddressState | 0x24 |
| HomeAddressStreet | 0x25 |
| HomeFaxNumber | 0x26 |
| HomePhoneNumber | 0x27 |
| JobTitle | 0x28 |
| LastName | 0x29 |
| MiddleName | 0x2A |
| MobilePhoneNumber | 0x2B |
| OfficeLocation | 0x2C |
| OtherAddressCity | 0x2D |

| Tag name | Token |
|---|-------|
| OtherAddressCountry | 0x2E |
| OtherAddressPostalCode | 0x2F |
| OtherAddressState | 0x30 |
| OtherAddressStreet | 0x31 |
| PagerNumber | 0x32 |
| RadioPhoneNumber | 0x33 |
| Spouse | 0x34 |
| Suffix | 0x35 |
| Title | 0x36 |
| WebPage | 0x37 |
| YomiCompanyName | 0x38 |
| YomiFirstName | 0x39 |
| YomiLastName | 0x3A |
| Picture | 0x3C |
| Alias^{<4>} | 0x3D |
| WeightedRank^{<5>} | 0x3E |

2.1.2.1.3 Code Page 2: Email

The tags and tokens in WBXML code page 2 are listed in the following table.

| Tag name | Token |
|---------------------|-------|
| DateReceived | 0x0F |
| DisplayTo | 0x11 |
| Importance | 0x12 |
| MessageClass | 0x13 |
| Subject | 0x14 |
| Read | 0x15 |
| To | 0x16 |
| Cc | 0x17 |
| From | 0x18 |
| ReplyTo | 0x19 |

| Tag name | Token |
|----------------------------|-------|
| AllDayEvent | 0x1A |
| Categories<6> | 0x1B |
| Category<7> | 0x1C |
| DtStamp | 0x1D |
| EndTime | 0x1E |
| InstanceType | 0x1F |
| BusyStatus | 0x20 |
| Location | 0x21 |
| MeetingRequest | 0x22 |
| Organizer | 0x23 |
| RecurrenceId | 0x24 |
| Reminder | 0x25 |
| ResponseRequested | 0x26 |
| Recurrences | 0x27 |
| Recurrence | 0x28 |
| Type | 0x29 |
| Until | 0x2A |
| Occurrences | 0x2B |
| Interval | 0x2C |
| DayOfWeek | 0x2D |
| DayOfMonth | 0x2E |
| WeekOfMonth | 0x2F |
| MonthOfYear | 0x30 |
| StartTime | 0x31 |
| Sensitivity | 0x32 |
| TimeZone | 0x33 |
| GlobalObjId | 0x34 |
| ThreadTopic | 0x35 |
| InternetCPID | 0x39 |
| Flag | 0x3A |

| Tag name | Token |
|---|--------------|
| Status | 0x3B |
| ContentClass | 0x3C |
| FlagType | 0x3D |
| CompleteTime | 0x3E |
| DisallowNewTimeProposal<8> | 0x3F |

2.1.2.1.4 Code Page 3: AirNotify

WBXML code page 3 is no longer in use.

2.1.2.1.5 Code Page 4: Calendar

The tags and tokens in WBXML code page 4 are listed in the following table.

| Tag name | Token |
|---------------------------|--------------|
| Timezone | 0x05 |
| AllDayEvent | 0x06 |
| Attendees | 0x07 |
| Attendee | 0x08 |
| Email | 0x09 |
| Name | 0x0A |
| BusyStatus | 0x0D |
| Categories | 0x0E |
| Category | 0x0F |
| DtStamp | 0x11 |
| EndTime | 0x12 |
| Exception | 0x13 |
| Exceptions | 0x14 |
| Deleted | 0x15 |
| ExceptionStartTime | 0x16 |
| Location | 0x17 |
| MeetingStatus | 0x18 |
| OrganizerEmail | 0x19 |
| OrganizerName | 0x1A |

| Tag name | Token |
|---|-------|
| Recurrence | 0x1B |
| Type | 0x1C |
| Until | 0x1D |
| Occurrences | 0x1E |
| Interval | 0x1F |
| DayOfWeek | 0x20 |
| DayOfMonth | 0x21 |
| WeekOfMonth | 0x22 |
| MonthOfYear | 0x23 |
| Reminder | 0x24 |
| Sensitivity | 0x25 |
| Subject | 0x26 |
| StartTime | 0x27 |
| UID | 0x28 |
| AttendeeStatus | 0x29 |
| AttendeeType | 0x2A |
| DisallowNewTimeProposal_{<9>} | 0x33 |
| ResponseRequested_{<10>} | 0x34 |
| AppointmentReplyTime_{<11>} | 0x35 |
| ResponseType_{<12>} | 0x36 |
| CalendarType_{<13>} | 0x37 |
| IsLeapMonth_{<14>} | 0x38 |
| FirstDayOfWeek_{<15>} | 0x39 |
| OnlineMeetingConfLink_{<16>} | 0x3A |
| OnlineMeetingExternalLink_{<17>} | 0x3B |

2.1.2.1.6 Code Page 5: Move

The tags and tokens in WBXML code page 5 are listed in the following table.

| Tag name | Token |
|------------------|-------|
| MoveItems | 0x05 |

| Tag name | Token |
|-----------------|-------|
| Move | 0x06 |
| SrcMsgId | 0x07 |
| SrcFldId | 0x08 |
| DstFldId | 0x09 |
| Response | 0x0A |
| Status | 0x0B |
| DstMsgId | 0x0C |

2.1.2.1.7 Code Page 6: GetItemEstimate

The tags and tokens in WBXML code page 6 are listed in the following table.

| Tag name | Token |
|---|-------|
| GetItemEstimate | 0x05 |
| Version <u><18></u> | 0x06 |
| Collections | 0x07 |
| Collection | 0x08 |
| Class <u><19></u> | 0x09 |
| CollectionId | 0x0A |
| DateTime <u><20></u> | 0x0B |
| Estimate | 0x0C |
| Response | 0x0D |
| Status | 0x0E |

2.1.2.1.8 Code Page 7: FolderHierarchy

The tags and tokens in WBXML code page 7 are listed in the following table.

| Tag name | Token |
|--------------------|-------|
| DisplayName | 0x07 |
| ServerId | 0x08 |
| ParentId | 0x09 |
| Type | 0x0A |
| Status | 0x0C |

| Tag name | Token |
|---------------------|-------|
| Changes | 0x0E |
| Add | 0x0F |
| Delete | 0x10 |
| Update | 0x11 |
| SyncKey | 0x12 |
| FolderCreate | 0x13 |
| FolderDelete | 0x14 |
| FolderUpdate | 0x15 |
| FolderSync | 0x16 |
| Count | 0x17 |

2.1.2.1.9 Code Page 8: MeetingResponse

The tags and tokens in WBXML code page 8 are listed in the following table.

| Tag name | Token |
|------------------------|-------|
| CalendarId | 0x05 |
| CollectionId | 0x06 |
| MeetingResponse | 0x07 |
| RequestId | 0x08 |
| Request | 0x09 |
| Result | 0x0A |
| Status | 0x0B |
| UserResponse | 0x0C |
| InstanceId | 0x0E |

2.1.2.1.10 Code Page 9: Tasks

The tags and tokens in WBXML code page 9 are listed in the following table.

| Tag name | Token |
|-------------------|-------|
| Categories | 0x08 |
| Category | 0x09 |
| Complete | 0x0A |

| Tag name | Token |
|---------------------------------|-------|
| DateCompleted | 0x0B |
| DueDate | 0x0C |
| UtcDueDate | 0x0D |
| Importance | 0x0E |
| Recurrence | 0x0F |
| Type | 0x10 |
| Start | 0x11 |
| Until | 0x12 |
| Occurrences | 0x13 |
| Interval | 0x14 |
| DayOfMonth | 0x15 |
| DayOfWeek | 0x16 |
| WeekOfMonth | 0x17 |
| MonthOfYear | 0x18 |
| Regenerate | 0x19 |
| DeadOccur | 0x1A |
| ReminderSet | 0x1B |
| ReminderTime | 0x1C |
| Sensitivity | 0x1D |
| StartDate | 0x1E |
| UtcStartDate | 0x1F |
| Subject | 0x20 |
| OrdinalDate | 0x22 |
| SubOrdinalDate | 0x23 |
| CalendarType<21> | 0x24 |
| IsLeapMonth<22> | 0x25 |
| FirstDayOfWeek<23> | 0x26 |

2.1.2.1.11 Code Page 10: ResolveRecipients

The tags and tokens in WBXML code page 10 are listed in the following table.

| Tag name | Token |
|--|-------|
| ResolveRecipients | 0x05 |
| Response | 0x06 |
| Status | 0x07 |
| Type | 0x08 |
| Recipient | 0x09 |
| DisplayName | 0x0A |
| EmailAddress | 0x0B |
| Certificates | 0x0C |
| Certificate | 0x0D |
| MiniCertificate | 0x0E |
| Options | 0x0F |
| To | 0x10 |
| CertificateRetrieval | 0x11 |
| RecipientCount | 0x12 |
| MaxCertificates | 0x13 |
| MaxAmbiguousRecipients | 0x14 |
| CertificateCount | 0x15 |
| Availability <24> | 0x16 |
| StartTime <25> | 0x17 |
| EndTime <26> | 0x18 |
| MergedFreeBusy <27> | 0x19 |
| Picture <28> | 0x1A |
| MaxSize <29> | 0x1B |
| Data <30> | 0x1C |
| MaxPictures <31> | 0x1D |

2.1.2.1.12 Code Page 11: ValidateCert

The tags and tokens in WBXML code page 11 are listed in the following table.

| Tag name | Token |
|---------------------|-------|
| ValidateCert | 0x05 |

| Tag name | Token |
|-------------------------|-------|
| Certificates | 0x06 |
| Certificate | 0x07 |
| CertificateChain | 0x08 |
| CheckCRL | 0x09 |
| Status | 0x0A |

2.1.2.1.13 Code Page 12: Contacts2

The tags and tokens in WBXML code page 12 are listed in the following table.

| Tag name | Token |
|-------------------------|-------|
| CustomerId | 0x05 |
| GovernmentId | 0x06 |
| IMAddress | 0x07 |
| IMAddress2 | 0x08 |
| IMAddress3 | 0x09 |
| ManagerName | 0x0A |
| CompanyMainPhone | 0x0B |
| AccountName | 0x0C |
| NickName | 0x0D |
| MMS | 0x0E |

2.1.2.1.14 Code Page 13: Ping

The tags and tokens in WBXML code page 13 are listed in the following table.

| Tag name | Token |
|-----------------------------|-------|
| Ping | 0x05 |
| AutdState (Not used) | 0x06 |
| Status | 0x07 |
| HeartbeatInterval | 0x08 |
| Folders | 0x09 |
| Folder | 0x0A |
| Id | 0x0B |

| Tag name | Token |
|-------------------|-------|
| Class | 0x0C |
| MaxFolders | 0x0D |

2.1.2.1.15 Code Page 14: Provision

The tags and tokens in WBXML code page 14 are listed in the following table.

| Tag name | Token |
|---|-------|
| Provision | 0x05 |
| Policies | 0x06 |
| Policy | 0x07 |
| PolicyType | 0x08 |
| PolicyKey | 0x09 |
| Data | 0x0A |
| Status | 0x0B |
| RemoteWipe | 0x0C |
| EASProvisionDoc | 0x0D |
| DevicePasswordEnabled | 0x0E |
| AlphanumericDevicePasswordRequired | 0x0F |
| DeviceEncryptionEnabled | 0x10 |
| RequireStorageCardEncryption (equivalent to DeviceEncryptionEnabled) | 0x10 |
| PasswordRecoveryEnabled | 0x11 |
| AttachmentsEnabled | 0x13 |
| MinDevicePasswordLength | 0x14 |
| MaxInactivityTimeDeviceLock | 0x15 |
| MaxDevicePasswordFailedAttempts | 0x16 |
| MaxAttachmentSize | 0x17 |
| AllowSimpleDevicePassword | 0x18 |
| DevicePasswordExpiration | 0x19 |
| DevicePasswordHistory | 0x1A |
| AllowStorageCard | 0x1B |
| AllowCamera | 0x1C |

| Tag name | Token |
|---|--------------|
| RequireDeviceEncryption | 0x1D |
| AllowUnsignedApplications | 0x1E |
| AllowUnsignedInstallationPackages | 0x1F |
| MinDevicePasswordComplexCharacters | 0x20 |
| AllowWiFi | 0x21 |
| AllowTextMessaging | 0x22 |
| AllowPOPIMAPEmail | 0x23 |
| AllowBluetooth | 0x24 |
| AllowIrDA | 0x25 |
| RequireManualSyncWhenRoaming | 0x26 |
| AllowDesktopSync | 0x27 |
| MaxCalendarAgeFilter | 0x28 |
| AllowHTMLEmail | 0x29 |
| MaxEmailAgeFilter | 0x2A |
| MaxEmailBodyTruncationSize | 0x2B |
| MaxEmailHTMLBodyTruncationSize | 0x2C |
| RequireSignedSMIMEMessages | 0x2D |
| RequireEncryptedSMIMEMessages | 0x2E |
| RequireSignedSMIMEAlgorithm | 0x2F |
| RequireEncryptionSMIMEAlgorithm | 0x30 |
| AllowSMIMEEncryptionAlgorithmNegotiation | 0x31 |
| AllowSMIMESoftCerts | 0x32 |
| AllowBrowser | 0x33 |
| AllowConsumerEmail | 0x34 |
| AllowRemoteDesktop | 0x35 |
| AllowInternetSharing | 0x36 |
| UnapprovedInROMApplicationList | 0x37 |
| ApplicationName | 0x38 |
| ApprovedApplicationList | 0x39 |
| Hash | 0x3A |

2.1.2.1.16 Code Page 15: Search

The tags and tokens in WBXML code page 15 are listed in the following table.

| Tag name | Token |
|-----------------|-------|
| Search | 0x05 |
| Store | 0x07 |
| Name | 0x08 |
| Query | 0x09 |
| Options | 0xA |
| Range | 0xB |
| Status | 0xC |
| Response | 0xD |
| Result | 0xE |
| Properties | 0xF |
| Total | 0x10 |
| EqualTo | 0x11 |
| Value | 0x12 |
| And | 0x13 |
| Or<32> | 0x14 |
| FreeText | 0x15 |
| DeepTraversal | 0x17 |
| LongId | 0x18 |
| RebuildResults | 0x19 |
| LessThan | 0x1A |
| GreaterThan | 0x1B |
| UserName | 0x1E |
| Password | 0x1F |
| ConversationId | 0x20 |
| Picture<33> | 0x21 |
| MaxSize<34> | 0x22 |
| MaxPictures<35> | 0x23 |

Note that WBXML tokens 0x06 and 0x16 are not used.

2.1.2.1.17 Code Page 16: GAL

The tags and tokens in WBXML code page 16 are listed in the following table.

| Tag name | Token |
|-----------------------------------|-------|
| DisplayName | 0x05 |
| Phone | 0x06 |
| Office | 0x07 |
| Title | 0x08 |
| Company | 0x09 |
| Alias | 0x0A |
| FirstName | 0x0B |
| LastName | 0x0C |
| HomePhone | 0x0D |
| MobilePhone | 0x0E |
| EmailAddress | 0x0F |
| Picture 36 | 0x10 |
| Status 37 | 0x11 |
| Data 38 | 0x12 |

2.1.2.1.18 Code Page 17: AirSyncBase

The tags and tokens in WBXML code page 17 are listed in the following table.

| Tag name | Token |
|-----------------------------|-------|
| BodyPreference | 0x05 |
| Type | 0x06 |
| TruncationSize | 0x07 |
| AllOrNone | 0x08 |
| Body | 0x0A |
| Data | 0x0B |
| EstimatedContentSize | 0x0C |
| Truncated | 0x0D |
| Attachments | 0x0E |
| Attachment | 0x0F |

| Tag name | Token |
|-------------------------------------|-----------------|
| DisplayName | 0x10 |
| FileReference | 0x11 |
| Method | 0x12 |
| ContentId | 0x13 |
| ContentLocation | 0x14 (not used) |
| IsInline | 0x15 |
| NativeBodyType | 0x16 |
| ContentType | 0x17 |
| Preview<39> | 0x18 |
| BodyPartPreference<40> | 0x19 |
| BodyPart<41> | 0x1A |
| Status<42> | 0x1B |

2.1.2.1.19 Code Page 18: Settings

The tags and tokens in WBXML code page 18 are listed in the following table.

| Tag name | Token |
|---------------------------------|-------|
| Settings | 0x05 |
| Status | 0x06 |
| Get | 0x07 |
| Set | 0x08 |
| Oof | 0x09 |
| OofState | 0x0A |
| StartTime | 0x0B |
| EndTime | 0x0C |
| OofMessage | 0x0D |
| AppliesToInternal | 0x0E |
| AppliesToExternalKnown | 0x0F |
| AppliesToExternalUnknown | 0x10 |
| Enabled | 0x11 |
| ReplyMessage | 0x12 |

| Tag name | Token |
|--|-------|
| BodyType | 0x13 |
| DevicePassword | 0x14 |
| Password | 0x15 |
| DeviceInformation | 0x16 |
| Model | 0x17 |
| IMEI | 0x18 |
| FriendlyName | 0x19 |
| OS | 0x1A |
| OSLanguage | 0x1B |
| PhoneNumber | 0x1C |
| UserInformation | 0x1D |
| EmailAddresses | 0x1E |
| SMTPAddress | 0x1F |
| UserAgent | 0x20 |
| EnableOutboundSMS<43> | 0x21 |
| MobileOperator<44> | 0x22 |
| PrimarySmtpAddress<45> | 0x23 |
| Accounts<46> | 0x24 |
| Account<47> | 0x25 |
| AccountId<48> | 0x26 |
| AccountName<49> | 0x27 |
| UserDisplayName<50> | 0x28 |
| SendDisabled<51> | 0x29 |
| RightsManagementInformation<52> | 0x2B |

2.1.2.1.20 Code Page 19: DocumentLibrary

The tags and tokens in WBXML code page 19 are listed in the following table.

| Tag name | Token |
|--------------------|-------|
| LinkId | 0x05 |
| DisplayName | 0x06 |

| Tag name | Token |
|-------------------------|-------|
| IsFolder | 0x07 |
| CreationDate | 0x08 |
| LastModifiedDate | 0x09 |
| IsHidden | 0x0A |
| ContentLength | 0x0B |
| ContentType | 0x0C |

2.1.2.1.21 Code Page 20: ItemOperations

The tags and tokens in WBXML code page 20 are listed in the following table.

| Tag name | Token |
|--|-------|
| ItemOperations | 0x05 |
| Fetch | 0x06 |
| Store | 0x07 |
| Options | 0x08 |
| Range | 0x09 |
| Total | 0x0A |
| Properties | 0x0B |
| Data | 0x0C |
| Status | 0x0D |
| Response | 0x0E |
| Version | 0x0F |
| Schema | 0x10 |
| Part | 0x11 |
| EmptyFolderContents | 0x12 |
| DeleteSubFolders | 0x13 |
| UserName | 0x14 |
| Password | 0x15 |
| Move <53> | 0x16 |
| DstFldId <54> | 0x17 |
| ConversationId <55> | 0x18 |

| Tag name | Token |
|-------------------------------|-------|
| MoveAlways 56 | 0x19 |

2.1.2.1.22 Code Page 21: ComposeMail

The tags and tokens in WBXML code page 21[57](#) are listed in the following table.

| Tag name | Token |
|------------------------------|-------|
| SendMail | 0x05 |
| SmartForward | 0x06 |
| SmartReply | 0x07 |
| SaveInSentItems | 0x08 |
| ReplaceMime | 0x09 |
| Source | 0x0B |
| FolderId | 0x0C |
| ItemId | 0x0D |
| LongId | 0x0E |
| InstanceId | 0x0F |
| Mime | 0x10 |
| ClientId | 0x11 |
| Status | 0x12 |
| AccountId 58 | 0x13 |

2.1.2.1.23 Code Page 22: Email2

The tags and tokens in WBXML code page 22[59](#) are listed in the following table.

| Tag name | Token |
|-------------------|-------|
| UmCallerID | 0x05 |
| UmUserNotes | 0x06 |
| UmAttDuration | 0x07 |
| UmAttOrder | 0x08 |
| ConversationId | 0x09 |
| ConversationIndex | 0x0A |
| LastVerbExecuted | 0x0B |

| Tag name | Token |
|---|-------|
| LastVerbExecutionTime | 0x0C |
| ReceivedAsBcc | 0x0D |
| Sender | 0x0E |
| CalendarType | 0x0F |
| IsLeapMonth | 0x10 |
| AccountId <60> | 0x11 |
| FirstDayOfWeek <61> | 0x12 |
| MeetingMessageType <62> | 0x13 |

2.1.2.1.24 Code Page 23: Notes

The tags and tokens in WBXML code page 23[<63>](#) are listed in the following table.

| Tag name | Token |
|------------------|-------|
| Subject | 0x05 |
| MessageClass | 0x06 |
| LastModifiedDate | 0x07 |
| Categories | 0x08 |
| Category | 0x09 |

2.1.2.1.25 Code Page 24: RightsManagement

The tags and tokens in WBXML code page 24[<64>](#) are listed in the following table.

| Tag name | Token |
|---------------------------|-------|
| RightsManagementSupport | 0x05 |
| RightsManagementTemplates | 0x06 |
| RightsManagementTemplate | 0x07 |
| RightsManagementLicense | 0x08 |
| EditAllowed | 0x09 |
| ReplyAllowed | 0x0A |
| ReplyAllAllowed | 0x0B |
| ForwardAllowed | 0x0C |
| ModifyRecipientsAllowed | 0x0D |

| Tag name | Token |
|---|-------|
| ExtractAllowed | 0x0E |
| PrintAllowed | 0x0F |
| ExportAllowed | 0x10 |
| ProgrammaticAccessAllowed | 0x11 |
| Owner | 0x12 |
| ContentExpiryDate | 0x13 |
| TemplateID | 0x14 |
| TemplateName | 0x15 |
| TemplateDescription | 0x16 |
| ContentOwner | 0x17 |
| RemoveRightsManagementDistribution | 0x18 |

2.1.3 Processing Rules

The processing rules for this algorithm are specified in [\[WBXML1.2\]](#).

This algorithm uses the following features that are specified in [\[WBXML1.2\]](#):

- WBXML tokens to encode XML tags
- WBXML code pages to support multiple XML namespaces
- Inline strings
- Opaque data

This algorithm does not use the following features that are specified in [\[WBXML1.2\]](#):

- String tables
- Entities
- Processing instructions
- Attribute encoding

3 Algorithm Examples

The following example shows the WBXML encoding of a server response that contains a new **contact (3)** and provides a byte-by-byte description of the encoding.

The following XML represents a server response to a request to create a new contact.

```
<?xml version="1.0" encoding="utf-8"?>
<Sync xmlns="AirSync" xmlns:airsyncbase="AirSyncBase" xmlns:contacts="Contacts">
  <Collections>
    <Collection>
      <Class>Contacts</Class>
      <SyncKey>2</SyncKey>
      <CollectionId>2</CollectionId>
      <Status>1</Status>
      <Commands>
        <Add>
          <ServerId>2:1</ServerId>
          <ApplicationData>
            <airsyncbase:Body>
              <airsyncbase:Type>1</airsyncbase:Type>
              <airsyncbase:EstimatedContentSize>0</airsyncbase:EstimatedContentSize>
              <airsyncbase:Truncated>1</airsyncbase:Truncated>
            </airsyncbase:Body>
            <contacts:FileAs>Funk, Don</contacts:FileAs>
            <contacts:FirstName>Don</contacts:FirstName>
            <contacts:LastName>Funk</contacts:LastName>
            <airsyncbase:NativeBodyType>1</airsyncbase:NativeBodyType>
          </ApplicationData>
        </Add>
      </Commands>
    </Collection>
  </Collections>
</Sync>
```

The Exchange ActiveSync: WAP Binary XML (WBXML) Algorithm encodes this XML as the following WBXML encoding.

```
03 01 6A 00 45 5C 4F 50 03 43 6F 6E 74 61 63 74 73 00 01 4B 03 32 00 01 52 03 32 00 01 4E 03
31 00 01 56 47 4D 03 32 3A 31 00 01 5D 00 11 4A 46 03 31 00 01 4C 03 30 00 01 4D 03 31 00 01
01 00 01 5E 03 46 75 6E 6B 2C 20 44 6F 6E 00 01 5F 03 44 6F 6E 00 01 69 03 46 75 6E 6B 00 01
00 11 56 03 31 00 01 01 01 01 01 01 01
```

The following table explains each byte in the WBXML encoding.

| Bytes | Description |
|-------|--|
| 03 | Version number – WBXML version 1.3 |
| 01 | Unknown public identifier |
| 6A | Charset = UTF-8 |
| 00 | String table length |
| 45 | <airsync:Sync>, with content (0x05 + 0x40) |

| Bytes | Description |
|----------------------------|--|
| 5C | <airsync:Collections>, with content |
| 4F | <airsync:Collection>, with content |
| 50 | <airsync:Class>, with content |
| 03 | Inline string follows |
| 43 6F 6E 74 61 63 74 73 00 | "contacts" (the 00 is the end of the string) |
| 01 | </airsync:Class> |
| 4B | <airsync:SyncKey>, with content |
| 03 | Inline string follows |
| 32 00 | "2" |
| 01 | </airsync:SyncKey> |
| 52 | <airsync:CollectionID>, with content |
| 03 | Inline string follows |
| 32 00 | "2" |
| 01 | </airsync:CollectionID> |
| 4E | <airsync>Status>, with content |
| 03 | Inline string follows |
| 31 00 | "1" |
| 01 | </airsync>Status> |
| 56 | <airsync:Commands>, with content |
| 47 | <airsync:Add>, with content |
| 4D | <airsync:ServerId>, with content |
| 03 | Inline string follows |
| 32 3A 31 00 | "2:1" |
| 01 | </airsync:ServerId> |
| 5D | <airsync:ApplicationData>, with content |
| 00 11 | Select WBXML code page 17 (AirSyncBase) |
| 4A | <airsyncbase:Body>, with content |
| 46 | <airsyncbase>Type>, with content |
| 03 | Inline string follows |
| 31 00 | "1" |

| Bytes | Description |
|-------------------------------|--|
| 01 | </airsyncbase:Type> |
| 4C | <airsyncbase:EstimatedContentSize>, with content |
| 03 | Inline string follows |
| 30 00 | "0" |
| 01 | </airsyncbase:EstimatedContentSize> |
| 4D | <airsyncbase:Truncated>, with content |
| 03 | Inline string follows |
| 31 00 | "1" |
| 01 | </airsyncbase:Truncated> |
| 01 | </airsyncbase:Body> |
| 00 01 | Select WBXML code page 1 (Contacts) |
| 5E | <contacts:FileAs>, with content |
| 03 | Inline string follows |
| 46 75 6E 6B 2C 20 44 6F 6E 00 | "Funk, Don" |
| 01 | </contacts:FileAs> |
| 5F | <contacts:FirstName>, with content |
| 03 | Inline string follows |
| 44 6F 6E 00 | "Don" |
| 01 | </contacts:FirstName> |
| 69 | <contacts:LastName>, with content |
| 03 | Inline string follows |
| 46 75 6E 6B 00 | "Funk" |
| 01 | </contacts:LastName> |
| 00 11 | Select WBXML code page 17 (AirSyncBase) |
| 56 | <airsyncbase:NativeBodyType>, with content |
| 03 | Inline string follows |
| 31 00 | "1" |
| 01 | </airsyncbase:NativeBodyType> |
| 01 | </airsync:ApplicationData> |
| 01 | </airsync:Add> |

| Bytes | Description |
|--------------|------------------------|
| 01 | </airsync:Commands> |
| 01 | </airsync:Collection> |
| 01 | </airsync:Collections> |
| 01 | </airsync:Sync> |

4 Security

4.1 Security Considerations for Implementers

In most cases, all communication between the client and server happens across an **HTTP** connection secured by the **Secure Sockets Layer (SSL)** protocol. The SSL connection is assumed to be secure enough to transmit confidential data, such as user credentials and sensitive e-mail. The SSL certificate on the server is assumed to be trusted by the client application.

4.2 Index of Security Parameters

None.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2007 Service Pack 1 (SP1)
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Windows 8.1
- Windows Communication Apps

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.2.1.1:](#) The **ConversationMode** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<2> Section 2.1.2.1.1:](#) The **MaxItems** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<3> Section 2.1.2.1.1:](#) The **HeartbeatInterval** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<4> Section 2.1.2.1.2:](#) The **Alias** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<5> Section 2.1.2.1.2:](#) The **WeightedRank** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<6> Section 2.1.2.1.3:](#) The **Categories** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<7> Section 2.1.2.1.3:](#) The **Category** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<8> Section 2.1.2.1.3:](#) The **DisallowNewTimeProposal** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<9> Section 2.1.2.1.5:](#) The **DisallowNewTimeProposal** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<10> Section 2.1.2.1.5:](#) The **ResponseRequested** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<11> Section 2.1.2.1.5:](#) The **AppointmentReplyTime** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<12> Section 2.1.2.1.5:](#) The **ResponseType** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<13> Section 2.1.2.1.5:](#) The **CalendarType** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<14> Section 2.1.2.1.5:](#) The **IsLeapMonth** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<15> Section 2.1.2.1.5:](#) The **FirstDayOfWeek** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<16> Section 2.1.2.1.5:](#) The **OnlineMeetingConfLink** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<17> Section 2.1.2.1.5:](#) The **OnlineMeetingExternalLink** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<18> Section 2.1.2.1.7:](#) The **Version** tag is supported only when the MS-ASProtocolVersion header is set to 12.1.

[<19> Section 2.1.2.1.7:](#) The **Class** tag is supported only when the MS-ASProtocolVersion header is set to 12.1. When the MS-ASProtocolVersion header is set to 14.0 or 14.1, the **Class** tag defined in WBXML code page 0 is used.

[<20> Section 2.1.2.1.7:](#) The **DateTime** tag is supported only when the MS-ASProtocolVersion header is set to 12.1.

[<21> Section 2.1.2.1.10:](#) The **CalendarType** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<22> Section 2.1.2.1.10:](#) The **IsLeapMonth** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<23> Section 2.1.2.1.10:](#) The **FirstDayOfWeek** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<24> Section 2.1.2.1.11:](#) The **Availability** tag is not supported if the MS-ASProtocolVersion header is set to 12.1.

[<25> Section 2.1.2.1.11:](#) The **StartTime** tag is not supported if the MS-ASProtocolVersion header is set to 12.1.

[<26> Section 2.1.2.1.11:](#) The **EndTime** tag is not supported if the MS-ASProtocolVersion header is set to 12.1.

[<27> Section 2.1.2.1.11:](#) The **MergedFreeBusy** tag is not supported if the MS-ASProtocolVersion header is set to 12.1.

[<28> Section 2.1.2.1.11:](#) The **Picture** tag is not supported if the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<29> Section 2.1.2.1.11:](#) The **MaxSize** tag is not supported if the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<30> Section 2.1.2.1.11:](#) The **Data** tag is not supported if the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<31> Section 2.1.2.1.11:](#) The **MaxPictures** tag is not supported if the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<32> Section 2.1.2.1.16:](#) The **Or** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<33> Section 2.1.2.1.16:](#) The **Picture** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<34> Section 2.1.2.1.16:](#) The **MaxSize** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<35> Section 2.1.2.1.16:](#) The **MaxPictures** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<36> Section 2.1.2.1.17:](#) The **Picture** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<37> Section 2.1.2.1.17:](#) The **Status** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<38> Section 2.1.2.1.17:](#) The **Data** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<39> Section 2.1.2.1.18:](#) The **Preview** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<40> Section 2.1.2.1.18:](#) The **BodyPartPreference** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<41> Section 2.1.2.1.18:](#) The **BodyPart** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<42> Section 2.1.2.1.18:](#) The **Status** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<43> Section 2.1.2.1.19:](#) The **EnableOutboundSMS** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<44> Section 2.1.2.1.19:](#) The **MobileOperator** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<45> Section 2.1.2.1.19:](#) The **PrimarySmtpAddress** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<46> Section 2.1.2.1.19:](#) The **Accounts** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<47> Section 2.1.2.1.19:](#) The **Account** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<48> Section 2.1.2.1.19:](#) The **AccountId** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<49> Section 2.1.2.1.19:](#) The **AccountName** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<50> Section 2.1.2.1.19:](#) The **UserDisplayName** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<51> Section 2.1.2.1.19:](#) The **SendDisabled** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<52> Section 2.1.2.1.19:](#) The **RightsManagementInformation** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<53> Section 2.1.2.1.21:](#) The **Move** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<54> Section 2.1.2.1.21:](#) The **DstFldId** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<55> Section 2.1.2.1.21:](#) The **ConversationId** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<56> Section 2.1.2.1.21:](#) The **MoveAlways** tag is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<57> Section 2.1.2.1.22:](#) WBXML code page 21 is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<58> Section 2.1.2.1.22:](#) The **AccountId** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<59> Section 2.1.2.1.23:](#) WBXML code page 22 is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<60> Section 2.1.2.1.23:](#) The **AccountId** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<61> Section 2.1.2.1.23:](#) The **FirstDayOfWeek** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<62> Section 2.1.2.1.23:](#) The **MeetingMessageType** tag is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

[<63> Section 2.1.2.1.24:](#) WBXML code page 23 is not supported when the MS-ASProtocolVersion header is set to 12.1.

[<64> Section 2.1.2.1.25:](#) WBXML code page 24 is not supported when the MS-ASProtocolVersion header is set to 12.1 or 14.0.

6 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

7 Index

A

ActiveSync WBXML
 [overview](#) 9
 [Applicability](#) 7

WBXML
 [code pages](#) 9

C

[Change tracking](#) 41
[Code pages](#) 9

E

Examples
 [overview](#) 32

G

[Glossary](#) 5

I

[Implementer - security considerations](#) 36
[Index of security parameters](#) 36
[Informative references](#) 6
[Introduction](#) 5

N

[Normative references](#) 5

O

[Overview \(synopsis\)](#) 6

P

[Parameters - security index](#) 36
[Product behavior](#) 37

R

References
 [informative](#) 6
 [normative](#) 5

S

Security
 [implementer considerations](#) 36
 [parameter index](#) 36
 [Standards assignments](#) 7

T

[Tracking changes](#) 41

W