

[MS-BCSDPFFS]: Business Connectivity Services Deployment Package File Format

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Major	Updated and revised the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Major	Updated and revised the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	1.04	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	1.5	Minor	Clarified the meaning of the technical content.
04/11/2012	1.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	1.5	No change	No changes to the meaning, language, or formatting of

Date	Revision History	Revision Class	Comments
			the technical content.

Preliminary

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	7
1.3 Structure Overview (Synopsis)	7
1.4 Relationship to Protocols and Other Structures	8
1.5 Applicability Statement	8
1.6 Versioning and Localization	8
1.7 Vendor-Extensible Fields	8
2 Structures	9
2.1 ClickOnceExtensions	10
2.1.1 Namespaces	10
2.1.2 Global Elements	10
2.1.2.1 solution	10
2.1.3 Global Attributes	10
2.1.4 Complex Types	10
2.1.4.1 UpdateType	10
2.1.4.2 UpdateType	11
2.1.4.3 AddInsType	12
2.1.4.4 SolutionType	12
2.1.4.5 ExpirationType	13
2.1.4.6 AddinType	13
2.1.5 Simple Types	14
2.1.5.1 IntervalUnit	14
2.2 EntityListInformation	15
2.2.1 Namespaces	15
2.2.2 Global Elements	15
2.2.2.1 List	15
2.2.3 Global Attributes	15
2.2.4 Complex Types	15
2.2.4.1 ListType	15
2.2.4.2 EntityType	16
2.2.4.3 ViewsType	17
2.2.4.4 FormType	17
2.2.4.5 ViewType	18
2.2.5 Simple Types	18
3 Structure Examples	19
3.1 Business Connectivity Services Deployment Manifest File	19
3.2 Business Connectivity Services Application Manifest File	21
3.3 External List View Schema File	25
3.4 Entity List Information File	25
3.5 BDC Model File	26
4 Security	35
4.1 Security Considerations for Implementers	35
4.2 Index of Security Parameters	35
5 Appendix A: Full XML Schemas	36

5.1 ClickOnceExtensions Structure XSD	36
5.2 EntityListInformation Structure XSD.....	36
6 Appendix B: Product Behavior	38
7 Change Tracking.....	39
8 Index	40

Preliminary

1 Introduction

This document specifies the Business Connectivity Services Deployment Package File Format. It describes the contents of a deployment package for a Business Connectivity Services solution, the Business Connectivity Services specific extensions to the Office Server ClickOnce application manifest as described in [\[MS-OSCO\]](#), and a Business Connectivity Services specific file format representing the properties of an external list.

A typical Business Connectivity Services deployment package includes files describing the data model, custom forms, business logic and any additional files (for example, icons and images) required to run the Business Connectivity Services solution on a protocol client.

The extensions to the Office Server ClickOnce application manifest as described in [\[MS-OSCO\]](#) focus on configuring the update behavior of Business Connectivity Services solutions and other Business Connectivity Services specific solution properties. It allows a protocol client to determine the solution type for a Business Connectivity Services solution.

The external list properties can be used to create a user experience on the client similar to that on the server. For example, an external list view for customer contact information on the server can be recreated as a list view in a rich client application based on the query and view definitions described in the external list properties.

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

GUID
Unicode

The following terms are defined in [\[MS-OFCGLOS\]](#):

add-in
complex type
external content type
external list
form template
line-of-business (LOB) system
LobSystemInstance
simple type
SpecificFinder
view
view identifier
Web site
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-BDCMFFS] Microsoft Corporation, "[Business Data Connectivity Model File Format Specification](#)".

[MS-IPFF2] Microsoft Corporation, "[InfoPath Form Template Format Version 2](#)".

[MS-OSCO] Microsoft Corporation, "[Office Server ClickOnce Manifest Structure Specification](#)".

[MS-WSSCAML] Microsoft Corporation, "[Collaborative Application Markup Language \(CAML\) Structure Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[AdventureWorks] Microsoft Corporation, "AdventureWorks Sample Databases", SQL Server 2008 Books Online (July 2009), <http://msdn.microsoft.com/en-us/library/ms124501.aspx>

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

1.3 Structure Overview (Synopsis)

This document describes the deployment package structure for Business Connectivity Services solutions and the schema for two structures: the post deployment configuration of a Business Connectivity Services solution and the client representation of an **external list** definition.

The bulk of the deployment package schema is described in [\[MS-OSCO\]](#). A Business Connectivity Services deployment package always includes a file describing how the solution can connect to and interact with **line-of-business (LOB) systems**. The schema for this file is described in [\[MS-BDCMFFS\]](#). For a Business Connectivity Services solution based on an external list, the deployment package also includes an external list manifest file, specified in the EntityListInformation section of

this document. Optionally, a deployment package can include custom form definitions, code representing business logic, configuration files and resource files.

There are additional configuration settings for Business Connectivity Services solutions that are defined in the configuration for post deployment processing. The schema for these settings is specified in section [2.1](#). It extends the post action data schema of the Office Server ClickOnce application manifest schema as described in [MS-OSCO]. The configuration settings enable a protocol client to determine the identity and type of the Business Connectivity Services solution, its components.

The external list manifest file format enables a protocol client to create and configure a client representation of an external list on the server. It allows a protocol client to determine the details about a data source required to configure the client-side user interface to retrieve and display the data in an equivalent way to the server object. For example, a list item representing contact information for a customer on a web page can be rendered in a dedicated contact management application on the client.

1.4 Relationship to Protocols and Other Structures

[\[MS-OSCO\]](#) describes the Office Server ClickOnce manifest schema, and [\[MS-BDCMFFS\]](#) describes the Business Data Connectivity model file format.

1.5 Applicability Statement

ClickOnce Extensions

This structure applies only to solutions that require custom configuration for protocol clients for solution types and update behavior beyond what ClickOnce provides.

Entity List Information

None.

1.6 Versioning and Localization

Structure version: This protocol does not specify any version.

Localization: This structure does not specify any locale-specific processes or data.

1.7 Vendor-Extensible Fields

None.

2 Structures

A Business Connectivity Services deployment package consists of files that describe a Business Connectivity Services solution. The package MUST contain following files:

- A Business Connectivity Services Deployment Manifest file. The Business Connectivity Services deployment manifest file describes the composition of a Business Connectivity Services solution, and it also contains information used by the protocol client to identify the publisher and ensure the integrity of the files in the package. The Business Connectivity Services deployment manifest file is the first file downloaded to the protocol client. The file name extension MUST be ".vsto" and the file MUST conform to the format specified in [\[MS-OSCO\]](#) section 2.1. The value of the element **mapFileExtensions** of **complexType** deploymentType defined in [\[MS-OSCO\]](#) section 2.1.2.3.1 MUST be true.
- A Business Connectivity Services Application Manifest file. The Business Connectivity Services Application Manifest includes references to all other files included in the packages. The file name extension MUST be ".manifest" and the file MUST conform to the format specified in [\[MS-OSCO\]](#) section 2.2. The application manifest MUST contain a **solution** element as a child element of **postActionDataType** defined in [\[MS-OSCO\]](#) section 2.2.5.3.9 and the solution element MUST conform to the format specified in section [2.1](#) of this document. The value of the element **entryPoint** of the **entryPointsType** defined in [\[MS-OSCO\]](#) section 2.2.5.3.3 MUST be set as follows:
 - The **class** attribute MUST be set to "Microsoft.Office.BusinessApplications.Runtime.OutlookAddIn".
 - The **assemblyIdentity** element MUST have the **name** attribute set to "Microsoft.Office.BusinessApplications.Runtime", the **version** attribute set to 14.0.0.0, the **language** attribute set to "neutral", and the **processorArchitecture** attribute set to "msil".
- The value of the **entryPoint** element of **postActionType** defined in [\[MS-OSCO\]](#) section 2.2.5.3.8 MUST be set as follows:
 - The **class** attribute MUST be set to "Microsoft.Office.BusinessApplications.Runtime.DeploymentAction.SolutionDeploymentAction".
 - The **assemblyIdentity** element MUST have the **name** attribute set to "Microsoft.Office.BusinessApplications.Runtime", the **version** attribute set to 14.0.0.0, the **language** attribute set to "neutral", and the **processorArchitecture** attribute set to "msil".
- An XML file that specifies **external content type** definitions associated with the external list used in the solution. The name of the file MUST be metadata.xml.deploy, and the format MUST conform to the Metadata Model structure format defined in [\[MS-BDCMFFS\]](#) section 2.1.

The package MUST also contain following files if the package is for a Business Connectivity Services solution based on an external list:

- External List View Schema files. The format of the file MUST conform to [\[MS-WSSCAML\]](#) section 2.3.2.17. The name of this file MUST be the **view identifier** of the external list appended with ".xml.deploy".
- An XML file that specifies the deployment related properties of the external list on which the solution is based. The file format MUST conform to section [2.2](#) of this document. The name of the file MUST be ExternalListManifest.xml.deploy.

The package MAY contain following file:

- A **form template**. The file MUST conform to the format specified in [\[MS-IPFF2\]](#).

2.1 ClickOnceExtensions

2.1.1 Namespaces

This specification defines and references various XML namespaces using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]
obav1	urn:schema.microsoft.com:oba.v1	
(none)	http://microsoft.com/webservices/SharePointPortalServer/ObaWS/	

2.1.2 Global Elements

Following section specifies the top-level **solution** element. This element MUST be the child element of the **postActionDataType** defined in [\[MS-OSCO\]](#) section 2.2.5.3.9.

2.1.2.1 solution

Target namespace: urn:schemas-microsoft-com:oba.v1

A **SolutionType** element (section [2.1.4.4](#)) that specifies the properties of the solution to be installed.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xs:element name="solution" type="obav1:SolutionType"/>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.3 Global Attributes

None.

2.1.4 Complex Types

The following sections list the complex types used by the ClickOnceExtensions schema.

2.1.4.1 UpdateType

Target namespace: urn:schemas-microsoft-com:oba.v1

Referenced by: **SolutionType**

A complex type that specifies the update behavior of a solution. It specifies whether and how often the solution MAY<1> check for updates.

Child Elements:

expiration: An **ExpirationType** element (section [2.1.4.5](#)) that specifies the minimum interval of time to wait before the solution MAY<2> check for an update.

Attributes:

enabled: An **xs:boolean** attribute ([\[XMLSCHEMA2\]](#) section 3.2.2) that specifies whether update check is enabled for the solution. If the value is true, the client MAY<3> check for the update for a Business Connectivity Service solution when the minimum interval of time specified by **expiration** has passed since the last time the client checked for an update. If the value is false, the solution MUST NOT check for updates automatically.

The following W3C XML Schema fragment ([\[XMLSCHEMA1\]](#) section 2.1) specifies the contents of this complex type.

```
<xs:complexType name="UpdateType">
  <xs:sequence>
    <xs:element name="expiration" type="obav1:ExpirationType" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
  <xs:attribute name="enabled" type="xs:boolean" use="required"/>
</xs:complexType>
```

2.1.4.2 UpdateType

Target namespace: urn:schemas-microsoft-com:oba.v1

Referenced by: [SolutionType](#)

A complex type that specifies the update behavior of a solution. It specifies whether and how often the solution MAY<4> check for updates.

Child Elements:

expiration: An **ExpirationType** element (section [2.1.4.5](#)) that specifies the minimum interval of time to wait before the solution MAY<5> check for an update.

Attributes:

enabled: An **xs:boolean** attribute ([\[XMLSCHEMA2\]](#) section 3.2.2) that specifies whether update check is enabled for the solution. If the value is true, the client MAY<6> check for the update for a Business Connectivity Service solution when the minimum interval of time specified by **expiration** has passed since the last time the client checked for an update. If the value is false, the solution MUST NOT check for updates automatically.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="UpdateType">
  <xs:sequence>
    <xs:element name="expiration" type="obav1:ExpirationType" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
  <xs:attribute name="enabled" type="xs:boolean" use="required"/>
</xs:complexType>
```

```
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.3 AddInsType

Target namespace: urn:schemas-microsoft-com:oba.v1

Referenced by: [SolutionType](#)

A complex type that specifies the locations of a list of **add-ins**. This type is deprecated from the protocol and MUST be ignored.

Child Elements:

addin: An **AddinType** element (section [2.1.4.6](#)) that specifies the location of an add-in. This element is deprecated from the protocol and MUST be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AddInsType">
  <xs:sequence>
    <xs:element name="addin" type="obav1:AddinType" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.4 SolutionType

Target namespace: urn:schemas-microsoft-com:oba.v1

Referenced by: [solution](#)

A complex type that specifies the components of a solution.

Child Elements:

addins: An **AddInsType** element (section [2.1.4.3](#)) that specifies the locations of all the solution add-ins. This element is deprecated from the protocol and MUST [<7>](#) be ignored.

update: An **UpdateType** element (section [2.1.4.2](#)) that specifies the update behavior of the solution.

Attributes:

solutionId: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the **GUID** of the solution.

isSimpleSolution: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies whether the solution is a Business Connectivity Services solution based on an external list. The value of **isSimpleSolution** MUST be **true** or **false**. This attribute MUST be ignored if the value of **isDataOnly** is **true**. If the value of **isDataOnly** is **false** and the value of **isSimpleSolution** is **true**, the deployment package is for a Business Connectivity Services solution based on an external list. If

the value is **false**, the deployment package is not for a Business Connectivity Services solution based on an external list.

isSolution: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1). This attribute is deprecated from the protocol and MUST [<8>](#) be ignored.

isDataOnly: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies if the solution is a data only solution. The client MUST only deploy data model, MUST not register add-ins.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="SolutionType">
  <xs:sequence>
    <xs:element name="addins" type="obav1:AddInsType" minOccurs="0" maxOccurs="1"/>
    <xs:element name="update" type="obav1:UpdateType" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
  <xs:attribute name="solutionId" type="xs:string" use="required"/>
  <xs:attribute name="isSimpleSolution" type="xs:string" use="optional"/>
  <xs:attribute name="isSolution" type="xs:string" use="optional"/>
  <xs:attribute name="isDataOnly" type="xs:string" use="optional"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.5 ExpirationType

Target namespace: urn:schemas-microsoft-com:oba.v1

Referenced by: [UpdateType](#)

A complex type that specifies the minimum interval of time between two update checks.

Attributes:

maximumAge: An **xs:positiveInteger** attribute ([\[XMLSCHEMA2\]](#) section 3.3.25) that specifies the number of interval units.

unit: An **IntervalUnit** attribute (section [2.1.5.1](#)) that specifies the unit of time. Together with the value of **maximumAge**, it specifies the minimum interval of time to wait before the solution MUST check for an update.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ExpirationType">
  <xs:attribute name="maximumAge" type="xs:positiveInteger" default="7"/>
  <xs:attribute name="unit" type="obav1:IntervalUnit" default="days"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.6 AddinType

Target namespace: urn:schemas-microsoft-com:oba.v1

Referenced by: [AddInsType](#)

A complex type that specifies the location of an add-in. This type is deprecated from the protocol and MUST be ignored.

Attributes:

url: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the URL of an add-in.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AddinType">
  <xs:attribute name="url" type="xs:string"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5 Simple Types

Following sections specifies the simple type used by the ClickOnceExtensions schema.

2.1.5.1 IntervalUnit

Target namespace: urn:schemas-microsoft-com:oba.v1

Referenced by: [ExpirationType](#)

A **simple type** that specifies the unit of the **maximumAge** time interval. The value MUST be "days", "hours" or "weeks", as defined in the following table.

Value	Meaning
days	The time interval is given in days.
hours	The time interval is given in hours.
weeks	The time interval is given in weeks.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="IntervalUnit">
  <xs:restriction base="xs:string">
    <xs:enumeration value="days"/>
    <xs:enumeration value="hours"/>
    <xs:enumeration value="weeks"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2 EntityListInformation

2.2.1 Namespaces

This section defines and references XML namespaces using the mechanisms specified in [\[XMLNS\]](#). Although this section associates a specific XML namespace prefix for each XML namespace that is used, the choice of a specific XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]
oba	http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication	

2.2.2 Global Elements

The following section contains the top-level **List** element, which MUST be the root element of the ExternalListManifest.xml.deploy file.

2.2.2.1 List

Target namespace: <http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication>

A **ListType** element (section [2.2.4.1](#)) that specifies the deployment related properties of the external list.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xs:element name="List" type="oba:ListType"/>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.3 Global Attributes

None.

2.2.4 Complex Types

The following sections list the types used in the XML schema for the ExternalListManifest.xml.deploy file.

2.2.4.1 ListType

Target namespace: <http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication>

Referenced by: [List](#)

A complex type that specifies the deployment-related properties of an external list.

Child Elements:

Entity: An **EntityType** element (section [2.2.4.2](#)) that specifies the deployment related properties of the external content type the external list is based on.

Views: A **ViewsType** element (section [2.2.4.3](#)) that specifies the properties of all the **views** of the external list.

Form: A **FormType** element (section [2.2.4.4](#)) that specifies the default views of the forms that are used to create, display and edit an item of the external list. If any view name specified by the attribute **CreateView**, **DisplayView** or **EditView** of this element is not empty, a form template **MUST** be included in the deployment package, and a view with specified name **MUST** be defined in the form template.

Attributes:

Title: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the title of the external list.

SiteId: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the identifier of the **Web site** associated with the external list.

SiteTitle: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the title of the Web site associated with the external list.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ListType">
  <xs:sequence>
    <xs:element name="Entity" type="oba:EntityType" minOccurs="1" maxOccurs="1"/>
    <xs:element name="Views" type="oba:ViewsType" minOccurs="1" maxOccurs="1"/>
    <xs:element name="Form" type="oba:FormType" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
  <xs:attribute name="Title" form="unqualified" type="xs:string"/>
  <xs:attribute name="SiteId" form="unqualified" type="xs:string"/>
  <xs:attribute name="SiteTitle" form="unqualified" type="xs:string"/>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.2 EntityType

Target namespace: <http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication>

Referenced by: [ListType](#)

The complex type specifies the deployment related properties of an external content type.

Attributes:

LobSystemInstance: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the name of the **LobSystemInstance** of the external content type. The value **MUST** have at least 1, and at most 255 **Unicode** characters.

EntityNamespace: An **xs:string** attribute ([\[XMLSCHEMA2\]](#) section 3.2.1) that specifies the namespace of the external content type. The value **MUST** have at least 1, and at most 255 Unicode characters.

EntityName: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the name of the external content type. The value MUST have at least 1, and at most 255 Unicode characters.

SpecificFinder: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the name of a **SpecificFinder** of the external content type. The value MUST have at least 1, and at most 255 Unicode characters

DefaultViewId: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the default view identifier of the external list based on this external content type.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="EntityType">
  <xs:attribute name="LobSystemInstance" form="unqualified" type="xs:string"/>
  <xs:attribute name="EntityNamespace" form="unqualified" type="xs:string"/>
  <xs:attribute name="EntityName" form="unqualified" type="xs:string"/>
  <xs:attribute name="SpecificFinder" form="unqualified" type="xs:string"/>
  <xs:attribute name="DefaultViewId" form="unqualified" type="xs:string"/>
</xs:complexType>
```

See section 5.2 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.2.4.3 ViewType

Target namespace: http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication

Referenced by: [ListType](#)

A complex type that specifies the properties of a list of views.

Child Elements:

View: A **ViewType** element (section 2.2.4.5) that specifies the view identifier and display name of the external list view.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ViewsType">
  <xs:sequence>
    <xs:element name="View" type="oba:ViewType" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section 5.2 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.2.4.4 FormType

Target namespace: http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication

Referenced by: [ListType](#)

A complex type that specifies the default views of the forms that are used to create, display and edit an item of an external list.

Attributes:

CreateView: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the view name of the form that is used to create a new item for the external list. If the view name string is empty, default form view MUST be used.

DisplayView: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the view name of the form that is used to display an item of the external list. If the view name string is empty, default form view MUST be used.

EditView: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the view name of the form that is used to edit an item of the external list. If the view name string is empty, default form view MUST be used.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="FormType">
  <xs:attribute name="CreateView" form="unqualified" type="xs:string"/>
  <xs:attribute name="DisplayView" form="unqualified" type="xs:string"/>
  <xs:attribute name="EditView" form="unqualified" type="xs:string"/>
</xs:complexType>
```

See section 5.2 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.2.4.5 ViewType

Target namespace: <http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication>

Referenced by: [ViewsType](#)

The complex type that specifies the deployment related properties of an external list view.

Attributes:

Id: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the GUID of the external list view.

DisplayName: An **xs:string** attribute ([XMLSCHEMA2] section 3.2.1) that specifies the display name of the external list view.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ViewType">
  <xs:attribute name="Id" form="unqualified" type="xs:string"/>
  <xs:attribute name="DisplayName" form="unqualified" type="xs:string"/>
</xs:complexType>
```

See section 5.2 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.2.5 Simple Types

None.

3 Structure Examples

The following example describes the contents of the deployment package for a typical scenario where the user deploys a Business Connectivity Services solution based on an external list offline to the client. This example uses an external list based on the Customer table from the [\[AdventureWorks\]](#) database.

The deployment package consists of the following files:

- Business Connectivity Services Deployment Manifest file
- Business Connectivity Services Application Manifest file
- External List View Schema file
- Entity List Information file
- BDC Model file

3.1 Business Connectivity Services Deployment Manifest File

The Business Connectivity Services Deployment Manifest file conforms to the Office Server ClickOnce deployment manifest schema as described in [\[MS-OSCO\]](#) section 2.1.

File name: c30d5708-62c9-43fd-ab4f-66a270fa4401.vsto

```
<?xml version="1.0" encoding="utf-8"?>
<asmv1:assembly xsi:schemaLocation="urn:schemas-microsoft-com:asm.v1 assembly.adaptive.xsd"
manifestVersion="1.0" xmlns:dsig="http://www.w3.org/2000/09/xmldsig#" xmlns="urn:schemas-
microsoft-com:asm.v2" xmlns:asmv1="urn:schemas-microsoft-com:asm.v1"
xmlns:asmv2="urn:schemas-microsoft-com:asm.v2" xmlns:xrml="urn:mpeg:mpeg21:2003:01-REL-R-NS"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <assemblyIdentity name="c30d5708-62c9-43fd-ab4f-66a270fa4401" version="1.0.0.2"
publicKeyToken="e7be6b6c1584dd2d" language="neutral" processorArchitecture="msil"
xmlns="urn:schemas-microsoft-com:asm.v1" />
  <description asmv2:publisher="DefaultPublisher" asmv2:product="ExternalList"
xmlns="urn:schemas-microsoft-com:asm.v1" />
  <deployment install="false" mapFileExtensions="true" />
  <dependency>
    <dependentAssembly dependencyType="install" codebase="1a71432d-a42b-488d-b997-
a33981706d4e\c30d5708-62c9-43fd-ab4f-66a270fa4401.manifest" size="9218">
      <assemblyIdentity name="c30d5708-62c9-43fd-ab4f-66a270fa4401" version="1.0.0.2"
publicKeyToken="e7be6b6c1584dd2d" language="neutral" processorArchitecture="msil"
type="win32" />
      <hash>
        <dsig:Transforms>
          <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
        </dsig:Transforms>
        <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
        <dsig:DigestValue>nZXIGWllasvWpy29MwRtbUrlYw=</dsig:DigestValue>
      </hash>
    </dependentAssembly>
  </dependency>
  <publisherIdentity name="CN=domain\user_name"
issuerKeyHash="d3b77cca297a35c9bdf34b571c9bf56a8f7eecdd" />
  <Signature Id="StrongNameSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
    <SignedInfo>
      <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
      <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
```

```

<Reference URI="">
  <Transforms>
    <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature" />
    <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
  </Transforms>
  <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
  <DigestValue>djOVkf9pLtr+Ty336Me1DxA4zMw=</DigestValue>
</Reference>
</SignedInfo>

<SignatureValue>RYTzCo+6VOBHfyVVi/tb3dZ/7vgL67vfcIaP+PIu1UTX6G7wceT8116H51zXNcr10wbNwL7LGZPqu
H50IyV3kZtOpp3Xi4SW2x91//4NYy3sZ+GsKUAbkLS2fYH0CNSNBrWbdBVUf6iqS9PhGFwueohghf5zLiYCL8MYyD5uvF
w=</SignatureValue>
  <KeyInfo Id="StrongNameKeyInfo">
    <KeyValue>
      <RSAKeyValue>

<Modulus>zL0sC9H1Od126c6MJjua/TOSyyKQXI3bPGY8yzoTh6dafUBP0hz/0008yltiJogOjJouFHUFdLhDuy1S98io
OF/ipTNwrNcdovtqWlRtMxD0hZ71N2tF5yEyEnlNFQbprRN3LI0Ez18vgMwDHy/u5CDPW+Eg1MKdqVclC/IEjM=</Mod
ulus>
    <Exponent>AQAB</Exponent>
  </RSAKeyValue>
</KeyValue>
  <msrel:RelData xmlns:msrel="http://schemas.microsoft.com/windows/rel/2005/reldata">
    <r:license xmlns:r="urn:mpeg:mpeg21:2003:01-REL-R-NS"
xmlns:as="http://schemas.microsoft.com/windows/pki/2005/Authenticode">
      <r:grant>
        <as:ManifestInformation Hash="cccc38100fa5c7e8f72d4ffeda2e69ff91953376"
Description="" Url="">
          <as:assemblyIdentity name="c30d5708-62c9-43fd-ab4f-66a270fa4401"
version="1.0.0.2" publicKeyToken="e7be6b6c1584dd2d" language="neutral"
processorArchitecture="msil" xmlns="urn:schemas-microsoft-com:asm.v1" />
        </as:ManifestInformation>
        <as:SignedBy />
        <as:AuthenticodePublisher>
          <as:X509SubjectName>CN=domain\user_name</as:X509SubjectName>
        </as:AuthenticodePublisher>
      </r:grant>
      <r:issuer>
        <Signature Id="AuthenticodeSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
          <SignedInfo>
            <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"
/>
            <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
            <Reference URI="">
              <Transforms>
                <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-
signature" />
                <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
              </Transforms>
              <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
              <DigestValue>RgctFiv/PenecRcsro9z6HbqQdM=</DigestValue>
            </Reference>
          </SignedInfo>
          <SignatureValue>DLgPJk2rZED338K8k6ZFxuWFRIKg1DLtc/KQG5jD2kqbIWs61X9o14LduOyyi+/uNmpkK5ED+2X6N
LElGQxvfp05QjwTxsRbmf05cT5rUubykqPEdelLejmUg/W3Pow/0kS+06Hmxhn7/GmNZbFIsyX02V3302Cb1ofqe1Z0wV
8=</SignatureValue>
            <KeyInfo>
              <KeyValue>

```

```

    <RSAKeyValue>
      <Modulus>zL0sC9HlOd126c6MJjua/TOSyyKQXI3bPGY8yzoTh6dafUBP0hz/0008yltiJogOjJouFHUFdLhDuy1S98io
      OF/ipTNwrNcdovtqWlRtMxD0hZ71N2tF5yEyEnleNFQbprRN3LI0Ez18vgMwDHy/u5CDPW+Eg1MKdqVclC/IEjM=</Mod
      ulus>
      <Exponent>AQAB</Exponent>
    </RSAKeyValue>
  </KeyValue>
  <X509Data>
    <X509Certificate>MIIB5jCCA VOgAwIBAgIQTPcmZZHsKa1PCFsSn1++HDAJBgUrDgMCHQUAMCkxJzAlBgNVBAMEHgBS
    AEUARABNAE8ATgBEAFwATwBmAGYAVAAyADMANTAEfW0xMDAxMTQwMjI2MzRaFw0xOTAxMDIwMDAwMDBaMCkxJzAlBgNVB
    AMeHgBSAEUARABNAE8ATgBEAFwATwBmAGYAVAAyADMANTCBnzANBgkqhkiG9w0BAQEFAAOBjQAwYkCgYEAzL0sC9HlOd
    126c6MJjua/TOSyyKQXI3bPGY8yzoTh6dafUBP0hz/0008yltiJogOjJouFHUFdLhDuy1S98ioOF/ipTNwrNcdovtqWlR
    tMxD0hZ71N2tF5yEyEnleNFQbprRN3LI0Ez18vgMwDHy/u5CDPW+Eg1MKdqVclC/IEjMCAwEAAMXMBUwEwYDVR01BAww
    CgYIKwYBBQUHAWMwCQYFKw4DAh0FAAOBgQDJLFkC9FSc/DwPub3019i5JpaKdaNWKsrsekeE3HfHSzcCft3/wBL7EnTHT
    cTCTnFOOnXEKVbeJC/CaV8PVowg/RvoVr1UBHa4sW8xBi4+NtIqWruy9WHP31Z1GLGEEW5RLwNBWfnZeKWHODlnJzt2/
    Wsr1aMllygKBelRmdHg==</X509Certificate>
  </X509Data>
</KeyInfo>
</Signature>
</r:issuer>
</r:license>
</msrel:RelData>
</KeyInfo>
</Signature>
</asmv1:assembly>

```

3.2 Business Connectivity Services Application Manifest File

The Business Connectivity Services Application Manifest file is an extension of the Office Server ClickOnce application manifest schema as described in [\[MS-OSCO\]](#) section 2.2. The extension to the Office Server ClickOnce application manifest consists of the XML element `obav1:solution` which specifies the parameters for the solution update check.

File name: `c30d5708-62c9-43fd-ab4f-66a270fa4401.manifest`

```

<?xml version="1.0" encoding="utf-8"?>
<asmv1:assembly xsi:schemaLocation="urn:schemas-microsoft-com:asm.v1 assembly.adaptive.xsd"
manifestVersion="1.0" xmlns:dsig="http://www.w3.org/2000/09/xmldsig#" xmlns="urn:schemas-
microsoft-com:asm.v2" xmlns:asmv1="urn:schemas-microsoft-com:asm.v1"
xmlns:asmv2="urn:schemas-microsoft-com:asm.v2" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance">
  <asmv1:assemblyIdentity name="c30d5708-62c9-43fd-ab4f-66a270fa4401" version="1.0.0.2"
publicKeyToken="e7be6b6c1584dd2d" language="neutral" processorArchitecture="msil"
type="win32" />
  <application />
  <entryPoint>
    <co.v1:customHostSpecified xmlns:co.v1="urn:schemas-microsoft-com:clickonce.v1" />
  </entryPoint>
  <trustInfo>
    <security xmlns="urn:schemas-microsoft-com:asm.v2">
      <applicationRequestMinimum>
        <PermissionSet Unrestricted="true" ID="Custom" SameSite="site" />
        <defaultAssemblyRequest permissionSetReference="Custom" />
      </applicationRequestMinimum>
      <requestedPrivileges xmlns="urn:schemas-microsoft-com:asm.v3">
        <requestedExecutionLevel level="asInvoker" />
      </requestedPrivileges>
    </security>
  </trustInfo>

```

```

    </security>
  </trustInfo>
  <dependency>
    <dependentOS>
      <osVersionInfo>
        <os majorVersion="4" minorVersion="10" buildNumber="0" servicePackMajor="0" />
      </osVersionInfo>
    </dependentOS>
  </dependency>
  <dependency>
    <dependentAssembly dependencyType="preRequisite" allowDelayedBinding="true">
      <assemblyIdentity name="Microsoft.Windows.CommonLanguageRuntime" version="2.0.50727.0"
    />
    </dependentAssembly>
  </dependency>
  <file name="03fcc009-72df-454b-8c89-bbb7d811b5a3.xml" size="677">
    <hash>
      <dsig:Transforms>
        <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
      </dsig:Transforms>
      <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <dsig:DigestValue>dhsAZIAQWXN0GiZza7483zh6xhk=</dsig:DigestValue>
    </hash>
  </file>
  <file name="ExternalListManifest.xml" size="570">
    <hash>
      <dsig:Transforms>
        <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
      </dsig:Transforms>
      <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <dsig:DigestValue>CouVSoFHiaCltx9gud3LabMZ1vA=</dsig:DigestValue>
    </hash>
  </file>
  <file name="metadata.xml" size="53794">
    <hash>
      <dsig:Transforms>
        <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
      </dsig:Transforms>
      <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <dsig:DigestValue>ZQc9PfIk6erGs+cMIHTfLvSoI+w=</dsig:DigestValue>
    </hash>
  </file>
  <file name="template.xsn" size="9321">
    <hash>
      <dsig:Transforms>
        <dsig:Transform Algorithm="urn:schemas-microsoft-com:HashTransforms.Identity" />
      </dsig:Transforms>
      <dsig:DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
      <dsig:DigestValue>wwI3lKsQv40z+vyV2I1bsFfOflo=</dsig:DigestValue>
    </hash>
  </file>
  <vstav3:addIn xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
    <vstav3:entryPointsCollection xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
      <vstav3:entryPoint
class="Microsoft.Office.BusinessApplications.Runtime.OutlookAddIn">
        <assemblyIdentity name="Microsoft.Office.BusinessApplications.Runtime"
version="14.0.0.0" publicKeyToken="94de0004b6e3fcc5" language="neutral"
processorArchitecture="msil" />

```

```

        </vstav3:entryPoint>
    </vstav3:entryPoints>
</vstav3:entryPointsCollection>
<vstav3:update enabled="false" xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3" />
<vstav3:postActions xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
    <vstav3:postAction>
        <vstav3:entryPoint
class="Microsoft.Office.BusinessApplications.Runtime.DeploymentAction.SolutionDeploymentAction"
n">
            <assemblyIdentity name="Microsoft.Office.BusinessApplications.Runtime"
version="14.0.0.0" publicKeyToken="94de0004b6e3fcc5" language="neutral"
processorArchitecture="msil" />
        </vstav3:entryPoint>
        <vstav3:postActionData>
            <obav1:solution solutionId="c30d5708-62c9-43fd-ab4f-66a270fa4401"
isSimpleSolution="True" isSolution="True" xmlns:obav1="urn:schemas-microsoft-com:oba.v1">
                <obav1:addins />
                <obav1:update enabled="true">
                    <obav1:expiration maximumAge="7" unit="days" />
                </obav1:update>
            </obav1:solution>
        </vstav3:postActionData>
    </vstav3:postAction>
</vstav3:postActions>
<vstav3:application xmlns:vstav3="urn:schemas-microsoft-com:vsta.v3">
    <vstov4:customizations xmlns:vstov4="urn:schemas-microsoft-com:vsto.v4">
        <vstov4:customization>
            <vstov4:appAddIn application="Outlook" loadBehavior="2" keyName="OutlookAddIn1">
                <vstov4:friendlyName>OutlookAddIn1</vstov4:friendlyName>
                <vstov4:description>OutlookAddIn1</vstov4:description>
            </vstov4:appAddIn>
        </vstov4:customization>
    </vstov4:customizations>
</vstav3:application>
</vstav3:addIn>
<publisherIdentity name="CN=domain\user_name"
issuerKeyHash="d3b77cca297a35c9bdf34b571cfbf56a8f7eecdd" />
<Signature Id="StrongNameSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
    <SignedInfo>
        <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
        <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
        <Reference URI="">
            <Transforms>
                <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-signature" />
                <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
            </Transforms>
            <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
            <DigestValue>bysVdOftdJo0X2ggS1cI4d7PF2c=</DigestValue>
        </Reference>
    </SignedInfo>
    <SignatureValue>se/KIMuEVxlMyoW9FThLkyH+F5kj2mRvD5Yyi92OjHtKWZFFsPfDbTMNVvavh3sNZnyktyY8YdqHT
1q48Xhf4YBpoIvecBEYWJTO1VasczzF1ATQg21yIAmRw6W124sKa3QMv9KXjh/0kuCnjwyt1zUJnG+4nWD1Y7jdxpDmdx
E=</SignatureValue>
    <KeyInfo Id="StrongNameKeyInfo">
        <KeyValue>
            <RSAKeyValue>
                <Modulus>zL0sC9H1Od126c6MJjua/TOSyyQXl3bPGY8yzoTh6dafUBP0hz/0008yltiJogOjJouFHUFdLhDuy1S98io

```

```

OF/ipTNwrNcdovtqWlRtMxD0hZ71N2tF5yEyEnleNFQbprRN3LI0Ez18vgMwDHy/u5CDPW+EglMKdqVclC/IEjM=</Mod
ulus>
  <Exponent>AQAB</Exponent>
</RSAKeyValue>
</KeyValue>
<msrel:RelData xmlns:msrel="http://schemas.microsoft.com/windows/rel/2005/reldata">
  <r:license xmlns:r="urn:mpeg:mpeg21:2003:01-REL-R-NS"
xmlns:as="http://schemas.microsoft.com/windows/pki/2005/Authenticode">
  <r:grant>
    <as:ManifestInformation Hash="6717cfdee108574b20685f349a74ede774152b6f"
Description="" Url="">
      <as:assemblyIdentity name="c30d5708-62c9-43fd-ab4f-66a270fa4401"
version="1.0.0.2" publicKeyToken="e7be6b6c1584dd2d" language="neutral"
processorArchitecture="msil" type="win32" />
    </as:ManifestInformation>
    <as:SignedBy />
    <as:AuthenticodePublisher>
      <as:X509SubjectName>CN=domain\user_name</as:X509SubjectName>
    </as:AuthenticodePublisher>
  </r:grant>
</r:issuer>
  <Signature Id="AuthenticodeSignature" xmlns="http://www.w3.org/2000/09/xmldsig#">
    <SignedInfo>
      <CanonicalizationMethod Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#"
/>
      <SignatureMethod Algorithm="http://www.w3.org/2000/09/xmldsig#rsa-sha1" />
      <Reference URI="">
        <Transforms>
          <Transform Algorithm="http://www.w3.org/2000/09/xmldsig#enveloped-
signature" />
            <Transform Algorithm="http://www.w3.org/2001/10/xml-exc-c14n#" />
          </Transforms>
          <DigestMethod Algorithm="http://www.w3.org/2000/09/xmldsig#sha1" />
          <DigestValue>u/kg55tTzZv1Cgwq6DxD0YEQpYE=</DigestValue>
        </Reference>
      </SignedInfo>
    <SignatureValue>EbOYHfvr622RRX850Q8OFttzhmKxGFHgORDu3F4gtZsF1PRLV1uBTh87nRqxrK6tLohyX26F32RyQ
VR7169eCOw8NcBxCyVm2I9bC/KrmZX+pXiP1J+N8EyhFoF1HG5zeyH1iw3CaDcYP0g3l1ddAlBBFWtD3Jc5j2f9u6HRK1X
k=</SignatureValue>
    <KeyInfo>
      <KeyValue>
        <RSAKeyValue>
          <Modulus>zL0sC9H1Od126c6MJjua/TOSyyKQXI3bPGY8yzoTh6dafUBP0hz/0008y1tiJogOjJouFHUFdLhDuy1S98io
OF/ipTNwrNcdovtqWlRtMxD0hZ71N2tF5yEyEnleNFQbprRN3LI0Ez18vgMwDHy/u5CDPW+EglMKdqVclC/IEjM=</Mod
ulus>
          <Exponent>AQAB</Exponent>
        </RSAKeyValue>
      </KeyValue>
      <X509Data>
        <X509Certificate>MIIB5jCCAvoGAWIBAgIQTPcmZHSKAlPCFsSn1++HDAJBgUrDgMCHQUAMCkxJzAlBgNVBAMEHgBS
AEUARABNAE8ATgBEAFwATwBmAGYAVAAyADMANTAEFw0xMDAxMTQwMjI2MzRaFw0xOTAxMDIwMDAwMDBaMCKxJzAlBgNVB
AMeHgBSAEUARABNAE8ATgBEAFwATwBmAGYAVAAyADMANTCBnzANBgkqhkiG9w0BAQEFAAOBjQAwYkCgYEAzL0sC9H1Od
126c6MJjua/TOSyyKQXI3bPGY8yzoTh6dafUBP0hz/0008y1tiJogOjJouFHUFdLhDuy1S98ioOF/ipTNwrNcdovtqWlR
tMxD0hZ71N2tF5yEyEnleNFQbprRN3LI0Ez18vgMwDHy/u5CDPW+EglMKdqVclC/IEjMCAwEAAaMXMBUwEwYDVR01BAww
CgYIKwYBBQUHAwMwCQYFKw4DAh0FAAOBgQDjLfkC9FSc/DwPub3019i5JpaKdaNWKsrsekeE3HfHSzcCft3/wBL7EnTHT
cTCtnf0OnwXEKVbeJC/CaV8PVowg/RvoVr1UBHa4sW8xBi4+NtIqWruy9WHP31Z1GLGEEW5RLwNBWfnZekWHODlnJzt2/
VwsrlaM1lygKBelRmdHg==</X509Certificate>
      </X509Data>
    </KeyInfo>
  </SignatureValue>
</SignatureValue>
</SignatureValue>

```



```

        </Signature>
      </r:issuer>
    </r:license>
  </msrel:RelData>
</KeyInfo>
</Signature>
</asmv1:assembly>

```

3.3 External List View Schema File

The External List View Schema file conforms to the schema described in [\[MS-WSSCAML\]](#) section 2.3.2.17. The file contains information about the views of the external list for which the deployment package is created. The following is an example view of an external list, which is based on an external content type, which is based on the Customer table from [\[AdventureWorks\]](#) database.

File name: 03fcc009-72df-454b-8c89-bbb7d811b5a3.xml.deploy

```

<View Name="{03FCC009-72DF-454B-8C89-BBB7D811B5A3}" DefaultView="TRUE" MobileView="TRUE"
MobileDefaultView="TRUE" Type="HTML" DisplayName="Customer"
Url="/Lists/ExternalList/CustomQuery Item List.aspx" Level="1" BaseViewID="1"
ContentTypeID="0x" ImageUrl="/_layouts/images/generic.png">
  <Method Name="CustomerQuery Item List"/>
  <Query>
    <OrderBy>
      <FieldRef Name="CustomerID"/>
    </OrderBy>
  </Query>
  <ViewFields>
    <FieldRef Name="CustomerID" ListItemMenu="TRUE" LinkToItem="TRUE"/>
    <FieldRef Name="TerritoryID"/>
    <FieldRef Name="AccountNumber"/>
    <FieldRef Name="CustomerType"/>
    <FieldRef Name="ModifiedDate"/>
  </ViewFields>
  <RowLimit Paged="TRUE">30</RowLimit>
  <Aggregations Value="Off"/>
</View>

```

3.4 Entity List Information File

The Entity List Information file contains the properties of the external list on which the solution is based.

File name: ExternalListManifest.xml.deploy

```

<?xml version="1.0" encoding="utf-8"?>
<List Title="ExternalList" SiteId="2e231fc1-e608-4f52-aef3-23244b6abc5b" SiteTitle="Example
Site" xmlns="http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication">
  <Entity LobSystemInstance="AdventureWorks" EntityNamespace="http://example.com"
EntityName="Customer" SpecificFinder="CustomerRead Item" DefaultViewId="03fcc009-72df-454b-
8c89-bbb7d811b5a3" />
  <Views>
    <View Id="03fcc009-72df-454b-8c89-bbb7d811b5a3" DisplayName="Customer" />
  </Views>
  <Form CreateView="" DisplayView="Read Item" EditView="" />
</List>

```

3.5 BDC Model File

The BDC Model file conforms to schema described in [\[MS-BDCMFFS\]](#). It contains the external content type definition associated with the external list included in the package.

File name: metadata.xml.deploy

```
<?xml version="1.0" encoding="utf-16" standalone="yes"?>
<Model xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog
BDCMetadata.xsd" Name="MC Sample" IsCached="false"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <AccessControlList>
    <AccessControlEntry Principal="domain\user_name">
      <Right BdcRight="Edit" />
      <Right BdcRight="Execute" />
      <Right BdcRight="SetPermissions" />
      <Right BdcRight="SelectableInClients" />
    </AccessControlEntry>
  </AccessControlList>
  <LobSystems>
    <LobSystem Type="Database" Name="AdventureWorks">
      <Properties>
        <Property Name="WildcardCharacter" Type="System.String">%</Property>
      </Properties>
      <AccessControlList>
        <AccessControlEntry Principal="domain\user_name">
          <Right BdcRight="Edit" />
          <Right BdcRight="Execute" />
          <Right BdcRight="SetPermissions" />
          <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
      </AccessControlList>
      <Proxy />
      <LobSystemInstances>
        <LobSystemInstance Name="AdventureWorks">
          <Properties>
            <Property Name="AuthenticationMode" Type="System.String">PassThrough</Property>
            <Property Name="DatabaseAccessProvider" Type="System.String">SqlServer</Property>
            <Property Name="RdbConnection Data Source"
Type="System.String">example.com</Property>
            <Property Name="RdbConnection Initial Catalog"
Type="System.String">AdventureWorks</Property>
            <Property Name="RdbConnection Integrated Security"
Type="System.String">SSPI</Property>
            <Property Name="RdbConnection Pooling" Type="System.String">True</Property>
          </Properties>
        </LobSystemInstance>
      </LobSystemInstances>
      <Entities>
        <Entity Namespace="http://example.com" Version="1.0.0.0"
EstimatedInstanceCount="10000" Name="Customer" DefaultDisplayName="Customer">
          <Properties>
            <Property Name="OutlookItemType" Type="System.String">Post</Property>
          </Properties>
        </Entity>
      </Entities>
    </LobSystem>
  </LobSystems>
  <AccessControlList>
```

```

    <AccessControlEntry Principal="domain\user_name">
      <Right BdcRight="Edit" />
      <Right BdcRight="Execute" />
      <Right BdcRight="SetPermissions" />
      <Right BdcRight="SelectableInClients" />
    </AccessControlEntry>
  </AccessControlList>
  <Identifiers>
    <Identifier TypeName="System.Int32" Name="CustomerID" />
  </Identifiers>
  <Methods>
    <Method Name="CustomerCreate Item" DefaultDisplayName="Create Item Customer">
      <Properties>
        <Property Name="BackEndObject" Type="System.String">Customer</Property>
        <Property Name="BackEndObjectType"
Type="System.String">SqlServerTable</Property>
        <Property Name="RdbCommandText" Type="System.String">INSERT INTO
[AdventureWorks].[Sales].[Customer]([TerritoryID] , [CustomerType] , [rowguid] ,
[ModifiedDate]) VALUES(@TerritoryID , @CustomerType , @rowguid , @ModifiedDate) SELECT
[CustomerID] FROM [AdventureWorks].[Sales].[Customer] WHERE [CustomerID] =
@@IDENTITY</Property>
        <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">Text</Property>
        <Property Name="Schema" Type="System.String">Sales</Property>
      </Properties>
      <AccessControlList>
        <AccessControlEntry Principal="domain\user_name">
          <Right BdcRight="Edit" />
          <Right BdcRight="Execute" />
          <Right BdcRight="SetPermissions" />
          <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
      </AccessControlList>
      <Parameters>
        <Parameter Direction="In" Name="@TerritoryID">
          <TypeDescriptor TypeName="System.Nullable`1[[System.Int32, mscorlib,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089]]" CreatorField="true"
Name="TerritoryID" />
        </Parameter>
        <Parameter Direction="In" Name="@CustomerType">
          <TypeDescriptor TypeName="System.String" CreatorField="true"
Name="CustomerType">
            <Properties>
              <Property Name="Size" Type="System.Int32">1</Property>
            </Properties>
          </TypeDescriptor>
        </Parameter>
        <Parameter Direction="In" Name="@rowguid">
          <TypeDescriptor TypeName="System.Guid" CreatorField="true" Name="rowguid"
/>
        </Parameter>
        <Parameter Direction="In" Name="@ModifiedDate">
          <TypeDescriptor TypeName="System.DateTime" CreatorField="true"
Name="ModifiedDate">
            <Interpretation>
              <NormalizeDateTime LobDateTimeMode="UTC" />
            </Interpretation>
          </TypeDescriptor>
        </Parameter>
        <Parameter Direction="Return" Name="Customer">

```

```

        <TypeDescriptor TypeName="System.Data.IDataReader, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" IsCollection="true"
Name="Customer">
        <TypeDescriptors>
        <TypeDescriptor TypeName="System.Data.IDataRecord, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" Name="CustomerElement">
        <TypeDescriptors>
        <TypeDescriptor TypeName="System.Int32" ReadOnly="true"
IdentifierName="CustomerID" Name="CustomerID" />
        </TypeDescriptors>
        </TypeDescriptor>
        </TypeDescriptors>
        </TypeDescriptor>
        </Parameters>
        <MethodInstances>
        <MethodInstance Type="Creator" ReturnParameterName="Customer"
ReturnTypeDescriptorPath="Customer[0]" Default="true" Name="CustomerCreate Item"
DefaultDisplayName="Customer">
        <AccessControlList>
        <AccessControlEntry Principal="domain\user_name">
        <Right BdcRight="Edit" />
        <Right BdcRight="Execute" />
        <Right BdcRight="SetPermissions" />
        <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
        </AccessControlList>
        </MethodInstance>
        </MethodInstances>
        </Method>
        <Method Name="CustomerRead Item" DefaultDisplayName="Read Item Customer">
        <Properties>
        <Property Name="BackEndObject" Type="System.String">Customer</Property>
        <Property Name="BackEndObjectType"
Type="System.String">SqlServerTable</Property>
        <Property Name="RdbCommandText" Type="System.String">SELECT [CustomerID] ,
[TerritoryID] , [AccountNumber] , [CustomerType] , [rowguid] , [ModifiedDate] FROM
[AdventureWorks].[Sales].[Customer] WHERE [CustomerID] = @CustomerID</Property>
        <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">Text</Property>
        <Property Name="Schema" Type="System.String">Sales</Property>
        </Properties>
        <AccessControlList>
        <AccessControlEntry Principal="domain\user_name">
        <Right BdcRight="Edit" />
        <Right BdcRight="Execute" />
        <Right BdcRight="SetPermissions" />
        <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
        </AccessControlList>
        <Parameters>
        <Parameter Direction="In" Name="@CustomerID">
        <TypeDescriptor TypeName="System.Int32" IdentifierName="CustomerID"
Name="CustomerID" />
        </Parameter>
        <Parameter Direction="Return" Name="Customer">
        <TypeDescriptor TypeName="System.Data.IDataReader, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" IsCollection="true"
Name="Customer">
        <TypeDescriptors>

```

```

        <TypeDescriptor TypeName="System.Data.IDataRecord, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" Name="CustomerElement">
        <TypeDescriptors>
        <TypeDescriptor TypeName="System.Int32" ReadOnly="true"
IdentifierName="CustomerID" Name="CustomerID" />
        <TypeDescriptor TypeName="System.Nullable`1[[System.Int32,
mscorlib, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089]]"
Name="TerritoryID" />
        <TypeDescriptor TypeName="System.String" ReadOnly="true"
Name="AccountNumber">
        <Properties>
        <Property Name="OfficeProperty"
Type="System.String">Subject</Property>
        <Property Name="Size" Type="System.Int32">10</Property>
        </Properties>
        </TypeDescriptor>
        <TypeDescriptor TypeName="System.String" Name="CustomerType">
        <Properties>
        <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
        <Property Name="Size" Type="System.Int32">1</Property>
        </Properties>
        </TypeDescriptor>
        <TypeDescriptor TypeName="System.Guid" Name="rowguid">
        <Properties>
        <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
        </Properties>
        </TypeDescriptor>
        <TypeDescriptor TypeName="System.DateTime" Name="ModifiedDate">
        <Properties>
        <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
        </Properties>
        <Interpretation>
        <NormalizeDateTime LobDateTimeMode="UTC" />
        </Interpretation>
        </TypeDescriptor>
        </TypeDescriptors>
        </TypeDescriptor>
        </TypeDescriptors>
        </TypeDescriptor>
        </Parameter>
        </Parameters>
        <MethodInstances>
        <MethodInstance Type="SpecificFinder" ReturnParameterName="Customer"
ReturnTypeDescriptorPath="Customer[0]" Default="true" Name="CustomerRead Item"
DefaultDisplayName="Customer">
        <Properties>
        <Property Name="LastDesignedOfficeItemType"
Type="System.String">Post</Property>
        </Properties>
        <AccessControlList>
        <AccessControlEntry Principal="domain\user_name">
        <Right BdcRight="Edit" />
        <Right BdcRight="Execute" />
        <Right BdcRight="SetPermissions" />
        <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
        </AccessControlList>

```

```

        </MethodInstance>
    </MethodInstances>
</Method>
<Method Name="CustomerUpdate Item" DefaultDisplayName="Update Item Customer">
    <Properties>
        <Property Name="BackEndObject" Type="System.String">Customer</Property>
        <Property Name="BackEndObjectType"
Type="System.String">SqlServerTable</Property>
        <Property Name="RdbCommandText" Type="System.String">UPDATE
[AdventureWorks].[Sales].[Customer] SET [TerritoryID] = @TerritoryID , [CustomerType] =
@CustomerType , [rowguid] = @rowguid , [ModifiedDate] = @ModifiedDate WHERE [CustomerID] =
@CustomerID</Property>
        <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">Text</Property>
        <Property Name="Schema" Type="System.String">Sales</Property>
    </Properties>
    <AccessControlList>
        <AccessControlEntry Principal="domain\user_name">
            <Right BdcRight="Edit" />
            <Right BdcRight="Execute" />
            <Right BdcRight="SetPermissions" />
            <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
    </AccessControlList>
    <Parameters>
        <Parameter Direction="In" Name="@CustomerID">
            <TypeDescriptor TypeName="System.Int32" UpdaterField="true"
IdentifierName="CustomerID" Name="CustomerID" />
        </Parameter>
        <Parameter Direction="In" Name="@TerritoryID">
            <TypeDescriptor TypeName="System.Nullable`1[[System.Int32, mscorlib,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089]]" UpdaterField="true"
Name="TerritoryID" />
        </Parameter>
        <Parameter Direction="In" Name="@CustomerType">
            <TypeDescriptor TypeName="System.String" UpdaterField="true"
Name="CustomerType">
                <Properties>
                    <Property Name="Size" Type="System.Int32">1</Property>
                </Properties>
            </TypeDescriptor>
        </Parameter>
        <Parameter Direction="In" Name="@rowguid">
            <TypeDescriptor TypeName="System.Guid" UpdaterField="true" Name="rowguid"
/>
        </Parameter>
        <Parameter Direction="In" Name="@ModifiedDate">
            <TypeDescriptor TypeName="System.DateTime" UpdaterField="true"
Name="ModifiedDate">
                <Interpretation>
                    <NormalizeDateTime LobDateTimeMode="UTC" />
                </Interpretation>
            </TypeDescriptor>
        </Parameter>
    </Parameters>
    <MethodInstances>
        <MethodInstance Type="Updater" Name="CustomerUpdate Item"
DefaultDisplayName="Customer">
            <AccessControlList>
                <AccessControlEntry Principal="domain\user_name">

```

```

        <Right BdcRight="Edit" />
        <Right BdcRight="Execute" />
        <Right BdcRight="SetPermissions" />
        <Right BdcRight="SelectableInClients" />
    </AccessControlEntry>
</AccessControlList>
</MethodInstance>
</MethodInstances>
</Method>
<Method Name="CustomerDelete Item" DefaultDisplayName="Delete Item Customer">
    <Properties>
        <Property Name="BackEndObject" Type="System.String">Customer</Property>
        <Property Name="BackEndObjectType"
Type="System.String">SqlServerTable</Property>
        <Property Name="RdbCommandText" Type="System.String">DELETE FROM
[AdventureWorks].[Sales].[Customer] WHERE [CustomerID] = @CustomerID</Property>
        <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">Text</Property>
        <Property Name="Schema" Type="System.String">Sales</Property>
    </Properties>
    <AccessControlList>
        <AccessControlEntry Principal="domain\user_name">
            <Right BdcRight="Edit" />
            <Right BdcRight="Execute" />
            <Right BdcRight="SetPermissions" />
            <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
    </AccessControlList>
    <Parameters>
        <Parameter Direction="In" Name="@CustomerID">
            <TypeDescriptor TypeName="System.Int32" IdentifierName="CustomerID"
Name="CustomerID" />
        </Parameter>
    </Parameters>
    <MethodInstances>
        <MethodInstance Type="Deleter" Name="CustomerDelete Item"
DefaultDisplayName="Customer">
            <AccessControlList>
                <AccessControlEntry Principal="domain\user_name">
                    <Right BdcRight="Edit" />
                    <Right BdcRight="Execute" />
                    <Right BdcRight="SetPermissions" />
                    <Right BdcRight="SelectableInClients" />
                </AccessControlEntry>
            </AccessControlList>
        </MethodInstance>
    </MethodInstances>
</Method>
<Method Name="CustomerQuery Item List" DefaultDisplayName="Customer Query Item
List">
    <Properties>
        <Property Name="BackEndObject" Type="System.String">Customer</Property>
        <Property Name="BackEndObjectType"
Type="System.String">SqlServerTable</Property>
        <Property Name="RdbCommandText" Type="System.String">SELECT [CustomerID] ,
[TerritoryID] , [AccountNumber] , [CustomerType] , [rowguid] , [ModifiedDate] FROM
[AdventureWorks].[Sales].[Customer]</Property>
        <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">Text</Property>
        <Property Name="Schema" Type="System.String">Sales</Property>
    </Properties>

```

```

</Properties>
<AccessControlList>
  <AccessControlEntry Principal="domain\user_name">
    <Right BdcRight="Edit" />
    <Right BdcRight="Execute" />
    <Right BdcRight="SetPermissions" />
    <Right BdcRight="SelectableInClients" />
  </AccessControlEntry>
</AccessControlList>
<Parameters>
  <Parameter Direction="Return" Name="Customer">
    <TypeDescriptor TypeName="System.Data.IDataReader, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" IsCollection="true"
Name="Customer">
      <TypeDescriptors>
        <TypeDescriptor TypeName="System.Data.IDataRecord, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" Name="CustomerElement">
          <TypeDescriptors>
            <TypeDescriptor TypeName="System.Int32" ReadOnly="true"
IdentifierName="CustomerID" Name="CustomerID" />
            <TypeDescriptor TypeName="System.Nullable`1[[System.Int32,
mscorlib, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089]]"
Name="TerritoryID" />
            <TypeDescriptor TypeName="System.String" ReadOnly="true"
Name="AccountNumber">
              <Properties>
                <Property Name="Size" Type="System.Int32">10</Property>
              </Properties>
            </TypeDescriptor>
            <TypeDescriptor TypeName="System.String" Name="CustomerType">
              <Properties>
                <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
                <Property Name="Size" Type="System.Int32">1</Property>
              </Properties>
            </TypeDescriptor>
            <TypeDescriptor TypeName="System.Guid" Name="rowguid">
              <Properties>
                <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
              </Properties>
            </TypeDescriptor>
            <TypeDescriptor TypeName="System.DateTime" Name="ModifiedDate">
              <Properties>
                <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
              </Properties>
              <Interpretation>
                <NormalizeDateTime LobDateTimeMode="UTC" />
              </Interpretation>
            </TypeDescriptor>
          </TypeDescriptors>
        </TypeDescriptor>
      </TypeDescriptors>
    </Parameter>
  </Parameters>
  <MethodInstances>
    <MethodInstance Type="Finder" ReturnParameterName="Customer" Default="true"
Name="CustomerQuery Item List" DefaultDisplayName="Customer">

```



```

    <AccessControlList>
      <AccessControlEntry Principal="domain\user_name">
        <Right BdcRight="Edit" />
        <Right BdcRight="Execute" />
        <Right BdcRight="SetPermissions" />
        <Right BdcRight="SelectableInClients" />
      </AccessControlEntry>
    </AccessControlList>
  </MethodInstance>
</MethodInstances>
</Method>
<Method Name="CustomerIdentifier Enumerator" DefaultDisplayName="Customer
Identifier Enumerator">
  <Properties>
    <Property Name="BackEndObject" Type="System.String">Customer</Property>
    <Property Name="BackEndObjectType"
Type="System.String">SqlServerTable</Property>
    <Property Name="RdbCommandText" Type="System.String">SELECT [CustomerID] ,
[TerritoryID] , [AccountNumber] , [CustomerType] , [rowguid] , [ModifiedDate] FROM
[AdventureWorks].[Sales].[Customer]</Property>
    <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">Text</Property>
    <Property Name="Schema" Type="System.String">Sales</Property>
  </Properties>
  <AccessControlList>
    <AccessControlEntry Principal="domain\user_name">
      <Right BdcRight="Edit" />
      <Right BdcRight="Execute" />
      <Right BdcRight="SetPermissions" />
      <Right BdcRight="SelectableInClients" />
    </AccessControlEntry>
  </AccessControlList>
  <Parameters>
    <Parameter Direction="Return" Name="Customer">
      <TypeDescriptor TypeName="System.Data.IDataReader, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" IsCollection="true"
Name="Customer">
        <TypeDescriptors>
          <TypeDescriptor TypeName="System.Data.IDataRecord, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089" Name="CustomerElement">
            <TypeDescriptors>
              <TypeDescriptor TypeName="System.Int32" ReadOnly="true"
IdentifierName="CustomerID" Name="CustomerID" />
              <TypeDescriptor TypeName="System.Nullable`1[[System.Int32,
mscorlib, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089]]"
Name="TerritoryID" />
              <TypeDescriptor TypeName="System.String" ReadOnly="true"
Name="AccountNumber">
                <Properties>
                  <Property Name="Size" Type="System.Int32">10</Property>
                </Properties>
              </TypeDescriptor>
              <TypeDescriptor TypeName="System.String" Name="CustomerType">
                <Properties>
                  <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
                  <Property Name="Size" Type="System.Int32">1</Property>
                </Properties>
              </TypeDescriptor>
              <TypeDescriptor TypeName="System.Guid" Name="rowguid">

```

```

        <Properties>
          <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
        </Properties>
      </TypeDescriptor>
    </TypeDescriptor>
    <TypeDescriptor TypeName="System.DateTime" Name="ModifiedDate">
      <Properties>
        <Property Name="RequiredInForms"
Type="System.Boolean">true</Property>
      </Properties>
      <Interpretation>
        <NormalizeDateTime LobDateTimeMode="UTC" />
      </Interpretation>
    </TypeDescriptor>
  </TypeDescriptors>
</TypeDescriptor>
</TypeDescriptors>
</TypeDescriptors>
</TypeDescriptor>
</Parameter>
</Parameters>
<MethodInstances>
  <MethodInstance Type="IdEnumerator" ReturnParameterName="Customer"
Default="true" Name="CustomerIdentifier Enumerator" DefaultDisplayName="Customer">
    <AccessControlList>
      <AccessControlEntry Principal="domain\user_name">
        <Right BdcRight="Edit" />
        <Right BdcRight="Execute" />
        <Right BdcRight="SetPermissions" />
        <Right BdcRight="SelectableInClients" />
      </AccessControlEntry>
    </AccessControlList>
  </MethodInstance>
</MethodInstances>
</Method>
</Methods>
</Entity>
</Entities>
</LobSystem>
</LobSystems>
</Model>

```

4 Security

4.1 Security Considerations for Implementers

Both ClickOnce extensions and the External List Information file are used to store or transmit well-formed, strongly typed tabular data. They do not introduce any security mechanisms, leaving those to the data store and communication transport where applicable.

4.2 Index of Security Parameters

None.

5 Appendix A: Full XML Schemas

For ease of implementation, this section provides the full **XML schemas** for the ClickOnceExtensions Structure and the EntityListInformation Structure, as specified in section 2.

5.1 ClickOnceExtensions Structure XSD

```
<xs:schema id="OBASolution" xmlns="" targetNamespace="urn:schemas-microsoft-com:oba.v1"
xmlns:obav1="urn:schemas-microsoft-com:oba.v1" xmlns:xs="http://www.w3.org/2001/XMLSchema"
attributeFormDefault="unqualified" elementFormDefault="qualified">
  <xs:element name="solution" type="obav1:SolutionType"/>
  <xs:complexType name="UpdateType">
    <xs:sequence>
      <xs:element name="expiration" type="obav1:ExpirationType" minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="AddInsType">
    <xs:sequence>
      <xs:element name="addin" type="obav1:AddinType" minOccurs="0" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <xs:simpleType name="IntervalUnit">
    <xs:restriction base="xs:string">
      <xs:enumeration value="days"/>
      <xs:enumeration value="hours"/>
      <xs:enumeration value="weeks"/>
    </xs:restriction>
  </xs:simpleType>
  <xs:complexType name="SolutionType">
    <xs:sequence>
      <xs:element name="addins" type="obav1:AddInsType" minOccurs="0" maxOccurs="1"/>
      <xs:element name="update" type="obav1:UpdateType" minOccurs="0" maxOccurs="1"/>
    </xs:sequence>
    <xs:attribute name="solutionId" type="xs:string" use="required"/>
    <xs:attribute name="isSimpleSolution" type="xs:string" use="optional"/>
    <xs:attribute name="isSolution" type="xs:string" use="optional"/>
    <xs:attribute name="isDataOnly" type="xs:string" use="optional"/>
  </xs:complexType>
  <xs:complexType name="ExpirationType">
    <xs:attribute name="maximumAge" type="xs:positiveInteger" default="7"/>
    <xs:attribute name="unit" type="obav1:IntervalUnit" default="days"/>
  </xs:complexType>
  <xs:complexType name="AddinType">
    <xs:attribute name="url" type="xs:string"/>
  </xs:complexType>
</xs:schema>
```

5.2 EntityListInformation Structure XSD

```
<xs:schema id="List"
targetNamespace="http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication"
xmlns:oba="http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication"
xmlns:mstns="http://schemas.microsoft.com/office/2006/03/OfficeBusinessApplication" xmlns=""
xmlns:xs="http://www.w3.org/2001/XMLSchema" attributeFormDefault="qualified"
elementFormDefault="qualified">
  <xs:element name="List" type="oba:ListType"/>
```

```

<xs:complexType name="ListType">
  <xs:sequence>
    <xs:element name="Entity" type="oba:EntityType" minOccurs="1" maxOccurs="1"/>
    <xs:element name="Views" type="oba:ViewsType" minOccurs="1" maxOccurs="1"/>
    <xs:element name="Form" type="oba:FormType" minOccurs="0" maxOccurs="1"/>
  </xs:sequence>
  <xs:attribute name="Title" form="unqualified" type="xs:string"/>
  <xs:attribute name="SiteId" form="unqualified" type="xs:string"/>
  <xs:attribute name="SiteTitle" form="unqualified" type="xs:string"/>
</xs:complexType>
<xs:complexType name="EntityType">
  <xs:attribute name="LobSystemInstance" form="unqualified" type="xs:string"/>
  <xs:attribute name="EntityNamespace" form="unqualified" type="xs:string"/>
  <xs:attribute name="EntityName" form="unqualified" type="xs:string"/>
  <xs:attribute name="SpecificFinder" form="unqualified" type="xs:string"/>
  <xs:attribute name="DefaultViewId" form="unqualified" type="xs:string"/>
</xs:complexType>
<xs:complexType name="ViewsType">
  <xs:sequence>
    <xs:element name="View" type="oba:ViewType" minOccurs="0" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="FormType">
  <xs:attribute name="CreateView" form="unqualified" type="xs:string"/>
  <xs:attribute name="DisplayView" form="unqualified" type="xs:string"/>
  <xs:attribute name="EditView" form="unqualified" type="xs:string"/>
</xs:complexType>
<xs:complexType name="ViewType">
  <xs:attribute name="Id" form="unqualified" type="xs:string"/>
  <xs:attribute name="DisplayName" form="unqualified" type="xs:string"/>
</xs:complexType>
</xs:schema>

```

6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Office 2010 suites
- Microsoft® SharePoint® Server 2010
- Microsoft® SharePoint® Workspace 2010
- Microsoft® Office 2013 Preview
- Microsoft® SharePoint® Server 2013 Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.4.1:](#) Office Professional Plus 2010 does not check for updates automatically.

[<2> Section 2.1.4.1:](#) Office Professional Plus 2010 does not check for updates automatically.

[<3> Section 2.1.4.1:](#) Office Professional Plus 2010 does not check for updates automatically.

[<4> Section 2.1.4.2:](#) Office Professional Plus 2010 does not check for updates automatically.

[<5> Section 2.1.4.2:](#) Office Professional Plus 2010 does not check for updates automatically.

[<6> Section 2.1.4.2:](#) Office Professional Plus 2010 does not check for updates automatically.

[<7> Section 2.1.4.4:](#) The ClickOnceExtensions generated by SharePoint Server 2010 Enterprise always include an empty **addins** element, but Office Professional Plus 2010 always ignores this element.

[<8> Section 2.1.4.4:](#) This attribute is included in the ClickOnceExtensions generated by SharePoint Server 2010 Enterprise and the value is always **true**, but Office Professional Plus 2010 ignores this attribute.

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

Preliminary

8 Index

A

[Applicability](#) 8

B

[BDC Model File example](#) 26

[Business Connectivity Services Application Manifest File example](#) 21

[Business Connectivity Services Deployment Manifest File example](#) 19

C

[Change tracking](#) 39

ClickOnceExtensions

[complex types](#) 10

[AddInsType](#) 12

[AddinType](#) 13

[ExpirationType](#) 13

[SolutionType](#) 12

UpdateType ([section 2.1.4.1](#) 10, [section 2.1.4.2](#) 11)

[global attributes](#) 10

[global elements](#) 10

[solution](#) 10

[namespaces](#) 10

[simple types](#) 14

[IntervalUnit](#) 14

[Common data types and fields](#) 9

Complex types

[AddInsType](#) 12

[AddinType](#) 13

[EntityType](#) 16

[ExpirationType](#) 13

[FormType](#) 17

[ListType](#) 15

[SolutionType](#) 12

UpdateType ([section 2.1.4.1](#) 10, [section 2.1.4.2](#) 11)

[ViewsType](#) 17

[ViewType](#) 18

D

[Data types and fields - common](#) 9

Details

[ClickOnceExtensions](#) 10

[common data types and fields](#) 9

[EntityListInformation](#) 15

E

[Entity List Information File example](#) 25

EntityListInformation

[complex types](#) 15

[EntityType](#) 16

[FormType](#) 17

[ListType](#) 15

[ViewsType](#) 17

[ViewType](#) 18

[global attributes](#) 15

[global elements](#) 15

[list](#) 15

[namespaces](#) 15

[overview](#) 7

[simple types](#) 18

[Examples](#) 19

[BDC Model File](#) 26

[Business Connectivity Services Application Manifest File](#) 21

[Business Connectivity Services Deployment Manifest File](#) 19

[Entity List Information File](#) 25

[External List View Schema File](#) 25

[External List View Schema File example](#) 25

F

[Fields - vendor-extensible](#) 8

[Full XML schema](#) 36

G

Global elements

[list](#) 15

[solution](#) 10

[Glossary](#) 6

I

[Implementer - security considerations](#) 35

[Index of security parameters](#) 35

[Informative references](#) 7

[Introduction](#) 6

L

[Localization](#) 8

N

Namespaces

[ClickOnceExtensions](#) 10

[EntityListInformation](#) 15

[Normative references](#) 7

O

[Overview \(synopsis\)](#) 7

P

[Parameters - security index](#) 35

[Product behavior](#) 38

R

[References](#) 7
 [informative](#) 7
 [normative](#) 7
[Relationship to protocols and other structures](#) 8

S

Security
 [implementer considerations](#) 35
 [parameter index](#) 35
Simple types
 [IntervalUnit](#) 14
Structures
 [overview](#) 9

T

[Tracking changes](#) 39

V

[Vendor-extensible fields](#) 8
[Versioning](#) 8

X

[XML schema](#) 36