

[MS-BDCMFFS]: Business Data Connectivity Model File Format

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final

documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
07/13/2009	0.1	Major	Initial Availability
08/28/2009	0.2	Editorial	Revised and edited the technical content
11/06/2009	0.3	Editorial	Revised and edited the technical content
02/19/2010	1.0	Major	Updated and revised the technical content
03/31/2010	1.01	Editorial	Revised and edited the technical content
04/30/2010	1.02	Editorial	Revised and edited the technical content
06/07/2010	1.03	Editorial	Revised and edited the technical content
06/29/2010	1.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.05	Minor	Clarified the meaning of the technical content.
09/27/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	1.05	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	1.6	Minor	Clarified the meaning of the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	8
1.2.1 Normative References	8
1.2.2 Informative References	9
1.3 Structure Overview (Synopsis)	9
1.4 Relationship to Protocols and Other Structures	9
1.5 Applicability Statement	9
1.6 Versioning and Localization	10
1.7 Vendor-Extensible Fields	10
2 Structures	11
2.1 Metadata Model	11
2.1.1 Namespaces	11
2.1.2 Global Elements	11
2.1.2.1 Model	11
2.1.3 Global Attributes	11
2.1.4 Complex Types	11
2.1.4.1 Model	11
2.1.4.2 LobSystems	13
2.1.4.3 MetadataObject	13
2.1.4.4 IndividuallySecurableMetadataObject	14
2.1.4.5 LocalizedDisplayNames	15
2.1.4.6 LocalizedDisplayName	15
2.1.4.7 LobSystem	16
2.1.4.8 LobSystemInstances	18
2.1.4.9 LobSystemInstance	19
2.1.4.10 Entities	20
2.1.4.11 Entity	20
2.1.4.12 AssociationGroups	22
2.1.4.13 AssociationGroup	23
2.1.4.14 AssociationReference	23
2.1.4.15 Identifiers	24
2.1.4.16 Identifier	25
2.1.4.17 Methods	26
2.1.4.18 Method	26
2.1.4.19 FilterDescriptors	28
2.1.4.20 FilterDescriptor	28
2.1.4.21 MethodInstances	29
2.1.4.22 MethodInstance	30
2.1.4.23 Parameters	32
2.1.4.24 Parameter	32
2.1.4.25 TypeDescriptor	33
2.1.4.26 DefaultValues	37
2.1.4.27 DefaultValue	38
2.1.4.28 Interpretation	38
2.1.4.29 ConvertType	39
2.1.4.30 NormalizeString	40
2.1.4.31 NormalizeDateTime	40
2.1.4.32 TypeDescriptors	41

2.1.4.33	Actions	41
2.1.4.34	Action.....	42
2.1.4.35	ActionParameters.....	44
2.1.4.36	ActionParameter	44
2.1.4.37	Association.....	45
2.1.4.38	SourceEntity	47
2.1.4.39	DestinationEntity	48
2.1.4.40	Property	48
2.1.4.41	Properties	49
2.1.4.42	AccessControlList	49
2.1.4.43	AccessControlEntry	50
2.1.4.44	Right.....	51
2.1.5	Simple Types	51
2.1.5.1	LobSystemType.....	51
2.1.5.2	OperationModeType	52
2.1.5.3	IdentifierType	53
2.1.5.4	FilterDescriptorType.....	54
2.1.5.5	TypeDescriptorPathString	56
2.1.5.6	MethodInstanceType	56
2.1.5.7	ParameterDirection	57
2.1.5.8	StringNormalizeMode	58
2.1.5.9	LobDateTimeMode	58
2.1.5.10	Ordinal	59
2.1.5.11	InstanceCount	59
2.1.5.12	ReturnTypeDescriptorLevel	60
2.1.5.13	ActionPosition.....	60
2.1.5.14	BdcRightName.....	60
2.1.5.15	NameString.....	61
2.1.5.16	TypeDescriptorTypeNameString.....	62
2.1.5.17	TypeNameString	63
2.1.5.18	UrlString.....	64
2.1.5.19	VersionString	64
2.2	Metadata Model Resources.....	65
2.2.1	Namespaces	65
2.2.2	Global Elements	65
2.2.2.1	Model.....	65
2.2.3	Global Attributes	65
2.2.4	Complex Types	66
2.2.4.1	Model.....	66
2.2.4.2	LobSystems	66
2.2.4.3	MetadataObject	67
2.2.4.4	IndividuallySecurableMetadataObject	68
2.2.4.5	LocalizedDisplayNames.....	68
2.2.4.6	LocalizedDisplayName	69
2.2.4.7	LobSystem.....	69
2.2.4.8	LobSystemInstances	70
2.2.4.9	LobSystemInstance.....	71
2.2.4.10	Entities	71
2.2.4.11	Entity	72
2.2.4.12	AssociationGroups.....	73
2.2.4.13	AssociationGroup	74
2.2.4.14	Identifiers	74
2.2.4.15	Identifier	75

2.2.4.16	Methods	75
2.2.4.17	Method	76
2.2.4.18	FilterDescriptors	77
2.2.4.19	FilterDescriptor	77
2.2.4.20	MethodInstances	78
2.2.4.21	MethodInstance	78
2.2.4.22	Parameters	79
2.2.4.23	Parameter	79
2.2.4.24	TypeDescriptor	80
2.2.4.25	TypeDescriptors	81
2.2.4.26	Actions	81
2.2.4.27	Action	82
2.2.4.28	ActionParameters	82
2.2.4.29	ActionParameter	83
2.2.4.30	Association	83
2.2.4.31	Property	84
2.2.4.32	Properties	84
2.2.4.33	AccessControlList	85
2.2.4.34	AccessControlEntry	85
2.2.4.35	Right	86
2.2.5	Simple Types	87
2.2.5.1	BdcRightName	87
2.2.5.2	NameString	88
2.2.5.3	TypeNameString	88
2.2.5.4	VersionString	89
3	Structure Examples	90
3.1	Database Model	90
3.2	DotNetAssembly Model	92
3.3	Web Service Model	93
3.4	Model Resources	94
3.5	Finders	95
3.6	CRUD	97
3.7	Associations	101
4	Security Considerations	104
5	Appendix A: Full XML Schemas	105
5.1	http://schemas.microsoft.com/windows/2007/BusinessDataCatalog	105
5.2	http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources	115
6	Appendix B: Product Behavior	122
7	Change Tracking	125
8	Index	144

1 Introduction

The Business Data Connectivity Model File Format Specification specifies two XML structures. The first, known as Metadata Model, is an XML structure used to describe the API of one or more line-of-business (LOB) systems and how that interface can be mapped to a well-defined interface of canonical operations. This structure is typically consumed by a runtime engine that translates canonical interface operation execution requests into the native LOB system's interface operation execution requests. The second XML structure, known as Metadata Model Resources, is used to describe permissions, localized names and additional information about utilizing the LOB system. The Metadata Model Resources structure is a subset of the Metadata Model structure.

Sections 1.7 and 2 of this specification are normative and contain RFC 2119 language. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

- access control entry (ACE)**
- access control list (ACL)**
- Augmented Backus-Naur Form (ABNF)**
- Coordinated Universal Time (UTC)**
- domain account**
- domain name**
- GUID**
- language code identifier (LCID)**
- Unicode**
- XML**

The following terms are defined in [\[MS-OFCGLOS\]](#):

- AccessChecker**
- Action**
- ActionParameter**
- ActivityTrackingFilter**
- Association**
- AssociationGroup**
- AssociationNavigator**
- AssociationReference**
- Associator**
- base64 encoding**
- BatchingPositionFilter**
- BatchingTerminationFilter**
- BinarySecurityDescriptorAccessor**
- bind**
- BulkAssociatedIdEnumerator**
- BulkAssociationNavigator**
- BulkIdEnumerator**
- BulkSpecificFinder**
- Business Logic Module**
- ChangedIdEnumerator**
- claim value**
- ComparisonFilter**
- Creator**
- DefaultValue**

DeletedIdEnumerator
Deleter
Disassociator
display name
endpoint
Entity
EntityInstance
field
filter
FilterDescriptor
Finder
GenericInvoker
Identifier
IdEnumerator
InputFilter
InputOutputFilter
LastIdFilter
LimitFilter
line-of-business (LOB) system
LobSystem
LobSystemInstance
locale
localized name
MetadataModel
MetadataObject
Method
MethodInstance
Model
OutputFilter
PageNumberFilter
Parameter
PasswordCredentialFilter
Property
ReturnTypeDescriptor
rights
root TypeDescriptor
Scalar
security principal
SpecificFinder
SsoTicketFilter
StreamAccessor
time zone
TimeStampFilter
TypeDescriptor
Uniform Resource Identifier (URI)
Uniform Resource Locator (URL)
Updater
UserContextFilter
UserCultureFilter
UsernameCredentialFilter
UserProfileFilter
View
Web service
WildcardFilter
XML namespace

XML namespace prefix
XML schema
XML schema definition (XSD)

The following terms are specific to this document:

Open Data Protocol (OData): A web protocol for querying and updating data specified in [MS-ODATA].

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[ECMA-335] ECMA International, "Common Language Infrastructure (CLI) Partitions I to VI", ECMA-335, June 2006, <http://www.ecma-international.org/publications/standards/Ecma-335.htm>

[MS-NRTP] Microsoft Corporation, "[.NET Remoting: Core Protocol Specification](#)".

[MS-SPSTWS] Microsoft Corporation, "[SharePoint Security Token Service Web Service Protocol Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", RFC 4648, October 2006, <http://www.ietf.org/rfc/rfc4648.txt>

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA1] Thompson, H.S., Ed., Beech, D., Ed., Maloney, M., Ed., and Mendelsohn, N., Ed., "XML Schema Part 1: Structures", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-1-20010502/>

[XMLSCHEMA2] Biron, P.V., Ed. and Malhotra, A., Ed., "XML Schema Part 2: Datatypes", W3C Recommendation, May 2001, <http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/>

1.2.2 Informative References

[CompositeFormatting] Microsoft Corporation, "Composite Formatting", .NET Framework Developer's Guide, <http://msdn.microsoft.com/en-us/library/txafckwd.aspx>

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

1.3 Structure Overview (Synopsis)

Enterprises have a variety of data stored in various **line-of-business (LOB) systems**. Typically, this data is accessible only through the proprietary programming interface of these software systems. It is desirable to be able to provide access to such data via a set of normalized interfaces so that users do not have to use system-specific or adapter-specific programming patterns for each system.

To facilitate this, it is possible to devise descriptions of the programmatic interface of the LOB systems using data structures such as **Methods**, **Parameters**, and **TypeDescriptors**, along with information about the LOB systems themselves (such as the server name, connection string and how to authenticate), using data structures such as **LobSystem** and **LobSystemInstance**. **Methods** can be considered to live within an **Entity** abstraction, representing a business data type, such as "customer" or "order". The LOB system interface definitions can then be transformed into normalized, stereotypical operations against **Entities** such as "Read-An-Entity-Instance-By-Id", "Read-Entity-Instances", and "Check-Entity-Instance-Permissions" by annotating the actual LOB system interface descriptions, with the annotations described by data structures such as **MethodInstance**, **Identifier**, **FilterDescriptor**, and **Association**. These data structures, collectively called **MetadataObjects**, can be grouped into related collections called **MetadataModels** that describe LOB systems. Once a store of **MetadataModels** is made available, it can be utilized by a runtime engine to convert a stereotypical, normalized operation requested by an application reading this structure into a LOB system-specific invocation programmatically.

This document specifies Metadata Model, an **XML** structure that represents a serialized **MetadataModel**. Consumers of this structure are typically runtime engines that transform client requests in normalized, stereotypical form into actual LOB system interface calls. Producers of this structure are typically **MetadataModel** design tools.

This document also specifies Metadata Model Resources, an XML structure that represents permissions, localized names, and other non-structural information of a **MetadataModel**. The Metadata Model Resources structure is a subset of the Metadata Model structure. Consumers of this structure are typically metadata stores that merge the information in the structure to the corresponding **MetadataModel** already present in the metadata store. Producers of this structure are typically localization and access control tools.

1.4 Relationship to Protocols and Other Structures

This file format is an **XML schema definition (XSD)** file, as described in [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#).

1.5 Applicability Statement

There are typically two types of applications that can use this file format, though an application that combines these functions in a single implementation is also feasible:

- MetadataModel designers, whose primary purpose is to create or edit a **MetadataModel**. These applications typically offer some graphical design surface and connectivity to LOB systems of

known types to enable mining of the LOB system public interface definition and creation of corresponding **MetadataModel**.

- **MetadataModel** consumers, whose primary purpose is to read the **MetadataModel** file and use the information therein to convert uniform, stereotypical operations into LOB system-specific interface invocations.

This file format specification does not specify how the **MetadataObjects** can be used to do the conversion from a stereotypical client request into a system-specific invocation; it merely defines a serialized representation of **MetadataObjects**.

1.6 Versioning and Localization

This document covers versioning issues in the following areas:

- **Structure versions:** This structure specifies the only version of this file format.
- **Localization:** This structure specifies no locale-specific processes or data.

1.7 Vendor-Extensible Fields

This file format defines vendor-extensible fields in the **Properties** element described in section [2.2.4.32](#).

2 Structures

The Metadata Model structure specifies an XML structure used to define a MetadataModel and all its MetadataObjects.

The Metadata Model Resources structure specifies an XML structure used to define **Properties**, **access control lists (ACLs)**, and **localized names** to be used with previously defined **MetadataObjects**.

2.1 Metadata Model

2.1.1 Namespaces

This specification defines and references various **XML namespaces** using the mechanisms specified in [\[XMLNS\]](#). Although this specification associates a specific **XML namespace prefix** for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]
bdc	http://schemas.microsoft.com/windows/2007/BusinessDataCatalog	

2.1.2 Global Elements

2.1.2.1 Model

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

A **Model** (section [2.1.4.1](#)) element that specifies a **Model**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this element.

```
<xs:element name="Model" type="bdc:Model"/>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.3 Global Attributes

None.

2.1.4 Complex Types

The definitions of some complex types in this section make use of **Augmented Backus-Naur Form (ABNF)** representation, as specified in [\[RFC5234\]](#).

2.1.4.1 Model

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Model](#)

A complex type that specifies a Model. **Models** refer to Entities. This complex type contains the **LobSystems** element (section [2.1.4.2](#)) that specifies the LobSystems containing the **Entities** the **Model** refers to.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

LobSystems: An **LobSystems** element (section [2.2.4.2](#)) that specifies the **LobSystems** that contain the **Entities** to which the **Model** refers.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default **display name** of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<1>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Model">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="LobSystems" type="bdc:LobSystems" minOccurs="0"
maxOccurs="1">
          <xs:unique name="LobSystemNameKey">
            <xs:selector xpath="*/">
              <xs:field xpath="@Name"/>
            </xs:unique>
          </xs:element>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.2 LobSystems

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Model](#)

A complex type that specifies a list of LobSystems of a Model.

Child Elements:

LobSystem: An **LobSystem** element (section [2.2.4.7](#)) that specifies a **LobSystem**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LobSystems">
  <xs:sequence>
    <xs:element name="LobSystem" type="bdc:LobSystem" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.3 MetadataObject

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [LobSystemInstance](#), [Identifier](#), [FilterDescriptor](#), [TypeDescriptor](#), [Parameter](#), [IndividuallySecurableMetadataObject](#), [AssociationGroup](#), [ActionParameter](#), [Action](#)

A complex type that specifies a MetadataObject.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<2>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="MetadataObject" abstract="true">
  <xs:sequence>
    <xs:element name="LocalizedDisplayNames" type="bcd:LocalizedDisplayNames"
minOccurs="0" maxOccurs="1">
      <xs:unique name="LocalizedDisplayNameLCIDKey">
        <xs:selector xpath="*/>
        <xs:field xpath="@LCID"/>
      </xs:unique>
    </xs:element>
    <xs:element name="Properties" type="bcd:Properties" minOccurs="0"
maxOccurs="1">
      <xs:unique name="PropertyNameKey">
        <xs:selector xpath="*/>
        <xs:field xpath="@Name"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="Name" type="bcd:NameString" use="required"/>
  <xs:attribute name="DefaultDisplayName" type="bcd:NameString"/>
  <xs:attribute name="IsCached" type="xs:boolean" default="true"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.4 IndividuallySecurableMetadataObject

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [MethodInstance](#), [Method](#), [Entity](#), [LobSystem](#), [Model](#)

A complex type that specifies a MetadataObject that can be assigned a specific access control list (ACL).

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [≤3>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="IndividuallySecurableMetadataObject" abstract="true">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>
        <xs:element name="AccessControlList" type="bdc:AccessControlList"
minOccurs="0" maxOccurs="1"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.5 LocalizedDisplayNames

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Model](#), [LobSystem](#), [LobSystemInstance](#), [MetadataObject](#), [Entity](#), [Identifier](#), [Method](#), [FilterDescriptor](#), [Parameter](#), [TypeDescriptor](#), [Association](#), [MethodInstance](#), [IndividuallySecurableMetadataObject](#), [AssociationGroup](#), [Action](#), [ActionParameter](#)

A complex type that specifies a list of localized names of a MetadataObject.

Child Elements:

LocalizedDisplayName: A **LocalizedDisplayName** element (section [2.2.4.6](#)) that specifies a localized name.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LocalizedDisplayNames">
  <xs:sequence>
    <xs:element name="LocalizedDisplayName" type="bdc:LocalizedDisplayName"
minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.6 LocalizedDisplayName

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [LocalizedDisplayNames](#)

A complex type that specifies a localized name. The text associated with this element is the localized name associated with the specified **language code identifier (LCID)**.

Attributes:

LCID: An **xs:integer** attribute that specifies the LCID.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LocalizedDisplayName" mixed="true">
  <xs:attribute name="LCID" type="xs:integer" use="required"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.7 LobSystem

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [LobSystems](#)

A complex type that specifies an LobSystem.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Proxy: An **xs:string** element that specifies the **base64 encoding** representation specified in [\[RFC4648\]](#) of the information about **Business Logic Modules** associated with the **LobSystem** containing this element. The information contained in this element **MUST** be in the format specified by the following ABNF, as specified by [\[RFC5234\]](#):

```
Information = HashLength Hash Modules
HashLength = HashLength1 HashLength2
HashLength1 = OCTET
HashLength2 = OCTET
Hash = WebServiceHash / WcfHash / DotNetHash / CustomHash
WebServiceHash = *OCTET
WcfHash = *OCTET
DotNetHash = 4*4%x00
CustomHash = *OCTET
Modules = WebServiceModule / WcfModule / DotNetModule / CustomModule
```



```
WebServiceModule = Assembly
WcfModule = Assembly
DotNetModule= 1*(Size Assembly)
Size = Size1 Size2 Size3 Size4
Size1 = OCTET
Size2 = OCTET
Size3 = OCTET
Size4 = OCTET
Assembly = *OCTET
CustomModule = *OCTET
```

HashLength1, HashLength2: represent the length of the **Hash**. The length of the **Hash** MUST be $\text{HashLength1} + 256 * \text{HashLength2}$.

Size1, Size2, Size3, Size4: represent the length of the **Assembly**. The length of the **Assembly** MUST be $((((\text{Size4} * 256) + \text{Size3}) * 256) + \text{Size2}) * 256 + \text{Size1}$.

Assembly: The bytes of a Business Logic Module. [<5>](#)

WebServiceHash: An implementation-specific identifier of the Business Logic Module [<6>](#) represented by the **WebServiceModule**. **Hash** MUST be "WebServiceHash" when the **Type** attribute of the **LobSystem** is "WebService".

WcfHash: An implementation-specific identifier of the Business Logic Module [<7>](#) represented by the **WcfModule**. **Hash** MUST be "WcfHash" when the **Type** attribute of the **LobSystem** is "Wcf".

DotNetHash: **Hash** MUST be "DotNetHashHash" when the **Type** attribute of the **LobSystem** is "DotNetAssembly".

CustomHash: An implementation-specific identifier of the Business Logic Module [<8>](#) represented by the **CustomModule**. **Hash** MUST be "CustomHash" when the **Type** attribute of the **LobSystem** is "Custom".

WebServiceModule: Modules MUST be **WebServiceModule** when the **Type** attribute of the **LobSystem** is "WebService"

WcfModule: Modules MUST be **WcfModule** when the **Type** attribute of the **LobSystem** is "Wcf"

DotNetModule: Modules MUST be **DotNetModule** when the **Type** attribute of the **LobSystem** is "DotNetAssembly"

CustomModule: An implementation-specific collection of Business Logic Modules. [<9>](#) Modules MUST be **CustomModule** when the **Type** attribute of the **LobSystem** is "Custom"

LobSystemInstances: An **LobSystemInstances** element (section [2.2.4.8](#)) that specifies a list of **LobSystemInstances** of the **LobSystem**.

Entities: An **Entities** element (section [2.2.4.10](#)) that specifies a list of **Entities** of the **LobSystem**.

Attributes:

Type: An **LobSystemType** attribute (section [2.1.5.1](#)) that specifies the type of the **LobSystem**.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<10>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LobSystem">
  <xs:complexContent>
    <xs:extension base="bcd:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="Proxy" type="xs:string" minOccurs="0" maxOccurs="1"/>
        <xs:element name="LobSystemInstances" type="bcd:LobSystemInstances"
minOccurs="0" maxOccurs="1">
          <xs:unique name="LobSystemInstanceNameKey">
            <xs:selector xpath="*/"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="Entities" type="bcd:Entities" minOccurs="0"
maxOccurs="1">
          <xs:unique name="EntityNameNamespaceVersionKey">
            <xs:selector xpath="*/"/>
            <xs:field xpath="@Name"/>
            <xs:field xpath="@Namespace"/>
            <xs:field xpath="@Version"/>
          </xs:unique>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="Type" type="bcd:LobSystemType" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.8 LobSystemInstances

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [LobSystem](#)

A complex type that specifies a list of LobSystemInstances of an LobSystem.

Child Elements:

LobSystemInstance: An **LobSystemInstance** element (section [2.2.4.9](#)) that specifies a LobSystemInstance.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LobSystemInstances">
  <xs:sequence>
    <xs:element name="LobSystemInstance" type="bcd:LobSystemInstance" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.9 LobSystemInstance

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [LobSystemInstances](#)

A complex type that specifies a LobSystemInstance of a LobSystem.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<11>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LobSystemInstance">
  <xs:complexContent>
```

```
<xs:extension base="bdc:MetadataObject"/>
</xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.10 Entities

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [LobSystem](#)

A complex type that specifies a list of Entities of a LobSystem.

Child Elements:

Entity: An **Entity** element (section [2.1.4.11](#)) that specifies an **Entity**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Entities">
  <xs:sequence>
    <xs:element name="Entity" type="bdc:Entity" minOccurs="1"
maxOccurs="unbounded">
      <xs:unique name="MethodNameKey">
        <xs:selector xpath="//bdc:MethodInstances/*"/>
        <xs:field xpath="@Name"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.11 Entity

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entities](#)

A complex type that specifies an Entity.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Identifiers: An **Identifiers** element (section [2.1.4.15](#)) that specifies the Identifiers of the **Entity**.

Methods: A **Methods** element (section [2.1.4.17](#)) that specifies the Methods of the **Entity**.

AssociationGroups: An **AssociationGroups** element (section [2.1.4.12](#)) that specifies the **AssociationGroups** of the **Entity**.

Actions: An **Actions** element (section [2.1.4.33](#)) that specifies the **Actions** of the **Entity**.

Attributes:

Namespace: A **NameString** attribute (section [2.2.5.2](#)) that specifies the namespace of the **Entity**.

Version: A **VersionString** attribute (section [2.2.5.4](#)) that specifies the version number of the **Entity**.

EstimatedInstanceCount: An **InstanceCount** attribute (section [2.1.5.11](#)) that specifies the estimated number of **EntityInstances** contained by the line-of-business (LOB) system.

DefaultOperationMode: An **OperationModeType** attribute (section [2.1.5.2](#)) that specifies the default behavior when interacting with a LOB system in an implementation-specific manner while creating, deleting, updating or reading EntityInstance data of the **Entity**.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<12>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Entity">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="Identifiers" type="bdc:Identifiers" minOccurs="0">
          <xs:unique name="IdentifierNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
          </xs:unique>
        </xs:element>
        <xs:element name="Methods" type="bdc:Methods" minOccurs="0">
          <xs:unique name="MethodNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
          </xs:unique>
        </xs:element>
        <xs:element name="AssociationGroups" type="bdc:AssociationGroups"
          minOccurs="0">
```

```

        <xs:unique name="AssociationGroupNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
        </xs:unique>
    </xs:element>
    <xs:element name="Actions" type="bdc:Actions" minOccurs="0">
        <xs:unique name="ActionNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
        </xs:unique>
    </xs:element>
</xs:sequence>
<xs:attribute name="Namespace" type="bdc:NameString" use="required" />
<xs:attribute name="Version" type="bdc:VersionString" use="required" />
<xs:attribute name="EstimatedInstanceCount" type="bdc:InstanceCount"
default="10000" />
<xs:attribute name="DefaultOperationMode" type="bdc:OperationModeType"
default="Default" use="optional" />
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.12 AssociationGroups

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entity](#)

A complex type that specifies a list of AssociationGroups of an Entity.

Child Elements:

AssociationGroup: An **AssociationGroup** element (section [2.1.4.13](#)) that specifies an **AssociationGroup**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="AssociationGroups">
    <xs:sequence>
        <xs:element name="AssociationGroup" type="bdc:AssociationGroup" minOccurs="1"
maxOccurs="unbounded">
            <xs:unique
name="AssociationReferenceAssociationNameEntityNameEntityNamespaceKey">
                <xs:selector xpath="*" />
                <xs:field xpath="@EntityNamespace" />
                <xs:field xpath="@EntityName" />
                <xs:field xpath="@AssociationName" />
            </xs:unique>
        </xs:element>
    </xs:sequence>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.13 AssociationGroup

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [AssociationGroups](#)

A complex type that specifies an AssociationGroup.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AssociationReference: An **AssociationReference** element (section [2.1.4.14](#)) that specifies an **AssociationReference** of the **AssociationGroup**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<13>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AssociationGroup">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>
        <xs:element name="AssociationReference" type="bdc:AssociationReference"
minOccurs="1" maxOccurs="unbounded"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.14 AssociationReference

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [AssociationGroup](#)

A complex type that specifies an AssociationReference in an AssociationGroup.
AssociationReferences refer to Associations.

Attributes:

EntityNamespace: A **NameString** attribute (section [2.2.5.2](#)) that specifies the namespace of the Entity where the referenced **Association** is defined.

EntityName: A **NameString** attribute that specifies the name of the **Entity** where the referenced **Association** is defined.

AssociationName: A **NameString** attribute that specifies the name of the referenced **Association**.

Reverse: An **xs:boolean** attribute that specifies whether the source of the referenced **Association** is the destination of the containing **AssociationGroup** and the destination of the referenced **Association** is the source of the containing **AssociationGroup**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The sources of the referenced Association are the sources of the containing AssociationGroup and the destination of the referenced Association is the destination of the containing AssociationGroup .
True	The source of the referenced Association is the destination of the containing AssociationGroup and destination of the referenced Association is the source of the containing AssociationGroup . The referenced Association MUST have only one source.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AssociationReference">  
  <xs:attribute name="EntityNamespace" type="bcd:NameString" use="optional"/>  
  <xs:attribute name="EntityName" type="bcd:NameString" use="optional"/>  
  <xs:attribute name="AssociationName" type="bcd:NameString" use="required"/>  
  <xs:attribute name="Reverse" type="xs:boolean" use="optional" default="false"/>  
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.15 Identifiers

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entity](#)

A complex type that specifies a list of Identifiers of an Entity.

Child Elements:

Identifier: An **Identifier** element (section [2.1.4.16](#)) that specifies an **Identifier**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.


```

<xs:complexType name="Identifiers">
  <xs:sequence>
    <xs:element name="Identifier" type="bdc:Identifier" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.16 Identifier

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Identifiers](#)

A complex type that specifies an Identifier.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

TypeName: An **IdentifierType** attribute (section [2.1.5.3](#)) that specifies the data type of the value corresponding to the **Identifier**.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [≤14>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="Identifier">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:attribute name="TypeName" type="bdc:IdentifierType" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.17 Methods

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entity](#)

A complex type that specifies a list of Methods of an Entity.

Child Elements:

Method: A **Method** element (section [2.1.4.18](#)) that specifies a **Method**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Methods">
  <xs:sequence>
    <xs:element name="Method" type="bdc:Method" minOccurs="1"
maxOccurs="unbounded">
      <xs:key name="ParameterNameKey">
        <xs:selector xpath="//bdc:Parameter"/>
        <xs:field xpath="@Name"/>
      </xs:key>
      <xs:keyref name="ParameterNameRef" refer="bdc:ParameterNameKey">
        <xs:selector xpath="//bdc:MethodInstances/*"/>
        <xs:field xpath="@ReturnParameterName"/>
      </xs:keyref>
      <xs:key name="MethodMethodNameKey">
        <xs:selector xpath="//bdc:MethodInstances/*"/>
        <xs:field xpath="@Name"/>
      </xs:key>
      <xs:keyref name="DefaultValueMethodNameRef"
refer="bdc:MethodMethodNameKey">
        <xs:selector xpath="//bdc:DefaultValue"/>
        <xs:field xpath="@MethodName"/>
      </xs:keyref>
    </xs:element>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.18 Method

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Methods](#)

A complex type that specifies a Method.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

FilterDescriptors: A **FilterDescriptors** element (section [2.1.4.19](#)) that specifies the FilterDescriptors of the **Method**.

Parameters: A **Parameters** element (section [2.1.4.23](#)) that specifies the Parameters of the **Method**. A **Method** MUST NOT have more than one **Parameter** that has the value of the **Direction** attribute equal to "Return".

MethodInstances: A **MethodInstances** element (section [2.1.4.21](#)) that specifies the MethodInstances of the **Method**.

Attributes:

IsStatic: An **xs:boolean** attribute that specifies whether an implementation-specific execution of the **Method** requires an **EntityInstance** to serve as the context for execution. [15](#) The value MUST be in the following table:

Value	Description
False	The Method represents an instance Method and requires an EntityInstance to provide the context for execution.
True	The Method represents a static Method and does not require a specific EntityInstance to provide context for execution.

LobName: A **NameString** attribute (section [2.2.5.2](#)) that specifies the name of the operation defined in the line-of-business (LOB) system that is represented by this **Method**. For example, an operation in an LOB system named "CN1A" can be represented by a **Method** with **Name** attribute equal to "GetCustomerByName". The **LobName** attribute of this **Method** can [16](#) be "CN1A".

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [17](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Method">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
```

```

    <xs:sequence>
      <xs:element name="FilterDescriptors" type="bdc:FilterDescriptors"
minOccurs="0" maxOccurs="1">
        <xs:unique name="FilterDescriptorNameKey">
          <xs:selector xpath="*" />
          <xs:field xpath="@Name" />
        </xs:unique>
      </xs:element>
      <xs:element name="Parameters" type="bdc:Parameters" minOccurs="0"
maxOccurs="1" />
      <xs:element name="MethodInstances" type="bdc:MethodInstances" minOccurs="0"
maxOccurs="1" />
    </xs:sequence>
    <xs:attribute name="IsStatic" type="xs:boolean" default="true" />
    <xs:attribute name="JobName" type="bdc:NameString" use="optional" />
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.19 FilterDescriptors

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Method](#)

A complex type that specifies a list of FilterDescriptors of a Method.

Child Elements:

FilterDescriptor: A **FilterDescriptor** element (section [2.2.4.19](#)) that specifies a **FilterDescriptor**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="FilterDescriptors">
  <xs:sequence>
    <xs:element name="FilterDescriptor" type="bdc:FilterDescriptor" minOccurs="1"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.20 FilterDescriptor

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [FilterDescriptors](#)

A complex type that specifies a FilterDescriptor.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Type: A **FilterDescriptorType** attribute (section [2.1.5.4](#)) that specifies the type of the **FilterDescriptor**.

FilterField: A **NameString** attribute (section [2.2.5.2](#)) that specifies the **field (4)** of an Entity to which the **Filter** is applied in an implementation-specific execution that uses the metadata.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<18>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="FilterDescriptor">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:attribute name="Type" type="bdc:FilterDescriptorType" use="required"/>
      <xs:attribute name="FilterField" type="bdc:NameString" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.21 MethodInstances

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Method](#)

A complex type that specifies a list of MethodInstances of a Method.

Child Elements:

Association: An **Association** element (section [2.1.4.37](#)) that specifies an Association.

MethodInstance: A **MethodInstance** element (section [2.1.4.22](#)) that specifies a **MethodInstance**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="MethodInstances">
  <xs:choice minOccurs="1" maxOccurs="unbounded">
    <xs:element name="Association" type="bdc:Association">
      <xs:unique name="SourceEntityNameNamespaceKey">
        <xs:selector xpath="bdc:SourceEntity"/>
        <xs:field xpath="@Name"/>
        <xs:field xpath="@Namespace"/>
      </xs:unique>
    </xs:element>
    <xs:element name="MethodInstance" type="bdc:MethodInstance"/>
  </xs:choice>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.22 MethodInstance

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Association](#), [MethodInstances](#)

A complex type that specifies a MethodInstance.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Attributes:

Type: A **MethodInstanceType** attribute (section [2.1.5.6](#)) that specifies the type of the **MethodInstance**.

Default: An **xs:boolean** attribute that specifies whether the **MethodInstance** is the default among all **MethodInstances** sharing its type within the containing Entity. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The MethodInstance is not the default among all MethodInstances sharing its type within the containing Entity .
True	The MethodInstance is the default among all MethodInstances sharing its type within the containing Entity .

ReturnParameterName: A **NameString** attribute (section [2.2.5.2](#)) that specifies the name of the Parameter that contains the **ReturnTypeDescriptor** of the **MethodInstance**. The **Direction** attribute of the Parameter MUST have a value of either "Out", "InOut" or "Return".

This attribute MUST be specified for all types of **MethodInstances** except **GenericInvoker**, **Deleter**, and **Updater**.

ReturnTypeDescriptorName: A **NameString** attribute that specifies the name of the **ReturnTypeDescriptor** of the **MethodInstance**. The **Parameter** specified by the **ReturnParameterName** attribute MUST contain the **ReturnTypeDescriptor**. This attribute MUST be ignored when **ReturnTypeDescriptorPath** attribute is specified. This attribute SHOULD NOT [<19>](#) be used.

When this attribute is missing, and the **ReturnTypeDescriptorPath** attribute is not specified, the application utilizing the structure MUST assume the name of the **ReturnTypeDescriptor** to be the name of the **root TypeDescriptor** of the **Parameter** specified by the **ReturnParameterName** attribute.

ReturnTypeDescriptorLevel: A **ReturnTypeDescriptorLevel** attribute (section [2.1.5.12](#)) that specifies the depth from the root of the **ReturnTypeDescriptor** of the **MethodInstance**, in the tree of nested **TypeDescriptors** where the root level equals 0. This attribute MUST be ignored. This attribute SHOULD NOT [<20>](#) be used.

ReturnTypeDescriptorPath: A **TypeDescriptorPathString** attribute (section [2.1.5.5](#)) that specifies the path [<21>](#) to the return value of the **MethodInstance**.

When this attribute is missing, and the **ReturnTypeDescriptorName** attribute is not specified, the application utilizing the structure MUST assume the name of the **ReturnTypeDescriptor** to be the name of the **root TypeDescriptor** of the **Parameter** specified by the **ReturnParameterName** attribute.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<22>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="MethodInstance">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:attribute name="Type" type="bdc:MethodInstanceType" use="required"/>
      <xs:attribute name="Default" type="xs:boolean" use="optional"
default="false"/>
      <xs:attribute name="ReturnParameterName" type="bdc:NameString"
use="optional"/>
      <xs:attribute name="ReturnTypeDescriptorName" type="bdc:NameString"
use="optional"/>
      <xs:attribute name="ReturnTypeDescriptorLevel"
type="bdc:ReturnTypeDescriptorLevel" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

```

        <xs:attribute name="ReturnTypeDescriptorPath" type="xs:string"
use="optional"/>
    </xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.23 Parameters

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Method](#)

A complex type that specifies a list of Parameters of a Method.

Child Elements:

Parameter: A **Parameter** element (section [2.1.4.24](#)) that specifies a **Parameter**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="Parameters">
  <xs:sequence>
    <xs:element name="Parameter" type="bdc:Parameter" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.24 Parameter

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Parameters](#)

A complex type that specifies a Parameter.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

TypeDescriptor: A **TypeDescriptor** element (section [2.1.4.25](#)) that specifies the root TypeDescriptor of the **Parameter**.

Attributes:

Direction: A **ParameterDirection** attribute (section [2.1.5.7](#)) that specifies the direction of the **Parameter**.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [<23>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Parameter">
  <xs:complexContent>
    <xs:extension base="bcd:MetadataObject">
      <xs:sequence>
        <xs:element name="TypeDescriptor" type="bcd:TypeDescriptor"/>
      </xs:sequence>
      <xs:attribute name="Direction" type="bcd:ParameterDirection" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.25 TypeDescriptor

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Parameter](#), [TypeDescriptors](#)

A complex type that specifies a **TypeDescriptor**.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Interpretation: An **Interpretation** element (section [2.1.4.28](#)) that specifies rules for the data stored by the data structure represented by the **TypeDescriptor**.

DefaultValues: A **DefaultValues** element (section [2.1.4.26](#)) that specifies the **DefaultValues** of the **TypeDescriptor**.

TypeDescriptors: A **TypeDescriptors** element (section [2.1.4.32](#)) that specifies the child **TypeDescriptors** of the **TypeDescriptor**.

Attributes:

TypeName: A **TypeDescriptorTypeNameString** attribute (section [2.1.5.16](#)) that specifies the implementation-specific identifier of the data type of the data structure that is represented by the **TypeDescriptor**.

LobName: A **NameString** attribute (section [2.2.5.2](#)) that specifies the name of the data structure that is represented by the **TypeDescriptor**. The default value of this attribute is the name of the **TypeDescriptor**. For example, a line-of-business (LOB) system data structure named "CN1A" can be represented by a **TypeDescriptor** with **Name** attribute equal to "Customer Name", if the **LobName** attribute of this **TypeDescriptor** is equal to "CN1A".

IdentifierEntityNamespace: A **NameString** attribute that specifies the namespace of the Entity that contains the Identifier that **TypeDescriptor** references. If the **TypeDescriptor** does not reference an **Identifier**, this attribute MUST NOT be present. When this attribute is present, the **IdentifierEntityName** and **IdentifierName** attributes MUST also be present. The default value of this attribute is the namespace of the **Entity** that contains the Method containing the Parameter that contains the **TypeDescriptor**.

IdentifierEntityName: A **NameString** attribute that specifies the name of the **Entity** that contains the **Identifier** that **TypeDescriptor** references. If the **TypeDescriptor** does not reference an **Identifier**, this attribute MUST NOT be present. When this attribute is present, the **IdentifierEntityNamespace** and **IdentifierName** attributes MUST also be present. The default value of this attribute is the name of the **Entity** that contains the **Method** containing the **Parameter** that contains the **TypeDescriptor**.

IdentifierName: A **NameString** attribute that specifies the name of the **Identifier** referenced by the **TypeDescriptor**. If the **TypeDescriptor** does not reference an **Identifier**, this attribute MUST NOT be present.

ForeignIdentifierAssociationName: A **NameString** attribute that specifies the name of the Association referenced by the **TypeDescriptor**. If the **TypeDescriptor** does not reference an **Association**, this attribute MUST NOT be present. When this attribute is present, the **IdentifierName** attribute MUST also be present. The **ForeignIdentifierAssociationName** attribute MUST be specified when the **Identifier** referenced by this **TypeDescriptor** is related to an **Association**, and the **Identifier** is contained by a source **Entity** of the **Association**.

ForeignIdentifierAssociationEntityName: A **NameString** attribute that specifies the name of the **Entity** that contains the **Association** referenced by the **TypeDescriptor**. If the **TypeDescriptor** does not reference an **Association**, this attribute MUST NOT be present. When this attribute is present, the **ForeignIdentifierAssociationEntityNamespace** and **ForeignIdentifierAssociationName** attributes MUST also be present. The default value of this attribute is the name of the **Entity** that contains the Method containing the Parameter that contains the **TypeDescriptor**.

ForeignIdentifierAssociationEntityNamespace: A **NameString** attribute that specifies the namespace of the **Entity** that contains the **Association** referenced by the **TypeDescriptor**. If the **TypeDescriptor** does not reference an **Association**, this attribute MUST NOT be present. When this attribute is present, the **ForeignIdentifierAssociationEntityName** and **ForeignIdentifierAssociationName** attributes MUST also be present. The default value of this attribute is the namespace of the **Entity** that contains the **Method** containing the **Parameter** that contains the **TypeDescriptor**.

AssociatedFilter: A **NameString** attribute that specifies the name of the **FilterDescriptor** that is associated with the **TypeDescriptor**. If the **TypeDescriptor** is not associated with a **FilterDescriptor**, this attribute MUST NOT be present.

IsCollection: An **xs:boolean** attribute that specifies whether the **TypeDescriptor** represents a single data structure or a collection of data structures. The value **MUST** be as listed in the following table.

Value	Description
False	The TypeDescriptor represents a single data structure.
True	The TypeDescriptor represents a collection of data structures.

ReadOnly: An **xs:boolean** attribute that specifies whether the data stored by the data structure represented by the **TypeDescriptor** can be modified. This attribute **MUST NOT** be specified if the value of the **Direction** attribute of the **Parameter** that contains the **TypeDescriptor** is "In". The value **MUST** be as listed in the following table.

Value	Description
False	The data can be modified.
True	The data cannot be modified.

CreatorField: An **xs:boolean** attribute that specifies whether the **TypeDescriptor** represents a field (4) for MethodInstances of type **Creator** that are contained by the **Method** that contains the **Parameter** containing the **TypeDescriptor**. The value **MUST** be as listed in the following table.

Value	Description
False	The TypeDescriptor is not a field (4) in the Creator View .
True	The TypeDescriptor is a field (4) in the Creator View .

UpdaterField: An **xs:boolean** attribute that specifies whether the **TypeDescriptor** represents a field (4) for MethodInstances of type **Updater** that are contained by the **Method** that contains the **Parameter** containing the **TypeDescriptor**. When this attribute is specified, **PreUpdaterField** attribute **MUST NOT** be specified. The value **MUST** be as listed in the following table.

Value	Description
False	The TypeDescriptor is not a field (4) in the Updater View .
True	The TypeDescriptor is a field (4) in the Updater View .

PreUpdaterField: An **xs:boolean** attribute that specifies whether data structure represented by the **TypeDescriptor** stores the latest data value received from the line-of-business (LOB) system of a field (4) for **MethodInstances** of type **Updater**. When this attribute is specified, **UpdaterField** attribute **MUST NOT** be specified. The value **MUST** be as listed in the following table.

Value	Description
False	The TypeDescriptor does not store the last received value.
True	The TypeDescriptor stores the last received value.

Significant: An **xs:boolean** attribute that specifies whether values stored by the data structure represented by this **TypeDescriptor** is included in calculating a hash code or comparing values stored in the data structures. For example, a **TypeDescriptor** representing a customer's last name is taken into account when determining whether a record has been modified, thus it is significant, whereas the **TypeDescriptor** representing date on which the customer record is last read typically is not taken into account to determine whether a record has been modified, thus it is not significant. The value **MUST** be as listed in the following table.

Value	Description
False	The TypeDescriptor is not significant.
True	The TypeDescriptor is significant.

IsSortInput: An **xs:boolean** attribute that specifies whether the value stored by the data structure represented by this **TypeDescriptor** stores the input value for the **SortingFilter**. When this attribute is not specified, the **SortingFilter** must be assumed to not being set and the default sort order should be used to fetch data from the line-of-business (LOB) system. The value **MUST** be as listed in the following table.

Value	Description
False	The TypeDescriptor does not specify the input to the SortingFilter .
True	The TypeDescriptor specified the input to the SortingFilter .

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This **MAY** [<24>](#) be used as a recommendation as to whether to cache the **Model**. This attribute **MUST** be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="TypeDescriptor">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>
        <xs:element name="Interpretation" type="bdc:Interpretation" minOccurs="0"/>
        <xs:element name="DefaultValues" type="bdc:DefaultValues" minOccurs="0">
          <xs:unique name="DefaultValueMethodInstanceNameKey">
            <xs:selector xpath="*"/>
            <xs:field xpath="@MethodInstanceName"/>
          </xs:unique>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

```

    <xs:element name="TypeDescriptors" type="bdc:TypeDescriptors"
minOccurs="0">
      <xs:unique name="TypeDescriptorNameKey">
        <xs:selector xpath="*"/>
        <xs:field xpath="@Name"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
  <xs:attribute name="TypeName" type="bdc:TypeDescriptorTypeNameString"
use="required"/>
  <xs:attribute name="LobName" type="bdc:NameString" use="optional"/>
  <xs:attribute name="IdentifierEntityNamespace" type="bdc:NameString"
use="optional"/>
  <xs:attribute name="IdentifierEntityName" type="bdc:NameString"
use="optional"/>
  <xs:attribute name="IdentifierName" type="bdc:NameString" use="optional"/>
  <xs:attribute name="ForeignIdentifierAssociationName" type="bdc:NameString"
use="optional"/>
  <xs:attribute name="ForeignIdentifierAssociationEntityName"
type="bdc:NameString" use="optional"/>
  <xs:attribute name="ForeignIdentifierAssociationEntityNamespace"
type="bdc:NameString" use="optional"/>
  <xs:attribute name="AssociatedFilter" type="bdc:NameString" use="optional"/>
  <xs:attribute name="IsCollection" type="xs:boolean" default="false"
use="optional"/>
  <xs:attribute name="ReadOnly" type="xs:boolean" default="false"
use="optional"/>
  <xs:attribute name="CreatorField" type="xs:boolean" default="false"
use="optional"/>
  <xs:attribute name="UpdaterField" type="xs:boolean" default="false"
use="optional"/>
  <xs:attribute name="PreUpdaterField" type="xs:boolean" default="false"
use="optional"/>
  <xs:attribute name="Significant" type="xs:boolean" default="true"
use="optional"/>
  <xs:attribute name="IsSortInput" type="xs:boolean" default="false"
use="optional"/>
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.26 DefaultValues

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [TypeDescriptor](#)

A complex type that specifies a list of DefaultValues of a TypeDescriptor.

Child Elements:

DefaultValue: A **DefaultValue** element (section [2.1.4.27](#)) that specifies the **DefaultValue** corresponding to a **MethodInstance**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="DefaultValues">
  <xs:sequence>
    <xs:element name="DefaultValue" type="bcd:DefaultValue" minOccurs="1"
maxOccurs="unbounded" nillable="true"/>
  </xs:sequence>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.27 DefaultValue

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [DefaultValue](#)

A complex type that specifies the DefaultValue of a TypeDescriptor for a MethodInstance. The text associated with this element is the **DefaultValue** of the containing **TypeDescriptor** for the specified **MethodInstance**.

The application that utilizes the structure MUST use this value during initialization of structures corresponding to the **TypeDescriptor** in the context of executing the referenced **MethodInstance**.

The **TypeDescriptor** containing a **DefaultValue** element MUST be contained by a **Parameter** whose **Direction** attribute is set to "In" or "InOut".

Attributes:

MethodInstanceName: A **NameString** attribute (section [2.2.5.2](#)) that specifies the name of the **MethodInstance** to which this **DefaultValue** refers.

Type: A **TypeDescriptorTypeNameString** attribute (section [2.1.5.16](#)) that specifies the data type of the **DefaultValue**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="DefaultValue" mixed="true">
  <xs:attribute name="MethodInstanceName" type="bcd:NameString" use="required"/>
  <xs:attribute name="Type" type="bcd:TypeDescriptorTypeNameString"
use="required"/>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.28 Interpretation

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [TypeDescriptor](#)

A complex type that specifies the rules to apply to the data stored in the data structures represented by a TypeDescriptor. These rules are specified to change the data values returned by the line-of-business (LOB) system to make it easier to represent them in the user interface when the metadata is being used. When the data value is obtained from the LOB system, the specified rules MUST be applied in the order they are specified in the Interpretation element. The first rule

MUST be applied to the data value received from the LOB system, the consecutive rules apply to the data value that results from the application of the previous rule. When the data value is sent to LOB system, the specified rules MUST be applied in the reverse order they are specified in the Interpretation element. The first rule MUST be applied to the data value received from the user, the consecutive rules apply to the data value that results from the application of the previous rule.

Child Elements:

ConvertType: A **ConvertType** element (section [2.1.4.29](#)) that specifies the conversion of a data type to another data type.

NormalizeDateTime: A **NormalizeDateTime** element (section [2.1.4.31](#)) that specifies the conversion of the date and time representation of a value obtained from a line-of-business (LOB) system into another representation.

NormalizeString: A **NormalizeString** element (section [2.1.4.30](#)) that specifies the conversion rules of the empty string or null value obtained from a LOB system into another representation.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Interpretation">
  <xs:choice minOccurs="1" maxOccurs="unbounded">
    <xs:element name="ConvertType" type="bdc:ConvertType"/>
    <xs:element name="NormalizeDateTime" type="bdc:NormalizeDateTime"/>
    <xs:element name="NormalizeString" type="bdc:NormalizeString"/>
  </xs:choice>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.29 ConvertType

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Interpretation](#)

A complex type that specifies the rule to convert the data type of a data value into another data type. When the rules are applied in order, this rule specifies the data type of the data value to be converted to the data type specified by BDCType attribute. When the rules are applied in reverse order, this rule specifies the data type of the data value to be converted to the data type specified by LOBType attribute. For example, this rule can specify converting a date value obtained from a line-of-business (LOB) system, into a culture and locale sensitive string which will eventually be displayed to the user, and converting the updated value for that string back into the date compatible with the LOB system.

Attributes:

LOBType: A **TypeNameString** attribute (section [2.1.5.17](#)) that specifies the data type to convert the data value into when the rules are applied in reverse order.

BDCType: A **TypeNameString** attribute that specifies the data type to convert the data value into when the rules are applied in order.

LOBLocale: A **TypeNameString** attribute that specifies the **locale** that the data is expected to be formatted according to, when the rules are applied in order, and the locale that the data MUST be formatted according to, when the rules are applied in reverse order. The value of this attribute MUST be ignored when the data does not have a locale specific formatting. For example, if the data is converted between an integer value and a string, value 1234 can be converted to "1234", "1.234" or "1,234" based on the specified locale. However, if the data is converted from an integer to a floating point number, the value is usually stored in an implementation-specific condensed form where a locale specific format is not applicable; therefore this attribute would be ignored.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ConvertType">
  <xs:attribute name="LOBType" type="bcd:TypeNameString" use="required"/>
  <xs:attribute name="BDCType" type="bcd:TypeNameString" use="required"/>
  <xs:attribute name="LOBLocale" type="bcd:TypeNameString" use="optional"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.30 NormalizeString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Interpretation](#)

A complex type that specifies the rule to convert the representation of an empty string or null value to another representation. For example, this rule can specify converting a null value obtained from a line-of-business (LOB) system, into an empty string, which will eventually be displayed to the user.

Attributes:

FromLOB: A **StringNormalizeMode** attribute (section [2.1.5.8](#)) that specifies the representation of null value or empty string to convert the data value into when the rules are applied in order.

ToLOB: A **StringNormalizeMode** attribute that specifies the representation of null value or empty string to convert the data value into when the rules are applied in reverse order.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="NormalizeString">
  <xs:attribute name="FromLOB" type="bcd:StringNormalizeMode" use="required"/>
  <xs:attribute name="ToLOB" type="bcd:StringNormalizeMode" use="required"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.31 NormalizeDateTime

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Interpretation](#)

A complex type that specifies the rule to convert the representation of a date and time value to another representation. For example, this rule can specify converting a value represented in **Coordinated Universal Time (UTC)** into a local **time zone**.

Attributes:

LobDateTimeMode: A **LobDateTimeMode** attribute (section [2.1.5.9](#)) that specifies the conversion to apply.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="NormalizeDateTime">
  <xs:attribute name="LobDateTimeMode" type="bcd:LobDateTimeMode" use="required"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.32 TypeDescriptors

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [TypeDescriptor](#)

A complex type that specifies a list of TypeDescriptors of a **TypeDescriptor**. If the containing **TypeDescriptor** has **IsCollection** attribute set to **true**, the **TypeDescriptors** element MUST have exactly one **TypeDescriptor** element.

Child Elements:

TypeDescriptor: A **TypeDescriptor** element (section [2.2.4.24](#)) that specifies a **TypeDescriptor**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="TypeDescriptors">
  <xs:sequence>
    <xs:element name="TypeDescriptor" type="bcd:TypeDescriptor" minOccurs="1"
      maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.33 Actions

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entity](#)

A complex type that specifies a list of Actions of an Entity.

Child Elements:

Action: An **Action** element (section [2.1.4.34](#)) that specifies an **Action**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Actions">
  <xs:sequence>
    <xs:element name="Action" type="bdc:Action" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.34 Action

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Actions](#)

A complex type that specifies an Action of an Entity.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

ActionParameters: An **ActionParameters** element (section [2.1.4.35](#)) that specifies the Parameters of the **Action**.

Attributes:

Position: An **ActionPosition** attribute (section [2.1.5.13](#)) that specifies the suggested position of this **Action** among the other **Actions** of this Entity. An application reading the structure can use this ordering as guidance in an implementation-specific algorithm that represents the **Actions** in the user interface.

IsOpenedInNewWindow: An **xs:boolean** attribute that specifies whether the results of executing an **Action** are presented in a new user interface context. An application reading the structure can use this value as guidance on creating new user interface context when the **Action** is executed.

Value	Description
False	Open in the same user interface context.
True	Open in a new user interface context.

Url: A **UriString** attribute (section [2.1.5.18](#)) that specifies an abstract command that is interpreted by an application reading this structure. The interpretation is implementation-specific. [<25>](#) The attribute includes text and placeholders. The application instantiates the abstract command by replacing the placeholders with values associated with the **Action's ActionParameters** in an implementation-specific manner. [<26>](#)

The value of this attribute MUST be in the following format as expressed in ABNF as specified in [\[RFC5234\]](#):

```

Url = 1*( Text / EscapedLeftBracket / EscapedRightBracket / Placeholder )
Text = %x21-7A / %x7C / %x7E
EscapedLeftBracket = %x7B %x7B
EscapedRightBracket = %x7D %x7D
Placeholder = %x7B Index [%x2C Alignment] [%x3A Format] %x7D
Index = 1*DIGIT
Alignment = [%x2D] 1*DIGIT
Format = 1*ALPHA

```

The **Text** rule is used to produce any visible character other than a curly bracket.

When instantiating the command, the **EscapedLeftBracket** and **EscapedRightBracket** rules MUST be changed to the following definitions:

```

EscapedLeftBracket = %x7B
EscapedRightBracket = %x7D

```

The **Placeholder** rule corresponds to a string segment that MUST be replaced with an implementation-specific value of an ActionParameter of the **Action**. The **ActionParameter** that MUST be used is identified by having the **Index** attribute equal to the integer value specified by the **Index** rule.

The **Index** rule corresponds to a string segment that represents an integer in base ten. The value of this integer MUST be identical to the value of Index attribute of exactly one **ActionParameter** of the **Action**.

The **Alignment** and **Format** rules correspond to string segments that are implementation-specific. <27>

ImageUrl: A **UriString** attribute that specifies the **Uniform Resource Locator (URL)** to the **Action**'s icon image. <28>

Name: A **NameString** attribute (section 2.1.5.15) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY <29> be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([XMLSCHEMA1](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="Action">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>

```

```

        <xs:element name="ActionParameters" type="bdc:ActionParameters"
minOccurs="0">
            <xs:unique name="ActionParameterNameKey">
                <xs:selector xpath="*"/>
                <xs:field xpath="@Name"/>
            </xs:unique>
            <xs:unique name="ActionParameterIndexKey">
                <xs:selector xpath="*"/>
                <xs:field xpath="@Index"/>
            </xs:unique>
        </xs:element>
    </xs:sequence>
    <xs:attribute name="Position" type="bdc:ActionPosition" use="required"/>
    <xs:attribute name="IsOpenedInNewWindow" type="xs:boolean" default="false"/>
    <xs:attribute name="Url" type="bdc:UrlString" use="required"/>
    <xs:attribute name="ImageUrl" type="bdc:UrlString"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.35 ActionParameters

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Action](#)

A complex type that specifies a list of ActionParameters of an Action.

Child Elements:

ActionParameter: An **ActionParameter** element (section [2.1.4.36](#)) that specifies an **ActionParameter**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="ActionParameters">
    <xs:sequence>
        <xs:element name="ActionParameter" type="bdc:ActionParameter" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.36 ActionParameter

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [ActionParameters](#)

A complex type that specifies an ActionParameter of an Action.

The application that utilizes this structure MUST use **ActionParameters** to instantiate the abstract command specified by the **Action's Url** attribute.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Index: An **Ordinal** attribute (section [2.1.5.10](#)) that specifies the position of this **ActionParameter** among the other **ActionParameters** in the **Action** that contains the **ActionParameter**.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [≤30>](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ActionParameter">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:attribute name="Index" type="bdc:Ordinal" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.37 Association

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [MethodInstances](#)

A complex type that specifies an Association.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

SourceEntity: A **SourceEntity** element (section [2.1.4.38](#)) that specifies a source Entity of the **Association**.

DestinationEntity: A **DestinationEntity** element (section [2.1.4.39](#)) that specifies the destination **Entity** of the **Association**.

Attributes:

Type: A **MethodInstanceType** attribute (section [2.1.5.6](#)) that specifies the type of the **MethodInstance**.

Default: An **xs:boolean** attribute that specifies whether the **MethodInstance** is the default among all **MethodInstances** sharing its type within the containing Entity. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The MethodInstance is not the default among all MethodInstances sharing its type within the containing Entity .
True	The MethodInstance is the default among all MethodInstances sharing its type within the containing Entity .

ReturnParameterName: A **NameString** attribute (section [2.2.5.2](#)) that specifies the name of the Parameter that contains the ReturnPropertyDescriptor of the **MethodInstance**. The **Direction** attribute of the Parameter MUST have a value of either "Out", "InOut" or "Return".

This attribute MUST be specified for all types of **MethodInstances** except GenericInvoker, Deleter, and Updater.

ReturnPropertyDescriptorName: A **NameString** attribute that specifies the name of the ReturnPropertyDescriptor of the **MethodInstance**. The Parameter specified by the ReturnParameterName attribute MUST contain the **ReturnPropertyDescriptor**. This attribute MUST be ignored when **ReturnPropertyDescriptorPath** attribute is specified. This attribute SHOULD NOT [<31>](#) be used.

When this attribute is missing, and the **ReturnPropertyDescriptorPath** attribute is not specified, the application utilizing the structure MUST assume the name of the **ReturnPropertyDescriptor** to be the name of the root TypeDescriptor of the **Parameter** specified by the **ReturnParameterName** attribute.

ReturnPropertyDescriptorLevel: A **ReturnPropertyDescriptorLevel** attribute (section [2.1.5.12](#)) that specifies the depth from the root of the **ReturnPropertyDescriptor** of the **MethodInstance**, in the tree of nested TypeDescriptors where the root level equals 0. This attribute MUST be ignored. This attribute SHOULD NOT [<32>](#) be used.

ReturnPropertyDescriptorPath: A **TypeDescriptorPathString** attribute (section [2.1.5.5](#)) that specifies the path [<33>](#) to the return value of the **MethodInstance**.

When this attribute is missing, and the **ReturnPropertyDescriptorName** attribute is not specified, the application utilizing the structure MUST assume the name of the

ReturnTypeDescriptor to be the name of the root **TypeDescriptor** of the **Parameter** specified by the **ReturnParameterName** attribute.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **Model**.

DefaultDisplayName: A **NameString** attribute that specifies the default display name of the **Model**.

IsCached: An **xs:boolean** attribute that specifies whether the **Model** is used frequently. This MAY [34](#) be used as a recommendation as to whether to cache the **Model**. This attribute MUST be set to one of the values listed in the following table.

Value	Description
False	The Model is infrequently used.
True	The Model is frequently used.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Association">
  <xs:complexContent>
    <xs:extension base="bdc:MethodInstance">
      <xs:sequence>
        <xs:element name="SourceEntity" type="bdc:SourceEntity" minOccurs="1"
maxOccurs="unbounded"/>
        <xs:element name="DestinationEntity" type="bdc:DestinationEntity"
minOccurs="1" maxOccurs="1"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.38 SourceEntity

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Association](#)

A complex type that specifies a source Entity of an Association.

Attributes:

Namespace: A **NameString** attribute (section [2.1.5.15](#)) that specifies the namespace of the **Entity** that is a source of the **Association** containing this element.

Name: A **NameString** attribute that specifies the name of the **Entity** that is a source of the **Association** containing this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="SourceEntity">
```

```
<xs:attribute name="Namespace" type="bdc:NameString" use="required"/>
<xs:attribute name="Name" type="bdc:NameString" use="required"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.39 DestinationEntity

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Association](#)

A complex type that specifies the destination Entity of an Association.

Attributes:

Namespace: A **NameString** attribute (section [2.1.5.15](#)) that specifies the namespace of the **Entity** that is the destination of the **Association** containing this element.

Name: A **NameString** attribute that specifies the name of the **Entity** that is the destination of the **Association** containing this element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="DestinationEntity">
  <xs:attribute name="Namespace" type="bdc:NameString" use="required"/>
  <xs:attribute name="Name" type="bdc:NameString" use="required"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.40 Property

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Properties](#)

A complex type that specifies the name and type of a Property. The text associated with this element is the value of the **Property** with the specified name for the containing MetadataObject.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the Property name.

Type: A **TypeNameString** attribute (section [2.1.5.17](#)) that specifies data type of the Property.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Property" mixed="true">
  <xs:attribute name="Name" type="bdc:NameString" use="required"/>
  <xs:attribute name="Type" type="bdc:TypeNameString" use="required"/>
</xs:complexType>
```


See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.41 Properties

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Model](#), [LobSystem](#), [LobSystemInstance](#), [MetadataObject](#), [Entity](#), [Identifier](#), [Method](#), [FilterDescriptor](#), [Parameter](#), [TypeDescriptor](#), [Association](#), [MethodInstance](#), [IndividuallySecurableMetadataObject](#), [AssociationGroup](#), [Action](#), [ActionParameter](#)

A complex type that specifies a list of Properties of a MetadataObject.

Child Elements:

Property: A **Property** element (section [2.1.4.40](#)) that specifies a **Property**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Properties">
  <xs:sequence>
    <xs:element name="Property" type="bdc:Property" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.42 AccessControlList

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Model](#), [LobSystem](#), [Entity](#), [Method](#), [Association](#), [MethodInstance](#), [IndividuallySecurableMetadataObject](#)

A complex type that specifies an access control list (ACL).

Child Elements:

AccessControlEntry: An **AccessControlEntry** element (section [2.1.4.43](#)) that specifies an **access control entry (ACE)**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AccessControlList">
  <xs:sequence>
    <xs:element name="AccessControlEntry" type="bdc:AccessControlEntry"
minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.43 AccessControlEntry

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [AccessControlList](#)

A complex type that specifies an **ACE** to specify access rights for the parent element.

Child Elements:

Right: A **Right** element (section [2.1.4.44](#)) that specifies the permissions available to the **security principal (2)**.

Attributes:

Principal: An **xs:string** attribute that specifies the name of the security principal (2). The value for this attribute MUST be as specified by the following ABNF.

```
principal = windows / membership / role / claim
windows = ["Windows" %x7C] ((domain "\\") / "") domainAccount
membership = "Membership" %x7C membershipIssuer %x7C ((domain "\\") / "")
            domainAccount
role = ["Role" %x7C] roleIssuer %x7C ((domain "\\") / "") domainAccount
claim = "STS" %x7C trustedSTS %x7C claimType %x7C claimValue %x7C
        claimValueType
claimValueType = "String"
```

The **domain** rule is the **domain name** of the security principal (2).

The **domainAccount** rule corresponds to the **domain account** of the security principal (2).

The **membershipIssuer** rule conforms to the format of an original issuer as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **roleIssuer** rule conforms to the format of an original issuer as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **trustedSTS** rule corresponds to the trusted STS as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **claimType** rule corresponds to the claim type **Uniform Resource Identifier (URI)** as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **claimValue** is a **claim value**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AccessControlEntry">
  <xs:sequence>
    <xs:element name="Right" type="bdc:Right" minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="Principal" type="xs:string" use="required"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.4.44 Right

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [AccessControlEntry](#)

A complex type that specifies a single access permission for an ACE.

Attributes:

BdcRight: A **BdcRightName** attribute (section [2.2.5.1](#)) that specifies the permission level of a **Right** element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Right">
  <xs:attribute name="BdcRight" type="bdc:BdcRightName" use="required"/>
</xs:complexType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5 Simple Types

The following table summarizes the set of common **XML schema** simple type definitions defined by this specification. XML schema simple type definitions that are specific to a particular operation are described with the operation.

The following simple types are used as specified by [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#):

- **xs:boolean**
- **xs:integer**
- **xs:string**

2.1.5.1 LobSystemType

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [LobSystem](#)

A simple type specifying the type of line-of-business (LOB) system that a LobSystem is representing. The attributes and settings describing the LOB system **MUST** be stored as Properties on the **LobSystem**, as specified in section [2.1.4.40](#). The value **MUST** be listed in the following table.

Value	Meaning
Database	The represented LOB system is a database.
DotNetAssembly	The represented LOB system is a set of Business Logic Modules. <35>
Wcf	The represented LOB system is a service for which the endpoint URI, the bind process and the contract is specified.
WebService	The represented LOB system is a Web service .

Value	Meaning
Custom	The represented LOB system is a LOB system for which external business logic manages the connection and data transfer through an implementation-specific extensibility mechanism.
OData	The represented LOB system is an OData service .

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="LobSystemType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Database"/>
    <xs:enumeration value="DotNetAssembly"/>
    <xs:enumeration value="Wcf"/>
    <xs:enumeration value="WebService"/>
    <xs:enumeration value="Custom"/>
    <xs:enumeration value="OData"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.2 OperationModeType

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entity](#)

A simple type specifying how a consumer of the structure interacts with a line-of-business (LOB) system when utilizing an implementation-specific cache of **EntityInstances**, when creating, deleting, updating or reading **EntityInstance** data in an implementation-specific manner. The value MUST be listed in the following table.

Value	Meaning
Online	Bypass the cached EntityInstances for all operations and interact with the LOB system directly.
Cached	Perform create, read, update and delete operations directly against the cached EntityInstances . For read operations, if the requested EntityInstances are available in the cache, use the EntityInstances in the cache. Otherwise, bypass the cache to obtain the EntityInstance data from the LOB system, and put it into the cache for later use.
Offline	Perform create, read, update and delete operations only against the cached EntityInstances .
Default	Make an implementation-specific choice to use any one of the other behaviors listed in this table based on capabilities of the consumer of this structure.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="OperationModeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Online"/>
  </xs:restriction>
</xs:simpleType>
```

```

    <xs:enumeration value="Cached" />
    <xs:enumeration value="Offline" />
    <xs:enumeration value="Default" />
  </xs:restriction>
</xs:simpleType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.3 IdentifierType

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Identifier](#)

A simple type that specifies the data type of the value corresponding to the Identifier. The value MUST be listed in the following table.

Value	Meaning
System.Boolean	A bit.
System.Byte	A number ranging from 0 through 255.
System.Char	A Unicode character.
System.DateTime	A date and time ranging from 12:00:00 midnight, January 1, 1 A.D. (Common Era) to 11:59:59 P.M., December 31, 9999 A.D. (Common Era) inclusive, in resolution of 100 nanoseconds.
System.Decimal	A number ranging from negative 79,228,162,514,264,337,593,543,950,335 to positive 79,228,162,514,264,337,593,543,950,335 inclusive.
System.Double	A double-precision number ranging from negative 1.79769313486232e308 to positive 1.79769313486232e308 inclusive, as well as positive zero, negative zero, positive infinity, negative infinity and not-a-number (NaN).
System.Guid	A GUID .
System.Int16	A number ranging from negative 32768 to positive 32767 inclusive.
System.Int32	A number ranging from negative 2,147,483,648 to positive 2,147,483,647 inclusive.
System.Int64	A number ranging from negative 9,223,372,036,854,775,808 to positive 9,223,372,036,854,775,807 inclusive.
System.SByte	A number ranging from negative 128 to positive 127 inclusive.
System.Single	A single precision number ranging from negative 3.402823e38 to 3.402823e38 inclusive.
System.String	A string of Unicode text.
System.TimeSpan	A duration ranging from negative 10675199 days 2 hours 48 minutes 5 seconds 477 milliseconds 580 microseconds 800 nanoseconds to positive 10675199 days 2 hours 48 minutes 5 seconds 477 milliseconds 580 microseconds 700 nanoseconds inclusive, in resolution of 100 nanoseconds.
System.UInt16	A number ranging from 0 to 65535 inclusive.

Value	Meaning
System.UInt32	A number ranging from 0 to 4,294,967,295 inclusive.
System.UInt64	A number ranging from 0 to 18,446,744,073,709,551,615 inclusive.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="IdentifierType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="System.Boolean"/>
    <xs:enumeration value="System.Byte"/>
    <xs:enumeration value="System.Char"/>
    <xs:enumeration value="System.DateTime"/>
    <xs:enumeration value="System.Decimal"/>
    <xs:enumeration value="System.Double"/>
    <xs:enumeration value="System.Guid"/>
    <xs:enumeration value="System.Int16"/>
    <xs:enumeration value="System.Int32"/>
    <xs:enumeration value="System.Int64"/>
    <xs:enumeration value="System.SByte"/>
    <xs:enumeration value="System.Single"/>
    <xs:enumeration value="System.String"/>
    <xs:enumeration value="System.TimeSpan"/>
    <xs:enumeration value="System.UInt16"/>
    <xs:enumeration value="System.UInt32"/>
    <xs:enumeration value="System.UInt64"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.4 FilterDescriptorType

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [FilterDescriptor](#)

Specifies the type of a FilterDescriptor. The value MUST be listed in the following table.

Value	Meaning
Limit	The FilterDescriptor is a LimitFilter .
PageNumber	The FilterDescriptor is a PageNumberFilter .
Wildcard	The FilterDescriptor is a WildcardFilter .
UserContext	The FilterDescriptor is a UserContextFilter .
UserCulture	The FilterDescriptor is a UserCultureFilter .
Username	The FilterDescriptor is a UsernameCredentialFilter .
Password	The FilterDescriptor is a PasswordCredentialFilter .

Value	Meaning
LastId	The FilterDescriptor is a LastIdFilter .
SsoTicket	The FilterDescriptor is an SsoTicketFilter .
UserProfile	The FilterDescriptor is a UserProfileFilter .
Comparison	The FilterDescriptor is a ComparisonFilter .
Timestamp	The FilterDescriptor is a TimeStampFilter .
Input	The FilterDescriptor is an InputFilter .
Output	The FilterDescriptor is an OutputFilter .
InputOutput	The FilterDescriptor is an InputOutputFilter .
Batching	The FilterDescriptor is a BatchingPositionFilter .
BatchingTermination	The FilterDescriptor is a BatchingTerminationFilter .
ActivityId	The FilterDescriptor is an ActivityTrackingFilter .
Sorting	The FilterDescriptor is a SortingFilter .

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xs:simpleType name="FilterDescriptorType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Limit"/>
    <xs:enumeration value="PageNumber"/>
    <xs:enumeration value="Wildcard"/>
    <xs:enumeration value="UserContext"/>
    <xs:enumeration value="UserCulture"/>
    <xs:enumeration value="Username"/>
    <xs:enumeration value="Password"/>
    <xs:enumeration value="LastId"/>
    <xs:enumeration value="SsoTicket"/>
    <xs:enumeration value="UserProfile"/>
    <xs:enumeration value="Comparison"/>
    <xs:enumeration value="Timestamp"/>
    <xs:enumeration value="Input"/>
    <xs:enumeration value="Output"/>
    <xs:enumeration value="InputOutput"/>
    <xs:enumeration value="Batching"/>
    <xs:enumeration value="BatchingTermination"/>
    <xs:enumeration value="ActivityId"/>
    <xs:enumeration value="Sorting"/>
  </xs:restriction>
</xs:simpleType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.5 TypeDescriptorPathString

2.1.5.6 MethodInstanceType

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Association](#), [MethodInstance](#)

Specifies the type of MethodInstance. The value MUST be listed in the following table.

Value	Meaning
Finder	The MethodInstance is a Finder .
SpecificFinder	The MethodInstance is a SpecificFinder .
GenericInvoker	The MethodInstance is a GenericInvoker.
IdEnumerator	The MethodInstance is an IdEnumerator .
ChangedIdEnumerator	The MethodInstance is a ChangedIdEnumerator .
DeletedIdEnumerator	The MethodInstance is a DeletedIdEnumerator .
Scalar	The MethodInstance is a Scalar .
AccessChecker	The MethodInstance is an AccessChecker .
AssociationNavigator	The MethodInstance is an AssociationNavigator .
Associator	The MethodInstance is an Associator .
Disassociator	The MethodInstance is a Disassociator .
Creator	The MethodInstance is a Creator.
Deleter	The MethodInstance is a Deleter.
Updater	The MethodInstance is an Updater.
StreamAccessor	The MethodInstance is a StreamAccessor .
BinarySecurityDescriptorAccessor	The MethodInstance is a BinarySecurityDescriptorAccessor .
BulkSpecificFinder	The MethodInstance is a BulkSpecificFinder .
BulkAssociatedIdEnumerator	The MethodInstance is a BulkAssociatedIdEnumerator .
BulkAssociationNavigator	The MethodInstance is a BulkAssociationNavigator .
BulkIdEnumerator	The MethodInstance is a BulkIdEnumerator .
EventSubscriber	The MethodInstance is an EventSubscriber.
EventUnsubscriber	The MethodInstance is an EventUnsubscriber.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="MethodInstanceType">
```



```

<xs:restriction base="xs:string">
  <xs:enumeration value="Finder"/>
  <xs:enumeration value="SpecificFinder"/>
  <xs:enumeration value="GenericInvoker"/>
  <xs:enumeration value="IdEnumerator"/>
  <xs:enumeration value="ChangedIdEnumerator"/>
  <xs:enumeration value="DeletedIdEnumerator"/>
  <xs:enumeration value="Scalar"/>
  <xs:enumeration value="AccessChecker"/>
  <xs:enumeration value="AssociationNavigator"/>
  <xs:enumeration value="Associator"/>
  <xs:enumeration value="Disassociator"/>
  <xs:enumeration value="Creator"/>
  <xs:enumeration value="Deleter"/>
  <xs:enumeration value="Updater"/>
  <xs:enumeration value="StreamAccessor"/>
  <xs:enumeration value="BinarySecurityDescriptorAccessor"/>
  <xs:enumeration value="BulkSpecificFinder"/>
  <xs:enumeration value="BulkAssociatedIdEnumerator"/>
  <xs:enumeration value="BulkAssociationNavigator"/>
  <xs:enumeration value="BulkIdEnumerator"/>
  <xs:enumeration value="EventSubscriber"/>
  <xs:enumeration value="EventUnsubscriber"/>
</xs:restriction>
</xs:simpleType>

```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.7 ParameterDirection

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Parameter](#)

ParameterDirection specifies the directionality of a Parameter. The value **MUST** be listed in the following table.

Value	Meaning
In	The represented Parameter is an input parameter.
Out	The represented Parameter is an output parameter.
InOut	The represented Parameter is an input and output parameter.
Return	The represented Parameter is a return parameter.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```

<xs:simpleType name="ParameterDirection">
  <xs:restriction base="xs:string">
    <xs:enumeration value="In"/>
    <xs:enumeration value="Out"/>
    <xs:enumeration value="InOut"/>
    <xs:enumeration value="Return"/>
  </xs:restriction>
</xs:simpleType>

```

</xs:simpleType>

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.8 StringNormalizeMode

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [NormalizeString](#)

A simple type specifying the conversion between representations of an empty string and null values for **NormalizeString** rule. The value MUST be listed in the following table.

Value	Meaning
NoChange	The value MUST NOT be modified when the rule is applied.
NormalizeToEmptyString	When the value is null value, it MUST be replaced with an empty string.
NormalizeToNull	When the value is empty string, it MUST be replaced with a null value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="StringNormalizeMode">  
  <xs:restriction base="xs:string">  
    <xs:enumeration value="NoChange"/>  
    <xs:enumeration value="NormalizeToEmptyString"/>  
    <xs:enumeration value="NormalizeToNull"/>  
  </xs:restriction>  
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.9 LobDateTimeMode

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [NormalizeDateTime](#)

A simple type specifying the conversion between representations of date and time values for a **NormalizeDateTime** rule. The value MUST be listed in the following table.

Value	Meaning
UTC	The value is represented in UTC . When the rules are applied in order, and if the value has an unknown time zone, the value MUST be assumed to be in UTC. When the rules are applied in reverse order, the value MUST be converted to UTC representation.
Local	The value is represented in local time zone. When the rules are applied in order, and if the value is represented in an unknown time zone, the value MUST assumed to be in local time. When the rules are applied in reverse order, the value MUST be converted to local time zone.
Unspecified	The value is not represented in any time zone. When the rules are applied in order, and if

Value	Meaning
	the value has an unknown time zone, the value MUST be assumed to be in UTC. When the rules are applied in reverse order, the time zone information MUST be removed.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="LobDateTimeMode">
  <xs:restriction base="xs:string">
    <xs:enumeration value="UTC"/>
    <xs:enumeration value="Local"/>
    <xs:enumeration value="Unspecified"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.10 Ordinal

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [ActionParameter](#)

An ordering of integers describing the position of an element in a sequence.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="Ordinal">
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="0"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.11 InstanceCount

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entity](#)

The estimated number of EntityInstances of an Entity.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="InstanceCount">
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="0"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.12 ReturnPropertyDescriptorLevel

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Association](#), [MethodInstance](#)

The depth from the root of the ReturnPropertyDescriptor of the MethodInstance or Association, in the tree of nested TypeDescriptors where the root level equals 0.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="ReturnPropertyDescriptorLevel">
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="0"/>
    <xs:maxInclusive value="29"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.13 ActionPosition

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Action](#)

The value of ActionPosition specifies the position of this Action among the other **Actions** of this Entity. The order of the **Actions** represented in the user interface is implementation-specific.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="ActionPosition">
  <xs:restriction base="xs:integer">
    <xs:minInclusive value="1"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.14 BdcRightName

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Right](#)

The value of **BdcRightName** specifies the permission available to the security principal (2) holding a Right. The value MUST be listed in the following table.

Value	Meaning
None	No permissions.

Value	Meaning
Execute	The represented security principal (2) has the permission to call a MethodInstance.
Edit	The represented security principal (2) has permission to change the attributes of a MetadataObject or its relationship to other MetadataObjects .
SetPermissions	The represented security principal (2) has permission to change the set of permissions for a MetadataObject .
SelectableInClients	The represented security principal (2) has permission to select the MetadataObject this right refers to in an implementation-specific user interface from a list of available MetadataObjects . If the security principal (2) does not have this permission, the MetadataObject SHOULD NOT be presented in such a list.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="BdcRightName">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Execute"/>
    <xs:enumeration value="Edit"/>
    <xs:enumeration value="SetPermissions"/>
    <xs:enumeration value="SelectableInClients"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.15 NameString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Model](#), [Property](#), [LobSystem](#), [LobSystemInstance](#), [MetadataObject](#), [Entity](#), [Identifier](#), [Method](#), [FilterDescriptor](#), [Parameter](#), [TypeDescriptor](#), [DefaultValue](#), [Association](#), [SourceEntity](#), [DestinationEntity](#), [MethodInstance](#), [IndividuallySecurableMetadataObject](#), [AssociationGroup](#), [AssociationReference](#), [Action](#), [ActionParameter](#)

A simple type used to specify MetadataObject names.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="NameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.16 TypeDescriptorTypeNameString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [TypeDescriptor](#), [DefaultValue](#)

A simple type used to specify implementation-specific identifier for data type of the data structure that the **TypeDescriptor** represents. The value of this element is mapped to a data type using an implementation-specific Business Logic Module<[36](#)> associated with the **Parameter** which contains this **TypeDescriptor**. The Business Logic Module<[37](#)> that can perform this mapping MUST be specified as follows.

1. If the **Parameter** that contains this **TypeDescriptor** contains a **Property** with name "TypeReflectorTypeName" and type "System.String", the Business Logic Module<[38](#)> specified by the implementation-specific identifier represented by the string **Property** value MUST be used.
2. If previous condition is not met, and if the **LobSystem** that contains the **Entity** containing the **Method** of the **Parameter** that contains this **TypeDescriptor** has section **type** specified as "Custom", and if the Business Logic Module<[39](#)> associated with the **LobSystem** for the purposes of communicating with the corresponding line-of-business (LOB) system, which is identified by the value of the **LobSystem** contained b with name "SystemUtilityTypeName" and type "System.String", specifies a Business Logic Module<[40](#)> for the purpose of mapping value of **typeName** element to a data type, the specified Business Logic Module<[41](#)> MUST be used.
3. If previous conditions are not met, implementation-specific Business Logic Module<[42](#)> MUST be used to perform the mapping. In this case, the value of the implementation-specific identifier for the data type of the data structure that the **TypeDescriptor** represents MUST be in the format specified by the following ABNF.

```
Value = TypeName *1(%x2C BusinessLogicModule)
BusinessLogicModule = FullAssemblyName / LobSystemName
FullAssemblyName = LibraryIdentifier %x2C VersionProperty %x2C CultureProperty %x2C
PublicKeyTokenProperty
```

Where **LibraryIdentifier**, **VersionProperty**, **PublicKeyTokenProperty**, and **CultureProperty** rules are as specified in [\[MS-NRTP\]](#) section 2.2.1.3.

The **TypeName** rule is the name of the type that conforms to the [\[ECMA-335\]](#) specification and can be understood by the .NET Framework. The format is as specified in [\[MS-NRTP\]](#) section 2.2.1.2.

The **LobSystemName** rule is the name of the **LobSystem** which contains the **Entity** that contains the **Method** which contains the **Parameter** which contains the **TypeDescriptor**.

The occurrence of **BusinessLogicModule** in the preceding ABNF MUST yield to an **LobSystemName**, if the represented data type resides in the Business Logic Module<[43](#)> associated with the **LobSystem** which contains the **TypeDescriptor**, otherwise the occurrence of **BusinessLogicModule** MUST be a FullAssemblyName. The values specified in the following table do not require a **BusinessLogicModule** to be specified.

Value	Description
System.String	A string of Unicode text.
System.Int16	A number ranging from negative 32768 to positive 32767 inclusive.

Value	Description
System.Int32	A number ranging from negative 2,147,483,648 to positive 2,147,483,647 inclusive.
System.Int64	A number ranging from negative 9,223,372,036,854,775,808 to positive 9,223,372,036,854,775,807 inclusive.
System.UInt16	A number ranging from 0 to 65535 inclusive.
System.UInt32	A number ranging from 0 to 4,294,967,295 inclusive.
System.UInt64	A number ranging from 0 to 18,446,744,073,709,551,615 inclusive.
System.DateTime	A date and time ranging from 12:00:00 midnight, January 1, 1 Anno Domini (Common Era) to 11:59:59 P.M., December 31, 9999 Anno Domini (Common Era) inclusive, in resolution of 100 nanoseconds.
System.TimeSpan	A duration ranging from negative 10675199 days 2 hours 48 minutes 5 seconds 477 milliseconds 580 microseconds 800 nanoseconds to positive 10675199 days 2 hours 48 minutes 5 seconds 477 milliseconds 580 microseconds 700 nanoseconds inclusive, in resolution of 100 nanoseconds.
System.Single	A single precision number ranging from negative 3.402823e38 to 3.402823e38 inclusive.
System.Double	A double precision number ranging from negative 1.79769313486232e308 to positive 1.79769313486232e308 inclusive as well as positive zero, negative zero, positive infinity, negative infinity and not-a-number (NaN).
System.Decimal	A number ranging from negative 79,228,162,514,264,337,593,543,950,335 to positive 79,228,162,514,264,337,593,543,950,335 inclusive.
System.Char	A Unicode character.
System.Byte	A number ranging from 0 to 255 inclusive.
System.SByte	A number ranging from negative 128 to positive 127 inclusive.
System.Guid	A GUID.
System.Boolean	A bit.
System.Uri	An URL.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="TypeDescriptorTypeNameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.17 TypeNameString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Property](#), [ConvertType](#)

A simple type used to specify data types. The value MUST be in the format specified by the following ABNF.

```
Identifier = TypeName *1(%x2C FullAssemblyName)
FullAssemblyName = LibraryIdentifier %x2C VersionProperty %x2C CultureProperty %x2C
PublicKeyTokenProperty
```

Where **LibraryIdentifier**, **VersionProperty**, **PublicKeyTokenProperty**, and **CultureProperty** are as specified in [\[MS-NRTP\]](#) section 2.2.1.3.

TypeName: The name of the type that conforms to the [\[ECMA-335\]](#) specification and can be understood by the .NET Framework. The format is as specified in [\[MS-NRTP\]](#) section 2.2.1.2.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="TypeNameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.18 UrlString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Action](#)

A simple type used to restrict the length of URL attributes.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="UrlString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="2080"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.1](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.1.5.19 VersionString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

Referenced by: [Entity](#)

A set of four numeric values separated by dots that represent the version of the parent element.

The first numerical value represents the major version, the second numerical value represents the minor version, the third numerical value represents the build version and the fourth numerical value represents the revision version.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="VersionString">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9]+(\.[0-9]+){1,3}" />
  </xs:restriction>
</xs:simpleType>
```

See section 5.1 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.2 Metadata Model Resources

2.2.1 Namespaces

This specification defines and references various XML namespaces using the mechanisms specified in [XMLNS]. Although this specification associates a specific XML namespace prefix for each XML namespace that is used, the choice of any particular XML namespace prefix is implementation-specific and not significant for interoperability.

Prefix	Namespace URI	Reference
xs	http://www.w3.org/2001/XMLSchema	[XMLSCHEMA1] [XMLSCHEMA2]
bdc	http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources	

2.2.2 Global Elements

2.2.2.1 Model

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

A **Model** element (section 2.2.4.1) that identifies a Model.

The following W3C XML Schema ([XMLSCHEMA1] section 2.1) fragment specifies the contents of this element.

```
<xs:element name="Model" type="bdc:Model"/>
```

See section 5.2 for the full W3C XML Schema ([XMLSCHEMA1] section 2.1).

2.2.3 Global Attributes

None.

2.2.4 Complex Types

2.2.4.1 Model

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Model](#)

A complex type that identifies a Model.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

LobSystems: An **LobSystems** element (section [2.2.4.2](#)) that specifies the LobSystems of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.2.5.2](#)) that specifies the name of the **Model**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Model">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="LobSystems" type="bdc:LobSystems" minOccurs="0"
maxOccurs="1">
          <xs:unique name="LobSystemNameKey">
            <xs:selector xpath="*/">
              <xs:field xpath="@Name"/>
            </xs:unique>
          </xs:element>
        </xs:sequence>
        <xs:attribute name="Name" type="bdc>NameString" use="required"/>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.2 LobSystems

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Model](#)

A complex type that identifies a list of LobSystems of a Model.

Child Elements:

LobSystem: An **LobSystems** element (section [2.2.4.2](#)) that specifies a **LobSystem**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LobSystems">
  <xs:sequence>
    <xs:element name="LobSystem" type="bcd:LobSystem" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.3 MetadataObject

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [LobSystemInstance](#), [Identifier](#), [FilterDescriptor](#), [TypeDescriptor](#), [Parameter](#), [IndividuallySecurableMetadataObject](#), [AssociationGroup](#), [ActionParameter](#), [Action](#)

A complex type that identifies a MetadataObject.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="MetadataObject" abstract="true">
  <xs:sequence>
    <xs:element name="LocalizedDisplayNames" type="bcd:LocalizedDisplayNames"
minOccurs="0" maxOccurs="1">
      <xs:unique name="LocalizedDisplayNameLCIDKey">
        <xs:selector xpath="*/>
        <xs:field xpath="@LCID"/>
      </xs:unique>
    </xs:element>
    <xs:element name="Properties" type="bcd:Properties" minOccurs="0"
maxOccurs="1">
      <xs:unique name="PropertyNameKey">
        <xs:selector xpath="*/>
        <xs:field xpath="@Name"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
```

```
<xs:attribute name="Name" type="bcd:NameString" use="required"/>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.4 IndividuallySecurableMetadataObject

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Association](#), [MethodInstance](#), [Method](#), [Entity](#), [LobSystem](#), [Model](#)

A complex type that identifies a MetadataObject that can be assigned a specific access control list (ACL).

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="IndividuallySecurableMetadataObject" abstract="true">
  <xs:complexContent>
    <xs:extension base="bcd:MetadataObject">
      <xs:sequence>
        <xs:element name="AccessControlList" type="bcd:AccessControlList"
minOccurs="0" maxOccurs="1"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.5 LocalizedDisplayNames

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Model](#), [LobSystem](#), [LobSystemInstance](#), [MetadataObject](#), [Entity](#), [Identifier](#), [Method](#), [FilterDescriptor](#), [Parameter](#), [TypeDescriptor](#), [Association](#), [IndividuallySecurableMetadataObject](#), [MethodInstance](#), [AssociationGroup](#), [Action](#), [ActionParameter](#)

A complex type that specifies a list of localized names of a MetadataObject.

Child Elements:

LocalizedDisplayName: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies a localized name.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LocalizedDisplayNames">
  <xs:sequence>
    <xs:element name="LocalizedDisplayName" type="bcd:LocalizedDisplayName"
      minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.6 LocalizedDisplayName

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [LocalizedDisplayNames](#)

A complex type that specifies a localized name. The text associated with this element is the localized name associated with the specified language code identifier (LCID).

Attributes:

LCID: An **xs:integer** attribute that specifies the LCID.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LocalizedDisplayName" mixed="true">
  <xs:attribute name="LCID" type="xs:integer" use="required"/>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.7 LobSystem

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [LobSystems](#)

A complex type that identifies an LobSystem.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

LobSystemInstances: An **LobSystemInstances** element (section [2.2.4.8](#)) that specifies a list of LobSystemInstances of the **LobSystem**.

Entities: An **Entities** element (section [2.1.4.10](#)) that specifies a list of Entities of the **LobSystem**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="LobSystem">
  <xs:complexContent>
    <xs:extension base="bcd:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="LobSystemInstances" type="bcd:LobSystemInstances"
minOccurs="0" maxOccurs="1">
          <xs:unique name="LobSystemInstanceNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
          </xs:unique>
        </xs:element>
        <xs:element name="Entities" type="bcd:Entities" minOccurs="0"
maxOccurs="1">
          <xs:unique name="EntityNameNamespaceVersionKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
            <xs:field xpath="@Namespace" />
            <xs:field xpath="@Version" />
          </xs:unique>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.8 LobSystemInstances

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [LobSystem](#)

A complex type that identifies a list of LobSystemInstances of a LobSystem.

Child Elements:

LobSystemInstance: An **LobSystemInstance** element (section [2.1.4.9](#)) that specifies a **LobSystemInstance**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="LobSystemInstances">
  <xs:sequence>
    <xs:element name="LobSystemInstance" type="bdc:LobSystemInstance" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.9 LobSystemInstance

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [LobSystemInstances](#)

A complex type that identifies an LobSystemInstance of an LobSystem.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="LobSystemInstance">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.10 Entities

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [LobSystem](#)

A complex type that identifies a list of Entities of an LobSystem.

Child Elements:

Entity: An **Entity** element (section [2.1.4.11](#)) that specifies an **Entity**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="Entities">
  <xs:sequence>
    <xs:element name="Entity" type="bdc:Entity" minOccurs="1"
maxOccurs="unbounded">
      <xs:unique name="MethodNameKey">
        <xs:selector xpath="//bdc:MethodInstances/*"/>
        <xs:field xpath="@Name"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.11 Entity

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Entities](#)

A complex type that identifies an Entity.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Identifiers: An **Identifiers** element (section [2.1.4.15](#)) that specifies the Identifiers of the **Entity**.

Methods: A **Methods** element (section [2.1.4.17](#)) that specifies the Methods of the **Entity**.

AssociationGroups: An **AssociationGroups** element (section [2.1.4.12](#)) that specifies the AssociationGroups of the **Entity**.

Actions: An **Actions** element (section [2.1.4.33](#)) that specifies the Actions of the **Entity**.

Attributes:

Namespace: A **NameString** attribute (section [2.1.5.15](#)) that specifies the namespace of the **Entity**.

Version: A **VersionString** attribute (section [2.1.5.19](#)) that specifies the version number of the **Entity**.

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="Entity">

```



```

<xs:complexContent>
  <xs:extension base="bdc:IndividuallySecurableMetadataObject">
    <xs:sequence>
      <xs:element name="Identifiers" type="bdc:Identifiers" minOccurs="0">
        <xs:unique name="IdentifierNameKey">
          <xs:selector xpath="*" />
          <xs:field xpath="@Name" />
        </xs:unique>
      </xs:element>
      <xs:element name="Methods" type="bdc:Methods" minOccurs="0">
        <xs:unique name="MethodNameKey">
          <xs:selector xpath="*" />
          <xs:field xpath="@Name" />
        </xs:unique>
      </xs:element>
      <xs:element name="AssociationGroups" type="bdc:AssociationGroups"
minOccurs="0">
        <xs:unique name="AssociationGroupNameKey">
          <xs:selector xpath="*" />
          <xs:field xpath="@Name" />
        </xs:unique>
      </xs:element>
      <xs:element name="Actions" type="bdc:Actions" minOccurs="0">
        <xs:unique name="ActionNameKey">
          <xs:selector xpath="*" />
          <xs:field xpath="@Name" />
        </xs:unique>
      </xs:element>
    </xs:sequence>
    <xs:attribute name="Namespace" type="bdc:NameString" use="required" />
    <xs:attribute name="Version" type="bdc:VersionString" use="required" />
  </xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.12 AssociationGroups

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Entity](#)

A complex type that identifies a list of AssociationGroups of an Entity.

Child Elements:

AssociationGroup: An **AssociationGroup** element (section [2.1.4.13](#)) that specifies an AssociationGroup.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="AssociationGroups">
  <xs:sequence>
    <xs:element name="AssociationGroup" type="bdc:AssociationGroup" minOccurs="1"
maxOccurs="unbounded" />
  </xs:sequence>
</xs:complexType>

```

```
</xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.13 AssociationGroup

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [AssociationGroups](#)

A complex type that identifies an AssociationGroup.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AssociationGroup">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.14 Identifiers

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Entity](#)

A complex type that identifies a list of Identifiers of an Entity.

Child Elements:

Identifier: An **Identifier** element (section [2.1.4.16](#)) that specifies an **Identifier**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Identifiers">
  <xs:sequence>
    <xs:element name="Identifier" type="bdc:Identifier" minOccurs="1"
      maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

```
</xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.15 Identifier

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Identifiers](#)

A complex type that identifies an Identifier.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Identifier">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.16 Methods

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Entity](#)

A complex type that identifies a list of Methods of an Entity.

Child Elements:

Method: A **Method** element (section [2.2.4.17](#)) that specifies a **Method**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Methods">
  <xs:sequence>
    <xs:element name="Method" type="bdc:Method" minOccurs="1"
      maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

```

    <xs:key name="ParameterNameKey">
      <xs:selector xpath="./bdc:Parameter"/>
      <xs:field xpath="@Name"/>
    </xs:key>
    <xs:key name="MethodMethodNameKey">
      <xs:selector xpath="./bdc:MethodInstances/*"/>
      <xs:field xpath="@Name"/>
    </xs:key>
  </xs:element>
</xs:sequence>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.17 Method

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Methods](#)

A complex type that identifies a Method.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

FilterDescriptors: A **FilterDescriptors** element (section [2.2.4.18](#)) that specifies the FilterDescriptors of the **Method**.

Parameters: A **Parameters** element (section [2.2.4.22](#)) that specifies the Parameters of the **Method**.

MethodInstances: A **MethodInstances** element (section [2.1.4.21](#)) that specifies the MethodInstances of the **Method**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="Method">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="FilterDescriptors" type="bdc:FilterDescriptors"
          minOccurs="0" maxOccurs="1">
          <xs:unique name="FilterDescriptorNameKey">
            <xs:selector xpath="*/>

```

```

        <xs:field xpath="@Name"/>
    </xs:unique>
</xs:element>
<xs:element name="Parameters" type="bdc:Parameters" minOccurs="0"
maxOccurs="1"/>
    <xs:element name="MethodInstances" type="bdc:MethodInstances" minOccurs="0"
maxOccurs="1"/>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.18 FilterDescriptors

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Method](#)

A complex type that identifies a list of FilterDescriptors of a Method.

Child Elements:

FilterDescriptor: A **FilterDescriptor** element (section [2.1.4.20](#)) that specifies a FilterDescriptor.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="FilterDescriptors">
    <xs:sequence>
        <xs:element name="FilterDescriptor" type="bdc:FilterDescriptor" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.19 FilterDescriptor

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [FilterDescriptors](#)

A complex type that identifies a FilterDescriptor.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="FilterDescriptor">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.20 MethodInstances

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Method](#)

A complex type that identifies a list of MethodInstances of a Method.

Child Elements:

Association: An **Association** element (section [2.2.4.30](#)) that specifies an Association.

MethodInstance: A **MethodInstance** element (section [2.2.4.21](#)) that specifies a MethodInstance.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="MethodInstances">
  <xs:choice minOccurs="1" maxOccurs="unbounded">
    <xs:element name="Association" type="bdc:Association"/>
    <xs:element name="MethodInstance" type="bdc:MethodInstance"/>
  </xs:choice>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.21 MethodInstance

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [MethodInstances](#)

A complex type that identifies a MethodInstance.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="MethodInstance">
  <xs:complexContent>
    <xs:extension base="bcd:IndividuallySecurableMetadataObject"/>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.22 Parameters

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Method](#)

A complex type that identifies a list of Parameters of a Method.

Child Elements:

Parameter: A **Parameter** element (section [2.1.4.24](#)) that specifies a **Parameter**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Parameters">
  <xs:sequence>
    <xs:element name="Parameter" type="bcd:Parameter" minOccurs="1"
      maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.23 Parameter

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Parameters](#)

A complex type that identifies a Parameter.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

TypeDescriptor: A **TypeDescriptor** element (section [2.2.4.24](#)) that specifies the root TypeDescriptor of the **Parameter**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Parameter">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>
        <xs:element name="TypeDescriptor" type="bdc:TypeDescriptor"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.24 TypeDescriptor

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Parameter](#), [TypeDescriptors](#)

A complex type that identifies a TypeDescriptor.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

TypeDescriptors: A **TypeDescriptors** element (section [2.2.4.25](#)) that specifies the child **TypeDescriptors** of the **TypeDescriptor**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="TypeDescriptor">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>
        <xs:element name="TypeDescriptors" type="bdc:TypeDescriptors"
          minOccurs="0"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```



```

        <xs:unique name="TypeDescriptorNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
        </xs:unique>
    </xs:element>
</xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.25 TypeDescriptors

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [TypeDescriptor](#)

A complex type that identifies a list of child TypeDescriptors of a parent **TypeDescriptor**.

Child Elements:

TypeDescriptor: A **TypeDescriptor** element (section [2.2.4.24](#)) that specifies a **TypeDescriptor**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="TypeDescriptors">
    <xs:sequence>
        <xs:element name="TypeDescriptor" type="bdc:TypeDescriptor" minOccurs="1"
maxOccurs="unbounded" />
    </xs:sequence>
</xs:complexType>

```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.26 Actions

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Entity](#)

A complex type that identifies a list of Actions of an Entity.

Child Elements:

Action: An **Action** element (section [2.1.4.34](#)) that specifies an **Action**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```

<xs:complexType name="Actions">
    <xs:sequence>
        <xs:element name="Action" type="bdc:Action" minOccurs="1"
maxOccurs="unbounded" />
    </xs:sequence>
</xs:complexType>

```

```
</xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.27 Action

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Actions](#)

A complex type that identifies an Action of an Entity.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

ActionParameters: An **ActionParameters** element (section [2.2.4.28](#)) that specifies the Parameters of the **Action**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Action">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>
        <xs:element name="ActionParameters" type="bdc:ActionParameters"
minOccurs="0">
          <xs:unique name="ActionParameterNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
          </xs:unique>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.28 ActionParameters

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Action](#)

A complex type that identifies a list of ActionParameters of an Action.

Child Elements:

ActionParameter: An **ActionParameter** element (section [2.2.4.29](#)) that specifies an **ActionParameter**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ActionParameters">
  <xs:sequence>
    <xs:element name="ActionParameter" type="bdc:ActionParameter" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.29 ActionParameter

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [ActionParameters](#)

A complex type that identifies an ActionParameter of an Action.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="ActionParameter">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.30 Association

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [MethodInstances](#)

A complex type that identifies an Association.

Child Elements:

LocalizedDisplayNames: A **LocalizedDisplayNames** element (section [2.1.4.5](#)) that specifies the localized names of the **Model**.

Properties: A **Properties** element (section [2.1.4.41](#)) that specifies the Properties of the **Model**.

AccessControlList: An **AccessControlList** element (section [2.1.4.42](#)) that specifies the access control list (ACL) of the **Model**.

Attributes:

Name: A **NameString** attribute (section [2.1.5.15](#)) that specifies the name of the **MetadataObject**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Association">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject"/>
  </xs:complexContent>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.31 Property

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Properties](#)

A complex type that specifies the name and type of a Property element. The text associated with this element is the value of the **Property** with the specified name for the containing MetadataObject.

Attributes:

Name: A **NameString** attribute (section [2.2.5.2](#)) that specifies the name of the **Property**.

Type: A section **TypeNameString** attribute (section [2.2.5.3](#)) that specifies data type of the **Property**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Property" mixed="true">
  <xs:attribute name="Name" type="bdc:NameString" use="required"/>
  <xs:attribute name="Type" type="bdc:TypeNameString" use="required"/>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.32 Properties

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Model](#), [LobSystem](#), [LobSystemInstance](#), [MetadataObject](#), [Entity](#), [Identifier](#), [Method](#), [FilterDescriptor](#), [Parameter](#), [TypeDescriptor](#), [Association](#), [IndividuallySecurableMetadataObject](#), [MethodInstance](#), [AssociationGroup](#), [Action](#), [ActionParameter](#)

A complex type that specifies a list of Properties of a MetadataObject.

Child Elements:

Property: A **Property** element (section [2.2.4.31](#)) that specifies a **Property**.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Properties">
  <xs:sequence>
    <xs:element name="Property" type="bcd:Property" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.33 AccessControlList

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Model](#), [LobSystem](#), [Entity](#), [Method](#), [Association](#), [IndividuallySecurableMetadataObject](#), [MethodInstance](#)

A complex type that specifies an access control list (ACL).

Child Elements:

AccessControlEntry: An **AccessControlEntry** element (section [2.2.4.34](#)) that specifies an ACE.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AccessControlList">
  <xs:sequence>
    <xs:element name="AccessControlEntry" type="bcd:AccessControlEntry"
minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.34 AccessControlEntry

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [AccessControlList](#)

A complex type that specifies an ACE to specify access rights for the parent element.

Child Elements:

Right: A **Right** element (section [2.2.4.35](#)) that specifies the permissions available to the security principal (2).

Attributes:

Principal: An **xs:string** attribute that specifies the name of the security principal (2). The value for this attribute **MUST** be as specified by the following ABNF.

```
principal = windows / membership / role / claim
windows = ["Windows" %x7C] ((domain "\") / "") domainAccount
membership = "Membership" %x7C membershipIssuer %x7C ((domain "\") / "")
            domainAccount
role = ["Role" %x7C] roleIssuer %x7C ((domain "\") / "") domainAccount
claim = "STS" %x7C trustedSTS %x7C claimType %x7C claimValue %x7C
       claimValueType
claimValueType = "String"
```

The **domain** rule is the domain name of the security principal (2).

The **domainAccount** rule corresponds to the domain account of the security principal (2).

The **membershipIssuer** rule conforms to the format of an original issuer as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **roleIssuer** rule conforms to the format of an original issuer as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **trustedSTS** rule conforms to the trusted STS as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **claimType** rule is the claim type URI as specified in [\[MS-SPSTWS\]](#) section 2.2.2.

The **claimValue** is a claim value.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="AccessControlEntry">
  <xs:sequence>
    <xs:element name="Right" type="bcd:Right" minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="Principal" type="xs:string" use="required"/>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.4.35 Right

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [AccessControlEntry](#)

A complex type that specifies a single access permission for an ACE.

Attributes:

BdcRight: A **BdcRight** attribute (section [2.2.5.1](#)) that specifies permission level of a **Right** element.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this complex type.

```
<xs:complexType name="Right">
  <xs:attribute name="BdcRight" type="bdc:BdcRightName" use="required"/>
</xs:complexType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.5 Simple Types

The following simple types are used as specified by [\[XMLSCHEMA1\]](#) and [\[XMLSCHEMA2\]](#):

- **xs:boolean**
- **xs:integer**
- **xs:string**

2.2.5.1 BdcRightName

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Right](#)

The value of **BdcRightName** specifies the permission available to the security principal (2) holding a **Right**. The value MUST be listed in the following table.

Value	Meaning
None	No permissions
Execute	The represented security principal (2) has the permission to call a MethodInstance
Edit	The represented security principal (2) has permission to change the attributes of a MetadataObject or its relationship to other MetadataObjects .
SetPermissions	The represented security principal (2) has permission to change the set of permissions for a MetadataObject .
SelectableInClients	The represented security principal (2) has permission to select the MetadataObject this right refers to in an implementation-specific user interface from a list of available MetadataObjects . If the security principal (2) does not have this permission, the MetadataObject SHOULD NOT be presented in such a list.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="BdcRightName">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Execute"/>
    <xs:enumeration value="Edit"/>
  </xs:restriction>
</xs:simpleType>
```

```
<xs:enumeration value="SetPermissions"/>
<xs:enumeration value="SelectableInClients"/>
</xs:restriction>
</xs:simpleType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.5.2 NameString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Model](#), [Property](#), [LobSystem](#), [LobSystemInstance](#), [MetadataObject](#), [Entity](#), [Identifier](#), [Method](#), [FilterDescriptor](#), [Parameter](#), [TypeDescriptor](#), [Association](#), [IndividuallySecurableMetadataObject](#), [MethodInstance](#), [AssociationGroup](#), [Action](#), [ActionParameter](#)

A simple type used to restrict the length of MetadataObject names.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="NameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.5.3 TypeNameString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Property](#)

A simple type used to specify data types. The value MUST be in the format specified by the following ABNF.

```
Identifier = TypeName (%x2C FullAssemblyName)
FullAssemblyName = LibraryIdentifier %x2C VersionProperty %x2C CultureProperty %x2C
PublicKeyTokenProperty
```

Where **LibraryIdentifier**, **VersionProperty**, **PublicKeyTokenProperty**, and **CultureProperty** are as specified in [\[MS-NRTP\]](#) section 2.2.1.3.

TypeName: The name of the type that conforms to the [\[ECMA-335\]](#) specification and can be understood by the .NET Framework. The format is as specified in [\[MS-NRTP\]](#) section 2.2.1.2.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="TypeNameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
  </xs:restriction>
</xs:simpleType>
```



```
<xs:maxLength value="255"/>
</xs:restriction>
</xs:simpleType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

2.2.5.4 VersionString

Target namespace: <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

Referenced by: [Entity](#)

A set of four numeric values separated by dots that represent the version of the parent element.

The first numerical value represents the major version, the second numerical value represents the minor version, the third numerical value represents the build version, and the fourth numerical value represents the revision version.

The following W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1) fragment specifies the contents of this simple type.

```
<xs:simpleType name="VersionString">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9]+(\.[0-9]+){1,3}"/>
  </xs:restriction>
</xs:simpleType>
```

See section [5.2](#) for the full W3C XML Schema ([\[XMLSCHEMA1\]](#) section 2.1).

3 Structure Examples

All the examples are using a simple model, describing hypothetical simplified Customer Relationship Management (CRM) system.

The examples in section [3.1](#), section [3.2](#), and section [3.3](#) are demonstrating the differences between equivalent Models targeting different LobSystem types (Database, DotNetAssembly, and Web Service). To make the comparison easier they only describe a single Entity "Customer" with a single Method, used as a SpecificFinder.

The example in section [3.4](#) demonstrates the restricted schema used to set **Rights**, Properties, and localized names for metadata object. This resources file can be used to extend any of the previous model examples.

The example in section [3.5](#) demonstrates Finders, Filters and DefaultValues.

The example in section [3.6](#) demonstrates Creator, Updater and Deleter MethodInstances.

The example in section [3.7](#) demonstrates Association between two **Entities**.

3.1 Database Model

This is an example of a simple model of an LOB system of type Database. It demonstrates how to use a set of LobSystem and LobSystemInstance properties to configure connection to a database.

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<Model Name="ExampleApplicationDefinition"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <LobSystems>
    <LobSystem Name="ExampleCRM" Type="Database">
      <Properties>
        <!-- This database uses % symbol for the LIKE operator. -->
        <Property Name="WildcardCharacter" Type="System.String">%</Property>
      </Properties>
      <LobSystemInstances>
        <LobSystemInstance Name="ExampleServer">
          <Properties>
            <Property Name="AuthenticationMode" Type="System.String">PassThrough</Property>
            <!-- The database instance is named ExampleSQL and is running on the same
computer as the application using this Model. -->
            <Property Name="RdbConnection Data Source"
Type="System.String">(local)\ExampleSQL</Property>
            <!-- The database to be used is named ExampleDB. -->
            <Property Name="RdbConnection Initial Catalog"
Type="System.String">ExampleDB</Property>
            <!-- The database instance is using integrated security. -->
            <Property Name="RdbConnection Integrated Security"
Type="System.String">SSPI</Property>
          </Properties>
        </LobSystemInstance>
      </LobSystemInstances>
    </LobSystem>
  </LobSystems>
  <Entities>
    <Entity Name="Customer" Namespace="example.com" Version="1.0.0.0">
      <Identifiers>
        <Identifier Name="CustomerIdentifier" TypeName="System.Int32" />
      </Identifiers>
      <Methods>
        <Method Name="GetCustomer">

```

```

        <Properties>
            <!-- sp_GetCustomer is the name of the stored procedure that implements this
method. -->
            <Property Name="RdbCommandText"
Type="System.String">sp_GetCustomer</Property>
            <!-- Using stored procedures is a best practice when connecting to database
systems. -->
            <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
        </Properties>
        <Parameters>
            <!-- The parameter name @CustomerId as expected by the stored procedure. -->
            <Parameter Name="@CustomerId" Direction="In">
                <!-- The IdentifierName attribute is required here. -->
                <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerId" />
            </Parameter>
            <Parameter Name="Customers" Direction="Return">
                <!-- This SQL command returns a result set containing precisely one row, but
it is still wrapped by a data reader and appears as a collection. -->
                <TypeDescriptor Name="CustomerDataReader"
TypeName="System.Data.SqlClient.SqlDataReader, System.Data, Version=2.0.0.0, Culture=neutral,
PublicKeyToken=b77a5c561934e089" IsCollection="true">
                    <TypeDescriptors>
                        <!-- This is a data record corresponding to a single row of the result
set. -->
                        <TypeDescriptor Name="Customer" TypeName="System.Data.IDataRecord,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">
                            <TypeDescriptors>
                                <!-- The IdentifierName attribute is required here to associate the
field with the Identifier. -->
                                <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerId" />
                                <TypeDescriptor Name="FirstName" TypeName="System.String" />
                                <TypeDescriptor Name="LastName" TypeName="System.String" />
                            </TypeDescriptors>
                        </TypeDescriptor>
                    </TypeDescriptors>
                </Parameter>
            </Parameters>
            <MethodInstances>
                <!-- The ReturnParameterName and ReturnPropertyDescriptor are pointing to the
data record to be returned. The result set that is wrapping it is not important and can be
ignored when processing results. -->
                <MethodInstance Name="GetCustomer" Type="SpecificFinder"
ReturnParameterName="Customers" ReturnPropertyDescriptorName="Customer" />
            </MethodInstances>
        </Method>
    </Methods>
</Entity>
</Entities>
</LobSystem>
</LobSystems>
</Model>

```

3.2 DotNetAssembly Model

This is an example of a simple model of an LOB system of type DotNetAssembly. It demonstrates how to use the Class property to configure connection to the business logic module.

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<Model Name="ExampleApplicationDefinition"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <LobSystems>
    <LobSystem Name="ExampleCRM" Type="DotNetAssembly">
      <LobSystemInstances>
        <LobSystemInstance Name="ExampleServer" />
      </LobSystemInstances>
      <Entities>
        <Entity Name="Customer" Namespace="example.com" Version="1.0.0.0">
          <Properties>
            <Property Name="Class" Type="System.String">ExampleCrmNamespace.Customer,
ExampleCRM</Property>
          </Properties>
          <Identifiers>
            <Identifier Name="CustomerIdentifier" TypeName="System.Int32" />
          </Identifiers>
          <Methods>
            <Method Name="GetCustomers">
              <Parameters>
                <Parameter Name="CustomerId" Direction="In">
                  <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                </Parameter>
                <Parameter Name="Customers" Direction="Return">
                  <TypeDescriptor Name="CustomerArray"
TypeName="ExampleCrmNamespace.Customer[], ExampleCRM" IsCollection="true">
                    <TypeDescriptors>
                      <TypeDescriptor Name="Customer" TypeName="ExampleCrmNamespace.Customer,
ExampleCRM">
                        <TypeDescriptors>
                          <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                          <TypeDescriptor Name="FirstName" TypeName="System.String" />
                          <TypeDescriptor Name="LastName" TypeName="System.String" />
                        </TypeDescriptors>
                      </TypeDescriptor>
                    </TypeDescriptors>
                  </TypeDescriptor>
                </Parameter>
              </Parameters>
              <MethodInstances>
                <MethodInstance Name="GetCustomer" Type="SpecificFinder"
ReturnParameterName="Customers" ReturnTypeDescriptorName="Customer" />
              </MethodInstances>
            </Method>
          </Methods>
        </Entity>
      </Entities>
    </LobSystem>
  </LobSystems>
</Model>
```

3.3 Web Service Model

This is an example of a simple model of an LOB system of type Web Service. It demonstrates how to use a LobSystem of type "Wcf" and a set of LobSystem and LobSystemInstance properties to configure connection to a web service. [<44>](#)

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<Model Name="ExampleApplicationDefinition"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <LobSystems>
    <LobSystem Name="ExampleCRM" Type="Wcf">
      <Properties>
        <Property Name="WcfMexDiscoMode" Type="System.String">Disco</Property>
        <Property Name="WcfMexDocumentUrl"
Type="System.String">http://example.org/?wsdl</Property>
        <Property Name="WcfProxyNamespace"
Type="System.String">ExampleCrmNamespace</Property>
        <Property Name="WsdIFetchAuthenticationMode"
Type="System.String">PassThrough</Property>
      </Properties>
      <LobSystemInstances>
        <LobSystemInstance Name="ExampleServer">
          <Properties>
            <Property Name="WcfAuthenticationMode"
Type="System.String">PassThrough</Property>
            <Property Name="WcfEndpointAddress"
Type="System.String">http://example.org</Property>
          </Properties>
        </LobSystemInstance>
      </LobSystemInstances>
      <Entities>
        <Entity Name="Customer" Namespace="example.com" Version="1.0.0.0">
          <Identifiers>
            <Identifier Name="CustomerId" TypeName="System.Int32" />
          </Identifiers>
          <Methods>
            <Method Name="GetCustomers">
              <Parameters>
                <Parameter Name="CustomerId" Direction="In">
                  <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerId" />
                </Parameter>
                <Parameter Name="Customers" Direction="Return">
                  <TypeDescriptor Name="CustomerArray"
TypeName="ExampleCrmNamespace.Customer[], ExampleCRM" IsCollection="true">
                    <TypeDescriptor Name="Customer" TypeName="ExampleCrmNamespace.Customer,
ExampleCRM">
                      <TypeDescriptors>
                        <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerId" />
                        <TypeDescriptor Name="FirstName" TypeName="System.String" />
                        <TypeDescriptor Name="LastName" TypeName="System.String" />
                      </TypeDescriptors>
                    </TypeDescriptor>
                  </TypeDescriptors>
                </Parameter>
              </Parameters>
            </MethodInstances>
          </Method>
        </Entity>
      </Entities>
    </LobSystem>
  </LobSystems>
</Model>
```

```

        <MethodInstance Name="GetCustomer" Type="SpecificFinder"
ReturnParameterName="Customers" ReturnPropertyDescriptorName="Customer" />
    </MethodInstances>
</Method>
</Methods>
</Entity>
</Entities>
</LobSystem>
</LobSystems>
</Model>

```

3.4 Model Resources

This is an example of model resource file. It can be used to extend any of the previous sample model files with permissions and localized names.

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<Model Name="ExampleApplicationDefinition"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <AccessControlList>
    <AccessControlEntry Principal="NT AUTHORITY\Authenticated Users">
      <Right BdcRight="Edit" />
      <Right BdcRight="Execute" />
      <Right BdcRight="SetPermissions" />
      <Right BdcRight="SelectableInClients" />
    </AccessControlEntry>
  </AccessControlList>
  <LobSystems>
    <LobSystem Name="ExampleCRM">
      <AccessControlList>
        <AccessControlEntry Principal="NT AUTHORITY\Authenticated Users">
          <Right BdcRight="Edit" />
          <Right BdcRight="Execute" />
          <Right BdcRight="SetPermissions" />
          <Right BdcRight="SelectableInClients" />
        </AccessControlEntry>
      </AccessControlList>
      <Entities>
        <Entity Name="Customer" Namespace="example.com" Version="1.0.0.0">
          <LocalizedDisplayNames>
            <LocalizedDisplayName LCID="2058">Cliente</LocalizedDisplayName>
            <LocalizedDisplayName LCID="1033">Customer</LocalizedDisplayName>
          </LocalizedDisplayNames>
          <AccessControlList>
            <AccessControlEntry Principal="NT AUTHORITY\Authenticated Users">
              <Right BdcRight="Edit" />
              <Right BdcRight="Execute" />
              <Right BdcRight="SetPermissions" />
              <Right BdcRight="SelectableInClients" />
            </AccessControlEntry>
          </AccessControlList>
          <Methods>
            <Method Name="GetCustomers">
              <MethodInstances>
                <MethodInstance Name="GetCustomer">
                  <AccessControlList>
                    <AccessControlEntry Principal="NT AUTHORITY\Authenticated Users">

```

```

        <Right BdcRight="Execute" />
        <Right BdcRight="Edit" />
        <Right BdcRight="SetPermissions" />
        <Right BdcRight="SelectableInClients" />
    </AccessControlEntry>
</AccessControlList>
</MethodInstance>
</MethodInstances>
</Method>
</Methods>
</Entity>
</Entities>
</LobSystem>
</LobSystems>
</Model>

```

3.5 Finders

This is an example of a model of an LOB system of type **Database** that uses filters to restrict the number of entity instances returned by a finder. It demonstrates how to associate filters to method parameters, how to reuse the same method for multiple method instances and how to annotate type descriptors with commonly used properties.

```

<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<Model Name="ExampleApplicationDefinition"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <LobSystems>
    <LobSystem Name="ExampleCRM" Type="Database">
      <Properties>
        <Property Name="WildcardCharacter" Type="System.String">%</Property>
      </Properties>
      <LobSystemInstances>
        <LobSystemInstance Name="ExampleServer">
          <Properties>
            <Property Name="AuthenticationMode" Type="System.String">PassThrough</Property>
            <Property Name="RdbConnection Data Source"
Type="System.String">(local)\ExampleSQL</Property>
            <Property Name="RdbConnection Initial Catalog"
Type="System.String">ExampleDB</Property>
            <Property Name="RdbConnection Integrated Security"
Type="System.String">SSPI</Property>
          </Properties>
        </LobSystemInstance>
      </LobSystemInstances>
      <Entities>
        <Entity Name="Customer" Namespace="example.com" Version="1.0.0.0">
          <Identifiers>
            <Identifier Name="CustomerIdentifier" TypeName="System.Int32" />
          </Identifiers>
          <Methods>
            <Method Name="GetCustomers">
              <Properties>
                <Property Name="RdbCommandType"
Type="System.Data.CommandType">Text</Property>
                <Property Name="RdbCommandText" Type="System.String">
                  <![CDATA[
                    SET ROWCOUNT @MaxCustomers;

```

```

        IF @CustomerIdentifier = '0'
            SELECT ID, FirstName, LastName, StreetAddress, City, ZipCode, Telephone,
LastChanged FROM Customers
        ELSE
            SELECT ID, FirstName, LastName, StreetAddress, City, ZipCode, Telephone,
LastChanged FROM Customers WHERE ID = @CustomerId;
        SET ROWCOUNT 0
    ]]>
</Property>
</Properties>
<FilterDescriptors>
    <FilterDescriptor Name="CustomerIdentifierFilter" Type="Comparison" />
    <FilterDescriptor Name="MaxCustomers" Type="Limit" />
</FilterDescriptors>
<Parameters>
    <Parameter Name="@CustomerId" Direction="In">
        <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" AssociatedFilter="CustomerIdentifierFilter">
            <DefaultValues>
                <DefaultValue MethodInstanceName="GetCustomers"
Type="System.Int32">0</DefaultValue>
            </DefaultValues>
        </TypeDescriptor>
    </Parameter>
    <Parameter Name="MaxCustomers" Direction="In">
        <TypeDescriptor Name="MaxCustomers" TypeName="System.Int32"
AssociatedFilter="MaxCustomers">
            <DefaultValues>
                <DefaultValue MethodInstanceName="GetCustomers"
Type="System.Int32">100</DefaultValue>
            </DefaultValues>
        </TypeDescriptor>
    </Parameter>
    <Parameter Name="Customers" Direction="Return">
        <TypeDescriptor Name="CustomerDataReader"
TypeName="System.Data.SqlClient.SqlDataReader, System.Data, Version=2.0.0.0, Culture=neutral,
PublicKeyToken=b77a5c561934e089" IsCollection="true">
            <TypeDescriptors>
                <TypeDescriptor Name="Customer" TypeName="System.Data.IDataRecord,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">
                    <TypeDescriptors>
                        <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                        <TypeDescriptor Name="FirstName" TypeName="System.String">
                            <Properties>
                                <Property Name="ShowInPicker"
Type="System.Boolean">true</Property>
                                <Property Name="Size" Type="System.Int32">128</Property>
                            </Properties>
                        </TypeDescriptor>
                        <TypeDescriptor Name="LastName" TypeName="System.String">
                            <Properties>
                                <Property Name="ShowInPicker"
Type="System.Boolean">true</Property>
                                <Property Name="Size" Type="System.Int32">60</Property>
                            </Properties>
                        </TypeDescriptor>
                        <TypeDescriptor Name="StreetAddress" TypeName="System.String">
                            <Properties>
                                <Property Name="Size" Type="System.Int32">128</Property>

```



```

        </Properties>
    </TypeDescriptor>
    <TypeDescriptor Name="City" TypeName="System.String">
        <Properties>
            <Property Name="Size" Type="System.Int32">128</Property>
        </Properties>
    </TypeDescriptor>
    <TypeDescriptor Name="ZipCode" TypeName="System.String">
        <Properties>
            <Property Name="Size" Type="System.Int32">128</Property>
        </Properties>
    </TypeDescriptor>
    <TypeDescriptor Name="Telephone" TypeName="System.String">
        <Properties>
            <Property Name="HideInListWebPartByDefault"
Type="System.Boolean">true</Property>
            <Property Name="HideInItemWebPartByDefault"
Type="System.Boolean">true</Property>
            <Property Name="Size" Type="System.Int32">128</Property>
        </Properties>
    </TypeDescriptor>
    <TypeDescriptor Name="LastChanged" TypeName="System.DateTime">
        <Properties>
            <Property Name="HideInListWebPartByDefault"
Type="System.Boolean">true</Property>
            <Property Name="HideInItemWebPartByDefault"
Type="System.Boolean">true</Property>
        </Properties>
        <Interpretation>
            <NormalizeDateTime LobDateTimeMode="UTC" />
        </Interpretation>
    </TypeDescriptor>
</TypeDescriptors>
</TypeDescriptors>
</TypeDescriptor>
</Parameters>
</MethodInstances>
    <MethodInstance Name="GetCustomers" Type="Finder"
ReturnParameterName="Customers" />
    <MethodInstance Name="GetCustomer" Type="SpecificFinder"
ReturnParameterName="Customers" ReturnPropertyDescriptorName="Customer" />
</MethodInstances>
</Method>
</Methods>
</Entity>
</Entities>
</LobSystem>
</LobSystems>
</Model>

```

3.6 CRUD

This is an example of a model of an LOB system of type **Database**. It demonstrates how to describe a full set of create, read, update, and delete (CRUD) stereotypes for an entity.

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
```

```

<Model Name="ExampleApplicationDefinition"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <LobSystems>
    <LobSystem Name="ExampleCRM" Type="Database">
      <Properties>
        <Property Name="WildcardCharacter" Type="System.String">%</Property>
      </Properties>
      <LobSystemInstances>
        <LobSystemInstance Name="ExampleServer">
          <Properties>
            <Property Name="AuthenticationMode" Type="System.String">PassThrough</Property>
            <Property Name="RdbConnection Data Source"
Type="System.String">(local)\ExampleSQL</Property>
            <Property Name="RdbConnection Initial Catalog"
Type="System.String">ExampleDB</Property>
            <Property Name="RdbConnection Integrated Security"
Type="System.String">SSPI</Property>
          </Properties>
        </LobSystemInstance>
      </LobSystemInstances>
      <Entities>
        <Entity Name="Customer" Namespace="example.com" Version="1.0.0.0">
          <Identifiers>
            <Identifier Name="CustomerIdentifier" TypeName="System.Int32" />
          </Identifiers>
          <Methods>
            <Method Name="GetCustomers">
              <Properties>
                <Property Name="RdbCommandText"
Type="System.String">sp_GetCustomers</Property>
                <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
              </Properties>
              <Parameters>
                <Parameter Name="@CustomerId" Direction="In">
                  <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                </Parameter>
                <Parameter Name="Customers" Direction="Return">
                  <TypeDescriptor Name="CustomerDataReader"
TypeName="System.Data.SqlClient.SqlDataReader, System.Data, Version=2.0.0.0, Culture=neutral,
PublicKeyToken=b77a5c561934e089" IsCollection="true">
                    <TypeDescriptors>
                      <TypeDescriptor Name="Customer" TypeName="System.Data.IDataRecord,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">
                        <TypeDescriptors>
                          <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                          <TypeDescriptor Name="FirstName" TypeName="System.String" />
                          <TypeDescriptor Name="LastName" TypeName="System.String" />
                          <TypeDescriptor Name="StreetAddress" TypeName="System.String" />
                          <TypeDescriptor Name="City" TypeName="System.String" />
                          <TypeDescriptor Name="ZipCode" TypeName="System.String" />
                          <TypeDescriptor Name="Telephone" TypeName="System.String" />
                          <TypeDescriptor Name="LastChanged" TypeName="System.DateTime" />
                        </TypeDescriptors>
                      </TypeDescriptor>
                    </TypeDescriptors>
                  </TypeDescriptor>
                </Parameter>
              </Parameters>
            </Method>
          </Methods>
        </Entity>
      </Entities>
    </LobSystem>
  </LobSystems>
</Model>

```

```

        </Parameters>
        <MethodInstances>
            <MethodInstance Name="GetCustomer" Type="SpecificFinder"
ReturnParameterName="Customers" ReturnTypeDescriptorName="Customer" />
        </MethodInstances>
    </Method>
    <Method Name="CreateCustomer">
        <Properties>
            <Property Name="RdbCommandText"
Type="System.String">sp_CreateCustomer</Property>
            <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
        </Properties>
        <Parameters>
            <Parameter Name="@FirstName" Direction="In">
                <TypeDescriptor Name="FirstName" TypeName="System.String"
CreatorField="true" />
            </Parameter>
            <Parameter Name="@LastName" Direction="In">
                <TypeDescriptor Name="LastName" TypeName="System.String"
CreatorField="true" />
            </Parameter>
            <Parameter Name="@StreetAddress" Direction="In">
                <TypeDescriptor TypeName="System.String" Name="StreetAddress"
CreatorField="true" />
            </Parameter>
            <Parameter Name="@City" Direction="In">
                <TypeDescriptor TypeName="System.String" Name="City" CreatorField="true" />
            </Parameter>
            <Parameter Name="@ZipCode" Direction="In">
                <TypeDescriptor TypeName="System.String" Name="ZipCode" CreatorField="true"
/>
            </Parameter>
            <Parameter Name="@Telephone" Direction="In">
                <TypeDescriptor TypeName="System.String" Name="Telephone"
CreatorField="true" />
            </Parameter>
            <Parameter Name="Customer" Direction="Return">
                <TypeDescriptor Name="CustomerDataReader"
TypeName="System.Data.SqlClient.SqlDataReader, System.Data, Version=2.0.0.0, Culture=neutral,
PublicKeyToken=b77a5c561934e089">
                    <TypeDescriptors>
                        <TypeDescriptor Name="Customer" TypeName="System.Data.IDataRecord,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">
                            <TypeDescriptors>
                                <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                            </TypeDescriptors>
                        </TypeDescriptor>
                    </TypeDescriptors>
                </Parameter>
            </Parameters>
        <MethodInstances>
            <MethodInstance Name="CreateCustomer" Type="Creator"
ReturnParameterName="Customer" />
        </MethodInstances>
    </Method>
    <Method Name="UpdateCustomer">
        <Properties>

```

```

        <Property Name="RdbCommandText"
Type="System.String">sp_UpdateCustomer</Property>
        <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
    </Properties>
    <Parameters>
        <Parameter Name="@CustomerId" Direction="In">
            <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" UpdaterField="true" />
        </Parameter>
        <Parameter Name="@FirstName" Direction="In">
            <TypeDescriptor Name="FirstName" TypeName="System.String"
UpdaterField="true" />
        </Parameter>
        <Parameter Name="@LastName" Direction="In">
            <TypeDescriptor Name="LastName" TypeName="System.String"
UpdaterField="true" />
        </Parameter>
        <Parameter Name="@StreetAddress" Direction="In">
            <TypeDescriptor Name="StreetAddress" TypeName="System.String"
UpdaterField="true" />
        </Parameter>
        <Parameter Name="@City" Direction="In">
            <TypeDescriptor Name="City" TypeName="System.String" UpdaterField="true" />
        </Parameter>
        <Parameter Name="@ZipCode" Direction="In">
            <TypeDescriptor Name="ZipCode" TypeName="System.String" UpdaterField="true"
/>
        </Parameter>
        <Parameter Name="@Telephone" Direction="In">
            <TypeDescriptor Name="Telephone" TypeName="System.String"
UpdaterField="true" />
        </Parameter>
    </Parameters>
    <MethodInstances>
        <MethodInstance Name="UpdateCustomer" Type="Updater" />
    </MethodInstances>
</Method>
<Method Name="DeleteCustomer">
    <Properties>
        <Property Name="RdbCommandText"
Type="System.String">sp_UpdateCustomer</Property>
        <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
    </Properties>
    <Parameters>
        <Parameter Name="@CustomerId" Direction="In">
            <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
        </Parameter>
    </Parameters>
    <MethodInstances>
        <MethodInstance Name="DeleteCustomer" Type="Deleter" />
    </MethodInstances>
</Method>
</Methods>
</Entity>
</Entities>
</LobSystem>
</LobSystems>

```

```
</Model>
```

3.7 Associations

This is an example of a model of an LOB system of type **Database**. It demonstrates how to describe a relationship between two entities within the same **LobSystem**.

```
<?xml version="1.0" encoding="UTF-8" standalone="yes"?>
<Model Name="ExampleApplicationDefinition"
xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog">
  <LobSystems>
    <LobSystem Name="ExampleCRM" Type="Database">
      <Properties>
        <Property Name="WildcardCharacter" Type="System.String">%</Property>
      </Properties>
      <LobSystemInstances>
        <LobSystemInstance Name="ExampleServer">
          <Properties>
            <Property Name="AuthenticationMode" Type="System.String">PassThrough</Property>
            <Property Name="RdbConnection Data Source"
Type="System.String">(local)\ExampleSQL</Property>
            <Property Name="RdbConnection Initial Catalog"
Type="System.String">ExampleDB</Property>
            <Property Name="RdbConnection Integrated Security"
Type="System.String">SSPI</Property>
          </Properties>
        </LobSystemInstance>
      </LobSystemInstances>
      <Entities>
        <Entity Name="Customer" Namespace="example.com" Version="1.0.0.0">
          <Identifiers>
            <Identifier Name="CustomerIdentifier" TypeName="System.Int32" />
          </Identifiers>
          <Methods>
            <Method Name="GetCustomers">
              <Properties>
                <Property Name="RdbCommandText"
Type="System.String">sp_GetCustomers</Property>
                <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
              </Properties>
              <Parameters>
                <Parameter Name="@CustomerId" Direction="In">
                  <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                </Parameter>
                <Parameter Name="Customers" Direction="Return">
                  <TypeDescriptor Name="CustomerDataReader"
Type="System.Data.SqlClient.SqlDataReader, System.Data, Version=2.0.0.0, Culture=neutral,
PublicKeyToken=b77a5c561934e089" IsCollection="true">
                    <TypeDescriptors>
                      <TypeDescriptor Name="Customer" TypeName="System.Data.IDataRecord,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">
                        <TypeDescriptors>
                          <TypeDescriptor Name="Id" TypeName="System.Int32"
IdentifierName="CustomerIdentifier" />
                          <TypeDescriptor Name="FirstName" TypeName="System.String" />
                          <TypeDescriptor Name="LastName" TypeName="System.String" />
                        </TypeDescriptors>
                      </TypeDescriptor>
                    </TypeDescriptors>
                  </Parameter>
                </Parameters>
            </Method>
          </Methods>
        </Entity>
      </Entities>
    </LobSystem>
  </LobSystems>
</Model>
```

```

        </TypeDescriptors>
    </TypeDescriptor>
</TypeDescriptors>
</TypeDescriptor>
    </Parameter>
</Parameters>
<MethodInstances>
    <MethodInstance Name="GetCustomer" Type="SpecificFinder"
ReturnParameterName="Customers" ReturnPropertyDescriptorName="Customer" />
</MethodInstances>
</Method>
</Methods>
</Entity>
<Entity Namespace="example.com" Name="Order" Version="1.0.0.0">
    <Identifiers>
        <Identifier Name="OrderIdentifier" TypeName="System.Int64" />
    </Identifiers>
    <Methods>
        <Method Name="GetOrders">
            <Properties>
                <Property Name="RdbCommandText" Type="System.String">sp_GetOrders</Property>
                <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
            </Properties>
            <Parameters>
                <Parameter Name="@Id" Direction="In">
                    <PropertyDescriptor Name="Id" TypeName="System.Int64"
IdentifierName="OrderIdentifier" />
                </Parameter>
                <Parameter Name="Orders" Direction="Return">
                    <PropertyDescriptor Name="OrderDataReader" TypeName="System.Data.IDataReader,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089"
IsCollection="true">
                        <TypeDescriptors>
                            <PropertyDescriptor Name="Order" TypeName="System.Data.IDataRecord,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">
                                <TypeDescriptors>
                                    <PropertyDescriptor Name="Id" TypeName="System.Int64"
IdentifierName="OrderIdentifier" />
                                    <PropertyDescriptor Name="CustomerId" TypeName="System.Int32"
IdentifierEntityName="Customer" IdentifierEntityNamespace="example.com"
IdentifierName="CustomerId" ForeignIdentifierAssociationName="GetOrdersForCustomer"
/>
                                    <PropertyDescriptor Name="OrderDate" TypeName="System.DateTime" />
                                </TypeDescriptors>
                            </PropertyDescriptor>
                        </TypeDescriptors>
                    </PropertyDescriptor>
                </Parameter>
            </Parameters>
            <MethodInstances>
                <MethodInstance Name="GetOrder" Type="SpecificFinder"
ReturnParameterName="Orders" ReturnPropertyDescriptorName="Order" />
            </MethodInstances>
        </Method>
        <Method Name="GetOrdersForCustomer">
            <Properties>
                <Property Name="RdbCommandText" Type="System.String">sp_GetOrders</Property>
                <Property Name="RdbCommandType" Type="System.Data.CommandType, System.Data,
Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089">StoredProcedure</Property>
            </Properties>
        </Method>
    </Methods>
</Entity>

```

```

    </Properties>
    <Parameters>
      <Parameter Direction="In" Name="@CustomerIdentifier">
        <TypeDescriptor Name="@CustomerIdentifier" TypeName="System.Int32"
IdentifierEntityName="Customer" IdentifierEntityNamespace="example.com"
IdentifierName="CustomerIdentifier" ForeignIdentifierAssociationName="GetOrdersForCustomer"
/>
      </Parameter>
      <Parameter Name="Orders" Direction="Return">
        <TypeDescriptor Name="OrderDataReader" TypeName="System.Data.IDataReader,
System.Data, Version=2.0.0.0, Culture=neutral, PublicKeyToken=b77a5c561934e089"
IsCollection="true">
          <TypeDescriptors>
            <TypeDescriptor Name="OrderDataRecord"
TypeName="System.Data.IDataRecord, System.Data, Version=2.0.0.0, Culture=neutral,
PublicKeyToken=b77a5c561934e089">
              <TypeDescriptors>
                <TypeDescriptor Name="Id" TypeName="System.Int64"
IdentifierName="OrderIdentifier" />
                <TypeDescriptor Name="CustomerId" TypeName="System.Int32"
IdentifierEntityName="Customer" IdentifierEntityNamespace="example.com"
IdentifierName="CustomerIdentifier" ForeignIdentifierAssociationName="GetOrdersForCustomer"
/>
                <TypeDescriptor Name="OrderDate" TypeName="System.DateTime" />
              </TypeDescriptors>
            </TypeDescriptor>
          </TypeDescriptors>
        </Parameter>
      </Parameters>
      <MethodInstances>
        <Association Name="GetOrdersForCustomer" Type="AssociationNavigator"
ReturnParameterName="Orders">
          <SourceEntity Name="Customer" Namespace="example.com" />
          <DestinationEntity Name="Order" Namespace="example.com" />
        </Association>
      </MethodInstances>
    </Method>
  </Methods>
</Entity>
</Entities>
</LobSystem>
</LobSystems>
</Model>

```

4 Security Considerations

The **proxy** attribute of the **LobSystem** element (section [2.1.4.7](#)) contain the binary representation of a Business Logic Module. When loading modules, verification is recommended to ensure the module origin is trusted.

Preliminary

5 Appendix A: Full XML Schemas

For ease of implementation, this section provides the full XML schemas for the Business Data Connectivity Model File Format and the Business Data Connectivity Model Resource File Format, as specified in section 2.

5.1 <http://schemas.microsoft.com/windows/2007/BusinessDataCatalog>

```
<xs:schema xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:bdc="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog"
targetNamespace="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog"
elementFormDefault="qualified">
  <xs:element name="Model" type="bdc:Model"/>
  <xs:complexType name="Model">
    <xs:complexContent>
      <xs:extension base="bdc:IndividuallySecurableMetadataObject">
        <xs:sequence>
          <xs:element name="LobSystems" type="bdc:LobSystems" minOccurs="0" maxOccurs="1">
            <xs:unique name="LobSystemNameKey">
              <xs:selector xpath="*/>
              <xs:field xpath="@Name"/>
            </xs:unique>
          </xs:element>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="LobSystems">
    <xs:sequence>
      <xs:element name="LobSystem" type="bdc:LobSystem" minOccurs="1" maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="MetadataObject" abstract="true">
    <xs:sequence>
      <xs:element name="LocalizedDisplayNames" type="bdc:LocalizedDisplayNames" minOccurs="0"
maxOccurs="1">
        <xs:unique name="LocalizedDisplayNameLCIDKey">
          <xs:selector xpath="*/>
          <xs:field xpath="@LCID"/>
        </xs:unique>
      </xs:element>
      <xs:element name="Properties" type="bdc:Properties" minOccurs="0" maxOccurs="1">
        <xs:unique name="PropertyNameKey">
          <xs:selector xpath="*/>
          <xs:field xpath="@Name"/>
        </xs:unique>
      </xs:element>
    </xs:sequence>
    <xs:attribute name="Name" type="bdc:NameString" use="required"/>
    <xs:attribute name="DefaultDisplayName" type="bdc:NameString"/>
    <xs:attribute name="IsCached" type="xs:boolean" default="true"/>
  </xs:complexType>
  <xs:complexType name="IndividuallySecurableMetadataObject" abstract="true">
    <xs:complexContent>
      <xs:extension base="bdc:MetadataObject">
        <xs:sequence>
```

```

        <xs:element name="AccessControlList" type="bdc:AccessControlList" minOccurs="0"
maxOccurs="1"/>
    </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="LocalizedDisplayNames">
    <xs:sequence>
        <xs:element name="LocalizedDisplayName" type="bdc:LocalizedDisplayName" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="LocalizedDisplayName" mixed="true">
    <xs:attribute name="LCID" type="xs:integer" use="required"/>
</xs:complexType>
<xs:complexType name="LobSystem">
    <xs:complexContent>
        <xs:extension base="bdc:IndividuallySecurableMetadataObject">
            <xs:sequence>
                <xs:element name="Proxy" type="xs:string" minOccurs="0" maxOccurs="1"/>
                <xs:element name="LobSystemInstances" type="bdc:LobSystemInstances" minOccurs="0"
maxOccurs="1">
                    <xs:unique name="LobSystemInstanceNameKey">
                        <xs:selector xpath="*/">
                        <xs:field xpath="@Name"/>
                    </xs:unique>
                </xs:element>
                <xs:element name="Entities" type="bdc:Entities" minOccurs="0" maxOccurs="1">
                    <xs:unique name="EntityNameNamespaceVersionKey">
                        <xs:selector xpath="*/">
                        <xs:field xpath="@Name"/>
                        <xs:field xpath="@Namespace"/>
                        <xs:field xpath="@Version"/>
                    </xs:unique>
                </xs:element>
            </xs:sequence>
            <xs:attribute name="Type" type="bdc:LobSystemType" use="required"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:simpleType name="LobSystemType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="Database"/>
        <xs:enumeration value="DotNetAssembly"/>
        <xs:enumeration value="Wcf"/>
        <xs:enumeration value="WebService"/>
        <xs:enumeration value="Custom"/>
        <xs:enumeration value="OData"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="LobSystemInstances">
    <xs:sequence>
        <xs:element name="LobSystemInstance" type="bdc:LobSystemInstance" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="LobSystemInstance">
    <xs:complexContent>
        <xs:extension base="bdc:MetadataObject"/>
    </xs:complexContent>

```

```

    </xs:complexContent>
  </xs:complexType>
<xs:complexType name="Entities">
  <xs:sequence>
    <xs:element name="Entity" type="bdc:Entity" minOccurs="1" maxOccurs="unbounded">
      <xs:unique name="MethodInstanceNameKey">
        <xs:selector xpath="./bdc:MethodInstances/*"/>
        <xs:field xpath="@Name"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Entity">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="Identifiers" type="bdc:Identifiers" minOccurs="0">
          <xs:unique name="IdentifierNameKey">
            <xs:selector xpath="*"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="Methods" type="bdc:Methods" minOccurs="0">
          <xs:unique name="MethodNameKey">
            <xs:selector xpath="*"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="AssociationGroups" type="bdc:AssociationGroups" minOccurs="0">
          <xs:unique name="AssociationGroupNameKey">
            <xs:selector xpath="*"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="Actions" type="bdc:Actions" minOccurs="0">
          <xs:unique name="ActionNameKey">
            <xs:selector xpath="*"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="Namespace" type="bdc:NameString" use="required"/>
      <xs:attribute name="Version" type="bdc:VersionString" use="required"/>
      <xs:attribute name="EstimatedInstanceCount" type="bdc:InstanceCount"
default="10000"/>
      <xs:attribute name="DefaultOperationMode" type="bdc:OperationModeType"
default="Default" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="OperationModeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Online"/>
    <xs:enumeration value="Cached"/>
    <xs:enumeration value="Offline"/>
    <xs:enumeration value="Default"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="AssociationGroups">

```

```

    <xs:sequence>
      <xs:element name="AssociationGroup" type="bdc:AssociationGroup" minOccurs="1"
maxOccurs="unbounded">
        <xs:unique name="AssociationReferenceAssociationNameEntityNameEntityNamespaceKey">
          <xs:selector xpath="*" />
          <xs:field xpath="@EntityNamespace" />
          <xs:field xpath="@EntityName" />
          <xs:field xpath="@AssociationName" />
        </xs:unique>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="AssociationGroup">
    <xs:complexContent>
      <xs:extension base="bdc:MetadataObject">
        <xs:sequence>
          <xs:element name="AssociationReference" type="bdc:AssociationReference"
minOccurs="1" maxOccurs="unbounded" />
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:complexType name="AssociationReference">
    <xs:attribute name="EntityNamespace" type="bdc:NameString" use="optional" />
    <xs:attribute name="EntityName" type="bdc:NameString" use="optional" />
    <xs:attribute name="AssociationName" type="bdc:NameString" use="required" />
    <xs:attribute name="Reverse" type="xs:boolean" use="optional" default="false" />
  </xs:complexType>
  <xs:complexType name="Identifiers">
    <xs:sequence>
      <xs:element name="Identifier" type="bdc:Identifier" minOccurs="1"
maxOccurs="unbounded" />
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="Identifier">
    <xs:complexContent>
      <xs:extension base="bdc:MetadataObject">
        <xs:attribute name="TypeName" type="bdc:IdentifierType" use="required" />
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>
  <xs:simpleType name="IdentifierType">
    <xs:restriction base="xs:string">
      <xs:enumeration value="System.Boolean" />
      <xs:enumeration value="System.Byte" />
      <xs:enumeration value="System.Char" />
      <xs:enumeration value="System.DateTime" />
      <xs:enumeration value="System.Decimal" />
      <xs:enumeration value="System.Double" />
      <xs:enumeration value="System.Guid" />
      <xs:enumeration value="System.Int16" />
      <xs:enumeration value="System.Int32" />
      <xs:enumeration value="System.Int64" />
      <xs:enumeration value="System.SByte" />
      <xs:enumeration value="System.Single" />
      <xs:enumeration value="System.String" />
      <xs:enumeration value="System.TimeSpan" />
      <xs:enumeration value="System.UInt16" />
      <xs:enumeration value="System.UInt32" />
    </xs:restriction>
  </xs:simpleType>

```

```

    <xs:enumeration value="System.UInt64"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="Methods">
  <xs:sequence>
    <xs:element name="Method" type="bdc:Method" minOccurs="1" maxOccurs="unbounded">
      <xs:key name="ParameterNameKey">
        <xs:selector xpath="//bdc:Parameter"/>
        <xs:field xpath="@Name"/>
      </xs:key>
      <xs:keyref name="ParameterNameRef" refer="bdc:ParameterNameKey">
        <xs:selector xpath="//bdc:MethodInstances/*"/>
        <xs:field xpath="@ReturnParameterName"/>
      </xs:keyref>
      <xs:key name="MethodMethodNameKey">
        <xs:selector xpath="//bdc:MethodInstances/*"/>
        <xs:field xpath="@Name"/>
      </xs:key>
      <xs:keyref name="DefaultValueMethodNameRef"
refer="bdc:MethodMethodNameKey">
        <xs:selector xpath="//bdc:DefaultValue"/>
        <xs:field xpath="@MethodName"/>
      </xs:keyref>
    </xs:element>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Method">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="FilterDescriptors" type="bdc:FilterDescriptors" minOccurs="0"
maxOccurs="1">
          <xs:unique name="FilterDescriptorNameKey">
            <xs:selector xpath="*"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="Parameters" type="bdc:Parameters" minOccurs="0" maxOccurs="1"/>
        <xs:element name="MethodInstances" type="bdc:MethodInstances" minOccurs="0"
maxOccurs="1"/>
      </xs:sequence>
      <xs:attribute name="IsStatic" type="xs:boolean" default="true"/>
      <xs:attribute name="LobName" type="bdc:NameString" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="FilterDescriptors">
  <xs:sequence>
    <xs:element name="FilterDescriptor" type="bdc:FilterDescriptor" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="FilterDescriptor">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:attribute name="Type" type="bdc:FilterDescriptorType" use="required"/>
      <xs:attribute name="FilterField" type="bdc:NameString" use="optional"/>
    </xs:extension>
  </xs:complexContent>

```

```

</xs:complexType>
<xs:simpleType name="FilterDescriptorType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Limit"/>
    <xs:enumeration value="PageNumber"/>
    <xs:enumeration value="Wildcard"/>
    <xs:enumeration value="UserContext"/>
    <xs:enumeration value="UserCulture"/>
    <xs:enumeration value="Username"/>
    <xs:enumeration value="Password"/>
    <xs:enumeration value="LastId"/>
    <xs:enumeration value="SsoTicket"/>
    <xs:enumeration value="UserProfile"/>
    <xs:enumeration value="Comparison"/>
    <xs:enumeration value="Timestamp"/>
    <xs:enumeration value="Input"/>
    <xs:enumeration value="Output"/>
    <xs:enumeration value="InputOutput"/>
    <xs:enumeration value="Batching"/>
    <xs:enumeration value="BatchingTermination"/>
    <xs:enumeration value="ActivityId"/>
    <xs:enumeration value="Sorting"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="MethodInstances">
  <xs:choice minOccurs="1" maxOccurs="unbounded">
    <xs:element name="Association" type="bcd:Association">
      <xs:unique name="SourceEntityNameNamespaceKey">
        <xs:selector xpath="bcd:SourceEntity"/>
        <xs:field xpath="@Name"/>
        <xs:field xpath="@Namespace"/>
      </xs:unique>
    </xs:element>
    <xs:element name="MethodInstance" type="bcd:MethodInstance"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="MethodInstance">
  <xs:complexContent>
    <xs:extension base="bcd:IndividuallySecurableMetadataObject">
      <xs:attribute name="Type" type="bcd:MethodInstanceType" use="required"/>
      <xs:attribute name="Default" type="xs:boolean" use="optional" default="false"/>
      <xs:attribute name="ReturnParameterName" type="bcd:NameString" use="optional"/>
      <xs:attribute name="ReturnTypeDescriptorName" type="bcd:NameString" use="optional"/>
      <xs:attribute name="ReturnTypeDescriptorLevel" type="bcd:ReturnTypeDescriptorLevel"
use="optional"/>
      <xs:attribute name="ReturnTypeDescriptorPath" type="xs:string" use="optional"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="MethodInstanceType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="Finder"/>
    <xs:enumeration value="SpecificFinder"/>
    <xs:enumeration value="GenericInvoker"/>
    <xs:enumeration value="IdEnumerator"/>
    <xs:enumeration value="ChangedIdEnumerator"/>
    <xs:enumeration value="DeletedIdEnumerator"/>
    <xs:enumeration value="Scalar"/>
    <xs:enumeration value="AccessChecker"/>
  </xs:restriction>

```

```

<xs:enumeration value="AssociationNavigator"/>
<xs:enumeration value="Associator"/>
<xs:enumeration value="Disassociator"/>
<xs:enumeration value="Creator"/>
<xs:enumeration value="Deleter"/>
<xs:enumeration value="Updater"/>
<xs:enumeration value="StreamAccessor"/>
<xs:enumeration value="BinarySecurityDescriptorAccessor"/>
<xs:enumeration value="BulkSpecificFinder"/>
<xs:enumeration value="BulkAssociatedIdEnumerator"/>
<xs:enumeration value="BulkAssociationNavigator"/>
<xs:enumeration value="BulkIdEnumerator"/>
<xs:enumeration value="EventSubscriber"/>
<xs:enumeration value="EventUnsubscriber"/>
</xs:restriction>
</xs:simpleType>
<xs:complexType name="Parameters">
  <xs:sequence>
    <xs:element name="Parameter" type="bcd:Parameter" minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Parameter">
  <xs:complexContent>
    <xs:extension base="bcd:MetadataObject">
      <xs:sequence>
        <xs:element name="TypeDescriptor" type="bcd:TypeDescriptor"/>
      </xs:sequence>
      <xs:attribute name="Direction" type="bcd:ParameterDirection" use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:simpleType name="ParameterDirection">
  <xs:restriction base="xs:string">
    <xs:enumeration value="In"/>
    <xs:enumeration value="Out"/>
    <xs:enumeration value="InOut"/>
    <xs:enumeration value="Return"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="TypeDescriptor">
  <xs:complexContent>
    <xs:extension base="bcd:MetadataObject">
      <xs:sequence>
        <xs:element name="Interpretation" type="bcd:Interpretation" minOccurs="0"/>
        <xs:element name="DefaultValues" type="bcd:DefaultValues" minOccurs="0">
          <xs:unique name="DefaultValueMethodInstanceNameKey">
            <xs:selector xpath="*/>
            <xs:field xpath="@MethodInstanceName"/>
          </xs:unique>
        </xs:element>
        <xs:element name="TypeDescriptors" type="bcd:TypeDescriptors" minOccurs="0">
          <xs:unique name="TypeDescriptorNameKey">
            <xs:selector xpath="*/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
      </xs:sequence>
      <xs:attribute name="TypeName" type="bcd:TypeDescriptorTypeNameString"
use="required"/>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

    <xs:attribute name="LobName" type="bdc:NameString" use="optional"/>
    <xs:attribute name="IdentifierEntityNamespace" type="bdc:NameString" use="optional"/>
    <xs:attribute name="IdentifierEntityName" type="bdc:NameString" use="optional"/>
    <xs:attribute name="IdentifierName" type="bdc:NameString" use="optional"/>
    <xs:attribute name="ForeignIdentifierAssociationName" type="bdc:NameString"
use="optional"/>
    <xs:attribute name="ForeignIdentifierAssociationEntityName" type="bdc:NameString"
use="optional"/>
    <xs:attribute name="ForeignIdentifierAssociationEntityNamespace"
type="bdc:NameString" use="optional"/>
    <xs:attribute name="AssociatedFilter" type="bdc:NameString" use="optional"/>
    <xs:attribute name="IsCollection" type="xs:boolean" default="false" use="optional"/>
    <xs:attribute name="ReadOnly" type="xs:boolean" default="false" use="optional"/>
    <xs:attribute name="CreatorField" type="xs:boolean" default="false" use="optional"/>
    <xs:attribute name="UpdaterField" type="xs:boolean" default="false" use="optional"/>
    <xs:attribute name="PreUpdaterField" type="xs:boolean" default="false"
use="optional"/>
    <xs:attribute name="Significant" type="xs:boolean" default="true" use="optional"/>
    <xs:attribute name="IsSortInput" type="xs:boolean" default="false" use="optional"/>
  </xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="DefaultValues">
  <xs:sequence>
    <xs:element name="DefaultValue" type="bdc:DefaultValue" minOccurs="1"
maxOccurs="unbounded" nillable="true"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="DefaultValue" mixed="true">
  <xs:attribute name="MethodName" type="bdc:NameString" use="required"/>
  <xs:attribute name="Type" type="bdc:TypeDescriptorTypeNameString" use="required"/>
</xs:complexType>
<xs:complexType name="Interpretation">
  <xs:choice minOccurs="1" maxOccurs="unbounded">
    <xs:element name="ConvertType" type="bdc:ConvertType"/>
    <xs:element name="NormalizeDateTime" type="bdc:NormalizeDateTime"/>
    <xs:element name="NormalizeString" type="bdc:NormalizeString"/>
  </xs:choice>
</xs:complexType>
<xs:complexType name="ConvertType">
  <xs:attribute name="LOBType" type="bdc:TypeNameString" use="required"/>
  <xs:attribute name="BDCType" type="bdc:TypeNameString" use="required"/>
  <xs:attribute name="LOBLocale" type="bdc:TypeNameString" use="optional"/>
</xs:complexType>
<xs:simpleType name="StringNormalizeMode">
  <xs:restriction base="xs:string">
    <xs:enumeration value="NoChange"/>
    <xs:enumeration value="NormalizeToEmptyString"/>
    <xs:enumeration value="NormalizeToNull"/>
  </xs:restriction>
</xs:simpleType>
<xs:complexType name="NormalizeString">
  <xs:attribute name="FromLOB" type="bdc:StringNormalizeMode" use="required"/>
  <xs:attribute name="ToLOB" type="bdc:StringNormalizeMode" use="required"/>
</xs:complexType>
<xs:simpleType name="LobDateTimeMode">
  <xs:restriction base="xs:string">
    <xs:enumeration value="UTC"/>
    <xs:enumeration value="Local"/>
  </xs:restriction>

```



```

        <xs:enumeration value="Unspecified"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="NormalizeDateTime">
    <xs:attribute name="LobDateTimeMode" type="bdc:LobDateTimeMode" use="required"/>
</xs:complexType>
<xs:complexType name="TypeDescriptors">
    <xs:sequence>
        <xs:element name="TypeDescriptor" type="bdc:TypeDescriptor" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Actions">
    <xs:sequence>
        <xs:element name="Action" type="bdc:Action" minOccurs="1" maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Action">
    <xs:complexContent>
        <xs:extension base="bdc:MetadataObject">
            <xs:sequence>
                <xs:element name="ActionParameters" type="bdc:ActionParameters" minOccurs="0">
                    <xs:unique name="ActionParameterNameKey">
                        <xs:selector xpath="*/>
                        <xs:field xpath="@Name"/>
                    </xs:unique>
                    <xs:unique name="ActionParameterIndexKey">
                        <xs:selector xpath="*/>
                        <xs:field xpath="@Index"/>
                    </xs:unique>
                </xs:element>
            </xs:sequence>
            <xs:attribute name="Position" type="bdc:ActionPosition" use="required"/>
            <xs:attribute name="IsOpenedInNewWindow" type="xs:boolean" default="false"/>
            <xs:attribute name="Url" type="bdc:UrlString" use="required"/>
            <xs:attribute name="ImageUrl" type="bdc:UrlString"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="ActionParameters">
    <xs:sequence>
        <xs:element name="ActionParameter" type="bdc:ActionParameter" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="ActionParameter">
    <xs:complexContent>
        <xs:extension base="bdc:MetadataObject">
            <xs:attribute name="Index" type="bdc:Ordinal" use="required"/>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="Association">
    <xs:complexContent>
        <xs:extension base="bdc:MethodInstance">
            <xs:sequence>
                <xs:element name="SourceEntity" type="bdc:SourceEntity" minOccurs="1"
maxOccurs="unbounded"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

```

        <xs:element name="DestinationEntity" type="bdc:DestinationEntity" minOccurs="1"
maxOccurs="1"/>
    </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="SourceEntity">
    <xs:attribute name="Namespace" type="bdc:NameString" use="required"/>
    <xs:attribute name="Name" type="bdc:NameString" use="required"/>
</xs:complexType>
<xs:complexType name="DestinationEntity">
    <xs:attribute name="Namespace" type="bdc:NameString" use="required"/>
    <xs:attribute name="Name" type="bdc:NameString" use="required"/>
</xs:complexType>
<xs:complexType name="Property" mixed="true">
    <xs:attribute name="Name" type="bdc:NameString" use="required"/>
    <xs:attribute name="Type" type="bdc:TypeNameString" use="required"/>
</xs:complexType>
<xs:complexType name="Properties">
    <xs:sequence>
        <xs:element name="Property" type="bdc:Property" minOccurs="1" maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="Ordinal">
    <xs:restriction base="xs:integer">
        <xs:minInclusive value="0"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="InstanceCount">
    <xs:restriction base="xs:integer">
        <xs:minInclusive value="0"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ReturnTypeDescriptorLevel">
    <xs:restriction base="xs:integer">
        <xs:minInclusive value="0"/>
        <xs:maxInclusive value="29"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="ActionPosition">
    <xs:restriction base="xs:integer">
        <xs:minInclusive value="1"/>
    </xs:restriction>
</xs:simpleType>
<xs:complexType name="AccessControlList">
    <xs:sequence>
        <xs:element name="AccessControlEntry" type="bdc:AccessControlEntry" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="AccessControlEntry">
    <xs:sequence>
        <xs:element name="Right" type="bdc:Right" minOccurs="1" maxOccurs="unbounded"/>
    </xs:sequence>
    <xs:attribute name="Principal" type="xs:string" use="required"/>
</xs:complexType>
<xs:complexType name="Right">
    <xs:attribute name="BdcRight" type="bdc:BdcRightName" use="required"/>
</xs:complexType>

```

```

<xs:simpleType name="BdcRightName">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Execute"/>
    <xs:enumeration value="Edit"/>
    <xs:enumeration value="SetPermissions"/>
    <xs:enumeration value="SelectableInClients"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="NameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="TypeDescriptorTypeNameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="TypeNameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="UrlString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="2080"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="VersionString">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9]+(\.[0-9]+){1,3}"/>
  </xs:restriction>
</xs:simpleType>
</xs:schema>

```

5.2

<http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources>

```

<xs:schema xmlns="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:bdc="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources"
  targetNamespace="http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources"
  elementFormDefault="qualified">
  <xs:element name="Model" type="bdc:Model"/>
  <xs:complexType name="Model">
    <xs:complexContent>
      <xs:extension base="bdc:IndividuallySecurableMetadataObject">
        <xs:sequence>
          <xs:element name="LobSystems" type="bdc:LobSystems" minOccurs="0" maxOccurs="1">
            <xs:unique name="LobSystemNameKey">
              <xs:selector xpath="*/>
              <xs:field xpath="@Name"/>
            </xs:unique>
          </xs:element>
        </xs:sequence>
      </xs:extension>
    </xs:complexContent>
  </xs:complexType>

```

```

        </xs:element>
    </xs:sequence>
    <xs:attribute name="Name" type="bdc:NameString" use="required"/>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="LobSystems">
    <xs:sequence>
        <xs:element name="LobSystem" type="bdc:LobSystem" minOccurs="1" maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="MetadataObject" abstract="true">
    <xs:sequence>
        <xs:element name="LocalizedDisplayNames" type="bdc:LocalizedDisplayNames" minOccurs="0"
maxOccurs="1">
            <xs:unique name="LocalizedDisplayNameLCIDKey">
                <xs:selector xpath="*/>
                <xs:field xpath="@LCID"/>
            </xs:unique>
        </xs:element>
        <xs:element name="Properties" type="bdc:Properties" minOccurs="0" maxOccurs="1">
            <xs:unique name="PropertyNameKey">
                <xs:selector xpath="*/>
                <xs:field xpath="@Name"/>
            </xs:unique>
        </xs:element>
    </xs:sequence>
    <xs:attribute name="Name" type="bdc:NameString" use="required"/>
</xs:complexType>
<xs:complexType name="IndividuallySecurableMetadataObject" abstract="true">
    <xs:complexContent>
        <xs:extension base="bdc:MetadataObject">
            <xs:sequence>
                <xs:element name="AccessControlList" type="bdc:AccessControlList" minOccurs="0"
maxOccurs="1"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="LocalizedDisplayNames">
    <xs:sequence>
        <xs:element name="LocalizedDisplayName" type="bdc:LocalizedDisplayName" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="LocalizedDisplayName" mixed="true">
    <xs:attribute name="LCID" type="xs:integer" use="required"/>
</xs:complexType>
<xs:complexType name="LobSystem">
    <xs:complexContent>
        <xs:extension base="bdc:IndividuallySecurableMetadataObject">
            <xs:sequence>
                <xs:element name="LobSystemInstances" type="bdc:LobSystemInstances" minOccurs="0"
maxOccurs="1">
                    <xs:unique name="LobSystemInstanceNameKey">
                        <xs:selector xpath="*/>
                        <xs:field xpath="@Name"/>
                    </xs:unique>
                </xs:element>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>

```

```

    <xs:element name="Entities" type="bdc:Entities" minOccurs="0" maxOccurs="1">
      <xs:unique name="EntityNameNamespaceVersionKey">
        <xs:selector xpath="*/"/>
        <xs:field xpath="@Name"/>
        <xs:field xpath="@Namespace"/>
        <xs:field xpath="@Version"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
</xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="LobSystemInstances">
  <xs:sequence>
    <xs:element name="LobSystemInstance" type="bdc:LobSystemInstance" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="LobSystemInstance">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="Entities">
  <xs:sequence>
    <xs:element name="Entity" type="bdc:Entity" minOccurs="1" maxOccurs="unbounded">
      <xs:unique name="MethodInstanceNameKey">
        <xs:selector xpath="./bdc:MethodInstances/*"/>
        <xs:field xpath="@Name"/>
      </xs:unique>
    </xs:element>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Entity">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="Identifiers" type="bdc:Identifiers" minOccurs="0">
          <xs:unique name="IdentifierNameKey">
            <xs:selector xpath="*/"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="Methods" type="bdc:Methods" minOccurs="0">
          <xs:unique name="MethodNameKey">
            <xs:selector xpath="*/"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="AssociationGroups" type="bdc:AssociationGroups" minOccurs="0">
          <xs:unique name="AssociationGroupNameKey">
            <xs:selector xpath="*/"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="Actions" type="bdc:Actions" minOccurs="0">
          <xs:unique name="ActionNameKey">
            <xs:selector xpath="*/"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

        </xs:unique>
      </xs:element>
    </xs:sequence>
    <xs:attribute name="Namespace" type="bcd:NameString" use="required"/>
    <xs:attribute name="Version" type="bcd:VersionString" use="required"/>
  </xs:extension>
</xs:complexContent>
</xs:complexType>
<xs:complexType name="AssociationGroups">
  <xs:sequence>
    <xs:element name="AssociationGroup" type="bcd:AssociationGroup" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="AssociationGroup">
  <xs:complexContent>
    <xs:extension base="bcd:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="Identifiers">
  <xs:sequence>
    <xs:element name="Identifier" type="bcd:Identifier" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Identifier">
  <xs:complexContent>
    <xs:extension base="bcd:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="Methods">
  <xs:sequence>
    <xs:element name="Method" type="bcd:Method" minOccurs="1" maxOccurs="unbounded">
      <xs:key name="ParameterNameKey">
        <xs:selector xpath="./bcd:Parameter"/>
        <xs:field xpath="@Name"/>
      </xs:key>
      <xs:key name="MethodMethodNameKey">
        <xs:selector xpath="./bcd:MethodInstances/*"/>
        <xs:field xpath="@Name"/>
      </xs:key>
    </xs:element>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Method">
  <xs:complexContent>
    <xs:extension base="bcd:IndividuallySecurableMetadataObject">
      <xs:sequence>
        <xs:element name="FilterDescriptors" type="bcd:FilterDescriptors" minOccurs="0"
maxOccurs="1">
          <xs:unique name="FilterDescriptorNameKey">
            <xs:selector xpath="*"/>
            <xs:field xpath="@Name"/>
          </xs:unique>
        </xs:element>
        <xs:element name="Parameters" type="bcd:Parameters" minOccurs="0" maxOccurs="1"/>
        <xs:element name="MethodInstances" type="bcd:MethodInstances" minOccurs="0"
maxOccurs="1"/>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>

```

```

        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="FilterDescriptors">
    <xs:sequence>
        <xs:element name="FilterDescriptor" type="bdc:FilterDescriptor" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="FilterDescriptor">
    <xs:complexContent>
        <xs:extension base="bdc:MetadataObject"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="MethodInstances">
    <xs:choice minOccurs="1" maxOccurs="unbounded">
        <xs:element name="Association" type="bdc:Association"/>
        <xs:element name="MethodInstance" type="bdc:MethodInstance"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="MethodInstance">
    <xs:complexContent>
        <xs:extension base="bdc:IndividuallySecurableMetadataObject"/>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="Parameters">
    <xs:sequence>
        <xs:element name="Parameter" type="bdc:Parameter" minOccurs="1" maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="Parameter">
    <xs:complexContent>
        <xs:extension base="bdc:MetadataObject">
            <xs:sequence>
                <xs:element name="TypeDescriptor" type="bdc:TypeDescriptor"/>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="TypeDescriptor">
    <xs:complexContent>
        <xs:extension base="bdc:MetadataObject">
            <xs:sequence>
                <xs:element name="TypeDescriptors" type="bdc:TypeDescriptors" minOccurs="0">
                    <xs:unique name="TypeDescriptorNameKey">
                        <xs:selector xpath="*/>
                        <xs:field xpath="@Name"/>
                    </xs:unique>
                </xs:element>
            </xs:sequence>
        </xs:extension>
    </xs:complexContent>
</xs:complexType>
<xs:complexType name="TypeDescriptors">
    <xs:sequence>
        <xs:element name="TypeDescriptor" type="bdc:TypeDescriptor" minOccurs="1"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>

```

```

<xs:complexType name="Actions">
  <xs:sequence>
    <xs:element name="Action" type="bdc:Action" minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="Action">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject">
      <xs:sequence>
        <xs:element name="ActionParameters" type="bdc:ActionParameters" minOccurs="0">
          <xs:unique name="ActionParameterNameKey">
            <xs:selector xpath="*" />
            <xs:field xpath="@Name" />
          </xs:unique>
        </xs:element>
      </xs:sequence>
    </xs:extension>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="ActionParameters">
  <xs:sequence>
    <xs:element name="ActionParameter" type="bdc:ActionParameter" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="ActionParameter">
  <xs:complexContent>
    <xs:extension base="bdc:MetadataObject"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="Association">
  <xs:complexContent>
    <xs:extension base="bdc:IndividuallySecurableMetadataObject"/>
  </xs:complexContent>
</xs:complexType>
<xs:complexType name="Property" mixed="true">
  <xs:attribute name="Name" type="bdc:NameString" use="required"/>
  <xs:attribute name="Type" type="bdc:TypeNameString" use="required"/>
</xs:complexType>
<xs:complexType name="Properties">
  <xs:sequence>
    <xs:element name="Property" type="bdc:Property" minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="AccessControlList">
  <xs:sequence>
    <xs:element name="AccessControlEntry" type="bdc:AccessControlEntry" minOccurs="1"
maxOccurs="unbounded"/>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="AccessControlEntry">
  <xs:sequence>
    <xs:element name="Right" type="bdc:Right" minOccurs="1" maxOccurs="unbounded"/>
  </xs:sequence>
  <xs:attribute name="Principal" type="xs:string" use="required"/>
</xs:complexType>
<xs:complexType name="Right">
  <xs:attribute name="BdcRight" type="bdc:BdcRightName" use="required"/>
</xs:complexType>

```



```
<xs:simpleType name="BdcRightName">
  <xs:restriction base="xs:string">
    <xs:enumeration value="None"/>
    <xs:enumeration value="Execute"/>
    <xs:enumeration value="Edit"/>
    <xs:enumeration value="SetPermissions"/>
    <xs:enumeration value="SelectableInClients"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="NameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="TypeNameString">
  <xs:restriction base="xs:string">
    <xs:minLength value="1"/>
    <xs:maxLength value="255"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="VersionString">
  <xs:restriction base="xs:string">
    <xs:pattern value="[0-9]+(\.[0-9]+){1,3}"/>
  </xs:restriction>
</xs:simpleType>
</xs:schema>
```

6 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® SharePoint® Foundation 2010
- Microsoft® Office 2010 suites
- Microsoft® SharePoint® Foundation 15 Technical Preview
- Microsoft® Office 15 Technical Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.1.4.1:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

[<2> Section 2.1.4.3:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

[<3> Section 2.1.4.4:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

[<4> Section 2.1.4.7:](#) A Business Logic Module that conforms to [\[ECMA-335\]](#) and is understood by the .NET Framework.

[<5> Section 2.1.4.7:](#) A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

[<6> Section 2.1.4.7:](#) A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

[<7> Section 2.1.4.7:](#) A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

[<8> Section 2.1.4.7:](#) A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

[<9> Section 2.1.4.7:](#) A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

[<10> Section 2.1.4.7:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

[<11> Section 2.1.4.9:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<12> [Section 2.1.4.11:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<13> [Section 2.1.4.13:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<14> [Section 2.1.4.16:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<15> [Section 2.1.4.18:](#) SharePoint Foundation 2010 currently ignores the value of this attribute.

<16> [Section 2.1.4.18:](#) SharePoint Foundation 2010 requires that the value of **LobName** matches the name of the operation in the line-of-business (LOB) system.

<17> [Section 2.1.4.18:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<18> [Section 2.1.4.20:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<19> [Section 2.1.4.22:](#) This attribute is deprecated; however, SharePoint Foundation 2010 evaluates this attribute when present for compatibility reasons.

<20> [Section 2.1.4.22:](#) This attribute is deprecated; however, SharePoint Foundation 2010 allows this attribute for compatibility reasons.

<21> [Section 2.1.4.22:](#) SharePoint Foundation 2010 ignores all index values specified in the path, and treats them as zero.

<22> [Section 2.1.4.22:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<23> [Section 2.1.4.24:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<24> [Section 2.1.4.25:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<25> [Section 2.1.4.34:](#) SharePoint Foundation 2010 expects the instantiated command to result in a well formed URL that is used in an HTTP GET operation.

<26> [Section 2.1.4.34:](#) SharePoint Foundation 2010 instantiates the abstract command in the context of an **EntityInstance**. The name of the **ActionParameter** is used to identify a field (4) of the **EntityInstance**. The placeholder is then replaced with the field (4) value.

<27> [Section 2.1.4.34:](#) The behavior of SharePoint Foundation 2010 is polymorphic and depends on the actual **ActionParameter** value, as described in [\[CompositeFormatting\]](#).

<28> [Section 2.1.4.34:](#) SharePoint Foundation 2010 expects the image dimensions to be 16 by 16 pixels.

<29> [Section 2.1.4.34:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<30> [Section 2.1.4.36:](#) SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<31> [Section 2.1.4.37](#): This attribute is deprecated; however, SharePoint Foundation 2010 evaluates this attribute when present for compatibility reasons.

<32> [Section 2.1.4.37](#): This attribute is deprecated; however, SharePoint Foundation 2010 allows this attribute for compatibility reasons.

<33> [Section 2.1.4.37](#): SharePoint Foundation 2010 ignores all index values specified in the path, and treats them as zero.

<34> [Section 2.1.4.37](#): SharePoint Foundation 2010 caches the metadata in memory if **IsCached** is **true**.

<35> [Section 2.1.5.1](#): A Business Logic Module that conforms to [\[ECMA-335\]](#) and is understood by the .NET Framework.

<36> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<37> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<38> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<39> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<40> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<41> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<42> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<43> [Section 2.1.5.16](#): A Business Logic Module that conforms to the [\[ECMA-335\]](#) specification and is understood by the .NET Framework.

<44> [Section 3.3](#): This example is using a fictitious web service and is not usable with SharePoint Foundation 2010 without modifications.

7 Change Tracking

This section identifies changes that were made to the [MS-BDCMFFS] protocol document between the June 2011 and January 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
1 Introduction	Clarified the description by adding "line-of-business (LOB) systems" to the information about the Metadata Model.	N	Content updated.
1.1 Glossary	Added the term "Open Data Protocol (OData)" to the list of terms specific to this document.	N	Content updated.
1.4 Relationship to Protocols and Other Structures	Clarified the description by removing the phrase describing the specification as an XML Schema file.	N	Content removed.
1.7 Vendor-Extensible Fields	Clarified the description by identifying the Properties element as part of what	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	vendor-extensible fields the file format defines.		
2.1.2.1 Model	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.1 Model	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.2 LobSystems	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.3 MetadataObject	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.3 MetadataObject	Changed "MetadataObject" to "Model".	N	Content updated.
2.1.4.4 IndividuallySecurableMetadataObject	Changed "MetadataObject" to "Model".	N	Content updated.
2.1.4.4 IndividuallySecurableMetadataObject	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.5 LocalizedDisplayNames	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.6 LocalizedDisplayName	Added reference to [XMLSCHEMA1].	N	Content updated.
2.1.4.7 LobSystem	Changed "LobSystem" to "Model".	N	Content updated.
2.1.4.7 LobSystem	Clarified the descriptions by adding links to related elements.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.1.4.7 LobSystem	Removed a paragraph about what the properties must contain.	N	Content removed.
2.1.4.7 LobSystem	Added product behavior notes for the phrase "Business Logic Module", saying that it conforms to [ECMA-335] and is understood by the .NET Framework.	N	New product behavior note added.
2.1.4.7 LobSystem	Updated product behavior notes by removing information about SharePoint Foundation 2010 using the Business Logic Module.	N	Product behavior note updated.
2.1.4.8 LobSystemInstances	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.9 LobSystemInstance	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.9 LobSystemInstance	Clarified the Model attribute description by adding a table of possible values.	N	Content updated.
2.1.4.9 LobSystemInstance	Changed "LobSystemInstance" to "Model".	N	Content updated.
2.1.4.10 Entities	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.11 Entity	Clarified the descriptions by adding links to related elements.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.1.4.11 Entity	Changed "Entity" to "Model" in the descriptions.	N	Content updated.
2.1.4.11 Entity	Removed a paragraph about what the properties may contain.	N	Content removed.
2.1.4.12 AssociationGroups	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.13 AssociationGroup	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.13 AssociationGroup	Changed "AssociationGroup" to "Model" in the descriptions.	N	Content updated.
2.1.4.14 AssociationReference	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.15 Identifiers	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.16 Identifier	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.16 Identifier	Changed "Identifier" to "Model" in the descriptions.	N	Content updated.
2.1.4.16 Identifier	Added a table of values for the IsCached element.	N	Content updated.
2.1.4.17 Methods	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.18	Removed	N	Content

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
Method	Properties element.		removed.
2.1.4.18 Method	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.18 Method	Changed "Method" to "Model" in the descriptions.	N	Content updated.
2.1.4.18 Method	Added a table of values for the IsCached element.	N	Content updated.
2.1.4.18 Method	Removed a paragraph about the scenario where the Type attribute is "Database".	N	Content removed.
2.1.4.18 Method	Updated product behavior note by removing information about SharePoint Foundation 2010 allowing certain values in "Text", "StoredProcedure", or "TableDirect".	N	Product behavior note updated.
2.1.4.19 FilterDescriptors	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.20 FilterDescriptor	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.20 FilterDescriptor	Changed "FilterDescriptor" to "Model" in the descriptions.	N	Content updated.
2.1.4.20 FilterDescriptor	Removed a paragraph about the scenario where the Type attribute of FilterDescriptor is "Comparison".	N	Content removed.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.1.4.21 MethodInstances	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.22 MethodInstance	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.22 MethodInstance	Changed "MethodInstance" to "Model" in the descriptions.	N	Content updated.
2.1.4.23 Parameters	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.24 Parameter	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.24 Parameter	Changed "Parameter" to "Model" in the descriptions.	N	Content updated.
2.1.4.25 TypeDescriptor	Changed "TypeDescriptor" to "Model" in the descriptions.	N	Content updated.
2.1.4.25 TypeDescriptor	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.25 TypeDescriptor	Removed a paragraph about what the properties may contain.	N	Content removed.
2.1.4.25 TypeDescriptor	Added the IsSortInput attribute description and table of values.	N	New content added.
2.1.4.26 DefaultValues	Clarified the descriptions by adding links to	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	related elements.		
2.1.4.27 DefaultValue	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.28 Interpretation	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.29 ConvertType	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.30 NormalizeString	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.31 NormalizeDateTime	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.32 TypeDescriptors	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.33 Actions	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.34 Action	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.34 Action	Changed "Action" to "Model" in the descriptions.	N	Content updated.
2.1.4.35 ActionParameters	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.36 ActionParameter	Clarified the descriptions by adding links to related elements.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.1.4.36 ActionParameter	Changed "ActionParameter" to "Model" in the descriptions.	N	Content updated.
2.1.4.36 ActionParameter	Removed a paragraph about what the properties may contain.	N	Content removed.
2.1.4.37 Association	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.37 Association	Changed "Association" to "Model" or "MethodInstance" in the descriptions.	N	Content updated.
2.1.4.37 Association	Updated the ReturnParameterName attribute by adding the MethodInstances for which the attribute does not need to be specified.	N	Content updated.
2.1.4.38 SourceEntity	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.39 DestinationEntity	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.40 Property	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.41 Properties	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.42 AccessControlList	Clarified the descriptions by adding links to	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	related elements.		
2.1.4.43 AccessControlEntry	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.4.44 Right	Clarified the descriptions by adding links to related elements.	N	Content updated.
2.1.5 Simple Types	Updated the introduction to include a summary of what is included in the table.	N	New content added.
2.1.5.1 LobSystemType	Added the value OData to the W3C XML Schema fragment and listed the value and its description in the table.	N	New content added.
2.1.5.1 LobSystemType	Added a link to the [XMLSCHEMA1] reference.	N	Content updated.
2.1.5.1 LobSystemType	Added product behavior note for the phrase "Business Logic Module", saying that it conforms to [ECMA-335] and is understood by the .NET Framework.	N	New product behavior note added.
2.1.5.2 OperationModeType	Added a link to the [XMLSCHEMA1] reference.	N	Content updated.
2.1.5.3 IdentifierType	Added a link to the [XMLSCHEMA1] reference.	N	Content updated.
2.1.5.3 IdentifierType	Updated the description of System.Byte in the table by changing "...from 0 to 255" to "...from 0 through 255".	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.1.5.4 FilterDescriptorType	Added the "Sorting" enumeration value to the fragment and a description of this value to the table.	N	Content updated.
2.1.5.5 TypeDescriptorPathString	Removed the target namespace and associated description and fragment.	N	Content removed.
2.1.5.5 TypeDescriptorPathString	Moved section down.	N	Content updated.
2.1.5.6 MethodInstanceType	Added the "EventSubscriber" and "EventUnsubscriber" enumeration values to the fragment and a description of these values to the table.	N	Content updated.
2.1.5.6 MethodInstanceType	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.7 ParameterDirection	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.8 StringNormalizeMode	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.9 LobDateTimeMode	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.10 Ordinal	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.11 InstanceCount	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.12 ReturnTypeDescriptorLevel	Added a reference to [XMLSCHEMA1].	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
			d.
2.1.5.13 ActionPosition	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.14 BdcRightName	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.15 NameString	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.16 TypeDescriptorTypeNameString	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.16 TypeDescriptorTypeNameString	Clarified that "Custom" is specified for the "section type", and not simply the "section", in the mapping steps.	N	Content updated.
2.1.5.16 TypeDescriptorTypeNameString	Added product behavior notes for the phrase "Business Logic Module", saying that it conforms to [ECMA-335] and is understood by the .NET Framework.	N	New product behavior note added.
2.1.5.17 TypeNameString	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.18 UrlString	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.1.5.19 VersionString	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.2.2.1 Model	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.1 Model	Clarified the descriptions by	N	Content update

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	adding link to related content.		d.
2.2.4.1 Model	Moved the Attributes list further down within the section.	N	Content updated.
2.2.4.2 LobSystems	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.3 MetadataObject	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.4 IndividuallySecurableMetadataObject	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.5 LocalizedDisplayNames	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.6 LocalizedDisplayName	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.2.4.7 LobSystem	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.7 LobSystem	Moved the Attributes list further down within the section.	N	Content updated.
2.2.4.8 LobSystemInstances	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.9 LobSystemInstance	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.9 LobSystemInstance	Moved the Attributes list further up within	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	the section.		
2.2.4.10 Entities	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.11 Entity	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.11 Entity	Changed the term "Entity" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.12 AssociationGroups	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.13 AssociationGroup	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.13 AssociationGroup	Changed the term "AssociationGroup" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.13 AssociationGroup	Moved the Attributes list further up within the section.	N	Content updated.
2.2.4.14 Identifiers	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.15 Identifier	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.15 Identifier	Changed the term "Identifier" to "Model" or "MetadataObject" where applicable.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.4.15 Identifier	Moved the Attributes list further down within the section.	N	Content updated.
2.2.4.16 Methods	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.17 Method	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.17 Method	Changed the term "Method" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.17 Method	Moved the Attributes list further down within the section.	N	Content updated.
2.2.4.18 FilterDescriptors	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.19 FilterDescriptor	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.19 FilterDescriptor	Changed the term "FilterDescriptor" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.20 MethodInstances	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.21 MethodInstance	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.21 MethodInstance	Changed the term "MethodInstance" to "Model" or	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	"MetadataObject" where applicable.		
2.2.4.22 Parameters	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.23 Parameter	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.23 Parameter	Changed the term "Parameter" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.24 TypeDescriptor	Changed the term "TypeDescriptor" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.24 TypeDescriptor	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.25 TypeDescriptors	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.26 Actions	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.27 Action	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.27 Action	Changed the term "Action" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.27 Action	Moved the Attributes list further up within the section.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.4.28 ActionParameters	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.29 ActionParameter	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.29 ActionParameter	Changed the term "ActionParameter" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.30 Association	Changed the term "Association" to "Model" or "MetadataObject" where applicable.	N	Content updated.
2.2.4.30 Association	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.30 Association	Moved the Attributes list further up within the section.	N	Content updated.
2.2.4.31 Property	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.32 Properties	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.33 AccessControlList	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.4.34 AccessControlEntry	Updated references in the attribute descriptions for AccessControlEntry.	N	Content updated.
2.2.4.34	Clarified the	N	Content

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
AccessControlEntry	descriptions of the rules by describing the entity the rule conforms to as an original issuer or a trusted STS.		updated.
2.2.4.35 Right	Clarified the descriptions by adding link to related content.	N	Content updated.
2.2.5.1 BdcRightName	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.2.5.1 BdcRightName	Updated the description to include a "Right" that is held by the security principal (2).	N	Content updated.
2.2.5.2 NameString	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.2.5.3 TypeNameString	Added a reference to [XMLSCHEMA1].	N	Content updated.
2.2.5.4 VersionString	Added a reference to [XMLSCHEMA1].	N	Content updated.
3.3 Web Service Model	Updated product behavior note by removing information about the Business Logic Module.	N	Product behavior note updated.
4 Security Considerations	Added a link to the LobSystem element.	N	Content updated.
5 Appendix A: Full XML Schemas	Clarified the section introduction by adding that the section provides the full "XML schemas".	N	Content updated.
5.1	Updated the name	N	Content

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
http://schemas.microsoft.com/windows/2007/BusinessDataCatalog	of the section from the previous "Business Data Connectivity Model Structure XSD".		updated.
5.1 http://schemas.microsoft.com/windows/2007/BusinessDataCatalog	Updated the schema based on new xs:schema xmlns value, new enumeration values, and a new attribute name.	N	Content updated.
5.2 http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources	Updated the schema based on a new xs:schema xmlns value and removal of </xs:extension> where applicable.	N	Content updated.
5.2 http://schemas.microsoft.com/windows/2007/BusinessDataCatalog/Resources	Updated the name of the section from the previous "Business Data Connectivity Model Resource Structure XSD".	N	Content updated.
6 Appendix B: Product Behavior	Updated the product list.	N	Content updated.

8 Index

A

[Applicability](#) 9
[Associations example](#) 101

C

[Change tracking](#) 125
Common data types and fields ([section 2](#) 11, [section 2](#) 11)
Complex types - metadata model
[AccessControlEntry](#) 50
[AccessControlList](#) 49
[Action](#) 42
[ActionParameter](#) 44
[ActionParameters](#) 44
[Actions](#) 41
[Association](#) 45
[AssociationGroup](#) 23
[AssociationGroups](#) 22
[AssociationReference](#) 23
[ConvertType](#) 39
[DefaultValue](#) 38
[DefaultValues](#) 37
[DestinationEntity](#) 48
[Entities](#) 20
[Entity](#) 20
[FilterDescriptor](#) 28
[FilterDescriptors](#) 28
[Identifier](#) 25
[Identifiers](#) 24
[IndividuallySecurableMetadataObject](#) 14
[Interpretation](#) 38
[LobSystem](#) 16
[LobSystemInstance](#) 19
[LobSystemInstances](#) 18
[LocalizedDisplayName](#) 15
[LocalizedDisplayNames](#) 15
[MetadataObject](#) 13
[Method](#) 26
[MethodInstance](#) 30
[MethodInstances](#) 29
[Methods](#) 26
[NormalizeDateTime](#) 40
[NormalizeString](#) 40
[Parameter](#) 32
[Parameters](#) 32
[Properties](#) 49
[Property](#) 48
[Right](#) 51
[SourceEntity](#) 47
[TypeDescriptor](#) 33
[TypeDescriptors](#) 41
Complex types – metadata model
[LobSystems](#) 13
[Model](#) 11
Complex types - metadata model resources
[AccessControlEntry](#) 85

[AccessControlList](#) 85
[Action](#) 82
[ActionParameter](#) 83
[ActionParameters](#) 82
[Actions](#) 81
[Association](#) 83
[AssociationGroup](#) 74
[AssociationGroups](#) 73
[Entities](#) 71
[Entity](#) 72
[FilterDescriptor](#) 77
[FilterDescriptors](#) 77
[Identifier](#) 75
[Identifiers](#) 74
[IndividuallySecurableMetadataObject](#) 68
[LobSystem](#) 69
[LobSystemInstance](#) 71
[LobSystemInstances](#) 70
[LobSystems](#) 66
[LocalizedDisplayName](#) 69
[LocalizedDisplayNames](#) 68
[MetadataObject](#) 67
[Method](#) 76
[MethodInstance](#) 78
[MethodInstances](#) 78
[Methods](#) 75
[Model](#) 66
[Parameter](#) 79
[Parameters](#) 79
[Properties](#) 84
[Property](#) 84
[Right](#) 86
[TypeDescriptor](#) 80
[TypeDescriptors](#) 81
[CRUD example](#) 97

D

Data types and fields - common ([section 2](#) 11, [section 2](#) 11)
[Database Model example](#) 90
Details
 common data types and fields ([section 2](#) 11, [section 2](#) 11)
Details – metadata model resources
 [Model element](#) 65
 [DotNetAssembly Model example](#) 92

E

Elements - metadata model resources
[Model](#) 65
[Examples](#) 90
[Associations](#) 101
[CRUD](#) 97
[Database Model](#) 90
[DotNetAssembly Model](#) 92
[Finders](#) 95

[Model Resources](#) 94
[overview](#) 90
[Web Service Model](#) 93

F

[Fields - vendor-extensible](#) 10
[Finders example](#) 95
[Full XML schema](#) 105

G

Global elements – metadata model
[Model](#) 11
[Glossary](#) 6

I

[Implementer - security considerations](#) 104
[Informative references](#) 9
[Introduction](#) 6

L

[Localization](#) 10

M

Metadata model

[AccessControlEntry complex type](#) 50
[AccessControlList complex type](#) 49
[Action complex type](#) 42
[ActionParameter complex type](#) 44
[ActionParameters complex type](#) 44
[ActionPosition simple type](#) 60
[Actions complex type](#) 41
[Association complex type](#) 45
[AssociationGroup complex type](#) 23
[AssociationGroups complex type](#) 22
[AssociationReference complex type](#) 23
[BdcRightName simple type](#) 60
[ConvertType complex type](#) 39
[DefaultValue complex type](#) 38
[DefaultValues complex type](#) 37
[DestinationEntity complex type](#) 48
[Entities complex type](#) 20
[Entity complex type](#) 20
[FilterDescriptor complex type](#) 28
[FilterDescriptors complex type](#) 28
[FilterDescriptorType simple type](#) 54
[global attributes](#) 11
[Identifier complex type](#) 25
[Identifiers complex type](#) 24
[IdentifierType simple type](#) 53
[IndividuallySecurableMetadataObject complex type](#) 14
[InstanceCount simple type](#) 59
[Interpretation complex type](#) 38
[LobDateTimeMode simple type](#) 58
[LobSystem complex type](#) 16
[LobSystemInstance complex type](#) 19
[LobSystemInstances complex type](#) 18

[LobSystems complex type](#) 13
[LobSystemType simple type](#) 51
[LocalizedDisplayName complex type](#) 15
[LocalizedDisplayNames complex type](#) 15
[MetadataObject complex type](#) 13
[Method complex type](#) 26
[MethodInstance complex type](#) 30
[MethodInstances complex type](#) 29
[MethodInstanceType simple type](#) 56
[Methods complex type](#) 26
[Model complex type](#) 11
[Model element](#) 11
[namespaces](#) 11
[NameString simple type](#) 61
[NormalizeDateTime complex type](#) 40
[NormalizeString complex type](#) 40
[OperationModeType simple type](#) 52
[Ordinal simple type](#) 59
[Parameter complex type](#) 32
[ParameterDirection simple type](#) 57
[Parameters complex type](#) 32
[Properties complex type](#) 49
[Property complex type](#) 48
[ReturnTypeDescriptorLevel simple type](#) 60
[Right complex type](#) 51
[SourceEntity complex type](#) 47
[StringNormalizeMode simple type](#) 58
[TypeDescriptor complex type](#) 33
[TypeDescriptors complex type](#) 41
[TypeDescriptorTypeNameString simple type](#) 62
[TypeNameString simple type](#) 63
[VersionString simple type](#) 64
Metadata model resources
[AccessControlEntry complex type](#) 85
[AccessControlList complex type](#) 85
[Action complex type](#) 82
[ActionParameter complex type](#) 83
[ActionParameters complex type](#) 82
[Actions complex type](#) 81
[Association complex type](#) 83
[AssociationGroup complex type](#) 74
[AssociationGroups complex type](#) 73
[BdcRightName simple type](#) 87
[Entities complex type](#) 71
[entity complex type](#) 72
[FilterDescriptor complex type](#) 77
[FilterDescriptors complex type](#) 77
[global attributes](#) 65
[Identifier complex type](#) 75
[Identifiers complex type](#) 74
[IndividuallySecurableMetadataObject complex type](#) 68
[LobSystem complex type](#) 69
[LobSystemInstance complex type](#) 71
[LobSystemInstances complex type](#) 70
[LobSystems complex type](#) 66
[LocalizedDisplayName complex type](#) 69
[LocalizedDisplayNames complex type](#) 68
[MetadataObject complex type](#) 67
[Method complex type](#) 76
[MethodInstance complex type](#) 78

- [MethodInstances complex type](#) 78
- [Methods complex type](#) 75
- [Model complex type](#) 66
- [Model element](#) 65
- [namespaces](#) 65
- [NameString simple type](#) 88
- [Parameter complex type](#) 79
- [Parameters complex type](#) 79
- [Properties complex type](#) 84
- [Property complex type](#) 84
- [Right complex type](#) 86
- [TypeDescriptor complex type](#) 80
- [TypeDescriptors complex type](#) 81
- [TypeNameString simple type](#) 88
- [VersionString simple type](#) 89
- [Metadata model UriString simple type](#) 64
- [Model Resources example](#) 94

N

- Namespaces
 - [metadata model resources](#) 65
- [Normative references](#) 8

O

- [Overview \(synopsis\)](#) 9

P

- [Product behavior](#) 122

R

- [References](#) 8
 - [informative](#) 9
 - [normative](#) 8
- [Relationship to protocols and other structures](#) 9

S

- [Security - implementer considerations](#) 104
- Simple types - metadata model
 - [ActionPosition](#) 60
 - [BdcRightName](#) 60
 - [FilterDescriptorType](#) 54
 - [IdentifierType](#) 53
 - [Instancecount](#) 59
 - [LobDateTimeMode](#) 58
 - [LobSystemType](#) 51
 - [MethodInstanceType](#) 56
 - [NameString](#) 61
 - [OperationModeType](#) 52
 - [Ordinal](#) 59
 - [ParameterDirection](#) 57
 - [ReturnTypeDescriptorLevel](#) 60
 - [StringNormalizeMode](#) 58
 - [TypeDescriptorTypeNameString](#) 62
 - [TypeNameString](#) 63
 - [UriString](#) 64
 - [VersionString](#) 64
- Simple types - metadata model resources

- [BdcRightName](#) 87
- [NameString](#) 88
- [TypeNameString](#) 88
- [VersionString](#) 89
- Structures
 - [metadata model namespaces](#) 11
 - overview ([section 2 11](#), [section 2 11](#))
- Structures - metadata model
 - [AccessControlEntry complex type](#) 50
 - [AccessControlList complex type](#) 49
 - [Action complex type](#) 42
 - [ActionParameter complex type](#) 44
 - [ActionParameters complex type](#) 44
 - [ActionPosition simple type](#) 60
 - [Actions complex type](#) 41
 - [Association complex type](#) 45
 - [AssociationGroup complex type](#) 23
 - [AssociationGroups complex type](#) 22
 - [AssociationReference complex type](#) 23
 - [BdcRightName simple type](#) 60
 - [ConvertType complex type](#) 39
 - [DefaultValue complex type](#) 38
 - [DefaultValues complex type](#) 37
 - [DestinationEntity complex type](#) 48
 - [Entities complex type](#) 20
 - [Entity complex type](#) 20
 - [FilterDescriptor complex type](#) 28
 - [FilterDescriptors complex type](#) 28
 - [FilterDescriptorType simple type](#) 54
 - [Identifiers complex type](#) 24
 - [Identifier complex type](#) 25
 - [IdentifierType simple type](#) 53
 - [IndividuallySecurableMetadataObject complex type](#) 14
 - [InstanceCount simple type](#) 59
 - [Interpretation complex type](#) 38
 - [LobDateTimeMode simple type](#) 58
 - [LobSystem complex type](#) 16
 - [LobSystemInstance complex type](#) 19
 - [LobSystemInstances complex type](#) 18
 - [LobSystemType simple type](#) 51
 - [LocalizedDisplayName complex type](#) 15
 - [LocalizedDisplayNames complex type](#) 15
 - [MetadataObject complex type](#) 13
 - [Method complex type](#) 26
 - [MethodInstance complex type](#) 30
 - [MethodInstances complex type](#) 29
 - [MethodInstanceType simple type](#) 56
 - [Methods complex type](#) 26
 - [NameString simple type](#) 61
 - [NormalizeDateTime complex type](#) 40
 - [NormalizeString complex type](#) 40
 - [OperationModeType simple type](#) 52
 - [Ordinal simple type](#) 59
 - [Parameter complex type](#) 32
 - [ParameterDirection simple type](#) 57
 - [Parameters complex type](#) 32
 - [Properties complex type](#) 49
 - [Property complex type](#) 48
 - [ReturnTypeDescriptorLevel simple type](#) 60
 - [Right complex type](#) 51

[SourceEntity complex type](#) 47
[StringNormalizeMode simple type](#) 58
[TypeDescriptor complex type](#) 33
[TypeDescriptors complex type](#) 41
[TypeDescriptorTypeNameString simple type](#) 62
[TypeNameString simple type](#) 63
[UrlString simple type](#) 64
[VersionString simple type](#) 64

Structures – metadata model
[global attributes](#) 11
[LobSystems complex type](#) 13
[Model complex type](#) 11

Structures - metadata model resources
[AccessControlEntry complex type](#) 85
[AccessControlList complex type](#) 85
[Action complex type](#) 82
[ActionParameter complex type](#) 83
[ActionParameters complex type](#) 82
[Actions complex type](#) 81
[Association complex type](#) 83
[AssociationGroup complex type](#) 74
[AssociationGroups complex type](#) 73
[BdcRightName simple type](#) 87
[Entities complex type](#) 71
[Entity complex type](#) 72
[FilterDescriptor complex type](#) 77
[FilterDescriptors complex type](#) 77
[global attributes](#) 65
[Identifier complex type](#) 75
[Identifiers complex type](#) 74
[IndividuallySecurableMetadataObject complex type](#) 68
[LobSystem complex type](#) 69
[LobSystemInstance complex type](#) 71
[LobSystemInstances complex type](#) 70
[LobSystems complex type](#) 66
[LocalizedDisplayName complex type](#) 69
[LocalizedDisplayNames complex type](#) 68
[MetadataObject complex type](#) 67
[Method complex type](#) 76
[MethodInstance complex type](#) 78
[MethodInstances complex type](#) 78
[Methods complex type](#) 75
[Model complex type](#) 66
[NameString simple type](#) 88
[Parameter complex type](#) 79
[Parameters complex type](#) 79
[Properties complex type](#) 84
[Property complex type](#) 84
[Right complex type](#) 86
[TypeDescriptor complex type](#) 80
[TypeDescriptors complex type](#) 81
[TypeNameString simple type](#) 88
[VersionString simple type](#) 89

T

[Tracking changes](#) 125

V

[Vendor-extensible fields](#) 10

[Versioning](#) 10

W

[Web Service Model example](#) 93

X

[XML schema](#) 105