

[MS-CUSTOMUI]: Custom UI XML Markup Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
01/15/2009	1.0	Major	Initial Availability
07/13/2009	1.01	Major	Revised and edited the technical content
08/28/2009	1.02	Editorial	Revised and edited the technical content
11/06/2009	1.03	Editorial	Revised and edited the technical content
02/19/2010	2.0	Editorial	Revised and edited the technical content
03/31/2010	2.01	Editorial	Revised and edited the technical content
04/30/2010	2.02	Editorial	Revised and edited the technical content
06/07/2010	2.03	Editorial	Revised and edited the technical content
06/29/2010	2.04	Editorial	Changed language and formatting in the technical content.
07/23/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	2.04	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	2.5	Minor	Clarified the meaning of the technical content.
04/11/2012	2.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	2.5	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	2.5	No change	No changes to the meaning, language, or formatting of the technical content.
02/11/2013	2.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/30/2013	2.5	No change	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
11/18/2013	2.5	No change	No changes to the meaning, language, or formatting of the technical content.
02/10/2014	2.5	No change	No changes to the meaning, language, or formatting of the technical content.
04/30/2014	2.5	No change	No changes to the meaning, language, or formatting of the technical content.
07/31/2014	2.6	Minor	Clarified the meaning of the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	6
1.2.1 Normative References	6
1.2.2 Informative References	6
2 Custom UI	7
2.1 Parts	7
2.1.1 Quick Access Toolbar Customizations Part	7
2.1.2 Ribbon Extensibility Part	8
2.2 Elements	9
2.2.1 box (Box Grouping Container)	9
2.2.2 button (Button)	13
2.2.3 button (Unsize Button)	23
2.2.4 button (Button Inside of a Split Button)	32
2.2.5 buttonGroup (Button Grouping Container)	41
2.2.6 checkBox (Check Box)	45
2.2.7 comboBox (Combo Box)	55
2.2.8 command (Repurposed Command)	67
2.2.9 commands (List of Repurposed Commands)	68
2.2.10 contextualTabs (List of Contextual Tab Sets)	69
2.2.11 control (Unsize Control Clone)	69
2.2.12 control (Control Clone)	77
2.2.13 control (Quick Access Toolbar Control Clone)	87
2.2.14 customUI (Custom UI Document Root)	96
2.2.15 dialogBoxLauncher (Dialog Box Launcher)	97
2.2.16 documentControls (List of Document-Specific Quick Access Toolbar Controls)	98
2.2.17 dropDown (Drop-down Control)	99
2.2.18 dynamicMenu (Unsize Dynamic Menu)	111
2.2.19 dynamicMenu (Dynamic Menu)	121
2.2.20 editBox (Edit Box)	132
2.2.21 gallery (Gallery)	142
2.2.22 gallery (Unsize Gallery)	159
2.2.23 group (Group)	175
2.2.24 item (Selection Item)	182
2.2.25 labelControl (Text Label)	185
2.2.26 menu (Unsize Menu)	194
2.2.27 menu (Menu with Title)	204
2.2.28 menu (Menu)	214
2.2.29 menu (Dynamic Menu Root XML Element)	224
2.2.30 menuSeparator (Menu Separator)	227
2.2.31 officeMenu (Office Menu)	230
2.2.32 qat (Quick Access Toolbar)	231
2.2.33 ribbon (Ribbon)	232
2.2.34 separator (Separator)	233
2.2.35 sharedControls (List of Shared Quick Access Toolbar Controls)	236
2.2.36 splitButton (Unsize Split Button)	237
2.2.37 splitButton (Split Button with Title)	246
2.2.38 splitButton (Split Button)	254
2.2.39 tab (Tab)	263

2.2.40	tabs (List of Tabs)	268
2.2.41	tabSet (Contextual Tab Set)	268
2.2.42	toggleButton (Unsize Toggle Button)	270
2.2.43	toggleButton (Toggle Button)	279
2.2.44	toggleButton (Toggle Button Inside of a Split Button)	289
2.3	Simple Types	298
2.3.1	ST_BoxStyle (Box Style)	298
2.3.2	ST_Delegate (Callback Function Name)	299
2.3.3	ST_GalleryItemWidthHeight (Gallery Item Width or Height)	302
2.3.4	ST_GalleryRowColumnCount (Gallery Row or Column Count)	302
2.3.5	ST_ID (Control ID)	303
2.3.6	ST_ItemSize (Menu Item Size)	304
2.3.7	ST_Keytip (Keytip)	305
2.3.8	ST_LongString (Long String)	305
2.3.9	ST_QID (Qualified Control ID)	306
2.3.10	ST_Size (Control Size)	308
2.3.11	ST_String (Short String)	308
2.3.12	ST_StringLength (String Length)	309
2.3.13	ST_UniqueID (Custom Control ID)	310
2.3.14	ST Uri (Image Relationship ID)	310
3	Appendix A: Custom UI Control ID Tables	312
3.1	idMso Tables	312
3.1.1	Word 2007	312
3.1.2	Excel 2007	370
3.1.3	PowerPoint 2007	408
3.2	imageMso Table	436
4	Appendix B: Product Behavior	545
5	Change Tracking	546
6	Index	553

1 Introduction

In creating an interoperable implementation, it is helpful to understand specific implementation choices made by other products implementing the same standard. For example, portions of the standard may provide only general guidance, leaving specific implementation choices up to the application implementer; in some circumstances it may be helpful for other implementers to understand those choices.

The information contained in this document provides information about how to implement UI customization in the context of ECMA-376 Office Open XML File Formats, as described in [\[ECMA-376\]](#).

1.1 Glossary

The following terms are defined in [\[MS-OFCGLOS\]](#):

XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[ECMA-376] ECMA International, "Office Open XML File Formats", 1st Edition, ECMA-376, December 2006, <http://www.ecma-international.org/publications/standards/Ecma-376.htm>

[MS-CUSTOMUI2] Microsoft Corporation, "[Custom UI XML Markup Version 2 Specification](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

1.2.2 Informative References

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

2 Custom UI

The subordinate clauses specify the semantics for the Custom UI XML markup contained within the ECMA-376 Office Open XML File Formats, as specified in [\[ECMA-376\]](#). These semantics describe customization of the UI interface. Examples in the following clauses highlight customizations in the context of the Microsoft Office Fluent interface (UI) but the concepts extend naturally to any user interface.

Customization of the UI is accomplished via the addition of parts containing Custom UI XML markup to the containing document package.

2.1 Parts

The parts described in the subordinate sections detail the additional part types utilized by CustomUI in an ECMA-376 Office Open XML File Formats [\[ECMA-376\]](#) file.

2.1.1 Quick Access Toolbar Customizations Part

Content Type:	application/xml
Root Namespace:	http://schemas.microsoft.com/office/2006/01/customui
Source Relationship:	http://schemas.microsoft.com/office/2006/relationships/ui/userCustomization

An instance of this part type contains information about the quick access toolbar customizations specific to the containing package.

For example, a user can customize the quick access toolbar for his WordProcessingML document to contain the UI controls that they commonly use.

A package is permitted to contain at most one Quick Access Toolbar Customizations part, and that part is the target of a relationship in the package-relationship item for the document.

For example, the following package part-relationship item contains a relationship to a Quick Access Toolbar Customizations part, which is stored in the ZIP item `/userCustomization/customUI.xml`:

```
<Relationships xmlns="...">
  <Relationship Id="rId2"
    Type="http://.../2006/relationships/ui/userCustomization"
    Target="/userCustomization/customUI.xml" />
</Relationships>
```

The root element for a part of this content type is **customUI**.

For example, the following Quick Access Toolbar Customizations content markup specifies that the control with identifier "SpellingAndGrammar" is to be added to the quick access toolbar for the package:

```
<mso:customUI xmlns:mso="http://schemas.microsoft.com/office/2006/01/customui">
  <mso:ribbon>
    <mso:qat>
      <mso:documentControls>
        <mso:control idQ="mso:SpellingAndGrammar" visible="true" />
      </mso:documentControls>
    </mso:qat>
```

```
</mso:ribbon>
</mso:customUI>
```

A Quick Access Toolbar Customizations part is located within the package containing the source relationship. Expressed syntactically, the **TargetMode** attribute of the **Relationship** element is "Internal".

A Quick Access Toolbar Customizations part does not have implicit or explicit relationships to any other part defined by ECMA-376 Office Open XML File Formats, as specified in [\[ECMA-376\]](#).

2.1.2 Ribbon Extensibility Part

Content Type:	application/xml
Root Namespace:	http://schemas.microsoft.com/office/2006/01/customui
Source Relationship:	http://schemas.microsoft.com/office/2006/relationships/ui/extensibility

An instance of this part type contains information about the ribbon customizations specific to the containing package.

For example, a SpreadsheetML document that represents a timecard could contain custom UI controls to guide the user in filling out the timecard.

A package is permitted to contain at most one Ribbon Extensibility part, and that part is the target of a relationship in the package-relationship item for the document.

For example, the following package part-relationship item contains a relationship to a Ribbon Extensibility part, which is stored in the ZIP item /customUI/customUI.xml:

```
<Relationships xmlns="...">
  <Relationship Id="rId5"
    Type="http://.../2006/relationships/ui/extensibility"
    Target="/customUI/customUI.xml" />
</Relationships>
```

The root element for a part of this content type is **customUI**.

For example, the following Ribbon Extensibility content markup specifies that the ribbon tab with identifier "TabHome" is to be hidden for the containing package:

```
<customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui">
  <ribbon>
    <tabs>
      <tab idMso="TabHome" visible="false" />
    </tabs>
  </ribbon>
</customUI>
```

A Ribbon Extensibility part is located within the package containing the source relationship. Expressed syntactically, the **TargetMode** attribute of the **Relationship** element is "Internal".

A Ribbon Extensibility part is permitted to have explicit relationships to the following parts defined by ECMA-376 Office Open XML File Formats, as specified in [\[ECMA-376\]](#):

- Image Part, as specified in [\[ECMA-376\]](#) Part 1 section 15.2.13.

2.2 Elements

A Custom UI document contains customizations of an application's UI. Customizations are mainly of two types:

- Modifications of the application's built-in UI, such as hiding or disabling built-in UI controls or repurposing command actions.
- Creation of custom UI controls, such as a custom ribbon tab, menu item, or quick access toolbar button.

For example, consider the following Custom UI document:

```
<customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui">
  <commands>
    <command idMso="Bold" enabled="false" />
  </commands>
  <ribbon>
    <tabs>
      <tab idMso="TabHome" visible="false" />
      <tab id="CustomTab" label="Custom Tab">
        <group id="CustomGroup" label="Custom Group">
          <button id="CustomButton" label="Custom Button"
            size="large" imageMso="HappyFace" onAction="OnButtonClick" />
        </group>
      </tab>
    </tabs>
  </ribbon>
</customUI>
```

This example disables the command with an identifier of "Bold", hides the ribbon tab with an identifier of "TabHome", and creates a new custom ribbon tab with a custom button in it.

The full XML Schema Definition of the XML Schema fragments listed in this section is defined in Appendix A of [\[MS-CUSTOMUI2\]](#).

2.2.1 box (Box Grouping Container)

This element specifies a grouping container control that can be used to align controls vertically or horizontally. **Box** elements can be nested to create complex UI layouts.

For example, consider a group of controls that are laid out horizontally, as follows:




Figure 1: Controls grouped horizontally

This layout is specified using the following XML fragment:

```

<box id="box" boxStyle="horizontal">
  <button id="button1" label="Button 1" imageMso="HappyFace" />
  <button id="button2" label="Button 2" imageMso="HappyFace" />
</box>

```

This is contrasted to the default vertical layout that is used if the **box** element is not specified.

The following table summarizes the elements that are parents of this element.

Parent Elements	Section
box	2.2.1
group	2.2.23

The following table summarizes the child elements of this element.

Child Elements	Section
box (Box Grouping Container)	2.2.1
button (Button)	2.2.2
buttonGroup (Button Grouping Container)	2.2.5
checkBox (Check Box)	2.2.6
comboBox (Combo Box)	2.2.7
control (Control Clone)	2.2.12
dropDown (Drop-down Control)	2.2.17
dynamicMenu (Dynamic Menu)	2.2.19
editBox (Edit Box)	2.2.20
gallery (Gallery)	2.2.21
labelControl (Text Label)	2.2.25
menu (Menu)	2.2.28
splitButton (Split Button)	2.2.38
toggleButton (Toggle Button)	2.2.43

The following table summarizes the attributes of this element.

Attributes	Description
boxStyle (box style)	<p>Specifies the layout direction for the child controls inside of the box element. If this attribute is omitted, the child controls SHOULD be laid out horizontally. For example, consider a group of controls to be laid out vertically. This is specified using the following XML:</p> <pre><box id="box" boxStyle="vertical"></pre>

Attributes	Description
	<p>...</p> <pre></box></pre> <p>The possible values for this attribute are defined by the ST_BoxStyle simple type, as specified in section 2.3.1.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function that is called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id and idQ attributes are mutually exclusive. At least one of these attributes is to be specified.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an id of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id and idQ attributes are mutually exclusive. At least one of these attributes is to be specified.</p> <p>For example, consider the following XML fragment:</p> <pre><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new</p>

Attributes	Description
	<p>group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 533 1289 611"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an id of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 999 1300 1077"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1465 1300 1543"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple, as specified in section 2.3.5.</p>
<p>insertBeforeQ</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted</p>

Attributes	Description
(qualified identifier of control to insert before)	<p>before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 401 1317 474"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 789 1019 810"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is to be hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Box">
  <xsd:group ref="EG_Controls" minOccurs="0" maxOccurs="1000"/>
  <xsd:attributeGroup ref="AG_IDCustom"/>
  <xsd:attributeGroup ref="AG_Visible"/>
  <xsd:attributeGroup ref="AG_PositionAttributes"/>
  <xsd:attribute name="boxStyle" type="ST_BoxStyle" use="optional"/>
</xsd:complexType>
```

2.2.2 button (Button)

This element specifies a standard push-button control that performs an action when clicked.

For example, consider a button control, as follows:



Figure 2: A button control


This is specified using the following XML fragment:

```
<button id="button" label="Button" imageMso="HappyFace" />
```

The following table summarizes the elements that are parents of this element.

Parent Elements	Section
box	2.2.1
group	2.2.23

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which is displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is always disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function that is called to determine the detailed description of this control. The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider the following XML fragment:</p> <pre><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p>


Attributes	Description
	The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2 .
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function that is called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 449 1175 474"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is to be called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 810 1138 835"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is to be called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function that is called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1171 1162 1197"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is to be called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1535 1138 1560"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is to be called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>



Attributes	Description
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 407 1235 432"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is to be called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application is to display the icon of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 827 1263 852"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is to be called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p>Specifies the name of a callback function to be called to determine whether the application is to display the label of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1247 1263 1272"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is to be called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSize (getSize callback)	<p>Specifies the name of a callback function to be called to determine the size of this control.</p> <p>The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1604 1110 1629"><button id="button" getSize="GetButtonSize" /></pre> <p>In this example, the GetButtonSize callback function is to be called when the application needs to determine the size of the button.</p>



Attributes	Description
	The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2 .
getSupertip (getSupertip callback)	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 449 1211 474"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is to be called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 810 1174 835"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is to be called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control is passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1194 1019 1220"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an id of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1539 829 1564"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified)	Specifies a qualified identifier for a control.

Attributes	Description
control identifier)	<p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1312 716"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p>Specifies the relationship identifier for an image that is to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1129 1036 1157"> <button id="button" image="ForestPic" /> </pre> <p>This specifies a custom button whose icon is to be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image that is to be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1549 1008 1577"> <button id="button" imageMso="Bold" /> </pre> <p>This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>

Attributes	Description
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 432 1289 506"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 898 1300 972"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1360 1300 1434"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the</p>

Attributes	Description
	<p>controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1317 390"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 835 1211 856"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string that is to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1108 1084 1129"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>onAction (onAction callback)</p>	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1381 1317 1402"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p>This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 596 1224 646"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>showImage (show image)</p>	<p>Specifies whether this control displays an icon. This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1169 993 1220"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control displays its label. This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1530 1172 1581"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

Attributes	Description
<p>size (control size)</p>	<p>Specifies the size of the control.</p> <p>The size and getSize attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 569 1057 594"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
<p>supertip (supertip)</p>	<p>Specifies a string that is to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1266 1224 1339"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>tag (tag)</p>	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1644 1122 1692"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre>

Attributes	Description
	<p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 489 1019 512"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an id of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Button">
  <xsd:complexContent>
    <xsd:extension base="CT_ButtonRegular">
      <xsd:attributeGroup ref="AG_SizeAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.3 button (Unsize Button)


This element specifies a push-button that, because of its location, cannot have its size changed. The **size** attribute is not present. This element otherwise behaves like the regular **button** element, as specified in section [2.2.2](#).

The following table summarizes the elements that are parents of this element.

Parent Elements	Section
buttonGroup	2.2.5
dialogBoxLauncher	2.2.15
documentControls	2.2.16
dropDown	2.2.17
gallery	2.2.21
gallery	2.2.22
menu	2.2.28
menu	2.2.26
menu	2.2.29

Parent Elements	Section
menu	2.2.27
officeMenu	2.2.31
sharedControls	2.2.35

The following table summarizes the attributes of this element.


Attributes	Description
description	<p>Specifies a detailed description of the control, which is displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is always disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control. The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider the following XML fragment:</p> <pre><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>


Attributes	Description
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 380 1174 405"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is to be called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 741 1135 766"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is to be called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function that is called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1100 1161 1125"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is to be called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1461 1135 1486"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is to be called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither</p>



Attributes	Description
	<p>attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1235 338"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is to be called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application is to display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1263 701"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is to be called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application is to display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1031 1263 1058"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is to be called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1388 1214 1415"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is to be called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1175 243"><button id="button" getVisible="IsButtonVisible" /></pre> <p data-bbox="493 275 1352 325">In this example, the IsButtonVisible callback function is to be called when the application needs to determine the visibility of the button.</p> <p data-bbox="493 333 1386 384">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p data-bbox="493 411 1382 487">Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p data-bbox="493 495 1346 546">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 554 1040 579">For example, consider the following XML fragment:</p> <pre data-bbox="521 606 1019 632"><button id="MyButton" label="Button" /></pre> <p data-bbox="493 659 1179 684">This specifies a custom button control with an id of "MyButton".</p> <p data-bbox="493 693 1393 743">The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p data-bbox="493 768 953 793">Specifies the identifier of a built-in control.</p> <p data-bbox="493 802 1065 827">The contents of this attribute are application-defined.</p> <p data-bbox="493 835 1346 886">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 894 1040 919">For example, consider the following XML fragment:</p> <pre data-bbox="521 947 829 972"><control idMso="Bold" /></pre> <p data-bbox="493 999 1154 1024">This creates a clone of the control with an identifier of "Bold".</p> <p data-bbox="493 1033 1341 1083">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p data-bbox="493 1115 953 1140">Specifies a qualified identifier for a control.</p> <p data-bbox="493 1148 1378 1199">The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p data-bbox="493 1207 1346 1257">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1266 1040 1291">For example, consider the following XML fragment:</p> <pre data-bbox="521 1318 1312 1661"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p data-bbox="493 1688 1192 1713">In this case, "ex" is an XML namespace prefix for the namespace</p>

Attributes	Description
	<p>http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 558 1032 579"><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon is to be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image to be used as the icon of this control. The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 953 1008 974"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1367 1289 1440"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the</p>

Attributes	Description
	<p>controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1300 390"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 779 1300 858"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1245 1300 1325"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (Keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p> 

Attributes	Description
	<p>This is specified using the following XML fragment:</p> <pre data-bbox="521 254 1211 279"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (Label)	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 531 1081 556"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
onAction (onAction callback)	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 804 1312 829"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p>This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1539 1222 1591"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show)	<p>Specifies whether this control displays an icon.</p>

Attributes	Description
image)	<p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 527 992 579"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (Show Label)	<p>Specifies whether this control displays its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 831 1170 884"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
supertip (Supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1608 1219 1692"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre>

Attributes	Description
	The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11 .
tag (Tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 478 1122 531"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 842 1019 863"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ButtonRegular">
  <xsd:complexContent>
    <xsd:extension base="CT_Control">
      <xsd:attributeGroup ref="AG_Action"/>
      <xsd:attributeGroup ref="AG_Enabled"/>
      <xsd:attributeGroup ref="AG_Description"/>
      <xsd:attributeGroup ref="AG_Image"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```


2.2.4 button (Button Inside of a Split Button)

This element specifies a push-button that is a child of a split button control. The **visible** and **getVisible** attributes are not present because the visibility is controlled by the split button. This element otherwise behaves in the same way as the unsized **button** element, as specified in section [2.2.3](#).

The following table summarizes the elements that are parents of this element.

Parent Elements	Section
splitButton	2.2.38
splitButton	2.2.36
splitButton	2.2.37

The following table summarizes the attributes of this element.


Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which is displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is always disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control. The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider the following XML fragment:</p> <pre><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>


Attributes	Description
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 380 1175 405"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 741 1138 766"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1100 1162 1125"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1461 1138 1486"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function that is called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither</p>



Attributes	Description
	<p>attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1239 338"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function that is called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1263 701"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function that is called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1035 1263 1062"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function that is called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1392 1211 1419"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function that is called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1175 243"><button id="button" getVisible="IsButtonVisible" /></pre> <p data-bbox="493 275 1289 327">In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p data-bbox="493 333 1386 386">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p data-bbox="493 411 1386 489">Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p data-bbox="493 495 1349 548">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 554 1040 579">For example, consider the following XML fragment:</p> <pre data-bbox="521 606 1019 632"><button id="MyButton" label="Button" /></pre> <p data-bbox="493 659 1179 684">This specifies a custom button control with an id of "MyButton".</p> <p data-bbox="493 690 1393 743">The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p data-bbox="493 768 954 793">Specifies the identifier of a built-in control.</p> <p data-bbox="493 800 1065 825">The contents of this attribute are application-defined.</p> <p data-bbox="493 831 1349 884">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 890 1040 915">For example, consider the following XML fragment:</p> <pre data-bbox="521 942 829 968"><control idMso="Bold" /></pre> <p data-bbox="493 995 1154 1020">This creates a clone of the control with an identifier of "Bold".</p> <p data-bbox="493 1026 1341 1079">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p data-bbox="493 1115 954 1140">Specifies a qualified identifier for a control.</p> <p data-bbox="493 1146 1382 1199">The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p data-bbox="493 1205 1349 1257">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1264 1040 1289">For example, consider the following XML fragment:</p> <pre data-bbox="521 1316 1312 1661"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p data-bbox="493 1688 1175 1713">In this case, ex is an XML namespace prefix for the namespace</p>

Attributes	Description
	<p>http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image that is used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 558 1036 583"><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image that is used as the icon of this control. The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 953 1008 978"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that uses the built-in image with an id of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1339 1289 1415"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are</p>

Attributes	Description
	<p>defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 289 1300 363"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 751 1300 825"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1220 1300 1293"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the custom tab with a qualified identifier of x:OtherTab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1211 243"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p data-bbox="493 275 1390 323">The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p data-bbox="493 350 1101 375">Specifies a string to be used as the label for this control.</p> <p data-bbox="493 384 1354 434">The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p data-bbox="493 443 1040 468">For example, consider the following XML fragment:</p> <pre data-bbox="521 495 1084 520"><button id="button" label="Custom Button" /></pre> <p data-bbox="493 548 1187 573">This specifies a custom button with a label of "Custom Button".</p> <p data-bbox="493 581 1386 632">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
onAction (onAction callback)	<p data-bbox="493 661 1370 711">Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p data-bbox="493 720 1040 745">For example, consider the following XML fragment:</p> <pre data-bbox="521 772 1312 798"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p data-bbox="493 825 1360 875">This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p data-bbox="493 884 1386 934">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
screentip (screentip)	<p data-bbox="493 961 1175 987">Specifies a string to be shown as the screentip for this control.</p> <p data-bbox="493 995 1390 1066">The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="493 1075 1133 1100">For example, consider a button with a screentip, as follows:</p>  <p data-bbox="493 1453 1036 1478">This is specified using the following XML fragment:</p> <pre data-bbox="521 1505 1224 1556"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="493 1583 1386 1633">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p data-bbox="493 1665 997 1690">Specifies whether this control displays an icon.</p> <p data-bbox="493 1698 1390 1724">The showImage and getShowImage attributes are mutually exclusive. If neither</p>

Attributes	Description
	<p>attribute is specified, the control SHOULD display its icon. For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 499 993 548"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control displays its label. The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label. For example, consider the following XML fragment:</p> <pre data-bbox="521 800 1172 848"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control. The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown. For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1583 1224 1661"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as</p>

Attributes	Description
	specified in section 2.3.11 .
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 449 1122 499"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 810 1019 835"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_VisibleButton">
  <xsd:complexContent>
    <xsd:restriction base="CT_ButtonRegular">
      <xsd:attribute name="visible" use="prohibited"/>
      <xsd:attribute name="getVisible" use="prohibited"/>
    </xsd:restriction>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.5 buttonGroup (Button Grouping Container)

This element specifies a grouping container that groups controls together visually. The child controls are laid out horizontally.

For example, consider a group of buttons, as follows:



Figure 3: A group of buttons

This is specified using the following XML fragment:

```
<buttonGroup id="buttonGroup">
  <button id="button1" imageMso="Bold" />
  <button id="button2" imageMso="Italic" />
  <button id="button3" imageMso="Underline" />
</buttonGroup>
```

The following table summarizes the elements that are parents of this element.

Parent Elements	Section
box	2.2.1
group	2.2.23

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
control (Unsize Control Clone)	2.2.11
dynamicMenu (Unsize Dynamic Menu)	2.2.18
gallery (Unsize Gallery)	2.2.22
menu (Unsize Menu)	2.2.26
splitButton (Unsize Split Button)	2.2.36
toggleButton (Unsize Toggle Button)	2.2.42

The following table summarizes the attributes of this element.

Attributes	Description
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id and idQ attributes are mutually exclusive. At least one of these attributes MUST be specified.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1019 275"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an id of "MyButton". The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control. The idQ attribute can be used to reference controls or containers created by other Custom UI documents. The id and idQ attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 625 1312 961"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab. The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored. The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML. For example, consider the following XML fragment:</p> <pre data-bbox="521 1409 1289 1478"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome". The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored. The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ</p>

Attributes	Description
after)	<p>attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 338 1300 415"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 804 1300 882"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the built-in tab with an id of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1266 1300 1344"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1654 1019 1682"><tab idMso="TabHome" visible="false" /></pre>

Attributes	Description
	In this example, the built-in tab with an identifier of "TabHome" is hidden. The possible values for this attribute are defined by the XML schema boolean datatype.

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ButtonGroup">
  <xsd:sequence>
    <xsd:choice minOccurs="0" maxOccurs="1000">
      <xsd:element name="control" type="CT_ControlCloneRegular"/>
      <xsd:element name="button" type="CT_ButtonRegular"/>
      <xsd:element name="toggleButton" type="CT_ToggleButtonRegular"/>
      <xsd:element name="gallery" type="CT_GalleryRegular"/>
      <xsd:element name="menu" type="CT_MenuRegular"/>
      <xsd:element name="dynamicMenu" type="CT_DynamicMenuRegular"/>
      <xsd:element name="splitButton" type="CT_SplitButtonRegular"/>
    </xsd:choice>
  </xsd:sequence>
  <xsd:attributeGroup ref="AG_IDCustom"/>
  <xsd:attributeGroup ref="AG_Visible"/>
  <xsd:attributeGroup ref="AG_PositionAttributes"/>
</xsd:complexType>
```

2.2.6 checkBox (Check Box)

This element specifies a standard checkbox control.

For example, consider a checkbox control, as follows:



Figure 4: A checkbox control

This is specified using the following XML fragment:


```
<checkBox id="checkBox" label="CheckBox" />
```

The following table summarizes the elements that are parents of this element.

Parent Elements	Section
box	2.2.1
group	2.2.23
menu	2.2.28
menu	2.2.26

Parent Elements	Section
menu	2.2.29
menu	2.2.27
officeMenu	2.2.31

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which is displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is always disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control. The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider the following XML fragment:</p> <pre><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>


Attributes	Description
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 380 1175 405"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 741 1138 766"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1100 1162 1125"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1461 1138 1486"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getPressed (getPressed callback)	<p>Specifies the name of a callback function to be called to determine the toggled state of this control.</p>



Attributes	Description
	<p>If this attribute is omitted, the control SHOULD default to the off state. For example, consider the following XML fragment:</p> <pre data-bbox="521 285 1252 310"><toggleButton id="toggle" getPressed="IsButtonToggled" /></pre> <p>In this example, the IsButtonToggled callback function is called when the application needs to determine the toggle state of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control. The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all. For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1235 699"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control. The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon. For example, consider the following XML fragment:</p> <pre data-bbox="521 1031 1260 1056"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application displays the label of this control. The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label. For example, consider the following XML fragment:</p> <pre data-bbox="521 1388 1260 1413"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control. The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown. For example, consider the following XML fragment:</p>


Attributes	Description
	<pre data-bbox="521 218 1211 243"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p data-bbox="493 275 1328 327">In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p data-bbox="493 333 1386 386">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p data-bbox="493 411 1344 464">Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p data-bbox="493 470 1386 522">The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p data-bbox="493 529 1040 554">For example, consider the following XML fragment:</p> <pre data-bbox="521 581 1174 606"><button id="button" getVisible="IsButtonVisible" /></pre> <p data-bbox="493 634 1289 686">In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p data-bbox="493 693 1386 745">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p data-bbox="493 768 1382 846">Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p data-bbox="493 852 1344 905">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 911 1040 936">For example, consider the following XML fragment:</p> <pre data-bbox="521 963 1019 989"><button id="MyButton" label="Button" /></pre> <p data-bbox="493 1016 1179 1041">This specifies a custom button control with an id of "MyButton".</p> <p data-bbox="493 1050 1393 1102">The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p data-bbox="493 1131 951 1157">Specifies the identifier of a built-in control.</p> <p data-bbox="493 1163 1065 1188">The contents of this attribute are application-defined.</p> <p data-bbox="493 1194 1344 1247">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1253 1040 1278">For example, consider the following XML fragment:</p> <pre data-bbox="521 1306 829 1331"><control idMso="Bold" /></pre> <p data-bbox="493 1358 1154 1383">This creates a clone of the control with an identifier of "Bold".</p> <p data-bbox="493 1392 1341 1444">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p data-bbox="493 1474 954 1499">Specifies a qualified identifier for a control.</p> <p data-bbox="493 1505 1378 1558">The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p data-bbox="493 1564 1344 1617">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1623 1040 1648">For example, consider the following XML fragment:</p> <pre data-bbox="521 1675 1312 1728"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui"</pre>

Attributes	Description
	<pre data-bbox="521 201 1122 489"> xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p data-bbox="493 520 1357 621">In this case, ex is an XML namespace prefix for the namespace <code>http://www.example.com</code>. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="493 632 1357 684">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="493 705 1357 785">Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="493 795 1357 848">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 858 1032 884">For example, consider the following XML fragment:</p> <pre data-bbox="521 905 1032 930"> <button id="button" image="ForestPic" /> </pre> <p data-bbox="493 961 1305 1014">This specifies a custom button whose icon is to be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="493 1024 1357 1077">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p data-bbox="493 1100 1390 1180">Specifies the identifier of a built-in image to be used as the icon of this control. The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="493 1190 1357 1243">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 1253 1032 1278">For example, consider the following XML fragment:</p> <pre data-bbox="521 1299 1008 1325"> <button id="button" imageMso="Bold" /> </pre> <p data-bbox="493 1356 1321 1381">This specifies a custom button to use the built-in image with an id of "Bold".</p> <p data-bbox="493 1392 1341 1444">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p data-bbox="493 1467 1390 1520">Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="493 1530 1390 1631">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="493 1642 1032 1667">For example, consider the following XML fragment:</p> <pre data-bbox="521 1688 1289 1713"> <tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> </pre>

Attributes	Description
	<p>...</p> <p></tab></p> <p>In this example, a new custom tab with an id of "MyTab" is inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 640 1300 716"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1102 1300 1178"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1568 1300 1644"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p>

Attributes	Description
	The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9 .
keytip (keytip)	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 558 1211 579"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 831 1081 852"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
onAction (onAction callback)	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1104 1308 1125"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p>This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 596 1224 646"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1108 993 1159"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control displays its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1411 1172 1461"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p>

Attributes	Description
	<p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 674 1224 751"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>tag (tag)</p>	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1052 1122 1104"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1415 1021 1440"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an id of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_CheckBox">
  <xsd:complexContent>
    <xsd:restriction base="CT_ToggleButtonRegular">
```

```

<xsd:attribute name="image" use="prohibited"/>
<xsd:attribute name="imageMso" use="prohibited"/>
<xsd:attribute name="getImage" use="prohibited"/>
<xsd:attribute name="showImage" use="prohibited"/>
<xsd:attribute name="getShowImage" use="prohibited"/>
<xsd:attribute name="showLabel" use="prohibited"/>
<xsd:attribute name="getShowLabel" use="prohibited"/>
</xsd:restriction>
</xsd:complexContent>
</xsd:complexType>

```

2.2.7 comboBox (Combo Box)

This element specifies a standard combo box control that allows a user to input a text **string** or select one from a list.

For example, consider a combo box control, as follows:




Figure 5: A combo box control

This is specified using the following XML fragment:

```

<comboBox id="comboBox" label="Combo Box">
  <item id="item1" label="Item 1" />
  <item id="item2" label="Item 2" />
  <item id="item3" label="Item 3" />
</comboBox>

```

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the child elements of this element.

Child Elements	Section
item (Selection Item)	2.2.24

The following table summarizes the attributes of this element.

Attributes	Description
enabled (enabled state)	Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither

Attributes	Description
	<p>attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre data-bbox="610 344 1360 390"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>getEnabled (getEnabled callback)</p>	<p>Specifies the name of a callback function to be called to determine the enabled state of this control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. For example, consider the following XML fragment:</p> <pre data-bbox="610 753 1260 779"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control. The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="610 1115 1222 1140"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemCount (getItemCount callback)</p>	<p>Specifies the name of a callback function to be called to determine the number of selection items in this control. If this attribute is omitted, the control SHOULD display any selection items that are specified as child elements. If no such items are specified, the control SHOULD be empty. For example, consider the following XML fragment:</p> <pre data-bbox="610 1503 1360 1528"><gallery id="gallery" getItemCount="GetGalleryItemCount" /></pre> <p>In this example, the GetGalleryItemCount callback function is called when the application needs to determine the number of items in the gallery. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>

Attributes	Description
getItemID (getItemID callback)	<p>Specifies the name of a callback function to be called to determine the identifier of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD have empty identifiers.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 407 1325 457"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemID="GetGalleryItemID" /></pre> <p>In this example, the GetGalleryItemID callback function is called when the application needs to determine the identifier of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getItemImage (getItemImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD NOT display icons.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 793 1325 844"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemImage="GetGalleryItemImage" /></pre> <p>In this example, the GetGalleryItemImage callback function is called when the application needs to determine the icon of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getItemLabel (getItemLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD NOT display labels.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1180 1325 1230"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemLabel="GetGalleryItemLabel" /></pre> <p>In this example, the GetGalleryItemLabel callback function is called when the application needs to determine the label of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getItemScreentip (getItemScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD use their labels as their screentips, or display no screentips at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1591 1325 1642"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemScreentip="GetGalleryItemScreentip" /></pre> <p>In this example, the GetGalleryItemScreentip callback function is called when the application needs to determine the screentip of a selection item.</p>


Attributes	Description
	<p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemSupertip (getItemSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD NOT display supertips.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 474 1325 527"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemSupertip="GetGalleryItemSupertip" /></pre> <p>In this example, the GetGalleryItemSupertip callback function is called when the application needs to determine the supertip of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 888 1247 909"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1251 1222 1272"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1633 1325 1654"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when</p>



Attributes	Description
	<p>the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 480 1349 506" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getShowImage="IsButtonImageVisible" /> </pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 892 1349 917" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getShowLabel="IsButtonLabelVisible" /> </pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1304 1300 1329" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getSupertip="GetButtonSupertip" /> </pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getText (getText callback)</p>	<p>Specifies the name of a callback function to be called to determine the text that is displayed in the control.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1606 1235 1631" style="background-color: #f0f0f0; padding: 5px;"> <editBox id="editBox" getText="GetEditBoxText" /> </pre> <p>In this example, the GetEditBoxText callback function is called when the application needs to determine the text to display in the control.</p>

Attributes	Description
	<p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 449 1260 472" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 835 1105 858" style="background-color: #f0f0f0; padding: 5px;"> <button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an id of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idMso (built-in control identifier)</p>	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1178 915 1201" style="background-color: #f0f0f0; padding: 5px;"> <control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1549 1373 1724" style="background-color: #f0f0f0; padding: 5px;"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"></pre>


Attributes	Description
	<pre data-bbox="610 201 1187 384"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p data-bbox="581 415 1382 516">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="581 527 1354 575">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p data-bbox="237 604 480 653">image (custom image identifier)</p>	<p data-bbox="581 604 1382 678">Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="581 688 1382 737">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="581 747 1127 772">For example, consider the following XML fragment:</p> <pre data-bbox="610 800 1122 825"> <button id="button" image="ForestPic" /> </pre> <p data-bbox="581 852 1333 905">This specifies a custom button whose icon is the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="581 915 1341 963">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p data-bbox="237 993 529 1041">imageMso (built-in image identifier)</p>	<p data-bbox="581 993 1341 1041">Specifies the identifier of a built-in image to be used as the icon of this control.</p> <p data-bbox="581 1052 1325 1100">The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="581 1110 1382 1159">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="581 1169 1127 1194">For example, consider the following XML fragment:</p> <pre data-bbox="610 1222 1097 1247"> <button id="button" imageMso="Bold" /> </pre> <p data-bbox="581 1274 1297 1327">This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p data-bbox="581 1337 1333 1386">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p data-bbox="237 1413 529 1486">insertAfterMso (identifier of built-in control to insert after)</p>	<p data-bbox="581 1413 1390 1486">Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 1497 1373 1598">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 1608 1127 1633">For example, consider the following XML fragment:</p> <pre data-bbox="610 1661 1373 1707"> <tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </pre>

Attributes	Description
	<p data-bbox="609 199 690 220"></tab></p> <p data-bbox="581 254 1377 304">In this example, a new custom tab with an id of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p data-bbox="581 312 1336 363">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p data-bbox="235 388 544 468">insertAfterQ (qualified identifier of control to insert after)</p>	<p data-bbox="581 388 1393 468">Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 476 1377 577">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 585 1128 611">For example, consider the following XML fragment:</p> <pre data-bbox="609 638 1388 714"> <tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p data-bbox="581 743 1377 793">In this example, a new custom tab with an id of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p data-bbox="581 802 1352 852">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p data-bbox="235 882 535 961">insertBeforeMso (identifier of built-in control to insert before)</p>	<p data-bbox="581 882 1393 961">Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 970 1377 1071">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 1079 1128 1104">For example, consider the following XML fragment:</p> <pre data-bbox="609 1131 1388 1207"> <tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p data-bbox="581 1236 1377 1287">In this example, a new custom tab with an id of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p data-bbox="581 1295 1336 1346">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p data-bbox="235 1375 544 1455">insertBeforeQ (qualified identifier of control to insert before)</p>	<p data-bbox="581 1375 1377 1455">Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 1463 1377 1564">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 1572 1128 1598">For example, consider the following XML fragment:</p> <pre data-bbox="609 1625 1323 1696"> <tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </pre>

Attributes	Description
	<p></tab></p> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>invalidateContentOnDrop (invalidate content on drop)</p>	<p>Specifies whether this control invalidates its contents and re-queries for them when the user opens its drop-down menu.</p> <p>If this attribute is omitted, its value SHOULD default to "false".</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 537 1365 611"><comboBox id="comboBox" getItemCount="GetComboBoxItemCount" getItemLabel="GetComboBoxItemLabel" invalidateContentOnDrop="true" /></pre> <p>In this example, this combo box clears out its items and re-calls the GetComboBoxItemCount and GetComboBoxItemLabel callback functions to populate its contents each time the user opens it.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="610 1108 1300 1136"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1381 1170 1409"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>maxLength (maximum input string length)</p>	<p>Specifies an integer to be used as the maximum length of a string that can be entered into the control.</p> <p>If the maxLength attribute is omitted, the length of the input string SHOULD NOT be limited, except by application-specific constraints.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="610 218 1105 241"><editBox id="editBox" maxLength="10" /></pre> <p data-bbox="581 275 1344 323">This specifies an edit box control that can only accept strings up to 10 characters in length.</p> <p data-bbox="581 333 1385 382">The possible values for this attribute are defined by the ST_StringLength simple type, as specified in section 2.3.12.</p>
onChange (onChange callback)	<p data-bbox="581 411 1377 459">Specifies the name of a callback function to be called when the text in the control has been changed by the user.</p> <p data-bbox="581 470 1127 493">For example, consider the following XML fragment:</p> <pre data-bbox="610 520 1300 543"><editBox id="editBox" onChange="EditBoxTextChanged" /></pre> <p data-bbox="581 573 1333 621">This specifies an edit box control that calls the EditBoxTextChanged callback function when the user inputs a text string.</p> <p data-bbox="581 632 1333 680">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
screentip (screentip)	<p data-bbox="581 711 1260 735">Specifies a string to be shown as the screentip for this control.</p> <p data-bbox="581 745 1365 821">The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="581 831 1219 854">For example, consider a button with a screentip, as follows:</p>  <p data-bbox="581 1203 1122 1226">This is specified using the following XML fragment:</p> <pre data-bbox="610 1253 1308 1302"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="581 1331 1377 1379">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p data-bbox="581 1415 1081 1438">Specifies whether this control displays an icon.</p> <p data-bbox="581 1449 1393 1497">The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p data-bbox="581 1507 1360 1530">For example, consider a button that does not display an icon, as follows:</p> 

Attributes	Description
	<p>This is specified using the following XML fragment:</p> <pre data-bbox="610 254 1081 302"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showItemImage (show item image)</p>	<p>Specifies whether this control displays icons on its selection items. If this attribute is omitted, the items' icons SHOULD be shown by default. For example, consider the following XML fragment:</p> <pre data-bbox="610 531 1390 684"><gallery id="gallery" label="Gallery" showItemImage="false" > <item id="item1" label="Item 1" /> <item id="item2" label="Item 1" /> <item id="item3" label="Item 2" /> <item id="item4" label="Item 3" /> </gallery></pre> <p>This specifies a gallery control that does not show any icons on its selection items.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control displays its label. The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label. For example, consider the following XML fragment:</p> <pre data-bbox="610 1024 1260 1073"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>sizeString (size string)</p>	<p>Specifies a string whose size is used to determine the width of the text input area of this control. If this attribute is omitted, the application SHOULD determine the width of the text input area of the control automatically. For example, consider the following XML fragment:</p> <pre data-bbox="610 1413 1260 1434"><editBox id="editBox" sizeString="XXXXXXXXXXXXXXXX" /></pre> <p>This specifies an edit box control that SHOULD be wide enough to display the string "XXXXXXXXXXXXXXXX".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control. The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown. For example, consider a control with a supertip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 640 1312 716"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1018 1209 1073"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1381 1112 1409"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ComboBox">
  <xsd:complexContent>
    <xsd:extension base="CT_EditBox">
      <xsd:sequence>
```

```

<xsd:element name="item" type="CT_Item" minOccurs="0" maxOccurs="1000"/>
</xsd:sequence>
<xsd:attributeGroup ref="AG_DropDownAttributes"/>
<xsd:attributeGroup ref="AG_DynamicContentAttributes"/>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>

```

2.2.8 command (Repurposed Command)

This element specifies that a particular built-in command in the application is to be repurposed.

The **enabled** and **getEnabled** attributes can be specified to disable a command.

The **onAction** attribute allows the functionality of a command to be repurposed to run a callback function. Only commands that execute simple actions (for example, commands represented as button controls) can be repurposed using **onAction**.

For example, consider the following XML fragment:

```

<commands>
  <command idMso="Bold" enabled="false" />
  <command idMso="Paste" onAction="MyPasteFunction" />
</commands>

```

In this example, the **Bold** command is permanently disabled and that the callback function **MyPasteFunction** is called when the **Paste** command is invoked.

The following table summarizes the elements that are parents of this element.

Parent Elements
commands (section 2.2.9)

The following table summarizes the attributes of this element.

Attributes	Description
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p>

Attributes	Description
callback)	<p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="548 310 1198 338"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="548 621 857 648"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
onAction (onAction callback)	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="548 894 1338 921"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p>This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Command" mixed="false">
  <xsd:attributeGroup ref="AG_Action"/>
  <xsd:attributeGroup ref="AG_Enabled"/>
  <xsd:attributeGroup ref="AG_IDMso"/>
</xsd:complexType>
```

2.2.9 commands (List of Repurposed Commands)

This element specifies a list of repurposed commands. This element SHOULD NOT be specified if the containing Custom UI XML document is a Quick Access Toolbar Customizations part.

The following table summarizes the elements that are parents of this element.

Parent Elements
customUI (section 2.2.14)

The following table summarizes the child elements of this element.

Child Elements	Subclause
command (Repurposed Command)	section 2.2.8

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Commands">
  <xsd:sequence>
    <xsd:element name="command" type="CT_Command" minOccurs="1" maxOccurs="5000"/>
  </xsd:sequence>
</xsd:complexType>
```

2.2.10 contextualTabs (List of Contextual Tab Sets)

This element specifies a list of contextual tab sets. This element SHOULD NOT be specified if the containing Custom UI XML document is a Quick Access Toolbar Customizations part.

The following table summarizes the elements that are parents of this element.

Parent Elements
ribbon (section 2.2.33)

The following table summarizes the child elements of this element.

Child Elements	Subclause
tabSet (Contextual Tab Set)	section 2.2.41

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ContextualTabs">
  <xsd:sequence>
    <xsd:element name="tabSet" type="CT_TabSet" minOccurs="1" maxOccurs="100"/>
  </xsd:sequence>
</xsd:complexType>
```

2.2.11 control (Unsize Control Clone)

This element specifies a clone of a control that, because of its location, cannot have its size changed. The **size** attribute is not present. The element otherwise behaves like the regular **control** element, as specified in section [2.2.12](#).

The following table summarizes the elements that are parents of this element.

Parent Elements
buttonGroup (section 2.2.5); menu (section 2.2.28); menu (section 2.2.26); menu (section 2.2.29); menu (section 2.2.27); officeMenu (section 2.2.31)

The following table summarizes the attributes of this element.



Attributes	Description
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 415 1317 436"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 772 1175 793"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1136 1138 1157"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1493 1162 1514"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel	<p>Specifies the name of a callback function to be called to determine the label of this</p>



Attributes	Description
(getLabel callback)	<p>control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 346 1133 369"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 730 1235 753"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1094 1263 1117"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1457 1263 1480"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither</p>

Attributes	Description
	<p>attribute is specified, no supertip for this control SHOULD be shown. For example, consider the following XML fragment:</p> <pre data-bbox="521 285 1211 310"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control. The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible. For example, consider the following XML fragment:</p> <pre data-bbox="521 646 1174 672"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 1035 1019 1060"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton". The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control. The contents of this attribute are application-defined. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 1377 829 1402"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold". The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control. The idQ attribute can be used to reference controls or containers created by other Custom UI documents. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 220 1315 562"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p data-bbox="493 594 1357 695">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="493 705 1357 758">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="493 783 1357 856">Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="493 867 1357 919">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 930 1036 951">For example, consider the following XML fragment:</p> <pre data-bbox="521 978 1032 999"> <button id="button" image="ForestPic" /> </pre> <p data-bbox="493 1035 1357 1087">This specifies a custom button whose icon is the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="493 1098 1357 1150">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p data-bbox="493 1171 1357 1245">Specifies the identifier of a built-in image to be used as the icon of this control. The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="493 1255 1357 1308">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 1318 1036 1339">For example, consider the following XML fragment:</p> <pre data-bbox="521 1367 1008 1388"> <button id="button" imageMso="Bold" /> </pre> <p data-bbox="493 1423 1357 1476">This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p data-bbox="493 1486 1357 1539">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p data-bbox="493 1560 1357 1612">Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="493 1623 1357 1717">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1289 327"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 720 1300 793"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1182 1300 1255"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1644 1313 1696"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ...</pre>

Attributes	Description
	<p></tab></p> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre>

Attributes	Description
	<p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>showImage (show image)</p>	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 642 993 695"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control displays its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 947 1170 999"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1224 296"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p data-bbox="493 323 1386 380">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p data-bbox="493 405 1393 478">Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p data-bbox="493 489 1349 541">If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p data-bbox="493 548 1040 573">For example, consider the following XML fragment:</p> <pre data-bbox="521 600 1122 648"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p data-bbox="493 680 1317 732">This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p data-bbox="493 739 1386 791">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p data-bbox="493 819 943 844">Specifies the visibility state of the control.</p> <p data-bbox="493 850 1360 903">The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p data-bbox="493 909 1040 934">For example, consider the following XML fragment:</p> <pre data-bbox="521 961 1019 987"><tab idMso="TabHome" visible="false" /></pre> <p data-bbox="493 1014 1292 1039">In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p data-bbox="493 1045 1333 1098">The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ControlCloneRegular">
  <xsd:complexContent>
    <xsd:restriction base="CT_Control">
      <xsd:attribute name="id" use="prohibited"/>
    </xsd:restriction>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.12 control (Control Clone)

This element specifies a clone of an existing control. Built-in controls can be cloned using the **idMso** attribute. Custom controls can be cloned using the **idQ** attribute. Custom controls cannot be created using the **control** element.

When an existing control is cloned, its non-location-specific properties, such as the icon and label, are copied to the clone. Location-specific properties, such as the size and visibility of the control, are not copied. These properties can be set by specifying additional attributes on the **control** element.

For example, consider the following XML fragment:

```
<control idMso="Paste" size="large" />
```

This results in a large copy of the **Paste** control, as follows:





Figure 6: A Paste control

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which is displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean</p>


Attributes	Description
	datatype.
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 422 1289 447"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 783 1175 808"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1144 1138 1169"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1507 1162 1533"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel	<p>Specifies the name of a callback function to be called to determine the label of this</p>



Attributes	Description
<p>(getLabel callback)</p>	<p>control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 344 1133 369"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 730 1235 756"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1150 1263 1176"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application displays the label of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1570 1263 1596"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type,</p>



Attributes	Description
	as specified in section 2.3.2 .
getSize (getSize callback)	<p>Specifies the name of a callback function to be called to determine the size of this control.</p> <p>The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 422 1110 447"><button id="button" getSize="GetButtonSize" /></pre> <p>In this example, the GetButtonSize callback function is called when the application needs to determine the size of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 783 1211 808"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1142 1175 1167"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1528 1021 1554"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in)	<p>Specifies the identifier of a built-in control.</p>

Attributes	Description
control identifier)	<p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 348 829 369"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 716 1312 1056"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p>Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1472 1032 1493"><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon is the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image to be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not</p>

Attributes	Description
	<p>understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 344 1008 369"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 758 1289 835"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1224 1300 1302"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1688 1300 1713"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"></pre>

Attributes	Description
	<p>...</p> <p></tab></p> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>onAction (onAction callback)</p>	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1317 243"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p data-bbox="493 275 1352 323">This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p data-bbox="493 331 1386 384">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 411 354 464">screentip (screentip)</p>	<p data-bbox="493 411 1174 436">Specifies a string to be shown as the screentip for this control.</p> <p data-bbox="493 445 1390 520">The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="493 529 1133 554">For example, consider a button with a screentip, as follows:</p>  <p data-bbox="493 903 1036 928">This is specified using the following XML fragment:</p> <pre data-bbox="521 955 1224 1008"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="493 1035 1386 1087">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 1115 451 1167">showImage (show image)</p>	<p data-bbox="493 1115 995 1140">Specifies whether this control displays an icon.</p> <p data-bbox="493 1148 1382 1201">This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p data-bbox="493 1209 1390 1262">The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p data-bbox="493 1270 1273 1295">For example, consider a button that does not display an icon, as follows:</p>  <p data-bbox="493 1476 1036 1501">This is specified using the following XML fragment:</p> <pre data-bbox="521 1528 992 1581"><button id="button" showImage="false" label="Button with no icon" /></pre> <p data-bbox="493 1608 1333 1661">The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p data-bbox="237 1692 440 1717">showLabel (show</p>	<p data-bbox="493 1692 1000 1717">Specifies whether this control displays its label.</p>

Attributes	Description
label)	<p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1170 422"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
size (control size)	<p>Specifies the size of the control.</p> <p>The size and getSize attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 947 1057 974"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1644 1219 1692"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip"</pre>

Attributes	Description
	<p>supertip="This is the supertip string" /></p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>tag (tag)</p>	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 527 1122 579"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 888 1019 909"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ControlClone">
  <xsd:complexContent>
    <xsd:restriction base="CT_Button">
      <xsd:attribute name="id" use="prohibited"/>
      <xsd:attribute name="onAction" use="prohibited"/>
    </xsd:restriction>
  </xsd:complexContent>
</xsd:complexType>
```


2.2.13 control (Quick Access Toolbar Control Clone)

This element specifies a clone of an existing control. It is specific to control clones on the quick access toolbar, but otherwise behaves the same way as the regular **control** element, as specified in section [2.2.12](#).

The following table summarizes the elements that are parents of this element.

Parent Elements
<p>documentControls (section 2.2.16); sharedControls (section 2.2.35)</p>

The following table summarizes the attributes of this element.

Attributes	Description
<p>description (description)</p>	<p>Specifies a detailed description of the control, which is displayed in detailed views.</p> <p>The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="540 577 1295 655"><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
<p>enabled (enabled state)</p>	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre data-bbox="540 961 1333 989"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>getDescription (getDescription callback)</p>	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider the following XML fragment:</p> <pre data-bbox="540 1325 1307 1352"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getEnabled (getEnabled callback)</p>	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. For example, consider the following XML fragment:</p> <pre data-bbox="540 1686 1192 1713"><button id="button" getEnabled="IsButtonEnabled" /></pre>



Attributes	Description
	<p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 512 1154 537"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 898 1179 924"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 1262 1154 1287"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 1646 1256 1671"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the</p>



Attributes	Description
	<p>application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 541 1279 562"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 961 1279 982"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSize (getSize callback)</p>	<p>Specifies the name of a callback function to be called to determine the size of this control.</p> <p>The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 1325 1127 1346"><button id="button" getSize="GetButtonSize" /></pre> <p>In this example, the GetButtonSize callback function is called when the application needs to determine the size of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 1682 1230 1703"><button id="button" getSupertip="GetButtonSupertip" /></pre>


Attributes	Description
	<p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 512 1192 537"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (custom control identifier)</p>	<p>Specifies the identifier for a custom control. All new custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 869 1045 894"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>idMso (built-in control identifier)</p>	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 1213 850 1239"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control. The identifier is qualified with an XML namespace prefix that specifies the owner of the control. If the namespace is equal to the Custom UI namespace, the idQ attribute behaves in the same manner as the idMso attribute. If the namespace is equal to the name of the current file, the idQ attribute behaves like the id attribute. If the namespace is equal to the name of a different file, the attribute references a control from that file.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="540 218 1040 348"><tab idQ="x:OtherTab"> <group id="MyGroup" label="My Group"> ... </group> </tab></pre> <p data-bbox="511 380 1377 457">In this case x is an XML namespace equal to the name of another file that has a Custom UI document with a tab with an identifier of "OtherTab". This example adds a custom group to that tab.</p> <p data-bbox="511 464 1377 516">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="511 541 1377 619">Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="511 625 1377 678">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="511 684 1057 716">For example, consider the following XML fragment:</p> <pre data-bbox="540 737 1052 762"><button id="button" image="ForestPic" /></pre> <p data-bbox="511 789 1377 842">This specifies a custom button whose icon is the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="511 848 1377 900">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p data-bbox="511 926 1377 1010">Specifies the identifier of a built-in image to be used as the icon of this control. The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="511 1016 1377 1068">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="511 1075 1057 1106">For example, consider the following XML fragment:</p> <pre data-bbox="540 1127 1027 1152"><button id="button" imageMso="Bold" /></pre> <p data-bbox="511 1180 1377 1232">This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p data-bbox="511 1239 1377 1291">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p data-bbox="511 1318 1377 1371">Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="511 1377 1377 1482">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="511 1488 1057 1520">For example, consider the following XML fragment:</p> <pre data-bbox="540 1541 1308 1619"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p data-bbox="511 1646 1377 1698">In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p data-bbox="511 1705 1377 1736">The possible values for this attribute are defined by the ST_ID simple type, as</p>

Attributes	Description
	specified in section 2.3.5 .
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 474 1321 548"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 940 1321 1014"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="542 1402 1321 1476"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
keytip (keytip)	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control</p>

Attributes	Description
	<p>automatically. For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="540 422 1230 447"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control. The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="540 695 1101 720"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button". The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control. The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all. For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="540 1409 1240 1457"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>showImage (show image)</p>	<p>Specifies whether this control displays an icon. This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large". The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p>

Attributes	Description
	<p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="540 468 1011 516"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control displays its label. This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="540 827 1190 875"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>size (control size)</p>	<p>Specifies the size of the control. The size and getSize attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="540 1402 1076 1430"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control. The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="540 638 1240 716"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="540 968 1036 993"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ControlCloneQat">
  <xsd:complexContent>
    <xsd:extension base="CT_ControlBase">
      <xsd:attribute name="id" type="ST_ID" use="optional"/>
      <xsd:attribute name="idQ" type="ST_QID" use="optional"/>
      <xsd:attributeGroup ref="AG_IDMso"/>
      <xsd:attributeGroup ref="AG_Description"/>
      <xsd:attributeGroup ref="AG_SizeAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.14 customUI (Custom UI Document Root)

This element specifies the root tag in a Custom UI XML document.

The following table summarizes the child elements of this element.

Child Elements	Section
commands (List of Repurposed Commands)	2.2.9
ribbon (Ribbon)	2.2.33

The following table summarizes the attributes of this element.

Attributes	Description
loadImage (loadImage callback)	<p>Specifies the name of a callback function to be called when the application needs to load an image for a control's icon.</p> <p>For example, consider the following XML fragment:</p> <pre><customUI xmlns="..." loadImage="LoadImageFunction" /></pre> <p>In this example, the LoadImageFunction callback is called to load icon images.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
onLoad (onLoad callback)	<p>Specifies the name of a callback function to be called when the Custom UI file is loaded by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><customUI xmlns="..." onLoad="OnCustomUILoaded" /></pre> <p>In this example, the OnCustomUILoaded callback function is called when the containing Custom UI file is loaded.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_CustomUI">
  <xsd:sequence>
    <xsd:element name="commands" type="CT_Commands" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="ribbon" type="CT_Ribbon" minOccurs="0" maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attribute name="onLoad" type="ST_Delegate" use="optional"/>
  <xsd:attribute name="loadImage" type="ST_Delegate" use="optional"/>
</xsd:complexType>
```

2.2.15 dialogBoxLauncher (Dialog Box Launcher)

This element specifies a button that is the dialog box launcher control for a ribbon group.

For example, consider a dialog box launcher control, as follows:




Figure 7: A dialog box launcher control

This is specified using the following XML fragment:

```
<group id="customGroup" label="Custom Group">
  <dialogBoxLauncher>
    <button id="button" screentip="Dialog Box Launcher" />
  </dialogBoxLauncher>
</group>
```

The following table summarizes the elements that are parents of this element.

Parent Elements
group (section 2.2.23)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_DialogLauncher">
  <xsd:sequence>
    <xsd:element name="button" type="CT_ButtonRegular" minOccurs="1" maxOccurs="1"/>
  </xsd:sequence>
</xsd:complexType>
```

2.2.16 documentControls (List of Document-Specific Quick Access Toolbar Controls)

This element specifies the list of controls on the quick access toolbar which are specific to the containing file.

For example, consider a set of controls on the document-specific quick access toolbar, as follows:




Figure 8: A set of controls on the document-specific quick access toolbar

This is specified using the following XML fragment:

```
<documentControls>
  <control idMso="CalculateNow" />
  <control idMso="HyperlinkInsert" />
</documentControls>
```

The following table summarizes the elements that are parents of this element.

Parent Elements
qat (section 2.2.32)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
control (Quick Access Toolbar Control Clone)	2.2.13
separator (Separator)	2.2.34

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_QatItems">
  <xsd:sequence>
    <xsd:choice minOccurs="0" maxOccurs="1000">
      <xsd:element name="control" type="CT_ControlCloneQat"/>
      <xsd:element name="button" type="CT_ButtonRegular"/>
      <xsd:element name="separator" type="CT_Separator"/>
    </xsd:choice>
  </xsd:sequence>
</xsd:complexType>
```

2.2.17 dropDown (Drop-down Control)

This element specifies a drop-down control that allows users to make a selection from a list of options. A drop-down control can optionally have buttons after its selection items.

For example, consider a drop-down control, as follows:



Figure 9: A drop-down control

This is specified using the following XML fragment:

```
<dropDown id="dropDown" label="DropDown">
  <item id="item1" label="Item 1" />
  <item id="item2" label="Item 2" />
  <item id="item3" label="Item 3" />
  <button id="button" label="Button..." />
</dropDown>
```

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
item (Selection Item)	2.2.24

The following table summarizes the attributes of this element.

Attributes	Description
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither</p>

Attributes	Description
	<p>attribute is specified, the control SHOULD default to being enabled. For example, consider the following XML fragment:</p> <pre data-bbox="589 289 1239 310"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="589 646 1203 667"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemCount (getItemCount callback)</p>	<p>Specifies the name of a callback function to be called to determine the number of selection items in this control.</p> <p>If this attribute is omitted, the control SHOULD display any selection items that are specified as child elements. If no such items are specified, the control SHOULD be empty. For example, consider the following XML fragment:</p> <pre data-bbox="589 1035 1341 1056"><gallery id="gallery" getItemCount="GetGalleryItemCount" /></pre> <p>In this example, the GetGalleryItemCount callback function is called when the application needs to determine the number of items in the gallery. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemID (getItemID callback)</p>	<p>Specifies the name of a callback function to be called to determine the identifier of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD have empty identifiers. For example, consider the following XML fragment:</p> <pre data-bbox="589 1392 1304 1444"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemID="GetGalleryItemID" /></pre> <p>In this example, the GetGalleryItemID callback function is called when the application needs to determine the identifier of a selection item. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemImage (getItemImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD NOT display icons.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="589 254 1304 306"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemImage="GetGalleryItemImage" /></pre> <p>In this example, the GetGalleryItemImage callback function is called when the application needs to determine the icon of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemLabel (getItemLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD NOT display labels.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 642 1304 695"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemLabel="GetGalleryItemLabel" /></pre> <p>In this example, the GetGalleryItemLabel callback function is called when the application needs to determine the label of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemScreentip (getItemScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD use their labels as their screentips, or display no screentips at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 1031 1304 1083"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemScreentip="GetGalleryItemScreentip" /></pre> <p>In this example, the GetGalleryItemScreentip callback function is called when the application needs to determine the screentip of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemSupertip (getItemSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD NOT display supertips.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 1419 1304 1472"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemSupertip="GetGalleryItemSupertip" /></pre> <p>In this example, the GetGalleryItemSupertip callback function is called when the application needs to determine the supertip of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither</p>



Attributes	Description
	<p>attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 310 1227 338"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 674 1203 701"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 1058 1305 1085"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSelectedItemID (getSelectedItemID callback)</p>	<p>Specifies the name of a callback function to be called to determine the identifier of the item to be selected in this control.</p> <p>The getSelectedItemID and getSelectedItemIndex attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display a selected item.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 1444 1305 1520"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemID="GetItemID" getSelectedItemID="GetGallerySelectedItemID" /></pre> <p>In this example, the GetGallerySelectedItemID callback function is called when the application needs to determine the selected item in the gallery. In this example the callback function returns one of the identifiers returned by the GetItemID callback function.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>


Attributes	Description
getSelectedItemIndex (getSelectedItemIndex callback)	<p>Specifies the name of a callback function to be called to determine the index of the item to be selected in this control.</p> <p>The getSelectedItemID and getSelectedItemIndex attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display a selected item.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 407 1304 457"><gallery id="gallery" getItemCount="GetGalleryItemCount" getSelectedItemIndex="GetGallerySelectedItemIndex" /></pre> <p>In this example, the GetGallerySelectedItemIndex callback function is called when the application needs to determine the selected item in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application displays the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 821 1328 842"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p>Specifies the name of a callback function to be called to determine whether the application displays the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 1182 1328 1203"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 1539 1279 1560"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>


Attributes	Description
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 380 1240 401" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getVisible="IsButtonVisible" /> </pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 764 1078 785" style="background-color: #f0f0f0; padding: 5px;"> <button id="MyButton" label="Button" /> </pre> <p>This specifies a custom button control with an id of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 1108 899 1129" style="background-color: #f0f0f0; padding: 5px;"> <control idMso="Bold" /> </pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 1478 1386 1713" style="background-color: #f0f0f0; padding: 5px;"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre>

Attributes	Description
	<pre data-bbox="589 201 743 302"></tab> </tabs> </ribbon> </customUI></pre> <p data-bbox="560 338 1390 436">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="560 447 1390 495">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="560 527 1357 600">Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="560 611 1390 659">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="560 669 1105 695">For example, consider the following XML fragment:</p> <pre data-bbox="589 720 1097 741"><button id="button" image="ForestPic" /></pre> <p data-bbox="560 772 1317 821">This specifies a custom button whose icon is the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="560 831 1390 879">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p data-bbox="560 911 1317 959">Specifies the identifier of a built-in image to be used as the icon of this control.</p> <p data-bbox="560 970 1390 1018">The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="560 1029 1390 1077">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="560 1087 1105 1113">For example, consider the following XML fragment:</p> <pre data-bbox="589 1138 1073 1159"><button id="button" imageMso="Bold" /></pre> <p data-bbox="560 1190 1377 1239">This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p data-bbox="560 1249 1377 1297">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p data-bbox="560 1331 1377 1379">Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="560 1390 1390 1488">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="560 1499 1105 1524">For example, consider the following XML fragment:</p> <pre data-bbox="589 1549 1354 1623"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p data-bbox="560 1654 1333 1703">In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p>

Attributes	Description
	The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5 .
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 499 1369 573"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 961 1369 1035"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 1423 1369 1497"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
keytip (keytip)	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither</p>

Attributes	Description
	<p>attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="589 447 1279 472"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 720 1149 745"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>onAction (onAction callback)</p>	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 993 1380 1018"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p>This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="589 218 1289 268"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="560 300 1357 350">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="235 380 451 430">showImage (show image)</p>	<p data-bbox="560 380 1377 495">Specifies whether this control displays an icon. The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon. For example, consider a button that does not display an icon, as follows:</p>  <p data-bbox="560 682 1101 709">This is specified using the following XML fragment:</p> <pre data-bbox="589 737 1057 787"><button id="button" showImage="false" label="Button with no icon" /></pre> <p data-bbox="560 816 1295 867">The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p data-bbox="235 894 509 945">showItemImage (show item image)</p>	<p data-bbox="560 894 1349 984">Specifies whether this control displays icons on its selection items. If this attribute is omitted, the items' icons SHOULD be shown by default. For example, consider the following XML fragment:</p> <pre data-bbox="589 1012 1365 1167"><gallery id="gallery" label="Gallery" showItemImage="false" > <item id="item1" label="Item 1" /> <item id="item2" label="Item 1" /> <item id="item3" label="Item 2" /> <item id="item4" label="Item 3" /> </gallery></pre> <p data-bbox="560 1197 1370 1247">This specifies a gallery control that does not show any icons on its selection items.</p> <p data-bbox="560 1260 1295 1310">The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p data-bbox="235 1339 496 1390">showItemLabel (show item label)</p>	<p data-bbox="560 1339 1357 1430">Specifies whether this control displays labels on its selection items. If this attribute is omitted, the item's labels SHOULD be shown by default. For example, consider the following XML fragment:</p> <pre data-bbox="589 1457 1365 1612"><gallery id="gallery" label="Gallery" showItemLabel="false" > <item id="item1" image="Forest" /> <item id="item2" image="Desert" /> <item id="item3" image="Mountain" /> <item id="item4" image="Ocean" /> </gallery></pre> <p data-bbox="560 1642 1378 1692">This specifies a gallery control that does not show any labels on its selection items.</p> <p data-bbox="560 1705 1295 1732">The possible values for this attribute are defined by the XML schema</p>

Attributes	Description
	boolean datatype.
showLabel (show label)	<p>Specifies whether this control displays its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 401 1240 449"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
sizeString (size string)	<p>Specifies a string whose size is used to determine the width of the text input area of this control.</p> <p>If this attribute is omitted, the application SHOULD determine the width of the text input area of the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="591 785 1240 806"><editBox id="editBox" sizeString="XXXXXXXXXXXXXXXX" /></pre> <p>This specifies an edit box control that is wide enough to display the string "XXXXXXXXXXXXXXXX".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="591 1541 1289 1619"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

Attributes	Description
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 407 1187 457"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="589 768 1084 793"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_DropDownRegular">
  <xsd:complexContent>
    <xsd:extension base="CT_Control">
      <xsd:sequence>
        <xsd:element name="item" type="CT_Item" minOccurs="0" maxOccurs="1000"/>
        <xsd:element name="button" type="CT_ButtonRegular" minOccurs="0" maxOccurs="16"/>
      </xsd:sequence>
      <xsd:attributeGroup ref="AG_Action"/>
      <xsd:attributeGroup ref="AG_Enabled"/>
      <xsd:attributeGroup ref="AG_Image"/>
      <xsd:attributeGroup ref="AG_DropDownAttributes"/>
      <xsd:attribute name="getSelectedItemID" type="ST_Delegate" use="optional"/>
      <xsd:attribute name="getSelectedItemIndex" type="ST_Delegate" use="optional"/>
      <xsd:attribute name="showItemLabel" type="xsd:boolean" use="optional"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```



2.2.18 dynamicMenu (Unsize Dynamic Menu)

This element specifies a dynamic menu control that, because of its location, cannot have its anchor size changed. The **size** attribute is not present. It otherwise behaves identically to the regular **dynamicMenu** element, as specified in section [2.2.19](#).

The following table summarizes the elements that are parents of this element.

Parent Elements
buttonGroup (section 2.2.5); menu (section 2.2.28); menu (section 2.2.26); menu (section 2.2.29); menu (section 2.2.27); officeMenu (section 2.2.31)

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which SHOULD be displayed in detailed views.</p> <p>The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getContent (getContent callback)	<p>Specifies the name of a callback function to be called when the application needs to determine the contents of the control.</p> <p>For example, consider a dynamic menu control, as follows:</p>  <p>This is specified using the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="607 218 1192 268"><dynamicMenu id="dynamic" label="Dynamic Menu" getContent="GetMenuContent" /></pre> <p data-bbox="578 300 1338 350">The GetMenuContent callback function is called when the menu is dropped, and in this case would return a string with the following XML:</p> <pre data-bbox="607 380 1386 554"><menu xmlns="http://schemas.microsoft.com/office/2006/01/customui"> <button id="button1" label="Button 1" /> <button id="button2" label="Button 2" /> <button id="button3" label="Button 3" /> </menu></pre> <p data-bbox="578 588 1338 638">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 663 526 714">getDescription (getDescription callback)</p>	<p data-bbox="578 663 1338 714">Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p data-bbox="578 722 1386 798">The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p data-bbox="578 806 1127 835">For example, consider the following XML fragment:</p> <pre data-bbox="607 861 1370 890"><button id="button" getDescription="GetButtonDescription" /></pre> <p data-bbox="578 915 1338 991">In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p data-bbox="578 999 1338 1050">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 1075 526 1125">getEnabled (getEnabled callback)</p>	<p data-bbox="578 1075 1338 1125">Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p data-bbox="578 1134 1386 1184">The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p data-bbox="578 1192 1127 1222">For example, consider the following XML fragment:</p> <pre data-bbox="607 1247 1256 1276"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p data-bbox="578 1302 1386 1352">In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p data-bbox="578 1360 1338 1411">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 1436 493 1486">getImage (getImage callback)</p>	<p data-bbox="578 1436 1386 1486">Specifies the name of a callback function to be called to determine the icon of this control.</p> <p data-bbox="578 1495 1386 1545">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="578 1554 1127 1583">For example, consider the following XML fragment:</p> <pre data-bbox="607 1608 1224 1638"><button id="button" getImage="GetButtonImage" /></pre> <p data-bbox="578 1663 1386 1713">In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p>



Attributes	Description
	<p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 472 1242 499"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 835 1218 863"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1224 1323 1251"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1581 1347 1608"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p>



Attributes	Description
	<p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 474 1349 495" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getShowLabel="IsButtonLabelVisible" /> </pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 863 1300 884" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getSupertip="GetButtonSupertip" /> </pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1220 1260 1241" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" getVisible="IsButtonVisible" /> </pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1608 1105 1629" style="background-color: #f0f0f0; padding: 5px;"> <button id="MyButton" label="Button" /> </pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID</p>

Attributes	Description
	simple type, as specified in section 2.3.13 .
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple</p>

Attributes	Description
	type, as specified in section 2.3.14 .
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image that is used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 478 1094 506"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 894 1373 968"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1381 1386 1455"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p>

Attributes	Description
	<p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 365 1386 438"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 856 1321 953"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>invalidateContentOnDrop (invalidate content on drop)</p>	<p>Specifies whether this control SHOULD invalidate its contents and re-query for them when the user opens its drop-down menu.</p> <p>If this attribute is omitted, its value SHOULD default to false.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1268 1354 1344"><comboBox id="comboBox" getItemCount="GetComboBoxItemCount" getItemLabel="GetComboBoxItemLabel" invalidateContentOnDrop="true" /></pre> <p>In this example, this combo box clears out its items and re-calls the GetComboBoxItemCount and GetComboBoxItemLabel callback functions to populate its contents each time the user opens it.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 352 1295 378"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 630 1169 655"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 1339 1308 1390"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 432 1078 485"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control SHOULD display its label. The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 758 1256 810"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control. The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 1541 1305 1619"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

Attributes	Description
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 407 1208 457"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 768 1110 798"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_DynamicMenuRegular">
  <xsd:complexContent>
    <xsd:extension base="CT_ControlBase">
      <xsd:attributeGroup ref="AG_Description"/>
      <xsd:attributeGroup ref="AG_IDAttributes"/>
      <xsd:attributeGroup ref="AG_GetContentAttributes"/>
      <xsd:attributeGroup ref="AG_DynamicContentAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.19 dynamicMenu (Dynamic Menu)

This element specifies a dynamic menu control that populates its contents dynamically.

For example, consider a dynamic menu control, as follows:



Figure 10: A dynamic menu control

This is specified using the following XML fragment:

```
<dynamicMenu id="dynamic" label="Dynamic Menu" getContent="GetMenuContent" />
```


The **GetMenuContent** callback function is called when the menu is dropped, and in this case would return a string with the following XML:


```
<menu xmlns="http://schemas.microsoft.com/office/2006/01/customui">  
  <button id="button1" label="Button 1" />  
  <button id="button2" label="Button 2" />  
  <button id="button3" label="Button 3" />  
</menu>
```

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which SHOULD be displayed in detailed views.</p> <p>The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre>

Attributes	Description
	<p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>getContent (getContent callback)</p>	<p>Specifies the name of a callback function to be called when the application needs to determine the contents of the control.</p> <p>For example, consider a dynamic menu control, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 699 1192 747"><dynamicMenu id="dynamic" label="Dynamic Menu" getContent="GetMenuContent" /></pre> <p>The GetMenuContent callback function is called when the menu is dropped, and in this case would return a string with the following XML:</p> <pre data-bbox="607 856 1386 1035"><menu xmlns="http://schemas.microsoft.com/office/2006/01/customui"> <button id="button1" label="Button 1" /> <button id="button2" label="Button 2" /> <button id="button3" label="Button 3" /> </menu></pre> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getDescription (getDescription callback)</p>	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1339 1373 1367"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getEnabled (getEnabled callback)</p>	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p>


Attributes	Description
	<pre data-bbox="610 218 1256 239" style="background-color: #f0f0f0; padding: 2px;"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p data-bbox="578 275 1390 323">In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p data-bbox="578 331 1333 380">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 411 488 459">getImage (getImage callback)</p>	<p data-bbox="578 411 1390 459">Specifies the name of a callback function to be called to determine the icon of this control.</p> <p data-bbox="578 468 1382 516">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="578 525 1125 552">For example, consider the following XML fragment:</p> <pre data-bbox="610 579 1219 600" style="background-color: #f0f0f0; padding: 2px;"><button id="button" getImage="GetButtonImage" /></pre> <p data-bbox="578 632 1390 680">In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p data-bbox="578 688 1333 737">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 768 488 816">getKeytip (getKeytip callback)</p>	<p data-bbox="578 768 1338 816">Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p data-bbox="578 825 1349 905">The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p data-bbox="578 913 1125 940">For example, consider the following XML fragment:</p> <pre data-bbox="610 968 1243 989" style="background-color: #f0f0f0; padding: 2px;"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p data-bbox="578 1020 1390 1068">In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p data-bbox="578 1077 1333 1125">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 1157 464 1205">getLabel (getLabel callback)</p>	<p data-bbox="578 1157 1390 1205">Specifies the name of a callback function to be called to determine the label of this control.</p> <p data-bbox="578 1213 1317 1262">The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p data-bbox="578 1270 1125 1297">For example, consider the following XML fragment:</p> <pre data-bbox="610 1325 1219 1346" style="background-color: #f0f0f0; padding: 2px;"><button id="button" getLabel="GetButtonLabel" /></pre> <p data-bbox="578 1377 1377 1425">In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p data-bbox="578 1434 1333 1482">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 1514 505 1562">getScreentip (getScreentip callback)</p>	<p data-bbox="578 1514 1338 1562">Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p data-bbox="578 1570 1365 1650">The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="578 1659 1125 1686">For example, consider the following XML fragment:</p>



Attributes	Description
	<pre data-bbox="609 218 1323 243"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p data-bbox="578 275 1382 325">In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p data-bbox="578 333 1333 384">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p data-bbox="578 411 1386 462">Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p data-bbox="578 470 1333 520">This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p data-bbox="578 529 1393 579">The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p data-bbox="578 588 1125 613">For example, consider the following XML fragment:</p> <pre data-bbox="609 640 1349 665"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p data-bbox="578 695 1386 770">In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p data-bbox="578 779 1333 829">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p data-bbox="578 858 1386 909">Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p data-bbox="578 917 1333 968">This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p data-bbox="578 976 1369 1052">The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p data-bbox="578 1060 1125 1085">For example, consider the following XML fragment:</p> <pre data-bbox="609 1113 1349 1138"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p data-bbox="578 1167 1393 1243">In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p data-bbox="578 1251 1333 1302">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSize (getSize callback)	<p data-bbox="578 1329 1386 1379">Specifies the name of a callback function to be called to determine the size of this control.</p> <p data-bbox="578 1388 1386 1438">The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p data-bbox="578 1446 1125 1472">For example, consider the following XML fragment:</p> <pre data-bbox="609 1499 1195 1524"><button id="button" getSize="GetButtonSize" /></pre> <p data-bbox="578 1554 1360 1604">In this example, the GetButtonSize callback function is called when the application needs to determine the size of the button.</p> <p data-bbox="578 1612 1333 1663">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip)	<p data-bbox="578 1688 1333 1713">Specifies the name of a callback function to be called to determine the</p>



Attributes	Description
callback)	<p>supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 344 1295 369"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 705 1256 730"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1094 1105 1119"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1436 915 1461"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of</p>

Attributes	Description
	<p>these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="607 289 1373 653"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1073 1117 1094"> <button id="button" image="ForestPic" /> </pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1493 1092 1514"> <button id="button" imageMso="Bold" /> </pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be</p>

Attributes	Description
after)	<p>ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 401 1373 474"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 890 1385 963"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1379 1385 1453"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and</p>

Attributes	Description
	<p>insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 338 1325 436"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab". The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>invalidateContentOnDrop (invalidate content on drop)</p>	<p>Specifies whether this control SHOULD invalidate its contents and re-query for them when the user opens its drop-down menu.</p> <p>If this attribute is omitted, its value SHOULD default to false.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 751 1360 827"><comboBox id="comboBox" getItemCount="GetComboBoxItemCount" getItemLabel="GetComboBoxItemLabel" invalidateContentOnDrop="true" /></pre> <p>In this example, this combo box clears out its items and re-calls the GetComboBoxItemCount and GetComboBoxItemLabel callback functions to populate its contents each time the user opens it. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control. The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 1325 1295 1346"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control. The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 1598 1170 1619"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button". The possible values for this attribute are defined by the ST_String simple</p>

Attributes	Description
	type, as specified in section 2.3.11 .
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 800 1308 848"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="607 1373 1081 1421"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="609 254 1258 306"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>size (control size)</p>	<p>Specifies the size of the control.</p> <p>The size and getSIZE attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 831 1144 852"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 1528 1307 1602"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

Attributes	Description
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 407 1208 457"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="607 768 1105 793"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_DynamicMenu">
  <xsd:complexContent>
    <xsd:extension base="CT_DynamicMenuRegular">
      <xsd:attributeGroup ref="AG_SizeAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.20 editBox (Edit Box)

This element specifies an edit box control that allows a user to enter a **string** of text.

For example, consider an edit box control, as follows:




Figure 11: An edit box control

This is specified using the following XML fragment:

```
<editBox id="editBox" label="Edit Box" />
```

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the attributes of this element.


Attributes	Description
enabled (Enabled State)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is</p>


Attributes	Description
	<p>specified, the application SHOULD generate a KeyTip for the control automatically. For example, consider the following XML fragment:</p> <pre data-bbox="521 285 1162 310"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 646 1133 672"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1031 1235 1056"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1392 1263 1417"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p>


Attributes	Description
	<pre data-bbox="521 218 1263 241"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p data-bbox="493 275 1354 325">In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p data-bbox="493 331 1386 382">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p data-bbox="493 409 1373 459">Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p data-bbox="493 466 1308 516">The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p data-bbox="493 522 1040 552">For example, consider the following XML fragment:</p> <pre data-bbox="521 579 1211 602"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p data-bbox="493 632 1328 682">In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p data-bbox="493 688 1386 739">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getText (getText callback)	<p data-bbox="493 766 1349 816">Specifies the name of a callback function to be called to determine the text that SHOULD be displayed in the control.</p> <p data-bbox="493 823 1040 852">For example, consider the following XML fragment:</p> <pre data-bbox="521 879 1146 903"><editBox id="editBox" getText="GetEditBoxText" /></pre> <p data-bbox="493 932 1289 982">In this example, the GetEditBoxText callback function is called when the application needs to determine the text to display in the control.</p> <p data-bbox="493 989 1386 1039">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p data-bbox="493 1071 1344 1121">Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p data-bbox="493 1127 1386 1178">The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p data-bbox="493 1184 1040 1213">For example, consider the following XML fragment:</p> <pre data-bbox="521 1241 1174 1264"><button id="button" getVisible="IsButtonVisible" /></pre> <p data-bbox="493 1293 1289 1344">In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p data-bbox="493 1350 1386 1400">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p data-bbox="493 1428 1382 1507">Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p data-bbox="493 1514 1344 1564">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1570 1040 1600">For example, consider the following XML fragment:</p> <pre data-bbox="521 1627 1019 1650"><button id="MyButton" label="Button" /></pre> <p data-bbox="493 1677 1252 1707">This specifies a custom button control with an identifier of "MyButton".</p>


Attributes	Description
	The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13 .
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control. The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 457 829 478"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 827 1312 1163"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1583 1032 1604"><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as</p>

Attributes	Description
	specified in section 2.3.14 .
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the</p>

Attributes	Description
	<p>controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1300 390"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 779 1300 858"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1297 1211 1325"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1577 1084 1604"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

Attributes	Description
maxLength (maximum input string length)	<p>Specifies an integer to be used as the maximum length of a string that can be entered into the control.</p> <p>If the maxLength attribute is omitted, the length of the input string SHOULD NOT be limited except by application-specific constraints.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 380 1019 405"><editBox id="editBox" maxLength="10" /></pre> <p>This specifies an edit box control that can only accept strings up to 10 characters in length.</p> <p>The possible values for this attribute are defined by the ST_StringLength simple type, as specified in section 2.3.12.</p>
onChange (onChange callback)	<p>Specifies the name of a callback function to be called when the text in the control has been changed by the user.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 680 1211 705"><editBox id="editBox" onChange="EditBoxTextChanged" /></pre> <p>This specifies an edit box control that calls the EditBoxTextChanged callback function when the user inputs a text string.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1415 1224 1465"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 432 993 485"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (Show Label)	<p>Specifies whether this control displays its label. The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label. For example, consider the following XML fragment:</p> <pre data-bbox="521 737 1172 789"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
sizeString (size string)	<p>Specifies a string whose size is used to determine the width of the text input area of this control. If this attribute is omitted, the application SHOULD determine the width of the text input area of the control automatically. For example, consider the following XML fragment:</p> <pre data-bbox="521 1125 1172 1146"><editBox id="editBox" sizeString="XXXXXXXXXXXXXXXX" /></pre> <p>This specifies an edit box control that is wide enough to display the string "XXXXXXXXXXXXXXXX". The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control. The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown. For example, consider a control with a supertip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 640 1224 716"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1020 1122 1073"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1381 1019 1409"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_EditBox">
  <xsd:complexContent>
    <xsd:extension base="CT_Control">
      <xsd:attributeGroup ref="AG_Enabled"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

```

<xsd:attributeGroup ref="AG_Image"/>
<xsd:attribute name="maxLength" type="ST_StringLength" use="optional"/>
<xsd:attribute name="getText" type="ST_Delegate" use="optional"/>
<xsd:attribute name="onChange" type="ST_Delegate" use="optional"/>
<xsd:attribute name="sizeString" type="ST_String" use="optional"/>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>

```

2.2.21 gallery (Gallery)

This element specifies a gallery control, which displays a drop-down grid of items that the user can select from. A gallery can optionally have buttons following its selection items.

For example, consider a gallery control that shows a selection of pictures, as follows:




Figure 12: A gallery control

This is specified using the following XML fragment:

```

<gallery id="gallery" label="Gallery" itemWidth="88" itemHeight="68"
  size="large" imageMso="HappyFace" >
  <item id="item1" image="Desert" />
  <item id="item2" image="Forest" />
  <item id="item3" image="Toucan" />
  <item id="item4" image="Tree" />
</gallery>

```


The following table summarizes the elements that are parents of this element.


Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
item (Selection Item)	2.2.24

The following table summarizes the attributes of this element.

Attributes	Description
columns (column count)	<p>Specifies the number of columns that the gallery's items SHOULD be arranged into.</p> <p>If the columns attribute is omitted, the application SHOULD choose the number of columns automatically based on the number of items.</p> <p>For example, consider a gallery control with six items arranged into two columns, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><gallery id="gallery" label="Gallery" columns="2" size="large" imageMso="HappyFace" > <item id="item1" image="Desert" /> <item id="item2" image="Forest" /> <item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> <item id="item5" image="Flowers" /> <item id="item6" image="Whale" /> </gallery></pre> <p>The possible values for this attribute are defined by the ST_GalleryRowColumnCount simple type, as specified in section 2.3.4.</p>
description (description)	<p>Specifies a detailed description of the control, which SHOULD be displayed in detailed views.</p> <p>The description and getDescription attributes are mutually exclusive. If</p>

Attributes	Description
	<p>neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="610 459 1365 533"><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the <code>ST_LongString</code> simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 848 1365 890"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1255 1365 1276"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1644 1260 1665"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the</p>

Attributes	Description
	<p>application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 480 1224 506"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemCount (getItemCount callback)</p>	<p>Specifies the name of a callback function to be called to determine the number of selection items in this control.</p> <p>If this attribute is omitted, the control SHOULD display any selection items that are specified as child elements. If no such items are specified, the control SHOULD be empty.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 867 1365 892"><gallery id="gallery" getItemCount="GetGalleryItemCount" /></pre> <p>In this example, the GetGalleryItemCount callback function is called when the application needs to determine the number of items in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemHeight (getItemHeight callback)</p>	<p>Specifies the name of a callback function to be called to determine the height of the selection items in this control.</p> <p>The itemHeight and getItemHeight attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents.</p> <p>The getItemHeight and getItemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1339 1325 1415"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemHeight="GetGalleryItemHeight" getItemWidth="GetGalleryItemWidth" /></pre> <p>In this example, the GetGalleryItemHeight callback function is called when the application needs to determine the height of the items in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemID (getItemID callback)</p>	<p>Specifies the name of a callback function to be called to determine the identifier of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD</p>

Attributes	Description
	<p>have empty identifiers. For example, consider the following XML fragment:</p> <pre data-bbox="610 289 1325 338"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemID="GetGalleryItemID" /></pre> <p>In this example, the GetGalleryItemID callback function is called when the application needs to determine the identifier of a selection item. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemImage (getItemImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD NOT display icons. For example, consider the following XML fragment:</p> <pre data-bbox="610 674 1325 722"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemImage="GetGalleryItemImage" /></pre> <p>In this example, the GetGalleryItemImage callback function is called when the application needs to determine the icon of a selection item. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemLabel (getItemLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD NOT display labels. For example, consider the following XML fragment:</p> <pre data-bbox="610 1062 1325 1110"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemLabel="GetGalleryItemLabel" /></pre> <p>In this example, the GetGalleryItemLabel callback function is called when the application needs to determine the label of a selection item. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemScreentip (getItemScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD use their labels as their screentips, or display no screentips at all. For example, consider the following XML fragment:</p> <pre data-bbox="610 1476 1325 1524"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemScreentip="GetGalleryItemScreentip" /></pre> <p>In this example, the GetGalleryItemScreentip callback function is called when the application needs to determine the screentip of a selection item. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemSupertip</p>	<p>Specifies the name of a callback function to be called to determine the</p>

Attributes	Description
(getItemSupertip callback)	<p>supertip of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD NOT display supertips.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 373 1325 426"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemSupertip="GetGalleryItemSupertip" /></pre> <p>In this example, the GetGalleryItemSupertip callback function is called when the application needs to determine the supertip of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getItemWidth (getItemWidth callback)	<p>Specifies the name of a callback function to be called to determine the width of the selection items in this control.</p> <p>The itemWidth and getItemWidth attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents.</p> <p>The getItemHeight and getItemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 846 1325 919"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemHeight="GetGalleryItemHeight" getItemWidth="GetGalleryItemWidth" /></pre> <p>In this example, the GetGalleryItemWidth callback function is called when the application needs to determine the width of the items in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1308 1247 1339"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1671 1222 1703"><button id="button" getLabel="GetButtonLabel" /></pre>

Attributes	Description
	<p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 537 1325 562"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSelectedItemID (getSelectedItemID callback)</p>	<p>Specifies the name of a callback function to be called to determine the identifier of the item that is selected in this control.</p> <p>The getSelectedItemID and getSelectedItemIndex attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display a selected item.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 926 1325 999"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemID="GetItemID" getSelectedItemID="GetGallerySelectedItemID" /></pre> <p>In this example, the GetGallerySelectedItemID callback function is called when the application needs to determine the selected item in the gallery. In this example the callback function returns one of the identifiers returned by the GetItemID callback function.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSelectedItemIndex (getSelectedItemIndex callback)</p>	<p>Specifies the name of a callback function to be called to determine the index of the item to be selected in this control.</p> <p>The getSelectedItemID and getSelectedItemIndex attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display a selected item.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1419 1325 1465"><gallery id="gallery" getItemCount="GetGalleryItemCount" getSelectedItemIndex="GetGallerySelectedItemIndex" /></pre> <p>In this example, the GetGallerySelectedItemIndex callback function is called when the application needs to determine the selected item in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p>


Attributes	Description
	<p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 373 1349 394" style="border: 1px solid black; padding: 2px;"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 846 1349 867" style="border: 1px solid black; padding: 2px;"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSize (getSize callback)</p>	<p>Specifies the name of a callback function to be called to determine the size of this control.</p> <p>The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1234 1195 1255" style="border: 1px solid black; padding: 2px;"><button id="button" getSize="GetButtonSize" /></pre> <p>In this example, the GetButtonSize callback function is called when the application needs to determine the size of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1619 1295 1640" style="border: 1px solid black; padding: 2px;"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p>



Attributes	Description
	<p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="613 449 1260 474"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="613 835 1107 861"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idMso (built-in control identifier)</p>	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="613 1178 919 1203"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="613 1549 1373 1724"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"></pre>


Attributes	Description
	<pre data-bbox="610 201 1187 384"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p data-bbox="581 415 1382 516">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="581 527 1354 575">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p data-bbox="237 604 480 653">image (custom image identifier)</p>	<p data-bbox="581 604 1386 680">Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="581 690 1382 739">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="581 749 1127 774">For example, consider the following XML fragment:</p> <pre data-bbox="610 800 1122 825"> <button id="button" image="ForestPic" /> </pre> <p data-bbox="581 856 1325 905">This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="581 915 1341 963">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p data-bbox="237 993 526 1041">imageMso (built-in image identifier)</p>	<p data-bbox="581 993 1357 1041">Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p data-bbox="581 1052 1325 1100">The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="581 1110 1382 1159">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="581 1169 1127 1194">For example, consider the following XML fragment:</p> <pre data-bbox="610 1220 1097 1245"> <button id="button" imageMso="Bold" /> </pre> <p data-bbox="581 1276 1386 1325">This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p data-bbox="581 1335 1341 1383">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p data-bbox="237 1413 526 1482">insertAfterMso (identifier of built-in control to insert after)</p>	<p data-bbox="581 1413 1395 1482">Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 1493 1373 1598">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 1608 1127 1633">For example, consider the following XML fragment:</p> <pre data-bbox="610 1659 1377 1707"> <tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </pre>

Attributes	Description
	<p data-bbox="610 201 688 222"></tab></p> <p data-bbox="581 254 1354 306">In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p data-bbox="581 317 1338 369">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p data-bbox="237 394 542 468">insertAfterQ (qualified identifier of control to insert after)</p>	<p data-bbox="581 394 1393 468">Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 478 1377 583">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 594 1127 615">For example, consider the following XML fragment:</p> <pre data-bbox="610 642 1386 716"> <tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p data-bbox="581 747 1354 800">In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p data-bbox="581 810 1354 863">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p data-bbox="237 888 542 961">insertBeforeMso (identifier of built-in control to insert before)</p>	<p data-bbox="581 888 1393 961">Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 972 1377 1077">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 1087 1127 1108">For example, consider the following XML fragment:</p> <pre data-bbox="610 1136 1386 1209"> <tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p data-bbox="581 1241 1354 1293">In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p data-bbox="581 1304 1338 1356">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p data-bbox="237 1381 542 1455">insertBeforeQ (qualified identifier of control to insert before)</p>	<p data-bbox="581 1381 1393 1455">Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="581 1465 1377 1570">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="581 1581 1127 1602">For example, consider the following XML fragment:</p> <pre data-bbox="610 1629 1321 1703"> <tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre>


Attributes	Description
	<p></tab></p> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab". The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>invalidateContentOnDrop (invalidate content on drop)</p>	<p>Specifies whether this control SHOULD invalidate its contents and re-query for them when the user opens its drop-down menu. If this attribute is omitted, its value SHOULD default to false. For example, consider the following XML fragment:</p> <pre data-bbox="613 537 1360 615"><comboBox id="comboBox" getItemCount="GetComboBoxItemCount" getItemLabel="GetComboBoxItemLabel" invalidateContentOnDrop="true" /></pre> <p>In this example, this combo box SHOULD clear out its items and re-call the GetComboBoxItemCount and GetComboBoxItemLabel callback functions to populate its contents each time the user opens it. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>itemHeight (selection item height)</p>	<p>Specifies the height of the selection items in this control. The itemHeight and getItemHeight attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents. The itemHeight and itemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored. For example, consider a gallery control with 68 pixel tall items. This is specified using the following XML fragment:</p> <pre data-bbox="613 1062 1287 1245"><gallery id="gallery" label="Gallery" itemWidth="88" itemHeight="68" size="large" imageMso="HappyFace" > <item id="item1" image="Desert" /> <item id="item2" image="Forest" /> <item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> </gallery></pre> <p>The possible values for this attribute are defined by the ST_GalleryItemWidthHeight simple type, as specified in section 2.3.3.</p>
<p>itemWidth (selection item width)</p>	<p>Specifies the width of the selection items in this control. The itemWidth and getItemWidth attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents. The itemHeight and itemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored. For example, consider a gallery control with 88 pixel wide items. This is specified using the following XML fragment:</p> <pre data-bbox="613 1608 1287 1707"><gallery id="gallery" label="Gallery" itemWidth="88" itemHeight="68" size="large" imageMso="HappyFace" > <item id="item1" image="Desert" /> <item id="item2" image="Forest" /></pre>

Attributes	Description
	<pre data-bbox="610 201 1068 275"><item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> </gallery></pre> <p data-bbox="581 306 1373 359">The possible values for this attribute are defined by the ST_GalleryItemWidthHeight simple type, as specified in section 2.3.3.</p>
<p data-bbox="237 384 402 415">keytip (keytip)</p>	<p data-bbox="581 384 1349 495">Specifies a string to be used as the suggested KeyTip for this control. The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p data-bbox="581 501 1211 527">For example, consider a button with KeyTip 'K', as follows:</p>  <p data-bbox="581 636 1122 661">This is specified using the following XML fragment:</p> <pre data-bbox="610 684 1300 709"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p data-bbox="581 741 1382 793">The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p data-bbox="237 819 375 850">label (label)</p>	<p data-bbox="581 819 1317 905">Specifies a string to be used as the label for this control. The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p data-bbox="581 911 1127 936">For example, consider the following XML fragment:</p> <pre data-bbox="610 961 1170 987"><button id="button" label="Custom Button" /></pre> <p data-bbox="581 1016 1276 1041">This specifies a custom button with a label of "Custom Button".</p> <p data-bbox="581 1050 1382 1102">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 1123 467 1176">onAction (onAction callback)</p>	<p data-bbox="581 1123 1365 1176">Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p data-bbox="581 1184 1127 1209">For example, consider the following XML fragment:</p> <pre data-bbox="610 1234 1360 1287"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p data-bbox="581 1316 1333 1369">In this example, the button calls the ButtonClicked callback function when it is invoked.</p> <p data-bbox="581 1375 1338 1428">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 1449 431 1480">rows (row count)</p>	<p data-bbox="581 1449 1349 1535">Specifies the number of rows that the gallery's items are arranged into. If the rows attribute is omitted, the application SHOULD choose the number of rows automatically based on the number of items.</p> <p data-bbox="581 1543 1354 1596">For example, consider a gallery control with six items arranged into two rows, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 722 1195 957"><gallery id="gallery" label="Gallery" rows="2" size="large" imageMso="HappyFace" > <item id="item1" image="Desert" /> <item id="item2" image="Forest" /> <item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> <item id="item5" image="Flowers" /> <item id="item6" image="Whale" /> </gallery></pre> <p>The possible values for this attribute are defined by the ST_GalleryRowColumnCount simple type, as specified in section 2.3.4.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 1612 1312 1665"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple</p>

Attributes	Description
	type, as specified in section 2.3.11 .
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 667 1079 720"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showItemImage (show item image)	<p>Specifies whether this control displays icons on its selection items.</p> <p>If this attribute is omitted, the items' icons SHOULD be shown by default.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 945 1388 1102"><gallery id="gallery" label="Gallery" showItemImage="false" > <item id="item1" label="Item 1" /> <item id="item2" label="Item 1" /> <item id="item3" label="Item 2" /> <item id="item4" label="Item 3" /> </gallery></pre> <p>This specifies a gallery control that does not show any icons on its selection items.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showItemLabel (show item label)	<p>Specifies whether this control displays labels on its selection items.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1354 1388 1512"><gallery id="gallery" label="Gallery" showItemLabel="false" > <item id="item1" image="Forest" /> <item id="item2" image="Desert" /> <item id="item3" image="Mountain " /> <item id="item4" image="Ocean" /> </gallery></pre> <p>In this example, the gallery control does not show any labels on its selection items.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showItemLabel (show item label)	<p>Specifies whether this control displays labels on its selection items.</p>

Attributes	Description
	<p>If this attribute is omitted, the item's labels SHOULD be shown by default. For example, consider the following XML fragment:</p> <pre data-bbox="610 289 1390 443"><gallery id="gallery" label="Gallery" showItemLabel="false" > <item id="item1" image="Forest" /> <item id="item2" image="Desert" /> <item id="item3" image="Mountain " /> <item id="item4" image="Ocean" /> </gallery></pre> <p>In this example, the gallery control does not show any labels on its selection items.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label. This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 842 1260 890"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
size (control size)	<p>Specifies the size of the control.</p> <p>The size and getSize attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p> <div data-bbox="581 1182 743 1352" data-label="Image"> </div> <p>This is specified using the following XML fragment:</p> <pre data-bbox="610 1415 1146 1440"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
sizeString (size string)	<p>Specifies a string whose size is used to determine the width of the text input area of this control.</p> <p>If this attribute is omitted, the application SHOULD determine the width of the text input area of the control automatically.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="613 218 1260 243"><editBox id="editBox" sizeString="WWWWWWWWWWWWW" /></pre> <p data-bbox="581 275 1382 323">This specifies an edit box control that is wide enough to display the string "WWWWWWWWWWWWW".</p> <p data-bbox="581 333 1382 382">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 411 451 436">supertip (supertip)</p>	<p data-bbox="581 411 1235 436">Specifies a string to be shown as the supertip of the control.</p> <p data-bbox="581 447 1386 495">The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p data-bbox="581 506 1214 531">For example, consider a control with a supertip, as follows:</p>  <p data-bbox="581 919 1122 945">This is specified using the following XML fragment:</p> <pre data-bbox="613 976 1308 1052"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p data-bbox="581 1083 1382 1131">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 1157 337 1182">tag (tag)</p>	<p data-bbox="581 1157 1365 1234">Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p data-bbox="581 1245 1360 1293">If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p data-bbox="581 1304 1127 1329">For example, consider the following XML fragment:</p> <pre data-bbox="613 1360 1208 1407"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p data-bbox="581 1438 1360 1486">This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p data-bbox="581 1497 1382 1545">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 1572 509 1598">visible (control visibility)</p>	<p data-bbox="581 1572 1029 1598">Specifies the visibility state of the control.</p> <p data-bbox="581 1608 1333 1656">The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p data-bbox="581 1667 1127 1692">For example, consider the following XML fragment:</p>

Attributes	Description
	<pre><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden. The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Gallery">
  <xsd:complexContent>
    <xsd:extension base="CT_GalleryRegular">
      <xsd:attributeGroup ref="AG_SizeAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.22 gallery (Unsize Gallery)

This element specifies a gallery which, because of its location, cannot have its size changed. The **size** attribute is not present. It otherwise behaves identically to the regular **gallery** element, as specified in section [2.2.21](#).

The following table summarizes the elements that are parents of this element.



Parent Elements
buttonGroup (section 2.2.5); menu (section 2.2.28); menu (section 2.2.26); menu (section 2.2.29); menu (section 2.2.27); officeMenu (section 2.2.31)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
item (Selection Item)	2.2.24

The following table summarizes the attributes of this element.

Attributes	Description
columns (column count)	<p>Specifies the number of columns that the gallery's items are arranged into. If the columns attribute is omitted, the application SHOULD choose the number of columns automatically based on the number of items.</p> <p>For example, consider a gallery control with six items arranged into two columns, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 877 1234 1117"><gallery id="gallery" label="Gallery" columns="2" size="large" imageMso="HappyFace" > <item id="item1" image="Desert" /> <item id="item2" image="Forest" /> <item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> <item id="item5" image="Flowers" /> <item id="item6" image="Whale" /> </gallery></pre> <p>The possible values for this attribute are defined by the ST_GalleryRowColumnCount simple type, as specified in section 2.3.4.</p>
<p>description (description)</p>	<p>Specifies a detailed description of the control, which SHOULD be displayed in detailed views.</p> <p>The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 1570 1364 1642"><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>

Attributes	Description
<p>enabled (enabled state)</p>	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 415 1360 464"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>getDescription (getDescription callback)</p>	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 827 1377 848"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getEnabled (getEnabled callback)</p>	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1213 1260 1234"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1575 1224 1596"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate</p>

Attributes	Description
	simple type, as specified in section 2.3.2 .
getItemCount (getItemCount callback)	<p>Specifies the name of a callback function to be called to determine the number of selection items in this control.</p> <p>If this attribute is omitted, the control SHOULD display any selection items that are specified as child elements. If no such items are specified, the control SHOULD be empty.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 449 1365 474"><gallery id="gallery" getItemCount="GetGalleryItemCount" /></pre> <p>In this example, the GetGalleryItemCount callback function is called when the application needs to determine the number of items in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getItemHeight (getItemHeight callback)	<p>Specifies the name of a callback function to be called to determine the height of the selection items in this control.</p> <p>The itemHeight and getItemHeight attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents.</p> <p>The getItemHeight and getItemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 919 1325 995"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemHeight="GetGalleryItemHeight" getItemWidth="GetGalleryItemWidth" /></pre> <p>In this example, the GetGalleryItemHeight callback function is called when the application needs to determine the height of the items in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getItemID (getItemID callback)	<p>Specifies the name of a callback function to be called to determine the identifier of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD have empty identifiers.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1381 1325 1436"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemID="GetGalleryItemID" /></pre> <p>In this example, the GetGalleryItemID callback function is called when the application needs to determine the identifier of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getItemImage (getItemImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of a specific dynamically-created selection item, identified by index.</p> <p>If this attribute is omitted, dynamically-created selection items SHOULD NOT display icons.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="610 254 1325 306"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemImage="GetGalleryItemImage" /></pre> <p>In this example, the GetGalleryItemImage callback function is called when the application needs to determine the icon of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemLabel (getItemLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD NOT display labels.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 642 1325 695"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemLabel="GetGalleryItemLabel" /></pre> <p>In this example, the GetGalleryItemLabel callback function is called when the application needs to determine the label of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemScreentip (getItemScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD use their labels as their screentips, or display no screentips at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1052 1325 1104"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemScreentip="GetGalleryItemScreentip" /></pre> <p>In this example, the GetGalleryItemScreentip callback function is called when the application needs to determine the screentip of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemSupertip (getItemSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of a specific dynamically-created selection item, identified by index. If this attribute is omitted, dynamically-created selection items SHOULD NOT display supertips.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1465 1325 1518"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemSupertip="GetGalleryItemSupertip" /></pre> <p>In this example, the GetGalleryItemSupertip callback function is called when the application needs to determine the supertip of a selection item.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getItemWidth</p>	<p>Specifies the name of a callback function to be called to determine the</p>

Attributes	Description
(getItemWidth callback)	<p>width of the selection items in this control.</p> <p>The itemWidth and getItemWidth attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents.</p> <p>The getItemHeight and getItemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 432 1325 506"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemHeight="GetGalleryItemHeight" getItemWidth="GetGalleryItemWidth" /></pre> <p>In this example, the GetGalleryItemWidth callback function is called when the application needs to determine the width of the items in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 894 1243 926"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1251 1227 1283"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1640 1325 1671"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when</p>


Attributes	Description
	<p>the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSelectedItemID (getSelectedItemID callback)</p>	<p>Specifies the name of a callback function to be called to determine the identifier of the item to be selected in this control.</p> <p>The getSelectedItemID and getSelectedItemIndex attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display a selected item.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 506 1328 583"><gallery id="gallery" getItemCount="GetGalleryItemCount" getItemID="GetItemID" getSelectedItemID="GetGallerySelectedItemID" /></pre> <p>In this example, the GetGallerySelectedItemID callback function is called when the application needs to determine the selected item in the gallery. The callback function returns one of the identifiers returned by the GetItemID callback function.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSelectedItemIndex (getSelectedItemIndex callback)</p>	<p>Specifies the name of a callback function to be called to determine the index of the item to be selected in this control.</p> <p>The getSelectedItemID and getSelectedItemIndex attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display a selected item.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 999 1328 1052"><gallery id="gallery" getItemCount="GetGalleryItemCount" getSelectedItemIndex="GetGallerySelectedItemIndex" /></pre> <p>In this example, the GetGallerySelectedItemIndex callback function is called when the application needs to determine the selected item in the gallery.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1413 1352 1436"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If</p>


Attributes	Description
	<p>neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 310 1349 338"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 722 1297 749"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1083 1260 1110"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1467 1105 1495"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idMso (built-in control identifier)</p>	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of</p>



Attributes	Description
	<p>these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 289 917 310" style="background-color: #f0f0f0; padding: 5px;"> <control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 657 1377 1024" style="background-color: #f0f0f0; padding: 5px;"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1438 1120 1459" style="background-color: #f0f0f0; padding: 5px;"> <button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be</p>

Attributes	Description
	<p>ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="610 344 1094 369"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 785 1377 856"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1276 1390 1348"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p>


Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="610 254 1390 327"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 743 1325 842"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>invalidateContentOnDrop (invalidate content on drop)</p>	<p>Specifies whether this control SHOULD invalidate its contents and re-query for them when the user opens its drop-down menu.</p> <p>If this attribute is omitted, its value SHOULD default to false.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1157 1357 1230"><comboBox id="comboBox" getItemCount="GetComboBoxItemCount" getItemLabel="GetComboBoxItemLabel" invalidateContentOnDrop="true" /></pre> <p>In this example, this combo box SHOULD clear out its items and re-call the GetComboBoxItemCount and GetComboBoxItemLabel callback functions to populate its contents each time the user opens it.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>itemHeight (selection item height)</p>	<p>Specifies the height of the selection items in this control.</p> <p>The itemHeight and getItemHeight attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents.</p> <p>The itemHeight and itemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored.</p> <p>For example, consider a gallery control with 68 pixel tall items. This is specified using the following XML fragment:</p> <pre data-bbox="610 1682 1284 1724"><gallery id="gallery" label="Gallery" itemWidth="88" itemHeight="68" size="large" imageMso="HappyFace" ></pre>

Attributes	Description
	<pre data-bbox="610 201 1068 331"><item id="item1" image="Desert" /> <item id="item2" image="Forest" /> <item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> </gallery></pre> <p data-bbox="581 363 1370 415">The possible values for this attribute are defined by the ST_GalleryItemWidthHeight simple type, as specified in section 2.3.3.</p>
itemWidth (selection item width)	<p data-bbox="581 436 1393 548">Specifies the width of the selection items in this control. The itemWidth and getItemWidth attributes are mutually exclusive. If neither attribute is specified, the items SHOULD all take the size of the first item, based on its contents.</p> <p data-bbox="581 558 1373 611">The itemHeight and itemWidth attributes are mutually required. If only one of the attributes is specified, its value is ignored.</p> <p data-bbox="581 621 1349 667">For example, consider a gallery control with 88 pixel wide items. This is specified using the following XML fragment:</p> <pre data-bbox="610 695 1287 877"><gallery id="gallery" label="Gallery" itemWidth="88" itemHeight="68" size="large" imageMso="HappyFace" > <item id="item1" image="Desert" /> <item id="item2" image="Forest" /> <item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> </gallery></pre> <p data-bbox="581 909 1370 961">The possible values for this attribute are defined by the ST_GalleryItemWidthHeight simple type, as specified in section 2.3.3.</p>
keytip (keytip)	<p data-bbox="581 982 1349 1014">Specifies a string to be used as the suggested KeyTip for this control.</p> <p data-bbox="581 1024 1349 1098">The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p data-bbox="581 1108 1211 1140">For example, consider a button with KeyTip 'K', as follows:</p>  <p data-bbox="581 1241 1122 1272">This is specified using the following XML fragment:</p> <pre data-bbox="610 1287 1295 1318"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p data-bbox="581 1346 1382 1398">The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p data-bbox="581 1417 1195 1449">Specifies a string to be used as the label for this control.</p> <p data-bbox="581 1459 1317 1512">The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p data-bbox="581 1522 1130 1554">For example, consider the following XML fragment:</p> <pre data-bbox="610 1568 1170 1600"><button id="button" label="Custom Button" /></pre> <p data-bbox="581 1627 1276 1659">This specifies a custom button with a label of "Custom Button".</p> <p data-bbox="581 1669 1382 1701">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

Attributes	Description
onAction (onAction callback)	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 321 1360 367"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p>In this example, the button calls the ButtonClicked callback function when it is invoked.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
rows (row count)	<p>Specifies the number of rows that the gallery's items are arranged into. If the rows attribute is omitted, the application SHOULD choose the number of rows automatically based on the number of items.</p> <p>For example, consider a gallery control with six items arranged into two rows, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 1209 1195 1444"><gallery id="gallery" label="Gallery" rows="2" size="large" imageMso="HappyFace" > <item id="item1" image="Desert" /> <item id="item2" image="Forest" /> <item id="item3" image="Toucan" /> <item id="item4" image="Tree" /> <item id="item5" image="Flowers" /> <item id="item6" image="Whale" /> </gallery></pre> <p>The possible values for this attribute are defined by the ST_GalleryRowColumnCount simple type, as specified in section 2.3.4.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="610 596 1312 646"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>showImage (show image)</p>	<p>Specifies whether this control displays an icon. The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon. For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="610 1110 1081 1161"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showItemImage (show item image)</p>	<p>Specifies whether this control displays icons on its selection items. If this attribute is omitted, the items' icons SHOULD be shown by default. For example, consider the following XML fragment:</p> <pre data-bbox="610 1388 1390 1543"><gallery id="gallery" label="Gallery" showItemImage="false" > <item id="item1" label="Item 1" /> <item id="item2" label="Item 1" /> <item id="item3" label="Item 2" /> <item id="item4" label="Item 3" /> </gallery></pre> <p>This specifies a gallery control that does not show any icons on its selection items.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

Attributes	Description
showItemLabel (show item label)	<p>Specifies whether this control displays labels on its selection items. For example, consider the following XML fragment:</p> <pre data-bbox="610 296 1390 453"><gallery id="gallery" label="Gallery" showItemLabel="false" > <item id="item1" image="Forest" /> <item id="item2" image="Desert" /> <item id="item3" image="Mountain" /> <item id="item4" image="Ocean" /> </gallery></pre> <p>In this example, the gallery control does not show any labels on its selection items.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label. The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 789 1260 842"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
sizeString (size string)	<p>Specifies a string whose size is used to determine the width of the text input area of this control.</p> <p>If this attribute is omitted, the application SHOULD determine the width of the text input area of the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="610 1178 1260 1199"><editBox id="editBox" sizeString="WWWWWWWWWWWW" /></pre> <p>This specifies an edit box control that is wide enough to display the string "WWWWWWWWWWWW".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control. The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="609 640 1312 716"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="ScreenTip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1018 1209 1073"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="609 1375 1112 1409"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_GalleryRegular">
  <xsd:complexContent>
    <xsd:extension base="CT_DropDownRegular">
      <xsd:attributeGroup ref="AG_Description"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

```

<xsd:attributeGroup ref="AG_DynamicContentAttributes"/>
<xsd:attribute name="columns" type="ST_GalleryRowColumnCount" use="optional"/>
<xsd:attribute name="rows" type="ST_GalleryRowColumnCount" use="optional"/>
<xsd:attribute name="itemWidth" type="ST_GalleryItemWidthHeight" use="optional"/>
<xsd:attribute name="itemHeight" type="ST_GalleryItemWidthHeight" use="optional"/>
<xsd:attribute name="getItemWidth" type="ST_Delegate" use="optional"/>
<xsd:attribute name="getItemHeight" type="ST_Delegate" use="optional"/>
<xsd:attribute name="showItemLabel" type="xsd:boolean" use="optional"/>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>

```

2.2.23 group (Group)

This element specifies a grouping of controls on a ribbon tab. All controls displayed in a ribbon tab **MUST** be contained within a **group**.

For example, consider a group with a single button, as follows:



Figure 13: A group with a single button

This is specified using the following XML fragment:

```

<group id="group" label="Custom Group">
  <button id="button" label="Button" imageMso="HappyFace" />
</group>

```

The following table summarizes the elements that are parents of this element.

Parent Elements
tab (section 2.2.39)

The following table summarizes the child elements of this element.

Child Elements	Section
box (Box Grouping Container)	2.2.1
button (Button)	2.2.2
buttonGroup (Button Grouping Container)	2.2.5
checkBox (Check Box)	2.2.6
comboBox (Combo Box)	2.2.7
control (Control Clone)	2.2.12

Child Elements	Section
dialogBoxLauncher (Dialog Box Launcher)	2.2.15
dropDown (Drop-down Control)	2.2.17
dynamicMenu (Dynamic Menu)	2.2.19
editBox (Edit Box)	2.2.20
gallery (Gallery)	2.2.21
labelControl (Text Label)	2.2.25
menu (Menu)	2.2.28
separator (Separator)	2.2.34
splitButton (Split Button)	2.2.38
toggleButton (Toggle Button)	2.2.43


The following table summarizes the attributes of this element.



Attributes	Description
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1133 243"><button id="button" getLabel="GetButtonLabel" /></pre> <p data-bbox="493 275 1289 325">In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p data-bbox="493 333 1386 384">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p data-bbox="493 411 1386 462">Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p data-bbox="493 470 1386 546">The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="493 554 1040 579">For example, consider the following XML fragment:</p> <pre data-bbox="521 606 1235 632"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p data-bbox="493 659 1338 709">In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p data-bbox="493 718 1386 768">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p data-bbox="493 795 1370 846">Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p data-bbox="493 854 1305 905">The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p data-bbox="493 913 1040 938">For example, consider the following XML fragment:</p> <pre data-bbox="521 966 1211 991"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p data-bbox="493 1018 1328 1068">In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p data-bbox="493 1077 1386 1127">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p data-bbox="493 1159 1344 1209">Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p data-bbox="493 1218 1386 1268">The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p data-bbox="493 1276 1040 1302">For example, consider the following XML fragment:</p> <pre data-bbox="521 1329 1174 1354"><button id="button" getVisible="IsButtonVisible" /></pre> <p data-bbox="493 1381 1289 1432">In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p data-bbox="493 1440 1386 1491">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p data-bbox="493 1522 1386 1598">Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p data-bbox="493 1606 1344 1656">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1665 1040 1690">For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1019 241"><button id="MyButton" label="Button" /></pre> <p data-bbox="493 275 1393 359">This specifies a custom button control with an id of "MyButton". The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p data-bbox="493 386 1347 537">Specifies the identifier of a built-in control. The contents of this attribute are application-defined. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 562 829 585"><control idMso="Bold" /></pre> <p data-bbox="493 617 1341 701">This creates a clone of the control with an identifier of "Bold". The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p data-bbox="493 726 1380 877">Specifies a qualified identifier for a control. The idQ attribute can be used to reference controls or containers created by other Custom UI documents. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 932 1312 1272"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p data-bbox="493 1304 1357 1409">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="493 1415 1360 1467">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="493 1495 1390 1568">Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="493 1577 1380 1629">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 1638 1040 1661">For example, consider the following XML fragment:</p> <pre data-bbox="521 1688 1032 1711"><button id="button" image="ForestPic" /></pre>

Attributes	Description
	<p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 573 1008 596"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 982 1289 1058"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1451 1300 1526"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted</p>

Attributes	Description
(identifier of built-in control to insert before)	<p>before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 401 1300 474"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 863 1300 936"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
keytip (keytip)	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1381 1211 1409"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1661 1084 1688"><button id="button" label="Custom Button" /></pre>

Attributes	Description
	<p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 863 1224 915"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1583 1224 1661"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as</p>

Attributes	Description
	specified in section 2.3.11 .
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 449 1122 499"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 810 1019 835"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Group">
  <xsd:sequence>
    <xsd:sequence>
      <xsd:choice minOccurs="0" maxOccurs="1000">
        <xsd:group ref="EG_Controls"/>
        <xsd:element name="separator" type="CT_Separator"/>
      </xsd:choice>
    </xsd:sequence>
    <xsd:element name="dialogBoxLauncher" type="CT_DialogLauncher" minOccurs="0"
      maxOccurs="1"/>
  </xsd:sequence>
  <xsd:attributeGroup ref="AG_IDAttributes"/>
  <xsd:attributeGroup ref="AG_Label"/>
  <xsd:attributeGroup ref="AG_Image"/>
  <xsd:attributeGroup ref="AG_PositionAttributes"/>
  <xsd:attributeGroup ref="AG_Screentip"/>
  <xsd:attributeGroup ref="AG_Visible"/>
  <xsd:attributeGroup ref="AG_Keytip"/>
</xsd:complexType>
```

2.2.24 item (Selection Item)

This element specifies an item in a selection-type control.

For example, consider a drop-down control with three selection items, as follows:



Figure 14: A drop-down control with selection items

This is specified using the following XML fragment:


```
<dropDown id="dropDown" label="DropDown">
  <item id="item1" label="Item 1" />
  <item id="item2" label="Item 2" />
  <item id="item3" label="Item 3" />
  <button id="button" label="Button..." />
</dropDown>
```


The following table summarizes the elements that are parents of this element.

Parent Elements
comboBox (section 2.2.7); dropDown (section 2.2.17); gallery (section 2.2.21); gallery (section 2.2.22)

The following table summarizes the attributes of this element.

Attributes	Description
id (custom control identifier)	<p>Specifies the identifier for a custom control. All new custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
image (custom image identifier)	<p>Specifies the identification information for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The image, and imageMso attributes are mutually exclusive.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" image="ForestPic" /></pre> <p>In this example, the custom button has an icon that is the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>

Attributes	Description
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image to be used as the icon of this control. The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The image, and imageMso attributes are mutually exclusive.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="488 390 976 411"><button id="button" imageMso="Bold" /></pre> <p>In this example, the custom button uses the built-in image with an identifier of "Bold". The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
label (label)	<p>Specifies a string to be used as the label for this control.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="488 642 1049 663"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="488 1262 1187 1314"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>For example, consider a control with a supertip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="487 640 1193 724"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Item">
  <xsd:attribute name="id" type="ST_UniqueID" use="optional"/>
  <xsd:attribute name="label" type="ST_String" use="optional"/>
  <xsd:attribute name="image" type="ST Uri" use="optional"/>
  <xsd:attribute name="imageMso" type="ST_ID" use="optional"/>
  <xsd:attribute name="screentip" type="ST_String" use="optional"/>
  <xsd:attribute name="supertip" type="ST_String" use="optional"/>
</xsd:complexType>
```

2.2.25 labelControl (Text Label)

This element specifies a control that displays a simple string of text.

For example, consider a label control, as follows:




Figure 15: A label control

This is specified using the following XML fragment:

```
<labelControl id="label" label="Label Control" />
```

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the attributes of this element.


Attributes	Description
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p>



Attributes	Description
	<pre data-bbox="521 218 1162 243"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p data-bbox="493 275 1304 327">In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p data-bbox="493 333 1386 386">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="235 411 456 464">getLabel (getLabel callback)</p>	<p data-bbox="493 411 1386 464">Specifies the name of a callback function to be called to determine the label of this control.</p> <p data-bbox="493 470 1354 522">The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p data-bbox="493 529 1040 554">For example, consider the following XML fragment:</p> <pre data-bbox="521 581 1135 606"><button id="button" getLabel="GetButtonLabel" /></pre> <p data-bbox="493 634 1289 686">In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p data-bbox="493 693 1386 745">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="235 768 402 842">getScreentip (getScreentip callback)</p>	<p data-bbox="493 768 1386 821">Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p data-bbox="493 827 1386 905">The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="493 911 1040 936">For example, consider the following XML fragment:</p> <pre data-bbox="521 963 1239 989"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p data-bbox="493 1016 1338 1068">In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p data-bbox="493 1075 1386 1127">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="235 1157 431 1230">getShowImage (getShowImage callback)</p>	<p data-bbox="493 1157 1346 1209">Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p data-bbox="493 1215 1386 1268">The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p data-bbox="493 1274 1040 1299">For example, consider the following XML fragment:</p> <pre data-bbox="521 1327 1263 1352"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p data-bbox="493 1379 1365 1432">In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p data-bbox="493 1438 1386 1491">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="235 1514 418 1587">getShowLabel (getShowLabel callback)</p>	<p data-bbox="493 1514 1346 1566">Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p data-bbox="493 1572 1365 1625">The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p data-bbox="493 1631 1040 1656">For example, consider the following XML fragment:</p> <pre data-bbox="521 1684 1263 1709"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre>


Attributes	Description
	<p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 512 1211 537"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 873 1174 898"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1262 1019 1287"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idMso (built-in control identifier)</p>	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1604 829 1629"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as</p>

Attributes	Description
	specified in section 2.3.5 .
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an</p>

Attributes	Description
	<p>identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 533 1289 611"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 999 1300 1077"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1465 1300 1543"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted</p>

Attributes	Description
(qualified identifier of control to insert before)	<p>before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 401 1317 474"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
keytip (keytip)	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 919 1211 940"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1192 1084 1213"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 596 1224 646"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1108 997 1159"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1411 1175 1461"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p>

Attributes	Description
	<p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 674 1224 751"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1052 1122 1104"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1415 1021 1440"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_LabelControl">
  <xsd:complexContent>
    <xsd:restriction base="CT_Control">
```

```

<xsd:attribute name="image" use="prohibited"/>
<xsd:attribute name="imageMso" use="prohibited"/>
<xsd:attribute name="getImage" use="prohibited"/>
<xsd:attribute name="keytip" use="prohibited"/>
<xsd:attribute name="getKeytip" use="prohibited"/>
<xsd:attribute name="showImage" use="prohibited"/>
<xsd:attribute name="getShowImage" use="prohibited"/>
</xsd:restriction>
</xsd:complexContent>
</xsd:complexType>

```

2.2.26 menu (Unsize Menu)

This element specifies a menu control that, because of its location, cannot have its size changed. The **size** attribute is not present. It otherwise behaves identically to the regular **menu** element, as specified in section [2.2.28](#).

The following table summarizes the elements that are parents of this element.


Parent Elements
buttonGroup (section 2.2.5); menu (section 2.2.28); menu (section 2.2.26); menu (section 2.2.29); splitButton (section 2.2.38); splitButton (section 2.2.36)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
checkBox (Check Box)	2.2.6
control (Unsize Control Clone)	2.2.11
dynamicMenu (Unsize Dynamic Menu)	2.2.18
gallery (Unsize Gallery)	2.2.22
menu (Unsize Menu)	2.2.26
menuSeparator (Menu Separator)	2.2.30
splitButton (Unsize Split Button)	2.2.36
toggleButton (Unsize Toggle Button)	2.2.42

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	Specifies a detailed description of the control, which SHOULD be displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:


Attributes	Description
	<div data-bbox="495 201 1065 302" style="border: 1px solid black; background-color: #ffffcc; padding: 5px;">  Button This is a verbose description that describes the function of this control in detail. </div> <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 365 1276 443"><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 751 1317 779"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1115 1289 1142"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1472 1175 1499"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p>



Attributes	Description
callback)	<p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1133 338"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1159 701"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1035 1133 1062"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1421 1235 1449"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p>



Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1263 279"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 615 1263 640"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 972 1211 997"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1333 1174 1358"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1019 241"><button id="MyButton" label="Button" /></pre> <p data-bbox="493 275 1393 359">This specifies a custom button control with an identifier of "MyButton". The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p data-bbox="493 386 1347 537">Specifies the identifier of a built-in control. The contents of this attribute are application-defined. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 562 829 585"><control idMso="Bold" /></pre> <p data-bbox="493 617 1341 701">This creates a clone of the control with an identifier of "Bold". The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p data-bbox="493 728 1380 869">Specifies a qualified identifier for a control. The idQ attribute can be used to reference controls or containers created by other Custom UI documents. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 932 1312 1272"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p data-bbox="493 1304 1357 1409">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="493 1415 1360 1467">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="493 1495 1390 1568">Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="493 1577 1380 1629">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 1638 1040 1661">For example, consider the following XML fragment:</p> <pre data-bbox="521 1688 1032 1711"><button id="button" image="ForestPic" /></pre>

Attributes	Description
	<p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 573 1008 596"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 984 1289 1058"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1451 1300 1524"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted</p>

Attributes	Description
(identifier of built-in control to insert before)	<p>before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 401 1300 474"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 863 1300 936"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
itemSize (item size)	<p>Specifies the size of the child controls in this menu.</p> <p>If this attribute is omitted, the menu's child controls SHOULD default to the normal size.</p> <p>For example, consider a menu control with large menu items, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1629 1325 1703"><menu id="menu" label="Menu with large items" itemSize="large"> <button id="button1" label="Button 1" imageMso="HappyFace" /> <button id="button2" label="Button 2" imageMso="Paste" /></pre>

Attributes	Description
	<pre data-bbox="521 201 1263 247"><button id="button3" label="Button 3" imageMso="Copy" /> </menu></pre> <p data-bbox="493 281 1386 331">The possible values for this attribute are defined by the ST_ItemSize simple type, as specified in section 2.3.6.</p>
keytip (keytip)	<p data-bbox="493 359 1386 478">Specifies a string to be used as the suggested KeyTip for this control. The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically. For example, consider a button with KeyTip 'K', as follows:</p>  <p data-bbox="493 583 1036 611">This is specified using the following XML fragment:</p> <pre data-bbox="521 636 1211 659"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p data-bbox="493 688 1386 739">The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p data-bbox="493 768 1354 852">Specifies a string to be used as the label for this control. The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="521 911 1084 934"><button id="button" label="Custom Button" /></pre> <p data-bbox="493 963 1386 1052">This specifies a custom button with a label of "Custom Button". The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
screentip (screentip)	<p data-bbox="493 1079 1386 1220">Specifies a string to be shown as the screentip for this control. The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all. For example, consider a button with a screentip, as follows:</p>  <p data-bbox="493 1566 1036 1593">This is specified using the following XML fragment:</p> <pre data-bbox="521 1619 1224 1669"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="493 1698 1386 1726">The possible values for this attribute are defined by the ST_String simple type, as</p>

Attributes	Description
	specified in section 2.3.11 .
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 611 995 659"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 915 1174 963"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1692 1224 1715"><button id="button" imageMso="HappyFace" label="Button"</pre>

Attributes	Description
	<pre>size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_MenuRegular">
  <xsd:complexContent>
    <xsd:extension base="CT_ControlBase">
      <xsd:sequence>
        <xsd:choice minOccurs="0" maxOccurs="1000">
          <xsd:group ref="EG_MenuControlsBase"/>
          <xsd:group ref="EG_MenuOrSplitButtonRegular"/>
        </xsd:choice>
      </xsd:sequence>
      <xsd:attribute name="itemSize" type="ST_ItemSize" use="optional"/>
      <xsd:attributeGroup ref="AG_Description"/>
      <xsd:attributeGroup ref="AG_IDAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.27 menu (Menu with Title)

This element specifies a menu control that, because of its location, can optionally include a title string via the **title** or **getTitle** attributes. It otherwise behaves identically to the regular **menu** element, as specified in section [2.2.28](#).

For example, consider a menu control with a title, as follows:




Figure 16: A menu control with title

This is specified with the following XML fragment:

```
<menu id="menu" label="Menu With Title" title="Title String">
  <button id="button" label="Button" />
</menu>
```

The following table summarizes the elements that are parents of this element.

Parent Elements
menu (section 2.2.27); officeMenu (section 2.2.31); splitButton (section 2.2.37)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
checkBox (Check Box)	2.2.6
control (Unsize Control Clone)	2.2.11
dynamicMenu (Unsize Dynamic Menu)	2.2.18
gallery (Unsize Gallery)	2.2.22
menu (Menu with Title)	2.2.27
menuSeparator (Menu Separator)	2.2.30
splitButton (Split Button with Title)	2.2.37
toggleButton (Unsize Toggle Button)	2.2.42

The following table summarizes the attributes of this element.

Attributes	Description
enabled (enabled state)	Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither


Attributes	Description
	<p>attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 344 1317 369"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>getEnabled (getEnabled callback)</p>	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 705 1175 730"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1066 1138 1092"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1430 1162 1455"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p>



Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1133 279"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 642 1235 667"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 999 1263 1024"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1360 1263 1386"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p>



Attributes	Description
	<pre data-bbox="521 218 1211 243"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p data-bbox="493 275 1328 327">In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p data-bbox="493 333 1386 386">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getTitle (getTitle callback)	<p data-bbox="493 411 1373 464">Specifies the name of a callback function to be called to determine the title of this control.</p> <p data-bbox="493 470 1333 522">The title and getTitle attributes are mutually exclusive. If neither attribute is specified no title SHOULD be shown.</p> <p data-bbox="493 529 1040 554">For example, consider the following XML fragment:</p> <pre data-bbox="521 581 1198 655"><menu id="menu" label="Menu" getTitle="GetMenuTitle"> ... </menu></pre> <p data-bbox="493 686 1386 739">In this example, the GetMenuTitle callback function is called when the application needs to determine the title of the menu.</p> <p data-bbox="493 745 1386 798">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p data-bbox="493 827 1344 879">Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p data-bbox="493 886 1386 938">The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p data-bbox="493 945 1040 970">For example, consider the following XML fragment:</p> <pre data-bbox="521 997 1174 1022"><button id="button" getVisible="IsButtonVisible" /></pre> <p data-bbox="493 1054 1289 1106">In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p data-bbox="493 1113 1386 1165">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p data-bbox="493 1184 1386 1268">Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p data-bbox="493 1274 1349 1327">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1333 1040 1358">For example, consider the following XML fragment:</p> <pre data-bbox="521 1386 1019 1411"><button id="MyButton" label="Button" /></pre> <p data-bbox="493 1442 1252 1467">This specifies a custom button control with an identifier of "MyButton".</p> <p data-bbox="493 1474 1386 1526">The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p data-bbox="493 1541 954 1566">Specifies the identifier of a built-in control.</p> <p data-bbox="493 1572 1068 1598">The contents of this attribute are application-defined.</p> <p data-bbox="493 1604 1349 1677">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1684 1040 1709">For example, consider the following XML fragment:</p>


Attributes	Description
	<pre data-bbox="521 218 829 239"><control idMso="Bold" /></pre> <p data-bbox="493 275 1341 359">This creates a clone of the control with an identifier of "Bold". The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p data-bbox="493 384 1382 562">Specifies a qualified identifier for a control. The idQ attribute can be used to reference controls or containers created by other Custom UI documents. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 590 1313 930"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p data-bbox="493 961 1357 1125">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab. The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="493 1150 1390 1318">Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file. The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="521 1346 1032 1367"><button id="button" image="ForestPic" /></pre> <p data-bbox="493 1398 1349 1509">This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic". The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p data-bbox="493 1539 1390 1703">Specifies the identifier of a built-in image which SHOULD be used as the icon of this control. The contents of this attribute are application-defined and SHOULD be ignored if not understood. The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1008 279"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 667 1289 741"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1136 1300 1209"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1598 1300 1671"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted</p>

Attributes	Description
	<p>before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 533 1317 611"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>itemSize (item size)</p>	<p>Specifies the size of the child controls in this menu.</p> <p>If this attribute is omitted, the menu's child controls SHOULD default to the normal size.</p> <p>For example, consider a menu control with large menu items, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1304 1328 1430"><menu id="menu" label="Menu with large items" itemSize="large"> <button id="button1" label="Button 1" imageMso="HappyFace" /> <button id="button2" label="Button 2" imageMso="Paste" /> <button id="button3" label="Button 3" imageMso="Copy" /> </menu></pre> <p>The possible values for this attribute are defined by the ST_ItemSize simple type, as specified in section 2.3.6.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 352 1211 380"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 632 1084 659"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1339 1224 1392"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 432 993 485"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 737 1172 789"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1514 1224 1587"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="ScreenTip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control.</p>

Attributes	Description
	<p>The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1122 422"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>title (title)</p>	<p>Specifies a string to be displayed as the title of the control.</p> <p>The title and getTitle attributes are mutually exclusive. If neither attribute is specified, no title SHOULD be shown.</p> <p>For example, consider a menu control with a title, as follows:</p>  <p>This is specified with the following XML fragment:</p> <pre data-bbox="521 911 1300 989"><menu id="menu" label="Menu With Title" title="Title String"> <button id="button" label="Button" /> </menu></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1241 1019 1266"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_MenuWithTitle">
  <xsd:complexContent>
    <xsd:extension base="CT_ControlBase">
      <xsd:sequence>
        <xsd:choice minOccurs="0" maxOccurs="1000">
          <xsd:group ref="EG_MenuControlsBase"/>
          <xsd:group ref="EG_MenuOrSplitButtonWithTitle"/>
        </xsd:choice>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</complexType>
```

```

<xsd:attributeGroup ref="AG_IDAttributes"/>
<xsd:attribute name="itemSize" type="ST_ItemSize" use="optional"/>
<xsd:attributeGroup ref="AG_Title"/>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>

```

2.2.28 menu (Menu)

This element specifies a drop-menu control.

For example, consider a menu control, as follows:



Figure 17: A menu control

This is specified using the following XML fragment:

```

<menu id="menu" label="Menu" imageMso="HappyFace" >
  <button id="button1" label="Button 1" imageMso="FileSave" />
  <button id="button2" label="Button 2" imageMso="Bold" />
  <button id="button3" label="Button 3" imageMso="Undo" />
</menu>

```

The following table summarizes the elements that are parents of this element.


Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
checkBox (Check Box)	2.2.6
control (Unsize Control Clone)	2.2.11
dynamicMenu (Unsize Dynamic Menu)	2.2.18
gallery (Unsize Gallery)	2.2.22
menu (Unsize Menu)	2.2.26
menuSeparator (Menu Separator)	2.2.30

Child Elements	Section
splitButton (Unsize Split Button)	2.2.36
toggleButton (Unsize Toggle Button)	2.2.42

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which SHOULD be displayed in detailed views.</p> <p>The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getEnabled	Specifies the name of a callback function to be called to determine the enabled



Attributes	Description
(getEnabled callback)	<p>state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 346 1174 369"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 705 1135 728"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1066 1162 1089"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1425 1135 1449"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the</p>



Attributes	Description
	<p>screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 285 1239 310"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 705 1263 730"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1125 1263 1150"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSize (getSize callback)</p>	<p>Specifies the name of a callback function to be called to determine the size of this control.</p> <p>The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1482 1109 1507"><button id="button" getSize="GetButtonSize" /></pre> <p>In this example, the GetButtonSize callback function is called when the application needs to determine the size of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p>



Attributes	Description
callback)	<p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1211 338"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1174 701"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1058 1019 1085"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1402 829 1430"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1317 596"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1010 1036 1037"> <button id="button" image="ForestPic" /> </pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1430 1008 1457"> <button id="button" imageMso="Bold" /> </pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the</p>

Attributes	Description
	<p>controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1289 390"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 779 1300 858"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1245 1300 1325"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1707 1313 1732"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"></pre>

Attributes	Description
	<p>...</p> <p></tab></p> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>itemSize (item size)</p>	<p>Specifies the size of the child controls in this menu.</p> <p>If this attribute is omitted, the menu's child controls SHOULD default to the normal size.</p> <p>For example, consider a menu control with large menu items, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 940 1328 1066"><menu id="menu" label="Menu with large items" itemSize="large"> <button id="button1" label="Button 1" imageMso="HappyFace" /> <button id="button2" label="Button 2" imageMso="Paste" /> <button id="button3" label="Button 3" imageMso="Copy" /> </menu></pre> <p>The possible values for this attribute are defined by the ST_ItemSize simple type, as specified in section 2.3.6.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1457 1211 1478"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1084 241"><button id="button" label="Custom Button" /></pre> <p data-bbox="493 275 1386 359">This specifies a custom button with a label of "Custom Button". The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 386 354 436">screentip (screentip)</p>	<p data-bbox="493 386 1386 531">Specifies a string to be shown as the screentip for this control. The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all. For example, consider a button with a screentip, as follows:</p>  <p data-bbox="493 877 1036 905">This is specified using the following XML fragment:</p> <pre data-bbox="521 932 1224 982"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="493 1010 1386 1060">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 1089 451 1140">showImage (show image)</p>	<p data-bbox="493 1089 1386 1266">Specifies whether this control displays an icon. This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large". The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon. For example, consider a button that does not display an icon, as follows:</p>  <p data-bbox="493 1455 1036 1482">This is specified using the following XML fragment:</p> <pre data-bbox="521 1509 997 1560"><button id="button" showImage="false" label="Button with no icon" /></pre> <p data-bbox="493 1587 1333 1638">The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p data-bbox="237 1663 440 1713">showLabel (show label)</p>	<p data-bbox="493 1663 1386 1713">Specifies whether this control SHOULD display its label. This attribute SHOULD have no effect if the size or getSize attributes specify that</p>

Attributes	Description
	<p>the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 346 1174 399"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>size (control size)</p>	<p>Specifies the size of the control.</p> <p>The size and getSize attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 919 1060 947"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1619 1222 1692"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre>

Attributes	Description
	The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11 .
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 478 1122 531"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 842 1019 863"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Menu">
  <xsd:complexContent>
    <xsd:extension base="CT_MenuRegular">
      <xsd:attributeGroup ref="AG_SizeAttributes"/>
      <xsd:attribute name="itemSize" type="ST_ItemSize" use="optional"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.29 menu (Dynamic Menu Root XML Element)

This element specifies the root tag of the XML **string** returned by a dynamic menu control.

For example, consider a dynamic menu control, as follows:



Figure 18: A dynamic menu control

This is specified using the following XML fragment:

```
<dynamicMenu id="dynamic" label="Dynamic Menu" getContent="GetMenuContent" />
```

The **GetMenuContent** callback function is called when the menu is dropped, and in this case returns a string with the following XML:



```
<menu xmlns="http://schemas.microsoft.com/office/2006/01/customui">
  <button id="button1" label="Button 1" />
  <button id="button2" label="Button 2" />
  <button id="button3" label="Button 3" />
</menu>
```

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
checkBox (Check Box)	2.2.6
control (Unsize Control Clone)	2.2.11
dynamicMenu (Unsize Dynamic Menu)	2.2.18
gallery (Unsize Gallery)	2.2.22
menu (Unsize Menu)	2.2.26
menuSeparator (Menu Separator)	2.2.30
splitButton (Unsize Split Button)	2.2.36
toggleButton (Unsize Toggle Button)	2.2.42

The following table summarizes the attributes of this element.

Attributes	Description
getTitle (getTitle callback)	<p>Specifies the name of a callback function to be called to determine the title of this control.</p> <p>The title and getTitle attributes are mutually exclusive. If neither attribute is specified no title SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre><menu id="menu" label="Menu" getTitle="GetMenuTitle"> ... </menu></pre> <p>In this example, the GetMenuTitle callback function is to be called when the application needs to determine the title of the menu.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>

Attributes	Description
<p>itemSize (item size)</p>	<p>Specifies the size of the child controls in this menu.</p> <p>If this attribute is not specified, the menu's child controls SHOULD default to the normal size.</p> <p>For example, consider a menu control with large menu items, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="505 737 1312 863"><menu id="menu" label="Menu with large items" itemSize="large"> <button id="button1" label="Button 1" imageMso="HappyFace" /> <button id="button2" label="Button 2" imageMso="Paste" /> <button id="button3" label="Button 3" imageMso="Copy" /> </menu></pre> <p>The possible values for this attribute are defined by the ST_ItemSize simple type, as specified in section 2.3.6.</p>
<p>title (title)</p>	<p>Specifies a string to be displayed as the title of the control.</p> <p>The title and getTitle attributes are mutually exclusive. If neither attribute is specified, no title SHOULD be shown.</p> <p>For example, consider a menu control with a title, as follows:</p>  <p>This is specified with the following XML fragment:</p> <pre data-bbox="505 1297 1284 1371"><menu id="menu" label="Menu With Title" title="Title String"> <button id="button" label="Button" /> </menu></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_MenuRoot">
  <xsd:sequence>
    <xsd:choice minOccurs="0" maxOccurs="1000">
      <xsd:group ref="EG_MenuControlsBase"/>
      <xsd:group ref="EG_MenuOrSplitButtonRegular"/>
    </xsd:choice>
  </xsd:sequence>
</complexType>
```

```

</xsd:sequence>
<xsd:attributeGroup ref="AG_Title"/>
<xsd:attribute name="itemSize" type="ST_ItemSize" use="optional"/>
</xsd:complexType>

```

2.2.30 menuSeparator (Menu Separator)

This element specifies a horizontal separator line in a menu control. Menu separators can optionally have title strings, which SHOULD display as headers in the menu.

For example, consider a menu with a separator in between two of its items, as follows:



Figure 19: Menu control with separator

This is specified using the following XML fragment:

```

<menu id="menu" label="Menu" imageMso="HappyFace" >
  <button id="button1" label="Button 1" imageMso="FileSave" />
  <menuSeparator id="separator" />
  <button id="button2" label="Button 2" imageMso="Bold" />
</menu>

```

The following table summarizes the elements that are parents of this element.


Parent Elements
menu (section 2.2.28); menu (section 2.2.26); menu (section 2.2.29); menu (section 2.2.27); officeMenu (section 2.2.31)

The following table summarizes the attributes of this element.

Attributes	Description
getTitle (getTitle callback)	<p>Specifies the name of a callback function to be called to determine the title of this control.</p> <p>The title and getTitle attributes are mutually exclusive. If neither attribute is specified no title SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre> <menu id="menu" label="Menu" getTitle="GetMenuTitle"> ... </menu> </pre> <p>In this example, the GetMenuTitle callback function is called when the application needs to determine the title of the menu.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>

Attributes	Description
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id and idQ attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 407 1019 428"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id and idQ attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 779 1312 1115"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertAfterMso (identifier of built-in control to insert after)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1562 1289 1633"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p>

Attributes	Description
	<p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 499 1300 575"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 968 1300 1043"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1434 1300 1509"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>title (title)</p>	<p>Specifies a string to be displayed as the title of the control.</p> <p>The title and getTitle attributes are mutually exclusive. If neither attribute is</p>

Attributes	Description
	<p>specified, no title SHOULD be shown. For example, consider a menu control with a title, as follows:</p>  <p>This is specified with the following XML fragment:</p> <pre data-bbox="521 468 1300 541"><menu id="menu" label="Menu With Title" title="Title String"> <button id="button" label="Button" /> </menu></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_MenuSeparator">
  <xsd:attributeGroup ref="AG_IDCustom"/>
  <xsd:attributeGroup ref="AG_PositionAttributes"/>
  <xsd:attributeGroup ref="AG_Title"/>
</xsd:complexType>
```

2.2.31 officeMenu (Office Menu)

This element specifies the Office Menu of the application. It is used to reference the built-in **Office** Menu. This element SHOULD NOT be specified if the containing Custom UI XML document is a Quick Access Toolbar Customizations part.

For example, consider the following XML fragment:

```
<officeMenu>
  <control idMso="FileSave" visible="false" />
</officeMenu>
```

This XML fragment specifies that the command with an identifier of "FileSave" on the Office Menu is hidden.

The following table summarizes the elements that are parents of this element.

Parent Elements
ribbon (section 2.2.33)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3

Child Elements	Section
checkBox (Check Box)	2.2.6
control (Unsize Control Clone)	2.2.11
dynamicMenu (Unsize Dynamic Menu)	2.2.18
gallery (Unsize Gallery)	2.2.22
menu (Menu with Title)	2.2.27
menuSeparator (Menu Separator)	2.2.30
splitButton (Split Button with Title)	2.2.37
toggleButton (Unsize Toggle Button)	2.2.42

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_OfficeMenu">
  <xsd:sequence>
    <xsd:choice minOccurs="0" maxOccurs="1000">
      <xsd:group ref="EG_MenuControlsBase"/>
      <xsd:group ref="EG_MenuOrSplitButtonWithTitle"/>
    </xsd:choice>
  </xsd:sequence>
</xsd:complexType>
```

2.2.32 qat (Quick Access Toolbar)

This element specifies the quick access toolbar. If the containing Custom UI file is a Ribbon Extensibility part the **qat** element cannot be used unless the **startFromScratch** attribute on the ribbon element is set to "true". In this case only the **sharedControls** child element SHOULD be used. If the containing Custom UI file is a Quick Access Toolbar Customizations part, the **documentControls** child element SHOULD be used.

For example, consider the following controls on the document-specific quick access toolbar:



Figure 20: Controls on the quick access toolbar

This is specified using the following XML fragment:

```
<qat>
  <documentControls>
    <control idMso="CalculateNow" />
    <control idMso="HyperlinkInsert" />
  </documentControls>
</qat>
```

The following table summarizes the elements that are parents of this element.

Parent Elements
ribbon (section 2.2.33)

The following table summarizes the child elements of this element.

Child Elements	Section
documentControls (List of Document-Specific Quick Access Toolbar Controls)	2.2.16
sharedControls (List of Shared Quick Access Toolbar Controls)	2.2.35

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Qat">
  <xsd:sequence>
    <xsd:element name="sharedControls" type="CT_QatItems" minOccurs="0"/>
    <xsd:element name="documentControls" type="CT_QatItems" minOccurs="0"/>
  </xsd:sequence>
</xsd:complexType>
```

2.2.33 ribbon (Ribbon)

This element is used to reference the Ribbon of the application and its contents.

The following table summarizes the elements that are parents of this element.

Parent Elements
customUI (section 2.2.14)

The following table summarizes the child elements of this element.

Child Elements	Section
contextualTabs (List of Contextual Tab Sets)	2.2.10
officeMenu (Office Menu)	2.2.31
qat (Quick Access Toolbar)	2.2.32
tabs (List of Tabs)	2.2.40

The following table summarizes the attributes of this element.

Attributes	Description
startFromScratch (start from scratch)	Specifies that the application's built-in ribbon UI is reduced to a minimal set of features, providing a clean slate on which to build custom UI. If this attribute is omitted, its value SHOULD default to "false". For example, consider the following XML fragment: <pre><ribbon startFromScratch="true"> ...</pre>

Attributes	Description
	<p data-bbox="602 201 716 222"></ribbon></p> <p data-bbox="570 254 1395 338">In this example, the application's ribbon is put into start from scratch mode. The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```

<xsd:complexType name="CT_Ribbon">
  <xsd:all>
    <xsd:element name="officeMenu" type="CT_OfficeMenu" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="qat" type="CT_Qat" minOccurs="0" maxOccurs="1">
      <xsd:unique name="qatControls">
        <xsd:selector xpath="*/**"/>
        <xsd:field xpath="@id"/>
      </xsd:unique>
    </xsd:element>
    <xsd:element name="tabs" type="CT_Tabs" minOccurs="0" maxOccurs="1"/>
    <xsd:element name="contextualTabs" type="CT_ContextualTabs" minOccurs="0" maxOccurs="1"/>
  </xsd:all>
  <xsd:attribute name="startFromScratch" type="xsd:boolean" use="optional"/>
</xsd:complexType>

```

2.2.34 separator (Separator)

This element specifies a vertical separator line between two sets of controls, either in the Quick Access Toolbar or within **group** elements.

For example, consider a vertical separator control between two buttons, as follows:



Figure 21: A vertical separator control

This is specified using the following XML fragment:

```

<button id="button1" label="Button 1" imageMso="HappyFace" size="large" />
<separator id="separator" />
<button id="button2" label="Button 2" imageMso="HappyFace" size="large" />

```

The following table summarizes the elements that are parents of this element.

Parent Elements
documentControls (section 2.2.16); group (section 2.2.23); sharedControls (section 2.2.35)

The following table summarizes the attributes of this element.

Attributes	Description
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 380 1175 405"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id and idQ attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 764 1019 789"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id and idQ attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1136 1312 1476"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertAfterMso	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted</p>

Attributes	Description
(identifier of built-in control to insert after)	<p>after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 401 1289 474"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 863 1300 936"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1325 1300 1398"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are</p>

Attributes	Description
	<p>defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 289 1317 363"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 678 1019 699"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_Separator">
  <xsd:attributeGroup ref="AG_IDCustom"/>
  <xsd:attributeGroup ref="AG_Visible"/>
  <xsd:attributeGroup ref="AG_PositionAttributes"/>
</xsd:complexType>
```

2.2.35 sharedControls (List of Shared Quick Access Toolbar Controls)

This element specifies the section of the quick access toolbar that is shared among all documents. This element SHOULD NOT be specified if the containing Custom UI XML document is a Quick Access Toolbar Customizations part. If the containing Custom UI XML document is a Ribbon Extensibility part, this element can be used if the **startFromScratch** attribute is set to "true" on the ribbon element.

For example, consider a Ribbon Extensibility XML document that adds the two buttons to the shared section of the quick access toolbar:



Figure 22: Shared controls on the quick access toolbar

This is specified using the following XML fragment:

```
<qat>
  <sharedControls>
    <button id="button1" imageMso="HappyFace" />
```

```

    <button idMso="Cut" />
  </sharedControls>
</qat>

```

The following table summarizes the elements that are parents of this element.

Parent Elements
qat (section 2.2.32)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Unsize Button)	2.2.3
control (Quick Access Toolbar Control Clone)	2.2.13
separator (Separator)	2.2.34

The following XML schema fragment defines the contents of this element:

```

<xsd:complexType name="CT_QatItems">
  <xsd:sequence>
    <xsd:choice minOccurs="0" maxOccurs="1000">
      <xsd:element name="control" type="CT_ControlCloneQat"/>
      <xsd:element name="button" type="CT_ButtonRegular"/>
      <xsd:element name="separator" type="CT_Separator"/>
    </xsd:choice>
  </xsd:sequence>
</xsd:complexType>

```

2.2.36 splitButton (Unsize Split Button)

This element specifies a split button control that, because of its location, cannot have its size changed. The **size** attribute is not present. It otherwise behaves identically to the regular **splitButton** element, as specified in section [2.2.38](#).

The following table summarizes the elements that are parents of this element.

Parent Elements
buttonGroup (section 2.2.5); menu (section 2.2.28); menu (section 2.2.26); menu (section 2.2.29)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Button Inside of a Split Button)	2.2.4
menu (Unsize Menu)	2.2.26
toggleButton (Toggle Button Inside of a Split Button)	2.2.44

The following table summarizes the attributes of this element.



Attributes	Description
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 468 1317 491"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 827 1175 850"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1186 1138 1209"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1549 1162 1572"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>



Attributes	Description
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 380 1133 405"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 764 1235 789"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1125 1263 1150"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1486 1263 1512"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p>

Attributes	Description
callback)	<p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1211 338"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1174 701"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1058 1019 1085"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1402 829 1430"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1317 596"> <customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI> </pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1010 1036 1037"> <button id="button" image="ForestPic" /> </pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1430 1008 1457"> <button id="button" imageMso="Bold" /> </pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the</p>

Attributes	Description
	<p>controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1289 390"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 779 1300 858"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1245 1300 1325"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1707 1317 1732"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"></pre>

Attributes	Description
	<p>...</p> <p></tab></p> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 695 1211 720"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 972 1084 997"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1682 1224 1707"><button id="button" imageMso="HappyFace" label="Button"</pre>

Attributes	Description
	<pre>size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>showImage (show image)</p>	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control SHOULD display its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p> 

Attributes	Description
	<p>This is specified using the following XML fragment:</p> <pre data-bbox="521 254 1224 331"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 632 1122 684"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 995 1019 1016"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_SplitButtonRegular">
  <xsd:complexContent>
    <xsd:extension base="CT_SplitButtonRestricted">
      <xsd:sequence minOccurs="0">
        <xsd:choice minOccurs="0">
          <xsd:element name="button" type="CT_VisibleButton"/>
          <xsd:element name="toggleButton" type="CT_VisibleToggleButton"/>
        </xsd:choice>
        <xsd:element name="menu" type="CT_MenuRegular"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.37 splitButton (Split Button with Title)

This element specifies a split button control that, because of its location, can optionally include a title string via the **title** or **getTitle** attributes. It otherwise behaves identically to the regular **splitButton** element, as specified in section [2.2.38](#).

The following table summarizes the elements that are parents of this element.

Parent Elements
menu (section 2.2.27); officeMenu (section 2.2.31)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Button Inside of a Split Button)	2.2.4
menu (Menu with Title)	2.2.27
toggleButton (Toggle Button Inside of a Split Button)	2.2.44

The following table summarizes the attributes of this element.


Attributes	Description
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none</p>



Attributes	Description
	<p>of these attributes are specified, no icon SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="521 285 1133 310"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control. The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically. For example, consider the following XML fragment:</p> <pre data-bbox="521 646 1159 672"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control. The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="521 1003 1133 1029"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control. The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all. For example, consider the following XML fragment:</p> <pre data-bbox="521 1392 1235 1417"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control. The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon. For example, consider the following XML fragment:</p>


Attributes	Description
	<pre data-bbox="521 218 1263 243"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p data-bbox="493 275 1365 327">In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p data-bbox="493 333 1386 386">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p data-bbox="493 411 1344 464">Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p data-bbox="493 470 1365 522">The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p data-bbox="493 529 1040 554">For example, consider the following XML fragment:</p> <pre data-bbox="521 581 1263 606"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p data-bbox="493 634 1354 686">In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p data-bbox="493 693 1386 745">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p data-bbox="493 768 1373 821">Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p data-bbox="493 827 1308 879">The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p data-bbox="493 886 1040 911">For example, consider the following XML fragment:</p> <pre data-bbox="521 938 1211 963"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p data-bbox="493 991 1328 1043">In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p data-bbox="493 1050 1386 1102">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p data-bbox="493 1131 1344 1184">Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p data-bbox="493 1190 1386 1243">The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p data-bbox="493 1249 1040 1274">For example, consider the following XML fragment:</p> <pre data-bbox="521 1302 1174 1327"><button id="button" getVisible="IsButtonVisible" /></pre> <p data-bbox="493 1354 1289 1407">In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p data-bbox="493 1413 1386 1465">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p data-bbox="493 1495 1382 1568">Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p data-bbox="493 1575 1344 1627">The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p data-bbox="493 1633 1040 1659">For example, consider the following XML fragment:</p> <pre data-bbox="521 1686 1019 1711"><button id="MyButton" label="Button" /></pre>

Attributes	Description
	<p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idMso (built-in control identifier)</p>	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 495 829 520"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 865 1312 1205"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1621 1032 1646"><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p>

Attributes	Description
	The possible values for this attribute are defined by the ST Uri simple type, as specified in section 2.3.14 .
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 506 1008 531"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 919 1289 995"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST ID simple type, as specified in section 2.3.5.</p>
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1383 1304 1459"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ</p>

Attributes	Description
before)	<p>attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 338 1300 415"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 800 1300 877"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
keytip (keytip)	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1325 1211 1346"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1598 1084 1619"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as</p>

Attributes	Description
	specified in section 2.3.11 .
screentip (screentip)	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the</p>

Attributes	Description
	<p>label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 877 1224 953"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>tag (tag)</p>	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1255 1122 1310"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1619 1019 1640"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean</p>

Attributes	Description
	datatype.

The following XML schema fragment defines the contents of this element:

```

<xsd:complexType name="CT_SplitButtonWithTitle">
  <xsd:complexContent>
    <xsd:extension base="CT_SplitButtonRestricted">
      <xsd:sequence minOccurs="0">
        <xsd:choice minOccurs="0">
          <xsd:element name="button" type="CT_VisibleButton"/>
          <xsd:element name="toggleButton" type="CT_VisibleToggleButton"/>
        </xsd:choice>
        <xsd:element name="menu" type="CT_MenuWithTitle"/>
      </xsd:sequence>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>

```

2.2.38 splitButton (Split Button)

This element specifies a split button control. A split button control is composed of either a button or a toggle button, and a drop-down menu. The icon and label shown on the split button come from the **button** or **toggleButton** child element.

For example, consider a split button control, as follows:



Figure 23: A split button control

This is specified using the following XML fragment:

```

<splitButton id="splitButton" size="large" >
  <button id="button" imageMso="HappyFace" label="Split Button" />
  <menu id="menu">
    <button id="button1" label="Button 1" />
    <button id="button2" label="Button 2" />
  </menu>
</splitButton>

```

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the child elements of this element.

Child Elements	Section
button (Button Inside of a Split Button)	2.2.4
menu (Unsize Menu)	2.2.26
toggleButton (Toggle Button Inside of a Split Button)	2.2.44

The following table summarizes the attributes of this element.


Attributes	Description
enabled (enabled state)	<p>Specifies the enabled state of the control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p>



Attributes	Description
callback)	<p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically. For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1162 338"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1138 701"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1058 1240 1085"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1478 1263 1505"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p>



Attributes	Description
callback)	<p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1263 394"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSize (getSize callback)	<p>Specifies the name of a callback function to be called to determine the size of this control.</p> <p>The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 730 1110 751"><button id="button" getSize="GetButtonSize" /></pre> <p>In this example, the GetButtonSize callback function is called when the application needs to determine the size of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1094 1214 1115"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1451 1175 1472"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p>

Attributes	Description
	<p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 310 1019 338"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
<p>idMso (built-in control identifier)</p>	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 657 829 684"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>idQ (qualified control identifier)</p>	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1024 1312 1367"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>image (custom image identifier)</p>	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1032 275"><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
<p>imageMso (built-in image identifier)</p>	<p>Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1008 695"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1083 1289 1157"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1549 1300 1623"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p>

Attributes	Description
	<p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 499 1300 575"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 968 1300 1043"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1486 1211 1514"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1084 275"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button". The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control.</p> <p>The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 961 1224 1014"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>showImage (show image)</p>	<p>Specifies whether this control displays an icon.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1535 997 1587"><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show</p>	<p>Specifies whether this control SHOULD display its label.</p>

Attributes	Description
label)	<p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1174 422"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
size (control size)	<p>Specifies the size of the control.</p> <p>The size and getSize attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 947 1060 972"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1644 1222 1692"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip"</pre>

Attributes	Description
	<p>supertip="This is the supertip string" /></p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>tag (tag)</p>	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 527 1122 579"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This example is a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 888 1019 909"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_SplitButton">
  <xsd:complexContent>
    <xsd:extension base="CT_SplitButtonRegular">
      <xsd:attributeGroup ref="AG_SizeAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.39 tab (Tab)

This element specifies a ribbon tab control.

For example, consider the following XML fragment:

```
<tab id="MyTab" label="My Custom Tab">
  ...
</tab>
```

This XML fragment specifies a custom tab with the **label** "My Custom Tab".

The following table summarizes the elements that are parents of this element.

Parent Elements
tabs (section 2.2.40); tabSet (section 2.2.41)

The following table summarizes the child elements of this element.


Child Elements	Section
group (Group)	2.2.23

The following table summarizes the attributes of this element.

Attributes	Description
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getLabel (getLabel callback)	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control)	Specifies the identifier for a custom control. All custom controls MUST have unique

Attributes	Description
identifier)	<p>identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1019 394"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 716 829 737"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1083 1312 1423"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertAfterMso (identifier of built-in control to insert)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ</p>

Attributes	Description
after)	<p>attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 338 1289 415"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterQ (qualified identifier of control to insert after)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 804 1300 882"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1266 1300 1344"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1317 296"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p data-bbox="493 325 1360 380">In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p data-bbox="493 386 1360 438">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
keytip (keytip)	<p data-bbox="493 464 1247 489">Specifies a string to be used as the suggested KeyTip for this control.</p> <p data-bbox="493 495 1382 550">The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p data-bbox="493 556 1122 581">For example, consider a button with KeyTip 'K', as follows:</p>  <p data-bbox="493 688 1036 714">This is specified using the following XML fragment:</p> <pre data-bbox="521 741 1211 766"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p data-bbox="493 793 1390 846">The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p data-bbox="493 873 1109 898">Specifies a string to be used as the label for this control.</p> <p data-bbox="493 905 1354 959">The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p data-bbox="493 966 1040 991">For example, consider the following XML fragment:</p> <pre data-bbox="521 1018 1084 1043"><button id="button" label="Custom Button" /></pre> <p data-bbox="493 1071 1187 1096">This specifies a custom button with a label of "Custom Button".</p> <p data-bbox="493 1102 1386 1155">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p data-bbox="493 1178 1393 1253">Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p data-bbox="493 1260 1349 1314">If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p data-bbox="493 1320 1040 1346">For example, consider the following XML fragment:</p> <pre data-bbox="521 1373 1122 1428"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p data-bbox="493 1455 1317 1509">This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p data-bbox="493 1516 1386 1568">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p data-bbox="493 1591 943 1617">Specifies the visibility state of the control.</p> <p data-bbox="493 1623 1360 1677">The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p data-bbox="493 1684 1040 1709">For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1019 239" style="font-family: monospace;"><tab idMso="TabHome" visible="false" /></pre> <p data-bbox="493 275 1333 359">In this example, the built-in tab with an identifier of "TabHome" is hidden. The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```

<xsd:complexType name="CT_Tab">
  <xsd:sequence>
    <xsd:choice minOccurs="0" maxOccurs="100">
      <xsd:element name="group" type="CT_Group"/>
    </xsd:choice>
  </xsd:sequence>
  <xsd:attributeGroup ref="AG_IDAttributes"/>
  <xsd:attributeGroup ref="AG_Label"/>
  <xsd:attributeGroup ref="AG_PositionAttributes"/>
  <xsd:attributeGroup ref="AG_Visible"/>
  <xsd:attributeGroup ref="AG_Keytip"/>
</xsd:complexType>

```

2.2.40 tabs (List of Tabs)

This element specifies a list of ribbon tab controls. This element SHOULD NOT be specified if the containing Custom UI XML document is a Quick Access Toolbar Customizations part.

The following table summarizes the elements that are parents of this element.

Parent Elements
ribbon (section 2.2.33)

The following table summarizes the child elements of this element.

Child Elements	Section
tab (Tab)	2.2.39

The following XML schema fragment defines the contents of this element:

```

<xsd:complexType name="CT_Tabs">
  <xsd:sequence>
    <xsd:element name="tab" type="CT_Tab" minOccurs="1" maxOccurs="100"/>
  </xsd:sequence>
</xsd:complexType>

```

2.2.41 tabSet (Contextual Tab Set)

This element specifies a contextual tab set control. As the **id** and **idQ** attributes are not present, this element can only be used to refer to existing built-in tab sets. This element cannot be used to create new contextual tab sets.

For example, consider the following XML fragment:

```
<tabSet idMso="TabSetPictureTools">
  <tab id="tab" label="Custom Tab">
    ...
  </tab>
</tabSet>
```

This XML fragment is used to add a new custom tab to the tab set with an identifier of "TabSetPictureTools".

The following table summarizes the elements that are parents of this element.

Parent Elements
contextualTabs (section 2.2.10)

The following table summarizes the child elements of this element.

Child Elements	Subclause
tab (Tab)	section 2.2.39

The following table summarizes the attributes of this element.

Attributes	Description
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>For example, consider the following XML fragment:</p> <pre><control idMso="Bold" /></pre> <p>This is used to create a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden. The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_TabSet">
  <xsd:sequence>
    <xsd:element name="tab" type="CT_Tab" minOccurs="0" maxOccurs="50"/>
  </xsd:sequence>
  <xsd:attribute name="idMso" type="ST_ID" use="required"/>
  <xsd:attributeGroup ref="AG_Visible"/>
</xsd:complexType>
```


2.2.42 toggleButton (Unsize Toggle Button)

This element specifies a toggle button control that, because of its location, cannot have its size changed. The **size** attribute is not present. It otherwise behaves identically to the regular **toggleButton** element, as specified in section [2.2.43](#).

The following table summarizes the elements that are parents of this element.

Parent Elements
buttonGroup (section 2.2.5); menu (section 2.2.28); menu (section 2.2.26); menu (section 2.2.29); menu (section 2.2.27); officeMenu (section 2.2.31)

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which SHOULD be displayed in detailed views.</p> <p>The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled)	Specifies the enabled state of the control.


Attributes	Description
state)	<p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1317 394"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control.</p> <p>The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 730 1289 751"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1094 1175 1115"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getImage (getImage callback)	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1451 1138 1472"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getKeytip (getKeytip callback)	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is</p>


Attributes	Description
	<p>specified, the application SHOULD generate a KeyTip for the control automatically. For example, consider the following XML fragment:</p> <pre data-bbox="521 289 1162 310"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 646 1138 667"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getPressed (getPressed callback)</p>	<p>Specifies the name of a callback function to be called to determine the toggled state of this control.</p> <p>If this attribute is omitted, the control SHOULD default to the off state.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 982 1252 1003"><toggleButton id="toggle" getPressed="IsButtonToggled" /></pre> <p>In this example, the IsButtonToggled callback function is called when the application needs to determine the toggle state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getScreentip (getScreentip callback)</p>	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1367 1235 1388"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowImage (getShowImage callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the icon of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p>



Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1263 279"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getShowLabel (getShowLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 674 1263 699"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getSupertip (getSupertip callback)</p>	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1035 1211 1060"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getVisible (getVisible callback)</p>	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1394 1174 1419"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>id (control identifier)</p>	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p>

Attributes	Description
	<p>For example, consider the following XML fragment:</p> <pre data-bbox="521 254 1019 275"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton". The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control. The contents of this attribute are application-defined. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 596 829 617"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold". The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control. The idQ attribute can be used to reference controls or containers created by other Custom UI documents. The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified. For example, consider the following XML fragment:</p> <pre data-bbox="521 968 1312 1304"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab. The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p>Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file. The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed. For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1036 241"><button id="button" image="ForestPic" /></pre> <p data-bbox="493 275 1349 323">This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="493 331 1349 380">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p data-bbox="493 411 1393 459">Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p data-bbox="493 468 1393 516">The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="493 525 1393 573">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 581 1040 609">For example, consider the following XML fragment:</p> <pre data-bbox="521 638 1008 661"><button id="button" imageMso="Bold" /></pre> <p data-bbox="493 690 1300 739">This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p data-bbox="493 747 1344 795">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p data-bbox="493 831 1349 879">Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="493 888 1393 989">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="493 997 1040 1024">For example, consider the following XML fragment:</p> <pre data-bbox="521 1054 1289 1125"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p data-bbox="493 1155 1360 1203">In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p data-bbox="493 1211 1344 1260">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterQ (qualified identifier of control to insert after)	<p data-bbox="493 1293 1365 1341">Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="493 1350 1393 1451">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="493 1459 1040 1486">For example, consider the following XML fragment:</p> <pre data-bbox="521 1516 1300 1587"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p data-bbox="493 1617 1360 1665">In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p data-bbox="493 1673 1360 1701">The possible values for this attribute are defined by the ST_QID simple type, as</p>

Attributes	Description
	specified in section 2.3.9 .
insertBeforeMso (identifier of built-in control to insert before)	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertBeforeQ (qualified identifier of control to insert before)	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
keytip (keytip)	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
label (label)	<p>Specifies a string that SHOULD be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1084 241"><button id="button" label="Custom Button" /></pre> <p data-bbox="493 275 1386 359">This specifies a custom button with a label of "Custom Button". The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
onAction (onAction callback)	<p data-bbox="493 384 1370 436">Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p data-bbox="493 443 1040 470">For example, consider the following XML fragment:</p> <pre data-bbox="521 495 1317 518"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p data-bbox="493 548 1357 600">In this example, the button calls the ButtonClicked callback function when it is invoked.</p> <p data-bbox="493 606 1386 659">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
screentip (screentip)	<p data-bbox="493 684 1390 793">Specifies a string to be shown as the screentip for this control. The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="493 800 1133 827">For example, consider a button with a screentip, as follows:</p>  <p data-bbox="493 1178 1036 1205">This is specified using the following XML fragment:</p> <pre data-bbox="521 1230 1224 1283"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="493 1312 1386 1365">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
showImage (show image)	<p data-bbox="493 1390 997 1417">Specifies whether this control displays an icon.</p> <p data-bbox="493 1423 1386 1476">This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p data-bbox="493 1482 1390 1535">The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p data-bbox="493 1541 1273 1568">For example, consider a button that does not display an icon, as follows:</p>

Attributes	Description
	 <p>This is specified using the following XML fragment:</p> <pre><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
showLabel (show label)	<p>Specifies whether this control SHOULD display its label.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as</p>

Attributes	Description
	specified in section 2.3.11 .
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 449 1122 499"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 810 1019 835"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ToggleButtonRegular">
  <xsd:complexContent>
    <xsd:extension base="CT_ButtonRegular">
      <xsd:attribute name="getPressed" type="ST_Delegate" use="optional"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```

2.2.43 toggleButton (Toggle Button)

This element specifies a toggle button control that can be toggled between the pressed and unpressed states by the end-user.

For example, consider a toggle button control, as follows:



Figure 24: A toggle button control


This is specified with the following XML fragment:

```
<toggleButton id="toggleButton" label="Toggle Button" />
```

The following table summarizes the elements that are parents of this element.

Parent Elements
box (section 2.2.1); group (section 2.2.23)

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which is displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control. The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider the following XML fragment:</p> <pre><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button.</p>


Attributes	Description
	<p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getEnabled (getEnabled callback)</p>	<p>Specifies the name of a callback function to be called to determine the enabled state of this control.</p> <p>The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 449 1175 474"><button id="button" getEnabled="IsButtonEnabled" /></pre> <p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 810 1138 835"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1171 1162 1197"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1533 1138 1558"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>



Attributes	Description
getPressed (getPressed callback)	<p>Specifies the name of a callback function to be called to determine the toggled state of this control.</p> <p>If this attribute is omitted, the control SHOULD default to the "off" state.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 352 1252 380"><toggleButton id="toggle" getPressed="IsButtonToggled" /></pre> <p>In this example, the IsButtonToggled callback function is called when the application needs to determine the toggle state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 741 1239 768"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application displays the icon of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1161 1263 1188"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p>Specifies the name of a callback function to be called to determine whether the application displays the label of this control.</p> <p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1581 1263 1608"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type,</p>



Attributes	Description
	as specified in section 2.3.2 .
getSize (getSize callback)	<p>Specifies the name of a callback function to be called to determine the size of this control.</p> <p>The getSize and size attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 422 1110 447"><button id="button" getSize="GetButtonSize" /></pre> <p>In this example, the GetButtonSize callback function is called when the application needs to determine the size of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 783 1211 808"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1142 1175 1167"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1528 1021 1554"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an id of ""MyButton"".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in)	Specifies the identifier of a built-in control.

Attributes	Description
control identifier)	<p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 346 829 369"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 716 1312 1056"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group> </tab> </tabs> </ribbon> </customUI></pre> <p>In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p>Specifies the relationship identifier for an image to be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1472 1032 1495"><button id="button" image="ForestPic" /></pre> <p>This specifies a custom button whose icon is the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p>The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p>Specifies the identifier of a built-in image to be used as the icon of this control.</p> <p>The contents of this attribute are application-defined and SHOULD be ignored if not</p>

Attributes	Description
	<p>understood.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 344 1008 369"><button id="button" imageMso="Bold" /></pre> <p>This specifies a custom button that uses the built-in image with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterMso (identifier of built-in control to insert after)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 758 1289 835"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1226 1300 1304"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1688 1300 1713"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"></pre>

Attributes	Description
	<p>...</p> <p></tab></p> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control is to be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an id of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control.</p> <p>The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button".</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>onAction (onAction callback)</p>	<p>Specifies the name of a callback function to be called when this control is invoked by the user.</p> <p>For example, consider the following XML fragment:</p>

Attributes	Description
	<pre data-bbox="521 218 1317 243"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p data-bbox="493 275 1365 323">This specifies a button that calls the ButtonClicked callback function when it is invoked.</p> <p data-bbox="493 333 1386 382">The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p data-bbox="237 411 358 464">screentip (screentip)</p>	<p data-bbox="493 411 1175 436">Specifies a string to be shown as the screentip for this control.</p> <p data-bbox="493 447 1390 520">The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p data-bbox="493 531 1135 556">For example, consider a button with a screentip, as follows:</p>  <p data-bbox="493 905 1037 930">This is specified using the following XML fragment:</p> <pre data-bbox="521 957 1224 1010"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="This is the screentip" /></pre> <p data-bbox="493 1037 1386 1085">The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p data-bbox="237 1115 451 1167">showImage (show image)</p>	<p data-bbox="493 1115 997 1140">Specifies whether this control displays an icon.</p> <p data-bbox="493 1150 1382 1199">This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p data-bbox="493 1209 1390 1262">The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p data-bbox="493 1272 1276 1297">For example, consider a button that does not display an icon, as follows:</p>  <p data-bbox="493 1476 1037 1501">This is specified using the following XML fragment:</p> <pre data-bbox="521 1528 992 1581"><button id="button" showImage="false" label="Button with no icon" /></pre> <p data-bbox="493 1608 1333 1661">The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p data-bbox="237 1688 440 1713">showLabel (show</p>	<p data-bbox="493 1688 1000 1713">Specifies whether this control displays its label.</p>

Attributes	Description
label)	<p>This attribute SHOULD have no effect if the size or getSize attributes specify that the control is "large".</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 373 1174 422"><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
size (control size)	<p>Specifies the size of the control.</p> <p>The size and getSize attributes are mutually exclusive. If neither attribute is specified, the control's size SHOULD default to the normal size.</p> <p>For example, consider a large button, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 947 1060 972"><toggleButton idMso="Bold" size="large" /></pre> <p>The possible values for this attribute are defined by the ST_Size simple type, as specified in section 2.3.10.</p>
supertip (supertip)	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1644 1222 1692"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip"</pre>

Attributes	Description
	<p>supertip="This is the supertip string" /></p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>tag (tag)</p>	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 527 1122 579"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>visible (control visibility)</p>	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 888 1019 909"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_ToggleButton">
  <xsd:complexContent>
    <xsd:extension base="CT_ToggleButtonRegular">
      <xsd:attributeGroup ref="AG_SizeAttributes"/>
    </xsd:extension>
  </xsd:complexContent>
</xsd:complexType>
```


2.2.44 toggleButton (Toggle Button Inside of a Split Button)

This element specifies a toggle button control that is part of a split button control. The **visible** and **getVisible** attributes are not present because the visibility is controlled by the split button. This element otherwise behaves in the same way as the regular **toggleButton** element, as specified in section [2.2.43](#).

The following table summarizes the elements that are parents of this element.

Parent Elements
<p>splitButton (section 2.2.38); splitButton (section 2.2.36); splitButton (section 2.2.37)</p>

The following table summarizes the attributes of this element.

Attributes	Description
description (description)	<p>Specifies a detailed description of the control, which is displayed in detailed views. The description and getDescription attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider a button with a detailed description, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 552 1276 627"><button id="button" label="Button" imageMso="HappyFace" description="This is a verbose description that describes the function of this control in detail." /></pre> <p>The possible values for this attribute are defined by the ST_LongString simple type, as specified in section 2.3.8.</p>
enabled (enabled state)	<p>Specifies the enabled state of the control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. This attribute cannot be used to enable a built-in control that would otherwise be disabled by the application. For example, consider the following XML fragment:</p> <pre data-bbox="521 940 1317 961"><button id="button" label="Disabled Button" enabled="false" /></pre> <p>This specifies a new button that is disabled. A permanently disabled button is not very useful, thus the enabled attribute is not commonly used. The possible values for this attribute are defined by the XML schema boolean datatype.</p>
getDescription (getDescription callback)	<p>Specifies the name of a callback function to be called to determine the detailed description of this control. The getDescription and description attributes are mutually exclusive. If neither attribute is specified, the control SHOULD NOT display any detailed text. For example, consider the following XML fragment:</p> <pre data-bbox="521 1299 1289 1320"><button id="button" getDescription="GetButtonDescription" /></pre> <p>In this example, the GetButtonDescription callback function is called when the application needs to determine the detailed description of the button. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getEnabled (getEnabled callback)	<p>Specifies the name of a callback function to be called to determine the enabled state of this control. The getEnabled and enabled attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being enabled. For example, consider the following XML fragment:</p> <pre data-bbox="521 1661 1175 1682"><button id="button" getEnabled="IsButtonEnabled" /></pre>



Attributes	Description
	<p>In this example, the IsButtonEnabled callback function is called when the application needs to determine the enabled state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getImage (getImage callback)</p>	<p>Specifies the name of a callback function to be called to determine the icon of this control.</p> <p>The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 512 1133 537"><button id="button" getImage="GetButtonImage" /></pre> <p>In this example, the GetButtonImage callback function is called when the application needs to determine the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getKeytip (getKeytip callback)</p>	<p>Specifies the name of a callback function to be called to determine the suggested KeyTip of this control.</p> <p>The getKeytip and keytip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD generate a KeyTip for the control automatically.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 873 1159 898"><button id="button" getKeytip="GetButtonKeytip" /></pre> <p>In this example, the GetButtonKeytip callback function is called when the application needs to determine the KeyTip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getLabel (getLabel callback)</p>	<p>Specifies the name of a callback function to be called to determine the label of this control.</p> <p>The getLabel and label attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1234 1133 1260"><button id="button" getLabel="GetButtonLabel" /></pre> <p>In this example, the GetButtonLabel callback function is called when the application needs to determine the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>getPressed (getPressed callback)</p>	<p>Specifies the name of a callback function to be called to determine the toggled state of this control.</p> <p>If this attribute is omitted, the control SHOULD default to the off state.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1570 1247 1596"><toggleButton id="toggle" getPressed="IsButtonToggled" /></pre> <p>In this example, the IsButtonToggled callback function is called when the application needs to determine the toggle state of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type,</p>



Attributes	Description
	as specified in section 2.3.2 .
getScreentip (getScreentip callback)	<p>Specifies the name of a callback function to be called to determine the screentip of this control.</p> <p>The getScreentip and screentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 449 1239 474"><button id="button" getScreentip="GetButtonScreentip" /></pre> <p>In this example, the GetButtonScreentip callback function is called when the application needs to determine the screentip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowImage (getShowImage callback)	<p>Specifies the name of a callback function to be called to determine whether the application displays the icon of this control.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 810 1263 835"><button id="button" getShowImage="IsButtonImageVisible" /></pre> <p>In this example, the IsButtonImageVisible callback function is called when the application needs to determine whether to display the icon of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getShowLabel (getShowLabel callback)	<p>Specifies the name of a callback function to be called to determine whether the application SHOULD display the label of this control.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1167 1263 1192"><button id="button" getShowLabel="IsButtonLabelVisible" /></pre> <p>In this example, the IsButtonLabelVisible callback function is called when the application needs to determine whether to display the label of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
getSupertip (getSupertip callback)	<p>Specifies the name of a callback function to be called to determine the supertip of this control.</p> <p>The getSupertip and supertip attributes are mutually exclusive. If neither attribute is specified, no supertip for this control SHOULD be shown.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1528 1211 1554"><button id="button" getSupertip="GetButtonSupertip" /></pre> <p>In this example, the GetButtonSupertip callback function is called when the application needs to determine the supertip of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>

Attributes	Description
getVisible (getVisible callback)	<p>Specifies the name of a callback function to be called to determine the visibility state of this control.</p> <p>The getVisible and visible attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 380 1175 405"><button id="button" getVisible="IsButtonVisible" /></pre> <p>In this example, the IsButtonVisible callback function is called when the application needs to determine the visibility of the button.</p> <p>The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
id (control identifier)	<p>Specifies the identifier for a custom control. All custom controls MUST have unique identifiers. The identifier of a control SHOULD be passed to callback functions to identify which control corresponds to the function call.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 764 1019 789"><button id="MyButton" label="Button" /></pre> <p>This specifies a custom button control with an identifier of "MyButton".</p> <p>The possible values for this attribute are defined by the ST_UniqueID simple type, as specified in section 2.3.13.</p>
idMso (built-in control identifier)	<p>Specifies the identifier of a built-in control.</p> <p>The contents of this attribute are application-defined.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1108 829 1134"><control idMso="Bold" /></pre> <p>This creates a clone of the control with an identifier of "Bold".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
idQ (qualified control identifier)	<p>Specifies a qualified identifier for a control.</p> <p>The idQ attribute can be used to reference controls or containers created by other Custom UI documents.</p> <p>The id, idQ, and idMso attributes are mutually exclusive. At least one of these attributes MUST be specified.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1478 1313 1711"><customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui" xmlns:ex="http://www.example.com"> <ribbon> <tabs> <tab idQ="ex:OtherTab" label="Shared Tab"> <group id="MyGroup" label="My Group"> ... </group></pre>

Attributes	Description
	<pre data-bbox="521 201 678 302"></tab> </tabs> </ribbon> </customUI></pre> <p data-bbox="493 338 1357 436">In this case, ex is an XML namespace prefix for the namespace http://www.example.com. This XML fragment refers to a tab in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the tab.</p> <p data-bbox="493 447 1357 495">The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
image (custom image identifier)	<p data-bbox="493 520 1390 598">Specifies the relationship identifier for an image which SHOULD be used as the icon for this control. This attribute is used to specify an embedded picture that resides locally within the containing file.</p> <p data-bbox="493 606 1377 657">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 665 1040 693">For example, consider the following XML fragment:</p> <pre data-bbox="521 720 1032 741"><button id="button" image="ForestPic" /></pre> <p data-bbox="493 772 1349 823">This specifies a custom button whose icon SHOULD be the embedded image file referenced by the relationship identifier of "ForestPic".</p> <p data-bbox="493 831 1349 882">The possible values for this attribute are defined by the ST_Uri simple type, as specified in section 2.3.14.</p>
imageMso (built-in image identifier)	<p data-bbox="493 909 1390 959">Specifies the identifier of a built-in image which SHOULD be used as the icon of this control.</p> <p data-bbox="493 968 1390 1018">The contents of this attribute are application-defined and SHOULD be ignored if not understood.</p> <p data-bbox="493 1026 1377 1077">The getImage, image, and imageMso attributes are mutually exclusive. If none of these attributes are specified, no icon SHOULD be displayed.</p> <p data-bbox="493 1085 1040 1113">For example, consider the following XML fragment:</p> <pre data-bbox="521 1140 1008 1161"><button id="button" imageMso="Bold" /></pre> <p data-bbox="493 1192 1295 1243">This specifies a custom button that SHOULD use the built-in image with an identifier of "Bold".</p> <p data-bbox="493 1251 1341 1302">The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
insertAfterMso (identifier of built-in control to insert after)	<p data-bbox="493 1329 1349 1379">Specifies the identifier of a built-in control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p data-bbox="493 1388 1382 1486">The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p data-bbox="493 1495 1040 1522">For example, consider the following XML fragment:</p> <pre data-bbox="521 1549 1287 1625"><tab id="MyTab" insertAfterMso="TabHome" label="Custom Tab"> ... </tab></pre> <p data-bbox="493 1656 1357 1707">In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the built-in tab with an identifier of "TabHome".</p>

Attributes	Description
	<p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertAfterQ (qualified identifier of control to insert after)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted after. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 499 1300 575"><tab id="MyTab" insertAfterQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted after the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>insertBeforeMso (identifier of built-in control to insert before)</p>	<p>Specifies the identifier of a built-in control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 968 1300 1043"><tab id="MyTab" insertBeforeMso="TabHome" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the built-in tab with an identifier of "TabHome".</p> <p>The possible values for this attribute are defined by the ST_ID simple type, as specified in section 2.3.5.</p>
<p>insertBeforeQ (qualified identifier of control to insert before)</p>	<p>Specifies the qualified identifier of a control that this control SHOULD be inserted before. If the value of this attribute is not understood, it SHOULD be ignored.</p> <p>The insertAfterMso, insertAfterQ, insertBeforeMso, and insertBeforeQ attributes are mutually exclusive. If none of these attributes are specified, the controls SHOULD be appended to the existing set of controls, in the order they are defined in the XML.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 1434 1300 1509"><tab id="MyTab" insertBeforeQ="x:OtherTab" label="Custom Tab"> ... </tab></pre> <p>In this example, a new custom tab with an identifier of "MyTab" is to be inserted before the custom tab with a qualified identifier of "x:OtherTab".</p> <p>The possible values for this attribute are defined by the ST_QID simple type, as specified in section 2.3.9.</p>
<p>keytip (keytip)</p>	<p>Specifies a string to be used as the suggested KeyTip for this control.</p> <p>The keytip and getKeytip attributes are mutually exclusive. If neither attribute is</p>

Attributes	Description
	<p>specified, the application SHOULD generate a KeyTip for the control automatically. For example, consider a button with KeyTip 'K', as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 422 1211 447"><button id="button" imageMso="HappyFace" keytip="K" /></pre> <p>The possible values for this attribute are defined by the ST_Keytip simple type, as specified in section 2.3.7.</p>
<p>label (label)</p>	<p>Specifies a string to be used as the label for this control. The label and getLabel attributes are mutually exclusive. If neither attribute is specified, no label SHOULD be displayed. For example, consider the following XML fragment:</p> <pre data-bbox="521 695 1084 720"><button id="button" label="Custom Button" /></pre> <p>This specifies a custom button with a label of "Custom Button". The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>onAction (onAction callback)</p>	<p>Specifies the name of a callback function to be called when this control is invoked by the user. For example, consider the following XML fragment:</p> <pre data-bbox="521 968 1317 993"><button id="button" label="Button" onAction="ButtonClicked" /></pre> <p>In this example, the button calls the ButtonClicked callback function when it is invoked. The possible values for this attribute are defined by the ST_Delegate simple type, as specified in section 2.3.2.</p>
<p>screentip (screentip)</p>	<p>Specifies a string to be shown as the screentip for this control. The screentip and getScreentip attributes are mutually exclusive. If neither attribute is specified, the application SHOULD display the label of the control as the screentip or display no screentip at all. For example, consider a button with a screentip, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre data-bbox="521 1703 1224 1728"><button id="button" imageMso="HappyFace" label="Button"</pre>

Attributes	Description
	<pre>size="large" screentip="This is the screentip" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
<p>showImage (show image)</p>	<p>Specifies whether this control displays an icon.</p> <p>The showImage and getShowImage attributes are mutually exclusive. If neither attribute is specified, the control SHOULD display its icon.</p> <p>For example, consider a button that does not display an icon, as follows:</p>  <p>This is specified using the following XML fragment:</p> <pre><button id="button" showImage="false" label="Button with no icon" /></pre> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>showLabel (show label)</p>	<p>Specifies whether this control SHOULD display its label.</p> <p>The showLabel and getShowLabel attributes are mutually exclusive. If neither attribute is specified, the control SHOULD default to showing its label.</p> <p>For example, consider the following XML fragment:</p> <pre><button id="button" label="Label" showLabel="false" imageMso="HappyFace" /></pre> <p>This specifies a button that has a label, but does not show it. Even though the label is hidden, it is provided to accessibility tools.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>
<p>supertip (supertip)</p>	<p>Specifies a string to be shown as the supertip of the control.</p> <p>The supertip and getSupertip attributes are mutually exclusive. If neither attribute is specified no supertip for this control SHOULD be shown.</p> <p>For example, consider a control with a supertip, as follows:</p> 

Attributes	Description
	<p>This is specified using the following XML fragment:</p> <pre data-bbox="521 254 1224 331"><button id="button" imageMso="HappyFace" label="Button" size="large" screentip="Screentip" supertip="This is the supertip string" /></pre> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
tag (tag)	<p>Specifies an arbitrary string that can be used to hold data or identify the control. The contents of this attribute SHOULD be passed to any callback functions specified on this control.</p> <p>If this attribute is omitted, the control's tag value SHOULD default to an empty string.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 632 1122 684"><button id="button" label="Button" tag="123456" onAction="ButtonClicked" /></pre> <p>This specifies a button with a tag value of "123456", which is passed to the ButtonClicked callback function.</p> <p>The possible values for this attribute are defined by the ST_String simple type, as specified in section 2.3.11.</p>
visible (control visibility)	<p>Specifies the visibility state of the control.</p> <p>The getVisible and visible attributes are mutually exclusive. If these attributes are omitted, the control SHOULD default to being visible.</p> <p>For example, consider the following XML fragment:</p> <pre data-bbox="521 995 1019 1020"><tab idMso="TabHome" visible="false" /></pre> <p>In this example, the built-in tab with an identifier of "TabHome" is hidden.</p> <p>The possible values for this attribute are defined by the XML schema boolean datatype.</p>

The following XML schema fragment defines the contents of this element:

```
<xsd:complexType name="CT_VisibleToggleButton">
  <xsd:complexContent>
    <xsd:restriction base="CT_ToggleButtonRegular">
      <xsd:attribute name="visible" use="prohibited"/>
      <xsd:attribute name="getVisible" use="prohibited"/>
    </xsd:restriction>
  </xsd:complexContent>
</xsd:complexType>
```

2.3 Simple Types

This is the complete list of simple types in the <http://schemas.microsoft.com/office/2006/01/customui> namespace.

2.3.1 ST_BoxStyle (Box Style)

Specifies the layout style of a **box** control.

This simple type's contents are a restriction of the XML schema **string** datatype.

The following are possible **enumeration** values for this type:

Enumeration Value	Description
horizontal (Horizontal)	Specifies that the child controls are laid out horizontally.
vertical (Vertical)	Specifies that the child controls are laid out vertically.

Referenced By
box@boxStyle (section 2.2.1)

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_BoxStyle">  
  <xsd:restriction base="xsd:string">  
    <xsd:enumeration value="horizontal"/>  
    <xsd:enumeration value="vertical"/>  
  </xsd:restriction>  
</xsd:simpleType>
```

2.3.2 ST_Delegate (Callback Function Name)

Specifies the name of a callback function. The format of this string is application-defined and SHOULD be ignored if not understood.

Examples of this simple type are macro scripts and add-in callback functions.

This simple type's contents are a restriction of the XML schema string datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 characters.
- This simple type's contents have a maximum length of 1024 characters.

Referenced By
box@getVisible (section 2.2.1); button@getDescription (section 2.2.2); button@getDescription (section 2.2.3); button@getDescription (section 2.2.4); button@getEnabled (section 2.2.2); button@getEnabled (section 2.2.3); button@getEnabled (section 2.2.4); button@getImage (section 2.2.2); button@getImage (section 2.2.3); button@getImage (section 2.2.4); button@getKeytip (section 2.2.2); button@getKeytip (section 2.2.3); button@getKeytip (section 2.2.4); button@getLabel (section 2.2.2); button@getLabel (section 2.2.3); button@getLabel (section 2.2.4); button@getScreentip (section 2.2.2); button@getScreentip (section 2.2.3); button@getScreentip (section 2.2.4); button@getShowImage (section 2.2.2); button@getShowImage (section 2.2.3); button@getShowImage (section 2.2.4); button@getShowLabel (section 2.2.2); button@getShowLabel (section 2.2.3); button@getShowLabel (section 2.2.4); button@getSize (section 2.2.2); button@getSupertip (section 2.2.2); button@getSupertip (section 2.2.3); button@getSupertip (section 2.2.4); button@getVisible (section 2.2.2); button@getVisible (section 2.2.3); button@getVisible (section 2.2.4); button@onAction (section 2.2.2); button@onAction (section 2.2.3); button@onAction (section 2.2.4); buttonGroup@getVisible (section 2.2.5); checkBox@getDescription (section 2.2.6); checkBox@getEnabled (section 2.2.6); checkBox@getImage

Referenced By

(section [2.2.6](#)); checkBox@getKeytip (section [2.2.6](#)); checkBox@getLabel (section [2.2.6](#)); checkBox@getPressed (section [2.2.6](#)); checkBox@getScreentip (section [2.2.6](#)); checkBox@getShowImage (section [2.2.6](#)); checkBox@getShowLabel (section [2.2.6](#)); checkBox@getSupertip (section [2.2.6](#)); checkBox@getVisible (section [2.2.6](#)); checkBox@onAction (section [2.2.6](#)); comboBox@getEnabled (section [2.2.7](#)); comboBox@getImage (section [2.2.7](#)); comboBox@getItemCount (section [2.2.7](#)); comboBox@getItemID (section [2.2.7](#)); comboBox@getItemImage (section [2.2.7](#)); comboBox@getItemLabel (section [2.2.7](#)); comboBox@getItemScreentip (section [2.2.7](#)); comboBox@getItemSupertip (section [2.2.7](#)); comboBox@getKeytip (section [2.2.7](#)); comboBox@getLabel (section [2.2.7](#)); comboBox@getScreentip (section [2.2.7](#)); comboBox@getShowImage (section [2.2.7](#)); comboBox@getShowLabel (section [2.2.7](#)); comboBox@getSupertip (section [2.2.7](#)); comboBox@getText (section [2.2.7](#)); comboBox@getVisible (section [2.2.7](#)); comboBox@onChange (section [2.2.7](#)); command@getEnabled (section [2.2.8](#)); command@onAction (section [2.2.8](#)); control@getDescription (section [2.2.12](#)); control@getDescription (section [2.2.13](#)); control@getEnabled (section [2.2.12](#)); control@getEnabled (section [2.2.13](#)); control@getEnabled (section [2.2.11](#)); control@getImage (section [2.2.12](#)); control@getImage (section [2.2.13](#)); control@getImage (section [2.2.11](#)); control@getKeytip (section [2.2.12](#)); control@getKeytip (section [2.2.13](#)); control@getKeytip (section [2.2.11](#)); control@getLabel (section [2.2.12](#)); control@getLabel (section [2.2.13](#)); control@getLabel (section [2.2.11](#)); control@getScreentip (section [2.2.12](#)); control@getScreentip (section [2.2.13](#)); control@getScreentip (section [2.2.11](#)); control@getShowImage (section [2.2.12](#)); control@getShowImage (section [2.2.13](#)); control@getShowImage (section [2.2.11](#)); control@getShowLabel (section [2.2.12](#)); control@getShowLabel (section [2.2.13](#)); control@getShowLabel (section [2.2.11](#)); control@getSize (section [2.2.12](#)); control@getSize (section [2.2.13](#)); control@getSupertip (section [2.2.12](#)); control@getSupertip (section [2.2.13](#)); control@getSupertip (section [2.2.11](#)); control@getVisible (section [2.2.12](#)); control@getVisible (section [2.2.13](#)); control@getVisible (section [2.2.11](#)); control@onAction (section [2.2.12](#)); customUI@loadImage (section [2.2.14](#)); customUI@onLoad (section [2.2.14](#)); dropDown@getEnabled (section [2.2.17](#)); dropDown@getImage (section [2.2.17](#)); dropDown@getItemCount (section [2.2.17](#)); dropDown@getItemID (section [2.2.17](#)); dropDown@getItemImage (section [2.2.17](#)); dropDown@getItemLabel (section [2.2.17](#)); dropDown@getItemScreentip (section [2.2.17](#)); dropDown@getItemSupertip (section [2.2.17](#)); dropDown@getKeytip (section [2.2.17](#)); dropDown@getLabel (section [2.2.17](#)); dropDown@getScreentip (section [2.2.17](#)); dropDown@getSelectedItemID (section [2.2.17](#)); dropDown@getSelectedItemIndex (section [2.2.17](#)); dropDown@getShowImage (section [2.2.17](#)); dropDown@getShowLabel (section [2.2.17](#)); dropDown@getSupertip (section [2.2.17](#)); dropDown@getVisible (section [2.2.17](#)); dropDown@onAction (section [2.2.17](#)); dynamicMenu@getContent (section [2.2.19](#)); dynamicMenu@getContent (section [2.2.18](#)); dynamicMenu@getDescription (section [2.2.19](#)); dynamicMenu@getDescription (section [2.2.18](#)); dynamicMenu@getEnabled (section [2.2.19](#)); dynamicMenu@getEnabled (section [2.2.18](#)); dynamicMenu@getImage (section [2.2.19](#)); dynamicMenu@getImage (section [2.2.18](#)); dynamicMenu@getKeytip (section [2.2.19](#)); dynamicMenu@getKeytip (section [2.2.18](#)); dynamicMenu@getLabel (section [2.2.19](#)); dynamicMenu@getLabel (section [2.2.18](#)); dynamicMenu@getScreentip (section [2.2.19](#)); dynamicMenu@getScreentip (section [2.2.18](#)); dynamicMenu@getShowImage (section [2.2.19](#)); dynamicMenu@getShowImage (section [2.2.18](#)); dynamicMenu@getShowLabel (section [2.2.19](#)); dynamicMenu@getShowLabel (section [2.2.18](#)); dynamicMenu@getSize (section [2.2.19](#)); dynamicMenu@getSupertip (section [2.2.19](#)); dynamicMenu@getSupertip (section [2.2.18](#)); dynamicMenu@getVisible (section [2.2.19](#)); dynamicMenu@getVisible (section [2.2.18](#)); editBox@getEnabled (section [2.2.20](#)); editBox@getImage (section [2.2.20](#)); editBox@getKeytip (section [2.2.20](#)); editBox@getLabel (section [2.2.20](#)); editBox@getScreentip (section [2.2.20](#)); editBox@getShowImage (section [2.2.20](#)); editBox@getShowLabel (section [2.2.20](#)); editBox@getSupertip (section [2.2.20](#)); editBox@getText (section [2.2.20](#)); editBox@getVisible (section [2.2.20](#)); editBox@onChange (section [2.2.20](#)); gallery@getDescription (section [2.2.21](#)); gallery@getDescription (section [2.2.22](#)); gallery@getEnabled (section [2.2.21](#)); gallery@getEnabled (section [2.2.22](#)); gallery@getImage (section [2.2.21](#)); gallery@getImage (section [2.2.22](#)); gallery@getItemCount (section [2.2.21](#)); gallery@getItemCount (section [2.2.22](#)); gallery@getItemHeight (section [2.2.21](#)); gallery@getItemHeight (section [2.2.22](#)); gallery@getItemID (section [2.2.21](#)); gallery@getItemID (section [2.2.22](#)); gallery@getItemImage (section [2.2.21](#)); gallery@getItemImage (section [2.2.22](#)); gallery@getItemLabel (section [2.2.21](#)); gallery@getItemLabel (section [2.2.22](#)); gallery@getItemScreentip (section [2.2.21](#)); gallery@getItemScreentip (section [2.2.22](#)); gallery@getItemSupertip (section [2.2.21](#)); gallery@getItemSupertip (section [2.2.22](#)); gallery@getItemWidth (section [2.2.21](#)); gallery@getItemWidth (section [2.2.22](#)); gallery@getKeytip (section [2.2.21](#)); gallery@getKeytip (section [2.2.22](#)); gallery@getLabel (section [2.2.21](#)); gallery@getLabel (section [2.2.22](#)); gallery@getScreentip (section [2.2.21](#));

Referenced By

gallery@getScreentip (section [2.2.22](#)); gallery@getSelectedItemID (section [2.2.21](#)); gallery@getSelectedItemID (section [2.2.22](#)); gallery@getSelectedItemIndex (section [2.2.21](#)); gallery@getSelectedItemIndex (section [2.2.22](#)); gallery@getShowImage (section [2.2.21](#)); gallery@getShowImage (section [2.2.22](#)); gallery@getShowLabel (section [2.2.21](#)); gallery@getShowLabel (section [2.2.22](#)); gallery@getSize (section [2.2.21](#)); gallery@getSupertip (section [2.2.21](#)); gallery@getSupertip (section [2.2.22](#)); gallery@setVisible (section [2.2.21](#)); gallery@setVisible (section [2.2.22](#)); gallery@onAction (section [2.2.21](#)); gallery@onAction (section [2.2.22](#)); group@getImage (section [2.2.23](#)); group@getKeytip (section [2.2.23](#)); group@getLabel (section [2.2.23](#)); group@getScreentip (section [2.2.23](#)); group@getSupertip (section [2.2.23](#)); group@setVisible (section [2.2.23](#)); labelControl@getEnabled (section [2.2.25](#)); labelControl@getImage (section [2.2.25](#)); labelControl@getImage (section [2.2.25](#)); labelControl@getLabel (section [2.2.25](#)); labelControl@getScreentip (section [2.2.25](#)); labelControl@getShowImage (section [2.2.25](#)); labelControl@getShowLabel (section [2.2.25](#)); labelControl@getSupertip (section [2.2.25](#)); labelControl@setVisible (section [2.2.25](#)); menu@getDescription (section [2.2.28](#)); menu@getDescription (section [2.2.26](#)); menu@getEnabled (section [2.2.28](#)); menu@getEnabled (section [2.2.26](#)); menu@getEnabled (section [2.2.27](#)); menu@getImage (section [2.2.28](#)); menu@getImage (section [2.2.26](#)); menu@getImage (section [2.2.27](#)); menu@getKeytip (section [2.2.28](#)); menu@getKeytip (section [2.2.26](#)); menu@getKeytip (section [2.2.27](#)); menu@getLabel (section [2.2.28](#)); menu@getLabel (section [2.2.26](#)); menu@getLabel (section [2.2.27](#)); menu@getScreentip (section [2.2.28](#)); menu@getScreentip (section [2.2.26](#)); menu@getScreentip (section [2.2.27](#)); menu@getShowImage (section [2.2.28](#)); menu@getShowImage (section [2.2.26](#)); menu@getShowImage (section [2.2.27](#)); menu@getShowLabel (section [2.2.28](#)); menu@getShowLabel (section [2.2.26](#)); menu@getShowLabel (section [2.2.27](#)); menu@getSize (section [2.2.28](#)); menu@getSupertip (section [2.2.28](#)); menu@getSupertip (section [2.2.26](#)); menu@getSupertip (section [2.2.27](#)); menu@getTitle (section [2.2.29](#)); menu@getTitle (section [2.2.27](#)); menu@setVisible (section [2.2.28](#)); menu@setVisible (section [2.2.26](#)); menu@setVisible (section [2.2.27](#)); menuSeparator@getTitle (section [2.2.30](#)); separator@setVisible (section [2.2.34](#)); splitButton@getEnabled (section [2.2.38](#)); splitButton@getEnabled (section [2.2.36](#)); splitButton@getEnabled (section [2.2.37](#)); splitButton@getImage (section [2.2.38](#)); splitButton@getImage (section [2.2.36](#)); splitButton@getImage (section [2.2.37](#)); splitButton@getKeytip (section [2.2.38](#)); splitButton@getKeytip (section [2.2.36](#)); splitButton@getKeytip (section [2.2.37](#)); splitButton@getLabel (section [2.2.38](#)); splitButton@getLabel (section [2.2.36](#)); splitButton@getLabel (section [2.2.37](#)); splitButton@getScreentip (section [2.2.38](#)); splitButton@getScreentip (section [2.2.36](#)); splitButton@getScreentip (section [2.2.37](#)); splitButton@getShowImage (section [2.2.38](#)); splitButton@getShowImage (section [2.2.36](#)); splitButton@getShowImage (section [2.2.37](#)); splitButton@getShowLabel (section [2.2.38](#)); splitButton@getShowLabel (section [2.2.36](#)); splitButton@getShowLabel (section [2.2.37](#)); splitButton@getSize (section [2.2.38](#)); splitButton@getSupertip (section [2.2.38](#)); splitButton@getSupertip (section [2.2.36](#)); splitButton@getSupertip (section [2.2.37](#)); splitButton@setVisible (section [2.2.38](#)); splitButton@setVisible (section [2.2.36](#)); splitButton@setVisible (section [2.2.37](#)); tab@getKeytip (section [2.2.39](#)); tab@getLabel (section [2.2.39](#)); tab@setVisible (section [2.2.39](#)); tabSet@setVisible (section [2.2.41](#)); toggleButton@getDescription (section [2.2.43](#)); toggleButton@getDescription (section [2.2.42](#)); toggleButton@getDescription (section [2.2.44](#)); toggleButton@getEnabled (section [2.2.43](#)); toggleButton@getEnabled (section [2.2.42](#)); toggleButton@getEnabled (section [2.2.44](#)); toggleButton@getImage (section [2.2.43](#)); toggleButton@getImage (section [2.2.42](#)); toggleButton@getImage (section [2.2.44](#)); toggleButton@getKeytip (section [2.2.43](#)); toggleButton@getKeytip (section [2.2.42](#)); toggleButton@getKeytip (section [2.2.44](#)); toggleButton@getLabel (section [2.2.43](#)); toggleButton@getLabel (section [2.2.42](#)); toggleButton@getLabel (section [2.2.44](#)); toggleButton@getPressed (section [2.2.43](#)); toggleButton@getPressed (section [2.2.42](#)); toggleButton@getPressed (section [2.2.44](#)); toggleButton@getScreentip (section [2.2.43](#)); toggleButton@getScreentip (section [2.2.42](#)); toggleButton@getScreentip (section [2.2.44](#)); toggleButton@getShowImage (section [2.2.43](#)); toggleButton@getShowImage (section [2.2.42](#)); toggleButton@getShowImage (section [2.2.44](#)); toggleButton@getShowLabel (section [2.2.43](#)); toggleButton@getShowLabel (section [2.2.42](#)); toggleButton@getShowLabel (section [2.2.44](#)); toggleButton@getSize (section [2.2.43](#)); toggleButton@getSupertip (section [2.2.43](#)); toggleButton@getSupertip (section [2.2.42](#)); toggleButton@getSupertip (section [2.2.44](#)); toggleButton@setVisible (section [2.2.43](#)); toggleButton@setVisible (section [2.2.42](#)); toggleButton@setVisible (section [2.2.44](#)); toggleButton@onAction (section [2.2.43](#)); toggleButton@onAction (section [2.2.42](#)); toggleButton@onAction (section [2.2.44](#));

The following XML schema fragment defines the contents of this simple type:

```

<xsd:simpleType name="ST_Delegate">
  <xsd:restriction base="xsd:string">
    <xsd:minLength value="1"/>
    <xsd:maxLength value="1024"/>
  </xsd:restriction>
</xsd:simpleType>

```

2.3.3 ST_GalleryItemWidthHeight (Gallery Item Width or Height)

Specifies the width or height of gallery items, in pixels.

This simple type's contents are a restriction of the XML schema positiveInteger datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 1.
- This simple type has a maximum value of less than or equal to 4096.

Referenced By

gallery@itemHeight (section [2.2.21](#)); gallery@itemHeight (section [2.2.22](#)); gallery@itemWidth (section [2.2.21](#)); gallery@itemWidth (section [2.2.22](#))

The following XML schema fragment defines the contents of this simple type:

```

<xsd:simpleType name="ST_GalleryItemWidthHeight">
  <xsd:restriction base="xsd:positiveInteger">
    <xsd:minInclusive value="1"/>
    <xsd:maxInclusive value="4096"/>
  </xsd:restriction>
</xsd:simpleType>

```

2.3.4 ST_GalleryRowColumnCount (Gallery Row or Column Count)

Specifies the count of rows or columns in a **gallery** control.

This simple type's contents are a restriction of the XML schema positiveInteger datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 1.
- This simple type has a maximum value of less than or equal to 1024.

Referenced By

gallery@columns (section [2.2.21](#)); gallery@columns (section [2.2.22](#)); gallery@rows (section [2.2.21](#)); gallery@rows (section [2.2.22](#))

The following XML schema fragment defines the contents of this simple type:

```

<xsd:simpleType name="ST_GalleryRowColumnCount">
  <xsd:restriction base="xsd:positiveInteger">

```

```

<xsd:minInclusive value="1"/>
<xsd:maxInclusive value="1024"/>
</xsd:restriction>
</xsd:simpleType>

```

2.3.5 ST_ID (Control ID)

Specifies the identifier of a built-in control. The format of this **string** is defined by per application by the Custom UI Control identifier Tables, as specified in section 3.

This simple type's contents are a restriction of the XML schema **NCName** datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 character.
- This simple type's contents have a maximum length of 1024 characters.

Referenced By
<p>box@insertAfterMso (section 2.2.1); box@insertBeforeMso (section 2.2.1); button@idMso (section 2.2.2); button@idMso (section 2.2.3); button@idMso (section 2.2.4); button@imageMso (section 2.2.2); button@imageMso (section 2.2.3); button@imageMso (section 2.2.4); button@insertAfterMso (section 2.2.2); button@insertAfterMso (section 2.2.3); button@insertAfterMso (section 2.2.4); button@insertBeforeMso (section 2.2.2); button@insertBeforeMso (section 2.2.3); button@insertBeforeMso (section 2.2.4); buttonGroup@insertAfterMso (section 2.2.5); buttonGroup@insertBeforeMso (section 2.2.5); checkBox@idMso (section 2.2.6); checkBox@imageMso (section 2.2.6); checkBox@insertAfterMso (section 2.2.6); checkBox@insertBeforeMso (section 2.2.6); comboBox@idMso (section 2.2.7); comboBox@imageMso (section 2.2.7); comboBox@insertAfterMso (section 2.2.7); comboBox@insertBeforeMso (section 2.2.7); command@idMso (section 2.2.8); control@id (section 2.2.13); control@idMso (section 2.2.12); control@idMso (section 2.2.13); control@idMso (section 2.2.11); control@imageMso (section 2.2.12); control@imageMso (section 2.2.13); control@imageMso (section 2.2.11); control@insertAfterMso (section 2.2.12); control@insertAfterMso (section 2.2.13); control@insertAfterMso (section 2.2.11); control@insertBeforeMso (section 2.2.12); control@insertBeforeMso (section 2.2.13); control@insertBeforeMso (section 2.2.11); dropDown@idMso (section 2.2.17); dropDown@imageMso (section 2.2.17); dropDown@insertAfterMso (section 2.2.17); dropDown@insertBeforeMso (section 2.2.17); dynamicMenu@idMso (section 2.2.19); dynamicMenu@idMso (section 2.2.18); dynamicMenu@imageMso (section 2.2.19); dynamicMenu@imageMso (section 2.2.18); dynamicMenu@insertAfterMso (section 2.2.19); dynamicMenu@insertAfterMso (section 2.2.18); dynamicMenu@insertBeforeMso (section 2.2.19); dynamicMenu@insertBeforeMso (section 2.2.18); editBox@idMso (section 2.2.20); editBox@imageMso (section 2.2.20); editBox@insertAfterMso (section 2.2.20); editBox@insertBeforeMso (section 2.2.20); gallery@idMso (section 2.2.21); gallery@idMso (section 2.2.22); gallery@imageMso (section 2.2.21); gallery@imageMso (section 2.2.22); gallery@insertAfterMso (section 2.2.21); gallery@insertAfterMso (section 2.2.22); gallery@insertBeforeMso (section 2.2.21); gallery@insertBeforeMso (section 2.2.22); group@idMso (section 2.2.23); group@imageMso (section 2.2.23); group@insertAfterMso (section 2.2.23); group@insertBeforeMso (section 2.2.23); item@imageMso (section 2.2.24); labelControl@idMso (section 2.2.25); labelControl@imageMso (section 2.2.25); labelControl@insertAfterMso (section 2.2.25); labelControl@insertBeforeMso (section 2.2.25); menu@idMso (section 2.2.28); menu@idMso (section 2.2.26); menu@idMso (section 2.2.27); menu@imageMso (section 2.2.28); menu@imageMso (section 2.2.26); menu@imageMso (section 2.2.27); menu@insertAfterMso (section 2.2.28); menu@insertAfterMso (section 2.2.26); menu@insertAfterMso (section 2.2.27); menu@insertBeforeMso (section 2.2.28); menu@insertBeforeMso (section 2.2.26); menu@insertBeforeMso (section 2.2.27); menuSeparator@insertAfterMso (section 2.2.30); menuSeparator@insertBeforeMso (section 2.2.30); separator@insertAfterMso (section 2.2.34); separator@insertBeforeMso (section 2.2.34); splitButton@idMso (section 2.2.38); splitButton@idMso (section 2.2.36); splitButton@idMso (section 2.2.37); splitButton@imageMso (section 2.2.38); splitButton@imageMso (section 2.2.36); splitButton@imageMso (section 2.2.37); splitButton@insertAfterMso (section 2.2.38);</p>

Referenced By

splitButton@insertAfterMso (section [2.2.36](#)); splitButton@insertAfterMso (section [2.2.37](#)); splitButton@insertBeforeMso (section [2.2.38](#)); splitButton@insertBeforeMso (section [2.2.36](#)); splitButton@insertBeforeMso (section [2.2.37](#)); tab@idMso (section [2.2.39](#)); tab@insertAfterMso (section [2.2.39](#)); tab@insertBeforeMso (section [2.2.39](#)); tabSet@idMso (section [2.2.41](#)); toggleButton@idMso (section [2.2.43](#)); toggleButton@idMso (section [2.2.42](#)); toggleButton@idMso (section [2.2.44](#)); toggleButton@imageMso (section [2.2.43](#)); toggleButton@imageMso (section [2.2.42](#)); toggleButton@imageMso (section [2.2.44](#)); toggleButton@insertAfterMso (section [2.2.43](#)); toggleButton@insertAfterMso (section [2.2.42](#)); toggleButton@insertAfterMso (section [2.2.44](#)); toggleButton@insertBeforeMso (section [2.2.43](#)); toggleButton@insertBeforeMso (section [2.2.42](#)); toggleButton@insertBeforeMso (section [2.2.44](#));

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_ID">
  <xsd:restriction base="xsd:NCName">
    <xsd:minLength value="1"/>
    <xsd:maxLength value="1024"/>
  </xsd:restriction>
</xsd:simpleType>
```

2.3.6 ST_ItemSize (Menu Item Size)

Specifies the size of the child controls in a **menu** control.

This simple type's contents are a restriction of the XML schema **string** datatype.

The following are possible **enumeration** values for this type:

Enumeration Value	Description
large (Large)	Specifies that the child controls have large sizes.
normal (Normal)	Specifies that the child controls have normal sizes.

Referenced By

menu@itemSize (section [2.2.28](#)); menu@itemSize (section [2.2.26](#)); menu@itemSize (section [2.2.29](#)); menu@itemSize (section [2.2.27](#));

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_ItemSize">
  <xsd:restriction base="xsd:string">
    <xsd:enumeration value="normal"/>
    <xsd:enumeration value="large"/>
  </xsd:restriction>
</xsd:simpleType>
```


2.3.7 ST_Keytip (Keytip)

Specifies a KeyTip string.

This simple type's contents are a restriction of the XML schema **token** datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 character.
- This simple type's contents have a maximum length of 3 characters.

Referenced By

button@keytip (section [2.2.2](#)); button@keytip (section [2.2.3](#)); button@keytip (section [2.2.4](#)); checkBox@keytip (section [2.2.6](#)); comboBox@keytip (section [2.2.7](#)); control@keytip (section [2.2.12](#)); control@keytip (section [2.2.13](#)); control@keytip (section [2.2.11](#)); dropDown@keytip (section [2.2.17](#)); dynamicMenu@keytip (section [2.2.19](#)); dynamicMenu@keytip (section [2.2.18](#)); editBox@keytip (section [2.2.20](#)); gallery@keytip (section [2.2.21](#)); gallery@keytip (section [2.2.22](#)); group@keytip (section [2.2.23](#)); labelControl@keytip (section [2.2.25](#)); menu@keytip (section [2.2.28](#)); menu@keytip (section [2.2.26](#)); menu@keytip (section [2.2.27](#)); splitButton@keytip (section [2.2.38](#)); splitButton@keytip (section [2.2.36](#)); splitButton@keytip (section [2.2.37](#)); tab@keytip (section [2.2.39](#)); toggleButton@keytip (section [2.2.43](#)); toggleButton@keytip (section [2.2.42](#)); toggleButton@keytip (section [2.2.44](#))

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_Keytip">
  <xsd:restriction base="xsd:token">
    <xsd:minLength value="1"/>
    <xsd:maxLength value="3"/>
    <xsd:whiteSpace value="collapse"/>
  </xsd:restriction>
</xsd:simpleType>
```

2.3.8 ST_LongString (Long String)

Specifies a string that can have an extended length.

This simple type's contents are a restriction of the XML schema **string** datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 character.
- This simple type's contents have a maximum length of 4096 characters.

Referenced By

button@description (section [2.2.2](#)); button@description (section [2.2.3](#)); button@description (section [2.2.4](#)); checkBox@description (section [2.2.6](#)); control@description (section [2.2.12](#)); control@description (section [2.2.13](#)); dynamicMenu@description (section [2.2.19](#)); dynamicMenu@description (section [2.2.18](#)); gallery@description (section [2.2.21](#)); gallery@description (section [2.2.22](#)); menu@description (section [2.2.28](#)); menu@description (section [2.2.26](#)); toggleButton@description (section [2.2.43](#)); toggleButton@description (section [2.2.42](#)); toggleButton@description (section [2.2.44](#))

The following XML schema fragment defines the contents of this simple type:

```

<xsd:simpleType name="ST_LongString">
  <xsd:restriction base="xsd:string">
    <xsd:minLength value="1"/>
    <xsd:maxLength value="4096"/>
  </xsd:restriction>
</xsd:simpleType>

```

2.3.9 ST_QID (Qualified Control ID)

Specifies a control identifier that is qualified by an XML namespace prefix. The prefix determines which namespace to which the control belongs.

If the namespace is equal to the Custom UI namespace, the qualified identifier references the application's built-in control set.

For example, consider the following XML fragment:

```

<customUI xmlns="http://schemas.microsoft.com/office/2006/01/customui"
  xmlns:mso="http://schemas.microsoft.com/office/2006/01/customui">
  <ribbon>
    <tabs>
      <tab idQ="mso:TabHome" visible="false" />
    </tabs>
  </ribbon>
</customUI>

```

In this example the **mso** namespace prefix is set to the Custom UI namespace, so names qualified with **mso** refer to built-in controls. Thus, the use of the **idQ** attribute on the **tab** element is equivalent to using the **idMso** attribute, as follows:

```

<tab idMso="TabHome" visible="false" />

```

If the prefix is set to any other value, qualified identifiers reference controls in a unique custom namespace. If multiple Custom UI documents refer to controls in the same namespace, they can share common containers.

For example, consider the following XML fragment:

```

<customUI
  xmlns="http://schemas.microsoft.com/office/2006/01/customui"
  xmlns:ex="http://www.example.com">
  <ribbon>
    <tabs>
      <tab idQ="ex:OtherTab" label="Shared Tab">
        <group id="MyGroup" label="My Group">
          ...
        </group>
      </tab>
    </tabs>
  </ribbon>
</customUI>

```

In this case, **ex** is an XML namespace prefix for the namespace <http://www.example.com>. This XML fragment refers to a **tab** in that namespace with an identifier of "OtherTab". If that tab cannot be found, it is created. A new group belonging to this file is added to the **tab**.

This simple type's contents are a restriction of the XML schema **QName** datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 character.
- This simple type's contents have a maximum length of 1024 characters.

Referenced By
<p>box@idQ (section 2.2.1); box@insertAfterQ (section 2.2.1); box@insertBeforeQ (section 2.2.1); button@idQ (section 2.2.2); button@idQ (section 2.2.3); button@idQ (section 2.2.4); button@insertAfterQ (section 2.2.2); button@insertAfterQ (section 2.2.3); button@insertAfterQ (section 2.2.4); button@insertBeforeQ (section 2.2.2); button@insertBeforeQ (section 2.2.3); button@insertBeforeQ (section 2.2.4); buttonGroup@idQ (section 2.2.5); buttonGroup@insertAfterQ (section 2.2.5); buttonGroup@insertBeforeQ (section 2.2.5); checkBox@idQ (section 2.2.6); checkBox@insertAfterQ (section 2.2.6); checkBox@insertBeforeQ (section 2.2.6); comboBox@idQ (section 2.2.7); comboBox@insertAfterQ (section 2.2.7); comboBox@insertBeforeQ (section 2.2.7); control@idQ (section 2.2.12); control@idQ (section 2.2.13); control@idQ (section 2.2.11); control@insertAfterQ (section 2.2.12); control@insertAfterQ (section 2.2.13); control@insertAfterQ (section 2.2.11); control@insertBeforeQ (section 2.2.12); control@insertBeforeQ (section 2.2.13); control@insertBeforeQ (section 2.2.11); dropDown@idQ (section 2.2.17); dropDown@insertAfterQ (section 2.2.17); dropDown@insertBeforeQ (section 2.2.17); dynamicMenu@idQ (section 2.2.18); dynamicMenu@insertAfterQ (section 2.2.19); dynamicMenu@insertAfterQ (section 2.2.18); dynamicMenu@insertBeforeQ (section 2.2.19); dynamicMenu@insertBeforeQ (section 2.2.18); editBox@idQ (section 2.2.20); editBox@insertAfterQ (section 2.2.20); editBox@insertBeforeQ (section 2.2.20); gallery@idQ (section 2.2.21); gallery@idQ (section 2.2.22); gallery@insertAfterQ (section 2.2.21); gallery@insertAfterQ (section 2.2.22); gallery@insertBeforeQ (section 2.2.21); gallery@insertBeforeQ (section 2.2.22); group@idQ (section 2.2.23); group@insertAfterQ (section 2.2.23); group@insertBeforeQ (section 2.2.23); labelControl@idQ (section 2.2.25); labelControl@insertAfterQ (section 2.2.25); labelControl@insertBeforeQ (section 2.2.25); menu@idQ (section 2.2.28); menu@idQ (section 2.2.27); menu@insertAfterQ (section 2.2.28); menu@insertAfterQ (section 2.2.26); menu@insertAfterQ (section 2.2.27); menu@insertBeforeQ (section 2.2.28); menu@insertBeforeQ (section 2.2.26); menu@insertBeforeQ (section 2.2.27); menuSeparator@idQ (section 2.2.30); menuSeparator@insertAfterQ (section 2.2.30); menuSeparator@insertBeforeQ (section 2.2.30); separator@idQ (section 2.2.34); separator@insertAfterQ (section 2.2.34); separator@insertBeforeQ (section 2.2.34); splitButton@idQ (section 2.2.38); splitButton@idQ (section 2.2.36); splitButton@idQ (section 2.2.37); splitButton@insertAfterQ (section 2.2.38); splitButton@insertAfterQ (section 2.2.37); splitButton@insertBeforeQ (section 2.2.38); splitButton@insertBeforeQ (section 2.2.36); splitButton@insertBeforeQ (section 2.2.37); tab@idQ (section 2.2.39); tab@insertAfterQ (section 2.2.39); tab@insertBeforeQ (section 2.2.39); toggleButton@idQ (section 2.2.43); toggleButton@idQ (section 2.2.42); toggleButton@idQ (section 2.2.44); toggleButton@insertAfterQ (section 2.2.43); toggleButton@insertAfterQ (section 2.2.42); toggleButton@insertAfterQ (section 2.2.44); toggleButton@insertBeforeQ (section 2.2.43); toggleButton@insertBeforeQ (section 2.2.42); toggleButton@insertBeforeQ (section 2.2.44);</p>

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_QID">
  <xsd:restriction base="xsd:QName">
    <xsd:minLength value="1"/>
    <xsd:maxLength value="1024"/>
  </xsd:restriction>
</xsd:simpleType>
```

```
</xsd:simpleType>
```

2.3.10 ST_Size (Control Size)

Specifies the size of a control.

This simple type's contents are a restriction of the XML schema **string** datatype.

The following are possible **enumeration** values for this type:

Enumeration Value	Description
large (Large Control Size)	Specifies the large control size.
normal (Normal Control Size)	Specifies the normal control size.

Referenced By
button@size (section 2.2.2); control@size (section 2.2.12); control@size (section 2.2.13); dynamicMenu@size (section 2.2.19); gallery@size (section 2.2.21); menu@size (section 2.2.28); splitButton@size (section 2.2.38); toggleButton@size (section 2.2.43)

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_Size">  
  <xsd:restriction base="xsd:string">  
    <xsd:enumeration value="normal"/>  
    <xsd:enumeration value="large"/>  
  </xsd:restriction>  
</xsd:simpleType>
```

2.3.11 ST_String (Short String)

Specifies a string with a limited length.

This simple type's contents are a restriction of the XML schema **string** datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 character.
- This simple type's contents have a maximum length of 1024 characters.

Referenced By
button@label (section 2.2.2); button@label (section 2.2.3); button@label (section 2.2.4); button@screentip (section 2.2.2); button@screentip (section 2.2.3); button@screentip (section 2.2.4); button@supertip (section 2.2.2); button@supertip (section 2.2.3); button@supertip (section 2.2.4); button@tag (section 2.2.2); button@tag (section 2.2.3); button@tag (section 2.2.4); checkBox@label (section 2.2.6); checkBox@screentip (section 2.2.6); checkBox@supertip (section 2.2.6); checkBox@tag (section 2.2.6); comboBox@label (section 2.2.7); comboBox@screentip (section 2.2.7); comboBox@sizeString (section 2.2.7); comboBox@supertip (section 2.2.7); comboBox@tag (section 2.2.7)

Referenced By

[2.2.7](#)); control@label (section [2.2.12](#)); control@label (section [2.2.13](#)); control@label (section [2.2.11](#)); control@screentip (section [2.2.12](#)); control@screentip (section [2.2.13](#)); control@screentip (section [2.2.11](#)); control@supertip (section [2.2.12](#)); control@supertip (section [2.2.13](#)); control@supertip (section [2.2.11](#)); control@tag (section [2.2.12](#)); control@tag (section [2.2.11](#)); dropDown@label (section [2.2.17](#)); dropDown@screentip (section [2.2.17](#)); dropDown@sizeString (section [2.2.17](#)); dropDown@supertip (section [2.2.17](#)); dropDown@tag (section [2.2.17](#)); dynamicMenu@label (section [2.2.19](#)); dynamicMenu@label (section [2.2.18](#)); dynamicMenu@screentip (section [2.2.19](#)); dynamicMenu@screentip (section [2.2.18](#)); dynamicMenu@supertip (section [2.2.19](#)); dynamicMenu@supertip (section [2.2.18](#)); dynamicMenu@tag (section [2.2.19](#)); dynamicMenu@tag (section [2.2.18](#)); editBox@label (section [2.2.20](#)); editBox@screentip (section [2.2.20](#)); editBox@sizeString (section [2.2.20](#)); editBox@supertip (section [2.2.20](#)); editBox@tag (section [2.2.20](#)); gallery@label (section [2.2.21](#)); gallery@label (section [2.2.22](#)); gallery@screentip (section [2.2.21](#)); gallery@screentip (section [2.2.22](#)); gallery@sizeString (section [2.2.21](#)); gallery@sizeString (section [2.2.22](#)); gallery@supertip (section [2.2.21](#)); gallery@supertip (section [2.2.22](#)); gallery@tag (section [2.2.21](#)); gallery@tag (section [2.2.22](#)); group@label (section [2.2.23](#)); group@screentip (section [2.2.23](#)); group@supertip (section [2.2.23](#)); group@tag (section [2.2.23](#)); item@label (section [2.2.24](#)); item@screentip (section [2.2.24](#)); item@supertip (section [2.2.24](#)); labelControl@label (section [2.2.25](#)); labelControl@screentip (section [2.2.25](#)); labelControl@supertip (section [2.2.25](#)); labelControl@tag (section [2.2.25](#)); menu@label (section [2.2.28](#)); menu@label (section [2.2.26](#)); menu@label (section [2.2.27](#)); menu@screentip (section [2.2.28](#)); menu@screentip (section [2.2.26](#)); menu@screentip (section [2.2.27](#)); menu@supertip (section [2.2.28](#)); menu@supertip (section [2.2.26](#)); menu@supertip (section [2.2.27](#)); menu@tag (section [2.2.28](#)); menu@tag (section [2.2.26](#)); menu@tag (section [2.2.27](#)); menu@title (section [2.2.29](#)); menu@title (section [2.2.27](#)); menuSeparator@title (section [2.2.30](#)); splitButton@label (section [2.2.38](#)); splitButton@label (section [2.2.36](#)); splitButton@label (section [2.2.37](#)); splitButton@screentip (section [2.2.38](#)); splitButton@screentip (section [2.2.36](#)); splitButton@screentip (section [2.2.37](#)); splitButton@supertip (section [2.2.38](#)); splitButton@supertip (section [2.2.36](#)); splitButton@supertip (section [2.2.37](#)); splitButton@tag (section [2.2.38](#)); splitButton@tag (section [2.2.36](#)); splitButton@tag (section [2.2.37](#)); tab@label (section [2.2.39](#)); tab@tag (section [2.2.39](#)); toggleButton@label (section [2.2.43](#)); toggleButton@label (section [2.2.42](#)); toggleButton@label (section [2.2.44](#)); toggleButton@screentip (section [2.2.43](#)); toggleButton@screentip (section [2.2.42](#)); toggleButton@screentip (section [2.2.44](#)); toggleButton@supertip (section [2.2.43](#)); toggleButton@supertip (section [2.2.42](#)); toggleButton@supertip (section [2.2.44](#)); toggleButton@tag (section [2.2.43](#)); toggleButton@tag (section [2.2.42](#)); toggleButton@tag (section [2.2.44](#))

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_String">
  <xsd:restriction base="xsd:string">
    <xsd:minLength value="1"/>
    <xsd:maxLength value="1024"/>
  </xsd:restriction>
</xsd:simpleType>
```

2.3.12 ST_StringLength (String Length)

Specifies the length of a string, in characters.

This simple type's contents are a restriction of the XML schema **positiveInteger** datatype.

This simple type also specifies the following restrictions:

- This simple type has a minimum value of greater than or equal to 1.
- This simple type has a maximum value of less than or equal to 1024.

Referenced By

comboBox@maxLength (section [2.2.7](#)); editBox@maxLength (section [2.2.20](#))

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_StringLength">
  <xsd:restriction base="xsd:positiveInteger">
    <xsd:minInclusive value="1"/>
    <xsd:maxInclusive value="1024"/>
  </xsd:restriction>
</xsd:simpleType>
```

2.3.13 ST_UniqueID (Custom Control ID)

Specifies a custom control identifier.

This simple type's contents are a restriction of the XML schema **identifier** datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 character.
- This simple type's contents have a maximum length of 1024 characters.

Referenced By

box@id (section [2.2.1](#)); button@id (section [2.2.2](#)); button@id (section [2.2.3](#)); button@id (section [2.2.4](#)); buttonGroup@id (section [2.2.5](#)); checkBox@id (section [2.2.6](#)); comboBox@id (section [2.2.7](#)); control@id (section [2.2.12](#)); control@id (section [2.2.11](#)); dropDown@id (section [2.2.17](#)); dynamicMenu@id (section [2.2.19](#)); dynamicMenu@id (section [2.2.18](#)); editBox@id (section [2.2.20](#)); gallery@id (section [2.2.21](#)); gallery@id (section [2.2.22](#)); group@id (section [2.2.23](#)); item@id (section [2.2.24](#)); labelControl@id (section [2.2.25](#)); menu@id (section [2.2.28](#)); menu@id (section [2.2.26](#)); menu@id (section [2.2.27](#)); menuSeparator@id (section [2.2.30](#)); separator@id (section [2.2.34](#)); splitButton@id (section [2.2.38](#)); splitButton@id (section [2.2.36](#)); splitButton@id (section [2.2.37](#)); tab@id (section [2.2.39](#)); toggleButton@id (section [2.2.43](#)); toggleButton@id (section [2.2.42](#)); toggleButton@id (section [2.2.44](#))

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_UniqueID">
  <xsd:restriction base="xsd:identifier">
    <xsd:minLength value="1"/>
    <xsd:maxLength value="1024"/>
  </xsd:restriction>
</xsd:simpleType>
```

2.3.14 ST_Uri (Image Relationship ID)

Specifies the relationship identifier of a part that is the target of a relationship from the containing Custom UI document.

The target part is an image part type, as specified in [\[ECMA-376\]](#) Part 1 section 15.2.13.

This simple type's contents are a restriction of the XML schema **string** datatype.

This simple type also specifies the following restrictions:

- This simple type's contents have a minimum length of 1 characters.
- This simple type's contents have a maximum length of 1024 characters.

Referenced By
button@image (section 2.2.2); button@image (section 2.2.3); button@image (section 2.2.4); checkBox@image (section 2.2.6); comboBox@image (section 2.2.7); control@image (section 2.2.12); control@image (section 2.2.13); control@image (section 2.2.11); dropDown@image (section 2.2.17); dynamicMenu@image (section 2.2.19); dynamicMenu@image (section 2.2.18); editBox@image (section 2.2.20); gallery@image (section 2.2.21); gallery@image (section 2.2.22); group@image (section 2.2.23); item@image (section 2.2.24); labelControl@image (section 2.2.25); menu@image (section 2.2.28); menu@image (section 2.2.26); menu@image (section 2.2.27); splitButton@image (section 2.2.38); splitButton@image (section 2.2.36); splitButton@image (section 2.2.37); toggleButton@image (section 2.2.43); toggleButton@image (section 2.2.42); toggleButton@image (section 2.2.44)

The following XML schema fragment defines the contents of this simple type:

```
<xsd:simpleType name="ST_Uri">  
  <xsd:restriction base="xsd:string">  
    <xsd:minLength value="1"/>  
    <xsd:maxLength value="1024"/>  
  </xsd:restriction>  
</xsd:simpleType>
```

3 Appendix A: Custom UI Control ID Tables

3.1 idMso Tables

3.1.1 Word 2007

idMso	Control Type	Label
Spelling	button	Spelling...
FileSave	button	Save
FilePrint	button	Print
ZoomOnePage	button	One Page
ZoomPageWidth	button	Page Width
Zoom100	button	Zoom 100%
ColumnsDialog	button	More Columns...
Numbering	toggleButton	Numbering
Bullets	toggleButton	Bullets
PageOrientationPortraitLandscape	button	Portrait/Landscape
OutdentClassic	button	Decrease Indent
IndentClassic	button	Increase Indent
DrawingInsert	button	Insert Drawing
ChartInsert	button	Chart...
FileNew	button	New
Copy	button	Copy
Cut	button	Cut
Paste	button	Paste
FileOpen	button	Open
EnvelopesAndLabelsDialog	button	Envelopes...
Superscript	toggleButton	Superscript
Subscript	toggleButton	Subscript
UnderlineDouble	toggleButton	Double Underline
UnderlineWords	button	Word Underline
FontSizeIncreaseWord	button	Grow Font

idMso	Control Type	Label
FontSizeDecreaseWord	button	Shrink Font
FileClose	button	Close
TableAutoFormat	button	Table AutoFormat...
FormatPainter	toggleButton	Format Painter
FilePrintPreview	toggleButton	Print Preview
PasteApplyStyle	button	Apply Style
Bold	toggleButton	Bold
Italic	toggleButton	Italic
Underline	toggleButton	Underline
ParagraphMarks	toggleButton	Show All
AlignLeft	toggleButton	Align Left
AlignRight	toggleButton	Align Right
AlignCenter	toggleButton	Center
AlignJustify	toggleButton	Justify
HeaderFooterPageNumberInsert	menu	Page Number
Undo	gallery	Undo
Redo	gallery	Redo
OutlinePromote	button	Promote
OutlineDemote	button	Demote
OutlineMoveUp	button	Move Up
OutlineMoveDown	button	Move Down
OutlineDemoteToBodyText	button	Demote to Body Text
OutlineExpand	button	Expand
OutlineCollapse	button	Collapse
TextBoxInsert	button	Text Box
FileFind	button	Find File...
FindDialog	button	Find...
TableExcelSpreadsheetInsert	button	Excel Spreadsheet
AutoFormat	button	AutoFormat...

idMso	Control Type	Label
BorderInside	toggleButton	Inside Borders
BorderOutside	toggleButton	Outside Borders
BorderNone	toggleButton	No Border
MailMergeGoToFirstRecord	button	First
MailMergeGoToPreviousRecord	button	Previous
MailMergeGoToNextRecord	button	Next
MailMergeGotToLastRecord	button	Last
MailMergeMergeToDocument	button	Edit Individual Documents...
MailMergeMergeToPrinter	button	Print Documents...
MailMergeAutoCheckForErrors	button	Auto Check for Errors...
DataFormSource	button	Data Form
MailMergeResultsPreview	toggleButton	Preview Results
ObjectsGroup	button	Group
ObjectsUngroup	button	Ungroup
ObjectBringToFront	button	Bring to Front
ObjectSendToBack	button	Send to Back
ObjectBringForward	button	Bring Forward
ObjectSendBackward	button	Send Backward
Magnifier	checkBox	Magnifier
PrintPreviewShrinkOnePage	button	Shrink One Page
ViewFullScreenView	button	Full Screen
VoiceInsert	button	Voice Comment
ObjectsSelect	toggleButton	Select Objects
TableFind	button	Find
MacroRecord	button	Record Macro...
MacroRecorderPause	button	Pause Recording
MacroPlay	button	Macros
ShapeFreeform	toggleButton	Freeform
ObjectEditPoints	toggleButton	Edit Points

idMso	Control Type	Label
CalloutOptions	button	Callout Options
DataFormAddRecord	button	Add
DataFormDeleteRecord	button	Delete
FieldsUpdate	button	Update
DatabaseInsert	button	Insert Database
GridSettings	button	Grid Settings...
WordPicture	button	Word Picture
FormControlEditBox	button	Edit Box
FormControlCheckBox	button	Check Box
FormControlComboBox	button	Combo Box
PropertySheet	button	Property Sheet
FieldShading	toggleButton	Show Field Shading
ViewDraftView	toggleButton	Draft
Lock	toggleButton	Lock
AutoSum	button	Sum
MasterDocumentShow	toggleButton	Show Document
MasterDocumentCreateSubdocument	button	Create
MasterDocumentUnlinkSubdocument	button	Unlink
MasterDocumentInsertSubdocument	button	Insert...
MasterDocumentSplitSubdocuments	button	Split
MasterDocumentMergeSubdocuments	button	Merge
MasterDocumentLockSubdocument	toggleButton	Lock Document
HeaderOrFooterShow	button	Show Header/Footer
HeaderFooterPreviousSection	button	Previous Section
HeaderFooterNextSection	button	Next Section
AlignDialog	button	Align
MailMergeDocument	button	Mail Merge Document
MergeOptions	button	Merge...
MailMergeHelper	button	Mail Merge...

idMso	Control Type	Label
PageSetupDialog	button	Page Setup...
BodyTextHide	button	Hide Body Text
HeaderFooterLinkToPrevious	toggleButton	Link to Previous
OutlineShowFirstLineOnly	checkBox	Show First Line Only
OutlineShowTextFormatting	checkBox	Show Text Formatting
FontDialog	button	Font...
StylesDialogClassic	button	Edit Cell Styles
FootnoteInsert	button	Insert Footnote
MicrosoftExcel	button	Microsoft Excel
MicrosoftAccess	button	Microsoft Access
MicrosoftPowerPoint	button	Microsoft Office PowerPoint
MicrosoftPublisher	button	Microsoft Publisher
MicrosoftProject	button	Microsoft Project
ViewPrintLayoutView	toggleButton	Print Layout
FieldCodes	toggleButton	View Field Codes
DropCapOptionsDialog	button	Drop Cap Options...
Strikethrough	toggleButton	Strikethrough
TextSmallCaps	toggleButton	Small Caps
CellsDelete	button	Delete Cells...
TableRowsDelete	button	Delete Rows
TableColumnsDelete	button	Delete Columns
CellsInsertDialog	button	Insert Cells...
TableRowsInsertWord	button	Insert Rows
WindowsArrangeAll	button	Arrange All
MarginsAdjust	button	Adjust Margins
ViewGridlinesWord	checkBox	View Gridlines
SubdocumentOpen	button	Open Subdocument
WindowSplit	button	Split
WindowNew	button	New Window

idMso	Control Type	Label
ReviewAcceptOrRejectChangeDialog	button	Accept/Reject Changes
TextAllCaps	toggleButton	All Caps
PictureDisassemble	button	Disassemble Picture
ChangeCaseDialogClassic	button	Change Case...
FontSizeDecrease1Point	button	Shrink Font 1 Pt
FontSizeIncrease1Point	button	Grow Font 1 Pt
Repaginate	button	Repaginate
ReplaceDialog	button	Replace...
StartOfLine	button	Start of Line
EndOfLine	button	End of Line
PagePrevious	button	Previous Page
PageNext	button	Next Page
StartOfDocument	button	Start of Document
EndOfDocument	button	End of Document
Grammar	button	Grammar...
FileCloseOrCloseAll	button	Close
TextToOrFromTable	button	Text to/from Table
TableRowsOrColumnsOrCellsInsert	button	Insert Table
TableRowsOrColumnsOrCellsDelete	button	Delete Rows/Columns/Cells
RedoOrRepeat	button	Redo
ProtectOrUnprotectDocument	button	Protect Document
FrameInsertOrFormat	button	Insert Frame
ObjectsRegroup	button	Regroup
AutoFormatChange	button	Tip Wizard 6
AddressBook	button	Address Book...
Reply	button	Reply
ReplyAll	button	Reply to All
Forward	button	Forward
MailMove	button	Move Mail

idMso	Control Type	Label
MailDelete	button	Delete Mail
MessagePrevious	button	Previous Item
MessageNext	button	Next Item
MailSelectNames	button	Select Names...
AsianLayoutCharacterScaling	menu	Character Scaling
ShapeScribble	toggleButton	Scribble
PrintSetupDialog	button	Print Setup...
RowHeight	button	Row Height...
ColumnWidth	button	Column Width...
OleObjectctInsert	button	Object...
Cancel	button	Cancel
FindNext	button	Find Next
PasteDuplicate	button	Duplicate
ClipArtInsert	toggleButton	Clip Art...
ParagraphSpacingIncrease	button	Increase Paragraph Spacing
ParagraphSpacingDecrease	button	Decrease Paragraph Spacing
OrganizationChartInsert	button	Organization Chart
CombineCharacters	toggleButton	Yoko-Gumi
DoubleStrikethrough	toggleButton	Double Strikethrough
PictureCrop	toggleButton	Crop
ViewOutlineView	toggleButton	Outline
FileCloseAll	button	Close All
FileSaveAs	button	Save As
SaveAll	button	Save All
AdvancedFileProperties	button	View Document Properties...
DocumentTemplate	button	Document Template
CopyAsPicture	button	Copy as Picture...
PasteSpecialDialog	button	Paste Special...

idMso	Control Type	Label
SelectAll	button	Select All
GoTo	button	Go To...
BookmarkInsert	button	Bookmark...
FileLinksToFiles	button	Edit Links to Files
ViewOnlineLayoutViewClassic	button	Online Layout
FootnotesEndnotesShow	button	Show Notes
BreakInsertDialog	button	Break
DateAndTimeInsert	button	Date & Time...
NumberInsert	button	Number...
FieldInsert	button	Field...
FormField	button	Form Field...
CaptionInsert	button	Insert Caption...
CrossReferenceInsert	button	Cross-reference...
IndexAndTables	button	Index and Tables
TextFromFileInsert	button	Text from File...
ParagraphDialog	button	Paragraph...
TabsDialog	button	Tabs...
BordersShadingDialog	button	Borders and Shading...
TextDirectionOptionsDialog	button	Text Direction Options...
BulletsAndNumberingBulletsDialog	button	Bullets and Numbering...
StyleGalleryDialog	button	Style Gallery...
FrameDialog	button	Frame...
SetLanguage	button	Set Language...
WordCount	button	Word Count...
AutoCorrect	button	AutoCorrect Options...
EnvelopesAndLabels	button	Envelope & Label Wizard
LabelsDialog	button	Labels...
MergeCells	button	Merge Cells
SplitCells	button	Split Cells...

idMso	Control Type	Label
TableRowSelect	button	Select Row
TableColumnSelect	button	Select Column
TableSelect	button	Select Table
TableCellHeightWidth	button	Cell Height and Width...
TableRepeatHeaderRows	toggleButton	Repeat Header Rows
ConvertTextToTable	button	Convert Text to Table...
TableFormulaDialog	button	Formula...
TableSplitTable	button	Split Table
ShowClipboard	button	Office Clipboard...
NumberingSkip	button	Skip Numbering
KeyboardCustomization	button	Customize Keyboard...
ShowAllHeadings	button	All
ImeDictionaryUpdate	button	Update IME Dictionary...
OutlookTaskCreate	button	Create Microsoft Office Outlook Task
WindowMinimize	button	Minimize
WindowRestore	button	Restore
WindowClose	button	Close
WindowMove	button	Move
WindowSize	button	Size
WindowNext	button	Next Window
ClearFormats	button	Clear Formats
OK	button	OK
ClosePane	button	Close
PrintPreviewClose	button	Close Print Preview
HeaderFooterClose	button	Close Header and Footer
ZoomDialog	button	Zoom...
About	button	About
SortDialogClassic	button	Sort...
ConvertTableToText	button	Convert to Text...

idMso	Control Type	Label
ExchangeFolder	button	Exchange Folder...
ChartEditDataSource	button	Select Data...
WindowMoreWindowsDialog	toggleButton	More Windows...
ObjectEditDialog	button	Object...
ObjectFormatDialog	button	Object...
AutoTextCreate	button	Create AutoText...
ContentsAndIndex	button	Contents and Index
Help	button	Help
FontColorMoreColorsDialog	button	More Colors...
WebGoBack	button	Back
WebGoForward	button	Forward
AddToFavorites	button	Add to Favorites...
BrowsePrevious	button	Previous
BrowseNext	button	Next
SmartArtInsert	button	SmartArt...
ShapeRerouteConnectors	toggleButton	Reroute Connectors
ObjectNudgeUp	button	Up
ObjectNudgeDown	button	Down
ObjectNudgeLeft	button	Left
ObjectNudgeRight	button	Right
ShapeCurve	toggleButton	Curve
ShapeStraightConnector	toggleButton	Straight Connector
ShapeElbowConnector	toggleButton	Elbow Connector
ObjectFillMoreColorsDialog	button	More Fill Colors...
ObjectBorderOutlineColorMoreColorsDialog	button	More Outline Colors...
OutlineLinePatternFill	button	Pattern...
LineStylesDialog	button	More Lines...
ArrowsMore	button	More Arrows...
WordArtVerticalText	toggleButton	Vertical Text

idMso	Control Type	Label
WordArtEvenTextHeightClassic	toggleButton	Even Height
ContrastMore	button	More Contrast
ContrastLess	button	Less Contrast
BrightnessMore	button	More Brightness
BrightnessLess	button	Less Brightness
ShadowNudgeUpClassic	button	Nudge Shadow Up
ShadowNudgeDownClassic	button	Nudge Shadow Down
ShadowNudgeLeftClassic	button	Nudge Shadow Left
ShadowNudgeRightClassic	button	Nudge Shadow Right
ObjectShadowColorMoreColorsDialog	button	More Shadow Colors...
_3DEffectColorPickerMoreClassic	button	More 3-D Colors...
TextAlignLeft	toggleButton	Left Align
TextAlignCenter	toggleButton	Center
ShapeRectangle	toggleButton	Rectangle
ShapeRoundedRectangle	toggleButton	Rounded Rectangle
ShapeIsoscelesTriangle	toggleButton	Isosceles Triangle
ShapeOval	toggleButton	Oval
ShapeLeftBrace	toggleButton	Left Brace
ShapeRightBrace	toggleButton	Right Brace
ShapeArc	toggleButton	Arc
ShapeRightArrow	toggleButton	Right Arrow
ShapeDownArrow	toggleButton	Down Arrow
ShapeRoundedRectangularCallout	toggleButton	Rounded Rectangular Callout
ShapeStar	toggleButton	5-Point Star
TextAlignRight	toggleButton	Right Align
TextAlignLetterJustify	toggleButton	Letter Justify
TextAlignWordJustify	toggleButton	Word Justify
TextAlignStretchJustify	toggleButton	Stretch Justify
WordArtSpacingVeryTight	toggleButton	Very Tight

idMso	Control Type	Label
WordArtSpacingTight	toggleButton	Tight
WordArtSpacingNormal	toggleButton	Normal
WordArtSpacingLoose	toggleButton	Loose
WordArtSpacingVeryLoose	toggleButton	Very Loose
WordArtSpacingKernCharacterPairs	toggleButton	Kern Character Pairs
PictureReset	button	Reset Picture
TextWrappingSquare	toggleButton	Square
TextWrappingTight	toggleButton	Tight
TextWrappingNoneClassic	toggleButton	None
TextWrappingEditWrapPoints	toggleButton	Edit Wrap Points
_3DEffectsOnOffClassic	toggleButton	3-D On/Off
_3DTiltDownClassic	button	Tilt Down
_3DTiltUpClassic	button	Tilt Up
_3DTiltLeftClassic	button	Tilt Left
_3DTiltRightClassic	button	Tilt Right
_3DExtrusionPerspectiveClassic	toggleButton	Perspective
_3DExtrusionParallelClassic	toggleButton	Parallel
_3DLightingFlatClassic	toggleButton	Bright
_3DLightingNormalClassic	toggleButton	Normal
_3DLightingDimClassic	toggleButton	Dim
ObjectEditText	button	Edit Text
PictureFormatDialog	button	Picture...
ViewVisualBasicCode	button	View Code
DrawingNewClassic	button	New Drawing
WebOpenInNewWindow	button	Open in New Window
HyperlinkCopy	button	Copy Hyperlink
HyperlinkInsert	button	Hyperlink...
HyperlinkEdit	button	Edit Hyperlink...
HyperlinkSelect	button	Select Hyperlink

idMso	Control Type	Label
ReviewNewComment	button	New Comment
ReviewPreviousComment	button	Previous
ReviewNextComment	button	Next
ReviewDeleteComment	button	Delete
ReviewShowAllComments	button	Show All Comments
DesignMode	toggleButton	Design Mode
WordArtInsertDialogClassic	button	WordArt Gallery
FormFieldProperties	button	Properties
FullScreenViewClassic	button	Full Screen
AutoScroll	button	Auto Scroll
MasterDocumentExpandOrCollapseSubdocuments	toggleButton	Expand/Collapse Subdocuments
VisualBasic	button	Visual Basic
BordersAll	toggleButton	All Borders
AutoSummarize	button	Auto Summarize
ViewDocumentMap	checkBox	Document Map
ReviewAcceptChange	button	Accept Change
ReviewRejectChange	button	Reject Change
TableDrawBorderPenStyle	dropDown	Pen Style
AutoSummaryExitView	button	Close
Font	comboBox	Font:
WhoIs	button	Who Is...
FontSize	comboBox	Font Size:
StyleGalleryClassic	comboBox	Style:
ZoomClassic	button	Zoom:
DocumentLocation	comboBox	Address:
MessageHeaderToggle	button	Message Header
BorderInsideHorizontal	toggleButton	Inside Horizontal Border
BorderInsideVertical	toggleButton	Inside Vertical Border
BorderDiagonalDown	toggleButton	Diagonal Down Border

idMso	Control Type	Label
BorderDiagonalUp	toggleButton	Diagonal Up Border
TextDirectionLeftToRight	toggleButton	Left-to-Right
TextDirectionRightToLeft	toggleButton	Right-to-Left
ActiveXCheckBox	button	Check Box
ActiveXTextBox	button	Text Box
ActiveXButton	button	Command Button
ActiveXRadioButton	button	Option Button
ActiveXListBox	button	List Box
ActiveXComboBox	button	Combo Box
ActiveXToggleButton	button	Toggle Button
ActiveXSpinButton	button	Spin Button
ActiveXScrollBar	button	Scroll Bar
ActiveXLabel	button	Label
ShadowSemitransparentClassic	toggleButton	Semitransparent Shadow
OleConvert	button	Convert...
ReviewTrackChanges	toggleButton	Track Changes
ReviewHighlightChanges	button	Highlight Changes...
ReviewEditComment	button	Edit Comment
TableDrawTable	toggleButton	Draw Table
TableEraser	toggleButton	Eraser
TableCellAlignTop	toggleButton	Align Top
TableCellAlignCenterVertically	toggleButton	Center Vertically
TableCellAlignBottom	toggleButton	Align Bottom
TableColumnsDistribute	button	Distribute Columns
TableRowsDistribute	button	Distribute Rows
ActiveXFrame	button	Frame
ActiveXImage	button	Image
WordArtEditTextClassic	button	Edit Text...
TableInsertCellsDialog	button	Insert Cells...

idMso	Control Type	Label
Organizer	button	Organizer
ShadowOnOrOffClassic	toggleButton	Shadow On/Off
ObjectSetShapeDefaults	button	Set AutoShape Defaults
ThesaurusClassic	button	Thesaurus...
MacroRecorderStop	button	Stop Recording
FileSendAsAttachment	button	E-mail
AutoSummaryViewByHighlight	toggleButton	Highlight/Show Only Summary
MasterDocument	button	Master Document
SystemInformation	button	Microsoft System Info
Overtyp	button	Overtyp
ExtendSelection	button	Extend Selection
Spike	button	Spike
SpikeInsert	button	Insert Spike
ChangeCase	button	Change Case
MoveText	button	Move Text
CopyText	button	Copy Text
AutoTextInsert	button	Insert AutoText
WindowOtherPane	button	Other Pane
WindowPrevious	button	Previous Window
FieldNext	button	Next Field
FieldPrevious	button	Previous Field
TableColumnSelectWord	button	Column Select
FieldCharactersInsert	button	Insert Field Chars
ListNumFieldInsert	button	Insert ListNum Field
FieldsUnlink	button	Unlink Fields
FieldsLock	button	Lock Fields
FieldsUnlock	button	Unlock Fields
UpdateSource	button	Update Source
HangingIndent	button	Hanging Indent

idMso	Control Type	Label
UnHang	button	Un Hang
HideText	button	Hidden
FontSpacingNormal	button	Normal Font Spacing
FontPositionNormal	button	Normal Font Position
ParagraphWidowOrphanControl	button	Para Widow Orphan Control
ParagraphKeepLinesTogether	button	Para Keep Lines Together
ParagraphKeepWithNext	toggleButton	Para Keep With Next
BreakParagraphPageBreakBefore	button	Para Page Break Before
ParagraphSpaceBeforeNone	button	No Space Before
ParagraphSpaceBefore	button	Space Before
ParagraphSpaceAddOrRemoveBefore	button	Add/Remove Space Before
ParagraphReset	button	Reset Para
PreviousEdit	button	Previous Edit
NextEdit	button	Next Edit
SaveTemplate	button	Save Template
PagePreviousWord	button	Previous Page
PageNextWord	button	Next Page
ObjectNext	button	Next Object
ObjectPrevious	button	Previous Object
FileConfirmConversions	button	File Confirm Conversions
MailMergeReceipientsUseExistingList	button	Use Existing List...
MailMergeOpenHeaderSource	button	Mail Merge Open Header Source
MailMergeQueryOptions	button	Query Options
MailMergeRuleIfThenElse	button	Mail Merge Insert If
MailMergeRuleMergeRecordNumber	button	Mail Merge Insert Merge Rec
MailMergeRuleMergeSequenceNumber	button	Mail Merge Insert Merge Seq
MailMergeRuleNextRecord	button	Mail Merge Insert Next

idMso	Control Type	Label
MailMergeRuleNextRecordIf	button	Mail Merge Insert Next If
MailMergeRuleSkipRecordIf	button	Mail Merge Insert Skip If
MailMergeRuleFillIn	button	Mail Merge Insert Fill In
MailMergeRuleAsk	button	Mail Merge Insert Ask
MailMergeRuleSetBookmark	button	Mail Merge Insert Set
MailMergeReset	button	Mail Merge Reset
MailMergeCreateDataSource	button	Mail Merge Create Data Source
MailMergeCreateHeaderSource	button	Mail Merge Create Header Source
GoToPreviousSection	button	Go To Previous Section
GoToNextSection	button	Go To Next Section
GoToPreviousPage	button	Go To Previous Page
GoToNextPage	button	Go To Next Page
FootnotePreviousWord	button	Previous Footnote
FootnoteNextWord	button	Next Footnote
EndnotePreviousWord	button	Previous Endnote
EndnoteNextWord	button	Next Endnote
ObjectActivate	button	Activate Object
TableAutoFormatUpdate	button	Table Update AutoFormat
DraftViewClassic	button	View Draft
NormalViewHeaderArea	button	Normal View Header Area
SectionBreakInsert	button	Insert Section Break
EndnoteInsertWord	button	Insert Endnote
FootnotesConvertAll	button	Edit Convert All Footnotes
EndnotesConvertAll	button	Edit Convert All Endnotes
SwapAllNotes	button	Edit Swap All Notes
InsertEnSpace	button	Insert En Space
InsertEmSpace	button	Insert Em Space
IndexMarkEntry	button	Mark Entry...

idMso	Control Type	Label
AutoMarkIndexEntries	button	Auto Mark Index Entries
CitationMark	button	Mark Citation...
TableOfAuthoritiesEditCategory	button	Edit TOA Category
IndexInsert	button	Insert Index...
TableOfContentsDialog	button	Insert Table of Contents...
TableOfContentsMarkEntry	button	Mark Entry
TableOfFiguresInsert	button	Insert Table of Figures...
TableOfAuthoritiesInsert	button	Insert Table of Authorities...
DrawingUnselect	button	Draw Unselect
DrawingSelectNext	button	Draw Select Next
DrawingSelectPrevious	button	Draw Select Previous
TextBoxLinkCreate	button	Create Link
TextBoxLinkBreak	button	Break Link
TextBoxNextLinked	button	Next Text Box
TextBoxPreviousLinked	button	Previous Text Box
FormatSectionLayout	button	Format Section Layout
StylesRedefineStyle	button	Redefine Style
Heading1Apply	button	Apply Heading 1
Heading2Apply	button	Apply Heading 2
Heading3Apply	button	Apply Heading 3
ListBulletApply	button	Apply List Bullet
TextBoxConvertToFrame	button	Convert Text Box To Frame
ListPromote	button	Promote List
ListDemote	button	Demote List
NextMisspeling	button	Next Misspelling
HyphenationManual	button	Manual
BulletsAndNumberingClassic	button	Tools Bullets Numbers
CompareAndCombine	button	Compare & Combine

idMso	Control Type	Label
Calculate	button	Tools Calculate
KeyboardCustomizationWord	button	Tools Customize Keyboard Shortcut
ListCommands	button	List Commands
PrintOptionsMenuWord	button	Options
SpellingRecheckDocument	button	Tools Spelling Recheck Document
ReviewChangeUserName	button	Change User Name...
AutoFormatOptions	button	Tools Options AutoFormat
AutoFormatAsYouType	button	Tools Options AutoFormat As You Type
MailMergeConvertChevrons	button	Mail Merge Convert Chevrons
MailMergeAskToConvertChevrons	button	Mail Merge Ask To Convert Chevrons
ControlRun	button	Control Run
ShrinkSelection	button	Shrink Selection
StyleNormal	button	Normal Style
TableCellNext	button	Next Cell
TableCellPrevious	button	Previous Cell
StartOfRow	button	Start Of Row
EndOfRow	button	End Of Row
StartOfColumn	button	Start Of Column
EndOfColumn	button	End Of Column
WindowMinimizeAll	button	Minimize All
WindowMaximizeAll	button	Maximize All
WindowRestoreAll	button	Restore All
FieldClick	button	Do Field Click
SelectCurrentFont	button	Select Cur Font
SelectCurrentAlignment	button	Select Cur Alignment
SelectCurrentSpacing	button	Select Cur Spacing
SelectCurrentIndent	button	Select Cur Indent

idMso	Control Type	Label
SelectCurrentTabs	button	Select Cur Tabs
SelectCurrentColor	button	Select Cur Color
FramesRemove	button	Remove Frames
MenuMode	button	Menu Mode
PageNumberFormat	button	Format Page Numbers...
Zoom200	button	View Zoom200
Zoom75	button	View Zoom75
AddressFontsFormat	button	Format Addr Fonts
ReturnAddressFormatFontDialog	button	Format Ret Addr Fonts
FileLocations	button	Tools Options File Locations
CreateDirectoryClassic	button	Tools Create Directory
TableOfContentsUpdateClassic	button	Update Table of Contents...
FootnoteSeparatorWord	button	View Footnote Separator
FootnoteContinuationSeparator	button	View Footnote Cont Separator
FootnoteContinuationNotice	button	View Footnote Cont Notice
EndnoteSeparator	button	View Endnote Separator
EndnoteContinuationSeparator	button	View Endnote Cont Separator
EndnoteContinuationNotice	button	View Endnote Cont Notice
AutoCaptionInsert	button	Insert Auto Caption
CaptionInsertWord	button	Insert Add Caption
InsertCaptionNumbering	button	Insert Caption Numbering
AutoCorrectReplaceText	button	Tools AutoCorrect Replace Text
AutoCorrectInitialCaps	button	Tools AutoCorrect Initial Caps
AutoCorrectSentenceCaps	button	Tools AutoCorrect Sentence Caps
AutoCorrectDays	button	Tools AutoCorrect Days
AutoCorrectSmartQuotes	button	Tools AutoCorrect Smart

idMso	Control Type	Label
		Quotes
AutoCorrectCapsLockOff	button	Tools AutoCorrect Caps Lock Off
AutoCorrectExceptions	button	Tools AutoCorrect Exceptions
WindowSizeAll	button	Size All
WindowMoveAll	button	Move All
ConnectToNetworkDrive	button	Connect
GoToAnnotationScope	button	Goto Annotation Scope
FontSubstitution	button	Font Substitution
ScreenRefresh	button	Screen Refresh
CharacterLeft	button	Char Left
CharacterRight	button	Char Right
WordLeft	button	Word Left
WordRight	button	Word Right
ExtendSelectionLeft	button	Sent Left
ExtendSelectionRight	button	Sent Right
ParagraphUp	button	Para Up
ParagraphDown	button	Para Down
LineUp	button	Line Up
LineDown	button	Line Down
CharacterLeftExtend	button	Char Left Extend
CharacterRightExtend	button	Char Right Extend
WordLeftExtend	button	Word Left Extend
WordRightExtend	button	Word Right Extend
ExtendSelectionLeftSentence	button	Sent Left Extend
ExtendSelectionRightSentence	button	Sent Right Extend
ParagraphUpExtend	button	Para Up Extend
ParagraphDownExtend	button	Para Down Extend
LineUpExtend	button	Line Up Extend
LineDownExtend	button	Line Down Extend

idMso	Control Type	Label
PageUpExtend	button	Page Up Extend
PageDownExtend	button	Page Down Extend
StartOfLineExtend	button	Start Of Line Extend
EndOfLineExtend	button	End Of Line Extend
StartOfWindowExtend	button	Start Of Window Extend
EndOfWindowExtend	button	End Of Window Extend
StartOfDocumentExtend	button	Start Of Doc Extend
EndOfDocumentExtend	button	End Of Doc Extend
SymbolFont	button	Symbol Font
GrammarSettingsDialog	button	Tools Gram Settings
FileNewDefault	button	New
FilePrintQuick	button	Quick Print
SpellingAndGrammar	button	Spelling & Grammar
ReviewPreviousChangeClassic	button	Previous Change
ReviewNextChangeClassic	button	Next Change
MessageProperties	button	Properties
PictureInsertFromFile	button	Picture...
TableDrawBorderPenWeight	dropDown	Pen Weight
TableShowGridlines	toggleButton	View Gridlines
ShapeStraightConnectorArrow	toggleButton	Straight Arrow Connector
ShapeElbowConnectorArrow	toggleButton	Elbow Arrow Connector
HyperlinkOpen	button	Open Hyperlink
TextWrappingTopAndBottom	toggleButton	Top and Bottom
TextWrappingThrough	toggleButton	Through
MacroRecordOrStop	button	Record Macro / Stop Recorder
AutoManager	button	AutoManager...
EndnoteOrFootnoteConvert	button	Convert Endnote/Footnote
FootnoteSeparatorReset	button	Reset
PasteAsHyperlink	button	Paste as Hyperlink

idMso	Control Type	Label
ProofingOptions	button	Options...
ParagraphDistributed	toggleButton	Distributed
HyphenationOptions	button	Hyphenation Options...
TableRowsOrColumnsDistribute	button	Distribute Rows/Columns
MergeOrSplitCells	button	Merge/Split Cells
ReviewJapaneseConsistencyChecker	button	Japanese Consistency Checker...
AutoSummaryResummarize	button	Resummarize
AutoSummaryUpdateProperties	button	Update Properties
DeleteWord	button	Delete Word
DeleteWordBack	button	Delete Back Word
CharacterFormattingReset	button	Reset Character Formatting
HeadingNumbers	button	Heading Numbers
PictureSetTransparentColor	toggleButton	Set Transparent Color
PageColorMoreColorsDialog	button	More Colors...
PageColorFillEffects	button	Fill Effects...
BorderTopWord	toggleButton	Top Border
BorderBottomWord	toggleButton	Bottom Border
BorderLeftWord	toggleButton	Left Border
BorderRightWord	toggleButton	Right Border
TextDirection	button	Text Direction
FieldsManage	button	Manage
FileSaveAsHtml	button	Save as HTML...
SortAscendingWord	button	Sort Ascending
SortDescendingWord	button	Sort Descending
FrameInsertHorizontal	button	Horizontal Frame
FieldCodesToggle	button	Toggle Field Codes
GoToFootnote	button	Go to Footnote
GoToEndnote	button	Go to Endnote

idMso	Control Type	Label
SpellingHideErrors	toggleButton	Hide Spelling Errors
GrammarHideErrors	toggleButton	Hide Grammar Errors
Dictionary	button	Dictionary
SummaryInformation	button	Summary Information...
FootnoteEndnoteOptions	button	Footnote/Endnote Options
UnderlineDotted	toggleButton	Dotted Underline
NumberingRemove	button	Remove Numbering
PictureEditClassic	button	Picture
GoToStartOfWindow	button	Start of Window
GoToEndOfWindow	button	End of Window
AutoCorrectHECorrect	button	HECorrect
FileSendToPowerPoint	button	Send to Microsoft Office PowerPoint
FormatObjectDialogClassic	button	AutoShape...
AutoFormatNow	button	AutoFormat...
DataFormWord	button	Data Form
BulletListDefault	button	Tools Bullet List Default
NumberListDefault	button	Tools Number List Default
OutlineNumberDefault	button	Format Outline Number Default
FormatNumberDefault	button	Format Number Default
TableOfContentsRebuild	button	Rebuild Table of Contents
FootnoteEndnoteDialog	button	Footnote and Endnote Dialog...
TableInsertDialogWord	button	Insert Table...
FormFieldClear	button	Clear Form Field
ObjectBringInFrontOfText	button	Bring in Front of Text
ObjectSendBehindText	button	Send Behind Text
PageBreakInsertWord	button	Page Break
BordersShadingDialogWord	button	Borders and Shading...
TextBoxWordClassic	button	Text Box

idMso	Control Type	Label
IndentIncreaseWord	button	Increase Indent
IndentDecreaseWord	button	Decrease Indent
SelectObjects	button	Select Objects
Callout	button	Callout
ReplaceWithAutoText	button	Replace with AutoText
LinkToPreviousClassic	button	Link to Previous
HangulHanjaConversion	button	Hangul Hanja Conversion...
HeaderSourceEdit	button	Edit Header Source
IndentIncrease	button	Increase Indent
IndentDecrease	button	Decrease Indent
AsianLayoutFitText	button	Fit Text...
AsianLayoutPhoneticGuide	button	Phonetic Guide...
AsianLayoutCombineCharacters	button	Combine Characters...
JapanesePostcardDialog	button	Japanese Postcard...
CharacterBorder	toggleButton	Character Border
CharacterShading	toggleButton	Character Shading
ViewWebLayoutView	toggleButton	Web Layout
PasteAlternative	button	Paste Table
PasteAsNestedTable	button	Paste as Nested Table
HyperlinkRemove	button	Remove Hyperlink
MacroSecurity	button	Macro Security
HorizontalLineInsert	button	Horizontal Line
WebPagePreview	button	Web Page Preview
RightToLeftRun	button	Rtl Run
LeftToRightRun	button	Ltr Run
BoldRun	button	Bold Run
ItalicRun	button	Italic Run
TableSelectCell	button	Select Cell
TableDelete	button	Delete Table

idMso	Control Type	Label
TableRowsInsertAboveWord	button	Insert Above
TableRowsInsertBelowWord	button	Insert Below
TableColumnsInsertLeft	button	Insert Left
TableColumnsInsertRight	button	Insert Right
TablePropertiesDialog	button	Properties...
TableOptionsDialog	button	Cell Margins...
TableCellOptions	button	Cell Options...
SendCopySendNow	button	Send Now
SendCopySelectNames	button	Select Names
SendCopyCheckNames	button	Check Names
SendCopyAddressBookTo	button	To: Focus
SendCopyAddressBookCc	button	CC: Focus
SendCopyAddressBookBcc	button	Bcc: Focus
SendCopyFocusSubject	button	Subject Focus
SendCopyOptions	button	Mail Options
SendCopyFlag	button	Mail Flag
SendCopySaveAttachment	button	Save Mail Attachments
FileCloseOrExit	button	Close or Exit
ImeReconvert	button	Reconvert
SendCopySendToMailRecipient	toggleButton	Mail Recipient
TableOfContentsInFrame	button	Table of Contents in Frame
SetLanguageMenu	comboBox	Language
TableWrapping	button	Table Wrapping
EmailOptions	button	E-mail Options...
ComAddInsDialog	button	COM Add-Ins...
SignaturesStationeryDialog	button	Signatures...
FramePropertiesDialog	button	Frame Properties...
OfficeOnTheWeb	button	Microsoft Office Online
PictureBulletsInsert	button	Picture Bullets...

idMso	Control Type	Label
FileNewWebPage	button	New Web Page
FileNewBlankDocument	button	New Blank Document
FileNewDialogClassic	button	New Document or Template...
FileSaveAsWebPage	button	Save as Web Page...
HorizontalLineInsertClassic	button	Horizontal Line...
WebOptionsDialog	button	Web Options...
FramesNewFramesPageWizard	button	New Frames Page
FrameCreateAbove	button	New Frame Above
FrameCreateBelow	button	New Frame Below
FrameCreateLeft	button	New Frame Left
FrameCreateRight	button	New Frame Right
FrameDelete	button	Delete Frame
EastAsianEditingMarks	toggleButton	Show/Hide Editing Marks
TableAutoFitContents	button	AutoFit Contents
TableAutoFitWindow	button	AutoFit Window
TableAutoFitFixedColumnWidth	button	Fixed Column Width
TableCellAlignTopLeft	toggleButton	Align Top Left
TableCellAlignTopCenter	toggleButton	Align Top Center
TableCellAlignTopRight	toggleButton	Align Top Right
TableCellAlignMiddleLeft	toggleButton	Align Center Left
TableCellAlignMiddleCenter	toggleButton	Align Center
TableCellAlignMiddleRight	toggleButton	Align Center Right
TableCellAlignBottomLeft	toggleButton	Align Bottom Left
TableCellAlignBottomCenter	toggleButton	Align Bottom Center
TableCellAlignBottomRight	toggleButton	Align Bottom Right
WebControlCheckBox	button	Checkbox
WebControlOptionButton	button	Option Button
WebControlDropDownBox	button	Drop-Down Box
WebControlListBox	button	List Box

idMso	Control Type	Label
WebControlTextBox	button	Textbox
WebControlTextArea	button	Text Area
WebControlSubmit	button	Submit
WebControlSubmitWithImage	button	Submit with Image
WebControlReset	button	Reset
WebControlHidden	button	Hidden
WebControlPassword	button	Password
UnderlineColorMoreColorsDialog	button	More Colors...
ChineseTranslationDialog	button	Translate with Options...
TableInsertMultidiagonalCell	button	Insert Multidiagonal Cell...
AsianLayoutHorizontalInVertical	button	Horizontal in Vertical...
AsianLayoutTwoLinesInOne	button	Two Lines in One...
AsianLayoutCharactersEnclose	button	Enclose Characters...
EnvelopeChineseDialog	button	Chinese Envelope...
ObjectsMultiSelect	button	Select Multiple Objects
TranslateToTraditionalChinese	button	Traditional
TextWrappingBehindText	toggleButton	Behind Text
TextWrappingInFrontOfText	toggleButton	In Front of Text
WatermarkCustomDialog	button	Custom Watermark...
FrameSaveCurrentAs	button	Save Current Frame As...
TranslateToSimplifiedChinese	button	Simplified
WebDesignMode	toggleButton	Web Design Mode
ViewMasterDocumentViewClassic	button	Master Document Tools
WhiteSpaceBetweenPagesShowHide	button	White Space Between Pages
EditField	button	Edit Field...
WordCountRecount	button	Recount
StylesModifyStyle	button	Modify Style
StyleByExample	button	Style by Example
CssLinksEdit	button	Edit CSS Links

idMso	Control Type	Label
StylesPane	button	Styles...
DeleteStyle	button	Delete Style
StylesRenameStyle	button	Rename Style
SelectNumber	button	Select Number
NumberingRestart	button	Restart Numbering
DrawingCanvasInsert	button	New Drawing Canvas
DiagramRadialInsertClassic	button	Radial Diagram
DiagramCycleInsertClassic	button	Cycle Diagram
DiagramPyramidInsertClassic	button	Pyramid Diagram
DiagramTargetInsertClassic	button	Target Diagram
DiagramVennDiagramInsertClassic	button	Venn Diagram
DiagramChangeToRadialClassic	button	Radial
DiagramChangeToCycleClassic	button	Cycle
DiagramChangeToTargetClassic	button	Target
DiagramChangeToVennDiagramClassic	button	Venn
CopyPasteSettings	button	Copy & paste settings...
PasteByAppendingTable	button	Paste by Appending Table
OrganizationChartInsertAssistant	button	Assistant
OrganizationChartInsertCoworker	button	Coworker
OrganizationChartInsertSubordinate	button	Subordinate
OrganizationChartDeleteNode	button	Delete
DrawingCanvasFit	button	Fit
DrawingCanvasResize	button	Resize
LabelOptions	button	Label Options...
SendCopySetup	button	Envelope Setup...
MailMergeMergeToEMail	button	Send E-mail Messages...
MailMergeMergeToFax	button	Merge to Fax
MailMergeCreateList	button	Type New List...
MailMergeEditList	button	Edit Mail Merge List

idMso	Control Type	Label
DrawingCanvasExpand	button	Expand
ActivateProduct	button	Activate Product...
TextWrappingInLineWithText	toggleButton	In Line with Text
ConsistencyCheck	button	Consistency Check...
SelectTextWithSimilarFormatting	button	Select Text with Similar Formatting
ReviewSendForReview	button	Send for Review...
WebComponent	button	Web Component...
DiagramChangeToPyramidClassic	button	Pyramid
DiagramShapeMoveBackwardClassic	button	Move Shape Backward
DiagramShapeMoveForwardClassic	button	Move Shape Forward
CharacterCodeToggle	button	Toggle Character Code
SmartTagOptions	button	Tools Options Smart Tag
SendCopyFocusIntroduction	button	Introduction Focus
StylesStyleVisibility	button	Style Visibility
DiagramStylesClassic	button	Diagram Styles...
MailMergeHighlightMergeFields	toggleButton	Highlight Merge Fields
MailMergeWizard	toggleButton	Step by Step Mail Merge Wizard...
OrganizationChartAutoLayout	toggleButton	AutoLayout
OrganizationChartSelectLevel	button	Level
OrganizationChartSelectBranch	button	Branch
OrganizationChartSelectAllAssistants	button	All Assistants
OrganizationChartSelectAllConnectors	button	All Connectors
MailMergeJapaneseGreetingInsert	button	Greeting...
MailMergeJapaneseGreetingJapaneseOpeningSentenceInsert	button	Opening...
MailMergeJapaneseGreetingClosingSentenceInsert	button	Closing...
RevealFormatting	button	Reveal Formatting...
DiagramReverseClassic	button	Reverse
DiagramAutoLayoutClassic	toggleButton	AutoLayout

idMso	Control Type	Label
TextBoxAutosize	button	Autosize textbox
TranslationPane	button	Translate...
GoToTableOfContents	button	Go to TOC
TableOfContentsUpdate	button	Update Table...
OutlineLevelGallery	dropDown	Outline Level
OutlineShowLevel	dropDown	Show Level:
NumberingContinue	button	Continue Numbering
FileCheckOut	button	Check Out
FileCheckIn	button	Check In
OrganizationChartLayoutStandard	toggleButton	Standard
OrganizationChartLayoutBothHanging	toggleButton	Both Hanging
OrganizationChartLayoutLeftHanging	toggleButton	Left Hanging
OrganizationChartLayoutRightHanging	toggleButton	Right Hanging
ReviewShowReviewersMenu	menu	Reviewers
ReviewReplyWithChanges	button	Reply with Changes...
ReviewEndReview	button	End Review...
NormalizeText	button	Normalize text
StylesStyleSeparator	button	Style Separator
SpeakLearnFromDocument	button	Learn from Document...
PictureEditWord	button	Edit Picture
OutlinePromoteToHeading	button	Promote to Heading 1
MicrosoftOutlook	button	Microsoft Outlook
ReviewShowComments	toggleButton	Comments
ReviewShowInsertionsAndDeletions	toggleButton	Insertions and Deletions
ReviewShowFormatting	toggleButton	Formatting
ReviewPreviousChange	button	Previous
ReviewNextChange	button	Next
ReviewReviewingPane	toggleButton	Reviewing Pane
ReviewAcceptAllChangesShown	button	Accept All Changes Shown

idMso	Control Type	Label
ReviewAcceptAllChangesInDocument	button	Accept All Changes in Document
ReviewRejectAllChangesShown	button	Reject All Changes Shown
ReviewRejectAllChangesInDocument	button	Reject All Changes in Document
ReviewDeleteAllCommentsShown	button	Delete All Comments Shown
ReviewDeleteAllCommentsInDocument	button	Delete All Comments in Document
ShowRepairs	button	Show Repairs
MailMergeMatchFields	button	Match Fields...
MailMergeAddressBlockInsert	button	Address Block...
MailMergeGreetingLineInsert	button	Greeting Line...
MailMergeMergeFieldInsert	button	Insert Merge Field
MailMergeRecipientsEditList	button	Edit Recipient List...
MailMergeEmailOptions	button	Mail Merge E-Mail Options
MailMergePrintOptions	button	Mail Merge Print Options
MailMergeFaxOptions	button	Mail Merge Fax Options
MailMergeMergeToNewDocumentOptions	button	Mail Merge to New Document Options
PicturesCompress	button	Compress Pictures...
Security	button	Security
TableAutoFormatStyle	button	Table AutoFormat...
MailMergeEditAddressBlock	button	Edit Address Block...
MailMergeEditGreetingLine	button	Edit Greeting Line...
MailMergeFindRecipient	button	Find Recipient...
FormFieldReset	button	Reset Form Fields
MailMergeUpdateLabels	button	Update Labels
DiagramFitToContentsClassic	button	Fit to Contents
DiagramResizeClassic	toggleButton	Resize
DiagramExpandClassic	button	Expand
OrganizationChartResize	button	Resize Organization Chart

idMso	Control Type	Label
AccountSettings	button	Account Settings...
MailMergeSetDocumentType	button	Main document setup
DiagramShapeInsertClassic	button	Insert Shape
OrganizationChartStyle	button	Style...
ReviewDisplayForReview	dropDown	Display for Review
DiagramAutoFormatClassic	button	Use AutoFormat
Translate	button	Translate...
ClearContentsWord	button	Contents
DrawingCanvasScale	button	Scale Drawing
ProtectDocument	toggleButton	Protect Document...
XmlViewStructure	button	View XML Structure
ReadingViewClose	button	Edit
ResearchPane	toggleButton	Research...
DocumentMapReadingView	button	Document Map
ReadingViewResearchPane	button	Research...
ReadingViewFontSizeIncrease	button	Increase Text Size
ReadingViewFontSizeDecrease	button	Decrease Text Size
ReadingViewShowPrintedPage	button	Show Printed Page
ViewRulerWord	checkBox	Ruler
FileInternetFax	button	Internet Fax
DocumentUpdatePane	button	Show Document Update Pane
ViewDocumentActionsPane	toggleButton	Document Actions
XmlToggleTagView	button	Toggle XML Tag View
InkDeleteAllInk	button	Delete All Ink
LookUp	button	Look Up
WindowSideBySide	toggleButton	View Side by Side
PrivacyOptionsDialog	button	Privacy Options...
FileVersionHistoryWord	button	View Version History
WindowSideBySideSynchronousScrolling	toggleButton	Synchronous Scrolling

idMso	Control Type	Label
WindowResetPosition	button	Reset Window Position
InkColorMoreColorsDialog	button	More Ink Colors...
XmlOptionsDialog	button	XML Options...
XmlTransformation	toggleButton	Transformation
StyleEnforcementSettings	button	Style Enforcement Settings
ContactUs	button	Contact Us...
FilePermissionUnrestricted	toggleButton	Unrestricted Access
FilePermissionDoNotDistribute	toggleButton	Restricted Access
FilePermissionView	button	View Permission
FilePermission	button	Permission
ReadingViewAllowMultiplePages	button	Allow Multiple Pages
ReadingViewStartInking	button	Ink
ReadingViewUnlockDocumentLayout	button	Unlock Document Layout
VoiceInsertInComment	button	Insert Voice
ViewThumbnails	checkBox	Thumbnails
Thesaurus	button	Thesaurus...
InkingStart	button	Start Inking
ReviewShowRevisionsInBalloons	toggleButton	Show Revisions in Balloons
ReviewShowRevisionsInline	toggleButton	Show All Revisions Inline
ReviewShowOnlyCommentsAndFormattingInBalloons	toggleButton	Show Only Comments and Formatting in Balloons
ReviewShowInkMarkup	toggleButton	Ink
CheckForUpdates	button	Check for Updates
ViewFullScreenReadingView	toggleButton	Full Screen Reading
InkCopyAsText	button	Copy Ink As Text
InkDrawingAndWriting	button	Ink Drawing and Writing
ReviewInkCommentPen	toggleButton	Pen
ReviewInkCommentEraser	toggleButton	Eraser
InkEraser	toggleButton	Eraser
SendCopyAttachmentOptions	button	Attachment Options

idMso	Control Type	Label
FilePermissionRestrictAs	button	Manage Credentials
ListSetNumberingValue	button	Set Numbering Value...
FileViewDigitalSignatures	toggleButton	View Signatures
FileWorkflowTasks	button	View Workflow Tasks
FileStartWorkflow	button	Workflows
SignatureLineInsert	button	Signature Line
BibliographyInsert	button	Insert Bibliography
BibliographyStyle	comboBox	Style:
CitationInsert	gallery	Insert Citation
BibliographyManageSources	button	Manage Sources...
BibliographyAddNewSource	button	Add New Source...
LabelInsert	button	Label
BarcodeInsert	button	Barcode
ReviewShowMarkupAreaHighlight	toggleButton	Markup Area Highlight
ChartStylesGallery	gallery	Quick Styles
ChartLayoutGallery	gallery	Quick Layout
ChartSaveTemplates	button	Save As Template
ChartAxisTitles	menu	Axis Titles
ChartAxes	menu	Axes
ChartGridlines	menu	Gridlines
ChartFormatSelection	button	Format Selection
ChartElementSelector	comboBox	Chart Elements
PageMarginsGallery	gallery	Margins
DropCapInsertGallery	gallery	Drop Cap
TabPictureToolsFormat	tab	Format
ShapesInsertGallery	gallery	Shapes
ShapeChangeShapeGallery	gallery	Change Shape
ShapeFillTextureGallery	gallery	Texture
ShapeStylesGallery	gallery	Quick Styles

idMso	Control Type	Label
PageOrientationGallery	gallery	Orientation
FileServerTasksMenu	menu	Server
FileSendMenu	menu	Send
TabInsert	tab	Insert
TabReferences	tab	References
TabMailings	tab	Mailings
TabReviewWord	tab	Review
TabView	tab	View
GroupFont	group	Font
GroupParagraph	group	Paragraph
GroupStyles	group	Styles
GroupProofing	group	Proofing
GroupInsertPages	group	Pages
GroupInsertIllustrations	group	Illustrations
GroupWordArtText	group	Text
GroupParagraphLayout	group	Paragraph
GroupCitationsAndBibliography	group	Citations & Bibliography
GroupFootnotes	group	Footnotes
GroupTableOfContents	group	Table of Contents
GroupMailMergeWriteInsertFields	group	Write & Insert Fields
GroupMailMergePreviewResults	group	Preview Results
GroupMailMergeFinish	group	Finish
GroupChangesTracking	group	Tracking
GroupComments	group	Comments
GroupChanges	group	Changes
GroupCompare	group	Compare
GroupPictureSize	group	Size
GroupTableAlignment	group	Alignment
GroupTextBoxText	group	Text

idMso	Control Type	Label
GroupArrange	group	Arrange
GroupShapeStyles	group	Shape Styles
GroupChartLayouts	group	Chart Layouts
GroupChartStyles	group	Chart Styles
GroupChartAxes	group	Axes
GroupChartShapes	group	Insert
GroupOrganizationChartShapeInsert	group	Insert
StylesManageStyles	button	Manage Styles
StylesStyleInspector	toggleButton	Style Inspector
ObjectEffectPresetGallery	gallery	Preset
PictureEffectsPresetGallery	gallery	Preset
_3DRotationGallery	gallery	3-D Rotation
TabSmartArtToolsDesign	tab	Design
TabSmartArtToolsFormat	tab	Format
TabChartToolsDesign	tab	Design
TabChartToolsLayout	tab	Layout
TabChartToolsFormat	tab	Format
ShapeFillColorPicker	gallery	Shape Fill
OutlineColorPicker	gallery	Picture Border
FileDocumentInspect	button	Inspect Document
QuickStylesGallery	gallery	Quick Styles
QuickStylesSets	gallery	Style Set
ClearFormatting	button	Clear Formatting
PanningHand	toggleButton	Panning Hand
BulletsGalleryWord	gallery	Bullets
NumberingGalleryWord	gallery	Numbering
GroupControls	group	Controls
GroupZoom	group	Zoom
ArrowStyleGallery	gallery	Arrows

idMso	Control Type	Label
OutlineDashesGallery	gallery	Dashes
OutlineWeightGallery	gallery	Weight
TabTableToolsLayout	tab	Layout
GroupPictureTools	group	Adjust
GroupSize	group	Size
ReviewTrackChangesMenu	splitButton	Track Changes
ReviewAcceptChangeMenu	splitButton	Accept
ReviewRejectChangeMenu	splitButton	Reject
ReviewBalloonsMenu	menu	Balloons
GroupTableRowsAndColumns	group	Rows & Columns
GroupTableData	group	Data
ObjectAlignMenu	menu	Align
ObjectRotateGallery	gallery	Rotate
SelectMenu	menu	Select
FontColorPicker	gallery	Font Color
TableColumnsGallery	gallery	Columns
TabHome	tab	Home
ChartTitle	gallery	Chart Title
ChartPrimaryHorizontalAxisTitle	gallery	Primary Horizontal Axis Title
ChartPrimaryVerticalAxisTitle	gallery	Primary Vertical Axis Title
ChartDepthAxisTitle	gallery	Depth Axis Title
ChartLegend	gallery	Legend
ChartDataLabel	gallery	Data Labels
ChartPrimaryHorizontalGridlines	gallery	Primary Horizontal Gridlines
ChartPrimaryVerticalGridlines	gallery	Primary Vertical Gridlines
ChartDepthGridlines	gallery	Depth Gridlines
ChartPrimaryHorizontalAxis	gallery	Primary Horizontal Axis
ChartPrimaryVerticalAxis	gallery	Primary Vertical Axis

idMso	Control Type	Label
ChartDepthAxis	gallery	Depth Axis
ChartDataTable	gallery	Data Table
ChartTrendline	gallery	Trendline
ChartErrorBars	gallery	Error Bars
ChartLines	gallery	Lines
ChartUpDownBars	gallery	Up/Down Bars
ChartPlotArea	gallery	Plot Area
ChartWall	gallery	Chart Wall
ChartFloor	gallery	Chart Floor
TabPageLayoutWord	tab	Page Layout
SmartArtAddShape	button	Add Shape
SmartArtLargerShape	button	Larger
SmartArtSmallerShape	button	Smaller
SmartArtResetGraphic	button	Reset Graphic
SmartArtTextPane	toggleButton	Text Pane
SmartArtEditIn2D	toggleButton	Edit in 2-D
SmartArtLayoutGallery	gallery	Change Layout
SmartArtMoreLayoutsDialog	button	More Layouts...
SmartArtStylesGallery	gallery	Quick Styles
SmartArtChangeColorsGallery	gallery	Change Colors
ObjectEffectSoftEdgesGallery	gallery	Soft Edges
ObjectEffectGlowGallery	gallery	Glow
GradientGallery	gallery	Gradient
ObjectEffectShadowGallery	gallery	Shadow
TextEffectTransformGallery	gallery	Transform
TabHeaderAndFooterToolsDesign	tab	Design
GroupHeaderFooterOptions	group	Options
ReviewPreviousCommentWord	button	Previous
ReviewNextCommentWord	button	Next

idMso	Control Type	Label
BulletDefineNew	button	Define New Bullet...
DefineNewNumberFormat	button	Define New Number Format...
ThemeColorsGallery	gallery	Colors
HeaderInsertGallery	gallery	Header
FooterInsertGallery	gallery	Footer
CoverPageInsertGallery	gallery	Cover Page
PageNumberFieldInsertGallery	gallery	Current Position
WatermarkGallery	gallery	Watermark
EquationInsertGallery	gallery	Equation
QuickTablesInsertGallery	gallery	Quick Tables
QuickPartsInsertGallery	gallery	Quick Parts
GroupSmartArtLayouts	group	Layouts
GroupSmartArtQuickStyles	group	SmartArt Styles
GroupSmartArtCreateGraphic	group	Create Graphic
GroupSmartArtReset	group	Reset
GroupSmartArtSize	group	Size
SaveSelectionToQuickPartGallery	button	Save Selection to Quick Part Gallery...
SaveSelectionToCoverPageGallery	button	Save Selection to Cover Page Gallery...
SaveSelectionToEquationGallery	button	Save Selection to Equation Gallery...
SaveSelectionToFooterGallery	button	Save Selection to Footer Gallery...
SaveSelectionToHeaderGallery	button	Save Selection to Header Gallery...
SaveSelectionToPageNumberGallery	button	Save Selection to Page Number Gallery...
SaveSelectionToQuickTablesGallery	button	Save Selection to Quick Tables Gallery...
SaveSelectionToWaterMarkGallery	button	Save Selection to Watermark Gallery...
ThemeSearchOfficeOnline	button	More Themes on Microsoft

idMso	Control Type	Label
		Office Online...
TabAddIns	tab	Add-Ins
ReviewShowMarkupMenu	menu	Show Markup
ObjectEditShapeMenu	menu	Edit Shape
SymbolInsertGallery	gallery	Symbol
TableStyleClear	button	Clear
FileSaveAsPdfOrXps	button	Publish as PDF or XPS
FileSaveAsWordOpenDocumentText	button	OpenDocument Text
SearchLibraries	button	Search Libraries...
MoreControlsDialog	button	More Controls...
GroupCode	group	Code
TabDeveloper	tab	Developer
GroupXml	group	XML
XmlStructure	toggleButton	Structure
XmlSchema	button	Schema
XmlExpansionPacksWord	button	Expansion Packs
GroupCaptions	group	Captions
GroupIndex	group	Index
GroupTableOfAuthorities	group	Table of Authorities
GroupEditing	group	Editing
SelectMenuExcel	splitButton	Find & Select
GroupClipboard	group	Clipboard
GroupInsertTables	group	Tables
GroupInsertLinks	group	Links
GroupInsertSymbols	group	Symbols
GroupInsertBarcode	group	Barcode
PageSizeGallery	gallery	Size
ObjectPictureFill	button	Picture...
TextWrappingMenu	menu	Text Wrapping
WindowSwitchWindowsMenuWord	menu	Switch Windows

idMso	Control Type	Label
ThemeColorsCreateNew	button	Create New Theme Colors...
ThemeFontsCreateNew	button	Create New Theme Fonts...
ShapeFillMoreGradientsDialog	button	More Gradients...
ShadowOptionsDialog	button	Shadow Options...
BuildingBlocksOrganizer	button	Building Blocks Organizer...
ReviewCompareMenu	menu	Compare
ReviewCompareTwoVersions	button	Compare...
ReviewCombineRevisions	button	Combine...
ReviewCompareMajorVersion	button	Major Version
ReviewCompareLastVersion	button	Last Version
ReviewCompareSpecificVersion	button	Specific Version...
PropertyInsert	gallery	Document Property
ObjectsAlignSelectedSmart	toggleButton	Align Selected Objects
ObjectsAlignRelativeToContainerSmart	toggleButton	Align to Slide
ObjectsAlignLeftSmart	button	Align Left
ObjectsAlignRightSmart	button	Align Right
ObjectsAlignTopSmart	button	Align Top
ObjectsAlignBottomSmart	button	Align Bottom
ObjectsAlignCenterHorizontalSmart	button	Align Center
ObjectsAlignMiddleVerticalSmart	button	Align Middle
AlignDistributeHorizontally	button	Distribute Horizontally
AlignDistributeVertically	button	Distribute Vertically
GroupProtect	group	Protect
IndexUpdate	button	Update Index
MarginsCustomMargins	button	Custom Margins...
MailMergeFinishAndMergeMenu	menu	Finish & Merge
HyphenationMenu	menu	Hyphenation
HyphenationAutomatic	toggleButton	Automatic

idMso	Control Type	Label
HyphenationNone	toggleButton	None
MailMergeRules	menu	Rules
TabWordArtToolsFormat	tab	Format
MailMergeStartMailMergeMenu	menu	Start Mail Merge
MailMergeStartLetters	toggleButton	Letters
MailMergeStartEmail	toggleButton	E-Mail Messages
MailMergeStartEnvelopes	toggleButton	Envelopes...
MailMergeStartLabels	toggleButton	Labels...
MailMergeStartDirectory	toggleButton	Directory
MailMergeClearMergeType	toggleButton	Normal Word Document
MailMergeSelectRecipients	menu	Select Recipients
TableOfContentsAddTextGallery	gallery	Add Text
BorderColorPicker	gallery	Pen Color
TranslationToolTip	gallery	Translation ScreenTip
ThemeFontsGallery	gallery	Fonts
ThemeEffectsGallery	gallery	Effects
FileProperties	toggleButton	Properties
TabPrintPreview	tab	Print Preview
GroupPrintPreviewPrint	group	Print
GroupPrintPreviewPreview	group	Preview
BreaksGallery	gallery	Breaks
LineNumbersMenu	menu	Line Numbers
LineNumbersOff	toggleButton	None
LineNumbersContinuous	toggleButton	Continuous
LineNumbersResetPage	toggleButton	Restart Each Page
LineNumbersResetSection	toggleButton	Restart Each Section
LineNumbersSuppress	toggleButton	Suppress for Current Paragraph
TabOutlining	tab	Outlining
GroupOutliningClose	group	Close

idMso	Control Type	Label
GroupOutliningTools	group	Outline Tools
GroupMasterDocument	group	Master Document
TableSelectMenu	menu	Select
TableDeleteRowsAndColumnsMenuWord	menu	Delete
GroupTableMerge	group	Merge
TableAutoFitMenu	menu	AutoFit
GroupTableDrawBorders	group	Draw Borders
TableBordersMenu	splitButton	Borders
FileCreateDocumentWorkspace	toggleButton	Create Document Workspace
FileSaveToDocumentManagementServer	button	Document Management Server
FileDocumentManagementInformation	toggleButton	Document Management Information
QuickAccessToolbarCustomization	button	Customize Quick Access Toolbar...
FilePrepareMenu	menu	Prepare
FileMarkAsFinal	toggleButton	Mark as Final
FileAddDigitalSignature	button	Add a Digital Signature
SignatureServicesAdd	button	Add Signature Services...
QuickStylesSaveSelectionAsNew	button	Save Selection as a New Quick Style...
StylesPaneNewStyle	button	New Style...
QuickStylesSaveQuickStyleSet	button	Save as Quick Style Set...
ChangeCaseGallery	gallery	Change Case
AlignJustifyMenu	menu	Justify
ControlProperties	button	Properties
GroupHeaderFooterInsert	group	Insert
GroupHeaderFooterNavigation	group	Navigation
GroupHeaderFooterPosition	group	Position
HeaderFooterDifferentFirstPageWord	checkBox	Different First Page
HeaderFooterDifferentOddEvenPageWord	checkBox	Different Odd & Even

idMso	Control Type	Label
		Pages
HeaderFooterShowDocumentText	checkBox	Show Document Text
BlankPageInsert	button	Blank Page
ShadowStyleGalleryClassic	gallery	Shadow Effects
TabOrganizationChartToolsFormat	tab	Format
TabDiagramToolsFormatClassic	tab	Format
GroupInkSelect	group	Select
WordArtSpacingMenu	menu	Spacing
TextAlignMenu	menu	Alignment
DiagramChangeToMenuClassic	menu	Change To
PictureBrightnessGallery	gallery	Brightness
PictureContrastGallery	gallery	Contrast
PicturePositionGallery	gallery	Position
TabPictureToolsFormatClassic	tab	Format
PictureBrightnessAndContrastDialog	button	Picture Correction Options...
GroupMailMergeStart	group	Start Mail Merge
OleObjectInsertMenu	splitButton	Object
ShadingColorPicker	gallery	Shading
ShadingColorsMoreColorsDialog	button	More Colors...
SmartArtAddShapeAfter	button	Add Shape After
SmartArtAddShapeBefore	button	Add Shape Before
SmartArtAddShapeAbove	button	Add Shape Above
SmartArtAddShapeBelow	button	Add Shape Below
SmartArtAddAssistant	button	Add Assistant
ChartSwitchRowColumn	button	Switch Row/Column
ChartShowData	button	Edit Data...
ChartRefresh	button	Refresh Data
ChartChangeType	button	Change Chart Type...
GroupChartData	group	Data

idMso	Control Type	Label
GroupChartType	group	Type
_3DRotationOptionsDialog	button	3-D Rotation Options...
_3DBevelOptionsDialog	button	3-D Options...
SmartArtOrganizationChartLeftHanging	button	Left Hanging
SmartArtOrganizationChartRightHanging	button	Right Hanging
SmartArtOrganizationChartBoth	button	Both
SmartArtOrganizationChartStandard	button	Standard
SmartArtRightToLeft	toggleButton	Right to Left
ListLevelGallery	gallery	Change List Level
MultilevelListGallery	gallery	Multilevel List
ListDefineNew	button	Define New Multilevel List...
ListDefineNewStyle	button	Define New List Style...
ViewMessageBar	checkBox	Message Bar
ApplyStylesPane	toggleButton	Apply Styles...
InsertAlignmentTab	button	Insert Alignment Tab
ShapeStylesOtherThemeFillsGallery	gallery	Other Theme Fills
SmartArtOrganizationChartMenu	menu	Layout
ReviewChangeTrackingOptions	button	Change Tracking Options...
SymbolsDialog	button	More Symbols...
ReviewReviewingPaneHorizontal	toggleButton	Reviewing Pane Horizontal...
ReviewReviewingPaneVertical	toggleButton	Reviewing Pane Vertical...
_3DEffectsGalleryClassic	gallery	3-D Effects
_3DDirectionGalleryClassic	gallery	Direction
_3DLightingGalleryClassic	gallery	Lighting
TabDrawingToolsFormatClassic	tab	Format
GroupShadowEffects	group	Shadow Effects
Group3DEffects	group	3-D Effects
WordArtStylesGalleryClassic	gallery	WordArt

idMso	Control Type	Label
WordArtInsertGalleryClassic	gallery	WordArt
TableInsertGallery	gallery	Table
ShapeStylesGalleryClassic	gallery	Shape Styles
WordArtChangeShapeGallery	gallery	Change Shape
ShadowColorPickerClassic	gallery	Shadow Color
_3DEffectColorPickerClassic	gallery	3-D Color
ShapeFillGradientGalleryClassic	gallery	Gradient
AsianLayoutMenu	menu	Asian Layout
JapaneseGreetingsInsertMenu	menu	Japanese Greetings
AlignJustifyWithMixedLanguages	toggleButton	Justify
AlignJustifyLow	toggleButton	Justify Low
AlignJustifyMedium	toggleButton	Justify Medium
AlignJustifyHigh	toggleButton	Justify High
AlignJustifyThai	toggleButton	Distribute
TextHighlightColorPicker	gallery	Text Highlight Color
PageColorPicker	gallery	Page Color
GoToHeader	button	Go to Header
GoToFooter	button	Go to Footer
HighlightingStop	button	Stop Highlighting
UnderlineGallery	gallery	Underline
UnderlineColorPicker	gallery	Underline Color
UnderlineMoreUnderlinesDialog	button	More Underlines...
TextDirectionGalleryWord	gallery	Text Direction
GroupAddInsMenuCommands	group	Menu Commands
GroupAddInsToolbarCommands	group	Toolbar Commands
GroupInk	group	Ink
TabInkToolsPens	tab	Pens
GroupInkPens	group	Pens
GroupInkClose	group	Close

idMso	Control Type	Label
InkBallpointPen	toggleButton	Ballpoint Pen
InkFeltTipPen	toggleButton	Felt Tip Pen
InkHighlighter	toggleButton	Highlighter
GroupBorder	group	Border
PictureRecolorGalleryWord	gallery	Recolor
_3DSurfaceMaterialGalleryClassic	gallery	Surface
_3DExtrusionDepthGalleryClassic	gallery	Depth
GroupHeaderFooter	group	Header & Footer
GroupPageLayoutSetup	group	Page Setup
GroupPageBackground	group	Page Background
ThemeSaveCurrent	button	Save Current Theme...
ThemesGallery	gallery	Themes
ChartResetToMatchStyle	button	Reset to Match Style
Chart3DView	button	3-D Rotation...
ObjectSizeDialog	button	Size...
AutoTextGallery	gallery	AutoText
TextBoxInsertGallery	gallery	Text Box
PageNumbersInHeaderInsertGallery	gallery	Top of Page
PageNumbersInFooterInsertGallery	gallery	Bottom of Page
PageNumbersInMarginsInsertGallery	gallery	Page Margins
SaveSelectionToAutoTextGallery	button	Save Selection to AutoText Gallery
SaveSelectionToTextBoxGallery	button	Save Selection to Text Box Gallery
SaveSelectionToPageNumberTop	button	Save Selection as Page Number (Top)
SaveSelectionToPageNumberBottom	button	Save Selection as Page Number (Bottom)
SaveSelectionToPageNumberMargin	button	Save Selection as Page Number (Margin)
HeaderFooterEditHeader	button	Edit Header
TableStyleHeaderRowWord	checkBox	Header Row

idMso	Control Type	Label
TableStyleTotalRowWord	checkBox	Total Row
TableStylesFirstColumnWord	checkBox	First Column
TableStyleLastColumnWord	checkBox	Last Column
TableStyleBandedRowsWord	checkBox	Banded Rows
TableStyleBandedColumnsWord	checkBox	Banded Columns
TableStyleModify	button	Modify Table Style...
TabTableToolsDesign	tab	Design
TableStylesGalleryWord	gallery	Table Styles
ReviewViewChangesInTheSourceDocument	button	View changes in the source document
GroupThemesWord	group	Themes
LayoutOptionsDialog	button	More Layout Options...
DrawingObjectFormatDialog	button	Advanced Tools...
ReflectionGallery	gallery	Reflection
PictureRecolorGallery	gallery	Recolor
SmartArtPromote	button	Promote
SmartArtDemote	button	Demote
ChartTitleOptionsDialog	button	More Title Options...
ChartLegendOptionsDialogDialog	button	More Legend Options...
ChartDataLabelDialog	button	More Data Label Options...
ChartPrimaryHorizontalAxisTitleOptionsDialog	button	More Primary Horizontal Axis Title Options...
ChartPrimaryVerticalAxisTitleOptionsDialog	button	More Primary Vertical Axis Title Options...
ChartSecondaryHorizontalAxisTitleOptionsDialog	button	More Secondary Horizontal Axis Title Options...
ChartSecondaryVerticalAxisTitleOptionsDialog	button	More Secondary Vertical Axis Title Options...
ChartDepthAxisTitleOptionsDialog	button	More Depth Axis Title Options...
ChartPrimaryHorizontalGridlinesOptionsDialog	button	More Primary Horizontal Gridlines Options...
ChartPrimaryVerticalGridlinesOptionsDialog	button	More Primary Vertical

idMso	Control Type	Label
		Gridlines Options...
ChartSecondaryHorizontalGridlinesOptionsDialog	button	More Secondary Horizontal Gridlines Options...
ChartSecondaryVerticalGridlinesOptionsDialog	button	More Secondary Vertical Gridlines Options...
ChartDepthGridlinesOptionsDialog	button	More Depth Gridlines Options...
ChartPrimaryHorizontalAxisOptionsDialog	button	More Primary Horizontal Axis Options...
ChartPrimaryVerticalAxisOptionsDialog	button	More Primary Vertical Axis Options...
ChartSecondaryHorizontalAxisOption	button	More Secondary Horizontal Axis Options...
ChartSecondaryVerticalAxisOptionsDialog	button	More Secondary Vertical Axis Options...
ChartDepthAxisOptionsDialog	button	More Depth Axis Options...
ChartDataTableOptionsDialog	button	More Data Table Options...
ChartTrendlineOptionsDialog	button	More Trendline Options...
ChartErrorBarsOptionsDialog	button	More Error Bars Options...
ChartUpDownBarsOptionsDialog	button	More Up/Down Bars Options...
ChartPlotAreaOptionsDialog	button	More Plot Area Options...
ChartWallOptionsDialog	button	More Walls Options...
ChartFloorOptionsDialog	button	More Floor Options...
ChartSecondaryHorizontalAxisTitle	gallery	Secondary Horizontal Axis Title
ChartSecondaryVerticalAxisTitle	gallery	Secondary Vertical Axis Title
ChartSecondaryHorizontalGridlines	gallery	Secondary Horizontal Gridlines
ChartSecondaryVerticalGridlines	gallery	Secondary Vertical Gridlines
ChartSecondaryHorizontalAxis	gallery	Secondary Horizontal Axis
ChartSecondaryVerticalAxis	gallery	Secondary Vertical Axis
GroupAddInsCustomToolbars	group	Custom Toolbars
ReviewDeleteCommentsMenu	splitButton	Delete

idMso	Control Type	Label
ObjectBringToFrontMenu	splitButton	Bring to Front
ObjectSendToBackMenu	splitButton	Send to Back
ObjectsGroupMenu	menu	Group
SignatureLineInsertMenu	splitButton	Signature Line
FileSaveAsWord97_2003	button	Word 97-2003 Document
EnglishWritingAssistant	button	English Assistant
TableOfContentsGallery	gallery	Table of Contents
SaveSelectionToTableOfContentsGallery	button	Save Selection to Table of Contents Gallery...
ObjectsAlignRelativeToMargin	toggleButton	Align to Margin
TabTextBoxToolsFormat	tab	Format
TextBoxStyleGallery	gallery	Text Box Style
TextBoxPositionGallery	gallery	Position
FileSaveAsMenu	splitButton	Save As Other Format
FilePrintMenu	splitButton	Preview and Print
FilePermissionRestrictMenu	menu	Restrict Permission
GroupEnvelopeLabelCreate	group	Create
ReviewInkCommentNew	button	Ink Comment
DocumentPanelTemplate	button	Document Panel
ObjectSizeDialogClassic	button	Size...
TextBoxInsertVerticalWord	button	Draw Vertical Text Box
BevelShapeGallery	gallery	Bevel
_3DBevelPictureTopGallery	gallery	Bevel
BibliographyAddNewPlaceholder	button	Add New Placeholder...
GroupTable	group	Table
GroupTableCellSize	group	Cell Size
GlowColorPicker	gallery	More Glow Colors
RecolorColorPicker	gallery	More Variations
GlowColorMoreColorsDialog	button	More Colors...
PictureRecolorMoreColorsDialog	button	More Colors...

idMso	Control Type	Label
QuickStylesResetDocumentStyles	button	Reset Document Quick Styles
QuickStylesResetFromTemplate	button	Reset to Quick Styles from Template
WatermarkRemove	button	Remove Watermark
CoverPageRemove	button	Remove Current Cover Page
HeaderFooterRemoveHeaderWord	button	Remove Header
HeaderFooterRemoveFooterWord	button	Remove Footer
PageNumbersRemove	button	Remove Page Numbers
TableOfContentsRemove	button	Remove Table of Contents
SmartArtAddBullet	button	Add Bullet
ThemeResetFromTemplate	button	Reset to Theme from Template
PictureChange	button	Change Picture...
GroupWordArtStyles	group	WordArt Styles
TextFillColorPicker	gallery	Text Fill
TextOutlineColorPicker	gallery	Text Outline
TextOutlineColorMoreColorsDialog	button	More Outline Colors...
TextEffectsMenu	menu	Text Effects
TextStylesGallery	gallery	Quick Styles
WordArtClear	button	Clear WordArt
TextPictureFill	button	Picture...
TextFillGradientGallery	gallery	Gradient
TextFillMoreGradientsDialog	button	More Gradients...
TextFillTextureGallery	gallery	Texture
TextOutlineDashesGallery	gallery	Dashes
TextOutlineMoreLinesDialog	button	More Lines...
TextOutlineWeightGallery	gallery	Weight
TextEffectShadowGallery	gallery	Shadow
TextEffectsMoreShadowsDialog	button	Shadow Options...

idMso	Control Type	Label
TextEffectsBevelMore3DOptionsDialog	button	3-D Options...
TextEffects3DRotationGallery	gallery	3-D Rotation
TextEffects3DRotationOptionsDialog	button	3-D Rotation Options...
TextEffectGlowGallery	gallery	Glow
TextGlowColorPicker	gallery	More Glow Colors
TextGlowColorMoreColorsDialog	button	More Colors...
TextReflectionGallery	gallery	Reflection
ShapeEffectsMenu	menu	Shape Effects
UpgradeDocument	button	Convert
GroupHeaderFooterClose	group	Close
GroupChartCurrentSelection	group	Current Selection
GroupChartLabels	group	Labels
PageSizeMorePaperSizesDialog	button	More Paper Sizes...
LineNumbersOptionsDialog	button	Line Numbering Options...
TableOfAuthoritiesUpdate	button	Update Table
TableOfFiguresUpdate	button	Update Table
ContentControlsGroup	button	Group
BevelTextGallery	gallery	Bevel
PictureCorrectionsDialog	button	Picture Corrections Options...
GroupTextBoxStyles	group	Text Box Styles
GroupTableStylesWord	group	Table Styles
GroupWordArtStylesClassic	group	WordArt Styles
PageBorderAndShadingDialog	button	Page Borders...
OutlineViewClose	button	Close Outline View
SmartArtAddShapeSplitMenu	splitButton	Add Shape Options
ContentControlRichText	button	Rich Text
ContentControlText	button	Text
ContentControlPicture	button	Picture
ContentControlComboBox	button	Combo Box

idMso	Control Type	Label
ContentControlDropDownList	button	Drop-Down List
ContentControlBuildingBlockGallery	button	Building Block Gallery
ContentControlDate	button	Date
AutoSummaryToolsMenu	menu	AutoSummary Tools
GroupInkFormat	group	Format
InkColorPicker	gallery	Color
GroupDiagramLayoutClassic	group	Layout
GroupDiagramStylesClassic	group	Styles
GroupOrganizationChartLayoutClassic	group	Layout
GroupOrganizationChartStyleClassic	group	Styles
TextBoxDrawMenu	menu	Draw Text Box
TextBoxInsertWord	button	Text Box
GroupOrganizationChartSelect	group	Select
ShapeFillEffectMoreGradientsDialogClassic	button	More Gradients...
ShapeFillEffectMoreTexturesDialogClassic	button	More Textures...
ShapeFillEffectPatternClassic	button	Pattern...
BibliographyGallery	gallery	Bibliography
CustomHeaderGallery	gallery	Custom Header
CustomFooterGallery	gallery	Custom Footer
CustomCoverPageGallery	gallery	Custom Cover Page
CustomPageNumberGallery	gallery	Custom Page Number
CustomPageNumberTopGallery	gallery	Custom Top of Page
CustomPageNumberBottomGallery	gallery	Custom Bottom of Page
CustomPageMargins	gallery	Custom Page Margins
CustomWatermarkGallery	gallery	Custom Watermark
CustomEquationsGallery	gallery	Custom Equation
CustomTablesGallery	gallery	Custom Tables
CustomQuickPartsGallery	gallery	Custom Quick Parts
CustomAutoTextGallery	gallery	Custom AutoText

idMso	Control Type	Label
CustomTextBoxGallery	gallery	Custom Text Box
CustomTableOfContentsGallery	gallery	Custom Table of Contents
CustomBibliographyGallery	gallery	Custom Bibliography
CustomGallery1	gallery	Custom Gallery 1
CustomGallery2	gallery	Custom Gallery 2
CustomGallery3	gallery	Custom Gallery 3
CustomGallery4	gallery	Custom Gallery 4
CustomGallery5	gallery	Custom Gallery 5
SaveSelectionToBibliographyGallery	button	Save Selection to Bibliography Gallery...
MailMergeReceipientsUseOutlookContacts	button	Select from Outlook Contacts...
FootnoteNext	splitButton	Next Footnote
ReviewReviewingPaneMenu	splitButton	Reviewing Pane
GroupSizeClassic	group	Size
GroupPictureSizeClassic	group	Size
GroupPictureToolsClassic	group	Adjust
GalleryAllShapesAndCanvas	gallery	Shapes
GroupShapesClassic	group	Insert Shapes
GroupSmartArtShapes	group	Shapes
GroupShapeStylesClassic	group	Shape Styles
GroupInsertText	group	Text
Drawing1ColorPickerFill	gallery	Shape Fill
ShapeOutlineColorPicker	gallery	Picture Border
Drawing1ColorPickerLineStyle	gallery	Picture Border
Drawing1GalleryTextures	gallery	Texture
InsertBuildingBlocksEquationsGallery	gallery	Equation
Drawing1GalleryBrightness	gallery	Brightness
Drawing1GalleryContrast	gallery	Contrast
GroupDiagramArrangeClassic	group	Arrange

idMso	Control Type	Label
GroupTextBoxArrange	group	Arrange
ContentControlsGroupMenu	menu	Group
ContentControlsUngroup	button	Ungroup
ControlsGalleryClassic	gallery	Legacy Tools
ReviewShowSourceDocumentsMenu	gallery	Show Source Documents
HeaderFooterEditFooter	button	Edit Footer
QuickStylesSetAsDefault	button	Set as Default
EquationInsertNew	button	Insert New Equation
EquationProfessional	button	Professional
EquationLinearFormat	button	Linear
EquationNormalText	toggleButton	Normal Text
EquationSymbolsInsertGallery	gallery	Equation Symbols
EquationIntegralGallery	gallery	Integral
EquationFractionGallery	gallery	Fraction
EquationRadicalGallery	gallery	Radical
EquationLargeOperatorGallery	gallery	Large Operator
EquationDelimiterGallery	gallery	Bracket
EquationScriptGallery	gallery	Script
EquationFunctionGallery	gallery	Function
EquationAccentGallery	gallery	Accent
EquationLimitGallery	gallery	Limit and Log
EquationOperatorGallery	gallery	Operator
EquationMatrixGallery	gallery	Matrix
EquationOptions	button	Equation Options...
TabEquationToolsDesign	tab	Design
GroupEquationTools	group	Tools
GroupEquationSymbols	group	Symbols
GroupEquationStructures	group	Structures
MailMergeMergeFieldInsertMenu	splitButton	Insert Merge Field

idMso	Control Type	Label
PasteMenu	splitButton	Paste
GroupPictureStyles	group	Picture Styles
PictureStylesGallery	gallery	Quick Styles
ReviewAcceptChangeAndMoveToNext	button	Accept and Move to Next
ReviewRejectChangeAndMoveToNext	button	Reject and Move to Next
PictureEffectsShadowGallery	gallery	Shadow
PictureEffectsGlowGallery	gallery	Glow
PictureEffectsSoftEdgesGallery	gallery	Soft Edges
PictureReflectionGallery	gallery	Reflection
PictureRotationGallery	gallery	3-D Rotation
InkToolsClose	button	Close Ink Tools
GroupChineseTranslation	group	Chinese Translation
LineSpacingMenu	menu	Line spacing
GroupDocumentViews	group	Document Views
GroupViewShowHide	group	Show/Hide
GroupWindow	group	Window
ViewGridlines	checkBox	View Gridlines
FileDocumentEncrypt	toggleButton	Encrypt Document
WordArtFormatDialog	button	Format Text Effects...
ObjectRotationOptionsDialog	button	More Rotation Options...
MoreTextureOptions	button	More Textures...
TextFillColorMoreColorsDialog	button	More Fill Colors...
ZoomTwoPages	button	Two Pages
QuickPartsInsertFromOnline	button	Get More on Office Online...
GroupPrintPreviewPageSetup	group	Page Setup
ShowRuler	checkBox	Ruler
FileEmailAsPdfEmailAttachment	button	E-mail as PDF Attachment
FileEmailAsXpsEmailAttachment	button	E-mail as XPS Attachment
GroupTemplates	group	Templates

idMso	Control Type	Label
SpellingMenu	splitButton	Spelling
PictureEffectsMenu	menu	Picture Effects
PictureShapeGallery	gallery	Change Shape
PictureBorderColorPickerClassic	gallery	Picture Border
GroupChartBackground	group	Background
GroupChartAnalysis	group	Analysis
FileNewBlogPost	button	Blog
TabBlogPost	tab	Blog Post
GroupBlogPublish	group	Blog
BlogPublishMenu	splitButton	Publish
BlogPublish	button	Publish
BlogPublishDraft	button	Publish as Draft
BlogManageAccounts	button	Manage Accounts
BlogCategoryInsert	button	Insert Category
BlogOpenExisting	button	Open Existing
GroupBlogBasicText	group	Basic Text
TabBlogInsert	tab	Insert
GroupBlogInsertText	group	Text
NewTableStyleWord	button	New Table Style...
MenuPublish	menu	Publish
ChangeStylesMenu	menu	Change Styles
GroupBlogInsertLinks	group	Links
FileCompatibilityCheckerWord	button	Run Compatibility Checker
FileSaveAsOtherFormats	button	Other Formats
FileSaveAsWordDocx	button	Word Document
FileSaveAsWordDotx	button	Word Template
ZoomCurrent100	button	100%
Drawing1ColorPickerLineStyleWordArt	gallery	Picture Border
Drawing1ColorPickerFillWordArt	gallery	Shape Fill

idMso	Control Type	Label
BlogInsertCategories	button	Insert Category
GroupTableLayout	group	Table Style Options
TextFillMoreTextures	button	More Textures...
GroupMacros	group	Macros
PlayMacro	button	Macros
MenuMacros	splitButton	Macros
AdvertisePublishAs	button	Find add-ins for other file formats
ReviewProtectDocumentMenu	menu	Protect Document
ReviewRestrictFormatting	toggleButton	Restrict Formatting and Editing
BlogHomePage	button	Home Page
GroupBlogProofing	group	Proofing
GroupBlogStyles	group	Styles
AlternativeText	button	Size...
ThemeBrowseForThemes	button	Browse for Themes...
FileCheckOutDiscard	button	Discard Check Out
GroupBlogSymbols	group	Symbols
ClearMenuWord	menu	Clear
MdiChildSystemMenu	menu	Document
NudgeMenu	menu	Nudge
RevisionsMenu	menu	Track Changes
TableCellVerticalAlignmentMenu	menu	Alignment
FramesetMenu	menu	Frames

3.1.2 Excel 2007

idMso	Control Type	Label
Spelling	button	Spelling...
FileSave	button	Save
FilePrint	button	Print

idMso	Control Type	Label
ChartInsert	button	Chart...
FileNew	button	New
Copy	button	Copy
Cut	button	Cut
Paste	button	Paste
FileOpen	button	Open
ZoomPrintPreviewExcel	toggleButton	Zoom
Repeat	button	Repeat
UnderlineDouble	toggleButton	Double Underline
FileClose	button	Close
FormatPainter	toggleButton	Format Painter
FilePrintPreview	button	Print Preview
Bold	toggleButton	Bold
Italic	toggleButton	Italic
Underline	toggleButton	Underline
DarkShading	button	Dark Shading
AlignLeft	toggleButton	Align Left
AlignRight	toggleButton	Align Right
AlignCenter	toggleButton	Center
AlignJustify	toggleButton	Justify
Undo	gallery	Undo
Redo	gallery	Redo
BorderTop	toggleButton	Top Border
BorderBottom	toggleButton	Bottom Border
BorderLeft	toggleButton	Left Border
BorderRight	toggleButton	Right Border
BorderInside	button	Inside Borders
BorderOutside	button	Outside Borders
BorderNone	button	No Border

idMso	Control Type	Label
ObjectsGroup	button	Group
ObjectsUngroup	button	Ungroup
ObjectBringToFront	button	Bring to Front
ObjectSendToBack	button	Send to Back
ObjectBringForward	button	Bring Forward
ObjectSendBackward	button	Send Backward
ViewFullScreenView	toggleButton	Full Screen
ObjectsSelect	toggleButton	Select Objects
MacroRecord	button	Record Macro...
MacroPlay	button	Macros
ObjectFlipHorizontal	button	Flip Horizontal
ObjectFlipVertical	button	Flip Vertical
ObjectRotateRight90	button	Rotate Right 90°
ObjectRotateLeft90	button	Rotate Left 90°
ShapeFreeform	toggleButton	Freeform
ObjectEditPoints	toggleButton	Edit Points
FormControlEditBox	button	Edit Box
FormControlCheckBox	button	Check Box
FormControlComboBox	button	Combo Box
PropertySheet	button	Property Sheet
Lock	toggleButton	Lock
AutoSum	button	Sum
StylesDialogClassic	button	Edit Cell Styles
Camera	button	Camera
FormControlButton	button	Button
Calculator	button	Calculator
Strikethrough	toggleButton	Strikethrough
CellsDelete	button	Delete Cells...
CellsInsertDialog	button	Insert Cells...

idMso	Control Type	Label
WindowsArrangeAll	button	Arrange All
WindowNew	button	New Window
ReviewAcceptOrRejectChangeDialog	button	Accept/Reject Changes
SymbolInsert	button	Symbol...
ReplaceDialog	button	Replace...
PagePrevious	button	Previous Page
PageNext	button	Next Page
TextBoxInsertVertical	toggleButton	Vertical Text Box
ObjectsRegroup	button	Regroup
PrintAreaSetPrintArea	button	Set Print Area
PasteFormatting	button	Paste Formatting
PasteValues	button	Paste Values
FillRight	button	Right
FillDown	button	Down
EqualSign	button	Equal Sign
PlusSign	button	Plus Sign
MinusSign	button	Minus Sign
MultiplicationSign	button	Multiplication Sign
DivisionSign	button	Division Sign
ExponentiationSign	button	Exponentiation Sign
ParenthesisLeft	button	Left Parenthesis
ParenthesisRight	button	Right Parenthesis
ColonSign	button	Colon
CommaSign	button	Comma
PercentSign	button	Percent Sign
DollarSign	button	Dollar Sign
FunctionWizard	button	Insert Function...
ConstrainNumeric	button	Constrain Numeric
LightShading	button	Light Shading

idMso	Control Type	Label
AccountingFormat	button	Accounting Number Format
PercentStyle	button	Percent Style
CommaStyle	button	Comma Style
DecimalsIncrease	button	Increase Decimal
DecimalsDecrease	button	Decrease Decimal
MergeCenter	toggleButton	Merge & Center
FontSizeIncrease	button	Increase Font Size
FontSizeDecrease	button	Decrease Font Size
TextOrientationVertical	toggleButton	Vertical Text
TextOrientationRotateUp	toggleButton	Rotate Text Up
TextOrientationRotateDown	toggleButton	Rotate Text Down
AlignDistributeHorizontallyClassic	button	Distribute Horizontally
ShapeScribble	toggleButton	Scribble
OutlineSymbolsShowHide	button	Show Outline Symbols
TableSelectVisibleCells	button	Select Visible Cells
SelectCurrentRegion	button	Select Current Region
FreezePanels	button	Freeze Panels
ZoomIn	button	Zoom In
ZoomOut	button	Zoom Out
FormControlRadioButton	button	Option Button
FormControlScrollBar	button	Scroll Bar
FormControlListBox	button	List Box
TraceDependentRemoveArrows	button	Remove Dependent Arrows
TraceDependents	button	Trace Dependents
TracePrecedentsRemoveArrows	button	Remove Precedent Arrows
TraceRemoveAllArrows	button	Remove Arrows
FileUpdate	button	Update File
ReadOnly	button	Toggle Read Only
AutoFilterClassic	button	AutoFilter

idMso	Control Type	Label
Refresh	button	Refresh
PivotTableFieldSettings	button	Field Settings
PivotTableShowPages	button	Show Report Filter Pages...
OutlineShowDetail	button	Show Detail
TraceError	button	Trace Error
OutlineHideDetail	button	Hide Detail
AlignDistributeVerticallyClassic	button	Distribute Vertically
FormControlGroupBox	button	Group Box
FormControlSpinner	button	Spinner
TabOrder	button	Tab Order...
RunDialog	button	Run Dialog
FormControlCombinationListEdit	button	Combination List-Edit
FormControlCombinationDropDownEdit	button	Combination Drop-Down Edit
FormControlLabel	button	Label
TracePrecedents	button	Trace Precedents
CodeEdit	button	Code
PageBreakInsertOrRemove	button	Insert Page Break
QueryParameters	button	Parameters
RowHeight	button	Row Height...
ColumnWidth	button	Column Width...
OleObjectctInsert	button	Object...
SnapToGrid	toggleButton	Snap to Grid
ObjectsAlignLeft	button	Align Left
ObjectsAlignRight	button	Align Right
ObjectsAlignTop	button	Align Top
ObjectsAlignBottom	button	Align Bottom
ObjectsAlignCenterHorizontal	button	Align Center
ObjectsAlignMiddleVertical	button	Align Middle
ClipArtInsert	toggleButton	Clip Art...

idMso	Control Type	Label
ObjectRotateFree	button	Free Rotate
CombineCharacters	toggleButton	Yoko-Gumi
ViewNormalViewExcel	toggleButton	Normal
ViewPageBreakPreviewView	toggleButton	Page Break Preview
PictureCrop	toggleButton	Crop
FileCloseAll	button	Close All
FileSaveAs	button	Save As
AdvancedFileProperties	button	View Document Properties...
CopyAsPicture	button	Copy as Picture...
PasteSpecialDialog	button	Paste Special...
SelectAll	button	Select All
GoTo	button	Go To...
FileLinksToFiles	button	Edit Links to Files
HeaderFooterInsert	button	Header & Footer...
BulletsAndNumberingBulletsDialog	button	Bullets and Numbering...
AutoFormatDialog	button	AutoFormat...
MergeCells	button	Merge Cells
SplitCells	button	Split Cells...
ConvertTextToTable	button	Convert Text to Table...
ShowClipboard	button	Office Clipboard...
OutlookTaskCreate	button	Create Microsoft Office Outlook Task
WindowMinimize	button	Minimize
WindowRestore	button	Restore
WindowClose	button	Close
WindowSaveWorkspace	button	Save Workspace...
SheetDelete	button	Delete Sheet
SheetMoveOrCopy	button	Move or Copy Sheet...
ViewFormulaBar	checkBox	Formula Bar
SheetInsert	button	Insert Sheet

idMso	Control Type	Label
FormatCellsDialog	button	Format Cells...
GoalSeek	button	Goal Seek...
ScenarioManager	button	Scenario Manager...
DataFormExcel	button	Form...
OutlineSubtotals	button	Subtotal
DataTable	button	Data Table...
Consolidate	button	Consolidate...
WindowHide	button	Hide
WindowUnhide	button	Unhide...
FillUp	button	Up
FillLeft	button	Left
FillAcrossWorksheets	button	Across Worksheets...
FillSeries	button	Series...
FillJustify	button	Justify
ClearFormats	button	Clear Formats
ClearContents	button	Clear Contents
ClearComments	button	Clear Comments
NamePasteName	button	Paste Names...
NameCreateFromSelection	button	Create from Selection...
NamesApply	button	Apply Names...
RowHeightAutoFit	button	AutoFit Row Height
RowsHide	button	Hide Rows
RowsUnhide	button	Unhide Rows
ColumnWidthAutoFit	button	AutoFit Column Width
ColumnsHide	button	Hide Columns
ColumnsUnhide	button	Unhide Columns
ColumnWidthDefault	button	Default Width...
SheetRename	button	Rename Sheet
SheetHide	button	Hide Sheet

idMso	Control Type	Label
SheetUnhide	button	Unhide Sheet...
SheetProtect	button	Protect Sheet...
ReviewProtectWorkbook	toggleButton	Protect Workbook...
MacroRelativeReferences	toggleButton	Use Relative References
Filter	toggleButton	Filter
SortClear	button	Clear
AdvancedFilterDialog	button	Advanced...
OutlineAuto	button	Auto Outline
OutlineClear	button	Clear Outline
OutlineSettings	button	Group and Outline Settings
PrintPreviewClose	button	Close Print Preview
ZoomDialog	button	Zoom...
SortDialogClassic	button	Sort...
ExchangeFolder	button	Exchange Folder...
AddInManager	button	Add-Ins...
ViewCustomViews	button	Custom Views...
SheetBackground	button	Background...
ChartEditDataSource	button	Select Data...
ChartPlacement	button	Move Chart...
CalculateNow	button	Calculate Now
ObjectFormatDialog	button	Object...
Help	button	Help
PivotTableEnableSelection	toggleButton	Enable Selection
PivotTableListFormulas	button	List Formulas
PivotTableSelectData	button	Values
PivotTableSelectLabelAndData	button	Labels and Values
PivotTableSelectLabel	button	Labels
PasteAsPicture	button	Paste as Picture
PastePictureLink	button	Paste Picture Link

idMso	Control Type	Label
CalculateSheet	button	Calculate Sheet
TextOrientationAngleCounterclockwise	toggleButton	Angle Counterclockwise
TextOrientationAngleClockwise	toggleButton	Angle Clockwise
WebGoBack	button	Back
WebGoForward	button	Forward
SmartArtInsert	button	SmartArt...
ShapeRerouteConnectors	toggleButton	Reroute Connectors
ObjectNudgeUp	button	Up
ObjectNudgeDown	button	Down
ObjectNudgeLeft	button	Left
ObjectNudgeRight	button	Right
ShapeCurve	toggleButton	Curve
ShapeStraightConnector	toggleButton	Straight Connector
ShapeElbowConnector	toggleButton	Elbow Connector
ObjectFillMoreColorsDialog	button	More Fill Colors...
ObjectBorderOutlineColorMoreColorsDialog	button	More Outline Colors...
LineStyleDialog	button	More Lines...
ArrowsMore	button	More Arrows...
WordArtVerticalText	button	Vertical Text
ContrastMore	button	More Contrast
ContrastLess	button	Less Contrast
BrightnessMore	button	More Brightness
BrightnessLess	button	Less Brightness
ShadowNudgeUpClassic	button	Nudge Shadow Up
ShadowNudgeDownClassic	button	Nudge Shadow Down
ShadowNudgeLeftClassic	button	Nudge Shadow Left
ShadowNudgeRightClassic	button	Nudge Shadow Right
ObjectShadowColorMoreColorsDialog	button	More Shadow Colors...
_3DEffectColorPickerMoreClassic	button	More 3-D Colors...

idMso	Control Type	Label
ShapeRectangle	toggleButton	Rectangle
ShapeRoundedRectangle	toggleButton	Rounded Rectangle
ShapeIsoscelesTriangle	toggleButton	Isosceles Triangle
ShapeOval	toggleButton	Oval
ShapeLeftBrace	toggleButton	Left Brace
ShapeRightBrace	toggleButton	Right Brace
ShapeArc	toggleButton	Arc
ShapeRightArrow	toggleButton	Right Arrow
ShapeDownArrow	toggleButton	Down Arrow
ShapeRoundedRectangularCallout	toggleButton	Rounded Rectangular Callout
ShapeStar	toggleButton	5-Point Star
PictureReset	button	Reset Picture
_3DEffectsOnOffClassic	toggleButton	3-D On/Off
_3DTiltDownClassic	button	Tilt Down
_3DTiltUpClassic	button	Tilt Up
_3DTiltLeftClassic	button	Tilt Left
_3DTiltRightClassic	button	Tilt Right
_3DSurfaceMaterialClassic	menu	Surface
_3DExtrusionPerspectiveClassic	toggleButton	Perspective
_3DExtrusionParallelClassic	toggleButton	Parallel
_3DLightingFlatClassic	toggleButton	Bright
_3DLightingNormalClassic	toggleButton	Normal
_3DLightingDimClassic	toggleButton	Dim
_3DSurfaceMatteClassic	toggleButton	Matte
_3DSurfacePlasticClassic	toggleButton	Plastic
_3DSurfaceMetalClassic	toggleButton	Metal
_3DSurfaceWireFrameClassic	toggleButton	Wire Frame
SnapToShapes	toggleButton	Snap to Shape
HyperlinkInsert	button	Hyperlink...

idMso	Control Type	Label
PrintAreaAddToPrintArea	button	Add to Print Area
PrintAreaClearPrintArea	button	Clear Print Area
PageBreaksResetAll	button	Reset All Page Breaks
ReviewNewComment	button	New Comment
ReviewPreviousComment	button	Previous
ReviewNextComment	button	Next
ReviewDeleteComment	button	Delete
ReviewShowOrHideComment	button	Show/Hide Comment
ReviewShowAllComments	toggleButton	Show All Comments
PivotTableFieldInsert	button	Calculated Field...
PivotTableCalculatedItem	button	Calculated Item...
PivotTableSelectEntireTable	button	Entire PivotTable
PivotTableOptions	button	Options
DesignMode	toggleButton	Design Mode
PhoneticGuideEdit	button	Edit Phonetic
PhoneticGuideSettings	button	Phonetic Settings...
PhoneticGuideFieldShow	toggleButton	Show Phonetic Field
CircularReferences	gallery	Circular References
VisualBasic	button	Visual Basic
BorderThickBottom	button	Thick Bottom Border
BorderTopAndBottom	button	Top and Bottom Border
BorderTopAndDoubleBottom	button	Top and Double Bottom Border
BorderTopAndThickBottom	button	Top and Thick Bottom Border
BordersAll	button	All Borders
BorderThickOutside	button	Thick Box Border
Font	comboBox	Font:
FontSize	comboBox	Font Size:
StyleGalleryClassic	gallery	Style:
ZoomClassic	gallery	Zoom:

idMso	Control Type	Label
ScenarioGallery	gallery	Scenario:
DocumentLocation	comboBox	Address:
MergeCellsAcross	button	Merge Across
BorderInsideHorizontal	button	Inside Horizontal Border
BorderInsideVertical	button	Inside Vertical Border
BorderDiagonalDown	button	Diagonal Down Border
BorderDiagonalUp	button	Diagonal Up Border
TextDirectionLeftToRight	toggleButton	Left-to-Right
TextDirectionRightToLeft	toggleButton	Right-to-Left
ActiveXCheckBox	button	Check Box
FindDialogExcel	button	Find...
ActiveXTextBox	button	Text Box
ActiveXButton	button	Command Button
ActiveXRadioButton	button	Option Button
ActiveXListBox	button	List Box
ActiveXComboBox	button	Combo Box
ActiveXToggleButton	button	Toggle Button
ActiveXSpinButton	button	Spin Button
ActiveXScrollBar	button	Scroll Bar
ActiveXLabel	button	Label
ShadowSemitransparentClassic	toggleButton	Semitransparent Shadow
RightToLeftDocument	toggleButton	Right-to-Left Document
EditQuery	button	Edit Query...
DataRangeProperties	button	Properties
RefreshAll	button	Refresh All
RefreshCancel	button	Cancel Refresh
RefreshStatus	button	Refresh Status
PasteLink	button	Paste Link...
ClearAll	button	Clear All

idMso	Control Type	Label
DataValidation	button	Data Validation...
DataValidationCircleInvalid	button	Circle Invalid Data
ReviewShareWorkbook	button	Share Workbook...
ReviewHighlightChanges	button	Highlight Changes...
CompareAndMergeWorkbooks	button	Compare and Merge Workbooks...
DatabaseQueryNew	button	New Database Query...
DataValidationClearValidationCircles	button	Clear Validation Circles
ActiveXImage	button	Image
ShadowOnOrOffClassic	toggleButton	Shadow On/Off
ObjectSetShapeDefaults	button	Set AutoShape Defaults
FileSendAsAttachment	button	E-mail
FileNewDefault	button	New
FilePrintQuick	button	Quick Print
PictureInsertFromFile	button	Picture...
ShapeStraightConnectorArrow	toggleButton	Straight Arrow Connector
ShapeElbowConnectorArrow	toggleButton	Elbow Arrow Connector
PasteAsHyperlink	button	Paste as Hyperlink
ParagraphDistributed	toggleButton	Distributed
PictureSetTransparentColor	toggleButton	Set Transparent Color
PivotTableSolveOrder	button	Solve Order...
PivotTableReport	button	PivotTable and PivotChart Wizard
ReviewProtectAndShareWorkbook	button	Protect Sharing
OutlineGroup	button	Group...
OutlineUngroup	button	Ungroup...
IndentIncreaseExcel	button	Increase Indent
IndentDecreaseExcel	button	Decrease Indent
HangulHanjaConversion	button	Hangul Hanja Conversion...
MacroSecurity	button	Macro Security
WebPagePreview	button	Web Page Preview

idMso	Control Type	Label
SendCopySendNow	button	Send Now
SendCopySelectNames	button	Select Names
SendCopySendToMailRecipient	toggleButton	Mail Recipient
ComAddInsDialog	button	COM Add-Ins...
PivotChartInsertClassic	button	PivotChart
PivotFieldListShowHide	toggleButton	Field List
FileSaveAsWebPage	button	Save as Web Page...
GetExternalDataFromWeb	button	From Web
WebOptionsDialog	button	Web Options...
GetExternalDataFromText	button	From Text
FilePublishAsWebPage	button	Publish as Web Page...
PivotTableOlapOffline	button	Offline OLAP...
ObjectsMultiSelect	button	Select Multiple Objects
TextDirectionContext	toggleButton	Context
CalculateFull	button	TBA
WatchWindow	toggleButton	Watch Window
FormulaEvaluate	button	Evaluate Formula
AutoSumAverage	button	Average
AutoSumCount	button	Count Numbers
AutoSumMax	button	Max
AutoSumMin	button	Min
AutoSumMoreFunctions	button	More Functions...
PasteFormulas	button	Formulas
PasteNoBorders	button	No Borders
PasteTranspose	button	Transpose
DrawingCanvasFit	button	Fit
DrawingCanvasResize	button	Resize
DrawingCanvasExpand	button	Expand
ReviewSendForReview	button	Send for Review...

idMso	Control Type	Label
BorderDrawMenu	splitButton	Draw Border
BorderErase	toggleButton	Erase Border
BorderStyle	dropDown	Line Style
ShowFormulas	toggleButton	Show Formulas
PivotTableOlapPropertyFields	button	Property Fields...
TranslationPane	button	Translate...
ErrorChecking	button	Error Checking...
FileCheckOut	button	Check Out
FileCheckIn	button	Check In
PivotTableGenerateGetPivotData	checkBox	Generate GetPivotData
ReviewReplyWithChanges	button	Reply with Changes...
ReviewEndReview	button	End Review...
BorderDrawLine	toggleButton	Draw Border
BorderDrawGrid	toggleButton	Draw Border Grid
GetExternalDataImportClassic	button	Import External Data
PicturesCompress	button	Compress Pictures...
VerticallyDistributed	button	Vertically Distributed
ReviewAllowUsersToEditRanges	button	Allow Users to Edit Ranges...
SpeakCells	button	Speak Cells
SpeakStop	button	Stop Speaking
SpeakByRows	toggleButton	By Rows
SpeakByColumns	toggleButton	By Columns
SpeakOnEnter	toggleButton	On Enter
TableInsertExcel	button	Table
ResearchPane	toggleButton	Research...
TableStyleTotalsRow	checkBox	Total Row
TableRowsInsertAboveExcel	button	Insert Table Rows Above
TableRowsDeleteExcel	button	Delete Table Rows
TableConvertToRange	button	Convert to Range

idMso	Control Type	Label
PrintListRange	button	Print List
FileInternetFax	button	Internet Fax
XmlExport	button	Export
XmlImport	button	Import
ViewDocumentActionsPane	toggleButton	Document Actions
ReviewShowInk	toggleButton	Show Ink
TableColumnsInsertLeftExcel	button	Insert Table Columns to the Left
TableColumnsDeleteExcel	button	Delete Table Columns
InkDeleteAllInk	button	Delete All Ink
TableUnlinkExternalData	button	Unlink
TableExportTableToSharePointList	button	Export Table to SharePoint List...
PrivacyOptionsDialog	button	Privacy Options...
ListSynchronize	button	Synchronize List
ChangesDiscardAndRefresh	button	Discard Changes and Refresh
TableOpenInBrowser	button	Open in Browser
TableResize	button	Resize Table
XmlExpansionPacksExcel	button	Expansion Packs
FileVersionHistory	button	View Version History
XmlDataRefresh	button	Refresh Data
XmlMapProperties	button	Map Properties
WindowSideBySideSynchronousScrolling	toggleButton	Synchronous Scrolling
WindowResetPosition	button	Reset Window Position
InkColorMoreColorsDialog	button	More Ink Colors...
ContactUs	button	Contact Us...
FilePermissionUnrestricted	toggleButton	Unrestricted Access
FilePermissionDoNotDistribute	toggleButton	Restricted Access
FilePermissionView	button	View Permission
FilePermission	button	Permission
Thesaurus	button	Thesaurus...

idMso	Control Type	Label
InkingStart	button	Start Inking
CheckForUpdates	button	Check for Updates
InkCopyAsText	button	Copy Ink As Text
InkEraser	toggleButton	Eraser
FilePermissionRestrictAs	button	Manage Credentials
Connections	button	Connections
FileViewDigitalSignatures	toggleButton	View Signatures
FileWorkflowTasks	button	View Workflow Tasks
FileStartWorkflow	button	Workflows
SignatureLineInsert	button	Signature Line
LabelInsert	button	Label
BarcodeInsert	button	Barcode
ViewPageLayoutView	toggleButton	Page Layout
PivotClearAll	button	Clear All
ChartStylesGallery	gallery	Quick Styles
ChartLayoutGallery	gallery	Quick Layout
ChartSaveTemplates	button	Save As Template
ChartAxisTitles	menu	Axis Titles
ChartAxes	menu	Axes
ChartGridlines	menu	Gridlines
ChartFormatSelection	button	Format Selection
ChartElementSelector	comboBox	Chart Elements
PageMarginsGallery	gallery	Margins
TabPictureToolsFormat	tab	Format
TabDrawingToolsFormat	tab	Format
ShapesInsertGallery	gallery	Shapes
ShapeChangeShapeGallery	gallery	Change Shape
ShapeFillTextureGallery	gallery	Texture
ShapeStylesGallery	gallery	Quick Styles

idMso	Control Type	Label
PageOrientationGallery	gallery	Orientation
FileServerTasksMenu	menu	Server
FileSendMenu	menu	Send
TabInsert	tab	Insert
TabPageLayoutExcel	tab	Page Layout
TabView	tab	View
GroupFont	group	Font
GroupStyles	group	Styles
GroupProofing	group	Proofing
GroupInsertIllustrations	group	Illustrations
GroupShapes	group	Insert Shapes
GroupPageSetup	group	Page Setup
GroupComments	group	Comments
GroupPictureSize	group	Size
GroupDrawBorders	group	Draw Borders
GroupTableProperties	group	Properties
GroupTableTools	group	Tools
GroupArrange	group	Arrange
GroupShapeStyles	group	Shape Styles
TabFormulas	tab	Formulas
TabData	tab	Data
TabReview	tab	Review
GroupChartLayouts	group	Chart Layouts
GroupChartStyles	group	Chart Styles
GroupChartAxes	group	Axes
GroupChartShapes	group	Insert
GroupNumber	group	Number
GroupAlignmentExcel	group	Alignment
GroupCells	group	Cells

idMso	Control Type	Label
GroupSortFilter	group	Sort & Filter
GroupInsertTablesExcel	group	Tables
GroupPageLayoutScaleToFit	group	Scale to Fit
GroupPageLayoutSheetOptions	group	Sheet Options
GroupFunctionLibrary	group	Function Library
GroupNamedCells	group	Defined Names
GroupFormulaAuditing	group	Formula Auditing
GroupGetExternalData	group	Get External Data
GroupConnections	group	Connections
GroupOutline	group	Outline
GroupDataTools	group	Data Tools
GroupChangesExcel	group	Changes
ObjectEffectPresetGallery	gallery	Preset
PictureEffectsPresetGallery	gallery	Preset
_3DRotationGallery	gallery	3-D Rotation
TabSmartArtToolsDesign	tab	Design
TabSmartArtToolsFormat	tab	Format
TabChartToolsDesign	tab	Design
TabChartToolsLayout	tab	Layout
TabChartToolsFormat	tab	Format
ShapeFillColorPicker	gallery	Shape Fill
OutlineColorPicker	gallery	Picture Border
FileDocumentInspect	button	Inspect Document
AlignLeftToRightMenu	splitButton	Left-to-Right
GroupControls	group	Controls
GroupZoom	group	Zoom
ArrowStyleGallery	gallery	Arrows
OutlineDashesGallery	gallery	Dashes
OutlineWeightGallery	gallery	Weight

idMso	Control Type	Label
GroupPictureTools	group	Adjust
GroupSize	group	Size
FormatCellsNumberDialog	button	Format Cell Number
FormatCellsFontDialog	button	Format Cell Font
CellAlignmentOptions	button	Format Cell Alignment
PageSetupPageDialog	button	Page Setup
PageSetupSheetDialog	button	Sheet Options
TabPivotTableToolsOptions	tab	Options
PivotTableLayoutGrandTotals	menu	Grand Totals
TabPivotTableToolsDesign	tab	Design
GroupPivotTableActiveField	group	Active Field
GroupPivotTableLayout	group	Layout
GroupPivotTableSort	group	Sort
GroupPivotTableShowHide	group	Show/Hide
PivotTableLayoutSubtotals	menu	Subtotals
GroupPivotTableGroup	group	Group
GroupPivotTableTools	group	Tools
GroupPivotTableData	group	Data
GroupPivotTableOptions	group	PivotTable
GroupPivotTableStyles	group	PivotTable Styles
GroupPivotTableStyleOptions	group	PivotTable Style Options
WrapText	toggleButton	Wrap Text
ClearMenu	menu	Clear
ReviewTrackChangesMenu	menu	Track Changes
ObjectAlignMenu	menu	Align
ObjectRotateGallery	gallery	Rotate
FillMenu	menu	Fill
OrientationMenu	menu	Orientation
MergeCenterMenu	splitButton	Merge

idMso	Control Type	Label
AutoSumMenu	splitButton	AutoSum
PrintAreaMenu	menu	Print Area
PageBreakMenu	menu	Breaks
NameDefineMenu	splitButton	Define Name
RefreshMenu	splitButton	Refresh
WhatIfAnalysisMenu	menu	What-If Analysis
PivotTableFormulasMenu	menu	Formulas
PivotTableOlapTools	menu	OLAP tools
PivotTableOptionsMenu	splitButton	Table Options
ErrorCheckingMenu	splitButton	Error Checking
TraceRemoveArrowsMenu	splitButton	Remove Arrows
SortFilterMenu	menu	Sort & Filter
FontColorPicker	gallery	Font Color
CellFillColorPicker	gallery	Shading
BorderDoubleBottom	button	Bottom Double Border
TabHome	tab	Home
ChartTitle	gallery	Chart Title
ChartPrimaryHorizontalAxisTitle	gallery	Primary Horizontal Axis Title
ChartPrimaryVerticalAxisTitle	gallery	Primary Vertical Axis Title
ChartDepthAxisTitle	gallery	Depth Axis Title
ChartLegend	gallery	Legend
ChartDataLabel	gallery	Data Labels
ChartPrimaryHorizontalGridlines	gallery	Primary Horizontal Gridlines
ChartPrimaryVerticalGridlines	gallery	Primary Vertical Gridlines
ChartDepthGridlines	gallery	Depth Gridlines
ChartPrimaryHorizontalAxis	gallery	Primary Horizontal Axis
ChartPrimaryVerticalAxis	gallery	Primary Vertical Axis
ChartDepthAxis	gallery	Depth Axis
ChartDataTable	gallery	Data Table

idMso	Control Type	Label
ChartTrendline	gallery	Trendline
ChartErrorBars	gallery	Error Bars
ChartLines	gallery	Lines
ChartUpDownBars	gallery	Up/Down Bars
ChartPlotArea	gallery	Plot Area
ChartWall	gallery	Chart Wall
ChartFloor	gallery	Chart Floor
SmartArtAddShape	button	Add Shape
SmartArtLargerShape	button	Larger
SmartArtSmallerShape	button	Smaller
SmartArtResetGraphic	button	Reset Graphic
SmartArtTextPane	toggleButton	Text Pane
SmartArtEditIn2D	toggleButton	Edit in 2-D
SmartArtLayoutGallery	gallery	Change Layout
SmartArtMoreLayoutsDialog	button	More Layouts...
SmartArtStylesGallery	gallery	Quick Styles
SmartArtChangeColorsGallery	gallery	Change Colors
ObjectEffectSoftEdgesGallery	gallery	Soft Edges
ObjectEffectGlowGallery	gallery	Glow
GradientGallery	gallery	Gradient
ObjectEffectShadowGallery	gallery	Shadow
WordArtInsertGallery	gallery	WordArt
TextEffectTransformGallery	gallery	Transform
TabHeaderAndFooterToolsDesign	tab	Design
HeaderFooterHeaderGallery	gallery	Header
HeaderFooterFooterGallery	gallery	Footer
GroupHeaderFooterElements	group	Header & Footer Elements
HeaderFooterPageNumberInsertExcel	button	Page Number
HeaderFooterNumberOfPagesInsert	button	Number of Pages

idMso	Control Type	Label
HeaderFooterCurrentDate	button	Current Date
HeaderFooterCurrentTimeInsert	button	Current Time
HeaderFooterFilePathInsert	button	File Path
HeaderFooterFileNameInsert	button	File Name
HeaderFooterSheetNameInsert	button	Sheet Name
HeaderFooterAlignMargins	checkBox	Align with Page Margins
HeaderFooterPictureInsert	button	Picture
HeaderFooterFormatPicture	button	Format Picture
GroupHeaderFooterOptions	group	Options
HeaderFooterDifferentOddEvenPageExcel	checkBox	Different Odd & Even Pages
HeaderFooterDifferentFirstPageExcel	checkBox	Different First Page
HeaderFooterScaleWithDocument	checkBox	Scale with Document
SheetTabColorGallery	gallery	Tab Color
FontShadingColorMoreColorsDialog	button	More Colors...
FontColorMoreColorsDialogExcel	button	More Colors...
BorderMoreColorsDialog	button	More Colors...
SheetTabColorMoreColorsDialog	button	More Colors...
PivotTableNewStyle	button	New PivotTable Style...
PivotPlusMinusFieldHeadersShowHide	toggleButton	Field Headers
PivotTableExpandField	button	Expand Entire Field
PivotCollapseField	button	Collapse Entire Field
ConditionalFormattingDataBarsGallery	gallery	Data Bars
ConditionalFormattingColorScalesGallery	gallery	Color Scales
ConditionalFormattingIconSetsGallery	gallery	Icon Sets
ConditionalFormattingDataBarsMoreOptions	button	More Rules...
ConditionalFormattingColorScalesMore	button	More Rules...
ConditionalFormattingIconSetsMore	button	More Rules...
TableColumnsInsertRightExcel	button	Insert Table Column to the Right
TableRowsInsertBelowExcel	button	Insert Table Row Below

idMso	Control Type	Label
ConditionalFormattingHighlightBetween	button	Between...
ConditionalFormattingClearSelectedCells	button	Clear Rules from Selected Cells
ConditionalFormattingClearSheet	button	Clear Rules from Entire Sheet
ConditionalFormattingClearTable	button	Clear Rules from This Table
ConditionalFormattingClearPivotTable	button	Clear Rules from This PivotTable
PivotTableStylesGallery	gallery	Quick Styles
FormatAsTableGallery	gallery	Format as Table
TableStylesGalleryExcel	gallery	Quick Styles
ConditionalFormattingsManage	button	Manage Rules...
ConditionalFormattingHighlightGreaterThan	button	Greater Than...
ConditionalFormattingHighlightLessThan	button	Less Than...
ConditionalFormattingHighlightEqualTo	button	Equal To...
ConditionalFormattingHighlightTextContaining	button	Text that Contains...
ConditionalFormattingHighlightDateOccuring	button	A Date Occurring...
ConditionalFormattingHighlightDuplicateValues	button	Duplicate Values...
ConditionalFormattingTopNItems	button	Top 10 Items...
ConditionalFormattingTopNPercent	button	Top 10 %...
ConditionalFormattingBottomNItems	button	Bottom 10 Items...
ConditionalFormattingBottomNPercent	button	Bottom 10 %...
ConditionalFormattingAboveAverage	button	Above Average...
ConditionalFormattingBelowAverage	button	Below Average...
RemoveDuplicates	button	Remove Duplicates
FilterReapply	button	Reapply
ThemeColorsGallery	gallery	Colors
PivotTableInsert	button	PivotTable
PivotChartInsert	button	PivotChart
PivotTableMove	button	Move PivotTable
PivotTableChangeDataSource	button	Change Data Source...
GroupSmartArtLayouts	group	Layouts

idMso	Control Type	Label
GroupSmartArtQuickStyles	group	SmartArt Styles
GroupSmartArtCreateGraphic	group	Create Graphic
GroupSmartArtReset	group	Reset
GroupSmartArtSize	group	Size
ConditionalFormattingHighlightCellsMenu	menu	Highlight Cells Rules
ConditionalFormattingTopBottomMenu	menu	Top/Bottom Rules
FormatCellsMenu	menu	Format
ConditionalFormattingClearMenu	menu	Clear Rules
ThemeSearchOfficeOnline	button	More Themes on Microsoft Office Online...
FontColorCycle	button	Color
TabAddIns	tab	Add-Ins
CellsInsertSmart	button	Insert Cells
CellsDeleteSmart	button	Delete Cells...
ObjectEditShapeMenu	menu	Edit Shape
PivotTableLayoutReportLayout	menu	Report Layout
PivotTableLayoutShowInCompactForm	button	Show in Compact Form
PivotTableLayoutShowInOutlineForm	button	Show in Outline Form
PivotTableLayoutShowInTabularForm	button	Show in Tabular Form
PivotTableClearMenu	menu	Clear
ConditionalFormattingTopBottomMore	button	More Rules...
ConditionalFormattingHighlightRulesMore	button	More Rules...
CellStylesGallery	gallery	Cell Styles
CellStyleNew	button	New Cell Style...
CellStylesMerge	button	Merge Styles...
TableStyleNew	button	New Table Style...
TableStyleClear	button	Clear
TableStyleHeaderRow	checkBox	Header Row
FilePublishExcelServices	button	Excel Services
PivotTableOlapConvertToFormulas	button	Convert to Formulas

idMso	Control Type	Label
PivotTableLayoutBlankRows	menu	Blank Rows
TableStyleFirstColumn	checkBox	First Column
TableStyleLastColumn	checkBox	Last Column
TableStyleBandedRows	checkBox	Banded Rows
TableStyleBandedColumns	checkBox	Banded Columns
TableStyleRowHeaders	checkBox	Row Headers
TableStyleColumnHeaders	checkBox	Column Headers
TableSummarizeWithPivot	button	Summarize with PivotTable
ConnectionProperties	button	Connection Properties...
PivotClearFilters	button	Clear Filters
GetExternalDataFromAccess	button	From Access
GetExternalDataFromOtherSources	gallery	From Other Sources
GetExternalDataExistingConnections	button	Existing Connections
GroupThemesExcel	group	Themes
PivotPlusMinusButtonsShowHide	toggleButton	+/- Buttons
FileSaveAsPdfOrXps	button	Publish as PDF or XPS
FileSaveAsExcelOpenDocumentSpreadsheet	button	OpenDocument Spreadsheet
MoreControlsDialog	button	More Controls...
GroupCode	group	Code
TabDeveloper	tab	Developer
GroupXml	group	XML
PageScaleToFitWidth	comboBox	Width:
PageScaleToFitHeight	comboBox	Height:
SelectMenuExcel	menu	Find & Select
GoToSpecial	button	Go To Special...
GoToFormulas	button	Formulas
GoToComments	button	Comments
GoToConditionalFormatting	button	Conditional Formatting
GoToConstants	button	Constants

idMso	Control Type	Label
GoToDataValidation	button	Data Validation
PrintTitles	button	Print Titles
NameUseInFormula	gallery	Use in Formula
CalculationOptionsMenu	menu	Calculation Options
CalculationOptionsManually	toggleButton	Manual
CalculationOptionsAutomatically	toggleButton	Automatic
CalculationOptionsAutomaticallyExceptDataTables	toggleButton	Automatic Except for Data Tables
XmlSource	toggleButton	Source...
GroupClipboard	group	Clipboard
GroupInsertLinks	group	Links
GroupInsertBarcode	group	Barcode
GroupCalculation	group	Calculation
BordersGallery	splitButton	Borders
BordersMoreDialog	button	More Borders...
PageScaleToFitOptionsDialog	button	More Pages...
PageBreakInsertExcel	button	Insert Page Break
PageBreakRemove	button	Remove Page Break
PageSizeGallery	gallery	Size
ObjectPictureFill	button	Picture...
PivotTableGroupSelection	button	Group Selection
PivotTableGroupField	button	Group Field
WindowSwitchWindowsMenuExcel	menu	Switch Windows
ThemeColorsCreateNew	button	Create New Theme Colors...
ThemeFontsCreateNew	button	Create New Theme Fonts...
ShapeFillMoreGradientsDialog	button	More Gradients...
ShadowOptionsDialog	button	Shadow Options...
MarginsCustomMargins	button	Custom Margins...
FunctionsRecentlyUsedInsertGallery	gallery	Recently Used
FunctionsFinancialInsertGallery	gallery	Financial

idMso	Control Type	Label
FunctionsDateTimeInsertGallery	gallery	Date & Time
FunctionsMathTrigInsertGallery	gallery	Math & Trig
FunctionsTextInsertGallery	gallery	Text
FunctionsLogicalInsertGallery	gallery	Logical
FunctionsStatisticalInsertGallery	gallery	Statistical
FunctionsLookupReferenceInsertGallery	gallery	Lookup & Reference
FunctionsInformationInsertGallery	gallery	Information
TabTableToolsDesignExcel	tab	Design
GroupTableStyleOptions	group	Table Style Options
GroupTableExternalData	group	External Table Data
GroupEditingExcel	group	Editing
FileCompatibilityChecker	button	Run Compatibility Checker
ThemeFontsGallery	gallery	Fonts
ThemeEffectsGallery	gallery	Effects
FileProperties	toggleButton	Properties
TabPrintPreview	tab	Print Preview
GroupPrintPreviewPrint	group	Print
GroupPrintPreviewPreview	group	Preview
SortDialog	button	Sort...
SortAscendingExcel	button	Sort Ascending
SortDescendingExcel	button	Sort Descending
SortCustomExcel	button	Custom Sort...
FileCreateDocumentWorkspace	toggleButton	Create Document Workspace
FileSaveToDocumentManagementServer	button	Document Management Server
FileDocumentManagementInformation	toggleButton	Document Management Information
QuickAccessToolbarCustomization	button	Customize Quick Access Toolbar...
FilePrepareMenu	menu	Prepare
FileMarkAsFinal	toggleButton	Mark as Final
FileAddDigitalSignature	button	Add a Digital Signature

idMso	Control Type	Label
SignatureServicesAdd	button	Add Signature Services...
TextBoxInsertMenu	splitButton	Text Box
TextBoxInsertHorizontal	toggleButton	Horizontal Text Box
ControlProperties	button	Properties
ViewCode	button	View Code
GroupHeaderFooterNavigation	group	Navigation
ShadowStyleGalleryClassic	gallery	Shadow Effects
GroupInkSelect	group	Select
NumberFormatGallery	comboBox	Number Format
NumberFormatsDialog	button	More Number Formats...
PageSizeMorePaperSizesDialogExcel	button	More Paper Sizes...
PictureBrightnessGallery	gallery	Brightness
PictureContrastGallery	gallery	Contrast
SmartArtAddShapeAfter	button	Add Shape After
SmartArtAddShapeBefore	button	Add Shape Before
SmartArtAddShapeAbove	button	Add Shape Above
SmartArtAddShapeBelow	button	Add Shape Below
SmartArtAddAssistant	button	Add Assistant
ChartSwitchRowColumn	button	Switch Row/Column
ChartChangeType	button	Change Chart Type...
GroupChartData	group	Data
GroupChartLocation	group	Location
GroupChartType	group	Type
_3DRotationOptionsDialog	button	3-D Rotation Options...
_3DBevelOptionsDialog	button	3-D Options...
SelectionPane	toggleButton	Selection Pane...
SmartArtOrganizationChartLeftHanging	button	Left Hanging
SmartArtOrganizationChartRightHanging	button	Right Hanging
SmartArtOrganizationChartBoth	button	Both

idMso	Control Type	Label
SmartArtOrganizationChartStandard	button	Standard
SmartArtRightToLeft	toggleButton	Right to Left
ViewMessageBar	checkBox	Message Bar
NameManager	button	Name Manager
NameDefine	button	Define Name...
AccountingFormatExcel	button	
AccountingFormatMoreExcel	button	More Accounting Formats...
ShapeStylesOtherThemeFillsGallery	gallery	Other Theme Fills
SmartArtOrganizationChartMenu	menu	Layout
_3DEffectsGalleryClassic	gallery	3-D Effects
_3DDirectionGalleryClassic	gallery	Direction
_3DLightingGalleryClassic	gallery	Lighting
GroupShadowEffects	group	Shadow Effects
Group3DEffects	group	3-D Effects
ShadowColorPickerClassic	gallery	Shadow Color
_3DEffectColorPickerClassic	gallery	3-D Color
ControlsGallery	gallery	Insert
GoToHeader	button	Go to Header
GoToFooter	button	Go to Footer
UnderlineGallery	splitButton	Underline
GroupAddInsMenuCommands	group	Menu Commands
GroupAddInsToolbarCommands	group	Toolbar Commands
ViewFreezePanelsGallery	gallery	Freeze Panes
GroupInk	group	Ink
TabInkToolsPens	tab	Pens
GroupInkPens	group	Pens
GroupInkClose	group	Close
InkBallpointPen	toggleButton	Ballpoint Pen
InkFeltTipPen	toggleButton	Felt Tip Pen

idMso	Control Type	Label
InkHighlighter	toggleButton	Highlighter
PhoneticGuideMenu	splitButton	Phonetic Guide
MarginsShowHide	checkBox	Show Margins
_3DSurfaceMaterialGalleryClassic	gallery	Surface
_3DExtrusionDepthGalleryClassic	gallery	Depth
GroupHeaderFooter	group	Header & Footer
FunctionsCubeInsertGallery	gallery	Cube
FunctionsEngineeringInsertGallery	gallery	Engineering
ThemeSaveCurrent	button	Save Current Theme...
ThemesGallery	gallery	Themes
ChartResetToMatchStyle	button	Reset to Match Style
Chart3DView	button	3-D Rotation...
ObjectSizeAndPropertiesDialog	button	Size and Properties...
ShapeConvertToFreeform	button	Convert to Freeform
ReflectionGallery	gallery	Reflection
PictureRecolorGallery	gallery	Recolor
SmartArtPromote	button	Promote
SmartArtDemote	button	Demote
TabPivotChartToolsAnalyze	tab	Analyze
GroupPivotChartShowOrHide	group	Show/Hide
GroupPivotChartData	group	Data
GroupPivotChartActiveField	group	Active Field
PivotChartFilterShow	toggleButton	PivotChart Filter
ChartTitleOptionsDialog	button	More Title Options...
ChartLegendOptionsDialogDialog	button	More Legend Options...
ChartDataLabelDialog	button	More Data Label Options...
ChartPrimaryHorizontalAxisTitleOptionsDialog	button	More Primary Horizontal Axis Title Options...
ChartPrimaryVerticalAxisTitleOptionsDialog	button	More Primary Vertical Axis Title Options...

idMso	Control Type	Label
ChartSecondaryHorizontalAxisTitleOptionsDialog	button	More Secondary Horizontal Axis Title Options...
ChartSecondaryVerticalAxisTitleOptionsDialog	button	More Secondary Vertical Axis Title Options...
ChartDepthAxisTitleOptionsDialog	button	More Depth Axis Title Options...
ChartPrimaryHorizontalGridlinesOptionsDialog	button	More Primary Horizontal Gridlines Options...
ChartPrimaryVerticalGridlinesOptionsDialog	button	More Primary Vertical Gridlines Options...
ChartSecondaryHorizontalGridlinesOptionsDialog	button	More Secondary Horizontal Gridlines Options...
ChartSecondaryVerticalGridlinesOptionsDialog	button	More Secondary Vertical Gridlines Options...
ChartDepthGridlinesOptionsDialog	button	More Depth Gridlines Options...
ChartPrimaryHorizontalAxisOptionsDialog	button	More Primary Horizontal Axis Options...
ChartPrimaryVerticalAxisOptionsDialog	button	More Primary Vertical Axis Options...
ChartSecondaryHorizontalAxisOption	button	More Secondary Horizontal Axis Options...
ChartSecondaryVerticalAxisOptionsDialog	button	More Secondary Vertical Axis Options...
ChartDepthAxisOptionsDialog	button	More Depth Axis Options...
ChartDataTableOptionsDialog	button	More Data Table Options...
ChartTrendlineOptionsDialog	button	More Trendline Options...
ChartErrorBarsOptionsDialog	button	More Error Bars Options...
ChartUpDownBarsOptionsDialog	button	More Up/Down Bars Options...
ChartPlotAreaOptionsDialog	button	More Plot Area Options...
ChartWallOptionsDialog	button	More Walls Options...
ChartFloorOptionsDialog	button	More Floor Options...
ChartSecondaryHorizontalAxisTitle	gallery	Secondary Horizontal Axis Title
ChartSecondaryVerticalAxisTitle	gallery	Secondary Vertical Axis Title
ChartSecondaryHorizontalGridlines	gallery	Secondary Horizontal Gridlines
ChartSecondaryVerticalGridlines	gallery	Secondary Vertical Gridlines
ChartSecondaryHorizontalAxis	gallery	Secondary Horizontal Axis

idMso	Control Type	Label
ChartSecondaryVerticalAxis	gallery	Secondary Vertical Axis
GroupAddInsCustomToolbars	group	Custom Toolbars
ConditionalFormattingMenu	menu	Conditional Formatting
TabPivotChartToolsDesign	tab	Design
TabPivotChartToolsLayout	tab	Layout
TabPivotChartToolsFormat	tab	Format
ObjectBringToFrontMenu	splitButton	Bring to Front
ObjectSendToBackMenu	splitButton	Send to Back
ObjectsGroupMenu	menu	Group
SignatureLineInsertMenu	splitButton	Signature Line
FileSaveAsExcel97_2003	button	Excel 97-2003 Workbook
TextBoxInsertExcel	toggleButton	Text Box
FileSaveAsMenu	splitButton	Save As Other Format
FilePrintMenu	splitButton	Preview and Print
FilePermissionRestrictMenu	menu	Restrict Permission
InsertCellstMenu	splitButton	Insert
PivotTableInsertMenu	splitButton	PivotTable
OutlineGroupMenu	splitButton	Group
OutlineUngroupMenu	splitButton	Ungroup
FormulaMoreFunctionsMenu	menu	More Functions
DocumentPanelTemplate	button	Document Panel
GroupModify	group	Modify
ViewGridlinesToggleExcel	toggleButton	View Gridlines
BevelShapeGallery	gallery	Bevel
_3DBevelPictureTopGallery	gallery	Bevel
EditLinks	button	Edit Links
GlowColorPicker	gallery	More Glow Colors
RecolorColorPicker	gallery	More Variations
GlowColorMoreColorsDialog	button	More Colors...

idMso	Control Type	Label
PictureRecolorMoreColorsDialog	button	More Colors...
SmartArtAddBullet	button	Add Bullet
PictureChange	button	Change Picture...
GroupWordArtStyles	group	WordArt Styles
TextFillColorPicker	gallery	Text Fill
TextOutlineColorPicker	gallery	Text Outline
TextOutlineColorMoreColorsDialog	button	More Outline Colors...
TextEffectsMenu	menu	Text Effects
TextStylesGallery	gallery	Quick Styles
WordArtClear	button	Clear WordArt
TextPictureFill	button	Picture...
TextFillGradientGallery	gallery	Gradient
TextFillMoreGradientsDialog	button	More Gradients...
TextFillTextureGallery	gallery	Texture
TextOutlineDashesGallery	gallery	Dashes
TextOutlineMoreLinesDialog	button	More Lines...
TextOutlineWeightGallery	gallery	Weight
TextEffectShadowGallery	gallery	Shadow
TextEffectsMoreShadowsDialog	button	Shadow Options...
TextEffectsBevelMore3DOptionsDialog	button	3-D Options...
TextEffects3DRotationGallery	gallery	3-D Rotation
TextEffects3DRotationOptionsDialog	button	3-D Rotation Options...
TextEffectGlowGallery	gallery	Glow
TextGlowColorPicker	gallery	More Glow Colors
TextGlowColorMoreColorsDialog	button	More Colors...
TextReflectionGallery	gallery	Reflection
ShapeEffectsMenu	menu	Shape Effects
PivotTableSubtotalsDoNotShow	button	Do Not Show Subtotals
PivotTableSubtotalsOnBottom	button	Show all Subtotals at Bottom of Group

idMso	Control Type	Label
PivotTableSubtotalsOnTop	button	Show all Subtotals at Top of Group
PivotTableGrandTotalsOffForRowsAndColumns	button	Off for Rows and Columns
PivotTableGrandTotalsOnForRowsAndColumns	button	On for Rows and Columns
PivotTableGrandTotalsOnForRowsOnly	button	On for Rows Only
PivotTableGrandTotalsOnForColumnsOnly	button	On for Columns Only
PivotTableBlankRowsInsert	button	Insert Blank Line after Each Item
PivotTableBlankRowsRemove	button	Remove Blank Line after Each Item
GroupChartCurrentSelection	group	Current Selection
GroupChartLabels	group	Labels
AlignTopExcel	toggleButton	Top Align
AlignMiddleExcel	toggleButton	Middle Align
AlignBottomExcel	toggleButton	Bottom Align
BevelTextGallery	gallery	Bevel
PictureCorrectionsDialog	button	Picture Corrections Options...
GroupTableStylesExcel	group	Table Styles
ConditionalFormattingNewRule	button	New Rule...
SmartArtAddShapeSplitMenu	splitButton	Add Shape Options
ViewRulerExcel	checkBox	Ruler
GroupInkFormat	group	Format
InkColorPicker	gallery	Color
BorderColorPickerExcel	gallery	Line Color
GroupSmartArtShapes	group	Shapes
GroupInsertText	group	Text
ShapeOutlineColorPicker	gallery	Picture Border
TableDeleteRowsAndColumnsMenu	splitButton	Delete
AccountingFormatMenu	splitButton	
GroupChartProperties	group	Properties
PivotTableEditDataSource	splitButton	Edit Data Source
FileExcelServicesOptions	button	Excel Services Options

idMso	Control Type	Label
TableExportMenu	menu	Export
TableExportTableToVisioPivotDiagram	button	Export Table to Visio PivotDiagram...
PasteMenu	splitButton	Paste
GroupPictureStyles	group	Picture Styles
PictureStylesGallery	gallery	Quick Styles
GroupInsertChartsExcel	group	Charts
ChartTypeColumnInsertGallery	gallery	Column
ChartTypeLineInsertGallery	gallery	Line
ChartTypePieInsertGallery	gallery	Pie
ChartTypeBarInsertGallery	gallery	Bar
ChartTypeAreaInsertGallery	gallery	Area
ChartTypeXYScatterInsertGallery	gallery	Scatter
ChartTypeOtherInsertGallery	gallery	Other Charts
ChartTypeAllInsertDialog	button	All Chart Types...
PivotChartClearMenu	menu	Clear
PictureEffectsShadowGallery	gallery	Shadow
PictureEffectsGlowGallery	gallery	Glow
PictureEffectsSoftEdgesGallery	gallery	Soft Edges
PictureReflectionGallery	gallery	Reflection
PictureRotationGallery	gallery	3-D Rotation
InkToolsClose	button	Close Ink Tools
SheetRowsInsert	button	Insert Sheet Rows
SheetColumnsInsert	button	Insert Sheet Columns
SheetRowsDelete	button	Delete Sheet Rows
SheetColumnsDelete	button	Delete Sheet Columns
GroupViewShowHide	group	Show/Hide
GroupWindow	group	Window
GroupWorkbookViews	group	Workbook Views
ViewHeadings	checkBox	View

idMso	Control Type	Label
RefreshAllMenu	splitButton	Refresh
HideAndUnhideMenu	menu	Hide & Unhide
DataValidationMenu	splitButton	Data Validation
FileDocumentEncrypt	toggleButton	Encrypt Document
WordArtFormatDialog	button	Format Text Effects...
ObjectRotationOptionsDialog	button	More Rotation Options...
MoreTextureOptions	button	More Textures...
TextFillColorMoreColorsDialog	button	More Fill Colors...
BorderTopNoToggle	button	Top Border
BorderBottomNoToggle	button	Bottom Border
BorderLeftNoToggle	button	Left Border
BorderRightNoToggle	button	Right Border
WindowSplitToggle	toggleButton	Split
FileEmailAsPdfEmailAttachment	button	E-mail as PDF Attachment
FileEmailAsXpsEmailAttachment	button	E-mail as XPS Attachment
GroupPrintPreviewZoom	group	Zoom
PictureEffectsMenu	menu	Picture Effects
PictureShapeGallery	gallery	Change Shape
GroupChartBackground	group	Background
GroupChartAnalysis	group	Analysis
ZoomToSelection	button	Zoom to Selection
GridlinesExcel	checkBox	View
UnmergeCells	button	Split Cells...
MenuPublish	menu	Publish
ViewSideBySide	toggleButton	View Side by Side
FileSaveAsOtherFormats	button	Save As
FileSaveAsExcelXlsx	button	Excel Workbook
FileSaveAsExcelXlsxMacro	button	Excel Macro-Enabled Workbook
FileSaveAsExcelXlsb	button	Excel Binary Workbook

idMso	Control Type	Label
PasteAsPictureMenu	menu	As Picture
GroupPivotActions	group	Actions
PivotTableSelectFlyout	menu	Select
ZoomCurrent100	button	100%
TextFillMoreTextures	button	More Textures...
GroupMacros	group	Macros
PlayMacro	button	Macros
MenuMacros	splitButton	Macros
AdvertisePublishAs	button	Find add-ins for other file formats
UpgradeWorkbook	button	Convert
ReviewProtectWorkbookMenu	menu	Protect Workbook
ReviewRestrictEditing	toggleButton	Protect Structure and Windows
AlternativeText	button	Size and Properties...
ThemeBrowseForThemes	button	Browse for Themes...
FileCheckOutDiscard	button	Discard Check Out
MdiChildSystemMenu	menu	Document

3.1.3 PowerPoint 2007

idMso	Control Type	Label
Spelling	button	Spelling...
FileSave	button	Save
FilePrint	button	Print
TableInsert	button	Insert Table...
ChartInsert	button	Chart...
FileNew	button	New
Copy	button	Copy
Cut	button	Cut
Paste	button	Paste
FileOpen	button	Open

idMso	Control Type	Label
Clear	button	Clear
Superscript	toggleButton	Superscript
Subscript	toggleButton	Subscript
FileClose	button	Close
FormatPainter	toggleButton	Format Painter
FilePrintPreview	toggleButton	Print Preview
PickUpStyle	button	Pick Up Style
PasteApplyStyle	button	Apply Style
Bold	toggleButton	Bold
Italic	toggleButton	Italic
Underline	toggleButton	Underline
AlignLeft	toggleButton	Align Left
AlignRight	toggleButton	Align Right
AlignCenter	toggleButton	Center
AlignJustify	toggleButton	Justify
Undo	gallery	Undo
Redo	gallery	Redo
OutlinePromote	button	Promote
OutlineDemote	button	Demote
OutlineMoveUp	button	Move Up
OutlineMoveDown	button	Move Down
OutlineExpand	button	Expand
OutlineCollapse	button	Collapse
TextBoxInsert	toggleButton	Text Box
FindDialog	button	Find...
BorderTop	toggleButton	Top Border
BorderBottom	toggleButton	Bottom Border
BorderLeft	toggleButton	Left Border
BorderRight	toggleButton	Right Border

idMso	Control Type	Label
BorderInside	toggleButton	Inside Borders
BorderOutside	toggleButton	Outside Borders
BorderNone	toggleButton	No Border
ObjectsGroup	button	Group
ObjectsUngroup	button	Ungroup
ObjectBringToFront	button	Bring to Front
ObjectSendToBack	button	Send to Back
ObjectBringForward	button	Bring Forward
ObjectSendBackward	button	Send Backward
ViewFullScreenView	button	Full Screen
ViewRulerPowerPoint	checkBox	Ruler
ObjectsSelect	toggleButton	Select Objects
MacroPlay	button	Macros
ObjectFlipHorizontal	button	Flip Horizontal
ObjectFlipVertical	button	Flip Vertical
ObjectRotateRight90	button	Rotate Right 90°
ObjectRotateLeft90	button	Rotate Left 90°
GroupDrawing	group	Drawing
ObjectEditPoints	toggleButton	Edit Points
GridSettings	button	Grid Settings...
PropertySheet	button	Property Sheet
OutlineShowTextFormatting	toggleButton	Show Text Formatting
Strikethrough	toggleButton	Strikethrough
WindowsArrangeAll	button	Arrange All
WindowNew	button	New Window
SymbolInsert	button	Symbol...
ReplaceDialog	button	Replace...
PagePrevious	button	Previous Page
PageNext	button	Next Page

idMso	Control Type	Label
TextBoxInsertVertical	toggleButton	Vertical Text Box
RedoOrRepeat	button	Redo
ObjectsRegroup	button	Regroup
FontSizeIncrease	button	Increase Font Size
FontSizeDecrease	button	Decrease Font Size
OleObjectctInsert	button	Object...
SnapToGrid	toggleButton	Snap to Grid
FindNext	button	Find Next
PasteDuplicate	button	Duplicate
SlideNew	button	New Slide
ClipArtInsert	toggleButton	Clip Art...
CreateHandoutsInWord	button	Create Handouts in Microsoft Office Word
Shadow	toggleButton	Shadow
ObjectRotateFree	button	Free Rotate
ShapesMoreShapes	button	More AutoShapes
SlideMasterMasterLayout	button	Slide Layout...
CollapseAll	button	Collapse All
OutlineExpandAll	button	Expand All
CombineCharacters	toggleButton	Yoko-Gumi
SlideHide	toggleButton	Hide Slide
AnimationCustom	toggleButton	Custom Animation...
PictureCrop	toggleButton	Crop
SlideShowRehearseTimings	button	Rehearse Timings
ViewSlideView	toggleButton	Slide
ViewOutlineView	toggleButton	Outline
ViewSlideSorterView	toggleButton	Slide Sorter
ViewNotesPageView	toggleButton	Notes Page
ViewSlideShowView	button	Slide Show
ViewSlideMasterView	toggleButton	Slide Master

idMso	Control Type	Label
FileSaveAs	button	Save As
AdvancedFileProperties	button	View Document Properties...
PasteSpecialDialog	button	Paste Special...
SelectAll	button	Select All
FileLinksToFiles	button	Edit Links to Files
HeaderFooterInsert	button	Header & Footer...
DateAndTimeInsert	button	Date & Time...
NumberInsert	button	Number...
BordersShadingDialog	button	Borders and Shading...
BulletsAndNumberingBulletsDialog	button	Bullets and Numbering...
SetLanguage	button	Set Language...
AutoCorrect	button	AutoCorrect Options...
MergeCells	button	Merge Cells
SplitCells	button	Split Cells...
TableRowSelect	button	Select Row
TableColumnSelect	button	Select Column
TableSelect	button	Select Table
ShowClipboard	button	Office Clipboard...
OutlookTaskCreate	button	Create Microsoft Office Outlook Task
WindowMinimize	button	Minimize
WindowRestore	button	Restore
WindowClose	button	Close
PrintPreviewClose	button	Close Print Preview
ZoomDialog	button	Zoom...
About	button	About
PictureInsertFromFilePowerPoint	button	Picture...
ExchangeFolder	button	Exchange Folder...
AddInManager	button	Add-Ins...
ChartEditDataSource	button	Select Data...

idMso	Control Type	Label
WindowMoreWindowsDialog	toggleButton	More Windows...
ObjectEditDialog	button	Object...
ObjectFormatDialog	button	Object...
Help	button	Help
WebGoBack	button	Back
WebGoForward	button	Forward
SmartArtInsert	button	SmartArt...
ShapeRerouteConnectors	toggleButton	Reroute Connectors
ObjectNudgeUp	button	Up
ObjectNudgeDown	button	Down
ObjectNudgeLeft	button	Left
ObjectNudgeRight	button	Right
ShapeStraightConnector	toggleButton	Straight Connector
ShapeElbowConnector	toggleButton	Elbow Connector
ObjectFillMoreColorsDialog	button	More Fill Colors...
ObjectBorderOutlineColorMoreColorsDialog	button	More Outline Colors...
LineStyleDialog	button	More Lines...
ArrowsMore	button	More Arrows...
WordArtVerticalText	button	Vertical Text
ContrastMore	button	More Contrast
ContrastLess	button	Less Contrast
BrightnessMore	button	More Brightness
BrightnessLess	button	Less Brightness
ShadowNudgeUpClassic	button	Nudge Shadow Up
ShadowNudgeDownClassic	button	Nudge Shadow Down
ShadowNudgeLeftClassic	button	Nudge Shadow Left
ShadowNudgeRightClassic	button	Nudge Shadow Right
ShapeRectangle	toggleButton	Rectangle
ShapeRoundedRectangle	toggleButton	Rounded Rectangle

idMso	Control Type	Label
ShapeIsoscelesTriangle	toggleButton	Isosceles Triangle
ShapeOval	toggleButton	Oval
ShapeLeftBrace	toggleButton	Left Brace
ShapeRightBrace	toggleButton	Right Brace
ShapeArc	toggleButton	Arc
ShapeRightArrow	toggleButton	Right Arrow
ShapeDownArrow	toggleButton	Down Arrow
ShapeRoundedRectangularCallout	toggleButton	Rounded Rectangular Callout
ShapeStar	toggleButton	5-Point Star
PictureReset	button	Reset Picture
SnapToShapes	toggleButton	Snap to Shape
ViewVisualBasicCode	button	View Code
MasterViewClose	button	Close
HyperlinkInsert	button	Hyperlink...
ReviewNewComment	button	New Comment
VisualBasic	button	Visual Basic
BordersAll	toggleButton	All Borders
SlideBackgroundFormatDialog	button	Format Background...
TableDrawBorderPenStyle	dropDown	Pen Style
Font	comboBox	Font:
FontSize	comboBox	Font Size:
ZoomClassic	gallery	Zoom:
DocumentLocation	comboBox	Address:
InsertTab	button	Tab
WindowsCascade	button	Cascade
BorderInsideHorizontal	toggleButton	Inside Horizontal Border
BorderInsideVertical	toggleButton	Inside Vertical Border
BorderDiagonalDown	toggleButton	Diagonal Down Border
BorderDiagonalUp	toggleButton	Diagonal Up Border

idMso	Control Type	Label
TextDirectionLeftToRight	toggleButton	Left-to-Right
TextDirectionRightToLeft	toggleButton	Right-to-Left
ActiveXCheckBox	button	Check Box
ActiveXTextBox	button	Text Box
ActiveXButton	button	Command Button
ActiveXRadioButton	button	Option Button
ActiveXListBox	button	List Box
ActiveXComboBox	button	Combo Box
ActiveXToggleButton	button	Toggle Button
ActiveXSpinButton	button	Spin Button
ActiveXScrollBar	button	Scroll Bar
ActiveXLabel	button	Label
OleConvert	button	Convert...
ReviewEditComment	button	Edit Comment
TableDrawTable	toggleButton	Draw Table
TableEraser	toggleButton	Eraser
TableCellAlignTop	toggleButton	Align Top
TableCellAlignCenterVertically	toggleButton	Center Vertically
TableCellAlignBottom	toggleButton	Align Bottom
TableColumnsDistribute	button	Distribute Columns
TableRowsDistribute	button	Distribute Rows
ActiveXImage	button	Image
TableDeleteRows	button	Delete Rows
TableDeleteColumns	button	Delete Columns
ShadowOnOrOffClassic	button	Shadow On/Off
ObjectSetShapeDefaults	button	Set AutoShape Defaults
FileSendAsAttachment	button	E-mail
FileNewDefault	button	New
FilePrintQuick	button	Quick Print

idMso	Control Type	Label
PictureInsertFromFile	button	Picture...
TableDrawBorderPenWeight	dropDown	Pen Weight
TableShowGridlines	toggleButton	View Gridlines
TableBorderPenColorPicker	gallery	Pen Color
ShapeStraightConnectorArrow	toggleButton	Straight Arrow Connector
ShapeElbowConnectorArrow	toggleButton	Elbow Arrow Connector
SlideDelete	button	Delete
ViewHandoutMasterView	toggleButton	Handout Master
ViewNotesMasterView	toggleButton	Notes Master
SlidesReuseSlides	toggleButton	Reuse Slides...
SlidesFromOutline	button	Slides from Outline...
MovieFromClipOrganizerInsert	button	Movie from Organizer...
MovieFromFileInsert	button	Movie from File...
SoundInsertFromClipOrganizer	button	Sound from Clip Organizer...
SoundInsertFromFile	button	Sound from File...
CDAudioPlayTrack	button	Play CD Audio Track...
FontsReplaceFonts	button	Replace Fonts...
ChangeCaseToggle	button	Toggle Case
BlackAndWhiteAutomatic	toggleButton	B & W Automatic
BlackAndWhiteBlack	toggleButton	B & W
BlackAndWhiteBlackWithGrayscaleFill	toggleButton	B & W Black with Grayscale Fill
BlackAndWhiteBlackWithWhiteFill	toggleButton	B & W Black with White Fill
BlackAndWhiteDontShow	toggleButton	B & W Don't Show
BlackAndWhiteGrayWithWhiteFill	toggleButton	B & W Gray with White Fill
BlackAndWhiteGrayscale	toggleButton	B & W Grayscale
BlackAndWhiteInverseGrayscale	toggleButton	B & W Inverse Grayscale
BlackAndWhiteWhite	toggleButton	B & W White
BlackAndWhiteLightGrayscale	toggleButton	B & W Light Grayscale
RecordNarration	button	Record Narration

idMso	Control Type	Label
SlideShowSetUpDialog	button	Set Up Slide Show...
PasteAsHyperlink	button	Paste as Hyperlink
ParagraphDistributed	toggleButton	Distributed
CharacterFormattingReset	button	Reset Character Formatting
PictureSetTransparentColor	toggleButton	Set Transparent Color
SlideShowCustom	button	Custom Slide Show
WindowFitToPage	button	Fit to Page
SoundRecord	button	Record Sound...
DuplicateSelectedSlides	button	Duplicate Selected Slides
ActionInsert	button	Action
SlideShowPreviousSlide	button	Previous
SlideShowNextSlide	button	Next
LinkBreak	button	Break Link
LinkChange	button	Change Link
LinksUpdate	button	Update Links
BaselineLower	button	Lower Baseline
BaselineRaise	button	Raise Baseline
SlideShowInAWindow	button	Slide Show in a Window
HangulHanjaConversionPowerPoint	button	Hangul Hanja Conversion
SlidesPerPage2Slides	toggleButton	2 Slides
SlidesPerPage3Slides	toggleButton	3 Slides
SlidesPerPage6Slides	toggleButton	6 Slides
SlidesPerPageSlideOutline	toggleButton	Slide Outline
GoToProperty	button	Go To...
IndentIncrease	button	Increase Indent
IndentDecrease	button	Decrease Indent
MoviePlay	button	Preview
SlidesPerPage4Slides	toggleButton	4 Slides
SlidesPerPage9Slides	toggleButton	9 Slides

idMso	Control Type	Label
MacroSecurity	button	Macro Security
WebPagePreview	button	Web Page Preview
TableInsertDialog	button	Table...
TableInsertRowsAbove	button	Insert Above
TableInsertRowsBelow	button	Insert Below
TableInsertColumnsLeft	button	Insert Left
TableInsertColumnsRight	button	Insert Right
ComAddInsDialog	button	COM Add-Ins...
ViewNormalViewPowerPoint	toggleButton	Normal
WebOptionsDialog	button	Web Options...
ViewDirectionLeftToRight	toggleButton	Left-to-Right
ViewDirectionRightToLeft	toggleButton	Right-to-Left
NextPane	button	Next Pane
WindowMoveSplit	button	Move Split
TableSetLeftToRight	toggleButton	Set Left-to-Right Table
TableSetRightToLeft	toggleButton	Set Right-to-Left Table
SlideShowResumeShow	button	Resume Slide Show
ObjectsMultiSelect	button	Select Multiple Objects
FontColorMoreColorsDialogPowerPoint	button	More Colors...
DrawingCanvasFit	button	Fit
DrawingCanvasResize	button	Resize
ViewBackToColorView	toggleButton	Back To Color View
ViewDisplayInGrayscale	toggleButton	Grayscale
ViewDisplayInHighContrast	toggleButton	High Contrast
ViewDisplayInPureBlackAndWhite	toggleButton	Pure Black and White
PrintWhat	dropDown	Print What
DrawingCanvasExpand	button	Expand
SlidesPerPage1Slide	toggleButton	1 Slide
SlideMasterPreserveMaster	toggleButton	Preserve

idMso	Control Type	Label
SlideMasterRenameMaster	button	Rename
OutlineThumbnailsShowHide	button	Show Outline
BulletsAndNumberingNumberingDialog	button	Bullets and Numbering...
FileCheckOut	button	Check Out
FileCheckIn	button	Check In
PageOrientationLandscape	toggleButton	Landscape
PageOrientationPortrait	toggleButton	Portrait
SlideReset	button	Reset
PicturesCompress	button	Compress Pictures...
ReviewDeleteCommentPowerPoint	button	Delete
ReviewNextCommentPowerPoint	button	Next
ReviewPreviousCommentPowerPoint	button	Previous
ReviewShowOrHideMarkup	toggleButton	Show Markup
ReviewDeleteAllMarkupOnSlide	button	Delete All Markup on the Current Slide
Translate	button	Translate...
ViewGridlinesPowerPoint	checkBox	View Gridlines
PhotoAlbumInsert	button	New Photo Album...
PhotoAlbumEdit	button	Edit Photo Album...
DrawingCanvasScale	button	Scale Drawing
ResearchPane	toggleButton	Research...
FileInternetFax	button	Internet Fax
FilePackageForCD	button	Package for CD
FileVersionHistory	button	View Version History
InkColorMoreColorsDialog	button	More Ink Colors...
ContactUs	button	Contact Us...
FilePermissionUnrestricted	toggleButton	Unrestricted Access
FilePermissionDoNotDistribute	toggleButton	Restricted Access
FilePermissionView	button	View Permission
Thesaurus	button	Thesaurus...

idMso	Control Type	Label
InkingStart	button	Start Inking
CheckForUpdates	button	Check for Updates
InkEraser	toggleButton	Eraser
FilePermissionRestrictAs	button	Manage Credentials
ThemeBrowseForThemesPowerPoint	button	Browse for Themes...
SlideMasterInsertLayout	button	Insert Layout
FileViewDigitalSignatures	toggleButton	View Signatures
FileWorkflowTasks	button	View Workflow Tasks
FileStartWorkflow	button	Workflows
SlideThemesGallery	gallery	Themes
LabelInsert	button	Label
BarcodeInsert	button	Barcode
ChartStylesGallery	gallery	Quick Styles
ChartLayoutGallery	gallery	Quick Layout
ChartSaveTemplates	button	Save As Template
ChartAxisTitles	menu	Axis Titles
ChartAxes	menu	Axes
ChartGridlines	menu	Gridlines
ChartFormatSelection	button	Format Selection
ChartElementSelector	comboBox	Chart Elements
SlideShowFromCurrent	button	From Current Slide
BulletsGallery	gallery	Bullets
NumberingGallery	gallery	Numbering
LineSpacingGalleryPowerPoint	gallery	Line Spacing
SlideNewGallery	gallery	New Slide
SlideLayoutGallery	gallery	Layout
TabPictureToolsFormat	tab	Format
TabDrawingToolsFormat	tab	Format
ShapesInsertGallery	gallery	Shapes

idMso	Control Type	Label
ShapeChangeShapeGallery	gallery	Change Shape
ShapeFillTextureGallery	gallery	Texture
ShapeStylesGallery	gallery	Quick Styles
PageOrientationGallery	menu	Orientation
FileServerTasksMenu	menu	Server
FileSendMenu	menu	Send
TabInsert	tab	Insert
TabView	tab	View
GroupFont	group	Font
GroupParagraph	group	Paragraph
GroupProofing	group	Proofing
GroupInsertIllustrations	group	Illustrations
GroupShapes	group	Insert Shapes
GroupPageSetup	group	Page Setup
GroupComments	group	Comments
GroupPictureSize	group	Size
GroupDrawBorders	group	Draw Borders
TabDesign	tab	Design
TabAnimations	tab	Animations
TabSlideShow	tab	Slide Show
GroupSlides	group	Slides
GroupArrange	group	Arrange
GroupInsertMediaClips	group	Media Clips
GroupSlideThemes	group	Themes
GroupBackground	group	Background
GroupPreview	group	Preview
GroupAnimations	group	Animations
GroupTransitionToThisSlide	group	Transition to This Slide
GroupSlideShowStart	group	Start Slide Show

idMso	Control Type	Label
GroupSlideShowSetup	group	Set Up
GroupShapeStyles	group	Shape Styles
TabReview	tab	Review
GroupChartLayouts	group	Chart Layouts
GroupChartStyles	group	Chart Styles
GroupChartAxes	group	Axes
GroupChartShapes	group	Insert
ObjectEffectPresetGallery	gallery	Preset
PictureEffectsPresetGallery	gallery	Preset
_3DRotationGallery	gallery	3-D Rotation
TabSmartArtToolsDesign	tab	Design
TabSmartArtToolsFormat	tab	Format
TabChartToolsDesign	tab	Design
TabChartToolsLayout	tab	Layout
TabChartToolsFormat	tab	Format
ShapeFillColorPicker	gallery	Shape Fill
OutlineColorPicker	gallery	Picture Border
FileDocumentInspect	button	Inspect Document
ClearFormatting	button	Clear Formatting
GroupControls	group	Controls
GroupZoom	group	Zoom
FilePublishSlides	button	Publish Slides
SlideShowUsePresenterView	checkBox	Use Presenter View
ArrowStyleGallery	gallery	Arrows
OutlineDashesGallery	gallery	Dashes
OutlineWeightGallery	gallery	Weight
TabTableToolsLayout	tab	Layout
GroupAlignment	group	Alignment
GroupPictureTools	group	Adjust

idMso	Control Type	Label
GroupSize	group	Size
TabSlideMaster	tab	Slide Master
GroupTableStylesPowerPoint	group	Table Styles
GroupTableRowsAndColumns	group	Rows & Columns
ObjectAlignMenu	menu	Align
MovieInsert	splitButton	Movie
SoundInsertMenu	splitButton	Sound
ObjectRotateGallery	gallery	Rotate
SelectMenu	menu	Select
AnimationGallery	dropDown	Animate:
AnimationTransitionGallery	gallery	Transition Scheme
AnimationTransitionSpeedGallery	dropDown	Transition Speed:
FontColorPicker	gallery	Font Color
TableColumnsGallery	gallery	Columns
TabHome	tab	Home
ChartTitle	gallery	Chart Title
ChartPrimaryHorizontalAxisTitle	gallery	Primary Horizontal Axis Title
ChartPrimaryVerticalAxisTitle	gallery	Primary Vertical Axis Title
ChartDepthAxisTitle	gallery	Depth Axis Title
ChartLegend	gallery	Legend
ChartDataLabel	gallery	Data Labels
ChartPrimaryHorizontalGridlines	gallery	Primary Horizontal Gridlines
ChartPrimaryVerticalGridlines	gallery	Primary Vertical Gridlines
ChartDepthGridlines	gallery	Depth Gridlines
ChartPrimaryHorizontalAxis	gallery	Primary Horizontal Axis
ChartPrimaryVerticalAxis	gallery	Primary Vertical Axis
ChartDepthAxis	gallery	Depth Axis
ChartDataTable	gallery	Data Table
ChartTrendline	gallery	Trendline

idMso	Control Type	Label
ChartErrorBars	gallery	Error Bars
ChartLines	gallery	Lines
ChartUpDownBars	gallery	Up/Down Bars
ChartPlotArea	gallery	Plot Area
ChartWall	gallery	Chart Wall
ChartFloor	gallery	Chart Floor
SmartArtAddShape	button	Add Shape
SmartArtLargerShape	button	Larger
SmartArtSmallerShape	button	Smaller
SmartArtResetGraphic	button	Reset Graphic
SmartArtTextPane	toggleButton	Text Pane
SmartArtEditIn2D	toggleButton	Edit in 2-D
SmartArtLayoutGallery	gallery	Change Layout
SmartArtMoreLayoutsDialog	button	More Layouts...
SmartArtStylesGallery	gallery	Quick Styles
SmartArtChangeColorsGallery	gallery	Change Colors
ObjectEffectSoftEdgesGallery	gallery	Soft Edges
ObjectEffectGlowGallery	gallery	Glow
GradientGallery	gallery	Gradient
ObjectEffectShadowGallery	gallery	Shadow
WordArtInsertGallery	gallery	WordArt
TextEffectTransformGallery	gallery	Transform
ThemeColorsGallery	gallery	Colors
GroupSmartArtLayouts	group	Layouts
GroupSmartArtQuickStyles	group	SmartArt Styles
GroupSmartArtCreateGraphic	group	Create Graphic
GroupSmartArtReset	group	Reset
GroupSmartArtSize	group	Size
ThemeSearchOfficeOnlinePowerPoint	button	More Themes on Microsoft Office Online...

idMso	Control Type	Label
TabAddIns	tab	Add-Ins
ObjectEditShapeMenu	menu	Edit Shape
SlideMasterContentPlaceholderInsert	button	Content
SlideMasterTextPlaceholderInsert	button	Text
SlideMasterChartPlaceholderInsert	button	Chart
SlideMasterTablePlaceholderInsert	button	Table
SlideMasterDiagramPlaceholderInsert	button	SmartArt
SlideMasterMediaPlaceholderInsert	button	Media
SlideMasterClipArtPlaceholderInsert	button	Clip Art
SlideMasterVerticalTextPlaceholderInsert	button	Text
SlideMasterShowTitle	checkBox	Title
SlideMasterShowFooters	checkBox	Footers
TableStylesGallery	gallery	Table Styles
FileSaveAsPdfOrXps	button	Publish as PDF or XPS
FileSaveAsPowerPointOpenDocumentPresentation	button	OpenDocument Presentation
MoreControlsDialog	button	More Controls...
GroupCode	group	Code
TabDeveloper	tab	Developer
SlideTransitionApplyToAll	button	Apply To All
SlideTransitionOnMouseClicked	checkBox	On Mouse Click
AnimationPreview	button	Preview
GroupEditing	group	Editing
GroupClipboard	group	Clipboard
GroupInsertTables	group	Tables
GroupInsertLinks	group	Links
GroupInsertBarcode	group	Barcode
AnimationTransitionSoundGallery	dropDown	Transition Sound:
ObjectPictureFill	button	Picture...
SlideShowFromBeginning	button	From Beginning

idMso	Control Type	Label
WindowSwitchWindowsMenuPowerPoint	menu	Switch Windows
ThemeColorsCreateNew	button	Create New Theme Colors...
ThemeFontsCreateNew	button	Create New Theme Fonts...
ShapeFillMoreGradientsDialog	button	More Gradients...
ShadowOptionsDialog	button	Shadow Options...
ObjectsAlignSelectedSmart	toggleButton	Align Selected Objects
ObjectsAlignRelativeToContainerSmart	toggleButton	Align to Slide
ObjectsAlignLeftSmart	button	Align Left
ObjectsAlignRightSmart	button	Align Right
ObjectsAlignTopSmart	button	Align Top
ObjectsAlignBottomSmart	button	Align Bottom
ObjectsAlignCenterHorizontalSmart	button	Align Center
ObjectsAlignMiddleVerticalSmart	button	Align Middle
AlignDistributeHorizontally	button	Distribute Horizontally
AlignDistributeVertically	button	Distribute Vertically
SlideShowCustomMenu	menu	Custom Slide Show
SlideShowResolutionGallery	dropDown	Resolution:
SlideShowUseRehearsedTimings	checkBox	Use Rehearsed Timings
SlideShowShowPresentationOnGallery	dropDown	Show Presentation On:
GroupMonitors	group	Monitors
ThemeFontsGallery	gallery	Fonts
ThemeEffectsGallery	gallery	Effects
FileProperties	toggleButton	Properties
TabPrintPreview	tab	Print Preview
GroupPrintPreviewPrint	group	Print
GroupPrintPreviewPreview	group	Preview
TabSoundToolsOptions	tab	Options
TabMovieToolsOptions	tab	Options
GroupPlay	group	Play

idMso	Control Type	Label
GroupMovieOptions	group	Movie Options
GroupSoundOptions	group	Sound Options
MediaClipToolsHideDuringShow	checkBox	Hide During Show
MediaClipLoopUntilStopped	checkBox	Loop Until Stopped
SoundPlaySoundGallery	dropDown	Play Sound:
SlideShowVolume	gallery	Slide Show Volume
MoviePlayFullScreen	checkBox	Play Full Screen
MovieRewindAfterPlaying	checkBox	Rewind Movie After Playing
TableBordersMenu	splitButton	Borders
FileCreateDocumentWorkspace	toggleButton	Create Document Workspace
FileSaveToDocumentManagementServer	button	Document Management Server
FileDocumentManagementInformation	toggleButton	Document Management Information
QuickAccessToolBarCustomization	button	Customize Quick Access Toolbar...
FilePrepareMenu	menu	Prepare
FileMarkAsFinal	toggleButton	Mark as Final
FileAddDigitalSignature	button	Add a Digital Signature
SlideBackgroundHideGraphics	checkBox	Hide Background Graphics
ChangeCaseGallery	gallery	Change Case
ReviewDeleteCommentsMenuPowerPoint	splitButton	Delete
GroupMerge	group	Merge
AlignJustifyMenu	menu	Justify
TextBoxInsertMenu	splitButton	Text Box
TextBoxInsertHorizontal	toggleButton	Horizontal Text Box
ControlProperties	button	Properties
HandoutOrientation	gallery	Handout Orientation
SlidesPerPageGallery	menu	Slides Per Page
MasterShowSlideImage	checkBox	Slide Image
MasterShowBody	checkBox	Body
MasterShowDate	checkBox	Date

idMso	Control Type	Label
MasterShowPageNumber	checkBox	Page Number
MasterShowHeader	checkBox	Header
MasterShowFooter	checkBox	Footer
TabHandoutMaster	tab	Handout Master
TabNotesMaster	tab	Notes Master
GroupPlaceholdersHandoutMaster	group	Placeholders
GroupMasterEditTheme	group	Edit Theme
GroupMasterClose	group	Close
GroupMasterEdit	group	Edit Master
GroupMasterLayout	group	Master Layout
TabGrayscale	tab	Grayscale
TabBlackAndWhite	tab	Black And White
GroupColorModeSetting	group	Change Selected Object
GroupInkSelect	group	Select
PictureBrightnessGallery	gallery	Brightness
PictureContrastGallery	gallery	Contrast
ShadingColorPicker	gallery	Shading
SmartArtAddShapeAfter	button	Add Shape After
SmartArtAddShapeBefore	button	Add Shape Before
SmartArtAddShapeAbove	button	Add Shape Above
SmartArtAddShapeBelow	button	Add Shape Below
SmartArtAddAssistant	button	Add Assistant
ThemeColorsReset	button	Reset Slide Theme Colors
ChartSwitchRowColumn	button	Switch Row/Column
ChartShowData	button	Edit Data...
ChartRefresh	button	Refresh Data
ChartChangeType	button	Change Chart Type...
GroupChartData	group	Data
GroupChartType	group	Type

idMso	Control Type	Label
GroupTableSize	group	Table Size
TableCellMarginsGallery	gallery	Cell Margins
SlideMasterVerticalContentPlaceholderInsert	button	Content (Vertical)
_3DRotationOptionsDialog	button	3-D Rotation Options...
_3DBevelOptionsDialog	button	3-D Options...
SlideBackgroundStylesGallery	gallery	Background Styles
TextDirectionGallery	gallery	Text Direction
GroupTableStyleOptionsPowerPoint	group	Table Style Options
TableStyleFirstRowPowerPoint	checkBox	Header Row
TableStyleFirstColumnPowerPoint	checkBox	First Column
TableStyleTotalRowPowerPoint	checkBox	Total Row
TableStyleLastColumnPowerPoint	checkBox	Last Column
TableStyleBandedRowsPowerPoint	checkBox	Banded Rows
TableStyleBandedColumnsPowerPoint	checkBox	Banded Columns
SelectionPane	toggleButton	Selection Pane...
SmartArtOrganizationChartLeftHanging	button	Left Hanging
SmartArtOrganizationChartRightHanging	button	Right Hanging
SmartArtOrganizationChartBoth	button	Both
SmartArtOrganizationChartStandard	button	Standard
SmartArtRightToLeft	toggleButton	Right to Left
TableCellCustomMarginsDialog	button	Custom Margins...
ViewMessageBar	checkBox	Message Bar
ShapeStylesOtherThemeFillsGallery	gallery	Other Theme Fills
SmartArtOrganizationChartMenu	menu	Layout
TabSlideMasterHome	tab	Home
TableInsertGallery	gallery	Table
AlignJustifyWithMixedLanguages	toggleButton	Justify
AlignJustifyLow	toggleButton	Justify Low
AlignJustifyThai	toggleButton	Distribute

idMso	Control Type	Label
ExcelSpreadsheetInsert	button	Excel Spreadsheet
TabCDAudioToolsOptions	tab	Options
SlideTransitionAutomaticallyAfter	checkBox	Automatically After:
SlideOrientationGallery	gallery	Slide Orientation
GroupAddInsMenuCommands	group	Menu Commands
GroupAddInsToolbarCommands	group	Toolbar Commands
GroupInk	group	Ink
TabInkToolsPens	tab	Pens
GroupInkPens	group	Pens
GroupInkClose	group	Close
InkBallpointPen	toggleButton	Ballpoint Pen
InkFeltTipPen	toggleButton	Felt Tip Pen
InkHighlighter	toggleButton	Highlighter
ThemeSaveCurrentPowerPoint	button	Save Current Theme...
TextAlignGallery	gallery	Align Text
CharacterSpacingGallery	gallery	Character Spacing
ChartResetToMatchStyle	button	Reset to Match Style
Chart3DView	button	3-D Rotation...
ObjectSizeAndPositionDialog	button	Size and Position...
ShapeConvertToFreeform	button	Convert to Freeform
TabTableToolsDesign	tab	Design
ConvertToSmartArt	gallery	Convert to SmartArt
ConvertToSmartArtMoreSmartArtGraphicsDialog	button	More SmartArt Graphics...
ReflectionGallery	gallery	Reflection
PictureRecolorGallery	gallery	Recolor
SmartArtPromote	button	Promote
SmartArtDemote	button	Demote
TableEffectsCellBevelGallery	gallery	Cell Bevel
TableBackgroundGallery	gallery	Table Background

idMso	Control Type	Label
ChartTitleOptionsDialog	button	More Title Options...
ChartLegendOptionsDialogDialog	button	More Legend Options...
ChartDataLabelDialog	button	More Data Label Options...
ChartPrimaryHorizontalAxisTitleOptionsDialog	button	More Primary Horizontal Axis Title Options...
ChartPrimaryVerticalAxisTitleOptionsDialog	button	More Primary Vertical Axis Title Options...
ChartSecondaryHorizontalAxisTitleOptionsDialog	button	More Secondary Horizontal Axis Title Options...
ChartSecondaryVerticalAxisTitleOptionsDialog	button	More Secondary Vertical Axis Title Options...
ChartDepthAxisTitleOptionsDialog	button	More Depth Axis Title Options...
ChartPrimaryHorizontalGridlinesOptionsDialog	button	More Primary Horizontal Gridlines Options...
ChartPrimaryVerticalGridlinesOptionsDialog	button	More Primary Vertical Gridlines Options...
ChartSecondaryHorizontalGridlinesOptionsDialog	button	More Secondary Horizontal Gridlines Options...
ChartSecondaryVerticalGridlinesOptionsDialog	button	More Secondary Vertical Gridlines Options...
ChartDepthGridlinesOptionsDialog	button	More Depth Gridlines Options...
ChartPrimaryHorizontalAxisOptionsDialog	button	More Primary Horizontal Axis Options...
ChartPrimaryVerticalAxisOptionsDialog	button	More Primary Vertical Axis Options...
ChartSecondaryHorizontalAxisOption	button	More Secondary Horizontal Axis Options...
ChartSecondaryVerticalAxisOptionsDialog	button	More Secondary Vertical Axis Options...
ChartDepthAxisOptionsDialog	button	More Depth Axis Options...
ChartDataTableOptionsDialog	button	More Data Table Options...
ChartTrendlineOptionsDialog	button	More Trendline Options...
ChartErrorBarsOptionsDialog	button	More Error Bars Options...
ChartUpDownBarsOptionsDialog	button	More Up/Down Bars Options...
ChartPlotAreaOptionsDialog	button	More Plot Area Options...
ChartWallOptionsDialog	button	More Walls Options...

idMso	Control Type	Label
ChartFloorOptionsDialog	button	More Floor Options...
ChartSecondaryHorizontalAxisTitle	gallery	Secondary Horizontal Axis Title
ChartSecondaryVerticalAxisTitle	gallery	Secondary Vertical Axis Title
ChartSecondaryHorizontalGridlines	gallery	Secondary Horizontal Gridlines
ChartSecondaryVerticalGridlines	gallery	Secondary Vertical Gridlines
ChartSecondaryHorizontalAxis	gallery	Secondary Horizontal Axis
ChartSecondaryVerticalAxis	gallery	Secondary Vertical Axis
GroupAddInsCustomToolbars	group	Custom Toolbars
MoviePlayAutomatically	dropDown	Play Movie:
ObjectBringToFrontMenu	splitButton	Bring to Front
ObjectSendToBackMenu	splitButton	Send to Back
ObjectsGroupMenu	menu	Group
ViewDisplayInColor	toggleButton	Color
FileSaveAsPowerPoint97_2003	button	PowerPoint 97-2003 Presentation
FileSaveAsMenu	splitButton	Save As Other Format
FilePrintMenu	splitButton	Preview and Print
FilePermissionRestrictMenu	menu	Restrict Permission
DocumentPanelTemplate	button	Document Panel
GroupModify	group	Modify
BevelShapeGallery	gallery	Bevel
_3DBevelPictureTopGallery	gallery	Bevel
TableStyleClearTable	button	Clear Table
GroupTable	group	Table
GroupTableCellSize	group	Cell Size
TableEffectsMenu	menu	Effects
GlowColorPicker	gallery	More Glow Colors
RecolorColorPicker	gallery	More Variations
GlowColorMoreColorsDialog	button	More Colors...
PictureRecolorMoreColorsDialog	button	More Colors...

idMso	Control Type	Label
SmartArtAddBullet	button	Add Bullet
TableLockAspectRatio	checkBox	Lock Aspect Ratio
SlideMasterPicturePlaceholderInsert	button	Picture
SlideMasterInsertPlaceholderMenu	splitButton	Insert Placeholder
TableBorderColorMoreColorsDialog	button	More Border Colors...
TableFillColorMoreColorsDialog	button	More Fill Colors...
PictureChange	button	Change Picture...
GroupWordArtStyles	group	WordArt Styles
TextFillColorPicker	gallery	Text Fill
TextOutlineColorPicker	gallery	Text Outline
TextOutlineColorMoreColorsDialog	button	More Outline Colors...
TextEffectsMenu	menu	Text Effects
TextStylesGallery	gallery	Quick Styles
WordArtClear	button	Clear WordArt
TextPictureFill	button	Picture...
TextFillGradientGallery	gallery	Gradient
TextFillMoreGradientsDialog	button	More Gradients...
TextFillTextureGallery	gallery	Texture
TextOutlineDashesGallery	gallery	Dashes
TextOutlineMoreLinesDialog	button	More Lines...
TextOutlineWeightGallery	gallery	Weight
TextEffectShadowGallery	gallery	Shadow
TextEffectsMoreShadowsDialog	button	Shadow Options...
TextEffectsBevelMore3DOptionsDialog	button	3-D Options...
TextEffects3DRotationGallery	gallery	3-D Rotation
TextEffects3DRotationOptionsDialog	button	3-D Rotation Options...
TextEffectGlowGallery	gallery	Glow
TextGlowColorPicker	gallery	More Glow Colors
TextGlowColorMoreColorsDialog	button	More Colors...

idMso	Control Type	Label
TextReflectionGallery	gallery	Reflection
ShapeEffectsMenu	menu	Shape Effects
TransitionSoundLoopUntilNextSound	toggleButton	Loop Until Next Sound
GroupChartCurrentSelection	group	Current Selection
GroupChartLabels	group	Labels
BevelTextGallery	gallery	Bevel
PictureCorrectionsDialog	button	Picture Corrections Options...
SmartArtAddShapeSplitMenu	splitButton	Add Shape Options
MasterNotesPageOrientation	gallery	Notes Page Orientation
GroupInkFormat	group	Format
InkColorPicker	gallery	Color
TextDirectionMoreOptionsDialog	button	More Options...
TextAlignMoreOptionsDialog	button	More Options...
ParagraphMoreColumnsDialog	button	More Columns...
SlideBackgroundReset	button	Reset Slide Background
CDAudioPlayTrackAutomatically	dropDown	Play Track:
GroupSmartArtShapes	group	Shapes
GroupInsertText	group	Text
ShapeOutlineColorPicker	gallery	Picture Border
GroupColorModeClose	group	Close
GroupPageSetupNotesMaster	group	Page Setup
GroupPageSetupHandoutMaster	group	Page Setup
GroupPlaceholdersNotesMaster	group	Placeholders
ReplaceMenu	splitButton	Replace...
TableSelectMenuPowerPoint	menu	Select
TableDeleteRowsAndColumnsMenu	menu	Delete
GroupCDAudioSetup	group	Set Up
PrintOptionsMenu	menu	Options
ReviewDeleteAllMarkupInPresentation	button	Delete All Markup in the Presentation

idMso	Control Type	Label
PasteMenu	splitButton	Paste
GroupPictureStyles	group	Picture Styles
PictureStylesGallery	gallery	Quick Styles
PictureEffectsShadowGallery	gallery	Shadow
PictureEffectsGlowGallery	gallery	Glow
PictureEffectsSoftEdgesGallery	gallery	Soft Edges
PictureReflectionGallery	gallery	Reflection
PictureRotationGallery	gallery	3-D Rotation
InkToolsClose	button	Close Ink Tools
GroupViewShowHide	group	Show/Hide
GroupWindow	group	Window
ViewGridlines	checkBox	View Gridlines
GroupPresentationViews	group	Presentation Views
GroupColorGrayscale	group	Color/Grayscale
FileDocumentEncrypt	toggleButton	Encrypt Document
WordArtFormatDialog	button	Format Text Effects...
ObjectRotationOptionsDialog	button	More Rotation Options...
MoreTextureOptions	button	More Textures...
TextFillColorMoreColorsDialog	button	More Fill Colors...
ZoomFitToWindow	button	Fit to Window
GroupPrintPreviewPageSetup	group	Page Setup
ViewDirectionMenu	menu	View Direction
FileEmailAsPdfEmailAttachment	button	E-mail as PDF Attachment
FileEmailAsXpsEmailAttachment	button	E-mail as XPS Attachment
PictureEffectsMenu	menu	Picture Effects
PictureShapeGallery	gallery	Change Shape
PhotoAlbumInsertMenu	splitButton	Photo Album...
GroupChartBackground	group	Background
GroupChartAnalysis	group	Analysis

idMso	Control Type	Label
MenuPublish	menu	Publish
FileCompatibilityCheckerPowerPoint	button	Run Compatibility Checker
TableBackgroundPictureFill	button	Picture...
UpgradePresentation	button	Convert
FileSaveAsOtherFormats	button	Save As
FileSaveAsPowerPointPptx	button	PowerPoint Presentation
FileSaveAsPowerPointPpsx	button	PowerPoint Show
FontDialogPowerPoint	button	Font...
PowerPointParagraphDialog	button	Paragraph...
PowerPointPageSetup	button	Page Setup...
ShapeQuickStylesHome	gallery	Quick Styles
GalleryAllShapesAndTextboxes	gallery	Shapes
TableTextStylesGallery	gallery	Quick Styles
GroupTextStylesTable	group	WordArt Styles
ObjectsArrangeMenu	menu	Arrange
TextFillMoreTextures	button	More Textures...
GroupMacros	group	Macros
AdvertisePublishAs	button	Find add-ins for other file formats
GroupPermission	group	Protect
ReviewProtectPresentationMenu	menu	Protect Presentation
AlternativeText	button	Size and Position...
FileCheckOutDiscard	button	Discard Check Out
MdiChildSystemMenu	menu	Document

3.2 imageMso Table

imageMso
Spelling
FileSave
FilePrint
ZoomOnePage

imageMso
ZoomPageWidth
Zoom100
TableInsert
ColumnsDialog
Numbering
Bullets
PageOrientationPortraitLandscape
OutdentClassic
IndentClassic
DrawingInsert
ChartInsert
FileNew
Copy
Cut
Paste
FileOpen
EnvelopesAndLabelsDialog
ZoomPrintPreviewExcel
PenComment
Folder
Repeat
UpArrow2
RightArrow2
DownArrow2
LeftArrow2
Clear
Breakpoint
Piggy
Superscript
Subscript

imageMso
HappyFace
UnderlineDouble
UnderlineWords
FontSizeIncreaseWord
FontSizeDecreaseWord
_0
_1
_2
_3
_4
_5
_6
_7
_8
_9
A
B
C
D
E
F
G
H
I
J
K
L
M
N
O

imageMso
P
Q
R
S
T
U
V
W
X
Y
Z
FileClose
TableAutoFormat
FormatPainter
FilePrintPreview
PickUpStyle
PasteApplyStyle
Bold
Italic
Underline
DarkShading
ParagraphMarks
AlignLeft
AlignRight
AlignCenter
AlignJustify
ContextHelp
HeaderFooterPageNumberInsert
Undo
Redo

imageMso
ControlLine
ControlRectangle
OutlinePromote
OutlineDemote
OutlineMoveUp
OutlineMoveDown
OutlineDemoteToBodyText
OutlineExpand
OutlineCollapse
TextBoxInsert
FileFind
FindDialog
TableExcelSpreadsheetInsert
AutoFormat
BorderTop
BorderBottom
BorderLeft
BorderRight
BorderInside
BorderOutside
BorderNone
MailMergeGoToFirstRecord
MailMergeGoToPreviousRecord
MailMergeGoToNextRecord
MailMergeGoToLastRecord
MailMergeMergeToDocument
MailMergeMergeToPrinter
MailMergeAutoCheckForErrors
DataFormSource
MailMergeResultsPreview

imageMso
ObjectsGroup
ObjectsUngroup
ObjectBringToFront
ObjectSendToBack
AboveText
BehindText
ObjectBringForward
ObjectSendBackward
Magnifier
PrintPreviewShrinkOnePage
MultiplePages
ViewFullScreenView
ViewRulerPowerPoint
VoiceInsert
ObjectsSelect
TableFind
MacroRecord
MacroRecorderPause
MacroPlay
ObjectFlipHorizontal
ObjectFlipVertical
ObjectRotateRight90
ObjectRotateLeft90
ShapeFreeform
GroupDrawing
ObjectEditPoints
CalloutOptions
SortUp
SortDown
TableDesign

imageMso
DataFormAddRecord
DataFormDeleteRecord
FieldsUpdate
DatabaseInsert
GridSettings
WordPicture
FormControlEditBox
FormControlCheckBox
FormControlComboBox
PropertySheet
FieldShading
ViewDraftView
Lock
AutoSum
MasterDocumentShow
MasterDocumentCreateSubdocument
MasterDocumentUnlinkSubdocument
MasterDocumentInsertSubdocument
MasterDocumentSplitSubdocuments
MasterDocumentMergeSubdocuments
MasterDocumentLockSubdocument
HeaderOrFooterShow
HeaderFooterPreviousSection
HeaderFooterNextSection
AlignDialog
MailMergeDocument
MergeOptions
MailMergeHelper
PageSetupDialog
BodyTextHide

imageMso
HeaderFooterLinkToPrevious
OutlineShowFirstLineOnly
OutlineShowTextFormatting
FontDialog
StylesDialogClassic
RoutingSlip
FootnoteInsert
MicrosoftExcel
MicrosoftAccess
Schedule
MicrosoftVisualFoxPro
MicrosoftPowerPoint
MicrosoftPublisher
MicrosoftProject
SadFace
Pushpin
Camera
FormControlButton
Calculator
ViewPrintLayoutView
FieldCodes
DropCapOptionsDialog
Strikethrough
TextSmallCaps
CellsDelete
TableRowsDelete
TableColumnsDelete
CellsInsertDialog
TableRowsInsertWord
QueryInsertColumns

imageMso
WindowsArrangeAll
MarginsAdjust
ViewGridlinesWord
SubdocumentOpen
WindowSplit
WindowNew
LegalBlackline
ReviewAcceptOrRejectChangeDialog
TextAllCaps
PictureDisassemble
SymbolInsert
ChangeCaseDialogClassic
FontSizeDecrease1Point
FontSizeIncrease1Point
Repaginate
ReplaceDialog
StartOfLine
EndOfLine
PagePrevious
PageNext
TextBoxInsertVertical
StartOfDocument
EndOfDocument
Grammar
FileCloseOrCloseAll
TextToOrFromTable
TableRowsOrColumnsOrCellsInsert
TableRowsOrColumnsOrCellsDelete
RedoOrRepeat
ObjectsRegroup

imageMso
_3DStyle
TipWizardHelp
AutoFormatChange
AddressBook
Reply
ReplyAll
Forward
MailMove
MailDelete
MessagePrevious
MessageNext
CheckNames
MailSelectNames
PrintAreaSetPrintArea
PasteFormatting
FillRight
FillDown
EqualSign
PlusSign
MinusSign
MultiplicationSign
DivisionSign
ExponentiationSign
ParenthesisLeft
ParenthesisRight
ColonSign
CommaSign
PercentSign
DollarSign
FunctionWizard

imageMso
AsianLayoutCharacterScaling
ConstrainNumeric
LightShading
AccountingFormat
PercentStyle
CommaStyle
DecimalsIncrease
DecimalsDecrease
MergeCenter
FontSizeIncrease
FontSizeDecrease
TextOrientationVertical
TextOrientationRotateUp
TextOrientationRotateDown
AlignDistributeHorizontallyClassic
ShapeScribble
ChartAreaChart
Chart3DBarChart
Chart3DColumnChart
Chart3DPieChart
ChartRadarChart
OutlineSymbolsShowHide
TableSelectVisibleCells
SelectCurrentRegion
FreezePanels
ZoomIn
ZoomOut
FormControlRadioButton
FormControlScrollBar
FormControlListBox

imageMso
TraceDependentRemoveArrows
TraceDependents
TracePrecedentsRemoveArrows
TraceRemoveAllArrows
FileUpdate
ReadOnly
AutoFilterClassic
Refresh
PivotTableFieldSettings
PivotTableShowPages
OutlineShowDetail
TraceError
OutlineHideDetail
AlignDistributeVerticallyClassic
FormControlGroupBox
FormControlSpinner
TabOrder
RunDialog
FormControlCombinationListEdit
FormControlCombinationDropDownEdit
FormControlLabel
Delete
Fish
Coffee
Heart
Diamond
Spade
Club
ViewSheetGridlines
TracePrecedents

imageMso
Info
CodeEdit
InsertDialog
ApplyFilter
DatasheetView
SortAndFilterAdvanced
ControlSubFormReport
FieldList
ViewsFormView
Grouping
AdpPrimaryKey
ControlBoundObjectFrame
ControlUnboundObjectFrame
PageBreakInsertOrRemove
PrintSetupDialog
CreateFormInDesignView
CreateQueryFromWizard
CreateReportInDesignView
MacroConditions
MacroNames
ControlToggleButton
DatabaseRelationships
TableIndexes
ViewsAdpDiagramSqlView
QueryTableNamesShowHide
QueryShowTable
QuerySelectQueryType
QueryCrosstab
QueryMakeTable
QueryUpdate

imageMso
QueryAppend
QueryDelete
QueryParameters
RecordsSaveRecord
GoToNewRecord
RowHeight
ColumnWidth
RecordsFreezeColumns
GridlinesGallery
OleObjectctInsert
ControlToolboxOutlook
SnapToGrid
SizeToFit
PageHeaderOrFooterShowHide
FormHeaderOrFooterShowHide
First10RecordsPreview
ControlSpecialEffectRaised
ControlSpecialEffectSunken
AutoDial
FindNext
PasteDuplicate
DatabasePermissions
ControlAlignToGrid
ControlSpecialEffectFlat
CreateTableInDesignView
MacroDefault
ModuleInsert
FilterToggleFilter
FilterClearAllFilters
Head

imageMso
ReminderSound
CreateModule
RelationshipsDirectRelationships
RelationshipDesignAllRelationships
ControlWizards
MergeToWord
FilterAdvancedByForm
CreateMacro
AutoFormatWizard
PrintPreviewZoomTwoPages
FilterBySelection
RecordsDeleteRecord
QueryBuilder
DatabaseDocumenter
DatabaseAnalyzePerformance
DatabaseAnalyzeTable
ObjectsAlignLeft
ObjectsAlignRight
ObjectsAlignTop
ObjectsAlignBottom
ObjectsAlignCenterHorizontal
ObjectsAlignMiddleVertical
SlideNew
ClipArtInsert
CreateHandoutsInWord
Shadow
ObjectRotateFree
ShapesMoreShapes
CopyToPersonalContacts
ParagraphSpacingIncrease

imageMso
ParagraphSpacingDecrease
SlideMasterMasterLayout
OrganizationChartInsert
CollapseAll
OutlineExpandAll
CombineCharacters
DoubleStrikethrough
QueryInsertColumn
EncryptMessage
DigitallySignMessage
CreateMailRule
ViewNormalViewExcel
ViewPageBreakPreviewView
SlideHide
AnimationCustom
PictureCrop
SlideShowRehearseTimings
ViewSlideView
ViewOutlineView
ViewSlideSorterView
ViewNotesPageView
ViewSlideShowView
ViewSlideMasterView
FileCloseAll
FileSaveAs
SaveAll
AdvancedFileProperties
DocumentTemplate
FileExit
PasteSpecialDialog

imageMso
SelectAll
GoTo
BookmarkInsert
FileLinksToFiles
ViewOnlineLayoutViewClassic
HeaderFooterInsert
FootnotesEndnotesShow
BreakInsertDialog
DateAndTimeInsert
NumberInsert
FieldInsert
CaptionInsert
CrossReferenceInsert
TextFromFileInsert
ParagraphDialog
BordersShadingDialog
TextDirectionOptionsDialog
BulletsAndNumberingBulletsDialog
AutoFormatDialog
SetLanguage
WordCount
AutoCorrect
EnvelopesAndLabels
LabelsDialog
MergeCells
SplitCells
TableRowSelect
TableColumnSelect
TableSelect
TableRepeatHeaderRows

imageMso
ConvertTextToTable
TableFormulaDialog
TableSplitTable
ShowClipboard
TechnicalSupport
ImeDictionaryUpdate
OutlookTaskCreate
WindowMinimize
WindowRestore
WindowClose
WindowSaveWorkspace
SheetDelete
ViewFormulaBar
SheetInsert
FormatCellsDialog
DataFormExcel
OutlineSubtotals
Consolidate
WindowHide
WindowUnhide
FillUp
FillLeft
ClearFormats
NameCreateFromSelection
SheetProtect
ReviewProtectWorkbook
MacroRelativeReferences
Filter
SortClear
AdvancedFilterDialog

imageMso
OutlineSettings
PrintPreviewClose
HeaderFooterClose
ZoomDialog
SortDialogClassic
ConvertTableToText
PictureInsertFromFilePowerPoint
ExchangeFolder
VisualBasicReferences
ViewCustomViews
SheetBackground
ChartEditDataSource
ChartPlacement
CalculateNow
ObjectEditDialog
ObjectFormatDialog
QueryRunQuery
ControlImage
RulerShowHide
GridShowHide
ContentsAndIndex
Help
PivotTableEnableSelection
PivotTableListFormulas
PivotTableSelectData
PivotTableSelectLabelAndData
PivotTableSelectLabel
CalculateSheet
FontColorMoreColorsDialog
FillEffects

imageMso
TextOrientationAngleCounterclockwise
TextOrientationAngleClockwise
HyperlinkOpenExcel
OpenStartPage
WebGoBack
WebGoForward
AddToFavorites
BrowsePrevious
BrowseNext
BrowseSelector
SmartArtInsert
ShapeRerouteConnectors
ObjectNudgeUp
ObjectNudgeDown
ObjectNudgeLeft
ObjectNudgeRight
ShapeCurve
ShapeStraightConnector
ShapeElbowConnector
ObjectFillMoreColorsDialog
ObjectBorderOutlineColorMoreColorsDialog
LineStylesDialog
ArrowsMore
TextEffectAlignment
TextEffectTracking
WordArtVerticalText
WordArtEvenTextHeightClassic
ContrastMore
ContrastLess
BrightnessMore

imageMso
BrightnessLess
ShadowNudgeUpClassic
ShadowNudgeDownClassic
ShadowNudgeLeftClassic
ShadowNudgeRightClassic
ObjectShadowColorMoreColorsDialog
HighImportance
LowImportance
AttachMenu
InviteAttendees
AcceptInvitation
DeclineInvitation
TentativeAcceptInvitation
NewContact
NewTask
NewAppointment
TextAlignLeft
TextAlignCenter
ShapeRectangle
ShapeRoundedRectangle
ShapeIsoscelesTriangle
ShapeOval
ShapeSmileyFace
ShapeDonut
ShapeLeftBrace
ShapeRightBrace
ShapeArc
ShapeLightningBolt
ShapeHeart
ShapeRightArrow

imageMso
ShapeLeftArrow
ShapeUpArrow
ShapeDownArrow
ShapeRoundedRectangularCallout
ShapeStar
ShapeSeal8
ShapeSeal16
ShapeSeal24
TextAlignRight
TextAlignLetterJustify
TextAlignWordJustify
TextAlignStretchJustify
PictureReset
PictureRecolorAutomatic
PictureRecolorGrayscale
PictureRecolorBlackAndWhite
PictureRecolorWashout
TextWrappingSquare
TextWrappingTight
TextWrappingNoneClassic
TextWrappingEditWrapPoints
_3DEffectsOnOffClassic
_3DTiltDownClassic
_3DTiltUpClassic
_3DTiltLeftClassic
_3DTiltRightClassic
_3DExtrusionDirectionClassic
_3DLightingClassic
_3DSurfaceMaterialClassic
_3DExtrusionDepthNoneClassic

imageMso
_3DExtrusionDepth36Classic
_3DExtrusionDepth72Classic
_3DExtrusionDepth144Classic
_3DExtrusionDepth288Classic
_3DExtrusionDepthInfinityClassic
_3DExtrusionPerspectiveClassic
_3DExtrusionParallelClassic
_3DLightingFlatClassic
_3DLightingNormalClassic
_3DLightingDimClassic
_3DSurfaceMatteClassic
_3DSurfacePlasticClassic
_3DSurfaceMetalClassic
_3DSurfaceWireFrameClassic
ObjectEditText
SnapToShapes
TextWrappingMenuClassic
WindowsArrangeIcons
PictureFormatDialog
ViewVisualBasicCode
RemoveFromCalendar
MasterViewClose
CreateShortcutMenuFromMacro
DrawingNewClassic
HyperlinkInsert
HyperlinkEdit
ReviewNewComment
ReviewPreviousComment
ReviewNextComment
ReviewDeleteComment

imageMso
ReviewShowOrHideComment
ReviewShowAllComments
PivotTableOptions
DesignMode
WordArtInsertDialogClassic
FormFieldProperties
PhoneticGuideEdit
FullScreenViewClassic
PhoneticGuideSettings
PhoneticGuideFieldShow
CircularReferences
MasterDocumentExpandOrCollapseSubdocuments
Chart3DConeChart
InternationalCurrency
ObjectsAlignCenterInFormHorizontally
ObjectsAlignCenterInFormVertically
SizeToControlWidth
SizeToControlHeight
SizeToControlHeightAndWidth
HorizontalSpacingDecrease
HorizontalSpacingIncrease
ObjectsAlignDistributeHorizontallyRemove
VerticalSpacingDecrease
VerticalSpacingIncrease
ObjectsAlignDistributeVerticallyRemove
ObjectsArrangeBottom
ObjectsArrangeRight
CancelMeeting
Private
AcceptTask

imageMso
SaveAndNew
CopyFolder
EmptyTrash
RecordInJournal
MarkAsUnread
CopyToFolder
MoveToFolder
ShapeFillColorPickerClassic
ControlLineColorPicker
VisualBasic
DoubleBottomBorder
BorderThickBottom
BorderTopAndBottom
BorderTopAndDoubleBottom
BorderTopAndThickBottom
BordersAll
BorderThickOutside
SlideBackgroundFormatDialog
AutoSummarize
ViewDocumentMap
ReviewAcceptChange
ReviewRejectChange
TableDrawBorderPenStyle
Font
FontSize
ZoomClassic
CreateMap
MergeCellsAcross
FieldChooser
MessageHeaderToggle

imageMso
MeetingRequest
NewNote
RecurrenceEdit
SendStatusReport
ImagerScan
QueryReturnGallery
SelectRecord
SelectAllRecords
TableTestValidationRules
RelationshipsClearLayout
SaveAsQuery
LoadFromQuery
DatasheetColumnRename
FileServerLinkTables
DatasheetColumnLookup
RecordsRefreshRecords
RelationshipsEditRelationships
RelationshipsHideTable
ReplicationRecoverDesignMaster
ReplicationResolveConflicts
ReplicationCreateReplica
ReplicationSynchronizeNow
SetDatabasePassword
DatabaseUserLevelSecurityWizard
DatabaseUserAndGroupAccounts
ControlSpecialEffectEtched
ControlSpecialEffectShadowed
ControlSpecialEffectChiseled
WindowsCascade
PositionFitToWindow

imageMso
BorderInsideHorizontal
BorderInsideVertical
BorderDiagonalDown
BorderDiagonalUp
MagicEightBall
TextDirectionLeftToRight
TextDirectionRightToLeft
ActiveXCheckBox
FindDialogExcel
ActiveXTextBox
ActiveXButton
ActiveXRadioButton
ActiveXListBox
ActiveXComboBox
ActiveXToggleButton
ActiveXSpinButton
ActiveXScrollBar
ActiveXLabel
ShowBcc
ShowFrom
DefinePrintStyles
TagMarkComplete
NewContactFromSameCompany
ChooseForm
RecoverInviteToMeeting
FormPublish
SkipOccurrence
RightToLeftDocument
EditQuery
DataRangeProperties

imageMso
RefreshAll
RefreshCancel
RefreshStatus
ClearAll
NewPostInThisFolder
ReplyToAttendeesWithMessage
SaveAndClose
AssignTask
Recurrence
NewMessageToContact
NewTaskForContact
NewMeetingWithContact
NewMessageToAttendees
SendUpdate
ReplyToAllAttendeesWithMessage
PostReplyToFolder
ViewAppointmentInCalendar
NewJournalEntry
NewMailMessage
CancelAcceptTask
CancelTaskAssignment
CancelDeclineTask
NewTaskRequest2
RecurrenceEditSeries
DataValidation
DataValidationCircleInvalid
ReviewShareWorkbook
ReviewTrackChanges
ReviewHighlightChanges
DatabaseQueryNew

imageMso
DataValidationClearValidationCircles
ReviewEditComment
TableDrawTable
TableEraser
TableCellAlignTop
TableCellAlignCenterVertically
TableCellAlignBottom
TableColumnsDistribute
TableRowsDistribute
FileCompactAndRepairDatabase
DatabaseMakeMdeFile
DatabaseEncodeDecode
SizeToTallest
SizeToShortest
SizeToWidest
SizeToNarrowest
QueryUnionQuery
QueryDataDefinition
QuerySqlPassThroughQuery
ClearGrid
ActiveXFrame
ActiveXImage
ShapeConnectorStyleStraight
ShapeConnectorStyleElbow
ShapeConnectorStyleCurved
WordArtEditTextClassic
FilterByResource
TableInsertCellsDialog
DeleteCells2
TableDeleteRows

imageMso
TableDeleteColumns
Organizer
ShadowOnOrOffClassic
MacroRecorderStop
FileSendAsAttachment
AutoSummaryViewByHighlight
MasterDocument
ChangeCase
ListNumFieldInsert
ParagraphSpaceBeforeNone
ParagraphSpaceBefore
ParagraphSpaceAddOrRemoveBefore
PagePreviousWord
PageNextWord
MailMergeReceipientsUseExistingList
FootnoteNextWord
EndnoteInsertWord
IndexMarkEntry
CitationMark
IndexInsert
TableOfContentsDialog
TableOfFiguresInsert
TableOfAuthoritiesInsert
TextBoxLinkCreate
TextBoxLinkBreak
TextBoxNextLinked
TextBoxPreviousLinked
CompareAndCombine
PrintOptionsMenuWord
PageNumberFormat

imageMso
CancelInvitation
ContactWebPage
AttachItem
SendAgain
EditComposePage
EditReadPage
DesignThisForm
FileNewDefault
FilePrintQuick
WindowsTileVertically
WindowsTileHorizontally
SpellingAndGrammar
CopyToPersonalCalendar
CopyToPersonalTaskList
Post
NewOfficeDocument
CreateClassModule
ControlTabControl
ControlPage
ReviewPreviousChangeClassic
ReviewNextChangeClassic
DialMenu
SendDefault
MessageProperties
PictureInsertFromFile
TableDrawBorderPenWeight
FormatObject2
TableShowGridlines
TableBorderPenColorPicker
ShowAutoShapesAndDrawingBars

imageMso
ShapeStraightConnectorArrow
ShapeElbowConnectorArrow
SourceControlAddObjects
SourceControlGetLatestVersion
SourceControlCheckOut
SourceControlCheckIn
SourceControlUndoCheckOut
SourceControlShareObjects
SourceControlShowDifferences
SourceControlShowHistory
SourceControlRun
SourceControlProperties
SourceControlCreateDatabaseFromProject
SourceControlAddDatabase
SourceControlOptions
SourceControlRefreshStatus
DatabaseMoveToSharePoint
NewPostInThisFolder3
SlideDelete
ViewHandoutMasterView
ViewNotesMasterView
SlidesReuseSlides
SlidesFromOutline
MovieFromFileInsert
SoundInsertFromFile
FontsReplaceFonts
SpeakerNotes
BlackAndWhiteAutomatic
BlackAndWhiteBlack
BlackAndWhiteBlackWithGrayscaleFill

imageMso
BlackAndWhiteBlackWithWhiteFill
BlackAndWhiteDontShow
BlackAndWhiteGrayWithWhiteFill
BlackAndWhiteGrayscale
BlackAndWhiteInverseGrayscale
BlackAndWhiteWhite
BlackAndWhiteLightGrayscale
RecordNarration
SlideShowSetUpDialog
SummarizeSlide
TextWrappingTopAndBottom
TextWrappingThrough
MoveToFolderMenu
MacroRecordOrStop
PasteAsHyperlink
ParagraphDistributed
HyphenationOptions
TableRowsOrColumnsDistribute
MergeOrSplitCells
ReviewJapaneseConsistencyChecker
ShowGridlines_HideGridlines
AutoSummaryResummarize
ViewFooter
PictureSetTransparentColor
DataRefreshAll
BorderTopWord
BorderBottomWord
BorderLeftWord
BorderRightWord
TextDirection

imageMso
SlideShowCustom
DuplicateSelectedSlides
ActionInsert
SlideMiniature
PivotTableReport
ControlSetControlDefaults
ControlActiveX
FileNewDatabase
FileOpenDatabase
FileDatabaseProperties
DatasheetColumnDelete
SelectAllAccess
QueryTotalsShowHide
MacroConvertMacrosToVisualBasic
ViewsDesignView
SlideShowInAWindow
HangulHanjaConversionPowerPoint
ReturnToTaskList
MarkTaskComplete
NewMailMessage2
PostReply
ShowGridOutlook
SizeToGridOutlook
ControlSnapToGrid
MacroSingleStep
MicrosoftOnTheWeb01
MicrosoftOnTheWeb02
MicrosoftOnTheWeb03
MicrosoftOnTheWeb04
MicrosoftOnTheWeb05

imageMso
MicrosoftOnTheWeb06
MicrosoftOnTheWeb07
MicrosoftOnTheWeb08
MicrosoftOnTheWeb09
MicrosoftOnTheWeb10
MicrosoftOnTheWeb11
MicrosoftOnTheWeb12
MicrosoftOnTheWeb13
MicrosoftOnTheWeb14
MicrosoftOnTheWeb15
MicrosoftOnTheWeb16
SendItem
SlidesPerPage2Slides
SlidesPerPage3Slides
SlidesPerPage6Slides
SlidesPerPageSlideOutline
FontConditionalFormatting
ReviewProtectAndShareWorkbook
ObjectsAlignLeftOutlook
ObjectsAlignRightOutlook
ObjectsAlignTopOutlook
ObjectsAlignBottomOutlook
ObjectsAlignCenterHorizontalOutlook
ObjectsAlignMiddleVerticalOutlook
MicrosoftOnTheWeb17
SizeToGridAccess
SizeToFitAccess
FieldsManage
HorizontalSpacingMakeEqual
VerticalSpacingMakeEqual

imageMso
ObjectsAlignToGridOutlook
SortAscendingWord
SortDescendingWord
OutlineGroup
OutlineUngroup
IndentIncreaseExcel
IndentDecreaseExcel
ControlAdvancedProperties
SaveAttachments
ViewVisualBasicCodeAccess
FrameInsertHorizontal
FormatPictureOrShapeDialogClassic
FileSendToPowerPoint
DeclineTask
AutoFormatNow
DataFormWord
ReviseContents
BulletListDefault
NumberListDefault
OutlineNumberDefault
FormatNumberDefault
FootnoteEndnoteDialog
TableInsertDialogWord
FormFieldClear
ObjectBringInFrontOfText
ObjectSendBehindText
RotateRight2
RotateLeft2
PageBreakInsertWord
BordersShadingDialogWord

imageMso
TextBoxWordClassic
WordIndent
WordOutdent
IndentIncreaseWord
IndentDecreaseWord
SelectObjects
Callout
ListMacros
ReplaceWithAutoText
FormatBackground
HangulHanjaConversion
HeaderSourceEdit
IndentIncrease
IndentDecrease
AsianLayoutFitText
AsianLayoutPhoneticGuide
AsianLayoutCombineCharacters
JapanesePostcardDialog
CharacterBorder
CharacterShading
MoviePlay
SlidesPerPage4Slides
SlidesPerPage9Slides
ViewWebLayoutView
PasteAlternative
PasteAsNestedTable
HyperlinkRemove
MacroSecurity
HorizontalLineInsert
WebPagePreview

imageMso
TableSelectCell
TableDelete
TableInsertDialog
TableRowsInsertAboveWord
TableInsertRowsAbove
TableRowsInsertBelowWord
TableInsertRowsBelow
TableColumnsInsertLeft
TableInsertColumnsLeft
TableColumnsInsertRight
TableInsertColumnsRight
TablePropertiesDialog
TableOptionsDialog
SendCopySendNow
SendCopySelectNames
SendCopyCheckNames
SendCopyOptions
SendCopyFlag
ConferenceMeetNow
SendCopySendToMailRecipient
TableOfContentsInFrame
ComAddInsDialog
FramePropertiesDialog
PivotChartInsertClassic
PivotFieldListShowHide
PictureBulletsInsert
FileNewWebPage
FileNewEmail
ToolboxAudio
ToolboxVideo

imageMso
ToolboxMarquee
CreateStoredProcedure
FileNewBlankDocument
FileNewDialogClassic
ViewNormalViewPowerPoint
SynchronizeHtml
IgnoreHtmlChanges
FileSaveAsWebPage
HorizontalLineInsertClassic
GetExternalDataFromWeb
FrameCreateAbove
FrameCreateBelow
FrameCreateLeft
FrameCreateRight
FrameDelete
RelationshipsReport
NewView
GetExternalDataFromText
ServerConnection
RecordsInsertSubdatasheet
AdpDiagramNewLabel
AdpDiagramAddRelatedTables
AdpDiagramShowRelationshipLabels
AdpDiagramViewPageBreaks
AdpDiagramRecalculatePageBreaks
AdpDiagramArrangeSelection
AdpDiagramArrangeTables
AdpDiagramNewTable
AdpDiagramColumnProperties
AdpDiagramColumnNames

imageMso
AdpDiagramKeys
AdpDiagramNameOnly
AdpDiagramCustomView
AdpDiagramDeleteTable
AdpDiagramHideTable
AdpDiagramAutosizeSelectedTables
DiagramDeleteRelationship
WindowMoveSplit
EastAsianEditingMarks
FilePublishAsWebPage
TableAutoFitContents
TableAutoFitWindow
TableAutoFitFixedColumnWidth
TableCellAlignTopLeft
TableCellAlignTopCenter
TableCellAlignTopRight
TableCellAlignMiddleLeft
TableCellAlignMiddleCenter
TableCellAlignMiddleRight
TableCellAlignBottomLeft
TableCellAlignBottomCenter
TableCellAlignBottomRight
ServerFilterApply
WebControlCheckBox
WebControlOptionButton
WebControlDropDownBox
WebControlListBox
WebControlTextBox
WebControlTextArea
WebControlSubmit

imageMso
WebControlSubmitWithImage
WebControlReset
WebControlHidden
WebControlPassword
TableSetLeftToRight
TableSetRightToLeft
ChineseTranslationDialog
TableInsertMultidiagonalCell
AsianLayoutCharactersEnclose
ServerFilterByForm
EnvelopeChineseDialog
AdpVerifySqlSyntax
AdpDiagramTableModesMenu
CreateDiagram
RecordsExpandAllSubdatasheets
RecordsCollapseAllSubdatasheets
ObjectsMultiSelect
DatabaseLinedTableManager
TranslateToTraditionalChinese
TextWrappingBehindText
TextWrappingInFrontOfText
WatermarkCustomDialog
FrameSaveCurrentAs
AdpOutputOperationsTableRemove
AdpOutputOperationsGroupBy
AdpViewDiagramPane
AdpViewGridPane
AdpViewSqlPane
AdpOutputOperationsAddToOutput
AdpOutputOperationsSortAscending

imageMso
AdpOutputOperationsSortDescending
DatabaseAccessBackEnd
DatabasePartialReplica
TextDirectionContext
TranslateToSimplifiedChinese
ChineseTranslationMenu
FileBackUpSqlDatabase
ServerRestoreSqlDatabase
FileDropSqlDatabase
DatabaseSetLogonSecurity
DatabaseSqlServer
DatabaseSwitchboardManager
WebServerDiscussions
FontColorMoreColorsDialogPowerPoint
HyperlinksVerify
BlackAndWhite
CancelRequest
ViewMasterDocumentViewClassic
HyperlinkInsertPowerPoint
AddOrRemoveAttendees
NewDistributionList
CalculateFull
SizeMenu
ScriptDebugger
RunThisForm
MessageFormatPlainText
MessageFormatHtml
MessageFormatRichText
ExportToVCardFile
MessageOptions

imageMso
MapContactAddress
SignatureInsertMenu
DesignAFormOutlook
WatchWindow
FormulaEvaluate
LineSpacing
WordCountList
StylesModifyStyle
MacroRun
ServerProperties
SignatureShow
StylesPane
SpeechMicrophone
SubformInNewWindow
NumberingRestart
DrawingCanvasInsert
ViewsPivotTableView
ViewsPivotChartView
DiagramRadialInsertClassic
DiagramCycleInsertClassic
DiagramPyramidInsertClassic
DiagramTargetInsertClassic
DiagramVennDiagramInsertClassic
DiagramChangeToRadialClassic
DiagramChangeToCycleClassic
DiagramChangeToTargetClassic
DiagramChangeToVennDiagramClassic
PasteByAppendingTable
OrganizationChartInsertAssistant
OrganizationChartInsertCoworker

imageMso
OrganizationChartInsertSubordinate
AdpStoredProcedureEditSql
DrawingCanvasFit
DrawingCanvasResize
ColorGrayscaleMenu
ViewBackToColorView
ViewDisplayInGrayscale
ViewDisplayInHighContrast
ViewDisplayInPureBlackAndWhite
PivotAutoFilter
PivotSubtotal
PivotRefresh
PivotMoveToFieldArea
PivotMoveToColumnArea
PivotMoveToFilterArea
PivotMoveToDetailArea
PivotExpandField
PivotExportToExcel
PivotExpandIndicators
PivotDropAreas
SearchUI
MailMergeMergeToEMail
MailMergeMergeToFax
MailMergeCreateList
DrawingCanvasExpand
TextWrappingInLineWithText
SlidesPerPage1Slide
ReviewSendForReview
WorkgroupAdmin
AdpDiagramAddTable

imageMso
WebComponent
PasteSpecial
AttachFile
DiagramChangeToPyramidClassic
DiagramShapeMoveBackwardClassic
DiagramShapeMoveForwardClassic
SlideMasterPreserveMaster
SlideMasterRenameMaster
CharacterCodeToggle
LinkBarCustom
BorderDrawMenu
BorderErase
BorderStyle
StylesStyleVisibility
ShowFormulas
DatabaseCopyDatabaseFile
FileServerTransferDatabase
DiagramStylesClassic
MailMergeHighlightMergeFields
MailMergeWizard
OrganizationChartAutoLayout
OrganizationChartSelectLevel
OrganizationChartSelectBranch
OrganizationChartSelectAllAssistants
OrganizationChartSelectAllConnectors
PivotTableOlapPropertyFields
RevealFormatting
DiagramReverseClassic
DiagramAutoLayoutClassic
PasteTableFromExcel

imageMso
TranslationPane
GoToTableOfContents
TableOfContentsUpdate
OutlineLevelGallery
OutlineShowLevel
ErrorChecking
BulletsAndNumberingNumberingDialog
NumberingContinue
FileCheckOut
FileCheckIn
OrganizationChartLayoutStandard
OrganizationChartLayoutBothHanging
OrganizationChartLayoutLeftHanging
OrganizationChartLayoutRightHanging
PivotTableGenerateGetPivotData
ReviewReplyWithChanges
StylesStyleSeparator
BorderDrawLine
BorderDrawGrid
OutlinePromoteToHeading
MicrosoftOutlook
ReviewPreviousChange
ReviewNextChange
ReviewReviewingPane
ReviewAcceptChangeClassic
ReviewRejectChangeOrDeleteComment
PageOrientationLandscape
PageOrientationPortrait
GetExternalDataImportClassic
SlideReset

imageMso
AnimationOnClick
StartAfterPrevious
MailMergeMatchFields
MailMergeAddressBlockInsert
MailMergeGreetingLineInsert
MailMergeMergeFieldInsert
MailMergeRecipientsEditList
PicturesCompress
TableAutoFormatStyle
PivotAutoCalcMenu
PivotChartType
PivotChartMultiplePlots
PivotChartMultipleUnified
PivotSwitchRowColumn
DrillInto
MailMergeFindRecipient
VerticallyDistributed
ReviewDeleteCommentPowerPoint
ReviewNextCommentPowerPoint
ReviewPreviousCommentPowerPoint
ReviewShowOrHideMarkup
FontSchemes
FormFieldReset
MailMergeUpdateLabels
PivotCollapseFieldAccess
PivotShowDetails
PivotHideDetails
PivotChartLegendShowHide
AnimationAudio
DiagramFitToContentsClassic

imageMso
DiagramResizeClassic
DiagramExpandClassic
PivotShowAsMenu
OrganizationChartResize
AcceptProposal
AppointmentColor0
AppointmentColor1
AppointmentColor2
AppointmentColor3
AppointmentColor4
AppointmentColor5
AppointmentColor6
AppointmentColor7
AppointmentColor8
AppointmentColor9
AppointmentColor10
AppointmentColorDialog
ProposeNewTime
ViewAllProposals
ReviewDeleteAllMarkupOnSlide
PasteOption
MailMergeSetDocumentType
DiagramShapeInsertClassic
OrganizationChartStyle
AdpStoredProcedureQuerySelect
AdpStoredProcedureQueryMakeTable
AdpStoredProcedureQueryUpdate
AdpStoredProcedureQueryAppend
AdpStoredProcedureQueryAppendValues
AdpStoredProcedureQueryDelete

imageMso
ReviewDisplayForReview
ReviewNewCommentMenu
ReviewAllowUsersToEditRanges
SpeakCells
SpeakStop
SpeakByRows
SpeakByColumns
SpeakOnEnter
Translate
PivotClearCustomOrdering
PivotFilterBySelection
PivotRemoveField
PivotGroupItems
PivotUngroupItems
DrillOut
AdpManageIndexes
ViewGridlinesPowerPoint
AdpDiagramIndexesKeys
AdpDiagramRelationships
AdpConstraints
PhotoAlbumInsert
PhotoAlbumEdit
DrawingCanvasScale
OrgChartScale
DiagramScale
ProtectDocument
BrightnessAndContrastEdit
TableInsertExcel
ReadingMode
ReadingViewClose

imageMso
PersonaStatusOnline
PersonaStatusOffline
PersonaStatusAway
PersonaStatusBusy
GoToMail
ResearchPane
TableStyleTotalsRow
TableRowsInsertAboveExcel
TableRowsDeleteExcel
TableConvertToRange
PrintListRange
ReadingModeMini
DocumentMapReadingView
ReadingViewResearchPane
ReadingViewFontSizeIncrease
ReadingViewFontSizeDecrease
ReadingViewShowPrintedPage
ViewRulerWord
FileInternetFax
XmlExport
XmlImport
ViewDocumentActionsPane
DatabaseObjectDependencies
ReviewShowInk
InkEraseMode
TableColumnsInsertLeftExcel
TableColumnsDeleteExcel
NewAlert
InkDeleteAllInk
TableUnlinkExternalData

imageMso
TableExportTableToSharePointList
LookUp
FilePackageForCD
DesignXml
WindowSideBySide
ViewGridlinesFrontPage
ChangeBinding
ListSynchronize
ChangesDiscardAndRefresh
TableOpenInBrowser
TableResize
XmlExpansionPacksExcel
FileVersionHistory
FileVersionHistoryWord
FrontPageToggleBookmark
XmlDataRefresh
XmlMapProperties
WindowSideBySideSynchronousScrolling
WindowResetPosition
InkColorMoreColorsDialog
XmlTransformation
XmlEditQuery
JotInkStyle1
InsertDrawingCanvas
FilePermissionView
FilePermission
ReadingViewAllowMultiplePages
VoiceInsertInComment
RmsInvokeBrowser
RmsImportanceCheck

imageMso
RmsImportanceUncheck
ViewThumbnails
Thesaurus
InkingStart
VoteMenu
RmsNavigationBar
RmsSendBizcard
RmsSendBizcardDesign
FindText
AudioNoteDelete
ViewFullScreenReadingView
VisibilityVisible
VisibilityHidden
VisibilityInherit
InkDrawingAndWriting
ReviewInkCommentPen
ReviewInkCommentEraser
NewInternetFax
MeetingsWorkspace
InkEraser
InkStopInkingReadingView
StarUnratedEmpty
StarUnratedFull
StarRatedEmpty
StarRatedFull
StarRatedHalf
OutlookGlobe
OutlookGears
MsnLogo
GoLeftToRight

imageMso
GoLtrHover
GoLtrFocus
GoLtrDown
GoRtl
GoRtlHover
GoRtlFocus
GoRtlDown
StopLeftToRight
StopLtrHover
StopLtrFocus
StopLtrDown
StopRtl
StopRtlHover
StopRtlFocus
StopRtlDown
ForwardToMobile
JunkEmailAddToBlockedSendersList
JunkEmailMarkAsNotJunk
JunkEmailOptions
CategoryCollapse
DataSourceCatalogServerScript
PermissionRestrict
Risks
SetPertWeights
PanAndZoomWindow
FileBackupDatabase
OrganizationOutlook
ThemeBrowseForThemesPowerPoint
AccessNavigationOptions
WorkflowComplete

imageMso
WorkflowPending
Connections
ViewGoBack
ViewGoForward
ListSetNumberingValue
SlideMasterInsertLayout
FileViewDigitalSignatures
SignaturesLoading
AppointmentAttachment
ViewsReportView
FileCloseDatabase
OpenInfopathForm
FileWorkflowTasks
FileStartWorkflow
SharingRequestAllow
SharingRequestDeny
SharingOpenCalendarFolder
SignatureLineInsert
SlideThemesGallery
ApplicationOptionsDialog
BibliographyInsert
BibliographyStyle
CitationInsert
BibliographyManageSources
BibliographyAddNewSource
LabelInsert
BarcodeInsert
CongratulatoryEvent
CondolatoryEvent
ViewPageLayoutView

imageMso
PivotClearAll
ChartStylesGallery
ChartLayoutGallery
ChartSaveTemplates
ChartAxisTitles
ChartAxes
ChartGridlines
ChartMoreElement
ChartFormatSelection
ChartElementSelector
PageMarginsGallery
LimeCatsAndDogsGallery
DropCapInsertGallery
TrustCenter
ReadingViewAllowTyping
ReadingViewMarginSettingsMenu
CalendarInsert
SlideShowFromCurrent
BulletsGallery
NumberingGallery
LineSpacingGalleryPowerPoint
SlideNewGallery
SlideLayoutGallery
ShapesInsertGallery
ShapeChangeShapeGallery
ShapeFillTextureGallery
ShapeStylesGallery
PageOrientationGallery
FileServerTasksMenu
FileSendMenu

imageMso
GroupFont
GroupParagraph
GroupStyles
GroupProofing
GroupInsertPages
GroupInsertIllustrations
GroupShapes
GroupWordArtText
GroupPageSetup
GroupParagraphLayout
GroupCitationsAndBibliography
GroupFootnotes
GroupTableOfContents
GroupMailMergeWriteInsertFields
GroupMailMergePreviewResults
GroupMailMergeFinish
GroupChangesTracking
GroupComments
GroupChanges
GroupCompare
GroupPictureSize
GroupDrawBorders
GroupTableAlignment
GroupTableProperties
GroupTableTools
GroupSlides
GroupTextBoxText
GroupArrange
GroupInsertMediaClips
GroupSlideThemes

imageMso
GroupThemes
GroupBackground
GroupPreview
GroupAnimations
GroupTransitionToThisSlide
GroupSlideShowStart
GroupSlideShowSetup
GroupShapeStyles
GroupFill
GroupLines
GroupEffects
GroupChartLayouts
GroupChartStyles
GroupChartAxes
GroupChartShapes
GroupNumber
GroupAlignmentExcel
GroupCells
GroupSortFilter
GroupInsertTablesExcel
GroupOrganizationChartShapeInsert
GroupPageLayoutScaleToFit
GroupPageLayoutSheetOptions
GroupFunctionLibrary
GroupNamedCells
GroupFormulaAuditing
GroupGetExternalData
GroupConnections
GroupOutline
GroupDataTools

imageMso
GroupChangesExcel
FollowUpReadMenu
StylesManageStyles
StylesStyleInspector
ObjectEffectPresetGallery
PictureEffectsPresetGallery
_3DRotationGallery
ControlLayoutTabular
ControlLayoutStacked
ControlLayoutRemove
ShapeFillColorPicker
OutlineColorPicker
ResultsPaneStartFindAndReplace
FileDocumentInspect
ImportSavedImports
ImportAccess
ImportExcel
ImportTextFile
ImportSharePointList
ImportXmlFile
ImportOdbcDatabase
ImportHtmlDocument
ImportOutlook
ImportDBase
ImportParadox
ImportLotus
ExportSavedExports
ExportExcel
ExportSharePointList
ExportWord

imageMso
ExportAccess
ExportTextFile
ExportXmlFile
ExportOdbcDatabase
ExportSnapshot
ExportHtmlDocument
ExportDBase
ExportParadox
ExportLotus
QuickStylesGallery
QuickStylesSets
ClearFormatting
FormRegionOpen
FormRegionSave
PanningHand
BulletsGalleryWord
NumberingGalleryWord
SharePointListsWorkOffline
SynchronizeData
SharePointListsDiscardAllChangesAndRefresh
FileManageMenu
ViewsModeMenu
GroupSortAndFilter
SortSelectionMenu
FiltersMenu
RecordsMoreRecordsMenu
FieldsMenu
RecordsSubdatasheetMenu
GroupAutoFormatAccess
GroupTextFormatting

imageMso
GroupDataTypeAndFormatting
AlignLeftToRightMenu
GroupCreateTables
GroupCreateForms
GroupCreateReports
GroupCreateOther
GroupSharepointLists
GroupCollectData
GroupImport
ImportMoreMenu
GroupExport
ExportMoreMenu
GroupDatabaseTools
DatabasePermissionsMenu
GroupMacro
GroupDatabaseSourceControl
GroupSourceControlShow
GroupSourceControlManage
GroupRelationships
GroupMacroRows
GroupQuerySetup
GroupQueryType
SqlSpecificMenu2
GroupQueryTools
GroupControls
GroupPageLayoutAccess
GroupZoom
GroupToolsAccess
GroupRichText
GroupSizeAndPosition

imageMso
PivotShowTopAndBottomItemsMenu
PivotFormulasMenu
FilePublishSlides
SlideShowUsePresenterView
ArrowStyleGallery
OutlineDashesGallery
OutlineWeightGallery
GroupAlignment
GroupPictureTools
GroupSize
FormatCellsNumberDialog
FormatCellsFontDialog
CellAlignmentOptions
PageSetupPageDialog
PageSetupSheetDialog
PivotTableLayoutGrandTotals
GroupPivotTableActiveField
GroupPivotTableLayout
GroupPivotTableSort
GroupPivotTableShowHide
PivotTableLayoutSubtotals
GroupPivotTableGroup
GroupPivotTableTools
GroupPivotTableData
GroupPivotTableOptions
GroupPivotTableStyles
GroupPivotTableStyleOptions
WrapText
ClearMenu
ProofingToolsFlyoutAnchor

imageMso
PictureInsertMenu
ReviewTrackChangesMenu
ReviewAcceptChangeMenu
ReviewRejectChangeMenu
ReviewBalloonsMenu
GroupTableStylesPowerPoint
GroupTableRowsAndColumns
GroupTableData
ObjectAlignMenu
MovieInsert
ObjectRotateGallery
FillMenu
SelectMenu
OrientationMenu
MergeCenterMenu
AutoSumMenu
PrintAreaMenu
PageBreakMenu
NameDefineMenu
RefreshMenu
WhatIfAnalysisMenu
PivotTableFormulasMenu
PivotTableOlapTools
PivotTableOptionsMenu
AnimationGallery
AnimationTransitionGallery
AnimationTransitionSpeedGallery
ErrorCheckingMenu
TraceRemoveArrowsMenu
SortFilterMenu

imageMso
FontColorPicker
TableColumnsGallery
CellFillColorPicker
BorderDoubleBottom
ChartTitle
ChartPrimaryHorizontalAxisTitle
ChartPrimaryVerticalAxisTitle
ChartDepthAxisTitle
ChartLegend
ChartDataLabel
ChartPrimaryHorizontalGridlines
ChartPrimaryVerticalGridlines
ChartDepthGridlines
ChartPrimaryHorizontalAxis
ChartPrimaryVerticalAxis
ChartDepthAxis
ChartDataTable
ChartTrendline
ChartErrorBars
ChartLines
ChartUpDownBars
ChartPlotArea
ChartWall
ChartFloor
GroupMarginsAndPadding
ControlLineTypeGallery
ControlLineThicknessGallery
GroupMacroTools
ReplicationOptionsMenu
GroupRecords

imageMso
LassoSelect
SmartArtAddShape
SmartArtIncreaseFontSize
SmartArtDecreaseFontSize
SmartArtLargerShape
SmartArtSmallerShape
SmartArtResetGraphic
SmartArtResetShape
SmartArtTextPane
SmartArtEditIn2D
SmartArtLayoutGallery
SmartArtMoreLayoutsDialog
SmartArtStylesGallery
SmartArtChangeColorsGallery
ObjectEffectSoftEdgesGallery
ObjectEffectGlowGallery
GradientGallery
ObjectEffectShadowGallery
WordArtInsertGallery
TextEffectTransformGallery
TextNoTransform
TextPathArchUp
TextPathArchDown
TextPathCircle
TextPathButton
TextPlain
TextStop
TextTriangle
TextTriangleInverted
TextChevron

imageMso
TextChevronInverted
TextRingInside
TextRingOutside
TextArchUpPour
TextArchDownPour
TextCirclePour
TextButtonPour
TextCurveUp
TextCurveDown
TextCascadeUp
TextCascadeDown
TextWave1
TextWave2
TextWave3
TextWave4
TextInflate
TextDeflate
TextInflateBottom
TextDeflateBottom
TextInflateTop
TextDeflateTop
TextDeflateInflate
TextDeflateInflateDeflate
TextFadeRight
TextFadeLeft
TextFadeUp
TextFadeDown
TextSlantUp
TextSlantDown
TextCanUp

imageMso
TextCanDown
GroupHeaderFooterExcel
HeaderFooterHeaderGallery
HeaderFooterFooterGallery
GroupHeaderFooterElements
HeaderFooterPageNumberInsertExcel
HeaderFooterNumberOfPagesInsert
HeaderFooterCurrentDate
HeaderFooterCurrentTimeInsert
HeaderFooterFilePathInsert
HeaderFooterFileNameInsert
HeaderFooterSheetNameInsert
HeaderFooterPictureInsert
HeaderFooterFormatPicture
GroupHeaderFooterOptions
FontShadingColorMoreColorsDialog
FontColorMoreColorsDialogExcel
BorderMoreColorsDialog
SheetTabColorMoreColorsDialog
PivotTableNewStyle
PivotPlusMinusFieldHeadersShowHide
PivotTableExpandField
PivotCollapseField
ConditionalFormattingDataBarsGallery
ConditionalFormattingColorScalesGallery
ConditionalFormattingIconSetsGallery
TableColumnsInsertRightExcel
TableRowsInsertBelowExcel
ConditionalFormattingHighlightBetween
ConditionalFormattingHighlightCompareColumns

imageMso
PivotTableStylesGallery
FormatAsTableGallery
TableStylesGalleryExcel
ConditionalFormattingsManage
ConditionalFormattingHighlightGreaterThan
ConditionalFormattingHighlightLessThan
ConditionalFormattingHighlightEqualTo
ConditionalFormattingHighlightTextContaining
ConditionalFormattingHighlightDateOccuring
ConditionalFormattingHighlightDuplicateValues
ConditionalFormattingTopNItems
ConditionalFormattingTopNPercent
ConditionalFormattingBottomNItems
ConditionalFormattingBottomNPercent
ConditionalFormattingAboveAverage
ConditionalFormattingBelowAverage
RemoveDuplicates
FilterReapply
CreateEmail
ManageReplies
ReviewPreviousCommentWord
ReviewNextCommentWord
ThemeColorsGallery
PivotTableInsert
PivotChartInsert
PivotTableMove
PivotTableChangeDataSource
BuildingBlocksCreateNewFromSel
HeaderInsertGallery
FooterInsertGallery

imageMso
CoverPageInsertGallery
PageNumberFieldInsertGallery
WatermarkGallery
EquationInsertGallery
QuickTablesInsertGallery
QuickPartsInsertGallery
SharePointListsDiscardAllChanges
SortRemoveAllSorts
GroupSmartArtLayouts
GroupSmartArtQuickStyles
GroupSmartArtChooseColor
GroupSmartArtCreateGraphic
GroupSmartArtReset
GroupSmartArtSize
ConditionalFormattingHighlightCellsMenu
ConditionalFormattingTopBottomMenu
SaveSelectionToQuickPartGallery
SaveSelectionToCoverPageGallery
SaveSelectionToEquationGallery
SaveSelectionToFooterGallery
SaveSelectionToHeaderGallery
SaveSelectionToPageNumberGallery
SaveSelectionToQuickTablesGallery
SaveSelectionToWaterMarkGallery
MenuView2
FormatCellsMenu
ConditionalFormattingClearMenu
FontColorCycle
CellsInsertSmart
CellsDeleteSmart

imageMso
ReviewShowMarkupMenu
ObjectEditShapeMenu
PivotTableLayoutReportLayout
PivotTableLayoutShowInCompactForm
PivotTableLayoutShowInOutlineForm
PivotTableLayoutShowInTabularForm
SymbolInsertGallery
ControlChart
SpellingAccess
ViewsDatasheetView
PivotTableClearMenu
MacroArguments
MacroShowAllActions
GroupControlsAccess
CreateTable
CreateTableTemplatesGallery
AccessTableContacts
AccessTableTasks
AccessTableIssues
AccessTableEvents
AccessTableAssets
CreateTableUsingSharePointListsGallery
AccessListContacts
AccessListTasks
AccessListIssues
AccessListEvents
AccessListAssets
AccessListCustom
AccessListCustomDdatasheet
CreateForm

imageMso
CreateFormSplitForm
CreateFormWithMultipleItems
CreateFormMoreFormsGallery
AccessFormWizard
CreateFormPivotChart
AccessFormPivotTable
AccessFormDatasheet
AccessFormModalDialog
CreateFormBlankForm
CreateReport
AccessReportMore
CreateReportFromWizard
CreateLabels
CreateReportBlankReport
CreateOtherObjectsMenu
ControlTitle
ControlLogo
ShowMargins
SlideMasterContentPlaceholderInsert
SlideMasterTextPlaceholderInsert
SlideMasterChartPlaceholderInsert
SlideMasterTablePlaceholderInsert
SlideMasterDiagramPlaceholderInsert
SlideMasterMediaPlaceholderInsert
SlideMasterClipArtPlaceholderInsert
SlideMasterVerticalTextPlaceholderInsert
SlideMasterShowFooters
CellStylesGallery
CellStyleNew
CellStylesMerge

imageMso
TableStylesGallery
TableStyleNew
TableStyleClear
FilePublishExcelServices
PivotTableOlapConvertToFormulas
PivotTableLayoutBlankRows
TableStyleFirstColumn
TableStyleLastColumn
TableStyleBandedRows
TableStyleBandedColumns
TableStyleRowHeaders
TableStyleColumnHeaders
TableSummarizeWithPivot
DisplayRuler
GetExternalDataFromAccess
GetExternalDataFromOtherSources
GetExternalDataExistingConnections
GroupThemesExcel
PivotPlusMinusButtonsShowHide
FileSaveAsPdfOrXps
FormattingDataType
FormattingRequiredField
FormattingFormat
ApplyCurrencyFormat
ApplyPercentageFormat
ApplyCommaFormat
FormattingIncreaseDecimals
FormattingDecreaseDecimals
BusinessCardInsertMenu
RecentFileList

imageMso
DataGraphicIconSet
SearchLibraries
MoreControlsDialog
GroupCode
GroupRestrictions
GroupXml
PageScaleToFitWidth
PageScaleToFitHeight
SlideTransitionApplyToAll
AnimationPreview
XmlStructure
XmlSchema
XmlExpansionPacksWord
GroupCaptions
GroupIndex
GroupTableOfAuthorities
GroupEditing
SelectMenuExcel
PrintTitles
NameUseInFormula
CalculationOptionsMenu
XmlSource
GroupClipboard
GroupInsertTables
GroupInsertLinks
GroupInsertSymbols
GroupInsertBarcode
GroupCalculation
BordersGallery
BordersMoreDialog

imageMso
PageScaleToFitOptionsDialog
PageSizeGallery
AnimationTransitionSoundGallery
ObjectPictureFill
TextWrappingMenu
RecordsAddFromOutlook
RecordsSaveAsOutlookContact
DatasheetNewField
PivotTableGroupSelection
PivotTableGroupField
SlideShowFromBeginning
WindowSwitchWindowsMenuWord
WindowSwitchWindowsMenuPowerPoint
WindowSwitchWindowsMenuExcel
ShapeFillMoreGradientsDialog
ShadowOptionsDialog
BuildingBlocksOrganizer
TableSharePointListsModifyColumnsAndSettings
TableListAlertMe
TableSharePointListsModifyWorkflow
TableListPermissions
TableSharePointListsRefreshList
CreateQueryInDesignView
ControlAttachment
GroupFieldsAndColumns
DataOptionsMenu
FormattingUnique
RecordsRefreshMenu
GroupLayoutShowHide
GroupQueryShowHide

imageMso
GroupMacroShowHide
GroupPosition
GroupAnalyze
GroupControlLayout
GroupRelationshipsTools
GroupTableDesignTools
GroupTableRows
GroupSharePointList
GroupPivotTableFilterAndSort
GroupPivotTableToolsAccess
GroupPivotTableShowHideAccess
GroupPivotTableSelections
GroupPivotTableDataAccess
GroupPivotTableActiveFieldAccess
GroupPivotChartFilterAndSort
GroupPivotChartTools
GroupPivotChartShowHide
GroupPivotChartDataAccess
GroupPivotChartActiveFieldAccess
GroupPivotChartType
ControlMarginsGallery
ControlPaddingGallery
AutoFormatGallery
PivotMoveField
PivotChartSortByTotalMenu
SharePointListsDiscardChangesMenu
ReviewCompareMenu
ReviewCompareTwoVersions
ReviewCombineRevisions
ReviewCompareMajorVersion

imageMso
ReviewCompareLastVersion
ReviewCompareSpecificVersion
PropertyInsert
ObjectsAlignLeftSmart
ObjectsAlignRightSmart
ObjectsAlignTopSmart
ObjectsAlignBottomSmart
ObjectsAlignCenterHorizontalSmart
ObjectsAlignMiddleVerticalSmart
AlignDistributeHorizontally
AlignDistributeVertically
GroupProtect
IndexUpdate
MailMergeFinishAndMergeMenu
HyphenationMenu
MailMergeRules
SlideShowCustomMenu
SlideShowResolutionGallery
SlideShowUseRehearsedTimings
SlideShowShowPresentationOnGallery
GroupMonitors
MailMergeStartMailMergeMenu
MailMergeStartLetters
MailMergeStartEmail
MailMergeStartEnvelopes
MailMergeStartLabels
MailMergeStartDirectory
MailMergeClearMergeType
MailMergeSelectRecipients
TableOfContentsAddTextGallery

imageMso
FunctionsRecentlyUsedtInsertGallery
FunctionsFinancialInsertGallery
FunctionsDateTimeInsertGallery
FunctionsMathTrigInsertGallery
FunctionsTextInsertGallery
FunctionsLogicalInsertGallery
FunctionsStatisticalInsertGallery
FunctionsLookupReferenceInsertGallery
FunctionsInformationInsertGallery
GroupTableStyleOptions
GroupTableExternalData
GroupEditingExcel
BorderColorPicker
TranslationToolTip
FileCompatibilityChecker
FollowUpComposeMenu
ThemeFontsGallery
ThemeEffectsGallery
PrintColumns
PrintDataOnly
GroupControlAlignment
RmsNavigationBarHome
FileProperties
ForwardAttach
BackAttach
ManageAttachments
GroupPrintPreviewPrint
GroupPrintPreviewPreview
GroupPlay
GroupMovieOptions

imageMso
GroupSoundOptions
SoundPlaySoundGallery
SlideShowVolume
BreaksGallery
LineNumbersMenu
GroupOutliningClose
GroupOutliningTools
GroupMasterDocument
TableSelectMenu
TableDeleteRowsAndColumnsMenuWord
GroupTableMerge
TableAutoFitMenu
GroupTableDrawBorders
TableBordersMenu
SortDialog
SortAscendingExcel
SortDescendingExcel
SortCustomExcel
EditListItems
PublishToPdfOrEdoc
FileSaveAsCurrentFileFormat
FileSaveAsAccess2007
FileSaveAsAccess2002_2003
FileSaveAsAccess2000
AcceptAndAdvance
RejectAndAdvance
FileCreateDocumentWorkspace
FileSaveToDocumentManagementServer
FileDocumentManagementInformation
ScreenNavigatorBack

imageMso
ScreenNavigatorForward
FilePrepareMenu
FileMarkAsFinal
FileAddDigitalSignature
ForwardAsBusinessCard
ChooseInfoPathForm
RecordsTotals
StylesPaneNewStyle
ChangeCaseGallery
ReviewDeleteCommentsMenuPowerPoint
GroupMerge
AlignJustifyMenu
TextBoxInsertMenu
TextBoxInsertHorizontal
ControlProperties
ViewCode
GroupHeaderFooterLayout
GroupHeaderFooterInsert
GroupHeaderFooterNavigation
GroupHeaderFooterPosition
BlankPageInsert
HandoutOrientation
SlidesPerPageGallery
GroupPlaceholdersHandoutMaster
GroupMasterEditTheme
GroupMasterClose
GroupMasterEdit
GroupMasterLayout
GroupColorModeSetting
ShadowStyleGalleryClassic

imageMso
GroupInkSelect
WordArtSpacingMenu
TextAlignMenu
DiagramChangeToMenuClassic
NumberFormatGallery
PictureBrightnessGallery
PictureContrastGallery
PicturePositionGallery
GroupPictureReset
GroupPictureCompress
GroupMailMergeStart
OleObjectInsertMenu
ViewsLayoutView
ForwardAsAttachment
InkInsertSpace
ShadingColorPicker
ShadingColorsMoreColorsDialog
SmartArtAddShapeAfter
SmartArtAddShapeBefore
SmartArtAddShapeAbove
SmartArtAddShapeBelow
SmartArtAddAssistant
ChartSwitchRowColumn
ChartShowData
ChartRefresh
ChartChangeType
GroupChartData
GroupChartLocation
GroupChartType
GroupTableSize

imageMso
TableCellMarginsGallery
SlideMasterVerticalContentPlaceholderInsert
_3DRotationOptionsDialog
_3DBevelOptionsDialog
SlideBackgroundStylesGallery
TextDirectionGallery
GroupTableStyleOptionsPowerPoint
TableStyleBandedRowsPowerPoint
TableStyleBandedColumnsPowerPoint
SelectionPane
SmartArtOrganizationChartLeftHanging
SmartArtOrganizationChartRightHanging
SmartArtOrganizationChartBoth
SmartArtOrganizationChartStandard
SmartArtRightToLeft
TableCellCustomMarginsDialog
ForwardContact
PositionAnchoringGallery
GroupMoveData
FilterAdvancedMenu
OmsSend
OmsFileSend
OmsSave
GroupOmsSend
GroupOmsInsert
GroupOmsView
GroupOmsMessageOptions
OmsViewAccountSetting
OmsInsertSymbolGallery
OmsEmoticonStringInsertGallery

imageMso
OmsEmoticonInsertGallery
OmsPreviewPane
OmsChangeZoom
OmsAccountSetup
OmsOptions
OmsSlideInsert
OmsChangeSlideLayoutGallery
OmsDelete
OmsInsertPicture
OmsInsertAudio
OmsCustomizeLayout
OmsAudioFromFile
OmsImageFromFile
OmsImageFromClip
OmsScanImage
OmsNewTextMessage
OmsNewMultimediaMessage
OmsNewTextMessageToContact
OmsNewMultimediaMessageToContact
OmsForwardAsTextMessage
OmsForwardAsMultimediaMessage
OmsMaximumMessages
OmsGroupCreateSlides
ListLevelGallery
MultilevelListGallery
BuildingBlockProperties
ApplyStylesPane
NameManager
NameDefine
OpenAttachedCalendar

imageMso
RssShareThisFeed
OpenInBrowserOutlook
InsertAlignmentTab
SharingOpenMailFolder
SharingOpenContactFolder
SharingOpenTaskFolder
SharingOpenNotesFolder
SharingOpenJournalFolder
SharingOpenDocumentFolder
ReplyWithInstantMessage
DefaultView
HideDetails
GridlinesWidthGallery
GridlinesColorPicker
GridlinesStyleGallery
SmartArtOrganizationChartMenu
SmartArtChangeLayout
ReadingViewToolsMenu
ReadingViewNextPage
ReadingViewPreviousPage
ReadingViewShowOnePage
ReadingViewShowTwoPages
ReadingViewViewOptionsMenu
EditWorkflowTask
SymbolsDialog
ReviewReviewingPaneHorizontal
ReviewReviewingPaneVertical
_3DEffectsGalleryClassic
_3DDirectionGalleryClassic
_3DLightingGalleryClassic

imageMso
GroupShadowEffects
Group3DEffects
WordArtStylesGalleryClassic
WordArtInsertGalleryClassic
TableInsertGallery
ShapeStylesGalleryClassic
WordArtChangeShapeGallery
ShadowColorPickerClassic
_3DEffectColorPickerClassic
ShapeFillGradientGalleryClassic
AsianLayoutMenu
JapaneseGreetingsInsertMenu
AlignJustifyWithMixedLanguages
AlignJustifyLow
AlignJustifyMedium
AlignJustifyHigh
AlignJustifyThai
ExcelSpreadsheetInsert
ParagraphIndentLeft
ParagraphIndentRight
ParagraphSpacingBefore
ParagraphSpacingAfter
HeaderFooterPositionHeaderFromTop
HeaderFooterPositionFooterFromBottom
ControlsGallery
ShapeHeight
ShapeWidth
TransitionTimeAutomaticallyAfter
SoundMaximumFileSize
CDAudioStartTrack

imageMso
CDAudioStopTrack
CDAudioStartTime
CDAudioStopTime
SlideOrientationGallery
TextHighlightColorPicker
PageColorPicker
GoToHeader
GoToFooter
UnderlineGallery
UnderlineColorPicker
TextDirectionGalleryWord
GroupAddInsMenuCommands
GroupAddInsToolbarCommands
ViewFreezePanelsGallery
GroupInk
GroupInkPens
GroupInkClose
InkBallpointPen
InkFeltTipPen
InkHighlighter
PhoneticGuideMenu
PageScaleToFitScale
GroupBorder
PictureRecolorGalleryWord
_3DSurfaceMaterialGalleryClassic
_3DExtrusionDepthGalleryClassic
GroupHeaderFooter
GroupPageLayoutSetup
GroupPageBackground
FunctionsCubeInsertGallery

imageMso
FunctionsEngineeringInsertGallery
ThemeSaveCurrentPowerPoint
ThemeSaveCurrent
TextAlignGallery
ThemesGallery
CharacterSpacingGallery
ChartFormatDataSeries
ChartFormatDataLabels
ChartResetToMatchStyle
ChartSeriesTypeChange
Chart3DView
ChartFormatDataPoint
ChartFormatDataLabel
ChartFormatAxis
ChartFormatGridlines
ChartFormatDisplayUnit
ChartFormatLegendEntry
ChartFormatChartArea
ChartFormatLegend
ChartFormatErrorBars
ChartFormatUpBars
ChartFormatDownBars
ChartFormatHighLowLine
ChartFormatDropLines
ChartFormatTrendline
ChartFormatTrendlineLabel
ChartFormatSeriesLine
ChartFormatDataTable
ChartFormatAxisTitle
ChartFormatChartTitle

imageMso
ChartFormatFloor
ChartFormatSideWall
ChartFormatBackWall
ChartFormatWalls
ChartFormatPlotArea
ObjectSizeAndPositionDialog
ObjectSizeAndPropertiesDialog
ObjectSizeDialog
ShapeConvertToFreeform
AutoTextGallery
TextBoxInsertGallery
PageNumbersInHeaderInsertGallery
PageNumbersInFooterInsertGallery
PageNumbersInMarginsInsertGallery
SaveSelectionToAutoTextGallery
SaveSelectionToTextBoxGallery
BuildingBlocksCreateLayout
SaveSelectionToPageNumberTop
SaveSelectionToPageNumberBottom
SaveSelectionToPageNumberMargin
BuildingBlocksSaveCoverPage
BuildingBlocksSaveHeader
BuildingBlocksSaveFooter
BuildingBlocksSavePageNumTop
BuildingBlocksSavePageNumBottom
BuildingBlocksSavePageNum
HeaderFooterEditHeader
TableStyleBandedRowsWord
TableStyleBandedColumnsWord
MSWordApplyTableStyle

imageMso
TableStyleModify
TableStylesGalleryWord
ReviewViewChangesInTheSourceDocument
GroupThemesWord
OfficeDiagnostics
WindowsSwitch
LayoutOptionsDialog
DrawingObjectFormatDialog
FontAlternateFillBackColorPicker
GroupGroupingAndTotals
GroupFindAccess
GroupSchemaTools
GroupAdpDiagramShowHide
GroupAdpDiagramLayout
GroupAdpQueryTools
GroupAdpOutputOperations
GroupAdpQueryType
GroupAdpSqlStatementDesignTools
ConvertToSmartArt
ConvertToSmartArtMoreSmartArtGraphicsDialog
ReflectionGallery
PictureRecolorGallery
SmartArtPromote
SmartArtDemote
TableEffectsCellBevelGallery
GroupPivotChartShowOrHide
GroupPivotChartData
GroupPivotChartActiveField
PivotChartRefresh
PivotChartFilterShow

imageMso
TableBackgroundGallery
_3DPerspectiveIncrease
_3DPerspectiveDecrease
ChartSecondaryHorizontalAxisTitle
ChartSecondaryVerticalAxisTitle
ChartSecondaryHorizontalGridlines
ChartSecondaryVerticalGridlines
ChartSecondaryHorizontalAxis
ChartSecondaryVerticalAxis
ReadingModeToPrintView
GroupAddInsCustomToolbars
MoviePlayAutomatically
ReviewDeleteCommentsMenu
ConditionalFormattingMenu
GroupPersonalInfo
GroupMessageOptions
GroupAttach
GroupNames
GroupRespond
GroupMembers
GroupContactOptions
GroupJunkEmail
ForwardMenu
JunkEmailSafeListsMenu
UseVotingButtonsMenu
RecentlyUsedFolder
ArrangeWindowsDialog
GroupForm
MakeSameSizeMenu
CategorizeMenu

imageMso
ReplyAllWithInstantMessage
ObjectBringToFrontMenu
ObjectSendToBackMenu
ObjectsGroupMenu
SignatureLineInsertMenu
FileSaveAsWord97_2003
ViewDisplayInColor
HyperlinkFlyoutAnchor
FileSaveAsPowerPoint97_2003
SelectionPaneHidden
PivotFieldList
FilePackageAndSign
TotalsMenu
EnglishWritingAssistant
TableOfContentsGallery
SaveSelectionToTableOfContentsGallery
BuildingBlocksCreateTableOfFigures
BuildingBlocksCreateTableOfAuthorities
BuildingBlocksCreateIndex
BuildingBlocksSaveTableOfContents
BuildingBlocksSaveTableOfFigures
BuildingBlocksSaveTableOfAuthorities
BuildingBlocksSaveIndex
FileSaveAsExcel97_2003
TextBoxInsertExcel
TextBoxStyleGallery
TableColumnWidth
TableRowHeight
TextBoxPositionGallery
FilePermissionRestrictMenu

imageMso
GroupEnvelopeLabelCreate
ReviewInkCommentNew
InsertCellstMenu
PivotTableInsertMenu
OutlineGroupMenu
OutlineUngroupMenu
FormulaMoreFunctionsMenu
WordInsertTableOfContents2
ReadingViewTrackChanges
ReadingViewShowCommentsAndChangesMenu
ReadingViewChangeInkPenMenu
DocumentPanelTemplate
GroupModify
ObjectSizeDialogClassic
ViewGridlinesToggleExcel
TextBoxInsertVerticalWord
BevelShapeGallery
_3DBevelPictureTopGallery
_3DMaterialMixed
_3DMaterialPlastic
_3DMaterialMetal
BibliographyAddNewPlaceholder
TableStyleClearTable
GroupTable
GroupTableCellSize
TableEffectsMenu
EditLinks
PositionAbsoluteMarks
QuerySplitMenu
FileSaveAsMenuAccess

imageMso
FileServerMenu
GlowColorPicker
RecolorColorPicker
GlowColorMoreColorsDialog
PictureRecolorMoreColorsDialog
ShapesDuplicate
CloseDocument
WatermarkRemove
CoverPageRemove
HeaderFooterRemoveHeaderWord
HeaderFooterRemoveFooterWord
PageNumbersRemove
TableOfContentsRemove
SmartArtAddBullet
TableWidth
TableHeight
SlideMasterPicturePlaceholderInsert
SlideMasterInsertPlaceholderMenu
RemoveCitation
EditCitation
TableBorderColorMoreColorsDialog
TableFillColorMoreColorsDialog
PictureChange
GroupWordArtStyles
TextFillColorPicker
TextOutlineColorPicker
TextOutlineColorMoreColorsDialog
TextEffectsMenu
TextStylesGallery
WordArtClear

imageMso
TextPictureFill
TextFillGradientGallery
TextFillMoreGradientsDialog
TextFillTextureGallery
TextOutlineDashesGallery
TextOutlineMoreLinesDialog
TextOutlineWeightGallery
TextEffectShadowGallery
TextEffectsMoreShadowsDialog
TextEffectsBevelMore3DOptionsDialog
TextEffects3DRotationGallery
TextEffects3DRotationOptionsDialog
TextEffectGlowGallery
TextGlowColorPicker
TextGlowColorMoreColorsDialog
TextReflectionGallery
ShapeEffectsMenu
NewTableStyle2
NewPivotTableStyle2
ShapeConnectorStyleMenu
PivotTableSubtotalsDoNotShow
PivotTableSubtotalsOnBottom
PivotTableSubtotalsOnTop
PivotTableGrandTotalsOffForRowsAndColumns
PivotTableGrandTotalsOnForRowsAndColumns
PivotTableGrandTotalsOnForRowsOnly
PivotTableGrandTotalsOnForColumnsOnly
PivotTableBlankRowsInsert
PivotTableBlankRowsRemove
ShowMessagePage

imageMso
ShowCustomPage
ShowTrackingPage
ShowCustomPropertiesPage
ShowCustomActionsPage
ShowFormRegionPage
GroupShow
ShowAllFieldsPage
MessageToAttendeesMenu
ReminderGallery
ShowTimeAsGallery
ProposeNewTimeMenu
GroupAttendeesMeetingNotSent
GroupAppointmentOptions
ShowAppointmentPage
ShowSchedulingPage
ShowContactPage
ShowCertificatesPage
ShowActivitesPage
ShowDetailsPage
ShowMembersPage
ShowNotesPage
GroupCopy
InterconnectOpen
InterconnectNextSide
DefinedPrintStyle
ItemProperties
PermissionRestrictMenu
MoveItem
ShowSharePage
EditBusinessCard

imageMso
GroupInterconnect
ContactPictureMenu
ContactSendMenu
DistributionListSelectMembers
DistributionListAddNewMember
DistributionListRemoveMember
DistributionListUpdateMembers
ObjectsGroupOutlook
ObjectsUngroupOutlook
ObjectBringToFrontOutlook
ObjectSendToBackOutlook
ObjectBringForwardOutlook
ObjectSendBackwardOutlook
FormPublishMenu
GroupDesign
PageMenu
AppointmentBusy
AppointmentOutOfOffice
ShowTaskPage
ShowTaskDetailsPage
GroupManageTask
GroupTaskOptions
ShowJournalPage
StartTimer
PauseTimer
FormRegionMenu
ObjectsAlignMenuOutlook
GroupSend
IMMenu
UpgradeDocument

imageMso
GroupHeaderFooterClose
GroupChartCurrentSelection
GroupChartLabels
AlignTopExcel
AlignMiddleExcel
AlignBottomExcel
CustomActionsMenu
GroupActions
TableOfAuthoritiesUpdate
TableOfFiguresUpdate
PrintPreviewMultiplePagesMenu
ContentControlsGroup
FormsMenu
TablesMenu
ReportsMenu
BevelTextGallery
PictureCorrectionsDialog
PostcardWizard
BusinessFormWizard
GroupTextBoxStyles
GroupTableStylesWord
GroupWordArtStylesClassic
PageBorderAndShadingDialog
GroupTableStylesExcel
OutlineViewClose
ConditionalFormattingNewRule
SmartArtAddShapeSplitMenu
ContentControlRichText
ContentControlText
ContentControlPicture

imageMso
ContentControlComboBox
ContentControlDropDownList
ContentControlBuildingBlockGallery
ContentControlDate
AccountMenu
MoveToFolderFileMenu
RssDownloadContent
InsertRow
InsertColumn3
MasterNotesPageOrientation
ViewRulerExcel
ReadingNextPageRtl
ReadingPrevPageRtl
AutoSummaryToolsMenu
GroupInkFormat
InkColorPicker
GroupDiagramLayoutClassic
GroupDiagramStylesClassic
GroupOrganizationChartLayoutClassic
GroupOrganizationChartStyleClassic
TextBoxDrawMenu
TextBoxInsertWord
GroupOrganizationChartSelect
BorderColorPickerExcel
TextDirectionMoreOptionsDialog
TextAlignMoreOptionsDialog
ParagraphMoreColumnsDialog
ObjectBringToFrontMenuOutlook
ObjectSendToBaseMenuOutlook
Call

imageMso
BibliographyGallery
CustomHeaderGallery
CustomFooterGallery
CustomCoverPageGallery
CustomPageNumberGallery
CustomPageNumberTopGallery
CustomPageNumberBottomGallery
CustomPageMargins
CustomWatermarkGallery
CustomEquationsGallery
CustomTablesGallery
CustomQuickPartsGallery
CustomAutoTextGallery
CustomTextBoxGallery
CustomTableOfContentsGallery
CustomBibliographyGallery
CustomGallery1
CustomGallery2
CustomGallery3
CustomGallery4
CustomGallery5
SlideBackgroundReset
ShapeCloud
MailMergeReceipientsUseOutlookContacts
CDAudioPlayTrackAutomatically
FootnoteNext
ColorPickerCommentFill
GroupConvert
ReviewReviewingPaneMenu
GroupSizeClassic

imageMso
GroupPictureSizeClassic
GroupPictureToolsClassic
GalleryAllShapesAndCanvas
GroupShapesClassic
GroupSmartArtShapes
GroupShapeStylesClassic
GroupInsertText
Drawing1ColorPickerFill
ShapeOutlineColorPicker
Drawing1ColorPickerLineStyle
Drawing1ColorPickerLineStyle2
Drawing1GalleryTextures
InsertBuildingBlocksHeaderGallery
InsertBuildingBlocksFooterGallery
InsertBuildingBlocksCommonPartsGallery
InsertBuildingBlocksEquationsGallery
Drawing1GalleryBrightness
Drawing1GalleryContrast
GroupDiagramArrangeClassic
GroupTextBoxArrange
GroupColorModeClose
GroupPageSetupNotesMaster
GroupPageSetupHandoutMaster
GroupPlaceholdersNotesMaster
GroupInsertSlides
InsertPicturePowerPointFlyoutAnchor
TableSelectMenuPowerPoint
TableDeleteRowsAndColumnsMenu
GroupCDAudioSetup
AccountingFormatMenu

imageMso
GroupCommentShapes
GroupCommentPosition
TripaneViewMode
PrintOptionsMenu
FileMenuSendHeader
FileMenuServerTasksHeader
ScreenNavigatorBackMenu
ScreenNavigatorForwardMenu
OutlineCollapseMenu
OutlineExpandMenu
ContentControlsGroupMenu
ContentControlsUngroup
EditCitationButton
GroupChartProperties
ControlsGalleryClassic
PivotTableEditDataSource
FileExcelServicesOptions
ReviewShowSourceDocumentsMenu
BuildingBlocksSaveEquation
HeaderFooterEditFooter
WordContentControlEditPlaceholderToggle
TableExportMenu
TableExportTableToVisioPivotDiagram
EquationToggle
EquationInsertNew
EquationProfessional
EquationLinearFormat
EquationNormalText
EquationSymbolsInsertGallery
EquationIntegralGallery

imageMso
EquationFractionGallery
EquationRadicalGallery
EquationLargeOperatorGallery
EquationDelimiterGallery
EquationScriptGallery
EquationFunctionGallery
EquationAccentGallery
EquationLimitGallery
EquationOperatorGallery
EquationMatrixGallery
EquationOptions
GroupEquationTools
GroupEquationSymbols
GroupEquationStructures
EquationOptionsMenu
GroupBasicText
GroupInclude
GroupFields
GroupMessageFormat
GroupTracking
GroupMoreOptions
GroupCommunicate
GroupTimer
SaveSentItemsMenu
DelayDeliveryOutlook
DirectRepliesTo
SaveSentItemRecentlyUsedFolder
SaveSentItemOtherFolder
FindRelatedMenu
OtherActionsMenu

imageMso
EncodingMenu
Drawing1GalleryRotateObject
MailMergeMergeFieldInsertMenu
ReviewDeleteAllMarkupInPresentation
PasteMenu
GroupPictureStyles
PictureStylesGallery
GroupInsertChartsExcel
ChartTypeColumnInsertGallery
ChartTypeLineInsertGallery
ChartTypePieInsertGallery
ChartTypeBarInsertGallery
ChartTypeAreaInsertGallery
ChartTypeXYScatterInsertGallery
ChartTypeOtherInsertGallery
ChartTypeAllInsertDialog
PivotChartClearMenu
ReviewAcceptChangeAndMoveToNext
ReviewRejectChangeAndMoveToNext
PictureEffectsShadowGallery
PictureEffectsGlowGallery
PictureEffectsSoftEdgesGallery
PictureReflectionGallery
PictureReflectionGalleryItem
PictureRotationGallery
ReadingViewShowOriginalOrFinalDocument
InterconnectDeleteCard
InkToolsClose
GroupChineseTranslation
CloseMasterView

imageMso
SheetRowsInsert
SheetColumnsInsert
SheetRowsDelete
SheetColumnsDelete
JustifyVerticalFlyoutAnchor
JustifyLowVertical
JustifyMediumVertical
JustifyHighVertical
LineSpacingMenu
WordOpenParaAbove
WordCloseParaAbove
WordOpenParaBelow
WordCloseParaBelow
AdpNewTable
ViewsSwitchToDefaultView
GroupDocumentViews
GroupViewShowHide
GroupWindow
GroupWorkbookViews
ViewGridlines
ViewHeadings
GroupPresentationViews
GroupColorGrayscale
RefreshAllMenu
DataValidationMenu
GroupViews
GroupViewsShowHide
GroupViewZoom
GroupWindowAccess
FPTableAutoFormat

imageMso
FPTable
PageViewMenu
ShowTimeZones
ViewOnlineConnection
CLViewDialogHelpID
FileDocumentEncrypt
WordArtFormatDialog
MoreTextureOptions
TextFillColorMoreColorsDialog
ZoomFitToWindow
ZoomTwoPages
BorderTopNoToggle
BorderBottomNoToggle
BorderLeftNoToggle
BorderRightNoToggle
WindowSplitToggle
QuickPartsInsertFromOnline
JotShapeRectangle
JotShapeEllipse
JotShapeParallelogram
JotShapeDiamond
JotSendPdf
ProjectTaskDrivers
ProjectStatusReports
ProjectRecalcChangeHighlighting
ProjectAdvancedDesktopReporting
ProjectManageDeliverables
ProjectManageDependenciesOnDeliverables
JotLineColor
AddInsMenu

imageMso
GroupPrintPreviewPageSetup
GroupPrintPageBackground
ShowRuler
ViewDirectionMenu
JustifyThaiVertical
FileEmailAsPdfEmailAttachment
FileEmailAsXpsEmailAttachment
FontFillBackColorPicker
GroupArrangeOutlook
GroupTemplates
SelectMenuAccess
GoToMenuAccess
GroupQueryResults
GroupAdminister
GroupTableDesignShowHide
GroupPrintPreviewData
GroupPrintPreviewClosePreview
GroupFormatting
GroupQueryClose
GroupMacroClose
ObjectsGroupMenuOutlook
RegionLayoutMenu
ResponsesMenu
GroupOpen
SpellingMenu
GroupPrintPreviewZoom
PictureEffectsMenu
PictureShapeGallery
PictureBorderColorPickerClassic
GroupInsertShapes

imageMso
PhotoAlbumInsertMenu
GroupChartBackground
GroupChartAnalysis
ZoomToSelection
FileNewBlogPost
GroupBlogPublish
BlogPublishMenu
BlogPublish
BlogPublishDraft
BlogManageAccounts
GroupBlogProperties
BlogCategories
BlogCategoryInsert
BlogCategoriesRefresh
BlogOpenExisting
GroupBlogBasicText
GroupBlogInsertText
DeleteSlideContextual
AutoSigInsertPictureFromFile
AutoSigWebInsertHyperlink
GroupFind
ViewPreviousItemMenu
ViewNextItemMenu
ContactLinkMenu
NewTableStyleWord
CacheListData
AccessRefreshAllLists
AccessOfflineLists
AccessOnlineLists
GridlinesExcel

imageMso
UnmergeCells
MenuPublish
FileMenuPublishHeader
ChangeStylesMenu
GroupBlogInsertLinks
SharePointSiteRecycleBin
SubformMenu
LabelFontDialog
PrintDialogAccess
ForwardInForwardMenu
FileCompatibilityCheckerPowerPoint
SharingNone
AccessRecycleBin
FileCompatibilityCheckerWord
AccessRelinkLists
StopAnimation
ViewSideBySide
TableBackgroundPictureFill
GroupAttendeesMeetingSent
ImexRunImport
ImexRunExport
GroupTools
GroupFormattingControls
GroupControlAlignmentLayout
GroupDesignGridlines
GroupFormattingGridlines
GroupFieldsTools
GroupFontAccess
GroupDatasheetRelationships
GroupPositionLayout

imageMso
GroupControlPositionLayout
GroupControlSize
PrintPreviewZoomMenu
GroupMarginsAndPaddingControlLayout
RecordsDeleteColumn
ViewsAdpDiagramPrintPreview
UpgradePresentation
ChartShowDataContexttualMenu
ChartSourceDataContexttualMenu
FileSaveAsOtherFormats
FileSaveAsWordDocx
FileSaveAsWordDotx
FileSaveAsExcelXlsx
FileSaveAsExcelXlsxMacro
FileSaveAsExcelXlsb
FileSaveAsPowerPointPptx
FileSaveAsPowerPointPpsx
LockCell
PasteAsPictureMenu
GroupPivotActions
PivotTableSelectFlyout
ZoomCurrent100
Drawing1ColorPickerLineStyleWordArt
Drawing1ColorPickerFillWordArt
FontDialogPowerPoint
PowerPointParagraphDialog
PowerPointPageSetup
GroupDrawing2
ShapeQuickStylesHome
GalleryAllShapesAndTextboxes

imageMso
TableTextStylesGallery
GroupTextStylesTable
UpdateBibliography
ExportToAccess
BizBarPublishToSharePoint
BlogInsertCategories
NewMailMessageNumbered
NewAppointmentNumbered
NewMeetingRequestNumbered
NewContactNumbered
NewDistributionListNumbered
NewTaskNumbered
NewNoteNumbered
FileMenuSaveAsHeaderOutlook
FileMenuPrintHeaderOutlook
GroupRecover
SmartArtInsertBulletRTL
NewContactMenu
GroupTableLayout
ObjectsArrangeMenu
TextFillMoreTextures
FileMenuPrintHeaderAccess
ConvertDatabaseFormat
PivotShowOnlyTheTopMenu
PivotShowOnlyTheBottomMenu
GroupMacros
PlayMacro
MenuMacros
SharingOpenWssDocumentList
SharingOpenWssDiscussionList

imageMso
SharingOpenWssCalendar
SharingOpenWssContactList
SharingOpenWssTaskList
SharingOpenRssFeed
SharingOpenPublishedCalendar
SharingOpenWebCalendar
SharingOpenICalendar
SharingPreviewPublishedCalendar
SharingPreviewWssCalendar
SharingPreviewWssContactList
SharingPreviewWssTaskList
SharingPreviewWssDocumentList
SharingPreviewWssDiscussionList
SaveObjectAs
AdvertisePublishAs
UpgradeWorkbook
ReviewProtectDocumentMenu
ReviewProtectWorkbookMenu
GroupPermission
ReviewProtectPresentationMenu
BlogHomePage
GroupBlogProofing
GroupBlogStyles
EquationEdit
AlternativeText
ChartFormatLeaderLines
ThemeBrowseForThemes
FilePublishToSharePoint
FileCheckOutDiscard
GroupBlogSymbols

4 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- The 2007 Microsoft Office system
- Microsoft Office 2010 suites
- Microsoft Office 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

5 Change Tracking

This section identifies changes that were made to the [MS-CUSTOMUI] protocol document between the April 2014 and July 2014 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
1 Introduction	Removed product names from the description.	N	Content removed.
2.2.1 box (Box Grouping Container)	Revised the descriptions for the id and idQ attributes to remove references to the unused idMso attribute.	N	Content updated.
2.2.1 box (Box Grouping Container)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.2 button (Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.3 button (Unsize Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.3 button (Unsize Button)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.4 button (Button Inside of a Split Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.4 button (Button Inside of a Split Button)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.5 buttonGroup (Button Grouping Container)	Revised the descriptions for the id and idQ attributes to remove references to the unused idMso attribute.	N	Content updated.
2.2.5 buttonGroup (Button Grouping Container)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.6 checkBox (Check Box)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.6 checkBox (Check Box)	Revised description to remove references to the size and getSize attributes.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.7 comboBox (Combo Box)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.7 comboBox (Combo Box)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.8 command (Repurposed Command)	Revised the attribute descriptions to remove references to the unused id and idQ attributes.	N	Content updated.
2.2.8 command (Repurposed Command)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.9 commands (List of Repurposed Commands)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.10 contextualTabs (List of Contextual Tab Sets)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.11 control (Unsize Control Clone)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.11 control (Unsize Control Clone)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.12 control (Control Clone)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.13 control (Quick Access Toolbar Control Clone)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.14 customUI (Custom UI Document Root)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.15 dialogBoxLauncher (Dialog Box Launcher)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.16 documentControls (List of Document-Specific Quick Access Toolbar Controls)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.17 dropDown (Drop-down Control)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.17 dropDown (Drop-down Control)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.18 dynamicMenu (Unsize Dynamic Menu)	Added the namespace prefix for the schema fragment.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.18 dynamicMenu (Unsize Dynamic Menu)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.19 dynamicMenu (Dynamic Menu)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.20 editBox (Edit Box)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.20 editBox (Edit Box)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.21 gallery (Gallery)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.22 gallery (Unsize Gallery)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.22 gallery (Unsize Gallery)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.23 group (Group)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.24 item (Selection Item)	Revised the attribute descriptions to remove references to the unused idQ, idMso, getImage, showImage, getShowImage, getLabel, getScreentip, and getSupertip attributes.	N	Content updated.
2.2.24 item (Selection Item)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.25 labelControl (Text Label)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.25 labelControl (Text Label)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.26 menu (Unsize Menu)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.26 menu (Unsize Menu)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.27 menu (Menu with Title)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.27 menu (Menu with Title)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.28 menu (Menu)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.29	Added the namespace prefix for the	N	Content

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
menu (Dynamic Menu Root XML Element)	schema fragment.		updated.
2.2.30 menuSeparator (Menu Separator)	Revised the descriptions for the id and idQ attributes to remove references to the unused idMso attribute.	N	Content updated.
2.2.30 menuSeparator (Menu Separator)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.31 officeMenu (Office Menu)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.32 gat (Quick Access Toolbar)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.33 ribbon (Ribbon)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.34 separator (Separator)	Revised the descriptions for the id and idQ attributes to remove references to the unused idMso attribute.	N	Content updated.
2.2.34 separator (Separator)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.35 sharedControls (List of Shared Quick Access Toolbar Controls)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.36 splitButton (Unsize Split Button)	Updated the description of the getShowImage attribute to indicate that this attribute is mutually exclusive with the showImage attribute.	N	Content updated.
2.2.36 splitButton (Unsize Split Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.36 splitButton (Unsize Split Button)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.37 splitButton (Split Button with Title)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.37 splitButton (Split Button with Title)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.2.38 splitButton (Split Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.39 tab (Tab)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.40 tabs (List of Tabs)	Added the namespace prefix for the schema fragment.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.41 tabSet (Contextual Tab Set)	Revised the attribute descriptions to remove references to the unused id and idQ attributes.	N	Content updated.
2.2.41 tabSet (Contextual Tab Set)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.42 toggleButton (Unsize Toggle Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.43 toggleButton (Toggle Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.44 toggleButton (Toggle Button Inside of a Split Button)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.2.44 toggleButton (Toggle Button Inside of a Split Button)	Revised description to remove references to the size and getSize attributes.	N	Content updated.
2.3.1 ST_BoxStyle (Box Style)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.3 ST_GalleryItemWidthHeight (Gallery Item Width or Height)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.4 ST_GalleryRowColumnCount (Gallery Row or Column Count)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.5 ST_ID (Control ID)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.6 ST_ItemSize (Menu Item Size)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.7 ST_Keytip (Keytip)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.8 ST_LongString (Long String)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.9 ST_QID (Qualified Control ID)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.10 ST_Size (Control Size)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.11 ST_String (Short String)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.12 ST_StringLength (String Length)	Added the namespace prefix for the schema fragment.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.3.13 ST_UniqueID (Custom Control ID)	Added the namespace prefix for the schema fragment.	N	Content updated.
2.3.14 ST Uri (Image Relationship ID)	Added the namespace prefix for the schema fragment.	N	Content updated.

6 Index

C

[Change tracking](#) 546
Custom UI
 [parts](#) 7
Custom UI control id table
 [imageMso table](#) 436

E

[Elements](#) 9
 [box \(box grouping container\)](#) 9
 [button \(button inside of a split button\)](#) 32
 [button \(button\)](#) 13
 [button \(unsized button\)](#) 23
 [buttonGroup \(button grouping container\)](#) 41
 [checkBox \(check box\)](#) 45
 [comboBox \(combo box\)](#) 55
 [command \(repurposed command\)](#) 67
 [commands \(list of repurposed commands\)](#) 68
 [contextualTabs \(list of contextual tab sets\)](#) 69
 [control \(control clone\)](#) 77
 [control \(Quick Access Toolbar control clone\)](#) 87
 [control \(unsized control clone\)](#) 69
 [customUI \(custom UI document root\)](#) 96
 [dialogBoxLauncher \(dialog box launcher\)](#) 97
 [documentControls \(list of document-specific Quick Access Toolbar controls\)](#) 98
 [dropDown \(drop-down control\)](#) 99
 [dynamicMenu \(dynamic menu\)](#) 121
 [dynamicMenu \(unsized dynamic menu\)](#) 111
 [editBox \(edit box\)](#) 132
 [gallery \(gallery\)](#) 142
 [gallery \(unsized gallery\)](#) 159
 [group \(group\)](#) 175
 [item \(selection item\)](#) 182
 [labelControl \(text label\)](#) 185
 [menu \(dynamic menu root XML element\)](#) 224
 [menu \(menu with title\)](#) 204
 [menu \(menu\)](#) 214
 [menu \(unsized menu\)](#) 194
 [menuSeparator \(menu separator\)](#) 227
 [officeMenu \(Office menu\)](#) 230
 [qat \(Quick Access Toolbar\)](#) 231
 [ribbon \(ribbon\)](#) 232
 [separator \(separator\)](#) 233
 [sharedControls \(list of shared Quick Access Toolbar controls\)](#) 236
 [splitButton \(split button with title\)](#) 246
 [splitButton \(split button\)](#) 254
 [splitButton \(unsized split button\)](#) 237
 [tab \(tab\)](#) 263
 [tabs \(list of tabs\)](#) 268
 [tabSet \(contextual tab set\)](#) 268
 [toggleButton \(toggle button inside of a split button\)](#) 289
 [toggleButton \(toggle button\)](#) 279
 [toggleButton \(unsized toggle button\)](#) 270

G

[Glossary](#) 6

I

idMso tables
 [Excel 2007](#) 370
 [PowerPoint 2007](#) 408
 [Word 2007](#) 312
[Informative references](#) 6
[Introduction](#) 6

N

[Normative references](#) 6

P

Parts
 [additional part types](#) 7
 [quick access toolbar customizations part](#) 7
 [ribbon extensibility part](#) 8
[Product behavior](#) 545

R

References
 [informative](#) 6
 [normative](#) 6

S

[Simple types](#) 298
 [ST_BoxStyle \(box style\)](#) 298
 [ST_Delegate \(callback function name\)](#) 299
 [ST_GalleryItemWidthHeight \(gallery item width or height\)](#) 302
 [ST_GalleryRowColumnCount \(gallery row or column count\)](#) 302
 [ST_ID \(control identifier\)](#) 303
 [ST_ItemSize \(menu item size\)](#) 304
 [ST_Keytip \(key tip\)](#) 305
 [ST_LongString \(long string\)](#) 305
 [ST_QID \(qualified control identifier\)](#) 306
 [ST_Size \(control size\)](#) 308
 [ST_String \(short string\)](#) 308
 [ST_StringLength \(string length\)](#) 309
 [ST_UniqueID \(custom control identifier\)](#) 310
 [ST Uri \(image relationship identifier\)](#) 310

T

Tables
 [idMso table – Excel 2007](#) 370
 [idMso table – PowerPoint 2007](#) 408
 [idMso table – Word 2007](#) 312

[imageMso table](#) 436
[Tracking changes](#) 546