

[MS-EUMR]: Routing to Exchange Unified Messaging Extensions

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
12/12/2008	1.0		Initial version
02/13/2009	1.01		Revised and edited the technical content
03/13/2009	1.02		Edited the technical content
07/13/2009	1.03	Major	Revised and edited the technical content
08/28/2009	1.04	Editorial	Revised and edited the technical content
11/06/2009	1.05	Editorial	Revised and edited the technical content
02/19/2010	1.06	Editorial	Revised and edited the technical content
03/31/2010	1.07	Major	Updated and revised the technical content
04/30/2010	1.08	Editorial	Revised and edited the technical content
06/07/2010	1.09	Minor	Updated the technical content
06/29/2010	1.10	Editorial	Changed language and formatting in the technical content.
07/23/2010	1.10	No change	No changes to the meaning, language, or formatting of the technical content.
09/27/2010	2.0	Major	Significantly changed the technical content.
11/15/2010	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
06/10/2011	2.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	2.1	Minor	Clarified the meaning of the technical content.
04/11/2012	2.1	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	2.1	No change	No changes to the meaning, language, or formatting of the technical content.
10/08/2012	2.1.1	Editorial	Changed language and formatting in the technical content.
02/11/2013	2.1.1	No change	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
07/30/2013	2.2	Minor	Clarified the meaning of the technical content.

Table of Contents

1 Introduction	6
1.1 Glossary	6
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	7
1.3 Overview	8
1.4 Relationship to Other Protocols	8
1.5 Prerequisites/Preconditions	8
1.6 Applicability Statement	8
1.7 Versioning and Capability Negotiation	9
1.8 Vendor-Extensible Fields	9
1.9 Standards Assignments	9
2 Messages	10
2.1 Transport	10
2.2 Message Syntax	10
2.2.1 Ms-Mras-Address Header Field	10
2.2.2 Request-URI Header Field	10
2.2.3 User Notification Extensions	10
2.2.3.1 User Notification Description Element	10
2.2.3.2 User Event Description Element	11
2.2.3.3 Event Type Attribute	11
2.2.4 User Notification INVITE Request	12
2.2.4.1 From Header Field	12
2.2.4.2 Request-URI Header Field	12
2.2.4.3 SDP Content	12
2.2.5 User Notification INVITE Response	13
2.2.6 Option Tag Extensions	13
3 Protocol Details	14
3.1 Extensions for Routing to Exchange Unified Messaging Details	14
3.1.1 Abstract Data Model	14
3.1.2 Timers	14
3.1.3 Initialization	14
3.1.4 Higher-Layer Triggered Events	14
3.1.5 Message Processing Events and Sequencing Rules	14
3.1.5.1 Interacting with an Audio/Video Edge Server	15
3.1.5.2 Publishing a Quality of Experience Report	15
3.1.5.3 Processing a 302 Response	15
3.1.5.4 Generating a 101 Progress Report	16
3.1.5.5 Processing a 415 Response	16
3.1.5.6 Processing Other Responses	16
3.1.5.7 Retrying a Request	16
3.1.6 Timer Events	16
3.1.7 Other Local Events	16
3.2 User Notification Extensions Details	17
3.2.1 Abstract Data Model	17
3.2.2 Timers	17
3.2.3 Initialization	17
3.2.4 Higher-Layer Triggered Events	18

3.2.4.1	Missed Call Event.....	18
3.2.4.1.1	SIP Proxy Operation	18
3.2.4.2	Call Answered Event	18
3.2.4.2.1	SIP Proxy Operation	18
3.2.4.3	Call Forbidden Event	19
3.2.4.3.1	SIP Proxy Operation	19
3.2.5	Message Processing Events and Sequencing Rules.....	19
3.2.6	Timer Events	20
3.2.7	Other Local Events	20
4	Protocol Examples.....	21
4.1	Missed Call Event.....	21
4.2	Call Answered Event	21
4.3	Call Forbidden Event	22
5	Security.....	23
5.1	Security Considerations for Implementers.....	23
5.2	Index of Security Parameters	23
6	Appendix A: Full User Notification Format.....	24
7	Appendix B: Product Behavior	26
8	Change Tracking.....	28
9	Index	30

1 Introduction

The Routing to Exchange Unified Messaging Extensions Protocol specifies extensions, which consist of proprietary application extensions for routing calls to Exchange Unified Messaging (UM) voice mail and generating user notifications based on the Session Initiation Protocol (SIP) INFO method.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Augmented Backus-Naur Form (ABNF)
authentication
Coordinated Universal Time (UTC)
fully qualified domain name (FQDN)
server
XML

The following terms are defined in [\[MS-OFCGLOS\]](#):

200 OK
address-of-record
Audio/Video Edge Server (A/V Edge Server)
caller
dial plan
dialog
endpoint
Globally Routable User Agent URI (GRUU)
in-band provisioning
INVITE
long-term credentials
Multipurpose Internet Mail Extensions (MIME)
proxy
QoE Monitoring Server
Quality of Experience (QoE)
Session Description Protocol (SDP)
Session Initiation Protocol (SIP)
token
Uniform Resource Identifier (URI)
user agent client (UAC)
XML schema

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[IETF DRAFT-DIISIP-08] Levy, S. and Yang, J. R., "Diversion Indication in Session Initiation Protocol (SIP)", draft-levey-sip-diversion-08, February 2005, <http://tools.ietf.org/id/draft-levy-sip-diversion-08.txt>

[MS-AVEDGEA] Microsoft Corporation, "[Audio Video Edge Authentication Protocol](#)".

[MS-QoE] Microsoft Corporation, "[Quality of Experience Monitoring Server Protocol](#)".

[MS-SIPRE] Microsoft Corporation, "[Session Initiation Protocol \(SIP\) Routing Extensions](#)".

[MS-SIPREGE] Microsoft Corporation, "[Session Initiation Protocol \(SIP\) Registration Extensions](#)".

[MS-TURN] Microsoft Corporation, "[Traversal Using Relay NAT \(TURN\) Extensions](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC2327] Handley, M., and Jacobson, V., "SDP: Session Description Protocol", RFC 2327, April 1998, <http://www.ietf.org/rfc/rfc2327.txt>

[RFC2976] Donovan, S., "The SIP INFO Method", RFC 2976, October 2000, <http://www.rfc-editor.org/rfc/rfc2976.txt>

[RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and Schooler, E., "SIP: Session Initiation Protocol", RFC 3261, June 2002, <http://www.ietf.org/rfc/rfc3261.txt>

[RFC3892] Sparks, R., "The Session Initiation Protocol (SIP) Referred-By Mechanism", RFC 3892, September 2004, <http://www.rfc-editor.org/rfc/rfc3892.txt>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

[XML10] World Wide Web Consortium, "Extensible Markup Language (XML) 1.0 (Third Edition)", February 2004, <http://www.w3.org/TR/2004/REC-xml-20040204/>

[XMLNS] Bray, T., Hollander, D., Layman, A., et al., Eds., "Namespaces in XML 1.0 (Third Edition)", W3C Recommendation, December 2009, <http://www.w3.org/TR/2009/REC-xml-names-20091208/>

[XMLSCHEMA0] Fallside, D., and Walmsley, P., Eds., "XML Schema Part 0: Primer, Second Edition", W3C Recommendation, October 2004, <http://www.w3.org/TR/2004/REC-xmlschema-0-20041028/>

1.3 Overview

This protocol specifies **Session Initiation Protocol (SIP)** extensions that are used to route calls to Exchange Unified Messaging (UM) and to generate user notification email messages on call events.

These voice mail routing extensions have been designed to route calls to Exchange UM servers based on SIP. They provide mechanisms to identify the voice mail box for deposit and provide means for communicating the **Audio/Video Edge Server (A/V Edge Server)** information that can be used by UM servers while talking to external **callers**. These extensions are described in detail in section [3.1](#).

This protocol provides a way for a SIP **proxy** that implements the protocol described in [\[MS-SIPRE\]](#) to use UM servers to generate call notification email messages if one of the following events occurs during the processing of a call:

- the user missed the call because the caller hung up before the call could be routed to voice mail or otherwise answered.
- the call was answered by one of the targets specified in the user's routing script preamble. Routing script preamble and call processing extensions are described in [\[MS-SIPRE\]](#).
- the proxy was unable to route to one of the targets specified in the routing script preamble because of the lack of authorization.

These extensions are described in section [3.2](#).

1.4 Relationship to Other Protocols

This protocol defines an **XML schema** that supports various extensions specified in this protocol. For more information about **XML**, see [\[XML10\]](#), [\[XMLNS\]](#), and [\[XMLSCHEMA0\]](#).

The voice mail routing extensions specified in this protocol augment the routing extensions for routing calls based on the Routing Script Preamble as described in [\[MS-SIPRE\]](#).

This protocol incorporates the Session Initiation Protocol (SIP) protocols.

1.5 Prerequisites/Preconditions

This protocol assumes that the Session Initiation Protocol (SIP) server implements the Session Initiation Protocol Routing Extensions as described in [\[MS-SIPRE\]](#). This protocol also assumes that the **server (1)** has knowledge of each voice mail **dial plan** in the enterprise, the Unified Messaging (UM) servers associated with each dial plan, and which dial plan each user is associated with.

The prerequisites for SIP are also applicable for this protocol.

1.6 Applicability Statement

This protocol is applicable when both the SIP protocol server (1) and the voicemail server (1) support SIP, and intend to use the enhancements offered by this protocol.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

This protocol does not introduce a new transport to exchange messages, but is capable of being used with any transport used by Session Initiation Protocol (SIP).

2.2 Message Syntax

2.2.1 Ms-Mras-Address Header Field

This protocol defines a new header field called **Ms-Mras-Address**. The **Ms-Mras-Address** header field identifies the Audio/Video Edge Server (A/V Edge Server) that can be used by the voice mail server (1) when the caller **endpoint (5)** is external to the enterprise.

The following example is the **Augmented Backus-Naur Form (ABNF)**, as defined in [\[RFC5234\]](#), for the **Ms-Mras-Address** header field:

```
Ms-Mras-Address = "Ms-Mras-Address" HCOLON LWS LAQOUT SIP-URI RAQOUT
```

The voice mail server (1) can use the A/V Edge Server information to obtain **authentication (2) tokens**, as specified in [\[MS-AVEDGEA\].<1>](#)

2.2.2 Request-URI Header Field

This protocol defines certain restrictions on the **Request-URI** field value while routing an **INVITE** to a Unified Messaging (UM) server for a user. The **user** portion of the **URI** MUST be the name of the dial plan to which the user belongs. The **host** portion MUST be the UM server **fully qualified domain name (FQDN) (1)** and the **port** portion MUST be "5061". The URI MUST have a **transport parameter** with a value "tls". The URI MUST have a **maddr** parameter with the UM server FQDN (1) as its value. URI parameters are specified in [\[RFC3261\]](#) section 19.1.1.

2.2.3 User Notification Extensions

This section describes the User Notification Extensions used to notify the Unified Messaging (UM) server about user call events. The UM servers use this information to generate the following types of email messages:

- Missed call email messages
- Call Answered email messages
- Call Forbidden email messages

The User Notification events are delivered as **application/ms-rtc-usernotification+xml** content in the body of Session Initiation Protocol (SIP) INFO messages, as specified in [\[RFC2976\]](#). The complete schema is defined in section 6. Each notification message is generated as a result of some notification-worthy call event occurring while processing an audio INVITE request.

2.2.3.1 User Notification Description Element

Each INFO message contains a description of one User Notification Event. The **User** element MUST be a valid Session Initiation Protocol (SIP) URI that identifies the user that will receive the email notification. If the **EumProxyAddress** element is present, it MUST be the address string used by

Exchange Unified Messaging (UM) to uniquely identify the user. The **Time** element MUST be a string that corresponds to the time the event occurred in **Coordinated Universal Time (UTC)**.

The following schema definition is for a **user-notification-type** element:

```
<xs:complexType name="user-notification-type">
  <xs:sequence>
    <xs:element name="User" type="xs:string" />
    <xs:element name="EumProxyAddress" type="xs:string" minOccurs="0" />
    <xs:element name="Time" type="xs:string" />
    <xs:element name="Template" type="xs:string" fixed="RtcDefault" />
    <xs:element name="Event" type="event-type" />
  </xs:sequence>
</xs:complexType>
```

2.2.3.2 User Event Description Element

Each **Event** element MUST include **CallId** and **From** elements. The **CallId** element MUST contain the **Call-ID** header field value of the INVITE request associated with the event. The **From** element MUST contain the **From** header field value of the INVITE request associated with the event. If the **Subject** element is present, it MUST contain the **Subject** header field value in the corresponding INVITE. If the **Priority** element is present, it MUST contain the **Priority** header field value in the corresponding INVITE. If the **ConversationID** element is present, it MUST contain the **Ms-Conversation-ID** header field value in the corresponding INVITE. If the **ReferredBy** element is present, it MUST contain the **referrer-uri** of the **Referred-By** header, as specified in [RFC3892](#), in the corresponding INVITE. If the **Target** element is present, it MUST contain the **Request-URI** used when routing the INVITE associated with the event.

If the **AnsweredBy** element is present, it MUST contain the URI present in the **P-Asserted-Identity** header found in the response to the INVITE.

The following schema definition is for an **event-type** element:

```
<xs:complexType name="event-type">
  <xs:sequence>
    <xs:element name="CallId" type="xs:string" />
    <xs:element name="From" type="xs:string" />
    <xs:element name="Subject" type="xs:string" minOccurs="0" />
    <xs:element name="Priority" type="xs:string" minOccurs="0" />
    <xs:element name="ConversationID" type="xs:string" minOccurs="0" />
    <xs:element name="ReferredBy" type="xs:string" minOccurs="0" />
    <xs:element name="Target" type="xs:string" minOccurs="0" />
    <xs:element name="TargetClass" type="target-class-type" minOccurs="0" />
    <xs:element name="AnsweredBy" type="xs:string" minOccurs="0" />
    <xs:element name="MissedReason" type="missed-reason-type" minOccurs="0" />
  </xs:sequence>
  <xs:attribute name="type" type="event-type-attribute-type" use="required" />
</xs:complexType>
```

2.2.3.3 Event Type Attribute

Each **Event** element MUST contain a **type** attribute. If the **type** attribute has the value "answered", the **Target**, **TargetClass**, and **AnsweredBy** elements MUST be present in the parent **Event**. If the **type** attribute has the value "forbidden", the **Target** and **TargetClass** elements MUST be present in the parent **Event**.

The following schema definition is for an **event-type-attribute-type** attribute:

```
<xs:simpleType name = "event-type-attribute-type">
  <xs:restriction base="xs:string">
    <xs:enumeration value="missed"/>
    <xs:enumeration value="answered"/>
    <xs:enumeration value="forbidden"/>
  </xs:restriction>
</xs:simpleType>
```

2.2.4 User Notification INVITE Request

2.2.4.1 From Header Field

This protocol specifies additional restrictions on the **From** header field syntax, as specified in [\[RFC3261\]](#), for the INVITE **dialog** established to send user event notifications to Unified Messaging (UM) servers.

The original Augmented Backus-Naur Form (ABNF), as defined in [\[RFC5234\]](#), for **from-spec**, as specified in [\[RFC3261\]](#) section 25, is replaced with the following:

```
from-spec = spl-user-identity *(SEMI from-param)
spl-user-identity = LAQUOT "sip" HCOLON "A410AA79-D874-4e56-9B46-709BDD0EB850" RAQUOT
```

2.2.4.2 Request-URI Header Field

This protocol specifies additional restrictions on the **Request-URI** header field syntax, as specified in [\[RFC3261\]](#), for the INVITE dialog established to send user event notifications to Unified Messaging (UM) servers. The **user** portion of the **Request-URI** header field MUST be empty. The **host** portion MUST be the fully qualified domain name (FQDN) (1) of the UM server and the **transport parameter** MUST have the value "tls". In addition, the **Request-URI** MUST have an **opaque parameter** with a **value** of "app:rtcevent". URI parameters are specified in [\[RFC3261\]](#) section 19.1.1.

2.2.4.3 SDP Content

The INVITE dialog that is established to send user event notifications to Unified Messaging (UM) servers MUST contain a **Session Description Protocol (SDP)** body, as specified in [\[RFC2327\]](#).

The SDP body MUST include a **media-field** with the following values:

- the value of **media** MUST be "application".
- the value of **port** MUST be "9".
- the value of **proto** MUST be "SIP".
- only one **fmt** is present, and its value is "*".

The SDP body MUST also have the following attribute values:

- an **attribute** line with "sendonly" as the value of **att-field**.

- an **attribute** line with "accept-types" as the value of **att-field** and "application/ms-rtc-usernotification+xml" as the value of **att-value**.

2.2.5 User Notification INVITE Response

The **200 OK** response from the Unified Messaging (UM) server MUST also contain a Session Description Protocol (SDP) body.

The SDP body MUST include a **media-field** with the following values:

- the value of **media** MUST be "application".
- the value of **port** MUST be "9".
- the value of **proto** MUST be "SIP".
- only one **fmt** is present, and its value is "*".

The SDP body MUST also have the following attribute values:

- an **attribute** line with "recvonly" as the value of **att-field**.
- an **attribute** line with "accept-types" as the value of **att-field** and "application/ms-rtc-usernotification+xml" as the value of **att-value**.
- an **attribute** line with "ms-rtc-accept-eventtemplates" as the value of **att-field** and "RtcDefault" as the value of **att-value**.

2.2.6 Option Tag Extensions

This protocol defines one new option tag for use in the **Supported** header field. The new tag extends the set of option tags as specified in [\[RFC3261\]](#).

Ms-Fe: This option tag is for supporting the routing extensions described in this protocol. The inclusion of this tag in the **Supported** header field of the INVITE request routed to the voice mail server (1) indicates that the Session Initiation Protocol (SIP) proxy adheres to the specifications of this protocol. [<2>](#)

3 Protocol Details

3.1 Extensions for Routing to Exchange Unified Messaging Details

An incoming audio INVITE is processed based on a routing script preamble published by the user, as specified in [\[MS-SIPRE\]](#). Under various circumstances, the proxy can decide to route the call to the user's voice mail, as specified in [\[MS-SIPRE\]](#) section 3.8.5. The extensions for routing to Exchange Unified Messaging (UM) are also applicable when the **Request-URI** matches the Augmented Backus-Naur Form (ABNF) rules, as defined in [\[RFC5234\]](#), for **voice-mail-gruu** syntax, as specified in [\[MS-SIPRE\]](#) section 2.2.2. This protocol is not applicable if the user is not UM-enabled.

This protocol provides a mechanism for routing such calls to Exchange UM if the user is UM-enabled. This protocol also defines a mechanism for providing the UM server with the Session Initiation Protocol (SIP) URI of an Audio/Video Edge Server (A/V Edge Server), if available. The UM server uses this URI to obtain authentication (2) tokens when needed, as specified in [\[MS-AVEDGEA\]](#).

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

A Session Initiation Protocol (SIP) proxy compliant with this protocol maintains a database of all the dial plans in the enterprise and all the Unified Messaging (UM) servers in each dial plan. In addition, the proxy also maintains a mapping of all UM-enabled users and their corresponding dial plans. In addition, if any Audio/Video Edge Servers (A/V Edge Servers) are present in the deployment, the SIP proxy stores the **Globally Routable User Agent URI (GRUU)** of the A/V Edge Server in memory.

3.1.2 Timers

A **Unified Messaging server** timer starts when the INVITE is routed to a Unified Messaging (UM) server. The amount of time to wait **MUST** be less than 180 seconds. The recommended wait time is 5 seconds.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

When the Session Initiation Protocol (SIP) proxy routes an INVITE to voice mail based on rules as specified in [\[MS-SIPRE\]](#) or when an INVITE with a **voice-mail-gruu** (as specified in [\[MS-SIPRE\]](#) section 2.2.2) arrives, and the user is enabled for Exchange Unified Messaging (UM), the proxy **MUST** process the request as follows:

1. If the INVITE already contains any **Diversion** headers, as specified in [\[IETF DRAFT-DIISIP-08\]](#), these headers **MUST** be removed before forwarding the request to Exchange UM.

2. If the **user** and **host** portions of the **Request-URI** field are not the same as those of the **From** header field, the proxy MUST add a **Diversion** header with **name-addr** equal to the SIP URI in the **Request-URI** field value without any **uri-parameters** or **headers**, as specified in [\[RFC3261\]](#).
3. The UM server can request the provisioning information from the SIP proxy to detect the Globally Routable User Agent URI (GRUU) of the Audio/Video Edge Server (A/V Edge Server).[<3>](#) The **QoE Monitoring Server** protocol and the message format for **in-band provisioning** requests to obtain provisioning information are specified in [\[MS-SIPREGE\]](#) section 3.3.
4. If an A/V Edge Server is configured, the proxy MUST add an **Ms-Mras-Address** header with the value of the A/V Edge Server GRUU, as specified in [\[MS-SIPRE\]](#). The **Ms-Mras-address** header in the incoming INVITE can be the secondary source to detect the A/V Edge Server GRUU in the absence of provisioning information.[<4>](#)
5. The proxy SHOULD[<5>](#) include the **Ms-Fe** option tag in the **Supported** header field of the request if one is not already present.
6. The proxy MUST decide on an ordering of the UM servers in the user's dial plan and route the INVITE to the first UM server. The **Request-URI** MUST be constructed as specified in section [2.2.2](#).
7. If there are multiple UM servers in the users dial plan with different versions, the proxy must restrict the ordering to UM servers with the highest version. Similarly, if at least one UM server in the user's dial plan is a front end or front end array, then the proxy SHOULD use only the front ends or arrays when determining the ordering[<6>](#).
8. The proxy MUST start the **Unified Messaging server** timer.
9. Outgoing messages from Exchange UM can include an **Ms-fe** header parameter containing its specific fully qualified domain name (FQDN) (1) value. The proxy MUST be able to handle the contact header with the **Ms-fe** parameter. The syntax and handling for the **Ms-Fe** parameter is specified in [\[MS-SIPRE\]](#).

3.1.5.1 Interacting with an Audio/Video Edge Server

The Unified Messaging (UM) server can request **long-term credentials** from the Audio/Video Edge Server (A/V Edge Server).[<7>](#) The protocol and message format for requesting an authentication (2) token is specified in [\[MS-AVEDGEA\]](#) section 2. When the caller endpoint (5) is external to the enterprise, the UM server can use the long-term credentials obtained from the A/V Edge Server to communicate with the A/V Edge Server, as specified in [\[MS-TURN\]](#) section 3.

3.1.5.2 Publishing a Quality of Experience Report

If a QoE Monitoring Server is detected from provisioning data, the Unified Messaging (UM) server can publish a **Quality of Experience (QoE)** report at the end of every audio call to the QoE Monitoring Server.[<8>](#) The format and protocol for publishing a QoE report is specified in [\[MS-QoE\]](#) section 3.

3.1.5.3 Processing a 302 Response

The Unified Messaging (UM) server can return a 302 Redirect response to the INVITE.[<9>](#) The Session Initiation Protocol (SIP) proxy implementing this protocol MUST process the 302 response without sending it back to the caller. The INVITE MUST be redirected to the UM server identified in the **contact** header field value of the 302 response if the following conditions are met:

- the 302 response came from the UM server that was selected.
- there is only one **contact** listed in the 302 response.
- the **contact** header field value identifies a UM server that is in the user's dial plan.
- no more than four previous 302 responses were processed in relation to routing this INVITE to this particular UM server.

If any one of the preceding conditions is not met, the proxy MUST retry the next UM server, as specified in section [3.1.5.7](#).

3.1.5.4 Generating a 101 Progress Report

Any time the INVITE is routed to a new Unified Messaging (UM) server, the Session Initiation Protocol (SIP) proxy SHOULD generate a 101 Progress response and send it back to the calling **user agent client (UAC)**.

3.1.5.5 Processing a 415 Response

If a Unified Messaging (UM) server returns a 415 response and the INVITE has multipart **Multipurpose Internet Mail Extensions (MIME)** content, the proxy MUST clear the UM server's ordering list and process the 415 response as specified in [\[MS-SIPRE\]](#) section 3.9.5.5. If a fresh INVITE is sent as a result of this processing, the proxy MUST redo the steps listed in section [3.1.5](#).

3.1.5.6 Processing Other Responses

Any response with a status code from 100 through 299, inclusive, MUST be processed as specified in [\[RFC3261\]](#) section 13.2.2.

If the Unified Messaging (UM) server returns any other response, the proxy MUST retry the request with the next server (1), as specified in section [3.1.5.7](#).

3.1.5.7 Retrying a Request

If the Unified Messaging (UM) server returns any failure response, as described in section [3.1.5.6](#), or if the **Unified Messaging server** timer expires, the next UM server in the list MUST be selected and the request MUST be routed to that server (1).

When selecting the next UM server, the UM server version and ordering to UM servers restrictions specified in step 7 of section [3.1.5](#) MUST be followed [<10>](#).

If all servers (1) in the list have been attempted, the call SHOULD be terminated with a response code 480. [<11>](#)

If the request was routed to a new UM server, the **Unified Messaging server** timer MUST be restarted.

3.1.6 Timer Events

When the **Unified Messaging server** timer expires, the request MUST be routed to the next Unified Messaging (UM) server in the list, as specified in section [3.1.5.7](#).

3.1.7 Other Local Events

None.

3.2 User Notification Extensions Details

This protocol specifies a mechanism for sending call event email notifications to users through Exchange Unified Messaging (UM). The event information is sent to the UM server by using the Session Initiation Protocol (SIP) INFO method, as specified in [\[RFC2976\]](#), over an already established SIP INVITE dialog. The body of the INFO message MUST adhere to the syntax specified in section [2.2.3](#). Call event notifications MUST NOT be sent for users who are not UM-enabled. The following events can trigger the User Notification extensions [<12>](#):

- **Missed call:** The caller hung up before the call was answered or routed to voice mail.
- **Team/Delegate pick up:** The call was answered by a team member or delegate. Team and delegate ringing are specified in [\[MS-SIPRE\]](#).
- **Call Forwarded:** The call was answered by the target defined in the user's routing preamble as the forwarding destination.
- **Call Forwarding Failed:** An attempt to forward the call was made, but it failed because the configured destination was invalid or not permitted by administrative policy.

3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

A Session Initiation Protocol (SIP) proxy that implements this protocol MUST maintain a database of all dial plans in the enterprise and all the Unified Messaging (UM) servers in each dial plan. When a call event occurs that requires an email notification to be sent to the user, the proxy MUST establish a SIP INVITE dialog with one of the UM servers in the user's dial plan if one does not already exist. The information about the event is then sent to the UM server using the INFO method on this dialog.

3.2.2 Timers

A **User Notification Inactivity** timer MUST start when an INVITE dialog is established with a Unified Messaging (UM) server. The wait time for this timer is 10 minutes.

3.2.3 Initialization

A Session Initiation Protocol (SIP) proxy implementing this protocol MUST establish a SIP INVITE dialog with one of the Unified Messaging (UM) servers in the user's dial plan before sending the event information. The proxy can randomly pick a UM server from the list [<13>](#). The proxy MUST establish a Mutual-TLS (MTLS) connection with the selected UM server and construct the INVITE as specified in section [2.2.4](#). After the INVITE dialog is established, the **User Notification Inactivity** timer MUST be started.

If a dialog already exists with a UM server in the user's dial plan, that dialog MUST be reused.

3.2.4 Higher-Layer Triggered Events

3.2.4.1 Missed Call Event

When processing an audio call targeted at a user, as specified in [\[MS-SIPRE\]](#), if the caller hangs up before the call was answered or routed to voice mail, information about the missed call event MUST be sent to the Unified Messaging (UM) server if the user is UM-enabled. A missed call event MUST also be raised if all destinations, as listed in the routing script preamble, returned a negative response code unless the INVITE has an **Ms-Sensitivity** header with the value "private-no-diversion", as specified in [\[MS-SIPRE\]](#).

3.2.4.1.1 SIP Proxy Operation

When a missed call event occurs for a user who is enabled for Exchange Unified Messaging (UM) on a Session Initiation Protocol (SIP) proxy compliant with this protocol, the proxy MUST send information about the missed call event to a UM server on the user's dial plan by sending an INFO request on an already existing INVITE dialog. If a dialog does not already exist, the proxy MUST establish one, as described in section [3.2.3](#).

The INFO request MUST have a **Content-Type** header with "application/ms-rtc-usernotification+xml" as its value. The body of the request MUST conform to the User Notification format, as specified in section [2.2.3](#). If the caller hung up the call, the **MissedReason** element MUST contain "CallerReleased". If all destinations returned a negative response code, the **MissedReason** element MUST contain "Declined".

The **Subject**, **Priority**, **ConversationID**, and **ReferredBy** elements MUST be present if their corresponding headers are present in the INVITE associated with the event.

The **type** attribute of the **Event** element MUST be set to "missed".

After the INFO request has been sent, the **User Notification Inactivity** timer for that UM server MUST be restarted.

3.2.4.2 Call Answered Event

When processing an audio call targeted at a user, as specified in [\[MS-SIPRE\]](#), if the call was answered by a destination other than the registered endpoint (5) associated with the **address-of-record** in the **Request-URI** header field or the simultaneous ring destination, information about the call answered event MUST be sent to the Unified Messaging (UM) server if the user is UM-enabled. A call is considered to be answered if one of the destinations responded with a 200, 303, or 605 response code.

3.2.4.2.1 SIP Proxy Operation

When a call answered event occurs for a user who is enabled for Exchange Unified Messaging (UM) on a Session Initiation Protocol (SIP) proxy compliant with this protocol, the proxy MUST send information about the call answered event to a UM server on the user's dial plan by sending an INFO request on an already existing INVITE dialog. If a dialog does not already exist, the proxy MUST establish one, as described in section [3.2.3](#).

The INFO request MUST have a **Content-Type** header with "application/ms-rtc-usernotification+xml" as its value. The body of the request MUST conform to the User Notification format, as specified in section [2.2.3](#).

The **Target** and **TargetClass** elements MUST be present. The **Target** element MUST contain the **Request-URI** used when routing the INVITE. If the destination that answered the call was rung as a part of team or delegate ringing, the **TargetClass** MUST be "secondary". Otherwise, the **TargetClass** MUST be "primary".

If the response that triggered the call answered event has a **P-Asserted-Identity** header, the **AnsweredBy** element MUST contain the URI present in the **P-Asserted-Identity** header.

The **Subject**, **Priority**, **ConversationID**, and **ReferredBy** elements MUST be present if their corresponding headers are present in the INVITE associated with the event.

The **type** attribute of the **Event** element MUST be set to "answered".

After the INFO request has been sent, the **User Notification Inactivity** timer for that UM server MUST be restarted.

3.2.4.3 Call Forbidden Event

When processing an audio call targeted at a user, as specified in [\[MS-SIPRE\]](#), if the call was routed to a destination other than the registered endpoints (5) associated with the address-of-record in the **Request-URI** header field and a 403 response was received on that client transaction, information about the call forbidden event MUST be sent to a Unified Messaging (UM) server if the user is UM-enabled.

3.2.4.3.1 SIP Proxy Operation

When a call forbidden event occurs for a user who is enabled for Exchange Unified Messaging (UM) on a Session Initiation Protocol (SIP) proxy compliant with this protocol, the proxy MUST send information about the call forbidden event to a UM server on the user's dial plan by sending an INFO request on an already existing INVITE dialog. If a dialog does not already exist, the proxy MUST establish one, as described in section [3.2.3](#).

The INFO request MUST have a **Content-Type** header with "application/ms-rtc-usernotification+xml" as its value. The body of the request MUST conform to the User Notification format, as specified in section [2.2.3](#).

The **Target** and **TargetClass** elements MUST be present. The **Target** element MUST contain the **Request-URI** used when routing the INVITE. If the destination was rung as a part of team or delegate ringing, the SIP proxy SHOULD NOT send a call forbidden event. If such an event is sent, the value of **TargetClass** MUST be "secondary". If the destination was not a part of team or delegate ringing, the value of **TargetClass** MUST be "primary".

The **Subject**, **Priority**, **ConversationID**, and **ReferredBy** elements MUST be present if their corresponding headers are present in the INVITE associated with the event.

The **type** attribute of the **Event** element MUST be set to "forbidden".

After the INFO request has been sent, the **User Notification Inactivity** timer for that UM server MUST be restarted.

3.2.5 Message Processing Events and Sequencing Rules

None.

3.2.6 Timer Events

When the **User Notification Inactivity** timer associated with a Unified Messaging (UM) server expires, the INVITE dialog SHOULD be terminated. If a new notification needs to be sent to this UM server later, a new INVITE dialog SHOULD be established with it.

3.2.7 Other Local Events

None.

4 Protocol Examples

4.1 Missed Call Event

The following example is an INFO dialog that includes a user notification of a missed call event. For more information, see section [3.2.4.1](#).

```
INFO sip:exchange-um1.contoso.com:5061;transport=Tls SIP/2.0
FROM: <sip:A410AA79-D874-4e56-9B46-709BDD0EB850>;epid=12E34CB0DB;tag=806bdbd128
TO: <sip:exchange-
um1.contoso.com;opaque=app:rtcevent;transport=tls>;epid=9EEC660CCD;tag=826c5fb8f
CSEQ: 7 INFO
CALL-ID: 63536088-9a24-4b36-a671-82c5de77de9c
CONTENT-TYPE: application/ms-rtc-usernotification+xml

<?xml version="1.0" encoding="us-ascii" ?>
<UserNotification>
  <User>sip:user@example.com</User>
  <EumProxyAddress>EUM:user@contoso.com;phone-context=dpl.contoso.com</EumProxyAddress>
  <Time>2006-05-12 01:33:32Z</Time>
  <Template>RtcDefault</Template>
  <Event type="missed">
    <CallId>234d82934091df92034ad3e329fae03234</CallId>
    <From>sip:someuser@contoso.com</From>
    <Subject>RE: Quote for widgets</Subject>
    <ConversationID>Aca6SdRQ/SvHLJIHDHoWAEvg==</ConversationID>
    <MissedReason>Declined</MissedReason>
  </Event>
</UserNotification>
```

4.2 Call Answered Event

The following example is an INFO dialog that includes a user notification of an answered call event. For more information, see section [3.2.4.2](#).

```
INFO sip:exchange-um1.contoso.com:5061;transport=Tls SIP/2.0
FROM: <sip:A410AA79-D874-4e56-9B46-709BDD0EB850>;epid=12E34CB0DB;tag=806bdbd128
TO: <sip:exchange-
um1.contoso.com;opaque=app:rtcevent;transport=tls>;epid=9EEC660CCD;tag=826c5fb8f
CSEQ: 6 INFO
CALL-ID: a7e36088-9a24-4b36-a671-82c5de77de9c
CONTENT-TYPE: application/ms-rtc-usernotification+xml

<?xml version="1.0" encoding="us-ascii" ?>
<UserNotification>
  <User>sip:user@contoso.com</User>
  <EumProxyAddress>EUM:user@contoso.com;phone-context=dpl.contoso.com</EumProxyAddress>
  <Time>2006-05-02 12:53:32Z</Time>
  <Template>RtcDefault</Template>
  <Event type="answered">
    <CallId>234d82934091df92034ad3e329fae03234</CallId>
    <From>sip:someuser@contoso.com</From>
    <Subject>RE: Car pool</Subject>
    <ConversationID>Aca6SdRQ/SvHLJIHDHoWAEvg==</ConversationID>
    <Target>sip:teammember@contoso.com</Target>
    <TargetClass>secondary</TargetClass>
  </Event>
</UserNotification>
```

```
<AnsweredBy>sip:teammember@contoso.com</AnsweredBy>
</Event>
</UserNotification>
```

4.3 Call Forbidden Event

The following example is an INFO dialog that includes a user notification of a forbidden call event. For more information, see section [3.2.4.3](#).

```
INFO sip:exchange-um1.contoso.com:5061;transport=Tls SIP/2.0
FROM: <sip:A410AA79-D874-4e56-9B46-709BDD0EB850>;epid=12E34CB0DB;tag=806bdbd128
TO: <sip:exchange-
um1.contoso.com;opaque=app:rtcevent;transport=tls>;epid=9EEC660CCD;tag=826c5fb8f
CSEQ: 10 INFO
CALL-ID: d5b36088-9a24-4b36-a671-82c5de77de9c
CONTENT-TYPE: application/ms-rtc-usernotification+xml

<?xml version="1.0" encoding="us-ascii" ?>
<UserNotification>
  <User>sip:user@contoso.com</User>
  <EumProxyAddress>EUM:user@contoso.com;phone-context=dp1.contoso.com</EumProxyAddress>
  <Time>2006-05-02 18:53:32Z</Time>
  <Template>RtcDefault</Template>
  <Event type="forbidden">
    <CallId>234d82934091df92034ad3e329fae03234</CallId>
    <From>sip:someuser@contoso.com</From>
    <Subject>Pricing figures</Subject>
    <Priority>High</Priority>
    <ConversationID>Aca6SdRQ/SvHLJIHDHoWAEvg==</ConversationID>
    <Target>sip:+145532290933@contoso.com;user=phone</Target>
    <TargetClass>primary</TargetClass>
  </Event>
</UserNotification>
```

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

6 Appendix A: Full User Notification Format

For ease of implementation, the full user notification format is provided as follows:

```
<?xml version="1.0" encoding="utf-8"?>
<xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema" elementFormDefault="unqualified"
attributeFormDefault="unqualified">

  <xs:simpleType name = "missed-reason-type">
    <xs:restriction base="xs:string">
      <xs:enumeration value="CallerReleased"/>
      <xs:enumeration value="Declined"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name = "target-class-type">
    <xs:restriction base="xs:string">
      <xs:enumeration value="primary"/>
      <xs:enumeration value="secondary"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:simpleType name = "event-type-attribute-type">
    <xs:restriction base="xs:string">
      <xs:enumeration value="missed"/>
      <xs:enumeration value="answered"/>
      <xs:enumeration value="forbidden"/>
    </xs:restriction>
  </xs:simpleType>

  <xs:complexType name="event-type">
    <xs:sequence>
      <xs:element name="CallId" type="xs:string" />
      <xs:element name="From" type="xs:string" />
      <xs:element name="Subject" type="xs:string" minOccurs="0" />
      <xs:element name="Priority" type="xs:string" minOccurs="0" />
      <xs:element name="ConversationID" type="xs:string" minOccurs="0" />
      <xs:element name="ReferredBy" type="xs:string" minOccurs="0" />
      <xs:element name="Target" type="xs:string" minOccurs="0" />
      <xs:element name="TargetClass" type="target-class-type" minOccurs="0" />
      <xs:element name="AnsweredBy" type="xs:string" minOccurs="0" />
      <xs:element name="MissedReason" type="missed-reason-type" minOccurs="0" />
    </xs:sequence>
    <xs:attribute name="type" type="event-type-attribute-type" use="required" />
  </xs:complexType>

  <!-- Root document defintion -->
  <xs:complexType name="user-notification-type">
    <xs:sequence>
      <xs:element name="User" type="xs:string" />
      <xs:element name="EumProxyAddress" type="xs:string" minOccurs="0" />
      <xs:element name="Time" type="xs:string" />
      <xs:element name="Template" type="xs:string" fixed="RtcDefault" />
      <xs:element name="Event" type="event-type" />
    </xs:sequence>
  </xs:complexType>

  <xs:element name="UserNotification" type="user-notification-type" />


```


</xs:schema>

7 Appendix B: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2007 Service Pack 1 (SP1)
- Microsoft Exchange Server 2010
- Microsoft Office Communications Server 2007
- Microsoft Office Communications Server 2007 R2
- Microsoft Office Communicator 2007
- Microsoft Office Communicator 2007 R2
- Microsoft Lync 2010
- Microsoft Lync Server 2010
- Microsoft Lync 2013
- Microsoft Lync Server 2013
- Microsoft Exchange Server 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.1:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

[<2> Section 2.2.6:](#) Office Communications Server 2007, Office Communicator 2007: This behavior is not supported. This behavior was added in relation to Knowledge Base Article 972700, July 2009 hotfix. This hotfix applies to Office Communications Server 2007 R2 and Office Communicator 2007 R2.

[<3> Section 3.1.5:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

[<4> Section 3.1.5:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

[<5> Section 3.1.5:](#) Office Communications Server 2007, Office Communicator 2007: This behavior is not supported. This behavior was added in relation to Knowledge Base Article 972700, July 2009 hotfix. This hotfix applies to Office Communications Server 2007 R2 and Office Communicator 2007 R2.

[<6> Section 3.1.5:](#) Office Communications Server 2007, Office Communicator 2007: This behavior is not supported.

[<7> Section 3.1.5.1:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

[<8> Section 3.1.5.2:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

[<9> Section 3.1.5.3:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

[<10> Section 3.1.5.7:](#) Office Communications Server 2007, Office Communicator 2007: This behavior is not supported.

[<11> Section 3.1.5.7:](#) Office Communications Server 2007, Office Communications Server 2007 R2: In these releases, the call was terminated with the lowest numbered response among all the final responses received.

[<12> Section 3.2:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

[<13> Section 3.2.3:](#) Office Communications Server 2007, Office Communicator 2007, Office Communications Server 2007 R2, Office Communicator 2007 R2: This behavior is not supported.

8 Change Tracking

This section identifies changes that were made to the [MS-EUMR] protocol document between the February 2013 and July 2013 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.2.3.1 User Notification Description Element	Updated "example is" to "schema definition is for".	N	Content updated.
2.2.3.2 User Event Description Element	Updated "example is" to "schema definition is for".	N	Content updated.
2.2.3.3 Event Type Attribute	Updated "example is" to "schema definition is for".	N	Content updated.
3.1.5 Message Processing Events and Sequencing Rules	Updated the term "must" to "SHOULD".	N	Content updated.
3.1.5.7 Retrying a Request	Updated the "CAFÉ " to "ordering to UM servers".	N	Content updated.
3.2.4.3.1 SIP Proxy Operation	Corrected the link "section 3.2.3".	N	Content updated.

9 Index

A

Abstract data model
[routing to Exchange UM](#) 14
[user notification](#) 17
[Applicability](#) 8

C

[Call answered event](#) 18
[example](#) 21
[SIP proxy operation](#) 18
[Call forbidden event](#) 19
[example](#) 22
[SIP proxy operation](#) 19
[Capability negotiation](#) 9
[Change tracking](#) 28

D

Data model - abstract
[routing to Exchange UM](#) 14
[user notification](#) 17

E

Elements
[event-type](#) 11
[event-type-attribute-type](#) 11
[user-notification-type](#) 10
Examples
[call answered event](#) 21
[call forbidden event](#) 22
[missed call event](#) 21

F

[Fields - vendor-extensible](#) 9

G

[Glossary](#) 6

H

Higher-layer triggered events
[routing to Exchange UM](#) 14
user notification
[call answered](#) 18
[SIP proxy operation](#) 18
[call forbidden](#) 19
[SIP proxy operation](#) 19
[missed call](#) 18
[SIP proxy operation](#) 18

I

[Implementer - security considerations](#) 23

[Index of security parameters](#) 23
[Informative references](#) 7
Initialization
[routing to Exchange UM](#) 14
[user notification](#) 17
[Introduction](#) 6

L

Local events
[routing to Exchange UM](#) 16
[user notification](#) 20

M

Message processing
[routing to Exchange UM](#) 14
[101 Progress report](#) 16
[302 Redirect response](#) 15
[415 response](#) 16
[interacting with an Audio/Video Edge Server](#) 15
[other responses](#) 16
[QoE report](#) 15
[retry request](#) 16
[user notification](#) 19

Messages

[Ms-Mras-Address Header Field](#) 10
[Option Tag Extensions](#) 13
[Request-URI Header Field](#) 10
[transport](#) 10
[User Notification Extensions](#) 10
[user event description](#) 11
[event type attribute type](#) 11
[user notification description](#) 10
User Notification INVITE Request
[From header field](#) 12
[Request-URI header field](#) 12
[SDP body](#) 12
[User Notification INVITE Response](#) 13
[Missed call event](#) 18
[example](#) 21
[SIP proxy operation](#) 18
[Ms-Mras-Address Header Field message](#) 10

N

[Normative references](#) 7

O

[Option Tag Extensions message](#) 13
[Overview \(synopsis\)](#) 8

P

[Parameters - security index](#) 23
[Preconditions](#) 8
[Prerequisites](#) 8

[Product behavior](#) 26

R

[References](#) 7

[informative](#) 7

[normative](#) 7

[Relationship to other protocols](#) 8

[Request-URI Header Field message](#) 10

Routing to Exchange UM

[abstract data model](#) 14

[higher-layer triggered events](#) 14

[initialization](#) 14

[local events](#) 16

[message processing](#) 14

[101 Progress report](#) 16

[302 Redirect response](#) 15

[415 response](#) 16

[interacting with an Audio/Video Edge Server](#) 15

[other responses](#) 16

[QoE report](#) 15

[retry request](#) 16

[overview](#) 14

[sequencing rules](#) 14

[101 Progress report](#) 16

[302 Redirect response](#) 15

[415 response](#) 16

[interacting with an Audio/Video Edge Server](#) 15

[other responses](#) 16

[QoE report](#) 15

[retry request](#) 16

[timer events](#) 16

[timers](#) 14

S

Schema

[user notification](#) 24

Security

[implementer considerations](#) 23

[parameter index](#) 23

Sequencing rules

[routing to Exchange UM](#) 14

[101 Progress report](#) 16

[302 Redirect response](#) 15

[415 response](#) 16

[interacting with an Audio/Video Edge Server](#) 15

[other responses](#) 16

[QoE report](#) 15

[retry request](#) 16

[user notification](#) 19

SIP proxy operation

[call answered event](#) 18

[call forbidden event](#) 19

[missed call event](#) 18

[Standards assignments](#) 9

T

Timer events

[routing to Exchange UM](#) 16

[user notification](#) 20

Timers

[routing to Exchange UM](#) 14

[user notification](#) 17

[Tracking changes](#) 28

[Transport](#) 10

Triggered events

[routing to Exchange UM](#) 14

user notification

[call answered](#) 18

[SIP proxy operation](#) 18

[call forbidden](#) 19

[SIP proxy operation](#) 19

[missed call](#) 18

[SIP proxy operation](#) 18

U

Unified Messaging server timer

[expiry](#) 16

[overview](#) 14

User notification

[abstract data model](#) 17

higher-layer triggered events

[call answered](#) 18

[SIP proxy operation](#) 18

[call forbidden](#) 19

[SIP proxy operation](#) 19

[missed call](#) 18

[SIP proxy operation](#) 18

[initialization](#) 17

[local events](#) 20

[message processing](#) 19

[overview](#) 17

[schema](#) 24

[sequencing rules](#) 19

[timer events](#) 20

[timers](#) 17

[User Notification Extensions message](#) 10

[user event description](#) 11

[event type attribute type](#) 11

[user notification description](#) 10

User Notification Inactivity timer

[expiry](#) 20

[overview](#) 17

User Notification INVITE Request message

[From header field](#) 12

[Request-URI header field](#) 12

[SDP body](#) 12

[User Notification INVITE Response message](#) 13

V

[Vendor-extensible fields](#) 9

[Versioning](#) 9