# [MS-EUMSDP]:

# **Exchange Unified Messaging Session Description Protocol Extension**

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation ("this documentation") for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights**. This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- No Trade Secrets. Microsoft does not claim any trade secret rights in this documentation.
- Patents. Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft Open Specifications Promise or the Microsoft Community Promise. If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplq@microsoft.com.
- **License Programs**. To see all of the protocols in scope under a specific license program and the associated patents, visit the Patent Map.
- Trademarks. The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit <a href="https://www.microsoft.com/trademarks">www.microsoft.com/trademarks</a>.
- **Fictitious Names**. The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights**. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools**. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

**Support.** For questions and support, please contact <u>dochelp@microsoft.com</u>.

**Preliminary Documentation.** This particular Open Specifications document provides documentation for past and current releases and/or for the pre-release version of this technology. This document provides final documentation for past and current releases and preliminary documentation, as applicable and specifically noted in this document, for the pre-release version. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this

technology. Because this documentation might change between the pre-release version and the final version of this technology, there are risks in relying on this preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.



# **Revision Summary**

Date	Revision History	Revision Class	Comments
6/7/2010	0.1	Major	Initial Availability
6/29/2010	0.2	Editorial	Changed language and formatting in the technical content.
7/23/2010	0.2	None	No changes to the meaning, language, or formatting of the technical content.
9/27/2010	1.0	Major	Significantly changed the technical content.
11/15/2010	1.0	None	No changes to the meaning, language, or formatting of the technical content.
12/17/2010	1.0	None	No changes to the meaning, language, or formatting of the technical content.
3/18/2011	1.0	None	No changes to the meaning, language, or formatting of the technical content.
6/10/2011	1.0	None	No changes to the meaning, language, or formatting of the technical content.
1/20/2012	1.1	Minor	Clarified the meaning of the technical content.
4/11/2012	1.1	None	No changes to the meaning, language, or formatting of the technical content.
7/16/2012	1.1	None	No changes to the meaning, language, or formatting of the technical content.
10/8/2012	2.0	Major	Significantly changed the technical content.
2/11/2013	2.0	None	No changes to the meaning, language, or formatting of the technical content.
7/30/2013	2.1	Minor	Clarified the meaning of the technical content.
11/18/2013	2.1	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	2.1	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	2.1	None	No changes to the meaning, language, or formatting of the technical content.
7/31/2014	2.1	None	No changes to the meaning, language, or formatting of the technical content.
10/30/2014	2.1	None	No changes to the meaning, language, or formatting of the technical content.
3/30/2015	3.0	Major	Significantly changed the technical content.
9/4/2015	3.0	None	No changes to the meaning, language, or formatting of the technical content.
7/15/2016	3.0	None	No changes to the meaning, language, or formatting of the technical content.

Date	Revision History	Revision Class	Comments
9/14/2016	3.0	None	No changes to the meaning, language, or formatting of the technical content.
4/27/2018	4.0	Major	Significantly changed the technical content.



# **Table of Contents**

1	Intro	duction	6
	1.1	Glossary	6
	1.2	References	7
	1.2.1	Normative References	
	1.2.2	Informative References	7
	1.3	Overview	7
	1.4	Relationship to Other Protocols	8
	1.5	Prerequisites/Preconditions	8
	1.6	Applicability Statement	
	1.7	Versioning and Capability Negotiation	8
	1.8	Vendor-Extensible Fields	
	1.9	Standards Assignments	. 9
2	Macc	ages	10
	2.1	Transport	
	2.2	Message Syntax	
		5 ,	
3		ocol Details	
	3.1	Server Details	
	3.1.1	Abstract Data Model	11
	3.1.2	Timers	
	3.1.3	Initialization	
	3.1.4	Higher-Layer Triggered Events	
	3.1.5	Message Processing Events and Sequencing Rules	
	3.1.6	Timer Events	
	3.1.7	Other Local Events	
4	Proto	ocol Examples	13
_	_	rity	
5		rity	15
	5.1	Security Considerations for Implementers	15
	5.2	Index of Security Parameters	
6	Appe	ndix A: Product Behavior	16
_		ge Tracking	
7	Chan		17
8	Inde	x	18

#### 1 Introduction

The Exchange Unified Messaging Session Description Protocol Extension is a proprietary extension to the Session Description Protocol (SDP) that extends the characteristics that are used to negotiate and establish audio calls between protocol clients (or servers) and unified messaging servers, typically to enable a client to play or record voice messages and to manage the unified messaging mailbox by using touch-tone commands.

Sections 1.5, 1.8, 1.9, 2, and 3 of this specification are normative. All other sections and examples in this specification are informative.

#### 1.1 Glossary

This document uses the following terms:

- **dual-tone multi-frequency (DTMF)**: In telephony systems, a signaling system in which each digit is associated with two specific frequencies. This system typically is associated with touchtone keypads for telephones.
- **Interactive Connectivity Establishment (ICE)**: A methodology that was established by the Internet Engineering Task Force (IETF) to facilitate the traversal of network address translation (NAT) by media.
- **Media Source ID (MSI)**: A 32-bit identifier that uniquely identifies an audio or video source in a conference.
- **Multipurpose Internet Mail Extensions (MIME)**: A set of extensions that redefines and expands support for various types of content in email messages, as described in <a href="[RFC2045]">[RFC2045]</a>, and <a href="[RFC2047]</a>.
- **network address translation (NAT)**: The process of converting between IP addresses used within an intranet, or other private network, and Internet IP addresses.
- **public switched telephone network (PSTN)**: Public switched telephone network is the voiceoriented public switched telephone network. It is circuit-switched, as opposed to the packetswitched networks.
- Quality of Experience (QoE): A subjective measure of a user's experiences with a media service.
- **Real-Time Transport Control Protocol (RTCP)**: A network transport protocol that enables monitoring of Real-Time Transport Protocol (RTP) data delivery and provides minimal control and identification functionality, as described in [RFC3550].
- remote endpoint: See peer.
- **SDP answer**: A **Session Description Protocol (SDP)** message that is sent by an answerer in response to an offer that is received from an offerer.
- SDP offer: A Session Description Protocol (SDP) message that is sent by an offerer.
- **Session Description Protocol (SDP)**: A protocol that is used for session announcement, session invitation, and other forms of multimedia session initiation. For more information see <a href="MS-SDP">[MS-SDP]</a> and <a href="RFC3264">[RFC3264]</a>.
- **Synchronization Source (SSRC)**: A 32-bit identifier that uniquely identifies a media stream in a Real-Time Transport Protocol (RTP) session. An SSRC value is part of an RTP packet header, as described in [RFC3550].

**Unified Communications**: A system that integrates platforms for communications including email, voice mail, telephony, instant messaging, and voice and video conferencing.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

#### 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

#### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact <a href="mailto:dochelp@microsoft.com">dochelp@microsoft.com</a>. We will assist you in finding the relevant information.

[MS-SDPEXT] Microsoft Corporation, "Session Description Protocol (SDP) Version 2.0 Extensions".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, http://www.rfc-editor.org/rfc/rfc2119.txt

[RFC4566] Handley, M., Jacobson, V., and Perkins, C., "SDP: Session Description Protocol", RFC 4566, July 2006, <a href="http://www.ietf.org/rfc/rfc4566.txt">http://www.ietf.org/rfc/rfc4566.txt</a>

#### 1.2.2 Informative References

[MS-DTMF] Microsoft Corporation, "RTP Payload for DTMF Digits, Telephony Tones, and Telephony Signals Extensions".

[MS-ICE2] Microsoft Corporation, "Interactive Connectivity Establishment (ICE) Extensions 2.0".

[MS-ICE] Microsoft Corporation, "Interactive Connectivity Establishment (ICE) Extensions".

[MS-QoE] Microsoft Corporation, "Quality of Experience Monitoring Server Protocol".

[MS-RTP] Microsoft Corporation, "Real-time Transport Protocol (RTP) Extensions".

[MS-SIPRE] Microsoft Corporation, "Session Initiation Protocol (SIP) Routing Extensions".

[MS-SRTP] Microsoft Corporation, "Secure Real-time Transport Protocol (SRTP) Extensions".

[MS-TURN] Microsoft Corporation, "Traversal Using Relay NAT (TURN) Extensions".

#### 1.3 Overview

This protocol describes the **Session Description Protocol (SDP)** extensions that are used by a protocol client (or server) to establish and exchange audio with a unified messaging server. The types of calls between the protocol client and the unified messaging server are as follows:

- Call-in: An incoming public switched telephone network (PSTN) call to a Unified Communications user leaves a voice message with the unified messaging server.
- **Play-On-Phone:** Upon receiving a notification from a protocol client, the unified messaging server deflects the call to the PSTN phone number to play a voice message.

The information in this document applies to all types of calls between a protocol client and the unified messaging server.

This protocol supplements [MS-SDPEXT], which describes a proprietary SDP extension that is used to establish audio sessions between unified communication clients and servers, with the following exceptions:

- Only the audio media type is supported.
- The session version on the o line can be incremented in subsequent offer/answer negotiations.
- If an **SDP answer** is given in an 18x-level provisional response, the SDP answer in the final response (for the same fork) is required not to contain any differences.
- Optimizing the media pathway using the a=x-bypassid and a=x-bypass attributes is not supported.
- Extensions for RTCP-based feedback messages, Synchronization Source (SSRC) range allocation, Media Source ID (MSI) assignment and media source labeling are not supported.

#### 1.4 Relationship to Other Protocols

This protocol depends on the following protocols:

- [MS-SDPEXT] for media negotiation.
- [MS-ICE] for media to traverse network address translation (NAT) and firewalls.
- [MS-ICE2] and [MS-TURN] for media to traverse NAT and firewalls.
- [MS-RTP] for media transmission.
- [MS-DTMF] for dual-tone multi-frequency (DTMF) digits or tones to be exchanged.
- [MS-SIPRE] section 3.2.4 for Interactive Connectivity Establishment (ICE) Session Description Protocol (SDP) interworking and Multipart Multipurpose Internet Mail Extensions (MIME) support.
- [MS-SRTP] for media encryption.
- [MS-QoE] for publishing audio Quality of Experience (QoE) metrics.

## 1.5 Prerequisites/Preconditions

The prerequisites for this protocol are the same as the prerequisites described in [MS-SDPEXT] section 1.5.

## 1.6 Applicability Statement

None.

## 1.7 Versioning and Capability Negotiation

None.

## 1.8 Vendor-Extensible Fields

None.

# 1.9 Standards Assignments

None.



## 2 Messages

## 2.1 Transport

This protocol does not introduce a new transport to support audio calls, and uses the transport specified in [MS-SDPEXT] section 2.1.

## 2.2 Message Syntax

The messages specified in [MS-SDPEXT] are **Session Description Protocol** (**SDP**) messages. An SDP message contains the description of a media session. The session and media characteristics are described by a set of **<type>=<value>** lines, as specified in [RFC4566]. The extensions are defined as custom SDP attributes.

#### 3 Protocol Details

#### 3.1 Server Details

## 3.1.1 Abstract Data Model

The abstract data model for this protocol is the same as that specified in [MS-SDPEXT] section 3.1.1.

#### **3.1.2 Timers**

The timers for this protocol are the same as those specified in [MS-SDPEXT] section 3.1.2.

#### 3.1.3 Initialization

The initialization for this protocol is the same as that specified in [MS-SDPEXT] section 3.1.3.

#### 3.1.4 Higher-Layer Triggered Events

The higher-layer triggered events for this protocol are the same as those specified in <a>[MS-SDPEXT]</a> section 3.1.4.

## 3.1.5 Message Processing Events and Sequencing Rules

This protocol follows the message processing rules specified in [MS-SDPEXT] section 3.1.5, with the following exceptions:

- [MS-SDPEXT] section 3.1.5.18: Only the m=audio line is supported in the Session Description Protocol (SDP). All other m line types, such as m=video and m=applicationsharing, are rejected.
- [MS-SDPEXT] section 3.1.5.19: Regarding the **o** line of an SDP message:
  - the parameter <sess-version> MUST be a numeric value, but the value SHOULD be ignored on receive.
  - the protocol server SHOULD increment the session version value (<sess-version>) in the o line in any subsequent SDP offers.
- [MS-SDPEXT] section 3.1.5.12.3: If an SDP answer is received in a provisional 18x-level response, any SDP answer given in a final response (for the same fork) is assumed to be identical. Any differences with the SDP answer in the final response will be ignored.
- [MS-SDPEXT] section 3.1.5.25: The a=x-bypassid, a=x-bypass and a=x-mediasettings attributes are ignored.
- [MS-SDPEXT] section 3.1.5.30: The a=rtcp-rsize and a=rtcp-fb attributes are ignored.
- [MS-SDPEXT] section 3.1.5.31: The **a=x-ssrc-range** attribute is ignored.
- [MS-SDPEXT] section 3.1.5.32: The **a=x-source-streamid** attribute is ignored.
- [MS-SDPEXT] section 3.1.5.33: The **a=x-source** attribute is ignored.

## 3.1.6 Timer Events

The timer events for this protocol are the same as those specified in [MS-SDPEXT] section 3.1.6.

## 3.1.7 Other Local Events

The local events for this protocol are the same as those specified in [MS-SDPEXT] section 3.1.7.



## 4 Protocol Examples

The following example is an **SDP offer** sent by a **remote endpoint** to a unified messaging server.

```
0=\nabla
o=- 0 0 IN IP4 10.56.65.184
s=session
c=IN IP4 10.56.65.184
b=CT:53980
t = 0 0
m=audio 50024 RTP/AVP 114 9 112 111 0 8 116 115 97 13 118 101
a=ice-ufrag:vxUD
a=ice-pwd:4QoBoSfCA7vYy9AwNBhsISk9
a=candidate:1 1 UDP 2130706431 10.56.65.184 50024 typ host
a=candidate:1 2 UDP 2130705918 10.56.65.184 50025 typ host
a=candidate: 2 1 TCP-PASS 6556159 10.9.66.105 51450 typ relay raddr 10.56.65.184
rport 50026
a=candidate: 2 TCP-PASS 6556158 10.9.66.105 51450 typ relay raddr 10.56.65.184
rport 50026
a=candidate:3 1 UDP 16648703 10.9.66.105 59291 typ relay raddr 10.56.65.184 rport
a=candidate:3 2 UDP 16648702 10.9.66.105 3937 typ relay raddr 10.56.65.184 rport
a=candidate:4 1 TCP-ACT 7076351 10.9.66.105 51450 typ relay raddr 10.56.65.184 rport
a=candidate:4 2 TCP-ACT 7075838 10.9.66.105 51450 typ relay raddr 10.56.65.184 rport
a=candidate:5 1 TCP-ACT 1684797439 10.56.65.184 50026 typ srflx raddr 10.56.65.184
rport 50026
a=candidate:5 2 TCP-ACT 1684796926 10.56.65.184 50026 typ srflx raddr 10.56.65.184
rport 50026
a=cryptoscale:1 client AES CM 128 HMAC SHA1 80
inline:Vg7c4/T5hsxb/UDMzHqSPk2DwKXzsJk1/IPIx2tI|2^31|1:1
a=crypto:2 AES_CM_128_HMAC_SHA1_80
inline:rX1Y0WgGnXDdutAA8eEH7ZYog+ydd//x+Cidwcvw|2^31|1:1
a=crypto:3 AES CM 128 HMAC SHA1 80
inline:ZRbU8mr2f5nK9adY1tjCzbb3AbDU8pfkRIpcrecA|2^31
a=maxptime:200
a=rtpmap:114 x-msrta/16000
a=fmtp:114 bitrate=29000
a=rtpmap:9 G722/8000
a=rtpmap:112 G7221/16000
a=fmtp:112 bitrate=24000
a=rtpmap:111 SIREN/16000
a=fmtp:111 bitrate=16000
a=rtpmap:0 PCMU/8000
a=rtpmap:8 PCMA/8000
a=rtpmap:116 AAL2-G726-32/8000
a=rtpmap:115 x-msrta/8000
a=fmtp:115 bitrate=11800
a=rtpmap:97 RED/8000
a=rtpmap:13 CN/8000
a=rtpmap:118 CN/16000
a=rtpmap:101 telephone-event/8000
a=fmtp:101 0-16
a=x-bypassid:9CD08A01-E998-456a-AC8A-D028930E5933
```

The following example is the **SDP answer** sent by the unified messaging server.

```
v=0
o=- 2303 0 IN IP4 157.56.65.134
s=session
c=IN IP4 157.56.65.134
b=CT:1000
m=audio 1469 RTP/SAVP 114 115 112 111 116 0 8 13 118 97 101
c=IN IP4 157.56.65.134
a=rtcp:32805
a=ice-ufrag:Aieb
a=ice-pwd:qw3WPnif3nyEAFbPHhtWpWs3
a=candidate:1 1 UDP 2130706431 157.56.65.134 1469 typ host
a=candidate:1 2 UDP 2130705918 157.56.65.13432805 typ host
a=candidate:2 1 tcp-pass 6555135 172.29.105.158 56439 typ relay raddr 205.248.125.34 rport
56439
a=candidate:2 2 tcp-pass 6555134 172.29.105.158 56439 typ relay raddr 205.248.125.34 rport
56439
a=candidate:3 1 UDP 16647679 172.29.105.158 56659 typ relay raddr 172.29.105.158 rport 56659
a=candidate:3 2 UDP 16647678 172.29.105.158 51883 typ relay raddr 172.29.105.158 rport 51883
a=candidate:4 1 tcp-act 7076863 172.29.105.158.34 56439 typ relay raddr 172.29.105.158 rport
a=candidate: 4 2 tcp-act 7076350 172.29.105.158 56439 typ relay raddr 172.29.105.158 rport
56439
a=candidate:5 1 tcp-act 1684797951 192.168.104.102 38263 typ srflx raddr 157.56.65.134 rport
a=candidate:5 2 tcp-act 1684797438 192.168.104.102 38263 typ srflx raddr 157.56.65.134 rport
a=crypto:2 AES CM 128 HMAC SHA1 80 inline:apG+pahPrJUcGUw3FMogAth9HWpCVzv6BxakuzNL|2^31|1:1
a=label:main-audio
a=rtpmap:114 x-msrta/16000
a=fmtp:114 bitrate=29000
a=rtpmap:115 x-msrta/8000
a=fmtp:115 bitrate=11800
a=rtpmap:112 G7221/16000
a=fmtp:112 bitrate=24000
a=rtpmap:111 SIREN/16000
a=fmtp:111 bitrate=16000
a=rtpmap:116 AAL2-G726-32/8000
a=rtpmap:0 PCMU/8000
a=rtpmap:8 PCMA/8000
a=rtpmap:13 CN/8000
a=rtpmap:118 CN/16000
a=rtpmap:97 RED/8000
a=rtpmap:101 telephone-event/8000
a=fmtp:101 0-16,36
```



# **5** Security

## **5.1 Security Considerations for Implementers**

This protocol has the security considerations described in [MS-SDPEXT] section 5.1.

## **5.2 Index of Security Parameters**

This protocol has the index of security parameters described in [MS-SDPEXT] section 5.2.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Microsoft Office Communications Server 2007 R2
- Microsoft Office Communicator 2007 R2
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Lync 2010
- Microsoft Lync Server 2010
- Microsoft Lync Client 2013/Skype for Business
- Microsoft Lync Server 2013
- Microsoft Skype for Business 2016
- Microsoft Skype for Business Server 2015
- Microsoft Skype for Business 2019 Preview

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

# 7 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact <a href="mailto:dochelp@microsoft.com">dochelp@microsoft.com</a>.

Section	Description	Revision class
6 Appendix A: Product Behavior	Updated list of supported products.	major

A	
Abotion students are dell 11	Other local events server 12
Abstract data model 11 server 11	Overview (synopsis) 7
Applicability 8	P
С	
Capability negotiation 8	<u>Parameters - security index</u> 15 <u>Preconditions</u> 8
Change tracking 17	Prerequisites 8
D	Product behavior 16
	R
Data model - abstract 11 server 11	References 7
SCIVET 11	informative 7
E	normative 7 Relationship to other protocols 8
Example	
SDP offer 13	S
F	SDP offer example 13
Fields - vendor-extensible 8	Security <u>implementer considerations</u> 15
Telds Vehidor exterisible	parameter index 15
G	Sequencing rules 11 server 11
Glossary 6	Server
н	<u>abstract data model</u> 11 <u>higher-layer triggered events</u> 11
	initialization 11 message processing 11
Higher-layer triggered events 11 server 11	other local events 12
SEIVEI II	sequencing rules 11 timer events 12
I	timers 11
Implementer - security considerations 15	Standards assignments 9
Index of security parameters 15 Informative references 7	Т
Initialization 11	<u>Timer events</u> 12
server 11 Introduction 6	server 12
	Timers 11 server 11
	Tracking changes 17
Local events 12	Triggered events 11
м	Triggered events - higher-layer server 11
	<u>server</u> 11
Message processing 11 server 11	V
Messages	Vendor-extensible fields 8
syntax 10 transport 10	Versioning 8
 N	
11	
Normative references 7	

Index

8

0