[MS-MCI]: MCI Compression and Decompression

Intellectual Property Rights Notice for Open Specifications Documentation

- Technical Documentation. Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- Copyrights. This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- No Trade Secrets. Microsoft does not claim any trade secret rights in this documentation.
- Patents. Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: http://www.microsoft.com/interop/osp) or the Community Promise (available here: http://www.microsoft.com/interop/cp/default.mspx). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks**. The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Reservation of Rights**. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.
- Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Author	Date	Versio n	Comments
Microsoft Corporation	April 4, 2008	0.1	Initial Availability.
Microsoft Corporation	June 27, 2008	1.0	Initial Release.
Microsoft Corporation	August 6, 2008	1.01	Revised and edited technical content.
Microsoft Corporation	September 3, 2008	1.02	Revised and edited technical content.
Microsoft Corporation	December 3, 2008	1.03	Revised and edited technical content.
Microsoft Corporation	March 4, 2009	1.04	Revised and edited technical content.
Microsoft Corporation	April 10, 2009	2.0	Updated technical content and applicable product releases.

Table of Contents

1	In	ntroduction	4
	1.1	Glossary	4
	1.2	References	
	1.	2.1 Normative References	4
	1.	2.2 Informative References	4
	1.3	Structure Overview	5
		Relationship to Protocols and Other Structures	
	1.5	Applicability Statement	
	1.6	Versioning and Localization	
		Vendor-Extensible Fields	
2	Si	tructures	5
3	Si	tructure Examples	6
4	S	ecurity Considerations	6
5	A	ppendix A: Office/Exchange Behavior	6
Ιı	ndex		8

1 Introduction

This document specifies the format of MSZIP compressed data as used in the MSZIP compression mode of **cabinet files**. The purpose of this specification is to enable anyone to encode or decode MSZIP compressed data.

1.1 Glossary

The following terms are defined in [MS-OXGLOS]:

ASCII cabinet file cabinet folder little-endian Unicode

The following terms are specific to this document:

RFC 1951 block: A compressed block format as defined in [RFC1951] section 3.2.

MSZIP block: One or more RFC 1951 blocks with an MSZIP signature.

MSZIP signature: The first two bytes of the **MSZIP block** that demarcate a unique **MSZIP block**.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

[MS-CAB] Microsoft Corporation, "Cabinet File Format", June 2008.

[RFC1951] Deutsch, P., "DEFLATE Compressed Data Format Specification version 1.3", RFC 1951, May 1996, http://www.ietf.org/rfc/rfc1951.txt.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, http://www.ietf.org/rfc/rfc2119.txt.

1.2.2 Informative References

None.

1.3 Structure Overview

MSZIP compression is a derivative of Phil Katz's DEFLATE Compressed Data Format. For more information about the DEFLATE Compressed Data Format, see [RFC1951]. MSZIP uses only the three basic modes of deflate: no compression, compressed with fixed Huffman codes, and compressed with dynamic Huffman codes.

1.4 Relationship to Protocols and Other Structures

None.

1.5 Applicability Statement

None.

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

None.

2 Structures

Each MSZIP block MUST consist of a 2-byte MSZIP signature and one or more RFC 1951 blocks. The 2-byte MSZIP signature MUST consist of the bytes 0x43 and 0x4B. The MSZIP signature MUST be the first 2 bytes in the MSZIP block. The MSZIP signature is shown in the following diagram.

0	1	2	3	4	5	6	7	0	1	2	3	4	5	6	7
MSZIP Signature Byte 0				e 0	M	ISZ	IP S	Sign	atu	re I	Byte	1			

MSZIP Signature Byte 0: The first byte of the MSZIP signature MUST be set to 0x43.

MSZIP Signature Byte 1: The second byte of the MSZIP signature MUST be set to 0x4B.

Each MSZIP block is the result of a single deflate compression operation, as defined in [RFC1951]. The compressor that performs the compression operation MUST generate one or more RFC 1951 blocks, as defined in [RFC1951]. The number, deflation mode, and type of RFC 1951 blocks in each MSZIP block is determined by the compressor, as defined in [RFC1951]. Each RFC 1951 block MUST be flushed out of the compressor before the next block begins. The last RFC 1951 block in each MSZIP block MUST be marked as the "end" of the stream, as defined by [RFC1951] section 3.2.3. Decoding trees MUST be discarded after each RFC 1951 block. Each MSZIP block that is not the last MSZIP block in a **cabinet**

folder MUST represent 32 KB of uncompressed data. The last block in a cabinet folder can be smaller than 32 KB of uncompressed data.

The maximum compressed size of each MSZIP block is 32 KB + 12 bytes. This allows for the data to be passed as two separate RFC 1951 blocks. Each RFC 1951 block can have a 5-byte overhead. The two separate RFC 1951 blocks with 5 bytes of overhead each, combined with the 2-byte MSZIP signature, constitute the 12 bytes in addition to the 32 KB of data contained in an MSZIP block. MSZIP MUST use a compression window of size 32 KB.

3 Structure Examples

The following MSZIP block structure contains a single compressed RFC 1951 block.

<= (32 KB+12 bytes)					
0x43 0x4B	Generated by single "deflate" compression operation				
2-Byte MSZIP Signature	RFC 1951 Block				

The MSZIP block structure shown below contains two RFC 1951 blocks.

<= (32 KB+ 12 bytes)						
0x43 0x4B	Generated by single "deflate" compression operation					
2-Byte MSZIP Signature	RFC 1951 Block	RFC 1951 Block				

4 Security Considerations

None.

5 Appendix A: Office/Exchange Behavior

The information in this specification is applicable to the following versions of Office/Exchange:

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007

• Microsoft Exchange Server 2010

Exceptions, if any, are noted below. Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies Office/Exchange behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies Office/Exchange does not follow the prescription.

Index

Applicability statement, 5
Glossary, 4
Informative references, 4
Introduction, 4
Normative references, 4
Office/Exchange behavior, 6
Overview, 5
References, 4
Informative references, 4
Normative references, 4
Relationship to protocols and other structures, 5

Security considerations, 6

Structure examples, 6

Structures, 5

Vendor-extensible fields, 5

Versioning and localization, 5