[MS-OCEXUM]: Call Control for Exchange Unified Messaging Protocol Extensions

Intellectual Property Rights Notice for Open Specifications Documentation

- Technical Documentation. Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- Patents. Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft <u>Open Specification Promise</u> or the <u>Community Promise</u>. If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting <u>iplq@microsoft.com</u>.
- Trademarks. The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- Fictitious Names. The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

Revision Summary

Date	Revision History	Revision Class	Comments	
04/04/2008	0.1		Initial version	
04/25/2008	0.2		Revised and edited technical content	
06/27/2008	1.0		Revised and edited technical content	
08/15/2008	1.01		Revised and edited technical content	
12/12/2008	2.0		Revised and edited technical content	
02/13/2009	2.01		Revised and edited technical content	
03/13/2009	2.02		Revised and edited technical content	
07/13/2009	2.03	Major	Revised and edited the technical content	
08/28/2009	2.04	Editorial	Revised and edited the technical content	
11/06/2009	2.05	Editorial	Revised and edited the technical content	
02/19/2010	2.06	Editorial	Revised and edited the technical content	
03/31/2010	2.07	Major	Updated and revised the technical content	
04/30/2010	2.08	Editorial	Revised and edited the technical content	
06/07/2010	2.09	Editorial	Revised and edited the technical content	
06/29/2010	2.10	Editorial	Changed language and formatting in the technical content.	
07/23/2010	2.10	No change	No changes to the meaning, language, or formatting of the technical content.	
09/27/2010	3.0	Major	Significantly changed the technical content.	
11/15/2010	3.0	No change	No changes to the meaning, language, or formatting of the technical content.	
12/17/2010	3.0	No change	No changes to the meaning, language, or formatting of the technical content.	
03/18/2011	3.0	No change	No changes to the meaning, language, or formatting of the technical content.	
06/10/2011	3.0	No change	No changes to the meaning, language, or formatting of the technical content.	
01/20/2012	4.0	Major	Significantly changed the technical content.	
04/11/2012	4.0	No change	No changes to the meaning, language, or formatting of the technical content.	

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

Date	Revision History	Revision Class	Comments	
07/16/2012	4.0	No change	No changes to the meaning, language, or formatting of the technical content.	
10/08/2012	4.0.1	Editorial	Changed language and formatting in the technical content.	
02/11/2013	4.0.1	No change	No changes to the meaning, language, or formatting of the technical content.	
07/30/2013	4.0.1	No change	No changes to the meaning, language, or formatting of the technical content.	
11/18/2013	4.0.1	No change	No changes to the meaning, language, or formatting of the technical content.	
02/10/2014	4.0.1	No change	No changes to the meaning, language, or formatting of the technical content.	
04/30/2014	4.1	Minor	Clarified the meaning of the technical content.	
07/31/2014	4.2	Minor	Clarified the meaning of the technical content.	
10/30/2014	4.3	Minor	Clarified the meaning of the technical content.	

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

Table of Contents

1	Introduction	5
1	L.1 Glossary	5
1	1.2 References	5
	1.2.1 Normative References	5
	1.2.2 Informative References	6
1	L.3 Overview	6
1	1.4 Relationship to Other Protocols	6
1	1.5 Prerequisites/Preconditions	
1	L.6 Applicability Statement	
1	1.7 Versioning and Capability Negotiation	
1	1.8 Vendor-Extensible Fields	
1	1.9 Standards Assignments	
2	Messages	8
2	2.1 Transport	8
2	2.2 Message Syntax	8
	2.2.1 Ms-Exchange-Command	8
	2.2.2 Ms-Sensitivity	8
3	Protocol Details1	-
3	3.1 Ms-Exchange-Command Details 1	
	3.1.1 Abstract Data Model 1	
	3.1.2 Timers	
	3.1.3 Initialization	
	3.1.4 Higher-Layer Triggered Events 1	0
	3.1.5 Message Processing Events and Sequencing Rules 1	0
	3.1.6 Timer Events 1	
	3.1.7 Other Local Events 1	0
3	3.2 Ms-Sensitivity Details 1	1
	3.2.1 Abstract Data Model	1
	3.2.2 Timers	1
	3.2.3 Initialization	1
	3.2.4 Higher-Layer Triggered Events1	1
	3.2.5 Message Processing Events and Sequencing Rules	1
	3.2.6 Timer Events	1
	3.2.7 Other Local Events	2
4	Protocol Examples1	
2	1.1 Ms-Exchange-Command 1	3
2	1.2 Ms-Sensitivity	3
-	Security1	-
	5.1 Security Considerations for Implementers1	
5	5.2 Index of Security Parameters 1	5
_		_
6	Appendix A: Product Behavior1	6
7	Change Tracking1	7
7		/
8	Index1	9
5		-

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

1 Introduction

The Call Control for Exchange Unified Messaging Protocol Extensions, which consist of proprietary extensions to the Session Initiation Protocol (SIP), is used to play voice messages and to manage the unified messaging mailbox using voice commands. **SIP** is used to establish, modify, and terminate multimedia sessions or calls. These protocol extensions are used to integrate with other telephony networks or systems, such as a private branch exchange (PBX).

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [RFC2119]. Sections 1.5 and 1.9 are also normative but do not contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [MS-OFCGLOS]:

```
Augmented Backus-Naur Form (ABNF)
authentication
endpoint
INVITE
server
Session Initiation Protocol (SIP)
SIP message
Transmission Control Protocol (TCP)
Transport Layer Security (TLS)
Uniform Resource Identifier (URI)
user agent client (UAC)
```

The following terms are specific to this document:

- **Exchange Web Service (EWS):** A service that is provided by Microsoft Exchange Server and that enables clients to access mailbox content.
- **personal identification number (PIN):** A number that is used by Exchange Unified Messaging to authenticate a user.
- **subscriber access:** The ability of a user to gain access to features of a Unified Messaging server, such as using a phone to listen to telephony voice messages or email messages.
- **MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact <u>dochelp@microsoft.com</u>. We will assist you in finding the relevant information.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

[MS-EUMR] Microsoft Corporation, "Routing to Exchange Unified Messaging Extensions".

[MS-OXWUMS] Microsoft Corporation, "Voice Mail Settings Web Service Protocol".

[MS-SIPRE] Microsoft Corporation, "Session Initiation Protocol (SIP) Routing Extensions".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <u>http://www.rfc-editor.org/rfc/rfc2119.txt</u>

[RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and Schooler, E., "SIP: Session Initiation Protocol", RFC 3261, June 2002, http://www.ietf.org/rfc/rfc3261.txt

1.2.2 Informative References

[MS-OFCGLOS] Microsoft Corporation, "Microsoft Office Master Glossary".

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <u>http://www.rfc-editor.org/rfc/rfc5234.txt</u>

1.3 Overview

The unified messaging **server** (2) provides a Session Initiation Protocol (SIP) interface toward a server (2) or gateways. By default, the unified messaging server (2) requires a **personal identification number (PIN)** to be entered to access the voice mail in a user's inbox. This protocol allows previously authenticated protocol clients to bypass the PIN requirement, thus streamlining the connection with the unified messaging server (2).

This protocol is used to support calls between a protocol client and the unified messaging server (2) supported by this protocol.

There are two types of calls between a protocol client and the unified messaging server (2):

- **Call-in:** Using the protocol client user interface (UI), a user calls into the unified messaging server (2) to access the voice mail system. This is also known as **subscriber access**.
- Dial Out (Play-On-Phone): Upon receiving an appropriate event, the unified messaging server
 (2) sends a SIP INVITE to the client for the purpose of playing back the recorded voice message on a protocol server (2) endpoint (5) identified by a phone number.

This protocol can be used in Play-On-Phone scenarios to prevent a protocol server from rerouting the message back to voice mail back and call forwarding when the Play-On-Phone call is not answered by the user.

Please refer to [MS-EUMR] for details on how the Lync Server routes the call from client to the unified messaging server.

1.4 Relationship to Other Protocols

This protocol depends on Session Initiation Protocol (SIP).

This protocol depends on all the protocols on which SIP depends.

1.5 Prerequisites/Preconditions

None.

Copyright © 2014 Microsoft Corporation.

1.6 Applicability Statement

This protocol is designed to be used to support calls between a protocol client and the unified messaging server (2) supported by this protocol.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

2 Messages

2.1 Transport

Messages MUST be transported over **Transmission Control Protocol (TCP)** or **Transport Layer Security (TLS)**.

2.2 Message Syntax

Messages are formatted as **SIP messages**, as specified in [RFC3261] section 7, with the custom headers and parameters described in this document.

2.2.1 Ms-Exchange-Command

The **Ms-Exchange-Command** custom Session Initiation Protocol (SIP) header is added to the INVITE method in calls originating from a protocol client. This header is used to indicate an action to be performed by the unified messaging server (2).

The syntax of this header, in the **Augmented Backus-Naur Form (ABNF)** notation, as defined in [RFC5234], is as follows:

```
Ms-Exchange-Command header = "Ms-Exchange-Command" HCOLON param
param = "skip-pin"
```

The only supported action is specified by the valueless parameter, **skip-pin**, which indicates to the unified messaging server (2) not to prompt the user for a personal identification number (PIN). Before this parameter can be set, the protocol client MUST be authenticated by the SIP server (2), and the additional level of **authentication** (2) in the form of a PIN is not needed for the INVITE transaction.

The syntax of the **Ms-Exchange-Command** header with the **skip-pin** parameter is illustrated as follows:

```
INVITE ... SIP/2.0
From: ...
To: ...
Ms-Exchange-Command: skip-pin
```

2.2.2 Ms-Sensitivity

The **Ms-Sensitivity** custom Session Initiation Protocol (SIP) header, as specified in [MS-SIPRE], is used to instruct a protocol server (2) not to reroute the call back to the unified messaging server (2) and to prevent call forwarding. When the value of this header is set to "private-no-diversion", a protocol server (2) does not reroute the message back to voice mail when a Play-On-Phone call is not answered by the user.

The syntax of this header, in the Augmented Backus-Naur Form (ABNF) notation, as defined in [RFC5234], is as follows:

```
Ms-Sensitivity header = "Ms-Sensitivity" HCOLON privacy privacy="private-no-diversion"
```

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

The syntax of the **Ms-Sensitivity** header is illustrated as follows:

INVITE ... SIP/2.0 From: ... To: ... Ms-Sensitivity: private-no-diversion

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

3 Protocol Details

3.1 Ms-Exchange-Command Details

The **Ms-Exchange-Command** header with the **skip-pin** parameter is used when the protocol client uses subscriber access to the voice mail system, and to provide a better user experience, requires the unified messaging server (2) to skip the personal identification number (PIN) prompt. When the unified messaging server (2) receives this command, it MUST skip the PIN prompt, provided that the INVITE is received over a trusted transport, such as a Transport Layer Security (TLS) transport, to the unified messaging server (2). The assumption here is that the voice mail system trusts the authentication (2) mechanism for requests that are received by it over the trusted transport.

Protocol Client Behavior

A **user agent client (UAC)** accessing the subscriber access feature of the voice mail system over a trusted transport SHOULD provide a **Ms-Exchange-Command** header with the **skip-pin** parameter to provide a better user experience.

Unified Messaging Server Behavior

If a unified messaging server receives a SIP INVITE over a trusted transport with a **Ms-Exchange-Command** header containing the **skip-pin** parameter, it MUST skip personal identification number (PIN) prompt.

3.1.1 Abstract Data Model

None.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

None.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

3.2 Ms-Sensitivity Details

The **Ms-Sensitivity** header, as specified in [MS-SIPRE], SHOULD be used in Dial Out (Play-On-Phone), scenarios when the user requests a voice mail message to be played on the phone from an application. In such a scenario, the unified messaging server (2) sends an INVITE to the user and uses this header to indicate to the protocol server (2) that the call MUST NOT be rerouted back to voice mail and call forwarding when the Play-On-Phone call is not answered by the user. In this case, unanswered call forwarding or immediate call forwarding MUST NOT be applied. The unified messaging server (2) sends such an INVITE through the **Exchange Web Service (EWS)**, as specified in [MS-OXWUMS]. The trigger point for this is an event sent by EWS. ≤ 1 >

The unified messaging server (2) supported by this protocol uses the **Ms-Sensitivity** header with the **private-no-diversion** parameter, as specified in section <u>2.2.2</u>.

Use of other parameters, as specified in [MS-SIPRE], is out of the scope of this extension.

Note that in Play-On-Phone INVITEs that originate from the unified messaging server (2), the **URIs** in the **From** header and the **To** header MUST point to same address. This is because the protocol clients have special logic that checks for this condition and allows the protocol client to ring for Play-On-Phone calls, even if the user has manually set himself or herself to the "Appear Offline" presence state.

Unified Messaging Server Behavior

A unified messaging server SHOULD send a **Ms-Sensitivity** header with the **private-no-diversion** parameter in Dial Out or Play-On-Phone scenarios.

Protocol Server Behavior

If a SIP INVITE contains a **Ms-Sensitivity** header with the **private-no-diversion** parameter, unanswered call forwarding or immediate call forwarding MUST NOT be applied.

3.2.1 Abstract Data Model

None.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

None.

3.2.5 Message Processing Events and Sequencing Rules

None.

3.2.6 Timer Events

None.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

11 / 20

3.2.7 Other Local Events

None.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

4 Protocol Examples

4.1 Ms-Exchange-Command

The **Ms-Exchange-Command** header can be used to skip pin verification for previously authenticated protocol clients.

The following figure shows the flow of the Session Initiation Protocol (SIP) INVITE transaction for subscriber access to voice mail.




Figure 1: Subscriber access flow

The INVITE message carries the **Ms-Exchange-Command** header with the **skip-pin** parameter, as shown in the following example.

```
INVITE sip:alice@contoso.com;opaque=app:voicemail SIP/2.0
Via: SIP/2.0/TLS 10.56.65.37:33876
Max-Forwards: 70
From: <sip:alice@contoso.com>;tag=01742a55e6;epid=6b5d10e663
To: <sip:alice@contoso.com;opaque=app:voicemail>
Call-ID: f7c2efff9240413cb6e5125fdca4b63a
CSeq: 1 INVITE
Contact: <sip:alice@contoso.com;opaque=user:epid:ihclvAI6-FmKSGLKr_2rtAAA;gruu>
Ms-Exchange-Command: skip-pin
... SDP SNIPPED ...
```

4.2 Ms-Sensitivity

The following figure shows the flow for the **Ms-Sensitivity** header that is added by the unified messaging server (2) when dialing out to the protocol client.




Figure 2: Play-On-Phone dial out

The INVITE message in step 2 of the preceding figure is shown in the following example.

```
INVITE sip:172.19.58.98:2280;transport=tls;ms-opaque=ce5f21cc9d;ms-received-cid=D0A300
SIP/2.0
Max-Forwards: 68
Content-Length: 317
From: <sip:alice@contoso.com>;epid=1944B98832;tag=7534fa434
To: <sip:alice@contoso.com>;epid=d793aff63a
CSeq: 5 INVITE
Call-ID: 7a7378c9-7b3c-4cec-b6da-ec27d752e904
Contact: <sip: exchange.contoso.com:5066;transport=Tls;ms-opaque=a752506cbee22182>;automata
User-Agent: RTCC/3.0.0.0
Content-Type: application/sdp
Allow: UPDATE
Ms-Sensitivity: private-no-diversion
Allow: Ack, Cancel, Bye, Invite, Message, Info, Service, Options, BeNotify
...SDP SNIPPED...
```

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

5 Security

5.1 Security Considerations for Implementers

None.

5.2 Index of Security Parameters

None.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Office Outlook 2007
- Microsoft Office Outlook 2007 Service Pack 1
- Microsoft Outlook 2010
- Microsoft Exchange Server 2007 Service Pack 1 (SP1)
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Lync 2010
- Microsoft Lync 2013
- Microsoft Lync Server 2010
- Microsoft Lync Server 2013
- Microsoft Office Communications Server 2007
- Microsoft Office Communications Server 2007 R2
- Microsoft Office Communicator 2007
- Microsoft Office Communicator 2007 R2

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

<<u>1> Section 3.2</u>: Office Outlook 2007, Office Outlook 2007 SP1, and Outlook 2010 support Play-On-Phone as an option. Any of these clients can be used to raise the event.

7 Change Tracking

This section identifies changes that were made to the [MS-OCEXUM] protocol document between the July 2014 and October 2014 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.

• Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated.**

Some important terms used in the change type descriptions are defined as follows:

- Protocol syntax refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- Protocol revision refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact <u>dochelp@microsoft.com</u>.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<u>1.3</u> <u>Overview</u>	Updated the Dial Out (Play-On-Phone) description to include "SIP INVITE".	N	Content updated.
<u>3.2</u> <u>Ms-Sensitivity</u> <u>Details</u>	Updated the description about Play-On-Phone INVITEs.	N	Content updated.
<u>6</u> <u>Appendix A:</u> <u>Product Behavior</u>	Added "Microsoft Office Outlook 2007", "Microsoft Office Outlook 2007 Service Pack 1" and "Microsoft Outlook 2010" to product list.	N	New content added.

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

8 Index

Α

Abstract data model <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11 <u>Applicability</u> 7

С

Capability negotiation 7 Change tracking 17

D

Data model - abstract <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11

Е

Examples <u>Ms-Exchange-Command</u> 13 <u>Ms-Sensitivity</u> 13

F

Fields - vendor-extensible 7

G

Glossary 5

Н

Higher-layer triggered events <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11

Ι

Implementer - security considerations 15 Index of security parameters 15 Informative references 6 Initialization <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11 Introduction 5

L

Local events <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 12

Μ

Message processing <u>Ms-Exchange-Command</u> 10

Ms-Sensitivity 11 Message syntax 8 Messages message syntax 8 Ms-Exchange-Command 8 Ms-Sensitivity 8 transport 8 Ms-Exchange-Command abstract data model 10 example 13 higher-layer triggered events 10 initialization 10 local events 10 message processing 10 overview 10 sequencing rules 10 timer events 10 timers 10 Ms-Exchange-Command message 8 Ms-Sensitivity abstract data model 11 example 13 higher-layer triggered events 11 initialization 11 local events 12 message processing 11 overview 11 sequencing rules 11 timer events 11 timers 11 Ms-Sensitivity message 8

Ν

Normative references 5

0

Overview (synopsis) 6

Ρ

Parameters - security index 15 Preconditions 6 Prerequisites 6 Product behavior 16

R

References 5 informative 6 normative 5 Relationship to other protocols 6

S

Security implementer considerations 15

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.

parameter index 15 Sequencing rules <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11 <u>Standards assignments</u> 7

т

Timer events <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11 Timers <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11 <u>Tracking changes</u> 17 <u>Transport</u> 8 Triggered events <u>Ms-Exchange-Command</u> 10 <u>Ms-Sensitivity</u> 11

V

<u>Vendor-extensible fields</u> 7 <u>Versioning</u> 7

[MS-OCEXUM] — v20141019 Call Control for Exchange Unified Messaging Protocol Extensions

Copyright © 2014 Microsoft Corporation.