

[MS-OCGCWEB]: Persistent Chat Web Protocol

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
11/06/2012	0.1	New	Released new document.

Table of Contents

1 Introduction	4
1.1 Glossary	4
1.2 References	4
1.2.1 Normative References	4
1.2.2 Informative References	5
1.3 Overview	5
1.4 Relationship to Other Protocols	5
1.5 Prerequisites/Preconditions	5
1.6 Applicability Statement	5
1.7 Versioning and Capability Negotiation	5
1.8 Vendor-Extensible Fields	5
1.9 Standards Assignments	5
2 Messages	6
2.1 Transport	6
2.2 Message Syntax	6
2.2.1 Create a Room	6
2.2.2 View or Edit a Room	6
3 Protocol Details	7
3.1 Client Details	7
3.1.1 Abstract Data Model	7
3.1.2 Timers	7
3.1.3 Initialization	7
3.1.4 Higher-Layer Triggered Events	7
3.1.5 Message Processing Events and Sequencing Rules	7
3.1.6 Timer Events	7
3.1.7 Other Local Events	8
4 Protocol Examples	9
5 Security	10
5.1 Security Considerations for Implementers	10
5.2 Index of Security Parameters	10
6 Appendix A: Product Behavior	11
7 Change Tracking	12
8 Index	13

1 Introduction

The Persistent Chat Web Protocol provides a mechanism that allows the client of a persistent chat system to start an external chat room management web application.

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

GUID

Hypertext Transfer Protocol (HTTP)

Hypertext Transfer Protocol over Secure Sockets Layer (HTTPS)

The following terms are defined in [\[MS-OFCGLOS\]](#):

Session Initiation Protocol (SIP)

Uniform Resource Identifier (URI)

Uniform Resource Locator (URL)

web application

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[ISO-3166] International Organization for Standardization, "Codes for the Representation of Names of Countries and Their Subdivisions", ISO 3166, http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=24591

Note There is a charge to download the specification.

[ISO-639] International Organization for Standardization, "Codes for the Representation of Names of Languages", ISO 639, <http://www.loc.gov/standards/iso639-2/>

[MS-SIPREGE] Microsoft Corporation, "[Session Initiation Protocol \(SIP\) Registration Extensions](#)".

[MS-XCCOSIP] Microsoft Corporation, "[Extensible Chat Control Over Session Initiation Protocol \(SIP\)](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3986] Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005, <http://www.ietf.org/rfc/rfc3986.txt>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OFCGLOS] Microsoft Corporation, "[Microsoft Office Master Glossary](#)".

1.3 Overview

This protocol defines **Uniform Resource Locator (URL)** formats that allow a client of a persistent chat system based on Extensible Chat Control over Session Initiation Protocol (XCCOS) (defined by [\[MS-XCCOSIP\]](#)) to start an external room management **web application**. The client can receive the URLs either from a persistent chat server as described in [\[MS-XCCOSIP\]](#) section 2.2.2.1.10 or from a Session Initiation Protocol (SIP) server as part of the server in-band provisioning data described in [\[MS-SIPREGE\]](#) section 2.2.2.5.11.

1.4 Relationship to Other Protocols

This protocol uses URL formats as described in [\[RFC3986\]](#).

1.5 Prerequisites/Preconditions

This protocol assumes that both clients and the server support **Session Initiation Protocol (SIP)**, XCCOS protocol ([\[MS-XCCOSIP\]](#)), and that they implement the SIP registration extensions as described in [\[MS-SIPREGE\]](#).

1.6 Applicability Statement

This protocol is applicable when a persistent chat system client is using an external web application for chat room management.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

No new transports are required. The client starts an external web application in an instance of a web browser using the URL defined by this protocol.

2.2 Message Syntax

2.2.1 Create a Room

The room creation URL specifies the location of the chat room management web application. This URL is constructed by concatenating the base room management application URL configured for the persistent chat system with a single parameter:

clientlang (string): A <language>-<REGION> pair defining the client language. The <language> is a lowercase [\[ISO-639\]](#) language code. The <REGION> is an uppercase [\[ISO-3166\]](#) country/region identifier. This parameter is used by the room management application to choose the same language for the user interface as the chat client.

Example:

```
http://example.com/RM/?clientlang=en-US
```

2.2.2 View or Edit a Room

Depending on user permissions a user of the persistent chat system can either view or edit specific chat room properties. To do that the client MUST point the room management application to that specific room. The room management URL is constructed by concatenating the base room management application URL configured for the persistent chat system with two parameters:

clientlang (string): A <language>-<REGION> pair defining the client language. The <language> is a lowercase [\[ISO-639\]](#) language code. The <REGION> is an uppercase [\[ISO-3166\]](#) country/region identifier. This parameter is used by the application to choose the same language for the user interface.

id (string): A **GUID** of a room in the persistent chat system that uniquely identifies the chat room in the system. The GUID is extracted from the room **URI** returned by XCCOS searches, invitations or associated room retrieval as specified in [\[MS-XCCOSIP\]](#) sections [3.1.9](#) - [3.1.11](#).

Example:

A client receives an XCCOS invitation to join the room with the following URI:

```
ma-chan://example.com/61E092C7-89BB-4DC4-A3F5-8C23FA940FAB
```

The client extracts the room GUID from the room URI and makes the following URL to view or modify the room:

```
http://example.com/RM/?clientlang=en-US&id=61E092C7-89BB-4DC4-A3F5-8C23FA940FAB
```

3 Protocol Details

3.1 Client Details

3.1.1 Abstract Data Model

If chat room management is implemented in an external web application a client obtains the base URL of that application. To create a new room the client creates a URL by appending *clientlang* parameter to the base URL. To view or edit an existing room the client creates a URL by appending *clientlang* and *id* parameters to the base URL. If the base URL cannot be obtained the client MUST disable room management functionality.

3.1.2 Timers

None.

3.1.3 Initialization

The client obtains the base room management application URL from two sources. First room management URLs can be present in the in-band provisioning settings supplied by the Session Initiation Protocol (SIP) server upon the client sign-in. If the client is signed on inside the enterprise network it MUST use the **PersistentChatWebManagerUriInt** setting; if the client is signed on externally it MUST use the **PersistentChatWebManagerUriExt** setting as specified in [\[MS-SIPREGE\]](#) section 2.2.2.5.11.

The persistent chat server can override that base URL with another URL which the client receives when it establishes an XCCOS dialog ([\[MS-XCCOSIP\]](#)) with the server. In this case the client MUST use the **roomManagementUri** parameter from the reply to the XCCOS **getserverinfo** command as specified in [\[MS-XCCOSIP\]](#) section 3.1.4.5.

If the base URL cannot be obtained the client MUST disable room management functionality.

3.1.4 Higher-Layer Triggered Events

None.

3.1.5 Message Processing Events and Sequencing Rules

To start the room management web application the client MUST construct a web application URL for the specific action.

To create a new chat room, the client MUST add the *clientlang* parameter to the base URL as specified in section [2.2.1](#).

To view or edit a specific chat room, the client MUST add the *clientlang* parameter and the *id* parameter to the base URL as specified in section [2.2.2](#).

If the base URL configured for the system already contains some parameters the client appends the task-specific parameters as specified by this protocol to the existing parameter list.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

4 Protocol Examples

In the following example the client constructs a URL for creating a new room by appending the language parameter `en-US` to the base URL `http://example.com/rm/`:

```
http://example.com/rm/?clientlang=en-US
```

In the following example the client constructs a URL for editing an existing room by appending the language parameter `de-DE` and the room GUID `61E092C7-89BB-4DC4-A3F5-8C23FA940FAB` to the base URL `http://example.com/rm/`:

```
http://example.com/rm/?clientlang=de-DE&id=61E092C7-89BB-4DC4-A3F5-8C23FA940FAB
```

In the following example the client constructs a URL for creating a new room by appending the language parameter `en-US` to the base URL that already has a parameter `http://example.com/rm/?extensionparam=value`:

```
http://example.com/rm/?extensionparam=value&clientlang=en-US
```

5 Security

5.1 Security Considerations for Implementers

This protocol relies on the security of the used URL scheme. The scheme choice is left to implementers but it is strongly recommended to use **HTTPS** protocol rather than **HTTP**. User authorization mechanism is defined by the room management web application.

5.2 Index of Security Parameters

None.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Lync 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

8 Index

A

Abstract data model
[client](#) 7
[Applicability](#) 5

C

[Capability negotiation](#) 5
[Change tracking](#) 12
Client
[abstract data model](#) 7
[higher-layer triggered events](#) 7
[initialization](#) 7
[message processing](#) 7
[other local events](#) 8
[sequencing rules](#) 7
[timer events](#) 7
[timers](#) 7
[Create a Room message](#) 6

D

Data model - abstract
[client](#) 7

F

[Fields - vendor-extensible](#) 5

G

[Glossary](#) 4

H

Higher-layer triggered events
[client](#) 7

I

[Implementer - security considerations](#) 10
[Index of security parameters](#) 10
[Informative references](#) 5
Initialization
[client](#) 7
[Introduction](#) 4

M

Message processing
[client](#) 7
Messages
[Create a Room](#) 6
[transport](#) 6
[View or Edit a Room](#) 6

N

[Normative references](#) 4

O

Other local events
[client](#) 8
[Overview \(synopsis\)](#) 5

P

[Parameters - security index](#) 10
[Preconditions](#) 5
[Prerequisites](#) 5
[Product behavior](#) 11

R

[References](#) 4
[informative](#) 5
[normative](#) 4
[Relationship to other protocols](#) 5

S

Security
[implementer considerations](#) 10
[parameter index](#) 10
Sequencing rules
[client](#) 7
[Standards assignments](#) 5

T

Timer events
[client](#) 7
Timers
[client](#) 7
[Tracking changes](#) 12
[Transport](#) 6
Triggered events - higher-layer
[client](#) 7

V

[Vendor-extensible fields](#) 5
[Versioning](#) 5
[View or Edit a Room message](#) 6