

## [MS-OODF13]:

# Office Implementation Information for ODF 1.3 Standards Support

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **License Programs.** To see all of the protocols in scope under a specific license program and the associated patents, visit the [Patent Map](#).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

**Support.** For questions and support, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

## Revision Summary

Date	Revision History	Revision Class	Comments
7/15/2021	1.0	New	Released new document.
11/16/2021	2.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>27</b>
1.1	Glossary .....	27
1.2	References .....	27
1.2.1	Normative References .....	27
1.2.2	Informative References .....	28
1.3	Microsoft Implementations .....	28
<b>2</b>	<b>Standards Support Statements .....</b>	<b>29</b>
2.1	Normative Variations .....	29
2.1.1	Part 3 Section 3.1.2, office:document .....	29
2.1.2	Part 3 Section 3.1.3.2, office:document-content .....	29
2.1.3	Part 3 Section 3.1.3.3, office:document-styles .....	29
2.1.4	Part 3 Section 3.1.3.4, office:document-meta .....	30
2.1.5	Part 3 Section 3.1.3.5, office:document-settings .....	30
2.1.6	Part 3 Section 3.5, office:drawing .....	31
2.1.7	Part 3 Section 3.6, office:presentation .....	31
2.1.8	Part 3 Section 3.7, office:spreadsheet .....	31
2.1.9	Part 3 Section 3.8, office:chart .....	31
2.1.10	Part 3 Section 3.9, office:image .....	31
2.1.11	Part 3 Section 3.10, office:settings .....	32
2.1.12	Part 3 Section 3.10.2, config:config-item-set .....	32
2.1.13	Part 3 Section 3.10.3, config:config-item .....	32
2.1.14	Part 3 Section 3.10.4, config:config-item-map-indexed .....	32
2.1.15	Part 3 Section 3.10.5, config:config-item-map-entry .....	32
2.1.16	Part 3 Section 3.10.6, config:config-item-map-named .....	32
2.1.17	Part 3 Section 3.11, Cursor Position Setting .....	32
2.1.18	Part 3 Section 3.13, office:script .....	32
2.1.19	Part 3 Section 3.14, office:font-face-decls .....	33
2.1.20	Part 3 Section 3.15.2, office:styles .....	33
2.1.21	Part 3 Section 3.15.3, office:automatic-styles .....	34
2.1.22	Part 3 Section 3.15.4, office:master-styles .....	34
2.1.23	Part 3 Section 4.3.2.8, meta:printed-by .....	35
2.1.24	Part 3 Section 4.3.2.10, dc:date .....	35
2.1.25	Part 3 Section 4.3.2.11, meta:print-date .....	35
2.1.26	Part 3 Section 4.3.2.12, meta:template .....	35
2.1.27	Part 3 Section 4.3.2.13, meta:auto-reload .....	35
2.1.28	Part 3 Section 4.3.2.14, meta:hyperlink-behaviour .....	36
2.1.29	Part 3 Section 4.3.2.15, dc:language .....	36
2.1.30	Part 3 Section 4.3.3, meta:user-defined .....	36
2.1.31	Part 3 Section 5.1.2, text:h .....	36
2.1.32	Part 3 Section 5.1.3, text:p .....	38
2.1.33	Part 3 Section 5.2, text:page-sequence .....	40
2.1.34	Part 3 Section 5.2.2, text:page .....	40
2.1.35	Part 3 Section 5.3.1, text:list .....	40
2.1.36	Part 3 Section 5.3.3, text:list-header .....	41
2.1.37	Part 3 Section 5.3.6, text:numbered-paragraph .....	42
2.1.38	Part 3 Section 5.4, text:section .....	42
2.1.39	Part 3 Section 5.4.2, text:section-source .....	42
2.1.40	Part 3 Section 5.5.2, text:tracked-changes .....	42
2.1.41	Part 3 Section 5.5.3, text:changed-region .....	43
2.1.42	Part 3 Section 5.5.4, text:insertion .....	43
2.1.43	Part 3 Section 5.5.5, text:deletion .....	43
2.1.44	Part 3 Section 5.5.6, text:format-change .....	43
2.1.45	Part 3 Section 5.5.7, office:change-info .....	43
2.1.46	Part 3 Section 5.5.8.2, text:change-start .....	43

2.1.47	Part 3 Section 5.5.8.3, text:change-end	43
2.1.48	Part 3 Section 5.5.8.4, text:change	44
2.1.49	Part 3 Section 5.6, text:soft-page-break	44
2.1.50	Part 3 Section 6.1.2, White Space Characters	45
2.1.51	Part 3 Section 6.1.3, text:s	46
2.1.52	Part 3 Section 6.1.4, text:tab	47
2.1.53	Part 3 Section 6.1.5, text:line-break	47
2.1.54	Part 3 Section 6.1.7, text:span	48
2.1.55	Part 3 Section 6.1.8, text:a	49
2.1.56	Part 3 Section 6.1.10, text:number	49
2.1.57	Part 3 Section 6.2.1.2, text:bookmark	50
2.1.58	Part 3 Section 6.2.1.3, text:bookmark-start	51
2.1.59	Part 3 Section 6.2.1.4, text:bookmark-end	51
2.1.60	Part 3 Section 6.2.2.2, text:reference-mark	52
2.1.61	Part 3 Section 6.2.2.3, text:reference-mark-start	53
2.1.62	Part 3 Section 6.2.2.4, text:reference-mark-end	53
2.1.63	Part 3 Section 6.3.2, text:note	53
2.1.64	Part 3 Section 6.3.3, text:note-citation	54
2.1.65	Part 3 Section 6.3.4, text:note-body	55
2.1.66	Part 3 Section 6.4, text:ruby	56
2.1.67	Part 3 Section 6.4.3, text:ruby-text	56
2.1.68	Part 3 Section 7.3.5, text:page-continuation	56
2.1.69	Part 3 Section 7.3.6.2, text:sender-firstname	56
2.1.70	Part 3 Section 7.3.6.3, text:sender-lastname	57
2.1.71	Part 3 Section 7.3.6.4, text:sender-initials	57
2.1.72	Part 3 Section 7.3.6.5, text:sender-title	57
2.1.73	Part 3 Section 7.3.6.6, text:sender-position	57
2.1.74	Part 3 Section 7.3.6.7, text:sender-email	57
2.1.75	Part 3 Section 7.3.6.8, text:sender-phone-private	57
2.1.76	Part 3 Section 7.3.6.9, text:sender-fax	58
2.1.77	Part 3 Section 7.3.6.10, text:sender-company	58
2.1.78	Part 3 Section 7.3.6.11, text:sender-phone-work	58
2.1.79	Part 3 Section 7.3.6.12, text:sender-street	58
2.1.80	Part 3 Section 7.3.6.13, text:sender-city	58
2.1.81	Part 3 Section 7.3.6.14, text:sender-postal-code	58
2.1.82	Part 3 Section 7.3.6.15, text:sender-country	59
2.1.83	Part 3 Section 7.3.6.16, text:sender-state-or-province	59
2.1.84	Part 3 Section 7.3.7.1, text:author-name	59
2.1.85	Part 3 Section 7.3.7.2, text:author-initials	59
2.1.86	Part 3 Section 7.3.8, text:chapter	59
2.1.87	Part 3 Section 7.3.9, text:file-name	59
2.1.88	Part 3 Section 7.3.10, text:template-name	59
2.1.89	Part 3 Section 7.3.11, text:sheet-name	60
2.1.90	Part 3 Section 7.4.2, text:variable-decls	60
2.1.91	Part 3 Section 7.4.3, text:variable-decl	60
2.1.92	Part 3 Section 7.4.4, text:variable-set	60
2.1.93	Part 3 Section 7.4.5, text:variable-get	60
2.1.94	Part 3 Section 7.4.6, text:variable-input	60
2.1.95	Part 3 Section 7.4.7, text:user-field-decls	61
2.1.96	Part 3 Section 7.4.8, text:user-field-decl	61
2.1.97	Part 3 Section 7.4.9, text:user-field-get	61
2.1.98	Part 3 Section 7.4.10, text:user-field-input	61
2.1.99	Part 3 Section 7.4.11, text:sequence-decls	61
2.1.100	Part 3 Section 7.4.12, text:sequence-decl	61
2.1.101	Part 3 Section 7.4.13, text:sequence	61
2.1.102	Part 3 Section 7.4.14, text:expression	62
2.1.103	Part 3 Section 7.4.15, text:text-input	62
2.1.104	Part 3 Section 7.4.16, text:drop-down	62



2.1.105	Part 3 Section 7.4.17, text:label .....	62
2.1.106	Part 3 Section 7.5.2, text:initial-creator.....	62
2.1.107	Part 3 Section 7.5.3, text:creation-date.....	62
2.1.108	Part 3 Section 7.5.4, text:creation-time.....	62
2.1.109	Part 3 Section 7.5.5, text:description .....	63
2.1.110	Part 3 Section 7.5.6, text:user-defined.....	63
2.1.111	Part 3 Section 7.5.7, text:print-time .....	63
2.1.112	Part 3 Section 7.5.8, text:print-date .....	63
2.1.113	Part 3 Section 7.5.9, text:printed-by.....	63
2.1.114	Part 3 Section 7.5.10, text:title .....	64
2.1.115	Part 3 Section 7.5.11, text:subject .....	64
2.1.116	Part 3 Section 7.5.12, text:keywords .....	64
2.1.117	Part 3 Section 7.5.13, text:editing-cycles .....	64
2.1.118	Part 3 Section 7.5.14, text:editing-duration .....	64
2.1.119	Part 3 Section 7.5.15, text:modification-time .....	64
2.1.120	Part 3 Section 7.5.16, text:modification-date .....	64
2.1.121	Part 3 Section 7.5.17, text:creator.....	65
2.1.122	Part 3 Section 7.5.18.2, text:page-count.....	65
2.1.123	Part 3 Section 7.5.18.3, text:paragraph-count .....	65
2.1.124	Part 3 Section 7.5.18.4, text:word-count.....	65
2.1.125	Part 3 Section 7.5.18.5, text:character-count.....	65
2.1.126	Part 3 Section 7.5.18.6, text:table-count.....	65
2.1.127	Part 3 Section 7.5.18.7, text:image-count .....	66
2.1.128	Part 3 Section 7.5.18.8, text:object-count .....	66
2.1.129	Part 3 Section 7.6.2, form:connection-resource.....	66
2.1.130	Part 3 Section 7.6.3, text:database-display.....	71
2.1.131	Part 3 Section 7.6.4, text:database-next .....	71
2.1.132	Part 3 Section 7.6.5, text:database-row-select .....	72
2.1.133	Part 3 Section 7.6.6, text:database-row-number .....	72
2.1.134	Part 3 Section 7.6.7, text:database-name.....	72
2.1.135	Part 3 Section 7.7.1.2, text:page-variable-set .....	72
2.1.136	Part 3 Section 7.7.1.3, text:page-variable-get.....	72
2.1.137	Part 3 Section 7.7.2, text:placeholder .....	72
2.1.138	Part 3 Section 7.7.3, text:conditional-text .....	72
2.1.139	Part 3 Section 7.7.4, text:hidden-text .....	73
2.1.140	Part 3 Section 7.7.5, text:reference-ref .....	73
2.1.141	Part 3 Section 7.7.6, text:bookmark-ref .....	73
2.1.142	Part 3 Section 7.7.7, text:note-ref .....	73
2.1.143	Part 3 Section 7.7.8, text:sequence-ref .....	73
2.1.144	Part 3 Section 7.7.9, text:script.....	73
2.1.145	Part 3 Section 7.7.10, text:execute-macro.....	74
2.1.146	Part 3 Section 7.7.11, text:hidden-paragraph.....	74
2.1.147	Part 3 Section 7.7.12, text:dde-connection .....	74
2.1.148	Part 3 Section 7.7.13, text:measure .....	74
2.1.149	Part 3 Section 7.7.14, text:table-formula.....	74
2.1.150	Part 3 Section 8.1.2, text:toc-mark-start.....	74
2.1.151	Part 3 Section 8.1.3, text:toc-mark-end .....	75
2.1.152	Part 3 Section 8.1.4, text:toc-mark.....	75
2.1.153	Part 3 Section 8.1.5, text:user-index-mark-start .....	75
2.1.154	Part 3 Section 8.1.6, text:user-index-mark-end.....	75
2.1.155	Part 3 Section 8.1.7, text:user-index-mark .....	75
2.1.156	Part 3 Section 8.1.8, text:alphabetical-index-mark-start.....	76
2.1.157	Part 3 Section 8.1.9, text:alphabetical-index-mark-end .....	76
2.1.158	Part 3 Section 8.1.10, text:alphabetical-index-mark.....	76
2.1.159	Part 3 Section 8.1.11, text:bibliography-mark .....	76
2.1.160	Part 3 Section 8.2.2, text:index-body.....	76
2.1.161	Part 3 Section 8.2.3, text:index-title .....	76
2.1.162	Part 3 Section 8.3, text:table-of-content .....	77

2.1.163	Part 3 Section 8.3.3, text:table-of-content-entry-template	77
2.1.164	Part 3 Section 8.4, text:illustration-index	77
2.1.165	Part 3 Section 8.4.2, text:illustration-index-source	77
2.1.166	Part 3 Section 8.4.3, text:illustration-index-entry-template	77
2.1.167	Part 3 Section 8.5, text:table-index	77
2.1.168	Part 3 Section 8.5.2, text:table-index-source	78
2.1.169	Part 3 Section 8.5.3, text:table-index-entry-template	78
2.1.170	Part 3 Section 8.6, text:object-index	78
2.1.171	Part 3 Section 8.6.2, text:object-index-source	78
2.1.172	Part 3 Section 8.6.3, text:object-index-entry-template	78
2.1.173	Part 3 Section 8.7, text:user-index	78
2.1.174	Part 3 Section 8.7.2, text:user-index-source	79
2.1.175	Part 3 Section 8.7.3, text:user-index-entry-template	79
2.1.176	Part 3 Section 8.8, text:alphabetical-index	79
2.1.177	Part 3 Section 8.8.3, text:alphabetical-index-auto-mark-file	79
2.1.178	Part 3 Section 8.8.4, text:alphabetical-index-entry-template	79
2.1.179	Part 3 Section 8.9, text:bibliography	79
2.1.180	Part 3 Section 8.9.2, text:bibliography-source	79
2.1.181	Part 3 Section 8.9.3, text:bibliography-entry-template	79
2.1.182	Part 3 Section 8.10, text:index-source-styles	80
2.1.183	Part 3 Section 8.12, text:index-title-template	80
2.1.184	Part 3 Section 8.13.1, text:index-entry-chapter	80
2.1.185	Part 3 Section 8.13.2, text:index-entry-text	80
2.1.186	Part 3 Section 8.13.3, text:index-entry-page-number	80
2.1.187	Part 3 Section 8.13.4, text:index-entry-span	80
2.1.188	Part 3 Section 8.13.5, text:index-entry-bibliography	80
2.1.189	Part 3 Section 8.13.6, text:index-entry-tab-stop	81
2.1.190	Part 3 Section 8.13.7, text:index-entry-link-start	81
2.1.191	Part 3 Section 8.13.8, text:index-entry-link-end	81
2.1.192	Part 3 Section 9.1.2, table:table	81
2.1.193	Part 3 Section 9.1.3, table:table-row	82
2.1.194	Part 3 Section 9.1.5, table:covered-table-cell	82
2.1.195	Part 3 Section 9.1.6, table:table-column	83
2.1.196	Part 3 Section 9.1.7, table:table-header-rows	83
2.1.197	Part 3 Section 9.1.8, table:table-rows	83
2.1.198	Part 3 Section 9.1.9, table:table-row-group	83
2.1.199	Part 3 Section 9.1.10, table:table-column-group	84
2.1.200	Part 3 Section 9.1.11, table:table-header-columns	84
2.1.201	Part 3 Section 9.1.12, table:table-columns	84
2.1.202	Part 3 Section 9.1.13, table:title	84
2.1.203	Part 3 Section 9.1.14, table:desc	84
2.1.204	Part 3 Section 9.2.6, table:table-source	84
2.1.205	Part 3 Section 9.2.7, table:scenario	85
2.1.206	Part 3 Section 9.2.8, table:shapes	85
2.1.207	Part 3 Section 9.3.1, table:cell-range-source	85
2.1.208	Part 3 Section 9.3.2, table:detective	85
2.1.209	Part 3 Section 9.3.3, table:operation	85
2.1.210	Part 3 Section 9.3.4, table:highlighted-range	85
2.1.211	Part 3 Section 9.4.8, table:error-macro	86
2.1.212	Part 3 Section 9.4.9, table:label-range	86
2.1.213	Part 3 Section 9.4.10, table:label-ranges	86
2.1.214	Part 3 Section 9.4.11, table:named-expressions	86
2.1.215	Part 3 Section 9.5.3, table:filter-and	86
2.1.216	Part 3 Section 9.5.4, table:filter-or	86
2.1.217	Part 3 Section 9.5.6, table:filter-set-item	86
2.1.218	Part 3 Section 9.6.6, table:source-service	86
2.1.219	Part 3 Section 9.7, table:consolidation	87
2.1.220	Part 3 Section 9.8, table:dde-links	87

2.1.221	Part 3 Section 9.9.2, table:tracked-changes.....	87
2.1.222	Part 3 Section 9.9.15, table:target-range-address .....	87
2.1.223	Part 3 Section 10.2.1, style:handout-master .....	87
2.1.224	Part 3 Section 10.2.3, draw:layer .....	87
2.1.225	Part 3 Section 10.3.2, draw:rect .....	89
2.1.226	Part 3 Section 10.3.3, draw:line .....	90
2.1.227	Part 3 Section 10.3.4, draw:polyline .....	91
2.1.228	Part 3 Section 10.3.5, draw:polygon .....	92
2.1.229	Part 3 Section 10.3.6, draw:regular-polygon .....	93
2.1.230	Part 3 Section 10.3.7, draw:path .....	94
2.1.231	Part 3 Section 10.3.8, draw:circle .....	96
2.1.232	Part 3 Section 10.3.9, draw:ellipse .....	97
2.1.233	Part 3 Section 10.3.10, draw:connector.....	98
2.1.234	Part 3 Section 10.3.11, draw:caption .....	99
2.1.235	Part 3 Section 10.3.12, draw:measure .....	100
2.1.236	Part 3 Section 10.3.13, draw:control.....	101
2.1.237	Part 3 Section 10.3.14, draw:page-thumbnail .....	101
2.1.238	Part 3 Section 10.3.15, draw:g.....	102
2.1.239	Part 3 Section 10.3.16, draw:glue-point .....	103
2.1.240	Part 3 Section 10.3.17, svg:title .....	104
2.1.241	Part 3 Section 10.3.18, svg:desc .....	105
2.1.242	Part 3 Section 10.3.19, office:event-listeners .....	106
2.1.243	Part 3 Section 10.4.2, draw:frame .....	106
2.1.244	Part 3 Section 10.4.3, draw:text-box .....	107
2.1.245	Part 3 Section 10.4.4, draw:image.....	108
2.1.246	Part 3 Section 10.4.5, office:binary-data .....	108
2.1.247	Part 3 Section 10.4.6.3, draw:object-ole .....	109
2.1.248	Part 3 Section 10.4.7, draw:applet .....	110
2.1.249	Part 3 Section 10.4.8, draw:plugin.....	110
2.1.250	Part 3 Section 10.4.9, draw:param .....	110
2.1.251	Part 3 Section 10.4.10, draw:floating-frame.....	111
2.1.252	Part 3 Section 10.4.11.2, draw:contour-polygon.....	111
2.1.253	Part 3 Section 10.4.11.3, draw:contour-path .....	112
2.1.254	Part 3 Section 10.4.12, draw:a .....	112
2.1.255	Part 3 Section 10.4.13.2, draw:image-map.....	112
2.1.256	Part 3 Section 10.5.2, dr3d:scene.....	113
2.1.257	Part 3 Section 10.5.3, dr3d:light .....	113
2.1.258	Part 3 Section 10.5.4, dr3d:cube .....	113
2.1.259	Part 3 Section 10.5.5, dr3d:sphere .....	113
2.1.260	Part 3 Section 10.5.6, dr3d:extrude .....	114
2.1.261	Part 3 Section 10.5.7, dr3d:rotate .....	114
2.1.262	Part 3 Section 10.8.1, presentation:animations .....	114
2.1.263	Part 3 Section 10.8.2, presentation:sound .....	114
2.1.264	Part 3 Section 10.8.3, presentation:show-shape.....	114
2.1.265	Part 3 Section 10.8.4, presentation:show-text.....	115
2.1.266	Part 3 Section 10.8.5, presentation:hide-shape .....	115
2.1.267	Part 3 Section 10.8.6, presentation:hide-text.....	115
2.1.268	Part 3 Section 10.8.7, presentation:dim .....	115
2.1.269	Part 3 Section 10.8.8, presentation:play.....	115
2.1.270	Part 3 Section 10.8.9, presentation:animation-group .....	115
2.1.271	Part 3 Section 10.9.2, presentation:event-listener .....	115
2.1.272	Part 3 Section 10.9.3.1, presentation:header .....	115
2.1.273	Part 3 Section 10.9.3.2, presentation:header-decl .....	116
2.1.274	Part 3 Section 10.9.3.3, presentation:footer .....	116
2.1.275	Part 3 Section 10.9.3.4, presentation:footer-decl.....	116
2.1.276	Part 3 Section 10.9.3.5, presentation:date-time .....	116
2.1.277	Part 3 Section 10.9.3.6, presentation:date-time-decl .....	116
2.1.278	Part 3 Section 11.1, chart:chart .....	116

2.1.279	Part 3 Section 11.2.2, chart:subtitle.....	117
2.1.280	Part 3 Section 11.2.3, chart:footer.....	117
2.1.281	Part 3 Section 11.3, chart:coordinate-region .....	117
2.1.282	Part 3 Section 11.4, chart:legend .....	117
2.1.283	Part 3 Section 11.9, chart:axis .....	117
2.1.284	Part 3 Section 11.16, chart:mean-value .....	117
2.1.285	Part 3 Section 11.17, chart:error-indicator.....	118
2.1.286	Part 3 Section 11.18, chart:regression-curve .....	118
2.1.287	Part 3 Section 11.20, chart:stock-gain-marker .....	118
2.1.288	Part 3 Section 11.21, chart:stock-loss-marker.....	118
2.1.289	Part 3 Section 11.22, chart:stock-range-line .....	118
2.1.290	Part 3 Section 13.2, office:forms .....	118
2.1.291	Part 3 Section 13.3, form:form.....	119
2.1.292	Part 3 Section 13.4, xforms:model.....	119
2.1.293	Part 3 Section 13.5.2, form:text.....	119
2.1.294	Part 3 Section 13.5.3, form:textarea .....	119
2.1.295	Part 3 Section 13.5.4, form:password .....	119
2.1.296	Part 3 Section 13.5.5, form:file .....	120
2.1.297	Part 3 Section 13.5.6, form:formatted-text.....	120
2.1.298	Part 3 Section 13.5.7, form:number.....	120
2.1.299	Part 3 Section 13.5.8, form:date .....	120
2.1.300	Part 3 Section 13.5.9, form:time .....	120
2.1.301	Part 3 Section 13.5.10, form:fixed-text .....	120
2.1.302	Part 3 Section 13.5.11, form:combobox .....	121
2.1.303	Part 3 Section 13.5.12, form:item .....	121
2.1.304	Part 3 Section 13.5.13, form:listbox.....	121
2.1.305	Part 3 Section 13.5.14, form:option .....	121
2.1.306	Part 3 Section 13.5.15, form:button.....	121
2.1.307	Part 3 Section 13.5.16, form:image .....	121
2.1.308	Part 3 Section 13.5.17, form:checkbox.....	121
2.1.309	Part 3 Section 13.5.18, form:radio.....	122
2.1.310	Part 3 Section 13.5.19, form:frame.....	122
2.1.311	Part 3 Section 13.5.20, form:image-frame.....	122
2.1.312	Part 3 Section 13.5.21, form:hidden .....	122
2.1.313	Part 3 Section 13.5.22, form:grid .....	122
2.1.314	Part 3 Section 13.5.23, form:column.....	123
2.1.315	Part 3 Section 13.5.24, form:value-range .....	123
2.1.316	Part 3 Section 13.5.25, form:generic-control.....	123
2.1.317	Part 3 Section 13.7, form:properties .....	123
2.1.318	Part 3 Section 13.8, form:property .....	123
2.1.319	Part 3 Section 13.9, form:list-property .....	123
2.1.320	Part 3 Section 13.10, form:list-value.....	124
2.1.321	Part 3 Section 14.1, office:annotation .....	124
2.1.322	Part 3 Section 14.2, office:annotation-end.....	124
2.1.323	Part 3 Section 14.3, meta:date-string .....	124
2.1.324	Part 3 Section 14.4, meta:creator-initials .....	125
2.1.325	Part 3 Section 14.5.2, script:event-listener.....	125
2.1.326	Part 3 Section 14.6, math:math .....	125
2.1.327	Part 3 Section 14.6 (MathML 2.0 Section 3.2.3), Identifier (mi) .....	126
2.1.328	Part 3 Section 14.6 (MathML 2.0 Section 3.2.4), Number (mn).....	131
2.1.329	Part 3 Section 14.6 (MathML 2.0 Section 3.2.5), Operator, Fence, Separator or Accent (mo).....	135
2.1.330	Part 3 Section 14.6 (MathML 2.0 Section 3.2.6), Text (mtext).....	142
2.1.331	Part 3 Section 14.6 (MathML 2.0 Section 3.2.7), Space (mspace) .....	146
2.1.332	Part 3 Section 14.6 (MathML 2.0 Section 3.2.8), String Literal (ms) .....	150
2.1.333	Part 3 Section 14.6 (MathML 2.0 Section 3.2.9), Accessing glyphs for characters from MathML (mglyph).....	154

2.1.334	Part 3 Section 14.6 (MathML 2.0 Section 3.2.9.2), Accessing glyphs for characters from MathML (mglyph).....	159
2.1.335	Part 3 Section 14.6 (MathML 2.0 Section 3.3.1), Horizontally Group Sub-Expressions (mrow).....	159
2.1.336	Part 3 Section 14.6 (MathML 2.0 Section 3.3.2), Fractions (mfrac).....	160
2.1.337	Part 3 Section 14.6 (MathML 2.0 Section 3.3.3), Radicals (msqrt, mroot).....	162
2.1.338	Part 3 Section 14.6 (MathML 2.0 Section 3.3.4), Style Change (mstyle).....	165
2.1.339	Part 3 Section 14.6 (MathML 2.0 Section 3.3.5), Error Message (merror).....	169
2.1.340	Part 3 Section 14.6 (MathML 2.0 Section 3.3.6), Adjust Space Around Content (mpadded).....	170
2.1.341	Part 3 Section 14.6 (MathML 2.0 Section 3.3.7), Making Sub-Expressions Invisible (mphantom).....	174
2.1.342	Part 3 Section 14.6 (MathML 2.0 Section 3.3.8), Expression Inside Pair of Fences (mfenced).....	176
2.1.343	Part 3 Section 14.6 (MathML 2.0 Section 3.3.9), Enclose Expression Inside Notation (menclose).....	178
2.1.344	Part 3 Section 14.6 (MathML 2.0 Section 3.4.1), Subscript (msub).....	181
2.1.345	Part 3 Section 14.6 (MathML 2.0 Section 3.4.2), Superscript (msup).....	183
2.1.346	Part 3 Section 14.6 (MathML 2.0 Section 3.4.3), Subscript-superscript Pair (msubsup).....	184
2.1.347	Part 3 Section 14.6 (MathML 2.0 Section 3.4.4), Underscript (munder).....	185
2.1.348	Part 3 Section 14.6 (MathML 2.0 Section 3.4.5), Overscript (mover).....	187
2.1.349	Part 3 Section 14.6 (MathML 2.0 Section 3.4.6), Underscript-overscript Pair (munderover).....	189
2.1.350	Part 3 Section 14.6 (MathML 2.0 Section 3.4.7), Prescripts and Tensor Indices (mmultiscripts).....	191
2.1.351	Part 3 Section 14.6 (MathML 2.0 Section 3.5.1), Table or Matrix (mtable).....	193
2.1.352	Part 3 Section 14.6 (MathML 2.0 Section 3.5.2), Row in Table or Matrix (mtr).....	199
2.1.353	Part 3 Section 14.6 (MathML 2.0 Section 3.5.3), Labeled Row in Table or Matrix (mlabeledtr).....	201
2.1.354	Part 3 Section 14.6 (MathML 2.0 Section 3.5.4), Entry in Table or Matrix (mtd).....	202
2.1.355	Part 3 Section 14.6 (MathML 2.0 Section 3.5.5.4), Specifying alignment points using malignmark.....	204
2.1.356	Part 3 Section 14.6 (MathML 2.0 Section 3.6.1), Bind Action to Sub-Expression (maction).....	207
2.1.357	Part 3 Section 14.7.2, text:dde-connection-decls.....	209
2.1.358	Part 3 Section 14.7.3, text:dde-connection-decl.....	210
2.1.359	Part 3 Section 14.7.5, office:dde-source.....	210
2.1.360	Part 3 Section 15.2.3, anim:animateTransform.....	210
2.1.361	Part 3 Section 15.2.6, anim:animateColor.....	210
2.1.362	Part 3 Section 15.5, anim:audio.....	211
2.1.363	Part 3 Section 15.6.1, anim:command.....	211
2.1.364	Part 3 Section 16.2, style:style.....	211
2.1.365	Part 3 Section 16.3, style:map.....	213
2.1.366	Part 3 Section 16.4, style:default-style.....	215
2.1.367	Part 3 Section 16.6, style:header-style.....	217
2.1.368	Part 3 Section 16.7, style:footer-style.....	217
2.1.369	Part 3 Section 16.8, style:default-page-layout.....	217
2.1.370	Part 3 Section 16.10, style:header.....	218
2.1.371	Part 3 Section 16.11, style:header-first.....	218
2.1.372	Part 3 Section 16.12, style:footer.....	218
2.1.373	Part 3 Section 16.13, style:footer-first.....	218
2.1.374	Part 3 Section 16.14, style:header-left.....	218
2.1.375	Part 3 Section 16.15, style:footer-left.....	218
2.1.376	Part 3 Section 16.16, style:region-left.....	218
2.1.377	Part 3 Section 16.17, style:region-center.....	219
2.1.378	Part 3 Section 16.18, style:region-right.....	219
2.1.379	Part 3 Section 16.19, presentation:notes.....	220

2.1.380	Part 3 Section 16.20, table:table-template.....	220
2.1.381	Part 3 Section 16.21.2, table:first-row .....	220
2.1.382	Part 3 Section 16.21.3, table:last-row .....	221
2.1.383	Part 3 Section 16.21.4, table:first-column .....	221
2.1.384	Part 3 Section 16.21.5, table:last-column .....	221
2.1.385	Part 3 Section 16.21.6, table:body.....	221
2.1.386	Part 3 Section 16.21.7, table:even-rows.....	221
2.1.387	Part 3 Section 16.21.8, table:odd-rows .....	221
2.1.388	Part 3 Section 16.21.9, table:even-columns.....	221
2.1.389	Part 3 Section 16.21.10, table:odd-columns.....	221
2.1.390	Part 3 Section 16.22, table:background .....	222
2.1.391	Part 3 Section 16.23, style:font-face .....	222
2.1.392	Part 3 Section 16.24, svg:font-face-src .....	223
2.1.393	Part 3 Section 16.25, svg:font-face-name.....	223
2.1.394	Part 3 Section 16.26, svg:font-face-uri.....	223
2.1.395	Part 3 Section 16.27, svg:definition-src.....	223
2.1.396	Part 3 Section 16.28, svg:font-face-format .....	223
2.1.397	Part 3 Section 16.29.2, number:number-style .....	224
2.1.398	Part 3 Section 16.29.3, number:number .....	224
2.1.399	Part 3 Section 16.29.4, number:embedded-text .....	224
2.1.400	Part 3 Section 16.29.6, number:scientific-number .....	224
2.1.401	Part 3 Section 16.29.7, number:fraction .....	224
2.1.402	Part 3 Section 16.29.8, number:currency-style.....	224
2.1.403	Part 3 Section 16.29.9, number:currency-symbol .....	225
2.1.404	Part 3 Section 16.29.10, number:percentage-style .....	225
2.1.405	Part 3 Section 16.29.15, number:era .....	225
2.1.406	Part 3 Section 16.29.17, number:week-of-year .....	225
2.1.407	Part 3 Section 16.29.18, number:quarter .....	225
2.1.408	Part 3 Section 16.29.19, number:time-style.....	226
2.1.409	Part 3 Section 16.29.23, number:am-pm.....	226
2.1.410	Part 3 Section 16.29.24, number:boolean-style .....	226
2.1.411	Part 3 Section 16.29.25, number:boolean.....	226
2.1.412	Part 3 Section 16.29.26, number:text-style .....	227
2.1.413	Part 3 Section 16.29.27, number:text .....	227
2.1.414	Part 3 Section 16.29.28, number:text-content .....	227
2.1.415	Part 3 Section 16.29.29, style:text-properties .....	227
2.1.416	Part 3 Section 16.31.1, text:linenumbing-configuration .....	230
2.1.417	Part 3 Section 16.31.2, text:linenumbing-separator .....	230
2.1.418	Part 3 Section 16.31.3, text:notes-configuration.....	230
2.1.419	Part 3 Section 16.31.4, text:note-continuation-notice-forward .....	231
2.1.420	Part 3 Section 16.31.5, text:note-continuation-notice-backward .....	231
2.1.421	Part 3 Section 16.31.6, text:bibliography-configuration .....	231
2.1.422	Part 3 Section 16.32, text:list-style.....	232
2.1.423	Part 3 Section 16.34, text:list-level-style-number .....	233
2.1.424	Part 3 Section 16.36, text:outline-style .....	242
2.1.425	Part 3 Section 16.42.1, draw:gradient.....	242
2.1.426	Part 3 Section 16.42.2, svg:linearGradient.....	243
2.1.427	Part 3 Section 16.42.3, svg:radialGradient.....	244
2.1.428	Part 3 Section 16.42.5, draw:hatch.....	245
2.1.429	Part 3 Section 16.42.6, draw:fill-image .....	246
2.1.430	Part 3 Section 16.42.7, draw:opacity .....	247
2.1.431	Part 3 Section 16.42.8, draw:marker .....	249
2.1.432	Part 3 Section 16.42.9, draw:stroke-dash.....	249
2.1.433	Part 3 Section 16.43, style:presentation-page-layout .....	252
2.1.434	Part 3 Section 16.44, presentation:placeholder .....	252
2.1.435	Part 3 Section 17.2, style:page-layout-properties .....	252
2.1.436	Part 3 Section 17.3, style:background-image .....	253
2.1.437	Part 3 Section 17.4, style:footnote-sep .....	255

2.1.438	Part 3 Section 17.5, style:header-footer-properties.....	256
2.1.439	Part 3 Section 17.6, style:paragraph-properties .....	257
2.1.440	Part 3 Section 17.7, style:tab-stops .....	258
2.1.441	Part 3 Section 17.8, style:tab-stop .....	259
2.1.442	Part 3 Section 17.9, style:drop-cap .....	259
2.1.443	Part 3 Section 17.10, style:ruby-properties.....	260
2.1.444	Part 3 Section 17.11, style:section-properties .....	261
2.1.445	Part 3 Section 17.12, style:columns .....	262
2.1.446	Part 3 Section 17.13, style:column .....	264
2.1.447	Part 3 Section 17.14, style:column-sep .....	265
2.1.448	Part 3 Section 17.15, style:table-properties .....	266
2.1.449	Part 3 Section 17.16, style:table-column-properties.....	266
2.1.450	Part 3 Section 17.17, style:table-row-properties.....	268
2.1.451	Part 3 Section 17.18, style:table-cell-properties .....	269
2.1.452	Part 3 Section 17.19, style:list-level-properties .....	270
2.1.453	Part 3 Section 17.21, style:graphic-properties.....	273
2.1.454	Part 3 Section 18.2, W3C Schema Datatypes .....	275
2.1.455	Part 3 Section 18.3.2, anyIRI .....	275
2.1.456	Part 3 Section 18.3.16, language.....	275
2.1.457	Part 3 Section 18.3.25, points .....	275
2.1.458	Part 3 Section 18.3.27, relativeLength.....	275
2.1.459	Part 3 Section 18.3.34, targetFrameName .....	275
2.1.460	Part 3 Section 18.3.39, variableName .....	275
2.1.461	Part 3 Section 18.3.40, vector3D .....	276
2.1.462	Part 3 Section 19.4, anim:audio-level.....	276
2.1.463	Part 3 Section 19.6, anim:formula .....	276
2.1.464	Part 3 Section 19.7, anim:id .....	276
2.1.465	Part 3 Section 19.11, anim:sub-item.....	276
2.1.466	Part 3 Section 19.15, chart:class .....	276
2.1.467	Part 3 Section 19.16, chart:column-mapping .....	277
2.1.468	Part 3 Section 19.17, chart:data-source-has-labels.....	277
2.1.469	Part 3 Section 19.22, chart:legend-align.....	277
2.1.470	Part 3 Section 19.23, chart:legend-position .....	277
2.1.471	Part 3 Section 19.26, chart:row-mapping .....	278
2.1.472	Part 3 Section 19.37, db:catalog-name .....	278
2.1.473	Part 3 Section 19.68, db:max-row-count .....	278
2.1.474	Part 3 Section 19.92, dr3d:ambient-color .....	278
2.1.475	Part 3 Section 19.94, dr3d:diffuse-color .....	278
2.1.476	Part 3 Section 19.96, dr3d:distance .....	279
2.1.477	Part 3 Section 19.98, dr3d:focal-length .....	279
2.1.478	Part 3 Section 19.99, dr3d:lighting-mode .....	279
2.1.479	Part 3 Section 19.102, dr3d:projection .....	279
2.1.480	Part 3 Section 19.103, dr3d:shade-mode.....	280
2.1.481	Part 3 Section 19.104, dr3d:shadow-slant .....	281
2.1.482	Part 3 Section 19.107, dr3d:transform .....	281
2.1.483	Part 3 Section 19.108, dr3d:vpn.....	281
2.1.484	Part 3 Section 19.110, dr3d:vup.....	281
2.1.485	Part 3 Section 19.112, draw:angle.....	282
2.1.486	Part 3 Section 19.114, draw:border .....	283
2.1.487	Part 3 Section 19.115, draw:caption-id .....	284
2.1.488	Part 3 Section 19.116, draw:caption-point-x .....	285
2.1.489	Part 3 Section 19.117, draw:caption-point-y .....	285
2.1.490	Part 3 Section 19.118, draw:chain-next-name.....	285
2.1.491	Part 3 Section 19.120, draw:class-names .....	285
2.1.492	Part 3 Section 19.124, draw:concentric-gradient-fill-allowed .....	287
2.1.493	Part 3 Section 19.126, draw:copy-of.....	287
2.1.494	Part 3 Section 19.127, draw:corner-radius.....	287
2.1.495	Part 3 Section 19.129, draw:cx .....	287

2.1.496	Part 3 Section 19.130, draw:cy	288
2.1.497	Part 3 Section 19.131, draw:data	289
2.1.498	Part 3 Section 19.133, draw:display-name	290
2.1.499	Part 3 Section 19.134, draw:distance	293
2.1.500	Part 3 Section 19.135, draw:dots1	294
2.1.501	Part 3 Section 19.136, draw:dots1-length	295
2.1.502	Part 3 Section 19.137, draw:dots2	296
2.1.503	Part 3 Section 19.138, draw:dots2-length	298
2.1.504	Part 3 Section 19.141, draw:end-color	299
2.1.505	Part 3 Section 19.143, draw:end-intensity	300
2.1.506	Part 3 Section 19.145, draw:enhanced-path	301
2.1.507	Part 3 Section 19.146, draw:engine	301
2.1.508	Part 3 Section 19.148, draw:extrusion	301
2.1.509	Part 3 Section 19.149, draw:extrusion-allowed	302
2.1.510	Part 3 Section 19.150, draw:extrusion-brightness	302
2.1.511	Part 3 Section 19.151, draw:extrusion-color	302
2.1.512	Part 3 Section 19.152, draw:extrusion-depth	302
2.1.513	Part 3 Section 19.153, draw:extrusion-diffusion	303
2.1.514	Part 3 Section 19.154, draw:extrusion-first-light-direction	303
2.1.515	Part 3 Section 19.155, draw:extrusion-first-light-harsh	303
2.1.516	Part 3 Section 19.156, draw:extrusion-first-light-level	304
2.1.517	Part 3 Section 19.157, draw:extrusion-light-face	304
2.1.518	Part 3 Section 19.158, draw:extrusion-metal	304
2.1.519	Part 3 Section 19.159, draw:extrusion-number-of-line-segments	305
2.1.520	Part 3 Section 19.160, draw:extrusion-origin	305
2.1.521	Part 3 Section 19.161, draw:extrusion-rotation-angle	305
2.1.522	Part 3 Section 19.162, draw:extrusion-rotation-center	305
2.1.523	Part 3 Section 19.163, draw:extrusion-second-light-direction	306
2.1.524	Part 3 Section 19.164, draw:extrusion-second-light-harsh	306
2.1.525	Part 3 Section 19.165, draw:extrusion-second-light-level	306
2.1.526	Part 3 Section 19.166, draw:extrusion-shininess	307
2.1.527	Part 3 Section 19.167, draw:extrusion-skew	307
2.1.528	Part 3 Section 19.168, draw:extrusion-specularity	307
2.1.529	Part 3 Section 19.169, draw:extrusion-viewpoint	308
2.1.530	Part 3 Section 19.170, draw:filter-name	308
2.1.531	Part 3 Section 19.171, draw:formula	308
2.1.532	Part 3 Section 19.175, draw:glue-points	308
2.1.533	Part 3 Section 19.176, draw:handle-mirror-horizontal	309
2.1.534	Part 3 Section 19.177, draw:handle-mirror-vertical	309
2.1.535	Part 3 Section 19.179, draw:handle-position	309
2.1.536	Part 3 Section 19.182, draw:handle-range-x-maximum	310
2.1.537	Part 3 Section 19.183, draw:handle-range-x-minimum	310
2.1.538	Part 3 Section 19.184, draw:handle-range-y-maximum	311
2.1.539	Part 3 Section 19.185, draw:handle-range-y-minimum	311
2.1.540	Part 3 Section 19.186, draw:handle-switched	312
2.1.541	Part 3 Section 19.187, draw:id	312
2.1.542	Part 3 Section 19.190, draw:line-skew	313
2.1.543	Part 3 Section 19.196, draw:modifiers	314
2.1.544	Part 3 Section 19.197, draw:name	314
2.1.545	Part 3 Section 19.198, draw:nav-order	319
2.1.546	Part 3 Section 19.200, draw:notify-on-update-of-ranges	319
2.1.547	Part 3 Section 19.204, draw:path-stretchpoint-x	319
2.1.548	Part 3 Section 19.205, draw:path-stretchpoint-y	319
2.1.549	Part 3 Section 19.214, draw:start-color	320
2.1.550	Part 3 Section 19.216, draw:start-intensity	321
2.1.551	Part 3 Section 19.218, draw:style	322
2.1.552	Part 3 Section 19.219, draw:style-name	329
2.1.553	Part 3 Section 19.220, draw:text-areas	330



2.1.554	Part 3 Section 19.221, draw:text-path .....	331
2.1.555	Part 3 Section 19.222, draw:text-path-allowed.....	331
2.1.556	Part 3 Section 19.223, draw:text-path-mode .....	331
2.1.557	Part 3 Section 19.224, draw:text-path-same-letter-heights .....	331
2.1.558	Part 3 Section 19.225, draw:text-path-scale .....	332
2.1.559	Part 3 Section 19.226, draw:text-rotate-angle .....	332
2.1.560	Part 3 Section 19.227, draw:text-style-name .....	332
2.1.561	Part 3 Section 19.228, draw:transform .....	332
2.1.562	Part 3 Section 19.229, draw:type .....	339
2.1.563	Part 3 Section 19.231, draw:z-index .....	339
2.1.564	Part 3 Section 19.232, fo:column-count .....	340
2.1.565	Part 3 Section 19.233, fo:column-gap .....	341
2.1.566	Part 3 Section 19.234, fo:country .....	341
2.1.567	Part 3 Section 19.235, fo:end-indent .....	342
2.1.568	Part 3 Section 19.236, fo:language .....	342
2.1.569	Part 3 Section 19.237, fo:margin-left .....	343
2.1.570	Part 3 Section 19.238, fo:max-height.....	346
2.1.571	Part 3 Section 19.239, fo:max-width.....	347
2.1.572	Part 3 Section 19.240, fo:min-height .....	348
2.1.573	Part 3 Section 19.241, fo:min-width .....	349
2.1.574	Part 3 Section 19.242.2, text:alphabetical-index-source .....	349
2.1.575	Part 3 Section 19.243, fo:space-after .....	349
2.1.576	Part 3 Section 19.244, fo:space-before .....	350
2.1.577	Part 3 Section 19.245, fo:start-indent .....	350
2.1.578	Part 3 Section 19.246, fo:text-indent .....	350
2.1.579	Part 3 Section 19.247, form:allow-deletes .....	351
2.1.580	Part 3 Section 19.248, form:allow-inserts .....	351
2.1.581	Part 3 Section 19.249, form:allow-updates .....	351
2.1.582	Part 3 Section 19.251, form:apply-filter .....	351
2.1.583	Part 3 Section 19.254, form:bound-column.....	352
2.1.584	Part 3 Section 19.255, form:button-type .....	352
2.1.585	Part 3 Section 19.256, form:command .....	352
2.1.586	Part 3 Section 19.257, form:command-type.....	352
2.1.587	Part 3 Section 19.258, form:control-implementation .....	352
2.1.588	Part 3 Section 19.259, form:convert-empty-to-null .....	352
2.1.589	Part 3 Section 19.260, form:current-selected .....	353
2.1.590	Part 3 Section 19.262, form:current-value .....	353
2.1.591	Part 3 Section 19.263, form:data-field .....	353
2.1.592	Part 3 Section 19.264, form:datasource .....	353
2.1.593	Part 3 Section 19.267, form:detail-fields .....	353
2.1.594	Part 3 Section 19.268, form:disabled .....	353
2.1.595	Part 3 Section 19.269, form:dropdown .....	354
2.1.596	Part 3 Section 19.271, form:enctype.....	354
2.1.597	Part 3 Section 19.272, form:escape-processing .....	354
2.1.598	Part 3 Section 19.273, form:filter .....	354
2.1.599	Part 3 Section 19.275, form:for .....	354
2.1.600	Part 3 Section 19.276, form:id .....	354
2.1.601	Part 3 Section 19.277, form:ignore-result.....	355
2.1.602	Part 3 Section 19.278, form:image-align .....	355
2.1.603	Part 3 Section 19.279, form:image-data .....	355
2.1.604	Part 3 Section 19.280, form:image-position .....	355
2.1.605	Part 3 Section 19.282, form:label .....	355
2.1.606	Part 3 Section 19.285, form:list-source .....	356
2.1.607	Part 3 Section 19.286, form:list-source-type .....	356
2.1.608	Part 3 Section 19.287, form:master-fields .....	356
2.1.609	Part 3 Section 19.288, form:max-length.....	356
2.1.610	Part 3 Section 19.291, form:method .....	356
2.1.611	Part 3 Section 19.294, form:name .....	356

2.1.612	Part 3 Section 19.295, form:navigation-mode	357
2.1.613	Part 3 Section 19.296, form:order	357
2.1.614	Part 3 Section 19.299, form:printable	357
2.1.615	Part 3 Section 19.300, form:property-name	357
2.1.616	Part 3 Section 19.301, form:readonly	357
2.1.617	Part 3 Section 19.303, form:selected	357
2.1.618	Part 3 Section 19.304, form:size	358
2.1.619	Part 3 Section 19.309, form:tab-cycle	358
2.1.620	Part 3 Section 19.310, form:tab-index	358
2.1.621	Part 3 Section 19.311, form:tab-stop	358
2.1.622	Part 3 Section 19.313, form:title	358
2.1.623	Part 3 Section 19.316, form:value	358
2.1.624	Part 3 Section 19.317, form:visual-effect	359
2.1.625	Part 3 Section 19.326, meta:frame-count	359
2.1.626	Part 3 Section 19.327, meta:image-count	359
2.1.627	Part 3 Section 19.330, meta:object-count	359
2.1.628	Part 3 Section 19.332, meta:page-count	359
2.1.629	Part 3 Section 19.335, meta:sentence-count	359
2.1.630	Part 3 Section 19.336, meta:syllable-count	359
2.1.631	Part 3 Section 19.340, number:automatic-order	359
2.1.632	Part 3 Section 19.341, number:calendar	360
2.1.633	Part 3 Section 19.342, number:country	362
2.1.634	Part 3 Section 19.343, number:decimal-places	362
2.1.635	Part 3 Section 19.344, number:decimal-replacement	363
2.1.636	Part 3 Section 19.348, number:format-source	363
2.1.637	Part 3 Section 19.350, number:grouping	364
2.1.638	Part 3 Section 19.351, number:language	364
2.1.639	Part 3 Section 19.355, number:min-integer-digits	364
2.1.640	Part 3 Section 19.359, number:possessive-form	364
2.1.641	Part 3 Section 19.361, number:script	364
2.1.642	Part 3 Section 19.362, number:style	365
2.1.643	Part 3 Section 19.364, number:title	366
2.1.644	Part 3 Section 19.365, number:transliteration-country	367
2.1.645	Part 3 Section 19.366, number:transliteration-format	367
2.1.646	Part 3 Section 19.367, number:transliteration-language	367
2.1.647	Part 3 Section 19.368, number:transliteration-style	368
2.1.648	Part 3 Section 19.369, number:truncate-on-overflow	368
2.1.649	Part 3 Section 19.371, office:boolean-value	368
2.1.650	Part 3 Section 19.372, office:conversion-mode	369
2.1.651	Part 3 Section 19.373, office:currency	369
2.1.652	Part 3 Section 19.374, office:date-value	369
2.1.653	Part 3 Section 19.379, office:mimetype	370
2.1.654	Part 3 Section 19.380, office:name	370
2.1.655	Part 3 Section 19.383, office:string-value	371
2.1.656	Part 3 Section 19.384, office:target-frame	371
2.1.657	Part 3 Section 19.385, office:target-frame-name	371
2.1.658	Part 3 Section 19.386, office:time-value	372
2.1.659	Part 3 Section 19.387, office:title	372
2.1.660	Part 3 Section 19.388, office:value	373
2.1.661	Part 3 Section 19.389, office:value-type	373
2.1.662	Part 3 Section 19.391, presentation:action	374
2.1.663	Part 3 Section 19.393, presentation:class	374
2.1.664	Part 3 Section 19.394, presentation:class-names	374
2.1.665	Part 3 Section 19.396, presentation:direction	374
2.1.666	Part 3 Section 19.398, presentation:effect	375
2.1.667	Part 3 Section 19.400, presentation:full-screen	375
2.1.668	Part 3 Section 19.402, presentation:master-element	375
2.1.669	Part 3 Section 19.403, presentation:mouse-as-pen	375

2.1.670	Part 3 Section 19.404,	presentation:mouse-visible .....	375
2.1.671	Part 3 Section 19.410,	presentation:pause .....	375
2.1.672	Part 3 Section 19.413,	presentation:presentation-page-layout-name .....	375
2.1.673	Part 3 Section 19.418,	presentation:show-end-of-presentation-slide .....	376
2.1.674	Part 3 Section 19.419,	presentation:show-logo .....	376
2.1.675	Part 3 Section 19.420,	presentation:source.....	376
2.1.676	Part 3 Section 19.421,	presentation:speed.....	376
2.1.677	Part 3 Section 19.422,	presentation:start-scale .....	376
2.1.678	Part 3 Section 19.424,	presentation:start-with-navigator.....	376
2.1.679	Part 3 Section 19.425,	presentation:stay-on-top .....	376
2.1.680	Part 3 Section 19.426,	presentation:style-name .....	377
2.1.681	Part 3 Section 19.427,	presentation:transition-on-click.....	377
2.1.682	Part 3 Section 19.428,	presentation:use-date-time-name .....	377
2.1.683	Part 3 Section 19.429,	presentation:use-footer-name .....	377
2.1.684	Part 3 Section 19.430,	presentation:use-header-name .....	378
2.1.685	Part 3 Section 19.431,	presentation:user-transformed .....	378
2.1.686	Part 3 Section 19.433,	script:event-name.....	378
2.1.687	Part 3 Section 19.434,	script:language .....	378
2.1.688	Part 3 Section 19.435,	script:macro-name.....	378
2.1.689	Part 3 Section 19.437,	smil:accumulate.....	379
2.1.690	Part 3 Section 19.438,	smil:additive.....	379
2.1.691	Part 3 Section 19.439,	smil:attributeName .....	379
2.1.692	Part 3 Section 19.443,	smil:calcMode .....	379
2.1.693	Part 3 Section 19.448,	smil:endsync .....	380
2.1.694	Part 3 Section 19.449,	smil:fadeColor .....	380
2.1.695	Part 3 Section 19.450,	smil:fill .....	380
2.1.696	Part 3 Section 19.451,	smil:fillDefault .....	380
2.1.697	Part 3 Section 19.453,	smil:keySplines.....	380
2.1.698	Part 3 Section 19.458,	smil:restart .....	380
2.1.699	Part 3 Section 19.459,	smil:restartDefault .....	381
2.1.700	Part 3 Section 19.463,	smil:type .....	381
2.1.701	Part 3 Section 19.465,	style:adjustment.....	388
2.1.702	Part 3 Section 19.466,	style:apply-style-name .....	388
2.1.703	Part 3 Section 19.467,	style:auto-update.....	388
2.1.704	Part 3 Section 19.468,	style:base-cell-address .....	390
2.1.705	Part 3 Section 19.469,	style:char.....	390
2.1.706	Part 3 Section 19.470,	style:class .....	391
2.1.707	Part 3 Section 19.471,	style:color .....	393
2.1.708	Part 3 Section 19.472,	style:condition .....	393
2.1.709	Part 3 Section 19.473,	style:data-style-name.....	393
2.1.710	Part 3 Section 19.474,	style:default-outline-level.....	393
2.1.711	Part 3 Section 19.475,	style:display .....	393
2.1.712	Part 3 Section 19.476,	style:display-name .....	394
2.1.713	Part 3 Section 19.477,	style:distance .....	397
2.1.714	Part 3 Section 19.478,	style:distance-before-sep.....	397
2.1.715	Part 3 Section 19.470,	style:distance-after-sep .....	397
2.1.716	Part 3 Section 19.480,	style:family .....	397
2.1.717	Part 3 Section 19.481,	style:filter-name .....	409
2.1.718	Part 3 Section 19.482,	style:font-adornments .....	409
2.1.719	Part 3 Section 19.483,	style:font-charset.....	410
2.1.720	Part 3 Section 19.484,	style:font-family-generic.....	413
2.1.721	Part 3 Section 19.485,	style:font-pitch .....	415
2.1.722	Part 3 Section 19.486,	style:height .....	417
2.1.723	Part 3 Section 19.487,	style:leader-char.....	417
2.1.724	Part 3 Section 19.488,	style:leader-color .....	417
2.1.725	Part 3 Section 19.489,	style:leader-style .....	418
2.1.726	Part 3 Section 19.490,	style:leader-text .....	419
2.1.727	Part 3 Section 19.491,	style:leader-text-style .....	420

2.1.728	Part 3 Section 19.492, style:leader-type	421
2.1.729	Part 3 Section 19.493, style:leader-width	422
2.1.730	Part 3 Section 19.494, style:legend-expansion	423
2.1.731	Part 3 Section 19.495, style:legend-expansion-aspect-ratio	423
2.1.732	Part 3 Section 19.496, style:length	423
2.1.733	Part 3 Section 19.497, style:line-style	423
2.1.734	Part 3 Section 19.498, style:lines	424
2.1.735	Part 3 Section 19.500, style:list-style-name	424
2.1.736	Part 3 Section 19.501, style:master-page-name	424
2.1.737	Part 3 Section 19.502, style:name	424
2.1.738	Part 3 Section 19.503, style:next-style-name	428
2.1.739	Part 3 Section 19.504, style:num-format	429
2.1.740	Part 3 Section 19.505, style:num-letter-sync	440
2.1.741	Part 3 Section 19.506, style:num-prefix	443
2.1.742	Part 3 Section 19.507, style:num-suffix	445
2.1.743	Part 3 Section 19.508, style:page-layout-name	449
2.1.744	Part 3 Section 19.509, style:page-usage	449
2.1.745	Part 3 Section 19.510, style:parent-style-name	449
2.1.746	Part 3 Section 19.512, style:position	451
2.1.747	Part 3 Section 19.513, style:rel-height	452
2.1.748	Part 3 Section 19.514, style:rel-width	452
2.1.749	Part 3 Section 19.515, style:repeat	453
2.1.750	Part 3 Section 19.518, style:style-name	454
2.1.751	Part 3 Section 19.519, style:type	455
2.1.752	Part 3 Section 19.520, style:vertical-align	456
2.1.753	Part 3 Section 19.521, style:volatile	457
2.1.754	Part 3 Section 19.522, style:width	457
2.1.755	Part 3 Section 19.523, svg:accent-height	458
2.1.756	Part 3 Section 19.524, svg:alphabetic	458
2.1.757	Part 3 Section 19.525, svg:ascent	458
2.1.758	Part 3 Section 19.526, svg:bbox	458
2.1.759	Part 3 Section 19.527, svg:cap-height	459
2.1.760	Part 3 Section 19.531, svg:descent	459
2.1.761	Part 3 Section 19.532, svg:font-family	459
2.1.762	Part 3 Section 19.533, svg:font-size	459
2.1.763	Part 3 Section 19.534, svg:font-stretch	459
2.1.764	Part 3 Section 19.535, svg:font-style	461
2.1.765	Part 3 Section 19.536, svg:font-variant	461
2.1.766	Part 3 Section 19.537, svg:font-weight	461
2.1.767	Part 3 Section 19.542, svg:hanging	461
2.1.768	Part 3 Section 19.543, svg:height	461
2.1.769	Part 3 Section 19.544, svg:ideographic	464
2.1.770	Part 3 Section 19.545, svg:mathematical	464
2.1.771	Part 3 Section 19.546, svg:name	464
2.1.772	Part 3 Section 19.549, svg:overline-position	464
2.1.773	Part 3 Section 19.550, svg:overline-thickness	464
2.1.774	Part 3 Section 19.551, svg:panose-1	465
2.1.775	Part 3 Section 19.556, svg:slope	465
2.1.776	Part 3 Section 19.558, svg:stemh	465
2.1.777	Part 3 Section 19.559, svg:stemv	465
2.1.778	Part 3 Section 19.562, svg:strikethrough-position	465
2.1.779	Part 3 Section 19.563, svg:strikethrough-thickness	465
2.1.780	Part 3 Section 19.564, svg:string	466
2.1.781	Part 3 Section 19.566, svg:underline-position	466
2.1.782	Part 3 Section 19.567, svg:underline-thickness	466
2.1.783	Part 3 Section 19.568, svg:unicode-range	466
2.1.784	Part 3 Section 19.569, svg:units-per-em	466
2.1.785	Part 3 Section 19.570, svg:v-alphabetic	467

2.1.786	Part 3 Section 19.571, svg:v-hanging	467
2.1.787	Part 3 Section 19.572, svg:v-ideographic	467
2.1.788	Part 3 Section 19.573, svg:v-mathematical	467
2.1.789	Part 3 Section 19.574, svg:viewBox	467
2.1.790	Part 3 Section 19.575, svg:width	468
2.1.791	Part 3 Section 19.576, svg:widths	470
2.1.792	Part 3 Section 19.577, svg:x	470
2.1.793	Part 3 Section 19.580, svg:x-height	471
2.1.794	Part 3 Section 19.581, svg:y	472
2.1.795	Part 3 Section 19.588, table:application-data	473
2.1.796	Part 3 Section 19.589, table:automatic-find-labels	473
2.1.797	Part 3 Section 19.590, table:base-cell-address	473
2.1.798	Part 3 Section 19.591, table:bind-styles-to-content	473
2.1.799	Part 3 Section 19.592, table:border-color	474
2.1.800	Part 3 Section 19.593, table:buttons	474
2.1.801	Part 3 Section 19.594, table:case-sensitive	474
2.1.802	Part 3 Section 19.597, table:cell-range-address	474
2.1.803	Part 3 Section 19.600, table:condition	475
2.1.804	Part 3 Section 19.601, table:condition-source	475
2.1.805	Part 3 Section 19.602, table:condition-source-range-address	475
2.1.806	Part 3 Section 19.603, table:contains-error	475
2.1.807	Part 3 Section 19.605, table:content-validation-name	475
2.1.808	Part 3 Section 19.606, table:copy-back	475
2.1.809	Part 3 Section 19.607, table:copy-formulas	476
2.1.810	Part 3 Section 19.608, table:copy-styles	476
2.1.811	Part 3 Section 19.610, table:country	476
2.1.812	Part 3 Section 19.612, table:data-cell-range-address	476
2.1.813	Part 3 Section 19.613, table:database-name	476
2.1.814	Part 3 Section 19.615, table:data-type	476
2.1.815	Part 3 Section 19.618, table:date-value	477
2.1.816	Part 3 Section 19.619, table:default-cell-style-name	477
2.1.817	Part 3 Section 19.620, table:direction	478
2.1.818	Part 3 Section 19.621, table:display	478
2.1.819	Part 3 Section 19.622, table:display-border	478
2.1.820	Part 3 Section 19.623, table:display-duplicates	478
2.1.821	Part 3 Section 19.625, table:display-list	478
2.1.822	Part 3 Section 19.629, table:enabled	478
2.1.823	Part 3 Section 19.631, table:end-cell-address	479
2.1.824	Part 3 Section 19.636, table:end-x	479
2.1.825	Part 3 Section 19.637, table:end-y	479
2.1.826	Part 3 Section 19.641, table:field-number	480
2.1.827	Part 3 Section 19.642, table:filter-name	480
2.1.828	Part 3 Section 19.643, table:filter-options	480
2.1.829	Part 3 Section 19.646, table:formula	480
2.1.830	Part 3 Section 19.647, table:function	481
2.1.831	Part 3 Section 19.649, table:group-by-field-number	481
2.1.832	Part 3 Section 19.650, table:grouped-by	482
2.1.833	Part 3 Section 19.653, table:identify-categories	482
2.1.834	Part 3 Section 19.654, table:ignore-empty-rows	482
2.1.835	Part 3 Section 19.655, table:index	482
2.1.836	Part 3 Section 19.658, table:is-selection	482
2.1.837	Part 3 Section 19.659, table:is-sub-table	482
2.1.838	Part 3 Section 19.660, table:label-cell-range-address	483
2.1.839	Part 3 Section 19.661, table:language	483
2.1.840	Part 3 Section 19.667, table:link-to-source-data	483
2.1.841	Part 3 Section 19.668, table:marked-invalid	483
2.1.842	Part 3 Section 19.675, table:mode	483
2.1.843	Part 3 Section 19.677, table:name	483

2.1.844	Part 3 Section 19.679, table:number-columns-repeated	484
2.1.845	Part 3 Section 19.679.3, table:table-cell	484
2.1.846	Part 3 Section 19.680, table:number-columns-spanned	484
2.1.847	Part 3 Section 19.681, table:number-rows-repeated	485
2.1.848	Part 3 Section 19.682, table:number-rows-spanned	485
2.1.849	Part 3 Section 19.683, table:number-matrix-columns-spanned	485
2.1.850	Part 3 Section 19.684, table:number-matrix-rows-spanned	486
2.1.851	Part 3 Section 19.685, table:object-name	486
2.1.852	Part 3 Section 19.686, table:on-update-keep-size	486
2.1.853	Part 3 Section 19.688, table:operator	486
2.1.854	Part 3 Section 19.689, table:order	487
2.1.855	Part 3 Section 19.690, table:orientation	487
2.1.856	Part 3 Section 19.691, table:page-breaks-on-group-change	487
2.1.857	Part 3 Section 19.693, table:parse-sql-statement	487
2.1.858	Part 3 Section 19.694, table:password	488
2.1.859	Part 3 Section 19.697, table:print	488
2.1.860	Part 3 Section 19.698, table:print-ranges	488
2.1.861	Part 3 Section 19.699, table:protect	488
2.1.862	Part 3 Section 19.700, table:protected	489
2.1.863	Part 3 Section 19.700.4, table:table	489
2.1.864	Part 3 Section 19.700.5, table:table-cell	489
2.1.865	Part 3 Section 19.701, table:protection-key	489
2.1.866	Part 3 Section 19.702, table:protection-key-digest-algorithm	489
2.1.867	Part 3 Section 19.704, table:range-usable-as	490
2.1.868	Part 3 Section 19.705, table:refresh-delay	490
2.1.869	Part 3 Section 19.712, table:selected-page	491
2.1.870	Part 3 Section 19.715, table:show-filter-button	491
2.1.871	Part 3 Section 19.717, table:source-cell-range-addresses	491
2.1.872	Part 3 Section 19.719, table:source-name	491
2.1.873	Part 3 Section 19.730, table:style-name	491
2.1.874	Part 3 Section 19.733, table:table-background	492
2.1.875	Part 3 Section 19.735, table:target-cell-address	493
2.1.876	Part 3 Section 19.737, table:template-name	493
2.1.877	Part 3 Section 19.741, table:use-banding-columns-styles	493
2.1.878	Part 3 Section 19.742, table:use-banding-rows-styles	493
2.1.879	Part 3 Section 19.743, table:use-first-column-styles	493
2.1.880	Part 3 Section 19.744, table:use-first-row-styles	493
2.1.881	Part 3 Section 19.745, table:use-last-column-styles	493
2.1.882	Part 3 Section 19.746, table:use-last-row-styles	494
2.1.883	Part 3 Section 19.747, table:use-labels	494
2.1.884	Part 3 Section 19.748, table:use-regular-expressions	494
2.1.885	Part 3 Section 19.750, table:used-hierarchy	494
2.1.886	Part 3 Section 19.751, table:user-name	494
2.1.887	Part 3 Section 19.752, table:value	494
2.1.888	Part 3 Section 19.753, table:value-type	494
2.1.889	Part 3 Section 19.754, table:visibility	495
2.1.890	Part 3 Section 19.755, text:active	495
2.1.891	Part 3 Section 19.758, text:anchor-page-number	495
2.1.892	Part 3 Section 19.759, text:anchor-type	496
2.1.893	Part 3 Section 19.765, text:bullet-char	497
2.1.894	Part 3 Section 19.766, text:bullet-relative-size	497
2.1.895	Part 3 Section 19.767, text:capitalize-entries	498
2.1.896	Part 3 Section 19.768, text:c	498
2.1.897	Part 3 Section 19.775, text:class-names	499
2.1.898	Part 3 Section 19.777, text:combine-entries	501
2.1.899	Part 3 Section 19.778, text:combine-entries-with-dash	501
2.1.900	Part 3 Section 19.779, text:combine-entries-with-pp	501
2.1.901	Part 3 Section 19.780, text:comma-separated	501

2.1.902	Part 3 Section 19.781, text:cond-style-name	501
2.1.903	Part 3 Section 19.782, text:condition	502
2.1.904	Part 3 Section 19.784, text:consecutive-numbering	502
2.1.905	Part 3 Section 19.785, text:continue-list	503
2.1.906	Part 3 Section 19.786, text:continue-numbering	503
2.1.907	Part 3 Section 19.788, text:count-empty-lines	504
2.1.908	Part 3 Section 19.789, text:count-in-text-boxes	504
2.1.909	Part 3 Section 19.790, text:current-selected	504
2.1.910	Part 3 Section 19.798, text:date-adjust	504
2.1.911	Part 3 Section 19.799, text:date-value	504
2.1.912	Part 3 Section 19.800, text:default-style-name	505
2.1.913	Part 3 Section 19.802, text:display	505
2.1.914	Part 3 Section 19.803, text:display-levels	506
2.1.915	Part 3 Section 19.809, text:fixed	508
2.1.916	Part 3 Section 19.811, text:formula	509
2.1.917	Part 3 Section 19.812, text:global	509
2.1.918	Part 3 Section 19.814, text:increment	509
2.1.919	Part 3 Section 19.815, text:id	509
2.1.920	Part 3 Section 19.818, text:index-scope	510
2.1.921	Part 3 Section 19.819, text:ignore-case	510
2.1.922	Part 3 Section 19.822, text:is-list-header	510
2.1.923	Part 3 Section 19.827, text:key1	510
2.1.924	Part 3 Section 19.828, text:key2	510
2.1.925	Part 3 Section 19.829, text:key1-phonetic	510
2.1.926	Part 3 Section 19.830, text:key2-phonetic	511
2.1.927	Part 3 Section 19.834, text:level	511
2.1.928	Part 3 Section 19.837, text:main-entry	514
2.1.929	Part 3 Section 19.838, text:main-entry-style-name	514
2.1.930	Part 3 Section 19.839, text:master-page-name	514
2.1.931	Part 3 Section 19.841, text:name	514
2.1.932	Part 3 Section 19.843, text:note-class	514
2.1.933	Part 3 Section 19.845, text:number-lines	515
2.1.934	Part 3 Section 19.846, text:number-position	515
2.1.935	Part 3 Section 19.850, text:outline-level	515
2.1.936	Part 3 Section 19.850.5, text:index-entry-chapter	516
2.1.937	Part 3 Section 19.851, text:page-adjust	516
2.1.938	Part 3 Section 19.855, text:protected	516
2.1.939	Part 3 Section 19.856, text:protection-key	516
2.1.940	Part 3 Section 19.857, text:protection-key-digest-algorithm	517
2.1.941	Part 3 Section 19.859, text:ref-name	517
2.1.942	Part 3 Section 19.860, text:reference-format	517
2.1.943	Part 3 Section 19.861, text:relative-tab-stop-position	518
2.1.944	Part 3 Section 19.863, text:restart-numbering	518
2.1.945	Part 3 Section 19.869, text:select-page	518
2.1.946	Part 3 Section 19.871, text:sort-algorithm	518
2.1.947	Part 3 Section 19.874, text:start-value	518
2.1.948	Part 3 Section 19.880, text:style-name	520
2.1.949	Part 3 Section 19.883, text:tab-ref	525
2.1.950	Part 3 Section 19.886, text:time-adjust	526
2.1.951	Part 3 Section 19.887, text:time-value	526
2.1.952	Part 3 Section 19.889, text:track-changes	527
2.1.953	Part 3 Section 19.898, text:use-keys-as-entries	527
2.1.954	Part 3 Section 19.906, text:value	527
2.1.955	Part 3 Section 19.907, text:visited-style-name	527
2.1.956	Part 3 Section 19.910, xforms:bind	528
2.1.957	Part 3 Section 19.911, xhtml:about	528
2.1.958	Part 3 Section 19.912, xhtml:content	528
2.1.959	Part 3 Section 19.913, xhtml:datatype	529

2.1.960	Part 3 Section 19.914, xlink:property	529
2.1.961	Part 3 Section 19.915, xlink:actuate	530
2.1.962	Part 3 Section 19.916, xlink:href	531
2.1.963	Part 3 Section 19.917, xlink:show	535
2.1.964	Part 3 Section 19.919, xlink:type	537
2.1.965	Part 3 Section 19.920, xml:id	539
2.1.966	Part 3 Section 20.2, chart:angle-offset	540
2.1.967	Part 3 Section 20.7, chart:connect-bars	540
2.1.968	Part 3 Section 20.8, chart:data-label-number	540
2.1.969	Part 3 Section 20.9, chart:data-label-series	540
2.1.970	Part 3 Section 20.10, chart:data-label-symbol	540
2.1.971	Part 3 Section 20.11, chart:data-label-text	541
2.1.972	Part 3 Section 20.12, chart:deep	541
2.1.973	Part 3 Section 20.13, chart:display-label	541
2.1.974	Part 3 Section 20.14, chart:error-category	541
2.1.975	Part 3 Section 20.15, chart:error-lower-indicator	542
2.1.976	Part 3 Section 20.16, chart:error-lower-limit	542
2.1.977	Part 3 Section 20.18, chart:error-margin	542
2.1.978	Part 3 Section 20.19, chart:error-percentage	542
2.1.979	Part 3 Section 20.20, chart:error-upper-indicator	542
2.1.980	Part 3 Section 20.21, chart:error-upper-limit	542
2.1.981	Part 3 Section 20.23, chart:gap-width	543
2.1.982	Part 3 Section 20.24, chart:group-bars-per-axis	543
2.1.983	Part 3 Section 20.27, chart:interpolation	543
2.1.984	Part 3 Section 20.28, chart:interval-major	543
2.1.985	Part 3 Section 20.29, chart:interval-minor-divisor	544
2.1.986	Part 3 Section 20.30, chart:japanese-candle-stick	544
2.1.987	Part 3 Section 20.31, chart:label-arrangement	544
2.1.988	Part 3 Section 20.33, chart:label-position-negative	544
2.1.989	Part 3 Section 20.34, chart:lines	544
2.1.990	Part 3 Section 20.35, chart:link-data-style-to-source	544
2.1.991	Part 3 Section 20.36, chart:logarithmic	545
2.1.992	Part 3 Section 20.37, chart:maximum	545
2.1.993	Part 3 Section 20.39, chart:minimum	545
2.1.994	Part 3 Section 20.40, chart:origin	545
2.1.995	Part 3 Section 20.41, chart:overlap	545
2.1.996	Part 3 Section 20.42, chart:pie-offset	545
2.1.997	Part 3 Section 20.43, chart:percentage	546
2.1.998	Part 3 Section 20.44, chart:regression-force-intercept	546
2.1.999	Part 3 Section 20.45, chart:regression-intercept-value	546
2.1.1000	Part 3 Section 20.46, chart:regression-max-degree	546
2.1.1001	Part 3 Section 20.47, chart:regression-moving-type	546
2.1.1002	Part 3 Section 20.48, chart:regression-name	546
2.1.1003	Part 3 Section 20.49, chart:regression-period	546
2.1.1004	Part 3 Section 20.50, chart:regression-type	547
2.1.1005	Part 3 Section 20.53, chart:scale-text	547
2.1.1006	Part 3 Section 20.54, chart:series-source	547
2.1.1007	Part 3 Section 20.55, chart:sort-by-x-values	547
2.1.1008	Part 3 Section 20.57, chart:spline-order	547
2.1.1009	Part 3 Section 20.58, chart:spline-resolution	547
2.1.1010	Part 3 Section 20.59, chart:stacked	547
2.1.1011	Part 3 Section 20.60, chart:symbol-height	548
2.1.1012	Part 3 Section 20.61, chart:symbol-name	548
2.1.1013	Part 3 Section 20.62, chart:symbol-type	549
2.1.1014	Part 3 Section 20.63, chart:symbol-width	549
2.1.1015	Part 3 Section 20.64, chart:text-overlap	550
2.1.1016	Part 3 Section 20.65, chart:three-dimensional	550
2.1.1017	Part 3 Section 20.66, chart:tick-marks-major-inner	550



2.1.1018	Part 3 Section 20.67, chart:tick-marks-major-outer	550
2.1.1019	Part 3 Section 20.68, chart:tick-marks-minor-inner	550
2.1.1020	Part 3 Section 20.69, chart:tick-marks-minor-outer	550
2.1.1021	Part 3 Section 20.70, chart:tick-mark-position	550
2.1.1022	Part 3 Section 20.72, chart:vertical	550
2.1.1023	Part 3 Section 20.73, chart:visible	551
2.1.1024	Part 3 Section 20.75, dr3d:back-scale	551
2.1.1025	Part 3 Section 20.76, dr3d:backface-culling	551
2.1.1026	Part 3 Section 20.77, dr3d:close-back	551
2.1.1027	Part 3 Section 20.78, dr3d:close-front	552
2.1.1028	Part 3 Section 20.79, dr3d:depth	552
2.1.1029	Part 3 Section 20.81, dr3d:edge-rounding	552
2.1.1030	Part 3 Section 20.82, dr3d:edge-rounding-mode	553
2.1.1031	Part 3 Section 20.83, dr3d:emissive-color	553
2.1.1032	Part 3 Section 20.84, dr3d:end-angle	553
2.1.1033	Part 3 Section 20.85, dr3d:horizontal-segments	553
2.1.1034	Part 3 Section 20.87, dr3d:normals-direction	554
2.1.1035	Part 3 Section 20.88, dr3d:normals-kind	554
2.1.1036	Part 3 Section 20.89, dr3d:shadow	554
2.1.1037	Part 3 Section 20.90, dr3d:shininess	555
2.1.1038	Part 3 Section 20.91, dr3d:specular-color	555
2.1.1039	Part 3 Section 20.92, dr3d:texture-filter	555
2.1.1040	Part 3 Section 20.93, dr3d:texture-kind	555
2.1.1041	Part 3 Section 20.94, dr3d:texture-mode	556
2.1.1042	Part 3 Section 20.95, dr3d:texture-generation-mode-x	556
2.1.1043	Part 3 Section 20.96, dr3d:texture-generation-mode-y	556
2.1.1044	Part 3 Section 20.97, dr3d:vertical-segments	557
2.1.1045	Part 3 Section 20.98, draw:auto-grow-height	557
2.1.1046	Part 3 Section 20.99, draw:auto-grow-width	558
2.1.1047	Part 3 Section 20.100, draw:background-size	559
2.1.1048	Part 3 Section 20.101, draw:blue	559
2.1.1049	Part 3 Section 20.102, draw:caption-angle	559
2.1.1050	Part 3 Section 20.103, draw:caption-angle-type	559
2.1.1051	Part 3 Section 20.104, draw:caption-escape	560
2.1.1052	Part 3 Section 20.105, draw:caption-escape-direction	560
2.1.1053	Part 3 Section 20.106, draw:caption-fit-line-length	560
2.1.1054	Part 3 Section 20.107, draw:caption-gap	561
2.1.1055	Part 3 Section 20.108, draw:caption-line-length	561
2.1.1056	Part 3 Section 20.109, draw:caption-type	561
2.1.1057	Part 3 Section 20.110, draw:color-inversion	561
2.1.1058	Part 3 Section 20.111, draw:color-mode	562
2.1.1059	Part 3 Section 20.112, draw:contrast	563
2.1.1060	Part 3 Section 20.113, draw:decimal-places	564
2.1.1061	Part 3 Section 20.114, draw:draw-aspect	564
2.1.1062	Part 3 Section 20.115, draw:end-guide	564
2.1.1063	Part 3 Section 20.116, draw:end-line-spacing-horizontal	564
2.1.1064	Part 3 Section 20.117, draw:end-line-spacing-vertical	565
2.1.1065	Part 3 Section 20.118, draw:fill	565
2.1.1066	Part 3 Section 20.119, draw:fill-color	570
2.1.1067	Part 3 Section 20.120, draw:fill-gradient-name	571
2.1.1068	Part 3 Section 20.121, draw:fill-hatch-name	572
2.1.1069	Part 3 Section 20.122, draw:fill-hatch-solid	573
2.1.1070	Part 3 Section 20.123, draw:fill-image-height	574
2.1.1071	Part 3 Section 20.124, draw:fill-image-name	575
2.1.1072	Part 3 Section 20.125, draw:fill-image-ref-point	576
2.1.1073	Part 3 Section 20.126, draw:fill-image-ref-point-x	577
2.1.1074	Part 3 Section 20.127, draw:fill-image-ref-point-y	578
2.1.1075	Part 3 Section 20.128, draw:fill-image-width	578

2.1.1076	Part 3 Section 20.129,	draw:fit-to-contour.....	579
2.1.1077	Part 3 Section 20.130,	draw:fit-to-size .....	580
2.1.1078	Part 3 Section 20.131,	draw:frame-display-border.....	581
2.1.1079	Part 3 Section 20.132,	draw:frame-margin-horizontal .....	582
2.1.1080	Part 3 Section 20.133,	draw:frame-display-scrollbar .....	582
2.1.1081	Part 3 Section 20.134,	draw:frame-margin-vertical.....	582
2.1.1082	Part 3 Section 20.135,	draw:gamma .....	582
2.1.1083	Part 3 Section 20.136,	draw:green .....	583
2.1.1084	Part 3 Section 20.137,	draw:gradient-step-count.....	583
2.1.1085	Part 3 Section 20.138,	draw:guide-distance .....	584
2.1.1086	Part 3 Section 20.139,	draw:guide-overhang .....	584
2.1.1087	Part 3 Section 20.140,	draw:image-opacity.....	585
2.1.1088	Part 3 Section 20.141,	draw:line-distance.....	585
2.1.1089	Part 3 Section 20.142,	draw:luminance .....	585
2.1.1090	Part 3 Section 20.143,	draw:marker-end .....	586
2.1.1091	Part 3 Section 20.144,	draw:marker-end-center .....	586
2.1.1092	Part 3 Section 20.145,	draw:marker-end-width .....	586
2.1.1093	Part 3 Section 20.146,	draw:marker-start.....	587
2.1.1094	Part 3 Section 20.147,	draw:marker-start-center.....	587
2.1.1095	Part 3 Section 20.148,	draw:marker-start-width.....	587
2.1.1096	Part 3 Section 20.149,	draw:measure-align .....	588
2.1.1097	Part 3 Section 20.150,	draw:measure-vertical-align .....	588
2.1.1098	Part 3 Section 20.151,	draw:ole-draw-aspect.....	588
2.1.1099	Part 3 Section 20.153,	draw:opacity-name .....	589
2.1.1100	Part 3 Section 20.154,	draw:parallel .....	590
2.1.1101	Part 3 Section 20.155,	draw:placing.....	590
2.1.1102	Part 3 Section 20.156,	draw:red .....	590
2.1.1103	Part 3 Section 20.157,	draw:secondary-fill-color.....	591
2.1.1104	Part 3 Section 20.158,	draw:shadow .....	591
2.1.1105	Part 3 Section 20.159,	draw:shadow-color.....	592
2.1.1106	Part 3 Section 20.160,	draw:shadow-offset-x .....	593
2.1.1107	Part 3 Section 20.161,	draw:shadow-offset-y .....	595
2.1.1108	Part 3 Section 20.162,	draw:shadow-opacity.....	596
2.1.1109	Part 3 Section 20.163,	draw:show-unit.....	597
2.1.1110	Part 3 Section 20.164,	draw:start-guide .....	597
2.1.1111	Part 3 Section 20.165,	draw:start-line-spacing-horizontal .....	597
2.1.1112	Part 3 Section 20.166,	draw:start-line-spacing-vertical .....	598
2.1.1113	Part 3 Section 20.167,	draw:stroke.....	598
2.1.1114	Part 3 Section 20.169,	draw:stroke-dash-names .....	599
2.1.1115	Part 3 Section 20.170,	draw:stroke-linejoin .....	600
2.1.1116	Part 3 Section 20.171,	svg:stroke-linecap.....	608
2.1.1117	Part 3 Section 20.172,	draw:symbol-color .....	609
2.1.1118	Part 3 Section 20.173,	draw:textarea-horizontal-align.....	610
2.1.1119	Part 3 Section 20.174,	draw:textarea-vertical-align .....	611
2.1.1120	Part 3 Section 20.175,	draw:tile-repeat-offset.....	612
2.1.1121	Part 3 Section 20.176,	draw:visible-area-height .....	613
2.1.1122	Part 3 Section 20.177,	draw:visible-area-left .....	614
2.1.1123	Part 3 Section 20.178,	draw:visible-area-top .....	614
2.1.1124	Part 3 Section 20.179,	draw:visible-area-width .....	614
2.1.1125	Part 3 Section 20.180,	draw:unit .....	614
2.1.1126	Part 3 Section 20.181,	draw:wrap-influence-on-position .....	615
2.1.1127	Part 3 Section 20.182,	fo:background-color .....	615
2.1.1128	Part 3 Section 20.183.2,	fo:border.....	618
2.1.1129	Part 3 Section 20.183.3,	fo:border-bottom .....	621
2.1.1130	Part 3 Section 20.183.4,	fo:border-left.....	623
2.1.1131	Part 3 Section 20.183.5,	fo:border-right.....	626
2.1.1132	Part 3 Section 20.183.6,	fo:border-top.....	628
2.1.1133	Part 3 Section 20.184,	fo:break-after.....	630

2.1.1134	Part 3 Section 20.185,	fo:break-before	632
2.1.1135	Part 3 Section 20.186,	fo:clip	633
2.1.1136	Part 3 Section 20.187,	fo:color	634
2.1.1137	Part 3 Section 20.189,	fo:font-family	635
2.1.1138	Part 3 Section 20.190,	fo:font-size	636
2.1.1139	Part 3 Section 20.191,	fo:font-style	637
2.1.1140	Part 3 Section 20.192,	fo:font-variant	638
2.1.1141	Part 3 Section 20.193,	fo:font-weight	640
2.1.1142	Part 3 Section 20.194,	fo:height	642
2.1.1143	Part 3 Section 20.195,	fo:hyphenate	643
2.1.1144	Part 3 Section 20.196,	fo:hyphenation-keep	644
2.1.1145	Part 3 Section 20.197,	fo:hyphenation-ladder-count	645
2.1.1146	Part 3 Section 20.198,	fo:hyphenation-push-char-count	646
2.1.1147	Part 3 Section 20.199,	fo:hyphenation-remain-char-count	647
2.1.1148	Part 3 Section 20.200,	fo:keep-together	648
2.1.1149	Part 3 Section 20.201,	fo:keep-with-next	648
2.1.1150	Part 3 Section 20.202,	fo:language	650
2.1.1151	Part 3 Section 20.203,	fo:letter-spacing	650
2.1.1152	Part 3 Section 20.204,	fo:line-height	651
2.1.1153	Part 3 Section 20.205,	fo:margin	652
2.1.1154	Part 3 Section 20.206,	fo:margin-bottom	654
2.1.1155	Part 3 Section 20.208,	fo:margin-right	656
2.1.1156	Part 3 Section 20.209,	fo:margin-top	660
2.1.1157	Part 3 Section 20.214,	fo:orphans	663
2.1.1158	Part 3 Section 20.215,	fo:page-height	664
2.1.1159	Part 3 Section 20.216,	fo:page-width	664
2.1.1160	Part 3 Section 20.217,	fo:padding	664
2.1.1161	Part 3 Section 20.218,	fo:padding-bottom	666
2.1.1162	Part 3 Section 20.219,	fo:padding-left	668
2.1.1163	Part 3 Section 20.220,	fo:padding-right	670
2.1.1164	Part 3 Section 20.221,	fo:padding-top	672
2.1.1165	Part 3 Section 20.222,	fo:script	674
2.1.1166	Part 3 Section 20.223,	fo:text-align	675
2.1.1167	Part 3 Section 20.224,	fo:text-align-last	677
2.1.1168	Part 3 Section 20.226,	fo:text-shadow	679
2.1.1169	Part 3 Section 20.227,	fo:text-transform	680
2.1.1170	Part 3 Section 20.228,	fo:widows	682
2.1.1171	Part 3 Section 20.229,	fo:width	683
2.1.1172	Part 3 Section 20.230,	fo:wrap-option	684
2.1.1173	Part 3 Section 20.233,	presentation:display-date-time	685
2.1.1174	Part 3 Section 20.234,	presentation:display-footer	685
2.1.1175	Part 3 Section 20.235,	presentation:display-header	685
2.1.1176	Part 3 Section 20.236,	presentation:display-page-number	685
2.1.1177	Part 3 Section 20.238,	presentation:transition-speed	685
2.1.1178	Part 3 Section 20.239,	presentation:transition-style	685
2.1.1179	Part 3 Section 20.240,	presentation:transition-type	689
2.1.1180	Part 3 Section 20.246,	style:auto-text-indent	689
2.1.1181	Part 3 Section 20.247,	style:background-transparency	690
2.1.1182	Part 3 Section 20.248,	style:border-line-width	690
2.1.1183	Part 3 Section 20.249,	style:border-line-width-bottom	692
2.1.1184	Part 3 Section 20.250,	style:border-line-width-left	694
2.1.1185	Part 3 Section 20.251,	style:border-line-width-right	696
2.1.1186	Part 3 Section 20.252,	style:border-line-width-top	698
2.1.1187	Part 3 Section 20.253,	style:cell-protect	700
2.1.1188	Part 3 Section 20.255,	style:contextual-spacing	700
2.1.1189	Part 3 Section 20.256,	style:country-asian	700
2.1.1190	Part 3 Section 20.257,	style:country-complex	702
2.1.1191	Part 3 Section 20.258,	style:decimal-places	703

2.1.1192	Part 3 Section 20.259, style:diagonal-bl-tr.....	703
2.1.1193	Part 3 Section 20.260, style:diagonal-bl-tr-widths .....	704
2.1.1194	Part 3 Section 20.261, style:diagonal-tl-br.....	704
2.1.1195	Part 3 Section 20.262, style:diagonal-tl-br-widths .....	704
2.1.1196	Part 3 Section 20.263, style:direction.....	705
2.1.1197	Part 3 Section 20.264, style:dynamic-spacing .....	705
2.1.1198	Part 3 Section 20.265, style:editable.....	705
2.1.1199	Part 3 Section 20.266, style:first-page-number .....	705
2.1.1200	Part 3 Section 20.267, style:flow-with-text .....	706
2.1.1201	Part 3 Section 20.269, style:font-charset-asian .....	706
2.1.1202	Part 3 Section 20.270, style:font-charset-complex.....	707
2.1.1203	Part 3 Section 20.271, style:font-family-asian.....	708
2.1.1204	Part 3 Section 20.272, style:font-family-complex .....	709
2.1.1205	Part 3 Section 20.274, style:font-family-generic-asian .....	710
2.1.1206	Part 3 Section 20.275, style:font-family-generic-complex .....	711
2.1.1207	Part 3 Section 20.276, style:font-independent-line-spacing.....	712
2.1.1208	Part 3 Section 20.277, style:font-name .....	713
2.1.1209	Part 3 Section 20.278, style:font-name-asian.....	714
2.1.1210	Part 3 Section 20.279, style:font-name-complex .....	715
2.1.1211	Part 3 Section 20.281, style:font-pitch-asian.....	716
2.1.1212	Part 3 Section 20.282, style:font-pitch-complex .....	717
2.1.1213	Part 3 Section 20.283, style:font-relief .....	718
2.1.1214	Part 3 Section 20.284, style:font-size-asian .....	720
2.1.1215	Part 3 Section 20.285, style:font-size-complex.....	721
2.1.1216	Part 3 Section 20.286, style:font-size-rel.....	722
2.1.1217	Part 3 Section 20.287, style:font-size-rel-asian .....	723
2.1.1218	Part 3 Section 20.288, style:font-size-rel-complex.....	724
2.1.1219	Part 3 Section 20.289, style:font-style-asian.....	725
2.1.1220	Part 3 Section 20.290, style:font-style-complex .....	726
2.1.1221	Part 3 Section 20.291, style:font-style-name .....	727
2.1.1222	Part 3 Section 20.292, style:font-style-name-asian.....	728
2.1.1223	Part 3 Section 20.293, style:font-style-name-complex .....	729
2.1.1224	Part 3 Section 20.294, style:font-weight-asian .....	730
2.1.1225	Part 3 Section 20.295, style:font-weight-complex.....	731
2.1.1226	Part 3 Section 20.296, style:footnote-max-height.....	732
2.1.1227	Part 3 Section 20.297, style:glyph-orientation-vertical .....	732
2.1.1228	Part 3 Section 20.299, style:horizontal-rel .....	733
2.1.1229	Part 3 Section 20.300, style:join-border .....	734
2.1.1230	Part 3 Section 20.301, style:justify-single-word .....	735
2.1.1231	Part 3 Section 20.302, style:language-asian .....	735
2.1.1232	Part 3 Section 20.303, style:language-complex .....	737
2.1.1233	Part 3 Section 20.304, style:layout-grid-base-height.....	738
2.1.1234	Part 3 Section 20.306, style:layout-grid-color .....	738
2.1.1235	Part 3 Section 20.307, style:layout-grid-display .....	738
2.1.1236	Part 3 Section 20.308, style:layout-grid-lines.....	738
2.1.1237	Part 3 Section 20.309, style:layout-grid-mode .....	739
2.1.1238	Part 3 Section 20.310, style:layout-grid-print.....	739
2.1.1239	Part 3 Section 20.311, style:layout-grid-ruby-below .....	739
2.1.1240	Part 3 Section 20.312, style:layout-grid-ruby-height.....	739
2.1.1241	Part 3 Section 20.313, style:layout-grid-snap-to .....	740
2.1.1242	Part 3 Section 20.315, style:line-break.....	740
2.1.1243	Part 3 Section 20.316, style:letter-kerning .....	741
2.1.1244	Part 3 Section 20.317, style:line-height-at-least.....	742
2.1.1245	Part 3 Section 20.318, style:line-spacing.....	743
2.1.1246	Part 3 Section 20.319, style:may-break-between-rows.....	743
2.1.1247	Part 3 Section 20.320, style:min-row-height .....	744
2.1.1248	Part 3 Section 20.321, style:mirror .....	744
2.1.1249	Part 3 Section 20.326, style:number-wrapped-paragraphs.....	748

2.1.1250	Part 3 Section 20.327, style:overflow-behavior	748
2.1.1251	Part 3 Section 20.328, style:page-number	748
2.1.1252	Part 3 Section 20.329, style:paper-tray-name	749
2.1.1253	Part 3 Section 20.330, style:print	749
2.1.1254	Part 3 Section 20.331, style:print-content	750
2.1.1255	Part 3 Section 20.332, style:print-page-order	750
2.1.1256	Part 3 Section 20.333, style:print-orientation	751
2.1.1257	Part 3 Section 20.334, style:protect	751
2.1.1258	Part 3 Section 20.335, style:punctuation-wrap	755
2.1.1259	Part 3 Section 20.336, style:register-true	756
2.1.1260	Part 3 Section 20.337, style:register-truth-ref-style-name	757
2.1.1261	Part 3 Section 20.338, style:rel-column-width	757
2.1.1262	Part 3 Section 20.340.2, style:table-properties	758
2.1.1263	Part 3 Section 20.342, style:repeat-content	758
2.1.1264	Part 3 Section 20.346, style:rotation-align	758
2.1.1265	Part 3 Section 20.347, style:rotation-angle	758
2.1.1266	Part 3 Section 20.349, style:ruby-align	759
2.1.1267	Part 3 Section 20.350, style:ruby-position	760
2.1.1268	Part 3 Section 20.351, style:run-through	761
2.1.1269	Part 3 Section 20.352, style:scale-to	761
2.1.1270	Part 3 Section 20.353, style:scale-to-pages	761
2.1.1271	Part 3 Section 20.356, style:script-asian	761
2.1.1272	Part 3 Section 20.357, style:script-complex	761
2.1.1273	Part 3 Section 20.358, style:script-type	762
2.1.1274	Part 3 Section 20.359, style:shadow	763
2.1.1275	Part 3 Section 20.360, style:shrink-to-fit	765
2.1.1276	Part 3 Section 20.361, style:snap-to-layout-grid	765
2.1.1277	Part 3 Section 20.362, style:tab-stop-distance	766
2.1.1278	Part 3 Section 20.363, style:table-centering	767
2.1.1279	Part 3 Section 20.364, style:text-align-source	767
2.1.1280	Part 3 Section 20.365, style:text-autospace	767
2.1.1281	Part 3 Section 20.366, style:text-blinking	768
2.1.1282	Part 3 Section 20.367, style:text-combine	769
2.1.1283	Part 3 Section 20.368, style:text-combine-start-char	770
2.1.1284	Part 3 Section 20.369, style:text-combine-end-char	771
2.1.1285	Part 3 Section 20.370, style:text-emphasize	772
2.1.1286	Part 3 Section 20.371, style:text-line-through-color	774
2.1.1287	Part 3 Section 20.372, style:text-line-through-mode	775
2.1.1288	Part 3 Section 20.373, style:text-line-through-style	776
2.1.1289	Part 3 Section 20.374, style:text-line-through-text	778
2.1.1290	Part 3 Section 20.375, style:text-line-through-text-style	779
2.1.1291	Part 3 Section 20.376, style:text-line-through-type	780
2.1.1292	Part 3 Section 20.377, style:text-line-through-width	781
2.1.1293	Part 3 Section 20.378, style:text-outline	782
2.1.1294	Part 3 Section 20.379, style:text-overline-color	783
2.1.1295	Part 3 Section 20.380, style:text-overline-mode	783
2.1.1296	Part 3 Section 20.381, style:text-overline-style	783
2.1.1297	Part 3 Section 20.382, style:text-overline-type	783
2.1.1298	Part 3 Section 20.383, style:text-overline-width	783
2.1.1299	Part 3 Section 20.384, style:text-position	784
2.1.1300	Part 3 Section 20.385, style:text-rotation-angle	786
2.1.1301	Part 3 Section 20.386, style:text-rotation-scale	787
2.1.1302	Part 3 Section 20.387, style:text-scale	788
2.1.1303	Part 3 Section 20.388, style:text-underline-color	789
2.1.1304	Part 3 Section 20.389, style:text-underline-mode	790
2.1.1305	Part 3 Section 20.390, style:text-underline-style	791
2.1.1306	Part 3 Section 20.391, style:text-underline-type	794
2.1.1307	Part 3 Section 20.392, style:text-underline-width	795

2.1.1308	Part 3 Section 20.393, style:use-optimal-column-width	796
2.1.1309	Part 3 Section 20.394, style:use-optimal-row-height	796
2.1.1310	Part 3 Section 20.395, style:use-window-font-color	796
2.1.1311	Part 3 Section 20.397, style:vertical-pos	797
2.1.1312	Part 3 Section 20.398, style:vertical-rel	798
2.1.1313	Part 3 Section 20.399, style:width	799
2.1.1314	Part 3 Section 20.400, style:wrap	800
2.1.1315	Part 3 Section 20.401, style:wrap-contour	800
2.1.1316	Part 3 Section 20.402, style:wrap-contour-mode	800
2.1.1317	Part 3 Section 20.403, style:wrap-dynamic-threshold	800
2.1.1318	Part 3 Section 20.404, style:writing-mode	800
2.1.1319	Part 3 Section 20.404.6, style:table-cell-properties	806
2.1.1320	Part 3 Section 20.405, style:writing-mode-automatic	807
2.1.1321	Part 3 Section 20.406, svg:fill-rule	808
2.1.1322	Part 3 Section 20.408, svg:stroke-color	809
2.1.1323	Part 3 Section 20.409, svg:stroke-opacity	810
2.1.1324	Part 3 Section 20.410, svg:stroke-width	811
2.1.1325	Part 3 Section 20.412.2, style:list-level-properties	812
2.1.1326	Part 3 Section 20.414, table:align	812
2.1.1327	Part 3 Section 20.415, table:border-model	812
2.1.1328	Part 3 Section 20.416, table:display	812
2.1.1329	Part 3 Section 20.419, text:animation	813
2.1.1330	Part 3 Section 20.420, text:animation-delay	813
2.1.1331	Part 3 Section 20.421, text:animation-direction	813
2.1.1332	Part 3 Section 20.422, text:animation-repeat	813
2.1.1333	Part 3 Section 20.423, text:animation-start-inside	813
2.1.1334	Part 3 Section 20.424, text:animation-steps	813
2.1.1335	Part 3 Section 20.425, text:animation-stop-inside	813
2.1.1336	Part 3 Section 20.427, text:display	813
2.1.1337	Part 3 Section 20.428, text:dont-balance-text-columns	814
2.1.1338	Part 3 Section 20.430, text:line-number	814
2.1.1339	Part 3 Section 20.431, text:list-level-position-and-space-mode	815
2.1.1340	Part 3 Section 20.432, text:min-label-distance	816
2.1.1341	Part 3 Section 20.433, text:min-label-width	816
2.1.1342	Part 3 Section 20.435, text:space-before	817
2.1.1343	Part 2 Section 4.16.11, manifest:preferred-view-mode	818
2.1.1344	Part 2 Section 4.16.14, manifest:version	818
2.1.1345	Part 4 Section 6.18.19, CRITBINOM	818
2.1.1346	Part 2 Section 3.4, Encryption	819
2.1.1347	Part 2 Section 3.9, Interactions Between Encryption and Digital Signatures	819
2.1.1348	Part 2 Section 4.16.3, manifest:checksum-type	819
2.1.1349	Part 2 Section 4.8, manifest:encrypted-key	819
2.1.1350	Part 2 Section 4.9, manifest:encryption-method	820
2.1.1351	Part 2 Section 4.10, manifest:keyinfo	820
2.1.1352	Part 2 Section 4.11, manifest:PGPData	820
2.1.1353	Part 2 Section 4.12, manifest:PGPKeyID	821
2.1.1354	Part 2 Section 4.13, manifest:PGPKeyPacket	821
2.1.1355	Part 2 Section 4.14, manifest:CipherData	821
2.1.1356	Part 2 Section 4.15, manifest:CipherValue	821
2.1.1357	Part 2 Section 4.17, manifest:PGPAlgorithm	822
<b>3</b>	<b>Change Tracking</b>	<b>823</b>
<b>4</b>	<b>Index</b>	<b>824</b>

# 1 Introduction

In creating an interoperable implementation, it may be helpful to understand specific implementation choices made by other products implementing the same standard. For example, portions of the standard may provide only general guidance, leaving specific implementation choices up to the application implementer; in some circumstances, it may be helpful for other implementers to understand those choices. In addition, products often vary from or extend standards either because of application deviations or to allow for use scenarios not originally envisioned by the specifications. Documentation of those variations and/or extensions may also be helpful to other implementers.

The implementer notes contained in this document provide preliminary information about how Office implements new elements introduced in Open Document Format for Office Applications (OpenDocument) v1.3 [\[ODF1.3\]](#)

## 1.1 Glossary

This document uses the following terms:

**OfficeArt Math:** A component of Office that handles the processing for displaying native math typography elements used in OfficeArt textboxes or SmartArt in Word.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[ISO/IEC29500-1:2016] ISO/IEC, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 1: Fundamentals and Markup Language Reference", ISO/IEC 29500-1:2016, <https://www.iso.org/standard/71691.html>

[MathML2.0] Ausbrooks, R., et al., "Mathematical Markup Language (MathML) Version 2.0 (Second Edition)", W3C Recommendation, October 2003, <http://www.w3.org/TR/2003/REC-MathML2-20031021/>

[MS-DOCX] Microsoft Corporation, "[Word Extensions to the Office Open XML \(.docx\) File Format](#)".

[ODF1.3] OASIS, "Open Document Format for Office Applications (OpenDocument) Version 1.3", <https://docs.oasis-open.org/office/OpenDocument/v1.3/cs02/part1-introduction/OpenDocument-v1.3-cs02-part1-introduction.html>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3986] Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005, <http://www.rfc-editor.org/rfc/rfc3986.txt>

## **1.2.2 Informative References**

None.

## **1.3 Microsoft Implementations**

Microsoft Excel 2013

Microsoft Excel 2016

Microsoft Excel 2019

Microsoft Excel 2021

Microsoft PowerPoint 2013

Microsoft PowerPoint 2016

Microsoft PowerPoint 2019

Microsoft PowerPoint 2021

Microsoft Word 2013

Microsoft Word 2016

Microsoft Word 2019

Microsoft Word 2021



## 2 Standards Support Statements

This section contains implementation information about how Microsoft Excel 2013, Microsoft PowerPoint 2013, Microsoft Word 2013, Microsoft Excel 2016, Microsoft PowerPoint 2016, Microsoft Word 2016, Microsoft Excel 2019, Microsoft PowerPoint 2019, Microsoft Word 2019, Microsoft Excel 2021, Microsoft PowerPoint 2021, Microsoft Word 2021, and later implement Open Document Format for Office Applications (OpenDocument) v1.3. Unless otherwise specified, implementation information in this document pertains to the client implementations of Microsoft Office 2013, Microsoft Office 2016, Microsoft Office 2019, Microsoft Office 2021, and later.

### 2.1 Normative Variations

#### 2.1.1 Part 3 Section 3.1.2, office:document

- a. *The standard defines the element <office:document>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <office:document>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <office:document>*

This element is not supported in PowerPoint 2013 or later.

#### 2.1.2 Part 3 Section 3.1.3.2, office:document-content

- a. *The standard defines the attribute office:version, contained within the element <office:document-content>*

This attribute is supported in Word 2013 and later.

On load, Word ignores this attribute.

On save, Word always writes a value of "1.3" for this attribute.

- b. *The standard defines the attribute office:version, contained within the element <office:document-content>*

This attribute is supported in Excel 2013 and later.

On load, Excel ignores this attribute.

On save, Excel always writes a value of "1.3" for this attribute.

- c. *The standard defines the attribute office:version, contained within the element <office:document-content>*

This attribute is supported in PowerPoint 2021 and later.

On load, PowerPoint ignores this attribute.

On save, PowerPoint always writes a value of "1.3" for this attribute.

### **2.1.3 Part 3 Section 3.1.3.3, office:document-styles**

- a. *The standard defines the attribute office:version, contained within the element <office:document-styles>*

This attribute is supported in Word 2013 and later.

On load, Word ignores this attribute.

On save, Word always writes a value of "1.3" for this attribute.

- b. *The standard defines the attribute office:version, contained within the element <office:document-styles>*

This attribute is supported in Excel 2013 and later.

On load, Excel ignores this attribute.

On save, Excel always writes a value of "1.3" for this attribute.

- c. *The standard defines the attribute office:version, contained within the element <office:document-styles>*

This attribute is supported in PowerPoint 2021 and later.

On load, PowerPoint ignores this attribute.

On save, PowerPoint always writes a value of "1.3" for this attribute.

### **2.1.4 Part 3 Section 3.1.3.4, office:document-meta**

- a. *The standard defines the attribute office:version, contained within the element <office:document-meta>*

This attribute is supported in Word 2013 and later.

On load, Word ignores this attribute.

On save, Word always writes a value of "1.3" for this attribute.

- b. *The standard defines the attribute office:version, contained within the element <office:document-meta>*

This attribute is supported in Excel 2013 and later.

On load, Excel ignores this attribute.

On save, Excel always writes a value of "1.3" for this attribute.

- c. *The standard defines the attribute office:version, contained within the element <office:document-meta>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint ignores this attribute.

On save, PowerPoint always writes a value of "1.3" for this attribute.

### **2.1.5 Part 3 Section 3.1.3.5, office:document-settings**

- a. *The standard defines the attribute office:version, contained within the element <office:document-settings>*

This attribute is supported in Word 2013 and later.

On load, Word ignores this attribute.

On save, Word always writes a value of "1.3" for this attribute.

- b. *The standard defines the element <office:document-settings>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the attribute office:version, contained within the element <office:document-settings>*

This attribute is supported in PowerPoint 2021 and later.

On load, PowerPoint ignores this attribute.

On save, PowerPoint always writes a value of "1.3" for this attribute.

### **2.1.6 Part 3 Section 3.5, office:drawing**

- a. *The standard defines the element <office:drawing>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <office:drawing>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <office:drawing>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.7 Part 3 Section 3.6, office:presentation**

- a. *The standard defines the element <office:presentation>*

This element is not supported in Word 2013 or later.

### **2.1.8 Part 3 Section 3.7, office:spreadsheet**

- a. *The standard defines the element <office:spreadsheet>*

This element is not supported in Word 2013 or later.

### **2.1.9 Part 3 Section 3.8, office:chart**

- a. *The standard defines the element <office:chart>*

This element is not supported in Word 2013 or later.

### **2.1.10 Part 3 Section 3.9, office:image**

- a. *The standard defines the element <office:image>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <office:image>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <office:image>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.11 Part 3 Section 3.10, office:settings**

- a. *The standard defines the element <office:settings>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <office:settings>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.12 Part 3 Section 3.10.2, config:config-item-set**

- a. *The standard defines the element <config:config-item-set>, contained within the parent element <office:settings>*

This element is not supported in Word 2013 or later.

#### **2.1.13 Part 3 Section 3.10.3, config:config-item**

- a. *The standard defines the element <config:config-item>, contained within the parent element <office:settings>*

This element is not supported in Word 2013 or later.

#### **2.1.14 Part 3 Section 3.10.4, config:config-item-map-indexed**

- a. *The standard defines the element <config:config-item-map-indexed>, contained within the parent element <office:settings>*

This element is not supported in Word 2013 or later.

#### **2.1.15 Part 3 Section 3.10.5, config:config-item-map-entry**

- a. *The standard defines the element <config:config-item-map-entry>, contained within the parent element <office:settings>*

This element is not supported in Word 2013 or later.

#### **2.1.16 Part 3 Section 3.10.6, config:config-item-map-named**

- a. *The standard defines the element <config:config-item-map-named>, contained within the parent element <office:settings>*

This element is not supported in Word 2013 or later.

### 2.1.17 Part 3 Section 3.11, Cursor Position Setting

- a. *The standard defines the attribute Cursor Position Setting*

This attribute is not supported in Word 2013 or later.

### 2.1.18 Part 3 Section 3.13, office:script

- a. *The standard defines the element <office:script>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <office:script>*

This element is not supported in PowerPoint 2013 or later.

### 2.1.19 Part 3 Section 3.14, office:font-face-decls

- a. *The standard defines the element <office:font-face-decls>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels. On save, font face declarations are not written out. Instead, the fo:font-family property is used to specify font face.

- b. *The standard defines the element <office:font-face-decls>*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, chart titles and labels. It is supported on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Font face declarations are only supported on read and are not written out. Instead, the fo:font-family property is used to specify font face on write.

- c. *The standard defines the element <office:font-face-decls>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

Font face declarations are supported only on read, and are not written out. Instead, the "fo:font-family" property is used to specify font face on write.

### **2.1.20 Part 3 Section 3.15.2, office:styles**

- a. *The standard defines the element <office:styles>*

Word 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

- b. *The standard defines the element <number:date-style>, contained within the parent element <office:styles>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <number:time-style>, contained within the parent element <office:styles>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <office:styles>*

Excel 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

- e. *The standard defines the element <office:styles>*

This element is supported in PowerPoint 2013 and later.

Only the default style and the presentation page layouts are stored here. All others are stored in automatic or master styles.

PowerPoint 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

### **2.1.21 Part 3 Section 3.15.3, office:automatic-styles**

- a. *The standard defines the element <office:automatic-styles>*

Word 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

- b. *The standard defines the element <office:automatic-styles>*

Excel 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

- c. *The standard defines the element <office:automatic-styles>*

This element is supported in PowerPoint 2013 and later.

This element is used for all of the formatting styles in both the content and in the masters/layouts.

PowerPoint 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

#### **2.1.22 Part 3 Section 3.15.4, office:master-styles**

- a. *The standard defines the element <office:master-styles>*

This element is supported in PowerPoint 2013 and later.

This location is used to store all of the master pages and layouts.

#### **2.1.23 Part 3 Section 4.3.2.8, meta:printed-by**

- a. *The standard defines the element <meta:printed-by>*

This element is not supported in Word 2013 or later.

Word does not save this property.

- b. *The standard defines the element <meta:printed-by>*

This element is not supported in Excel 2013 or later.

Excel does not save this property.

- c. *The standard defines the element <meta:printed-by>*

This element is not supported in PowerPoint 2013 or later.

PowerPoint does not save this property.

#### **2.1.24 Part 3 Section 4.3.2.10, dc:date**

- a. *The standard defines the element <dc:date>*

This element is not supported in Excel 2013 or later.

#### **2.1.25 Part 3 Section 4.3.2.11, meta:print-date**

- a. *The standard defines the element <meta:print-date>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.26 Part 3 Section 4.3.2.12, meta:template**

- a. *The standard defines the element <meta:template>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.27 Part 3 Section 4.3.2.13, meta:auto-reload**

- a. *The standard defines the element <meta:auto-reload>*

This element is not supported in Word 2013 or later.

Word does not save this property.

- b. *The standard defines the element <meta:auto-reload>*

This element is not supported in Excel 2013 or later.

Excel does not save this property.

- c. *The standard defines the element <meta:auto-reload>*

This element is not supported in PowerPoint 2013 or later.

PowerPoint does not save this property.

### **2.1.28 Part 3 Section 4.3.2.14, meta:hyperlink-behaviour**

- a. *The standard defines the element <meta:hyperlink-behaviour>*

This element is not supported in Word 2013 or later.

Word does not save this property.

- b. *The standard defines the element <meta:hyperlink-behaviour>*

This element is not supported in Excel 2013 or later.

Excel does not save this property.

- c. *The standard defines the element <meta:hyperlink-behaviour>*

This element is not supported in PowerPoint 2013 or later.

PowerPoint does not save this property.

### **2.1.29 Part 3 Section 4.3.2.15, dc:language**

- a. *The standard defines the element <dc:language>, contained within the parent element <office:meta-data>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <dc:language>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.30 Part 3 Section 4.3.3, meta:user-defined**

- a. *The standard defines the element <meta:user-defined>*

This element is supported in Word 2013 and later.

Word supports the creation of user defined metadata in the following variant types: string, float, date, and boolean.

- b. *The standard defines the element <meta:user-defined>*

This element is supported in Excel 2013 and later.

Excel supports the creation of user defined metadata in the following variant types: string, float, date, and boolean.

- c. *The standard defines the element <meta:user-defined>*



This element is supported in PowerPoint 2013 and later.

PowerPoint supports the creation of user defined metadata in the following variant types: string, float, date, and boolean.

### 2.1.31 Part 3 Section 5.1.2, text:h

a. *The standard defines the element <text:h>*

This element is supported in Word 2013 and later.

Word allows multiple styles to map to the same outline level. According to Section 16.37 of the [\[ODF1.3\]](#) specification, each <text:outline-level-style> element may only have one style per specified level.

On save, Word takes the following steps to determine which style should be included for each level under the <text:outline-style> element:

First, Word looks for styles named "Heading 1" to "Heading 9" to see if any of them have numbering as a part of the style. If one of these styles has numbering, then that style is associated with the corresponding level in the outline style.

Next, Word looks for other styles to see if any of them have an outline level and numbering. If so, the first style that encountered with both a unique outline level and numbering is put into the outline-style.

On save, Word writes out text content within a <text:h> element under the following conditions:

- the paragraph has an outline level
- the paragraph's style is referenced by the outline style

On save, paragraphs with numbering, whose style is not in the outline-style but have a style:default-outline-level attribute in their paragraph style, are written out with <text:p> within a list.

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <text:h>*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. *The standard defines the element <text:h>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>
- <table:table-cell>

### 2.1.32 Part 3 Section 5.1.3, text:p

- a. *The standard defines the element <text:p>, contained within the parent element <draw:custom-shape>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:p>, contained within the parent element <text:list-item>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt.

- c. *The standard defines the element <text:p>, contained within the parent element <chart:title>*

This element is supported in Excel 2013 and later.

Excel loads <span> tags but does not save them.

- d. *The standard defines the element <text:p>, contained within the parent element <draw:connector>*

This element is not supported in Excel 2013 or later.

- e. *The standard defines the element <text:p>, contained within the parent element <draw:image>*

This element is not supported in Excel 2013 or later.

- f. *The standard defines the element <text:p>, contained within the parent element <draw:line>*

This element is not supported in Excel 2013 or later.

- g. *The standard defines the element <text:p>, contained within the parent element <text:list-header>*

OfficeArt Math in Excel 2013 supports this element on save, for text in text boxes and shapes. It is supported on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The text:list-header property is only supported on load and is not saved.

- h. *The standard defines the element <text:p>, contained within the parent element <text:list-item>*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes, shapes, and SmartArt. On load, it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the element <text:p>, contained within the parent element <draw:connector>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

- j. *The standard defines the element <text:p>, contained within the parent element <draw:image>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

- k. *The standard defines the element <text:p>, contained within the parent element <draw:line>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

- l. *The standard defines the element <text:p>, contained within the parent element <text:list-header>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text:list-header" property is supported only on read and is not written out.

- m. *The standard defines the element <text:p>, contained within the parent element <text:list-item>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.33 Part 3 Section 5.2, text:page-sequence**

- a. *The standard defines the element <text:page-sequence>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:page-sequence>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.34 Part 3 Section 5.2.2, text:page**

- a. *The standard defines the element <text:page>, contained within the parent element <text:page-sequence>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:page>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.35 Part 3 Section 5.3.1, text:list**

- a. *The standard defines the element <text:list>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt.

- b. *The standard defines the element <text:list>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:list>, contained within the parent element <draw:connector>*

This element is not supported in Excel 2013 or later.

- d. *The standard defines the element <text:list>, contained within the parent element <draw:image>*

This element is not supported in Excel 2013 or later.

- e. *The standard defines the element <text:list>, contained within the parent element <draw:line>*

This element is not supported in Excel 2013 or later.

- f. *The standard defines the element <text:list>, contained within the parent element <draw:connector>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

- g. *The standard defines the element <text:list>, contained within the parent element <draw:image>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

- h. *The standard defines the element <text:list>, contained within the parent element <draw:line>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.36 Part 3 Section 5.3.3, text:list-header**

- a. *The standard defines the element <text:list-header>, contained within the parent element <text:list>*

This element is not supported in Word 2013 or later.

On load, Word drops the <text:list-header> element but retains the content of the tags as a paragraph.

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt.

- b. *The standard defines the element <text:list-header>, contained within the parent element <text:list>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- c. *The standard defines the element <text:list-header>, contained within the parent element <text:list>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text:list-header" attribute is supported on load, but is not saved. To achieve the same effect on save, level 0 list items are saved as a regular paragraphs, that is <text:p> elements, and text greater than level 0 is assigned a list style with an empty "style:num-format" attribute (style:num-format="").

### **2.1.37 Part 3 Section 5.3.6, text:numbered-paragraph**

- a. *The standard defines the element <text:numbered-paragraph>*

This element is not supported in Word 2013 or later.

*This element was deprecated in the ODF 1.3 standard.*

- b. *The standard defines the element <text:numbered-paragraph>*

This element is not supported in Excel 2013 or later.

*This element was deprecated in the ODF 1.3 standard.*

### **2.1.38 Part 3 Section 5.4, text:section**

- a. *The standard defines the element <text:section>*

This element is supported in Word 2013 and later.

On save, a continuous section in Word is mapped to the <text:section> element. The following properties are preserved: left and right margins, columns, and text direction.

- b. *The standard defines the element <text:section>, contained within the parent element <draw:text-box>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <text:section>, contained within the parent element <style:drop-cap>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <text:section>*

This element is not supported in Excel 2013 or later.

This element is not supported in PowerPoint 2013 or later.

### **2.1.39 Part 3 Section 5.4.2, text:section-source**

- a. *The standard defines the element <text:section-source>*

This element is not supported in Word 2013 or later.

This element is not supported in Excel 2013 or later.

This element is not supported in PowerPoint 2013 or later.

#### **2.1.40 Part 3 Section 5.5.2, text:tracked-changes**

- a. *The standard defines the element <text:tracked-changes>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <text:tracked-changes>*  
This element is not supported in Excel 2013 or later.
- c. *The standard defines the element <text:tracked-changes>*  
This element is not supported in PowerPoint 2013 or later.

#### **2.1.41 Part 3 Section 5.5.3, text:changed-region**

- a. *The standard defines the element <text:changed-region>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <text:changed-region>*

#### **2.1.42 Part 3 Section 5.5.4, text:insertion**

- a. *The standard defines the element <text:insertion>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <text:insertion>*

#### **2.1.43 Part 3 Section 5.5.5, text:deletion**

- a. *The standard defines the element <text:deletion>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <text:deletion>*

#### **2.1.44 Part 3 Section 5.5.6, text:format-change**

- a. *The standard defines the element <text:format-change>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <text:format-change>*

#### **2.1.45 Part 3 Section 5.5.7, office:change-info**

- a. *The standard defines the element <office:change-info>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <office:change-info>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.46 Part 3 Section 5.5.8.2, text:change-start**

- a. *The standard defines the element <text:change-start>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:change-start>*

### **2.1.47 Part 3 Section 5.5.8.3, text:change-end**

- a. *The standard defines the element <text:change-end>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:change-end>*

### **2.1.48 Part 3 Section 5.5.8.4, text:change**

- a. *The standard defines the element <text:change>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:change>*

### **2.1.49 Part 3 Section 5.6, text:soft-page-break**

- a. *The standard defines the element <text:soft-page-break>*

This element is supported in Word 2013 and later.

On save, Word puts a <text:soft-page-break> element everywhere it would normally mark a soft page break location for all of its other document formats. For ODF, this is only done if <text:soft-page-break> is allowed in that location by the ODF specification.

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:soft-page-break>, contained within the parent element <table:table>*

This element is supported in Word 2013 and later.

Word writes out this element everywhere it would for all its other document formats, as long as it is allowed in that location by the ODF specification.

- c. *The standard defines the element <text:soft-page-break>, contained within the parent element <text:p>*

This element is supported in Word 2013 and later.

On save, Word puts a <text:soft-page-break> element everywhere it would normally mark a soft page break location for all of its other document formats. For ODF, this is only done if <text:soft-page-break> is allowed in that location by the ODF specification.

- d. *The standard defines the attribute text:soft-page-break, contained within the element <table:table>, contained within the parent element <table:dde-link>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the element <text:soft-page-break>*



This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the element <text:soft-page-break>, contained within the parent element <text:p>*

This element is not supported in Excel 2013 or later.

- g. *The standard defines the element <text:soft-page-break>*

This element is not supported in PowerPoint 2013 or later.

OfficeArt Math in PowerPoint 2013 or later does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- h. *The standard defines the element <text:soft-page-break>, contained within the parent element <table:table>*

- i. *The standard defines the element <text:soft-page-break>, contained within the parent element <table:table-rows>*

### **2.1.50 Part 3 Section 6.1.2, White Space Characters**

The standard defines an ordered seven-step algorithm for collapsing white space characters in paragraph elements <text:p> and <text:h>.

PowerPoint and graphical content in Word and Excel have partial support for this algorithm, according to the following details:

Algorithm step 1: The application does not support <text:ruby> elements and therefore skips this step.

Algorithm step 2: The application removes all descendant elements of a text paragraph, so does perform this step.

Algorithm step 3: The application removes all descendant elements of <text:s> and does not perform this step of promoting nested text elements to the ancestor paragraph.

Algorithm steps 4-7: The application does perform these steps.

Word content (other than graphical content) has partial support for this algorithm, according to the following details:

Algorithm step 1: Word's descendant <text:ruby> elements are not replaced with their <text:ruby-base> child elements.

Algorithm step 2: Word does not remove these child elements from the paragraph element. The exception is the <text:text-input> element, which does get removed.

Algorithm steps 3-7: Word does perform these steps.

Excel content (other than graphical content) has partial support for this algorithm, according to the following details:

Algorithm steps 1 and 2: Excel supports steps 1 and 2 of the algorithm.

Algorithm step 3: Excel does not support step 3 of the algorithm, which promotes nested text elements to the ancestor paragraph element.

Algorithm step 4-7: Excel does perform these steps.

### 2.1.51 Part 3 Section 6.1.3, text:s

a. *The standard defines the element <text:s>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <text:s>*

This element is supported in Excel 2013 and later.

On load, Excel reads this attribute. On save, Excel does not write this attribute.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. *The standard defines the element <text:s>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.52 Part 3 Section 6.1.4, text:tab

- a. *The standard defines the element <text:tab>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:tab>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <text:tab>, contained within the parent element <text:p>*

This element is supported in Excel 2013 and later.

On load, Excel converts <tab> elements to spaces.

- d. *The standard defines the element <text:tab>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.53 Part 3 Section 6.1.5, text:line-break

- a. *The standard defines the element <text:line-break>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute text:line-break*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:line-break>*

This element is supported in Excel 2013 and later.

On load, Excel reads this attribute. On save, Excel does not write this attribute.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the element <text:line-break>, contained within the parent element <text:p>*

This element is supported in Excel 2013 and later.

On load, Excel converts the <text:line-break> element to a line feed character in the text. On save, if the parent element is <ruby-base> or <span>, Excel converts the combination of line feed and return characters to a <text:line-break> element. If the parent element is <text:p> Excel closes the current <text:p> element, and begins a new <text:p> element.

- e. *The standard defines the element <text:line-break>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.54 Part 3 Section 6.1.7, text:span

- a. *The standard defines the element <text:span>*

This element is supported in Excel 2013 and later.

On load, Excel reads the element <text:span> but does not write it on save.

**OfficeArt Math** in Excel 2013 does not support this element on save, for text in text boxes, shapes, SmartArt, and chart titles and labels. On load it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The text:class-name attribute is always written as empty and is not supported on read.

### 2.1.55 Part 3 Section 6.1.8, text:a

- a. *The standard defines the element <text:a>*

This element is supported in Excel 2013 and later.

On load, Excel reads the element <text:a> but does not write it on save.

### 2.1.56 Part 3 Section 6.1.10, text:number

- a. *The standard defines the attribute text:number, contained within the element <text:h>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the element <text:number>, contained within the parent element <text:list-item>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <text:number>, contained within the parent element <text:list-item>*

**OfficeArt Math** in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- d. *The standard defines the element <text:number>, contained within the parent element <text:list-item>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.57 Part 3 Section 6.2.1.2, text:bookmark

- a. *The standard defines the element <text:bookmark>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:bookmark>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <text:bookmark>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.58 Part 3 Section 6.2.1.3, text:bookmark-start**

- a. *The standard defines the element <text:bookmark-start>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:bookmark-start>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <text:bookmark-start>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.59 Part 3 Section 6.2.1.4, text:bookmark-end

- a. *The standard defines the element <text:bookmark-end>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:bookmark-end>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <text:bookmark-end>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.60 Part 3 Section 6.2.2.2, text:reference-mark

- a. *The standard defines the element <text:reference-mark>*

This element is supported in Word 2013 and later.

On load, Word converts reference marks to bookmarks.



**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <text:reference-mark>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes, shapes, SmartArt, chart titles and labels, On load, it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. *The standard defines the element <text:reference-mark>*

This element is not supported in PowerPoint 2013 or later.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.61 Part 3 Section 6.2.2.3, text:reference-mark-start**

a. *The standard defines the element <text:reference-mark-start>*

This element is supported in Word 2013 and later.

On load, Word converts reference marks to bookmarks.

b. *The standard defines the element <text:reference-mark-start>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.62 Part 3 Section 6.2.2.4, text:reference-mark-end**

a. *The standard defines the element <text:reference-mark-end>*

This element is supported in Word 2013 and later.

On load, Word converts reference marks to bookmarks.

- b. *The standard defines the element <text:reference-mark-end>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.63 Part 3 Section 6.3.2, text:note**

- a. *The standard defines the element <text:note>*

This element is supported in Word 2013 and later.

On load, footnotes are dropped from headers, footers, textboxes, ,and annotations.

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:note>, contained within the parent element <draw:frame>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <text:note>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the element <text:note>*

This element is not supported in PowerPoint 2013 or later.

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.64 Part 3 Section 6.3.3, text:note-citation

- a. *The standard defines the element <text:note-citation>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:note-citation>, contained within the parent element <text:note>*

This element is supported in Word 2013 and later.

Word always reads the contents of the element instead of the text:label attribute.

- c. *The standard defines the element <text:note-citation>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the element <text:note-citation>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### 2.1.65 Part 3 Section 6.3.4, text:note-body

- a. *The standard defines the element <text:note-body>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:note-body>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. *The standard defines the element <text:note-body>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.66 Part 3 Section 6.4, text:ruby**

a. *The standard defines the element <text:ruby>*

This element is supported in Excel 2013 and later.

On load, Excel reads the element <text:ruby> but does not write it on save.

b. *The standard defines the element <text:ruby>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.67 Part 3 Section 6.4.3, text:ruby-text**

a. *The standard defines the element <text:ruby-text>*

This element is not supported in Excel 2013 or later.

### **2.1.68 Part 3 Section 7.3.5, text:page-continuation**

a. *The standard defines the element <text:page-continuation>*

This element is not supported in Word 2013 or later.

b. *The standard defines the element <text:page-continuation>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:page-continuation>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.69 Part 3 Section 7.3.6.2, text:sender-firstname**

- a. *The standard defines the element <text:sender-firstname>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-firstname>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.70 Part 3 Section 7.3.6.3, text:sender-lastname**

- a. *The standard defines the element <text:sender-lastname>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-lastname>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.71 Part 3 Section 7.3.6.4, text:sender-initials**

- a. *The standard defines the element <text:sender-initials>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-initials>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.72 Part 3 Section 7.3.6.5, text:sender-title**

- a. *The standard defines the element <text:sender-title>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-title>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.73 Part 3 Section 7.3.6.6, text:sender-position**

- a. *The standard defines the element <text:sender-position>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-position>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.74 Part 3 Section 7.3.6.7, text:sender-email**

- a. *The standard defines the element <text:sender-email>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-email>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.75 Part 3 Section 7.3.6.8, text:sender-phone-private**

- a. *The standard defines the element <text:sender-phone-private>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-phone-private>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.76 Part 3 Section 7.3.6.9, text:sender-fax**

- a. *The standard defines the element <text:sender-fax>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-fax>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.77 Part 3 Section 7.3.6.10, text:sender-company**

- a. *The standard defines the element <text:sender-company>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-company>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.78 Part 3 Section 7.3.6.11, text:sender-phone-work**

- a. *The standard defines the element <text:sender-phone-work>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-phone-work>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.79 Part 3 Section 7.3.6.12, text:sender-street**

- a. *The standard defines the element <text:sender-street>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-street>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.80 Part 3 Section 7.3.6.13, text:sender-city**

- a. *The standard defines the element <text:sender-city>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-city>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.81 Part 3 Section 7.3.6.14, text:sender-postal-code**

- a. *The standard defines the element <text:sender-postal-code>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-postal-code>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.82 Part 3 Section 7.3.6.15, text:sender-country**

- a. *The standard defines the element <text:sender-country>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-country>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.83 Part 3 Section 7.3.6.16, text:sender-state-or-province**

- a. *The standard defines the element <text:sender-state-or-province>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sender-state-or-province>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.84 Part 3 Section 7.3.7.1, text:author-name**

- a. *The standard defines the element <text:author-name>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.85 Part 3 Section 7.3.7.2, text:author-initials**

- a. *The standard defines the element <text:author-initials>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.86 Part 3 Section 7.3.8, text:chapter**

- a. *The standard defines the element <text:chapter>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:chapter>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.87 Part 3 Section 7.3.9, text:file-name**

- a. *The standard defines the element <text:file-name>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.88 Part 3 Section 7.3.10, text:template-name**

- a. *The standard defines the element <text:template-name>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.89 Part 3 Section 7.3.11, text:sheet-name**

- a. *The standard defines the element <text:sheet-name>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sheet-name>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.90 Part 3 Section 7.4.2, text:variable-decls**

- a. *The standard defines the element <text:variable-decls>*

This element is not supported in Word 2013 or later.

#### **2.1.91 Part 3 Section 7.4.3, text:variable-decl**

- a. *The standard defines the element <text:variable-decl>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:variable-decl>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.92 Part 3 Section 7.4.4, text:variable-set**

- a. *The standard defines the element <text:variable-set>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:variable-set>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.93 Part 3 Section 7.4.5, text:variable-get**

- a. *The standard defines the element <text:variable-get>*

This element is not supported in Word 2013 or later.



- b. *The standard defines the element <text:variable-get>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.94 Part 3 Section 7.4.6, text:variable-input**

- a. *The standard defines the element <text:variable-input>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:variable-input>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.95 Part 3 Section 7.4.7, text:user-field-decls**

- a. *The standard defines the element <text:user-field-decls>*

This element is not supported in Word 2013 or later.

#### **2.1.96 Part 3 Section 7.4.8, text:user-field-decl**

- a. *The standard defines the element <text:user-field-decl>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-field-decl>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.97 Part 3 Section 7.4.9, text:user-field-get**

- a. *The standard defines the element <text:user-field-get>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-field-get>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.98 Part 3 Section 7.4.10, text:user-field-input**

- a. *The standard defines the element <text:user-field-input>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-field-input>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.99 Part 3 Section 7.4.11, text:sequence-decls**

- a. *The standard defines the element <text:sequence-decls>*

This element is not supported in Word 2013 or later.

### **2.1.100 Part 3 Section 7.4.12, text:sequence-decl**

- a. *The standard defines the element <text:sequence-decl>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sequence-decl>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.101 Part 3 Section 7.4.13, text:sequence**

- a. *The standard defines the element <text:sequence>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:sequence>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.102 Part 3 Section 7.4.14, text:expression**

- a. *The standard defines the element <text:expression>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:expression>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.103 Part 3 Section 7.4.15, text:text-input**

- a. *The standard defines the element <text:text-input>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.104 Part 3 Section 7.4.16, text:drop-down**

- a. *The standard defines the element <text:drop-down>*

This element is supported in Word 2021 and later.

### **2.1.105 Part 3 Section 7.4.17, text:label**

- a. *The standard defines the element <text:label>*

This element is supported in Word 2021 and later.

### **2.1.106 Part 3 Section 7.5.2, text:initial-creator**

- a. *The standard defines the element <text:initial-creator>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.107 Part 3 Section 7.5.3, text:creation-date**

- a. *The standard defines the element <text:creation-date>*

This element is supported in Word 2013 and later.

On load, Word always assumes that the <text:creation-date> element in the meta.xml is written in UTC (Coordinated Universal Time). On save, Word always saves the <text:creation-date> in the meta.xml as UTC by using the "Z" suffix in the time stamp.

- b. *The standard defines the element <text:creation-date>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.108 Part 3 Section 7.5.4, text:creation-time**

- a. *The standard defines the element <text:creation-time>*

This element is supported in Word 2013 and later.

On load, Word always assumes that the <text:creation-date> element in the meta.xml is written in UTC (Coordinated Universal Time). On save, Word always saves the <text:creation-date> in the meta.xml as UTC by using the "Z" suffix in the time stamp.

On load, Word converts <text:creation-time> elements to <text:creation-date> elements.

- b. *The standard defines the element <text:creation-time>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.109 Part 3 Section 7.5.5, text:description**

- a. *The standard defines the attribute text:description*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:description*

This attribute is not supported in PowerPoint 2013 or later.

- c. *The standard defines the element <text:description>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.110 Part 3 Section 7.5.6, text:user-defined**

- a. *The standard defines the element <text:user-defined>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-defined>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.111 Part 3 Section 7.5.7, text:print-time**

- a. *The standard defines the element <text:print-time>*

This element is supported in Word 2013 and later.

On load, Word converts <text:print-time> elements to <text:print-date> elements.

- b. *The standard defines the element <text:print-time>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.112 Part 3 Section 7.5.8, text:print-date**

- a. *The standard defines the element <text:print-date>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.113 Part 3 Section 7.5.9, text:printed-by**

- a. *The standard defines the element <text:printed-by>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:printed-by>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.114 Part 3 Section 7.5.10, text:title**

- a. *The standard defines the element <text:title>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.115 Part 3 Section 7.5.11, text:subject**

- a. *The standard defines the element <text:subject>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.116 Part 3 Section 7.5.12, text:keywords**

- a. *The standard defines the element <text:keywords>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.117 Part 3 Section 7.5.13, text:editing-cycles**

- a. *The standard defines the element <text:editing-cycles>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.118 Part 3 Section 7.5.14, text:editing-duration**

- a. *The standard defines the element <text:editing-duration>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.119 Part 3 Section 7.5.15, text:modification-time**

- a. *The standard defines the element <text:modification-time>*

This element is supported in Word 2013 and later.

On load, Word converts <text:modification-time> elements to <text:modification-date> elements.

- b. *The standard defines the element <text:modification-time>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.120 Part 3 Section 7.5.16, text:modification-date**

- a. *The standard defines the element <text:modification-date>*

This element is supported in Word 2013 and later.

On load, Word always assumes that the <text:modification-date> element in the meta.xml is written in UTC (Coordinated Universal Time). On save, Word always saves the <dc:date> in the meta.xml as UTC by using the "Z" suffix in the time stamp.

- b. *The standard defines the element <text:modification-date>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.121 Part 3 Section 7.5.17, text:creator**

- a. *The standard defines the element <text:creator>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.122 Part 3 Section 7.5.18.2, text:page-count**

- a. *The standard defines the element <text:page-count>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.123 Part 3 Section 7.5.18.3, text:paragraph-count**

- a. *The standard defines the attribute text:paragraph-count*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the element <text:paragraph-count>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.124 Part 3 Section 7.5.18.4, text:word-count**

- a. *The standard defines the attribute text:word-count*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the element <text:word-count>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.125 Part 3 Section 7.5.18.5, text:character-count**

- a. *The standard defines the attribute text:character-count*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the element <text:character-count>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.126 Part 3 Section 7.5.18.6, text:table-count**

- a. *The standard defines the element <text:table-count>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the attribute text:table-count*  
This attribute is not supported in Excel 2013 or later.
- c. *The standard defines the element <text:table-count>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.127 Part 3 Section 7.5.18.7, text:image-count**

- a. *The standard defines the element <text:image-count>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the attribute text:image-count*  
This attribute is not supported in Excel 2013 or later.
- c. *The standard defines the element <text:image-count>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.128 Part 3 Section 7.5.18.8, text:object-count**

- a. *The standard defines the element <text:object-count>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the attribute text:object-count*  
This attribute is not supported in Excel 2013 or later.
- c. *The standard defines the element <text:object-count>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.129 Part 3 Section 7.6.2, form:connection-resource**

- a. *The standard defines the element <form:connection-resource>*  
This element is supported in Word 2013 and later.

This implementer note references the following standards:

[\[ISO/IEC29500-1:2016\]](https://www.iso.org/standard/71691.html) ISO/IEC, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 1: Fundamentals and Markup Language Reference", ISO/IEC 29500-1:2016, <https://www.iso.org/standard/71691.html>.

[\[RFC3986\]](http://www.ietf.org/rfc/rfc3986.txt) Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", January 2005, <http://www.ietf.org/rfc/rfc3986.txt>.

Word can support only one database connection per document. On load Word uses the first <form:connection-resource> element in the document as the database connection for the entire document.

On save Word constructs a string that is the value for the xlink:href attribute for the form:connection-resource element from elements as specified in [ISO/IEC29500-1:2016] part 1, section 17.14. The string is comprised of four different parts.

The last three parts of the string contain the properties required by Word to complete a mail merge connection. Each property is represented by a key/value pair that is linked by an equals sign ("="). Multiple properties are separated by an ampersand (denoted as "&").

#### Part 1

The first part contains the complete path of the data source, as specified in [RFC3986]. This portion of the string is terminated by a number sign ("#"). The path comes directly from the dataType key as described in part 2 in this section. If the dataType key is empty, then the path will be empty also, and the xlink:href attribute's value starts from "#".

#### Part 2

The second part of the string contains keys as specified in mainDocumentType Key. The description for each of these keys matches that of an element in [ISO/IEC29500-1:2016]. The relevant section of the specification is identified with the name of the key and its section number.

##### mainDocumentType Key

The definition of the mainDocumentType key is specified in section 17.14.22. The enumerations specified are represented by the following values in this key:

- "0" represents formLetters
- "1" represents mailingLabels
- "2" represents envelopes
- "3" represents catalog
- "4" represents email
- "5" represents fax

##### linktoQuery Key

The definition of the linktoQuery key is described in section 17.14.18. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

##### dataType Key

The definition of the dataType key is described in section 17.14.22. The enumerations described in the specification are represented by the following values in this key:

- "0" represents textFile
- "1" represents database
- "2" represents spreadsheet
- "3" represents query
- "4" represents odbc
- "5" represents native

##### connectString Key

The definition and possible values for the connectString key are described in section 17.14.8.

##### query Key

The definition and possible values for the query key are described in section 17.14.26.

#### dataSource Key

The definition and possible values for the dataSource key are described in section 17.14.9.

#### headerSource Key

The definition and possible values for the headerSource key are described in section 17.14.16.

#### doNotSuppressBlankLines Key

The definition of the doNotSuppressBlankLines key is described in section 17.14.12. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

#### destination Key

The definition of the destination key is described in section 17.14.19. The enumerations described in the specification are represented by the following values in this key:

- "0" represents newDocument
- "1" represents printer
- "2" represents email
- "3" represents fax

#### addressFieldName Key

The definition and possible values for the addressFieldName key are described in section 17.14.3.

#### mailSubject Key

The definition and possible values for the mailSubject key are described in section 17.14.21.

#### mailAsAttachment Key

The definition of the mailAsAttachment key is described in section 17.14.19. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

#### viewMergedData Key

The definition of the viewMergedData key is described in section 17.14.36. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

#### activeRecord Key

The definition and possible values for the activeRecord key are described in section 17.14.2.

#### checkErrors Key

The definition and possible values for the checkErrors key are described in section 17.14.4.

#### odsoUd Key

The definition and possible values for the odsoUd key are described in section 17.14.34. Word only writes this key if the dataType key is the "native" value.



#### odsoTable Key

The definition and possible values for the odsoTable key are described in section 17.14.31. Word only writes this key if the dataType key is the "native" value.

#### odsoSrc Key

The definition and possible values for the odsoSrc key are described in section 17.14.30. Word only writes this key if the dataType key is the "native" value.

#### odsoColDelim Key

The definition and possible values for the odsoColDelim key are described in section 17.14.5. Word only writes this key if the dataType key is the "native" value.

#### odsoType Key

The definition and possible values for the odsoType key are described in section 17.14.32. Word only writes this key if the dataType key is the "native" value.

#### odsoFHdr Key

The definition and possible values for the odsoFHdr key are described in section 17.14.14. Word only writes this key if the dataType key is the "native" value.

#### Part 3

The third part of the string is used to describe the properties of each column in the data source. The properties for a given column follow the same key/value syntax as described previously in part 2. Section numbers refer to [ISO/IEC29500-1:2016].

#### fieldMapType Key

The definition of the fieldMapType key is described in section 17.14.33. The enumerations described in the specification are represented by the following values in this key:

- "0" represents null
- "1" represents dbColumn
- "2" represents addressBlock
- "3" represents salutation
- "4" represents mapped
- "5" represents barcode

#### fieldMapName Key

The definition and possible values for the fieldMapName key are described in section 17.14.24.

#### fieldMapMappedName Key

The definition and possible values for the fieldMapMappedName key are described in section 17.14.23.

#### fieldMapColumn Key

The definition and possible values for the fieldMapColumn key are described in section 17.14.6.

#### fieldMapDynamicAddress Key

The definition and possible values for the fieldMapDynamicAddress key are described in section 17.14.13.

#### fieldMapLid Key

The definition and possible values for the fieldMapLid key are described in section 17.14.17.

#### fieldMapDataEnd Key

The fieldMapDataEnd key specifies that there is no more information for a single column. The value of the key is a one-based index of the column within a given external data source.

#### Part 4

The last part of the string is used to describe the properties of each recipient in the mail merge. The properties for a given recipient follow the same key/value syntax as described previously in part 2. Section numbers refer to [ISO/IEC29500-1:2016].

#### recipientActive Key

The definition and possible values for the recipientActive key are described in section 17.14.28.

#### recipientHash Key

The definition and possible values for the recipientHash key are described in section 17.14.27.

#### recipientColumn Key

The definition and possible values for the recipientColumn key are described in section 17.14.6.

#### recipientUniqueTag Key

The definition and possible values for the recipientUniqueTag key are described in section 17.14.7.

#### recipientDataEnd Key

The recipientDataEnd key specifies that there is no more information for a single recipient. The value of the key is a one-based index value, which is used to look up the appropriate recipient in the data source.

The following example shows a connection string saved by Word to connect to the data source that is being used by the mail merge:

```
<text:database-display text:table-name="Sheet1$" text:table-type="table" text:column-name="Title"><form:connection-resource  
xlink:href="file:///\\word\public\user\sample%20mail%20merge%20data%20sources\Word%20C  
reate%20Date.xls#mainDocumentType=0&linkToQuery=1&dataType=5&connectS  
tring=Provider%3DMicrosoft.ACE.OLEDB.12.0;User%20ID%3DAdmin;Data%20Source%3D\\word  
\public\user\sample%20mail%20merge%20data%20sources\Word%20Create%20Date.xls;Mode  
%3DRead;Extended%20Properties%3D%22HDR%3DYES;IMEX%3D1;%22;Jet%20OLEDB:System  
%20database%3D%22%22;Jet%20OLEDB:Registry%20Path%3D%22%22;Jet%20OLEDB:Engine  
%20Type%3D35;Jet%20OLEDB:Database%20Locking%20Mode%3D0;Jet%20OLEDB:Global%20P  
artial%20Bulk%20Ops%3D2;Jet%20OLEDB:Global%20Bulk%20Transactions%3D1;Jet%20OLEDB  
:New%20Database%20Password%3D%22%22;Jet%20OLEDB:Create%20System%20Database%  
3DFalse;Jet%20OLEDB:Encrypt%20Database%3DFalse;Jet%20OLEDB:Don't%20Copy%20Locale  
%20on%20Compact%3DFalse;Jet%20OLEDB:Compact%20Without%20Replica%20Repair%3DFal  
se;Jet%20OLEDB:SFP%3DFalse;Jet%20OLEDB:Support%20Complex%20Data%3DFalse&que  
ry=SELECT%20*%20FROM%20%60Sheet1$%60%20&dataSource=\\word\public\user\samp  
le%20mail%20merge%20data%20sources\Word%20Create%20Date.xls&activeRecord=4&a  
mp;odsoUdl=Provider%3DMicrosoft.ACE.OLEDB.12.0;User%20ID%3DAdmin;Data%20Source%3D  
\\word\public\user\sample%20mail%20merge%20data%20sources\Word%20Create%20Date.xls;  
Mode%3DRead;Extended%20Properties%3D%22HDR%3DYES;IMEX%3D1;%22;Jet%20OLEDB:S  
ystem%20database%3D%22%22;Jet%20OLEDB:Registry%20Path%3D%22%22;Jet%20OLEDB:E  
ngine%20Type%3D35;Jet%20OLEDB:Database%20Locking%20Mode%3D0;Jet%20OLEDB:Global  
%20Partial%20Bulk%20Ops%3D2;Jet%20OLEDB:Global%20Bulk%20Transactions%3D1;Jet%20  
OLEDB:New%20Database%20Password%3D%22%22;Jet%20OLEDB:Create%20System%20Data
```

base%3DFalse;Jet%20OLEDB:Encrypt%20Database%3DFalse;Jet%20OLEDB:Don't%20Copy%20Locale%20on%20Compact%3DFalse;Jet%20OLEDB:Compact%20Without%20Replica%20Repair%3DFalse;Jet%20OLEDB:SFP%3DFalse;Jet%20OLEDB:Support%20Complex%20Data%3DFalse&amp;odsoTable=Sheet1&odsoSrc=\\word\public\user\sample%20mail%20merge%20data%20sources\Word%20Create%20Date.xls&odsoColDelim=9&odsoType=1&odsoFHdr=1&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=1&fieldMapType=1&fieldMapName=Title&fieldMapMappedName=Courtesy%20Title&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=2&fieldMapType=1&fieldMapName=First%20Name&fieldMapMappedName=First%20Name&fieldMapColumn=1&fieldMapLid=1033&fieldMapDataEnd=3&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=4&fieldMapType=1&fieldMapName=Last%20Name&fieldMapMappedName=Last%20Name&fieldMapColumn=2&fieldMapLid=1033&fieldMapDataEnd=5&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=6&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=7&fieldMapType=1&fieldMapName=Company%20Name&fieldMapMappedName=Company&fieldMapColumn=3&fieldMapLid=1033&fieldMapDataEnd=9&fieldMapType=1&fieldMapName=Address%20Line%201&fieldMapMappedName=Address%201&fieldMapColumn=4&fieldMapLid=1033&fieldMapDataEnd=10&fieldMapType=1&fieldMapName=Address%20Line%202&fieldMapMappedName=Address%202&fieldMapColumn=5&fieldMapLid=1033&fieldMapDataEnd=11&fieldMapType=1&fieldMapName=City&fieldMapMappedName=City&fieldMapColumn=6&fieldMapLid=1033&fieldMapDataEnd=12&fieldMapType=1&fieldMapName=State&fieldMapMappedName=State&fieldMapColumn=7&fieldMapLid=1033&fieldMapDataEnd=13&fieldMapType=1&fieldMapName=ZIP%20Code&fieldMapMappedName=Postal%20Code&fieldMapColumn=8&fieldMapLid=1033&fieldMapDataEnd=14&fieldMapType=1&fieldMapName=Country&fieldMapMappedName=Country%20or%20Region&fieldMapColumn=9&fieldMapLid=1033&fieldMapDataEnd=15&fieldMapType=1&fieldMapName=Work%20Phone&fieldMapMappedName=Business%20Phone&fieldMapColumn=11&fieldMapLid=1033&fieldMapDataEnd=16&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=17&fieldMapType=1&fieldMapName=Home%20Phone&fieldMapMappedName=Home%20Phone&fieldMapColumn=10&fieldMapLid=1033&fieldMapDataEnd=18&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=19&fieldMapType=1&fieldMapName=E-mail%20Address&fieldMapMappedName=E-mail%20Address&fieldMapColumn=12&fieldMapLid=1033&fieldMapDataEnd=20&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=21&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=22&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=23&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=24&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=25&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=26&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=27&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=28&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=29&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=30&recipientActive=1&recipientHash=-1949734214&recipientDataEnd=1&recipientActive=1&recipientHash=870254691&recipientDataEnd=2&recipientActive=0&recipientHash=-1107777181&recipientDataEnd=3&recipientActive=1&recipientHash=-1973497891&recipientDataEnd=4&recipientActive=0&recipientHash=2014681738&recipientDataEnd=5&recipientActive=1&recipientHash=571221072&recipientDataEnd=6&recipientActive=1&recipientHash=0&recipientDataEnd=7"/><Title></text:database-display>

b. *The standard defines the element <form:connection-resource>*

This element is not supported in Excel 2013 or later.

**2.1.130 Part 3 Section 7.6.3, text:database-display**

- a. *The standard defines the element <text:database-display>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

**2.1.131 Part 3 Section 7.6.4, text:database-next**

- a. *The standard defines the element <text:database-next>*

This element is not supported in Word 2013 or later.

**2.1.132 Part 3 Section 7.6.5, text:database-row-select**

- a. *The standard defines the element <text:database-row-select>*

This element is not supported in Word 2013 or later.

**2.1.133 Part 3 Section 7.6.6, text:database-row-number**

- a. *The standard defines the element <text:database-row-number>*

This element is not supported in Word 2013 or later.

**2.1.134 Part 3 Section 7.6.7, text:database-name**

- a. *The standard defines the element <text:database-name>*

This element is not supported in Word 2013 or later.

**2.1.135 Part 3 Section 7.7.1.2, text:page-variable-set**

- a. *The standard defines the element <text:page-variable-set>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:page-variable-set>*

This element is not supported in PowerPoint 2013 or later.

**2.1.136 Part 3 Section 7.7.1.3, text:page-variable-get**

- a. *The standard defines the element <text:page-variable-get>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

**2.1.137 Part 3 Section 7.7.2, text:placeholder**

- a. *The standard defines the element <text:placeholder>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:placeholder>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.138 Part 3 Section 7.7.3, text:conditional-text**

- a. *The standard defines the element <text:conditional-text>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <text:conditional-text>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.139 Part 3 Section 7.7.4, text:hidden-text**

- a. *The standard defines the element <text:hidden-text>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <text:hidden-text>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.140 Part 3 Section 7.7.5, text:reference-ref**

- a. *The standard defines the element <text:reference-ref>*  
This element is supported in Word 2013 and later.  
On load, Word converts the element <text:reference-ref> to <text:bookmark-ref>.  
On save, the hyperlink to the object being referenced is lost.
- b. *The standard defines the element <text:reference-ref>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.141 Part 3 Section 7.7.6, text:bookmark-ref**

- a. *The standard defines the element <text:bookmark-ref>*  
This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.142 Part 3 Section 7.7.7, text:note-ref**

- a. *The standard defines the element <text:note-ref>*  
This element is not supported in Word 2013 or later.  
On load, Word ignores footnote references. On save, Word writes out footnote references.
- b. *The standard defines the element <text:note-ref>*  
This element is not supported in PowerPoint 2013 or later.

### **2.1.143 Part 3 Section 7.7.8, text:sequence-ref**

- a. *The standard defines the element <text:sequence-ref>*  
This element is not supported in Word 2013 or later.

### **2.1.144 Part 3 Section 7.7.9, text:script**

- a. *The standard defines the element <text:script>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:script>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.145 Part 3 Section 7.7.10, text:execute-macro**

- a. *The standard defines the element <text:execute-macro>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:execute-macro>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.146 Part 3 Section 7.7.11, text:hidden-paragraph**

- a. *The standard defines the element <text:hidden-paragraph>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:hidden-paragraph>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.147 Part 3 Section 7.7.12, text:dde-connection**

- a. *The standard defines the element <text:dde-connection>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:dde-connection>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.148 Part 3 Section 7.7.13, text:measure**

- a. *The standard defines the element <text:measure>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:measure>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.149 Part 3 Section 7.7.14, text:table-formula**

- a. *The standard defines the element <text:table-formula>*

This element is not supported in Word 2013 or later.

*This element was deprecated in the ODF 1.2 standard.*

- b. *The standard defines the element <text:table-formula>*

This element is not supported in PowerPoint 2013 or later.

*This element was deprecated in the ODF 1.2 standard.*

#### **2.1.150 Part 3 Section 8.1.2, text:toc-mark-start**

- a. *The standard defines the element <text:toc-mark-start>*

This element is supported in Word 2013 and later.

On load, Word collapses the range encapsulated by a <text:toc-mark-start> element and a <text:toc-mark-end> element to a single <text:toc-mark> element.

- b. *The standard defines the element <text:toc-mark-start>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.151 Part 3 Section 8.1.3, text:toc-mark-end**

- a. *The standard defines the element <text:toc-mark-end>*

This element is supported in Word 2013 and later.

On load, Word collapses the range encapsulated by a <text:toc-mark-start> element and a <text:toc-mark-end> element to a single <text:toc-mark> element.

- b. *The standard defines the element <text:toc-mark-end>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.152 Part 3 Section 8.1.4, text:toc-mark**

- a. *The standard defines the element <text:toc-mark>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.153 Part 3 Section 8.1.5, text:user-index-mark-start**

- a. *The standard defines the element <text:user-index-mark-start>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-index-mark-start>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.154 Part 3 Section 8.1.6, text:user-index-mark-end**

- a. *The standard defines the element <text:user-index-mark-end>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-index-mark-end>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.155 Part 3 Section 8.1.7, text:user-index-mark**

- a. *The standard defines the element <text:user-index-mark>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-index-mark>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.156 Part 3 Section 8.1.8, text:alphabetical-index-mark-start**

- a. *The standard defines the element <text:alphabetical-index-mark-start>*

This element is supported in Word 2013 and later.

On load, Word collapses the range encapsulated by a <text:alphabetical-index-mark-start> element and <text:alphabetical-index-mark-end> element to a single <text:alphabetical-index-mark> element.

- b. *The standard defines the element <text:alphabetical-index-mark-start>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.157 Part 3 Section 8.1.9, text:alphabetical-index-mark-end**

- a. *The standard defines the element <text:alphabetical-index-mark-end>*

This element is supported in Word 2013 and later.

On load, Word collapses the range encapsulated by a <text:alphabetical-index-mark-start> element and <text:alphabetical-index-mark-end> element to a single <text:alphabetical-index-mark> element.

- b. *The standard defines the element <text:alphabetical-index-mark-end>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.158 Part 3 Section 8.1.10, text:alphabetical-index-mark**

- a. *The standard defines the element <text:alphabetical-index-mark>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.159 Part 3 Section 8.1.11, text:bibliography-mark**

- a. *The standard defines the element <text:bibliography-mark>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:bibliography-mark>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.160 Part 3 Section 8.2.2, text:index-body**

- a. *The standard defines the element <text:index-body>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.



### **2.1.161 Part 3 Section 8.2.3, text:index-title**

- a. *The standard defines the element <text:index-title>, contained within the parent element <text:index-body>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:index-title>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:index-title>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.162 Part 3 Section 8.3, text:table-of-content**

- a. *The standard defines the element <text:table-of-content>*

This element is not supported in Excel 2013 or later.

- b. *The standard defines the element <text:table-of-content>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.163 Part 3 Section 8.3.3, text:table-of-content-entry-template**

- a. *The standard defines the element <text:table-of-content-entry-template>*

This element is not supported in Word 2013 or later.

On load, Word ignores the table of contents style and uses a default table of contents style.

On save, Word writes out the style of the table of contents.

### **2.1.164 Part 3 Section 8.4, text:illustration-index**

- a. *The standard defines the element <text:illustration-index>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:illustration-index>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:illustration-index>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.165 Part 3 Section 8.4.2, text:illustration-index-source**

- a. *The standard defines the element <text:illustration-index-source>*

This element is not supported in Word 2013 or later.

### **2.1.166 Part 3 Section 8.4.3, text:illustration-index-entry-template**

- a. *The standard defines the element <text:illustration-index-entry-template>*

This element is not supported in Word 2013 or later.

**2.1.167 Part 3 Section 8.5, text:table-index**

- a. *The standard defines the element <text:table-index>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:table-index>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:table-index>*

This element is not supported in PowerPoint 2013 or later.

**2.1.168 Part 3 Section 8.5.2, text:table-index-source**

- a. *The standard defines the element <text:table-index-source>*

This element is not supported in Word 2013 or later.

**2.1.169 Part 3 Section 8.5.3, text:table-index-entry-template**

- a. *The standard defines the element <text:table-index-entry-template>*

This element is not supported in Word 2013 or later.

**2.1.170 Part 3 Section 8.6, text:object-index**

- a. *The standard defines the element <text:object-index>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:object-index>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:object-index>*

This element is not supported in PowerPoint 2013 or later.

**2.1.171 Part 3 Section 8.6.2, text:object-index-source**

- a. *The standard defines the element <text:object-index-source>*

This element is not supported in Word 2013 or later.

**2.1.172 Part 3 Section 8.6.3, text:object-index-entry-template**

- a. *The standard defines the element <text:object-index-entry-template>*

This element is not supported in Word 2013 or later.

**2.1.173 Part 3 Section 8.7, text:user-index**

- a. *The standard defines the element <text:user-index>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:user-index>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:user-index>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.174 Part 3 Section 8.7.2, text:user-index-source**

- a. *The standard defines the element <text:user-index-source>*

This element is not supported in Word 2013 or later.

#### **2.1.175 Part 3 Section 8.7.3, text:user-index-entry-template**

- a. *The standard defines the element <text:user-index-entry-template>*

This element is not supported in Word 2013 or later.

#### **2.1.176 Part 3 Section 8.8, text:alphabetical-index**

- a. *The standard defines the element <text:alphabetical-index>*

This element is not supported in Excel 2013 or later.

- b. *The standard defines the element <text:alphabetical-index>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.177 Part 3 Section 8.8.3, text:alphabetical-index-auto-mark-file**

- a. *The standard defines the element <text:alphabetical-index-auto-mark-file>*

This element is not supported in Word 2013 or later.

#### **2.1.178 Part 3 Section 8.8.4, text:alphabetical-index-entry-template**

- a. *The standard defines the element <text:alphabetical-index-entry-template>*

This element is not supported in Word 2013 or later.

#### **2.1.179 Part 3 Section 8.9, text:bibliography**

- a. *The standard defines the element <text:bibliography>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:bibliography>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:bibliography>*

**2.1.180 Part 3 Section 8.9.2, text:bibliography-source**

- a. *The standard defines the element <text:bibliography-source>*

This element is not supported in Word 2013 or later.

**2.1.181 Part 3 Section 8.9.3, text:bibliography-entry-template**

- a. *The standard defines the element <text:bibliography-entry-template>*

This element is not supported in Word 2013 or later.

**2.1.182 Part 3 Section 8.10, text:index-source-styles**

- a. *The standard defines the element <text:index-source-styles>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

**2.1.183 Part 3 Section 8.12, text:index-title-template**

- a. *The standard defines the element <text:index-title-template>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:index-title-template>*

This element is not supported in PowerPoint 2013 or later.

**2.1.184 Part 3 Section 8.13.1, text:index-entry-chapter**

- a. *The standard defines the element <text:index-entry-chapter>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:index-entry-chapter>*

This element is not supported in PowerPoint 2013 or later.

**2.1.185 Part 3 Section 8.13.2, text:index-entry-text**

- a. *The standard defines the element <text:index-entry-text>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

**2.1.186 Part 3 Section 8.13.3, text:index-entry-page-number**

- a. *The standard defines the element <text:index-entry-page-number>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

**2.1.187 Part 3 Section 8.13.4, text:index-entry-span**

- a. *The standard defines the element <text:index-entry-span>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:index-entry-span>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.188 Part 3 Section 8.13.5, text:index-entry-bibliography**

- a. *The standard defines the element <text:index-entry-bibliography>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:index-entry-bibliography>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.189 Part 3 Section 8.13.6, text:index-entry-tab-stop**

- a. *The standard defines the element <text:index-entry-tab-stop>*

This element is supported in Word 2013 and later.

On load, Word ignores this element and uses a default style to format tables of contents and indexes. On save, Word saves this element for tables of contents, but not for indexes.

- b. *The standard defines the element <text:index-entry-tab-stop>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.190 Part 3 Section 8.13.7, text:index-entry-link-start**

- a. *The standard defines the element <text:index-entry-link-start>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.191 Part 3 Section 8.13.8, text:index-entry-link-end**

- a. *The standard defines the element <text:index-entry-link-end>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.192 Part 3 Section 9.1.2, table:table**

- a. *The standard defines the element <table:table>*

This element is supported in Word 2013 and later.

On save, Word converts floating tables to inline tables.

- b. *The standard defines the element <table:table>, contained within the parent element <draw:text-box>*

This element is supported in Word 2013 and later.

On load, tables in textboxes are supported.

On save, a Word frame becomes an ODF textbox. If the Word frame contains a table, the frame content is saved but the frame itself is lost. If a Word textbox contains a table, then both the textbox contents and the table are saved.

- c. *The standard defines the element <table:table>, contained within the parent element <office:annotation>*

This element is not supported in Word 2013 or later.

On load and save, Word does not support tables inside annotations. Word retains the contents of the table but loses the table structure.

- d. *The standard defines the element <table:table>*

This element is not supported in Excel 2013 or later.

- e. *The standard defines the element <table:table>, contained within the parent element <chart:chart>*
- f. *The standard defines the element <table:table>, contained within the parent element <draw:textbox>*
- g. *The standard defines the element <table:table>, contained within the parent element <office:text>*
- h. *The standard defines the element <table:table>, contained within the parent element <style:footer>*
- i. *The standard defines the element <table:table>, contained within the parent element <style:footer-left>*
- j. *The standard defines the element <table:table>, contained within the parent element <style:header>*
- k. *The standard defines the element <table:table>, contained within the parent element <style:header-left>*
- l. *The standard defines the element <table:table>, contained within the parent element <table:covered-table-cell>*
- m. *The standard defines the element <table:table>, contained within the parent element <table:dde-link>*
- n. *The standard defines the element <table:table>, contained within the parent element <table:table-cell>*
- o. *The standard defines the element <table:table>, contained within the parent element <text:deletion>*
- p. *The standard defines the element <table:table>, contained within the parent element <text:index-body>*
- q. *The standard defines the element <table:table>, contained within the parent element <text:index-title>*
- r. *The standard defines the element <table:table>, contained within the parent element <text:note-body>*
- s. *The standard defines the element <table:table>, contained within the parent element <text:section>*

### **2.1.193 Part 3 Section 9.1.3, table:table-row**

- a. *The standard defines the element <table:table-row>, contained within the parent element <table:table-header-rows>*
- b. *The standard defines the element <table:table-row>, contained within the parent element <table:table-row-group>*

- c. *The standard defines the element <table:table-row>, contained within the parent element <table:table-rows>*

#### **2.1.194 Part 3 Section 9.1.5, table:covered-table-cell**

- a. *The standard defines the element <table:covered-table-cell>*

This element is not supported in Excel 2013 or later.

- b. *The standard defines the element <table:covered-table-cell>*

This element is supported in PowerPoint 2013 and later.

PowerPoint only writes out this element for cells spanning multiple rows/columns but does not read it on file open.

#### **2.1.195 Part 3 Section 9.1.6, table:table-column**

- a. *The standard defines the element <table:table-column>*

This element is supported in Word 2013 and later.

Word does not support more than 63 columns. On load, any columns beyond this limit are dropped, along with their content.

- b. *The standard defines the element <table:table-column>*

This element is supported in Excel 2013 and later.

On load, Excel reads this attribute. On save, Excel does not write this attribute.

- c. *The standard defines the element <table:table-column>*

#### **2.1.196 Part 3 Section 9.1.7, table:table-header-rows**

- a. *The standard defines the element <table:table-header-rows>*

This element is supported in Excel 2013 and later.

On load, Excel reads the element <table:table-header-rows> and treats it as a regular row, but on save, the element <table:table-header-rows> is never written.

#### **2.1.197 Part 3 Section 9.1.8, table:table-rows**

- a. *The standard defines the element <table:table-rows>*

This element is supported in Excel 2013 and later.

On load, Excel reads this element. On save, Excel does not write this element.

- b. *The standard defines the element <table:table-rows>*

This element is supported in PowerPoint 2021 and later.

On load, PowerPoint reads this element. On save, PowerPoint does not write this element.

#### **2.1.198 Part 3 Section 9.1.9, table:table-row-group**

- a. *The standard defines the element <table:table-row-group>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <table:table-row-group>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <table:table-row-group>*

### **2.1.199 Part 3 Section 9.1.10, table:table-column-group**

- a. *The standard defines the element <table:table-column-group>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <table:table-column-group>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <table:table-column-group>*

### **2.1.200 Part 3 Section 9.1.11, table:table-header-columns**

- a. *The standard defines the element <table:table-header-columns>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <table:table-header-columns>*

This element is supported in Excel 2013 and later.

On load, Excel reads this element and treats it as a regular column, but never writes it out on save.

### **2.1.201 Part 3 Section 9.1.12, table:table-columns**

- a. *The standard defines the element <table:table-columns>*

This element is supported in Excel 2013 and later.

On load, Excel reads this element. On save, Excel does not write this element.

- b. *The standard defines the element <table:table-columns>*

This element is supported in PowerPoint 2021 and later.

On load, PowerPoint reads this element. On save, PowerPoint does not write this element.

### **2.1.202 Part 3 Section 9.1.13, table:title**

- a. *The standard defines the element <table:title>*

### **2.1.203 Part 3 Section 9.1.14, table:desc**

- a. *The standard defines the element <table:desc>*

### **2.1.204 Part 3 Section 9.2.6, table:table-source**

- a. *The standard defines the element <table:table-source>*



This element is not supported in Excel 2013 or later.

- b. *The standard defines the element <table:table-source>, contained within the parent element <table:dde-link>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <table:table-source>, contained within the parent element <table:table>*

#### **2.1.205 Part 3 Section 9.2.7, table:scenario**

- a. *The standard defines the element <table:scenario>*

This element is not supported in Excel 2013 or later.

This element is supported in Excel 2013 and later.

Excel stores the scenario name in the table:name attribute of the parent table.

- b. *The standard defines the element <table:scenario>, contained within the parent element <table:dde-link>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <table:scenario>, contained within the parent element <table:table>*

#### **2.1.206 Part 3 Section 9.2.8, table:shapes**

- a. *The standard defines the element <table:shapes>*

This element is not supported in Excel 2013 or later.

- b. *The standard defines the element <table:shapes>, contained within the parent element <table:dde-link>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <table:shapes>, contained within the parent element <table:table>*

#### **2.1.207 Part 3 Section 9.3.1, table:cell-range-source**

- a. *The standard defines the element <table:cell-range-source>*

This element is not supported in Excel 2013 or later.

#### **2.1.208 Part 3 Section 9.3.2, table:detective**

- a. *The standard defines the element <table:detective>*

This element is not supported in Excel 2013 or later.

#### **2.1.209 Part 3 Section 9.3.3, table:operation**

- a. *The standard defines the attribute table:operation, contained within the element <table:detective>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.210 Part 3 Section 9.3.4, table:highlighted-range**

- a. *The standard defines the attribute table:highlighted-range, contained within the element <table:detective>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.211 Part 3 Section 9.4.8, table:error-macro**

- a. *The standard defines the attribute table:error-macro, contained within the element <table:content-validation>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.212 Part 3 Section 9.4.9, table:label-range**

- a. *The standard defines the element <table:label-range>, contained within the parent element <table:label-ranges>*

This element is not supported in Excel 2013 or later.

#### **2.1.213 Part 3 Section 9.4.10, table:label-ranges**

- a. *The standard defines the element <table:label-ranges>*

This element is not supported in Excel 2013 or later.

#### **2.1.214 Part 3 Section 9.4.11, table:named-expressions**

- a. *The standard defines the element <table:named-expressions>, contained within the parent element <table:table>*

#### **2.1.215 Part 3 Section 9.5.3, table:filter-and**

- a. *The standard defines the element <table:filter-and>, contained within the parent element <table:filter>*

This element is supported in Excel 2013 and later.

Some combinations of the elements <filter-and> and <filter-or> are not supported.

#### **2.1.216 Part 3 Section 9.5.4, table:filter-or**

- a. *The standard defines the element <table:filter-or>, contained within the parent element <table:filter>*

This element is supported in Excel 2013 and later.

Some combinations of the elements <filter-and> and <filter-or> are not supported.

#### **2.1.217 Part 3 Section 9.5.6, table:filter-set-item**

- a. *The standard defines the attribute [all attributes], contained within the element <table:filter-set-item>*

This attribute is supported in Word 2013 and later.

#### **2.1.218 Part 3 Section 9.6.6, table:source-service**

- a. *The standard defines the element <table:source-service>, contained within the parent element <table:data-pilot-table>*

This element is not supported in Excel 2013 or later.

#### **2.1.219 Part 3 Section 9.7, table:consolidation**

- a. *The standard defines the element <table:consolidation>*

This element is not supported in Excel 2013 or later.

#### **2.1.220 Part 3 Section 9.8, table:dde-links**

- a. *The standard defines the element <text:dde-links>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.221 Part 3 Section 9.9.2, table:tracked-changes**

- a. *The standard defines the element <table:tracked-changes>*

This element is not supported in Excel 2013 or later.

#### **2.1.222 Part 3 Section 9.9.15, table:target-range-address**

- a. *The standard defines the attribute table:target-range-address, contained within the element <table:filter>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute table:target-range-address, contained within the element <table:sort>, contained within the parent element <table:database-range>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.223 Part 3 Section 10.2.1, style:handout-master**

- a. *The standard defines the element <style:handout-master>*

This element is not supported in Excel 2013 or later.

- b. *The standard defines the element <style:handout-master>*

This element is supported in PowerPoint 2013 and later.

Handouts are saved with 6 slides per page. However, PowerPoint does not read in the handout master style when loading a file as this property is not persisted.

#### **2.1.224 Part 3 Section 10.2.3, draw:layer**

- a. *The standard defines the attribute draw:layer*

Word 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:layer, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute draw:layer*

Excel 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- d. *The standard defines the attribute draw:layer, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute draw:layer*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

f. *The standard defines the element <draw:layer>*

This element is supported in PowerPoint 2013 and later.

This element is used to identify backgrounds inherited by layouts from masters. If a shape on a master-page is identified as a layout and the shape is on a layer that has a name in the form "<master-page-bg>", then these shapes are inherited from the slide master, and will not appear on the slide. Layers are also used to signify hidden/protected shapes. Beyond these uses, PowerPoint does not support a general concept of layers.

### **2.1.225 Part 3 Section 10.3.2, draw:rect**

a. *The standard defines the element <draw:rect>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:rect>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:rect>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.226 Part 3 Section 10.3.3, draw:line**

- a. *The standard defines the element <draw:line>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

- b. *The standard defines the element <draw:line>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:line>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

## **2.1.227 Part 3 Section 10.3.4, draw:polyline**

a. *The standard defines the element <draw:polyline>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:polyline>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:polyline>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.228 Part 3 Section 10.3.5, draw:polygon**

a. *The standard defines the element <draw:polygon>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>



- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:polygon>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:polygon>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.229 Part 3 Section 10.3.6, draw:regular-polygon**

a. *The standard defines the element <draw:regular-polygon>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:regular-polygon>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:regular-polygon>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

## 2.1.230 Part 3 Section 10.3.7, draw:path

### a. *The standard defines the element <draw:path>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

### b. *The standard defines the element <draw:path>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

### c. *The standard defines the element <draw:path>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation element>
- <table:table-cell>

### **2.1.231 Part 3 Section 10.3.8, draw:circle**

a. *The standard defines the element <draw:circle>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:circle>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:circle>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.232 Part 3 Section 10.3.9, draw:ellipse**

- a. *The standard defines the element <draw:ellipse>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

- b. *The standard defines the element <draw:ellipse>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:ellipse>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.233 Part 3 Section 10.3.10, draw:connector**

a. *The standard defines the element <draw:connector>*

This element is supported in Word 2013 and later.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:connector>*

This element is supported in Excel 2013 and later.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:connector>*

This element is supported in PowerPoint 2013 and later.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.234 Part 3 Section 10.3.11, draw:caption**

a. *The standard defines the element <draw:caption>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:caption>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:caption>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.235 Part 3 Section 10.3.12, draw:measure**

a. *The standard defines the element <draw:measure>*

This element is supported in Word 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>



- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:measure>*

This element is supported in Excel 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:measure>*

This element is supported in PowerPoint 2013 and later.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

### **2.1.236 Part 3 Section 10.3.13, draw:control**

a. *The standard defines the element <draw:control>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <draw:control>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <draw:control>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.237 Part 3 Section 10.3.14, draw:page-thumbnail**

- a. *The standard defines the element <draw:page-thumbnail>, contained within the parent element <draw:handout-master>*

This element is supported in PowerPoint 2013 and later.

PowerPoint writes out handout masters using this element, but does not read it in when loading a presentation.

- b. *The standard defines the element <draw:page-thumbnail>, contained within the parent element <draw:page>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.238 Part 3 Section 10.3.15, draw:g**

- a. *The standard defines the element <draw:g>*

This element is supported in Word 2013 and later.

This element is not supported and will be lost when contained within a <text:p> element that is contained within one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

If a group contains only one object, Word loads only the object, and the grouping is lost.

- b. *The standard defines the element <draw:g>*

This element is supported in Excel 2013 and later.

This element is not supported and will be lost when contained within a <text:p> element that is contained within one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

Excel cannot support certain types of objects being grouped together. An OLE object grouped with anything other than another OLE object will cause the group to be split into two groups: one containing the OLE objects and one containing all other objects. If a group contains only one object, Excel loads only the object, and the grouping is lost.

On save, Excel horizontally flips the position of objects in a group located on a right-to-left oriented worksheet.

c. *The standard defines the element <draw:g>*

This element is supported in PowerPoint 2013 and later.

This element is not supported and will be lost when contained within a <text:p> element that is contained within one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>
- <table:table-cell>

If a group contains only one object, then PowerPoint loads only the object, and loses the grouping.

### **2.1.239 Part 3 Section 10.3.16, draw:glue-point**

a. *The standard defines the element <draw:glue-point>*

Word 2013 does not support this element for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:custom-shape>

b. *The standard defines the element <draw:glue-point>*

Excel 2013 does not support this element for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:custom-shape>

c. *The standard defines the element <draw:glue-point>*

PowerPoint 2013 does not support this element for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:custom-shape>

## **2.1.240 Part 3 Section 10.3.17, svg:title**

a. *The standard defines the attribute svg:title*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

b. *The standard defines the attribute svg:title*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

c. *The standard defines the attribute `svg:title`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

d. *The standard defines the attribute `svg:title`, contained within the element `<draw:layer>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.241 Part 3 Section 10.3.18, `svg:desc`**

a. *The standard defines the attribute `svg:desc`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- b. *The standard defines the attribute `svg:desc`*

Excel 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `svg:desc`*

PowerPoint 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:custom-shape>`

- d. *The standard defines the attribute `svg:desc`, contained within the element `<draw:layer>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.242 Part 3 Section 10.3.19, `office:event-listeners`**

- a. *The standard defines the element `<office:event-listeners>`*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element `<office:event-listeners>`*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `office:event-listeners`, contained within the element `<text:a>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.243 Part 3 Section 10.4.2, `draw:frame`**

- a. *The standard defines the element `<draw:frame>`*

This element is supported in Word 2013 and later.

Word frames become textboxes after save.

This element is supported in Word 2013 and later.

This element is not supported and will be lost when located inside a <text:p> element in an <office:annotation> element.

b. *The standard defines the element <draw:frame>*

This element is supported in Excel 2013 and later.

This element is not supported, and will be lost, when contained within a <text:p>, when that <text:p> is within an <office:annotation>.

c. *The standard defines the element <draw:frame>*

This element is supported in PowerPoint 2013 and later.

This element is not supported when located inside a <text:p> element in an <office:annotation> element, and will be lost.

d. *The standard defines the element <draw:frame>, contained within the parent element <draw:a>*

This element is not supported in PowerPoint 2013 or later.

PowerPoint creates hyperlinks on shapes using the event-listener mechanism. PowerPoint does not load frames in hyperlinks.

## **2.1.244 Part 3 Section 10.4.3, draw:text-box**

a. *The standard defines the element <draw:text-box>*

This element is supported in Word 2013 and later.

A <draw:text-box> element located inside a <draw:frame> element in a <text:p> element in the following elements is not supported and will be lost:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>

b. *The standard defines the element <draw:text-box>*

This element is supported in Excel 2013 and later.

A <draw:text-box> element located inside a <draw:frame> element in a <text:p> element in the following elements is not supported and will be lost:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>

c. *The standard defines the element <draw:text-box>*

This element is supported in PowerPoint 2013 and later.

A <draw:text-box> element located inside a <draw:frame> element in a <text:p> element in the following elements is not supported and will be lost:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <table:table-cell>

### **2.1.245 Part 3 Section 10.4.4, draw:image**

a. *The standard defines the element <draw:image>*

This element is supported in Word 2013 and later.

Text on an image is not supported and on load, Word drops the text.

b. *The standard defines the element <draw:image>*

This element is supported in Excel 2013 and later.

Text on an image is not supported and on load, Excel drops the text.

c. *The standard defines the element <draw:image>*

This element is supported in PowerPoint 2013 and later.

Text on an image is not supported and on load, PowerPoint drops the text.

### **2.1.246 Part 3 Section 10.4.5, office:binary-data**

a. *The standard defines the element <office:binary-data>*

This element is not supported in Word 2013 or later.

b. *The standard defines the element <office:binary-data>, contained within the parent element <draw:object-ole>*

This element is not supported in Word 2013 or later.



- c. *The standard defines the element <office:binary-data>, contained within the parent element <text:list-level-style-image>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the attribute office:binary-data, contained within the element <draw:object-ole>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the element <office:binary-data>*

This element is not supported in Excel 2013 or later.

- f. *The standard defines the element <office:binary-data>, contained within the parent element <style:background-image>*

This element is not supported in Excel 2013 or later.

- g. *The standard defines the element <office:binary-data>, contained within the parent element <text:list-level-style-image>*

**OfficeArt Math** in Excel 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- h. *The standard defines the element <office:binary-data>*

This element is not supported in PowerPoint 2013 or later.

- i. *The standard defines the element <office:binary-data>, contained within the parent element <text:list-level-style-image>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- `<draw:custom-shape>`.

### **2.1.247 Part 3 Section 10.4.6.3, draw:object-ole**

- a. *The standard defines the element `<draw:object-ole>`*

This element is supported in Excel 2013 and later.

Excel does not write a fill on OLE objects, so the background of a OLE object will appear transparent.

Excel only supports absolute paths for OLE links.

- b. *The standard defines the element `<draw:object-ole>`*

This element is supported in PowerPoint 2013 and later.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

### **2.1.248 Part 3 Section 10.4.7, draw:applet**

- a. *The standard defines the element `<draw:applet>`*

This element is not supported in Word 2013 or later.

*This element was deprecated in the ODF 1.3 standard.*

- b. *The standard defines the element `<draw:applet>`*

This element is not supported in Excel 2013 or later.

*This element was deprecated in the ODF 1.3 standard.*

- c. *The standard defines the element `<draw:applet>`*

This element is not supported in PowerPoint 2013 or later.

*This element was deprecated in the ODF 1.3 standard.*

### **2.1.249 Part 3 Section 10.4.8, draw:plugin**

- a. *The standard defines the element `<draw:plugin>`*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element `<draw:plugin>`*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element `<draw:plugin>`*

This element is supported in PowerPoint 2013 and later.

Plug-ins are used to load and save movies and sounds. PowerPoint accepts links to hrefs in the document package.

PowerPoint saves the mime-type of the media as one of the parameters, but ignores it on load.

PowerPoint will not be able to play any plug-ins that cannot be played back using the media pipeline in PowerPoint.

### **2.1.250 Part 3 Section 10.4.9, draw:param**

- a. *The standard defines the element <draw:param>, contained within the parent element <draw:applet>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <draw:param>, contained within the parent element <draw:plugin>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <draw:param>*

This element is not supported in Excel 2013 or later.

- d. *The standard defines the element <draw:param>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.251 Part 3 Section 10.4.10, draw:floating-frame**

- a. *The standard defines the element <draw:floating-frame>*

This element is not supported in Word 2013 or later.

On load, Word ignores the <draw:floating-frame> element and reads the contents of the floating frame as paragraph contents.

- b. *The standard defines the element <draw:floating-frame>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <draw:floating-frame>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.252 Part 3 Section 10.4.11.2, draw:contour-polygon**

- a. *The standard defines the element <draw:contour>, contained within the parent element <draw:applet>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <draw:contour>, contained within the parent element <draw:floating frame>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <draw:contour>, contained within the parent element <draw:image>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <draw:contour>, contained within the parent element <draw:object>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <draw:contour>, contained within the parent element <draw:object-ole>*

This element is not supported in Word 2013 or later.

- f. *The standard defines the element <draw:contour>, contained within the parent element <draw:plugin>*

This element is not supported in Word 2013 or later.

### **2.1.253 Part 3 Section 10.4.11.3, draw:contour-path**

- a. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:applet>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:floating frame>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:image>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:object>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:object-ole>*

This element is not supported in Word 2013 or later.

- f. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:plugin>*

This element is not supported in Word 2013 or later.

### **2.1.254 Part 3 Section 10.4.12, draw:a**

- a. *The standard defines the element <draw:a>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <draw:a>, contained within the parent element <text:p>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <draw:a>*

This element is not supported in Excel 2013 or later.

- d. *The standard defines the element <draw:a>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.255 Part 3 Section 10.4.13.2, draw:image-map**

- a. *The standard defines the element <draw:image-map>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <draw:image-map>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <draw:image-map>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.256 Part 3 Section 10.5.2, dr3d:scene**

- a. *The standard defines the element <dr3d:scene>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <dr3d:scene>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <dr3d:scene>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.257 Part 3 Section 10.5.3, dr3d:light**

- a. *The standard defines the element <dr3d:light>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <dr3d:light>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <dr3d:light>, contained within the parent element <chart:plot-area>*

This element is not supported in Excel 2013 or later.

- d. *The standard defines the element <dr3d:light>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.258 Part 3 Section 10.5.4, dr3d:cube**

- a. *The standard defines the element <dr3d:cube>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <dr3d:cube>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <dr3d:cube>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.259 Part 3 Section 10.5.5, dr3d:sphere**

- a. *The standard defines the element <dr3d:sphere>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <dr3d:sphere>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <dr3d:sphere>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.260 Part 3 Section 10.5.6, dr3d:extrude**

- a. *The standard defines the element <dr3d:extrude>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <dr3d:extrude>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <dr3d:extrude>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.261 Part 3 Section 10.5.7, dr3d:rotate**

- a. *The standard defines the element <dr3d:rotate>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <dr3d:rotate>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <dr3d:rotate>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.262 Part 3 Section 10.8.1, presentation:animations**

- a. *The standard defines the element <presentation:animations>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.263 Part 3 Section 10.8.2, presentation:sound**

- a. *The standard defines the element <presentation:sound>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

- b. *The standard defines the element <presentation:sound>, contained within the parent element <presentation:event-listener>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

- c. *The standard defines the attribute presentation:sound, contained within the element <style:drawing-page-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.264 Part 3 Section 10.8.3, presentation:show-shape**

- a. *The standard defines the element <presentation:show-shape>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.265 Part 3 Section 10.8.4, presentation:show-text**

- a. *The standard defines the element <presentation:show-text>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

*This element was deprecated in the ODF 1.3 standard.*

### **2.1.266 Part 3 Section 10.8.5, presentation:hide-shape**

- a. *The standard defines the element <presentation:hide-shape>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.267 Part 3 Section 10.8.6, presentation:hide-text**

- a. *The standard defines the element <presentation:hide-text>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.268 Part 3 Section 10.8.7, presentation:dim**

- a. *The standard defines the element <presentation:dim>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.269 Part 3 Section 10.8.8, presentation:play**

- a. *The standard defines the element <presentation:play>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.270 Part 3 Section 10.8.9, presentation:animation-group**

- a. *The standard defines the element <presentation:animation-group>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.271 Part 3 Section 10.9.2, presentation:event-listener**

- a. *The standard defines the element <presentation:event-listener>*

This element is supported in PowerPoint 2013 and later.

Shapes and text that link to actions use the <presentation:event-listener> element. Grouped shapes cannot have links to actions.

Actions that are set to happen when the mouse rests on an item, such as a button or link, use the <presentation:event-listener> element. Grouped shapes cannot have actions associated with the mouse resting on an item.

Text links to URLs use the <text:a> hyperlink tag.

### **2.1.272 Part 3 Section 10.9.3.1, presentation:header**

- a. *The standard defines the element <presentation:header>*

This element is supported in PowerPoint 2013 and later.

PowerPoint does not save this element, but does read it in on master-pages to determine the location of the header field.

### **2.1.273 Part 3 Section 10.9.3.2, presentation:header-decl**

- a. *The standard defines the element <presentation:header-decl>*

This element is supported in PowerPoint 2013 and later.

PowerPoint loads headers declared using this attribute, but saves them as textboxes with regular text.

### **2.1.274 Part 3 Section 10.9.3.3, presentation:footer**

- a. *The standard defines the element <presentation:footer>*

This element is supported in PowerPoint 2013 and later.

PowerPoint does not save this element, but does read it in on master-pages to determine the location of the footer field.

### **2.1.275 Part 3 Section 10.9.3.4, presentation:footer-decl**

- a. *The standard defines the element <presentation:footer-decl>*

This element is supported in PowerPoint 2013 and later.

PowerPoint loads footers declared using this attribute, but saves them as textboxes with regular text.

### **2.1.276 Part 3 Section 10.9.3.5, presentation:date-time**

- a. *The standard defines the element <presentation:date-time>*

This element is supported in PowerPoint 2013 and later.

PowerPoint does not save this element, but does read it in on master-pages to determine the location of the date-time field.

### **2.1.277 Part 3 Section 10.9.3.6, presentation:date-time-decl**

- a. *The standard defines the element <presentation:date-time-decl>*

This element is supported in PowerPoint 2013 and later.

PowerPoint loads dates/times declared using this attribute, but saves them as textboxes with regular text.



### **2.1.278 Part 3 Section 11.1, chart:chart**

- a. *The standard defines the element <chart:chart>, contained within the parent element <office:chart>*

The draw:connector, draw:custom-shape, draw:frame, and draw:g child elements are supported in Excel 2021 or later.

The dr3d:scene, draw:a, draw:caption, draw:circle, draw:control, draw:ellipse, draw:line, draw:measure, draw:page-thumbnail, draw:path, draw:polygon, draw:polyline, draw:rect, and draw-regular-polygon child elements are not supported in Excel 2013 and later.

### **2.1.279 Part 3 Section 11.2.2, chart:subtitle**

- a. *The standard defines the element <chart:subtitle>, contained within the parent element <chart:chart>*

This element is not supported in Excel 2013 or later.

### **2.1.280 Part 3 Section 11.2.3, chart:footer**

- a. *The standard defines the element <chart:footer>, contained within the parent element <chart:chart>*

This element is not supported in Excel 2013 or later.

### **2.1.281 Part 3 Section 11.3, chart:coordinate-region**

- a. *The standard defines the element <chart:coordinate-region>, contained within the parent element <chart:plot-area>*

This element is not supported in Excel 2013 and later.

### **2.1.282 Part 3 Section 11.4, chart:legend**

- a. *The standard defines the element <chart:legend>, contained within the parent element <chart:chart>*

This element is supported in Excel 2013 and later.

The svg:height, and svg:width attributes are supported in Excel 2021 and later, but are ignored when a chart:legend-position attribute is present.

### **2.1.283 Part 3 Section 11.9, chart:axis**

- a. *The standard defines the element <chart:axis>, contained within the parent element <chart:plot-area>*

This element is supported in Excel 2013 and later.

Excel requires two (2) <chart:axis> elements on load.

### **2.1.284 Part 3 Section 11.16, chart:mean-value**

- a. *The standard defines the attribute chart:mean-value*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the element <chart:mean-value>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <chart:mean-value>, contained within the parent element <chart:series>*

This element is not supported in Excel 2013 or later.

#### **2.1.285 Part 3 Section 11.17, chart:error-indicator**

- a. *The standard defines the element <chart:error-indicator>*

This element is supported in Excel 2013 and later.

Excel only supports this element when the series type is line, area, scatter, bar, stock, or bubble; and the chart is not three dimensional.

#### **2.1.286 Part 3 Section 11.18, chart:regression-curve**

- a. *The standard defines the element <chart:regression-curve>*

This element is supported in Excel 2013 and later.

Excel only supports this element when the series type is line, area, scatter, bar, stock, or bubble; and the chart is not three dimensional.

#### **2.1.287 Part 3 Section 11.20, chart:stock-gain-marker**

- a. *The standard defines the element <chart:stock-gain-marker>*

This element is supported in Excel 2013 and later.

Excel only supports this element when the series type is line or stock and the chart is not three dimensional.

#### **2.1.288 Part 3 Section 11.21, chart:stock-loss-marker**

- a. *The standard defines the element <chart:stock-loss-marker>*

This element is supported in Excel 2013 and later.

Excel only supports this element when the series type is line or stock and the chart is not three dimensional.

#### **2.1.289 Part 3 Section 11.22, chart:stock-range-line**

- a. *The standard defines the element <chart:stock-range-line>*

This element is supported in Excel 2013 and later.

Excel only supports this element when the series type is line or stock and the chart is not three dimensional.

#### **2.1.290 Part 3 Section 13.2, office:forms**

- a. *The standard defines the element <office:forms>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <office:forms>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <office:forms>, contained within the parent element <table:dde-link>*

This element is not supported in Excel 2013 or later.

- d. *The standard defines the element <office:forms>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.291 Part 3 Section 13.3, form:form**

- a. *The standard defines the element <form:form>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:form>*

This element is not supported in Excel 2013 or later.

#### **2.1.292 Part 3 Section 13.4, xforms:model**

- a. *The standard defines the element <xforms:model>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <xforms:model>*

This element is not supported in Excel 2013 or later.

#### **2.1.293 Part 3 Section 13.5.2, form:text**

- a. *The standard defines the element <form:text>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:text>*

This element is not supported in Excel 2013 or later.

#### **2.1.294 Part 3 Section 13.5.3, form:textarea**

- a. *The standard defines the element <form:textarea>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:textarea>*

This element is not supported in Excel 2013 or later.

#### **2.1.295 Part 3 Section 13.5.4, form:password**

- a. *The standard defines the element <form:password>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:password>*

This element is not supported in Excel 2013 or later.

#### **2.1.296 Part 3 Section 13.5.5, form:file**

- a. *The standard defines the element <form:file>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:file>*

This element is not supported in Excel 2013 or later.

#### **2.1.297 Part 3 Section 13.5.6, form:formatted-text**

- a. *The standard defines the element <form:formatted-text>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:formatted-text>*

This element is not supported in Excel 2013 or later.

#### **2.1.298 Part 3 Section 13.5.7, form:number**

- a. *The standard defines the element <form:number>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:number>*

This element is not supported in Excel 2013 or later.

#### **2.1.299 Part 3 Section 13.5.8, form:date**

- a. *The standard defines the element <form:date>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:date>*

This element is not supported in Excel 2013 or later.

#### **2.1.300 Part 3 Section 13.5.9, form:time**

- a. *The standard defines the element <form:time>*

This element is not supported in Excel 2013 or later.

#### **2.1.301 Part 3 Section 13.5.10, form:fixed-text**

- a. *The standard defines the element <form:fixed-text>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:fixed-text>*

This element is not supported in Excel 2013 or later.

#### **2.1.302 Part 3 Section 13.5.11, form:combobox**

- a. *The standard defines the element <form:combobox>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:combobox>*

This element is not supported in Excel 2013 or later.

#### **2.1.303 Part 3 Section 13.5.12, form:item**

- a. *The standard defines the element <form:item>, contained within the parent element <form:combobox>*

This element is not supported in Word 2013 or later.

#### **2.1.304 Part 3 Section 13.5.13, form:listbox**

- a. *The standard defines the element <form:listbox>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:listbox>*

This element is not supported in Excel 2013 or later.

#### **2.1.305 Part 3 Section 13.5.14, form:option**

- a. *The standard defines the element <form:option>, contained within the parent element <form:listbox>*

This element is not supported in Word 2013 or later.

#### **2.1.306 Part 3 Section 13.5.15, form:button**

- a. *The standard defines the element <form:button>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:button>*

This element is not supported in Excel 2013 or later.

#### **2.1.307 Part 3 Section 13.5.16, form:image**

- a. *The standard defines the element <form:image>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:image>*

This element is not supported in Excel 2013 or later.

### **2.1.308 Part 3 Section 13.5.17, form:checkbox**

- a. *The standard defines the element <form:checkbox>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <form:checkbox>*  
This element is not supported in Excel 2013 or later.

### **2.1.309 Part 3 Section 13.5.18, form:radio**

- a. *The standard defines the element <form:radio>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <form:radio>*  
This element is not supported in Excel 2013 or later.

### **2.1.310 Part 3 Section 13.5.19, form:frame**

- a. *The standard defines the element <form:frame>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <form:frame>*  
This element is not supported in Excel 2013 or later.

### **2.1.311 Part 3 Section 13.5.20, form:image-frame**

- a. *The standard defines the element <form:image-frame>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <form:image-frame>*  
This element is not supported in Excel 2013 or later.

### **2.1.312 Part 3 Section 13.5.21, form:hidden**

- a. *The standard defines the element <form:hidden>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <form:hidden>*  
This element is not supported in Excel 2013 or later.

### **2.1.313 Part 3 Section 13.5.22, form:grid**

- a. *The standard defines the element <form:grid>*  
This element is not supported in Word 2013 or later.
- b. *The standard defines the element <form:grid>*  
This element is not supported in Excel 2013 or later.

### **2.1.314 Part 3 Section 13.5.23, form:column**

- a. *The standard defines the element <form:column>, contained within the parent element <form:grid>*

This element is not supported in Word 2013 or later.

### **2.1.315 Part 3 Section 13.5.24, form:value-range**

- a. *The standard defines the element <form:value-range>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:value-range>*

This element is not supported in Excel 2013 or later.

### **2.1.316 Part 3 Section 13.5.25, form:generic-control**

- a. *The standard defines the element <form:generic-control>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:generic-control>*

This element is not supported in Excel 2013 or later.

### **2.1.317 Part 3 Section 13.7, form:properties**

- a. *The standard defines the element <form:properties>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:properties>*

This element is not supported in Excel 2013 or later.

### **2.1.318 Part 3 Section 13.8, form:property**

- a. *The standard defines the element <form:property>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:property>*

This element is not supported in Excel 2013 or later.

### **2.1.319 Part 3 Section 13.9, form:list-property**

- a. *The standard defines the element <form:list-property>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <form:list-property>*

This element is not supported in Excel 2013 or later.

### **2.1.320 Part 3 Section 13.10, form:list-value**

- a. *The standard defines the attribute form:list-value*

This attribute is not supported in Word 2013 or later.

### **2.1.321 Part 3 Section 14.1, office:annotation**

- a. *The standard defines the element <office:annotation>*

This element is supported in Word 2013 and later.

On load, annotations are dropped from headers, footers, footnotes, endnotes, and textboxes.

On save, annotations are dropped from equations.

The xml:id attribute for this element is not supported in Word 2013, Word 2016, or Word 2019.

- b. *The standard defines the element <office:annotation>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <office:annotation>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.322 Part 3 Section 14.2, office:annotation-end**

- a. *The standard defines the element <office:annotation-end>*

This element is supported in Word 2013 and later.

On load, annotations are dropped from headers, footers, footnotes, endnotes, and textboxes.

On save, annotations are dropped from equations.

- b. *The standard defines the element <office:annotation-end>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.323 Part 3 Section 14.3, meta:date-string**

- a. *The standard defines the element <meta:date-string>, contained within the parent element <office:annotation>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <meta:date-string>, contained within the parent element <office:annotation>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <meta:date-string>, contained within the parent element <office:annotation>*

This element is not supported in PowerPoint 2013 or later.



### **2.1.324 Part 3 Section 14.4, meta:creator-initials**

- a. *The standard defines the element <meta:creator-initials>, contained within the parent element <office:annotation>*

This element is not supported in PowerPoint 2021 or later.

- b. *The standard defines the element <meta:creator-initials>, contained within the parent element <office:annotation>*

This element is supported in Word 2021 or later.

### **2.1.325 Part 3 Section 14.5.2, script:event-listener**

- a. *The standard defines the element <office:event-listeners>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <script:event-listener>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.326 Part 3 Section 14.6, math:math**

- a. *The standard defines the attribute display, contained within the element <math>*

This attribute is supported in Word 2013 and later.

On load, Word does not read the display attribute in a <math> element.

On save, Word writes the display attribute in a <math> element.

- b. *The standard defines the element <math:math>*

This element is supported in Word 2013 and later.

On load, alignment of text around formula objects may be lost.

On load, the MathML namespace qualifier must be present for math elements, and may be present for attributes.

On save, only bold and italics text properties are supported.

On save, Word equations that contain images are lost, and their images are also lost.

On save, if a Word equation contains OLE objects, the Word equation and the OLE objects it contains are lost.

On save, Word writes the MathML namespace qualifier for elements but does not write the namespace qualifier for attributes.

This element is supported in Word 2013 and later.

On load, Word reads only presentation MathML elements within the <math> element. Word does not read any of the attributes of the math element.

On save, Word writes only presentation MathML elements within the <math> element.

- c. *The standard defines the attribute display, contained within the element <math>*

This attribute is supported in Excel 2013 and later.

On load, Excel does not read the display attribute in a <math> element.

On save, Excel writes the display attribute in a <math> element.

d. *The standard defines the element <math:math>*

This element is supported in Excel 2013 and later.

On load, Excel reads only presentation MathML elements within the <math> element. Excel does not read any of the attributes of the math element.

On save, Excel writes only presentation MathML elements within the <math> element.

e. *The standard defines the element <math:math>, contained within the parent element <draw:object>*

This element is not supported in Excel 2013 or later.

f. *The standard defines the attribute display, contained within the element <math>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint does not read the display attribute in a <math> element.

On save, PowerPoint writes the display attribute in a <math> element.

g. *The standard defines the element <math:math>*

This element is supported in PowerPoint 2013 and later.

On load, PowerPoint reads only presentation MathML elements within the <math> element. PowerPoint does not read any of the attributes of the math element.

On save, PowerPoint writes only presentation MathML elements within the <math> element.

## **2.1.327 Part 3 Section 14.6 (MathML 2.0 Section 3.2.3), Identifier (mi)**

a. *The standard defines the element <mi>*

This element is supported in MathML in Word 2013 and later.

On load, MathML in Word recognizes MathML as a function if:

(a) the parent wrapper is an <mrow> element

(b) there are three child elements, and

(c) the second child element is an <mo> element that contains the function apply character, <U+2061>.

On save, MathML in Word separates the text that was contained in <mi> element tags into single characters unless the identifier is a function name.

This element is supported in **OfficeArt Math** in Word 2013 and later.

b. *The standard defines the attribute class, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

c. *The standard defines the attribute color, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the color attribute in an <mi> element. On save, OfficeArt Math in Word does not write the color attribute in an <mi> element.

- d. *The standard defines the attribute fontfamily, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute fontsize, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute fontstyle, contained within the element <mi>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontstyle attribute in an <mi> element. On save, Word does not write the fontstyle attribute in an <mi> element.

- g. *The standard defines the attribute fontweight, contained within the element <mi>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontweight attribute in an <mi> element. On save, Word does not write the fontweight attribute in an <mi> element.

- h. *The standard defines the attribute id, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the attribute mathbackground, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- j. *The standard defines the attribute mathcolor, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the mathcolor attribute in an <mi> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mi> element.

- k. *The standard defines the attribute mathsize, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- l. *The standard defines the attribute mathvariant, contained within the element <mi>*

This attribute is supported in Word 2013 and later.

On load, Word reads the mathvariant attribute in an <mi> element.

On save, Word writes only the 'normal' value to distinguish upright characters from math italics. All math alphanumeric characters are written using Unicode code points.

- m. *The standard defines the property "(everything else)", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in Word 2013 and later.

On load, Word reads the mathvariant attribute in an <mi> element.

On save, Word does not write the mathvariant attribute in an <mi> element for the value of '(everything else)'.

- n. *The standard defines the property "monospace", contained within the attribute mathvariant, contained within the element <mi>*

This property is not supported in Word 2013 or later.

- o. *The standard defines the attribute style, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- p. *The standard defines the attribute xref, contained within the element <mi>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- q. *The standard defines the element <mi>*

This element is supported in Excel 2013 and later.

- r. *The standard defines the attribute class, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- s. *The standard defines the attribute color, contained within the element <mi>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the color attribute in an <mi> element. On save, Excel does not write the color attribute in an <mi> element.

- t. *The standard defines the attribute fontfamily, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- u. *The standard defines the attribute fontsize, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- v. *The standard defines the attribute fontstyle, contained within the element <mi>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontstyle attribute in an <mi> element. On save, Excel does not write the fontstyle attribute in an <mi> element.

- w. *The standard defines the attribute fontweight, contained within the element <mi>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontweight attribute in an <mi> element. On save, Excel does not write the fontweight attribute in an <mi> element.

- x. *The standard defines the attribute id, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- y. *The standard defines the attribute mathbackground, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- z. *The standard defines the attribute mathcolor, contained within the element <mi>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathcolor attribute in an <mi> element. On save, Excel does not write the mathcolor attribute in an <mi> element.

- aa. *The standard defines the attribute mathsize, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- bb. *The standard defines the attribute mathvariant, contained within the element <mi>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathvariant attribute in an <mi> element.

On save, Excel writes only the 'normal' value to distinguish upright characters from math italics. All math alphanumeric characters are written using Unicode code points.

- cc. *The standard defines the property "(everything else)", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in Excel 2013 and later.

On load, Excel reads the mathvariant attribute in an <mi> element.

On save, Excel does not write the mathvariant attribute in an <mi> element for the value of '(everything else)'.

- dd. *The standard defines the attribute style, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- ee. *The standard defines the attribute xref, contained within the element <mi>*

This attribute is not supported in Excel 2013 or later.

- ff. *The standard defines the element <mi>*

This element is supported in PowerPoint 2013 and later.

- gg. *The standard defines the attribute class, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

- hh. *The standard defines the attribute color, contained within the element <mi>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the color attribute in an <mi> element. On save, PowerPoint does not write the color attribute in an <mi> element.

ii. *The standard defines the attribute fontfamily, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

jj. *The standard defines the attribute fontsize, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

kk. *The standard defines the attribute fontstyle, contained within the element <mi>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontstyle attribute in an <mi> element. On save, PowerPoint does not write the fontstyle attribute in an <mi> element.

ll. *The standard defines the attribute fontweight, contained within the element <mi>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontweight attribute in an <mi> element. On save, PowerPoint does not write the fontweight attribute in an <mi> element.

mm. *The standard defines the attribute id, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

nn. *The standard defines the attribute mathbackground, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

oo. *The standard defines the attribute mathcolor, contained within the element <mi>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathcolor attribute in an <mi> element. On save, PowerPoint does not write the mathcolor attribute in an <mi> element.

pp. *The standard defines the attribute mathsize, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

qq. *The standard defines the attribute mathvariant, contained within the element <mi>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathvariant attribute in an <mi> element.

On save, PowerPoint writes only the 'normal' value to distinguish upright characters from math italics. All math alphanumeric characters are written using Unicode code points.

rr. *The standard defines the property "(everything else)", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in PowerPoint 2013 and PowerPoint 2016.

On load, PowerPoint reads the mathvariant attribute in an <mi> element.

On save, PowerPoint does not write the mathvariant attribute in an <mi> element for the value of '(everything else)'.

ss. *The standard defines the property "normal", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in PowerPoint 2013 and PowerPoint 2016.

tt. *The standard defines the attribute style, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

uu. *The standard defines the attribute xref, contained within the element <mi>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.328 Part 3 Section 14.6 (MathML 2.0 Section 3.2.4), Number (mn)**

a. *The standard defines the element <mn>*

This element is supported in MathML in Word 2013 and later.

MathML in Word supports only numbers composed of the digits 0-9 for the <mn> element. On load, numbers containing other characters, such as roman numerals and hexadecimal numbers, may be interpreted differently than was intended.

On save, the <mn> element is used only for numbers that are composed of the digits 0-9. Periods and commas that are used as delimiters are also saved in the <mn> element.

This element is supported in **OfficeArt Math** in Word 2013 and later.

b. *The standard defines the attribute class, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

c. *The standard defines the attribute color, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the color attribute in an <mn> element. On save, OfficeArt Math in Word does not write the color attribute in an <mn> element.

d. *The standard defines the attribute fontfamily, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

e. *The standard defines the attribute fontsize, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

f. *The standard defines the attribute fontstyle, contained within the element <mn>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontstyle attribute in an <mn> element. On save, Word does not write the fontstyle attribute in an <mn> element.

- g. *The standard defines the attribute fontweight, contained within the element <mn>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontweight attribute in an <mn> element. On save, Word does not write the fontweight attribute in an <mn> element.

- h. *The standard defines the attribute id, contained within the element <mn>*

This attribute is not supported in Word 2013 or later.

- i. *The standard defines the attribute mathbackground, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- j. *The standard defines the attribute mathcolor, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the mathcolor attribute in an <mn> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mn> element.

- k. *The standard defines the attribute mathsize, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- l. *The standard defines the attribute mathvariant, contained within the element <mn>*

This attribute is supported in MathML in Word 2013 and later.

On load, MathML in Word reads the mathvariant attribute in an <mn> element.

On save, MathML in Word does not write the mathvariant attribute in an <mn> element.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the mathvariant attribute in an <mn> element.

On save, OfficeArt Math in Word does not write the mathvariant attribute in an <mn> element. All math alphanumeric characters are written using Unicode code points.

- m. *The standard defines the property "monospace", contained within the attribute mathvariant, contained within the element <mn>*

This property is not supported in Word 2013 or later.

- n. *The standard defines the attribute style, contained within the element <mn>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- o. *The standard defines the attribute xref, contained within the element <mn>*

This attribute is not supported in Word 2013 or later.

- p. *The standard defines the element <mn>*



This element is supported in Excel 2013 and later.

- q. *The standard defines the attribute class, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

- r. *The standard defines the attribute color, contained within the element <mn>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the color attribute in an <mn> element. On save, Excel does not write the color attribute in an <mn> element.

- s. *The standard defines the attribute fontfamily, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

- t. *The standard defines the attribute fontsize, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

- u. *The standard defines the attribute fontstyle, contained within the element <mn>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontstyle attribute in an <mn> element. On save, Excel does not write the fontstyle attribute in an <mn> element.

- v. *The standard defines the attribute fontweight, contained within the element <mn>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontweight attribute in an <mn> element. On save, Excel does not write the fontweight attribute in an <mn> element.

- w. *The standard defines the attribute id, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

- x. *The standard defines the attribute mathbackground, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

- y. *The standard defines the attribute mathcolor, contained within the element <mn>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathcolor attribute in an <mn> element. On save, Excel does not write the mathcolor attribute in an <mn> element.

- z. *The standard defines the attribute mathsize, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

- aa. *The standard defines the attribute mathvariant, contained within the element <mn>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathvariant attribute in an <mn> element.

On save, Excel does not write the mathvariant attribute in an <mn> element. All math alphanumeric characters are written using Unicode code points.

bb. *The standard defines the attribute style, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

cc. *The standard defines the attribute xref, contained within the element <mn>*

This attribute is not supported in Excel 2013 or later.

dd. *The standard defines the element <mn>*

This element is supported in PowerPoint 2013 and later.

ee. *The standard defines the attribute class, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

ff. *The standard defines the attribute color, contained within the element <mn>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the color attribute in an <mn> element. On save, PowerPoint does not write the color attribute in an <mn> element.

gg. *The standard defines the attribute fontfamily, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

hh. *The standard defines the attribute fontsize, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

ii. *The standard defines the attribute fontstyle, contained within the element <mn>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontstyle attribute in an <mn> element. On save, PowerPoint does not write the fontstyle attribute in an <mn> element.

jj. *The standard defines the attribute fontweight, contained within the element <mn>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontweight attribute in an <mn> element. On save, PowerPoint does not write the fontweight attribute in an <mn> element.

kk. *The standard defines the attribute id, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

ll. *The standard defines the attribute mathbackground, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

mm. *The standard defines the attribute mathcolor, contained within the element <mn>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathcolor attribute in an <mn> element. On save, PowerPoint does not write the mathcolor attribute in an <mn> element.

nn. *The standard defines the attribute mathsize, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

oo. *The standard defines the attribute mathvariant, contained within the element <mn>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathvariant attribute in an <mn> element.

On save, PowerPoint does not write the mathvariant attribute in an <mn> element. All math alphanumeric characters are written using Unicode code points.

pp. *The standard defines the attribute style, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

qq. *The standard defines the attribute xref, contained within the element <mn>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.329 Part 3 Section 14.6 (MathML 2.0 Section 3.2.5), Operator, Fence, Separator or Accent (mo)**

a. *The standard defines the element <mo>*

This element is supported in MathML in Word 2013 and later.

On save, MathML in Word does not write out the mathvariant, fontweight, or fontstyle attributes for the <mo> element.

On load, MathML in Word recognizes MathML <mrow> elements as functions if the following are true:

- There are three child elements.
- The second child element is an <mo> element that contains one character - the function apply character, <U+2061>.

On load, Nary operators with no limits defined are interpreted as regular operators.

MathML in Word may inconsistently apply italic formatting to operators.

On load, operators are always assumed to have italics applied unless mathvariant, fontweight, or fontstyle attributes are present and state otherwise. (For example, <mo mathvariant="normal">+</mo>). The values of the mathvariant, fontweight or fontstyle attributes are reflected on the format buttons on the MathML in Word user interface, but may not impact whether the operator renders in italics or non-italics.

This element is supported in **OfficeArt Math** in Word 2013 and later.

b. *The standard defines the attribute accent, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the accent attribute in an <mo> element.

On save, OfficeArt Math in Word does not write the accent attribute in an <mo> element.

c. *The standard defines the attribute class, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute color, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the color attribute in an <mo> element. On save, OfficeArt Math in Word does not write the color attribute in an <mo> element.

- e. *The standard defines the attribute fence, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

MathML in Word does not support this attribute. MathML in Word does support the <mfence> element on load, which can be used instead.

This attribute is supported in OfficeArt Math in Word 2013 and later.

- f. *The standard defines the attribute fontfamily, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the attribute fontsize, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the attribute fontstyle, contained within the element <mo>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontstyle attribute in an <mo> element. On save, Word does not write the fontstyle attribute in an <mo> element.

- i. *The standard defines the attribute fontweight, contained within the element <mo>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontweight attribute in an <mo> element. On save, Word does not write the fontweight attribute in an <mo> element.

- j. *The standard defines the attribute form, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

- k. *The standard defines the attribute id, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- l. *The standard defines the attribute largeop, contained within the element <mo>*

This attribute is not supported in Word 2013 or later.

- m. *The standard defines the attribute lspace, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- n. *The standard defines the attribute `mathbackground`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the `mathbackground` attribute in an `<mo>` element. On save, OfficeArt Math in Word does not write the `mathbackground` attribute in an `<mo>` element.

- o. *The standard defines the attribute `mathcolor`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the `mathcolor` attribute in an `<mo>` element. On save, OfficeArt Math in Word does not write the `mathcolor` attribute in an `<mo>` element.

- p. *The standard defines the attribute `mathsize`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- q. *The standard defines the attribute `mathvariant`, contained within the element `<mo>`*

This attribute is supported in Word 2013 and later.

On load, Word reads the `mathvariant` attribute in an `<mo>` element.

On save, Word does not write the `mathvariant` attribute in an `<mo>` element. All math alphanumeric characters are written using Unicode code points.

- r. *The standard defines the property "monospace", contained within the attribute `mathvariant`, contained within the element `<mo>`*

This property is supported in Word 2013 and later.

On load, Word ignores the `mathvariant` attribute when it has a value of "monospace".

- s. *The standard defines the attribute `maxsize`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- t. *The standard defines the attribute `minsize`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- u. *The standard defines the attribute `movablelimits`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- v. *The standard defines the attribute `rspace`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- w. *The standard defines the attribute separator, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

MathML in Word does not support the "separator" attribute of the <mo> element. MathML in Word does support the <mfence> element on load, which can be used instead.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- x. *The standard defines the attribute stretchy, contained within the element <mo>*

This attribute is supported in MathML in Word 2013 and later.

ON SAVE, MathML in Word will emit stretchy for the following N-Ary operators: '&#x222B;', '&#x222C;', '&#x222D;', '&#x222E;', '&#x222F;', '&#x2230;', '&#x2232;', '&#x2233;', '&#x2231;', '&#x2229;', '&#x222A;', '&#x220F;', '&#x2210;', '&#x2211;', '&#x22C0;', '&#x22C1;', '&#x22C2;', '&#x22C3;'

ON LOAD, MathML in Word will respect the stretchy attribute for the following N-Ary operators: '&#x222B;', '&#x222C;', '&#x222D;', '&#x222E;', '&#x222F;', '&#x2230;', '&#x2232;', '&#x2233;', '&#x2231;', '&#x2229;', '&#x222A;', '&#x220F;', '&#x2210;', '&#x2211;', '&#x22C0;', '&#x22C1;', '&#x22C2;', '&#x22C3;'

ON LOAD, if the stretchy attribute is absent then MathML in Word will interpret the stretchy attribute value to be TRUE for the following N-Ary operators: '&#x222B;', '&#x222E;', '&#x222F;', '&#x2232;', '&#x2233;', '&#x2229;', '&#x222A;', '&#x220F;', '&#x2211;', '&#x22C0;', '&#x22C1;', '&#x22C2;', '&#x22C3;'

And, MathML in Word will interpret the stretchy attribute value to be FALSE for the following N-Ary operators: '&#x222C;', '&#x222D;', '&#x2230;', '&#x2231;', '&#x2210;'

This attribute is supported in OfficeArt Math in Word 2013 and later.

- y. *The standard defines the attribute style, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- z. *The standard defines the attribute symmetric, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- aa. *The standard defines the attribute xref, contained within the element <mo>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- bb. *The standard defines the element <mo>*

This element is supported in Excel 2013 and later.

- cc. *The standard defines the attribute accent, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the accent attribute in an <mo> element.

On save, Excel does not write the accent attribute in an <mo> element.

dd. *The standard defines the attribute class, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

ee. *The standard defines the attribute color, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the color attribute in an <mo> element. On save, Excel does not write the color attribute in an <mo> element.

ff. *The standard defines the attribute fence, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

gg. *The standard defines the attribute fontfamily, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

hh. *The standard defines the attribute fontsize, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

ii. *The standard defines the attribute fontstyle, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontstyle attribute in an <mo> element. On save, Excel does not write the fontstyle attribute in an <mo> element.

jj. *The standard defines the attribute fontweight, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontweight attribute in an <mo> element. On save, Excel does not write the fontweight attribute in an <mo> element.

kk. *The standard defines the attribute form, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

ll. *The standard defines the attribute id, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

mm. *The standard defines the attribute lspace, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

nn. *The standard defines the attribute mathbackground, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathbackground attribute in an <mo> element. On save, Excel does not write the mathbackground attribute in an <mo> element.

oo. *The standard defines the attribute mathcolor, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathcolor attribute in an <mo> element. On save, Excel does not write the mathcolor attribute in an <mo> element.

pp. *The standard defines the attribute mathsize, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

qq. *The standard defines the attribute mathvariant, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathvariant attribute in an <mo> element.

On save, Excel does not write the mathvariant attribute in an <mo> element. All math alphanumeric characters are written using Unicode code points.

rr. *The standard defines the attribute maxsize, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

ss. *The standard defines the attribute minsize, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

tt. *The standard defines the attribute movablelimits, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

uu. *The standard defines the attribute rspace, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

vv. *The standard defines the attribute separator, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

ww. *The standard defines the attribute stretchy, contained within the element <mo>*

This attribute is supported in Excel 2013 and later.

xx. *The standard defines the attribute style, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

yy. *The standard defines the attribute symmetric, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

zz. *The standard defines the attribute xref, contained within the element <mo>*

This attribute is not supported in Excel 2013 or later.

aaa. *The standard defines the element <mo>*

This element is supported in PowerPoint 2013 and later.

bbb. *The standard defines the attribute accent, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the accent attribute in an <mo> element.

On save, PowerPoint does not write the accent attribute in an <mo> element.



ccc. *The standard defines the attribute class, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

ddd. *The standard defines the attribute color, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the color attribute in an <mo> element. On save, PowerPoint does not write the color attribute in an <mo> element.

eee. *The standard defines the attribute fence, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

fff. *The standard defines the attribute fontfamily, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

ggg. *The standard defines the attribute fontsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

hhh. *The standard defines the attribute fontstyle, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontstyle attribute in an <mo> element. On save, PowerPoint does not write the fontstyle attribute in an <mo> element.

iii. *The standard defines the attribute fontweight, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontweight attribute in an <mo> element. On save, PowerPoint does not write the fontweight attribute in an <mo> element.

jjj. *The standard defines the attribute form, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

kkk. *The standard defines the attribute id, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

lll. *The standard defines the attribute lspace, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

mmm. *The standard defines the attribute mathbackground, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathbackground attribute in an <mo> element. On save, PowerPoint does not write the mathbackground attribute in an <mo> element.

nnn. *The standard defines the attribute mathcolor, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathcolor attribute in an <mo> element. On save, PowerPoint does not write the mathcolor attribute in an <mo> element.

ooo. *The standard defines the attribute mathsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

ppp. *The standard defines the attribute mathvariant, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathvariant attribute in an <mo> element.

On save, PowerPoint does not write the mathvariant attribute in an <mo> element. All math alphanumeric characters are written using Unicode code points.

qqq. *The standard defines the attribute maxsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

rrr. *The standard defines the attribute minsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

sss. *The standard defines the attribute movablelimits, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

ttt. *The standard defines the attribute rspace, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

uuu. *The standard defines the attribute separator, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

vvv. *The standard defines the attribute stretchy, contained within the element <mo>*

This attribute is supported in PowerPoint 2013 and later.

www. *The standard defines the attribute style, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

xxx. *The standard defines the attribute symmetric, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

yyy. *The standard defines the attribute xref, contained within the element <mo>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.330 Part 3 Section 14.6 (MathML 2.0 Section 3.2.6), Text (mtext)**

a. *The standard defines the element <mtext>*

This element is supported in Word 2013 and later.

b. *The standard defines the attribute class, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

c. *The standard defines the attribute color, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the color attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the color attribute in an <mtext> element.

- d. *The standard defines the attribute fontfamily, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute fontsize, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute fontstyle, contained within the element <mtext>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontstyle attribute in an <mtext> element. On save, Word does not write the fontstyle attribute in an <mtext> element.

- g. *The standard defines the attribute fontweight, contained within the element <mtext>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontweight attribute in an <mtext> element. On save, Word does not write the fontweight attribute in an <mtext> element.

- h. *The standard defines the attribute id, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the attribute mathbackground, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the mathbackground attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the mathbackground attribute in an <mtext> element.

- j. *The standard defines the attribute mathcolor, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the mathcolor attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mtext> element.

- k. *The standard defines the attribute mathsize, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- l. *The standard defines the attribute `mathvariant`, contained within the element `<mtext>`*

This attribute is supported in Word 2013 and later.

On load, Word reads the `mathvariant` attribute in an `<mtext>` element.

On save, Word does not write the `mathvariant` attribute in an `<mtext>` element. All math alphanumeric characters are written using Unicode code points.
- m. *The standard defines the property "monospace", contained within the attribute `mathvariant`, contained within the element `<mtext>`*

This property is supported in Word 2013 and later.

On load, Word ignores the `mathvariant` attribute if the value is "monospace".
- n. *The standard defines the attribute `style`, contained within the element `<mtext>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.
- o. *The standard defines the attribute `xref`, contained within the element `<mtext>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.
- p. *The standard defines the element `<mtext>`*

This element is supported in Excel 2013 and later.
- q. *The standard defines the attribute `class`, contained within the element `<mtext>`*

This attribute is not supported in Excel 2013 or later.
- r. *The standard defines the attribute `color`, contained within the element `<mtext>`*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the `color` attribute in an `<mtext>` element. On save, Excel does not write the `color` attribute in an `<mtext>` element.
- s. *The standard defines the attribute `fontfamily`, contained within the element `<mtext>`*

This attribute is not supported in Excel 2013 or later.
- t. *The standard defines the attribute `fontsize`, contained within the element `<mtext>`*

This attribute is not supported in Excel 2013 or later.
- u. *The standard defines the attribute `fontstyle`, contained within the element `<mtext>`*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the `fontstyle` attribute in an `<mtext>` element. On save, Excel does not write the `fontstyle` attribute in an `<mtext>` element.
- v. *The standard defines the attribute `fontweight`, contained within the element `<mtext>`*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontweight attribute in an <mtext> element. On save, Excel does not write the fontweight attribute in an <mtext> element.

- w. *The standard defines the attribute id, contained within the element <mtext>*

This attribute is not supported in Excel 2013 or later.

- x. *The standard defines the attribute mathbackground, contained within the element <mtext>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathbackground attribute in an <mtext> element. On save, Excel does not write the mathbackground attribute in an <mtext> element.

- y. *The standard defines the attribute mathcolor, contained within the element <mtext>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathcolor attribute in an <mtext> element. On save, Excel does not write the mathcolor attribute in an <mtext> element.

- z. *The standard defines the attribute mathsize, contained within the element <mtext>*

This attribute is not supported in Excel 2013 or later.

- aa. *The standard defines the attribute mathvariant, contained within the element <mtext>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathvariant attribute in an <mtext> element.

On save, Excel does not write the mathvariant attribute in an <mtext> element. All math alphanumeric characters are written using Unicode code points.

- bb. *The standard defines the attribute style, contained within the element <mtext>*

This attribute is not supported in Excel 2013 or later.

- cc. *The standard defines the attribute xref, contained within the element <mtext>*

This attribute is not supported in Excel 2013 or later.

- dd. *The standard defines the element <mtext>*

This element is supported in PowerPoint 2013 and later.

- ee. *The standard defines the attribute class, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2013 or later.

- ff. *The standard defines the attribute color, contained within the element <mtext>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the color attribute in an <mtext> element. On save, PowerPoint does not write the color attribute in an <mtext> element.

- gg. *The standard defines the attribute fontfamily, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2013 or later.

- hh. *The standard defines the attribute fontsize, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2013 or later.

- ii. *The standard defines the attribute fontstyle, contained within the element <mtext>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontstyle attribute in an <mtext> element. On save, PowerPoint does not write the fontstyle attribute in an <mtext> element.

- jj. *The standard defines the attribute fontweight, contained within the element <mtext>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontweight attribute in an <mtext> element. On save, PowerPoint does not write the fontweight attribute in an <mtext> element.

- kk. *The standard defines the attribute id, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2013 or later.

- ll. *The standard defines the attribute mathbackground, contained within the element <mtext>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathbackground attribute in an <mtext> element. On save, PowerPoint does not write the mathbackground attribute in an <mtext> element.

- mm. *The standard defines the attribute mathcolor, contained within the element <mtext>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathcolor attribute in an <mtext> element. On save, PowerPoint does not write the mathcolor attribute in an <mtext> element.

- nn. *The standard defines the attribute mathsize, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2013 or later.

- oo. *The standard defines the attribute mathvariant, contained within the element <mtext>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathvariant attribute in an <mtext> element.

On save, PowerPoint does not write the mathvariant attribute in an <mtext> element. All math alphanumeric characters are written using Unicode code points.

- pp. *The standard defines the attribute style, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2013 or later.

- qq. *The standard defines the attribute xref, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.331 Part 3 Section 14.6 (MathML 2.0 Section 3.2.7), Space (mspace)**

- a. *The standard defines the element <mspace>*

This element is not supported in MathML in Word 2013 or later.

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word reads the <mspace> element. On load, the <mspace> element is treated as a space character when width, height or depth are specified.

On save, OfficeArt Math in Word does not write the <mspace> element.

- b. *The standard defines the attribute class, contained within the element <mspace>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute depth, contained within the element <mspace>*

This attribute is supported in Word 2013 and later.

On load, Word reads the depth attribute in an <mspace> element. An ASCII space is inserted.

On save, Word does not write the <mspace> element.

- d. *The standard defines the attribute height, contained within the element <mspace>*

This attribute is supported in Word 2013 and later.

On load, Word reads the height attribute in an <mspace> element. An ASCII space is inserted.

On save, Word does not write the <mspace> element.

- e. *The standard defines the attribute id, contained within the element <mspace>*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute linebreak, contained within the element <mspace>*

This attribute is supported in Word 2013 and later.

On load, Word reads the linebreak attribute in an <mspace> element. If the linebreak attribute has the value of "newline" or "indentingnewline" and the following element is <mo> then a break is inserted. Otherwise, the linebreak attribute is ignored.

On save, Word does not write the <mspace> element.

- g. *The standard defines the property "auto | nobreak | goodbreak | badbreak", contained within the attribute linebreak, contained within the element <mspace>*

This property is not supported in Word 2013 or later.

- h. *The standard defines the attribute style, contained within the element <mspace>*

This attribute is not supported in Word 2013 or later.

- i. *The standard defines the attribute width, contained within the element <mspace>*

This attribute is supported in Word 2013 and later.

On load, Word reads the width attribute in an <mspace> element. An ASCII space is inserted.

On save, Word does not write the <mspace> element.

- j. *The standard defines the attribute xref, contained within the element <mspace>*

This attribute is not supported in Word 2013 or later.

- k. *The standard defines the element <mspace>*

This element is supported in Excel 2013 and later.

On load, Excel reads the <mspace> element. On load, the <mspace> element is treated as a space character when width, height or depth are specified.

On save, Excel does not write the <mspace> element.

- l. *The standard defines the attribute class, contained within the element <mspace>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute depth, contained within the element <mspace>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the depth attribute in an <mspace> element. An ASCII space is inserted.

On save, Excel does not write the <mspace> element.

- n. *The standard defines the attribute height, contained within the element <mspace>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the height attribute in an <mspace> element. An ASCII space is inserted.

On save, Excel does not write the <mspace> element.

- o. *The standard defines the attribute id, contained within the element <mspace>*

This attribute is not supported in Excel 2013 or later.

- p. *The standard defines the attribute linebreak, contained within the element <mspace>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the linebreak attribute in an <mspace> element. If the linebreak attribute has the value of "newline" or "indentingnewline" and the following element is <mo> then a break is inserted. Otherwise, the linebreak attribute is ignored.

On save, Excel does not write the <mspace> element.

- q. *The standard defines the property "auto | nobreak | goodbreak | badbreak", contained within the attribute linebreak, contained within the element <mspace>*

This property is not supported in Excel 2013 or later.

- r. *The standard defines the attribute style, contained within the element <mspace>*

This attribute is not supported in Excel 2013 or later.

- s. *The standard defines the attribute width, contained within the element <mspace>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the width attribute in an <mspace> element. An ASCII space is inserted.

On save, Excel does not write the <mspace> element.

- t. *The standard defines the attribute xref, contained within the element <mspace>*

This attribute is not supported in Excel 2013 or later.

- u. *The standard defines the element <mspace>*

This element is supported in PowerPoint 2013 and later.



On load, PowerPoint reads the <mspace> element. On load, the <mspace> element is treated as a space character when width, height, or depth are specified.

On save, PowerPoint does not write the <mspace> element.

- v. *The standard defines the attribute class, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2013 or later.

- w. *The standard defines the attribute depth, contained within the element <mspace>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the depth attribute in an <mspace> element. An ASCII space is inserted.

On save, PowerPoint does not write the <mspace> element.

- x. *The standard defines the attribute height, contained within the element <mspace>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the height attribute in an <mspace> element. An ASCII space is inserted.

On save, PowerPoint does not write the <mspace> element.

- y. *The standard defines the attribute id, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2013 or later.

- z. *The standard defines the attribute linebreak, contained within the element <mspace>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the linebreak attribute in an <mspace> element. If the linebreak attribute has the value of "newline" or "indentingnewline" and the following element is <mo>, then a break is inserted. Otherwise, the linebreak attribute is ignored.

On save, PowerPoint does not write the <mspace> element.

- aa. *The standard defines the property "auto | nobreak | goodbreak | badbreak", contained within the attribute linebreak, contained within the element <mspace>*

This property is not supported in PowerPoint 2013 or later.

- bb. *The standard defines the attribute style, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2013 or later.

- cc. *The standard defines the attribute width, contained within the element <mspace>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the width attribute in an <mspace> element. An ASCII space is inserted.

On save, PowerPoint does not write the <mspace> element.

- dd. *The standard defines the attribute xref, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2013 or later.

## 2.1.332 Part 3 Section 14.6 (MathML 2.0 Section 3.2.8), String Literal (ms)

- a. *The standard defines the element <ms>*

This element is supported in MathML in Word 2013 and later.

On save, MathML in Word saves previously loaded <ms> elements as one or more tokenized elements instead of as a single <ms> element.

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word reads the <ms> element.

On save, OfficeArt Math in Word does not write the <ms> element.

- b. *The standard defines the attribute class, contained within the element <ms>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute color, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the color attribute in an <ms> element. On save, Word does not write the color attribute in an <ms> element.

- d. *The standard defines the attribute fontfamily, contained within the element <ms>*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute fontsize, contained within the element <ms>*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute fontstyle, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontstyle attribute in an <ms> element. On save, Word does not write the fontstyle attribute in an <ms> element.

- g. *The standard defines the attribute fontweight, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontweight attribute in an <ms> element. On save, Word does not write the fontweight attribute in an <ms> element.

- h. *The standard defines the attribute id, contained within the element <ms>*

This attribute is not supported in Word 2013 or later.

- i. *The standard defines the attribute lquote, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the lquote attribute in an <ms> element.

On save, Word does not write the lquote attribute in an <ms> element.

- j. *The standard defines the attribute mathbackground, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the mathbackground attribute in an <ms> element. On save, Word does not write the mathbackground attribute in an <ms> element.

- k. *The standard defines the attribute mathcolor, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the mathcolor attribute in an <ms> element. On save, Word does not write the mathcolor attribute in an <ms> element.

- l. *The standard defines the attribute mathsize, contained within the element <ms>*

This attribute is not supported in Word 2013 or later.

- m. *The standard defines the attribute mathvariant, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the mathvariant attribute in an <ms> element.

On save, Word does not write the mathvariant attribute in an <ms> element. All math alphanumeric characters are written using Unicode code points.

- n. *The standard defines the attribute rquote, contained within the element <ms>*

This attribute is supported in Word 2013 and later.

On load, Word reads the rquote attribute in an <ms> element.

On save, Word does not write the rquote attribute in an <ms> element.

- o. *The standard defines the attribute style, contained within the element <ms>*

This attribute is not supported in Word 2013 or later.

- p. *The standard defines the attribute xref, contained within the element <ms>*

This attribute is not supported in Word 2013 or later.

- q. *The standard defines the element <ms>*

This element is supported in Excel 2013 and later.

On load, Excel reads the <ms> element.

On save, Excel does not write the <ms> element.

- r. *The standard defines the attribute class, contained within the element <ms>*

This attribute is not supported in Excel 2013 or later.

- s. *The standard defines the attribute color, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the color attribute in an <ms> element. On save, Excel does not write the color attribute in an <ms> element.

- t. *The standard defines the attribute fontfamily, contained within the element <ms>*

This attribute is not supported in Excel 2013 or later.

- u. *The standard defines the attribute fontsize, contained within the element <ms>*

This attribute is not supported in Excel 2013 or later.

- v. *The standard defines the attribute fontstyle, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontstyle attribute in an <ms> element. On save, Excel does not write the fontstyle attribute in an <ms> element.

- w. *The standard defines the attribute fontweight, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontweight attribute in an <ms> element. On save, Excel does not write the fontweight attribute in an <ms> element.

- x. *The standard defines the attribute id, contained within the element <ms>*

This attribute is not supported in Excel 2013 or later.

- y. *The standard defines the attribute lquote, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the lquote attribute in an <ms> element.

On save, Excel does not write the lquote attribute in an <ms> element.

- z. *The standard defines the attribute mathbackground, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathbackground attribute in an <ms> element. On save, Excel does not write the mathbackground attribute in an <ms> element.

- aa. *The standard defines the attribute mathcolor, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathcolor attribute in an <ms> element. On save, Excel does not write the mathcolor attribute in an <ms> element.

- bb. *The standard defines the attribute mathsize, contained within the element <ms>*

This attribute is not supported in Excel 2013 or later.

- cc. *The standard defines the attribute mathvariant, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathvariant attribute in an <ms> element.

On save, Excel does not write the mathvariant attribute in an <ms> element. All math alphanumeric characters are written using Unicode code points.

- dd. *The standard defines the attribute rquote, contained within the element <ms>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the rquote attribute in an <ms> element.

On save, Excel does not write the rquote attribute in an <ms> element.

- ee. *The standard defines the attribute style, contained within the element <ms>*  
This attribute is not supported in Excel 2013 or later.
- ff. *The standard defines the attribute xref, contained within the element <ms>*  
This attribute is not supported in Excel 2013 or later.
- gg. *The standard defines the element <ms>*  
This element is supported in PowerPoint 2013 and later.  
On load, PowerPoint reads the <ms> element.  
On save, PowerPoint does not write the <ms> element.
- hh. *The standard defines the attribute class, contained within the element <ms>*  
This attribute is not supported in PowerPoint 2013 or later.
- ii. *The standard defines the attribute color, contained within the element <ms>*  
This attribute is supported in PowerPoint 2013 and later.  
On load, PowerPoint reads the color attribute in an <ms> element. On save, PowerPoint does not write the color attribute in an <ms> element.
- jj. *The standard defines the attribute fontfamily, contained within the element <ms>*  
This attribute is not supported in PowerPoint 2013 or later.
- kk. *The standard defines the attribute fontsize, contained within the element <ms>*  
This attribute is not supported in PowerPoint 2013 or later.
- ll. *The standard defines the attribute fontstyle, contained within the element <ms>*  
This attribute is supported in PowerPoint 2013 and later.  
On load, PowerPoint reads the fontstyle attribute in an <ms> element. On save, PowerPoint does not write the fontstyle attribute in an <ms> element.
- mm. *The standard defines the attribute fontweight, contained within the element <ms>*  
This attribute is supported in PowerPoint 2013 and later.  
On load, PowerPoint reads the fontweight attribute in an <ms> element. On save, PowerPoint does not write the fontweight attribute in an <ms> element.
- nn. *The standard defines the attribute id, contained within the element <ms>*  
This attribute is not supported in PowerPoint 2013 or later.
- oo. *The standard defines the attribute lquote, contained within the element <ms>*  
This attribute is supported in PowerPoint 2013 and later.  
On load, PowerPoint reads the lquote attribute in an <ms> element.  
On save, PowerPoint does not write the lquote attribute in an <ms> element.
- pp. *The standard defines the attribute mathbackground, contained within the element <ms>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathbackground attribute in an <ms> element. On save, PowerPoint does not write the mathbackground attribute in an <ms> element.

qq. *The standard defines the attribute mathcolor, contained within the element <ms>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathcolor attribute in an <ms> element. On save, PowerPoint does not write the mathcolor attribute in an <ms> element.

rr. *The standard defines the attribute mathsize, contained within the element <ms>*

This attribute is not supported in PowerPoint 2013 or later.

ss. *The standard defines the attribute mathvariant, contained within the element <ms>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathvariant attribute in an <ms> element.

On save, PowerPoint does not write the mathvariant attribute in an <ms> element. All math alphanumeric characters are written using Unicode code points.

tt. *The standard defines the attribute rquote, contained within the element <ms>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the rquote attribute in an <ms> element.

On save, PowerPoint does not write the rquote attribute in an <ms> element.

uu. *The standard defines the attribute style, contained within the element <ms>*

This attribute is not supported in PowerPoint 2013 or later.

vv. *The standard defines the attribute xref, contained within the element <ms>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.333 Part 3 Section 14.6 (MathML 2.0 Section 3.2.9), Accessing glyphs for characters from MathML (mglyph)**

a. *The standard defines the element <mglyph>*

This element is supported in MathML in Word 2013 and later.

ON SAVE, MathML in Word will never write <mglyph>.

ON LOAD, MathML in Word will replace the <mglyph> with the value of the alt attribute as normal text. The fontfamily and index attributes will be dropped.

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word, reads content only from the alt attribute of the mglyph element. Specifying glyphs directly is not supported.

On save, OfficeArt Math in Word does not write the <mglyph> element.

b. *The standard defines the attribute alt, contained within the element <mglyph>*

This attribute is supported in Word 2013 and later.

On load, Word reads the alt attribute in an <mglyph> element. The value of the alt attribute is inserted as text.

On save, Word does not write the alt attribute in an <mglyph> element.

- c. *The standard defines the attribute class, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute color, contained within the element <mglyph>*

This attribute is supported in Word 2013 and later.

On load, Word reads the color attribute in an <mglyph> element. On save, Word does not write the color attribute in an <mglyph> element.

- e. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute fontsize, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- g. *The standard defines the attribute fontstyle, contained within the element <mglyph>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontstyle attribute in an <mglyph> element. On save, Word does not write the fontstyle attribute in an <mglyph> element.

- h. *The standard defines the attribute fontweight, contained within the element <mglyph>*

This attribute is supported in Word 2013 and later.

On load, Word reads the fontweight attribute in an <mglyph> element. On save, Word does not write the fontweight attribute in an <mglyph> element.

- i. *The standard defines the attribute id, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- j. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- k. *The standard defines the attribute mathbackground, contained within the element <mglyph>*

This attribute is supported in Word 2013 and later.

On load, Word reads the mathbackground attribute in an <mglyph> element. On save, Word does not write the mathbackground attribute in an <mglyph> element.

- l. *The standard defines the attribute mathcolor, contained within the element <mglyph>*

This attribute is supported in Word 2013 and later.

On load, Word reads the mathcolor attribute in an <mglyph> element. On save, Word does not write the mathcolor attribute in an <mglyph> element.

- m. *The standard defines the attribute mathsize, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- n. *The standard defines the attribute style, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- o. *The standard defines the attribute xref, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- p. *The standard defines the element <mglyph>*

This element is supported in Excel 2013 and later.

On load, Excel, reads content only from the alt attribute of the mglyph element. Specifying glyphs directly is not supported.

On save, Excel does not write the <mglyph> element.

- q. *The standard defines the attribute alt, contained within the element <mglyph>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the alt attribute in an <mglyph> element. The value of the alt attribute is inserted as text.

On save, Excel does not write the alt attribute in an <mglyph> element.

- r. *The standard defines the attribute class, contained within the element <mglyph>*

This attribute is not supported in Excel 2013 or later.

- s. *The standard defines the attribute color, contained within the element <mglyph>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the color attribute in an <mglyph> element. On save, Excel does not write the color attribute in an <mglyph> element.

- t. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in Excel 2013 or later.

- u. *The standard defines the attribute fontsize, contained within the element <mglyph>*

This attribute is not supported in Excel 2013 or later.

- v. *The standard defines the attribute fontstyle, contained within the element <mglyph>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontstyle attribute in an <mglyph> element. On save, Excel does not write the fontstyle attribute in an <mglyph> element.

- w. *The standard defines the attribute fontweight, contained within the element <mglyph>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the fontweight attribute in an <mglyph> element. On save, Excel does not write the fontweight attribute in an <mglyph> element.

- x. *The standard defines the attribute id, contained within the element <mglyph>*



This attribute is not supported in Excel 2013 or later.

- y. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in Excel 2013 or later.

- z. *The standard defines the attribute mathbackground, contained within the element <mglyph>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathbackground attribute in an <mglyph> element. On save, Excel does not write the mathbackground attribute in an <mglyph> element.

- aa. *The standard defines the attribute mathcolor, contained within the element <mglyph>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the mathcolor attribute in an <mglyph> element. On save, Excel does not write the mathcolor attribute in an <mglyph> element.

- bb. *The standard defines the attribute mathsize, contained within the element <mglyph>*

This attribute is not supported in Excel 2013 or later.

- cc. *The standard defines the attribute mathvariant, contained within the element <mglyph>*

This attribute is supported in Excel 2013 and later.

- dd. *The standard defines the attribute style, contained within the element <mglyph>*

This attribute is not supported in Excel 2013 or later.

- ee. *The standard defines the attribute xref, contained within the element <mglyph>*

This attribute is not supported in Excel 2013 or later.

- ff. *The standard defines the element <mglyph>*

This element is supported in PowerPoint 2013 and later.

On load, PowerPoint, reads content only from the alt attribute of the mglyph element. Specifying glyphs directly is not supported.

On save, PowerPoint does not write the <mglyph> element.

- gg. *The standard defines the attribute alt, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the alt attribute in an <mglyph> element. The value of the alt attribute is inserted as text.

On save, PowerPoint does not write the alt attribute in an <mglyph> element.

- hh. *The standard defines the attribute class, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

- ii. *The standard defines the attribute color, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the color attribute in an <mglyph> element. On save, PowerPoint does not write the color attribute in an <mglyph> element.

jj. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

kk. *The standard defines the attribute fontsize, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

ll. *The standard defines the attribute fontstyle, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontstyle attribute in an <mglyph> element. On save, PowerPoint does not write the fontstyle attribute in an <mglyph> element.

mm. *The standard defines the attribute fontweight, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the fontweight attribute in an <mglyph> element. On save, PowerPoint does not write the fontweight attribute in an <mglyph> element.

nn. *The standard defines the attribute id, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

oo. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

pp. *The standard defines the attribute mathbackground, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathbackground attribute in an <mglyph> element. On save, PowerPoint does not write the mathbackground attribute in an <mglyph> element.

qq. *The standard defines the attribute mathcolor, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the mathcolor attribute in an <mglyph> element. On save, PowerPoint does not write the mathcolor attribute in an <mglyph> element.

rr. *The standard defines the attribute mathsize, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

ss. *The standard defines the attribute style, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

tt. *The standard defines the attribute xref, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.334 Part 3 Section 14.6 (MathML 2.0 Section 3.2.9.2), Accessing glyphs for characters from MathML (mglyph)**

- a. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in Word 2013 or later.

### **2.1.335 Part 3 Section 14.6 (MathML 2.0 Section 3.3.1), Horizontally Group Sub-Expressions (mrow)**

- a. *The standard defines the element <mrow>*

This element is supported in MathML in Word 2013 and later.

On load, MathML in Word supports the use of the <mrow> element with or without attributes. MathML in Word ignores any attributes that are present.

On save, MathML in Word may write more <mrow> elements than are strictly necessary.

This element is supported in **OfficeArt Math** in Word 2013 and later.

- b. *The standard defines the attribute class, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- c. *The standard defines the attribute id, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute style, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute xref, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the element <mrow>*

This element is supported in Excel 2013 and later.

- g. *The standard defines the attribute class, contained within the element <mrow>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute id, contained within the element <mrow>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute style, contained within the element <mrow>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute xref, contained within the element <mrow>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the element <mrow>*

This element is supported in PowerPoint 2013 and later.

- l. *The standard defines the attribute class, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2013 or later.

- m. *The standard defines the attribute id, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2013 or later.

- n. *The standard defines the attribute style, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2013 or later.

- o. *The standard defines the attribute xref, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.336 Part 3 Section 14.6 (MathML 2.0 Section 3.3.2), Fractions (mfrac)**

- a. *The standard defines the element <mfrac>*

This element is supported in Word 2013 and later.

- b. *The standard defines the attribute bevelled, contained within the element <mfrac>*

This attribute is supported in Word 2013 and later.

- c. *The standard defines the attribute class, contained within the element <mfrac>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

- d. *The standard defines the attribute denomalign, contained within the element <mfrac>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute id, contained within the element <mfrac>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute linethickness, contained within the element <mfrac>*

This attribute is supported in MathML in Word 2013 and later.

Fraction bars in MathML in Word are either displayed or not displayed.

On load, MathML in Word displays a fraction bar if the linethickness attribute has a value of "thin", "medium", "thick", any nonzero digit, or is empty. In all other cases, no fraction bar is displayed.

This attribute is supported in OfficeArt Math in Word 2013 and later.

Fraction bars in OfficeArt Math in Word are either displayed or not displayed.

On load, OfficeArt Math in Word displays a fraction bar unless linethickness is zero and the fraction is not of the bevelled style.

On save, OfficeArt Math in Word either writes a value of '0' or omits this attribute.

- g. *The standard defines the attribute numalign, contained within the element <mfrac>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the attribute style, contained within the element <mfrac>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the attribute xref, contained within the element <mfrac>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- j. *The standard defines the element <mfrac>*

This element is supported in Excel 2013 and later.

- k. *The standard defines the attribute bevelled, contained within the element <mfrac>*

This attribute is supported in Excel 2013 and later.

- l. *The standard defines the attribute class, contained within the element <mfrac>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute denomalign, contained within the element <mfrac>*

This attribute is not supported in Excel 2013 or later.

- n. *The standard defines the attribute id, contained within the element <mfrac>*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the attribute linethickness, contained within the element <mfrac>*

This attribute is supported in Excel 2013 and later.

Fraction bars in Excel are either displayed or not displayed.

On load, Excel displays a fraction bar unless linethickness is zero and the fraction is not of the bevelled style.

On save, Excel either writes a value of '0' or omits this attribute.

- p. *The standard defines the attribute numalign, contained within the element <mfrac>*

This attribute is not supported in Excel 2013 or later.

- q. *The standard defines the attribute style, contained within the element <mfrac>*

This attribute is not supported in Excel 2013 or later.

- r. *The standard defines the attribute xref, contained within the element <mfrac>*

This attribute is not supported in Excel 2013 or later.

- s. *The standard defines the element <mfrac>*

This element is supported in PowerPoint 2013 and later.

- t. *The standard defines the attribute bevelled, contained within the element <mfrac>*

This attribute is supported in PowerPoint 2013 and later.

- u. *The standard defines the attribute class, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2013 or later.

- v. *The standard defines the attribute denomalign, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2013 or later.

- w. *The standard defines the attribute id, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2013 or later.

- x. *The standard defines the attribute linethickness, contained within the element <mfrac>*

This attribute is supported in PowerPoint 2013 and later.

Fraction bars in PowerPoint are either displayed or not displayed.

On load, PowerPoint displays a fraction bar unless the linethickness attribute is zero and the fraction is not of the bevelled style.

On save, PowerPoint either writes a value of '0' or omits this attribute.

- y. *The standard defines the attribute numalign, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2013 or later.

- z. *The standard defines the attribute style, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2013 or later.

- aa. *The standard defines the attribute xref, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.337 Part 3 Section 14.6 (MathML 2.0 Section 3.3.3), Radicals (msqrt, mroot)**

- a. *The standard defines the element <mroot>*

This element is supported in Word 2013 and later.

- b. *The standard defines the attribute class, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

- c. *The standard defines the attribute id, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute style, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute xref, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the element <msqrt>*

This element is supported in Word 2013 and later.

- g. *The standard defines the attribute class, contained within the element <msqrt>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the attribute id, contained within the element <msqrt>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the attribute style, contained within the element <msqrt>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- j. *The standard defines the attribute xref, contained within the element <msqrt>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- k. *The standard defines the element <mroot>*

This element is supported in Excel 2013 and later.

- l. *The standard defines the attribute class, contained within the element <mroot>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute id, contained within the element <mroot>*

This attribute is not supported in Excel 2013 or later.

- n. *The standard defines the attribute style, contained within the element <mroot>*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the attribute xref, contained within the element <mroot>*

This attribute is not supported in Excel 2013 or later.

- p. *The standard defines the element <msqrt>*  
This element is supported in Excel 2013 and later.
- q. *The standard defines the attribute class, contained within the element <msqrt>*  
This attribute is not supported in Excel 2013 or later.
- r. *The standard defines the attribute id, contained within the element <msqrt>*  
This attribute is not supported in Excel 2013 or later.
- s. *The standard defines the attribute style, contained within the element <msqrt>*  
This attribute is not supported in Excel 2013 or later.
- t. *The standard defines the attribute xref, contained within the element <msqrt>*  
This attribute is not supported in Excel 2013 or later.
- u. *The standard defines the element <mroot>*  
This element is supported in PowerPoint 2013 and later.
- v. *The standard defines the attribute class, contained within the element <mroot>*  
This attribute is not supported in PowerPoint 2013 or later.
- w. *The standard defines the attribute id, contained within the element <mroot>*  
This attribute is not supported in PowerPoint 2013 or later.
- x. *The standard defines the attribute style, contained within the element <mroot>*  
This attribute is not supported in PowerPoint 2013 or later.
- y. *The standard defines the attribute xref, contained within the element <mroot>*  
This attribute is not supported in PowerPoint 2013 or later.
- z. *The standard defines the element <msqrt>*  
This element is supported in PowerPoint 2013 and later.
- aa. *The standard defines the attribute class, contained within the element <msqrt>*  
This attribute is not supported in PowerPoint 2013 or later.
- bb. *The standard defines the attribute id, contained within the element <msqrt>*  
This attribute is not supported in PowerPoint 2013 or later.
- cc. *The standard defines the attribute style, contained within the element <msqrt>*  
This attribute is not supported in PowerPoint 2013 or later.
- dd. *The standard defines the attribute xref, contained within the element <msqrt>*  
This attribute is not supported in PowerPoint 2013 or later.



## 2.1.338 Part 3 Section 14.6 (MathML 2.0 Section 3.3.4), Style Change (mstyle)

- a. *The standard defines the element <mstyle>*

This element is supported in MathML in Word 2013 and later.

MathML in Word supports only the scriptlevel attribute of the <mstyle> element.

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word reads the <mstyle> element.

On save, OfficeArt Math in Word does not write the <mstyle> element.

- b. *The standard defines the attribute background, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- c. *The standard defines the attribute class, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute color, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the color attribute in an <mstyle> element. On save, OfficeArt Math in Word does not write the color attribute in an <mstyle> element.

- e. *The standard defines the attribute displaystyle, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute id, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the attribute mathcolor, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the mathcolor attribute in an <mstyle> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mstyle> element.

- h. *The standard defines the attribute mediummathspace, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the attribute scriptlevel, contained within the element <mstyle>*

This attribute is not supported in Word 2013 or later.

- j. *The standard defines the attribute `scriptminsize`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- k. *The standard defines the attribute `scriptsizemultiplier`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- l. *The standard defines the attribute `style`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- m. *The standard defines the attribute `thickmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- n. *The standard defines the attribute `thinmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- o. *The standard defines the attribute `verythickmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- p. *The standard defines the attribute `verythinmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- q. *The standard defines the attribute `veryverythickmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- r. *The standard defines the attribute `veryverythinmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- s. *The standard defines the attribute `xref`, contained within the element `<mstyle>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- t. *The standard defines the element <mstyle>*  
This element is supported in Excel 2013 and later.  
On load, Excel reads the <mstyle> element.  
On save, Excel does not write the <mstyle> element.
- u. *The standard defines the attribute background, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- v. *The standard defines the attribute class, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- w. *The standard defines the attribute color, contained within the element <mstyle>*  
This attribute is supported in Excel 2013 and later.  
On load, Excel reads the color attribute in an <mstyle> element. On save, Excel does not write the color attribute in an <mstyle> element.
- x. *The standard defines the attribute displaystyle, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- y. *The standard defines the attribute id, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- z. *The standard defines the attribute mathcolor, contained within the element <mstyle>*  
This attribute is supported in Excel 2013 and later.  
On load, Excel reads the mathcolor attribute in an <mstyle> element. On save, Excel does not write the mathcolor attribute in an <mstyle> element.
- aa. *The standard defines the attribute mediummathspace, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- bb. *The standard defines the attribute scriptlevel, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- cc. *The standard defines the attribute scriptminsize, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- dd. *The standard defines the attribute scriptsizemultiplier, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- ee. *The standard defines the attribute style, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- ff. *The standard defines the attribute thickmathspace, contained within the element <mstyle>*  
This attribute is not supported in Excel 2013 or later.
- gg. *The standard defines the attribute thinmathspace, contained within the element <mstyle>*

This attribute is not supported in Excel 2013 or later.

hh. *The standard defines the attribute `verythickmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in Excel 2013 or later.

ii. *The standard defines the attribute `verythinmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in Excel 2013 or later.

jj. *The standard defines the attribute `veryverythickmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in Excel 2013 or later.

kk. *The standard defines the attribute `veryverythinmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in Excel 2013 or later.

ll. *The standard defines the attribute `xref`, contained within the element `<mstyle>`*

This attribute is not supported in Excel 2013 or later.

mm. *The standard defines the element `<mstyle>`*

This element is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the `<mstyle>` element.

On save, PowerPoint does not write the `<mstyle>` element.

nn. *The standard defines the attribute `background`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2013 or later.

oo. *The standard defines the attribute `class`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2013 or later.

pp. *The standard defines the attribute `color`, contained within the element `<mstyle>`*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the `color` attribute in an `<mstyle>` element. On save, PowerPoint does not write the `color` attribute in an `<mstyle>` element.

qq. *The standard defines the attribute `displaystyle`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2013 or later.

rr. *The standard defines the attribute `id`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2013 or later.

ss. *The standard defines the attribute `mathcolor`, contained within the element `<mstyle>`*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the `mathcolor` attribute in an `<mstyle>` element. On save, PowerPoint does not write the `mathcolor` attribute in an `<mstyle>` element.

tt. *The standard defines the attribute `mediummathspace`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2013 or later.

uu. *The standard defines the attribute scriptlevel, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

vv. *The standard defines the attribute scriptminsize, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

ww. *The standard defines the attribute scriptsizemultiplier, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

xx. *The standard defines the attribute style, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

yy. *The standard defines the attribute thickmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

zz. *The standard defines the attribute thinmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

aaa. *The standard defines the attribute verythickmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

bbb. *The standard defines the attribute verythinmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

ccc. *The standard defines the attribute veryverythickmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

ddd. *The standard defines the attribute veryverythinmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

eee. *The standard defines the attribute xref, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.339 Part 3 Section 14.6 (MathML 2.0 Section 3.3.5), Error Message (merror)**

a. *The standard defines the element <merror>*

This element is not supported in MathML in Word 2013 or later.

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word reads the <merror> element. On save, OfficeArt Math in Word does not write the <merror> element.

b. *The standard defines the attribute class, contained within the element <merror>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute id, contained within the element <merror>*  
This attribute is not supported in Word 2013 or later.
- d. *The standard defines the attribute style, contained within the element <merror>*  
This attribute is not supported in Word 2013 or later.
- e. *The standard defines the attribute xref, contained within the element <merror>*  
This attribute is not supported in Word 2013 or later.
- f. *The standard defines the element <merror>*  
This element is supported in Excel 2013 and later.  
  
On load, Excel reads the <merror> element. On save, Excel does not write the <merror> element.
- g. *The standard defines the attribute class, contained within the element <merror>*  
This attribute is not supported in Excel 2013 or later.
- h. *The standard defines the attribute id, contained within the element <merror>*  
This attribute is not supported in Excel 2013 or later.
- i. *The standard defines the attribute style, contained within the element <merror>*  
This attribute is not supported in Excel 2013 or later.
- j. *The standard defines the attribute xref, contained within the element <merror>*  
This attribute is not supported in Excel 2013 or later.
- k. *The standard defines the element <merror>*  
This element is supported in PowerPoint 2013 and later.  
  
On load, PowerPoint reads the <merror> element. On save, PowerPoint does not write the <merror> element.
- l. *The standard defines the attribute class, contained within the element <merror>*  
This attribute is not supported in PowerPoint 2013 or later.
- m. *The standard defines the attribute id, contained within the element <merror>*  
This attribute is not supported in PowerPoint 2013 or later.
- n. *The standard defines the attribute style, contained within the element <merror>*  
This attribute is not supported in PowerPoint 2013 or later.
- o. *The standard defines the attribute xref, contained within the element <merror>*  
This attribute is not supported in PowerPoint 2013 or later.

### **2.1.340 Part 3 Section 14.6 (MathML 2.0 Section 3.3.6), Adjust Space Around Content (mpadded)**

- a. *The standard defines the element <mpadded>*

This element is supported in MathML in Word 2013 and later.

On save, to make a phantom visible, MathML in Word uses an `<mpadded>` element only (not `<mphantom>`). This is true whether the object is smashed or not.

On save, to make a phantom invisible with no smashing, MathML in Word uses an `<mphantom>` element only (not `<mpadded>`).

On save, to make a phantom invisible with smashing, MathML in Word uses an `<mpadded>` element nested inside an `<mphantom>` element.

On save, MathML in Word converts any smashing into the appropriate attribute for the `<mpadded>` element and sets the value of the attribute to "0in" (for example, the OOXML construct `<m:zeroWid m:val="on" />` maps to the MathML attribute `width="0in"`).

On load, MathML in Word maps an `<mphantom>` element to an `<omml:phant>` element. Furthermore, if the `<mphantom>` element has exactly one child element and that child is an `<mpadded>` element, MathML in Word converts the `<mpadded>` element's attributes the appropriate MathML in Word smash properties (`zeroWid`, `zeroDesc`, `zeroAsc`) as specified in Note 6).

On load, MathML in Word converts the width, height, and depth attributes of the `<mpadded>` element into MathML in Word phantom properties `zeroWid`, `zeroAsc`, and `zeroDesc`, respectively.

Unless an `<mpadded>` element is the sole child of an `<mphantom>` element (in which case it would be handled by note 5), MathML in Word maps it to a MathML in Word `<phant>` element with the `show` property set to true.

This element is supported in **OfficeArt Math** in Word 2013 and later.

Padding in OfficeArt Math in Word is either normal or collapsed in any dimension.

On load, OfficeArt Math in Word displays elements with normal dimensions unless depth, height or width are set to '0', in which case they are collapsed in the corresponding dimension.

On save, OfficeArt Math in Word either writes a value of '0' or omits an attribute in the `<mpadded>` element.

b. *The standard defines the attribute class, contained within the element `<mpadded>`*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

c. *The standard defines the attribute depth, contained within the element `<mpadded>`*

This attribute is supported in MathML in Word 2013 and later.

On load, MathML in Word uses the depth attribute to specify the vertical smashing below the baseline. Values containing one numeric digit, all of which are the digit zero, specify that smashing in this direction is on, otherwise smashing is off.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the depth attribute in an `<mpadded>` element.

On save, OfficeArt Math in Word either writes a value of '0' or omits the depth attribute in the `<mpadded>` element.

d. *The standard defines the attribute height, contained within the element `<mpadded>`*

This attribute is supported in MathML in Word 2013 and later.

This attribute specifies vertical smashing above the baseline. A value of zero specifies that smashing has a value of "off", or the height dimension of the object has a value of zero. Nonzero values specify that smashing has a value of "on", or the height dimension of the object is nonzero.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the height attribute in an <mpadded> element.

On save, OfficeArt Math in Word either writes a value of '0' or omits the height attribute in the <mpadded> element.

- e. *The standard defines the attribute id, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute lspace, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the attribute style, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the attribute width, contained within the element <mpadded>*

This attribute is supported in MathML in Word 2013 and later.

A value of zero specifies that smashing has a value of "off", or the width dimension of the object has a value of zero. Nonzero values specify that smashing has a value of "on", or the width dimension of the object is nonzero.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the width attribute in an <mpadded> element.

On save, OfficeArt Math in Word either writes a value of '0' or omits the width attribute in the <mpadded> element.

- i. *The standard defines the attribute xref, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- j. *The standard defines the element <mpadded>*

This element is supported in Excel 2013 and later.

Padding in Excel is either normal or collapsed in any dimension.

On load, Excel displays elements with normal dimensions unless depth, height or width are set to '0', in which case they are collapsed in the corresponding dimension.

On save, Excel either writes a value of '0' or omits an attribute in the <mpadded> element.

- k. *The standard defines the attribute class, contained within the element <mpadded>*



This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute depth, contained within the element <mpadded>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the depth attribute in an <mpadded> element.

On save, Excel either writes a value of '0' or omits the depth attribute in the <mpadded> element.

- m. *The standard defines the attribute height, contained within the element <mpadded>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the height attribute in an <mpadded> element.

On save, Excel either writes a value of '0' or omits the height attribute in the <mpadded> element.

- n. *The standard defines the attribute id, contained within the element <mpadded>*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the attribute lspace, contained within the element <mpadded>*

This attribute is not supported in Excel 2013 or later.

- p. *The standard defines the attribute style, contained within the element <mpadded>*

This attribute is not supported in Excel 2013 or later.

- q. *The standard defines the attribute width, contained within the element <mpadded>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the width attribute in an <mpadded> element.

On save, Excel either writes a value of '0' or omits the width attribute in the <mpadded> element.

- r. *The standard defines the attribute xref, contained within the element <mpadded>*

This attribute is not supported in Excel 2013 or later.

- s. *The standard defines the element <mpadded>*

This element is supported in PowerPoint 2013 and later.

Padding in PowerPoint is either normal or collapsed in any dimension.

On load, PowerPoint displays elements with normal dimensions unless depth, height or width are set to '0', in which case they are collapsed in the corresponding dimension.

On save, PowerPoint either writes a value of '0' or omits an attribute in the <mpadded> element.

- t. *The standard defines the attribute class, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2013 or later.

- u. *The standard defines the attribute depth, contained within the element <mpadded>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the depth attribute in an <mpadded> element.

On save, PowerPoint either writes a value of '0' or omits the depth attribute in the <mpadded> element.

- v. *The standard defines the attribute height, contained within the element <mpadded>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the height attribute in an <mpadded> element.

On save, PowerPoint either writes a value of '0' or omits the height attribute in the <mpadded> element.

- w. *The standard defines the attribute id, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2013 or later.

- x. *The standard defines the attribute lspace, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2013 or later.

- y. *The standard defines the attribute style, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2013 or later.

- z. *The standard defines the attribute width, contained within the element <mpadded>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the width attribute in an <mpadded> element.

On save, PowerPoint either writes a value of '0' or omits the width attribute in the <mpadded> element.

- aa. *The standard defines the attribute xref, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.341 Part 3 Section 14.6 (MathML 2.0 Section 3.3.7), Making Sub-Expressions Invisible (mphantom)**

- a. *The standard defines the element <mphantom>*

This element is supported in MathML in Word 2013 and later.

On save, to make a phantom visible, MathML in Word uses an <mpadded> element only (not <mphantom>). This is true whether the object is smashed or not.

On save, to make a phantom invisible with no smashing, MathML in Word uses an <mphantom> element only (not <mpadded>).

On save, to make a phantom invisible with smashing, MathML in Word uses an <mpadded> element nested inside an <mphantom> element.

On save, MathML in Word converts any smashing into the appropriate attribute of an <mpadded> element and sets the value to "0in". (For example, the OOXML construct <m:zeroWid m:val="on" /> maps to the MathML attribute width="0in").

On load, MathML in Word maps an <mphantom> element to a MathML in Word <omml:phant> element. Furthermore, if the <mphantom> element has exactly one child element and that child is an <mpadded> element, MathML in Word converts the <mpadded> element's attributes into MathML in Word smash properties (zeroWid, zeroDesc, zeroAsc) as specified in Note 6.

On load, MathML in Word converts the width, height, and depth attributes of the <mpadded> element into MathML in Word phantom properties zeroWid, zeroAsc, and zeroDesc, respectively.

Unless an <mpadded> element is the sole child of an <mphantom> element (in which case it would be handled by note 5), MathML in Word maps it to a MathML in Word <phant> element with the show attribute set to true.

This element is supported in **OfficeArt Math** in Word 2013 and later.

- b. *The standard defines the attribute class, contained within the element <mphantom>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- c. *The standard defines the attribute id, contained within the element <mphantom>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute style, contained within the element <mphantom>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute xref, contained within the element <mphantom>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the element <mphantom>*

This element is supported in Excel 2013 and later.

- g. *The standard defines the attribute class, contained within the element <mphantom>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute id, contained within the element <mphantom>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute style, contained within the element <mphantom>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute xref, contained within the element <mphantom>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the element <mphantom>*

This element is supported in PowerPoint 2013 and later.

- l. *The standard defines the attribute class, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2013 or later.

- m. *The standard defines the attribute id, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2013 or later.

- n. *The standard defines the attribute style, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2013 or later.

- o. *The standard defines the attribute xref, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.342 Part 3 Section 14.6 (MathML 2.0 Section 3.3.8), Expression Inside Pair of Fences (mfenced)**

- a. *The standard defines the element <mfenced>*

This element is supported in Word 2013 and later.

- b. *The standard defines the attribute class, contained within the element <mfenced>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

- c. *The standard defines the attribute close, contained within the element <mfenced>*

This attribute is supported in Word 2013 and later.

- d. *The standard defines the attribute id, contained within the element <mfenced>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute open, contained within the element <mfenced>*

This attribute is supported in Word 2013 and later.

- f. *The standard defines the attribute separators, contained within the element <mfenced>*

This attribute is supported in MathML in Word 2013 and later.

On load, MathML in Word only uses the first separator that is specified and discards all others. On save, MathML in Word only writes out a single separator.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the separators attribute in an <mfenced> element and uses only the first separator.

On save, OfficeArt Math in Word writes the separators attribute with a single separator in an <mfenced> element.

- g. *The standard defines the attribute style, contained within the element <mfenced>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the attribute xref, contained within the element <mfenced>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the element <mfenced>*

This element is supported in Excel 2013 and later.

- j. *The standard defines the attribute class, contained within the element <mfenced>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute close, contained within the element <mfenced>*

This attribute is supported in Excel 2013 and later.

- l. *The standard defines the attribute id, contained within the element <mfenced>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute open, contained within the element <mfenced>*

This attribute is supported in Excel 2013 and later.

- n. *The standard defines the attribute separators, contained within the element <mfenced>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the separators attribute in an <mfenced> element and uses only the first separator.

On save, Excel writes the separators attribute with a single separator in an <mfenced> element.

- o. *The standard defines the attribute style, contained within the element <mfenced>*

This attribute is not supported in Excel 2013 or later.

- p. *The standard defines the attribute xref, contained within the element <mfenced>*

This attribute is not supported in Excel 2013 or later.

- q. *The standard defines the element <mfenced>*

This element is supported in PowerPoint 2013 and later.

- r. *The standard defines the attribute class, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2013 or later.

- s. *The standard defines the attribute close, contained within the element <mfenced>*

This attribute is supported in PowerPoint 2013 and later.

- t. *The standard defines the attribute id, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2013 or later.

- u. *The standard defines the attribute open, contained within the element <mfenced>*

This attribute is supported in PowerPoint 2013 and later.

- v. *The standard defines the attribute separators, contained within the element <mfenced>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the separators attribute in an <mfenced> element and uses only the first separator.

On save, PowerPoint writes the separators attribute with a single separator in an <mfenced> element.

- w. *The standard defines the attribute style, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2013 or later.

- x. *The standard defines the attribute xref, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.343 Part 3 Section 14.6 (MathML 2.0 Section 3.3.9), Enclose Expression Inside Notation (menclose)**

- a. *The standard defines the element <menclose>*

This element is supported in Word 2013 and later.

- b. *The standard defines the attribute class, contained within the element <menclose>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

- c. *The standard defines the attribute id, contained within the element <menclose>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute notation, contained within the element <menclose>*

This attribute is supported in Word 2013 and later.

- e. *The standard defines the property "(everything else)", contained within the attribute notation, contained within the element <menclose>*

This property is supported in Word 2013 and later.

- f. *The standard defines the property "actuarial", contained within the attribute notation, contained within the element <menclose>*

This property is not supported in MathML in Word 2013 or later.

This property is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the property "circle", contained within the attribute notation, contained within the element <menclose>*

This property is supported in MathML in Word 2013 and later.

On load, MathML in Word converts a value of "circle" to the value of "box".

This property is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the property "longdiv", contained within the attribute notation, contained within the element <menclose>*

This property is not supported in MathML in Word 2013 or later.

This property is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the property "none", contained within the attribute notation, contained within the element <menclase>*

This property is supported in Word 2013 and later.

On load, Word reads the 'none' value of the notation attribute as a box with invisible borders.

On save, Word writes the notation, 'none' to denote a box with invisible borders.

- j. *The standard defines the property "radical", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in Word 2013 or later.

- k. *The standard defines the property "roundedbox", contained within the attribute notation, contained within the element <menclase>*

This property is supported in MathML in Word 2013 and later.

On load, MathML in Word converts the value "roundedbox" to the value "box".

This property is not supported in OfficeArt Math in Word 2013 or later.

- l. *The standard defines the attribute style, contained within the element <menclase>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- m. *The standard defines the attribute xref, contained within the element <menclase>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- n. *The standard defines the element <menclase>*

This element is supported in Excel 2013 and later.

- o. *The standard defines the attribute class, contained within the element <menclase>*

This attribute is not supported in Excel 2013 or later.

- p. *The standard defines the attribute id, contained within the element <menclase>*

This attribute is not supported in Excel 2013 or later.

- q. *The standard defines the attribute notation, contained within the element <menclase>*

This attribute is supported in Excel 2013 and later.

- r. *The standard defines the property "(everything else)", contained within the attribute notation, contained within the element <menclase>*

This property is supported in Excel 2013 and later.

- s. *The standard defines the property "actuarial", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in Excel 2013 or later.

- t. *The standard defines the property "circle", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in Excel 2013 or later.

- u. *The standard defines the property "longdiv", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in Excel 2013 or later.

- v. *The standard defines the property "none", contained within the attribute notation, contained within the element <menclase>*

This property is supported in Excel 2013 and later.

On load, Excel reads the 'none' value of the notation attribute as a box with invisible borders.

On save, Excel writes the notation, 'none' to denote a box with invisible borders.

- w. *The standard defines the property "radical", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in Excel 2013 or later.

- x. *The standard defines the property "roundedbox", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in Excel 2013 or later.

- y. *The standard defines the attribute style, contained within the element <menclase>*

This attribute is not supported in Excel 2013 or later.

- z. *The standard defines the attribute xref, contained within the element <menclase>*

This attribute is not supported in Excel 2013 or later.

- aa. *The standard defines the element <menclase>*

This element is supported in PowerPoint 2013 and later.

- bb. *The standard defines the attribute class, contained within the element <menclase>*

This attribute is not supported in PowerPoint 2013 or later.

- cc. *The standard defines the attribute id, contained within the element <menclase>*

This attribute is not supported in PowerPoint 2013 or later.

- dd. *The standard defines the attribute notation, contained within the element <menclase>*

This attribute is supported in PowerPoint 2013 and later.

- ee. *The standard defines the property "(everything else)", contained within the attribute notation, contained within the element <menclase>*

This property is supported in PowerPoint 2013 and PowerPoint 2016.

- ff. *The standard defines the property "actuarial", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2013 or later.



gg. *The standard defines the property "circle", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2013 or later.

hh. *The standard defines the property "longdiv", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2013 or later.

ii. *The standard defines the property "none", contained within the attribute notation, contained within the element <menclase>*

This property is supported in PowerPoint 2013 and PowerPoint 2016.

On load, PowerPoint reads the 'none' value of the notation attribute as a box with invisible borders.

On save, PowerPoint writes the notation, 'none' to denote a box with invisible borders.

jj. *The standard defines the property "radical", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2013 or later.

On load, PowerPoint reads the 'radical' value of the notation attribute in an <menclase> element.

On save, PowerPoint does not write the 'radical' value of the notation attribute in an <menclase> element.

kk. *The standard defines the property "roundedbox", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2013 or later.

ll. *The standard defines the attribute style, contained within the element <menclase>*

This attribute is not supported in PowerPoint 2013 or later.

mm. *The standard defines the attribute xref, contained within the element <menclase>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.344 Part 3 Section 14.6 (MathML 2.0 Section 3.4.1), Subscript (msub)**

a. *The standard defines the element <msub>*

This element is supported in Word 2013 and later.

b. *The standard defines the attribute class, contained within the element <msub>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

c. *The standard defines the attribute id, contained within the element <msub>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

d. *The standard defines the attribute style, contained within the element <msub>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute subscriptshift, contained within the element <msub>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute xref, contained within the element <msub>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the element <msub>*

This element is supported in Excel 2013 and later.

- h. *The standard defines the attribute class, contained within the element <msub>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute id, contained within the element <msub>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute style, contained within the element <msub>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute subscriptshift, contained within the element <msub>*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute xref, contained within the element <msub>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the element <msub>*

This element is supported in PowerPoint 2013 and later.

- n. *The standard defines the attribute class, contained within the element <msub>*

This attribute is not supported in PowerPoint 2013 or later.

- o. *The standard defines the attribute id, contained within the element <msub>*

This attribute is not supported in PowerPoint 2013 or later.

- p. *The standard defines the attribute style, contained within the element <msub>*

This attribute is not supported in PowerPoint 2013 or later.

- q. *The standard defines the attribute subscriptshift, contained within the element <msub>*

This attribute is not supported in PowerPoint 2013 or later.

- r. *The standard defines the attribute xref, contained within the element <msub>*

This attribute is not supported in PowerPoint 2013 or later.

## 2.1.345 Part 3 Section 14.6 (MathML 2.0 Section 3.4.2), Superscript (msup)

- a. *The standard defines the element <msup>*  
This element is supported in Word 2013 and later.
- b. *The standard defines the attribute class, contained within the element <msup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in **OfficeArt Math** in Word 2013 or later.
- c. *The standard defines the attribute id, contained within the element <msup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- d. *The standard defines the attribute style, contained within the element <msup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- e. *The standard defines the attribute superscriptshift, contained within the element <msup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- f. *The standard defines the attribute xref, contained within the element <msup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- g. *The standard defines the element <msup>*  
This element is supported in Excel 2013 and later.
- h. *The standard defines the attribute class, contained within the element <msup>*  
This attribute is not supported in Excel 2013 or later.
- i. *The standard defines the attribute id, contained within the element <msup>*  
This attribute is not supported in Excel 2013 or later.
- j. *The standard defines the attribute style, contained within the element <msup>*  
This attribute is not supported in Excel 2013 or later.
- k. *The standard defines the attribute superscriptshift, contained within the element <msup>*  
This attribute is not supported in Excel 2013 or later.
- l. *The standard defines the attribute xref, contained within the element <msup>*  
This attribute is not supported in Excel 2013 or later.
- m. *The standard defines the element <msup>*  
This element is supported in PowerPoint 2013 and later.

- n. *The standard defines the attribute class, contained within the element <msup>*  
This attribute is not supported in PowerPoint 2013 or later.
- o. *The standard defines the attribute id, contained within the element <msup>*  
This attribute is not supported in PowerPoint 2013 or later.
- p. *The standard defines the attribute style, contained within the element <msup>*  
This attribute is not supported in PowerPoint 2013 or later.
- q. *The standard defines the attribute superscriptshift, contained within the element <msup>*  
This attribute is not supported in PowerPoint 2013 or later.
- r. *The standard defines the attribute xref, contained within the element <msup>*  
This attribute is not supported in PowerPoint 2013 or later.

### **2.1.346 Part 3 Section 14.6 (MathML 2.0 Section 3.4.3), Subscript-superscript Pair (msubsup)**

- a. *The standard defines the element <msubsup>*  
This element is supported in Word 2013 and later.
- b. *The standard defines the attribute class, contained within the element <msubsup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in **OfficeArt Math** in Word 2013 or later.
- c. *The standard defines the attribute id, contained within the element <msubsup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- d. *The standard defines the attribute style, contained within the element <msubsup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- e. *The standard defines the attribute subscriptshift, contained within the element <msubsup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- f. *The standard defines the attribute superscriptshift, contained within the element <msubsup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- g. *The standard defines the attribute xref, contained within the element <msubsup>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the element <msubsup>*  
This element is supported in Excel 2013 and later.
- i. *The standard defines the attribute class, contained within the element <msubsup>*  
This attribute is not supported in Excel 2013 or later.
- j. *The standard defines the attribute id, contained within the element <msubsup>*  
This attribute is not supported in Excel 2013 or later.
- k. *The standard defines the attribute style, contained within the element <msubsup>*  
This attribute is not supported in Excel 2013 or later.
- l. *The standard defines the attribute subscriptshift, contained within the element <msubsup>*  
This attribute is not supported in Excel 2013 or later.
- m. *The standard defines the attribute superscriptshift, contained within the element <msubsup>*  
This attribute is not supported in Excel 2013 or later.
- n. *The standard defines the attribute xref, contained within the element <msubsup>*  
This attribute is not supported in Excel 2013 or later.
- o. *The standard defines the element <msubsup>*  
This element is supported in PowerPoint 2013 and later.
- p. *The standard defines the attribute class, contained within the element <msubsup>*  
This attribute is not supported in PowerPoint 2013 or later.
- q. *The standard defines the attribute id, contained within the element <msubsup>*  
This attribute is not supported in PowerPoint 2013 or later.
- r. *The standard defines the attribute style, contained within the element <msubsup>*  
This attribute is not supported in PowerPoint 2013 or later.
- s. *The standard defines the attribute subscriptshift, contained within the element <msubsup>*  
This attribute is not supported in PowerPoint 2013 or later.
- t. *The standard defines the attribute superscriptshift, contained within the element <msubsup>*  
This attribute is not supported in PowerPoint 2013 or later.
- u. *The standard defines the attribute xref, contained within the element <msubsup>*  
This attribute is not supported in PowerPoint 2013 or later.

### **2.1.347 Part 3 Section 14.6 (MathML 2.0 Section 3.4.4), Underscript (munder)**

- a. *The standard defines the element <munder>*  
This element is supported in MathML in Word 2013 and later.

On load, MathML in Word maps an <munder> element to one of four different elements: <nAry>, <underbar>, <groupChr>, or <limLow>. MathML in Word identifies the type of <munder> element using the following criteria:

MathML in Word maps an <munder> element to an <nAry> element when the following conditions are true:

- the accentunder attribute is false
- the first child of the <munder> element is an nAry operator.
- the operator is not contained inside any structure other than an <mml:mo>, <mml:mstyle>, or <mml:mrow> element

MathML in Word maps an <munder> element to an <underbar> element when the following conditions are true:

- the accentunder attribute is false
- the second child of an <munder> element is a <mo> element
- the operator of the second child equals 0x0332

MathML in Word maps an <munder> element to a <groupchr> element when the following conditions are true:

- when the accentunder attribute is false
- one child of the <munder> element is an <mrow> element and another child is a <mo> element
- the number of chars in the <mo> element is less than or equal to 1

Otherwise, MathML in Word maps the <munder> element to the <limLow> element.

This element is supported in **OfficeArt Math** in Word 2013 and later.

- b. *The standard defines the attribute accentunder, contained within the element <munder>*

This attribute is supported in Word 2013 and later.

- c. *The standard defines the attribute class, contained within the element <munder>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute id, contained within the element <munder>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute style, contained within the element <munder>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute xref, contained within the element <munder>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the element <munder>*

This element is supported in Excel 2013 and later.

- h. *The standard defines the attribute `accentunder`, contained within the element `<munder>`*  
This attribute is supported in Excel 2013 and later.
- i. *The standard defines the attribute `class`, contained within the element `<munder>`*  
This attribute is not supported in Excel 2013 or later.
- j. *The standard defines the attribute `id`, contained within the element `<munder>`*  
This attribute is not supported in Excel 2013 or later.
- k. *The standard defines the attribute `style`, contained within the element `<munder>`*  
This attribute is not supported in Excel 2013 or later.
- l. *The standard defines the attribute `xref`, contained within the element `<munder>`*  
This attribute is not supported in Excel 2013 or later.
- m. *The standard defines the element `<munder>`*  
This element is supported in PowerPoint 2013 and later.
- n. *The standard defines the attribute `accentunder`, contained within the element `<munder>`*  
This attribute is supported in PowerPoint 2013 and later.
- o. *The standard defines the attribute `class`, contained within the element `<munder>`*  
This attribute is not supported in PowerPoint 2013 or later.
- p. *The standard defines the attribute `id`, contained within the element `<munder>`*  
This attribute is not supported in PowerPoint 2013 or later.
- q. *The standard defines the attribute `style`, contained within the element `<munder>`*  
This attribute is not supported in PowerPoint 2013 or later.
- r. *The standard defines the attribute `xref`, contained within the element `<munder>`*  
This attribute is not supported in PowerPoint 2013 or later.

### **2.1.348 Part 3 Section 14.6 (MathML 2.0 Section 3.4.5), Overscript (`mover`)**

- a. *The standard defines the element `<mover>`*

This element is supported in MathML in Word 2013 and later.

On load, MathML in Word maps a `<mover>` element to one of five different elements: `<nAry>`, `<overbar>`, `<accent>`, `<groupChr>`, or `<limUpp>`. MathML in Word identifies the type of `<mover>` element using the following criteria:

MathML in Word maps a `<mover>` element to an `<nAry>` element when the following conditions are true:

- the `accent` attribute is false
- the core of the `<mover>` element is an nAry operator
- the operator is not contained inside any structure other than an `<mml:mo>`, `<mml:mstyle>`, or `<mml:mrow>` element

MathML in Word maps a <mover> element to an <overbar> element when the following conditions are true:

- the accent attribute is false
- the second child of the <mover> element is a <mo> element
- the operator equals 0xAF

MathML in Word maps a <mover> element to an <accent> element when the following conditions are true:

- the accent attribute is true
- the second child of the <mover> element is a <mo> element
- the string-length of the operator is 1

MathML in Word maps a <mover> element to a <groupChr> element when the following conditions are true:

- the accent attribute is false
- one child of the <mover> element is an <mrow> element and another child is a <mo> element
- the number of characters in the <mo> element is less than or equal to 1

Otherwise, MathML in Word maps a <mover> element to a <limUpp> element.

This element is supported in **OfficeArt Math** in Word 2013 and later.

- b. *The standard defines the attribute `accent`, contained within the element <mover>*

This attribute is supported in Word 2013 and later.

- c. *The standard defines the attribute `class`, contained within the element <mover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute `id`, contained within the element <mover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute `style`, contained within the element <mover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute `xref`, contained within the element <mover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the element <mover>*

This element is supported in Excel 2013 and later.

- h. *The standard defines the attribute `accent`, contained within the element <mover>*

This attribute is supported in Excel 2013 and later.

- i. *The standard defines the attribute `class`, contained within the element <mover>*



This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute id, contained within the element <mover>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute style, contained within the element <mover>*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute xref, contained within the element <mover>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the element <mover>*

This element is supported in PowerPoint 2013 and later.

- n. *The standard defines the attribute accent, contained within the element <mover>*

This attribute is supported in PowerPoint 2013 and later.

- o. *The standard defines the attribute class, contained within the element <mover>*

This attribute is not supported in PowerPoint 2013 or later.

- p. *The standard defines the attribute id, contained within the element <mover>*

This attribute is not supported in PowerPoint 2013 or later.

- q. *The standard defines the attribute style, contained within the element <mover>*

This attribute is not supported in PowerPoint 2013 or later.

- r. *The standard defines the attribute xref, contained within the element <mover>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.349 Part 3 Section 14.6 (MathML 2.0 Section 3.4.6), Underscript-overscript Pair (munderover)**

- a. *The standard defines the element <munderover>*

This element is supported in MathML in Word 2013 and later.

On load, MathML in Word maps an <munderover> element to one of two different elements: an <nAry> element or a <limLow> element nested inside a <limUpp> element.

MathML in Word maps an <munderover> element to an <nAry> element when the following conditions are true:

- the accent attribute is false
- the first child of the <munder> element is an nAry operator
- the operator is not contained inside any elements other than an <mml:mo>, <mml:mstyle>, or <mml:mrow>

Otherwise, the <munderover> element is mapped to a <limLow> element that is nested inside a <limUpp> element.

This element is supported in **OfficeArt Math** in Word 2013 and later.

- b. *The standard defines the attribute accent, contained within the element <munderover>*

This attribute is supported in Word 2013 and later.

On load, Word reads the accent attribute in an <munderover> element.

On save, Word does not write the accent attribute in an <munderover> element.

- c. *The standard defines the attribute accentunder, contained within the element <munderover>*

This attribute is supported in Word 2013 and later.

On load, Word reads the accentunder attribute in an <munderover> element.

On save, Word does not write the accentunder attribute in an <munderover> element.

- d. *The standard defines the attribute class, contained within the element <munderover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute id, contained within the element <munderover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute style, contained within the element <munderover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the attribute xref, contained within the element <munderover>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the element <munderover>*

This element is supported in Excel 2013 and later.

- i. *The standard defines the attribute accent, contained within the element <munderover>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the accent attribute in an <munderover> element.

On save, Excel does not write the accent attribute in an <munderover> element.

- j. *The standard defines the attribute accentunder, contained within the element <munderover>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the accentunder attribute in an <munderover> element.

On save, Excel does not write the accentunder attribute in an <munderover> element.

- k. *The standard defines the attribute class, contained within the element <munderover>*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute id, contained within the element <munderover>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute style, contained within the element <munderover>*

This attribute is not supported in Excel 2013 or later.

- n. *The standard defines the attribute xref, contained within the element <munderover>*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the element <munderover>*

This element is supported in PowerPoint 2013 and later.

- p. *The standard defines the attribute accent, contained within the element <munderover>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the accent attribute in an <munderover> element.

On save, PowerPoint does not write the accent attribute in an <munderover> element.

- q. *The standard defines the attribute accentunder, contained within the element <munderover>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the accentunder attribute in an <munderover> element.

On save, PowerPoint does not write the accentunder attribute in an <munderover> element.

- r. *The standard defines the attribute class, contained within the element <munderover>*

This attribute is not supported in PowerPoint 2013 or later.

- s. *The standard defines the attribute id, contained within the element <munderover>*

This attribute is not supported in PowerPoint 2013 or later.

- t. *The standard defines the attribute style, contained within the element <munderover>*

This attribute is not supported in PowerPoint 2013 or later.

- u. *The standard defines the attribute xref, contained within the element <munderover>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.350 Part 3 Section 14.6 (MathML 2.0 Section 3.4.7), Prescripts and Tensor Indices (mmultiscripts)**

- a. *The standard defines the element <mmultiscripts>*

This element is supported in MathML in Word 2013 and later.

On load, MathML in Word maps the <mmultiscripts> element to a combination of the following elements:

- <sSubSup>
- <sSub>
- <sSup>
- <sPre>

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word reads the <mmultiscripts> element.

On save, OfficeArt Math in Word writes the <mmultiscripts> element if prescripts are present.

- b. *The standard defines the attribute class, contained within the element <mmultiscripts>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- c. *The standard defines the attribute id, contained within the element <mmultiscripts>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- d. *The standard defines the attribute style, contained within the element <mmultiscripts>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- e. *The standard defines the attribute subscriptshift, contained within the element <mmultiscripts>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- f. *The standard defines the attribute superscriptshift, contained within the element <mmultiscripts>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- g. *The standard defines the attribute xref, contained within the element <mmultiscripts>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- h. *The standard defines the element <mmultiscripts>*  
This element is supported in Excel 2013 and later.  
On load, Excel reads the <mmultiscripts> element.  
On save, Excel writes the <mmultiscripts> element if prescripts are present.
- i. *The standard defines the attribute class, contained within the element <mmultiscripts>*  
This attribute is not supported in Excel 2013 or later.
- j. *The standard defines the attribute id, contained within the element <mmultiscripts>*  
This attribute is not supported in Excel 2013 or later.
- k. *The standard defines the attribute style, contained within the element <mmultiscripts>*  
This attribute is not supported in Excel 2013 or later.
- l. *The standard defines the attribute subscriptshift, contained within the element <mmultiscripts>*  
This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute superscriptshift, contained within the element <mmultiscripts>*  
This attribute is not supported in Excel 2013 or later.
- n. *The standard defines the attribute xref, contained within the element <mmultiscripts>*  
This attribute is not supported in Excel 2013 or later.
- o. *The standard defines the element <mmultiscripts>*  
This element is supported in PowerPoint 2013 and later.  
On load, PowerPoint reads the <mmultiscripts> element.  
On save, PowerPoint writes the <mmultiscripts> element if prescripts are present.
- p. *The standard defines the attribute class, contained within the element <mmultiscripts>*  
This attribute is not supported in PowerPoint 2013 or later.
- q. *The standard defines the attribute id, contained within the element <mmultiscripts>*  
This attribute is not supported in PowerPoint 2013 or later.
- r. *The standard defines the attribute style, contained within the element <mmultiscripts>*  
This attribute is not supported in PowerPoint 2013 or later.
- s. *The standard defines the attribute subscriptshift, contained within the element <mmultiscripts>*  
This attribute is not supported in PowerPoint 2013 or later.
- t. *The standard defines the attribute superscriptshift, contained within the element <mmultiscripts>*  
This attribute is not supported in PowerPoint 2013 or later.
- u. *The standard defines the attribute xref, contained within the element <mmultiscripts>*  
This attribute is not supported in PowerPoint 2013 or later.

### **2.1.351 Part 3 Section 14.6 (MathML 2.0 Section 3.5.1), Table or Matrix (mtable)**

- a. *The standard defines the element <mtable>*

This element is supported in MathML in Word 2013 and later.

On load, MathML in Word may transform a MathML <mtable> element into either an equation array (<omml:eqArray> element) or a matrix (<omml:m> element).

MathML in Word transforms an <mtable> element as an <omml:eqArray> element if the following conditions are true:

- no frame lines
- no column lines
- no row lines
- all rows have exactly one column
- no labeled rows

Otherwise, MathML in Word transforms an <mtable> element as an <omml:m> element.

This element is supported in **OfficeArt Math** in Word 2013 and later.

- b. *The standard defines the attribute align, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- c. *The standard defines the attribute alignmentscope, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- d. *The standard defines the attribute class, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- e. *The standard defines the attribute columnalign, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- f. *The standard defines the attribute columnlines, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is supported in OfficeArt Math in Word 2013 and later.  
On load, OfficeArt Math in Word reads the columnlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.  
On save, OfficeArt Math in Word does not write the columnlines attribute in an <mtable> element.
- g. *The standard defines the attribute columnspacing, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- h. *The standard defines the attribute columnwidth, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- i. *The standard defines the attribute displaystyle, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- j. *The standard defines the attribute equalcolumns, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- k. *The standard defines the attribute equalrows, contained within the element <mtable>*  
This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

l. *The standard defines the attribute frame, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the frame attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, OfficeArt Math in Word does not write the frame attribute in an <mtable> element.

m. *The standard defines the attribute framespacing, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

n. *The standard defines the attribute groupalign, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the groupalign attribute in an <mtable> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, OfficeArt Math in Word does not write the groupalign attribute in an <mtable> element.

o. *The standard defines the attribute id, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

p. *The standard defines the attribute minlabelspacing, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

q. *The standard defines the attribute rowalign, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

r. *The standard defines the attribute rowlines, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the rowlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, OfficeArt Math in Word does not write the rowlines attribute in an <mtable> element.

s. *The standard defines the attribute rowspacing, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- t. *The standard defines the attribute side, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- u. *The standard defines the attribute style, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- v. *The standard defines the attribute width, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- w. *The standard defines the attribute xref, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- x. *The standard defines the element <mtable>*

This element is supported in Excel 2013 and later.

- y. *The standard defines the attribute align, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.

- z. *The standard defines the attribute alignmentscope, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.

- aa. *The standard defines the attribute class, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.

- bb. *The standard defines the attribute columnalign, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.

- cc. *The standard defines the attribute columncolspan, contained within the element <mtable>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the columncolspan attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, Excel does not write the columncolspan attribute in an <mtable> element.

- dd. *The standard defines the attribute columnspacing, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.

- ee. *The standard defines the attribute columnwidth, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.



- ff. *The standard defines the attribute `displaystyle`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- gg. *The standard defines the attribute `equalcolumns`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- hh. *The standard defines the attribute `equalrows`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- ii. *The standard defines the attribute `frame`, contained within the element `<mtable>`*  
This attribute is supported in Excel 2013 and later.  
  
On load, Excel reads the frame attribute in an `<mtable>` element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.  
  
On save, Excel does not write the frame attribute in an `<mtable>` element.
- jj. *The standard defines the attribute `framespacing`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- kk. *The standard defines the attribute `groupalign`, contained within the element `<mtable>`*  
This attribute is supported in Excel 2013 and later.  
  
On load, Excel reads the groupalign attribute in an `<mtable>` element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, Excel does not write the groupalign attribute in an `<mtable>` element.
- ll. *The standard defines the attribute `id`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- mm. *The standard defines the attribute `minlabelspacing`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- nn. *The standard defines the attribute `rowalign`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- oo. *The standard defines the attribute `rowlines`, contained within the element `<mtable>`*  
This attribute is supported in Excel 2013 and later.  
  
On load, Excel reads the rowlines attribute in an `<mtable>` element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.  
  
On save, Excel does not write the rowlines attribute in an `<mtable>` element.
- pp. *The standard defines the attribute `rowspacing`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- qq. *The standard defines the attribute `side`, contained within the element `<mtable>`*  
This attribute is not supported in Excel 2013 or later.
- rr. *The standard defines the attribute `style`, contained within the element `<mtable>`*

This attribute is not supported in Excel 2013 or later.

ss. *The standard defines the attribute width, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.

tt. *The standard defines the attribute xref, contained within the element <mtable>*

This attribute is not supported in Excel 2013 or later.

uu. *The standard defines the element <mtable>*

This element is supported in PowerPoint 2013 and later.

vv. *The standard defines the attribute align, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

ww. *The standard defines the attribute alignmentscope, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

xx. *The standard defines the attribute class, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

yy. *The standard defines the attribute columnalign, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

zz. *The standard defines the attribute columncolspan, contained within the element <mtable>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the columncolspan attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, PowerPoint does not write the columncolspan attribute in an <mtable> element.

aaa. *The standard defines the attribute columnspacing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

bbb. *The standard defines the attribute columnwidth, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

ccc. *The standard defines the attribute displaystyle, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

ddd. *The standard defines the attribute equalcolumns, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

eee. *The standard defines the attribute equalrows, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

fff. *The standard defines the attribute frame, contained within the element <mtable>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the frame attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, PowerPoint does not write the frame attribute in an <mtable> element.

ggg. *The standard defines the attribute framespacing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

hhh. *The standard defines the attribute groupalign, contained within the element <mtable>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the groupalign attribute in an <mtable> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <mtable> element.

iii. *The standard defines the attribute id, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

jjj. *The standard defines the attribute minlabelspacing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

kkk. *The standard defines the attribute rowalign, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

lll. *The standard defines the attribute rowlines, contained within the element <mtable>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the rowlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, PowerPoint does not write the rowlines attribute in an <mtable> element.

mmm. *The standard defines the attribute rowspacing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

nnn. *The standard defines the attribute side, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

ooo. *The standard defines the attribute style, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

ppp. *The standard defines the attribute width, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

qqq. *The standard defines the attribute xref, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.352 Part 3 Section 14.6 (MathML 2.0 Section 3.5.2), Row in Table or Matrix (mtr)**

a. *The standard defines the element <mtr>*

This element is supported in Word 2013 and later.

- b. *The standard defines the attribute class, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

- c. *The standard defines the attribute columnalign, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute groupalign, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the groupalign attribute in an <mtr> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, OfficeArt Math in Word does not write the groupalign attribute in an <mtr> element.

- e. *The standard defines the attribute id, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute rowalign, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the attribute style, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the attribute xref, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the element <mtr>*

This element is supported in Excel 2013 and later.

- j. *The standard defines the attribute class, contained within the element <mtr>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute columnalign, contained within the element <mtr>*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute groupalign, contained within the element <mtr>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the groupalign attribute in an <mtr> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, Excel does not write the groupalign attribute in an <mtr> element.

- m. *The standard defines the attribute id, contained within the element <mtr>*

This attribute is not supported in Excel 2013 or later.

- n. *The standard defines the attribute rowalign, contained within the element <mtr>*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the attribute style, contained within the element <mtr>*

This attribute is not supported in Excel 2013 or later.

- p. *The standard defines the attribute xref, contained within the element <mtr>*

This attribute is not supported in Excel 2013 or later.

- q. *The standard defines the element <mtr>*

This element is supported in PowerPoint 2013 and later.

- r. *The standard defines the attribute class, contained within the element <mtr>*

This attribute is not supported in PowerPoint 2013 or later.

- s. *The standard defines the attribute columnalign, contained within the element <mtr>*

This attribute is not supported in PowerPoint 2013 or later.

- t. *The standard defines the attribute groupalign, contained within the element <mtr>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the groupalign attribute in an <mtr> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <mtr> element.

- u. *The standard defines the attribute id, contained within the element <mtr>*

This attribute is not supported in PowerPoint 2013 or later.

- v. *The standard defines the attribute rowalign, contained within the element <mtr>*

This attribute is not supported in PowerPoint 2013 or later.

- w. *The standard defines the attribute style, contained within the element <mtr>*

This attribute is not supported in PowerPoint 2013 or later.

- x. *The standard defines the attribute xref, contained within the element <mtr>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.353 Part 3 Section 14.6 (MathML 2.0 Section 3.5.3), Labeled Row in Table or Matrix (mlabeledtr)**

- a. *The standard defines the element <mlabeledtr>*

This element is supported in MathML in Word 2013 and later.

On load, MathML in Word converts <mlabeledtr> elements into <mtr> elements.

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word reads the <mlabeledtr> element. The label argument is ignored, making an <mlabeledtr> element equivalent to an <mtr> element.

On save, OfficeArt Math in Word does not write the <mlabeledtr> element.

b. *The standard defines the element <mlabeledtr>*

This element is supported in Excel 2013 and later.

On load, Excel reads the <mlabeledtr> element. The label argument is ignored, making an <mlabeledtr> element equivalent to an <mtr> element.

On save, Excel does not write the <mlabeledtr> element.

c. *The standard defines the element <mlabeledtr>*

This element is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the <mlabeledtr> element. The label argument is ignored, making an <mlabeledtr> element equivalent to an <mtr> element.

On save, PowerPoint does not write the <mlabeledtr> element.

### **2.1.354 Part 3 Section 14.6 (MathML 2.0 Section 3.5.4), Entry in Table or Matrix (mtd)**

a. *The standard defines the element <mtd>*

This element is supported in Word 2013 and later.

b. *The standard defines the attribute class, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in **OfficeArt Math** in Word 2013 or later.

c. *The standard defines the attribute columnalign, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

d. *The standard defines the attribute colspan, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

e. *The standard defines the attribute groupalign, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the groupalign attribute in an <mtd> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, OfficeArt Math in Word does not write the groupalign attribute in an <mtd> element.

- f. *The standard defines the attribute `id`, contained within the element `<mtd>`*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- g. *The standard defines the attribute `rowalign`, contained within the element `<mtd>`*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- h. *The standard defines the attribute `rowspan`, contained within the element `<mtd>`*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- i. *The standard defines the attribute `style`, contained within the element `<mtd>`*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- j. *The standard defines the attribute `xref`, contained within the element `<mtd>`*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- k. *The standard defines the element `<mtd>`*  
This element is supported in Excel 2013 and later.
- l. *The standard defines the attribute `class`, contained within the element `<mtd>`*  
This attribute is not supported in Excel 2013 or later.
- m. *The standard defines the attribute `columnalign`, contained within the element `<mtd>`*  
This attribute is not supported in Excel 2013 or later.
- n. *The standard defines the attribute `columnspan`, contained within the element `<mtd>`*  
This attribute is not supported in Excel 2013 or later.
- o. *The standard defines the attribute `groupalign`, contained within the element `<mtd>`*  
This attribute is supported in Excel 2013 and later.  
  
On load, Excel reads the `groupalign` attribute in an `<mtd>` element. Only the 'left' and 'right' values of the `groupalign` attribute are supported. On save, Excel does not write the `groupalign` attribute in an `<mtd>` element.
- p. *The standard defines the attribute `id`, contained within the element `<mtd>`*  
This attribute is not supported in Excel 2013 or later.
- q. *The standard defines the attribute `rowalign`, contained within the element `<mtd>`*  
This attribute is not supported in Excel 2013 or later.
- r. *The standard defines the attribute `rowspan`, contained within the element `<mtd>`*

This attribute is not supported in Excel 2013 or later.

- s. *The standard defines the attribute style, contained within the element <mtd>*

This attribute is not supported in Excel 2013 or later.

- t. *The standard defines the attribute xref, contained within the element <mtd>*

This attribute is not supported in Excel 2013 or later.

- u. *The standard defines the element <mtd>*

This element is supported in PowerPoint 2013 and later.

- v. *The standard defines the attribute class, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

- w. *The standard defines the attribute columnalign, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

- x. *The standard defines the attribute colspan, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

- y. *The standard defines the attribute groupalign, contained within the element <mtd>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the groupalign attribute in an <mtd> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <mtd> element.

- z. *The standard defines the attribute id, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

- aa. *The standard defines the attribute rowalign, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

- bb. *The standard defines the attribute rowspan, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

- cc. *The standard defines the attribute style, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

- dd. *The standard defines the attribute xref, contained within the element <mtd>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.355 Part 3 Section 14.6 (MathML 2.0 Section 3.5.5.4), Specifying alignment points using malignmark**

- a. *The standard defines the element <maligngroup>*

This element is supported in MathML in Word 2013 and later.



On load, MathML in Word ignores the <mathgroup> element when the element is not inside a table that MathML in Word interprets as an equation array.

This element is supported in **OfficeArt Math** in Word 2013 and later.

- b. *The standard defines the attribute class, contained within the element <mathgroup>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- c. *The standard defines the attribute groupalign, contained within the element <mathgroup>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the groupalign attribute in an <mathgroup> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, OfficeArt Math in Word does not write the groupalign attribute in an <mathgroup> element.

- d. *The standard defines the attribute id, contained within the element <mathgroup>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute style, contained within the element <mathgroup>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- f. *The standard defines the attribute xref, contained within the element <mathgroup>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the element <mathmark>*

This element is supported in Word 2013 and later.

On load, Word ignores the <mathmark> element when the element is not inside a table that Word interprets as an equation array.

- h. *The standard defines the attribute class, contained within the element <mathmark>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- i. *The standard defines the attribute edge, contained within the element <mathmark>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- j. *The standard defines the attribute id, contained within the element <mathmark>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- k. *The standard defines the attribute style, contained within the element <malignmark>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- l. *The standard defines the attribute xref, contained within the element <malignmark>*  
This attribute is not supported in MathML in Word 2013 or later.  
This attribute is not supported in OfficeArt Math in Word 2013 or later.
- m. *The standard defines the element <maligngroup>*  
This element is supported in Excel 2013 and later.
- n. *The standard defines the attribute class, contained within the element <maligngroup>*  
This attribute is not supported in Excel 2013 or later.
- o. *The standard defines the attribute groupalign, contained within the element <maligngroup>*  
This attribute is supported in Excel 2013 and later.  
On load, Excel reads the groupalign attribute in an <maligngroup> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, Excel does not write the groupalign attribute in an <maligngroup> element.
- p. *The standard defines the attribute id, contained within the element <maligngroup>*  
This attribute is not supported in Excel 2013 or later.
- q. *The standard defines the attribute style, contained within the element <maligngroup>*  
This attribute is not supported in Excel 2013 or later.
- r. *The standard defines the attribute xref, contained within the element <maligngroup>*  
This attribute is not supported in Excel 2013 or later.
- s. *The standard defines the attribute class, contained within the element <malignmark>*  
This attribute is not supported in Excel 2013 or later.
- t. *The standard defines the attribute edge, contained within the element <malignmark>*  
This attribute is not supported in Excel 2013 or later.
- u. *The standard defines the attribute id, contained within the element <malignmark>*  
This attribute is not supported in Excel 2013 or later.
- v. *The standard defines the attribute style, contained within the element <malignmark>*  
This attribute is not supported in Excel 2013 or later.
- w. *The standard defines the attribute xref, contained within the element <malignmark>*  
This attribute is not supported in Excel 2013 or later.
- x. *The standard defines the element <maligngroup>*  
This element is supported in PowerPoint 2013 and later.

- y. *The standard defines the attribute class, contained within the element <maligngroup>*

This attribute is not supported in PowerPoint 2013 or later.

- z. *The standard defines the attribute groupalign, contained within the element <maligngroup>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the groupalign attribute in an <maligngroup> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <maligngroup> element.

- aa. *The standard defines the attribute id, contained within the element <maligngroup>*

This attribute is not supported in PowerPoint 2013 or later.

- bb. *The standard defines the attribute style, contained within the element <maligngroup>*

This attribute is not supported in PowerPoint 2013 or later.

- cc. *The standard defines the attribute xref, contained within the element <maligngroup>*

This attribute is not supported in PowerPoint 2013 or later.

- dd. *The standard defines the attribute class, contained within the element <malignmark>*

This attribute is not supported in PowerPoint 2013 or later.

- ee. *The standard defines the attribute edge, contained within the element <malignmark>*

This attribute is not supported in PowerPoint 2013 or later.

- ff. *The standard defines the attribute id, contained within the element <malignmark>*

This attribute is not supported in PowerPoint 2013 or later.

- gg. *The standard defines the attribute style, contained within the element <malignmark>*

This attribute is not supported in PowerPoint 2013 or later.

- hh. *The standard defines the attribute xref, contained within the element <malignmark>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.356 Part 3 Section 14.6 (MathML 2.0 Section 3.6.1), Bind Action to Sub-Expression (maction)**

- a. *The standard defines the element <maction>*

This element is not supported in MathML in Word 2013 or later.

This element is supported in **OfficeArt Math** in Word 2013 and later.

On load, OfficeArt Math in Word reads the <maction> element. Content other than the sub-expression identified by the selection attribute is ignored.

On save, OfficeArt Math in Word does not write the <maction> element.

- b. *The standard defines the attribute actiontype, contained within the element <maction>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- c. *The standard defines the attribute class, contained within the element <maction>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- d. *The standard defines the attribute id, contained within the element <maction>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- e. *The standard defines the attribute selection, contained within the element <maction>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is supported in OfficeArt Math in Word 2013 and later.

On load, OfficeArt Math in Word reads the selection attribute in an <maction> element.

On save, OfficeArt Math in Word does not write the selection attribute in an <maction> element.

- f. *The standard defines the attribute style, contained within the element <maction>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- g. *The standard defines the attribute xref, contained within the element <maction>*

This attribute is not supported in MathML in Word 2013 or later.

This attribute is not supported in OfficeArt Math in Word 2013 or later.

- h. *The standard defines the element <maction>*

This element is supported in Excel 2013 and later.

On load, Excel reads the <maction> element. Content other than the sub-expression identified by the selection attribute is ignored.

On save, Excel does not write the <maction> element.

- i. *The standard defines the attribute actiontype, contained within the element <maction>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute class, contained within the element <maction>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute id, contained within the element <maction>*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute selection, contained within the element <maction>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the selection attribute in an <maction> element.

On save, Excel does not write the selection attribute in an <maction> element.

- m. *The standard defines the attribute style, contained within the element <maction>*

This attribute is not supported in Excel 2013 or later.

- n. *The standard defines the attribute xref, contained within the element <maction>*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the element <maction>*

This element is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the <maction> element. Content other than the sub-expression identified by the selection attribute is ignored.

On save, PowerPoint does not write the <maction> element.

- p. *The standard defines the attribute actiontype, contained within the element <maction>*

This attribute is not supported in PowerPoint 2013 or later.

- q. *The standard defines the attribute class, contained within the element <maction>*

This attribute is not supported in PowerPoint 2013 or later.

- r. *The standard defines the attribute id, contained within the element <maction>*

This attribute is not supported in PowerPoint 2013 or later.

- s. *The standard defines the attribute selection, contained within the element <maction>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint reads the selection attribute in an <maction> element.

On save, PowerPoint does not write the selection attribute in an <maction> element.

- t. *The standard defines the attribute style, contained within the element <maction>*

This attribute is not supported in PowerPoint 2013 or later.

- u. *The standard defines the attribute xref, contained within the element <maction>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.357 Part 3 Section 14.7.2, text:dde-connection-decls**

- a. *The standard defines the element <text:dde-connection-decls>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <text:dde-connection-decls>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:dde-connection-decls>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.358 Part 3 Section 14.7.3, text:dde-connection-decl**

- a. *The standard defines the element <text:dde-connection-decl>*

This element is not supported in Word 2013 or later.

### **2.1.359 Part 3 Section 14.7.5, office:dde-source**

- a. *The standard defines the element <office:dde-source>*

This element is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:section-source-dde>, contained within the parent element <text:section>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <office:dde-source>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the element <office:dde-source>*

This element is not supported in PowerPoint 2013 or later.

- e. *The standard defines the element <office:dde-source>, contained within the parent element <table:table>*

### **2.1.360 Part 3 Section 15.2.3, anim:animateTransform**

- a. *The standard defines the element <anim:animateTransform>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.361 Part 3 Section 15.2.6, anim:animateColor**

- a. *The standard defines the element <anim:animateColor>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.362 Part 3 Section 15.5, anim:audio**

- a. *The standard defines the element <anim:audio>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.363 Part 3 Section 15.6.1, anim:command**

- a. *The standard defines the property "custom", contained within the attribute anim:command*

This property is not supported in PowerPoint 2013 or later.

- b. *The standard defines the property "stop-audio", contained within the attribute anim:command*

This property is not supported in PowerPoint 2013 or later.

### **2.1.364 Part 3 Section 16.2, style:style**

- a. *The standard defines the property "dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Word 2013 or later.

- b. *The standard defines the property "dot-dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Word 2013 or later.

- c. *The standard defines the property "dotted", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Word 2013 or later.

- d. *The standard defines the element <style:style>*

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the element <anyAttListOrElements>*

This element is not supported in Excel 2013 or later.

- f. *The standard defines the element <anyElements>, contained within the parent element <anyAttListOrElements>*

This element is not supported in Excel 2013 or later.

- g. *The standard defines the property "dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2013 or later.

- h. *The standard defines the property "dot-dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2013 or later.

- i. *The standard defines the property "dotted", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2013 or later.

- j. *The standard defines the property "none", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2013 or later.

- k. *The standard defines the property "solid", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2013 or later.

- l. *The standard defines the element <style:style>*

This element is supported in Excel 2013 and later.

On load, Excel maps the "default" style to its "normal" style. On save, Excel maps its "normal" style back to "default".

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- m. *The standard defines the element <style:style>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:



- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### 2.1.365 Part 3 Section 16.3, style:map

- a. *The standard defines the element <style:map>*

This element is not supported in Word 2013 or later.

Word 2013 does not support this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:map>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <style:map>, contained within the parent element <number:date-style>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <style:map>, contained within the parent element <number:number-style>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <style:map>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2013 or later.

- f. *The standard defines the element <style:map>, contained within the parent element <number:time-style>*

This element is not supported in Word 2013 or later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- g. *The standard defines the element <style:map>*

Excel 2013 does not support this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- h. *The standard defines the element <style:map>, contained within the parent element <number:boolean-style>*

This element is not supported in Excel 2013 or later.

- i. *The standard defines the element <style:map>*

This element is not supported in PowerPoint 2013 or later.

PowerPoint 2013 does not support this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.366 Part 3 Section 16.4, style:default-style**

- a. *The standard defines the element <style:default-style>*

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <style:default-style>*

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

c. *The standard defines the element <style:default-style>, contained within the parent element <office:styles>*

This element is not supported in Excel 2013 or later.

- d. *The standard defines the element <style:default-style>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.367 Part 3 Section 16.6, style:header-style**

- a. *The standard defines the element <style:header-style>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.368 Part 3 Section 16.7, style:footer-style**

- a. *The standard defines the element <style:footer-style>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.369 Part 3 Section 16.8, style:default-page-layout**

- a. *The standard defines the element <style:default-page-layout>*

This element is supported in Word 2013 and later.

On load, Word reads in the properties specified by style:default-page-layout but stores them in multiple different levels (page or section).

### **2.1.370 Part 3 Section 16.10, style:header**

- a. *The standard defines the element <style:header>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.371 Part 3 Section 16.11, style:header-first**

- a. *The standard defines the element <style:header-first>*

This element is not supported in PowerPoint 2021 or later.

- b. *The standard defines the element <style:header-first>*

This element is supported in Word 2021 or later.

### **2.1.372 Part 3 Section 16.12, style:footer**

- a. *The standard defines the element <style:footer>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.373 Part 3 Section 16.13, style:footer-first**

- a. *The standard defines the element <style:footer-first>*

This element is not supported in PowerPoint 2021 or later.

- b. *The standard defines the element <style:footer-first>*

This element is supported in Word 2021 or later.

### **2.1.374 Part 3 Section 16.14, style:header-left**

- a. *The standard defines the element <style:header-left>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.375 Part 3 Section 16.15, style:footer-left**

- a. *The standard defines the element <style:footer-left>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.376 Part 3 Section 16.16, style:region-left**

- a. *The standard defines the element <style:region-left>, contained within the parent element <style:footer>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <style:region-left>, contained within the parent element <style:footer-left>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <style:region-left>, contained within the parent element <style:footer-right>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <style:region-left>, contained within the parent element <style:header>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <style:region-left>, contained within the parent element <style:header-left>*

This element is not supported in Word 2013 or later.

- f. *The standard defines the element <style:region-left>, contained within the parent element <style:header-right>*

This element is not supported in Word 2013 or later.

### **2.1.377 Part 3 Section 16.17, style:region-center**

- a. *The standard defines the element <style:region-center>, contained within the parent element <style:footer>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <style:region-center>, contained within the parent element <style:footer-left>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <style:region-center>, contained within the parent element <style:footer-right>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <style:region-center>, contained within the parent element <style:header>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <style:region-center>, contained within the parent element <style:header-left>*

This element is not supported in Word 2013 or later.

- f. *The standard defines the element <style:region-center>, contained within the parent element <style:header-right>*

This element is not supported in Word 2013 or later.

### **2.1.378 Part 3 Section 16.18, style:region-right**

- a. *The standard defines the element <style:region-right>, contained within the parent element <style:footer>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <style:region-right>, contained within the parent element <style:footer-left>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <style:region-right>, contained within the parent element <style:footer-right>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <style:region-right>, contained within the parent element <style:header>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <style:region-right>, contained within the parent element <style:header-left>*

This element is not supported in Word 2013 or later.

- f. *The standard defines the element <style:region-right>, contained within the parent element <style:header-right>*

This element is not supported in Word 2013 or later.

### **2.1.379 Part 3 Section 16.19, presentation:notes**

- a. *The standard defines the element <presentation:notes>*

This element is supported in PowerPoint 2013 and later.

Certain OLE objects cannot be saved by PowerPoint when they exist in the notes section of a master page.

- b. *The standard defines the element <presentation:notes>, contained within the parent element <style:master-page>*

This element is supported in PowerPoint 2013 and later.

Only the notes for the first master page will be loaded into PowerPoint as the master notes. All other <presentation:notes> elements for other master pages will be ignored.

If there are any <draw:object> child elements of the <presentation:notes> element for a master page, those elements will be lost.

### **2.1.380 Part 3 Section 16.20, table:table-template**

- a. *The standard defines the element <table:table-template>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:table-template*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.381 Part 3 Section 16.21.2, table:first-row**

- a. *The standard defines the element <table:first-row>, contained within the parent element <table:table-template>*



This element is not supported in Word 2013 or later.

**2.1.382 Part 3 Section 16.21.3, table:last-row**

- a. *The standard defines the element <table:last-row>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

**2.1.383 Part 3 Section 16.21.4, table:first-column**

- a. *The standard defines the element <table:first-column>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

**2.1.384 Part 3 Section 16.21.5, table:last-column**

- a. *The standard defines the element <table:last-column>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

**2.1.385 Part 3 Section 16.21.6, table:body**

- a. *The standard defines the element <table:body>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

**2.1.386 Part 3 Section 16.21.7, table:even-rows**

- a. *The standard defines the element <table:even-rows>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

**2.1.387 Part 3 Section 16.21.8, table:odd-rows**

- a. *The standard defines the element <table:odd-rows>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

**2.1.388 Part 3 Section 16.21.9, table:even-columns**

- a. *The standard defines the element <table:even-columns>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

**2.1.389 Part 3 Section 16.21.10, table:odd-columns**

- a. *The standard defines the element <table:odd-columns>, contained within the parent element <table:table-template>*

This element is not supported in Word 2013 or later.

### **2.1.390 Part 3 Section 16.22, table:background**

- a. *The standard defines the element <table:background>*

This element is supported in Word 2013 and later.

### **2.1.391 Part 3 Section 16.23, style:font-face**

- a. *The standard defines the element <style:font-face>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels. Font face declarations are not written. Instead, on save, the fo:font-family attribute specifies the font face.

- b. *The standard defines the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Font face declarations are supported only on load and are not written. Instead, on save the fo:font-family attribute specifies the font face.

- c. *The standard defines the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This element is not supported in Excel 2013 or later.

On load, Excel ignores the <style:font-face> element, all attributes of the <style:font-face> element, and all child elements. Excel reads the <style:font-name> attribute to determine the font to apply.

On save, Excel writes out the <style:font-face> element, along with values for the <style:name> and <svg:font-family> attributes.

- d. *The standard defines the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Font face declarations are supported only on load and are not written. Instead, on save the fo:font-family attribute specifies the font face.

### **2.1.392 Part 3 Section 16.24, svg:font-face-src**

- a. *The standard defines the element <svg:font-face-src>, contained within the parent element <style:font-face>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <svg:font-face-src>, contained within the parent element <style:font-face>*

This element is not supported in Excel 2013 or later.

### **2.1.393 Part 3 Section 16.25, svg:font-face-name**

- a. *The standard defines the element <svg:font-face-name>, contained within the parent element <svg:font-face-src>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <svg:font-face-name>, contained within the parent element <svg:font-face-src>*

This element is not supported in Excel 2013 or later.

### **2.1.394 Part 3 Section 16.26, svg:font-face-uri**

- a. *The standard defines the element <svg:font-face-uri>, contained within the parent element <svg:font-face-src>*

This element is not supported in Word 2013 or later.

### **2.1.395 Part 3 Section 16.27, svg:definition-src**

- a. *The standard defines the element <svg:definition-src>, contained within the parent element <style:font-face>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <svg:definition-src>, contained within the parent element <style:font-face>*

This element is not supported in Excel 2013 or later.

### **2.1.396 Part 3 Section 16.28, svg:font-face-format**

- a. *The standard defines the element <svg:font-face-format>, contained within the parent element <svg:font-face-uri>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <svg:font-face-format>, contained within the parent element <svg:font-face-src>*

This element is not supported in Excel 2013 or later.

#### **2.1.397 Part 3 Section 16.29.2, number:number-style**

- a. *The standard defines the element <number:number-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:number-style>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.398 Part 3 Section 16.29.3, number:number**

- a. *The standard defines the element <number:number>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:number>, contained within the parent element <number:number-style>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <number:number>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2013 or later.

#### **2.1.399 Part 3 Section 16.29.4, number:embedded-text**

- a. *The standard defines the element <number:embedded-text>, contained within the parent element <number:number>*

This element is not supported in Word 2013 or later.

#### **2.1.400 Part 3 Section 16.29.6, number:scientific-number**

- a. *The standard defines the element <number:scientific-number>, contained within the parent element <number:number-style>*

This element is not supported in Word 2013 or later.

#### **2.1.401 Part 3 Section 16.29.7, number:fraction**

- a. *The standard defines the element <number:fraction>, contained within the parent element <number:number-style>*

This element is not supported in Word 2013 or later.

#### **2.1.402 Part 3 Section 16.29.8, number:currency-style**

- a. *The standard defines the element <number:currency-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:currency-style>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.403 Part 3 Section 16.29.9, number:currency-symbol**

- a. *The standard defines the element <number:currency-symbol>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2013 or later.

#### **2.1.404 Part 3 Section 16.29.10, number:percentage-style**

- a. *The standard defines the element <number:percentage-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:percentage-style>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.405 Part 3 Section 16.29.15, number:era**

- a. *The standard defines the element <number:era>, contained within the parent element <number:date-style>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

#### **2.1.406 Part 3 Section 16.29.17, number:week-of-year**

- a. *The standard defines the element <number:week-of-year>, contained within the parent element <number:date-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:week-of-year>, contained within the parent element <number:date-style>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <number:week-of-year>, contained within the parent element <number:date-style>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.407 Part 3 Section 16.29.18, number:quarter**

- a. *The standard defines the element <number:quarter>, contained within the parent element <number:date-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:quarter>, contained within the parent element <number:date-style>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <number:quarter>, contained within the parent element <number:date-style>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.408 Part 3 Section 16.29.19, number:time-style**

- a. *The standard defines the element <number:time-style>*

This element is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- b. *The standard defines the attribute style:name, contained within the element <number:time-style>*

#### **2.1.409 Part 3 Section 16.29.23, number:am-pm**

- a. *The standard defines the element <number:am-pm>, contained within the parent element <number:time-style>*

This element is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

#### **2.1.410 Part 3 Section 16.29.24, number:boolean-style**

- a. *The standard defines the element <number:boolean-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:boolean-style>*

This element is not supported in Excel 2013 or later.

On load, Boolean styles are loaded; however, Excel does not have a number format token corresponding to the <number:boolean-style> element. Therefore, only the standard data style attributes are applied to specify the format. On save, Boolean styles are not saved.

- c. *The standard defines the element <number:boolean-style>*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.411 Part 3 Section 16.29.25, number:boolean**

- a. *The standard defines the element <number:boolean>, contained within the parent element <number:boolean-style>*

This element is not supported in Excel 2013 or later.

#### **2.1.412 Part 3 Section 16.29.26, number:text-style**

- a. *The standard defines the element <number:text-style>*

This element is not supported in Word 2013 or later.

#### **2.1.413 Part 3 Section 16.29.27, number:text**

- a. *The standard defines the element <number:text>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element <number:text>, contained within the parent element <number:number-style>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <number:text>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <number:text>, contained within the parent element <number:text-style>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <number:text>, contained within the parent element <number:time-style>*

This element is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- f. *The standard defines the element <number:text>, contained within the parent element <number:boolean-style>*

This element is not supported in Excel 2013 or later.

#### **2.1.414 Part 3 Section 16.29.28, number:text-content**

- a. *The standard defines the element <number:text-content>, contained within the parent element <number:text-style>*

This element is not supported in Word 2013 or later.

#### **2.1.415 Part 3 Section 16.29.29, style:text-properties**

- a. *The standard defines the element <style:text-properties>*

This element is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:text-properties>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <style:text-properties>, contained within the parent element <number:date-style>*

This element is not supported in Word 2013 or later.

Word applies text properties to this element via a <text:span> around the object.

- d. *The standard defines the element <style:text-properties>, contained within the parent element <number:number-style>*

This element is not supported in Word 2013 or later.

- e. *The standard defines the element <style:text-properties>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2013 or later.

- f. *The standard defines the element <style:text-properties>, contained within the parent element <number:time-style>*

This element is not supported in Word 2013 or later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- g. *The standard defines the element <style:text-properties>*

This element is supported in Excel 2013 and later.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

This element is supported in Excel 2013 and later.

Excel uses text styles for headers and footers.

This element is supported in Excel 2013 and later.

On load, Excel applies only the non-asian or non-complex version of the font property, if it is specified, for any font property that ends in "-asian" or "-complex". If the non-asian or non-complex version of the property is not specified, then Excel applies the font property that ends in "-asian" or "-complex", and that is read last.

On save, Excel writes the same value for all three types of these font properties. This is because Excel does not support dynamically selecting a different font based on evaluating UNICODE characters as either CJK, CTL, or other.

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>



- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- h. *The standard defines the element <style:text-properties>, contained within the parent element <number:boolean-style>*

This element is not supported in Excel 2013 or later.

- i. *The standard defines the element <style:text-properties>, contained within the parent element <number:currency-style>*

This element is supported in Excel 2013 and later.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- j. *The standard defines the element <style:text-properties>, contained within the parent element <number:date-style>*

This element is supported in Excel 2013 and later.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- k. *The standard defines the element <style:text-properties>, contained within the parent element <number:number-style>*

This element is supported in Excel 2013 and later.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- l. *The standard defines the element <style:text-properties>, contained within the parent element <number:percentage-style>*

This element is supported in Excel 2013 and later.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- m. *The standard defines the element <style:text-properties>, contained within the parent element <number:text-style>*

This element is supported in Excel 2013 and later.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- n. *The standard defines the element <style:text-properties>, contained within the parent element <number:time-style>*

This element is supported in Excel 2013 and later.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- o. *The standard defines the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.416 Part 3 Section 16.31.1, text:linenumbering-configuration**

- a. *The standard defines the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This element is supported in Word 2013 and later.

Word saves the line numbering configuration only if the following conditions are met:

All sections restart per page.

All sections start line numbering at 1.

All sections have the same distance between the line numbering and the text.

All sections have line numbering that increments by the same amount.

#### **2.1.417 Part 3 Section 16.31.2, text:linenumbering-separator**

- a. *The standard defines the element <text:linenumbering-separator>, contained within the parent element <text:linenumbering-configuration>*

This element is not supported in Word 2013 or later.

#### **2.1.418 Part 3 Section 16.31.3, text:notes-configuration**

- a. *The standard defines the element <text:notes-configuration>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:notes-configuration>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <text:notes-configuration>, contained within the parent element <style:section-properties>*

This element is not supported in Excel 2013 or later.

- d. *The standard defines the element <text:notes-configuration>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

#### **2.1.419 Part 3 Section 16.31.4, text:note-continuation-notice-forward**

- a. *The standard defines the attribute text:note-continuation-notice-forward, contained within the element <text:notes-configuration>*

This attribute is not supported in Word 2013 or later.

#### **2.1.420 Part 3 Section 16.31.5, text:note-continuation-notice-backward**

- a. *The standard defines the attribute text:note-continuation-notice-backward, contained within the element <text:notes-configuration>*

This attribute is not supported in Word 2013 or later.

#### **2.1.421 Part 3 Section 16.31.6, text:bibliography-configuration**

- a. *The standard defines the element <text:bibliography-configuration>*

This element is not supported in Word 2013 or later.

## 2.1.422 Part 3 Section 16.32, text:list-style

- a. *The standard defines the element <text:list-style>, contained within the parent element <style:graphic-properties>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:list-style>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element <text:list-style>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- d. *The standard defines the element <text:list-style>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## 2.1.423 Part 3 Section 16.34, text:list-level-style-number

- a. *The standard defines the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

**OfficeArt Math** in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes. (1) On save, Excel uses the following mappings between the "buAutoNum" string values and the style:num-prefix, style:num-suffix, style:num-format, and style:num-letter-sync attributes in ODF:

(1.1) The string value "buAutoNum" equals the value "arabicPlain" is written as style:num-format equals the value "1".

(1.2) The string value "buAutoNum" values "circleNumWdBlackPlain" and "circleNumWdWhitePlain" are written as style:num-format equals the value "1" and style:num-letter-sync equals the value "true".

(1.3) The string value "buAutoNum" equals the value "arabicParenR" is written as style:num-format equals the value "1" and style:num-suffix equals the value ")".

(1.4) The string value "buAutoNum" equals the value "arabicPeriod" is written as style:num-format equals the value "1" and style:num-suffix equals the value ".".

(1.5) The string value "buAutoNum" equals the value "arabicParenBoth" is written as style:num-format equals the value "1", style:num-prefix equals the value "(", and style:num-suffix equals the value ")".

(1.6) The string value "buAutoNum" equals the value "hindiNumParenR" is written as style:num-format equals the value "१ , २ , ३ , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.7) The string value "buAutoNum" equals the value "hindiNumPeriod" is written as style:num-format equals the value "१ , २ , ३ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.8) The string value "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value "1 , 2 , 3 , ..." and style:num-letter-sync equals the value "true".

(1.9) The string value "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "① , ② , ③ , ..." and style:num-letter-sync equals the value "true".

(1.10) The string value "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value "1., 2., 3., ..." and style:num-letter-sync equals the value "true".

(1.11) The string value "buAutoNum" equals the value "thaiNumParenR" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.12) The string value "buAutoNum" equals the value "thaiNumPeriod" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.13) The string value "buAutoNum" equals the value "thaiNumParenBoth" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.14) The string value "buAutoNum" equals the value "alphaLcParenR" is written as style:num-format equals the value "a", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.15) The string value "buAutoNum" equals the value "alphaUcParenR" is written as style:num-format equals the value "A", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.16) The string value "buAutoNum" equals the value "alphaLcPeriod" is written as style:num-format equals the value "a", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.17) The string value "buAutoNum" equals the value "alphaUcPeriod" is written as style:num-format equals the value "A", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.18) The string value "buAutoNum" equals the value "alphaLcParenBoth" is written as style:num-format equals the value "a", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.19) The string value "buAutoNum" equals the value "alphaUcParenBoth" is written as style:num-format equals the value "A", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.20) The string value "buAutoNum" equals the value "romanLcParenR" is written as style:num-format equals the value "i" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.21) The string value "buAutoNum" equals the value "romanUcParenR" is written as style:num-format equals the value "I" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.22) The string value "buAutoNum" equals the value "romanLcPeriod" is written as style:num-format equals the value "i" and style:num-suffix equals the value ".".

(1.23) The string value "buAutoNum" equals the value "romanUcPeriod" is written as style:num-format equals the value "I" and style:num-suffix equals the value ".".

(1.24) The string value "buAutoNum" equals the value "romanLcParenBoth" is written as style:num-format equals the value "i", style:num-prefix equals the value "(", and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.25) The string value "buAutoNum" equals the value "romanUcParenBoth" is written as style:num-format equals the value "I", style:num-prefix equals the value "(", and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.26) The string value "buAutoNum" equals the value "hebrew2Minus" is written as style:num-format equals the value "א , ב , ג , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

(1.27) The string value "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "أ , ب , ت , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

(1.28) The string value "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "أ , ب , ج , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

(1.29) The string value "buAutoNum" equals the value "hindiAlphaPeriod" is written as style:num-format equals the value "अ, आ, इ, ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.30) The string value "buAutoNum" equals the value "hindiAlpha1Period" is written as style:num-format equals the value "क, ख, ग, ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.31) The string value "buAutoNum" equals the value "thaiAlphaParenR" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.32) The string value "buAutoNum" equals the value "thaiAlphaPeriod" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.33) The string value "buAutoNum" equals the value "thaiAlphaParenBoth" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.34) The string value "buAutoNum" equals the value "ea1ChsPlain", "ea1ChtPlain", and "ea1JpnKorPlain" are written as style:num-format equals the value "一, 二, 三, 四..." and style:num-letter-sync equals the value "true".

(1.35) The string value "buAutoNum" equals the value "ea1ChsPeriod", "ea1ChtPeriod", and "ea1JpnKorPeriod" are written as style:num-format equals the value "一, 二, 三, 四...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.36) The string value "buAutoNum" equals the value "ea1JpnChsDbPeriod" is written as style:num-format equals the value "一, 二, 三, 四, ...", style:num-suffix equals the value ". " (double-byte period UNICODE FF0E), and style:num-letter-sync equals the value "true".

On read, the style:num-format, style:num-prefix, and style:num-suffix attributes are considered together to determine the "buAutoNum" value to use in OOXML. The style:num-format attribute is the key attribute and determines the default mapping if the prefix and suffix characters are not supported. The mapping is as follows:

(2.1) For style:num-format equals the value "1":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenR".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "arabicPeriod".

In all other cases where style:num-format equals the value "1", then "buAutoNum" equals the value "arabicPlain".

(2.2) For style:num-format equals the value "a":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenR".

In all other cases where style:num-format equals the value "a", then "buAutoNum" equals the value "alphaLcPeriod".

(2.3) For style:num-format equals the value "A":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaUcParenR".

In all other cases where style:num-format equals the value "A", then "buAutoNum" equals the value "alphaUcPeriod".

(2.4) For style:num-format equals the value "i":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenR".

In all other cases where style:num-format equals the value "i", then "buAutoNum" equals the value "romanLcPeriod".

(2.5) For style:num-format equals the value "I":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenR".

In all other cases where style:num-format equals the value "I", then "buAutoNum" equals the value "romanUcPeriod".

(2.6) In all cases where style:num-format equals the value "أ , ب , ت ,..." or style:num-format equals the value "ا ", then "buAutoNum" equals the value "arabic1Minus".

(2.7) In all cases where style:num-format equals the value "أ , ب , ج ,..." , then "buAutoNum" equals the value "arabic2Minus".

(2.8) In all cases where style:num-format equals the value "1,2,3,..." or style:num-format equals the value "1.", then "buAutoNum" equals the value "arabicDbPeriod".

(2.9) In all cases where style:num-format equals the value " 1 , 2 , 3 ,..." or style:num-format equals the value " 1 ", then "buAutoNum" equals the value "arabicDbPlain".

(2.10) In all cases where style:num-format equals the value "①,②,③,..." or style:num-format equals the value "①", then "buAutoNum" equals the value "circleNumDbPlain".

(2.11) For style:num-format equals the value "一, 二, 三, 四,..." or "style:num-format equals the value "—":



If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "ea1JpnKorPeriod".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ". " (double-byte period UNICODE FF0E), then "buAutoNum" equals the value "ea1JpnChsDbPeriod".

In all other cases where style:num-format equals the value "一, 二, 三, 四, ..." or "style:num-format equals the value "—", then "buAutoNum" equals the value "ea1JpnKorPlain".

(2.12) In all cases where style:num-format equals the value "א, ב, ג, ..." or style:num-format equals the value "א ", then "buAutoNum" equals the value "hebrew2Minus".

(2.13) In all cases where style:num-format equals the value "क, ख, ग, ..." or "क", "buAutoNum" equals the value "hindiAlpha1Period".

(2.14) In all cases where style:num-format equals the value "अ, आ, इ, ..." or "अ", "buAutoNum" equals the value "hindiAlphaPeriod".

(2.15) For style:num-format equals the value "१, २, ३, ..." or style:num-format equals the value "१ ":

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "hindiNumParenR".

In all other cases where style:num-format equals the value "१, २, ३, ..." or style:num-format equals the value "१ ", then "buAutoNum" equals the value "hindiNumPeriod".

(2.16) For style:num-format equals the value "๑, ๒, ๓, ...":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiAlphaParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiAlphaPeriod".

In all other cases where style:num-format equals the value "๑, ๒, ๓, ...", then "buAutoNum" equals the value "thaiAlphaParenR".

(2.17) For style:num-format equals the value "๑, ๒, ๓, ...":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiNumParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiNumPeriod".

In all other cases where style:num-format equals the value "๑, ๒, ๓, ...", then "buAutoNum" equals the value "thaiNumParenR".

(2.18) If style:num-format equals the value "empty", the OOXML property "buNone" is set.

(2.19) If style:num-format contains anything other than what is specified previously, "buAutoNum" equals the value "arabicPlain".

- b. *The standard defines the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the style:num-format, style:num-prefix, and style:num-suffix attributes are considered together to determine the "buAutoNum" value to use in OOXML. style:num-format is the key attribute and determines the default mapping if the prefix and suffix characters are not supported. The mapping is as follows:

1.1) For style:num-format equals the value "1":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenR".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "arabicPeriod".

In all other cases where style:num-format equals the value "1", then "buAutoNum" equals the value "arabicPlain".

1.2) For style:num-format equals the value "a":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenR".

In all other cases where style:num-format equals the value "a", then "buAutoNum" equals the value "alphaLcPeriod".

1.3) For style:num-format equals the value "A":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaUcParenR".

In all other cases where style:num-format equals the value "A", then "buAutoNum" equals the value "alphaUcPeriod".

1.4) For style:num-format equals the value "i":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenR".

In all other cases where style:num-format equals the value "i", then "buAutoNum" equals the value "romanLcPeriod".

1.5) For style:num-format equals the value "I":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenR".

In all other cases where style:num-format equals the value "I", then "buAutoNum" equals the value "romanUcPeriod".

1.6) In all cases where style:num-format equals the value "أ , ب , ت ,..." or style:num-format equals the value "ا ", then "buAutoNum" equals the value "arabic1Minus".

1.7) In all cases where style:num-format equals the value "أ , ب , ج ,..." , then "buAutoNum" equals the value "arabic2Minus".

1.8) In all cases where style:num-format equals the value "1,2,3,..." or style:num-format equals the value "1.", then "buAutoNum" equals the value "arabicDbPeriod".

1.9) In all cases where style:num-format equals the value " 1 , 2 , 3 ,..." or style:num-format equals the value " 1 ", then "buAutoNum" equals the value "arabicDbPlain".

1.10) In all cases where style:num-format equals the value "①,②,③,..." or style:num-format equals the value "①", then "buAutoNum" equals the value "circleNumDbPlain".

1.11) For style:num-format equals the value "一 , 二 , 三 , 四 ,..." or "style:num-format equals the value "一":

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "ea1JpnKorPeriod".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ". ." (double-byte period UNICODE FF0E), then "buAutoNum" equals the value "ea1JpnChsDbPeriod".

In all other cases where style:num-format equals the value "一 , 二 , 三 , 四 , ..." or "style:num-format equals the value "一", then "buAutoNum" equals the value "ea1JpnKorPlain".

1.12) In all cases where style:num-format equals the value "א , ב , ג , ..." or style:num-format equals the value "א ", then "buAutoNum" equals the value "hebrew2Minus".

1.13) In all cases where style:num-format equals the value "क , ख , ग , ..." or "क", "buAutoNum" equals the value "hindiAlpha1Period".

1.14) In all cases where style:num-format equals the value "अ , आ , इ , ..." or "अ", "buAutoNum" equals the value "hindiAlphaPeriod".

1.15) For style:num-format equals the value "१ , २ , ३ , ..." or style:num-format equals the value "१ ":

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "hindiNumParenR".

In all other cases where style:num-format equals the value "१ , २ , ३ , ..." or style:num-format equals the value "१ ", then "buAutoNum" equals the value "hindiNumPeriod".

1.16) For style:num-format equals the value "१ , २ , ३ ":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiAlphaParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiAlphaPeriod".

In all other cases where style:num-format equals the value "๓ , ๔ , ๕ , ...", then "buAutoNum" equals the value "thaiAlphaParenR".

1.17) For style:num-format equals the value "๑ , ๒ , ๓ , ...":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiNumParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiNumPeriod".

In all other cases where style:num-format equals the value "๑ , ๒ , ๓ , ...", then "buAutoNum" equals the value "thaiNumParenR".

1.18) If style:num-format equals the value empty, the OOXML property "buNone" is set.

1.19) If style:num-format contains anything other than what is specified previously, "buAutoNum" equals the value "arabicPlain".

On write, the following mappings are used between the "buAutoNum" string values used in OOXML and the style:num-prefix, style:num-suffix, style:num-format, and style:num-letter-sync attributes in ODF:

2.1) "buAutoNum" equals the value "arabicPlain" is written as style:num-format equals the value "1".

2.2) "buAutoNum" values "circleNumWdBlackPlain" and "circleNumWdWhitePlain" are written as style:num-format equals the value "1" and style:num-letter-sync equals the value "true".

2.3) "buAutoNum" equals the value "arabicParenR" is written as style:num-format equals the value "1" and style:num-suffix equals the value ")".

2.4) "buAutoNum" equals the value "arabicPeriod" is written as style:num-format equals the value "1" and style:num-suffix equals the value ".".

2.5) "buAutoNum" equals the value "arabicParenBoth" is written as style:num-format equals the value "1" and style:num-prefix equals the value "(", style:num-suffix equals the value ")".

2.6) "buAutoNum" equals the value "hindiNumParenR" is written as style:num-format equals the value "१ , २ , ३ , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

2.7) "buAutoNum" equals the value "hindiNumPeriod" is written as style:num-format equals the value "१ , २ , ३ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

2.8) "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value "1 , 2 , 3 , ..." and style:num-letter-sync equals the value "true".

2.9) "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "① , ② , ③ , ..." and style:num-letter-sync equals the value "true".

2.10) "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value "1., 2., 3., ..." and style:num-letter-sync equals the value "true".

- 2.11) "buAutoNum" equals the value "thaiNumParenR" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.12) "buAutoNum" equals the value "thaiNumPeriod" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.13) "buAutoNum" equals the value "thaiNumParenBoth" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.14) "buAutoNum" equals the value "alphaLcParenR" is written as style:num-format equals the value "a", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.15) "buAutoNum" equals the value "alphaUcParenR" is written as style:num-format equals the value "A", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.16) "buAutoNum" equals the value "alphaLcPeriod" is written as style:num-format equals the value "a", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.17) "buAutoNum" equals the value "alphaUcPeriod" is written as style:num-format equals the value "A", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.18) "buAutoNum" equals the value "alphaLcParenBoth" is written as style:num-format equals the value "a", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.19) "buAutoNum" equals the value "alphaUcParenBoth" is written as style:num-format equals the value "A", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.20) "buAutoNum" equals the value "romanLcParenR" is written as style:num-format equals the value "i" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.21) "buAutoNum" equals the value "romanUcParenR" is written as style:num-format equals the value "I" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.22) "buAutoNum" equals the value "romanLcPeriod" is written as style:num-format equals the value "i" and style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.23) "buAutoNum" equals the value "romanUcPeriod" is written as style:num-format equals the value "I" and style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.24) "buAutoNum" equals the value "romanLcParenBoth" is written as style:num-format equals the value "i", style:num-prefix equals the value "(", and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.25) "buAutoNum" equals the value "romanUcParenBoth" is written as style:num-format equals the value "I", style:num-prefix equals the value "(", and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.26) "buAutoNum" equals the value "hebrew2Minus" is written as style:num-format equals the value "א , ב , ג , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".
- 2.27) "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "أ , ب , ت , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

2.28) "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "ا , ب , ج , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

2.29) "buAutoNum" equals the value "hindiAlphaPeriod" is written as style:num-format equals the value "अ, आ, इ, ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

2.30) "buAutoNum" equals the value "hindiAlpha1Period" is written as style:num-format equals the value "क, ख, ग, ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

2.31) "buAutoNum" equals the value "thaiAlphaParenR" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

2.32) "buAutoNum" equals the value "thaiAlphaPeriod" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

2.33) "buAutoNum" equals the value "thaiAlphaParenBoth" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

2.34) "buAutoNum" equals the values "ea1ChsPlain", "ea1ChtPlain", and "ea1JpnKorPlain" are written as style:num-format equals the value "一, 二, 三, 四..." and style:num-letter-sync equals the value "true".

2.35) "buAutoNum" equals the values "ea1ChsPeriod", "ea1ChtPeriod", and "ea1JpnKorPeriod" are written as style:num-format equals the value "一, 二, 三, 四...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

2.36) "buAutoNum" equals the value "ea1JpnChsDbPeriod" is written as style:num-format equals the value "一, 二, 三, 四, ...", style:num-suffix equals the value ". " (double-byte period UNICODE FF0E), and style:num-letter-sync equals the value "true".

#### **2.1.424 Part 3 Section 16.36, text:outline-style**

- a. *The standard defines the attribute text:outline-style*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.425 Part 3 Section 16.42.1, draw:gradient**

- a. *The standard defines the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>

- <draw:text-box>
  - <draw:custom-shape>
- b. *The standard defines the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.426 Part 3 Section 16.42.2, svg:linearGradient**

- a. *The standard defines the element <svg:linearGradient>, contained within the parent element <office:styles>*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the element <svg:linearGradient>, contained within the parent element <office:styles>*

Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <svg:linearGradient>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.427 Part 3 Section 16.42.3, svg:radialGradient**

- a. *The standard defines the element <svg:radialGradient>, contained within the parent element <office:styles>*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the element <svg:radialGradient>, contained within the parent element <office:styles>*



Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the element <svg:radialGradient>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

#### **2.1.428 Part 3 Section 16.42.5, draw:hatch**

- a. *The standard defines the element <draw:hatch>, contained within the parent element <office:styles>*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the element <draw:hatch>, contained within the parent element <office:styles>*

Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <draw:hatch>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.429 Part 3 Section 16.42.6, draw:fill-image**

- a. *The standard defines the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

#### **2.1.430 Part 3 Section 16.42.7, draw:opacity**

- a. *The standard defines the element <draw:opacity>, contained within the parent element <office:styles>*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:opacity, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the element <draw:opacity>, contained within the parent element <office:styles>*

Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute draw:opacity, contained within the element <style:background-image>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute draw:opacity, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- f. *The standard defines the element <draw:opacity>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>

- <draw:text-box>
  - <draw:custom-shape>
- g. *The standard defines the attribute draw:opacity, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.431 Part 3 Section 16.42.8, draw:marker**

- a. *The standard defines the element <draw:marker>, contained within the parent element <office:styles>*

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:line>
- <draw:connector>
- <draw:measure>

Word interprets all marker styles as "solid arrow".

- b. *The standard defines the element <draw:marker>, contained within the parent element <office:styles>*

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:line>
- <draw:connector>
- <draw:measure>

Excel interprets all marker styles as "solid arrow".

- c. *The standard defines the element <draw:marker>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:line>
- <draw:connector>
- <draw:measure>

PowerPoint interprets all marker styles as "solid arrow".

### **2.1.432 Part 3 Section 16.42.9, draw:stroke-dash**

- a. *The standard defines the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:stroke-dash`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

Dash styles that cannot be represented are converted to solid lines.

- c. *The standard defines the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>

- <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- d. *The standard defines the attribute `draw:stroke-dash`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Dash styles that cannot be represented are converted to solid lines.

- e. *The standard defines the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute `draw:stroke-dash`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Dash styles that cannot be represented are converted to solid lines.

### **2.1.433 Part 3 Section 16.43, style:presentation-page-layout**

- a. *The standard defines the attribute style:name, contained within the element <style:presentation-page-layout>*
- b. *The standard defines the element <style:presentation-page-layout>*

This element is supported in PowerPoint 2013 and later.

On load, PowerPoint ignores presentation page layouts. On save, PowerPoint writes out presentation page layouts.

### **2.1.434 Part 3 Section 16.44, presentation:placeholder**

- a. *The standard defines the attribute presentation:placeholder*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint uses this attribute to describe placeholders that are empty. It is ignored on load.

### **2.1.435 Part 3 Section 17.2, style:page-layout-properties**

- a. *The standard defines the element <style:page-layout-properties>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:page-layout-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:



- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the element <style:page-layout-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.436 Part 3 Section 17.3, style:background-image**

- a. *The standard defines the element <style:background-image>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:background-image>, contained within the parent element <style:header-footer-properties>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the element <style:background-image>, contained within the parent element <style:paragraph-properties>*

This element is not supported in Word 2013 or later.

- d. *The standard defines the element <style:background-image>, contained within the parent element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute style:background-image, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- f. *The standard defines the element <style:background-image>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the element <style:background-image>, contained within the parent element <style:header-footer-properties>*

This element is not supported in Excel 2013 or later.

- h. *The standard defines the element <style:background-image>, contained within the parent element <style:section-properties>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the element <style:background-image>, contained within the parent element <style:table-properties>*

This element is not supported in Excel 2013 or later.

- j. *The standard defines the attribute style:background-image, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- k. *The standard defines the attribute style:background-image, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the element <style:background-image>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the element <style:background-image>, contained within the parent element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- n. *The standard defines the element <style:background-image>, contained within the parent element <Style:table-cell-properties>*

- o. *The standard defines the element <style:background-image>, contained within the parent element <Style:table-row-properties>*

- p. *The standard defines the attribute style:background-image, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- q. *The standard defines the attribute style:background-image, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.437 Part 3 Section 17.4, style:footnote-sep**

- a. *The standard defines the element <style:footnote-sep>*

This element is not supported in Excel 2013 or later.

- b. *The standard defines the attribute style:footnote-sep, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

### **2.1.438 Part 3 Section 17.5, style:header-footer-properties**

- a. *The standard defines the element <style:header-footer-properties>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:header-footer-properties>*

This element is supported in Excel 2013 and later.

On save, Excel does not write the header or footer information if the "Different First Page" option is selected for the worksheet.

Excel's maximum length for headers and footers is 255 characters.

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the element <style:header-footer-properties>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math h in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.439 Part 3 Section 17.6, style:paragraph-properties

- a. *The standard defines the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:paragraph-properties>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.440 Part 3 Section 17.7, style:tab-stops**

- a. *The standard defines the element <style:tab-stops>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:tab-stops>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <style:tab-stops>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- `<draw:custom-shape>`.

#### **2.1.441 Part 3 Section 17.8, style:tab-stop**

- a. *The standard defines the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This element is not supported in Excel 2013 or later.

#### **2.1.442 Part 3 Section 17.9, style:drop-cap**

- a. *The standard defines the element `<style:drop-cap>`*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element `<style:drop-cap>`, contained within the parent element `<style:paragraph-properties>`*

This element is supported in Word 2013 and later.

On save, if a second frame is anchored to the paragraph inside a drop cap, Word will lose the `<style:drop-cap>` element but retain the contents contained within the element tags.

On save and load, if a paragraph is both right-to-left and has a drop cap applied, Word will lose the `<style:drop-cap>` element but retain the contents contained within the element tags.

On save and load, if a paragraph has both `fo:break-before=column` and a drop cap applied, Word will lose the `<style:drop-cap>` element but retain the contents contained within the element tags.

- c. *The standard defines the element `<style:drop-cap>`*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- d. *The standard defines the element `<style:drop-cap>`*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.443 Part 3 Section 17.10, style:ruby-properties

- a. *The standard defines the element <style:ruby-properties>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:ruby-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>



- c. *The standard defines the element <style:ruby-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.444 Part 3 Section 17.11, style:section-properties**

- a. *The standard defines the element <style:section-properties>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:section-properties>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. *The standard defines the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.445 Part 3 Section 17.12, style:columns**

a. *The standard defines the element <style:columns>, contained within the parent element <style:graphic-properties>*

This element is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <style:columns>, contained within the parent element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

c. *The standard defines the element <style:columns>*

This element is not supported in Excel 2013 or later.

d. *The standard defines the element <style:columns>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the element <style:columns>, contained within the parent element <style:page-layout-properties>*

This element is not supported in Excel 2013 or later.

- f. *The standard defines the element <style:columns>, contained within the parent element <style:section-properties>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the element <style:columns>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- h. *The standard defines the element <style:columns>, contained within the parent element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the attribute style:columns, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.446 Part 3 Section 17.13, style:column**

- a. *The standard defines the element <style:column>, contained within the parent element <style:columns>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:column>, contained within the parent element <style:columns>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <style:column>, contained within the parent element <style:columns>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.447 Part 3 Section 17.14, style:column-sep

- a. *The standard defines the element <style:column-sep>, contained within the parent element <style:columns>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:column-sep>, contained within the parent element <style:columns>*

This element is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <style:column-sep>, contained within the parent element <style:columns>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- `<draw:custom-shape>`.

### 2.1.448 Part 3 Section 17.15, style:table-properties

- a. *The standard defines the element `<style:table-properties>`*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element `<style:table-properties>`*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the element `<style:table-properties>`*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### 2.1.449 Part 3 Section 17.16, style:table-column-properties

- a. *The standard defines the element `<style:table-column-properties>`*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "style:use-optimal-column-width", contained within the attribute style:table-column-properties, contained within the element <style:style>*

This property is supported in Excel 2013 and later.

On load, if the style:use-optimal-column-width attribute contains the value "true", then Excel may widen the column to fit the digits of a number value entered in the column.

On save, Excel writes the value "true" for the style:use-optimal-column-width attribute for columns that do not have a default width because they have been widened to fit an existing number value.

Excel writes the value "false" for the style:use-optimal-column-width attribute if the column has been set to a custom size or the column has not been automatically widened to fit an existing number value.

- c. *The standard defines the property "style-properties-content", contained within the attribute style:table-column-properties, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the element <style:table-column-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the element <style:table-column-properties>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.450 Part 3 Section 17.17, style:table-row-properties

- a. *The standard defines the element <style:table-row-properties>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "fo:background-color", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

- c. *The standard defines the property "fo:break-before", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is supported in Excel 2013 and later.

On load, if the fo:break-after property is set to any value other than "auto", then Excel sets a page break after the corresponding row or column. If the fo:break-before property is set to any value other than "auto" and the fo:break-after property is not specified, or set to "auto", then Excel sets a page break before the corresponding row or column. If both the fo:break-before and fo:break-after properties have a value of "auto" or are not specified, then Excel does not set a page break for the corresponding row or column.

On save, Excel writes out the value "auto" for the fo:break-before property, and either nothing or "page" for the fo:break-after property.

- d. *The standard defines the property "fo:keep-together", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the property "style:background-image", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

- f. *The standard defines the element <style:table-row-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>



- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

g. *The standard defines the element <style:table-row-properties>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.451 Part 3 Section 17.18, style:table-cell-properties**

a. *The standard defines the element <style:table-cell-properties>*

**OfficeArt Math** in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <style:table-cell-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

c. *The standard defines the element <style:table-cell-properties>*

This element is not supported in PowerPoint 2013, PowerPoint 2016, PowerPoint 2019.

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## **2.1.452 Part 3 Section 17.19, style:list-level-properties**

a. *The standard defines the element <style:list-level-properties>*

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt.

b. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-bullet>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt.

c. *The standard defines the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, and for SmartArt.

- d. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-bullet>*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes and for SmartArt and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-image>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- f. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-number>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- g. *The standard defines the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- h. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-image>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.453 Part 3 Section 17.21, style:graphic-properties

- a. *The standard defines the element <style:graphic-properties>*

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

**OfficeArt Math** in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:graphic-properties>*

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>

- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

c. *The standard defines the element <style:graphic-properties>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.454 Part 3 Section 18.2, W3C Schema Datatypes**

- a. *The standard defines the element <base64Binary>*  
This element is not supported in Excel 2013 or later.
- b. *The standard defines the element <IDREF>*  
This element is not supported in Excel 2013 or later.
- c. *The standard defines the element <IDREFS>*  
This element is not supported in Excel 2013 or later.
- d. *The standard defines the element <formula>*  
This element is not supported in Excel 2013 or later.

#### **2.1.455 Part 3 Section 18.3.2, anyIRI**

- a. *The standard defines the element <anyIRI>, contained within the parent element <xlink:href>*  
This element is not supported in Excel 2013 or later.

#### **2.1.456 Part 3 Section 18.3.16, language**

- a. *The standard defines the element <language>*  
This element is not supported in Excel 2013 or later.

#### **2.1.457 Part 3 Section 18.3.25, points**

- a. *The standard defines the element <points>*  
This element is not supported in Excel 2013 or later.

#### **2.1.458 Part 3 Section 18.3.27, relativeLength**

- a. *The standard defines the element <relativeLength>*  
This element is not supported in Excel 2013 or later.

#### **2.1.459 Part 3 Section 18.3.34, targetFrameName**

- a. *The standard defines the element <targetFrameName>*  
This element is not supported in Excel 2013 or later.

#### **2.1.460 Part 3 Section 18.3.39, variableName**

- a. *The standard defines the element <variableName>*  
This element is not supported in Excel 2013 or later.

### **2.1.461 Part 3 Section 18.3.40, vector3D**

- a. *The standard defines the element <vector3D>*

This element is not supported in Excel 2013 or later.

### **2.1.462 Part 3 Section 19.4, anim:audio-level**

- a. *The standard defines the attribute anim:audio-level, contained within the element <anim:audio>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.463 Part 3 Section 19.6, anim:formula**

- a. *The standard defines the attribute anim:formula*

This attribute is supported in PowerPoint 2013 and later.

On load, the entire animation will be lost if the operators "exp" or "log" are present. On save, the entire animation will be lost if any of the following elements are present in the native PowerPoint animation: "^", "?", "=", ">=", "<=", "!", "!".

### **2.1.464 Part 3 Section 19.7, anim:id**

- a. *The standard defines the attribute anim:id*

This attribute is not supported in PowerPoint 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

### **2.1.465 Part 3 Section 19.11, anim:sub-item**

- a. *The standard defines the attribute anim:sub-item*

This attribute is not supported in PowerPoint 2013 or later.

- b. *The standard defines the property "background", contained within the attribute anim:sub-item*

This property is not supported in PowerPoint 2013 or later.

- c. *The standard defines the property "text", contained within the attribute anim:sub-item*

This property is not supported in PowerPoint 2013 or later.

- d. *The standard defines the property "whole", contained within the attribute anim:sub-item*

This property is not supported in PowerPoint 2013 or later.

- e. *The standard defines the attribute anim:sub-item, contained within the element <anim:iterate>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.466 Part 3 Section 19.15, chart:class**

- a. *The standard defines the property "gantt", contained within the attribute chart:class*

This property is not supported in Excel 2013 or later.

- b. *The standard defines the property "minor", contained within the attribute chart:class*



This property is not supported in Excel 2013 or later.

Excel saves the minor gridlines element on a category axis, but does not save it on a value axis.

- c. *The standard defines the property "stock", contained within the attribute chart:class*

This property is supported in Excel 2013 and later.

Stock charts can have three (3) or more series.

#### **2.1.467 Part 3 Section 19.16, chart:column-mapping**

- a. *The standard defines the attribute chart:column-mapping*

This attribute is not supported in Excel 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

#### **2.1.468 Part 3 Section 19.17, chart:data-source-has-labels**

- a. *The standard defines the attribute chart:data-source-has-labels*

This attribute is supported in Excel 2013 and later.

On load, this attribute is ignored. It is saved if the chart uses a local <table:table> element.

*This attribute was deprecated in the ODF 1.2 standard.*

#### **2.1.469 Part 3 Section 19.22, chart:legend-align**

- a. *The standard defines the attribute chart:legend-align*

This attribute is not supported in Excel 2013 or later.

On load, this attribute is ignored. On save, it takes on a value of "center" when a "chart:legend-position" attribute is saved.

#### **2.1.470 Part 3 Section 19.23, chart:legend-position**

- a. *The standard defines the property "bottom-end", contained within the attribute chart:legend-position*

This property is not supported in Excel 2013 or later.

- b. *The standard defines the property "bottom-start", contained within the attribute chart:legend-position*

This property is not supported in Excel 2013 or later.

- c. *The standard defines the property "top-end", contained within the attribute chart:legend-position*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "top-start", contained within the attribute chart:legend-position*

This property is not supported in Excel 2013 or later.

### **2.1.471 Part 3 Section 19.26, chart:row-mapping**

- a. *The standard defines the attribute chart:row-mapping*

This attribute is not supported in Excel 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

### **2.1.472 Part 3 Section 19.37, db:catalog-name**

- a. *The standard defines the attribute office:date-value, contained within the element <table:table-cell>*

### **2.1.473 Part 3 Section 19.68, db:max-row-count**

- a. *The standard defines the attribute table:number-matrix-rows-spanned, contained within the element <table:table-cell>*

### **2.1.474 Part 3 Section 19.92, dr3d:ambient-color**

- a. *The standard defines the attribute dr3d:ambient-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:ambient-color, contained within the parent element <chart:plot-area>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:ambient-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute dr3d:ambient-color, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.475 Part 3 Section 19.94, dr3d:diffuse-color**

- a. *The standard defines the attribute dr3d:diffuse-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:diffuse-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:diffuse-color, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.476 Part 3 Section 19.96, dr3d:distance**

- a. *The standard defines the attribute dr3d:distance, contained within the parent element <chart:plot-area>*

This attribute is supported in Excel 2013 and later.

Excel saves this element, but ignores it on load.

### **2.1.477 Part 3 Section 19.98, dr3d:focal-length**

- a. *The standard defines the attribute dr3d:focal-length, contained within the parent element <chart:plot-area>*

This attribute is supported in Excel 2013 and later.

Excel saves this element but ignores it on load.

### **2.1.478 Part 3 Section 19.99, dr3d:lighting-mode**

- a. *The standard defines the attribute dr3d:lighting-mode, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:lighting-mode, contained within the parent element <chart:plot-area>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:lighting-mode, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute dr3d:lighting-mode, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.479 Part 3 Section 19.102, dr3d:projection**

- a. *The standard defines the attribute dr3d:projection, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- b. *The standard defines the property "parallel", contained within the attribute dr3d:projection, contained within the parent element <chart:plot-area>*

This property is supported in Excel 2013 and later.

Excel loads this element, but always saves it as perspective 0.1.

- c. *The standard defines the attribute dr3d:projection, contained within the element <draw:enhanced-geometry>*

Excel 2013 supports this attribute for the <draw:custom-shape> element.

- d. *The standard defines the attribute `dr3d:projection`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

### **2.1.480 Part 3 Section 19.103, `dr3d:shade-mode`**

- a. *The standard defines the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this attribute for the `<draw:custom-shape>` element.

- b. *The standard defines the property "draft", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this enum for the `<draw:custom-shape>` element.

- c. *The standard defines the property "flat", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this enum for `draw:custom-shape`. Word changes this to `gourard`.

- d. *The standard defines the property "gourard", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this enum for the `<draw:custom-shape>` element.

- e. *The standard defines the property "phong", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this enum for `draw:custom-shape`. Word changes this to `gourard`.

- f. *The standard defines the attribute `dr3d:shade-mode`, contained within the parent element `<chart:plot-area>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

- h. *The standard defines the property "draft", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this enum for the `<draw:custom-shape>` element.

- i. *The standard defines the property "flat", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this enum for `draw:custom-shape`. Excel changes this to `gourard`.

- j. *The standard defines the property "gourard", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this enum for the `<draw:custom-shape>` element.

- k. *The standard defines the property "phong", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this enum for `draw:custom-shape`. Excel changes this to `gourard`.

- l. *The standard defines the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

- m. *The standard defines the property "draft", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this enum for the `<draw:custom-shape>` element.

- n. *The standard defines the property "flat", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this enum for `draw:custom-shape`. PowerPoint changes this to `gourard`.

- o. *The standard defines the property "gourard", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this enum for the `<draw:custom-shape>` element.

- p. *The standard defines the property "phong", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this enum for `draw:custom-shape`. PowerPoint changes this to `gourard`.

#### **2.1.481 Part 3 Section 19.104, `dr3d:shadow-slant`**

- a. *The standard defines the attribute `dr3d:shadow-slant`, contained within the parent element `<chart:plot-area>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.482 Part 3 Section 19.107, `dr3d:transform`**

- a. *The standard defines the attribute `dr3d:transform`, contained within the parent element `<chart:plot-area>`*

This attribute is supported in Excel 2013 and later.

"matrix" is the only transform definition that Excel supports.

#### **2.1.483 Part 3 Section 19.108, `dr3d:vpn`**

- a. *The standard defines the attribute `dr3d:vpn`, contained within the parent element `<chart:plot-area>`*

This attribute is supported in Excel 2013 and later.

Excel saves this element but ignores it on load.

#### **2.1.484 Part 3 Section 19.110, `dr3d:vup`**

- a. *The standard defines the attribute `dr3d:vup`, contained within the parent element `<chart:plot-area>`*

This attribute is supported in Excel 2013 and later.

Excel saves this element on write, but ignores it on load.

### **2.1.485 Part 3 Section 19.112, draw:angle**

- a. *The standard defines the attribute draw:angle, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

This attribute is supported in Word 2013 and later.

The draw:angle attribute is only supported when draw:gradient-style attribute is set to "linear".

- b. *The standard defines the attribute draw:angle, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

This attribute is supported in Excel 2013 and later.

The draw:angle attribute is only supported when draw:gradient-style attribute is set to "linear".

- c. *The standard defines the attribute draw:angle, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>
- <table:table-cell>

This attribute is supported in PowerPoint 2013 and later.

The draw:angle attribute is only supported when draw:gradient-style attribute is set to "linear".

### **2.1.486 Part 3 Section 19.114, draw:border**

- a. *The standard defines the attribute draw:border, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:border, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:border, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.487 Part 3 Section 19.115, draw:caption-id**

a. *The standard defines the attribute draw:caption-id*

Word 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

b. *The standard defines the attribute draw:caption-id*

Excel 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

c. *The standard defines the attribute draw:caption-id*

PowerPoint 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>



- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

**2.1.488 Part 3 Section 19.116, draw:caption-point-x**

- a. *The standard defines the attribute draw:caption-point-x, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:caption-point-x, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

**2.1.489 Part 3 Section 19.117, draw:caption-point-y**

- a. *The standard defines the attribute draw:caption-point-y, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:caption-point-y, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

**2.1.490 Part 3 Section 19.118, draw:chain-next-name**

- a. *The standard defines the attribute draw:chain-next-name, contained within the element <draw:text-box>*

This attribute is supported in Word 2013 and later.

Text linking between text boxes in headers or footers are lost on load.

- b. *The standard defines the attribute draw:chain-next-name, contained within the element <draw:text-box>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:chain-next-name, contained within the element <draw:text-box>*

This attribute is not supported in PowerPoint 2013 or later.

**2.1.491 Part 3 Section 19.120, draw:class-names**

- a. *The standard defines the attribute draw:class-names*

Word 2013 does not support this attribute for the following elements:

- <draw:rect>

- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

b. *The standard defines the attribute draw:class-names*

Excel 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

c. *The standard defines the attribute draw:class-names*

This attribute is not supported in PowerPoint 2013 or later.

PowerPoint does not support or preserve this element.

PowerPoint 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

### **2.1.492 Part 3 Section 19.124, draw:concentric-gradient-fill-allowed**

- a. *The standard defines the attribute draw:concentric-gradient-fill-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:concentric-gradient-fill-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:concentric-gradient-fill-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.493 Part 3 Section 19.126, draw:copy-of**

- a. *The standard defines the attribute draw:copy-of, contained within the element <draw:frame>*

This attribute is not supported in Word 2013 or later.

### **2.1.494 Part 3 Section 19.127, draw:corner-radius**

- a. *The standard defines the attribute draw:corner-radius, contained within the element <draw:text-box>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:corner-radius, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute draw:corner-radius, contained within the element <draw:text-box>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute draw:corner-radius, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute draw:corner-radius, contained within the element <draw:text-box>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.495 Part 3 Section 19.129, draw:cx**

- a. *The standard defines the attribute draw:cx, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:cx, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:cx, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.496 Part 3 Section 19.130, draw:cy**

- a. *The standard defines the attribute draw:cy, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- b. *The standard defines the attribute draw:cy, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the attribute draw:cy, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.497 Part 3 Section 19.131, draw:data**

- a. *The standard defines the attribute draw:data, contained within the element <draw:custom-shape>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:data, contained within the element <draw:custom-shape>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:data, contained within the element <draw:custom-shape>*

This attribute is not supported in PowerPoint 2013 or later.

## 2.1.498 Part 3 Section 19.133, draw:display-name

- a. *The standard defines the attribute draw:display-name, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:display-name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:display-name, contained within the element <draw:marker>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:line>
- <draw:connector>
- <draw:measure>

- d. *The standard defines the attribute draw:display-name, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- e. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:line>
- <draw:connector>
- <draw:measure>

- h. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>

- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:line>



- <draw:connector>
  - <draw:measure>
- l. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

#### **2.1.499 Part 3 Section 19.134, draw:distance**

- a. *The standard defines the attribute `draw:distance`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:distance`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the attribute `draw:distance`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.500 Part 3 Section 19.135, draw:dots1**

- a. *The standard defines the attribute `draw:dots1`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:dots1`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:dots1`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

### **2.1.501 Part 3 Section 19.136, `draw:dots1-length`**

- a. *The standard defines the attribute `draw:dots1-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`

- <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- b. *The standard defines the attribute `draw:dots1-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the attribute `draw:dots1-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.502 Part 3 Section 19.137, draw:dots2**

- a. *The standard defines the attribute `draw:dots2`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:dots2`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:dots2`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>

- <draw:custom-shape>

### 2.1.503 Part 3 Section 19.138, draw:dots2-length

- a. *The standard defines the attribute draw:dots2-length, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:dots2-length, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:dots2-length, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

#### **2.1.504 Part 3 Section 19.141, draw:end-color**

- a. *The standard defines the attribute draw:end-color, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:end-color, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:end-color, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### 2.1.505 Part 3 Section 19.143, draw:end-intensity

- a. *The standard defines the attribute draw:end-intensity, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:end-intensity, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:end-intensity, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>



- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.506 Part 3 Section 19.145, draw:enhanced-path**

- a. *The standard defines the attribute draw:enhanced-path, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Word 2013 and later.

On load, Word rounds floats to integers.

- b. *The standard defines the attribute draw:enhanced-path, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Excel 2013 and later.

On load, Excel rounds floats to integers.

- c. *The standard defines the attribute draw:enhanced-path, contained within the element <draw:enhanced-geometry>*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint rounds floats to integers.

### **2.1.507 Part 3 Section 19.146, draw:engine**

- a. *The standard defines the attribute draw:engine, contained within the element <draw:custom-shape>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:engine, contained within the element <draw:custom-shape>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:engine, contained within the element <draw:custom-shape>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.508 Part 3 Section 19.148, draw:extrusion**

- a. *The standard defines the attribute draw:extrusion, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion, contained within the element <draw:enhanced-geometry>*

Excel 2013 supports this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 supports this attribute for the <draw:custom-shape> element.

### **2.1.509 Part 3 Section 19.149, draw:extrusion-allowed**

- a. *The standard defines the attribute draw:extrusion-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:extrusion-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:extrusion-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.510 Part 3 Section 19.150, draw:extrusion-brightness**

- a. *The standard defines the attribute draw:extrusion-brightness, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion-brightness, contained within the element <draw:enhanced-geometry>*

Excel 2013 supports this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-brightness, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 supports this attribute for the <draw:custom-shape> element.

### **2.1.511 Part 3 Section 19.151, draw:extrusion-color**

- a. *The standard defines the attribute draw:extrusion-color, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion-color, contained within the element <draw:enhanced-geometry>*

Excel 2013 supports this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-color, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 supports this attribute for the <draw:custom-shape> element.

### **2.1.512 Part 3 Section 19.152, draw:extrusion-depth**

- a. *The standard defines the attribute draw:extrusion-depth, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute `draw:extrusion-depth`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

- c. *The standard defines the attribute `draw:extrusion-depth`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

### **2.1.513 Part 3 Section 19.153, `draw:extrusion-diffusion`**

- a. *The standard defines the attribute `draw:extrusion-diffusion`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for `draw:custom-shape`. Word always writes out the value 65.536% for this attribute.

- b. *The standard defines the attribute `draw:extrusion-diffusion`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for `draw:custom-shape`. Excel always writes out the value 65.536% for this attribute.

- c. *The standard defines the attribute `draw:extrusion-diffusion`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for `draw:custom-shape`. PowerPoint always writes out the value 65.536% for this attribute.

### **2.1.514 Part 3 Section 19.154, `draw:extrusion-first-light-direction`**

- a. *The standard defines the attribute `draw:extrusion-first-light-direction`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this attribute for `draw:custom-shape`.

- b. *The standard defines the attribute `draw:extrusion-first-light-direction`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for `draw:custom-shape`.

- c. *The standard defines the attribute `draw:extrusion-first-light-direction`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for `draw:custom-shape`.

### **2.1.515 Part 3 Section 19.155, `draw:extrusion-first-light-harsh`**

- a. *The standard defines the attribute `draw:extrusion-first-light-harsh`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

- b. *The standard defines the attribute `draw:extrusion-first-light-harsh`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.

- c. *The standard defines the attribute `draw:extrusion-first-light-harsh`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

#### **2.1.516 Part 3 Section 19.156, `draw:extrusion-first-light-level`**

- a. *The standard defines the attribute `draw:extrusion-first-light-level`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

- b. *The standard defines the attribute `draw:extrusion-first-light-level`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.

- c. *The standard defines the attribute `draw:extrusion-first-light-level`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

#### **2.1.517 Part 3 Section 19.157, `draw:extrusion-light-face`**

- a. *The standard defines the attribute `draw:extrusion-light-face`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

- b. *The standard defines the attribute `draw:extrusion-light-face`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.

- c. *The standard defines the attribute `draw:extrusion-light-face`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

#### **2.1.518 Part 3 Section 19.158, `draw:extrusion-metal`**

- a. *The standard defines the attribute `draw:extrusion-metal`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this attribute for the `<draw:custom-shape>` element.

- b. *The standard defines the attribute `draw:extrusion-metal`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

- c. *The standard defines the attribute `draw:extrusion-metal`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

### **2.1.519 Part 3 Section 19.159, draw:extrusion-number-of-line-segments**

- a. *The standard defines the attribute draw:extrusion-number-of-line-segments, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion-number-of-line-segments, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-number-of-line-segments, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for the <draw:custom-shape> element.

### **2.1.520 Part 3 Section 19.160, draw:extrusion-origin**

- a. *The standard defines the attribute draw:extrusion-origin, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for draw:custom-shape. Word always writes out (-0.5 0.5).

- b. *The standard defines the attribute draw:extrusion-origin, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for draw:custom-shape. Excel always writes out (-0.5 0.5).

- c. *The standard defines the attribute draw:extrusion-origin, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for draw:custom-shape. PowerPoint always writes out (-0.5 0.5).

### **2.1.521 Part 3 Section 19.161, draw:extrusion-rotation-angle**

- a. *The standard defines the attribute draw:extrusion-rotation-angle, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion-rotation-angle, contained within the element <draw:enhanced-geometry>*

Excel 2013 supports this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-rotation-angle, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 supports this attribute for the <draw:custom-shape> element.

### **2.1.522 Part 3 Section 19.162, draw:extrusion-rotation-center**

- a. *The standard defines the attribute draw:extrusion-rotation-center, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion-rotation-center, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-rotation-center, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for the <draw:custom-shape> element.

### **2.1.523 Part 3 Section 19.163, draw:extrusion-second-light-direction**

- a. *The standard defines the attribute draw:extrusion-second-light-direction, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for draw:custom-shape. Word always writes out (-0.05468 0 0.01094).

- b. *The standard defines the attribute draw:extrusion-second-light-direction, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for draw:custom-shape. Excel always writes out (-0.05468 0 0.01094).

- c. *The standard defines the attribute draw:extrusion-second-light-direction, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for draw:custom-shape. PowerPoint always writes out (-0.05468 0 0.01094).

### **2.1.524 Part 3 Section 19.164, draw:extrusion-second-light-harsh**

- a. *The standard defines the attribute draw:extrusion-second-light-harsh, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for draw:custom-shape. Word always writes out false.

- b. *The standard defines the attribute draw:extrusion-second-light-harsh, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for draw:custom-shape. Excel always writes out false.

- c. *The standard defines the attribute draw:extrusion-second-light-harsh, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for draw:custom-shape. PowerPoint always writes out false.

### **2.1.525 Part 3 Section 19.165, draw:extrusion-second-light-level**

- a. *The standard defines the attribute draw:extrusion-second-light-level, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for draw:custom-shape. Word always writes out 37%.

- b. *The standard defines the attribute draw:extrusion-second-light-level, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for draw:custom-shape. Excel always writes out 37%.

- c. *The standard defines the attribute draw:extrusion-second-light-level, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for draw:custom-shape. PowerPoint always writes out 37%.

#### **2.1.526 Part 3 Section 19.166, draw:extrusion-shininess**

- a. *The standard defines the attribute draw:extrusion-shininess, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion-shininess, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-shininess, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for the <draw:custom-shape> element.

#### **2.1.527 Part 3 Section 19.167, draw:extrusion-skew**

- a. *The standard defines the attribute draw:extrusion-skew, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for draw:custom-shape.

- b. *The standard defines the attribute draw:extrusion-skew, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-skew, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for the <draw:custom-shape> element.

#### **2.1.528 Part 3 Section 19.168, draw:extrusion-specularity**

- a. *The standard defines the attribute draw:extrusion-specularity, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for draw:custom-shape. Word always writes out 80%.

- b. *The standard defines the attribute draw:extrusion-specularity, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for draw:custom-shape. Excel always writes out 80%.

- c. *The standard defines the attribute draw:extrusion-specularity, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for draw:custom-shape. PowerPoint always writes out 80%.

### **2.1.529 Part 3 Section 19.169, draw:extrusion-viewpoint**

- a. *The standard defines the attribute draw:extrusion-viewpoint, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for the <draw:custom-shape> element.

- b. *The standard defines the attribute draw:extrusion-viewpoint, contained within the element <draw:enhanced-geometry>*

Excel 2013 does not support this attribute for the <draw:custom-shape> element.

- c. *The standard defines the attribute draw:extrusion-viewpoint, contained within the element <draw:enhanced-geometry>*

PowerPoint 2013 does not support this attribute for the <draw:custom-shape> element.

### **2.1.530 Part 3 Section 19.170, draw:filter-name**

- a. *The standard defines the attribute draw:filter-name, contained within the element <draw:image>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:filter-name, contained within the element <draw:image>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:filter-name, contained within the element <draw:image>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.531 Part 3 Section 19.171, draw:formula**

- a. *The standard defines the attribute draw:formula, contained within the element <draw:equation>*

This attribute is supported in Word 2013 and later.

Word does not support the identifiers 'logwidth' and 'logheight'.

- b. *The standard defines the attribute draw:formula, contained within the element <draw:equation>*

This attribute is supported in Excel 2013 and later.

Excel does not support the identifiers 'logwidth' and 'logheight'.

- c. *The standard defines the attribute draw:formula, contained within the element <draw:equation>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint does not support the identifiers "logwidth" and "logheight".

### **2.1.532 Part 3 Section 19.175, draw:glue-points**

- a. *The standard defines the attribute draw:glue-points, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Word 2013 and later.

On load, Word rounds floats to integers.



- b. *The standard defines the attribute `draw:glue-points`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2013 and later.

On load, Excel rounds floats to integers.

- c. *The standard defines the attribute `draw:glue-points`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint rounds floats to integers.

### **2.1.533 Part 3 Section 19.176, `draw:handle-mirror-horizontal`**

- a. *The standard defines the attribute `draw:handle-mirror-horizontal`, contained within the element `<draw:handle>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:handle-mirror-horizontal`, contained within the element `<draw:handle>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:handle-mirror-horizontal`, contained within the element `<draw:handle>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.534 Part 3 Section 19.177, `draw:handle-mirror-vertical`**

- a. *The standard defines the attribute `draw:handle-mirror-vertical`, contained within the element `<draw:handle>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:handle-mirror-vertical`, contained within the element `<draw:handle>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:handle-mirror-vertical`, contained within the element `<draw:handle>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.535 Part 3 Section 19.179, `draw:handle-position`**

- a. *The standard defines the attribute `draw:handle-position`, contained within the element `<draw:handle>`*

This attribute is supported in Word 2013 and later.

Word does not support the identifiers 'logwidth' and 'logheight'.

- b. *The standard defines the attribute `draw:handle-position`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2013 and later.

Excel does not support the identifiers 'logwidth' and 'logheight'.

- c. *The standard defines the attribute `draw:handle-position`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint does not support the identifiers "logwidth" and "logheight".

### **2.1.536 Part 3 Section 19.182, `draw:handle-range-x-maximum`**

- a. *The standard defines the attribute `draw:handle-range-x-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in Word 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- b. *The standard defines the attribute `draw:handle-range-x-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- c. *The standard defines the attribute `draw:handle-range-x-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

### **2.1.537 Part 3 Section 19.183, `draw:handle-range-x-minimum`**

- a. *The standard defines the attribute `draw:handle-range-x-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Word 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- b. *The standard defines the attribute `draw:handle-range-x-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- c. *The standard defines the attribute `draw:handle-range-x-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

### **2.1.538 Part 3 Section 19.184, `draw:handle-range-y-maximum`**

- a. *The standard defines the attribute `draw:handle-range-y-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in Word 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- b. *The standard defines the attribute `draw:handle-range-y-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- c. *The standard defines the attribute `draw:handle-range-y-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

### **2.1.539 Part 3 Section 19.185, `draw:handle-range-y-minimum`**

- a. *The standard defines the attribute `draw:handle-range-y-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Word 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- b. *The standard defines the attribute `draw:handle-range-y-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- c. *The standard defines the attribute `draw:handle-range-y-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2013 and later.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

#### **2.1.540 Part 3 Section 19.186, draw:handle-switched**

- a. *The standard defines the attribute draw:handle-switched, contained within the element <draw:handle>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:handle-switched, contained within the element <draw:handle>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:handle-switched, contained within the element <draw:handle>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.541 Part 3 Section 19.187, draw:id**

- a. *The standard defines the attribute draw:id*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:id, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute draw:id*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- d. *The standard defines the attribute draw:id, contained within the element <office:annotation>*
- This attribute is not supported in Excel 2013 or later.
- e. *The standard defines the attribute draw:id*
- PowerPoint 2013 supports this attribute for the following elements:
- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- f. *The standard defines the attribute draw:id, contained within the element <draw:page>*
- This attribute is not supported in PowerPoint 2013 or later.

### **2.1.542 Part 3 Section 19.190, draw:line-skew**

- a. *The standard defines the attribute draw:line-skew, contained within the element <draw:connector>*
- This attribute is not supported in Word 2013 or later.
- Non-default connector elbow positions revert to default positioning after save from Word.
- b. *The standard defines the attribute draw:line-skew, contained within the element <draw:connector>*
- This attribute is not supported in Excel 2013 or later.
- Non-default connector elbow positions revert to default positioning after save from Excel.
- c. *The standard defines the attribute draw:line-skew, contained within the element <draw:connector>*
- This attribute is not supported in PowerPoint 2013 or later.
- Non-default connector elbow positions revert to default positioning after save from PowerPoint.

### **2.1.543 Part 3 Section 19.196, draw:modifiers**

- a. *The standard defines the attribute draw:modifiers, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:modifiers, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:modifiers, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.544 Part 3 Section 19.197, draw:name**

- a. *The standard defines the attribute draw:name*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:name, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute `draw:name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:line>
- <draw:connector>
- <draw:measure>

- e. *The standard defines the attribute `draw:name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute `draw:name`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

- g. *The standard defines the attribute `draw:name`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- h. *The standard defines the attribute draw:name, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- i. *The standard defines the attribute draw:name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- j. *The standard defines the attribute draw:name, contained within the element <draw:marker>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:line>
  - <draw:connector>
  - <draw:measure>
- k. *The standard defines the attribute draw:name, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>



- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

l. *The standard defines the attribute draw:name, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

m. *The standard defines the attribute draw:name*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

n. *The standard defines the attribute draw:name, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

o. *The standard defines the attribute draw:name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- p. *The standard defines the attribute `draw:name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:line>
  - <draw:connector>
  - <draw:measure>
- q. *The standard defines the attribute `draw:name`, contained within the element `<draw:object>`*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

This attribute is not supported in PowerPoint 2013 or later.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

- r. *The standard defines the attribute `draw:name`, contained within the element `<draw:object-ole>`*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

- s. *The standard defines the attribute `draw:name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2013 and later.

- t. *The standard defines the attribute `draw:name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>

- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

#### **2.1.545 Part 3 Section 19.198, draw:nav-order**

- a. *The standard defines the attribute draw:nav-order, contained within the element <draw:page>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.546 Part 3 Section 19.200, draw:notify-on-update-of-ranges**

- a. *The standard defines the attribute draw:notify-on-update-of-ranges, contained within the element <draw:object>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute draw:notify-on-update-of-ranges, contained within the element <draw:object>*

This attribute is not supported in PowerPoint 2013 or later.

- c. *The standard defines the attribute draw:notify-on-update-of-ranges, contained within the element <draw:object-ole>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.547 Part 3 Section 19.204, draw:path-stretchpoint-x**

- a. *The standard defines the attribute draw:path-stretchpoint-x, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Word 2013 and later.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- b. *The standard defines the attribute draw:path-stretchpoint-x, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Excel 2013 and later.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- c. *The standard defines the attribute draw:path-stretchpoint-x, contained within the element <draw:enhanced-geometry>*

This attribute is supported in PowerPoint 2013 and later.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

#### **2.1.548 Part 3 Section 19.205, draw:path-stretchpoint-y**

- a. *The standard defines the attribute draw:path-stretchpoint-y, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Word 2013 and later.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- b. *The standard defines the attribute `draw:path-stretchpoint-y`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2013 and later.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- c. *The standard defines the attribute `draw:path-stretchpoint-y`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2013 and later.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

### **2.1.549 Part 3 Section 19.214, `draw:start-color`**

- a. *The standard defines the attribute `draw:start-color`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
  - `<draw:polyline>`
  - `<draw:polygon>`
  - `<draw:regular-polygon>`
  - `<draw:path>`
  - `<draw:circle>`
  - `<draw:ellipse>`
  - `<draw:caption>`
  - `<draw:g>`
  - `<draw:image>`
  - `<draw:text-box>`
  - `<draw:custom-shape>`
- b. *The standard defines the attribute `draw:start-color`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:start-color`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

### **2.1.550 Part 3 Section 19.216, `draw:start-intensity`**

- a. *The standard defines the attribute `draw:start-intensity`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- b. *The standard defines the attribute `draw:start-intensity`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:start-intensity`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

### **2.1.551 Part 3 Section 19.218, draw:style**

- a. *The standard defines the property "axial", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the property "ellipsoid", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word interprets this enumeration as "radial".

- c. *The standard defines the property "linear", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the property "radial", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the property "rectangular", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word interprets this enumeration as "square".

- f. *The standard defines the property "square", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute `draw:style`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word interprets all styles as "rect".

- h. *The standard defines the property "axial", contained within the attribute `draw:style`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the property "ellipsoid", contained within the attribute `draw:style`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>



- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel interprets this enumeration as the value "radial".

- j. *The standard defines the property "linear", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the property "radial", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- l. *The standard defines the property "rectangular", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel interprets this enumeration as "square".

- m. *The standard defines the property "square", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- n. *The standard defines the attribute draw:style, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel interprets all styles as 'rect'.

- o. *The standard defines the property "axial", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- p. *The standard defines the property "ellipsoid", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint interprets this enumeration as "radial".

- q. *The standard defines the property "linear", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- r. *The standard defines the property "radial", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- s. *The standard defines the property "rectangular", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint interprets this enumeration as "square".

- t. *The standard defines the property "square", contained within the attribute draw:style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- u. *The standard defines the attribute draw:style, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>

- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint interprets all styles as "rect".

### **2.1.552 Part 3 Section 19.219, draw:style-name**

- a. *The standard defines the attribute draw:style-name*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:style-name, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute draw:style-name, contained within the element <style:master-page>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute draw:style-name*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- e. *The standard defines the attribute `draw:style-name`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2013 and later.

On load, Excel does not read in this attribute. On save, different BG colors and BG images on comments are not written to ODF.

- f. *The standard defines the attribute `draw:style-name`, contained within the element `<style:master-page>`, contained within the parent element `<office:master-styles>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `draw:style-name`*

PowerPoint 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:custom-shape>`

- h. *The standard defines the attribute `draw:style-name`, contained within the element `<style:handout-master>`*

This attribute is supported in PowerPoint 2013 and later.

Gradient backgrounds are not supported for handout masters.

### **2.1.553 Part 3 Section 19.220, `draw:text-areas`**

- a. *The standard defines the attribute `draw:text-areas`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2013 and later.

Only one text area per drawing shape is supported.

- b. *The standard defines the attribute `draw:text-areas`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2013 and later.

Only one text area per drawing shape is supported.

- c. *The standard defines the attribute `draw:text-areas`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2013 and later.

Only one text area per drawing shape is supported.

### **2.1.554 Part 3 Section 19.221, draw:text-path**

- a. *The standard defines the attribute draw:text-path, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute draw:text-path, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.555 Part 3 Section 19.222, draw:text-path-allowed**

- a. *The standard defines the attribute draw:text-path-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:text-path-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:text-path-allowed, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.556 Part 3 Section 19.223, draw:text-path-mode**

- a. *The standard defines the attribute draw:text-path-mode, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Word 2013 or later.

Word always sets the value of draw:text-path-mode to "shape".

- b. *The standard defines the attribute draw:text-path-mode, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:text-path-mode, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.557 Part 3 Section 19.224, draw:text-path-same-letter-heights**

- a. *The standard defines the attribute draw:text-path-same-letter-heights, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:text-path-same-letter-heights, contained within the element <draw:enhanced-geometry>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:text-path-same-letter-heights`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.558 Part 3 Section 19.225, `draw:text-path-scale`**

- a. *The standard defines the attribute `draw:text-path-scale`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2013 or later.

Word only uses shape text path scaling.

- b. *The standard defines the attribute `draw:text-path-scale`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:text-path-scale`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.559 Part 3 Section 19.226, `draw:text-rotate-angle`**

- a. *The standard defines the attribute `draw:text-rotate-angle`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:text-rotate-angle`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:text-rotate-angle`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.560 Part 3 Section 19.227, `draw:text-style-name`**

- a. *The standard defines the attribute `draw:text-style-name`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2013 or later.

On load, Excel does not read this attribute. On save, Excel does not write different text alignment to ODF.

#### **2.1.561 Part 3 Section 19.228, `draw:transform`**

- a. *The standard defines the property "`matrix(a b c d e f)`", contained within the attribute `draw:transform`*

Word 2013 does not support this enum for the following elements:

- `<draw:rect>`



- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- b. *The standard defines the property "rotate(rotate-angle)", contained within the attribute draw:transform*

Word 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

Rotation is not supported for a <draw:frame> element that contains a <draw:object-ole> element.

- c. *The standard defines the property "scale(sx [sy])", contained within the attribute draw:transform*

Word 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- d. *The standard defines the property "skewX(skew-angle)", contained within the attribute draw:transform*

Word 2013 does not support this enum for the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- e. *The standard defines the property "skewY(skew-angle)", contained within the attribute draw:transform*

Word 2013 does not support this enum for the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- f. *The standard defines the property "translate(tx [ty])", contained within the attribute draw:transform*

Word 2013 supports this enum for the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- g. *The standard defines the attribute draw:transform, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- h. *The standard defines the property "matrix(a b c d e f)", contained within the attribute draw:transform*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- i. *The standard defines the property "rotate(rotate-angle)", contained within the attribute draw:transform*

Excel 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

Rotation is not supported for a <draw:frame> element that contains a <draw:object-ole> element.

- j. *The standard defines the property "scale(sx [sy])", contained within the attribute draw:transform*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>

- <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- k. *The standard defines the property "skewX(skew-angle)", contained within the attribute draw:transform*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- l. *The standard defines the property "skewY(skew-angle)", contained within the attribute draw:transform*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- m. *The standard defines the property "translate(tx [ty])", contained within the attribute draw:transform*

Excel 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>

- <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- n. *The standard defines the attribute `draw:transform`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the property "`matrix(a b c d e f)`", contained within the attribute `draw:transform`*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- p. *The standard defines the property "`rotate(rotate-angle)`", contained within the attribute `draw:transform`*

PowerPoint 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

Rotation is not supported for a <draw:frame> element that contains a <draw:object-ole> element.

- q. *The standard defines the property "`scale(sx [sy])`", contained within the attribute `draw:transform`*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

r. *The standard defines the property "skewX(skew-angle)", contained within the attribute draw:transform*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

s. *The standard defines the property "skewY(skew-angle)", contained within the attribute draw:transform*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

t. *The standard defines the property "translate(tx [ty])", contained within the attribute draw:transform*

PowerPoint 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

### **2.1.562 Part 3 Section 19.229, draw:type**

- a. *The standard defines the attribute draw:type, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Word 2013 and later.

The enumeration "non-primitive" is supported. Any other value for the draw:type attribute is ignored.

- b. *The standard defines the attribute draw:type, contained within the element <draw:enhanced-geometry>*

This attribute is supported in Excel 2013 and later.

The enumeration "non-primitive" is supported. Any other value for the draw:type attribute is ignored.

- c. *The standard defines the attribute draw:type, contained within the element <draw:enhanced-geometry>*

This attribute is supported in PowerPoint 2013 and later.

The enumeration "non-primitive" is supported. Any other value for the draw:type attribute is ignored.

### **2.1.563 Part 3 Section 19.231, draw:z-index**

- a. *The standard defines the attribute draw:z-index*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

The draw:z-index values increase from back to front regardless of the style:run-through attribute setting.

- b. *The standard defines the attribute draw:z-index, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute draw:z-index*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- d. *The standard defines the attribute draw:z-index, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute draw:z-index*

This attribute is not supported in PowerPoint 2013 or later.

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

## **2.1.564 Part 3 Section 19.232, fo:column-count**

- a. *The standard defines the attribute fo:column-count, contained within the element <style:columns>*

This attribute is not supported in Excel 2013 or later.



## 2.1.565 Part 3 Section 19.233, fo:column-gap

- a. *The standard defines the attribute fo:column-gap, contained within the element <style:columns>*  
This attribute is not supported in Excel 2013 or later.

## 2.1.566 Part 3 Section 19.234, fo:country

- a. *The standard defines the attribute fo:country, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load, Word preserves the fo:country attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:country", "style:country-asian" and "style:country-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:language", "fo:language-asian", and "fo:language-complex" attributes.

- b. *The standard defines the attribute fo:country, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:country, style:country-asian, and style:country-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:language, fo:language-asian, and fo:language-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the Excel lang property.

- c. *The standard defines the attribute fo:country, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the PowerPoint lang property.

### **2.1.567 Part 3 Section 19.235, fo:end-indent**

- a. *The standard defines the attribute fo:end-indent, contained within the element <style:column>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2013 or later.

### **2.1.568 Part 3 Section 19.236, fo:language**

- a. *The standard defines the attribute fo:language, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load, Word preserves the fo:language attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

If the language is missing, Word ignores both the language and the country.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:language", "fo:language-asian" and "fo:language-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:country", "style:country-asian", and "style:country-complex".

- b. *The standard defines the attribute fo:language, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute fo:language, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, or fo:language-complex attributes is used to populate the PowerPoint lang attribute. PowerPoint's altLang attribute is not populated on read.

### **2.1.569 Part 3 Section 19.237, fo:margin-left**

- a. *The standard defines the attribute fo:margin-left, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:margin-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:margin-left, contained within the element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:margin-left, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute fo:margin-left, contained within the element <style:paragraph-properties>*

This attribute is supported in Excel 2013 and later.

Excel maps this attribute to the indent value for text alignment.

On load, Excel only applies this attribute to the indent value for text alignment if the fo:text-align attribute is not specified, or either fo:margin-left has a value of "left" or fo:margin-right has a value of "right".

On save, Excel does not write this attribute if the alignment of the text is set to center or justified.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage values are not supported.

- g. *The standard defines the attribute fo:margin-left, contained within the element <style:section-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- h. *The standard defines the attribute fo:margin-left, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:margin-left, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute fo:margin-left, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- k. *The standard defines the attribute fo:margin-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage values are not supported.

- l. *The standard defines the attribute fo:margin-left, contained within the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## **2.1.570 Part 3 Section 19.238, fo:max-height**

- a. *The standard defines the attribute fo:max-height, contained within the element <draw:text-box>*

This attribute is supported in Word 2013 and later.

Word supports length but not percent for this attribute.

Word supports the fo:max-height attribute when the value is less than the value of the svg:height attribute on the text box's <draw:frame> parent element. For this case, Word uses the value specified in the fo:max-height attribute as the text box's height instead of the svg:height attribute and writes this value to the svg:height attribute on save.

- b. *The standard defines the attribute fo:max-height, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- c. *The standard defines the attribute fo:max-height, contained within the element <draw:text-box>*

This attribute is supported in Excel 2013 and later.

Excel supports length but not percent for this attribute.

Excel supports the fo:max-height attribute when the value is less than the value for the svg:height attribute on the text box's <draw:frame> parent element. For this case, Excel uses the value specified in the fo:max-height attribute as the text box's height instead of the svg:height attribute and writes this value to the svg:height attribute on save.

- d. *The standard defines the attribute fo:max-height, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- e. *The standard defines the attribute fo:max-height, contained within the element <draw:text-box>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint supports length but not percent for this attribute.

PowerPoint supports the fo:max-height attribute when the value is less than the value for the svg:height attribute on the text box's <draw:frame> parent element. For this case, PowerPoint uses the value specified in the fo:max-height attribute as the text box's height instead of the svg:height attribute and writes this value to the svg:height attribute on save.

- f. *The standard defines the attribute fo:max-height, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

### **2.1.571 Part 3 Section 19.239, fo:max-width**

- a. *The standard defines the attribute fo:max-width, contained within the element <draw:text-box>*

This attribute is supported in Word 2013 and later.

Word supports length but not percent for this attribute.

Word supports the fo:max-width attribute when the value is less than the value of the svg:width attribute on the text box's <draw:frame> parent element. For this case, Word uses the value specified in the fo:max-width attribute as the text box's width instead of the svg:width attribute, and Word writes this value to the svg:width attribute on save.

- b. *The standard defines the attribute fo:max-width, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- c. *The standard defines the attribute fo:max-width, contained within the element <draw:text-box>*

This attribute is supported in Excel 2013 and later.

Excel supports length, but not percent for this attribute.

Excel supports the fo:max-width attribute when the value is less than the value for the svg:width attribute on the text box's <draw:frame> parent element. For this case, Excel uses the value specified in the fo:max-width attribute as the text box's width instead of the svg:width attribute and writes this value to the svg:width attribute on save.

- d. *The standard defines the attribute fo:max-width, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- e. *The standard defines the attribute fo:max-width, contained within the element <draw:text-box>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint supports length but not percent for this attribute.

PowerPoint supports the `fo:max-width` attribute when the value is less than the value for the `svg:width` attribute on the text box's `<draw:frame>` parent element. For this case, PowerPoint uses the value specified in the `fo:max-width` attribute as the text box's width instead of the `svg:width` attribute and writes this value to the `svg:width` attribute on save.

- f. *The standard defines the attribute `fo:max-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

## **2.1.572 Part 3 Section 19.240, `fo:min-height`**

- a. *The standard defines the attribute `fo:min-height`, contained within the element `<draw:text-box>`*

This attribute is supported in Word 2013 and later.

Word supports length but not percent for this attribute.

This attribute is used when the `svg:height` attribute on the text box's `<draw:frame>` parent element is missing. Otherwise, this attribute is ignored.

- b. *The standard defines the attribute `fo:min-height`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- c. *The standard defines the attribute `fo:min-height`, contained within the element `<draw:text-box>`*

This attribute is supported in Excel 2013 and later.

Excel supports length but not percent for this attribute.

Excel uses the `fo:min-height` attribute when the `svg:height` attribute on the text box's `<draw:frame>` parent element is missing. Otherwise, Excel ignores this attribute.

- d. *The standard defines the attribute `fo:min-height`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- e. *The standard defines the attribute `fo:min-height`, contained within the element `<draw:text-box>`*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint supports length but not percent for this attribute.

PowerPoint uses the `fo:min-height` attribute when the `svg:height` attribute on the text box's `<draw:frame>` parent element is missing. Otherwise, PowerPoint ignores this attribute.

- f. *The standard defines the attribute `fo:min-height`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.



### **2.1.573 Part 3 Section 19.241, fo:min-width**

- a. *The standard defines the attribute fo:min-width, contained within the element <draw:text-box>*

This attribute is supported in Word 2013 and later.

Word supports length but not percent for this attribute.

Word uses the fo:min-width attribute when the svg:width attribute on the text box's <draw:frame> parent element is missing. Otherwise, Word ignores this attribute.

- b. *The standard defines the attribute fo:min-width, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- c. *The standard defines the attribute fo:min-width, contained within the element <draw:text-box>*

This attribute is supported in Excel 2013 and later.

Excel supports length, but not percent for this attribute.

Excel uses the fo:min-width attribute when the svg:width attribute on the text box's <draw:frame> parent element is missing. Otherwise, Excel ignores this attribute.

- d. *The standard defines the attribute fo:min-width, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- e. *The standard defines the attribute fo:min-width, contained within the element <draw:text-box>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint supports length, but not percent for this attribute.

PowerPoint uses the fo:min-width attribute when the svg:width attribute on the text box's <draw:frame> parent element is missing. Otherwise, PowerPoint ignores this attribute.

- f. *The standard defines the attribute fo:min-width, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

### **2.1.574 Part 3 Section 19.242.2, text:alphabetical-index-source**

- a. *The standard defines the attribute fo:script, contained within the element <text:alphabetical-index-source>*

This attribute is supported in Word 2013 and later.

### **2.1.575 Part 3 Section 19.243, fo:space-after**

- a. *The standard defines the attribute fo:space-after, contained within the element <style:column>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `fo:space-after`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.576 Part 3 Section 19.244, `fo:space-before`**

- a. *The standard defines the attribute `fo:space-before`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `fo:space-before`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.577 Part 3 Section 19.245, `fo:start-indent`**

- a. *The standard defines the attribute `fo:start-indent`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.578 Part 3 Section 19.246, `fo:text-indent`**

- a. *The standard defines the attribute `fo:text-indent`, contained within the element `<style:paragraph-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:text-indent`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage values are not supported.

- c. *The standard defines the attribute `fo:text-indent`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage values are not supported.

### **2.1.579 Part 3 Section 19.247, form:allow-deletes**

- a. *The standard defines the attribute form:allow-deletes, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:allow-deletes, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.580 Part 3 Section 19.248, form:allow-inserts**

- a. *The standard defines the attribute form:allow-inserts, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:allow-inserts, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.581 Part 3 Section 19.249, form:allow-updates**

- a. *The standard defines the attribute form:allow-updates, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:allow-updates, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.582 Part 3 Section 19.251, form:apply-filter**

- a. *The standard defines the attribute form:apply-filter, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:apply-filter, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

**2.1.583 Part 3 Section 19.254, form:bound-column**

- a. *The standard defines the attribute form:bound-column*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:bound-column*  
This attribute is not supported in Excel 2013 or later.

**2.1.584 Part 3 Section 19.255, form:button-type**

- a. *The standard defines the attribute form:button-type*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:button-type*  
This attribute is not supported in Excel 2013 or later.

**2.1.585 Part 3 Section 19.256, form:command**

- a. *The standard defines the attribute form:command, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:command, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

**2.1.586 Part 3 Section 19.257, form:command-type**

- a. *The standard defines the attribute form:command-type, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:command-type, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

**2.1.587 Part 3 Section 19.258, form:control-implementation**

- a. *The standard defines the attribute form:control-implementation*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:control-implementation*  
This attribute is not supported in Excel 2013 or later.

**2.1.588 Part 3 Section 19.259, form:convert-empty-to-null**

- a. *The standard defines the attribute form:convert-empty-to-null*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:convert-empty-to-null*

This attribute is not supported in Excel 2013 or later.

**2.1.589 Part 3 Section 19.260, form:current-selected**

- a. *The standard defines the attribute form:current-selected*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:current-selected*

This attribute is not supported in Excel 2013 or later.

**2.1.590 Part 3 Section 19.262, form:current-value**

- a. *The standard defines the attribute form:current-value*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:current-value*

This attribute is not supported in Excel 2013 or later.

**2.1.591 Part 3 Section 19.263, form:data-field**

- a. *The standard defines the attribute form:data-field*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:data-field*

This attribute is not supported in Excel 2013 or later.

**2.1.592 Part 3 Section 19.264, form:datasource**

- a. *The standard defines the attribute form:datasource, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:datasource, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

**2.1.593 Part 3 Section 19.267, form:detail-fields**

- a. *The standard defines the attribute form:detail-fields, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:detail-fields, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

**2.1.594 Part 3 Section 19.268, form:disabled**

- a. *The standard defines the attribute form:disabled*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:disabled*

This attribute is not supported in Excel 2013 or later.

#### **2.1.595 Part 3 Section 19.269, form:dropdown**

- a. *The standard defines the attribute form:dropdown*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:dropdown*

This attribute is not supported in Excel 2013 or later.

#### **2.1.596 Part 3 Section 19.271, form:enctype**

- a. *The standard defines the attribute form:enctype, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:enctype, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.597 Part 3 Section 19.272, form:escape-processing**

- a. *The standard defines the attribute form:escape-processing, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

#### **2.1.598 Part 3 Section 19.273, form:filter**

- a. *The standard defines the attribute form:filter, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:filter, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.599 Part 3 Section 19.275, form:for**

- a. *The standard defines the attribute form:for*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:for*

This attribute is not supported in Excel 2013 or later.

#### **2.1.600 Part 3 Section 19.276, form:id**

- a. *The standard defines the attribute form:id*

This attribute is not supported in Word 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

- b. *The standard defines the attribute form:id*

This attribute is not supported in Excel 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

#### **2.1.601 Part 3 Section 19.277, form:ignore-result**

- a. *The standard defines the attribute form:ignore-result, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:ignore-result, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.602 Part 3 Section 19.278, form:image-align**

- a. *The standard defines the attribute form:image-align*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:image-align*

This attribute is not supported in Excel 2013 or later.

#### **2.1.603 Part 3 Section 19.279, form:image-data**

- a. *The standard defines the attribute form:image-data*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:image-data*

This attribute is not supported in Excel 2013 or later.

#### **2.1.604 Part 3 Section 19.280, form:image-position**

- a. *The standard defines the attribute form:image-position*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:image-position*

This attribute is not supported in Excel 2013 or later.

#### **2.1.605 Part 3 Section 19.282, form:label**

- a. *The standard defines the attribute form:label*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:label*

This attribute is not supported in Excel 2013 or later.

### **2.1.606 Part 3 Section 19.285, form:list-source**

- a. *The standard defines the attribute form:list-source*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:list-source*  
This attribute is not supported in Excel 2013 or later.

### **2.1.607 Part 3 Section 19.286, form:list-source-type**

- a. *The standard defines the attribute form:list-source-type*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:list-source-type*  
This attribute is not supported in Excel 2013 or later.

### **2.1.608 Part 3 Section 19.287, form:master-fields**

- a. *The standard defines the attribute form:master-fields, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:master-fields, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.609 Part 3 Section 19.288, form:max-length**

- a. *The standard defines the attribute form:max-length*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:max-length*  
This attribute is not supported in Excel 2013 or later.

### **2.1.610 Part 3 Section 19.291, form:method**

- a. *The standard defines the attribute form:method, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:method, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.611 Part 3 Section 19.294, form:name**

- a. *The standard defines the attribute form:name*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:name*  
This attribute is not supported in Excel 2013 or later.



### **2.1.612 Part 3 Section 19.295, form:navigation-mode**

- a. *The standard defines the attribute form:navigation-mode, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:navigation-mode, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

### **2.1.613 Part 3 Section 19.296, form:order**

- a. *The standard defines the attribute form:order, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:order, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

### **2.1.614 Part 3 Section 19.299, form:printable**

- a. *The standard defines the attribute form:printable*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:printable*

This attribute is not supported in Excel 2013 or later.

### **2.1.615 Part 3 Section 19.300, form:property-name**

- a. *The standard defines the attribute form:property-name, contained within the element <form:property>*

This attribute is not supported in Word 2013 or later.

### **2.1.616 Part 3 Section 19.301, form:readonly**

- a. *The standard defines the attribute form:readonly*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:readonly*

This attribute is not supported in Excel 2013 or later.

### **2.1.617 Part 3 Section 19.303, form:selected**

- a. *The standard defines the attribute form:selected*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:selected*

This attribute is not supported in Excel 2013 or later.

### **2.1.618 Part 3 Section 19.304, form:size**

- a. *The standard defines the attribute form:size*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:size*  
This attribute is not supported in Excel 2013 or later.

### **2.1.619 Part 3 Section 19.309, form:tab-cycle**

- a. *The standard defines the attribute form:tab-cycle, contained within the element <form:form>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:tab-cycle, contained within the element <form:form>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.620 Part 3 Section 19.310, form:tab-index**

- a. *The standard defines the attribute form:tab-index*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:tab-index*  
This attribute is not supported in Excel 2013 or later.

### **2.1.621 Part 3 Section 19.311, form:tab-stop**

- a. *The standard defines the attribute form:tab-stop*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:tab-stop*  
This attribute is not supported in Excel 2013 or later.

### **2.1.622 Part 3 Section 19.313, form:title**

- a. *The standard defines the attribute form:title*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:title*  
This attribute is not supported in Excel 2013 or later.

### **2.1.623 Part 3 Section 19.316, form:value**

- a. *The standard defines the attribute form:value*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute form:value*  
This attribute is not supported in Excel 2013 or later.

### **2.1.624 Part 3 Section 19.317, form:visual-effect**

- a. *The standard defines the attribute form:visual-effect*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute form:visual-effect*

This attribute is not supported in Excel 2013 or later.

### **2.1.625 Part 3 Section 19.326, meta:frame-count**

- a. *The standard defines the attribute meta:frame-count, contained within the element <meta:document-statistic>*

This attribute is supported in Word 2013 and later.

### **2.1.626 Part 3 Section 19.327, meta:image-count**

- a. *The standard defines the attribute meta:image-count, contained within the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This attribute is not supported in Word 2013 or later.

### **2.1.627 Part 3 Section 19.330, meta:object-count**

- a. *The standard defines the attribute meta:object-count, contained within the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This attribute is not supported in Word 2013 or later.

### **2.1.628 Part 3 Section 19.332, meta:page-count**

- a. *The standard defines the attribute meta:page-count, contained within the element <meta:document-statistic>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.629 Part 3 Section 19.335, meta:sentence-count**

- a. *The standard defines the attribute meta:sentence-count, contained within the element <meta:document-statistic>*

This attribute is supported in Word 2013 and later.

### **2.1.630 Part 3 Section 19.336, meta:syllable-count**

- a. *The standard defines the attribute meta:syllable-count, contained within the element <meta:document-statistic>*

This attribute is supported in Word 2013 and later.

### **2.1.631 Part 3 Section 19.340, number:automatic-order**

- a. *The standard defines the attribute number:automatic-order*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `number:automatic-order`, contained within the element `<number:date-style>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `number:automatic-order`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `number:automatic-order`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.632 Part 3 Section 19.341, `number:calendar`**

- a. *The standard defines the property `"hanja"`, contained within the attribute `number:calendar`*

This property is not supported in Word 2013 or later.

- b. *The standard defines the property `"hanja_yoil"`, contained within the attribute `number:calendar`*

This property is not supported in Word 2013 or later.

- c. *The standard defines the property `"ROC"`, contained within the attribute `number:calendar`*

This property is not supported in Word 2013 or later.

- d. *The standard defines the property `"hanja"`, contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2013 or later.

- e. *The standard defines the property `"hanja_yoil"`, contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2013 or later.

- f. *The standard defines the property `"ROC"`, contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2013 or later.

- g. *The standard defines the property `"hanja"`, contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2013 or later.

- h. *The standard defines the property `"hanja_yoil"`, contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2013 or later.

- i. *The standard defines the property `"ROC"`, contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2013 or later.

- j. *The standard defines the property "hanja", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- k. *The standard defines the property "hanja\_yoil", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- l. *The standard defines the property "ROC", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- m. *The standard defines the property "hanja", contained within the attribute number:calendar, contained within the element <number:month>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- n. *The standard defines the property "hanja\_yoil", contained within the attribute number:calendar, contained within the element <number:month>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- o. *The standard defines the property "ROC", contained within the attribute number:calendar, contained within the element <number:month>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- p. *The standard defines the property "hanja", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- q. *The standard defines the property "hanja\_yoil", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- r. *The standard defines the property "ROC", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is not supported in Word 2013 or later.

- s. *The standard defines the property "buddhist", contained within the attribute number:calendar*

This property is supported in Excel 2013 and later.

This value corresponds to CAL\_THAI in Excel.

- t. *The standard defines the property "gengou", contained within the attribute number:calendar*  
This property is supported in Excel 2013 and later.  
This value corresponds to CAL\_JAPAN in Excel.
- u. *The standard defines the property "hanja", contained within the attribute number:calendar*  
This property is supported in Excel 2013 and later.  
This value corresponds to CAL\_KOREA in Excel.
- v. *The standard defines the property "hanja\_yoil", contained within the attribute number:calendar*  
This property is not supported in Excel 2013 or later.
- w. *The standard defines the property "jewish", contained within the attribute number:calendar*  
This property is supported in Excel 2013 and later.  
This value corresponds to CAL\_HEBREW in Excel.
- x. *The standard defines the property "ROC", contained within the attribute number:calendar*  
This property is not supported in Excel 2013 or later.
- y. *The standard defines the property "hanja\_yoil", contained within the attribute number:calendar*  
This property is not supported in PowerPoint 2013 or later.
- z. *The standard defines the property "ROC", contained within the attribute number:calendar*  
This property is not supported in PowerPoint 2013 or later.

### **2.1.633 Part 3 Section 19.342, number:country**

- a. *The standard defines the attribute number:country, contained within the element <number:time-style>*  
This attribute is supported in Word 2013 and later.  
On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.  
On save, Word does not write out time fields or time styles.
- b. *The standard defines the attribute number:country*  
This attribute is not supported in PowerPoint 2013 or later.

### **2.1.634 Part 3 Section 19.343, number:decimal-places**

- a. *The standard defines the attribute number:decimal-places*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute number:decimal-places, contained within the element <number:seconds>, contained within the parent element <number:date-style>*  
This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `number:decimal-places`, contained within the element `<number:seconds>`, contained within the parent element `<number:time-style>`*

This attribute is not supported in Word 2013 or later.

On load, Word reads the `<number:time-style>` element and converts it to the matching `<text:date-style>` element.

On save, Word does not write out time fields or time styles.

- d. *The standard defines the attribute `number:decimal-places`, contained within the element `<number:seconds>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.635 Part 3 Section 19.344, `number:decimal-replacement`**

- a. *The standard defines the attribute `number:decimal-replacement`, contained within the element `<number:number>`, contained within the parent element `<number:number-style>`*

This attribute is supported in Excel 2013 and later.

If this attribute contains the empty string, Excel treats the values after the decimal as numeric instead of zero. On save, the attribute or empty string is saved only if all digits to the right of the decimal are insignificant digits.

### **2.1.636 Part 3 Section 19.348, `number:format-source`**

- a. *The standard defines the attribute `number:format-source`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `number:format-source`, contained within the element `<number:date-style>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `number:format-source`, contained within the element `<number:time-style>`*

This attribute is not supported in Word 2013 or later.

On load, Word reads the `<number:time-style>` element and converts it to the matching `<text:date-style>` element.

On save, Word does not write out time fields or time styles.

- d. *The standard defines the property `"fixed"`, contained within the attribute `number:format-source`*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the property `"language"`, contained within the attribute `number:format-source`*

This property is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `number:format-source`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.637 Part 3 Section 19.350, number:grouping**

- a. *The standard defines the attribute number:grouping*

This attribute is not supported in Word 2013 or later.

### **2.1.638 Part 3 Section 19.351, number:language**

- a. *The standard defines the attribute number:language, contained within the element <number:time-style>*

This attribute is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- b. *The standard defines the attribute number:language*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.639 Part 3 Section 19.355, number:min-integer-digits**

- a. *The standard defines the attribute number:min-integer-digits*

This attribute is not supported in Word 2013 or later.

### **2.1.640 Part 3 Section 19.359, number:possessive-form**

- a. *The standard defines the attribute number:possessive-form, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute number:possessive-form, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute number:possessive-form, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.641 Part 3 Section 19.361, number:script**

- a. *The standard defines the attribute number:script, contained within the element <number:date-style>*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the attribute number:script, contained within the element <number:time-style>*

This attribute is supported in Word 2013 and later.



## 2.1.642 Part 3 Section 19.362, number:style

- a. *The standard defines the attribute number:style, contained within the element <number:day>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute number:style, contained within the element <number:day-of-week>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute number:style, contained within the element <number:era>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute number:style, contained within the element <number:hours>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute number:style, contained within the element <number:hours>, contained within the parent element <number:time-style>*

This attribute is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- f. *The standard defines the attribute number:style, contained within the element <number:minutes>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- g. *The standard defines the attribute number:style, contained within the element <number:minutes>, contained within the parent element <number:time-style>*

This attribute is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- h. *The standard defines the attribute number:style, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- i. *The standard defines the attribute number:style, contained within the element <number:seconds>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- j. *The standard defines the attribute number:style, contained within the element <number:seconds>, contained within the parent element <number:time-style>*

This attribute is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- k. *The standard defines the attribute number:style, contained within the element <number:year>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- l. *The standard defines the attribute number:style, contained within the element <number:quarter>, contained within the parent element <number:date-style>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:quarter>, contained within the parent element <number:date-style>*

This property is not supported in Excel 2013 or later.

- n. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:quarter>, contained within the parent element <number:date-style>*

This property is not supported in Excel 2013 or later.

- o. *The standard defines the attribute number:style, contained within the element <number:quarter>, contained within the parent element <number:date-style>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.643 Part 3 Section 19.364, number:title**

- a. *The standard defines the attribute number:title*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute number:title, contained within the element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute number:title, contained within the element <number:time-style>*

This attribute is not supported in Word 2013 or later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- d. *The standard defines the attribute number:title*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute number:title*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.644 Part 3 Section 19.365, number:transliteration-country**

- a. *The standard defines the attribute number:transliteration-country*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute number:transliteration-country, contained within the element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute number:transliteration-country, contained within the element <number:time-style>*

This attribute is not supported in Word 2013 or later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- d. *The standard defines the attribute number:transliteration-country*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.645 Part 3 Section 19.366, number:transliteration-format**

- a. *The standard defines the attribute number:transliteration-format, contained within the element <number:time-style>*

This attribute is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

#### **2.1.646 Part 3 Section 19.367, number:transliteration-language**

- a. *The standard defines the attribute number:transliteration-language*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute number:transliteration-language, contained within the element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute number:transliteration-language, contained within the element <number:time-style>*

This attribute is not supported in Word 2013 or later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- d. *The standard defines the attribute number:transliteration-language*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.647 Part 3 Section 19.368, number:transliteration-style**

- a. *The standard defines the attribute number:transliteration-style, contained within the element <number:time-style>*

This attribute is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- b. *The standard defines the property "long", contained within the attribute number:transliteration-style*

This property is supported in Excel 2013 and later.

On load, Excel ignores this attribute. On save, Excel outputs this attribute in case of general format.

- c. *The standard defines the property "medium", contained within the attribute number:transliteration-style*

This property is not supported in Excel 2013 or later.

### **2.1.648 Part 3 Section 19.369, number:truncate-on-overflow**

- a. *The standard defines the attribute number:truncate-on-overflow, contained within the element <number:time-style>*

This attribute is supported in Word 2013 and later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- b. *The standard defines the attribute number:truncate-on-overflow*

This attribute is supported in Excel 2013 and later.

If the attribute is true or not present, then the <number:hours>, <number:minutes>, or <number:seconds> child elements of the <number:time-style> element is truncated, which means hours do not exceed 24 and minutes and seconds do not exceed 60.

- c. *The standard defines the attribute number:truncate-on-overflow, contained within the element <number:time-style>, contained within the parent element <number:date-style>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.649 Part 3 Section 19.371, office:boolean-value**

- a. *The standard defines the attribute office:boolean-value, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute office:boolean-value, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `office:boolean-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.650 Part 3 Section 19.372, `office:conversion-mode`**

- a. *The standard defines the attribute `office:conversion-mode`, contained within the element `<office:dde-source>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.651 Part 3 Section 19.373, `office:currency`**

- a. *The standard defines the attribute `office:currency`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `office:currency`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `office:currency`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `office:currency`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `office:currency`, contained within the element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `office:currency`, contained within the element `<table:table-cell>`*

#### **2.1.652 Part 3 Section 19.374, `office:date-value`**

- a. *The standard defines the attribute `office:date-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `office:date-value`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `office:date-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

### 2.1.653 Part 3 Section 19.379, office:mimetype

- a. *The standard defines the attribute office:mimetype, contained within the element <office:document-content>*

This attribute is not supported in PowerPoint 2013 or later.

- b. *The standard defines the attribute office:mimetype, contained within the element <office:document-meta>*

This attribute is not supported in PowerPoint 2013 or later.

- c. *The standard defines the attribute office:mimetype, contained within the element <office:document-settings>*

This attribute is not supported in PowerPoint 2013 or later.

- d. *The standard defines the attribute office:mimetype, contained within the element <office:document-styles>*

This attribute is not supported in PowerPoint 2013 or later.

### 2.1.654 Part 3 Section 19.380, office:name

- a. *The standard defines the attribute office:name, contained within the element <text:a>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute office:name, contained within the element <office:dde-source>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute office:name, contained within the element <text:a>*

This attribute is not supported in Excel 2013 or later.

**OfficeArt Math** in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- d. *The standard defines the attribute office:name, contained within the element <text:a>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.655 Part 3 Section 19.383, office:string-value**

- a. *The standard defines the attribute office:string-value, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute office:string-value, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute office:string-value, contained within the element <table:covered-table-cell>*

This attribute is not supported in Excel 2013 or later.

### **2.1.656 Part 3 Section 19.384, office:target-frame**

- a. *The standard defines the attribute office:target-frame*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute office:target-frame, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute office:target-frame*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute office:target-frame, contained within the element <form:form>*

This attribute is not supported in Excel 2013 or later.

### **2.1.657 Part 3 Section 19.385, office:target-frame-name**

- a. *The standard defines the attribute office:target-frame-name, contained within the element <text:a>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute office:target-frame-name, contained within the element <text:a>*

**OfficeArt Math** in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

PowerPoint uses a string value for this property. On write, if the PowerPoint string value matches one of the enumerations ("\_self", "\_blank", "\_parent", or "\_top"), then that enumeration is used. Otherwise, the string value is written to the ODF property.

On read, all values for this property are written as string values to PowerPoint.

### **2.1.658 Part 3 Section 19.386, office:time-value**

- a. *The standard defines the attribute office:time-value, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute office:time-value, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute office:time-value, contained within the element <table:covered-table-cell>*

This attribute is not supported in Excel 2013 or later.

### **2.1.659 Part 3 Section 19.387, office:title**

- a. *The standard defines the attribute office:title, contained within the element <text:a>*

This attribute is not supported in Excel 2013 or later.

**OfficeArt Math** in Excel 2013 does not support this attribute, on load, for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.



- b. *The standard defines the attribute `office:title`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

### **2.1.660 Part 3 Section 19.388, `office:value`**

- a. *The standard defines the attribute `office:value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `office:value`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `office:value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `office:value`, contained within the element `<table:table-cell>`*

### **2.1.661 Part 3 Section 19.389, `office:value-type`**

- a. *The standard defines the attribute `office:value-type`, contained within the element `<form:property>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `office:value-type`, contained within the element `<form:property>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `office:value-type`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `office:value-type`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.662 Part 3 Section 19.391, presentation:action**

- a. *The standard defines the property "fade-out", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is not supported in PowerPoint 2013 or later.

- b. *The standard defines the property "hide", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is not supported in PowerPoint 2013 or later.

- c. *The standard defines the property "show", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2013 and later.

PowerPoint does not support links to slides in other presentations.

- d. *The standard defines the property "sound", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is not supported in PowerPoint 2013 or later.

- e. *The standard defines the property "verb", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2013 and later.

If this property is used but no presentation:verb attribute is present, PowerPoint replaces the slide with a blank slide.

### **2.1.663 Part 3 Section 19.393, presentation:class**

- a. *The standard defines the attribute presentation:class*

This attribute is supported in PowerPoint 2013 and later.

If an object placeholder exists on a slide, but PowerPoint finds no matching placeholder for that type of object in the layout, PowerPoint writes the placeholder out as a general object placeholder.

### **2.1.664 Part 3 Section 19.394, presentation:class-names**

- a. *The standard defines the attribute presentation:class-names*

This attribute is not supported in PowerPoint 2013 or later.

PowerPoint does not support or preserve this element.

### **2.1.665 Part 3 Section 19.396, presentation:direction**

- a. *The standard defines the attribute presentation:direction, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.666 Part 3 Section 19.398, presentation:effect**

- a. *The standard defines the attribute presentation:effect, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.667 Part 3 Section 19.400, presentation:full-screen**

- a. *The standard defines the attribute presentation:full-screen, contained within the element <presentation:settings>*

This attribute is supported in PowerPoint 2013 and later.

When this attribute value is False and the transition-on-click value is True, the presentation displays in a window. When this attribute value is True, the presentation shows in full slideshow or kiosk mode.

### **2.1.668 Part 3 Section 19.402, presentation:master-element**

- a. *The standard defines the attribute presentation:master-element*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.669 Part 3 Section 19.403, presentation:mouse-as-pen**

- a. *The standard defines the attribute presentation:mouse-as-pen, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.670 Part 3 Section 19.404, presentation:mouse-visible**

- a. *The standard defines the attribute presentation:mouse-visible, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.671 Part 3 Section 19.410, presentation:pause**

- a. *The standard defines the attribute presentation:pause, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.672 Part 3 Section 19.413, presentation:presentation-page-layout-name**

- a. *The standard defines the attribute presentation:presentation-page-layout-name, contained within the element <draw:page>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint does not read this attribute when loading a slide.

- b. *The standard defines the attribute presentation:presentation-page-layout-name, contained within the element <style:handout-master>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.673 Part 3 Section 19.418, presentation:show-end-of-presentation-slide**

- a. *The standard defines the attribute presentation:show-end-of-presentation-slide, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.674 Part 3 Section 19.419, presentation:show-logo**

- a. *The standard defines the attribute presentation:show-logo, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.675 Part 3 Section 19.420, presentation:source**

- a. *The standard defines the attribute presentation:source, contained within the element <presentation:date-time-decl>*

If the value of this attribute is "current-date", then PowerPoint attempts to map the date style and/or time style in the presentation to one of its preset date formats and/or time formats. If an exact match is not found, PowerPoint ignores the "number:transliteration-style" and "number:transliteration-format" attributes of the "number:date-style" and the "number:time-style" elements, and tries again to find an exact match.

If a match is not found by the above algorithm, PowerPoint assumes the locale-specific "datetime1" format for date styles and date-and-time styles, and the locale-specific "datetime10" format for time styles.

#### **2.1.676 Part 3 Section 19.421, presentation:speed**

- a. *The standard defines the attribute presentation:speed, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.677 Part 3 Section 19.422, presentation:start-scale**

- a. *The standard defines the attribute presentation:start-scale, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.678 Part 3 Section 19.424, presentation:start-with-navigator**

- a. *The standard defines the attribute presentation:start-with-navigator, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.679 Part 3 Section 19.425, presentation:stay-on-top**

- a. *The standard defines the attribute presentation:stay-on-top, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.680 Part 3 Section 19.426, presentation:style-name**

- a. *The standard defines the attribute presentation:style-name*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint treats draw:style-name and presentation:style-name equivalently. On write, PowerPoint uses presentation style names for placeholder shapes.

### **2.1.681 Part 3 Section 19.427, presentation:transition-on-click**

- a. *The standard defines the attribute presentation:transition-on-click, contained within the element <presentation:settings>*

This attribute is supported in PowerPoint 2013 and later.

A value of True for this attribute and a value of True for presentation:full-screen shows the slideshow in regular full screen mode. A value of True for this attribute and a value of False for presentation:full-screen shows the slideshow in browsing (windowed) mode. A value of False for this attribute and a value of True for presentation:full-screen shows the slideshow in kiosk mode. A value of False for this attribute and a value of False for presentation:full-screen shows the slide show in regular full-screen slideshow mode.

### **2.1.682 Part 3 Section 19.428, presentation:use-date-time-name**

- a. *The standard defines the attribute presentation:use-date-time-name, contained within the element <draw:page>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint reads dates and times declared using this attribute, but writes them out as textboxes with regular text.

- b. *The standard defines the attribute presentation:use-date-time-name, contained within the element <style:handout-master>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.683 Part 3 Section 19.429, presentation:use-footer-name**

- a. *The standard defines the attribute presentation:use-footer-name, contained within the element <draw:page>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint reads footers declared using this attribute, but writes them out as textboxes with regular text.

- b. *The standard defines the attribute presentation:use-footer-name, contained within the element <style:handout-master>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.684 Part 3 Section 19.430, presentation:use-header-name**

- a. *The standard defines the attribute presentation:use-header-name, contained within the element <draw:page>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint reads headers declared using this attribute, but writes them out as textboxes with regular text.

- b. *The standard defines the attribute presentation:use-header-name, contained within the element <style:handout-master>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.685 Part 3 Section 19.431, presentation:user-transformed**

- a. *The standard defines the attribute presentation:user-transformed*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.686 Part 3 Section 19.433, script:event-name**

- a. *The standard defines the attribute script:event-name, contained within the element <presentation:event-listener>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint only supports the dom:click and dom:mouseover events.

This attribute is supported in PowerPoint 2013 and later.

Only the dom:click and dom:mouseover events are loaded/saved by PowerPoint (See section 9.9). Other events are not supported.

- b. *The standard defines the property "dom:mouseover", contained within the attribute script:event-name, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2013 and later.

PowerPoint only supports this property on shapes. It is not supported on text.

### **2.1.687 Part 3 Section 19.434, script:language**

- a. *The standard defines the attribute script:language, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.688 Part 3 Section 19.435, script:macro-name**

- a. *The standard defines the attribute script:macro-name, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.689 Part 3 Section 19.437, smil:accumulate**

- a. *The standard defines the attribute smil:accumulate*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.690 Part 3 Section 19.438, smil:additive**

- a. *The standard defines the attribute smil:additive*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.691 Part 3 Section 19.439, smil:attributeName**

- a. *The standard defines the property "charColor", contained within the attribute smil:attributeName*

This property is not supported in PowerPoint 2013 or later.

PowerPoint disregards color animations for animations that use the AnimColor element.

- b. *The standard defines the property "charPosture", contained within the attribute smil:attributeName*

This property is not supported in PowerPoint 2013 or later.

- c. *The standard defines the property "fillColor", contained within the attribute smil:attributeName*

This property is not supported in PowerPoint 2013 or later.

PowerPoint disregards color animations for animations that use the AnimColor element.

- d. *The standard defines the property "lineColor", contained within the attribute smil:attributeName*

This property is not supported in PowerPoint 2013 or later.

PowerPoint disregards color animations for animations that use the AnimColor element.

- e. *The standard defines the property "skewX", contained within the attribute smil:attributeName*

This property is not supported in PowerPoint 2013 or later.

### **2.1.692 Part 3 Section 19.443, smil:calcMode**

- a. *The standard defines the property "paced", contained within the attribute smil:calcMode*

This property is not supported in PowerPoint 2013 or later.

- b. *The standard defines the property "spline", contained within the attribute smil:calcMode*

This property is not supported in PowerPoint 2013 or later.

- c. *The standard defines the attribute smil:calcMode, contained within the element <anim:animateMotion>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint supports the values "discrete" and "linear" for this attribute.

### **2.1.693 Part 3 Section 19.448, smil:endsync**

- a. *The standard defines the attribute smil:endsync*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.694 Part 3 Section 19.449, smil:fadeColor**

- a. *The standard defines the attribute smil:fadeColor, contained within the element <anim:transitionFilter>*

This attribute is not supported in PowerPoint 2013 or later.

- b. *The standard defines the attribute smil:fadeColor, contained within the element <style:drawing-page-properties>*

This attribute is not supported in PowerPoint 2013 or later.

The fadeColor can only be black.

### **2.1.695 Part 3 Section 19.450, smil:fill**

- a. *The standard defines the property "auto", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2013 or later.

- b. *The standard defines the property "default", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2013 or later.

- c. *The standard defines the property "freeze", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2013 or later.

- d. *The standard defines the property "transition", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2013 or later.

### **2.1.696 Part 3 Section 19.451, smil:fillDefault**

- a. *The standard defines the attribute smil:fillDefault*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.697 Part 3 Section 19.453, smil:keySplines**

- a. *The standard defines the attribute smil:keySplines*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.698 Part 3 Section 19.458, smil:restart**

- a. *The standard defines the attribute smil:restart*

This attribute is not supported in PowerPoint 2013 or later.



## **2.1.699 Part 3 Section 19.459, smil:restartDefault**

- a. *The standard defines the attribute smil:restartDefault*

This attribute is not supported in PowerPoint 2013 or later.

## **2.1.700 Part 3 Section 19.463, smil:type**

- a. *The standard defines the property "arrowHeadWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- b. *The standard defines the property "barnDoorWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

Subtypes "vertical" and "horizontal" are supported in both forward and reverse directions.

- c. *The standard defines the property "barnVeeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- d. *The standard defines the property "barnZigZagWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- e. *The standard defines the property "barWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- f. *The standard defines the property "bowTieWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- g. *The standard defines the property "boxSnakesWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- h. *The standard defines the property "clockWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

Only the "clockwiseTwelve" subtype in the forward direction is supported. All other subtypes and directions are mapped to this one.

- i. *The standard defines the property "diagonalWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- j. *The standard defines the property "doubleFanWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- k. *The standard defines the property "doubleSweepWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- l. *The standard defines the property "ellipseWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

Only the "circle" subtype is supported. All other subtypes are mapped to this one.

- m. *The standard defines the property "eyeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- n. *The standard defines the property "fade", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

All fade wipes map to "crossfade".

- o. *The standard defines the property "fanWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

Only the "centerTop" subtype in the forward direction is supported. All other fanwipe objects map to this one.

- p. *The standard defines the property "fourBoxWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

The fourBoxWipe property in combination with direction "forward" maps to "cornersOut". The fourBoxWipe property in combination with direction "reverse" maps to "cornersIn".

- q. *The standard defines the property "hexagonWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- r. *The standard defines the property "irisWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

Subtypes "rectangle" and "diamond" are supported in both forward and reverse directions.

- s. *The standard defines the property "miscDiagonalWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- t. *The standard defines the property "miscShapeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- u. *The standard defines the property "parallelSnakesWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- v. *The standard defines the property "pentagonWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- w. *The standard defines the property "pinWheelWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2013 and later.

Only the "twoBladeVertical" and the "fourBlade" subtypes in the forward directions are supported. All other subtypes and directions map to the clockWipe, single spoke transition on load in PowerPoint.

- x. *The standard defines the property "pushWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- y. *The standard defines the property "roundRectWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- z. *The standard defines the property "saloonDoorWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- aa. *The standard defines the property "singleSweepWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- bb. *The standard defines the property "snakeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- cc. *The standard defines the property "spiralWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- dd. *The standard defines the property "starWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- ee. *The standard defines the property "triangleWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- ff. *The standard defines the property "veeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- gg. *The standard defines the property "waterfallWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- hh. *The standard defines the property "windshieldWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- ii. *The standard defines the property "zigZagWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2013 or later.

- jj. *The standard defines the attribute smil:type, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2013 and later.

In PowerPoint, if a slide has a transition that is not found in the ODF or SMIL spec, it will be saved with a fade transition, that is, smil:type="fade".

- kk. *The standard defines the property "arrowHeadWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- ll. *The standard defines the property "barnDoorWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint supports BarnDoorWipe subtypes "vertical" and "horizontal" in forward and reverse directions.

- mm. *The standard defines the property "barnVeeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- nn. *The standard defines the property "barnZigZagWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- oo. *The standard defines the property "barWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint supports BarWipe subtypes "topToBottom" and "leftToRight" in forward and reverse directions. All other subtype/direction combinations map to "topToBottom" in forward direction.

- pp. *The standard defines the property "bowTieWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- qq. *The standard defines the property "boxSnakesWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- rr. *The standard defines the property "boxWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- ss. *The standard defines the property "clockWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint only supports the clockwiseTwelve subtype in the forward direction. All other subtype/direction combinations are mapped to this one.

- tt. *The standard defines the property "diagonalWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- uu. *The standard defines the property "doubleFanWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- vv. *The standard defines the property "doubleSweepWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- ww. *The standard defines the property "ellipseWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint only supports the circular ellipseWipe subtype in the forward direction. All other subtype/direction combinations are mapped to this one.

- xx. *The standard defines the property "eyeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- yy. *The standard defines the property "fade", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint supports crossfade and fadeFromColor. All others map to "crossfade".

- zz. *The standard defines the property "fanWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint only supports the centerTop fanWipe in the forward direction. All other subtype/direction combinations are mapped to this one.

aaa. *The standard defines the property "fourBoxWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

bbb. *The standard defines the property "hexagonWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

ccc. *The standard defines the property "irisWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint supports the "rectangle" irisWipe subtype in both the forward and reverse directions. The "diamond" irisWipe subtype is only supported in the forward direction. All other subtype/direction combinations map to "rectangle" in the forward direction.

ddd. *The standard defines the property "miscDiagonalWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

eee. *The standard defines the property "miscShapeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

fff. *The standard defines the property "parallelSnakesWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

ggg. *The standard defines the property "pentagonWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

hhh. *The standard defines the property "pinWheelWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint makes the following mappings: pinWheelWipe subtypes "twoBladeVertical" and "twoBladeHorizontal" (in any direction) both map to "twoBladeVertical" forward. pinWheelWipe subtype "fourBlade" (in any direction) maps to "fourBlade" forward. All other subtypes map to the clockWipe transition.

iii. *The standard defines the property "pushWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint supports pushWipes subtypes "fromTop", "fromBottom", "fromLeft" and "fromRight" in the forward direction. Other subtypes and reverse pushWipes are mapped to "fromLeft" pushWipes in the forward direction.

jjj. *The standard defines the property "roundRectWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

kkk. *The standard defines the property "saloonDoorWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

lll. *The standard defines the property "singleSweepWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

mmm. *The standard defines the property "slideWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint supports slideWipe subtypes "fromTop", "fromBottom", "fromLeft" and "fromRight" in forward and reverse directions. All other slideWipe subtypes are mapped to "fromLeft" in forward or reverse direction.

nnn. *The standard defines the property "snakeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

ooo. *The standard defines the property "spiralWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

ppp. *The standard defines the property "starWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

PowerPoint only supports the four-point starWipe in the forward direction. All other subtype/direction combinations are mapped to this one.

qqq. *The standard defines the property "triangleWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

rrr. *The standard defines the property "veeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

sss. *The standard defines the property "waterfallWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

ttt. *The standard defines the property "windshieldWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

uuu. *The standard defines the property "zigZagWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

### 2.1.701 Part 3 Section 19.465, style:adjustment

- a. *The standard defines the attribute style:adjustment, contained within the element <style:footnote-sep>*

This attribute is not supported in Excel 2013 or later.

### 2.1.702 Part 3 Section 19.466, style:apply-style-name

- a. *The standard defines the attribute style:apply-style-name, contained within the element <style:map>, contained within the parent element <style:style>*

This attribute is supported in Excel 2013 and later.

Excel conditional formatting does not support the following formatting:

alignment formatting

font size

font face

thick and double borders

diagonal borders

Excel does not save pattern fills.

### 2.1.703 Part 3 Section 19.467, style:auto-update

- a. *The standard defines the attribute style:auto-update, contained within the element <style:style>*

Word 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:auto-update, contained within the element <style:style>*

This attribute is not supported in Excel 2013 or later.

Excel 2013 does not support this attribute for a style applied to any of the following elements:



- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

c. *The standard defines the attribute style:auto-update, contained within the element <style:style>*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>

- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.704 Part 3 Section 19.468, style:base-cell-address**

- a. *The standard defines the attribute style:base-cell-address, contained within the element <style:map>, contained within the parent element <style:style>*

This attribute is supported in Excel 2013 and later.

The value of this attribute is the address of the upper-left cell of the conditional formatting's bounding reference. This attribute may be used in discontinuous ranges with conditional formatting.

### **2.1.705 Part 3 Section 19.469, style:char**

- a. *The standard defines the attribute style:char, contained within the element <style:tab-stop>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:char, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:char, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute style:char, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.706 Part 3 Section 19.470, style:class

- a. *The standard defines the attribute style:class, contained within the element <style:style>*

This attribute is not supported in Word 2013 or later.

Word 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:class, contained within the element <style:style>*

This attribute is not supported in Excel 2013 or later.

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

c. *The standard defines the attribute style:class, contained within the element <style:style>*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

#### **2.1.707 Part 3 Section 19.471, style:color**

- a. *The standard defines the attribute style:color, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:color, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:color, contained within the element <style:footnote-sep>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.708 Part 3 Section 19.472, style:condition**

- a. *The standard defines the attribute style:condition, contained within the element <style:map>, contained within the parent element <style:style>*

This attribute is supported in Excel 2013 and later.

#### **2.1.709 Part 3 Section 19.473, style:data-style-name**

- a. *The standard defines the attribute style:data-style-name, contained within the element <style:style>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:data-style-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.710 Part 3 Section 19.474, style:default-outline-level**

- a. *The standard defines the attribute style:default-outline-level, contained within the element <style:style>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute style:default-outline-level, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.711 Part 3 Section 19.475, style:display**

- a. *The standard defines the attribute style:display, contained within the element <style:footer>*

This attribute is not supported in Excel 2013 or later.

On load, Excel drops this attribute, and causes a header or footer to be dropped completely if present.

- b. *The standard defines the attribute `style:display`, contained within the element `<style:header>`*

This attribute is not supported in Excel 2013 or later.

On load, Excel drops this attribute, and causes a header or footer to be dropped completely if present.

### **2.1.712 Part 3 Section 19.476, `style:display-name`**

- a. *The standard defines the attribute `style:display-name`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:display-name`, contained within the element `<number:date-style>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:display-name`, contained within the element `<number:time-style>`*

This attribute is not supported in Word 2013 or later.

On load, Word reads the `<number:time-style>` element and converts it to the matching `<text:date-style>` element.

On save, Word does not write out time fields or time styles.

- d. *The standard defines the attribute `style:display-name`, contained within the element `<style:master-page>`*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute `style:display-name`, contained within the element `<style:style>`*

Word 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- f. *The standard defines the attribute `style:display-name`, contained within the element `<text:list-style>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- g. *The standard defines the attribute `style:display-name`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `style:display-name`, contained within the element `<style:master-page>`, contained within the parent element `<office:master-styles>`*

This attribute is not supported in Excel 2013 or later.

On load, Excel does not read or display a master style name.

- i. *The standard defines the attribute `style:display-name`, contained within the element `<style:style>`*

This attribute is supported in Excel 2013 and later.

On save, Excel determines if an Excel style's name is a valid RNG (Relax-NG) name. If it is, the Excel style's name will be output to the `style:name` attribute. If the Excel style's name is not a valid RNG name, the name will be modified to make it a valid RNG escaped name before being output to the `style:name` attribute. If the style name is an escaped name, the original name will be output to the `style:display-name` attribute.

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- j. *The standard defines the attribute `style:display-name`, contained within the element `<text:list-style>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

k. *The standard defines the attribute `style:display-name`*

This attribute is not supported in PowerPoint 2013 or later.

l. *The standard defines the attribute `style:display-name`, contained within the element `<style:master-page>`*

This attribute is not supported in PowerPoint 2013 or later.

m. *The standard defines the attribute `style:display-name`, contained within the element `<style:presentation-page-layout>`*

This attribute is not supported in PowerPoint 2013 or later.

n. *The standard defines the attribute `style:display-name`, contained within the element `<style:style>`*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

o. *The standard defines the attribute `style:display-name`, contained within the element `<text:list-style>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.



### **2.1.713 Part 3 Section 19.477, style:distance**

- a. *The standard defines the attribute style:distance, contained within the element <style:drop-cap>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.714 Part 3 Section 19.478, style:distance-before-sep**

- a. *The standard defines the attribute style:distance-before-sep, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute style:distance-before-sep, contained within the element <style:footnote-sep>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.715 Part 3 Section 19.470, style:distance-after-sep**

- a. *The standard defines the attribute style:distance-after-sep, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute style:distance-after-sep, contained within the element <style:footnote-sep>*  
This attribute is not supported in Excel 2013 or later.

### **2.1.716 Part 3 Section 19.480, style:family**

- a. *The standard defines the attribute style:family, contained within the element <style:default-style>*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the property "chart", contained within the attribute style:family, contained within the element <style:default-style>*  
This property is not supported in Word 2013 or later.
- c. *The standard defines the property "control", contained within the attribute style:family, contained within the element <style:default-style>*  
This property is not supported in Word 2013 or later.
- d. *The standard defines the property "default", contained within the attribute style:family, contained within the element <style:default-style>*  
This property is not supported in Word 2013 or later.
- e. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:default-style>*  
This property is not supported in Word 2013 or later.
- f. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:default-style>*  
This property is supported in Word 2013 and later.

On load, Word does not support paragraph or text properties from styles of the graphic family.

On save, Word always writes "lr-tb" as the writing mode for styles of the graphic family.

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

**OfficeArt Math** in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- g. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- h. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2013 or later.

- i. *The standard defines the property "table-page", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2013 or later.

- j. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- k. *The standard defines the attribute style:family, contained within the element <style:style>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- l. *The standard defines the property "control", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2013 or later.

- m. *The standard defines the property "default", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2013 or later.

- n. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2013 or later.

- o. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2013 and later.

On load, Word does not support paragraph, text, or list properties from styles of the graphic family.

On save, Word always writes "lr-tb" as the writing mode for styles of the graphic family.

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- p. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- q. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2013 or later.

- r. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- s. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- t. *The standard defines the property "table-page", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2013 or later.

- u. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- v. *The standard defines the attribute style:family*

This attribute is not supported in Excel 2013 or later.

- w. *The standard defines the attribute style:family, contained within the element <style:default-style>*

This attribute is not supported in Excel 2013 or later.

- x. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:default-style>*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- y. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- z. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

aa. *The standard defines the attribute style:family, contained within the element <style:style>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

bb. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

cc. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>

- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

dd. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

ee. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

- ff. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- gg. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- hh. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*



This property is supported in Excel 2013 and later.

Excel uses text styles for headers, footers and Rich text formatting in cells.

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- ii. *The standard defines the attribute style:family, contained within the element <style:default-style>*

This attribute is not supported in PowerPoint 2013 or later.

- jj. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:default-style>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

kk. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

ll. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

mm. *The standard defines the attribute style:family, contained within the element <style:style>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>

- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

nn. *The standard defines the property "control", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2013 or later.

oo. *The standard defines the property "default", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2013 or later.

pp. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

qq. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

rr. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2013 or later.

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

ss. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2013 or later.

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

tt. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.717 Part 3 Section 19.481, style:filter-name**

- a. *The standard defines the attribute style:filter-name, contained within the element <style:background-image>*

This attribute is not supported in Excel 2013 or later.

### **2.1.718 Part 3 Section 19.482, style:font-adornments**

- a. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- c. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in <the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

### **2.1.719 Part 3 Section 19.483, style:font-charset**

- a. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-charset, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the property "other", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the property "x-symbol", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- f. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute style:font-charset, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

Excel supports only the value "x-symbol" to identify symbol fonts.

- h. *The standard defines the property "character encoding", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- i. *The standard defines the property "other", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- j. *The standard defines the property "x-symbol", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

Excel supports only the value "x-symbol" to identify symbol fonts.

OfficeArt Math in Excel 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in text boxes and shapes, SmartArt, and chart titles and labels, On load, this value of this attribute is used. It is not saved.

- k. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- l. *The standard defines the property "other", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.



- m. *The standard defines the property "x-symbol", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. It is not written out.

### **2.1.720 Part 3 Section 19.484, style:font-family-generic**

- a. *The standard defines the attribute style:font-family-generic, contained within the element <style:font-face>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-family-generic, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:font-family-generic, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- d. *The standard defines the attribute `style:font-family-generic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `style:font-family-generic`, contained within the element `<style:text-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute `style:font-family-generic`, contained within the element `<style:font-face>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- g. *The standard defines the attribute `style:font-family-generic`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.721 Part 3 Section 19.485, style:font-pitch

- a. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-pitch, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- d. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:font-pitch, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

f. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

g. *The standard defines the attribute style:font-pitch, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.722 Part 3 Section 19.486, style:height**

- a. *The standard defines the attribute style:height, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:height, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2013 or later.

### **2.1.723 Part 3 Section 19.487, style:leader-char**

- a. *The standard defines the attribute style:leader-char, contained within the element <text:index-entry-tab-stop>*

This attribute is supported in Word 2013 and later.

On load, Word ignores this element and uses a default style to format tables of contents and indexes. On save, Word saves this element for tables of contents, but not for indexes.

### **2.1.724 Part 3 Section 19.488, style:leader-color**

- a. *The standard defines the attribute style:leader-color, contained within the element <style:tab-stop>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:leader-color, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:leader-color, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute `style:leader-color`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `style:leader-color`, contained within the element `<style:tab-stop>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.725 Part 3 Section 19.489, style:leader-style**

- a. *The standard defines the attribute `style:leader-style`, contained within the element `<style:tab-stop>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "dot-dash", contained within the attribute `style:leader-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This property is supported in Word 2013 and later.

On load, Word interprets the "dot-dash" value of `style:leader-style` as a dotted line style, similar to that of the "dotted" value for this attribute.

- c. *The standard defines the property "dot-dot-dash", contained within the attribute `style:leader-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This property is supported in Word 2013 and later.

On load, Word interprets the "dot-dash" value of `style:leader-style` as a dotted line style, similar to that of the "dotted" value for this attribute.

- d. *The standard defines the property "long-dash", contained within the attribute `style:leader-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This property is not supported in Word 2013 or later.

- e. *The standard defines the property "wave", contained within the attribute `style:leader-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This property is not supported in Word 2013 or later.

- f. *The standard defines the attribute `style:leader-style`, contained within the element `<style:tab-stop>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- g. *The standard defines the attribute `style:leader-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `style:leader-style`, contained within the element `<style:tab-stop>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.726 Part 3 Section 19.490, `style:leader-text`**

- a. *The standard defines the attribute `style:leader-text`, contained within the element `<style:tab-stop>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:leader-text`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is supported in Word 2013 and later.

On load and save, Word supports the following characters for the style:leader-text attribute: ".", "-", "\_", " ", plus locale-specific characters defined by the country/language pair of the surrounding text.

On load, if Word does not recognize the character used, then it reverts to a default of no leader text.

- c. *The standard defines the attribute style:leader-text, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute style:leader-text, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:leader-text, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## **2.1.727 Part 3 Section 19.491, style:leader-text-style**

- a. *The standard defines the attribute style:leader-text-style, contained within the element <style:tab-stop>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.



- b. *The standard defines the attribute `style:leader-text-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:leader-text-style`, contained within the element `<style:tab-stop>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- d. *The standard defines the attribute `style:leader-text-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `style:leader-text-style`, contained within the element `<style:tab-stop>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

## **2.1.728 Part 3 Section 19.492, `style:leader-type`**

- a. *The standard defines the attribute `style:leader-type`, contained within the element `<style:tab-stop>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:leader-type`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:leader-type`, contained within the element `<style:tab-stop>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- d. *The standard defines the attribute `style:leader-type`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `style:leader-type`, contained within the element `<style:tab-stop>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.729 Part 3 Section 19.493, `style:leader-width`**

- a. *The standard defines the attribute `style:leader-width`, contained within the element `<style:tab-stop>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:leader-width`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:leader-width`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `style:leader-width`, contained within the element `<style:tab-stop>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

#### **2.1.730 Part 3 Section 19.494, style:legend-expansion**

- a. *The standard defines the attribute `style:legend-expansion`*

This attribute is supported in Excel 2021 and later.

On save, if the legend has custom dimensions Excel writes `custom` for this attribute.

On load, Excel ignores this attribute.

#### **2.1.731 Part 3 Section 19.495, style:legend-expansion-aspect-ratio**

- a. *The standard defines the attribute `style:legend-expansion-aspect-ratio`*

This attribute is supported in Excel 2021 and later.

On save, if the legend has custom dimensions Excel writes the aspect ratio to this attribute.

On load, Excel ignores this attribute.

#### **2.1.732 Part 3 Section 19.496, style:length**

- a. *The standard defines the attribute `style:length`, contained within the element `<style:drop-cap>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.733 Part 3 Section 19.497, style:line-style**

- a. *The standard defines the attribute `style:line-style`, contained within the element `<style:footnote-sep>`, contained within the parent element `<style:page-layout-properties>`*

This attribute is supported in Word 2013 and later.

On load and on save, Word supports the following line styles for the style:line-style attribute: "solid", "dotted", "dashed", and "none". All other line styles map to a default of "solid".

- b. *The standard defines the attribute style:line-style, contained within the element <style:footnote-sep>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.734 Part 3 Section 19.498, style:lines**

- a. *The standard defines the attribute style:lines, contained within the element <style:drop-cap>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.735 Part 3 Section 19.500, style:list-style-name**

- a. *The standard defines the attribute style:list-style-name, contained within the element <style:style>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute style:list-style-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.736 Part 3 Section 19.501, style:master-page-name**

- a. *The standard defines the attribute style:master-page-name, contained within the element <style:style>*

This attribute is supported in Word 2013 and later.

On load, Word reads in the master-page properties but store them in multiple different levels (page or section).

On load, if Word cannot find any references to master page styles, then it generates a new master-page and assigns it application default properties.

On save, Word creates a new master-page and associates it with a new application generated name.

- b. *The standard defines the attribute style:master-page-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.737 Part 3 Section 19.502, style:name**

- a. *The standard defines the attribute style:name, contained within the element <style:font-face>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:name, contained within the element <style:style>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word requires that a style name be unique not only within the same style:family attribute but within the entire file. If a style with a duplicate name exists, Word ignores the duplicate style.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:name, contained within the element <text:list-style>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- d. *The standard defines the attribute style:name, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- e. *The standard defines the attribute style:name, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2013 or later.

On load, Excel ignores the <style:font-face> element, all attributes of the <style:font-face> element, and all child elements. Excel reads the <style:font-name> attribute to determine the font to apply.

On save, Excel writes out the <style:font-face> element, along with values for the <style:name> and <svg:font-family> attributes.

f. *The standard defines the attribute style:name, contained within the element <style:style>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel requires that a style name be unique not only within the same style:family attribute but within the entire file. If a style with a duplicate name exists, Excel ignores the duplicate style.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

g. *The standard defines the attribute style:name, contained within the element <text:list-style>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- h. *The standard defines the attribute style:name, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- i. *The standard defines the attribute style:name, contained within the element <style:master-page>*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint has two levels of masters: masters and layouts. Masters have the naming convention "Master#-[Master Name]" while layouts take the form "Master#-Layout#-[Layout Name]". On load, PowerPoint matches layout pages with their corresponding master pages (those having the same Master#), as one of the inheriting layouts. Master pages whose names do not conform to either of these formats, and layout pages that do not have a corresponding master, are treated as masters and are given the default PowerPoint layouts.

- j. *The standard defines the attribute style:name, contained within the element <style:style>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint requires that a style name be unique not only within the same style:family attribute but within the entire file. If a style with a duplicate name exists, PowerPoint ignores the duplicate style.

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- k. *The standard defines the attribute style:name, contained within the element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.738 Part 3 Section 19.503, style:next-style-name**

- a. *The standard defines the attribute style:next-style-name, contained within the element <style:master-page>*

This attribute is not supported in Word 2013 or later.

On load, Word maintains the style:next-style-name attribute of the first page by allowing all subsequent pages to inherit their headers/footers from the style specified by the style:next-style-name attribute.

Word only saves the style:next-style-name attribute if the master page for the first page of the document differs from the second page.

- b. *The standard defines the attribute style:next-style-name, contained within the element <style:master-page>, contained within the parent element <office:master-styles>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:next-style-name, contained within the element <style:style>*



This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute style:next-style-name, contained within the element <style:master-page>*

This attribute is not supported in PowerPoint 2013 or later.

- e. *The standard defines the attribute style:next-style-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.739 Part 3 Section 19.504, style:num-format**

- a. *The standard defines the attribute style:num-format*

This attribute is supported in Word 2013 and later.

See Section 12.2.2 for supported formats.

- b. *The standard defines the property "[string]", contained within the attribute style:num-format*

This property is supported in Word 2013 and later.

On load, numbering formats that are not familiar to Word are displayed using the Arabic numeral format (1, 2, 3...).

On save and load, the following strings are also supported by Word as numbering formats:

᠑ , ᠠ , ᠡ , ...

ᠠ , ᠡ , ᠢ , ...

ᠠ , ᠡ , ᠢ , ...

ᠠ , ᠡ , ᠢ , ...

One, Two, Three, ...

\* , † , ‡ , ...

一 , 十 , 一〇〇(簡) , ...

一 , 十 , 一百 (簡) , ...

壹 , 貳 叁 , ...

ㄱ , ㄴ , ㄷ , ...

① , ② , ③ , ...

① , ② , ③ , ...

1 , 2 , 3 , ...

(1) , (2) , (3) , ...

1 , 2 , 3 , ...

01 , 02 , 03 , ...

가 , 나 , 다 , ...

κ , ' , 7 , ...  
κ , 2 , λ , ...  
1, A, B, ...  
अ, आ, इ , ...  
□□, □□, □□□, ...  
१ , २ , ३ , ...  
क, ख, ग , ...  
一, 一〇, 一〇〇, ...  
(一), (二), (三), ...  
壹, 貳, 參, ...  
甲, 乙, 丙, ...  
子, 丑, 寅, ...  
甲子, 乙丑, 丙寅, ...  
イ, 口, 八 , ...  
イ, 口, 八, ...  
一, 二, 三 ...  
一, 二, 三, 万, ...  
壹, 貳, 參, ...  
일, 이, 삼, ...  
일, 일영, 일영영, ...  
一, 一零, 一零零, ...  
하나, 둘, 셋, ...  
- 1 -, - 2 -, - 3 -, ...  
1st, 2nd, 3rd, ...  
First, Second, Third, ...  
a, б, B, ...  
A, B, B, ...  
一, 十, 一〇〇(繁), ...  
一, 十, 一百 (繁), ...  
一, 一〇, 一〇〇(繁), ...  
□□□□, ส ข ง , ส 7 ม , ...  
ဂ , ဘ , င , ...

၁ ,၂ ,၃ , ...

A, Ç, Ğ, ...

a, ç, ğ, ...

A,Й,Ъ, ...

a,й,ъ, ...

A, B, Γ, ...

α, β, γ, ...

001,002, 003, ...

0001,0002, 0003, ...

00001,00002, 00003, ...

- c. *The standard defines the attribute style:num-format, contained within the element <text:linenumbers-configuration>*

This attribute is not supported in Word 2013 or later.

All values for the style:num-format attribute revert to the Word default of Arabic numerals (1,2,3, ...).

- d. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

This attribute is supported in Word 2013 and later.

On load, numbering formats that are not familiar to Word will be displayed using the Arabic numeral format (1, 2, 3...).

On save and load, the following strings are also supported by Word as numbering formats:

ア , イ , ウ , ...

ア , イ , ウ , ...

أ , ب , ج , ...

أ , ب , ت , ...

One, Two, Three, ...

\*, †, ‡, ...

一, 十, 一〇〇(簡), ...

一, 十, 一百 (簡), ...

壹, 貳, 參, ...

ㄱ , ㄴ , ㄷ , ...

①,②,③, ...

①,②,③, ...

1.,2.,3., ...

(1), (2), (3), ...  
1, 2, 3, ...  
01, 02, 03, ...  
가, 나, 다, ...  
κ, λ, μ, ...  
κ, γ, λ, ...  
1, A, B, ...  
ਅ, ਆ, ਐ, ...  
□□, □□, □□□, ...  
१, २, ३, ...  
क, ख, ग, ...  
一, 一〇, 一〇〇, ...  
(一), (二), (三), ...  
壹, 貳, 參, ...  
甲, 乙, 丙, ...  
子, 丑, 寅, ...  
甲子, 乙丑, 丙寅, ...  
イ, 口, 八, ...  
イ, 口, 八, ...  
一, 二, 三, ...  
一, 二, 三, 万, ...  
壹, 貳, 參, ...  
일, 이, 삼, ...  
일, 일영, 일영영, ...  
一, 一零, 一零零, ...  
하나, 둘, 셋, ...  
- 1 -, - 2 -, - 3 -, ...  
1st, 2nd, 3rd, ...  
First, Second, Third, ...  
a, б, в, ...  
A, Б, В, ...  
一, 十, 一〇〇(繁), ...

一, 十, 一百 (繁), ...  
一, 一〇, 一〇〇(繁), ...  
□□□□, ส ข ง , ส ๗ ม , ...  
п , ы , ъ , ...  
๑ , ๒ , ๓ , ...  
A, Ç, Ĝ, ...  
a, ç, ĝ, ...  
А, Ё, Ъ, ...  
а, ё, ъ, ...  
A, B, Г, ...  
a, β, γ, ...  
001,002, 003, ...  
0001,0002, 0003, ...  
00001,00002, 00003, ...

- e. *The standard defines the attribute style:num-format, contained within the element <text:notes-configuration>*

This attribute is supported in Word 2013 and later.

On load, numbering formats that are not familiar to Word will be displayed using the Arabic numeral format (1, 2, 3...).

On save and load, the following strings are also supported by Word as numbering formats:

ｱ , ｲ , ｳ , ...  
ア, イ, ウ, ...  
ﺍ , ﺑ , ﺝ , ...  
ا , ب , ت , ...  
One, Two, Three, ...  
\*, †, ‡, ...  
一, 十, 一〇〇(简), ...  
一, 十, 一百 (简), ...  
壹, 貳, 叁, ...  
ㄐ , ㄌ , ㄍ , ...  
①,②,③, ...  
①,②,③, ...  
1.,2.,3., ...

(1), (2), (3), ...  
1, 2, 3, ...  
01, 02, 03, ...  
가, 나, 다, ...  
κ, λ, μ, ν, ...  
κ, ρ, σ, τ, ...  
1, A, B, ...  
ਅ, ਆ, ਐ, ...  
□□, □□, □□□, ...  
१, २, ३, ...  
क, ख, ग, ...  
一, 一〇, 一〇〇, ...  
(一), (二), (三), ...  
壹, 貳, 參, ...  
甲, 乙, 丙, ...  
子, 丑, 寅, ...  
甲子, 乙丑, 丙寅, ...  
イ, ロ, ハ, ...  
イ, ロ, ハ, ...  
一, 二, 三, ...  
一, 二, 三, 万, ...  
壹, 貳, 參, ...  
일, 이, 삼, ...  
일, 일영, 일영영, ...  
一, 一零, 一零零, ...  
하나, 둘, 셋, ...  
- 1 -, - 2 -, - 3 -, ...  
1st, 2nd, 3rd, ...  
First, Second, Third, ...  
a, б, в, ...  
A, Б, В, ...  
一, 十, 一〇〇(繁), ...

一, 十, 一百 (繁), ...

一, 一〇, 一〇〇(繁), ...

□□□□, સ ં ં , સ ૃ મ , ...

୩ , ୩ , ୩ , ...

୧ , ୨ , ୩ , ...

- f. *The standard defines the attribute style:num-format, contained within the element <text:page-number>*

This attribute is supported in Word 2013 and later.

On load, numbering formats that are not familiar to Word will be displayed using the Arabic numeral format (1, 2, 3...).

On save and load, the following strings are also supported by Word as numbering formats:

ア , イ , ウ , ...

ア , イ , ウ , ...

أ , ب , ج , ...

أ , ب , ت , ...

One, Two, Three, ...

\* , † , ‡ , ...

一, 十, 一〇〇(简), ...

一, 十, 一百 (简), ...

壹, 貳, 參, ...

ㄱ , ㄴ , ㄷ , ...

①, ②, ③, ...

①, ②, ③, ...

1., 2., 3., ...

(1), (2), (3), ...

1, 2, 3, ...

01, 02, 03, ...

가, 나, 다, ...

κ , λ , μ , ...

κ , λ , μ , ...

1, A, B, ...

अ, आ, इ, ...

□□, □□, □□□, ...

१ , २ , ३ , ...  
 क, ख, ग, ...  
 一, 一〇, 一〇〇, ...  
 (一), (二), (三), ...  
 壹, 貳, 參, ...  
 甲, 乙, 丙, ...  
 子, 丑, 寅, ...  
 甲子, 乙丑, 丙寅, ...  
 一, 二, 三, ...  
 一, 二, 三, ...  
 一, 二, 三, 万, ...  
 壹, 貳, 參, ...  
 일, 이, 삼, ...  
 일, 일영, 일영영, ...  
 一, 一零, 一零零, ...  
 하나, 둘, 셋, ...  
 - 1 -, - 2 -, - 3 -, ...  
 1st, 2nd, 3rd, ...  
 First, Second, Third, ...  
 a, б, в, ...  
 A, Б, В, ...  
 一, 十, 一〇〇(繁), ...  
 一, 十, 一百(繁), ...  
 一, 一〇, 一〇〇(繁), ...  
 □□□□, ส อ ง , ส ำ ม , ...  
 १ , २ , ३ , ...  
 ๑ , ๒ , ๓ , ...

- g. *The standard defines the attribute style:num-format, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>*



**OfficeArt Math** in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- i. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

On load, the value of the style:num-format attribute is considered in combination with the values of the style:num-prefix and style:num-suffix attributes to determine the "buAutoNum" value used.

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "a":

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaLcPeriod"

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "A":

- "alphaUcParenBoth"
- "AlphaUcParenR"
- "AlphaUcPeriod"

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "1":

- "arabicParenBoth"
- "arabicParenR"
- "arabicPeriod"

- "arabicPlain"
- "circleNumWdBlackPlain"
- "circleNumWdWhitePlain"

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "一, 二, 三, 四, ...":

- "ea1ChsPeriod"
- "ea1ChsPlain"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnChsDbPeriod"
- "ea1JpnKorPeriod"
- "ea1JpnKorPlain"

On save, "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "أ, ب, ت, ...".

On save, "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "أ, ب, ج, ...".

On save, "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value "1., 2., 3., ...".

On save, "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value "1, 2, 3, ...".

On save, "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "①, ②, ③, ...".

On save, "buAutoNum" equals the value "hebrew2Minus" is written as style:num-format equals the value "א, ב, ג, ...".

On save, "buAutoNum" equals the value "hindiAlpha1Period" is written as style:num-format equals the value "क, ख, ग, ...".

On save, "buAutoNum" equals the value "hindiAlphaPeriod" is written as style:num-format equals the value "अ, आ, इ, ...".

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "१, २, ३, ...":

- "hindiNumParenR"
- "hindiNumPeriod"

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "i":

- "romanLcParenBoth"
- "romanLcParenR"
- "RomanLcPeriod"

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "I":

- "romanUcParenBoth"
- "romanUcParenR"
- "RomanUcPeriod"

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "ñ, ы, ъ, ...":

- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiAlphaPeriod"

On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "๑ , ๒ , ๓ , ...":

- "thaiNumParenBoth"
- "thaiNumParenR"
- "thaiNumPeriod"

- j. *The standard defines the attribute style:num-format, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- k. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- l. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the value of the style:num-format attribute is considered in combination with the values of the style:num-prefix and style:num-suffix attributes to determine the "buAutoNum" value used.

On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "a":

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaLcPeriod"

On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "A":

- "alphaUcParenBoth"
- "AlphaUcParenR"
- "AlphaUcPeriod"

On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "1":

- "arabicParenBoth"
- "arabicParenR"
- "arabicPeriod"
- "arabicPlain"
- "circleNumWdBlackPlain"
- "circleNumWdWhitePlain"

On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "一, 二, 三, 四, ...":

- "ea1ChsPeriod"
- "ea1ChsPlain"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnChsDbPeriod"
- "ea1JpnKorPeriod"
- "ea1JpnKorPlain"

On write, "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "أ , ب , ت , ...".

On write, "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "أ , ب , ج , ...".

On write, "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value "1., 2., 3., ...".

On write, "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value "1, 2, 3, ...".

On write, "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "①, ②, ③, ...".

On write, "buAutoNum" equals the value "hebrew2Minus" is written as s

## 2.1.740 Part 3 Section 19.505, style:num-letter-sync

- a. The standard defines the attribute style:num-letter-sync, contained within the element <text:linenumbers-configuration>

This attribute is not supported in Word 2013 or later.

- b. The standard defines the property "false", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>

**OfficeArt Math** in Excel 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- c. *The standard defines the property "true", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes. 1) On load, this value is ignored.

On save, this value is written for the following "buAutoNum" values:

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaLcPeriod"
- "alphaUcParenBoth"
- "alphaUcParenR"
- "alphaUcPeriod"
- "arabic1Minus"
- "arabic2Minus"
- "arabicDbPeriod"
- "arabicDbPlain"
- "circleNumDbPlain"
- "circleNumWdBlackPlain"
- "circleNumWdWhitePlain"
- "ea1ChsPeriod"
- "ea1ChsPlain"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnChsDbPeriod"

- "ea1JpnKorPeriod"
  - "ea1JpnKorPlain"
  - "hebrew2Minus"
  - "hindiAlpha1Period"
  - "hindiAlphaPeriod"
  - "hindiNumParenR"
  - "hindiNumPeriod"
  - "thaiAlphaParenBoth"
  - "thaiAlphaParenR"
  - "thaiAlphaPeriod"
  - "thaiNumParenBoth"
  - "thaiNumParenR"
  - "thaiNumPeriod"
- d. *The standard defines the property "false", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:text-box>
  - <draw:frame>
  - <draw:custom-shape>
- e. *The standard defines the property "true", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this property is ignored.

On write, this property is written for the following "buAutoNum" values:

- "alphaLcParenBoth"
- "alphaLcParenR"

- "alphaLcPeriod"
- "alphaUcParenBoth"
- "alphaUcParenR"
- "alphaUcPeriod"
- "arabic1Minus"
- "arabic2Minus"
- "arabicDbPeriod"
- "arabicDbPlain"
- "circleNumDbPlain"
- "circleNumWdBlackPlain"
- "circleNumWdWhitePlain"
- "ea1ChsPeriod"
- "ea1ChsPlain"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnChsDbPeriod"
- "ea1JpnKorPeriod"
- "ea1JpnKorPlain"
- "hebrew2Minus"
- "hindiAlpha1Period"
- "hindiAlphaPeriod"
- "hindiNumParenR"
- "hindiNumPeriod"
- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiAlphaPeriod"
- "thaiNumParenBoth"
- "thaiNumParenR"
- "thaiNumPeriod"

## 2.1.741 Part 3 Section 19.506, style:num-prefix

- a. *The standard defines the attribute style:num-prefix, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-bullet>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt.

- c. *The standard defines the attribute style:num-prefix, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- e. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

On load, the value of the style:num-prefix attribute is considered in combination with the values of the style:num-format and style:num-suffix attributes to determine the "buAutoNum" value used. The only prefix character that is converted is "(".

On save, the following "buAutoNum" values are written as style-num-prefix equals the value "(":

- "alphaLcParenBoth"
- "alphaUcParenBoth"
- "arabicParenBoth"
- "romanLcParenBoth"
- "romanUcParenBoth"
- "thaiAlphaParenBoth"
- "thaiNumParenBoth"

For all other values, style-num-prefix is not written.

- f. *The standard defines the attribute style:num-prefix, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- g. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>



- <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:text-box>
  - <draw:frame>
  - <draw:custom-shape>.
- h. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On load, the value of the style:num-prefix attribute is considered in combination with values of the style:num-format and style:num-suffix attributes to determine the "buAutoNum" value used. The only prefix character that may be converted is "(".

On save, the following "buAutoNum" values from OOXML are written as style-num-prefix equals the value "(":

- "alphaLcParenBoth"
- "alphaUcParenBoth"
- "arabicParenBoth"
- "romanLcParenBoth"
- "romanUcParenBoth"
- "thaiAlphaParenBoth"
- "thaiNumParenBoth"

For all other values, style-num-prefix is not written.

### **2.1.742 Part 3 Section 19.507, style:num-suffix**

- a. *The standard defines the attribute style:num-suffix, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:num-suffix, contained within the element <text:list-level-style-bullet>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt.

- c. *The standard defines the attribute `style:num-suffix`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `style:num-suffix`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- e. *The standard defines the attribute `style:num-suffix`, contained within the element `<text:list-level-style-number>`, contained within the parent element `<text:list-style>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

On load, the value of the `style:num-suffix` attribute is considered in combination with the values of the `style:num-format` and `style:num-prefix` attributes to determine the "buAutoNum" value used.

On save, the following "buAutoNum" values are written as `style:num-suffix` equals the value "):

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaUcParenBoth"
- "alphaUcParenR"
- "arabicParenBoth"
- "arabicParenR"

- "hindiNumParenR"
- "romanLcParenBoth"
- "romanLcParenR"
- "romanUcParenBoth"
- "romanUcParenR"
- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiNumParenBoth"
- "thaiNumParenR"

On save, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value ".":

- "alphaLcPeriod"
- "alphaUcPeriod"
- "arabicPeriod"
- "ea1ChsPeriod"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnKorPeriod"
- "hindiAlpha1Period"
- "hindiAlphaPeriod"
- "thaiNumPeriod"
- "hindiNumPeriod"
- "romanLcPeriod"
- "romanUcPeriod"
- "thaiAlphaPeriod"

On save, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value "-":

- "arabic1Minus"
- "arabic2Minus"
- "hebrew2Minus"

On save, "buAutoNum" equals the value "ea1JpnChsDbPeriod" is written as style:num-suffix equals the value ". " (double byte UNICODE character FF0E).

- f. *The standard defines the attribute style:num-suffix, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- g. *The standard defines the attribute style:num-suffix, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- <draw:custom-shape>.
- h. *The standard defines the attribute style:num-suffix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value ")":

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaUcParenBoth"
- "alphaUcParenR"
- "arabicParenBoth"
- "arabicParenR"
- "hindiNumParenR"
- "romanLcParenBoth"
- "romanLcParenR"
- "romanUcParenBoth"
- "romanUcParenR"
- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiNumParenBoth"
- "thaiNumParenR".

On write, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value ".":

- "alphaLcPeriod"
- "alphaUcPeriod"
- "arabicPeriod"
- "ea1ChsPeriod"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnKorPeriod"
- "hindiAlpha1Period"
- "hindiAlphaPeriod"
- "thaiNumPeriod"
- "hindiNumPeriod"
- "romanLcPeriod"
- "romanUcPeriod"
- "thaiAlphaPeriod"

On write, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value "-":

- "arabic1Minus"
- "arabic2Minus"
- "hebrew2Minus"

On write, value "buAutoNum" equals "ea1JpnChsDbPeriod" is written as style:num-suffix equals the value ". " (double byte UNICODE character FF0E).

On read, the value of style:num-suffix is considered in combination with the values of the style:num-format and style:num-prefix attributes to determine the "buAutoNum" value used.

### **2.1.743 Part 3 Section 19.508, style:page-layout-name**

- a. *The standard defines the attribute style:page-layout-name, contained within the element <style:master-page>*

This attribute is supported in PowerPoint 2013 and later.

In PowerPoint, if different masters or pages have different size dimensions, they will all default to the dimensions of the last master that is not recognized to be a layout.

### **2.1.744 Part 3 Section 19.509, style:page-usage**

- a. *The standard defines the attribute style:page-usage, contained within the element <style:page-layout>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:page-usage, contained within the element <style:page-layout>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:page-usage, contained within the element <style:page-layout>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.745 Part 3 Section 19.510, style:parent-style-name**

- a. *The standard defines the attribute style:parent-style-name, contained within the element <style:style>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>

- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:parent-style-name, contained within the element <style:style>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:parent-style-name, contained within the element <style:style>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>

- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

## 2.1.746 Part 3 Section 19.512, style:position

- a. *The standard defines the attribute style:position, contained within the element <style:tab-stop>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:position, contained within the element <text:index-entry-tab-stop>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:position, contained within the element <style:background-image>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute style:position, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:frame>
  - <draw:text-box>
  - <draw:custom-shape>
- e. *The standard defines the attribute style:position, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute style:position, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.747 Part 3 Section 19.513, style:rel-height**

- a. *The standard defines the attribute style:rel-height, contained within the element <draw:frame>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:rel-height, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- c. *The standard defines the attribute style:rel-height, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- d. *The standard defines the attribute style:rel-height, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

### **2.1.748 Part 3 Section 19.514, style:rel-width**

- a. *The standard defines the attribute style:rel-width, contained within the element <draw:frame>*



This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:rel-width`, contained within the element `<style:footnote-sep>`, contained within the parent element `<style:page-layout-properties>`*

This attribute is supported in Word 2013 and later.

On load, all values for the `style:rel-width` attribute map to a default footnote separator width.

- c. *The standard defines the attribute `style:rel-width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- d. *The standard defines the attribute `style:rel-width`, contained within the element `<style:table-properties>`*

This attribute is supported in Word 2013 and later.

On load, if the width of the table is greater than can be supported by Word, the table will be automatically sized to fit the page.

- e. *The standard defines the attribute `style:rel-width`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `style:rel-width`, contained within the element `<style:footnote-sep>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `style:rel-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- h. *The standard defines the attribute `style:rel-width`, contained within the element `<style:table-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `style:rel-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

### **2.1.749 Part 3 Section 19.515, `style:repeat`**

- a. *The standard defines the attribute `style:repeat`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute style:repeat, contained within the element <style:background-image>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:repeat, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- d. *The standard defines the attribute style:repeat, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.750 Part 3 Section 19.518, style:style-name**

- a. *The standard defines the attribute style:style-name, contained within the element <style:drop-cap>, contained within the parent element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:style-name, contained within the element <style:drop-cap>*

This attribute is not supported in Excel 2013 or later.

## 2.1.751 Part 3 Section 19.519, style:type

- a. *The standard defines the attribute style:type, contained within the element <style:tab-stop>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "char", contained within the attribute style:type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2013 and later.

Word allows the character used here to be based on the country/language pair of the surrounding text. For example, U.S. English surrounding text would allow the use of "." as the tab character.

- c. *The standard defines the attribute style:type, contained within the element <text:index-entry-tab-stop>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute style:type, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, the enumerated value "char" is not supported.

- e. *The standard defines the attribute style:type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute style:type, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, the enumerated value "char" is not supported.

### 2.1.752 Part 3 Section 19.520, style:vertical-align

- a. *The standard defines the attribute style:vertical-align, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:vertical-align, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:vertical-align, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute style:vertical-align, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the property "bottom", contained within the attribute style:vertical-align, contained within the element <style:table-cell-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the vertical alignment property to automatic.

- f. *The standard defines the attribute style:vertical-align, contained within the element <style:paragraph-properties>*

This attribute is supported on load in PowerPoint 2013 and later. If the attribute is not explicitly provided, PowerPoint 2013 and later assume the value "auto" for the attribute, which results in behavior that is similar to, but not identical to, the default value of "baseline" that is indicated in the standard.

OfficeArt Math in PowerPoint 2013 and later supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.753 Part 3 Section 19.521, style:volatile**

- a. *The standard defines the attribute style:volatile*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:volatile, contained within the element <number:date-style>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:volatile, contained within the element <number:time-style>*

This attribute is not supported in Word 2013 or later.

On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.

On save, Word does not write out time fields or time styles.

- d. *The standard defines the attribute style:volatile*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:volatile*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.754 Part 3 Section 19.522, style:width**

- a. *The standard defines the attribute style:width, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:width, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

On load, all values for the style:width attribute map to a default footnote separator width.

- c. *The standard defines the attribute `style:width`, contained within the element `<style:table-properties>`*

This attribute is supported in Word 2013 and later.

On load, if the width of the table is greater than can be supported by Word, the table will be automatically sized to fit the page.

- d. *The standard defines the attribute `style:width`, contained within the element `<style:column-sep>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `style:width`, contained within the element `<style:footnote-sep>`*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `style:width`, contained within the element `<style:table-properties>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.755 Part 3 Section 19.523, `svg:accent-height`**

- a. *The standard defines the attribute `svg:accent-height`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:accent-height`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.756 Part 3 Section 19.524, `svg:alphabetic`**

- a. *The standard defines the attribute `svg:alphabetic`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:alphabetic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.757 Part 3 Section 19.525, `svg:ascent`**

- a. *The standard defines the attribute `svg:ascent`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:ascent`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.758 Part 3 Section 19.526, `svg:bbox`**

- a. *The standard defines the attribute `svg:bbox`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:bbbox`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.759 Part 3 Section 19.527, `svg:cap-height`**

- a. *The standard defines the attribute `svg:cap-height`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:cap-height`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.760 Part 3 Section 19.531, `svg:descent`**

- a. *The standard defines the attribute `svg:descent`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:descent`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.761 Part 3 Section 19.532, `svg:font-family`**

- a. *The standard defines the attribute `svg:font-family`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

On load, Excel ignores the `<style:font-face>` element, all attributes of the `<style:font-face>` element, and all child elements. Excel reads the `<style:font-name>` attribute to determine the font to apply.

On save, Excel writes out the `<style:font-face element>`, along with values for the `<style:name>` and `<svg:font-family>` attributes.

### **2.1.762 Part 3 Section 19.533, `svg:font-size`**

- a. *The standard defines the attribute `svg:font-size`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:font-size`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.763 Part 3 Section 19.534, `svg:font-stretch`**

- a. *The standard defines the attribute `svg:font-stretch`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the property "condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the property "extra-condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- f. *The standard defines the property "extra-expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- g. *The standard defines the property "normal", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- h. *The standard defines the property "semi-condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- i. *The standard defines the property "semi-expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- j. *The standard defines the property "ultra-condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.

- k. *The standard defines the property "ultra-expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2013 or later.



### **2.1.764 Part 3 Section 19.535, svg:font-style**

- a. *The standard defines the attribute `svg:font-style`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:font-style`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.765 Part 3 Section 19.536, svg:font-variant**

- a. *The standard defines the attribute `svg:font-variant`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:font-variant`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.766 Part 3 Section 19.537, svg:font-weight**

- a. *The standard defines the attribute `svg:font-weight`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:font-weight`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.767 Part 3 Section 19.542, svg:hanging**

- a. *The standard defines the attribute `svg:hanging`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:hanging`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.768 Part 3 Section 19.543, svg:height**

- a. *The standard defines the attribute `svg:height`*

Word 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- b. *The standard defines the attribute `svg:height`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the attribute `svg:height`, contained within the element <office:annotation>*
- This attribute is not supported in Word 2013 or later.
- d. *The standard defines the attribute `svg:height`, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- e. *The standard defines the attribute `svg:height`*
- Excel 2013 supports this attribute for the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- f. *The standard defines the attribute `svg:height`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute `svg:height`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- h. *The standard defines the attribute `svg:height`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `svg:height`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- j. *The standard defines the attribute `svg:height`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute `svg:height`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

### **2.1.769 Part 3 Section 19.544, `svg:ideographic`**

- a. *The standard defines the attribute `svg:ideographic`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:ideographic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.770 Part 3 Section 19.545, `svg:mathematical`**

- a. *The standard defines the attribute `svg:mathematical`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:mathematical`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.771 Part 3 Section 19.546, `svg:name`**

- a. *The standard defines the attribute `svg:name`, contained within the element `<svg:font-face-name>`, contained within the parent element `<svg:font-face-src>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.772 Part 3 Section 19.549, `svg:overline-position`**

- a. *The standard defines the attribute `svg:overline-position`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:overline-position`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.773 Part 3 Section 19.550, `svg:overline-thickness`**

- a. *The standard defines the attribute `svg:overline-thickness`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:overline-thickness`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.774 Part 3 Section 19.551, svg:panose-1**

- a. *The standard defines the attribute `svg:panose-1`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.775 Part 3 Section 19.556, svg:slope**

- a. *The standard defines the attribute `svg:slope`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:slope`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.776 Part 3 Section 19.558, svg:stemh**

- a. *The standard defines the attribute `svg:stemh`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:stemh`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.777 Part 3 Section 19.559, svg:stemv**

- a. *The standard defines the attribute `svg:stemv`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:stemv`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.778 Part 3 Section 19.562, svg:strikethrough-position**

- a. *The standard defines the attribute `svg:strikethrough-position`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:strikethrough-position`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.779 Part 3 Section 19.563, svg:strikethrough-thickness**

- a. *The standard defines the attribute `svg:strikethrough-thickness`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:strikethrough-thickness`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.780 Part 3 Section 19.564, `svg:string`**

- a. *The standard defines the attribute `svg:string`, contained within the element `<svg:font-face-format>`, contained within the parent element `<svg:font-face-src>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.781 Part 3 Section 19.566, `svg:underline-position`**

- a. *The standard defines the attribute `svg:underline-position`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:underline-position`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.782 Part 3 Section 19.567, `svg:underline-thickness`**

- a. *The standard defines the attribute `svg:underline-thickness`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:underline-thickness`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.783 Part 3 Section 19.568, `svg:unicode-range`**

- a. *The standard defines the attribute `svg:unicode-range`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:unicode-range`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.784 Part 3 Section 19.569, `svg:units-per-em`**

- a. *The standard defines the attribute `svg:units-per-em`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:units-per-em`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.785 Part 3 Section 19.570, `svg:v-alphabetic`**

- a. *The standard defines the attribute `svg:v-alphabetic`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:v-alphabetic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.786 Part 3 Section 19.571, `svg:v-hanging`**

- a. *The standard defines the attribute `svg:v-hanging`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:v-hanging`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.787 Part 3 Section 19.572, `svg:v-ideographic`**

- a. *The standard defines the attribute `svg:v-ideographic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.788 Part 3 Section 19.573, `svg:v-mathematical`**

- a. *The standard defines the attribute `svg:v-mathematical`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `svg:v-mathematical`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.789 Part 3 Section 19.574, `svg:viewBox`**

- a. *The standard defines the attribute `svg:viewBox`*

Word 2013 supports this attribute for the following elements:

- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:path>`

- b. *The standard defines the attribute `svg:viewBox`*

Excel 2013 supports this attribute for the following elements:

- draw:polyline
  - draw:polygon
  - draw:path
- c. *The standard defines the attribute `svg:viewBox`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:polyline>
- <draw:polygon>
- <draw:path>

## **2.1.790 Part 3 Section 19.575, `svg:width`**

- a. *The standard defines the attribute `svg:width`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- b. *The standard defines the attribute `svg:width`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the attribute `svg:width`, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute `svg:width`, contained within the element <style:font-face>*

This attribute is not supported in Word 2013 or later.



- e. *The standard defines the attribute `svg:width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- f. *The standard defines the attribute `svg:width`*

Excel 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:custom-shape>`

- g. *The standard defines the attribute `svg:width`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- h. *The standard defines the attribute `svg:width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- i. *The standard defines the attribute `svg:width`*

PowerPoint 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- j. *The standard defines the attribute `svg:width`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:image>
  - <draw:text-box>
  - <draw:custom-shape>
- k. *The standard defines the attribute `svg:width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

### **2.1.791 Part 3 Section 19.576, `svg:widths`**

- a. *The standard defines the attribute `svg:widths`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.792 Part 3 Section 19.577, `svg:x`**

- a. *The standard defines the attribute `svg:x`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>

- <draw:custom-shape>
- b. *The standard defines the attribute `svg:x`, contained within the element `<office:annotation>`*  
This attribute is not supported in Word 2013 or later.
- c. *The standard defines the attribute `svg:x`, contained within the element `<style:graphic-properties>`*  
This attribute is not supported in Word 2013 or later.
- d. *The standard defines the attribute `svg:x`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame>
  - <draw:custom-shape>
- e. *The standard defines the attribute `svg:x`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

### **2.1.793 Part 3 Section 19.580, `svg:x-height`**

- a. *The standard defines the attribute `svg:x-height`, contained within the element `<style:font-face>`*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute `svg:x-height`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*  
This attribute is not supported in Excel 2013 or later.

## 2.1.794 Part 3 Section 19.581, *svg:y*

- a. *The standard defines the attribute *svg:y**

Word 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:custom-shape>`

- b. *The standard defines the attribute *svg:y*, contained within the element `<draw:g>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute *svg:y*, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute *svg:y*, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute *svg:y**

Excel 2013 supports this attribute for the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:custom-shape>`

- f. *The standard defines the attribute *svg:y*, contained within the element `<draw:g>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute *svg:y**

PowerPoint 2013 supports this attribute for the following elements:

- `<draw:rect>`

- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

h. *The standard defines the attribute `svg:y`, contained within the element `<draw:g>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.795 Part 3 Section 19.588, table:application-data**

a. *The standard defines the attribute `table:application-data`, contained within the element `<table:data-pilot-table>`, contained within the parent element `<table:data-pilot-tables>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.796 Part 3 Section 19.589, table:automatic-find-labels**

a. *The standard defines the attribute `table:automatic-find-labels`, contained within the element `<table:calculation-settings>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.797 Part 3 Section 19.590, table:base-cell-address**

a. *The standard defines the attribute `table:base-cell-address`, contained within the element `<table:named-expression>`, contained within the parent element `<table:named-expressions>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.798 Part 3 Section 19.591, table:bind-styles-to-content**

a. *The standard defines the attribute `table:bind-styles-to-content`, contained within the element `<table:sort>`*

This attribute is supported in Word 2013 and later.

b. *The standard defines the attribute `table:bind-styles-to-content`, contained within the element `<table:subtotal-rules>`*

This attribute is supported in Word 2013 and later.

c. *The standard defines the attribute `table:bind-styles-to-content`, contained within the element `<table:sort>`, contained within the parent element `<table:database-range>`*

This attribute is not supported in Excel 2013 or later.

d. *The standard defines the attribute `table:bind-styles-to-content`, contained within the element `<table:subtotal-rules>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.799 Part 3 Section 19.592, table: border-color**

- a. *The standard defines the attribute table: border-color, contained within the element <table: scenario>*

This attribute is not supported in Excel 2013 or later.

### **2.1.800 Part 3 Section 19.593, table: buttons**

- a. *The standard defines the attribute table: buttons, contained within the element <table: data-pilot-table>, contained within the parent element <table: data-pilot-tables>*

This attribute is supported in Excel 2013 and later.

The ODF specification does not specify DataPilot layout details.

On load, Excel uses button location information to help determine how to render the DataPilot, including page field locations, row and column headings, and data area.

On save, Excel writes button locations, based on how the DataPilot is positioned in Excel, so that other implementers can provide interactive buttons, if desired.

### **2.1.801 Part 3 Section 19.594, table: case-sensitive**

- a. *The standard defines the attribute table: case-sensitive, contained within the element <table: calculation-settings>*

This attribute is supported in Excel 2013 and later.

- b. *The standard defines the attribute table: case-sensitive, contained within the element <table: filter-condition>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute table: case-sensitive, contained within the element <table: subtotal-rules>*

This attribute is not supported in Excel 2013 or later.

### **2.1.802 Part 3 Section 19.597, table: cell-range-address**

- a. *The standard defines the attribute table: cell-range-address*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute table: cell-range-address, contained within the element <table: detective>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute table: cell-range-address, contained within the element <table: named-range>, contained within the parent element <table: named-expressions>*

This attribute is supported in Excel 2013 and later.

### **2.1.803 Part 3 Section 19.600, table:condition**

- a. *The standard defines the attribute table:condition, contained within the element <table:content-validation>*

This attribute is supported in Excel 2013 and later.

Excel does not support the function cell-content-is-text(), and data validation is lost in this case.

### **2.1.804 Part 3 Section 19.601, table:condition-source**

- a. *The standard defines the attribute table:condition-source, contained within the element <table:filter>*

This attribute is not supported in Excel 2013 or later.

Excel assumes the default filter, "condition-source: self".

### **2.1.805 Part 3 Section 19.602, table:condition-source-range-address**

- a. *The standard defines the attribute table:condition-source-range-address, contained within the element <table:filter>*

This attribute is not supported in Excel 2013 or later.

### **2.1.806 Part 3 Section 19.603, table:contains-error**

- a. *The standard defines the attribute table:contains-error, contained within the element <table:detective>*

This attribute is not supported in Excel 2013 or later.

### **2.1.807 Part 3 Section 19.605, table:content-validation-name**

- a. *The standard defines the attribute table:content-validation-name, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:content-validation-name, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute table:content-validation-name, contained within the element <table:table-cell>*

### **2.1.808 Part 3 Section 19.606, table:copy-back**

- a. *The standard defines the attribute table:copy-back, contained within the element <table:scenario>*

This attribute is not supported in Excel 2013 or later.

On load, Excel ignores this attribute. On save, Excel writes it out as false.

### **2.1.809 Part 3 Section 19.607, table:copy-formulas**

- a. *The standard defines the attribute table:copy-formulas, contained within the element <table:scenario>*

This attribute is not supported in Excel 2013 or later.

### **2.1.810 Part 3 Section 19.608, table:copy-styles**

- a. *The standard defines the attribute table:copy-styles, contained within the element <table:scenario>*

This attribute is not supported in Excel 2013 or later.

### **2.1.811 Part 3 Section 19.610, table:country**

- a. *The standard defines the attribute table:country, contained within the element <table:sort>, contained within the parent element <table:database-range>*

This attribute is not supported in Excel 2013 or later.

### **2.1.812 Part 3 Section 19.612, table:data-cell-range-address**

- a. *The standard defines the attribute table:data-cell-range-address, contained within the element <table:label-range>, contained within the parent element <table:label-ranges>*

This attribute is not supported in Excel 2013 or later.

### **2.1.813 Part 3 Section 19.613, table:database-name**

- a. *The standard defines the attribute table:database-name, contained within the element <table:database-source-query>, contained within the parent element <table:database-range>*

This attribute is supported in Excel 2013 and later.

Excel stores the connection string in the name attribute because it is the unique identifier.

- b. *The standard defines the attribute table:database-name, contained within the element <table:database-source-sql>, contained within the parent element <table:database-range>*

This attribute is supported in Excel 2013 and later.

Excel stores the connection string in the name attribute because it is the unique identifier.

- c. *The standard defines the attribute table:database-name, contained within the element <table:database-source-table>, contained within the parent element <table:database-range>*

This attribute is supported in Excel 2013 and later.

Excel stores the connection string in the name attribute because it is the unique identifier.

### **2.1.814 Part 3 Section 19.615, table:data-type**

- a. *The standard defines the attribute table:data-type, contained within the element <table:filter-condition>*

This attribute is supported in Excel 2013 and later.



Color, icon, and some dynamic filters are not saved.

- b. *The standard defines the attribute `table:data-type`, contained within the element `<table:sort-by>`, contained within the parent element `<table:sort>`*

This attribute is supported in Excel 2013 and later.

For custom list sorts, Excel writes out the entire custom list.

Excel does not save color and icon sorts.

Excel does not write out the text or numeric types. It loads both as automatic.

- c. *The standard defines the attribute `table:data-type`, contained within the element `<table:sort-groups>`, contained within the parent element `<table:subtotal-rules>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.815 Part 3 Section 19.618, `table:date-value`**

- a. *The standard defines the attribute `table:date-value`, contained within the element `<table:null-date>`, contained within the parent element `<table:calculation-settings>`*

This attribute is supported in Excel 2013 and later.

Excel supports the `table:date-value` attribute for only the values "1899-12-30" and "1904-01-01". Excel does not load the `table:date-value` attribute if it is set to other values.

### **2.1.816 Part 3 Section 19.619, `table:default-cell-style-name`**

- a. *The standard defines the attribute `table:default-cell-style-name`, contained within the element `<table:table-column>`*

This attribute is supported in Word 2013 and later.

On load, Word reads and respects this property. However, on save, Word writes out these properties as properties in the styles of individual cells.

- b. *The standard defines the attribute `table:default-cell-style-name`, contained within the element `<table:table-row>`*

This attribute is supported in Word 2013 and later.

On load, Word reads and respects this property. However, on save, Word writes out these properties as properties in the styles of individual cells.

- c. *The standard defines the attribute `table:default-cell-style-name`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `table:default-cell-style-name`, contained within the element `<table:table-column>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `table:default-cell-style-name`, contained within the element `<table:table-row>`*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-row>`*

**2.1.817 Part 3 Section 19.620, `table:direction`**

- a. *The standard defines the attribute `table:direction`, contained within the element `<table:detective>`*  
This attribute is not supported in Excel 2013 or later.

**2.1.818 Part 3 Section 19.621, `table:display`**

- a. *The standard defines the attribute `table:display`, contained within the element `<style:table-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `table:display`, contained within the element `<table:table-column-group>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `table:display`, contained within the element `<table:table-row-group>`*

This attribute is not supported in Excel 2013 or later.

**2.1.819 Part 3 Section 19.622, `table:display-border`**

- a. *The standard defines the attribute `table:display-border`, contained within the element `<table:scenario>`*

This attribute is not supported in Excel 2013 or later.

**2.1.820 Part 3 Section 19.623, `table:display-duplicates`**

- a. *The standard defines the attribute `table:display-duplicates`, contained within the element `<table:filter>`*

This attribute is not supported in Excel 2013 or later.

**2.1.821 Part 3 Section 19.625, `table:display-list`**

- a. *The standard defines the attribute `table:display-list`, contained within the element `<table:content-validation>`*

This attribute is supported in Excel 2013 and later.

If `table:display-list` is set to "sort-ascending", Excel loads and saves data as unsorted.

**2.1.822 Part 3 Section 19.629, `table:enabled`**

- a. *The standard defines the attribute `table:enabled`, contained within the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2013 and later.

On load, if the attribute `table:enabled` is "false", then Excel ignores the TopN filter information. If the attribute `table:enabled` is "true", then Excel loads and applies the TopN filter.

On save, Excel always writes "true", and only writes this when there's a TopN filter or AutoShow filter.

### **2.1.823 Part 3 Section 19.631, table:end-cell-address**

- a. *The standard defines the attribute table:end-cell-address, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the element <table:end-cell-address>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the attribute table:end-cell-address*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:end-cell-address, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

### **2.1.824 Part 3 Section 19.636, table:end-x**

- a. *The standard defines the attribute table:end-x, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the element <table:end-x>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the attribute table:end-x*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:end-x, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

### **2.1.825 Part 3 Section 19.637, table:end-y**

- a. *The standard defines the attribute table:end-y, contained within the element <office:annotation>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the element <table:end-y>*

This element is not supported in Word 2013 or later.

- c. *The standard defines the attribute table:end-y*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:end-y, contained within the element <office:annotation>*

This attribute is not supported in Excel 2013 or later.

### **2.1.826 Part 3 Section 19.641, table:field-number**

- a. *The standard defines the attribute table:field-number, contained within the element <table:sort-by>, contained within the parent element <table:sort>*

This attribute is supported in Excel 2013 and later.

On save, Excel writes out a zero-based field number.

- b. *The standard defines the attribute table:field-number, contained within the element <table:subtotal-field>*

This attribute is not supported in Excel 2013 or later.

### **2.1.827 Part 3 Section 19.642, table:filter-name**

- a. *The standard defines the attribute table:filter-name, contained within the element <table:cell-range-source>, contained within the parent element <table:table-cell>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute table:filter-name, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is not supported in Excel 2013 or later.

### **2.1.828 Part 3 Section 19.643, table:filter-options**

- a. *The standard defines the attribute table:filter-options, contained within the element <table:cell-range-source>, contained within the parent element <table:table-cell>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute table:filter-options, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is not supported in Excel 2013 or later.

### **2.1.829 Part 3 Section 19.646, table:formula**

- a. *The standard defines the attribute table:formula, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:formula, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute table:formula, contained within the element <table:covered-table-cell>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:formula, contained within the element <table:table-cell>*

This attribute is supported in Excel 2013 and later.

When saving the table:formula attribute, Excel precedes the formula string with the "of" namespace.

When saving the table:formula attribute, Excel saves a formula string that follows [\[ODF1.3\]](#) part 4.

When loading the attribute table:formula, Excel first looks at the namespace. If the namespace is 'of', 'msoxl' or not specified, Excel will attempt to load the value of table:formula as a formula in Excel.

Formulas using the 'of' namespace and those without a namespaces are expected to follow [\[ODF1.3\]](#) part 4.

Formulas using the 'msoxl' namespace follow [\[ISO/IEC29500-1:2016\]](#) section 18.17, except workbook-names are written as literal values instead of tokens given the lack of a relationship part.

When loading the table:formula attribute, if the namespace is unknown, the table:formula attribute is not loaded, and the value "office:value" is used instead. If the result of the formula is an error, Excel loads the <text:p> element and maps the element to an Error data type. Error data types that Excel does not support are mapped to #VALUE!

- e. *The standard defines the attribute table:formula, contained within the element <table:table-cell>*

### **2.1.830 Part 3 Section 19.647, table:function**

- a. *The standard defines the attribute table:function, contained within the element <table:consolidation>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the property "any string", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is not supported in Excel 2013 or later.

On load, string values that don't match the explicitly listed enumerated values are converted to "auto".

- c. *The standard defines the property "any string", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is not supported in Excel 2013 or later.

On load, string values that don't match the explicitly listed enumerated values are converted to "auto".

- d. *The standard defines the attribute table:function, contained within the element <table:subtotal-field>*

This attribute is not supported in Excel 2013 or later.

### **2.1.831 Part 3 Section 19.649, table:group-by-field-number**

- a. *The standard defines the attribute table:group-by-field-number, contained within the element <table:subtotal-rule>*

This attribute is not supported in Excel 2013 or later.

### **2.1.832 Part 3 Section 19.650, table:grouped-by**

- a. *The standard defines the property "days", contained within the attribute table:grouped-by, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2013 and later.

The RNG schema language specifies that the attributes table:end, table:step, and table:grouped-by are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the "DataPilot" items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the "DataPilot" items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

Excel supports grouping by days but does not explicitly write grouped-by="days". Instead, Excel only writes the step value and date-start / date-end; therefore "days" is implied.

### **2.1.833 Part 3 Section 19.653, table:identify-categories**

- a. *The standard defines the attribute table:identify-categories, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This attribute is not supported in Excel 2013 or later.

### **2.1.834 Part 3 Section 19.654, table:ignore-empty-rows**

- a. *The standard defines the attribute table:ignore-empty-rows, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This attribute is not supported in Excel 2013 or later.

### **2.1.835 Part 3 Section 19.655, table:index**

- a. *The standard defines the attribute table:index, contained within the element <table:operation>*

This attribute is not supported in Excel 2013 or later.

### **2.1.836 Part 3 Section 19.658, table:is-selection**

- a. *The standard defines the attribute table:is-selection, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is not supported in Excel 2013 or later.

### **2.1.837 Part 3 Section 19.659, table:is-sub-table**

- a. *The standard defines the attribute table:is-sub-table, contained within the element <table:table>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:is-sub-table, contained within the element <table:table>*

### **2.1.838 Part 3 Section 19.660, table:label-cell-range-address**

- a. *The standard defines the attribute table:label-cell-range-address, contained within the element <table:label-range>, contained within the parent element <table:label-ranges>*

This attribute is not supported in Excel 2013 or later.

### **2.1.839 Part 3 Section 19.661, table:language**

- a. *The standard defines the attribute table:language, contained within the element <table:sort>, contained within the parent element <table:database-range>*

This attribute is not supported in Excel 2013 or later.

### **2.1.840 Part 3 Section 19.667, table:link-to-source-data**

- a. *The standard defines the attribute table:link-to-source-data, contained within the element <table:consolidation>*

This attribute is not supported in Excel 2013 or later.

### **2.1.841 Part 3 Section 19.668, table:marked-invalid**

- a. *The standard defines the attribute table:marked-invalid, contained within the element <table:detective>*

This attribute is not supported in Excel 2013 or later.

### **2.1.842 Part 3 Section 19.675, table:mode**

- a. *The standard defines the property "copy-all", contained within the attribute table:mode, contained within the element <table:table-source>, contained within the parent element <table:table>*

This property is not supported in Excel 2013 or later.

On load, Excel reads the value of "copy-all" and maps it to copy-results-only. Excel does not write this property on save.

- b. *The standard defines the property "copy-results-only", contained within the attribute table:mode, contained within the element <table:table-source>, contained within the parent element <table:table>*

This property is supported in Excel 2013 and later.

On load, Excel always reads table:mode as "copy-results-only". On save, Excel always writes this attribute as "copy-results-only".

### **2.1.843 Part 3 Section 19.677, table:name**

- a. *The standard defines the attribute table:name, contained within the element <table:table>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:name, contained within the element <table:content-validation>*

This attribute is supported in Excel 2013 and later.

The table:name attribute is required, Excel doesn't load the validation if this attribute is missing.

- c. *The standard defines the attribute table:name, contained within the element <table:operation>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:name, contained within the element <table:source-service>, contained within the parent element <table:data-pilot-table>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute table:name, contained within the element <table:table>, contained within the parent element <office:spreadsheet>*

This attribute is supported in Excel 2013 and later.

Excel supports sheet names that are shorter than 32 characters.

- f. *The standard defines the attribute table:name, contained within the element <table:table>, contained within the parent element <table:dde-link>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.844 Part 3 Section 19.679, table:number-columns-repeated**

- a. *The standard defines the attribute table:number-columns-repeated, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:number-columns-repeated, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute table:number-columns-repeated, contained within the element <table:table-cell>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:number-columns-repeated, contained within the element <table:table-column>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.845 Part 3 Section 19.679.3, table:table-cell**

- a. *The standard defines the attribute table:number-columns-repeated, contained within the element <table:table-cell>*

#### **2.1.846 Part 3 Section 19.680, table:number-columns-spanned**

- a. *The standard defines the attribute table:number-columns-spanned*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute table:number-columns-spanned, contained within the element <table:covered-table-cell>*

This attribute is not supported in Excel 2013 or later.



- c. *The standard defines the attribute `table:number-columns-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.847 Part 3 Section 19.681, `table:number-rows-repeated`**

- a. *The standard defines the attribute `table:number-rows-repeated`, contained within the element `<table:table-row>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `table:number-rows-repeated`*

This attribute is supported in Excel 2013 and later.

On load, Excel reads this attribute, but does not write it on save.

- c. *The standard defines the attribute `table:number-rows-repeated`, contained within the element `<table:table-row>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `table:number-rows-repeated`, contained within the element `<table:table-row>`*

#### **2.1.848 Part 3 Section 19.682, `table:number-rows-spanned`**

- a. *The standard defines the attribute `table:number-rows-spanned`*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute `table:number-rows-spanned`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `table:number-rows-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.849 Part 3 Section 19.683, `table:number-matrix-columns-spanned`**

- a. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:table-cell>`*

### **2.1.850 Part 3 Section 19.684, `table:number-matrix-rows-spanned`**

- a. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.851 Part 3 Section 19.685, `table:object-name`**

- a. *The standard defines the attribute `table:object-name`, contained within the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.852 Part 3 Section 19.686, `table:on-update-keep-size`**

- a. *The standard defines the property "false", contained within the attribute `table:on-update-keep-size`, contained within the element `<table:database-range>`, contained within the parent element `<table:database-ranges>`*

This property is supported in Excel 2013 and later.

This value maps to "Insert/Delete" on refresh.

- b. *The standard defines the property "true", contained within the attribute `table:on-update-keep-size`, contained within the element `<table:database-range>`, contained within the parent element `<table:database-ranges>`*

This property is supported in Excel 2013 and later.

This value maps to "Overwrite/Clear" on refresh.

### **2.1.853 Part 3 Section 19.688, `table:operator`**

- a. *The standard defines the attribute `table:operator`, contained within the element `<table:filter-condition>`*

This attribute is supported in Excel 2013 and later.

Some operators are not supported for Pivot Table Filters, for example, "bottom values" and "top values".

#### **2.1.854 Part 3 Section 19.689, table:order**

- a. *The standard defines the attribute table:order, contained within the element <table:sort-groups>, contained within the parent element <table:subtotal-rules>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.855 Part 3 Section 19.690, table:orientation**

- a. *The standard defines the property "column", contained within the attribute table:orientation, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is not supported in Excel 2013 or later.

- b. *The standard defines the property "row", contained within the attribute table:orientation, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is supported in Excel 2013 and later.

The only orientation that Excel supports is row. Therefore, this is an optional attribute, and Excel neither reads nor writes it.

- c. *The standard defines the property "hidden", contained within the attribute table:orientation, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2013 and later.

On save, for a range-based data source, Excel does not write fields that are not displayed on the "DataPilot". For external data sources, Excel writes out all fields, and marks those not in the "DataPilot" view as hidden.

- d. *The standard defines the attribute table:orientation, contained within the element <table:label-range>, contained within the parent element <table:label-ranges>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.856 Part 3 Section 19.691, table:page-breaks-on-group-change**

- a. *The standard defines the attribute table:page-breaks-on-group-change, contained within the element <table:subtotal-rules>*

This attribute is not supported in Excel 2013 or later.

#### **2.1.857 Part 3 Section 19.693, table:parse-sql-statement**

- a. *The standard defines the attribute table:parse-sql-statement, contained within the element <table:database-source-sql>, contained within the parent element <table:database-range>*

This attribute is not supported in Excel 2013 or later.

### **2.1.858 Part 3 Section 19.694, table:password**

- a. *The standard defines the attribute table:password, contained within the element <table:source-service>, contained within the parent element <table:data-pilot-table>*

This attribute is not supported in Excel 2013 or later.

### **2.1.859 Part 3 Section 19.697, table:print**

- a. *The standard defines the attribute table:print, contained within the element <table:table>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:print*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute table:print, contained within the element <table:table>, contained within the parent element <office:spreadsheet>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:print, contained within the element <table:table>, contained within the parent element <table:dde-link>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute table:print, contained within the element <table:table>*

### **2.1.860 Part 3 Section 19.698, table:print-ranges**

- a. *The standard defines the attribute table:print-ranges, contained within the element <table:table>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:print-ranges*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute table:print-ranges, contained within the element <table:table>, contained within the parent element <table:dde-link>*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute table:print-ranges, contained within the element <table:table>*

### **2.1.861 Part 3 Section 19.699, table:protect**

- a. *The standard defines the attribute table:protect*

This attribute is not supported in Excel 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

- b. *The standard defines the attribute table:protect, contained within the element <table:table-cell>*

*This attribute was deprecated in the ODF 1.2 standard.*

### **2.1.862 Part 3 Section 19.700, table:protected**

- a. *The standard defines the attribute table:protected, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:protected, contained within the element <table:table>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute table:protected, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute table:protected*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute table:protected, contained within the element <table:table>, contained within the parent element <table:dde-link>*

This attribute is not supported in Excel 2013 or later.

### **2.1.863 Part 3 Section 19.700.4, table:table**

- a. *The standard defines the attribute table:protected, contained within the element <table:table>*

### **2.1.864 Part 3 Section 19.700.5, table:table-cell**

- a. *The standard defines the attribute table:protected, contained within the element <table:table-cell>*

### **2.1.865 Part 3 Section 19.701, table:protection-key**

- a. *The standard defines the attribute table:protection-key, contained within the element <table:table>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:protection-key*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute table:protection-key, contained within the element <office:spreadsheet>*

This attribute is not supported in Excel 2013 or later.

Excel does not load a workbook if a protection-key is specified.

- d. *The standard defines the attribute table:protection-key, contained within the element <table:table>*

### **2.1.866 Part 3 Section 19.702, table:protection-key-digest-algorithm**

- a. *The standard defines the attribute table:protection-key-digest-algorithm, contained within the element <table:table>*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the attribute `table:protection-key-digest-algorithm`, contained within the element `<table:table>`*

### **2.1.867 Part 3 Section 19.704, `table:range-usable-as`**

- a. *The standard defines the property "filter", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2013 or later.

- b. *The standard defines the property "none", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2013 or later.

- c. *The standard defines the property "print-range", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "repeat-column", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the property "repeat-row", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2013 or later.

### **2.1.868 Part 3 Section 19.705, `table:refresh-delay`**

- a. *The standard defines the attribute `table:refresh-delay`, contained within the element `<table:database-range>`, contained within the parent element `<table:database-ranges>`*

This attribute is supported in Excel 2013 and later.

The attribute `table:refresh-delay` is a boolean type, while the corresponding setting in Excel is an interval of time.

- b. *The standard defines the property "false", contained within the attribute `table:refresh-delay`, contained within the element `<table:database-range>`, contained within the parent element `<table:database-ranges>`*

This property is supported in Excel 2013 and later.

This value maps to the feature being off.

- c. *The standard defines the property "true", contained within the attribute `table:refresh-delay`, contained within the element `<table:database-range>`, contained within the parent element `<table:database-ranges>`*

This property is supported in Excel 2013 and later.

On load, this value maps to the default interval. On save, if the interval is nonzero, Excel writes 'true'.

- d. *The standard defines the attribute `table:refresh-delay`, contained within the element `<table:table-source>`, contained within the parent element `<table:table>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.869 Part 3 Section 19.712, `table:selected-page`**

- a. *The standard defines the attribute `table:selected-page`, contained within the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is supported in Excel 2013 and later.

On save, if Excel writes an empty value for this attribute, it means that 'blank' is chosen for the filter value. This corresponds to an empty string in the data source. If Excel doesn't write this attribute at all, it means the user has not selected a value for the manual filter.

### **2.1.870 Part 3 Section 19.715, `table:show-filter-button`**

- a. *The standard defines the attribute `table:show-filter-button`, contained within the element `<table:data-pilot-table>`, contained within the parent element `<table:data-pilot-tables>`*

This attribute is not supported in Excel 2013 or later.

On load, Excel uses the value of the attribute `table:show-filter-button` to help determine the layout of the DataPilot.

Excel does not support toggling the DataPilot buttons "on" and "off".

On save, Excel always writes the attribute `table:show-filter-button` as "false".

### **2.1.871 Part 3 Section 19.717, `table:source-cell-range-addresses`**

- a. *The standard defines the attribute `table:source-cell-range-addresses`, contained within the element `<table:consolidation>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.872 Part 3 Section 19.719, `table:source-name`**

- a. *The standard defines the attribute `table:source-name`, contained within the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.873 Part 3 Section 19.730, `table:style-name`**

- a. *The standard defines the attribute `table:style-name`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `table:style-name`, contained within the element `<table:table>`*

This attribute is supported in Word 2013 and later.

Word does not support the use of common styles from the table family, that is using a table style defined under the <office:styles> element.

- c. *The standard defines the attribute table:style-name, contained within the element <table:table-cell>*

This attribute is supported in Word 2013 and later.

Word does not support the use of common styles from the table-cell family, that is using a table style defined under the <office:styles> element.

- d. *The standard defines the attribute table:style-name, contained within the element <table:table-column>*

This attribute is supported in Word 2013 and later.

Word does not support the use of common styles from the table-column family, that is using a table style defined under the <office:styles> element. Word requires a valid table:style-name attribute for a table:table-column element.

- e. *The standard defines the attribute table:style-name, contained within the element <table:table-row>*

This attribute is supported in Word 2013 and later.

Word does not support the use of common styles from the table-row family, that is using a table style defined under the <office:styles> element.

- f. *The standard defines the attribute table:style-name*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute table:style-name, contained within the element <table:covered-table-cell>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute table:style-name, contained within the element <table:table>, contained within the parent element <table:dde-link>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute table:style-name, contained within the element <table:table-cell>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute table:style-name, contained within the element <table:table-column>*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute table:style-name, contained within the element <table:table-row>*

This attribute is not supported in Excel 2013 or later.

## **2.1.874 Part 3 Section 19.733, table:table-background**

- a. *The standard defines the element <table:table-background>*



This element is not supported in Word 2013 or later.

- b. *The standard defines the attribute `table:table-background`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.875 Part 3 Section 19.735, `table:target-cell-address`**

- a. *The standard defines the attribute `table:target-cell-address`, contained within the element `<table:consolidation>`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.876 Part 3 Section 19.737, `table:template-name`**

- a. *The standard defines the attribute `table:template-name`, contained within the element `<table:table>`*

This attribute is supported in Word 2013 and later.

#### **2.1.877 Part 3 Section 19.741, `table:use-banding-columns-styles`**

- a. *The standard defines the attribute `table:use-banding-columns-styles`, contained within the element `<table:table>`*

This attribute is supported in Word 2013 and later.

#### **2.1.878 Part 3 Section 19.742, `table:use-banding-rows-styles`**

- a. *The standard defines the attribute `table:use-banding-rows-styles`, contained within the element `<table:table>`*

This attribute is supported in Word 2013 and later.

#### **2.1.879 Part 3 Section 19.743, `table:use-first-column-styles`**

- a. *The standard defines the attribute `table:use-first-column-styles`, contained within the element `<table:table>`*

This attribute is supported in Word 2013 and later.

#### **2.1.880 Part 3 Section 19.744, `table:use-first-row-styles`**

- a. *The standard defines the attribute `table:use-first-row-styles`, contained within the element `<table:table>`*

This attribute is supported in Word 2013 and later.

#### **2.1.881 Part 3 Section 19.745, `table:use-last-column-styles`**

- a. *The standard defines the attribute `table:use-last-column-styles`, contained within the element `<table:table>`*

This attribute is supported in Word 2013 and later.

### **2.1.882 Part 3 Section 19.746, table:use-last-row-styles**

- a. *The standard defines the attribute table:use-last-row-styles, contained within the element <table:table>*

This attribute is supported in Word 2013 and later.

### **2.1.883 Part 3 Section 19.747, table:use-labels**

- a. *The standard defines the attribute table:use-labels, contained within the element <table:consolidation>*

This attribute is not supported in Excel 2013 or later.

### **2.1.884 Part 3 Section 19.748, table:use-regular-expressions**

- a. *The standard defines the attribute table:use-regular-expressions, contained within the element <table:calculation-settings>*

This attribute is not supported in Excel 2013 or later.

### **2.1.885 Part 3 Section 19.750, table:used-hierarchy**

- a. *The standard defines the attribute table:used-hierarchy, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This attribute is not supported in Excel 2013 or later.

### **2.1.886 Part 3 Section 19.751, table:user-name**

- a. *The standard defines the attribute table:user-name, contained within the element <table:source-service>, contained within the parent element <table:data-pilot-table>*

This attribute is not supported in Excel 2013 or later.

### **2.1.887 Part 3 Section 19.752, table:value**

- a. *The standard defines the attribute table:value, contained within the element <table:filter-condition>*

This attribute is supported in Excel 2013 and later.

However, some regular expressions are not supported. Also, some values are not supported for AF, such as filtering with "Date = 36527" instead of "1/2/2000". The attribute table:value is supported in Calc 3. However, only "." and ".\*" are supported for Regular Expressions, all other expressions are dropped. On save, non-wildcard filters, such as "Contains", are transformed into corresponding regular expressions.

### **2.1.888 Part 3 Section 19.753, table:value-type**

- a. *The standard defines the attribute table:value-type, contained within the element <table:covered-table-cell>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute table:value-type, contained within the element <table:table-cell>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `table:value-type`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `table:value-type`, contained within the element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.889 Part 3 Section 19.754, `table:visibility`**

- a. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-column>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-row>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `table:visibility`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-column>`*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-row>`*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-row>`*

### **2.1.890 Part 3 Section 19.755, `text:active`**

- a. *The standard defines the attribute `text:active`, contained within the element `<table:page-variable-set>`*

This attribute is supported in Word 2013 and later.

### **2.1.891 Part 3 Section 19.758, `text:anchor-page-number`**

- a. *The standard defines the attribute `text:anchor-page-number`*

This attribute is not supported in Word 2013 or later.

On load, objects that are anchored to a specific page number using the `text:anchor-page-number` attribute will appear on the first page.

- b. *The standard defines the attribute `text:anchor-page-number`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `text:anchor-page-number`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `text:anchor-page-number`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2013 or later.

## **2.1.892 Part 3 Section 19.759, `text:anchor-type`**

- a. *The standard defines the property "as-char", contained within the attribute `text:anchor-type`*

This property is supported in Word 2013 and later.

On load and save, Word supports this value for the `text:anchor-type` attribute when a shape is inserted inline with text.

- b. *The standard defines the property "char", contained within the attribute `text:anchor-type`*

This property is not supported in Word 2013 or later.

On load, Word reverts to a default value of "paragraph" for all unsupported values of the `text:anchor-type` attribute.

- c. *The standard defines the property "frame", contained within the attribute `text:anchor-type`*

This property is not supported in Word 2013 or later.

On load, Word reverts to a default value of "paragraph" for all unsupported values of the `text:anchor-type` attribute.

- d. *The standard defines the property "page", contained within the attribute `text:anchor-type`*

This property is not supported in Word 2013 or later.

On load, Word reverts to a default value of "paragraph" for all unsupported values of the `text:anchor-type` attribute.

- e. *The standard defines the attribute `text:anchor-type`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the property "as-char", contained within the attribute `text:anchor-type`*

This property is not supported in Excel 2013 or later.

- g. *The standard defines the property "chart", contained within the attribute `text:anchor-type`*

This property is not supported in Excel 2013 or later.

- h. *The standard defines the property "frame", contained within the attribute `text:anchor-type`*

This property is not supported in Excel 2013 or later.

- i. *The standard defines the property "page", contained within the attribute `text:anchor-type`*

This property is not supported in Excel 2013 or later.

- j. *The standard defines the property "paragraph", contained within the attribute `text:anchor-type`*

This property is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `text:anchor-type`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.893 Part 3 Section 19.765, `text:bullet-char`**

- a. *The standard defines the attribute `text:bullet-char`, contained within the element `<text:list-level-style-bullet>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- b. *The standard defines the attribute `text:bullet-char`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- c. *The standard defines the attribute `text:bullet-char`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.894 Part 3 Section 19.766, `text:bullet-relative-size`**

- a. *The standard defines the attribute `text:bullet-relative-size`, contained within the element `<text:list-level-style-bullet>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt.

- b. *The standard defines the attribute `text:bullet-relative-size`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- c. *The standard defines the attribute `text:bullet-relative-size`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.895 Part 3 Section 19.767, `text:capitalize-entries`**

- a. *The standard defines the attribute `text:capitalize-entries`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2013 or later.

### **2.1.896 Part 3 Section 19.768, `text:c`**

- a. *The standard defines the attribute `text:c`, contained within the element `<text:s>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `text:c`, contained within the element `<text:s>`*

This attribute is supported in Excel 2013 and later.

On load, Excel reads this attribute. On save, Excel does not write this attribute.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute text:c, contained within the element <text:s>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.897 Part 3 Section 19.775, text:class-names**

- a. *The standard defines the attribute text:class-names, contained within the element <text:p>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The text:class-names attribute is always written as empty.

- b. *The standard defines the attribute text:class-names, contained within the element <text:span>*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. The text:class-name attribute is always written as empty.

- c. *The standard defines the attribute text:class-names, contained within the element <text:p>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save, for text in text boxes, shapes, SmartArt, chart titles and labels. On load, it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The text: class-names attribute is always written as empty and is not supported on read.

- d. *The standard defines the attribute text: class-names, contained within the element <text:span>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute text: class-names, contained within the element <text:span>, contained within the parent element <text:p>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute text: class-names, contained within the element <text:p>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text: class-names" attribute is always written and empty, and is not supported on read.

- g. *The standard defines the attribute text: class-names, contained within the element <text:span>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>



- <draw:custom-shape>

The "text:class-name" attribute is always written and empty, and is not supported on read.

### **2.1.898 Part 3 Section 19.777, text:combine-entries**

- a. *The standard defines the attribute text:combine-entries, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

### **2.1.899 Part 3 Section 19.778, text:combine-entries-with-dash**

- a. *The standard defines the attribute text:combine-entries-with-dash, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

### **2.1.900 Part 3 Section 19.779, text:combine-entries-with-pp**

- a. *The standard defines the attribute text:combine-entries-with-pp, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

### **2.1.901 Part 3 Section 19.780, text:comma-separated**

- a. *The standard defines the attribute text:comma-separated, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

### **2.1.902 Part 3 Section 19.781, text:cond-style-name**

- a. *The standard defines the attribute text:cond-style-name, contained within the element <text:p>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The text:cond-style-name attribute is always written as empty.

- b. *The standard defines the attribute text:cond-style-name, contained within the element <text:p>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save, for text in text boxes, shapes, SmartArt, and chart titles and labels. On load, it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>

- <draw:text-box>
- <draw:custom-shape>

The text:cond-style-name attribute is always written as empty and is not supported on read.

- c. *The standard defines the attribute text:cond-style-name, contained within the element <text:p>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text:cond-style-name" attribute is always written as empty and is not supported on read.

### **2.1.903 Part 3 Section 19.782, text:condition**

- a. *The standard defines the attribute text:condition, contained within the element <text:section>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:condition, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

### **2.1.904 Part 3 Section 19.784, text:consecutive-numbering**

- a. *The standard defines the attribute text:consecutive-numbering, contained within the element <text:list-style>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:consecutive-numbering, contained within the element <text:list-style>*

**OfficeArt Math** h in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- c. *The standard defines the attribute text:consecutive-numbering, contained within the element <text:list-style>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.905 Part 3 Section 19.785, text:continue-list**

- a. *The standard defines the attribute text:continue-list, contained within the element <text:list>*

This attribute is supported in Word 2013 and later.

On load, the behavior dictated by text:continue-list overrides the behavior dictated by text:continue-numbering

### **2.1.906 Part 3 Section 19.786, text:continue-numbering**

- a. *The standard defines the attribute text:continue-numbering, contained within the element <text:list>*

**OfficeArt Math** in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

- b. *The standard defines the attribute text:continue-numbering, contained within the element <text:list>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.907 Part 3 Section 19.788, text:count-empty-lines**

- a. *The standard defines the attribute text:count-empty-lines, contained within the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This attribute is not supported in Word 2013 or later.

### **2.1.908 Part 3 Section 19.789, text:count-in-text-boxes**

- a. *The standard defines the attribute text:count-in-text-boxes, contained within the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This attribute is not supported in Word 2013 or later.

### **2.1.909 Part 3 Section 19.790, text:current-selected**

- a. *The standard defines the attribute text:current-selected, contained within the element <text:label>*

This attribute is supported in Word 2021 and later.

### **2.1.910 Part 3 Section 19.798, text:date-adjust**

- a. *The standard defines the attribute text:date-adjust, contained within the element <text:date>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:date-adjust*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute text:date-adjust, contained within the element <text:date>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.911 Part 3 Section 19.799, text:date-value**

- a. *The standard defines the attribute text:date-value, contained within the element <text:date>*

This attribute is not supported in Word 2013 or later.

On load, if the date field is not fixed, Word displays the current date. On save, Word writes out the current date as the text between the <text:date> element tags. The field is retained within the document.

- b. *The standard defines the attribute text:date-value*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute text:date-value, contained within the element <text:date>*

This attribute is not supported in PowerPoint 2013 or later.

Date values are specified as text content between the start and end <text:date> element tags.

### **2.1.912 Part 3 Section 19.800, text:default-style-name**

- a. *The standard defines the attribute text:default-style-name, contained within the element <text:notes-configuration>*

This attribute is not supported in Word 2013 or later.

### **2.1.913 Part 3 Section 19.802, text:display**

- a. *The standard defines the property "name", contained within the attribute text:display, contained within the element <text:file-name>*

This property is supported in Word 2013 and later.

On load, Word converts this value for the text:display attribute to "name-and-extension".

- b. *The standard defines the property "path", contained within the attribute text:display, contained within the element <text:file-name>*

This property is not supported in Word 2013 or later.

On load, Word converts this value for the text:display attribute to "full".

- c. *The standard defines the attribute text:display, contained within the element <text:index-entry-chapter>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute text:display, contained within the element <text:section>*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the property "area", contained within the attribute text:display, contained within the element <text:template-name>*

This property is not supported in Word 2013 or later.

- f. *The standard defines the property "name", contained within the attribute text:display, contained within the element <text:template-name>*

This property is supported in Word 2013 and later.

On load, Word converts this value for the text:display attribute to "name-and-extension".

- g. *The standard defines the property "path", contained within the attribute text:display, contained within the element <text:template-name>*

This property is not supported in Word 2013 or later.

- h. *The standard defines the property "title", contained within the attribute text:display, contained within the element <text:template-name>*

This property is not supported in Word 2013 or later.

- i. *The standard defines the attribute text:display, contained within the element <text:file-name>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads in the "name" value and maps it to "name-and-extension". On save, Excel ignores "name" and writes out "name-and-extension".

- j. *The standard defines the attribute text:display, contained within the element <text:chapter>, <text:expression>, <text:index-entry-chapter>, <text:section>, <text:table-formula>, <text:template-name>, <text:user-field-get>, <text:variable-get>, <text:variable-input> or <text:variable-set>*

This attribute is not supported in Excel 2013 or later

- j. *The standard defines the attribute text:display*

This attribute is not supported in PowerPoint 2013 or later.

## **2.1.914 Part 3 Section 19.803, text:display-levels**

- a. *The standard defines the attribute text:display-levels, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute text:display-levels, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `text:display-levels`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes.

- d. *The standard defines the attribute `text:display-levels`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- e. *The standard defines the attribute `text:display-levels`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

## **2.1.915 Part 3 Section 19.809, text:fixed**

- a. *The standard defines the attribute text:fixed, contained within the element <text:creation-date>*  
This attribute is not supported in Word 2013 or later.  
On save, if the field is fixed, Word replaces the <text:creation-date> field with its resulting output text.
- b. *The standard defines the attribute text:fixed, contained within the element <text:creation-time>*  
This attribute is not supported in Word 2013 or later.  
On save, if the field is fixed, Word replaces the <text:creation-time> field with its resulting output text.
- c. *The standard defines the attribute text:fixed, contained within the element <text:date>*  
This attribute is not supported in Word 2013 or later.
- d. *The standard defines the attribute text:fixed, contained within the element <text:modification-date>*  
This attribute is not supported in Word 2013 or later.  
On save, if the field is fixed, Word replaces the <text:modification-date> field with its resulting output text.
- e. *The standard defines the attribute text:fixed, contained within the element <text:modification-time>*  
This attribute is not supported in Word 2013 or later.  
On save, if the field is fixed, Word replaces the <text:modification-time> field with its resulting output text.
- f. *The standard defines the attribute text:fixed, contained within the element <text:print-date>*  
This attribute is not supported in Word 2013 or later.  
On save, if the field is fixed, Word replaces the <text:print-date> field with its resulting output text.
- g. *The standard defines the attribute text:fixed, contained within the element <text:print-time>*  
This attribute is not supported in Word 2013 or later.  
On save, if the field is fixed, Word replaces the <text:print-time> field with its resulting output text.
- h. *The standard defines the attribute text:fixed, contained within the element <text:time>*  
This attribute is not supported in Word 2013 or later.
- i. *The standard defines the attribute text:fixed*  
This attribute is not supported in Excel 2013 or later.
- j. *The standard defines the attribute text:fixed, contained within the element <text:date>*  
This attribute is supported in PowerPoint 2013 and later.



For fixed dates, this attribute is not used. For non-fixed dates this attribute is written out with the value "false".

- k. *The standard defines the attribute text:fixed, contained within the element <text:time>*

This attribute is supported in PowerPoint 2013 and later.

For fixed time values, this attribute is not used. For non-fixed time values, this attribute is written out with the value "false".

### **2.1.916 Part 3 Section 19.811, text:formula**

- a. *The standard defines the attribute text:formula*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:formula*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.917 Part 3 Section 19.812, text:global**

- a. *The standard defines the attribute text:global, contained within the element <office:text>*

This attribute is not supported in Word 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

### **2.1.918 Part 3 Section 19.814, text:increment**

- a. *The standard defines the attribute text:increment, contained within the element <text:linenumbing-separator>, contained within the parent element <text:linenumbing-configuration>*

This attribute is not supported in Word 2013 or later.

### **2.1.919 Part 3 Section 19.815, text:id**

- a. *The standard defines the attribute text:id, contained within the element <draw:text-box>*

This attribute is not supported in Word 2013 or later.

*This attribute was deprecated in the ODF 1.3 standard.*

- b. *The standard defines the attribute text:id, contained within the element <text:alphabetical-index-mark-start>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute text:id, contained within the element <text:toc-mark-start>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute text:id, contained within the element <text:p>*

This attribute is not supported in Excel 2013 or later.

*This attribute was deprecated in the ODF 1.3 standard.*

### **2.1.920 Part 3 Section 19.818, text:index-scope**

- a. *The standard defines the attribute text:index-scope, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

On load, Word reverts to a default of "document" for all values of the text:index-scope attribute.

- b. *The standard defines the attribute text:index-scope, contained within the element <text:table-of-content-source>*

This attribute is not supported in Word 2013 or later.

On load, Word reverts to a default of "document" for all values of the text:index-scope attribute.

### **2.1.921 Part 3 Section 19.819, text:ignore-case**

- a. *The standard defines the attribute text:ignore-case, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

### **2.1.922 Part 3 Section 19.822, text:is-list-header**

- a. *The standard defines the attribute text:is-list-header, contained within the element <text:h>*

This attribute is not supported in Word 2013 or later.

### **2.1.923 Part 3 Section 19.827, text:key1**

- a. *The standard defines the attribute text:key1, contained within the element <text:alphabetical-index-mark-start>*

This attribute is not supported in Word 2013 or later.

### **2.1.924 Part 3 Section 19.828, text:key2**

- a. *The standard defines the attribute text:key2, contained within the element <text:alphabetical-index-mark-start>*

This attribute is not supported in Word 2013 or later.

### **2.1.925 Part 3 Section 19.829, text:key1-phonetic**

- a. *The standard defines the attribute text:key1-phonetic, contained within the element <text:alphabetical-index-mark>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:key1-phonetic, contained within the element <text:alphabetical-index-mark-start>*

This attribute is not supported in Word 2013 or later.

## 2.1.926 Part 3 Section 19.830, text:key2-phonetic

- a. *The standard defines the attribute text:key2-phonetic, contained within the element <text:alphabetical-index-mark>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:key2-phonetic, contained within the element <text:alphabetical-index-mark-start>*

This attribute is not supported in Word 2013 or later.

## 2.1.927 Part 3 Section 19.834, text:level

- a. *The standard defines the attribute text:level*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- b. *The standard defines the attribute text:level, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- c. *The standard defines the attribute text:level*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes, shapes, and SmartArt.

- d. *The standard defines the attribute text:level, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes and for SmartArt Graphics.

- e. *The standard defines the attribute `text:level`, contained within the element `<text:list-level-style-image>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes.

- f. *The standard defines the attribute `text:level`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes.

- g. *The standard defines the attribute `text:level`, contained within the element `<text:numbered-paragraph>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `text:level`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`

- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

i. *The standard defines the attribute text:level, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

j. *The standard defines the attribute text:level, contained within the element <text:list-level-style-image>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

k. *The standard defines the attribute text:level, contained within the element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
  - <draw:custom-shape>.
- l. *The standard defines the attribute text:level, contained within the element <text:numbered-paragraph>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.928 Part 3 Section 19.837, text:main-entry**

- a. *The standard defines the attribute text:main-entry, contained within the element <text:alphabetical-index-mark>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:main-entry, contained within the element <text:alphabetical-index-mark-start>*

This attribute is not supported in Word 2013 or later.

### **2.1.929 Part 3 Section 19.838, text:main-entry-style-name**

- a. *The standard defines the attribute text:main-entry-style-name, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

### **2.1.930 Part 3 Section 19.839, text:master-page-name**

- a. *The standard defines the attribute text:master-page-name, contained within the element <text:notes-configuration>*

This attribute is not supported in Word 2013 or later.

### **2.1.931 Part 3 Section 19.841, text:name**

- a. *The standard defines the attribute text:name, contained within the element <text:section>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:name, contained within the element <text:drop-down>*

This attribute is supported in Word 2021 or later.

- c. *The standard defines the attribute text:name*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.932 Part 3 Section 19.843, text:note-class**

- a. *The standard defines the attribute text:note-class, contained within the element <text:note-ref>*

This attribute is not supported in Word 2013 or later.

On load, Word ignores footnote references. On save, Word writes out footnote references.

### 2.1.933 Part 3 Section 19.845, text:number-lines

- a. *The standard defines the attribute text:number-lines, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute text:number-lines, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute text:number-lines, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.934 Part 3 Section 19.846, text:number-position

- a. *The standard defines the attribute text:number-position, contained within the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This attribute is not supported in Word 2013 or later.

### 2.1.935 Part 3 Section 19.850, text:outline-level

- a. *The standard defines the attribute text:outline-level, contained within the element <text:h>*

This attribute is supported in Word 2013 and later.

On save, if the numbering applied to a set of headings (via outline level) is not continuous, Word outputs the missing numbers as numbered blank paragraphs--- for example:

first item

second item

third item

is output as follows:

first item

second item

3.

third item

### **2.1.936 Part 3 Section 19.850.5, text:index-entry-chapter**

- a. *The standard defines the attribute text:outline-level, contained within the element <text:index-entry-chapter>*

This attribute is supported in Word 2013 and later.

### **2.1.937 Part 3 Section 19.851, text:page-adjust**

- a. *The standard defines the attribute text:page-adjust, contained within the element <text:page-number>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:page-adjust*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute text:page-adjust, contained within the element <text:page-number>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.938 Part 3 Section 19.855, text:protected**

- a. *The standard defines the attribute text:protected, contained within the element <text:section>*

This attribute is not supported in Word 2013 or later.

### **2.1.939 Part 3 Section 19.856, text:protection-key**

- a. *The standard defines the attribute text:protection-key, contained within the element <text:section>*

This attribute is not supported in Word 2013 or later.



### **2.1.940 Part 3 Section 19.857, text:protection-key-digest-algorithm**

- a. *The standard defines the attribute text:protection-key-digest-algorithm, contained within the element <text:alphabetical-index>*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the attribute text:protection-key-digest-algorithm, contained within the element <text:bibliography>*

This attribute is supported in Word 2013 and later.

- c. *The standard defines the attribute text:protection-key-digest-algorithm, contained within the element <text:section>*

This attribute is supported in Word 2013 and later.

- d. *The standard defines the attribute text:protection-key-digest-algorithm, contained within the element <text:table-of-content>*

This attribute is supported in Word 2013 and later.

### **2.1.941 Part 3 Section 19.859, text:ref-name**

- a. *The standard defines the attribute text:ref-name, contained within the element <text:note-ref>*

This attribute is not supported in Word 2013 or later.

On load, Word ignores footnote references. On save, Word writes out footnote references.

### **2.1.942 Part 3 Section 19.860, text:reference-format**

- a. *The standard defines the property "chapter", contained within the attribute text:reference-format, contained within the element <text:bookmark-ref>*

This property is not supported in Word 2013 or later.

- b. *The standard defines the property "chapter", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2013 or later.

- c. *The standard defines the property "direction", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2013 or later.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- d. *The standard defines the property "page", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2013 or later.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- e. *The standard defines the property "text", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2013 or later.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- f. *The standard defines the property "chapter", contained within the attribute `text:reference-format`, contained within the element `<text:reference-ref>`*

This property is not supported in Word 2013 or later.

#### **2.1.943 Part 3 Section 19.861, `text:relative-tab-stop-position`**

- a. *The standard defines the attribute `text:relative-tab-stop-position`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `text:relative-tab-stop-position`, contained within the element `<text:table-of-content-source>`*

This attribute is not supported in Word 2013 or later.

#### **2.1.944 Part 3 Section 19.863, `text:restart-numbering`**

- a. *The standard defines the attribute `text:restart-numbering`, contained within the element `<text:h>`*

This attribute is not supported in Word 2013 or later.

#### **2.1.945 Part 3 Section 19.869, `text:select-page`**

- a. *The standard defines the attribute `text:select-page`, contained within the element `<text:page-number>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `text:select-page`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `text:select-page`, contained within the element `<text:page-number>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.946 Part 3 Section 19.871, `text:sort-algorithm`**

- a. *The standard defines the attribute `text:sort-algorithm`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2013 or later.

#### **2.1.947 Part 3 Section 19.874, `text:start-value`**

- a. *The standard defines the attribute `text:start-value`, contained within the element `<text:list-item>`, contained within the parent element `<text:list>`*

**OfficeArt Math** in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

- b. *The standard defines the attribute `text:start-value`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- c. *The standard defines the attribute `text:start-value`, contained within the element `<text:list-item>`, contained within the parent element `<text:list>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- d. *The standard defines the attribute `text:start-value`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.948 Part 3 Section 19.880, text:style-name

- a. *The standard defines the attribute text:style-name, contained within the element <text:a>*

This attribute is not supported in Word 2013 or later.

On load, Word applies text properties to hyperlinks via properties defined by the <text:span> element containing the displayed hyperlink text.

- b. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-chapter>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-link-end>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-link-start>*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-page-number>*

This attribute is supported in Word 2013 and later.

On load, Word ignores this element and reverts to a default index style. On save, Word writes this element within its table of contents and index.

- f. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-text>*

This attribute is supported in Word 2013 and later.

On load, Word ignores this element and reverts to a default index style. On save, Word writes this element within its table of contents and index.

- g. *The standard defines the attribute text:style-name, contained within the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This attribute is not supported in Word 2013 or later.

- h. *The standard defines the attribute text:style-name, contained within the element <text:list>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- i. *The standard defines the attribute text:style-name, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- j. *The standard defines the attribute `text:style-name`, contained within the element `<text:p>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- k. *The standard defines the attribute `text:style-name`, contained within the element `<text:ruby-text>`, contained within the parent element `<text:ruby>`*

This attribute is supported in Word 2013 and later.

On save, text formatting properties on ruby text are retained if all characters in the ruby text share the same text properties.

- l. *The standard defines the attribute `text:style-name`, contained within the element `<text:span>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- m. *The standard defines the attribute `text:style-name`, contained within the element `<text:table-of-content>`*

This attribute is not supported in Word 2013 or later.

On load, Word ignores the table of contents style and uses a default table of contents style.

On save, Word writes out the style of the table of contents.

- n. *The standard defines the attribute `text:style-name`, contained within the element `<text:a>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

Hyperlinks are not supported at the text level.

- o. *The standard defines the attribute `text:style-name`, contained within the element `<text:list>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

- p. *The standard defines the attribute text:style-name, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes and SmartArt.

- q. *The standard defines the attribute text:style-name, contained within the element <text:list-level-style-number>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- r. *The standard defines the attribute text:style-name, contained within the element <text:p>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

s. *The standard defines the attribute text:style-name, contained within the element <text:ruby>*

This attribute is not supported in Excel 2013 or later.

t. *The standard defines the attribute text:style-name, contained within the element <text:ruby-text>*

This attribute is not supported in Excel 2013 or later.

u. *The standard defines the attribute text:style-name, contained within the element <text:span>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

v. *The standard defines the attribute text:style-name, contained within the element <text:a>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

w. *The standard defines the attribute text:style-name, contained within the element <text:list>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- x. *The standard defines the attribute text:style-name, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- y. *The standard defines the attribute text:style-name, contained within the element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- z. *The standard defines the attribute text:style-name, contained within the element <text:p>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>



- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

aa. *The standard defines the attribute text:style-name, contained within the element <text:span>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

## **2.1.949 Part 3 Section 19.883, text:tab-ref**

a. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

b. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>, contained within the parent element <text:p>*

This attribute is not supported in Word 2013 or later.

c. *The standard defines the attribute text:tab-ref*

This attribute is not supported in Excel 2013 or later.

d. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>

- <draw:text-box>
  - <draw:custom-shape>
- e. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>, contained within the parent element <text:p>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

#### **2.1.950 Part 3 Section 19.886, text:time-adjust**

- a. *The standard defines the attribute text:time-adjust, contained within the element <text:time>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:time-adjust*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute text:time-adjust, contained within the element <text:time>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.951 Part 3 Section 19.887, text:time-value**

- a. *The standard defines the attribute text:time-value, contained within the element <text:time>*

This attribute is not supported in Word 2013 or later.

On load, if the time field is not fixed, Word displays the current time. On save, Word converts the time field to a date field and writes the current time as the text between the <text:date> element tags.

- b. *The standard defines the attribute text:time-value*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute text:time-value, contained within the element <text:time>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.952 Part 3 Section 19.889, text:track-changes**

- a. *The standard defines the element <text:track-changes>*

This element is not supported in Word 2013 or later.

On load and save, Word automatically accepts any tracked changes and applies the changes to the document.

### **2.1.953 Part 3 Section 19.898, text:use-keys-as-entries**

- a. *The standard defines the attribute text:use-keys-as-entries, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2013 or later.

### **2.1.954 Part 3 Section 19.906, text:value**

- a. *The standard defines the attribute text:value, contained within the element <text:label>*

This attribute is supported in Word 2021 and later.

### **2.1.955 Part 3 Section 19.907, text:visited-style-name**

- a. *The standard defines the attribute text:visited-style-name, contained within the element <text:a>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute text:visited-style-name, contained within the element <text:a>*

This attribute is not supported in Excel 2013 or later.

**OfficeArt Math** in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- c. *The standard defines the attribute text:visited-style-name, contained within the element <text:a>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

### **2.1.956 Part 3 Section 19.910, xforms:bind**

- a. *The standard defines the attribute xforms:bind*  
This attribute is not supported in Word 2013 or later.
- b. *The standard defines the attribute xforms:bind*  
This attribute is not supported in Excel 2013 or later.

### **2.1.957 Part 3 Section 19.911, xhtml:about**

- a. *The standard defines the attribute xhtml:about, contained within the element <table:covered-table-cell>*  
This attribute is supported in Word 2013 and later.
- b. *The standard defines the attribute xhtml:about, contained within the element <table:table-cell>*  
This attribute is supported in Word 2013 and later.
- c. *The standard defines the attribute xhtml:about, contained within the element <text:bookmark-start>*  
This attribute is supported in Word 2013 and later.
- d. *The standard defines the attribute xhtml:about, contained within the element <text:h>*  
This attribute is supported in Word 2013 and later.
- e. *The standard defines the attribute xhtml:about, contained within the element <text:meta>*  
This attribute is supported in Word 2013 and later.
- f. *The standard defines the attribute xhtml:about, contained within the element <text:p>*  
This attribute is supported in Word 2013 and later.
- g. *The standard defines the attribute xhtml:about, contained within the element <table:table-cell>*

### **2.1.958 Part 3 Section 19.912, xhtml:content**

- a. *The standard defines the attribute xhtml:content, contained within the element <table:covered-table-cell>*  
This attribute is supported in Word 2013 and later.
- b. *The standard defines the attribute xhtml:content, contained within the element <table:table-cell>*  
This attribute is supported in Word 2013 and later.

- c. *The standard defines the attribute `xhtml:content`, contained within the element `<text:bookmark-start>`*

This attribute is supported in Word 2013 and later.

- d. *The standard defines the attribute `xhtml:content`, contained within the element `<text:h>`*

This attribute is supported in Word 2013 and later.

- e. *The standard defines the attribute `xhtml:content`, contained within the element `<text:meta>`*

This attribute is supported in Word 2013 and later.

- f. *The standard defines the attribute `xhtml:content`, contained within the element `<text:p>`*

This attribute is supported in Word 2013 and later.

- g. *The standard defines the attribute `xhtml:content`, contained within the element `<table:table-cell>`*

### **2.1.959 Part 3 Section 19.913, `xhtml:datatype`**

- a. *The standard defines the attribute `xhtml:datatype`, contained within the element `<table:covered-table-cell>`*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the attribute `xhtml:datatype`, contained within the element `<table:table-cell>`*

This attribute is supported in Word 2013 and later.

- c. *The standard defines the attribute `xhtml:datatype`, contained within the element `<text:bookmark-start>`*

This attribute is supported in Word 2013 and later.

- d. *The standard defines the attribute `xhtml:datatype`, contained within the element `<text:h>`*

This attribute is supported in Word 2013 and later.

- e. *The standard defines the attribute `xhtml:datatype`, contained within the element `<text:meta>`*

This attribute is supported in Word 2013 and later.

- f. *The standard defines the attribute `xhtml:datatype`, contained within the element `<text:p>`*

This attribute is supported in Word 2013 and later.

- g. *The standard defines the attribute `xhtml:datatype`, contained within the element `<table:table-cell>`*

### **2.1.960 Part 3 Section 19.914, `xhtml:property`**

- a. *The standard defines the attribute `xhtml:property`, contained within the element `<table:covered-table-cell>`*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the attribute `xhtml:property`, contained within the element `<table:table-cell>`*

This attribute is supported in Word 2013 and later.

- c. *The standard defines the attribute `xhtml:property`, contained within the element `<text:bookmark-start>`*

This attribute is supported in Word 2013 and later.

- d. *The standard defines the attribute `xhtml:property`, contained within the element `<text:h>`*

This attribute is supported in Word 2013 and later.

- e. *The standard defines the attribute `xhtml:property`, contained within the element `<text:meta>`*

This attribute is supported in Word 2013 and later.

- f. *The standard defines the attribute `xhtml:property`, contained within the element `<text:p>`*

This attribute is supported in Word 2013 and later.

- g. *The standard defines the attribute `xhtml:property`, contained within the element `<table:table-cell>`*

### **2.1.961 Part 3 Section 19.915, `xlink:actuate`**

- a. *The standard defines the attribute `xlink:actuate`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- b. *The standard defines the attribute `xlink:actuate`, contained within the element `<draw:object>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `xlink:actuate`, contained within the element `<form:form>`*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute `xlink:actuate`, contained within the element `<text:a>`*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute `xlink:actuate`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute `xlink:actuate`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `xlink:actuate`, contained within the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `xlink:actuate`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `xlink:actuate`, contained within the element `<table:table-source>`, contained within the parent element `<table:table>`*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute `xlink:actuate`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

## **2.1.962 Part 3 Section 19.916, `xlink:href`**

- a. *The standard defines the attribute `xlink:href`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `xlink:href`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Relative URIs are not supported, only absolute URIs are supported.

- c. *The standard defines the attribute `xlink:href`, contained within the element `<draw:image>`*

This attribute is supported in Word 2013 and later.

Relative URIs are not supported, only absolute URIs are supported.

- d. *The standard defines the attribute `xlink:href`, contained within the element `<draw:object>`*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute `xlink:href`, contained within the element `<form:form>`*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute `xlink:href`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `xlink:href`, contained within the element `<chart:symbol-image>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `xlink:href`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Relative URIs are not supported, only absolute URIs are supported.

- i. *The standard defines the attribute `xlink:href`, contained within the element `<draw:image>`*

This attribute is supported in Excel 2013 and later.



Relative URIs are not supported, only absolute URIs are supported.

- j. *The standard defines the attribute `xlink:href`, contained within the element `<form:form>`*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `xlink:href`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute `xlink:href`, contained within the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute `xlink:href`, contained within the element `<text:a>`*

This attribute is not supported in Excel 2013 or later.

On load, `xlink:href` attribute is not supported for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

Hyperlinks are not supported at the text level.

- n. *The standard defines the attribute `xlink:href`, contained within the element `<text:list-level-style-image>`*

**OfficeArt Math** in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes.

- o. *The standard defines the attribute `xlink:href`, contained within the element `<anim:audio>`*

This attribute is not supported in PowerPoint 2013 or later.

- p. *The standard defines the attribute `xlink:href`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

Relative URIs are not supported, only absolute URIs are supported.

- q. *The standard defines the attribute `xlink:href`, contained within the element `<draw:image>`*

This attribute is supported in PowerPoint 2013 and later.

Relative URIs are not supported, only absolute URIs are supported.

- r. *The standard defines the attribute `xlink:href`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

- s. *The standard defines the attribute `xlink:href`, contained within the element `<text:list-level-style-image>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`

- <draw:frame>
- <draw:custom-shape>.

### 2.1.963 Part 3 Section 19.917, xlink:show

- a. *The standard defines the attribute xlink:show, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute xlink:show, contained within the element <draw:object>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute xlink:show, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute xlink:show, contained within the element <style:background-image>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute xlink:show, contained within the element <text:a>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the property "new", contained within the attribute xlink:show, contained within the element <text:a>*

**OfficeArt Math** in Excel 2013 does not support this enum, on load, for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- g. *The standard defines the property "replace", contained within the attribute xlink:show, contained within the element <text:a>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- h. *The standard defines the attribute xlink:show, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the property "new", contained within the attribute xlink:show, contained within the element <text:a>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- j. *The standard defines the property "replace", contained within the attribute xlink:show, contained within the element <text:a>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

Written as "replace" if the target frame is not empty.

## **2.1.964 Part 3 Section 19.919, xlink:type**

- a. *The standard defines the attribute xlink:type, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute xlink:type, contained within the element <draw:object>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute xlink:type, contained within the element <form:form>*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute `xlink:type`, contained within the element `<text:a>`*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute `xlink:type`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- f. *The standard defines the attribute `xlink:type`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `xlink:type`, contained within the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `xlink:type`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `xlink:type`, contained within the element `<table:table-source>`, contained within the parent element `<table:table>`*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute `xlink:type`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

## **2.1.965 Part 3 Section 19.920, xml:id**

- a. *The standard defines the attribute xml:id, contained within the element <office:annotation>*  
This attribute is supported in Word 2013 and later.
- b. *The standard defines the attribute xml:id, contained within the element <table:covered-table-cell>*  
This attribute is supported in Word 2013 and later.
- c. *The standard defines the attribute xml:id, contained within the element <table:table>*  
This attribute is supported in Word 2013 and later.
- d. *The standard defines the attribute xml:id, contained within the element <table:table-cell>*  
This attribute is supported in Word 2013 and later.
- e. *The standard defines the attribute xml:id, contained within the element <table:table-column>*  
This attribute is supported in Word 2013 and later.
- f. *The standard defines the attribute xml:id, contained within the element <table:table-row>*  
This attribute is supported in Word 2013 and later.
- g. *The standard defines the attribute xml:id, contained within the element <text:alphabetical-index>*  
This attribute is supported in Word 2013 and later.
- h. *The standard defines the attribute xml:id, contained within the element <text:bookmark>*  
This attribute is supported in Word 2013 and later.
- i. *The standard defines the attribute xml:id, contained within the element <text:bookmark-start>*  
This attribute is supported in Word 2013 and later.
- j. *The standard defines the attribute xml:id, contained within the element <text:changed-region>*  
This attribute is supported in Word 2013 and later.
- k. *The standard defines the attribute xml:id, contained within the element <text:h>*  
This attribute is supported in Word 2013 and later.
- l. *The standard defines the attribute xml:id, contained within the element <text:list-item>*  
This attribute is supported in Word 2013 and later.
- m. *The standard defines the attribute xml:id, contained within the element <text:meta>*  
This attribute is supported in Word 2013 and later.
- n. *The standard defines the attribute xml:id, contained within the element <text:meta-field>*  
This attribute is supported in Word 2013 and later.
- o. *The standard defines the attribute xml:id, contained within the element <text:numbered-paragraph>*  
This attribute is supported in Word 2013 and later.

- p. *The standard defines the attribute `xml:id`, contained within the element `<text:p>`*  
This attribute is supported in Word 2013 and later.
- q. *The standard defines the attribute `xml:id`, contained within the element `<text:section>`*  
This attribute is supported in Word 2013 and later.
- r. *The standard defines the attribute `xml:id`, contained within the element `<text:table-of-content>`*  
This attribute is supported in Word 2013 and later.
- s. *The standard defines the attribute `xml:id`, contained within the element `<table:table>`*
- t. *The standard defines the attribute `xml:id`, contained within the element `<table:table-cell>`*
- u. *The standard defines the attribute `xml:id`, contained within the element `<table:table-row>`*

#### **2.1.966 Part 3 Section 20.2, chart:angle-offset**

- a. *The standard defines the attribute `fo:margin-left`, contained within the element `<style:table-properties>`*

#### **2.1.967 Part 3 Section 20.7, chart:connect-bars**

- a. *The standard defines the attribute `chart:connect-bars`*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the elements `<chart:chart>`, `<chart:plot-area>`, and `<chart:series>`, when the series type is bar.

#### **2.1.968 Part 3 Section 20.8, chart:data-label-number**

- a. *The standard defines the attribute `chart:data-label-number`*

This attribute is supported in Excel 2013 and later.

On load Excel applies the "percentage" value only if the chart type is `chart:circle` or `chart:ring`. Also, Excel applies the "percentage" value if the chart contains a circle or ring series when the attribute is on the style of the `chart:plot-area`.

On save Excel writes the "percentage" value only if the series type is pie or doughnut in Excel.

#### **2.1.969 Part 3 Section 20.9, chart:data-label-series**

- a. *The standard defines the attribute `chart:data-label-series`*

This attribute is supported in Excel 2021 and later.

#### **2.1.970 Part 3 Section 20.10, chart:data-label-symbol**

- a. *The standard defines the attribute `chart:data-label-symbol`*

Excel 2013 supports this attribute for a style of the `<chart:plot-area>`, `<chart:series>`, and `<chart:data-point>` elements.



### **2.1.971 Part 3 Section 20.11, chart:data-label-text**

- a. *The standard defines the attribute chart:data-label-text*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:plot-area>, <chart:series>, and <chart:data-point> elements.

### **2.1.972 Part 3 Section 20.12, chart:deep**

- a. *The standard defines the attribute chart:deep*

This attribute is supported in Excel 2013 and later.

When the chart:deep attribute is "true", the chart must have a <chart:axis> element with the chart:dimension attribute equal to "z" and the chart:three-dimensional attribute must equal "true".

On load, the <style-chart-properties-attlist> element is ignored when the chart type is surface, and is always saved as "true".

This attribute must equal "false" when the chart:stacked or chart:percentage attributes are "true".

This attribute must equal "false" when the chart type is bar and the "chart:vertical" property equals "false". This attribute applies to the style of the <chart:chart> and <chart:plot-area> elements when the chart type is area or bar.

### **2.1.973 Part 3 Section 20.13, chart:display-label**

- a. *The standard defines the attribute chart:display-label*

This attribute is supported in Excel 2013 and later.

This attribute applies to the <style-chart-properties-attlist> element of the <chart:axis> element.

### **2.1.974 Part 3 Section 20.14, chart:error-category**

- a. *The standard defines the property "constant", contained within the attribute chart:error-category*

Excel 2013 supports this enum for the style of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is line, area, scatter, bar, stock, or bubble.

- b. *The standard defines the property "error-margin", contained within the attribute chart:error-category*

This property is not supported in Excel 2013 or later.

- c. *The standard defines the property "none", contained within the attribute chart:error-category*

This property is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is "line", "area", "scatter", "bar", "stock", or "bubble".

- d. *The standard defines the property "percentage", contained within the attribute chart:error-category*

This property is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is "line", "area", "scatter", "bar", "stock", or "bubble".

- e. *The standard defines the property "variance", contained within the attribute chart:error-category*

This property is not supported in Excel 2013 or later.

### **2.1.975 Part 3 Section 20.15, chart:error-lower-indicator**

- a. *The standard defines the attribute chart:error-lower-indicator*

This attribute is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is "line", "area", "scatter", "bar", "stock", or "bubble".

### **2.1.976 Part 3 Section 20.16, chart:error-lower-limit**

- a. *The standard defines the attribute chart:error-lower-limit*

This attribute is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is "line", "area", "scatter", "bar", "stock", or "bubble".

### **2.1.977 Part 3 Section 20.18, chart:error-margin**

- a. *The standard defines the attribute chart:error-margin*

This attribute is not supported in Excel 2013 or later.

### **2.1.978 Part 3 Section 20.19, chart:error-percentage**

- a. *The standard defines the attribute chart:error-percentage*

Excel 2013 supports this attribute for the style of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is line, area, scatter, bar, stock, or bubble.

### **2.1.979 Part 3 Section 20.20, chart:error-upper-indicator**

- a. *The standard defines the attribute chart:error-upper-indicator*

This attribute is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is "line", "area", "scatter", "bar", "stock", or "bubble".

### **2.1.980 Part 3 Section 20.21, chart:error-upper-limit**

- a. *The standard defines the attribute chart:error-upper-limit*

Excel 2013 supports this attribute uses this attribute for the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements when the chart is not three dimensional and the series type is "line", "area", "scatter", "bar", "stock", or "bubble".

### **2.1.981 Part 3 Section 20.23, chart:gap-width**

- a. *The standard defines the attribute chart:gap-width*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the element <chart:axis>, when the attribute chart:dimension of the axis equals "y" and the chart type is bar.

### **2.1.982 Part 3 Section 20.24, chart:group-bars-per-axis**

- a. *The standard defines the attribute chart:group-bars-per-axis*

This attribute is supported in Excel 2013 and later.

### **2.1.983 Part 3 Section 20.27, chart:interpolation**

- a. *The standard defines the attribute chart:interpolation*

This attribute is supported in Excel 2013 and later.

On load, both the "cubic-spline" and "b-spline" values load as "cubic-spline". On save, only the "cubic-spline" value is applied to the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements.

- b. *The standard defines the property "step-center-x", contained within the attribute chart:interpolation*

This property is not supported in Excel 2013 or later. In Excel 2021 and later this property will load as "none".

- c. *The standard defines the property "step-center-y", contained within the attribute chart:interpolation*

This property is not supported in Excel 2013 or later. In Excel 2021 and later this property will load as "none".

- d. *The standard defines the property "step-start", contained within the attribute chart:interpolation*

This property is not supported in Excel 2013 or later. In Excel 2021 and later this property will load as "none".

- e. *The standard defines the property "step-end", contained within the attribute chart:interpolation*

This property is not supported in Excel 2013 or later. In Excel 2021 and later this property will load as "none".

### **2.1.984 Part 3 Section 20.28, chart:interval-major**

- a. *The standard defines the attribute chart:interval-major*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:axis> element when the chart:dimension attribute of the <chart:axis> element equals "y" or the <chart:axis> element is associated with a scatter chart.

### **2.1.985 Part 3 Section 20.29, chart:interval-minor-divisor**

- a. *The standard defines the attribute chart:interval-minor-divisor*

This attribute is supported in Excel 2013 and later.

This element is ignored if the chart:interval-major attribute is not specified. This attribute applies to the style of the <chart:axis> element when the chart:dimension attribute of the axis equals "y" or the axis is associated with a scatter chart.

### **2.1.986 Part 3 Section 20.30, chart:japanese-candle-stick**

- a. *The standard defines the attribute chart:japanese-candle-stick*

This attribute is not supported in Excel 2013 or later.

### **2.1.987 Part 3 Section 20.31, chart:label-arrangement**

- a. *The standard defines the attribute chart:label-arrangement*

This attribute is not supported in Excel 2013 or later.

### **2.1.988 Part 3 Section 20.33, chart:label-position-negative**

- a. *The standard defines the attribute chart:label-position-negative*

This attribute is supported in Excel 2013 and later.

- b. *The standard defines the attribute style:page-number, contained within the element <style:table-properties>*

### **2.1.989 Part 3 Section 20.34, chart:lines**

- a. *The standard defines the attribute chart:lines*

This attribute is supported in Excel 2013 and later.

This attribute applies to the <style-chart-properties-attlist> element of the <chart:chart>, <chart:plot-area>, and <chart:series> elements when the series type is "line", "scatter", or "radar".

*This attribute was deprecated in the ODF 1.2 standard.*

### **2.1.990 Part 3 Section 20.35, chart:link-data-style-to-source**

- a. *The standard defines the attribute chart:link-data-style-to-source*

This attribute is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:axis> and <chart:series> elements when the chart has data labels.

### **2.1.991 Part 3 Section 20.36, chart:logarithmic**

- a. *The standard defines the attribute chart:logarithmic*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:axis> element when the chart:dimension attribute of the <chart:axis> element equals "y" or the <chart:axis> element is associated with a scatter chart.

### **2.1.992 Part 3 Section 20.37, chart:maximum**

- a. *The standard defines the attribute chart:maximum*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:axis> element when the chart:dimension attribute of the <chart:axis> element equals "y" or the <chart:axis> element is associated with a scatter chart.

### **2.1.993 Part 3 Section 20.39, chart:minimum**

- a. *The standard defines the attribute chart:minimum*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:axis> element when the chart:dimension attribute of the <chart:axis> element equals "y" or the <chart:axis> element is associated with a scatter chart.

### **2.1.994 Part 3 Section 20.40, chart:origin**

- a. *The standard defines the attribute chart:origin*

This attribute is supported in Excel 2013 and later.

This attribute applies to the <style-chart-properties-attlist> element of the <chart:axis> element.

### **2.1.995 Part 3 Section 20.41, chart:overlap**

- a. *The standard defines the attribute chart:overlap*

This attribute is supported in Excel 2013 and later.

The attribute chart:overlap applies to the style of the element <chart:axis>, when the attribute chart:dimension of the axis equals "y" and the chart type is bar.

### **2.1.996 Part 3 Section 20.42, chart:pie-offset**

- a. *The standard defines the attribute chart:pie-offset*

This attribute is supported in Excel 2013 and later.

This attribute applies to the <style-chart-properties-attlist> element of the <chart:plot-area>, <chart:series>, and <chart:data-point> elements when the series type is "circle" or "ring".

### **2.1.997 Part 3 Section 20.43, chart:percentage**

- a. *The standard defines the attribute chart:percentage*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:chart>, <chart:plot-area>, and <chart:series> elements when the series type is line, area, or bar.

### **2.1.998 Part 3 Section 20.44, chart:regression-force-intercept**

- a. *The standard defines the attribute chart:regression-force-intercept*

This attribute is supported in Excel 2021 and later.

### **2.1.999 Part 3 Section 20.45, chart:regression-intercept-value**

- a. *The standard defines the attribute chart:regression-intercept-value*

This attribute is supported in Excel 2021 and later.

### **2.1.1000 Part 3 Section 20.46, chart:regression-max-degree**

- a. *The standard defines the attribute chart:regression-max-degree*

This attribute is supported in Excel 2021 and later.

Values above 6 are not supported.

### **2.1.1001 Part 3 Section 20.47, chart:regression-moving-type**

- a. *The standard defines the property "prior", contained within the attribute chart:regression-moving-type*

This property is supported in Excel 2021 and later.

- b. *The standard defines the property "central", contained within the attribute chart:regression-moving-type*

This property is not supported in Excel 2013 or later.

- c. *The standard defines the property "averaged-abcissa", contained within the attribute chart:regression-moving-type*

This property is not supported in Excel 2013 or later.

### **2.1.1002 Part 3 Section 20.48, chart:regression-name**

- a. *The standard defines the attribute chart:regression-name*

This attribute is supported in Excel 2021 and later.

### **2.1.1003 Part 3 Section 20.49, chart:regression-period**

- a. *The standard defines the attribute chart:regression-period*

This attribute is supported in Excel 2021 and later.

### **2.1.1004 Part 3 Section 20.50, chart:regression-type**

- a. *The standard defines the attribute chart:regression-type*

This attribute is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:series> or <chart:plot-area> elements when the series type is "line", "area", "scatter", "bar", "stock", or "bubble", and the chart is not three dimensional.

The "moving-average" and "polynomial" values for this attribute are supported in Excel 2021 and later.

- b. *The standard defines the property "moving-average", contained within the attribute chart:regression-type*

This property is supported in Excel 2021 and later.

- c. *The standard defines the property "polynomial", contained within the attribute chart:regression-type*

This property is supported in Excel 2021 and later.

### **2.1.1005 Part 3 Section 20.53, chart:scale-text**

- a. *The standard defines the attribute chart:scale-text*

This attribute is not supported in Excel 2013 or later.

### **2.1.1006 Part 3 Section 20.54, chart:series-source**

- a. *The standard defines the attribute chart:series-source*

This attribute is not supported in Excel 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

### **2.1.1007 Part 3 Section 20.55, chart:sort-by-x-values**

- a. *The standard defines the attribute chart:sort-by-x-values*

This attribute is supported in Excel 2013 and later.

### **2.1.1008 Part 3 Section 20.57, chart:spline-order**

- a. *The standard defines the attribute chart:spline-order*

This attribute is not supported in Excel 2013 or later.

### **2.1.1009 Part 3 Section 20.58, chart:spline-resolution**

- a. *The standard defines the attribute chart:spline-resolution*

This attribute is not supported in Excel 2013 or later.

### **2.1.1010 Part 3 Section 20.59, chart:stacked**

- a. *The standard defines the attribute chart:stacked*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:chart>, <chart:plot-area>, and <chart:series> elements when the series type is line, area, or bar.

### **2.1.1011 Part 3 Section 20.60, chart:symbol-height**

- a. *The standard defines the attribute chart:symbol-height*

This attribute is supported in Excel 2013 and later.

The attribute chart:symbol-height, contained within the element <style-chart-properties-attlist>, applies to the style of the elements <chart:series> and <chart:data-point>, when the series type is line, scatter, or radar.

### **2.1.1012 Part 3 Section 20.61, chart:symbol-name**

- a. *The standard defines the property "arrow-down", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- b. *The standard defines the property "arrow-left", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- c. *The standard defines the property "arrow-right", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "arrow-up", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the property "asterisk", contained within the attribute chart:symbol-name*

This property is supported in Excel 2013 and later.

When the series is of type line, scatter, or radar, the attribute chart:symbol-name applies to the style of the elements <chart:series> and <chart:data-point>.

- f. *The standard defines the property "bow-tie", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- g. *The standard defines the property "circle", contained within the attribute chart:symbol-name*

This property is supported in Excel 2013 and later.

The property "circle," contained within the attribute chart:symbol-name, contained within the element <style-chart-properties-attlist>, applies to the style of the elements <chart:series> and <chart:data-point>, when the series type is line, scatter, or radar.

- h. *The standard defines the property "diamond", contained within the attribute chart:symbol-name*

This property is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:series> and <chart:data-point> elements when the series type is line, scatter, or radar.



- i. *The standard defines the property "horizontal-bar", contained within the attribute chart:symbol-name*

This property is supported in Excel 2013 and later.

The "horizontal-bar" property, contained within the chart:symbol-name attribute, contained within the <style-chart-properties> element, applies to the style of the <chart:series> and <chart:data-point> elements when the series type is line, scatter, or radar.

- j. *The standard defines the property "hourglass", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- k. *The standard defines the property "plus", contained within the attribute chart:symbol-name*

This property is supported in Excel 2013 and later.

The property "plus," contained within the attribute chart:symbol-name, contained within the element <style-chart-properties-attlist>, applies to the style of the elements <chart:series> and <chart:data-point>, when the series type is line, scatter, or radar.

- l. *The standard defines the property "square", contained within the attribute chart:symbol-name*

This property is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:series> and <chart:data-point> elements when the series type is line, scatter, or radar.

- m. *The standard defines the property "star", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- n. *The standard defines the property "vertical-bar", contained within the attribute chart:symbol-name*

This property is not supported in Excel 2013 or later.

- o. *The standard defines the property "x", contained within the attribute chart:symbol-name*

This property is supported in Excel 2013 and later.

The property "x," contained within the attribute chart:symbol-name, contained within the element <style-chart-properties-attlist>, applies to the style of the elements <chart:series> and <chart:data-point>, when the series type is line, scatter, or radar.

### **2.1.1013 Part 3 Section 20.62, chart:symbol-type**

- a. *The standard defines the attribute chart:symbol-type*

This attribute is supported in Excel 2013 and later.

This attribute applies to the style of the <chart:series> and <chart:data-point> elements when the series type is line, scatter, or radar.

### **2.1.1014 Part 3 Section 20.63, chart:symbol-width**

- a. *The standard defines the attribute chart:symbol-width*

This attribute is supported in Excel 2013 and later.

This attribute is ignored if the `chart:symbol-height` attribute is specified. Otherwise, the `chart:symbol-width` attribute applies to the style of the `<chart:series>` and `<chart:data-point>` elements, when the series type is line, scatter, or radar.

#### **2.1.1015 Part 3 Section 20.64, `chart:text-overlap`**

- a. *The standard defines the attribute `chart:text-overlap`*

This attribute is not supported in Excel 2013 or later.

#### **2.1.1016 Part 3 Section 20.65, `chart:three-dimensional`**

- a. *The standard defines the attribute `chart:three-dimensional`*

This attribute is supported in Excel 2013 and later.

This attribute must equal the value "true" when the chart type is surface. This attribute applies to the style of the `<chart:chart>` and `<chart:plot-area>` elements when the series type is line, area, circle, bar, or surface.

#### **2.1.1017 Part 3 Section 20.66, `chart:tick-marks-major-inner`**

- a. *The standard defines the attribute `chart:tick-marks-major-inner`*

Excel 2013 supports this attribute for the style of the `<chart:axis>` element.

#### **2.1.1018 Part 3 Section 20.67, `chart:tick-marks-major-outer`**

- a. *The standard defines the attribute `chart:tick-marks-major-outer`*

Excel 2013 supports this attribute for the style of the `<chart:axis>` element.

#### **2.1.1019 Part 3 Section 20.68, `chart:tick-marks-minor-inner`**

- a. *The standard defines the attribute `chart:tick-marks-minor-inner`*

Excel 2013 supports this attribute for the style of the `<chart:axis>` element.

#### **2.1.1020 Part 3 Section 20.69, `chart:tick-marks-minor-outer`**

- a. *The standard defines the attribute `chart:tick-marks-minor-outer`*

Excel 2013 supports this attribute for the style of the `<chart:axis>` element.

#### **2.1.1021 Part 3 Section 20.70, `chart:tick-mark-position`**

- a. *The standard defines the attribute `chart:tick-mark-position`*

This attribute is supported in Excel 2013 and later.

#### **2.1.1022 Part 3 Section 20.72, `chart:vertical`**

- a. *The standard defines the attribute `chart:vertical`*

Excel 2013 supports this attribute The chart:vertical attribute applies to the <style-chart-properties-attlist> element of the <chart:plot-area> and <chart:series> elements when the series type is bar.

### **2.1.1023 Part 3 Section 20.73, chart:visible**

- a. *The standard defines the attribute chart:visible*

This attribute is supported in Excel 2013 and later.

Excel uses this attribute for the <style-chart-properties-attlist> element of the <chart:axis> element.

### **2.1.1024 Part 3 Section 20.75, dr3d:back-scale**

- a. *The standard defines the attribute dr3d:back-scale, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:back-scale, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:back-scale, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1025 Part 3 Section 20.76, dr3d:backface-culling**

- a. *The standard defines the attribute dr3d:backface-culling, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:backface-culling, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:backface-culling, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1026 Part 3 Section 20.77, dr3d:close-back**

- a. *The standard defines the attribute dr3d:close-back, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:close-back, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:close-back`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1027 Part 3 Section 20.78, `dr3d:close-front`**

- a. *The standard defines the attribute `dr3d:close-front`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:close-front`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:close-front`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1028 Part 3 Section 20.79, `dr3d:depth`**

- a. *The standard defines the attribute `dr3d:depth`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:depth`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:depth`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1029 Part 3 Section 20.81, `dr3d:edge-rounding`**

- a. *The standard defines the attribute `dr3d:edge-rounding`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:edge-rounding`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:edge-rounding`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1030 Part 3 Section 20.82, dr3d:edge-rounding-mode**

- a. *The standard defines the attribute dr3d:edge-rounding-mode, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:edge-rounding-mode, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:edge-rounding-mode, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1031 Part 3 Section 20.83, dr3d:emissive-color**

- a. *The standard defines the attribute dr3d:emissive-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:emissive-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:emissive-color, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1032 Part 3 Section 20.84, dr3d:end-angle**

- a. *The standard defines the attribute dr3d:end-angle, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:end-angle, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:end-angle, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1033 Part 3 Section 20.85, dr3d:horizontal-segments**

- a. *The standard defines the attribute dr3d:horizontal-segments, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:horizontal-segments, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:horizontal-segments`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1034 Part 3 Section 20.87, `dr3d:normals-direction`**

- a. *The standard defines the attribute `dr3d:normals-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:normals-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:normals-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1035 Part 3 Section 20.88, `dr3d:normals-kind`**

- a. *The standard defines the attribute `dr3d:normals-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:normals-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:normals-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1036 Part 3 Section 20.89, `dr3d:shadow`**

- a. *The standard defines the attribute `dr3d:shadow`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:shadow`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:shadow`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1037 Part 3 Section 20.90, dr3d:shininess**

- a. *The standard defines the attribute dr3d:shininess, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:shininess, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:shininess, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1038 Part 3 Section 20.91, dr3d:specular-color**

- a. *The standard defines the attribute dr3d:specular-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:specular-color, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:specular-color, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1039 Part 3 Section 20.92, dr3d:texture-filter**

- a. *The standard defines the attribute dr3d:texture-filter, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:texture-filter, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:texture-filter, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1040 Part 3 Section 20.93, dr3d:texture-kind**

- a. *The standard defines the attribute dr3d:texture-kind, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:texture-kind, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:texture-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1041 Part 3 Section 20.94, `dr3d:texture-mode`**

- a. *The standard defines the attribute `dr3d:texture-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:texture-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:texture-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1042 Part 3 Section 20.95, `dr3d:texture-generation-mode-x`**

- a. *The standard defines the attribute `dr3d:texture-generation-mode-x`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:texture-generation-mode-x`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:texture-generation-mode-x`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1043 Part 3 Section 20.96, `dr3d:texture-generation-mode-y`**

- a. *The standard defines the attribute `dr3d:texture-generation-mode-y`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `dr3d:texture-generation-mode-y`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `dr3d:texture-generation-mode-y`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.



### 2.1.1044 Part 3 Section 20.97, dr3d:vertical-segments

- a. *The standard defines the attribute dr3d:vertical-segments, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute dr3d:vertical-segments, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute dr3d:vertical-segments, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### 2.1.1045 Part 3 Section 20.98, draw:auto-grow-height

- a. *The standard defines the attribute draw:auto-grow-height, contained within the element <style:graphic-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute draw:auto-grow-height, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute draw:auto-grow-height, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1046 Part 3 Section 20.99, draw:auto-grow-width

- a. *The standard defines the attribute draw:auto-grow-width, contained within the element <style:graphic-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute draw:auto-grow-width, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute draw:auto-grow-width, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1047 Part 3 Section 20.100, draw:background-size**

- a. *The standard defines the attribute draw:background-size, contained within the element <style:drawing-page-properties>*

This attribute is not supported in PowerPoint 2013 or later.

On load, PowerPoint writes this attribute as "border" On load PowerPoint ignores this attribute.

### **2.1.1048 Part 3 Section 20.101, draw:blue**

- a. *The standard defines the attribute draw:blue, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the attribute draw:blue, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the attribute draw:blue, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

### **2.1.1049 Part 3 Section 20.102, draw:caption-angle**

- a. *The standard defines the attribute draw:caption-angle, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:caption-angle, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:caption-angle, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1050 Part 3 Section 20.103, draw:caption-angle-type**

- a. *The standard defines the attribute draw:caption-angle-type, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:caption-angle-type`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:caption-angle-type`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1051 Part 3 Section 20.104, `draw:caption-escape`**

- a. *The standard defines the attribute `draw:caption-escape`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:caption-escape`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:caption-escape`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1052 Part 3 Section 20.105, `draw:caption-escape-direction`**

- a. *The standard defines the attribute `draw:caption-escape-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:caption-escape-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:caption-escape-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1053 Part 3 Section 20.106, `draw:caption-fit-line-length`**

- a. *The standard defines the attribute `draw:caption-fit-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:caption-fit-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:caption-fit-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1054 Part 3 Section 20.107, draw:caption-gap**

- a. *The standard defines the attribute draw:caption-gap, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:caption-gap, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:caption-gap, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1055 Part 3 Section 20.108, draw:caption-line-length**

- a. *The standard defines the attribute draw:caption-line-length, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:caption-line-length, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:caption-line-length, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1056 Part 3 Section 20.109, draw:caption-type**

- a. *The standard defines the attribute draw:caption-type, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:caption-type, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:caption-type, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1057 Part 3 Section 20.110, draw:color-inversion**

- a. *The standard defines the attribute draw:color-inversion, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the attribute `draw:color-inversion`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- c. *The standard defines the attribute `draw:color-inversion`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

### **2.1.1058 Part 3 Section 20.111, `draw:color-mode`**

- a. *The standard defines the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- b. *The standard defines the property "greyscale", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- c. *The standard defines the property "mono", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- d. *The standard defines the property "standard", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- e. *The standard defines the property "watermark", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- f. *The standard defines the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- g. *The standard defines the property "greyscale", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- h. *The standard defines the property "mono", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- i. *The standard defines the property "standard", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*  
  
Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element.
- j. *The standard defines the property "watermark", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*  
  
Excel 2013 does not support this enum for a style applied to a <draw:frame> element containing a <draw:image> element.
- k. *The standard defines the attribute draw:color-mode, contained within the element <style:graphic-properties>*  
  
PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.
- l. *The standard defines the property "greyscale", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*  
  
PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element.
- m. *The standard defines the property "mono", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*  
  
PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element.
- n. *The standard defines the property "standard", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*  
  
PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element.
- o. *The standard defines the property "watermark", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*  
  
PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element containing a <draw:image> element.

### **2.1.1059 Part 3 Section 20.112, draw:contrast**

- a. *The standard defines the attribute draw:contrast, contained within the element <style:graphic-properties>*  
  
Word 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.
- b. *The standard defines the attribute draw:contrast, contained within the element <style:graphic-properties>*  
  
Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.
- c. *The standard defines the attribute draw:contrast, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

### **2.1.1060 Part 3 Section 20.113, draw:decimal-places**

- a. *The standard defines the attribute draw:decimal-places, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:decimal-places, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:decimal-places, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1061 Part 3 Section 20.114, draw:draw-aspect**

- a. *The standard defines the attribute draw:draw-aspect, contained within the element <style:graphic-properties>*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the attribute draw:draw-aspect, contained within the element <style:graphic-properties>*

This attribute is supported in Excel 2013 Client and Excel 2016 Client.

- c. *The standard defines the attribute draw:draw-aspect, contained within the element <style:graphic-properties>*

This attribute is supported in PowerPoint 2013 Client and PowerPoint 2016 Client.

### **2.1.1062 Part 3 Section 20.115, draw:end-guide**

- a. *The standard defines the attribute draw:end-guide, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:end-guide, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:end-guide, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1063 Part 3 Section 20.116, draw:end-line-spacing-horizontal**

- a. *The standard defines the attribute draw:end-line-spacing-horizontal, contained within the element <style:graphic-properties>*



This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:end-line-spacing-horizontal`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:end-line-spacing-horizontal`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1064 Part 3 Section 20.117, `draw:end-line-spacing-vertical`**

- a. *The standard defines the attribute `draw:end-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:end-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:end-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1065 Part 3 Section 20.118, `draw:fill`**

- a. *The standard defines the attribute `draw:fill`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- b. *The standard defines the property "bitmap", contained within the attribute `draw:fill`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- c. *The standard defines the property "gradient", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- d. *The standard defines the property "hatch", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- e. *The standard defines the property "none", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- f. *The standard defines the property "solid", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- g. *The standard defines the attribute `draw:fill`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- h. *The standard defines the property "bitmap", contained within the attribute `draw:fill`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- i. *The standard defines the property "gradient", contained within the attribute `draw:fill`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- j. *The standard defines the property "hatch", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- k. *The standard defines the property "none", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- l. *The standard defines the property "solid", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- m. *The standard defines the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- n. *The standard defines the property "bitmap", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- o. *The standard defines the property "gradient", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- p. *The standard defines the property "hatch", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- q. *The standard defines the property "none", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- r. *The standard defines the property "solid", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1066 Part 3 Section 20.119, draw:fill-color**

- a. *The standard defines the attribute draw:fill-color, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-color, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- c. *The standard defines the attribute `draw:fill-color`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1067 Part 3 Section 20.120, `draw:fill-gradient-name`**

- a. *The standard defines the attribute `draw:fill-gradient-name`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:fill-gradient-name`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:g>
  - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
  - <draw:custom-shape>
- c. *The standard defines the attribute draw:fill-gradient-name, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1068 Part 3 Section 20.121, draw:fill-hatch-name**

- a. *The standard defines the attribute draw:fill-hatch-name, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-hatch-name, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element



- <draw:custom-shape>
- c. *The standard defines the attribute draw:fill-hatch-name, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1069 Part 3 Section 20.122, draw:fill-hatch-solid**

- a. *The standard defines the attribute draw:fill-hatch-solid, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-hatch-solid, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute draw:fill-hatch-solid, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1070 Part 3 Section 20.123, draw:fill-image-height**

- a. *The standard defines the attribute draw:fill-image-height, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- b. *The standard defines the attribute draw:fill-image-height, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- c. *The standard defines the attribute draw:fill-image-height, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

### **2.1.1071 Part 3 Section 20.124, draw:fill-image-name**

- a. *The standard defines the attribute draw:fill-image-name, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-image-name, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute draw:fill-image-name, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1072 Part 3 Section 20.125, draw:fill-image-ref-point**

- a. *The standard defines the attribute draw:fill-image-ref-point, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-image-ref-point, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:fill-image-ref-point, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>

- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1073 Part 3 Section 20.126, draw:fill-image-ref-point-x**

- a. *The standard defines the attribute draw:fill-image-ref-point-x, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-image-ref-point-x, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:fill-image-ref-point-x, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### 2.1.1074 Part 3 Section 20.127, draw:fill-image-ref-point-y

- a. *The standard defines the attribute draw:fill-image-ref-point-y, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-image-ref-point-y, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:fill-image-ref-point-y, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### 2.1.1075 Part 3 Section 20.128, draw:fill-image-width

- a. *The standard defines the attribute draw:fill-image-width, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- b. *The standard defines the attribute draw:fill-image-width, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- c. *The standard defines the attribute draw:fill-image-width, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

### **2.1.1076 Part 3 Section 20.129, draw:fit-to-contour**

- a. *The standard defines the attribute draw:fit-to-contour, contained within the element <style:graphic-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `draw:fit-to-contour`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `draw:fit-to-contour`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

## **2.1.1077 Part 3 Section 20.130, `draw:fit-to-size`**

- a. *The standard defines the attribute `draw:fit-to-size`, contained within the element `<style:graphic-properties>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.



- b. *The standard defines the attribute `draw:fit-to-size`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `draw:fit-to-size`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1078 Part 3 Section 20.131, `draw:frame-display-border`**

- a. *The standard defines the attribute `draw:frame-display-border`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:frame-display-border`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:frame-display-border`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1079 Part 3 Section 20.132, `draw:frame-margin-horizontal`**

- a. *The standard defines the attribute `draw:frame-margin-horizontal`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:frame-margin-horizontal`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:frame-margin-horizontal`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1080 Part 3 Section 20.133, `draw:frame-display-scrollbar`**

- a. *The standard defines the attribute `draw:frame-display-scrollbar`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:frame-display-scrollbar`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:frame-display-scrollbar`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1081 Part 3 Section 20.134, `draw:frame-margin-vertical`**

- a. *The standard defines the attribute `draw:frame-margin-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:frame-margin-vertical`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:frame-margin-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1082 Part 3 Section 20.135, `draw:gamma`**

- a. *The standard defines the attribute `draw:gamma`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the attribute `draw:gamma`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the attribute `draw:gamma`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

### **2.1.1083 Part 3 Section 20.136, `draw:green`**

- a. *The standard defines the attribute `draw:green`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the attribute `draw:green`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the attribute `draw:green`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

### **2.1.1084 Part 3 Section 20.137, `draw:gradient-step-count`**

- a. *The standard defines the attribute `draw:gradient-step-count`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:gradient-step-count`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:gradient-step-count`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

#### **2.1.1085 Part 3 Section 20.138, draw:guide-distance**

- a. *The standard defines the attribute `draw:guide-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:guide-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:guide-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1086 Part 3 Section 20.139, draw:guide-overhang**

- a. *The standard defines the attribute `draw:guide-overhang`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:guide-overhang`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:guide-overhang`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1087 Part 3 Section 20.140, `draw:image-opacity`**

- a. *The standard defines the attribute `draw:image-opacity`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- b. *The standard defines the attribute `draw:image-opacity`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- c. *The standard defines the attribute `draw:image-opacity`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

### **2.1.1088 Part 3 Section 20.141, `draw:line-distance`**

- a. *The standard defines the attribute `draw:line-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:line-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:line-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1089 Part 3 Section 20.142, `draw:luminance`**

- a. *The standard defines the attribute `draw:luminance`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

- b. *The standard defines the attribute `draw:luminance`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

- c. *The standard defines the attribute `draw:luminance`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

### **2.1.1090 Part 3 Section 20.143, `draw:marker-end`**

- a. *The standard defines the attribute `draw:marker-end`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to one of the following elements:

- `<draw:line>`
- `<draw:connector>`
- `<draw:measure>`

- b. *The standard defines the attribute `draw:marker-end`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-end`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

### **2.1.1091 Part 3 Section 20.144, `draw:marker-end-center`**

- a. *The standard defines the attribute `draw:marker-end-center`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- b. *The standard defines the attribute `draw:marker-end-center`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-end-center`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

### **2.1.1092 Part 3 Section 20.145, `draw:marker-end-width`**

- a. *The standard defines the attribute `draw:marker-end-width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- b. *The standard defines the attribute `draw:marker-end-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-end-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

### **2.1.1093 Part 3 Section 20.146, `draw:marker-start`**

- a. *The standard defines the attribute `draw:marker-start`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- b. *The standard defines the attribute `draw:marker-start`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-start`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

### **2.1.1094 Part 3 Section 20.147, `draw:marker-start-center`**

- a. *The standard defines the attribute `draw:marker-start-center`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- b. *The standard defines the attribute `draw:marker-start-center`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-start-center`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

### **2.1.1095 Part 3 Section 20.148, `draw:marker-start-width`**

- a. *The standard defines the attribute `draw:marker-start-width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- b. *The standard defines the attribute `draw:marker-start-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-start-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

#### **2.1.1096 Part 3 Section 20.149, `draw:measure-align`**

- a. *The standard defines the attribute `draw:measure-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:measure-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:measure-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1097 Part 3 Section 20.150, `draw:measure-vertical-align`**

- a. *The standard defines the attribute `draw:measure-vertical-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:measure-vertical-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:measure-vertical-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1098 Part 3 Section 20.151, `draw:ole-draw-aspect`**

- a. *The standard defines the attribute `draw:ole-draw-aspect`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

- b. *The standard defines the attribute `draw:ole-draw-aspect`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.



*This attribute was deprecated in the ODF 1.2 standard.*

- c. *The standard defines the attribute `draw:ole-draw-aspect`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

*This attribute was deprecated in the ODF 1.2 standard.*

### **2.1.1099 Part 3 Section 20.153, `draw:opacity-name`**

- a. *The standard defines the attribute `draw:opacity-name`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- b. *The standard defines the attribute `draw:opacity-name`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:opacity-name`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`

- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

#### **2.1.1100 Part 3 Section 20.154, draw:parallel**

- a. *The standard defines the attribute draw:parallel, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:parallel, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:parallel, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1101 Part 3 Section 20.155, draw:placing**

- a. *The standard defines the attribute draw:placing, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:placing, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:placing, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1102 Part 3 Section 20.156, draw:red**

- a. *The standard defines the attribute draw:red, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the attribute draw:red, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the attribute draw:red, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

### 2.1.1103 Part 3 Section 20.157, draw:secondary-fill-color

- a. *The standard defines the attribute draw:secondary-fill-color, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:secondary-fill-color, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:secondary-fill-color, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

### 2.1.1104 Part 3 Section 20.158, draw:shadow

- a. *The standard defines the attribute draw:shadow, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:shadow, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:shadow, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1105 Part 3 Section 20.159, draw:shadow-color**

- a. *The standard defines the attribute draw:shadow-color, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:shadow-color`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:shadow-color`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1106 Part 3 Section 20.160, `draw:shadow-offset-x`**

- a. *The standard defines the attribute `draw:shadow-offset-x`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:shadow-offset-x, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:shadow-offset-x, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

## 2.1.1107 Part 3 Section 20.161, draw:shadow-offset-y

- a. *The standard defines the attribute draw:shadow-offset-y, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:shadow-offset-y, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:shadow-offset-y, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>

- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1108 Part 3 Section 20.162, draw:shadow-opacity**

- a. *The standard defines the attribute draw:shadow-opacity, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:shadow-opacity, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:shadow-opacity, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>



- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1109 Part 3 Section 20.163, draw:show-unit**

- a. *The standard defines the attribute draw:show-unit, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:show-unit, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:show-unit, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1110 Part 3 Section 20.164, draw:start-guide**

- a. *The standard defines the attribute draw:start-guide, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:start-guide, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:start-guide, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1111 Part 3 Section 20.165, draw:start-line-spacing-horizontal**

- a. *The standard defines the attribute draw:start-line-spacing-horizontal, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:start-line-spacing-horizontal, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:start-line-spacing-horizontal, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1112 Part 3 Section 20.166, draw:start-line-spacing-vertical**

- a. *The standard defines the attribute `draw:start-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `draw:start-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:start-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1113 Part 3 Section 20.167, draw:stroke**

- a. *The standard defines the attribute `draw:stroke`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` containing a `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

On save, stroke styles are converted to a solid line when applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:custom-shape>`
- `<draw:text-box>`
- `<draw:frame>` element containing a `<draw:text-box>` element

- b. *The standard defines the attribute `draw:stroke`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

If the stroke is applied to a <draw:line> or <draw:connector> element with zero width, the stroke style will be lost and will be converted to a solid stroke style on load into Excel.

If an ODS file is saved as XLS format from Excel, the stroke style will be lost and will become a solid line.

- c. *The standard defines the attribute `draw:stroke`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

If the stroke is applied to a <draw:line> or <draw:connector> element with zero width, the stroke style will be lost and will be converted to a solid stroke style on load into PowerPoint.

#### **2.1.1114 Part 3 Section 20.169, draw:stroke-dash-names**

- a. *The standard defines the attribute `draw:stroke-dash-names`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:stroke-dash-names`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:stroke-dash-names`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1115 Part 3 Section 20.170, `draw:stroke-linejoin`**

- a. *The standard defines the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>

- <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
  - <draw:custom-shape>
- b. *The standard defines the property "bevel", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
  - <draw:line>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:connector>
  - <draw:caption>
  - <draw:measure>
  - <draw:g>
  - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
  - <draw:custom-shape>
- c. *The standard defines the property "inherit", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing a <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

Word interprets this enumeration as "miter".

- d. *The standard defines the property "middle", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Word interprets this enumeration as "miter".

- e. *The standard defines the property "miter", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- f. *The standard defines the property "none", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Word interprets this enumeration as "round".

- g. *The standard defines the property "round", contained within the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to the following elements:

- `<draw:rect>`
  - `<draw:line>`
  - `<draw:polyline>`
  - `<draw:polygon>`
  - `<draw:regular-polygon>`
  - `<draw:path>`
  - `<draw:circle>`
  - `<draw:ellipse>`
  - `<draw:connector>`
  - `<draw:caption>`
  - `<draw:measure>`
  - `<draw:g>`
  - `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
  - `<draw:custom-shape>`
- h. *The standard defines the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
  - `<draw:line>`
  - `<draw:polyline>`
  - `<draw:polygon>`
  - `<draw:regular-polygon>`
  - `<draw:path>`
  - `<draw:circle>`
  - `<draw:ellipse>`
  - `<draw:connector>`
  - `<draw:caption>`
  - `<draw:measure>`
  - `<draw:g>`
  - `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
  - `<draw:custom-shape>`
- i. *The standard defines the property "bevel", contained within the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this enum for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`

- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
  - <draw:custom-shape>
- j. *The standard defines the property "inherit", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Excel interprets this enumeration as "miter".

- k. *The standard defines the property "middle", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Excel interprets this enumeration as "miter".

- l. *The standard defines the property "miter", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>



- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- m. *The standard defines the property "none", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Excel interprets this enumeration as "round".

- n. *The standard defines the property "round", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- o. *The standard defines the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- p. *The standard defines the property "bevel", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- q. *The standard defines the property "inherit", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

PowerPoint interprets this enumeration as "miter".

- r. *The standard defines the property "middle", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

PowerPoint interprets this enumeration as "miter".

- s. *The standard defines the property "miter", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- t. *The standard defines the property "none", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

PowerPoint interprets this enumeration as "round".

- u. *The standard defines the property "round", contained within the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
- `<draw:custom-shape>`

### **2.1.1116 Part 3 Section 20.171, `svg:stroke-linecap`**

- a. *The standard defines the attribute `svg:stroke-linecap`, contained within the element `<style:graphic-properties>`*

If linecaps are present, the length of each dash is increased by the value of the line's width. Correspondingly, the value of the line's width is subtracted from the length of each gap.

Word 2021 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
- `<draw:custom-shape>`

- b. *The standard defines the attribute `svg:stroke-linecap`, contained within the element `<style:graphic-properties>`*

If linecaps are present, the length of each dash is increased by the value of the line's width. Correspondingly, the value of the line's width is subtracted from the length of each gap.

Excel 2021 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `svg:stroke-linecap`, contained within the element `<style:graphic-properties>`*

If linecaps are present, the length of each dash is increased by the value of the line's width. Correspondingly, the value of the line's width is subtracted from the length of each gap.

PowerPoint 2021 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1117 Part 3 Section 20.172, draw:symbol-color**

- a. *The standard defines the attribute `draw:symbol-color`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:symbol-color`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:symbol-color`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1118 Part 3 Section 20.173, `draw:textarea-horizontal-align`**

- a. *The standard defines the attribute `draw:textarea-horizontal-align`, contained within the element `<style:graphic-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The conversion between ODF anchoring properties (`draw:textarea-vertical-align` and `draw:textarea-horizontal-align`) and OOXML anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (`style:writing-mode` in ODF and "bodyPr vert" in OOXML). On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape.

- b. *The standard defines the attribute `draw:textarea-horizontal-align`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The conversion between anchoring properties in the standard ("draw:textarea-vertical-align" and "draw:textarea-horizontal-align") and OOXML anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode in the standard and "bodyPr vert" in OOXML).

On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to properties in the standard relative to the text box regardless of text direction within the shape.

On read, the reverse is true: anchoring values in the standard are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to OOXML relative to the text direction within the text box.

- c. *The standard defines the attribute draw:textarea-horizontal-align, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The conversion between ODF anchoring properties (draw:textarea-vertical-align and draw:textarea-horizontal-align) and PowerPoint anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode in ODF and "bodyPr vert" in PowerPoint). On write, PowerPoint anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape. On read, the reverse is true: ODF anchoring values are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to PowerPoint relative to the text direction within the text box.

### **2.1.1119 Part 3 Section 20.174, draw:textarea-vertical-align**

- a. *The standard defines the attribute draw:textarea-vertical-align, contained within the element <style:graphic-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The conversion between ODF anchoring properties ("draw:textarea-vertical-align" and "draw:textarea-horizontal-align") and OOXML anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes ("style:writing-mode" in ODF and "bodyPr vert" in OOXML). On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape.

- b. *The standard defines the attribute draw:textarea-vertical-align, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. The conversion between ODF anchoring properties (draw:textarea-vertical-align and draw:textarea-horizontal-align) and OOXML anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode in ODF and "bodyPr vert" in OOXML). On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape. On read, the reverse is true: ODF anchoring values are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to OOXML relative to the text direction within the text box.

- c. *The standard defines the attribute draw:textarea-vertical-align, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in <the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The conversion between ODF anchoring attributes (draw:textarea-vertical-align and draw:textarea-horizontal-align) and PowerPoint anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode attribute in ODF and "bodyPr vert" in PowerPoint). On write, PowerPoint anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape. On read, the reverse is true: ODF anchoring values are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to PowerPoint relative to the text direction within the text box.

### **2.1.1120 Part 3 Section 20.175, draw:tile-repeat-offset**

- a. *The standard defines the attribute draw:tile-repeat-offset, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>



- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute draw:tile-repeat-offset, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute draw:tile-repeat-offset, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

### **2.1.1121 Part 3 Section 20.176, draw:visible-area-height**

- a. *The standard defines the attribute draw:visible-area-height, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:visible-area-height*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:visible-area-height, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1122 Part 3 Section 20.177, draw:visible-area-left**

- a. *The standard defines the attribute draw:visible-area-left, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:visible-area-left*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:visible-area-left, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1123 Part 3 Section 20.178, draw:visible-area-top**

- a. *The standard defines the attribute draw:visible-area-top, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:visible-area-top*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:visible-area-top, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1124 Part 3 Section 20.179, draw:visible-area-width**

- a. *The standard defines the attribute draw:visible-area-width, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:visible-area-width*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute draw:visible-area-width, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1125 Part 3 Section 20.180, draw:unit**

- a. *The standard defines the attribute draw:unit, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute draw:unit, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `draw:unit`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1126 Part 3 Section 20.181, `draw:wrap-influence-on-position`**

- a. *The standard defines the attribute `draw:wrap-influence-on-position`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

### **2.1.1127 Part 3 Section 20.182, `fo:background-color`**

- a. *The standard defines the attribute `fo:background-color`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- b. *The standard defines the attribute `fo:background-color`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `fo:background-color`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

- d. *The standard defines the attribute `fo:background-color`, contained within the element `<style:paragraph-properties>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `fo:background-color`, contained within the element `<style:section-properties>`*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the attribute `fo:background-color`, contained within the element `<style:table-properties>`*

This attribute is supported in Word 2013 and later.

On load, Word reads and applies the `fo:background-color` attribute. On save, Word writes this attribute as a part of the cell style of each individual table cell in the table.

- g. *The standard defines the attribute `fo:background-color`, contained within the element `<style:table-row-properties>`*

This attribute is supported in Word 2013 and later.

On load, Word reads and applies the `fo:background-color` attribute. On save, Word writes this attribute as a part of the cell style of each individual table cell in the row.

- h. *The standard defines the attribute `fo:background-color`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- i. *The standard defines the attribute `fo:background-color`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- j. *The standard defines the attribute `fo:background-color`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `fo:background-color`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute `fo:background-color`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- m. *The standard defines the attribute `fo:background-color`, contained within the element `<style:section-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`

- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- n. *The standard defines the attribute fo:background-color, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- o. *The standard defines the attribute fo:background-color, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- p. *The standard defines the attribute fo:background-color, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- q. *The standard defines the attribute fo:background-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- r. *The standard defines the attribute fo:background-color, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- s. *The standard defines the attribute fo:background-color, contained within the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- t. *The standard defines the attribute fo:background-color, contained within the element <style:table-properties>*

- u. *The standard defines the attribute fo:background-color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1128 Part 3 Section 20.183.2, fo:border**

- a. *The standard defines the attribute fo:border, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute fo:border, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:border, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

Page borders with widths that cannot be generated by Word are normalized to the default border width.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- d. *The standard defines the attribute fo:border, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:border, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- f. *The standard defines the attribute fo:border, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- g. *The standard defines the attribute fo:border, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute fo:border, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:border, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute fo:border, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2013 and later.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: "groove", "ridge", "inset", and "outset". These styles map to a "solid" border type.

On save Excel maps border length as follows: medium and medium dashed borders map to a 2.0 pt border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- k. *The standard defines the attribute fo:border, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- l. *The standard defines the attribute fo:border, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- m. *The standard defines the attribute fo:border, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:



- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:text-box>
  - <draw:frame>
  - <draw:custom-shape>.
- n. *The standard defines the attribute fo:border, contained within the element <style:table-cell-properties>*

### **2.1.1129 Part 3 Section 20.183.3, fo:border-bottom**

- a. *The standard defines the attribute fo:border-bottom, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute fo:border-bottom, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:border-bottom, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

Page borders with widths that cannot be generated by Word are normalized to the default border width.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- d. *The standard defines the attribute fo:border-bottom, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `fo:border-bottom`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
  - Word supports all values for color.
- f. *The standard defines the attribute `fo:border-bottom`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements. Supported if the `fo:border-top`, `fo:border-bottom`, `fo:border-left`, and `fo:border-right` attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- g. *The standard defines the attribute `fo:border-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `fo:border-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `fo:border-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- j. *The standard defines the attribute `fo:border-bottom`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Excel 2013 and later.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- k. *The standard defines the attribute fo:border-bottom, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- l. *The standard defines the attribute fo:border-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1130 Part 3 Section 20.183.4, fo:border-left**

- a. *The standard defines the attribute fo:border-left, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute fo:border-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:border-left, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

Page borders with widths that cannot be generated by Word are normalized to the default border width.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
  - Word supports all values for color.
- d. *The standard defines the attribute fo:border-left, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:border-left, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- f. *The standard defines the attribute fo:border-left, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- g. *The standard defines the attribute fo:border-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute fo:border-left, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:border-left, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute fo:border-left, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2013 and later.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- k. *The standard defines the attribute fo:border-left, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. This attribute is supported if the attributes named fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right all have the same value. Otherwise, the attributes are ignored and a default border is applied.

- l. *The standard defines the attribute fo:border-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1131 Part 3 Section 20.183.5, fo:border-right

- a. *The standard defines the attribute fo:border-right, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute fo:border-right, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:border-right, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

Page borders with widths that cannot be generated by Word are normalized to the default border width.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- d. *The standard defines the attribute fo:border-right, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:border-right, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
  - Word supports all values for color.
- f. *The standard defines the attribute fo:border-right, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- g. *The standard defines the attribute fo:border-right, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute fo:border-right, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:border-right, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute fo:border-right, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2013 and later.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- k. *The standard defines the attribute fo:border-right, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. This attribute is supported if the attributes named fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right all have the same value. Otherwise, the attributes are ignored and a default border is applied.

- l. *The standard defines the attribute fo:border-right, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1132 Part 3 Section 20.183.6, fo:border-top**

- a. *The standard defines the attribute fo:border-top, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute fo:border-top, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:border-top, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

Page borders with widths that cannot be generated by Word are normalized to the default border width.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".



- Word supports all values for color.
- d. *The standard defines the attribute fo:border-top, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:border-top, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2013 and later.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- f. *The standard defines the attribute fo:border-top, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- g. *The standard defines the attribute fo:border-top, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute fo:border-top, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:border-top, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:frame>
  - <draw:text-box>
  - <draw:custom-shape>
- j. *The standard defines the attribute fo:border-top, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2013 and later.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- k. *The standard defines the attribute fo:border-top, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- l. *The standard defines the attribute fo:border-top, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1133 Part 3 Section 20.184, fo:break-after**

- a. *The standard defines the attribute fo:break-after, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:break-after, contained within the element <style:table-column-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:break-after, contained within the element <style:table-properties>*

This attribute is supported in Word 2013 and later.

On load, Word applies the fo:break-after attribute to the document as a page break (after the table) that is separate from the table.

- d. *The standard defines the attribute fo:break-after, contained within the element <style:table-row-properties>*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute fo:break-after, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute fo:break-after, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute fo:break-after, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
  - <draw:text-box>
  - <draw:frame>
  - <draw:custom-shape>.
- h. *The standard defines the attribute fo:break-after, contained within the element <style:table-column-properties>*
- i. *The standard defines the attribute fo:break-after, contained within the element <style:table-properties>*
- j. *The standard defines the attribute fo:break-after, contained within the element <style:table-row-properties>*

### **2.1.1134 Part 3 Section 20.185, fo:break-before**

- a. *The standard defines the attribute fo:break-before, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:break-before, contained within the element <style:table-column-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:break-before, contained within the element <style:table-properties>*

This attribute is supported in Word 2013 and later.

On load, Word applies the fo:break-before attribute to the document as a page break (before the table) that is separate from the table.

- d. *The standard defines the attribute fo:break-before, contained within the element <style:table-row-properties>*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute fo:break-before, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute fo:break-before, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute fo:break-before, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- h. *The standard defines the attribute fo:break-before, contained within the element <style:table-column-properties>*

- i. *The standard defines the attribute fo:break-before, contained within the element <style:table-properties>*

- j. *The standard defines the attribute fo:break-before, contained within the element <style:table-row-properties>*

### **2.1.1135 Part 3 Section 20.186, fo:clip**

- a. *The standard defines the attribute fo:clip, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> element.

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- b. *The standard defines the property "auto", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- c. *The standard defines the property "rect(top, right, bottom, left)", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element. Word only supports lengths for "top", "bottom", "right", and "left" values and does not support 'auto'.

- d. *The standard defines the attribute fo:clip, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> element.

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> or a <draw:object-ole> element.

- e. *The standard defines the property "auto", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or a <draw:object-ole> element.

- f. *The standard defines the property "rect(top, right, bottom, left)", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or a <draw:object-ole> element. Excel only supports lengths for "top", "bottom", "right", and "left" values and does not support "auto".

- g. *The standard defines the attribute fo:clip, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> element.

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- h. *The standard defines the property "auto", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- i. *The standard defines the property "rect(top, right, bottom, left)", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element. PowerPoint only supports lengths for the "top", "bottom", "right", and "left" values and does not support "auto".

### **2.1.1136 Part 3 Section 20.187, fo:color**

- a. *The standard defines the attribute fo:color, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:color, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1137 Part 3 Section 20.189, fo:font-family**

- a. *The standard defines the attribute fo:font-family, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

When applying font to a run of text on load, if it isn't specified via the style:font-name attribute in the office:font-face-decls element at the top of the XML part, Word looks for the style:font-family attribute on the immediate style:text-properties element. If Word finds it, then the font is applied to the run of text.

This attribute is not supported for font specifications in a list style definition.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:font-family, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:font-family, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1138 Part 3 Section 20.190, fo:font-size**

- a. *The standard defines the attribute fo:font-size, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

Word does not support percentage font sizes for the font size attribute. If a percentage font-size is used for the font size attribute, the text becomes the same size as the parent style on load.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:font-size, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>



- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:font-size, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1139 Part 3 Section 20.191, fo:font-style**

- a. *The standard defines the attribute fo:font-style, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:font-style, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

On load, the values "italic" and "oblique" both map to a value of "italic".

On save, Excel writes only the values "normal" and "italic".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the property "oblique", contained within the attribute fo:font-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, and on save, Excel maps the fo:font-style attribute to italic.

- d. *The standard defines the attribute fo:font-style, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1140 Part 3 Section 20.192, fo:font-variant**

- a. *The standard defines the attribute fo:font-variant, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

If, on load, both text:font-variant="small-caps" and fo:text-transform="uppercase" are applied to the text span, then Word does not apply either property to the text.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:font-variant, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the property "normal", contained within the attribute fo:font-variant, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "small-caps", contained within the attribute fo:font-variant, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the attribute fo:font-variant, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## 2.1.1141 Part 3 Section 20.193, fo:font-weight

- a. *The standard defines the attribute fo:font-weight, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

Word does not support a gradient of font weights; it only supports the ability to turn bold on or off. On load, font weights from 100-500 map to "normal", and font weights from 600-900 map to "bold".

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, "bold" and "normal" are the only values written.

- b. *The standard defines the attribute fo:font-weight, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

On load, Excel maps the following values to the "Bold" font style: "bold", "400", "500", "600", "700", "800", and "900". Excel maps all other values to the "Regular" font style.

On save, Excel writes "bold" if the font style is "Bold" or "Bold Italic". Excel writes "normal" if the font style is "Regular" or "Italic".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the following values are read as "bold": "bold", "600", and "700". All other values are read as "normal". On save, the only values written are "bold" and "normal".

- c. *The standard defines the property "100", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- d. *The standard defines the property "200", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- e. *The standard defines the property "300", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- f. *The standard defines the property "400", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- g. *The standard defines the property "500", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- h. *The standard defines the property "600", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- i. *The standard defines the property "700", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- j. *The standard defines the property "800", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- k. *The standard defines the property "900", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- l. *The standard defines the attribute fo:font-weight, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on read for text that is contained in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the following values are read as "bold": "bold", "600", and "700". All other values are read as "normal".

On write, "bold" and "normal" are the only values written.

### 2.1.1142 Part 3 Section 20.194, fo:height

- a. *The standard defines the attribute fo:height, contained within the element <style:list-level-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- b. *The standard defines the attribute fo:height, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- c. *The standard defines the attribute fo:height, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1143 Part 3 Section 20.195, fo:hyphenate

- a. *The standard defines the attribute fo:hyphenate, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

Word has an auto-hyphenation property at the document level and a "do not hyphenate" property at the paragraph level. The ODF auto-hyphenation property is stored at the text property level.

On load, Word sets the document-level auto-hyphenation property to true. If a paragraph style is set to not to auto-hyphenate the current paragraph, then Word sets the paragraph-level "do not hyphenate" property to true. Otherwise, Word sets this property to false.

On save, Word always sets fo:hyphenate to true in the text properties of the default paragraph style. For each paragraph style in the document, Word sets fo:hyphenate to true or fo:hyphenate to false based on the value used in the default paragraph style.

Word does not support the fo:hyphenate property from any other styles that can contain a style:text-properties element. For example, if text is contained within a span that is within a paragraph, then Word ignores the value of fo:hyphenate defined by the span and applies the value defined by the paragraph.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenate, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt

- chart titles
  - labels
- c. *The standard defines the attribute fo:hyphenate, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1144 Part 3 Section 20.196, fo:hyphenation-keep**

- a. *The standard defines the attribute fo:hyphenation-keep, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later. [\[MS-DOCX\]](#) section 2.3.7 and [\[MS-DOCX\]](#) section 2.3.8.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-keep, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:hyphenation-keep, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:



- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1145 Part 3 Section 20.197, fo:hyphenation-ladder-count**

- a. *The standard defines the attribute fo:hyphenation-ladder-count, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-ladder-count, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:hyphenation-ladder-count, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1146 Part 3 Section 20.198, fo:hyphenation-push-char-count

- a. *The standard defines the attribute fo:hyphenation-push-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-push-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:hyphenation-push-char-count, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1147 Part 3 Section 20.199, fo:hyphenation-remain-char-count

- a. *The standard defines the attribute fo:hyphenation-remain-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-remain-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:hyphenation-remain-char-count, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1148 Part 3 Section 20.200, fo:keep-together

- a. *The standard defines the attribute fo:keep-together, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:keep-together, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:keep-together, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- d. *The standard defines the attribute fo:keep-together, contained within the element <style:table-row-properties>*

### 2.1.1149 Part 3 Section 20.201, fo:keep-with-next

- a. *The standard defines the attribute fo:keep-with-next, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:keep-with-next, contained within the element <style:table-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:keep-with-next, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute fo:keep-with-next, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute fo:keep-with-next, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- f. *The standard defines the attribute fo:keep-with-next, contained within the element <style:table-properties>*

### 2.1.1150 Part 3 Section 20.202, fo:language

- a. *The standard defines the attribute fo:language, contained within the element <style:text-properties>*

**OfficeArt Math** in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, and fo:language-complex attributes is used to populate the Excel lang attribute. Excel's altLang attribute is not populated on read.

### 2.1.1151 Part 3 Section 20.203, fo:letter-spacing

- a. *The standard defines the attribute fo:letter-spacing, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:letter-spacing, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>

- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:letter-spacing, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1152 Part 3 Section 20.204, fo:line-height

- a. *The standard defines the attribute fo:line-height, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:line-height, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:line-height, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1153 Part 3 Section 20.205, fo:margin**

- a. *The standard defines the attribute fo:margin, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:margin, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:margin, contained within the element <style:table-properties>*

This attribute is supported in Word 2013 and later.

Word only supports a left margin for tables. On load, the value for fo:margin is applied to the left margin for the table.

- e. *The standard defines the attribute fo:margin, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>



- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute fo:margin, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute fo:margin, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute fo:margin, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the attribute fo:margin, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute fo:margin, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:text-box>
  - <draw:frame>
  - <draw:custom-shape>
- k. *The standard defines the attribute fo:margin, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- l. *The standard defines the attribute fo:margin, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the attribute fo:margin, contained within the element <style:table-properties>*

### **2.1.1154 Part 3 Section 20.206, fo:margin-bottom**

- a. *The standard defines the attribute fo:margin-bottom, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin-bottom, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:margin-bottom, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:table-properties>`*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage value is always read as "0".

- g. *The standard defines the attribute fo:margin-bottom, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute fo:margin-bottom, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the attribute fo:margin-bottom, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- j. *The standard defines the attribute fo:margin-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage value is always read as "0".

- k. *The standard defines the attribute fo:margin-bottom, contained within the element <style:table-properties>*

### **2.1.1155 Part 3 Section 20.208, fo:margin-right**

- a. *The standard defines the attribute fo:margin-right, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:section-properties>`*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:table-properties>`*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Excel 2013 and later.

Excel maps this attribute to the indent value for text alignment.

On load, Excel only applies this attribute to the indent value for text alignment if the fo:text-align attribute is not specified, or either fo:margin-left has a value of "left" or fo:margin-right has a value of "right".

On save, Excel does not write this attribute if the alignment of the text is set to center or justified.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage values are not supported.

- h. *The standard defines the attribute fo:margin-right, contained within the element <style:section-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the attribute fo:margin-right, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute fo:margin-right, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- k. *The standard defines the attribute fo:margin-right, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- l. *The standard defines the attribute fo:margin-right, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage values are not supported.

- m. *The standard defines the attribute fo:margin-right, contained within the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- n. *The standard defines the attribute fo:margin-right, contained within the element <style:table-properties>*

## 2.1.1156 Part 3 Section 20.209, fo:margin-top

- a. *The standard defines the attribute fo:margin-top, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin-top, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:margin-top, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:margin-top, contained within the element <style:table-properties>*

This attribute is not supported in Word 2013 or later.

- e. *The standard defines the attribute fo:margin-top, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute fo:margin-top, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2013 and later.



On load, Excel reads the attributes in the <style:page-layout-properties> element and calculates values as follows:

The header size is set to the value of the fo:margin-top attribute.

The footer size is set to the value of the fo:margin-bottom attribute.

The right margin size is set to the value of the fo:margin-right attribute.

The left margin size is set to the value of the fo:margin-left attribute.

The top margin size is set:

- to the value of the fo:margin-top attribute and the value of the fo:margin-bottom attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.
- and to the value of fo:min-height attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.

The bottom margin size is set:

- to the value of the fo:margin-bottom attribute and the value of the fo:margin-top attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.
- and to the value of fo:min-height attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.

On save, Excel writes values for attributes in the <style:page-layout-properties> element as follows:

- Excel writes the fo:margin-top attribute as the value of the top margin size, or the header size, whichever is less.
- Excel writes the fo:margin-bottom attribute as the value of the bottom margin size or the footer size, whichever is less.
- Excel writes the fo:margin-left attribute as the value of the left margin size.
- Excel writes the fo:margin-right attribute as the value of the right margin size.

On save, Excel writes values for properties in the <style:header-footer-properties> element of the <style:header-style> element's as follows:

- Excel writes the fo:min-height attribute as the top margin size minus the header size. If this value is less than or equal to 0, the value is written as "0".
- Excel writes the fo:margin-left attribute as the left margin size.
- Excel writes the fo:margin-right attribute as the right margin size.
- Excel writes the fo:margin-bottom attribute as "0".

On save, Excel writes values for properties in the <style:footer-style> element's <style:header-footer-properties> element as follows:

Excel writes the fo:min-height attribute as the bottom margin size minus the footer size. If this value is less than or equal to 0, the value is written as "0".

Excel writes the fo:margin-left attribute as the left margin size.

Excel writes the fo:margin-right attribute as the value of the right margin size.

Excel writes the fo:margin-top as the value "0".

On save, Excel always writes the style:display attribute of the <style:header> element as "true".

On save, Excel always writes the style:display attribute of the <style:footer> element as "true".

- g. *The standard defines the attribute fo:margin-top, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage value is always read as "0".

- h. *The standard defines the attribute fo:margin-top, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:margin-top, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute fo:margin-top, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- k. *The standard defines the attribute fo:margin-top, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage value is always read as "0".

- l. *The standard defines the attribute fo:margin-top, contained within the element <style:table-properties>*

### **2.1.1157 Part 3 Section 20.214, fo:orphans**

- a. *The standard defines the attribute fo:orphans, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2013 and later.

On load and save, Word only supports a value of 2 lines for the fo:orphans attribute; all nonzero values for the fo:orphans attribute default to this value.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:orphans, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:orphans, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1158 Part 3 Section 20.215, fo:page-height**

- a. *The standard defines the attribute fo:page-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

### **2.1.1159 Part 3 Section 20.216, fo:page-width**

- a. *The standard defines the attribute fo:page-width, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

### **2.1.1160 Part 3 Section 20.217, fo:padding**

- a. *The standard defines the attribute fo:padding, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:padding, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:padding, contained within the element <style:paragraph-properties>*

Word 2013, Word 2016, and Word 2019 support this attribute for values up to 31pt (0.4305in) when the style:paragraph-properties element also has an fo:border attribute.

OfficeArt Math in Word 2013, Word 2016, and Word 2019 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:padding, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013, Word 2016, or Word 2019 .

- e. *The standard defines the attribute fo:padding, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute fo:padding, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute fo:padding, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute fo:padding, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the attribute fo:padding, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute fo:padding, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- l. *The standard defines the attribute fo:padding, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- l. *The standard defines the attribute fo:padding, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the attribute fo:padding, contained within the element <style:table-cell-properties>*

### **2.1.1161 Part 3 Section 20.218, fo:padding-bottom**

- a. *The standard defines the attribute fo:padding-bottom, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:padding-bottom, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`

- <draw:caption>
  - <draw:measure>
  - <draw:frame>
  - <draw:text-box>
  - <draw:custom-shape>
- h. *The standard defines the attribute fo:padding-bottom, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:padding-bottom, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute fo:padding-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1162 Part 3 Section 20.219, fo:padding-left**

- a. *The standard defines the attribute fo:padding-left, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.



- b. *The standard defines the attribute fo:padding-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute fo:padding-left, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:padding-left, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute fo:padding-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute fo:padding-left, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute fo:padding-left, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:frame>
  - <draw:text-box>
  - <draw:custom-shape>
- h. *The standard defines the attribute fo:padding-left, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:padding-left, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute fo:padding-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1163 Part 3 Section 20.220, fo:padding-right**

- a. *The standard defines the attribute fo:padding-right, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`

- <draw:frame>
  - <draw:text-box>
  - <draw:custom-shape>
- f. *The standard defines the attribute fo:padding-right, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute fo:padding-right, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- h. *The standard defines the attribute fo:padding-right, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1164 Part 3 Section 20.221, fo:padding-top**

- a. *The standard defines the attribute fo:padding-top, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:padding-top, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- e. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- g. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:frame>
  - <draw:text-box>
  - <draw:custom-shape>
- h. *The standard defines the attribute fo:padding-top, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:padding-top, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute fo:padding-top, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1165 Part 3 Section 20.222, fo:script**

- a. *The standard defines the attribute fo:script, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

## 2.1.1166 Part 3 Section 20.223, fo:text-align

- a. *The standard defines the attribute fo:text-align, contained within the element <style:list-level-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt.

- b. *The standard defines the attribute fo:text-align, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute fo:text-align, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- d. *The standard defines the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This attribute is supported in Excel 2013 and later.

On load, Excel reads the start value as meaning left and the end value as meaning right. On save, Excel does not use the start value or end value.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels.

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>

- `<draw:custom-shape>`

On load, the values "start" and "end" map to the values "left" or "right" in OOXML, depending on text direction. If the text direction cannot be determined, "start" is mapped to "left" and "end" is mapped to "right".

- e. *The standard defines the property "end", contained within the attribute `fo:text-align`, contained within the element `<style:paragraph-properties>`*

This property is not supported in Excel 2013 or later.

On load, Excel maps the "end" property to right alignment. On save, the "end" property is not used, and right alignment is mapped to the "right" property.

- f. *The standard defines the property "start", contained within the attribute `fo:text-align`, contained within the element `<style:paragraph-properties>`*

This property is not supported in Excel 2013 or later.

On load, Excel maps the "start" property to left alignment. On save, the "start" property is not used, and left alignment is mapped to the "left" property.

- g. *The standard defines the attribute `fo:text-align`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- h. *The standard defines the attribute `fo:text-align`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`



- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

On read, "start" and "end" map to either "left" or "right" in PowerPoint depending on text direction. If text direction cannot be determined, "start" is mapped to "left" and "end" is mapped to "right".

### 2.1.1167 Part 3 Section 20.224, fo:text-align-last

- a. *The standard defines the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the property "center", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the property "justify", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the property "start", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the property "center", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels.

- g. *The standard defines the property "justify", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels.

- h. *The standard defines the property "start", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. This property is written out but is not read in. It is always written as fo:text-align-last="start".

- i. *The standard defines the property "center", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:text-box>
  - <draw:frame>
  - <draw:custom-shape>.
- j. *The standard defines the property "justify", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- k. *The standard defines the property "start", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

This property is written out but is not read in. It is always written as fo:text-align-last="start".

### **2.1.1168 Part 3 Section 20.226, fo:text-shadow**

- a. *The standard defines the attribute fo:text-shadow, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:text-shadow, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

On load, Excel interprets size values greater than 0 to mean that text shadow is activated.

On save, Excel writes "1pt1pt" when text has a shadow, or "none" when text does not have a shadow.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the fo:text-shadow attribute is mapped to the <outerShdw> element of OOXML. Where there is no correspondence between the fo:text-shadow attribute and the <outerShdw> element, default values are used.

- c. *The standard defines the attribute fo:text-shadow, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the fo:text-shadow attribute is mapped to the PowerPoint <outerShdw> element with default values.

### **2.1.1169 Part 3 Section 20.227, fo:text-transform**

- a. *The standard defines the attribute fo:text-transform, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "capitalized", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Word 2013 or later.

- c. *The standard defines the property "lowercase", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Word 2013 or later.

- d. *The standard defines the attribute fo:text-transform, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. Excel does not support the value of "capitalize" for this attribute. When this attribute has a value of "capitalize", Excel interprets it as a value of "none".

- e. *The standard defines the property "capitalize", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- f. *The standard defines the property "lowercase", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- g. *The standard defines the property "none", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- h. *The standard defines the property "uppercase", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- i. *The standard defines the attribute fo:text-transform, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

PowerPoint does not support "fo:text-transform=capitalize" and interprets this as "fo:text-transform=none".

### 2.1.1170 Part 3 Section 20.228, fo:widows

- a. *The standard defines the attribute fo:widows, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2013 and later.

On load and save, Word only supports a value of 2 lines for the fo:widows attribute; all nonzero values for the fo:widows attribute default to this value.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:widows, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:widows, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1171 Part 3 Section 20.229, fo:width

- a. *The standard defines the attribute fo:width, contained within the element <style:list-level-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- b. *The standard defines the attribute fo:width, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:width, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
- <draw:custom-shape>.

### 2.1.1172 Part 3 Section 20.230, fo:wrap-option

- a. *The standard defines the attribute fo:wrap-option, contained within the element <style:graphic-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:wrap-option, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:wrap-option, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- d. *The standard defines the attribute fo:wrap-option, contained within the element <style:table-cell-properties>*



### **2.1.1173 Part 3 Section 20.233, presentation:display-date-time**

- a. *The standard defines the attribute presentation:display-date-time, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2013 and later.

On load, this attribute is read to determine whether to display the date and time. It is not written on save.

### **2.1.1174 Part 3 Section 20.234, presentation:display-footer**

- a. *The standard defines the attribute presentation:display-footer, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2013 and later.

On load, this attribute is read to determine whether to display the footer. It is not written on save.

### **2.1.1175 Part 3 Section 20.235, presentation:display-header**

- a. *The standard defines the attribute presentation:display-header, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2013 and later.

On load, this attribute is read to determine whether to display the header. It is not written on save.

### **2.1.1176 Part 3 Section 20.236, presentation:display-page-number**

- a. *The standard defines the attribute presentation:display-page-number, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2013 and later.

On load, this attribute is read to determine whether to display the page number. It is not written on save.

### **2.1.1177 Part 3 Section 20.238, presentation:transition-speed**

- a. *The standard defines the property "medium", contained within the attribute presentation:transition-speed, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

The default value for the transition speed is "medium".

### **2.1.1178 Part 3 Section 20.239, presentation:transition-style**

- a. *The standard defines the property "close", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- b. *The standard defines the property "fade-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- c. *The standard defines the property "fade-from-center", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- d. *The standard defines the property "fade-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- e. *The standard defines the property "fade-from-lowerleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- f. *The standard defines the property "fade-from-lowerright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- g. *The standard defines the property "fade-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- h. *The standard defines the property "fade-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- i. *The standard defines the property "fade-from-upperleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- j. *The standard defines the property "fade-from-upperright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- k. *The standard defines the property "fade-to-center", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- l. *The standard defines the property "fly-away", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- m. *The standard defines the property "horizontal-stripes", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- n. *The standard defines the property "interlocking-horizontal-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- o. *The standard defines the property "interlocking-horizontal-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- p. *The standard defines the property "interlocking-vertical-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- q. *The standard defines the property "interlocking-vertical-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- r. *The standard defines the property "melt", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- s. *The standard defines the property "move-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- t. *The standard defines the property "move-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- u. *The standard defines the property "move-from-lowerleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- v. *The standard defines the property "move-from-lowerright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- w. *The standard defines the property "move-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- x. *The standard defines the property "move-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- y. *The standard defines the property "move-from-upperleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- z. *The standard defines the property "move-from-upperright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.
- aa. *The standard defines the property "open", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- bb. *The standard defines the property "spiralin-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- cc. *The standard defines the property "spiralin-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- dd. *The standard defines the property "spiralout-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- ee. *The standard defines the property "spiralout-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- ff. *The standard defines the property "stretch-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- gg. *The standard defines the property "stretch-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- hh. *The standard defines the property "stretch-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- ii. *The standard defines the property "stretch-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- jj. *The standard defines the property "vertical-stripes", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- kk. *The standard defines the property "wavyline-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- ll. *The standard defines the property "wavyline-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- mm. *The standard defines the property "wavyline-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

- nn. *The standard defines the property "wavyline-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

### **2.1.1179 Part 3 Section 20.240, presentation:transition-type**

- a. *The standard defines the property "automatic", contained within the attribute presentation:transition-type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2013 and later.

On load, PowerPoint sets the manual value as well, permitting slides to be advanced manually in an automated presentation.

- b. *The standard defines the property "semi-automatic", contained within the attribute presentation:transition-type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2013 or later.

PowerPoint treats semi-automatic the same way as manual.

### **2.1.1180 Part 3 Section 20.246, style:auto-text-indent**

- a. *The standard defines the attribute style:auto-text-indent, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:auto-text-indent, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:auto-text-indent, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1181 Part 3 Section 20.247, style:background-transparency

- a. *The standard defines the attribute style:background-transparency, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:background-transparency, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:background-transparency, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1182 Part 3 Section 20.248, style:border-line-width

- a. *The standard defines the attribute style:border-line-width, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

Word ignores this property on load, but writes it out on save for double borders.

- d. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- g. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- j. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- l. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

- m. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1183 Part 3 Section 20.249, `style:border-line-width-bottom`**

- a. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element. Supported if `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

Word ignores this property on load, but writes it out on save for double borders.

- d. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:paragraph-properties>`*



This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements. This attribute is supported if the attributes named `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- g. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- j. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` attributes. This attribute is supported if the attributes named `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-`

line-width-left, and style:border-line-width-right all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- l. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- m. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.1184 Part 3 Section 20.250, style:border-line-width-left**

- a. *The standard defines the attribute style:border-line-width-left, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute style:border-line-width-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:border-line-width-left, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

Word ignores this property on load, but writes it out on save for double borders.

- d. *The standard defines the attribute style:border-line-width-left, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute style:border-line-width-left, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing one of the following elements:

- `<draw:image>`
- `<draw:text-box>`
- `<draw:object-ole>`

This attribute is supported if the attributes named `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- g. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- j. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing one of the following elements:

- `<draw:image>`
- `<draw:text-box>`
- `<draw:object-ole>`

This attribute is supported if the attributes named `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- l. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- m. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:table-cell-properties>`*

### **2.1.1185 Part 3 Section 20.251, `style:border-line-width-right`**

- a. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element. Supported if `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

Word ignores this property on load, but writes it out on save for double borders.

- d. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing one of the following elements:

- `<draw:image>`
- `<draw:text-box>`
- `<draw:object-ole>`

This attribute is supported if the attributes named `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- g. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- j. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing one of the following elements:

- `<draw:image>`
- `<draw:text-box>`
- `<draw:object-ole>`

This attribute is supported if the attributes named `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- l. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

- m. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1186 Part 3 Section 20.252, `style:border-line-width-top`**

- a. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element. Supported if `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- b. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

Word ignores this property on load, but writes it out on save for double borders

- d. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements. This attribute is supported if the elements named `<style:border-line-width-top>`, `<style:border-line-width-bottom>`, `<style:border-line-width-left>`, and `<style:border-line-width-right>` all have the same value. Otherwise, these elements are ignored and a default border is applied.

- g. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

- h. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- j. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- k. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements. This attribute is supported if the attributes named `style:border-line-width-top`, `style:border-line-width-bottom`, `style:border-line-width-left`, and `style:border-line-width-right` all have the same value. Otherwise, these elements are ignored and a default border is applied.

- l. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

- m. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1187 Part 3 Section 20.253, `style:cell-protect`**

- a. *The standard defines the attribute `style:cell-protect`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:cell-protect`, contained within the element `<table:table>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:cell-protect`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the attribute `style:cell-protect`, contained within the element `<style:table-cell-properties>`*

### **2.1.1188 Part 3 Section 20.255, `style:contextual-spacing`**

- a. *The standard defines the attribute `style:contextual-spacing` within the element `<style:paragraph-properties>`*

This attribute is supported in Word 2021 and later.

### **2.1.1189 Part 3 Section 20.256, `style:country-asian`**

- a. *The standard defines the attribute `style:country-asian`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

On load, Word preserves the `style:country-asian` attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF



"fo:country", "style:country-asian" and "style:country-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:language", "fo:language-asian", and "fo:language-complex" attributes.

- b. *The standard defines the attribute style:country-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:country, style:country-asian, and style:country-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate fo:language, fo:language-asian, and fo:language-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the Excel lang property.

- c. *The standard defines the attribute style:country-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is

mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the PowerPoint lang property.

### **2.1.1190 Part 3 Section 20.257, style:country-complex**

- a. *The standard defines the attribute style:country-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load, Word preserves the style:country-complex attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:country", "style:country-asian" and "style:country-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:language", "fo:language-asian", and "fo:language-complex" attributes.

- b. *The standard defines the attribute style:country-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:country, style:country-asian, and style:country-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:language, fo:language-asian, and fo:language-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the Excel lang property.

- c. *The standard defines the attribute style:country-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the PowerPoint lang property.

#### **2.1.1191 Part 3 Section 20.258, style:decimal-places**

- a. *The standard defines the attribute style:decimal-places, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:decimal-places, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:decimal-places, contained within the element <style:table-cell-properties>*

#### **2.1.1192 Part 3 Section 20.259, style:diagonal-bl-tr**

- a. *The standard defines the attribute style:diagonal-bl-tr, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:diagonal-bl-tr, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2013 and later.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

#### **2.1.1193 Part 3 Section 20.260, style:diagonal-bl-tr-widths**

- a. *The standard defines the attribute style:diagonal-bl-tr-widths, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:diagonal-bl-tr-widths, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:diagonal-bl-tr-widths, contained within the element <style:table-cell-properties>*

#### **2.1.1194 Part 3 Section 20.261, style:diagonal-tl-br**

- a. *The standard defines the attribute style:diagonal-tl-br, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:diagonal-tl-br, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2013 and later.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

#### **2.1.1195 Part 3 Section 20.262, style:diagonal-tl-br-widths**

- a. *The standard defines the attribute style:diagonal-tl-br-widths, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:diagonal-tl-br-widths`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:diagonal-tl-br-widths`, contained within the element `<style:table-cell-properties>`*

### **2.1.1196 Part 3 Section 20.263, style:direction**

- a. *The standard defines the attribute `style:direction`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:direction`, contained within the element `<style:table-cell-properties>`*

### **2.1.1197 Part 3 Section 20.264, style:dynamic-spacing**

- a. *The standard defines the attribute `style:dynamic-spacing`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:dynamic-spacing`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2013 or later.

### **2.1.1198 Part 3 Section 20.265, style:editable**

- a. *The standard defines the attribute `style:editable`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:editable`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:editable`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1199 Part 3 Section 20.266, style:first-page-number**

- a. *The standard defines the attribute `style:first-page-number`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:first-page-number`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1200 Part 3 Section 20.267, style:flow-with-text**

- a. *The standard defines the attribute style:flow-with-text, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

### **2.1.1201 Part 3 Section 20.269, style:font-charset-asian**

- a. *The standard defines the attribute style:font-charset-asian, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-charset-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:font-charset-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1202 Part 3 Section 20.270, style:font-charset-complex

- a. *The standard defines the attribute style:font-charset-complex, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-charset-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:font-charset-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1203 Part 3 Section 20.271, style:font-family-asian

- a. *The standard defines the attribute style:font-family-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

When applying font to a run of text on load, if it isn't specified via the style:font-name-asian attribute in the office:font-face-decls element at the top of the XML part, Word looks for the style:font-family-asian attribute on the immediate style:text-properties element. If Word finds it, then the font is applied to the run of text.

This attribute is not supported for font specifications in a list style definition.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-family-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:font-family-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>



- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1204 Part 3 Section 20.272, style:font-family-complex

- a. *The standard defines the attribute style:font-family-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

When applying font to a run of text on load, if it isn't specified via the style:font-name attribute in the office:font-face-decls element at the top of the XML part, Word looks for the style:font-family attribute on the immediate style:text-properties element. If Word finds it, then the font is applied to the run of text.

This attribute is not supported for font specifications in a list style definition.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-family-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:font-family-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1205 Part 3 Section 20.274, style:font-family-generic-asian**

- a. *The standard defines the attribute style:font-family-generic-asian, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-family-generic-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:font-family-generic-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1206 Part 3 Section 20.275, style:font-family-generic-complex**

- a. *The standard defines the attribute style:font-family-generic-complex, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-family-generic-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:font-family-generic-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1207 Part 3 Section 20.276, style:font-independent-line-spacing**

- a. *The standard defines the attribute style:font-independent-line-spacing, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-independent-line-spacing, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:font-independent-line-spacing, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1208 Part 3 Section 20.277, style:font-name

- a. *The standard defines the attribute style:font-name, contained within the element <style:list-level-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- b. *The standard defines the attribute style:font-name, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:font-name, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- d. *The standard defines the attribute style:font-name, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On load, this attribute is used to specify font. On save, the fo:font-family attribute is used to specify font instead.

- e. *The standard defines the attribute style:font-name, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- f. *The standard defines the attribute style:font-name, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. On write, the "fo:font-family" property is used to specify font instead.

### **2.1.1209 Part 3 Section 20.278, style:font-name-asian**

- a. *The standard defines the attribute style:font-name-asian, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-name-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On load, this attribute is used to specify font. On save, the attribute `style:font-family-asian` is used to specify font instead.

- c. *The standard defines the attribute `style:font-name-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. On write, the `"style:font-family-asian"` property is used to specify font instead.

### **2.1.1210 Part 3 Section 20.279, `style:font-name-complex`**

- a. *The standard defines the attribute `style:font-name-complex`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-name-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On load, this attribute is used to specify font. On save, the attribute style:font-family-complex is used to specify font instead.

- c. *The standard defines the attribute style:font-name-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. On write, the "style:font-family-complex" property is used to specify font instead.

## **2.1.1211 Part 3 Section 20.281, style:font-pitch-asian**

- a. *The standard defines the attribute style:font-pitch-asian, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-pitch-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>



- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:font-pitch-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1212 Part 3 Section 20.282, style:font-pitch-complex**

- a. *The standard defines the attribute style:font-pitch-complex, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-pitch-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:font-pitch-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1213 Part 3 Section 20.283, style:font-relief**

- a. *The standard defines the property "embossed", contained within the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "engraved", contained within the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

- d. *The standard defines the property "embossed", contained within the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the property "engraved", contained within the attribute style:font-relief, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the property "embossed", contained within the attribute style:font-relief, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
  - <draw:frame>
  - <draw:custom-shape>.
- g. *The standard defines the property "engraved", contained within the attribute style:font-relief, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1214 Part 3 Section 20.284, style:font-size-asian**

- a. *The standard defines the attribute style:font-size-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

Word does not support percentage font sizes for the font size attribute. If a percentage font-size is used for the font size attribute, the text becomes the same size as the parent style on load.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-size-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes

- shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute `style:font-size-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1215 Part 3 Section 20.285, style:font-size-complex**

- a. *The standard defines the attribute `style:font-size-complex`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

Word does not support percentage font sizes for the font size attribute. If a percentage font-size is used for the font size attribute, the text becomes the same size as the parent style on load.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-size-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute `style:font-size-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1216 Part 3 Section 20.286, `style:font-size-rel`**

- a. *The standard defines the attribute `style:font-size-rel`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-size-rel`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute `style:font-size-rel`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1217 Part 3 Section 20.287, style:font-size-rel-asian**

- a. *The standard defines the attribute `style:font-size-rel-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-size-rel-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute `style:font-size-rel-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1218 Part 3 Section 20.288, style:font-size-rel-complex**

- a. *The standard defines the attribute `style:font-size-rel-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-size-rel-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:



- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute `style:font-size-rel-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1219 Part 3 Section 20.289, style:font-style-asian**

- a. *The standard defines the attribute `style:font-style-asian`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-style-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt

- chart titles
  - labels
- c. *The standard defines the attribute `style:font-style-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1220 Part 3 Section 20.290, `style:font-style-complex`**

- a. *The standard defines the attribute `style:font-style-complex`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-style-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:font-style-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1221 Part 3 Section 20.291, `style:font-style-name`**

- a. *The standard defines the attribute `style:font-style-name`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-style-name`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:font-style-name`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1222 Part 3 Section 20.292, `style:font-style-name-asian`**

- a. *The standard defines the attribute `style:font-style-name-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-style-name-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:font-style-name-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1223 Part 3 Section 20.293, `style:font-style-name-complex`**

- a. *The standard defines the attribute `style:font-style-name-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-style-name-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:font-style-name-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1224 Part 3 Section 20.294, `style:font-weight-asian`**

- a. *The standard defines the attribute `style:font-weight-asian`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

Word does not support a gradient of font weights; it only supports the ability to turn bold on or off. On load, font weights from 100-500 map to "normal", and font weights from 600-900 map to "bold".

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, "bold" and "normal" are the only values written.

- b. *The standard defines the attribute `style:font-weight-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the following values are read as "bold": "bold", "600", and "700". All other values are read as "normal". On save, the only values written are "bold" and "normal".

- c. *The standard defines the attribute `style:font-weight-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On read, the following values are read as "bold": "bold", "600", "700". All other values are read as "normal".

On write, "bold" and "normal" are the only values written.

### **2.1.1225 Part 3 Section 20.295, style:font-weight-complex**

- a. *The standard defines the attribute `style:font-weight-complex`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

Word does not support a gradient of font weights; it only supports the ability to turn bold on or off. On load, font weights from 100-500 map to "normal", and font weights from 600-900 map to "bold".

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, "bold" and "normal" are the only values written.

- b. *The standard defines the attribute `style:font-weight-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the following values are changed to "bold": "bold", "600", and "700". All other values are read as "normal". On save, the only values written are "bold" and "normal".

- c. *The standard defines the attribute `style:font-weight-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On read, the following values are read as "bold": "bold", "600", "700". All other values are read as "normal".

On write, "bold" and "normal" are the only values written.

### **2.1.1226 Part 3 Section 20.296, `style:footnote-max-height`**

- a. *The standard defines the attribute `style:footnote-max-height`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:footnote-max-height`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:footnote-max-height`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1227 Part 3 Section 20.297, `style:glyph-orientation-vertical`**

- a. *The standard defines the attribute `style:glyph-orientation-vertical`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the property "0", contained within the attribute `style:glyph-orientation-vertical`, contained within the element `<style:table-cell-properties>`*

This property is supported in Word 2013 and later.



- c. *The standard defines the property "0deg", contained within the attribute style:glyph-orientation-vertical, contained within the element <style:table-cell-properties>*

This property is supported in Word 2013 and later.

- d. *The standard defines the property "0rad", contained within the attribute style:glyph-orientation-vertical, contained within the element <style:table-cell-properties>*

This property is supported in Word 2013 and later.

- e. *The standard defines the attribute style:glyph-orientation-vertical, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- f. *The standard defines the attribute style:glyph-orientation-vertical, contained within the element <style:table-cell-properties>*

### **2.1.1228 Part 3 Section 20.299, style:horizontal-rel**

- a. *The standard defines the property "char", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- b. *The standard defines the property "frame", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- c. *The standard defines the property "frame-content", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- d. *The standard defines the property "frame-end-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- e. *The standard defines the property "frame-start-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- f. *The standard defines the property "page-end-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- g. *The standard defines the property "page-start-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- h. *The standard defines the property "paragraph-content", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- i. *The standard defines the property "paragraph-end-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- j. *The standard defines the property "paragraph-start-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

### **2.1.1229 Part 3 Section 20.300, style:join-border**

- a. *The standard defines the attribute style:join-border, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 and later.

- b. *The standard defines the attribute style:join-border, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 and later.

- c. *The standard defines the attribute style:join-border, contained within the element <style:paragraph-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### 2.1.1230 Part 3 Section 20.301, style:justify-single-word

- a. *The standard defines the attribute style:justify-single-word, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:justify-single-word, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:justify-single-word, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1231 Part 3 Section 20.302, style:language-asian

- a. *The standard defines the attribute style:language-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load, Word preserves the fo:language-asian property as a part of a country language id (as specified by BCP 47) applied to the text range.

If the language is missing, Word ignores both the language and country.

This attribute is supported in Word 2013 and later.

On load, Word preserves the fo:language-complex property as a part of a country language id (as specified by BCP 47) applied to the text range.

If the language is missing, Word ignores both the language and country.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:language", "fo:language-asian" and "fo:language-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:country", "style:country-asian", and "style:country-complex" attributes.

- b. *The standard defines the attribute style:language-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, and fo:language-complex attributes is used to populate the Excel lang attribute. Excel's altLang attribute is not populated on read.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, and fo:language-complex attributes is used to populate the Excel lang attribute. Excel's altLang attribute is not populated on read.

- c. *The standard defines the attribute style:language-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, or fo:language-complex attributes is used to populate the PowerPoint lang attribute. PowerPoint's altLang attribute is not populated on read.

### **2.1.1232 Part 3 Section 20.303, style:language-complex**

- a. *The standard defines the attribute style:language-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

### **2.1.1233 Part 3 Section 20.304, style:layout-grid-base-height**

- a. *The standard defines the attribute style:layout-grid-base-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

On load Word uses style:layout-grid-base-height and style:layout-grid-ruby-height properties to calculate the number of lines per page. If either of these properties is missing then style:layout-grid-lines is used. However, Word does not save the style:layout-grid-base-height property.

- b. *The standard defines the attribute style:layout-grid-base-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:layout-grid-base-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1234 Part 3 Section 20.306, style:layout-grid-color**

- a. *The standard defines the attribute style:layout-grid-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:layout-grid-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:layout-grid-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1235 Part 3 Section 20.307, style:layout-grid-display**

- a. *The standard defines the attribute style:layout-grid-display, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:layout-grid-display, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1236 Part 3 Section 20.308, style:layout-grid-lines**

- a. *The standard defines the attribute style:layout-grid-lines, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute style:layout-grid-lines, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1237 Part 3 Section 20.309, style:layout-grid-mode**

- a. *The standard defines the attribute style:layout-grid-mode, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute style:layout-grid-mode, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1238 Part 3 Section 20.310, style:layout-grid-print**

- a. *The standard defines the attribute style:layout-grid-print, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:layout-grid-print, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:layout-grid-print, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1239 Part 3 Section 20.311, style:layout-grid-ruby-below**

- a. *The standard defines the attribute style:layout-grid-ruby-below, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

In Word, ruby text is always displayed preceding the base text. If the text direction is vertical, ruby text is displayed to the left of the base text.

- b. *The standard defines the attribute style:layout-grid-ruby-below, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:layout-grid-ruby-below, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1240 Part 3 Section 20.312, style:layout-grid-ruby-height**

- a. *The standard defines the attribute style:layout-grid-ruby-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

On load Word uses style:layout-grid-ruby-height and style:layout-grid-base-height properties to calculate the number of lines per page. If either of these properties is missing then style:layout-grid-lines property is used. However, Word does not save the style:layout-grid-ruby-height property.

- b. *The standard defines the attribute style:layout-grid-ruby-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:layout-grid-ruby-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1241 Part 3 Section 20.313, style:layout-grid-snap-to**

- a. *The standard defines the attribute style:layout-grid-snap-to, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

### **2.1.1242 Part 3 Section 20.315, style:line-break**

- a. *The standard defines the attribute style:line-break, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:line-break, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:line-break, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>



- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1243 Part 3 Section 20.316, style:letter-kerning

- a. *The standard defines the attribute style:letter-kerning, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, all nonzero values are mapped to "true".

- b. *The standard defines the attribute style:letter-kerning, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, a value of "true" is mapped to a default integer. On save, all nonzero values are mapped to "true".

- c. *The standard defines the attribute style:letter-kerning, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, a "true" value is mapped to a default integer.

On write, all nonzero values are mapped to "true".

### 2.1.1244 Part 3 Section 20.317, style:line-height-at-least

- a. *The standard defines the attribute style:line-height-at-least, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:line-height-at-least, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:line-height-at-least, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1245 Part 3 Section 20.318, style:line-spacing

- a. *The standard defines the attribute style:line-spacing, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:line-spacing, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:line-spacing, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1246 Part 3 Section 20.319, style:may-break-between-rows

- a. *The standard defines the attribute style:may-break-between-rows, contained within the element <style:table-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:may-break-between-rows, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:may-break-between-rows`, contained within the element `<style:table-properties>`*

### **2.1.1247 Part 3 Section 20.320, `style:min-row-height`**

- a. *The standard defines the attribute `style:min-row-height`, contained within the element `<style:table-row-properties>`, contained within the parent element `<style:style>`*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute `style:min-row-height`, contained within the element `<style:table-row-properties>`*

### **2.1.1248 Part 3 Section 20.321, `style:mirror`**

- a. *The standard defines the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:text-box>` or `<draw:object-ole>` element.

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- b. *The standard defines the property "horizontal", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- c. *The standard defines the property "horizontal vertical", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- d. *The standard defines the property "horizontal-on-even", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- e. *The standard defines the property "horizontal-on-even vertical", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- f. *The standard defines the property "horizontal-on-odd", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- g. *The standard defines the property "horizontal-on-odd vertical", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- h. *The standard defines the property "none", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- i. *The standard defines the property "vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- j. *The standard defines the property "vertical horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- k. *The standard defines the property "vertical horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- l. *The standard defines the property "vertical horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- m. *The standard defines the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- n. *The standard defines the property "horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- o. *The standard defines the property "horizontal vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- p. *The standard defines the property "horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- q. *The standard defines the property "horizontal-on-even vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- r. *The standard defines the property "horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- s. *The standard defines the property "horizontal-on-odd vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- t. *The standard defines the property "none", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- u. *The standard defines the property "vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- v. *The standard defines the property "vertical horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- w. *The standard defines the property "vertical horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- x. *The standard defines the property "vertical horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- y. *The standard defines the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- z. *The standard defines the property "horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- aa. *The standard defines the property "horizontal vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- bb. *The standard defines the property "horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- cc. *The standard defines the property "horizontal-on-even vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- dd. *The standard defines the property "horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- ee. *The standard defines the property "horizontal-on-odd vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- ff. *The standard defines the property "none", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- gg. *The standard defines the property "vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- hh. *The standard defines the property "vertical horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- ii. *The standard defines the property "vertical horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- jj. *The standard defines the property "vertical horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

### **2.1.1249 Part 3 Section 20.326, style:number-wrapped-paragraphs**

- a. *The standard defines the attribute style:number-wrapped-paragraphs, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

### **2.1.1250 Part 3 Section 20.327, style:overflow-behavior**

- a. *The standard defines the attribute style:overflow-behavior, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

### **2.1.1251 Part 3 Section 20.328, style:page-number**

- a. *The standard defines the attribute style:page-number, contained within the element <style:paragraph-properties>*

This attribute is supported in Microsoft Office Word 2007 and later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:page-number, contained within the element <style:table-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:page-number, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>



- <draw:custom-shape>
- d. *The standard defines the attribute style:page-number, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:page-number, contained within the element <style:paragraph-properties>*

This attribute is not supported in PowerPoint 2013 or later.

OfficeArt Math in PowerPoint 2013 or later does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- f. *The standard defines the attribute style:page-number, contained within the element <style:table-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1252 Part 3 Section 20.329, style:paper-tray-name**

- a. *The standard defines the attribute style:paper-tray-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:paper-tray-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:paper-tray-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1253 Part 3 Section 20.330, style:print**

- a. *The standard defines the attribute style:print, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:print, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2013 and later.

On load, Excel only reads the following values: headers, grid, and annotations. On save, Excel only writes the following values: objects, charts, and drawings.

- c. *The standard defines the property "formulas", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "zero-values", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:print, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1254 Part 3 Section 20.331, style:print-content**

- a. *The standard defines the attribute style:print-content, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute style:print-content, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:print-content, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- d. *The standard defines the attribute style:print-content, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:print-content, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- f. *The standard defines the attribute style:print-content, contained within the element <style:table-cell-properties>*

#### **2.1.1255 Part 3 Section 20.332, style:print-page-order**

- a. *The standard defines the attribute style:print-page-order, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:print-page-order`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1256 Part 3 Section 20.333, style:print-orientation**

- a. *The standard defines the attribute `style:print-orientation`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in PowerPoint 2013 and later.

On load, PowerPoint ignores this attribute, but writes it out on save.

### **2.1.1257 Part 3 Section 20.334, style:protect**

- a. *The standard defines the attribute `style:protect`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:text-box>` or `<draw:object-ole>` element.

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- b. *The standard defines the property "content", contained within the attribute `style:protect`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- c. *The standard defines the property "content position", contained within the attribute `style:protect`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- d. *The standard defines the property "content size", contained within the attribute `style:protect`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- e. *The standard defines the property "none", contained within the attribute `style:protect`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- f. *The standard defines the property "position", contained within the attribute `style:protect`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- g. *The standard defines the property "position content", contained within the attribute `style:protect`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- h. *The standard defines the property "position size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- i. *The standard defines the property "size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- j. *The standard defines the property "size content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- k. *The standard defines the property "size position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- l. *The standard defines the attribute style:protect, contained within the element <style:section-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- m. *The standard defines the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- n. *The standard defines the property "content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- o. *The standard defines the property "content position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported when opening the file in Excel, content protection is not supported. After saving from Excel, the value of the style:protect attribute changes to "position size".

- p. *The standard defines the property "content size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported when opening the file in Excel,

content protection is not supported. After saving from Excel, the value of the style:protect attribute changes to "" and size protection is lost.

- q. *The standard defines the property "none", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- r. *The standard defines the property "position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into Excel. After saving from Excel, the value of the style:protect attribute changes to "position size".

- s. *The standard defines the property "position content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported on load into Excel. Content protection is not supported. After saving from Excel, the value of the style:protect attribute changes to "position size".

- t. *The standard defines the property "position size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- u. *The standard defines the property "size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into Excel. After saving from Excel, size protection is lost and the value of the style:protect attribute changes to "".

- v. *The standard defines the property "size content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported when opening the file in Excel, content protection is not supported. After saving from Excel, size protection is lost and the value of the style:protect attribute changes to "".

- w. *The standard defines the property "size position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. After saving from Excel, the value of the style:protect attribute changes to "position size".

- x. *The standard defines the attribute style:protect, contained within the element <style:section-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- y. *The standard defines the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- z. *The standard defines the property "content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- aa. *The standard defines the property "content position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

- bb. *The standard defines the property "content size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, size protection is lost and the value of the style:protect attribute changes to "".

- cc. *The standard defines the property "none", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- dd. *The standard defines the property "position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into PowerPoint. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

- ee. *The standard defines the property "position content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

- ff. *The standard defines the property "position size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- gg. *The standard defines the property "size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into PowerPoint. After saving from PowerPoint, size protection is lost and the value of the style:protect attribute changes to "".

- hh. *The standard defines the property "size content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, size protection is lost and the value of the style:protect attribute changes to "".

- ii. *The standard defines the property "size position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

- jj. *The standard defines the attribute style:protect, contained within the element <style:section-properties>*

This attribute is not supported in PowerPoint 2013 or later.

OfficeArt Math in PowerPoint 2013 or later does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## **2.1.1258 Part 3 Section 20.335, style:punctuation-wrap**

- a. *The standard defines the attribute style:punctuation-wrap, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:punctuation-wrap`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `style:punctuation-wrap`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1259 Part 3 Section 20.336, style:register-true**

- a. *The standard defines the attribute `style:register-true`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:register-true`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.



OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
  - <draw:polyline>
  - <draw:polygon>
  - <draw:regular-polygon>
  - <draw:path>
  - <draw:circle>
  - <draw:ellipse>
  - <draw:caption>
  - <draw:measure>
  - <draw:frame>
  - <draw:text-box>
  - <draw:custom-shape>
- c. *The standard defines the attribute `style:register-true`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1260 Part 3 Section 20.337, style:register-truth-ref-style-name**

- a. *The standard defines the attribute `style:register-truth-ref-style-name`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:register-truth-ref-style-name`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:register-truth-ref-style-name`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1261 Part 3 Section 20.338, style:rel-column-width**

- a. *The standard defines the attribute `style:rel-column-width`, contained within the element `<style:table-column-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:rel-column-width`, contained within the element `<style:table-column-properties>`, contained within the parent element `<style:style>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:rel-column-width`, contained within the element `<style:table-column-properties>`*

### **2.1.1262 Part 3 Section 20.340.2, `style:table-properties`**

- a. *The standard defines the attribute `style:rel-width`, contained within the element `<style:table-properties>`*

### **2.1.1263 Part 3 Section 20.342, `style:repeat-content`**

- a. *The standard defines the attribute `style:repeat-content`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:repeat-content`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Excel 2013 and later.

This attribute maps to the fill horizontal alignment property in Excel.

- c. *The standard defines the attribute `style:repeat-content`, contained within the element `<style:table-cell-properties>`*

### **2.1.1264 Part 3 Section 20.346, `style:rotation-align`**

- a. *The standard defines the attribute `style:rotation-align`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:rotation-align`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:rotation-align`, contained within the element `<style:table-cell-properties>`*

### **2.1.1265 Part 3 Section 20.347, `style:rotation-angle`**

- a. *The standard defines the attribute `style:rotation-angle`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:rotation-angle`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Excel 2013 and later.

Excel supports only values within these ranges: 0 - 90 and 270 - 360.

On load, Excel does not ignore values outside of these ranges. On save, Excel does not write the style:rotation-angle attribute if the style:direction attribute is the value "ttb".

- c. *The standard defines the attribute style:rotation-angle, contained within the element <style:table-cell-properties>*

## **2.1.1266 Part 3 Section 20.349, style:ruby-align**

- a. *The standard defines the attribute style:ruby-align, contained within the element <style:ruby-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "distribute-letter", contained within the attribute style:ruby-align*

This property is not supported in Excel 2013 or later.

- c. *The standard defines the property "right", contained within the attribute style:ruby-align*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the attribute style:ruby-align, contained within the element <style:ruby-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the attribute style:ruby-align, contained within the element <style:ruby-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- <draw:custom-shape>.

### 2.1.1267 Part 3 Section 20.350, style:ruby-position

- a. *The standard defines the attribute style:ruby-position, contained within the element <style:ruby-properties>*

This attribute is not supported in Word 2013 or later.

Word always displays Ruby text above the base text or to the left of the base text when text direction is vertical.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:ruby-position*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the property "above", contained within the attribute style:ruby-position*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "below", contained within the attribute style:ruby-position*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:ruby-position, contained within the element <style:ruby-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute style:ruby-position, contained within the element <style:ruby-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.1268 Part 3 Section 20.351, style:run-through**

- a. *The standard defines the property "background", contained within the attribute style:run-through, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

#### **2.1.1269 Part 3 Section 20.352, style:scale-to**

- a. *The standard defines the attribute style:scale-to, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:scale-to, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1270 Part 3 Section 20.353, style:scale-to-pages**

- a. *The standard defines the attribute style:scale-to-pages, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute style:scale-to-pages, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute style:scale-to-pages, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1271 Part 3 Section 20.356, style:script-asian**

- a. *The standard defines the attribute style:script-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

#### **2.1.1272 Part 3 Section 20.357, style:script-complex**

- a. *The standard defines the attribute style:script-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

## 2.1.1273 Part 3 Section 20.358, style:script-type

- a. *The standard defines the attribute style:script-type, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "latin", contained within the attribute style:script-type, contained within the element <style:text-properties>*

This property is supported in Word 2013 and later.

Word uses a Boolean setting to signal whether a range of text should be treated as a complex script or not.

On load, if style:script-type is "complex", then the text is tagged as complex script. If the script-type attribute is "asian" or "latin" then the text is tagged as "not complex". A value of "ignore" causes Word to ignore this attribute.

On save, if this Word property states that the text is "complex", then Word writes style:script-type="complex" to the file. Otherwise, nothing is written to the file for this attribute.

- c. *The standard defines the attribute style:script-type, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- d. *The standard defines the attribute style:script-type, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1274 Part 3 Section 20.359, style:shadow

- a. *The standard defines the attribute style:shadow, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element that contains one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

The style:shadow attribute is supported only when the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes are all the same value, or when the fo:border attribute is specified.

- b. *The standard defines the attribute style:shadow, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute style:shadow, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2013 and later.

All values for style:shadow property map to the default page border shadow in Word.

- d. *The standard defines the attribute style:shadow, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute style:shadow, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2013 or later.

- f. *The standard defines the attribute style:shadow, contained within the element <style:table-properties>*

This attribute is not supported in Word 2013 or later.

- g. *The standard defines the attribute style:shadow, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. The style:shadow attribute is supported only when the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes are all the same value, or when the fo:border attribute is specified.

- h. *The standard defines the attribute style:shadow, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2013 or later.

- i. *The standard defines the attribute style:shadow, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2013 or later.

- j. *The standard defines the attribute style:shadow, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute style:shadow, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2013 or later.

- l. *The standard defines the attribute style:shadow, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2013 or later.

- m. *The standard defines the attribute style:shadow, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element that contains one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

The style:shadow attribute is supported only when the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes are all the same value, or when the fo:border attribute is specified.



- n. *The standard defines the attribute `style:shadow`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

- o. *The standard defines the attribute `style:shadow`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- p. *The standard defines the attribute `style:shadow`, contained within the element `<style:table-cell-properties>`*

### **2.1.1275 Part 3 Section 20.360, `style:shrink-to-fit`**

- a. *The standard defines the attribute `style:shrink-to-fit`, contained within the element `<style:graphic-properties>`*

This attribute is supported in Word 2013 and later.

- b. *The standard defines the attribute `style:shrink-to-fit`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:shrink-to-fit`, contained within the element `<style:table-cell-properties>`*

### **2.1.1276 Part 3 Section 20.361, `style:snap-to-layout-grid`**

- a. *The standard defines the attribute `style:snap-to-layout-grid`, contained within the element `<style:paragraph-properties>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:snap-to-layout-grid`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:snap-to-layout-grid, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1277 Part 3 Section 20.362, style:tab-stop-distance**

- a. *The standard defines the attribute style:tab-stop-distance, contained within the element <style:paragraph-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:tab-stop-distance, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute `style:tab-stop-distance`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1278 Part 3 Section 20.363, `style:table-centering`**

- a. *The standard defines the attribute `style:table-centering`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:table-centering`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1279 Part 3 Section 20.364, `style:text-align-source`**

- a. *The standard defines the attribute `style:text-align-source`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `style:text-align-source`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `style:text-align-source`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1280 Part 3 Section 20.365, `style:text-autospace`**

- a. *The standard defines the attribute `style:text-autospace`, contained within the element `<style:paragraph-properties>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-autospace`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:text-autospace, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1281 Part 3 Section 20.366, style:text-blinking**

- a. *The standard defines the attribute style:text-blinking, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-blinking, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:text-blinking`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1282 Part 3 Section 20.367, `style:text-combine`**

- a. *The standard defines the attribute `style:text-combine`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "letters", contained within the attribute `style:text-combine`, contained within the element `<style:text-properties>`*

This property is not supported in Word 2013 or later.

- c. *The standard defines the attribute `style:text-combine`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- d. *The standard defines the attribute style:text-combine, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1283 Part 3 Section 20.368, style:text-combine-start-char**

- a. *The standard defines the attribute style:text-combine-start-char, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load and on save, Word supports the following characters for this attribute: "<", "{", "(", "[", ".".

If a character is used that Word does not recognize, Word uses the default "(" character.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-combine-start-char, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
  - shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute style:text-combine-start-char, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## **2.1.1284 Part 3 Section 20.369, style:text-combine-end-char**

- a. *The standard defines the attribute style:text-combine-end-char, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load and on save, Word supports the following characters for this attribute: ">", "}", ")", "]", " ".

If a character is used that Word does not recognize, Word uses the default ")" character.

Word requires the start and end characters be a matching set - for example, "<" and ">".

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-combine-end-char`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:text-combine-end-char`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1285 Part 3 Section 20.370, `style:text-emphasize`**

- a. *The standard defines the attribute `style:text-emphasize`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.



- b. *The standard defines the property "accent below", contained within the attribute style:text-emphasize, contained within the element <style:text-properties>*

This property is not supported in Word 2013 or later.

- c. *The standard defines the property "circle below", contained within the attribute style:text-emphasize, contained within the element <style:text-properties>*

This property is not supported in Word 2013 or later.

- d. *The standard defines the property "disc above", contained within the attribute style:text-emphasize, contained within the element <style:text-properties>*

This property is not supported in Word 2013 or later.

- e. *The standard defines the property "disc below", contained within the attribute style:text-emphasize, contained within the element <style:text-properties>*

This property is not supported in Word 2013 or later.

- f. *The standard defines the attribute style:text-emphasize, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute style:text-emphasize, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

## 2.1.1286 Part 3 Section 20.371, style:text-line-through-color

- a. *The standard defines the attribute style:text-line-through-color, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

On load and on save, Word always matches the current font color.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, this property is always written as "font-color" for strikethrough values that are not set to "none".

- b. *The standard defines the attribute style:text-line-through-color, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels.

The only value supported in OOXML for this attribute is the value of "font-color". On load, this attribute maps to a value of "font-color" when it does not have a value of "none". On save, this attribute maps to a value of "font-color" when it does not have a value of "none".

- c. *The standard defines the attribute style:text-line-through-color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the value for this property is always mapped as if it was "font-color" because this is the only value supported in PowerPoint.

On write, for non-"none" strikethrough values, this property is always written as "font-color".

### 2.1.1287 Part 3 Section 20.372, style:text-line-through-mode

- a. *The standard defines the attribute style:text-line-through-mode, contained within the element <style:text-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-line-through-mode, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

In Excel, line-through is equivalent to strikethrough.

On load, Excel ignores the "skip-white-space" value to apply strikethrough to all characters in the text run. On save, Excel does not write the style:text-line-through-mode attribute.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:text-line-through-mode, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### 2.1.1288 Part 3 Section 20.373, style:text-line-through-style

- a. *The standard defines the attribute style:text-line-through-style, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, any non-"none" value in OOXML is written to ODF as "solid" for this property.

- b. *The standard defines the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

On load, Excel maps the value "none" to no strikethrough, and all other enumeration values to solid strikethrough. On save, Excel maps solid strikethrough to the value "solid", and no strikethrough to the value "none".

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. Strikethrough line type values other than the value of "solid" are not supported in OOXML. On load, all enumerations that do not have a value of "none" are mapped to a value of "solid".

On save, this attribute is written as "solid" for all strikethrough line types that do not have a value of "none".

- c. *The standard defines the property "dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- d. *The standard defines the property "dot-dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- e. *The standard defines the property "dot-dot-dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- f. *The standard defines the property "dotted", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- g. *The standard defines the property "long-dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- h. *The standard defines the property "none", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

On load, Excel maps this property to no strikethrough. On save, Excel maps this property to "none".

- i. *The standard defines the property "solid", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- j. *The standard defines the property "wave", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- k. *The standard defines the attribute `style:text-line-through-style`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On read, all enumerations (except for "none") are mapped to solid strikethrough because other types of strikethrough lines are not supported in PowerPoint.

On write, any non-"none" value in PowerPoint is written to ODF as "solid" for this property.

### **2.1.1289 Part 3 Section 20.374, style:text-line-through-text**

- a. *The standard defines the attribute `style:text-line-through-text`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-line-through-text`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes

- shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute `style:text-line-through-text`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1290 Part 3 Section 20.375, `style:text-line-through-text-style`**

- a. *The standard defines the attribute `style:text-line-through-text-style`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-line-through-text-style`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes

- shapes
  - SmartArt
  - chart titles
  - labels
- c. *The standard defines the attribute `style:text-line-through-text-style`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1291 Part 3 Section 20.376, `style:text-line-through-type`**

- a. *The standard defines the attribute `style:text-line-through-type`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-line-through-type`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles



- labels
- c. *The standard defines the attribute `style:text-line-through-type`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1292 Part 3 Section 20.377, `style:text-line-through-width`**

- a. *The standard defines the attribute `style:text-line-through-width`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

On load, all widths, except 0 or 0%, are mapped to a default strikethrough width.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, this property is always written as "auto" for strikethrough values that are not set to "none".

- b. *The standard defines the attribute `style:text-line-through-width`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. OOXML does not support strikethrough widths. On load, this attribute maps as though it had a value of "auto".

On save, this attribute is written as "auto" when strikethrough does not have a value of "none".

- c. *The standard defines the attribute `style:text-line-through-width`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On read, the value for this property is always mapped as if it was "auto" because PowerPoint does not support strikethrough widths.

On write, for non-"none" strikethrough values, this property is always written as "auto".

### **2.1.1293 Part 3 Section 20.378, `style:text-outline`**

- a. *The standard defines the attribute `style:text-outline`, contained within the element `<style:text-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-outline`, contained within the element `<style:text-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:text-outline`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

#### **2.1.1294 Part 3 Section 20.379, `style:text-overline-color`**

- a. *The standard defines the attribute `style:text-overline-color`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

#### **2.1.1295 Part 3 Section 20.380, `style:text-overline-mode`**

- a. *The standard defines the attribute `style:text-overline-mode`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

#### **2.1.1296 Part 3 Section 20.381, `style:text-overline-style`**

- a. *The standard defines the attribute `style:text-overline-style`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

#### **2.1.1297 Part 3 Section 20.382, `style:text-overline-type`**

- a. *The standard defines the attribute `style:text-overline-type`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

#### **2.1.1298 Part 3 Section 20.383, `style:text-overline-width`**

- a. *The standard defines the attribute `style:text-overline-width`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2013 and later.

## 2.1.1299 Part 3 Section 20.384, style:text-position

- a. *The standard defines the attribute style:text-position, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

Word applies the style:text-position property as a vertical position change, with the following exceptions:

- If the second item in the style:text-position attribute string value is less than 67% then Word displays the text as subscripted or superscripted, instead of applying a vertical position change to the text.
- If the second item in the style:text-position attribute string value is greater than 67% and "sub" or "sup" is the first item in the string, then Word displays the text as subscripted or superscripted, instead of applying a vertical position change to the text.

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt. The vertical text position value is always written as a percentage.

- b. *The standard defines the attribute style:text-position, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

The following enumerations map to a superscript value of 33 percent:

- super
- super <positive percent>
- <positive percent>
- sub <negative percent>

The following enumerations map to a subscript value of -33 percent:

- sub
- sub <positive percent>
- <negative percent>
- super <negative percent>

Enumerations with a value of 0 percent map to the No Vertical Alignment Setting.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes and SmartArt, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On load, enumerations "sub" and "super" are mapped to default numerical values and the font height percentage value is not supported.

On save, the vertical text position value is always written as a percentage.

- c. *The standard defines the property "negative percent", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "negative percent" property maps to a value of -33 percent.

- d. *The standard defines the property "positive percent", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "positive percent" property maps to a value of 33 percent.

- e. *The standard defines the property "sub", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "sub" property maps to a value of -33 percent.

- f. *The standard defines the property "sub negative percent", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "sub<negative percent>" property maps to a value of -33 percent.

- g. *The standard defines the property "sub positive percent", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "sub<positive percent>" property maps to a value of -33 percent.

- h. *The standard defines the property "super", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "super" property maps to a value of 33 percent.

- i. *The standard defines the property "super negative percent", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "super<negative percent>" property maps to a value of -33 percent.

- j. *The standard defines the property "super positive percent", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2013 and later.

The "super<positive percent>" property maps to a value of 33 percent.

- k. *The standard defines the attribute style:text-position, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On load, enumerations "sub" and "super" are mapped to default numerical values, and the font height percentage value is not supported.

On save, the vertical text position value is always written as a percentage.

### **2.1.1300 Part 3 Section 20.385, style:text-rotation-angle**

- a. *The standard defines the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "0", contained within the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

This property is supported in Word 2013 and later.

On load, if both style:text-rotation-angle and style:text-combine are applied to the text span, then Word ignores the style:text-rotation-angle property.

- c. *The standard defines the property "270", contained within the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

This property is not supported in Word 2013 or later.

- d. *The standard defines the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>

- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1301 Part 3 Section 20.386, style:text-rotation-scale**

- a. *The standard defines the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

On load and on save, Excel does not read or write this attribute. Excel always renders rotated text such that the width of the text remains fixed.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the property "fixed", contained within the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- d. *The standard defines the property "line-height", contained within the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

- e. *The standard defines the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1302 Part 3 Section 20.387, style:text-scale**

- a. *The standard defines the attribute style:text-scale, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load, percentage values that are less than 1% are rounded up to 1%, and percentage values that are greater than 600% are rounded down to 600%.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-scale, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.



OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:text-scale, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1303 Part 3 Section 20.388, style:text-underline-color**

- a. *The standard defines the attribute style:text-underline-color, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-underline-color, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:text-underline-color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.1304 Part 3 Section 20.389, style:text-underline-mode**

- a. *The standard defines the attribute style:text-underline-mode, contained within the element <style:text-properties>*

This attribute is supported in Word 2013 and later.

On load and on save, Word only supports the style:text-underline-mode property when style:text-underline-style="solid".

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-underline-mode, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

On load, Excel ignores the "skip-white-space" value to apply underline to all characters in a text run. On save, Excel does not write the style:text-underline-mode attribute.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML.

- c. *The standard defines the attribute style:text-underline-mode, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are considered together to determine which enumeration to set for the u (Underline) run property attribute in PowerPoint.

### **2.1.1305 Part 3 Section 20.390, style:text-underline-style**

- a. *The standard defines the attribute style:text-underline-style, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-underline-style, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

On load, Excel maps the value "none" to "No Line Style". All other values of the attribute `style:text-underline-style` map to "Solid Line Style".

On save, Excel writes only the values "none" or "solid".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

On load, the attributes named `style:text-underline-type`, `style:text-underline-style`, `style:text-underline-width`, and the mode named `style:text-underline` are all used in determining which enumeration to set for the `u` (Underline) run attribute in OOXML.

On load, no underline is read if either the `style:text-underline-type` attribute or the `style:text-underline-style` attribute has a value of "none".

On load, an underline type with a value of "double" takes precedence over underline style. Only the enumeration values of "solid" and "wave" are supported for underline types with a value of "double" in OOXML. For example, if the `style:text-underline-type` attribute has a value of "double" and the `style:text-underline-style` attribute has a value that is anything other than "solid" or "wave", then the `style:text-underline-type` attribute is changed to "double" and the `style:text-underline-style` attribute is changed to "solid".

- c. *The standard defines the property "dash", contained within the attribute `style:text-underline-style`, contained within the element `<style:text-properties>`*

This property is not supported in Excel 2013 or later.

The property "dash" maps to "solid underline".

- d. *The standard defines the property "dot-dash", contained within the attribute `style:text-underline-style`, contained within the element `<style:text-properties>`*

This property is not supported in Excel 2013 or later.

The property "dot-dash" maps to "solid underline".

- e. *The standard defines the property "dot-dot-dash", contained within the attribute `style:text-underline-style`, contained within the element `<style:text-properties>`*

This property is not supported in Excel 2013 or later.

The property "dot-dot-dash" maps to "solid underline".

- f. *The standard defines the property "dotted", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

The property "dot-dot-dash" maps to "solid underline".

- g. *The standard defines the property "long-dash", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

The property "long-dash" maps to "solid underline".

- h. *The standard defines the property "wave", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2013 or later.

The property "long-dash" maps to "solid underline".

- i. *The standard defines the attribute style:text-underline-style, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and the mode named style:text-underline are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML.

On load, no underline is read if either the style:text-underline-type attribute or the style:text-underline-style attribute has a value of "none".

On load, an underline type with a value of "double" takes precedence over underline style. Only the enumeration values of "solid" and "wave" are supported for underline types with a value of "double" in OOXML. For example, if the style:text-underline-type attribute has a value of "double" and the style:text-underline-style attribute has a value that is anything other than "solid" or "wave", then the style:text-underline-type attribute is changed to "double" and the style:text-underline-style attribute is changed to "solid".

## 2.1.1306 Part 3 Section 20.391, style:text-underline-type

- a. *The standard defines the attribute style:text-underline-type, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-underline-type, contained within the element <style:text-properties>*

This attribute is supported in Excel 2013 and later.

On save, Excel converts its Single Accounting type to the value "single," and its Double Accounting type to the value "double".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML. On load, no underline is read if either the style:text-underline-type attribute or the style:text-underline-style attribute has a value of "none".

- c. *The standard defines the attribute style:text-underline-type, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the properties `style:text-underline-type`, `style:text-underline-style`, `style:text-underline-width`, and `style:text-underline-mode` are considered together to determine which enumeration to set for the `u` (Underline) run property attribute in PowerPoint.

On read, if either of the properties `"style:text-underline-type="none"` or `"style:text-underline-style="none"`, no underline is read.

### **2.1.1307 Part 3 Section 20.392, style:text-underline-width**

- a. *The standard defines the attribute `style:text-underline-width`, contained within the element `<style:text-properties>`*

Word 2013, Word 2016, and Word 2019 support this attribute for values of "auto", "bold", or "0".

- b. *The standard defines the attribute `style:text-underline-width`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2013 or later.

**OfficeArt Math** in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

On load, the attributes named `style:text-underline-type`, `style:text-underline-style`, `style:text-underline-width`, and `style:text-underline-mode` are all used in determining which enumeration to set for the `u` (Underline) run attribute in OOXML. On load, all enumerations that have values other than "bold" and "thick" are treated as having a value of "normal". On save, the only values written are "auto" and "bold".

- c. *The standard defines the attribute `style:text-underline-width`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On load, the style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are considered together to determine which enumeration to set for the u (Underline) run property attribute in PowerPoint.

On load, all enumerations other than "bold" and "thick" are treated as "normal".

On save, "auto" and "bold" are the only values written.

### **2.1.1308 Part 3 Section 20.393, style:use-optimal-column-width**

- a. *The standard defines the attribute style:use-optimal-column-width, contained within the element <style:table-column-properties>*

This attribute is supported in Word 2013 and later.

Word has a table-level autofit property, while ODF has autofit properties at both the row and column-level.

On load, if all the columns and all the rows of the table support the same value for this attribute, then it is preserved at the table-level. Otherwise, the property is lost.

- b. *The standard defines the attribute style:use-optimal-column-width, contained within the element <style:table-column-properties>*

### **2.1.1309 Part 3 Section 20.394, style:use-optimal-row-height**

- a. *The standard defines the attribute style:use-optimal-row-height, contained within the element <style:table-row-properties>*

This attribute is supported in Word 2013 and later.

Word has a table-level autofit property, and ODF has autofit properties at both the row and column-level.

On load, if all the columns and all the rows of the table support the same value for this attribute, then it is preserved at the table-level. Otherwise, the property is not preserved.

- b. *The standard defines the attribute style:use-optimal-row-height, contained within the element <style:table-row-properties>*

### **2.1.1310 Part 3 Section 20.395, style:use-window-font-color**

- a. *The standard defines the attribute style:use-window-font-color, contained within the element <style:text-properties>*

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:use-window-font-color, contained within the element <style:text-properties>*



This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:use-window-font-color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1311 Part 3 Section 20.397, style:vertical-pos**

- a. *The standard defines the attribute style:vertical-pos, contained within the element <style:list-level-properties>*

This attribute is not supported in Word 2013 or later.

Word ignores the style:vertical-pos property on load, but writes it out on save.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt.

- b. *The standard defines the attribute style:vertical-pos, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- c. *The standard defines the attribute `style:vertical-pos`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1312 Part 3 Section 20.398, `style:vertical-rel`**

- a. *The standard defines the property "baseline", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the `style:vertical-rel` attribute.

- b. *The standard defines the property "char", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the `style:vertical-rel` attribute.

- c. *The standard defines the property "frame", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- d. *The standard defines the property "frame-content", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- e. *The standard defines the property "line", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- f. *The standard defines the property "page-content", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- g. *The standard defines the property "paragraph-content", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- h. *The standard defines the property "text", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- i. *The standard defines the attribute style:vertical-rel, contained within the element <style:list-level-properties>*

This attribute is not supported in Word 2013 or later.

Word ignores the style:vertical-rel property on load, but writes it out on save.

### **2.1.1313 Part 3 Section 20.399, style:width**

- a. *The standard defines the attribute style:width, contained within the element <style:table-properties>*

### **2.1.1314 Part 3 Section 20.400, style:wrap**

- a. *The standard defines the property "run-through", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is not supported in Word 2013 or later.

### **2.1.1315 Part 3 Section 20.401, style:wrap-contour**

- a. *The standard defines the attribute style:wrap-contour, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

### **2.1.1316 Part 3 Section 20.402, style:wrap-contour-mode**

- a. *The standard defines the attribute style:wrap-contour-mode, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

### **2.1.1317 Part 3 Section 20.403, style:wrap-dynamic-threshold**

- a. *The standard defines the attribute style:wrap-dynamic-threshold, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2013 or later.

### **2.1.1318 Part 3 Section 20.404, style:writing-mode**

- a. *The standard defines the attribute style:writing-mode, contained within the element <style:graphic-properties>*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. ODF's attribute style:writing-mode under the element <style:graphic-properties> assigned to at the text box or shape level corresponds to the Word body attribute "vert".

On save, style:writing-mode="tb-rl" is written for the Word vert enumerations "vert", "eaVert", and "wordArtVertRtl". All other vert enumerations are written as style:writing-mode="lr-tb".

- b. *The standard defines the property "lr", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2013 or later.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- c. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2013 or later.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- d. *The standard defines the property "rl", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2013 or later.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- e. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2013 or later.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- f. *The standard defines the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. ODF's style:writing-mode under the element <style:paragraph-properties> assigned to a paragraph correspond to OOXML's paragraph attribute "rtl".

On save, only "rl-tb" and "lr-tb" are written for this attribute at the paragraph level, corresponding to the boolean "rtl" paragraph property in OOXML.

- g. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps the "page" value for style:writing-mode attribute to the default text direction for the language of the paragraph.

- h. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Word 2013 or later.

On load, Word maps the "tb" value for style:writing-mode to the default text direction for the language of the paragraph.

- i. *The standard defines the attribute style:writing-mode, contained within the element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- j. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Word 2013 or later.

For all unsupported values of the style:writing-mode attribute, Word reverts to the default text direction based on the locale of the application.

- k. *The standard defines the property "rl", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Word 2013 or later.

For all unsupported values of the style:writing-mode attribute, Word reverts to the default text direction based on the locale of the application.

- l. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Word 2013 or later.

For all unsupported values of the style:writing-mode attribute, Word reverts to the default text direction based on the locale of the application.

- m. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:table-properties>*

This property is not supported in Word 2013 or later.

- n. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:table-properties>*

This property is not supported in Word 2013 or later.

- o. *The standard defines the property "tb-lr", contained within the attribute style:writing-mode, contained within the element <style:table-properties>*

This property is not supported in Word 2013 or later.

This value for the style:writing-mode attribute causes the layout of the table to be left-to-right.

- p. *The standard defines the property "tb-rl", contained within the attribute style:writing-mode, contained within the element <style:table-properties>*

This property is not supported in Word 2013 or later.

This value for the style:writing-mode attribute causes the layout of the table to be right-to-left.

- q. *The standard defines the attribute style:writing-mode, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. This attribute in the element <style:graphic-properties> assigned at the text box or shape level corresponds to the attribute vert in Excel. On load, the values "tb-rl" and "tb" of this attribute are converted to the value of "eaVert" of the vert attribute in Excel. All other values of this attribute are converted to the value of "horz" of the vert attribute in Excel. On save, Excel converts the values "vert", "eaVert", and "wordArtVertRtl" of the vert attribute to the value "tb-rl" of this attribute. All other values of the vert attribute are written as the value "lr-tb".

- r. *The standard defines the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This attribute is supported in Excel 2013 and later.

On load, Excel defaults to context-dependent reading order unless the following values are specified:

- "lr"
- "lr-tb"
- "tb-lr"
- "rl"
- "rl-tb"
- "tb-rl"

The values "lr", "lr-tb", and "tb-lr" are interpreted as left-to-right. The values "rl", "rl-tb", and "tb-rl" are interpreted as right-to-left.

On save, Excel will not write a value when the reading order is context dependent. Excel will write the value "rl" when right-to-left is set or the value "lr" when left-to-right is set.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. ODF's attribute style:writing-mode under the element <style:paragraph-properties> assigned to a paragraph correspond to OOXML's paragraph attribute "rtl".

On read, enumerations "rl-tb" and "rl" are mapped to OOXML rtl=true, and all other values map to rtl=false.

On write, only "rl-tb" and "lr-tb" are written for this attribute at the paragraph level, corresponding to the boolean "rtl" paragraph property in OOXML.

- s. *The standard defines the property "lr-tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

On load, when encountering this value, Excel will set the reading order to left-to-right.

- t. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel defaults to context-dependent reading order, because the left-to-right or right-to-left reading order was not specified.

- u. *The standard defines the property "rl-tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

On load, when encountering this value, Excel will set the reading order to right-to-left.

- v. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

On load, Excel defaults to context-dependent reading order, because the left-to-right or right-to-left reading order was not specified.

- w. *The standard defines the property "tb-lr", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

On load, when encountering this value, Excel will set the reading order to left-to-right.

- x. *The standard defines the property "tb-rl", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2013 or later.

On load, when encountering this value, Excel will set the reading order to right-to-left.

- y. *The standard defines the attribute style:writing-mode, contained within the element <style:section-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- z. *The standard defines the property "lr-tb", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Excel 2013 or later.

- aa. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Excel 2013 or later.

- bb. *The standard defines the property "rl-tb", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Excel 2013 or later.



- cc. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Excel 2013 or later.

- dd. *The standard defines the property "tb-lr", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Excel 2013 or later.

- ee. *The standard defines the property "tb-rl", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Excel 2013 or later.

- ff. *The standard defines the attribute style:writing-mode, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

This attribute in the element <style:graphic-properties> assigned at the text box or shape level corresponds to the body attribute vert in PowerPoint.

On load, the values "tb-rl" and "tb" of this attribute are converted to the value "eaVert" of the body attribute vert in PowerPoint. All other values of this attribute are converted to the value "horz" of the body attribute vert in PowerPoint.

On save, PowerPoint converts the values "vert", "eaVert", and "wordArtVertRtl" of the body attribute vert to the value "tb-rl" of this attribute. All other values of the body attribute vert are written as the value "lr-tb".

- gg. *The standard defines the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2013 or later.

- hh. *The standard defines the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

ODF's attribute `style:writing-mode` under the element `<style:paragraph-properties>` assigned to a paragraph correspond to PowerPoint's paragraph attribute `"rtl"`.

On read, enumerations `"rl-tb"` and `"rl"` are mapped to PowerPoint `"rtl"` equals the value `true`, and all other values map to `"rtl"` equals the value `false`.

On write, only `"rl-tb"` and `"lr-tb"` are written for this attribute at the paragraph level, corresponding to the boolean `"rtl"` paragraph property in PowerPoint.

- ii. *The standard defines the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1319 Part 3 Section 20.404.6, `style:table-cell-properties`**

- a. *The standard defines the property `"page"`, contained within the attribute `style:table-cell-properties`, contained within the element `<style:table-cell-properties>`*

This property is supported in Word 2013 and later.

On load, Word uses the application default text direction for the current language.

- b. *The standard defines the property `"rl"`, contained within the attribute `style:table-cell-properties`, contained within the element `<style:table-cell-properties>`*

This property is supported in Word 2013 and later.

On load, Word uses the application default text direction for the current language.

- c. *The standard defines the property `"tb"`, contained within the attribute `style:table-cell-properties`, contained within the element `<style:table-cell-properties>`*

This property is supported in Word 2013 and later.

On load, Word uses the application default text direction for the current language.

- d. *The standard defines the property "tb-lr", contained within the attribute style:table-cell-properties, contained within the element <style:table-cell-properties>*

This property is supported in Word 2013 and later.

On load, Word uses the application default text direction for the current language.

- e. *The standard defines the property "tb-rl", contained within the attribute style:table-cell-properties, contained within the element <style:table-cell-properties>*

This property is supported in Word 2013 and later.

On load, Word uses the application default text direction for the current language.

### **2.1.1320 Part 3 Section 20.405, style:writing-mode-automatic**

- a. *The standard defines the attribute style:writing-mode-automatic, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:writing-mode-automatic, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:writing-mode-automatic, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

### **2.1.1321 Part 3 Section 20.406, svg:fill-rule**

- a. *The standard defines the attribute `svg:fill-rule`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `svg:fill-rule`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute `svg:fill-rule`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

## 2.1.1322 Part 3 Section 20.408, `svg:stroke-color`

- a. *The standard defines the attribute `svg:stroke-color`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
- `<draw:custom-shape>`

- b. *The standard defines the attribute `svg:stroke-color`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `svg:stroke-color`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`

- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1323 Part 3 Section 20.409, svg:stroke-opacity**

- a. *The standard defines the attribute `svg:stroke-opacity`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `svg:stroke-opacity`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `svg:stroke-opacity`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>

- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1324 Part 3 Section 20.410, svg:stroke-width**

- a. *The standard defines the attribute `svg:stroke-width`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `svg:stroke-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `svg:stroke-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

### **2.1.1325 Part 3 Section 20.412.2, style:list-level-properties**

- a. *The standard defines the attribute `svg:y`, contained within the element `<style:list-level-properties>`*

This attribute is supported in Word 2013 and later.

### **2.1.1326 Part 3 Section 20.414, table:align**

- a. *The standard defines the property "margins", contained within the attribute `table:align`, contained within the element `<style:table-properties>`*

This property is not supported in Word 2013 or later.

On load, Word treats this value for the `table:align` attribute as "left".

- b. *The standard defines the attribute `table:align`, contained within the element `<style:table-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `table:align`, contained within the element `<style:table-properties>`*

### **2.1.1327 Part 3 Section 20.415, table:border-model**

- a. *The standard defines the attribute `table:border-model`, contained within the element `<style:table-properties>`*

This attribute is not supported in Word 2013 or later.

Word only supports the "collapsing" value of the `table:border-model` attribute.

- b. *The standard defines the attribute `table:border-model`, contained within the element `<style:table-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `table:border-model`, contained within the element `<style:table-properties>`*

### **2.1.1328 Part 3 Section 20.416, table:display**

- a. *The standard defines the attribute `table:display`, contained within the element `<style:table-properties>`*



### **2.1.1329 Part 3 Section 20.419, text:animation**

- a. *The standard defines the attribute text:animation, contained within the element <style:graphics-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1330 Part 3 Section 20.420, text:animation-delay**

- a. *The standard defines the attribute text:animation-delay, contained within the element <style:graphics-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1331 Part 3 Section 20.421, text:animation-direction**

- a. *The standard defines the attribute text:animation-direction, contained within the element <style:graphics-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1332 Part 3 Section 20.422, text:animation-repeat**

- a. *The standard defines the attribute text:animation-repeat, contained within the element <style:graphics-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1333 Part 3 Section 20.423, text:animation-start-inside**

- a. *The standard defines the attribute text:animation-start-inside, contained within the element <style:graphics-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1334 Part 3 Section 20.424, text:animation-steps**

- a. *The standard defines the attribute text:animation-steps, contained within the element <style:graphics-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1335 Part 3 Section 20.425, text:animation-stop-inside**

- a. *The standard defines the attribute text:animation-stop-inside, contained within the element <style:graphics-properties>*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1336 Part 3 Section 20.427, text:display**

- a. *The standard defines the attribute text:display, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2013 or later.

- b. *The standard defines the attribute `text:display`, contained within the element `<style:text-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1337 Part 3 Section 20.428, `text:dont-balance-text-columns`**

- a. *The standard defines the attribute `text:dont-balance-text-columns`, contained within the element `<style:section-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `text:dont-balance-text-columns`, contained within the element `<style:section-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `text:dont-balance-text-columns`, contained within the element `<style:section-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1338 Part 3 Section 20.430, `text:line-number`**

- a. *The standard defines the attribute `text:line-number`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2013 or later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `text:line-number`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2013 or later.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `text:line-number`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1339 Part 3 Section 20.431, `text:list-level-position-and-space-mode`**

- a. *The standard defines the attribute `text:list-level-position-and-space-mode`, contained within the element `<style:list-level-properties>`*

This attribute is supported in Word 2013 and later.

On save, Word always writes the value "label-alignment" for this attribute.

- b. *The standard defines the attribute `text:list-level-position-and-space-mode`, contained within the element `<style:list-level-properties>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `text:list-level-position-and-space-mode`, contained within the element `<style:list-level-properties>`*

This attribute is not supported in PowerPoint 2013 or later.

### **2.1.1340 Part 3 Section 20.432, `text:min-label-distance`**

- a. *The standard defines the attribute `text:min-label-distance`, contained within the element `<style:list-level-properties>`*

This attribute is supported in Word 2013 and later.

**OfficeArt Math** in Word 2013 does not support this attribute on save for text in SmartArt.

- b. *The standard defines the attribute `text:min-label-distance`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- c. *The standard defines the attribute `text:min-label-distance`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1341 Part 3 Section 20.433, `text:min-label-width`**

- a. *The standard defines the attribute `text:min-label-width`, contained within the element `<style:list-level-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- b. *The standard defines the attribute `text:min-label-width`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- c. *The standard defines the attribute `text:min-label-width`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

### **2.1.1342 Part 3 Section 20.435, `text:space-before`**

- a. *The standard defines the attribute `text:space-before`, contained within the element `<style:list-level-properties>`*

**OfficeArt Math** in Word 2013 supports this attribute on save for text in SmartArt.

- b. *The standard defines the attribute `text:space-before`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- c. *The standard defines the attribute `text:space-before`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

#### **2.1.1343 Part 2 Section 4.16.11, manifest:preferred-view-mode**

- a. *The standard defines the attribute `manifest:preferred-view-mode`, contained within the element `<manifest:file-entry>`*

This attribute is supported in PowerPoint 2013 and later.

PowerPoint only supports reading a value of "presentation-slide-show"

#### **2.1.1344 Part 2 Section 4.16.14, manifest:version**

- a. *The standard defines the attribute `manifest:version`, contained within the element `<manifest:manifest>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `manifest:version`, contained within the element `<manifest:manifest>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `manifest:version`, contained within the element `<manifest:manifest>`*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1345 Part 4 Section 6.18.19, CRITBINOM**

- a. *The standard defines the constraints,  $Trials \geq 0$ ,  $0 \leq SP \leq 1$ ,  $0 \leq Alpha \leq 1$*

The constraints are partially supported by Excel, Trials  $\geq 0$ ,  $0 < SP < 1$ ,  $0 < Alpha < 1$

#### **2.1.1346 Part 2 Section 3.4, Encryption**

- a. *The standard defines OpenDocument packages may be encrypted by encrypting some or all files within the package.*

Encryption is not supported for ODF file types in Word 2013 or later.

- b. *The standard defines OpenDocument packages may be encrypted by encrypting some or all files within the package.*

Encryption is not supported for ODF file types in Excel 2013 or later.

- c. *The standard defines OpenDocument packages may be encrypted by encrypting some or all files within the package.*

Encryption is not supported for ODF file types in PowerPoint 2013 or later.

#### **2.1.1347 Part 2 Section 3.9, Interactions Between Encryption and Digital Signatures**

- a. *The standard defines OpenDocument Package Producer that encrypts files per section 3.4.*

Encryption is not supported for ODF file types in Word 2013 or later.

- b. *The standard defines OpenDocument Package Producer that encrypts files per section 3.4.*

Encryption is not supported for ODF file types in Excel 2013 or later.

- c. *The standard defines OpenDocument Package Producer that encrypts files per section 3.4.*

Encryption is not supported for ODF file types in PowerPoint 2013 or later.

#### **2.1.1348 Part 2 Section 4.16.3, manifest:checksum-type**

- a. *The standard defines the attribute manifest:checksum-type, contained within the element <manifest:manifest>*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute manifest:checksum-type, contained within the element <manifest:manifest>*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute manifest:checksum-type, contained within the element <manifest:manifest>*

This attribute is not supported in PowerPoint 2013 or later.

#### **2.1.1349 Part 2 Section 4.8, manifest:encrypted-key**

- a. *The standard defines the element manifest:encrypted-key, contained within the element <manifest:manifest>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element `manifest:encrypted-key`, contained within the element `<manifest:manifest>`*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element `manifest:encrypted-key`, contained within the element `<manifest:manifest>`*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.1350 Part 2 Section 4.9, `manifest:encryption-method`**

- a. *The standard defines the element `manifest:encryption-method`, contained within the element `<manifest:encrypted-key>`*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element `manifest:encryption-method`, contained within the element `<manifest:encrypted-key>`*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element `manifest:encryption-method`, contained within the element `<manifest:encrypted-key>`*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.1351 Part 2 Section 4.10, `manifest:keyinfo`**

- a. *The standard defines the element `manifest:keyinfo`, contained within the element `<manifest:encrypted-key>`*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element `manifest:keyinfo`, contained within the element `<manifest:encrypted-key>`*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element `manifest:keyinfo`, contained within the element `<manifest:encrypted-key>`*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.1352 Part 2 Section 4.11, `manifest:PGPData`**

- a. *The standard defines the element `manifest:PGPData`, contained within the element `<manifest:keyinfo>`*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element `manifest:PGPData`, contained within the element `<manifest:keyinfo>`*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element `manifest:PGPData`, contained within the element `<manifest:keyinfo>`*

This element is not supported in PowerPoint 2013 or later.



### **2.1.1353 Part 2 Section 4.12, manifest:PGPKeyID**

- a. *The standard defines the element manifest:PGPKeyID, contained within the element <manifest:PGPData>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element manifest:PGPKeyID, contained within the element <manifest:PGPData>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element manifest:PGPKeyID, contained within the element <manifest:PGPData>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.1354 Part 2 Section 4.13, manifest:PGPKeyPacket**

- a. *The standard defines the element manifest:PGPKeyPacket, contained within the element <manifest:PGPData>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element manifest:PGPKeyPacket, contained within the element <manifest:PGPData>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the attr element ibute manifest:PGPKeyPacket, contained within the element <manifest:PGPData>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.1355 Part 2 Section 4.14, manifest:CipherData**

- a. *The standard defines the element manifest:CipherData, contained within the element <manifest:encrypted-key>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element manifest:CipherData, contained within the element <manifest:encrypted-key>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element manifest:CipherData, contained within the element <manifest:encrypted-key>*

This element is not supported in PowerPoint 2013 or later.

### **2.1.1356 Part 2 Section 4.15, manifest:CipherValue**

- a. *The standard defines the element manifest:CipherValue, contained within the element <manifest:CipherData>*

This element is not supported in Word 2013 or later.

- b. *The standard defines the element manifest:CipherValue, contained within the element <manifest:CipherData>*

This element is not supported in Excel 2013 or later.

- c. *The standard defines the element `manifest:CipherValue`, contained within the element `<manifest:CipherData>`*

This element is not supported in PowerPoint 2013 or later.

#### **2.1.1357 Part 2 Section 4.17, manifest:PGPAlgorithm**

- a. *The standard defines the attribute `manifest:PGPAlgorithm`, contained within the element `<manifest:encryption-method>`*

This attribute is not supported in Word 2013 or later.

- b. *The standard defines the attribute `manifest:PGPAlgorithm`, contained within the element `<manifest:encryption-method>`*

This attribute is not supported in Excel 2013 or later.

- c. *The standard defines the attribute `manifest:PGPAlgorithm`, contained within the element `<manifest:encryption-method>`*

This attribute is not supported in PowerPoint 2013 or later.

### 3 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Description	Revision class
<a href="#">2.1.20</a> Part 3 Section 3.15.2, office:styles	Added support info for number:date-style and number:time-style.	Major
<a href="#">2.1.31</a> Part 3 Section 5.1.2, text:h	Clarified behavior of the text:h element.	Minor

## 4 Index

### A

Accessing glyphs for characters from MathML  
([mglyph](#)) ([section 2.1.333](#) 154, [section 2.1.334](#)  
159)

[Adjust Space Around Content \(mpadded\)](#) 170

[anim:animateColor](#) 210

[anim:animateTransform](#) 210

[anim:audio](#) 211

[anim:audio-level](#) 276

[anim:command](#) 211

[anim:formula](#) 276

[anim:id](#) 276

[anim:sub-item](#) 276

[anyIRI](#) 275

### B

[Bind Action to Sub-Expression \(maction\)](#) 207

### C

[Change tracking](#) 823

[chart:angle-offset](#) 540

[chart:axis](#) 117

[chart:chart](#) 116

[chart:class](#) 276

[chart:column-mapping](#) 277

[chart:connect-bars](#) 540

[chart:coordinate-region](#) 117

[chart:data-label-number](#) 540

[chart:data-label-series](#) 540

[chart:data-label-symbol](#) 540

[chart:data-label-text](#) 541

[chart:data-source-has-labels](#) 277

[chart:deep](#) 541

[chart:display-label](#) 541

[chart:error-category](#) 541

[chart:error-indicator](#) 118

[chart:error-lower-indicator](#) 542

[chart:error-lower-limit](#) 542

[chart:error-margin](#) 542

[chart:error-percentage](#) 542

[chart:error-upper-indicator](#) 542

[chart:error-upper-limit](#) 542

[chart:footer](#) 117

[chart:gap-width](#) 543

[chart:group-bars-per-axis](#) 543

[chart:interpolation](#) 543

[chart:interval-major](#) 543

[chart:interval-minor-divisor](#) 544

[chart:japanese-candle-stick](#) 544

[chart:label-arrangement](#) 544

[chart:label-position-negative](#) 544

[chart:legend](#) 117

[chart:legend-align](#) 277

[chart:legend-position](#) 277

[chart:lines](#) 544

[chart:link-data-style-to-source](#) 544

[chart:logarithmic](#) 545

[chart:maximum](#) 545

[chart:mean-value](#) 117

[chart:minimum](#) 545

[chart:origin](#) 545

[chart:overlap](#) 545

[chart:percentage](#) 546

[chart:pie-offset](#) 545

[chart:regression-curve](#) 118

[chart:regression-force-intercept](#) 546

[chart:regression-intercept-value](#) 546

[chart:regression-max-degree](#) 546

[chart:regression-moving-type](#) 546

[chart:regression-name](#) 546

[chart:regression-period](#) 546

[chart:regression-type](#) 547

[chart:row-mapping](#) 278

[chart:scale-text](#) 547

[chart:series-source](#) 547

[chart:sort-by-x-values](#) 547

[chart:spline-order](#) 547

[chart:spline-resolution](#) 547

[chart:stacked](#) 547

[chart:stock-gain-marker](#) 118

[chart:stock-loss-marker](#) 118

[chart:stock-range-line](#) 118

[chart:subtitle](#) 117

[chart:symbol-height](#) 548

[chart:symbol-name](#) 548

[chart:symbol-type](#) 549

[chart:symbol-width](#) 549

[chart:text-overlap](#) 550

[chart:three-dimensional](#) 550

[chart:tick-mark-position](#) 550

[chart:tick-marks-major-inner](#) 550

[chart:tick-marks-major-outer](#) 550

[chart:tick-marks-minor-inner](#) 550

[chart:tick-marks-minor-outer](#) 550

[chart:vertical](#) 550

[chart:visible](#) 551

[config:config-item](#) 32

[config:config-item-map-entry](#) 32

[config:config-item-map-indexed](#) 32

[config:config-item-map-named](#) 32

[config:config-item-set](#) 32

[CRITBINOM](#) 818

[Cursor Position Setting](#) 32

### D

[db:catalog-name](#) 278

[db:max-row-count](#) 278

[dc:date](#) 35

[dc:language](#) 36

[dr3d:ambient-color](#) 278

[dr3d:backface-culling](#) 551

[dr3d:back-scale](#) 551

[dr3d:close-back](#) 551

[dr3d:close-front](#) 552

[dr3d:cube](#) 113

[dr3d:depth](#) 552

[dr3d:diffuse-color](#) 278

[dr3d:distance](#) 279

[dr3d:edge-rounding](#) 552  
[dr3d:edge-rounding-mode](#) 553  
[dr3d:emissive-color](#) 553  
[dr3d:end-angle](#) 553  
[dr3d:extrude](#) 114  
[dr3d:focal-length](#) 279  
[dr3d:horizontal-segments](#) 553  
[dr3d:light](#) 113  
[dr3d:lighting-mode](#) 279  
[dr3d:normals-direction](#) 554  
[dr3d:normals-kind](#) 554  
[dr3d:projection](#) 279  
[dr3d:rotate](#) 114  
[dr3d:scene](#) 113  
[dr3d:shade-mode](#) 280  
[dr3d:shadow](#) 554  
[dr3d:shadow-slant](#) 281  
[dr3d:shininess](#) 555  
[dr3d:specular-color](#) 555  
[dr3d:sphere](#) 113  
[dr3d:texture-filter](#) 555  
[dr3d:texture-generation-mode-x](#) 556  
[dr3d:texture-generation-mode-y](#) 556  
[dr3d:texture-kind](#) 555  
[dr3d:texture-mode](#) 556  
[dr3d:transform](#) 281  
[dr3d:vertical-segments](#) 557  
[dr3d:vpn](#) 281  
[dr3d:vup](#) 281  
[draw:a](#) 112  
[draw:angle](#) 282  
[draw:applet](#) 110  
[draw:auto-grow-height](#) 557  
[draw:auto-grow-width](#) 558  
[draw:background-size](#) 559  
[draw:blue](#) 559  
[draw:border](#) 283  
[draw:caption](#) 99  
[draw:caption-angle](#) 559  
[draw:caption-angle-type](#) 559  
[draw:caption-escape](#) 560  
[draw:caption-escape-direction](#) 560  
[draw:caption-fit-line-length](#) 560  
[draw:caption-gap](#) 561  
[draw:caption-id](#) 284  
[draw:caption-line-length](#) 561  
[draw:caption-point-x](#) 285  
[draw:caption-point-y](#) 285  
[draw:caption-type](#) 561  
[draw:chain-next-name](#) 285  
[draw:circle](#) 96  
[draw:class-names](#) 285  
[draw:color-inversion](#) 561  
[draw:color-mode](#) 562  
[draw:concentric-gradient-fill-allowed](#) 287  
[draw:connector](#) 98  
[draw:contour-path](#) 112  
[draw:contour-polygon](#) 111  
[draw:contrast](#) 563  
[draw:control](#) 101  
[draw:copy-of](#) 287  
[draw:corner-radius](#) 287  
[draw:cx](#) 287  
[draw:cy](#) 288  
[draw:data](#) 289  
[draw:decimal-places](#) 564  
[draw:display-name](#) 290  
[draw:distance](#) 293  
[draw:dots1](#) 294  
[draw:dots1-length](#) 295  
[draw:dots2](#) 296  
[draw:dots2-length](#) 298  
[draw:draw-aspect](#) 564  
[draw:ellipse](#) 97  
[draw:end-color](#) 299  
[draw:end-guide](#) 564  
[draw:end-intensity](#) 300  
[draw:end-line-spacing-horizontal](#) 564  
[draw:end-line-spacing-vertical](#) 565  
[draw:engine](#) 301  
[draw:enhanced-path](#) 301  
[draw:extrusion](#) 301  
[draw:extrusion-allowed](#) 302  
[draw:extrusion-brightness](#) 302  
[draw:extrusion-color](#) 302  
[draw:extrusion-depth](#) 302  
[draw:extrusion-diffusion](#) 303  
[draw:extrusion-first-light-direction](#) 303  
[draw:extrusion-first-light-harsh](#) 303  
[draw:extrusion-first-light-level](#) 304  
[draw:extrusion-light-face](#) 304  
[draw:extrusion-metal](#) 304  
[draw:extrusion-number-of-line-segments](#) 305  
[draw:extrusion-origin](#) 305  
[draw:extrusion-rotation-angle](#) 305  
[draw:extrusion-rotation-center](#) 305  
[draw:extrusion-second-light-direction](#) 306  
[draw:extrusion-second-light-harsh](#) 306  
[draw:extrusion-second-light-level](#) 306  
[draw:extrusion-shininess](#) 307  
[draw:extrusion-skew](#) 307  
[draw:extrusion-specularity](#) 307  
[draw:extrusion-viewpoint](#) 308  
[draw:fill](#) 565  
[draw:fill-color](#) 570  
[draw:fill-gradient-name](#) 571  
[draw:fill-hatch-name](#) 572  
[draw:fill-hatch-solid](#) 573  
[draw:fill-image](#) 246  
[draw:fill-image-height](#) 574  
[draw:fill-image-name](#) 575  
[draw:fill-image-ref-point](#) 576  
[draw:fill-image-ref-point-x](#) 577  
[draw:fill-image-ref-point-y](#) 578  
[draw:fill-image-width](#) 578  
[draw:filter-name](#) 308  
[draw:fit-to-contour](#) 579  
[draw:fit-to-size](#) 580  
[draw:floating-frame](#) 111  
[draw:formula](#) 308  
[draw:frame](#) 106  
[draw:frame-display-border](#) 581  
[draw:frame-display-scrollbar](#) 582  
[draw:frame-margin-horizontal](#) 582  
[draw:frame-margin-vertical](#) 582  
[draw:g](#) 102  
[draw:gamma](#) 582  
[draw:glue-point](#) 103  
[draw:glue-points](#) 308  
[draw:gradient](#) 242

[draw:gradient-step-count](#) 583  
[draw:green](#) 583  
[draw:guide-distance](#) 584  
[draw:guide-overhang](#) 584  
[draw:handle-mirror-horizontal](#) 309  
[draw:handle-mirror-vertical](#) 309  
[draw:handle-position](#) 309  
[draw:handle-range-x-maximum](#) 310  
[draw:handle-range-x-minimum](#) 310  
[draw:handle-range-y-maximum](#) 311  
[draw:handle-range-y-minimum](#) 311  
[draw:handle-switched](#) 312  
[draw:hatch](#) 245  
[draw:id](#) 312  
[draw:image](#) 108  
[draw:image-map](#) 112  
[draw:image-opacity](#) 585  
[draw:layer](#) 87  
[draw:line](#) 90  
[draw:line-distance](#) 585  
[draw:line-skew](#) 313  
[draw:luminance](#) 585  
[draw:marker](#) 249  
[draw:marker-end](#) 586  
[draw:marker-end-center](#) 586  
[draw:marker-end-width](#) 586  
[draw:marker-start](#) 587  
[draw:marker-start-center](#) 587  
[draw:marker-start-width](#) 587  
[draw:measure](#) 100  
[draw:measure-align](#) 588  
[draw:measure-vertical-align](#) 588  
[draw:modifiers](#) 314  
[draw:name](#) 314  
[draw:nav-order](#) 319  
[draw:notify-on-update-of-ranges](#) 319  
[draw:object-ole](#) 109  
[draw:ole-draw-aspect](#) 588  
[draw:opacity](#) 247  
[draw:opacity-name](#) 589  
[draw:page-thumbnail](#) 101  
[draw:parallel](#) 590  
[draw:param](#) 110  
[draw:path](#) 94  
[draw:path-stretchpoint-x](#) 319  
[draw:path-stretchpoint-y](#) 319  
[draw:placing](#) 590  
[draw:plugin](#) 110  
[draw:polygon](#) 92  
[draw:polyline](#) 91  
[draw:rect](#) 89  
[draw:red](#) 590  
[draw:regular-polygon](#) 93  
[draw:secondary-fill-color](#) 591  
[draw:shadow](#) 591  
[draw:shadow-color](#) 592  
[draw:shadow-offset-x](#) 593  
[draw:shadow-offset-y](#) 595  
[draw:shadow-opacity](#) 596  
[draw:show-unit](#) 597  
[draw:start-color](#) 320  
[draw:start-guide](#) 597  
[draw:start-intensity](#) 321  
[draw:start-line-spacing-horizontal](#) 597  
[draw:start-line-spacing-vertical](#) 598

[draw:stroke](#) 598  
[draw:stroke-dash](#) 249  
[draw:stroke-dash-names](#) 599  
[draw:stroke-linejoin](#) 600  
[draw:style](#) 322  
[draw:style-name](#) 329  
[draw:symbol-color](#) 609  
[draw:textarea-horizontal-align](#) 610  
[draw:text-areas](#) 330  
[draw:textarea-vertical-align](#) 611  
[draw:text-box](#) 107  
[draw:text-path](#) 331  
[draw:text-path-allowed](#) 331  
[draw:text-path-mode](#) 331  
[draw:text-path-same-letter-heights](#) 331  
[draw:text-path-scale](#) 332  
[draw:text-rotate-angle](#) 332  
[draw:text-style-name](#) 332  
[draw:tile-repeat-offset](#) 612  
[draw:transform](#) 332  
[draw:type](#) 339  
[draw:unit](#) 614  
[draw:visible-area-height](#) 613  
[draw:visible-area-left](#) 614  
[draw:visible-area-top](#) 614  
[draw:visible-area-width](#) 614  
[draw:wrap-influence-on-position](#) 615  
[draw:z-index](#) 339

## E

[Enclose Expression Inside Notation \(menclose\)](#) 178  
[Encryption](#) 819  
[Entry in Table or Matrix \(mtd\)](#) 202  
[Error Message \(merror\)](#) 169  
[Expression Inside Pair of Fences \(mfenced\)](#) 176

## F

[fo:background-color](#) 615  
[fo:border](#) 618  
[fo:border-bottom](#) 621  
[fo:border-left](#) 623  
[fo:border-right](#) 626  
[fo:border-top](#) 628  
[fo:break-after](#) 630  
[fo:break-before](#) 632  
[fo:clip](#) 633  
[fo:color](#) 634  
[fo:column-count](#) 340  
[fo:column-gap](#) 341  
[fo:country](#) 341  
[fo:end-indent](#) 342  
[fo:font-family](#) 635  
[fo:font-size](#) 636  
[fo:font-style](#) 637  
[fo:font-variant](#) 638  
[fo:font-weight](#) 640  
[fo:height](#) 642  
[fo:hyphenate](#) 643  
[fo:hyphenation-keep](#) 644  
[fo:hyphenation-ladder-count](#) 645  
[fo:hyphenation-push-char-count](#) 646  
[fo:hyphenation-remain-char-count](#) 647  
[fo:keep-together](#) 648

[fo:keep-with-next](#) 648  
[fo:language](#) ([section 2.1.568](#) 342, [section 2.1.1150](#) 650)  
[fo:letter-spacing](#) 650  
[fo:line-height](#) 651  
[fo:margin](#) 652  
[fo:margin-bottom](#) 654  
[fo:margin-left](#) 343  
[fo:margin-right](#) 656  
[fo:margin-top](#) 660  
[fo:max-height](#) 346  
[fo:max-width](#) 347  
[fo:min-height](#) 348  
[fo:min-width](#) 349  
[fo:orphans](#) 663  
[fo:padding](#) 664  
[fo:padding-bottom](#) 666  
[fo:padding-left](#) 668  
[fo:padding-right](#) 670  
[fo:padding-top](#) 672  
[fo:page-height](#) 664  
[fo:page-width](#) 664  
[fo:script](#) 674  
[fo:space-after](#) 349  
[fo:space-before](#) 350  
[fo:start-indent](#) 350  
[fo:text-align](#) 675  
[fo:text-align-last](#) 677  
[fo:text-indent](#) 350  
[fo:text-shadow](#) 679  
[fo:text-transform](#) 680  
[fo:widows](#) 682  
[fo:width](#) 683  
[fo:wrap-option](#) 684  
[form:allow-deletes](#) 351  
[form:allow-inserts](#) 351  
[form:allow-updates](#) 351  
[form:apply-filter](#) 351  
[form:bound-column](#) 352  
[form:button](#) 121  
[form:button-type](#) 352  
[form:checkbox](#) 121  
[form:column](#) 123  
[form:combobox](#) 121  
[form:command](#) 352  
[form:command-type](#) 352  
[form:connection-resource](#) 66  
[form:control-implementation](#) 352  
[form:convert-empty-to-null](#) 352  
[form:current-selected](#) 353  
[form:current-value](#) 353  
[form:data-field](#) 353  
[form:datasource](#) 353  
[form:date](#) 120  
[form:detail-fields](#) 353  
[form:disabled](#) 353  
[form:dropdown](#) 354  
[form:enctype](#) 354  
[form:escape-processing](#) 354  
[form:file](#) 120  
[form:filter](#) 354  
[form:fixed-text](#) 120  
[form:for](#) 354  
[form:form](#) 119  
[form:formatted-text](#) 120  
[form:frame](#) 122  
[form:generic-control](#) 123  
[form:grid](#) 122  
[form:hidden](#) 122  
[form:id](#) 354  
[form:ignore-result](#) 355  
[form:image](#) 121  
[form:image-align](#) 355  
[form:image-data](#) 355  
[form:image-frame](#) 122  
[form:image-position](#) 355  
[form:item](#) 121  
[form:label](#) 355  
[form:listbox](#) 121  
[form:list-property](#) 123  
[form:list-source](#) 356  
[form:list-source-type](#) 356  
[form:list-value](#) 124  
[form:master-fields](#) 356  
[form:max-length](#) 356  
[form:method](#) 356  
[form:name](#) 356  
[form:navigation-mode](#) 357  
[form:number](#) 120  
[form:option](#) 121  
[form:order](#) 357  
[form:password](#) 119  
[form:printable](#) 357  
[form:properties](#) 123  
[form:property](#) 123  
[form:property-name](#) 357  
[form:radio](#) 122  
[form:readonly](#) 357  
[form:selected](#) 357  
[form:size](#) 358  
[form:tab-cycle](#) 358  
[form:tab-index](#) 358  
[form:tab-stop](#) 358  
[form:text](#) 119  
[form:textarea](#) 119  
[form:time](#) 120  
[form:title](#) 358  
[form:value](#) 358  
[form:value-range](#) 123  
[form:visual-effect](#) 359  
[Fractions \(mfrac\)](#) 160

## G

[Glossary](#) 27

## H

[Horizontally Group Sub-Expressions \(mrow\)](#) 159

## I

[Identifier \(mi\)](#) 126

[Informative references](#) 28

[Interactions Between Encryption and Digital Signatures](#) 819

[Introduction](#) 27

## L

[Labeled Row in Table or Matrix \(mlabeledtr\)](#) 201  
[language](#) 275

## M

[Making Sub-Expressions Invisible \(mphantom\)](#) 174  
[manifest:checksum-type](#) 819  
[manifest:CipherData](#) 821  
[manifest:CipherValue](#) 821  
[manifest:encrypted-key](#) 819  
[manifest:encryption-method](#) 820  
[manifest:keyinfo](#) 820  
[manifest:PGPAlgorithm](#) 822  
[manifest:PGPData](#) 820  
[manifest:PGPKeyID](#) 821  
[manifest:PGPKeyPacket](#) 821  
[manifest:preferred-view-mode](#) 818  
[manifest:version](#) 818  
[math:math](#) 125  
[meta:auto-reload](#) 35  
[meta:creator-initials](#) 125  
[meta:date-string](#) 124  
[meta:frame-count](#) 359  
[meta:hyperlink-behaviour](#) 36  
[meta:image-count](#) 359  
[meta:object-count](#) 359  
[meta:page-count](#) 359  
[meta:print-date](#) 35  
[meta:printed-by](#) 35  
[meta:sentence-count](#) 359  
[meta:syllable-count](#) 359  
[meta:template](#) 35  
[meta:user-defined](#) 36

## N

[Normative references](#) 27  
[Number \(mn\)](#) 131  
[number:am-pm](#) 226  
[number:automatic-order](#) 359  
[number:boolean](#) 226  
[number:boolean-style](#) 226  
[number:calendar](#) 360  
[number:country](#) 362  
[number:currency-style](#) 224  
[number:currency-symbol](#) 225  
[number:decimal-places](#) 362  
[number:decimal-replacement](#) 363  
[number:embedded-text](#) 224  
[number:era](#) 225  
[number:format-source](#) 363  
[number:fraction](#) 224  
[number:grouping](#) 364  
[number:language](#) 364  
[number:min-integer-digits](#) 364  
[number:number](#) 224  
[number:number-style](#) 224  
[number:percentage-style](#) 225  
[number:possessive-form](#) 364  
[number:quarter](#) 225  
[number:scientific-number](#) 224  
[number:script](#) 364  
[number:style](#) 365  
[number:text](#) 227  
[number:text-content](#) 227

[number:text-style](#) 227  
[number:time-style](#) 226  
[number:title](#) 366  
[number:transliteration-country](#) 367  
[number:transliteration-format](#) 367  
[number:transliteration-language](#) 367  
[number:transliteration-style](#) 368  
[number:truncate-on-overflow](#) 368  
[number:week-of-year](#) 225

## O

[office:annotation](#) 124  
[office:annotation-end](#) 124  
[office:automatic-styles](#) 34  
[office:binary-data](#) 108  
[office:boolean-value](#) 368  
[office:change-info](#) 43  
[office:chart](#) 31  
[office:conversion-mode](#) 369  
[office:currency](#) 369  
[office:date-value](#) 369  
[office:dde-source](#) 210  
[office:document](#) 29  
[office:document-content](#) 29  
[office:document-meta](#) 30  
[office:document-settings](#) 30  
[office:document-styles](#) 29  
[office:drawing](#) 31  
[office:event-listeners](#) 106  
[office:font-face-decls](#) 33  
[office:forms](#) 118  
[office:image](#) 31  
[office:master-styles](#) 34  
[office:mimetype](#) 370  
[office:name](#) 370  
[office:presentation](#) 31  
[office:script](#) 32  
[office:settings](#) 32  
[office:spreadsheet](#) 31  
[office:string-value](#) 371  
[office:styles](#) 33  
[office:target-frame](#) 371  
[office:target-frame-name](#) 371  
[office:time-value](#) 372  
[office:title](#) 372  
[office:value](#) 373  
[office:value-type](#) 373  
[Operator - Fence - Separator or Accent \(mo\)](#) 135  
[Overscript \(mover\)](#) 187

## P

[points](#) 275  
[Prescripts and Tensor Indices \(mmultiscripts\)](#) 191  
[presentation:action](#) 374  
[presentation:animation-group](#) 115  
[presentation:animations](#) 114  
[presentation:class](#) 374  
[presentation:class-names](#) 374  
[presentation:date-time](#) 116  
[presentation:date-time-decl](#) 116  
[presentation:dim](#) 115  
[presentation:direction](#) 374  
[presentation:display-date-time](#) 685



[presentation:display-footer](#) 685  
[presentation:display-header](#) 685  
[presentation:display-page-number](#) 685  
[presentation:effect](#) 375  
[presentation:event-listener](#) 115  
[presentation:footer](#) 116  
[presentation:footer-decl](#) 116  
[presentation:full-screen](#) 375  
[presentation:header](#) 115  
[presentation:header-decl](#) 116  
[presentation:hide-shape](#) 115  
[presentation:hide-text](#) 115  
[presentation:master-element](#) 375  
[presentation:mouse-as-pen](#) 375  
[presentation:mouse-visible](#) 375  
[presentation:notes](#) 220  
[presentation:pause](#) 375  
[presentation:placeholder](#) 252  
[presentation:play](#) 115  
[presentation:presentation-page-layout-name](#) 375  
[presentation:show-end-of-presentation-slide](#) 376  
[presentation:show-logo](#) 376  
[presentation:show-shape](#) 114  
[presentation:show-text](#) 115  
[presentation:sound](#) 114  
[presentation:source](#) 376  
[presentation:speed](#) 376  
[presentation:start-scale](#) 376  
[presentation:start-with-navigator](#) 376  
[presentation:stay-on-top](#) 376  
[presentation:style-name](#) 377  
[presentation:transition-on-click](#) 377  
[presentation:transition-speed](#) 685  
[presentation:transition-style](#) 685  
[presentation:transition-type](#) 689  
[presentation:use-date-time-name](#) 377  
[presentation:use-footer-name](#) 377  
[presentation:use-header-name](#) 378  
[presentation:user-transformed](#) 378

## R

[Radicals \(msqrt - mroot\)](#) 162

References

[informative](#) 28  
[normative](#) 27  
[relativeLength](#) 275  
[Row in Table or Matrix \(mtr\)](#) 199

## S

[script:event-listener](#) 125  
[script:event-name](#) 378  
[script:language](#) 378  
[script:macro-name](#) 378  
[smil:accumulate](#) 379  
[smil:additive](#) 379  
[smil:attributeName](#) 379  
[smil:calcMode](#) 379  
[smil:endsync](#) 380  
[smil:fadeColor](#) 380  
[smil:fill](#) 380  
[smil:fillDefault](#) 380  
[smil:keySplines](#) 380  
[smil:restart](#) 380

[smil:restartDefault](#) 381  
[smil:type](#) 381  
[Space \(mspace\)](#) 146  
[Specifying alignment points using malignmark](#) 204  
[Standards support statements](#) 29  
 Statements  
   [standards support](#) 29  
[String Literal \(ms\)](#) 150  
[Style Change \(mstyle\)](#) 165  
[style:adjustment](#) 388  
[style:apply-style-name](#) 388  
[style:auto-text-indent](#) 689  
[style:auto-update](#) 388  
[style:background-image](#) 253  
[style:background-transparency](#) 690  
[style:base-cell-address](#) 390  
[style:border-line-width](#) 690  
[style:border-line-width-bottom](#) 692  
[style:border-line-width-left](#) 694  
[style:border-line-width-right](#) 696  
[style:border-line-width-top](#) 698  
[style:cell-protect](#) 700  
[style:char](#) 390  
[style:class](#) 391  
[style:color](#) 393  
[style:column](#) 264  
[style:columns](#) 262  
[style:column-sep](#) 265  
[style:condition](#) 393  
[style:contextual-spacing](#) 700  
[style:country-asian](#) 700  
[style:country-complex](#) 702  
[style:data-style-name](#) 393  
[style:decimal-places](#) 703  
[style:default-outline-level](#) 393  
[style:default-page-layout](#) 217  
[style:default-style](#) 215  
[style:diagonal-bl-tr](#) 703  
[style:diagonal-bl-tr-widths](#) 704  
[style:diagonal-tl-br](#) 704  
[style:diagonal-tl-br-widths](#) 704  
[style:direction](#) 705  
[style:display](#) 393  
[style:display-name](#) 394  
[style:distance](#) 397  
[style:distance-after-sep](#) 397  
[style:distance-before-sep](#) 397  
[style:drop-cap](#) 259  
[style:dynamic-spacing](#) 705  
[style:editable](#) 705  
[style:family](#) 397  
[style:filter-name](#) 409  
[style:first-page-number](#) 705  
[style:flow-with-text](#) 706  
[style:font-adornments](#) 409  
[style:font-charset](#) 410  
[style:font-charset-asian](#) 706  
[style:font-charset-complex](#) 707  
[style:font-face](#) 222  
[style:font-family-asian](#) 708  
[style:font-family-complex](#) 709  
[style:font-family-generic](#) 413  
[style:font-family-generic-asian](#) 710  
[style:font-family-generic-complex](#) 711  
[style:font-independent-line-spacing](#) 712

[style:font-name](#) 713  
[style:font-name-asian](#) 714  
[style:font-name-complex](#) 715  
[style:font-pitch](#) 415  
[style:font-pitch-asian](#) 716  
[style:font-pitch-complex](#) 717  
[style:font-relief](#) 718  
[style:font-size-asian](#) 720  
[style:font-size-complex](#) 721  
[style:font-size-rel](#) 722  
[style:font-size-rel-asian](#) 723  
[style:font-size-rel-complex](#) 724  
[style:font-style-asian](#) 725  
[style:font-style-complex](#) 726  
[style:font-style-name](#) 727  
[style:font-style-name-asian](#) 728  
[style:font-style-name-complex](#) 729  
[style:font-weight-asian](#) 730  
[style:font-weight-complex](#) 731  
[style:footer](#) 218  
[style:footer-first](#) 218  
[style:footer-left](#) 218  
[style:footer-style](#) 217  
[style:footnote-max-height](#) 732  
[style:footnote-sep](#) 255  
[style:glyph-orientation-vertical](#) 732  
[style:graphic-properties](#) 273  
[style:handout-master](#) 87  
[style:header](#) 218  
[style:header-first](#) 218  
[style:header-footer-properties](#) 256  
[style:header-left](#) 218  
[style:header-style](#) 217  
[style:height](#) 417  
[style:horizontal-rel](#) 733  
[style:join-border](#) 734  
[style:justify-single-word](#) 735  
[style:language-asian](#) 735  
[style:language-complex](#) 737  
[style:layout-grid-base-height](#) 738  
[style:layout-grid-color](#) 738  
[style:layout-grid-display](#) 738  
[style:layout-grid-lines](#) 738  
[style:layout-grid-mode](#) 739  
[style:layout-grid-print](#) 739  
[style:layout-grid-ruby-below](#) 739  
[style:layout-grid-ruby-height](#) 739  
[style:layout-grid-snap-to](#) 740  
[style:leader-char](#) 417  
[style:leader-color](#) 417  
[style:leader-style](#) 418  
[style:leader-text](#) 419  
[style:leader-text-style](#) 420  
[style:leader-type](#) 421  
[style:leader-width](#) 422  
[style:legend-expansion](#) 423  
[style:legend-expansion-aspect-ratio](#) 423  
[style:length](#) 423  
[style:letter-kerning](#) 741  
[style:line-break](#) 740  
[style:line-height-at-least](#) 742  
[style:lines](#) 424  
[style:line-spacing](#) 743  
[style:line-style](#) 423  
[style:list-level-properties](#) ([section 2.1.452](#) 270, [section 2.1.1325](#) 812)  
[style:list-style-name](#) 424  
[style:map](#) 213  
[style:master-page-name](#) 424  
[style:may-break-between-rows](#) 743  
[style:min-row-height](#) 744  
[style:mirror](#) 744  
[style:name](#) 424  
[style:next-style-name](#) 428  
[style:number-wrapped-paragraphs](#) 748  
[style:num-format](#) 429  
[style:num-letter-sync](#) 440  
[style:num-prefix](#) 443  
[style:num-suffix](#) 445  
[style:overflow-behavior](#) 748  
[style:page-layout-name](#) 449  
[style:page-layout-properties](#) 252  
[style:page-number](#) 748  
[style:page-usage](#) 449  
[style:paper-tray-name](#) 749  
[style:paragraph-properties](#) 257  
[style:parent-style-name](#) 449  
[style:position](#) 451  
[style:presentation-page-layout](#) 252  
[style:print](#) 749  
[style:print-content](#) 750  
[style:print-orientation](#) 751  
[style:print-page-order](#) 750  
[style:protect](#) 751  
[style:punctuation-wrap](#) 755  
[style:region-center](#) 219  
[style:region-left](#) 218  
[style:region-right](#) 219  
[style:register-true](#) 756  
[style:register-truth-ref-style-name](#) 757  
[style:rel-column-width](#) 757  
[style:rel-height](#) 452  
[style:rel-width](#) 452  
[style:repeat](#) 453  
[style:repeat-content](#) 758  
[style:rotation-align](#) 758  
[style:rotation-angle](#) 758  
[style:ruby-align](#) 759  
[style:ruby-position](#) 760  
[style:ruby-properties](#) 260  
[style:run-through](#) 761  
[style:scale-to](#) 761  
[style:scale-to-pages](#) 761  
[style:script-asian](#) 761  
[style:script-complex](#) 761  
[style:script-type](#) 762  
[style:section-properties](#) 261  
[style:shadow](#) 763  
[style:shrink-to-fit](#) 765  
[style:snap-to-layout-grid](#) 765  
[style:style](#) 211  
[style:style-name](#) 454  
[style:table-cell-properties](#) ([section 2.1.451](#) 269, [section 2.1.1319](#) 806)  
[style:table-centering](#) 767  
[style:table-column-properties](#) 266  
[style:table-properties](#) ([section 2.1.448](#) 266, [section 2.1.1262](#) 758)  
[style:table-row-properties](#) 268

[style:tab-stop](#) 259  
[style:tab-stop-distance](#) 766  
[style:tab-stops](#) 258  
[style:text-align-source](#) 767  
[style:text-autospace](#) 767  
[style:text-blinking](#) 768  
[style:text-combine](#) 769  
[style:text-combine-end-char](#) 771  
[style:text-combine-start-char](#) 770  
[style:text-emphasize](#) 772  
[style:text-line-through-color](#) 774  
[style:text-line-through-mode](#) 775  
[style:text-line-through-style](#) 776  
[style:text-line-through-text](#) 778  
[style:text-line-through-text-style](#) 779  
[style:text-line-through-type](#) 780  
[style:text-line-through-width](#) 781  
[style:text-outline](#) 782  
[style:text-overline-color](#) 783  
[style:text-overline-mode](#) 783  
[style:text-overline-style](#) 783  
[style:text-overline-type](#) 783  
[style:text-overline-width](#) 783  
[style:text-position](#) 784  
[style:text-properties](#) 227  
[style:text-rotation-angle](#) 786  
[style:text-rotation-scale](#) 787  
[style:text-scale](#) 788  
[style:text-underline-color](#) 789  
[style:text-underline-mode](#) 790  
[style:text-underline-style](#) 791  
[style:text-underline-type](#) 794  
[style:text-underline-width](#) 795  
[style:type](#) 455  
[style:use-optimal-column-width](#) 796  
[style:use-optimal-row-height](#) 796  
[style:use-window-font-color](#) 796  
[style:vertical-align](#) 456  
[style:vertical-pos](#) 797  
[style:vertical-rel](#) 798  
[style:volatile](#) 457  
[style:width](#) ([section 2.1.754](#) 457, [section 2.1.1313](#) 799)  
[style:wrap](#) 800  
[style:wrap-contour](#) 800  
[style:wrap-contour-mode](#) 800  
[style:wrap-dynamic-threshold](#) 800  
[style:writing-mode](#) 800  
[style:writing-mode-automatic](#) 807  
[Subscript \(msub\)](#) 181  
[Subscript-superscript Pair \(msubsup\)](#) 184  
[Superscript \(msup\)](#) 183  
[svg:accent-height](#) 458  
[svg:alphanumeric](#) 458  
[svg:ascent](#) 458  
[svg:bbox](#) 458  
[svg:cap-height](#) 459  
[svg:definition-src](#) 223  
[svg:desc](#) 105  
[svg:descent](#) 459  
[svg:fill-rule](#) 808  
[svg:font-face-format](#) 223  
[svg:font-face-name](#) 223  
[svg:font-face-src](#) 223  
[svg:font-face-uri](#) 223

[svg:font-family](#) 459  
[svg:font-size](#) 459  
[svg:font-stretch](#) 459  
[svg:font-style](#) 461  
[svg:font-variant](#) 461  
[svg:font-weight](#) 461  
[svg:hanging](#) 461  
[svg:height](#) 461  
[svg:ideographic](#) 464  
[svg:linearGradient](#) 243  
[svg:mathematical](#) 464  
[svg:name](#) 464  
[svg:overline-position](#) 464  
[svg:overline-thickness](#) 464  
[svg:panose-1](#) 465  
[svg:radialGradient](#) 244  
[svg:slope](#) 465  
[svg:stemh](#) 465  
[svg:stemv](#) 465  
[svg:strikethrough-position](#) 465  
[svg:strikethrough-thickness](#) 465  
[svg:string](#) 466  
[svg:stroke-color](#) 809  
[svg:stroke-linecap](#) 608  
[svg:stroke-opacity](#) 810  
[svg:stroke-width](#) 811  
[svg:title](#) 104  
[svg:underline-position](#) 466  
[svg:underline-thickness](#) 466  
[svg:unicode-range](#) 466  
[svg:units-per-em](#) 466  
[svg:v-alphabetic](#) 467  
[svg:v-hanging](#) 467  
[svg:v-ideographic](#) 467  
[svg:viewBox](#) 467  
[svg:v-mathematical](#) 467  
[svg:width](#) 468  
[svg:widths](#) 470  
[svg:x](#) 470  
[svg:x-height](#) 471  
[svg:y](#) 472

## T

[Table or Matrix \(mtable\)](#) 193  
[table:align](#) 812  
[table:application-data](#) 473  
[table:automatic-find-labels](#) 473  
[table:background](#) 222  
[table:base-cell-address](#) 473  
[table:bind-styles-to-content](#) 473  
[table:body](#) 221  
[table:border-color](#) 474  
[table:border-model](#) 812  
[table:buttons](#) 474  
[table:case-sensitive](#) 474  
[table:cell-range-address](#) 474  
[table:cell-range-source](#) 85  
[table:condition](#) 475  
[table:condition-source](#) 475  
[table:condition-source-range-address](#) 475  
[table:consolidation](#) 87  
[table:contains-error](#) 475  
[table:content-validation-name](#) 475  
[table:copy-back](#) 475

[table:copy-formulas](#) 476  
[table:copy-styles](#) 476  
[table:country](#) 476  
[table:covered-table-cell](#) 82  
[table:database-name](#) 476  
[table:data-cell-range-address](#) 476  
[table:data-type](#) 476  
[table:date-value](#) 477  
[table:dde-links](#) 87  
[table:default-cell-style-name](#) 477  
[table:desc](#) 84  
[table:detective](#) 85  
[table:direction](#) 478  
[table:display](#) ([section 2.1.818](#) 478, [section 2.1.1328](#) 812)  
[table:display-border](#) 478  
[table:display-duplicates](#) 478  
[table:display-list](#) 478  
[table:enabled](#) 478  
[table:end-cell-address](#) 479  
[table:end-x](#) 479  
[table:end-y](#) 479  
[table:error-macro](#) 86  
[table:even-columns](#) 221  
[table:even-rows](#) 221  
[table:field-number](#) 480  
[table:filter-and](#) 86  
[table:filter-name](#) 480  
[table:filter-options](#) 480  
[table:filter-or](#) 86  
[table:filter-set-item](#) 86  
[table:first-column](#) 221  
[table:first-row](#) 220  
[table:formula](#) 480  
[table:function](#) 481  
[table:group-by-field-number](#) 481  
[table:grouped-by](#) 482  
[table:highlighted-range](#) 85  
[table:identify-categories](#) 482  
[table:ignore-empty-rows](#) 482  
[table:index](#) 482  
[table:is-selection](#) 482  
[table:is-sub-table](#) 482  
[table:label-cell-range-address](#) 483  
[table:label-range](#) 86  
[table:label-ranges](#) 86  
[table:language](#) 483  
[table:last-column](#) 221  
[table:last-row](#) 221  
[table:link-to-source-data](#) 483  
[table:marked-invalid](#) 483  
[table:mode](#) 483  
[table:name](#) 483  
[table:named-expressions](#) 86  
[table:number-columns-repeated](#) 484  
[table:number-columns-spanned](#) 484  
[table:number-matrix-columns-spanned](#) 485  
[table:number-matrix-rows-spanned](#) 486  
[table:number-rows-repeated](#) 485  
[table:number-rows-spanned](#) 485  
[table:object-name](#) 486  
[table:odd-columns](#) 221  
[table:odd-rows](#) 221  
[table:on-update-keep-size](#) 486  
[table:operation](#) 85  
[table:operator](#) 486  
[table:order](#) 487  
[table:orientation](#) 487  
[table:page-breaks-on-group-change](#) 487  
[table:parse-sql-statement](#) 487  
[table:password](#) 488  
[table:print](#) 488  
[table:print-ranges](#) 488  
[table:protect](#) 488  
[table:protected](#) 489  
[table:protection-key](#) 489  
[table:protection-key-digest-algorithm](#) 489  
[table:range-usable-as](#) 490  
[table:refresh-delay](#) 490  
[table:scenario](#) 85  
[table:selected-page](#) 491  
[table:shapes](#) 85  
[table:show-filter-button](#) 491  
[table:source-cell-range-addresses](#) 491  
[table:source-name](#) 491  
[table:source-service](#) 86  
[table:style-name](#) 491  
[table:table](#) ([section 2.1.192](#) 81, [section 2.1.863](#) 489)  
[table:table-background](#) 492  
[table:table-cell](#) ([section 2.1.845](#) 484, [section 2.1.864](#) 489)  
[table:table-column](#) 83  
[table:table-column-group](#) 84  
[table:table-columns](#) 84  
[table:table-header-columns](#) 84  
[table:table-header-rows](#) 83  
[table:table-row](#) 82  
[table:table-row-group](#) 83  
[table:table-rows](#) 83  
[table:table-source](#) 84  
[table:table-template](#) 220  
[table:target-cell-address](#) 493  
[table:target-range-address](#) 87  
[table:template-name](#) 493  
[table:title](#) 84  
[table:tracked-changes](#) 87  
[table:use-banding-columns-styles](#) 493  
[table:use-banding-rows-styles](#) 493  
[table:used-hierarchy](#) 494  
[table:use-first-column-styles](#) 493  
[table:use-first-row-styles](#) 493  
[table:use-labels](#) 494  
[table:use-last-column-styles](#) 493  
[table:use-last-row-styles](#) 494  
[table:use-regular-expressions](#) 494  
[table:user-name](#) 494  
[table:value](#) 494  
[table:value-type](#) 494  
[table:visibility](#) 495  
[targetFrameName](#) 275  
[Text \(mtext\)](#) 142  
[text:a](#) 49  
[text:active](#) 495  
[text:alphabetical-index](#) 79  
[text:alphabetical-index-auto-mark-file](#) 79  
[text:alphabetical-index-entry-template](#) 79  
[text:alphabetical-index-mark](#) 76  
[text:alphabetical-index-mark-end](#) 76  
[text:alphabetical-index-mark-start](#) 76  
[text:alphabetical-index-source](#) 349

[text:anchor-page-number](#) 495  
[text:anchor-type](#) 496  
[text:animation](#) 813  
[text:animation-delay](#) 813  
[text:animation-direction](#) 813  
[text:animation-repeat](#) 813  
[text:animation-start-inside](#) 813  
[text:animation-steps](#) 813  
[text:animation-stop-inside](#) 813  
[text:author-initials](#) 59  
[text:author-name](#) 59  
[text:bibliography](#) 79  
[text:bibliography-configuration](#) 231  
[text:bibliography-entry-template](#) 79  
[text:bibliography-mark](#) 76  
[text:bibliography-source](#) 79  
[text:bookmark](#) 50  
[text:bookmark-end](#) 51  
[text:bookmark-ref](#) 73  
[text:bookmark-start](#) 51  
[text:bullet-char](#) 497  
[text:bullet-relative-size](#) 497  
[text:c](#) 498  
[text:capitalize-entries](#) 498  
[text:change](#) 44  
[text:changed-region](#) 43  
[text:change-end](#) 43  
[text:change-start](#) 43  
[text:chapter](#) 59  
[text:character-count](#) 65  
[text:class-names](#) 499  
[text:combine-entries](#) 501  
[text:combine-entries-with-dash](#) 501  
[text:combine-entries-with-pp](#) 501  
[text:comma-separated](#) 501  
[text:condition](#) 502  
[text:conditional-text](#) 72  
[text:cond-style-name](#) 501  
[text:consecutive-numbering](#) 502  
[text:continue-list](#) 503  
[text:continue-numbering](#) 503  
[text:count-empty-lines](#) 504  
[text:count-in-text-boxes](#) 504  
[text:creation-date](#) 62  
[text:creation-time](#) 62  
[text:creator](#) 65  
[text:current-selected](#) 504  
[text:database-display](#) 71  
[text:database-name](#) 72  
[text:database-next](#) 71  
[text:database-row-number](#) 72  
[text:database-row-select](#) 72  
[text:date-adjust](#) 504  
[text:date-value](#) 504  
[text:dde-connection](#) 74  
[text:dde-connection-decl](#) 210  
[text:dde-connection-decls](#) 209  
[text:default-style-name](#) 505  
[text:deletion](#) 43  
[text:description](#) 63  
[text:display](#) ([section 2.1.913](#) 505, [section 2.1.1336](#) 813)  
[text:display-levels](#) 506  
[text:dont-balance-text-columns](#) 814  
[text:drop-down](#) 62  
[text:editing-cycles](#) 64  
[text:editing-duration](#) 64  
[text:execute-macro](#) 74  
[text:expression](#) 62  
[text:file-name](#) 59  
[text:fixed](#) 508  
[text:format-change](#) 43  
[text:formula](#) 509  
[text:global](#) 509  
[text:h](#) 36  
[text:hidden-paragraph](#) 74  
[text:hidden-text](#) 73  
[text:id](#) 509  
[text:ignore-case](#) 510  
[text:illustration-index](#) 77  
[text:illustration-index-entry-template](#) 77  
[text:illustration-index-source](#) 77  
[text:image-count](#) 66  
[text:increment](#) 509  
[text:index-body](#) 76  
[text:index-entry-bibliography](#) 80  
[text:index-entry-chapter](#) ([section 2.1.184](#) 80, [section 2.1.936](#) 516)  
[text:index-entry-link-end](#) 81  
[text:index-entry-link-start](#) 81  
[text:index-entry-page-number](#) 80  
[text:index-entry-span](#) 80  
[text:index-entry-tab-stop](#) 81  
[text:index-entry-text](#) 80  
[text:index-scope](#) 510  
[text:index-source-styles](#) 80  
[text:index-title](#) 76  
[text:index-title-template](#) 80  
[text:initial-creator](#) 62  
[text:insertion](#) 43  
[text:is-list-header](#) 510  
[text:key1](#) 510  
[text:key1-phonetic](#) 510  
[text:key2](#) 510  
[text:key2-phonetic](#) 511  
[text:keywords](#) 64  
[text:label](#) 62  
[text:level](#) 511  
[text:line-break](#) 47  
[text:line-number](#) 814  
[text:linenumbering-configuration](#) 230  
[text:linenumbering-separator](#) 230  
[text:list](#) 40  
[text:list-header](#) 41  
[text:list-level-position-and-space-mode](#) 815  
[text:list-level-style-number](#) 233  
[text:list-style](#) 232  
[text:main-entry](#) 514  
[text:main-entry-style-name](#) 514  
[text:master-page-name](#) 514  
[text:measure](#) 74  
[text:min-label-distance](#) 816  
[text:min-label-width](#) 816  
[text:modification-date](#) 64  
[text:modification-time](#) 64  
[text:name](#) 514  
[text:note](#) 53  
[text:note-body](#) 55  
[text:note-citation](#) 54  
[text:note-class](#) 514

[text:note-continuation-notice-backward](#) 231  
[text:note-continuation-notice-forward](#) 231  
[text:note-ref](#) 73  
[text:notes-configuration](#) 230  
[text:number](#) 49  
[text:numbered-paragraph](#) 42  
[text:number-lines](#) 515  
[text:number-position](#) 515  
[text:object-count](#) 66  
[text:object-index](#) 78  
[text:object-index-entry-template](#) 78  
[text:object-index-source](#) 78  
[text:outline-level](#) 515  
[text:outline-style](#) 242  
[text:p](#) 38  
[text:page](#) 40  
[text:page-adjust](#) 516  
[text:page-continuation](#) 56  
[text:page-count](#) 65  
[text:page-sequence](#) 40  
[text:page-variable-get](#) 72  
[text:page-variable-set](#) 72  
[text:paragraph-count](#) 65  
[text:placeholder](#) 72  
[text:print-date](#) 63  
[text:printed-by](#) 63  
[text:print-time](#) 63  
[text:protected](#) 516  
[text:protection-key](#) 516  
[text:protection-key-digest-algorithm](#) 517  
[text:reference-format](#) 517  
[text:reference-mark](#) 52  
[text:reference-mark-end](#) 53  
[text:reference-mark-start](#) 53  
[text:reference-ref](#) 73  
[text:ref-name](#) 517  
[text:relative-tab-stop-position](#) 518  
[text:restart-numbering](#) 518  
[text:ruby](#) 56  
[text:ruby-text](#) 56  
[text:s](#) 46  
[text:script](#) 73  
[text:section](#) 42  
[text:section-source](#) 42  
[text:select-page](#) 518  
[text:sender-city](#) 58  
[text:sender-company](#) 58  
[text:sender-country](#) 59  
[text:sender-email](#) 57  
[text:sender-fax](#) 58  
[text:sender-firstname](#) 56  
[text:sender-initials](#) 57  
[text:sender-lastname](#) 57  
[text:sender-phone-private](#) 57  
[text:sender-phone-work](#) 58  
[text:sender-position](#) 57  
[text:sender-postal-code](#) 58  
[text:sender-state-or-province](#) 59  
[text:sender-street](#) 58  
[text:sender-title](#) 57  
[text:sequence](#) 61  
[text:sequence-decl](#) 61  
[text:sequence-decls](#) 61  
[text:sequence-ref](#) 73  
[text:sheet-name](#) 60  
[text:soft-page-break](#) 44  
[text:sort-algorithm](#) 518  
[text:space-before](#) 817  
[text:span](#) 48  
[text:start-value](#) 518  
[text:style-name](#) 520  
[text:subject](#) 64  
[text:tab](#) 47  
[text:table-count](#) 65  
[text:table-formula](#) 74  
[text:table-index](#) 77  
[text:table-index-entry-template](#) 78  
[text:table-index-source](#) 78  
[text:table-of-content](#) 77  
[text:table-of-content-entry-template](#) 77  
[text:tab-ref](#) 525  
[text:template-name](#) 59  
[text:text-input](#) 62  
[text:time-adjust](#) 526  
[text:time-value](#) 526  
[text:title](#) 64  
[text:toc-mark](#) 75  
[text:toc-mark-end](#) 75  
[text:toc-mark-start](#) 74  
[text:track-changes](#) 527  
[text:tracked-changes](#) 42  
[text:use-keys-as-entries](#) 527  
[text:user-defined](#) 63  
[text:user-field-decl](#) 61  
[text:user-field-decls](#) 61  
[text:user-field-get](#) 61  
[text:user-field-input](#) 61  
[text:user-index](#) 78  
[text:user-index-entry-template](#) 79  
[text:user-index-mark](#) 75  
[text:user-index-mark-end](#) 75  
[text:user-index-mark-start](#) 75  
[text:user-index-source](#) 79  
[text:value](#) 527  
[text:variable-decl](#) 60  
[text:variable-decls](#) 60  
[text:variable-get](#) 60  
[text:variable-input](#) 60  
[text:variable-set](#) 60  
[text:visited-style-name](#) 527  
[text:word-count](#) 65  
[Tracking changes](#) 823

**U**

[Underscript \(munder\)](#) 185  
[Underscript-overscript Pair \(munderover\)](#) 189

**V**

[variableName](#) 275  
[vector3D](#) 276

**W**

[W3C Schema Datatypes](#) 275  
[White Space Characters](#) 45

**X**

[xforms:bind](#) 528  
[xforms:model](#) 119  
[xhtml:about](#) 528  
[xhtml:content](#) 528  
[xhtml:datatype](#) 529  
[xhtml:property](#) 529  
[xlink:actuate](#) 530  
[xlink:href](#) 531  
[xlink:show](#) 535  
[xlink:type](#) 537  
[xml:id](#) 539