

[MS-OODF2]:

Office Implementation Information for ODF 1.1 Version 2 Standards Support

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
12/15/2009	1.0	Major	Initial Availability
2/19/2010	1.01	Major	Updated and revised the technical content
3/31/2010	1.02	Major	Revised for template compliance
4/30/2010	1.03	Major	Updated and revised the technical content
6/7/2010	1.04	Editorial	Revised and edited the technical content
6/29/2010	1.05	Editorial	Changed language and formatting in the technical content.
7/23/2010	1.05	No Change	No changes to the meaning, language, or formatting of the technical content.
9/27/2010	1.05	No Change	No changes to the meaning, language, or formatting of the technical content.
11/15/2010	1.06	Editorial	Changed language and formatting in the technical content.
12/17/2010	1.06	No Change	No changes to the meaning, language, or formatting of the technical content.
3/18/2011	1.06	No Change	No changes to the meaning, language, or formatting of the technical content.
6/10/2011	1.06	No Change	No changes to the meaning, language, or formatting of the technical content.
1/20/2012	2.0	Major	Significantly changed the technical content.
4/11/2012	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
7/16/2012	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
10/8/2012	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
2/11/2013	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
7/30/2013	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
11/18/2013	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
7/31/2014	2.0	No Change	No changes to the meaning, language, or formatting of the technical content.
10/30/2014	2.0	No Change	No changes to the meaning, language, or formatting of the

Date	Revision History	Revision Class	Comments
			technical content.
9/4/2015	3.0	Major	Significantly changed the technical content.
9/25/2015	4.0	Major	Significantly changed the technical content.

Table of Contents

1	Introduction	22
1.1	Glossary	22
1.2	References	22
1.2.1	Normative References	22
1.2.2	Informative References	23
1.3	Microsoft Implementations	23
2	Conformance Statements	24
2.1	Normative Variations	24
2.1.1	Section 2, Document Structure.....	24
2.1.2	Section 2.1.1, Document Root Element Content Models.....	24
2.1.3	Section 2.1.2, Document Root Attributes	25
2.1.4	Section 2.2, Document Metadata	27
2.1.5	Section 2.2.1, Pre-Defined vs. Custom Metadata	27
2.1.6	Section 2.3, Body Element and Document Types	27
2.1.7	Section 2.3.1, Text Documents.....	27
2.1.8	Section 2.3.2, Drawing Documents	28
2.1.9	Section 2.3.3, Presentation Documents	28
2.1.10	Section 2.3.4, Spreadsheet Documents	28
2.1.11	Section 2.3.5, Chart Documents	28
2.1.12	Section 2.3.6, Image Documents.....	28
2.1.13	Section 2.4, Application Settings	29
2.1.14	Section 2.4.1, Sequence of Settings.....	29
2.1.15	Section 2.4.2, Base Settings	29
2.1.16	Section 2.4.3, Index Access of Sequences	29
2.1.17	Section 2.4.4, Map Entry	29
2.1.18	Section 2.4.5, Name Access of Sequences	30
2.1.19	Section 2.4.6, Cursor Position Setting	30
2.1.20	Section 2.5, Scripts.....	30
2.1.21	Section 2.5.1, Script	30
2.1.22	Section 2.6, Font Face Declarations	30
2.1.23	Section 2.7, Styles.....	31
2.1.24	Section 2.7.1, Location of Styles.....	32
2.1.25	Section 2.8, Page Styles and Layout	34
2.1.26	Section 3, Metadata Elements	34
2.1.27	Section 3.1, Pre-Defined Metadata Elements	34
2.1.28	Section 3.1.1, Generator	34
2.1.29	Section 3.1.2, Title	34
2.1.30	Section 3.1.3, Description.....	34
2.1.31	Section 3.1.4, Subject.....	35
2.1.32	Section 3.1.5, Keywords.....	35
2.1.33	Section 3.1.6, Initial Creator	35
2.1.34	Section 3.1.7, Creator	35
2.1.35	Section 3.1.8, Printed By	36
2.1.36	Section 3.1.9, Creation Date and Time	36
2.1.37	Section 3.1.10, Modification Date and Time	36
2.1.38	Section 3.1.11, Print Date and Time.....	36
2.1.39	Section 3.1.12, Document Template	37
2.1.40	Section 3.1.13, Automatic Reload	37
2.1.41	Section 3.1.14, Hyperlink Behavior	37
2.1.42	Section 3.1.15, Language	37
2.1.43	Section 3.1.16, Editing Cycles	38
2.1.44	Section 3.1.17, Editing Duration	38
2.1.45	Section 3.1.18, Document Statistics.....	38
2.1.46	Section 3.2, User-defined Metadata	39

2.1.47	Section 3.3, Custom Metadata.....	40
2.1.48	Section 4, Text Content.....	40
2.1.49	Section 4.1, Headings, Paragraphs and Basic Text Structure	40
2.1.50	Section 4.1.1, Headings.....	41
2.1.51	Section 4.1.2, Paragraphs.....	43
2.1.52	Section 4.1.3, Common Paragraph Elements Attributes	46
2.1.53	Section 4.2, Page Sequences	49
2.1.54	Section 4.2.1, Page.....	49
2.1.55	Section 4.3, Lists.....	49
2.1.56	Section 4.3.1, List Block	50
2.1.57	Section 4.3.2, List Item	53
2.1.58	Section 4.3.3, List Header.....	55
2.1.59	Section 4.3.4, Numbered Paragraphs	56
2.1.60	Section 4.4, Text Sections	56
2.1.61	Section 4.4.1, Section Attributes	57
2.1.62	Section 4.4.2, Section Source	58
2.1.63	Section 4.4.3, DDE Source.....	59
2.1.64	Section 4.5, Page-bound graphical content	59
2.1.65	Section 4.6, Change Tracking.....	59
2.1.66	Section 4.6.1, Tracked Changes	59
2.1.67	Section 4.6.2, Changed Regions	60
2.1.68	Section 4.6.3, Insertion.....	60
2.1.69	Section 4.6.4, Deletion.....	60
2.1.70	Section 4.6.5, Format Change	60
2.1.71	Section 4.6.6, Change Info	60
2.1.72	Section 4.6.7, Change Marks.....	60
2.1.73	Section 4.7, Soft Page Break.....	61
2.1.74	Section 4.8, Text Declarations.....	61
2.1.75	Section 5, Paragraph Elements Content.....	62
2.1.76	Section 5.1, Basic Text Content.....	63
2.1.77	Section 5.1.1, White-space Characters	64
2.1.78	Section 5.1.2, Soft Hyphens, Hyphens, and Non-breaking Blanks	69
2.1.79	Section 5.1.3, Attributed Text	70
2.1.80	Section 5.1.4, Hyperlinks.....	72
2.1.81	Section 5.2, Bookmarks and References	79
2.1.82	Section 5.2.1, Bookmarks.....	79
2.1.83	Section 5.2.2, References	82
2.1.84	Section 5.3, Notes	83
2.1.85	Section 5.3.1, Note Element.....	84
2.1.86	Section 5.4, Ruby	86
2.1.87	Section 5.5, Text Annotation.....	88
2.1.88	Section 5.6, Index Marks	89
2.1.89	Section 5.7, Change Tracking and Change Marks.....	90
2.1.90	Section 5.8, Inline graphics and text-boxes.....	91
2.1.91	Section 6, Text Fields.....	91
2.1.92	Section 6.1, Common Characteristics of Field Elements	92
2.1.93	Section 6.2, Document Fields	92
2.1.94	Section 6.2.1, Date Fields.....	92
2.1.95	Section 6.2.2, Time Fields.....	93
2.1.96	Section 6.2.3, Page Number Fields.....	94
2.1.97	Section 6.2.4, Page Continuation Text.....	97
2.1.98	Section 6.2.5, Sender Fields.....	97
2.1.99	Section 6.2.6, Author Fields	99
2.1.100	Section 6.2.7, Chapter Fields	99
2.1.101	Section 6.2.8, File Name Fields.....	100
2.1.102	Section 6.2.9, Document Template Name Fields	100
2.1.103	Section 6.2.10, Sheet Name Fields.....	101
2.1.104	Section 6.3, Variable Fields.....	101

2.1.105	Section 6.3.1, Declaring Simple Variables	101
2.1.106	Section 6.3.2, Setting Simple Variables	102
2.1.107	Section 6.3.3, Displaying Simple Variables	102
2.1.108	Section 6.3.4, Simple Variable Input Fields	102
2.1.109	Section 6.3.5, Declaring User Variables	102
2.1.110	Section 6.3.6, Displaying User Variables	102
2.1.111	Section 6.3.7, User Variable Input Fields	103
2.1.112	Section 6.3.8, Declaring Sequence Variables	103
2.1.113	Section 6.3.9, Using Sequence Fields	103
2.1.114	Section 6.3.10, Expression Fields.....	103
2.1.115	Section 6.3.11, Text Input Fields	103
2.1.116	Section 6.4, Metadata Fields	104
2.1.117	Section 6.4.1, Initial Creator	104
2.1.118	Section 6.4.2, Document Creation Date.....	104
2.1.119	Section 6.4.3, Document Creation Time.....	104
2.1.120	Section 6.4.4, Document Description	105
2.1.121	Section 6.4.5, User-Defined Document Information	105
2.1.122	Section 6.4.6, Print Time	105
2.1.123	Section 6.4.7, Print Date	106
2.1.124	Section 6.4.8, Printed By	106
2.1.125	Section 6.4.9, Document Title	106
2.1.126	Section 6.4.10, Document Subject.....	106
2.1.127	Section 6.4.11, Document Keywords.....	107
2.1.128	Section 6.4.12, Document Revision Number.....	107
2.1.129	Section 6.4.13, Document Edit Duration	107
2.1.130	Section 6.4.14, Document Modification Time	107
2.1.131	Section 6.4.15, Document Modification Date	108
2.1.132	Section 6.4.16, Document Modified By	108
2.1.133	Section 6.4.17, Document Statistics Fields.....	108
2.1.134	Section 6.5, Database Fields	110
2.1.135	Section 6.5.1, Database Field Data Source.....	110
2.1.136	Section 6.5.2, Displaying Database Content.....	115
2.1.137	Section 6.5.3, Selecting the Next Database Row.....	116
2.1.138	Section 6.5.4, Selecting a Row Number	116
2.1.139	Section 6.5.5, Displaying the Row Number.....	116
2.1.140	Section 6.5.6, Display Current Database and Table	116
2.1.141	Section 6.6, More Fields	116
2.1.142	Section 6.6.1, Page Variable Fields	116
2.1.143	Section 6.6.2, Placeholders	117
2.1.144	Section 6.6.3, Conditional Text Fields.....	117
2.1.145	Section 6.6.4, Hidden Text Field	117
2.1.146	Section 6.6.5, Reference Fields.....	117
2.1.147	Section 6.6.6, Script Fields	119
2.1.148	Section 6.6.7, Macro Fields	120
2.1.149	Section 6.6.8, Hidden Paragraph Fields	120
2.1.150	Section 6.6.9, DDE Connection Fields.....	120
2.1.151	Section 6.6.10, Measure Fields	120
2.1.152	Section 6.6.11, Table Formula Field	120
2.1.153	Section 6.7, Common Field Attributes	121
2.1.154	Section 6.7.1, Variable Value Types and Values	121
2.1.155	Section 6.7.2, Fixed	123
2.1.156	Section 6.7.3, Variable Name	123
2.1.157	Section 6.7.4, Description.....	123
2.1.158	Section 6.7.5, Display	123
2.1.159	Section 6.7.6, Formula	123
2.1.160	Section 6.7.7, Formatting Style	124
2.1.161	Section 6.7.8, Number Formatting Style	124
2.1.162	Section 7, Text Indices	125

2.1.163	Section 7.1, Index Marks	125
2.1.164	Section 7.1.1, Table of Content Index Marks	125
2.1.165	Section 7.1.2, User-Defined Index Marks	126
2.1.166	Section 7.1.3, Alphabetical Index Mark	126
2.1.167	Section 7.1.4, Bibliography Index Mark	128
2.1.168	Section 7.2, Index Structure	128
2.1.169	Section 7.2.1, Index Source	128
2.1.170	Section 7.2.2, Index Body Section	128
2.1.171	Section 7.2.3, Index Title Section	128
2.1.172	Section 7.3, Table Of Content	128
2.1.173	Section 7.3.1, Table of Content Source	129
2.1.174	Section 7.3.2, Table of Content Entry Template	129
2.1.175	Section 7.4, Index of Illustrations	129
2.1.176	Section 7.4.1, Index of Illustration Source	130
2.1.177	Section 7.4.2, Illustration Index Entry Template	130
2.1.178	Section 7.5, Index of Tables	130
2.1.179	Section 7.5.1, Table Index Source	130
2.1.180	Section 7.5.2, Table Index Entry Template	130
2.1.181	Section 7.6, Index of Objects	130
2.1.182	Section 7.6.1, Object Index Source	130
2.1.183	Section 7.6.2, Object Index Entry Template	130
2.1.184	Section 7.7, User-Defined Index	131
2.1.185	Section 7.7.1, User-Defined Index Source	131
2.1.186	Section 7.7.2, User-Defined Index Entry Template	131
2.1.187	Section 7.8, Alphabetical Index	131
2.1.188	Section 7.8.1, Alphabetical Index Source	131
2.1.189	Section 7.8.2, Auto Mark File	132
2.1.190	Section 7.8.3, Alphabetical Index Entry Template	132
2.1.191	Section 7.9, Bibliography	133
2.1.192	Section 7.9.1, Bibliography Index Source	133
2.1.193	Section 7.9.2, Bibliography Entry Template	133
2.1.194	Section 7.10, index source styles	133
2.1.195	Section 7.10.1, Index source style	133
2.1.196	Section 7.11, Index title template	133
2.1.197	Section 7.12.1, Chapter Information	134
2.1.198	Section 7.12.2, Entry Text	134
2.1.199	Section 7.12.3, Page Number	134
2.1.200	Section 7.12.4, Fixed String	135
2.1.201	Section 7.12.5, Bibliography Information	135
2.1.202	Section 7.12.6, Tab Stop	135
2.1.203	Section 7.12.7, Hyperlink Start and End	135
2.1.204	Section 7.12.8, Example of an Index Entry Configuration	136
2.1.205	Section 8, Tables	136
2.1.206	Section 8.1, Basic Table Model	136
2.1.207	Section 8.1.1, Table Element	136
2.1.208	Section 8.1.2, Table Row	140
2.1.209	Section 8.1.3, Table Cell	141
2.1.210	Section 8.2, Advanced Table Model	147
2.1.211	Section 8.2.1, Column Description	148
2.1.212	Section 8.2.2, Header Columns	149
2.1.213	Section 8.2.3, Column Groups	150
2.1.214	Section 8.2.4, Header Rows	150
2.1.215	Section 8.2.5, Row Groups	151
2.1.216	Section 8.2.6, Subtables	151
2.1.217	Section 8.3, Advanced Tables	151
2.1.218	Section 8.3.1, Referencing Table Cells	151
2.1.219	Section 8.3.2, Linked Tables	151
2.1.220	Section 8.3.3, Scenario Tables	152

2.1.221	Section 8.3.4, Shapes	153
2.1.222	Section 8.4, Advanced Table Cells.....	153
2.1.223	Section 8.4.1, Linked Table Cells	153
2.1.224	Section 8.4.2, Cell Annotation	154
2.1.225	Section 8.4.3, Detective	154
2.1.226	Section 8.4.4, Detective Operation.....	154
2.1.227	Section 8.4.5, Highlighted Range.....	155
2.1.228	Section 8.5, Spreadsheet Document Content	155
2.1.229	Section 8.5.1, Document Protection	155
2.1.230	Section 8.5.2, Calculation Settings.....	155
2.1.231	Section 8.5.3, Table Cell Content Validations.....	157
2.1.232	Section 8.5.4, Label Ranges	158
2.1.233	Section 8.5.5, Named Expressions	158
2.1.234	Section 8.6, Database Ranges.....	159
2.1.235	Section 8.6.1, Database Range.....	160
2.1.236	Section 8.6.2, Database Source SQL	161
2.1.237	Section 8.6.3, Database Source Table	162
2.1.238	Section 8.6.4, Database Source Query	162
2.1.239	Section 8.6.5, Sort.....	162
2.1.240	Section 8.6.6, Sort By	163
2.1.241	Section 8.6.7, Subtotal Rules	163
2.1.242	Section 8.6.8, Subtotal Sort Groups	164
2.1.243	Section 8.6.9, Subtotal Rule.....	164
2.1.244	Section 8.6.10, Subtotal Field	164
2.1.245	Section 8.7, Filters.....	164
2.1.246	Section 8.7.1, Table Filter	165
2.1.247	Section 8.7.2, Filter And	165
2.1.248	Section 8.7.3, Filter Or	165
2.1.249	Section 8.7.4, Filter Condition	166
2.1.250	Section 8.8, Data Pilot Tables.....	166
2.1.251	Section 8.8.1, Data Pilot Table	166
2.1.252	Section 8.8.2, Source Cell Range	168
2.1.253	Section 8.8.3, Source Service.....	168
2.1.254	Section 8.8.4, Data Pilot Field	169
2.1.255	Section 8.8.5, Data Pilot Level.....	171
2.1.256	Section 8.8.6, Data Pilot Subtotals.....	172
2.1.257	Section 8.8.7, Data Pilot Subtotal	172
2.1.258	Section 8.8.8, Data Pilot Members	173
2.1.259	Section 8.8.9, Data Pilot Member.....	173
2.1.260	Section 8.8.10, Data Pilot Display Info	174
2.1.261	Section 8.8.11, Data Pilot Sort Info.....	174
2.1.262	Section 8.8.12, Data Pilot Layout Info	175
2.1.263	Section 8.8.13, Data Pilot Field Reference.....	176
2.1.264	Section 8.8.14, Data Pilot Groups	178
2.1.265	Section 8.8.15, Data Pilot Group.....	182
2.1.266	Section 8.8.16, Data Pilot Group Member	182
2.1.267	Section 8.9, Consolidation	182
2.1.268	Section 8.10, DDE Links	183
2.1.269	Section 8.11.1, Tracked Changes.....	183
2.1.270	Section 9, Graphic Content	183
2.1.271	Section 9.1, Enhanced Page Features for Graphical Applications	183
2.1.272	Section 9.1.1, Handout Master	183
2.1.273	Section 9.1.2, Layer Sets.....	184
2.1.274	Section 9.1.3, Layer.....	184
2.1.275	Section 9.1.4, Drawing Pages.....	184
2.1.276	Section 9.1.5, Presentation Notes	185
2.1.277	Section 9.2, Drawing Shapes	185
2.1.278	Section 9.2.1, Rectangle.....	186

2.1.279	Section 9.2.2, Line.....	187
2.1.280	Section 9.2.3, Polyline.....	188
2.1.281	Section 9.2.4, Polygon	189
2.1.282	Section 9.2.5, Regular Polygon.....	190
2.1.283	Section 9.2.6, Path	191
2.1.284	Section 9.2.7, Circle.....	192
2.1.285	Section 9.2.8, Ellipse.....	194
2.1.286	Section 9.2.9, Connector	195
2.1.287	Section 9.2.10, Caption	198
2.1.288	Section 9.2.11, Measure	199
2.1.289	Section 9.2.12, Control	200
2.1.290	Section 9.2.13, Page Thumbnail	201
2.1.291	Section 9.2.14, Grouping.....	201
2.1.292	Section 9.2.15, Common Drawing Shape Attributes	202
2.1.293	Section 9.2.16, Common Shape Attributes for Text and Spreadsheet Documents.....	220
2.1.294	Section 9.2.17, Common Drawing Shape Content	221
2.1.295	Section 9.2.18, Common Shape Attribute Groups	221
2.1.296	Section 9.2.19, Glue Points	221
2.1.297	Section 9.2.20, Title and Description.....	222
2.1.298	Section 9.2.21, Event Listeners	224
2.1.299	Section 9.3, Frames	225
2.1.300	Section 9.3.1, Text Box	226
2.1.301	Section 9.3.2, Image	229
2.1.302	Section 9.3.3, Objects.....	231
2.1.303	Section 9.3.4, Applet.....	233
2.1.304	Section 9.3.5, Plugins	233
2.1.305	Section 9.3.6, Parameters	234
2.1.306	Section 9.3.7, Floating Frame.....	234
2.1.307	Section 9.3.8, Contour	234
2.1.308	Section 9.3.9, Hyperlinks.....	235
2.1.309	Section 9.3.10, Client Side Image Maps.....	236
2.1.310	Section 9.4, 3D Shapes	236
2.1.311	Section 9.4.1, Scene	236
2.1.312	Section 9.4.2, Light	236
2.1.313	Section 9.4.3, Cube	236
2.1.314	Section 9.4.4, Sphere	237
2.1.315	Section 9.4.5, Extrude.....	237
2.1.316	Section 9.4.6, Rotate	237
2.1.317	Section 9.5, Custom Shape	237
2.1.318	Section 9.5.1, Enhanced Geometry	238
2.1.319	Section 9.5.2, Enhanced Geometry - Extrusion Attributes	240
2.1.320	Section 9.5.3, Enhanced Geometry - Path Attributes	247
2.1.321	Section 9.5.4, Enhanced Geometry - Text Path Attributes	250
2.1.322	Section 9.5.5, Enhanced Geometry - Equation	251
2.1.323	Section 9.5.6, Enhanced Geometry - Handle Attributes.....	252
2.1.324	Section 9.6, Presentation Shapes.....	255
2.1.325	Section 9.6.1, Common Presentation Shape Attributes	256
2.1.326	Section 9.7, Presentation Animations	256
2.1.327	Section 9.7.1, Sound.....	256
2.1.328	Section 9.7.2, Show Shape	256
2.1.329	Section 9.7.3, Show Text.....	256
2.1.330	Section 9.7.4, Hide Shape	256
2.1.331	Section 9.7.5, Hide Text	256
2.1.332	Section 9.7.6, Dim.....	257
2.1.333	Section 9.7.7, Play.....	257
2.1.334	Section 9.7.8, Effect groups	257
2.1.335	Section 9.8, SMIL Presentation Animations	257
2.1.336	Section 9.8.1, Recommended Usage Of SMIL	257

2.1.337	Section 9.8.2, Document Dependent SMIL Animation Attribute Values.....	257
2.1.338	Section 9.8.3, SMIL Presentation Animation Attributes	259
2.1.339	Section 9.9, Presentation Events	260
2.1.340	Section 9.10, Presentation Text Fields	262
2.1.341	Section 9.10.1, Header Field	262
2.1.342	Section 9.10.2, Footer Field	262
2.1.343	Section 9.10.3, Date and Time Field.....	262
2.1.344	Section 9.11, Presentation Document Content.....	263
2.1.345	Section 9.11.1, Presentation Declarations	263
2.1.346	Section 9.11.2, Header field declaration	263
2.1.347	Section 9.11.3, Footer field declaration	263
2.1.348	Section 9.11.4, Date and Time field declaration.....	263
2.1.349	Section 9.11.5, Presentation Settings.....	264
2.1.350	Section 9.11.6, Show Definitions	265
2.1.351	Section 10, Chart Content.....	265
2.1.352	Section 10.1, Introduction to Chart Documents	265
2.1.353	Section 10.2, Chart.....	265
2.1.354	Section 10.3, Title, Subtitle and Footer.....	265
2.1.355	Section 10.3.1, Title.....	265
2.1.356	Section 10.3.2, Subtitle.....	266
2.1.357	Section 10.3.3, Footer.....	266
2.1.358	Section 10.4, Legend	266
2.1.359	Section 10.5, Plot Area.....	266
2.1.360	Section 10.6, Wall	266
2.1.361	Section 10.7, Floor	267
2.1.362	Section 10.8, Axis.....	267
2.1.363	Section 10.8.1, Grid.....	267
2.1.364	Section 10.9, Series	267
2.1.365	Section 10.9.1, Domain	267
2.1.366	Section 10.10, Categories.....	268
2.1.367	Section 10.11, Data Point	268
2.1.368	Section 10.12, Mean Value	268
2.1.369	Section 10.13, Error Indicator	268
2.1.370	Section 10.14, Regression Curves.....	268
2.1.371	Section 10.14.1, Stock Chart Markers	269
2.1.372	Section 11, Form Content	269
2.1.373	Section 11.1, Form	269
2.1.374	Section 11.1.1, Action	270
2.1.375	Section 11.1.2, Target Frame.....	270
2.1.376	Section 11.1.3, Method	270
2.1.377	Section 11.1.4, Encoding Type	270
2.1.378	Section 11.1.5, Allow Deletes.....	270
2.1.379	Section 11.1.6, Allow Inserts	271
2.1.380	Section 11.1.7, Allow Updates.....	271
2.1.381	Section 11.1.8, Apply Filter.....	271
2.1.382	Section 11.1.9, Command Type.....	271
2.1.383	Section 11.1.10, Command.....	271
2.1.384	Section 11.1.11, Data Source.....	272
2.1.385	Section 11.1.12, Master Fields.....	272
2.1.386	Section 11.1.13, Detail Fields.....	272
2.1.387	Section 11.1.14, Escape Processing	272
2.1.388	Section 11.1.15, Filter.....	272
2.1.389	Section 11.1.16, Ignore Result	272
2.1.390	Section 11.1.17, Navigation Mode.....	273
2.1.391	Section 11.1.18, Order.....	273
2.1.392	Section 11.1.19, Tabbing Cycle	273
2.1.393	Section 11.1.20, Connection Resource.....	273
2.1.394	Section 11.2, XForms Model.....	273

2.1.395	Section 11.2.1, XForms Model	273
2.1.396	Section 11.3, Controls.....	274
2.1.397	Section 11.3.1, Text.....	274
2.1.398	Section 11.3.2, Text Area	274
2.1.399	Section 11.3.3, Password	274
2.1.400	Section 11.3.4, File	274
2.1.401	Section 11.3.5, Formatted Text	274
2.1.402	Section 11.3.6, Number.....	275
2.1.403	Section 11.3.7, Date And Time	275
2.1.404	Section 11.3.8, Fixed Text	275
2.1.405	Section 11.3.9, Combo Box.....	275
2.1.406	Section 11.3.10, List Box.....	275
2.1.407	Section 11.3.11, Button.....	276
2.1.408	Section 11.3.12, Image	276
2.1.409	Section 11.3.13, Check Box	276
2.1.410	Section 11.3.14, Radio Button	276
2.1.411	Section 11.3.15, Frame	276
2.1.412	Section 11.3.16, Image Frame	276
2.1.413	Section 11.3.17, Hidden	277
2.1.414	Section 11.3.18, Grid	277
2.1.415	Section 11.3.19, Value Range	277
2.1.416	Section 11.3.20, Generic Control	277
2.1.417	Section 11.4, Common Form and Control Attributes	277
2.1.418	Section 11.4.1, Name.....	277
2.1.419	Section 11.4.2, Control Implementation	278
2.1.420	Section 11.4.3, Bind to XForms	278
2.1.421	Section 11.5, Common Control Attributes	278
2.1.422	Section 11.5.1, Button Type.....	278
2.1.423	Section 11.5.2, Control ID	278
2.1.424	Section 11.5.3, Current Selected	278
2.1.425	Section 11.5.4, Value and Current Value	279
2.1.426	Section 11.5.5, Disabled.....	279
2.1.427	Section 11.5.6, Dropdown	279
2.1.428	Section 11.5.7, For	279
2.1.429	Section 11.5.8, Image Data	279
2.1.430	Section 11.5.9, Label	280
2.1.431	Section 11.5.10, Maximum Length.....	280
2.1.432	Section 11.5.11, Printable.....	280
2.1.433	Section 11.5.12, Read only	280
2.1.434	Section 11.5.13, Selected	280
2.1.435	Section 11.5.14, Size	280
2.1.436	Section 11.5.15, Tab Index.....	281
2.1.437	Section 11.5.16, Tab Stop	281
2.1.438	Section 11.5.17, Target Frame	281
2.1.439	Section 11.5.18, Target Location	281
2.1.440	Section 11.5.19, Title	281
2.1.441	Section 11.5.20, Visual Effect.....	281
2.1.442	Section 11.5.21, Relative Image Position	282
2.1.443	Section 11.5.22, Database Binding Attributes.....	282
2.1.444	Section 11.6, Event Listeners	283
2.1.445	Section 11.7, Properties	283
2.1.446	Section 11.7.1, Property Set	283
2.1.447	Section 11.7.2, Property.....	283
2.1.448	Section 11.7.3, List Property	283
2.1.449	Section 12, Common Content.....	284
2.1.450	Section 12.1, Annotation	284
2.1.451	Section 12.1.1, Creator	287
2.1.452	Section 12.1.2, Creation Date and Time	287

2.1.453	Section 12.1.3, Creation Date and Time String	288
2.1.454	Section 12.2, Number Format	288
2.1.455	Section 12.2.1, Prefix and Suffix.....	297
2.1.456	Section 12.2.2, Format Specification	301
2.1.457	Section 12.2.3, Letter Synchronization in Number Formats	307
2.1.458	Section 12.3, Change Tracking Metadata	310
2.1.459	Section 12.4, Event Listener Tables	310
2.1.460	Section 12.4.1, Event Listener.....	310
2.1.461	Section 12.4.2, Event Types.....	311
2.1.462	Section 12.5, Mathematical Content.....	311
2.1.463	Section 12.5 (MathML 2.0 Section 3.2), Token Elements.....	312
2.1.464	Section 12.5 (MathML 2.0 Section 3.2.3), Identifier (mi)	312
2.1.465	Section 12.5 (MathML 2.0 Section 3.2.4), Number (mn)	317
2.1.466	Section 12.5 (MathML 2.0 Section 3.2.5), Operator, Fence, Separator or Accent (mo)	321
2.1.467	Section 12.5 (MathML 2.0 Section 3.2.6), Text (mtext)	329
2.1.468	Section 12.5 (MathML 2.0 Section 3.2.7), Space (mspace)	333
2.1.469	Section 12.5 (MathML 2.0 Section 3.2.8), String Literal (ms)	337
2.1.470	Section 12.5 (MathML 2.0 Section 3.2.9), Accessing glyphs for characters from MathML (mglyph)	341
2.1.471	Section 12.5 (MathML 2.0 Section 3.2.9.2), Accessing glyphs for characters from MathML (mglyph)	346
2.1.472	Section 12.5 (MathML 2.0 Section 3.3.1), Horizontally Group Sub-Expressions (mrow).....	346
2.1.473	Section 12.5 (MathML 2.0 Section 3.3.2), Fractions (mfrac)	347
2.1.474	Section 12.5 (MathML 2.0 Section 3.3.3), Radicals (msqrt, mroot).....	350
2.1.475	Section 12.5 (MathML 2.0 Section 3.3.4), Style Change (mstyle).....	352
2.1.476	Section 12.5 (MathML 2.0 Section 3.3.5), Error Message (merror)	357
2.1.477	Section 12.5 (MathML 2.0 Section 3.3.6), Adjust Space Around Content (mpadded) 358	
2.1.478	Section 12.5 (MathML 2.0 Section 3.3.7), Making Sub-Expressions Invisible (mphantom)	362
2.1.479	Section 12.5 (MathML 2.0 Section 3.3.8), Expression Inside Pair of Fences (mfenced).....	363
2.1.480	Section 12.5 (MathML 2.0 Section 3.3.9), Enclose Expression Inside Notation (menclose)	365
2.1.481	Section 12.5 (MathML 2.0 Section 3.4.1), Subscript (msub)	369
2.1.482	Section 12.5 (MathML 2.0 Section 3.4.2), Superscript (msup)	370
2.1.483	Section 12.5 (MathML 2.0 Section 3.4.3), Subscript-superscript Pair (msubsup)	372
2.1.484	Section 12.5 (MathML 2.0 Section 3.4.4), Underscript (munder)	373
2.1.485	Section 12.5 (MathML 2.0 Section 3.4.5), Overscript (mover)	375
2.1.486	Section 12.5 (MathML 2.0 Section 3.4.6), Underscript-overscript Pair (munderover) 377	
2.1.487	Section 12.5 (MathML 2.0 Section 3.4.7), Prescripts and Tensor Indices (mmultiscripts).....	379
2.1.488	Section 12.5 (MathML 2.0 Section 3.5.1), Table or Matrix (mtable).....	381
2.1.489	Section 12.5 (MathML 2.0 Section 3.5.2), Row in Table or Matrix (mtr)	387
2.1.490	Section 12.5 (MathML 2.0 Section 3.5.3), Labeled Row in Table or Matrix (mlabeledtr)	389
2.1.491	Section 12.5 (MathML 2.0 Section 3.5.4), Entry in Table or Matrix (mtd)	390
2.1.492	Section 12.5 (MathML 2.0 Section 3.5.5.4), Specifying alignment points using malignmark	392
2.1.493	Section 12.5 (MathML 2.0 Section 3.6.1), Bind Action to Sub-Expression (maction) 395	
2.1.494	Section 12.6, DDE Connections	397
2.1.495	Section 12.6.1, Container for DDE Connection Declarations	398
2.1.496	Section 12.6.2, Declaring DDE Connections for Text Fields.....	398
2.1.497	Section 12.6.3, Declaring DDE Connections for Tables.....	398

2.1.498	Section 13, SMIL Animations.....	398
2.1.499	Section 13.1.1, Animate	399
2.1.500	Section 13.1.2, Set	399
2.1.501	Section 13.1.3, Animate Motion.....	399
2.1.502	Section 13.1.4, Animate Color	399
2.1.503	Section 13.1.5, Animate Transform	399
2.1.504	Section 13.1.6, Transition Filter.....	399
2.1.505	Section 13.2, Animation Model Attributes	403
2.1.506	Section 13.3, Common Animation Attributes	403
2.1.507	Section 13.3.1, Animation Target Attributes.....	403
2.1.508	Section 13.3.2, Animation Function Attributes	403
2.1.509	Section 13.4, Animation Timing	404
2.1.510	Section 13.4.1, Animation Timing Attributes	404
2.1.511	Section 13.4.2, Parallel Animations	406
2.1.512	Section 13.4.3, Sequential Animations	406
2.1.513	Section 13.4.4, Iterative Animations	406
2.1.514	Section 13.5, Media Elements	406
2.1.515	Section 13.5.1, Audio	406
2.1.516	Section 13.6, Special Elements.....	407
2.1.517	Section 13.6.1, Command	407
2.1.518	Section 14, Styles.....	407
2.1.519	Section 14.1, Style Element	408
2.1.520	Section 14.1.1, Style Mappings	426
2.1.521	Section 14.2, Default Styles.....	428
2.1.522	Section 14.3, Page Layout	435
2.1.523	Section 14.3.1, Header and Footer Styles	436
2.1.524	Section 14.4, Master Pages	437
2.1.525	Section 14.4.1, Headers and Footers.....	438
2.1.526	Section 14.4.2, Presentation Notes	442
2.1.527	Section 14.5, Table Templates	443
2.1.528	Section 14.5.1, Row and Column Styles.....	443
2.1.529	Section 14.6, Font Face Declaration	444
2.1.530	Section 14.6.1, CSS2/SVG Font Descriptors	445
2.1.531	Section 14.6.2, Name.....	453
2.1.532	Section 14.6.3, Adornments.....	454
2.1.533	Section 14.6.4, Font Family Generic.....	455
2.1.534	Section 14.6.5, Font Pitch.....	456
2.1.535	Section 14.6.6, Font Character Set	457
2.1.536	Section 14.7, Data Styles	458
2.1.537	Section 14.7.1, Number Style	458
2.1.538	Section 14.7.2, Currency Style	460
2.1.539	Section 14.7.3, Percentage Style	461
2.1.540	Section 14.7.4, Date Style	462
2.1.541	Section 14.7.5, Time Style.....	472
2.1.542	Section 14.7.6, Boolean Style	476
2.1.543	Section 14.7.7, Text Style	477
2.1.544	Section 14.7.8, Common Data Style Elements.....	477
2.1.545	Section 14.7.9, Common Data Style Attributes	478
2.1.546	Section 14.7.10, Transliteration.....	479
2.1.547	Section 14.7.11, Common Data Style Child Element Attributes.....	479
2.1.548	Section 14.8, Text Styles.....	481
2.1.549	Section 14.8.1, Text Styles	481
2.1.550	Section 14.8.2, Paragraph Styles.....	482
2.1.551	Section 14.8.3, Section Styles.....	483
2.1.552	Section 14.8.4, Ruby Style.....	484
2.1.553	Section 14.9, Enhanced Text Styles	485
2.1.554	Section 14.9.1, Line Numbering Configuration.....	486
2.1.555	Section 14.9.2, Notes Configuration Element.....	487

2.1.556	Section 14.9.3, Bibliography Configuration.....	490
2.1.557	Section 14.10, List Style.....	490
2.1.558	Section 14.10.1, Common List-Level Style Attributes	493
2.1.559	Section 14.10.2, Number Level Style	493
2.1.560	Section 14.10.3, Bullet Level Style.....	499
2.1.561	Section 14.10.4, Image Level Style.....	504
2.1.562	Section 14.10.5, List Level Style Example.....	507
2.1.563	Section 14.11, Outline Style.....	507
2.1.564	Section 14.11.1, Outline Level Style.....	507
2.1.565	Section 14.12, Table Styles.....	508
2.1.566	Section 14.12.1, Table Styles	508
2.1.567	Section 14.12.2, Table Column Styles	508
2.1.568	Section 14.12.3, Table Row Styles	509
2.1.569	Section 14.12.4, Table Cell Styles.....	509
2.1.570	Section 14.13, Graphic Styles	509
2.1.571	Section 14.13.1, Graphic and Presentation Styles	510
2.1.572	Section 14.13.2, Drawing Page Style.....	512
2.1.573	Section 14.14, Enhanced Graphic Style Elements.....	512
2.1.574	Section 14.14.1, Gradient.....	513
2.1.575	Section 14.14.2, SVG Gradients	529
2.1.576	Section 14.14.3, Hatch.....	531
2.1.577	Section 14.14.4, Fill Image	532
2.1.578	Section 14.14.5, Opacity Gradient	540
2.1.579	Section 14.14.6, Marker	541
2.1.580	Section 14.14.7, Stroke Dash.....	543
2.1.581	Section 14.15, Presentation Page Layouts.....	553
2.1.582	Section 14.15.1, Presentation Placeholder	553
2.1.583	Section 15, Formatting Properties.....	554
2.1.584	Section 15.1, Simple and Complex Formatting Properties	565
2.1.585	Section 15.1.1, Simple Formatting Properties.....	567
2.1.586	Section 15.1.2, Complex Formatting Properties	568
2.1.587	Section 15.1.3, Processing Rules for Formatting Properties	570
2.1.588	Section 15.2, Page Layout Formatting Properties	572
2.1.589	Section 15.2.1, Page Size	572
2.1.590	Section 15.2.2, Page Number Format.....	573
2.1.591	Section 15.2.3, Paper Tray.....	573
2.1.592	Section 15.2.4, Print Orientation.....	574
2.1.593	Section 15.2.5, Margins.....	574
2.1.594	Section 15.2.6, Border	576
2.1.595	Section 15.2.7, Border Line Width	578
2.1.596	Section 15.2.8, Padding.....	580
2.1.597	Section 15.2.9, Shadow.....	581
2.1.598	Section 15.2.10, Background	581
2.1.599	Section 15.2.11, Columns.....	581
2.1.600	Section 15.2.12, Register-truth	582
2.1.601	Section 15.2.13, Print	582
2.1.602	Section 15.2.14, Print Page Order.....	583
2.1.603	Section 15.2.15, First Page Number	583
2.1.604	Section 15.2.16, Scale	583
2.1.605	Section 15.2.17, Table Centering.....	584
2.1.606	Section 15.2.18, Maximum Footnote Height.....	584
2.1.607	Section 15.2.19, Writing Mode	585
2.1.608	Section 15.2.20, Footnote Separator.....	586
2.1.609	Section 15.2.21, Layout Grid.....	587
2.1.610	Section 15.2.22, Layout Grid Base Height.....	587
2.1.611	Section 15.2.23, Layout Grid Ruby Height.....	588
2.1.612	Section 15.2.24, Layout Grid Lines.....	588
2.1.613	Section 15.2.25, Layout Grid Color	588

2.1.614	Section 15.2.26, Layout Grid Ruby Below	589
2.1.615	Section 15.2.27, Layout Grid Print	589
2.1.616	Section 15.2.28, Layout Grid Display.....	589
2.1.617	Section 15.3, Header Footer Formatting Properties	590
2.1.618	Section 15.3.1, Fixed and Minimum heights	590
2.1.619	Section 15.3.2, Margins.....	590
2.1.620	Section 15.3.3, Border	591
2.1.621	Section 15.3.4, Border Line Width	592
2.1.622	Section 15.3.5, Padding.....	593
2.1.623	Section 15.3.6, Background	594
2.1.624	Section 15.3.7, Shadow.....	594
2.1.625	Section 15.3.8, Dynamic Spacing.....	594
2.1.626	Section 15.4, Text Formatting Properties	594
2.1.627	Section 15.4.1, Font Variant	595
2.1.628	Section 15.4.2, Text Transformations	597
2.1.629	Section 15.4.3, Color	598
2.1.630	Section 15.4.4, Window Font Color	599
2.1.631	Section 15.4.5, Text Outline.....	600
2.1.632	Section 15.4.6, Line-Through Type	601
2.1.633	Section 15.4.7, Line-Through Style	602
2.1.634	Section 15.4.8, Line-Through Width	604
2.1.635	Section 15.4.9, Line-Through Color.....	605
2.1.636	Section 15.4.10, Line-Through Text	606
2.1.637	Section 15.4.11, Line-Through Text Style	607
2.1.638	Section 15.4.12, Text Position	608
2.1.639	Section 15.4.13, Font Name.....	611
2.1.640	Section 15.4.14, Font Family.....	613
2.1.641	Section 15.4.15, Font Family Generic	617
2.1.642	Section 15.4.16, Font Style.....	620
2.1.643	Section 15.4.17, Font Pitch	622
2.1.644	Section 15.4.18, Font Character Set.....	625
2.1.645	Section 15.4.19, Font Size	629
2.1.646	Section 15.4.20, Relative Font Size	632
2.1.647	Section 15.4.21, Script Type	635
2.1.648	Section 15.4.22, Letter Spacing.....	637
2.1.649	Section 15.4.23, Language	638
2.1.650	Section 15.4.24, Country.....	642
2.1.651	Section 15.4.25, Font Style.....	646
2.1.652	Section 15.4.26, Font Relief	649
2.1.653	Section 15.4.27, Text Shadow	652
2.1.654	Section 15.4.28, Underlining Type	653
2.1.655	Section 15.4.29, Underlining Style	654
2.1.656	Section 15.4.30, Underling Width	656
2.1.657	Section 15.4.31, Underline Color	658
2.1.658	Section 15.4.32, Font Weight	659
2.1.659	Section 15.4.33, Text Underline Word Mode.....	663
2.1.660	Section 15.4.34, Text Line-Through Word Mode	664
2.1.661	Section 15.4.35, Letter Kerning	665
2.1.662	Section 15.4.36, Text Blinking.....	666
2.1.663	Section 15.4.37, Text Background Color	667
2.1.664	Section 15.4.38, Text Combine.....	668
2.1.665	Section 15.4.39, Text Combine Start and End Characters	670
2.1.666	Section 15.4.40, Text Emphasis	672
2.1.667	Section 15.4.41, Text Scale	674
2.1.668	Section 15.4.42, Text Rotation Angle	675
2.1.669	Section 15.4.43, Text Rotation Scale.....	676
2.1.670	Section 15.4.44, Hyphenation	677
2.1.671	Section 15.4.45, Hyphenation Remain Char Count	679

2.1.672	Section 15.4.46, Hyphenation Push Char Count	680
2.1.673	Section 15.4.47, Hidden or Conditional Text	681
2.1.674	Section 15.5, Paragraph Formatting Properties	682
2.1.675	Section 15.5.1, Fixed Line Height	683
2.1.676	Section 15.5.2, Minimum Line Height	683
2.1.677	Section 15.5.3, Line Distance	684
2.1.678	Section 15.5.4, Font-Independent Line Spacing	685
2.1.679	Section 15.5.5, Text Align	686
2.1.680	Section 15.5.6, Text Align of Last Line	688
2.1.681	Section 15.5.7, Justify Single Word	691
2.1.682	Section 15.5.8, Keep Together	691
2.1.683	Section 15.5.9, Widows	692
2.1.684	Section 15.5.10, Orphans	693
2.1.685	Section 15.5.11, Tab Stops	694
2.1.686	Section 15.5.12, Tab Stop Distance	704
2.1.687	Section 15.5.13, Hyphenation Keep	704
2.1.688	Section 15.5.14, Maximum Hyphens	705
2.1.689	Section 15.5.15, Drop Caps	706
2.1.690	Section 15.5.16, Register True	708
2.1.691	Section 15.5.17, Left and Right Margins	709
2.1.692	Section 15.5.18, Text Indent	711
2.1.693	Section 15.5.19, Automatic Text Indent	712
2.1.694	Section 15.5.20, Top and Bottom Margins	712
2.1.695	Section 15.5.21, Margins	714
2.1.696	Section 15.5.22, Break Before and Break After	715
2.1.697	Section 15.5.23, Paragraph Background Color	717
2.1.698	Section 15.5.24, Paragraph Background Image	718
2.1.699	Section 15.5.25, Border	719
2.1.700	Section 15.5.26, Border Line Width	724
2.1.701	Section 15.5.27, Padding	728
2.1.702	Section 15.5.28, Shadow	732
2.1.703	Section 15.5.29, Keep with Next	733
2.1.704	Section 15.5.30, Line Numbering	734
2.1.705	Section 15.5.31, Line Number Start Value	735
2.1.706	Section 15.5.32, Text Autospace	735
2.1.707	Section 15.5.33, Punctuation Wrap	736
2.1.708	Section 15.5.34, Line Break	737
2.1.709	Section 15.5.35, Vertical Alignment	738
2.1.710	Section 15.5.36, Writing Mode	739
2.1.711	Section 15.5.37, Automatic Writing Mode	742
2.1.712	Section 15.5.38, Snap To Layout	743
2.1.713	Section 15.5.39, Page Number	744
2.1.714	Section 15.5.40, Background Transparency	744
2.1.715	Section 15.6, Ruby Text Formatting Properties	745
2.1.716	Section 15.6.1, Ruby Position	746
2.1.717	Section 15.6.2, Ruby Alignment	747
2.1.718	Section 15.7, Section Formatting Properties	748
2.1.719	Section 15.7.1, Section Background	749
2.1.720	Section 15.7.2, Margins	750
2.1.721	Section 15.7.3, Columns	752
2.1.722	Section 15.7.4, Column Specification	753
2.1.723	Section 15.7.5, Column Separator	755
2.1.724	Section 15.7.6, Protect	757
2.1.725	Section 15.7.7, Don't Balance Text Columns	758
2.1.726	Section 15.7.8, Writing Mode	759
2.1.727	Section 15.7.9, Notes Configuration	761
2.1.728	Section 15.8, Table Formatting Properties	761
2.1.729	Section 15.8.1, Table Width	761

2.1.730	Section 15.8.2, Table Alignment	762
2.1.731	Section 15.8.3, Table Left and Right Margin	762
2.1.732	Section 15.8.4, Table Top and Bottom Margin	762
2.1.733	Section 15.8.5, Table Margins	763
2.1.734	Section 15.8.6, Page Number	763
2.1.735	Section 15.8.7, Break Before and Break After.....	763
2.1.736	Section 15.8.8, Table Background and Background Image	764
2.1.737	Section 15.8.9, Table Shadow	764
2.1.738	Section 15.8.10, Keep with Next.....	764
2.1.739	Section 15.8.11, May Break Between Rows	764
2.1.740	Section 15.8.12, Border Model Property.....	765
2.1.741	Section 15.8.13, Writing Mode	765
2.1.742	Section 15.8.14, Display.....	766
2.1.743	Section 15.9, Column Formatting Properties	766
2.1.744	Section 15.9.1, Column Width	766
2.1.745	Section 15.9.2, Optimal Table Column Width.....	767
2.1.746	Section 15.9.3, Break Before and Break After.....	767
2.1.747	Section 15.10, Table Row Formatting Properties	767
2.1.748	Section 15.10.1, Row Height.....	768
2.1.749	Section 15.10.2, Optimal Table Row Height.....	768
2.1.750	Section 15.10.3, Row Background	768
2.1.751	Section 15.10.4, Break Before and Break After	769
2.1.752	Section 15.10.5, Keep Together	769
2.1.753	Section 15.11, Table Cell Formatting Properties.....	770
2.1.754	Section 15.11.1, Vertical Alignment	770
2.1.755	Section 15.11.2, Text Align Source	770
2.1.756	Section 15.11.3, Direction	770
2.1.757	Section 15.11.4, Vertical Glyph Orientation.....	771
2.1.758	Section 15.11.5, Cell Shadow.....	771
2.1.759	Section 15.11.6, Cell Background	771
2.1.760	Section 15.11.7, Cell Border	771
2.1.761	Section 15.11.8, Diagonal Lines.....	774
2.1.762	Section 15.11.9, Border Line Width.....	775
2.1.763	Section 15.11.10, Padding	776
2.1.764	Section 15.11.11, Wrap Option.....	777
2.1.765	Section 15.11.12, Rotation Angle.....	777
2.1.766	Section 15.11.13, Rotation Align.....	777
2.1.767	Section 15.11.14, Cell Protect	778
2.1.768	Section 15.11.15, Print Content.....	778
2.1.769	Section 15.11.16, Decimal places	778
2.1.770	Section 15.11.17, Repeat Content	778
2.1.771	Section 15.11.18, Shrink To Fit	778
2.1.772	Section 15.12, List-Level Style Properties	779
2.1.773	Section 15.13, Stroke Properties	787
2.1.774	Section 15.13.1, Stroke Style.....	788
2.1.775	Section 15.13.2, Dash.....	790
2.1.776	Section 15.13.3, Multiple Dashes.....	791
2.1.777	Section 15.13.4, Width.....	792
2.1.778	Section 15.13.5, Color.....	793
2.1.779	Section 15.13.6, Start Marker	794
2.1.780	Section 15.13.7, End Marker	795
2.1.781	Section 15.13.8, Start Marker Width	795
2.1.782	Section 15.13.9, End Marker Width	795
2.1.783	Section 15.13.10, Start Marker Center	796
2.1.784	Section 15.13.11, End Marker Center	796
2.1.785	Section 15.13.12, Opacity.....	796
2.1.786	Section 15.13.13, Line Join	797
2.1.787	Section 15.14, Fill Properties.....	805

2.1.788	Section 15.14.1, Fill Style	806
2.1.789	Section 15.14.2, Color	811
2.1.790	Section 15.14.3, Secondary Fill Color	812
2.1.791	Section 15.14.4, Gradient	813
2.1.792	Section 15.14.5, Gradient Step Count	813
2.1.793	Section 15.14.6, Hatch	814
2.1.794	Section 15.14.7, Solid Hatch	815
2.1.795	Section 15.14.8, Fill Image	816
2.1.796	Section 15.14.9, Fill Image Rendering Style	817
2.1.797	Section 15.14.10, Fill Image Size	818
2.1.798	Section 15.14.11, Fill Image Tile Reference Point	820
2.1.799	Section 15.14.12, Fill Image Tile Translation	823
2.1.800	Section 15.14.13, None and Linear Opacity	824
2.1.801	Section 15.14.14, Gradient Opacity	824
2.1.802	Section 15.14.15, Fill Rule	825
2.1.803	Section 15.14.16, Symbol color	826
2.1.804	Section 15.15, Text Animation Properties	827
2.1.805	Section 15.15.1, Animation	827
2.1.806	Section 15.15.2, Animation Direction	827
2.1.807	Section 15.15.3, Animation Start Inside	827
2.1.808	Section 15.15.4, Animation Stop Inside	828
2.1.809	Section 15.15.5, Animation Repeat	828
2.1.810	Section 15.15.6, Animation Delay	828
2.1.811	Section 15.15.7, Animation Steps	828
2.1.812	Section 15.16, Text and Text Alignment Properties	828
2.1.813	Section 15.16.1, Auto Grow Width and Height	829
2.1.814	Section 15.16.2, Fit To Size	831
2.1.815	Section 15.16.3, Fit To Contour	832
2.1.816	Section 15.16.4, Text Area Vertical Align	833
2.1.817	Section 15.16.5, Text Area Horizontal Align	834
2.1.818	Section 15.16.6, Word Wrap	835
2.1.819	Section 15.16.7, List Styles	836
2.1.820	Section 15.17, Color Properties	837
2.1.821	Section 15.17.1, Color Mode	837
2.1.822	Section 15.17.2, Color Inversion	839
2.1.823	Section 15.17.3, Adjust Luminance	839
2.1.824	Section 15.17.4, Adjust Contrast	839
2.1.825	Section 15.17.5, Adjust Gamma	840
2.1.826	Section 15.17.6, Adjust Red	840
2.1.827	Section 15.17.7, Adjust Green	840
2.1.828	Section 15.17.8, Adjust Blue	841
2.1.829	Section 15.17.9, Adjust Opacity	841
2.1.830	Section 15.18, Shadow Properties	841
2.1.831	Section 15.18.1, Shadow	842
2.1.832	Section 15.18.2, Offset	843
2.1.833	Section 15.18.3, Color	846
2.1.834	Section 15.18.4, Opacity	847
2.1.835	Section 15.19, Connector Properties	848
2.1.836	Section 15.19.1, Start Line Spacing	848
2.1.837	Section 15.19.2, End Line Spacing	848
2.1.838	Section 15.20, Measure Properties	849
2.1.839	Section 15.20.1, Line Distance	849
2.1.840	Section 15.20.2, Guide Overhang	849
2.1.841	Section 15.20.3, Guide Distance	850
2.1.842	Section 15.20.4, Start Guide	850
2.1.843	Section 15.20.5, End Guide	850
2.1.844	Section 15.20.6, Placing	851
2.1.845	Section 15.20.7, Parallel	851

2.1.846	Section 15.20.8, Text Alignment.....	851
2.1.847	Section 15.20.9, Unit	852
2.1.848	Section 15.20.10, Show Unit.....	852
2.1.849	Section 15.20.11, Decimal Places	852
2.1.850	Section 15.21, Caption Properties	853
2.1.851	Section 15.21.1, Type	853
2.1.852	Section 15.21.2, Angle Type	853
2.1.853	Section 15.21.3, Angle	853
2.1.854	Section 15.21.4, Gap	854
2.1.855	Section 15.21.5, Escape Direction.....	854
2.1.856	Section 15.21.6, Escape	854
2.1.857	Section 15.21.7, Line Length.....	855
2.1.858	Section 15.21.8, Fit Line Length	855
2.1.859	Section 15.22, 3D Geometry Properties.....	855
2.1.860	Section 15.22.1, Horizontal Segments.....	855
2.1.861	Section 15.22.2, Vertical Segments	856
2.1.862	Section 15.22.3, Edge Rounding	856
2.1.863	Section 15.22.4, Edge Rounding Mode.....	856
2.1.864	Section 15.22.5, Back Scale.....	857
2.1.865	Section 15.22.6, Depth	857
2.1.866	Section 15.22.7, Backface Culling	857
2.1.867	Section 15.22.8, End Angle	857
2.1.868	Section 15.22.9, Close Front	858
2.1.869	Section 15.22.10, Close Back	858
2.1.870	Section 15.23, 3D Lighting Properties.....	858
2.1.871	Section 15.23.1, Mode	858
2.1.872	Section 15.23.2, Normals Kind	859
2.1.873	Section 15.23.3, Normals Direction	859
2.1.874	Section 15.24, 3D Texture Properties	859
2.1.875	Section 15.24.1, Generation Mode	860
2.1.876	Section 15.24.2, Kind.....	860
2.1.877	Section 15.24.3, Filter.....	860
2.1.878	Section 15.24.4, Mode	861
2.1.879	Section 15.25, 3D Material Properties.....	861
2.1.880	Section 15.25.1, Colors	861
2.1.881	Section 15.25.2, Shininess.....	862
2.1.882	Section 15.26, 3D Shadow Properties.....	862
2.1.883	Section 15.26.1, Shadow.....	863
2.1.884	Section 15.27, Frame Formatting Properties.....	863
2.1.885	Section 15.27.1, Frame Widths.....	863
2.1.886	Section 15.27.2, Frame Heights.....	864
2.1.887	Section 15.27.3, Maximum Width and Height	865
2.1.888	Section 15.27.4, Left and Right Margins	866
2.1.889	Section 15.27.5, Top and Bottom Margins.....	868
2.1.890	Section 15.27.6, Margins	870
2.1.891	Section 15.27.7, Print Content	871
2.1.892	Section 15.27.8, Protect	871
2.1.893	Section 15.27.9, Horizontal Position	875
2.1.894	Section 15.27.10, Horizontal Relation.....	875
2.1.895	Section 15.27.11, Vertical Position	877
2.1.896	Section 15.27.12, Vertical Relation	877
2.1.897	Section 15.27.14, Border.....	878
2.1.898	Section 15.27.15, Border Line Width	880
2.1.899	Section 15.27.16, Padding	882
2.1.900	Section 15.27.17, Shadow	887
2.1.901	Section 15.27.18, Background.....	888
2.1.902	Section 15.27.19, Columns	888
2.1.903	Section 15.27.20, Editable.....	889

2.1.904	Section 15.27.21, Wrapping	890
2.1.905	Section 15.27.22, Dynamic Wrap Threshold	890
2.1.906	Section 15.27.23, Paragraph-only Wrapping	890
2.1.907	Section 15.27.24, Contour Wrapping	890
2.1.908	Section 15.27.25, Contour Wrapping Mode	891
2.1.909	Section 15.27.26, Run Through	891
2.1.910	Section 15.27.27, Flow with Text	891
2.1.911	Section 15.27.28, Overflow behavior	891
2.1.912	Section 15.27.29, Mirroring	891
2.1.913	Section 15.27.30, Clipping	895
2.1.914	Section 15.27.31, Wrap Influence on Position	896
2.1.915	Section 15.27.32, Writing Mode	896
2.1.916	Section 15.28, Floating Frame Formatting Properties	898
2.1.917	Section 15.28.1, Display Scrollbar	898
2.1.918	Section 15.28.2, Display Border	898
2.1.919	Section 15.28.3, Margins	899
2.1.920	Section 15.28.4, Object Formatting Properties	899
2.1.921	Section 15.28.5, Visible Area	899
2.1.922	Section 15.28.6, Draw Aspect	899
2.1.923	Section 15.29, Chart Formatting Properties	899
2.1.924	Section 15.30.3, Chart Symbol	900
2.1.925	Section 15.31, Chart Axes Properties	900
2.1.926	Section 15.32, Common Chart Properties	900
2.1.927	Section 15.33, Statistical Properties	900
2.1.928	Section 15.34, Plot Area Properties	900
2.1.929	Section 15.35, Regression Curve Properties	900
2.1.930	Section 15.36, Presentation Page Attributes	900
2.1.931	Section 15.36.1, Transition Type	900
2.1.932	Section 15.36.2, Transition Style	901
2.1.933	Section 15.36.3, Transition Speed	906
2.1.934	Section 15.36.4, Transition Type or Family	906
2.1.935	Section 15.36.5, Transition Subtype	910
2.1.936	Section 15.36.6, Transition Direction	910
2.1.937	Section 15.36.7, Fade Color	910
2.1.938	Section 15.36.8, Page Duration	910
2.1.939	Section 15.36.9, Page Visibility	911
2.1.940	Section 15.36.10, Sound	911
2.1.941	Section 15.36.11, Background Size	911
2.1.942	Section 15.36.12, Background Objects Visible	911
2.1.943	Section 15.36.13, Background Visible	911
2.1.944	Section 15.36.14, Display Header	911
2.1.945	Section 15.36.15, Display Footer	911
2.1.946	Section 15.36.16, Display Page Number	912
2.1.947	Section 15.36.17, Display Date And Time	912
2.1.948	Section 16, Data Types and Schema Definitions	912
2.1.949	Section 16.1, Data Types	912
2.1.950	Section 16.2, Other Definitions	912
2.1.951	Section 16.3, Relax-NG Schema Suffix	913
2.1.952	Section 17, Packages	913
2.1.953	Section 17.1, Introduction	913
2.1.954	Section 17.2, Zip File Structure	913
2.1.955	Section 17.3, Encryption	913
2.1.956	Section 17.4, MIME Type Stream	914
2.1.957	Section 17.5, Usage of IRIs Within Packages	914
2.1.958	Section 17.6, Preview Image	914
2.1.959	Section 17.7, Manifest File	914
2.1.960	Section 17.7.1, Relax-NG Schema	914
2.1.961	Section 17.7.2, Manifest Root Element	914

2.1.962	Section 17.7.3, File Entry	914
2.1.963	Section 17.7.4, Encryption Data	915
2.1.964	Section 17.7.5, Algorithm	915
2.1.965	Section 17.7.6, Key Derivation	915
2.1.966	Section 17.7.7, Relax-NG Schema Suffix	915
2.1.967	Section Appendix E, Accessibility Guidelines (Non Normative)	915
2.1.968	Section Appendix E.1, Title, Description and Caption of Graphical Elements	915
2.1.969	Section Appendix E.2, Hyperlink Titles.....	916
2.1.970	Section Appendix E.4, Further Guidelines.....	917
3	Change Tracking.....	918
4	Index.....	920

1 Introduction

In creating an interoperable implementation, it may be helpful to understand specific implementation choices made by other products implementing the same standard. For example, portions of the standard may provide only general guidance, leaving specific implementation choices up to the application implementer; in some circumstances, it may be helpful for other implementers to understand those choices. In addition, products often vary from or extend standards either because of application deviations or to allow for use scenarios not originally envisioned by the specifications. Documentation of those variations and/or extensions may also be helpful to other implementers.

The implementer notes contained in this document provide information about how Office implements Open Document Format for Office Applications (OpenDocument) v1.1 [ODF], including areas where additional detail may be of benefit to other implementers and areas where the product is known to vary from or extend the specification.

1.1 Glossary

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[ISO/IEC-29500-1] International Organization for Standardization, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Part 1: Fundamentals and Markup Language Reference", ISO/IEC 29500-1:2008, http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=51463

[ISO/IEC-29500:2008] International Organization for Standardization, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Parts 1-4", ISO/IEC 29500-1:2008, http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=51463

[MathML2.0] Ausbrooks, R., et al., "Mathematical Markup Language (MathML) Version 2.0 (Second Edition)", W3C Recommendation, October 2003, <http://www.w3.org/TR/2003/REC-MathML2-20031021/>

[ODF] OASIS, "Open Document Format for Office Applications (OpenDocument) v1.1", 1 February 2007, <http://docs.oasis-open.org/office/v1.1/OS/OpenDocument-v1.1-html/OpenDocument-v1.1.html>

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3986] Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", STD 66, RFC 3986, January 2005, <http://www.ietf.org/rfc/rfc3986.txt>

1.2.2 Informative References

None.

1.3 Microsoft Implementations

Microsoft Excel 2010

Microsoft Excel 2013

Microsoft Excel 2016

Microsoft PowerPoint 2010

Microsoft PowerPoint 2013

Microsoft PowerPoint 2016

Microsoft Word 2010

Microsoft Word 2013

Microsoft Word 2016

2 Conformance Statements

This section contains implementation information about how Microsoft® Office Excel® 2010, Microsoft® Office PowerPoint® 2010, Microsoft® Office Word 2010, Microsoft® Office Excel® 2013, Microsoft® Office PowerPoint® 2013, Microsoft® Office Word 2013, Microsoft® Office Excel® 2016, Microsoft® Office PowerPoint® 2016, and Microsoft® Office Word 2016 implement Open Document Format for Office Applications (OpenDocument) v1.1. Unless otherwise specified, implementation information in this document pertains to both client and server implementations of both Office 2010, Office 2013 and Office 2016 versions of the Microsoft Excel, Word and PowerPoint Products.

2.1 Normative Variations

2.1.1 Section 2, Document Structure

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.2 Section 2.1.1, Document Root Element Content Models

- a. *The standard defines the element <office:document>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <office:document-content>*

This element is supported in Word 2010 and Word 2013.

- c. *The standard defines the element <office:document-meta>*

This element is supported in Word 2010 and Word 2013.

- d. *The standard defines the element <office:document-settings>*

This element is supported in Word 2010 and Word 2013.

- e. *The standard defines the element <office:document-styles>*

This element is supported in Word 2010 and Word 2013.

- f. *The standard defines the element <office:document>*

This element is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the element <office:document-content>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the element <office:document-meta>*

This element is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the element <office:document-settings>*

This element is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the element <office:document-styles>*

This element is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the element <office:document>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the element <office:document-content>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- m. *The standard defines the element <office:document-meta>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- n. *The standard defines the element <office:document-settings>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- o. *The standard defines the element <office:document-styles>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.3 Section 2.1.2, Document Root Attributes

- a. *The standard defines the attribute office:mimetype, contained within the element <office:document-content>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute office:version, contained within the element <office:document-content>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute office:mimetype, contained within the element <office:document-meta>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute office:version, contained within the element <office:document-meta>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word ignores this attribute.

On save, Word always writes a value of "1.1" for this attribute.

- e. *The standard defines the attribute office:mimetype, contained within the element <office:document-settings>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute office:version, contained within the element <office:document-settings>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word ignores this attribute.

On save, Word always writes a value of "1.1" for this attribute.

- g. *The standard defines the attribute office:mimetype, contained within the element <office:document-styles>*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute `office:version`, contained within the element `<office:document-styles>`*
- This attribute is not supported in Word 2010 or Word 2013.
- i. *The standard defines the attribute `office:mimetype`, contained within the element `<office:document-content>`*
- This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute `office:version`, contained within the element `<office:document-content>`*
- This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute `office:mimetype`, contained within the element `<office:document-meta>`*
- This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute `office:version`, contained within the element `<office:document-meta>`*
- This attribute is supported in Excel 2010 and Excel 2013.
- On load, Excel ignores this attribute.
- On save, Excel always writes a value of "1.1" for this attribute.
- m. *The standard defines the attribute `office:mimetype`, contained within the element `<office:document-styles>`*
- This attribute is not supported in Excel 2010 or Excel 2013.
- n. *The standard defines the attribute `office:version`, contained within the element `<office:document-styles>`*
- This attribute is not supported in Excel 2010 or Excel 2013.
- o. *The standard defines the attribute `office:mimetype`, contained within the element `<office:document-content>`*
- This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- p. *The standard defines the attribute `office:version`, contained within the element `<office:document-content>`*
- This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- q. *The standard defines the attribute `office:mimetype`, contained within the element `<office:document-meta>`*
- This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- r. *The standard defines the attribute `office:version`, contained within the element `<office:document-meta>`*
- This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- On load, PowerPoint ignores this attribute.
- On save, PowerPoint always writes a value of "1.1" for this attribute.

- s. *The standard defines the attribute `office:mimetype`, contained within the element `<office:document-settings>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- t. *The standard defines the attribute `office:version`, contained within the element `<office:document-settings>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- u. *The standard defines the attribute `office:mimetype`, contained within the element `<office:document-styles>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- v. *The standard defines the attribute `office:version`, contained within the element `<office:document-styles>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.4 Section 2.2, Document Metadata

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.5 Section 2.2.1, Pre-Defined vs. Custom Metadata

- a. This is not supported in Word 2010 or Word 2013.

On load Word ignores custom metadata, therefore the metadata is lost on save.

- b. This is not supported in Excel 2010 or Excel 2013.

On load, Excel ignores custom metadata, therefore the metadata is lost on save.

- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

On load, PowerPoint ignores custom metadata, therefore the metadata is lost on save.

2.1.6 Section 2.3, Body Element and Document Types

- a. *The standard defines the element `<office:body>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element `<office:body>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.7 Section 2.3.1, Text Documents

- a. *The standard defines the element `<office:text>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `text:global`, contained within the element `<office:text>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `text:use-soft-page-breaks`, contained within the element `<office:text>`*

This attribute is supported in Word 2010 and Word 2013.

2.1.8 Section 2.3.2, Drawing Documents

- a. *The standard defines the element `<office:drawing>`*

This element is not supported in Word 2010 or Word 2013.

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<office:drawing>`*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element `<office:drawing>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.9 Section 2.3.3, Presentation Documents

- a. *The standard defines the element `<office:presentation>`*

This element is not supported in Word 2010 or Word 2013.

- b. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.10 Section 2.3.4, Spreadsheet Documents

- a. *The standard defines the element `<office:spreadsheet>`*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<office:spreadsheet>`*

This element is supported in Excel 2010 and Excel 2013.

2.1.11 Section 2.3.5, Chart Documents

- a. *The standard defines the element `<office:chart>`*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<office:chart>`, contained within the parent element `<office:body>`*

This element is supported in Excel 2010 and Excel 2013.

2.1.12 Section 2.3.6, Image Documents

- a. *The standard defines the element `<office:image>`*

This element is not supported in Word 2010 or Word 2013.

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <office:image>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <office:image>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.13 Section 2.4, Application Settings

- a. *The standard defines the element <office:settings>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <<office:settings>>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.14 Section 2.4.1, Sequence of Settings

- a. *The standard defines the element <config:config-item-set>, contained within the parent element <office:settings>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.15 Section 2.4.2, Base Settings

- a. *The standard defines the element <config:config-item>, contained within the parent element <office:settings>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.16 Section 2.4.3, Index Access of Sequences

- a. *The standard defines the element <config:config-item-map-indexed>, contained within the parent element <office:settings>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.17 Section 2.4.4, Map Entry

- a. *The standard defines the element <config:config-item-map-entry>, contained within the parent element <office:settings>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.18 Section 2.4.5, Name Access of Sequences

- a. *The standard defines the element <config:config-item-map-named>, contained within the parent element <office:settings>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.19 Section 2.4.6, Cursor Position Setting

- a. *The standard defines the attribute view-id, contained within the element <opendocument cursor-position>*

This attribute is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.20 Section 2.5, Scripts

- a. This is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the element <<office:script>>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.21 Section 2.5.1, Script

- a. *The standard defines the element <office:script>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.22 Section 2.6, Font Face Declarations

- a. *The standard defines the element <office:font-face-decls>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels. On save, font face declarations are not written out. Instead, the fo:font-family property is used to specify font face.

- b. *The standard defines the element <office:font-face-decls>*

This element is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, chart titles and labels. It is supported on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Font face declarations are only supported on read and are not written out. Instead, the fo:font-family property is used to specify font face on write.

- c. *The standard defines the element <<style:font-face>>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the element <office:font-face-decls>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

Font face declarations are supported only on read, and are not written out. Instead, the "fo:font-family" property is used to specify font face on write.

2.1.23 Section 2.7, Styles

- a. This is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.

- b. This is supported in Excel 2010 and Excel 2013.

This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.24 Section 2.7.1, Location of Styles

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
- b. *The standard defines the element <office:automatic-styles>*

This element is supported in Word 2010 and Word 2013.

Word 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

- c. *The standard defines the element <office:master-styles>*

This element is supported in Word 2010 and Word 2013.

- d. *The standard defines the element <office:styles>*

This element is supported in Word 2010 and Word 2013.

Word 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

- e. OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the element <office:automatic-styles>*

This element is supported in Excel 2010 and Excel 2013.

Excel 2013 supports this element for <style:style> and <style:default-style> elements

when the <style:family> attribute has a value of "graphic".

g. *The standard defines the element <office:master-styles>*

This element is supported in Excel 2010 and Excel 2013.

h. *The standard defines the element <office:styles>*

This element is supported in Excel 2010 and Excel 2013.

Excel 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

i. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

j. *The standard defines the element <<office:automatic-styles>>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is used for all of the formatting styles in both the content and in the masters/layouts.

k. *The standard defines the element <<office:master-styles>>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This location is used to store all of the master pages and layouts.

l. *The standard defines the element <<office:styles>>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

Only the default style and the presentation page layouts are stored here. All others are stored in automatic or master styles.

m. *The standard defines the element <office:automatic-styles>*

PowerPoint 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

n. *The standard defines the element <office:styles>*

PowerPoint 2013 supports this element for <style:style> and <style:default-style> elements when the <style:family> attribute has a value of "graphic".

2.1.25 Section 2.8, Page Styles and Layout

- a. This is supported in Excel 2010 and Excel 2013.
- b. This is supported in PowerPoint 2010 and PowerPoint 2013.

Master pages are assigned to drawing pages using the style:master-page-name attribute rather than the style:parent-style-name attribute.

2.1.26 Section 3, Metadata Elements

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.27 Section 3.1, Pre-Defined Metadata Elements

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.28 Section 3.1.1, Generator

- a. This is supported in Word 2010 and Word 2013.

Word does not support MathML entities. Only unicode characters are used.

- b. *The standard defines the element <meta:generator>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.29 Section 3.1.2, Title

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <dc:title>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.30 Section 3.1.3, Description

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <dc:description>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.31 Section 3.1.4, Subject

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <dc:subject>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.32 Section 3.1.5, Keywords

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <meta:keyword>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.33 Section 3.1.6, Initial Creator

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <meta:initial-creator>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.34 Section 3.1.7, Creator

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <dc:creator>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.35 Section 3.1.8, Printed By

- a. *The standard defines the element <meta:printed-by>*
This element is not supported in Word 2010 or Word 2013.
Word does not save this property.
- b. *The standard defines the element <meta:printed-by>*
This element is not supported in Excel 2010 or Excel 2013.
Excel does not save this property.
- c. *The standard defines the element <meta:printed-by>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
PowerPoint does not save this property.

2.1.36 Section 3.1.9, Creation Date and Time

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <meta:creation-date>, contained within the parent element <office:meta-data>*
This element is supported in Word 2010 and Word 2013.
- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.37 Section 3.1.10, Modification Date and Time

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <dc:date>, contained within the parent element <office:meta-data>*
This element is supported in Word 2010 and Word 2013.
- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.38 Section 3.1.11, Print Date and Time

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <meta:print-date>, contained within the parent element <office:meta-data>*
This element is supported in Word 2010 and Word 2013.
- c. This is supported in Excel 2010 and Excel 2013.
- d. *The standard defines the element <meta:print-date>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.39 Section 3.1.12, Document Template

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <meta:template>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. *The standard defines the element <meta:template>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.40 Section 3.1.13, Automatic Reload

- a. *The standard defines the element <meta:auto-reload>*

This element is not supported in Word 2010 or Word 2013.

Word does not save this property.

- b. *The standard defines the element <meta:auto-reload>*

This element is not supported in Excel 2010 or Excel 2013.

Excel does not save this property.

- c. *The standard defines the element <meta:auto-reload>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint does not save this property.

2.1.41 Section 3.1.14, Hyperlink Behavior

- a. *The standard defines the element <meta:hyperlink-behaviour>*

This element is not supported in Word 2010 or Word 2013.

Word does not save this property.

- b. *The standard defines the element <meta:hyperlink-behaviour>*

This element is not supported in Excel 2010 or Excel 2013.

Excel does not save this property.

- c. *The standard defines the element <meta:hyperlink-behaviour>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint does not save this property.

2.1.42 Section 3.1.15, Language

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <dc:language>, contained within the parent element <office:meta-data>*

This element is not supported in Word 2010 or Word 2013.

- c. This is not supported in Excel 2010 or Excel 2013.
- d. This is not supported in PowerPoint 2010 or PowerPoint 2013.
- e. *The standard defines the element <dc:language>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.43 Section 3.1.16, Editing Cycles

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <meta:editing-cycles>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.
- e. *The standard defines the element <meta:editing-cycles>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.44 Section 3.1.17, Editing Duration

- a. This is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <meta:editing-duration>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.
- d. This is supported in PowerPoint 2010 and PowerPoint 2013.
- e. *The standard defines the element <meta:editing-duration>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.45 Section 3.1.18, Document Statistics

- a. *The standard defines the element <meta:document-statistic>*

Word loads/saves the following statistics for Text documents:

meta:page-count

meta:paragraph-count

meta:word-count

meta:character-count

meta:row-count

meta:non-whitespace-character-count

- b. *The standard defines the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This element is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute meta:image-count, contained within the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute meta:object-count, contained within the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute meta:page-count, contained within the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute meta:paragraph-count, contained within the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute meta:word-count, contained within the element <meta:document-statistic>, contained within the parent element <office:meta-data>*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the element <meta:document-statistic>*

Excel loads and saves the following statistic for Spreadsheet documents: "meta:page-count"

- i. *The standard defines the element <meta:document-statistic>*

PowerPoint loads/saves the following statistics for Graphic documents: the "meta:page-count" attribute.

- j. *The standard defines the attribute meta:page-count, contained within the element <meta:document-statistic>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.46 Section 3.2, User-defined Metadata

- a. *The standard defines the element <meta:user-defined>*

This element is supported in Word 2010 and Word 2013.

Word supports the creation of user defined metadata in the following variant types: string, float, date, and boolean.

- b. *The standard defines the element <meta:user-defined>*

This element is supported in Excel 2010 and Excel 2013.

Excel supports the creation of user defined metadata in the following variant types: string, float, date, and boolean.

- c. *The standard defines the element <meta:user-defined>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports the creation of user defined metadata in the following variant types: string, float, date, and boolean.

2.1.47 Section 3.3, Custom Metadata

- a. This is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.48 Section 4, Text Content

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
- b. This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:measure>
 - <draw:frame>
 - <draw:text-box>
 - <draw:custom-shape>
- c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:
 - <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:measure>
 - <draw:text-box>
 - <draw:frame>
 - <draw:custom-shape>

2.1.49 Section 4.1, Headings, Paragraphs and Basic Text Structure

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
- b. This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.50 Section 4.1.1, Headings

a. *The standard defines the element <text:h>*

This element is supported in Word 2010 and Word 2013.

1. Word allows multiple styles to map to the same outline level. According to the ODF 1.1 spec, each outline level may only have one style associated with it.

On save, Word takes the following steps to determine which style should be included for each level under the outline style element:

First, Word looks for styles named "Heading 1" to "Heading 9" to see if any of them have numbering as a part of the style. If one of these styles has numbering, then that style is associated with the corresponding level in the outline style.

Next, Word looks for other styles to see if any of them have an outline level and numbering. If so, the first style that encountered with both a unique outline level and numbering is put into the outline-style.

2. On save, Word writes out text content within a <text:h> element under the following conditions:
 - the paragraph has an outline level
 - the paragraph's style is referenced by the outline style
3. On save, paragraphs with numbering, whose style is not in the outline-style but have a style:default-outline-level attribute in their paragraph style, are written out with <text:p> within a list.

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `text:is-list-header`, contained within the element `<text:h>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `text:number`, contained within the element `<text:h>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `text:outline-level`, contained within the element `<text:h>`*

This attribute is supported in Word 2010 and Word 2013.

On save, if the numbering applied to a set of headings (via outline level) is not continuous, Word outputs the missing numbers as numbered blank paragraphs--- for example:

1. first item
2. second item
3. third item

is output as follows:

1. first item
2. second item

3.

3. third item

- e. *The standard defines the attribute `text:restart-numbering`, contained within the element `<text:h>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute `text:start-value`, contained within the element `<text:h>`*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the element `<text:h>`*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- h. *The standard defines the element `<text:h>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.51 Section 4.1.2, Paragraphs

- a. *The standard defines the element <text:p>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <text:p>, contained within the parent element <draw:custom-shape>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the element <text:p>, contained within the parent element <text:list-item>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt.

- d. *The standard defines the element <text:p>*

This element is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the element <text:p>, contained within the parent element <chart:chart \..\table:table \..\text-p>*

This element is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the element <text:p>, contained within the parent element <draw:caption>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the element <text:p>, contained within the parent element <draw:circle>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the element <text:p>, contained within the parent element <draw:connector>*

This element is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the element <text:p>, contained within the parent element <draw:custom-shape>*

This element is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the element <text:p>, contained within the parent element <draw:ellipse>*

This element is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the element <text:p>, contained within the parent element <draw:image>*

This element is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the element <text:p>, contained within the parent element <draw:line>*

This element is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the element <text:p>, contained within the parent element <draw:measure>*

This element is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the element <text:p>, contained within the parent element <draw:path>*

This element is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the element <text:p>, contained within the parent element <draw:polygon>*

This element is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the element <text:p>, contained within the parent element <draw:polyline>*

This element is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the element <text:p>, contained within the parent element <draw:rect>*

This element is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the element <text:p>, contained within the parent element <draw:regular-polygon>*

This element is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the element <text:p>, contained within the parent element <draw:text-box>*

This element is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the element <text:p>, contained within the parent element <text:list-header>*

OfficeArt Math in Excel 2013 supports this element on save, for text in text boxes and shapes. It is supported on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The text:list-header property is only supported on load and is not saved.

- u. *The standard defines the element <text:p>, contained within the parent element <text:list-item>*
- OfficeArt Math in Excel 2013 supports this element on save for text in text boxes, shapes, and SmartArt. On load, it is supported for text in the following elements:
- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:measure>
 - <draw:frame>
 - <draw:text-box>
 - <draw:custom-shape>
- v. *The standard defines the element <text:p>, contained within the parent element <draw:caption>*
- This element is supported in PowerPoint 2010 and PowerPoint 2013.
- w. *The standard defines the element <text:p>, contained within the parent element <draw:circle>*
- This element is supported in PowerPoint 2010 and PowerPoint 2013.
- x. *The standard defines the element <text:p>, contained within the parent element <draw:connector>*
- This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- y. *The standard defines the element <text:p>, contained within the parent element <draw:custom-shape>*
- This element is supported in PowerPoint 2010 and PowerPoint 2013.
- z. *The standard defines the element <text:p>, contained within the parent element <draw:ellipse>*
- This element is supported in PowerPoint 2010 and PowerPoint 2013.
- aa. *The standard defines the element <text:p>, contained within the parent element <draw:image>*
- This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- bb. *The standard defines the element <text:p>, contained within the parent element <draw:line>*
- This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- cc. *The standard defines the element <text:p>, contained within the parent element <draw:measure>*
- This element is supported in PowerPoint 2010 and PowerPoint 2013.
- dd. *The standard defines the element <text:p>, contained within the parent element <draw:path>*
- This element is supported in PowerPoint 2010 and PowerPoint 2013.
- ee. *The standard defines the element <text:p>, contained within the parent element <draw:polygon>*
- This element is supported in PowerPoint 2010 and PowerPoint 2013.

ff. *The standard defines the element <text:p>, contained within the parent element <draw:polyline>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

gg. *The standard defines the element <text:p>, contained within the parent element <draw:rect>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

hh. *The standard defines the element <text:p>, contained within the parent element <draw:regular-polygon>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

ii. *The standard defines the element <text:p>, contained within the parent element <draw:text-box>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

jj. *The standard defines the element <text:p>, contained within the parent element <text:list-header>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text:list-header" property is supported only on read and is not written out.

kk. *The standard defines the element <text:p>, contained within the parent element <text:list-item>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.52 Section 4.1.3, Common Paragraph Elements Attributes

a. *The standard defines the attribute text:class-names, contained within the element <text:p>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The text:math-class-names attribute is always written as empty.

- b. *The standard defines the attribute text:cond-style-name, contained within the element <text:p>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The text:cond-style-name attribute is always written as empty.

- c. *The standard defines the attribute text:style-name, contained within the element <text:p>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute text:class-names, contained within the element <text:p>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save, for text in text boxes, shapes, SmartArt, chart titles and labels. On load, it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The text:math-class-names attribute is always written as empty and is not supported on read.

- e. *The standard defines the attribute text:cond-style-name, contained within the element <text:p>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save, for text in text boxes, shapes, SmartArt, and chart titles and labels. On load, it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The text:cond-style-name attribute is always written as empty and is not supported on read.

- f. *The standard defines the attribute text:style-name, contained within the element <text:p>*

This attribute is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute text-id, contained within the element <text:p>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute text:class-names, contained within the element <text:p>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text:class-names" attribute is always written and empty, and is not supported on read.

- i. *The standard defines the attribute text:cond-style-name, contained within the element <text:p>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text:cond-style-name" attribute is always written as empty and is not supported on read.

- j. *The standard defines the attribute text:style-name, contained within the element <text:p>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.53 Section 4.2, Page Sequences

- a. *The standard defines the element <text:page-sequence>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:page-sequence>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.54 Section 4.2.1, Page

- a. *The standard defines the element <text:page>, contained within the parent element <text:page-sequence>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:page>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.55 Section 4.3, Lists

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt.

- b. This is not supported in Excel 2010 or Excel 2013.

This is supported in Excel 2010 and Excel 2013.

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.56 Section 4.3.1, List Block

- a. *The standard defines the element <text:list>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <text:list>, contained within the parent element <text:list>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt.

- c. *The standard defines the attribute text:continue-numbering, contained within the element <text:list>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute text:style-name, contained within the element <text:list>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- e. This is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the element <text:list>, contained within the parent element <draw:caption>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the element <text:list>, contained within the parent element <draw:circle>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the element <text:list>, contained within the parent element <draw:connector>*

This element is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the element <text:list>, contained within the parent element <draw:custom-shape>*

This element is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the element <text:list>, contained within the parent element <draw:ellipse>*

This element is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the element <text:list>, contained within the parent element <draw:image>*

This element is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the element <text:list>, contained within the parent element <draw:line>*

This element is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the element <text:list>, contained within the parent element <draw:measure>*

This element is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the element <text:list>, contained within the parent element <draw:path>*

This element is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the element <text:list>, contained within the parent element <draw:polygon>*

This element is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the element <text:list>, contained within the parent element <draw:polyline>*

This element is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the element <text:list>, contained within the parent element <draw:rect>*

This element is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the element <text:list>, contained within the parent element <draw:regular-polygon>*

This element is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the element <text:list>, contained within the parent element <draw:text-box>*

This element is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the element <text:list>, contained within the parent element <text:list>*

This element is supported in Excel 2010 and Excel 2013.

- u. *The standard defines the attribute text:continue-numbering, contained within the element <text:list>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

- v. *The standard defines the attribute text:style-name, contained within the element <text:list>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

- w. *The standard defines the element <text:list>, contained within the parent element <draw:caption>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- x. *The standard defines the element <text:list>, contained within the parent element <draw:circle>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- y. *The standard defines the element <text:list>, contained within the parent element <draw:connector>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- z. *The standard defines the element <text:list>, contained within the parent element <draw:custom-shape>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- aa. *The standard defines the element <text:list>, contained within the parent element <draw:ellipse>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- bb. *The standard defines the element <text:list>, contained within the parent element <draw:image>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- cc. *The standard defines the element <text:list>, contained within the parent element <draw:line>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- dd. *The standard defines the element <text:list>, contained within the parent element <draw:measure>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- ee. *The standard defines the element <text:list>, contained within the parent element <draw:path>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- ff. *The standard defines the element <text:list>, contained within the parent element <draw:polygon>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- gg. *The standard defines the element <text:list>, contained within the parent element <draw:polyline>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- hh. *The standard defines the element <text:list>, contained within the parent element <draw:rect>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- ii. *The standard defines the element <text:list>, contained within the parent element <draw:regular-polygon>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- jj. *The standard defines the element <text:list>, contained within the parent element <draw:text-box>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- kk. *The standard defines the element <text:list>, contained within the parent element <text:list>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- ll. *The standard defines the attribute text:continue-numbering, contained within the element <text:list>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- mm. *The standard defines the attribute text:style-name, contained within the element <text:list>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.57 Section 4.3.2, List Item

- a. *The standard defines the element <text:list-item>, contained within the parent element <text:list>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:start-value, contained within the element <text:list-item>, contained within the parent element <text:list>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the element <text:number>, contained within the parent element <text:list-item>*

This element is not supported in Word 2010 or Word 2013.

- d. This is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute text:start-value, contained within the element <text:list-item>, contained within the parent element <text:list>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

- f. *The standard defines the element <text:number>, contained within the parent element <text:list-item>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- g. *The standard defines the attribute text:start-value, contained within the element <text:list-item>, contained within the parent element <text:list>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- h. *The standard defines the element <text:number>, contained within the parent element <text:list-item>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.58 Section 4.3.3, List Header

- a. *The standard defines the element <text:list-header>, contained within the parent element <text:list>*

This element is not supported in Word 2010 or Word 2013.

On load, Word drops the <text:list-header> element but retains the content of the tags as a paragraph.

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:list-header>, contained within the parent element <text:list>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- d. *The standard defines the element <text:list-header>, contained within the parent element <text:list>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The "text:list-header" attribute is supported on load, but is not saved. To achieve the same effect on save, level 0 list items are saved as a regular paragraphs, that is <text:p> elements, and text greater than level 0 is assigned a list style with an empty "style:num-format" attribute (style:num-format="").

2.1.59 Section 4.3.4, Numbered Paragraphs

- a. *The standard defines the element <text:numbered-paragraph>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute text:level, contained within the element <text:numbered-paragraph>*

- c. This is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute text:level, contained within the element <text:numbered-paragraph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute text:level, contained within the element <text:numbered-paragraph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.60 Section 4.4, Text Sections

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:section>*

This element is supported in Word 2010 and Word 2013.

On save, a continuous section in Word is mapped to the <text:section> element. The following properties are preserved: left and right margins, columns, and text direction.

- c. *The standard defines the element <text:section>, contained within the parent element <draw:text-box>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <text:section>, contained within the parent element <style:drop-cap>*

This element is not supported in Word 2010 or Word 2013.

- e. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the element <text:section>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.61 Section 4.4.1, Section Attributes

- a. *The standard defines the element <text:section>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute text:condition, contained within the element <text:section>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute text:display, contained within the element <text:section>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute text:name, contained within the element <text:section>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute text:protected, contained within the element <text:section>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute text:protection-key, contained within the element <text:section>*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute text:style-name, contained within the element <text:section>*

This attribute is supported in Word 2010 and Word 2013.

h. This is not supported in Excel 2010 or Excel 2013.

i. *The standard defines the element <text:section>*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

j. *The standard defines the element <text:section>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.62 Section 4.4.2, Section Source

a. *The standard defines the element <text:section-source>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <text:section-source>, contained within the parent element <text:section>*

This element is not supported in Word 2010 or Word 2013.

c. This is not supported in Excel 2010 or Excel 2013.

d. *The standard defines the element <text:section-source>*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

e. *The standard defines the element <text:section-source>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.63 Section 4.4.3, DDE Source

- a. *The standard defines the element <office:dde-source>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:section-source-dde>, contained within the parent element <text:section>*

This element is not supported in Word 2010 or Word 2013.

- c. This is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the element <office:dde-source>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the element <office:dde-source>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.64 Section 4.5, Page-bound graphical content

- a. This is not supported in Excel 2010 or Excel 2013.

2.1.65 Section 4.6, Change Tracking

- a. This is not supported in Excel 2010 or Excel 2013.

- b. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.66 Section 4.6.1, Tracked Changes

- a. *The standard defines the element <text:track-changes>*

This element is not supported in Word 2010 or Word 2013.

On load and save, Word automatically accepts any tracked changes and applies the changes to the document.

- b. *The standard defines the element <text:tracked-changes>*

This element is not supported in Word 2010 or Word 2013.

- c. This is not supported in Excel 2010 or Excel 2013.
- d. *The standard defines the element <text:tracked-changes>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.67 Section 4.6.2, Changed Regions

- a. *The standard defines the element <text:changed-region>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.

2.1.68 Section 4.6.3, Insertion

- a. *The standard defines the element <text:insertion>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.

2.1.69 Section 4.6.4, Deletion

- a. *The standard defines the element <text:deletion>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.

2.1.70 Section 4.6.5, Format Change

- a. *The standard defines the element <text:format-change>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.

2.1.71 Section 4.6.6, Change Info

- a. This is not supported in Excel 2010 or Excel 2013.

2.1.72 Section 4.6.7, Change Marks

- a. *The standard defines the element <text:change>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <text:change-end>*
This element is not supported in Word 2010 or Word 2013.
- c. *The standard defines the element <text:change-start>*
This element is not supported in Word 2010 or Word 2013.
- d. This is not supported in Excel 2010 or Excel 2013.

2.1.73 Section 4.7, Soft Page Break

- a. *The standard defines the element <text:soft-page-break>*

This element is supported in Word 2010 and Word 2013.

On save, Word puts a <text:soft-page-break> element everywhere it would normally mark a soft page break location for all of its other document formats. For ODF, this is only done if <text:soft-page-break> is allowed in that location by the ODF specification.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:soft-page-break>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the element <text:soft-page-break>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.74 Section 4.8, Text Declarations

- a. *The standard defines the element <text:dde-connection-decls>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:decls>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the element <text:sequence-decls>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <text:user-field-decls>*

This element is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <text:variable-decls>*

This element is not supported in Word 2010 or Word 2013.

- f. This is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the element <text:decls>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- h. *The standard defines the element <text:decls>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.75 Section 5, Paragraph Elements Content

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.

- b. This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.76 Section 5.1, Basic Text Content

a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.

b. OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.77 Section 5.1.1, White-space Characters

- a. *The standard defines the element <text:line-break>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:line-break>, contained within the parent element <text:p>*

This element is supported in Word 2010 and Word 2013.

- c. *The standard defines the element <text:s>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the element <text:s>, contained within the parent element <text:p>*

This element is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute text:c, contained within the element <text:s>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the element <text:soft-page-break>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- g. *The standard defines the element <text:soft-page-break>, contained within the parent element <text:p>*

This element is supported in Word 2010 and Word 2013.

On save, Word puts a <text:soft-page-break> element everywhere it would normally mark a soft page break location for all of its other document formats. For ODF, this is only done if <text:soft-page-break> is allowed in that location by the ODF specification.

- h. *The standard defines the element <text:tab>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- i. *The standard defines the element <text:tab>, contained within the parent element <text:p>*

This element is supported in Word 2010 and Word 2013.

- j. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- k. *The standard defines the attribute `text:tab-ref`, contained within the element `<text:tab>`, contained within the parent element `<text:p>`*

This attribute is not supported in Word 2010 or Word 2013.

- l. *The standard defines the element `<text:line-break>`*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- m. *The standard defines the element `<text:line-break>`, contained within the parent element `<chart:chart \..\ table:table \..\ paragraph-content>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads this attribute. On save, Excel does not write this attribute.

- n. *The standard defines the element `<text:line-break>`, contained within the parent element `<text:p>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel converts the `<text:line-break>` element to a line feed character in the text. On save, if the parent element is `<ruby-base>` or ``, Excel converts the combination of line feed and return characters to a `<text:line-break>` element. If the parent element is `<text:p>` Excel closes the current `<text:p>` element, and begins a new `<text:p>` element.

- o. *The standard defines the element `<text:s>`*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- p. *The standard defines the element `<text:s>`, contained within the parent element `<chart:chart \..\ table:table \..\ paragraph-content>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads this attribute. On save, Excel does not write this attribute.

- q. *The standard defines the element <text:s>, contained within the parent element <text:p>*

This element is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the attribute text:c, contained within the element <text:s>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- s. *The standard defines the attribute text:c, contained within the element <text:s>, contained within the parent element <chart:chart \.\ table:table \.\ paragraph-content>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads this attribute. On save, Excel does not write this attribute.

- t. *The standard defines the attribute text:c, contained within the element <text:s>, contained within the parent element <text:p>*

This attribute is supported in Excel 2010 and Excel 2013.

- u. *The standard defines the element <text:soft-page-break>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- v. *The standard defines the element <text:soft-page-break>, contained within the parent element <text:p>*

This element is not supported in Excel 2010 or Excel 2013.

w. *The standard defines the element <text:tab>*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

x. *The standard defines the element <text:tab>, contained within the parent element <chart:chart \.\ table:table \.\ paragraph-content>*

This element is not supported in Excel 2010 or Excel 2013.

y. *The standard defines the element <text:tab>, contained within the parent element <text:p>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel converts <tab> elements to spaces.

z. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

aa. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>, contained within the parent element <text:p>*

This attribute is not supported in Excel 2010 or Excel 2013.

bb. *The standard defines the attribute text-tab-attr, contained within the element <text:tab>, contained within the parent element <chart:chart \.\ table:table \.\ paragraph-content>*

This attribute is not supported in Excel 2010 or Excel 2013.

cc. *The standard defines the element <text:line-break>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

dd. *The standard defines the element <text:s>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

ee. *The standard defines the attribute text:c, contained within the element <text:s>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

ff. *The standard defines the element <text:soft-page-break>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

gg. *The standard defines the element <text:tab>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

hh. *The standard defines the attribute text:tab-ref, contained within the element <text:tab>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.78 Section 5.1.2, Soft Hyphens, Hyphens, and Non-breaking Blanks

- OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
- The standard defines the element <NO-BREAK SPACE (0x00A0)>, contained within the parent element <text:p>*

This element is supported in Word 2010 and Word 2013.

- The standard defines the element <NON-BREAKING HYPHEN (0x2011)>, contained within the parent element <text:p>*

This element is supported in Word 2010 and Word 2013.

- d. *The standard defines the element <SOFT HYPHEN (0x00AD)>, contained within the parent element <text:p>*

This element is supported in Word 2010 and Word 2013.

- e. This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.79 Section 5.1.3, Attributed Text

- a. *The standard defines the element <text:span>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:class-name, contained within the element <text:span>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. The text:class-name attribute is always written as empty.

- c. *The standard defines the attribute text:class-names, contained within the element <text:span>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute text:style-name, contained within the element <text:span>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the element <text:span>, contained within the parent element <chart:chart \..\ table:table \..\ paragraph-content>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads the element <text:span> but does not write it on save.

- f. *The standard defines the element <text:span>, contained within the parent element <text:p>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the attribute text:class-name, contained within the element <text:span>*

OfficeArt Math in Excel 2013 does not support this attribute on save, for text in text boxes, shapes, SmartArt, and chart titles and labels. On load it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The text:class-name attribute is always written as empty and is not supported on read.

- h. *The standard defines the attribute text:class-names, contained within the element <text:span>, contained within the parent element <chart:chart \..\ table:table \..\ paragraph-content>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute text:class-names, contained within the element <text:span>, contained within the parent element <text:p>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute text:style-name, contained within the element <text:span>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute `text:style-name`, contained within the element `<text:span>`, contained within the parent element `<chart:chart \..\ table:table \..\ paragraph-content>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute `text:style-name`, contained within the element `<text:span>`, contained within the parent element `<text:p>`*

This attribute is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the attribute `text:class-name`, contained within the element `<text:span>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

The "text:class-name" attribute is always written and empty, and is not supported on read.

- n. *The standard defines the attribute `text:style-name`, contained within the element `<text:span>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

2.1.80 Section 5.1.4, Hyperlinks

- a. *The standard defines the element `<text:a>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `office:name`, contained within the element `<text:a>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `office:target-frame-name`, contained within the element `<text:a>`*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute `office:title`, contained within the element `<text:a>`*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute `text:style-name`, contained within the element `<text:a>`*

This attribute is not supported in Word 2010 or Word 2013.

On load, Word applies text properties to hyperlinks via properties defined by the `<text:span>` element containing the displayed hyperlink text.

- f. *The standard defines the attribute `text:visited-style-name`, contained within the element `<text:a>`*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute `xlink:actuate`, contained within the element `<text:a>`*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute `xlink:href`, contained within the element `<text:a>`*

This attribute is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute `xlink:type`, contained within the element `<text:a>`*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the element `<text:a>`*

This element is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the element `<text:a>`, contained within the parent element `<chart:chart \..\table:table \..\paragraph-content>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads the element `<text:a>` but does not write it on save.

- l. *The standard defines the attribute `office:event-listeners`, contained within the element `<text:a>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute `office:name`, contained within the element `<text:a>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`

- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- n. *The standard defines the attribute office:target-frame-name, contained within the element <text:a>*

This attribute is not supported in Excel 2010 or Excel 2013.

This attribute is not supported in Excel 2010 or Excel 2013.

On load, the office:target-frame-name attribute is not supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- o. *The standard defines the attribute office:title, contained within the element <text:a>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute, on load, for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- p. *The standard defines the attribute text:style-name, contained within the element <text:a>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- q. *The standard defines the attribute `text:visited-style-name`, contained within the element `<text:a>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- r. *The standard defines the attribute `xlink:href`, contained within the element `<text:a>`*

This attribute is supported in Excel 2010 and Excel 2013.

This attribute is not supported in Excel 2010 or Excel 2013.

On load, `xlink:href` attribute is not supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- s. *The standard defines the attribute `xlink:show`, contained within the element `<text:a>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- t. *The standard defines the property "new", contained within the attribute xlink:show, contained within the element <text:a>*

OfficeArt Math in Excel 2013 does not support this enum, on load, for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- u. *The standard defines the property "replace", contained within the attribute xlink:show, contained within the element <text:a>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Hyperlinks are not supported at the text level.

- v. *The standard defines the attribute office:name, contained within the element <text:a>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- w. *The standard defines the attribute `office:target-frame-name`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
 - `<draw:polyline>`
 - `<draw:polygon>`
 - `<draw:regular-polygon>`
 - `<draw:path>`
 - `<draw:circle>`
 - `<draw:ellipse>`
 - `<draw:caption>`
 - `<draw:measure>`
 - `<draw:text-box>`
 - `<draw:frame>`
 - `<draw:custom-shape>`
1. PowerPoint uses a string value for this property. On write, if the PowerPoint string value matches one of the enumerations ("`_self`", "`_blank`", "`_parent`", or "`_top`"), then that enumeration is used. Otherwise, the string value is written to the ODF property.
 2. On read, all values for this property are written as string values to PowerPoint.

- x. *The standard defines the attribute `office:title`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

- y. *The standard defines the attribute `text:style-name`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

z. *The standard defines the attribute `text:visited-style-name`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

aa. *The standard defines the attribute `xlink:href`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

bb. *The standard defines the property "new", contained within the attribute `xlink:show`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

cc. *The standard defines the property "replace", contained within the attribute `xlink:show`, contained within the element `<text:a>`*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

Written as "replace" if the target frame is not empty.

2.1.81 Section 5.2, Bookmarks and References

- OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.
- This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- This is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.82 Section 5.2.1, Bookmarks

- The standard defines the element <text:bookmark>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:bookmark-end>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the element <text:bookmark-start>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- d. This is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the element <text:bookmark>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the element <text:bookmark-end>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the element <text:bookmark-start>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

h. *The standard defines the element <text:bookmark>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

i. *The standard defines the element <text:bookmark-end>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

j. *The standard defines the element <text:bookmark-start>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.83 Section 5.2.2, References

- a. *The standard defines the element <text:reference-mark>*

This element is supported in Word 2010 and Word 2013.

On load, Word converts reference marks to bookmarks.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:reference-mark-end>*

This element is supported in Word 2010 and Word 2013.

On load, Word converts reference marks to bookmarks.

- c. *The standard defines the element <text:reference-mark-start>*

This element is supported in Word 2010 and Word 2013.

On load, Word converts reference marks to bookmarks.

- d. This is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the element <text:reference-mark>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes, shapes, SmartArt, chart titles and labels, On load, it is supported for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the element <text:reference-mark>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

g. *The standard defines the element <text:reference-mark-end>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

h. *The standard defines the element <text:reference-mark-start>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.84 Section 5.3, Notes

a. *The standard defines the element <text:note>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

b. This is not supported in Excel 2010 or Excel 2013.

c. *The standard defines the element <text:note>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

d. *The standard defines the element <text:note>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.85 Section 5.3.1, Note Element

- a. *The standard defines the element <text:note>*

This element is supported in Word 2010 and Word 2013.

On load, footnotes and endnotes are dropped when the reference to the footnote or endnote is in a comment, textbox, or header/footer and that is the only reference to the footnote or endnote.

On save, footnotes and endnotes are dropped when the reference to the footnote or endnote is in a Word Equation and that is the only reference to the footnote or endnote.

- b. *The standard defines the element <text:note>, contained within the parent element <draw:frame>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute text:id, contained within the element <text:note>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute text:note-class, contained within the element <text:note>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the element <text:note-body>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the element <text:note-body>, contained within the parent element <text:note>*

This element is supported in Word 2010 and Word 2013.

- g. *The standard defines the element <text:note-citation>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- h. *The standard defines the element <text:note-citation>, contained within the parent element <text:note>*

This element is supported in Word 2010 and Word 2013.

Word always reads the contents of the element instead of the text:label attribute.

- i. *The standard defines the element <text:notes-configuration>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

j. This is not supported in Excel 2010 or Excel 2013.

k. *The standard defines the element <text:note-body>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

l. *The standard defines the element <text:note-citation>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

m. *The standard defines the element <text:notes-configuration>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

n. *The standard defines the element <text:note-body>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

o. *The standard defines the element <text:note-citation>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

p. *The standard defines the element <text:notes-configuration>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.86 Section 5.4, Ruby

a. OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <text:ruby>*

This element is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `text:style-name`, contained within the element `<text:ruby>`*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the element `<text:ruby-base>`, contained within the parent element `<text:ruby>`*

This element is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute `text:style-name`, contained within the element `<text:ruby-base>`, contained within the parent element `<text:ruby>`*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `text:style-name`, contained within the element `<text:ruby-text>`, contained within the parent element `<text:ruby>`*

This attribute is supported in Word 2010 and Word 2013.

On save, text formatting properties on ruby text are retained if all characters in the ruby text share the same text properties.

- g. OfficeArt Math in Excel 2013 does not support this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- h. *The standard defines the element `<text:ruby>`, contained within the parent element `<chart:chart \.\ table:table \.\ paragraph-content>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads the element `<text:ruby>` but does not write it on save.

- i. *The standard defines the element `<text:ruby>`, contained within the parent element `<text:p>`*

This element is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute `text:style-name`, contained within the element `<text:ruby>`, contained within the parent element `<chart:chart \.\ table:table \.\ paragraph-content>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute `text:style-name`, contained within the element `<text:ruby>`, contained within the parent element `<text:p>`*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the element <text:ruby-base>, contained within the parent element <chart:chart \..\ table:table \..\ text:ruby>*

This element is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the element <text:ruby-base>, contained within the parent element <text:ruby>*

This element is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the element <text:ruby-text>, contained within the parent element <chart:chart \..\ table:table \..\ text:ruby>*

This element is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the element <text:ruby-text>, contained within the parent element <text:ruby>*

This element is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the attribute <text/>, contained within the element <text:ruby-text>, contained within the parent element <chart:chart \..\ table:table \..\ text:ruby>*

This attribute is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the attribute text:style-name, contained within the element <text:ruby-text>, contained within the parent element <chart:chart \..\ table:table \..\ text:ruby>*

This attribute is not supported in Excel 2010 or Excel 2013.

- r. *The standard defines the attribute text:style-name, contained within the element <text:ruby-text>, contained within the parent element <text:ruby>*

This attribute is supported in Excel 2010 and Excel 2013.

- s. OfficeArt Math in PowerPoint 2013 does not support this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- t. *The standard defines the element <text:ruby>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.87 Section 5.5, Text Annotation

- a. OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.
- b. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. OfficeArt Math in PowerPoint 2013 does not support this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

d. *The standard defines the element <office:annotation>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.88 Section 5.6, Index Marks

a. OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.

b. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 does not support this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.89 Section 5.7, Change Tracking and Change Marks

- a. OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.
- b. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 does not support this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.90 Section 5.8, Inline graphics and text-boxes

a. OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.

b. *The standard defines the element <draw:a>, contained within the parent element <text:p>*

This element is not supported in Word 2010 or Word 2013.

c. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

d. This is not supported in PowerPoint 2010 or PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 does not support this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.91 Section 6, Text Fields

a. This is supported in Word 2010 and Word 2013.

1. On save, Word will not preserve the text formatting on fields whose text have multiple text styles applied.
2. On save, Word retains the resulting output text of unsupported fields as plain text.
3. On save, nested fields (excluding those in fields which can contain <text:p> elements) are replaced by their resulting output text. This applies to the interior fields only. The containing field remains a field.
4. On save, fields in equations are replaced by their resulting output text.

b. This is supported in Excel 2010 and Excel 2013.

c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.92 Section 6.1, Common Characteristics of Field Elements

- a. This is supported in Excel 2010 and Excel 2013.
- b. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.93 Section 6.2, Document Fields

- a. This is supported in Excel 2010 and Excel 2013.
- b. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.94 Section 6.2.1, Date Fields

- a. *The standard defines the element <text:date>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:date>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:date-adjust, contained within the element <text:date>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute text:date-value, contained within the element <text:date>*

This attribute is not supported in Word 2010 or Word 2013.

According to section 6.2.1 of the ODF specification, the current date is assumed if no value is specified, even if the date field is marked as fixed.

1. On load, if the date field is fixed, Word ignores the value in the text:date-value attribute and displays the text enclosed by the <text:date> element tags. On save, Word replaces the field with the text between the <text:date> element tags.
2. On load, if the text between the <text:date> element tags is missing and the date field is not fixed, then Word displays nothing in the field. On save, the date field element and its contents are removed.
3. On load, if the date field is not fixed, Word displays the current date. On save, Word writes out the current date as the text between the <text:date> element tags. The field is retained within the document.

- e. *The standard defines the attribute text:fixed, contained within the element <text:date>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute text:date-adjust*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute text:date-value*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the element <text:date>*

This element is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the element <text:date>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- j. *The standard defines the attribute style:data-style-name, contained within the element <text:date>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- k. *The standard defines the attribute text:date-adjust, contained within the element <text:date>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the attribute text:date-value, contained within the element <text:date>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

Date values are specified as text content between the start and end <text:date> element tags.

- m. *The standard defines the attribute text:fixed, contained within the element <text:date>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

For fixed dates, this attribute is not used. For non-fixed dates this attribute is written out with the value "false".

2.1.95 Section 6.2.2, Time Fields

- a. *The standard defines the element <text:time>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:time>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:fixed, contained within the element <text:time>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute text:time-adjust, contained within the element <text:time>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute text:time-value, contained within the element <text:time>*

This attribute is not supported in Word 2010 or Word 2013.

According to section 6.2.2 of the ODF spec, the current time is assumed if no value is specified, even if the time field is marked as fixed.

1. On load, if the time field is fixed, Word ignores the value in the text:time-value attribute and displays the text enclosed by the <text:time> element tags. On save, Word replaces the field with the text between the <text:time> element tags.
2. On load, if the text between the <text:time> element tags is missing and the time field is not fixed, then Word displays nothing in the field. On save, the time field element and its contents are removed.
3. On load, if the time field is not fixed, Word displays the current time. On save, Word converts the time field to a date field and writes the current time as the text between the <text:date> element tags.

- f. *The standard defines the attribute text:fixed*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute text:time*

This attribute is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute text:time-adjust*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute text:time-value*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the element <text:time>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- k. *The standard defines the attribute style:data-style-name, contained within the element <text:time>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- l. *The standard defines the attribute text:fixed, contained within the element <text:time>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

For fixed time values, this attribute is not used. For non-fixed time values, this attribute is written out with the value "false".

- m. *The standard defines the attribute text:time-adjust, contained within the element <text:time>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute text:time-value, contained within the element <text:time>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.96 Section 6.2.3, Page Number Fields

- a. *The standard defines the element <text:page-number>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:num-format, contained within the element <text:page-number>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, numbering formats that are not familiar to Word will be displayed using the Arabic numeral format (1, 2, 3...).
2. On save and load, the following strings are also supported by Word as numbering formats:

١ , ٢ , ٣ , ...

ア , イ , ウ , ...

أ , ب , ج , ...

ا , ب , ت , ...

One, Two, Three, ...

* , † , ‡ , ...
一 , 十 , 一〇〇(简) , ...
一 , 十 , 一百 (简) , ...
壹 , 貳 叁 , ...
ㄱ , ㄴ , ㄷ , ...
① , ② , ③ , ...
① , ② , ③ , ...
1 , 2 , 3 , ...
(1) , (2) , (3) , ...
1 , 2 , 3 , ...
01 , 02 , 03 , ...
가 , 나 , 다 , ...
κ , λ , μ , ...
κ , λ , μ , ...
1 , A , B , ...
अ , आ , इ , ...
□□ , □□ , □□□ , ...
१ , २ , ३ , ...
क , ख , ग , ...
一 , 一〇 , 一〇〇 , ...
(一) , (二) , (三) , ...
壹 , 貳 , 參 , ...
甲 , 乙 , 丙 , ...
子 , 丑 , 寅 , ...
甲子 , 乙丑 , 丙寅 , ...
イ , ロ , ハ , ...
イ , ロ , ハ , ...
一 , 二 , 三 ...
一 , 二 , 三 , 万 , ...
壹 , 貳 , 參 , ...
일 , 이 , 삼 , ...
일 , 일영 , 일영영 , ...

一, 一零, 一零零, ...

하나, 둘, 셋, ...

- 1 -, - 2 -, - 3 -, ...

1st, 2nd, 3rd, ...

First, Second, Third, ...

a, б, B, ...

A,Б,B, ...

一, 十, 一〇〇(繁), ...

一, 十, 一百 (繁), ...

一, 一〇, 一〇〇(繁), ...

□□□□□, ஸ ஐ ங , ஸ ா ழ , ...

π , ϖ , ϑ , ...

๑ ,๒ ,๓ , ...

- c. *The standard defines the attribute style:num-letter-sync, contained within the element <text:page-number>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute text:fixed, contained within the element <text:page-number>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute text:page-adjust, contained within the element <text:page-number>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute text:select-page, contained within the element <text:page-number>*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute text:page-adjust*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute text:select-page*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the element <text:page-number>*

This element is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the element <<text:page-number>>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- k. *The standard defines the attribute style:num-format, contained within the element <<text:page-number>>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- l. *The standard defines the attribute `text:fixed`, contained within the element `<<text:page-number>>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- m. *The standard defines the attribute `text:page-adjust`, contained within the element `<<text:page-number>>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute `text:select-page`, contained within the element `<<text:page-number>>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.97 Section 6.2.4, Page Continuation Text

- a. *The standard defines the element `<text:page-continuation>`*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<text:page-continuation>`*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element `<text:page-continuation>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.98 Section 6.2.5, Sender Fields

- a. *The standard defines the element `<text:sender-city>`*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<text:sender-company>`*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element `<text:sender-country>`*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element `<text:sender-email>`*

This element is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element `<text:sender-fax>`*

This element is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element `<text:sender-firstname>`*

This element is not supported in Word 2010 or Word 2013.

- g. *The standard defines the element `<text:sender-initials>`*

This element is not supported in Word 2010 or Word 2013.

- h. *The standard defines the element <text:sender-lastname>*
This element is not supported in Word 2010 or Word 2013.
- i. *The standard defines the element <text:sender-phone-private>*
This element is not supported in Word 2010 or Word 2013.
- j. *The standard defines the element <text:sender-phone-work>*
This element is not supported in Word 2010 or Word 2013.
- k. *The standard defines the element <text:sender-position>*
This element is not supported in Word 2010 or Word 2013.
- l. *The standard defines the element <text:sender-postal-code>*
This element is not supported in Word 2010 or Word 2013.
- m. *The standard defines the element <text:sender-state-or-province>*
This element is not supported in Word 2010 or Word 2013.
- n. *The standard defines the element <text:sender-street>*
This element is not supported in Word 2010 or Word 2013.
- o. *The standard defines the element <text:sender-title>*
This element is not supported in Word 2010 or Word 2013.
- p. This is not supported in Excel 2010 or Excel 2013.
- q. *The standard defines the element <text:sender-city>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- r. *The standard defines the element <text:sender-company>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- s. *The standard defines the element <text:sender-country>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- t. *The standard defines the element <text:sender-email>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- u. *The standard defines the element <text:sender-fax>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- v. *The standard defines the element <text:sender-firstname>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- w. *The standard defines the element <text:sender-initials>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- x. *The standard defines the element <text:sender-lastname>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- y. *The standard defines the element <text:sender-phone-private>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- z. *The standard defines the element <text:sender-phone-work>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- aa. *The standard defines the element <text:sender-position>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- bb. *The standard defines the element <text:sender-postal-code>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- cc. *The standard defines the element <text:sender-state-or-province>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- dd. *The standard defines the element <text:sender-street>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- ee. *The standard defines the element <text:sender-title>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.99 Section 6.2.6, Author Fields

- a. *The standard defines the element <text:author-initials>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <text:author-name>*

This element is supported in Word 2010 and Word 2013.

- c. This is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the element <text:author-initials>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the element <text:author-name>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.100 Section 6.2.7, Chapter Fields

- a. *The standard defines the element <text:chapter>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:chapter>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.101 Section 6.2.8, File Name Fields

- a. *The standard defines the element <text:file-name>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "full", contained within the attribute text:display, contained within the element <text:file-name>*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "name", contained within the attribute text:display, contained within the element <text:file-name>*

This property is supported in Word 2010 and Word 2013.

On load, Word converts this value for the text:display attribute to "name-and-extension".

- d. *The standard defines the property "name-and-extension", contained within the attribute text:display, contained within the element <text:file-name>*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the property "path", contained within the attribute text:display, contained within the element <text:file-name>*

This property is not supported in Word 2010 or Word 2013.

On load, Word converts this value for the text:display attribute to "full".

- f. *The standard defines the attribute text:fixed, contained within the element <text:file-name>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute text:display*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads in the "name" value and maps it to "name-and-extension". On save, Excel ignores "name" and writes out "name-and-extension".

- h. *The standard defines the element <text:file-name>*

This element is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the element <text:file-name>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.102 Section 6.2.9, Document Template Name Fields

- a. *The standard defines the element <text:template-name>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "area", contained within the attribute text:display, contained within the element <text:template-name>*

This property is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property "full", contained within the attribute text:display, contained within the element <text:template-name>*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "name", contained within the attribute text:display, contained within the element <text:template-name>*

This property is supported in Word 2010 and Word 2013.

On load, Word converts this value for the text:display attribute to "name-and-extension".

- e. *The standard defines the property "name-and-extension", contained within the attribute text:display, contained within the element <text:template-name>*

This property is supported in Word 2010 and Word 2013.

- f. *The standard defines the property "path", contained within the attribute text:display, contained within the element <text:template-name>*

This property is not supported in Word 2010 or Word 2013.

- g. *The standard defines the property "title", contained within the attribute text:display, contained within the element <text:template-name>*

This property is not supported in Word 2010 or Word 2013.

- h. This is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the element <text:template-name>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.103 Section 6.2.10, Sheet Name Fields

- a. *The standard defines the element <text:sheet-name>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:sheet-name>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the element <text:sheet-name>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.104 Section 6.3, Variable Fields

- a. This is not supported in Excel 2010 or Excel 2013.

- b. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.105 Section 6.3.1, Declaring Simple Variables

- a. *The standard defines the element <text:variable-decl>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:variable-decl>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.106 Section 6.3.2, Setting Simple Variables

- a. *The standard defines the element <text:variable-set>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:variable-set>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.107 Section 6.3.3, Displaying Simple Variables

- a. *The standard defines the element <text:variable-get>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:variable-get>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.108 Section 6.3.4, Simple Variable Input Fields

- a. *The standard defines the element <text:variable-input>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:variable-input>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.109 Section 6.3.5, Declaring User Variables

- a. *The standard defines the element <text:user-field-decl>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:user-field-del>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.110 Section 6.3.6, Displaying User Variables

- a. *The standard defines the element <text:user-field-get>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:user-field-get>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.111 Section 6.3.7, User Variable Input Fields

- a. *The standard defines the element <text:user-field-input>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:user-field-input>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.112 Section 6.3.8, Declaring Sequence Variables

- a. *The standard defines the element <text:sequence-decl>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:sequence-del>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.113 Section 6.3.9, Using Sequence Fields

- a. *The standard defines the element <text:sequence>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:sequence>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.114 Section 6.3.10, Expression Fields

- a. *The standard defines the element <text:expression>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:expression>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.115 Section 6.3.11, Text Input Fields

- a. *The standard defines the element <text:text-input>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:text-input>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.116 Section 6.4, Metadata Fields

- a. This is not supported in Excel 2010 or Excel 2013.
- b. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.117 Section 6.4.1, Initial Creator

- a. *The standard defines the element <text:initial-creator>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:initial-creator>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.118 Section 6.4.2, Document Creation Date

- a. *The standard defines the element <text:creation-date>*

This element is supported in Word 2010 and Word 2013.

On load, Word always assumes that the <text:creation-date> element in the meta.xml is written in UTC (Coordinated Universal Time). On save, Word always saves the <text:creation-date> in the meta.xml as UTC by using the "Z" suffix in the time stamp.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:creation-date>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:fixed, contained within the element <text:creation-date>*

This attribute is not supported in Word 2010 or Word 2013.

On save, if the field is fixed, Word replaces the <text:creation-date> field with its resulting output text.

- d. This is not supported in Excel 2010 or Excel 2013.
- e. *The standard defines the element <text:creation-date>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.119 Section 6.4.3, Document Creation Time

- a. *The standard defines the element <text:creation-time>*

This element is supported in Word 2010 and Word 2013.

1. On load, Word always assumes that the <text:creation-date> element in the meta.xml is written in UTC (Coordinated Universal Time). On save, Word always saves the <text:creation-date> in the meta.xml as UTC by using the "Z" suffix in the time stamp.
2. On load, Word converts <text:creation-time> elements to <text:creation-date> elements.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:creation-time>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:fixed, contained within the element <text:creation-time>*

This attribute is not supported in Word 2010 or Word 2013.

On save, if the field is fixed, Word replaces the <text:creation-time> field with its resulting output text.

- d. This is not supported in Excel 2010 or Excel 2013.
- e. *The standard defines the element <text:creation-time>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.120 Section 6.4.4, Document Description

- a. *The standard defines the element <text:description>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:description>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.121 Section 6.4.5, User-Defined Document Information

- a. *The standard defines the element <text:user-defined>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:user-defined>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.122 Section 6.4.6, Print Time

- a. *The standard defines the element <text:print-time>*

This element is supported in Word 2010 and Word 2013.

On load, Word converts <text:print-time> elements to <text:print-date> elements.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:print-time>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:fixed, contained within the element <text:print-time>*

This attribute is not supported in Word 2010 or Word 2013.

On save, if the field is fixed, Word replaces the <text:print-time> field with its resulting output text.

- d. This is not supported in Excel 2010 or Excel 2013.
- e. *The standard defines the element <text:print-time>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.123 Section 6.4.7, Print Date

- a. *The standard defines the element <text:print-date>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:print-date>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:fixed, contained within the element <text:print-date>*

This attribute is not supported in Word 2010 or Word 2013.

On save, if the field is fixed, Word replaces the <text:print-date> field with its resulting output text.

- d. This is not supported in Excel 2010 or Excel 2013.
- e. *The standard defines the element <text:print-date>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.124 Section 6.4.8, Printed By

- a. *The standard defines the element <text:printed-by>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:printed-by>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.125 Section 6.4.9, Document Title

- a. *The standard defines the element <text:title>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:title>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.126 Section 6.4.10, Document Subject

- a. *The standard defines the element <text:subject>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:subject>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.127 Section 6.4.11, Document Keywords

- a. *The standard defines the element <text:keywords>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:keywords>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.128 Section 6.4.12, Document Revision Number

- a. *The standard defines the element <text:editing-cycles>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:editing-cycles>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.129 Section 6.4.13, Document Edit Duration

- a. *The standard defines the element <text:editing-duration>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:editing-duration>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.130 Section 6.4.14, Document Modification Time

- a. *The standard defines the element <text:modification-time>*

This element is supported in Word 2010 and Word 2013.

On load, Word converts <text:modification-time> elements to <text:modification-date> elements.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:modification-time>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:fixed, contained within the element <text:modification-time>*

This attribute is not supported in Word 2010 or Word 2013.

On save, if the field is fixed, Word replaces the <text:modification-time> field with its resulting output text.

- d. This is not supported in Excel 2010 or Excel 2013.
- e. *The standard defines the element <text:modification-time>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.131 Section 6.4.15, Document Modification Date

- a. *The standard defines the element <text:modification-date>*

This element is supported in Word 2010 and Word 2013.

On load, Word always assumes that the <text:modification-date> element in the meta.xml is written in UTC (Coordinated Universal Time). On save, Word always saves the <dc:date> in the meta.xml as UTC by using the "Z" suffix in the time stamp.

- b. *The standard defines the attribute style:data-style-name, contained within the element <text:modification-date>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:fixed, contained within the element <text:modification-date>*

This attribute is not supported in Word 2010 or Word 2013.

On save, if the field is fixed, Word replaces the <text:modification-date> field with its resulting output text.

- d. This is not supported in Excel 2010 or Excel 2013.
- e. *The standard defines the element <text:modification-date>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.132 Section 6.4.16, Document Modified By

- a. *The standard defines the element <text:creator>*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:creator>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.133 Section 6.4.17, Document Statistics Fields

- a. *The standard defines the element <text:character-count>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <text:image-count>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <text:object-count>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <text:page-count>*

This element is supported in Word 2010 and Word 2013.

- e. *The standard defines the element <text:paragraph-count>*

This element is supported in Word 2010 and Word 2013.

- f. *The standard defines the element <text:table-count>*

This element is not supported in Word 2010 or Word 2013.

- g. *The standard defines the element <text:word-count>*

This element is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute text:character-count*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute text:image-count*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute text:object-count*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute text:page-count*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the attribute text:paragraph-count*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute text:table-count*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute text:word-count*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the element <text:character-count>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- p. *The standard defines the element <text:image-count>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the element <text:object-count>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the element <text:page-count>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the element <text:paragraph-count>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- t. *The standard defines the element <text:table-count>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- u. *The standard defines the element <text:word-count>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.134 Section 6.5, Database Fields

- a. This is not supported in Excel 2010 or Excel 2013.
b. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.135 Section 6.5.1, Database Field Data Source

- a. *The standard defines the element <form:connection-resource>*

This element is supported in Word 2010 and Word 2013.

This implementer note references the following standards:

1. [\[ISO/IEC-29500:2008\]](http://standards.iso.org/ittf/PubliclyAvailableStandards/index.html) International Organization for Standardization, "Information technology -- Document description and processing languages -- Office Open XML File Formats -- Parts 1-4", <http://standards.iso.org/ittf/PubliclyAvailableStandards/index.html>.
2. [\[RFC3986\]](http://www.ietf.org/rfc/rfc3986.txt) Berners-Lee, T., Fielding, R., and Masinter, L., "Uniform Resource Identifier (URI): Generic Syntax", January 2005, <http://www.ietf.org/rfc/rfc3986.txt>.

Word can support only one database connection per document. On load Word uses the first <form:connection-resource> element in the document as the database connection for the entire document.

On save Word constructs a string that is the value for the xlink:href attribute for the form:connection-resource element from elements as specified in [ISO/IEC-29500:2008] part 1, section 17.14. The string is comprised of four different parts.

The last three parts of the string contain the properties required by Word to complete a mail merge connection. Each property is represented by a key/value pair that is linked by an equals sign ("="). Multiple properties are separated by an ampersand (denoted as "&").

Part 1

The first part contains the complete path of the data source, as specified in [RFC3986]. This portion of the string is terminated by a number sign ("#"). The path comes directly from the dataType key as described in part 2 in this section. If the dataType key is empty, then the path will be empty also, and the xlink:href attribute's value starts from "#".

Part 2

The second part of the string contains keys as specified in mainDocumentType Key. The description for each of these keys matches that of an element in [ISO/IEC-29500:2008]. The relevant section of the specification is identified with the name of the key.

mainDocumentType Key

The definition of the mainDocumentType key is specified in [ISO/IEC-29500:2008] section 17.14.22. The enumerations specified in [ISO/IEC-29500:2008] are represented by the following values in this key:

- "0" represents formLetters
- "1" represents mailingLabels
- "2" represents envelopes
- "3" represents catalog
- "4" represents email
- "5" represents fax

linktoQuery Key

The definition of the linktoQuery key is described in [ISO/IEC-29500:2008] section 17.14.18. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

dataType Key

The definition of the dataType key is described in [ISO/IEC-29500:2008] section 17.14.22. The enumerations described in the specification are represented by the following values in this key:

- "0" represents textFile
- "1" represents database
- "2" represents spreadsheet
- "3" represents query
- "4" represents odbc
- "5" represents native

connectString Key

The definition and possible values for the connectString key are described in [ISO/IEC-29500:2008] section 17.14.8.

query Key

The definition and possible values for the query key are described in [ISO/IEC-29500:2008] section 17.14.26.

dataSource Key

The definition and possible values for the dataSource key are described in [ISO/IEC-29500:2008] section 17.14.9.

headerSource Key

The definition and possible values for the headerSource key are described in [ISO/IEC-29500:2008] section 17.14.16.

doNotSuppressBlankLines Key

The definition of the doNotSuppressBlankLines key is described in [ISO/IEC-29500:2008] section 17.14.12. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

destination Key

The definition of the destination key is described in [ISO/IEC-29500:2008] section 17.14.19. The enumerations described in the specification are represented by the following values in this key:

- "0" represents newDocument
- "1" represents printer
- "2" represents email
- "3" represents fax

addressFieldName Key

The definition and possible values for the addressFieldName key are described in [ISO/IEC-29500:2008] section 17.14.3.

mailSubject Key

The definition and possible values for the mailSubject key are described in [ISO/IEC-29500:2008] section 17.14.21.

mailAsAttachment Key

The definition of the mailAsAttachment key is described in [ISO/IEC-29500:2008] section 17.14.19. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

viewMergedData Key

The definition of the viewMergedData key is described in [ISO/IEC-29500:2008] section 17.14.36. The enumerations described in the specification are represented by the following values in this key:

- "0" represents false
- "1" represents true

activeRecord Key

The definition and possible values for the activeRecord key are described in [ISO/IEC-29500:2008] section 17.14.2.

checkErrors Key

The definition and possible values for the checkErrors key are described in [ISO/IEC-29500:2008] section 17.14.4.

odsoUd Key

The definition and possible values for the odsoUd key are described in [ISO/IEC-29500:2008] section 17.14.34. Word only writes this key if the dataType key is the "native" value.

odsoTable Key

The definition and possible values for the odsoTable key are described in [ISO/IEC-29500:2008] section 17.14.31. Word only writes this key if the dataType key is the "native" value.

odsoSrc Key

The definition and possible values for the odsoSrc key are described in [ISO/IEC-29500:2008] section 17.14.30. Word only writes this key if the dataType key is the "native" value.

odsoColDelim Key

The definition and possible values for the `odsoColDelim` key are described in [ISO/IEC-29500:2008] section 17.14.5. Word only writes this key if the `dataType` key is the "native" value.

`odsoType` Key

The definition and possible values for the `odsoType` key are described in [ISO/IEC-29500:2008] section 17.14.32. Word only writes this key if the `dataType` key is the "native" value.

`odsoFHdr` Key

The definition and possible values for the `odsoFHdr` key are described in [ISO/IEC-29500:2008] section 17.14.14. Word only writes this key if the `dataType` key is the "native" value.

Part 3

The third part of the string is used to describe the properties of each column in the data source. The properties for a given column follow the same key/value syntax as described previously in part 2.

`fieldMapType` Key

The definition of the `fieldMapType` key is described in [ISO/IEC-29500:2008] section 17.14.33. The enumerations described in the specification are represented by the following values in this key:

- "0" represents null
- "1" represents `dbColumn`
- "2" represents `addressBlock`
- "3" represents salutation
- "4" represents mapped
- "5" represents barcode

`fieldMapName` Key

The definition and possible values for the `fieldMapName` key are described in [ISO/IEC-29500:2008] section 17.14.24.

`fieldMapMappedName` Key

The definition and possible values for the `fieldMapMappedName` key are described in [ISO/IEC-29500:2008] section 17.14.23.

`fieldMapColumn` Key

The definition and possible values for the `fieldMapColumn` key are described in [ISO/IEC-29500:2008] section 17.14.6.

`fieldMapDynamicAddress` Key

The definition and possible values for the `fieldMapDynamicAddress` key are described in [ISO/IEC-29500:2008] section 17.14.13.

`fieldMapLid` Key

The definition and possible values for the `fieldMapLid` key are described in [ISO/IEC-29500:2008] section 17.14.17.

`fieldMapDataEnd` Key

The `fieldMapDataEnd` key specifies that there is no more information for a single column. The value of the key is a one-based index of the column within a given external data source.

Part 4

The last part of the string is used to describe the properties of each recipient in the mail merge. The properties for a given recipient follow the same key/value syntax as described previously in part 2.

recipientActive Key

The definition and possible values for the recipientActive key are described in [ISO/IEC-29500:2008] section 17.14.28.

recipientHash Key

The definition and possible values for the recipientHash key are described in [ISO/IEC-29500:2008] section 17.14.27.

recipientColumn Key

The definition and possible values for the recipientColumn key are described in [ISO/IEC-29500:2008] section 17.14.6.

recipientUniqueTag Key

The definition and possible values for the recipientUniqueTag key are described in [ISO/IEC-29500:2008] section 17.14.7.

recipientDataEnd Key

The recipientDataEnd key specifies that there is no more information for a single recipient. The value of the key is a one-based index value, which is used to look up the appropriate recipient in the data source.

The following example shows a connection string saved by Word to connect to the data source that is being used by the mail merge:

```
<text:database-display text:table-name="Sheet1$" text:table-type="table" text:column-
name="Title"><form:connection-resource
xlink:href="file:///\\word\public\user\sample%20mail%20merge%20data%20sources\Word%20C
reate%20Date.xls#mainDocumentType=0&amp;linkToQuery=1&amp;dataType=5&amp;connectS
tring=Provider%3DMicrosoft.ACE.OLEDB.12.0;User%20ID%3DAdmin;Data%20Source%3D\\word
\public\user\sample%20mail%20merge%20data%20sources\Word%20Create%20Date.xls;Mode
%3DRead;Extended%20Properties%3D%22HDR%3DYES;IMEX%3D1;%22;Jet%20OLEDB:System
%20database%3D%22%22;Jet%20OLEDB:Registry%20Path%3D%22%22;Jet%20OLEDB:Engine
%20Type%3D35;Jet%20OLEDB:Database%20Locking%20Mode%3D0;Jet%20OLEDB:Global%20P
artial%20Bulk%20Ops%3D2;Jet%20OLEDB:Global%20Bulk%20Transactions%3D1;Jet%20OLEDB
:New%20Database%20Password%3D%22%22;Jet%20OLEDB:Create%20System%20Database%
3DFalse;Jet%20OLEDB:Encrypt%20Database%3DFalse;Jet%20OLEDB:Don't%20Copy%20Locale
%20on%20Compact%3DFalse;Jet%20OLEDB:Compact%20Without%20Replica%20Repair%3DFal
se;Jet%20OLEDB:SFP%3DFalse;Jet%20OLEDB:Support%20Complex%20Data%3DFalse&amp;que
ry=SELECT%20*%20FROM%20%60Sheet1$%60%20&amp;dataSource=\\word\public\user\samp
le%20mail%20merge%20data%20sources\Word%20Create%20Date.xls&amp;activeRecord=4&a
mp;odsoUdl=Provider%3DMicrosoft.ACE.OLEDB.12.0;User%20ID%3DAdmin;Data%20Source%3D
\\word\public\user\sample%20mail%20merge%20data%20sources\Word%20Create%20Date.xls;
Mode%3DRead;Extended%20Properties%3D%22HDR%3DYES;IMEX%3D1;%22;Jet%20OLEDB:S
ystem%20database%3D%22%22;Jet%20OLEDB:Registry%20Path%3D%22%22;Jet%20OLEDB:E
ngine%20Type%3D35;Jet%20OLEDB:Database%20Locking%20Mode%3D0;Jet%20OLEDB:Global
%20Partial%20Bulk%20Ops%3D2;Jet%20OLEDB:Global%20Bulk%20Transactions%3D1;Jet%20
OLEDB:New%20Database%20Password%3D%22%22;Jet%20OLEDB:Create%20System%20Data
base%3DFalse;Jet%20OLEDB:Encrypt%20Database%3DFalse;Jet%20OLEDB:Don't%20Copy%20
Locale%20on%20Compact%3DFalse;Jet%20OLEDB:Compact%20Without%20Replica%20Repair%
```

3DFalse;Jet%20OLEDB:SFP%3DFalse;Jet%20OLEDB:Support%20Complex%20Data%3DFalse&odsoTable=Sheet1\$&odsoSrc=\\word\public\user\sample%20mail%20merge%20data%20sources\Word%20Create%20Date.xls&odsoColDelim=9&odsoType=1&odsoFHdr=1&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=1&fieldMapType=1&fieldMapName=Title&fieldMapMappedName=Courtesy%20Title&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=2&fieldMapType=1&fieldMapName=First%20Name&fieldMapMappedName=First%20Name&fieldMapColumn=1&fieldMapLid=1033&fieldMapDataEnd=3&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=4&fieldMapType=1&fieldMapName=Last%20Name&fieldMapMappedName=Last%20Name&fieldMapColumn=2&fieldMapLid=1033&fieldMapDataEnd=5&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=6&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=7&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=8&fieldMapType=1&fieldMapName=Company%20Name&fieldMapMappedName=Company&fieldMapColumn=3&fieldMapLid=1033&fieldMapDataEnd=9&fieldMapType=1&fieldMapName=Address%20Line%201&fieldMapMappedName=Address%201&fieldMapColumn=4&fieldMapLid=1033&fieldMapDataEnd=10&fieldMapType=1&fieldMapName=Address%20Line%202&fieldMapMappedName=Address%202&fieldMapColumn=5&fieldMapLid=1033&fieldMapDataEnd=11&fieldMapType=1&fieldMapName=City&fieldMapMappedName=City&fieldMapColumn=6&fieldMapLid=1033&fieldMapDataEnd=12&fieldMapType=1&fieldMapName=State&fieldMapMappedName=State&fieldMapColumn=7&fieldMapLid=1033&fieldMapDataEnd=13&fieldMapType=1&fieldMapName=ZIP%20Code&fieldMapMappedName=Postal%20Code&fieldMapColumn=8&fieldMapLid=1033&fieldMapDataEnd=14&fieldMapType=1&fieldMapName=Country&fieldMapMappedName=Country%20or%20Region&fieldMapColumn=9&fieldMapLid=1033&fieldMapDataEnd=15&fieldMapType=1&fieldMapName=Work%20Phone&fieldMapMappedName=Business%20Phone&fieldMapColumn=11&fieldMapLid=1033&fieldMapDataEnd=16&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=17&fieldMapType=1&fieldMapName=Home%20Phone&fieldMapMappedName=Home%20Phone&fieldMapColumn=10&fieldMapLid=1033&fieldMapDataEnd=18&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=19&fieldMapType=1&fieldMapName=E-mail%20Address&fieldMapMappedName=E-mail%20Address&fieldMapColumn=12&fieldMapLid=1033&fieldMapDataEnd=20&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=21&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=22&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=23&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=24&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=25&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=26&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=27&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=28&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=29&fieldMapColumn=0&fieldMapLid=1033&fieldMapDataEnd=30&recipientActive=1&recipientHash=-1949734214&recipientDataEnd=1&recipientActive=1&recipientHash=870254691&recipientDataEnd=2&recipientActive=0&recipientHash=-1107777181&recipientDataEnd=3&recipientActive=1&recipientHash=-1973497891&recipientDataEnd=4&recipientActive=0&recipientHash=2014681738&recipientDataEnd=5&recipientActive=1&recipientHash=571221072&recipientDataEnd=6&recipientActive=1&recipientHash=0&recipientDataEnd=7"/><Title></text:database-display>

- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.136 Section 6.5.2, Displaying Database Content

- a. The standard defines the element <text:database-display>

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:database-display>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.137 Section 6.5.3, Selecting the Next Database Row

- a. *The standard defines the element <text:database-next>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.138 Section 6.5.4, Selecting a Row Number

- a. *The standard defines the element <text:database-row-select>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.139 Section 6.5.5, Displaying the Row Number

- a. *The standard defines the element <text:database-row-number>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.140 Section 6.5.6, Display Current Database and Table

- a. *The standard defines the element <text:database-name>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.141 Section 6.6, More Fields

- a. This is not supported in Excel 2010 or Excel 2013.
- b. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.142 Section 6.6.1, Page Variable Fields

- a. *The standard defines the element <text:variable-page-set>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:variable-page-get>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the element <text:variable-page-set>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.143 Section 6.6.2, Placeholders

- a. *The standard defines the element <text:placeholder>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:placeholder>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.144 Section 6.6.3, Conditional Text Fields

- a. *The standard defines the element <text:conditional-text>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:conditional-text>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.145 Section 6.6.4, Hidden Text Field

- a. *The standard defines the element <text:hidden-text>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:hidden-text>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.146 Section 6.6.5, Reference Fields

- a. *The standard defines the element <text:bookmark-ref>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "chapter", contained within the attribute text:reference-format, contained within the element <text:bookmark-ref>*

This property is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property "direction", contained within the attribute text:reference-format, contained within the element <text:bookmark-ref>*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "page", contained within the attribute text:reference-format, contained within the element <text:bookmark-ref>*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the property "text", contained within the attribute text:reference-format, contained within the element <text:bookmark-ref>*

This property is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute text:ref-name, contained within the element <text:bookmark-ref>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the element <text:note-ref>*

This element is not supported in Word 2010 or Word 2013.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- h. *The standard defines the attribute text:note-class, contained within the element <text:note-ref>*

This attribute is not supported in Word 2010 or Word 2013.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- i. *The standard defines the property "chapter", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2010 or Word 2013.

- j. *The standard defines the property "direction", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2010 or Word 2013.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- k. *The standard defines the property "page", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2010 or Word 2013.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- l. *The standard defines the property "text", contained within the attribute text:reference-format, contained within the element <text:note-ref>*

This property is not supported in Word 2010 or Word 2013.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- m. *The standard defines the attribute text:ref-name, contained within the element <text:note-ref>*

This attribute is not supported in Word 2010 or Word 2013.

On load, Word ignores footnote references. On save, Word writes out footnote references.

- n. *The standard defines the element <text:reference-ref>*

This element is supported in Word 2010 and Word 2013.

1. On load, Word converts the element <text:reference-ref> to <text:bookmark-ref>.
2. On save, the hyperlink to the object being referenced is lost.

- o. *The standard defines the property "chapter", contained within the attribute text:reference-format, contained within the element <text:reference-ref>*

This property is not supported in Word 2010 or Word 2013.

- p. *The standard defines the property "direction", contained within the attribute text:reference-format, contained within the element <text:reference-ref>*

This property is supported in Word 2010 and Word 2013.

- q. *The standard defines the property "page", contained within the attribute text:reference-format, contained within the element <text:reference-ref>*

This property is supported in Word 2010 and Word 2013.

- r. *The standard defines the property "text", contained within the attribute text:reference-format, contained within the element <text:reference-ref>*

This property is supported in Word 2010 and Word 2013.

- s. *The standard defines the attribute text:ref-name, contained within the element <text:reference-ref>*

This attribute is supported in Word 2010 and Word 2013.

- t. *The standard defines the element <text:sequence-ref>*

This element is not supported in Word 2010 or Word 2013.

- u. This is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the element <text:bookmark-ref>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- w. *The standard defines the element <text:note-ref>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- x. *The standard defines the element <text:reference-ref>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.147 Section 6.6.6, Script Fields

- a. *The standard defines the element <text:script>*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <text:script>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.148 Section 6.6.7, Macro Fields

- a. *The standard defines the element <text:execute-macro>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:execute-macro>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.149 Section 6.6.8, Hidden Paragraph Fields

- a. *The standard defines the element <text:hidden-paragraph>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:hidden-paragraph>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.150 Section 6.6.9, DDE Connection Fields

- a. *The standard defines the element <text:dde-connection>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:dde-connection>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.151 Section 6.6.10, Measure Fields

- a. *The standard defines the element <text:measure>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:measure>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.152 Section 6.6.11, Table Formula Field

- a. *The standard defines the element <text:table-formula>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <text:table-formula>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.153 Section 6.7, Common Field Attributes

- a. This is not supported in Excel 2010 or Excel 2013.

2.1.154 Section 6.7.1, Variable Value Types and Values

- a. *The standard defines the attribute `office:boolean-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the attribute `office:currency`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `office:date-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `office:string-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `office:time-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `office:value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the property "boolean", contained within the attribute `office:value-type`, contained within the element `<table:covered-table-cell>`*

This property is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the property "currency", contained within the attribute `office:value-type`, contained within the element `<table:covered-table-cell>`*

This property is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the property "date", contained within the attribute `office:value-type`, contained within the element `<table:covered-table-cell>`*

This property is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the property "float", contained within the attribute `office:value-type`, contained within the element `<table:covered-table-cell>`*

This property is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the property "percentage", contained within the attribute `office:value-type`, contained within the element `<table:covered-table-cell>`*

This property is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the property "string", contained within the attribute office:value-type, contained within the element <table:covered-table-cell>*

This property is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the property "time", contained within the attribute office:value-type, contained within the element <table:covered-table-cell>*

This property is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute office:boolean-value, contained within the element <table:table-cell>*

This attribute is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the attribute office:currency, contained within the element <table:table-cell>*

This attribute is not supported in Excel 2010 or Excel 2013.

- p. *The standard defines the attribute office:date-value, contained within the element <table:table-cell>*

This attribute is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the attribute office:string-value, contained within the element <table:table-cell>*

This attribute is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the attribute office:time-value, contained within the element <table:table-cell>*

This attribute is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the attribute office:value, contained within the element <table:table-cell>*

This attribute is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the property "boolean", contained within the attribute office:value-type, contained within the element <table:table-cell>*

This property is supported in Excel 2010 and Excel 2013.

- u. *The standard defines the property "currency", contained within the attribute office:value-type, contained within the element <table:table-cell>*

This property is supported in Excel 2010 and Excel 2013.

- v. *The standard defines the property "date", contained within the attribute office:value-type, contained within the element <table:table-cell>*

This property is supported in Excel 2010 and Excel 2013.

- w. *The standard defines the property "float", contained within the attribute office:value-type, contained within the element <table:table-cell>*

This property is supported in Excel 2010 and Excel 2013.

- x. *The standard defines the property "percentage", contained within the attribute office:value-type, contained within the element <table:table-cell>*

This property is supported in Excel 2010 and Excel 2013.

- y. *The standard defines the property "string", contained within the attribute office:value-type, contained within the element <table:table-cell>*

This property is supported in Excel 2010 and Excel 2013.

- z. *The standard defines the property "time", contained within the attribute office:value-type, contained within the element <table:table-cell>*

This property is supported in Excel 2010 and Excel 2013.

- aa. *The standard defines the attribute office:value-type*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.155 Section 6.7.2, Fixed

- a. This is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the attribute text:fixed*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.156 Section 6.7.3, Variable Name

- a. This is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the attribute text:name*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.157 Section 6.7.4, Description

- a. *The standard defines the attribute text:description*

This attribute is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute text:description*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.158 Section 6.7.5, Display

- a. This is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the attribute text:Display*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.159 Section 6.7.6, Formula

- a. *The standard defines the attribute text:formula*

This attribute is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute text:formula*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.160 Section 6.7.7, Formatting Style

- a. *The standard defines the attribute text:data-style-name*

This attribute is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:data-style-name*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.161 Section 6.7.8, Number Formatting Style

- a. *The standard defines the attribute style:num-format*

This attribute is supported in Word 2010 and Word 2013.

See Section 12.2.2 for supported formats.

- b. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes.

- c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.162 Section 7, Text Indices

- a. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.163 Section 7.1, Index Marks

- a. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.164 Section 7.1.1, Table of Content Index Marks

- a. *The standard defines the element <text:toc-mark>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:outline-level, contained within the element <text:toc-mark>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:string-value, contained within the element <text:toc-mark>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the element <text:toc-mark-end>*

This element is supported in Word 2010 and Word 2013.

On load, Word collapses the range encapsulated by a <text:toc-mark-start> element and a <text:toc-mark-end> element to a single <text:toc-mark> element.

- e. *The standard defines the element <text:toc-mark-start>*

This element is supported in Word 2010 and Word 2013.

On load, Word collapses the range encapsulated by a <text:toc-mark-start> element and a <text:toc-mark-end> element to a single <text:toc-mark> element.

- f. *The standard defines the attribute text:id, contained within the element <text:toc-mark-start>*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute text:outline-level, contained within the element <text:toc-mark-start>*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the element <text:toc-mark>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- i. *The standard defines the element <text:toc-mark-end>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the element <text:toc-mark-start>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.165 Section 7.1.2, User-Defined Index Marks

- a. *The standard defines the element <text:user-index-mark>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <text:user-index-mark-end>*
This element is not supported in Word 2010 or Word 2013.
- c. *The standard defines the element <text:user-index-mark-start>*
This element is not supported in Word 2010 or Word 2013.
- d. *The standard defines the element <text:user-index-mark>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- e. *The standard defines the element <text:user-index-mark-end>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.
- f. *The standard defines the element <text:user-index-mark-start>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.166 Section 7.1.3, Alphabetical Index Mark

- a. *The standard defines the element <text:alphabetical-index-mark>*
This element is supported in Word 2010 and Word 2013.
- b. *The standard defines the attribute text:key1, contained within the element <text:alphabetical-index-mark>*
This attribute is supported in Word 2010 and Word 2013.
- c. *The standard defines the attribute text:key1-phonetic, contained within the element <text:alphabetical-index-mark>*
This attribute is not supported in Word 2010 or Word 2013.
- d. *The standard defines the attribute text:key2, contained within the element <text:alphabetical-index-mark>*
This attribute is supported in Word 2010 and Word 2013.
- e. *The standard defines the attribute text:key2-phonetic, contained within the element <text:alphabetical-index-mark>*
This attribute is not supported in Word 2010 or Word 2013.
- f. *The standard defines the attribute text:main-entry, contained within the element <text:alphabetical-index-mark>*
This attribute is not supported in Word 2010 or Word 2013.
- g. *The standard defines the attribute text:string-value, contained within the element <text:alphabetical-index-mark>*
This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute `text:string-value-phonetic`, contained within the element `<text:alphabetical-index-mark>`*

This attribute is supported in Word 2010 and Word 2013.

- i. *The standard defines the element `<text:alphabetical-index-mark-end>`*

This element is supported in Word 2010 and Word 2013.

On load, Word collapses the range encapsulated by a `<text:alphabetical-index-mark-start>` element and `<text:alphabetical-index-mark-end>` element to a single `<text:alphabetical-index-mark>` element.

- j. *The standard defines the element `<text:alphabetical-index-mark-start>`*

This element is supported in Word 2010 and Word 2013.

On load, Word collapses the range encapsulated by a `<text:alphabetical-index-mark-start>` element and `<text:alphabetical-index-mark-end>` element to a single `<text:alphabetical-index-mark>` element.

- k. *The standard defines the attribute `text:id`, contained within the element `<text:alphabetical-index-mark-start>`*

This attribute is not supported in Word 2010 or Word 2013.

- l. *The standard defines the attribute `text:key1`, contained within the element `<text:alphabetical-index-mark-start>`*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute `text:key1-phonetic`, contained within the element `<text:alphabetical-index-mark-start>`*

This attribute is not supported in Word 2010 or Word 2013.

- n. *The standard defines the attribute `text:key2`, contained within the element `<text:alphabetical-index-mark-start>`*

This attribute is not supported in Word 2010 or Word 2013.

- o. *The standard defines the attribute `text:key2-phonetic`, contained within the element `<text:alphabetical-index-mark-start>`*

This attribute is not supported in Word 2010 or Word 2013.

- p. *The standard defines the attribute `text:main-entry`, contained within the element `<text:alphabetical-index-mark-start>`*

This attribute is not supported in Word 2010 or Word 2013.

- q. *The standard defines the attribute `text:string-value-phonetic`, contained within the element `<text:alphabetical-index-mark-start>`*

This attribute is supported in Word 2010 and Word 2013.

- r. *The standard defines the element `<text:alpha-index-mark>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the element `<text:alpha-index-mark-end>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- t. *The standard defines the element <text:alpha-index-mark-start>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.167 Section 7.1.4, Bibliography Index Mark

- a. *The standard defines the element <text:bibliography-mark>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:bibliography-mark>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.168 Section 7.2, Index Structure

- a. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.169 Section 7.2.1, Index Source

- a. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.170 Section 7.2.2, Index Body Section

- a. *The standard defines the element <text:index-body>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <text:index-body>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.171 Section 7.2.3, Index Title Section

- a. *The standard defines the element <text:index-title>, contained within the parent element <text:index-body>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:index-title>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.172 Section 7.3, Table Of Content

- a. *The standard defines the element <text:table-of-content>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:style-name, contained within the element <text:table-of-content>*

This attribute is not supported in Word 2010 or Word 2013.

On load, Word ignores the table of contents style and uses a default table of contents style.

On save, Word writes out the style of the table of contents.

- c. *The standard defines the element <text:table-of-content>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.173 Section 7.3.1, Table of Content Source

- a. *The standard defines the element <text:table-of-content-source>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:index-scope, contained within the element <text:table-of-content-source>*

This attribute is not supported in Word 2010 or Word 2013.

On load, Word reverts to a default of "document" for all values of the text:index-scope attribute.

- c. *The standard defines the attribute text:outline-level, contained within the element <text:table-of-content-source>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute text:relative-tab-stop-position, contained within the element <text:table-of-content-source>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute text:use-index-marks, contained within the element <text:table-of-content-source>*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute text:use-index-source-styles, contained within the element <text:table-of-content-source>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute text:user-outline-level, contained within the element <text:table-of-content-source>*

This attribute is supported in Word 2010 and Word 2013.

2.1.174 Section 7.3.2, Table of Content Entry Template

- a. *The standard defines the element <text:table-of-content-entry-template>*

This element is not supported in Word 2010 or Word 2013.

On load, Word ignores the table of contents style and uses a default table of contents style.

On save, Word writes out the style of the table of contents.

2.1.175 Section 7.4, Index of Illustrations

- a. *The standard defines the element <text:illustration-index>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:illustration-index>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.176 Section 7.4.1, Index of Illustration Source

- a. *The standard defines the element <text:illustration-index-source>*

This element is not supported in Word 2010 or Word 2013.

2.1.177 Section 7.4.2, Illustration Index Entry Template

- a. *The standard defines the element <text:illustration-index-entry-template>*

This element is not supported in Word 2010 or Word 2013.

2.1.178 Section 7.5, Index of Tables

- a. *The standard defines the element <text:table-index>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:table-index>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.179 Section 7.5.1, Table Index Source

- a. *The standard defines the element <text:table-index-source>*

This element is not supported in Word 2010 or Word 2013.

2.1.180 Section 7.5.2, Table Index Entry Template

- a. *The standard defines the element <text:table-index-entry-template>*

This element is not supported in Word 2010 or Word 2013.

2.1.181 Section 7.6, Index of Objects

- a. *The standard defines the element <text:object-index>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:object-index>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.182 Section 7.6.1, Object Index Source

- a. *The standard defines the element <text:object-index-source>*

This element is not supported in Word 2010 or Word 2013.

2.1.183 Section 7.6.2, Object Index Entry Template

- a. *The standard defines the element <text:object-index-entry-template>*

This element is not supported in Word 2010 or Word 2013.

2.1.184 Section 7.7, User-Defined Index

- a. *The standard defines the element <text:user-index>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:user-index>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.185 Section 7.7.1, User-Defined Index Source

- a. *The standard defines the element <text:user-index-source>*

This element is not supported in Word 2010 or Word 2013.

2.1.186 Section 7.7.2, User-Defined Index Entry Template

- a. *The standard defines the element <text:user-index-entry-template>*

This element is not supported in Word 2010 or Word 2013.

2.1.187 Section 7.8, Alphabetical Index

- a. *The standard defines the element <text:alphabetical-index>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <text:alphabetical-index>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.188 Section 7.8.1, Alphabetical Index Source

- a. *The standard defines the element <text:alphabetical-index-source>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute fo:country, contained within the element <text:alphabetical-index-source>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute fo:language, contained within the element <text:alphabetical-index-source>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute text:alphabetical-separators, contained within the element <text:alphabetical-index-source>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute text:capitalize-entries, contained within the element <text:alphabetical-index-source>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute `text:combine-entries`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute `text:combine-entries-with-dash`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute `text:combine-entries-with-pp`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute `text:comma-separated`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute `text:ignore-case`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- k. *The standard defines the attribute `text:index-scope`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

On load, Word reverts to a default of "document" for all values of the `text:index-scope` attribute.

- l. *The standard defines the attribute `text:main-entry-style-name`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute `text:relative-tab-stop-position`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- n. *The standard defines the attribute `text:sort-algorithm`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

- o. *The standard defines the attribute `text:use-keys-as-entries`, contained within the element `<text:alphabetical-index-source>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.189 Section 7.8.2, Auto Mark File

- a. *The standard defines the element `<text:alphabetical-index-auto-mark-file>`*

This element is not supported in Word 2010 or Word 2013.

2.1.190 Section 7.8.3, Alphabetical Index Entry Template

- a. *The standard defines the element `<text:alphabetical-index-entry-template>`*

This element is not supported in Word 2010 or Word 2013.

2.1.191 Section 7.9, Bibliography

- a. *The standard defines the element <text:bibliography>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:bibliography-mark>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.192 Section 7.9.1, Bibliography Index Source

- a. *The standard defines the element <text:bibliography-source>*

This element is not supported in Word 2010 or Word 2013.

2.1.193 Section 7.9.2, Bibliography Entry Template

- a. *The standard defines the element <text:bibliography-entry-template>*

This element is not supported in Word 2010 or Word 2013.

2.1.194 Section 7.10, index source styles

- a. *The standard defines the element <text:index-source-styles>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:outline-level, contained within the element <text:index-source-styles>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the element <text:index-source-styles>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.195 Section 7.10.1, Index source style

- a. *The standard defines the element <text:index-source-style>, contained within the parent element <text:index-source-styles>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:style-name, contained within the element <text:index-source-style>, contained within the parent element <text:index-source-styles>*

This attribute is supported in Word 2010 and Word 2013.

2.1.196 Section 7.11, Index title template

- a. *The standard defines the element <text:index-title-template>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:index-title-template>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.197 Section 7.12.1, Chapter Information

- a. *The standard defines the element <text:index-entry-chapter>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute text:display, contained within the element <text:index-entry-chapter>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-chapter>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <text:index-entry-chapter>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.198 Section 7.12.2, Entry Text

- a. *The standard defines the element <text:index-entry-text>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-text>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word ignores this element and reverts to a default index style. On save, Word writes this element within its table of contents and index.

- c. *The standard defines the element <text:index-entry-text>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.199 Section 7.12.3, Page Number

- a. *The standard defines the element <text:index-entry-page-number>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-page-number>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word ignores this element and reverts to a default index style. On save, Word writes this element within its table of contents and index.

- c. *The standard defines the element <text:index-entry-page-number>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.200 Section 7.12.4, Fixed String

- a. *The standard defines the element <text:index-entry-span>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:index-entry-span>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.201 Section 7.12.5, Bibliography Information

- a. *The standard defines the element <text:index-entry-bibliography>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:index-entry-bibliography>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.202 Section 7.12.6, Tab Stop

- a. *The standard defines the element <text:index-entry-tab-stop>*

This element is supported in Word 2010 and Word 2013.

On load, Word ignores this element and uses a default style to format tables of contents and indexes. On save, Word saves this element for tables of contents, but not for indexes.

- b. *The standard defines the attribute style:leader-char, contained within the element <text:index-entry-tab-stop>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word ignores this element and uses a default style to format tables of contents and indexes. On save, Word saves this element for tables of contents, but not for indexes.

- c. *The standard defines the attribute style:position, contained within the element <text:index-entry-tab-stop>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute style:type, contained within the element <text:index-entry-tab-stop>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <text:index-entry-tab-stop>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.203 Section 7.12.7, Hyperlink Start and End

- a. *The standard defines the element <text:index-entry-link-end>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-link-end>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <text:index-entry-link-start>*

This element is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute text:style-name, contained within the element <text:index-entry-link-start>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <text:index-entry-link-end>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the element <text:index-entry-link-start>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.204 Section 7.12.8, Example of an Index Entry Configuration

- a. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.205 Section 8, Tables

- a. *The standard defines the parent element <chart:chart \..>*

This is supported in Excel 2010 and Excel 2013.

- b. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.206 Section 8.1, Basic Table Model

- a. This is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the parent element <chart:chart \..>*

This is supported in Excel 2010 and Excel 2013.

- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.207 Section 8.1.1, Table Element

- a. *The standard defines the element <table:table>*

This element is supported in Word 2010 and Word 2013.

On save, Word converts floating tables to inline tables.

- b. *The standard defines the element <table:table>, contained within the parent element <draw:text-box>*

This element is supported in Word 2010 and Word 2013.

On load, tables in textboxes are supported.

On save, a Word frame becomes an ODF textbox. If the Word frame contains a table, the frame content is saved but the frame itself is lost. If a Word textbox contains a table, then both the textbox contents and the table are saved.

- c. *The standard defines the element <table:table>, contained within the parent element <office:annotation>*

This element is not supported in Word 2010 or Word 2013.

On load and save, Word does not support tables inside annotations. Word retains the contents of the table but loses the table structure.

- d. *The standard defines the attribute style:cell-protect, contained within the element <table:table>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute table:name, contained within the element <table:table>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute table:print, contained within the element <table:table>*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute table:print-ranges, contained within the element <table:table>*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute table:protected, contained within the element <table:table>*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute table:protection-key, contained within the element <table:table>*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute table:style-name, contained within the element <table:table>*

This attribute is supported in Word 2010 and Word 2013.

Word does not support the use of common styles from the table family, that is using a table style defined under the <office:styles> element.

- k. *The standard defines the element <text:soft-page-break>, contained within the parent element <table:table>*

This element is supported in Word 2010 and Word 2013.

Word writes out this element everywhere it would for all its other document formats, as long as it is allowed in that location by the ODF specification.

- l. *The standard defines the element <office:dde-source>, contained within the parent element <office:spreadsheet \ table:table>*

This element is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the element <office:dde-source>, contained within the parent element <table:dde-link>*

This element is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the element <office:forms>, contained within the parent element <office:spreadsheet \ table:table>*

This element is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the element <office:forms>, contained within the parent element <table:dde-link>*
This element is not supported in Excel 2010 or Excel 2013.
- p. *The standard defines the element <table:scenario>, contained within the parent element <office:spreadsheet \ table:table>*
This element is supported in Excel 2010 and Excel 2013.
- q. *The standard defines the element <table:scenario>, contained within the parent element <table:dde-link>*
This element is not supported in Excel 2010 or Excel 2013.
- r. *The standard defines the element <table:shapes>, contained within the parent element <office:spreadsheet \ table:table>*
This element is supported in Excel 2010 and Excel 2013.
- s. *The standard defines the element <table:shapes>, contained within the parent element <table:dde-link>*
This element is not supported in Excel 2010 or Excel 2013.
- t. *The standard defines the element <table:table>, contained within the parent element <chart:chart \ table-table>*
This element is supported in Excel 2010 and Excel 2013.
- u. *The standard defines the element <table:table>, contained within the parent element <header-footer-content>*
This element is not supported in Excel 2010 or Excel 2013.
- v. *The standard defines the element <table:table>, contained within the parent element <office:spreadsheet>*
This element is supported in Excel 2010 and Excel 2013.
- w. *The standard defines the element <table:table>, contained within the parent element <table:dde-link>*
This element is supported in Excel 2010 and Excel 2013.
This element is supported in Excel 2010 and Excel 2013.
- x. *The standard defines the element <table:table>, contained within the parent element <text-content>*
This element is not supported in Excel 2010 or Excel 2013.
- y. *The standard defines the attribute table:name, contained within the element <table:table>, contained within the parent element <office:spreadsheet>*
This attribute is supported in Excel 2010 and Excel 2013.
Excel supports sheet names that are shorter than 32 characters.
- z. *The standard defines the attribute table:name, contained within the element <table:table>, contained within the parent element <table:dde-link>*

This attribute is not supported in Excel 2010 or Excel 2013.

- aa. *The standard defines the attribute `table:print`, contained within the element `<table:table>`, contained within the parent element `<office:spreadsheet>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- bb. *The standard defines the attribute `table:print`, contained within the element `<table:table>`, contained within the parent element `<table:dde-link>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- cc. *The standard defines the attribute `table:print-ranges`, contained within the element `<table:table>`, contained within the parent element `<office:spreadsheet>`*

This attribute is supported in Excel 2010 and Excel 2013.

- dd. *The standard defines the attribute `table:print-ranges`, contained within the element `<table:table>`, contained within the parent element `<table:dde-link>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- ee. *The standard defines the attribute `table:protected`, contained within the element `<table:table>`, contained within the parent element `<office:spreadsheet>`*

This attribute is supported in Excel 2010 and Excel 2013.

- ff. *The standard defines the attribute `table:protected`, contained within the element `<table:table>`, contained within the parent element `<table:dde-link>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- gg. *The standard defines the attribute `table:style-name`, contained within the element `<table:table>`, contained within the parent element `<office:spreadsheet>`*

This attribute is supported in Excel 2010 and Excel 2013.

- hh. *The standard defines the attribute `table:style-name`, contained within the element `<table:table>`, contained within the parent element `<table:dde-link>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- ii. *The standard defines the attribute `text:soft-page-break`, contained within the element `<table:table>`, contained within the parent element `<table:dde-link>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- jj. *The standard defines the element `<table:table-source>`, contained within the parent element `<office:spreadsheet \ table:table>`*

This element is supported in Excel 2010 and Excel 2013.

- kk. *The standard defines the element `<text:soft-page-break>`, contained within the parent element `<table-rows>`*

This element is not supported in Excel 2010 or Excel 2013.

- ll. *The standard defines the element `<table:table>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.208 Section 8.1.2, Table Row

- a. *The standard defines the element <table:table-row>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute table:default-cell-style-name, contained within the element <table:table-row>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads and respects this property. However, on save, Word writes out these properties as properties in the styles of individual cells.

- c. *The standard defines the attribute table:number-rows-repeated, contained within the element <table:table-row>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute table:style-name, contained within the element <table:table-row>*

This attribute is supported in Word 2010 and Word 2013.

Word does not support the use of common styles from the table-row family, that is using a table style defined under the <office:styles> element.

- e. *The standard defines the attribute table:visibility, contained within the element <table:table-row>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <table:table-row>, contained within the parent element <chart:chart \..\ table-table-row>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the element <table:table-row>, contained within the parent element <office:spreadsheet \ table:table>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the element <table:table-row>, contained within the parent element <table:dde-link \ table:table>*

This element is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute table:default-cell-style-name, contained within the element <table:table-row>, contained within the parent element <office:spreadsheet \ table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute table:default-cell-style-name, contained within the element <table:table-row>, contained within the parent element <table:dde-link \ table:table>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute table:number-rows-repeated, contained within the element <table:table-row>, contained within the parent element <office:spreadsheet \ table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the attribute `table:number-rows-repeated`, contained within the element `<table:table-row>`, contained within the parent element `<table:dde-link \ table:table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-row>`, contained within the parent element `<office:spreadsheet \ table:table>`*

This attribute is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-row>`, contained within the parent element `<table:dde-link \ table:table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-row>`, contained within the parent element `<office:spreadsheet \ table:table>`*

This attribute is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-row>`, contained within the parent element `<table:dde-link \ table:table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.209 Section 8.1.3, Table Cell

- a. *The standard defines the element `<table:covered-table-cell>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `office:boolean-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `office:currency`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `office:date-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `office:string-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute `office:time-value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute `office:value`, contained within the element `<table:covered-table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute `table:content-validation-name`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- i. *The standard defines the attribute `table:formula`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- j. *The standard defines the attribute `table:number-columns-repeated`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- k. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- l. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- m. *The standard defines the attribute `table:protected`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- n. *The standard defines the attribute `table:style-name`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- o. *The standard defines the attribute `table:value-type`, contained within the element `<table:covered-table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- p. *The standard defines the element `<table:table-cell>`*
- This element is supported in Word 2010 and Word 2013.
- q. *The standard defines the attribute `office:boolean-value`, contained within the element `<table:table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- r. *The standard defines the attribute `office:currency`, contained within the element `<table:table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- s. *The standard defines the attribute `office:date-value`, contained within the element `<table:table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.
- t. *The standard defines the attribute `office:string-value`, contained within the element `<table:table-cell>`*
- This attribute is not supported in Word 2010 or Word 2013.

- u. *The standard defines the attribute `office:time-value`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- v. *The standard defines the attribute `office:value`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- w. *The standard defines the attribute `table:content-validation-name`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- x. *The standard defines the attribute `table:formula`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- y. *The standard defines the attribute `table:number-columns-repeated`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- z. *The standard defines the attribute `table:number-columns-spanned`, contained within the element `<table:table-cell>`*

This attribute is supported in Word 2010 and Word 2013.

- aa. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- bb. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- cc. *The standard defines the attribute `table:number-rows-spanned`, contained within the element `<table:table-cell>`*

This attribute is supported in Word 2010 and Word 2013.

- dd. *The standard defines the attribute `table:protected`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

- ee. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-cell>`*

This attribute is supported in Word 2010 and Word 2013.

Word does not support the use of common styles from the table-cell family, that is using a table style defined under the `<office:styles>` element.

- ff. *The standard defines the attribute `table:value-type`, contained within the element `<table:table-cell>`*

This attribute is not supported in Word 2010 or Word 2013.

gg. *The standard defines the element <office:annotation>, contained within the parent element <office:spreadsheet \ table:table-cell>*

This element is supported in Excel 2010 and Excel 2013.

hh. *The standard defines the element <office:annotation>, contained within the parent element <table:dde-link \ table:table-cell>*

This element is not supported in Excel 2010 or Excel 2013.

ii. *The standard defines the attribute style:cell-protect, contained within the element <style:table-cell-properties>, contained within the parent element <table:dde-link \ table:table-cell>*

This attribute is not supported in Excel 2010 or Excel 2013.

jj. *The standard defines the attribute style:cell-protect, contained within the element <style:table-cell-properties>, contained within the parent element <table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

kk. *The standard defines the element <table:cell-range-source>, contained within the parent element <office:spreadsheet \ table:table-cell>*

This element is supported in Excel 2010 and Excel 2013.

ll. *The standard defines the element <table:cell-range-source>, contained within the parent element <table:dde-link \ table:table-cell>*

This element is not supported in Excel 2010 or Excel 2013.

mm. *The standard defines the element <table:covered-table-cell>, contained within the parent element <chart:chart \.. \ table-covered-table-cell>*

This element is not supported in Excel 2010 or Excel 2013.

nn. *The standard defines the element <table:covered-table-cell>, contained within the parent element <office:spreadsheet \ table:table-row>*

This element is supported in Excel 2010 and Excel 2013.

oo. *The standard defines the element <table:covered-table-cell>, contained within the parent element <table:dde-link \ table:table-row>*

This element is not supported in Excel 2010 or Excel 2013.

pp. *The standard defines the attribute table:content-validation-name, contained within the element <table:covered-table-cell>, contained within the parent element <office:spreadsheet \ table:table-row>*

This attribute is not supported in Excel 2010 or Excel 2013.

qq. *The standard defines the attribute table:formula, contained within the element <table:covered-table-cell>, contained within the parent element <office:spreadsheet \ table:table-row>*

This attribute is not supported in Excel 2010 or Excel 2013.

rr. *The standard defines the attribute table:number-columns-repeated, contained within the element <table:covered-table-cell>, contained within the parent element <office:spreadsheet \ table:table-row>*

This attribute is supported in Excel 2010 and Excel 2013.

ss. *The standard defines the attribute `table:number-columns-spanned`, contained within the element `<table:covered-table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

tt. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:covered-table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

uu. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:covered-table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

vv. *The standard defines the attribute `table:number-rows-spanned`, contained within the element `<table:covered-table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ww. *The standard defines the attribute `table:style-name`, contained within the element `<table:covered-table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

xx. *The standard defines the attribute `table:value-type`, contained within the element `<table:covered-table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

yy. *The standard defines the element `<table:detective>`, contained within the parent element `<office:spreadsheet \ table:table-cell>`*

This element is not supported in Excel 2010 or Excel 2013.

zz. *The standard defines the element `<table:detective>`, contained within the parent element `<table:dde-link \ table:table-cell>`*

This element is not supported in Excel 2010 or Excel 2013.

aaa. *The standard defines the element `<table:table-cell>`, contained within the parent element `<chart:chart \..\ table-table-cell>`*

This element is supported in Excel 2010 and Excel 2013.

bbb. *The standard defines the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This element is supported in Excel 2010 and Excel 2013.

ccc. *The standard defines the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This element is supported in Excel 2010 and Excel 2013.

ddd. *The standard defines the attribute `table:content-validation-name`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

eee. *The standard defines the attribute `table:content-validation-name`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

fff. *The standard defines the attribute `table:formula`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

1. When saving the `table:formula` attribute, Excel precedes the formula string with the "of" namespace.
2. When saving the `table:formula` attribute, Excel saves a formula string that follows [ODF1.2] part 2.
3. When loading the attribute `table:formula`, Excel first looks at the namespace. If the namespace is 'of', 'msoxl' or not specified, Excel will attempt to load the value of `table:formula` as a formula in Excel.
4. Formulas using the 'of' namespace and those without a namespaces are expected to follow [ODF1.2] part 2.
5. Formulas using the 'msoxl' namespace follow [\[ISO/IEC-29500-1\]](#) section 18.17, except workbook-names are written as literal values instead of tokens given the lack of a relationship part.
6. When loading the `table:formula` attribute, if the namespace is unknown, the `table:formula` attribute is not loaded, and the value "office:value" is used instead. If the result of the formula is an error, Excel loads the `<text:p>` element and maps the element to an Error data type. Error data types that Excel does not support are mapped to #VALUE!

ggg. *The standard defines the attribute `table:formula`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

hhh. *The standard defines the attribute `table:number-columns-repeated`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

iii. *The standard defines the attribute `table:number-columns-repeated`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

jjj. *The standard defines the attribute `table:number-columns-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

kkk. *The standard defines the attribute `table:number-columns-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

lll. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

mmm. *The standard defines the attribute `table:number-matrix-columns-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

nnn. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

ooo. *The standard defines the attribute `table:number-matrix-rows-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ppp. *The standard defines the attribute `table:number-rows-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

qqq. *The standard defines the attribute `table:number-rows-spanned`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

rrr. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

sss. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ttt. *The standard defines the attribute `table:value`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

uuu. *The standard defines the attribute `table:value-type`, contained within the element `<table:table-cell>`, contained within the parent element `<office:spreadsheet \ table:table-row>`*

This attribute is not supported in Excel 2010 or Excel 2013.

vvv. *The standard defines the attribute `table:value-type`, contained within the element `<table:table-cell>`, contained within the parent element `<table:dde-link \ table:table-row>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.210 Section 8.2, Advanced Table Model

a. This is supported in Excel 2010 and Excel 2013.

b. *The standard defines the parent element `<chart:chart \..\>`*

This is supported in Excel 2010 and Excel 2013.

2.1.211 Section 8.2.1, Column Description

- a. *The standard defines the element <table:table-column>*

This element is supported in Word 2010 and Word 2013.

Word does not support more than 63 columns. On load, any columns beyond this limit are dropped, along with their content.

- b. *The standard defines the attribute table:default-cell-style-name, contained within the element <table:table-column>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads and respects this property. However, on save, Word writes out these properties as properties in the styles of individual cells.

- c. *The standard defines the attribute table:number-columns-repeated, contained within the element <table:table-column>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute table:style-name, contained within the element <table:table-column>*

This attribute is supported in Word 2010 and Word 2013.

Word does not support the use of common styles from the table-column family, that is using a table style defined under the <office:styles> element.

- e. *The standard defines the attribute table:visibility, contained within the element <table:table-column>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <table:table-column>, contained within the parent element <chart:chart \..\ table-table-column>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the element <table:table-column>, contained within the parent element <office:spreadsheet \ table:table>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the element <table:table-column>, contained within the parent element <table:dde-link \ table:table>*

This element is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute table:default-cell-style-name, contained within the element <table:table-column>, contained within the parent element <office:spreadsheet \ table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute table:default-cell-style-name, contained within the element <table:table-column>, contained within the parent element <table:dde-link \ table:table>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute `table:number-columns-repeated`, contained within the element `<table:table-column>`, contained within the parent element `<office:spreadsheet \ table:table>`*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the attribute `table:number-columns-repeated`, contained within the element `<table:table-column>`, contained within the parent element `<table:dde-link \ table:table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-column>`, contained within the parent element `<office:spreadsheet \ table:table>`*

This attribute is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the attribute `table:style-name`, contained within the element `<table:table-column>`, contained within the parent element `<table:dde-link \ table:table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-column>`, contained within the parent element `<office:spreadsheet \ table:table>`*

This attribute is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the attribute `table:visibility`, contained within the element `<table:table-column>`, contained within the parent element `<table:dde-link \ table:table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.212 Section 8.2.2, Header Columns

- a. *The standard defines the element `<table:table-columns>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element `<table:table-header-columns>`*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element `<table:table-columns>`, contained within the parent element `<chart:chart \..\ table-table-columns>`*

This element is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the element `<table:table-header-columns>`, contained within the parent element `<chart:chart \..\ table-table-header-columns>`*

This element is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the element `<table:table-header-columns>`, contained within the parent element `<office:spreadsheet \ table:table>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads this element and treats it as a regular column, but never writes it out on save.

- f. *The standard defines the element `<table:table-header-columns>`, contained within the parent element `<table:dde-link \ table:table>`*

This element is not supported in Excel 2010 or Excel 2013.

On load, Excel reads this element and treats it as a regular column, but never writes it out on save.

2.1.213 Section 8.2.3, Column Groups

- a. *The standard defines the element <table:table-column-group>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element <chart:chart \..\>*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute table:display, contained within the element <table:table-column-group>, contained within the parent element <office:spreadsheet \ table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the attribute table:display, contained within the element <table:table-column-group>, contained within the parent element <table:dde-link \ table:table>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.214 Section 8.2.4, Header Rows

- a. *The standard defines the element <table:table-header-rows>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <table:table-header-rows>, contained within the parent element <chart:chart \..\ table-table-header-rows>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the element <table:table-header-rows>, contained within the parent element <office:spreadsheet \ table:table>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads this element and treats it as a regular row, but never writes it out on save.

- d. *The standard defines the element <table:table-header-rows>, contained within the parent element <table:dde-link \ table:table>*

This element is not supported in Excel 2010 or Excel 2013.

On load, Excel reads the element <table:table-header-rows> and treats it as a regular row, but on save, the element <table:table-header-rows> is never written.

- e. *The standard defines the element <table:table-rows>, contained within the parent element <chart:chart \..\ table-table-rows>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads this element, but does not write it on save.

2.1.215 Section 8.2.5, Row Groups

- a. *The standard defines the element <table:table-row-group>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the parent element <chart:chart \..>*
This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the attribute table:display, contained within the element <table:table-row-group>, contained within the parent element <office:spreadsheet \ table:table>*
This attribute is supported in Excel 2010 and Excel 2013.
- d. *The standard defines the attribute table:display, contained within the element <table:table-row-group>, contained within the parent element <table:dde-link \ table:table>*
This attribute is not supported in Excel 2010 or Excel 2013.

2.1.216 Section 8.2.6, Subtables

- a. *The standard defines the attribute table:is-subtable, contained within the element <table:table>*
This attribute is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the parent element <chart:chart \..>*
This is not supported in Excel 2010 or Excel 2013.

2.1.217 Section 8.3, Advanced Tables

- a. This is supported in Excel 2010 and Excel 2013.

2.1.218 Section 8.3.1, Referencing Table Cells

- a. This is not supported in Word 2010 or Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.

2.1.219 Section 8.3.2, Linked Tables

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute table:filter-name, contained within the element <table:table-source>, contained within the parent element <table:table>*
This attribute is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the attribute table:filter-options, contained within the element <table:table-source>, contained within the parent element <table:table>*
This attribute is not supported in Excel 2010 or Excel 2013.
- d. *The standard defines the attribute table:mode, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "copy-all", contained within the attribute table:mode, contained within the element <table:table-source>, contained within the parent element <table:table>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel reads the value of "copy-all" and maps it to copy-results-only. Excel does not write this property on save.

- f. *The standard defines the property "copy-results-only", contained within the attribute table:mode, contained within the element <table:table-source>, contained within the parent element <table:table>*

This property is supported in Excel 2010 and Excel 2013.

On load, Excel always reads table:mode as "copy-results-only". On save, Excel always writes this attribute as "copy-results-only".

- g. *The standard defines the attribute table:refresh-delay, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute table:table-name, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute xlink:actuate, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute xlink:href, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the attribute xlink:type, contained within the element <table:table-source>, contained within the parent element <table:table>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.220 Section 8.3.3, Scenario Tables

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <table:scenario>*

This element is supported in Excel 2010 and Excel 2013.

Excel stores the scenario name in the table:name attribute of the parent table.

- c. *The standard defines the attribute table:border-color, contained within the element <table:scenario>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute table:comment, contained within the element <table:scenario>*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute `table:copy-back`, contained within the element `<table:scenario>`*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel ignores this attribute. On save, Excel writes it out as false.

- f. *The standard defines the attribute `table:copy-formulas`, contained within the element `<table:scenario>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `table:copy-style`, contained within the element `<table:scenario>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `table:display-border`, contained within the element `<table:scenario>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `table:is-active`, contained within the element `<table:scenario>`*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute `table:protected`, contained within the element `<table:scenario>`*

This attribute is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the attribute `table:scenario-ranges`, contained within the element `<table:scenario>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.221 Section 8.3.4, Shapes

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<table:shapes>`, contained within the parent element `<table-shapes>`*

This element is supported in Excel 2010 and Excel 2013.

2.1.222 Section 8.4, Advanced Table Cells

- a. This is not supported in Word 2010 or Word 2013.

2.1.223 Section 8.4.1, Linked Table Cells

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:filter-name`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:filter-options`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:last-column-spanned`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute `table:last-row-spanned`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the attribute `table:refresh-delay`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the attribute `xlink:actuate`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `xlink:href`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute `xlink:type`, contained within the element `<table:cell-range-source>`, contained within the parent element `<table:table-cell>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.224 Section 8.4.2, Cell Annotation

- a. This is not supported in Word 2010 or Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.

2.1.225 Section 8.4.3, Detective

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element `<table:detective>`*

This element is not supported in Excel 2010 or Excel 2013.

2.1.226 Section 8.4.4, Detective Operation

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute `table:operation`, contained within the element `<table:detective>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:index`, contained within the element `<table:operation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:name`, contained within the element `<table:operation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.227 Section 8.4.5, Highlighted Range

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:cell-range-address`, contained within the element `<table:detective>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:contains-error`, contained within the element `<table:detective>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:direction`, contained within the element `<table:detective>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `table:highlighted-range`, contained within the element `<table:detective>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `table:marked-invalid`, contained within the element `<table:detective>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.228 Section 8.5, Spreadsheet Document Content

- a. This is supported in Excel 2010 and Excel 2013.

2.1.229 Section 8.5.1, Document Protection

- a. *The standard defines the attribute `table:protection-key`, contained within the element `<office:spreadsheet>`*

This attribute is not supported in Excel 2010 or Excel 2013.

Excel does not load a workbook if a protection-key is specified.

- b. *The standard defines the attribute `table:structure-protected`, contained within the element `<office:spreadsheet>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.230 Section 8.5.2, Calculation Settings

- a. *The standard defines the element `<table:calculation-settings>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:automatic-find-labels`, contained within the element `<table:calculation-settings>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:case-sensitive`, contained within the element `<table:calculation-settings>`*

This attribute is supported in Excel 2010.

The `table:case-sensitive` attribute is never loaded. However, Excel always behaves as though this setting were "false". To be consistent, on save, Excel always sets the `table:case-sensitive` attribute to "false".

This attribute is supported in Excel 2013.

- d. *The standard defines the attribute `table:Null-year`, contained within the element `<table:calculation-settings>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `table:precision-as-shown`, contained within the element `<table:calculation-settings>`*

This attribute is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the attribute `table:use-regular-expression`, contained within the element `<table:calculation-settings>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `table:maximum-difference`, contained within the element `<table:iteration>`, contained within the parent element `<table:calculation-settings>`*

This attribute is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute `table:status`, contained within the element `<table:iteration>`, contained within the parent element `<table:calculation-settings>`*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute `table:steps`, contained within the element `<table:iteration>`, contained within the parent element `<table:calculation-settings>`*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute `table:date-value`, contained within the element `<table:null-date>`, contained within the parent element `<table:calculation-settings>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel supports the `table:date-value` attribute for only the values "1899-12-30" and "1904-01-01". Excel does not load the `table:date-value` attribute if it is set to other values.

- k. *The standard defines the attribute `table:value-type`, contained within the element `<table:null-date>`, contained within the parent element `<table:calculation-settings>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.231 Section 8.5.3, Table Cell Content Validations

- a. *The standard defines the element <table:content-validation>*

This element is supported in Excel 2010 and Excel 2013.
- b. *The standard defines the attribute table:allow-empty-cell, contained within the element <table:content-validation>*

This attribute is supported in Excel 2010 and Excel 2013.
- c. *The standard defines the attribute table:base-cell-address, contained within the element <table:content-validation>*

This attribute is supported in Excel 2010 and Excel 2013.
- d. *The standard defines the attribute table:condition, contained within the element <table:content-validation>*

This attribute is supported in Excel 2010.

 1. Excel does not support the "cell-content-is-in-list" validation.
 2. Excel does not support the function cell-content-is-text(), and data validation is lost in this case.

This attribute is supported in Excel 2013.
- e. *The standard defines the attribute table:display-list, contained within the element <table:content-validation>*

This attribute is supported in Excel 2010 and Excel 2013.

If table:display-list is set to "sort-ascending", Excel loads and saves data as unsorted.
- f. *The standard defines the attribute table:error-macro, contained within the element <table:content-validation>*

This attribute is not supported in Excel 2010 or Excel 2013.
- g. *The standard defines the attribute table:error-message, contained within the element <table:content-validation>*

This attribute is supported in Excel 2010 and Excel 2013.
- h. *The standard defines the attribute table:help-message, contained within the element <table:content-validation>*

This attribute is supported in Excel 2010 and Excel 2013.
- i. *The standard defines the attribute table:name, contained within the element <table:content-validation>*

This attribute is supported in Excel 2010 and Excel 2013.

The table:name attribute is required, Excel doesn't load the validation if this attribute is missing.
- j. *The standard defines the element <table:content-validations>*

This element is supported in Excel 2010 and Excel 2013.

2.1.232 Section 8.5.4, Label Ranges

- a. *The standard defines the element <table:label-range>, contained within the parent element <table:label-ranges>*

This element is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the attribute table:data-cell-range-address, contained within the element <table:label-range>, contained within the parent element <table:label-ranges>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute table:label-cell-range-address, contained within the element <table:label-range>, contained within the parent element <table:label-ranges>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute table:orientation, contained within the element <table:label-range>, contained within the parent element <table:label-ranges>*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the element <table:label-ranges>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.233 Section 8.5.5, Named Expressions

- a. *The standard defines the element <table:named-expression>, contained within the parent element <table:named-expressions>*

This element is not supported in Excel 2010 or Excel 2013.

This element is supported in Excel 2013.

- b. *The standard defines the attribute table:base-cell-address, contained within the element <table:named-expression>, contained within the parent element <table:named-expressions>*

This attribute is not supported in Excel 2010 or Excel 2013.

This attribute is supported in Excel 2013.

- c. *The standard defines the attribute table:expression, contained within the element <table:named-expression>, contained within the parent element <table:named-expressions>*

This attribute is not supported in Excel 2010 or Excel 2013.

This attribute is supported in Excel 2013.

- d. *The standard defines the attribute table:name, contained within the element <table:named-expression>, contained within the parent element <table:named-expressions>*

This attribute is not supported in Excel 2010 or Excel 2013.

This attribute is supported in Excel 2013.

- e. *The standard defines the element <table:named-expressions>*

This element is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the element <table:named-range>, contained within the parent element <table:named-expressions>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the attribute `table:base-cell-address`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This attribute is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute `table:cell-range-address`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This attribute is supported in Excel 2010.

Excel does not save named ranges that refer to non-contiguous (non-rectangular) ranges.

This attribute is supported in Excel 2013.

- i. *The standard defines the attribute `table:name`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "filter", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the property "none", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the property "print-range", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the property "repeat-column", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the property "repeat-row", contained within the attribute `table:range-usable-as`, contained within the element `<table:named-range>`, contained within the parent element `<table:named-expressions>`*

This property is not supported in Excel 2010 or Excel 2013.

2.1.234 Section 8.6, Database Ranges

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element `<table:database-ranges>`, contained within the parent element `<office:spreadsheet>`*

This element is supported in Excel 2010 and Excel 2013.

2.1.235 Section 8.6.1, Database Range

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <table:database-range>, contained within the parent element <table:database-ranges>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute table:contains-header, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the attribute table:display-filter-buttons, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute table:has-persistent-data, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the attribute table:is-selection, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute table:name, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute table:on-update-keep-size, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "false", contained within the attribute table:on-update-keep-size, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is supported in Excel 2010 and Excel 2013.

This value maps to "Insert/Delete" on refresh.

- j. *The standard defines the property "true", contained within the attribute table:on-update-keep-size, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is supported in Excel 2010 and Excel 2013.

This value maps to "Overwrite/Clear" on refresh.

- k. *The standard defines the attribute table:on-update-keep-styles, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the attribute table:orientation, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the property "column", contained within the attribute table:orientation, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the property "row", contained within the attribute table:orientation, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is supported in Excel 2010 and Excel 2013.

The only orientation that Excel supports is row. Therefore, this is an optional attribute, and Excel neither reads nor writes it.

- o. *The standard defines the attribute table:refresh-delay, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

The attribute table-refresh-delay is a boolean type, while the corresponding setting in Excel is an interval of time.

- p. *The standard defines the property "false", contained within the attribute table:refresh-delay, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is supported in Excel 2010 and Excel 2013.

This value maps to the feature being off.

- q. *The standard defines the property "true", contained within the attribute table:refresh-delay, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This property is supported in Excel 2010 and Excel 2013.

On load, this value maps to the default interval. On save, if the interval is nonzero, Excel writes 'true'.

- r. *The standard defines the attribute table:target-range-address, contained within the element <table:database-range>, contained within the parent element <table:database-ranges>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.236 Section 8.6.2, Database Source SQL

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <table:database-source-sql>, contained within the parent element <table:database-range>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute table:database-name, contained within the element <table:database-source-sql>, contained within the parent element <table:database-range>*

This attribute is supported in Excel 2010 and Excel 2013.

Excel stores the connection string in the name attribute because it is the unique identifier.

- d. *The standard defines the attribute `table:parse-sql-statement`, contained within the element `<table:database-source-sql>`, contained within the parent element `<table:database-range>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `table:sql-statement`, contained within the element `<table:database-source-sql>`, contained within the parent element `<table:database-range>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.237 Section 8.6.3, Database Source Table

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<table:database-source-table>`, contained within the parent element `<table:database-range>`*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `table:database-name`, contained within the element `<table:database-source-table>`, contained within the parent element `<table:database-range>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel stores the connection string in the name attribute because it is the unique identifier.

- d. *The standard defines the attribute `table:database-table-name`, contained within the element `<table:database-source-table>`, contained within the parent element `<table:database-range>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.238 Section 8.6.4, Database Source Query

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<table:database-source-query>`, contained within the parent element `<table:database-range>`*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `table:database-name`, contained within the element `<table:database-source-query>`, contained within the parent element `<table:database-range>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel stores the connection string in the name attribute because it is the unique identifier.

- d. *The standard defines the attribute `table:query-name`, contained within the element `<table:database-source-query>`, contained within the parent element `<table:database-range>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.239 Section 8.6.5, Sort

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:algorithm`, contained within the element `<table:sort>`, contained within the parent element `<table:database-range>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `table:bind-styles-to-content`, contained within the element `<table:sort>`, contained within the parent element `<table:database-range>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:case-sensitive`, contained within the element `<table:sort>`, contained within the parent element `<table:database-range>`*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute `table:country`, contained within the element `<table:sort>`, contained within the parent element `<table:database-range>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `table:language`, contained within the element `<table:sort>`, contained within the parent element `<table:database-range>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `table:target-range-address`, contained within the element `<table:sort>`, contained within the parent element `<table:database-range>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.240 Section 8.6.6, Sort By

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:data-type`, contained within the element `<table:sort-by>`, contained within the parent element `<table:sort>`*

This attribute is supported in Excel 2010 and Excel 2013.

1. For custom list sorts, Excel writes out the entire custom list.
 2. Excel does not save color and icon sorts.
 3. Excel does not write out the text or numeric types. It loads both as automatic.
- c. *The standard defines the attribute `table:field-number`, contained within the element `<table:sort-by>`, contained within the parent element `<table:sort>`*

This attribute is supported in Excel 2010 and Excel 2013.

On save, Excel writes out a zero-based field number.

- d. *The standard defines the attribute `table:order`, contained within the element `<table:sort-by>`, contained within the parent element `<table:sort>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.241 Section 8.6.7, Subtotal Rules

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:bind-styles-to-content`, contained within the element `<table:subtotal-rules>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:case-sensitive`, contained within the element `<table:subtotal-rules>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:page-breaks-on-group-change`, contained within the element `<table:subtotal-rules>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.242 Section 8.6.8, Subtotal Sort Groups

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:data-type`, contained within the element `<table:sort-groups>`, contained within the parent element `<table:subtotal-rules>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:order`, contained within the element `<table:sort-groups>`, contained within the parent element `<table:subtotal-rules>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.243 Section 8.6.9, Subtotal Rule

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:group-by-field-number`, contained within the element `<table:subtotal-rule>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.244 Section 8.6.10, Subtotal Field

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:field-number`, contained within the element `<table:subtotal-field>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:function`, contained within the element `<table:subtotal-field>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.245 Section 8.7, Filters

- a. This is not supported in Word 2010 or Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

1. If the filter is applied to a query table, Excel will lose the filter if the query table is refreshed.
2. Only top/bottom filters are supported if the filter is on a pivot table with external data.
3. If any of the filters specified on a range or data pilot isn't fully supported, Excel will not load the filter for that range or data pilot.
4. These are some of the cases that cause a filter to be dropped on load, this is not a comprehensive list:

OR statements nested within an AND statement.

The top 10 filters within an OR statement (the top 10 filters are the only things that can be applied to a column).

If the number of filters for a particular column > 2 and all signs are not a series of "OR equals X", that is, not a "list of possible values" scenario.

If one column has more than one filter criteria within a single OR statement.

If a single column has criteria in multiple AND statements and at least one of them is a Top 10 filter.

If a single column has >2 criteria and an AND statement.

If a column has a top 10 filter and the column type is text instead of numerical data.

2.1.246 Section 8.7.1, Table Filter

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute `table:condition-source`, contained within the element `<table:filter>`*

This attribute is not supported in Excel 2010 or Excel 2013.

Excel assumes the default filter, "condition-source: self".

- c. *The standard defines the attribute `table:condition-source-range-address`, contained within the element `<table:filter>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:display-duplicates`, contained within the element `<table:filter>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `table:target-range-address`, contained within the element `<table:filter>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.247 Section 8.7.2, Filter And

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element `<table:filter-and>`, contained within the parent element `<table:filter>`*

This element is supported in Excel 2010 and Excel 2013.

Some combinations of the elements `<filter-and>` and `<filter-or>` are not supported.

2.1.248 Section 8.7.3, Filter Or

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element `<table:filter-or>`, contained within the parent element `<table:filter>`*

This element is supported in Excel 2010 and Excel 2013.

Some combinations of the elements <filter-and> and <filter-or> are not supported.

2.1.249 Section 8.7.4, Filter Condition

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute table:case-sensitive, contained within the element <table:filter-condition>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute table:data-type, contained within the element <table:filter-condition>*

This attribute is supported in Excel 2010 and Excel 2013.

Color, icon, and some dynamic filters are not saved.

- d. *The standard defines the attribute table:field-number, contained within the element <table:filter-condition>*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute table:operator, contained within the element <table:filter-condition>*

This attribute is supported in Excel 2010 and Excel 2013.

Some operators are not supported for Pivot Table Filters, for example, "bottom values" and "top values".

- f. *The standard defines the attribute table:value, contained within the element <table:filter-condition>*

This attribute is supported in Excel 2010 and Excel 2013.

However, some regular expressions are not supported. Also, some values are not supported for AF, such as filtering with "Date = 36527" instead of "1/2/2000". The attribute table:value is supported in Calc 3. However, only "." and ".*" are supported for Regular Expressions, all other expressions are dropped. On save, non-wildcard filters, such as "Contains", are transformed into corresponding regular expressions.

2.1.250 Section 8.8, Data Pilot Tables

- a. *The standard defines the element <table:data-pilot-tables>, contained within the parent element <office:spreadsheet>*

This element is supported in Excel 2010 and Excel 2013.

2.1.251 Section 8.8.1, Data Pilot Table

- a. *The standard defines the element <table:database-source-query>, contained within the parent element <table:data-pilot-table>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the element <table:database-source-sql>, contained within the parent element <table:data-pilot-table>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the element <table:database-source-table>, contained within the parent element <table:data-pilot-table>*

This element is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This element is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute table:application-data, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute table:buttons, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This attribute is supported in Excel 2010 and Excel 2013.

The ODF specification does not specify DataPilot layout details.

On load, Excel uses button location information to help determine how to render the DataPilot, including page field locations, row and column headings, and data area.

On save, Excel writes button locations, based on how the DataPilot is positioned in Excel, so that other implementers can provide interactive buttons, if desired.

- g. *The standard defines the attribute table:drill-down-on-double-click, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This attribute is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute table:grand-total, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "both", contained within the attribute table:grand-total, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This property is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "column", contained within the attribute table:grand-total, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This property is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the property "none", contained within the attribute table:grand-total, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This property is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the property "row", contained within the attribute table:grand-total, contained within the element <table:data-pilot-table>, contained within the parent element <table:data-pilot-tables>*

This property is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the attribute `table:identify-categories`, contained within the element `<table:data-pilot-table>`, contained within the parent element `<table:data-pilot-tables>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute `table:ignore-empty-rows`, contained within the element `<table:data-pilot-table>`, contained within the parent element `<table:data-pilot-tables>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the attribute `table:name`, contained within the element `<table:data-pilot-table>`, contained within the parent element `<table:data-pilot-tables>`*

This attribute is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the attribute `table:show-filter-button`, contained within the element `<table:data-pilot-table>`, contained within the parent element `<table:data-pilot-tables>`*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel uses the value of the attribute `table:show-filter-button` to help determine the layout of the DataPilot.

Excel does not support toggling the DataPilot buttons “on” and “off”.

On save, Excel always writes the attribute `table:show-filter-button` as “false”.

- q. *The standard defines the attribute `table:target-range-address`, contained within the element `<table:data-pilot-table>`, contained within the parent element `<table:data-pilot-tables>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.252 Section 8.8.2, Source Cell Range

- a. *The standard defines the element `<table:source-cell-range>`, contained within the parent element `<table:data-pilot-table>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:cell-range-address`, contained within the element `<table:source-cell-range>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.253 Section 8.8.3, Source Service

- a. *The standard defines the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This element is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the attribute `table:name`, contained within the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:object-name`, contained within the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:password`, contained within the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `table:source-name`, contained within the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `table:user-name`, contained within the element `<table:source-service>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.254 Section 8.8.4, Data Pilot Field

- a. *The standard defines the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:function`, contained within the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the property "`<any string>`", contained within the attribute `table:function`, contained within the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This property is not supported in Excel 2010 or Excel 2013.

On load, string values that don't match the explicitly listed enumerated values are converted to "auto".

- d. *The standard defines the property "auto", contained within the attribute `table:function`, contained within the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This property is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "average", contained within the attribute `table:function`, contained within the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "count", contained within the attribute `table:function`, contained within the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This property is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the property "countnums", contained within the attribute `table:function`, contained within the element `<table:data-pilot-field>`, contained within the parent element `<table:data-pilot-table>`*

This property is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the property "max", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "min", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "product", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the property "stdev", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the property "stdevp", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the property "sum", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the property "var", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the property "varp", contained within the attribute table:function, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the attribute table:is-data-layout-field, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This attribute is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the attribute table:orientation, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This attribute is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the property "column", contained within the attribute table:orientation, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the property "data", contained within the attribute table:orientation, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the property "hidden", contained within the attribute table:orientation, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

On save, for a range-based data source, Excel does not write fields that are not displayed on the "DataPilot". For external data sources, Excel writes out all fields, and marks those not in the "DataPilot" view as hidden.

- u. *The standard defines the property "page", contained within the attribute table:orientation, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- v. *The standard defines the property "row", contained within the attribute table:orientation, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This property is supported in Excel 2010 and Excel 2013.

- w. *The standard defines the attribute table:selected-page, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This attribute is supported in Excel 2010 and Excel 2013.

On save, if Excel writes an empty value for this attribute, it means that 'blank' is chosen for the filter value. This corresponds to an empty string in the data source. If Excel doesn't write this attribute at all, it means the user has not selected a value for the manual filter.

- x. *The standard defines the attribute table:source-field-name, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This attribute is supported in Excel 2010 and Excel 2013.

- y. *The standard defines the attribute table:used-hierarchy, contained within the element <table:data-pilot-field>, contained within the parent element <table:data-pilot-table>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.255 Section 8.8.5, Data Pilot Level

- a. *The standard defines the element <table:data-pilot-level>, contained within the parent element <table:data-pilot-field>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute table:show-empty, contained within the element <table:data-pilot-level>, contained within the parent element <table:data-pilot-field>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.256 Section 8.8.6, Data Pilot Subtotals

- a. *The standard defines the element <table:data-pilot-subtotals>, contained within the parent element <table:data-pilot-level>*

This element is supported in Excel 2010 and Excel 2013.

2.1.257 Section 8.8.7, Data Pilot Subtotal

- a. *The standard defines the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the property "<any string>", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is not supported in Excel 2010 or Excel 2013.

On load, string values that don't match the explicitly listed enumerated values are converted to "auto".

- d. *The standard defines the property "auto", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "average", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "count", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the property "countnums", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the property "max", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "min", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "product", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the property "stdev", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the property "stdevp", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the property "sum", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the property "var", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the property "varp", contained within the attribute table:function, contained within the element <table:data-pilot-subtotal>, contained within the parent element <table:data-pilot-subtotals>*

This property is supported in Excel 2010 and Excel 2013.

2.1.258 Section 8.8.8, Data Pilot Members

- a. *The standard defines the element <table:data-pilot-members>, contained within the parent element <table:data-pilot-level>*

This element is supported in Excel 2010 and Excel 2013.

2.1.259 Section 8.8.9, Data Pilot Member

- a. *The standard defines the element <table:data-pilot-member>, contained within the parent element <table:data-pilot-members>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute table:display, contained within the element <table:data-pilot-member>, contained within the parent element <table:data-pilot-members>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute table:name, contained within the element <table:data-pilot-member>, contained within the parent element <table:data-pilot-members>*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the attribute `table:show-details`, contained within the element `<table:data-pilot-member>`, contained within the parent element `<table:data-pilot-members>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.260 Section 8.8.10, Data Pilot Display Info

- a. *The standard defines the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:data-field`, contained within the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `table:display-member-mode`, contained within the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property "from-bottom", contained within the attribute `table:display-member-mode`, contained within the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "from-top", contained within the attribute `table:display-member-mode`, contained within the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the attribute `table:enabled`, contained within the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, if the attribute `table:enabled` is "false", then Excel ignores the TopN filter information. If the attribute `table:enabled` is "true", then Excel loads and applies the TopN filter.

On save, Excel always writes "true", and only writes this when there's a TopN filter or AutoShow filter.

- g. *The standard defines the attribute `table:member-count`, contained within the element `<table:data-pilot-display-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.261 Section 8.8.11, Data Pilot Sort Info

- a. *The standard defines the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:data-field`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `table:sort-mode`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property "data", contained within the attribute `table:sort-mode`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "manual", contained within the attribute `table:sort-mode`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "name", contained within the attribute `table:sort-mode`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the property "none", contained within the attribute `table:sort-mode`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute `table:sort-order`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "ascending", contained within the attribute `table:sort-order`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "descending", contained within the attribute `table:sort-order`, contained within the element `<table:data-pilot-sort-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

2.1.262 Section 8.8.12, Data Pilot Layout Info

- a. *The standard defines the element `<table:data-pilot-layout-info>`, contained within the parent element `<table:data-pilot-level>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:add-empty-lines`, contained within the element `<table:data-pilot-layout-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `table:layout-mode`, contained within the element `<table:data-pilot-layout-info>`, contained within the parent element `<table:data-pilot-level>`*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property "outline-subtotals-bottom", contained within the attribute `table:layout-mode`, contained within the element `<table:data-pilot-layout-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "outline-subtotals-top", contained within the attribute `table:layout-mode`, contained within the element `<table:data-pilot-layout-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "tabular-layout", contained within the attribute `table:layout-mode`, contained within the element `<table:data-pilot-layout-info>`, contained within the parent element `<table:data-pilot-level>`*

This property is supported in Excel 2010 and Excel 2013.

2.1.263 Section 8.8.13, Data Pilot Field Reference

- a. *The standard defines the element `<table:data-pilot-field-reference>`, contained within the parent element `<table:data-pilot-field>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:field-name`, contained within the element `<table:data-pilot-field-reference>`, contained within the parent element `<table:data-pilot-field>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `table:member-name`, contained within the element `<table:data-pilot-field-reference>`, contained within the parent element `<table:data-pilot-field>`*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the attribute `table:member-type`, contained within the element `<table:data-pilot-field-reference>`, contained within the parent element `<table:data-pilot-field>`*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "named", contained within the attribute `table:member-type`, contained within the element `<table:data-pilot-field-reference>`, contained within the parent element `<table:data-pilot-field>`*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "next", contained within the attribute `table:member-type`, contained within the element `<table:data-pilot-field-reference>`, contained within the parent element `<table:data-pilot-field>`*

This property is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the property "previous", contained within the attribute table:member-type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "column-percentage", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "index", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the property "member-difference", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the property "member-percentage", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the property "member-percentage-difference", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the property "none", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the property "row-percentage", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the property "running-total", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the property "total-percentage", contained within the attribute table:type, contained within the element <table:data-pilot-field-reference>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

2.1.264 Section 8.8.14, Data Pilot Groups

- a. *The standard defines the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute table:date-end, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This attribute is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- c. *The standard defines the property "auto", contained within the attribute table:date-end, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- d. *The standard defines the attribute table:date-start, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This attribute is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- e. *The standard defines the property "auto", contained within the attribute table:date-start, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the `table:end`, `table:step`, and `table:grouped-by` attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- f. *The standard defines the attribute `table:end`, contained within the element `<table:data-pilot-groups>`, contained within the parent element `<table:data-pilot-field>`*

This attribute is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the `table:end`, `table:step`, and `table:grouped-by` attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- g. *The standard defines the property "auto", contained within the attribute `table:end`, contained within the element `<table:data-pilot-groups>`, contained within the parent element `<table:data-pilot-field>`*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the `table:end`, `table:step`, and `table:grouped-by` attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- h. *The standard defines the attribute `table:grouped-by`, contained within the element `<table:data-pilot-groups>`, contained within the parent element `<table:data-pilot-field>`*

This attribute is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the `table:end`, `table:step`, and `table:grouped-by` attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- i. *The standard defines the property "days", contained within the attribute `table:grouped-by`, contained within the element `<table:data-pilot-groups>`, contained within the parent element `<table:data-pilot-field>`*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the attributes `table:end`, `table:step`, and `table:grouped-by` are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the "DataPilot" items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the "DataPilot" items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

Excel supports grouping by days but does not explicitly write grouped-by="days". Instead, Excel only writes the step value and date-start / date-end; therefore "days" is implied.

- j. *The standard defines the property "hours", contained within the attribute table:grouped-by, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- k. *The standard defines the property "minutes", contained within the attribute table:grouped-by, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- l. *The standard defines the property "months", contained within the attribute table:grouped-by, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- m. *The standard defines the property "quarters", contained within the attribute table:grouped-by, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- n. *The standard defines the property "seconds", contained within the attribute table:grouped-by, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- o. *The standard defines the property "years", contained within the attribute table:grouped-by, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- p. *The standard defines the attribute table:source-field-name, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This attribute is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the attribute table:start, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This attribute is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- r. *The standard defines the property "auto", contained within the attribute table:start, contained within the element <table:data-pilot-groups>, contained within the parent element <table:data-pilot-field>*

This property is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the table:end, table:step, and table:grouped-by attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

- s. *The standard defines the attribute `table:step`, contained within the element `<table:data-pilot-groups>`, contained within the parent element `<table:data-pilot-field>`*

This attribute is supported in Excel 2010 and Excel 2013.

The RNG schema language specifies that the `table:end`, `table:step`, and `table:grouped-by` attributes are required. However, the text describing these attributes uses conditional language, such as "if", to specify when these attributes are needed.

Excel does not save these attributes when the DataPilot items are grouped manually, meaning that they are arranged by name. However, Excel saves these attributes when the DataPilot items are grouped automatically based on the "start", "end", "grouped-by", and "step" values.

2.1.265 Section 8.8.15, Data Pilot Group

- a. *The standard defines the element `<table:data-pilot-group>`, contained within the parent element `<table:data-pilot-groups>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:name`, contained within the element `<table:data-pilot-group>`, contained within the parent element `<table:data-pilot-groups>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.266 Section 8.8.16, Data Pilot Group Member

- a. *The standard defines the element `<table:data-pilot-group-member>`, contained within the parent element `<table:data-pilot-group>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `table:name`, contained within the element `<table:data-pilot-group-member>`, contained within the parent element `<table:data-pilot-group>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.267 Section 8.9, Consolidation

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `table:function`, contained within the element `<table:consolidation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `table:link-to-source-data`, contained within the element `<table:consolidation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `table:source-cell-range-addresses`, contained within the element `<table:consolidation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `table:target-cell-address`, contained within the element `<table:consolidation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `table:use-label`, contained within the element `<table:consolidation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.268 Section 8.10, DDE Links

- a. *The standard defines the element `<table:dde-link>`, contained within the parent element `<table:dde-links>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the element `<table:dde-links>`*

This element is supported in Excel 2010 and Excel 2013.

2.1.269 Section 8.11.1, Tracked Changes

- a. *The standard defines the element `<table:tracked-changes>`*

This element is not supported in Excel 2010 or Excel 2013.

2.1.270 Section 9, Graphic Content

- a. This is supported in Word 2010 and Word 2013.
b. This is supported in Excel 2010 and Excel 2013.
c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.271 Section 9.1, Enhanced Page Features for Graphical Applications

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.272 Section 9.1.1, Handout Master

- a. *The standard defines the element `<style:handout-master>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

Handouts are saved with 6 slides per page. However, PowerPoint does not read in the handout master style when loading a file as this property is not persisted.

- b. *The standard defines the attribute `draw:style-name`, contained within the element `<style:handout-master>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

Gradient backgrounds are not supported for handout masters.

- c. *The standard defines the attribute `presentation:presentation-page-layout-name`, contained within the element `<style:handout-master>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the attribute `presentation:use-date-time-name`, contained within the element `<style:handout-master>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the attribute presentation:use-footer-name, contained within the element <style:handout-master>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the attribute presentation:use-header-name, contained within the element <style:handout-master>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- g. *The standard defines the attribute style:page-layout-name, contained within the element <style:handout-master>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.273 Section 9.1.2, Layer Sets

- a. *The standard defines the element <draw:layer-set>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.274 Section 9.1.3, Layer

- a. *The standard defines the element <draw:layer>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is used to identify backgrounds inherited by layouts from masters. If a shape on a master-page is identified as a layout and the shape is on a layer that has a name in the form "<master-page-bg>", then these shapes are inherited from the slide master, and will not appear on the slide. Layers are also used to signify hidden/protected shapes. Beyond these uses, PowerPoint does not support a general concept of layers.

- b. *The standard defines the attribute draw:display, contained within the element <draw:layer>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the attribute draw:name, contained within the element <draw:layer>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute draw:protected, contained within the element <draw:layer>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- e. *The standard defines the attribute svg:desc, contained within the element <draw:layer>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the attribute svg:title, contained within the element <draw:layer>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.275 Section 9.1.4, Drawing Pages

- a. *The standard defines the element <draw:page>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute `draw:master-page-name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the attribute `draw:name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute `draw:nav-order`, contained within the element `<draw:page>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the attribute `draw:style-name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the attribute `ID`, contained within the element `<draw:page>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- g. *The standard defines the attribute `presentation:presentation-page-layout-name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not read this attribute when loading a slide.

- h. *The standard defines the attribute `presentation:use-date-time-name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint reads dates and times declared using this attribute, but writes them out as textboxes with regular text.

- i. *The standard defines the attribute `presentation:use-footer-name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint reads footers declared using this attribute, but writes them out as textboxes with regular text.

- j. *The standard defines the attribute `presentation:use-header-name`, contained within the element `<draw:page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint reads headers declared using this attribute, but writes them out as textboxes with regular text.

2.1.276 Section 9.1.5, Presentation Notes

- a. *The standard defines the element `<presentation:notes>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.277 Section 9.2, Drawing Shapes

- a. This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.278 Section 9.2.1, Rectangle

- a. *The standard defines the element <draw:rect>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

- b. *The standard defines the element <draw:rect>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

- c. *The standard defines the element <draw:rect>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.279 Section 9.2.2, Line

- a. *The standard defines the element <draw:line>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

- b. *The standard defines the element <draw:line>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

- c. *The standard defines the element <draw:line>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.280 Section 9.2.3, Polyline

a. *The standard defines the element <draw:polyline>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:polyline>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:polyline>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.281 Section 9.2.4, Polygon

a. *The standard defines the element <draw:polygon>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:polygon>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:polygon>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.282 Section 9.2.5, Regular Polygon

a. *The standard defines the element <draw:regular-polygon>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:regular-polygon>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:regular-polygon>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.283 Section 9.2.6, Path

a. *The standard defines the element <draw:path>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:path>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:path>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation element>

2.1.284 Section 9.2.7, Circle

a. *The standard defines the element <draw:circle>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:circle>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:circle>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.285 Section 9.2.8, Ellipse

a. *The standard defines the element <draw:ellipse>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:ellipse>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:ellipse>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.286 Section 9.2.9, Connector

- a. *The standard defines the element <draw:connector>*

This element is supported in Word 2010 and Word 2013.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

- b. *The standard defines the attribute draw:end-glue-point, contained within the element <draw:connector>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute draw:end-shape, contained within the element <draw:connector>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute draw:line-skew, contained within the element <draw:connector>*

This attribute is not supported in Word 2010 or Word 2013.

Non-default connector elbow positions revert to default positioning after save from Word.

- e. *The standard defines the attribute draw:start-glue-point, contained within the element <draw:connector>*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute draw:start-shape, contained within the element <draw:connector>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute `draw:type`, contained within the element `<draw:connector>`*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute `svg:x1`, contained within the element `<draw:connector>`*

This attribute is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute `svg:x2`, contained within the element `<draw:connector>`*

This attribute is supported in Word 2010 and Word 2013.

- j. *The standard defines the attribute `svg:y1`, contained within the element `<draw:connector>`*

This attribute is supported in Word 2010 and Word 2013.

- k. *The standard defines the attribute `svg:y2`, contained within the element `<draw:connector>`*

This attribute is supported in Word 2010 and Word 2013.

- l. *The standard defines the element `<draw:connector>`*

This element is supported in Excel 2010 and Excel 2013.

This element is not supported, and will be lost, when located inside a `<text:p>` element in one of the following elements:

- `<draw:text-box>`
- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:custom-shape>`
- `<text:note-body>`
- `<office:annotation>`

- m. *The standard defines the attribute `draw:end-glue-point`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the attribute `draw:end-shape`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the attribute `draw:line-skew`, contained within the element `<draw:connector>`*

This attribute is not supported in Excel 2010 or Excel 2013.

Non-default connector elbow positions revert to default positioning after save from Excel.

- p. *The standard defines the attribute `draw:start-glue-point`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the attribute `draw:start-shape`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the attribute `draw:type`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the attribute `svg:x1`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the attribute `svg:x2`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- u. *The standard defines the attribute `svg:y1`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- v. *The standard defines the attribute `svg:y2`, contained within the element `<draw:connector>`*

This attribute is supported in Excel 2010 and Excel 2013.

- w. *The standard defines the element `<draw:connector>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is not supported, and will be lost, when located inside a `<text:p>` element in one of the following elements:

- `<draw:text-box>`
- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:custom-shape>`
- `<text:note-body>`
- `<office:annotation>`

- x. *The standard defines the attribute `draw:end-glue-point`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- y. *The standard defines the attribute `draw:end-shape`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- z. *The standard defines the attribute `draw:line-skew`, contained within the element `<draw:connector>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

Non-default connector elbow positions revert to default positioning after save from PowerPoint.

aa. *The standard defines the attribute `draw:start-glue-point`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

bb. *The standard defines the attribute `draw:start-shape`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

cc. *The standard defines the attribute `draw:type`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

dd. *The standard defines the attribute `svg:x1`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

ee. *The standard defines the attribute `svg:x2`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

ff. *The standard defines the attribute `svg:y1`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

gg. *The standard defines the attribute `svg:y2`, contained within the element `<draw:connector>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.287 Section 9.2.10, Caption

a. *The standard defines the element `<draw:caption>`*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a `<draw:custom-shape>` element.

This element is not supported and will be lost when located inside a `<text:p>` element in the following elements:

- `<draw:text-box>`
- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:custom-shape>`
- `<text:note-body>`
- `<office:annotation>`

b. *The standard defines the element `<draw:caption>`*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a `<draw:custom-shape>` element.

This element is not supported and will be lost when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:caption>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.288 Section 9.2.11, Measure

a. *The standard defines the element <draw:measure>*

This element is supported in Word 2010 and Word 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

- <text:note-body>
- <office:annotation>

b. *The standard defines the element <draw:measure>*

This element is supported in Excel 2010 and Excel 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported and will be lost when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

c. *The standard defines the element <draw:measure>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is converted on save to a <draw:custom-shape> element.

This element is not supported, and will be lost, when located inside a <text:p> element in one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

2.1.289 Section 9.2.12, Control

a. *The standard defines the element <draw:control>*

This element is not supported in Word 2010 or Word 2013.

b. *The standard defines the element <draw:control>*

This element is not supported in Excel 2010 or Excel 2013.

c. *The standard defines the element <draw:control>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.290 Section 9.2.13, Page Thumbnail

- a. *The standard defines the element <draw:page-thumbnail>, contained within the parent element <draw:handout-master>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint writes out handout masters using this element, but does not read it in when loading a presentation.

- b. *The standard defines the element <draw:page-thumbnail>, contained within the parent element <draw:page>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- c. *The standard defines the element <draw:page-thumbnail>, contained within the parent element <presentation:notes>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.291 Section 9.2.14, Grouping

- a. *The standard defines the element <draw:g>*

This element is supported in Word 2010 and Word 2013.

This element is not supported and will be lost when contained within a <text:p> element that is contained within one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

If a group contains only one object, Word loads only the object, and the grouping is lost.

- b. *The standard defines the attribute `svg:y`, contained within the element <draw:g>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <draw:g>*

This element is supported in Excel 2010 and Excel 2013.

This element is not supported and will be lost when contained within a <text:p> element that is contained within one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

Excel cannot support certain types of objects being grouped together. An OLE object grouped with anything other than another OLE object will cause the group to be split into two groups: one containing the OLE objects and one containing all other objects. If a group contains only one object, Excel loads only the object, and the grouping is lost.

On save, Excel horizontally flips the position of objects in a group located on a right-to-left oriented worksheet.

- d. *The standard defines the attribute `svg:y`, contained within the element `<draw:g>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the element `<draw:g>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is not supported and will be lost when contained within a `<text:p>` element that is contained within one of the following elements:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>
- <office:annotation>

If a group contains only one object, then PowerPoint loads only the object, and loses the grouping.

- f. *The standard defines the attribute `svg:y`, contained within the element `<draw:g>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.292 Section 9.2.15, Common Drawing Shape Attributes

- a. *The standard defines the attribute `draw:caption-id`*

Word 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

b. *The standard defines the attribute draw:class-names*

Word 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

c. *The standard defines the attribute draw:id*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

d. *The standard defines the attribute draw:layer*

Word 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>

- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

e. *The standard defines the attribute draw:name*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

f. *The standard defines the attribute draw:style-name*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

g. *The standard defines the property "matrix(<a> <c> <d> <e> <f>)", contained within the attribute draw:transform*

Word 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>

- <draw:g>
 - <draw:frame>
 - <draw:custom-shape>
- h. *The standard defines the property "rotate(<rotate-angle>)", contained within the attribute draw:transform*

Word 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

Rotation is not supported for a <draw:frame> element that contains a <draw:object-ole> element.

- i. *The standard defines the property "scale(<sx> [<sy>])", contained within the attribute draw:transform*

Word 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- j. *The standard defines the property "skewX(<skew-angle>)", contained within the attribute draw:transform*

Word 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

k. *The standard defines the property "skewY(<skew-angle>)", contained within the attribute draw:transform*

Word 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

l. *The standard defines the property "translate(<tx> [<ty>])", contained within the attribute draw:transform*

Word 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

m. *The standard defines the attribute draw:z-index*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

n. *The standard defines the attribute `svg:height`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

o. *The standard defines the attribute `svg:view-box`*

Word 2013 supports this attribute for the following elements:

- <draw:polyline>
- <draw:polygon>
- <draw:path>

p. *The standard defines the attribute `svg:width`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

q. *The standard defines the attribute `svg:x`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

r. *The standard defines the attribute `svg:y`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

s. *The standard defines the attribute `draw:caption-id`*

Excel 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

t. *The standard defines the attribute `draw:class-names`*

Excel 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

u. *The standard defines the attribute draw:id*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

v. *The standard defines the attribute draw:layer*

Excel 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

w. *The standard defines the attribute draw:name*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

x. *The standard defines the attribute `draw:style-name`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

y. *The standard defines the property "`matrix(<a> <c> <d> <e> <f>)`", contained within the attribute `draw:transform`*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

z. *The standard defines the property "`rotate(<rotate-angle>)`", contained within the attribute `draw:transform`*

Excel 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

Rotation is not supported for a <draw:frame> element that contains a <draw:object-ole> element.

- aa. *The standard defines the property "scale(<sx> [<sy>])", contained within the attribute draw:transform*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- bb. *The standard defines the property "skewX(<skew-angle>)", contained within the attribute draw:transform*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

- cc. *The standard defines the property "skewY(<skew-angle>)", contained within the attribute draw:transform*

Excel 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

dd. *The standard defines the property "translate(<tx> [<ty>])", contained within the attribute draw:transform*

Excel 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

ee. *The standard defines the attribute draw:z-index*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

ff. *The standard defines the attribute svg:height*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

gg. *The standard defines the attribute `svg:view-box`*

Excel 2013 supports this attribute for the following elements:

- draw:polyline
- draw:polygon
- draw:path

hh. *The standard defines the attribute `svg:width`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

ii. *The standard defines the attribute `svg:x`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

jj. *The standard defines the attribute `svg:y`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

kk. *The standard defines the attribute draw:caption-id*

PowerPoint 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

ll. *The standard defines the attribute draw:class-name*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint does not support or preserve this element.

mm. *The standard defines the attribute draw:class-names*

PowerPoint 2013 does not support this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

nn. *The standard defines the attribute draw:id*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

oo. *The standard defines the attribute draw:layer*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

pp. *The standard defines the attribute draw:name*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

qq. *The standard defines the attribute draw:style-name*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>

- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

rr. *The standard defines the property "matrix(<a> <c> <d> <e> <f>)", contained within the attribute draw:transform*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

ss. *The standard defines the property "rotate(<rotate-angle>)", contained within the attribute draw:transform*

PowerPoint 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

Rotation is not supported for a <draw:frame> element that contains a <draw:object-ole> element.

tt. *The standard defines the property "scale(<sx> [<sy>])", contained within the attribute draw:transform*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

uu. *The standard defines the property "skewX(<skew-angle>)", contained within the attribute draw:transform*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

vv. *The standard defines the property "skewY(<skew-angle>)", contained within the attribute draw:transform*

PowerPoint 2013 does not support this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

ww. *The standard defines the property "translate(<tx> [<ty>])", contained within the attribute draw:transform*

PowerPoint 2013 supports this enum for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

xx. *The standard defines the attribute draw:z-index*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

yy. *The standard defines the attribute presentation:class-name*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint does not support or preserve this element.

zz. *The standard defines the attribute presentation:style-name*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint treats draw:style-name and presentation:style-name equivalently. On write, PowerPoint uses presentation style names for placeholder shapes.

aaa. *The standard defines the attribute svg:height*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

bbb. *The standard defines the attribute `svg:view-box`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:polyline>
- <draw:polygon>
- <draw:path>

ccc. *The standard defines the attribute `svg:width`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

ddd. *The standard defines the attribute `svg:x`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

eee. *The standard defines the attribute `svg:y`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

fff. *The standard defines the attribute `svg:z-index`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ggg. *The standard defines the attribute `draw:name`, contained within the element `<draw:object>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

hhh. *The standard defines the attribute `draw:name`, contained within the element `<draw:object-ole>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

2.1.293 Section 9.2.16, Common Shape Attributes for Text and Spreadsheet Documents

a. *The standard defines the attribute `text:anchor-page-number`*

This attribute is not supported in Word 2010 or Word 2013.

On load, objects that are anchored to a specific page number using the `text:anchor-page-number` attribute will appear on the first page.

b. *The standard defines the property `"as-char"`, contained within the attribute `text:anchor-type`*

This property is supported in Word 2010 and Word 2013.

On load and save, Word supports this value for the `text:anchor-type` attribute when a shape is inserted inline with text.

c. *The standard defines the property `"char"`, contained within the attribute `text:anchor-type`*

This property is not supported in Word 2010 or Word 2013.

On load, Word reverts to a default value of "paragraph" for all unsupported values of the `text:anchor-type` attribute.

d. *The standard defines the property `"frame"`, contained within the attribute `text:anchor-type`*

This property is not supported in Word 2010 or Word 2013.

On load, Word reverts to a default value of "paragraph" for all unsupported values of the `text:anchor-type` attribute.

e. *The standard defines the property `"page"`, contained within the attribute `text:anchor-type`*

This property is not supported in Word 2010 or Word 2013.

On load, Word reverts to a default value of "paragraph" for all unsupported values of the text:anchor-type attribute.

- f. *The standard defines the property "paragraph", contained within the attribute text:anchor-type*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the element <table:end-cell-address>*

This element is not supported in Word 2010 or Word 2013.

- h. *The standard defines the element <table:end-x>*

This element is not supported in Word 2010 or Word 2013.

- i. *The standard defines the element <table:end-y>*

This element is not supported in Word 2010 or Word 2013.

- j. *The standard defines the element <table:table-background>*

This element is not supported in Word 2010 or Word 2013.

2.1.294 Section 9.2.17, Common Drawing Shape Content

- a. Word supports text on shapes.

This is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <text:list>, contained within the parent element <draw-text>*

This element is supported in Word 2010 and Word 2013.

- c. This is supported in Excel 2010 and Excel 2013.

- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.295 Section 9.2.18, Common Shape Attribute Groups

- a. This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.296 Section 9.2.19, Glue Points

- a. *The standard defines the element <draw:glue-point>*

Word 2013 does not support this element for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:custom-shape>

b. *The standard defines the element <draw:glue-point>*

Excel 2013 does not support this element for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:custom-shape>

c. *The standard defines the element <draw:glue-point>*

PowerPoint 2013 does not support this element for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:custom-shape>

2.1.297 Section 9.2.20, Title and Description

a. *The standard defines the attribute svg:desc*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>

- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

b. *The standard defines the attribute `svg:title`*

Word 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

c. *The standard defines the attribute `svg:desc`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

d. *The standard defines the attribute `svg:title`*

Excel 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>

- <draw:frame>
- <draw:custom-shape>

e. *The standard defines the attribute `svg:desc`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

f. *The standard defines the attribute `svg:title`*

PowerPoint 2013 supports this attribute for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

2.1.298 Section 9.2.21, Event Listeners

a. Word 2013 does not support this for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:text-box>
- <draw:image>

- <draw:custom-shape>
- b. Excel 2013 does not support this for the following elements:
- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:text-box>
 - <draw:image>
 - <draw:custom-shape>
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.299 Section 9.3, Frames

- a. *The standard defines the element <draw:frame>*

This element is supported in Word 2010 and Word 2013.

Word frames become textboxes after save.

This element is supported in Word 2010 and Word 2013.

This element is not supported and will be lost when located inside a <text:p> element in an <office:annotation> element.

- b. *The standard defines the attribute draw:copy-of, contained within the element <draw:frame>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute style:rel-height, contained within the element <draw:frame>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute style:rel-width, contained within the element <draw:frame>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <draw:frame>*

This element is supported in Excel 2010 and Excel 2013.

This element is not supported, and will be lost, when contained within a <text:p>, when that <text:p> is within an <office:annotation>.

- f. *The standard defines the element <draw:frame>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

This element is not supported when located inside a <text:p> element in an <office:annotation> element, and will be lost.

2.1.300 Section 9.3.1, Text Box

- a. *The standard defines the element <draw:text-box>*

This element is supported in Word 2010 and Word 2013.

A <draw:text-box> element located inside a <draw:frame> element in a <text:p> element in the following elements is not supported and will be lost:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>

- b. *The standard defines the attribute draw:chain-next-name, contained within the element <draw:text-box>*

This attribute is supported in Word 2010 and Word 2013.

Text linking between text boxes in headers or footers are lost on load.

- c. *The standard defines the attribute draw:corner-radius, contained within the element <draw:text-box>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute fo:max-height, contained within the element <draw:text-box>*

This attribute is supported in Word 2010 and Word 2013.

Word supports length but not percent for this attribute.

Word supports the fo:max-height attribute when the value is less than the value of the svg:height attribute on the text box's <draw:frame> parent element. For this case, Word uses the value specified in the fo:max-height attribute as the text box's height instead of the svg:height attribute and writes this value to the svg:height attribute on save.

- e. *The standard defines the attribute fo:max-width, contained within the element <draw:text-box>*

This attribute is supported in Word 2010 and Word 2013.

Word supports length but not percent for this attribute.

Word supports the fo:max-width attribute when the value is less than the value of the svg:width attribute on the text box's <draw:frame> parent element. For this case, Word uses the value specified in the fo:max-width attribute as the text box's width instead of the svg:width attribute, and Word writes this value to the svg:width attribute on save.

- f. *The standard defines the attribute fo:min-height, contained within the element <draw:text-box>*

This attribute is supported in Word 2010 and Word 2013.

Word supports length but not percent for this attribute.

This attribute is used when the `svg:height` attribute on the text box's `<draw:frame>` parent element is missing. Otherwise, this attribute is ignored.

- g. *The standard defines the attribute `fo:min-width`, contained within the element `<draw:text-box>`*

This attribute is supported in Word 2010 and Word 2013.

Word supports length but not percent for this attribute.

Word uses the `fo:min-width` attribute when the `svg:width` attribute on the text box's `<draw:frame>` parent element is missing. Otherwise, Word ignores this attribute.

- h. *The standard defines the attribute `text:id`, contained within the element `<draw:text-box>`*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the element `<draw:text-box>`*

This element is supported in Excel 2010 and Excel 2013.

A `<draw:text-box>` element located inside a `<draw:frame>` element in a `<text:p>` element in the following elements is not supported and will be lost:

- `<draw:text-box>`
- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:custom-shape>`
- `<text:note-body>`

- j. *The standard defines the attribute `draw:chain-next-name`, contained within the element `<draw:text-box>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute `draw:corner-radius`, contained within the element `<draw:text-box>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute `fo:max-height`, contained within the element `<draw:text-box>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel supports length but not percent for this attribute.

Excel supports the `fo:max-height` attribute when the value is less than the value for the `svg:height` attribute on the text box's `<draw:frame>` parent element. For this case, Excel uses the value specified in the `fo:max-height` attribute as the text box's height instead of the `svg:height` attribute and writes this value to the `svg:height` attribute on save.

- m. *The standard defines the attribute `fo:max-width`, contained within the element `<draw:text-box>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel supports length, but not percent for this attribute.

Excel supports the fo:max-width attribute when the value is less than the value for the svg:width attribute on the text box's <draw:frame> parent element. For this case, Excel uses the value specified in the fo:max-width attribute as the text box's width instead of the svg:width attribute and writes this value to the svg:width attribute on save.

- n. *The standard defines the attribute fo:min-height, contained within the element <draw:text-box>*

This attribute is supported in Excel 2010 and Excel 2013.

Excel supports length but not percent for this attribute.

Excel uses the fo:min-height attribute when the svg:height attribute on the text box's <draw:frame> parent element is missing. Otherwise, Excel ignores this attribute.

- o. *The standard defines the attribute fo:min-width, contained within the element <draw:text-box>*

This attribute is supported in Excel 2010 and Excel 2013.

Excel supports length, but not percent for this attribute.

Excel uses the fo:min-width attribute when the svg:width attribute on the text box's <draw:frame> parent element is missing. Otherwise, Excel ignores this attribute.

- p. *The standard defines the element <draw:text-box>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

A <draw:text-box> element located inside a <draw:frame> element in a <text:p> element in the following elements is not supported and will be lost:

- <draw:text-box>
- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>
- <text:note-body>

- q. *The standard defines the attribute draw:chain-next-name, contained within the element <draw:text-box>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute draw:corner-radius, contained within the element <draw:text-box>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the attribute fo:max-height, contained within the element <draw:text-box>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports length but not percent for this attribute.

PowerPoint supports the fo:max-height attribute when the value is less than the value for the svg:height attribute on the text box's <draw:frame> parent element. For this case, PowerPoint

uses the value specified in the fo:max-height attribute as the text box's height instead of the svg:height attribute and writes this value to the svg:height attribute on save.

- t. *The standard defines the attribute fo:max-width, contained within the element <draw:text-box>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports length but not percent for this attribute.

PowerPoint supports the fo:max-width attribute when the value is less than the value for the svg:width attribute on the text box's <draw:frame> parent element. For this case, PowerPoint uses the value specified in the fo:max-width attribute as the text box's width instead of the svg:width attribute and writes this value to the svg:width attribute on save.

- u. *The standard defines the attribute fo:min-height, contained within the element <draw:text-box>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports length but not percent for this attribute.

PowerPoint uses the fo:min-height attribute when the svg:height attribute on the text box's <draw:frame> parent element is missing. Otherwise, PowerPoint ignores this attribute.

- v. *The standard defines the attribute fo:min-width, contained within the element <draw:text-box>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports length, but not percent for this attribute.

PowerPoint uses the fo:min-width attribute when the svg:width attribute on the text box's <draw:frame> parent element is missing. Otherwise, PowerPoint ignores this attribute.

2.1.301 Section 9.3.2, Image

- a. *The standard defines the element <draw:image>*

This element is supported in Word 2010 and Word 2013.

Text on an image is not supported and on load, Word drops the text.

- b. *The standard defines the attribute draw:filter-name, contained within the element <draw:image>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute xlink:actuate, contained within the element <draw:image>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute xlink:href, contained within the element <draw:image>*

This attribute is supported in Word 2010 and Word 2013.

Relative URIs are not supported, only absolute URIs are supported.

- e. *The standard defines the attribute xlink:show, contained within the element <draw:image>*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute xlink:type, contained within the element <draw:image>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the element <office:binary-data>*
This element is not supported in Word 2010 or Word 2013.
- h. *The standard defines the element <draw:image>*
This element is supported in Excel 2010 and Excel 2013.
Text on an image is not supported and on load, Excel drops the text.
- i. *The standard defines the attribute draw:filter-name, contained within the element <draw:image>*
This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute xlink:actuate, contained within the element <draw:image>*
This attribute is supported in Excel 2010 and Excel 2013.
- k. *The standard defines the attribute xlink:href, contained within the element <draw:image>*
This attribute is supported in Excel 2010 and Excel 2013.
Relative URIs are not supported, only absolute URIs are supported.
- l. *The standard defines the attribute xlink:show, contained within the element <draw:image>*
This attribute is supported in Excel 2010 and Excel 2013.
- m. *The standard defines the attribute xlink:type, contained within the element <draw:image>*
This attribute is supported in Excel 2010 and Excel 2013.
- n. *The standard defines the element <office:binary-data>*
This element is not supported in Excel 2010 or Excel 2013.
- o. *The standard defines the element <draw:image>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
Text on an image is not supported and on load, PowerPoint drops the text.
- p. *The standard defines the attribute draw:filter-name, contained within the element <draw:image>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- q. *The standard defines the attribute xlink:actuate, contained within the element <draw:image>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- r. *The standard defines the attribute xlink:href, contained within the element <draw:image>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
Relative URIs are not supported, only absolute URIs are supported.
- s. *The standard defines the attribute xlink:show, contained within the element <draw:image>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- t. *The standard defines the attribute xlink:type, contained within the element <draw:image>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- u. *The standard defines the element <office:binary-data>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.302 Section 9.3.3, Objects

- a. *The standard defines the element <draw:object>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute xlink:actuate, contained within the element <draw:object>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute xlink:href, contained within the element <draw:object>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute xlink:show, contained within the element <draw:object>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute xlink:type, contained within the element <draw:object>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <draw:object-ole>*

This element is supported in Word 2010 and Word 2013.

- g. *The standard defines the element <math:math>, contained within the parent element <draw:object>*

This element is supported in Word 2010 and Word 2013.

- h. *The standard defines the element <office:binary-data>, contained within the parent element <draw:object-ole>*

This element is not supported in Word 2010 or Word 2013.

- i. *The standard defines the element <draw:object>*

This element is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute draw:notify-on-update-of-ranges, contained within the element <draw:object>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute xlink:actuate, contained within the element <draw:object>*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the attribute xlink:href, contained within the element <draw:object>*

This attribute is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the attribute xlink:show, contained within the element <draw:object>*

This attribute is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the attribute xlink:type, contained within the element <draw:object>*

This attribute is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the element <draw:object-ole>*

This element is supported in Excel 2010 and Excel 2013.

1. Excel does not write a fill on OLE objects, so the background of a OLE object will appear transparent.
2. Excel only supports absolute paths for OLE links.

- p. *The standard defines the attribute draw:class-id, contained within the element <draw:object-ole>*

This attribute is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the attribute office:binary-data, contained within the element <draw:object-ole>*

This attribute is not supported in Excel 2010 or Excel 2013.

- r. *The standard defines the attribute xlink:actuate, contained within the element <draw:object-ole>*

This attribute is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the attribute xlink:href, contained within the element <draw:object-ole>*

This attribute is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the attribute xlink:show, contained within the element <draw:object-ole>*

This attribute is supported in Excel 2010 and Excel 2013.

- u. *The standard defines the attribute xlink:type, contained within the element <draw:object-ole>*

This attribute is supported in Excel 2010 and Excel 2013.

- v. *The standard defines the element <math:math>, contained within the parent element <draw:object>*

This element is not supported in Excel 2010 or Excel 2013.

- w. *The standard defines the element <office:document>, contained within the parent element <draw:object>*

This element is not supported in Excel 2010 or Excel 2013.

- x. *The standard defines the element <draw:object>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- y. *The standard defines the attribute draw:class-id, contained within the element <draw:object>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- z. *The standard defines the attribute draw:name, contained within the element <draw:object>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

- aa. *The standard defines the attribute draw:notify-on-change-of-table, contained within the element <draw:object>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

bb. *The standard defines the attribute `xlink:href`, contained within the element `<draw:object>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

cc. *The standard defines the element `<draw:object-ole>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not read in OLE object names; it sets default values for these attributes on load.

dd. *The standard defines the attribute `draw:class-id`, contained within the element `<draw:object-ole>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

ee. *The standard defines the attribute `draw:notify-on-change-of-table`, contained within the element `<draw:object-ole>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ff. *The standard defines the attribute `xlink:href`, contained within the element `<draw:object-ole>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.303 Section 9.3.4, Applet

a. *The standard defines the element `<draw:applet>`*

This element is not supported in Word 2010 or Word 2013.

b. *The standard defines the element `<draw:applet>`, contained within the parent element `<draw-applet>`*

This element is not supported in Excel 2010 or Excel 2013.

c. *The standard defines the element `<draw:applet>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.304 Section 9.3.5, Plugins

a. *The standard defines the element `<draw:plugin>`*

This element is not supported in Word 2010 or Word 2013.

b. *The standard defines the element `<draw:plugin>`, contained within the parent element `<draw-plugin>`*

This element is not supported in Excel 2010 or Excel 2013.

c. *The standard defines the element `<draw:plugin>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

Plug-ins are used to load and save movies and sounds. PowerPoint accepts links to hrefs in the document package.

PowerPoint saves the mime-type of the media as one of the parameters, but ignores it on load.

PowerPoint will not be able to play any plug-ins that cannot be played back using the media pipeline in PowerPoint.

2.1.305 Section 9.3.6, Parameters

- a. *The standard defines the element <draw:param>, contained within the parent element <draw:applet>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <draw:param>, contained within the parent element <draw:plugin>*
This element is not supported in Word 2010 or Word 2013.
- c. *The standard defines the element <draw:param>, contained within the parent element <draw-param>*
This element is not supported in Excel 2010 or Excel 2013.
- d. *The standard defines the element <draw:param>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.306 Section 9.3.7, Floating Frame

- a. *The standard defines the element <draw:floating-frame>*
This element is not supported in Word 2010 or Word 2013.
On load, Word ignores the <draw:floating-frame> element and reads the contents of the floating frame as paragraph contents.
- b. *The standard defines the element <draw:floating-frame>, contained within the parent element <draw-floating-frame>*
This element is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <draw:floating-frame>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.307 Section 9.3.8, Contour

- a. *The standard defines the element <draw:contour>, contained within the parent element <draw:applet>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <draw:contour>, contained within the parent element <draw:floating frame>*
This element is not supported in Word 2010 or Word 2013.
- c. *The standard defines the element <draw:contour>, contained within the parent element <draw:image>*
This element is not supported in Word 2010 or Word 2013.
- d. *The standard defines the element <draw:contour>, contained within the parent element <draw:object>*
This element is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <draw:contour>, contained within the parent element <draw:object-ole>*

This element is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <draw:contour>, contained within the parent element <draw:plugin>*

This element is not supported in Word 2010 or Word 2013.

- g. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:applet>*

This element is not supported in Word 2010 or Word 2013.

- h. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:floating frame>*

This element is not supported in Word 2010 or Word 2013.

- i. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:image>*

This element is not supported in Word 2010 or Word 2013.

- j. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:object>*

This element is not supported in Word 2010 or Word 2013.

- k. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:object-ole>*

This element is not supported in Word 2010 or Word 2013.

- l. *The standard defines the element <draw:contour-path>, contained within the parent element <draw:plugin>*

This element is not supported in Word 2010 or Word 2013.

2.1.308 Section 9.3.9, Hyperlinks

- a. *The standard defines the element <draw:a>*

This element is not supported in Word 2010 or Word 2013.

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <draw:a>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <draw:a>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the element <draw:frame>, contained within the parent element <draw:a>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint creates hyperlinks on shapes using the event-listener mechanism. PowerPoint does not load frames in hyperlinks.

2.1.309 Section 9.3.10, Client Side Image Maps

- a. *The standard defines the element <draw:image-map>*
This element is not supported in Word 2010 or Word 2013.
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <draw:image-map>*
This element is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <draw:image-map>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.310 Section 9.4, 3D Shapes

- a. This is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.311 Section 9.4.1, Scene

- a. *The standard defines the element <dr3d:scene>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <dr3d:scene>*
This element is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <dr3d:scene>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.312 Section 9.4.2, Light

- a. *The standard defines the element <dr3d:light>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <dr3d:light>*
This element is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the element <dr3d:light>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.313 Section 9.4.3, Cube

- a. *The standard defines the element <dr3d:cube>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <dr3d:cube>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <dr3d:cube>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.314 Section 9.4.4, Sphere

- a. *The standard defines the element <dr3d:sphere>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <dr3d:sphere>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <dr3d:sphere>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.315 Section 9.4.5, Extrude

- a. *The standard defines the element <dr3d:extrude>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <dr3d:extrude>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <dr3d:extrude>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.316 Section 9.4.6, Rotate

- a. *The standard defines the element <dr3d:rotate>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <dr3d:rotate>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <dr3d:rotate>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.317 Section 9.5, Custom Shape

- a. *The standard defines the element <draw:custom-shape>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute draw:data, contained within the element <draw:custom-shape>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `draw:engine`, contained within the element `<draw:custom-shape>`*
This attribute is not supported in Word 2010 or Word 2013.
- d. *The standard defines the element `<draw:custom-shape>`*
This element is supported in Excel 2010 and Excel 2013.
- e. *The standard defines the attribute `draw:data`, contained within the element `<draw:custom-shape>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- f. *The standard defines the attribute `draw:engine`, contained within the element `<draw:custom-shape>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- g. *The standard defines the element `<draw:custom-shape>`*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- h. *The standard defines the attribute `draw:data`, contained within the element `<draw:custom-shape>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- i. *The standard defines the attribute `draw:engine`, contained within the element `<draw:custom-shape>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.318 Section 9.5.1, Enhanced Geometry

- a. *The standard defines the element `<draw:enhanced-geometry>`*
This element is supported in Word 2010 and Word 2013.
- b. *The standard defines the attribute `draw:concentric-gradient-fill-allowed`, contained within the element `<draw:enhanced-geometry>`*
This attribute is not supported in Word 2010 or Word 2013.
- c. *The standard defines the attribute `draw:extrusion-allowed`, contained within the element `<draw:enhanced-geometry>`*
This attribute is not supported in Word 2010 or Word 2013.
- d. *The standard defines the attribute `draw:mirror-horizontal`, contained within the element `<draw:enhanced-geometry>`*
This attribute is supported in Word 2010 and Word 2013.
- e. *The standard defines the attribute `draw:mirror-vertical`, contained within the element `<draw:enhanced-geometry>`*
This attribute is supported in Word 2010 and Word 2013.
- f. *The standard defines the attribute `draw:text-path-allowed`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute `draw:text-rotate-angle`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute `draw:type`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

The enumeration "non-primitive" is supported. Any other value for the `draw:type` attribute is ignored.

- i. *The standard defines the attribute `svg:view-box`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

- j. *The standard defines the element `<draw:enhanced-geometry>`*

This element is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the attribute `draw:concentric-gradient-fill-allowed`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute `draw:extrusion-allowed`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute `draw:mirror-horizontal`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the attribute `draw:mirror-vertical`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the attribute `draw:text-path-allowed`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- p. *The standard defines the attribute `draw:text-rotate-angle`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the attribute `draw:type`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

The enumeration "non-primitive" is supported. Any other value for the `draw:type` attribute is ignored.

- r. *The standard defines the attribute `svg:view-box`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the element `<draw:enhanced-geometry>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- t. *The standard defines the attribute `draw:concentric-gradient-fill-allowed`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- u. *The standard defines the attribute `draw:extrusion-allowed`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- v. *The standard defines the attribute `draw:mirror-horizontal`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- w. *The standard defines the attribute `draw:mirror-vertical`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- x. *The standard defines the attribute `draw:text-path-allowed`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- y. *The standard defines the attribute `draw:text-rotate-angle`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- z. *The standard defines the attribute `draw:type`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

The enumeration "non-primitive" is supported. Any other value for the `draw:type` attribute is ignored.

- aa. *The standard defines the attribute `svg:view-box`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.319 Section 9.5.2, Enhanced Geometry - Extrusion Attributes

- a. *The standard defines the attribute `dr3d:projection`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this attribute for the `<draw:custom-shape>` element.

- b. *The standard defines the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- c. *The standard defines the property "draft", contained within the attribute dr3d:shade-mode, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this enum for the <draw:custom-shape> element.

- d. *The standard defines the property "flat", contained within the attribute dr3d:shade-mode, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this enum for draw:custom-shape. Word changes this to gourard.

- e. *The standard defines the property "gourard", contained within the attribute dr3d:shade-mode, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this enum for the <draw:custom-shape> element.

- f. *The standard defines the property "phong", contained within the attribute dr3d:shade-mode, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this enum for draw:custom-shape. Word changes this to gourard.

- g. *The standard defines the attribute draw:extrusion, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- h. *The standard defines the attribute draw:extrusion-brightness, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- i. *The standard defines the attribute draw:extrusion-color, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- j. *The standard defines the attribute draw:extrusion-depth, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for the <draw:custom-shape> element.

- k. *The standard defines the attribute draw:extrusion-diffusion, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for draw:custom-shape. Word always writes out the value 65.536% for this attribute.

- l. *The standard defines the attribute draw:extrusion-first-light-direction, contained within the element <draw:enhanced-geometry>*

Word 2013 supports this attribute for draw:custom-shape.

- m. *The standard defines the attribute draw:extrusion-first-light-harsh, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for the <draw:custom-shape> element.

- n. *The standard defines the attribute draw:extrusion-first-light-level, contained within the element <draw:enhanced-geometry>*

Word 2013 does not support this attribute for the <draw:custom-shape> element.

- o. *The standard defines the attribute `draw:extrusion-light-face`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

- p. *The standard defines the attribute `draw:extrusion-metal`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this attribute for the `<draw:custom-shape>` element.

- q. *The standard defines the attribute `draw:extrusion-number-of-line-segments`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

- r. *The standard defines the attribute `draw:extrusion-origin`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for `draw:custom-shape`. Word always writes out (-0.5 0.5).

- s. *The standard defines the attribute `draw:extrusion-rotation-angle`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 supports this attribute for the `<draw:custom-shape>` element.

- t. *The standard defines the attribute `draw:extrusion-rotation-center`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

- u. *The standard defines the attribute `draw:extrusion-second-light-direction`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for `draw:custom-shape`. Word always writes out (-0.05468 0 0.01094).

- v. *The standard defines the attribute `draw:extrusion-second-light-harsh`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for `draw:custom-shape`. Word always writes out false.

- w. *The standard defines the attribute `draw:extrusion-second-light-level`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for `draw:custom-shape`. Word always writes out 37%.

- x. *The standard defines the attribute `draw:extrusion-shininess`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

- y. *The standard defines the attribute `draw:extrusion-skew`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for `draw:custom-shape`.

- z. *The standard defines the attribute `draw:extrusion-specularity`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for `draw:custom-shape`. Word always writes out 80%.

aa. *The standard defines the attribute `draw:extrusion-viewpoint`, contained within the element `<draw:enhanced-geometry>`*

Word 2013 does not support this attribute for the `<draw:custom-shape>` element.

bb. *The standard defines the attribute `dr3d:projection`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

cc. *The standard defines the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

dd. *The standard defines the property "draft", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this enum for the `<draw:custom-shape>` element.

ee. *The standard defines the property "flat", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this enum for `draw:custom-shape`. Excel changes this to `gourard`.

ff. *The standard defines the property "gourard", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this enum for the `<draw:custom-shape>` element.

gg. *The standard defines the property "phong", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this enum for `draw:custom-shape`. Excel changes this to `gourard`.

hh. *The standard defines the attribute `draw:extrusion`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

ii. *The standard defines the attribute `draw:extrusion-brightness`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

jj. *The standard defines the attribute `draw:extrusion-color`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

kk. *The standard defines the attribute `draw:extrusion-depth`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 supports this attribute for the `<draw:custom-shape>` element.

ll. *The standard defines the attribute `draw:extrusion-diffusion`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for `draw:custom-shape`. Excel always writes out the value 65.536% for this attribute.

- mm. *The standard defines the attribute `draw:extrusion-first-light-direction`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 supports this attribute for `draw:custom-shape`.
- nn. *The standard defines the attribute `draw:extrusion-first-light-harsh`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.
- oo. *The standard defines the attribute `draw:extrusion-first-light-level`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.
- pp. *The standard defines the attribute `draw:extrusion-light-face`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.
- qq. *The standard defines the attribute `draw:extrusion-metal`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 supports this attribute for the `<draw:custom-shape>` element.
- rr. *The standard defines the attribute `draw:extrusion-number-of-line-segments`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.
- ss. *The standard defines the attribute `draw:extrusion-origin`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for `draw:custom-shape`. Excel always writes out (-0.5 0.5).
- tt. *The standard defines the attribute `draw:extrusion-rotation-angle`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 supports this attribute for the `<draw:custom-shape>` element.
- uu. *The standard defines the attribute `draw:extrusion-rotation-center`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.
- vv. *The standard defines the attribute `draw:extrusion-second-light-direction`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for `draw:custom-shape`. Excel always writes out (-0.05468 0 0.01094).
- ww. *The standard defines the attribute `draw:extrusion-second-light-harsh`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for `draw:custom-shape`. Excel always writes out false.
- xx. *The standard defines the attribute `draw:extrusion-second-light-level`, contained within the element `<draw:enhanced-geometry>`*
- Excel 2013 does not support this attribute for `draw:custom-shape`. Excel always writes out 37%.

yy. *The standard defines the attribute `draw:extrusion-shininess`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.

zz. *The standard defines the attribute `draw:extrusion-skew`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.

aaa. *The standard defines the attribute `draw:extrusion-specularity`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for `draw:custom-shape`. Excel always writes out 80%.

bbb. *The standard defines the attribute `draw:extrusion-viewpoint`, contained within the element `<draw:enhanced-geometry>`*

Excel 2013 does not support this attribute for the `<draw:custom-shape>` element.

ccc. *The standard defines the attribute `dr3d:projection`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

ddd. *The standard defines the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

eee. *The standard defines the property "draft", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this enum for the `<draw:custom-shape>` element.

fff. *The standard defines the property "flat", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this enum for `draw:custom-shape`. PowerPoint changes this to `gourard`.

ggg. *The standard defines the property "gourard", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this enum for the `<draw:custom-shape>` element.

hhh. *The standard defines the property "phong", contained within the attribute `dr3d:shade-mode`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this enum for `draw:custom-shape`. PowerPoint changes this to `gourard`.

iii. *The standard defines the attribute `draw:extrusion`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

jjj. *The standard defines the attribute `draw:extrusion-brightness`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

kkk. *The standard defines the attribute `draw:extrusion-color`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

lll. *The standard defines the attribute `draw:extrusion-depth`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

mmm. *The standard defines the attribute `draw:extrusion-diffusion`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for `draw:custom-shape`. PowerPoint always writes out the value 65.536% for this attribute.

nnn. *The standard defines the attribute `draw:extrusion-first-light-direction`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for `draw:custom-shape`.

ooo. *The standard defines the attribute `draw:extrusion-first-light-harsh`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

ppp. *The standard defines the attribute `draw:extrusion-first-light-level`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

qqq. *The standard defines the attribute `draw:extrusion-light-face`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

rrr. *The standard defines the attribute `draw:extrusion-metal`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

sss. *The standard defines the attribute `draw:extrusion-number-of-line-segments`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

ttt. *The standard defines the attribute `draw:extrusion-origin`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for `draw:custom-shape`. PowerPoint always writes out (-0.5 0.5).

uuu. *The standard defines the attribute `draw:extrusion-rotation-angle`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 supports this attribute for the `<draw:custom-shape>` element.

vvv. *The standard defines the attribute `draw:extrusion-rotation-center`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

www. *The standard defines the attribute `draw:extrusion-second-light-direction`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for `draw:custom-shape`. PowerPoint always writes out (-0.05468 0 0.01094).

xxx. *The standard defines the attribute `draw:extrusion-second-light-harsh`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for `draw:custom-shape`. PowerPoint always writes out false.

yyy. *The standard defines the attribute `draw:extrusion-second-light-level`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for `draw:custom-shape`. PowerPoint always writes out 37%.

zzz. *The standard defines the attribute `draw:extrusion-shininess`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

aaaa. *The standard defines the attribute `draw:extrusion-skew`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

bbbb. *The standard defines the attribute `draw:extrusion-specularity`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for `draw:custom-shape`. PowerPoint always writes out 80%.

cccc. *The standard defines the attribute `draw:extrusion-viewpoint`, contained within the element `<draw:enhanced-geometry>`*

PowerPoint 2013 does not support this attribute for the `<draw:custom-shape>` element.

2.1.320 Section 9.5.3, Enhanced Geometry - Path Attributes

a. *The standard defines the attribute `draw:enhanced-path`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

On load, Word rounds floats to integers.

b. *The standard defines the attribute `draw:glue-point-leaving-directions`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

c. *The standard defines the attribute `draw:glue-points`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

On load, Word rounds floats to integers.

- d. *The standard defines the attribute `draw:glue-point-type`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute `draw:path-stretchpoint-x`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- f. *The standard defines the attribute `draw:path-stretchpoint-y`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- g. *The standard defines the attribute `draw:text-areas`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

Only one text area per drawing shape is supported.

- h. *The standard defines the attribute `draw:enhanced-path`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel rounds floats to integers.

- i. *The standard defines the attribute `draw:glue-point-leaving-directions`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute `draw:glue-points`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel rounds floats to integers.

- k. *The standard defines the attribute `draw:glue-point-type`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the attribute `draw:path-stretchpoint-x`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- m. *The standard defines the attribute `draw:path-stretchpoint-y`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- n. *The standard defines the attribute `draw:text-areas`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Excel 2010 and Excel 2013.

Only one text area per drawing shape is supported.

- o. *The standard defines the attribute `draw:enhanced-path`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint rounds floats to integers.

- p. *The standard defines the attribute `draw:glue-point-leaving-directions`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- q. *The standard defines the attribute `draw:glue-points`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint rounds floats to integers.

- r. *The standard defines the attribute `draw:glue-point-type`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- s. *The standard defines the attribute `draw:path-stretchpoint-x`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- t. *The standard defines the attribute `draw:path-stretchpoint-y`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

The presence of this attribute is interpreted to mean that the application should maintain the aspect ratio of the shape's view box. The actual value of this attribute is ignored.

- u. *The standard defines the attribute `draw:text-areas`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

Only one text area per drawing shape is supported.

2.1.321 Section 9.5.4, Enhanced Geometry - Text Path Attributes

- a. *The standard defines the attribute `draw:modifiers`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:text-path`, contained within the element `<draw:enhanced-geometry>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `draw:text-path-mode`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2010 or Word 2013.

Word always sets the value of `draw:text-path-mode` to "shape".

- d. *The standard defines the attribute `draw:text-path-same-letter-heights`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `draw:text-path-scale`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Word 2010 or Word 2013.

Word only uses shape text path scaling.

- f. *The standard defines the attribute `draw:modifiers`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `draw:text-path`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `draw:text-path-mode`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `draw:text-path-same-letter-heights`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute `draw:text-path-scale`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute `draw:modifiers`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the attribute `draw:text-path`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute `draw:text-path-mode`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute `draw:text-path-same-letter-heights`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- o. *The standard defines the attribute `draw:text-path-scale`, contained within the element `<draw:enhanced-geometry>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.322 Section 9.5.5, Enhanced Geometry – Equation

- a. *The standard defines the element `<draw:equation>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `draw:formula`, contained within the element `<draw:equation>`*

This attribute is supported in Word 2010 and Word 2013.

Word does not support the identifiers 'logwidth' and 'logheight'.

- c. *The standard defines the attribute `draw:name`, contained within the element `<draw:equation>`*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the element `<draw:equation>`*

This element is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute `draw:formula`, contained within the element `<draw:equation>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel does not support the identifiers 'logwidth' and 'logheight'.

- f. *The standard defines the attribute `draw:name`, contained within the element `<draw:equation>`*

This attribute is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the element `<draw:equation>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- h. *The standard defines the attribute `draw:formula`, contained within the element `<draw:equation>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not support the identifiers "logwidth" and "logheight".

- i. *The standard defines the attribute `draw:name`, contained within the element `<draw:equation>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.323 Section 9.5.6, Enhanced Geometry - Handle Attributes

- a. *The standard defines the element <draw:handle>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute draw:handle-mirror-horizontal, contained within the element <draw:handle>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute draw:handle-mirror-vertical, contained within the element <draw:handle>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute draw:handle-polar, contained within the element <draw:handle>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute draw:handle-position, contained within the element <draw:handle>*

This attribute is supported in Word 2010 and Word 2013.

Word does not support the identifiers 'logwidth' and 'logheight'.

- f. *The standard defines the attribute draw:handle-radius-range-maximum, contained within the element <draw:handle>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute draw:handle-radius-range-minimum, contained within the element <draw:handle>*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute draw:handle-range-x-maximum, contained within the element <draw:handle>*

This attribute is supported in Word 2010 and Word 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- i. *The standard defines the attribute draw:handle-range-x-minimum, contained within the element <draw:handle>*

This attribute is supported in Word 2010 and Word 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- j. *The standard defines the attribute draw:handle-range-y-maximum, contained within the element <draw:handle>*

This attribute is supported in Word 2010 and Word 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- k. *The standard defines the attribute `draw:handle-range-y-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Word 2010 and Word 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- l. *The standard defines the attribute `draw:handle-switched`, contained within the element `<draw:handle>`*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the element `<draw:handle>`*

This element is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the attribute `draw:handle-mirror-horizontal`, contained within the element `<draw:handle>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the attribute `draw:handle-mirror-vertical`, contained within the element `<draw:handle>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- p. *The standard defines the attribute `draw:handle-polar`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the attribute `draw:handle-position`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel does not support the identifiers 'logwidth' and 'logheight'.

- r. *The standard defines the attribute `draw:handle-radius-range-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the attribute `draw:handle-radius-range-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the attribute `draw:handle-range-x-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- u. *The standard defines the attribute `draw:handle-range-x-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- v. *The standard defines the attribute `draw:handle-range-y-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- w. *The standard defines the attribute `draw:handle-range-y-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in Excel 2010 and Excel 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- x. *The standard defines the attribute `draw:handle-switched`, contained within the element `<draw:handle>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- y. *The standard defines the element `<draw:handle>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- z. *The standard defines the attribute `draw:handle-mirror-horizontal`, contained within the element `<draw:handle>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- aa. *The standard defines the attribute `draw:handle-mirror-vertical`, contained within the element `<draw:handle>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- bb. *The standard defines the attribute `draw:handle-polar`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- cc. *The standard defines the attribute `draw:handle-position`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not support the identifiers "logwidth" and "logheight".

- dd. *The standard defines the attribute `draw:handle-radius-range-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- ee. *The standard defines the attribute `draw:handle-radius-range-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- ff. *The standard defines the attribute `draw:handle-range-x-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- gg. *The standard defines the attribute `draw:handle-range-x-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- hh. *The standard defines the attribute `draw:handle-range-y-maximum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- ii. *The standard defines the attribute `draw:handle-range-y-minimum`, contained within the element `<draw:handle>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

If the formula that specifies this value contains a reference to the current value of the handle (either directly or by referencing another formula), a circular reference is created, and the range is lost. This may allow the user to move the adjustment handle outside of the specified range.

- jj. *The standard defines the attribute `draw:handle-switched`, contained within the element `<draw:handle>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.324 Section 9.6, Presentation Shapes

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

In PowerPoint, changing layouts will adapt the presentation shapes (also known as placeholders within PowerPoint). However, PowerPoint does not load the `presentation-page-layout`, as defined in section 14.15, therefore there is no way to change this property for a given slide inside of PowerPoint.

2.1.325 Section 9.6.1, Common Presentation Shape Attributes

- a. *The standard defines the attribute presentation:class*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

If an object placeholder exists on a slide, but PowerPoint finds no matching placeholder for that type of object in the layout, PowerPoint writes the placeholder out as a general object placeholder.

- b. *The standard defines the attribute presentation:placeholder*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint uses this attribute to describe placeholders that are empty. It is ignored on load.

- c. *The standard defines the attribute presentation:style-name*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute presentation:user-transform*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.326 Section 9.7, Presentation Animations

- a. *The standard defines the element <presentation:animations>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.327 Section 9.7.1, Sound

- a. *The standard defines the element <presentation:sound>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.328 Section 9.7.2, Show Shape

- a. *The standard defines the element <presentation:show-shape>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.329 Section 9.7.3, Show Text

- a. *The standard defines the element <presentation:show-text>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.330 Section 9.7.4, Hide Shape

- a. *The standard defines the element <presentation:hide-shape>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.331 Section 9.7.5, Hide Text

- a. *The standard defines the element <presentation:hide-text>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.332 Section 9.7.6, Dim

- a. *The standard defines the element <presentation:dim>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.333 Section 9.7.7, Play

- a. *The standard defines the element <presentation:play>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.334 Section 9.7.8, Effect groups

- a. *The standard defines the element <presentation:animation-group>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.335 Section 9.8, SMIL Presentation Animations

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.336 Section 9.8.1, Recommended Usage Of SMIL

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the element <anim:par>, contained within the parent element <draw:page>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.337 Section 9.8.2, Document Dependent SMIL Animation Attribute Values

- a. *The standard defines the property "custom", contained within the attribute anim:command*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- b. *The standard defines the property "play", contained within the attribute anim:command*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the property "stop", contained within the attribute anim:command*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the property "stop-audio", contained within the attribute anim:command*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the property "toggle-pause", contained within the attribute anim:command*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the property "verb", contained within the attribute anim:command*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- g. *The standard defines the attribute anim:formula*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- h. *The standard defines the property "background", contained within the attribute anim:sub-item*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- i. *The standard defines the property "text", contained within the attribute anim:sub-item*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- j. *The standard defines the property "whole", contained within the attribute anim:sub-item*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- k. *The standard defines the property "charColor", contained within the attribute smil:attributeName*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
PowerPoint disregards color animations for animations that use the AnimColor element.
- l. *The standard defines the property "charFontName", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- m. *The standard defines the property "charHeight", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- n. *The standard defines the property "charPosture", contained within the attribute smil:attributeName*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- o. *The standard defines the property "charUnderline", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- p. *The standard defines the property "charWeight", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- q. *The standard defines the property "color", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- r. *The standard defines the property "fillColor", contained within the attribute smil:attributeName*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
PowerPoint disregards color animations for animations that use the AnimColor element.
- s. *The standard defines the property "fillStyle", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- t. *The standard defines the property "height", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- u. *The standard defines the property "lineColor", contained within the attribute smil:attributeName*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint disregards color animations for animations that use the AnimColor element.

- v. *The standard defines the property "lineStyle", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- w. *The standard defines the property "opacity", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- x. *The standard defines the property "rotate", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- y. *The standard defines the property "skewX", contained within the attribute smil:attributeName*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- z. *The standard defines the property "visibility", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- aa. *The standard defines the property "width", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- bb. *The standard defines the property "x", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- cc. *The standard defines the property "y", contained within the attribute smil:attributeName*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- dd. *The standard defines the attribute smil:targetElement*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- ee. *The standard defines the attribute anim:iterate-type, contained within the element <anim:iterate>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- ff. *The standard defines the attribute smil:targetElement, contained within the element <anim:iterate>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.338 Section 9.8.3, SMIL Presentation Animation Attributes

- a. *The standard defines the attribute presentation:group-id*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- b. *The standard defines the attribute presentation:master-element*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- c. *The standard defines the attribute presentation:node-type*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute `presentation:preset-class`*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- e. *The standard defines the attribute `presentation:preset-id`*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- f. *The standard defines the attribute `presentation:preset-sub-type`*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.339 Section 9.9, Presentation Events

- a. *The standard defines the element `<presentation:event-listener>`*
This element is supported in PowerPoint 2010 and PowerPoint 2013.

Shapes and text that link to actions use the `<presentation:event-listener>` element. Grouped shapes cannot have links to actions.

Actions that are set to happen when the mouse rests on an item, such as a button or link, use the `<presentation:event-listener>` element. Grouped shapes cannot have actions associated with the mouse resting on an item.

Text links to URLs use the `<text:a>` hyperlink tag.
- b. *The standard defines the attribute `presentation:action`, contained within the element `<presentation:event-listener>`*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- c. *The standard defines the property "execute", contained within the attribute `presentation:action`, contained within the element `<presentation:event-listener>`*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- d. *The standard defines the property "fade-out", contained within the attribute `presentation:action`, contained within the element `<presentation:event-listener>`*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- e. *The standard defines the property "first-page", contained within the attribute `presentation:action`, contained within the element `<presentation:event-listener>`*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- f. *The standard defines the property "hide", contained within the attribute `presentation:action`, contained within the element `<presentation:event-listener>`*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- g. *The standard defines the property "last-page", contained within the attribute `presentation:action`, contained within the element `<presentation:event-listener>`*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- h. *The standard defines the property "next-page", contained within the attribute `presentation:action`, contained within the element `<presentation:event-listener>`*
This property is supported in PowerPoint 2010 and PowerPoint 2013.

- i. *The standard defines the property "none", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- j. *The standard defines the property "previous-page", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- k. *The standard defines the property "show", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not support links to slides in other presentations.

- l. *The standard defines the property "sound", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the property "stop", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- n. *The standard defines the property "verb", contained within the attribute presentation:action, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

If this property is used but no presentation:verb attribute is present, PowerPoint replaces the slide with a blank slide.

- o. *The standard defines the attribute presentation:direction, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- p. *The standard defines the attribute presentation:effect, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the attribute presentation:speed, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute presentation:start-scale, contained within the element <presentation:event-listener>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the attribute presentation:verb, contained within the element <presentation:event-listener>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- t. *The standard defines the attribute script:event-name, contained within the element <presentation:event-listener>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint only supports the dom:click and dom:mouseover events.

- u. *The standard defines the property "dom:click", contained within the attribute script:event-name, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- v. *The standard defines the property "dom:mouseover", contained within the attribute script:event-name, contained within the element <presentation:event-listener>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint only supports this property on shapes. It is not supported on text.

- w. *The standard defines the attribute xlink:href, contained within the element <presentation:event-listener>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- x. *The standard defines the element <presentation:sound>, contained within the parent element <presentation:event-listener>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.340 Section 9.10, Presentation Text Fields

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.341 Section 9.10.1, Header Field

- a. *The standard defines the element <presentation:header>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not save this element, but does read it in on master-pages to determine the location of the header field.

2.1.342 Section 9.10.2, Footer Field

- a. *The standard defines the element <presentation:footer>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not save this element, but does read it in on master-pages to determine the location of the footer field.

2.1.343 Section 9.10.3, Date and Time Field

- a. *The standard defines the element <presentation:date-time>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint does not save this element, but does read it in on master-pages to determine the location of the date-time field.

2.1.344 Section 9.11, Presentation Document Content

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.345 Section 9.11.1, Presentation Declarations

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.346 Section 9.11.2, Header field declaration

- a. *The standard defines the element <presentation:header-decl>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint loads headers declared using this attribute, but saves them as textboxes with regular text.

- b. *The standard defines the attribute presentation:name, contained within the element <presentation:header-decl>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.347 Section 9.11.3, Footer field declaration

- a. *The standard defines the element <presentation:footer-decl>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint loads footers declared using this attribute, but saves them as textboxes with regular text.

- b. *The standard defines the attribute presentation:name, contained within the element <presentation:footer-decl>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.348 Section 9.11.4, Date and Time field declaration

- a. *The standard defines the attribute presentation:source*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute style:date-style-name*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the element <presentation:date-time-decl>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint loads dates/times declared using this attribute, but saves them as textboxes with regular text.

- d. *The standard defines the attribute presentation:name, contained within the element <presentation:date-time-decl>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.349 Section 9.11.5, Presentation Settings

- a. *The standard defines the element <presentation:settings>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute presentation:animations, contained within the element <presentation:settings>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the attribute presentation:endless, contained within the element <presentation:settings>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute presentation:force-manual, contained within the element <presentation:settings>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- e. *The standard defines the attribute presentation:full-screen, contained within the element <presentation:settings>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

When this attribute value is False and the transition-on-click value is True, the presentation displays in a window. When this attribute value is True, the presentation shows in full slideshow or kiosk mode.

- f. *The standard defines the attribute presentation:mouse-as-pen, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- g. *The standard defines the attribute presentation:mouse-visible, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- h. *The standard defines the attribute presentation:pause, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- i. *The standard defines the attribute presentation:show-end-of-presentation-slide, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the attribute presentation:show-logo, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- k. *The standard defines the attribute presentation:start-page, contained within the element <presentation:settings>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- l. *The standard defines the attribute presentation:start-with-navigator, contained within the element <presentation:settings>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute `presentation:stay-on-top`, contained within the element `<presentation:settings>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute `presentation:transition-on-click`, contained within the element `<presentation:settings>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

A value of True for this attribute and a value of True for `presentation:full-screen` shows the slideshow in regular full screen mode. A value of True for this attribute and a value of False for `presentation:full-screen` shows the slideshow in browsing (windowed) mode. A value of False for this attribute and a value of True for `presentation:full-screen` shows the slideshow in kiosk mode. A value of False for this attribute and a value of False for `presentation:full-screen` shows the slide show in regular full-screen slideshow mode.

2.1.350 Section 9.11.6, Show Definitions

- a. *The standard defines the attribute `presentation:show`, contained within the element `<presentation:settings>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the element `<presentation:show>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.351 Section 10, Chart Content

- a. This is supported in Excel 2010 and Excel 2013.

2.1.352 Section 10.1, Introduction to Chart Documents

- a. This is supported in Excel 2010 and Excel 2013.

2.1.353 Section 10.2, Chart

- a. *The standard defines the element `<chart:chart>`, contained within the parent element `<chart-chart>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `chart-chart-attlist`, contained within the element `<chart:chart>`, contained within the parent element `<chart-chart>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.354 Section 10.3, Title, Subtitle and Footer

- a. This is supported in Excel 2010 and Excel 2013.

2.1.355 Section 10.3.1, Title

- a. *The standard defines the element `<chart:title>`, contained within the parent element `<chart-title>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `chart-title-attlist`, contained within the element `<chart:title>`, contained within the parent element `<chart-title>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.356 Section 10.3.2, Subtitle

- a. *The standard defines the element `<chart:subtitle>`, contained within the parent element `<chart:chart>`*

This element is not supported in Excel 2010 or Excel 2013.

2.1.357 Section 10.3.3, Footer

- a. *The standard defines the element `<chart:footer>`, contained within the parent element `<chart:chart>`*

This element is not supported in Excel 2010 or Excel 2013.

2.1.358 Section 10.4, Legend

- a. *The standard defines the element `<chart:legend>`, contained within the parent element `<chart:chart>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `chart-legend-attlist`, contained within the element `<chart:legend>`, contained within the parent element `<chart:chart>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.359 Section 10.5, Plot Area

- a. *The standard defines the element `<chart:plot-area>`, contained within the parent element `<chart-plot-area>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `chart-plot-area-attlist`, contained within the element `<chart:plot-area>`, contained within the parent element `<chart-plot-area>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.360 Section 10.6, Wall

- a. *The standard defines the element `<chart:wall>`, contained within the parent element `<chart-wall>`*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute `chart-wall-attlist`, contained within the element `<chart:wall>`, contained within the parent element `<chart-wall>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.361 Section 10.7, Floor

- a. *The standard defines the element <chart:floor>, contained within the parent element <chart-floor>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute chart-floor-attlist, contained within the element <chart:floor>, contained within the parent element <chart-floor>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.362 Section 10.8, Axis

- a. *The standard defines the element <chart:axis>, contained within the parent element <chart-axis>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute chart-axis-attlist, contained within the element <chart:axis>, contained within the parent element <chart-axis>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.363 Section 10.8.1, Grid

- a. *The standard defines the element <chart:grid>, contained within the parent element <chart-grid>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute chart-grid-attlist, contained within the element <chart:grid>, contained within the parent element <chart-grid>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.364 Section 10.9, Series

- a. *The standard defines the element <chart:series>, contained within the parent element <chart-series>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute chart-series-attlist, contained within the element <chart:series>, contained within the parent element <chart-series>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.365 Section 10.9.1, Domain

- a. *The standard defines the element <chart:domain>, contained within the parent element <chart-domain>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute table:cell-range-address, contained within the element <chart:domain>, contained within the parent element <chart-domain>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.366 Section 10.10, Categories

- a. *The standard defines the element <chart:categories>, contained within the parent element <chart-categories>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute table:cell-range-address, contained within the element <chart:categories>, contained within the parent element <chart-categories>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.367 Section 10.11, Data Point

- a. *The standard defines the element <chart:data-point>, contained within the parent element <chart-data-point>*

This element is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the attribute chart-data-point-attlist, contained within the element <chart:data-point>, contained within the parent element <chart-data-point>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.368 Section 10.12, Mean Value

- a. *The standard defines the element <chart:mean-value>, contained within the parent element <chart-mean-value>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.369 Section 10.13, Error Indicator

- a. *The standard defines the element <chart:error-indicator>, contained within the parent element <chart-error-indicator>*

This element is supported in Excel 2010 and Excel 2013.

Excel only supports this element when the series type is line, area, scatter, bar, stock, or bubble; and the chart is not three dimensional.

- b. *The standard defines the attribute chart-error-indicator-attlist, contained within the element <chart:error-indicator>, contained within the parent element <chart-error-indicator>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.370 Section 10.14, Regression Curves

- a. *The standard defines the element <chart:regression-curve>, contained within the parent element <chart-regression-curve>*

This element is supported in Excel 2010 and Excel 2013.

Excel only supports this element when the series type is line, area, scatter, bar, stock, or bubble; and the chart is not three dimensional.

- b. *The standard defines the attribute chart-regression-curve-attlist, contained within the element <chart:regression-curve>, contained within the parent element <chart-regression-curve>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.371 Section 10.14.1, Stock Chart Markers

- a. *The standard defines the element <chart:stock-gain-marker>, contained within the parent element <chart-stock-gain-marker>*

This element is supported in Excel 2010 and Excel 2013.

Excel only supports this element when the series type is line or stock and the chart is not three dimensional.

- b. *The standard defines the attribute common-stock-marker-attlist, contained within the element <chart:stock-gain-marker>, contained within the parent element <chart-stock-gain-marker>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the element <chart:stock-loss-marker>, contained within the parent element <chart-stock-loss-marker>*

This element is supported in Excel 2010 and Excel 2013.

Excel only supports this element when the series type is line or stock and the chart is not three dimensional.

- d. *The standard defines the attribute common-stock-marker-attlist, contained within the element <chart:stock-loss-marker>, contained within the parent element <chart-stock-loss-marker>*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the element <chart:stock-range-line>, contained within the parent element <chart-stock-range-line>*

This element is supported in Excel 2010 and Excel 2013.

Excel only supports this element when the series type is line or stock and the chart is not three dimensional.

- f. *The standard defines the attribute common-stock-marker-attlist, contained within the element <chart:stock-range-line>, contained within the parent element <chart-stock-range-line>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.372 Section 11, Form Content

- a. *The standard defines the element <office:forms>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <office:forms>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <office:forms>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.373 Section 11.1, Form

- a. *The standard defines the element <form:form>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:form>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.374 Section 11.1.1, Action

- a. *The standard defines the attribute xlink:actuate, contained within the element <form:form>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute xlink:href, contained within the element <form:form>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute xlink:type, contained within the element <form:form>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute xlink:href, contained within the element <form:form>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.375 Section 11.1.2, Target Frame

- a. *The standard defines the attribute office:target-frame, contained within the element <form:form>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute office:target-frame, contained within the element <form:form>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.376 Section 11.1.3, Method

- a. *The standard defines the attribute form:method, contained within the element <form:form>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:method, contained within the element <form:form>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.377 Section 11.1.4, Encoding Type

- a. *The standard defines the attribute form:enctype, contained within the element <form:form>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:enctype, contained within the element <form:form>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.378 Section 11.1.5, Allow Deletes

- a. *The standard defines the attribute form:allow-deletes, contained within the element <form:form>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `form:allow-deletes`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.379 Section 11.1.6, Allow Inserts

- a. *The standard defines the attribute `form:allow-inserts`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:allow-inserts`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.380 Section 11.1.7, Allow Updates

- a. *The standard defines the attribute `form:allow-updates`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:allow-updates`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.381 Section 11.1.8, Apply Filter

- a. *The standard defines the attribute `form:apply-filter`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:apply-filter`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.382 Section 11.1.9, Command Type

- a. *The standard defines the attribute `form:command-type`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:command-type`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.383 Section 11.1.10, Command

- a. *The standard defines the attribute `form:command`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:command`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.384 Section 11.1.11, Data Source

- a. *The standard defines the attribute `form:datasource`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:datasource`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.385 Section 11.1.12, Master Fields

- a. *The standard defines the attribute `form:master-fields`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:master-fields`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.386 Section 11.1.13, Detail Fields

- a. *The standard defines the attribute `form:detail-fields`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:detail-fields`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.387 Section 11.1.14, Escape Processing

- a. *The standard defines the attribute `form:escape-processing`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:command-type`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.388 Section 11.1.15, Filter

- a. *The standard defines the attribute `form:filter`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:filter`, contained within the element `<form:form>`
This attribute is not supported in Excel 2010 or Excel 2013.*

2.1.389 Section 11.1.16, Ignore Result

- a. *The standard defines the attribute `form:ignore-result`, contained within the element `<form:form>`
This attribute is not supported in Word 2010 or Word 2013.*
- b. *The standard defines the attribute `form:ignore-result`, contained within the element `<form:form>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.390 Section 11.1.17, Navigation Mode

- a. *The standard defines the attribute `form:navigation-mode`, contained within the element `<form:form>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `form:navigation-mode`, contained within the element `<form:form>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.391 Section 11.1.18, Order

- a. *The standard defines the attribute `form:order`, contained within the element `<form:form>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `form:order`, contained within the element `<form:form>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.392 Section 11.1.19, Tabbing Cycle

- a. *The standard defines the attribute `form:tab-cycle`, contained within the element `<form:form>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `form:tab-cycle`, contained within the element `<form:form>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.393 Section 11.1.20, Connection Resource

- a. *The standard defines the element `<form:connection-resource>`*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<form:connection-resource>`*

This element is not supported in Excel 2010 or Excel 2013.

2.1.394 Section 11.2, XForms Model

- a. This is not supported in Excel 2010 or Excel 2013.

2.1.395 Section 11.2.1, XForms Model

- a. *The standard defines the element `<xforms:model>`*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element `<xforms:model>`*

This element is not supported in Excel 2010 or Excel 2013.

2.1.396 Section 11.3, Controls

- a. *The standard defines the element <form:properties>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.

2.1.397 Section 11.3.1, Text

- a. *The standard defines the element <form:text>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <form:text>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.398 Section 11.3.2, Text Area

- a. *The standard defines the element <form:textarea>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <form:textarea>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.399 Section 11.3.3, Password

- a. *The standard defines the element <form:password>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <form:password>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.400 Section 11.3.4, File

- a. *The standard defines the element <form:file>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <form:file>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.401 Section 11.3.5, Formatted Text

- a. *The standard defines the element <form:formatted-text>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <form:formatted-text>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.402 Section 11.3.6, Number

- a. *The standard defines the element <form:number>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:number>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.403 Section 11.3.7, Date And Time

- a. *The standard defines the element <form:date>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:date>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <form:time>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.404 Section 11.3.8, Fixed Text

- a. *The standard defines the element <form:fixed-text>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:fixed-text>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.405 Section 11.3.9, Combo Box

- a. *The standard defines the element <form:combobox>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:item>, contained within the parent element <form:combobox>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <form:combobox>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.406 Section 11.3.10, List Box

- a. *The standard defines the element <form:listbox>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:option>, contained within the parent element <form:listbox>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <form:listbox>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.407 Section 11.3.11, Button

- a. *The standard defines the element <form:button>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:button>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.408 Section 11.3.12, Image

- a. *The standard defines the element <form:image>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:image>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.409 Section 11.3.13, Check Box

- a. *The standard defines the element <form:checkbox>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:checkbox>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.410 Section 11.3.14, Radio Button

- a. *The standard defines the element <form:radio>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:radio>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.411 Section 11.3.15, Frame

- a. *The standard defines the element <form:frame>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:frame>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.412 Section 11.3.16, Image Frame

- a. *The standard defines the element <form:image-frame>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:image-frame>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.413 Section 11.3.17, Hidden

- a. *The standard defines the element <form:hidden>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:hidden>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.414 Section 11.3.18, Grid

- a. *The standard defines the element <form:column>, contained within the parent element <form:grid>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:grid>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <form:grid>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.415 Section 11.3.19, Value Range

- a. *The standard defines the element <form:value-range>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:value-range>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.416 Section 11.3.20, Generic Control

- a. *The standard defines the element <form:generic-control>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <form:generic-control>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.417 Section 11.4, Common Form and Control Attributes

- a. This is not supported in Excel 2010 or Excel 2013.

2.1.418 Section 11.4.1, Name

- a. *The standard defines the attribute form:name*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:name*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.419 Section 11.4.2, Control Implementation

- a. *The standard defines the attribute form:control-implementation*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:control-implementation*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.420 Section 11.4.3, Bind to XForms

- a. *The standard defines the attribute xforms:bind*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute xforms:bind*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.421 Section 11.5, Common Control Attributes

- a. This is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.422 Section 11.5.1, Button Type

- a. *The standard defines the attribute form:button-type*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:button-type*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.423 Section 11.5.2, Control ID

- a. *The standard defines the attribute form:id*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:id*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.424 Section 11.5.3, Current Selected

- a. *The standard defines the attribute form:current-selected*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:current-selected*
This attribute is not supported in Excel 2010 or Excel 2013.

2.1.425 Section 11.5.4, Value and Current Value

- a. *The standard defines the attribute form:current-value*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute form:value*
This attribute is not supported in Word 2010 or Word 2013.
- c. *The standard defines the attribute form:current-value*
This attribute is not supported in Excel 2010 or Excel 2013.
- d. *The standard defines the attribute form:value*
This attribute is not supported in Excel 2010 or Excel 2013.

2.1.426 Section 11.5.5, Disabled

- a. *The standard defines the attribute form:disabled*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute form:disabled*
This attribute is not supported in Excel 2010 or Excel 2013.

2.1.427 Section 11.5.6, Dropdown

- a. *The standard defines the attribute form:dropdown*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute form:dropdown*
This attribute is not supported in Excel 2010 or Excel 2013.

2.1.428 Section 11.5.7, For

- a. *The standard defines the attribute form:for*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute form:for*
This attribute is not supported in Excel 2010 or Excel 2013.

2.1.429 Section 11.5.8, Image Data

- a. *The standard defines the attribute form:image-data*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute form:image-data*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.430 Section 11.5.9, Label

- a. *The standard defines the attribute form:label*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:label*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.431 Section 11.5.10, Maximum Length

- a. *The standard defines the attribute form:max-length*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:max-length*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.432 Section 11.5.11, Printable

- a. *The standard defines the attribute form:printable*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:printable*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.433 Section 11.5.12, Read only

- a. *The standard defines the attribute form:read-only*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:readonly*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.434 Section 11.5.13, Selected

- a. *The standard defines the attribute form:selected*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:selected*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.435 Section 11.5.14, Size

- a. *The standard defines the attribute form:size*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:size*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.436 Section 11.5.15, Tab Index

- a. *The standard defines the attribute form:tab-index*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:tab-index*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.437 Section 11.5.16, Tab Stop

- a. *The standard defines the attribute form:tab-stop*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:tab-stop*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.438 Section 11.5.17, Target Frame

- a. *The standard defines the attribute office:target-frame*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:target-frame*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.439 Section 11.5.18, Target Location

- a. *The standard defines the attribute xlink:href*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute xlink:href*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.440 Section 11.5.19, Title

- a. *The standard defines the attribute form:title*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:title*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.441 Section 11.5.20, Visual Effect

- a. *The standard defines the attribute form:visual-effect*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:visual-effect*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.442 Section 11.5.21, Relative Image Position

- a. *The standard defines the attribute form:image-align*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:image-position*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute form:image-align*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute form:image-position*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.443 Section 11.5.22, Database Binding Attributes

- a. *The standard defines the attribute form:bound-column*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute form:convert-empty-to-null*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute form:data-field*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute form:list-source*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute form:list-source-type*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute form:bound-column*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute form:convert-empty-to-null*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute form:data-field*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute form:list-source*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute form:list-source-type*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.444 Section 11.6, Event Listeners

- a. This is not supported in Word 2010 or Word 2013.
b. This is not supported in Excel 2010 or Excel 2013.

2.1.445 Section 11.7, Properties

- a. This is not supported in Word 2010 or Word 2013.
b. This is not supported in Excel 2010 or Excel 2013.

2.1.446 Section 11.7.1, Property Set

- a. *The standard defines the element <form:properties>*
This element is not supported in Word 2010 or Word 2013.
b. *The standard defines the element <form:properties>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.447 Section 11.7.2, Property

- a. *The standard defines the element <form:property>*
This element is not supported in Word 2010 or Word 2013.
b. *The standard defines the attribute form:property-name, contained within the element <form:property>*
This attribute is not supported in Word 2010 or Word 2013.
c. *The standard defines the attribute office:value-type, contained within the element <form:property>*
This attribute is not supported in Word 2010 or Word 2013.
d. *The standard defines the element <form:property>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.448 Section 11.7.3, List Property

- a. *The standard defines the attribute form:list-value*
This attribute is not supported in Word 2010 or Word 2013.
b. *The standard defines the element <form:list-property>*
This element is not supported in Word 2010 or Word 2013.
c. *The standard defines the element <form:list-property>*
This element is not supported in Excel 2010 or Excel 2013.

2.1.449 Section 12, Common Content

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
- b. OfficeArt Math in Excel 2013 supports this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.450 Section 12.1, Annotation

- a. *The standard defines the element <office:annotation>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute draw:caption-point-x, contained within the element <office:annotation>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute draw:caption-point-y, contained within the element <office:annotation>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute draw:corner-radius, contained within the element <office:annotation>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `draw:id`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute `draw:layer`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute `draw:name`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute `draw:style-name`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute `draw:transform`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute `draw:z-index`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- k. *The standard defines the attribute `office:display`, contained within the element `<office:annotation>`*

This attribute is supported in Word 2010 and Word 2013.

- l. *The standard defines the attribute `svg:height`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute `svg:width`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- n. *The standard defines the attribute `svg:x`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- o. *The standard defines the attribute `svg:y`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- p. *The standard defines the attribute `table:end-cell-address`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- q. *The standard defines the attribute `table:end-x`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- r. *The standard defines the attribute `table:end-y`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- s. *The standard defines the attribute `text:anchor-page-number`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- t. *The standard defines the attribute `text:anchor-type`, contained within the element `<office:annotation>`*

This attribute is not supported in Word 2010 or Word 2013.

- u. *The standard defines the attribute `draw:caption-point-x`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the attribute `draw:caption-point-y`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- w. *The standard defines the attribute `draw:corner-radius`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- x. *The standard defines the attribute `draw:id`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- y. *The standard defines the attribute `draw:layer`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- z. *The standard defines the attribute `draw:name`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- aa. *The standard defines the attribute `draw:style-name`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel does not read in this attribute. On save, different BG colors and BG images on comments are not written to ODF.

- bb. *The standard defines the attribute `draw:text-style-name`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel does not read this attribute. On save, Excel does not write different text alignment to ODF.

- cc. *The standard defines the attribute `draw:transform`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- dd. *The standard defines the attribute `draw:z-index`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ee. *The standard defines the attribute `office:display`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2010 and Excel 2013.

ff. *The standard defines the attribute `svg:height`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2010 and Excel 2013.

gg. *The standard defines the attribute `svg:width`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2010 and Excel 2013.

hh. *The standard defines the attribute `svg:x`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2010 and Excel 2013.

ii. *The standard defines the attribute `svg:y`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2010 and Excel 2013.

jj. *The standard defines the attribute `table:end-cell-address`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

kk. *The standard defines the attribute `table:end-x`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ll. *The standard defines the attribute `table:end-y`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

mm. *The standard defines the attribute `text:anchor-page-number`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

nn. *The standard defines the attribute `text:anchor-type`, contained within the element `<office:annotation>`*

This attribute is not supported in Excel 2010 or Excel 2013.

oo. *The standard defines the attribute `text:p`, contained within the element `<office:annotation>`*

This attribute is supported in Excel 2010 and Excel 2013.

pp. *The standard defines the element `<<office:annotation>>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.451 Section 12.1.1, Creator

a. *The standard defines the element `<dc:creator>`*

This element is supported in Excel 2010 and Excel 2013.

2.1.452 Section 12.1.2, Creation Date and Time

a. *The standard defines the element `<dc:date>`*

This element is not supported in Excel 2010 or Excel 2013.

2.1.453 Section 12.1.3, Creation Date and Time String

- a. *The standard defines the element <meta:date-string>, contained within the parent element <office:annotation>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <meta:date-string>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.454 Section 12.2, Number Format

- a. *The standard defines the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

- b. *The standard defines the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes. (1) On save, Excel uses the following mappings between the "buAutoNum" string values and the style:num-prefix, style:num-suffix, style:num-format, and style:num-letter-sync attributes in ODF:

(1.1) The string value "buAutoNum" equals the value "arabicPlain" is written as style:num-format equals the value "1".

(1.2) The string value "buAutoNum" values "circleNumWdBlackPlain" and "circleNumWdWhitePlain" are written as style:num-format equals the value "1" and style:num-letter-sync equals the value "true".

(1.3) The string value "buAutoNum" equals the value "arabicParenR" is written as style:num-format equals the value "1" and style:num-suffix equals the value ")".

(1.4) The string value "buAutoNum" equals the value "arabicPeriod" is written as style:num-format equals the value "1" and style:num-suffix equals the value ".".

(1.5) The string value "buAutoNum" equals the value "arabicParenBoth" is written as style:num-format equals the value "1", style:num-prefix equals the value "(", and style:num-suffix equals the value ")".

- (1.6) The string value "buAutoNum" equals the value "hindiNumParenR" is written as style:num-format equals the value "१ , २ , ३ , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.7) The string value "buAutoNum" equals the value "hindiNumPeriod" is written as style:num-format equals the value "१ , २ , ३ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- (1.8) The string value "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value " 1 , 2 , 3 , ..." and style:num-letter-sync equals the value "true".
- (1.9) The string value "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "① , ② , ③ , ..." and style:num-letter-sync equals the value "true".
- (1.10) The string value "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value " 1., 2., 3., ..." and style:num-letter-sync equals the value "true".
- (1.11) The string value "buAutoNum" equals the value "thaiNumParenR" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.12) The string value "buAutoNum" equals the value "thaiNumPeriod" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- (1.13) The string value "buAutoNum" equals the value "thaiNumParenBoth" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.14) The string value "buAutoNum" equals the value "alphaLcParenR" is written as style:num-format equals the value "a", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.15) The string value "buAutoNum" equals the value "alphaUcParenR" is written as style:num-format equals the value "A", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.16) The string value "buAutoNum" equals the value "alphaLcPeriod" is written as style:num-format equals the value "a", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- (1.17) The string value "buAutoNum" equals the value "alphaUcPeriod" is written as style:num-format equals the value "A", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- (1.18) The string value "buAutoNum" equals the value "alphaLcParenBoth" is written as style:num-format equals the value "a", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.19) The string value "buAutoNum" equals the value "alphaUcParenBoth" is written as style:num-format equals the value "A", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.20) The string value "buAutoNum" equals the value "romanLcParenR" is written as style:num-format equals the value "i" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.21) The string value "buAutoNum" equals the value "romanUcParenR" is written as style:num-format equals the value "I" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- (1.22) The string value "buAutoNum" equals the value "romanLcPeriod" is written as style:num-format equals the value "i" and style:num-suffix equals the value ".".

(1.23) The string value "buAutoNum" equals the value "romanUcPeriod" is written as style:num-format equals the value "I" and style:num-suffix equals the value ".".

(1.24) The string value "buAutoNum" equals the value "romanLcParenBoth" is written as style:num-format equals the value "i", style:num-prefix equals the value "(", and style:num-suffix equals the value ")".

(1.25) The string value "buAutoNum" equals the value "romanUcParenBoth" is written as style:num-format equals the value "I", style:num-prefix equals the value "(", and style:num-suffix equals the value ")".

(1.26) The string value "buAutoNum" equals the value "hebrew2Minus" is written as style:num-format equals the value "א , ב , ג , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

(1.27) The string value "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "أ , ب , ت , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

(1.28) The string value "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "أ , ب , ج , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".

(1.29) The string value "buAutoNum" equals the value "hindiAlphaPeriod" is written as style:num-format equals the value "अ , आ , इ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.30) The string value "buAutoNum" equals the value "hindiAlpha1Period" is written as style:num-format equals the value "क , ख , ग , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.31) The string value "buAutoNum" equals the value "thaiAlphaParenR" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.32) The string value "buAutoNum" equals the value "thaiAlphaPeriod" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.33) The string value "buAutoNum" equals the value "thaiAlphaParenBoth" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

(1.34) The string value "buAutoNum" equals the value "ea1ChsPlain", "ea1ChtPlain", and "ea1JpnKorPlain" are written as style:num-format equals the value "一 , 二 , 三 , 四..." and style:num-letter-sync equals the value "true".

(1.35) The string value "buAutoNum" equals the value "ea1ChsPeriod", "ea1ChtPeriod", and "ea1JpnKorPeriod" are written as style:num-format equals the value "一 , 二 , 三 , 四...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

(1.36) The string value "buAutoNum" equals the value "ea1JpnChsDbPeriod" is written as style:num-format equals the value "一 , 二 , 三 , 四 , ...", style:num-suffix equals the value ". " (double-byte period UNICODE FF0E), and style:num-letter-sync equals the value "true".

1. On read, the style:num-format, style:num-prefix, and style:num-suffix attributes are considered together to determine the "buAutoNum" value to use in OOXML. The style:num-format attribute is the key attribute and determines the default mapping if the prefix and suffix characters are not supported. The mapping is as follows:

(2.1) For style:num-format equals the value "1":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenR".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "arabicPeriod".

In all other cases where style:num-format equals the value "1", then "buAutoNum" equals the value "arabicPlain".

(2.2) For style:num-format equals the value "a":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenR".

In all other cases where style:num-format equals the value "a", then "buAutoNum" equals the value "alphaLcPeriod".

(2.3) For style:num-format equals the value "A":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaUcParenR".

In all other cases where style:num-format equals the value "A", then "buAutoNum" equals the value "alphaUcPeriod".

(2.4) For style:num-format equals the value "i":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenR".

In all other cases where style:num-format equals the value "i", then "buAutoNum" equals the value "romanLcPeriod".

(2.5) For style:num-format equals the value "I":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenR".

In all other cases where style:num-format equals the value "I", then "buAutoNum" equals the value "romanUcPeriod".

(2.6) In all cases where style:num-format equals the value "أ , ب , ت , ..." or style:num-format equals the value "i ", then "buAutoNum" equals the value "arabic1Minus".

(2.7) In all cases where style:num-format equals the value "أ , ب , ج , ...", then "buAutoNum" equals the value "arabic2Minus".

(2.8) In all cases where style:num-format equals the value "1,2,3,..." or style:num-format equals the value "1.", then "buAutoNum" equals the value "arabicDbPeriod".

(2.9) In all cases where style:num-format equals the value " 1 , 2 , 3 , ..." or style:num-format equals the value " 1 ", then "buAutoNum" equals the value "arabicDbPlain".

(2.10) In all cases where style:num-format equals the value "①,②,③,..." or style:num-format equals the value "①", then "buAutoNum" equals the value "circleNumDbPlain".

(2.11) For style:num-format equals the value "一 , 二 , 三 , 四 , ..." or "style:num-format equals the value "一":

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "ea1JpnKorPeriod".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ". " (double-byte period UNICODE FF0E), then "buAutoNum" equals the value "ea1JpnChsDbPeriod".

In all other cases where style:num-format equals the value "一 , 二 , 三 , 四 , ..." or "style:num-format equals the value "一", then "buAutoNum" equals the value "ea1JpnKorPlain".

(2.12) In all cases where style:num-format equals the value "א , ב , ג , ..." or style:num-format equals the value "א ", then "buAutoNum" equals the value "hebrew2Minus".

(2.13) In all cases where style:num-format equals the value "क , ख , ग , ..." or "क", "buAutoNum" equals the value "hindiAlpha1Period".

(2.14) In all cases where style:num-format equals the value "अ , आ , इ , ..." or "अ", "buAutoNum" equals the value "hindiAlphaPeriod".

(2.15) For style:num-format equals the value "१ , २ , ३ , ..." or style:num-format equals the value "१ ":

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "hindiNumParenR".

In all other cases where style:num-format equals the value "१ , २ , ३ , ..." or style:num-format equals the value "१ ", then "buAutoNum" equals the value "hindiNumPeriod".

(2.16) For style:num-format equals the value "๓ , ๔ , ๕ , ...":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiAlphaParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiAlphaPeriod".

In all other cases where style:num-format equals the value "๓ , ๔ , ๕ , ..." , then "buAutoNum" equals the value "thaiAlphaParenR".

(2.17) For style:num-format equals the value "๑ , ๒ , ๓ , ...":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiNumParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiNumPeriod".

In all other cases where style:num-format equals the value "๑ , ๒ , ๓ , ...", then "buAutoNum" equals the value "thaiNumParenR".

(2.18) If style:num-format equals the value "empty", the OOXML property "buNone" is set.

(2.19) If style:num-format contains anything other than what is specified previously, "buAutoNum" equals the value "arabicPlain".

- c. *The standard defines the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:measure>
 - <draw:text-box>
 - <draw:frame>
 - <draw:custom-shape>
1. On read, the style:num-format, style:num-prefix, and style:num-suffix attributes are considered together to determine the "buAutoNum" value to use in OOXML. style:num-format is the key attribute and determines the default mapping if the prefix and suffix characters are not supported. The mapping is as follows:

1.1) For style:num-format equals the value "1":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "arabicParenR".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "arabicPeriod".

In all other cases where style:num-format equals the value "1", then "buAutoNum" equals the value "arabicPlain".

1.2) For style:num-format equals the value "a":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaLcParenR".

In all other cases where style:num-format equals the value "a", then "buAutoNum" equals the value "alphaLcPeriod".

1.3) For style:num-format equals the value "A":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "alphaUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ""), then "buAutoNum" equals the value "alphaUcParenR".

In all other cases where style:num-format equals the value "A", then "buAutoNum" equals the value "alphaUcPeriod".

1.4) For style:num-format equals the value "i":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanLcParenR".

In all other cases where style:num-format equals the value "i", then "buAutoNum" equals the value "romanLcPeriod".

1.5) For style:num-format equals the value "I":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "romanUcParenR".

In all other cases where style:num-format equals the value "I", then "buAutoNum" equals the value "romanUcPeriod".

1.6) In all cases where style:num-format equals the value "أ , ب , ت , ..." or style:num-format equals the value "ا ", then "buAutoNum" equals the value "arabic1Minus".

1.7) In all cases where style:num-format equals the value "أ , ب , ج , ..." , then "buAutoNum" equals the value "arabic2Minus".

1.8) In all cases where style:num-format equals the value "1.,2.,3,..." or style:num-format equals the value "1.", then "buAutoNum" equals the value "arabicDbPeriod".

1.9) In all cases where style:num-format equals the value "1,2,3,..." or style:num-format equals the value "1 ", then "buAutoNum" equals the value "arabicDbPlain".

1.10) In all cases where style:num-format equals the value "①,②,③,..." or style:num-format equals the value "①", then "buAutoNum" equals the value "circleNumDbPlain".

1.11) For style:num-format equals the value "一, 二, 三, 四, ..." or "style:num-format equals the value "一":

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "ea1JpnKorPeriod".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ". " (double-byte period UNICODE FF0E), then "buAutoNum" equals the value "ea1JpnChsDbPeriod".

In all other cases where style:num-format equals the value "一, 二, 三, 四, ..." or "style:num-format equals the value "一", then "buAutoNum" equals the value "ea1JpnKorPlain".

1.12) In all cases where style:num-format equals the value "א , ב , ג , ..." or style:num-format equals the value "א ", then "buAutoNum" equals the value "hebrew2Minus".

1.13) In all cases where style:num-format equals the value "क , ख , ग , ..." or "क", "buAutoNum" equals the value "hindiAlpha1Period".

1.14) In all cases where style:num-format equals the value "अ, आ, इ, ..." or "अ", "buAutoNum" equals the value "hindiAlphaPeriod".

1.15) For style:num-format equals the value "१, २, ३, ..." or style:num-format equals the value "१":

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "hindiNumParenR".

In all other cases where style:num-format equals the value "१, २, ३, ..." or style:num-format equals the value "१", then "buAutoNum" equals the value "hindiNumPeriod".

1.16) For style:num-format equals the value "၈, ၉, ၁၀":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiAlphaParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiAlphaPeriod".

In all other cases where style:num-format equals the value "၈, ၉, ၁၀, ...", then "buAutoNum" equals the value "thaiAlphaParenR".

1.17) For style:num-format equals the value "๑, ๒, ๓, ...":

If style:num-prefix equals the value "(" AND style:num-suffix equals the value ")", then "buAutoNum" equals the value "thaiNumParenBoth".

If style:num-prefix equals the value empty or missing AND style:num-suffix equals the value ".", then "buAutoNum" equals the value "thaiNumPeriod".

In all other cases where style:num-format equals the value "๑, ๒, ๓, ...", then "buAutoNum" equals the value "thaiNumParenR".

1.18) If style:num-format equals the value empty, the OOXML property "buNone" is set.

1.19) If style:num-format contains anything other than what is specified previously, "buAutoNum" equals the value "arabicPlain".

On write, the following mappings are used between the "buAutoNum" string values used in OOXML and the style:num-prefix, style:num-suffix, style:num-format, and style:num-letter-sync attributes in ODF:

2.1) "buAutoNum" equals the value "arabicPlain" is written as style:num-format equals the value "1".

2.2) "buAutoNum" values "circleNumWdBlackPlain" and "circleNumWdWhitePlain" are written as style:num-format equals the value "1" and style:num-letter-sync equals the value "true".

2.3) "buAutoNum" equals the value "arabicParenR" is written as style:num-format equals the value "1" and style:num-suffix equals the value ")".

2.4) "buAutoNum" equals the value "arabicPeriod" is written as style:num-format equals the value "1" and style:num-suffix equals the value ".".

2.5) "buAutoNum" equals the value "arabicParenBoth" is written as style:num-format equals the value "1" and style:num-prefix equals the value "(", style:num-suffix equals the value ")".

2.6) "buAutoNum" equals the value "hindiNumParenR" is written as style:num-format equals the value "१, २, ३, ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".

- 2.7) "buAutoNum" equals the value "hindiNumPeriod" is written as style:num-format equals the value "१ , २ , ३ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.8) "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value "1 , 2 , 3 , ..." and style:num-letter-sync equals the value "true".
- 2.9) "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "①, ②, ③, ..." and style:num-letter-sync equals the value "true".
- 2.10) "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value "1., 2., 3., ..." and style:num-letter-sync equals the value "true".
- 2.11) "buAutoNum" equals the value "thaiNumParenR" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.12) "buAutoNum" equals the value "thaiNumPeriod" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.13) "buAutoNum" equals the value "thaiNumParenBoth" is written as style:num-format equals the value "๑ , ๒ , ๓ , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.14) "buAutoNum" equals the value "alphaLcParenR" is written as style:num-format equals the value "a", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.15) "buAutoNum" equals the value "alphaUcParenR" is written as style:num-format equals the value "A", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.16) "buAutoNum" equals the value "alphaLcPeriod" is written as style:num-format equals the value "a", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.17) "buAutoNum" equals the value "alphaUcPeriod" is written as style:num-format equals the value "A", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.18) "buAutoNum" equals the value "alphaLcParenBoth" is written as style:num-format equals the value "a", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.19) "buAutoNum" equals the value "alphaUcParenBoth" is written as style:num-format equals the value "A", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.20) "buAutoNum" equals the value "romanLcParenR" is written as style:num-format equals the value "i" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.21) "buAutoNum" equals the value "romanUcParenR" is written as style:num-format equals the value "I" and style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.22) "buAutoNum" equals the value "romanLcPeriod" is written as style:num-format equals the value "i" and style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.23) "buAutoNum" equals the value "romanUcPeriod" is written as style:num-format equals the value "I" and style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".

- 2.24) "buAutoNum" equals the value "romanLcParenBoth" is written as style:num-format equals the value "i", style:num-prefix equals the value "(", and style:num-suffix equals the value ")".
- 2.25) "buAutoNum" equals the value "romanUcParenBoth" is written as style:num-format equals the value "I", style:num-prefix equals the value "(", and style:num-suffix equals the value ")".
- 2.26) "buAutoNum" equals the value "hebrew2Minus" is written as style:num-format equals the value "א , ב , ג , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".
- 2.27) "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "أ , ب , ت , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".
- 2.28) "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "أ , ب , ج , ...", style:num-suffix equals the value "-", and style:num-letter-sync equals the value "true".
- 2.29) "buAutoNum" equals the value "hindiAlphaPeriod" is written as style:num-format equals the value "अ , आ , इ , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.30) "buAutoNum" equals the value "hindiAlpha1Period" is written as style:num-format equals the value "क , ख , ग , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.31) "buAutoNum" equals the value "thaiAlphaParenR" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.32) "buAutoNum" equals the value "thaiAlphaPeriod" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.33) "buAutoNum" equals the value "thaiAlphaParenBoth" is written as style:num-format equals the value "ก , ข , ค , ...", style:num-prefix equals the value "(", style:num-suffix equals the value ")", and style:num-letter-sync equals the value "true".
- 2.34) "buAutoNum" equals the values "ea1ChsPlain", "ea1ChtPlain", and "ea1JpnKorPlain" are written as style:num-format equals the value "一 , 二 , 三 , 四..." and style:num-letter-sync equals the value "true".
- 2.35) "buAutoNum" equals the values "ea1ChsPeriod", "ea1ChtPeriod", and "ea1JpnKorPeriod" are written as style:num-format equals the value "一 , 二 , 三 , 四...", style:num-suffix equals the value ".", and style:num-letter-sync equals the value "true".
- 2.36) "buAutoNum" equals the value "ea1JpnChsDbPeriod" is written as style:num-format equals the value "一 , 二 , 三 , 四 , ...", style:num-suffix equals the value ". " (double-byte period UNICODE FF0E), and style:num-letter-sync equals the value "true".

2.1.455 Section 12.2.1, Prefix and Suffix

- a. *The standard defines the attribute style:num-prefix*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:num-suffix*

This attribute is supported in Word 2010 and Word 2013.

- c. This is not supported in Excel 2010 or Excel 2013.
- d. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

1. On load, the value of the style:num-prefix attribute is considered in combination with the values of the style:num-format and style:num-suffix attributes to determine the "buAutoNum" value used. The only prefix character that is converted is "(".
2. On save, the following "buAutoNum" values are written as style:num-prefix equals the value "(":
 - "alphaLcParenBoth"
 - "alphaUcParenBoth"
 - "arabicParenBoth"
 - "romanLcParenBoth"
 - "romanUcParenBoth"
 - "thaiAlphaParenBoth"
 - "thaiNumParenBoth"

For all other values, style-num-prefix is not written.

- e. *The standard defines the attribute style:num-suffix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

1. On load, the value of the style:num-suffix attribute is considered in combination with the values of the style:num-format and style:num-prefix attributes to determine the "buAutoNum" value used.
2. On save, the following "buAutoNum" values are written as style:num-suffix equals the value ")":

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaUcParenBoth"
- "alphaUcParenR"
- "arabicParenBoth"
- "arabicParenR"
- "hindiNumParenR"
- "romanLcParenBoth"
- "romanLcParenR"
- "romanUcParenBoth"
- "romanUcParenR"
- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiNumParenBoth"
- "thaiNumParenR"

3. On save, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value ".":

- "alphaLcPeriod"
- "alphaUcPeriod"
- "arabicPeriod"
- "ea1ChsPeriod"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnKorPeriod"
- "hindiAlpha1Period"
- "hindiAlphaPeriod"
- "thaiNumPeriod"
- "hindiNumPeriod"
- "romanLcPeriod"
- "romanUcPeriod"
- "thaiAlphaPeriod"

4. On save, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value "-":

- "arabic1Minus"
- "arabic2Minus"
- "hebrew2Minus"

5. On save, "buAutoNum" equals the value "ea1JpnChsDbPeriod" is written as style:num-suffix equals the value ". " (double byte UNICODE character FF0E).

f. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On load, the value of the style:num-prefix attribute is considered in combination with values of the style:num-format and style:num-suffix attributes to determine the "buAutoNum" value used. The only prefix character that may be converted is "(".

On save, the following "buAutoNum" values from OOXML are written as style-num-prefix equals the value "(":

- "alphaLcParenBoth"
- "alphaUcParenBoth"
- "arabicParenBoth"
- "romanLcParenBoth"
- "romanUcParenBoth"
- "thaiAlphaParenBoth"
- "thaiNumParenBoth"

For all other values, style-num-prefix is not written.

- g. *The standard defines the attribute style:num-suffix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

1. On write, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value ")":

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaUcParenBoth"
- "alphaUcParenR"
- "arabicParenBoth"
- "arabicParenR"
- "hindiNumParenR"
- "romanLcParenBoth"
- "romanLcParenR"
- "romanUcParenBoth"
- "romanUcParenR"
- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiNumParenBoth"
- "thaiNumParenR".

2. On write, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value ".":
 - "alphaLcPeriod"
 - "alphaUcPeriod"
 - "arabicPeriod"
 - "ea1ChsPeriod"
 - "ea1ChtPeriod"
 - "ea1ChtPlain"
 - "ea1JpnKorPeriod"
 - "hindiAlpha1Period"
 - "hindiAlphaPeriod"
 - "thaiNumPeriod"
 - "hindiNumPeriod"
 - "romanLcPeriod"
 - "romanUcPeriod"
 - "thaiAlphaPeriod"
3. On write, the following "buAutoNum" values from OOXML are written as style:num-suffix equals the value "-":
 - "arabic1Minus"
 - "arabic2Minus"
 - "hebrew2Minus"
4. On write, value "buAutoNum" equals "ea1JpnChsDbPeriod" is written as style:num-suffix equals the value ". " (double byte UNICODE character FF0E).
5. On read, the value of style:num-suffix is considered in combination with the values of the style:num-format and style:num-prefix attributes to determine the "buAutoNum" value used.

2.1.456 Section 12.2.2, Format Specification

- a. *The standard defines the property "[string]", contained within the attribute style:num-format*

This property is supported in Word 2010 and Word 2013.

1. On load, numbering formats that are not familiar to Word are displayed using the Arabic numeral format (1, 2, 3...).
2. On save and load, the following strings are also supported by Word as numbering formats:

ア, イ, ウ, ...

ア, イ, ウ, ...

أ, ب, ج, ...

أ, ب, ت, ...

One, Two, Three, ...

*, †, ‡, ...

一, 十, 一〇〇(簡), ...

一, 十, 一百 (簡), ...

壹, 貳, 參, ...

ㄅ, ㄆ, ㄇ, ...

①,②,③, ...
①,②,③, ...
1,2,3, ...
(1), (2), (3), ...
1, 2, 3, ...
01, 02, 03, ...
가, 나, 다, ...
κ, λ, μ, ν, ...
κ, λ, μ, ν, ...
1, A, B, ...
अ, आ, इ, ...
□□, □□, □□□, ...
१, २, ३, ...
क, ख, ग, ...
一, 一〇, 一〇〇, ...
(一), (二), (三), ...
壹, 貳, 參, ...
甲,乙,丙, ...
子,丑,寅, ...
甲子, 乙丑, 丙寅, ...
イ, ロ, ハ, ...
イ, ロ, ハ, ...
一, 二, 三 ...
一, 二, 三,万, ...
壹, 貳, 參, ...
일, 이, 삼, ...
일,일영,일영영, ...
一, 一零, 一零零, ...
하나, 둘,셋, ...
- 1 -, - 2 -, - 3 -, ...
1st, 2nd, 3rd, ...
First, Second, Third, ...

а, б, в, ...

A,Б,В, ...

一, 十, 一〇〇(繁), ...

一, 十, 一百 (繁), ...

一, 一〇, 一〇〇(繁), ...

□□□□, ஸ ஐ ங , ஸ ா ழ , ...

π , ϖ , ϑ , ...

๑ ,๒ ,๓ , ...

A, Ç, Ğ, ...

a, ç, ğ, ...

A,Й,Ъ, ...

a,й,ъ, ...

A, B, Γ, ...

α, β, γ, ...

001,002, 003, ...

0001,0002, 0003, ...

00001,00002, 00003, ...

- b. *The standard defines the property "1", contained within the attribute style:num-format*
This property is supported in Word 2010 and Word 2013.
- c. *The standard defines the property "A", contained within the attribute style:num-format*
This property is supported in Word 2010 and Word 2013.
- d. *The standard defines the property "a", contained within the attribute style:num-format*
This property is supported in Word 2010 and Word 2013.
- e. *The standard defines the property "i", contained within the attribute style:num-format*
This property is supported in Word 2010 and Word 2013.
- f. *The standard defines the property "I", contained within the attribute style:num-format*
This property is supported in Word 2010 and Word 2013.
- g. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*
- h. This is not supported in Excel 2010 or Excel 2013.
- i. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes.

1. On load, the value of the style:num-format attribute is considered in combination with the values of the style:num-prefix and style:num-suffix attributes to determine the "buAutoNum" value used.
2. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "a":
 - "alphaLcParenBoth"
 - "alphaLcParenR"
 - "alphaLcPeriod"
3. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "A":
 - "alphaUcParenBoth"
 - "AlphaUcParenR"
 - "AlphaUcPeriod"
4. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "1":
 - "arabicParenBoth"
 - "arabicParenR"
 - "arabicPeriod"
 - "arabicPlain"
 - "circleNumWdBlackPlain"
 - "circleNumWdWhitePlain"
5. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "一, 二, 三, 四, ...":
 - "ea1ChsPeriod"
 - "ea1ChsPlain"
 - "ea1ChtPeriod"
 - "ea1ChtPlain"
 - "ea1JpnChsDbPeriod"
 - "ea1JpnKorPeriod"
 - "ea1JpnKorPlain"
6. On save, "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "ا , ب , ت , ...".
7. On save, "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "أ , ب , ج , ...".
8. On save, "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value "1., 2., 3., ...".
9. On save, "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value "1 , 2 , 3 , ...".

10. On save, "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "①, ②, ③, ...".
 11. On save, "buAutoNum" equals the value "hebrew2Minus" is written as style:num-format equals the value "א, ב, ג, ...".
 12. On save, "buAutoNum" equals the value "hindiAlpha1Period" is written as style:num-format equals the value "क, ख, ग, ...".
 13. On save, "buAutoNum" equals the value "hindiAlphaPeriod" is written as style:num-format equals the value "अ, आ, इ, ...".
 14. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "१, २, ३, ...":
 - "hindiNumParenR"
 - "hindiNumPeriod"
 15. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "i":
 - "romanLcParenBoth"
 - "romanLcParenR"
 - "RomanLcPeriod"
 16. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "I":
 - "romanUcParenBoth"
 - "romanUcParenR"
 - "RomanUcPeriod"
 17. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "๓, ๔, ๕, ...":
 - "thaiAlphaParenBoth"
 - "thaiAlphaParenR"
 - "thaiAlphaPeriod"
 18. On save, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "๑, ๒, ๓, ...":
 - "thaiNumParenBoth"
 - "thaiNumParenR"
 - "thaiNumPeriod"
- j. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

1. On read, the value of the style:num-format attribute is considered in combination with the values of the style:num-prefix and style:num-suffix attributes to determine the "buAutoNum" value used.
2. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "a":
 - "alphaLcParenBoth"
 - "alphaLcParenR"
 - "alphaLcPeriod"
3. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "A":
 - "alphaUcParenBoth"
 - "AlphaUcParenR"
 - "AlphaUcPeriod"
4. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "1":
 - "arabicParenBoth"
 - "arabicParenR"
 - "arabicPeriod"
 - "arabicPlain"
 - "circleNumWdBlackPlain"
 - "circleNumWdWhitePlain"
5. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "一, 二, 三, 四, ...":
 - "ea1ChsPeriod"
 - "ea1ChsPlain"
 - "ea1ChtPeriod"
 - "ea1ChtPlain"
 - "ea1JpnChsDbPeriod"
 - "ea1JpnKorPeriod"
 - "ea1JpnKorPlain"
6. On write, "buAutoNum" equals the value "arabic1Minus" is written as style:num-format equals the value "١ , ٢ , ٣ , ...".
7. On write, "buAutoNum" equals the value "arabic2Minus" is written as style:num-format equals the value "١٠ , ١١ , ١٢ , ...".
8. On write, "buAutoNum" equals the value "arabicDbPeriod" is written as style:num-format equals the value "1., 2., 3., ...".
9. On write, "buAutoNum" equals the value "arabicDbPlain" is written as style:num-format equals the value "1, 2, 3, ...".
10. On write, "buAutoNum" equals the value "circleNumDbPlain" is written as style:num-format equals the value "①, ②, ③, ...".
11. On write, "buAutoNum" equals the value "hebrew2Minus" is written as style:num-format equals the value "א , ב , ג , ...".
12. On write, "buAutoNum" equals the value "hindiAlpha1Period" is written as style:num-format equals the value "क , ख , ग , ...".
13. On write, "buAutoNum" equals the value "hindiAlphaPeriod" is written as style:num-format equals the value "अ , आ , इ , ...".
14. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "१ , २ , ३ , ...":
 - "hindiNumParenR"
 - "hindiNumPeriod"

15. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "i":
- "romanLcParenBoth"
 - "romanLcParenR"
 - "RomanLcPeriod"
16. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "I":
- "romanUcParenBoth"
 - "romanUcParenR"
 - "RomanUcPeriod"
17. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "๓ , ๔ , ๕ , ...":
- "thaiAlphaParenBoth"
 - "thaiAlphaParenR"
 - "thaiAlphaPeriod"
18. On write, the following "buAutoNum" values from OOXML are written as style:num-format equals the value "๑ , ๒ , ๓ , ...":
- "thaiNumParenBoth"
 - "thaiNumParenR",
 - "thaiNumPeriod"

2.1.457 Section 12.2.3, Letter Synchronization in Number Formats

- a. *The standard defines the attribute style:num-letter-sync*

This attribute is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the property "false", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- d. *The standard defines the property "true", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes. 1) On load, this value is ignored.

1. On save, this value is written for the following "buAutoNum" values:

- "alphaLcParenBoth"
- "alphaLcParenR"
- "alphaLcPeriod"
- "alphaUcParenBoth"
- "alphaUcParenR"
- "alphaUcPeriod"
- "arabic1Minus"
- "arabic2Minus"
- "arabicDbPeriod"
- "arabicDbPlain"
- "circleNumDbPlain"
- "circleNumWdBlackPlain"
- "circleNumWdWhitePlain"
- "ea1ChsPeriod"
- "ea1ChsPlain"
- "ea1ChtPeriod"
- "ea1ChtPlain"
- "ea1JpnChsDbPeriod"
- "ea1JpnKorPeriod"
- "ea1JpnKorPlain"
- "hebrew2Minus"
- "hindiAlpha1Period"
- "hindiAlphaPeriod"
- "hindiNumParenR"
- "hindiNumPeriod"
- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiAlphaPeriod"
- "thaiNumParenBoth"
- "thaiNumParenR"
- "thaiNumPeriod"

- e. *The standard defines the property "false", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:measure>
 - <draw:text-box>
 - <draw:frame>
 - <draw:custom-shape>
- f. *The standard defines the property "true", contained within the attribute style:num-letter-sync, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:measure>
 - <draw:text-box>
 - <draw:frame>
 - <draw:custom-shape>
1. On read, this property is ignored.
 2. On write, this property is written for the following "buAutoNum" values:
 - "alphaLcParenBoth"
 - "alphaLcParenR"
 - "alphaLcPeriod"
 - "alphaUcParenBoth"
 - "alphaUcParenR"
 - "alphaUcPeriod"
 - "arabic1Minus"
 - "arabic2Minus"
 - "arabicDbPeriod"
 - "arabicDbPlain"
 - "circleNumDbPlain"
 - "circleNumWdBlackPlain"
 - "circleNumWdWhitePlain"
 - "ea1ChsPeriod"
 - "ea1ChsPlain"
 - "ea1ChtPeriod"
 - "ea1ChtPlain"
 - "ea1JpnChsDbPeriod"
 - "ea1JpnKorPeriod"
 - "ea1JpnKorPlain"
 - "hebrew2Minus"

- "hindiAlpha1Period"
- "hindiAlphaPeriod"
- "hindiNumParenR"
- "hindiNumPeriod"
- "thaiAlphaParenBoth"
- "thaiAlphaParenR"
- "thaiAlphaPeriod"
- "thaiNumParenBoth"
- "thaiNumParenR"
- "thaiNumPeriod"

2.1.458 Section 12.3, Change Tracking Metadata

- The standard defines the element <office:change-info>*
This element is not supported in Word 2010 or Word 2013.
- This is not supported in Excel 2010 or Excel 2013.
- The standard defines the element <office:change-info>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.459 Section 12.4, Event Listener Tables

- The standard defines the element <office:event-listeners>*
This element is not supported in Word 2010 or Word 2013.
- This is not supported in Excel 2010 or Excel 2013.
- The standard defines the element <office:event-listeners>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- The standard defines the element <presentation:event-listener>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- The standard defines the element <script:event-listener>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.460 Section 12.4.1, Event Listener

- The standard defines the element <office:event-listener>*
This element is not supported in Word 2010 or Word 2013.
- This is not supported in Excel 2010 or Excel 2013.
- The standard defines the attribute script:event-name, contained within the element <presentation:event-listener>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
Only the dom:click and dom:mouseover events are loaded/saved by PowerPoint (See section 9.9). Other events are not supported.

2.1.461 Section 12.4.2, Event Types

- a. This is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the attribute `script:language`, contained within the element `<presentation:event-listener>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the attribute `script:macro-name`, contained within the element `<presentation:event-listener>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.462 Section 12.5, Mathematical Content

- a. *The standard defines the attribute `display`, contained within the element `<math>`*

This attribute is supported in Word 2010 and Word 2013.

On load, Word does not read the `display` attribute in a `<math>` element.

On save, Word writes the `display` attribute in a `<math>` element.

- b. *The standard defines the element `<math:math>`*

This element is supported in Word 2010 and Word 2013.

- 1. On load, alignment of text around formula objects may be lost.
- 2. On load, the MathML namespace qualifier must be present for math elements, and may be present for attributes.
- 3. On save, only bold and italics text properties are supported.
- 4. On save, Word equations that contain images are lost, and their images are also lost.
- 5. On save, if a Word equation contains OLE objects, the Word equation and the OLE objects it contains are lost.
- 6. On save, Word writes the MathML namespace qualifier for elements but does not write the namespace qualifier for attributes.

This element is supported in Word 2010 and Word 2013.

On load, Word reads only presentation MathML elements within the `<math>` element. Word does not read any of the attributes of the math element.

On save, Word writes only presentation MathML elements within the `<math>` element.

- c. *The standard defines the attribute `display`, contained within the element `<math>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel does not read the `display` attribute in a `<math>` element.

On save, Excel writes the `display` attribute in a `<math>` element.

- d. *The standard defines the element `<math:math>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads only presentation MathML elements within the `<math>` element. Excel does not read any of the attributes of the math element.

On save, Excel writes only presentation MathML elements within the $<math>$ element.

- e. *The standard defines the attribute $display$, contained within the element $<math>$*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint does not read the $display$ attribute in a $<math>$ element.

On save, PowerPoint writes the $display$ attribute in a $<math>$ element.

- f. *The standard defines the element $<math:math>$*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads only presentation MathML elements within the $<math>$ element. PowerPoint does not read any of the attributes of the $math$ element.

On save, PowerPoint writes only presentation MathML elements within the $<math>$ element.

2.1.463 Section 12.5 (MathML 2.0 Section 3.2), Token Elements

a.

1. On load, Word recognizes MathML as a function if all the following are true:

(a) the parent wrapper is an $<mrow>$ element

(b) there are three child elements

(c) the second child element is a $<mo>$ element that contains the function apply character $<U+2061>$

2. On save, Word uses the $<mo>$ element for math characters that are considered operators, including the function apply character $<U+2061>$.
3. On save, Word uses the $<mn>$ element only for numbers that are composed of the digits 0-9. Word also saves periods and commas that are used as delimiters in the $<mn>$ element.
4. On save, Word separates math characters into individual $<mi>$ elements unless they are function names in which case the entire function name is contained in a single $<mi>$ element.

2.1.464 Section 12.5 (MathML 2.0 Section 3.2.3), Identifier (mi)

- a. *The standard defines the element $<mi>$*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word recognizes MathML as a function if:

(a) the parent wrapper is an $<mrow>$ element

(b) there are three child elements, and

(c) the second child element is an $<mo>$ element that contains the function apply character, $<U+2061>$.

On save, MathML in Word separates the text that was contained in $<mi>$ element tags into single characters unless the identifier is a function name.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute $class$, contained within the element $<mi>$*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute color, contained within the element <mi>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the color attribute in an <mi> element. On save, OfficeArt Math in Word does not write the color attribute in an <mi> element.

- d. *The standard defines the attribute fontfamily, contained within the element <mi>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute fontsize, contained within the element <mi>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the attribute fontstyle, contained within the element <mi>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the fontstyle attribute in an <mi> element. On save, OfficeArt Math in Word does not write the fontstyle attribute in an <mi> element.

- g. *The standard defines the attribute fontweight, contained within the element <mi>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the fontweight attribute in an <mi> element. On save, OfficeArt Math in Word does not write the fontweight attribute in an <mi> element.

- h. *The standard defines the attribute id, contained within the element <mi>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- i. *The standard defines the attribute mathbackground, contained within the element <mi>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- j. *The standard defines the attribute mathcolor, contained within the element <mi>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the mathcolor attribute in an <mi> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mi> element.

- k. *The standard defines the attribute `mathsize`, contained within the element `<mi>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- l. *The standard defines the attribute `mathvariant`, contained within the element `<mi>`*
This attribute is supported in MathML in Word 2010 and MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the `mathvariant` attribute in an `<mi>` element.
On save, OfficeArt Math in Word writes only the 'normal' value to distinguish upright characters from math italics. All math alphanumeric characters are written using Unicode code points.
- m. *The standard defines the property "(everything else)", contained within the attribute `mathvariant`, contained within the element `<mi>`*
This property is supported in MathML in Word 2010 and MathML in Word 2013.
This property is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the `mathvariant` attribute in an `<mi>` element.
On save, OfficeArt Math in Word does not write the `mathvariant` attribute in an `<mi>` element for the value of '(everything else)'.
- n. *The standard defines the property "monospace", contained within the attribute `mathvariant`, contained within the element `<mi>`*
This property is not supported in Word 2010 or Word 2013.
- o. *The standard defines the property "normal", contained within the attribute `mathvariant`, contained within the element `<mi>`*
This property is supported in Word 2010 and Word 2013.
- p. *The standard defines the attribute `style`, contained within the element `<mi>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- q. *The standard defines the attribute `xref`, contained within the element `<mi>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- r. *The standard defines the element `<mi>`*
This element is supported in Excel 2010 and Excel 2013.
- s. *The standard defines the attribute `class`, contained within the element `<mi>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- t. *The standard defines the attribute `color`, contained within the element `<mi>`*
This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the color attribute in an <mi> element. On save, Excel does not write the color attribute in an <mi> element.

- u. *The standard defines the attribute fontfamily, contained within the element <mi>*

This attribute is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the attribute fontsize, contained within the element <mi>*

This attribute is not supported in Excel 2010 or Excel 2013.

- w. *The standard defines the attribute fontstyle, contained within the element <mi>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontstyle attribute in an <mi> element. On save, Excel does not write the fontstyle attribute in an <mi> element.

- x. *The standard defines the attribute fontweight, contained within the element <mi>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontweight attribute in an <mi> element. On save, Excel does not write the fontweight attribute in an <mi> element.

- y. *The standard defines the attribute id, contained within the element <mi>*

This attribute is not supported in Excel 2010 or Excel 2013.

- z. *The standard defines the attribute mathbackground, contained within the element <mi>*

This attribute is not supported in Excel 2010 or Excel 2013.

- aa. *The standard defines the attribute mathcolor, contained within the element <mi>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathcolor attribute in an <mi> element. On save, Excel does not write the mathcolor attribute in an <mi> element.

- bb. *The standard defines the attribute mathsize, contained within the element <mi>*

This attribute is not supported in Excel 2010 or Excel 2013.

- cc. *The standard defines the attribute mathvariant, contained within the element <mi>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathvariant attribute in an <mi> element.

On save, Excel writes only the 'normal' value to distinguish upright characters from math italics. All math alphanumeric characters are written using Unicode code points.

- dd. *The standard defines the property "(everything else)", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathvariant attribute in an <mi> element.

On save, Excel does not write the mathvariant attribute in an <mi> element for the value of '(everything else)'.

ee. *The standard defines the property "normal", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in Excel 2010 and Excel 2013.

ff. *The standard defines the attribute style, contained within the element <mi>*

This attribute is not supported in Excel 2010 or Excel 2013.

gg. *The standard defines the attribute xref, contained within the element <mi>*

This attribute is not supported in Excel 2010 or Excel 2013.

hh. *The standard defines the element <mi>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

ii. *The standard defines the attribute class, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

jj. *The standard defines the attribute color, contained within the element <mi>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the color attribute in an <mi> element. On save, PowerPoint does not write the color attribute in an <mi> element.

kk. *The standard defines the attribute fontfamily, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ll. *The standard defines the attribute fontsize, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

mm. *The standard defines the attribute fontstyle, contained within the element <mi>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontstyle attribute in an <mi> element. On save, PowerPoint does not write the fontstyle attribute in an <mi> element.

nn. *The standard defines the attribute fontweight, contained within the element <mi>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontweight attribute in an <mi> element. On save, PowerPoint does not write the fontweight attribute in an <mi> element.

oo. *The standard defines the attribute id, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

pp. *The standard defines the attribute mathbackground, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

qq. *The standard defines the attribute mathcolor, contained within the element <mi>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathcolor attribute in an <mi> element. On save, PowerPoint does not write the mathcolor attribute in an <mi> element.

rr. *The standard defines the attribute mathsize, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ss. *The standard defines the attribute mathvariant, contained within the element <mi>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathvariant attribute in an <mi> element.

On save, PowerPoint writes only the 'normal' value to distinguish upright characters from math italics. All math alphanumeric characters are written using Unicode code points.

tt. *The standard defines the property "(everything else)", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathvariant attribute in an <mi> element.

On save, PowerPoint does not write the mathvariant attribute in an <mi> element for the value of '(everything else)'.

uu. *The standard defines the property "normal", contained within the attribute mathvariant, contained within the element <mi>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

vv. *The standard defines the attribute style, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ww. *The standard defines the attribute xref, contained within the element <mi>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.465 Section 12.5 (MathML 2.0 Section 3.2.4), Number (mn)

a. *The standard defines the element <mn>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

MathML in Word supports only numbers composed of the digits 0-9 for the <mn> element. On load, numbers containing other characters, such as roman numerals and hexadecimal numbers, may be interpreted differently than was intended.

On save, the <mn> element is used only for numbers that are composed of the digits 0-9. Periods and commas that are used as delimiters are also saved in the <mn> element.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

b. *The standard defines the attribute class, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

c. *The standard defines the attribute color, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the color attribute in an <mn> element. On save, OfficeArt Math in Word does not write the color attribute in an <mn> element.

- d. *The standard defines the attribute fontfamily, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute fontsize, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the attribute fontstyle, contained within the element <mn>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the fontstyle attribute in an <mn> element. On save, OfficeArt Math in Word does not write the fontstyle attribute in an <mn> element.

- g. *The standard defines the attribute fontweight, contained within the element <mn>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the fontweight attribute in an <mn> element. On save, OfficeArt Math in Word does not write the fontweight attribute in an <mn> element.

- h. *The standard defines the attribute id, contained within the element <mn>*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute mathbackground, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- j. *The standard defines the attribute mathcolor, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the mathcolor attribute in an <mn> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mn> element.

- k. *The standard defines the attribute mathsize, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- l. *The standard defines the attribute mathvariant, contained within the element <mn>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word reads the mathvariant attribute in an <mn> element.

On save, MathML in Word does not write the mathvariant attribute in an <mn> element.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the mathvariant attribute in an <mn> element.

On save, OfficeArt Math in Word does not write the mathvariant attribute in an <mn> element. All math alphanumeric characters are written using Unicode code points.

- m. *The standard defines the property "(everything else)", contained within the attribute mathvariant, contained within the element <mn>*

This property is supported in Word 2010 and Word 2013.

- n. *The standard defines the property "monospace", contained within the attribute mathvariant, contained within the element <mn>*

This property is not supported in Word 2010 or Word 2013.

- o. *The standard defines the attribute style, contained within the element <mn>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- p. *The standard defines the attribute xref, contained within the element <mn>*

This attribute is not supported in Word 2010 or Word 2013.

- q. *The standard defines the element <mn>*

This element is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the attribute class, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- s. *The standard defines the attribute color, contained within the element <mn>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the color attribute in an <mn> element. On save, Excel does not write the color attribute in an <mn> element.

- t. *The standard defines the attribute fontfamily, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- u. *The standard defines the attribute fontsize, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the attribute fontstyle, contained within the element <mn>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontstyle attribute in an <mn> element. On save, Excel does not write the fontstyle attribute in an <mn> element.

- w. *The standard defines the attribute fontweight, contained within the element <mn>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontweight attribute in an <mn> element. On save, Excel does not write the fontweight attribute in an <mn> element.

- x. *The standard defines the attribute id, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- y. *The standard defines the attribute mathbackground, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- z. *The standard defines the attribute mathcolor, contained within the element <mn>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathcolor attribute in an <mn> element. On save, Excel does not write the mathcolor attribute in an <mn> element.

- aa. *The standard defines the attribute mathsize, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- bb. *The standard defines the attribute mathvariant, contained within the element <mn>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathvariant attribute in an <mn> element.

On save, Excel does not write the mathvariant attribute in an <mn> element. All math alphanumeric characters are written using Unicode code points.

- cc. *The standard defines the attribute style, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- dd. *The standard defines the attribute xref, contained within the element <mn>*

This attribute is not supported in Excel 2010 or Excel 2013.

- ee. *The standard defines the element <mn>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- ff. *The standard defines the attribute class, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- gg. *The standard defines the attribute color, contained within the element <mn>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the color attribute in an <mn> element. On save, PowerPoint does not write the color attribute in an <mn> element.

- hh. *The standard defines the attribute fontfamily, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- ii. *The standard defines the attribute fontsize, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

jj. *The standard defines the attribute fontstyle, contained within the element <mn>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontstyle attribute in an <mn> element. On save, PowerPoint does not write the fontstyle attribute in an <mn> element.

kk. *The standard defines the attribute fontweight, contained within the element <mn>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontweight attribute in an <mn> element. On save, PowerPoint does not write the fontweight attribute in an <mn> element.

ll. *The standard defines the attribute id, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

mm. *The standard defines the attribute mathbackground, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

nn. *The standard defines the attribute mathcolor, contained within the element <mn>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathcolor attribute in an <mn> element. On save, PowerPoint does not write the mathcolor attribute in an <mn> element.

oo. *The standard defines the attribute mathsize, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

pp. *The standard defines the attribute mathvariant, contained within the element <mn>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathvariant attribute in an <mn> element.

On save, PowerPoint does not write the mathvariant attribute in an <mn> element. All math alphanumeric characters are written using Unicode code points.

qq. *The standard defines the attribute style, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

rr. *The standard defines the attribute xref, contained within the element <mn>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.466 Section 12.5 (MathML 2.0 Section 3.2.5), Operator, Fence, Separator or Accent (mo)

a. *The standard defines the element <mo>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On save, MathML in Word does not write out the mathvariant, fontweight, or fontstyle attributes for the <mo> element.

On load, MathML in Word recognizes MathML $\langle mrow \rangle$ elements as functions if the following are true:

- There are three child elements.
- The second child element is an $\langle mo \rangle$ element that contains one character - the function apply character, $\langle U+2061 \rangle$.

On load, Nary operators with no limits defined are interpreted as regular operators.

MathML in Word may inconsistently apply italic formatting to operators.

On load, operators are always assumed to have italics applied unless `mathvariant`, `fontweight`, or `fontstyle` attributes are present and state otherwise. (For example, $\langle mo \text{ mathvariant="normal"} \rangle + \langle /mo \rangle$). The values of the `mathvariant`, `fontweight` or `fontstyle` attributes are reflected on the format buttons on the MathML in Word user interface, but may not impact whether the operator renders in italics or non-italics.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute `accent`, contained within the element $\langle mo \rangle$*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the `accent` attribute in an $\langle mo \rangle$ element.

On save, OfficeArt Math in Word does not write the `accent` attribute in an $\langle mo \rangle$ element.

- c. *The standard defines the attribute `class`, contained within the element $\langle mo \rangle$*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute `color`, contained within the element $\langle mo \rangle$*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the `color` attribute in an $\langle mo \rangle$ element. On save, OfficeArt Math in Word does not write the `color` attribute in an $\langle mo \rangle$ element.

- e. *The standard defines the attribute `fence`, contained within the element $\langle mo \rangle$*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

MathML in Word does not support this attribute. MathML in Word does support the $\langle mfence \rangle$ element on load, which can be used instead.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- f. *The standard defines the attribute `fontfamily`, contained within the element $\langle mo \rangle$*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- g. *The standard defines the attribute `fontsize`, contained within the element $\langle mo \rangle$*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- h. *The standard defines the attribute fontstyle, contained within the element <mo>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the fontstyle attribute in an <mo> element. On save, OfficeArt Math in Word does not write the fontstyle attribute in an <mo> element.

- i. *The standard defines the attribute fontweight, contained within the element <mo>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the fontweight attribute in an <mo> element. On save, OfficeArt Math in Word does not write the fontweight attribute in an <mo> element.

- j. *The standard defines the attribute form, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- k. *The standard defines the attribute id, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- l. *The standard defines the attribute largeop, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- m. *The standard defines the attribute lspace, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- n. *The standard defines the attribute mathbackground, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the mathbackground attribute in an <mo> element. On save, OfficeArt Math in Word does not write the mathbackground attribute in an <mo> element.

- o. *The standard defines the attribute mathcolor, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the mathcolor attribute in an <mo> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mo> element.

- p. *The standard defines the attribute mathsize, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- q. *The standard defines the attribute `mathvariant`, contained within the element `<mo>`*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the `mathvariant` attribute in an `<mo>` element.

On save, OfficeArt Math in Word does not write the `mathvariant` attribute in an `<mo>` element. All math alphanumeric characters are written using Unicode code points.

- r. *The standard defines the property "(everything else)", contained within the attribute `mathvariant`, contained within the element `<mo>`*

This property is supported in Word 2010 and Word 2013.

- s. *The standard defines the property "monospace", contained within the attribute `mathvariant`, contained within the element `<mo>`*

This property is supported in Word 2010 and Word 2013.

On load, Word ignores the `mathvariant` attribute when it has a value of "monospace".

- t. *The standard defines the attribute `maxsize`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- u. *The standard defines the attribute `minsize`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- v. *The standard defines the attribute `movablelimits`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- w. *The standard defines the attribute `rspace`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- x. *The standard defines the attribute `separator`, contained within the element `<mo>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

MathML in Word does not support the "separator" attribute of the `<mo>` element.. MathML in Word does support the `<mfence>` element on load, which can be used instead.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- y. *The standard defines the attribute `stretchy`, contained within the element `<mo>`*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

On save, MathML in Word will emit stretchy for the following N-Ary operators: '∫', '∬', '∭', '∮', '∯', '∰', '∲', '∳', '∱', '∩', '∪', '∏', '∐', '∑', '⋀', '⋁', '⋂', '⋃'

On load, MathML in Word will respect the stretchy attribute for the following N-Ary operators: '∫', '∬', '∭', '∮', '∯', '∰', '∲', '∳', '∱', '∩', '∪', '∏', '∐', '∑', '⋀', '⋁', '⋂', '⋃'

On load, if the stretchy attribute is absent then MathML in Word will interpret the stretchy attribute value to be TRUE for the following N-Ary operators: '∫', '∮', '∯', '∲', '∳', '∩', '∪', '∏', '∑', '⋀', '⋁', '⋂', '⋃'

And, MathML in Word will interpret the stretchy attribute value to be false for the following N-Ary operators: '∬', '∭', '∰', '∱', '∐'

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

z. *The standard defines the attribute style, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

aa. *The standard defines the attribute symmetric, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

bb. *The standard defines the attribute xref, contained within the element <mo>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

cc. *The standard defines the element <mo>*

This element is supported in Excel 2010 and Excel 2013.

dd. *The standard defines the attribute accent, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the accent attribute in an <mo> element.

On save, Excel does not write the accent attribute in an <mo> element.

ee. *The standard defines the attribute class, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

ff. *The standard defines the attribute color, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the color attribute in an <mo> element. On save, Excel does not write the color attribute in an <mo> element.

gg. *The standard defines the attribute fence, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

hh. *The standard defines the attribute fontfamily, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

ii. *The standard defines the attribute fontsize, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

jj. *The standard defines the attribute fontstyle, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontstyle attribute in an <mo> element. On save, Excel does not write the fontstyle attribute in an <mo> element.

kk. *The standard defines the attribute fontweight, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontweight attribute in an <mo> element. On save, Excel does not write the fontweight attribute in an <mo> element.

ll. *The standard defines the attribute form, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

mm. *The standard defines the attribute id, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

nn. *The standard defines the attribute largeop, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

oo. *The standard defines the attribute lspace, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

pp. *The standard defines the attribute mathbackground, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathbackground attribute in an <mo> element. On save, Excel does not write the mathbackground attribute in an <mo> element.

qq. *The standard defines the attribute mathcolor, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathcolor attribute in an <mo> element. On save, Excel does not write the mathcolor attribute in an <mo> element.

rr. *The standard defines the attribute mathsize, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

ss. *The standard defines the attribute mathvariant, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathvariant attribute in an <mo> element.

On save, Excel does not write the mathvariant attribute in an <mo> element. All math alphanumeric characters are written using Unicode code points.

tt. *The standard defines the attribute maxsize, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

uu. *The standard defines the attribute minsize, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

vv. *The standard defines the attribute movablelimits, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

ww. *The standard defines the attribute rspace, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

xx. *The standard defines the attribute separator, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

yy. *The standard defines the attribute stretchy, contained within the element <mo>*

This attribute is supported in Excel 2010 and Excel 2013.

zz. *The standard defines the attribute style, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

aaa. *The standard defines the attribute symmetric, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

bbb. *The standard defines the attribute xref, contained within the element <mo>*

This attribute is not supported in Excel 2010 or Excel 2013.

ccc. *The standard defines the element <mo>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

ddd. *The standard defines the attribute accent, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the accent attribute in an <mo> element.

On save, PowerPoint does not write the accent attribute in an <mo> element.

eee. *The standard defines the attribute class, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

fff. *The standard defines the attribute color, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the color attribute in an <mo> element. On save, PowerPoint does not write the color attribute in an <mo> element.

ggg. *The standard defines the attribute fence, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

hhh. *The standard defines the attribute fontfamily, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

iii. *The standard defines the attribute fontsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

jjj. *The standard defines the attribute fontstyle, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontstyle attribute in an <mo> element. On save, PowerPoint does not write the fontstyle attribute in an <mo> element.

kkk. *The standard defines the attribute fontweight, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontweight attribute in an <mo> element. On save, PowerPoint does not write the fontweight attribute in an <mo> element.

lll. *The standard defines the attribute form, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

mmm. *The standard defines the attribute id, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

nnn. *The standard defines the attribute largeop, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

ooo. *The standard defines the attribute lspace, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ppp. *The standard defines the attribute mathbackground, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathbackground attribute in an <mo> element. On save, PowerPoint does not write the mathbackground attribute in an <mo> element.

qqq. *The standard defines the attribute mathcolor, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathcolor attribute in an <mo> element. On save, PowerPoint does not write the mathcolor attribute in an <mo> element.

rrr. *The standard defines the attribute mathsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

sss. *The standard defines the attribute mathvariant, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathvariant attribute in an <mo> element.

On save, PowerPoint does not write the mathvariant attribute in an <mo> element. All math alphanumeric characters are written using Unicode code points.

ttt. *The standard defines the attribute maxsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

uuu. *The standard defines the attribute minsize, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

vvv. *The standard defines the attribute movablelimits, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

www. *The standard defines the attribute rspace, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

xxx. *The standard defines the attribute separator, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

yyy. *The standard defines the attribute stretchy, contained within the element <mo>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

zzz. *The standard defines the attribute style, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

aaaa. *The standard defines the attribute symmetric, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

bbbb. *The standard defines the attribute xref, contained within the element <mo>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.467 Section 12.5 (MathML 2.0 Section 3.2.6), Text (mtext)

a. *The standard defines the element <mtext>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

b. *The standard defines the attribute class, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

c. *The standard defines the attribute color, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the color attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the color attribute in an <mtext> element.

- d. *The standard defines the attribute fontfamily, contained within the element <mtext>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- e. *The standard defines the attribute fontsize, contained within the element <mtext>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- f. *The standard defines the attribute fontstyle, contained within the element <mtext>*
This attribute is supported in MathML in Word 2010 and MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the fontstyle attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the fontstyle attribute in an <mtext> element.
- g. *The standard defines the attribute fontweight, contained within the element <mtext>*
This attribute is supported in MathML in Word 2010 and MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the fontweight attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the fontweight attribute in an <mtext> element.
- h. *The standard defines the attribute id, contained within the element <mtext>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- i. *The standard defines the attribute mathbackground, contained within the element <mtext>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the mathbackground attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the mathbackground attribute in an <mtext> element.
- j. *The standard defines the attribute mathcolor, contained within the element <mtext>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the mathcolor attribute in an <mtext> element. On save, OfficeArt Math in Word does not write the mathcolor attribute in an <mtext> element.
- k. *The standard defines the attribute mathsize, contained within the element <mtext>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- l. *The standard defines the attribute mathvariant, contained within the element <mtext>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the mathvariant attribute in an <mtext> element.

On save, OfficeArt Math in Word does not write the mathvariant attribute in an <mtext> element. All math alphanumeric characters are written using Unicode code points.

- m. *The standard defines the property "(everything else)", contained within the attribute mathvariant, contained within the element <mtext>*

This property is supported in Word 2010 and Word 2013.

- n. *The standard defines the property "monospace", contained within the attribute mathvariant, contained within the element <mtext>*

This property is supported in Word 2010 and Word 2013.

On load, Word ignores the mathvariant attribute if the value is "monospace".

- o. *The standard defines the attribute style, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- p. *The standard defines the attribute xref, contained within the element <mtext>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- q. *The standard defines the element <mtext>*

This element is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the attribute class, contained within the element <mtext>*

This attribute is not supported in Excel 2010 or Excel 2013.

- s. *The standard defines the attribute color, contained within the element <mtext>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the color attribute in an <mtext> element. On save, Excel does not write the color attribute in an <mtext> element.

- t. *The standard defines the attribute fontfamily, contained within the element <mtext>*

This attribute is not supported in Excel 2010 or Excel 2013.

- u. *The standard defines the attribute fontsize, contained within the element <mtext>*

This attribute is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the attribute fontstyle, contained within the element <mtext>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontstyle attribute in an <mtext> element. On save, Excel does not write the fontstyle attribute in an <mtext> element.

- w. *The standard defines the attribute fontweight, contained within the element <mtext>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontweight attribute in an <mtext> element. On save, Excel does not write the fontweight attribute in an <mtext> element.

- x. *The standard defines the attribute id, contained within the element <mtext>*

This attribute is not supported in Excel 2010 or Excel 2013.

- y. *The standard defines the attribute mathbackground, contained within the element <mtext>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathbackground attribute in an <mtext> element. On save, Excel does not write the mathbackground attribute in an <mtext> element.

- z. *The standard defines the attribute mathcolor, contained within the element <mtext>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathcolor attribute in an <mtext> element. On save, Excel does not write the mathcolor attribute in an <mtext> element.

- aa. *The standard defines the attribute mathsize, contained within the element <mtext>*

This attribute is not supported in Excel 2010 or Excel 2013.

- bb. *The standard defines the attribute mathvariant, contained within the element <mtext>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathvariant attribute in an <mtext> element.

On save, Excel does not write the mathvariant attribute in an <mtext> element. All math alphanumeric characters are written using Unicode code points.

- cc. *The standard defines the attribute style, contained within the element <mtext>*

This attribute is not supported in Excel 2010 or Excel 2013.

- dd. *The standard defines the attribute xref, contained within the element <mtext>*

This attribute is not supported in Excel 2010 or Excel 2013.

- ee. *The standard defines the element <mtext>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- ff. *The standard defines the attribute class, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- gg. *The standard defines the attribute color, contained within the element <mtext>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the color attribute in an <mtext> element. On save, PowerPoint does not write the color attribute in an <mtext> element.

- hh. *The standard defines the attribute fontfamily, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- ii. *The standard defines the attribute fontsize, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- jj. *The standard defines the attribute fontstyle, contained within the element <mtext>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontstyle attribute in an <mtext> element. On save, PowerPoint does not write the fontstyle attribute in an <mtext> element.

- kk. *The standard defines the attribute fontweight, contained within the element <mtext>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontweight attribute in an <mtext> element. On save, PowerPoint does not write the fontweight attribute in an <mtext> element.

- ll. *The standard defines the attribute id, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- mm. *The standard defines the attribute mathbackground, contained within the element <mtext>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathbackground attribute in an <mtext> element. On save, PowerPoint does not write the mathbackground attribute in an <mtext> element.

- nn. *The standard defines the attribute mathcolor, contained within the element <mtext>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathcolor attribute in an <mtext> element. On save, PowerPoint does not write the mathcolor attribute in an <mtext> element.

- oo. *The standard defines the attribute mathsize, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- pp. *The standard defines the attribute mathvariant, contained within the element <mtext>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathvariant attribute in an <mtext> element.

On save, PowerPoint does not write the mathvariant attribute in an <mtext> element. All math alphanumeric characters are written using Unicode code points.

- qq. *The standard defines the attribute style, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- rr. *The standard defines the attribute xref, contained within the element <mtext>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.468 Section 12.5 (MathML 2.0 Section 3.2.7), Space (mspace)

- a. *The standard defines the element <mspace>*

This element is not supported in MathML in Word 2010 or MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the `<mspace>` element. On load, the `<mspace>` element is treated as a space character when width, height or depth are specified.

On save, OfficeArt Math in Word does not write the `<mspace>` element.

- b. *The standard defines the attribute class, contained within the element `<mspace>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute depth, contained within the element `<mspace>`*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the depth attribute in an `<mspace>` element. An ASCII space is inserted.

On save, Word does not write the `<mspace>` element.

- d. *The standard defines the attribute height, contained within the element `<mspace>`*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the height attribute in an `<mspace>` element. An ASCII space is inserted.

On save, Word does not write the `<mspace>` element.

- e. *The standard defines the attribute id, contained within the element `<mspace>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute linebreak, contained within the element `<mspace>`*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the linebreak attribute in an `<mspace>` element. If the linebreak attribute has the value of "newline" or "indentingnewline" and the following element is `<mo>` then a break is inserted. Otherwise, the linebreak attribute is ignored.

On save, Word does not write the `<mspace>` element.

- g. *The standard defines the property "auto | nobreak | goodbreak | badbreak", contained within the attribute linebreak, contained within the element `<mspace>`*

This property is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute style, contained within the element `<mspace>`*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute width, contained within the element `<mspace>`*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the width attribute in an `<mspace>` element. An ASCII space is inserted.

On save, Word does not write the `<mspace>` element.

- j. *The standard defines the attribute xref, contained within the element `<mspace>`*

This attribute is not supported in Word 2010 or Word 2013.

k. *The standard defines the element <mspace>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads the <mspace> element. On load, the <mspace> element is treated as a space character when width, height or depth are specified.

On save, Excel does not write the <mspace> element.

l. *The standard defines the attribute class, contained within the element <mspace>*

This attribute is not supported in Excel 2010 or Excel 2013.

m. *The standard defines the attribute depth, contained within the element <mspace>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the depth attribute in an <mspace> element. An ASCII space is inserted.

On save, Excel does not write the <mspace> element.

n. *The standard defines the attribute height, contained within the element <mspace>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the height attribute in an <mspace> element. An ASCII space is inserted.

On save, Excel does not write the <mspace> element.

o. *The standard defines the attribute id, contained within the element <mspace>*

This attribute is not supported in Excel 2010 or Excel 2013.

p. *The standard defines the attribute linebreak, contained within the element <mspace>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the linebreak attribute in an <mspace> element. If the linebreak attribute has the value of "newline" or "indentingnewline" and the following element is <mo> then a break is inserted. Otherwise, the linebreak attribute is ignored.

On save, Excel does not write the <mspace> element.

q. *The standard defines the property "auto | nobreak | goodbreak | badbreak", contained within the attribute linebreak, contained within the element <mspace>*

This property is not supported in Excel 2010 or Excel 2013.

r. *The standard defines the attribute style, contained within the element <mspace>*

This attribute is not supported in Excel 2010 or Excel 2013.

s. *The standard defines the attribute width, contained within the element <mspace>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the width attribute in an <mspace> element. An ASCII space is inserted.

On save, Excel does not write the <mspace> element.

t. *The standard defines the attribute xref, contained within the element <mspace>*

This attribute is not supported in Excel 2010 or Excel 2013.

- u. *The standard defines the element <mspace>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the <mspace> element. On load, the <mspace> element is treated as a space character when width, height, or depth are specified.

On save, PowerPoint does not write the <mspace> element.

- v. *The standard defines the attribute class, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- w. *The standard defines the attribute depth, contained within the element <mspace>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the depth attribute in an <mspace> element. An ASCII space is inserted.

On save, PowerPoint does not write the <mspace> element.

- x. *The standard defines the attribute height, contained within the element <mspace>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the height attribute in an <mspace> element. An ASCII space is inserted.

On save, PowerPoint does not write the <mspace> element.

- y. *The standard defines the attribute id, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- z. *The standard defines the attribute linebreak, contained within the element <mspace>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the linebreak attribute in an <mspace> element. If the linebreak attribute has the value of "newline" or "indentingnewline" and the following element is <mo>, then a break is inserted. Otherwise, the linebreak attribute is ignored.

On save, PowerPoint does not write the <mspace> element.

- aa. *The standard defines the property "auto | nobreak | goodbreak | badbreak", contained within the attribute linebreak, contained within the element <mspace>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- bb. *The standard defines the attribute style, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- cc. *The standard defines the attribute width, contained within the element <mspace>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the width attribute in an <mspace> element. An ASCII space is inserted.

On save, PowerPoint does not write the <mspace> element.

dd. *The standard defines the attribute xref, contained within the element <mspace>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.469 Section 12.5 (MathML 2.0 Section 3.2.8), String Literal (ms)

a. *The standard defines the element <ms>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On save, MathML in Word saves previously loaded <ms> elements as one or more tokenized elements instead of as a single <ms> element.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the <ms> element.

On save, OfficeArt Math in Word does not write the <ms> element.

b. *The standard defines the attribute class, contained within the element <ms>*

This attribute is not supported in Word 2010 or Word 2013.

c. *The standard defines the attribute color, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the color attribute in an <ms> element. On save, Word does not write the color attribute in an <ms> element.

d. *The standard defines the attribute fontfamily, contained within the element <ms>*

This attribute is not supported in Word 2010 or Word 2013.

e. *The standard defines the attribute fontsize, contained within the element <ms>*

This attribute is not supported in Word 2010 or Word 2013.

f. *The standard defines the attribute fontstyle, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the fontstyle attribute in an <ms> element. On save, Word does not write the fontstyle attribute in an <ms> element.

g. *The standard defines the attribute fontweight, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the fontweight attribute in an <ms> element. On save, Word does not write the fontweight attribute in an <ms> element.

h. *The standard defines the attribute id, contained within the element <ms>*

This attribute is not supported in Word 2010 or Word 2013.

i. *The standard defines the attribute lquote, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the lquote attribute in an <ms> element.

On save, Word does not write the lquote attribute in an <ms> element.

- j. *The standard defines the attribute mathbackground, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the mathbackground attribute in an <ms> element. On save, Word does not write the mathbackground attribute in an <ms> element.

- k. *The standard defines the attribute mathcolor, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the mathcolor attribute in an <ms> element. On save, Word does not write the mathcolor attribute in an <ms> element.

- l. *The standard defines the attribute mathsize, contained within the element <ms>*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute mathvariant, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the mathvariant attribute in an <ms> element.

On save, Word does not write the mathvariant attribute in an <ms> element. All math alphanumeric characters are written using Unicode code points.

- n. *The standard defines the attribute rquote, contained within the element <ms>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the rquote attribute in an <ms> element.

On save, Word does not write the rquote attribute in an <ms> element.

- o. *The standard defines the attribute style, contained within the element <ms>*

This attribute is not supported in Word 2010 or Word 2013.

- p. *The standard defines the attribute xref, contained within the element <ms>*

This attribute is not supported in Word 2010 or Word 2013.

- q. *The standard defines the element <ms>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads the <ms> element.

On save, Excel does not write the <ms> element.

- r. *The standard defines the attribute class, contained within the element <ms>*

This attribute is not supported in Excel 2010 or Excel 2013.

- s. *The standard defines the attribute color, contained within the element <ms>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the color attribute in an <ms> element. On save, Excel does not write the color attribute in an <ms> element.

- t. *The standard defines the attribute fontfamily, contained within the element <ms>*
This attribute is not supported in Excel 2010 or Excel 2013.
- u. *The standard defines the attribute fontsize, contained within the element <ms>*
This attribute is not supported in Excel 2010 or Excel 2013.
- v. *The standard defines the attribute fontstyle, contained within the element <ms>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the fontstyle attribute in an <ms> element. On save, Excel does not write the fontstyle attribute in an <ms> element.
- w. *The standard defines the attribute fontweight, contained within the element <ms>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the fontweight attribute in an <ms> element. On save, Excel does not write the fontweight attribute in an <ms> element.
- x. *The standard defines the attribute id, contained within the element <ms>*
This attribute is not supported in Excel 2010 or Excel 2013.
- y. *The standard defines the attribute lquote, contained within the element <ms>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the lquote attribute in an <ms> element.
On save, Excel does not write the lquote attribute in an <ms> element.
- z. *The standard defines the attribute mathbackground, contained within the element <ms>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the mathbackground attribute in an <ms> element. On save, Excel does not write the mathbackground attribute in an <ms> element.
- aa. *The standard defines the attribute mathcolor, contained within the element <ms>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the mathcolor attribute in an <ms> element. On save, Excel does not write the mathcolor attribute in an <ms> element.
- bb. *The standard defines the attribute mathsize, contained within the element <ms>*
This attribute is not supported in Excel 2010 or Excel 2013.
- cc. *The standard defines the attribute mathvariant, contained within the element <ms>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the mathvariant attribute in an <ms> element.
On save, Excel does not write the mathvariant attribute in an <ms> element. All math alphanumeric characters are written using Unicode code points.
- dd. *The standard defines the attribute rquote, contained within the element <ms>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the rquote attribute in an <ms> element.

On save, Excel does not write the rquote attribute in an <ms> element.

ee. *The standard defines the attribute style, contained within the element <ms>*

This attribute is not supported in Excel 2010 or Excel 2013.

ff. *The standard defines the attribute xref, contained within the element <ms>*

This attribute is not supported in Excel 2010 or Excel 2013.

gg. *The standard defines the element <ms>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the <ms> element.

On save, PowerPoint does not write the <ms> element.

hh. *The standard defines the attribute class, contained within the element <ms>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ii. *The standard defines the attribute color, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the color attribute in an <ms> element. On save, PowerPoint does not write the color attribute in an <ms> element.

jj. *The standard defines the attribute fontfamily, contained within the element <ms>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

kk. *The standard defines the attribute fontsize, contained within the element <ms>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ll. *The standard defines the attribute fontstyle, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontstyle attribute in an <ms> element. On save, PowerPoint does not write the fontstyle attribute in an <ms> element.

mm. *The standard defines the attribute fontweight, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontweight attribute in an <ms> element. On save, PowerPoint does not write the fontweight attribute in an <ms> element.

nn. *The standard defines the attribute id, contained within the element <ms>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

oo. *The standard defines the attribute lquote, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the lquote attribute in an <ms> element.

On save, PowerPoint does not write the lquote attribute in an <ms> element.

pp. *The standard defines the attribute mathbackground, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathbackground attribute in an <ms> element. On save, PowerPoint does not write the mathbackground attribute in an <ms> element.

qq. *The standard defines the attribute mathcolor, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathcolor attribute in an <ms> element. On save, PowerPoint does not write the mathcolor attribute in an <ms> element.

rr. *The standard defines the attribute mathsize, contained within the element <ms>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ss. *The standard defines the attribute mathvariant, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathvariant attribute in an <ms> element.

On save, PowerPoint does not write the mathvariant attribute in an <ms> element. All math alphanumeric characters are written using Unicode code points.

tt. *The standard defines the attribute rquote, contained within the element <ms>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the rquote attribute in an <ms> element.

On save, PowerPoint does not write the rquote attribute in an <ms> element.

uu. *The standard defines the attribute style, contained within the element <ms>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

vv. *The standard defines the attribute xref, contained within the element <ms>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.470 Section 12.5 (MathML 2.0 Section 3.2.9), Accessing glyphs for characters from MathML (mglyph)

a. *The standard defines the element <mglyph>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On save, MathML in Word will never write <mglyph>.

On load, MathML in Word will replace the <mglyph> with the value of the alt attribute as normal text. The fontfamily and index attributes will be dropped.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word, reads content only from the alt attribute of the `mglyph` element. Specifying glyphs directly is not supported.

On save, OfficeArt Math in Word does not write the `<mglyph>` element.

- b. *The standard defines the attribute alt, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the alt attribute in an `<mglyph>` element. The value of the alt attribute is inserted as text.

On save, Word does not write the alt attribute in an `<mglyph>` element.

- c. *The standard defines the attribute class, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute color, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the color attribute in an `<mglyph>` element. On save, Word does not write the color attribute in an `<mglyph>` element.

- e. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute fontsize, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute fontstyle, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the fontstyle attribute in an `<mglyph>` element. On save, Word does not write the fontstyle attribute in an `<mglyph>` element.

- h. *The standard defines the attribute fontweight, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the fontweight attribute in an `<mglyph>` element. On save, Word does not write the fontweight attribute in an `<mglyph>` element.

- i. *The standard defines the attribute id, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- k. *The standard defines the attribute mathbackground, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the mathbackground attribute in an `<mglyph>` element. On save, Word does not write the mathbackground attribute in an `<mglyph>` element.

- l. *The standard defines the attribute mathcolor, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads the mathcolor attribute in an <mglyph> element. On save, Word does not write the mathcolor attribute in an <mglyph> element.

- m. *The standard defines the attribute mathsize, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- n. *The standard defines the attribute mathvariant, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

- o. *The standard defines the attribute style, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- p. *The standard defines the attribute xref, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

- q. *The standard defines the element <mglyph>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel, reads content only from the alt attribute of the mglyph element. Specifying glyphs directly is not supported.

On save, Excel does not write the <mglyph> element.

- r. *The standard defines the attribute alt, contained within the element <mglyph>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the alt attribute in an <mglyph> element. The value of the alt attribute is inserted as text.

On save, Excel does not write the alt attribute in an <mglyph> element.

- s. *The standard defines the attribute class, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- t. *The standard defines the attribute color, contained within the element <mglyph>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the color attribute in an <mglyph> element. On save, Excel does not write the color attribute in an <mglyph> element.

- u. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the attribute fontsize, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- w. *The standard defines the attribute fontstyle, contained within the element <mglyph>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontstyle attribute in an <mglyph> element. On save, Excel does not write the fontstyle attribute in an <mglyph> element.

- x. *The standard defines the attribute fontweight, contained within the element <mglyph>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the fontweight attribute in an <mglyph> element. On save, Excel does not write the fontweight attribute in an <mglyph> element.

- y. *The standard defines the attribute id, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- z. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- aa. *The standard defines the attribute mathbackground, contained within the element <mglyph>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathbackground attribute in an <mglyph> element. On save, Excel does not write the mathbackground attribute in an <mglyph> element.

- bb. *The standard defines the attribute mathcolor, contained within the element <mglyph>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the mathcolor attribute in an <mglyph> element. On save, Excel does not write the mathcolor attribute in an <mglyph> element.

- cc. *The standard defines the attribute mathsize, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- dd. *The standard defines the attribute mathvariant, contained within the element <mglyph>*

This attribute is supported in Excel 2010 and Excel 2013.

- ee. *The standard defines the attribute style, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- ff. *The standard defines the attribute xref, contained within the element <mglyph>*

This attribute is not supported in Excel 2010 or Excel 2013.

- gg. *The standard defines the element <mglyph>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint, reads content only from the alt attribute of the mglyph element. Specifying glyphs directly is not supported.

On save, PowerPoint does not write the <mglyph> element.

- hh. *The standard defines the attribute alt, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the alt attribute in an <mglyph> element. The value of the alt attribute is inserted as text.

On save, PowerPoint does not write the alt attribute in an <mglyph> element.

- ii. *The standard defines the attribute class, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- jj. *The standard defines the attribute color, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the color attribute in an <mglyph> element. On save, PowerPoint does not write the color attribute in an <mglyph> element.

- kk. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- ll. *The standard defines the attribute fontsize, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- mm. *The standard defines the attribute fontstyle, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontstyle attribute in an <mglyph> element. On save, PowerPoint does not write the fontstyle attribute in an <mglyph> element.

- nn. *The standard defines the attribute fontweight, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the fontweight attribute in an <mglyph> element. On save, PowerPoint does not write the fontweight attribute in an <mglyph> element.

- oo. *The standard defines the attribute id, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- pp. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- qq. *The standard defines the attribute mathbackground, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathbackground attribute in an <mglyph> element. On save, PowerPoint does not write the mathbackground attribute in an <mglyph> element.

- rr. *The standard defines the attribute mathcolor, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathcolor attribute in an <mglyph> element. On save, PowerPoint does not write the mathcolor attribute in an <mglyph> element.

- ss. *The standard defines the attribute mathsize, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- tt. *The standard defines the attribute mathvariant, contained within the element <mglyph>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

uu. *The standard defines the attribute style, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

vv. *The standard defines the attribute xref, contained within the element <mglyph>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.471 Section 12.5 (MathML 2.0 Section 3.2.9.2), Accessing glyphs for characters from MathML (mglyph)

a. *The standard defines the attribute alt, contained within the element <mglyph>*

This attribute is supported in Word 2010 and Word 2013.

b. *The standard defines the attribute fontfamily, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

c. *The standard defines the attribute index, contained within the element <mglyph>*

This attribute is not supported in Word 2010 or Word 2013.

2.1.472 Section 12.5 (MathML 2.0 Section 3.3.1), Horizontally Group Sub-Expressions (mrow)

a. *The standard defines the element <mrow>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word supports the use of the <mrow> element with or without attributes. MathML in Word ignores any attributes that are present.

On save, MathML in Word may write more <mrow> elements than are strictly necessary.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

b. *The standard defines the attribute class, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

c. *The standard defines the attribute id, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

d. *The standard defines the attribute style, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

e. *The standard defines the attribute xref, contained within the element <mrow>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the element <mrow>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the attribute class, contained within the element <mrow>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute id, contained within the element <mrow>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute style, contained within the element <mrow>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute xref, contained within the element <mrow>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the element <mrow>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- l. *The standard defines the attribute class, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute id, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute style, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- o. *The standard defines the attribute xref, contained within the element <mrow>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.473 Section 12.5 (MathML 2.0 Section 3.3.2), Fractions (mfrac)

- a. *The standard defines the element <mfrac>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute bevelled, contained within the element <mfrac>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- c. *The standard defines the attribute class, contained within the element <mfrac>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute `denomalign`, contained within the element `<mfrac>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- e. *The standard defines the attribute `id`, contained within the element `<mfrac>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- f. *The standard defines the attribute `linethickness`, contained within the element `<mfrac>`*
This attribute is supported in MathML in Word 2010 and MathML in Word 2013.
1. Fraction bars in MathML in Word are either displayed or not displayed.
 2. On load, MathML in Word displays a fraction bar if the `linethickness` attribute has a value of "thin", "medium", "thick", any nonzero digit, or is empty. In all other cases, no fraction bar is displayed.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
Fraction bars in OfficeArt Math in Word are either displayed or not displayed.
On load, OfficeArt Math in Word displays a fraction bar unless `linethickness` is zero and the fraction is not of the bevelled style.
On save, OfficeArt Math in Word either writes a value of '0' or omits this attribute.
- g. *The standard defines the attribute `numalign`, contained within the element `<mfrac>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the attribute `style`, contained within the element `<mfrac>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- i. *The standard defines the attribute `xref`, contained within the element `<mfrac>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- j. *The standard defines the element `<mfrac>`*
This element is supported in Excel 2010 and Excel 2013.
- k. *The standard defines the attribute `bevelled`, contained within the element `<mfrac>`*
This attribute is supported in Excel 2010 and Excel 2013.
- l. *The standard defines the attribute `class`, contained within the element `<mfrac>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the attribute `denomalign`, contained within the element `<mfrac>`*
This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute id, contained within the element <mfrac>*
This attribute is not supported in Excel 2010 or Excel 2013.
- o. *The standard defines the attribute linethickness, contained within the element <mfrac>*
This attribute is supported in Excel 2010 and Excel 2013.
Fraction bars in Excel are either displayed or not displayed.
On load, Excel displays a fraction bar unless linethickness is zero and the fraction is not of the bevelled style.
On save, Excel either writes a value of '0' or omits this attribute.
- p. *The standard defines the attribute numalign, contained within the element <mfrac>*
This attribute is not supported in Excel 2010 or Excel 2013.
- q. *The standard defines the attribute style, contained within the element <mfrac>*
This attribute is not supported in Excel 2010 or Excel 2013.
- r. *The standard defines the attribute xref, contained within the element <mfrac>*
This attribute is not supported in Excel 2010 or Excel 2013.
- s. *The standard defines the element <mfrac>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- t. *The standard defines the attribute bevelled, contained within the element <mfrac>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- u. *The standard defines the attribute class, contained within the element <mfrac>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- v. *The standard defines the attribute denomalign, contained within the element <mfrac>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- w. *The standard defines the attribute id, contained within the element <mfrac>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- x. *The standard defines the attribute linethickness, contained within the element <mfrac>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
Fraction bars in PowerPoint are either displayed or not displayed.
On load, PowerPoint displays a fraction bar unless the linethickness attribute is zero and the fraction is not of the bevelled style.
On save, PowerPoint either writes a value of '0' or omits this attribute.
- y. *The standard defines the attribute numalign, contained within the element <mfrac>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- z. *The standard defines the attribute style, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- aa. *The standard defines the attribute xref, contained within the element <mfrac>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.474 Section 12.5 (MathML 2.0 Section 3.3.3), Radicals (msqrt, mroot)

- a. *The standard defines the element <mroot>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute class, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute id, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute style, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute xref, contained within the element <mroot>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the element <msqrt>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- g. *The standard defines the attribute class, contained within the element <msqrt>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- h. *The standard defines the attribute id, contained within the element <msqrt>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- i. *The standard defines the attribute style, contained within the element <msqrt>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- j. *The standard defines the attribute xref, contained within the element <msqrt>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- k. *The standard defines the element <mroot>*
This element is supported in Excel 2010 and Excel 2013.
- l. *The standard defines the attribute class, contained within the element <mroot>*
This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the attribute id, contained within the element <mroot>*
This attribute is not supported in Excel 2010 or Excel 2013.
- n. *The standard defines the attribute style, contained within the element <mroot>*
This attribute is not supported in Excel 2010 or Excel 2013.
- o. *The standard defines the attribute xref, contained within the element <mroot>*
This attribute is not supported in Excel 2010 or Excel 2013.
- p. *The standard defines the element <msqrt>*
This element is supported in Excel 2010 and Excel 2013.
- q. *The standard defines the attribute class, contained within the element <msqrt>*
This attribute is not supported in Excel 2010 or Excel 2013.
- r. *The standard defines the attribute id, contained within the element <msqrt>*
This attribute is not supported in Excel 2010 or Excel 2013.
- s. *The standard defines the attribute style, contained within the element <msqrt>*
This attribute is not supported in Excel 2010 or Excel 2013.
- t. *The standard defines the attribute xref, contained within the element <msqrt>*
This attribute is not supported in Excel 2010 or Excel 2013.
- u. *The standard defines the element <mroot>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- v. *The standard defines the attribute class, contained within the element <mroot>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- w. *The standard defines the attribute id, contained within the element <mroot>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- x. *The standard defines the attribute style, contained within the element <mroot>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- y. *The standard defines the attribute xref, contained within the element <mroot>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

z. *The standard defines the element <msqrt>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

aa. *The standard defines the attribute class, contained within the element <msqrt>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

bb. *The standard defines the attribute id, contained within the element <msqrt>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

cc. *The standard defines the attribute style, contained within the element <msqrt>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

dd. *The standard defines the attribute xref, contained within the element <msqrt>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.475 Section 12.5 (MathML 2.0 Section 3.3.4), Style Change (mstyle)

a. *The standard defines the element <mstyle>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

MathML in Word supports only the scriptlevel attribute of the <mstyle> element.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the <mstyle> element.

On save, OfficeArt Math in Word does not write the <mstyle> element.

b. *The standard defines the attribute background, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

c. *The standard defines the attribute class, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

d. *The standard defines the attribute color, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the color attribute in an <mstyle> element. On save, OfficeArt Math in Word does not write the color attribute in an <mstyle> element.

e. *The standard defines the attribute displaystyle, contained within the element <mstyle>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the attribute `id`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- g. *The standard defines the attribute `mathcolor`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the `mathcolor` attribute in an `<mstyle>` element. On save, OfficeArt Math in Word does not write the `mathcolor` attribute in an `<mstyle>` element.
- h. *The standard defines the attribute `mediummathspace`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- i. *The standard defines the attribute `scriptlevel`, contained within the element `<mstyle>`*
This attribute is supported in MathML in Word 2010 and MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- j. *The standard defines the attribute `scriptminsize`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- k. *The standard defines the attribute `scriptsizemultiplier`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- l. *The standard defines the attribute `style`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- m. *The standard defines the attribute `thickmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- n. *The standard defines the attribute `thinmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- o. *The standard defines the attribute `verythickmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- p. *The standard defines the attribute `verythinmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- q. *The standard defines the attribute `veryverythickmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- r. *The standard defines the attribute `veryverythinmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- s. *The standard defines the attribute `xref`, contained within the element `<mstyle>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- t. *The standard defines the element `<mstyle>`*
This element is supported in Excel 2010 and Excel 2013.
On load, Excel reads the `<mstyle>` element.
On save, Excel does not write the `<mstyle>` element.
- u. *The standard defines the attribute `background`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- v. *The standard defines the attribute `class`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- w. *The standard defines the attribute `color`, contained within the element `<mstyle>`*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the `color` attribute in an `<mstyle>` element. On save, Excel does not write the `color` attribute in an `<mstyle>` element.
- x. *The standard defines the attribute `displaystyle`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- y. *The standard defines the attribute `id`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- z. *The standard defines the attribute `mathcolor`, contained within the element `<mstyle>`*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the `mathcolor` attribute in an `<mstyle>` element. On save, Excel does not write the `mathcolor` attribute in an `<mstyle>` element.

- aa. *The standard defines the attribute `mediummathspace`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- bb. *The standard defines the attribute `scriptlevel`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- cc. *The standard defines the attribute `scriptminsize`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- dd. *The standard defines the attribute `scriptsizemultiplier`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- ee. *The standard defines the attribute `style`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- ff. *The standard defines the attribute `thickmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- gg. *The standard defines the attribute `thinmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- hh. *The standard defines the attribute `verythickmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- ii. *The standard defines the attribute `verythinmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- jj. *The standard defines the attribute `veryverythickmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- kk. *The standard defines the attribute `veryverythinmathspace`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- ll. *The standard defines the attribute `xref`, contained within the element `<mstyle>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- mm. *The standard defines the element `<mstyle>`*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
On load, PowerPoint reads the `<mstyle>` element.
On save, PowerPoint does not write the `<mstyle>` element.
- nn. *The standard defines the attribute `background`, contained within the element `<mstyle>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- oo. *The standard defines the attribute `class`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

pp. *The standard defines the attribute color, contained within the element <mstyle>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the color attribute in an <mstyle> element. On save, PowerPoint does not write the color attribute in an <mstyle> element.

qq. *The standard defines the attribute displaystyle, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

rr. *The standard defines the attribute id, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ss. *The standard defines the attribute mathcolor, contained within the element <mstyle>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the mathcolor attribute in an <mstyle> element. On save, PowerPoint does not write the mathcolor attribute in an <mstyle> element.

tt. *The standard defines the attribute mediummathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

uu. *The standard defines the attribute scriptlevel, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

vv. *The standard defines the attribute scriptminsize, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ww. *The standard defines the attribute scriptsizemultiplier, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

xx. *The standard defines the attribute style, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

yy. *The standard defines the attribute thickmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

zz. *The standard defines the attribute thinmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

aaa. *The standard defines the attribute verythickmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

bbb. *The standard defines the attribute verythinmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ccc. *The standard defines the attribute veryverythickmathspace, contained within the element <mstyle>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ddd. *The standard defines the attribute `veryverythinmathspace`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

eee. *The standard defines the attribute `xref`, contained within the element `<mstyle>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.476 Section 12.5 (MathML 2.0 Section 3.3.5), Error Message (`merror`)

a. *The standard defines the element `<merror>`*

This element is not supported in MathML in Word 2010 or MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the `<merror>` element. On save, OfficeArt Math in Word does not write the `<merror>` element.

b. *The standard defines the attribute `class`, contained within the element `<merror>`*

This attribute is not supported in Word 2010 or Word 2013.

c. *The standard defines the attribute `id`, contained within the element `<merror>`*

This attribute is not supported in Word 2010 or Word 2013.

d. *The standard defines the attribute `style`, contained within the element `<merror>`*

This attribute is not supported in Word 2010 or Word 2013.

e. *The standard defines the attribute `xref`, contained within the element `<merror>`*

This attribute is not supported in Word 2010 or Word 2013.

f. *The standard defines the element `<merror>`*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads the `<merror>` element. On save, Excel does not write the `<merror>` element.

g. *The standard defines the attribute `class`, contained within the element `<merror>`*

This attribute is not supported in Excel 2010 or Excel 2013.

h. *The standard defines the attribute `id`, contained within the element `<merror>`*

This attribute is not supported in Excel 2010 or Excel 2013.

i. *The standard defines the attribute `style`, contained within the element `<merror>`*

This attribute is not supported in Excel 2010 or Excel 2013.

j. *The standard defines the attribute `xref`, contained within the element `<merror>`*

This attribute is not supported in Excel 2010 or Excel 2013.

k. *The standard defines the element `<merror>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the <merror> element. On save, PowerPoint does not write the <merror> element.

- l. *The standard defines the attribute class, contained within the element <merror>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute id, contained within the element <merror>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute style, contained within the element <merror>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- o. *The standard defines the attribute xref, contained within the element <merror>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.477 Section 12.5 (MathML 2.0 Section 3.3.6), Adjust Space Around Content (mpadded)

- a. *The standard defines the element <mpadded>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

1. On save, to make a phantom visible, MathML in Word uses an <mpadded> element only (not <mphantom>). This is true whether the object is smashed or not.
2. On save, to make a phantom invisible with no smashing, MathML in Word uses an <mphantom> element only (not <mpadded>).
3. On save, to make a phantom invisible with smashing, MathML in Word uses an <mpadded> element nested inside an <mphantom> element.
4. On save, MathML in Word converts any smashing into the appropriate attribute for the <mpadded> element and sets the value of the attribute to "0in" (for example, the OOXML construct <m:zeroWid m:val="on" /> maps to the MathML attribute width="0in").
5. On load, MathML in Word maps an <mphantom> element to an <omml:phant> element. Furthermore, if the <mphantom> element has exactly one child element and that child is an <mpadded> element, MathML in Word converts the <mpadded> element's attributes the appropriate MathML in Word smash properties (zeroWid, zeroDesc, zeroAsc) as specified in Note 6).
6. On load, MathML in Word converts the width, height, and depth attributes of the <mpadded> element into MathML in Word phantom properties zeroWid, zeroAsc, and zeroDesc, respectively.
7. Unless an <mpadded> element is the sole child of an <mphantom> element (in which case it would be handled by note 5), MathML in Word maps it to a MathML in Word <phant> element with the show property set to true.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

Padding in OfficeArt Math in Word is either normal or collapsed in any dimension.

On load, OfficeArt Math in Word displays elements with normal dimensions unless depth, height or width are set to '0', in which case they are collapsed in the corresponding dimension.

On save, OfficeArt Math in Word either writes a value of '0' or omits an attribute in the <mpadded> element.

- b. *The standard defines the attribute class, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

c. *The standard defines the attribute depth, contained within the element <mpadded>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word uses the depth attribute to specify the vertical smashing below the baseline. Values containing one numeric digit, all of which are the digit zero, specify that smashing in this direction is on, otherwise smashing is off.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the depth attribute in an <mpadded> element.

On save, OfficeArt Math in Word either writes a value of '0' or omits the depth attribute in the <mpadded> element.

d. *The standard defines the attribute height, contained within the element <mpadded>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute specifies vertical smashing above the baseline. A value of zero specifies that smashing has a value of "off", or the height dimension of the object has a value of zero. Nonzero values specify that smashing has a value of "on", or the height dimension of the object is nonzero.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the height attribute in an <mpadded> element.

On save, OfficeArt Math in Word either writes a value of '0' or omits the height attribute in the <mpadded> element.

e. *The standard defines the attribute id, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

f. *The standard defines the attribute lspace, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

g. *The standard defines the attribute style, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

h. *The standard defines the attribute width, contained within the element <mpadded>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

A value of zero specifies that smashing has a value of "off", or the width dimension of the object has a value of zero. Nonzero values specify that smashing has a value of "on", or the width dimension of the object is nonzero.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the width attribute in an <mpadded> element.

On save, OfficeArt Math in Word either writes a value of '0' or omits the width attribute in the <mpadded> element.

- i. *The standard defines the attribute xref, contained within the element <mpadded>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- j. *The standard defines the element <mpadded>*

This element is supported in Excel 2010 and Excel 2013.

Padding in Excel is either normal or collapsed in any dimension.

On load, Excel displays elements with normal dimensions unless depth, height or width are set to '0', in which case they are collapsed in the corresponding dimension.

On save, Excel either writes a value of '0' or omits an attribute in the <mpadded> element.

- k. *The standard defines the attribute class, contained within the element <mpadded>*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute depth, contained within the element <mpadded>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the depth attribute in an <mpadded> element.

On save, Excel either writes a value of '0' or omits the depth attribute in the <mpadded> element.

- m. *The standard defines the attribute height, contained within the element <mpadded>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the height attribute in an <mpadded> element.

On save, Excel either writes a value of '0' or omits the height attribute in the <mpadded> element.

- n. *The standard defines the attribute id, contained within the element <mpadded>*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the attribute lspace, contained within the element <mpadded>*

This attribute is not supported in Excel 2010 or Excel 2013.

- p. *The standard defines the attribute style, contained within the element <mpadded>*

This attribute is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the attribute width, contained within the element <mpadded>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the width attribute in an <mpadded> element.

On save, Excel either writes a value of '0' or omits the width attribute in the <mpadded> element.

- r. *The standard defines the attribute xref, contained within the element <mpadded>*

This attribute is not supported in Excel 2010 or Excel 2013.

s. *The standard defines the element <mpadded>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

Padding in PowerPoint is either normal or collapsed in any dimension.

On load, PowerPoint displays elements with normal dimensions unless depth, height or width are set to '0', in which case they are collapsed in the corresponding dimension.

On save, PowerPoint either writes a value of '0' or omits an attribute in the <mpadded> element.

t. *The standard defines the attribute class, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

u. *The standard defines the attribute depth, contained within the element <mpadded>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the depth attribute in an <mpadded> element.

On save, PowerPoint either writes a value of '0' or omits the depth attribute in the <mpadded> element.

v. *The standard defines the attribute height, contained within the element <mpadded>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the height attribute in an <mpadded> element.

On save, PowerPoint either writes a value of '0' or omits the height attribute in the <mpadded> element.

w. *The standard defines the attribute id, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

x. *The standard defines the attribute lspace, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

y. *The standard defines the attribute style, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

z. *The standard defines the attribute width, contained within the element <mpadded>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the width attribute in an <mpadded> element.

On save, PowerPoint either writes a value of '0' or omits the width attribute in the <mpadded> element.

aa. *The standard defines the attribute xref, contained within the element <mpadded>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.478 Section 12.5 (MathML 2.0 Section 3.3.7), Making Sub-Expressions Invisible (`mphantom`)

- a. *The standard defines the element `<mphantom>`*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

1. On save, to make a phantom visible, MathML in Word uses an `<mpadded>` element only (not `<mphantom>`). This is true whether the object is smashed or not.
2. On save, to make a phantom invisible with no smashing, MathML in Word uses an `<mphantom>` element only (not `<mpadded>`).
3. On save, to make a phantom invisible with smashing, MathML in Word uses an `<mpadded>` element nested inside an `<mphantom>` element.
4. On save, MathML in Word converts any smashing into the appropriate attribute of an `<mpadded>` element and sets the value to "0in". (For example, the OOXML construct `<m:zeroWid m:val="on" />` maps to the MathML attribute `width="0in"`).
5. On load, MathML in Word maps an `<mphantom>` element to a MathML in Word `<omml:phant>` element. Furthermore, if the `<mphantom>` element has exactly one child element and that child is an `<mpadded>` element, MathML in Word converts the `<mpadded>` element's attributes into MathML in Word smash properties (`zeroWid`, `zeroDesc`, `zeroAsc`) as specified in Note 6.
6. On load, MathML in Word converts the width, height, and depth attributes of the `<mpadded>` element into MathML in Word phantom properties `zeroWid`, `zeroAsc`, and `zeroDesc`, respectively.
7. Unless an `<mpadded>` element is the sole child of an `<mphantom>` element (in which case it would be handled by note 5), MathML in Word maps it to a MathML in Word `<phant>` element with the `show` attribute set to true.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute class, contained within the element `<mphantom>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute id, contained within the element `<mphantom>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute style, contained within the element `<mphantom>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute xref, contained within the element `<mphantom>`*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the element `<mphantom>`*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the attribute class, contained within the element `<mphantom>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute id, contained within the element `<mphantom>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute style, contained within the element <mphantom>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute xref, contained within the element <mphantom>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the element <mphantom>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- l. *The standard defines the attribute class, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute id, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute style, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- o. *The standard defines the attribute xref, contained within the element <mphantom>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.479 Section 12.5 (MathML 2.0 Section 3.3.8), Expression Inside Pair of Fences (mfenced)

- a. *The standard defines the element <mfenced>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute class, contained within the element <mfenced>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute close, contained within the element <mfenced>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- d. *The standard defines the attribute id, contained within the element <mfenced>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute open, contained within the element <mfenced>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- f. *The standard defines the attribute separators, contained within the element <mfenced>*
 This attribute is supported in MathML in Word 2010 and MathML in Word 2013.
 On load, MathML in Word only uses the first separator that is specified and discards all others. On save, MathML in Word only writes out a single separator.
 This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
 On load, OfficeArt Math in Word reads the separators attribute in an <mfenced> element and uses only the first separator.
 On save, OfficeArt Math in Word writes the separators attribute with a single separator in an <mfenced> element.
- g. *The standard defines the attribute style, contained within the element <mfenced>*
 This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
 This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the attribute xref, contained within the element <mfenced>*
 This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
 This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- i. *The standard defines the element <mfenced>*
 This element is supported in Excel 2010 and Excel 2013.
- j. *The standard defines the attribute class, contained within the element <mfenced>*
 This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute close, contained within the element <mfenced>*
 This attribute is supported in Excel 2010 and Excel 2013.
- l. *The standard defines the attribute id, contained within the element <mfenced>*
 This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the attribute open, contained within the element <mfenced>*
 This attribute is supported in Excel 2010 and Excel 2013.
- n. *The standard defines the attribute separators, contained within the element <mfenced>*
 This attribute is supported in Excel 2010 and Excel 2013.
 On load, Excel reads the separators attribute in an <mfenced> element and uses only the first separator.
 On save, Excel writes the separators attribute with a single separator in an <mfenced> element.
- o. *The standard defines the attribute style, contained within the element <mfenced>*
 This attribute is not supported in Excel 2010 or Excel 2013.
- p. *The standard defines the attribute xref, contained within the element <mfenced>*
 This attribute is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the element <mfenced>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- r. *The standard defines the attribute class, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the attribute close, contained within the element <mfenced>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- t. *The standard defines the attribute id, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- u. *The standard defines the attribute open, contained within the element <mfenced>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- v. *The standard defines the attribute separators, contained within the element <mfenced>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the separators attribute in an <mfenced> element and uses only the first separator.

On save, PowerPoint writes the separators attribute with a single separator in an <mfenced> element.

- w. *The standard defines the attribute style, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- x. *The standard defines the attribute xref, contained within the element <mfenced>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.480 Section 12.5 (MathML 2.0 Section 3.3.9), Enclose Expression Inside Notation (menclose)

- a. *The standard defines the element <menclose>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute class, contained within the element <menclose>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute id, contained within the element <menclose>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute notation, contained within the element <menclose>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

On load, if notation is not set, the default is assumed to be a "radical", not "longdiv".

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- e. *The standard defines the property "(everything else)", contained within the attribute notation, contained within the element <menclase>*

This property is supported in MathML in Word 2010 and MathML in Word 2013.

This property is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- f. *The standard defines the property "actuarial", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in MathML in Word 2010 or MathML in Word 2013.

This property is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- g. *The standard defines the property "circle", contained within the attribute notation, contained within the element <menclase>*

This property is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word converts a value of "circle" to the value of "box".

This property is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- h. *The standard defines the property "longdiv", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in MathML in Word 2010 or MathML in Word 2013.

This property is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- i. *The standard defines the property "none", contained within the attribute notation, contained within the element <menclase>*

This property is supported in Word 2010 and Word 2013.

On load, Word reads the 'none' value of the notation attribute as a box with invisible borders.

On save, Word writes the notation, 'none' to denote a box with invisible borders.

- j. *The standard defines the property "radical", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in Word 2010 or Word 2013.

- k. *The standard defines the property "roundedbox", contained within the attribute notation, contained within the element <menclase>*

This property is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word converts the value "roundedbox" to the value "box".

This property is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- l. *The standard defines the attribute style, contained within the element <menclase>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- m. *The standard defines the attribute xref, contained within the element <menclase>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- n. *The standard defines the element <menclase>*
This element is supported in Excel 2010 and Excel 2013.
- o. *The standard defines the attribute class, contained within the element <menclase>*
This attribute is not supported in Excel 2010 or Excel 2013.
- p. *The standard defines the attribute id, contained within the element <menclase>*
This attribute is not supported in Excel 2010 or Excel 2013.
- q. *The standard defines the attribute notation, contained within the element <menclase>*
This attribute is supported in Excel 2010 and Excel 2013.
- r. *The standard defines the property "(everything else)", contained within the attribute notation, contained within the element <menclase>*
This property is supported in Excel 2010 and Excel 2013.
- s. *The standard defines the property "actuarial", contained within the attribute notation, contained within the element <menclase>*
This property is not supported in Excel 2010 or Excel 2013.
- t. *The standard defines the property "circle", contained within the attribute notation, contained within the element <menclase>*
This property is not supported in Excel 2010 or Excel 2013.
- u. *The standard defines the property "longdiv", contained within the attribute notation, contained within the element <menclase>*
This property is not supported in Excel 2010 or Excel 2013.
- v. *The standard defines the property "none", contained within the attribute notation, contained within the element <menclase>*
This property is supported in Excel 2010 and Excel 2013.
On load, Excel reads the 'none' value of the notation attribute as a box with invisible borders.
On save, Excel writes the notation, 'none' to denote a box with invisible borders.
- w. *The standard defines the property "radical", contained within the attribute notation, contained within the element <menclase>*
This property is not supported in Excel 2010 or Excel 2013.
- x. *The standard defines the property "roundedbox", contained within the attribute notation, contained within the element <menclase>*
This property is not supported in Excel 2010 or Excel 2013.
- y. *The standard defines the attribute style, contained within the element <menclase>*

This attribute is not supported in Excel 2010 or Excel 2013.

- z. *The standard defines the attribute xref, contained within the element <menclase>*

This attribute is not supported in Excel 2010 or Excel 2013.

- aa. *The standard defines the element <menclase>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- bb. *The standard defines the attribute class, contained within the element <menclase>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- cc. *The standard defines the attribute id, contained within the element <menclase>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- dd. *The standard defines the attribute notation, contained within the element <menclase>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- ee. *The standard defines the property "(everything else)", contained within the attribute notation, contained within the element <menclase>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- ff. *The standard defines the property "actuarial", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- gg. *The standard defines the property "circle", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- hh. *The standard defines the property "longdiv", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ii. *The standard defines the property "none", contained within the attribute notation, contained within the element <menclase>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the 'none' value of the notation attribute as a box with invisible borders.

On save, PowerPoint writes the notation, 'none' to denote a box with invisible borders.

- jj. *The standard defines the property "radical", contained within the attribute notation, contained within the element <menclase>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

On load, PowerPoint reads the 'radical' value of the notation attribute in an <menclase> element.

On save, PowerPoint does not write the 'radical' value of the notation attribute in an <menclase> element.

kk. *The standard defines the property "roundedbox", contained within the attribute notation, contained within the element <math><math>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

ll. *The standard defines the attribute style, contained within the element <math><math>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

mm. *The standard defines the attribute xref, contained within the element <math><math>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.481 Section 12.5 (MathML 2.0 Section 3.4.1), Subscript (msub)

a. *The standard defines the element <math><math>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

b. *The standard defines the attribute class, contained within the element <math><math>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

c. *The standard defines the attribute id, contained within the element <math><math>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

d. *The standard defines the attribute style, contained within the element <math><math>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

e. *The standard defines the attribute subscriptshift, contained within the element <math><math>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

f. *The standard defines the attribute xref, contained within the element <math><math>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

g. *The standard defines the element <math><math>*

This element is supported in Excel 2010 and Excel 2013.

h. *The standard defines the attribute class, contained within the element <math><math>*

This attribute is not supported in Excel 2010 or Excel 2013.

i. *The standard defines the attribute id, contained within the element <math><math>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute style, contained within the element <msub>*
This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute subscriptshift, contained within the element <msub>*
This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute xref, contained within the element <msub>*
This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the element <msub>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- n. *The standard defines the attribute class, contained within the element <msub>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- o. *The standard defines the attribute id, contained within the element <msub>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- p. *The standard defines the attribute style, contained within the element <msub>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- q. *The standard defines the attribute subscriptshift, contained within the element <msub>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- r. *The standard defines the attribute xref, contained within the element <msub>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.482 Section 12.5 (MathML 2.0 Section 3.4.2), Superscript (msup)

- a. *The standard defines the element <msup>*
This element is supported in MathML in Word 2010 and MathML in Word 2013.
This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
- b. *The standard defines the attribute class, contained within the element <msup>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- c. *The standard defines the attribute id, contained within the element <msup>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- d. *The standard defines the attribute style, contained within the element <msup>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute superscriptshift, contained within the element <msup>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- f. *The standard defines the attribute xref, contained within the element <msup>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- g. *The standard defines the element <msup>*
This element is supported in Excel 2010 and Excel 2013.
- h. *The standard defines the attribute class, contained within the element <msup>*
This attribute is not supported in Excel 2010 or Excel 2013.
- i. *The standard defines the attribute id, contained within the element <msup>*
This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute style, contained within the element <msup>*
This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute superscriptshift, contained within the element <msup>*
This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute xref, contained within the element <msup>*
This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the element <msup>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- n. *The standard defines the attribute class, contained within the element <msup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- o. *The standard defines the attribute id, contained within the element <msup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- p. *The standard defines the attribute style, contained within the element <msup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- q. *The standard defines the attribute superscriptshift, contained within the element <msup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- r. *The standard defines the attribute xref, contained within the element <msup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.483 Section 12.5 (MathML 2.0 Section 3.4.3), Subscript-superscript Pair (msubsup)

- a. *The standard defines the element <msubsup>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
- b. *The standard defines the attribute class, contained within the element <msubsup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- c. *The standard defines the attribute id, contained within the element <msubsup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- d. *The standard defines the attribute style, contained within the element <msubsup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- e. *The standard defines the attribute subscriptshift, contained within the element <msubsup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- f. *The standard defines the attribute superscriptshift, contained within the element <msubsup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- g. *The standard defines the attribute xref, contained within the element <msubsup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the element <msubsup>*

This element is supported in Excel 2010 and Excel 2013.
- i. *The standard defines the attribute class, contained within the element <msubsup>*

This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute id, contained within the element <msubsup>*

This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute style, contained within the element <msubsup>*

This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute subscriptshift, contained within the element <msubsup>*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute superscriptshift, contained within the element <msubsup>*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute xref, contained within the element <msubsup>*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the element <msubsup>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- p. *The standard defines the attribute class, contained within the element <msubsup>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the attribute id, contained within the element <msubsup>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute style, contained within the element <msubsup>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the attribute subscriptshift, contained within the element <msubsup>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- t. *The standard defines the attribute superscriptshift, contained within the element <msubsup>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- u. *The standard defines the attribute xref, contained within the element <msubsup>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.484 Section 12.5 (MathML 2.0 Section 3.4.4), Underscript (munder)

- a. *The standard defines the element <munder>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word maps an <munder> element to one of four different elements: <nAry>, <underbar>, <groupChr>, or <limLow>. MathML in Word identifies the type of <munder> element using the following criteria:

1. MathML in Word maps an <munder> element to an <nAry> element when the following conditions are true:
 - the accentunder attribute is false
 - the first child of the <munder> element is an nAry operator.
 - the operator is not contained inside any structure other than an <mml:mo>, <mml:mstyle>, or <mml:mrow> element
2. MathML in Word maps an <munder> element to an <underbar> element when the following conditions are true:
 - the accentunder attribute is false
 - the second child of an <munder> element is a <mo> element
 - the operator of the second child equals 0x0332

3. MathML in Word maps an <munder> element to a <groupchr> element when the following conditions are true:
 - when the accentunder attribute is false
 - one child of the <munder> element is an <mrow> element and another child is a <mo> element
 - the number of chars in the <mo> element is less than or equal to 1
4. Otherwise, MathML in Word maps the <munder> element to the <limLow> element.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

 - b. *The standard defines the attribute accentunder, contained within the element <munder>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
 - c. *The standard defines the attribute class, contained within the element <munder>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
 - d. *The standard defines the attribute id, contained within the element <munder>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
 - e. *The standard defines the attribute style, contained within the element <munder>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
 - f. *The standard defines the attribute xref, contained within the element <munder>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
 - g. *The standard defines the element <munder>*

This element is supported in Excel 2010 and Excel 2013.
 - h. *The standard defines the attribute accentunder, contained within the element <munder>*

This attribute is supported in Excel 2010 and Excel 2013.
 - i. *The standard defines the attribute class, contained within the element <munder>*

This attribute is not supported in Excel 2010 or Excel 2013.
 - j. *The standard defines the attribute id, contained within the element <munder>*

This attribute is not supported in Excel 2010 or Excel 2013.
 - k. *The standard defines the attribute style, contained within the element <munder>*

This attribute is not supported in Excel 2010 or Excel 2013.
 - l. *The standard defines the attribute xref, contained within the element <munder>*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the element <munder>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- n. *The standard defines the attribute accentunder, contained within the element <munder>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- o. *The standard defines the attribute class, contained within the element <munder>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- p. *The standard defines the attribute id, contained within the element <munder>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the attribute style, contained within the element <munder>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute xref, contained within the element <munder>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.485 Section 12.5 (MathML 2.0 Section 3.4.5), Overscript (mover)

- a. *The standard defines the element <mover>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word maps a <mover> element to one of five different elements: <nAry>, <overbar>, <accent>, <groupChr>, or <limUpp>. MathML in Word identifies the type of <mover> element using the following criteria:

1. MathML in Word maps a <mover> element to an <nAry> element when the following conditions are true:
 - the accent attribute is false
 - the core of the <mover> element is an nAry operator
 - the operator is not contained inside any structure other than an <mml:mo>, <mml:mstyle>, or <mml:mrow> element
2. MathML in Word maps a <mover> element to an <overbar> element when the following conditions are true:
 - the accent attribute is false
 - the second child of the <mover> element is a <mo> element
 - the operator equals 0xAF
3. MathML in Word maps a <mover> element to an <accent> element when the following conditions are true:
 - the accent attribute is true
 - the second child of the <mover> element is a <mo> element
 - the string-length of the operator is 1
4. MathML in Word maps a <mover> element to a <groupChr> element when the following conditions are true:

- the accent attribute is false
 - one child of the <mover> element is an <mrow> element and another child is a <mo> element
 - the number of characters in the <mo> element is less than or equal to 1
5. Otherwise, MathML in Word maps a <mover> element to a <limUpp> element.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute accent, contained within the element <mover>*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- c. *The standard defines the attribute class, contained within the element <mover>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute id, contained within the element <mover>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute style, contained within the element <mover>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the attribute xref, contained within the element <mover>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- g. *The standard defines the element <mover>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute accent, contained within the element <mover>*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute class, contained within the element <mover>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute id, contained within the element <mover>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute style, contained within the element <mover>*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute xref, contained within the element <mover>*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the element <mover>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- n. *The standard defines the attribute `accent`, contained within the element `<mover>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- o. *The standard defines the attribute `class`, contained within the element `<mover>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- p. *The standard defines the attribute `id`, contained within the element `<mover>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the attribute `style`, contained within the element `<mover>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute `xref`, contained within the element `<mover>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.486 Section 12.5 (MathML 2.0 Section 3.4.6), Underscript-overscript Pair (munderover)

- a. *The standard defines the element `<munderover>`*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word maps an `<munderover>` element to one of two different elements: an `<nAry>` element or a `<limLow>` element nested inside a `<limUpp>` element.

1. MathML in Word maps an `<munderover>` element to an `<nAry>` element when the following conditions are true:
 - the `accent` attribute is false
 - the first child of the `<munder>` element is an nAry operator
 - the operator is not contained inside any elements other than an `<mml:mo>`, `<mml:mstyle>`, or `<mml:mrow>`
2. Otherwise, the `<munderover>` element is mapped to a `<limLow>` element that is nested inside a `<limUpp>` element.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute `accent`, contained within the element `<munderover>`*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the `accent` attribute in an `<munderover>` element.

On save, OfficeArt Math in Word does not write the `accent` attribute in an `<munderover>` element.

- c. *The standard defines the attribute `accentunder`, contained within the element `<munderover>`*

This attribute is supported in MathML in Word 2010 and MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the `accentunder` attribute in an `<munderover>` element.

On save, OfficeArt Math in Word does not write the accentunder attribute in an <munderover> element.

- d. *The standard defines the attribute class, contained within the element <munderover>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- e. *The standard defines the attribute id, contained within the element <munderover>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- f. *The standard defines the attribute style, contained within the element <munderover>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- g. *The standard defines the attribute xref, contained within the element <munderover>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the element <munderover>*
This element is supported in Excel 2010 and Excel 2013.
- i. *The standard defines the attribute accent, contained within the element <munderover>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the accent attribute in an <munderover> element.
On save, Excel does not write the accent attribute in an <munderover> element.
- j. *The standard defines the attribute accentunder, contained within the element <munderover>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the accentunder attribute in an <munderover> element.
On save, Excel does not write the accentunder attribute in an <munderover> element.
- k. *The standard defines the attribute class, contained within the element <munderover>*
This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute id, contained within the element <munderover>*
This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the attribute style, contained within the element <munderover>*
This attribute is not supported in Excel 2010 or Excel 2013.
- n. *The standard defines the attribute xref, contained within the element <munderover>*
This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the element <munderover>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- p. *The standard defines the attribute accent, contained within the element <munderover>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
On load, PowerPoint reads the accent attribute in an <munderover> element.
On save, PowerPoint does not write the accent attribute in an <munderover> element.
- q. *The standard defines the attribute accentunder, contained within the element <munderover>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
On load, PowerPoint reads the accentunder attribute in an <munderover> element.
On save, PowerPoint does not write the accentunder attribute in an <munderover> element.
- r. *The standard defines the attribute class, contained within the element <munderover>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- s. *The standard defines the attribute id, contained within the element <munderover>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- t. *The standard defines the attribute style, contained within the element <munderover>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- u. *The standard defines the attribute xref, contained within the element <munderover>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.487 Section 12.5 (MathML 2.0 Section 3.4.7), Prescripts and Tensor Indices (mmultiscripts)

- a. *The standard defines the element <mmultiscripts>*
This element is supported in MathML in Word 2010 and MathML in Word 2013.
On load, MathML in Word maps the <mmultiscripts> element to a combination of the following elements:
 - <sSubSup>
 - <sSub>
 - <sSup>
 - <sPre>
 This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the <mmultiscripts> element.
On save, OfficeArt Math in Word writes the <mmultiscripts> element if prescripts are present.
- b. *The standard defines the attribute class, contained within the element <mmultiscripts>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute `id`, contained within the element `<mmultiscripts>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- d. *The standard defines the attribute `style`, contained within the element `<mmultiscripts>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- e. *The standard defines the attribute `subscriptshift`, contained within the element `<mmultiscripts>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- f. *The standard defines the attribute `superscriptshift`, contained within the element `<mmultiscripts>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- g. *The standard defines the attribute `xref`, contained within the element `<mmultiscripts>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the element `<mmultiscripts>`*
This element is supported in Excel 2010 and Excel 2013.
On load, Excel reads the `<mmultiscripts>` element.
On save, Excel writes the `<mmultiscripts>` element if prescripts are present.
- i. *The standard defines the attribute `class`, contained within the element `<mmultiscripts>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute `id`, contained within the element `<mmultiscripts>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute `style`, contained within the element `<mmultiscripts>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute `subscriptshift`, contained within the element `<mmultiscripts>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the attribute `superscriptshift`, contained within the element `<mmultiscripts>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- n. *The standard defines the attribute `xref`, contained within the element `<mmultiscripts>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- o. *The standard defines the element `<mmultiscripts>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the <mmultiscripts> element.

On save, PowerPoint writes the <mmultiscripts> element if prescripts are present.

- p. *The standard defines the attribute class, contained within the element <mmultiscripts>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the attribute id, contained within the element <mmultiscripts>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute style, contained within the element <mmultiscripts>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the attribute subscriptshift, contained within the element <mmultiscripts>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- t. *The standard defines the attribute superscriptshift, contained within the element <mmultiscripts>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- u. *The standard defines the attribute xref, contained within the element <mmultiscripts>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.488 Section 12.5 (MathML 2.0 Section 3.5.1), Table or Matrix (mtable)

- a. *The standard defines the element <mtable>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word may transform a MathML <mtable> element into either an equation array (<omml:eqArray> element) or a matrix (<omml:m> element).

MathML in Word transforms an <mtable> element as an <omml:eqArray> element if the following conditions are true:

- no frame lines
- no column lines
- no row lines
- all rows have exactly one column
- no labeled rows

Otherwise, MathML in Word transforms an <mtable> element as an <omml:m> element.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute align, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute alignmentscope, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute class, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute columnalign, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the attribute columnlines, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the columnlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, OfficeArt Math in Word does not write the columnlines attribute in an <mtable> element.

- g. *The standard defines the attribute columnspacing, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- h. *The standard defines the attribute columnwidth, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- i. *The standard defines the attribute displaystyle, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- j. *The standard defines the attribute equalcolumns, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- k. *The standard defines the attribute equalrows, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- l. *The standard defines the attribute frame, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the frame attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, OfficeArt Math in Word does not write the frame attribute in an <mtable> element.

- m. *The standard defines the attribute framespacing, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- n. *The standard defines the attribute groupalign, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the groupalign attribute in an <mtable> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, OfficeArt Math in Word does not write the groupalign attribute in an <mtable> element.

- o. *The standard defines the attribute id, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- p. *The standard defines the attribute minlabelspacing, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- q. *The standard defines the attribute rowalign, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- r. *The standard defines the attribute rowlines, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the rowlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, OfficeArt Math in Word does not write the rowlines attribute in an <mtable> element.

- s. *The standard defines the attribute rowspacing, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- t. *The standard defines the attribute side, contained within the element <mtable>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- u. *The standard defines the attribute style, contained within the element <mtable>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- v. *The standard defines the attribute width, contained within the element <mtable>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- w. *The standard defines the attribute xref, contained within the element <mtable>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- x. *The standard defines the element <mtable>*
This element is supported in Excel 2010 and Excel 2013.
- y. *The standard defines the attribute align, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- z. *The standard defines the attribute alignmentscope, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- aa. *The standard defines the attribute class, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- bb. *The standard defines the attribute columnalign, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- cc. *The standard defines the attribute columnlines, contained within the element <mtable>*
This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the columnlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, Excel does not write the columnlines attribute in an <mtable> element.
- dd. *The standard defines the attribute columnspacing, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- ee. *The standard defines the attribute columnwidth, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- ff. *The standard defines the attribute displaystyle, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- gg. *The standard defines the attribute equalcolumns, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.

- hh. *The standard defines the attribute equalrows, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- ii. *The standard defines the attribute frame, contained within the element <mtable>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the frame attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.
On save, Excel does not write the frame attribute in an <mtable> element.
- jj. *The standard defines the attribute framespacing, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- kk. *The standard defines the attribute groupalign, contained within the element <mtable>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the groupalign attribute in an <mtable> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, Excel does not write the groupalign attribute in an <mtable> element.
- ll. *The standard defines the attribute id, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- mm. *The standard defines the attribute minlabelspacing, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- nn. *The standard defines the attribute rowalign, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- oo. *The standard defines the attribute rowlines, contained within the element <mtable>*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the rowlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.
On save, Excel does not write the rowlines attribute in an <mtable> element.
- pp. *The standard defines the attribute rowspacing, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- qq. *The standard defines the attribute side, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- rr. *The standard defines the attribute style, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- ss. *The standard defines the attribute width, contained within the element <mtable>*
This attribute is not supported in Excel 2010 or Excel 2013.
- tt. *The standard defines the attribute xref, contained within the element <mtable>*

This attribute is not supported in Excel 2010 or Excel 2013.

uu. *The standard defines the element <mtable>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

vv. *The standard defines the attribute align, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ww. *The standard defines the attribute alignmentscope, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

xx. *The standard defines the attribute class, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

yy. *The standard defines the attribute columnalign, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

zz. *The standard defines the attribute columlines, contained within the element <mtable>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the columlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, PowerPoint does not write the columlines attribute in an <mtable> element.

aaa. *The standard defines the attribute columnspacing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

bbb. *The standard defines the attribute columnwidth, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ccc. *The standard defines the attribute displaystyle, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ddd. *The standard defines the attribute equalcolumns, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

eee. *The standard defines the attribute equalrows, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

fff. *The standard defines the attribute frame, contained within the element <mtable>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the frame attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, PowerPoint does not write the frame attribute in an <mtable> element.

ggg. *The standard defines the attribute framespacing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

hhh. *The standard defines the attribute groupalign, contained within the element <mtable>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the groupalign attribute in an <mtable> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <mtable> element.

iii. *The standard defines the attribute id, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

jjj. *The standard defines the attribute minlabelsparing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

kkk. *The standard defines the attribute rowalign, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

lll. *The standard defines the attribute rowlines, contained within the element <mtable>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the rowlines attribute in an <mtable> element. The presence of this attribute identifies the content in this element as a matrix, rather than an equation array.

On save, PowerPoint does not write the rowlines attribute in an <mtable> element.

mmm. *The standard defines the attribute rowspacing, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

nnn. *The standard defines the attribute side, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ooo. *The standard defines the attribute style, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ppp. *The standard defines the attribute width, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

qqq. *The standard defines the attribute xref, contained within the element <mtable>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.489 Section 12.5 (MathML 2.0 Section 3.5.2), Row in Table or Matrix (mtr)

a. *The standard defines the element <mtr>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

b. *The standard defines the attribute class, contained within the element <mtr>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute `columnalign`, contained within the element `<mtr>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- d. *The standard defines the attribute `groupalign`, contained within the element `<mtr>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the `groupalign` attribute in an `<mtr>` element. Only the 'left' and 'right' values of the `groupalign` attribute are supported. On save, OfficeArt Math in Word does not write the `groupalign` attribute in an `<mtr>` element.
- e. *The standard defines the attribute `id`, contained within the element `<mtr>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- f. *The standard defines the attribute `rowalign`, contained within the element `<mtr>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- g. *The standard defines the attribute `style`, contained within the element `<mtr>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the attribute `xref`, contained within the element `<mtr>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- i. *The standard defines the element `<mtr>`*
This element is supported in Excel 2010 and Excel 2013.
- j. *The standard defines the attribute `class`, contained within the element `<mtr>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute `columnalign`, contained within the element `<mtr>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute `groupalign`, contained within the element `<mtr>`*
This attribute is supported in Excel 2010 and Excel 2013.
On load, Excel reads the `groupalign` attribute in an `<mtr>` element. Only the 'left' and 'right' values of the `groupalign` attribute are supported. On save, Excel does not write the `groupalign` attribute in an `<mtr>` element.
- m. *The standard defines the attribute `id`, contained within the element `<mtr>`*
This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute rowalign, contained within the element <mtr>*
This attribute is not supported in Excel 2010 or Excel 2013.
- o. *The standard defines the attribute style, contained within the element <mtr>*
This attribute is not supported in Excel 2010 or Excel 2013.
- p. *The standard defines the attribute xref, contained within the element <mtr>*
This attribute is not supported in Excel 2010 or Excel 2013.
- q. *The standard defines the element <mtr>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- r. *The standard defines the attribute class, contained within the element <mtr>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- s. *The standard defines the attribute columnalign, contained within the element <mtr>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- t. *The standard defines the attribute groupalign, contained within the element <mtr>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the groupalign attribute in an <mtr> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <mtr> element.
- u. *The standard defines the attribute id, contained within the element <mtr>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- v. *The standard defines the attribute rowalign, contained within the element <mtr>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- w. *The standard defines the attribute style, contained within the element <mtr>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- x. *The standard defines the attribute xref, contained within the element <mtr>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.490 Section 12.5 (MathML 2.0 Section 3.5.3), Labeled Row in Table or Matrix (mlabeledtr)

- a. *The standard defines the element <mlabeledtr>*
This element is supported in MathML in Word 2010 and MathML in Word 2013.
On load, MathML in Word converts <mlabeledtr> elements into <mtr> elements.
This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the <mlabeledtr> element. The label argument is ignored, making an <mlabeledtr> element equivalent to an <mtr> element.

On save, OfficeArt Math in Word does not write the <mtable> element.

- b. *The standard defines the element <mtable>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel reads the <mtable> element. The label argument is ignored, making an <mtable> element equivalent to an <mtr> element.

On save, Excel does not write the <mtable> element.

- c. *The standard defines the element <mtable>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the <mtable> element. The label argument is ignored, making an <mtable> element equivalent to an <mtr> element.

On save, PowerPoint does not write the <mtable> element.

2.1.491 Section 12.5 (MathML 2.0 Section 3.5.4), Entry in Table or Matrix (mtd)

- a. *The standard defines the element <mtd>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- b. *The standard defines the attribute class, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute columnalign, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- d. *The standard defines the attribute colspan, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute groupalign, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the groupalign attribute in an <mtd> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, OfficeArt Math in Word does not write the groupalign attribute in an <mtd> element.

- f. *The standard defines the attribute id, contained within the element <mtd>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- g. *The standard defines the attribute rowalign, contained within the element <mtd>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the attribute rowspan, contained within the element <mtd>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- i. *The standard defines the attribute style, contained within the element <mtd>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- j. *The standard defines the attribute xref, contained within the element <mtd>*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- k. *The standard defines the element <mtd>*
This element is supported in Excel 2010 and Excel 2013.
- l. *The standard defines the attribute class, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.
- m. *The standard defines the attribute columnalign, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.
- n. *The standard defines the attribute columnspan, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.
- o. *The standard defines the attribute groupalign, contained within the element <mtd>*
This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the groupalign attribute in an <mtd> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, Excel does not write the groupalign attribute in an <mtd> element.
- p. *The standard defines the attribute id, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.
- q. *The standard defines the attribute rowalign, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.
- r. *The standard defines the attribute rowspan, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.
- s. *The standard defines the attribute style, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.

- t. *The standard defines the attribute xref, contained within the element <mtd>*
This attribute is not supported in Excel 2010 or Excel 2013.
- u. *The standard defines the element <mtd>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- v. *The standard defines the attribute class, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- w. *The standard defines the attribute columnalign, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- x. *The standard defines the attribute colspan, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- y. *The standard defines the attribute groupalign, contained within the element <mtd>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the groupalign attribute in an <mtd> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <mtd> element.
- z. *The standard defines the attribute id, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- aa. *The standard defines the attribute rowalign, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- bb. *The standard defines the attribute rowspan, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- cc. *The standard defines the attribute style, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- dd. *The standard defines the attribute xref, contained within the element <mtd>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.492 Section 12.5 (MathML 2.0 Section 3.5.5.4), Specifying alignment points using malignmark

- a. *The standard defines the element <maligngroup>*
This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word ignores the <maligngroup> element when the element is not inside a table that MathML in Word interprets as an equation array.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
- b. *The standard defines the attribute class, contained within the element <maligngroup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- c. *The standard defines the attribute groupalign, contained within the element <maligngroup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

On load, OfficeArt Math in Word reads the groupalign attribute in an <maligngroup> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, OfficeArt Math in Word does not write the groupalign attribute in an <maligngroup> element.

- d. *The standard defines the attribute id, contained within the element <maligngroup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- e. *The standard defines the attribute style, contained within the element <maligngroup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- f. *The standard defines the attribute xref, contained within the element <maligngroup>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- g. *The standard defines the element <malignmark>*

This element is supported in MathML in Word 2010 and MathML in Word 2013.

On load, MathML in Word ignores the <malignmark> element when the element is not inside a table that MathML in Word interprets as an equation array.

This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.

- h. *The standard defines the attribute class, contained within the element <malignmark>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- i. *The standard defines the attribute edge, contained within the element <malignmark>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- j. *The standard defines the attribute id, contained within the element <malignmark>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- k. *The standard defines the attribute style, contained within the element <malignmark>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- l. *The standard defines the attribute xref, contained within the element <malignmark>*

This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.

This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.

- m. *The standard defines the element <maligngroup>*

This element is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the attribute class, contained within the element <maligngroup>*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the attribute groupalign, contained within the element <maligngroup>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the groupalign attribute in an <maligngroup> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, Excel does not write the groupalign attribute in an <maligngroup> element.

- p. *The standard defines the attribute id, contained within the element <maligngroup>*

This attribute is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the attribute style, contained within the element <maligngroup>*

This attribute is not supported in Excel 2010 or Excel 2013.

- r. *The standard defines the attribute xref, contained within the element <maligngroup>*

This attribute is not supported in Excel 2010 or Excel 2013.

- s. *The standard defines the element <malignmark>*

This element is supported in Excel 2010 and Excel 2013.

- t. *The standard defines the attribute class, contained within the element <malignmark>*

This attribute is not supported in Excel 2010 or Excel 2013.

- u. *The standard defines the attribute edge, contained within the element <malignmark>*

This attribute is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the attribute id, contained within the element <malignmark>*

This attribute is not supported in Excel 2010 or Excel 2013.

- w. *The standard defines the attribute style, contained within the element <malignmark>*

This attribute is not supported in Excel 2010 or Excel 2013.

- x. *The standard defines the attribute xref, contained within the element <malignmark>*

This attribute is not supported in Excel 2010 or Excel 2013.

- y. *The standard defines the element <maligngroup>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- z. *The standard defines the attribute class, contained within the element <maligngroup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- aa. *The standard defines the attribute groupalign, contained within the element <maligngroup>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
On load, PowerPoint reads the groupalign attribute in an <maligngroup> element. Only the 'left' and 'right' values of the groupalign attribute are supported. On save, PowerPoint does not write the groupalign attribute in an <maligngroup> element.
- bb. *The standard defines the attribute id, contained within the element <maligngroup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- cc. *The standard defines the attribute style, contained within the element <maligngroup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- dd. *The standard defines the attribute xref, contained within the element <maligngroup>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- ee. *The standard defines the element <malignmark>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- ff. *The standard defines the attribute class, contained within the element <malignmark>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- gg. *The standard defines the attribute edge, contained within the element <malignmark>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- hh. *The standard defines the attribute id, contained within the element <malignmark>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- ii. *The standard defines the attribute style, contained within the element <malignmark>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- jj. *The standard defines the attribute xref, contained within the element <malignmark>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.493 Section 12.5 (MathML 2.0 Section 3.6.1), Bind Action to Sub-Expression (maction)

- a. *The standard defines the element <maction>*
This element is not supported in MathML in Word 2010 or MathML in Word 2013.
This element is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the <maction> element. Content other than the sub-expression identified by the selection attribute is ignored.
On save, OfficeArt Math in Word does not write the <maction> element.

- b. *The standard defines the attribute `actiontype`, contained within the element `<maction>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- c. *The standard defines the attribute `class`, contained within the element `<maction>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- d. *The standard defines the attribute `id`, contained within the element `<maction>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- e. *The standard defines the attribute `selection`, contained within the element `<maction>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is supported in OfficeArt Math in Word 2010 and OfficeArt Math in Word 2013.
On load, OfficeArt Math in Word reads the selection attribute in an `<maction>` element.
On save, OfficeArt Math in Word does not write the selection attribute in an `<maction>` element.
- f. *The standard defines the attribute `style`, contained within the element `<maction>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- g. *The standard defines the attribute `xref`, contained within the element `<maction>`*
This attribute is not supported in MathML in Word 2010 or MathML in Word 2013.
This attribute is not supported in OfficeArt Math in Word 2010 or OfficeArt Math in Word 2013.
- h. *The standard defines the element `<maction>`*
This element is supported in Excel 2010 and Excel 2013.
On load, Excel reads the `<maction>` element. Content other than the sub-expression identified by the selection attribute is ignored.
On save, Excel does not write the `<maction>` element.
- i. *The standard defines the attribute `actiontype`, contained within the element `<maction>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute `class`, contained within the element `<maction>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute `id`, contained within the element `<maction>`*
This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute `selection`, contained within the element `<maction>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the selection attribute in an <maction> element.

On save, Excel does not write the selection attribute in an <maction> element.

- m. *The standard defines the attribute style, contained within the element <maction>*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute xref, contained within the element <maction>*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the element <maction>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the <maction> element. Content other than the sub-expression identified by the selection attribute is ignored.

On save, PowerPoint does not write the <maction> element.

- p. *The standard defines the attribute actiontype, contained within the element <maction>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the attribute class, contained within the element <maction>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute id, contained within the element <maction>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the attribute selection, contained within the element <maction>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint reads the selection attribute in an <maction> element.

On save, PowerPoint does not write the selection attribute in an <maction> element.

- t. *The standard defines the attribute style, contained within the element <maction>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- u. *The standard defines the attribute xref, contained within the element <maction>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.494 Section 12.6, DDE Connections

- a. This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:dde-connection-decls>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- c. *The standard defines the element <text:Dde-links>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.495 Section 12.6.1, Container for DDE Connection Declarations

- a. This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <text:dde-connection-decls>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.496 Section 12.6.2, Declaring DDE Connections for Text Fields

- a. *The standard defines the element <text:dde-connection-decl>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <text:dde-connection-decls>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.497 Section 12.6.3, Declaring DDE Connections for Tables

- a. *The standard defines the element <odf:office:dde-source>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute office:automatic-update, contained within the element <office:dde-source>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute office:conversion-mode, contained within the element <office:dde-source>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute office:dde-application, contained within the element <office:dde-source>*

This attribute is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the attribute office:dde-item, contained within the element <office:dde-source>*

This attribute is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the attribute office:dde-topic, contained within the element <office:dde-source>*

This attribute is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the attribute office:name, contained within the element <office:dde-source>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.498 Section 13, SMIL Animations

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.499 Section 13.1.1, Animate

- a. *The standard defines the element <anim:animate>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.500 Section 13.1.2, Set

- a. *The standard defines the element <anim:set>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.501 Section 13.1.3, Animate Motion

- a. *The standard defines the element <anim:animateMotion>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute smil:calcMode, contained within the element <anim:animateMotion>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports the values "discrete" and "linear" for this attribute.

- c. *The standard defines the attribute svg:origin, contained within the element <anim:animateMotion>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute svg:path, contained within the element <anim:animateMotion>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.502 Section 13.1.4, Animate Color

- a. *The standard defines the element <anim:animateColor>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.503 Section 13.1.5, Animate Transform

- a. *The standard defines the element <anim:animateTransform>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.504 Section 13.1.6, Transition Filter

- a. *The standard defines the element <anim:transitionFilter>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute smil:direction, contained within the element <anim:transitionFilter>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the attribute smil:fadeColor, contained within the element <anim:transitionFilter>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the attribute `smil:mode`, contained within the element `<anim:transitionFilter>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- e. *The standard defines the attribute `smil:subtype`, contained within the element `<anim:transitionFilter>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the property "arrowHeadWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- g. *The standard defines the property "barnDoorWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

Subtypes "vertical" and "horizontal" are supported in both forward and reverse directions.

- h. *The standard defines the property "barnVeeWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- i. *The standard defines the property "barnZigZagWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the property "barWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- k. *The standard defines the property "bowTieWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the property "boxSnakesWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the property "clockWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

Only the "clockwiseTwelve" subtype in the forward direction is supported. All other subtypes and directions are mapped to this one.

- n. *The standard defines the property "diagonalWipe", contained within the attribute `smil:type`, contained within the element `<anim:transitionFilter>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- o. *The standard defines the property "doubleFanWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- p. *The standard defines the property "doubleSweepWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the property "ellipseWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

Only the "circle" subtype is supported. All other subtypes are mapped to this one.

- r. *The standard defines the property "eyeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the property "fade", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

All fade wipes map to "crossfade".

- t. *The standard defines the property "fanWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

Only the "centerTop" subtype in the forward direction is supported. All other fanwipe objects map to this one.

- u. *The standard defines the property "fourBoxWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

The fourBoxWipe property in combination with direction "forward" maps to "cornersOut". The fourBoxWipe property in combination with direction "reverse" maps to "cornersIn".

- v. *The standard defines the property "hexagonWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- w. *The standard defines the property "irisWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

Subtypes "rectangle" and "diamond" are supported in both forward and reverse directions.

- x. *The standard defines the property "miscDiagonalWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- y. *The standard defines the property "miscShapeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- z. *The standard defines the property "parallelSnakesWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- aa. *The standard defines the property "pentagonWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- bb. *The standard defines the property "pinWheelWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

Only the "twoBladeVertical" and the "fourBlade" subtypes in the forward directions are supported. All other subtypes and directions map to the clockWipe, single spoke transition on load in PowerPoint.

- cc. *The standard defines the property "pushWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- dd. *The standard defines the property "roundRectWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ee. *The standard defines the property "saloonDoorWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ff. *The standard defines the property "singleSweepWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- gg. *The standard defines the property "slideWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- hh. *The standard defines the property "snakeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ii. *The standard defines the property "spiralWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- jj. *The standard defines the property "starWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- kk. *The standard defines the property "triangleWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ll. *The standard defines the property "veeWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- mm. *The standard defines the property "waterfallWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- nn. *The standard defines the property "windshieldWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- oo. *The standard defines the property "zigZagWipe", contained within the attribute smil:type, contained within the element <anim:transitionFilter>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.505 Section 13.2, Animation Model Attributes

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.506 Section 13.3, Common Animation Attributes

- a. *The standard defines the attribute anim:id*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.507 Section 13.3.1, Animation Target Attributes

- a. *The standard defines the attribute smil:targetElement*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.508 Section 13.3.2, Animation Function Attributes

- a. *The standard defines the attribute anim:formula*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, the entire animation will be lost if the operators "exp" or "log" are present. On save, the entire animation will be lost if any of the following elements are present in the native PowerPoint animation: "^", "?", "==", ">=", "<=", "!=", "!".

- b. *The standard defines the attribute anim:sub-item*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- c. *The standard defines the attribute smil:accumulate*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the attribute `smil:additive`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the attribute `smil:attributeName`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the attribute `smil:by`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- g. *The standard defines the attribute `smil:calcMode`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- h. *The standard defines the property "discrete", contained within the attribute `smil:calcMode`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- i. *The standard defines the property "linear", contained within the attribute `smil:calcMode`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- j. *The standard defines the property "paced", contained within the attribute `smil:calcMode`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- k. *The standard defines the property "spline", contained within the attribute `smil:calcMode`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the attribute `smil:from`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- m. *The standard defines the attribute `smil:keySplines`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute `smil:keyTimes`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- o. *The standard defines the attribute `smil:to`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- p. *The standard defines the attribute `smil:values`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.509 Section 13.4, Animation Timing

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.510 Section 13.4.1, Animation Timing Attributes

- a. *The standard defines the attribute `smil:accelerate`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute smil:autoreverse*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the attribute smil:begin*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute smil:decelerate*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- e. *The standard defines the attribute smil:dur*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the attribute smil:end*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- g. *The standard defines the attribute smil:endsync*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- h. *The standard defines the attribute smil:fill*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- i. *The standard defines the property "auto", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the property "default", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- k. *The standard defines the property "freeze", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the property "hold", contained within the attribute smil:fill*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- m. *The standard defines the property "remove", contained within the attribute smil:fill*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- n. *The standard defines the property "transition", contained within the attribute smil:fill*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- o. *The standard defines the attribute smil:fillDefault*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- p. *The standard defines the attribute smil:RepeatCount*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- q. *The standard defines the attribute smil:restart*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the attribute `smil:restartDefault`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.511 Section 13.4.2, Parallel Animations

- a. *The standard defines the element `<anim:par>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.512 Section 13.4.3, Sequential Animations

- a. *The standard defines the element `<anim:seq>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.513 Section 13.4.4, Iterative Animations

- a. *The standard defines the element `<anim:iterate>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute `anim:iterate-interval`, contained within the element `<anim:iterate>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the attribute `anim:iterate-type`, contained within the element `<anim:iterate>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute `anim:sub-item`, contained within the element `<anim:iterate>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the attribute `smil:targetElement`, contained within the element `<anim:iterate>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.514 Section 13.5, Media Elements

- a. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.515 Section 13.5.1, Audio

- a. *The standard defines the element `<anim:audio>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- b. *The standard defines the attribute `anim:audio-level`, contained within the element `<anim:audio>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- c. *The standard defines the attribute `xlink:href`, contained within the element `<anim:audio>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.516 Section 13.6, Special Elements

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.517 Section 13.6.1, Command

- a. *The standard defines the element <anim:command>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute anim:command, contained within the element <anim:command>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.518 Section 14, Styles

- a. This is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.

- b. This is supported in Excel 2010 and Excel 2013.

This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.519 Section 14.1, Style Element

- a. *The standard defines the element <style:style>*

This element is supported in Word 2010 and Word 2013.

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute style:auto-update, contained within the element <style:style>*

This attribute is supported in Word 2010 and Word 2013.

Word 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:class, contained within the element <style:style>*

This attribute is not supported in Word 2010 or Word 2013.

Word 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `style:data-style-name`, contained within the element `<style:style>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `style:default-outline-level`, contained within the element `<style:style>`*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `style:display-name`, contained within the element `<style:style>`*

This attribute is supported in Word 2010 and Word 2013.

Word 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute `style:family`, contained within the element `<style:style>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- h. *The standard defines the property "chart", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the property "control", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2010 or Word 2013.

- j. *The standard defines the property "default", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2010 or Word 2013.

- k. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2010 or Word 2013.

- l. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

On load, Word does not support paragraph, text, or list properties from styles of the graphic family.

On save, Word always writes "lr-tb" as the writing mode for styles of the graphic family.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- m. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- n. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2010 or Word 2013.

- o. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

- p. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

- q. *The standard defines the property "table", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

- r. *The standard defines the property "table-cell", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

- s. *The standard defines the property "table-column", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

- t. *The standard defines the property "table-page", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Word 2010 or Word 2013.

- u. *The standard defines the property "table-row", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

- v. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- w. *The standard defines the attribute style:list-style-name, contained within the element <style:style>*

This attribute is supported in Word 2010 and Word 2013.

- x. *The standard defines the attribute style:master-page-name, contained within the element <style:style>*

This attribute is supported in Word 2010 and Word 2013.

On load, if the value of the style:master-page-name attribute for the first paragraph of the document is "" or missing, then Word will apply a default master page style named "Standard".

- y. *The standard defines the attribute style:name, contained within the element <style:style>*

This attribute is supported in Word 2010 and Word 2013.

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word requires that a style name be unique not only within the same style:family attribute but within the entire file. If a style with a duplicate name exists, Word ignores the duplicate style.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- z. *The standard defines the attribute style:next-style-name, contained within the element <style:style>*

This attribute is supported in Word 2010 and Word 2013.

- aa. *The standard defines the attribute style:parent-style-name, contained within the element <style:style>*

This attribute is supported in Word 2010 and Word 2013.

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- bb. *The standard defines the element <style:style>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel maps the "default" style to its "normal" style. On save, Excel maps its "normal" style back to "default".

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

cc. *The standard defines the attribute style:auto-update, contained within the element <style:style>*

This attribute is not supported in Excel 2010 or Excel 2013.

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>

- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

dd. *The standard defines the attribute style:class, contained within the element <style:style>*

This attribute is not supported in Excel 2010 or Excel 2013.

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

ee. *The standard defines the attribute `style:data-style-name`, contained within the element `<style:style>`*

This attribute is supported in Excel 2010 and Excel 2013.

ff. *The standard defines the attribute `style:default-outline-level`, contained within the element `<style:style>`*

This attribute is not supported in Excel 2010 or Excel 2013.

gg. *The standard defines the attribute `style:display-name`, contained within the element `<style:style>`*

This attribute is supported in Excel 2010 and Excel 2013.

On save, Excel determines if an Excel style's name is a valid RNG (Relax-NG) name. If it is, the Excel style's name will be output to the `style:name` attribute. If the Excel style's name is not a valid RNG name, the name will be modified to make it a valid RNG escaped name before being output to the `style:name` attribute. If the style name is an escaped name, the original name will be output to the `style:display-name` attribute.

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

hh. *The standard defines the attribute `style:family`, contained within the element `<style:style>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`

- <draw:text-box>
 - <draw:custom-shape>
- ii. *The standard defines the property "chart", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

- jj. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

- kk. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- ll. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

mm. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

nn. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

oo. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

pp. *The standard defines the property "table", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

qq. *The standard defines the property "table-cell", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

rr. *The standard defines the property "table-column", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

ss. *The standard defines the property "table-row", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

tt. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

Excel uses text styles for headers, footers and Rich text formatting in cells.

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

uu. *The standard defines the attribute style:list-style-name, contained within the element <style:style>*

This attribute is not supported in Excel 2010 or Excel 2013.

vv. *The standard defines the attribute style:master-page-name, contained within the element <style:style>*

This attribute is supported in Excel 2010 and Excel 2013.

ww. *The standard defines the attribute style:name, contained within the element <style:style>*

This attribute is supported in Excel 2010 and Excel 2013.

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel requires that a style name be unique not only within the same style:family attribute but within the entire file. If a style with a duplicate name exists, Excel ignores the duplicate style.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

xx. *The standard defines the attribute style:next-style-name, contained within the element <style:style>*

This attribute is not supported in Excel 2010 or Excel 2013.

yy. *The standard defines the attribute style:parent-style-name, contained within the element <style:style>*

This attribute is supported in Excel 2010 and Excel 2013.

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes

- shapes
- SmartArt
- chart titles
- labels

zz. *The standard defines the element <style:style>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

aaa. *The standard defines the attribute style:auto-update, contained within the element <style:style>*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

bbb. *The standard defines the attribute style:class, contained within the element <style:style>*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

ccc. *The standard defines the attribute style:data-style-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

ddd. *The standard defines the attribute style:default-outline-level, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

eee. *The standard defines the attribute style:display-name, contained within the element <style:style>*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>

- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

fff. *The standard defines the attribute style:family, contained within the element <style:style>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

ggg. *The standard defines the property "chart", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

hhh. *The standard defines the property "control", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

iii. *The standard defines the property "default", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

jjj. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

kkk. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

III. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

mmm. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

nnn. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

ooo. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

ppp. *The standard defines the property "table", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

qqq. *The standard defines the property "table-cell", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

rrr. *The standard defines the property "table-column", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

sss. *The standard defines the property "table-page", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

ttt. *The standard defines the property "table-row", contained within the attribute style:family, contained within the element <style:style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

uuu. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

vvv. *The standard defines the attribute style:list-style-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

www. *The standard defines the attribute style:master-page-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

xxx. *The standard defines the attribute style:name, contained within the element <style:style>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>

- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint requires that a style name be unique not only within the same style:family attribute but within the entire file. If a style with a duplicate name exists, PowerPoint ignores the duplicate style.

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

yyy. *The standard defines the attribute style:next-style-name, contained within the element <style:style>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

zzz. *The standard defines the attribute style:parent-style-name, contained within the element <style:style>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.520 Section 14.1.1, Style Mappings

- a. *The standard defines the element <style:map>*

This element is not supported in Word 2010 or Word 2013.

Word 2013 does not support this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:map>*

Excel 2013 does not support this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:apply-style-name`, contained within the element `<style:map>`, contained within the parent element `<style:style>`*

This attribute is supported in Excel 2010 and Excel 2013.

1. Excel conditional formatting does not support the following formatting:

alignment formatting

font size

font face

thick and double borders

diagonal borders

2. Excel does not save pattern fills.

- d. *The standard defines the attribute `style:base-cell-address`, contained within the element `<style:map>`, contained within the parent element `<style:style>`*

This attribute is supported in Excel 2010 and Excel 2013.

The value of this attribute is the address of the upper-left cell of the conditional formatting's bounding reference. This attribute may be used in discontinuous ranges with conditional formatting.

- e. *The standard defines the attribute `style:condition`, contained within the element `<style:map>`, contained within the parent element `<style:style>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel conditional formatting does not support the following conditions:

1. "Stop if true" condition; Excel always stops if the condition has been met.
2. Conditions describing data bars, icon sets, or color scales.
3. Conditions describing discontinuous ranges for Top 10, Top 10%, Bottom 10, Bottom 10%, Above Average with standard deviation, and Below Average with standard deviation rules.

Excel conditional formatting supports the following conditions:

1. Conditions using the following: is-true-formula, cell-content-is-between, cell-content-is-not-between, and cell-content.
2. Conditions describing discontinuous ranges for Above and Below Average rules WITHOUT standard deviation.

Additionally, the following features apply to Excel's treatment of the style:condition attribute in conditional formatting:

1. Multiple rules with the same criteria could round trip as a single rule.
2. Some rules will round trip back as a formula instead of a friendly name (like highlight dups).

f. *The standard defines the element <style:map>*

PowerPoint 2013 does not support this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.521 Section 14.2, Default Styles

a. *The standard defines the element <style:default-style>*

This element is supported in Word 2010 and Word 2013.

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "control", contained within the attribute draw:family, contained within the element <style:default-style>*

This property is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property "graphic", contained within the attribute draw:family, contained within the element <style:default-style>*

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the property "chart", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2010 or Word 2013.

- e. *The standard defines the property "control", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2010 or Word 2013.

- f. *The standard defines the property "default", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2010 or Word 2013.

- g. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2010 or Word 2013.

- h. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

On load, Word does not support paragraph or text properties from styles of the graphic family.

On save, Word always writes "lr-tb" as the writing mode for styles of the graphic family.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- i. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- j. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2010 or Word 2013.

- k. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

- l. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

- m. *The standard defines the property "table", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

- n. *The standard defines the property "table-cell", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

- o. *The standard defines the property "table-column", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

- p. *The standard defines the property "table-page", contained within the attribute style:family, contained within the element <style:default-style>*

This property is not supported in Word 2010 or Word 2013.

- q. *The standard defines the property "table-row", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

- r. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:default-style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- s. *The standard defines the element <style:default-style>*

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- t. *The standard defines the element <style:default-style>, contained within the parent element <office:styles>*

This element is not supported in Excel 2010 or Excel 2013.

- u. *The standard defines the property "control", contained within the attribute draw:family, contained within the element <style:default-style>*

This property is not supported in Excel 2010 or Excel 2013.

- v. *The standard defines the property "graphic", contained within the attribute draw:family, contained within the element <style:default-style>*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- w. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- x. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- y. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- z. *The standard defines the element <style:default-style>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>

- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

- aa. *The standard defines the property "control", contained within the attribute draw:family, contained within the element <style:default-style>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- bb. *The standard defines the property "graphic", contained within the attribute draw:family, contained within the element <style:default-style>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- cc. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

dd. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

ee. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:default-style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.522 Section 14.3, Page Layout

a. *The standard defines the element <style:page-layout>*

This element is supported in Word 2010 and Word 2013.

b. *The standard defines the attribute style:name, contained within the element <style:page-layout>*

This attribute is supported in Word 2010 and Word 2013.

c. *The standard defines the attribute style:page-usage, contained within the element <style:page-layout>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute style:page-layout*
This attribute is supported in Excel 2010 and Excel 2013.
- e. *The standard defines the attribute style:name, contained within the element <style:page-layout>*
This attribute is supported in Excel 2010 and Excel 2013.
- f. *The standard defines the attribute style:page-layout-properties, contained within the element <style:page-layout>*
This attribute is supported in Excel 2010 and Excel 2013.
- g. *The standard defines the attribute style:page-usage, contained within the element <style:page-layout>*
This attribute is not supported in Excel 2010 or Excel 2013.
- h. *The standard defines the element <style:page-layout>*
This element is supported in PowerPoint 2010 and PowerPoint 2013.
- i. *The standard defines the attribute style:name, contained within the element <style:page-layout>*
This attribute is supported in PowerPoint 2010 and PowerPoint 2013.
- j. *The standard defines the attribute style:page-usage, contained within the element <style:page-layout>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.523 Section 14.3.1, Header and Footer Styles

- a. *The standard defines the element <style:footer-style>*
This element is supported in Word 2010 and Word 2013.
- b. *The standard defines the element <style:header-style>*
This element is supported in Word 2010 and Word 2013.
- c. *The standard defines the attribute style:footer-style*
This attribute is supported in Excel 2010 and Excel 2013.
- d. *The standard defines the attribute style:header-style*
This attribute is supported in Excel 2010 and Excel 2013.
- e. *The standard defines the attribute style:header-footer-properties, contained within the element <style:footer-style>*
This attribute is supported in Excel 2010 and Excel 2013.
- f. *The standard defines the attribute style:header-footer-properties, contained within the element <style:header-style>*
This attribute is supported in Excel 2010 and Excel 2013.
- g. *The standard defines the element <style:footer-style>*
This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- h. *The standard defines the element <style:header-style>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.524 Section 14.4, Master Pages

- a. *The standard defines the element <style:master-page>*

This element is supported in Word 2010 and Word 2013.

On save, Word creates a new master page and associates it with a new application generated name.

- b. *The standard defines the attribute draw:style-name, contained within the element <style:master-page>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute style:display-name, contained within the element <style:master-page>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute style:name, contained within the element <style:master-page>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute style:next-style-name, contained within the element <style:master-page>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word maintains the style:next-style-name attribute of the first page by allowing all subsequent pages to inherit their headers/footers from the style specified by the style:next-style-name attribute.
2. Word only saves the style:next-style-name attribute if the master page for the first page of the document differs from the second page.

- f. *The standard defines the attribute style:page-layout-name, contained within the element <style:master-page>*

This attribute is supported in Word 2010 and Word 2013.

- g. This is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute draw:style-name, contained within the element <style:master-page>, contained within the parent element <office:master-styles>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute style:display-name, contained within the element <style:master-page>, contained within the parent element <office:master-styles>*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel does not read or display a master style name.

- j. *The standard defines the attribute style:name, contained within the element <style:master-page>, contained within the parent element <office:master-styles>*

This attribute is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the attribute `style:next-style-name`, contained within the element `<style:master-page>`, contained within the parent element `<office:master-styles>`*
- This attribute is not supported in Excel 2010 or Excel 2013.
- l. *The standard defines the attribute `style:page-layout-name`, contained within the element `<style:master-page>`, contained within the parent element `<office:master-styles>`*

This attribute is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the element `<presentation:notes>`, contained within the parent element `<style:master-page>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

1. Only the notes for the first master page will be loaded into PowerPoint as the master notes. All other `<presentation:notes>` elements for other master pages will be ignored.
2. If there are any `<draw:object>` child elements of the `<presentation:notes>` element for a master page, those elements will be lost.

- n. *The standard defines the element `<style:master-page>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- o. *The standard defines the attribute `draw:style-name`, contained within the element `<style:master-page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- p. *The standard defines the attribute `style:display-name`, contained within the element `<style:master-page>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- q. *The standard defines the attribute `style:name`, contained within the element `<style:master-page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint has two levels of masters: masters and layouts. Masters have the naming convention "Master#-[Master Name]" while layouts take the form "Master#-Layout#-[Layout Name]". On load, PowerPoint matches layout pages with their corresponding master pages (those having the same Master#), as one of the inheriting layouts. Master pages whose names do not conform to either of these formats, and layout pages that do not have a corresponding master, are treated as masters and are given the default PowerPoint layouts.

- r. *The standard defines the attribute `style:next-style-name`, contained within the element `<style:master-page>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the attribute `style:page-layout-name`, contained within the element `<style:master-page>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

In PowerPoint, if different masters or pages have different size dimensions, they will all default to the dimensions of the last master that is not recognized to be a layout.

2.1.525 Section 14.4.1, Headers and Footers

- a. *The standard defines the element `<style:footer>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:display, contained within the element <style:footer>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the element <style:footer-left>*

This element is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute style:display, contained within the element <style:footer-left>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the element <style:footer-right>*

This element is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute style:display, contained within the element <style:footer-right>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the element <style:header>*

This element is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute style:display, contained within the element <style:header>*

This attribute is supported in Word 2010 and Word 2013.

- i. *The standard defines the element <style:header-left>*

This element is supported in Word 2010 and Word 2013.

- j. *The standard defines the attribute style:display, contained within the element <style:header-left>*

This attribute is supported in Word 2010 and Word 2013.

- k. *The standard defines the element <style:header-right>*

This element is supported in Word 2010 and Word 2013.

- l. *The standard defines the attribute style:display, contained within the element <style:header-right>*

This attribute is supported in Word 2010 and Word 2013.

- m. *The standard defines the element <style:region-center>, contained within the parent element <style:footer>*

This element is not supported in Word 2010 or Word 2013.

- n. *The standard defines the element <style:region-center>, contained within the parent element <style:footer-left>*

This element is not supported in Word 2010 or Word 2013.

- o. *The standard defines the element <style:region-center>, contained within the parent element <style:footer-right>*

This element is not supported in Word 2010 or Word 2013.

- p. *The standard defines the element <style:region-center>, contained within the parent element <style:header>*

This element is not supported in Word 2010 or Word 2013.

- q. *The standard defines the element <style:region-center>, contained within the parent element <style:header-left>*

This element is not supported in Word 2010 or Word 2013.

- r. *The standard defines the element <style:region-center>, contained within the parent element <style:header-right>*

This element is not supported in Word 2010 or Word 2013.

- s. *The standard defines the element <style:region-left>, contained within the parent element <style:footer>*

This element is not supported in Word 2010 or Word 2013.

- t. *The standard defines the element <style:region-left>, contained within the parent element <style:footer-left>*

This element is not supported in Word 2010 or Word 2013.

- u. *The standard defines the element <style:region-left>, contained within the parent element <style:footer-right>*

This element is not supported in Word 2010 or Word 2013.

- v. *The standard defines the element <style:region-left>, contained within the parent element <style:header>*

This element is not supported in Word 2010 or Word 2013.

- w. *The standard defines the element <style:region-left>, contained within the parent element <style:header-left>*

This element is not supported in Word 2010 or Word 2013.

- x. *The standard defines the element <style:region-left>, contained within the parent element <style:header-right>*

This element is not supported in Word 2010 or Word 2013.

- y. *The standard defines the element <style:region-right>, contained within the parent element <style:footer>*

This element is not supported in Word 2010 or Word 2013.

- z. *The standard defines the element <style:region-right>, contained within the parent element <style:footer-left>*

This element is not supported in Word 2010 or Word 2013.

- aa. *The standard defines the element <style:region-right>, contained within the parent element <style:footer-right>*

This element is not supported in Word 2010 or Word 2013.

- bb. *The standard defines the element <style:region-right>, contained within the parent element <style:header>*

This element is not supported in Word 2010 or Word 2013.

- cc. *The standard defines the element <style:region-right>, contained within the parent element <style:header-left>*

This element is not supported in Word 2010 or Word 2013.

- dd. *The standard defines the element <style:region-right>, contained within the parent element <style:header-right>*

This element is not supported in Word 2010 or Word 2013.

- ee. *The standard defines the attribute style:display, contained within the element <style:footer>, contained within the parent element <style:master-page>*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel drops this attribute, and causes a header or footer to be dropped completely if present.

- ff. *The standard defines the attribute style:display, contained within the element <style:header>, contained within the parent element <style:master-page>*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel drops this attribute, and causes a header or footer to be dropped completely if present.

- gg. *The standard defines the attribute style:display, contained within the element <style:header-left>, contained within the parent element <style:master-page>*

This attribute is supported in Excel 2010 and Excel 2013.

- hh. *The standard defines the element <style:region-center>, contained within the parent element <style:footer>*

This element is supported in Excel 2010 and Excel 2013.

- ii. *The standard defines the element <style:region-center>, contained within the parent element <style:footer-left>*

This element is supported in Excel 2010 and Excel 2013.

- jj. *The standard defines the element <style:region-center>, contained within the parent element <style:header>*

This element is supported in Excel 2010 and Excel 2013.

- kk. *The standard defines the element <style:region-center>, contained within the parent element <style:header-left>*

This element is supported in Excel 2010 and Excel 2013.

- ll. *The standard defines the element <style:region-left>, contained within the parent element <style:footer>*

This element is supported in Excel 2010 and Excel 2013.

- mm. *The standard defines the element <style:region-left>, contained within the parent element <style:header>*

This element is supported in Excel 2010 and Excel 2013.

nn. *The standard defines the element <style:region-left>, contained within the parent element <style:header-left>*

This element is supported in Excel 2010 and Excel 2013.

oo. *The standard defines the element <style:region-left>, contained within the parent element <style:footer-left>*

This element is supported in Excel 2010 and Excel 2013.

pp. *The standard defines the element <style:region-right>, contained within the parent element <style:footer>*

This element is supported in Excel 2010 and Excel 2013.

qq. *The standard defines the element <style:region-right>, contained within the parent element <style:header>*

This element is supported in Excel 2010 and Excel 2013.

rr. *The standard defines the element <style:region-right>, contained within the parent element <style:header-left>*

This element is supported in Excel 2010 and Excel 2013.

ss. *The standard defines the element <style:region-right>, contained within the parent element <style:footer-left>*

This element is supported in Excel 2010 and Excel 2013.

tt. *The standard defines the attribute style:display, contained within the element <style:footer-left>, contained within the parent element <style:master-page>*

This attribute is supported in Excel 2010 and Excel 2013.

uu. *The standard defines the element <style:footer>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

vv. *The standard defines the element <style:footer-left>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

ww. *The standard defines the element <style:header>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

xx. *The standard defines the element <style:header-left>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.526 Section 14.4.2, Presentation Notes

a. This is not supported in Excel 2010 or Excel 2013.

b. *The standard defines the element <presentation:notes>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

Certain OLE objects cannot be saved by PowerPoint when they exist in the notes section of a master page.

2.1.527 Section 14.5, Table Templates

- a. *The standard defines the element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the attribute table:table-template*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.528 Section 14.5.1, Row and Column Styles

- a. *The standard defines the element <table:body>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- b. *The standard defines the element <table:even-columns>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- c. *The standard defines the element <table:even-rows>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- d. *The standard defines the element <table:first-column>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- e. *The standard defines the element <table:first-row>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- f. *The standard defines the element <table:last-column>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- g. *The standard defines the element <table:last-row>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- h. *The standard defines the element <table:odd-columns>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- i. *The standard defines the element <table:odd-rows>, contained within the parent element <table:table-template>*
This element is not supported in Word 2010 or Word 2013.
- j. This is not supported in Excel 2010 or Excel 2013.

2.1.529 Section 14.6, Font Face Declaration

- a. *The standard defines the element <style:font-face>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels. Font face declarations are not written. Instead, on save, the fo:font-family attribute specifies the font face.

- b. *The standard defines the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

Font face declarations are supported only on load and are not written. Instead, on save the fo:font-family attribute specifies the font face.

- c. *The standard defines the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This element is not supported in Excel 2010 or Excel 2013.

On load, Excel ignores the <style:font-face> element, all attributes of the <style:font-face> element, and all child elements. Excel reads the <style:font-name> attribute to determine the font to apply.

On save, Excel writes out the <style:font-face> element, along with values for the <style:name> and <svg:font-family> attributes.

This element is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>

- <draw:text-box>
- <draw:custom-shape>

Font face declarations are supported only on load and are not written. Instead, on save the fo:font-family attribute specifies the font face.

2.1.530 Section 14.6.1, CSS2/SVG Font Descriptors

- a. *The standard defines the element <style:font-face>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute svg:accent-height, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute svg:alphabetic, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute svg:ascent, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute svg:bbox, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute svg:cap-height, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute svg:descent, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute svg:font-family, contained within the element <style:font-face>*

This attribute is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute svg:font-size, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute svg:font-stretch, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- k. *The standard defines the attribute svg:font-style, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- l. *The standard defines the attribute svg:font-variant, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute `svg:font-weight`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- n. *The standard defines the attribute `svg:hanging`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- o. *The standard defines the attribute `svg:ideographic`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- p. *The standard defines the attribute `svg:mathematical`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- q. *The standard defines the attribute `svg:overline-position`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- r. *The standard defines the attribute `svg:overline-thickness`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- s. *The standard defines the attribute `svg:panose-1`, contained within the element `<style:font-face>`*
This attribute is supported in Word 2010 and Word 2013.
- t. *The standard defines the attribute `svg:slope`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- u. *The standard defines the attribute `svg:stemh`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- v. *The standard defines the attribute `svg:stemv`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- w. *The standard defines the attribute `svg:strikethrough-position`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- x. *The standard defines the attribute `svg:strikethrough-thickness`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- y. *The standard defines the attribute `svg:underline-position`, contained within the element `<style:font-face>`*
This attribute is not supported in Word 2010 or Word 2013.
- z. *The standard defines the attribute `svg:underline-thickness`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- aa. *The standard defines the attribute `svg:unicode-range`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- bb. *The standard defines the attribute `svg:units-per-em`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- cc. *The standard defines the attribute `svg:v-alphabetic`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- dd. *The standard defines the attribute `svg:v-hanging`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- ee. *The standard defines the attribute `svg:v-mathematical`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- ff. *The standard defines the attribute `svg:width`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- gg. *The standard defines the attribute `svg:x-height`, contained within the element `<style:font-face>`*

This attribute is not supported in Word 2010 or Word 2013.

- hh. *The standard defines the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This element is not supported in Word 2010 or Word 2013.

- ii. *The standard defines the element `<svg:font-face-format>`, contained within the parent element `<svg:font-face-uri>`*

This element is not supported in Word 2010 or Word 2013.

- jj. *The standard defines the element `<svg:font-face-name>`, contained within the parent element `<svg:font-face-src>`*

This element is not supported in Word 2010 or Word 2013.

- kk. *The standard defines the element `<svg:font-face-src>`, contained within the parent element `<style:font-face>`*

This element is not supported in Word 2010 or Word 2013.

- ll. *The standard defines the element `<svg:font-face-uri>`, contained within the parent element `<svg:font-face-src>`*

This element is not supported in Word 2010 or Word 2013.

- mm. *The standard defines the element `<style:font-face>`*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

nn. *The standard defines the attribute `svg:accent-height`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

oo. *The standard defines the attribute `svg:alphabetic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

pp. *The standard defines the attribute `svg:ascent`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

qq. *The standard defines the attribute `svg:bbox`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

rr. *The standard defines the attribute `svg:cap-height`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ss. *The standard defines the attribute `svg:descent`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

tt. *The standard defines the attribute `svg:font-family`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel ignores the `<style:font-face>` element, all attributes of the `<style:font-face>` element, and all child elements. Excel reads the `<style:font-name>` attribute to determine the font to apply.

On save, Excel writes out the `<style:font-face element>`, along with values for the `<style:name>` and `<svg:font-family>` attributes.

uu. *The standard defines the attribute `svg:font-size`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

vv. *The standard defines the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ww. *The standard defines the property "condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

xx. *The standard defines the property "expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

yy. *The standard defines the property "extra-condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

zz. *The standard defines the property "extra-expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

aaa. *The standard defines the property "normal", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

bbb. *The standard defines the property "semi-condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

ccc. *The standard defines the property "semi-expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

ddd. *The standard defines the property "ultra-condensed", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

eee. *The standard defines the property "ultra-expanded", contained within the attribute `svg:font-stretch`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This property is not supported in Excel 2010 or Excel 2013.

fff. *The standard defines the attribute `svg:font-style`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ggg. *The standard defines the attribute `svg:font-variant`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

hhh. *The standard defines the attribute `svg:font-weight`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

iii. *The standard defines the attribute `svg:hanging`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

jjj. *The standard defines the attribute `svg:ideographic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

kkk. *The standard defines the attribute `svg:mathematical`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

lll. *The standard defines the attribute `svg:overline-position`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

mmm. *The standard defines the attribute `svg:overline-thickness`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

nnn. *The standard defines the attribute `svg:panose-1`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ooo. *The standard defines the attribute `svg:slope`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ppp. *The standard defines the attribute `svg:stemh`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

qqq. *The standard defines the attribute `svg:stemv`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

rrr. *The standard defines the attribute `svg:strikethrough-position`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

sss. *The standard defines the attribute `svg:strikethrough-thickness`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ttt. *The standard defines the attribute `svg:underline-position`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

uuu. *The standard defines the attribute `svg:underline-thickness`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

vvv. *The standard defines the attribute `svg:unicode-range`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

www. *The standard defines the attribute `svg:units-per-em`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

xxx. *The standard defines the attribute `svg:v-alphabetic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

yyy. *The standard defines the attribute `svg:v-hanging`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

zzz. *The standard defines the attribute `svg:v-ideographic`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

aaaa. *The standard defines the attribute `svg:v-mathematical`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

bbbb. *The standard defines the attribute `svg:widths`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

cccc. *The standard defines the attribute `svg:x-height`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

dddd. *The standard defines the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This element is not supported in Excel 2010 or Excel 2013.

eeee. *The standard defines the attribute `xlink:actuate`, contained within the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This attribute is not supported in Excel 2010 or Excel 2013.

ffff. *The standard defines the attribute `xlink:href`, contained within the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This attribute is not supported in Excel 2010 or Excel 2013.

gggg. *The standard defines the attribute `xlink:type`, contained within the element `<svg:definition-src>`, contained within the parent element `<style:font-face>`*

This attribute is not supported in Excel 2010 or Excel 2013.

hhhh. *The standard defines the element `<svg:font-face-format>`, contained within the parent element `<svg:font-face-src>`*

This element is not supported in Excel 2010 or Excel 2013.

iiii. *The standard defines the attribute `svg:string`, contained within the element `<svg:font-face-format>`, contained within the parent element `<svg:font-face-src>`*

This attribute is not supported in Excel 2010 or Excel 2013.

jjjj. *The standard defines the element `<svg:font-face-name>`, contained within the parent element `<svg:font-face-src>`*

This element is not supported in Excel 2010 or Excel 2013.

kkkk. *The standard defines the attribute `svg:name`, contained within the element `<svg:font-face-name>`, contained within the parent element `<svg:font-face-src>`*

This attribute is not supported in Excel 2010 or Excel 2013.

llll. *The standard defines the element `<svg:font-face-src>`, contained within the parent element `<style:font-face>`*

This element is not supported in Excel 2010 or Excel 2013.

mmmm. *The standard defines the element `<style:font-face>`*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

2.1.531 Section 14.6.2, Name

- a. *The standard defines the attribute `style:name`, contained within the element `<style:font-face>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute `style:name`, contained within the element `<style:font-face>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- c. *The standard defines the attribute `style:name`, contained within the element `<style:font-face>`, contained within the parent element `<office:font-face-decls>`*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel ignores the `<style:font-face>` element, all attributes of the `<style:font-face>` element, and all child elements. Excel reads the `<style:font-name>` attribute to determine the font to apply.

On save, Excel writes out the `<style:font-face>` element, along with values for the `<style:name>` and `<svg:font-family>` attributes.

- d. *The standard defines the attribute `style:name`, contained within the element `<style:font-face>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

2.1.532 Section 14.6.3, Adornments

- a. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- c. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute style:font-adornments, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in <the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

2.1.533 Section 14.6.4, Font Family Generic

- a. *The standard defines the attribute style:font-family-generic, contained within the element <style:font-face>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-family-generic, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- c. *The standard defines the attribute style:font-family-generic, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute style:font-family-generic, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

2.1.534 Section 14.6.5, Font Pitch

- a. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- c. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute style:font-pitch, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

2.1.535 Section 14.6.6, Font Character Set

- a. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels. On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

- b. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font face declarations. Font face declarations are not written.

- c. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>, contained within the parent element <office:font-face-decls>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute style:font-charset, contained within the element <style:font-face>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On save, this attribute is not supported in the context of font-face declarations. Font face declarations are not written.

2.1.536 Section 14.7, Data Styles

- a. *The standard defines the element <number:number-style>*

This element is supported in Excel 2010 and Excel 2013.

- b. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.537 Section 14.7.1, Number Style

- a. *The standard defines the element <number:embedded-text>, contained within the parent element <number:number>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <number:fraction>, contained within the parent element <number:number-style>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <number:number>, contained within the parent element <number:number-style>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <number:number-style>*

This element is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <number:scientific-number>, contained within the parent element <number:number-style>*

This element is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <number:text>, contained within the parent element <number:number-style>*

This element is not supported in Word 2010 or Word 2013.

- g. *The standard defines the element <style:map>, contained within the parent element <number:number-style>*

This element is not supported in Word 2010 or Word 2013.

- h. *The standard defines the element <style:text-properties>, contained within the parent element <number:number-style>*

This element is not supported in Word 2010 or Word 2013.

- i. *The standard defines the element <number:embedded-text>, contained within the parent element <number:number>*

This element is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute number:position, contained within the element <number:embedded-text>, contained within the parent element <number:number>*

This attribute is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the element <number:fraction>, contained within the parent element <number:number-style>*

This element is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the element <number:number>, contained within the parent element <number:number-style>*

This element is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the attribute number:decimal-replacement, contained within the element <number:number>, contained within the parent element <number:number-style>*

This attribute is supported in Excel 2010 and Excel 2013.

If this attribute contains the empty string, Excel treats the values after the decimal as numeric instead of zero. On save, the attribute or empty string is saved only if all digits to the right of the decimal are insignificant digits.

- n. *The standard defines the attribute number:display-factor, contained within the element <number:number>, contained within the parent element <number:number-style>*

This attribute is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the element <number:scientific-number>, contained within the parent element <number:number-style>*

This element is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the attribute number:min-exponent-digits, contained within the element <number:scientific-number>, contained within the parent element <number:number-style>*

This attribute is supported in Excel 2010 and Excel 2013.

- q. *The standard defines the element <number:text>, contained within the parent element <number:number-style>*

This element is supported in Excel 2010 and Excel 2013.

- r. *The standard defines the element <style:map>, contained within the parent element <number:number-style>*

This element is supported in Excel 2010 and Excel 2013.

- s. *The standard defines the element <style:text-properties>, contained within the parent element <number:number-style>*

This element is supported in Excel 2010 and Excel 2013.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- t. *The standard defines the element <number:number-style>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.538 Section 14.7.2, Currency Style

- a. *The standard defines the element <number:currency-style>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <number:currency-symbol>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <number:number>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <number:text>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <style:map>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <style:text-properties>, contained within the parent element <number:currency-style>*

This element is not supported in Word 2010 or Word 2013.

- g. *The standard defines the element <number:currency-style>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the element <number:currency-symbol>*

This element is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the element <number:currency-symbol>, contained within the parent element <number:currency-style>*

This element is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute number:country, contained within the element <number:currency-symbol>*

This attribute is supported in Excel 2010 and Excel 2013.

- k. *The standard defines the attribute number:language, contained within the element <number:currency-symbol>*

This attribute is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the element <number:number>, contained within the parent element <number:currency-style>*

This element is supported in Excel 2010 and Excel 2013.

- m. *The standard defines the element <number:text>, contained within the parent element <number:currency-style>*

This element is supported in Excel 2010 and Excel 2013.

- n. *The standard defines the element <style:map>, contained within the parent element <number:currency-style>*

This element is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the element <style:text-properties>, contained within the parent element <number:currency-style>*

This element is supported in Excel 2010 and Excel 2013.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- p. *The standard defines the element <number:currency-style>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.539 Section 14.7.3, Percentage Style

- a. *The standard defines the element <number:number>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <number:percentage-style>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <number:text>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <style:map>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2010 or Word 2013.

- e. *The standard defines the element <style:text-properties>, contained within the parent element <number:percentage-style>*

This element is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <number:percentage-style>, contained within the parent element <number:percentage-style>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the element <style:map>, contained within the parent element <number:percentage-style>*

This element is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the element <number:percentage-style>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.540 Section 14.7.4, Date Style

- a. *The standard defines the element <number:am-pm>, contained within the parent element <number:date-style>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <number:date-style>*

This element is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute number:automatic-order, contained within the element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute number:country, contained within the element <number:date-style>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute number:format-source, contained within the element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute number:language, contained within the element <number:date-style>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute number:title, contained within the element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute number:transliteration-country, contained within the element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute number:transliteration-format, contained within the element <number:date-style>*

This attribute is supported in Word 2010 and Word 2013.

- j. *The standard defines the attribute number:transliteration-language, contained within the element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

- k. *The standard defines the attribute number:transliteration-style, contained within the element <number:date-style>*

This attribute is supported in Word 2010 and Word 2013.

- l. *The standard defines the attribute style:display-name, contained within the element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute `style:name`, contained within the element `<number:date-style>`*

This attribute is supported in Word 2010 and Word 2013.

- n. *The standard defines the attribute `style:volatile`, contained within the element `<number:date-style>`*

This attribute is not supported in Word 2010 or Word 2013.

- o. *The standard defines the element `<number:day>`, contained within the parent element `<number:date-style>`*

This element is supported in Word 2010 and Word 2013.

- p. *The standard defines the property "buddhist", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- q. *The standard defines the property "gengou", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- r. *The standard defines the property "gregorian", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- s. *The standard defines the property "hanja", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

- t. *The standard defines the property "hanja_yoil", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

- u. *The standard defines the property "hijri", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- v. *The standard defines the property "jewish", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- w. *The standard defines the property "ROC", contained within the attribute `number:calendar`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

- x. *The standard defines the attribute `number:style`, contained within the element `<number:day>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in Word 2010 or Word 2013.

- y. *The standard defines the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This element is supported in Word 2010 and Word 2013.

- z. *The standard defines the property "buddhist", contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- aa. *The standard defines the property "gengou", contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- bb. *The standard defines the property "hanja", contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

- cc. *The standard defines the property "hanja_yoil", contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

- dd. *The standard defines the property "hijri", contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- ee. *The standard defines the property "jewish", contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

- ff. *The standard defines the property "ROC", contained within the attribute `number:calendar`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

- gg. *The standard defines the attribute `number:style`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in Word 2010 or Word 2013.

- hh. *The standard defines the element `<number:era>`, contained within the parent element `<number:date-style>`*

This element is supported in Word 2010 and Word 2013.

- ii. *The standard defines the property "buddhist", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

- jj. *The standard defines the property "gengou", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

- kk. *The standard defines the property "gregorian", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

- ll. *The standard defines the property "hanja", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is not supported in Word 2010 or Word 2013.

- mm. *The standard defines the property "hanja_yoil", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is not supported in Word 2010 or Word 2013.

- nn. *The standard defines the property "hijri", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

- oo. *The standard defines the property "jewish", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

- pp. *The standard defines the property "ROC", contained within the attribute number:calendar, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is not supported in Word 2010 or Word 2013.

- qq. *The standard defines the attribute number:style, contained within the element <number:era>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

- rr. *The standard defines the element <number:hours>, contained within the parent element <number:date-style>*

This element is supported in Word 2010 and Word 2013.

ss. *The standard defines the attribute `number:style`, contained within the element `<number:hours>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in Word 2010 or Word 2013.

tt. *The standard defines the element `<number:minutes>`, contained within the parent element `<number:date-style>`*

This element is supported in Word 2010 and Word 2013.

uu. *The standard defines the attribute `number:style`, contained within the element `<number:minutes>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in Word 2010 or Word 2013.

vv. *The standard defines the element `<number:month>`, contained within the parent element `<number:date-style>`*

This element is supported in Word 2010 and Word 2013.

ww. *The standard defines the property "buddhist", contained within the attribute `number:calendar`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

xx. *The standard defines the property "gengou", contained within the attribute `number:calendar`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

yy. *The standard defines the property "gregorian", contained within the attribute `number:calendar`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

zz. *The standard defines the property "hanja", contained within the attribute `number:calendar`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

aaa. *The standard defines the property "hanja_yoil", contained within the attribute `number:calendar`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This property is not supported in Word 2010 or Word 2013.

bbb. *The standard defines the property "hijri", contained within the attribute `number:calendar`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

ccc. *The standard defines the property "jewish", contained within the attribute `number:calendar`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This property is supported in Word 2010 and Word 2013.

ddd. *The standard defines the property "ROC", contained within the attribute number:calendar, contained within the element <number:month>, contained within the parent element <number:date-style>*

This property is not supported in Word 2010 or Word 2013.

eee. *The standard defines the attribute number:possessive-form, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

fff. *The standard defines the attribute number:style, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

ggg. *The standard defines the attribute number:textual, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is supported in Word 2010 and Word 2013.

hhh. *The standard defines the element <number:quarter>, contained within the parent element <number:date-style>*

This element is not supported in Word 2010 or Word 2013.

iii. *The standard defines the element <number:seconds>, contained within the parent element <number:date-style>*

This element is supported in Word 2010 and Word 2013.

jjj. *The standard defines the attribute number:decimal-places, contained within the element <number:seconds>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

kkk. *The standard defines the attribute number:style, contained within the element <number:seconds>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

lll. *The standard defines the element <number:week-of-year>, contained within the parent element <number:date-style>*

This element is not supported in Word 2010 or Word 2013.

mmm. *The standard defines the element <number:year>, contained within the parent element <number:date-style>*

This element is supported in Word 2010 and Word 2013.

nnn. *The standard defines the property "buddhist", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

ooo. *The standard defines the property "gengou", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

ppp. *The standard defines the property "gregorian", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

qqq. *The standard defines the property "hanja", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is not supported in Word 2010 or Word 2013.

rrr. *The standard defines the property "hanja_yoil", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is not supported in Word 2010 or Word 2013.

sss. *The standard defines the property "hijri", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

ttt. *The standard defines the property "jewish", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is supported in Word 2010 and Word 2013.

uuu. *The standard defines the property "ROC", contained within the attribute number:calendar, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is not supported in Word 2010 or Word 2013.

vvv. *The standard defines the attribute number:style, contained within the element <number:year>, contained within the parent element <number:date-style>*

This attribute is not supported in Word 2010 or Word 2013.

www. *The standard defines the element <style:map>, contained within the parent element <number:date-style>*

This element is not supported in Word 2010 or Word 2013.

xxx. *The standard defines the element <style:text-properties>, contained within the parent element <number:date-style>*

This element is not supported in Word 2010 or Word 2013.

Word applies text properties to this element via a <text:span> around the object.

yyy. *The standard defines the parent element <number:date-style>*

This is supported in Excel 2010 and Excel 2013.

zzz. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:day>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

aaaa. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:day>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

bbbb. *The standard defines the attribute number:style, contained within the element <number:day-of-week>, contained within the parent element <number:date-style>*

This attribute is supported in Excel 2010 and Excel 2013.

cccc. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:day-of-week>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

dddd. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:day-of-week>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

eeee. *The standard defines the element <number:era>, contained within the parent element <number:date-style>*

This element is supported in Excel 2010 and Excel 2013.

ffff. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

gggg. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:era>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

hhhh. *The standard defines the attribute number:possessive-form, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is not supported in Excel 2010 or Excel 2013.

iiii. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:month>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

jjjj. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:month>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

kkkk. *The standard defines the attribute number:textual, contained within the element <number:month>, contained within the parent element <number:date-style>*

This attribute is supported in Excel 2010 and Excel 2013.

llll. *The standard defines the attribute number:style, contained within the element <number:quarter>, contained within the parent element <number:date-style>*

This attribute is not supported in Excel 2010 or Excel 2013.

mmmm. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:quarter>, contained within the parent element <number:date-style>*

This property is not supported in Excel 2010 or Excel 2013.

nnnn. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:quarter>, contained within the parent element <number:date-style>*

This property is not supported in Excel 2010 or Excel 2013.

oooo. *The standard defines the element <number:week-of-year>, contained within the parent element <number:date-style>*

This element is not supported in Excel 2010 or Excel 2013.

pppp. *The standard defines the element <number:year>, contained within the parent element <number:date-style>*

This element is supported in Excel 2010 and Excel 2013.

qqqq. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

rrrr. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:year>, contained within the parent element <number:date-style>*

This property is supported in Excel 2010 and Excel 2013.

ssss. *The standard defines the element <style:map>, contained within the parent element <number:date-style>*

This element is supported in Excel 2010 and Excel 2013.

tttt. *The standard defines the element <style:text-properties>, contained within the parent element <number:date-style>*

This element is supported in Excel 2010 and Excel 2013.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

uuuu. *The standard defines the element <number:am-pm>, contained within the parent element <number:date-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

vvvv. *The standard defines the element <number:date-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

www. *The standard defines the element <number:day>, contained within the parent element <number:date-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

xxxx. *The standard defines the attribute `number:style`, contained within the element `<number:day>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

yyyy. *The standard defines the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

zzzz. *The standard defines the attribute `number:style`, contained within the element `<number:day-of-week>`, contained within the parent element `<number:date-style>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

aaaaa. *The standard defines the element `<number:era>`, contained within the parent element `<number:date-style>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

bbbbbb. *The standard defines the element `<number:hours>`, contained within the parent element `<number:date-style>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

cccc. *The standard defines the attribute `number:style`, contained within the element `<number:hours>`, contained within the parent element `<number:date-style>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

dddddd. *The standard defines the element `<number:minutes>`, contained within the parent element `<number:date-style>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

eeee. *The standard defines the attribute `number:style`, contained within the element `<number:minutes>`, contained within the parent element `<number:date-style>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

ffff. *The standard defines the element `<number:month>`, contained within the parent element `<number:date-style>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

ggggg. *The standard defines the attribute `number:possessive-form`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

hhhhh. *The standard defines the attribute `number:style`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

iiii. *The standard defines the attribute `number:textual`, contained within the element `<number:month>`, contained within the parent element `<number:date-style>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

jjjjj. *The standard defines the element `<number:quarter>`, contained within the parent element `<number:date-style>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

kkkkk. *The standard defines the attribute `number:style`, contained within the element `<number:quarter>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

lllll. *The standard defines the element `<number:seconds>`, contained within the parent element `<number:date-style>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

mmmmm. *The standard defines the attribute `number:decimal-places`, contained within the element `<number:seconds>`, contained within the parent element `<number:date-style>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

nnnnn. *The standard defines the attribute `number:style`, contained within the element `<number:seconds>`, contained within the parent element `<number:date-style>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

ooooo. *The standard defines the element `<number:week-of-year>`, contained within the parent element `<number:date-style>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

ppppp. *The standard defines the element `<number:year>`, contained within the parent element `<number:date-style>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

qqqqq. *The standard defines the attribute `number:style`, contained within the element `<number:year>`, contained within the parent element `<number:date-style>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.541 Section 14.7.5, Time Style

a. *The standard defines the element `<number:am-pm>`, contained within the parent element `<number:time-style>`*

This element is supported in Word 2010 and Word 2013.

1. On load, Word reads the `<number:time-style>` element and converts it to the matching `<text:date-style>` element.
2. On save, Word does not write out time fields or time styles.

b. *The standard defines the attribute `number:style`, contained within the element `<number:hours>`, contained within the parent element `<number:time-style>`*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the `<number:time-style>` element and converts it to the matching `<text:date-style>` element.
2. On save, Word does not write out time fields or time styles.

c. *The standard defines the attribute `number:style`, contained within the element `<number:minutes>`, contained within the parent element `<number:time-style>`*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- d. *The standard defines the attribute number:decimal-places, contained within the element <number:seconds>, contained within the parent element <number:time-style>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- e. *The standard defines the attribute number:style, contained within the element <number:seconds>, contained within the parent element <number:time-style>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- f. *The standard defines the element <number:text>, contained within the parent element <number:time-style>*

This element is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- g. *The standard defines the element <number:time-style>*

This element is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- h. *The standard defines the attribute number:country, contained within the element <number:time-style>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- i. *The standard defines the attribute number:format-source, contained within the element <number:time-style>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- j. *The standard defines the attribute number:language, contained within the element <number:time-style>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- k. *The standard defines the attribute number:title, contained within the element <number:time-style>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- l. *The standard defines the attribute number:transliteration-country, contained within the element <number:time-style>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- m. *The standard defines the attribute number:transliteration-format, contained within the element <number:time-style>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- n. *The standard defines the attribute number:transliteration-language, contained within the element <number:time-style>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- o. *The standard defines the attribute number:transliteration-style, contained within the element <number:time-style>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- p. *The standard defines the attribute number:truncate-on-overflow, contained within the element <number:time-style>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- q. *The standard defines the attribute style:display-name, contained within the element <number:time-style>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- r. *The standard defines the attribute style:volatile, contained within the element <number:time-style>*

This attribute is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- s. *The standard defines the element <style:map>, contained within the parent element <number:time-style>*

This element is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- t. *The standard defines the element <style:text-properties>, contained within the parent element <number:time-style>*

This element is not supported in Word 2010 or Word 2013.

1. On load, Word reads the <number:time-style> element and converts it to the matching <text:date-style> element.
 2. On save, Word does not write out time fields or time styles.
- u. *The standard defines the element <number:am-pm>*

This element is supported in Excel 2010 and Excel 2013.

- v. *The standard defines the property "long", contained within the attribute number:style, contained within the element <number:minutes>*

This property is supported in Excel 2010 and Excel 2013.

- w. *The standard defines the property "short", contained within the attribute number:style, contained within the element <number:minutes>*

This property is supported in Excel 2010 and Excel 2013.

- x. *The standard defines the element <number:seconds>*

This element is supported in Excel 2010 and Excel 2013.

- y. *The standard defines the attribute number:decimal-places, contained within the element <number:seconds>*

This attribute is supported in Excel 2010 and Excel 2013.

- z. *The standard defines the element <number:time-style>*

This element is supported in Excel 2010 and Excel 2013.

- aa. *The standard defines the element <style:map>, contained within the parent element <number:time-style>*

This element is supported in Excel 2010 and Excel 2013.

- bb. *The standard defines the element <number:am-pm>, contained within the parent element <number:time-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- cc. *The standard defines the element <number:hours>, contained within the parent element <number:time-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- dd. *The standard defines the attribute number:style, contained within the element <number:hours>, contained within the parent element <number:time-style>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- ee. *The standard defines the element <number:minutes>, contained within the parent element <number:time-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- ff. *The standard defines the attribute number:style, contained within the element <number:minutes>, contained within the parent element <number:time-style>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- gg. *The standard defines the element <number:seconds>, contained within the parent element <number:time-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- hh. *The standard defines the attribute number:style, contained within the element <number:seconds>, contained within the parent element <number:time-style>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- ii. *The standard defines the element <number:time-style>, contained within the parent element <number:date-style>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- jj. *The standard defines the attribute number:truncate-on-overflow, contained within the element <number:time-style>, contained within the parent element <number:date-style>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.542 Section 14.7.6, Boolean Style

- a. *The standard defines the element <number:boolean-style>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <number:boolean>, contained within the parent element <number:boolean-style>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <number:boolean-style>*

This element is not supported in Excel 2010 or Excel 2013.

On load, Boolean styles are loaded; however, Excel does not have a number format token corresponding to the <number:boolean-style> element. Therefore, only the standard data style attributes are applied to specify the format. On save, Boolean styles are not saved.

- d. *The standard defines the element <style:map>, contained within the parent element <number:boolean-style>*

This element is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the element <number:boolean-style>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.543 Section 14.7.7, Text Style

- a. *The standard defines the element <number:text>, contained within the parent element <number:text-style>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <number:text-content>, contained within the parent element <number:text-style>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <number:text-style>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <number:text>*

This element is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the element <number:text-content>*

This element is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the element <number:text-style>*

This element is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the element <style:map>, contained within the parent element <number:text-style>*

This element is supported in Excel 2010 and Excel 2013.

2.1.544 Section 14.7.8, Common Data Style Elements

- a. *The standard defines the element <style:map>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <style:text-properties>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <style:map>*

This element is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the element <style:text-properties>*

This element is supported in Excel 2010 and Excel 2013.

A subset of formatting can be applied through number formats. This subset of formatting is limited to colors.

- e. *The standard defines the element <style:map>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the element <style:text-properties>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.545 Section 14.7.9, Common Data Style Attributes

- a. *The standard defines the attribute number:automatic-order*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute number:country*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute number:format-source*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute number:language*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute number:title*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute style:display-name*

This attribute is not supported in Word 2010 or Word 2013.

- g. *The standard defines the attribute style:name*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute style:volatile*

This attribute is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute number:automatic-order*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the attribute number:country*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- k. *The standard defines the attribute number:format-source*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the attribute number:language*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

m. *The standard defines the attribute number:title*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

n. *The standard defines the attribute style:display-name*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

o. *The standard defines the attribute style:name*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

p. *The standard defines the attribute style:volatile*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.546 Section 14.7.10, Transliteration

a. *The standard defines the attribute number:transliteration-country*

This attribute is not supported in Word 2010 or Word 2013.

b. *The standard defines the attribute number:transliteration-format*

This attribute is supported in Word 2010 and Word 2013.

c. *The standard defines the attribute number:transliteration-language*

This attribute is not supported in Word 2010 or Word 2013.

d. *The standard defines the attribute number:transliteration-style*

This attribute is supported in Word 2010 and Word 2013.

e. *The standard defines the attribute number:transliteration-format*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

f. *The standard defines the attribute number:transliteration-language*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

g. *The standard defines the attribute transliteration-country*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

h. *The standard defines the attribute transliteration-style*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.547 Section 14.7.11, Common Data Style Child Element Attributes

a. *The standard defines the property "buddhist", contained within the attribute number:calendar*

This property is supported in Word 2010 and Word 2013.

b. *The standard defines the property "gengou", contained within the attribute number:calendar*

This property is supported in Word 2010 and Word 2013.

c. *The standard defines the property "gregorian", contained within the attribute number:calendar*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "hanja", contained within the attribute number:calendar*

This property is not supported in Word 2010 or Word 2013.

- e. *The standard defines the property "hanja_yoil", contained within the attribute number:calendar*

This property is not supported in Word 2010 or Word 2013.

- f. *The standard defines the property "hijri", contained within the attribute number:calendar*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the property "jewish", contained within the attribute number:calendar*

This property is supported in Word 2010 and Word 2013.

- h. *The standard defines the property "ROC", contained within the attribute number:calendar*

This property is not supported in Word 2010 or Word 2013.

- i. *The standard defines the attribute number:decimal-places*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute number:grouping*

This attribute is not supported in Word 2010 or Word 2013.

- k. *The standard defines the attribute number:min-integer-digits*

This attribute is not supported in Word 2010 or Word 2013.

- l. *The standard defines the attribute number:calendar*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- m. *The standard defines the property "buddhist", contained within the attribute number:calendar*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- n. *The standard defines the property "gengou", contained within the attribute number:calendar*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- o. *The standard defines the property "gregorian", contained within the attribute number:calendar*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- p. *The standard defines the property "hanja", contained within the attribute number:calendar*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- q. *The standard defines the property "hanja_yoil", contained within the attribute number:calendar*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- r. *The standard defines the property "hijiri", contained within the attribute number:calendar*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- s. *The standard defines the property "jewish", contained within the attribute number:calendar*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- t. *The standard defines the property "ROC", contained within the attribute number:calendar*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.548 Section 14.8, Text Styles

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
b. OfficeArt Math in Excel 2013 supports this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.549 Section 14.8.1, Text Styles

- a. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the property "text", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.550 Section 14.8.2, Paragraph Styles

- a. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
 - shapes
 - SmartArt
 - chart titles
 - labels
- c. *The standard defines the property "paragraph", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

2.1.551 Section 14.8.3, Section Styles

- a. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the property "section", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.552 Section 14.8.4, Ruby Style

- a. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the property "ruby", contained within the attribute style:family, contained within the element <style:style>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.553 Section 14.9, Enhanced Text Styles

- a. OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.
- b. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this on save for text in any of the following items:

- text boxes
 - shapes
 - SmartArt
 - chart titles
 - labels
- c. OfficeArt Math in PowerPoint 2013 does not support this on load for text in the following elements:
- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:measure>
 - <draw:text-box>
 - <draw:frame>
 - <draw:custom-shape>.

2.1.554 Section 14.9.1, Line Numbering Configuration

- a. *The standard defines the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This element is supported in Word 2010 and Word 2013.

Word saves the line numbering configuration only if the following conditions are met:

1. All sections restart per page.
 2. All sections start line numbering at 1.
 3. All sections have the same distance between the line numbering and the text.
 4. All sections have line numbering that increments by the same amount.
- b. *The standard defines the attribute style:num-format, contained within the element <text:linenumbering-configuration>*

This attribute is not supported in Word 2010 or Word 2013.

All values for the style:num-format attribute revert to the Word default of Arabic numerals (1,2,3, ...).

- c. *The standard defines the attribute style:num-letter-sync, contained within the element <text:linenumbering-configuration>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute text:count-empty-lines, contained within the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute text:count-in-text-boxes, contained within the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute text:increment, contained within the element <text:linenumbering-configuration>, contained within the parent element <office:styles>*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute `text:number-lines`, contained within the element `<text:linenumbers-configuration>`, contained within the parent element `<office:styles>`*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute `text:offset`, contained within the element `<text:linenumbers-configuration>`, contained within the parent element `<office:styles>`*

This attribute is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute `text:position`, contained within the element `<text:linenumbers-configuration>`, contained within the parent element `<office:styles>`*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute `text:restart-on-page`, contained within the element `<text:linenumbers-configuration>`, contained within the parent element `<office:styles>`*

This attribute is supported in Word 2010 and Word 2013.

- k. *The standard defines the attribute `text:style-name`, contained within the element `<text:linenumbers-configuration>`, contained within the parent element `<office:styles>`*

This attribute is not supported in Word 2010 or Word 2013.

- l. *The standard defines the element `<text:linenumbers-separator>`, contained within the parent element `<text:linenumbers-configuration>`*

This element is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute `text:increment`, contained within the element `<text:linenumbers-separator>`, contained within the parent element `<text:linenumbers-configuration>`*

This attribute is not supported in Word 2010 or Word 2013.

- n. This is not supported in Excel 2010 or Excel 2013.

2.1.555 Section 14.9.2, Notes Configuration Element

- a. *The standard defines the element `<text:notes-configuration>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `style:num-letter-sync`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `style:num-prefix`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute `style:num-suffix`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute `text:citation-body-style-name`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `text:citation-style`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute `text:default-style-name`, contained within the element `<text:notes-configuration>`*

This attribute is not supported in Word 2010 or Word 2013.

- h. *The standard defines the attribute `text:footnotes-position`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute `text:master-page-name`, contained within the element `<text:notes-configuration>`*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute `text:note-class`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- k. *The standard defines the attribute `text:note-continuation-notice-backward`, contained within the element `<text:notes-configuration>`*

This attribute is not supported in Word 2010 or Word 2013.

- l. *The standard defines the attribute `text:note-continuation-notice-forward`, contained within the element `<text:notes-configuration>`*

This attribute is not supported in Word 2010 or Word 2013.

- m. *The standard defines the attribute `text:num-format`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

1. On load, numbering formats that are not familiar to Word will be displayed using the Arabic numeral format (1, 2, 3...).
2. On save and load, the following strings are also supported by Word as numbering formats:

ア, イ, ウ, ...

ア, イ, ウ, ...

أ, ب, ج, ...

أ, ب, ت, ...

One, Two, Three, ...

*, †, ‡, ...

一, 十, 一〇〇(簡), ...

一, 十, 一百 (简), ...
壹, 貳, 叁, ...
ㄱ, ㄴ, ㄷ, ...
①, ②, ③, ...
①, ②, ③, ...
1, 2, 3, ...
(1), (2), (3), ...
1, 2, 3, ...
01, 02, 03, ...
가, 나, 다, ...
κ, λ, μ, ν, ...
κ, γ, λ, ...
1, A, B, ...
अ, आ, इ, ...
□□, □□, □□□, ...
१, २, ३, ...
क, ख, ग, ...
一, 一〇, 一〇〇, ...
(一), (二), (三), ...
壹, 貳, 參, ...
甲, 乙, 丙, ...
子, 丑, 寅, ...
甲子, 乙丑, 丙寅, ...
イ, ロ, ハ, ...
イ, ロ, ハ, ...
一, 二, 三 ...
一, 二, 三, 万, ...
壹, 貳, 參, ...
일, 이, 삼, ...
일, 일영, 일영영, ...
一, 一零, 一零零, ...
하나, 둘, 셋, ...

- 1 -, 2 -, 3 -, ...

1st, 2nd, 3rd, ...

First, Second, Third, ...

a, б, B, ...

A,Б,B, ...

一, 十, 一〇〇(繁), ...

一, 十, 一百 (繁), ...

一, 一〇, 一〇〇(繁), ...

□□□□, ஸ ஐ ங , ஸ ௮ ஡ , ...

π , π , π , ...

๑ ,๒ ,๓ , ...

- n. *The standard defines the attribute `text:start-numbering-at`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- o. *The standard defines the attribute `text:start-value`, contained within the element `<text:notes-configuration>`*

This attribute is supported in Word 2010 and Word 2013.

- p. This is not supported in Excel 2010 or Excel 2013.

2.1.556 Section 14.9.3, Bibliography Configuration

- a. *The standard defines the element `<text:bibliography-configuration>`*

This element is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

2.1.557 Section 14.10, List Style

- a. *The standard defines the element `<text:list-style>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `style:display-name`, contained within the element `<text:list-style>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- c. *The standard defines the attribute `style:name`, contained within the element `<text:list-style>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- d. *The standard defines the attribute `text:consecutive-numbering`, contained within the element `<text:list-style>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. This is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `style:display-name`, contained within the element `<text:list-style>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- g. *The standard defines the attribute `style:name`, contained within the element `<text:list-style>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- h. *The standard defines the attribute `text:consecutive-numbering`, contained within the element `<text:list-style>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- i. *The standard defines the attribute style:display-name, contained within the element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute style:name, contained within the element <text:list-style>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- k. *The standard defines the attribute text:consecutive-numbering, contained within the element <text:list-style>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.558 Section 14.10.1, Common List-Level Style Attributes

- a. *The standard defines the attribute text:level*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute text:level*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes, shapes, and SmartArt.

- d. *The standard defines the attribute text:level*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.559 Section 14.10.2, Number Level Style

- a. *The standard defines the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute style:num-suffix, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute text:display-levels, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute text:level, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute text:num-format, contained within the element <text:list-level-style-number>, contained within the parent element <text:list-style>*

This attribute is supported in Word 2010 and Word 2013.

1. On load, numbering formats that are not familiar to Word will be displayed using the Arabic numeral format (1, 2, 3...).
2. On save and load, the following strings are also supported by Word as numbering formats:

ア, イ, ウ, ...

ア, イ, ウ, ...

أ, ب, ج, ...

أ, ب, ت, ...

One, Two, Three, ...

*, †, ‡, ...

一, 十, 一〇〇(簡), ...

一, 十, 一百 (簡), ...

壹, 貳, 參, ...

ㄱ, ㄴ, ㄷ, ...

①, ②, ③, ...

①, ②, ③, ...

1., 2., 3., ...

(1), (2), (3), ...

1, 2, 3, ...

01, 02, 03, ...

가, 나, 다, ...

κ , ι , ρ , ...

κ , ς , λ , ...

1, A, B, ...

अ, आ, इ , ...

□□, □□, □□□, ...

१ , २ , ३ , ...

क, ख, ग , ...

一, 一〇, 一〇〇, ...

(一), (二), (三), ...

壹, 貳, 參, ...

甲, 乙, 丙, ...

子, 丑, 寅, ...

甲子, 乙丑, 丙寅, ...

イ, ロ, ハ , ...

イ, 口, ハ, ...

一, 二, 三 ...

一, 二, 三, 万, ...

壹, 貳, 參, ...

일, 이, 삼, ...

일, 일영, 일영영, ...

一, 一零, 一零零, ...

하나, 둘, 셋, ...

- 1 -, - 2 -, - 3 -, ...

1st, 2nd, 3rd, ...

First, Second, Third, ...

a, б, в, ...

A, B, B, ...

一, 十, 一〇〇(繁), ...

一, 十, 一百 (繁), ...

一, 一〇, 一〇〇(繁), ...

□□□□, ஸ ஐ ங , ஸ ா ழ , ...

π , ϕ , φ , ...

๑ ,๒ ,๓ , ...

A, Ç, Ğ, ...

a, ç, ğ, ...

A,Й,Ъ, ...

a,й,ъ, ...

A, B, Γ, ...

α, β, γ, ...

001,002, 003, ...

0001,0002, 0003, ...

00001,00002, 00003, ...

- g. *The standard defines the attribute `text:start-value`, contained within the element `<text:list-level-style-number>`, contained within the parent element `<text:list-style>`*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute `text:style-name`, contained within the element `<text:list-level-style-number>`, contained within the parent element `<text:list-style>`*

This attribute is supported in Word 2010 and Word 2013.

- i. This is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute `style:num-format`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes.

- k. *The standard defines the attribute `text:display-levels`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- l. *The standard defines the attribute `text:level`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- m. *The standard defines the attribute `text:start-value`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- n. *The standard defines the attribute `text:style-name`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- o. *The standard defines the attribute style:num-format, contained within the element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- p. *The standard defines the attribute text:display-levels, contained within the element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- q. *The standard defines the attribute text:level, contained within the element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- r. *The standard defines the attribute `text:start-value`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- s. *The standard defines the attribute `text:style-name`, contained within the element `<text:list-level-style-number>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.560 Section 14.10.3, Bullet Level Style

- a. *The standard defines the element `<text:list-level-style-bullet>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `style:num-prefix`, contained within the element `<text:list-level-style-bullet>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- c. *The standard defines the attribute `style:num-suffix`, contained within the element `<text:list-level-style-bullet>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- d. *The standard defines the attribute `text:bullet-char`, contained within the element `<text:list-level-style-bullet>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- e. *The standard defines the attribute `text:bullet-relative-size`, contained within the element `<text:list-level-style-bullet>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- f. *The standard defines the attribute `text:level`, contained within the element `<text:list-level-style-bullet>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- g. *The standard defines the attribute `text:style-name`, contained within the element `<text:list-level-style-bullet>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- h. This is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `style:num-prefix`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- j. *The standard defines the attribute `style:num-suffix`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- k. *The standard defines the attribute `text:bullet-char`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- l. *The standard defines the attribute `text:bullet-relative-size`, contained within the element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`

- <draw:custom-shape>.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- m. *The standard defines the attribute text:level, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes and for SmartArt Graphics.

- n. *The standard defines the attribute text:style-name, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes and SmartArt.

- o. *The standard defines the attribute style:num-prefix, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

p. *The standard defines the attribute style:num-suffix, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

q. *The standard defines the attribute text:bullet-char, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

r. *The standard defines the attribute text:bullet-relative-size, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
 - <draw:custom-shape>.
- s. *The standard defines the attribute text:level, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- t. *The standard defines the attribute text:style-name, contained within the element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.561 Section 14.10.4, Image Level Style

- a. *The standard defines the element <office:binary-data>, contained within the parent element <text:list-level-style-image>*

This element is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <text:list-level-style-image>*

This element is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute text:level, contained within the element <text:list-level-style-image>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute xlink:href, contained within the element <text:list-level-style-image>*

This attribute is supported in Word 2010 and Word 2013.

- e. This is not supported in Excel 2010 or Excel 2013.
- f. *The standard defines the element <office:binary-data>, contained within the parent element <text:list-level-style-image>*

OfficeArt Math in Excel 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- g. *The standard defines the attribute text:level, contained within the element <text:list-level-style-image>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- h. *The standard defines the attribute xlink:href, contained within the element <text:list-level-style-image>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
- <draw:custom-shape>

And on save for text in text boxes and shapes.

- i. *The standard defines the element <office:binary-data>, contained within the parent element <text:list-level-style-image>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute text:level, contained within the element <text:list-level-style-image>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- k. *The standard defines the attribute xlink:href, contained within the element <text:list-level-style-image>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- `<draw:custom-shape>`.

2.1.562 Section 14.10.5, List Level Style Example

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt.
- b. This is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this on save for text in text boxes and shapes, and for SmartArt.

- c. OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.563 Section 14.11, Outline Style

- a. *The standard defines the element `<text:outline-style>`*

This element is supported in Word 2010 and Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `text:outline-style`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.564 Section 14.11.1, Outline Level Style

- a. *The standard defines the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `style:num-prefix`, contained within the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `style:num-suffix`, contained within the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute `text:display-level`, contained within the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute `text:level`, contained within the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `text:num-format`, contained within the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the attribute `text:start-value`, contained within the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This attribute is supported in Word 2010 and Word 2013.

- h. *The standard defines the attribute `text:style-name`, contained within the element `<text:outline-level-style>`, contained within the parent element `<text:outline-style>`*

This attribute is supported in Word 2010 and Word 2013.

- i. This is not supported in Excel 2010 or Excel 2013.

2.1.565 Section 14.12, Table Styles

- a. This is supported in Excel 2010 and Excel 2013.

- b. *The standard defines the property "table", contained within the attribute `style:family`, contained within the element `<style:style>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.566 Section 14.12.1, Table Styles

- a. *The standard defines the property "table", contained within the attribute `family`, contained within the element `<style:style>`*

This property is supported in Word 2010 and Word 2013.

2.1.567 Section 14.12.2, Table Column Styles

- a. *The standard defines the property "table-column", contained within the attribute `family`, contained within the element `<style:style>`*

This property is supported in Word 2010 and Word 2013.

2.1.568 Section 14.12.3, Table Row Styles

- a. *The standard defines the property "table-row", contained within the attribute family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

2.1.569 Section 14.12.4, Table Cell Styles

- a. *The standard defines the property "table-cell", contained within the attribute family, contained within the element <style:style>*

This property is supported in Word 2010 and Word 2013.

2.1.570 Section 14.13, Graphic Styles

- a. Word 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. Excel 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. PowerPoint 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

2.1.571 Section 14.13.1, Graphic and Presentation Styles

- a. *The standard defines the element <style:graphic-properties>*

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>

- <draw:custom-shape>

c. *The standard defines the element <style:graphic-properties>*

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

d. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

e. *The standard defines the element <style:graphic-properties>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>

- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

f. *The standard defines the property "graphic", contained within the attribute style:family, contained within the element <style:style>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

g. *The standard defines the property "presentation", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.572 Section 14.13.2, Drawing Page Style

a. *The standard defines the property "drawing-page", contained within the attribute style:family, contained within the element <style:style>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.573 Section 14.14, Enhanced Graphic Style Elements

a. *The standard defines the parent element <office:styles>*

Word 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>

- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

b. *The standard defines the parent element <office:styles>*

Excel 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

c. *The standard defines the parent element <office:styles>*

PowerPoint 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

2.1.574 Section 14.14.1, Gradient

a. *The standard defines the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- b. *The standard defines the attribute draw:angle, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

This attribute is supported in Word 2010 and Word 2013.

The draw:angle attribute is only supported when draw:gradient-style attribute is set to "linear".

- c. *The standard defines the attribute draw:border, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute draw:cx, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>

- <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- e. *The standard defines the attribute draw:cy, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute draw:display-name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute draw:end-color, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- h. *The standard defines the attribute draw:end-intensity, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- i. *The standard defines the property "axial", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- j. *The standard defines the property "ellipsoid", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word interprets this enumeration as "radial".

- k. *The standard defines the property "linear", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- l. *The standard defines the property "radial", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- m. *The standard defines the property "rectangular", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word interprets this enumeration as "square".

- n. *The standard defines the property "square", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>

- <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- o. *The standard defines the attribute draw:name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- p. *The standard defines the attribute draw:start-color, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- q. *The standard defines the attribute draw:start-intensity, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

r. *The standard defines the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

s. *The standard defines the attribute draw:angle, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

This attribute is supported in Excel 2010 and Excel 2013.

The draw:angle attribute is only supported when draw:gradient-style attribute is set to "linear".

t. *The standard defines the attribute draw:border, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- u. *The standard defines the attribute `draw:cx`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- v. *The standard defines the attribute `draw:cy`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- w. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- x. *The standard defines the attribute `draw:end-color`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- y. *The standard defines the attribute `draw:end-intensity`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- z. *The standard defines the property "axial", contained within the attribute `draw:gradient-style`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this enum for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- aa. *The standard defines the property "ellipsoid", contained within the attribute `draw:gradient-style`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel interprets this enumeration as the value "radial".

- bb. *The standard defines the property "linear", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- cc. *The standard defines the property "radial", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- dd. *The standard defines the property "rectangular", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel interprets this enumeration as "square".

- ee. *The standard defines the property "square", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- ff. *The standard defines the attribute draw:name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- gg. *The standard defines the attribute draw:start-color, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

hh. *The standard defines the attribute draw:start-intensity, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

ii. *The standard defines the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

jj. *The standard defines the attribute draw:angle, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>

- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

The draw:angle attribute is only supported when draw:gradient-style attribute is set to "linear".

- kk. *The standard defines the attribute draw:border, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- ll. *The standard defines the attribute draw:cx, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- mm. *The standard defines the attribute draw:cy, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>

- <draw:custom-shape>

nn. *The standard defines the attribute draw:display-name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

oo. *The standard defines the attribute draw:end-color, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

pp. *The standard defines the attribute draw:end-intensity, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

qq. *The standard defines the property "axial", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

rr. *The standard defines the property "ellipsoid", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint interprets this enumeration as "radial".

ss. *The standard defines the property "linear", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

tt. *The standard defines the property "radial", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

uu. *The standard defines the property "rectangular", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint interprets this enumeration as "square".

vv. *The standard defines the property "square", contained within the attribute draw:gradient-style, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

ww. *The standard defines the attribute draw:name, contained within the element <draw:gradient>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

xx. *The standard defines the attribute `draw:start-color`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

yy. *The standard defines the attribute `draw:start-intensity`, contained within the element `<draw:gradient>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

2.1.575 Section 14.14.2, SVG Gradients

a. *The standard defines the element `<svg:linearGradient>`, contained within the parent element `<office:styles>`*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the element <svg:radialGradient>, contained within the parent element <office:styles>*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <svg:linearGradient>, contained within the parent element <office:styles>*

Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the element <svg:radialGradient>, contained within the parent element <office:styles>*

Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>

- <draw:text-box>
 - <draw:custom-shape>
- e. *The standard defines the element <svg:linearGradient>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the element <svg:radialGradient>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

2.1.576 Section 14.14.3, Hatch

- a. *The standard defines the element <draw:hatch>, contained within the parent element <office:styles>*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the element <draw:hatch>, contained within the parent element <office:styles>*

Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <draw:hatch>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

2.1.577 Section 14.14.4, Fill Image

- a. *The standard defines the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:display-name, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- c. *The standard defines the attribute `draw:name`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- d. *The standard defines the attribute `svg:height`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- e. *The standard defines the attribute `svg:width`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

f. *The standard defines the attribute `xlink:actuate`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

g. *The standard defines the attribute `xlink:href`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Relative URIs are not supported, only absolute URIs are supported.

h. *The standard defines the attribute `xlink:show`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- i. *The standard defines the attribute `xlink:type`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- j. *The standard defines the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 supports this element for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- k. *The standard defines the attribute `draw:display-name`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- l. *The standard defines the attribute `draw:name`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- m. *The standard defines the attribute `svg:height`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- n. *The standard defines the attribute `svg:width`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- o. *The standard defines the attribute `xlink:actuate`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- p. *The standard defines the attribute xlink:href, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Relative URIs are not supported, only absolute URIs are supported.

- q. *The standard defines the attribute xlink:show, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- r. *The standard defines the attribute xlink:type, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- s. *The standard defines the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this element for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- t. *The standard defines the attribute draw:display-name, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- u. *The standard defines the attribute draw:name, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>

- <draw:text-box>
 - <draw:custom-shape>
- v. *The standard defines the attribute `svg:height`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- w. *The standard defines the attribute `svg:width`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- x. *The standard defines the attribute `xlink:actuate`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- y. *The standard defines the attribute `xlink:href`, contained within the element <draw:fill-image>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Relative URIs are not supported, only absolute URIs are supported.

- z. *The standard defines the attribute `xlink:show`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- aa. *The standard defines the attribute `xlink:type`, contained within the element `<draw:fill-image>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

2.1.578 Section 14.14.5, Opacity Gradient

- a. *The standard defines the element `<draw:opacity>`, contained within the parent element `<office:styles>`*

Word 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- b. *The standard defines the element <draw:opacity>, contained within the parent element <office:styles>*

Excel 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <draw:opacity>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this element for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

2.1.579 Section 14.14.6, Marker

- a. *The standard defines the element <draw:marker>, contained within the parent element <office:styles>*

Word 2013 supports this element for a style applied to any of the following elements:

- <draw:line>
- <draw:connector>
- <draw:measure>

Word interprets all marker styles as "solid arrow".

- b. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

Word 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:line>`
 - `<draw:connector>`
 - `<draw:measure>`
- c. *The standard defines the attribute `draw:name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:line>`
 - `<draw:connector>`
 - `<draw:measure>`
- d. *The standard defines the element `<draw:marker>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this element for a style applied to any of the following elements:

- `<draw:line>`
- `<draw:connector>`
- `<draw:measure>`

Excel interprets all marker styles as "solid arrow".

- e. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:line>`
 - `<draw:connector>`
 - `<draw:measure>`
- f. *The standard defines the attribute `draw:name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:line>`
 - `<draw:connector>`
 - `<draw:measure>`
- g. *The standard defines the element `<draw:marker>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- `<draw:line>`
- `<draw:connector>`
- `<draw:measure>`

PowerPoint interprets all marker styles as "solid arrow".

- h. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:line>`
- `<draw:connector>`
- `<draw:measure>`

- i. *The standard defines the attribute `draw:name`, contained within the element `<draw:marker>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- `<draw:line>`
- `<draw:connector>`
- `<draw:measure>`

2.1.580 Section 14.14.7, Stroke Dash

- a. *The standard defines the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this element for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>`
- `<draw:image>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- b. *The standard defines the attribute `draw:display-name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 does not support this attribute for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`

- <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- c. *The standard defines the attribute `draw:distance`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- d. *The standard defines the attribute `draw:dots1`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- e. *The standard defines the attribute `draw:dots1-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

f. *The standard defines the attribute `draw:dots2`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

g. *The standard defines the attribute `draw:dots2-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

h. *The standard defines the attribute `draw:name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- i. *The standard defines the attribute `draw:style`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Word interprets all styles as "rect".

- j. *The standard defines the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>

- <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- k. *The standard defines the attribute `draw:display-name`, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Excel 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- l. *The standard defines the attribute `draw:distance`, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- m. *The standard defines the attribute `draw:dots1`, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- n. *The standard defines the attribute `draw:dots1-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- o. *The standard defines the attribute `draw:dots2`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame>
 - <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- p. *The standard defines the attribute `draw:dots2-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- q. *The standard defines the attribute `draw:name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- r. *The standard defines the attribute `draw:style`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>

- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

Excel interprets all styles as 'rect'.

- s. *The standard defines the element <draw:stroke-dash>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this element for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- t. *The standard defines the attribute draw:display-name, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

PowerPoint 2013 does not support this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- u. *The standard defines the attribute draw:distance, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- v. *The standard defines the attribute `draw:dots1`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- w. *The standard defines the attribute `draw:dots1-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- x. *The standard defines the attribute `draw:dots2`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- y. *The standard defines the attribute `draw:dots2-length`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

- z. *The standard defines the attribute `draw:name`, contained within the element `<draw:stroke-dash>`, contained within the parent element `<office:styles>`*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>

- <draw:image>
 - <draw:text-box>
 - <draw:custom-shape>
- aa. *The standard defines the attribute draw:style, contained within the element <draw:stroke-dash>, contained within the parent element <office:styles>*

PowerPoint 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

PowerPoint interprets all styles as "rect".

2.1.581 Section 14.15, Presentation Page Layouts

- a. *The standard defines the element <style:presentation-page-layout>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint ignores presentation page layouts. On save, PowerPoint writes out presentation page layouts.

- b. *The standard defines the attribute style:display-name, contained within the element <style:presentation-page-layout>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- c. *The standard defines the attribute style:name, contained within the element <style:presentation-page-layout>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.582 Section 14.15.1, Presentation Placeholder

- a. *The standard defines the element <presentation:placeholder>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the attribute presentation:object, contained within the element <presentation:placeholder>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the attribute `svg:height`, contained within the element `<presentation:placeholder>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- d. *The standard defines the attribute `svg:width`, contained within the element `<presentation:placeholder>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- e. *The standard defines the attribute `svg:x`, contained within the element `<presentation:placeholder>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the attribute `svg:y`, contained within the element `<presentation:placeholder>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.583 Section 15, Formatting Properties

- a. *The standard defines the parent element `<style:graphic-properties>`*

Word 2013 supports this for a style applied to any of the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` element containing a `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- b. *The standard defines the element `<style:graphic-properties>`*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the element `<style:header-footer-properties>`*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the element `<style:list-level-properties>`*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt.

- e. *The standard defines the element `<style:page-layout-properties>`*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- g. *The standard defines the element <style:ruby-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- h. *The standard defines the element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- i. *The standard defines the element <style:table-cell-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- j. *The standard defines the element <style:table-column-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- k. *The standard defines the element <style:table-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- l. *The standard defines the element <style:table-row-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- m. *The standard defines the element <style:text-properties>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- n. This is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

p. *The standard defines the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

q. *The standard defines the element <style:header-footer-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

r. *The standard defines the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, and for SmartArt.

s. *The standard defines the element <style:page-layout-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

t. *The standard defines the element <style:paragraph-properties>*

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

u. *The standard defines the element <style:ruby-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

v. *The standard defines the element <style:section-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

w. *The standard defines the element <style:table-cell-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

x. *The standard defines the element <style:table-column-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

y. *The standard defines the element <style:table-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

z. The standard defines the element <style:table-row-properties>

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

aa. The standard defines the element <style:text-properties>

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

bb. This is supported in PowerPoint 2010 and PowerPoint 2013.

cc. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

dd. *The standard defines the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

ee. *The standard defines the element <style:header-footer-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

ff. *The standard defines the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

gg. *The standard defines the element <style:page-layout-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

hh. *The standard defines the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

ii. *The standard defines the element <style:ruby-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

jj. *The standard defines the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

kk. *The standard defines the element <style:table-cell-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- <draw:custom-shape>.

ll. *The standard defines the element <style:table-column-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

mm. *The standard defines the element <style:table-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

nn. *The standard defines the element <style:table-row-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

oo. *The standard defines the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.584 Section 15.1, Simple and Complex Formatting Properties

- OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
- The standard defines the parent element <style:graphic-properties>*

Word 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles

- labels

d. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

e. This is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

f. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.585 Section 15.1.1, Simple Formatting Properties

- a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.
- b. *The standard defines the parent element <style:graphic-properties>*

Word 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- d. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

e. This is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

f. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.586 Section 15.1.2, Complex Formatting Properties

a. OfficeArt Math in Word 2013 supports this on save for text in SmartArt and chart titles and labels.

b. *The standard defines the parent element <style:graphic-properties>*

Word 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

c. This is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

d. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

e. This is supported in PowerPoint 2010 and PowerPoint 2013.

OfficeArt Math in PowerPoint 2013 supports this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

f. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.587 Section 15.1.3, Processing Rules for Formatting Properties

a. OfficeArt Math in Word 2013 does not support this on save for text in SmartArt and chart titles and labels.

b. *The standard defines the parent element <style:graphic-properties>*

Word 2013 does not support this for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g> or <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Custom formatting attributes and elements (not defined in the ODF version 1.1 spec) are not preserved.

c. OfficeArt Math in Excel 2013 does not support this on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

d. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 does not support this for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Custom formatting attributes and elements (not defined in the standard) are not preserved.

e. OfficeArt Math in PowerPoint 2013 does not support this on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

f. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 does not support this for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Custom formatting attributes and elements (not defined in the standard) are not preserved.

2.1.588 Section 15.2, Page Layout Formatting Properties

- a. *The standard defines the element <style:page-layout-properties>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <style:page-layout-properties>*

This element is supported in Excel 2010 and Excel 2013.

2.1.589 Section 15.2.1, Page Size

- a. *The standard defines the attribute fo:page-height, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute fo:page-width, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute fo:page-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute fo:page-width, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute fo:page-height, contained within the element <style:page-layout-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the attribute fo:page-width, contained within the element <style:page-layout-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.590 Section 15.2.2, Page Number Format

- a. *The standard defines the attribute style:num-prefix, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:num-suffix, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute text:num-format, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute style:num-format, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute style:num-prefix, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute style:num-suffix, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute style:num-format, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- h. *The standard defines the attribute style:num-prefix, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- i. *The standard defines the attribute style:num-suffix, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.591 Section 15.2.3, Paper Tray

- a. *The standard defines the attribute style:paper-tray-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:paper-tray-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:paper-tray-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.592 Section 15.2.4, Print Orientation

- a. *The standard defines the attribute `style:print-orientation`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `style:print-orientation`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `style:print-orientation`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint ignores this attribute, but writes it out on save.

2.1.593 Section 15.2.5, Margins

- a. *The standard defines the attribute `fo:margin`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `fo:margin-left`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute `fo:margin-top`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `fo:margin`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute `fo:margin-left`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute fo:margin-right, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute fo:margin-top, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the attributes in the <style:page-layout-properties> element and calculates values as follows:

The header size is set to the value of the fo:margin-top attribute.

The footer size is set to the value of the fo:margin-bottom attribute.

The right margin size is set to the value of the fo:margin-right attribute.

The left margin size is set to the value of the fo:margin-left attribute.

The top margin size is set:

- to the value of the fo:margin-top attribute and the value of the fo:margin-bottom attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.
- and to the value of fo:min-height attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.

The bottom margin size is set:

- to the value of the fo:margin-bottom attribute and the value of the fo:margin-top attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.
- and to the value of fo:min-height attribute of the <style:header-footer-properties> element that is contained in the <style:header-style> element.

On save, Excel writes values for attributes in the <style:page-layout-properties> element as follows:

- Excel writes the fo:margin-top attribute as the value of the top margin size, or the header size, whichever is less.
- Excel writes the fo:margin-bottom attribute as the value of the bottom margin size or the footer size, whichever is less.
- Excel writes the fo:margin-left attribute as the value of the left margin size.
- Excel writes the fo:margin-right attribute as the value of the right margin size.

On save, Excel writes values for properties in the <style:header-footer-properties> element of the <style:header-style> element's as follows:

- Excel writes the fo:min-height attribute as the top margin size minus the header size. If this value is less than or equal to 0, the value is written as "0".
- Excel writes the fo:margin-left attribute as the left margin size.
- Excel writes the fo:margin-right attribute as the right margin size.
- Excel writes the fo:margin-bottom attribute as "0".

On save, Excel writes values for properties in the <style:footer-style> element's <style:header-footer-properties> element as follows:

Excel writes the fo:min-height attribute as the bottom margin size minus the footer size. If this value is less than or equal to 0, the value is written as "0".

Excel writes the fo:margin-left attribute as the left margin size.

Excel writes the fo:margin-right attribute as the value of the right margin size.

Excel writes the fo:margin-top as the value "0".

On save, Excel always writes the style:display attribute of the <style:header> element as "true".

On save, Excel always writes the style:display attribute of the <style:footer> element as "true".

- k. *The standard defines the attribute fo:margin, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the attribute fo:margin-bottom, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute fo:margin-left, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute fo:margin-right, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- o. *The standard defines the attribute fo:margin-top, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.594 Section 15.2.6, Border

- a. *The standard defines the attribute fo:border, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

1. Page borders with widths that cannot be generated by Word are normalized to the default border width.
2. The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:
 - Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
 - Word supports all values for color.

- b. *The standard defines the attribute fo:border-bottom, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

1. Page borders with widths that cannot be generated by Word are normalized to the default border width.
2. The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
 - Word supports all values for color.
- c. *The standard defines the attribute fo:border-left, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

1. Page borders with widths that cannot be generated by Word are normalized to the default border width.
 2. The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:
 - Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
 - Word supports all values for color.
- d. *The standard defines the attribute fo:border-right, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

1. Page borders with widths that cannot be generated by Word are normalized to the default border width.
 2. The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:
 - Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
 - Word supports all values for color.
- e. *The standard defines the attribute fo:border-top, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

1. Page borders with widths that cannot be generated by Word are normalized to the default border width.
 2. The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:
 - Word supports all values of border-width, and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
 - Word supports all values for color.
- f. *The standard defines the attribute fo:border, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute fo:border-bottom, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute fo:border-left, contained within the element <style:page-layout-properties>*
This attribute is not supported in Excel 2010 or Excel 2013.
- i. *The standard defines the attribute fo:border-right, contained within the element <style:page-layout-properties>*
This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute fo:border-top, contained within the element <style:page-layout-properties>*
This attribute is not supported in Excel 2010 or Excel 2013.
- k. *The standard defines the attribute fo:border, contained within the element <style:page-layout-properties>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- l. *The standard defines the attribute fo:border-bottom, contained within the element <style:page-layout-properties>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- m. *The standard defines the attribute fo:border-left, contained within the element <style:page-layout-properties>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- n. *The standard defines the attribute fo:border-right, contained within the element <style:page-layout-properties>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- o. *The standard defines the attribute fo:border-top, contained within the element <style:page-layout-properties>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.595 Section 15.2.7, Border Line Width

- a. *The standard defines the attribute style:border-line-width, contained within the element <style:page-layout-properties>*
This attribute is not supported in Word 2010 or Word 2013.
Word ignores this property on load, but writes it out on save for double borders.
- b. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:page-layout-properties>*
This attribute is not supported in Word 2010 or Word 2013.
Word ignores this property on load, but writes it out on save for double borders.
- c. *The standard defines the attribute style:border-line-width-left, contained within the element <style:page-layout-properties>*
This attribute is not supported in Word 2010 or Word 2013.

Word ignores this property on load, but writes it out on save for double borders.

- d. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

Word ignores this property on load, but writes it out on save for double borders.

- e. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

Word ignores this property on load, but writes it out on save for double borders

- f. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `style:border-linewidth-left`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.596 Section 15.2.8, Padding

- a. *The standard defines the attribute fo:padding, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.
- b. *The standard defines the attribute fo:padding-bottom, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.
- c. *The standard defines the attribute fo:padding-left, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.
- d. *The standard defines the attribute fo:padding-right, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.
- e. *The standard defines the attribute fo:padding-top, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.
- f. *The standard defines the attribute fo:padding, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.
- g. *The standard defines the attribute fo:padding-bottom, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.
- h. *The standard defines the attribute fo:padding-left, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.
- i. *The standard defines the attribute fo:padding-top, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.
- j. *The standard defines the attribute fo:padding, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- k. *The standard defines the attribute fo:padding-bottom, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- l. *The standard defines the attribute fo:padding-left, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the attribute fo:padding-right, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the attribute fo:padding-top, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.597 Section 15.2.9, Shadow

- a. *The standard defines the attribute style:shadow, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

All values for style:shadow property map to the default page border shadow in Word.

- b. *The standard defines the attribute style:shadow, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:shadow, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.598 Section 15.2.10, Background

- a. *The standard defines the attribute fo:background-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <style:background-image>, contained within the parent element <style:page-layout-properties>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute fo:background-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute fo:background-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the attribute style:background-image, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.599 Section 15.2.11, Columns

- a. *The standard defines the element <style:columns>, contained within the parent element <style:page-layout-properties>*

This element is not supported in Excel 2010 or Excel 2013.

- b. *The standard defines the attribute style:columns, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.600 Section 15.2.12, Register-truth

- a. *The standard defines the attribute style:register-truth-ref-style, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:register-truth-ref-style-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:register-truth-ref-style-name, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.601 Section 15.2.13, Print

- a. *The standard defines the attribute style:print, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:print, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel only reads the following values: headers, grid, and annotations. On save, Excel only writes the following values: objects, charts, and drawings.

- c. *The standard defines the property "annotations", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property "charts", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the property "drawings", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "formulas", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the property "grid", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the property "headers", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "objects", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "zero-values", contained within the attribute style:print, contained within the element <style:page-layout-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute style:print, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.602 Section 15.2.14, Print Page Order

- a. *The standard defines the attribute style:print-page-order, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:print-page-order, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute style:print-page-order, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.603 Section 15.2.15, First Page Number

- a. *The standard defines the attribute style:first-page-number, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:first-page-number, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute style:first-page-number, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.604 Section 15.2.16, Scale

- a. *The standard defines the attribute style:scale-to, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:scale-to-pages`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `style:scale-to`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the attribute `style:scale-to-pages`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `style:scale-to`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the attribute `style:scale-to-pages`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.605 Section 15.2.17, Table Centering

- a. *The standard defines the attribute `style:table-centering`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:table-centering`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `style:table-centering`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.606 Section 15.2.18, Maximum Footnote Height

- a. *The standard defines the attribute `style:footnote-max-height`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:footnote-max-height`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `style:footnote-max-height`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.607 Section 15.2.19, Writing Mode

- a. *The standard defines the property "lr", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2010 or Word 2013.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- b. *The standard defines the property "lr-tb", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2010 or Word 2013.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- d. *The standard defines the property "rl", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2010 or Word 2013.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- e. *The standard defines the property "rl-tb", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is supported in Word 2010 and Word 2013.

- f. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is not supported in Word 2010 or Word 2013.

For all unsupported values of the style:writing-mode attribute, Word maps to the default text direction, based on the locale of the application.

- g. *The standard defines the property "tb-lr", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is supported in Word 2010 and Word 2013.

- h. *The standard defines the property "tb-rl", contained within the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute style:writing-mode, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.608 Section 15.2.20, Footnote Separator

- a. *The standard defines the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:adjustment, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute style:color, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute style:distance-after-sep, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute style:distance-before-sep, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute style:line-style, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load and on save, Word supports the following line styles for the style:line-style attribute: "solid", "dotted", "dashed", and "none". All other line styles map to a default of "solid".

- g. *The standard defines the attribute style:rel-width, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, all values for the style:rel-width attribute map to a default footnote separator width.

- h. *The standard defines the attribute style:width, contained within the element <style:footnote-sep>, contained within the parent element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, all values for the style:width attribute map to a default footnote separator width.

- i. *The standard defines the element <style:footnote-sep>*

This element is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute style:adjustment, contained within the element <style:footnote-sep>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute style:color, contained within the element <style:footnote-sep>*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute `style:distance-after-sep`, contained within the element `<style:footnote-sep>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute `style:distance-before-sep`, contained within the element `<style:footnote-sep>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute `style:line-style`, contained within the element `<style:footnote-sep>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the attribute `style:rel-width`, contained within the element `<style:footnote-sep>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- p. *The standard defines the attribute `style:width`, contained within the element `<style:footnote-sep>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the attribute `style:footnote-sep`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- r. *The standard defines the element `<style:footnote-sep>`, contained within the parent element `<style:page-layout-properties>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.609 Section 15.2.21, Layout Grid

- a. *The standard defines the attribute `style:layout-grid-mode`, contained within the element `<style:page-layout-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `style:layout-grid-mode`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `style:layout-grid-mode`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.610 Section 15.2.22, Layout Grid Base Height

- a. *The standard defines the attribute `style:layout-grid-base-height`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

On load Word uses style:layout-grid-base-height and style:layout-grid-ruby-height properties to calculate the number of lines per page. If either of these properties is missing then style:layout-grid-lines is used. However, Word does not save the style:layout-grid-base-height property.

- b. *The standard defines the attribute style:layout-grid-base-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:layout-grid-base-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.611 Section 15.2.23, Layout Grid Ruby Height

- a. *The standard defines the attribute style:layout-grid-ruby-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

On load Word uses style:layout-grid-ruby-height and style:layout-grid-base-height properties to calculate the number of lines per page. If either of these properties is missing then style:layout-grid-lines property is used. However, Word does not save the style:layout-grid-ruby-height property.

- b. *The standard defines the attribute style:layout-grid-ruby-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:layout-grid-ruby-height, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.612 Section 15.2.24, Layout Grid Lines

- a. *The standard defines the attribute style:layout-grid-lines, contained within the element <style:page-layout-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:layout-grid-lines, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:layout-grid-lines, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.613 Section 15.2.25, Layout Grid Color

- a. *The standard defines the attribute style:layout-grid-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:layout-grid-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:layout-grid-color, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.614 Section 15.2.26, Layout Grid Ruby Below

- a. *The standard defines the attribute style:layout-grid-ruby-below, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

In Word, ruby text is always displayed preceding the base text. If the text direction is vertical, ruby text is displayed to the left of the base text.

- b. *The standard defines the attribute style:layout-grid-ruby-below, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:layout-grid-ruby-below, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.615 Section 15.2.27, Layout Grid Print

- a. *The standard defines the attribute style:layout-grid-ruby-print, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:layout-grid-ruby-print, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:layout-grid-ruby-print, contained within the element <style:page-layout-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.616 Section 15.2.28, Layout Grid Display

- a. *The standard defines the attribute style:layout-grid-ruby-display, contained within the element <style:page-layout-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:layout-grid-ruby-print, contained within the element <style:page-layout-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `style:layout-grid-ruby-display`, contained within the element `<style:page-layout-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.617 Section 15.3, Header Footer Formatting Properties

- a. *The standard defines the element `<style:header-footer-properties>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element `<style:header-footer-properties>`*

This element is supported in Excel 2010 and Excel 2013.

On save, Excel does not write the header or footer information if the "Different First Page" option is selected for the worksheet.

Excel's maximum length for headers and footers is 255 characters.

- c. *The standard defines the element `<style:header-footer-properties>`*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.618 Section 15.3.1, Fixed and Minimum heights

- a. *The standard defines the attribute `fo:min-height`, contained within the element `<style:header-footer-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `svg:height`, contained within the element `<style:header-footer-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `fo:min-height`, contained within the element `<style:header-footer-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the attribute `svg:height`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.619 Section 15.3.2, Margins

- a. *The standard defines the attribute `fo:margin`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `fo:margin-left`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `fo:margin-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute `fo:margin`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the attribute `fo:margin-left`, contained within the element `<style:header-footer-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:header-footer-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the attribute `fo:margin-top`, contained within the element `<style:header-footer-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.620 Section 15.3.3, Border

- a. *The standard defines the attribute `fo:border`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `fo:border-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `fo:border-left`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `fo:border-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `fo:border-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute fo:border, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute fo:border-bottom, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute fo:border-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute fo:border-right, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute fo:border-top, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.621 Section 15.3.4, Border Line Width

- a. *The standard defines the attribute style:border-line-width, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute style:border-line-width-left, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute style:border-line-width-right, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute style:border-line-width-top, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute style:border-line-width, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `style:border-linewidth-left`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.622 Section 15.3.5, Padding

- a. *The standard defines the attribute `fo:padding`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `fo:padding-left`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute `fo:padding`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `fo:padding-left`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:header-footer-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.623 Section 15.3.6, Background

- a. *The standard defines the attribute fo:background-color, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the element <style:background-image>, contained within the parent element <style:header-footer-properties>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute fo:background-color, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.624 Section 15.3.7, Shadow

- a. *The standard defines the attribute style:shadow, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:shadow, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.625 Section 15.3.8, Dynamic Spacing

- a. *The standard defines the attribute style:dynamic-spacing, contained within the element <style:header-footer-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:dynamic-spacing, contained within the element <style:header-footer-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.626 Section 15.4, Text Formatting Properties

- a. *The standard defines the element <style:text-properties>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:text-properties>*

This element is supported in Excel 2010 and Excel 2013.

On load, Excel applies only the non-asian or non-complex version of the font property, if it is specified, for any font property that ends in "-asian" or "-complex". If the non-asian or non-

complex version of the property is not specified, then Excel applies the font property that ends in "-asian" or "-complex", and that is read last.

On save, Excel writes the same value for all three types of these font properties. This is because Excel does not support dynamically selecting a different font based on evaluating UNICODE characters as either CJK, CTL, or other.

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

c. *The standard defines the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.627 Section 15.4.1, Font Variant

a. *The standard defines the attribute fo:font-variant, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

If, on load, both text:font-variant="small-caps" and fo:text-transform="uppercase" are applied to the text span, then Word does not apply either property to the text.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:font-variant, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the property "normal", contained within the attribute fo:font-variant, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the property "small-caps", contained within the attribute fo:font-variant, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute fo:font-variant, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.628 Section 15.4.2, Text Transformations

- a. *The standard defines the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "capitalized", contained within the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

This property is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property "lowercase", contained within the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

This property is not supported in Word 2010 or Word 2013.

- d. *The standard defines the property "none", contained within the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the property "uppercase", contained within the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

This property is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. Excel does not support the value of "capitalize" for this attribute. When this attribute has a value of "capitalize", Excel interprets it as a value of "none".

- g. *The standard defines the property "capitalize", contained within the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the property "lowercase", contained within the attribute `fo:text-transform`, contained within the element `<style:text-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the property "none", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the property "uppercase", contained within the attribute fo:text-transform, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute fo:text-transform, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

PowerPoint does not support "fo:text-transform=capitalize" and interprets this as "fo:text-transform=none".

2.1.629 Section 15.4.3, Color

- a. *The standard defines the attribute fo:color, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:color, contained within the element <style:text-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

c. *The standard defines the attribute fo:color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.630 Section 15.4.4, Window Font Color

a. *The standard defines the attribute style:use-window-font-color, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

b. *The standard defines the attribute style:use-window-font-color, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
 - shapes
 - SmartArt
 - chart titles
 - labels
- c. *The standard defines the attribute `style:use-window-font-color`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.631 Section 15.4.5, Text Outline

- a. *The standard defines the attribute `style:text-outline`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-outline`, contained within the element `<style:text-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes

- shapes
 - SmartArt
 - chart titles
 - labels
- c. *The standard defines the attribute style:text-outline, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.632 Section 15.4.6, Line-Through Type

- a. *The standard defines the attribute style:text-line-through-type, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-line-through-type, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes

- SmartArt
 - chart titles
 - labels
- c. *The standard defines the attribute `style:text-line-through-type`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.633 Section 15.4.7, Line-Through Style

- a. *The standard defines the attribute `style:text-line-through-style`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, any non-"none" value in OOXML is written to ODF as "solid" for this property.

- b. *The standard defines the attribute `style:text-line-through-style`, contained within the element `<style:text-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel maps the value "none" to no strikethrough, and all other enumeration values to solid strikethrough. On save, Excel maps solid strikethrough to the value "solid", and no strikethrough to the value "none".

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. Strikethrough line type values other than the value of "solid" are not supported in OOXML. On load, all enumerations that do not have a value of "none" are mapped to a value of "solid".

On save, this attribute is written as "solid" for all strikethrough line types that do not have a value of "none".

- c. *The standard defines the property "dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- d. *The standard defines the property "dot-dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- e. *The standard defines the property "dot-dot-dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- f. *The standard defines the property "dotted", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- g. *The standard defines the property "long-dash", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- h. *The standard defines the property "none", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

On load, Excel maps this property to no strikethrough. On save, Excel maps this property to "none".

- i. *The standard defines the property "solid", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- j. *The standard defines the property "wave", contained within the attribute style:text-line-through-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps any property of the style:text-line-through-style attribute that does not have the value "none" to solid strikethrough.

- k. *The standard defines the attribute style:text-line-through-style, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, all enumerations (except for "none") are mapped to solid strikethrough because other types of strikethrough lines are not supported in PowerPoint.

On write, any non-"none" value in PowerPoint is written to ODF as "solid" for this property.

2.1.634 Section 15.4.8, Line-Through Width

- a. *The standard defines the attribute style:text-line-through-width, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, all widths, except 0 or 0%, are mapped to a default strikethrough width.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, this property is always written as "auto" for strikethrough values that are not set to "none".

- b. *The standard defines the attribute style:text-line-through-width, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. OOXML does not support strikethrough widths. On load, this attribute maps as though it had a value of "auto".

On save, this attribute is written as "auto" when strikethrough does not have a value of "none".

- c. *The standard defines the attribute style:text-line-through-width, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the value for this property is always mapped as if it was "auto" because PowerPoint does not support strikethrough widths.

On write, for non-"none" strikethrough values, this property is always written as "auto".

2.1.635 Section 15.4.9, Line-Through Color

- a. *The standard defines the attribute style:text-line-through-color, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

On load and on save, Word always matches the current font color.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, this property is always written as "font-color" for strikethrough values that are not set to "none".

- b. *The standard defines the attribute style:text-line-through-color, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels.

The only value supported in OOXML for this attribute is the value of "font-color". On load, this attribute maps to a value of "font-color" when it does not have a value of "none". On save, this attribute maps to a value of "font-color" when it does not have a value of "none".

- c. *The standard defines the attribute style:text-line-through-color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the value for this property is always mapped as if it was "font-color" because this is the only value supported in PowerPoint.

On write, for non-"none" strikethrough values, this property is always written as "font-color".

2.1.636 Section 15.4.10, Line-Through Text

- a. *The standard defines the attribute style:text-line-through-text, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:text-linethrough-text, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:text-line-through-text, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `style:text-linethrough-text`, contained within the element `<style:text-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `style:text-linethrough-text`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.637 Section 15.4.11, Line-Through Text Style

- a. *The standard defines the attribute `style:text-line-through-text-style`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:text-linethrough-text-style`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:text-line-through-text-style`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `style:text-linethrough-text-style`, contained within the element `<style:text-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `style:text-linethrough-text-style`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.638 Section 15.4.12, Text Position

- a. *The standard defines the attribute `style:text-position`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

Word applies the style:text-position property as a vertical position change, with the following exceptions:

- If the second item in the style:text-position attribute string value is less than 67% then Word displays the text as subscripted or superscripted, instead of applying a vertical position change to the text.
- If the second item in the style:text-position attribute string value is greater than 67% and "sub" or "sup" is the first item in the string, then Word displays the text as subscripted or superscripted, instead of applying a vertical position change to the text.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt. The vertical text position value is always written as a percentage.

- b. *The standard defines the attribute style:text-position, contained within the element <style:text-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

The following enumerations map to a superscript value of 33 percent:

- super
- super <positive percent>
- <positive percent>
- sub <negative percent>

The following enumerations map to a subscript value of -33 percent:

- sub
- sub <positive percent>
- <negative percent>
- super <negative percent>

Enumerations with a value of 0 percent map to the No Vertical Alignment Setting.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes and SmartArt, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On load, enumerations "sub" and "super" are mapped to default numerical values and the font height percentage value is not supported.

On save, the vertical text position value is always written as a percentage.

- c. *The standard defines the property "<negative percent>", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "negative percent" property maps to a value of -33 percent.

- d. *The standard defines the property "<positive percent>", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "positive percent" property maps to a value of 33 percent.

- e. *The standard defines the property "sub", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "sub" property maps to a value of -33 percent.

- f. *The standard defines the property "sub <negative percent>", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "sub<negative percent>" property maps to a value of -33 percent.

- g. *The standard defines the property "sub <positive percent>", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "sub<positive percent>" property maps to a value of -33 percent.

- h. *The standard defines the property "super", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "super" property maps to a value of 33 percent.

- i. *The standard defines the property "super <negative percent>", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "super<negative percent>" property maps to a value of -33 percent.

- j. *The standard defines the property "super <positive percent>", contained within the attribute style:text-position, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

The "super<positive percent>" property maps to a value of 33 percent.

- k. *The standard defines the attribute style:text-position, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On load, enumerations "sub" and "super" are mapped to default numerical values, and the font height percentage value is not supported.

On save, the vertical text position value is always written as a percentage.

2.1.639 Section 15.4.13, Font Name

- a. *The standard defines the attribute style:font-name, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-name-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:font-name-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute style:font-name, contained within the element <style:text-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On load, this attribute is used to specify font. On save, the fo:font-family attribute is used to specify font instead.

- e. *The standard defines the attribute `style:font-name-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On load, this attribute is used to specify font. On save, the attribute `style:font-family-asian` is used to specify font instead.

- f. *The standard defines the attribute `style:font-name-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On load, this attribute is used to specify font. On save, the attribute `style:font-family-complex` is used to specify font instead.

- g. *The standard defines the attribute `style:font-name`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. On write, the "fo:font-family" property is used to specify font instead.

- h. *The standard defines the attribute style:font-name-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. On write, the "style:font-family-asian" property is used to specify font instead.

- i. *The standard defines the attribute style:font-name-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. On write, the "style:font-family-complex" property is used to specify font instead.

2.1.640 Section 15.4.14, Font Family

- a. *The standard defines the attribute fo:font-family, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

When applying font to a run of text on load, if it isn't specified via the style:font-name attribute in the office:font-face-decls element at the top of the XML part, Word looks for the style:font-family attribute on the immediate style:text-properties element. If Word finds it, then the font is applied to the run of text.

This attribute is not supported for font specifications in a list style definition.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-family-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

When applying font to a run of text on load, if it isn't specified via the style:font-name-asian attribute in the office:font-face-decls element at the top of the XML part, Word looks for the style:font-family-asian attribute on the immediate style:text-properties element. If Word finds it, then the font is applied to the run of text.

This attribute is not supported for font specifications in a list style definition.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:font-family-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

When applying font to a run of text on load, if it isn't specified via the style:font-name attribute in the office:font-face-decls element at the top of the XML part, Word looks for the style:font-family attribute on the immediate style:text-properties element. If Word finds it, then the font is applied to the run of text.

This attribute is not supported for font specifications in a list style definition.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:font-family, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
 - shapes
 - SmartArt
 - chart titles
 - labels
- e. *The standard defines the attribute `style:font-family`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `style:font-family-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
 - shapes
 - SmartArt
 - chart titles
 - labels
- g. *The standard defines the attribute `style:font-family-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`

- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- h. *The standard defines the attribute fo:font-family, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the attribute style:font-family-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the attribute style:font-family-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.641 Section 15.4.15, Font Family Generic

- a. *The standard defines the attribute `style:font-family-generic`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-family-generic-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:font-family-generic-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `style:font-family-generic`, contained within the element `<style:text-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt

- chart titles
 - labels
- e. *The standard defines the attribute `style:font-family-generic-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute `style:font-family-generic-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute `style:font-family-generic`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- h. *The standard defines the attribute `style:font-family-generic-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- i. *The standard defines the attribute `style:font-family-generic-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.642 Section 15.4.16, Font Style

- a. *The standard defines the attribute `style:font-style-name`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-style-name-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:font-style-name-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `style:font-style-name`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `style:font-style-name-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute `style:font-style-name-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute `style:font-style-name`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- h. *The standard defines the attribute style:font-style-name-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the attribute style:font-style-name-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.643 Section 15.4.17, Font Pitch

- a. *The standard defines the attribute style:font-pitch, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-pitch-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:font-pitch-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `style:font-pitch`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `style:font-pitch-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute `style:font-pitch-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute `style:font-pitch`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- h. *The standard defines the attribute style:font-pitch-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the attribute style:font-pitch-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.644 Section 15.4.18, Font Character Set

- a. *The standard defines the attribute style:font-charset, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the property "<other>", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the property "x-symbol", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `style:font-charset-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `style:font-charset-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the attribute `style:font-charset`, contained within the element `<style:text-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel supports only the value "x-symbol" to identify symbol fonts.

- g. *The standard defines the property "`<character encoding>`", contained within the attribute `style:font-charset`, contained within the element `<style:text-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the property "`<other>`", contained within the attribute `style:font-charset`, contained within the element `<style:text-properties>`*

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- i. *The standard defines the property "x-symbol", contained within the attribute `style:font-charset`, contained within the element `<style:text-properties>`*

This property is supported in Excel 2010 and Excel 2013.

Excel supports only the value "x-symbol" to identify symbol fonts.

OfficeArt Math in Excel 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in text boxes and shapes, SmartArt, and chart titles and labels, On load, this value of this attribute is used. It is not saved.

- j. *The standard defines the attribute `style:font-charset-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- k. *The standard defines the attribute `style:font-charset-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- l. *The standard defines the property "<other>", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the property "x-symbol", contained within the attribute style:font-charset, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, this value is mapped. It is not written out.

- n. *The standard defines the attribute `style:font-charset-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- o. *The standard defines the attribute `style:font-charset-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.645 Section 15.4.19, Font Size

- a. *The standard defines the attribute `fo:font-size`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

Word does not support percentage font sizes for the font size attribute. If a percentage font-size is used for the font size attribute, the text becomes the same size as the parent style on load.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:font-size-asian`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

Word does not support percentage font sizes for the font size attribute. If a percentage font-size is used for the font size attribute, the text becomes the same size as the parent style on load.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:font-size-complex`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

Word does not support percentage font sizes for the font size attribute. If a percentage font-size is used for the font size attribute, the text becomes the same size as the parent style on load.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:font-size`, contained within the element `<style:text-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `style:font-size-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute `style:font-size-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute `fo:font-size`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
 - <draw:custom-shape>.
- h. *The standard defines the attribute style:font-size-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the attribute style:font-size-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.646 Section 15.4.20, Relative Font Size

- a. *The standard defines the attribute style:font-size-rel, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-size-rel-asian, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:font-size-rel-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `style:font-size-rel`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `style:font-size-rel-asian`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

f. *The standard defines the attribute `style:font-size-rel-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

g. *The standard defines the attribute `style:font-size-rel`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

h. *The standard defines the attribute `style:font-size-rel-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- i. *The standard defines the attribute `style:font-size-rel-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.647 Section 15.4.21, Script Type

- a. *The standard defines the attribute `style:script-type`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "asian", contained within the attribute `style:script-type`, contained within the element `<style:text-properties>`*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "complex", contained within the attribute `style:script-type`, contained within the element `<style:text-properties>`*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "ignore", contained within the attribute `style:script-type`, contained within the element `<style:text-properties>`*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the property "latin", contained within the attribute style:script-type, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

Word uses a Boolean setting to signal whether a range of text should be treated as a complex script or not.

On load, if style:script-type is "complex", then the text is tagged as complex script. If the script-type attribute is "asian" or "latin" then the text is tagged as "not complex". A value of "ignore" causes Word to ignore this attribute.

On save, if this Word property states that the text is "complex", then Word writes style:script-type="complex" to the file. Otherwise, nothing is written to the file for this attribute.

- f. *The standard defines the attribute style:script-type, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute style:script-type, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.648 Section 15.4.22, Letter Spacing

- a. *The standard defines the attribute fo:letter-spacing, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:letter-spacing, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute fo:letter-spacing, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute style:letter-spacing, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute style:letter-spacing, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.649 Section 15.4.23, Language

- a. *The standard defines the attribute fo:language, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word preserves the fo:language attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

If the language is missing, Word ignores both the language and the country.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:language", "fo:language-asian" and "fo:language-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:country", "style:country-asian", and "style:country-complex".

- b. *The standard defines the attribute fo:language-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word preserves the fo:language-asian property as a part of a country language id (as specified by BCP 47) applied to the text range.

If the language is missing, Word ignores both the language and country.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:language", "fo:language-asian" and "fo:language-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:country", "style:country-asian", and "style:country-complex" attributes.

- c. *The standard defines the attribute fo:language-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word preserves the fo:language-complex property as a part of a country language id (as specified by BCP 47) applied to the text range.

If the language is missing, Word ignores both the language and country.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF

"fo:language", "fo:language-asian" and "fo:language-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:country", "style:country-asian", and "style:country-complex" attributes.

- d. *The standard defines the attribute fo:language, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, and fo:language-complex attributes is used to populate the Excel lang attribute. Excel's altLang attribute is not populated on read.

- e. *The standard defines the attribute fo:language-asian, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, and fo:language-complex attributes is used to populate the Excel lang attribute. Excel's altLang attribute is not populated on read.

- f. *The standard defines the attribute fo:language-complex, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, and fo:language-complex attributes is used to populate the Excel lang attribute. Excel's altLang attribute is not populated on read.

- g. *The standard defines the attribute style:language-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute style:language-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute fo:language, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, or fo:language-complex attributes is used to populate the PowerPoint lang attribute. PowerPoint's altLang attribute is not populated on read.

- j. *The standard defines the attribute fo:language-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, or fo:language-complex attributes is used to populate the PowerPoint lang attribute. PowerPoint's altLang attribute is not populated on read.

- k. *The standard defines the attribute fo:language-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, the script type for the first character of the run is used to determine which of the fo:language, fo:language-asian, or fo:language-complex attributes is used to populate the PowerPoint lang attribute. PowerPoint's altLang attribute is not populated on read.

2.1.650 Section 15.4.24, Country

- a. *The standard defines the attribute fo:country, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word preserves the fo:country attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:country", "style:country-asian" and "style:country-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:language", "fo:language-asian", and "fo:language-complex" attributes.

- b. *The standard defines the attribute style:country-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word preserves the style:country-asian attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:country", "style:country-asian" and "style:country-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a

different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:language", "fo:language-asian", and "fo:language-complex" attributes.

- c. *The standard defines the attribute style:country-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word preserves the style:country-complex attribute as a part of a country language id (as specified by BCP 47) applied to the text range.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, OOXML's run properties "lang" and "altLang" are used to populate the ODF "fo:country", "style:country-asian" and "style:country-complex" text property attributes. First, "lang" is mapped to the corresponding attribute according to script type. Second, if "altLang" is a different script type than "lang", "altLang" is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If "altLang" is the same script type as "lang", it is not written and the remaining two ODF attributes are not written out. This method is also used to populate "fo:language", "fo:language-asian", and "fo:language-complex" attributes.

- d. *The standard defines the attribute fo:country, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:country, style:country-asian, and style:country-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:language, fo:language-asian, and fo:language-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the Excel lang property.

- e. *The standard defines the attribute style:country-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

This attribute is supported in Excel 2010 and Excel 2013.

scope /> on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:country, style:country-asian, and style:country-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate fo:language, fo:language-asian, and fo:language-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the Excel lang property.

- f. *The standard defines the attribute style:country-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in Excel are used to populate the ODF fo:country, style:country-asian, and style:country-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:language, fo:language-asian, and fo:language-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the Excel lang property.

- g. *The standard defines the attribute fo:country, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the PowerPoint lang property.

- h. *The standard defines the attribute style:country-asian, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the PowerPoint lang property.

- i. *The standard defines the attribute style:country-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On write, the run properties lang and altLang in PowerPoint are used to populate the ODF fo:language, fo:language-asian, and fo:language-complex text property attributes. First, lang is mapped to the corresponding attribute according to script type. Second, if altLang is a different script type than lang, altLang is mapped to the corresponding ODF attribute according to script type, and the third ODF attribute is not written out. If altLang is the same script type as lang, it is not written, and the remaining two ODF attributes are not written out. This method is also used to populate the fo:country, style:country-asian, and style:country-complex attributes.

On read, this attribute is dropped. The fo:language, fo:language-asian, and fo:language-complex attributes are used to populate the PowerPoint lang property.

2.1.651 Section 15.4.25, Font Style

- a. *The standard defines the attribute fo:font-style, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:font-style-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:font-style-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:font-style, contained within the element <style:text-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, the values "italic" and "oblique" both map to a value of "italic".

On save, Excel writes only the values "normal" and "italic".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the property "italic", contained within the attribute fo:font-style, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "normal", contained within the attribute fo:font-style, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the property "oblique", contained within the attribute fo:font-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, and on save, Excel maps the fo:font-style attribute to italic.

- h. *The standard defines the attribute style:font-style-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- i. *The standard defines the attribute style:font-style-complex, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- j. *The standard defines the attribute fo:font-style, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- k. *The standard defines the attribute `style:font-style-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- l. *The standard defines the attribute `style:font-style-complex`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.652 Section 15.4.26, Font Relief

- a. *The standard defines the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "embossed", contained within the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the property "engraved", contained within the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `style:font-relief`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the property "embossed", contained within the attribute style:font-relief, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the property "engraved", contained within the attribute style:font-relief, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this enum on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the property "embossed", contained within the attribute style:font-relief, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- h. *The standard defines the property "engraved", contained within the attribute style:font-relief, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.653 Section 15.4.27, Text Shadow

- a. *The standard defines the attribute fo:text-shadow, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:text-shadow, contained within the element <style:text-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel interprets size values greater than 0 to mean that text shadow is activated.

On save, Excel writes "1pt1pt" when text has a shadow, or "none" when text does not have a shadow.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the fo:text-shadow attribute is mapped to the <outerShdw> element of OOXML. Where there is no correspondence between the fo:text-shadow attribute and the <outerShdw> element, default values are used.

- c. *The standard defines the attribute fo:text-shadow, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the fo:text-shadow attribute is mapped to the PowerPoint <outerShdw> element with default values.

2.1.654 Section 15.4.28, Underlining Type

- a. *The standard defines the attribute style:text-underline-type, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-underline-type, contained within the element <style:text-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On save, Excel converts its Single Accounting type to the value "single," and its Double Accounting type to the value "double".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML. On load, no underline is read if either the style:text-underline-type attribute or the style:text-underline-style attribute has a value of "none".

- c. *The standard defines the attribute `style:text-underline-type`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On read, the properties `style:text-underline-type`, `style:text-underline-style`, `style:text-underline-width`, and `style:text-underline-mode` are considered together to determine which enumeration to set for the `u` (Underline) run property attribute in PowerPoint.

On read, if either of the properties `"style:text-underline-type="none"` or `"style:text-underline-style="none"`, no underline is read.

2.1.655 Section 15.4.29, Underlining Style

- a. *The standard defines the attribute `style:text-underline-style`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-underline-style`, contained within the element `<style:text-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel maps the value "none" to "No Line Style". All other values of the attribute `style:text-underline-style` map to "Solid Line Style".

On save, Excel writes only the values "none" or "solid".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`

- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and the mode named style:text-underline are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML.

On load, no underline is read if either the style:text-underline-type attribute or the style:text-underline-style attribute has a value of "none".

On load, an underline type with a value of "double" takes precedence over underline style. Only the enumeration values of "solid" and "wave" are supported for underline types with a value of "double" in OOXML. For example, if the style:text-underline-type attribute has a value of "double" and the style:text-underline-style attribute has a value that is anything other than "solid" or "wave", then the style:text-underline-type attribute is changed to "double" and the style:text-underline-style attribute is changed to "solid".

- c. *The standard defines the property "dash", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

The property "dash" maps to "solid underline".

- d. *The standard defines the property "dot-dash", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

The property "dot-dash" maps to "solid underline".

- e. *The standard defines the property "dot-dot-dash", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

The property "dot-dot-dash" maps to "solid underline".

- f. *The standard defines the property "dotted", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

The property "dot-dot-dash" maps to "solid underline".

- g. *The standard defines the property "long-dash", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

The property "long-dash" maps to "solid underline".

- h. *The standard defines the property "none", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

- i. *The standard defines the property "solid", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

- j. *The standard defines the property "wave", contained within the attribute style:text-underline-style, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

The property "long-dash" maps to "solid underline".

- k. *The standard defines the attribute style:text-underline-style, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and the mode named style:text-underline are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML.

On load, no underline is read if either the style:text-underline-type attribute or the style:text-underline-style attribute has a value of "none".

On load, an underline type with a value of "double" takes precedence over underline style. Only the enumeration values of "solid" and "wave" are supported for underline types with a value of "double" in OOXML. For example, if the style:text-underline-type attribute has a value of "double" and the style:text-underline-style attribute has a value that is anything other than "solid" or "wave", then the style:text-underline-type attribute is changed to "double" and the style:text-underline-style attribute is changed to "solid".

2.1.656 Section 15.4.30, Underling Width

- a. *The standard defines the attribute style:text-underline-width, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-underline-width, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML. On load, all enumerations that have values other than "bold" and "thick" are treated as having a value of "normal". On save, the only values written are "auto" and "bold".

- c. *The standard defines the attribute style:text-underline-width, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On load, the style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are considered together to determine which enumeration to set for the u (Underline) run property attribute in PowerPoint.

On load, all enumerations other than "bold" and "thick" are treated as "normal".

On save, "auto" and "bold" are the only values written.

2.1.657 Section 15.4.31, Underline Color

- a. *The standard defines the attribute `style:text-underline-color`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:underline-color`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `style:text-underline-color`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- d. *The standard defines the attribute `style:text-underline-color`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.658 Section 15.4.32, Font Weight

- a. *The standard defines the attribute fo:font-weight, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

Word does not support a gradient of font weights; it only supports the ability to turn bold on or off. On load, font weights from 100-500 map to "normal", and font weights from 600-900 map to "bold".

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, "bold" and "normal" are the only values written.

- b. *The standard defines the attribute style:font-weight-asian, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

Word does not support a gradient of font weights; it only supports the ability to turn bold on or off. On load, font weights from 100-500 map to "normal", and font weights from 600-900 map to "bold".

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, "bold" and "normal" are the only values written.

- c. *The standard defines the attribute style:font-weight-complex, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

Word does not support a gradient of font weights; it only supports the ability to turn bold on or off. On load, font weights from 100-500 map to "normal", and font weights from 600-900 map to "bold".

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, "bold" and "normal" are the only values written.

- d. *The standard defines the attribute fo:font-weight, contained within the element <style:text-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel maps the following values to the "Bold" font style: "bold", "400", "500", "600", "700", "800", and "900". Excel maps all other values to the "Regular" font style.

On save, Excel writes "bold" if the font style is "Bold" or "Bold Italic". Excel writes "normal" if the font style is "Regular" or "Italic".

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the following values are read as "bold": "bold", "600", and "700". All other values are read as "normal". On save, the only values written are "bold" and "normal".

- e. *The standard defines the property "100", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- f. *The standard defines the property "200", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- g. *The standard defines the property "300", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- h. *The standard defines the property "400", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- i. *The standard defines the property "500", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- j. *The standard defines the property "600", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- k. *The standard defines the property "700", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- l. *The standard defines the property "800", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- m. *The standard defines the property "900", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the following values from the fo:font-weight attribute to bold: "bold", "400", "500", "600", "700", "800", and "900". Any other value maps to "normal".

- n. *The standard defines the property "bold", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the property "normal", contained within the attribute fo:font-weight, contained within the element <style:text-properties>*

This property is supported in Excel 2010 and Excel 2013.

- p. *The standard defines the attribute style:font-weight-asian, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the following values are read as "bold": "bold", "600", and "700". All other values are read as "normal". On save, the only values written are "bold" and "normal".

- q. *The standard defines the attribute `style:font-weight-complex`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the following values are changed to "bold": "bold", "600", and "700". All other values are read as "normal". On save, the only values written are "bold" and "normal".

- r. *The standard defines the attribute `fo:font-weight`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on read for text that is contained in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On read, the following values are read as "bold": "bold", "600", and "700". All other values are read as "normal".

On write, "bold" and "normal" are the only values written.

- s. *The standard defines the attribute `style:font-weight-asian`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the following values are read as "bold": "bold", "600", "700". All other values are read as "normal".

On write, "bold" and "normal" are the only values written.

- t. *The standard defines the attribute style:font-weight-complex, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the following values are read as "bold": "bold", "600", "700". All other values are read as "normal".

On write, "bold" and "normal" are the only values written.

2.1.659 Section 15.4.33, Text Underline Word Mode

- a. *The standard defines the attribute style:text-underline-mode, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load and on save, Word only supports the style:text-underline-mode property when style:text-underline-style="solid".

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-underline-mode, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

On load, Excel ignores the "skip-white-space" value to apply underline to all characters in a text run. On save, Excel does not write the style:text-underline-mode attribute.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, the attributes named style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are all used in determining which enumeration to set for the u (Underline) run attribute in OOXML.

- c. *The standard defines the attribute style:text-underline-mode, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

On read, the style:text-underline-type, style:text-underline-style, style:text-underline-width, and style:text-underline-mode are considered together to determine which enumeration to set for the u (Underline) run property attribute in PowerPoint.

2.1.660 Section 15.4.34, Text Line-Through Word Mode

- a. *The standard defines the attribute style:text-line-through-mode, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-line-through-mode, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

In Excel, line-through is equivalent to strikethrough.

On load, Excel ignores the "skip-white-space" value to apply strikethrough to all characters in the text run. On save, Excel does not write the style:text-line-through-mode attribute.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:text-line-through-mode, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.661 Section 15.4.35, Letter Kerning

- a. *The standard defines the attribute style:letter-kerning, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. On write, all nonzero values are mapped to "true".

- b. *The standard defines the attribute `style:letter-kerning`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels. On load, a value of "true" is mapped to a default integer. On save, all nonzero values are mapped to "true".

- c. *The standard defines the attribute `style:letter-kerning`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`

On read, a "true" value is mapped to a default integer.

On write, all nonzero values are mapped to "true".

2.1.662 Section 15.4.36, Text Blinking

- a. *The standard defines the attribute `style:text-blinking`, contained within the element `<style:text-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-blinking`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `style:text-blinking`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.663 Section 15.4.37, Text Background Color

- a. *The standard defines the attribute `fo:background-color`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:background-color, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:background-color, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.664 Section 15.4.38, Text Combine

- a. *The standard defines the attribute style:text-combine, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "letters", contained within the attribute style:text-combine, contained within the element <style:text-properties>*

This property is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property "lines", contained within the attribute style:text-combine, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "none", contained within the attribute style:text-combine, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute style:text-combine, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute style:text-combine, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.665 Section 15.4.39, Text Combine Start and End Characters

- a. *The standard defines the attribute `style:text-combine-end-char`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

On load and on save, Word supports the following characters for this attribute: ">", "}", ")", "]", ".".

If a character is used that Word does not recognize, Word uses the default ")" character.

Word requires the start and end characters be a matching set - for example, "<" and ">".

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-combine-start-char`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

On load and on save, Word supports the following characters for this attribute: "<", "{", "(", "[", ".".

If a character is used that Word does not recognize, Word uses the default "(" character.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `style:text-combine-end-char`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- d. *The standard defines the attribute `style:text-combine-start-char`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `style:text-combine-end-char`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- f. *The standard defines the attribute `style:text-combine-start-char`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.666 Section 15.4.40, Text Emphasis

- a. *The standard defines the property "accent above", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "accent below", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property "circle above", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "circle below", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is not supported in Word 2010 or Word 2013.

- e. *The standard defines the property "disc above", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is not supported in Word 2010 or Word 2013.

- f. *The standard defines the property "disc below", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is not supported in Word 2010 or Word 2013.

- g. *The standard defines the property "dot above", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- h. *The standard defines the property "dot below", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the property "none", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- j. *The standard defines the property "none above", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- k. *The standard defines the property "none below", contained within the attribute style:text-emphasis, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- l. *The standard defines the attribute style:text-emphasize, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- m. *The standard defines the attribute style:text-emphasis, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the attribute style:text-emphasize, contained within the element <style:text-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- o. *The standard defines the attribute style:text-emphasize, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
- <draw:custom-shape>.

2.1.667 Section 15.4.41, Text Scale

- a. *The standard defines the attribute style:text-scale, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, percentage values that are less than 1% are rounded up to 1%, and percentage values that are greater than 600% are rounded down to 600%.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:text-scale, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute style:text-scale, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.668 Section 15.4.42, Text Rotation Angle

- a. *The standard defines the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "0", contained within the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

On load, if both style:text-rotation-angle and style:text-combine are applied to the text span, then Word ignores the style:text-rotation-angle property.

- c. *The standard defines the property "270", contained within the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

This property is not supported in Word 2010 or Word 2013.

- d. *The standard defines the property "90", contained within the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute style:text-rotation-angle, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles

- labels
- f. *The standard defines the attribute `style:text-rotation-angle`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.669 Section 15.4.43, Text Rotation Scale

- a. *The standard defines the attribute `style:text-rotation-scale`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "fixed", contained within the attribute `style:text-rotation-scale`, contained within the element `<style:text-properties>`*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "line-height", contained within the attribute `style:text-rotation-scale`, contained within the element `<style:text-properties>`*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute `style:text-rotation-scale`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

On load and on save, Excel does not read or write this attribute. Excel always renders rotated text such that the width of the text remains fixed.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`

- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
 - shapes
 - SmartArt
 - chart titles
 - labels
- e. *The standard defines the property "fixed", contained within the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the property "line-height", contained within the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

This property is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute style:text-rotation-scale, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.670 Section 15.4.44, Hyphenation

- a. *The standard defines the attribute fo:hyphenate, contained within the element <style:text-properties>*

This attribute is supported in Word 2010 and Word 2013.

Word has an auto-hyphenation property at the document level and a "do not hyphenate" property at the paragraph level. The ODF auto-hyphenation property is stored at the text property level.

On load, Word sets the document-level auto-hyphenation property to true. If a paragraph style is set to not to auto-hyphenate the current paragraph, then Word sets the paragraph-level "do not hyphenate" property to true. Otherwise, Word sets this property to false.

On save, Word always sets fo:hyphenate to true in the text properties of the default paragraph style. For each paragraph style in the document, Word sets fo:hyphenate to true or fo:hyphenate to false based on the value used in the default paragraph style.

Word does not support the fo:hyphenate property from any other styles that can contain a style:text-properties element. For example, if text is contained within a span that is within a paragraph, then Word ignores the value of fo:hyphenate defined by the span and applies the value defined by the paragraph.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenate, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:hyphenate, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.671 Section 15.4.45, Hyphenation Remain Char Count

- a. *The standard defines the attribute fo:hyphenation-remain-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-remain-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:hyphenation-remain-char-count, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.672 Section 15.4.46, Hyphenation Push Char Count

- a. *The standard defines the attribute fo:hyphenation-push-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-push-char-count, contained within the element <style:text-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:hyphenation-push-char-count, contained within the element <style:text-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.673 Section 15.4.47, Hidden or Conditional Text

- a. *The standard defines the attribute `text:display`, contained within the element `<style:text-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `text:display-levels`, contained within the element `<style:text-properties>`*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `text:condition`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `text:display`, contained within the element `<style:text-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `text:display-levels`, contained within the element `<style:text-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- f. *The standard defines the attribute `text:display-levels`, contained within the element `<style:text-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.674 Section 15.5, Paragraph Formatting Properties

- a. *The standard defines the element <style:paragraph-properties>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:paragraph-properties>*

This element is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.675 Section 15.5.1, Fixed Line Height

- a. *The standard defines the attribute fo:line-height, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:line-height, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:line-height, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.676 Section 15.5.2, Minimum Line Height

- a. *The standard defines the attribute style:line-height-at-least, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:line-height-at-least`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `style:line-height-at-least`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.677 Section 15.5.3, Line Distance

- a. *The standard defines the attribute `style:line-distance`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:line-spacing`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `style:line-distance`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute style:line-spacing, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute style:line-distance, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.678 Section 15.5.4, Font-Independent Line Spacing

- a. *The standard defines the attribute style:font-independent-line-space, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:font-independent-line-spacing, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:font-independent-line-spacing, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute style:font-independent-line-spacing, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.679 Section 15.5.5, Text Align

- a. *The standard defines the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel reads the start value as meaning left and the end value as meaning right. On save, Excel does not use the start value or end value.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels.

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On load, the values "start" and "end" map to the values "left" or "right" in OOXML, depending on text direction. If the text direction cannot be determined, "start" is mapped to "left" and "end" is mapped to "right".

- c. *The standard defines the property "center", contained within the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This property is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property "end", contained within the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the "end" property to right alignment. On save, the "end" property is not used, and right alignment is mapped to the "right" property.

- e. *The standard defines the property "justify", contained within the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "left", contained within the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This property is supported in Excel 2010 and Excel 2013.

- g. *The standard defines the property "right", contained within the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This property is supported in Excel 2010 and Excel 2013.

- h. *The standard defines the property "start", contained within the attribute fo:text-align, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the "start" property to left alignment. On save, the "start" property is not used, and left alignment is mapped to the "left" property.

- i. *The standard defines the attribute fo:text-align, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:image>
- <draw:text-box>
- <draw:custom-shape>

On read, "start" and "end" map to either "left" or "right" in PowerPoint depending on text direction. If text direction cannot be determined, "start" is mapped to "left" and "end" is mapped to "right".

2.1.680 Section 15.5.6, Text Align of Last Line

- a. *The standard defines the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the property "center", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the property "justify", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 does not support this enum on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the property "start", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 supports this enum on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the property "center", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels.

- g. *The standard defines the property "justify", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this enum on save for text in any of the following items: text boxes, shapes, SmartArt, chart titles, and labels.

- h. *The standard defines the property "start", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. This property is written out but is not read in. It is always written as fo:text-align-last="start".

- i. *The standard defines the property "center", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- j. *The standard defines the property "justify", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this enum on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- k. *The standard defines the property "start", contained within the attribute fo:text-align-last, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this enum on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

This property is written out but is not read in. It is always written as fo:text-align-last="start".

2.1.681 Section 15.5.7, Justify Single Word

- a. *The standard defines the attribute style:justify-single-word, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:justify-single-word, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:justify-single-word, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.682 Section 15.5.8, Keep Together

- a. *The standard defines the attribute fo:keep-together, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:keep-together, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:keep-together, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.683 Section 15.5.9, Widows

- a. *The standard defines the attribute fo:widows, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load and save, Word only supports a value of 2 lines for the fo:widows attribute; all nonzero values for the fo:widows attribute default to this value.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:widows, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:widows, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.684 Section 15.5.10, Orphans

- a. *The standard defines the attribute fo:orphans, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load and save, Word only supports a value of 2 lines for the fo:orphans attribute; all nonzero values for the fo:orphans attribute default to this value.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:orphans, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:orphans, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.685 Section 15.5.11, Tab Stops

- a. *The standard defines the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:char, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:char, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute style:leader-color, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute style:leader-color, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute style:leader-style, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- g. *The standard defines the property "dash", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

- h. *The standard defines the property "dot-dash", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

On load, Word interprets the "dot-dash" value of style:leader-style as a dotted line style, similar to that of the "dotted" value for this attribute.

- i. *The standard defines the property "dot-dot-dash", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

On load, Word interprets the "dot-dot-dash" value of style:leader-style as a dotted line style, similar to that of the "dotted" value for this attribute.

- j. *The standard defines the property "dotted", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

- k. *The standard defines the property "long-dash", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is not supported in Word 2010 or Word 2013.

- l. *The standard defines the property "none", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

- m. *The standard defines the property "solid", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

- n. *The standard defines the property "wave", contained within the attribute style:leader-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is not supported in Word 2010 or Word 2013.

- o. *The standard defines the attribute style:leader-text, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- p. *The standard defines the attribute style:leader-text, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is supported in Word 2010 and Word 2013.

On load and save, Word supports the following characters for the style:leader-text attribute: ".", "-", "_", " ", plus locale-specific characters defined by the country/language pair of the surrounding text.

On load, if Word does not recognize the character used, then it reverts to a default of no leader text.

- q. *The standard defines the attribute style:leader-text-style, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- r. *The standard defines the attribute style:leader-text-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Word 2010 or Word 2013.

- s. *The standard defines the attribute style:leader-type, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- t. *The standard defines the attribute style:leader-type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Word 2010 or Word 2013.

- u. *The standard defines the attribute style:leader-width, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- v. *The standard defines the attribute style:leader-width, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Word 2010 or Word 2013.

- w. *The standard defines the attribute style:position, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- x. *The standard defines the attribute style:position, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is supported in Word 2010 and Word 2013.

- y. *The standard defines the attribute style:type, contained within the element <style:tab-stop>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- z. *The standard defines the property "center", contained within the attribute style:type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

- aa. *The standard defines the property "char", contained within the attribute style:type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

Word allows the character used here to be based on the country/language pair of the surrounding text. For example, U.S. English surrounding text would allow the use of "." as the tab character.

- bb. *The standard defines the property "left", contained within the attribute style:type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

- cc. *The standard defines the property "right", contained within the attribute style:type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This property is supported in Word 2010 and Word 2013.

- dd. *The standard defines the element <style:tab-stops>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- ee. *The standard defines the element <style:tab-stops>, contained within the parent element <style:paragraph-properties>*

This element is supported in Word 2010 and Word 2013.

- ff. *The standard defines the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This element is not supported in Excel 2010 or Excel 2013.

- gg. *The standard defines the attribute style:char, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2010 or Excel 2013.

- hh. *The standard defines the attribute style:leader-color, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- ii. *The standard defines the attribute `style:leader-color`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- jj. *The standard defines the attribute `style:leader-style`, contained within the element `<style:tab-stop>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- kk. *The standard defines the attribute `style:leader-style`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- ll. *The standard defines the attribute `style:leader-text`, contained within the element `<style:tab-stop>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- mm. *The standard defines the attribute `style:leader-text`, contained within the element `<style:tab-stop>`, contained within the parent element `<style:tab-stops>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- nn. *The standard defines the attribute `style:leader-text-style`, contained within the element `<style:tab-stop>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

oo. *The standard defines the attribute style:leader-text-style, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2010 or Excel 2013.

pp. *The standard defines the attribute style:leader-type, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

qq. *The standard defines the attribute style:leader-type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2010 or Excel 2013.

rr. *The standard defines the attribute style:leader-width, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2010 or Excel 2013.

ss. *The standard defines the attribute style:position, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>

- <draw:text-box>
- <draw:custom-shape>

tt. *The standard defines the attribute style:position, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2010 or Excel 2013.

uu. *The standard defines the attribute style:type, contained within the element <style:tab-stop>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, the enumerated value "char" is not supported.

vv. *The standard defines the attribute style:type, contained within the element <style:tab-stop>, contained within the parent element <style:tab-stops>*

This attribute is not supported in Excel 2010 or Excel 2013.

ww. *The standard defines the element <style:tab-stops>*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

xx. *The standard defines the attribute style:char, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

yy. *The standard defines the attribute style:leader-color, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

zz. *The standard defines the attribute style:leader-style, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

aaa. *The standard defines the attribute style:leader-text, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

bbb. *The standard defines the attribute style:leader-text-style, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

ccc. *The standard defines the attribute style:leader-type, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

ddd. *The standard defines the attribute style:leader-width, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

eee. *The standard defines the attribute style:position, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

fff. *The standard defines the attribute style:type, contained within the element <style:tab-stop>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, the enumerated value "char" is not supported.

ggg. *The standard defines the element <style:tab-stops>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.686 Section 15.5.12, Tab Stop Distance

- a. *The standard defines the attribute style:tab-stop-distance, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:tab-stop-distance, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:tab-stop-distance, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.687 Section 15.5.13, Hyphenation Keep

- a. *The standard defines the attribute fo:hyphenation-keep, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-keep, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:hyphenation-keep, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.688 Section 15.5.14, Maximum Hyphens

- a. *The standard defines the attribute fo:hyphenation-ladder-count, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:hyphenation-ladder-count, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:hyphenation-ladder-count, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.689 Section 15.5.15, Drop Caps

- a. *The standard defines the element <style:drop-cap>, contained within the parent element <style:paragraph-properties>*

This element is supported in Word 2010 and Word 2013.

On save, if a second frame is anchored to the paragraph inside a drop cap, Word will lose the <style:drop-cap> element but retain the contents contained within the element tags.

On save and load, if a paragraph is both right-to-left and has a drop cap applied, Word will lose the <style:drop-cap> element but retain the contents contained within the element tags.

On save and load, if a paragraph has both fo:break-before=column and a drop cap applied, Word will lose the <style:drop-cap> element but retain the contents contained within the element tags.

- b. *The standard defines the attribute style:distance, contained within the element <style:drop-cap>, contained within the parent element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute style:length, contained within the element <style:drop-cap>, contained within the parent element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute style:lines, contained within the element <style:drop-cap>, contained within the parent element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute style:style-name, contained within the element <style:drop-cap>, contained within the parent element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the element <style:drop-caps>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- g. *The standard defines the element <style:drop-cap>*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- h. *The standard defines the attribute style:distance, contained within the element <style:drop-cap>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute style:length, contained within the element <style:drop-cap>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute style:lines, contained within the element <style:drop-cap>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute style:style-name, contained within the element <style:drop-cap>*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the element <style:drop-caps>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.690 Section 15.5.16, Register True

- a. *The standard defines the attribute style:register-true, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:register-true, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:register-true, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- `<draw:custom-shape>`.

2.1.691 Section 15.5.17, Left and Right Margins

- a. *The standard defines the attribute `fo:margin-left`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `fo:margin-left`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel maps this attribute to the indent value for text alignment.

On load, Excel only applies this attribute to the indent value for text alignment if the `fo:text-align` attribute is not specified, or either `fo:margin-left` has a value of "left" or `fo:margin-right` has a value of "right".

On save, Excel does not write this attribute if the alignment of the text is set to center or justified.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage values are not supported.

- d. *The standard defines the attribute `fo:margin-right`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

Excel maps this attribute to the indent value for text alignment.

On load, Excel only applies this attribute to the indent value for text alignment if the fo:text-align attribute is not specified, or either fo:margin-left has a value of "left" or fo:margin-right has a value of "right".

On save, Excel does not write this attribute if the alignment of the text is set to center or justified.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage values are not supported.

- e. *The standard defines the attribute fo:margin-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage values are not supported.

- f. *The standard defines the attribute fo:margin-right, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage values are not supported.

2.1.692 Section 15.5.18, Text Indent

- a. *The standard defines the attribute fo:text-indent, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:text-indent, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage values are not supported.

- c. *The standard defines the attribute fo:text-indent, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage values are not supported.

2.1.693 Section 15.5.19, Automatic Text Indent

- a. *The standard defines the attribute `style:auto-text-indent`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:auto-text-indent`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `style:auto-text-indent`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.694 Section 15.5.20, Top and Bottom Margins

- a. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:margin-top`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `fo:margin-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage value is always read as "0".

- d. *The standard defines the attribute fo:margin-top, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. On read, percentage value is always read as "0".

- e. *The standard defines the attribute fo:margin-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>

- <draw:custom-shape>

On read, percentage value is always read as "0".

- f. *The standard defines the attribute fo:margin-top, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

On read, percentage value is always read as "0".

2.1.695 Section 15.5.21, Margins

- a. *The standard defines the attribute fo:margin, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:margin, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.696 Section 15.5.22, Break Before and Break After

- a. *The standard defines the attribute fo:break-after, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "auto", contained within the attribute fo:break-after, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "column", contained within the attribute fo:break-after, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "page", contained within the attribute fo:break-after, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute fo:break-before, contained within the element <style:paragraph-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the property "auto", contained within the attribute fo:break-before, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the property "column", contained within the attribute fo:break-before, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- h. *The standard defines the property "page", contained within the attribute fo:break-before, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute fo:break-after, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute fo:break-before, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute fo:break-after, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- l. *The standard defines the attribute fo:break-before, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.697 Section 15.5.23, Paragraph Background Color

- a. *The standard defines the attribute fo:background-color, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:background-color, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:background-color, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.698 Section 15.5.24, Paragraph Background Image

- a. *The standard defines the element <style:background-image>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:background-image>, contained within the parent element <style:header-footer-properties>*

This element is not supported in Word 2010 or Word 2013.

- c. *The standard defines the element <style:background-image>, contained within the parent element <style:paragraph-properties>*

This element is not supported in Word 2010 or Word 2013.

- d. *The standard defines the element <office:binary-data>, contained within the parent element <style:background-image>*

This element is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the element <style:background-image>*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- f. *The standard defines the attribute draw:opacity, contained within the element <style:background-image>*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute style:filter-name, contained within the element <style:background-image>*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `style:position`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `style:repeat`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute `xlink:actuate`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute `xlink:href`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute `xlink:show`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute `xlink:type`, contained within the element `<style:background-image>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the element `<style:background-image>`*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.699 Section 15.5.25, Border

- a. *The standard defines the attribute `fo:border`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:border-bottom, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute fo:border-left, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute fo:border-right, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute fo:border-top, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. Support for each item in the string is as follows:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the attribute fo:border, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute fo:border-bottom, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- h. *The standard defines the attribute fo:border-left, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the attribute fo:border-right, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute fo:border-top, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute fo:border, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- l. *The standard defines the attribute fo:border-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the attribute fo:border-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- n. *The standard defines the attribute fo:border-right, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- o. *The standard defines the attribute fo:border-top, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.700 Section 15.5.26, Border Line Width

- a. *The standard defines the attribute style:border-line-width, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute style:border-line-width-left, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute style:border-line-width-right, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- g. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- h. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the attribute style:border-line-width-right, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute style:border-line-width-top, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute style:border-line-width, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- l. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the attribute style:border-line-width-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- n. *The standard defines the attribute style:border-line-width-right, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- o. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.701 Section 15.5.27, Padding

- a. *The standard defines the attribute `fo:padding`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `fo:padding-left`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the attribute `fo:padding`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- g. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- h. *The standard defines the attribute `fo:padding-left`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- i. *The standard defines the attribute fo:padding-right, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- j. *The standard defines the attribute fo:padding-top, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- k. *The standard defines the attribute fo:padding, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- l. *The standard defines the attribute fo:padding-bottom, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the attribute fo:padding-left, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- n. *The standard defines the attribute fo:padding-right, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- o. *The standard defines the attribute fo:padding-top, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.702 Section 15.5.28, Shadow

- a. *The standard defines the attribute style:shadow, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:shadow, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>

- <draw:custom-shape>
- c. *The standard defines the attribute style:shadow, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.703 Section 15.5.29, Keep with Next

- a. *The standard defines the attribute fo:keep-with-next, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:keep-with-next, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute fo:keep-with-next, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.704 Section 15.5.30, Line Numbering

- a. *The standard defines the attribute text:number-lines, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute text:number-lines, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute text:number-lines, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>

- <draw:frame>
- <draw:custom-shape>.

2.1.705 Section 15.5.31, Line Number Start Value

- a. *The standard defines the attribute text:line-number, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute text:line-number, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute text:line-number, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.706 Section 15.5.32, Text Autospace

- a. *The standard defines the attribute style:text-autospace, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:text-autospace`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `style:text-autospace`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.707 Section 15.5.33, Punctuation Wrap

- a. *The standard defines the attribute `style:punctuation-wrap`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:punctuation-wrap`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute `style:punctuation-wrap`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.708 Section 15.5.34, Line Break

- a. *The standard defines the attribute `style:line-break`, contained within the element `<style:paragraph-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:line-break`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:line-break, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.709 Section 15.5.35, Vertical Alignment

- a. *The standard defines the attribute style:vertical-align, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

Word defaults to a value of "baseline" instead of "auto".

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:vertical-align, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute `style:vertical-align`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.710 Section 15.5.36, Writing Mode

- a. *The standard defines the attribute `style:writing-mode`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. ODF's `style:writing-mode` under the element `<style:paragraph-properties>` assigned to a paragraph correspond to OOXML's paragraph attribute "rtl".

On save, only "rl-tb" and "lr-tb" are written for this attribute at the paragraph level, corresponding to the boolean "rtl" paragraph property in OOXML.

- b. *The standard defines the property "lr", contained within the attribute `style:writing-mode`, contained within the element `<style:paragraph-properties>`*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "lr-tb", contained within the attribute `style:writing-mode`, contained within the element `<style:paragraph-properties>`*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "page", contained within the attribute `style:writing-mode`, contained within the element `<style:paragraph-properties>`*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps the "page" value for `style:writing-mode` attribute to the default text direction for the language of the paragraph.

- e. *The standard defines the property "rl", contained within the attribute `style:writing-mode`, contained within the element `<style:paragraph-properties>`*

This property is supported in Word 2010 and Word 2013.

- f. *The standard defines the property "rl-tb", contained within the attribute `style:writing-mode`, contained within the element `<style:paragraph-properties>`*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps the "tb" value for style:writing-mode to the default text direction for the language of the paragraph.

- h. *The standard defines the property "tb-lr", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the property "tb-rl", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is supported in Word 2010 and Word 2013.

- j. *The standard defines the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, Excel defaults to context-dependent reading order unless the following values are specified:

- "lr"
- "lr-tb"
- "tb-lr"
- "rl"
- "rl-tb"
- "tb-rl"

The values "lr", "lr-tb", and "tb-lr" are interpreted as left-to-right. The values "rl", "rl-tb", and "tb-rl" are interpreted as right-to-left.

On save, Excel will not write a value when the reading order is context dependent. Excel will write the value "rl" when right-to-left is set or the value "lr" when left-to-right is set.

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

And on save for text in text boxes and shapes, SmartArt, and chart titles and labels. ODF's attribute style:writing-mode under the element <style:paragraph-properties> assigned to a paragraph correspond to OOXML's paragraph attribute "rtl".

On read, enumerations "rl-tb" and "rl" are mapped to OOXML rtl=true, and all other values map to rtl=false.

On write, only "rl-tb" and "lr-tb" are written for this attribute at the paragraph level, corresponding to the boolean "rtl" paragraph property in OOXML.

- k. *The standard defines the property "lr", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is supported in Excel 2010 and Excel 2013.

- l. *The standard defines the property "lr-tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, when encountering this value, Excel will set the reading order to left-to-right.

- m. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel defaults to context-dependent reading order, because the left-to-right or right-to-left reading order was not specified.

- n. *The standard defines the property "rl", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is supported in Excel 2010 and Excel 2013.

- o. *The standard defines the property "rl-tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, when encountering this value, Excel will set the reading order to right-to-left.

- p. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel defaults to context-dependent reading order, because the left-to-right or right-to-left reading order was not specified.

- q. *The standard defines the property "tb-lr", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, when encountering this value, Excel will set the reading order to left-to-right.

- r. *The standard defines the property "tb-rl", contained within the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, when encountering this value, Excel will set the reading order to right-to-left.

- s. *The standard defines the attribute style:writing-mode, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

ODF's attribute style:writing-mode under the element <style:paragraph-properties> assigned to a paragraph correspond to PowerPoint's paragraph attribute "rtl".

On read, enumerations "rl-tb" and "rl" are mapped to PowerPoint "rtl" equals the value true, and all other values map to "rtl" equals the value false.

On write, only "rl-tb" and "lr-tb" are written for this attribute at the paragraph level, corresponding to the boolean "rtl" paragraph property in PowerPoint.

2.1.711 Section 15.5.37, Automatic Writing Mode

- a. *The standard defines the attribute style:writing-mode-automatic, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:writing-mode-automatic, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:writing-mode-automatic, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.712 Section 15.5.38, Snap To Layout

- a. *The standard defines the attribute style:snap-to-layout-grid, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:snap-to-layout-grid, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:snap-to-layout-grid, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.713 Section 15.5.39, Page Number

- a. *The standard defines the attribute style:page-number, contained within the element <style:paragraph-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:page-number, contained within the element <style:paragraph-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:page-number, contained within the element <style:paragraph-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.714 Section 15.5.40, Background Transparency

- a. *The standard defines the attribute style:background-transparency, contained within the element <style:paragraph-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `style:background-transparency`, contained within the element `<style:paragraph-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `style:background-transparency`, contained within the element `<style:paragraph-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.715 Section 15.6, Ruby Text Formatting Properties

- a. *The standard defines the element `<style:ruby-properties>`*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element `<style:ruby-properties>`*

This element is supported in Excel 2010 and Excel 2013.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

c. *The standard defines the element <style:ruby-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.716 Section 15.6.1, Ruby Position

a. *The standard defines the attribute style:ruby-position, contained within the element <style:ruby-properties>*

This attribute is not supported in Word 2010 or Word 2013.

Word always displays Ruby text above the base text or to the left of the base text when text direction is vertical.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

b. *The standard defines the attribute style:ruby-position, contained within the element <style:ruby-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
 - <draw:text-box>
 - <draw:custom-shape>
- c. *The standard defines the attribute style:ruby-position, contained within the element <style:ruby-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.717 Section 15.6.2, Ruby Alignment

- a. *The standard defines the attribute style:ruby-align, contained within the element <style:ruby-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:ruby-align, contained within the element <style:ruby-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:ruby-align, contained within the element <style:ruby-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.718 Section 15.7, Section Formatting Properties

- a. *The standard defines the element <style:section-properties>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:section-properties>*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.719 Section 15.7.1, Section Background

- a. *The standard defines the element <style:background-image>, contained within the parent element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:background-color, contained within the element <style:section-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the element <style:background-image>, contained within the parent element <style:section-properties>*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute fo:background-color, contained within the element <style:section-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the element <style:background-image>, contained within the parent element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- f. *The standard defines the attribute fo:background-color, contained within the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.720 Section 15.7.2, Margins

- a. *The standard defines the attribute fo:margin-left, contained within the element <style:section-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin-right, contained within the element <style:section-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute fo:margin-left, contained within the element <style:section-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- d. *The standard defines the attribute fo:margin-right, contained within the element <style:section-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- e. *The standard defines the attribute fo:margin-left, contained within the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- f. *The standard defines the attribute fo:margin-right, contained within the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.721 Section 15.7.3, Columns

- a. *The standard defines the element <style:columns>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <style:columns>, contained within the parent element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute fo:column-count, contained within the element <style:columns>*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute fo:column-gap, contained within the element <style:columns>*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the element <style:columns>*

This element is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the element <style:columns>, contained within the parent element <style:section-properties>*

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- g. *The standard defines the attribute `fo:column-count`, contained within the element `<style:columns>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `fo:column-gap`, contained within the element `<style:columns>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the element `<style:columns>`, contained within the parent element `<style:section-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

2.1.722 Section 15.7.4, Column Specification

- a. *The standard defines the element `<style:column>`, contained within the parent element `<style:columns>`*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:end-indent`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `fo:space-after`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `fo:space-before`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `fo:start-indent`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `style:rel-width`, contained within the element `<style:column>`, contained within the parent element `<style:columns>`*

This attribute is supported in Word 2010 and Word 2013.

- g. *The standard defines the element <style:column>, contained within the parent element <style:columns>*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- h. *The standard defines the attribute fo:end-indent, contained within the element <style:column>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute fo:space-after, contained within the element <style:column>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute fo:space-before, contained within the element <style:column>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- k. *The standard defines the attribute fo:start-indent, contained within the element <style:column>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the attribute style:rel-width, contained within the element <style:column>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the element <style:column>, contained within the parent element <style:columns>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.723 Section 15.7.5, Column Separator

- a. *The standard defines the element <style:column-sep>, contained within the parent element <style:columns>*

This element is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:color, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute style:height, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the property "dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Word 2010 or Word 2013.

- e. *The standard defines the property "dot-dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Word 2010 or Word 2013.

- f. *The standard defines the property "dotted", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Word 2010 or Word 2013.

- g. *The standard defines the property "none", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is supported in Word 2010 and Word 2013.

- h. *The standard defines the property "solid", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the attribute style:vertical-align, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2010 or Word 2013.

- j. *The standard defines the attribute style:width, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Word 2010 or Word 2013.

- k. *The standard defines the element <style:column-sep>, contained within the parent element <style:columns>*

This element is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this element on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- l. *The standard defines the attribute style:color, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the attribute style:height, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the property "dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the property "dot-dashed", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2010 or Excel 2013.

- p. *The standard defines the property "dotted", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the property "none", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2010 or Excel 2013.

- r. *The standard defines the property "solid", contained within the attribute style:style, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This property is not supported in Excel 2010 or Excel 2013.

- s. *The standard defines the attribute style:vertical-align, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- t. *The standard defines the attribute style:width, contained within the element <style:column-sep>, contained within the parent element <style:columns>*

This attribute is not supported in Excel 2010 or Excel 2013.

- u. *The standard defines the element <style:column-sep>, contained within the parent element <style:columns>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.724 Section 15.7.6, Protect

- a. *The standard defines the attribute style:protect, contained within the element <style:section-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute style:protect, contained within the element <style:section-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute style:protect, contained within the element <style:section-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.725 Section 15.7.7, Don't Balance Text Columns

- a. *The standard defines the attribute `text:don't-balance-text-columns`, contained within the element `<style:section-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `text:don't-balance-text-columns`, contained within the element `<style:section-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

- c. *The standard defines the attribute `text:don't-balance-text-columns`, contained within the element `<style:section-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.726 Section 15.7.8, Writing Mode

- a. *The standard defines the attribute style:writing-mode, contained within the element <style:section-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the property "lr", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "lr-tb", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "page", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Word 2010 or Word 2013.

For all unsupported values of the style:writing-mode attribute, Word reverts to the default text direction based on the locale of the application.

- e. *The standard defines the property "rl", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Word 2010 or Word 2013.

For all unsupported values of the style:writing-mode attribute, Word reverts to the default text direction based on the locale of the application.

- f. *The standard defines the property "rl-tb", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the property "tb", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is not supported in Word 2010 or Word 2013.

For all unsupported values of the style:writing-mode attribute, Word reverts to the default text direction based on the locale of the application.

- h. *The standard defines the property "tb-lr", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the property "tb-rl", contained within the attribute style:writing-mode, contained within the element <style:section-properties>*

This property is supported in Word 2010 and Word 2013.

- j. *The standard defines the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- k. *The standard defines the property `"lr-tb"`, contained within the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- l. *The standard defines the property `"page"`, contained within the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the property `"rl-tb"`, contained within the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- n. *The standard defines the property `"tb"`, contained within the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- o. *The standard defines the property `"tb-lr"`, contained within the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- p. *The standard defines the property `"tb-rl"`, contained within the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

This property is not supported in Excel 2010 or Excel 2013.

- q. *The standard defines the attribute `style:writing-mode`, contained within the element `<style:section-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.727 Section 15.7.9, Notes Configuration

- a. *The standard defines the element <text:notes-configuration>, contained within the parent element <style:section-properties>*

This element is not supported in Excel 2010 or Excel 2013.

2.1.728 Section 15.8, Table Formatting Properties

- a. *The standard defines the element <style:table-properties>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <style:table-properties>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the element <style:table-properties>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.729 Section 15.8.1, Table Width

- a. *The standard defines the attribute style:rel-width, contained within the element <style:table-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, if the width of the table is greater than can be supported by Word, the table will be automatically sized to fit the page.

- b. *The standard defines the attribute style:width, contained within the element <style:table-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, if the width of the table is greater than can be supported by Word, the table will be automatically sized to fit the page.

- c. *The standard defines the attribute style:rel-width, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute style:width, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.730 Section 15.8.2, Table Alignment

- a. *The standard defines the property "center", contained within the attribute table:align, contained within the element <style:table-properties>*

This property is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "left", contained within the attribute table:align, contained within the element <style:table-properties>*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "margins", contained within the attribute table:align, contained within the element <style:table-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word treats this value for the table:align attribute as "left".

- d. *The standard defines the property "right", contained within the attribute table:align, contained within the element <style:table-properties>*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute table:align, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.731 Section 15.8.3, Table Left and Right Margin

- a. *The standard defines the attribute fo:margin-left, contained within the element <style:table-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute fo:margin-right, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute fo:margin-left, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute fo:margin-right, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.732 Section 15.8.4, Table Top and Bottom Margin

- a. *The standard defines the attribute fo:margin-bottom, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute fo:margin-top, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute fo:margin-bottom, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute fo:margin-top, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.733 Section 15.8.5, Table Margins

- a. *The standard defines the attribute fo:margin, contained within the element <style:table-properties>*

This attribute is supported in Word 2010 and Word 2013.

Word only supports a left margin for tables. On load, the value for fo:margin is applied to the left margin for the table.

- b. *The standard defines the attribute fo:margins, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.734 Section 15.8.6, Page Number

- a. *The standard defines the attribute style:page-number, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:page-number, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.735 Section 15.8.7, Break Before and Break After

- a. *The standard defines the attribute fo:break-after, contained within the element <style:table-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word applies the fo:break-after attribute to the document as a page break (after the table) that is separate from the table.

- b. *The standard defines the attribute fo:break-before, contained within the element <style:table-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word applies the fo:break-before attribute to the document as a page break (before the table) that is separate from the table.

- c. *The standard defines the attribute fo:break-after, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute fo:break-before, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.736 Section 15.8.8, Table Background and Background Image

- a. *The standard defines the attribute fo:background-color, contained within the element <style:table-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads and applies the fo:background-color attribute. On save, Word writes this attribute as a part of the cell style of each individual table cell in the table.

- b. *The standard defines the element <style:background-image>, contained within the parent element <style:table-properties>*

This element is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute fo:background-color, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.737 Section 15.8.9, Table Shadow

- a. *The standard defines the attribute style:shadow, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:shadow, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.738 Section 15.8.10, Keep with Next

- a. *The standard defines the attribute fo:keep-with-next, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute fo:keep-with-next, contained within the element <style:table-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.739 Section 15.8.11, May Break Between Rows

- a. *The standard defines the attribute style:may-break-between-rows, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:may-break-between-rows`, contained within the element `<style:table-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.740 Section 15.8.12, Border Model Property

- a. *The standard defines the attribute `table:border-model`, contained within the element `<style:table-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

Word only supports the "collapsing" value of the `table:border-model` attribute.

- b. *The standard defines the attribute `table:border-model`, contained within the element `<style:table-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.741 Section 15.8.13, Writing Mode

- a. *The standard defines the property "lr", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "lr-tb", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "page", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is not supported in Word 2010 or Word 2013.

- d. *The standard defines the property "rl", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the property "rl-tb", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is supported in Word 2010 and Word 2013.

- f. *The standard defines the property "tb", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is not supported in Word 2010 or Word 2013.

- g. *The standard defines the property "tb-lr", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is not supported in Word 2010 or Word 2013.

This value for the `style:writing-mode` attribute causes the layout of the table to be left-to-right.

- h. *The standard defines the property "tb-rl", contained within the attribute `style:writing-mode`, contained within the element `<style:table-properties>`*

This property is not supported in Word 2010 or Word 2013.

This value for the style:writing-mode attribute causes the layout of the table to be right-to-left.

- i. *The standard defines the attribute style:writing-mode, contained within the element <style:table-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.742 Section 15.8.14, Display

- a. *The standard defines the attribute table:display, contained within the element <style:table-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute table:display, contained within the element <style:table-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.743 Section 15.9, Column Formatting Properties

- a. *The standard defines the element <style:table-column-properties>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:column-width, contained within the element <style:table-column-properties>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute style:table-column-properties, contained within the element <style:style>*

This attribute is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property "style-properties-content", contained within the attribute style:table-column-properties, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the element <style:table-column-properties>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.744 Section 15.9.1, Column Width

- a. *The standard defines the attribute style:rel-column-width, contained within the element <style:table-column-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:column-width, contained within the element <style:table-column-properties>, contained within the parent element <style:style>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute style:rel-column-width, contained within the element <style:table-column-properties>, contained within the parent element <style:style>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.745 Section 15.9.2, Optimal Table Column Width

- a. *The standard defines the attribute `style:use-optimal-column-width`, contained within the element `<style:table-column-properties>`*

This attribute is supported in Word 2010 and Word 2013.

Word has a table-level autofit property, while ODF has autofit properties at both the row and column-level.

On load, if all the columns and all the rows of the table support the same value for this attribute, then it is preserved at the table-level. Otherwise, the property is lost.

- b. *The standard defines the property `"style:use-optimal-column-width"`, contained within the attribute `style:table-column-properties`, contained within the element `<style:style>`*

This property is supported in Excel 2010 and Excel 2013.

On load, if the `style:use-optimal-column-width` attribute contains the value "true", then Excel may widen the column to fit the digits of a number value entered in the column.

On save, Excel writes the value "true" for the `style:use-optimal-column-width` attribute for columns that do not have a default width because they have been widened to fit an existing number value.

Excel writes the value "false" for the `style:use-optimal-column-width` attribute if the column has been set to a custom size or the column has not been automatically widened to fit an existing number value.

2.1.746 Section 15.9.3, Break Before and Break After

- a. *The standard defines the attribute `fo:break-after`, contained within the element `<style:table-column-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `fo:break-before`, contained within the element `<style:table-column-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property `"fo:break-after"`, contained within the attribute `style:table-column-properties`, contained within the element `<style:style>`*

This property is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property `"fo:break-before"`, contained within the attribute `style:table-column-properties`, contained within the element `<style:style>`*

This property is supported in Excel 2010 and Excel 2013.

2.1.747 Section 15.10, Table Row Formatting Properties

- a. *The standard defines the element `<style:table-row-properties>`*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <style:table-row-properties>, contained within the parent element <style:style>*

This element is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the element <style:table-row-properties>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.748 Section 15.10.1, Row Height

- a. *The standard defines the attribute style:min-row-height, contained within the element <style:table-row-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:row-height, contained within the element <style:table-row-properties>*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute style:min-row-height, contained within the element <style:table-row-properties>, contained within the parent element <style:style>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute style:row-height, contained within the element <style:table-row-properties>, contained within the parent element <style:style>*

This attribute is supported in Excel 2010 and Excel 2013.

On save, Excel writes a value of "0" if the row is hidden.

2.1.749 Section 15.10.2, Optimal Table Row Height

- a. *The standard defines the attribute style:use-optimal-row-height, contained within the element <style:table-row-properties>*

This attribute is supported in Word 2010 and Word 2013.

Word has a table-level autofit property, and ODF has autofit properties at both the row and column-level.

On load, if all the columns and all the rows of the table support the same value for this attribute, then it is preserved at the table-level. Otherwise, the property is not preserved.

- b. *The standard defines the property "style:use-optimal-row-height", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

2.1.750 Section 15.10.3, Row Background

- a. *The standard defines the attribute fo:background-color, contained within the element <style:table-row-properties>*

This attribute is supported in Word 2010 and Word 2013.

On load, Word reads and applies the fo:background-color attribute. On save, Word writes this attribute as a part of the cell style of each individual table cell in the row.

- b. *The standard defines the property "fo:background-color", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the property "style:background-image", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

2.1.751 Section 15.10.4, Break Before and Break After

- a. *The standard defines the attribute fo:break-after, contained within the element <style:table-row-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute fo:break-before, contained within the element <style:table-row-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the property "fo:break-before", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is supported in Excel 2010 and Excel 2013.

On load, if the fo:break-after property is set to any value other than "auto", then Excel sets a page break after the corresponding row or column. If the fo:break-before property is set to any value other than "auto" and the fo:break-after property is not specified, or set to "auto", then Excel sets a page break before the corresponding row or column. If both the fo:break-before and fo:break-after properties have a value of "auto" or are not specified, then Excel does not set a page break for the corresponding row or column.

On save, Excel writes out the value "auto" for the fo:break-before property, and either nothing or "page" for the fo:break-after property.

- d. *The standard defines the attribute fo:break-after, contained within the element <style:table-row-properties>, contained within the parent element <style:style>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.752 Section 15.10.5, Keep Together

- a. *The standard defines the attribute fo:keep-together, contained within the element <style:table-row-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "fo:keep-together", contained within the attribute style:table-row-properties, contained within the element <style:style>*

This property is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the element <style:table-cell-properties>*

This element is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.753 Section 15.11, Table Cell Formatting Properties

- a. *The standard defines the element <style:table-cell-properties>*

This element is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

2.1.754 Section 15.11.1, Vertical Alignment

- a. *The standard defines the attribute style:vertical-align, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute style:vertical-align, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the property "automatic", contained within the attribute style:vertical-align, contained within the element <style:table-cell-properties>*

This property is supported in Excel 2010 and Excel 2013.

- d. *The standard defines the property "bottom", contained within the attribute style:vertical-align, contained within the element <style:table-cell-properties>*

This property is not supported in Excel 2010 or Excel 2013.

On load, Excel maps the vertical alignment property to automatic.

- e. *The standard defines the property "middle", contained within the attribute style:vertical-align, contained within the element <style:table-cell-properties>*

This property is supported in Excel 2010 and Excel 2013.

- f. *The standard defines the property "top", contained within the attribute style:vertical-align, contained within the element <style:table-cell-properties>*

This property is supported in Excel 2010 and Excel 2013.

2.1.755 Section 15.11.2, Text Align Source

- a. *The standard defines the attribute style:text-align-source, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:text-align-source, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.756 Section 15.11.3, Direction

- a. *The standard defines the attribute style:direction, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:direction`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.757 Section 15.11.4, Vertical Glyph Orientation

- a. *The standard defines the attribute `style:glyph-orientation-vertical`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `style:glyph-orientation-vertical`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.758 Section 15.11.5, Cell Shadow

- a. *The standard defines the attribute `style:shadow`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:shadow`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.759 Section 15.11.6, Cell Background

- a. *The standard defines the attribute `fo:background-color`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `fo:background-color`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the attribute `style-background-image`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.760 Section 15.11.7, Cell Border

- a. *The standard defines the attribute `fo:border`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".

- Word supports all values for color.
- b. *The standard defines the attribute fo:border-bottom, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- c. *The standard defines the attribute fo:border-left, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- d. *The standard defines the attribute fo:border-right, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- e. *The standard defines the attribute fo:border-top, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2010 and Word 2013.

The string value for this attribute is discussed in detail in section 7.29.3 of the XSL specification. The following summarizes the support for each item in the string:

- Word supports all values of border-width and supports the following values for border-style: "none", "dotted", "dashed", "solid", "double", "inset", and "outset". All other values for border-style map to "solid".
- Word supports all values for color.

- f. *The standard defines the attribute fo:border, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: "groove", "ridge", "inset", and "outset". These styles map to a "solid" border type.

On save Excel maps border length as follows: medium and medium dashed borders map to a 2.0 pt border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- g. *The standard defines the attribute fo:border-bottom, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- h. *The standard defines the attribute fo:border-left, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- i. *The standard defines the attribute fo:border-right, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- j. *The standard defines the attribute fo:border-top, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

2.1.761 Section 15.11.8, Diagonal Lines

- a. *The standard defines the attribute style:diagonal-bl-tr, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:diagonal-bl-tr-widths, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute style:diagonal-tl-br, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute style:diagonal-tl-br-widths, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute style:diagonal-bl-tr, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- f. *The standard defines the attribute `style:diagonal-bl-tr-widths`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `style:diagonal-tl-br`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Excel 2010 and Excel 2013.

On load, when the border width has been numerically specified, the value is mapped to "thin", "medium", or "thick", as appropriate.

Excel does not support the following ODF border styles: groove, ridge, inset, and outset. These styles map to the value of "solid".

On save, Excel maps border length as follows: medium and medium dashed borders map to the value of "2.0 pt" border; thick borders maps to the value "thick", and all other borders map to the value "thin".

On save, Excel maps border types as follows: dotted border types maps to the value "dotted", dashed and medium dashed border types map to the value "dashed", double border types map to the value "double", and all other border types map to the value "solid".

- h. *The standard defines the attribute `style:diagonal-tl-br-widths`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.762 Section 15.11.9, Border Line Width

- a. *The standard defines the attribute `style:border-line-bottom-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `style:border-line-left-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `style:border-line-right-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `style:border-line-top-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- f. *The standard defines the attribute `style:border-line-width`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `style:border-line-width-bottom`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `style:border-line-width-left`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `style:border-line-width-right`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute `style:border-line-width-top`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.763 Section 15.11.10, Padding

- a. *The standard defines the attribute `fo:padding`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- c. *The standard defines the attribute `fo:padding-left`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- d. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- e. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:table-cell-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- f. *The standard defines the attribute `fo:padding`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:table-cell-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute fo:padding-left, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute fo:padding-right, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- j. *The standard defines the attribute fo:padding-top, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.764 Section 15.11.11, Wrap Option

- a. *The standard defines the attribute fo:wrap-option, contained within the element <style:table-cell-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute fo:wrap-option, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.765 Section 15.11.12, Rotation Angle

- a. *The standard defines the attribute style:rotation-angle, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:rotation-angle, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

Excel supports only values within these ranges: 0 - 90 and 270 - 360.

On load, Excel does not ignore values outside of these ranges. On save, Excel does not write the style:rotation-angle attribute if the style:direction attribute is the value "ttb".

2.1.766 Section 15.11.13, Rotation Align

- a. *The standard defines the attribute style:rotation-align, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:rotation-align, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.767 Section 15.11.14, Cell Protect

- a. *The standard defines the attribute style:cell-protect, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:cell-protect, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.768 Section 15.11.15, Print Content

- a. *The standard defines the attribute style:print-content, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:print-content, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.769 Section 15.11.16, Decimal places

- a. *The standard defines the attribute style:decimal-places, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:decimal-places, contained within the element <style:table-cell-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.770 Section 15.11.17, Repeat Content

- a. *The standard defines the attribute style:repeat-content, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:repeat-content, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

This attribute maps to the fill horizontal alignment property in Excel.

2.1.771 Section 15.11.18, Shrink To Fit

- a. *The standard defines the attribute style:shrink-to-fit, contained within the element <style:table-cell-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:shrink-to-fit, contained within the element <style:table-cell-properties>*

This attribute is supported in Excel 2010 and Excel 2013.

2.1.772 Section 15.12, List-Level Style Properties

- a. *The standard defines the element <style:list-level-properties>*

This element is supported in Word 2010 and Word 2013.

- b. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-bullet>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt.

- c. *The standard defines the attribute fo:height, contained within the element <style:list-level-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- d. *The standard defines the attribute fo:text-align, contained within the element <style:list-level-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- e. *The standard defines the attribute fo:width, contained within the element <style:list-level-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- f. *The standard defines the attribute style:font-name, contained within the element <style:list-level-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- g. *The standard defines the attribute style:vertical-pos, contained within the element <style:list-level-properties>*

This attribute is not supported in Word 2010 or Word 2013.

Word ignores the style:vertical-pos property on load, but writes it out on save.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- h. *The standard defines the attribute style:vertical-rel, contained within the element <style:list-level-properties>*

This attribute is not supported in Word 2010 or Word 2013.

Word ignores the style:vertical-rel property on load, but writes it out on save.

- i. *The standard defines the attribute text:min-label-distance, contained within the element <style:list-level-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt.

- j. *The standard defines the attribute `text:min-label-width`, contained within the element `<style:list-level-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- k. *The standard defines the attribute `text:space-before`, contained within the element `<style:list-level-properties>`*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt.

- l. This is not supported in Excel 2010 or Excel 2013.

- m. *The standard defines the element `<style:list-level-properties>`, contained within the parent element `<text:list-level-style-bullet>`*

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes and for SmartArt and on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

- n. *The standard defines the element `<style:list-level-properties>`, contained within the parent element `<text:list-level-style-image>`*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`.

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- o. *The standard defines the element `<style:list-level-properties>`, contained within the parent element `<text:list-level-style-number>`*

OfficeArt Math in Excel 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in text boxes and shapes.

- p. *The standard defines the attribute fo:height, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- q. *The standard defines the attribute fo:text-align, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- r. *The standard defines the attribute fo:width, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
 - shapes
 - SmartArt
 - chart titles
 - labels
- s. *The standard defines the attribute style:font-name, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- t. *The standard defines the attribute style:vertical-pos, contained within the element <style:list-level-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- u. *The standard defines the attribute `text:min-label-distance`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 does not support this attribute on save for text in text boxes and shapes, and for SmartArt.

- v. *The standard defines the attribute `text:min-label-width`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- w. *The standard defines the attribute `text:space-before`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>.

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, and for SmartArt.

- x. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-bullet>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- y. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-image>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- z. *The standard defines the element <style:list-level-properties>, contained within the parent element <text:list-level-style-number>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

aa. *The standard defines the attribute fo:height, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

bb. *The standard defines the attribute fo:text-align, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

cc. *The standard defines the attribute fo:width, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

dd. *The standard defines the attribute style:font-name, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

ee. *The standard defines the attribute style:vertical-pos, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

ff. *The standard defines the attribute text:min-label-distance, contained within the element <style:list-level-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

gg. *The standard defines the attribute `text:min-label-width`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

hh. *The standard defines the attribute `text:space-before`, contained within the element `<style:list-level-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.773 Section 15.13, Stroke Properties

a. *The standard defines the parent element `<style:graphic-properties>`*

Word 2013 supports this for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>

- <draw:g>
- <draw:frame> containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

On load, a border applied to a text box in a group will be lost in Word.

- b. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.774 Section 15.13.1, Stroke Style

- a. *The standard defines the attribute draw:stroke, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

On save, stroke styles are converted to a solid line when applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:custom-shape>
- <draw:text-box>
- <draw:frame> element containing a <draw:text-box> element

- b. *The standard defines the attribute draw:stroke, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

If the stroke is applied to a <draw:line> or <draw:connector> element with zero width, the stroke style will be lost and will be converted to a solid stroke style on load into Excel.

If an ODS file is saved as XLS format from Excel, the stroke style will be lost and will become a solid line.

- c. *The standard defines the attribute draw:stroke, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

If the stroke is applied to a <draw:line> or <draw:connector> element with zero width, the stroke style will be lost and will be converted to a solid stroke style on load into PowerPoint.

2.1.775 Section 15.13.2, Dash

- a. *The standard defines the attribute draw:stroke-dash, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

Dash styles that cannot be represented are converted to solid lines.

- b. *The standard defines the attribute draw:stroke-dash, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element

- <draw:custom-shape>

Dash styles that cannot be represented are converted to solid lines.

- c. *The standard defines the attribute `draw:stroke-dash`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Dash styles that cannot be represented are converted to solid lines.

2.1.776 Section 15.13.3, Multiple Dashes

- a. *The standard defines the attribute `draw:stroke-dash-names`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:stroke-dash-names`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:stroke-dash-names`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.777 Section 15.13.4, Width

- a. *The standard defines the attribute `svg:stroke-width`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `svg:stroke-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>

- <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
 - <draw:custom-shape>
- c. *The standard defines the attribute `svg:stroke-width`, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.778 Section 15.13.5, Color

- a. *The standard defines the attribute `svg:stroke-color`, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `svg:stroke-color`, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `svg:stroke-color`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.779 Section 15.13.6, Start Marker

- a. *The standard defines the attribute `draw:marker-start`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

- b. *The standard defines the attribute `draw:marker-start`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

- c. *The standard defines the attribute `draw:marker-start`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

2.1.780 Section 15.13.7, End Marker

- a. *The standard defines the attribute `draw:marker-end`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to one of the following elements:

- `<draw:line>`
- `<draw:connector>`
- `<draw:measure>`

- b. *The standard defines the attribute `draw:marker-end`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-end`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

2.1.781 Section 15.13.8, Start Marker Width

- a. *The standard defines the attribute `draw:marker-start-width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- b. *The standard defines the attribute `draw:marker-start-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-start-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

2.1.782 Section 15.13.9, End Marker Width

- a. *The standard defines the attribute `draw:marker-end-width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- b. *The standard defines the attribute `draw:marker-end-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:line>`, `<draw:connector>`, or `<draw:measure>` element.

- c. *The standard defines the attribute `draw:marker-end-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

2.1.783 Section 15.13.10, Start Marker Center

- a. *The standard defines the attribute `draw:marker-start-center`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

- b. *The standard defines the attribute `draw:marker-start-center`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

- c. *The standard defines the attribute `draw:marker-start-center`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

2.1.784 Section 15.13.11, End Marker Center

- a. *The standard defines the attribute `draw:marker-end-center`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

- b. *The standard defines the attribute `draw:marker-end-center`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

- c. *The standard defines the attribute `draw:marker-end-center`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:line>, <draw:connector>, or <draw:measure> element.

2.1.785 Section 15.13.12, Opacity

- a. *The standard defines the attribute `svg:stroke-opacity`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>

- <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
 - <draw:custom-shape>
- b. *The standard defines the attribute `svg:stroke-opacity`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
 - <draw:custom-shape>
- c. *The standard defines the attribute `svg:stroke-opacity`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.786 Section 15.13.13, Line Join

- a. *The standard defines the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the property "bevel", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the property "inherit", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing a <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

Word interprets this enumeration as "miter".

- d. *The standard defines the property "middle", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Word interprets this enumeration as "miter".

- e. *The standard defines the property "miter", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- f. *The standard defines the property "none", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Word interprets this enumeration as "round".

- g. *The standard defines the property "round", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

h. *The standard defines the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

i. *The standard defines the property "bevel", contained within the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

j. *The standard defines the property "inherit", contained within the attribute `draw:stroke-linejoin`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Excel interprets this enumeration as "miter".

- k. *The standard defines the property "middle", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Excel interprets this enumeration as "miter".

- l. *The standard defines the property "miter", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>

- <draw:custom-shape>
- m. *The standard defines the property "none", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

Excel interprets this enumeration as "round".

- n. *The standard defines the property "round", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- o. *The standard defines the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>

- <draw:measure>
 - <draw:g>
 - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
 - <draw:custom-shape>
- p. *The standard defines the property "bevel", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
 - <draw:line>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:connector>
 - <draw:caption>
 - <draw:measure>
 - <draw:g>
 - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
 - <draw:custom-shape>
- q. *The standard defines the property "inherit", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

PowerPoint interprets this enumeration as "miter".

- r. *The standard defines the property "middle", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

PowerPoint interprets this enumeration as "miter".

- s. *The standard defines the property "miter", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- t. *The standard defines the property "none", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to one of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

PowerPoint interprets this enumeration as "round".

- u. *The standard defines the property "round", contained within the attribute draw:stroke-linejoin, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>

- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.787 Section 15.14, Fill Properties

- a. *The standard defines the parent element <style:graphic-properties>*

Word 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.788 Section 15.14.1, Fill Style

- a. *The standard defines the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the property "bitmap", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the property "gradient", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- d. *The standard defines the property "hatch", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- e. *The standard defines the property "none", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- f. *The standard defines the property "solid", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- g. *The standard defines the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- h. *The standard defines the property "bitmap", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- i. *The standard defines the property "gradient", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- j. *The standard defines the property "hatch", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- k. *The standard defines the property "none", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- l. *The standard defines the property "solid", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- m. *The standard defines the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- n. *The standard defines the property "bitmap", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>

- <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- o. *The standard defines the property "gradient", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- p. *The standard defines the property "hatch", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- q. *The standard defines the property "none", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- r. *The standard defines the property "solid", contained within the attribute draw:fill, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.789 Section 15.14.2, Color

- a. *The standard defines the attribute draw:fill-color, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-color, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute draw:fill-color, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.790 Section 15.14.3, Secondary Fill Color

- a. *The standard defines the attribute draw:secondary-fill-color, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:secondary-fill-color, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:secondary-fill-color, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:custom-shape>

2.1.791 Section 15.14.4, Gradient

- a. *The standard defines the attribute `draw:fill-gradient-name`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- b. *The standard defines the attribute `draw:fill-gradient-name`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:fill-gradient-name`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

2.1.792 Section 15.14.5, Gradient Step Count

- a. *The standard defines the attribute `draw:gradient-step-count`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:gradient-step-count`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:gradient-step-count`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.793 Section 15.14.6, Hatch

- a. *The standard defines the attribute `draw:fill-hatch-name`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- b. *The standard defines the attribute `draw:fill-hatch-name`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
 - <draw:polyline>
 - <draw:polygon>
 - <draw:regular-polygon>
 - <draw:path>
 - <draw:circle>
 - <draw:ellipse>
 - <draw:caption>
 - <draw:g>
 - <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
 - <draw:custom-shape>
- c. *The standard defines the attribute `draw:fill-hatch-name`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.794 Section 15.14.7, Solid Hatch

- a. *The standard defines the attribute `draw:fill-hatch-solid`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:fill-hatch-solid`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:fill-hatch-solid`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

2.1.795 Section 15.14.8, Fill Image

- a. *The standard defines the attribute `draw:fill-image-name`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- b. *The standard defines the attribute `draw:fill-image-name`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:fill-image-name`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.796 Section 15.14.9, Fill Image Rendering Style

- a. *The standard defines the attribute `style:repeat`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `style:repeat`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>

- <draw:caption>
 - <draw:g>
 - <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
 - <draw:custom-shape>
- c. *The standard defines the attribute style:repeat, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.797 Section 15.14.10, Fill Image Size

- a. *The standard defines the attribute draw:fill-image-height, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- b. *The standard defines the attribute draw:fill-image-width, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>

- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- c. *The standard defines the attribute draw:fill-image-height, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- d. *The standard defines the attribute draw:fill-image-width, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- e. *The standard defines the attribute draw:fill-image-height, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>

- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

- f. *The standard defines the attribute draw:fill-image-width, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to one of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> element containing a <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

This attribute is not supported when style:repeat="no-repeat".

2.1.798 Section 15.14.11, Fill Image Tile Reference Point

- a. *The standard defines the attribute draw:fill-image-ref-point, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:fill-image-ref-point-x, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>

- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

c. *The standard defines the attribute draw:fill-image-ref-point-y, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

d. *The standard defines the attribute draw:fill-image-ref-point, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

e. *The standard defines the attribute draw:fill-image-ref-point-x, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

f. *The standard defines the attribute draw:fill-image-ref-point-y, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>

- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

g. *The standard defines the attribute `draw:fill-image-ref-point`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

h. *The standard defines the attribute `draw:fill-image-ref-point-x`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

i. *The standard defines the attribute `draw:fill-image-ref-point-y`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>

- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.799 Section 15.14.12, Fill Image Tile Translation

- a. *The standard defines the attribute draw:tile-repeat-offset, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute draw:tile-repeat-offset, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute draw:tile-repeat-offset, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.800 Section 15.14.13, None and Linear Opacity

- a. *The standard defines the attribute `draw:opacity`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- b. *The standard defines the attribute `draw:opacity`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:opacity`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

2.1.801 Section 15.14.14, Gradient Opacity

- a. *The standard defines the attribute `draw:opacity-name`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:opacity-name`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:opacity-name`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.802 Section 15.14.15, Fill Rule

- a. *The standard defines the attribute `svg:fill-rule`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

b. *The standard defines the attribute `svg:fill-rule`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

c. *The standard defines the attribute `svg:fill-rule`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

2.1.803 Section 15.14.16, Symbol color

a. *The standard defines the attribute `draw:symbol-color`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:g>
- <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> element
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:symbol-color`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:symbol-color`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:g>`
- `<draw:frame>` containing `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` element
- `<draw:custom-shape>`

2.1.804 Section 15.15, Text Animation Properties

- a. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.805 Section 15.15.1, Animation

- a. *The standard defines the attribute `text:animation`, contained within the element `<style:graphics-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.806 Section 15.15.2, Animation Direction

- a. *The standard defines the attribute `text:animation-direction`, contained within the element `<style:graphics-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.807 Section 15.15.3, Animation Start Inside

- a. *The standard defines the attribute `text:animation-start-inside`, contained within the element `<style:graphics-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.808 Section 15.15.4, Animation Stop Inside

- a. *The standard defines the attribute `text:animation-stop-inside`, contained within the element `<style:graphics-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.809 Section 15.15.5, Animation Repeat

- a. *The standard defines the attribute `text:animation-repeat`, contained within the element `<style:graphics-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.810 Section 15.15.6, Animation Delay

- a. *The standard defines the attribute `text:animation-delay`, contained within the element `<style:graphics-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.811 Section 15.15.7, Animation Steps

- a. *The standard defines the attribute `text:animation-steps`, contained within the element `<style:graphics-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.812 Section 15.16, Text and Text Alignment Properties

- a. *The standard defines the element `<style:graphic-properties>`*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt

- chart titles
 - labels
- c. *The standard defines the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.813 Section 15.16.1, Auto Grow Width and Height

- a. *The standard defines the attribute draw:auto-grow-height, contained within the element <style:graphic-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute draw:auto-grow-width, contained within the element <style:graphic-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute draw:auto-grow-height, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt

- chart titles
 - labels
- d. *The standard defines the attribute `draw:auto-grow-width`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute `draw:auto-grow-height`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:text-box>`
- `<draw:frame>`
- `<draw:custom-shape>`.

- f. *The standard defines the attribute `draw:auto-grow-width`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`

- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.814 Section 15.16.2, Fit To Size

- a. *The standard defines the attribute draw:fit-to-size, contained within the element <style:graphic-properties>*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute draw:fit-to-size, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute draw:fit-to-size, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.815 Section 15.16.3, Fit To Contour

- a. *The standard defines the attribute `draw:fit-to-contour`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `draw:fit-to-contour`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute `draw:fit-to-contour`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.816 Section 15.16.4, Text Area Vertical Align

- a. *The standard defines the attribute `draw:textarea-vertical-align`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The conversion between ODF anchoring properties ("`draw:textarea-vertical-align`" and "`draw:textarea-horizontal-align`") and OOXML anchoring properties ("`bodyPr anchor`" and "`bodyPr anchorCtr`") is dependent on text direction attributes ("`style:writing-mode`" in ODF and "`bodyPr vert`" in OOXML). On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape.

- b. *The standard defines the attribute `draw:textarea-vertical-align`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. The conversion between ODF anchoring properties (`draw:textarea-vertical-align` and `draw:textarea-horizontal-align`) and OOXML anchoring properties ("`bodyPr anchor`" and "`bodyPr anchorCtr`") is dependent on text direction attributes (`style:writing-mode` in ODF and "`bodyPr vert`" in OOXML). On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape. On read, the reverse is true: ODF anchoring values are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to OOXML relative to the text direction within the text box.

- c. *The standard defines the attribute `draw:textarea-vertical-align`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in <the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

The conversion between ODF anchoring attributes (draw:textarea-vertical-align and draw:textarea-horizontal-align) and PowerPoint anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode attribute in ODF and "bodyPr vert" in PowerPoint). On write, PowerPoint anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape. On read, the reverse is true: ODF anchoring values are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to PowerPoint relative to the text direction within the text box.

2.1.817 Section 15.16.5, Text Area Horizontal Align

- a. *The standard defines the attribute draw:textarea-horizontal-align, contained within the element <style:graphic-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. The conversion between ODF anchoring properties (draw:textarea-vertical-align and draw:textarea-horizontal-align) and OOXML anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode in ODF and "bodyPr vert" in OOXML). On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape.

- b. *The standard defines the attribute draw:textarea-horizontal-align, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels, and on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

The conversion between anchoring properties in the standard ("draw:textarea-vertical-align" and "draw:textarea-horizontal-align") and OOXML anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode in the standard and "bodyPr vert" in OOXML).

On write, OOXML anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to properties in the standard relative to the text box regardless of text direction within the shape.

On read, the reverse is true: anchoring values in the standard are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to OOXML relative to the text direction within the text box.

- c. *The standard defines the attribute draw:textarea-horizontal-align, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

The conversion between ODF anchoring properties (draw:textarea-vertical-align and draw:textarea-horizontal-align) and PowerPoint anchoring properties ("bodyPr anchor" and "bodyPr anchorCtr") is dependent on text direction attributes (style:writing-mode in ODF and "bodyPr vert" in PowerPoint). On write, PowerPoint anchoring properties are evaluated relative to the text direction of the text within the text box (or shape) and then mapped to ODF relative to the text box regardless of text direction within the shape. On read, the reverse is true: ODF anchoring values are evaluated relative to the position of the text box, regardless of text direction, and then are mapped to PowerPoint relative to the text direction within the text box.

2.1.818 Section 15.16.6, Word Wrap

- a. *The standard defines the attribute fo:word-wrap, contained within the element <style:graphic-properties>*

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:word-wrap, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:word-wrap, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.819 Section 15.16.7, List Styles

- a. *The standard defines the element <text:list-style>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <text:list-style>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the element <text:list-style>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.820 Section 15.17, Color Properties

- a. *The standard defines the parent element <style:graphic-properties>*

Word 2013 supports this for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to a <draw:frame> element containing a <draw:image> element.

2.1.821 Section 15.17.1, Color Mode

- a. *The standard defines the attribute draw:color-mode, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the property "greyscale", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the property "mono", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element.

- d. *The standard defines the property "standard", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element.

- e. *The standard defines the property "watermark", contained within the attribute draw:color-mode, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing a <draw:image> element.

- f. *The standard defines the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- g. *The standard defines the property "greyscale", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- Excel 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- h. *The standard defines the property "mono", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- Excel 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- i. *The standard defines the property "standard", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- Excel 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- j. *The standard defines the property "watermark", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- Excel 2013 does not support this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- k. *The standard defines the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- l. *The standard defines the property "greyscale", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- PowerPoint 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- m. *The standard defines the property "mono", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- PowerPoint 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- n. *The standard defines the property "standard", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- PowerPoint 2013 supports this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.
- o. *The standard defines the property "watermark", contained within the attribute `draw:color-mode`, contained within the element `<style:graphic-properties>`*
- PowerPoint 2013 does not support this enum for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

2.1.822 Section 15.17.2, Color Inversion

- a. *The standard defines the attribute `draw:color-inversion`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- b. *The standard defines the attribute `draw:color-inversion`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- c. *The standard defines the attribute `draw:color-inversion`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

2.1.823 Section 15.17.3, Adjust Luminance

- a. *The standard defines the attribute `draw:luminance`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

- b. *The standard defines the attribute `draw:luminance`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

- c. *The standard defines the attribute `draw:luminance`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

2.1.824 Section 15.17.4, Adjust Contrast

- a. *The standard defines the attribute `draw:contrast`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

- b. *The standard defines the attribute `draw:contrast`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

- c. *The standard defines the attribute `draw:contrast`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element. This attribute is loaded but is not saved. The effect of this attribute is flattened into the picture on save.

2.1.825 Section 15.17.5, Adjust Gamma

- a. *The standard defines the attribute `draw:gamma`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- b. *The standard defines the attribute `draw:gamma`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- c. *The standard defines the attribute `draw:gamma`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

2.1.826 Section 15.17.6, Adjust Red

- a. *The standard defines the attribute `draw:red`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- b. *The standard defines the attribute `draw:red`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- c. *The standard defines the attribute `draw:red`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

2.1.827 Section 15.17.7, Adjust Green

- a. *The standard defines the attribute `draw:green`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing a `<draw:image>` element.

- b. *The standard defines the attribute `draw:green`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the attribute draw:green, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

2.1.828 Section 15.17.8, Adjust Blue

- a. *The standard defines the attribute draw:blue, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the attribute draw:blue, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the attribute draw:blue, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

2.1.829 Section 15.17.9, Adjust Opacity

- a. *The standard defines the attribute draw:image-opacity, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- b. *The standard defines the attribute draw:image-opacity, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

- c. *The standard defines the attribute draw:image-opacity, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> element.

2.1.830 Section 15.18, Shadow Properties

- a. *The standard defines the parent element <style:graphic-properties>*

Word 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

b. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

c. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.831 Section 15.18.1, Shadow

a. *The standard defines the attribute draw:shadow, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:shadow`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:shadow`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.832 Section 15.18.2, Offset

- a. *The standard defines the attribute `draw:shadow-offset-x`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute `draw:shadow-offset-y`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute `draw:shadow-offset-x`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- d. *The standard defines the attribute `draw:shadow-offset-y`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

e. *The standard defines the attribute `draw:shadow-offset-x`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

f. *The standard defines the attribute `draw:shadow-offset-y`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.833 Section 15.18.3, Color

- a. *The standard defines the attribute `draw:shadow-color`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
- `<draw:custom-shape>`

- b. *The standard defines the attribute `draw:shadow-color`, contained within the element `<style:graphic-properties>`*

Excel 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`
- `<draw:frame>` containing the elements `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>`
- `<draw:custom-shape>`

- c. *The standard defines the attribute `draw:shadow-color`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- `<draw:rect>`
- `<draw:line>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:connector>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:g>`

- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.834 Section 15.18.4, Opacity

- a. *The standard defines the attribute draw:shadow-opacity, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- b. *The standard defines the attribute draw:shadow-opacity, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

- c. *The standard defines the attribute draw:shadow-opacity, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>

- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame> containing the elements <draw:image>, <draw:text-box>, or <draw:object-ole>
- <draw:custom-shape>

2.1.835 Section 15.19, Connector Properties

- a. *The standard defines the parent element <style:graphic-properties>*

This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element <style:graphic-properties>*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the parent element <style:graphic-properties>*

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.836 Section 15.19.1, Start Line Spacing

- a. *The standard defines the attribute draw:start-line-spacing-horizontal, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute draw:start-line-spacing-vertical, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute draw:start-line-spacing-horizontal, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute draw:start-line-spacing-vertical, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute draw:start-line-spacing-horizontal, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the attribute draw:start-line-spacing-vertical, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.837 Section 15.19.2, End Line Spacing

- a. *The standard defines the attribute draw:end-line-spacing-horizontal, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:end-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `draw:end-line-spacing-horizontal`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `draw:end-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `draw:end-line-spacing-horizontal`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the attribute `draw:end-line-spacing-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.838 Section 15.20, Measure Properties

- a. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.839 Section 15.20.1, Line Distance

- a. *The standard defines the attribute `draw:line-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:line-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:line-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.840 Section 15.20.2, Guide Overhang

- a. *The standard defines the attribute `draw:guide-overhang`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:guide-overhang`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:guide-overhang`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.841 Section 15.20.3, Guide Distance

- a. *The standard defines the attribute `draw:guide-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:guide-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:guide-distance`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.842 Section 15.20.4, Start Guide

- a. *The standard defines the attribute `draw:start-guide`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:start-guide`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:start-guide`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.843 Section 15.20.5, End Guide

- a. *The standard defines the attribute `draw:end-guide`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:end-guide`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:end-guide`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.844 Section 15.20.6, Placing

- a. *The standard defines the attribute `draw:placing`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:placing`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:placing`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.845 Section 15.20.7, Parallel

- a. *The standard defines the attribute `draw:parallel`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:parallel`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:parallel`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.846 Section 15.20.8, Text Alignment

- a. *The standard defines the attribute `draw:measure-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:measure-vertical-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `draw:measure-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `draw:measure-vertical-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `draw:measure-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the attribute `draw:measure-vertical-align`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.847 Section 15.20.9, Unit

- a. *The standard defines the attribute `draw:unit`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:unit`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:unit`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.848 Section 15.20.10, Show Unit

- a. *The standard defines the attribute `draw:show-unit`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:show-unit`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:show-unit`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.849 Section 15.20.11, Decimal Places

- a. *The standard defines the attribute `draw:decimal-places`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:decimal-places`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:decimal-places`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.850 Section 15.21, Caption Properties

- a. *The standard defines the parent element <style:graphic-properties>*
This is not supported in Word 2010 or Word 2013.
- b. *The standard defines the parent element <style:graphic-properties>*
This is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the parent element <style:graphic-properties>*
This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.851 Section 15.21.1, Type

- a. *The standard defines the attribute draw:caption-type, contained within the element <style:graphic-properties>*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute draw:caption-type, contained within the element <style:graphic-properties>*
This attribute is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the attribute draw:caption-type, contained within the element <style:graphic-properties>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.852 Section 15.21.2, Angle Type

- a. *The standard defines the attribute draw:caption-angle-type, contained within the element <style:graphic-properties>*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute draw:caption-angle-type, contained within the element <style:graphic-properties>*
This attribute is not supported in Excel 2010 or Excel 2013.
- c. *The standard defines the attribute draw:caption-angle-type, contained within the element <style:graphic-properties>*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.853 Section 15.21.3, Angle

- a. *The standard defines the attribute draw:caption-angle, contained within the element <style:graphic-properties>*
This attribute is not supported in Word 2010 or Word 2013.
- b. *The standard defines the attribute draw:caption-angle, contained within the element <style:graphic-properties>*
This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:caption-angle`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.854 Section 15.21.4, Gap

- a. *The standard defines the attribute `draw:caption-gap`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:caption-gap`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:caption-gap`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.855 Section 15.21.5, Escape Direction

- a. *The standard defines the attribute `draw:caption-escape-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:caption-escape-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:caption-escape-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.856 Section 15.21.6, Escape

- a. *The standard defines the attribute `draw:caption-escape`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:caption-escape`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:caption-escape`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.857 Section 15.21.7, Line Length

- a. *The standard defines the attribute `draw:caption-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:caption-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:caption-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.858 Section 15.21.8, Fit Line Length

- a. *The standard defines the attribute `draw:caption-fit-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:caption-fit-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `draw:caption-fit-line-length`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.859 Section 15.22, 3D Geometry Properties

- a. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.860 Section 15.22.1, Horizontal Segments

- a. *The standard defines the attribute `dr3d:horizontal-segments`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:horizontal-segments`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:horizontal-segments`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.861 Section 15.22.2, Vertical Segments

- a. *The standard defines the attribute `dr3d:vertical-segments`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:vertical-segments`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:vertical-segments`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.862 Section 15.22.3, Edge Rounding

- a. *The standard defines the attribute `dr3d:edge-rounding`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:edge-rounding`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:edge-rounding`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.863 Section 15.22.4, Edge Rounding Mode

- a. *The standard defines the attribute `dr3d:edge-rounding-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:edge-rounding-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:edge-rounding-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.864 Section 15.22.5, Back Scale

- a. *The standard defines the attribute `dr3d:back-scale`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:back-scale`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:back-scale`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.865 Section 15.22.6, Depth

- a. *The standard defines the attribute `dr3d:depth`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:depth`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:depth`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.866 Section 15.22.7, Backface Culling

- a. *The standard defines the attribute `dr3d:backface-culling`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:backface-culling`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:backface-culling`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.867 Section 15.22.8, End Angle

- a. *The standard defines the attribute `dr3d:end-angle`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:end-angle`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:end-angle`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.868 Section 15.22.9, Close Front

- a. *The standard defines the attribute `dr3d:close-front`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:close-front`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:close-front`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.869 Section 15.22.10, Close Back

- a. *The standard defines the attribute `dr3d:close-back`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:close-back`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:close-back`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.870 Section 15.23, 3D Lighting Properties

- a. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.871 Section 15.23.1, Mode

- a. *The standard defines the attribute `dr3d:lighting-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:lighting-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:lighting-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.872 Section 15.23.2, Normals Kind

- a. *The standard defines the attribute `dr3d:normals-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:normals-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:normals-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.873 Section 15.23.3, Normals Direction

- a. *The standard defines the attribute `dr3d:normals-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:normals-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:normals-direction`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.874 Section 15.24, 3D Texture Properties

- a. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.875 Section 15.24.1, Generation Mode

- a. *The standard defines the attribute `dr3d:texture-generation-mode-x`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:texture-generation-mode-y`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `dr3d:texture-generation-mode-x`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- d. *The standard defines the attribute `dr3d:texture-generation-mode-y`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- e. *The standard defines the attribute `dr3d:texture-generation-mode-x`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the attribute `dr3d:texture-generation-mode-y`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.876 Section 15.24.2, Kind

- a. *The standard defines the attribute `dr3d:texture-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:texture-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:texture-kind`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.877 Section 15.24.3, Filter

- a. *The standard defines the attribute `dr3d:texture-filter`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:texture-filter`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:texture-filter`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.878 Section 15.24.4, Mode

- a. *The standard defines the attribute `dr3d:texture-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:texture-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:texture-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.879 Section 15.25, 3D Material Properties

- a. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.880 Section 15.25.1, Colors

- a. *The standard defines the attribute `dr3d:ambient-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:diffuse-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `dr3d:emissive-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `dr3d:specular-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- e. *The standard defines the attribute `dr3d:ambient-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- f. *The standard defines the attribute `dr3d:diffuse-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- g. *The standard defines the attribute `dr3d:emissive-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- h. *The standard defines the attribute `dr3d:specular-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- i. *The standard defines the attribute `dr3d:ambient-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the attribute `dr3d:diffuse-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- k. *The standard defines the attribute `dr3d:emissive-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the attribute `dr3d:specular-color`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.881 Section 15.25.2, Shininess

- a. *The standard defines the attribute `dr3d:shininess`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:shininess`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:shininess`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.882 Section 15.26, 3D Shadow Properties

- a. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Word 2010 or Word 2013.

- b. *The standard defines the parent element `<style:graphic-properties>`*

This is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the parent element <style:graphic-properties>*

This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.883 Section 15.26.1, Shadow

- a. *The standard defines the attribute `dr3d:shadow`, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `dr3d:shadow`, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute `dr3d:shadow`, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.884 Section 15.27, Frame Formatting Properties

- a. *The standard defines the parent element <style:graphic-properties>*

Word 2013 supports this for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the element <style:graphic-properties>*

OfficeArt Math in Word 2013 supports this element on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the parent element <style:graphic-properties>*

Excel 2013 supports this for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- d. *The standard defines the element <style:graphic-properties>*

This element is supported in Excel 2010 and Excel 2013.

- e. *The standard defines the parent element <style:graphic-properties>*

PowerPoint 2013 supports this for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- f. *The standard defines the element <style:graphic-properties>*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.885 Section 15.27.1, Frame Widths

- a. *The standard defines the attribute `fo:min-width`, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute `style:rel-width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- c. *The standard defines the attribute `svg:width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- d. *The standard defines the attribute `fo:min-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- e. *The standard defines the attribute `style:rel-width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- f. *The standard defines the attribute `svg:width`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- g. *The standard defines the attribute `fo:min-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- h. *The standard defines the attribute `style:rel-width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- i. *The standard defines the attribute `svg:width`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

2.1.886 Section 15.27.2, Frame Heights

- a. *The standard defines the attribute `fo:min-height`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- b. *The standard defines the attribute `style:rel-height`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- c. *The standard defines the attribute `svg:height`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- d. *The standard defines the attribute `fo:min-height`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- e. *The standard defines the attribute `style:rel-height`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- f. *The standard defines the attribute `svg:height`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- g. *The standard defines the attribute `fo:min-height`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- h. *The standard defines the attribute `style:rel-height`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- i. *The standard defines the attribute `svg:height`, contained within the element `<style:graphic-properties>`*

PowerPoint 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

2.1.887 Section 15.27.3, Maximum Width and Height

- a. *The standard defines the attribute `fo:max-height`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- b. *The standard defines the attribute `fo:max-width`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- c. *The standard defines the attribute `fo:max-height`, contained within the element `<style:graphic-properties>`*

Excel 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>`, `<draw:text-box>`, or `<draw:object-ole>` elements.

- d. *The standard defines the attribute fo:max-width, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- e. *The standard defines the attribute fo:max-height, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- f. *The standard defines the attribute fo:max-width, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

2.1.888 Section 15.27.4, Left and Right Margins

- a. *The standard defines the attribute fo:margin-left, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin-right, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute fo:margin-left, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes

- SmartArt
- chart titles
- labels

- d. *The standard defines the attribute fo:margin-right, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute fo:margin-left, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- f. *The standard defines the attribute fo:margin-right, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>

- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.889 Section 15.27.5, Top and Bottom Margins

- a. *The standard defines the attribute fo:margin-bottom, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin-top, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute fo:margin-bottom, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- d. *The standard defines the attribute fo:margin-top, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- e. *The standard defines the attribute fo:margin-bottom, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- f. *The standard defines the attribute fo:margin-top, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>

- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.890 Section 15.27.6, Margins

- a. *The standard defines the attribute fo:margin, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute fo:margin, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the attribute fo:margin, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>

- <draw:custom-shape>

2.1.891 Section 15.27.7, Print Content

- a. *The standard defines the attribute style:print-content, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute style:print-content, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- c. *The standard defines the attribute style:print-content, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

2.1.892 Section 15.27.8, Protect

- a. *The standard defines the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- b. *The standard defines the property "content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- c. *The standard defines the property "content position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- d. *The standard defines the property "content size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- e. *The standard defines the property "none", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- f. *The standard defines the property "position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- g. *The standard defines the property "position content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- h. *The standard defines the property "position size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- i. *The standard defines the property "size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- j. *The standard defines the property "size content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- k. *The standard defines the property "size position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- l. *The standard defines the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- m. *The standard defines the property "content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- n. *The standard defines the property "content position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported when opening the file in Excel, content protection is not supported. After saving from Excel, the value of the style:protect attribute changes to "position size".

- o. *The standard defines the property "content size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported when opening the file in Excel,

content protection is not supported. After saving from Excel, the value of the style:protect attribute changes to "" and size protection is lost.

- p. *The standard defines the property "none", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- q. *The standard defines the property "position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into Excel. After saving from Excel, the value of the style:protect attribute changes to "position size".

- r. *The standard defines the property "position content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported on load into Excel. Content protection is not supported. After saving from Excel, the value of the style:protect attribute changes to "position size".

- s. *The standard defines the property "position size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- t. *The standard defines the property "size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into Excel. After saving from Excel, size protection is lost and the value of the style:protect attribute changes to "".

- u. *The standard defines the property "size content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported when opening the file in Excel, content protection is not supported. After saving from Excel, size protection is lost and the value of the style:protect attribute changes to "".

- v. *The standard defines the property "size position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. After saving from Excel, the value of the style:protect attribute changes to "position size".

- w. *The standard defines the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- x. *The standard defines the property "content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- y. *The standard defines the property "content position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

- z. *The standard defines the property "content size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, size protection is lost and the value of the style:protect attribute changes to "".

- aa. *The standard defines the property "none", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- bb. *The standard defines the property "position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into PowerPoint. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

- cc. *The standard defines the property "position content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Position protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

- dd. *The standard defines the property "position size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- ee. *The standard defines the property "size", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. This property is supported on load into PowerPoint. After saving from PowerPoint, size protection is lost and the value of the style:protect attribute changes to "".

- ff. *The standard defines the property "size content", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. Size protection is supported on load into PowerPoint. Content protection is not supported. After saving from PowerPoint, size protection is lost and the value of the style:protect attribute changes to "".

- gg. *The standard defines the property "size position", contained within the attribute style:protect, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element that contains a <draw:image> element. After saving from PowerPoint, the value of the style:protect attribute changes to "position size".

2.1.893 Section 15.27.9, Horizontal Position

- a. *The standard defines the attribute style:horizontal-pos, contained within the element <style:graphic-properties>*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute svg:x, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

2.1.894 Section 15.27.10, Horizontal Relation

- a. *The standard defines the property "char", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- b. *The standard defines the property "frame", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- c. *The standard defines the property "frame-content", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- d. *The standard defines the property "frame-end-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- e. *The standard defines the property "frame-start-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- f. *The standard defines the property "page", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the property "page-content", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- h. *The standard defines the property "page-end-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- i. *The standard defines the property "page-start-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- j. *The standard defines the property "paragraph", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- k. *The standard defines the property "paragraph-content", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- l. *The standard defines the property "paragraph-end-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

- m. *The standard defines the property "paragraph-start-margin", contained within the attribute style:horizontal-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:horizontal-rel attribute.

2.1.895 Section 15.27.11, Vertical Position

- a. *The standard defines the attribute `style:vertical-pos`, contained within the element `<style:graphic-properties>`*

This attribute is supported in Word 2010 and Word 2013.

- b. *The standard defines the attribute `svg:y`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.896 Section 15.27.12, Vertical Relation

- a. *The standard defines the property "baseline", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the `style:vertical-rel` attribute.

- b. *The standard defines the property "char", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the `style:vertical-rel` attribute.

- c. *The standard defines the property "frame", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the `style:vertical-rel` attribute.

- d. *The standard defines the property "frame-content", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the `style:vertical-rel` attribute.

- e. *The standard defines the property "line", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the `style:vertical-rel` attribute.

- f. *The standard defines the property "page", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the property "page-content", contained within the attribute `style:vertical-rel`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- h. *The standard defines the property "paragraph", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- i. *The standard defines the property "paragraph-content", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

- j. *The standard defines the property "text", contained within the attribute style:vertical-rel, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

On load, Word maps to a default value of "paragraph" for this value of the style:vertical-rel attribute.

2.1.897 Section 15.27.14, Border

- a. *The standard defines the attribute fo:border, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute fo:border-bottom, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- c. *The standard defines the attribute fo:border-left, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- d. *The standard defines the attribute fo:border-right, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- e. *The standard defines the attribute fo:border-top, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- f. *The standard defines the attribute fo:border, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- g. *The standard defines the attribute fo:border-bottom, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- h. *The standard defines the attribute fo:border-left, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- i. *The standard defines the attribute fo:border-right, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- j. *The standard defines the attribute fo:border-top, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- k. *The standard defines the attribute fo:border, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- l. *The standard defines the attribute fo:border-bottom, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- m. *The standard defines the attribute fo:border-left, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. This attribute is supported if the attributes named fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right all have the same value. Otherwise, the attributes are ignored and a default border is applied.

- n. *The standard defines the attribute fo:border-right, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. This attribute is supported if the attributes named fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right all have the same value. Otherwise, the attributes are ignored and a default border is applied.

- o. *The standard defines the attribute fo:border-top, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. Supported if the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

2.1.898 Section 15.27.15, Border Line Width

- a. *The standard defines the attribute style:border-line-width, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- c. *The standard defines the attribute style:border-line-width-left, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- d. *The standard defines the attribute style:border-line-width-right, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- e. *The standard defines the attribute style:border-line-width-top, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> element. Supported if style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right attributes all have the same value. Otherwise, they are ignored and a default border is applied.

- f. *The standard defines the attribute style:border-line-width, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- g. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. This attribute is supported if the attributes named style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- h. *The standard defines the attribute style:border-line-width-left, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

This attribute is supported if the attributes named style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- i. *The standard defines the attribute style:border-line-width-right, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

This attribute is supported if the attributes named style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- j. *The standard defines the attribute style:border-line-width-top, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. This attribute is supported if the elements named <style:border-line-width-top>, <style:border-line-width-bottom>, <style:border-line-width-left>, and <style:border-line-width-right> all have the same value. Otherwise, these elements are ignored and a default border is applied.

- k. *The standard defines the attribute style:border-line-width, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- l. *The standard defines the attribute style:border-line-width-bottom, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> attributes. This attribute is supported if the attributes named style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- m. *The standard defines the attribute style:border-line-width-left, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

This attribute is supported if the attributes named style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- n. *The standard defines the attribute style:border-line-width-right, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

This attribute is supported if the attributes named style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right all have the same value. Otherwise, these attributes are ignored and a default border is applied.

- o. *The standard defines the attribute style:border-line-width-top, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. This attribute is supported if the attributes named style:border-line-width-top, style:border-line-width-bottom, style:border-line-width-left, and style:border-line-width-right all have the same value. Otherwise, these elements are ignored and a default border is applied.

2.1.899 Section 15.27.16, Padding

- a. *The standard defines the attribute fo:padding, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this attribute on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the attribute `fo:padding-bottom`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- c. *The standard defines the attribute `fo:padding-left`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- d. *The standard defines the attribute `fo:padding-right`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- e. *The standard defines the attribute `fo:padding-top`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels.

- f. *The standard defines the attribute `fo:padding`, contained within the element `<style:graphic-properties>`*

OfficeArt Math in Excel 2013 does not support this attribute on load for text in any of the following elements:

- `<draw:rect>`
- `<draw:polyline>`
- `<draw:polygon>`
- `<draw:regular-polygon>`
- `<draw:path>`
- `<draw:circle>`
- `<draw:ellipse>`
- `<draw:caption>`
- `<draw:measure>`
- `<draw:frame>`
- `<draw:text-box>`
- `<draw:custom-shape>`

OfficeArt Math in Excel 2013 does not support this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- g. *The standard defines the attribute fo:padding-bottom, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- h. *The standard defines the attribute fo:padding-left, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- i. *The standard defines the attribute fo:padding-right, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- j. *The standard defines the attribute fo:padding-top, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- k. *The standard defines the attribute fo:padding, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>

- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- l. *The standard defines the attribute fo:padding-bottom, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- m. *The standard defines the attribute fo:padding-left, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

- n. *The standard defines the attribute fo:padding-right, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>

- <draw:measure>
 - <draw:text-box>
 - <draw:frame>
 - <draw:custom-shape>.
- o. *The standard defines the attribute fo:padding-top, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.900 Section 15.27.17, Shadow

- a. *The standard defines the attribute style:shadow, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element that contains one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

The style:shadow attribute is supported only when the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes are all the same value, or when the fo:border attribute is specified.

- b. *The standard defines the attribute style:shadow, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing <draw:image>, <draw:text-box>, or <draw:object-ole> elements. The style:shadow attribute is supported only when the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes are all the same value, or when the fo:border attribute is specified.

- c. *The standard defines the attribute style:shadow, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element that contains one of the following elements:

- <draw:image>
- <draw:text-box>
- <draw:object-ole>

The style:shadow attribute is supported only when the fo:border-top, fo:border-bottom, fo:border-left, and fo:border-right attributes are all the same value, or when the fo:border attribute is specified.

2.1.901 Section 15.27.18, Background

- a. *The standard defines the attribute fo:background-color, contained within the element <style:graphic-properties>*

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- b. *The standard defines the attribute style:background-image, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- c. *The standard defines the attribute fo:background-color, contained within the element <style:graphic-properties>*

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- d. *The standard defines the attribute style:background-image, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- e. *The standard defines the attribute fo:background-color, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

- f. *The standard defines the attribute style:background-image, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:image>, <draw:text-box>, or <draw:object-ole> elements.

2.1.902 Section 15.27.19, Columns

- a. *The standard defines the element <style:columns>, contained within the parent element <style:graphic-properties>*

This element is not supported in Word 2010 or Word 2013.

OfficeArt Math in Word 2013 does not support this element on save for text in SmartArt and chart titles and labels.

- b. *The standard defines the element <style:columns>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in Excel 2013 does not support this element on load for text in any of the following elements:

- <draw:rect>
- <draw:polyline>

- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:frame>
- <draw:text-box>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 does not support this element on save for text in any of the following items:

- text boxes
- shapes
- SmartArt
- chart titles
- labels

- c. *The standard defines the element <style:columns>, contained within the parent element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 does not support this element on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>.

2.1.903 Section 15.27.20, Editable

- a. *The standard defines the attribute style:editable, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute style:editable, contained within the element <style:graphic-properties>*

This attribute is not supported in Excel 2010 or Excel 2013.

- c. *The standard defines the attribute style:editable, contained within the element <style:graphic-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.904 Section 15.27.21, Wrapping

- a. *The standard defines the property "biggest", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- b. *The standard defines the property "dynamic", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- c. *The standard defines the property "left", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- d. *The standard defines the property "none", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- e. *The standard defines the property "parallel", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- f. *The standard defines the property "right", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is supported in Word 2010 and Word 2013.

- g. *The standard defines the property "run-through", contained within the attribute style:wrap, contained within the element <style:graphic-properties>*

This property is not supported in Word 2010 or Word 2013.

2.1.905 Section 15.27.22, Dynamic Wrap Threshold

- a. *The standard defines the attribute style:wrap-dynamic-threshold, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

2.1.906 Section 15.27.23, Paragraph-only Wrapping

- a. *The standard defines the attribute style:number-wrapped-paragraphs, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

2.1.907 Section 15.27.24, Contour Wrapping

- a. *The standard defines the attribute style:wrap-contour, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

2.1.908 Section 15.27.25, Contour Wrapping Mode

- a. *The standard defines the attribute `style:wrap-contour-mode`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.909 Section 15.27.26, Run Through

- a. *The standard defines the property "background", contained within the attribute `style:run-through`, contained within the element `<style:graphic-properties>`*

This property is not supported in Word 2010 or Word 2013.

- b. *The standard defines the property "foreground", contained within the attribute `style:run-through`, contained within the element `<style:graphic-properties>`*

This property is supported in Word 2010 and Word 2013.

2.1.910 Section 15.27.27, Flow with Text

- a. *The standard defines the attribute `style:flow-with-text`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.911 Section 15.27.28, Overflow behavior

- a. *The standard defines the attribute `style:overflow-behavior`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.912 Section 15.27.29, Mirroring

- a. *The standard defines the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this attribute for a style applied to a `<draw:frame>` element containing the `<draw:text-box>` or `<draw:object-ole>` element.

Word 2013 supports this attribute for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- b. *The standard defines the property "horizontal", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- c. *The standard defines the property "horizontal vertical", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 supports this enum for a style applied to a `<draw:frame>` element containing the `<draw:image>` element.

- d. *The standard defines the property "horizontal-on-even", contained within the attribute `style:mirror`, contained within the element `<style:graphic-properties>`*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- e. *The standard defines the property "horizontal-on-even vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- f. *The standard defines the property "horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- g. *The standard defines the property "horizontal-on-odd vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- h. *The standard defines the property "none", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- i. *The standard defines the property "vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- j. *The standard defines the property "vertical horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- k. *The standard defines the property "vertical horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- l. *The standard defines the property "vertical horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- m. *The standard defines the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- n. *The standard defines the property "horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- o. *The standard defines the property "horizontal vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- p. *The standard defines the property "horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- q. *The standard defines the property "horizontal-on-even vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- r. *The standard defines the property "horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- s. *The standard defines the property "horizontal-on-odd vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- t. *The standard defines the property "none", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- u. *The standard defines the property "vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- v. *The standard defines the property "vertical horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- w. *The standard defines the property "vertical horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- x. *The standard defines the property "vertical horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- y. *The standard defines the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> or <draw:object-ole> element.

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing the <draw:image> element.

- z. *The standard defines the property "horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- aa. *The standard defines the property "horizontal vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- bb. *The standard defines the property "horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- cc. *The standard defines the property "horizontal-on-even vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- dd. *The standard defines the property "horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- ee. *The standard defines the property "horizontal-on-odd vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

- ff. *The standard defines the property "none", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- gg. *The standard defines the property "vertical", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- hh. *The standard defines the property "vertical horizontal", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing the <draw:image> element.

- ii. *The standard defines the property "vertical horizontal-on-even", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-even" attribute is not supported.

- jj. *The standard defines the property "vertical horizontal-on-odd", contained within the attribute style:mirror, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> element. The "vertical flip" style is supported, but the "horizontal-on-odd" attribute is not supported.

2.1.913 Section 15.27.30, Clipping

- a. *The standard defines the attribute fo:clip, contained within the element <style:graphic-properties>*

Word 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> element.

Word 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- b. *The standard defines the property "auto", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- c. *The standard defines the property "rect(<top>, <right>, <bottom>, <left>)", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Word 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element. Word only supports lengths for "top", "bottom", "right", and "left" values and does not support 'auto'.

- d. *The standard defines the attribute fo:clip, contained within the element <style:graphic-properties>*

Excel 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> element.

Excel 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> or a <draw:object-ole> element.

- e. *The standard defines the property "auto", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or a <draw:object-ole> element.

- f. *The standard defines the property "rect(<top>, <right>, <bottom>, <left>)", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

Excel 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or a <draw:object-ole> element. Excel only supports lengths for "top", "bottom", "right", and "left" values and does not support "auto".

- g. *The standard defines the attribute fo:clip, contained within the element <style:graphic-properties>*

PowerPoint 2013 does not support this attribute for a style applied to a <draw:frame> element containing the <draw:text-box> element.

PowerPoint 2013 supports this attribute for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- h. *The standard defines the property "auto", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element.

- i. *The standard defines the property "rect(<top>, <right>, <bottom>, <left>)", contained within the attribute fo:clip, contained within the element <style:graphic-properties>*

PowerPoint 2013 supports this enum for a style applied to a <draw:frame> element containing a <draw:image> or <draw:object-ole> element. PowerPoint only supports lengths for the "top", "bottom", "right", and "left" values and does not support "auto".

2.1.914 Section 15.27.31, Wrap Influence on Position

- a. *The standard defines the attribute draw:wrap-influence-on-position, contained within the element <style:graphic-properties>*

This attribute is not supported in Word 2010 or Word 2013.

2.1.915 Section 15.27.32, Writing Mode

- a. *The standard defines the attribute style:writing-mode, contained within the element <style:graphic-properties>*

This attribute is supported in Word 2010 and Word 2013.

OfficeArt Math in Word 2013 supports this attribute on save for text in SmartArt and chart titles and labels. ODF's attribute style:writing-mode under the element <style:graphic-properties> assigned to at the text box or shape level corresponds to the Word body attribute "vert".

On save, style:writing-mode="tb-rl" is written for the Word vert enumerations "vert", "eaVert", and "wordArtVertRtl". All other vert enumerations are written as style:writing-mode="lr-tb".

- b. *The standard defines the attribute style:writing-mode, contained within the element <style:graphic-properties>*

OfficeArt Math in Excel 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

OfficeArt Math in Excel 2013 supports this attribute on save for text in text boxes and shapes, SmartArt, and chart titles and labels. This attribute in the element <style:graphic-properties> assigned at the text box or shape level corresponds to the attribute vert in Excel. On load, the values "tb-rl" and "tb" of this attribute are converted to the value of "eaVert" of the vert attribute in Excel. All other values of this attribute are converted to the value of "horz" of the vert attribute in Excel. On save, Excel converts the values "vert", "eaVert", and "wordArtVertRtl" of the vert attribute to the value "tb-rl" of this attribute. All other values of the vert attribute are written as the value "lr-tb".

- c. *The standard defines the attribute style:writing-mode, contained within the element <style:graphic-properties>*

OfficeArt Math in PowerPoint 2013 supports this attribute on load for text in the following elements:

- <draw:rect>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:caption>
- <draw:measure>
- <draw:text-box>
- <draw:frame>
- <draw:custom-shape>

This attribute in the element <style:graphic-properties> assigned at the text box or shape level corresponds to the body attribute vert in PowerPoint.

On load, the values "tb-rl" and "tb" of this attribute are converted to the value "eaVert" of the body attribute vert in PowerPoint. All other values of this attribute are converted to the value "horz" of the body attribute vert in PowerPoint.

On save, PowerPoint converts the values "vert", "eaVert", and "wordArtVertRtl" of the body attribute vert to the value "tb-rl" of this attribute. All other values of the body attribute vert are written as the value "lr-tb".

2.1.916 Section 15.28, Floating Frame Formatting Properties

- a. This is not supported in Excel 2010 or Excel 2013.
- b. *The standard defines the attribute `draw:display-border`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- c. *The standard defines the attribute `draw:display-scrollbar`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- d. *The standard defines the attribute `draw:margin-horizontal`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- e. *The standard defines the attribute `draw:margin-vertical`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- f. *The standard defines the attribute `draw:ole-draw-aspect`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- g. *The standard defines the attribute `draw:visible-area-height`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- h. *The standard defines the attribute `draw:visible-area-left`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- i. *The standard defines the attribute `draw:visible-area-top`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.
- j. *The standard defines the attribute `draw:visible-area-width`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.917 Section 15.28.1, Display Scrollbar

- a. *The standard defines the attribute `draw:display-scrollbar`, contained within the element `<style:graphic-properties>`*
This attribute is not supported in Word 2010 or Word 2013.

2.1.918 Section 15.28.2, Display Border

- a. *The standard defines the attribute `draw:display-border`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.919 Section 15.28.3, Margins

- a. *The standard defines the attribute `draw-margin-horizontal`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw-margin-vertical`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.920 Section 15.28.4, Object Formatting Properties

- a. This is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.

2.1.921 Section 15.28.5, Visible Area

- a. *The standard defines the attribute `draw:visible-area-height`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- b. *The standard defines the attribute `draw:visible-area-left`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- c. *The standard defines the attribute `draw:visible-area-top`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

- d. *The standard defines the attribute `draw:visible-area-width`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.922 Section 15.28.6, Draw Aspect

- a. *The standard defines the attribute `draw:ole-draw-aspect`, contained within the element `<style:graphic-properties>`*

This attribute is not supported in Word 2010 or Word 2013.

2.1.923 Section 15.29, Chart Formatting Properties

- a. *The standard defines the element `<style:chart-properties>`, contained within the parent element `<style-chart-properties>`*

This element is supported in Excel 2010 and Excel 2013.

2.1.924 Section 15.30.3, Chart Symbol

- a. *The standard defines the attribute `xlink:href`, contained within the element `<chart:symbol-image>`, contained within the parent element `<style-chart-properties-attlist>`*

This attribute is not supported in Excel 2010 or Excel 2013.

2.1.925 Section 15.31, Chart Axes Properties

- a. This is supported in Excel 2010 and Excel 2013.

2.1.926 Section 15.32, Common Chart Properties

- a. This is supported in Excel 2010 and Excel 2013.

2.1.927 Section 15.33, Statistical Properties

- a. This is supported in Excel 2010 and Excel 2013.

2.1.928 Section 15.34, Plot Area Properties

- a. This is not supported in Excel 2010 or Excel 2013.

2.1.929 Section 15.35, Regression Curve Properties

- a. This is supported in Excel 2010 and Excel 2013.

2.1.930 Section 15.36, Presentation Page Attributes

- a. *The standard defines the element `<style:drawing-page-properties>`*

This element is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.931 Section 15.36.1, Transition Type

- a. *The standard defines the property "automatic", contained within the attribute `presentation:transition-type`, contained within the element `<style:drawing-page-properties>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

On load, PowerPoint sets the manual value as well, permitting slides to be advanced manually in an automated presentation.

- b. *The standard defines the property "manual", contained within the attribute `presentation:transition-type`, contained within the element `<style:drawing-page-properties>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the property "semi-automatic", contained within the attribute `presentation:transition-type`, contained within the element `<style:drawing-page-properties>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

PowerPoint treats semi-automatic the same way as manual.

2.1.932 Section 15.36.2, Transition Style

- a. *The standard defines the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

- b. *The standard defines the property "clockwise", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- c. *The standard defines the property "close", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- d. *The standard defines the property "close-horizontal", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- e. *The standard defines the property "close-vertical", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- f. *The standard defines the property "counterclockwise", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- g. *The standard defines the property "dissolve", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- h. *The standard defines the property "fade-from-bottom", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- i. *The standard defines the property "fade-from-center", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the property "fade-from-left", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- k. *The standard defines the property "fade-from-lowerleft", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the property "fade-from-lowerright", contained within the attribute `presentation:transition-style`, contained within the element `<style:drawing-page-properties>`*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the property "fade-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- n. *The standard defines the property "fade-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- o. *The standard defines the property "fade-from-upperleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- p. *The standard defines the property "fade-from-upperright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- q. *The standard defines the property "fade-to-center", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- r. *The standard defines the property "fly-away", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- s. *The standard defines the property "horizontal-checkerboard", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- t. *The standard defines the property "horizontal-lines", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is supported in PowerPoint 2010 and PowerPoint 2013.
- u. *The standard defines the property "horizontal-stripes", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- v. *The standard defines the property "interlocking-horizontal-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- w. *The standard defines the property "interlocking-horizontal-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- x. *The standard defines the property "interlocking-vertical-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- y. *The standard defines the property "interlocking-vertical-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- z. *The standard defines the property "melt", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- aa. *The standard defines the property "move-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- bb. *The standard defines the property "move-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- cc. *The standard defines the property "move-from-lowerleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- dd. *The standard defines the property "move-from-lowerright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ee. *The standard defines the property "move-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ff. *The standard defines the property "move-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- gg. *The standard defines the property "move-from-upperleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- hh. *The standard defines the property "move-from-upperright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ii. *The standard defines the property "none", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- jj. *The standard defines the property "open", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- kk. *The standard defines the property "open-horizontal", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

- ll. *The standard defines the property "open-vertical", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is supported in PowerPoint 2010 and PowerPoint 2013.
- mm. *The standard defines the property "random", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is supported in PowerPoint 2010 and PowerPoint 2013.
- nn. *The standard defines the property "roll-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is supported in PowerPoint 2010 and PowerPoint 2013.
- oo. *The standard defines the property "roll-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is supported in PowerPoint 2010 and PowerPoint 2013.
- pp. *The standard defines the property "roll-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is supported in PowerPoint 2010 and PowerPoint 2013.
- qq. *The standard defines the property "roll-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is supported in PowerPoint 2010 and PowerPoint 2013.
- rr. *The standard defines the property "spiralin-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- ss. *The standard defines the property "spiralin-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- tt. *The standard defines the property "spiralout-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- uu. *The standard defines the property "spiralout-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- vv. *The standard defines the property "stretch-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- ww. *The standard defines the property "stretch-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*
- This property is not supported in PowerPoint 2010 or PowerPoint 2013.
- xx. *The standard defines the property "stretch-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

yy. *The standard defines the property "stretch-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

zz. *The standard defines the property "uncover-to-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

aaa. *The standard defines the property "uncover-to-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

bbb. *The standard defines the property "uncover-to-lowerleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

ccc. *The standard defines the property "uncover-to-lowerright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

ddd. *The standard defines the property "uncover-to-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

eee. *The standard defines the property "uncover-to-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

fff. *The standard defines the property "uncover-to-upperleft", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

ggg. *The standard defines the property "uncover-to-upperright", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

hhh. *The standard defines the property "vertical-checkerboard", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

iii. *The standard defines the property "vertical-lines", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

jjj. *The standard defines the property "vertical-stripes", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

kkk. *The standard defines the property "wavyline-from-bottom", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

lll. *The standard defines the property "wavyline-from-left", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

mmm. *The standard defines the property "wavyline-from-right", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

nnn. *The standard defines the property "wavyline-from-top", contained within the attribute presentation:transition-style, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.933 Section 15.36.3, Transition Speed

a. *The standard defines the attribute presentation:transition-speed, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

b. *The standard defines the property "fast", contained within the attribute presentation:transition-speed, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

c. *The standard defines the property "medium", contained within the attribute presentation:transition-speed, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

The default value for the transition speed is "medium".

d. *The standard defines the property "slow", contained within the attribute presentation:transition-speed, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.934 Section 15.36.4, Transition Type or Family

a. *The standard defines the attribute smil:type, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

In PowerPoint, if a slide has a transition that is not found in the ODF or SMIL spec, it will be saved with a fade transition, that is, smil:type="fade".

b. *The standard defines the property "arrowHeadWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

c. *The standard defines the property "barnDoorWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports BarnDoorWipe subtypes "vertical" and "horizontal" in forward and reverse directions.

- d. *The standard defines the property "barnVeeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- e. *The standard defines the property "barnZigZagWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- f. *The standard defines the property "barWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports BarWipe subtypes "topToBottom" and "leftToRight" in forward and reverse directions. All other subtype/direction combinations map to "topToBottom" in forward direction.

- g. *The standard defines the property "bowTieWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- h. *The standard defines the property "boxSnakesWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- i. *The standard defines the property "boxWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- j. *The standard defines the property "clockWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint only supports the clockwiseTwelve subtype in the forward direction. All other subtype/direction combinations are mapped to this one.

- k. *The standard defines the property "diagonalWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- l. *The standard defines the property "doubleFanWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- m. *The standard defines the property "doubleSweepWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- n. *The standard defines the property "ellipseWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint only supports the circular ellipseWipe subtype in the forward direction. All other subtype/direction combinations are mapped to this one.

- o. *The standard defines the property "eyeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- p. *The standard defines the property "fade", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports crossfade and fadeFromColor. All others map to "crossfade".

- q. *The standard defines the property "fanWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint only supports the centerTop fanWipe in the forward direction. All other subtype/direction combinations are mapped to this one.

- r. *The standard defines the property "fourBoxWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- s. *The standard defines the property "hexagonWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- t. *The standard defines the property "irisWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports the "rectangle" irisWipe subtype in both the forward and reverse directions. The "diamond" irisWipe subtype is only supported in the forward direction. All other subtype/direction combinations map to "rectangle" in the forward direction.

- u. *The standard defines the property "miscDiagonalWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- v. *The standard defines the property "miscShapeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- w. *The standard defines the property "parallelSnakesWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- x. *The standard defines the property "pentagonWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- y. *The standard defines the property "pinWheelWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint makes the following mappings: pinWheelWipe subtypes "twoBladeVertical" and "twoBladeHorizontal" (in any direction) both map to "twoBladeVertical" forward. pinWheelWipe subtype "fourBlade" (in any direction) maps to "fourBlade" forward. All other subtypes map to the clockWipe transition.

- z. *The standard defines the property "pushWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports pushWipes subtypes "fromTop", "fromBottom", "fromLeft" and fromRight" in the forward direction. Other subtypes and reverse pushWipes are mapped to "fromLeft" pushWipes in the forward direction.

- aa. *The standard defines the property "roundRectWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- bb. *The standard defines the property "saloonDoorWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- cc. *The standard defines the property "singleSweepWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- dd. *The standard defines the property "slideWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint supports slideWipe subtypes "fromTop", "fromBottom", "fromLeft" and fromRight" in forward and reverse directions. All other slideWipe subtypes are mapped to "fromLeft" in forward or reverse direction.

- ee. *The standard defines the property "snakeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ff. *The standard defines the property "spiralWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- gg. *The standard defines the property "starWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is supported in PowerPoint 2010 and PowerPoint 2013.

PowerPoint only supports the four-point starWipe in the forward direction. All other subtype/direction combinations are mapped to this one.

- hh. *The standard defines the property "triangleWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ii. *The standard defines the property "veeWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- jj. *The standard defines the property "waterfallWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- kk. *The standard defines the property "windshieldWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

- ll. *The standard defines the property "zigZagWipe", contained within the attribute smil:type, contained within the element <style:drawing-page-properties>*

This property is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.935 Section 15.36.5, Transition Subtype

- a. *The standard defines the attribute smil:subtype, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.936 Section 15.36.6, Transition Direction

- a. *The standard defines the attribute smil:direction, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.937 Section 15.36.7, Fade Color

- a. *The standard defines the attribute smil:fadeColor, contained within the element <style:drawing-page-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

The fadeColor can only be black.

2.1.938 Section 15.36.8, Page Duration

- a. *The standard defines the attribute presentation:duration, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.939 Section 15.36.9, Page Visibility

- a. *The standard defines the attribute presentation:visibility, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.940 Section 15.36.10, Sound

- a. *The standard defines the attribute presentation:sound, contained within the element <style:drawing-page-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.941 Section 15.36.11, Background Size

- a. *The standard defines the attribute draw:background-size, contained within the element <style:drawing-page-properties>*

This attribute is not supported in PowerPoint 2010 or PowerPoint 2013.

On load, PowerPoint writes this attribute as "border" On load PowerPoint ignores this attribute.

2.1.942 Section 15.36.12, Background Objects Visible

- a. *The standard defines the attribute presentation:background-objects-visible, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.943 Section 15.36.13, Background Visible

- a. *The standard defines the attribute presentation:background-visible, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.944 Section 15.36.14, Display Header

- a. *The standard defines the attribute presentation:display-header, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, this attribute is read to determine whether to display the header. It is not written on save.

2.1.945 Section 15.36.15, Display Footer

- a. *The standard defines the attribute presentation:display-footer, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, this attribute is read to determine whether to display the footer. It is not written on save.

2.1.946 Section 15.36.16, Display Page Number

- a. *The standard defines the attribute presentation:display-page-number, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, this attribute is read to determine whether to display the page number. It is not written on save.

2.1.947 Section 15.36.17, Display Date And Time

- a. *The standard defines the attribute presentation:display-date-time, contained within the element <style:drawing-page-properties>*

This attribute is supported in PowerPoint 2010 and PowerPoint 2013.

On load, this attribute is read to determine whether to display the date and time. It is not written on save.

2.1.948 Section 16, Data Types and Schema Definitions

- a. This is supported in Word 2010 and Word 2013.

This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

This is supported in Excel 2010 and Excel 2013.

This is supported in Excel 2010 and Excel 2013.

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.949 Section 16.1, Data Types

- a. This is supported in Word 2010 and Word 2013.

This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

This is supported in Excel 2010 and Excel 2013.

- c. *The standard defines the element <NCName>*

This element is supported in Excel 2010 and Excel 2013.

- d. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.950 Section 16.2, Other Definitions

- a. This is not supported in Word 2010 or Word 2013.

No custom attributes or elements are saved. Unknown elements and attributes encountered on load are ignored, and therefore lost, when saving from Word.

This is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

No custom attributes or elements are saved. Unknown elements and attributes encountered on load are ignored, and therefore lost, when saving from Excel.

This is not supported in Excel 2010 or Excel 2013.

- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

No custom attributes or elements are saved. Unknown elements and attributes encountered on load are ignored, and therefore lost when saving from PowerPoint.

2.1.951 Section 16.3, Relax-NG Schema Suffix

- a. This is supported in Word 2010 and Word 2013.

This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

This is supported in Excel 2010 and Excel 2013.

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.952 Section 17, Packages

- a. This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.953 Section 17.1, Introduction

- a. This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.954 Section 17.2, Zip File Structure

- a. This is supported in Word 2010 and Word 2013.

- b. This is supported in Excel 2010 and Excel 2013.

- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.955 Section 17.3, Encryption

- a. This is not supported in Word 2010 or Word 2013.

- b. This is not supported in Excel 2010 or Excel 2013.

- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.956 Section 17.4, MIME Type Stream

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.957 Section 17.5, Usage of IRIs Within Packages

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.958 Section 17.6, Preview Image

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.959 Section 17.7, Manifest File

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.960 Section 17.7.1, Relax-NG Schema

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.961 Section 17.7.2, Manifest Root Element

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.962 Section 17.7.3, File Entry

- a. This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.963 Section 17.7.4, Encryption Data

- a. This is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.964 Section 17.7.5, Algorithm

- a. This is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.965 Section 17.7.6, Key Derivation

- a. This is not supported in Word 2010 or Word 2013.
- b. This is not supported in Excel 2010 or Excel 2013.
- c. This is not supported in PowerPoint 2010 or PowerPoint 2013.

2.1.966 Section 17.7.7, Relax-NG Schema Suffix

- a. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.967 Section Appendix E, Accessibility Guidelines (Non Normative)

- a. This is supported in Word 2010 and Word 2013.
This is supported in Word 2010 and Word 2013.
- b. This is supported in Excel 2010 and Excel 2013.
This is supported in Excel 2010 and Excel 2013.
- c. This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.968 Section Appendix E.1, Title, Description and Caption of Graphical Elements

- a.
 1. The <svg:title> element is not supported.
 2. The draw:caption-id attribute is not supported because Word does not treat "caption text" differently from other paragraph text via any special association.
 3. The <svg:desc> element is supported and holds the alternative text for the image.

Word 2013 supports this for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>

- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

b. Excel 2013 supports this for the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

c. PowerPoint 2013 supports this for any of the following elements:

- <draw:rect>
- <draw:line>
- <draw:polyline>
- <draw:polygon>
- <draw:regular-polygon>
- <draw:path>
- <draw:circle>
- <draw:ellipse>
- <draw:connector>
- <draw:caption>
- <draw:measure>
- <draw:g>
- <draw:frame>
- <draw:custom-shape>

2.1.969 Section Appendix E.2, Hyperlink Titles

a.

1. The alt-text of a hyperlink is mapped to the office:title attribute of the <text:a> element.
2. The element <draw:a> is not supported.

This is supported in Word 2010 and Word 2013.

b. Excel 2013 does not support this for draw:a.

This is supported in Excel 2010 and Excel 2013.

c. PowerPoint 2013 does not support this for <draw:a> element.

This is supported in PowerPoint 2010 and PowerPoint 2013.

2.1.970 Section Appendix E.4, Further Guidelines

- a. Implementer notes have been added to the relevant sections in this document to address any accessibility issues, in accordance with the Accessibility Guidelines documentation.
- b. This is supported in PowerPoint 2010 and PowerPoint 2013.

Implementer notes have been added to the relevant sections in this document to address any accessibility issues, per the Accessibility Guidelines documentation.

3 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
1.3 Microsoft Implementations	Updated for Office 2016.	Y	Content update.
2.1 Normative Variations	Updated product names throughout this section.	Y	Content update.
2.1.466 Section 12.5 (MathML 2.0 Section 3.2.5), Operator, Fence, Separator or Accent (mo)	Clarified the support for the separator attribute of the mo element.	Y	Content update.
2.1.899 Section 15.27.16, Padding	Clarified the support for the fo:padding-bottom attribute of the style:graphic-properties element.	Y	Content update.

4 Index

3

[3D Geometry Properties](#) 855
[3D Lighting Properties](#) 858
[3D Material Properties](#) 861
[3D Shadow Properties](#) 862
[3D Shapes](#) 236
[3D Texture Properties](#) 859

A

[Accessibility Guidelines \(Non Normative\)](#) 915
Accessing glyphs for characters from MathML
(mglyph) ([section 2.1.470](#) 341, [section 2.1.471](#)
346)
[Action](#) 270
[Adjust Blue](#) 841
[Adjust Contrast](#) 839
[Adjust Gamma](#) 840
[Adjust Green](#) 840
[Adjust Luminance](#) 839
[Adjust Opacity](#) 841
[Adjust Red](#) 840
[Adjust Space Around Content \(mpadded\)](#) 358
[Adornments](#) 454
[Advanced Table Cells](#) 153
[Advanced Table Model](#) 147
[Advanced Tables](#) 151
[Algorithm](#) 915
[Allow Deletes](#) 270
[Allow Inserts](#) 271
[Allow Updates](#) 271
[Alphabetical Index](#) 131
[Alphabetical Index Entry Template](#) 132
[Alphabetical Index Mark](#) 126
[Alphabetical Index Source](#) 131
[Angle](#) 853
[Angle Type](#) 853
[Animate](#) 399
[Animate Color](#) 399
[Animate Motion](#) 399
[Animate Transform](#) 399
[Animation](#) 827
[Animation Delay](#) 828
[Animation Direction](#) 827
[Animation Function Attributes](#) 403
[Animation Model Attributes](#) 403
[Animation Repeat](#) 828
[Animation Start Inside](#) 827
[Animation Steps](#) 828
[Animation Stop Inside](#) 828
[Animation Target Attributes](#) 403
[Animation Timing](#) 404
[Animation Timing Attributes](#) 404
[Annotation](#) 284
[Applet](#) 233
[Application Settings](#) 29
[Apply Filter](#) 271
[Attributed Text](#) 70
[Audio](#) 406
[Author Fields](#) 99

[Auto Grow Width and Height](#) 829
[Auto Mark File](#) 132
[Automatic Reload](#) 37
[Automatic Text Indent](#) 712
[Automatic Writing Mode](#) 742
[Axis](#) 267

B

[Back Scale](#) 857
[Backface Culling](#) 857
Background ([section 2.1.598](#) 581, [section 2.1.623](#)
594, [section 2.1.901](#) 888)
[Background Objects Visible](#) 911
[Background Size](#) 911
[Background Transparency](#) 744
[Background Visible](#) 911
[Base Settings](#) 29
[Basic Table Model](#) 136
[Basic Text Content](#) 63
[Bibliography](#) 133
[Bibliography Configuration](#) 490
[Bibliography Entry Template](#) 133
[Bibliography Index Mark](#) 128
[Bibliography Index Source](#) 133
[Bibliography Information](#) 135
[Bind Action to Sub-Expression \(maction\)](#) 395
[Bind to XForms](#) 278
[Body Element and Document Types](#) 27
[Bookmarks](#) 79
[Bookmarks and References](#) 79
[Boolean Style](#) 476
Border ([section 2.1.594](#) 576, [section 2.1.620](#) 591,
[section 2.1.699](#) 719, [section 2.1.897](#) 878)
Border Line Width ([section 2.1.595](#) 578, [section](#)
[2.1.621](#) 592, [section 2.1.700](#) 724, [section](#)
[2.1.762](#) 775, [section 2.1.898](#) 880)
[Border Model Property](#) 765
Break Before and Break After ([section 2.1.696](#) 715,
[section 2.1.735](#) 763, [section 2.1.746](#) 767,
[section 2.1.751](#) 769)
[Bullet Level Style](#) 499
[Button](#) 276
[Button Type](#) 278

C

[Calculation Settings](#) 155
[Caption](#) 198
[Caption Properties](#) 853
[Categories](#) 268
[Cell Annotation](#) 154
[Cell Background](#) 771
[Cell Border](#) 771
[Cell Protect](#) 778
[Cell Shadow](#) 771
[Change Info](#) 60
[Change Marks](#) 60
Change Tracking ([section 2.1.65](#) 59, [section 3](#) 918)
[Change Tracking and Change Marks](#) 90
[Change Tracking Metadata](#) 310

[Changed Regions](#) 60
[Chapter Fields](#) 99
[Chapter Information](#) 134
[Chart](#) 265
[Chart Axes Properties](#) 900
[Chart Content](#) 265
[Chart Documents](#) 28
[Chart Formatting Properties](#) 899
[Chart Symbol](#) 900
[Check Box](#) 276
[Circle](#) 192
[Client Side Image Maps](#) 236
[Clipping](#) 895
[Close Back](#) 858
[Close Front](#) 858
Color ([section 2.1.629](#) 598, [section 2.1.778](#) 793, [section 2.1.789](#) 811, [section 2.1.833](#) 846)
[Color Inversion](#) 839
[Color Mode](#) 837
[Color Properties](#) 837
[Colors](#) 861
[Column Description](#) 148
[Column Formatting Properties](#) 766
[Column Groups](#) 150
[Column Separator](#) 755
[Column Specification](#) 753
[Column Width](#) 766
Columns ([section 2.1.599](#) 581, [section 2.1.721](#) 752, [section 2.1.902](#) 888)
[Combo Box](#) 275
Command ([section 2.1.383](#) 271, [section 2.1.517](#) 407)
[Command Type](#) 271
[Common Animation Attributes](#) 403
[Common Characteristics of Field Elements](#) 92
[Common Chart Properties](#) 900
[Common Content](#) 284
[Common Control Attributes](#) 278
[Common Data Style Attributes](#) 478
[Common Data Style Child Element Attributes](#) 479
[Common Data Style Elements](#) 477
[Common Drawing Shape Attributes](#) 202
[Common Drawing Shape Content](#) 221
[Common Field Attributes](#) 121
[Common Form and Control Attributes](#) 277
[Common List-Level Style Attributes](#) 493
[Common Paragraph Elements Attributes](#) 46
[Common Presentation Shape Attributes](#) 256
[Common Shape Attribute Groups](#) 221
[Common Shape Attributes for Text and Spreadsheet Documents](#) 220
[Complex Formatting Properties](#) 568
[Conditional Text Fields](#) 117
[Conformance Statements](#) 24
[Connection Resource](#) 273
[Connector](#) 195
[Connector Properties](#) 848
[Consolidation](#) 182
[Container for DDE Connection Declarations](#) 398
[Contour](#) 234
[Contour Wrapping](#) 890
[Contour Wrapping Mode](#) 891
[Control](#) 200
[Control ID](#) 278
[Control Implementation](#) 278

[Controls](#) 274
[Country](#) 642
Creation Date and Time ([section 2.1.36](#) 36, [section 2.1.452](#) 287)
[Creation Date and Time String](#) 288
Creator ([section 2.1.34](#) 35, [section 2.1.451](#) 287)
[CSS2/SVG Font Descriptors](#) 445
[Cube](#) 236
[Currency Style](#) 460
[Current Selected](#) 278
[Cursor Position Setting](#) 30
[Custom Metadata](#) 40
[Custom Shape](#) 237

D

[Dash](#) 790
[Data Pilot Display Info](#) 174
[Data Pilot Field](#) 169
[Data Pilot Field Reference](#) 176
[Data Pilot Group](#) 182
[Data Pilot Group Member](#) 182
[Data Pilot Groups](#) 178
[Data Pilot Layout Info](#) 175
[Data Pilot Level](#) 171
[Data Pilot Member](#) 173
[Data Pilot Members](#) 173
[Data Pilot Sort Info](#) 174
[Data Pilot Subtotal](#) 172
[Data Pilot Subtotals](#) 172
[Data Pilot Table](#) 166
[Data Pilot Tables](#) 166
[Data Point](#) 268
[Data Source](#) 272
[Data Styles](#) 458
[Data Types](#) 912
[Data Types and Schema Definitions](#) 912
[Database Binding Attributes](#) 282
[Database Field Data Source](#) 110
[Database Fields](#) 110
[Database Range](#) 160
[Database Ranges](#) 159
[Database Source Query](#) 162
[Database Source SQL](#) 161
[Database Source Table](#) 162
[Date And Time](#) 275
[Date and Time Field](#) 262
[Date and Time field declaration](#) 263
[Date Fields](#) 92
[Date Style](#) 462
[DDE Connection Fields](#) 120
[DDE Connections](#) 397
[DDE Links](#) 183
[DDE Source](#) 59
Decimal places ([section 2.1.769](#) 778, [section 2.1.849](#) 852)
[Declaring DDE Connections for Tables](#) 398
[Declaring DDE Connections for Text Fields](#) 398
[Declaring Sequence Variables](#) 103
[Declaring Simple Variables](#) 101
[Declaring User Variables](#) 102
[Default Styles](#) 428
[Deletion](#) 60
[Depth](#) 857
Description ([section 2.1.30](#) 34, [section 2.1.157](#) 123)

[Detail Fields](#) 272
[Detective](#) 154
[Detective Operation](#) 154
[Diagonal Lines](#) 774
[Dim](#) 257
[Direction](#) 770
[Disabled](#) 279
Display ([section 2.1.158](#) 123, [section 2.1.742](#) 766)
[Display Border](#) 898
[Display Current Database and Table](#) 116
[Display Date And Time](#) 912
[Display Footer](#) 911
[Display Header](#) 911
[Display Page Number](#) 912
[Display Scrollbar](#) 898
[Displaying Database Content](#) 115
[Displaying Simple Variables](#) 102
[Displaying the Row Number](#) 116
[Displaying User Variables](#) 102
[Document Creation Date](#) 104
[Document Creation Time](#) 104
[Document Dependent SMIL Animation Attribute Values](#) 257
[Document Description](#) 105
[Document Edit Duration](#) 107
[Document Fields](#) 92
[Document Keywords](#) 107
[Document Metadata](#) 27
[Document Modification Date](#) 108
[Document Modification Time](#) 107
[Document Modified By](#) 108
[Document Protection](#) 155
[Document Revision Number](#) 107
[Document Root Attributes](#) 25
[Document Root Element Content Models](#) 24
[Document Statistics](#) 38
[Document Statistics Fields](#) 108
[Document Structure](#) 24
[Document Subject](#) 106
[Document Template](#) 37
[Document Template Name Fields](#) 100
[Document Title](#) 106
[Domain](#) 267
[Don't Balance Text Columns](#) 758
[Draw Aspect](#) 899
[Drawing Documents](#) 28
[Drawing Page Style](#) 512
[Drawing Pages](#) 184
[Drawing Shapes](#) 185
[Drop Caps](#) 706
[Dropdown](#) 279
[Dynamic Spacing](#) 594
[Dynamic Wrap Threshold](#) 890

E

[Edge Rounding](#) 856
[Edge Rounding Mode](#) 856
[Editable](#) 889
[Editing Cycles](#) 38
[Editing Duration](#) 38
[Effect groups](#) 257
[Ellipse](#) 194
[Enclose Expression Inside Notation \(menclose\)](#) 365
[Encoding Type](#) 270

[Encryption](#) 913
[Encryption Data](#) 915
[End Angle](#) 857
[End Guide](#) 850
[End Line Spacing](#) 848
[End Marker](#) 795
[End Marker Center](#) 796
[End Marker Width](#) 795
[Enhanced Geometry](#) 238
[Enhanced Geometry - Equation](#) 251
[Enhanced Geometry - Extrusion Attributes](#) 240
[Enhanced Geometry - Handle Attributes](#) 252
[Enhanced Geometry - Path Attributes](#) 247
[Enhanced Geometry - Text Path Attributes](#) 250
[Enhanced Graphic Style Elements](#) 512
[Enhanced Page Features for Graphical Applications](#) 183
[Enhanced Text Styles](#) 485
[Entry in Table or Matrix \(mtd\)](#) 390
[Entry Text](#) 134
[Error Indicator](#) 268
[Error Message \(merror\)](#) 357
[Escape](#) 854
[Escape Direction](#) 854
[Escape Processing](#) 272
[Event Listener](#) 310
[Event Listener Tables](#) 310
Event Listeners ([section 2.1.298](#) 224, [section 2.1.444](#) 283)
[Event Types](#) 311
[Example of an Index Entry Configuration](#) 136
[Expression Fields](#) 103
[Expression Inside Pair of Fences \(mfenced\)](#) 363
[Extrude](#) 237

F

[Fade Color](#) 910
[File](#) 274
[File Entry](#) 914
[File Name Fields](#) 100
Fill Image ([section 2.1.577](#) 532, [section 2.1.795](#) 816)
[Fill Image Rendering Style](#) 817
[Fill Image Size](#) 818
[Fill Image Tile Reference Point](#) 820
[Fill Image Tile Translation](#) 823
[Fill Properties](#) 805
[Fill Rule](#) 825
[Fill Style](#) 806
Filter ([section 2.1.388](#) 272, [section 2.1.877](#) 860)
[Filter And](#) 165
[Filter Condition](#) 166
[Filter Or](#) 165
[Filters](#) 164
[First Page Number](#) 583
[Fit Line Length](#) 855
[Fit To Contour](#) 832
[Fit To Size](#) 831
[Fixed](#) 123
[Fixed and Minimum heights](#) 590
[Fixed Line Height](#) 683
[Fixed String](#) 135
[Fixed Text](#) 275
[Floating Frame](#) 234

[Floating Frame Formatting Properties](#) 898
[Floor](#) 267
[Flow with Text](#) 891
Font Character Set ([section 2.1.535](#) 457, [section 2.1.644](#) 625)
[Font Face Declaration](#) 444
[Font Face Declarations](#) 30
[Font Family](#) 613
Font Family Generic ([section 2.1.533](#) 455, [section 2.1.641](#) 617)
[Font Name](#) 611
Font Pitch ([section 2.1.534](#) 456, [section 2.1.643](#) 622)
[Font Relief](#) 649
[Font Size](#) 629
Font Style ([section 2.1.642](#) 620, [section 2.1.651](#) 646)
[Font Variant](#) 595
[Font Weight](#) 659
[Font-Independent Line Spacing](#) 685
[Footer](#) 266
[Footer Field](#) 262
[Footer field declaration](#) 263
[Footnote Separator](#) 586
[For](#) 279
[Form](#) 269
[Form Content](#) 269
[Format Change](#) 60
[Format Specification](#) 301
[Formatted Text](#) 274
[Formatting Properties](#) 554
[Formatting Style](#) 124
[Formula](#) 123
[Fractions \(mfrac\)](#) 347
[Frame](#) 276
[Frame Formatting Properties](#) 863
[Frame Heights](#) 864
[Frame Widths](#) 863
[Frames](#) 225
[Further Guidelines](#) 917

G

[Gap](#) 854
[Generation Mode](#) 860
[Generator](#) 34
[Generic Control](#) 277
[Glossary](#) 22
[Glue Points](#) 221
Gradient ([section 2.1.574](#) 513, [section 2.1.791](#) 813)
[Gradient Opacity](#) 824
[Gradient Step Count](#) 813
[Graphic and Presentation Styles](#) 510
[Graphic Content](#) 183
[Graphic Styles](#) 509
Grid ([section 2.1.363](#) 267, [section 2.1.414](#) 277)
[Grouping](#) 201
[Guide Distance](#) 850
[Guide Overhang](#) 849

H

[Handout Master](#) 183
Hatch ([section 2.1.576](#) 531, [section 2.1.793](#) 814)
[Header and Footer Styles](#) 436

[Header Columns](#) 149
[Header Field](#) 262
[Header field declaration](#) 263
[Header Footer Formatting Properties](#) 590
[Header Rows](#) 150
[Headers and Footers](#) 438
[Headings](#) 41
[Headings - Paragraphs and Basic Text Structure](#) 40
[Hidden](#) 277
[Hidden or Conditional Text](#) 681
[Hidden Paragraph Fields](#) 120
[Hidden Text Field](#) 117
[Hide Shape](#) 256
[Hide Text](#) 256
[Highlighted Range](#) 155
[Horizontal Position](#) 875
[Horizontal Relation](#) 875
[Horizontal Segments](#) 855
[Horizontally Group Sub-Expressions \(mrow\)](#) 346
[Hyperlink Behavior](#) 37
[Hyperlink Start and End](#) 135
[Hyperlink Titles](#) 916
Hyperlinks ([section 2.1.80](#) 72, [section 2.1.308](#) 235)
[Hyphenation](#) 677
[Hyphenation Keep](#) 704
[Hyphenation Push Char Count](#) 680
[Hyphenation Remain Char Count](#) 679

I

[Identifier \(mi\)](#) 312
[Ignore Result](#) 272
[Illustration Index Entry Template](#) 130
Image ([section 2.1.301](#) 229, [section 2.1.408](#) 276)
[Image Data](#) 279
[Image Documents](#) 28
[Image Frame](#) 276
[Image Level Style](#) 504
[Index Access of Sequences](#) 29
[Index Body Section](#) 128
Index Marks ([section 2.1.88](#) 89, [section 2.1.163](#) 125)
[Index of Illustration Source](#) 130
[Index of Illustrations](#) 129
[Index of Objects](#) 130
[Index of Tables](#) 130
[Index Source](#) 128
[Index source style](#) 133
[index source styles](#) 133
[Index Structure](#) 128
[Index Title Section](#) 128
[Index title template](#) 133
[Informative references](#) 23
Initial Creator ([section 2.1.33](#) 35, [section 2.1.117](#) 104)
[Inline graphics and text-boxes](#) 91
[Insertion](#) 60
Introduction ([section 1](#) 22, [section 2.1.953](#) 913)
[Introduction to Chart Documents](#) 265
[Iterative Animations](#) 406

J

[Justify Single Word](#) 691

K

Keep Together ([section 2.1.682](#) 691, [section 2.1.752](#) 769)
Keep with Next ([section 2.1.703](#) 733, [section 2.1.738](#) 764)
[Key Derivation](#) 915
[Keywords](#) 35
[Kind](#) 860

L

[Label](#) 280
[Label Ranges](#) 158
[Labeled Row in Table or Matrix \(mlabeledtr\)](#) 389
Language ([section 2.1.42](#) 37, [section 2.1.649](#) 638)
[Layer](#) 184
[Layer Sets](#) 184
[Layout Grid](#) 587
[Layout Grid Base Height](#) 587
[Layout Grid Color](#) 588
[Layout Grid Display](#) 589
[Layout Grid Lines](#) 588
[Layout Grid Print](#) 589
[Layout Grid Ruby Below](#) 589
[Layout Grid Ruby Height](#) 588
Left and Right Margins ([section 2.1.691](#) 709, [section 2.1.888](#) 866)
[Legend](#) 266
[Letter Kerning](#) 665
[Letter Spacing](#) 637
[Letter Synchronization in Number Formats](#) 307
[Light](#) 236
[Line](#) 187
[Line Break](#) 737
Line Distance ([section 2.1.677](#) 684, [section 2.1.839](#) 849)
[Line Join](#) 797
[Line Length](#) 855
[Line Number Start Value](#) 735
[Line Numbering](#) 734
[Line Numbering Configuration](#) 486
[Line-Through Color](#) 605
[Line-Through Style](#) 602
[Line-Through Text](#) 606
[Line-Through Text Style](#) 607
[Line-Through Type](#) 601
[Line-Through Width](#) 604
[Linked Table Cells](#) 153
[Linked Tables](#) 151
[List Block](#) 50
[List Box](#) 275
[List Header](#) 55
[List Item](#) 53
[List Level Style Example](#) 507
[List Property](#) 283
[List Style](#) 490
[List Styles](#) 836
[List-Level Style Properties](#) 779
[Lists](#) 49
[Location of Styles](#) 32

M

[Macro Fields](#) 120

[Making Sub-Expressions Invisible \(mphantom\)](#) 362
[Manifest File](#) 914
[Manifest Root Element](#) 914
[Map Entry](#) 29
Margins ([section 2.1.593](#) 574, [section 2.1.619](#) 590, [section 2.1.695](#) 714, [section 2.1.720](#) 750, [section 2.1.890](#) 870, [section 2.1.919](#) 899)
[Marker](#) 541
[Master Fields](#) 272
[Master Pages](#) 437
[Mathematical Content](#) 311
[Maximum Footnote Height](#) 584
[Maximum Hyphens](#) 705
[Maximum Length](#) 280
[Maximum Width and Height](#) 865
[May Break Between Rows](#) 764
[Mean Value](#) 268
[Measure](#) 199
[Measure Fields](#) 120
[Measure Properties](#) 849
[Media Elements](#) 406
[Metadata Elements](#) 34
[Metadata Fields](#) 104
[Method](#) 270
[MIME Type Stream](#) 914
[Minimum Line Height](#) 683
[Mirroring](#) 891
Mode ([section 2.1.871](#) 858, [section 2.1.878](#) 861)
[Modification Date and Time](#) 36
[More Fields](#) 116
[Multiple Dashes](#) 791

N

Name ([section 2.1.418](#) 277, [section 2.1.531](#) 453)
[Name Access of Sequences](#) 30
[Named Expressions](#) 158
[Navigation Mode](#) 273
[None and Linear Opacity](#) 824
[Normals Direction](#) 859
[Normals Kind](#) 859
[Normative references](#) 22
[Note Element](#) 84
[Notes](#) 83
[Notes Configuration](#) 761
[Notes Configuration Element](#) 487
[Number](#) 275
[Number \(mn\)](#) 317
[Number Format](#) 288
[Number Formatting Style](#) 124
[Number Level Style](#) 493
[Number Style](#) 458
[Numbered Paragraphs](#) 56

O

[Object Formatting Properties](#) 899
[Object Index Entry Template](#) 130
[Object Index Source](#) 130
[Objects](#) 231
[Offset](#) 843
Opacity ([section 2.1.785](#) 796, [section 2.1.834](#) 847)
[Opacity Gradient](#) 540
[Operator - Fence - Separator or Accent \(mo\)](#) 321
[Optimal Table Column Width](#) 767

[Optimal Table Row Height](#) 768
[Order](#) 273
[Orphans](#) 693
[Other Definitions](#) 912
[Outline Level Style](#) 507
[Outline Style](#) 507
[Overflow behavior](#) 891
[Overscript \(mover\)](#) 375

P

[Packages](#) 913
Padding ([section 2.1.596](#) 580, [section 2.1.622](#) 593, [section 2.1.701](#) 728, [section 2.1.763](#) 776, [section 2.1.899](#) 882)
[Page](#) 49
[Page Continuation Text](#) 97
[Page Duration](#) 910
[Page Layout](#) 435
[Page Layout Formatting Properties](#) 572
Page Number ([section 2.1.199](#) 134, [section 2.1.713](#) 744, [section 2.1.734](#) 763)
[Page Number Fields](#) 94
[Page Number Format](#) 573
[Page Sequences](#) 49
[Page Size](#) 572
[Page Styles and Layout](#) 34
[Page Thumbnail](#) 201
[Page Variable Fields](#) 116
[Page Visibility](#) 911
[Page-bound graphical content](#) 59
[Paper Tray](#) 573
[Paragraph Background Color](#) 717
[Paragraph Background Image](#) 718
[Paragraph Elements Content](#) 62
[Paragraph Formatting Properties](#) 682
[Paragraph Styles](#) 482
[Paragraph-only Wrapping](#) 890
[Paragraphs](#) 43
[Parallel](#) 851
[Parallel Animations](#) 406
[Parameters](#) 234
[Password](#) 274
[Path](#) 191
[Percentage Style](#) 461
[Placeholders](#) 117
[Placing](#) 851
[Play](#) 257
[Plot Area](#) 266
[Plot Area Properties](#) 900
[Plugins](#) 233
[Polygon](#) 189
[Polyline](#) 188
[Pre-Defined Metadata Elements](#) 34
[Pre-Defined vs. Custom Metadata](#) 27
[Prefix and Suffix](#) 297
[Prescripts and Tensor Indices \(mmultiscripts\)](#) 379
[Presentation Animations](#) 256
[Presentation Declarations](#) 263
[Presentation Document Content](#) 263
[Presentation Documents](#) 28
[Presentation Events](#) 260
Presentation Notes ([section 2.1.276](#) 185, [section 2.1.526](#) 442)
[Presentation Page Attributes](#) 900

[Presentation Page Layouts](#) 553
[Presentation Placeholder](#) 553
[Presentation Settings](#) 264
[Presentation Shapes](#) 255
[Presentation Text Fields](#) 262
[Preview Image](#) 914
[Print](#) 582
Print Content ([section 2.1.768](#) 778, [section 2.1.891](#) 871)
[Print Date](#) 106
[Print Date and Time](#) 36
[Print Orientation](#) 574
[Print Page Order](#) 583
[Print Time](#) 105
[Printable](#) 280
Printed By ([section 2.1.35](#) 36, [section 2.1.124](#) 106)
[Processing Rules for Formatting Properties](#) 570
[Properties](#) 283
[Property](#) 283
[Property Set](#) 283
Protect ([section 2.1.724](#) 757, [section 2.1.892](#) 871)
[Punctuation Wrap](#) 736

R

[Radicals \(msqrt - mroot\)](#) 350
[Radio Button](#) 276
[Read only](#) 280
[Recommended Usage Of SMIL](#) 257
[Rectangle](#) 186
[Reference Fields](#) 117
[References](#) 82
 [informative](#) 23
 [normative](#) 22
[Referencing Table Cells](#) 151
[Register True](#) 708
[Register-truth](#) 582
[Regression Curve Properties](#) 900
[Regression Curves](#) 268
[Regular Polygon](#) 190
[Relative Font Size](#) 632
[Relative Image Position](#) 282
[Relax-NG Schema](#) 914
Relax-NG Schema Suffix ([section 2.1.951](#) 913, [section 2.1.966](#) 915)
[Repeat Content](#) 778
[Rotate](#) 237
[Rotation Align](#) 777
[Rotation Angle](#) 777
[Row and Column Styles](#) 443
[Row Background](#) 768
[Row Groups](#) 151
[Row Height](#) 768
[Row in Table or Matrix \(mtr\)](#) 387
[Ruby](#) 86
[Ruby Alignment](#) 747
[Ruby Position](#) 746
[Ruby Style](#) 484
[Ruby Text Formatting Properties](#) 745
[Run Through](#) 891

S

[Scale](#) 583
[Scenario Tables](#) 152

[Scene](#) 236
[Script](#) 30
[Script Fields](#) 119
[Script Type](#) 635
[Scripts](#) 30
[Secondary Fill Color](#) 812
[Section Attributes](#) 57
[Section Background](#) 749
[Section Formatting Properties](#) 748
[Section Source](#) 58
[Section Styles](#) 483
[Selected](#) 280
[Selecting a Row Number](#) 116
[Selecting the Next Database Row](#) 116
[Sender Fields](#) 97
[Sequence of Settings](#) 29
[Sequential Animations](#) 406
[Series](#) 267
[Set](#) 399
[Setting Simple Variables](#) 102
Shadow ([section 2.1.597](#) 581, [section 2.1.624](#) 594, [section 2.1.702](#) 732, [section 2.1.831](#) 842, [section 2.1.883](#) 863, [section 2.1.900](#) 887)
[Shadow Properties](#) 841
[Shapes](#) 153
[Sheet Name Fields](#) 101
[Shininess](#) 862
[Show Definitions](#) 265
[Show Shape](#) 256
[Show Text](#) 256
[Show Unit](#) 852
[Shrink To Fit](#) 778
[Simple and Complex Formatting Properties](#) 565
[Simple Formatting Properties](#) 567
[Simple Variable Input Fields](#) 102
[Size](#) 280
[SMIL Animations](#) 398
[SMIL Presentation Animation Attributes](#) 259
[SMIL Presentation Animations](#) 257
[Snap To Layout](#) 743
[Soft Hyphens - Hyphens - and Non-breaking Blanks](#) 69
[Soft Page Break](#) 61
[Solid Hatch](#) 815
[Sort](#) 162
[Sort By](#) 163
Sound ([section 2.1.327](#) 256, [section 2.1.940](#) 911)
[Source Cell Range](#) 168
[Source Service](#) 168
[Space \(mspace\)](#) 333
[Special Elements](#) 407
[Specifying alignment points using malignmark](#) 392
[Sphere](#) 237
[Spreadsheet Document Content](#) 155
[Spreadsheet Documents](#) 28
[Start Guide](#) 850
[Start Line Spacing](#) 848
[Start Marker](#) 794
[Start Marker Center](#) 796
[Start Marker Width](#) 795
[Statistical Properties](#) 900
[Stock Chart Markers](#) 269
[String Literal \(ms\)](#) 337
[Stroke Dash](#) 543
[Stroke Properties](#) 787

[Stroke Style](#) 788
[Style Change \(mstyle\)](#) 352
[Style Element](#) 408
[Style Mappings](#) 426
Styles ([section 2.1.23](#) 31, [section 2.1.518](#) 407)
[Subject](#) 35
[Subscript \(msub\)](#) 369
[Subscript-superscript Pair \(msubsup\)](#) 372
[Subtables](#) 151
[Subtitle](#) 266
[Subtotal Field](#) 164
[Subtotal Rule](#) 164
[Subtotal Rules](#) 163
[Subtotal Sort Groups](#) 164
[Superscript \(msup\)](#) 370
[SVG Gradients](#) 529
[Symbol color](#) 826

T

[Tab Index](#) 281
Tab Stop ([section 2.1.202](#) 135, [section 2.1.437](#) 281)
[Tab Stop Distance](#) 704
[Tab Stops](#) 694
[Tabbing Cycle](#) 273
[Table Alignment](#) 762
[Table Background and Background Image](#) 764
[Table Cell](#) 141
[Table Cell Content Validations](#) 157
[Table Cell Formatting Properties](#) 770
[Table Cell Styles](#) 509
[Table Centering](#) 584
[Table Column Styles](#) 508
[Table Element](#) 136
[Table Filter](#) 165
[Table Formatting Properties](#) 761
[Table Formula Field](#) 120
[Table Index Entry Template](#) 130
[Table Index Source](#) 130
[Table Left and Right Margin](#) 762
[Table Margins](#) 763
[Table Of Content](#) 128
[Table of Content Entry Template](#) 129
[Table of Content Index Marks](#) 125
[Table of Content Source](#) 129
[Table or Matrix \(mtable\)](#) 381
[Table Row](#) 140
[Table Row Formatting Properties](#) 767
[Table Row Styles](#) 509
[Table Shadow](#) 764
Table Styles ([section 2.1.565](#) 508, [section 2.1.566](#) 508)
[Table Templates](#) 443
[Table Top and Bottom Margin](#) 762
[Table Width](#) 761
[Tables](#) 136
Target Frame ([section 2.1.375](#) 270, [section 2.1.438](#) 281)
[Target Location](#) 281
[Text](#) 274
[Text \(mtext\)](#) 329
[Text Align](#) 686
[Text Align of Last Line](#) 688
[Text Align Source](#) 770
[Text Alignment](#) 851

[Text and Text Alignment Properties](#) 828
[Text Animation Properties](#) 827
[Text Annotation](#) 88
[Text Area](#) 274
[Text Area Horizontal Align](#) 834
[Text Area Vertical Align](#) 833
[Text Autospace](#) 735
[Text Background Color](#) 667
[Text Blinking](#) 666
[Text Box](#) 226
[Text Combine](#) 668
[Text Combine Start and End Characters](#) 670
[Text Content](#) 40
[Text Declarations](#) 61
[Text Documents](#) 27
[Text Emphasis](#) 672
[Text Fields](#) 91
[Text Formatting Properties](#) 594
[Text Indent](#) 711
[Text Indices](#) 125
[Text Input Fields](#) 103
[Text Line-Through Word Mode](#) 664
[Text Outline](#) 600
[Text Position](#) 608
[Text Rotation Angle](#) 675
[Text Rotation Scale](#) 676
[Text Scale](#) 674
[Text Sections](#) 56
[Text Shadow](#) 652
[Text Style](#) 477
Text Styles ([section 2.1.548](#) 481, [section 2.1.549](#) 481)
[Text Transformations](#) 597
[Text Underline Word Mode](#) 663
[Time Fields](#) 93
[Time Style](#) 472
Title ([section 2.1.29](#) 34, [section 2.1.355](#) 265, [section 2.1.440](#) 281)
[Title - Description and Caption of Graphical Elements](#) 915
[Title - Subtitle and Footer](#) 265
[Title and Description](#) 222
[Token Elements](#) 312
Top and Bottom Margins ([section 2.1.694](#) 712, [section 2.1.889](#) 868)
Tracked Changes ([section 2.1.66](#) 59, [section 2.1.269](#) 183)
[Tracking changes](#) 918
[Transition Direction](#) 910
[Transition Filter](#) 399
[Transition Speed](#) 906
[Transition Style](#) 901
[Transition Subtype](#) 910
[Transition Type](#) 900
[Transition Type or Family](#) 906
[Transliteration](#) 479
[Type](#) 853

U

[Underline Color](#) 658
[Underling Width](#) 656
[Underlining Style](#) 654
[Underlining Type](#) 653
[Underscript \(munder\)](#) 373

[Underscript-overscript Pair \(munderover\)](#) 377
[Unit](#) 852
[Usage of IRIs Within Packages](#) 914
[User Variable Input Fields](#) 103
[User-Defined Document Information](#) 105
[User-Defined Index](#) 131
[User-Defined Index Entry Template](#) 131
[User-Defined Index Marks](#) 126
[User-Defined Index Source](#) 131
[User-defined Metadata](#) 39
[Using Sequence Fields](#) 103

V

[Value and Current Value](#) 279
[Value Range](#) 277
[Variable Fields](#) 101
[Variable Name](#) 123
[Variable Value Types and Values](#) 121
Vertical Alignment ([section 2.1.709](#) 738, [section 2.1.754](#) 770)
[Vertical Glyph Orientation](#) 771
[Vertical Position](#) 877
[Vertical Relation](#) 877
[Vertical Segments](#) 856
[Visible Area](#) 899
[Visual Effect](#) 281

W

[Wall](#) 266
[White-space Characters](#) 64
[Widows](#) 692
[Width](#) 792
[Window Font Color](#) 599
[Word Wrap](#) 835
[Wrap Influence on Position](#) 896
[Wrap Option](#) 777
[Wrapping](#) 890
Writing Mode ([section 2.1.607](#) 585, [section 2.1.710](#) 739, [section 2.1.726](#) 759, [section 2.1.741](#) 765, [section 2.1.915](#) 896)

X

XForms Model ([section 2.1.394](#) 273, [section 2.1.395](#) 273)

Z

[Zip File Structure](#) 913