

[MS-OXCMSG]: Message and Attachment Object Protocol Specification

Intellectual Property Rights Notice for Protocol Documentation

- **Copyrights.** This protocol documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the protocols, and may distribute portions of it in your implementations of the protocols or your documentation as necessary to properly document the implementation. This permission also applies to any documents that are referenced in the protocol documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the protocols. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, the protocols may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>). If you would prefer a written license, or if the protocols are not covered by the OSP, patent licenses are available by contacting protocol@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. This protocol documentation is intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it. A protocol specification does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them.

Revision Summary			
Author	Date	Version	Comments
Microsoft Corporation	April 4, 2008	0.1	Initial Availability.
Microsoft Corporation	April 25, 2008	0.2	Revised and updated property names and other technical content.
Microsoft Corporation	June 27, 2008	1.0	Initial Release.

Table of Contents

1	Introduction.....	8
1.1	Glossary.....	8
1.2	References.....	9
1.2.1	Normative References.....	9
1.2.2	Informative References.....	10
1.3	Protocol Overview.....	11
1.3.1	Messages.....	11
1.3.2	FAI Messages.....	11
1.3.3	Message Recipients.....	11
1.3.4	Message Attachments.....	11
1.4	Relationship to Other Protocols.....	11
1.5	Prerequisites/Preconditions.....	12
1.6	Applicability Statement.....	12
1.7	Versioning and Capability Negotiation.....	12
1.8	Vendor-Extensible Fields.....	12
1.9	Standards Assignments.....	12
2	Messages.....	12
2.1	Transport.....	12
2.2	Message Syntax.....	12
2.2.1	Message Object Properties.....	13
2.2.1.1	General Properties.....	13
2.2.1.2	PidTagHasAttachments.....	13
2.2.1.3	PidTagMessageClass.....	13
2.2.1.4	PidTagMessageCodepage.....	13
2.2.1.5	PidTagMessageLocaleId.....	14
2.2.1.6	PidTagMessageFlags.....	14
2.2.1.7	PidTagMessageSize.....	15
2.2.1.8	PidTagMessageStatus.....	15
2.2.1.9	PidTagSubjectPrefix.....	15
2.2.1.10	PidTagNormalizedSubject.....	16
2.2.1.11	PidTagImportance.....	16
2.2.1.12	PidTagPriority.....	16
2.2.1.13	PidTagSensitivity.....	16
2.2.1.14	PidLidSmartNoAttach.....	17
2.2.1.15	PidLidPrivate.....	17
2.2.1.16	PidLidSideEffects.....	17
2.2.1.17	PidNameKeywords.....	18
2.2.1.18	PidLidCommonStart.....	18
2.2.1.19	PidLidCommonEnd.....	18
2.2.1.20	Body Properties.....	18

2.2.1.20.1	PidTagBody	18
2.2.1.20.2	PidTagBodyHtml	18
2.2.1.20.3	PidTagRtfCompressed	18
2.2.1.20.4	PidTagRtfInSync	18
2.2.1.20.5	PidTagInternetCodepage	19
2.2.1.21	Contact Linking Properties	19
2.2.1.21.1	PidLidContactLinkEntry	19
2.2.1.21.2	PidLidContacts	19
2.2.1.21.3	PidLidContactLinkName	19
2.2.1.21.4	PidLidContactLinkSearchKey	19
2.2.2	Attachment Object Properties	20
2.2.2.1	General Properties	20
2.2.2.2	PidTagLastModificationTime	20
2.2.2.3	PidTagCreationTime	20
2.2.2.4	PidTagDisplayName	20
2.2.2.5	PidTagAttachSize	20
2.2.2.6	PidTagAttachNumber	20
2.2.2.7	PidTagAttachDataBinary	20
2.2.2.8	PidTagAttachDataObject	21
2.2.2.9	PidTagAttachMethod	21
2.2.2.10	PidTagAttachLongFilename	21
2.2.2.11	PidTagAttachFilename	21
2.2.2.12	PidTagAttachExtension	21
2.2.2.13	PidTagAttachLongPathname	21
2.2.2.14	PidTagAttachPathname	22
2.2.2.15	PidTagAttachTag	22
2.2.2.16	PidTagRenderingPosition	22
2.2.2.17	PidTagAttachRendering	22
2.2.2.18	PidTagAttachFlags	22
2.2.2.19	PidTagAttachTransportName	22
2.2.2.20	PidTagAttachEncoding	23
2.2.2.21	PidTagAttachAdditionalInformation	23
2.2.2.22	PidTagAttachmentLinkId	23
2.2.2.23	PidTagAttachmentFlags	23
2.2.2.24	PidTagAttachmentHidden	23
2.2.2.25	MIME properties	23
2.2.3	Message Object ROPS	24
2.2.3.1	RopOpenMessage Buffer Format	24
2.2.3.1.1	Request Buffer	24
2.2.3.1.2	Response Buffer	25
2.2.3.2	RopCreateMessage Buffer Format	26
2.2.3.2.1	Request Buffer	27

2.2.3.2.2	Response Buffer	27
2.2.3.3	RopSaveChangesMessageBuffer Format	27
2.2.3.3.1	Request Buffer	28
2.2.3.3.2	Response Buffer	28
2.2.3.4	RopRemoveAllRecipients Buffer Format	29
2.2.3.4.1	Request Buffer	29
2.2.3.4.2	Response Buffer	29
2.2.3.5	RopModifyRecipients Buffer Format	29
2.2.3.5.1	Request Buffer	29
2.2.3.5.2	Response Buffer	30
2.2.3.6	RopReadRecipients Buffer Format	30
2.2.3.6.1	Request Buffer	30
2.2.3.6.2	Response Buffer	31
2.2.3.7	RopReloadCachedInformation Buffer Format	31
2.2.3.7.1	Request Buffer	31
2.2.3.7.2	Response Buffer	32
2.2.3.8	RopSetMessageStatus Buffer Format	32
2.2.3.8.1	Request Buffer	32
2.2.3.8.2	Response Buffer	32
2.2.3.9	RopGetMessageStatusBuffer Format	33
2.2.3.9.1	Request Buffer	33
2.2.3.9.2	Response Buffer	33
2.2.3.10	RopSetReadFlags Buffer Format	33
2.2.3.10.1	Request Buffer	33
2.2.3.10.2	Response Buffer	34
2.2.3.11	RopSetMessageReadFlag	34
2.2.3.11.1	Request Buffer	35
2.2.3.11.2	Response Buffer	35
2.2.3.12	RopOpenAttachment	36
2.2.3.12.1	Request Buffer	36
2.2.3.12.2	Response Buffer	36
2.2.3.13	RopCreateAttachment	36
2.2.3.13.1	Request Buffer	36
2.2.3.13.2	Response Buffer	36
2.2.3.14	RopDeleteAttachment	37
2.2.3.14.1	Request Buffer	37
2.2.3.14.2	Response Buffer	37
2.2.3.15	RopSaveChangesAttachment Buffer Format	37
2.2.3.15.1	Request Buffer	37
2.2.3.16	RopOpenEmbeddedMessage Buffer Format	38
2.2.3.16.1	Request Buffer	38
2.2.3.16.2	Response Buffer	38

2.2.3.17	RopGetAttachmentTable Buffer Format	39
2.2.3.17.1	Request Buffer	39
2.2.3.17.2	Response Buffer	40
3	Protocol Details.....	40
3.1	Client Details.....	40
3.1.1	Abstract Data Model	40
3.1.1.1	Linking a Contact Object.....	40
3.1.2	Timers	40
3.1.3	Initialization	40
3.1.4	Higher-Layer Triggered Events.....	40
3.1.4.1	Opening a Message Object.....	40
3.1.4.2	Creating a Message Object.....	41
3.1.4.3	Saving Message Object Changes.....	41
3.1.4.4	Removing All Recipients.....	41
3.1.4.5	Adding, Deleting, and Modifying Recipients.....	41
3.1.4.6	Reading Recipients	42
3.1.4.7	Reload Message Object Header Info	42
3.1.4.8	Setting Message Status	42
3.1.4.9	Getting Message Status	42
3.1.4.10	Setting Message Object Read State.....	43
3.1.4.11	Opening Attachments	43
3.1.4.12	Creating Attachments	43
3.1.4.13	Setting Attachment Object Content	43
3.1.4.14	Saving Attachment Object Changes	44
3.1.4.15	Opening an Embedded Message Object.....	44
3.1.4.16	Accessing the Attachments Table	44
3.1.4.17	Creating an Embedded Message	44
3.1.4.18	Saving an Embedded Message	44
3.1.5	Message Processing Events and Sequencing Rules	45
3.1.6	Timer Events	45
3.1.7	Other Local Events.....	45
3.2	Server Details.....	45
3.2.1	Abstract Data Model	45
3.2.2	Timers	45
3.2.3	Initialization	45
3.2.4	Higher-Layer Triggered Events.....	45
3.2.4.1	RopOpenMessage.....	45
3.2.4.2	RopCreateMessage	46
3.2.4.3	RopSaveChangesMessage	47
3.2.4.4	RopRemoveAllRecipients	47
3.2.4.5	RopModifyRecipients.....	47
3.2.4.6	RopReadRecipients	48

3.2.4.7	RopReloadCachedInformation	49
3.2.4.8	RopSetMessageStatus	49
3.2.4.9	RopGetMessageStatus	49
3.2.4.10	RopSetReadFlags	49
3.2.4.11	RopSetMessageReadFlag	50
3.2.4.12	RopOpenAttachment	50
3.2.4.13	RopCreateAttachment	50
3.2.4.14	RopSaveChangesAttachment	51
3.2.4.15	RopDeleteAttachment	51
3.2.4.16	RopOpenEmbeddedMessage	52
3.2.4.17	RopGetAttachmentTable	52
4	Protocol Examples.....	52
4.1	Create Message	52
4.1.1	RopCreateMessage Request Buffer	52
4.1.2	RopCreateMessage Response Buffer	53
4.2	Name to Id Mapping.....	53
4.3	Get Attachment Table.....	53
4.3.1	RopGetAttachmentTable Request Buffer	53
4.3.2	RopGetAttachmentTable Response Buffer	53
4.4	Insert HTML Embedded Image.....	53
4.4.1	RopCreateAttachment Request Buffer.....	53
4.4.2	RopCreateAttachment Response Buffer	54
4.4.3	Setting Properties	54
4.4.4	RopSaveChangesAttachment Request Buffer	55
4.4.5	RopSaveChangesAttachment Response Buffer	55
4.4.6	Releasing Attachment Object	55
4.5	Attach Text File	55
4.5.1	RopCreateAttachment Request Buffer.....	55
4.5.2	RopCreateAttachment Response Buffer	55
4.5.3	Setting Properties	55
4.5.4	RopSaveChangesAttachment Request Buffer	56
4.5.5	RopSaveChangesAttachment Response Buffer	56
4.5.6	Releasing Attachment Object	56
4.6	Setting Message Properties	56
4.7	Adding Recipients	57
4.7.1	RopModifyRecipients Request Buffer	57
4.7.2	RopModifyRecipients Response Buffer	58
4.8	Save Message.....	59
4.8.1	RopSaveChangesMessage Request Buffer.....	59
4.8.2	RopSaveChangesMessage Response Buffer	59
4.9	Releasing Message Object	59
5	Security.....	59

5.1	Security Considerations for Implementers	59
5.2	Index of Security Parameters	59
6	<i>Appendix A:Office/Exchange Behavior</i>	59
	<i>Index</i>	61

1 Introduction

The Message and Attachment Object Protocol provides the methods used within the server for manipulating **Message objects**.

1.1 Glossary

The following terms are defined in [MS-OXGLOS]:

- ASCII
- Attachment object
- BCC recipient
- CC recipient
- code page
- Contact object
- contents table
- Embedded Message object
- folder associated information (FAI)
- folder ID (FID)
- Folder object
- handle
- LogonID
- message ID (MID)
- Message object
- metafile
- MIME
- primary recipient
- property tag
- read receipt
- remote operation (ROP)
- ROP request buffer
- ROP response buffer
- soft delete
- table
- Unicode

The following terms are defined in [MS-GLOS]:

8.3 Name

The following terms are specific to this document:

header message object: A **Message object** that contains partial information about a message left on a server such as an identifier for the message, the display names of the recipients and sender of the message, the subject of the message, and the delivery time

of the message. It allows a client to display enough information about a message to let a user choose which messages to download.

Object Linking and Embedding (OLE): A Microsoft compound document standard that enables cross-application linking and embedding of objects.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

[MS-LCID] Microsoft Corporation, "Windows Language Code Identifier (LCID) Reference", March 2007, <http://msdn.microsoft.com/en-us/library/cc233965.aspx>.

[MS-OXCDATA] Microsoft Corporation, "Data Structures Protocol Specification", April 2008.

[MS-OXCFOLD] Microsoft Corporation, "Folder Object Protocol Specification", April 2008.

[MS-OXCMAIL] Microsoft Corporation, "RFC2822 and MIME to E-mail Object Conversion Protocol Specification", April 2008.

[MS-OXCPRPT] Microsoft Corporation, "Property and Stream Object Protocol Specification", April 2008.

[MS-OXCROPS] Microsoft Corporation, "Remote Operations (ROP) List and Encoding Protocol Specification", April 2008.

[MS-OXCSTOR] Microsoft Corporation, "Store Object Protocol Specification", April 2008.

[MS-OXCTABL] Microsoft Corporation, "Table Object Protocol Specification", April 2008.

[MS-OXOABK] Microsoft Corporation, "Address Book Object Protocol Specification", April 2008.

[MS-OXOCAL] Microsoft Corporation, "Appointment and Meeting Object Protocol Specification", April 2008.

[MS-OXOCNTC] Microsoft Corporation, "Contact Object Protocol Specification", April 2008.

[MS-OXODOC] Microsoft Corporation, "Document Object Protocol Specification", April 2008.

[MS-OXOJRNL] Microsoft Corporation, "Journal Object Protocol Specification", April 2008.

[MS-OXOMSG] Microsoft Corporation, "E-mail Object Protocol Specification", April 2008.

[MS-OXONOTE] Microsoft Corporation, "Note Object Protocol Specification", April 2008.

[MS-OXOPOST] Microsoft Corporation, "Post Object Protocol Specification", April 2008.

[MS-OXORSS] Microsoft Corporation, "RSS Object Protocol Specification", April 2008.

[MS-OXOSFLD] Microsoft Corporation, "Special Folders Protocol Specification", April 2008.

[MS-OXOSMIME] Microsoft Corporation, "S/MIME E-mail Object Protocol Specification", April 2008.

[MS-OXOSMMS] Microsoft Corporation, "SMS and MMS Object Protocol Specification", April 2008.

[MS-OXOTASK] Microsoft Corporation, "Task-Related Objects Protocol Specification", April 2008.

[MS-OXOUM] Microsoft Corporation, "Voice Mail and Fax Objects Protocol Specification", April 2008.

[MS-OXPROPS] Microsoft Corporation, "Office Exchange Protocols Master Property List Specification", April 2008.

[MS-OXTNEF] Microsoft Corporation, "Transport Neutral Encapsulation Format (TNEF) Protocol Specification", April 2008.

[MS-WMF] Microsoft Corporation, "Windows Metafile Format Specification", June 2007, <http://msdn.microsoft.com/en-us/library/cc215212.aspx>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

[RFC2822] Resnick, P., Ed., "Internet Message Format", RFC 2822, April 2001, <http://www.ietf.org/rfc/rfc2822.txt>.

1.2.2 Informative References

None.

1.3 Protocol Overview

1.3.1 Messages

Message objects are representations of end-users' data that store properties and are persisted in a folder hierarchy within a message store.

1.3.2 FAI Messages

FAI messages are a type of message that contains non-user data needed by the client or server. FAI messages are persisted in the same way as **Message objects**, but cannot be sent.

1.3.3 Message Recipients

Message objects allow clients to associate one or more recipients to a message. A recipient is a set of properties that describe where the message is to be delivered. Clients add, remove or modify recipients through the **RecipientRows**.

1.3.4 Message Attachments

An **Attachment object** is used by a client to associate files, **OLE** objects, other messages, or binary data with a particular **Message object**. Because Attachment objects are created, maintained, and accessed only in the context of a message, they are considered sub-objects. Operations that affect the location of a Message object also apply to its attachments. Clients retrieve information about attachments in a message via an attachment **table**, which is a table object as specified in the [MS-OXCTABL].

1.4 Relationship to Other Protocols

The Message and **Attachment object** Protocol relies on **folders**, **tables**, and **properties**, as specified in [MS-OXCFOLD], [MS-OXOSFLD], [MS-OXCTABL], [MS-OXCPRPT], as well as the underlying Remote Operations transport, specified in [MS-OXCROPS].

At the time of this publication, the following protocols are known to extend Message and Attachment Object Protocol.

- Appointment and Meeting Object Protocol, [MS-OXOCAL]
- Contact Object Protocol, [MS-OXOCNTC]
- E-mail Object Protocol, [MS-OXOMSG]
- Task –Related Objects Protocol, [MS-OXOTASK]
- Note Object Protocol, [MS-OXONOTE]
- Journal Object Protocol, [MS-OXOJRNL]
- RSS Object Protocol, [MS-OXORSS]
- Post Object Protocol, [MS-OXOPOST]
- SMS and MMS Object Protocol, [MS-OXOSMMS]
- Document Object Protocol, [MS-OXODOC]
- S/MIME E-mail Object Protocol, [MS-OXOSMIME]

- Voice Mail and Fax Objects Protocol, [MS-OXOUM]

1.5 Prerequisites/Preconditions

The Message and **Attachment object** Protocol assumes the client has previously logged on to the server and has acquired a **handle** to the **Folder object** upon which it needs to operate. For more information, see [MS-OXCFOLD] and [MS-OXCSTOR].

1.6 Applicability Statement

The Message and **Attachment object** Protocol can be used as the basis for different types of personal information messages, like E-mail, Contacts, Appointments, Notes, etc.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

A third-party application can create its own set of **named properties** on a **Message object** as specified in [MS-OXCPRPT]. A third-party application can also extend the Message and **Attachment object** Protocol to implement its own object type, by changing **PidTagMessageClass**. See [MS-OXONOTES] for a simple example that extends this protocol to implement an electronic representation of a "Sticky Note".

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The **ROP Request Buffers** and **ROP Response Buffers** specified by this protocol are sent to and respectively are received from the server using the underlying Remote Operations transport as specified in [MS-OXCROPS].

2.2 Message Syntax

Message objects can be created and modified by clients and servers. Except where noted below, this section defines constraints to which both clients and servers **MUST** adhere when operating on **Message objects**.

Clients operate on **Message objects** using the **ROPs** as specified in section 2.2.3, and the Property and Stream Object Protocol. See [MS-OXCPRPT] for more information.

Unless otherwise specified below, all property constraints specified in [MS-OXPROPS] apply to **Message objects**. A Message object MAY also contain other properties defined in [MS-OXPROPS] but these properties have no impact on this protocol.

When a property is referred to as "read-only for the client" the server MUST return an error and ignore any request to change the value of that property.

2.2.1 Message Object Properties

2.2.1.1 General Properties

The following properties exist on all **Message objects**. These properties are read-only for the client. For specifications of the properties listed here see [MS-OXCPRPT].

PidTagAccess	PidTagLastModificationTime
PidTagAccessLevel	PidTagObjectType
PidTagChangeKey	PidTagRecordKey
PidTagCreationTime	PidTagSearchKey
PidTagLastModifierName	

2.2.1.2 PidTagHasAttachments

Type: **PtypBoolean**.

Indicates whether the **Message object** contains at least one attachment. This property is read-only for the client.

The server computes this property from the **mfHasAttach** flag of **PidTagMessageFlags**.

2.2.1.3 PidTagMessageClass

Type: **PtypString**.

Denotes the specific type of the **Message object**. It determines the set of properties defined for the message, the kind of information the message conveys, and how to **handle** the message.

All characters in this property MUST be from the **ASCII** characters 0x20 through 0x7F. It MUST NOT end with a period (ASCII character 0x2E), and its length MUST be greater than zero and less than 256 characters. Furthermore, its length SHOULD be fewer than 128 characters, because some operations require extending the value of **PidTagMessageClass**.

The value of this property is interpreted in groups of characters separated by periods ("."). Each group specifies a derived type of object. If a server or client does not recognize a message class, it reverts to acting on all but the last group, recursively, until a recognized form remains. A message class of "IPM.Note" denotes a standard Message object, and a message class of "Remote.IPM.Note" indicates a **header message object**.

2.2.1.4 PidTagMessageCodepage

Type: **PtypInteger32**, unsigned

Specifies the **code page** used to encode the **non-Unicode** string properties on this **Message object**. The Folder object code page is used if this property is set to "0x0000".

2.2.1.5 PidTagMessageLocaleId

Type: **PtypInteger32**, unsigned

Contains the Windows LCID of the end-user who created this message. For more information see [MS-LCID].

2.2.1.6 PidTagMessageFlags

Type: **PtypeInteger32**

Specifies the status of the **Message object**; MUST be set to a bitwise OR of zero or more of the values from the following tables.

After the first successful **RopSaveChangesMessage**, as described in section 2.2.3.3, these flags are read-only for the client.

Name	Value	Description
mfRead	0x00000001	The message is marked as having been read.
mfUnsent	0x00000008	The message is still being composed. This bit MUST be cleared by the server when responding to RopSubmitMessage with a success code. See [MS-OXOMSG] for details.
mfResend	0x00000080	The message includes a request for a resend operation with a non-delivery report. See [MS-OXOMSG] for details.

These flags are always read-only for the client.

Type	Value	Description
mfUnmodified	0x00000002	The message has not been modified since it was first saved (if unsent) or it was delivered (if sent).
mfSubmitted	0x00000004	The message is marked for sending as a result of a call to RopSubmitMessage [MS-OXOMSG].
mfHasAttach	0x00000010	The message has at least one attachment. This flag corresponds to the message's PidTagHasAttachments property.
mfFromMe	0x00000020	The user receiving the message was also the user who sent the message.
mfFAI	0x00000040	The message is an FAI message.
mfNotifyRead	0x00000100	The user who sent the message has requested notification when a recipient first reads it.
mfNotifyUnread	0x00000200	The user who sent the message has requested notification when a recipient deletes it before reading or the Message object expires as specified in [MS-OXOMSG].
mfInternet	0x00002000	The incoming message arrived over the Internet and

Type	Value	Description
		originated either outside the organization or from a source the gateway does not consider trusted.
mfUntrusted	0x00008000	The incoming message arrived over an external link other than X.400 or the Internet. It originated either outside the organization or from a source the gateway does not consider trusted.

PidTagMessageFlags are also modified using **RopSetMessageReadFlag** request, as described in section 2.2.3.11, or **RopSetReadFlags**, as described in [MS-OXCFCOLD].

2.2.1.7 PidTagMessageSize

Type: **PtypInteger32**, unsigned

Contains the size in **bytes** consumed by the **Message object** on the server. This property is read-only for the client.

2.2.1.8 PidTagMessageStatus

Type: **PtypInteger32**

Specifies the status of a message in a **contents table**. MUST contain a bitwise OR of zero or more values from following table.

Type	Value	Description
msRemoteDownload	0x00001000	The message has been marked for downloading from the remote message store to the local client.
msInConflict	0x00000800	This is a conflict resolve message as specified in [MS-OXCASYNC]. This is a read-only value for the client.
msRemoteDelete	0x00002000	The message has been marked for deletion at the remote message store without downloading to the local client.

In order to set **PidTagMessageStatus**, the client does not include it in a **RopSetProperties** request. Instead, the client calls **RopSetMessageStatus**, as described in section 2.2.3.7.

In order to get **PidTagMessageStatus**, the client does not include it in a **RopGetPropertiesSpecific** request. Instead, the client calls **RopSetMessageStatus**, as described in section 2.2.3.8. Additionally, **PidTagMessageStatus** may be set as a column on a **contents table** (for more information on **tables**, see MS-OXCTBL).

2.2.1.9 PidTagSubjectPrefix

Type: **PtypString**

Contains the prefix for the subject of the message. MUST be set by the client, but MAY be an empty string. The sum of the lengths of **PidTagNormalizedSubject** and **PidTagSubjectPrefix** MUST be less than 254 characters.

The client does not include **PidTagSubjectPrefix** in a **RopGetPropertiesSpecific** request. Instead, the client uses the **SubjectPrefix** field from the **RopOpenMessage** response buffer.

2.2.1.10 **PidTagNormalizedSubject**

Type: **PtypString**

Contains the normalized subject of the message. MUST be set by the client, but MAY be an empty string. The sum of the lengths of **PidTagNormalizedSubject** and **PidTagSubjectPrefix** MUST be less than 254 characters.

The client does not include **PidTagNormalizedSubject** in a **RopGetPropertiesSpecific** request. Instead, the client uses the **NormalizedSubject** field from the **RopOpenMessage** response buffer.

2.2.1.11 **PidTagImportance**

Type: **PtypInteger32**

Indicates the level of importance assigned by the end user to the **Message object**; MUST be set to one of the following values.

Value	Description
0x00000000	Low importance.
0x00000001	Normal importance.
0x00000002	High importance.

2.2.1.12 **PidTagPriority**

Type: **PtypInteger32**

Indicates the client's request for the priority at which the message is to be sent by the messaging system; MUST be one of the following values.

Value	Description
0xFFFFFFFF	Urgent.
0x00000000	Normal.
0x00000001	Non-Urgent

2.2.1.13 **PidTagSensitivity**

Type: **PtypInteger32**

Indicates the sender's assessment of the sensitivity of the **Message object**. MUST be one of the following.

Value	Description
0x00000000	Normal
0x00000001	Personal
0x00000002	Private
0x00000003	Confidential

2.2.1.14 PidLidSmartNoAttach

Type: **PtypBoolean**

Indicates whether the **Message object** has no end-user visible attachments. This property MAY be unset; if so, a default value of "0x00" is assumed.

2.2.1.15 PidLidPrivate

Type: **PtypBoolean**

Indicates whether the end-user wishes for this **Message object** to be hidden from other users who have access to the Message object.

2.2.1.16 PidLidSideEffects

Type: **PtypInteger32**

Controls how a **Message object** is handled by the client when acting on end-user input. MUST be set to a bitwise OR of zero or more of the following flags.

Name	Value	Description
seOpenToDelete	0x0001	Additional processing is required on the Message object when deleting.
seNoFrame	0x0008	No UI is associated with the Message object.
seCoerceToInbox	0x0010	Additional processing is required on the Message object when moving or copying to a Folder object with a PidTagContainerClass of "IPF.Note".
seOpenToCopy	0x0020	Additional processing is required on the Message object when copying to another folder.
seOpenToMove	0x0040	Additional processing is required on the Message object when moving to another folder.
seOpenForCtxMenu	0x0100	Additional processing is required on the Message object when displaying verbs to the end-user.
seCannotUndoDelete	0x0400	Cannot undo delete operation, MUST NOT be set unless "0x0001" is set
seCannotUndoCopy	0x0800	Cannot undo copy operation, MUST NOT be set unless "0x0020" is set
seCannotUndoMove	0x1000	Cannot undo move operation, MUST NOT be set unless "0x0040" is set
seHasScript	0x2000	The Message object contains end-user script.

seOpenToPermDelete	0x4000	Additional processing is required to permanently delete the Message object.
--------------------	--------	---

2.2.1.17 **PidNameKeywords**

Type: **PtypMultiString**

Contains keywords or categories for the **Message object**. The length of each string within the multi-valued string MUST be less than 256.

2.2.1.18 **PidLidCommonStart**

Type: **PtypTime**

Indicates the start time for the **Message object**. MUST be less than or equal to the value of **PidLidCommonEnd**. This time is interpreted as UTC or local depending on the specification of an extension to this protocol.

2.2.1.19 **PidLidCommonEnd**

Type: **PtypTime**

Indicates the end time for the **Message object**. MUST be greater than or equal to the value of **PidLidCommonStart**. This time is interpreted as UTC or local depending on the specification of an extension to this protocol.

2.2.1.20 **Body Properties**

A group of related properties valid on any **Message object** that specify the body text format and contents and conform to the specification in [MS-OXBBODY].

2.2.1.20.1 **PidTagBody**

Type: **PtypString**

Contains the unformatted text analogous to the text/plain body of [RFC2822].

2.2.1.20.2 **PidTagBodyHtml**

Type: **PtypBinary**

Contains the HTML body as specified in [RFC2822].

2.2.1.20.3 **PidTagRtfCompressed**

Type: **PtypBinary**

Contains a Rich Text Format (RTF) body compressed as specified in [MS-OXRTFCP].

2.2.1.20.4 **PidTagRtfInSync**

Type: **PtypBoolean**

Indicates whether the RTF body has been synchronized with the contents in **PidTagBody**.

2.2.1.20.5 **PidTagInternetCodepage**

Type: **PtypInteger32**

Indicates the **code page** used for **PidTagBody** or **PidTagBodyHtml**.

2.2.1.21 **Contact Linking Properties**

A group of related properties valid on any **Message object** containing information about the linked **Contact objects**.

2.2.1.21.1 **PidLidContactLinkEntry**

Type: **PtypBinary**

Contains the list of **Address Book EntryIDs** linked to by this **Message object**.

Size in bytes	Meaning	Notes
4	Address Entry Count	
4	Size of this property minus 4 (FieldSize)	
variable	Address Book EntryID data	Repeats Address Entry Count times
0 – 3	Padding to make FieldSize a multiple of 4	Each padding BYTE MUST be 0x00.

2.2.1.21.2 **PidLidContacts**

Type: **PtypMultiString**

Contains the **PidTagDisplayName** of each Address Book **EntryID** referenced in the value of **PidLidContactLinkEntry**. MAY also include names not referenced in **PidLidContactLinkEntry**.

2.2.1.21.3 **PidLidContactLinkName**

Type: **PtypString**

Contains the elements of **PidLidContacts**, separated by a semicolon and a space ("; ").

2.2.1.21.4 **PidLidContactLinkSearchKey**

Type: **PtypBinary**

Contains the list of SearchKeys for the **Contact object** linked to by this **Message object**.

Length in bytes	Meaning	Notes
2	ContactEntryCount	
variable	SearchKey data	Repeats ContactEntryCount times

2.2.2 Attachment Object Properties

2.2.2.1 General Properties

The following properties exist on any **Attachment object**. These properties **MUST** be set by the server and are read-only for the client. For specifications of these properties see [MS-OXPRPT].

PidTagAccessLevel
PidTagObjectType

PidTagRecordKey

2.2.2.2 PidTagLastModificationTime

Type: **PtypTime**, in UTC

Indicates the last time the file referenced by the **Attachment object** was modified, or the last time the Attachment object itself was modified.

2.2.2.3 PidTagCreationTime

Type: **PtypTime**, in UTC

Indicates the time the file referenced by the **Attachment object** was created, or the time the Attachment object itself was created.

2.2.2.4 PidTagDisplayName

Type: **PtypString**

Contains the name of the attachment as input by the end user. **MUST** be set to the same as **PidTagAttachLongFilename**.

2.2.2.5 PidTagAttachSize

Type: **PtypInteger32**, unsigned

Contains the size in **bytes** consumed by the **Attachment object** on the server. This property is read-only for the client.

2.2.2.6 PidTagAttachNumber

Type: **PtypInteger32**, unsigned

Identifies the **Attachment object** within its **Message object**. **MUST** be unique among the Attachment objects in a message.

2.2.2.7 PidTagAttachDataBinary

Type: **PtypBinary**

Contains the contents of the file to be attached.

2.2.2.8 PidTagAttachDataObject

Type: **PtypObject**

Contains the binary representation of the **Attachment object** in an application-specific format.

2.2.2.9 PidTagAttachMethod

Type: **PtypInteger32**

Represents the way the contents of an attachment are accessed. MUST be one of the following values.

Name	Value	Description
afNone	0x00000000	The attachment has just been created.
afByValue	0x00000001	PidTagAttachDataBinary contains the attachment data.
afByReference	0x00000002	PidTagAttachLongPathname contains a fully qualified path identifying the attachment to recipients with access to a common file server.
afByReferenceOnly	0x00000004	PidTagAttachLongPathname contains a fully qualified path identifying the attachment.
afEmbeddedMessage	0x00000005	The attachment is an embedded message that must be accessed via RopOpenEmbeddedMessage
afStorage	0x00000006	PidTagAttachDataObject contains data in an application-specific format.

2.2.2.10 PidTagAttachLongFilename

Type: **PtypString**

Contains the full filename and extension of the **Attachment object**.

2.2.2.11 PidTagAttachFilename

Type: **PtypString**

Contains the **8.3 name** of **PidTagAttachLongFilename**

2.2.2.12 PidTagAttachExtension

Type: **PtypString**

Contains a filename extension that indicates the document type of an attachment.

2.2.2.13 PidTagAttachLongPathname

Type: **PtypString**

Contains the fully qualified path and filename with extension.

2.2.2.14 PidTagAttachPathname

Type: **PtypString**

Contains the **8.3 name** of **PidTagAttachLongPathname**.

2.2.2.15 PidTagAttachTag

Type: **PtypBinary**

Contains the identifier information for the application which supplied the **Attachment object**'s data. This property MAY be left unset; if set, it MUST be one of the following.

Definition	Data	Comments
TNEF	{0x2A,86,48,86,F7,14,03,0A,01}	See [MS-OXTNEF]
afStorage	{0x2A,86,48,86,F7,14,03,0A,03,02,01}	Data is in an application-specific format.
MIME	{0x2A,86,48,86,F7,14,03,0A,04}	See [MS-OXCMAIL]

2.2.2.16 PidTagRenderingPosition

Type: **PtypInteger32**, unsigned

Represents an offset, in rendered characters, to use when rendering an attachment within the main message text. The value "0xFFFFFFFF" indicates a hidden attachment.

2.2.2.17 PidTagAttachRendering

Type: **PtypBinary**

Contains a Windows **Metafile** as specified in [MS-WMF] for the **Attachment object**.

2.2.2.18 PidTagAttachFlags

Type: **PtypInteger32**, as a bit field

Indicates which body formats might reference this attachment when rendering data. MUST contain a bitwise OR of zero or more of the following flags.

Value	Meaning
0x00000001	The Attachment object is not available to be rendered in HTML.
0x00000002	The Attachment object is not available to be rendered in Rich Text Format.
0x00000004	The Attachment object is referenced and rendered within the HTML body of the associated Message object . See PidTagBodyHtml .

2.2.2.19 PidTagAttachTransportName

Type: **PtypString**.

Contains the name of an attachment file, modified so that it can be correlated with TNEF messages, see [MS-OXTNEF].

2.2.2.20 **PidTagAttachEncoding**

Type: **PtypBinary**

Contains encoding information about the **Attachment object**. MUST be either unset or set to "{0x2A,86,48,86,F7,14,03,0B,01}". This property is used to indicate that the attachment content, which is the value of the **PidTagAttachDataBinary** property, MUST be encoded in the MacBinary format as specified in [MS-OXCMAIL].

2.2.2.21 **PidTagAttachAdditionalInformation**

Type: **PtypString**

MUST be unset if **PidTagAttachEncoding** is unset. MUST be set to ":CREA:TYPE" if **PidTagAttachEncoding** is set.

2.2.2.22 **PidTagAttachmentLinkId**

Type: **PtypInteger32**

The type of **Message object** to which this attachment is linked. MUST be "0x00000000", unless overridden by other protocols that extend the Message and Attachment Object Protocol as noted in section 1.4.

2.2.2.23 **PidTagAttachmentFlags**

Type: **PtypInteger32**

Indicates special handling for this **Attachment object**. MUST be "0x00000000", unless overridden by other protocols that extend the Message and Attachment Object Protocol as noted in section 1.4

2.2.2.24 **PidTagAttachmentHidden**

Type: **PtypBoolean**

Indicates whether this **Attachment object** is hidden from the end user.

2.2.2.25 **MIME properties**

The following properties contain **MIME** information and MAY be left unset. For MIME specifications, see [RFC2045]. For the specification on mapping these properties, see [MS-OXCMAIL].

Type	Property	Content
PtypString	PidTagAttachMimeTag	The content-type MIME header
PtypString	PidTagAttachContentId	A content identifier unique to this Message

		object that matches a corresponding "cid:" URI scheme reference in the HTML body of the Message object
PtypString	PidTagAttachContentLocation	A relative or full URI that matches a corresponding reference in the HTML body of the Message object
PtypString	PidTagAttachContentBase	The base of a relative URI. MUST be set if PidTagAttachContentLocation contains a relative URI.

2.2.3 Message Object ROPS

The following sections specify the format of the **ROP request buffers** specific to the Message and Attachment Object Protocol. Before sending these requests to the server, the client has logged on to the server, and acquired a **handle** to the **Message object** or **Folder object** used in the ROP request.

2.2.3.1 RopOpenMessage Buffer Format

RopOpenMessage provides access to an existing **Message object**, which is identified by the **MID**. The folder containing the Message object is identified by the **FID**.

For this ROP, the **InputHandleIndex** is either a **Store object** or a **Folder object**. If a folder is used, it is not necessary that it is the parent folder, only that it is a folder within the same Store. The **OutputHandleIndex** is a Message object.

When the server receives multiple requests to open the same Message object, it returns a different **handle** and maintains a separate transaction for each.

2.2.3.1.1 Request Buffer

The syntax of the **RopOpenMessage** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopOpenMessage** request buffer.

2.2.3.1.1.1 CodePageId

2-bytes specifying the **code page** in which the non-**Unicode** representation of the strings on this **Message object** are encoded. A value of 0x0FFF means that the code page of the Logon object is used.

2.2.3.1.1.2 FolderId

8-bytes containing the **FID** of the folder from which the message is to be opened.

2.2.3.1.1.3 OpenModeFlag

1-byte; **MUST** be one of the following.

Name	Value	Meaning
ReadOnly	0x00	Message will be opened as read only.
ReadWrite	0x01	Message will be opened for both reading and writing.
BestAccess	0x03	Open for read/write if possible, read-only if not.
OpenSoftDeleted	0x04	Open a soft deleted Message object if available.

2.2.3.1.1.4 MessageId

8-bytes containing the **MID** for the **Message object** to open.

2.2.3.1.2 Response Buffer

The syntax of the **RopOpenMessage** response buffer is specified in the [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopOpenMessage** response buffer.

2.2.3.1.2.1 HasNamedProperties

1-byte.

Value	Meaning
0x00	No named properties are included in the ROP Response Buffer .
non-zero	Named properties are included.

2.2.3.1.2.2 SubjectPrefix

A **TypedString** structure specifying the prefix for the subject of the **Message object**. **MUST** be the value of the **PidTagSubjectPrefix** property.

2.2.3.1.2.3 NormalizedSubject

A **TypedString** structure specifying the normalized subject of the **Message object**. **MUST** be the value of the **PidTagNormalizedSubject** property.

2.2.3.1.2.4 RecipientCount

A 2-BYTE unsigned **integer** containing the number of recipients associated with the **Message object**.

2.2.3.1.2.5 ColumnCount

A 2-BYTE unsigned integer containing the number of elements in the **RecipientColumns** field.

2.2.3.1.2.6 RecipientColumns

An array of **PropertyTag** structures with **ColumnCount** elements. Each element is valid for a Recipient as specified in [MS-OXPROPS].

2.2.3.1.2.7 RowCount

A 1-BYTE unsigned integer containing the number of rows in the **RecipientRows** field. The value MUST be less than or equal to **RecipientCount**.

2.2.3.1.2.8 RecipientRows

An array of **OpenRecipientRow** structures with **RowCount** elements.

Element	Type	Size in bytes	Description
Recipient Type	Byte	1	See Recipient Type , below.
CodePageId	Integer	2	The code page in which the non-Unicode representation of the strings in the Recipient Data are encoded.
Reserved	Integer	2	MUST be "0x0000"
RecipientRowSize	Integer	2	The total number of bytes in the following RecipientRow .
RecipientRow	RecipientRow	RecipientRowSize	See [MS-OXCDATA].

A Recipient Type is a bitwise OR of one value from the Types **table** with zero or more values from the Flags table.

Types are as follows.

Value	Description
0x01	Primary recipient.
0x02	CC recipient.
0x03	BCC recipient.

Flags are as follows.

Value	Description
0x10	When resending a previous failure this flag indicates that this recipient did not successfully receive the message on the previous attempt.
0x80	When resending a previous failure this flag indicates that this recipient did successfully receive the message on the previous attempt.

2.2.3.2 RopCreateMessage Buffer Format

RopCreateMessage is used to create a new **Message object**.

For this ROP, the **InputHandleIndex** is a Folder or Logon object and the **OutputHandleIndex** is a Message object.

2.2.3.2.1 Request Buffer

The syntax of the **RopCreateMessage** request buffer is specified in the [MS-OXCROPS]. The fields specified in the following sub-sections are part of the **RopCreateMessage** request buffer.

2.2.3.2.1.1 CodePageId

2-bytes specifying the **code page** that the non-**Unicode** representation of the strings on this **Message object** are to be encoded; a value of "0x0FFF" means that the code page of the Logon object is used.

2.2.3.2.1.2 FolderId

8-bytes containing the **FID** for the **Folder object** in which the **Message object** is to be created.

2.2.3.2.1.3 AssociatedFlag

1-byte.

Value	Meaning
0x00	Not an FAI Message
non-zero	Is an FAI Message

2.2.3.2.2 Response Buffer

The syntax of the **RopCreateMessage** response buffer is specified in the [MS-OXCROPS]. The fields specified in the following sub-sections are part of the **RopCreateMessage** response buffer.

2.2.3.2.2.1 HasMessageId

1-byte.

Value	Meaning
0x00	This is the last byte in the buffer.
non-zero	MessageId follows beginning with the next byte in the buffer.

2.2.3.2.2.2 MessageId

8-bytes containing the **MID** for the newly created **Message object**;

2.2.3.3 RopSaveChangesMessageBuffer Format

RopSaveChangesMessage commits the changes made to the **Message object**.

For this ROP, the **ResponseHandleIndex** is the containing **Folder object** or, for an embedded message, the **Embedded Message object**. The **InputHandleIndex** is a Message object.

When the server receives multiple requests to open the same Message object, it returns a different **handle** and maintains a separate transaction for each. Any changes made on one transaction **MUST NOT** be visible to another transaction until the changes are committed via **RopSaveChangesMessage**. Once a transaction on one handle has been committed, the server **MUST** return **ecObjectModified** for **RopSaveChangesMessage** requests on other handles and **MUST NOT** allow those transactions to be committed, unless the client instructs the server to override previous changes with the **ForceSave** flag from section 2.2.3.3.1.1.

2.2.3.3.1 Request Buffer

The syntax of the **RopSaveChangesMessage** request buffer is specified in the [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSaveChangesMessage** request buffer.

2.2.3.3.1.1 SaveFlags

1-byte indicating the server save behavior; **MUST** be one value from the following table.

SaveType

Name	Value	Description
KeepOpenReadOnly	0x09	The client requests that the server commit the changes. The server MUST either return an error and leave the Message object open with unchanged access level, or return a success code and keep the Message object open with read only access.
KeepOpenReadWrite	0x0A	The client requests that the server commit the changes. The server MUST either return an error and leave the Message object open with unchanged access level, or return a success code and keep the Message object open with read/write access.
ForceSave	0x0C	The client requests that the server commit the changes. The server MUST either return an error and leave the Message object open with unchanged access level, or return a success code and keep the Message object open with read/write access. The ecObjectModified error code is not valid when this flag is set: the server overwrites any changes instead.

2.2.3.3.2 Response Buffer

The syntax of the **RopSaveChangesMessage** response buffer is specified in the [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSaveChangesMessage** response buffer.

2.2.3.3.2.1 Message Id

8-bytes containing the **MID** for the saved **Message object**.

2.2.3.4 **RopRemoveAllRecipients Buffer Format**

The client sends the **RopRemoveAllRecipients** request to delete all recipients from a message.

For this **ROP** the **InputHandleIndex** is a Message object.

2.2.3.4.1 **Request Buffer**

The syntax of the **RopRemoveAllRecipients** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopRemoveAllRecipients** request buffer.

2.2.3.4.1.1 **Reserved**

4-bytes; unspecified value.

2.2.3.4.2 **Response Buffer**

The syntax of the **RopRemoveAllRecipients** response buffer is specified in [MS-OXCROPS].

This protocol adds no additional field information to the **RopRemoveAllRecipients** response buffer.

2.2.3.5 **RopModifyRecipients Buffer Format**

RopModifyRecipients modifies recipients associated with the **Message object**.

For this **ROP** the **InputHandleIndex** is a Message object.

2.2.3.5.1 **Request Buffer**

The syntax of the **RopModifyRecipients** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopModifyRecipients** request buffer.

2.2.3.5.1.1 **ColumnCount**

2-bytes containing the number of elements in the **RecipientColumns** field. MUST be greater than or equal to "0x0000" and less than "0x7FEF".

2.2.3.5.1.2 **RecipientColumns**

An array of **PropertyTag** structures with **ColumnCount** elements. Each element is valid for a Recipient as specified in [MS-OXPROPS]. The client MUST NOT include **property tags**

for any properties that are part of an unextended **RecipientRow**, as specified in [MS-OXCADATA]:

PidTagAddressType	PidTagDisplayName
PidTagEmailAddress	PidTagEntryId
PidTagInstanceKey	PidTagRecipientType
PidTagSearchKey	PidTagSendRichInfo
PidTagTransmittableDisplayName	

2.2.3.5.1.3 **RowCount**

2-bytes containing the number of elements in the **RecipientRows** field. MUST be greater than or equal to "0x0000" and less than "0x7FEF".

2.2.3.5.1.4 **RecipientRows**

An array of **ModifyRecipientRow** structures with **RowCount** elements.

Element	Type	Size in bytes	Description
RowId	Integer	4	Row Identifier
RecipientType	Byte	1	See Recipient Type in section 2.2.3.1.2.8
RecipientRowSize	Integer	2	The total number of bytes in the RecipientRow that follows.
RecipientRow	RecipientRow	RecipientRowSize	See [MS-OXCADATA].

2.2.3.5.2 **Response Buffer**

The syntax of the **RopModifyRecipients** response buffer is specified in [MS-OXCROPS].

This protocol adds no additional field information to the **RopModifyRecipients** response buffer.

2.2.3.6 **RopReadRecipients Buffer Format**

RopReadRecipients retrieves the recipients associated with the **Message object**.

For this ROP, the **InputHandleIndex** is a Message object.

2.2.3.6.1 **Request Buffer**

The syntax of the **RopReadRecipients** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopReadRecipients** request buffer.

2.2.3.6.1.1 **RowId**

4-bytes containing the starting index for the recipients to be retrieved.

2.2.3.6.1.2 **Reserved**

2-bytes; MUST be 0x0000.

2.2.3.6.2 **Response Buffer**

The syntax of the **RopReadRecipients** response buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopReadRecipients** response buffer.

2.2.3.6.2.1 **RowCount**

2-bytes containing the number of elements in the **RecipientRows** field. MUST be greater than or equal " 0x0000" and less than "0x7FEF".

2.2.3.6.2.2 **RecipientRows**

An array of **ReadRecipientRow** structures with **RowCount** elements.

Element	Type	Size	Description
RowId	Integer	4	Index into the recipient list
Recipient Type	Byte	1	See Recipient Type in Section 2.2.3.1.2.8
CodePageId	Integer	2	The code page that the non- Unicode representation of the strings in the RecipientData are encoded.
Reserved	n/a	2	MUST be "0x0000"
RecipientRowSize	Integer	2	The total number of bytes in the RecipientRow .
RecipientRow	RecipientRow	RecipientRowSize	See [MS-OXCADATA].

2.2.3.7 **RopReloadCachedInformation Buffer Format**

RopReloadCachedInformation retrieves the same information as **RopOpenMessage** but operates on an already opened **Message object**.

For this **ROP** the **InputHandleIndex** is a Message object.

2.2.3.7.1 **Request Buffer**

The syntax of the **RopReloadCachedInformation** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopReloadCachedInformation** request buffer.

2.2.3.7.1.1 **Reserved**

2-bytes; MUST be "0x0000".

2.2.3.7.2 Response Buffer

The response buffer for **RopReloadCachedInformation** is identical to the response buffer for **RopOpenMessage**.

2.2.3.8 RopSetMessageStatus Buffer Format

RopSetMessageStatus sets **PidTagMessageStatus** on a message in a folder without the need to open or save the **Message object**.

For this **ROP** the **InputHandleIndex** is a **Folder object**.

2.2.3.8.1 Request Buffer

The syntax of the **RopSetMessageStatus** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSetMessageStatus** request buffer.

2.2.3.8.1.1 MessageId

8-bytes containing the **MID** for the **Message object** to modify.

2.2.3.8.1.2 MessageStatusFlags

4-bytes containing the **PidTagMessageStatus**.

2.2.3.8.1.3 MessageStatusMask

4-bytes indicating which status flags are to be set and which are to be cleared. MUST contain a bitwise OR of zero or more values from table in section 2.2.1.8. The server sets all flags that are set in both **MessageStatusMask** and **MessageStatusFlags**, and clears all flags that are set in **MessageStatusMask** but clear in **MessageStatusFlags**.

2.2.3.8.2 Response Buffer

The syntax of the **RopSetMessageStatus** response buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSetMessageStatus** response buffer.

2.2.3.8.2.1 MessageStatusFlags

4-bytes indicating the status flags that were set on the **Message object** prior to processing this request. MUST contain a bitwise OR of zero or more values from the table in Section

2.2.3.8.1.2

2.2.3.9 RopGetMessageStatusBuffer Format

RopGetMessageStatus gets the message status of a message in a folder.

For this **ROP** the **InputHandleIndex** is a **Folder object**.

2.2.3.9.1 Request Buffer

The syntax of the **RopGetMessageStatus** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopGetMessageStatus** request buffer.

2.2.3.9.1.1 MessageId

8-bytes containing the **MID** for the **Message object** in which to operate.

2.2.3.9.2 Response Buffer

The syntax of the **RopGetMessageStatus** response buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSetMessageStatus** response buffer.

2.2.3.9.2.1 MessageStatusFlags

4-bytes indicating the status of the **Message object**. MUST contain a bitwise OR of zero or more values from the table in section 2.2.3.8.1.2

2.2.3.10 RopSetReadFlags Buffer Format

RopSetReadFlags changes the state of the **PidTagMessageFlags** property on one or more **Message objects** within a **Folder object**. It also triggers the sending of **read receipts**, as specified in [MS-OXOMSG].

For this **ROP** the **InputHandleIndex** is a **Folder object**.

2.2.3.10.1 Request Buffer

The syntax of the **RopSetReadFlags** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSetReadFlags** request buffer.

2.2.3.10.1.1 WantAsynchronous

1-byte indicating whether client is prepared for the **RopSetReadFlags** request to be processed asynchronously with status reported via **RopProgress**;

If the value is non-zero, the server SHOULD return a **RopAsyncProgress** response, but MAY return a **RopSetReadFlags** response instead. For more details on the asynchronous behavior of ROPs see [MS-OXCROPS].

2.2.3.10.1.2 ReadFlags

1-byte containing a bitwise OR of zero or more values from the following table. The server modifies bits on the **PidTagMessageFlags** property. The flags, **frGenerateReceiptOnly**, **rfsuppressReceipt**, and **rfClearReadFlag**, (**rfClearNotifyRead** OR **rfClearNotifyUnread**), are mutually exclusive.

Name	Value	Description
rfDefault	0x00	The server sets the read flag and sends the receipt.
rfSuppressReceipt	0x01	The user requests that any pending read report be canceled; Server sets mfRead bit.
rfReserved	0x0A	Ignored by the server.
rfClearReadFlag	0x04	Server clears the mfRead bit; Client MUST include rfSuppressReceipt with this flag.
rfGenerateReceiptOnly	0x10	The server sends a read report if one is pending, but does not change the mfRead bit.
rfClearNotifyRead	0x20	The server clears the mfNotifyRead bit, but does not send a read report.
rfClearNotifyUnread	0x40	The server clears the mfNotifyUnread bit, but does not send a non-read report.

2.2.3.10.1.3 MessageIdCount

2-bytes containing the number of elements in the **MessageIds** field.

2.2.3.10.1.4 MessageIds

An array of **MIDs** with **MessageIdCount** elements.

2.2.3.10.2 Response Buffer

The syntax of the **RopSetReadFlags** response buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSetReadFlags** response buffer.

2.2.3.10.2.1 PartialCompletion

1-byte indicating the server was unable to modify one or more of the **Message objects** represented in the **MessageIds** field.

2.2.3.11 RopSetMessageReadFlag

RopSetMessageReadFlag changes the state of the **PidTagMessageFlags** property for the **Message object**. It also triggers the sending of **read receipts**, as specified in [MS-OXOMSG].

In this section, "in public folder mode" means that the logon associated with the **LogonId** from the request was created with the **Private** flag unset (see [MS-OXCSTOR] for more information).

For this **ROP** the **ResponseHandleIndex** is a **Folder object** and the **InputHandleIndex** is a **Message object**.

2.2.3.11.1 Request Buffer

The syntax of the **RopSetMessageReadFlag** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSetMessageReadFlag** request buffer.

2.2.3.11.1.1 ReadFlags

1-byte containing a bitwise OR of one or more values from the table in section 2.2.3.10.1.2

2.2.3.11.1.2 ClientData

24-bytes containing a **LongTermID** (see [MS-OXCADATA]) for the user that is making the **ROP** request when in public folder mode; 0-bytes otherwise.

2.2.3.11.2 Response Buffer

The syntax of the **RopSetMessageReadFlag** response buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSetMessageReadFlag** response buffer.

2.2.3.11.2.1 ReadStatusChanged

1-byte:

Value	Description
0x00	The read status on the Message object was unchanged or the logon is not in public folder mode.
non-zero	The read status on the Message object changed and the logon is in public folder mode.

2.2.3.11.2.2 LogonId

1-byte; containing the **LogonId** from the request when the value in **ReadStatusChanged** is non-zero; 0-bytes otherwise.

2.2.3.11.2.3 ClientData

24-bytes; containing the **ClientData** from the request when the value in **ReadStatusChanged** is non-zero; 0-bytes otherwise.

2.2.3.12 RopOpenAttachment

RopOpenAttachment opens an **Attachment object** stored on the **Message object**.

For this **ROP** the **InputHandleIndex** is a Message object and the **OutputHandleIndex** is an Attachment object.

2.2.3.12.1 Request Buffer

The syntax of the **RopOpenAttachment** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopOpenAttachment** request buffer.

2.2.3.12.1.1 OpenAttachmentFlags

1-byte containing one of the following values.

Name	Value	Meaning
ReadOnly	0x00	Message will be opened as read only.
ReadWrite	0x01	Message will be opened for both reading and writing.
BestAccess	0x03	Open for read/write if possible, read-only if not.

2.2.3.12.1.2 AttachmentID

4-bytes containing the ID of the **Attachment object** to be opened. See **PidTagAttachNumber**.

2.2.3.12.2 Response Buffer

The syntax of the **RopOpenAttachment** response buffer is specified in [MS-OXCROPS].

This protocol adds no additional field information to the **RopOpenAttachment** response buffer.

2.2.3.13 RopCreateAttachment

RopCreateAttachment creates a new **Attachment object** on the **Message object**.

For this **ROP** the **InputHandleIndex** is a Message object and the **OutputHandleIndex** is an Attachment object.

2.2.3.13.1 Request Buffer

The syntax of the **RopCreateAttachment** request buffer is specified in [MS-OXCROPS].

This protocol adds no additional field information to the **RopCreateAttachment** request buffer.

2.2.3.13.2 Response Buffer

The syntax of the **RopCreateAttachment** response buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopCreateAttachment** response buffer.

2.2.3.13.2.1 AttachmentID

4-bytes containing the ID for the **Attachment object** that was created. See **PidTagAttachNumber**.

2.2.3.14 RopDeleteAttachment

RopDeleteAttachment deletes an existing **Attachment object** from the **Message object**. For this ROP, the **InputHandleIndex** is a Message object.

2.2.3.14.1 Request Buffer

The syntax of the **RopDeleteAttachment** request buffer is specified in [MS-OXCROPS]. The fields specified in the following sub-sections are part of the **RopDeleteAttachment** request buffer.

2.2.3.14.1.1 AttachmentID

4-bytes containing the ID of the **Attachment object** to be deleted. See **PidTagAttachNumber**.

2.2.3.14.2 Response Buffer

The syntax of the **RopDeleteAttachment** response buffer is specified in [MS-OXCROPS]. This protocol adds no additional field information to the **RopDeleteAttachment** response buffer.

2.2.3.15 RopSaveChangesAttachment Buffer Format

RopSaveChangesAttachment commits the changes made to the **Attachment object**. For this ROP, the **ResponseHandleIndex** is the containing **Message object** and **InputHandleIndex** is an Attachment object.

2.2.3.15.1 Request Buffer

The syntax of the **RopSaveChangesAttachment** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopSaveChangesAttachment** request buffer.

2.2.3.15.1.1 SaveFlags

See section 2.2.3.3.1.1.

2.2.3.15.1.2 Response Buffer

The syntax of the **RopSaveAttachmentChanges** response buffer is specified in [MS-OXCROPS].

This protocol adds no additional field information to the **RopSaveAttachmentChanges** response buffer.

2.2.3.16 RopOpenEmbeddedMessage Buffer Format

RopOpenEmbeddedMessage retrieves a **handle** to a **Message object** from the given **Attachment object**.

For this **ROP** the **InputHandleIndex** is an Attachment object and the **OutputHandleIndex** is a Message object.

2.2.3.16.1 Request Buffer

The syntax of the **RopOpenEmbeddedMessage** request buffer is specified in [MS-OXCROPS]. The fields specified in the following sub-sections are part of the **RopOpenEmbeddedMessage** request buffer.

2.2.3.16.1.1 CodePageId

2-bytes specifying the **code page** in which the non-**Unicode** representation of the strings on this **Message object** MUST be encoded.

2.2.3.16.1.2 OpenModeFlags

1-byte.

Name	Value	Meaning
ReadOnly	0x00	Message will be opened as read only.
ReadWrite	0x01	Message will be opened for both reading and writing.
Create	0x02	Create the attachment if it does not already exist and open the message for both reading and writing.

2.2.3.16.2 Response Buffer

The syntax of the **RopOpenEmbeddedMessage** response buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopOpenEmbeddedMessage** response buffer.

2.2.3.16.2.1 MessageId

8-byteS containing the **MID** for the **Message object**.

2.2.3.16.2.2 HasNamedProperties

See section 2.2.3.1.2.1

2.2.3.16.2.3 **Subject Prefix**

See section 2.2.3.1.2.2.

2.2.3.16.2.4 **NormalizedSubject**

See section 2.2.3.1.2.3.

2.2.3.16.2.5 **RecipientCount**

See section 2.2.3.1.2.4.

2.2.3.16.2.6 **ColumnCount**

See section 2.2.3.1.2.5.

2.2.3.16.2.7 **RecipientColumns**

See section 2.2.3.1.2.6.

2.2.3.16.2.8 **RowCount**

See section 2.2.3.1.2.7.

2.2.3.16.2.9 **RecipientRows**

See section 2.2.3.1.2.8.

2.2.3.17 **RopGetAttachmentTable Buffer Format**

RopGetAttachmentTable retrieves a **handle** to a **table** object that represents the attachments stored on the **Message object**. See [MS-OXCTABL] for more information on table objects.

For this **ROP** the **InputHandleIndex** is a Message object and the **OutputHandleIndex** is a table object.

2.2.3.17.1 **Request Buffer**

The syntax of the **RopGetAttachmentTable** request buffer is specified in [MS-OXCROPS].

The fields specified in the following sub-sections are part of the **RopGetAttachmentTable** request buffer.

2.2.3.17.1.1 **Table Flags**

1-byte.

Name	Value	Description
Standard	0x00	Open the table .
Unicode	0x40	Open the table. Also requests that the columns containing string data

Name	Value	Description
		be returned in Unicode format.

2.2.3.17.2 Response Buffer

The syntax of the **RopGetAttachmentTable** response buffer is specified in [MS-OXCROPS].

This protocol adds no additional field information to the **RopGetAttachmentTable** response buffer.

3 Protocol Details

3.1 Client Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

3.1.1.1 Linking a Contact Object

To link a **Contact object** with another **Message object**, the client sets the following properties. See section 2.2.1.20 for more details.

- **PidLidContactLinkEntry**
- **PidLidContactLinkName**
- **PidLidContactLinkSearchKey**
- **PidLidContacts**

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

3.1.4.1 Opening a Message Object

When a higher layer needs to obtain a **handle** to an existing **Message object** the client sends a **RopOpenMessage** request. In order to send this request, the client first obtains the **MID** for the Message object to be opened, and either the **FID** or the **LogonID**. The MID is accessible

from the **contents table** of the **Folder object** that contains the Message object by including **PidTagMid** in a **RopSetColumns** request. For more details, see [MS-OXCTABL].

To open a **soft deleted Message object**, the client MUST include **OpenSoftDeleted** in the **OpenModeFlag** field.

When the client receives the response buffer, it caches the data from the **NormalizedSubject** and **SubjectPrefix** fields; it also updates the cache when issuing **RopSetProperties** for **PidTagNormalizedSubject** and **PidTagSubjectPrefix** and uses the cached values.

The client uses the opened Message object in subsequent **ROPs**; it MUST eventually send a **RopRelease** request on the Message object, and after doing so, MUST NOT use the Message object for any subsequent ROPs.

The client is responsible for maintaining the privacy of the properties on the Message object when **PidLidPrivate** is set to "0x01".

3.1.4.2 Creating a Message Object

When a higher layer needs to create a new **Message object**, the client sends a **RopCreateMessage** request. The client sends a **RopSaveChangesMessage** request to commit the new Message object, and uses the opened Message object in subsequent ROPs. It MUST eventually send a **RopRelease** request on the Message object and after doing so MUST NOT use the Message object for any subsequent ROPs.

3.1.4.3 Saving Message Object Changes

When a higher layer wants to save all the changes to a **Message object**, the client sends a **RopSaveChangesMessage** request.

The client controls the access level of the Message object **handle** after saving changes by setting the proper flags as specified in section 2.2.3.3.1.1.

3.1.4.4 Removing All Recipients

When a higher layer wants to clear all recipients from a **Message object**, the client sends a **RopRemoveAllRecipients** request.

The client sends a **RopSaveChangesMessage** for the Message object associated with the removed recipients in order to commit the changes.

3.1.4.5 Adding, Deleting, and Modifying Recipients

When a higher layer wants to modify recipients of the **Message object**, the client sends a **RopModifyRecipients** request.

To modify an existing recipient the client sets the **RowId** field to the **RowId** of the recipient to be modified and sets all of the **ModifyRecipientRow** data to the desired values for that recipient, including any additional property information for the recipients. Additional property

information is set by adding **PropertyTag** values to the **RecipientColumns** field and including the property values in the **RecipientProperties** field.

To delete an existing recipient the client sets the **RowId** field to the **RowId** of the recipient to be deleted and sets the **RecipientRowSize** field to "0x0000".

To add a new recipient the client sets the **RowId** field to a value greater than the largest **RowId** for any recipient that already exists on the Message object. The client sets all of the **ModifyRecipientRow** data to the desired values for that recipient, including any additional property information.

The client sends a **RopSaveChangesMessage** for the Message object associated with the added recipients in order to commit the changes.

3.1.4.6 Reading Recipients

When a higher layer want a list of all recipients on the **Message object**, the client sends a **RopReadRecipients** request.

If the count of recipients and the count of recipient rows in the **RopOpenMessage** response buffer are the same, then the client uses the **RecipientRow** information from **RopOpenMessage** instead of sending a **RopReadRecipients** request. If the counts are not equal then the response buffers for a series of **RopReadRecipients** contain all the recipients associated with the Message object including those returned in the **RopOpenMessage** response buffer.

A client accesses the information for all recipients in the message by setting the **RowId** field to "0x0000", and then iteratively sending **RopReadRecipients** with an increasing **RowId** value to obtain the recipients that did not fit in the previous request.

3.1.4.7 Reload Message Object Header Info

When a higher layer wants to retrieve the current state of the data returned in **RopOpenMessage** then the client sends a **RopReloadCachedInformation** request.

3.1.4.8 Setting Message Status

When a higher layer is working with a **header Message object** and wants to change its status, (mark or unmark the header Message object for download or delete), the client sends a **RopSetMessageStatus** request.

To modify the status of a header Message object:

1. Obtain the message's **MID**, see section 3.1.4.1.
2. Send the **RopSetMessageStatus** request, setting the mask and status appropriately.

3.1.4.9 Getting Message Status

When a higher layer is working with a **header Message object** and wants to check its status, the client sends a **RopGetMessageStatus** request.

To retrieve the status of a header Message object:

1. Obtain the message's **MID**, see section 3.1.4.1.
2. Sent the **RopGetMessageStatus** request; if the request succeeds then the header Message object's **PidTagMessageStatus** value is returned in the response buffer.

3.1.4.10 Setting Message Object Read State

When a higher layer wants to mark one or more **Message objects** as read or unread without opening the **Message objects**, the client sends a **RopSetReadFlags** request. The client obtains a list of **MIDs** using a **contents table**; see section 3.1.4.1, and uses the list of **MIDs** in the **RopSetReadFlags** request.

When a higher layer wants to mark or unmark a single opened Message object as read, the client sends a **RopSetMessageReadFlag** request.

The client controls whether the Message object is marked as read or unread, as well as the sending of **read receipts** by setting the appropriate flags as specified in section 2.2.3.10.1.2.

3.1.4.11 Opening Attachments

When a higher layer wants to open and manipulate an existing **Attachment object** to a **Message object**, the client sends a **RopOpenAttachment** request.

The client **MUST** use a valid **AttachmentID**, see section 2.2.3.12.1.2, when requesting to open an attachment. See section 3.1.4.16.

The client uses the opened Attachment object in subsequent ROPs. It **MUST** eventually send a **RopRelease** request on the Attachment object and after doing so, **MUST NOT** use the Attachment object for any subsequent ROPs.

3.1.4.12 Creating Attachments

When a higher layer wants to add a new **Attachment object** to a **Message object**, the client sends a **RopCreateAttachment** request.

The client sends a **RopSaveChangesAttachment** request to commit the new Attachment object, and uses the newly created Attachment object in subsequent ROPs. The client **MUST** eventually send a **RopRelease** request on the Attachment object and after doing so, **MUST NOT** use the Attachment object for any subsequent ROPs.

The client sends a **RopSaveChangesMessage** request to commit the Attachment object change to the Message object.

3.1.4.13 Setting Attachment Object Content

When a higher layer wants to add the contents of a file to an **Attachment object**, the client sends a **RopSetProperties** request as specified in [MS-OXCPRPT].

Depending on the type of Attachment object the higher layer intends to use, the client sets the appropriate value for **PidTagAttachMethod** and sets the properties as specified in section 2.2.2.

The client sends a **RopSaveChangesAttachment** request to commit the change to the Attachment object and a **RopSaveChangesMessage** request to commit the Attachment object change to the **Message object**.

3.1.4.14 Saving Attachment Object Changes

When a higher layer wants to save changes to an **Attachment object**, the client sends a **RopSaveChangesAttachment** request. It sends a **RopSaveChangesMessage** request to commit the Attachment object changes to the **Message object**.

3.1.4.15 Opening an Embedded Message Object

When a higher layer wants to open an existing **Attachment object** and access and manipulate it as if it were a **Message object**, the client sends a **RopOpenEmbeddedMessage** request.

The client uses the opened Message object in subsequent ROPs; it **MUST** eventually send a **RopRelease** request on the Message object and after doing so, **MUST NOT** use the Message object for any subsequent ROPs.

3.1.4.16 Accessing the Attachments Table

When a higher layer wants to retrieve information about all **Attachment objects** associated with a **Message object** without opening each Attachment object, the client sends a **RopGetAttachmentTable** request.

The server returns a **table** of properties for each Attachment object associated with the Message object as specified in [MS-OXCTBL]. To retrieve the **AttachmentID**, the client includes **PidTagAttachNumber** when sending a **RopSetColumns** request.

3.1.4.17 Creating an Embedded Message

When a higher layer wants to create an embedded message, the client sends a **RopCreateAttachment** to create an attachment on a message. The client uses **RopSetProperties** to set the value of **PidTagAttachMethod** to **afEmbeddedMessage**. Finally the client sends a **RopOpenEmbeddedMessage** on the attachment to get a **Message object handle**.

3.1.4.18 Saving an Embedded Message

When a higher layer wants to save an embedded message, the client sends a **RopSaveChangesMessage** on the embedded message. Then the client sends a **RopSaveChangesAttachment** on the attachment from which the embedded message was opened. Finally, the client sends a **RopSaveChangesMessage** on the enclosing message.

3.1.5 Message Processing Events and Sequencing Rules

None.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Server Details

3.2.1 Abstract Data Model

None.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

3.2.4.1 RopOpenMessage

Provides access to existing **Message objects** stored by the server. The Message object returned by this **ROP** is used in subsequent ROPs, such as **RopGetPropertiesSpecific**. See specific ROPs for information of which operate on **Message objects**, as specified in [MS-OXCROPS].

RopOpenMessage MUST NOT succeed if a Message object with the specified ID does not exist or the client has insufficient access rights to view the Message object.

If the **OpenMode** field includes the **OpenSoftDeleted flag**, then **RopOpenMessage** provides access to all **Message objects**, including **soft deleted Message objects**. If **OpenSoftDeleted** is not included, then the server MUST NOT provide access to soft deleted **Message objects**.

The response field **RecipientCount** indicates the current number of recipients in the message. In addition, the server returns data for as many recipients as will fit in the response buffer, in order of **RowId** value. The data for each recipient is encoded as an **OpenRecipientRow** structure in the **RecipientRows** field. The response field **RowCount** indicates how many recipients are present in **RecipientRows**.

The following are specific error codes which apply to this ROP.

Name	Value	Meaning
ecNotFound	0x8004010F	The MID does not correspond to a message in the database.

Name	Value	Meaning
		The user does not have rights to the message. The message is soft deleted and the caller has not specified the OpenSoftDeleted flag as part of the OpenMode field.
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a folder or logon object.

3.2.4.2 RopCreateMessage

Creates a new **Message object** on the server and provides access to it by returning a Message object **handle** for use in subsequent ROPs. The server **MUST NOT** commit the new Message object until it receives a **RopSaveChangesMessage** request.

The server **MUST** initialize the following properties before responding.

Property Name	Initial Data
PidTagImportance	"0x00000001"
PidTagMessageClass	"IPM.Note"
PidTagSensitivity	"0x00000000"
PidTagDisplayBcc	""
PidTagDisplayCc	""
PidTagDisplayTo	""
PidTagMessageFlags	"0x00000009"
PidTagMessageSize	Calculated based on the data
PidTagHasAttachments	"0x00"
PidTagSecurityDescriptor	See PidTagSecurityDescriptor
PidTagUrlCompNameSet	"0x00"
PidTagTrustSender	"0x00000001"
PidTagAccess	"0x00000003"
PidTagAccessLevel	"0x00000001"
PidTagUrlCompName	"No Subject.EML"
PidTagCreationTime	Time RopCreateMessage was processed
PidTagLastModificationTime	Same as PidTagCreationTime
PidTagSearchKey	Server generated SearchKey .
PidTagMessageLocaleId	The logon object LocaleID .
PidTagCreatorName	Name of the creator.
PidTagCreatorEntryId	Address Book EntryID of the creator
PidTagLastModifierName	Same as PidTagCreatorName
PidTagLastModifierEntryId	Same as PidTagCreatorEntryId
PidTagHasNamedProperties	"0x00"
PidTagLocaleId	Same as PidTagMessageLocaleId
PidTagLocalCommitTime	Same as PidTagCreationTime

The following specific error code applies to this ROP.

Name	Value	Meaning
ecAccessDenied	0x80000009	The user does not have permissions to create this message.

3.2.4.3 RopSaveChangesMessage

Commits the changes made to a **Message object** on the server. The status of the Message object after the commit is determined by the value of the **SaveFlags** as documented in section 2.2.3.3.1.1.

The response contains the message identifier of the committed message.

The following specific error code applies to this ROP.

Name	Value	Meaning
ecNotSupported	0x80040102	The values of the SaveFlags are not a supported combination as documented in section 2.2.3.3.1.1.
ecObjectModified	0x80040109	The underlying data for this Message object was changed through another transaction context.

3.2.4.4 RopRemoveAllRecipients

Removes all the recipients from a **Message object**.

The server ignores the value of Reserved.

Until the server receives a **RopSaveChangesMessage** request from the client, the server adheres to the following:

- The **RowIds** and associated data of removed recipients **MUST NOT** be returned as part of any subsequent handling of ROPs for the opened Message object.
- The changes made to the recipients **MUST NOT** be included in the response buffer returned for **ROP** requests that apply to recipients on Message object **handles**.

The following specific error code applies to this ROP.

Name	Value	Meaning
ecNotSupported	0x80000102	The InputHandleIndex on which this ROP was called does not refer to a Message object.

3.2.4.5 RopModifyRecipients

Modifies the recipients on a **Message object** according to the data in the request buffer. The format of the request buffer is specified in section 2.2.3.5.1.

For each recipient provided the server locates its representation of the recipient based on **RowId**. If the recipient indicated by **RowId** does not exist then the server creates a new recipient with that **RowId** and applies the data from the request.

If the recipient currently exists on the Message object and the value of **RecipientRowSize** in the request buffer is non-zero, the server replaces all existing properties of the recipient with the property values supplied in the request. If the value of **RecipientRowSize** in the request buffer is "0x0000" then the server deletes the recipient from the Message object.

Until the server receives a **RopSaveChangesMessage** request from the client, the server adheres to the following:

- If a recipient was deleted, its **RowId** and associated data **MUST NOT** be returned as part of any subsequent handling of ROPs for the opened Message object.
- Any changes made to the recipients **MUST** be included in the response buffer for any subsequent **ROP** requests that apply to recipients for the same Message object **handle**.
- The changes made to the recipients **MUST NOT** be included in the response buffer returned for ROP requests that apply to recipients on different Message object handles.

The following specific error code applies to this ROP.

Name	Value	Meaning
ecNotSupported	0x80000102	The InputHandleIndex on which this ROP was called does not refer to a Message object.

3.2.4.6 RopReadRecipients

Provides the recipient information for the **Message object** in a tabular form, where each row has information for a single recipient. **RopReadRecipients** is used to obtain information for all recipients in the Message object, regardless of the number of recipients on the message.

The server provides the recipient information starting with the recipient specified by the **RowId** field. If there is a recipient with the given **RowId**, the server provides the information for that recipient and as many recipients as possible, limited by the number of actual recipients in the message and the amount of recipient information that fits in the output buffer.

When **RowId** is "0x0000", the server chooses the first recipient in the message even if its **RowId** does not match. If the message does not have recipients, the server returns **ecNotFound**.

The following specific error codes apply to this ROP.

Name	Value	Meaning
ecNotFound	0x8004010F	Recipient row RowId does not exist on the message.
ecBufferTooSmall	0x0000047D	Unable to fit at least one recipient in the response buffer. See [MS-OXCROPS] for specific handling.
ecNotSupported	0x80000102	The InputHandleIndex on which this ROP was called does not refer to a Message object.

3.2.4.7 RopReloadCachedInformation

Returns the same information as would be returned by **RopOpenMessage**, except that it is updated with the information that has been modified on the **Message object**.

The following specific error code applies to this ROP.

Name	Value	Meaning
ecNotSupported	0x80000102	The InputHandleIndex on which this ROP was called does not refer to a Message object .

3.2.4.8 RopSetMessageStatus

Modifies the **PidTagMessageStatus** property of a single message.

The server modifies the bits on this property specified by the **MessageStatusMask**.

The server immediately commits the changes to the **Message object** as if the **Message object** had been opened and **RopSaveMessageChanges** had been called, except that it only changes **PidTagMessageStatus**, not **PidTagChangeKey**, **PidTagLastModificationTime**, or any other property that is normally modified during **RopSaveChangesMessage**.

The following specific error code applies to this ROP.

Name	Value	Meaning
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Folder object .

3.2.4.9 RopGetMessageStatus

Provides the value of **PidTagMessageStatus** property of a single message; MUST NOT require the **Message object** to be opened.

The following specific error code applies to this ROP.

Name	Value	Meaning
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Folder object .

3.2.4.10 RopSetReadFlags

Modifies the **PidTagMessageFlags** property of several messages.

The server immediately commits the changes to the **Message objects** as if the **Message objects** had been opened and **RopSaveMessageChanges** had been called, except that it only changes **PidTagMessageFlags**, not **PidTagChangeKey**, **PidTagLastModificationTime**, or any other property that is normally modified during **RopSaveChangesMessage**.

If the **WantAsynchronous** flag is non-zero, then the server MAY execute this **ROP** asynchronously. For more information see **RopProgress** in [MS-OXCPRPT].

The following specific error code applies to this ROP.

Name	Value	Meaning
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Folder object .

3.2.4.11 RopSetMessageReadFlag

Modifies the **PidTagMessageFlags** property of a single message.

The server immediately commits the changes to the **Message object** as if the Message object had been opened and **RopSaveMessageChanges** had been called, except that it only changes **PidTagMessageFlags**, not **PidTagChangeKey**, **PidTagLastModificationTime**, or any other property that is normally modified during **RopSaveChangesMessage**.

The following specific error code applies to this **ROP**.

Name	Value	Meaning
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Message object.

3.2.4.12 RopOpenAttachment

Provides access to a single existing **Attachment object**. The handle returned by this **ROP** is used in subsequent ROPs, such as **RopGetPropertiesSpecific**. See specific ROPs for information of which operate on Attachment objects [MS-OXCROPS].

The following specific error codes apply to this ROP.

Name	Value	Meaning
ecNotFound	0x8004010F	The AttachmentID does not correspond to an attachment on the Message object .
ecAccessDenied	0x80000009	The user has insufficient privileges.
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Message object.

3.2.4.13 RopCreateAttachment

Creates a new **Attachment object** and provides a **handle** to it for use in subsequent ROPs.

The server does not commit the new Attachment object until it receives a call to

RopSaveChangesAttachment.

The server **MUST** initialize the following properties before responding.

PropertyName	Initial Data
PidTagAttachNumber	Varies, depending on the number of existing attachments on the Message object .
PidTagAttachSize	"0x00000000 "
PidTagAccessLevel	"0x00000001"
PidTagRenderingPosition	"0x00000000"

PidTagCreationTime	Time RopCreateAttachment was processed.
PidTagLastModificationTime	Same as PidTagCreationTime

The following specific error codes apply to this **ROP**.

Name	Value	Meaning
ecAccessDenied	0x80000009	The user does not have permissions to create an attachment on this message.
ecMaxAttachmentExceeded	0x000004DB	The (server defined) maximum number of attachments for a message has been exceeded.
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Message object.

3.2.4.14 **RopSaveChangesAttachment**

Commits the changes made to an **Attachment object**. The status of the Attachment object after the commit is determined by the values of the **SaveFlags** as documented in section 2.2.3.3.1.1.

Although the server commits any pending changes to the Attachment object in the context of its containing **Message object**, the changes MUST NOT be committed to the database until **RopSaveChangesMessage** has been executed on the **handle** of the Message object.

The following specific error code applies to this **ROP**.

Name	Value	Meaning
ecNotSupported	0x80040102	The value of SaveFlags is not a supported combination as documented in section 2.2.3.3.1.1. The InputHandleIndex on which this ROP was called does not refer to an Attachment object.

3.2.4.15 **RopDeleteAttachment**

Removes an **Attachment object** from a message. The server recalculates **PidTagHasAttachments** during this **ROP**.

The following specific error codes apply to this ROP.

Name	Value	Meaning
ecNotFound	0x8004010F	The AttachmentID does not correspond to an attachment on the Message object .
ecAccessDenied	0x80000009	The user has insufficient privileges.
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Message object.

3.2.4.16 RopOpenEmbeddedMessage

Provides access to an **Embedded Message object** stored in an **Attachment object**. If the Embedded Message object does not exist, the server creates one and initializes its properties as specified in section 3.2.4.2. The returned **handle** is used in subsequent **ROPs** (similar to the one returned by **RopOpenMessage**). The server **MUST NOT** commit the Message object to the containing Attachment object until **RopSaveChangesMessage** is called with the Embedded Message object's handle.

The following specific error codes apply to this ROP.

Name	Value	Meaning
ecAccessDenied	0x80000009	The user does not have permission to open or create this message.
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to an Attachment object.
ecUnknownCodePage	0x000003ef	The code page is unknown

3.2.4.17 RopGetAttachmentTable

Returns a **handle** to a **table** object for use in subsequent **ROPs** as specified in [MS-OXCTBL]. The table object returned allows access to the properties of **Attachment objects**.

The following specific error codes apply to this ROP.

Name	Value	Meaning
ecNotSupported	0x80040102	The InputHandleIndex on which this ROP was called does not refer to a Message object .
ecBusy	0x80040108	The server is too busy to complete the request.

4 Protocol Examples

A user creates a new HTML-format e-mail, sets its subject to "abc123sample" and its body to "This is a sample body text". The user also adds two attachments: an HTML embedded image and a text file, adds a recipient, then saves and closes the message.

4.1 Create Message

The client first creates a new **Message object** by sending a **RopCreateMessage** request.

4.1.1 RopCreateMessage Request Buffer

0000: 06 00 00 01 ff 0f 01 00-00 00 00 f0 79 93 00

RopId: 0x06

LogonIndex: 0x00

HandleIndex: 0x00

MessageHandleIndex: 0x01

CodePageId: 0x0FFF
FolderId: 01 00 00 00 00 00 f0 79 93
AssociatedFlag: 0x00

4.1.2 RopCreateMessage Response Buffer

0000: 06 01 00 00 00 00 00 00
RopId: 0x06
HandleIndex: 0x01
ReturnValue: 0x00000000
HasMessageId: 0x00

4.2 Name to Id Mapping

Before manipulating named properties on **Message objects**, the client needs to ask the server to perform a mapping from the named properties to property identifiers, using **RopGetPropertyIdsFromNames** as specified in [MS-OXCPRPT].

4.3 Get Attachment Table

The client sends a **RopGetAttachmentTable** request to retrieve the attachment **table** for a **Message object**.

4.3.1 RopGetAttachmentTable Request Buffer

0000: 21 00 00 01 00
RopId: 0x21
LogonIndex: 0x00
MessageHandleIndex: 0x00
AttachmentHandleIndex: 0x01
TableFlags: 0x00 (Standard)

4.3.2 RopGetAttachmentTable Response Buffer

0000: 21 01 00 00 00 00
RopId: 0x21
HandleIndex: 0x01
ReturnValue: 0x00000000

4.4 Insert HTML Embedded Image

The client first creates the **Attachment object** on the **Message object**, then sets its properties and commits the changes.

4.4.1 RopCreateAttachment Request Buffer

0000: 23 00 00 01
RopId: 0x23

LogonIndex: 0x00
 HandleIndex: 0x00
 AttachmentHandleIndex: 0x01

4.4.2 RopCreateAttachment Response Buffer

0000: 23 01 00 00 00 00 00 00-00 00
 RopId: 0x23
 HandleIndex: 0x01
 ReturnValue: 0x00000000
 AttachmentID: 0x00000000

4.4.3 Setting Properties

At this point the client uses **RopSetProperties** as specified in [MS-OXCPRPT] to set properties on the **Attachment** objects.

Property tag	Property name	Data
0x37050003	PidTagAttachMethod	"0x00000001"
0x370b0003	PidTagRenderingPosition	"0xFFFFFFFF"
0x7ffd0003	PidTagAttachmentFlags	"0x00000008"
0x3001001f	PidTagDisplayName	"image001.png"
0x3712001f	PidTagAttachContentId	"image001.png@01C86E1C.F1954390"
0x370e001f	PidTagAttachMimeTag	"image/png"
0x7ffa0003	PidTagAttachmentLinkId	"0x00000000"
0x37140003	PidTagAttachFlags	"0x00000004"
0x7ffe000b	PidTagAttachmentHidden	"0x01"
0x3707001f	PidTagAttachLongFilename	"image001.png"
0x3704001f	PidTagAttachFilename	"image001.png"
0x3703001f	PidTagAttachExtension	".png"

To set the contents of the embedded image, the client uses four ROPs, as described in [MS-OXCPRPT].

1. **RopOpenStream** with **PidTagAttachDataBinary**.

2. **RopSetStreamSize** with the size of image file data.
3. **RopWriteStream** request with the actual file contents.
4. **RopRelease** for the **handle** returned from **RopOpenStream**.

4.4.4 RopSaveChangesAttachment Request Buffer

```
0000: 25 00 01 00 02
      RopId: 0x25
      LogonIndex: 0x00
      HandleIndex: 0x01
      AttachmentHandleIndex: 0x00
      SaveFlags: 0x02 (KeepOpenReadWrite)
```

4.4.5 RopSaveChangesAttachment Response Buffer

```
0000: 25 01 00 00 00 00
      RopId: 0x25
      HandleIndex: 0x01
      ReturnValue: 0x00000000
```

4.4.6 Releasing Attachment Object

Finally, the client releases the **Attachment object** by using **RopRelease**. See [MS-OXPRPT].

4.5 Attach Text File

The client first creates the **Attachment object** on the **Message object**, then sets its properties and commits the changes.

4.5.1 RopCreateAttachment Request Buffer

```
0000: 23 00 00 03
      RopId: 0x23
      LogonIndex: 0x00
      HandleIndex: 0x00
      AttachmentHandleIndex: 0x03
```

4.5.2 RopCreateAttachment Response Buffer

```
0000: 23 03 00 00 00 00 01 00-00 00
      RopId: 0x23
      HandleIndex: 0x03
      ReturnValue: 0x00000000
      AttachmentID: 0x00000001
```

4.5.3 Setting Properties

At this point the client uses **RopSetProperties** as specified in [MS-OXCPRPT] to set properties on the **Attachment objects**.

Property tag	Property name	Data
0x37050003	PidTagAttachMethod	"0x00000001"
0x370b0003	PidTagRenderingPosition	"0xFFFFFFFF"
0x7ffd0003	PidTagAttachmentFlags	"0x00000000"
0x3001001f	PidTagDisplayName	"test.txt"
0x7ffa0003	PidTagAttachmentLinkId	"0x00000000"
0x37140003	PidTagAttachFlags	"0x00000000"
0x7ffe000b	PidTagAttachmentHidden	"0x00"
0x3707001f	PidTagAttachLongFilename	"test.txt"
0x3704001f	PidTagAttachFilename	"test.txt"
0x3703001f	PidTagAttachExtension	".txt"
0x30070040	PidTagCreationTime	"2008/02/1222:28:34.636"
0x30080040	PidTagLastModificationTime	"2008/02/1222:28:50.112"
0x37090102	PidTagAttachRendering	3512 Bytes of Windows Metafile

To set the contents of the embedded image, the client uses four ROPs. For more information, see [MS-OXCPRPT].

1. **RopOpenStream** with **PidTagAttachDataBinary**.
2. **RopSetStreamSize** with the size of image file data.
3. **RopWriteStream** request with the actual file contents.
4. **RopRelease** for the **handle** returned from **RopOpenStream**.

4.5.4 RopSaveChangesAttachment Request Buffer

0000: 25 00 02 01 02

RopId: 0x25

LogonIndex: 0x00

HandleIndex: 0x02

AttachmentHandleIndex: 0x01

SaveFlags: 0x02 (**KeepOpenReadWrite**)

4.5.5 RopSaveChangesAttachment Response Buffer

0000: 25 02 00 00 00 00

RopId: 0x25

HandleIndex: 0x02

ReturnValue: 0x00000000

4.5.6 Releasing Attachment Object

Finally, the client releases the **Attachment object** by using **RopRelease**. See [MS-OXPRPT].

4.6 Setting Message Properties

The client sets all the necessary properties using **RopSetProperties** as specified in [MS-OXPRPT].

The HTML body, stored in **PidTagBodyHtml**, is the following:

```
<html>
<head>
<meta http-equiv=Content-Type content="text/html; charset=us-ascii">
</head>
<body lang=EN-US link=blue vlink=purple>
<p>This is a sample body text<o:p></o:p></p>
<p ><o:p></o:p></p>
</div>
</body>
</html>
```

4.7 Adding Recipients

4.7.1 RopModifyRecipients Request Buffer

```
0000: 0e 00 08 0c 00 03 00 fe-0f 03 00 00 39 1f 00 ff
0010: 39 1f 00 fe 39 03 00 71-3a 03 00 05 39 1f 00 f6
0020: 5f 03 00 fd 5f 03 00 ff-5f 03 00 de 5f 03 00 df
0030: 5f 02 01 f7 5f 01 00 00-00 00 00 01 27 01 51 06
0040: 5a 00 55 73 65 72 32 00-75 00 73 00 65 00 72 00
0050: 32 00 00 00 75 00 73 00-65 00 72 00 32 00 00 00
0060: 0c 00 00 06 00 00 00 00-00 00 00 75 00 73 00 65
0070: 00 72 00 32 00 00 00 75-00 73 00 65 00 72 00 32
0080: 00 40 00 73 00 7a 00 66-00 6b 00 75 00 6b 00 2d
0090: 00 64 00 6f 00 6d 00 2e-00 65 00 78 00 74 00 65
00a0: 00 73 00 74 00 2e 00 6d-00 69 00 63 00 72 00 6f
00b0: 00 73 00 6f 00 66 00 74-00 2e 00 63 00 6f 00 6d
00c0: 00 00 00 00 00 00 00 00-00 00 40 75 00 73 00 65
00d0: 00 72 00 32 00 00 00 01-00 00 00 00 00 00 00 00
00e0: 00 00 00 00 00 00 00 7c-00 00 00 00 00 dc a7 40
00f0: c8 c0 42 10 1a b4 b9 08-00 2b 2f e1 82 01 00 00
0100: 00 00 00 00 00 2f 6f 3d-46 69 72 73 74 20 4f 72
0110: 67 61 6e 69 7a 61 74 69-6f 6e 2f 6f 75 3d 45 78
0120: 63 68 61 6e 67 65 20 41-64 6d 69 6e 69 73 74 72
0130: 61 74 69 76 65 20 47 72-6f 75 70 20 28 46 59 44
0140: 49 42 4f 48 46 32 33 53-50 44 4c 54 29 2f 63 6e
0150: 3d 52 65 63 69 70 69 65-6e 74 73 2f 63 6e 3d 75
0160: 73 65 72 32 00
```

RopId: 0x0e

LogonIndex: 0x00

HandleIndex: 0x08

ColumnCount: 0x000c (Count of following **RecipientColumns**)

PidTagObjectType: 0x0ffe0003

PidTagDisplayType: 0x39000003

PidTagAddressBookDisplayNamePrintable: 0x39ff001f

PidTagSmtAddress: 0x39fe001f

PidTagSendInternetEncoding: 0x3a710003
 PidTagDisplayTypeEx: 0x39050003
 PidTagRecipientDisplayName: 0x5fff6001f
 PidTagRecipientFlags: 0x5ffd0003
 PidTagRecipientTrackStatus: 0x5fff0003
 PidTagRecipientResourceState: 0x5fde0003
 PidTagRecipientOrder: 0x5fdf0003
 PidTagRecipientEntryId: 0x5ff70102
 RowCount: 0x0001 (Count of following **ModifyRecipientRows**)
 RowId: 0x00000000
 RecipientType: 0x01(primary recipient)
 RecipientRowSize: 0x0127(bytes in following **RecipientRow**)
 RecipientFlags:0101000100000110 (S,D,Type=Exchange,I,U)
 AddressPrefixUsed: 0x5A (present because Type=Exchange)
 DisplayType: 0x00 (present because Type=Exchange)
 ExchangeAddress: User2 (present because Type=Exchange)
 DisplayName: user2 (present because D is set)
 SimpleDisplayName: user2 (present because S is set)
 RecipientColumnCount: 0x000C (matches ColumnCount)
 StandardPropertyRow:
 Flag: 0x00
 ValueArray: (property order defined by **RecipientColumns**)
 PidTagObjectType:0x00000006
 PidTagDisplayType:0x00000000
 PidTag7BitDisplayName:user2
 PidTagSmtppAddress:user2@szfkuk-dom.extest.microsoft.com
 PidTagSendInternetEncoding:0
 PidTagDisplayTypeEx:0x40000000
 PidTagRecipientDisplayName:user2
 PidTagRecipientFlags:0x00000001
 PidTagRecipientTrackStatus:0x00000000
 PidTagRecipientResourceState:0x00000000
 PidTagRecipientOrder:0x00000000
 PidTagRecipientEntryId:0x007c and the subsequent 124 (0x7c) bytes

4.7.2 RopModifyRecipients Response Buffer

0000: 0e 08 00 00 00 00
 RopId: 0x0e
 HandleIndex: 0x08
 ReturnValue: 0x000000

4.8 Save Message

After all necessary properties set for the message it was saved. The client sends **RopSaveChangesMessage** request.

4.8.1 RopSaveChangesMessage Request Buffer

```
0000: 0c 00 00 01 0a
      RopId: 0x0c
      LogonIndex: 0x00
      HandleIndex: 0x00
      MessageHandleIndex: 0x01
      SaveFlags: 0x0A (KeepOpenReadWrite)
```

4.8.2 RopSaveChangesMessage Response Buffer

```
0000: 0c 00 00 00 00 00 01 01-00 00 00 00 f0 86 39
      RopId: 0x0c
      HandleIndex: 0x00
      ReturnValue: 0x00000000
      MessageHandleIndex: 0x01
      MessageId: 01 00 00 00 00 f0 86 39
```

4.9 Releasing Message Object

Finally, the client releases the **Message object** by using **RopRelease**. See [MS-OXPRPT].

5 Security

5.1 Security Considerations for Implementers

There are no special security considerations specific to the [MS-OXCMSG] protocol. General security considerations pertaining to the underlying RPC-based transport apply (see [MS-OXCROPS]).

5.2 Index of Security Parameters

None.

6 Appendix A:Office/Exchange Behavior

The information in this specification is applicable to the following versions of Office/Exchange:

- Office 2003 with Service Pack 3 applied
- Exchange 2003 with Service Pack 2 applied
- Office 2007 with Service Pack 1 applied
- Exchange 2007 with Service Pack 1 applied

Exceptions, if any, are noted below. Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies Office/Exchange behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies Office/Exchange does not follow the prescription.

Index

Appendix A

- Office/Exchange Behavior, 59

Introduction, 8

- Applicability statement, 12
- Glossary, 8
- Prerequisites/Preconditions, 12
- Protocol overview, 11
- References, 9
- Relationship to other protocols, 11
- Standards assignments, 12
- Vendor-extensible fields, 12
- Versioning and capability negotiation, 12

Messages, 12

- Message syntax, 12
- Transport, 12

Protocol details, 40

- Client details, 40
- Server details, 45

Protocol examples, 52

- Adding recipients, 57
- Attach text file, 55
- Create message, 52
- Get attachment table, 53
- Insert HTML embedded image, 53
- Name to Id mapping, 53
- Releasing message object, 59
- Save message, 59
- Setting message properties, 56

References

- Informative references, 10
- Normative references, 9

Security, 59

- Index of security parameters, 59
- Security considerations for implementers, 59