

[MS-OXCSPAM]: Spam Confidence Level Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final

documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Updated references to reflect date of initial release.
09/03/2008	1.02		Revised and edited technical content.
12/03/2008	1.03		Updated IP notice.
03/04/2009	1.04		Revised and edited technical content.
04/10/2009	2.0		Updated applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	3.2.0	Minor	Updated the technical content.
05/05/2010	3.3.0	Minor	Updated the technical content.
08/04/2010	3.4	Minor	Clarified the meaning of the technical content.
11/03/2010	3.5	Minor	Clarified the meaning of the technical content.
03/18/2011	3.5	No change	No changes to the meaning, language, and formatting of the technical content.
08/05/2011	4.0	Major	Significantly changed the technical content.
10/07/2011	4.0	No change	No changes to the meaning, language, or formatting of the technical content.
01/20/2012	5.0	Major	Significantly changed the technical content.

Table of Contents

1 Introduction	5
1.1 Glossary	5
1.2 References	5
1.2.1 Normative References	6
1.2.2 Informative References	6
1.3 Overview	6
1.4 Relationship to Other Protocols	7
1.5 Prerequisites/Preconditions	7
1.6 Applicability Statement	7
1.7 Versioning and Capability Negotiation	7
1.8 Vendor-Extensible Fields	7
1.9 Standards Assignments	7
2 Messages	8
2.1 Transport	8
2.2 Message Syntax	8
2.2.1 Message Object Properties	8
2.2.1.1 PidLidSpamOriginalFolder Property	8
2.2.1.2 PidNameExchangeJunkEmailMoveStamp Property	8
2.2.1.3 PidTagContentFilterSpamConfidenceLevel Property	8
2.2.2 Junk E-Mail Rule Properties	8
2.2.2.1 PidTagJunkAddRecipientsToSafeSendersList Property	8
2.2.2.2 PidTagJunkIncludeContacts Property	9
2.2.2.3 PidTagJunkPermanentlyDelete Property	9
2.2.2.4 PidTagJunkPhishingEnableLinks Property	9
2.2.2.5 PidTagJunkThreshold Property	9
2.2.2.6 PidTagReportTime Property	10
2.2.3 Inbox Folder Properties	10
2.2.3.1 PidTagAdditionalRenEntryIds Property	10
3 Protocol Details	11
3.1 Server Details	11
3.1.1 Abstract Data Model	11
3.1.1.1 Junk E-Mail Move Stamp	11
3.1.1.2 Junk E-Mail Rule	11
3.1.2 Timers	12
3.1.3 Initialization	12
3.1.4 Higher-Layer Triggered Events	12
3.1.4.1 Obtaining or Creating the Junk E-Mail Move Stamp	12
3.1.4.2 Creating the Junk E-Mail Rule	12
3.1.5 Message Processing Events and Sequencing Rules	14
3.1.5.1 Executing the Junk E-Mail Rule on a Message	14
3.1.6 Timer Events	14
3.1.7 Other Local Events	14
3.2 Client Details	15
3.2.1 Abstract Data Model	15
3.2.1.1 Junk E-Mail Move Stamp	15
3.2.1.2 Junk E-Mail Rule	15
3.2.2 Timers	15
3.2.3 Initialization	15

3.2.4	Higher-Layer Triggered Events.....	15
3.2.4.1	Obtaining or Creating the Junk E-Mail Move Stamp	15
3.2.4.1.1	Obtaining the Junk E-Mail Move Stamp	16
3.2.4.1.2	Generating the Junk E-Mail Move Stamp	16
3.2.4.2	Creating the Junk E-Mail Rule.....	16
3.2.4.3	Retrieval of Spam Preferences.....	16
3.2.4.4	User Changes Client Spam Preferences.....	16
3.2.4.5	Server Junk E-Mail Rule Changes.....	16
3.2.4.6	User Adds a New Contact to Their Contacts Folder	17
3.2.4.7	User Sends an E-Mail	17
3.2.5	Message Processing Events and Sequencing Rules.....	17
3.2.5.1	Receiving an E-Mail Message.....	17
3.2.6	Timer Events	17
3.2.7	Other Local Events	17
4	Protocol Examples.....	18
4.1	Adding a Sender to the Trusted Recipients List.....	18
5	Security.....	21
5.1	Security Considerations for Implementers.....	21
5.2	Index of Security Parameters	21
6	Appendix A: Product Behavior.....	22
7	Change Tracking.....	23
8	Index	25

1 Introduction

The Spam Confidence Level Protocol enables the sharing of preferences for the filtering of unsolicited e-mail messages between the client and the server.

Sections 1.8, 2, and 3 of this specification are normative and contain RFC 2119 language. Sections 1.5 and 1.9 are also normative but cannot contain RFC 2119 language. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

domain

The following terms are defined in [\[MS-OXGLOS\]](#):

action
contact
Contacts folder
entry ID
extended rule
folder associated information (FAI)
Folder object
Inbox folder
Junk E-mail folder
Junk E-mail rule
mailbox
Message object
phishing
phishing message
recipient
remote operation (ROP)
restriction
ROP request
rule
Simple Mail Transfer Protocol (SMTP)
spam
spam filter
store

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)".

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".

[MS-OXORULE] Microsoft Corporation, "[E-Mail Rules Protocol Specification](#)".

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol Specification](#)".

[MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol Specification](#)".

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXCFCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol Specification](#)".

1.3 Overview

The Spam Confidence Level Protocol enables the client to process e-mail messages that are likely to be **phishing messages** or **spam** by doing the following:

- Blocking the delivery of messages to the **Inbox folder** that are from specific senders or classes of senders.
- Allowing the delivery of messages that are either from specific senders or to specific **recipients (1)**, regardless of whether the messages are identified as spam or phishing messages.

The **Junk E-mail rule**, which is an **extended rule**, specifies the client's spam and **phishing** preferences. When an e-mail message is delivered to a server, the server applies the Junk E-mail rule against the properties of the e-mail message to determine whether to put the message in the **Junk E-mail folder**.

1.4 Relationship to Other Protocols

The Spam Confidence Level Protocol relies on the following protocols:

- The E-Mail Rules Protocol, as described in [\[MS-OXORULE\]](#), to create **rules (4)**.
- The Message and Attachment Object Protocol, as described in [\[MS-OXCMSG\]](#), to create and access **Message objects**.
- The Folder Object Protocol, as described in [\[MS-OXCFOLD\]](#), to access **Folder objects**.
- The Property and Stream Object Protocol, as described in [\[MS-OXCPRPT\]](#), to get and set properties on Message objects and Folder objects.

1.5 Prerequisites/Preconditions

This protocol assumes that a system is in place to set and retrieve the properties of Message objects and of Folder objects.

1.6 Applicability Statement

This protocol defines the properties and rules that are relevant to the processing of spam and phishing messages. This protocol does not specify the algorithm that determines the likelihood of a message being spam or a phishing message or whether to consider a sender safe or blocked.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

The Spam Confidence Level Protocol uses the same underlying transport as that used by the Message and Attachment Object Protocol, as specified in [\[MS-OXCMSG\]](#), and the E-Mail Rules Protocol, as specified in [\[MS-OXORULE\]](#).

2.2 Message Syntax

2.2.1 Message Object Properties

The properties persisted on a Message object are listed in sections [2.2.1.1](#) through [2.2.1.3](#).

2.2.1.1 PidLidSpamOriginalFolder Property

Type: **PtypBinary** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidSpamOriginalFolder** property ([\[MS-OXPROPS\]](#) section 2.303) specifies the folder that contained the message before the message was moved into the Junk E-mail folder. The value of this property is the **entry ID** of the folder.

2.2.1.2 PidNameExchangeJunkEmailMoveStamp Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameExchangeJunkEmailMoveStamp** property ([\[MS-OXPROPS\]](#) section 2.460), if present and valid, indicates that either the message was already processed or the message is safe. The value of this property is valid only if it matches the value at index 5 of the **PidTagAdditionalRenEntryIds** property (section [2.2.3.1](#)).

If the **PidNameExchangeJunkEmailMoveStamp** property is not present or if the value of the **PidNameExchangeJunkEmailMoveStamp** property is invalid, the message MUST be processed by the client's **spam filter**.

2.2.1.3 PidTagContentFilterSpamConfidenceLevel Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagContentFilterSpamConfidenceLevel** property ([\[MS-OXPROPS\]](#) section 2.726) indicates the likelihood that the e-mail message is spam. The value MUST be in the range -1 to 9 (inclusive). The value -1 indicates that the message is not spam, and a value greater than -1 indicates that the message likely is spam. The greater the number, the higher the likelihood that the message is spam, with 9 indicating the highest likelihood. This property SHOULD be set by the server's spam filter before the Junk E-mail rule is executed.

2.2.2 Junk E-Mail Rule Properties

The properties persisted on the Junk E-mail rule are listed in sections [2.2.2.1](#) through [2.2.2.6](#).

2.2.2.1 PidTagJunkAddRecipientsToSafeSendersList Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagJunkAddRecipientsToSafeSendersList** property ([\[MS-OXPROPS\]](#) section 2.834) MUST be set to either 0 (zero) or 1. The value 1 indicates that the mail recipients (1) are to be added to the safe senders list. The value zero indicates that the mail recipients (1) are not to be added to the safe senders list.

2.2.2.2 PidTagJunkIncludeContacts Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagJunkIncludeContacts** property ([\[MS-OXPROPS\]](#) section 2.835) indicates whether e-mail messages from **contacts (3)** can be treated as junk.

If this property is set to 1, the Junk E-mail rule MUST specify conditions such that e-mail messages from contacts (3) are never treated as junk. If this property is set to 0 (zero), the Junk E-mail rule MUST specify conditions such that e-mail messages from contacts (3) can be treated as junk. The conditions of the Junk E-mail rule are specified in the **PidTagExtendedRuleMessageCondition** property ([\[MS-OXORULE\]](#) section 2.2.4.1.10). For details about creating the Junk E-mail rule, see section [3.1.4.2](#).

2.2.2.3 PidTagJunkPermanentlyDelete Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagJunkPermanentlyDelete** property ([\[MS-OXPROPS\]](#) section 2.836) indicates whether spam messages can be permanently deleted. If this property is set to 1, messages identified as spam can be permanently deleted. If this property is set to 0 (zero), messages identified as spam cannot be permanently deleted.

2.2.2.4 PidTagJunkPhishingEnableLinks Property

Type: **PtypBoolean** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagJunkPhishingEnableLinks** property ([\[MS-OXPROPS\]](#) section 2.837) indicates whether the phishing stamp on the message can be ignored. If the value is nonzero (TRUE), the phishing stamp, as specified in [\[MS-OXPHISH\]](#) section 2.2.1.1, can be ignored. If the value is zero (FALSE), the phishing stamp on the message cannot be ignored.

2.2.2.5 PidTagJunkThreshold Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagJunkThreshold** property ([\[MS-OXPROPS\]](#) section 2.838) indicates how aggressively the client is to send incoming mail to the Junk E-mail folder. When the value is 0xFFFFFFFF, spam filtering SHOULD NOT be applied; however, the blocked sender domains clause of the Junk E-mail rule MUST still be applied. A value of 0x80000000 indicates that all mail is spam except those messages from senders on the trusted senders list or sent to recipients (1) on the trusted recipients list.

The following table lists the valid values for this property.

Value	Meaning
0xFFFFFFFF	No spam filtering
0x00000006	Low spam filtering

Value	Meaning
0x00000003	High spam filtering
0x80000000	Trusted lists only

2.2.2.6 PidTagReportTime Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagReportTime** property ([\[MS-OXPROPS\]](#) section 2.999) indicates the last time the contact list that is controlled by the **PidTagJunkIncludeContacts** property (section [2.2.2.2](#)) was updated.

2.2.3 Inbox Folder Properties

The property listed in section [2.2.3.1](#) is on the Inbox folder.

2.2.3.1 PidTagAdditionalRenEntryIds Property

Type: **PtypMultipleBinary** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagAdditionalRenEntryIds** property ([\[MS-OXOSFLD\]](#) section 2.2.4) is persisted on the Inbox folder of a message **store**. The value at zero-based index five of this property is used to validate the **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)), as specified in section [3.1.4.1](#).

3 Protocol Details

3.1 Server Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

3.1.1.1 Junk E-Mail Move Stamp

The junk e-mail move stamp is as specified in section [3.2.1.1](#).

3.1.1.2 Junk E-Mail Rule

The Junk E-mail rule stores preferences regarding how spam filtering is applied.

The format of the preferences is a server-side extended rule that follows the E-Mail Rules Protocol, as specified in [\[MS-OXORULE\]](#). This format is convenient for a server that implements the E-Mail Rules Protocol, because executing the rule (4) on a message will apply the spam filtering preferences to the message and move it to the Junk E-mail folder if it fits the condition for spam.

The **restriction (2)** that makes up the condition of the Junk E-mail rule, as specified in [\[MS-OXORULE\]](#) section 2.2.1.3.2.9, contains several interdependent clauses. These clauses are essentially lists of **Simple Mail Transfer Protocol (SMTP)** e-mail addresses and several categories of e-mail **domains**.

The clauses are listed in the following table.

Blocked sender addresses	E-mail addresses of senders (who the message was sent from) to be blocked
Blocked sender domains	E-mail domains of senders that can be blocked.
Trusted sender domains	E-mail domains of senders that are trusted.
Trusted recipient domains	E-mail domains of recipients (1) (who the message was sent to) that are trusted.
Trusted sender addresses	E-mail addresses of senders that can be trusted.
Trusted recipient addresses	E-mail addresses of recipients (1) that can be trusted.
Trusted contact addresses	E-mail addresses of contacts (3) from the mailbox Contacts folder .

There is also a clause that checks the value of the **PidTagContentFilterSpamConfidenceLevel** property ([\[MS-OXPROPS\]](#) section 2.726) in the event that this property was applied to the message during delivery.

For more details about executing the Junk E-mail rule on a message, see section [3.1.5.1](#).

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

3.1.4.1 Obtaining or Creating the Junk E-Mail Move Stamp

The value of the **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)) SHOULD be created on the first interaction of the user with a mailbox. The **PidNameExchangeJunkEmailMoveStamp** property is set on every message that is moved by the Junk E-mail rule or is otherwise trusted content. For more details about obtaining or creating the junk e-mail move stamp, see sections [3.2.4.1.1](#) and [3.2.4.1.2](#).

3.1.4.2 Creating the Junk E-Mail Rule

The Junk E-mail rule is a server-side extended rule that follows the syntax specified in [\[MS-OXORULE\]](#) section 2.2.4. When the user first interacts with the mailbox, the server SHOULD create the Junk E-mail rule in the Inbox folder.

The Junk E-mail rule is represented by a **folder associated information (FAI)** message. The Junk E-mail rule is created or modified by adding or modifying an FAI message as specified in [\[MS-OXORULE\]](#) section 3.1.4.3.2.

The FAI Message object MUST have properties set as follows.

The **PidTagRuleMessageName** property ([\[MS-OXORULE\]](#) section 2.2.4.1.1) MUST be set to "Junk E-mail rule".

The **PidTagSubject** property ([\[MS-OXCMSG\]](#) section 2.2.1.46) MUST be set to "Junk E-mail rule".

The **PidTagRuleMessageProvider** property ([\[MS-OXORULE\]](#) section 2.2.4.1.7) MUST be set to "JunkEmailRule".

The **PidTagRuleMessageState** property ([\[MS-OXORULE\]](#) section 2.2.4.1.4) MUST be set to ST_ENABLED | ST_EXIT_LEVEL | ST_SKIP_IF_SCL_IS_SAFE.

The **PidTagRuleMessageSequence** property ([\[MS-OXORULE\]](#) section 2.2.4.1.3) MUST be set to 0 (zero).

The **PidTagRuleMessageUserFlags** property ([\[MS-OXORULE\]](#) section 2.2.4.1.5) MUST be set to 0 (zero).

The **PidTagRuleMessageLevel** property ([\[MS-OXORULE\]](#) section 2.2.4.1.6) MUST be set to 0 (zero).

The **PidTagExtendedRuleMessageActions** property ([\[MS-OXORULE\]](#) section 2.2.4.1.9) MUST contain the following two **actions (3)** in the format specified in [\[MS-OXORULE\]](#) section 2.2.4.2:

- An OP_MOVE action (3) to move the message to the Junk E-mail folder.

- An OP_TAG action (3) to set the **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)) on the message that is moved to the Junk E-mail folder.

The **PidTagReportTime** (section [2.2.2.6](#)), **PidTagJunkIncludeContacts** (section [2.2.2.2](#)), and **PidTagJunkThreshold** (section [2.2.2.5](#)) properties are set as appropriate. The **PidTagExtendedRuleMessageCondition** property ([\[MS-OXORULE\]](#) section 2.2.4.1.10) MUST contain the following restrictions (2). The formats of the restriction (2) structures are specified in [\[MS-OXCDATA\]](#) section 2.12.1 through section [2.12.12](#). All e-mail addresses MUST be of the SMTP address type.

A RES_AND restriction (2) with two subclauses:

1. A **RES_OR** restriction (2) with two subclauses:

1. A **RES_OR** restriction (2) with zero or more subclauses, one for each bad sender e-mail address. Each subclause MUST be a **RES_CONTENT** restriction (2) with the **FuzzyLevelLow** field set to FL_FULLSTRING and the **FuzzyLevelHigh** field set to FL_IGNORECASE comparing the value of the **PidTagSenderEmailAddress** property ([\[MS-OXOMSG\]](#) section 2.2.1.41) with a string that contains the e-mail address of a bad sender.

2. A **RES_AND** restriction (2) with two subclauses:

1. A **RES_OR** restriction (2) with two subclauses:

- A **RES_AND** restriction (2) with two subclauses:
 1. A **RES_EXIST** restriction (2) for the **PidTagContentFilterSpamConfidenceLevel** property (section [2.2.1.3](#)).
 2. A **RES_PROPERTY** restriction (2) for the **PidTagContentFilterSpamConfidenceLevel** property, with a relative operation of RELOP_GT against a value of -1.
- A **RES_OR** restriction (2) with zero or more subclauses, one for each bad sender domain. Each subclause MUST be a **RES_CONTENT** restriction (2) with the **FuzzyLevelLow** field set to FL_SUBSTRING and the **FuzzyLevelHigh** field set to FL_IGNORECASE comparing the value of the **PidTagSenderEmailAddress** property with a string that contains the domain of a bad sender.

2. A **RES_NOT** restriction (2) with a **RES_OR** restriction (2) that has two subclauses:

1. A **RES_OR** restriction (2) with zero or more subclauses, one for each trusted sender domain. Each subclause MUST be a **RES_CONTENT** restriction (2) with the **FuzzyLevelLow** field set to FL_SUBSTRING and the **FuzzyLevelHigh** field set to FL_IGNORECASE comparing the value of the **PidTagSenderEmailAddress** property with a string that contains the domain of a trusted sender.
2. A **RES_SUB** restriction (2) for the **PidTagMessageRecipients** property ([\[MS-OXCMSG\]](#) section 2.2.1.47), with a RES_OR restriction (2) with zero or more subclauses, one for each trusted recipient domain. Each subclause MUST be a **RES_CONTENT** restriction (2) with the **FuzzyLevelLow** field set to FL_SUBSTRING and the **FuzzyLevelHigh** field set to FL_IGNORECASE comparing the value of the **PidTagEmailAddress** property ([\[MS-OXOABK\]](#) section 2.2.3.14) with a string that contains the domain of a trusted recipient.

2. A **RES_NOT** restriction (2) with a **RES_OR** restriction (2) that has three subclauses:

1. A **RES_OR** restriction (2) with zero or more subclauses, one for each trusted sender e-mail address. Each subclause MUST be a **RES_CONTENT** restriction (2) with the **FuzzyLevelLow** field set to FL_FULLSTRING and the **FuzzyLevelHigh** field set to FL_IGNORECASE comparing the value of the **PidTagSenderEmailAddress** property with a string that contains the e-mail address of a trusted sender.
2. A **RES_SUB** restriction (2) for the **PidTagMessageRecipients** property, with a **RES_OR** restriction (2) with zero or more subclauses, one for each trusted recipient e-mail address. Each subclause MUST be a **RES_CONTENT** restriction (2) with the **FuzzyLevelLow** field set to FL_FULLSTRING and the **FuzzyLevelHigh** field set to FL_IGNORECASE comparing the value of the **PidTagEmailAddress** property with a string that the e-mail address of a trusted recipient.
3. A **RES_OR** restriction (2) with zero or more subclauses. Each subclause MUST be a **RES_CONTENT** restriction (2) with the **FuzzyLevelLow** field set to FL_SUBSTRING and the **FuzzyLevelHigh** field set to FL_IGNORECASE comparing the value of the **PidTagSenderEmailAddress** property with a string that contains the e-mail address of a contact (3) from the mailbox's contact list. If the **PidTagJunkIncludeContacts** property (section [2.2.2.2](#)) is set to 0 (zero), this restriction (2) MUST be empty (NULL); if the **PidTagJunkIncludeContacts** property is set to 1, then there SHOULD be one of these restrictions (2) for each trusted contact (3) e-mail address.

3.1.5 Message Processing Events and Sequencing Rules

None.

3.1.5.1 Executing the Junk E-Mail Rule on a Message

When the server executes the Junk E-mail rule on a message, it applies the spam filtering preferences to the message and then handles the message according to the value of the **PidTagExtendedRuleMessageCondition** property ([\[MS-OXORULE\]](#) section 2.2.4.1.10) on the Junk E-mail rule (as specified in section [3.1.4.2](#)).

If the **PidTagExtendedRuleMessageCondition** property on the Junk E-mail rule evaluates to true, then the server does the following:

1. Moves the message to the Junk E-mail folder.
2. Sets the **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)) on the message.

If the **PidTagExtendedRuleMessageCondition** property on the Junk E-mail rule evaluates to false, the server routes the message to the Inbox folder.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Client Details

3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model, as long as their external behavior is consistent with that described in this document.

3.2.1.1 Junk E-Mail Move Stamp

A valid **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)), when stamped on a message, indicates that the message bypasses the client's spam filter.

A common scenario in which this occurs is when the client's spam filter has already moved the message to the Junk E-mail folder once. If the user has retrieved a message from the Junk E-mail folder, it will not be reprocessed.

If clients want to populate a message store with trusted Message objects that are never spam but might look like spam to a spam filter, they can set this property. The RSS Object Protocol, as described in [\[MS-OXORSS\]](#), is a practical example of this method.

3.2.1.2 Junk E-Mail Rule

The client uses the Junk E-mail rule to store user preferences regarding how spam filtering occurs for a mailbox, but the rule (4) itself is executed only on the server.

Clients interpret properties on the message and data in the **PidTagExtendedRuleMessageCondition** property ([\[MS-OXORULE\]](#) section 2.2.4.1.10) of the Junk E-mail rule as specifying preferences and lists of data that are used to control the client spam filter and user interface elements.

The rule (4) contains a **PidTagContentFilterSpamConfidenceLevel** property (section [2.2.1.3](#)) that can be used to determine the user preference for how aggressively spam is filtered.

The rule (4) contains various lists of SMTP e-mail addresses that are stored in the **PidTagExtendedRuleMessageCondition** property. For a summary of these, see section [3.1.1.2](#).

3.2.2 Timers

None.

3.2.3 Initialization

The junk e-mail move stamp and Junk E-mail rule SHOULD be created on the first interaction of the user with a mailbox that requires them.

3.2.4 Higher-Layer Triggered Events

3.2.4.1 Obtaining or Creating the Junk E-Mail Move Stamp

The **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)) is set on every message that is moved by the Junk E-mail rule or is otherwise trusted content.

The value of the **PidNameExchangeJunkEmailMoveStamp** property is valid only if it matches the value in the **PidTagAdditionalRenEntryIds** property (section [2.2.3.1](#)), as specified in section [3.2.4.1.1](#).

The client MUST obtain or create the junk e-mail move stamp as specified in sections [3.2.4.1.1](#) and [3.2.4.1.2](#).

3.2.4.1.1 Obtaining the Junk E-Mail Move Stamp

To obtain the junk e-mail move stamp, the client MUST read the **PidTagAdditionalRenEntryIds** property (section [2.2.3.1](#)) from the Inbox folder and do one the following:

- If there is a value at zero-based index 5 of the array, this value is the value of the **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)), stored as an unsigned **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1). The client MUST use this value for the **PidNameExchangeJunkEmailMoveStamp** property when creating the Junk E-mail rule.
- If there is no value at zero-based index 5, the client MUST generate a value for the **PidNameExchangeJunkEmailMoveStamp** property, as described in section [3.2.4.1.2](#).

3.2.4.1.2 Generating the Junk E-Mail Move Stamp

If there is no value at zero-based index 5 of the **PidTagAdditionalRenEntryIds** property (section [2.2.3.1](#)) of the Inbox folder, the client MUST generate an arbitrary **PtypInteger32** value ([\[MS-OXCDATA\]](#) section 2.11.1) and store it as an unsigned **PtypInteger32** to the zero-based index 5 of the **PidTagAdditionalRenEntryIds** property of the Inbox folder. For security details, see section [5.1](#).

The client MUST set the value of the **PidNameExchangeJunkEmailMoveStamp** (section [2.2.1.2](#)) to the **PtypInteger32** value that is stored in the zero-based index 5 of the **PidTagAdditionalRenEntryIds** property of the Inbox folder.

3.2.4.2 Creating the Junk E-Mail Rule

The client MUST create the Junk E-mail rule, as specified in [\[MS-OXORULE\]](#) section 3.1.4.3.2, whenever it requires the spam preferences as specified in section [3.1.4.2](#).

The client MUST format the Junk E-mail rule as specified in section [3.1.4.2](#).

3.2.4.3 Retrieval of Spam Preferences

After clients log on to the messaging server, they SHOULD retrieve preferences from the server Junk E-mail rule, as specified in [\[MS-OXORULE\]](#) section 3.1.4.2, before they apply any spam filtering on messages.

3.2.4.4 User Changes Client Spam Preferences

When users change their spam preferences, messaging clients SHOULD update the server Junk E-mail rule, as specified in [\[MS-OXORULE\]](#) section 3.1.4.3.2, to match these new preferences.

3.2.4.5 Server Junk E-Mail Rule Changes

Clients SHOULD periodically retrieve the server Junk E-mail rule, as specified in [\[MS-OXORULE\]](#) section 3.1.4.2, and compare the Junk E-mail rule settings with the client spam filter settings to determine whether the server Junk E-mail rule has changed. If the Junk E-mail rule settings do not

match the client spam filter settings, the client SHOULD update its spam filter settings to match the server Junk E-mail rule settings. The interval at which the client retrieves the server Junk E-mail rule and compares the settings is implementation-dependent.

3.2.4.6 User Adds a New Contact to Their Contacts Folder

If the **PidTagJunkIncludeContacts** property (section [2.2.2.2](#)) is present with a value of 1, the client MUST determine whether the added contact (3) has e-mail addresses that are not yet included in the trusted contacts section of the Junk E-mail rule. If the added contact's (3) e-mail addresses are already included in the trusted contacts section of the Junk E-mail rule, no action is required. If the added contact (3) has e-mail addresses that are not yet included in the trusted contacts section of the Junk E-mail rule, the client MUST update the server Junk E-mail rule (as specified in section [3.1.4.2](#) and in [\[MS-OXORULE\]](#) section 3.1.4.3.2) to add those e-mail addresses to the restriction (2).

If the value of the **PidTagJunkIncludeContacts** property is 0 (zero), no action is required.

3.2.4.7 User Sends an E-Mail

If the **PidTagJunkAddRecipientsToSafeSendersList** property (section [2.2.2.1](#)) is present with a value of 1, the client MUST update the server Junk E-mail rule (as specified in section [3.1.4.2](#) and in [\[MS-OXORULE\]](#) section 3.1.4.3.2) to add the SMTP addresses of the e-mail recipients (1) to the trusted senders clause of the Junk E-mail rule condition.

If the value of the **PidTagJunkAddRecipientsToSafeSendersList** property is 0 (zero), no action is required.

3.2.5 Message Processing Events and Sequencing Rules

3.2.5.1 Receiving an E-Mail Message

If the client receives an e-mail message that has the **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)) set, that property MUST be validated against the **PidTagAdditionalRenEntryIds** property (section [2.2.3.1](#)), as specified in section [3.1.4.1](#). If the value matches, the client MUST NOT run a spam filter against the e-mail message.

If the client runs a spam filter to determine whether the e-mail message is spam, the client SHOULD use the preferences specified in the Junk E-mail rule to control the spam filter.

If the client spam filter determines that the e-mail message is spam, the client uses the value of the **PidTagJunkPermanentlyDelete** property (section [2.2.2.3](#)) on the Junk E-mail rule to determine whether to permanently delete the e-mail message. The client SHOULD set the **PidLidSpamOriginalFolder** property (section [2.2.1.1](#)) on each message that is moved to the Junk E-mail folder.

The client can use the **PidTagJunkPhishingEnableLinks** property (section [2.2.2.4](#)) on the Junk E-mail rule to determine whether to enable links within the message.

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

4 Protocol Examples

4.1 Adding a Sender to the Trusted Recipients List

Jim consistently receives mail from a mailing list that his spam filter moves to the Junk E-mail folder. Jim trusts all mail sent to the mailing list, and so adds the mailing list SMTP address "recip2@example.com" to his trusted recipients list.

The client first receives a handle to the Junk E-mail rule by using the **RopOpenMessage ROP** ([\[MS-OXCROPS\]](#) section 2.2.6.1).

The client retrieves the **PidTagExtendedRuleMessageCondition** property ([\[MS-OXPROPS\]](#) section 2.771) by using the **RopGetPropertiesSpecific ROP** ([\[MS-OXCROPS\]](#) section 2.2.8.3). The response contains the following data:

```
0000: 00 00 00 02 00 00 00 01-02 00 00 00 01 03 00 00
0010: 00 03 00 00 01 00 1F 00-1F 0C 1F 00 1F 0C 62 00
0020: 6C 00 6F 00 63 00 6B 00-65 00 64 00 32 00 40 00
0030: 65 00 78 00 61 00 6D 00-70 00 6C 00 65 00 2E 00
0040: 63 00 6F 00 6D 00 00 00-03 00 00 01 00 1F 00 1F
0050: 0C 1F 00 1F 0C 62 00 6C-00 6F 00 63 00 6B 00 65
0060: 00 64 00 33 00 40 00 65-00 78 00 61 00 6D 00 70
0070: 00 6C 00 65 00 2E 00 63-00 6F 00 6D 00 00 00 03
0080: 00 00 01 00 1F 00 1F 0C-1F 00 1F 0C 62 00 6C 00
0090: 6F 00 63 00 6B 00 65 00-64 00 40 00 65 00 78 00
00a0: 61 00 6D 00 70 00 6C 00-65 00 2E 00 63 00 6F 00
00b0: 6D 00 00 00 00 02 00 00-00 01 02 00 00 00 00 02
00c0: 00 00 00 08 03 00 76 40-04 02 03 00 76 40 03 00
00d0: 76 40 FF FF FF FF 01 00-00 00 00 02 01 02 00 00
00e0: 00 01 01 00 00 00 03 01-00 01 00 1F 00 1F 0C 1F
00f0: 00 1F 0C 40 00 65 00 78-00 61 00 6D 00 70 00 6C
0100: 00 65 00 2E 00 63 00 6F-00 6D 00 00 00 09 0D 00
0110: 12 0E 01 00 00 00 00 02-01 03 00 00 00 01 01 00
0120: 00 00 03 00 00 01 00 1F-00 1F 0C 1F 00 1F 0C 73
0130: 00 61 00 66 00 65 00 40-00 65 00 78 00 61 00 6D
0140: 00 70 00 6C 00 65 00 2E-00 63 00 6F 00 6D 00 00
0150: 00 09 0D 00 12 0E 01 01-00 00 00 03 00 00 01 00
0160: 1F 00 03 30 1F 00 03 30-72 00 65 00 63 00 69 00
0170: 70 00 40 00 65 00 78 00-61 00 6D 00 70 00 6C 00
0180: 65 00 2E 00 63 00 6F 00-6D 00 00 00 01 00 00 00
0190: 00
```

The following table lists the spam lists that this data corresponds to. In the "C-style string representation" column, the letter "L" that precedes each string literal indicates that the string is a wide-character string literal (that is, an array of **wchar_t**).

List	C-style string representation
Blocked sender addresses	L"blocked@example.com" L"blocked2@example.com" L"blocked3@example.com"
Blocked sender domains	None
Trusted sender domains	L "@example.com"

List	C-style string representation
Trusted recipient domains	None
Trusted sender addresses	L"safe@example.com"
Trusted recipient addresses	L"recip@example.com"
Trusted contact addresses	None

The client constructs the new restriction (2), including recip2@example.com as a trusted recipient. The client sets the new property value on the message. Because this condition can be large, the client chooses to set the property by calling the following ROPs:

- **RopOpenStream** ([MS-OXCROPS] section 2.2.9.1)
- **RopSetStreamSize** ([MS-OXCROPS] section 2.2.9.6)
- **RopWriteStream** ([MS-OXCROPS] section 2.2.9.3)
- **RopCommitStream** ([MS-OXCROPS] section 2.2.9.4)
- **RopRelease** ([MS-OXCROPS] section 2.2.15.3)

The **RopWriteStream** ROP sets the following data:

```

0000: 00 00 00 02 00 00 00 01-02 00 00 00 01 03 00 00
0010: 00 03 00 00 01 00 1F 00-1F 0C 1F 00 1F 0C 62 00
0020: 6C 00 6F 00 63 00 6B 00-65 00 64 00 32 00 40 00
0030: 65 00 78 00 61 00 6D 00-70 00 6C 00 65 00 2E 00
0040: 63 00 6F 00 6D 00 00 00-03 00 00 01 00 1F 00 1F
0050: 0C 1F 00 1F 0C 62 00 6C-00 6F 00 63 00 6B 00 65
0060: 00 64 00 33 00 40 00 65-00 78 00 61 00 6D 00 70
0070: 00 6C 00 65 00 2E 00 63-00 6F 00 6D 00 00 00 03
0080: 00 00 01 00 1F 00 1F 0C-1F 00 1F 0C 62 00 6C 00
0090: 6F 00 63 00 6B 00 65 00-64 00 40 00 65 00 78 00
00a0: 61 00 6D 00 70 00 6C 00-65 00 2E 00 63 00 6F 00
00b0: 6D 00 00 00 00 02 00 00-00 01 02 00 00 00 00 02
00c0: 00 00 00 08 03 00 76 40-04 02 03 00 76 40 03 00
00d0: 76 40 FF FF FF FF 01 00-00 00 00 02 01 02 00 00
00e0: 00 01 01 00 00 00 03 01-00 01 00 1F 00 1F 0C 1F
00f0: 00 1F 0C 40 00 65 00 78-00 61 00 6D 00 70 00 6C
0100: 00 65 00 2E 00 63 00 6F-00 6D 00 00 00 09 0D 00
0110: 12 0E 01 00 00 00 00 00 02-01 03 00 00 00 01 01 00
0120: 00 00 03 00 00 01 00 1F-00 1F 0C 1F 00 1F 0C 73
0130: 00 61 00 66 00 65 00 40-00 65 00 78 00 61 00 6D
0140: 00 70 00 6C 00 65 00 2E-00 63 00 6F 00 6D 00 00
0150: 00 09 0D 00 12 0E 01 02-00 00 00 03 00 00 01 00
0160: 1F 00 03 30 1F 00 03 30-72 00 65 00 63 00 69 00
0170: 70 00 32 00 40 00 65 00-78 00 61 00 6D 00 70 00
0180: 6C 00 65 00 2E 00 63 00-6F 00 6D 00 00 00 03 00
0190: 00 01 00 1F 00 03 30 1F-00 03 30 72 00 65 00 63
01a0: 00 69 00 70 00 40 00 65-00 78 00 61 00 6D 00 70
01b0: 00 6C 00 65 00 2E 00 63-00 6F 00 6D 00 00 00 01
01c0: 00 00 00 00

```

This data corresponds to the spam lists in the following table.

List	C-style string representation
Blocked sender addresses	L"blocked@example.com" L"blocked2@example.com" L"blocked3@example.com"
Blocked sender domains	None
Trusted sender domains	L "@example.com"
Trusted recipient domains	None
Trusted sender addresses	L"safe@example.com"
Trusted recipient addresses	L"recip@example.com" L"recip2@example.com"
Trusted contact addresses	None

Finally, the client sends a **RopSaveChangesMessage ROP request** ([\[MS-OXCROPS\]](#) section 2.2.6.3) to persist the object on the server and a **RopRelease** ROP request to release the object.

5 Security

5.1 Security Considerations for Implementers

The **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.1.2](#)) is used to bypass content protection offered by client spam filters. If the valid junk e-mail move stamp can be determined by an outside party, that party might discover a clever way to exploit the protocol such that untrusted and potentially malicious content could bypass protective filters.

Implement the procedure in section [3.2.4.1.2](#) in such a way that the value of the zero-based index 5 of the **PidTagAdditionalRenEntryIds** property (section [2.2.3.1](#)) of the Inbox folder cannot be guessed.

5.2 Index of Security Parameters

Security parameter	Section
PidNameExchangeJunkEmailMoveStamp	2.2.1.2

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2003
- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 15 Technical Preview
- Microsoft® Office Outlook® 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Outlook® 2010
- Microsoft® Outlook® 15 Technical Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

7 Change Tracking

This section identifies changes that were made to the [MS-OXCSPAM] protocol document between the October 2011 and January 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
6 Appendix A: Product Behavior	Added Exchange 15 Technical Preview and Outlook 15 Technical Preview to the list of applicable product versions.	Y	Content updated.

8 Index

A

Abstract data model
[client](#) 15
[server](#) 11
Abstract data model - client
[junk e-mail move stamp](#) 15
[Junk E-mail rule](#) 15
Abstract data model - server
[junk e-mail move stamp](#) 11
[Junk E-mail rule](#) 11
[Adding a sender to the trusted recipients list](#)
[example](#) 18
[Applicability](#) 7

C

[Capability negotiation](#) 7
[Change tracking](#) 23
Client
[abstract data model](#) 15
[initialization](#) 15
[other local events](#) 17
[timer events](#) 17
[timers](#) 15
Client - abstract data model
[junk e-mail move stamp](#) 15
[Junk E-mail rule](#) 15
Client - higher layer triggered events
[retrieval of spam preferences](#) 16
[user adds a new contact to their Contacts folder](#)
17
[user changes client spam preferences](#) 16
[user sends an e-mail](#) 17
Client - higher-layer triggered events
[creating the Junk E-mail rule](#) 16
[obtaining or creating the junk e-mail move stamp](#)
16
[server Junk E-mail rule changes](#) 16
Client - message processing
[receiving an e-mail message](#) 17
Client - sequencing rules
[receiving an e-mail message](#) 17

D

Data model - abstract
[client](#) 15
[server](#) 11

E

Example
[adding a sender to the trusted recipients list](#) 18

F

[Fields - vendor-extensible](#) 7

G

[Glossary](#) 5

H

Higher layer triggered events - client
[retrieval of spam preferences](#) 16
[user adds a new contact to their Contacts folder](#)
17
[user changes client spam preferences](#) 16
[user sends an e-mail](#) 17
Higher-layer triggered events - client
[creating the Junk E-mail rule](#) 16
[obtaining or creating the junk e-mail move stamp](#)
16
[server Junk E-mail rule changes](#) 16
Higher-layer triggered events - server
[creating the Junk E-mail rule](#) 12
[obtaining or creating the junk e-mail move stamp](#)
12

I

[Implementer - security considerations](#) 21
Inbox folder properties
[PidTagAdditionalRenEntryIds property](#) 10
[Inbox Folder Properties message](#) 10
[Index of security parameters](#) 21
[Informative references](#) 6
Initialization
[client](#) 15
[server](#) 12
[Introduction](#) 5

J

Junk E-mail rule properties
[PidTagJunkAddRecipientsToSafeSendersList](#)
[property](#) 8
[PidTagJunkIncludeContacts property](#) 9
[PidTagJunkPermanentlyDelete property](#) 9
[PidTagJunkPhishingEnableLinks property](#) 9
[PidTagJunkThreshold property](#) 9
[PidTagReportTime property](#) 10
[Junk E-Mail Rule Properties message](#) 8

M

Message object properties
[PidLidSpamOriginalFolder property](#) 8
[PidNameExchangeJunkEmailMoveStamp property](#)
8
[PidTagContentFilterSpamConfidenceLevel](#)
[property](#) 8
[Message Object Properties message](#) 8
Message processing

[server](#) 14
Message processing - client
[receiving an e-mail message](#) 17
Message processing - server
[executing the Junk E-mail rule on a message](#) 14
Messages
[Inbox Folder Properties](#) 10
[Junk E-Mail Rule Properties](#) 8
[Message Object Properties](#) 8
[transport](#) 8

N

[Normative references](#) 6

O

Other local events
[client](#) 17
[server](#) 14
[Overview \(synopsis\)](#) 6

P

[Parameters - security index](#) 21
[PidLidSpamOriginalFolder Message object property](#) 8
[PidNameExchangeJunkEmailMoveStamp Message object property](#) 8
[PidTagAdditionalRenEntryIds Inbox folder property](#) 10
[PidTagContentFilterSpamConfidenceLevel Message object property](#) 8
[PidTagJunkAddRecipientsToSafeSendersList Junk E-mail rule property](#) 8
[PidTagJunkIncludeContacts Junk E-mail rule property](#) 9
[PidTagJunkPermanentlyDelete Junk E-mail rule property](#) 9
[PidTagJunkPhishingEnableLinks Junk E-mail rule property](#) 9
[PidTagJunkThreshold Junk E-mail rule property](#) 9
[PidTagReportTime Junk E-mail rule property](#) 10
[Preconditions](#) 7
[Prerequisites](#) 7
[Product behavior](#) 22

R

References
[informative](#) 6
[normative](#) 6
[Relationship to other protocols](#) 7

S

Security
[implementer considerations](#) 21
[parameter index](#) 21
Sequencing rules
[server](#) 14
Sequencing rules - client

[receiving an e-mail message](#) 17
Sequencing rules - server
[executing the Junk E-mail rule on a message](#) 14

Server

[abstract data model](#) 11
[initialization](#) 12
[message processing](#) 14
[other local events](#) 14
[sequencing rules](#) 14
[timer events](#) 14
[timers](#) 12
Server - abstract data model
[junk e-mail move stamp](#) 11
[Junk E-mail rule](#) 11
Server - higher-layer triggered events
[creating the Junk E-mail rule](#) 12
[obtaining or creating the junk e-mail move stamp](#) 12
Server - message processing
[executing the Junk E-mail rule on a message](#) 14
Server - sequencing rules
[executing the Junk E-mail rule on a message](#) 14
[Standards assignments](#) 7

T

Timer events
[client](#) 17
[server](#) 14
Timers
[client](#) 15
[server](#) 12
[Tracking changes](#) 23
[Transport](#) 8
Triggered events - client
[creating the Junk E-mail rule](#) 16
[obtaining or creating the junk e-mail move stamp](#) 16
[retrieval of spam preferences](#) 16
[server Junk E-mail rule changes](#) 16
[user adds a new contact to their Contacts folder](#) 17
[user changes client spam preferences](#) 16
[user sends an e-mail](#) 17
Triggered events - server
[creating the Junk E-mail rule](#) 12
[obtaining or creating the junk e-mail move stamp](#) 12

V

[Vendor-extensible fields](#) 7
[Versioning](#) 7