

# [MS-OXCTABL]: Table Object Protocol Specification

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Revised and edited technical content.
09/03/2008	1.02		Revised and edited technical content.
12/03/2008	1.03		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	3.2.0	Minor	Updated the technical content.
05/05/2010	4.0.0	Major	Updated and revised the technical content.
08/04/2010	5.0	Major	Significantly changed the technical content.
11/03/2010	6.0	Major	Significantly changed the technical content.

# Contents

<b>1 Introduction</b>	<b>8</b>
1.1 Glossary	8
1.2 References	9
1.2.1 Normative References	9
1.2.2 Informative References	10
1.3 Overview	10
1.3.1 Table Notifications	10
1.4 Relationship to Other Protocols	10
1.5 Prerequisites/Preconditions	11
1.6 Applicability Statement	11
1.7 Versioning and Capability Negotiation	11
1.8 Vendor-Extensible Fields	11
1.9 Standards Assignments	11
<b>2 Messages</b>	<b>12</b>
2.1 Transport	12
2.2 Message Syntax	12
2.2.1 Table-Specific Properties	12
2.2.1.1 PidTagInstID	12
2.2.1.2 PidTagInstanceNum	12
2.2.1.3 PidTagRowType	12
2.2.1.4 PidTagDepth	12
2.2.1.5 PidTagContentCount	13
2.2.1.6 PidTagContentUnreadCount	13
2.2.2 Table ROPs	13
2.2.2.1 Table ROP Constants	13
2.2.2.1.1 Pre-Defined Bookmarks	13
2.2.2.1.2 Custom Bookmarks	13
2.2.2.1.3 Table Status	13
2.2.2.1.4 Asynchronous Flags	14
2.2.2.2 RopSetColumns Semantics	14
2.2.2.2.1 Request Field Overview	14
2.2.2.2.1.1 SetColumnsFlags	14
2.2.2.2.1.2 PropertyTagCount	14
2.2.2.2.1.3 PropertyTags	14
2.2.2.2.2 Response Field Overview	15
2.2.2.2.2.1 TableStatus	15
2.2.2.3 RopSortTable Semantics	15
2.2.2.3.1 Request Field Overview	15
2.2.2.3.1.1 SortTableFlags	15
2.2.2.3.1.2 SortOrderCount	15
2.2.2.3.1.3 CategoryCount	15
2.2.2.3.1.4 ExpandedCount	15
2.2.2.3.1.5 SortOrders	15
2.2.2.3.2 Response Field Overview	16
2.2.2.3.2.1 TableStatus	16
2.2.2.4 RopRestrict Semantics	16
2.2.2.4.1 Request Field Overview	16
2.2.2.4.1.1 RestrictFlags	16
2.2.2.4.1.2 RestrictionDataSize	16

2.2.2.4.1.3	RestrictionData .....	16
2.2.2.4.2	Response Field Overview .....	17
2.2.2.4.2.1	TableStatus .....	17
2.2.2.5	RopQueryRows Semantics .....	17
2.2.2.5.1	Request Field Overview .....	17
2.2.2.5.1.1	QueryRowsFlags .....	17
2.2.2.5.1.2	ForwardRead .....	17
2.2.2.5.1.3	RowCount .....	17
2.2.2.5.2	Response Field Overview .....	17
2.2.2.5.2.1	Origin .....	17
2.2.2.5.2.2	RowCount .....	18
2.2.2.5.2.3	RowData .....	18
2.2.2.6	RopAbort Semantics .....	18
2.2.2.6.1	Request Field Overview .....	18
2.2.2.6.2	Response Field Overview .....	18
2.2.2.6.2.1	TableStatus .....	18
2.2.2.7	RopGetStatus Semantics .....	18
2.2.2.7.1	Request Field Overview .....	18
2.2.2.7.2	Response Field Overview .....	18
2.2.2.7.2.1	TableStatus .....	18
2.2.2.8	RopQueryPosition Semantics .....	19
2.2.2.8.1	Request Field Overview .....	19
2.2.2.8.2	Response Field Overview .....	19
2.2.2.8.2.1	Numerator .....	19
2.2.2.8.2.2	Denominator .....	19
2.2.2.9	RopSeekRow Semantics .....	19
2.2.2.9.1	Request Field Overview .....	19
2.2.2.9.1.1	Origin .....	19
2.2.2.9.1.2	RowCount .....	19
2.2.2.9.1.3	WantRowMovedCount .....	19
2.2.2.9.2	Response Field Overview .....	20
2.2.2.9.2.1	HasSoughtLess .....	20
2.2.2.9.2.2	RowsSought .....	20
2.2.2.10	RopSeekRowBookmark Semantics .....	20
2.2.2.10.1	Request Field Overview .....	20
2.2.2.10.1.1	BookmarkSize .....	20
2.2.2.10.1.2	Bookmark .....	20
2.2.2.10.1.3	RowCount .....	20
2.2.2.10.1.4	WantRowMovedCount .....	20
2.2.2.10.2	Response Field Overview .....	21
2.2.2.10.2.1	RowNoLongerVisible .....	21
2.2.2.10.2.2	HasSoughtLess .....	21
2.2.2.10.2.3	RowsSought .....	21
2.2.2.11	RopSeekRowFractional Semantics .....	21
2.2.2.11.1	Request Field Overview .....	21
2.2.2.11.1.1	Numerator .....	21
2.2.2.11.1.2	Denominator .....	22
2.2.2.11.2	Response Field Overview .....	22
2.2.2.12	RopCreateBookmark Semantics .....	22
2.2.2.12.1	Request Field Overview .....	22
2.2.2.12.2	Response Field Overview .....	22
2.2.2.12.2.1	BookmarkSize .....	22
2.2.2.12.2.2	Bookmark .....	22

2.2.2.13	RopQueryColumnsAll Semantics.....	22
2.2.2.13.1	Request Field Overview .....	22
2.2.2.13.2	Response Field Overview .....	22
2.2.2.13.2.1	PropertyTagCount .....	22
2.2.2.13.2.2	PropertyTags.....	23
2.2.2.14	RopFindRow Semantics.....	23
2.2.2.14.1	Request Field Overview .....	23
2.2.2.14.1.1	FindRowFlags .....	23
2.2.2.14.1.2	RestrictionDataSize .....	23
2.2.2.14.1.3	RestrictionData.....	23
2.2.2.14.1.4	Origin.....	23
2.2.2.14.1.5	BookmarkSize .....	23
2.2.2.14.1.6	Bookmark .....	23
2.2.2.14.2	Response Field Overview .....	24
2.2.2.14.2.1	RowNoLongerVisible.....	24
2.2.2.14.2.2	HasRowData .....	24
2.2.2.14.2.3	RowData.....	24
2.2.2.15	RopFreeBookmark Semantics .....	24
2.2.2.15.1	Request Field Overview .....	24
2.2.2.15.1.1	BookmarkSize .....	24
2.2.2.15.1.2	Bookmark.....	24
2.2.2.15.2	Response Field Overview .....	24
2.2.2.16	RopResetTable Semantics .....	24
2.2.2.16.1	Request Field Overview .....	25
2.2.2.16.2	Response Field Overview .....	25
2.2.2.17	RopExpandRow Semantics .....	25
2.2.2.17.1	Request Field Overview .....	25
2.2.2.17.1.1	MaxRowCount .....	25
2.2.2.17.1.2	CategoryId.....	25
2.2.2.17.2	Response Field Overview .....	25
2.2.2.17.2.1	ExpandedRowCount .....	25
2.2.2.17.2.2	RowCount.....	25
2.2.2.17.2.3	RowData.....	26
2.2.2.18	RopCollapseRow Semantics.....	26
2.2.2.18.1	Request Field Overview .....	26
2.2.2.18.1.1	CategoryId.....	26
2.2.2.18.2	Response Field Overview .....	26
2.2.2.18.2.1	CollapsedRowCount.....	26
2.2.2.19	RopGetCollapseState Semantics .....	26
2.2.2.19.1	Request Field Overview .....	26
2.2.2.19.1.1	RowId .....	26
2.2.2.19.1.2	RowIndex.....	26
2.2.2.19.2	Response Field Overview .....	26
2.2.2.19.2.1	CollapseStateSize .....	26
2.2.2.19.2.2	CollapseState .....	26
2.2.2.20	RopSetCollapseState Semantics.....	27
2.2.2.20.1	Request Field Overview .....	27
2.2.2.20.1.1	CollapseStateSize .....	27
2.2.2.20.1.2	CollapseState .....	27
2.2.2.20.2	Response Field Overview .....	27
2.2.2.20.2.1	BookmarkSize .....	27
2.2.2.20.2.2	Bookmark .....	27

<b>3</b>	<b>Protocol Details</b>	<b>28</b>
3.1	Client Details	28
3.1.1	Abstract Data Model	28
3.1.2	Timers	28
3.1.3	Initialization	28
3.1.4	Higher-Layer Triggered Events	28
3.1.4.1	Preparing the Table	28
3.1.4.1.1	Asynchronous Table Preparation	29
3.1.4.2	Querying the Table	30
3.1.4.3	Advancing the Table	30
3.1.4.4	Getting Table State	30
3.1.4.5	Registering For Notifications	31
3.1.5	Message Processing Events and Sequencing Rules	31
3.1.5.1	Processing Notifications	31
3.1.6	Timer Events	31
3.1.7	Other Local Events	31
3.2	Server Details	31
3.2.1	Abstract Data Model	31
3.2.2	Timers	32
3.2.3	Initialization	32
3.2.4	Higher-Layer Triggered Events	32
3.2.5	Message Processing Events and Sequencing Rules	32
3.2.5.1	Processing Asynchronous Requests	32
3.2.5.2	Processing RopSetColumns	32
3.2.5.3	Processing RopSortTable	33
3.2.5.4	Processing RopRestrict	34
3.2.5.5	Processing RopQueryRows	34
3.2.5.6	Processing RopAbort	35
3.2.5.7	Processing RopGetStatus	35
3.2.5.8	Processing RopQueryPosition	36
3.2.5.9	Processing RopSeekRow	36
3.2.5.10	Processing RopSeekRowBookmark	36
3.2.5.11	Processing RopSeekRowFractional	37
3.2.5.12	Processing RopCreateBookmark	37
3.2.5.13	Processing RopQueryColumnsAll	38
3.2.5.14	Processing RopFindRow	38
3.2.5.15	Processing RopFreeBookmark	39
3.2.5.16	Processing RopResetTable	39
3.2.5.17	Processing RopExpandRow	40
3.2.5.18	Processing RopCollapseRow	40
3.2.5.19	Processing RopGetCollapseState	40
3.2.5.20	Processing RopSetCollapseState	41
3.2.6	Timer Events	41
3.2.7	Other Local Events	41
<b>4</b>	<b>Protocol Examples</b>	<b>42</b>
4.1	Obtaining a Message List	42
4.1.1	Client Request Buffer	42
4.1.2	Server Response to Client Request	43
4.2	Setting the Columns on a Table	43
4.2.1	Client Request Buffer	43
4.2.2	Server Response to Client Request	44
4.3	Sorting a Table by Time Delivered	45

4.3.1	Client Request Buffer .....	45
4.3.2	Server Response to Client Request .....	46
4.4	Querying Rows .....	46
4.4.1	Client Request Buffer .....	46
4.4.2	Server Response to Client Request .....	47
4.5	Working with Categories .....	48
4.5.1	Sorting a Table by Category .....	48
4.5.1.1	Client Request Buffer .....	48
4.5.1.2	Server Response to Client Request .....	49
4.5.2	Expanding a Category Row .....	50
4.5.2.1	Client Request Buffer .....	50
4.5.2.2	Server Response to Client Request .....	50
4.5.3	Querying Rows with Category View.....	51
4.5.3.1	Client Request Buffer .....	51
4.5.3.2	Server Response to Client Request .....	51
<b>5</b>	<b>Security.....</b>	<b>54</b>
5.1	Security Considerations for Implementers.....	54
5.2	Index of Security Parameters .....	54
<b>6</b>	<b>Appendix A: Product Behavior .....</b>	<b>55</b>
<b>7</b>	<b>Change Tracking.....</b>	<b>57</b>
<b>8</b>	<b>Index .....</b>	<b>63</b>

# 1 Introduction

This document specifies the Table Object Protocol, which is used by a client to read and navigate through data that is retrieved in tabular format from the server. In addition to retrieving filtered, sorted **rows** of tabular data, the Table Object Protocol also allows the client to collapse a grouping of rows and to navigate through the rows.

## 1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

- attachment**
- attachments table**
- binary large object (BLOB)**
- contents table**
- conversation**
- flags**
- folder**
- Folder object**
- handle**
- handle array**
- header**
- hierarchy table**
- instance**
- little-endian**
- message**
- Message object**
- permissions**
- property (1)**
- property ID**
- property tag**
- property type**
- remote operation (ROP)**
- remote procedure call (RPC)**
- restriction**
- ROP buffer**
- ROP request**
- ROP request buffer**
- ROP response**
- ROP response buffer**
- rule**
- rules table**
- search criteria**
- single instance**
- sort order**
- table**
- Table object**

The following terms are specific to this document:

**bookmark:** A data structure that the server uses to point to a position in the **table**. There are three pre-defined **bookmarks** (beginning, end, and current). A custom **bookmark** is a server-specific data structure that can be stored by the client for easily navigating a **table**.

**category:** A grouping of **rows** in a **table** that all have the same value for a specified **property**.



**column set:** A set of properties that are requested by the client for each **row** of data.

**cursor:** The location of the next **row** to be read from the **table**. (The location marked by the **cursor** is also referred to as the current location in the **table**.) The **cursor** may point to any **row** in the **table**, or may be located after the last **row** in the **table**.

**header row:** A **row** at the beginning of a **category** that does not represent data in the **table**, but provides information about a grouping.

**leaf row:** A **row** that is in a **category**.

**multi-value instance:** A **row** in a **table** corresponding to a single value in a **multi-value property**. There will be multiple **rows** for each **Message object** in the **table**, each **row** corresponding to one value of the **multi-value property**. Each **row** will have a single value for the **property** and the properties for the other columns are repeated.

**multi-value property:** A **property** that can have multiple values simultaneously.

**permissions table:** A **table** of permissions to a **folder**.

**row:** A set of **properties** associated with one record in the **table**.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-DTYP] Microsoft Corporation, "Windows Data Types", March 2007, <http://msdn.microsoft.com/en-us/library/cc230273.aspx>

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)", April 2008.

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)", April 2008.

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)", April 2008.

[MS-OXCNOTIF] Microsoft Corporation, "[Core Notifications Protocol Specification](#)", April 2008.

[MS-OXCPerm] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol Specification](#)", April 2008.

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)", April 2008.

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol Specification](#)", April 2008.

[MS-OXORULE] Microsoft Corporation, "[E-Mail Rules Protocol Specification](#)", April 2008.

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)", April 2008.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

## 1.2.2 Informative References

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

## 1.3 Overview

The Table Object Protocol is used to read tabular data from a server. It specifies a set of operations that a client can use to request tabular data from a server based on a **handle** to the **table**. The client can specify the columns, the **restriction**, and the **sort order** for the table, and can request that the rows of the table be categorized according to specific **properties**. The client can then request one or more rows of data. Additionally, the client can find rows, navigate through the rows, and create **bookmarks** for easier navigation. The protocol can provide a way of freeing server resources associated with bookmarks.

When the client requests that the rows of the table be categorized, the server will include "header" rows in the table which don't have the same properties as normal rows. The client can request that the server hide or show all of the normal rows for which the **header row** represents their **category**. Categories can be nested inside categories. The client can retrieve a **BLOB** that specifies which categories are collapsed and which are expanded in the current table. This can then be given to the table at a future time to restore the collapsed state of the table as well as the **cursor** location.

**Multi-value instances** can be retrieved from the table when a **multi-value property** is specified in the **column set**. When multi-value instances are requested, for each value in a multi-value property there will be an **instance** of the row that has that single value for the property. All other properties are repeated in each multi-value instance.

Categories that are based on multi-value properties will display the multi-value instances under each **header** representing a value that is set on that row. The row that is displayed under a given header row will include the single property value specified by the header row, not all values for the property.

Some tables might not support certain table operations. For example, **rules tables** do not support sorting and return an error if attempted. Tables that do not support asynchronous operations can perform them synchronously or return an error.

### 1.3.1 Table Notifications

Tables are not static representations of the data. Table rows can be modified, moved, created, and deleted while the client is using the table. Table notifications are used to inform the client of all changes made to the table since it was opened.

To properly use the Table Object Protocol, both client and server need to implement the Core Notifications Protocol, as specified in [\[MS-OXCNOTIF\]](#).

## 1.4 Relationship to Other Protocols

The Table Object Protocol uses the Remote Operations (ROP) List and Encoding Protocol, as specified in [\[MS-OXCROPS\]](#), and the Core Notifications protocol, as specified in [\[MS-OXCNOTIF\]](#).

The Message and Attachment object Protocol, the E-mail Rules Protocol, the Exchange Access and Operation Permissions protocol, and the Folder Object Protocol depend on the Table Object Protocol. For information about these protocols, see [\[MS-OXCMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXCPerm\]](#), and [\[MS-OXCFOLD\]](#), respectively.

## 1.5 Prerequisites/Preconditions

The Table Object Protocol assumes that the client has acquired a handle to the **Table object** on which it is going to operate. The method by which a handle to a Table object is acquired is dependent on the **table** type. For specifications on how to obtain a handle to a specific **table** type, see the appropriate document, as stated in the following list.

Table Type	ROP to get a table handle	Specified in
<b>Contents Table</b>	<a href="#">RopGetContentsTable</a>	<a href="#">[MS-OXCFOLD]</a> section 2.2.14
<b>Hierarchy Table</b>	<a href="#">RopGetHierarchyTable</a>	<a href="#">[MS-OXCFOLD]</a> section 2.2.13
<b>Attachments Table</b>	<a href="#">RopGetAttachmentTable</a>	<a href="#">[MS-OXCMSG]</a> section 2.2.3.17
<b>Permissions Table</b>	<a href="#">RopGetPermissionsTable</a>	<a href="#">[MS-OXCPerm]</a> section 2.2.1.1
Rules Table	<a href="#">RopGetRulesTable</a>	<a href="#">[MS-OXORULE]</a> section 2.2.2

## 1.6 Applicability Statement

The Table Object Protocol is used to query tabular data associated with **folders**, **messages**, **attachments**, **permissions**, and **rules** on the server.

## 1.7 Versioning and Capability Negotiation

The Table Object Protocol does not support negotiation of the version to be used. Instead, the client determines the server version to which it has connected. The client's behavior is limited by the capabilities of the server version with which it communicates.

A feature, packed buffers for the [RopQueryRows ROP](#) (see [3.2.5.5](#)), was added for servers with a major version of eight (8). The client checks the version number that is returned by the server in the results from the **EcDoConnectEx** method, as specified in [\[MS-OXCRPC\]](#) section 3.1.4.11.

## 1.8 Vendor-Extensible Fields

None.

## 1.9 Standards Assignments

None.

## 2 Messages

Unless otherwise specified, sizes in this section are expressed in bytes.

### 2.1 Transport

The **ROP request buffers** and **ROP response buffers** specified by this protocol are sent to and received from, respectively, the server using the underlying Wire Format protocol, as specified in [\[MS-OXCRPC\]](#).

### 2.2 Message Syntax

#### 2.2.1 Table-Specific Properties

The following properties can be included in the column set of a table for the purpose of collapsing and expanding categories. The following properties are used by the client, but are produced by the server. For more details about these properties, see [\[MS-OXPROPS\]](#).

##### 2.2.1.1 PidTagInstID

This is a **PtypInteger64** property that is an identifier for all instances of a row in the table. When a [RopGetCollapseState](#) request is sent, the client passes this property value in the **RowId** field to specify a cursor to store. When the [PidTagInstID](#) property is included in the column set, the server sets the property to the same value for each row that is an instance of the same underlying data.

##### 2.2.1.2 PidTagInstanceNum

This is a **PtypInteger32** property that is an **identifier** for a **single instance** of a row in the table. When a [RopGetCollapseState](#) request is sent, the client passes this property value in the **RowInstanceNumber** field to specify a cursor to store. When this property is included in the column set, the server sets it to a different value for each row that is an instance of the same underlying data.

##### 2.2.1.3 PidTagRowType

This is a **PtypInteger32** property that identifies the type of the row. The possible values are:

Name	Value	Meaning
TBL_LEAF_ROW	0x00000001	The row is a row of data.
TBL_EMPTY_CATEGORY	0x00000002	The row is a header row with no rows inside the category.
TBL_EXPANDED_CATEGORY	0x00000003	The row is a header row that is expanded.
TBL_COLLAPSED_CATEGORY	0x00000004	The row is a header row that is collapsed.

##### 2.2.1.4 PidTagDepth

This is a **PtypInteger32** property that specifies the number of nested categories in which a given row is contained. For example, if a row is contained within two header rows, its depth is 0x0002. When a table contains no categories, all rows will have a depth of 0x0000.

### 2.2.1.5 PidTagContentCount

This is a **PtypInteger32** property that specifies the number of rows under the header row. This property is set whether the header row is collapsed or expanded.

### 2.2.1.6 PidTagContentUnreadCount

This is a **PtypInteger32** property that specifies the number of rows under the header row that have the [PidTagRead](#) property set to FALSE. This value is set whether the header row is collapsed or expanded.

## 2.2.2 Table ROPs

The following sections specify the semantics of ROP fields that are specific to the Table Object Protocol. Before sending these requests to the server, the handle to the Table object that is used in the **ROP requests** MUST be acquired.

For more details about the syntax for these ROPs, as well as the semantics of common ROP fields, see [\[MS-OXCROPS\]](#).

### 2.2.2.1 Table ROP Constants

#### 2.2.2.1.1 Pre-Defined Bookmarks

The following values are used in the [RopSeekRow](#) request, the [RopQueryRows](#) response, and the [RopFindRow](#) request.

Name	Value	Meaning
BOOKMARK_BEGINNING	0x00	Points to the beginning position of the table, or the first row.
BOOKMARK_CURRENT	0x01	Points to the current position of the table, or the current row.
BOOKMARK_END	0x02	Points to the ending position of the table, or the location after the last row.

#### 2.2.2.1.2 Custom Bookmarks

The following value is used in the [RopFindRow](#) request.

Name	Value	Meaning
BOOKMARK_CUSTOM	0x03	Points to the custom position in the table. Used with the <b>BookmarkSize</b> and <b>Bookmark</b> fields.

#### 2.2.2.1.3 Table Status

The table status refers to the status of any asynchronous operations being performed on the table. <1> The following values are used in the [RopGetStatus](#), [RopAbort](#), [RopSetColumns](#), [RopRestrict](#), and [RopSortTable](#) responses.

Name	Value	Meaning
TBLSTAT_COMPLETE	0x00	No operations are in progress.

Name	Value	Meaning
TBLSTAT_SORTING	0x09	A <a href="#">RopSortTable</a> operation is in progress.
TBLSTAT_SORT_ERROR	0x0A	An error occurred during a <a href="#">RopSortTable</a> operation.
TBLSTAT_SETTING_COLS	0x0B	A <a href="#">RopSetColumns</a> operation is in progress.
TBLSTAT_SETCOL_ERROR	0x0D	An error occurred during a <a href="#">RopSetColumns</a> operation.
TBLSTAT_RESTRICTING	0x0E	A <a href="#">RopRestrict</a> operation is in progress.
TBLSTAT_RESTRICT_ERROR	0x0F	An error occurred during a <a href="#">RopRestrict</a> operation.

#### 2.2.2.1.4 Asynchronous Flags

The asynchronous **flags** are flags that specify whether certain ROPs are to be performed asynchronously. <2>

Name	Value	Meaning
TBL_ASYNC	0x01	The server SHOULD perform the operation asynchronously. For details about asynchronous table operations, see sections <a href="#">3.1.4.1.1</a> and <a href="#">3.2.5.1</a> . If the server does not honor requests to perform operations asynchronously, asynchronous flags will be ignored by the server (they are not read or written to).
	0x00	The server will perform the operation synchronously.

#### 2.2.2.2 RopSetColumns Semantics

[RopSetColumns](#) is used to set the properties that the client wants to be included in the table. This ROP is only valid on Table objects.

##### 2.2.2.2.1 Request Field Overview

###### 2.2.2.2.1.1 SetColumnsFlags

This is a **BYTE** field [[MS-DTYP](#)] that contains an OR'ed combination of the asynchronous flags, which are specified in section [2.2.2.1.4.<3>](#) The field MUST NOT have any of the other bits set.

###### 2.2.2.2.1.2 PropertyTagCount

This is a **WORD** field [[MS-DTYP](#)] that specifies the number of **property tags** in the **PropertyTags** field. This value MUST be 1 or greater.

###### 2.2.2.2.1.3 PropertyTags

This is an array of **PropertyTag** structures identifying the set and order of property values to be returned by the server in the ROP response buffer of [RopQueryRows](#), [RopFindRow](#), and [RopExpandRow](#), as specified in sections [2.2.2.5](#), [2.2.2.14](#), and [2.2.2.17](#), respectively. Every table MUST have at least one column. If the **property type** is a multi-value property, and the client wants multi-value instances based on this property, it MUST also set the **MultivalueInstance** bit (0x2000) of the **PropertyTag** structure. If the property type is not multi-valued, it does not set the **MultivalueInstance** bit of the **PropertyTag** structure set.

For details about the **MultivalueInstance** bit, see [\[MS-OXCDATA\]](#) section 2.11.1.2. For details about the **PropertyTag** structure, see [\[MS-OXCDATA\]](#) section 2.9.

## 2.2.2.2.2 Response Field Overview

### 2.2.2.2.2.1 TableStatus

This is a **BYTE** field [\[MS-DTYP\]](#) indicating the status of asynchronous operations being performed on the table. [<4>](#) It MUST have one of the table status values that are specified in [2.2.2.1.3](#).

### 2.2.2.3 RopSortTable Semantics

[RopSortTable](#) orders the rows of a contents table based on sort criteria. This ROP is valid only on Table objects.

#### 2.2.2.3.1 Request Field Overview

##### 2.2.2.3.1.1 SortTableFlags

This is a **BYTE** field [\[MS-DTYP\]](#) that contains an OR'ed combination of the asynchronous flags, which are specified in section [2.2.2.1.4.<5>](#) The field MUST NOT have any of the other bits set.

##### 2.2.2.3.1.2 SortOrderCount

This is a **WORD** field [\[MS-DTYP\]](#) that specifies the number of **SortOrder** structures in the **SortOrders** field.

##### 2.2.2.3.1.3 CategoryCount

This is a **WORD** field [\[MS-DTYP\]](#) that specifies the number of **SortOrder** structures in **SortOrders** that are designated as category columns. They occupy the first **CategoryCount** positions in the **SortOrders** array. The value of the **CategoryCount** field MUST be in the range 0 to **SortOrderCount**.

##### 2.2.2.3.1.4 ExpandedCount

This is a **WORD** field [\[MS-DTYP\]](#) that specifies the number of categories that start in the expanded state. This value MUST be in the range 0 to **CategoryCount**. The first **ExpandedCount** categories are initially expanded. If **CategoryCount** is equal to **ExpandedCount**, then all categories are expanded.

##### 2.2.2.3.1.5 SortOrders

This is an array of **SortOrder** structures which defines the sort to be performed. The number of **SortOrder** structures in the array MUST be equal to the value of **SortOrderCount**. For categorized sorting, the **SortOrder** structure specifies the property type and **property ID** that are used as the category. When the value of the **SortOrderCount** field exceeds the value of the **SortOrderCount** field, indicating that there are more sort keys than categories, categories are created from the **SortOrder** structures that appear first in the SortOrders array. The remaining **SortOrder** structures are used to sort the rows within the categories.

For example, if **SortOrderCount** is set to 0x0003 and **CategoryCount** is set to 0x0002, the columns described by the **PropertyType** and **PropertyId** members of the first two entries in SortOrders are used as the category columns. The first entry serves as the top-level category

grouping; the second entry as the secondary grouping. All of the rows that match the two category columns are sorted using the sort key defined in the third entry.

If a **SortOrder** structure specifies a multi-value property, it MUST also have the **MultivalueInstance** bit set, specifying that the sort be performed using the individual values of that property. Sort order on a multi-value property that is not also being used for multi-value instances is undefined. The **SortOrders** field MUST NOT contain more than one **SortOrder** structure specifying a multi-value property in the first **CategoryCount** positions of the array.

If the **Order** member of a **SortOrder** structure is set to Ascending, the table will be sorted in ascending order by the column specified in the **PropertyType** and **PropertyId** members.

If the **Order** member of a **SortOrder** structure is set to Descending, the table will be sorted in descending order by the column specified in the **PropertyType** and **PropertyId** members.

If the **Order** member of a **SortOrder** structure is set to MaximumCategory, that structure directly follows the first **CategoryCount** structure in the **SortOrders** field and **CategoryCount** MUST be greater than 0x0000 (zero). This **SortOrder** structure, at position **CategoryCount** + 1 in the array, modifies the immediately previous category sort. The categories in the table will be not be sorted by the column specified in the category sort. The categories will be sorted according to each category's maximum value of the specified column. Any **SortOrder** structures after this one will sub-sort the rows within each category.

For details about the **SortOrder** structure, see [\[MS-OXCDATA\]](#) section 2.13.1.

## 2.2.2.3.2 Response Field Overview

### 2.2.2.3.2.1 TableStatus

This is a **BYTE** field [\[MS-DTYP\]](#) indicating the status of asynchronous operations being performed on the table. [<6>](#) It MUST have one of the table status values that are specified in [2.2.2.1.3](#).

## 2.2.2.4 RopRestrict Semantics

[RopRestrict](#) establishes a restriction on a table. Applying a restriction has no effect on the underlying data of a table; it simply alters the table by limiting the rows that can be retrieved to rows containing data that satisfy the restriction. This ROP is only valid on Table objects.

### 2.2.2.4.1 Request Field Overview

#### 2.2.2.4.1.1 RestrictFlags

This is a **BYTE** field [\[MS-DTYP\]](#) that contains an OR'ed combination of the asynchronous flags, as specified in section [2.2.2.1.4.<7>](#) The field MUST NOT have any of the other bits set.

#### 2.2.2.4.1.2 RestrictionDataSize

This is a **WORD** field [\[MS-DTYP\]](#) that specifies the size, in bytes, of the **RestrictionData** field.

#### 2.2.2.4.1.3 RestrictionData

This is a restriction that is applied to the table. For details about restrictions, see [\[MS-OXCDATA\]](#) section 2.12. It has **RestrictionDataSize** bytes.



## 2.2.2.4.2 Response Field Overview

### 2.2.2.4.2.1 TableStatus

This is a **BYTE** field [MS-DTYP] indicating the status of asynchronous operations being performed on the table. <8> It MUST have one of the table status values that are specified in section 2.2.2.1.3.

## 2.2.2.5 RopQueryRows Semantics

[RopQueryRows](#) returns zero or more rows from a table, beginning from the current table cursor position. This ROP is only valid on Table objects.

### 2.2.2.5.1 Request Field Overview

#### 2.2.2.5.1.1 QueryRowsFlags

This is a **BYTE** field [MS-DTYP] that contains any of the following bit flags.

Name	Value	Meaning
Advance	0x00	Advance the table cursor.
NoAdvance	0x01	Do not advance the table cursor.
EnablePackedBuffers	0x02	Enable packed buffers for the response. To allow packed buffers to be used, this flag is used in conjunction with the Chain flag (0x00000004) that is passed in the <i>pulFlags</i> parameter of the <b>EcDoRpcExt2</b> method. For details about extended-buffer packing, see [MS-OXCRPC]. This flag is only supported against servers with a major version of at least eight (8) as described in section 1.7.

This field MUST NOT contain both the Advance and NoAdvance flags set simultaneously. The field MUST NOT have any of the other bits set.

#### 2.2.2.5.1.2 ForwardRead

This is a **BYTE** field [MS-DTYP] that specifies the direction in which to retrieve rows. It is set to TRUE (0x01) to read the table forwards. It is set to FALSE (0x00) to read the table backwards. It MUST NOT be set to any other value.

#### 2.2.2.5.1.3 RowCount

This is a **WORD** field [MS-DTYP] that specifies the maximum number of rows to be returned.

### 2.2.2.5.2 Response Field Overview

#### 2.2.2.5.2.1 Origin

This is a **BYTE** field [MS-DTYP] that identifies the cursor position. It MUST be set to one of the pre-defined bookmark values specified in 2.2.2.1.1.

#### 2.2.2.5.2.2 RowCount

This is a **WORD** field [\[MS-DTYP\]](#) that specifies the number of rows returned. It MUST be less than or equal to the **RowCount** that is specified in the request, and it MUST be greater than or equal to 0x0000. It MUST be equal to the number of **PropertyRow** objects returned in the **RowData** field.

#### 2.2.2.5.2.3 RowData

The array of rows returned. Each row is represented by a **PropertyRow** object. For details about the format of the **PropertyRow** object, see [\[MS-OXCDATA\]](#). Each row MUST have the same columns and ordering of columns as specified in the last [RopSetColumns](#) request. The **RowData** field MUST NOT include rows that don't match the criteria specified in the last [RopRestrict](#) request. If [RopRestrict](#) has not been issued, the **RowData** field MUST include all rows. The rows MUST be sorted and grouped according to the sort order specified in the last [RopSortTable](#) request. If [RopSortTable](#) has not been sent, the default sort order is undefined. Every property value returned in a row MUST be less than or equal to 510 bytes in size. If a property value is greater than 510 bytes in size, it MUST be truncated to 510 bytes.

#### 2.2.2.6 RopAbort Semantics

[RopAbort](#) attempts to stop any asynchronous table operations that are currently in progress. This ROP is only valid on Table objects.

##### 2.2.2.6.1 Request Field Overview

There are no ROP-specific request fields.

##### 2.2.2.6.2 Response Field Overview

###### 2.2.2.6.2.1 TableStatus

This is a **BYTE** field [\[MS-DTYP\]](#) indicating the status of asynchronous operations being performed on the table before the abort. [<9>](#) It MUST have one of the table status values that are specified in [2.2.2.1.3](#).

#### 2.2.2.7 RopGetStatus Semantics

The [RopGetStatus](#) ROP retrieves information about the current status of asynchronous operations being performed on the table. [<10>](#) This ROP is only valid on Table objects.

##### 2.2.2.7.1 Request Field Overview

There are no ROP-specific request fields.

##### 2.2.2.7.2 Response Field Overview

###### 2.2.2.7.2.1 TableStatus

This is a **BYTE** field [\[MS-DTYP\]](#) indicating the status of asynchronous operations being performed on the table. [<11>](#) It MUST have one of the table status values that are specified in [2.2.2.1.3](#).

### 2.2.2.8 RopQueryPosition Semantics

[RopQueryPosition](#) returns the location of cursor in the table. Note that the current position and total number of rows could change based on external events before the response to this message is received. This ROP is only valid on Table objects.

#### 2.2.2.8.1 Request Field Overview

There are no ROP-specific request fields.

#### 2.2.2.8.2 Response Field Overview

##### 2.2.2.8.2.1 Numerator

This **ULONG** field [\[MS-DTYP\]](#) contains the index (0-based) of the current row. It MUST be greater than or equal to 0x00000000.

##### 2.2.2.8.2.2 Denominator

This **ULONG** field [\[MS-DTYP\]](#) contains the total number of rows in the table. It MUST be greater than or equal to the value of the **Numerator** field.

### 2.2.2.9 RopSeekRow Semantics

[RopSeekRow](#) moves the table cursor to a specific location in the table. The new location is specified by a pre-defined bookmark and the number of rows to move (forward or backwards) from that bookmark. This ROP is only valid on Table objects.

#### 2.2.2.9.1 Request Field Overview

##### 2.2.2.9.1.1 Origin

This **BYTE** field [\[MS-DTYP\]](#) contains the bookmark indicating the starting position of the seek operation. This field's value MUST be one of the pre-defined bookmark values that are specified in [2.2.2.1.1](#).

##### 2.2.2.9.1.2 RowCount

This **LONG** field [\[MS-DTYP\]](#) contains the number of rows to seek, starting from the bookmark. To seek forward from the bookmark, the value MUST be positive; to seek backwards, the value MUST be negative.

##### 2.2.2.9.1.3 WantRowMovedCount

This is a **BYTE** field [\[MS-DTYP\]](#) that specifies whether the actual number of rows moved MUST be returned by the server. This field MUST be set to TRUE (0x01) or FALSE (0x00). If this field is set to TRUE (0x01), the server MUST return the actual number of rows moved. If this field is set to FALSE (0x00), the value of the **HasSoughtLess** (section [2.2.2.9.2.1](#)) and **RowsSought** (section [2.2.2.9.2.2](#)) fields are undefined, and the client MUST ignore them.

The actual number of rows moved can differ from the requested number of rows if the beginning or end of the table is encountered prior to moving the requested number of rows.

## 2.2.2.9.2 Response Field Overview

### 2.2.2.9.2.1 HasSoughtLess

This is a **BYTE** field [MS-DTYP] that specifies whether the number of rows moved is less than the number of rows requested. This field **MUST** be set to TRUE (0x01) if the number of rows moved is less than the number of rows requested (**RowCount** field), otherwise it **MUST** be set to FALSE (0x00).

The **HasSoughtLess** field **MUST** be present in the response. This field's value **MUST** be valid if the **WantRowMovedCount** field (in the request) is set to TRUE and its value **MUST** be ignored if **WantRowMovedCount** is set to FALSE.

### 2.2.2.9.2.2 RowsSought

This **LONG** field [MS-DTYP] specifies the actual number of rows moved. If the value of the **RowCount** field (in the request) is negative, the value of **RowsSought** **MUST** also be negative or 0x00000000, indicating that the seek was performed backwards. If the value of the **RowCount** field (in the request) is positive, then the value of **RowsSought** **MUST** also be positive.

This field **MUST** be present in the response. This field's value **MUST** be valid if the **WantRowMovedCount** field (in the request) is set to TRUE and **MUST** be ignored if **WantRowMovedCount** is set to FALSE.

## 2.2.2.10 RopSeekRowBookmark Semantics

[RopSeekRowBookmark](#) moves the table cursor to a specific location in the table. The new location is specified by a custom bookmark and the number of rows to move (forward or backwards) from that bookmark.

This ROP is distinguished from [RopSeekRow](#) in that the bookmark is not a pre-defined one, but one created by a [RopCreateBookmark](#) request. This ROP is only valid on Table objects.

### 2.2.2.10.1 Request Field Overview

#### 2.2.2.10.1.1 BookmarkSize

This is a **WORD** field [MS-DTYP] that specifies the size in bytes of the **Bookmark** field.

#### 2.2.2.10.1.2 Bookmark

A bookmark indicating the starting position of the seek operation. The bookmark **MUST** be data that was returned by a previous [RopCreateBookmark](#) request. The bookmark **MUST NOT** have been previously freed using [RopFreeBookmark](#).

#### 2.2.2.10.1.3 RowCount

This is a **LONG** field [MS-DTYP] that specifies the number of rows to seek, starting from the bookmark. To seek forward from the bookmark, the value **MUST** be positive; to seek backward, the value **MUST** be negative.

#### 2.2.2.10.1.4 WantRowMovedCount

This is a **BYTE** field [MS-DTYP] that specifies whether the actual number of rows moved is returned by the server. This field **MUST** be set to TRUE (0x01) or FALSE (0x00). If this field is set to TRUE

(0x01), the server MUST return the actual number of rows moved. If this field is set to FALSE (0x00), the value of the **HasSoughtLess** (section [2.2.2.9.2.1](#)) and **RowsSought** (section [2.2.2.9.2.2](#)) fields is undefined, and the client MUST ignore them.

The actual number of rows moved can differ from the requested number of rows if the beginning or end of the table is encountered prior to moving the requested number of rows.

## 2.2.2.10.2 Response Field Overview

### 2.2.2.10.2.1 RowNoLongerVisible

This **BYTE** field [\[MS-DTYP\]](#) indicates whether the row to which the bookmark pointed is no longer visible. This field MUST be set to TRUE (0x01) if the row to which the bookmark pointed has been removed from the table. (For example, the row's properties changed so that they didn't match the restriction, the row was deleted, or the row's header row has been collapsed.) Otherwise, this field MUST be set to FALSE (0x00).

When the row to which the bookmark pointed is no longer visible, the bookmark will point to the next row in the table. In this case, the seek will begin from the next row after the bookmark in the table.

### 2.2.2.10.2.2 HasSoughtLess

This **BYTE** field [\[MS-DTYP\]](#) specifies whether the number of rows moved is less than the number of rows requested. This field MUST be set to TRUE (0x01) if the number of rows moved is less than the number of rows requested (**RowCount** field), otherwise it MUST be set to FALSE (0x00).

The **HasSoughtLess** field MUST be present in the response. This field's value MUST be valid if the **WantRowMovedCount** field (in the request) is set to TRUE and its value MUST be ignored if **WantRowMovedCount** is set to FALSE.

### 2.2.2.10.2.3 RowsSought

This **LONG** field [\[MS-DTYP\]](#) specifies the actual number of rows moved. If the value of the **RowCount** field (in the request) is negative, the value of **RowsSought** MUST also be negative or 0x00000000, indicating that the seek was performed backwards. If the value of the **RowCount** field (in the request) is positive, then the value of **RowsSought** MUST also be positive.

This field MUST be present in the response. This field's value MUST be valid if the **WantRowMovedCount** field (in the request) is set to TRUE and MUST be ignored if **WantRowMovedCount** is set to FALSE.

## 2.2.2.11 RopSeekRowFractional Semantics

[RopSeekRowFractional](#) moves the table cursor to an approximate position in the table. [<12>](#) The new location is specified as a fraction of the table size. This ROP is only valid on Table objects.

### 2.2.2.11.1 Request Field Overview

#### 2.2.2.11.1.1 Numerator

This **ULONG** field [\[MS-DTYP\]](#) is the numerator of the fractional position. The value SHOULD be less than or equal to the value of the **Denominator** field.

If a client sets the **Numerator** to a value greater than the **Denominator**, the server is required to set the cursor past the last row in the table. If the value of **Numerator** is 0x00000000, the cursor MUST be set to the first row in the table. If the value is equal to or greater than the value of **Denominator**, the cursor MUST be set past the last row in the table.

#### 2.2.2.11.1.2 Denominator

This **ULONG** field [\[MS-DTYP\]](#) is the denominator of the fractional position. The value MUST NOT be set to 0x00000000.

#### 2.2.2.11.2 Response Field Overview

There are no ROP-specific response fields.

#### 2.2.2.12 RopCreateBookmark Semantics

[RopCreateBookmark](#) creates a new bookmark at the current cursor position in the table. This ROP is only valid on Table objects.

##### 2.2.2.12.1 Request Field Overview

There are no ROP-specific request fields.

##### 2.2.2.12.2 Response Field Overview

###### 2.2.2.12.2.1 BookmarkSize

This **WORD** field specifies the size in bytes of the **Bookmark** field. This field MUST be present.

###### 2.2.2.12.2.2 Bookmark

This field contains the bookmark data. This data is specific to the server. The client MUST NOT assume that this data has a specific format.

#### 2.2.2.13 RopQueryColumnsAll Semantics

[RopQueryColumnsAll](#) returns a complete list of all columns for the table. The list includes all columns that the server has for the table, not necessarily only those requested by [RopSetColumns](#). This ROP is only valid on Table objects.

##### 2.2.2.13.1 Request Field Overview

There are no ROP-specific request fields.

##### 2.2.2.13.2 Response Field Overview

###### 2.2.2.13.2.1 PropertyTagCount

This **WORD** field specifies the number of property tags in the **PropertyTags** field.

### 2.2.2.13.2.2 PropertyTags

An array of property tags, each of which corresponds to an available column in the table. Each property tag is represented by a **PropertyTag** structure. For details about the **PropertyTag** structure, see [\[MS-OXCDATA\]](#) section 2.9.

### 2.2.2.14 RopFindRow Semantics

[RopFindRow](#) returns the next row in a table that matches the **search criteria** and moves the cursor to that row. The initial location for the search is specified by a bookmark. This ROP is only valid on Table objects.

#### 2.2.2.14.1 Request Field Overview

##### 2.2.2.14.1.1 FindRowFlags

This is a **BYTE** field [\[MS-DTYP\]](#) that contains an OR'ed combination of any of the following bit flags.

Value	Meaning
0x00	Perform the find forwards.
0x01	Perform the find backwards.

The field MUST NOT have any of the other bits set.

##### 2.2.2.14.1.2 RestrictionDataSize

This **WORD** field [\[MS-DTYP\]](#) specifies the size, in bytes, of the **RestrictionData** field.

##### 2.2.2.14.1.3 RestrictionData

A restriction which specifies the criteria to be used for the search. For details about restrictions, see [\[MS-OXCDATA\]](#) section 2.12.

##### 2.2.2.14.1.4 Origin

This **BYTE** field [\[MS-DTYP\]](#) specifies the bookmark and MUST be set to either one of the pre-defined bookmark values or BOOKMARK\_CUSTOM. For details about bookmarks, see sections [2.2.2.1.1](#) and [2.2.2.1.2](#).

##### 2.2.2.14.1.5 BookmarkSize

This **WORD** field [\[MS-DTYP\]](#) specifies the size, in bytes, of the **Bookmark** field. If the **Origin** field specifies a pre-defined bookmark, this field MUST be set to 0x0000.

##### 2.2.2.14.1.6 Bookmark

This field specifies the bookmark from which to begin the search. The bookmark MUST be one that was returned by a previous [RopCreateBookmark](#) request. The bookmark MUST NOT have been previously freed using [RopFreeBookmark](#). If the **Origin** field specifies a pre-defined bookmark, this field MUST NOT be present in the request.

## 2.2.2.14.2 Response Field Overview

### 2.2.2.14.2.1 RowNoLongerVisible

This **BYTE** field [\[MS-DTYP\]](#) indicates whether the row to which the bookmark pointed, is no longer visible. This field **MUST** be set to TRUE (0x01) if the row to which the bookmark pointed, has been removed from the table. (For example, the row's properties changed so that it didn't match the restriction, the row was deleted, or the row's header row has been collapsed.) Otherwise, this field **MUST** be set to FALSE (0x00).

When the row to which the bookmark pointed is no longer visible, the search will begin from the next row after the bookmark in the table. When searching backward, the search will not consider the row to which the bookmark is currently pointing, but will begin at the previous row.

### 2.2.2.14.2.2 HasRowData

This is a **BYTE** field [\[MS-DTYP\]](#) that specifies whether a row meeting the specified criteria was found. If a row that meets the specified criteria was found, this field **MUST** be set to TRUE (0x01).

### 2.2.2.14.2.3 RowData

This field contains a **PropertyRow** structure that specifies the row. If the value of the **HasRowData** field is TRUE, the **RowData** field **MUST** be present. If the value of **HasRowData** is FALSE, the **RowData** field **MUST NOT** be present.

For details about the **PropertyRow** structure, see [\[MS-OXCDATA\]](#) section 2.8.1.

## 2.2.2.15 RopFreeBookmark Semantics

[RopFreeBookmark](#) frees the memory associated with a bookmark that was returned by a previous [RopCreateBookmark](#) request. After the bookmark has been released, attempts to use the bookmark will fail with `ecInvalidBookmark`. This ROP is only valid on Table objects.

The server processing behaviors for [RopFreeBookmark](#), including the complete list of possible error codes returned, are further specified in section [3.2.5.15](#).

## 2.2.2.15.1 Request Field Overview

### 2.2.2.15.1.1 BookmarkSize

This **WORD** field [\[MS-DTYP\]](#) specifies the size, in bytes, of the **Bookmark** field.

### 2.2.2.15.1.2 Bookmark

This field specifies the bookmark to be freed. The bookmark **MUST** be one that was returned by a previous [RopCreateBookmark](#) request. The bookmark **MUST NOT** have been previously freed using [RopFreeBookmark](#).

## 2.2.2.15.2 Response Field Overview

There are no ROP-specific response Fields.

## 2.2.2.16 RopResetTable Semantics

[RopResetTable](#) performs the following actions:



- Removes the existing column set, restriction, and sort order from the table.
- Invalidates bookmarks.
- Resets the cursor to the beginning of the table.

This ROP is only valid on Table objects.

After sending this ROP, a [RopSetColumns](#) request MUST be sent prior to sending a [RopFindRow](#), [RopQueryRows](#), or [RopExpandRow](#) request. Existing bookmarks SHOULD be freed using [RopFreeBookmark](#). The client can choose not to send [RopFreeBookmark](#); however, this can degrade server performance until the table is released by using [RopRelease](#). For details about [RopRelease](#), see [\[MS-OXCROPS\]](#) section 2.2.15.3.

### 2.2.2.16.1 Request Field Overview

There are no ROP-specific request fields.

### 2.2.2.16.2 Response Field Overview

There are no ROP-specific response fields.

### 2.2.2.17 RopExpandRow Semantics

[RopExpandRow](#) expands a collapsed category of a table and returns the rows that belong in the newly expanded category. The maximum number of **leaf rows** to be returned can be specified. This ROP is only valid on Table objects.

#### 2.2.2.17.1 Request Field Overview

##### 2.2.2.17.1.1 MaxRowCount

This **WORD** field [\[MS-DTYP\]](#) specifies the maximum number of leaf rows to be returned in the response.

##### 2.2.2.17.1.2 CategoryId

This 8-byte field specifies the category to be expanded. This field is set to the value of the [PidTagInstID](#) property of the category's header row.

#### 2.2.2.17.2 Response Field Overview

##### 2.2.2.17.2.1 ExpandedRowCount

This **ULONG** field [\[MS-DTYP\]](#) specifies the total number of rows that are in the expanded category.

##### 2.2.2.17.2.2 RowCount

This **WORD** field [\[MS-DTYP\]](#) specifies the number of **PropertyRow** structures that are contained in the **RowData** field. The value of this field MUST be less than or equal to both of the following:

- The value of the **MaxRowCount** field in the ROP request buffer.
- The value of the **ExpandedRowCount** field in the ROP response buffer.

### 2.2.2.17.2.3 RowData

This field contains an array of **PropertyRow** structures, each of which specifies a row in the expanded category. For details about the **PropertyRow** structure, see [\[MS-OXCDATA\]](#) section 2.8.1.

### 2.2.2.18 RopCollapseRow Semantics

[RopCollapseRow](#) collapses an expanded category. This ROP is only valid on Table objects.

#### 2.2.2.18.1 Request Field Overview

##### 2.2.2.18.1.1 CategoryId

This 8-byte field specifies the category to be collapsed. This field is set to the value of the [PidTagInstID](#) property of the category's header row.

#### 2.2.2.18.2 Response Field Overview

##### 2.2.2.18.2.1 CollapsedRowCount

This **ULONG** field [\[MS-DTYP\]](#) specifies the number of rows that have been collapsed.

### 2.2.2.19 RopGetCollapseState Semantics

[RopGetCollapseState](#) returns the data necessary to rebuild the current expanded/collapsed state of the table. The data returned is in the form of an opaque BLOB that can be passed to a [RopSetCollapseState](#) request. This ROP is only valid on Table objects.

#### 2.2.2.19.1 Request Field Overview

##### 2.2.2.19.1.1 RowId

This 8-**BYTE** field [\[MS-DTYP\]](#) specifies the row to be preserved as the current cursor, which is returned in the **CollapseState** field of the [RopGetCollapseState](#) response. This field is set to the value of the [PidTagInstID](#) property of the row to be preserved as the current cursor.

##### 2.2.2.19.1.2 RowInstanceNumber

This **ULONG** field [\[MS-DTYP\]](#) is set to the value of the [PidTagInstanceNum](#) property of the row to be preserved as the current cursor, which is returned in the **CollapseState** field of the [RopGetCollapseState](#) response.

#### 2.2.2.19.2 Response Field Overview

##### 2.2.2.19.2.1 CollapseStateSize

This **WORD** field specifies the size, in bytes, of the **CollapseState** field.

##### 2.2.2.19.2.2 CollapseState

This field contains the data necessary for [RopSetCollapseState](#) to rebuild the table's collapsed state, including the current cursor.

## 2.2.2.20 RopSetCollapseState Semantics

[RopSetCollapseState](#) rebuilds a table's collapsed state, which is specified by the data returned from [RopGetCollapseState](#). The [RopSetCollapseState](#) response contains a bookmark referencing the row that was identified by the **RowId** and **RowInstanceNumber** fields in the [RopGetCollapseState](#) request. This ROP is only valid on Table objects.

The collapsed state sent to the server need not have been retrieved from the same table to which it is being applied. The table **MUST** have the same sort and restriction for the ROP to succeed. If the table is not the same table from which the collapse state was retrieved, the bookmark specified in the [RopSetCollapseState](#) response will be invalid. The bookmark returned **MUST** be freed by using [RopFreeBookmark](#).

### 2.2.2.20.1 Request Field Overview

#### 2.2.2.20.1.1 CollapseStateSize

This **WORD** field [\[MS-DTYP\]](#) specifies the size, in bytes, of the **CollapseState** field.

#### 2.2.2.20.1.2 CollapseState

This field contains the data that is necessary to rebuild the table's collapsed state. This data is obtained by sending a [RopGetCollapseState](#) request.

### 2.2.2.20.2 Response Field Overview

#### 2.2.2.20.2.1 BookmarkSize

This **WORD** field [\[MS-DTYP\]](#) specifies the size, in **BYTES**, of the **Bookmark** field.

#### 2.2.2.20.2.2 Bookmark

This field contains the bookmark data for the row stored as the current cursor, which was passed in the **CollapseState** field of the [RopSetCollapseState](#) request.

## 3 Protocol Details

### 3.1 Client Details

A table is not a static representation of data. Table rows can be modified, moved, created, and deleted while the Table object is in use. Table notifications are used to inform the client of all changes made to the table since it was opened.

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

Tabular data is retrieved by a client from the server, and then read, navigated, filtered, sorted, and grouped using the properties and operations specified in the Table Object Protocol.

When retrieving a table from the server, the set of properties returned for each row can be limited by a column set, and which rows are returned can be limited by a restriction. The order in which rows are returned can be specified by the sort order.

Additionally, tables can categorize rows by column values, and if a table has multi-value properties, it can have multi-value instances, which allows for categorization based on these multi-value instances.

Navigation in a table is aided by using a cursor and bookmarks. The current location in a table is determined by the cursor position, which points to a row of data. A row can also be referred to by a bookmark. Three pre-defined bookmarks point to the current position, the beginning of a table, and the end of a table.

A client can have more than one table opened on each data source. Each table is independent and has its own cursor, bookmarks, sort order, restriction, column set, and notification requests.

#### 3.1.2 Timers

There are no timers specific to this protocol.

#### 3.1.3 Initialization

A client can begin using this protocol with a valid table handle. The method to open the table and acquire a handle is dependent on the table's type. The types of tables are specified in section [1.5](#).

#### 3.1.4 Higher-Layer Triggered Events

##### 3.1.4.1 Preparing the Table

When a higher layer, or the user, needs to modify the column set, the client MUST send [RopSetColumns](#) to change the column set.

When a higher layer, or the user, needs to modify the sort order, the client MUST send [RopSortTable](#) to change the sort order. [RopSortTable](#) is only supported on contents tables.

In order to categorize a table, the category properties MUST be the first properties in the **SortOrders** array passed to [RopSortTable](#). The number of category properties MUST be set in the **CategoryCount** field passed to [RopSortTable](#).

When a higher layer, or the user, needs to filter the rows returned in [RopQueryRows](#), [RopFindRow](#), or [RopExpandRow](#), the client MUST send [RopRestrict](#) to change the filter applied to the table.

When a higher layer, or the user, needs to clean up the table by removing old sorts, column sets or restrictions, the client MUST send [RopResetTable](#). After doing this, the client MUST send [RopSetColumns](#) before sending [RopQueryRows](#), [RopFindRow](#), or [RopExpandRow](#).

If a request to [RopSetColumns](#), [RopSortTable](#), or [RopRestrict](#) fails, the client can send [RopResetTable](#) before retrying the failed message.

If [RopSetColumns](#) fails, the client MUST consider the table as invalid and MUST NOT send any other ROPs on it until a successful [RopSetColumns](#) or [RopResetTable](#) is made.

If [RopSortTable](#) fails, the client MUST consider the table as invalid and MUST NOT send any ROPs on it until a successful [RopSortTable](#) or [RopResetTable](#) is made.

If [RopRestrict](#) fails, the client MUST consider the table as invalid and MUST NOT send any ROPs on it until a successful [RopRestrict](#) or [RopResetTable](#) is made.

#### 3.1.4.1.1 Asynchronous Table Preparation

The client MAY request that the server perform [RopSetColumns](#), [RopSortTable](#), or [RopRestrict](#) asynchronously. <13> In this case, the client MUST NOT request additional asynchronous work to be done until pending asynchronous work is complete or cancelled using [RopAbort](#). If the client requests additional synchronous work while an existing asynchronous request is pending, the server will respond in one of two ways:

- The server returns ecBusy and does not perform the requested action.
- The server waits until the first asynchronous action is complete, then completes the synchronous action and sends the **ROP response** at that time.

When a higher layer or the user needs to know the status of pending asynchronous requests, the client MUST get the status using [RopGetStatus](#). When a higher layer, or the user, needs to abort a pending asynchronous request (to set columns, sort the table, or restrict), the client MUST send a [RopAbort](#) request. After a successful [RopAbort](#), the client MUST assume the table is in an undefined state and use [RopResetTable](#) before using the table again.

If an asynchronous request to [RopSetColumns](#), [RopSortTable](#), or [RopRestrict](#) fails with the error ecNotSupported, the client can reattempt the request synchronously.

If a [RopSetColumns](#) request fails, the client MUST assume that the table has an invalid column set and MUST perform a successful [RopSetColumns](#) before proceeding.

If a [RopSortTable](#) request fails, the client MUST assume that the table has an invalid sort and MUST perform a successful [RopSortTable](#) before proceeding.

If a [RopRestrict](#) request fails, the client MUST assume that the table has an invalid restriction and MUST perform a successful [RopRestrict](#) before proceeding.

### 3.1.4.2 Querying the Table

When a higher layer or the user requests tabular data from a table, the client MUST retrieve that information using [RopQueryRows](#) or [RopFindRow](#).

The client can get the whole table by sending [RopQueryRows](#) repeatedly with the *Advance* option until [RopQueryRows](#) returns zero rows (indicating the end of the table has been reached).

When a higher layer or the user needs to know the list of available columns for the table, the client MUST get the column list by sending [RopQueryColumnsAll](#).

When a higher layer or the user needs to collapse rows that are grouped into a category into one header row, the client MUST send [RopCollapseRow](#).

When a higher layer or the user needs to expand rows that are grouped into a collapsed header row, the client MUST send [RopExpandRow](#). The client can retrieve some or all of the rows expanded.

If the client is going to expand and collapse categories, it MUST include the [PidTagInstID](#) property in the **PropertyTags** field of the [RopSetColumns](#) request, and use the value of that property in [RopExpandRow](#), [RopCollapseRow](#), and [RopGetCollapseState](#) requests.

### 3.1.4.3 Advancing the Table

When querying the table, the client can advance the table by setting the **QueryRowsFlags** field to 0x00 in the [RopQueryRows](#) request. Additionally, when higher layers need to move the current cursor in the table, the client MUST use [RopFindRow](#), [RopSeekRow](#), [RopSeekRowBookmark](#), or [RopSeekRowFractional<14>](#) to advance to the correct row. [RopFindRow](#) can be used to both advance the table and query for the row found at the same time.

The client MUST NOT expect [RopSeekRowFractional](#) to place the cursor in any exact position. It is always an approximation.

When a higher layer or the user needs to determine the current location in a table, the client MUST send the [RopQueryPosition](#) request.

When a higher layer or the user needs to save the current location in the table for future use, the client MUST send [RopCreateBookmark](#), and cache the bookmark data.

When a higher layer, or the user, no longer needs a bookmark that was created using [RopCreateBookmark](#), the client SHOULD send [RopFreeBookmark](#) with the bookmark data. The client can choose not to send [RopFreeBookmark](#); however, this can degrade server performance until the table is released via [RopRelease](#).

When a higher layer or the user needs to move the current table location to a previously created bookmark, the client MUST send [RopSeekRowBookmark](#).

### 3.1.4.4 Getting Table State

When a higher layer or the user needs to preserve the expanded/collapsed state of the categories, it MUST send [RopGetCollapseState](#) and store the BLOB sent in the response for future use.

When a higher layer or the user needs to reset the expanded/collapsed state of the categories to a previously cached state, it MUST send [RopSetCollapseState](#) with the BLOB returned from [RopGetCollapseState](#). The bookmark sent in the response to [RopSetCollapseState](#) SHOULD be freed using [RopFreeBookmark](#). The client can choose not to send [RopFreeBookmark](#); however, this can degrade server performance until the table is released via [RopRelease](#).

### 3.1.4.5 Registering For Notifications

The protocol assumes that tables are dynamic. This means that the state on the server can significantly change while waiting for responses. If the server supports notifications on the table, the client SHOULD register for notifications and respond appropriately in order to have an accurate understanding of server state. See [\[MS-OXCNOTIF\]](#) for details about notifications.

### 3.1.5 Message Processing Events and Sequencing Rules

After opening the table or sending a [RopResetTable](#) request, the client MUST send a [RopSetColumns](#) request before querying the table for data.

The client SHOULD send a [RopSortTable](#) request before querying a contents table for data. If the client does not send a [RopSortTable](#), it MUST consider the sort order of the table as undefined.

The client can send [RopRestrict](#) before querying the table for data.

When the **TableStatus** field of the [RopSortTable](#) response has a value that is equal to TBLSTAT\_SORT\_ERROR, then [RopSortTable](#) failed, and the client MUST consider the table invalid until it receives a successful [RopSortTable](#) response. When the **TableStatus** field of the [RopSetColumns](#) response has a value that is equal to TBLSTAT\_SETCOL\_ERROR, then [RopSetColumns](#) failed, and the client MUST consider the table invalid until it receives a successful [RopSetColumns](#) response. When the **TableStatus** field of the [RopRestrict](#) response has a value that is equal to TBLSTAT\_RESTRICT\_ERROR, then [RopRestrict](#) failed, and the client MUST consider the table invalid until it receives a successful [RopRestrict](#) response.

The client SHOULD NOT send [RopAbort](#) unless the last **TableStatus** returned in a ROP response indicated that the server is executing an asynchronous task. <15> If the server has no asynchronous work executing when [RopAbort](#) is requested, it will return ecUnableToAbort in the **ReturnValue** field of the [RopAbort](#) response.

#### 3.1.5.1 Processing Notifications

The protocol assumes that tables are dynamic. This means that the state on the server can significantly change while waiting for responses. If the server supports notifications on the table, the client SHOULD register for notifications and respond appropriately in order to have an accurate understanding of server state. See [\[MS-OXCNOTIF\]](#) for details about notifications.

### 3.1.6 Timer Events

There are no timers specific to this protocol.

### 3.1.7 Other Local Events

There are no other local events specific to this protocol.

## 3.2 Server Details

### 3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

The abstract data model for the server is the same as the abstract data model for the client, as defined in section [3.1.1](#).

### 3.2.2 Timers

There are no timers specific to this protocol.

### 3.2.3 Initialization

There is no initialization specific to this protocol.

### 3.2.4 Higher-Layer Triggered Events

The server MUST send notifications to all clients that have requested them based on the appropriate triggers at higher layers. See [\[MS-OXCNOTIF\]](#) for details on notifications.

### 3.2.5 Message Processing Events and Sequencing Rules

#### 3.2.5.1 Processing Asynchronous Requests

If the client requests that the server perform [RopSetColumns](#), [RopSortTable](#), or [RopRestrict](#) asynchronously, the server MAY [<16>](#) perform the operation synchronously and return TBLSTAT\_COMPLETE in the **TableStatus** field of the ROP response buffer. However, if the server executes the ROP asynchronously, the server SHOULD return TBLSTAT\_SORTING, TBLSTAT\_SETTING\_COLS, or TBLSTAT\_RESTRICTING (depending on the ROP performed) in the **TableStatus** field of the ROP response buffer, and do the work asynchronously. The server MUST return the same **TableStatus** value in the [RopGetStatus](#) response, unless the work has been completed or [RopAbort](#) has been sent.

If there is an error setting the columns, sorting the table, or restricting, the server MUST send the **TableError** notification. The next response to [RopGetStatus](#) MUST set the **TableStatus** field to TBLSTAT\_SETCOL\_ERROR, TBLSTAT\_SORT\_ERROR, or TBLSTAT\_RESTRICT\_ERROR, depending on the ROP performed. When the asynchronous work is complete, the server MUST send the **TableSortDone**, **TableRestrictionChanged**, or **TableColumnsChanged** notifications, depending on the ROP performed. For details about these notifications, see [\[MS-OXCNOTIF\]](#) section 2.2.1.1.1.

If the client requests additional asynchronous work while the server is still performing asynchronous work, the server MUST set the value of the **ReturnValue** field in the ROP response buffer to ecBusy. If the client requests additional synchronous work while the server is still performing asynchronous work, the server can:

Set the value of the **ReturnValue** field in the ROP response buffer to ecBusy and not perform the requested action.

Wait until the first asynchronous action is complete, then complete the synchronous action and send the ROP response at that time.

#### 3.2.5.2 Processing RopSetColumns

The server MUST remember the requested columns, and apply them to the table when executing other ROPs that act on that table. The columns that are set by [RopSetColumns](#) MUST be the ones sent in the responses to subsequent [RopQueryRows](#), [RopFindRow](#), or [RopExpandRow](#) executed on that table.



If either [RopQueryRows](#) or [RopFindRow](#) is sent prior to a successful [RopSetColumns](#), then the server fails the ROP with ecNullObject.<17>

If [RopSetColumns](#) fails, the server SHOULD invalidate the table column set until a successful [RopSetColumns](#) is made. The server can restore the previous column set.

If the TBL\_ASYNC bit of the **SetColumnsFlags** field is set, the server can execute the ROP as a table-asynchronous ROP.<18> See section [3.2.5.1](#).

[RopSetColumns](#) MUST be supported for all types of tables.

If a column has the **MultivalueInstance** bit set in a **PropertyTag** structure, the server MUST expand the rows that have multiple values for the property into multi-value instances in subsequent [RopQueryRows](#), [RopFindRow](#), or [RopExpandRow](#) that are executed on the table.

The following specific error codes apply to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecInvalidParam	0x80070057, %x57.00.07.80	A property tag in the column array is of type PT_UNSPECIFIED, PT_ERROR, or an invalid type. These property types are specified in <a href="#">[MS-OXCDATA]</a> section 2.11.1.
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not of type table.

### 3.2.5.3 Processing RopSortTable

The server MUST apply the sort order to the table, and subsequent requests sent that operate on the table MUST consider the new sort order.

If a sort order is already specified, the new sort order returned with the ROP MUST replace the old sort order.

When this ROP is sent, the server MUST invalidate all current bookmarks of the table and MUST move the cursor position to the beginning of the table.

If [RopSortTable](#) is not sent (a sort order is not specified) then the table MUST be considered as having the default sort order. Default sort order is undefined.

If [RopSortTable](#) fails, the server SHOULD invalidate the table sort order until a successful [RopSortTable](#) is made. The server can restore the previous sort order.

If the TBL\_ASYNC bit of the **SortTableFlags** field is set, the server can execute the ROP as a table-asynchronous ROP.<19> See section [3.2.5.1](#).

[RopSortTable](#) MUST be supported for contents tables.

If a multi-value property has the *MultivalueInstance* bit set in the **SortOrder** structure, the server MUST sort the rows that have multiple values for the property according to the single values used in the multi-value instances in subsequent [RopQueryRows](#), [RopFindRow](#), or [RopExpandRow](#) that are executed on the table.

The following specific error codes apply to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table.

### 3.2.5.4 Processing RopRestrict

The server MUST apply the restriction to the table, and subsequent requests that operate on the table MUST consider the new restriction.

If a restriction is applied to a table, the table MUST appear as if it only contains the rows that match the restriction.

When this ROP is sent, the server MUST invalidate all current bookmarks of the table and MUST move the cursor position to the beginning of the table.

If [RopRestrict](#) is not sent (a restriction is not specified) then the table MUST be considered as not having any restriction.

If [RopRestrict](#) fails, the server SHOULD invalidate the table restriction until a successful [RopRestrict](#) is made. The server can restore the previous restriction.

If the TBL\_ASYNC bit of the **RestrictFlags** field is set, the server MAY [<20>](#) execute the ROP as a table-asynchronous ROP. See section [3.2.5.1](#).

[RopRestrict](#) MUST be supported for contents tables, hierarchy tables, and rules tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table, hierarchy table, or rules table.

### 3.2.5.5 Processing RopQueryRows

When [RopQueryRows](#) is sent the server MUST send the rows from the table starting at the current cursor position.

The number of rows sent in the response MUST be less than or equal to the number of rows specified on the **RowCount** field. The number of rows sent in the response MUST be as many rows as can fit in the ROP response buffer. Whole rows MUST always be sent (partial rows MUST NOT be sent). If there are rows to send in the database, then at least one row MUST be returned, or the ROP MUST fail with `ecBufferTooSmall` ([\[MS-OXCDATA\]](#) section 2.4). This ROP MUST only send zero rows when there are no more rows in the table.

If the **ForwardRead** field is TRUE, [RopQueryRows](#) MUST return the rows beginning at the origin, reading forward. If it is FALSE the server MUST return the rows starting at **RowCount** rows before the current cursor position, such that the **RowCount** rows before the cursor position are returned.

If the NoAdvance flag (0x01) is set in the **QueryRowsFlags** field, the server MUST NOT change the position of the cursor.

[RopSetColumns](#) MUST be sent on the table prior to sending [RopQueryRows](#). The columns sent in the response for each row MUST be the ones specified on [RopSetColumns](#).

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy. See section [3.2.5.1](#).

[RopQueryRows](#) MUST be supported for all types of tables.

The following specific error codes apply to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNullObject	0x000004B9, %xB9.04.00.00	<a href="#">RopSetColumns</a> has not been sent on this table.
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not of type table.
ecBufferTooSmall	0x0000047D, %x7D.04.00.00	The space allocated in the return buffer is insufficient to fit at least one row of data.

### 3.2.5.6 Processing RopAbort

[RopAbort](#) MUST abort the current asynchronous table ROP that is executing on the table, or send an error if there is nothing to abort or if it fails to abort.

If the server receives a [RopAbort](#) while asynchronous work is being done, it MUST abort that work. The table state after a [RopAbort](#) request is received is undefined until the server receives a [RopResetTable](#) request. This is true whether or not the [RopAbort](#) succeeds. See section [3.2.5.1](#).

[RopAbort](#) MUST be supported for contents tables and hierarchy tables.

The following specific error codes apply to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecUnableToAbort	0x80040114, %x14.01.04.80	There were no asynchronous operations to abort, or the server was unable to abort the operations.
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table or a hierarchy table.

### 3.2.5.7 Processing RopGetStatus

[RopGetStatus](#) MUST send the status of the current asynchronous execution being performed on the table in the response. <21> See section [3.2.5.1](#).

[RopGetStatus](#) MUST be supported for all types of tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not of type table.

### 3.2.5.8 Processing RopQueryPosition

[RopQueryPosition](#) MUST send the current position of the cursor, and the total number of rows in the table in the response.

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy. For details, see section [3.2.5.1](#).

[RopQueryPosition](#) MUST be supported for all types of tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not of type table.

### 3.2.5.9 Processing RopSeekRow

[RopSeekRow](#) MUST move the cursor position according to its request fields. If moving the cursor **RowCount** rows would put it past the end (or beginning, if seeking backwards) of the table, and the **WantRowMovedCount** field was TRUE in the request, the server MUST set the **HasSoughtLess** field to TRUE and set **RowsSought** to the actual number of rows moved to reach the end of the table (or, in the case of seeking backwards, to the beginning of the table).

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy. See section [3.2.5.1](#).

[RopSeekRow](#) MUST be supported for all types of tables.

The following specific error code applies to this ROP. If the server encounters this error while processing this ROP, it MUST NOT process any remaining ROPs in the ROP request buffer. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not of type table.

### 3.2.5.10 Processing RopSeekRowBookmark

[RopSeekRowBookmark](#) MUST move the cursor position according to its request fields. It should act in the same way as [RopSeekRow](#), except that it moves the cursor using a custom-defined bookmark as a reference.

If the bookmark has become invalid because of a [RopSortTable](#), [RopRestrict](#), or [RopResetTable](#), the server MUST set the **ReturnValue** field to ecInvalidBookmark. If the bookmark points to a row that is no longer visible (for example, it has been deleted, or its properties have changed so that it no

longer matches the restriction, or its header row has been collapsed) the server MUST set **RowNoLongerVisible** to TRUE, and move the cursor to the next row in the table.

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy. See section [3.2.5.1](#).

[RopSeekRowBookmark](#) MUST be supported for contents tables and hierarchy tables.

The following specific error codes apply to this ROP. If the server encounters one of these errors while processing this ROP, it MUST NOT process any remaining ROPs in the ROP request buffer. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecInvalidBookmark	0x80040405, %x05.04.04.80	The bookmark sent in the request is no longer valid.
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table or hierarchy table.

### 3.2.5.11 Processing RopSeekRowFractional

[RopSeekRowFractional](#) MUST move the cursor position in the same way as [RopSeekRow](#) does, except that the desired position is indicated as a fraction of the total table size. [<23>](#)

If the numerator is 0, the cursor MUST move to the beginning of the table.

If the numerator is greater than or equal to the denominator, the cursor MUST move to the end of the table.

The cursor MUST be moved to the place in the table that would be closest to the fraction provided. The exact location is dependent on the implementation of the server.

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy. [<24>](#) See section [3.2.5.1](#).

[RopSeekRowFractional](#) MUST be supported for all types of tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not of type table.

### 3.2.5.12 Processing RopCreateBookmark

The protocol server MUST create a custom bookmark that uniquely identifies a row in the table and can be subsequently used in [RopSeekRowBookmark](#).

The server can allocate resources on the server to keep track of the bookmark created by [RopCreateBookmark](#). If the client does not send [RopFreeBookmark](#), the server MUST release all bookmarks related to a table when that table is released (as a result of sending [ROPrelease](#) on the table) or when [RopResetTable](#), [RopSortTable](#), or [RopRestrict](#) is sent.

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy.<25> See section [3.2.5.1](#).

[RopCreateBookmark](#) MUST be supported for contents tables and hierarchy tables.

The following specific error code applies to this ROP. If the server encounters this error while processing this ROP, it MUST NOT process any remaining ROPs in the ROP request buffer. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents or hierarchy table.

### 3.2.5.13 Processing RopQueryColumnsAll

[RopQueryColumnsAll](#) MUST send all properties that can be queried for in the table in the response.

[RopQueryColumnsAll](#) MUST be supported for all types of tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Meaning
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not of type table.

### 3.2.5.14 Processing RopFindRow

[RopFindRow](#) sets the cursor position to the first row that matches the criteria specified in the ROP (starting the search from the current cursor position) and returns the found row. Rows that do not match the search criteria MUST remain unchanged in the table, but the cursor position is updated to match the found row. If no rows match the search criteria, the cursor position for [RopFindRow](#) is undefined.

If the client requested that the find be performed from a custom bookmark, but the bookmark has become invalid because of a [RopSortTable](#), [RopRestrict](#), or [RopResetTable](#), then the server MUST set the **ReturnValue** field to ecInvalidBookmark. If the bookmark points to a row that is no longer visible (for example, the row has been deleted, or its properties have changed so that it no longer matches the restriction, or its header row has been collapsed), the server MUST set the **RowNoLongerVisible** field to TRUE, and perform the find from the next row in the table.

[RopSetColumns](#) MUST be sent on the table prior to sending [RopFindRow](#). The columns sent for the row found MUST be the columns that are specified on [RopSetColumns](#).

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy.<26> See section [3.2.5.1](#).

[RopFindRow](#) MUST be supported on contents tables, hierarchy tables, and rules tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents, hierarchy, or rules table.

### 3.2.5.15 Processing RopFreeBookmark

[RopFreeBookmark](#) MUST release any resources on the server used to keep track of the bookmark (created using [RopCreateBookmark](#)).

If the client does not send [RopFreeBookmark](#), the server MUST release all bookmarks related to a table if that table is released (as a result of sending [RopRelease](#) on the table).

[RopFreeBookmark](#) MUST be supported by hierarchy tables.

[RopFreeBookmark](#) SHOULD be supported by contents tables. <27>

The following specific error codes apply to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102 %x02.01.04.80	The object on which this ROP was sent is not a hierarchy table.
ecNullObject	0x000004B9 %xB9.04.00.00	Attempted to use the bookmark after it was released.

### 3.2.5.16 Processing RopResetTable

[RopResetTable](#) MUST remove the column set previously specified by [RopSetColumns](#) (if any). The columns on the table MUST be treated as if [RopSetColumns](#) had never been sent on the table.

[RopResetTable](#) MUST remove the restriction previously applied to the table using [RopRestrict](#) (if any). The table MUST afterwards appear as if [RopRestrict](#) had never been sent on it—as if it had no restriction (all rows MUST be present).

[RopResetTable](#) MUST remove the sort order previously applied to the table using [RopSortTable](#) (if any). The table MUST afterwards appear as if [RopSortTable](#) had never been sent on it—the default sort order is undefined.

[RopResetTable](#) MUST clear any errors that currently invalidate the table (if any), such as a failed send to [RopSortTable](#) or [RopRestrict](#). Note that even though the errors for the table are cleared, it is not ready to accept [RopQueryRows](#), since its column set has not been specified (the column set can be specified by sending [RopSetColumns](#)).

[RopResetTable](#) MUST move the cursor to the beginning of the table.

After [RopResetTable](#), all previously existing bookmarks on the table are invalid.

The server MUST complete all asynchronous table ROPs prior to executing this ROP or fail the ROP with ecBusy. <28> See section [3.2.5.1](#).

[RopResetTable](#) MUST be supported on contents tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table.

### 3.2.5.17 Processing RopExpandRow

[RopExpandRow](#) MUST set a category row to expanded state.

[RopExpandRow](#) MUST be supported for contents tables.

The following specific error codes apply to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotFound	0x8004010F, %x0F.01.04.80	The row specified by the <b>CategoryId</b> field was not found.
ecNotCollapsed	0x000004F8, %xF8.04.00.00	The row specified by the <b>CategoryId</b> field was not collapsed.
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table.

### 3.2.5.18 Processing RopCollapseRow

[RopCollapseRow](#) MUST set a category row to collapsed state.

[RopCollapseRow](#) MUST be supported for contents tables.

The following specific error codes apply to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotFound	0x8004010F, %x0F.01.04.80	The row specified by the <b>CategoryId</b> field was not found.
ecNotExpanded	0x000004F7, %xF7.04.00.00	The row specified by the <b>CategoryId</b> field was not expanded.
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table.

### 3.2.5.19 Processing RopGetCollapseState

[RopGetCollapseState](#) MUST send the collapsed state of the whole table in the **CollapseState** field of the response. The collapsed state indicates what categories are expanded. It MUST also include a bookmark to the row indicated by **RowId** and **RowInstanceNumber**.



[RopGetCollapseState](#) MUST be supported for contents tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table.

### 3.2.5.20 Processing RopSetCollapseState

[RopSetCollapseState](#) MUST modify the collapsed state of the table to match the collapsed state being sent. The collapsed state indicates what categories are expanded. It MUST also move the cursor position to the row specified by the bookmark.

[RopSetCollapseState](#) MUST be supported for contents tables.

The following specific error code applies to this ROP. For more details about ROP errors returned, see Error Codes in [\[MS-OXCDATA\]](#) section 2.4.

Name	Value	Description
ecNotSupported	0x80040102, %x02.01.04.80	The object on which this ROP was sent is not a contents table.

### 3.2.6 Timer Events

There are no timers specific to this protocol.

### 3.2.7 Other Local Events

There are no other local events specific to this protocol.

## 4 Protocol Examples

The following examples illustrate the byte order of ROPs in a buffer being prepared for transmission. Please note that the examples listed here only show the relevant portions of the specified ROPs; this is not the final byte sequence which gets transmitted over the wire. Also note that the data for a multi-byte field appear in **little-endian** format, with the bytes in the field presented from least significant to most significant. Generally speaking, these ROP requests are packed with other ROP requests and are compressed and packed in one or more **RPC** calls according to the specification in [\[MS-OXCRPC\]](#). These examples assume the client has already successfully logged on to the server and opened the table. Unless otherwise noted, these examples are additive; the second example is performed after the first example, and so on. For details, see [\[MS-OXCROPS\]](#).

Examples in this section use the following format for byte sequences:

**0080**: 45 4d 53 4d 44 42 2e 44-4c 4c 00 00 00 00 00

The bold value at the far left is the offset of the following bytes into the buffer, expressed in hexadecimal notation. Following the offset is a series of up to 16 bytes, with each two character sequence describing the value of 1 byte in hexadecimal notation. Here, the underlines byte "4d" (01001101) is located 0x83 bytes (131 bytes) from the beginning of the buffer. The dash between eighth byte ("44") and ninth byte ("4c") has no semantic value, and serves only to distinguish the 8-byte boundary for readability purposes.

Such a byte sequence is then followed by one or more lines interpreting it. In larger examples, the byte sequence is shown once in its entirety and then repeated in smaller chunks, with each smaller chunk interpreted separately.

The following example shows how a property tag and its property value are represented in a buffer and interpreted directly from it (according to the **TaggedPropertyValue** structure format specified in [\[MS-OXCDATA\]](#) section 2.11.4). The property tag appears in the buffer in little-endian format.

0021: 03 00 76 66 0a 00 00-00

PropertyTag: 0x66760003 ([PidTagRuleSequence](#))

PropertyValue: 10

Generally speaking, interpreted values will be shown in their native format, interpreted appropriately from the raw byte sequence as described in the appropriate section. Here, the byte sequence "0a 00 00 00" has been interpreted as a **PtypInteger32** with a value of 10 because the type of the [PidTagRuleSequence](#) property is **PtypInteger32**.

### 4.1 Obtaining a Message List

The following example describes the contents of the ROP request buffer and ROP response buffer for a successful [RopGetContentsTable](#) operation, as specified in [\[MS-OXCFOLD\]](#) section 2.2.14.

#### 4.1.1 Client Request Buffer

A complete ROP request buffer is a 5-byte sequence formatted as follows:

0000: 05 00 00 01 00

The first 4 bytes are the **RopId**, **LogonID**, **InputHandleIndex**, and **OutputHandleIndex** fields, as specified in [\[MS-OXCROPS\]](#) section 2.2.4.14.1.

0000: 05 00 00 01

**RopId:** 0x05 ([RopGetContentsTable](#))

**LogonID:** 0x00

**InputHandleIndex:** 0x00. The object for which to obtain the contents table (such as a **Folder object**).

**OutputHandleIndex:** 0x01. The location to store the table.

The last byte is the **TableFlags** field, which holds the table operation flags (detailed in [\[MS-OXCFOOLD\]](#) section 2.2.14).

0004: 00

**TableFlags:** 0x00 (Standard)

#### 4.1.2 Server Response to Client Request

0000: 05 01 00 00 00 00 04 00-00 00

The first 6 bytes of the ROP response buffer are the **RopId**, **OutputHandleIndex**, and **ReturnValue** fields, as specified in [\[MS-OXCROPS\]](#) section 2.2.4.14.2.

0000: 05 01 00 00 00 00

**RopId:** 0x05 ([RopGetContentsTable](#))

**OutputHandleIndex:** 0x01

**ReturnValue:** 0x00000000 (Success)

The next 4 bytes are the **RowCount** field, as specified in [\[MS-OXCFOOLD\]](#) section 2.2.14.2.2, which gives the number of rows in the contents table.

**RowCount:** 0x00000004 (four rows in the table)

## 4.2 Setting the Columns on a Table

The following example describes the contents of the ROP request and ROP response buffers for a successful [RopSetColumns](#) operation as specified in section [2.2.2.2](#).

### 4.2.1 Client Request Buffer

A complete ROP request buffer is a variable length sequence, with 6 required bytes and 4 bytes for each property tag to be included in the columns set. An example of the ROP request buffer is as follows:

```
0000: 12 00 01 00 06 00 14 00-48 67 14 00 4a 67 14 00
0010: 4d 67 03 00 4e 67 1f 00-37 00 40 00 06 0e
```

The first 3 bytes of the ROP request buffer are the **RopId**, **LogonID**, and **InputHandleIndex** fields of [RopSetColumns](#), as specified in [\[MS-OXCROPS\]](#) section 2.2.5.1.1.

```
0000: 12 00 01
```

**RopId:** 0x12 ([RopSetColumns](#))

**LogonID:** 0x00

**InputHandleIndex:** 0x01

The next 3 bytes are the **SetColumnsFlags** and **PropertyTagCount** fields of [RopSetColumns](#), defined in section [2.2.2.2.1](#). For more details on property buffer format, see [\[MS-OXCADATA\]](#).

```
0003: 00 06 00
```

**SetColumnsFlags:** 0x00. Perform this operation synchronously.

**PropertyValueCount:** 0x0006. Six 4-byte **PropertyTags** follow.

The remaining bytes are the **PropertyTags** field, which holds an array of 4-byte property tags.

```
0006: 14 00 48 67 14 00 4a 67-14 00 4d 67 03 00 4e 67
0016: 1f 00 37 00 40 00 06 0e
```

**PropertyTag:** 0x67480014 ([PidTagFolderId](#))

**PropertyTag:** 0x674a0014 ([PidTagMid](#))

**PropertyTag:** 0x674d0014 ([PidTagInstID](#))

**PropertyTag:** 0x674e0003 ([PidTagInstanceNum](#))

**PropertyTag:** 0x0037001f ([PidTagSubject](#))

**PropertyTag:** 0x0e060040 ([PidTagMessageDeliveryTime](#))

## 4.2.2 Server Response to Client Request

```
0000: 12 01 00 00 00 00 00
```

The first 6 bytes of the ROP response buffer are the **RopId**, **InputHandleIndex**, and **ReturnValue** fields.

**RopId:** 0x12 ([RopSetColumns](#))

**InputHandleIndex:** 0x01

**ReturnValue:** 0x00000000 (Success)

The final byte in the ROP response buffer is the **TableStatus** field, described in section [2.2.2.1.3](#).

```
0006: 00
```

**TableStatus:** 0x00. This value is TBLSTAT\_COMPLETE, indicating that the operation has been completed.

### 4.3 Sorting a Table by Time Delivered

The following example describes the contents of the ROP request and ROP response buffers for a successful [RopSortTable](#) operation as described in section [2.2.2.3](#).

#### 4.3.1 Client Request Buffer

A complete ROP request buffer is a variable length sequence, with 10 required bytes and 5 bytes for each sorting flag used. An example of the ROP request buffer is as follows:

```
0000: 13 00 01 00 01 00 00 00-00 00 40 00 06 0e 01
```

The first 3 bytes of the ROP request buffer are the **RopId**, **LogonID**, and **InputHandleIndex** fields of [RopSetColumns](#) as specified in [\[MS-OXCROPS\]](#) section 2.2.5.1.1.

```
0000: 13 00 01
```

**RopId:** 0x13 ([RopSortTable](#))

**LogonID:** 0x00

**InputHandleIndex:** 0x01. Index in **handle array** for the table to be sorted.

The next 7 bytes are the **SortTableFlags**, **SortOrderCount**, **CategoryCount**, and **ExpandedCount** fields defined in section [2.2.2.3.1](#).

```
0003: 00 01 00 00 00 00 00
```

**SortTableFlags:** 0x00. Perform the operation synchronously.

**SortOrderCount:** 0x0001. Number of **SortOrder** structures to follow

**CategoryCount:** 0x0000

**ExpandedCount:** 0x0000

The remaining bytes are the **SortOrders** field, which contain properties to sort by (where there must be exactly **SortOrderCount** properties) and a sorting method (defined in section [2.2.2.3.1.5](#)).

```
000a: 40 00 06 0e 01
```

**PropertyTag:** 0x0e060040 ([PidTagMessageDeliveryTime](#))

**Order:** 0x01 (Flag: TABLE\_SORT\_DESCEND)

### 4.3.2 Server Response to Client Request

```
0000: 13 01 00 00 00 00 00
```

The first 6 bytes of the ROP response buffer are the **RopId**, **InputHandleIndex**, and **ReturnValue** fields.

```
0000: 13 01 00 00 00 00
```

**RopId:** 0x13 ([RopSortTable](#))

**InputHandleIndex:** 0x01

**ReturnValue:** 0x00000000 (Success)

The final byte in the ROP response buffer is the **TableStatus** field described in section [2.2.2.3.2.1](#).

```
0006: 00
```

**TableStatus:** 0x00. This value is TBLSTAT\_COMPLETE, indicating that the sorting operation has been completed.

## 4.4 Querying Rows

The following example describes the contents of the ROP request and ROP response buffers for a successful [RopQueryRows](#) operation as described in section [2.2.2.5](#).

### 4.4.1 Client Request Buffer

A complete ROP request buffer for [RopQueryRows](#) is a 7-byte sequence formatted as follows:

```
0000: 15 00 01 00 01 32 00
```

The first 3 bytes are the **RopId**, **RopId**, and **InputHandleIndex** fields as specified in [\[MS-OXCROPS\]](#) section 2.2.5.4.1.

```
0000: 15 00 01
```

**RopId:** 0x15 ([RopQueryRows](#))

**LogonID:** 0x00

**InputHandleIndex:** 0x01. The handle of the table to query.

The final 4 bytes of the ROP request buffer are the **QueryRowsFlags**, **ForwardRead**, and **RowCount** fields described in section [2.2.2.5.1](#).

```
0003: 00 01 32 00
```

**QueryRowsFlags:** 0x00. Advance the table cursor.

**ForwardRead:** 0x01. Read the table forward.

**RowCount:** 0x0032. Return a maximum of 50 rows.

#### 4.4.2 Server Response to Client Request

```
0000: 15 01 00 00 00 02 04-00 01 00 01 00 00 00 00
0010: 00 14 88 00 01 00 00-0b 3f 87 47 00 01 00 00
0020: 00 0b 3f 87 47 00 00-00 00 00 01 00 00 00 0a
0030: 0f 01 04 80 00 49 00 50-00 4d 00 2e 00 4e 00 6f
0040: 00 74 00 65 00 00 00-ff ff ff ff 00 00 00 00
0050: 00 0a 0f 01 04 80 00 00-00 00 00 00 23 00 00 00
0060: 0a 0f 01 04 80 0a 0f 01-04 80 0a 0f 01 04 80 0a
0070: 0f 01 04 80 0a 0f 01 04-80 0a 0f 01 04 80 00 ea
0080: 04 00 00 00 1d 05 03 ea-55 73 c8 01 00 6d 00 79
0090: 00 53 00 75 00 62 00 6a-00 65 00 63 00 74 00 00
00a0: 00 00 52 00 45 00 3a 00-20 00 6d 00 79 00 53 00
00b0: 75 00 62 00 6a 00 65 00-63 00 74 00 00 00 00 41
00c0: 00 75 00 74 00 6f 00 55-00 73 00 65 00 72 00 32
00d0: 00 30 00 30 00 30 00 31-00 00 00 0a 0f 01 04 80
00e0: 0a 0f 01 04 80 00 00 00-00 00 01 00 00 00 00 10
00f0: 00 f6 e9 ad 14 41 50 e6-4d 9f 42 64 6e d0 98 c2
```

The first 6 bytes of the ROP response buffer are the **RopId**, **InputHandleIndex**, and **ReturnValue** fields.

```
0000: 15 01 00 00 00 00
```

**RopId:** 0x15 ([RopQueryRows](#))

**InputHandleIndex:** 0x01

**ReturnValue:** 0x00000000 (Success)

The next 3 bytes are the **Origin** and **RowCount** fields described in section [2.2.2.5.2](#).

```
0006: 02 04 00
```

**Origin:** 0x02. Corresponds to bookmark BOOKMARK\_END.

**RowCount:** 0x0004. Four row property arrays follow in the response.

The remaining bytes in the ROP response buffer are for the **RowData** array, which consists of a **HasError** field for the row and a **ColumnArray** of properties.

```
0009: 01 00 01 00 00 00 00 00-14 88 00 01 00 00 00 0b
0019: 3f 87 47 ...
```

**HasError:** 0x01 (for the row)

**ErrorType:** 0x00

**FlaggedPropertyValue:** 0x8814000000000001. From the [RopSetColumns](#) operation, this property is [PidTagFolderId](#) (0x67480014) because the order must be maintained.

**ErrorType:** 0x00

**FlaggedPropertyValue:** 0x47873f0b00000001. From the [RopSetColumns](#) operation, this property is [PidTagMid](#) (0x674a0014) because the order must be maintained.

This format continues for the remainder of the column properties and then for the remainder of the rows.

## 4.5 Working with Categories

The following sections give examples of sorting, expanding a row, and querying messages that have been categorized. These examples are separate and do not follow from the ones above.

### 4.5.1 Sorting a Table by Category

The following example describes the contents of the ROP request and ROP response buffers for a successful [RopSortTable](#) operation for category (ascending) and time (descending) sort as described in section [2.2.2.3](#).

#### 4.5.1.1 Client Request Buffer

A complete ROP request buffer is a variable length sequence, with 10 required bytes and 5 bytes for each sorting flag used. An example of the ROP request buffer is as follows:

```
0000: 13 00 00 00 02 00 01 00-01 00 1f 30 08 80 00 40
0010: 00 06 0e 01
```

The first 3 bytes of the ROP request buffer are the **RopId**, **LogonID**, and **InputHandleIndex** fields of [RopSortTable](#), as specified in [\[MS-OXCROPS\]](#) section 2.2.5.2.1.

```
0000: 13 00 00
```

**RopId:** 0x13 ([RopSortTable](#))

**LogonID:** 0x00

**InputHandleIndex:** 0x00. Index in handle array for the table to be sorted.



The next 7 bytes are the **SortTableFlags**, **SortOrderCount**, **CategoryCount**, and **ExpandedCount** fields defined in section [2.2.2.3.1](#).

```
0003: 00 02 00 01 00 01 00
```

**SortTableFlags:** 0x00. Perform the operation synchronously.

**SortOrderCount:** 0x0002. Number of sort order structures to follow.

**CategoryCount:** 0x0001. There is one category column.

**ExpandedCount:** 0x0001. All categories are expanded.

The remaining bytes are the **SortOrders** field, which contain properties to sort by (where there must be exactly **SortOrderCount** properties) and a sorting method (defined in section [2.2.2.3.1.5](#)).

```
000a: 1f 30 08 80 00 40 00 06-0e 01
```

**PropertyTag:** 0x8008301F ([PidTagTcvConstLongOne](#))

**Order:** 0x00 (Flag: TABLE\_SORT\_ASCEND)

**PropertyTag:** 0x0E060040 ([PidTagMessageDeliveryTime](#))

**Order:** 0x01 (Flag: TABLE\_SORT\_DESCEND)

#### 4.5.1.2 Server Response to Client Request

```
0000: 13 00 00 00 00 00 00
```

The first 6 bytes of the ROP response buffer are the **RopId**, **InputHandleIndex**, and **ReturnValue** fields.

```
0000: 13 00 00 00 00 00
```

**RopId:** 0x13 ([RopSortTable](#))

**InputHandleIndex:** 0x00

**ReturnValue:** 0x00000000 (Success)

The final byte in the ROP response buffer is the **TableStatus** field described in section [2.2.2.3.2.1](#).

```
0006: 00
```

**TableStatus:** 0x00. This value is TBLSTAT\_COMPLETE, indicating that the sorting operation has been completed.

## 4.5.2 Expanding a Category Row

The following example describes the contents of the ROP request and ROP response buffers for a successful [RopExpandRow](#) operation as described in section [2.2.2.17](#).

### 4.5.2.1 Client Request Buffer

A complete ROP request buffer is a 13-byte sequence, formatted as follows:

```
0000: 59 00 01 00 00 01 00 00-00 00 f1 88 bd
```

The first 3 bytes of the ROP request buffer are the **RopId**, **LogonID**, and **InputHandleIndex** fields of [RopExpandRow](#) as specified in [\[MS-OXCROPS\]](#) section 2.2.5.16.1.

```
0000: 59 00 00
```

**RopId:** 0x59 ([RopExpandRow](#))

**LogonID:** 0x00

**InputHandleIndex:** 0x01

The remaining 13 bytes are the **MaxRowCount** and **CategoryId** fields described in section [2.2.2.17.1](#).

```
0003: 00 00 01 00 00 00 00 f1-88 bd
```

**MaxRowCount:** 0x0000. Rows will be expanded but not returned in the response.

**CategoryId:** 0xbd88f10000000001. The [PidTagInstID](#) of the category row to expand.

### 4.5.2.2 Server Response to Client Request

```
0000: 59 01 00 00 00 00 03 00-00 00 00 00
```

The first 6 bytes of the ROP response buffer are the **RopId**, **InputHandleIndex**, and **ReturnValue** fields.

```
0000: 59 00 00 00 00 00
```

**RopId:** 0x59 ([RopExpandRow](#))

**InputHandleIndex:** 0x00

**ReturnValue:** 0x00000000 (Success)

The remaining bytes are the **ExpandedRowCount**, **RowCount**, and **RowData** fields described in section [2.2.2.17.2](#).

```
0006: 03 00 00 00 00 00
```

**ExpandedRowCount:** 0x00000003. There are a total of three rows in the expanded category.

**RowCount:** 0x0000. No row data follows.

**RowData:** [EMPTY]

### 4.5.3 Querying Rows with Category View

The following example describes the contents of the ROP request and ROP response buffers for a successful [RopQueryRows](#) operation as described in section [2.2.2.17](#) when the messages are grouped by category.

#### 4.5.3.1 Client Request Buffer

A complete ROP request buffer for [RopQueryRows](#) is a 7-byte sequence formatted as follows:

```
0000: 15 00 00 00 01 32 00
```

The first 3 bytes are the **RopId**, **LogonID**, and **InputHandleIndex** fields as specified in [\[MS-OXCROPS\]](#) section 2.2.5.4.1.

```
0000: 15 00 00
```

**RopId:** 0x15 ([RopQueryRows](#))

**LogonID:** 0x00

**InputHandleIndex:** 0x00. The handle of the table to query.

The final 4 bytes of the ROP request buffer are the [QueryRowsFlags](#), [ForwardRead](#), and [RowCount](#) fields described in section [2.2.2.5.2](#).

```
0003: 00 01 32 00
```

**QueryRowsFlags:** 0x00. Advance the table cursor.

**ForwardRead:** 0x01. Read the table forward.

**RowCount:** 0x0032. Return a maximum of 50 rows.

#### 4.5.3.2 Server Response to Client Request

```
0000: 15 00 00 00 00 00 02 09-00 01 00 01 00 00 00 00
0010: f1 1f 32 0a 0f 01 04 80-00 01 00 00 00 00 f1 88
0020: bd 00 00 00 00 00 00 03-00 00 00 00 00 00 00 00
0030: 0a 0f 01 04 80 0a 0f 01-04 80 0a 0f 01 04 80 0a ...
```

The first 6 bytes of the ROP response buffer are the **RopId**, **InputHandleIndex**, and **ReturnValue** fields.

```
0000: 15 00 00 00 00 00
```

**RopId:** 0x15 ([RopQueryRows](#))

**InputHandleIndex:** 0x00

**ReturnValue:** 0x00000000 (Success)

The next 3 bytes are the **Origin** and **RowCount** fields described in section [2.2.2.5.2](#).

```
0006: 02 09 00
```

**Origin:** 0x02. Corresponds to bookmark BOOKMARK\_END.

**RowCount:** 0x0009. Nine row property arrays follow in the response.

The remaining bytes in the ROP response buffer are for the **RowData** array, which consists of a **HasError** field for the row and a **ColumnArray** of properties. The [RopSetColumns](#) request for this sequence of ROPs has not been shown.

```
0009: 01 00 01 00 00 00 00 f1-1f 32 0a 0f 01 04 80 00
0019: 01 00 00 00 00 00 f1 88 bd-00 00 00 00 00 03 00
0029: 00 00 00 00 00 00 00 0a-0f 01 04 80 0a 0f 01 04
0039: 80 0a 0f 01 04 80 0a ...
```

**HasError:** 0x01. For the entire row.

**ErrorType:** 0x00.

**FlaggedPropertyValue:** 0x321ff10000000001. This property is [PidTagFolderId](#) (0x67480014).

The format follows this pattern as covered in section [4.4.2](#), the server response buffer for the first [RopQueryRows](#) example.

Because this example is for messages with categories, there is an interesting case when one message has multiple categories assigned to it. Further into the buffer, there are the following sets of properties:

Property tag	Property value
0x674D0014 ( <a href="#">PidTagInstID</a> )	0xb773f10000000001
0x674E0003 ( <a href="#">PidTagInstanceNum</a> )	1
0x8008001F ( <a href="#">PidTagTcvConstLongOne</a> )	Category1

Property tag	Property value
0x674D0014 ( <a href="#">PidTagInstID</a> )	0xb773f10000000001
0x674E0003 ( <a href="#">PidTagInstanceNum</a> )	2
0x8008001F ( <a href="#">PidTagTcvConstLongOne</a> )	Category2

The same message appears twice in the contents table due to the category grouping. The [PidTagInstanceNum](#) property makes this phenomenon easily recognizable.

## 5 Security

### 5.1 Security Considerations for Implementers

There are no special security considerations specific to the Table Object Protocol. General security considerations pertaining to the underlying protocol apply, as specified in [\[MS-OXCROPS\]](#).

### 5.2 Index of Security Parameters

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products:

- Microsoft® Office Outlook® 2003
- Microsoft® Exchange Server 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Exchange Server 2007
- Microsoft® Outlook® 2010
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

[<1> Section 2.2.2.1.3:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<2> Section 2.2.2.1.4:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<3> Section 2.2.2.2.1.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<4> Section 2.2.2.2.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<5> Section 2.2.2.3.1.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<6> Section 2.2.2.3.2.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<7> Section 2.2.2.4.1.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<8> Section 2.2.2.4.2.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<9> Section 2.2.2.6.2.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<10> Section 2.2.2.7:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

[<11> Section 2.2.2.7.2.1:](#) Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<12> [Section 2.2.2.11](#): Exchange 2010 does not implement this ROP, but Exchange 2010 SP1 does.

<13> [Section 3.1.4.1.1](#): Office Outlook 2007 never performs asynchronous table ROPs against the server. Exchange 2010 never honors requests to perform asynchronous table ROPs

<14> [Section 3.1.4.3](#): Exchange 2010 does not support this ROP, but Exchange 2010 SP1 does.

<15> [Section 3.1.5](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<16> [Section 3.2.5.1](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<17> [Section 3.2.5.2](#): Exchange 2003 and Exchange 2007 do not fail this ROP if the columns are not set, but return a set of columns that are undefined.

<18> [Section 3.2.5.2](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<19> [Section 3.2.5.3](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<20> [Section 3.2.5.4](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<21> [Section 3.2.5.7](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<22> [Section 3.2.5.9](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<23> [Section 3.2.5.11](#): Exchange 2010 does not support **RopSeekRowFractional**, but Exchange 2010 SP1 does.

<24> [Section 3.2.5.11](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<25> [Section 3.2.5.12](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<26> [Section 3.2.5.14](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.

<27> [Section 3.2.5.15](#): Exchange 2003 and Exchange 2007 do not conform to the specification and currently send the value `ecNotSupported` in the **ReturnValue** field of the ROP response buffer for contents tables.

<28> [Section 3.2.5.16](#): Exchange 2010 does not support asynchronous operations on tables and ignores all values of asynchronous flags.



## 7 Change Tracking

This section identifies changes that were made to the [MS-OXCTABL] protocol document between the August 2010 and November 2010 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- Changes made for template compliance.
- Removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change Type
<a href="#">2 Messages</a>	58627 Removed product behavior note specifying ROPs are unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">2.2.2 Table ROPs</a>	58366 Added cross-references to [MS-DTYP] for data types in subsections where data types are mentioned.	N	Content updated.
<a href="#">2.2.2.1.2 Custom Bookmarks</a>	57627 Removed product behavior note specifying that custom bookmarks are not supported when Client Access Services are deployed on an Exchange server.	N	Content removed.
<a href="#">2.2.2.1.3 Table Status</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.1.4 Asynchronous Flags</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010	Y	New product behavior note added.
<a href="#">2.2.2.1.4 Asynchronous Flags</a>	57417 Specified behavior when TBL_ASYNC is set to 0x00 and clarified behavior when TBL_ASYNC is set to 0x01.	N	Content updated.

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change Type</b>
<a href="#">2.2.2.2.1.1 SetColumnsFlags</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010	Y	New product behavior note added.
<a href="#">2.2.2.2.1.3 PropertyTags</a>	58627 Removed product behavior note specifying ROP is unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">2.2.2.2.2.1 TableStatus</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.3.1.1 SortTableFlags</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.3.2.1 TableStatus</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.4.1.1 RestrictFlags</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.4.2.1 TableStatus</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.6.2.1 TableStatus</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.7 RopGetStatus Semantics</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.7.2.1 TableStatus</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">2.2.2.10.1.2 Bookmark</a>	58627 Removed product behavior note specifying ROP is unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">2.2.2.10.1.4 WantRowMovedCount</a>	57681 Clarified wording of return value specification.	N	Content updated.
<a href="#">2.2.2.11 RopSeekRowFractional Semantics</a>	55747 Added product behavior note specifying which product versions support this ROP.	Y	Product behavior note updated.
<a href="#">2.2.2.11.1.1 Numerator</a>	57697 Clarified description of Numerator field	N	Content updated.

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change Type</b>
<a href="#">2.2.2.18 RopCollapseRow Semantics</a>	58627 Removed product behavior note specifying ROP is unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">2.2.2.19 RopGetCollapseState Semantics</a>	58627 Removed product behavior note specifying ROP is unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">2.2.2.19.2.2 CollapseState</a>	58627 Removed product behavior note specifying ROP is unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">3.1.4.1.1 Asynchronous Table Preparation</a>	57682 Amended product behavior note specifying changes in behavior for Exchange 2010.	Y	Product behavior note updated.
<a href="#">3.1.4.1.1 Asynchronous Table Preparation</a>	58627 Removed product behavior notes specifying ROPs are unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">3.1.4.2 Querying the Table</a>	58627 Removed product behavior note specifying ROP is unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">3.1.4.3 Advancing the Table</a>	55747 Amended product behavior note specifying which product versions support a ROP.	Y	Product behavior note updated.
<a href="#">3.1.4.3 Advancing the Table</a>	58627 Removed product behavior notes specifying ROPs are unsupported when Client Access Services are deployed on an Exchange server.	Y	Product behavior note removed.
<a href="#">3.1.5 Message Processing Events and Sequencing Rules</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.1 Processing Asynchronous Requests</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.1 Processing Asynchronous Requests</a>	58089 Clarified text specifying behavior in processing asynchronous requests.	N	Content updated.
<a href="#">3.2.5.2 Processing RopSetColumns</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.2</a>	58272	Y	Product

<b>Section</b>	<b>Tracking number (if applicable) and description</b>	<b>Major change (Y or N)</b>	<b>Change Type</b>
<a href="#">Processing RopSetColumns</a>	Updated behavior for Exchange 2003 and Exchange 2007 when columns are not set.		behavior note updated.
<a href="#">3.2.5.3 Processing RopSortTable</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.4 Processing RopRestrict</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.4 Processing RopRestrict</a>	57741 Updated description in table to include "rules table".	N	Content updated.
<a href="#">3.2.5.7 Processing RopGetStatus</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.9 Processing RopSeekRow</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.10 Processing RopSeekRowBookmark</a>	58114 Changed error returned when bookmark is invalid from ecNotFound to ecInvalidBookmark.	N	Content updated.
<a href="#">3.2.5.11 Processing RopSeekRowFractional</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.11 Processing RopSeekRowFractional</a>	55474 Added product behavior note specifying changes in behavior for Exchange 2010 and Exchange 2010 SP1.	Y	Product behavior note updated.
<a href="#">3.2.5.12 Processing RopCreateBookmark</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.14 Processing RopFindRow</a>	58114 Changed error returned when bookmark is invalid from ecNotFound to ecInvalidBookmark.	N	Content updated.
<a href="#">3.2.5.14 Processing RopFindRow</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">3.2.5.15 Processing RopFreeBookmark</a>	57160 Changed error returned when attempting to use a bookmark after it is released from ecInvalidBookmark to ecNullObject.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change Type
<a href="#">3.2.5.16 Processing RopResetTable</a>	57682 Added product behavior note specifying changes in behavior for Exchange 2010.	Y	New product behavior note added.
<a href="#">4 Protocol Examples</a>	57470 Changed "property Buffer" to "TaggedPropertyValue structure" and added link to section in [MS-OXCADATA] that specifies the TaggedPropertyValue structure.	N	Content updated.

## 8 Index

### A

[Applicability](#) 11

### C

[Capability negotiation](#) 11

[Change tracking](#) 57

Client

[overview](#) 28

### E

Examples

[overview](#) 42

### F

[Fields – vendor-extensible](#) 11

### G

[Glossary](#) 8

### I

Implementer

[security considerations](#) 54

[Index of security parameters](#) 54

[Informative references](#) 10

[Introduction](#) 8

### M

Messages

[overview](#) 12

Messaging

[transport](#) 12

### N

[Normative references](#) 9

### O

[Overview \(synopsis\)](#) 10

### P

[Preconditions](#) 11

[Prerequisites](#) 11

[Product behavior](#) 55

### R

References

[informative](#) 10

[normative](#) 9

[Relationship to other protocols](#) 10

### S

Security

[implementer considerations](#) 54

[overview](#) 54

[parameter index](#) 54

Server

[overview](#) 31

[Standards Assignments](#) 11

### T

[Tracking changes](#) 57

[Transport](#) 12

### V

[Vendor-extensible fields](#) 11

[Versioning](#) 11