

# [MS-OXOAB]: Offline Address Book (OAB) Format and Schema Protocol Specification

## Intellectual Property Rights Notice for Protocol Documentation

- **Copyrights.** This protocol documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the protocols, and may distribute portions of it in your implementations of the protocols or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the protocol documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the protocols. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, the protocols may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>). If you would prefer a written license, or if the protocols are not covered by the OSP, patent licenses are available by contacting [protocol@microsoft.com](mailto:protocol@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** This protocol documentation is intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it. A protocol specification does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them.

Revision Summary			
Author	Date	Version	Comments
Microsoft Corporation	April 4, 2008	0.1	Initial Availability.
Microsoft Corporation	April 25, 2008	0.2	Revised and updated property names and other technical content.
Microsoft Corporation	June 27, 2008	1.0	Initial Release.
Microsoft Corporation	August 6, 2008	1.01	Revised and edited technical content.
Microsoft Corporation	September 3, 2008	1.02	Revised and edited technical content.

Microsoft Corporation	October 1, 2008	1.03	Revised and edited technical content.
Microsoft Corporation	December 3, 2008	1.04	Updated IP notice.

# Table of Contents

<b>1</b>	<b>Introduction.....</b>	<b>5</b>
1.1	Glossary .....	5
1.2	References .....	6
1.2.1	Normative References .....	6
1.2.2	Informative References .....	7
1.3	Structure Overview .....	8
1.3.1	OAB Version 2 .....	8
1.3.1.1	Uncompressed Browse File .....	10
1.3.1.2	Uncompressed RDN Index File.....	11
1.3.1.3	Uncompressed ANR Index File.....	11
1.3.1.4	Uncompressed Details File .....	11
1.3.1.5	Uncompressed Display Template File .....	11
1.3.1.6	Uncompressed Changes File.....	11
1.3.1.7	Compressed OAB Version 2 Files .....	12
1.3.2	OAB Version 4 .....	12
1.3.2.1	Uncompressed Full Details File.....	13
1.3.2.2	Property Encodings .....	14
1.3.2.3	Uncompressed Differential Patch File.....	14
1.3.2.4	Uncompressed Display Template File .....	15
1.3.2.5	Compressed OAB Details File and Compressed OAB Template file ....	15
1.3.2.6	Truncated Properties.....	15
1.4	Relationship to Protocols and Other Structures .....	15
1.5	Applicability Statement.....	16
1.6	Versioning and Localization.....	16
1.7	Vendor-Extensible Fields .....	16
<b>2</b>	<b>Structures.....</b>	<b>16</b>
2.1	X500 Distinguished Name.....	16
2.2	Uncompressed OAB Display Template File .....	17
2.2.1	OAB_HDR .....	18
2.2.2	TMPLT_ENTRY .....	19
2.2.3	NAMES_STRUCT .....	20
2.3	Uncompressed OAB Version 2 Browse file .....	20
2.3.1	OAB_HDR .....	21
2.3.2	B2_REC .....	22
2.3.3	RDN Hash Computation.....	23
2.4	Uncompressed OAB Version 2 RDN Index File .....	23
2.4.1	RDN_HDR .....	24
2.4.2	RDN2_REC .....	24
2.5	Uncompressed OAB Version 2 ANR Index File .....	26
2.5.1	OAB_HDR .....	26
2.5.2	ANR_REC .....	26
2.6	Uncompressed OAB Version 2 Details File .....	28

2.6.1	OAB_HDR .....	33
2.7	Uncompressed OAB Version 2 Changes File .....	34
2.7.1	OAB_HDR .....	35
2.7.2	CHG_REC .....	36
2.8	Compressed OAB Version 2 File .....	37
2.8.1	MDI_HDR .....	37
2.8.2	MDI_BLK .....	38
2.9	Uncompressed OAB Version 4 Full Details File .....	39
2.9.1	OAB_HDR .....	39
2.9.2	OAB_META_DATA .....	39
2.9.3	OAB_PROP_TABLE .....	40
2.9.4	OAB_PROP_REC .....	40
2.9.5	OAB_V4_REC .....	42
2.9.6	Data Encoding .....	42
2.9.6.1	PtypInteger32 (0x0003) Value Encoding .....	42
2.9.6.2	PtypBoolean (0x000B) Value Encoding .....	43
2.9.6.3	PtypString8 (0x001E) Value Encoding .....	43
2.9.6.4	PtypString (0x001F) Value Encoding .....	43
2.9.6.5	PtypBinary (0x0102) Value Encoding .....	43
2.9.6.6	PtypMultipleInteger32 (0x1003) Value Encoding .....	43
2.9.6.7	PtypMultipleString8 (0x101E) Value Encoding .....	43
2.9.6.8	PtypMultipleString (0x101F) Value Encoding .....	44
2.9.6.9	PtypMultipleBinary (0x1102) Value Encoding .....	44
2.10	Compressed OAB Version 4 Differential Patch File .....	44
2.10.1	PATCH_HDR .....	44
2.10.2	PATCH_BLK .....	45
2.11	Compressed OAB Version 4 file .....	46
2.11.1	LZX_HDR .....	46
2.11.2	LZX_BLK .....	47
<b>3</b>	<b><i>Structure Examples</i></b> .....	<b>47</b>
3.1	Full OAB Version 2 Offline Address List .....	47
3.2	Full OAB Version 4 Details File .....	51
<b>4</b>	<b><i>Security Considerations</i></b> .....	<b>54</b>
<b>5</b>	<b><i>Appendix A: Office/Exchange Behavior</i></b> .....	<b>54</b>
	<b><i>Index</i></b> .....	<b>63</b>

# 1 Introduction

This document specifies the offline address book (OAB) version 2 and OAB version 4 file formats. OABs are files that store address list information on the client, so that the client can access the information when it does not have a network connection with the server or is working offline. This specification assumes the reader has familiarity with the address book concepts and requirements of the Address Book Object protocol, as specified in [MS-OXOABK]. Those concepts and requirements are not repeated in this specification.

## 1.1 Glossary

The following terms are defined in [MS-OXGLOS]:

- address book**
- Address Book object**
- address creation template**
- address list**
- alias**
- ambiguous name resolution (ANR)**
- ASCII**
- distinguished name (DN)**
- distribution list**
- GUID**
- Lempel-Ziv Extended (LZX)**
- Lempel-Ziv Extended Delta (LZXD)**
- little-endian**
- mailbox**
- message database (MBD)**
- offline address book (OAB)**
- public folder**
- property tag**
- relative distinguished name (RDN)**
- recipient**
- Rich Text Format (RTF)**
- Simple Mail Transfer Protocol (SMTP)**
- X500 DN**

The following data types are defined in [MS-OXCDATA]:

- PtypBinary**
- PtypBoolean**
- PtypInteger32**
- PtypMultipleInteger32**
- PtypMultipleString**
- PtypMultipleString8**

## **PtypString**

### **PtypString8**

The following terms are specific to this document:

**mail agent:** An **Address Book object** other than a **remote mail user**, **mail user**, **distribution list**, or **public folder**.

**narrow character set:** A character set that represents text characters as a sequence of bytes, where each byte represents a unique character. The **ASCII** character set is a **narrow character set**.

**parent DN (PDN):** The **distinguished name** of the next immediate object closer to the root of the tree of **relative distinguished names (RDNs)**.

**remote mail user:** A collection of properties such as telephone numbers, e-mail addresses, and pager numbers pertaining to a person or business external to the messaging server.

**X509:** An ITU-T standard for Public Key Infrastructure subsequently adapted by the IETF, as specified in [RFC3280].

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## **1.2 References**

### **1.2.1 Normative References**

[ISO/IEC 8802-3] International Organization for Standardization, "Information technology -- Telecommunications and information exchange between systems -- Local and metropolitan area networks -- Specific requirements -- Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications", ISO/IEC 8802-3:2000, [http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=31002](http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=31002).

[MS-MCI] Microsoft Corporation, "MCI Compression and Decompression", June 2008.

[MS-OXCDATA] Microsoft Corporation, "Data Structures Protocol Specification", June 2008.

[MS-OXGLOS] Microsoft Corporation, "Exchange Server Protocols Master Glossary", June 2008.

[MS-OXOAB] - v1.04

Offline Address Book (OAB) Format and Schema Protocol Specification  
Copyright © 2008 Microsoft Corporation.  
Release: Wednesday, December 3, 2008

[MS-OXOABK] Microsoft Corporation, "Address Book Object Protocol Specification", June 2008.

[MS-OXOABKT] Microsoft Corporation, "Address Book User Interface Templates Protocol Specification", June 2008.

[MS-OXPFOAB] Microsoft Corporation, "Offline Address Book (OAB) Public Folder Retrieval Protocol Specification", June 2008.

[MS-OXPROPS] Microsoft Corporation, "Exchange Server Protocols Master Property List Specification", June 2008.

[MS-PATCH] Microsoft Corporation, "LZX DELTA Compression and Decompression", June 2008.

[RFC2044] Yergeau, F., "UTF-8, a transformation format of Unicode and ISO 10646", RFC 2044, October 1996, <http://www.ietf.org/rfc/rfc2044.txt>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

[RFC4234] Crocker, D., Ed. and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 4234, October 2005, <http://www.ietf.org/rfc/rfc4234.txt>.

## 1.2.2 Informative References

[ISO/IEC 8825-1] "ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)", ISO/IEC 8825-1:1998, [http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=32306](http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=32306).

[MS-ADTS] Microsoft Corporation, "Active Directory Technical Specification", July 2006, <http://go.microsoft.com/fwlink/?LinkId=112149>.

[MS-OXWOAB] Microsoft Corporation, "Offline Address Book (OAB) Retrieval Protocol Specification", June 2008.

[RFC2315] Kaliski, B., "PKCS #7: Cryptographic Message Syntax", RFC 2315, March 1998, <http://www.ietf.org/rfc/rfc2315.txt>.

[RFC3280] Housley, R., Polk, W., Ford, W., and Solo, D., "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 3280, April 2002, <http://www.ietf.org/rfc/rfc3280.txt>.

### 1.3 Structure Overview

A server can choose to make user properties, such as job titles, addresses, and telephone numbers, available to its clients in an **address book**. The address book can then be browsed or searched by clients looking for recipient information. To organize the contents of an address book, the server can divide recipients into containers and the client can choose which container to browse or search.

Each address book container is known as an **address list**. The collection of available containers, or address lists, is the address book. When the client is unable to reach the server, which can be caused by working offline or having high network costs to access the server, the client can use a local copy of the address book or address lists to retrieve user information. The local copy of the address book is known as an **offline address book (OAB)**.

An OAB is composed of three or more files that provide the full functionality of the online address book when the client is working offline. This specification describes the structure of each of the files required to create an OAB version 2 and OAB version 4 file.

#### 1.3.1 OAB Version 2

The OAB version 2 file format specifies the structure of files that are downloaded from the server to the client to support an offline address book. The OAB version 2 file consists of the following files:

- Browse file. The Browse file contains one fixed size record per user, with members that point to offsets in the RDN Index, ANR Index, and Details files. The fixed size record contains data and offsets that account for all of the user's data in the OAB version 2 file. For an overview of the Browse file, see section 1.3.1.1. For information about the structure of the Browse file, see section 2.3.
- RDN Index file. The **relative distinguished name (RDN)** Index file is used for primary key lookups based on the **X500 DN** and **Simple Mail Transfer Protocol (SMTP)** address properties of the **Address Book object**. For an overview of the RDN Index file, see section 1.3.1.2. For information about the structure of the RDN Index file, see section 2.4.
- ANR Index file. The ANR Index file is used for **ambiguous name resolution (ANR)**. Values for the display name, surname, office location, and e-mail **alias** are all sorted together into one structure so that a single search can find Address Book objects based on multiple properties. For an overview of the ANR Index file, see section 1.3.1.3. For information about the structure of the ANR Index file, see section 2.5.
- Details file. The Details file contains all other properties for **Address Book** objects in the version 2 OAB. The Details file is not indexed. The client can




choose not to download the Details file in order to save space and bandwidth since there is no information in there that is required for basic e-mail addressing. For an overview of the Details file, see section 1.3.1.4. For information about the structure of the Details file, see section 2.6.

- Display Template files. For an overview of the Display Template file, see section 1.3.1.5. For information about the structure of the Display Template file used by OAB version 2 and OAB version 4, see section 2.2.

Each of these files is compressed before synchronization to save network bandwidth.

Figure 1 shows each of these OAB files and the indexes that point from one file to another. After an OAB has been downloaded to the client, incremental updates can be downloaded using a Changes file.



**Figure 1: Relationship of the OAB version 2 files**

### 1.3.1.1 Uncompressed Browse File

The Browse file is sorted in alphabetical order according to **Address Book** object display names and allows for fast paging of **Address Book** object data. It has offsets into the other files for the display name, the surname, the office location, the X500 DN, the SMTP address, the e-mail alias, and the details record. It also maintains values for the object type and **Address Book** object display type. Each record is a fixed size. Fetching

an entire record requires that the client follow each link from the Browse file and retrieve data from the other files. The header of the Browse file includes a file type, a record count, and a serial number. The serial number is a rotating hash of the RDN value of each record in the Browse file order.

### 1.3.1.2 Uncompressed RDN Index File

The RDN Index file is split into two sections: the **parent distinguished name (PDN)** table and the RDN index. The PDN table contains the list of all parent **distinguished name** values for X500 DNs and all domain names used by SMTP addresses. The last RDN of the X500 DNs and the local-part of SMTP addresses are stored in the key field of the records in the RDN index section.

Records in the RDN index part of the file are of variable size, contain the index key value, and have pointers to the record in the PDN table so that the original value of the X500 DN or SMTP address can be reconstructed. In the record is an index of the related browse record in the Browse file and four more offsets are stored to create a threaded tree structure within the RDN Index file. An offset in the header of the RDN Index file points past the end of the PDN table to the root of the RDN index tree.

### 1.3.1.3 Uncompressed ANR Index File

The ANR Index file is structured similarly to the RDN Index file, but does not contain a PDN table. Each record is a variable size and has four offsets that construct a threaded tree structure. Records have an index of master records in the **Browse** file and the value portion is either an office location string, a surname string, an alias string, or a display name string. The root of the ANR index tree is always the first node in the file; therefore no root offset is required in the header.

### 1.3.1.4 Uncompressed Details File

The Details file contains variable size records that store a fixed set of properties for each **Address Book** object. Each record can be up to 65536 bytes long and all the stored properties for a single **Address Book** object have to fit into that record. The data is not indexed and there are no links from this file to any of the other files, but the Browse file does have links to this file.

### 1.3.1.5 Uncompressed Display Template File

The Template file describes how the **Address Book** object data can be presented to a user, as specified in [MS-OXOABKT].

### 1.3.1.6 Uncompressed Changes File

The Changes file describes the changes that need to happen to the other files to produce a file set that represents the next generational version of the OAB version 2 files. It consists of a sequence of variable size records that contain data to update individual records.

Numerous change files might be required to make a set of OAB version 2 files current with the server.

### 1.3.1.7 Compressed OAB Version 2 Files

OAB version 2 files are compressed by the server before being transferred to the client. A compressed file starts with a header and then a sequence of compressed blocks. All OAB version 2 files are compressed the same way. For more information about the compression of OAB version 2 files, see [MS-MCI].

### 1.3.2 OAB Version 4

The OAB version 4 file format specifies the structure of three files that are downloaded from the server to the client.

- Full Details file. The Full Details file contains the entire offline address book, including all **Address Book** objects, the list of property types that can be found in the address book, and information about the address book itself, including its name, a unique identity identifier, a version number, and a hash value. For an overview of the Full Details file, see section 1.3.2.1. For the structure of the Full Details file, see section 2.9.
- Differential Patch file. A Differential Patch file can be used to transform a previously downloaded version of the Full Details file to the next version of the Full Details file, which saves the client from downloading the entire Full Details file again. For an overview of the Differential Patch file, see section 1.3.2.3. For the structure of the Differential Patch file, see section 2.10.
- Display Template file. A Display Template file describes how the **Address Book** objects in the OAB can be rendered by the client on a display device to the user, as specified in [MS-EXOABKT]. For an overview of the Display Template file, see section 1.3.2.4. For the structure of the Display Template file used by OAB version 2 and OAB version 4, see section 2.2.

The **Address Book** object data in the Full Details file is not sorted in a predetermined manner, thus it is up to the client to decompress and index the file to enable fast retrieval and searches.

The files stored on the server are in a compressed format, as specified in [MS-PATCH]. All the uncompressed OAB version 4 files contain the same header structure. The OAB version 2 file consists of the following files:

- A 32 bit **little-endian** file version number. The version number used to determine the type of file: Full Details or Display Template.

- A 32 bit little-endian serial number. The serial number is a calculated value in the Full Details file and is used to validate file consistency. It is the Cyclic Redundancy Check (CRC)-32 checksum of the file not including the header structure itself. For more information about CRC-32, see [ISO/IEC 8802-3] section 3.2.8.
- A 32 bit little-endian record count. The record count tells the client how many **Address Book** objects exist in the Full Details file.

### 1.3.2.1 Uncompressed Full Details File

Apart from the OAB header, the uncompressed Full Details file consists of the following three sections:

- OAB meta-data record
- OAB header record
- One or more **Address Book** object records. Each **Address Book** object record starts with a little-endian 32 bit value that specifies the size of the record in bytes, including the record size field itself.

The OAB metadata record describes the schema of the OAB header record and **Address Book** object records. It starts with a record size value, then two schema tables: one for the OAB header record, and one for the **Address Book** object records. The tables are stored sequentially after each other. The schema tables contain a 32 bit little-endian record count followed by the specified number of 32 bit **property tag** and 32 bit flag value pairs. The flag value is used to tell the client which properties are supposed to be indexed to match the behavior of a client working online.

The first property in the OAB header record and **Address Book** object records is the record size value, followed by a presence bit array, and then the property values. The property values appear in the order provided in the property table in the metadata record. The presence bit array is used to indicate whether the property exists in the OAB header record or **Address Book** object records.

The OAB header record contains information about the address list itself, including the Unicode OAB name, the **ASCII X500** distinguished name of the OAB, an integer sequence number, and the OAB **GUID** formatted as an ASCII string.

**Address Book** object records contain at minimum an ASCII SMTP address, an ASCII distinguished name, a Unicode display name, an integer display type, and an integer object type. The number of **Address Book** object records matches the record count contained in the file header.

### 1.3.2.2 Property Encodings

ASCII strings are encoded as null terminated strings.

Unicode strings are stored as null terminated UTF-8 strings [RFC2204].

Integer values are treated as unsigned and stored in one to five bytes. If the value is less than 0x80, the value is stored as a single byte. If the value is larger than or equal to 0x80, the number of bytes that can minimally hold the value is added to 0x80 and followed by the bytes of the value itself in little-endian format. Values 0x00 through 0x7f are encoded as themselves. Values 0x80 through 0xFF are encoded as 0x81 0xXX. Values 0x0100 through 0xFFFF are encoded as 0x82 0xLSB 0xMSB. Values 0x00010000 through 0x00FFFFFF are encoded as 0x83 0xLSB 0xXX 0xMSB, and values 0x01000000 through 0xFFFFFFFF are encoded as 0x84 0xLSB 0xXX 0xXX 0xMSB.

Boolean values are stored as single bytes: 0x00 for FALSE, and 0x01 for TRUE.

Octet strings are stored using an integer byte length field first (encoded by using the preceding integer encoding rules) followed by the octet stream.

Multi-valued properties are encoded with an integer value count first (encoded by using the preceding integer encoding rules) followed by the specified number of values as encoded by the preceding rules. Multi-valued properties cannot contain empty values.

Null or empty strings are not encoded as single null terminators, but are indicated as not-present using the presence bit array.

Data encoding is specified in more detail in section 2.9.6.

### 1.3.2.3 Uncompressed Differential Patch File

The Differential Patch file cannot be uncompressed by itself as it requires the original Full Details file. The Differential Patch file describes how to transform an outdated Full Details file into another Full Details file. During transformation, the Differential Patch file is read by the client one block at a time to determine how large a block of the original Full Details file to read, how large the output block will be, and what the compressed patch data is. The patch file starts with a patch header that contains the file format version numbers, a maximum block size value, source and target file sizes, and the source and target file CRC-32 hash codes. The maximum block size value tells the client the maximum size it can expect to be required to read from the original Full Details file, the maximum size it can expect to have to write to the output file, and the size of the largest patch record that will be produced. Following the patch header are a series of patch blocks. The patch block contains the patch size in bytes to be read from the patch file, the size in bytes of the target block that will be produced, the size in bytes of the block to be read from the original Full Details file, and the CRC-32 hash that the resulting output block will have. The start and end of the source and output blocks do not necessarily fall on record boundaries of the source or output files.

### 1.3.2.4 Uncompressed Display Template File

The Display Template file describes how the **Address Book** object data can be presented to a user, as specified in [MS-OXOABKT].

### 1.3.2.5 Compressed OAB Details File and Compressed OAB Template file

Uncompressed Details and Display Template files can be very large due to the amount of information stored. In order to reduce the network traffic between the client and the server, these files are transmitted in a compressed form. A compressed file always starts with a **LZX\_HDR** structure followed by one or more **LZX\_BLK** structures. The **LZX\_HDR** structure contains a maximum block size field that is used to tell the client the maximum size of a block it can expect to have to read from the compressed file and the maximum size of a block it can expect to have to write to an output file. It is passed so that the client can pre-allocate buffers before attempting to decompress a file. Also included in the compressed Details or Display Template file is a length field that indicates what the size of the resulting decompressed file will be. It is provided to help the client allocate disk storage and determine whether the resulting output file size is correct.

Each **LZX\_BLK** structure contains a flag indicating whether the data field is compressed. If the size of a compressed block is larger than the source data, the server might choose to not compress the block and just pass it verbatim. A CRC-32 hash of the expected decompressed output block is passed to the client to help it determine if the results of decompression are valid.

### 1.3.2.6 Truncated Properties

Stored on each **Address Book** object record is a **PidTagOfflineAddressBookTruncatedProperties** attribute. This contains the list of property tags that have been truncated or dropped due to size limits. Clients ought to check the property being retrieved from the OAB record against the list of truncated properties for the record. If the property is included in the truncated property list, the value stored in the OAB file is not the same as the address book value that is available online.<1>

Two properties are exempt from truncation: **PidTagEmailAddress** (X500 DN) and **PidTagAddressBookHomeMessageDatabase** [home-message database (MDB)]. These two properties are not limited because they are primary key values that uniquely identify an object.

## 1.4 Relationship to Protocols and Other Structures

Distributing OABs requires a means of distributing the files to clients by using either public folders or a Web-based distribution method, as described in [MS-OXPFOAB] and [MS-OXWOAB] respectively.

In order to minimize communication costs, the data in the OAB is compressed, as described in [MS-PATCH] and [MS-MCI].

After the data is available to the client, a way of displaying the data is required. The client is free to choose its own method or the server's format can be used, as described in [MS-OXOABKT].

The method of naming properties in the OAB is based on the property tag naming convention, as described in [MS-OXPROPS] section 1.3.3.

### ***1.5 Applicability Statement***

The OAB structures are used to download information about the **Address Book** objects for use when working offline or in cached mode.

### ***1.6 Versioning and Localization***

None.

### ***1.7 Vendor-Extensible Fields***

The OAB version 2 and 4 structures make use of property tags, but OAB version 4 has an extensible schema. New properties can be added to OAB version 4 by a vendor by assigning property tags to Active Directory directory service properties, as described in [MS-ADTS] section 3.1.1.2.3.

## **2 Structures**

All integer fields in the OAB structures are unsigned and use little-endian byte order.

All CRC 32 hash values are calculated using the IEEE 802.3 CRC polynomial of  $0xEDB88320 (x^{32} + x^{26} + x^{23} + x^{22} + x^{16} + x^{12} + x^{11} + x^{10} + x^8 + x^7 + x^5 + x^4 + x^2 + x + 1)$  and are seeded with the value  $0xFFFFFFFF$ . For more details, see [ISO/IEC 8802-3].

All structures are packed on single byte boundaries.

All offsets are measured in bytes from the beginning of the specified file.

### ***2.1 X500 Distinguished Name***

X500 DNs are used to uniquely identify **Address Book** objects in the OAB. Each **Address Book** object **MUST** have a unique X500 DN value. The X500 DN is stored in the **PidTagEmailAddress** property, as specified in [MS-OXOABK] section 2.2.3.14. X500 DNs are structured as the following ABNF [RFC4234] definition illustrates:

```
x500-dn      =      org org-unit 0*13(container) object-rdn
                  ; x500-dns are limited to 16 levels

org           =      "/o=" rdn

org-unit     =      "/ou=" rdn

container    =      "/cn=" rdn
```



```

object-rdn    =   "/cn=" rdn

rdn           =   ( non-space-teletex ) /
                  ( non-space-teletex *62 (teletex-char)
                    non-space-teletex )
                  ; rdn values are limited to 64 characters
                  ; the number of rdns is limited to 16 but the
                  ; total cumulative length of rdn characters in
                  ; an x500-dn is limited to 256.

teletex-char =   SP / non-space-teletex

non-space-teletex =  "!" / DQUOTE / "%" / "&" / "\" / "(" / ")" /
                    "*" / "+" / "," / "-" / "." / "0" / "1" /
                    "2" / "3" / "4" / "5" / "6" / "7" / "8" /
                    "9" / ":" / "<" / "=" / ">" / "?" / "@" /
                    "A" / "B" / "C" / "D" / "E" / "F" / "G" /
                    "H" / "I" / "J" / "K" / "L" / "M" / "N" /
                    "O" / "P" / "Q" / "R" / "S" / "T" / "U" /
                    "V" / "W" / "X" / "Y" / "Z" / "[" / "]" /
                    "_" / "a" / "b" / "c" / "d" / "e" / "f" /
                    "g" / "h" / "i" / "j" / "k" / "l" / "m" /
                    "n" / "o" / "p" / "q" / "r" / "s" / "t" /
                    "u" / "v" / "w" / "x" / "y" / "z" / "|"

addresslist-x500-dn    =  "/guid=" 32 (HEXDIG) / "/" / x500-dn

```

## 2.2 Uncompressed OAB Display Template File

The Display Template file is a file that describes to the client how **Address Book** objects and e-mail addresses SHOULD be displayed to the client. The Display Template file is a package that wraps display template and **address creation template** data structures. For more details, see [MS-OXOABKT]. The following ABNF definition shows the format of an uncompressed Display Template file.

```

template-file    =   OAB_HDR mail-user-template
                    distribution-list-template
                    forum-template agent-template
                    organization-template
                    private-distributionlist-template
                    remote-mailuser-template
                    NAMES_STRUCT
                    address-templates data

mail-user-template =  TEMPLT_ENTRY
                    ; display template for mailboxes

```

```

distribution-list-template = TMPLT_ENTRY
                           ; display template for distribution lists

forum-template           =   TMPLT_ENTRY
                           ; display template for public folders

agent-template          =   TMPLT_ENTRY
                           ; display template for mail agents

organization-template = TMPLT_ENTRY
                           ; Unused, SHOULD be set to all zeros.

private-distributionlist-template = TMPLT_ENTRY
                                   ; Unused, SHOULD be set to all zeros.

remote-mailuser-template = TMPLT_ENTRY
                           ; display template for external email
                           ; addresses

address-templates =      oot-count *(address-creation-template)

oot-count             =   %x00000000-%xFFFFFFFF
                           ; 32 bits of data

address-creation-template      =   TMPLT_ENTRY
                                   ; an address creation display template
                                   ; The x500 DN MUST end in the value
                                   ; /CN=XXXX where XXXX is the mail-type
                                   ; eg: SMTP, X400, or MSMAIL

data                  =   *(OCTET)
                           ; unstructured data section

```

All the following fields that start with an ‘o’ indicate an offset from the beginning of the file into the unstructured data section.

### 2.2.1 OAB\_HDR

The **OAB\_HDR** structure is used to determine the OAB file format version.

0	1	2	3	4	5	6	7	8	9	1	2	3	4	5	6	7	8	9	2	1	2	3	4	5	6	7	8	9	3	1	
ulVersion																															
ulSerial																															
ulTotRecs																															

**ulVersion (4 bytes):** MUST be set to 0x00000007 for uncompressed Display Template files.

**ulSerial (4 bytes):** Unused, SHOULD be set to 0. Other values MUST be ignored.

**ulTotRecs (4 bytes):** Unused, SHOULD be set to 0. Other values MUST be ignored.

### 2.2.2 TMPLT\_ENTRY

The **TMPLT\_ENTRY** structure is used to encode properties of an individual display template.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
oDN																															
cbDN																															
oTmplt																															
cbTmplt																															
oScript																															
cbScript																															
oDispName																															
cbDispName																															

**oDN (4 bytes):** Absolute offset in the Display Template file to the X500 DN of the template.

**cbDN (4 bytes):** Length of the X500 DN value in bytes including the null terminator.

**oTmplt (4 bytes):** Absolute offset in the Display Template file to the template structure data. For more details, see [MS-OXOABKT].

**cbTmplt (4 bytes):** Length of the template structure data in bytes.

**oScript (4 bytes):** Absolute offset in the Display Template file of the Script file for the template. For more details, see [MS-OXOABKT] section 2.2.2.2.

**cbScript (4 bytes):** Length of the Script file data in bytes.

**oDispName (4 bytes):** Absolute offset in the Display Template file to the display name for the template. A null terminated ANSI string.

**cbDispName (4 bytes):** Length of the display name in bytes including null terminator.

### 2.2.3 NAMES\_STRUCT

The **NAMES\_STRUCT** structure is used to map GUIDs to and from property tags.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
cIDsNames																cGuids															
oIDs																															
oGuids																															
oNames																															

**cIDsNames (2 bytes):** Count of property IDs and named properties.

**cGuids (2 bytes):** Count of GUIDs.

**oIDs (4 bytes):** Absolute offset in the Display Template file to the ID table. Each ID is a 4 byte integer that represents a property tag. For more details, see [MS-OXOABKT].

**oGuids (4 bytes):** Absolute offset in the Display Template file to the GUID table. Each GUID is stored in binary format in 16 bytes. For more details, see [MS-OXOABKT].

**oNames (4 bytes):** Absolute offset in the Display Template file to the MAPINAMEID structure table. For more details, see [MS-OXOABKT].

### 2.3 Uncompressed OAB Version 2 Browse file

The following ABNF definition shows the format of an uncompressed OAB version 2 Browse file.

```

browse-file           =   OAB_HDR 1*16777213(B2_REC)

display-type         =   DT-MAILUSER / DT-DISTLIST /
                        DT-FORUM / DT-AGENT / DT-ORGANIZATION /
                        DT-REMOTE-MAILUSER
                        ; 8 bit value

DT-MAILUSER          =   %x00
                        ; mailbox display type

```

```

DT-DISTLIST      =    %x01
                  ; distribution list display type

DT-FORUM         =    %x02
                  ; public folder display type

DT-AGENT         =    %x03
                  ; mail agent display type

DT-ORGANIZATION  =    %x04
                  ; department or organization display type

DT-REMOTE-MAILUSER = %x06
                  ; external e-mail address display type

object-type      =    MAPI-FOLDER / MAPI-MAILUSER /
                    MAPI-DISTLIST
                  ; 8 bit value - high order bit is set to
                  ; 1 if the entry can receive all
                  ; message content, including Rich Text
                  ; Format (RTF) and OLE objects
                  ; see [MS-OXPROPS] section 2.924

MAPI-FOLDER      =    %x03

MAPI-MAILUSER    =    %x06

MAPI-DISTLIST    =    %x08

```

### 2.3.1 OAB\_HDR

The **OAB\_HDR** structure is used to determine the OAB file format version and the number of **Address Book** object records in the address list, and it contains a hash value for consistency checks.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulVersion																															
ulSerial																															
ulTotRecs																															

**ulVersion (4 bytes):** MUST be set to 0x0000000A for uncompressed version 2 OAB Browse files.

**ulSerial (4 bytes):** A hash of the RDN records for the current set of files.

**ulTotRecs (4 bytes):** The number of **B2\_REC** records stored in the Browse file. MUST be 1 or larger and MUST be less than 16,777,213.

### 2.3.2 B2\_REC

The **B2\_REC** structure is used to encode an **Address Book** object in the Browse file. The **Address Book** objects are sorted in the Browse file by alphabetical display name order. The locale that is used by the server to sort the files SHOULD be stored on the **public folder** message that contains the files. The client SHOULD use the stored locale for string comparison when searching the files. For more details, see [MS-OXPFOAB] section 2.2.1.5.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
oRDN																															
oDetails																															
cbDetails																bDispType								a	bObjType						
oSMTP																															
oDispName																															
oAlias																															
oLocation																															
oSurname																															

**oRDN (4 bytes):** Offset of the RDN record in the RDN Index file.

**oDetails (4 bytes):** Offset of the details record in the Details file.

**cbDetails (2 bytes):** Size of the details record in the Details file.

**bDispType (1 byte):** Display type of the **Address Book** object. MUST be set to one of the values in the following table.

Value	Meaning
0x00	DT_MAILUSER
0x01	DT_DISTLIST
0x02	DT_FORUM
0x03	DT_AGENT
0x06	DT_REMOTE_MAILUSER

**a (1 bit):** SHOULD be set to 1 if the **Address Book** object can receive all message content, including **Rich Text Format (RTF)** and OLE objects. SHOULD be set to 0 if the **Address Book** object cannot receive all message content. For more details, see [MS-OXOABK] section 2.2.3.18.

**bObjType (7 bits):** Object type of the **Address Book** object. MUST be set to one of the values in the following table.

Value	Meaning
0x03	MAPI-FOLDER
0x06	MAPI-MAILUSER
0x08	MAPI-DISTLIST

**oSMTP (4 bytes):** Offset of the SMTP address record in the RDN Index file.

**oDispName (4 bytes):** Offset of the display name record in the ANR Index file.

**oAlias (4 bytes):** Offset of the alias record in the ANR Index file.

**oLocation (4 bytes):** Offset of the office location record in the ANR Index file.

**oSurname (4 bytes):** Offset of the surname record in the ANR Index file.

### 2.3.3 RDN Hash Computation

The RDN hash value stored in the **OAB\_HDR** record of the Browse file is calculated by seeding a 4 byte integer with 0x00000000 and updated by combining the current value with a hash value of the RDN property for each record in the OAB in Browse file order.

The hash value for each RDN value is computed from the RDN value by padding the end of the null terminated string with extra nulls to align it to a 4 byte boundary. Then all the 4 byte blocks are XOR together along with the input seed. Each block is treated as a little-endian integer value. Finally the value is shifted to the left by one bit with the highest order bit being rotated into the lowest order bit.

## 2.4 Uncompressed OAB Version 2 RDN Index File

The following ABNF definition illustrates an uncompressed OAB version 2 RDN Index file.

```
rdn-file           =      RDN_HDR 1*pdn-record 1*RDN2_REC
```

*pdn-record* = 1\*(CHAR) %x00

### 2.4.1 RDN\_HDR

The **RDN\_HDR** structure is used to determine the OAB file format version and the number of RDN records in the RDN Index file, and it contains a hash value for consistency checks.

0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
ulVersion																															
ulSerial																															
ulTotRecs																															
oRoot																															

**ulVersion (4 bytes):** MUST be set to 0x0000000A for uncompressed version 2 RDN Index files.

**ulSerial (4 bytes):** Unused, SHOULD be set to zero and MUST be ignored by the client.

**ulTotRecs (4 bytes):** The number of **RDN2\_REC** records stored in the RDN Index file.

**oRoot (4 bytes):** The offset of the root **RDN2\_REC** node of the RDN index tree. This record MUST be after the last **pdn-record** in the file.

### 2.4.2 RDN2\_REC

Each **RDN2\_REC** structure corresponds to a node in the RDN index tree. The tree is constructed as a threaded tree so that searches and moving to the next and previous records are efficient.



0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
oLT																															
oGT																															
iBrowse																															
oPrev																															
oNext																															
oParentDN																															
acKey (variable)																															
...																															
...																															

**oLT (4 bytes):** Offset of the left **RDN2\_REC** child of the current node in the RDN Index file. The left child **MUST** sort to the same value as the current node or less. **MUST** be set to 0x00000000 to indicate that there is no left child node.

**oGT (4 bytes):** Offset of the right **RDN2\_REC** child of the current node in the RDN Index file. The right child **MUST** sort to the same value as the current node or greater. **MUST** be set to 0x00000000 to indicate that there is no right child node.

**iBrowse (4 bytes):** Index to the **B2\_REC** in the browse file that references this record. The values 0x00000000 through 0x00000002 are reserved and **MUST NOT** be used. The index value in the Browse file is computed by using the following equation:  $iBrowse - 0x00000003$ .

**oPrev (4 bytes):** Offset of the previous **RDN2\_REC** record in the RDN Index file when sorted as a flat list. **MUST** be set to 0x00000000 to indicate that this is the first node in the list.

**oNext (4 bytes):** Offset of the next **RDN2\_REC** record in the RDN Index file when sorted as a flat list. **MUST** be set to 0x00000000 to indicate that this is the last node in the list.

**oParentDN (4 bytes):** Offset of the null-terminated ANSI **pdn-record** string in the RDN Index file. **MUST NOT** be set to 0x00000000.

**acKey (Variable):** The null-terminated ANSI string value of the record. It **MUST** be 64 characters or fewer including the null terminator.

For RDN records, “/cn=” **MUST** be removed from the final RDN before storing in the RDN Index file. The **oParentDN** points at the parent X500 DN; therefore,

the actual value is computed by prepending the **acKey** value with “/cn=” then appending that result onto the end of the **parent DN** value.

For SMTP records, the SMTP address is split after ‘@’ and the local-part of the SMTP address including the ‘@’ is stored in the **acKey** field. The domain name part of the SMTP address is pointed to by the **oParentDN** offset.

## 2.5 Uncompressed OAB Version 2 ANR Index File

The following ABNF definition shows the format of an uncompressed OAB version 2 ANR Index file.

```
anr-file = OAB_HDR 1*ANR_REC
```

### 2.5.1 OAB\_HDR

The **OAB\_HDR** structure is used to determine the OAB file format version and the number of **Address Book** object records in the ANR Index file, and it contains a hash value for consistency checks.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulVersion																															
ulSerial																															
ulTotRecs																															


**ulVersion (4 bytes):** MUST be set to 0x0000000A for uncompressed OAB version 2 ANR Index files.

**ulSerial (4 bytes):** Unused, SHOULD be set to zero. Other values MUST be ignored.

**ulTotRecs (4 bytes):** The number of **ANR\_REC** records stored in the ANR Index file.

### 2.5.2 ANR\_REC

Each **ANR\_REC** structure corresponds to a node in the ANR index tree. The tree is constructed as a threaded tree so that searches are efficient, and traversing to the next and previous records is also efficient. The root of the tree MUST be the first **ANR\_REC** in the ANR Index file.



**oLT (4 bytes):** Offset of the left **ANR\_REC** child of the current node in the ANR Index file. The left child **MUST** sort to the same value as the current node or less. **MUST** be set to 0x00000000 to indicate that there is no left child node.

**oGT (4 bytes):** Offset of the right **ANR\_REC** child of the current node in the ANR Index file. The right child **MUST** sort to the same value as the current node or greater. **MUST** be set to 0x00000000 to indicate that there is no right child node.

**iBrowse (3 bytes):** Index to the B2\_REC in the Browse file that references this record. The values 0x000000 through 0x000002 are reserved and **MUST NOT** be used. The index value in the browse file is computed by using the following equation:  $iBrowse - 0x000003$ .

**a (1 bit):** **MUST** be set to 1 for e-mail alias records. **MUST** be set to 0 for display name, office location, and surname records.

**b (7 bits):** **MUST** be all zeros.

**oPrev (4 bytes):** Offset of the previous **ANR\_REC** record in the ANR Index file when sorted as a flat list. **MUST** be set to 0x00000000 when this is the first node in the list.

**oNext (4 bytes):** Offset of the next **ANR\_REC** record in the ANR Index file when sorted as a flat list. **MUST** be set to 0x00000000 when this is the last node in the list.

**acKey (Variable):** The null-terminated ANSI string value of the record. It **MUST** be 64 characters or fewer including the null terminator.

## 2.6 Uncompressed OAB Version 2 Details File

The following ABNF definition shows the format of an uncompressed OAB version 2 Details file.

```
v2-details-file = OAB_HDR 1*details-record

details-record = user-certificate business-telephone
                given-name initials street-address
                city-locality state-province postal-code
                country-region title company-name
                assistant-name
                department-name null home-telephone
                business2-telephone home2-telephone
                primary-fax mobile-telephone
                assistant-telephone pager-telephone
                comment proxy-addresses smime-certs
                x509-certs

user-certificate = binary-value

business-telephone = string-value

given-name = string-value

initials = string-value

street-address = string-value

city-locality = string-value

state-province = string-value

postal-code = string-value

country-region = string-value

title = string-value

company-name = string-value

assistant-name = string-value

department-name = string-value

home-telephone = string-value

business2-telephone = string-value

home2-telephone = string-value
```

```

primary-fax      = string-value
mobile-telephone = string-value
assistant-telephone = string-value
pager-telephone = string-value
comment         = string-value
proxy-addresses = multivalued-string
smime-certs    = multivalued-binary
x509-certs     = multivalued-binary
string-value   = *(ansi-char) null / null
ansi-char      = %x01-%xFF
                ; 8 bits of data
null           = %x00
                ; 8 bits of data
multivalued-string = count 0*255(string-value) / null
count          = %x00-%xFF
                ; 8 bits of data
binary-value   = byte-count 0*65535(OCTET) / null
byte-count     = %x0000-%xFFFF
                ; 16 bits of data
multivalued-binary = count 0*255(binary-value) / null

```

Each Details record MUST fit into 65535 bytes. If a value is not present, a null byte MUST be encoded. All strings MUST be null terminated. Multivalued-binary or multivalued-string encodings with one or more values MUST NOT have any zero length elements.

The details elements map directly to the following property tag table. For details about the following properties, see [MS-OXOABK].

Property tag name	Property tag	Property type	Description
-------------------	--------------	---------------	-------------

Property tag name	Property tag	Property type	Description
<b>PidTagUserCertificate</b>	0x3A220102	<b>PtypBinary</b>	The <b>user-certificate</b> property contains an ASN.1 authentication certificate for a messaging user. For more details, see [ISO/IEC 8825-1]. This property is deprecated and SHOULD be set to a null entry.
<b>PidTagBusinessTelephone Number</b>	0x3A08001E	<b>PtypString8</b>	The <b>business-telephone</b> property contains the primary telephone number of the place of business of the <b>Address Book</b> object.
<b>PidTagGivenName</b>	0x3A06001E	<b>PtypString8</b>	The <b>given-name</b> property contains the given name of the <b>Address Book</b> object.
<b>PidTagInitials</b>	0x3A0A001E	<b>PtypString8</b>	The <b>initials</b> property contains the initials for parts of the full name of the <b>Address Book</b> object.
<b>PidTagStreetAddress</b>	0x3A29001E	<b>PtypString8</b>	The <b>street-address</b> property contains the street address of the <b>Address Book</b> object.
<b>PidTagLocality</b>	0x3A27001E	<b>PtypString8</b>	The <b>city-locality</b> property contains the name of the locality of the <b>Address Book</b> object, such as the town or city.
<b>PidTagStateOrProvince</b>	0x3A28001E	<b>PtypString8</b>	The <b>state-province</b> property contains the name of the state or province where the <b>Address Book</b> object is located.

Property tag name	Property tag	Property type	Description
<b>PidTagPostalCode</b>	0x3A2A001E	<b>PtypString8</b>	The <b>postal-code</b> property contains the postal code of the <b>Address Book</b> object.
<b>PidTagCountry</b>	0x3A26001E	<b>PtypString8</b>	The <b>country-region</b> property contains the name of the country or region where the <b>Address Book</b> object is located.
<b>PidTagTitle</b>	0x3A17001E	<b>PtypString8</b>	The <b>title</b> property contains the job title of the <b>Address Book</b> object.
<b>PidTagCompanyName</b>	0x3A16001E	<b>PtypString8</b>	The <b>company-name</b> property contains the name of the company that employs the <b>Address Book</b> object.
<b>PidTagAssistant</b>	0x3A30001E	<b>PtypString8</b>	The <b>assistant-name</b> property contains the name of the administrative assistant for the <b>Address Book</b> object.
<b>PidTagDepartmentName</b>	0x3A18001E	<b>PtypString8</b>	The <b>department-name</b> property contains the department name in which the <b>Address Book</b> object works.
<i>null</i>	0x3A08001E	<b>PtypString8</b>	Exchange 2003 and Exchange 2007 duplicate the <b>PidTagBusinessTelephoneNumber</b> property in this field. It is not used by Outlook 2003 or Outlook 2007 and <b>MUST</b> be ignored by clients.

Property tag name	Property tag	Property type	Description
<b>PidTagHomeTelephoneNumber</b>	0x3A09001E	<b>PtypString8</b>	The <b>home-telephone</b> property contains the primary home telephone number for the <b>Address Book</b> object.
<b>PidTagBusiness2TelephoneNumber</b>	0x3A1B001E	<b>PtypString8</b>	The <b>business2-telephone</b> property contains a secondary business telephone for the <b>Address Book</b> object.
<b>PidTagHome2TelephoneNumber</b>	0x3A2F001E	<b>PtypString8</b>	The <b>home2-telephone</b> property contains a secondary home telephone number for the <b>Address Book</b> object.
<b>PidTagPrimaryFaxNumber</b>	0x3A23001E	<b>PtypString8</b>	The <b>primary-fax</b> property contains the telephone number for the fax machine of the <b>Address Book</b> object.
<b>PidTagMobileTelephoneNumber</b>	0x3A1C001E	<b>PtypString8</b>	The <b>mobile-telephone</b> property contains the mobile telephone number of the <b>Address Book</b> object.
<b>PidTagAssistantTelephoneNumber</b>	0x3A2E001E	<b>PtypString8</b>	The <b>assistant-telephone</b> property contains the telephone number for the administrative assistant of the <b>Address Book</b> object.
<b>PidTagPagerTelephoneNumber</b>	0x3A21001E	<b>PtypString8</b>	The <b>pager-telephone</b> property contains the pager telephone number of the <b>Address Book</b> object.



Property tag name	Property tag	Property type	Description
<b>PidTagComment</b>	0x3004001E	<b>PtypString8</b>	The <b>comment</b> property contains a description of the purpose or content of an object.
<b>PidTagAddressBookProxy Addresses</b>	0x800F101E	<b>PtypMultipleString8</b>	The <b>proxy-addresses</b> property contains a list of e-mail addresses that this <b>Address Book</b> object is known by.  Each value MUST begin with an e-mail address type followed by a colon character then followed by the address value.
<b>PidTagUserX509Certificate</b>	0x3A701102	<b>PtypMultipleBinary</b>	The <b>smime-certs</b> property contains SMIME certificates formatted as PKCS-7 encodings. For more details, see [RFC2315].
<b>PidTagAddressBookX509 Certificate</b>	0x8C6A1102	<b>PtypMultipleBinary</b>	The <b>x509-certs</b> property contains ASN.1 [ISO/IEC 8825-1] encoded X.509 certificates. For more details, see [RFC3280].

### 2.6.1 OAB\_HDR

The **OAB\_HDR** structure is used to determine the OAB file format version and the number of **Address Book** object records in the address list, and it contains a hash value for consistency checks.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulVersion																															
ulSerial																															
ulTotRecs																															

**ulVersion (4 bytes):** MUST be set to 0x00000007 for uncompressed version 2 Details files.

**ulSerial (4 bytes):** Unused, SHOULD be set to zero. Other values MUST be ignored.

**ulTotRecs (4 bytes):** Unused, SHOULD be set to zero. Other values MUST be ignored.

## 2.7 Uncompressed OAB Version 2 Changes File

The following ABNF definition shows the format of an uncompressed OAB version 2 Changes file.

```

changes-file      =  OAB_HDR 1*change-record

change-record     =  CHG_REC [display-name parent-dn-offset
rdn]
                    [domain-name-offset local-portion]
                    [alias] [location] [surname]
                    [byte-count 0*65535(OCTET)]
                    [display-type] [object-type]

display-name      =  string-value

parent-dn-offset  =  %x00000000-%xFFFFFFFF
                    ; little endian 32 bit value
                    ; offset of the pdn-record in the
                    ; rdn index file

domain-name-offset = %x00000000-%xFFFFFFFF
                    ; little endian 32 bit value
                    ; offset of the domain name record in the
                    ; rdn index file

local-portion     =  1*62(ansi-char) '@' null

alias             =  1*63(ansi-char) null

location         =  0*63(ansi-char) null

surname          =  0*63(ansi-char) null

```

```

display-type      =  DT-MAILUSER / DT-DISTLIST /
                    DT-FORUM / DT-AGENT / DT-ORGANIZATION /
                    DT-REMOTE-MAILUSER
                    ; 8 bit value

DT-MAILUSER      =  %x00
                    ; mailbox display type

DT-DISTLIST      =  %x01
                    ; distribution list display type

DT-FORUM         =  %x02
                    ; public folder display type

DT-AGENT         =  %x03
                    ; mail agent display type

DT-ORGANIZATION  =  %x04
                    ; department or organization display type

DT-REMOTE-MAILUSER = %x06
                    ; external e-mail address display type

object-type      =  MAPI-FOLDER / MAPI-MAILUSER /
                    MAPI-DISTLIST
                    ; 8 bit value - high order bit is set to
                    ; 1 if the entry can receive all
                    ; message content, including Rich Text
                    ; Format (RTF) and OLE objects
                    ; For details, see section 2.786
                    ; in [MS-OXPROPS]

MAPI-FOLDER      =  %x03

MAPI-MAILUSER    =  %x06

MAPI-DISTLIST    =  %x08

```

### 2.7.1 OAB\_HDR

The **OAB\_HDR** structure is used to determine the OAB file format version and the number of **Address Book** object records in the address list, and it contains a hash value for consistency checks.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulVersion																															
ulSerial																															
ulTotRecs																															


**ulVersion (4 bytes):** MUST be set to 0x0000000B for uncompressed version 2 Changes files.

**ulSerial (4 bytes):** MUST be set to the **ulSerial** value of the version 2 OAB Browse file that these changes are to be applied against. The client MUST NOT apply a Changes file to a set of OAB files if the serial number does not match.

**ulTotRecs (4 bytes):** The count of the **change-record** structures in the Changes file.

## 2.7.2 CHG\_REC

The **CHG\_REC** structure is used to tell the client which record to update and what attributes are included in the change record.



**iBrowse (4 bytes):** The index of the record to be changed. The values 0x00000000 through 0x00000002 are reserved and MUST not be used. The index value in the browse file is computed by using the following equation:  $iBrowse - 0x00000003$ .

If the change type is an addition, the **iBrowse** points to the record in the old file that the new record MUST be inserted before. For example, if the record is to be inserted at the beginning of the file, the **iBrowse** value will be 0x00000003. If the record is to be appended at the end of the file, the **iBrowse** will be one plus the maximum **iBrowse** index in the old file. If the change type is a modification, the **iBrowse** points at the record in the old file that MUST be modified. If the change type is a deletion, the **iBrowse** points at the record in the old file that MUST be removed.

**l (5 bits):** MUST be 00000. Other values MUST be ignored.

**type (3 bits):** MUST be 000, 001, or 010. A value of 000 indicates a modification record, a value of 001 indicates a record addition, and a value of 010 indicates a record deletion. A value of 010 means that fields **a** through **j** MUST be 0 and that **display-name**, **parent-dn-offset**, and **rdn** MUST be present in the change record. A value of 001 means that fields **a** through **j** MUST be 1. A value of 000 means that fields **a** through **i** are set according to the presence of the data fields in the change record.

**k (8 bits):** MUST be 0.

**j (7 bits):** MUST be all 0 for a modification or deletion record. MUST be all 1s for an addition record.

**a (1 bit):** 1 indicates that the **object-type** field MUST be present in the change-record. 0 indicates that it MUST NOT be present.

**b (1 bit):** 1 indicates that the **local-portion** field MUST be present in the change-record. The value of this field MUST be the same as field **c**.

**c (1 bit):** 1 indicates that the **domain-name-offset** field MUST be present in the change-record. 0 indicates that it MUST NOT be present.

**d (1 bit):** 1 indicates that the **alias** field MUST be present in the change-record. 0 indicates that it MUST NOT be present.

**e (1 bit):** 1 indicates that the **location** field MUST be present in the change-record. 0 indicates that it MUST NOT be present.

**f (1 bit):** 1 indicates that the **surname** field MUST be present in the change-record. 0 indicates that it MUST NOT be present.

**g (1 bit):** 1 indicates that the **details** field MUST be present in the change-record. 0 indicates that it MUST NOT be present.

**h (1 bit):** 1 indicates that the **details** field MUST be present in the change-record and that it is larger than the old details record in the old Details file. 0 indicates that the size of the `details` field is equal to or smaller than the old record in the Details file. If field **g** is 0 then field **h** MUST be set to 0.

**i (1 bit):** 1 indicates that the **display-type** field MUST be present in the change-record. 0 indicates that it MUST NOT be present.

## 2.8 Compressed OAB Version 2 File

A compressed OAB version 2 file is structured as the following ABNF definition illustrates.

```
v2-compressed-file = MDI_HDR 1*MDI_BLK
```

### 2.8.1 MDI\_HDR

The **MDI\_HDR** structure contains versioning information to indicate that it is an OAB version 2 compressed file. It contains the target file size value that SHOULD be used by the client to check that the final result is correct.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulVersionHi																															
ulVersionLo																															
ulBlockMax																															
ulTargetSize																															

**ulVersionHi (4 bytes):** An integer value that MUST be 0x00000002.

**ulVersionLo (4 bytes):** An integer value that MUST be 0x00000001.

**ulBlockMax (4 bytes):** An integer value that indicates in bytes the largest size of a block that will be read from the source compressed input file or written to the target output file. This field is here so that the client can pre-allocate required buffers. MUST be 0x00008000.

**ulTargetSize (4 bytes):** An integer value that specifies the expected length of the resulting output target file. This value SHOULD be used by the client to ensure that the target output file was generated correctly.

## 2.8.2 MDI\_BLK

The **MDI\_BLK** structure is used to split the decompression process into more easily handled smaller sized blocks.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulFlags																															
ulCompSize																															
ulUncompSize																															
Data (variable)																															
...																															
...																															

**ulFlags (4 bytes):** An integer value that indicates whether the data field is compressed. MUST be either 0x00000000 to indicate the data field is not compressed and can be written out directly to the target file, or 0x00000001 to indicate the data field is compressed and ought to be decompressed using MCI decompression first.

**ulCompSize (4 bytes):** An integer value that specifies the size of the data field in bytes.

**ulUncompSize (4 bytes):** An integer value that specifies the size in bytes of the output target block to be written to the output file.

**data (variable):** Either a raw data stream or a compressed byte stream depending on the value of the **ulFlags** field. For more details, see [MS-MCI].

## 2.9 Uncompressed OAB Version 4 Full Details File

The following ABNF definition shows the format of an uncompressed OAB version 4 Details file.

```

v4-details-file      =  OAB_HDR OAB_META_DATA
                        header-record
                        1*address-book-object-record

header-record        =  OAB_V4_REC

address-book-object-record =  OAB_V4_REC
  
```

### 2.9.1 OAB\_HDR

The **OAB\_HDR** structure is used to determine the OAB file format version and the number of **Address Book** object records in the address list, and it contains a hash value for consistency checks.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulVersion																															
ulSerial																															
ulTotRecs																															

**ulVersion (4 bytes):** Set to 0x00000020 for uncompressed version 4 OAB Full Details files. Set to 0x00000007 for uncompressed Details Template files.

**ulSerial (4 bytes):** The CRC-32 hash of the rest of the file not including this header structure. All CRC checksums are calculated with an initial seed of 0xFFFFFFFF and use the IEEE 802.3 [ISO/IEC 8802-3] CRC polynomial of 0xEDB88320.

**ulTotRecs (4 bytes):** The number of **address-book-object-records** stored in the file.

### 2.9.2 OAB\_META\_DATA

The **OAB\_META\_DATA** structure contains information about the schema of all properties that can be represented in an OAB header or **Address Book** object record.

0	1	2	3	4	5	6	7	8	9	1	0	1	2	3	4	5	6	7	8	9	2	0	1	2	3	4	5	6	7	8	9	3	0	1
cbSize																																		
rgHdrAtts (variable)																																		
...																																		
rgOabAtts (variable)																																		
...																																		

**cbSize (4 bytes):** The length of the **OAB\_META\_DATA** structure in bytes. This count includes both the **cbSize** field and the combined length of the **rgHdrAtts** and **rgOabAtts** fields.

**rgHdrAtts (Variable):** An **OAB\_PROP\_TABLE** structure that describes the properties that can be present in the **header-record**. MUST contain 0 or more header property records.<2>

**rgOabAtts (Variable):** An **OAB\_PROP\_TABLE** structure that describes the properties that can be present in any **address-book-object-record**. MUST contain 0 or more **Address Book** object property records.<3>

### 2.9.3 OAB\_PROP\_TABLE

The **OAB\_PROP\_TABLE** structure represents the property schema of either the OAB header record or all the **Address Book** object records. It contains a list of **OAB\_PROP\_REC** structures.

0	1	2	3	4	5	6	7	8	9	1	0	1	2	3	4	5	6	7	8	9	2	0	1	2	3	4	5	6	7	8	9	3	0	1
cAtts																																		
rgProps (variable)																																		
...																																		


**cAtts (4 bytes):** An integer that specifies the number of **OAB\_PROP\_REC** records in **rgProps**.

**rgProps (Variable):** A list of 0 or more **OAB\_PROP\_REC** structures.

### 2.9.4 OAB\_PROP\_REC

The **OAB\_PROP\_REC** structure defines a property that can be stored in an OAB header or **Address Book** object record and describes how the attribute is used online.





**ulPropId (4 bytes):** A property tag. The property type portion of the property tag MUST be one of the following values. For more details about the data types provided in the table, see [MS-OXCADATA] section 2.13.1.

Value	Meaning
0x0003	<b>PtypInteger32</b>
0x000B	<b>PtypBoolean</b>
0x001E	<b>PtypString8</b>
0x001F	<b>PtypString</b>
0x0102	<b>PtypBinary</b>
0x1003	<b>PtypMultipleInteger32</b>
0x101E	<b>PtypMultipleString8</b>
0x101F	<b>PtypMultipleString</b>
0x1102	<b>PtypMultipleBinary</b>

**a (1 bit):** 1 indicates that the property is part of the ANR property set online. 0 indicates that it is not part of the ANR property set online.


**b (1 bit):** 1 indicates that the property is a primary key index when used online and a value MUST be present on **every address-book-object-record** in the OAB version 4 Full Details file.

**c (1 bit):** 1 indicates that the property is indexed separately online. The client MAY choose to index the property locally.

**d (29 bits):** All bits of **d** MUST be 0 and ignored on receipt.

## 2.9.5 OAB\_V4\_REC

The **OAB\_V4\_REC** structure represents either the OAB header record or an individual **Address Book** object record in an OAB file.



**cbSize (4 bytes):** The length of the **OAB\_V4\_REC** structure in bytes. This count includes both the **cbSize** field and the combined length of the **presenceBitArray** and **data** fields.

**presenceBitArray (variable):** A bit array that indicates whether a property specified in the **OAB\_PROP\_TABLE** structure is present in the data field. The first element of the bit array is the most significant bit of the first byte. The size of the **presenceBitArray** field in bytes **MUST** be the value of the **cAtts** field of the appropriate **OAB\_PROP\_TABLE** structure divided by 8 and rounded up to the nearest integer value. A 0 record in the **presenceBitArray** indicates that the property is not present in the data field. 1 indicates the property is present. The index of the property in the **OAB\_PROP\_TABLE** structure **MUST** match the index of the value in the **presenceBitArray**. Unused bits in the final byte **MUST** be set to 0.

**data (variable):** The set of property values for the **address-book-object-record** or **header-record**. The format of the **data** field is specified in section 2.9.6.

## 2.9.6 Data Encoding

Property values are encoded in the data field based on the property type and are packed on byte boundaries. The properties are laid out in the order that the property definition exists in the **OAB\_PROP\_TABLE** structure. If a property does not exist, the **presenceBitArray** value **MUST** be 0 and no value is encoded in the data field.

### 2.9.6.1 PtyInteger32 (0x0003) Value Encoding

All integer values are considered unsigned and **MUST** fit in the range of a 32 bit integer ( $0 - 2^{32}-1$ ). Integers equal to or less than 127 **MUST** be encoded as a single byte. Integers 128 or greater are encoded with first a byte count byte with the most significant bit set, then the little-endian value encoding. The byte count, if required, **MUST** be 0x81, 0x82, 0x83, or 0x84 representing 1, 2, 3, or 4 bytes. The most significant byte of the value representation **MUST NOT** be 0x00, a lower byte count **MUST** be used. For example,

0x0000007F MUST be encoded as 0x7F and MUST NOT be encoded as 0x81 0x7F, 0x82 0x7F 0x00, 0x83 0x7F 0x00 0x00, or 0x84 0x7F 0x00 0x00 0x00.

For more details about the **PtypInteger32** data type and the data types specified in the following encoding sections, see [MS-OXCDATA] section 2.13.1.

### 2.9.6.2 PtypBoolean (0x000B) Value Encoding

All Boolean values are encoded as a single byte. TRUE MUST be encoded as 0x01 and FALSE MUST be encoded as 0x00.

### 2.9.6.3 PtypString8 (0x001E) Value Encoding

All narrow or multi-byte character set strings are encoded as byte sequences and MUST be terminated by a single 0x00 byte. A string sequence MUST NOT contain a 0x00 byte as part of the string itself. A zero length or empty string MUST NOT be encoded, but MUST be marked as not present in the **presenceBitArray**.

### 2.9.6.4 PtypString (0x001F) Value Encoding

All Unicode strings are encoded as UTF-8 byte sequences and MUST be terminated by a single 0x00 byte. A string encoding MUST NOT contain a 0x00 byte as part of the string itself. A zero length or empty string MUST NOT be encoded, but MUST be marked as not present in the **presenceBitArray**.

### 2.9.6.5 PtypBinary (0x0102) Value Encoding

All raw byte sequences are encoded by a length value followed by the specified number of bytes. The length value is encoded as a **PtypInteger32** as shown in section 2.9.6.1. For example, the byte sequence 0x22 0xF8 0xFF 0x00 0x22 would be encoded as 0x05 0x22 0xF8 0xFF 0x00 0x22. A zero length **PtypBinary** value MUST NOT be encoded, but MUST be marked as not present in the **presenceBitArray**.

### 2.9.6.6 PtypMultipleInteger32 (0x1003) Value Encoding

Multi-valued integer encodings start with an integer count encoding followed by the specified number of integer value encodings. All integer encodings, including the value count, are encoded in the same way that **PtypInteger32** is encoded. All values MUST be unique. Values MAY appear in any order.

### 2.9.6.7 PtypMultipleString8 (0x101E) Value Encoding

Multi-valued string encodings start with an integer count encoding followed by the specified number of string value encodings. The count encoding is encoded in the same way that **PtypInteger32** is encoded. The individual string encodings are encoded in the same way that **PtypString8** is encoded. Strings MUST be case-insensitive. All values MUST be unique. Values MAY appear in any order. All strings MUST NOT be zero length or empty.

### 2.9.6.8 PtypMultipleString (0x101F) Value Encoding

Multi-valued Unicode string encodings start with an integer count encoding followed by the specified number of Unicode string value encodings. The count encoding is encoded in the same way that **PtypInteger32** is encoded. The individual string encodings are encoded in the same way that **PtypString** is encoded. Strings **MUST** be case-insensitive. All values **MUST** be unique. Values **MAY** appear in any order. All strings **MUST NOT** be zero length or empty.

### 2.9.6.9 PtypMultipleBinary (0x1102) Value Encoding

Multi-valued binary octet encodings start with an integer count encoding, followed by the specified number of binary value encodings. The count encoding is encoded in the same way that **PtypInteger32** is encoded. The individual binary encodings are encoded in the same way that **PtypBinary** is encoded. All values **MUST** be unique. Values **MAY** appear in any order. Any binary value **MUST NOT** be zero length.

## 2.10 Compressed OAB Version 4 Differential Patch File

The following ABNF definition shows the format of a compressed OAB version 4 Differential Patch file.

```
patch-file = PATCH_HDR 1*PATCH_BLK
```

Patch files are only applied against OAB version 4 Full Details files to produce the next generation of the file.

### 2.10.1 PATCH\_HDR

The **PATCH\_HDR** structure contains versioning information to indicate that it is an OAB version 4 patch file. It contains source and target file hash and file size values that **SHOULD** be used by the client to check that the patch is being applied against the correct file and that the final result is correct.

0	1	2	3	4	5	6	7	8	9	1	2	3	4	5	6	7	8	9	2	0	1	2	3	4	5	6	7	8	9	3	0	1
ulVersionHi																																
ulVersionLo																																
ulBlockMax																																
ulSourceSize																																
ulTargetSize																																
ulSourceCRC																																
ulTargetCRC																																

**ulVersionHi (4 bytes):** An integer value that **MUST** be 0x00000003.

**ulVersionLo (4 bytes):** An integer value that **MUST** be 0x00000002.

**ulBlockMax (4 bytes):** An integer value that indicates in bytes the largest size of a block that will be read from the source OAB Details input file, written to the target OAB details output file, or read from the Differential Patch file. This field is here so that the client can pre-allocate required buffers.

**ulSourceSize (4 bytes):** An integer value that specifies the length in bytes that the source input file is expected to be. This value SHOULD be used by the client to make sure that the correct input file is being read.


**ulTargetSize (4 bytes):** An integer value that specifies the length that the resulting output target file is expected to be. This value SHOULD be used by the client to ensure that the target output file was generated correctly.

**ulSourceCRC (4 bytes):** An integer value that represents the CRC-32 hash of the source input file (excluding the **OAB\_HDR** structure). This value SHOULD be used by the client to make sure that the correct input source file is being read.

**ulVersionLo (4 bytes):** An integer value that represents the CRC-32 hash of the target output file (excluding the **OAB\_HDR** structure). This value SHOULD be used by the client to ensure that output target file was generated correctly.

### 2.10.2 PATCH\_BLK

The **PATCH\_BLK** structure is used to split the patch process into more easily handled smaller-sized blocks.



**ulPatchSize (4 bytes):** An integer value that specifies the size of the data field in bytes.

**ulTargetSize (4 bytes):** An integer value that specifies the size in bytes of the output target block to be written to the output file.

**ulSourceSize (4 bytes):** An integer value that specifies the size in bytes of the source input block to be read from the source input file and used to generate the output block.

**ulCRC (4 bytes):** An integer value that specifies the CRC-32 hash of the resulting target block. This value SHOULD be used by the client to make sure that the correct output block has been generated.

**data (variable):** A byte stream of **LZXD** compressed differences to apply to the source block that results in the target block. For more details, see [MS-PATCH].

## 2.11 Compressed OAB Version 4 file

The following ABNF definition shows the format of a compressed OAB version 4 file.

```
v4-compressed-file = LZX_HDR 1*LZX_BLK
```

### 2.11.1 LZX\_HDR

The **LZX\_HDR** structure contains versioning information to indicate that it is an OAB version 4 compressed file. It contains the target file size value that SHOULD be used by the client to check that the final result is correct.

0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
ulVersionHi																															
ulVersionLo																															
ulBlockMax																															
ulTargetSize																															

**ulVersionHi (4 bytes):** An integer value that MUST be 0x00000003.


**ulVersionLo (4 bytes):** An integer value that MUST be 0x00000001.

**ulBlockMax (4 bytes):** An integer value that indicates in bytes the maximum block size that will be read from the source compressed input file or written to the target output file. This field is provided so that the client can pre-allocate required buffers.

**ulTargetSize (4 bytes):** An integer value that specifies the expected length of the resulting output target file. This value SHOULD be used by the client to ensure that the target output file was generated correctly.

## 2.11.2 LZX\_BLK

The **LZX\_BLK** structure is used to split the decompression process into more easily handled smaller-sized blocks.



**ulFlags (4 bytes):** An integer value that indicates whether the data field is compressed. MUST be either 0x00000000 to indicate that the data field is not compressed and can be written out directly to the target file, or 0x00000001 to indicate the that data field is compressed and ought to be decompressed using **LZX** decompression first.

**ulCompSize (4 bytes):** An integer value that specifies the size of the data field in bytes.

**ulUncompSize (4 bytes):** An integer value that specifies the size in bytes of the output target block to be written to the output file.

**ulCRC (4 bytes):** An integer value that specifies the CRC-32 hash of the resulting target block. This value SHOULD be used by the client to ensure that the correct output block has been generated.

**data (variable):** Either a raw data stream or a compressed byte stream, depending on the value of the **ulFlags** field. For more details, see [MS-PATCH].

## 3 Structure Examples

The examples in this section illustrate the data after it is downloaded to the client and decompressed when they have an OAB installed. The client can use the data in these files to retrieve user information when working offline. The structure of the data in each file is specified in section 2.

### 3.1 Full OAB Version 2 Offline Address List

The following data show the contents of a sample OAB version 2 Browse file. All data in this section is shown in actual byte order.

```
OAB_HDR
  ulVersion  0a 00 00 00
  ulSerial   bd 32 79 d3
  ulTotRecs  02 00 00 00
```

```
B2_REC
  oRDN       d2 00 00 00
  oDetails   0c 00 00 00
  cbDetails  39 00
  bDispType  00
  bObjType   06
  oSmtP      8c 00 00 00
  oDispName  69 00 00 00
  oAlias      2c 00 00 00
  oLocation  00 00 00 00
  oSurname   00 00 00 00
```

```
B2_REC
  oRDN       68 00 00 00
  oDetails   45 00 00 00
  cbDetails  35 00
  bDispType  00
  bObjType   06
  oSmtP      b3 00 00 00
  oDispName  0c 00 00 00
  oAlias      8b 00 00 00
  oLocation  00 00 00 00
  oSurname   4e 00 00 00
```

The following data show the contents of a sample OAB version 2 ANR Index file.

```
OAB_HDR
  ulVersion  0a 00 00 00
  ulSerial   00 00 00 00
  ulTotRecs  05 00 00 00
```

```
ANR_REC (offset 0x0000000C)
  oLT        2c 00 00 00
  oGT        4e 00 00 00
  iBrowse    04 00 00 00
  oPrev      69 00 00 00
  oNext      8b 00 00 00
  acKey      4c 69 73 61 20 4d 69 6c 6c 65 72 00
              ; 'Lisa Miller'
```

```
ANR_REC (offset 0x0000002C)
  oLT        00 00 00 00 ; 0 = no left child
  oGT        69 00 00 00
```



```

iBrowse      03 00 00 80 ; high order bit = alias field
oPrev        00 00 00 00 ; 0 = left-most record
oNext        69 00 00 00
acKey        41 64 6d 69 6e 69 73 74 72 61 74 6f 72 00
              ; 'Administrator'

ANR_REC (offset 0x0000004E)
oLT          8b 00 00 00
oGT          00 00 00 00 ; 0 = no right child
iBrowse      04 00 00 00
oPrev        8b 00 00 00
oNext        00 00 00 00 ; 0 = right most record
acKey        4d 69 6c 6c 65 72 00
              ; 'Miller'

ANR_REC (offset 0x00000069)
oLT          00 00 00 00 ; 0 = no left child
oGT          00 00 00 00 ; 0 = no right child
iBrowse      03 00 00 00
oPrev        2c 00 00 00
oNext        0c 00 00 00
acKey        41 64 6d 69 6e 69 73 74 72 61 74 6f 72 00
              ; 'Administrator'

ANR_REC (offset 0x0000008B)
oLT          00 00 00 00 ; 0 = no left child
oGT          00 00 00 00 ; 0 = no right child
iBrowse      04 00 00 80 ; high order bit = alias field
oPrev        0c 00 00 00
oNext        4e 00 00 00
acKey        4c 69 73 61 4d 69 6c 6c 65 72 00
              ; 'LisaMiller'

```

The following code shows the contents of a sample OAB version 2 RDN Index file.

```

OAB_HDR
ulVersion    0a00 00 00
ulSerial     00 00 00 00
ulTotRecs    04 00 00 00
oRoot        68 00 00 00

pdn-record (offset 0x00000010) '/o=example/ou=Exchange
Administrative Group (FYDIBOHF23SPDLT)/cn=Recipients'
2f 6f 3d 65 78 61 6d 70 6c 65 2f 6f 75 3d 45 78
63 68 61 6e 67 65 20 41 64 6d 69 6e 69 73 74 72
61 74 69 76 65 20 47 72 6f 75 70 20 28 46 59 44
49 42 4f 48 46 32 33 53 50 44 4c 54 29 2f 63 6e
3d 52 65 63 69 70 69 65 6e 74 73 00

```

```
pdn-record (offset 0x0000005C) 'example.com'
        65 78 61 6d 70 6c 65 2e 63 6f 6d 00
```

```
RDN2_REC (offset 0x00000068)
    oLT      8c 00 00 00
    oGT      b3 00 00 00
    iBrowse  04 00 00 00
    oPrev    8c 00 00 00
    oNext    b3 00 00 00
    oParentDN 10 00 00 00
    acKey    4c 69 73 61 20 4d 69 6c 6c 65 72 00
            ; 'Lisa Miller'
```

```
RDN2_REC (offset 0x0000008C)
    oLT      d2 00 00 00
    oGT      00 00 00 00
    iBrowse  03 00 00 00
    oPrev    d2 00 00 00
    oNext    68 00 00 00
    oParentDN 5c 00 00 00
    acKey    41 64 6d 69 6e 69 73 74 72 61 74 6f 72 40 00
            ; 'Administrator@'
```

```
RDN2_REC (offset 0x000000B3)
    oLT      00 00 00 00
    oGT      00 00 00 00
    iBrowse  04 00 00 00
    oPrev    68 00 00 00
    oNext    00 00 00 00
    oParentDN 5c 00 00 00
    acKey    4c 69 73 61 4d 40 00
            ; 'LisaM@'
```

```
RDN2_REC (offset 0x000000d2)
    oLT      00 00 00 00
    oGT      00 00 00 00
    iBrowse  03 00 00 00
    oPrev    00 00 00 00
    oNext    8c 00 00 00
    oParentDN 10 00 00 00
    acKey    41 64 6d 69 6e 69 73 74 72 61 74 6f 72 00
            ; 'Administrator'
```

The following data show the contents of a sample OAB version 2 Details file.

```
OAB_HDR
    ulVersion 07 00 00 00
    ulSerial  00 00 00 00
    ulTotRecs 00 00 00 00
```

```

Details-Record (offset 0x0000000C)
    ; empty values for first 22 properties
    00 00 ; empty binary property
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
    00 00 00 00 00 00 00 ; empty ANSI properties
    01 ; 1 value for multivalued PidTagAddressBookProxyAddresses
    53 4d 54 50 3a 41 64 6d 69 6e 69 73 74 72 61 74
    6f 72 40 65 78 61 6d 70 6c 65 2e 63
    6f 6d 00
    ; 'SMTP:Administrator@example.com'
    00 ; empty multivalued binary property
    00 ; empty multivalued binary property

```

```

Details-Record (offset 0x00000045)
    00 00; empty binary property
    00 00 00 ; empty ANSI properties
    4c 69 73 61 00 ; 'Lisa' PidTagGivenName
    00 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
    00 00 00 ; empty ANSI properties
    01 ; 1 value for multivalued PidTagAddressBookProxyAddresses
    01 53 4d 54 50 3a 4c 69 73 61 4d 40 65 78 61 6d
    70 6c 65 2e 63 6f 6d 00
    ; 'SMTP:LisaM@example.com'
    00 ; empty multivalued binary property
    00 ; empty multivalued binary property

```

### 3.2 Full OAB Version 4 Details File

The following code shows the contents of a sample OAB version 4 Details file. All data in this section are shown in actual byte order.

```

OAB_HDR
    ulVersion      20 00 00 00
    ulSerial       f7 da c0 7f
    ulTotRecs     02 00 00 00

OAB_META_DATA
    cbSize        5c 00 00 00
    pHdrAtts
        cAtts     04 00 00 00
        rgProps [0]
            ulPropID 1f 00 00 68
            ulFlags  00 00 00 00 ; combination of fields a,b,c,d
        rgProps [1]
            ulPropID 1e 00 04 68
            ulFlags  00 00 00 00
        rgProps [2]
            ulPropID 03 00 01 68
            ulFlags  00 00 00 00

```

```

    rgProps [3]
      ulPropID 1e 00 02 68
      ulFlags 00 00 00 00
  pOabAtts
    cAtts 06 00 00 00
    rgProps [0]
      ulPropID 1e 00 03 30
      ulFlags 02 00 00 00 ; combination of fields a,b,c,d
    rgProps [1]
      ulPropID 1f 00 fe 39
      ulFlags 02 00 00 00
    rgProps [2]
      ulPropID 1f 00 01 30
      ulFlags 01 00 00 00
    rgProps [3]
      ulPropID 03 00 fe 0f
      ulFlags 00 00 00 00
    rgProps [4]
      ulPropID 03 00 00 39
      ulFlags 00 00 00 00
    rgProps [5]
      ulPropID 03 10 05 68
      ulFlags 00 00 00 00

```

OAB\_V4\_REC (Header Properties)

```

  cbSize 42 00 00 00
  PresenceArray f0
  Att [0] (Utf8) 5c 47 6c 6f 62 61 6c 20
                  41 64 64 72 65 73 73 20
                  4c 69 73 74 00
  Att [1] (String) 2f 00
  Att [2] (Integer) 06
  Att [3] (String) 64 34 66 32 34 34 61 38
                  2d 61 38 65 63 2d 34 34
                  32 61 2d 38 37 61 33 2d
                  35 32 33 36 66 38 32 63
                  61 62 64 63 00

```

OAB\_V4\_REC (Address book object 0)

```

  cbSize 80 00 00 00
  PresenceArray f8
  Att [0] (string) 2f 6f 3d 65 78 61 6d 70
                  6c 65 2f 6f 75 3d 45 78
                  63 68 61 6e 67 65 20 41
                  64 6d 69 6e 69 73 74 72
                  61 74 69 76 65 20 47 72
                  6f 75 70 20 28 46 59 44
                  49 42 4f 48 46 32 33 53
                  50 44 4c 54 29 2f 63 6e
                  3d 52 65 63 69 70 69 65
                  6e 74 73 2f 63 6e 3d 4c

```

```

        69 73 61 20 4d 69 6c 6c
        65 72 00
Att [1] (Utf8) 4c 69 73 61 4d 40 65 78
        61 6d 70 6c 65 2e 63 6f
        6d 00
Att [2] (Utf8) 4c 69 73 61 20 4d 69 6c
        6c 65 72 00
Att [3] (Integer) 06
Att [4] (Integer) 00

```

```

OAB_V4_REC (Address book object 1)
  cbSize      8c 00 00 00
  PresenceArray  f8
Att [0] (string) 2f 6f 3d 65 78 61 6d 70
        6c 65 2f 6f 75 3d 45 78
        63 68 61 6e 67 65 20 41
        64 6d 69 6e 69 73 74 72
        61 74 69 76 65 20 47 72
        6f 75 70 20 28 46 59 44
        49 42 4f 48 46 32 33 53
        50 44 4c 54 29 2f 63 6e
        3d 52 65 63 69 70 69 65
        6e 74 73 2f 63 6e 3d 41
        64 6d 69 6e 69 73 74 72
        61 74 6f 72 00
Att [1] (Utf8) 41 64 6d 69 6e 69 73 74
        72 61 74 6f 72 40 65 78
        61 6d 70 6c 65 2e 63 6f
        6d 00
Att [2] (Utf8) 41 64 6d 69 6e 69 73 74
        72 61 74 6f 72 00
Att [3] (Integer) 06
Att [4] (Integer) 00

```

Flat OAB header version 32, serial 7FC0DAF7, records 2

```

-----
Header Attributes
Property  Flags
cAtts = 4
0x6800001F: 0      PidTagOfflineAddressBookName
0x6804001E: 0      PidTagOfflineAddressBookDistinguishedName
0x68010003: 0      PidTagOfflineAddressBookSequence
0x6802001E: 0      PidTagOfflineAddressBookContainerGuid
-----

```

```

OAB Attributes
Property  Flags
cAtts = 6
0x3003001E: 2      PidTagEmailAddress
0x39FE001F: 2      PidTagSmtppAddress

```

```
0x3001001F: 1      PidTagDisplayName
0x0FFE0003: 0      PidTagObjectType
0x39000003: 0      PidTagDisplayType
0x68051003: 0      PidTagOfflineAddressBookTruncatedProperties
-----
```

OAB Meta Data

```
0x6800001F: \Global Address List
0x6804001E: /
0x68010003: 6
0x6802001E: d4f244a8-a8ec-442a-87a3-5236f82cabdc
-----
```

-----  
Record 0  
-----

```
0x3003001E: /o=example/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=Lisa Miller
0x39FE001F: LisaM@example.com
0x3001001F: Lisa Miller
0x0FFE0003: 6
0x39000003: 0
-----
```

Record 1  
-----

```
0x3003001E: /o=example/ou=Exchange Administrative Group
(FYDIBOHF23SPDLT)/cn=Recipients/cn=Administrator
0x39FE001F: Administrator@example.com
0x3001001F: Administrator
0x0FFE0003: 6
0x39000003: 0
-----
```

## 4 Security Considerations

Data stored in OAB files contain personally identifiable information. Implementers have to ensure that only authorized individuals have access to the data.

## 5 Appendix A: Office/Exchange Behavior

The information in this specification is applicable to the following versions of Office/Exchange:

- Office 2003 with Service Pack 3 applied
- Exchange 2003 with Service Pack 2 applied
- Office 2007 with Service Pack 1 applied
- Exchange 2007 with Service Pack 1 applied

Exceptions, if any, are noted below. Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies Office/Exchange behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies Office/Exchange does not follow the prescription.

<1> Section 1.3.2.6: For string and Unicode attributes, Exchange 2003 SP2 and Exchange 2007 SP1 truncate strings to a size limit. For binary properties, Exchange 2003 SP2 and Exchange 2007 SP1 will drop the entire property if it exceeds the size limit. For multi-valued properties, Exchange 2003 SP2 and Exchange 2007 SP1 will drop individual values for both string and binary properties if the combined size of all the values exceeds a size limit.

The following table defines the default minimum and maximum values of limit settings for **String** and **Binary** data types for files generated by Exchange 2003 SP2 and Exchange 2007 SP1. The minimum limit value is the smallest value that a limit can be set to, not the smallest size an actual value can be. The maximum limit value is the largest value that a size limit can be set to, and does reflect the largest size a property can be.

Data type	Type	Minimum limit value (in bytes)	Maximum limit value (in bytes)
String limit	DWORD	32	3400
Binary limit	DWORD	1024	32768
String multivalued limit	DWORD	512	65536
Binary multivalued limit	DWORD	2048	65536

<2> Section 2.9.2: The rgHdrAtts table MUST have at least the four following attributes for compatibility with Outlook 2007 SP1:

Index Number	Property tag name	Property Tag	Property type	Description
1	<b>PidTagOabName</b>	0x6800001F	<b>PtypString</b>	Display name of the address list. MAY change between generation versions of the same address list.

2	<b>PidTagOabDn</b>	0x6804001E	<b>PtypString8</b>	The <i>addresslist-X500-dn</i> of the address list container object. MAY change between generation versions of the same address list.
3	<b>PidTagOabSequence</b>	0x68010003	<b>PtypInteger32</b>	The sequence number of the OAB. MUST increase by one between generation versions of the same address list.
4	<b>PidTagOabContainerGuid</b>	0x6802001E	<b>PtypString8</b>	A string formatted GUID that represents the address list container object. This value MUST never change between generation versions of the same address list. This value MUST be formatted as "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx"



<3> Section 2.9.2: The **rgOabAtts** table MUST have at least the five following attributes for compatibility with Outlook 2007 SP1 and MUST be present on all address book object records:

1. **PidTagEmailAddress** – this MUST be the first entry.
2. **PidTagSmtpAddress** – this MUST be the second entry.
3. **PidTagDisplayName**
4. **PidTagDisplayType**
5. **PidTagObjectType**

The following table describes the default attributes populated on address book object records by Exchange 2007 SP1 in the OAB version 4 Full Details file.

**Properties populated in the OAB Version 4 Data file by Exchange 2007 SP1**

Index Number	Property tag name	Property Tag	Property type	Description
1	<b>PidTagEmailAddress</b>	0x3003001E	<b>PtypString8</b>	Contains the X500 DN.
2	<b>PidTagSmtpAddress</b>	0x39fe001f	<b>PtypString</b>	Contains the SMTP mailing address of the sender.
3	<b>PidTagDisplayName</b>	0x3001001F	<b>PtypString</b>	Contains the display name for a given Address Book object.
4	<b>PidTagEmsAbPhoeneticDisplayname</b>	0x8C92001F	<b>PtypString</b>	Contains the phonetic display name of an object.
5	<b>PidTagAccount</b>	0x3A00001F	<b>PtypString</b>	Contains the account name for the Address Book object.
6	<b>PidTagSurname</b>	0x3A11001F	<b>PtypString</b>	Contains the family name of the Address Book object.
7	<b>PidTagEmsAbPhoneticSurname</b>	0x8C8F001F	<b>PtypString</b>	Contains the phonetic spelling of the surname.
8	<b>PidTagGivenName</b>	0x3A06001F	<b>PtypString</b>	Contains the given name of the Address Book object.

9	<b>PidTagEmsAbPhoneticGivenName</b>	0x8C8E001F	<b>PtypString</b>	Contains the phonetic given name of the Address Book object.
10	<b>PidTagEmsAbProxyAddresses</b>	0x800f101f	<b>PtypMultipleString</b>	Contains the e-mail proxy addresses of the Address Book object. For example, SMTP:Laura.Miller@example.com or X400:c=US;a=;p=example;o=example;s=Miller;g=Laura;.
11	<b>PidTagOfficeLocation</b>	0x3A19001F	<b>PtypString</b>	Contains the office location of the Address Book object.
12	<b>PidTagDisplayType</b>	0x39000003	<b>PtypInteger32</b>	Contains a value that is used to associate an icon with a particular row of a table.
13	<b>PidTagObjectType</b>	0x0FFE0003	<b>PtypInteger32</b>	Contains the type of an object. The object type corresponds to the primary interface that is available for an object that is available through the <b>OpenEntry</b> interface.
14	<b>PidTagSendRichInfo</b>	0x3A40000B	<b>PtypBoolean</b>	Contains <b>TRUE</b> if the entry can receive all message content, including RTF and OLE objects.
15	<b>PidTagBusinessTelephoneNumber</b>	0x3A08001F	<b>PtypString</b>	Contains the primary business telephone for the Address Book object.
16	<b>PidTagInitials</b>	0x3A0A001F	<b>PtypString</b>	Contains the initials for parts of the full name of the Address Book object.
17	<b>PidTagStreetAddress</b>	0x3A29001F	<b>PtypString</b>	Contains the street address of the Address Book object.

18	<b>PidTagLocality</b>	0x3A27 001F	<b>PtypString</b>	Contains the name of the locality for the Address Book object, such as the town or city.
19	<b>PidTagStateOrProvince</b>	0x3A28 001F	<b>PtypString</b>	Contains the name of the state or province the Address Book object is located in.
20	<b>PidTagPostalCode</b>	0x3A2 A001F	<b>PtypString</b>	Contains the postal code for the postal address for the Address Book object.
21	<b>PidTagCountry</b>	0x3A26 001F	<b>PtypString</b>	Contains the name of the country or region where the Address Book object is located.
22	<b>PidTagTitle</b>	0x3A17 001F	<b>PtypString</b>	Contains the job title of the Address Book object.
23	<b>PidTagCompanyName</b>	0x3A16 001F	<b>PtypString</b>	Contains the name of the company associated with the Address Book object.
24	<b>PidTagEmsAbPhoneticCompany</b> <b>nyName</b>	0x8C91 001F	<b>PtypString</b>	Contains the phonetic spelling of the company name.
25	<b>PidTagAssistant</b>	0x3A30 001F	<b>PtypString</b>	Contains the name of the administrative assistant for the Address Book object.
26	<b>PidTagDepartment</b>	0x3A18 001F	<b>PtypString</b>	Contains a name for the department in which the Address Book object works.
27	<b>PidTagEmsAbPhoneticDepart</b> <b>mentName</b>	0x8C90 001F	<b>PtypString</b>	Contains the phonetic spelling of the department.
28	<b>PidTagEmsAbTargetAddress</b>	0x8011 001F	<b>PtypString</b>	Contains the destination address for this object.

29	<b>PidTagHomeTelephoneNumber</b>	0x3A09001F	<b>PtypString</b>	Contains the primary home telephone number for the Address Book object.
30	<b>PidTagBusiness2TelephoneNumber</b>	0x3A1B101F	<b>PtypMultipleString</b>	Contains secondary business telephone numbers for the Address Book object.
31	<b>PidTagHome2TelephoneNumber</b>	0x3A2F101F	<b>PtypMultipleString</b>	Contains secondary home telephone numbers for the Address Book object.
32	<b>PidTagPrimaryFaxNumber</b>	0x3A23001F	<b>PtypString</b>	Contains the telephone number of the primary fax machine used by the Address Book object.
33	<b>PidTagMobileTelephoneNumber</b>	0x3A1C001F	<b>PtypString</b>	Contains the cellular telephone number for the Address Book object.
34	<b>PidTagAssistantTelephoneNumber</b>	0x3A2E001F	<b>PtypString</b>	Contains the telephone number of the administrative assistant for the Address Book object.
35	<b>PidTagPagerTelephoneNumber</b>	0x3A21001F	<b>PtypString</b>	Contains the pager telephone number for the Address Book object.
36	<b>PidTagComment</b>	0x3004001F	<b>PtypString</b>	Contains a comment about the purpose or content of an object.
37	<b>PidTagUserCertificate</b>	0x3A220102	<b>PtypBinary</b>	Contains an ASN.1 authentication certificate for a messaging user.
38	<b>PidTagUserX509Certificate</b>	0x3A701102	<b>PtypMultipleBinary</b>	Contains X.509 version 3 security certificates for the Address Book object, as described in [RFC2459].

39	<b>PidTagEmsAbX509Cert</b>	0x8C6A1102	<b>PtypMultipleBinary</b>	Contains ASN.1 encoded X.509 certificates, as described in [RFC2459].
40	<b>PidTagEmsAbHomeMdb</b>	0x8006001e	<b>PtypString8</b>	Contains the X500 DN of the <b>message database (MDB)</b> for this mailbox. This property value is not subject to truncation.
41	<b>PidTagEmsAbDisplayNamePrintable</b>	0x39FF001e	<b>PtypString8</b>	Contains the printable string version of the display name.
42	<b>PidTagEmsAbDisplayType</b>	0x39050003	<b>PtypInteger32</b>	Contains a value used to associate an icon with a particular row of a table.
43	<b>PidTagOabTruncatedProps</b>	0x68051003	<b>PtypMultipleInteger32</b>	Contains a list of the property tags that have been truncated or limited by the server. If no properties have been removed or limited, the attribute will not be present.

Outlook 2007 SP1 expects the following attributes to be populated in the OAB Version 4 **rgOabAtts** table, and if they are missing, will not try to contact the server to retrieve the values when using the OAB files as a cache:

- **PidTagSmtAddress**
- **PidTagDisplayName**
- **PidTagAccount**
- **PidTagSurname**
- **PidTagGivenName**
- **PidTagEmsAbProxyAddresses**
- **PidTagOfficeLocation**
- **PidTagDisplayType**
- **PidTagObjectType**
- **PidTagSendRichInfo**
- **PidTagBusinessTelephoneNumber**
- **PidTagInitials**

- 
- **PidTagStreetAddress**
  - **PidTagLocality**
  - **PidTagStateOrProvince**
  - **PidTagPostalCode**
  - **PidTagCountry**
  - **PidTagTitle**
  - **PidTagCompanyName**
  - **PidTagAssistant**
  - **PidTagDepartment**
  - **PidTagEmsAbTargetAddress**
  - **PidTagHomeTelephoneNumber**
  - **PidTagBusiness2TelephoneNumber**
  - **PidTagHome2TelephoneNumber**
  - **PidTagPrimaryFaxNumber**
  - **PidTagMobileTelephoneNumber**
  - **PidTagAssistantTelephoneNumber**
  - **PidTagPagerTelephoneNumber**
  - **PidTagComment**
  - **PidTagUserCertificate**
  - **PidTagUserX509Certificate**
  - **PidTagEmsAbX509Cert**
  - **PidTagEmsAbHomeMdb**
  - **PidTagEmsAbDisplayNamePrintable**

## **Index**

- Applicability, 16
- Examples
  - Structure examples, 47
- Fields - vendor-extensible, 16
- Glossary, 5
- Informative references, 7
- Introduction, 5
- Normative references, 6
- OAB version 2
  - Structure overview, 8
- OAB version 4
  - Structure overview, 12
- Office/Exchange behavior, 54
- References, 6
  - Informative references, 7
  - Normative references, 6
- Relationship to protocols and other structures, 15
- Security considerations, 54
- Structure examples, 47
- Structure overview, 8
  - OAB version 2, 8
  - OAB version 4, 12
- Structures, 16
- Vendor-extensible fields, 16
- Versioning, 16