

[MS-OXODLGT]: Delegate Access Configuration Protocol Specification

Intellectual Property Rights Notice for Protocol Documentation

- **Copyrights.** This protocol documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the protocols, and may distribute portions of it in your implementations of the protocols or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the protocol documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the protocols. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, the protocols may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>). If you would prefer a written license, or if the protocols are not covered by the OSP, patent licenses are available by contacting protocol@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. This protocol documentation is intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it. A protocol specification does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them.

Revision Summary			
Author	Date	Version	Comments
Microsoft Corporation	April 4, 2008	0.1	Initial Availability.
Microsoft Corporation	April 25, 2008	0.2	Revised and updated property names and other technical content.
Microsoft Corporation	June 27, 2008	1.0	Initial Release.
Microsoft Corporation	August 6, 2008	1.01	Revised and edited technical content.
Microsoft Corporation	September 3, 2008	1.02	Revised and edited technical content.

1 of 36

[MS-OXODLGT] - v1.03

Delegate Access Configuration Protocol Specification
Copyright © 2008 Microsoft Corporation.
Release: Wednesday, December 3, 2008

Microsoft Corporation	December 3, 2008	1.03	Updated IP notice.
--------------------------	---------------------	------	--------------------

Table of Contents

1	<i>Introduction</i>	6
1.1	Glossary	6
1.2	References	7
1.2.1	Normative References	7
1.2.2	Informative References	8
1.3	Protocol Overview	8
1.3.1	Granting Delegate Permissions	9
1.3.2	Accessing Delegator Information	9
1.3.3	Acting on Behalf of a Delegator	9
1.4	Relationship to Other Protocols	9
1.5	Prerequisites/Preconditions	10
1.6	Applicability Statement	10
1.7	Versioning and Capability Negotiation	10
1.8	Vendor-Extensible Fields	10
1.9	Standards Assignments	10
2	<i>Messages</i>	10
2.1	Transport	10
2.2	Message Syntax	10
2.2.1	Delegate Data Folder	10
2.2.1.1	Common Properties	11
2.2.1.1.1	PidTagDisplayName	11
2.2.2	Delegate Information Object	11
2.2.2.1	Common Properties	11
2.2.2.1.1	PidTagMessageClass	11
2.2.2.1.2	PidTagNormalizedSubject	11
2.2.2.2	Delegate Information Properties	11
2.2.2.2.1	PidTagScheduleInfoDelegatorWantsCopy	11
2.2.2.2.2	PidTagScheduleInfoDelegatorWantsInfo	11
2.2.2.2.3	PidTagScheduleInfoDelegateNames	11
2.2.2.2.4	PidTagScheduleInfoDelegateNamesW	12
2.2.2.2.5	PidTagScheduleInfoDelegateEntryIds	12
2.2.2.2.6	PidTagDelegateFlags	12
2.2.3	Delegate Rule	12
2.2.3.1	Delegate Rule Properties	12
2.2.3.1.1	PidTagRuleState	12
2.2.3.1.2	PidTagRuleName	12
2.2.3.1.3	PidTagRuleProvider	13
2.2.3.1.4	PidTagRuleLevel	13
2.2.3.1.5	PidTagRuleCondition	13
2.2.3.1.6	PidTagRuleActions	13
3	<i>Protocol Details</i>	14
3.1	Client Details	14

3.1.1	Abstract Data Model	14
3.1.1.1	Delegator Client.....	14
3.1.1.2	Delegate Client	14
3.1.2	Timers	14
3.1.3	Initialization.....	14
3.1.4	Higher-Layer Triggered Events.....	14
3.1.4.1	Creating Delegate Data Folder	14
3.1.4.2	Creating Delegate Information Object	14
3.1.4.3	Creating Delegate Relationship	15
3.1.4.3.1	Set Send-On-Behalf-Of Delegator Permissions.....	15
3.1.4.3.2	Set Delegate Folder Permissions	15
3.1.4.3.3	Set Individual Delegate Preferences	17
3.1.4.3.4	Set Global Delegate Preferences.....	17
3.1.4.3.5	Set Delegate Rule.....	18
3.1.4.4	Opening Delegator's Special Folder.....	19
3.1.4.5	Display Delegator Contents.....	20
3.1.4.6	Send On Behalf Of Delegator.....	20
3.1.4.7	Receive/Process On Behalf Of Delegator	20
3.1.5	Message Processing Events and Sequencing Rules	20
3.1.6	Timer Events	20
3.1.7	Other Local Events.....	20
3.2	Server Details.....	20
3.2.1	Abstract Data Model	20
3.2.2	Timers	21
3.2.3	Initialization.....	21
3.2.4	Higher-Layer Triggered Events.....	21
3.2.4.1	Opening Delegator Root Special Folder.....	21
3.2.4.2	External Higher-Layer Triggered Events	21
3.2.4.2.1	Submitting On Behalf Of Delegator	21
3.2.4.2.2	Message Delivery to Delegator.....	21
3.2.4.2.3	Creating, Modifying, or Deleting Message Objects	21
3.2.5	Message Processing Events and Sequencing Rules	22
3.2.6	Timer Events	22
3.2.7	Other Local Events.....	22
4	Protocol Examples.....	22
4.1	Create Delegate Relationship with Multiple Delegates	22
4.1.1	Identify Delegator Special Folders	22
4.1.2	Set Send On Behalf Of Delegator Permissions	23
4.1.3	Update the Delegate Information Object	24
4.1.3.1	Open the Delegator Information Object	24
4.1.3.2	Update the Delegator Information Object Properties	24
4.1.4	Update the Delegate Rule	25
4.1.5	Set Permissions for Delegator Special Folders	27
4.2	Accept Meeting Request Object On Behalf Of Delegator	30

4.2.1	Identify Meeting Request Object Received on Behalf of Delegator	30
4.2.2	Identify Delegator Server and Mailbox.....	32
4.2.3	Access Delegator Calendar Special Folder.....	32
4.2.4	Send a Meeting Response Object on Behalf of the Delegator.....	33
5	<i>Security</i>	34
5.1	Security Considerations for Implementers	34
5.2	Index of Security Parameters	34
6	<i>Appendix A: Office/Exchange Behavior</i>	34
	<i>Index</i>	36

1 Introduction

This document specifies the Delegate Access Configuration protocol, which allows a user to delegate the responsibility for his or her **mailbox** to another user.

The Delegate Access Configuration protocol defines the following:

- The format to enable a user to send mail on behalf of the delegating user.
- The format to enable a user to receive meeting requests on behalf of the delegating user.
- The format for granting permissions to a user to read from or write to all or part of the delegating user's mailbox.
- The mechanism for accessing the delegating user's mailbox.

1.1 Glossary

The following terms are defined in [MS-OXGLOS]:

Address Book object
Calendar object
Calendar special folder
delegate
Delegate Information object
EntryID
folder ID (FID)
folder
from properties
handle
mailbox
meeting-related object
Meeting Request object
Meeting Response object
Meeting Update object
message ID (MID)
Message object
property
recipient properties
restriction
remote operation (ROP)
rule
rule action
sender properties
server-side rule
special folder
Task object

task request

Unicode

The following terms are specific to this document:

delegator: An individual who has granted permissions to a **delegate** to act on his or her behalf.

delegate data folder: A special folder that contains the **Delegate Information object**.

delegate rule: A server-side rule used to send mail to **delegates** on behalf of the **delegator**.

informational update: A **Meeting Update object** that includes a change, such as adding agenda details, which does not require attendees to re-respond.

Private Message object: A **Message object** with **properties** indicating that it contains sensitive information.

received representing properties: A group of **properties** that identifies the end user represented by the receiving **mailbox** owner.

remote user: An **Address Book object** known to be from a foreign or remote messaging system. For more information about remote users, see [MS-OXOABK] sections 2.2.3.11 and 2.2.3.12.

send on behalf of: A special permission granted to a **delegate** that allows him or her to send **Message objects** representing the **delegator**.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

[MS-OXCDATA] Microsoft Corporation, "Data Structures Protocol Specification", June 2008.

[MS-OXCFOLD] Microsoft Corporation, "Folder Object Protocol Specification", June 2008.

[MS-OXCMSG] Microsoft Corporation, "Message and Attachment Object Protocol Specification", June 2008.

[MS-OXCPERM] Microsoft Corporation, "Exchange Access and Operation Permissions Specification", June 2008.

[MS-OXCROPS] Microsoft Corporation, "Remote Operations (ROP) List and Encoding Protocol Specification", June 2008.

[MS-OXCSTOR] Microsoft Corporation, "Store Object Protocol Specification", June 2008.

[MS-OXDISCO] Microsoft Corporation, "Autodiscover HTTP Service Protocol Specification", June 2008.

[MS-OXOABK] Microsoft Corporation, "Address Book Object Protocol Specification", June 2008.

[MS-OXOCAL] Microsoft Corporation, "Appointment and Meeting Object Protocol Specification", June 2008.

[MS-OXOMSG] Microsoft Corporation, "E-Mail Object Protocol Specification", June 2008.

[MS-OXOPFFB] Microsoft Corporation, "Public Folder-Based Free/Busy Protocol Specification", June 2008.

[MS-OXORULE] Microsoft Corporation, "E-Mail Rules Protocol Specification", June 2008.

[MS-OXOSFLD] Microsoft Corporation, "Special Folders Protocol Specification", June 2008.

[MS-OXOTASK] Microsoft Corporation, "Task-Related Objects Protocol Specification", June 2008.

[MS-OXPROPS] Microsoft Corporation, "Exchange Server Protocols Master Property List Specification", June 2008.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

1.2.2 Informative References

None.

1.3 Protocol Overview

The Delegate Access Configuration protocol can be used to allow a **delegator** in an organization to delegate responsibility for several activities that are commonly performed on objects in the delegator's **mailbox**, or a delegator can configure delivery of **Meeting Request objects** directly to the **delegate**.

To allow a delegate to perform these activities, the delegator grants the delegate permissions to the resources required by the activity being performed. After permissions have been granted, the delegate is able to access the delegator's mailbox and complete the desired actions.

1.3.1 Granting Delegate Permissions

There are three sets of permissions that are commonly granted to a **delegate**: reviewer, author, and editor. These permissions are set on a specific set of **special folders**. The delegator decides on the level of permissions based on the activities the delegate will be performing, as follows:

- Reviewer permissions give the delegate read-only access to items.
- Author permissions allow the delegate to read all items, create new items, and delete and modify the items that the delegate creates.
- Editor permissions provide full control to the delegate.

Additionally, the delegate can be granted permissions to **send on behalf of** the delegator. This can be useful if the delegate will be responding to **Message objects**, managing **meeting-related objects**, and/or managing **Task objects**.

1.3.2 Accessing Delegator Information

To access the delegator's information, a **delegate** will identify and log on to the delegator's **mailbox**. The delegate will then identify the desired **special folder**, open the delegator's special folder, and manipulate items (such as creating or modifying appointments) to complete the task.

1.3.3 Acting on Behalf of a Delegator

If the **delegate** desires to send on behalf of the delegator, the delegate sets **properties** on the **Message** object to indicate that it is being sent on behalf of the delegator. The server will then validate that the delegate has the appropriate permissions to send on behalf of the delegator. It is also possible for the delegate to receive **meeting-related objects** on behalf of the delegator. These objects can only be acted on if the delegate has the appropriate permissions to the delegator's **Calendar special folder** and permission to send mail on behalf of the delegator. This is due to the fact that both of these permissions are required to properly process and respond to meeting-related objects.

1.4 Relationship to Other Protocols

The Delegate Access Configuration protocol depends on the following:

- Message and Attachment Object protocol, as specified in [MS-OXCMSG].
- Folder Object protocol, as specified in [MS-OXCFOLD].
- Exchange Access and Operation Permissions, as specified in [MS-OXCPERM].
- E-mail Rules protocol, as specified in [MS-OXORULE].
- E-mail Object protocol, as specified in [MS-OXOMSG].

- Address Book Object protocol, as specified in [MS-OXOABK].

1.5 Prerequisites/Preconditions

In the case of a delegator, this protocol assumes that the client has previously resolved the name of the delegator, logged on to the server, and acquired a **handle** to the **mailbox** of the delegator.

In the case of the **delegate**, this protocol assumes that the messaging client has previously resolved the name of the delegator, as specified in [MS-OXOABK].

1.6 Applicability Statement

This protocol is implemented when a user wants to manipulate the objects in another user's **mailbox**, send mail on another user's behalf, and/or manage meeting and **task requests** for another user.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

None.

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

This protocol uses the protocols specified in [MS-OXCFOLD], [MS-OXCMSG], [MS-OXCPERM], [MS-OXOMSG], [MS-OXOABK], and [MS-OXORULE] as its underlying transport mechanism.

2.2 Message Syntax

This protocol uses the structures specified in [MS-OXCDATA] and the **properties** specified in [MS-OXPROPS] as the low-level syntax through which the following property/value pairs are encoded. For more details about the values stored in these properties, see section 3.

2.2.1 Delegate Data Folder

The **delegate data folder** is a **special folder** residing under the root special folder that contains the **Delegate Information object**.

2.2.1.1 Common Properties

In addition to standard **folder properties** specified in [MS-OXCFOLD], the **delegate** data folder MUST contain the property listed in the following section.

2.2.1.1.1 *PidTagDisplayName*

This is a **PtypString** property and its value MUST be set to “Freebusy Data”.

2.2.2 Delegate Information Object

The **Delegate Information object** is special **Message object** used to store **delegate** access settings for a delegator. This Delegate Information object MUST be stored in the delegate data **folder** for the delegator.

Unless otherwise specified, the Delegate Information object adheres to all **property** constraints specified in [MS-OXPROPS] and [MS-OXCMSG]. A Delegate Information object MAY also contain other properties<1>, which are defined in [MS-OXPROPS], but these properties have no impact on the Delegate Access Configuration protocol.

2.2.2.1 Common Properties

In addition to standard **Message object properties** specified in [MS-OXCMSG], the **Delegate Information object** MUST contain the properties listed in the following sections.

2.2.2.1.1 *PidTagMessageClass*

This is a **PtypString** property and its value MUST be set to “IPM.Microsoft.ScheduleData.FreeBusy”.

2.2.2.1.2 *PidTagNormalizedSubject*

This is a **PtypString** property and its value MUST be set to “LocalFreebusy”.

2.2.2.2 Delegate Information Properties

2.2.2.2.1 *PidTagScheduleInfoDelegatorWantsCopy*

This **PtypBoolean** property indicates whether the delegator wants to receive copies of the meeting-related objects that are sent to the **delegate**.

This property MUST be set in the **Delegate Information object**.

2.2.2.2.2 *PidTagScheduleInfoDelegatorWantsInfo*

This **PtypBoolean** property indicates whether the delegator wants to receive **informational updates**, as specified in [MS-OXOCAL] sections 3.1.4.6.2.1 and 3.1.4.6.4.1. For more details about informational updates, see [MS-OXOCAL] section 1.3.1.5.

This **property** MUST be set in the **Delegate Information object**.

2.2.2.2.3 *PidTagScheduleInfoDelegateNames*

This **PtypMultipleString** property specifies the names of the **delegates**. Each entry MUST contain the value of the **PidTagDisplayName** property of each delegate's **Address Book object**. For details about the Address Book object, see [MS-OXOABK].

This **property** MAY <2> be accessed and manipulated as a **PtypMultipleString8** property, which can cause a loss of fidelity when converting from **Unicode**.

2.2.2.2.4 PidTagScheduleInfoDelegateNamesW

This **PtypMultipleString** property specifies the names of the **delegates**. Each entry MUST contain the value of the **PidTagDisplayName** property of each delegate's **Address Book object**. For more details about the Address Book object, see [MS-OXOABK].

This **property** MUST be accessed and manipulated as a **PtypMultipleString** property, preserving the fidelity of **Unicode** information.

2.2.2.2.5 PidTagScheduleInfoDelegateEntryIds

This **PtypMultipleBinary** property specifies the **EntryIDs** of the **delegates**. Each entry MUST contain the value of the **PidTagEntryId** property of each delegate's **Address Book object**. For more details about the Address Book object, see [MS-OXOABK].

This property MUST be set in the **Delegate Information object**.

2.2.2.2.6 PidTagDelegateFlags

This **PtypMultipleInteger32** property indicates whether **delegates** can view **Private Message objects**. Each entry of this property MUST be set to one of the following values.

Flag	Value	Description
HidePrivate	0x00000000	The delegate SHOULD NOT be allowed to view Private Message objects.
ShowPrivate	0x00000001	The delegate SHOULD be allowed to view Private Message objects.

This property MUST be set in the **Delegate Information object**.

2.2.3 Delegate Rule

To enable calendar workflow scenarios where **delegates** receive copies of **meeting-related objects** that are sent to the delegator, a delegator's client MUST create a specific type of **server-side rule**, as specified in [MS-OXORULE] section 3.1.4.3.

2.2.3.1 Delegate Rule Properties

The **delegate rule** is specified by setting the properties listed in the following sections.

2.2.3.1.1 PidTagRuleState

This is a **PtypInteger32** property and its value MUST be set to "0x00000001".

2.2.3.1.2 PidTagRuleName

This is a **PtypString** property and its value MUST be set to "" (a zero-length string).

2.2.3.1.3 *PidTagRuleProvider*

This is a **PtypString** property and its value MUST be set to “Schedule+ EMS Interface”.

2.2.3.1.4 *PidTagRuleLevel*

This is a **PtypInteger32** property and its value MUST be set to “0x00000000”.

2.2.3.1.5 *PidTagRuleCondition*

This is a **PtypRestriction** property and its value MUST be set to a **restriction** of type RES_AND with the following three sub-clauses:

1. A restriction of type RES_CONTENT that limits a table view to rows that include the string “IPM.Schedule.Meeting” in the **PidTagMessageClass** property column. The level of precision, which is specified in the **FuzzyLevelLow** field of the **ContentRestriction** structure, is set to FL_PREFIX.
2. A restriction of type RES_NOT with the following sub-clause:
 - i) A restriction of type RES_EXIST that specifies the **PidTagDelegatedByRule** property.
3. A restriction of type RES_OR with the following two sub-clauses:
 - i) A restriction of type RES_NOT with the following sub-clause:
 - (1) A restriction of type RES_EXIST that specifies the **PidTagSensitivity** property.
 - ii) A restriction of type RES_PROPERTY that specifies a comparison of the value of the **PidTagSensitivity** property to the value “Private” (“0x00000002”). The relationship operator, which is specified in the **RelOp** field of the **PropertyRestriction** structure, is set to RELOP_NE.

For more details about restrictions, see [MS-OXCDATA] section 2.14.

2.2.3.1.6 *PidTagRuleActions*

This **PtypRuleAction** property specifies the **delegate's rule actions**, which are used to:

1. Send copies of **meeting-related objects** to delegates.
Use the OP_DELEGATE action, as specified in [MS-OXORULE] section 2.2.5.1.3.4.
2. Delete the delegator's copy of meeting-related objects.
Use the OP_DELETE action, as specified in [MS-OXORULE] section 2.2.5.1.3.7.

Sections 3.1.4.3.2.1 and 3.1.4.3.4 specify when these actions MUST be specified in the delegate rule. For more details about rule actions, see [MS-OXORULE] section 2.2.5.

3 Protocol Details

3.1 Client Details

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

3.1.1.1 Delegator Client

A **delegator** client is used by a delegator to establish delegation relationships with one or more **delegates**, and is used to store delegator preferences in the **Delegate Information object**.

3.1.1.2 Delegate Client

A **delegate** client is used to perform actions on behalf of the delegator. To perform these actions, the delegate client will:

- Access the delegator's **mailbox** to create, modify, or delete objects.
- Honor preferences stored by the delegator client in the **Delegate Information object**.
- Send **Message objects** on behalf of the delegator.

3.1.2 Timers

None.

3.1.3 Initialization

None.

3.1.4 Higher-Layer Triggered Events

3.1.4.1 Creating Delegate Data Folder

The client for a delegator MUST create the **delegate data folder** under the delegator's root **special folder**.

In addition, the **EntryID** for the delegate data folder is stamped in the **PidTagFreeBusyEntryIds** property, as specified in [MS-OXOPFFB] section 2.2.2.1.

3.1.4.2 Creating Delegate Information Object

The client for a delegator MUST create the **Delegate Information object** under the delegator's **delegate data folder**.

In addition, the **EntryID** for the Delegate Information object is stamped in the **PidTagFreeBusyEntryIds** property, as specified in [MS-OXOPFFB] section 2.2.2.1.

3.1.4.3 Creating Delegate Relationship

The client for a **delegator** establishes the **delegate** relationship by setting permissions and individual preferences for delegates, as well as setting global delegate preferences. A client for the delegator accomplishes this by performing the following steps, as specified in sections 3.1.4.3.1 through 3.1.4.3.5.

3.1.4.3.1 Set Send-On-Behalf-Of Delegator Permissions

The delegator's client SHOULD grant **send-on-behalf-of** permissions to every **delegate** <3>. This is accomplished by adding the value of the **PidTagEntryId** property of the delegate's **Address Book object** to the **PidTagAddressBookPublicDelegates** property of the delegator's address book container, as specified in [MS-OXOABK].

A client MAY<4> support delegation for a **remote user** if it indicates that it supports sharing of the delegator's information. The remote user supports sharing of the delegator's information if the remote user's Address Book object has bit S set in the **PidTagDisplayTypeEx** property, as specified in [MS-OXOABK] section 2.2.3.12.

3.1.4.3.2 Set Delegate Folder Permissions

The following table specifies roles supported by this protocol. Roles are a specific set of flags for the value of the **PidTagMemberRights** property, which is used when setting **folder** permissions, as specified in [MS-OXCPERM] section 2.2.1.6.

Role name	Numeric value	PidTagMemberRights flags	Description
None	0x00000000	None	The delegate is not able to view, create, modify, or delete any contents from the folder .
Reviewer	0x00000001	ReadAny	The delegate is able to view contents of the folder. However, the delegate will not be able to create, modify, or delete any contents from the folder.

Role name	Numeric value	PidTagMemberRights flags	Description
Author	0x00000001B	ReadAny Create EditOwned DeleteOwn	The delegate is able to view contents of the folder. In addition, the delegate is able to create, modify, and delete any items created by this delegate.
Editor	0x00000007B	ReadAny Create EditOwned DeleteOwn EditAny DeleteAny	The delegate is able to view, create, modify, and delete any items in the folder.

The delegator client MUST specify a role for each of the following **special folders**, as specified in [MS-OXOSFLD]:

- Calendar
- Inbox
- Tasks
- Contacts
- Notes
- Journal

The delegator **special folders** listed in the following sections have additional constraints.

3.1.4.3.2.1 Additional Constraints for Calendar Folder

If a **delegate** will process **meeting-related objects** on behalf of the delegator, a client MUST:

1. Grant, to the delegate, the Author or Editor role on the delegator's **Calendar special folder**, as specified in [MS-OXCPERM] section 3.1.4.2.
Note: Granting the Author role will allow the delegate to act only on new **Message objects** or those created by the same delegate.
2. Grant, to the delegate, the Editor role on the delegate data **folder**, as specified in [MS-OXCPERM] section 3.1.4.2.
Note: If the delegate data folder doesn't exist, the client for the delegator MUST create it.

Additionally, if a delegate will receive meeting-related objects on behalf of the delegator, a client MUST:

1. Grant, to the delegate, the Editor role on the delegator's Calendar special folder, as specified in [MS-OXCPERM] section 3.1.4.2.
2. Grant **send-on-behalf-of** permissions to the delegate.
3. Add the OP_DELEGATE action, including all delegates that will receive meeting-related objects on behalf the delegator. The OP_DELEGATE action is specified in [MS-OXORULE] section 2.2.5.1.3.4.

3.1.4.3.2.2 Additional Constraints for the Tasks Folder

If a **delegate** will process **task requests** on behalf of the delegator, a client MUST:

1. Grant, to the delegate, the Author or Editor role on the delegator's Task **special folder**, as specified in [MS-OXOPERM] section 3.1.4.2.
Note: Granting the Author role will allow the delegate to act only on new items or ones created by the same delegate.
2. Grant **send-on-behalf-of** permissions to the delegate.

3.1.4.3.3 Set Individual Delegate Preferences

For each **delegate** being specified, the client for the delegator MUST:

1. Specify the delegate's name, using the value of the **PidTagDisplayName** property for the **Address Book object** of the delegate.
This MAY<5> be specified as an entry in the **PidTagScheduleInfoDelegateNames** property, or it MAY<6> be specified as an entry in the **PidTagScheduleInfoDelegateNamesW** property.
A client SHOULD specify both **PidTagScheduleInfoDelegateNames** and **PidTagScheduleInfoDelegateNamesW** information for highest fidelity; otherwise a client MUST specify all delegates using the same **property** (either all in **PidTagScheduleInfoDelegateNames** or all in **PidTagScheduleInfoDelegateNamesW**).
2. Specify the value of the **PidTagEntryId** property for the Address Book object of the delegate as an entry in the **PidTagScheduleInfoDelegateEntryIds** property.
3. Specify whether the delegate can view the delegator's private **Message objects** as an entry in the **PidTagDelegateFlags** property. This preference is applicable to all **folders** for which the delegate has a role of Reviewer, Author, or Editor.

Note: Because each multiple-valued property specified above MUST have one entry for each delegate, they are correlated by their index into these multiple-valued properties, and are only valid if an entry is present for all three properties.

3.1.4.3.4 Set Global Delegate Preferences

The following preferences are specific to Calendar workflows, and are applicable to all **delegates**. These preferences are used in conjunction with **rules**, and allow a delegator to have

greater control over which **meeting-related objects** are delivered to the delegator, the delegate, or both.

For more details about Calendar workflows, see [MS-OXOCAL].

3.1.4.3.4.1 Set the **PidTagScheduleInfoDelegatorWantsCopy** Property

The value of this property MUST be set to “0x01” in the following cases:

- A delegator wants to receive **meeting-related objects**.
- No **delegates** will receive meeting-related objects on behalf of the delegator.

Otherwise, the value MUST be set to “0x00”.

The OP_DELETE action MUST NOT be present when this **property** has a value of “0x01”.

The value of this property MUST be set to “0x01” if the value of the

PidTagScheduleInfoDelegatorWantsInfo property is set to “0x01”.

The delegator MUST add the OP_DELETE action, as specified in [MS-OXORULE] section 2.2.5.1.3.7, when this property has a value of “0x00”.

For more information about how this property is used, see [MS-OXOCAL] section 3.1.4.

3.1.4.3.4.2 Set the **PidTagScheduleInfoDelegatorWantsInfo** Property

The value of this **property** MUST be set to “0x01” when a delegator wants to receive informational updates, as specified in [MS-OXOCAL] section 3.1.4.6.2.1. Otherwise, it MUST be set to “0x00”.

The value of this property MUST be set to “0x00” if the value of property **PidTagScheduleInfoDelegatorWantsCopy** is set to “0x00”. For more information about how this property is used, see [MS-OXOCAL] section 3.1.4.

The following table illustrates valid combinations of the **PidTagScheduleInfoDelegatorWantsCopy** (WC) and **PidTagScheduleInfoDelegatorWantsInfo** (WI) properties.

WC	WI	Description
1	1	The delegator wants to receive copies and would like these copies to be informational updates when applicable.
1	0	The delegator wants to receive copies.
0	1	Invalid, as the delegator cannot receive informational updates unless the delegator receives copies.
0	0	The delegator doesn't want to receive copies or informational updates.

3.1.4.3.5 Set Delegate Rule

The client for the delegator MUST create or update the **delegate rule**, which is specified in section 2.2.3, if, while creating the delegate relationship:

1. Any delegate will be receiving **Meeting-Request objects** on behalf of the delegator, as this adds the OP_DELEGATE action to the delegate rule.

2. The delegator has elected not to receive copies of Meeting Request objects, as this adds the OP_DELETE action to the delegate rule.

3.1.4.4 Opening Delegator's Special Folder

To open a **special folder** belonging to a delegator, the client for the **delegate** MUST use the following steps:

1. Identify and establish a connection to the delegator's server.
2. Identify and log on to the delegator's **mailbox**.
3. Identify and open the delegator's special folder.

The delegate's client uses properties from the **Address Book object** that represents the delegator to identify the delegator's server and mailbox.

If the Address Book object has a value in the **PidTagAddressBookHomeMessageDatabase** property, this value MUST be used to identify the delegator's server. Otherwise, if the delegator is a **remote user**, the client MAY<7> use the delegate's own server and let the Autodiscover HTTP Service protocol **handle** redirection to the correct server [MS-OXDISCO]. A remote user can be identified by examining the **PidTagDisplayType** property of the user's Address Book object. If the **PidTagDisplayType** property has the value DT_REMOTE_MAILUSER, then the delegate is a remote user. For more information about the **PidTagDisplayType** property, see [MS-OXOABK] section 2.2.3.11.

If the Address Book object has a valid **PidTagAddressBookProxyAddresses** property and this **property** contains "MAILBOX" or "EX", then one of these strings MUST be used, in the following order, to identify the delegator's mailbox.:

1. The "MAILBOX" entry, if present.
2. The "EX" entry, if present.

If the Address Book object doesn't contain a valid **PidTagAddressBookProxyAddresses** property, or this property doesn't contain "MAILBOX" or "EX" entries, then the mailbox MUST be identified by the value of the **PidTagEmailAddress** property.

After establishing a connection to the server, the client uses **RopLogon** to connect to the delegator's private mailbox with HOME_LOGON and TAKE_OWNERSHIP flags, as specified in [MS-OXCSTOR] section 2.2.1.1.

After the client has logged on to the delegator's mailbox, the delegate's client identifies the desired **special folder** within the delegator's mailbox, as specified in [MS-OXCSTOR] or [MS-OXOSFLD].

The client uses **RopOpenFolder** to open the delegator's special folder as specified in [MS-OXCFOLD] section 2.2.1.

3.1.4.5 Display Delegator Contents

The client for a **delegate** SHOULD NOT show private **Message objects** of the delegator unless the **PidTagDelegateFlags** property for the delegate has a value of “ShowPrivate”, indicating that the delegator wants to make private Message objects visible.

3.1.4.6 Send On Behalf Of Delegator

When sending **Message objects** on behalf of the delegator, the client of the **delegate** MUST populate **from properties**, as specified in [MS-OXOMSG] section 3.1.1.2.1, with information from the delegator.

3.1.4.7 Receive/Process On Behalf Of Delegator

The client for a **delegate** can identify that a **Message object** has been received on behalf of the delegator when the **received representing properties** are present and different than the **recipient properties**. For more details about recipient properties, see [MS-OXOMSG] section 3.1.1.2.2.1.

If received representing properties are present, these MUST take precedence over recipient properties to identify the delegator **Address Book object**.

When the client for a delegate is processing a meeting-related object received on behalf of a delegator, the client for the delegate MUST create or access the corresponding **Calendar object** in the delegator’s **special folder**. For more details about processing a meeting-related object, see [MS-OXOCAL].

When the client for a delegate is processing a **task request** on behalf of a delegator, the client for the delegate MUST create the corresponding **Task object** in the delegator’s special folder. For more details about processing a task request, see [MS-OXOTASK].

3.1.5 Message Processing Events and Sequencing Rules

None.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

3.2 Server Details

3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not

mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

This protocol is primarily client driven; however, the server plays an important role in ensuring that **delegate** scenarios are possible, which is accomplished mostly by implementing underlying protocols. As such, the abstract data model for this protocol is not significantly different than that of its underlying protocols.

3.2.2 Timers

None.

3.2.3 Initialization

None.

3.2.4 Higher-Layer Triggered Events

3.2.4.1 Opening Delegator Root Special Folder

The server MUST provide read access to a delegator's root **special folder** and its **properties**, as the **delegate** will need to obtain the **FID** for the delegator's special folders, as specified in [MS-OXOSFLD].

3.2.4.2 External Higher-Layer Triggered Events

This section specifies higher-layer triggered events implemented in external protocols that are required for scenarios in this protocol.

3.2.4.2.1 Submitting On Behalf Of Delegator

For non-meeting related objects, a server MUST validate that the **delegate**, which is specified in **sender properties**, has access to send-on-behalf-of the delegator, which is specified in **from properties**. For more details about sender properties and from properties, see [MS-OXOMSG] section 3.1.1.2.

3.2.4.2.2 Message Delivery to Delegator

A server MUST process the **delegate rule** when present, as specified in [MS-OXORULE]. When present, the delegator's **rule actions** accomplish the following:

- The OP_DELEGATE action ensures that **meeting-related objects** are delivered to the **delegate**, and that these meeting-related objects are on behalf of the delegator, who is identified by **received representing properties**.
- The OP_DELETE action ensures that the delegator does not receive unwanted **Meeting Request objects**.

3.2.4.2.3 Creating, Modifying, or Deleting Message Objects

When a **delegate** attempts to create, modify, or delete a **Message object** that resides in the delegator **mailbox**, a server MUST ensure that the delegate has sufficient permissions [MS-OXCPERM].

Additionally, a server MUST track the creator and last modifier of any Message object as specified in [MS-OXCMSG].

3.2.5 Message Processing Events and Sequencing Rules

None.

3.2.6 Timer Events

None.

3.2.7 Other Local Events

None.

4 Protocol Examples

4.1 Create Delegate Relationship with Multiple Delegates

The following example shows the **ROP** traces for the delegator named “delegator1” creating a relationship with the **delegate** named “delegate1” and the delegate named “delegate2”. The ROP traces in this example are truncated to more easily illustrate ROP information that is specific to this protocol.

This example highlights the following steps when setting up the delegate relationship:

1. Identifying delegator **special folders**.
2. Setting send-on-behalf-of delegator permissions.
3. Updating the **Delegate Information object**.
4. Updating the delegate rule.
5. Setting permissions for delegator special folders.

4.1.1 Identify Delegator Special Folders

To identify the delegator **special folders**, the client will log on to the delegator **mailbox** and query for the special folder **properties** from the Inbox special folder, which is provided in response to the **RopLogon** request. For more information about **ROPs**, see [MS-OXCROPS].

```
RopLogon
    ROPid: 0xFE
    LogonFlags: 0x01 Private
    OpenFlags: 0x0100040C HOME_LOGON TAKE_OWNERSHIP NO_MAIL CLI_WITH_PER_MDB_FIX
    Private Logon  LegacyDN: /o=First Organization/ou=Exchange Administrative
Group (FYDIBOHF23SPDLT)/cn=Recipients/cn=delegator1
RopLogon
```

```

ROPid: 0xFE
FolderArray:
...
    FolderID 4: 0001-00174ea8cd9d IPM subtree
FolderID 5: 0001-00174ea8cda0 Inbox
    FolderID 6: 0001-00174ea8cd9d Outbox
...
RopOpenFolder
    ROPid: 0x02
FID: 0001-00174ea8cda0
RopOpenFolder
    ROPid: 0x02
HandleIndex: 1 (HSOT=0x00000085)
    ReturnValue: ecNone (success) (0x00000000)
RopGetPropertiesSpecific
    ROPid: 0x07
HandleIndex: 2 (HSOT=0x00000085)
    ReturnValue: ecNone (success) (0x00000000)
    PropCount: 29
...
    0x36D00102 PidTagIpmAppointmentEntryId      PttypBinary      46 Bytes
        0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
        0010: 7F 9B 97 BC 01 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
        0020: 07 ED 54 48 84 OF 00 17-4E A8 9C 98 00 00 ..TH....N....
    0x36D10102 PidTagIpmContactEntryId      PttypBinary      46 Bytes
        0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
        0010: 7F 9B 97 BC 01 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
        0020: 07 ED 54 48 84 OF 00 17-4E A8 9C 99 00 00 ..TH....N....
    0x36D20102 PidTagIpmJournalEntryId      PttypBinary      46 Bytes
        0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
        0010: 7F 9B 97 BC 01 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
        0020: 07 ED 54 48 84 OF 00 17-4E A8 9C 9B 00 00 ..TH....N....
    0x36D30102 PidTagIpmNoteEntryId      PttypBinary      46 Bytes
        0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
        0010: 7F 9B 97 BC 01 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
        0020: 07 ED 54 48 84 OF 00 17-4E A8 9C 9C 00 00 ..TH....N....
    0x36D40102 PidTagIpmTaskEntryId      PttypBinary      46 Bytes
        0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
        0010: 7F 9B 97 BC 01 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
        0020: 07 ED 54 48 84 OF 00 17-4E A8 9C 9D 00 00 ..TH....N....
    0x36E41102 PidTagFreeBusyEntryIds      PttypMultipleBinary
        PttypMultipleBinary[0] (0 bytes):
        PttypMultipleBinary[1] (70 bytes):
            0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
            0010: 7F 9B 97 BC 07 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
            0020: 07 ED 54 48 84 OF 00 17-4E A8 9C D4 00 00 8B 8D ..TH....N....
            0030: B1 82 AF 2E D0 48 93 47-07 ED 54 48 84 OF 00 17 4E A8 E7 68 00 00 .....H.G..TH....
            0040: 4E A8 E7 68 00 00 N...h..
        PttypMultipleBinary[2] (0 bytes):
        PttypMultipleBinary[3] (46 bytes):
            0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
            0010: 7F 9B 97 BC 01 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
            0020: 07 ED 54 48 84 OF 00 17-4E A8 9C D4 00 00 ..TH....N....
...

```

4.1.2 Set Send On Behalf Of Delegator Permissions

Then, the delegator will set send-on-behalf-of permissions by using the **NspiModLinkAtt** method, as specified in [MS-OXOABK] section 2.2.5.

```

NspiModLinkAtt
...
0x8015000D PidTagAddressBookPublicDelegates
...
PtypMultipleBinary
  PtypMultipleBinary[0] (128 bytes):
    0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
    0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 6F 3D 46 +/...../o=F
    0020: 69 72 73 74 20 4F 72 67-61 6E 69 7A 61 74 69 6F irst Organizatio
    0030: 6E 2F 6F 75 3D 45 78 63-68 61 6E 67 65 20 41 64 n/ou=Exchange Ad
    0040: 6D 69 6E 69 73 74 72 61-74 69 76 65 20 47 72 6F ministrative Gro
    0050: 75 70 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 up (FYDIBOHF23SP
    0060: 44 4C 54 29 2F 63 6E 3D-52 65 63 69 70 69 65 6E DLT)/cn=Recipien
    0070: 74 73 2F 63 6E 3D 64 65-6C 65 67 61 74 65 32 00 ts/cn=delegate2.

  PtypMultipleBinary[1] (128 bytes):
    0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
    0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 6F 3D 46 +/...../o=F
    0020: 69 72 73 74 20 4F 72 67-61 6E 69 7A 61 74 69 6F irst Organizatio
    0030: 6E 2F 6F 75 3D 45 78 63-68 61 6E 67 65 20 41 64 n/ou=Exchange Ad
    0040: 6D 69 6E 69 73 74 72 61-74 69 76 65 20 47 72 6F ministrative Gro
    0050: 75 70 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 up (FYDIBOHF23SP
    0060: 44 4C 54 29 2F 63 6E 3D-52 65 63 69 70 69 65 6E DLT)/cn=Recipien
    0070: 74 73 2F 63 6E 3D 64 65-6C 65 67 61 74 65 31 00 ts/cn=delegate1.

...

```

4.1.3 Update the Delegate Information Object

There are two steps necessary to update the **Delegate Information object**: opening the object and updating the **properties**.

4.1.3.1 Open the Delegator Information Object

The client will open the **Delegate Information object** by using the **MID** and the **FID**, which are the first entry and the fourth entry, respectively, in the **PidTagFreeBusyEntryIds** property. The value of the **NormalizedSubject** field (in the **RopOpenMessage** response) can be examined to determine whether the intended object has been opened. In this case, the value is “LocalFreebusy”, verifying that the operation opened the correct object.

```

RopOpenMessage
  ROPid: 0x03
  FolderId: 0001-00174ea89cd4
  OpenModeFlags: 0x03 BestAccess rights
  MessageID: 0001-00174ea8e768
RopOpenMessage
  ROPid: 0x03
  HandleIndex: 1 (HSOT=0x00000062)
  ReturnValue: ecNone (success) (0x00000000)
  NormalizedSubject: LocalFreebusy

```

4.1.3.2 Update the Delegator Information Object Properties

The client will update the **PidTagScheduleInfoDelegatorWantsCopy** property and the **PidTagScheduleInfoDelegatorWantsInfo** property with the delegator global settings. In this case, the **delegate** does want copies of meeting-related objects, and would prefer to receive informational meeting-related objects if the client supports this workflow.

In addition, the delegator will update the **PidTagScheduleInfoDelegateNamesW**, **PidTagScheduleInfoDelegateEntryIds**, and **PidTagDelegateFlags** properties for each delegate. “delegate2” is stored in the first entry of these multiple-valued properties, and “delegate1” is stored in the second entry of these multiple-valued properties. The delegator is only allowing “delegate2” to see private **Message objects**. The “delegate2” preferences, as well as global delegator preferences, are highlighted.

```
RopSetProperties
    ROPid: 0x0A
    HandleIndex: 0 (HSOT=0x00000062)
    PropCount: 12 (0x0C)
    ...
    0x6842000B PidTagScheduleInfoDelegatorWantsCopy      PttypBoolean 0x01 (TRUE)
    0x684A101F PidTagScheduleInfoDelegateNamesW          PttypMultipleString
        PttypMultipleString[0]:delegate2
        PttypMultipleString[1]:delegate1
    0x68451102 PidTagScheduleInfoDelegateEntryIds       PttypMultipleBinary
        PttypMultipleBinary[0] (128 bytes):
        0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
        0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 6F 3D 46 +/...../o=F
        0020: 69 72 73 74 20 4F 72 67-61 6E 69 7A 61 74 69 6F irst Organizatio
        0030: 6E 2F 6F 75 3D 45 78 63-68 61 6E 67 65 20 41 64 n/ou=Exchange Ad
        0040: 6D 69 6E 69 73 74 72 61-74 69 76 65 20 47 72 6F ministrative Gro
        0050: 75 70 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 up (FYDIBOHF23SP
        0060: 44 4C 54 29 2F 63 6E 3D-52 65 63 69 70 69 65 6E DLT)/cn=Recipien
        0070: 74 73 2F 63 6E 3D 64 65-6C 65 67 61 74 65 32 00 ts/cn=delegate2.
        PttypMultipleBinary[1] (128 bytes):
        0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
        0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 6F 3D 46 +/...../o=F
        0020: 69 72 73 74 20 4F 72 67-61 6E 69 7A 61 74 69 6F irst Organizatio
        0030: 6E 2F 6F 75 3D 45 78 63-68 61 6E 67 65 20 41 64 n/ou=Exchange Ad
        0040: 6D 69 6E 69 73 74 72 61-74 69 76 65 20 47 72 6F ministrative Gro
        0050: 75 70 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 up (FYDIBOHF23SP
        0060: 44 4C 54 29 2F 63 6E 3D-52 65 63 69 70 69 65 6E DLT)/cn=Recipien
        0070: 74 73 2F 63 6E 3D 64 65-6C 65 67 61 74 65 31 00 ts/cn=delegate1.
    0x686B1003 PidTagDelegateFlags                      PttypMultipleInteger32
        PttypMultipleInteger32[0]: 0
        PttypMultipleInteger32[1]: 1
    0x684B000B PidTagScheduleInfoDelegatorWantsInfo     PttypBoolean 0x01 (TRUE)
    ...
RopSaveChangesMessage
    ROPid: 0x0C
    LogonIndex: 0
    HandleIndex: 0 (HSOT=0x00000062)
    SaveOptions: 0x0A KeepOpenReadWrite DelayedCall
```

4.1.4 Update the Delegate Rule

The delegator's client will update the **delegate rule** on the receive **folder** rule by using **RopModifyRules**, as specified in [MS-OXORULE] section 2.2.1. Given the actions, only “delegate1” will be receiving meeting-related objects on behalf of the delegator.

```
RopGetReceiveFolder
    ROPid: 0x27
    HandleIndex: 0 (HSOT=0x0000006f)
    ReturnValue: ecNone (success) (0x00000000)
```

```

FID: 0001-00174ea8cda0
RopOpenFolder
    ROPid: 0x02
HandleIndex: 0 (HSOT=0x0000006f)
FID: 0001-00174ea8cda0
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
HandleIndex: 2 (HSOT=0x00000058)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyRules
    ROPid: 0x41
HandleIndex: 0 (HSOT=0x00000058)
    ModifyRulesFlags: 0x01 ROWLIST_REPLACE
    RulesCount: 1
Parsing row: 1
    RuleModificationFlag: 0x01 ROW_ADD
    PropCount: 8 (0x08)
    0x66760003 PidTagRuleSequence      PtypInteger32  0x00000000 (0)
    0x66770003 PidTagRuleState       PtypInteger32  Flags: 0x00000001 ST_ENABLED
    0x667900FD PidTagRuleCondition   PtypRestriction Linked Restriction
        Linked Restriction:
            ConditionType: 0x00 RES_AND:
                NoOfConditions: 3 restrictions
                ConditionType: 0x03 RES_CONTENT:
                    FuzzyLevel: 0x00000002 FL_PREFIX
                    0x001A001F PidTagMessageClass          PtypString
                        IPM.Schedule.Meeting
                ConditionType: 0x02 RES_NOT
                    Linked Restriction:
                        ConditionType: 0x08 RES_EXIST:
                            PropertyTag: 0x3FE3000B PidTagDelegatedByRule
                ConditionType: 0x01 RES_OR:
                    NoOfConditions: 2 restrictions
                    ConditionType: 0x02 RES_NOT
                        Linked Restriction:
                            ConditionType: 0x08 RES_EXIST:
                                PropertyTag: 0x00360003 PidTagSensitivity
                ConditionType: 0x04 RES_PROPERTY:
                    RelationalOperator: 0x05 RELOP_NE
                    0x00360003 PidTagSensitivity          PtypInteger32
                        Flags: 0x00000002 SENSITIVITY_PRIVATE
    0x668000FE PidTagRuleActions      PtypRuleAction
        NoOfActions: 0x0001 (1)
        Parsing action 1
ActionType: 0x08 OP_DELEGATE
        Parsing action data:
        RecipientCount: 0x0001 (1)
        Recipient 1:
            PropCount: 12 (0x0C)
            0xFFFF0102 PidTagEntryId           PtypBinary      128 Bytes
                0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
                0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 6F 3D 46 +/...../o=F
                0020: 69 72 73 74 20 4F 72 67-61 6E 69 7A 61 74 69 6F irst Organizatio
                0030: 6E 2F 6F 75 3D 45 78 63-68 61 6E 67 65 20 41 64 n/ou=Exchange Ad
                0040: 6D 69 6E 69 73 74 72 61-74 69 76 65 20 47 72 6F ministrative Gro
                0050: 75 70 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 up (FYDIBOHF23SP
                0060: 44 4C 54 29 2F 63 6E 3D-52 65 63 69 70 69 65 6E DLT)/cn=Recipien
                0070: 74 73 2F 63 6E 3D 64 65-6C 65 67 61 74 65 31 00 ts/cn=delegate1.
            0x3001001F PidTagDisplayName     PtypString      delegate1

```

0x681001F PidTagRuleProvider	PtypString	Schedule+ EMS Interface
0x6830003 PidTagRuleLevel	PtypInteger32	0x00000000 (0)
0x682001F PidTagRuleName	PtypString	(null)
0x6780003 PidTagRuleUserFlags	PtypInteger32	0x00000000 (0)

4.1.5 Set Permissions for Delegator Special Folders

Lastly, the client will apply **folder** permissions to all delegator **special folders** that are specified in this protocol.

In this example, the client is granting the same role to both **delegates**. The client grants the following:

- Editor role to the Calendar (the only **ROP** trace shown for both delegates) and Task special folders.
- None role to the Inbox, Contacts, Notes, and Journal special folders.
- Editor role to the “Freebusy Data” folder.

```
RopOpenFolder
    ROPid: 0x02
    FID: 0001-00174ea89c98
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
    HandleIndex: 9 (HSOT=0x00000055)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyPermissions
    ROPid: 0x40
    HandleIndex: 0 (HSOT=0x00000055)
    ACLTableFlags: 0x01 ROWLIST_REPLACE
    RecipientRowCount: 3
    Parsing row: 3
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
        0xFFFF0102 PidTagEntryId          PtypBinary      128 Bytes
        0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
        0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 6F 3D 46 +/...../o=F
        0020: 69 72 73 74 20 4F 72 67-61 6E 69 7A 61 74 69 6F irst Organizatio
        0030: 6E 2F 6F 75 3D 45 78 63-68 61 6E 67 65 20 41 64 n/ou=Exchange Ad
        0040: 6D 69 6E 69 73 74 72 61-74 69 76 65 20 47 72 6F ministrative Gro
        0050: 75 70 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 up (FYDIBOHF23SP
        0060: 44 4C 54 29 2F 63 6E 3D-52 65 63 69 70 69 65 6E DLT)/cn=Recipien
        0070: 74 73 2F 63 6E 3D 64 65-6C 65 67 61 74 65 32 00 ts/cn=delegate2.

        0x66730003 PidTagMemberRights          PtypInteger32  0x0000007B (123)
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
        0xFFFF0102 PidTagEntryId          PtypBinary      128 Bytes
        0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
        0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 6F 3D 46 +/...../o=F
        0020: 69 72 73 74 20 4F 72 67-61 6E 69 7A 61 74 69 6F irst Organizatio
        0030: 6E 2F 6F 75 3D 45 78 63-68 61 6E 67 65 20 41 64 n/ou=Exchange Ad
        0040: 6D 69 6E 69 73 74 72 61-74 69 76 65 20 47 72 6F ministrative Gro
        0050: 75 70 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 up (FYDIBOHF23SP
        0060: 44 4C 54 29 2F 63 6E 3D-52 65 63 69 70 69 65 6E DLT)/cn=Recipien
        0070: 74 73 2F 63 6E 3D 64 65-6C 65 67 61 74 65 31 00 ts/cn=delegate1.

        0x66730003 PidTagMemberRights          PtypInteger32  0x0000007B (123)
    ACLFlag: 0x01 ROW_ADD
```

```

PropCount: 2 (0x2)
    0xFFFF0102 PidTagEntryId
    0x66730003 PidTagMemberRights
RopOpenFolder
    ROPid: 0x02
FID: 0001-00174ea89c9d
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
HandleIndex: 1 (HSOT=0x0000004d)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyPermissions
    ROPid: 0x40
HandleIndex: 0 (HSOT=0x0000004d)
    ACLTableFlags: 0x01 ROWLIST_REPLACE
    RecipientRowCount: 3
    Parsing row: 3
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
    ...
0x66730003 PidTagMemberRights PtypInteger32 0x0000007B (123)
    ...
RopOpenFolder
    ROPid: 0x02
FID: 0001-00174ea8cd40
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
HandleIndex: 1 (HSOT=0x00000066)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyPermissions
    ROPid: 0x40
    LogonIndex: 0
HandleIndex: 0 (HSOT=0x00000066)
    ACLTableFlags: 0x01 ROWLIST_REPLACE
    RecipientRowCount: 3
    Parsing row: 3
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
    ...
0x66730003 PidTagMemberRights PtypInteger32 0x00000000 (0)
    ...
RopOpenFolder
    ROPid: 0x02
FID: 0001-00174ea89c99
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
HandleIndex: 1 (HSOT=0x00000086)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyPermissions
    ROPid: 0x40
HandleIndex: 0 (HSOT=0x00000086)
    ACLTableFlags: 0x01 ROWLIST_REPLACE
    RecipientRowCount: 3
    Parsing row: 3
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
    ...
0x66730003 PidTagMemberRights PtypInteger32 0x00000000 (0)

```

```

...
RopOpenFolder
    ROPid: 0x02
FID: 0001-00174ea89c9c
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
HandleIndex: 1 (HSOT=0x0000008f)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyPermissions
    ROPid: 0x40
HandleIndex: 0 (HSOT=0x0000008f)
    ACLTableFlags: 0x01 ROWLIST_REPLACE
    RecipientRowCount: 3
    Parsing row: 3
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
    ...
0x66730003 PidTagMemberRights          PttypInteger32  0x00000000 (0)

...
RopOpenFolder
    ROPid: 0x02
FID: 0001-00174ea89c9b
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
HandleIndex: 1 (HSOT=0x000000d3)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyPermissions
    ROPid: 0x40
HandleIndex: 0 (HSOT=0x000000d3)
    ACLTableFlags: 0x01 ROWLIST_REPLACE
    RecipientRowCount: 3
    Parsing row: 3
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
    ...
0x66730003 PidTagMemberRights          PttypInteger32  0x00000000 (0)

...
RopOpenFolder
    ROPid: 0x02
FID: 0001-00174ea89cd4
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
HandleIndex: 1 (HSOT=0x0000006a)
    ReturnValue: ecNone (success) (0x00000000)
RopModifyPermissions
    ROPid: 0x40
HandleIndex: 0 (HSOT=0x0000006a)
    ACLTableFlags: 0x01 ROWLIST_REPLACE
    RecipientRowCount: 3
    Parsing row: 3
    ACLFlag: 0x01 ROW_ADD
    PropCount: 2 (0x02)
    ...
0x66730003 PidTagMemberRights          PttypInteger32  0x0000007B (123)
...

```

4.2 Accept Meeting Request Object On Behalf Of Delegator

The following example shows the ROP traces for the **delegate**, “delegate1”, receiving and processing a **Meeting Request object** on behalf of the delegator, “delegator1”. The ROP traces in this example are truncated to more easily illustrate ROP information that is specific to this protocol.

This example shows that the delegator’s **Calendar special folder** is opened to process the Meeting Request object, but the example doesn’t go into the details of the creation of the **Calendar object** in the delegator’s **mailbox**, as this is specified in [MS-OXOCAL].

This example also shows the creation and submission of a **Meeting Response object** on behalf of the delegator, as this illustrates setting the **from properties**.

This example highlights the following steps when accepting a Meeting Request object on behalf of the delegator:

1. Identify that the meeting-related object is received on behalf of the delegator.
2. Identify the delegator’s server and mailbox.
3. Access the delegator’s Calendar special folder.
4. Send a Meeting Response object on behalf of the delegator.

4.2.1 Identify Meeting Request Object Received on Behalf of Delegator

In the following ROP traces, the client is logged on to the **delegate** “delegate1” **mailbox**, and opens a **Meeting Request object** from the **Inbox special folder**. **Received representing properties** are present and different than **recipient properties**; therefore, as specified in section 3, the Meeting Request object is being received on behalf of the delegator.

```
RopLogon
    ROPid: 0xFE
    LogonFlags: 0x01 Private
    OpenFlags: 0x0100040C HOME_LOGON TAKE_OWNERSHIP NO_MAIL CLI_WITH_PER_MDB_FIX
    Private Logon   LegacyDN: /o=First Organization/ou=Exchange Administrative
Group (FYDIBOHF23SPDLT)/cn=Recipients/cn=delegate1
RopLogon
    ROPid: 0xFE
    HandleIndex: 0 (HSOT=0x00000049)
    ReturnValue: ecNone (success) (0x00000000)
    FolderArray:
        ...
        FolderID 4: 0001-00174ea8cfdc IPM subtree
        FolderID 5: 0001-00174ea8cfdf Inbox
        FolderID 6: 0001-00174ea8cfe0 Outbox
        ...
RopOpenMessage
    ROPid: 0x03
    FolderId: 0001-00174ea8cfdf
    OpenModeFlags: 0x03 BestAccess rights
    MessageID: 0001-00174ea8d45b
RopOpenMessage
    ROPid: 0x03
    HandleIndex: 1 (HSOT=0x0000007b)
    ReturnValue: ecNone (success) (0x00000000)
```

30 of 36

[MS-OXODLGT] - v1.03

Delegate Access Configuration Protocol Specification
Copyright © 2008 Microsoft Corporation.
Release: Wednesday, December 3, 2008

```

NormalizedSubject: delegatetest
...
RopGetPropertiesSpecific
    ROPid: 0x07
    HandleIndex: 0 (HSOT=0x0000007b)
    ReturnValue: ecNone (success) (0x00000000)
    HasError: 1
    PropertyArray:
    PropCount: 349
...
    0x0040001F PidTagReceivedByName          PttypString      delegate1
    0x0075001F PidTagReceivedByAddressType  PttypString      EX
    0x003F0102 PidTagReceivedEntryId        PttypBinary     128 Bytes
        0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
        0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 4F 3D 46 +/...../O=F
        0020: 49 52 53 54 20 4F 52 47-41 4E 49 5A 41 54 49 4F IRST ORGANIZATIO
        0030: 4E 2F 4F 55 3D 45 58 43-48 41 4E 47 45 20 41 44 N/OU=EXCHANGE AD
        0040: 4D 49 4E 49 53 54 52 41-54 49 56 45 20 47 52 4F MINISTRATIVE GRO
        0050: 55 50 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 UP (FYDIBOHF23SP
        0060: 44 4C 54 29 2F 43 4E 3D-52 45 43 49 50 49 45 4E DLT) /CN=RECIPIEN
        0070: 54 53 2F 43 4E 3D 44 45-4C 45 47 41 54 45 31 00 TS/CN=DELEGATE1.
    0x0076001F PidTagReceivedByEmail1Address PttypString      /O=FIRST
ORGANIZATION/OU=EXCHANGE ADMINISTRATIVE GROUP
(FYDIBOHF23SPDLT) /CN=RECIPIENTS/CN=DELEGATE1
    0x00510102 PidTagReceivedBySearchKey    PttypBinary     103 Bytes
        0000: 45 58 3A 2F 4F 3D 46 49-52 53 54 20 4F 52 47 41 EX:/O=FIRST ORGA
        0010: 4E 49 5A 41 54 49 4F 4E-2F 4F 55 3D 45 58 43 48 NIZATION/OU=EXCH
        0020: 41 4E 47 45 20 41 44 4D-49 4E 49 53 54 52 41 54 ANGE ADMINISTRAT
        0030: 49 56 45 20 47 52 4F 55-50 20 28 46 59 44 49 42 IVE GROUP (FYDIB
        0040: 4F 48 46 32 33 53 50 44-4C 54 29 2F 43 4E 3D 52 OHF23SPDLT) /CN=R
        0050: 45 43 49 50 49 45 4E 54-53 2F 43 4E 3D 44 45 4C ECIPENTS/CN=DEL
        0060: 45 47 41 54 45 31 00 EGATE1.
    0x0044001F PidTagReceivedRepresentingName PttypString      delegator1
    0x0077001F PidTagReceivedRepresentingAddressType PttypString      EX
    0x00430102 PidTagReceivedRepresentingEntryId  PttypBinary     129 Bytes
        0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B.....
        0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 4F 3D 46 +/...../O=F
        0020: 49 52 53 54 20 4F 52 47-41 4E 49 5A 41 54 49 4F IRST ORGANIZATIO
        0030: 4E 2F 4F 55 3D 45 58 43-48 41 4E 47 45 20 41 44 N/OU=EXCHANGE AD
        0040: 4D 49 4E 49 53 54 52 41-54 49 56 45 20 47 52 4F MINISTRATIVE GRO
        0050: 55 50 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 UP (FYDIBOHF23SP
        0060: 44 4C 54 29 2F 43 4E 3D-52 45 43 49 50 49 45 4E DLT) /CN=RECIPIEN
        0070: 54 53 2F 43 4E 3D 44 45-4C 45 47 41 54 4F 52 31 TS/CN=DELEGATOR1
        0080: 00 .
    0x0078001F PidTagReceivedRepresentingEmailAddress
        PidTagRemoteHeaderLoc          PttypString      /O=FIRST
ORGANIZATION/OU=EXCHANGE ADMINISTRATIVE GROUP
(FYDIBOHF23SPDLT) /CN=RECIPIENTS/CN=DELEGATOR1
    0x00520102 PidTagReceivedRepresentingSearchKey PttypBinary     104 Bytes
        0000: 45 58 3A 2F 4F 3D 46 49-52 53 54 20 4F 52 47 41 EX:/O=FIRST ORGA
        0010: 4E 49 5A 41 54 49 4F 4E-2F 4F 55 3D 45 58 43 48 NIZATION/OU=EXCH
        0020: 41 4E 47 45 20 41 44 4D-49 4E 49 53 54 52 41 54 ANGE ADMINISTRAT
        0030: 49 56 45 20 47 52 4F 55-50 20 28 46 59 44 49 42 IVE GROUP (FYDIB
        0040: 4F 48 46 32 33 53 50 44-4C 54 29 2F 43 4E 3D 52 OHF23SPDLT) /CN=R
        0050: 45 43 49 50 49 45 4E 54-53 2F 43 4E 3D 44 45 4C ECIPENTS/CN=DEL
        0060: 45 47 41 54 4F 52 31 00 EGATOR1.
    0x001A001F PidTagMessageClass            PttypString
IPM.Schedule.Meeting.Request
...

```

4.2.2 Identify Delegator Server and Mailbox

Because this **Meeting Request object** is received on behalf of the delegator, the next step is to identify the server and **mailbox** for the delegator, and log on to the delegator's mailbox. The server will be identified by the value of the **PidTagAddressBookHomeMessageDatabase** property, and because the **PidTagAddressBookProxyAddresses** property doesn't have a "MAILXOB" or "EX" entry, the mailbox will be identified by the value of the **PidTagEmailAddress** property.

```
NspiGetProps
...
    0x8006001f PidTagAddressBookHomeMessageDatabase          PtypString
        /o=First Organization/ou=Exchange Administrative Group
        (FYDIBOHF23SPDLT)/cn=Configuration/cn=Servers/cn=3659R9-A13/cn=Microsoft Private
        MDB
    0x3003001f PidTagEmailAddress          PtypString
        /o=First Organization/ou=Exchange Administrative Group
        (FYDIBOHF23SPDLT)/cn=Recipients/cn=delegator1
    0x800f101f PidTagAddressBookProxyAddresses      PtypMultipleString
        PtypMultipleString[0]: SMTP:delegator1@jlpno-dom.extest.microsoft.com
...

```

4.2.3 Access Delegator Calendar Special Folder

Because this is a **Meeting Request object**, the client will need to access the delegator's **Calendar special folder**. As specified, the delegator's Calendar special folder is identified by using the value of the **PidTagIpmAppointmentEntryId** property, which is found in the delegator's root folder.

The following example shows the ROP traces to accomplish this.

```
RopLogon
    ROPid: 0xFE
    LogonFlags: 0x01 Private
    OpenFlags: 0x0100040C HOME_LOGON TAKE_OWNERSHIP NO_MAIL CLI_WITH_PER_MDB_FIX
    Private Logon LegacyDN: /o=First Organization/ou=Exchange Administrative
    Group (FYDIBOHF23SPDLT)/cn=Recipients/cn=delegator1
RopLogon
    ROPid: 0xFE
    HandleIndex: 0 (HSOT=0x0000008f)
    ReturnValue: ecNone (success) (0x00000000)
    FolderArray:
        FolderID 1: 0001-00174ea8cd9c Root Folder
    ...
RopOpenFolder
    ROPid: 0x02
    HandleIndex: 0 (HSOT=0x0000008f)
    FID: 0001-00174ea8cd9c
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
    HandleIndex: 1 (HSOT=0x00000068)
    ReturnValue: ecNone (success) (0x00000000)
RopGetPropertySpecific
    ROPid: 0x07
    HandleIndex: 0 (HSOT=0x00000068)
```

```

ReturnValue: ecNone (success) (0x00000000)
PropCount: 11
0x36D00102 PidTagIpmAppointmentEntryId          PtypBinary      46 Bytes
    0000: 00 00 00 00 C3 E1 78 57-96 52 CE 46 A3 53 B3 E0 .....xW.R.F.S..
    0010: 7F 9B 97 BC 01 00 8B 8D-B1 82 AF 2E D0 48 93 47 .....H.G
    0020: 07 ED 54 48 84 0F 00 17-4E A8 9C 98 00 00 ..TH....N.....
...
RopOpenFolder
    ROPid: 0x02
    HandleIndex: 0 (HSOT=0x0000008f)
    FID: 0001-00174ea89c98
    OpenModeFlags: 0x00 ReadOnly
RopOpenFolder
    ROPid: 0x02
    HandleIndex: 1 (HSOT=0x00000080)
    ReturnValue: ecNone (success) (0x00000000)
RopGetPropertiesSpecific
    ROPid: 0x07
    HandleIndex: 1 (HSOT=0x00000080)
    ReturnValue: ecNone (success) (0x00000000)
    PropertyArray:
    PropCount: 17
...
0x3001001F PidTagDisplayName                  PtypString      Calendar
...

```

4.2.4 Send a Meeting Response Object on Behalf of the Delegator

The final step in this example is to create and submit a **Meeting Response object** on behalf of the delegator. The following example shows that the client is populating the **from properties** with delegator information.

```

RopCreateMessage
    ROPid: 0x06
    HandleIndex: 1 (HSOT=0x000000a4)
    ReturnValue: ecNone (success) (0x00000000)
RopSetProperties
    ROPid: 0x0A
    LogonIndex: 0
    HandleIndex: 0 (HSOT=0x000000a4)
    PropertySize: 0x0A46 (2630)
    PropCount: 123 (0x7B)
...
0x0042001F PidTagSentRepresentingName
    PidTagSentRepresentingName      PtypString      delegator1
0x0064001F PidTagSentRepresentingAddressType   PtypString      (null)
0x00410102 PidTagSentRepresentingEntryId       PtypBinary     129 Bytes
    0000: 00 00 00 00 DC A7 40 C8-C0 42 10 1A B4 B9 08 00 .....@..B....
    0010: 2B 2F E1 82 01 00 00 00-00 00 00 00 2F 4F 3D 46 +/...../O=F
    0020: 49 52 53 54 20 4F 52 47-41 4E 49 5A 41 54 49 4F IRST ORGANIZATIO
    0030: 4E 2F 4F 55 3D 45 58 43-48 41 4E 47 45 20 41 44 N/OU=EXCHANGE AD
    0040: 4D 49 4E 49 53 54 52 41-54 49 56 45 20 47 52 4F MINISTRATIVE GRO
    0050: 55 50 20 28 46 59 44 49-42 4F 48 46 32 33 53 50 UP (FYDIBOHF23SP
    0060: 44 4C 54 29 2F 43 4E 3D-52 45 43 49 50 49 45 4E DLT)/CN=RECIPIEN
    0070: 54 53 2F 43 4E 3D 44 45-4C 45 47 41 54 4F 52 31 TS/CN=DELEGATOR1
    0080: 00
0x001A001F PidTagMessageClass                PtypString
IPM.Schedule.Meeting.Resp.Pos
...

```

```

RopSetProperties
    ROPid: 0x0A
    HandleIndex: 2 (HSOT=0x000000a4)
    PropertySize: 0x003A (58)
    PropCount: 2 (0x02)
        0x003D001F PidTagSubjectPrefix
        0x0E1D001F PidTagNormalizedSubject
            PttypString Accepted: delegatetest
RopSubmitMessage
    ROPid: 0x32
    HandleIndex: 2 (HSOT=0x000000a4)
    SubmitMessageFlags: 0x00

```

5 Security

5.1 Security Considerations for Implementers

There are no special security considerations specific to the Delegate Access Configuration protocol. General security considerations pertaining to the underlying RPC-based transport apply. For more information about these security considerations, see [MS-OXCROPS].

5.2 Index of Security Parameters

None.

6 Appendix A: Office/Exchange Behavior

The information in this specification is applicable to the following versions of Office/Exchange:

- Office 2003 with Service Pack 3 applied
- Exchange 2003 with Service Pack 2 applied
- Office 2007 with Service Pack 1 applied
- Exchange 2007 with Service Pack 1 applied

Exceptions, if any, are noted below. Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies Office/Exchange behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies Office/Exchange does not follow the prescription.

<1> Section 2.2.2: Outlook 2003 and Outlook 2007 sometimes set the following properties regardless of user input; their values have no meaning in the context of this protocol.

PidTagScheduleInfoDontMailDelegates, **PidTagScheduleInfoDelegateEntryIds2**, and **PidTagDelegateFlag2**.

<2> Section 2.2.2.2.3: Outlook 2003 uses a **PtypMutipleString8** internal representation. Therefore, this version is unable to preserve the fidelity for all **Unicode** strings.

-
- <3> Section 3.1.4.3.1: Outlook 2007 will stop creating delegate relationship if send-on-behalf-of permissions cannot be granted.
- <4> Section 3.1.4.3.1: This is only supported by Outlook 2007 when running against Exchange 2007.
- <5> Section 3.1.4.3.3: Outlook 2003 uses the **PidTagScheduleInfoDelegateNames** property.
- <6> Section 3.1.4.3.3: Outlook 2007 uses the **PidTagScheduleInfoDelegateNamesW** property.
- <7> Section 3.1.4.4: This is only supported by Outlook 2007 when running against Exchange 2007.

Index

Applicability statement, 10
Client details, 14
Examples, 22
Glossary, 6
Index of security parameters, 34
Informative references, 8
Introduction, 6
Message syntax, 10
Messages, 10

- Message syntax, 10
- Transport, 10

Normative references, 7
Office/Exchange behavior, 34
Overview, 8
Preconditions, 10
Prerequisites, 10
Protocol details, 14

- Client details, 14
- Server details, 20

References, 7

- Informative references, 8
- Normative references, 7

Relationship to other protocols, 9
Security, 34

- Considerations for implementers, 34
- Index of security parameters, 34

Security considerations for implementers, 34
Server details, 20
Standards assignments, 10
Transport, 10
Vendor-extensible fields, 10
Versioning and capability negotiation, 10