

# [MS-OXOPFFB]: Public Folder Based Free/Busy Protocol Specification

## Intellectual Property Rights Notice for Protocol Documentation

- **Copyrights.** This protocol documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the protocols, and may distribute portions of it in your implementations of the protocols or your documentation as necessary to properly document the implementation. This permission also applies to any documents that are referenced in the protocol documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the protocols. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, the protocols may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>). If you would prefer a written license, or if the protocols are not covered by the OSP, patent licenses are available by contacting [protocol@microsoft.com](mailto:protocol@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** This protocol documentation is intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it. A protocol specification does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them.

Revision Summary			
Author	Date	Version	Comments
Microsoft Corporation	April 4, 2008	0.1	Initial Availability.
Microsoft Corporation	April 25, 2008	0.2	Revised and updated property names and other technical content.
Microsoft Corporation	June 27, 2008	1.0	Initial Release.
Microsoft Corporation	August 6, 2008	1.01	Updated references to reflect date of initial release.

Microsoft Corporation	September 3, 2008	1.02	Updated references.
-----------------------	-------------------	------	---------------------

# Table of Contents

<b>1</b>	<b>Introduction.....</b>	<b>5</b>
1.1	Glossary .....	5
1.2	References .....	7
1.2.1	Normative References .....	7
1.2.2	Informative References .....	8
1.3	Protocol Overview .....	8
1.4	Relationship to Other Protocols.....	8
1.5	Prerequisites/Preconditions.....	8
1.6	Applicability Statement.....	8
1.7	Versioning and Capability Negotiation.....	8
1.8	Vendor-Extensible Fields .....	9
1.9	Standards Assignments .....	9
<b>2</b>	<b>Messages.....</b>	<b>9</b>
2.1	Transport.....	9
2.2	Message Syntax.....	9
2.2.1	Free/Busy Message.....	9
2.2.1.1	Common Properties.....	9
2.2.1.1.1	PidTagNormalizedSubject .....	9
2.2.1.1.2	PidTagMessageClass.....	9
2.2.1.2	Free/Busy Properties .....	9
2.2.1.2.1	PidTagScheduleInfoMonthsTentative.....	9
2.2.1.2.2	PidTagScheduleInfoFreeBusyTentative .....	10
2.2.1.2.3	PidTagScheduleInfoMonthsBusy.....	10
2.2.1.2.4	PidTagScheduleInfoFreeBusyBusy .....	10
2.2.1.2.5	PidTagScheduleInfoMonthsAway .....	11
2.2.1.2.6	PidTagScheduleInfoFreeBusyAway .....	11
2.2.1.2.7	PidTagScheduleInfoMonthsMerged .....	11
2.2.1.2.8	PidTagScheduleInfoFreeBusyMerged .....	11
2.2.1.2.9	PidTagFreeBusyPublishStart .....	11
2.2.1.2.10	PidTagFreeBusyPublishEnd.....	11
2.2.1.2.11	PidTagFreeBusyRangeTimestamp.....	11
2.2.1.2.12	PidTagFreeBusyMessageEmailAddress.....	12
2.2.1.3	Delegate Information Properties .....	12
2.2.1.4	Deprecated Properties.....	12
2.2.1.4.1	PidTagGatewayNeedsToRefresh .....	12
2.2.1.4.2	PidTagScheduleInfoResourceType .....	12
2.2.1.4.3	PidTagScheduleInfoFreeBusy .....	12
2.2.2	Public Folder Free/Busy Related Properties .....	12
2.2.2.1	PidTagFreeBusyEntryIds.....	12
<b>3</b>	<b>Protocol Details.....</b>	<b>13</b>

3.1	Client Details .....	13
3.1.1	Abstract Data Model .....	13
3.1.1.1	Non-Persisted Free/Busy Related Properties .....	13
3.1.1.1.1	PidTagSchedulePlusFreeBusyEntryId .....	14
3.1.2	Timers .....	14
3.1.3	Initialization .....	14
3.1.4	Higher-Layer Triggered Events .....	14
3.1.4.1	Publishing Free/Busy Data.....	14
3.1.4.1.1	Determining the Data Set for Publishing.....	14
3.1.4.1.2	Finding the Free/Busy Message.....	15
3.1.5	Message Processing Events and Sequencing Rules.....	16
3.1.6	Timer Events.....	16
3.1.7	Other Local Events .....	16
<b>4</b>	<b>Protocol Examples.....</b>	<b>17</b>
4.1	Updating the Free/Busy Message.....	17
4.2	Finding Free/Busy Messages Using E-mail Addresses .....	18
4.3	PidTagScheduleInfoMonthsBusy Calculation .....	32
4.4	PidTagScheduleInfoFreeBusyBusy Calculation .....	33
4.4.1	PidTagScheduleInfoFreeBusyBusy Calculation with Two Non-Consecutive Events .....	35
4.4.2	PidTagScheduleInfoFreeBusyBusy Calculation with Two Consecutive Events	35
4.4.3	PidTagScheduleInfoFreeBusyBusy Calculation with Events in Multiple Months.	36
4.4.4	PidTagScheduleInfoFreeBusyBusy Calculation When an Event is Spread Across Multiple Months .....	36
4.5	PidTagScheduleInfoFreeBusyMerged Calculation.....	37
<b>5</b>	<b>Security.....</b>	<b>37</b>
5.1	Security Considerations for Implementers.....	37
5.2	Index of Security Parameters.....	37
<b>6</b>	<b>Appendix A: Office/Exchange Behavior.....</b>	<b>37</b>
	<b>Index.....</b>	<b>39</b>

# 1 Introduction

The Public Folder Based Free/Busy Protocol is a format used to publish information describing the availability of an **attendee** or **resource**. This information can be leveraged by a broad range of consumers to efficiently schedule meetings and/or provide presence information.

The Public Folder Based Free/Busy protocol specifies:

- The format in which **free/busy** data is represented.
- A method for publishing data in the prescribed format.
- A method for discovering and interpreting data in the prescribed format.

## 1.1 Glossary

The following terms are defined in [MS-OXGLOS]:

**attendee**  
**Address Book object**  
**ambiguous name resolution (ANR)**  
**appointment**  
**Calendar object**  
**Coordinated Universal Time (UTC)**  
**delegate**  
**Delegate Information object**  
**distinguished name (DN)**  
**EntryID**  
**folder**  
**folder ID (FID)**  
**free/busy**  
**little-endian**  
**message**  
**message ID (MID)**  
**Message object**  
**non-IPM subtree**  
**Out of Office (OOF)**  
**property**  
**property ID**  
**public folder**  
**remote operation (ROP)**  
**resource**  
**special folder**  
**store**

The following data types are defined in [MS-DTYP]:

## BYTE

The following data types are defined in [MS-OXCADATA]:

**PtypBinary**  
**PtypBoolean**  
**PtypInteger32**  
**PtypMultipleBinary**  
**PtypMultipleInteger32**  
**PtypString**  
**PtypTime**

The following terms are specific to this document:

**Availability Service:** A Web service that provides free/busy information.

**Busy:** One of the possible values of the **free/busy status** on an **appointment**. Indicates that the user is not available for other **appointments** during this time.

**calendar:** See **Calendar object**.

**conflict:** When an **appointment** is scheduled at the same time as another, the **appointments** are said to be in **conflict**.

**end of range:** End date of **publishing range**.

**Free:** One of the possible values of the **free/busy status** on an **appointment**. Indicates that the user is available during this **appointment**.

**free/busy message:** A message in the **public folder store** that contains **free/busy** data.

**free/busy status:** Indicates how an **appointment** on the calendar of an **attende**e or **resource** affects their availability. The **free/busy status** is the value of the **PidLidBusyStatus** property of the **appointment**, as specified in [MS-OXOCAL].

**Tentative:** One of the possible values of the **free/busy status** on an **appointment**. Indicates that the user is tentatively booked during this **appointment**.

**publishing:** In the context of this specification, this term is used to denote writing **free/busy** data to a shared location.

**publishing range:** The number of months of **calendar** data to be published.

**start of range:** The start date of **publishing range**.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [RFC2119]. All statements of optional behavior use either **MAY**, **SHOULD**, or **SHOULD NOT**.

## 1.2 References

### 1.2.1 Normative References

[MS-DTYP] Microsoft Corporation, "Windows Data Types", March 2007, <http://go.microsoft.com/fwlink/?LinkId=111558>.

[MS-OXCDATA] Microsoft Corporation, "Data Structures Protocol Specification", June 2008.

[MS-OXCFOLD] Microsoft Corporation, "Folder Object Protocol Specification", June 2008.

[MS-OXCMSG] Microsoft Corporation, "Message and Attachment Object Protocol Specification", June 2008.

[MS-OXCSTOR] Microsoft Corporation, "Store Object Protocol Specification", June 2008.

[MS-OXCTABL] Microsoft Corporation, "Table Object Protocol Specification", June 2008.

[MS-OXDSCLI] Microsoft Corporation, "Autodiscover Publishing and Lookup Protocol Specification", June 2008.

[MS-OXGLOS] Microsoft Corporation, "Exchange Server Protocols Master Glossary", June 2008.

[MS-OXOABK] Microsoft Corporation, "Address Book Object Protocol Specification", June 2008.

[MS-OXOCAL] Microsoft Corporation, "Appointment and Meeting Object Protocol Specification", June 2008.

[MS-OXODLGT] Microsoft Corporation, "Delegate Access Configuration Protocol Specification", June 2008.

[RFC1279] Hardcastle-Kille, S.E., "X.500 and Domains", RFC 1279, November 1991, <http://www.ietf.org/rfc/rfc1279.txt>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

## 1.2.2 Informative References

None.

## 1.3 Protocol Overview

**Free/busy** data is derived from **calendar** data and falls into four categories: **Free**, **Busy**, **Tentative** and **Out of Office (OOF)**.

The Public Folder Based Free/Busy Protocol specifies how free/busy data is read from and written to a shared location so that it can be used to effectively and efficiently schedule meetings.

Free/busy data can also be obtained using the Availability Web service as specified in [MS-OXWAVLS], and by directly accessing the calendar of a user and reading the free/busy status property as specified in [MS-OXOCAL].

## 1.4 Relationship to Other Protocols

The Public Folder Based Free/Busy protocol extends the Message and Attachment Object protocol [MS-OXCMSG].

## 1.5 Prerequisites/Preconditions

The Public Folder Based Free/Busy protocol assumes that the server is configured to support **public folders**.<1>

## 1.6 Applicability Statement

The Public Folder Based Free/Busy protocol is appropriate for use by higher layers of a server or client implementation that schedule meetings to avoid scheduling **conflicts**.

The following related functionality is best accomplished using other protocols:

- Displaying complete **calendar** details is best accomplished by receiving permissions and directly browsing the calendar of the other **attendee** or **resource**. For more details, see [MS-OXODLGT].
- Displaying **free/busy** data outside of the **publishing range** is best accomplished by using the **Availability Service**, as specified in [MS-OXWAVLS].

It is recommended that this specification only be used if the Availability Service is not supported by the server.<2> For more details about the Availability Service, see [MS-OXDSCLI].

## 1.7 Versioning and Capability Negotiation

None.



## ***1.8 Vendor-Extensible Fields***

None.

## ***1.9 Standards Assignments***

None.

# **2 Messages**

## ***2.1 Transport***

The Public Folder Based Free/Busy protocol uses the protocol defined in [MS-OXCMSG] as its primary transport mechanism.

## ***2.2 Message Syntax***

### **2.2.1 Free/Busy Message**

**Free/busy** data is represented as a set of properties set on a message in the **public folders store**. The **message** is referred to as the **free/busy message**. The location of this message is specified in section 3. Unless otherwise specified below, the free/busy message adheres to the **Message object** guidance in [MS-OXCMSG].

#### **2.2.1.1 Common Properties**

##### ***2.2.1.1.1 PidTagNormalizedSubject***

A **PtypString** property that specifies the subject of the **free/busy message**. Its value is a string derived from the e-mail address of the user. The e-mail address is the value of the **PidTagEmailAddress** property of the **Address Book object** of the user. The subject is derived by taking the sub-string starting with “/cn” and prepending “USER-” and converting all the characters to upper-case.

##### ***2.2.1.1.2 PidTagMessageClass***

A **PtypString** property that **MUST** be set to “IPM.Post”.

#### **2.2.1.2 Free/Busy Properties**

##### ***2.2.1.2.1 PidTagScheduleInfoMonthsTentative***

A **PtypMultipleInteger32** property that specifies the months for which **free/busy** data of type **Tentative** is present in the **free/busy message**. The number of **PtypInteger32** values in this property **MUST** be between zero and the number of months covered by the **publishing range**, which is the period between **PidTagFreeBusyPublishStart** and **PidTagFreeBusyPublishEnd**.

Each value in this **PtypMultipleInteger32**, interpreted as a signed **PtypInteger32**, has a month and year encoded in it. This is calculated using the expression “year × 16 + month” where year and month are based on the Gregorian **calendar**. The values are sorted in ascending order and are encoded in **little-endian** format.

If an event is spread across multiple months, or multiple years, there **MUST** be one value for each of the months that fall in the publishing range. If there are no tentative events in the publishing range, then this **property** and **PidTagScheduleInfoFreeBusyTentative** **MUST NOT** be set or **MUST** be deleted if they already exist. Otherwise, this property **MUST** be set.

#### ***2.2.1.2.2 PidTagScheduleInfoFreeBusyTentative***

A **PtypMultipleBinary** property that specifies the blocks of times for which the **free/busy status** is **Tentative**. This property has as many values as the number of values in **PidTagScheduleInfoMonthsTentative**. Each binary value represents a month and corresponds to the value at the same index in **PidTagScheduleInfoMonthsTentative**. The binary values are sorted in the same order as the values in **PidTagScheduleInfoMonthsTentative**.

Each binary value has one or more 4-**BYTE** blocks and each of them contains the start time in the first two bytes and end time in the second two bytes in **little-endian** format. The start time is the number of minutes between 12 AM **Coordinated Universal Time (UTC)** of the first day of the month and the start time of the event in UTC. The end time is the number of minutes between 12 AM UTC of the first day of the month and the end time of the event in UTC. The 4-**BYTE** blocks are sorted in ascending order.

Consecutive or overlapping blocks of time are merged into one block with start time as the start time of the first block and end time as the end time of the last block. If an event is spread across multiple months or years, the event is split into multiple blocks, one for each month. If there are no tentative events in the **publishing range**, then this **property** and **PidTagScheduleInfoMonthsTentative** **MUST NOT** be set or **MUST** be deleted if they already exist. Otherwise, this property **MUST** be set.

#### ***2.2.1.2.3 PidTagScheduleInfoMonthsBusy***

A **PtypMultipleInteger32** property that specifies the months for which **free/busy** data of type **Busy** is present in the **free/busy message**. The format, computation and constraints of this **property** are the same as those of **PidTagScheduleInfoMonthsTentative** but refer to **appointments** that are marked **busy** on the associated **calendar**.

#### ***2.2.1.2.4 PidTagScheduleInfoFreeBusyBusy***

A **PtypMultipleBinary** property that specifies the blocks of time for which the **free/busy status** is type **Busy**. The format, computation and constraints of this **property** are the same as those of **PidTagScheduleInfoFreeBusyTentative** but refer to **appointments** that are marked **Busy** on the associated **Calendar object**.

#### *2.2.1.2.5 PidTagScheduleInfoMonthsAway*

A **PtypMultipleInteger32** property that specifies the months for which **free/busy** data of type **OOF** is present in the **free/busy message**. The format, computation and constraints of this **property** are the same as those of **PidTagScheduleInfoMonthsTentative** but refer to **appointments** that are marked OOF on the associated **Calendar object**.

#### *2.2.1.2.6 PidTagScheduleInfoFreeBusyAway*

A **PtypMultipleBinary** property that specifies the times for which the **free/busy status** is set to **OOF**. The format, computation and constraints of this **property** are the same as those of **PidTagScheduleInfoFreeBusyTentative** but refer to **appointments** that are marked OOF on the associated **Calendar object**.

#### *2.2.1.2.7 PidTagScheduleInfoMonthsMerged*

A **PtypMultipleInteger32** property that specifies the months for which **free/busy** data of type **Busy** or **OOF** is present in the **free/busy message**. Events of free/busy type **Tentative** are not included in this **property**. The syntax/format and constraints of this property are the same as those of **PidTagScheduleInfoMonthsTentative** but refer to **appointments** that are marked OOF or Busy on the associated **Calendar object**.

#### *2.2.1.2.8 PidTagScheduleInfoFreeBusyMerged*

A **PtypMultipleBinary** property that specifies the times for which the **free/busy status** is set to **Busy** or **OOF**. Events of **free/busy** type **Tentative** are not included in this **property**. The format, computation and the restrictions of this property are the same as those of **PidTagScheduleInfoFreeBusyTentative** but refer to **appointments** that are marked OOF or Busy on the associated **Calendar object**.

#### *2.2.1.2.9 PidTagFreeBusyPublishStart*

A signed **PtypInteger32** property that specifies the start time of the **publishing range**. This value is expressed as the number of minutes since midnight, January 1, 1601 in **UTC**.

#### *2.2.1.2.10 PidTagFreeBusyPublishEnd*

A signed **PtypInteger32** property that specifies the end time of the **publishing range**. It is computed by adding the value of **PidTagFreeBusyCountMonths** to the start date of the publishing range. This value is expressed as the number of minutes since midnight, January 1, 1601 in **UTC**.

#### *2.2.1.2.11 PidTagFreeBusyRangeTimestamp*

A **PtypTime** property that specifies the time that the data was published, in **UTC**.

#### ***2.2.1.2.12 PidTagFreeBusyMessageEmailAddress***

A **PtypString** property that specifies the e-mail address of the user to whom this **free/busy message** applies. The value of this property is the same as the **PidTagEmailAddress** property value of the **Address Book object** for the **attendee** or **resource**.

#### **2.2.1.3 Delegate Information Properties**

The following properties are used in Delegate Access Configuration Protocol and Appointment and Meeting Object Protocol as defined in [MS-OXODLGT] and [MS-OXOCAL], respectively. These properties are optional on a **free/busy message**. If they are set on the **free/busy message**, the value of these properties **MUST** be equal to the value of the same **property** on the **Delegate Information object** as defined in [MS-OXOCAL].

- **PidTagScheduleInfoAutoAcceptAppointments**
- **PidTagScheduleInfoDisallowRecurringAppts**
- **PidTagScheduleInfoDisallowOverlappingAppts**
- **PidTagScheduleInfoDelegatorWantsCopy**
- **PidTagScheduleInfoDontMailDelegates**
- **PidTagScheduleInfoDelegatorWantsInfo**
- **PidTagFreeBusyCountMonths**

#### **2.2.1.4 Deprecated Properties**

##### ***2.2.1.4.1 PidTagGatewayNeedsToRefresh***

A **PtypBoolean** property. This **property** is deprecated and **SHOULD NOT** be used.<3>

##### ***2.2.1.4.2 PidTagScheduleInfoResourceType***

A signed **PtypInteger32** property that **MUST** be set to 0 when sending and ignored on receipt.<4>

##### ***2.2.1.4.3 PidTagScheduleInfoFreeBusy***

A **PtypBinary** property. This **property** is deprecated. It **SHOULD NOT** be set and **MUST** be ignored.<5>

### **2.2.2 Public Folder Free/Busy Related Properties**

#### **2.2.2.1 PidTagFreeBusyEntryIds**

A **PtypMultipleBinary** property. This property is set on the root **folder** and on the **Inbox special folder** of the local **store**. The value on the root folder of the local store **MUST** be equal to the value on the **Inbox special folder**. The property value contains the following 4 binary values:

- i) The first value **MUST** be set to NULL.
- ii) The second value **MUST** be set to the **EntryID** of the delegate information message. For more details about the delegate information message, see [MS-OXODLGT].
- iii) The third value **MAY** be set to the EntryID of the **free/busy message** of the logged in user. It **MUST** be set to NULL if the **free/busy public folder** is unavailable. This value is set when a client or server creates the **free/busy message** for the first time for a user.
- iv) The fourth value **MUST** be set to the EntryID of the folder whose **PidTagDisplayName** is equal to “FreeBusy Data” and is a child folder of the root folder of the store.

## 3 Protocol Details

### 3.1 Client Details

**Free/busy** data is kept in a specific **message** in the **public folders store**. There is one message for each user for whom free/busy data is published. This message is called **free/busy message**. It is contained in a **folder** representing the Administrative Group to which the user belongs. There is one folder for each Administrative Group in the organization. All these folders are descendants of the **special folder** “SCHEDULE+ FREE BUSY”. Each folder representing an Administrative Group is a sibling of the folders representing other Administrative Groups. An Administrative Group represents an “Organisational Unit”, within an organization, as specified in [RFC1279]. It is the *org-unit-rdn* component of the **distinguished name (DN)** of the **Address Book object** for the user, as defined in [MS-OXOABK] section 2.2.1.1.

A client **MAY** read or write free/busy data for another user. For more details about finding the free/busy message for a specific user, see section 3.1.4.1.2.

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

##### 3.1.1.1 Non-Persisted Free/Busy Related Properties

Some properties are not persisted on any object but are temporarily cached in memory or computed on demand. The free/busy related properties in this section are not persisted.

#### ***3.1.1.1.1 PidTagSchedulePlusFreeBusyEntryId***

A **PtypBinary** property that contains the **EntryID** of the **folder** named “SCHEDULE+ FREE BUSY” under the NON\_IPM\_SUBTREE of the **public folder store**. This **property** is not stored on any object but is computed on demand. The **folder ID (FID)** of “SCHEDULE+ FREE BUSY” is returned in response to **RopLogon**. The FID is preserved and used to compute the EntryID when it is needed.

#### **3.1.2 Timers**

None.

#### **3.1.3 Initialization**

None.

#### **3.1.4 Higher-Layer Triggered Events**

##### **3.1.4.1 Publishing Free/Busy Data**

The **free/busy** data SHOULD be published whenever **appointments** are created, deleted or when any of the following three properties of an appointment are modified – **PidLidAppointmentStartWhole**, **PidLidAppointmentEndWhole**, **PidLidBusyStatus**.

A client or server MAY keep a local copy of free/busy data and publish the changes periodically or immediately after the data changes.

The client MAY perform the following steps below to publish the data:

1. Determine the data to be published using the steps specified in section 3.1.4.1.1.
2. Find the **free/busy message** using the steps specified in section 3.1.4.1.2.
3. If the **message** does not exist, create a new message. Use step 2 to determine the **subfolder** and the subject of the message.
4. If the message was created, set the third binary value of the **PidTagFreeBusyEntryIds** property to the **EntryID** of the free/busy message. For more details about how to create a message, see [MS-OXCMSG].

##### ***3.1.4.1.1 Determining the Data Set for Publishing***

Data to be published is determined by finding all the calendar events that are in the **publishing range**. The publishing range is calculated as follows:

- **Start of range** is 12 AM UTC on the first day of the month or the first day of the week, whichever occurs earlier at the time of **publishing**.
- **End of range** is calculated by adding the value of **PidTagFreeBusyCountMonths** to start of range.

- All the **appointments** with an end time greater than the start of range and start time less than the end of range are considered to be in the publishing range.

#### 3.1.4.1.2 Finding the Free/Busy Message

The **free/busy messages** are stored in a descendant **folder** of the “SCHEDULE+ FREE BUSY” folder, under the NON\_IPM\_SUBTREE of the **public folders store**. There **MUST** be only one free/busy message for each user. A client can read or write **free/busy** data for users other than the logged on users. The client **MUST** find the free/busy message corresponding to the user before reading or writing information for that user. At the time of **publishing**, the client **MUST** determine whether a free/busy message already exists for the user in question before creating one.

The following steps **MAY** be used to locate the free/busy message corresponding to a given user:

- To find the free/busy message of the logged on user, get the **EntryID** of the free/busy message. The **EntryID** of the free/busy message is set in the third binary value of the **PidTagFreeBusyEntryIds** property for the Inbox. Use the **EntryID** of the free/busy message to generate the **message ID** of the message, as described in section 2.2.1.3.1 of [MS-OXCDATA]. Use the message ID of the message to open the **message**, as described in [MS-OXCMSG].
- To find the free/busy message of another user, use the name (full name or part of their name) and perform an **ambiguous name resolution (ANR)** to get their **Address Book object**, as specified in [MS-OXOABK] section 3.1.4.4.

If the **PidTagFreeBusyEntryIds** property does not exist or if the third binary value of this property is empty, or if free/busy message is being requested for another user, then the subject and the name of the sub-folder can be used to find the free/busy message as specified in sections 3.1.4.1.2.1 through 3.1.4.1.2.4.

##### 3.1.4.1.2.1 Determining the E-mail Address

Get the **Address Book object**:

1. If the client is **publishing** the data for the logged on user, find the **Address Book object** of the logged on user by matching its **EntryID** with the **PidTagMailboxOwnerEntryId** of the **store**.
2. If the client is publishing the data for another user, get the **Address Book object** by performing an **ANR** using the full name or partial name of the delegator. For details on how to resolve a name, see [MS-OXOABK] section 3.1.4.4.
3. Get the e-mail address from the **PidTagEmailAddress** property of the **Address Book object**.

#### **3.1.4.1.2.2 Determining the Name of the Appropriate Sub-Folder of the “SCHEDULE+ FREE BUSY” Folder**

1. Derive the name of the sub-**folder** by truncating the e-mail address up to, but not including, the first occurrence of “/cn”.
2. Prepend the string “EX:” to the value computed in step 1.
3. Find the folder using the name derived in the step 1. For details about how to find a folder by name, see [MS-OXCFOLD].

#### **3.1.4.1.2.3 Determining the Subject of the Appropriate Message**

1. Derive the subject by taking the sub-string that starts with the first occurrence of “/cn” in the e-mail address.
2. Prepend the string “USER-“ to the value computed in step 1.
3. Convert all the characters to upper-case.

#### **3.1.4.1.2.4 Finding the Message**

1. Derive the **folder** name and the subject of the **message** using the logic specified in section 3.1.4.1.2.2 and 3.1.4.1.2.3.
2. Open the “SCHEDULE + FREE BUSY” folder using **PidTagSchedulePlusFreeBusyEntryId** property.
3. Open the specific folder for this user using the name derived using steps in specified section 3.1.4.1.2.2.
  - Find the specific **message** for this user by finding the message in which **PidTagSubject** equals the subject derived using the steps specified in section 3.1.4.1.2.3. For more details on how to find a message that matches a subject, see [MS-OXCTABL] section 2.2.2.5.

### **3.1.5 Message Processing Events and Sequencing Rules**

None.

### **3.1.6 Timer Events**

None.

### **3.1.7 Other Local Events**

None.



## 4 Protocol Examples

### 4.1 Updating the Free/Busy Message

The following example describes how the **free/busy message** of a user is updated by the client after the user adds new appointments to their calendar.

Joe sets his **publishing** interval to 3 months.

Joe creates the following **appointments** on his **calendar**. All the events have a **free/busy status** type of **Busy**.

**Note** All times in this example are in Pacific Time.

Feb 2<sup>nd</sup>

Appointment time: 12 PM – 1 PM

Appointment time: 1 PM – 2 PM

April 2<sup>nd</sup>

Appointment time: 12 PM – 1 PM

Appointment time: 3 PM – 4 PM

The client publishes the availability information by using **RopCreateMessage** to create the **message** in the sub-**folder** for the Administrative Group of the user under the “SCHEDULE + FREE/BUSY” folder. The server returns a success code and a handle to a **Message object**.

Then the client uses **RopSetProperties** to transmit availability data to the server. The properties in the following table are sent.

Property	Property ID	Property Type	Value
<b>PidTagScheduleInfoResource Type</b>	0x6841	Signed <b>PtypInteger32</b>	0x00000000
<b>PidTagGatewayNeedsToRefresh</b>	0x6846	<b>PtypBoolean</b>	0x00000001
<b>PidTagNormalizedSubject</b>	0x0E1D	<b>PtypString</b>	USER- /CN=RECIPIENTS/CN

			=JOE
<b>PidTagScheduleInfoMonthsMerged</b>	0x684F	Signed <b>PtypMultipleInteger32</b>	See section 4.3 below.
<b>PidTagScheduleInfoFreeBusyMerged</b>	0x6850	<b>PtypMultipleBinary</b>	See section 4.5.
<b>PidTagScheduleInfoMonthsBusy</b>	0x6853	Signed <b>PtypMultipleInteger32</b>	See section 4.3.
<b>PidTagScheduleInfoFreeBusyBusy</b>	0x6854	Signed <b>PtypMultipleBinary</b>	See section 4.4.
<b>PidTagFreeBusyPublishStart</b>	0x6847	Signed <b>PtypInteger32</b>	214105440
<b>PidTagFreeBusyPublishEnd</b>	0x6848	Signed <b>PtypInteger32</b>	214234980
<b>PidTagFreeBusyRangeTimestamp</b>	0x6868	<b>PtypTime</b>	2008/02/22 01:13:00.000

Because there are no events with free/busy type of **Tentative** or **OOF**, the client does not set **PidTagScheduleInfoFreeBusyTentative**, **PidTagScheduleInfoMonthsTentative**, **PidTagScheduleInfoFreeBusyAway**, or **PidTagScheduleInfoMonthsAway**.

The client then uses **RopSaveChanges** to commit the properties on the server, and then **RopRelease** to release the **Message** object.

The values of some properties will change during the execution of **RopSaveChanges**, but the properties specified in this protocol will not change.

## 4.2 Finding Free/Busy Messages Using E-mail Addresses

The following example describes how to find the **free/busy message** of a user by using their e-mail address.

First, determine the **folder** name in which the free/busy message exists and determine the subject using the e-mail address of the user.

For example, a user who has a **PidTagEmailAddress** value of “/o=Adventure-Works/ou=New York/cn= Recipients/cn=David” would have his or her **free/busy** data

stored in the folder named “EX:/o=Adventure-Works/ou=New York” and in a **message** with subject equal to “USER-/CN=RECIPIENTS/CN=David”.

For examples of how to get the **Address Book object** of a user and the value of the **PidTagEmailAddress** property, see [MS-OXOABK].

The folder name and subject have now been determined.

The following is an example of the ROPs the client uses to find the **free/busy message**. David has one event in his **calendar** which starts on December 25<sup>th</sup>, 2007 at 7:10 PM and ends on Dec 25<sup>th</sup>, 2008 at 7:10 PM, Pacific Time.

#### **RopLogon Request**

**RopId:** 0xFE

**LogonId:** 0

**OutputHandleIndex:** 0 (HSOT=0xffffffff)

**LogonFlags:** 0x04 Replicated

**OpenFlags:** 0x00000406 PUBLIC HOME\_LOGON NO\_MAIL

**StoreState:** 0x00000000 <none>

**EssdnSize:** 0x00

**Essdn** <no mailbox>

#### **Response to RopLogon**

##### **RopLogon**

**RopId:** 0xFE

**OutputHandleIndex:** 0 (HSOT=0x00000017)

**ReturnValue:** ecNone (success) (0x00000000)

**LogonFlags:** 0x04 Replicated

Public **store**

**FolderArray:**

FolderID 1: 0001-000000000006 Root Folder  
FolderID 2: 0001-000000000001 IPM subtree  
FolderID 3: 0001-000000000002 Non-IPM subtree  
FolderID 4: 0001-000000000003 Eforms registry  
FolderID 5: 0001-000000000004  
FolderID 6: 0001-000000000005 Offline address book  
FolderID 7: 0000-000000000000 Local Eforms registry  
FolderID 8: 0003-000000000007 SCHEDULE+ FREEBUSY  
FolderID 9: 0004-000000000008 Local address book  
FolderID 10: 0000-000000000000 Article index  
FolderID 11: 0000-000000000000 Schedule  
FolderID 12: 0000-000000000000 <not used>  
FolderID 13: 0000-000000000000 <not used>

**ServerGUID:** a608eae8-6603-4509-89b3-6dac886dca4d

**PublicFolderPerUserGUID:** fbdd61f1-4863-4d07-902a-64d07f4ca88d

Open the folder named SCHEDULE+ FREEBUSY which has an ID of 0001-000000000004 as determined from above.

#### **RopOpenFolder** Request

**RopId:** 0x02

**LogonId:** 5

**InputHandleIndex:** 0 (HSOT=0x0000008c)

**FolderId:** 0001-000000000004

**OpenModeFlags:** 0x00 ReadOnly

Response to **RopOpenFolder** is omitted for readability and clarity.

To find the sub-folder that matches the name we determined earlier, the client sends the following ROP requests:

**RopGetHierarchyTable** Request

**RopId:** 0x04

**LogonId:** 5

**InputHandleIndex:** 0 (HSOT=0x0000008b)

**OutputHandleIndex:** 1 (HSOT=0xffffffff)

**TableFlags:** 0x00 Standard

The response to **RopGetHierarchyTable** has been omitted for readability and clarity.

**RopSetColumns** Request

**RopId:** 0x12

**LogonId:** 5

**InputHandleIndex:** 1 (HSOT=0xffffffff)

**SetColumnsFlag:** 0x00 Wait

**PropertyTagCount:** 3 (0x03)

**PropertyTags:** 0x67480014 **PidTagFolderId**

0x3001001F **PidTagDisplayName**

The response to **RopSetColumns** has been omitted for readability and clarity.

**RopFindRow** Request

**RopId:** 0x4F

**LogonId:** 5

**InputHandleIndex:** 1 (HSOT=0xffffffff)

**FindRowFlags:** 0x00 Direction: forward

**RestrictionDataSize:** 0x0078 (120)

**RestrictionData:**

**ConditionType:** 0x04 RES\_PROPERTY:

**RelationalOperator:** 0x04 RELOP\_EQ

0x3001001F **PidTagDisplayName** EX:/o=Adventure-Works/ou=New  
York

**Origin:** 0x00 BOOKMARK\_BEGINNING

**BookmarkSize:** 0x0000 (0)

Response to **RopFindRow**

**RopId:** 0x4F

**InputHandleIndex:** 1 (HSOT=0x00000039)

**ReturnValue:** ecNone (success) (0x00000000)

**RowNoLongerVisible:** 0x00 (FALSE)

**HasRowData:** 0x01 (TRUE)

**RowData:**

HasError: 0

PropertyArray:

PropCount: 3

0x67480014 **PidTagFolderId** 0x0700000000000000

0x3001001F **PidTagDisplayName** EX:/o=Adventure-  
Works/ou=New York

Now that the folder has been found, and the **FID** was retrieved using **RopFindRow**, open the folder.

**RopOpenFolder** Request

**RopId:** 0x02

**LogonId:** 5

**InputHandleIndex:** 0 (HSOT=0x0000008c)

**FolderId:** 0003-000000000007

**OpenModeFlags:** 0x00 ReadOnly

The response to **RopOpenFolder** has been omitted for readability and clarity.

#### **RopGetContentsTable** Request

**RopId:** 0x05

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000023)

**OutputHandleTable:** 1 (HSOT=0xffffffff)

**TableFlags:** 0x00 Standard

#### **RopSetColumns** Request

**RopId:** 0x12

**LogonId:** 0

**InputHandleIndex:** 1 (HSOT=0xffffffff)

**SetColumnFlags:** 0x00 Wait

**PropertyTagCount:** 5 (0x05)

**PropertyTags:** 0x67480014 **PidTagFolderId**

0x674A0014 **PidTagMid**

0x674D0014 **PidTagInstID**

0x674E0003 **PidTagInstanceNum**

0x0E1D001F **PidTagNormalizedSubject**

#### **RopSortTable** Request

**RopId:** 0x13

**LogonId:** 0

**InputHandleIndex:** 1 (HSOT=0xffffffff)

**SortTableFlags:** 0x00 Wait

**SortOrderCount:** 0x0001 (1)

**CategoryCount:** 0x0000 (0)

**ExpandedCount:** 0x0000 (0)

**PropertyTag:**

0x0E1D001F **PidTagNormalizedSubject**

**SortOrders:** 0x00 Flag: TABLE\_SORT\_ASCEND

#### **RopFindRow Request**

**RopId:** 0x4F

**LogonId:** 0

**InputHandleIndex:** 1 (HSOT=0xffffffff)

**FindRowFlags:** 0x00 Direction: forward

**RestrictionDataSize:** 0x0054 (84)

**RestrictionData:**

**ConditionType:** 0x04 RES\_PROPERTY:

**RelationalOperator:** 0x04 RELOP\_EQ

0x0E1D001F **PidTagNormalizedSubject** USER-  
/CN=RECIPIENTS/CN=DAVID

**Origin:** 0x00 BOOKMARK\_BEGINNING

**BookmarkSize:** 0x0000 (0)

#### **Response to RopGetContentsTable**



**RopId:** 0x05

**OutputHandleIndex:** 1 (HSOT=0x00000022)

**ReturnValue:** ecNone (success) (0x00000000)

**RowCount:** 113

Response to **RopSetColumns**

**RopId:** 0x12

**InputHandleIndex:** 1 (HSOT=0x00000022)

**ReturnValue:** ecNone (success) (0x00000000)

**TableStatus:** TBLSTAT\_COMPLETE (0x00)

Response to **RopSortTable**

**RopId:** 0x13

**InputHandleIndex:** 1 (HSOT=0x00000022)

**ReturnValue:** ecNone (success) (0x00000000)

**TableStatus:** TBLSTAT\_COMPLETE (0x00)

Response to **RopFindRow**

**RopId:** 0x4F

**InputHandleIndex:** 1 (HSOT=0x00000022)

**ReturnValue:** NotFound (0x8004010f)

The message is not found, so create it:

**RopCreateMessage** Request

**RopId:** 0x06

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000023)

**OutputHandleIndex:** 1 (HSOT=0xffffffff)

**CodePageId:** 0x0FFF (4095)

**FolderId:** 0003-000000000007

**AssociatedFlag:** 0x00

Response to **RopCreateMessage**

**RopId:** 0x06

**OutputHandleIndex:** 1 (HSOT=0x00000020)

**ReturnValue:** ecNone (success) (0x00000000)

**HasMessageId:** 0

Now set the properties:

**RopSetProperties** Request

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x000F (15)

**PropertyValueCount:** 2 (0x02)

**PropertyValues:** 0x68410003 **PidTagScheduleInfoResourceType**  
0x00000000 (0)

0x6846000B **PidTagGatewayNeedsToRefresh** 0x0001 (TRUE)

**RopSetProperties** Request

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x0156 (342)

**PropertyValueCount:** 7 (0x07)

**PropertyValues:** 0x68410003 **PidTagScheduleInfoResourceType**

0x6842000B **PidTagScheduleInfoDelegatorWantsCopy** 0x0001  
(TRUE)

0x6843000B **PidTagScheduleInfoDontMailDelegates** 0x0001 (TRUE)

0x686D000B **PidTagScheduleInfoAutoAcceptAppointments** 0x0000  
(FALSE)

0x686E000B **PidTagScheduleInfoDisallowRecurringAppts** 0x0000  
(FALSE)

0x686F000B **PidTagScheduleInfoDisallowOverlappingAppts** 0x0000  
(FALSE)

0x684B000B **PidTagScheduleInfoDelegatorWantsInfo** 0x0001 (TRUE)

#### **RopSetProperties** Request

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x0056 (86)

**PropertyValueCount:** 2 (0x02)

**PropertyValues:** 0x003D001F **PidTagSubjectPrefix** (null)

0x0E1D001F **PidTagNormalizedSubject** USER-  
/CN=RECIPIENTS/CN=DAVID

#### **RopSaveChangesMessage** Request

**RopId:** 0x0C

**LogonId:** 0

**ResponseHandleIndex:** 1 (HSOT=0x00000023)

**InputHandleIndex:** 0 (HSOT=0x00000020)

**SaveFlags:** 0x0A KeepOpenReadWrite DelayedCall

Response to **RopSaveChangesMessage:**

**RopSaveChangesMessage**

**RopId:** 0x0C

**ResponseHandleIndex:** 1 (HSOT=0x00000023)

**ReturnValue:** ecNone (success) (0x00000000)

**InputHandleIndex:** 0 (HSOT=0x00000020)

**MessageID:** 0001-0000000051e3

**RopSetProperties Request**

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 2 (HSOT=0x00000020)

**PropertyValueSize:** 0x00AC (172)

**PropertyValueCount:** 1 (0x01)

**PropertyValues:** 0x6849001F **PidTagFreeBusyMessageEmailAddress**  
/o=Adventure-Works/ou=New York/cn=Recipients/cn=David

**RopSetProperties Request**

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x0026 (38)

**PropertyValueCount:** 2 (0x02)

**PropertyValues:** 0x684F1003 **PidTagScheduleInfoMonthsMerged**

**PtypMultipleInteger32[0]:** 32130

**PtypMultipleInteger32[1]: 32131**

**0x68501102 PidTagScheduleInfoFreeBusyMerged**

**PtypMultipleBinary[0] (4 bytes):**

0000: E0 01 20 A3

**PtypMultipleBinary[1] (4 bytes):**

0000: 00 00 E0 01

**RopDeletePropertiesNoReplicate Request**

**RopId: 0x7A**

**LogonId: 0**

**InputHandleIndex: 0 (HSOT=0x00000020)**

**PropertyTagCount: 2 (0x02)**

**PropertyTags: 0x68511003 PidTagScheduleInfoMonthsTentative**

**0x68521102 PidTagScheduleInfoFreeBusyTentative**

**RopSetProperties Request**

**RopId: 0x0A**

**LogonId: 0**

**InputHandleIndex: 0 (HSOT=0x00000020)**

**PropertyValueSize: 0x0026 (38)**

**PropertyValueCount: 2 (0x02)**

**PropertyValues: 0x68531003 PidTagScheduleInfoMonthsBusy**

**PtypMultipleInteger32[0]: 32130**

**PtypMultipleInteger32[1]: 32131**

**0x68541102 PidTagScheduleInfoFreeBusyBusy**

**PtypMultipleBinary [0] (4 bytes):**

0000: E0 01 20 A3

**PtypMultipleBinary [1] (4 bytes):**

0000: 00 00 E0 01

**RopSetProperties Request**

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x0007 (7)

**PropertyValueCount:** 1 (0x01)

**PropertyValues:** 0x6846000B **PidTagGatewayNeedsToRefresh** 0x0001  
(TRUE)

**RopSetProperties Request**

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x000A (10)

**PropertyValueCount:** 1 (0x01)

**PropertyValues:** 0x68470003 **PidTagFreeBusyPublishStart**  
**PtypInteger32** 0x0CC2FD60 (214105440)

**RopSetProperties Request**

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x000A (10)

**PropertyValueCount:** 1 (0x01)

**PropertyValues:** 0x68480003 **PidTagFreeBusyPublishEnd** 0x0CC3A080  
(214147200)

#### **RopSetProperties** Request

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x000E (14)

**PropertyValueCount:** 1 (0x01)

**PropertyValues:** 0x68680040 **PidTagFreeBusyRangeTimestamp**

High: 0x01C87A68

Low: 0x430A6000 (2008/02/29 00:16:00.000)

#### **RopSetProperties** Request

**RopId:** 0x0A

**LogonId:** 0

**InputHandleIndex:** 0 (HSOT=0x00000020)

**PropertyValueSize:** 0x000A (10)

**PropertyValueCount:** 1 (0x01)

**PropertyValues:** 0x68410003 **PidTagScheduleInfoResourceType** 0x00000000  
(0)

#### **RopSaveChangesMessage** Request

**RopId:** 0x0C

**LogonId:** 0

**ResponseHandleIndex:** 1 (HSOT=0x00000023)

**InputHandleIndex:** 0 (HSOT=0x00000020)

**SaveFlags:** 0x08 DelayedCall

Response to **RopSaveChangesMessage:**

**RopSaveChangesMessage**

**RopId:** 0x0C

**ResponseHandleIndex:** 1 (HSOT=0x00000023)

**ReturnValue:** ecNone (success) (0x00000000)

**InputHandleIndex:** 0 (HSOT=0x00000020)

**MessageID:** 0001-0000000051e3

The client then calls **ROPRelease** on all open folders and the newly created message.

### **4.3 PidTagScheduleInfoMonthsBusy Calculation**

The **PidTagScheduleInfoMonthsBusy** property is calculated by using the following equations:

1.  $(Year \times 16) + month$
2. *Convert result of equation 1 to hexadecimal*

Consider the following example:

**Free/busy** range is 3 months from the time of **publishing**. The time of publishing is 12 AM on Feb 25<sup>th</sup> UTC. There is at least one **calendar** item with free/busy type of **Busy** in the months of February, March, and April.

So, we will publish data in the months of February, March, April and May. More specifically,

Feb 25<sup>th</sup> 12 AM to Feb 29<sup>th</sup> 11:59 PM

March 1<sup>st</sup> 12 AM to March 31<sup>st</sup> 11:59 PM

April 1<sup>st</sup> 12 AM to April 30<sup>th</sup> 11:59 PM

May 1<sup>st</sup> 12 AM to May 25<sup>th</sup> 12 AM



All the times above are in UTC. The property value is determined by using the following calculations.

#### For February

Year = 2008

Month = February = 2

$(2008 * 16) + 2 = 32130$

32130 converted to hexadecimal = 7d82

#### For March

Year = 2008

Month = March = 3

$(2008 * 16) + 3 = 32131$

32131 converted to hexadecimal = 7d83

#### For April

Year = 2008

Month = April = 4

$(2008 * 16) + 4 = 32132$

32132 converted to hexadecimal = 7d84

So the **PtypMultipleInteger32** will have 3 values with 0x00007D82, 0x00007D83, 0x00007D84 in each of the LONG values. Because the month of May did not have any events, there will not be a value representing May. Otherwise, there would have been 4 values.

If the month of March, for example, did not have any **calendar** items with free/busy type of **Busy**, then there would be only two values.

#### 4.4 *PidTagScheduleInfoFreeBusyBusy Calculation*

The **PidTagScheduleInfoFreeBusyBusy** property is calculated by using the following equations:

- Start time is the number of minutes between midnight on the first day of the month and the start time of the event in hexadecimal.

*Number of days before the scheduled date in that particular month × 24 (hours/day) \* 60 (minutes/hour) + (hour of start time on a 24-hour clock adjusted for UTC) \* 60 (minutes/hour) = Text value of start time in minutes*

**Note:** Each time zone requires a different adjustment for UTC.

- End time is the number of minutes between midnight on the first day of the month and the end time of the event in hexadecimal.

For example, assume there is only one event with a free/busy status of **Busy** that occurs during the months of February, March, April and May. It occurs between noon and 1 P.M Pacific Time on February 2nd. The **publishing** interval is 3 months. The time of publishing is 12 AM on Feb 25<sup>th</sup> UTC.

The value is determined by using the following calculations.

Start time
<i>Number of days before the scheduled date in that particular month = 1</i>
<i>Start hour = noon = 12 on a 24-hour clock + 8 for UTC conversion = 20</i>
<b>Note:</b>
+8 is the difference between UTC and Pacific Time Zone. The adjustment is different for each time zone.
<i>Start time in minutes = (1 * 60 * 24) + (20 * 60) = 1440 + 1200 = 2640</i>
<i>Hexadecimal start time = 0A50</i>

End time
<i>Number of days before the scheduled date in that particular month = 1</i>
<i>End hour = 1 PM Pacific Time = 13 on a 24-hour clock + 8 for UTC conversion = 21</i>

End time
<p><b>Note:</b></p> <p>+8 is the difference between UTC and Pacific Time Zone. The adjustment is different for each time zone.</p> <p><i>End time in minutes = (1 * 60 * 24) + (21 * 60) = 1440 + 1260 = 2700</i></p> <p><i>Hexadecimal end time = 0A8C</i></p>

**Note:** In some cases, the UTC conversion changes the date of the start time or end time.

The Multi-value binary will have one binary value. The binary value will have the following 4 bytes, encoded in little-endian; the first two bytes for the start time and the second two bytes for the end time: 0x50, 0x0A, 0x8C, 0x50.

#### 4.4.1 PidTagScheduleInfoFreeBusyBusy Calculation with Two Non-Consecutive Events

Assume there are two events with free/busy status of **Busy**, in the month of February.

February 2nd (times are in Pacific Time)

Appointment time: 12 PM to 1 PM

Appointment time: 3PM to 4PM

The **PtypMultipleBinary** will have one binary value. The binary value will have the following 8 bytes. 0x50, 0x0A, 0x8C, 0x0A, 0x04, 0x0B, 0x40, 0x0B.

#### 4.4.2 PidTagScheduleInfoFreeBusyBusy Calculation with Two Consecutive Events

If there are two consecutive events with the same **free/busy status**, the two times are merged together. For example, assume the following two events are of type **Busy**.

February 2<sup>nd</sup> (times are in Pacific Time)

Appointment time: 12 P.M. to 1 P.M.

Appointment time: 1P.M. to 2 P.M.

There will be only one block with a start time of 12 PM and an end time of 2 PM. The **PtypMultipleBinary** will have one binary value. The binary value will have the following 4 bytes: 0x50, 0x0A, 0xC8, 0x0A.

#### 4.4.3 PidTagScheduleInfoFreeBusyBusy Calculation with Events in Multiple Months

Assume there are two events of type **Busy** in the month of February and two events in the month of April. There are no events in March.

February 2<sup>nd</sup> (times are in Pacific Time)

Appointment time: 12 P.M. to 1 P.M.

Appointment time: 1 P.M. to 2 P.M.

April 2<sup>nd</sup>

Appointment time: 12 P.M. to 1 P.M.

Appointment time: 3 P.M. to 4 P.M.

The **PtypMultipleBinary** will have two binary values.

The first binary value will have the following 4 bytes: 0x50, 0x0A, 0xC8, 0x0A

The second binary value will have the following 8 bytes: 0x14, 0x0A, 0x50, 0x0A, 0xC8, 0x0A, 0x04, 0x0B.

Note that the time difference between **UTC** and **PST** in April is +7 hours and hence the values are calculated by adding 7 hours to the **PST** time.

#### 4.4.4 PidTagScheduleInfoFreeBusyBusy Calculation When an Event is Spread Across Multiple Months

Consider an example where an event starts on Dec 25<sup>th</sup> 2007, 9 AM and ends on Dec 25<sup>th</sup> 2008, 10 AM. This event is considered as a series of events that start and end as follows:

Dec 25<sup>th</sup> 2007, 9 A.M. - Dec 31<sup>st</sup> 2007, 12:00 A.M.

Jan 1<sup>st</sup> 2008, 12:00 A.M. - Jan 31<sup>st</sup> 2008, 12:00 A.M.

....

....

Dec 1<sup>st</sup> 2008, 12:00 A.M. – Dec 25<sup>th</sup>, 10:00 A.M.

The values are calculated as specified in the examples in sections 4.4.1 through 4.4.3.

If the **publishing** interval is 12 months and the time of publishing is 12 AM Dec 25<sup>th</sup>, 2007 **UTC** then there would be 13 binary values in both **PidTagScheduleInfoMonthsBusy** and **PidTagScheduleInfoFreeBusyBusy** properties; one for Dec 2007 and one for each month in 2008.

If the publishing interval is 12 months and the time of publishing is 12 A.M. Feb 25, 2007, **UTC**, then there would be 11 binary values.

If the publishing interval is 1 month and the time of publishing is 12 A.M. Feb 25, 2007, UTC, then there would be 2 binary values, for the months of Feb and March.

#### ***4.5 PidTagScheduleInfoFreeBusyMerged Calculation***

The **PidTagScheduleInfoFreeBusyMerged** property includes events of type **Busy** and **OOF**. For example, if a user has an event from 1 PM to 2 PM of type Busy and another from 4 PM to 5 PM of type OOF, then **PidTagScheduleInfoFreeBusyMerged** will contain two binary values.

If there are consecutive or overlapping scheduled events of type Busy and OOF, they will be merged into one block. For example, if a user has an event from 1 PM to 2 PM, of type Busy and another from 1:30 PM to 3 PM, of type OOF, the **PidTagScheduleInfoFreeBusyMerged** property will contain one binary value with start time of 1 PM and an end time of 3 PM.

## **5 Security**

### ***5.1 Security Considerations for Implementers***

There are no special security considerations specific to this protocol. General security considerations pertaining to the underlying [MS-OXOMSG] protocol apply.

### ***5.2 Index of Security Parameters***

None.

## **6 Appendix A: Office/Exchange Behavior**

The information in this specification is applicable to the following versions of Office/Exchange:

- Office 2003 with Service Pack 3 applied
- Exchange 2003 with Service Pack 2 applied
- Office 2007 with Service Pack 1 applied
- Exchange 2007 with Service Pack 1 applied

Exceptions, if any, are noted below. Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies Office/Exchange behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies Office/Exchange does not follow the prescription.

---

<1> Section 1.5: Public folders are supported by default by Exchange Server 2003 SP2. Public folders MAY have to be configured explicitly on an Exchange 2007 SP1 server.

<2 > Section 1.6: Exchange 2003 SP2 does not support the Availability Service.

<3> Section 2.2.1.4.1: Outlook 2003 SP3 and Outlook 2007 SP1 will set **PidTagGatewayNeedsToRefresh** to 1. This property is not read by Outlook 2003 SP3, Outlook 2007 SP1, Exchange 2003 SP2, or Exchange 2007 SP1.

<4> Section 2.2.1.4.2: The **PidTagSchdInfoResourceType** from the **free/busy message** is read from and written to by Outlook 2003 SP3 and Outlook 2007 SP1, but the value is not used.

<5> Section 2.2.1.4.3: The **PidTagSchdinfoFreebusy** property MAY be set on the **Delegate Info object** by lower-level versions of Outlook 2003 SP3. This property is deprecated and MUST not be read from or written to.

## Index

### Appendix A

Office/Exchange behavior, 37

### Introduction, 5

Applicability statement, 8

Glossary, 5

Prerequisites/Preconditions, 8

Protocol Overview, 8

References, 7

Relationship to other protocols, 8

Standards assignments, 9

Vendor-extensible fields, 9

Versioning and capability statement, 8

### Messages, 9

Message syntax, 9

Transport, 9

### Protocol details, 13

Client details, 13

### Protocol examples, 17

Finding free/busy messages using e-mail addresses, 18

Free/Busy message, 17

PidTagScheduleInfoFreeBusyBusy calculation, 33

PidTagScheduleInfoFreeBusyMerged calculation, 37

PidTagScheduleInfoMonthsBusy calculation, 32

### References

Informative references, 8

Normative references, 7

### Security, 37

Index of security parameters, 37

Security considerations for implementers, 37