

[MS-OXORMDR]: Reminder Settings Protocol Specification

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.msp>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplq@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Revised and edited technical content.
09/03/2008	1.02		Updated references.
12/03/2008	1.03		Updated IP notice.
04/10/2009	2.0		Updated technical content for new product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	4.1.0	Minor	Updated the technical content.
05/05/2010	4.2.0	Minor	Updated the technical content.
08/04/2010	4.3	Minor	Clarified the meaning of the technical content.
11/03/2010	4.4	Minor	Clarified the meaning of the technical content.
03/18/2011	4.4	No change	No changes to the meaning, language, and formatting of the technical content.
08/05/2011	4.5	Minor	Clarified the meaning of the technical content.
10/07/2011	4.5	No change	No changes to the meaning, language, or formatting of the technical content.

Table of Contents

1	Introduction	5
1.1	Glossary	5
1.2	References.....	6
1.2.1	Normative References.....	6
1.2.2	Informative References	7
1.3	Overview	7
1.3.1	Creating, Modifying, and Removing Reminders.....	7
1.3.2	Processing Overdue Reminders	7
1.3.3	Dismissing and Snoozing Reminders	7
1.4	Relationship to Other Protocols.....	7
1.5	Prerequisites/Preconditions	8
1.6	Applicability Statement.....	8
1.7	Versioning and Capability Negotiation.....	8
1.8	Vendor-Extensible Fields.....	8
1.9	Standards Assignments	8
2	Messages.....	9
2.1	Transport.....	9
2.2	Message Syntax	9
2.2.1	Properties Used to Specify and/or Decode Reminders	9
2.2.1.1	PidLidReminderSet Property	9
2.2.1.2	PidLidReminderSignalTime Property	9
2.2.1.3	PidLidReminderDelta Property	10
2.2.1.4	PidLidReminderTime Property.....	10
2.2.1.5	PidLidReminderOverride Property	10
2.2.1.6	PidLidReminderPlaySound Property	10
2.2.1.7	PidLidReminderFileParameter Property	10
2.2.1.8	PidTagReplyTime Property	10
2.2.1.9	PidLidReminderType Property	11
2.2.2	Shared Properties.....	11
2.2.2.1	Properties Shared with the Message and Attachment Object Protocol	11
2.2.2.2	Properties Shared with the Informational Flagging Protocol.....	11
2.2.2.3	Properties Shared with the Task-Related Objects Protocol.....	11
2.2.2.3.1	PidLidTaskDueDate Property	11
2.2.2.4	Properties Shared with the Appointment and Meeting Object Protocol	12
2.2.3	Properties Used to Specify User Preferences that are Roamed on the Server.....	12
2.2.3.1	piReminderUpgradeTime Property.....	12
3	Protocol Details.....	13
3.1	Client and Server Details	13
3.1.1	Abstract Data Model	13
3.1.2	Timers	13
3.1.3	Initialization	14
3.1.3.1	Populating the Reminder Queue	14
3.1.3.1.1	Scope	14
3.1.3.1.1.1	Requirements for Clients Using a Full Reminder Domain	14
3.1.3.1.2	Loading/Processing.....	14
3.1.4	Higher-Layer Triggered Events.....	14
3.1.4.1	Setting a Reminder	14
3.1.4.1.1	Reminders on Task Objects	14

3.1.4.1.2	Reminders on Neither Calendar nor Task Objects	14
3.1.4.1.3	Reminders on Calendar Objects	15
3.1.4.1.4	Reminders on Recurring Calendar Objects	15
3.1.4.1.5	Setting Reminders on Draft Message Objects	16
3.1.4.1.5.1	Setting a Reminder for all Recipients	16
3.1.4.1.5.2	Setting a Reminder for the Sender	16
3.1.4.2	Post-Transmit Processing	16
3.1.4.3	Post-Receive Processing	16
3.1.4.4	Removing a Reminder	16
3.1.4.4.1	Single Instance Objects	16
3.1.4.4.2	Recurring Calendar Objects	17
3.1.4.4.3	Recurring Task Objects	17
3.1.4.5	When a Reminder Becomes Overdue	17
3.1.4.5.1	Reminders That Are Ignored When They Become Overdue	17
3.1.4.5.2	Reminders That Are Auto-Dismissed When Overdue	18
3.1.4.5.3	Actions for Overdue Reminders That Are Not Ignored or Auto-Dismissed....	18
3.1.4.5.3.1	Starting a Conference	19
3.1.4.6	Dismissing a Reminder	19
3.1.4.6.1	Dismissing for Single Instance Objects	19
3.1.4.6.2	Dismissing for Recurring Calendar Objects	19
3.1.4.6.3	Dismissing for Recurring Task Objects	19
3.1.4.7	Snoozing a Reminder	20
3.1.4.7.1	Snoozing for Single Instance Objects	20
3.1.4.7.2	Snoozing for Recurring Objects	20
3.1.4.8	Generating Instances for Recurring Task Objects	20
3.1.5	Message Processing Events and Sequencing Rules	20
3.1.6	Timer Events	20
3.1.7	Other Local Events	20
4	Protocol Examples	21
4.1	Set a Reminder on a Single Instance Appointment	22
4.2	Set a Reminder on a Message Object	23
4.3	Dismiss a Reminder on a Task	24
4.4	Dismiss a Reminder on a Recurring Calendar Object	25
4.5	Snooze a Reminder on a Contact Object	27
4.6	Remove a Reminder From an Instance of a Recurring Calendar Object	28
5	Security	34
5.1	Security Considerations for Implementers	34
5.2	Index of Security Parameters	34
6	Appendix A: Product Behavior	35
7	Change Tracking	39
8	Index	40

1 Introduction

This document specifies a protocol for discovering and acting upon **Message objects** that have a deadline. This includes upcoming (or past) appointments, tasks, messages, or **contacts** for which follow-up is necessary, or any other Message object for which the properties specified in this document have been set.

The Reminder Settings Protocol specifies the following:

- Methods by which a client can add, remove, or modify **reminders** on a Message object.
- Methods by which a client can **dismiss** or **snooze** a reminder.
- Details that allow the client to process **overdue reminders**.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

Coordinated Universal Time (UTC) handle

The following terms are defined in [\[MS-OXGLOS\]](#):

active reminder
Calendar object
calendar options dictionary
contact
Draft Message object
Exception Attachment object
Exception Embedded Message object
instance
mailbox
meeting-related object
Message object
named property
recipient
recurrence BLOB
recurrence pattern
Recurring Calendar object
recurring series
recurring task
reminder
reminder properties
search folder
signal time
special folder
store
Task object

The following terms are specific to this document:

dismiss: A process that disables an overdue reminder. After a reminder is dismissed, it is not considered overdue anymore and is not signaled or displayed to a user or any agents who are acting on behalf of that user.

due time: The time after which a user is considered late, such as the start time of an appointment or the time at which a work item is expected to be complete.

full reminder domain: The maximum scope that a client is allowed to use when searching for objects that have reminders enabled. The full reminder domain includes all folders except the following: Deleted Items, Junk E-mail, Drafts, Outbox, Conflicts, Local Failures, Server Failures, and Sync Issues.

minimal reminder domain: The smallest scope that a client is allowed to use when searching for objects that have an active reminder. The minimal reminder domain includes the following folders: Inbox, primary Contacts, primary Calendar, and primary Tasks. It does not include sub-folders.

overdue reminder: An active reminder whose signal time has passed.

Recurring object: An object that is a Recurring Calendar object or a Recurring Task object.

Recurring Task object: A Task object that represents a recurring task.

reminder domain: A set of folders that are searched for objects that have an active reminder.

reminder queue: A sorted list of objects that are in a reminder domain and have been stamped with properties implying that they could have an active reminder.

snooze: A process that delays an overdue reminder by a specified time interval. At the end of the time interval, the reminder becomes overdue again.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)".

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)".

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol Specification](#)".

[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol Specification](#)".

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)".

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol Specification](#)".

[MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol Specification](#)".

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol Specification](#)".

[MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol Specification](#)".

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol Specification](#)".

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol Specification](#)".

1.3 Overview

This protocol allows the user or an agent who is acting on behalf of the user to associate a reminder with a given Message object with the intention that a client will somehow signal the user or agent when the **signal time** is reached.

1.3.1 Creating, Modifying, and Removing Reminders

The client creates, modifies, or removes reminders by setting **reminder properties** on objects, as specified in section [3.1.4](#). The client can specify such things as when to signal a reminder, the **due time** for the object about which the user is to be reminded, whether to play a sound when the reminder is signaled, which sound to play, and whether the reminder is enabled. On a **Draft Message object**, reminders for the **recipient** or recipients can be specified independently from those for the sender.

1.3.2 Processing Overdue Reminders

The client processes overdue reminders, as specified in section [3.1.4.5](#). Before signaling an overdue reminder, the client is responsible for deciding which reminders to ignore and which reminders to automatically dismiss.

1.3.3 Dismissing and Snoozing Reminders

The client can dismiss or snooze overdue reminders, as specified in section [3.1.4.6](#) and section [3.1.4.7](#).

1.4 Relationship to Other Protocols

The Reminder Setting Protocol extends the Message and Attachment Object Protocol and relies on an understanding of how to work with folders, messages, and tables. For details, see [\[MS-](#)

[OXCDATA](#), [\[MS-OXPROPS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOTASK\]](#), and [\[MS-OXOFLAG\]](#).

1.5 Prerequisites/Preconditions

For requesting and configuring reminders, the Reminder Settings Protocol assumes that the client has previously logged on to the server and has acquired a **handle** to the object for which it intends to create or update reminder properties, as specified in [\[MS-OXCFOLD\]](#) and [\[MS-OXCMSG\]](#).

For discovering Message objects that have reminders, the Reminder Settings Protocol assumes that the client has previously logged on to the server and has acquired a handle to the **mailbox store** in which it intends to search, as specified in [\[MS-OXCSTOR\]](#).

1.6 Applicability Statement

The Reminder Settings Protocol is used to specify and raise time-specific notifications to a user or an agent who is acting on behalf of a user.

1.7 Versioning and Capability Negotiation

None.

1.8 Vendor-Extensible Fields

This protocol provides no vendor extensibility beyond what is already specified in [\[MS-OXCMSG\]](#).

1.9 Standards Assignments

None.

2 Messages

2.1 Transport

This protocol uses the transport specified in [\[MS-OXCMMSG\]](#).

2.2 Message Syntax

Reminders can be created and modified, on any type of Message object, by clients and servers. Except where noted, this section defines constraints to which both clients and servers adhere when operating on the reminder properties of Message objects.

Clients operate on the reminder properties of Message objects by using the Message and Attachment Object Protocol, as specified in [\[MS-OXCMMSG\]](#). How a server operates on the reminder properties of Message objects is implementation-dependent. The results of any such operation are exposed to clients in a manner that is consistent with the Reminder Settings Protocol.

2.2.1 Properties Used to Specify and/or Decode Reminders

The following properties are used to specify the reminder for a given object. These properties are set by the client to ensure that the user is notified in the manner and at the time that is preferred.

2.2.1.1 PidLidReminderSet Property

Type: **PtypBoolean** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidReminderSet** property ([\[MS-OXPROPS\]](#) section 2.216) specifies whether a reminder is set on the object.

If a **Recurring Calendar object** has the **PidLidReminderSet** property set to **TRUE**, the client can override this value for exceptions. See the definition of **PidLidAppointmentRecur** in [\[MS-OXOCAL\]](#) section 2.2.1.44 for details.

If the **PidLidReminderSet** property is **FALSE** on a Recurring Calendar object, reminders are disabled for the entire series, including exceptions.

For **Recurring Task objects**, the **PidLidReminderSet** property cannot be overridden by exceptions (see [\[MS-OXOCAL\]](#) and [\[MS-OXOTASK\]](#) for details).

2.2.1.2 PidLidReminderSignalTime Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidReminderSignalTime** property ([\[MS-OXPROPS\]](#) section 2.217) specifies the point in time when a reminder transitions from pending to overdue. This property MUST be set if the **PidLidReminderSet** property (section [2.2.1.1](#)) is **TRUE**. Clients MUST set the value in **Coordinated Universal Time (UTC)**.

This property is not overridden by exceptions; there is a single signal time per Recurring Calendar object.

The value of this property is not interpreted strictly as **UTC**. For details, see [\[MS-OXOCAL\]](#) section 3.1.5.5.

2.2.1.3 PidLidReminderDelta Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidReminderDelta** property ([\[MS-OXPROPS\]](#) section 2.212) MUST be set on **Calendar objects** and specifies the interval, in minutes, between the time at which the reminder first becomes overdue and the start time of the Calendar object. For all non-Calendar objects, this property SHOULD be set to 0x00000000 and is ignored.

When a reminder is dismissed for one instance of a Recurring Calendar object, the value of this property is used in the calculation of the signal time for the next instance. See [\[MS-OXOCAL\]](#) for details about Calendar object creation.

2.2.1.4 PidLidReminderTime Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

For non-Calendar objects, the **PidLidReminderTime** property ([\[MS-OXPROPS\]](#) section 2.218) specifies the initial signal time. For Calendar objects, this property represents the time after which the user would be late; that is, the start time of the appointment. Clients MUST set the value in UTC.

2.2.1.5 PidLidReminderOverride Property

Type: **PtypBoolean** ([\[MS-OXCDATA\]](#) section 2.11.1)

If set to **TRUE**, the **PidLidReminderOverride** property ([\[MS-OXPROPS\]](#) section 2.214) specifies that the client SHOULD [<1>](#) respect the values of the **PidLidReminderPlaySound** property (section [2.2.1.6](#)) and the **PidLidReminderFileParameter** property (section [2.2.1.7](#)). Otherwise, a client can use default values in place of the values of the **PidLidReminderPlaySound** and **PidLidReminderFileParameter** properties.

2.2.1.6 PidLidReminderPlaySound Property

Type: **PtypBoolean** ([\[MS-OXCDATA\]](#) section 2.11.1)

If set to **TRUE**, the **PidLidReminderPlaySound** property ([\[MS-OXPROPS\]](#) section 2.215) specifies that the client SHOULD [<2>](#) play a sound when the reminder becomes overdue.

2.2.1.7 PidLidReminderFileParameter Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidReminderFileParameter** property ([\[MS-OXPROPS\]](#) section 2.213) SHOULD specify the full path (but MAY specify only the filename) of the sound [<3>](#) that a client SHOULD [<4>](#) play when the reminder for that object becomes overdue. If this property is not present, the client can use a default value.

2.2.1.8 PidTagReplyTime Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

Upon receipt of a Message object, the **PidTagReplyTime** property ([\[MS-OXOFLAG\]](#) section 2.2.3.1) specifies the due time that the sender wants, presumably for an associated work item, and is otherwise ignored. Clients MUST set the value in UTC. See [\[MS-OXOFLAG\]](#) for additional details.

2.2.1.9 PidLidReminderType Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidReminderType** property ([\[MS-OXPROPS\]](#) section 2.221) SHOULD NOT [<5>](#) be set, and MUST be ignored.

2.2.2 Shared Properties

These properties are set at reminder configuration time and/or processed and/or presented to the user (or an agent who is acting on behalf of the user) as described in the following sections.

2.2.2.1 Properties Shared with the Message and Attachment Object Protocol

The following properties are shared by this protocol and the Message and Attachment Object Protocol [\[MS-OXCMSG\]](#):

- **PidTagAttachDataObject** ([\[MS-OXCMSG\]](#) section 2.2.2.8)
- **PidTagMessageClass** ([\[MS-OXCMSG\]](#) section 2.2.1.3)
- **PidTagMessageFlags** ([\[MS-OXCMSG\]](#) section 2.2.1.6)

The semantics and accepted values are identical to those specified in [\[MS-OXCMSG\]](#).

2.2.2.2 Properties Shared with the Informational Flagging Protocol

The following properties are shared by this protocol and the Informational Flagging Protocol [\[MS-OXOFLAG\]](#):

- **PidTagSwappedToDoData** ([\[MS-OXOFLAG\]](#) section 2.2.1.7)
- **PidTagSwappedToDoStore** ([\[MS-OXOFLAG\]](#) section 2.2.1.8)

The semantics and accepted values are identical to those specified in [\[MS-OXOFLAG\]](#).

2.2.2.3 Properties Shared with the Task-Related Objects Protocol

The following properties are shared by this protocol and the Task-Related Objects Protocol [\[MS-OXOTASK\]](#):

- **PidLidTaskDueDate** ([\[MS-OXOTASK\]](#) section 2.2.2.2.5)
- **PidLidTaskRecurrence** ([\[MS-OXOTASK\]](#) section 2.2.2.2.15)
- **PidLidTaskResetReminder** ([\[MS-OXOTASK\]](#) section 2.2.2.2.6)

Unless noted, the semantics and accepted values are identical to those specified in [\[MS-OXOTASK\]](#).

2.2.2.3.1 PidLidTaskDueDate Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidTaskDueDate** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.5) SHOULD [<6>](#) be set when creating a reminder on an object that is neither a **Task object** nor a Calendar object.

Setting the **PidLidTaskDueDate** property allows for a more intuitive "due-in" time when the reminder signals.

2.2.2.4 Properties Shared with the Appointment and Meeting Object Protocol

The following properties are shared by this protocol and the Appointment and Meeting Object Protocol [\[MS-OXOCAL\]](#):

- **PidLidAppointmentRecur** ([\[MS-OXOCAL\]](#) section 2.2.1.44) - The semantics and accepted values are identical to those specified in [\[MS-OXOCAL\]](#).
- **PidLidAutoStartCheck** ([\[MS-OXPROPS\]](#) section 2.41) - The semantics and accepted values are identical to those specified in [\[MS-OXOCAL\]](#).<7>
- **PidLidConferencingCheck** ([\[MS-OXOCAL\]](#) section 2.2.1.50.2) - The semantics and accepted values are identical to those specified in [\[MS-OXOCAL\]](#).<8>

2.2.3 Properties Used to Specify User Preferences that are Roamed on the Server

The following property is used to specify global state with respect to reminders. This property uses the protocol defined in [\[MS-OXOCFG\]](#) as a transport.

2.2.3.1 piReminderUpgradeTime Property

The **piReminderUpgradeTime** property is a 32-bit integer value (specified in number of minutes since midnight, January 1, 1601), stored in the **calendar options dictionary** (see [\[MS-OXOCFG\]](#) for details), that specifies the first time a **full reminder domain** client was used on the mailbox. The time is interpreted in the user's current time zone, not UTC.

3 Protocol Details

Except where noted, this section defines behavioral constraints to which both clients and servers MUST adhere when operating on the reminder properties of Message objects.

3.1 Client and Server Details

The server fulfills the server role in the following protocols.

- Office Exchange Protocols Master Property List Specification [\[MS-OXPROPS\]](#)
- E-Mail Object Protocol Specification [\[MS-OXOMSG\]](#)
- Folder Object Protocol Specification [\[MS-OXCFOLD\]](#)
- Table Object Protocol Specification [\[MS-OXCTABL\]](#)
- Special Folders Protocol Specification [\[MS-OXOSFLD\]](#)
- Search Folder List Configuration Protocol Specification [\[MS-OXOSRCH\]](#)
- Configuration Information Protocol Specification [\[MS-OXOCFG\]](#)
- Appointment and Meeting Object Protocol Specification [\[MS-OXOCAL\]](#)
- Task-Related Objects Protocol Specification [\[MS-OXOTASK\]](#)
- Informational Flagging Protocol Specification [\[MS-OXOFLAG\]](#)

3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

Messages with **active reminders** can be discovered by using a persistent **search folder** as specified in [\[MS-OXCFOLD\]](#). Those messages can then be loaded into a list, referred to as the **reminder queue**, that holds the relevant information in memory for pending and/or overdue reminders and is sorted by the **PidLidReminderSignalTime** property (section [2.2.1.2](#)).

Objects can be in one of the following states:

- No active reminder
- Pending reminder
- Overdue reminders

The reminder queue only contains Message objects that have a pending or overdue reminder.

3.1.2 Timers

None.

3.1.3 Initialization

3.1.3.1 Populating the Reminder Queue

3.1.3.1.1 Scope

Two approaches are typically used to specify the scope of the search for active reminders in the reminder queue: **minimal reminder domain** or full reminder domain.

Clients SHOULD<9> use a full domain scope strategy. Using multiple clients that use different scope strategies to access the same mailbox is not recommended.

Using multiple clients that use different **reminder domains** can lead to inconsistent reminder signaling behavior. For example, such an environment might have different overdue reminders signaled in different clients, which can lead to unexpectedly missed reminders when using the client with the smaller reminder domain.

3.1.3.1.1.1 Requirements for Clients Using a Full Reminder Domain

Clients that use a full domain scope strategy MUST ensure that the **piReminderUpgradeTime** property (section [2.2.3.1](#)) is set. If the **piReminderUpgradeTime** property does not exist, the client MUST set it. The value SHOULD correspond to the current local time, to reflect the time of upgrade to the expanded scope strategy of the newer client. The **piReminderUpgradeTime** property SHOULD<10> only be set once. If the **piReminderUpgradeTime** property is already set, it SHOULD NOT be changed as it represents the first time an "upgraded" client was used.

3.1.3.1.2 Loading/Processing

When populating or updating the reminder queue with Message objects found in the reminder domain, the client SHOULD:

- Ignore certain objects. For details, see section [3.1.4.5.1](#).
- Auto-dismiss certain objects. For details, see section [3.1.4.5.2](#).
- Include any remaining objects that have active reminders (pending or overdue reminders).

3.1.4 Higher-Layer Triggered Events

3.1.4.1 Setting a Reminder

In addition to the behaviors specified in this section, the client sets the **PidLidReminderSet** property (section [2.2.1.1](#)) to **TRUE** on an object to enable the signaling of a reminder. The client sets **PidLidReminderSignalTime** (section [2.2.1.2](#)) to the specified time the reminder becomes overdue, and sets the **PidLidReminderTime** property (section [2.2.1.4](#)).

3.1.4.1.1 Reminders on Task Objects

The client sets the **PidLidReminderTime** property (section [2.2.1.4](#)) to the specified time at which the reminder becomes overdue.

3.1.4.1.2 Reminders on Neither Calendar nor Task Objects

The client sets the **PidLidReminderTime** property (section [2.2.1.4](#)) and SHOULD<11> set **PidTagReplyTime** ([\[MS-OXOFLAG\]](#) section 2.2.3.1) to the specified signal time.

In summary, the client sets the following properties (or ensures that they are already set<12> for objects that are neither Calendar objects nor Task objects):

Property	Value
PidLidReminderSet (section 2.2.1.1)	TRUE
PidLidReminderTime	The specified signal time
PidLidReminderSignalTime (section 2.2.1.2)	The specified signal time
PidTagReplyTime	The specified signal time

3.1.4.1.3 Reminders on Calendar Objects

The client sets **PidLidReminderTime** (section [2.2.1.4](#)), and the value SHOULD<13> correspond to the appointment start time (see [\[MS-OXOCAL\]](#) for details).

For Calendar objects, the client MUST set **PidLidReminderDelta** (section [2.2.1.3](#)) to reflect the specified interval, in minutes, between the signal time of the reminder and the start time of the Calendar object.

In summary, the client sets the following properties (or otherwise ensures that the properties are already set):

Property	Value
PidLidReminderSet (section 2.2.1.1)	TRUE.
PidLidReminderTime	MUST be set, and SHOULD<14> be the appointment start time.
PidLidReminderDelta	The interval, in minutes, between signal time and the appointment start time.
PidLidReminderSignalTime (section 2.2.1.2)	The signal time in UTC.

3.1.4.1.4 Reminders on Recurring Calendar Objects

For Recurring Calendar objects, the client also sets or modifies the **recurrence BLOB** **PidLidAppointmentRecur** ([\[MS-OXOCAL\]](#) section 2.2.1.44) on the Recurring Calendar object, and the **Exception Embedded Message object** **PidTagAttachDataObject** ([\[MS-OXCMSG\]](#) section 2.2.2.8) on the **Exception Attachment object**, as specified in the following paragraphs.

To modify the reminder for specific instances in a **recurring series**, the client MUST create an exception if one does not already exist for that instance, and then modify the recurrence BLOB and Exception Embedded Message object, to store whichever properties are different from the Recurring Calendar object, such as **StartTime**, **ReminderDelta**, or **ReminderSet**. See [\[MS-OXOCAL\]](#) for details about the recurrence BLOB **PidLidAppointmentRecur**, and the Exception Attachment object, and see [\[MS-OXCMSG\]](#) for details about accessing the Exception Embedded Message object, which is stored in the **PidTagAttachDataObject** property.

Setting **PidLidReminderSet** (section [2.2.1.1](#)) to **FALSE** on the Recurring Calendar object MUST take precedence over any reminders that are specified for exceptions. To disable reminders for the

entire series, including all exceptions, set **PidLidReminderSet** to **FALSE** on the Recurring Calendar object.

If one or more instances, but not all instances, need a reminder, set the **PidLidReminderSet** property to **TRUE** on the Recurring Calendar object. Then set the **ReminderSet** field to **FALSE** in the recurrence BLOB for each instance that does not have a reminder, and set the property **PidLidReminderSet** on the Exception Embedded Message object to **FALSE**, creating exceptions as appropriate (see [MS-OXOCAL] and [MS-OXCMMSG] for details).

3.1.4.1.5 Setting Reminders on Draft Message Objects

By using the same mechanism that allows the client to set flagging properties for the sender of a Message object independently from the flagging properties that are sent to recipients [MS-OXOFLAG], a client can set the reminder properties for the sender of a Message object independently from the reminder properties that are sent to recipients.

If either a sender or recipient reminder is specified by a client that supports sender reminders, the **PidTagSwappedToDoStore** property ([MS-OXOFLAG] section 2.2.1.8) MUST be set to enable post-transmit processing. The remaining work to process recipient and sender reminders is covered during post-transmit processing as specified in [MS-OXOFLAG].

3.1.4.1.5.1 Setting a Reminder for all Recipients

To set a recipient reminder on a Draft Message object, the client sets **PidLidReminderSet** (section 2.2.1.1) to **TRUE** and sets the **PidLidReminderTime** property (section 2.2.1.4), the **PidLidReminderSignalTime** property (section 2.2.1.2), and the **PidTagReplyTime** property ([MS-OXOFLAG] section 2.2.3.1) to the required signal time.

3.1.4.1.5.2 Setting a Reminder for the Sender

The client MUST set the field **rtmReminder** to the required signal time and the field **fReminderSet** to **TRUE** in the **PtypBinary** property **PidTagSwappedToDoData** ([MS-OXOFLAG] section 2.2.1.7). The client sets the corresponding validity bits (0x00000040 and 0x00000080) to 1 in the **dwFlags** field in the **PidTagSwappedToDoData** property.

3.1.4.2 Post-Transmit Processing

The post-transmit processing required by the Reminder Settings Protocol is identical to the post-transmit processing specified in [MS-OXOFLAG].

3.1.4.3 Post-Receive Processing

For received Message objects that are not time flagged objects [MS-OXOFLAG], if the **PidTagReplyTime** property ([MS-OXOFLAG] section 2.2.3.1) exists, the value of the **PidTagReplyTime** property SHOULD <15> be copied into the **PidLidReminderTime** (section 2.2.1.4) and **PidLidReminderSignalTime** (section 2.2.1.2) properties, and the **PidLidReminderSet** property (section 2.2.1.1) SHOULD be set to **TRUE**.

3.1.4.4 Removing a Reminder

3.1.4.4.1 Single Instance Objects

The client sets the **PidLidReminderSet** property (section 2.2.1.1) to **FALSE**, which disables the reminder.

If the object is neither a Task object nor a Calendar object, the client MAY [<16>](#) delete the **PidLidReminderTime** property (section [2.2.1.4](#)) and **PidLidReminderSignalTime** (section [2.2.1.2](#)) and SHOULD delete the **PidTagReplyTime** property ([[MS-OXOFLAG](#)] section 2.2.3.1).

If the object is a Calendar object, the client SHOULD [<17>](#) set the **PidLidAutoStartCheck** property ([[MS-OXPROPS](#)] section 2.41) to **FALSE**.

If the object is a Task object, then the client SHOULD NOT perform any changes to the **PidLidAutoStartCheck** property.

3.1.4.4.2 Recurring Calendar Objects

To remove the reminder for all instances, including any exceptions, the client MUST set the **PidLidReminderSet** property (section [2.2.1.1](#)) to **FALSE** on the Recurring Calendar object.

To remove the reminder for a single instance, the client ensures that an exception exists for the instance, set the value of the **ReminderSet** field for the corresponding exception in the recurrence BLOB to **FALSE**, and set the **PidLidReminderSet** property on the Exception Embedded Message object to **FALSE**, and SHOULD [<18>](#) set the **PidLidAutoStartCheck** property ([[MS-OXPROPS](#)] section 2.41) on the Exception Embedded Message object to **FALSE**. See [[MS-OXOCAL](#)] for details about how to modify the appointment recurrence BLOB (**PidLidAppointmentRecur** ([[MS-OXOCAL](#)] section 2.2.1.44)) and the Exception Attachment object, and see [[MS-OXCMSG](#)] for details about accessing the Exception Embedded Message object, which is stored in **PidTagAttachDataObject** ([[MS-OXCMSG](#)] section 2.2.2.8).

3.1.4.4.3 Recurring Task Objects

To remove the reminder for all instances, the client sets the **PidLidReminderSet** property (section [2.2.1.1](#)) to **FALSE** on the recurring Task object, and SHOULD [<19>](#) ensure that the **PidLidTaskResetReminder** property ([[MS-OXOTASK](#)] section 2.2.2.2.6) is either not present or has the value **FALSE**.

Removing the reminder for a single instance of a Recurring Task object is not possible, because Recurring Task objects do not support exceptions. Therefore, the reminder can only be enabled or disabled for the entire **recurrence pattern**.

3.1.4.5 When a Reminder Becomes Overdue

3.1.4.5.1 Reminders That Are Ignored When They Become Overdue

Minimal domain clients SHOULD ignore reminders for the following types of objects, and full domain clients MUST ignore reminders for the following types of objects:

- **Meeting-related objects** - any object where the **PtypString** property **PidTagMessageClass** ([[MS-OXCMSG](#)] section 2.2.1.3) contains the prefix "IPM.Schedule". [<20>](#)
- Unsent mail - any object that contains the **PtypInteger32** property **PidTagMessageFlags** ([[MS-OXCMSG](#)] section 2.2.1.6) with the flag set corresponding to MSGFLAG_UNSENT (see [[MS-OXCMSG](#)] for details about Message flags, and the definition of MSGFLAG_UNSENT).
- Objects that have the **PtypBinary** property **PidTagSwappedToDoStore** ([[MS-OXOFLAG](#)] section 2.2.1.8) set. [<21>](#)

3.1.4.5.2 Reminders That Are Auto-Dismissed When Overdue

Clients following the full reminder domain scope strategy, as specified in section [3.1.3.1.1](#), SHOULD<22> auto-dismiss any objects found outside the minimal domain, which also have a signal time (**PidLidReminderSignalTime** (section [2.2.1.2](#))) that is earlier than the upgrade time (**piReminderUpgradeTime** (section [2.2.3.1](#))), so that the objects never have to be considered again. A reminder is auto-dismissed by setting the **PidLidReminderSet** property (section [2.2.1.1](#)) to **FALSE**.

3.1.4.5.3 Actions for Overdue Reminders That Are Not Ignored or Auto-Dismissed

When a reminder becomes overdue, the client commonly prompts the user to take action, such as dismissing or snoozing. To identify the reminder to the user (or user agent), the client can use any properties,<23> in addition to the following properties that the client SHOULD use to determine the due time for displaying how long until the object is due, or how much time has passed since the object became due.

When DueIn time is displayed, it is calculated from the due time, as summarized in the following table:

Case	Due time
For non-Calendar objects (tasks and flagged objects)<24>	If the PidLidTaskDueDate property ([MS-OXOTASK] section 2.2.2.2.5) exists, the client SHOULD<25> use "TaskDueDate + default End-of-Day time", otherwise use the PidLidReminderTime property (section 2.2.1.4) as the due time. For more details about End-of-Day time, see the <End> element in [MS-OXOCFG] section 2.2.5.2.1.
For single instance Calendar objects	PidLidReminderTime
For Recurring Calendar objects	The client SHOULD use the start time of the latest instance with enabled reminder for which the time defined by evaluating the expression (StartTime – ReminderDelta) is less than or equal to the time encoded in the PidLidReminderSignalTime property (section 2.2.1.2) on the Recurring Calendar object. See [MS-OXOCAL] . NOTE: StartTime and ReminderDelta could be overridden by exceptions.

If the **PidLidReminderOverride** property (section [2.2.1.5](#)) is set to **FALSE**, or not set, the client SHOULD<26> play the default reminder sound.

If the **PidLidReminderOverride** property is set to **TRUE**, the client SHOULD<27> use the **PidLidReminderPlaySound** (section [2.2.1.6](#)) and **PidLidReminderFileParameter** (section [2.2.1.7](#)) properties from the reminder properties of the given object.

If the **PidLidReminderPlaySound** property is **TRUE**, the client SHOULD<28> use the **PidLidReminderFileParameter** property to locate the specified sound file, and then play it.

If the **PidLidReminderPlaySound** property is **FALSE**, the client SHOULD NOT<29> play a reminder sound.

If the client uses the **PidLidReminderFileParameter** property for purposes of playing a sound, and it does not represent a full path, the client can search for a matching file name.

3.1.4.5.3.1 Starting a Conference

If the **PidLidConferencingCheck** property ([\[MS-OXOCAL\]](#) section 2.2.1.50.2) and the **PidLidAutoStartCheck** property ([\[MS-OXPROPS\]](#) section 2.41) are both set to **TRUE**, the client can launch the conference. The client MAY launch a conference if the **PidLidConferencingType** property ([\[MS-OXOCAL\]](#) section 2.2.1.50.3) is set to 0x00000000, and use the properties **PidLidConferencingCheck**, **PidLidConferencingType**, **PidLidOrganizerAlias** ([\[MS-OXOCAL\]](#) section 2.2.1.50.6), **PidLidDirectory** ([\[MS-OXPROPS\]](#) section 2.89), **PidTagConversationTopic** ([\[MS-OXOMSG\]](#) section 2.2.1.5), **PidLidCollaborateDoc** ([\[MS-OXOCAL\]](#) section 2.2.1.50.7), **PidLidNetShowUrl** ([\[MS-OXOCAL\]](#) section 2.2.1.50.8), and **PidLidAppointmentStateFlags** ([\[MS-OXOCAL\]](#) section 2.2.1.10). For more details, see [\[MS-OXOCAL\]](#).

3.1.4.6 Dismissing a Reminder

3.1.4.6.1 Dismissing for Single Instance Objects

For all single instance objects, the client MUST set the **PidLidReminderSet** property (section [2.2.1.1](#)) to **FALSE**.

In addition, for single instance Task objects, the client can follow the guidance in the following section for dismissing a Recurring Task object.

3.1.4.6.2 Dismissing for Recurring Calendar Objects

If there is a future instance (including exceptions) with a pending reminder (in other words, not disabled individually on all future instances), the client MUST set the **PidLidReminderSignalTime** property (section [2.2.1.2](#)) on the Recurring Calendar object based on the **PidLidReminderDelta** property (section [2.2.1.3](#)) and the start of that instance (that is, **NextInstanceStartTime** - **PidLidReminderDelta**). If no more instances (including exceptions) have a pending reminder, it is recommended that the client avoid setting the **PidLidReminderSet** property (section [2.2.1.1](#)) to **FALSE**, and the client MUST set the **PidLidReminderSignalTime** property to the **PtypTime** value "Midnight (UTC) January 1, 4501" (value Low:0xA3DD4000 High:0x0CB34557).

It is recommended that the client avoid setting the **PidLidReminderSet** property to **FALSE** when dismissing reminders for Recurring Calendar objects, even when no more instances require a reminder to signal. This is to preserve the user's intent to signal reminders, in case the recurrence is extended at a later date, to include instances in the future.

NOTE: Instances never "turn into" exceptions as a result of dismissing/snoozing.

3.1.4.6.3 Dismissing for Recurring Task Objects

The client MUST set the **PidLidReminderSet** property (section [2.2.1.1](#)) to **FALSE**, and SHOULD [<30>](#) set the **PidLidTaskResetReminder** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.6) to **TRUE** to dismiss the reminder.

For Task objects, if the value of the **PidLidReminderTime** property (section [2.2.1.4](#)) is in the future, the client SHOULD [<31>](#) set the **PidLidReminderSignalTime** property (section [2.2.1.2](#)) to the same value as **PidLidReminderTime** so that the reminder will be signaled at the appropriate time for the next instance.

3.1.4.7 Snoozing a Reminder

3.1.4.7.1 Snoozing for Single Instance Objects

The client MUST set **PidLidReminderSignalTime** (section [2.2.1.2](#)) to the time specified by the user (or user agent).

3.1.4.7.2 Snoozing for Recurring Objects

The client MUST set **PidLidReminderSignalTime** (section [2.2.1.2](#)) to either the specified time, or the signal time for the next instance with an active reminder (for example, `NextInstanceStart - ReminderDelta`), whichever is earlier.

NOTE: Instances never "turn into" exceptions as a result of dismissing/snoozing.

3.1.4.8 Generating Instances for Recurring Task Objects

In addition to the details related to the semantics and the use of the **PidLidTaskResetReminder** property specified in [\[MS-OXOTASK\]](#) section 2.2.2.2.6, the following applies to generating instances for Recurring Task objects:

When a Recurring Task object is updated after one instance of the task is marked complete, if the **PtypBoolean** property **PidLidTaskResetReminder** is **TRUE**, or the **PidLidReminderSet** property (section [2.2.1.1](#)) is **TRUE**, a reminder SHOULD [<32>](#) be set on the Recurring Task object by setting both the **PidLidReminderTime** property (section [2.2.1.4](#)) and the **PidLidReminderSignalTime** property (section [2.2.1.2](#)) to the next signal time. These values SHOULD correspond to the same time as the previous reminder, but on a different day, such that the difference between the new signal time and the new task due date is the same as the difference between the old signal time and old task due date values. The client adjusts for Daylight Saving Time when necessary (if a change in DST occurs between the current and next instance), so the reminder signals at the same time of day.

After an instance of a **recurring task** that has an active reminder is complete, the future instance MUST have the **PidLidReminderSet** property set to **TRUE**, and the **PidLidTaskResetReminder** property SHOULD NOT [<33>](#) be **TRUE**. The now-completed instance MUST have the **PidLidReminderSet** property set to **FALSE**, and the **PidLidTaskResetReminder** property SHOULD NOT [<34>](#) be **TRUE**.

3.1.5 Message Processing Events and Sequencing Rules

None.

3.1.6 Timer Events

None.

3.1.7 Other Local Events

None.

4 Protocol Examples

Before adding, removing, or modifying a reminder on any Message objects, the client has to ask the server to perform a mapping from **named properties** to property identifiers by using **RopGetPropertyIdsFromNames**, as follows:

Property	Property Set GUID	Name or ID
PidLidReminderSet (section 2.2.1.1)	{00062008-0000-0000-C000-000000000046}	0x8503
PidLidReminderTime (section 2.2.1.4)	{00062008-0000-0000-C000-000000000046}	0x8502
PidLidReminderDelta (section 2.2.1.3)	{00062008-0000-0000-C000-000000000046}	0x8501
PidLidReminderSignalTime (section 2.2.1.2)	{00062008-0000-0000-C000-000000000046}	0x8560
PidLidTaskDueDate ([MS-OXOTASK] section 2.2.2.2.5)	{00062003-0000-0000-C000-000000000046}	0x8105
PidLidTaskResetReminder ([MS-OXOTASK] section 2.2.2.2.6)	{00062003-0000-0000-C000-000000000046}	0x8107
PidLidAppointmentRecur ([MS-OXOCAL] section 2.2.1.44)	{00062002-0000-0000-C000-000000000046}	0x8216
PidLidAutoStartCheck ([MS-OXPROPS] section 2.41)	{00062002-0000-0000-C000-000000000046}	0x8244
PidLidFExceptionalAttendees ([MS-OXOCAL] section 2.2.2.3)	{00062002-0000-0000-C000-000000000046}	0x822B

The server might respond with the following identifiers, which will be used in the examples that follow (the actual identifiers are at the discretion of the server):

Property	Property Identifier
PidLidReminderSet	0x8004
PidLidReminderTime	0x8005
PidLidReminderDelta	0x81FF
PidLidReminderSignalTime	0x8006
PidLidTaskDueDate	0x8144
PidLidTaskResetReminder	0x815B
PidLidAppointmentRecur	0x81AE
PidLidAutoStartCheck	0x82E0
PidLidFExceptionalAttendees	0x82D7

4.1 Set a Reminder on a Single Instance Appointment

John has an existing appointment for "Dinner with Robin Counts" at Coho Vineyard on February 15, 2008 from 6:00 P.M. to 7:00 P.M. Pacific Standard Time. Around 11:44 A.M., John sets a reminder on the appointment for 30 minutes.

Before John modified the object, some of the properties were as follows:

Property Name	Property Identifier	Property Type	Data	Value
PidTagNormalizedSubject ([MS-OXCMSG] section 2.2.1.10)	0x0E1D	PtypString	44 00 69 00 6E 00 6E 00 65 00 72 00 20 00 77 00 69 00 74 00 68 00 20 00 52 00 6F 00 62 00 69 00 6E 00 20 00 43 00 6F 00 75 00 6E 00 74 00 73 00 00 00	"Dinner with Robin Counts"
PidLidLocation ([MS-OXOCAL] section 2.2.1.4)	0x8009	PtypString	43 00 6F 00 68 00 6F 00 20 00 56 00 69 00 6E 00 65 00 79 00 61 00 72 00 64 00 00 00	"Coho Vineyard"
PidTagStartDate ([MS-OXOCAL] section 2.2.1.30)	0x0060	PtypTime	00 10 00 A3 3F 70 C8 01	2008/02/16 02:00:00.000
PidTagEndDate ([MS-OXOCAL] section 2.2.1.31)	0x0061	PtypTime	00 78 C4 04 48 70 C8 01	2008/02/16 03:00:00.000
PidLidReminderSet (section 2.2.1.1)	0x8004	PtypBoolean	00	FALSE
PidLidReminderTime (section 2.2.1.4)	0x8005	PtypTime	00 10 00 A3 3F 70 C8 01	2008/02/16 02:00:00.000
PidLidReminderSignalTime (section 2.2.1.2)	0x8006	PtypTime	00 F6 8E 8A 3D 70 C8 01	2008/02/16 01:45:00.000
PidLidReminderDelta (section 2.2.1.3)	0x81FF	PtypInteger32	0F 00 00 00	15 minutes

The client sends a **RopOpenMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.1) request and waits for the server to respond. The server response contains a handle to the Message object.

The client then sends a **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) request with the following properties in response to user-entered data:

Property	Property Identifier	Property Type	Data	Value
PidLidReminderSet	0x8004	PtypBoolean	01	TRUE
PidLidReminderDelta	0x81FF	PtypInteger32	1E 00 00 00	30 minutes

Property	Property Identifier	Property Type	Data	Value
PidLidReminderSignalTime	0x8006	PtypTime	00 DC 1D 72 3B 70 C8 01	2008/02/16 01:30:00.000

Finally, the client sends a **RopSaveChangesMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.3) request to persist the object on the server, and a **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) request to release the object.

4.2 Set a Reminder on a Message Object

John, who is currently working in the Pacific Standard time zone, has an existing message titled "Important Project Information" that was previously flagged for follow-up by February 14, 2008. To ensure that it is not forgotten, John sets a reminder for 6:00 P.M.

Before John modified the object, some of its properties were as follows:

Property Name	Property Identifier	Property Type	Data	Value
PidTagNormalizedSubject ([MS-OXCMSG] section 2.2.1.10)	0x0E1D	PtypString	49 00 6D 00 70 00 6F 00 72 00 74 00 61 00 6E 00 74 00 20 00 50 00 72 00 6F 00 6A 00 65 00 63 00 74 00 20 00 49 00 6E 00 66 00 6F 00 72 00 6D 00 61 00 74 00 69 00 6F 00 6E 00 00 00	"Important Project Information"
PidLidTaskStartDate ([MS-OXOTASK] section 2.2.2.2.4)	0x8143	PtypTime	00 C0 A3 8A 9C 6E C8 01	2008/02/14 00:00:00.000
PidLidTaskDueDate ([MS-OXOTASK] section 2.2.2.2.5)	0x8144	PtypTime	00 C0 A3 8A 9C 6E C8 01	2008/02/14 00:00:00.000
PidLidReminderSet (section 2.2.1.1)	0x8004	PtypBoolean	00	FALSE
PidLidReminderTime (section 2.2.1.4)	0x8005	PtypTime	Deleted	N/A
PidLidReminderSignalTime (section 2.2.1.2)	0x8006	PtypTime	Deleted	N/A

The client sends a **RopOpenMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.1) request and waits for the server to respond. The server response contains a handle to the Message object.

The client then sends a **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) request with the following properties in response to user-entered data:

Property	Property Identifier	Property Type	Data	Value
PidLidReminderTime	0x8005	PtypTime	00 50 96	2008/02/15

Property	Property Identifier	Property Type	Data	Value
			78 76 6f c8 01	02:00:00.000
PidLidReminderSignalTime	0x8006	PtypTime	00 50 96 78 76 6f c8 01	2008/02/15 02:00:00.000
PidLidReminderSet (section 2.2.1.1)	0x8004	PtypBoolean	01	TRUE
PidTagReplyTime ([MS-OXOFLAG] section 2.2.3.1)	0x0030	PtypTime	00 50 96 78 76 6f c8 01	2008/02/15 02:00:00.000
PidTagReplyRequested ([MS-OXOMSG] section 2.2.1.37)	0x0C17	PtypBoolean	01	TRUE
PidTagResponseRequested ([MS-OXOMSG] section 2.2.1.37)	0x0063	PtypBoolean	01	TRUE
PidTagFlagStatus ([MS-OXOFLAG] section 2.2.1.1)	0x1090	PtypInteger32	02 00 00 00	follow-up marked

Next, the client sends a **RopDeletePropertiesNoReplicate** ([MS-OXCROPS] section 2.2.8.9) request for the following properties:

Property	Property Identifier	Property Type
PidTagFlagCompleteTime ([MS-OXOFLAG] section 2.2.1.3)	0x1091	PtypTime

Finally, the client sends a **RopSaveChangesMessage** ([MS-OXCROPS] section 2.2.6.3) request to persist the object on the server, and a **RopRelease** ([MS-OXCROPS] section 2.2.15.3) request to release the object.

4.3 Dismiss a Reminder on a Task

John had previously created a Task object titled "Prepare for Contoso presentation", with a reminder that was signaled on February 15, 2008, at 11:30 A.M. Pacific Standard Time. Because he is done, John dismisses the reminder at 11:31 A.M.

Before John dismissed the reminder, some of its properties were as follows:

Property Name	Property Identifier	Property Type	Data	Value
PidTagNormalizedSubject ([MS-OXCMSG] section 2.2.1.10)	0x0E1D	PtypString	50 00 72 00 65 00 70 00 61 00 72 00 65 00 20 00 66 00 6F 00 72 00 20 00 43 00 6F 00 6E 00 74 00 6F 00 73 00 6F 00 20 00 70 00 72 00 65 00 73 00 65 00 6E 00 74 00 61 00 74 00 69 00	"Prepare for Contoso presentation"

Property Name	Property Identifier	Property Type	Data	Value
			6F 00 6E 00 00 00	
PidLidTaskStartDate ([MS-OXOTASK] section 2.2.2.2.4)	0x8143	PtypTime	00 80 0D B5 65 6F C8 01	2008/02/15 00:00:00.000
PidLidTaskDueDate ([MS-OXOTASK] section 2.2.2.2.5)	0x8144	PtypTime	00 80 0D B5 65 6F C8 01	2008/02/15 00:00:00.000
PidLidReminderSet (section 2.2.1.1)	0x8004	PtypBoolean	01	TRUE
PidLidReminderTime (section 2.2.1.4)	0x8005	PtypTime	00 6C 83 27 09 70 C8 01	2008/02/15 19:30:00.000
PidLidReminderSignalTime (section 2.2.1.2)	0x8006	PtypTime	00 6C 83 27 09 70 C8 01	2008/02/15 19:30:00.000
PidLidTaskResetReminder ([MS-OXOTASK] section 2.2.2.2.6)	0x815B	PtypBoolean	Deleted	N/A

The client sends a **RopOpenMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.1) request and waits for the server to respond. The server response contains a handle to the Message object.

The client then sends a **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) request with the following properties in response to user-entered data:

Property	Property Identifier	Property Type	Data	Value
PidLidReminderSet	0x8004	PtypBoolean	00	FALSE
PidLidTaskResetReminder	0x815B	PtypBoolean	01	TRUE

Finally, the client sends a **RopSaveChangesMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.3) request to persist the object on the server, and a **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) request to release the object.

4.4 Dismiss a Reminder on a Recurring Calendar Object

John has a recurring appointment for lunch with Ben Smith every Friday at noon Pacific Standard Time, with a 20 minute reminder. The reminder for the first instance is displayed, and John dismisses the reminder before leaving for the Coho Winery.

Before John dismissed the object, some of its properties were as follows:

Property Name	Property Identifier	Property Type	Data	Value
PidTagNormalizedSubject ([MS-OXCMSG] section 2.2.1.10)	0x0E1D	PtypString	4C 00 75 00 6E 00 63 00 68 00 20 00 77 00 69 00 74 00 68 00 20 00 42 00 65 00 6E 00 20 00 53 00 6D 00 69	"Lunch with Ben Smith"

Property Name	Property Identifier	Property Type	Data	Value
			00 74 00 68 00 00 00	
PidLidLocation ([MS-OXOCAL] section 2.2.1.4)	0x8009	PtypString	43 00 6F 00 68 00 6F 00 20 00 57 00 69 00 6E 00 65 00 72 00 79 00 00 00	"Coho Winery"
PidTagStartDate ([MS-OXOCAL] section 2.2.1.30)	0x0060	PtypTime	00 A0 65 58 0D 70 C8 01	2008/02/15 20:00:00.000
PidTagEndDate ([MS-OXOCAL] section 2.2.1.31)	0x0061	PtypTime	00 08 2A BA 15 70 C8 01	2008/02/15 21:00:00.000
PidLidReminderSet (section 2.2.1.1)	0x8004	PtypBoolean	01	TRUE
PidLidReminderTime (section 2.2.1.4)	0x8005	PtypTime	00 A0 65 58 0D 70 C8 01	2008/02/15 20:00:00.000
PidLidReminderSignalTime (section 2.2.1.2)	0x8006	PtypTime	00 28 24 8D 0A 70 C8 01	2008/02/15 19:40:00.000
PidLidReminderDelta (section 2.2.1.3)	0x81FF	PtypInteger32	14 00 00 00	20 minutes
PidLidAppointmentRecur ([MS-OXOCAL] section 2.2.1.44)	0x81AE	PtypBinary	Cb: 50 00 Lpb: See below	Cb: 80 bytes Lpb: See [MS-OXOCAL]

The value of the **PidLidAppointmentRecur** property is as follows:

Cb: 50 00

Lpb:

```

0x0000: 04 30 04 30 0B 20 01 00-00 00 C0 21 00 00 01 00
0x0010: 00 00 00 00 00 00 20 00-00 00 23 20 00 00 0A 00
0x0020: 00 00 00 00 00 00 00 00-00 00 00 00 00 00 40 4A
0x0030: C3 0C DF 80 E9 5A 06 30-00 00 09 30 00 00 D0 02
0x0040: 00 00 0C 03 00 00 00 00-00 00 00 00 00 00 00 00

```

See [MS-OXOCAL] for information about interpreting the data.

The client sends a **RopOpenMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.1) request and waits for the server to respond. The server response contains a handle to the Message object.

The client then sends a **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) request with the following properties in response to user-entered data:

Property	Property Identifier	Property Type	DATA	Value
PidLidReminderSignalTime	0x8006	PtypTime	00 68 08 B6	2008/02/22

Property	Property Identifier	Property Type	DATA	Value
			8A 75 C8 01	19:40:00.000

Finally, the client sends a **RopSaveChangesMessage** ([MS-OXCROPS] section 2.2.6.3) request to persist the object on the server, and a **RopRelease** ([MS-OXCROPS] section 2.2.15.3) request to release the object.

4.5 Snooze a Reminder on a Contact Object

John has an existing Contact object for Adam Barr with a reminder set so he is reminded to call on February 15, 2008 at 11:15 A.M., Pacific Standard Time. The reminder is displayed, but John is still in the middle of a project, so around 11:18 A.M., John snoozes the reminder for 1 hour.

Before John snoozed the object, some of its properties were as follows:

Property Name	Property Identifier	Property Type	Data	Value
PidTagNormalizedSubject ([MS-OXCMSG] section 2.2.1.10)	0x0E1D	PtypString	41 00 64 00 61 00 6D 00 20 00 42 00 61 00 72 00 72 00 00 00	"Adam Barr"
PidLidTaskStartDate ([MS-OXOTASK] section 2.2.2.2.4)	0x8143	PtypTime	00 80 0D B5 65 6F C8 01	2008/02/15 00:00:00.000
PidLidTaskDueDate ([MS-OXOTASK] section 2.2.2.2.5)	0x8144	PtypTime	00 80 0D B5 65 6F C8 01	2008/02/15 00:00:00.000
PidLidReminderSet (section 2.2.1.1)	0x8004	PtypBoolean	01	TRUE
PidLidReminderTime (section 2.2.1.4)	0x8005	PtypTime	00 52 12 0F 07 70 C8 01	2008/02/15 19:15:00.000
PidLidReminderSignalTime (section 2.2.1.2)	0x8006	PtypTime	00 52 12 0F 07 70 C8 01	2008/02/15 19:15:00.000

The client sends a **RopOpenMessage** ([MS-OXCROPS] section 2.2.6.1) request and waits for the server to respond. The server response contains a handle to the Message object.

The client then sends a **RopSetProperties** ([MS-OXCROPS] section 2.2.8.6) request with the following properties in response to user-entered data:

Property	Property Identifier	Property Type	Data	Value
PidLidReminderSignalTime	0x8006	PtypTime	00 8C 20 DC 0F 70 C8 01	2008/02/15 20:18:00.000

Finally, the client sends a **RopSaveChangesMessage** ([MS-OXCROPS] section 2.2.6.3) request to persist the object on the server, and a **RopRelease** ([MS-OXCROPS] section 2.2.15.3) request to release the object.

4.6 Remove a Reminder From an Instance of a Recurring Calendar Object

John has an existing recurring appointment for lunch on Fridays at noon, Pacific Standard Time, but the instance for next week, which occurs on February 22, 2008, was previously changed to 11:00 A.M. (that is, the next instance already has an exception). John opens that instance, sets the signal time to none, and saves the object, disabling the reminder for just that instance.

Before John modified the object, some of the properties on the Recurring Calendar object were as follows:

Property Name	Property Identifier	Property Type	Data	Value
PidTagNormalizedSubject ([MS-OXCMMSG] section 2.2.1.10)	0x0E1D	PtypString	4C 00 75 00 6E 00 63 00 68 00 20 00 77 00 69 00 74 00 68 00 20 00 42 00 65 00 6E 00 20 00 53 00 6D 00 69 00 74 00 68 00 00 00	"Lunch with Ben Smith"
PidTagStartDate ([MS-OXOCAL] section 2.2.1.30)	0x0060	PtypTime	00 A0 65 58 0D 70 C8 01	2008/02/15 20:00:00.000
PidTagEndDate ([MS-OXOCAL] section 2.2.1.31)	0x0061	PtypTime	00 08 2A BA 15 70 C8 01	2008/02/15 21:00:00.000
PidLidReminderSet (section 2.2.1.1)	0x8004	PtypBoolean	01	TRUE
PidLidReminderTime (section 2.2.1.4)	0x8005	PtypTime	00 A0 65 58 0D 70 C8 01	2008/02/15 20:00:00.000
PidLidReminderSignalTime (section 2.2.1.2)	0x8006	PtypTime	00 00 44 54 82 75 C8 01	2008/02/22 06:40:00.000
PidLidAppointmentRecur ([MS-OXOCAL] section 2.2.1.44)	0x81AE	PtypBinary	Cb: 72 00 Lpb: See below	Cb: 114 bytes Lpb: See [MS-OXOCAL]

The value of the **PidLidAppointmentRecur** property is as follows:

Cb: 72 00

Lpb:

```
0x0000: 04 30 04 30 0B 20 01 00-00 00 C0 21 00 00 01 00
0x0010: 00 00 00 00 00 00 00 20 00-00 00 23 20 00 00 0A 00
0x0020: 00 00 00 00 00 00 00 01 00-00 00 A0 71 C3 0C 01 00
0x0030: 00 00 A0 71 C3 0C 40 4A-C3 0C DF 80 E9 5A 06 30
0x0040: 00 00 09 30 00 00 D0 02-00 00 0C 03 00 00 01 00
0x0050: 34 74 C3 0C 70 74 C3 0C-70 74 C3 0C 00 00 00 00
0x0060: 00 00 04 00 00 00 00 00-00 00 00 00 00 00 00 00
0x0070: 00 00
```

See [\[MS-OXOCAL\]](#) for details about interpreting the data.

Some properties from the Exception Attachment object are listed in the following table.

Property Name	Property Identifier	Property Type	Data	Value
PidTagAttachSize ([MS-OXCMSG] section 2.2.2.5)	0x0E20	PtypInteger32	DC 0E 00 00	3804 bytes
PidTagLastModificationTime ([MS-OXCMSG] section 2.2.2.2)	0x3008	PtypTime	62 BC D2 86 20 70 C8 01	2008/02/15 22:17:18.328

The client sends a **RopOpenMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.1) request and waits for the server to respond. The server response contains a handle to the Recurring Calendar object.

Then the client sends a **RopOpenAttachment** ([\[MS-OXCROPS\]](#) section 2.2.6.12) request and waits for the server to respond. The server response contains a handle to the Exception Attachment object. See [\[MS-OXOCAL\]](#) for details about using the attachment table to find the attachment that corresponds to a given exception.

Then the client sends a **RopOpenEmbeddedMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.16) request and waits for the server to respond. The server response contains a handle to the Exception Embedded Message object.

Next, the client sends a **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) request with the following properties in response to the user-entered data for the Exception Embedded Message object (followed by a **RopSaveChangesMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.3) request to persist the object on the server):

Property Name	Property Identifier	Property Type	Data	Value
PidLidAutoStartCheck ([MS-OXPROPS] section 2.41)	0x82E0	PtypBoolean	00	FALSE
PidLidReminderSet	0x8004	PtypBoolean	00	FALSE

Next, the client sends a **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) request with the following properties in response to user-entered data for the Exception Attachment object (followed by a **RopSaveChangesAttachment** ([\[MS-OXCROPS\]](#) section 2.2.6.15) request to persist the object on the server):

Property Name	Property Identifier	Property Type	Data	Value
PidTagAttachMethod ([MS-OXCMSG] section 2.2.2.9)	0x3705	PtypInteger32	05 00 00 00	5
PidTagRenderingPosition ([MS-OXCMSG] section 2.2.2.16)	0x370B	PtypInteger32	FF FF FF FF	-1
PidTagExceptionStartTime ([MS-OXOCAL] section 2.2.10.1.4)	0x7FFB	PtypTime	00 38 62 11 42 75 c8 01	2008/02/22 11:00:00.000
PidTagAttachEncoding ([MS-OXCMSG] section 2.2.2.20)	0x3702	PtypBinary	00 00	Size: 0 bytes
PidTagExceptionEndTime ([MS-	0x7FFC	PtypTime	00 a0 26	2008/02/22

Property Name	Property Identifier	Property Type	Data	Value
OXOCAL section 2.2.10.1.5)			73 4a 75 c8 01	12:00:00.000
PidTagAttachmentFlags ([MS-OXCMSG] section 2.2.2.23)	0x7FFD	PtypInteger32	02 00 00 00	Exception to a recurrence
PidTagDisplayName ([MS-OXCFOLD] section 2.2.2.2.3)	0x3001	PtypString	55 00 6e 00 74 00 69 00 74 00 6c 00 65 00 64 00 00 00	"Untitled"
PidTagAttachmentLinkId ([MS-OXCMSG] section 2.2.2.22)	0x7FFA	PtypInteger32	00 00 00 00	0
PidTagAttachFlags ([MS-OXCMSG] section 2.2.2.18)	0x3714	PtypInteger32	00 00 00 00	0
PidTagAttachmentHidden ([MS-OXCMSG] section 2.2.2.24)	0x7FFE	PtypBoolean	01	TRUE
PidTagAttachmentContactPhoto ([MS-OXOCNTC] section 2.2.1.8)	0x7FFF	PtypBoolean	00	FALSE

Next, the client sends a **RopSetProperties** ([\[MS-OXCROPS\]](#) section 2.2.8.6) request with the following properties in response to user-entered data for the Recurring Calendar object (followed by a **RopSaveChangesMessage** ([\[MS-OXCROPS\]](#) section 2.2.6.3) request to persist the object on the server):

Property Name	Property Identifier	Property Type	Data	Value
PidLidAppointmentRecur	0x81AE	PtypBinary	Cb: 76 00 Lpb: See below	Cb: 118 bytes Lpb: See below
PidLidFExceptionalAttendees ([MS-OXOCAL] section 2.2.2.3)	0x82D7	PtypBoolean	00	FALSE
PidLidReminderSignalTime	0x8006	PtypTime	00 A8 EC DE 0A 7B C8 01	2008/02/29 19:40:00.000

Then the client sends a **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) request to release the Exception Embedded Message object, and a **RopRelease** request to release the Exception Attachment object.

Finally, the client sends a **RopRelease** ([\[MS-OXCROPS\]](#) section 2.2.15.3) request to release the attachment table, and a **RopRelease** request to release the Recurring Calendar object.

The value of the **PidLidAppointmentRecur** property is as follows:

Cb: 76 00

Lpb:

```

0x0000: 04 30 04 30 0B 20 01 00-00 00 C0 21 00 00 01 00
0x0010: 00 00 00 00 00 00 20 00-00 00 23 20 00 00 0A 00
0x0020: 00 00 00 00 00 00 01 00-00 00 A0 71 C3 0C 01 00
0x0030: 00 00 A0 71 C3 0C 40 4A-C3 0C DF 80 E9 5A 06 30
0x0040: 00 00 09 30 00 00 D0 02-00 00 0C 03 00 00 01 00
0x0050: 34 74 C3 0C 70 74 C3 0C-70 74 C3 0C 08 00 00 00
0x0060: 00 00 00 00 00 00 04 00-00 00 00 00 00 00 00
0x0070: 00 00 00 00 00 00

```

This corresponds to the following table, in which the **OverrideFlags** and **fReminder** fields for the first exception are the only two fields that changed within the **PtypBinary** property **PidLidAppointmentRecur**. In this specific case, the 2 byte value, starting at the 93rd byte (flags), was changed from 0x0000 to 0x0008, and a 4 byte value representing FALSE (0x00000000) was inserted between the 94th and 95th bytes, extending the size of the property from 114 bytes to 118 bytes. See [MS-OXOCAL] for details about how to determine the byte position in other cases.

Name	Type	Size	Data	Description
ReaderVersion	WORD	2	04 30	This field is set to 0x3004.
WriterVersion	WORD	2	04 30	This field is set to 0x3004.
UIGroup	WORD	2	0b 20	The pattern of the recurrence is weekly (0x200b).
PatternType	WORD	2	01 00	The pattern type is weekly (0x0001).
CalendarType	WORD	2	00 00	The calendar type is Gregorian (0x0000).
FirstDateTime	ULONG	4	c0 21 00 00	See [MS-OXOCAL] for details about how this property was calculated based on the StartDate.
Period	ULONG	4	01 00 00 00	The recurrence occurs every week (0x00000001).
SlidingFlag	ULONG	4	00 00 00 00	The recurring instances do not rely on completion of the previous instances.
PatternTypeSpecific	Byte Array	Varies (4 bytes, in this case, for Weekly pattern)	20 00 00 00	The recurring appointment occurs on Friday. See [MS-OXOCAL] for details about how the value is determined.
EndType	ULONG	4	23 20 00 00	No End. (0x00002023)
OccurrenceCount	ULONG	4	0A 00 00 00	Ignored, because recurrence does not have an end.
FirstDOW	ULONG	4	00 00 00 00	The first day of the week on the calendar is Sunday (the default value).
DeletedInstanceCount	ULONG	4	01 00 00 00	One deleted instance.
Deleted Instance Start	ULONG	4	A0 71	0x0CC371A0 == February 22, 2008 at

Name	Type	Size	Data	Description
			C3 0C	00:00 in UTC.
ModifiedInstanceCount	ULONG	4	01 00 00 00	One modified instance.
Modified Instance Start	ULONG	4	A0 71 C3 0C	0x0CC371A0 == February 22, 2008 at 00:00 in UTC.
StartDate of entire series	ULONG	4	40 4A C3 0C	The start date of the recurrence given in minutes since midnight January 1, 1601 corresponds to February 15, 2008 12:00:00 A.M. 0x0CC34A40
EndDate of entire series	ULONG	4	DF 80 E9 5A	The end date of the recurrence given in minutes since midnight January 1, 1601, however, since there is no end date, this value corresponds to the "last valid" date: December 31, 4500 11:59 P.M. (0x5AE980DF)
ReaderVersion2	ULONG	4	06 30 00 00	This value is set to 0x00003006.
WriterVersion2	ULONG	4	09 30 00 00	This value is set to 0x00003009.<35>
StartTimeOffset	ULONG	4	D0 02 00 00	The hexadecimal start time of the recurrence is 0x000002D0, which corresponds to 720 in decimal. 720 minutes is 12 hours, which is 12 P.M.
EndTimeOffset	ULONG	4	0C 03 00 00	The hexadecimal end time of the recurrence is 0x00000030C, which corresponds to 780 minutes, which is 1:00 P.M.
ExceptionCount	WORD	2	01 00	There is one exception in this recurrence BLOB.
ExceptionInfo block for exception 1:				
Start Date Time	ULONG	4	34 74 C3 0C	0x0CC37434 == February 22, 2008 at 11:00 A.M.
End Date Time	ULONG	4	70 74 C3 0C	0x0CC37470 == February 22, 2008 at 12:00 P.M.
Original Start Time	ULONG	4	70 74 C3 0C	0x0CC37470 == February 22, 2008 at 12:00 P.M.
OverrideFlags	WORD	2	08 00	0x0008 corresponds to the "fReminderSet" flag, meaning just that field is specified for this exception.
fReminderSet	ULONG	4	00 00 00 00	0x00000000 == FALSE, meaning ReminderSet is overridden with the value FALSE for this exception.

Name	Type	Size	Data	Description
ReservedBlock1Size	ULONG	4	00 00 00 00	There is no data in the reserved block.
ExtendedException block for exception 1:				
ChangeHighlight	Byte Array	Varies	04 00 00 00 00 00 00 00	The size of the ChangeHighlight is 4. The value of the PidLidChangeHighlight ([MS-OXOCAL] section 2.2.6.2) property is zero for this exception.
ReservedBlockEE1Size	ULONG	4	00 00 00 00	There is no data in the reserved block.
ReservedBlock2Size	ULONG	4	00 00 00 00	There is no data in the reserved block.

5 Security

5.1 Security Considerations for Implementers

There are no special security considerations specific to the Reminder Settings Protocol. General security considerations pertaining to the underlying transport apply, as specified in [\[MS-OXCMSG\]](#) and [\[MS-OXCPRPT\]](#).

5.2 Index of Security Parameters

None.

6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2003
- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Office Outlook® 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Outlook® 2010

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.1.5:](#) In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidReminderOverride** property.

[<2> Section 2.2.1.6:](#) In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidReminderPlaySound** property.

[<3> Section 2.2.1.7:](#) Office Outlook 2003, Office Outlook 2007, and Outlook 2010 support whatever the Windows API WINMM!PlaySound is able to play.

[<4> Section 2.2.1.7:](#) In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidReminderFileParameter** property.

[<5> Section 2.2.1.9:](#) Office Outlook 2003, Office Outlook 2007, and Outlook 2010 preserve the value if already set.

[<6> Section 2.2.2.3.1:](#) Office Outlook 2003 does not set the **PidLidTaskDueDate** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.5) for non-Task objects, so when a reminder signals for a flagable object, the "due in" time is calculated based on the value of the **PidLidReminderTime** property (section [2.2.1.4](#)). Office Outlook 2007 SP1 does set the **PidLidTaskDueDate** property for flaggable objects, so has a more intuitive "due in" time when the reminder signals. Office Outlook 2003, Office Outlook 2007, and Outlook 2010 do not set the **PidLidTaskDueDate** property for tasks when the user only specifies a reminder on a Task object without also specifying a due date. In other words, this property can be set on a Task object in the context of setting a due date. The task due date is independent of the signal time. See [\[MS-OXOTASK\]](#) for complete details about the conditions where the **PidLidTaskDueDate** property is set on a Task object.

[<7> Section 2.2.2.4:](#) In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidAutoStartCheck** property ([\[MS-OXPROPS\]](#) section 2.41).

<8> [Section 2.2.2.4](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidConferencingCheck** property ([\[MS-OXOCAL\]](#) section 2.2.1.50.2).

<9> [Section 3.1.3.1.1](#): Office Outlook 2003 follows the minimal reminder domain scope strategy. Exchange 2003 signals reminders only from the calendar and Tasks folders.

<10> [Section 3.1.3.1.1.1](#): Not supported in Office Outlook 2003. Office Outlook 2007 and Outlook 2010 set the **piReminderUpgradeTime** property (section [2.2.3.1](#)) to 0, when the "cleanreminders" feature is invoked, via command-line parameter, to clean the reminders search folder, after which all reminders would be eligible to signal again. Under normal operation, Office Outlook 2003, Office Outlook 2007, and Outlook 2010 do not change the **piReminderUpgradeTime** property after the value is initialized; they do this only when the "cleanreminders" command-line option is used with Office Outlook 2007 and Outlook 2010.

<11> [Section 3.1.4.1.2](#): Office Outlook 2003, Office Outlook 2007, Outlook 2010, Exchange 2007, and Exchange 2010 user interfaces set the **PidTagReplyTime** property ([\[MS-OXOFLAG\]](#) section 2.2.3.1) when setting a reminder on an already-flagged object. Setting the **PidTagReplyTime** property is not required for reminders to signal locally, but this property is used to transmit a reminder on a sent message. The Exchange 2003 user interface does not expose a way to set reminders on objects that are neither Calendar objects nor Task objects, so this constraint does not apply.

<12> [Section 3.1.4.1.2](#): Office Outlook 2003, Office Outlook 2007, and Outlook 2010 do not set all the specified properties at "reminder creation" time, because some of the properties were set in a previous operation (such as object creation or flagging for follow-up), or are set independent of the reminder itself (such as for Task objects), and the values did not change during the reminder creation process. Because Office Outlook 2003, Office Outlook 2007, and Outlook 2010 do not expose UI to just set a reminder on an e-mail message without also flagging, some properties, such as **PidLidFlagRequest** ([\[MS-OXOFLAG\]](#) section 2.2.1.9), happen to get set by Office Outlook 2003, Office Outlook 2007, and Outlook 2010 when a reminder is added to an e-mail message. These properties are not required for the reminder to function but are listed for completeness.

<13> [Section 3.1.4.1.3](#): The user interfaces of Exchange 2007 and Exchange 2010 set the **PidLidReminderTime** property (section [2.2.1.4](#)) to the start time for the next instance with an active reminder that has an end date in the future. This is true regardless of whether the Recurring Calendar object is created where part of the **instances** occur in the past, or when dismissing a reminder. When a reminder is dismissed (or a recurrence is created where part of the recurrence is in the past), the **PidLidReminderTime** property is updated to match the start time of the next instance with an active reminder. Office Outlook 2003, Office Outlook 2007, Outlook 2010, and the Exchange 2003 user interface set the **PidLidReminderTime** property to the start time of the first instance, and do not modify the **PidLidReminderTime** property during snooze or dismiss operations after the property is set on a Recurring Calendar object, even if the value has been modified. To clarify, Office Outlook 2003, Office Outlook 2007, Outlook 2010, and the Exchange 2003 user interface only set the **PidLidReminderTime** property when creating the Recurring Calendar object or modifying the series such that the series start date changes, and otherwise do not modify the property. In other words, the **PidLidReminderTime** property cannot be assumed to have a specific value for **Recurring objects**.

<14> [Section 3.1.4.1.3](#): The Exchange 2007 and Exchange 2010 user interfaces set the **PidLidReminderTime** property (section [2.2.1.4](#)) to the start time for the next instance with an active reminder that has an end date in the future. This is true regardless of whether the Recurring Calendar object is created where part of the instances occur in the past, or when dismissing a reminder. When a reminder is dismissed (or a recurrence is created where part of the recurrence is in the past), the **PidLidReminderTime** property is updated to match the start time of the next instance with an active reminder. Office Outlook 2003, Office Outlook 2007, Outlook 2010, and the Exchange 2003 user interface set the **PidLidReminderTime** property to the start time of the first

instance, and do not modify the **PidLidReminderTime** property during snooze or dismiss operations after the property is set on a Recurring Calendar object, even if the value has been modified. To clarify, Office Outlook 2003, Office Outlook 2007, Outlook 2010, and the Exchange 2003 user interface only set the **PidLidReminderTime** property when creating the Recurring Calendar object or modifying the series such that the series start date changes, and otherwise do not modify the property. In other words, the **PidLidReminderTime** property cannot be assumed to have a specific value for Recurring objects.

<15> [Section 3.1.4.3](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interface does not perform this processing.

<16> [Section 3.1.4.4.1](#): In addition to the properties specified, Office Outlook 2003 deletes the **PidTagReplyTime** property ([\[MS-OXOFLAG\]](#) section 2.2.3.1) for an object that is neither a Calendar object nor a Task object. Office Outlook 2007 deletes the **PidLidReminderTime** (section [2.2.1.4](#)), **PidLidReminderSignalTime** (section [2.2.1.2](#)), and **PidTagReplyTime** properties when removing the reminder from an object that is neither a Calendar object nor a Task object. For the remaining cases, Office Outlook 2003 and Office Outlook 2007 do not delete the properties **PidLidReminderTime** or **PidLidReminderSignalTime** when removing the reminder for calendar or Task objects; this is for user convenience to persist the signal time values even when the reminder is disabled.

<17> [Section 3.1.4.4.1](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidAutoStartCheck** property ([\[MS-OXPROPS\]](#) section 2.41).

<18> [Section 3.1.4.4.2](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidAutoStartCheck** property ([\[MS-OXPROPS\]](#) section 2.41).

<19> [Section 3.1.4.4.3](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidTaskResetReminder** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.6).

<20> [Section 3.1.4.5.1](#): The Exchange 2007 and Exchange 2010 user interface use stricter criteria when ignoring meeting-related objects, by ignoring messages with the **PidTagMessageClass** property ([\[MS-OXCMMSG\]](#) section 2.2.1.3) prefixed with "IPM.Schedule.meeting". Office Outlook 2007 and Outlook 2010 use slightly more lenient criteria: "IPM.Schedule" (note the missing trailing dot).

<21> [Section 3.1.4.5.1](#): Office Outlook 2003 does not ignore objects that have the **PidTagSwappedToDoStore** property ([\[MS-OXOFLAG\]](#) section 2.2.1.8) set. Office Outlook 2003 also does not ignore meeting-related objects, but this is not a problem because it uses the minimal reminder domain, which does not include **special folders** like Sent Items.

<22> [Section 3.1.4.5.2](#): Exchange 2003, Exchange 2007, and Exchange 2010 never read the **piReminderUpgradeTime** property (section [2.2.3.1](#)). Exchange 2003 does not auto-dismiss reminders that appear outside the minimal reminder domain. Exchange 2007 and Exchange 2010 do auto-dismiss said reminders, but only on initial transition to using the full reminder domain on a given mailbox store.

<23> [Section 3.1.4.5.3](#): Office Outlook 2003, Office Outlook 2007, and Outlook 2010 use **PidTagNormalizedSubject** ([\[MS-OXCMMSG\]](#) section 2.2.1.10), **PidLidFlagRequest** ([\[MS-OXOFLAG\]](#) section 2.2.1.9), and **PidLidLocation** ([\[MS-OXOCAL\]](#) section 2.2.1.4). Office Outlook 2007 and Outlook 2010 use the **PidLidTaskDueDate** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.5).

<24> [Section 3.1.4.5.3](#): Office Outlook 2003 displays DueIn "Now" when first signaling a reminder for a task or flagged object; Office Outlook 2007 and Outlook 2010 display a more intuitive time-until-DueDate value for these object types. Office Outlook 2007 and Outlook 2010 use the **PidLidTaskDueDate** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.5) and the "end of workday" value

to determine the due time. Office Outlook 2003 and the Exchange 2003 user interface use the **PidLidReminderTime** property (section [2.2.1.4](#)) as the due time.

<25> [Section 3.1.4.5.3](#): Office Outlook 2003 uses the signal time as the "due time".

<26> [Section 3.1.4.5.3](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not use the **PidLidReminderOverride** (section [2.2.1.5](#)), **PidLidReminderPlaySound** (section [2.2.1.6](#)), or **PidLidReminderFileParameter** (section [2.2.1.7](#)) properties.

<27> [Section 3.1.4.5.3](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not use the **PidLidReminderOverride** (section [2.2.1.5](#)), **PidLidReminderPlaySound** (section [2.2.1.6](#)), or **PidLidReminderFileParameter** (section [2.2.1.7](#)) properties.

<28> [Section 3.1.4.5.3](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not use the **PidLidReminderOverride** (section [2.2.1.5](#)), **PidLidReminderPlaySound** (section [2.2.1.6](#)), or **PidLidReminderFileParameter** (section [2.2.1.7](#)) properties.

<29> [Section 3.1.4.5.3](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not use the **PidLidReminderOverride** (section [2.2.1.5](#)), **PidLidReminderPlaySound** (section [2.2.1.6](#)), or **PidLidReminderFileParameter** (section [2.2.1.7](#)) properties.

<30> [Section 3.1.4.6.3](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not set the **PidLidTaskResetReminder** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.6) when dismissing a reminder on a Task object. This means that Exchange 2003, Exchange 2007, and Exchange 2010 do not support dismissing reminders on single instances of Recurring Task objects. Office Outlook 2003, Office Outlook 2007, and Outlook 2010 do set the **PidLidTaskResetReminder** property.

<31> [Section 3.1.4.6.3](#): The Exchange 2003 user interface sets the **PidLidReminderSignalTime** property (section [2.2.1.2](#)) when dismissing Task objects. Exchange 2007 does not set the **PidLidReminderSignalTime** property when dismissing Task objects.

<32> [Section 3.1.4.8](#): The Exchange 2003 user interface sets these properties if the **PidLidReminderSet** property (section [2.2.1.1](#)) is **TRUE**.

<33> [Section 3.1.4.8](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidTaskResetReminder** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.6).

<34> [Section 3.1.4.8](#): In Exchange 2003, Exchange 2007, and Exchange 2010, the user interfaces do not honor or set the **PidLidTaskResetReminder** property ([\[MS-OXOTASK\]](#) section 2.2.2.2.6).

<35> [Section 4.6](#): Office Outlook 2003 uses a different format for this property stream and sets the **WriterVersion2** property to 0x00003008.

7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

8 Index

A

Abstract data model
 [server](#) 13
[Applicability](#) 8

C

[Capability negotiation](#) 8
[Change tracking](#) 39

D

Data model - abstract
 [server](#) 13

F

[Fields - vendor-extensible](#) 8

G

[Glossary](#) 5

I

[Implementer - security considerations](#) 34
[Index of security parameters](#) 34
[Informative references](#) 7
[Introduction](#) 5

M

Message processing
 [server](#) 20
Messages
 [Properties Used to Specify and/or Decode Reminders message](#) 9
 [Properties Used to Specify User Preferences that are Roamed on the Server message](#) 12
 [Shared Properties](#) 11
 [transport](#) 9

N

[Normative references](#) 6

O

Other local events
 [server](#) 20
[Overview \(synopsis\)](#) 7

P

[Parameters - security index](#) 34
[Preconditions](#) 8
[Prerequisites](#) 8
[Product behavior](#) 35

[Properties Used to Specify and/or Decode Reminders message](#) 9
[Properties Used to Specify User Preferences that are Roamed on the Server message](#) 12

R

References
 [informative](#) 7
 [normative](#) 6
[Relationship to other protocols](#) 7

S

Security
 [implementer considerations](#) 34
 [parameter index](#) 34
Sequencing rules
 [server](#) 20
Server
 [abstract data model](#) 13
 [message processing](#) 20
 [other local events](#) 20
 [overview](#) 13
 [sequencing rules](#) 20
 [timer events](#) 20
 [timers](#) 13
[Shared Properties message](#) 11
[Standards assignments](#) 8

T

Timer events
 [server](#) 20
Timers
 [server](#) 13
[Tracking changes](#) 39
[Transport](#) 9

V

[Vendor-extensible fields](#) 8
[Versioning](#) 8