

# [MS-OXORSS]: RSS Object Protocol Specification

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

**Preliminary Documentation.** This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final

documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Revised and edited technical content.
09/03/2008	1.02		Revised and edited technical content.
12/03/2008	1.03		Revised and edited technical content.
04/10/2009	2.0		Updated applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0	Major	Updated and revised the technical content.
02/10/2010	4.1	Minor	Updated the technical content.
05/05/2010	5.0	Major	Updated and revised the technical content.
08/04/2010	5.1	Minor	Clarified the meaning of the technical content.
11/03/2010	5.1	No change	No changes to the meaning, language, or formatting of the technical content.
03/18/2011	5.1	No change	No changes to the meaning, language, and formatting of the technical content.
08/05/2011	5.1	No change	No changes to the meaning, language, or formatting of the technical content.
10/07/2011	5.2	Minor	Clarified the meaning of the technical content.
01/20/2012	6.0	Major	Significantly changed the technical content.
04/27/2012	6.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	6.0	No change	No changes to the meaning, language, or formatting of the technical content.

Preliminary

# Table of Contents

<b>1 Introduction .....</b>	<b>6</b>
1.1 Glossary .....	6
1.2 References.....	6
1.2.1 Normative References .....	7
1.2.2 Informative References .....	7
1.3 Overview .....	7
1.4 Relationship to Other Protocols.....	8
1.5 Prerequisites/Preconditions .....	8
1.6 Applicability Statement.....	8
1.7 Versioning and Capability Negotiation.....	8
1.8 Vendor-Extensible Fields.....	8
1.9 Standards Assignments .....	8
<b>2 Messages.....</b>	<b>9</b>
2.1 Transport.....	9
2.2 Message Syntax .....	9
2.2.1 RSS Object-Specific Properties .....	9
2.2.1.1 PidLidPostRssChannelLink Property .....	9
2.2.1.2 PidLidPostRssItemLink Property .....	9
2.2.1.3 PidLidPostRssItemHash Property.....	9
2.2.1.4 PidLidPostRssItemGuid Property .....	10
2.2.1.5 PidLidPostRssChannel Property .....	10
2.2.1.6 PidLidPostRssItemXml Property .....	10
2.2.1.7 PidLidPostRssSubscription Property .....	10
2.2.1.8 PidTagMessageDeliveryTime Property.....	10
2.2.2 Additional Property Constraints .....	11
2.2.2.1 Attachment Objects .....	11
2.2.2.1.1 Full Article Attachment Objects .....	11
2.2.2.1.2 Enclosure Attachment Objects .....	11
2.2.2.1.3 Other Attachment Objects .....	11
2.2.2.2 PidNameExchangeJunkEmailMoveStamp Property .....	11
2.2.2.3 PidTagMessageClass Property.....	11
2.2.2.4 PidTagSenderName Property.....	11
2.2.2.5 PidTagSenderEmailAddress Property .....	12
2.2.2.6 PidTagSentRepresentingName Property .....	12
2.2.2.7 PidTagSentRepresentingEmailAddress Property .....	12
2.2.2.8 Recipients.....	12
<b>3 Protocol Details.....</b>	<b>13</b>
3.1 Client Details.....	13
3.1.1 Abstract Data Model .....	13
3.1.2 Timers .....	13
3.1.3 Initialization .....	13
3.1.4 Higher-Layer Triggered Events.....	13
3.1.4.1 Creation of an RSS Object .....	13
3.1.4.2 Modification of an RSS Object .....	13
3.1.4.3 Deletion of an RSS Object.....	13
3.1.5 Message Processing Events and Sequencing Rules.....	14
3.1.6 Timer Events .....	14
3.1.7 Other Local Events .....	14

3.2	Server Details .....	14
3.2.1	Abstract Data Model .....	14
3.2.2	Timers .....	14
3.2.3	Initialization .....	14
3.2.4	Higher-Layer Triggered Events .....	14
3.2.5	Message Processing Events and Sequencing Rules .....	14
3.2.6	Timer Events .....	14
3.2.7	Other Local Events .....	15
<b>4</b>	<b>Protocol Examples .....</b>	<b>16</b>
<b>5</b>	<b>Security .....</b>	<b>20</b>
5.1	Security Considerations for Implementers .....	20
5.2	Index of Security Parameters .....	20
<b>6</b>	<b>Appendix A: Product Behavior .....</b>	<b>21</b>
<b>7</b>	<b>Change Tracking .....</b>	<b>22</b>
<b>8</b>	<b>Index .....</b>	<b>23</b>

# 1 Introduction

The RSS Object Protocol enables representation of an item that is from a news feed. This protocol extends the Message and Attachment Object Protocol, which is described in [\[MS-OXCMMSG\]](#).

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. Sections 1.5 and 1.9 are also normative but cannot contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**Coordinated Universal Time (UTC)**  
**handle**  
**XML**

The following terms are defined in [\[MS-OXGLOS\]](#):

**atom feed**  
**Attachment object**  
**Folder object**  
**Mail User Agent (MUA)**  
**Message object**  
**named property**  
**property ID**  
**Really Simple Syndication (RSS)**  
**recipient**  
**remote operation (ROP)**  
**ROP request**  
**ROP response**  
**RSS item**  
**RSS object**  
**Uniform Resource Locator (URL)**  
**XML element**

The following terms are specific to this document:

**enclosure:** An XML element that is in a feed and contains information such as a URL for a file, typically a media file, that is associated with an RSS item or Atom entry, for example, a podcast.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the technical documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol Specification](#)".

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC4287] Nottingham, M., and Sayre, E.R., "The Atom Syndication Format", RFC 4287, December 2005, <http://www.ietf.org/rfc/rfc4287.txt>

[RSS2.0] Winer, D., "RSS 2.0 Specification", Fall 2002, version 2.0.1: July 2003, <http://cyber.law.harvard.edu/rss/rss.html>

### 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Algorithm](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

### 1.3 Overview

The RSS Object Protocol allows representation of an item from either an **RSS** feed or an **atom feed** for viewing by the user. Items from the feed are in **XML** format. This protocol enables a client to convert the XML of an **RSS item**, described in [\[RSS2.0\]](#), or an atom entry, described in [\[RFC4287\]](#), to properties on an **RSS object**. In addition to the XML conversion, the entire XML content of the RSS item or atom entry is saved in its own property on the RSS object.

The RSS Object Protocol extends the Message and Attachment Object Protocol in that it defines new properties on a **Message object** and adds constraints to the existing properties of a Message object. For information about the Message and Attachment Object Protocol, see [\[MS-OXCMSG\]](#).

## 1.4 Relationship to Other Protocols

The RSS Object Protocol has the same dependencies as the Message and Attachment Object Protocol, as described in [\[MS-OXCMSG\]](#).

The RSS Object Protocol is a peer of the E-Mail Object Protocol and uses a subset of the properties that are described in [\[MS-OXOMSG\]](#).

## 1.5 Prerequisites/Preconditions

The RSS Object Protocol has the same prerequisites and preconditions as the Message and Attachment Object Protocol, as specified in [\[MS-OXCMSG\]](#).

## 1.6 Applicability Statement

A client can use this protocol to represent an item that is transmitted in a news feed format when the user subscribes to a news feed.

## 1.7 Versioning and Capability Negotiation

None.

## 1.8 Vendor-Extensible Fields

This protocol provides no extensibility beyond what is already specified in [\[MS-OXCMSG\]](#).

## 1.9 Standards Assignments

None.



## 2 Messages

### 2.1 Transport

The RSS Object Protocol uses the same underlying transport as that used by the Message and Attachment Object Protocol, as specified in [\[MS-OXCMSG\]](#).

### 2.2 Message Syntax

An RSS object can be created and modified by clients and servers. Except where noted below, this section defines constraints under which both clients and servers operate.

Clients operate on an RSS object by using the Message and Attachment Object Protocol, as specified in [\[MS-OXCMSG\]](#). The manner in which a server operates on an RSS object is implementation-dependent, but the results of any such operations MUST be exposed to clients in a manner that is consistent with the RSS Object Protocol.

Unless otherwise specified in sections [2.2.1](#) and [2.2.2](#), an RSS object adheres to all property constraints, as specified in both [\[MS-OXPROPS\]](#) and [\[MS-OXCMSG\]](#). An RSS object can also contain other properties, but these properties have no impact on the RSS Object Protocol.

The values of the properties specified in sections [2.2.1](#) and [2.2.2](#) are taken from the **XML elements** of the RSS feed or atom feed. For details about the XML formats of the RSS feed and the atom feed, see [\[RSS2.0\]](#) and [\[RFC4287\]](#), respectively.

#### 2.2.1 RSS Object-Specific Properties

The properties that are specific to RSS objects are defined in section [2.2.1.1](#) through section [2.2.1.8](#).

##### 2.2.1.1 PidLidPostRssChannelLink Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidPostRssChannelLink** property ([\[MS-OXPROPS\]](#) section 2.205) contains the **URL** of the RSS feed or atom feed from which the XML file came.

##### 2.2.1.2 PidLidPostRssItemLink Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidPostRssItemLink** property ([\[MS-OXPROPS\]](#) section 2.208) contains the URL of the item or entry. For an RSS item, this property is set to the value of the **link** child element of the **item** element. For an atom entry, the following applies:

- If the **rel** attribute is not present, or if it is present and set to "alternate", then this property is set to the value of the **href** attribute.
- If the **rel** attribute is present and set to anything besides "alternate", then the **PidLidPostRssItemLink** property is not set.

##### 2.2.1.3 PidLidPostRssItemHash Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidPostRssItemHash** property ([\[MS-OXPROPS\]](#) section 2.207) contains a hash of the XML from the RSS feed or the atom feed. The hash is computed by using an implementation-dependent algorithm and is used to quickly determine whether two items are different.

#### 2.2.1.4 PidLidPostRssItemGuid Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidPostRssItemGuid** property ([\[MS-OXPROPS\]](#) section 2.206) contains a unique identifier for the object.

This property is set as follows:

- For an RSS item, this property is set to the value of the **GUID** element or the **link** element.
- For an atom entry, this property is set to the value of the **id** element. If the **id** element is not present, this property is set to the value of the **href** attribute of the **link** element.

#### 2.2.1.5 PidLidPostRssChannel Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidPostRssChannel** property ([\[MS-OXPROPS\]](#) section 2.204) contains the title of the atom feed or the RSS feed. For an atom feed, this property is set to the value of the **title** child element of the **feed** element. For an RSS feed, this property is set to the value of the **title** child element of the **channel** element.

#### 2.2.1.6 PidLidPostRssItemXml Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidPostRssItemXml** property ([\[MS-OXPROPS\]](#) section 2.209) contains either the contents of the **item** element and all of its child elements from an RSS feed or the contents of the **entry** element and all of its child elements from an atom feed.

#### 2.2.1.7 PidLidPostRssSubscription Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidLidPostRssSubscription** property ([\[MS-OXPROPS\]](#) section 2.210) contains the user's preferred name for the subscription.

#### 2.2.1.8 PidTagMessageDeliveryTime Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagMessageDeliveryTime** property ([\[MS-OXPROPS\]](#) section 2.856) specifies the posting date, in **Coordinated Universal Time (UTC)**, of the item or entry. This property is optional.

This property is set as follows:

- For an RSS item, this property is set to the value of the **date** element or the **pubDate** element. If neither of these elements is present in the RSS item, this property is set to the value of the **lastBuildDate** element.

- For an atom entry, this property is set to the value of the **modified**, **issued**, **updated**, or **published** element. If none of these elements is present under the **entry** element, then the **modified** element or the **updated** element that is under the **feed** element is used.
- This property can be set to the current time if none of the specified elements exist in the RSS item or the atom entry.

## 2.2.2 Additional Property Constraints

Additional constraints beyond those specified in [\[MS-OXCMMSG\]](#), [\[MS-OXOMSG\]](#), and [\[MS-OXCSPAM\]](#) are specified in section [2.2.2.1](#) through section [2.2.2.8](#).

### 2.2.2.1 Attachment Objects

#### 2.2.2.1.1 Full Article Attachment Objects

A full article **Attachment object** contains the contents of the linked document. Its **PidTagAttachMethod** property ([\[MS-OXCMMSG\]](#) section 2.2.2.9) MUST be set to 0x00000001 (afByValue). The **PidLidPostRssItemLink** property (section [2.2.1.2](#)) MUST be set to the URL from which the document was downloaded.

An RSS object MUST NOT have more than one full article Attachment object.

#### 2.2.2.1.2 Enclosure Attachment Objects

An enclosure Attachment object contains the contents of an **enclosure**. For an atom entry, the enclosure is a file referenced in the **href** attribute of a **link** element that has its **rel** attribute set to "enclosure". For an RSS item, the enclosure is a file referenced in the **enclosure** element.

An enclosure Attachment object MUST have the **PidTagAttachMethod** property ([\[MS-OXCMMSG\]](#) section 2.2.2.9) set to 0x00000001 (afByValue). The **PidLidPostRssItemLink** property (section [2.2.1.2](#)) MUST be set to the URL from which the enclosure was downloaded.

#### 2.2.2.1.3 Other Attachment Objects

An RSS object MUST NOT have Attachment objects other than full article Attachment objects and enclosure Attachment objects.

#### 2.2.2.2 PidNameExchangeJunkEmailMoveStamp Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameExchangeJunkEmailMoveStamp** property ([\[MS-OXCSPAM\]](#) section 2.2.1.2) MUST be set on all RSS objects.

#### 2.2.2.3 PidTagMessageClass Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagMessageClass** ([\[MS-OXCMMSG\]](#) section 2.2.1.3) property specifies the type of the Message object. The value MUST be "IPM.Post.RSS" or begin with "IPM.Post.RSS.".

#### 2.2.2.4 PidTagSenderName Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagSenderName** property ([\[MS-OXOMSG\]](#) section 2.2.1.48) contains origination information about the RSS object.

This property is set as follows:

- For an RSS item, this property is set to the value of the **author**, **publisher**, or **title** element.
- For an atom entry, this property is set to the value of the **name** or **title** element.
- If none of the specified elements exist in the RSS item or the atom entry, this property is set to an empty string.

#### 2.2.2.5 PidTagSenderEmailAddress Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagSenderEmailAddress** property ([\[MS-OXOMSG\]](#) section 2.2.1.46) contains the value of the **email** child element of the **author** element of an atom entry. If the **email** element is not present, this property is set to an empty string. This property does not apply to an RSS item.

#### 2.2.2.6 PidTagSentRepresentingName Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagSentRepresentingName** property ([\[MS-OXOMSG\]](#) section 2.2.1.54) contains origination information about the RSS object.

This property is set as follows:

- For an RSS item, this property is set to the value of the **author**, **publisher**, or **title** element.
- For an atom entry, this property is set either to the value of the **title** element or to the value of the **name** child element of the **author** element.
- If none of the specified elements exist in the RSS item or the atom entry, this property is set to an empty string.

#### 2.2.2.7 PidTagSentRepresentingEmailAddress Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagSentRepresentingEmailAddress** property ([\[MS-OXOMSG\]](#) section 2.2.1.52) contains the contents of the **email** child element of the **author** element of an atom entry. If the **email** element is not present, this property is set to an empty string. This property does not apply to an RSS item.

#### 2.2.2.8 Recipients

An RSS object MUST NOT have **recipients (1)**.

## 3 Protocol Details

### 3.1 Client Details

The client creates and manipulates an RSS object and in all other ways operates within the client role as specified in [\[MS-OXCMSG\]](#).

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

This protocol uses the abstract data model that is specified in [\[MS-OXCMSG\]](#) section 3.1.1 with the following adaptations:

- The RSS object is an extension of the Message object.
- An RSS object is created in a **Folder object** that has a container class of "IPF.Note.OutlookHomepage" unless the **Mail User Agent (MUA)** explicitly specifies otherwise.

#### 3.1.2 Timers

None.

#### 3.1.3 Initialization

None.

#### 3.1.4 Higher-Layer Triggered Events

##### 3.1.4.1 Creation of an RSS Object

When the user subscribes to a news feed, the client creates an RSS object by creating a Message object, as specified in [\[MS-OXCMSG\]](#), sets properties on the RSS object in accordance with the requirements in section [2.2](#), and saves the resulting RSS object as specified in [\[MS-OXCMSG\]](#). In particular, the **PidNameExchangeJunkEmailMoveStamp** property (section [2.2.2.2](#)) MUST be set before the RSS object is saved the first time.

##### 3.1.4.2 Modification of an RSS Object

When the user updates a subscription to a news feed, the client first opens the RSS object in the same way that it opens any Message object, as specified in [\[MS-OXCMSG\]](#). The client then modifies any properties in accordance with the requirements in section [2.2](#) and saves the RSS object as specified in [\[MS-OXCMSG\]](#).

##### 3.1.4.3 Deletion of an RSS Object

When the user deletes a subscription to a news feed, the client deletes the RSS object in the same way that it deletes any Message object, as specified in [\[MS-OXCFC\]](#).

### 3.1.5 Message Processing Events and Sequencing Rules

None.

### 3.1.6 Timer Events

None.

### 3.1.7 Other Local Events

None.

## 3.2 Server Details

The server processes a client's requests regarding an RSS object and in all other ways operates within the server role as specified in [\[MS-OXCMSG\]](#).

### 3.2.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

This protocol uses the abstract data model that is specified in [\[MS-OXCMSG\]](#) section 3.2.1 with the following adaptations:

- The RSS object is an extension of the Message object.
- An RSS object is created in a Folder object that has a container class of "IPF.Note.OutlookHomepage" unless the MUA explicitly specifies otherwise.

### 3.2.2 Timers

None.

### 3.2.3 Initialization

None.

### 3.2.4 Higher-Layer Triggered Events

None.

### 3.2.5 Message Processing Events and Sequencing Rules

The server responds to client requests as specified in [\[MS-OXCMSG\]](#).

### 3.2.6 Timer Events

None.

### 3.2.7 Other Local Events

None.

## 4 Protocol Examples

A user subscribes to an RSS feed. The client polls the feed and finds a new item. The following is a description of what a client might do to accomplish the user's intentions and describes the responses a server might return. For information about the **remote operations (ROPs)** described in the example, see [\[MS-OXCPRPT\]](#) and [\[MS-OXCMMSG\]](#).

Before manipulating RSS objects, the client asks the server to map **named properties** to **property IDs** by sending a **RopGetPropertyIDsFromNames ROP request** ([\[MS-OXCROPS\]](#) section 2.2.8.1).

Property	Property set GUID	LID or property name
<b>PidLidPostRssChannel</b> (section <a href="#">2.2.1.5</a> )	{00062041-0000-0000-C000-000000000046}	0x00008904
<b>PidLidPostRssChannelLink</b> (section <a href="#">2.2.1.1</a> )	{00062041-0000-0000-C000-000000000046}	0x00008900
<b>PidLidPostRssItemGuid</b> (section <a href="#">2.2.1.4</a> )	{00062041-0000-0000-C000-000000000046}	0x00008903
<b>PidLidPostRssItemHash</b> (section <a href="#">2.2.1.3</a> )	{00062041-0000-0000-C000-000000000046}	0x00008902
<b>PidLidPostRssItemLink</b> (section <a href="#">2.2.1.2</a> )	{00062041-0000-0000-C000-000000000046}	0x00008901
<b>PidLidPostRssItemXml</b> (section <a href="#">2.2.1.6</a> )	{00062041-0000-0000-C000-000000000046}	0x00008905
<b>PidLidPostRssSubscription</b> (section <a href="#">2.2.1.7</a> )	{00062041-0000-0000-C000-000000000046}	0x00008906
<b>PidLidSideEffects</b> ( <a href="#">[MS-OXCMMSG]</a> section 2.2.1.16)	{00062008-0000-0000-C000-000000000000}	0x00008510



Property	Property set GUID	LID or property name
	46}	
<b>PidNameExchangeJunkEmailMoveStamp</b> ([MS-OXCSPAM] section 2.2.1.2)	{00020329-0000-0000-C000-000000000046}	HTTP://schemas.microsoft.com/exchange/junkemail/movestamp

The server sends a **RopGetPropertyIDsFromNames ROP response** with the following property IDs, which will be used in the example that follows. (The actual property IDs are at the discretion of the server.)

Property	Property ID
<b>PidLidPostRssChannel</b>	0x8318
<b>PidLidPostRssChannelLink</b>	0x8314
<b>PidLidPostRssItemGuid</b>	0x8317
<b>PidLidPostRssItemHash</b>	0x8316
<b>PidLidPostRssItemLink</b>	0x8315
<b>PidLidPostRssItemXml</b>	0x8319
<b>PidLidPostRssSubscription</b>	0x831A
<b>PidLidSideEffects</b>	0x81F8
<b>PidNameExchangeJunkEmailMoveStamp</b>	0x8415

To create an RSS object, the client uses the **RopCreateMessage ROP** ([MS-OXCROPS] section 2.2.6.2). The server returns a success code and a **handle** to the object.

After processing the contents of the RSS item, the client transmits the properties to the server by using the **RopSetProperties ROP** ([MS-OXCROPS] section 2.2.8.6). The properties that are set are shown in the following table.

Property	Property ID	Data type	Value
<b>PidLidPostRssChannel</b>	0x8318	0x001F (PtypString ([MS-OXCDATA] section 2.11.1))	Help and How-To for Contoso
<b>PidLidPostRssChannelLink</b>	0x8314	0x001F	HTTP://www.contoso.com
<b>PidLidPostRssItemGuid</b>	0x8317	0x001F	HTTP://www.contoso.com
<b>PidLidPostRssItemHash</b>	0x8316	0x0003 (PtypInteger32 ([MS-OXCDATA] section 2.11.1))	0xCD0E93CF

Property	Property ID	Data type	Value
<b>PidLidPostRssItemLink</b>	0x8315	0x001F	HTTP://www.contoso.com
<b>PidLidPostRssItemXml</b>	0x8319	0x001F	(See note 1 following the table.)
<b>PidLidPostRssSubscription</b>	0x831a	0x001F	Help and How-To for Contoso
<b>PidLidSideEffects</b>	0x81f8	0x0003	0x00000100
<b>PidTagHtml</b> ([MS-OXCMMSG] section 2.2.1.49.9)	0x1013	0x0102 ( <b>PtypBinary</b> ([MS-OXCADATA] section 2.11.1))	(See note 2 following the table.)
<b>PidTagClientSubmitTime</b> ([MS-OXOMSG] section 2.2.3.11)	0x0039	0x0040 ( <b>PtypTime</b> ([MS-OXCADATA] section 2.11.1))	High: 0x01C87A36 Low: 0xD74C8CC0 (2008/02/28 18:22:13.900)
<b>PidTagConversationTopic</b> ([MS-OXOMSG] section 2.2.1.5)	0x0070	0x001F	Learn to narrow your search criteria for better searches in Contoso
<b>PidTagInternetCodepage</b> ([MS-OXCMMSG] section 2.2.1.49.6)	0x3FDE	0x0003	0x0000FDE9
<b>PidTagMessageClass</b> ([MS-OXCMMSG] section 2.2.1.3)	0x001A	0x001F	"IPM.Post.RSS"
<b>PidTagMessageFlags</b> ([MS-OXCMMSG] section 2.2.1.6)	0x0E07	0x0003	Flags: 0x00000000 <none>
<b>PidTagNormalizedSubject</b> ([MS-OXCMMSG] section 2.2.1.10)	0x0E1D	0x001F	Learn to narrow your search criteria for better searches in Contoso
<b>PidTagSenderName</b> (section 2.2.2.4)	0x0C1A	0x001F	Help and How-To for Contoso
<b>PidTagSentRepresentingName</b> (section 2.2.2.6)	0x0042	0x001F	Help and How-To for Contoso
<b>PidTagSubjectPrefix</b> ([MS-OXCMMSG] section 2.2.1.9)	0x003D	0x001F	(null)
<b>PidNameExchangeJunkEmailMoveStamp</b>	0x8415	0x0003	0x802454D1

When the client has made all its changes to the item, it commits the properties to the server by using the **RopSaveChangesMessage** ROP ([MS-OXCROPS] section 2.2.6.3) and then releases the RSS object by using the **RopRelease** ROP ([MS-OXCROPS] section 2.2.15.3). The values of some properties will change during the processing of the **RopSaveChangesMessage** ROP, but the properties specified in this document will not change.

**Note 1:** The **PidLidPostRssItemXml** property contains the following text.

```
<?xml version="1.0"?>
```

```
<item>
<title>Learn to narrow your search criteria for better searches in Contoso</title>
<description>Instant Search can help you find information in a flash.</description>
<link>http://www.contoso.com</link>
</item>
```

**Note 2:** The **PidTagHtml** property contains the following text, encoded into binary as described in [\[MS-OXBBODY\]](#).

```
<html>
  <body>
    <table>
      <tr>
        <td>Instant Search can help you find information in a flash.</td>
      </tr>
    </table>
    <p><BR/><A HREF="http://www.contoso.com">View article...</A></p>
  </body>
</html>
```

## 5 Security

### 5.1 Security Considerations for Implementers

There are no special security considerations specific to this protocol. General security considerations that pertain to the underlying transport apply as described in [\[MS-OXCMG\]](#).

### 5.2 Index of Security Parameters

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2003
- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 2013 Preview
- Microsoft® Office Outlook® 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Outlook® 2010
- Microsoft® Outlook® 2013 Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

Abstract data model

[client](#) 13  
[server](#) 14

Additional property constraints

[PidNameExchangeJunkEmailMoveStamp property](#) 11  
[PidTagMessageClass property](#) 11  
[PidTagSenderEmailAddress property](#) 12  
[PidTagSenderName property](#) 11  
[PidTagSentRepresentingEmailAddress property](#) 12  
[PidTagSentRepresentingName property](#) 12  
[Recipients](#) 12

[Additional Property Constraints message](#) 11

[Applicability](#) 8

### C

[Capability negotiation](#) 8

[Change tracking](#) 22

Client

[abstract data model](#) 13  
[initialization](#) 13  
[message processing](#) 14  
[other local events](#) 14  
[overview](#) 13  
[sequencing rules](#) 14  
[timer events](#) 14  
[timers](#) 13

Client - higher-layer triggered events

[creation of an RSS object](#) 13  
[deletion of an RSS object](#) 13  
[modification of an RSS object](#) 13

### D

Data model - abstract

[client](#) 13  
[server](#) 14

### E

[Examples](#) 16

### F

[Fields - vendor-extensible](#) 8

### G

[Glossary](#) 6

### H

Higher-layer triggered events

[server](#) 14

Higher-layer triggered events - client

[creation of an RSS object](#) 13  
[deletion of an RSS object](#) 13  
[modification of an RSS object](#) 13

### I

[Implementer - security considerations](#) 20

[Index of security parameters](#) 20

[Informative references](#) 7

Initialization

[client](#) 13  
[server](#) 14

[Introduction](#) 6

### M

Message processing

[client](#) 14  
[server](#) 14

Messages

[Additional Property Constraints](#) 11  
[RSS Object-Specific Properties](#) 9  
[syntax](#) 9  
[transport](#) 9

### N

[Normative references](#) 7

### O

Other local events

[client](#) 14  
[server](#) 15  
[Overview \(synopsis\)](#) 7

### P

[Parameters - security index](#) 20

[PidLidPostRssChannel RSS object-specific property](#) 10

[PidLidPostRssChannelLink RSS object-specific property](#) 9

[PidLidPostRssItemGuid RSS object-specific property](#) 10

[PidLidPostRssItemHash RSS object-specific property](#) 9

[PidLidPostRssItemLink RSS object-specific property](#) 9

[PidLidPostRssItemXml RSS object-specific property](#) 10

[PidLidPostRssSubscription RSS object-specific property](#) 10

[PidNameExchangeJunkEmailMoveStamp property additional property constraints](#) 11

[PidTagMessageClass property additional property constraints](#) 11

[PidTagMessageDeliveryTime RSS object-specific property](#) 10

[PidTagSenderEmailAddress property additional property constraints](#) 12  
[PidTagSenderName property additional property constraints](#) 11  
[PidTagSentRepresentingEmailAddress property additional property constraints](#) 12  
[PidTagSentRepresentingName property additional property constraints](#) 12  
[Preconditions](#) 8  
[Prerequisites](#) 8  
[Product behavior](#) 21  
[Protocol examples](#) 16

## R

[Recipient additional property constraints](#) 12  
[References](#) 6  
    [informative](#) 7  
    [normative](#) 7  
[Relationship to other protocols](#) 8  
RSS object-specific properties  
    [PidLidPostRssChannel property](#) 10  
    [PidLidPostRssChannelLink property](#) 9  
    [PidLidPostRssItemGuid property](#) 10  
    [PidLidPostRssItemHash property](#) 9  
    [PidLidPostRssItemLink property](#) 9  
    [PidLidPostRssItemXml property](#) 10  
    [PidLidPostRssSubscription property](#) 10  
    [PidTagMessageDeliveryTime property](#) 10  
[RSS Object-Specific Properties message](#) 9

## S

Security  
    [implementer considerations](#) 20  
    [parameter index](#) 20  
Sequencing rules  
    [client](#) 14  
    [server](#) 14  
Server  
    [abstract data model](#) 14  
    [higher-layer triggered events](#) 14  
    [initialization](#) 14  
    [message processing](#) 14  
    [other local events](#) 15  
    [overview](#) 14  
    [sequencing rules](#) 14  
    [timer events](#) 14  
    [timers](#) 14  
[Standards assignments](#) 8  
[Syntax](#) 9

## T

Timer events  
    [client](#) 14  
    [server](#) 14  
Timers  
    [client](#) 13  
    [server](#) 14  
[Tracking changes](#) 22  
[Transport](#) 9

Triggered events - client  
    [creation of an RSS object](#) 13  
    [deletion of an RSS object](#) 13  
    [modification of an RSS object](#) 13  
Triggered events - higher-layer  
    [server](#) 14

## V

[Vendor-extensible fields](#) 8  
[Versioning](#) 8