

# [MS-OXOSFLD]: Special Folders Protocol Specification

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.msp>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Updated references to reflect date of initial release.
09/03/2008	1.02		Revised and edited technical content.
12/03/2008	1.03		Revised and edited technical content.
03/04/2009	1.04		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	3.1.0	Minor	Updated the technical content.
02/10/2010	3.2.0	Minor	Updated the technical content.
05/05/2010	3.3.0	Minor	Updated the technical content.
08/04/2010	3.3.0	No change	No changes to the meaning, language, or formatting of the technical content.
11/03/2010	3.3.0	No change	No changes to the meaning, language, or formatting of the technical content.

# Contents

<b>1 Introduction</b>	<b>5</b>
1.1 Glossary	5
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	8
1.3 Overview	8
1.4 Relationship to Other Protocols	11
1.5 Prerequisites/Preconditions	11
1.6 Applicability Statement	11
1.7 Versioning and Capability Negotiation	11
1.8 Vendor-Extensible Fields	11
1.9 Standards Assignments	11
<b>2 Messages</b>	<b>12</b>
2.1 Transport	12
2.2 Message Syntax	12
2.2.1 Binary Identification Properties	12
2.2.2 Format of PidTagAdditionalRenEntryIds	13
2.2.3 Format of PidTagAdditionalRenEntryIdsEx	13
2.2.3.1 PersistData Block	13
2.2.3.2 PersistElement Block	14
2.2.4 Inbox Identification	15
2.2.5 PidTagContainerClass	15
<b>3 Protocol Details</b>	<b>17</b>
3.1 Common Details	17
3.1.1 Abstract Data Model	17
3.1.1.1 Folder Hierarchy	17
3.1.1.2 Search Criteria for Search Special Folders	18
3.1.2 Timers	20
3.1.3 Initialization	20
3.1.4 Higher-Layer Triggered Events	20
3.1.4.1 Folder Creation	20
3.1.4.1.1 Creating the Reminders Folder	20
3.1.4.1.2 Creating the To-Do Search Folder	22
3.1.4.1.3 Creating the Tracked Mail Processing Folder	24
3.1.4.1.4 Creating Other Special Folders	25
3.1.5 Message Processing Events and Sequencing Rules	25
3.1.6 Timer Events	25
3.1.7 Other Local Events	25
<b>4 Protocol Examples</b>	<b>26</b>
4.1 Opening a Special Folder	26
4.1.1 Client Request for Opening a Special Folder	26
4.1.2 Server Response for Opening a Special Folder	28
4.2 Creating a Special Folder	29
4.2.1 Client Request for Creating a Special Folder	29
4.2.2 Server Response for Creating a Special Folder	31
<b>5 Security</b>	<b>34</b>
5.1 Security Considerations for Implementers	34

5.2 Index of Security Parameters .....	34
<b>6 Appendix A: Product Behavior .....</b>	<b>35</b>
<b>7 Change Tracking.....</b>	<b>36</b>
<b>8 Index .....</b>	<b>37</b>

# 1 Introduction

The Special Folders protocol document specifies the following:

- The set of special containers shared by client and server implementations of this protocol.
- The specific protocol used to find and interact with each container.
- The type of objects stored in each container.

## 1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

**address book**  
**appointment**  
**Calendar folder**  
**Calendar object**  
**client-side rule**  
**Common Views folder**  
**complete flag**  
**Conflicts folder**  
**contact**  
**Contact object**  
**conversation action**  
**Deferred Action Folder (DAF)**  
**Deferred Action Message (DAM)**  
**Deferred Error Message (DEM)**  
**delegate**  
**Deleted Items folder**  
**Drafts folder**  
**entry ID**  
**feed**  
**Finder folder**  
**folder**  
**folder associated information (FAI)**  
**folder ID (FID)**  
**Folder object**  
**free/busy**  
**header**  
**handle**  
**Inbox folder**  
**journal**  
**Journal object**  
**Junk E-mail folder**  
**Junk E-Mail rule**  
**little-endian**  
**locale**  
**message**  
**message class**  
**message ID (MID)**  
**Message object**  
**messaging object**  
**Note object**  
**Outbox folder**

**Personal Information Manager (PIM)**  
**property (1)**  
**property tag**  
**Receive folder**  
**recipient**  
**reminder**  
**remote operation (ROP)**  
**remote procedure call (RPC)**  
**restriction**  
**Root folder**  
**ROP request**  
**search criteria**  
**search folder**  
**Sent Items folder**  
**Server object**  
**Server object handle**  
**Server object handle table**  
**special folder**  
**store**  
**stream**  
**Store object**  
**synchronization**  
**Task object**

The following terms are specific to this document:

**Container class:** The value of the **PidTagContainerClass property** on a **folder**, which indicates the default **Message object** type for the **folder**.

**Conversation Action Settings folder:** The **special folder** that contains the **FAI messages** that are used to persist **conversation actions**.

**identification method:** The means by which an implementation locates or identifies a particular **special folder**.

**Local Failures folder:** The **special folder** that contains **messages** that indicate client-side **synchronization** failures.

**Notes folder:** The **special folder** that contains **Note objects**.

**Personal Views folder:** The **special folder** that contains the data for views defined by a particular user.

**Really Simple Syndication (RSS):** A Web content syndication format as described in [\[RSS2.0\]](#).

**Reminders folder:** The **special folder** that is a **search folder** that supports **reminder** functionality.

**RSS Feeds folder:** The **special folder** that contains **Really Simple Syndication (RSS) feed messages**.

**Server Failures folder:** The **special folder** that contains **messages** that indicate server-side **synchronization** failures.

**Suggested Contacts folder:** The **special folder** that contains **contacts** that are created when a **message recipient** is not in an **address book**.

**Sync Issues folder:** The **special folder** that contains other **folders** that contain **messages** that indicate particular issues encountered during **synchronization** between client and server.

**Tasks folder:** The **special folder** that contains **Task objects**.

**To-Do Search folder:** The **special folder** that is used to track **Task objects**.

**Top of Personal Folders folder:** The **special folder** that is the top **folder** of the inter-personal **message** hierarchy, which contains user data **folders**, including most **special folders**, such as **Inbox**, and so on.

**Tracked Mail Processing folder:** The **special folder** that contains objects flagged by the Send and Track feature.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-DTYP] Microsoft Corporation, "Windows Data Types", March 2007, <http://msdn.microsoft.com/en-us/library/cc230273.aspx>

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)", April 2008.

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)", April 2008.

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)", April 2008.

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)", April 2008.

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)", April 2008.

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol Specification](#)", April 2008.

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol Specification](#)", April 2008.

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol Specification](#)", April 2008.

[MS-OXCSYNC] Microsoft Corporation, "[Mailbox Synchronization Protocol Specification](#)", April 2008.

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)", April 2008.

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol Specification](#)", April 2008.

- [MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol Specification](#)", April 2008.
- [MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol Specification](#)", April 2008.
- [MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol Specification](#)", April 2008.
- [MS-OXOJRN] Microsoft Corporation, "[Journal Object Protocol Specification](#)", April 2008.
- [MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)", April 2008.
- [MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol Specification](#)", April 2008.
- [MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol Specification](#)", April 2008.
- [MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol Specification](#)", April 2008.
- [MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol Specification](#)", April 2008.
- [MS-OXORULE] Microsoft Corporation, "[E-Mail Rules Protocol Specification](#)", April 2008.
- [MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol Specification](#)", April 2008.
- [MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol Specification](#)", April 2008.
- [MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol Specification](#)", April 2008.
- [MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)", April 2008.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>
- [RSS2.0] Winer, D., "RSS 2.0 Specification", July 2003, <http://cyber.law.harvard.edu/rss/rss.html>

### 1.2.2 Informative References

- [MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

### 1.3 Overview

The Special Folders protocol extends the Folder Object protocol [[MS-OXCFOLD](#)], which provides clients with a general-purpose organizational mechanism based on **Folder objects**. Clients have the option of storing particular types of data, such as e-mail **messages** or **Personal Information Manager (PIM)** objects such as **appointments** and **contacts**, in particular **folders**. The Special Folders protocol specifies the default set of such folders that the server supports, as well as other **special folders** that support specific folders for certain types of application data, such as **reminders** and views.

Interaction with special folders begins with a determination of whether or not a particular special Folder exists within an opened **Store object**, which is specified by the Store Object protocol [[MS-OXCSTOR](#)]. This determination is based on the following criteria—note that all **properties** referenced in this and subsequent sections are specified by [[MS-OXPROPS](#)]:

- The appropriate **identification method** has been established for the given special folder.
- The special folder exists in the store object.



- The value of the [PidTagContainerClass](#) property of the folder is set to the value defined for that particular special folder.

If these criteria are not met for a particular special folder, an implementation uses the Folder Object protocol to create the folder or, in the case of the **Root folder**, returns an error.

An important aspect of the Special Folders protocol is the method used to identify special folders after they are created. Following these identification methods ensures that the same special folder will continue to be used for a particular type of **messaging object** after the folder is created. The identification method for each special folder is specified in section [2.2](#).

The following table lists the set of folders that are special folders, along with the **Container class** for each folder where applicable, and references for further information.

Special folder name	Description	Container class	Related information
Root	The <b>store</b> hierarchy's top-level folder, which contains all other Folder objects in that store.	None	[MS- OXCSTOR]
<b>Finder</b>	Contains the default <b>search folders</b> .	None	<a href="#">[MS- OXOSRCH]</a>
Freebusy Data	Contains the <b>free/busy</b> data of the owner.	None	<a href="#">[MS- OXOPFB]</a>
<b>Top of Personal Folders</b>	The top folder of the interpersonal message hierarchy, which contains user data folders, including most special folders, such as the <b>Inbox</b> .	None	[MS- OXCSTOR]
<b>Deleted Items</b>	The default location for objects that have been deleted.	"IPF.Note"	<a href="#">[MS- OXOMSG]</a>
<b>Outbox</b>	Outgoing e-mail <b>Message objects</b> are placed in this folder at submit time (when the Message object is sent).	"IPF.Note"	[MS- OXOMSG]
<b>Sent Items</b>	The default location in which copies of e-mail Message objects are placed after they have been submitted (sent).	"IPF.Note"	[MS- OXOMSG]
Inbox	The default location for incoming (received) e-mail Message objects.	"IPF.Note"	[MS- OXOMSG]
<b>Common Views</b>	Contains the data for default views that are standard for the messagestore and that can be used by any user of a client accessing the messagestore.	None	None
<b>Personal Views</b>	Contains the data for views defined by a particular user.	None	None
<b>Deferred Action</b>	Contains the <b>Deferred Action Messages (DAM)</b> and <b>Deferred</b>	None	<a href="#">[MS- OXORULE]</a>

Special folder name	Description	Container class	Related information
	<b>Error Messages (DEM)</b> that resulted from the execution of <b>client-side rules</b>		
<b>Calendar</b>	Contains <b>Calendar objects</b> , such as appointments	"IPF.Appointment"	<a href="#">[MS-OXOCAL]</a>
Contacts	Contains <b>Contact objects</b> .	"IPF.Contact"	<a href="#">[MS-OXOCNTC]</a>
<b>Journal</b>	Contains <b>Journal objects</b> .	"IPF.Journal"	<a href="#">[MS-OXOJRNL]</a>
<b>Notes</b>	Contains <b>Note objects</b>	"IPF.StickyNote"	<a href="#">[MS-OXONOTE]</a>
<b>Tasks</b>	Contains <b>Task objects</b> .	"IPF.Task"	<a href="#">[MS-OXOTASK]</a>
<b>Reminders</b>	Search folder that supports reminder functionality.	"Outlook.Reminder"	<a href="#">[MS-OXORMDR]</a>
<b>Drafts</b>	The default location for composed e-mail Message objects that have been saved but not sent.	"IPF.Note"	[MS-OXOMSG]
<b>Conflicts</b>	Contains Message objects that indicate synchronization conflicts between client and server.	"IPF.Note"	<a href="#">[MS-OXCSYNC]</a>
<b>Sync Issues</b>	Contains folders that contain messages that indicate particular issues encountered during synchronization between client and server.	"IPF.Note"	[MS-OXCSYNC]
<b>Local Failures</b>	Contains messages that indicate client-side synchronization failures.	"IPF.Note"	[MS-OXCSYNC]
<b>Server Failures</b>	Contains messages that indicate server-side synchronization failures.	"IPF.Note"	[MS-OXCSYNC]
<b>Junk E-mail</b>	Default location for e-mail Message objects determined to be Junk e-mail by a <b>Junk E-Mail rule</b> .	"IPF.Note"	<a href="#">[MS-OXCSPAM]</a>
<b>RSS Feeds</b>	Contains <b>Really Simple Syndication (RSS) feed</b> messages.	"IPF.Note.OutlookHomepage"	<a href="#">[MS-OXORSS]</a>
<b>Tracked Mail Processing</b>	Search folder that contains flagged objects.	"IPF.Note"	<a href="#">[MS-OXOFLAG]</a>
<b>To-Do Search</b>	Search folder used for tracking task objects.	"IPF.Task"	[MS-OXOTASK]

Special folder name	Description	Container class	Related information
<b>Conversation Action Settings</b>	Contains <b>FAI</b> messages that are used for persisting <b>conversation actions</b> .	"IPF.Configuration"	<a href="#">[MS-OXOCFG]</a>

#### 1.4 Relationship to Other Protocols

The Special Folders protocol specification relies on an understanding of how to work with stores, folders, and properties (for more details see [\[MS-OXCSTOR\]](#), [\[MS-OXCFOLD\]](#), and [\[MS-OXCPRPT\]](#)), and how these objects are synchronized between the client and server.

#### 1.5 Prerequisites/Preconditions

The Special Folders protocol specification assumes that the messaging client has previously logged on to the messaging server and has acquired a **handle** to the store in which the special folders are located, as specified in [\[MS-OXCSTOR\]](#).

#### 1.6 Applicability Statement

The Special Folders protocol can be used to locate existing or to store newly created well-known object types.

#### 1.7 Versioning and Capability Negotiation

None.

#### 1.8 Vendor-Extensible Fields

None.

#### 1.9 Standards Assignments

None.

## 2 Messages

### 2.1 Transport

The specific formats for the underlying messages that are sent to and received from the server are specified in [\[MS-OXCSTOR\]](#) for Store objects, [\[MS-OXCFOLD\]](#) for Folder objects, and [\[MS-OXCPRPT\]](#) for properties.

### 2.2 Message Syntax

The identification method for a special folder consists of one of the following:

- **Folder IDs (FIDs)** returned from [RopLogon](#), as specified in [\[MS-OXCSTOR\]](#). These FIDs identify the following folders:
  - Root folder
  - Finder folder
  - Top of Personal Folders folder
  - Deleted Items folder
  - Outbox folder
  - Sent Items folder
  - Inbox folder
  - Common Views folder
  - Personal Views folder
  - Deferred Action folder
- Binary properties that each contains only a single **entry ID**.
- [PidTagAdditionalRenEntryIds](#), a **PtypMultipleBinary** property in which each indexed value contains an entry ID.
- [PidTagAdditionalRenEntryIdsEx](#), a **PtypBinary** property in which the binary data is in its own format, allowing for multiple entry IDs.
- [PidTagFreeBusyEntryIds](#), a **PtypMultipleBinary** property in which indexed value 3 contains the entry ID for the Freebusy Data folder. For more details about this property, see [\[MS-OXOPFFB\]](#).
- Use of the Store Object protocol to get or set the identity of the Inbox folder.

Unless otherwise noted, the entry IDs that are returned by these identification methods MUST be converted to FIDs, as specified in [\[MS-OXCDATA\]](#), by using [RopIdFromLongTermId](#), as defined in [\[MS-OXCROPS\]](#), before they are used to open a special folder that uses the Folder Object protocol.

#### 2.2.1 Binary Identification Properties

The binary properties, each of which contains only a single entry ID, are read or written by using the property and Stream Object protocol. The following table lists these properties.

Property name	Folder ID
<a href="#">PidTagIpmAppointmentEntryId</a>	Calendar
<a href="#">PidTagIpmContactEntryId</a>	Contacts
<a href="#">PidTagIpmJournalEntryId</a>	Journal
<a href="#">PidTagIpmNoteEntryId</a>	Notes
<a href="#">PidTagIpmTaskEntryId</a>	Tasks
<a href="#">PidTagRemindersOnlineEntryId</a>	Reminders
<a href="#">PidTagIpmDraftsEntryId</a>	Drafts

These properties are read from/written to the Inbox folder or Root folder. The implementation MUST use the Inbox folder when the store is that of the primary messaging user, and it MUST use the Root folder when the store is that of a **delegate** user. These user roles are specified in [\[MS-OXODLGT\]](#).

## 2.2.2 Format of PidTagAdditionalRenEntryIds

This **MultiBinary** property on the Inbox folder contains the entry IDs for several special folders. The following table lists the index into the [PidTagAdditionalRenEntryIds](#) value for each of these special folders.

Index	Folder identified
0x0000	Conflicts
0x0001	Sync Issues
0x0002	Local Failures
0x0003	Server Failures
0x0004	Junk E-mail
0x0005	None. Reserved for use by the Spam Confidence Level, Allow and Block Lists protocol <a href="#">[MS-OXCSPAM]</a> and the Phishing Warning protocol <a href="#">[MS-OXPHISH]</a> .

If the implementation encounters an unknown index value in [PidTagAdditionalRenEntryIds](#), the implementation MUST ignore and preserve the data in the index entry ID.

## 2.2.3 Format of PidTagAdditionalRenEntryIdsEx

Several of the special folder entry IDs are identified by this binary property on the Store object that contains the folders. If present, the value of this property MUST contain an array of blocks that contain the entry IDs for these folders, in the format specified in the following sections.

### 2.2.3.1 PersistData Block

Name	Type	Size	Description
<b>PersistID</b>	<b>WORD</b>	2	Type identifier value for this <b>PersistData</b> block. SHOULD be one of <b>PersistBlockType</b>

Name	Type	Size	Description
			values.
<b>DataElementsSize</b>	<b>WORD</b>	2	The size in <b>BYTES</b> of the <b>DataElements</b> field.
<b>DataElements</b>	Array of <b>PersistElement</b> blocks	variable	0 (zero) or more <b>PersistElement</b> blocks.

**PersistBlockType** values SHOULD be one of those listed in the following table. If a **PersistData** block is encountered where the **PersistID** value is not known to the implementation, the implementation MUST ignore that **PersistData** block and continue processing until either a **PERSIST\_SENTINEL PersistID** or the end of the **stream** is encountered. <1><2><3>

Name	Value	Description
RSF_PID_RSS_SUBSCRIPTION	0x8001	Indicates that this block contains data for the RSS Feeds folder.
RSF_PID_SEND_AND_TRACK	0x8002	Indicates that this block contains data for the Tracked Mail Processing folder.
RSF_PID_TODO_SEARCH	0x8004	Indicates that this block contains data for the To-Do Search folder.
RSF_PID_CONV_ACTIONS	0x8006	Indicates that this block contains data for the Conversation Action Settings folder.
RSF_PID_COMBINED_ACTIONS	0x8007	This value is reserved.
RSF_PID_SUGGESTED_CONTACTS	0x8008	Indicates that this block contains data for the <b>Suggested Contacts folder</b> .
PERSIST_SENTINEL	0x0000	Indicates that the implementation MUST stop processing further <b>PersistData</b> blocks. <b>PERSIST_SENTINEL</b> is optional; if it is not included, processing continues to the end of the stream.

### 2.2.3.2 PersistElement Block

Name	Type	Size	Description
<b>ElementID</b>	<b>WORD</b>	2	Type identifier value for this <b>PersistElement</b> block. SHOULD be one of <b>PersistElementType</b> values.
<b>ElementDataSize</b>	<b>WORD</b>	2	The size in <b>BYTES</b> of the <b>ElementData</b> field.
<b>ElementData</b>	<b>BYTE</b> array of binary data	variable	The data corresponding to this <b>PersistID</b> .

**PersistElementType** values SHOULD be one of those listed in the following table. If a **PersistElement** block is encountered where **ElementID** is not known to the implementation, the implementation MUST ignore that **PersistElement** block and continue processing further **PersistElement** blocks until an **ELEMENT\_SENTINEL ElementID** or the end of the stream is encountered. The implementation MUST then continue processing additional **PersistData** blocks until either a **PERSIST\_SENTINEL PersistID** or the end of the stream is encountered.

Name	Value	Value of ElementDataSize	Description
RSF_ELID_HEADER	0x0002	0x0004	Indicates that this block's <b>ElementData</b> contains a <b>DWORD header</b> value. The interpretation of this value depends on the current block's <b>PersistID</b> type. For all <b>PersistID</b> types specified in this section, this value <b>MUST</b> be 0 (zero).
RSF_ELID_ENTRYID	0x0001	variable	Indicates that this block contains the entry ID of the folder indicated by <b>PersistID</b> .
ELEMENT_SENTINEL	0x0000	0x0000	Indicates that the implementation <b>MUST</b> stop processing further <b>PersistElement</b> blocks for the current <b>PersistData</b> block.

## 2.2.4 Inbox Identification

To identify the Inbox, an implementation **MUST** use [RopGetReceiveFolder](#) from the Store object protocol to get the FID for the default **Receive folder** for the Store object.

## 2.2.5 PidTagContainerClass

Several special folders use this **PtypString** property, located on the special folder itself, to describe the type of Message objects that the folder contains. For these folders, an implementation **MUST** set this property, as shown in the following table.

Property value	Special folder
"IPF.Note"	Deleted Items Outbox Sent Items Inbox Drafts Conflicts Sync Issues Local Failures Server Failures Junk E-mail Tracked Mail Processing
"IPF.Appointment"	Calendar
"IPF.Contact"	Contacts
"IPF.Journal"	Journal
"IPF.StickyNote"	Notes
"IPF.Task"	Tasks To-Do Search
"Outlook.Reminder"	Reminders

<b>Property value</b>	<b>Special folder</b>
"IPF.Note.OutlookHomepage"	RSS Feeds
"IPF.Configuration"	Conversation Action Settings



## 3 Protocol Details

Note that the programming elements used in this section are specified in [\[MS-OXCDATA\]](#).

### 3.1 Common Details

Special folders can be opened or created by clients and servers. Except where noted, this section defines constraints to which clients and servers adhere when interacting with special folders. In all other respects, clients and servers operate as specified in [\[MS-OXCFOLD\]](#).

#### 3.1.1 Abstract Data Model

This section describes a conceptual model of possible data organization that an implementation maintains to participate in this protocol. The described organization is provided to facilitate the explanation of how the protocol behaves. This document does not mandate that implementations adhere to this model as long as their external behavior is consistent with that described in this document.

##### 3.1.1.1 Folder Hierarchy

The following outline depicts a hierarchy for special folders.

- Store
  - Root
    1. Deferred Action Folder
    2. Finder
    3. Reminders
    4. Tracked Mail Processing
    5. To-Do Search
    6. Common Views
    7. Personal Views
      1. Deleted Items
      2. Outbox
      3. Sent Items
      4. Inbox
      5. Calendar
      6. Contacts
      7. Journal

- 8. Notes
- 9. Tasks
- 10. Drafts
- 11. Sync Issues
  - 1. Conflicts
  - 2. Local Failures
  - 3. Server Failures
- 12. Junk E-mail
- 13. RSS Feeds
- 14. Conversation Action Settings

### 3.1.1.2 Search Criteria for Search Special Folders

Some of the special folders are search folders, as specified in [\[MS-OXOSRCH\]](#), and the functionality supported by these folders depends on specific **search criteria**. The detailed specification for each of these is given in section [3.1.4.1](#), and an abstracted outline of these search criteria is as follows.

For the Reminders folder:

Include all Message objects in any folder contained within the Top of Personal Folders folder, with the following **restrictions**:

- The following special folders are excluded from the search:
  - Deleted Items folder
  - Junk E-mail folder
  - Drafts folder
  - Outbox folder
  - Conflicts folder
  - Local Failures folder
  - Server Failures folder
  - Sync Issues folder
- The value of the [PidTagMessageClass](#) property does not contain a string with the prefix "IPM.Schedule."
- The value of the [PidTagMessageFlags](#) property, defined in [\[MS-OXCMSG\]](#), does not have the mfSubmitted flag set (that is, submitted Message objects are excluded).
- The value of the [PidLidReminderSet](#) property is set to the **Boolean** value 1, **OR** the value of the [PidLidRecurring](#) property is set to the **Boolean** value 1.

For the To-Do Search folder:

All Message objects in any folder contained within the Top of Personal Folders folder, with the following restrictions:

- The following special folders are excluded from the search:
  - Deleted Items folder
  - Junk E-mail folder
  - Drafts folder
  - Outbox folder
  - Conflicts folder
  - Local Failures folder
  - Server Failures folder
  - Sync Issues folder
- The **message class** does not start with "IPM.Appointment" OR "IPM.Activity" OR "IPM.StickyNote".
- Any one of the following is true:
  - The Message object is a Task object, as specified in [\[MS-OXOTASK\]](#), **AND** the Task object is owned **AND NOT** accepted **AND** the Task object was sent to the currently logged-on user.
  - The Message object's [PidTagFollowupIcon](#) property is greater than 0.
  - The Message object's [PidTagToDoItemFlags](#) property includes the IsToDoItem flag.
  - The Message object is an object with the **complete flag** set to **TRUE** or a completed task.

For the Tracked Mail Processing folder:

All Message objects in any folder contained within the Top of Personal Folders folder, with the following restrictions:

- The following special folders are excluded from the search:
  - Deleted Items folder
  - Junk E-mail folder
  - Drafts folder
  - Outbox folder
  - Conflicts folder
  - Local Failures folder
  - Server Failures folder
  - Sync Issues folder
- The [PidTagSwappedToDoStore](#) property exists on the object.

- The value of the [PidTagMessageFlags](#) property does not include the mfUnsent or the mfSubmitted flags.

### 3.1.2 Timers

None.

### 3.1.3 Initialization

None.

### 3.1.4 Higher-Layer Triggered Events

Before an implementation tries to read or write Message objects within a special folder, the implementation MUST obtain a handle to the special folder by using the following steps:

1. The implementation MUST try to open the special folder by using an identification method, as specified in section [2.2](#), and the Folder Object protocol, as specified in [\[MS-OXCFOLD\]](#).
2. If the identification method fails, or the special folder does not exist within the store, the implementation MUST create the special folder as specified in the following section.

#### 3.1.4.1 Folder Creation

The folder hierarchy specified in section [3.1.1.1](#) also specifies the dependency chain for special folder creation. Before a special folder can be created, all its container objects in this hierarchy MUST already exist. For example, all special folders (except the Root folder) depend on the Store object and the Root folder. Therefore, the Store object and Root folder MUST exist before any special folder can exist. Also, before any folder is created or opened, a handle to the Store object that contains the folder, as specified in [\[MS-OXCSTOR\]](#), MUST be obtained by opening the Store object.

To create a special folder, an implementation MUST do the following:

1. Open the parent folder of the desired special folder, as specified in the folder hierarchy in section [3.1.1.1](#), by using the Folder Object protocol.
2. Create the folder in the opened parent folder, by using the Folder Object protocol and using the special folder name for the implementation's **locale**, reusing the existing folder if one already exists by that name. The FID that is returned MUST be converted to an entry ID, as by [\[MS-OXCDATA\]](#), by using [RopIdFromLongTermId](#), as defined in [\[MS-OXCROPS\]](#). The resulting entry ID of the new folder will be used in the following steps.
3. Establish the identification method for the particular special folder created, as specified in section [2.2](#).
4. If applicable, set the [PidTagContainerClass](#) property to the appropriate value, as specified in section [2.2.5](#).
5. Perform any special folder-specific initialization, as specified in the following sections.

##### 3.1.4.1.1 Creating the Reminders Folder

To complete the creation of the Reminders folder, an implementation SHOULD [≤4>](#) set the search criteria for the Reminders folder by using the Search Folder List Configuration protocol [\[MS-OXOSRCH\]](#) and the Folder Object protocol [\[MS-OXCFOLD\]](#), such that:

1. The Top of Personal Folders folder SHOULD be the only container included in the search.
2. The search applies a restriction of type RES\_AND with the following two sub-clauses:
  1. A restriction of type RES\_AND, with the following sub-clauses – note that a sub-clause is only added if the particular special folder already exists within the store:
    2. A restriction of type RES\_PROPERTY with a relational operator (relop) value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Deleted Items folder.
    3. A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Junk E-mail folder.
    4. A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Drafts folder.
    5. A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Outbox folder.
    6. A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Conflicts folder.
    7. A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Local Failures folder.
    8. A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Server Failures folder.
    9. A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Sync Issues folder.
  10. A restriction of type RES\_AND, with the following three sub-clauses:
    1. A restriction of type RES\_NOT with the following sub-clause:
      - A restriction of type RES\_AND with the following 2 sub-clauses:
        1. A restriction of type RES\_EXIST that specifies the [PidTagMessageClass](#) property.
        2. A restriction of type RES\_CONTENT with a ulFuzzyLevel of FL\_PREFIX, comparing the value of [PidTagMessageClass](#) property to the string value "IPM.Schedule".
    2. A restriction of type **BitMaskRestriction** with a **BitMapRelOp** value of BMR\_EQZ that compares the value of the [PidTagMessageFlags](#) property to the **ULONG** value mfSubmitted.
    3. A restriction of type RES\_OR, with the following two sub-clauses:
      1. A restriction of type RES\_PROPERTY, with relop RELOP\_EQ, comparing the value of the [PidLidReminderSet](#) property to the **Boolean** value of 1.
      2. A restriction of type RES\_AND, with the following two sub-clauses:
        1. A restriction of type RES\_EXIST that specifies the [PidLidRecurring](#) property.
        2. A restriction of type RES\_PROPERTY, with relop RELOP\_EQ, comparing the value of the [PidLidRecurring](#) property to the **Boolean** value of 1.

3. The search SHOULD provide the client with the information when requested, include child folders, and run without content indexing.

#### 3.1.4.1.2 Creating the To-Do Search Folder

To complete the creation of the To-Do Search folder, an implementation MUST set the search criteria for the To-Do Search folder by using the Search Folder List Configuration protocol [\[MS-OXOSRCH\]](#) and the Folder Object protocol [\[MS-OXCFOLD\]](#), such that: <5>

1. The Top of Personal Folders folder MUST be the only container included in the search.
2. The search applies a restriction of type RES\_AND with the following two sub-clauses:
  1. A restriction of type RES\_AND, with the following three sub-clauses:
    1. A restriction of type RES\_NOT, with the following sub-clause:
      - A restriction of type RES\_CONTENT with a ulFuzzyLevel of FL\_PREFIX bitwise or FL\_IGNORECASE, comparing the value of the [PidTagMessageClass](#) property to the string value "IPM.appointment".
    2. A restriction of type RES\_NOT, with the following sub-clause:
      - A restriction of type RES\_CONTENT with a ulFuzzyLevel of FL\_PREFIX bitwise or FL\_IGNORECASE, comparing the value of the [PidTagMessageClass](#) property to the string value "IPM.Activity".
    3. A restriction of type RES\_NOT, with the following sub-clause:
      - A restriction of type RES\_CONTENT with a ulFuzzyLevel of FL\_PREFIX bitwise or FL\_IGNORECASE, comparing the value of the [PidTagMessageClass](#) property to the string value "IPM.StickyNote."
  2. A restriction of type RES\_AND, with the following two sub-clauses:
    1. A restriction of type RES\_AND, with the following sub-clauses—note that a sub-clause is only added if the particular special folder already exists within the store:
      - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Deleted Items folder.
      - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Junk E-mail folder.
      - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Drafts folder.
      - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Outbox folder.
      - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Conflicts folder.
      - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Local Failures folder.

- A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Server Failures folder.
  - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Sync Issues folder.
2. A restriction of type RES\_OR, with the following four sub-clauses:
1. A restriction of type RES\_AND with the following two sub-clauses:
    1. A restriction of type RES\_OR, with the following two sub-clauses:
 

A restriction of type RES\_CONTENT with a ulFuzzyLevel of FL\_FULLSTRING bitwise or FL\_IGNORECASE, comparing the value of the [PidTagMessageClass](#) property to the string value "IPM.Task."

A restriction of type RES\_CONTENT with a ulFuzzyLevel of FL\_PREFIX bitwise or FL\_IGNORECASE, comparing the value of the [PidTagMessageClass](#) property to the string value "IPM.Task."
    1. A restriction of type RES\_NOT with the following sub-clause:
      - A restriction of type RES\_AND with the following two sub-clauses:
 

A restriction of type RES\_PROPERTY, with relop RELOP\_EQ, comparing the value of the [PidLidTaskState](#) property to the **LONG** value 2.

A restriction of type RES\_PROPERTY, with relop RELOP\_NE, comparing the value of the [PidLidTaskAccepted](#) property to the binary value 1.
  2. A restriction of type RES\_AND with the following two sub-clauses:
    1. A restriction of type RES\_EXIST that specifies the [PidTagFollowupIcon](#) property.
    2. A restriction of type RES\_PROPERTY, with relop RELOP\_GT, comparing the value of the [PidTagFollowupIcon](#) property to the **LONG** value 0 (zero).
  3. A restriction of type RES\_AND with the following two sub-clauses:
    1. A restriction of type RES\_EXIST that specifies the [PidTagToDoItemFlags](#) property.
    2. A restriction of type BitMaskRestriction with a BitMapRelOp value of BMR\_NEZ that compares the value of the [PidTagToDoItemFlags](#) property to the **ULONG** value 0x00000001.
  4. A restriction of type RES\_OR, with the following two sub-clauses:
    1. A restriction of type RES\_AND with the following three sub-clauses:
 

A restriction of type RES\_OR, with the following two sub-clauses:

A restriction of type RES\_NOT, with the following sub-clause:

      - A restriction of type RES\_EXIST that specifies the [PidTagFollowupIcon](#) property.

A restriction of type RES\_PROPERTY, with relop RELOP\_EQ, comparing the value of the [PidTagFollowupIcon](#) property to the **LONG** value 0 (zero).

A restriction of type RES\_EXIST that specifies the [PidTagFlagStatus](#) property.  
A restriction of type RES\_PROPERTY, with relop RELOP\_EQ, comparing the value of the [PidTagFlagStatus](#) property to the **LONG** value 1.

1. A restriction of type RES\_AND with the following two sub-clauses:

A restriction of type RES\_EXIST that specifies the [PidLidTaskStatus](#) property.  
A restriction of type RES\_PROPERTY, with relop RELOP\_EQ, comparing the value of the [PidLidTaskStatus](#) property to the **ULONG** value 2.

3. The search SHOULD provide the client with the information when requested, include child folders, and run without content indexing.

### 3.1.4.1.3 Creating the Tracked Mail Processing Folder

To complete the creation of the Tracked Mail Processing folder, an implementation MUST set the search criteria for the Tracked Mail Processing folder by using the Search Folder List Configuration protocol [[MS-OXOSRCH](#)] and the Folder Object protocol [[MS-OXCFOLD](#)], such that: <6>

1. The Top of Personal Folders folder MUST be the only container included in the search.
2. The search applies a restriction of type RES\_AND with the following two sub-clauses:
  1. A restriction of type RES\_AND, with the following sub-clauses – note that a sub-clause is only added if the particular special folder already exists within the store:
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Deleted Items folder.
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Junk E-Mail folder.
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Drafts folder.
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Outbox folder.
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Conflicts folder.
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Local Failures folder.
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Server Failures folder.
    - A restriction of type RES\_PROPERTY with a relop value of RELOP\_NE, comparing the value of the [PidTagParentEntryId](#) property with the FID/MID pair of the Sync Issues folder.
  2. A restriction of type RES\_AND, with the following two sub-clauses:
    1. A restriction of type RES\_EXIST that specifies the [PidTagSwappedToDoStore](#) property.
    2. A restriction of type BitMaskRestriction with a BitMapRelOp value of BMR\_EQZ that compares the value of the [PidTagMessageFlags](#) property to the **ULONG** value including mfUnsent bitwise or mfSubmitted.



3. The search SHOULD provide the client with the information when requested, include child folders, and run without content indexing.

#### **3.1.4.1.4 Creating Other Special Folders**

If the special folder that is being created is one of the following:

- Deleted Items folder
- Junk E-mail folder
- Outbox folder
- Conflicts folder
- Local Failures folder
- Server Failures folder
- Sync Issues folder
- Drafts folder

An implementation MUST take the following additional steps:

1. Open the Reminders folder by using its identification method and the Folder Object protocol. If this succeeds, perform the steps in section [3.1.4.1.1](#).
2. Open the To-Do Search folder by using its identification method and the Folder Object protocol. If this succeeds, perform the steps in section [3.1.4.1.2](#).
3. Open the Tracked Mail Processing folder by using its identification method and the Folder Object protocol. If this succeeds, perform the steps in section [3.1.4.1.3](#).

If the special folder that is being created is a Conversation Action Settings folder, an implementation MUST set the [PidTagAttributeHidden](#) property of the Folder object to TRUE.

#### **3.1.5 Message Processing Events and Sequencing Rules**

An implementation MUST treat any failure to open the Root folder as a failure of the entire Special Folders protocol.

For all other special folders, an implementation SHOULD create the special folder if an attempt to open the folder using that folder's identification method fails.

#### **3.1.6 Timer Events**

None.

#### **3.1.7 Other Local Events**

None.

## 4 Protocol Examples

The following examples illustrate the byte order of **ROPs** in a buffer that is being prepared for transmission. Note that the examples in this section show only the relevant portions of the specified ROPs; this is not the final byte sequence that gets transmitted over the wire. Also note that the data format for a multi-byte field appears in **little-endian** format, with the **bytes** in the field presented from least significant to most significant.

Frequently, these **ROP requests** are packed with other ROP requests, compressed, obfuscated, and then packed in one or more **RPC** calls. These examples assume that the client has already successfully logged on to the server and has obtained any **Server object handles** that are to be used as inputs into the ROPs. For more information about RPC calls, see [\[MS-OXCRPC\]](#).

Examples in this section use the following format for byte sequences:

```
0080: 45 4d 53 4d 44 42 2e 44-4c 4c 00 00 00 00 00 00
```

The bold value at the far left ("**0080**") is the offset of the following bytes into the buffer, expressed in hexadecimal notation. Following the offset is a series of up to 16 bytes, with each two-character sequence describing the value of one byte in hexadecimal notation. The bolded byte "**4d**" (01001101) is located 0x83 bytes (131 bytes) from the beginning of the buffer. The dash between the eighth byte ("44") and the ninth byte ("4c") bytes has no semantic value, and serves only to distinguish the eight-byte boundary for readability.

This byte sequence is followed by one or more lines that interpret it. In larger examples, the byte sequence is shown once in its entirety and then repeated in smaller chunks, with each smaller chunk interpreted separately.

When explaining **InputHandleIndex** values, the example text describes the **Server object** that is referenced by the handle index. For more information about Server object handles, see [\[MS-OXCROPS\]](#) section 1.3.1.

### 4.1 Opening a Special Folder

Using the Calendar folder as an example, opening this special folder involves the following:

1. Open the Inbox folder by using the Inbox folder's identification method and the Folder Object protocol. This operation returns a Folder object.
2. Get the value of the [PidTagIpmAppointmentEntryId](#) property from the Inbox folder object returned in step 1 by using the property and Stream Object protocol. This operation returns an entry ID for the Calendar folder.
3. Convert the entry ID returned in step 2 to an FID as specified in [\[MS-OXCADATA\]](#), then open this FID by using the Store Object protocol. This operation returns a Folder object for the Calendar folder.

#### 4.1.1 Client Request for Opening a Special Folder

A complete ROP request to open the Calendar folder would look like the following:

```
0000: 02 01 00 01 01 00 00 00-01 42 0E 44 00
```

[RopOpenFolder](#)

RopId: 0x02

LogonId: 0

HandleIndex: 0 (HSOT=0x00000160)

FolderId: 0001-000001420e44

**Note** The folder identifier of the Inbox folder to open.

OpenModeFlags: 0x00 Open existing folder

```
0000: 07 00 02 00 00 01 00 1D-00 14 00 49 67 03 00 F4
0010: 0F 02 01 72 66 1F 00 E5-36 1F 00 E6 36 1F 00 01
0020: 30 03 00 01 36 03 00 02-36 03 00 03 36 0B 00 0A
0030: 36 1F 00 13 36 02 01 16-36 02 01 D0 36 02 01 D1
0040: 36 02 01 D2 36 02 01 D3-36 02 01 D4 36 02 01 D5
0050: 36 02 01 D6 36 02 01 D7-36 02 11 D8 36 02 01 D9
0060: 36 03 00 DE 36 02 01 DF-36 02 01 E0 36 03 00 E1
0070: 36 02 11 E4 36 02 01 EB-36 02 01 DA 36
```

#### [RopGetPropertiesSpecific](#)

RopId: 0x07

LogonId: 1

HandleIndex: 1 (HSOT=0x000000e2)

PropertySizeLimit: 0x0000

WantUnicode: 0x0001 (TRUE)

PropertyValueCount: 29 (0x001D)

...

#### [PidTagIpmAppointmentEntryId](#)

...

```
0000: 02 01 00 01 01 00 00 00-01 50 4D F6 00
```

#### [RopOpenFolder](#)

RopId: 0x02

LogonId: 1

HandleIndex: 0 (HSOT=0x00000160)

FolderId: 0001-000001504df6

**Note** This is the FID for Calendar folder to open.

OpenModeFlags: 0x00 Open existing folder

#### 4.1.2 Server Response for Opening a Special Folder

```
0000: 02 01 00 00 00 00 00 00
```

##### [RopOpenFolder](#)

RopId: 0x02

HandleIndex: 1 (HSOT=0x000000e2)

ReturnValue: Success (0x00000000)

HasRules: 0x00 (FALSE)

IsGhosted: 0x00 (FALSE)

Only 256 bytes dumped:

```
0000: 07 01 00 00 00 00 01 00-01 00 00 00 01 42 0E 41
0010: 00 3F 00 00 00 0A 0F 01-04 80 0A 0F 01 04 80 0A
0020: 0F 01 04 80 00 49 00 6E-00 62 00 6F 00 78 00 00
0030: 00 00 01 00 00 00 00 00-00 00 00 00 00 00 00 00
0040: 00 00 00 49 00 50 00 46-00 2E 00 4E 00 6F 00 74
0050: 00 65 00 00 00 0A 0F 01-04 80 00 2E 00 00 00 00
0060: 00 6A 3C B8 FA 3B A9 F0-46 B4 F4 E4 B6 C7 74 45
0070: 09 01 00 02 27 39 56 14-8B EF 4F 98 14 81 7E 2C
0080: 82 BD C2 00 00 01 50 4D-F6 00 00 00 2E 00 00 00
0090: 00 00 6A 3C B8 FA 3B A9-F0 46 B4 F4 E4 B6 C7 74
00a0: 45 09 01 00 02 27 39 56-14 8B EF 4F 98 14 81 7E
00b0: 2C 82 BD C2 00 00 01 50-4D F7 00 00 00 2E 00 00
00c0: 00 00 00 6A 3C B8 FA 3B-A9 F0 46 B4 F4 E4 B6 C7
00d0: 74 45 09 01 00 02 27 39-56 14 8B EF 4F 98 14 81
00e0: 7E 2C 82 BD C2 00 00 01-50 4D F8 00 00 00 2E 00
00f0: 00 00 00 00 6A 3C B8 FA-3B A9 F0 46 B4 F4 E4 B6
...
```

##### [RopGetPropertiesSpecific](#)

RopId: 0x07

HandleIndex: 1 (HSOT=0x000000e2)

ReturnValue: Success (0x00000000)

...

PropertyArray:

PropCount: 29

...

[PidTagIpmAppointmentEntryId](#) 46 Bytes

```
0000: 00 00 00 00 6A 3C B8 FA-3B A9 F0 46 B4 F4 E4 B6
0010: C7 74 45 09 01 00 02 27-39 56 14 8B EF 4F 98 14
0020: 81 7E 2C 82 BD C2 00 00-01 50 4D F6 00 00
...
```

**Note** The entry ID contains 00 00-01 50 4D F6 that is part of the FID: 0001-000001504df6 used for the [RopOpenFolder](#) in section [4.1.1](#).

```
0000: 02 01 00 00 00 00 00 00
```

### [RopOpenFolder](#)

RopId: 0x02

HandleIndex: 1 (HSOT=0x000000e2)

**Note** Successfully opened the Calendar folder, and the Calendar folder has a handle HSOT=0x000000e2.

HasRules: 0x00 (FALSE)

IsGhosted: 0x00 (FALSE)

...

## 4.2 Creating a Special Folder

Using the Calendar folder as an example, creating this special folder involves the following:

1. Open the parent folder, in this case the Top of Personal Folders folder, as specified in the folder hierarchy in section [3.1.1.1](#), by using the Top of Personal Folders identification method and the Folder Object protocol [[MS-OXCFCOLD](#)]. This operation returns a Folder object.
2. Create a new folder in the opened parent folder, by using the Folder Object protocol [[MS-OXCFCOLD](#)], and using the name "calendar" in English locales, reusing the existing folder if one already exists by that name. The entry ID of the newly created folder will be used in the following steps.
3. Open the Inbox folder by using the Inbox identification method and the Folder Object protocol [[MS-OXCFCOLD](#)]. This operation returns a Folder object.
4. Set the value of the [PidTagIpmAppointmentEntryId](#) property on the Inbox folder object returned in step 3 to the entry ID value of the folder created in step 2, by using the Property and Stream Object protocol [[MS-OXCPRPT](#)].
5. Set the value of the [PidTagContainerClass](#) property on the new Calendar folder to the value "IPF.Appointment".

### 4.2.1 Client Request for Creating a Special Folder

A complete ROP request to create the Calendar folder would look like the following:

0000: 02 00 00 01 01 00 00 00-01 42 0E 41 00

### [RopOpenFolder](#)

RopId: 0x02

LogonId: 0x00

HandleIndex: 0 (HSOT=0x00000059)

FolderId: 0001-000001420e41

**Note** FolderID 4: 0001-000001420e41 Top of Personal Folders folder from [RopLogon](#).

OpenModeFlags: 0x00 (ReadOnly)

...

0000: 1C 00 00 01 01 01 00 00-43 00 61 00 6C 00 65 00  
0010: 6E 00 64 00 61 00 72 00-00 00 43 00 61 00 6C 00  
0020: 65 00 6E 00 64 00 61 00-72 00 20 00 43 00 6F 00  
0030: 6D 00 6D 00 65 00 6E 00-74 00 00 00

### [RopCreateFolder](#)

RopId: 0x1C

LogonId: 0

InputHandleIndex: 0 (HSOT=0x00000497)

OutputHandleIndex: 1

FolderType: 0x01

UseUnicodeStrings: (0x01) (TRUE)

OpenExisting: 0x00 (FALSE)

Reserved: 0x00 (FALSE)

DisplayName: **Calendar**

Comment: Calendar Comment

0000: 02 00 00 01 01 00 00 00-01 42 0E 44 00

### [RopOpenFolder](#)

RopId: 0x02

LogonId: 0

HandleIndex: 0 (HSOT=0x00000059)

FolderId: 0001-000001420e44

**Note** Open the Inbox folder with above FID.

OpenModeFlags: 0x00 (Open existing folder)

```
0000: 0A 00 00 36 00 01 00 02-01 D0 36 2E 00 00 00 00
0010: 00 6A 3C B8 FA 3B A9 F0-46 B4 F4 E4 B6 C7 74 45
0020: 09 01 00 02 27 39 56 14-8B EF 4F 98 14 81 7E 2C
0030: 82 BD C2 00 00 01 50 4D-F6 00 00
```

#### [RopSetProperties](#)

RopId: 0x0A

LogonId: 0

HandleIndex: 0 (HSOT=0x000004e4)

**Note** HSOT=0x000004e4 is a handle to Inbox.

PropertyValueSize: 0x0036 (54)

PropertyValueCount: 1 (0x01)

0x36D00102 [PidTagIpmAppointmentEntryId](#) 46 Bytes

```
0000: 00 00 00 00 6A 3C B8 FA-3B A9 F0 46 B4 F4 E4 B6
0010: C7 74 45 09 01 00 02 27-39 56 14 8B EF 4F 98 14
0020: 81 7E 2C 82 BD C2 00 00-01 50 4D F6 00 00

0000: 0A 00 00 26 00 01 00 1F-00 13 36 49 00 50 00 46
0010: 00 2E 00 41 00 70 00 70-00 6F 00 69 00 6E 00 74
0020: 00 6D 00 65 00 6E 00 74-00 00 00
```

#### [RopSetProperties](#)

RopId: 0x0A

LogonId: 0

HandleIndex: 0 (HSOT=0x0000042e)

PropertyValueSize: 0x0026 (38)

PropertyValueCount: 1 (0x01)

#### [PidTagContainerClass](#)

IPF.Appointment

### 4.2.2 Server Response for Creating a Special Folder

```
0000: 02 01 00 00 00 00 00 00
```

### [RopOpenFolder](#)

RopId: 0x02

HandleIndex: 1 (HSOT=0x00000497)

**Note** Handle HSOT=0x00000497 of Top of Personal Folders folder is used to create the Calendar folder in section [4.2.1](#), Client Request [RopCreateFolder](#).

ReturnValue: Success (0x00000000)

HasRules: 0x00 (FALSE)

IsGhosted: 0x00 (FALSE)

```
0000: 1C 01 00 00 00 00 01 00-00 00 01 50 4D F6 00
```

### [RopCreateFolder](#)

RopId: 0x1C

HandleIndex: 1 (HSOT=0x0000042e)

**Note** HSOT=0x0000042e is the handle to the Calendar folder that was created.

ReturnValue: ecNone (success) (0x00000000)

FolderId: 0001-000001504df6

IsExistingFolder: 0x00 (FALSE)

```
0000: 02 01 00 00 00 00 00 00 00
```

### [RopOpenFolder](#)

RopId: 0x02

HandleIndex: 1 (HSOT=0x000004e4)

**Note** HSOT=0x000004e4 is the handle of the Inbox folder. It is used in [4.2.1](#), Client Request [RopSetProperties](#). [PidTagIpmAppointmentEntryId](#) of Calendar folder.

ReturnValue: Success (0x00000000)

HasRules: 0x00 (FALSE)

IsGhosted: 0x00 (FALSE)

```
0000: 0A 00 00 00 00 00 00 00 00
```

### [RopSetProperties](#)

RopId: 0x0A



HandleIndex: 0 (HSOT=0x0000042e)

ReturnValue: ecNone (success) (0x00000000)

PropertyProblemCount: 0

PropertyProblems:

0000: 0A 00 00 00 00 00 00 00

### [RopSetProperties](#)

RopId: 0x0A

HandleIndex: 0 (HSOT=0x0000042e)

ReturnValue: ecNone (success) (0x00000000)

PropertyProblemCount: 0

PropertyProblems:

## 5 Security

### 5.1 Security Considerations for Implementers

There are no special security considerations specific to the Special Folders protocol. General security considerations pertaining to the underlying protocols apply (see [\[MS-OXCSTOR\]](#), [\[MS-OXCFOLD\]](#), and [\[MS-OXCPRPT\]](#)).

### 5.2 Index of Security Parameters

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products:

- Microsoft® Office Outlook® 2003
- Microsoft® Exchange Server 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Exchange Server 2007
- Microsoft® Outlook® 2010
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

[<1> Section 2.2.3.1](#): Office Outlook 2003 clients and Exchange 2003 servers do not recognize as special the RSS Feeds, Tracked Mail Processing, and To-Do Search folders.

[<2> Section 2.2.3.1](#): Office Outlook 2003 and Office Outlook 2007 clients and Exchange 2003 and Exchange 2007 servers do not recognize the Conversation Action Settings folder as a special folder.

[<3> Section 2.2.3.1](#): Office Outlook 2003 and Office Outlook 2007 clients and Exchange 2003 and Exchange 2007 servers do not recognize the Suggested Contacts folder as a special folder.

[<4> Section 3.1.4.1.1](#): Office Outlook 2003 sets the search criteria to include only the Calendar, Tasks, Inbox, and Contacts folders, and it only sets a restriction for [PidLidReminderSet](#) and [PidLidRecurring](#), and it does not include RECURSIVE\_SEARCH.

[<5> Section 3.1.4.1.2](#): Office Outlook 2003 clients and Exchange 2003 servers do not recognize the To-Do search criteria.

[<6> Section 3.1.4.1.3](#): Office Outlook 2003 clients and Exchange 2003 servers do not recognize the Tracked Mail search criteria.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

[Applicability](#) 11

### C

[Capability negotiation](#) 11

[Change tracking](#) 36

Client

[overview](#) 17

### E

Examples

[overview](#) 26

### F

[Fields – vendor-extensible](#) 11

### G

[Glossary](#) 5

### I

[Implementer – security considerations](#) 34

[Index of security parameters](#) 34

[Informative references](#) 8

[Introduction](#) 5

### M

Messages

[overview](#) 12

Messaging

[transport](#) 12

### N

[Normative references](#) 7

### O

[Overview \(synopsis\)](#) 8

### P

[Parameters – security index](#) 34

[Preconditions](#) 11

[Prerequisites](#) 11

[Product behavior](#) 35

### R

References

[informative](#) 8

[normative](#) 7

[Relationship to other protocols](#) 11

### S

Security

[implementer considerations](#) 34

[overview](#) 34

[parameter index](#) 34

[Standards Assignments](#) 11

### T

[Tracking changes](#) 36

[Transport](#) 12

### V

[Vendor-extensible fields](#) 11

[Versioning](#) 11