

# [MS-OXOSMMS]: Short Message Service (SMS) and Multimedia Messaging Service (MMS) Object Protocol

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Revised and edited technical content.
09/03/2008	1.02		Updated references.
12/03/2008	1.03		Updated IP notice.
04/10/2009	2.0		Updated applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	4.0.0	None	Version 4.0.0 release
05/05/2010	5.0.0	Major	Updated and revised the technical content.
08/04/2010	5.1	Minor	Clarified the meaning of the technical content.
11/03/2010	5.2	Minor	Clarified the meaning of the technical content.
03/18/2011	5.2	No change	No changes to the meaning, language, or formatting of the technical content.
08/05/2011	5.3	Minor	Clarified the meaning of the technical content.
10/07/2011	6.0	Major	Significantly changed the technical content.
01/20/2012	7.0	Major	Significantly changed the technical content.
04/27/2012	7.0	No change	No changes to the meaning, language, or formatting of the technical content.
07/16/2012	8.0	Major	Significantly changed the technical content.
10/08/2012	8.1	Minor	Clarified the meaning of the technical content.
02/11/2013	8.1	No change	No changes to the meaning, language, or formatting of the technical content.
07/26/2013	8.2	Minor	Clarified the meaning of the technical content.
11/18/2013	8.2	No change	No changes to the meaning, language, or formatting of the technical content.
02/10/2014	8.2	No change	No changes to the meaning, language, or formatting of the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
04/30/2014	8.2	No change	No changes to the meaning, language, or formatting of the technical content.
07/31/2014	8.2	No change	No changes to the meaning, language, or formatting of the technical content.

# Table of Contents

<b>1 Introduction</b>	<b>6</b>
1.1 Glossary	6
1.2 References	7
1.2.1 Normative References	7
1.2.2 Informative References	7
1.3 Overview	7
1.4 Relationship to Other Protocols	8
1.5 Prerequisites/Preconditions	8
1.6 Applicability Statement	8
1.7 Versioning and Capability Negotiation	8
1.8 Vendor-Extensible Fields	8
1.9 Standards Assignments	8
<b>2 Messages</b>	<b>9</b>
2.1 Transport	9
2.2 Message Syntax	9
2.2.1 Common SMS and MMS Object Properties	9
2.2.1.1 PidNameOMSAccountGuid Property	9
2.2.1.2 PidNameOMSScheduleTime Property	9
2.2.1.3 PidNameOMSServiceType Property	9
2.2.1.4 PidNameOMSSourceType Property	9
2.2.1.5 PidNameContentClass Property	10
2.2.1.6 PidNameOMSMobileModel Property	10
2.2.2 Additional Property Constraints	10
2.2.2.1 PidTagIconIndex Property	10
2.2.2.2 PidTagMessageClass Property	10
2.2.2.3 Body Properties	11
2.2.2.4 PidTagNormalizedSubject Property	11
<b>3 Protocol Details</b>	<b>12</b>
3.1 Client Details	12
3.1.1 Abstract Data Model	12
3.1.2 Timers	12
3.1.3 Initialization	12
3.1.4 Higher-Layer Triggered Events	12
3.1.4.1 Creation of an SMS or MMS Object	12
3.1.4.2 Modification of an SMS or MMS Object	12
3.1.4.3 Deletion of an SMS or MMS Object	12
3.1.5 Message Processing Events and Sequencing Rules	12
3.1.6 Timer Events	12
3.1.7 Other Local Events	12
<b>4 Protocol Examples</b>	<b>13</b>
4.1 Sample SMS Object	13
4.2 Sample MMS Object	14
<b>5 Security</b>	<b>18</b>
5.1 Security Considerations for Implementers	18
5.2 Index of Security Parameters	18
<b>6 Appendix A: Product Behavior</b>	<b>19</b>

**7 Change Tracking..... 20**  
**8 Index ..... 21**

# 1 Introduction

The Short Message Service (SMS) and Multimedia Messaging Service (MMS) Object Protocol enables clients to create, modify, and delete **Short Message Service (SMS)** and **Multimedia Messaging Service (MMS)** messages.

This protocol extends the Message and Attachment Object Protocol, as described in [\[MS-OXCMSG\]](#).

Sections 1.8, 2, and 3 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in [\[RFC2119\]](#). Sections 1.5 and 1.9 are also normative but does not contain those terms. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

**Coordinated Universal Time (UTC)**  
**flags**  
**GUID**  
**handle**  
**Unicode**

The following terms are defined in [\[MS-OXGLOS\]](#):

**Attachment object**  
**calendar**  
**Hypertext Markup Language (HTML)**  
**Message object**  
**message store**  
**Multimedia Messaging Service (MMS)**  
**named property**  
**plain text**  
**property ID**  
**reminder**  
**remote operation (ROP)**  
**ROP request**  
**ROP response**  
**rule**  
**Short Message Service (SMS)**  
**stream**

The following terms are specific to this document:

**Multimedia Messaging Service (MMS) object:** A Message object that represents a Multimedia Messaging Service (MMS) message in a message store.

**SMS object:** A Message object that represents a Short Message Service (SMS) message in a message store.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specification documents do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC 2822 and MIME to Email Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol](#)".

[MS-OXOMSG] Microsoft Corporation, "[Email Object Protocol](#)".

[MS-OXPROPS] Microsoft Corporation, "[Exchange Server Protocols Master Property List](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

### 1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[SMIL2.1] Bulterman, D., Grassel, G., Jansen, J., Koivisto, A., Layaida, N., et al., Eds., "Synchronized Multimedia Integration Language", W3C Recommendation, December, 2005, <http://www.w3.org/TR/SMIL2/>

## 1.3 Overview

This protocol enables a client to create, modify, and delete SMS text messages and MMS multimedia messages in a **message store**. SMS text messages are characterized by a short unformatted text body. MMS messages are characterized by text and multimedia components.

This protocol extends the Message and Attachment Object Protocol, as described in [\[MS-OXCMSG\]](#), in that it defines new properties unique to **SMS objects** and **MMS objects** and adds restrictions to the existing of the **Message object**.

A typical scenario for using this protocol is to create, modify, or delete SMS text messages or MMS multimedia messages.

## **1.4 Relationship to Other Protocols**

This protocol has the same dependencies as the Message and Attachment Object Protocol, which it extends. For more details about the Message and Attachment Object Protocol, see [\[MS-OXCMSG\]](#).

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

## **1.5 Prerequisites/Preconditions**

This protocol has the same prerequisites and preconditions as the Message and Attachment Object Protocol, as specified in [\[MS-OXCMSG\]](#).

## **1.6 Applicability Statement**

None.

## **1.7 Versioning and Capability Negotiation**

None.

## **1.8 Vendor-Extensible Fields**

This protocol provides no vendor-extensibility beyond what is already specified in [\[MS-OXCMSG\]](#).

## **1.9 Standards Assignments**

None.



## 2 Messages

### 2.1 Transport

This protocol uses the protocols specified in [\[MS-OXCPRPT\]](#) and [\[MS-OXCMSG\]](#) as its primary transport mechanism.

### 2.2 Message Syntax

Clients operate on SMS objects and MMS objects using the Message and Attachment Object Protocol, as specified in [\[MS-OXCMSG\]](#).

Unless otherwise specified, SMS objects and MMS objects adhere to all property constraints specified in [\[MS-OXPROPS\]](#) and [\[MS-OXCMSG\]](#). SMS objects and MMS objects can also contain other properties, but these properties have no impact on this protocol.

#### 2.2.1 Common SMS and MMS Object Properties

##### 2.2.1.1 PidNameOMSAccountGuid Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameOMSAccountGuid** property ([\[MS-OXPROPS\]](#) section 2.454) encodes the **GUID** of the SMS account used to deliver the message in the following format (including the braces): {DWORD-WORD-WORD-WORD.DWORD}; for example, "{C200E360-38C5-11CE-AE62-08002B2B79EF}".

##### 2.2.1.2 PidNameOMSScheduleTime Property

Type: **PtypTime** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameOMSScheduleTime** property ([\[MS-OXPROPS\]](#) section 2.456) specifies the time, in **Coordinated Universal Time (UTC)**, that the client sends the requests instructing the service provider to send the SMS or MMS message.

##### 2.2.1.3 PidNameOMSServiceType Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameOMSServiceType** property ([\[MS-OXPROPS\]](#) section 2.457) indicates the type of service used to send the SMS or MMS message. The value of this property MUST be one of the values in the following table.

Value	Meaning
0x00000001	SMS
0x00000004	MMS

##### 2.2.1.4 PidNameOMSSourceType Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameOMSSourceType** property ([\[MS-OXPROPS\]](#) section 2.458) indicates the source of the SMS or MMS message. The value of this property MUST be one of the values in the following table.

Value	Source type
0x00000000	XMS inspector
0x00000001	<b>Reminder</b>
0x00000002	<b>Calendar</b> summary
0x00000003	<b>Rule (1)</b>
0x00000004	Unknown

### 2.2.1.5 PidNameContentClass Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameContentClass** property ([\[MS-OXCMSG\]](#) section 2.2.1.48) MUST be set to one of the values in the following table.

Value	Meaning
MS-OMS-SMS	SMS
MS-OMS-MMS	MMS

### 2.2.1.6 PidNameOMSMobileModel Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidNameOMSMobileModel** property ([\[MS-OXPROPS\]](#) section 2.455) indicates the model of the mobile device used to send the SMS or MMS message.

## 2.2.2 Additional Property Constraints

This protocol makes additional constraints on the properties specified in section [2.2.2.1](#) through section [2.2.2.4](#) beyond what is specified in [\[MS-OXCMSG\]](#) and [\[MS-OXOMSG\]](#).

### 2.2.2.1 PidTagIconIndex Property

Type: **PtypInteger32** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagIconIndex** property ([\[MS-OXOMSG\]](#) section 2.2.1.10) specifies which icon is to be used by a user interface when displaying a group of SMS objects and/or MMS objects. This property SHOULD [<1>](#) be set; if set, the value MUST be 0xFFFFFFFF.

### 2.2.2.2 PidTagMessageClass Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagMessageClass** property ([\[MS-OXCMSG\]](#) section 2.2.1.3) specifies the type of the Message object. In addition to meeting the criteria specified in [\[MS-OXCMSG\]](#), for SMS objects this value MUST either be set to "IPM.Note.Mobile.SMS" or begin with "IPM.Note.Mobile.SMS". For MMS

objects, this property MUST either be set to "IPM.Note.Mobile.MMS" or begin with "IPM.Note.Mobile.MMS".

### 2.2.2.3 Body Properties

The contents of SMS objects are stored and retrieved following the details specified for **plain text** messages in [\[MS-OXCMAIL\]](#) section 2.1.3.3.1.<2>

The contents of MMS objects are stored and retrieved following the details specified for **HTML** messages, as specified in [\[MS-OXCMAIL\]](#) section 2.1.3.3.1.<3>

### 2.2.2.4 PidTagNormalizedSubject Property

Type: **PtypString** ([\[MS-OXCDATA\]](#) section 2.11.1)

The **PidTagNormalizedSubject** property ([\[MS-OXCMSG\]](#) section 2.2.1.10) contains an abbreviated version of the contents of the message suitable for displaying groups of SMS objects to a user. For MMS objects, only the constraints specified in [\[MS-OXCMSG\]](#) section 2.2.1.10 apply.

## 3 Protocol Details

### 3.1 Client Details

The client role creates and sets properties on SMS objects and MMS objects.

#### 3.1.1 Abstract Data Model

None.

#### 3.1.2 Timers

None.

#### 3.1.3 Initialization

None.

#### 3.1.4 Higher-Layer Triggered Events

##### 3.1.4.1 Creation of an SMS or MMS Object

To create an SMS object or MMS object, the client sets properties in accordance with the requirements in section 2 and [\[MS-OXCPRPT\]](#) and then saves the resulting Message object as specified in [\[MS-OXCMSG\]](#).

##### 3.1.4.2 Modification of an SMS or MMS Object

When modifying an SMS object or MMS object, the client modifies any of the properties in accordance with the requirements in section 2 and [\[MS-OXCPRPT\]](#) and then saves the Message object as specified in [\[MS-OXCMSG\]](#).

##### 3.1.4.3 Deletion of an SMS or MMS Object

An SMS object or MMS object has no special deletion semantics beyond what is specified in [\[MS-OXCMSG\]](#).

#### 3.1.5 Message Processing Events and Sequencing Rules

None.

#### 3.1.6 Timer Events

None.

#### 3.1.7 Other Local Events

None.

## 4 Protocol Examples

### 4.1 Sample SMS Object

A user creates an SMS text message, types in some text, and sends it. The following is a description of what a client might do to accomplish the user's intentions and the responses a server might return. For more details about **remote operations (ROPs)**, see [\[MS-OXCPRPT\]](#) and [\[MS-OXCMSG\]](#).

Before manipulating SMS objects, the client asks the server to map the **named properties to property IDs** by sending a **RopGetPropertyIDsFromNames ROP request** ([\[MS-OXCROPS\]](#) section 2.2.8.1).

Property	Property set GUID	NameID
<b>PidNameOMSMobileModel</b> (section <a href="#">2.2.1.6</a> )	{00020329-0000-0000-C000-00000000046}	OMSMobileModel
<b>PidNameOMSAccountGuid</b> (section <a href="#">2.2.1.1</a> )	{00020329-0000-0000-C000-00000000046}	OMSAccountGuid
<b>PidNameOMSServiceType</b> (section <a href="#">2.2.1.3</a> )	{00020329-0000-0000-C000-00000000046}	OMSServiceType
<b>PidNameOMSSourceType</b> (section <a href="#">2.2.1.4</a> )	{00020329-0000-0000-C000-00000000046}	OMSSourceType

The server might send a **RopGetPropertyIDsFromNames ROP response** with the following property IDs, which are used in the example that follows. (The actual property IDs are at the discretion of the server.)

Property	Property ID
<b>PidNameOMSMobileModel</b>	0x84C3
<b>PidNameOMSAccountGuid</b>	0x84C4
<b>PidNameOMSServiceType</b>	0x84C5
<b>PidNameOMSSourceType</b>	0x84C6

To create an SMS object, the client uses the **RopCreateMessage ROP** ([\[MS-OXCROPS\]](#) section 2.2.6.2). The server returns a success code and a **handle** to a Message object.

After the user inputs the content for the SMS object, the client transmits the data to the server by using the **RopSetProperties ROP** ([\[MS-OXCROPS\]](#) section 2.2.8.6).

Property	Property ID	Data type	Value
<b>PidNameOMSAccountGuid</b>	0x84C4	<b>PtypString</b> ( <a href="#">[MS-OXCADATA]</a> section 2.11.1)	{01234567-0123-0123-0123-0123456789AB}
<b>PidNameOMSMobileModel</b>	0x84C3	<b>PtypString</b>	(null)

Property	Property ID	Data type	Value
<b>PidNameOMSServiceType</b>	0x84C5	<b>PtypInteger32</b> ( <a href="#">[MS-OXCDATA]</a> section 2.11.1)	0x00000001
<b>PidNameOMSSourceType</b>	0x84C6	<b>PtypInteger32</b>	0x00000000
<b>PidTagBody</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.56.1)	0x1000	<b>PtypString</b>	What time is the meeting?
<b>PidTagInternetCodepage</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.56.6)	0x3FDE	<b>PtypInteger32</b>	0x0000FDE9
<b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.3)	0x001A	<b>PtypString</b>	IPM.Note.Mobile.SMS
<b>PidTagNormalizedSubject</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.10)	0x0E1D	<b>PtypString</b>	What time is the meeting?
<b>PidTagSubjectPrefix</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.9)	0x003D	<b>PtypString</b>	(null)

When the user sends the message, the client commits the properties on the server by using the **RopSaveChangesMessage** ROP ([\[MS-OXCROPS\]](#) section 2.2.6.3) and then releases the SMS object by using the **RopRelease** ROP ([\[MS-OXCROPS\]](#) section 2.2.15.3). The client then submits the message to an SMS provider by using the **RopSubmitMessage** ROP ([\[MS-OXCROPS\]](#) section 2.2.7.1).

The values of some properties change during the processing of the **RopSaveChangesMessage** ROP, but the properties defined in this specification do not change.

## 4.2 Sample MMS Object

A user creates an MMS message, gives it a subject, types some text, attaches a picture, and sends it. The following is a description of what a client might do to accomplish the user's intentions and the responses a server might return. For more details about ROPs, see [\[MS-OXCPRPT\]](#) and [\[MS-OXCMSG\]](#).

Before manipulating an MMS object, the client asks the server to map the named properties to property IDs by sending a **RopGetPropertyIDsFromNames** ROP request ([\[MS-OXCROPS\]](#) section 2.2.8.1).

Property	Property set GUID	NameID
<b>PidNameOMSMobileModel</b> (section <a href="#">2.2.1.6</a> )	{00020329-0000-0000-C00000000046}	OMSMobileModel
<b>PidNameOMSAccountGuid</b> (section <a href="#">2.2.1.1</a> )	{00020329-0000-0000-C00000000046}	OMSAccountGuid
<b>PidNameOMSServiceType</b> (section <a href="#">2.2.1.3</a> )	{00020329-0000-0000-C00000000046}	OMSServiceType
<b>PidNameOMSSourceType</b> (section <a href="#">2.2.1.4</a> )	{00020329-0000-0000-C00000000046}	OMSSourceType

The server might send a **RopGetPropertyIDsFromNames** ROP response with the following property IDs, which are used in the example that follows. (The actual property IDs are at the discretion of the server.)

Property	Property ID
<b>PidNameOMSMobileModel</b>	0x84CE
<b>PidNameOMSAccountGuid</b>	0x84CF
<b>PidNameOMSServiceType</b>	0x84D0
<b>PidNameOMSSourceType</b>	0x84D1

To create an MMS object, the client uses the **RopCreateMessage** ROP ([\[MS-OXCROPS\]](#) section 2.2.6.2). The server returns a success code and a handle to an object.

After the user inputs the content for the MMS object, the client transmits the data to the server by using the **RopSetProperties** ROP ([\[MS-OXCROPS\]](#) section 2.2.8.6).

Property	Property ID	Data type	Value
<b>PidNameOMSAccountGuid</b>	0x84CF	<b>PtypString</b> ( <a href="#">[MS-OXCADATA]</a> section 2.11.1)	{01234567-0123-0123-0123456789ABC}
<b>PidNameOMSMobileModel</b>	0x84CE	<b>PtypString</b>	(empty)
<b>PidNameOMSServiceType</b>	0x84D0	<b>PtypInteger32</b> ( <a href="#">[MS-OXCADATA]</a> section 2.11.1)	0x00000004
<b>PidNameOMSSourceType</b>	0x84D1	<b>PtypInteger32</b>	0x00000000
<b>PidTagInternetCodepage</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.56.6)	0x3FDE	<b>PtypInteger32</b>	0x0000FDE9
<b>PidTagHtml</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.56.9)	0x1013	<b>PtypBinary</b> ( <a href="#">[MS-OXCADATA]</a> section 2.11.1)	(The content of this property is given following the table.)
<b>PidTagIconIndex</b> ( <a href="#">[MS-OXOMSG]</a> section 2.2.1.10)	0x1080	<b>PtypInteger32</b>	0xFFFFFFFF
<b>PidTagMessageClass</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.3)	0x001A	<b>PtypString</b>	IPM.Note.Mobile.MMS
<b>PidTagMessageFlags</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.6)	0x0E07	<b>PtypInteger32</b>	<b>Flags:</b> 0x00000018 MSGFLAG_UNSENT MSGFLAG_HASATTACH
<b>PidTagNormalizedSubject</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.10)	0x0E1d	<b>PtypString</b>	Here's the photo.
<b>PidTagSubjectPrefix</b> ( <a href="#">[MS-OXCMSG]</a> section 2.2.1.9)	0x003d	<b>PtypString</b>	(empty)

The **PidTagHtml** property is a binary property containing the following text.

```

<HTML>
<BODY>
<IMG SRC="cid:Att1.jpg@AB1B43B2B0594564.B94EF7ABB12B49BA" border="0">
<BR>
This is the photo you asked for.
<BR>
<A HREF="cid:Att0.txt@AB1B43B2B0594564.B94EF7ABB12B49BA"></A>
</BODY>
</HTML>

```

The client allocates space for a data file in the message by using the **RopCreateAttachment** ROP ([MS-OXCROPS] section 2.2.6.13). In response, the server returns a success code and a handle to an **Attachment object**. The client uses this handle with the **RopSetProperties** ROP ([MS-OXCROPS] section 2.2.8.6) to transmit data about the attachment to the server.

Property	Property ID	Data type	Value
<b>PidTagAttachmentHidden</b> ([MS-OXCMSG] section 2.2.2.24)	0x7FFE	<b>PtypBoolean</b> ([MS-OXCDATA] section 2.11.1)	0x01
<b>PidTagAttachMethod</b> ([MS-OXCMSG] section 2.2.2.9)	0x3705	<b>PtypInteger32</b>	0x00000001 (ATTACH_BY_VALUE)
<b>PidTagAttachContentId</b> ([MS-OXCMSG] section 2.2.2.26)	0x3712	<b>PtypString</b>	MMS.smil@AB1B43B2B0594564.B94EF7ABB12B49BA
<b>PidTagAttachMimeType</b> ([MS-OXCMSG] section 2.2.2.26)	0x370E	<b>PtypString</b>	application/smil
<b>PidTagAttachLongFilename</b> ([MS-OXCMSG] section 2.2.2.10)	0x3707	<b>PtypString</b>	MMS.smil

The client sets the contents of the attachment by using the attachment handle with the **RopOpenStream** ROP ([MS-OXCROPS] section 2.2.9.1), passing in the **PidTagAttachDataBinary** property ([MS-OXPROPS] section 2.580) as the property to open. With the handle returned from the **RopOpenStream** ROP, the client calls the **RopWriteStream** ROP ([MS-OXCROPS] section 2.2.9.3), writing out the contents of the Synchronized Multimedia Integration Language (SMIL) file, the format of which is described in [SMIL2.1], describing the layout of the MMS message. The client follows this with the **RopRelease** ROP ([MS-OXCROPS] section 2.2.15.3) on the **stream (2)** handle, then commits the changes by using the **RopSaveChangesAttachment** ROP ([MS-OXCROPS] section 2.2.6.15), releases the handle to the attachment by using the **RopRelease** ROP.

The client repeats the process from the **RopCreateAttachment** ROP ([MS-OXCROPS] section 2.2.6.13) for the **RopRelease** ROP with the attachment handle twice more, once for a plain-text version of the body, and once for the image. The attachment containing the body uses the following properties and values with the **RopSetProperties** ROP.



Property	Property ID	Data type	Value
<b>PidTagAttachmentHidden</b>	0x7FFE	<b>PtypBoolean</b>	0x01
<b>PidTagAttachMethod</b>	0x3705	<b>PtypInteger32</b>	0x00000001 (ATTACH_BY_VALUE)
<b>PidTagAttachContentId</b>	0x3712	<b>PtypString</b>	Att0.txt@AB1B43B2B0594564.B94EF7ABB12B49BA
<b>PidTagAttachMimeType</b>	0x370E	<b>PtypString</b>	text/plain
<b>PidTagAttachLongFilename</b>	0x3707	<b>PtypString</b>	1.txt

The **RopOpenStream** ROP for the plain-text body is also on the **PidTagAttachDataBinary** property, but the contents written are **Unicode** text. The last attachment the client creates contains the image, and the **RopSetProperties** ROP sends the following data.

Property	Property ID	Data type	Value
<b>PidTagAttachmentHidden</b>	0x7FFE	<b>PtypBoolean</b>	0x01
<b>PidTagAttachMethod</b>	0x3705	<b>PtypInteger32</b>	0x00000001 (ATTACH_BY_VALUE)
<b>PidTagAttachContentId</b>	0x3712	<b>PtypString</b>	Att1.jpg@AB1B43B2B0594564.B94EF7ABB12B49BA
<b>PidTagAttachMimeType</b>	0x370E	<b>PtypString</b>	image/jpeg
<b>PidTagAttachLongFilename</b>	0x3707	<b>PtypString</b>	photo.jpg

The contents of the **PidTagAttachDataBinary** property on the image attachment are the binary contents of the image file.

When the user sends the message, the client commits the properties on the server by using the **RopSaveChangesMessage** ROP ([\[MS-OXCROPS\]](#) section 2.2.6.3) and then releases the MMS object by using the **RopRelease** ROP. The client then submits the message to an MMS provider by using the **RopSubmitMessage** ROP ([\[MS-OXCROPS\]](#) section 2.2.7.1).

The values of some properties change during the processing of the **RopSaveChangesMessage** ROP, but the properties specified in this protocol do not change.

## 5 Security

### 5.1 Security Considerations for Implementers

There are no special security considerations specific to the SMS and MMS Object Protocol. General security considerations pertaining to the underlying transport apply, as specified in [\[MS-OXCMSG\]](#) and [\[MS-OXCPRPT\]](#).

### 5.2 Index of Security Parameters

None.

## 6 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Office Outlook 2003
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

[<1> Section 2.2.2.1](#): Office Outlook 2007 does not set the **PidTagIconIndex** property ([\[MS-OXOMSG\]](#) section 2.2.1.10) on SMS objects or MMS objects.

[<2> Section 2.2.2.3](#): Office Outlook 2007 SP1 sets both the **PidTagBody** property ([\[MS-OXCMSG\]](#) section 2.2.1.56.1) and the **PidTagHtml** property ([\[MS-OXCMSG\]](#) section 2.2.1.56.9) on SMS objects.

[<3> Section 2.2.2.3](#): Office Outlook 2007 SP1 sets both the **PidTagBody** property ([\[MS-OXCMSG\]](#) section 2.2.1.56.1) and the **PidTagHtml** property ([\[MS-OXCMSG\]](#) section 2.2.1.56.9) on MMS objects.

## 7 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 8 Index

### A

Abstract data model  
[client](#) 12

Additional property constraints  
[body properties](#) 11  
[PidTagIconIndex property](#) 10  
[PidTagMessageClass property](#) 10  
[PidTagNormalizedSubject property](#) 11  
[Additional Property Constraints message](#) 10  
[Applicability](#) 8

### B

[Body properties additional property constraints](#) 11

### C

[Capability negotiation](#) 8  
[Change tracking](#) 20

Client  
[abstract data model](#) 12  
[initialization](#) 12  
[message processing](#) 12  
[other local events](#) 12  
[overview](#) 12  
[sequencing rules](#) 12  
[timer events](#) 12  
[timers](#) 12

Client - higher-layer triggered events  
[creation of an SMS or MMS object](#) 12  
[deletion of an SMS or MMS object](#) 12  
[modification of an SMS or MMS object](#) 12  
[Client - overview](#) 12

Common SMS and MMS object properties  
[PidNameContentClass property](#) 10  
[PidNameOMSAccountGuid property](#) 9  
[PidNameOMSMobileModel property](#) 10  
[PidNameOMSScheduleTime property](#) 9  
[PidNameOMSServiceType property](#) 9  
[PidNameOMSSourceType property](#) 9

### D

Data model - abstract  
[client](#) 12

### E

Examples  
[sample MMS object](#) 14  
[sample SMS object](#) 13

### F

[Fields - vendor-extensible](#) 8

### G

[Glossary](#) 6

### H

Higher-layer triggered events - client  
[creation of an SMS or MMS object](#) 12  
[deletion of an SMS or MMS object](#) 12  
[modification of an SMS or MMS object](#) 12

### I

[Implementer - security considerations](#) 18  
[Index of security parameters](#) 18  
[Informative references](#) 7

Initialization  
[client](#) 12

[Introduction](#) 6

### M

Message processing  
[client](#) 12

Messages  
[Additional Property Constraints](#) 10  
[syntax](#) 9  
[transport](#) 9

### N

[Normative references](#) 7

### O

Other local events  
[client](#) 12  
[Overview \(synopsis\)](#) 7

### P

[Parameters - security index](#) 18

[PidNameContentClass common SMS and MMS object property](#) 10

[PidNameOMSAccountGuid common SMS and MMS object property](#) 9

[PidNameOMSMobileModel common SMS and MMS object property](#) 10

[PidNameOMSScheduleTime common SMS and MMS object property](#) 9

[PidNameOMSServiceType common SMS and MMS object property](#) 9

[PidNameOMSSourceType common SMS and MMS object property](#) 9

[PidTagIconIndex additional property constraints](#) 10

[PidTagMessageClass additional property constraints](#) 10

[PidTagNormalizedSubject additional property constraints](#) 11

[Preconditions](#) 8

[Prerequisites](#) 8

[Product behavior](#) 19

## **R**

[References](#) 7

[informative](#) 7

[normative](#) 7

[Relationship to other protocols](#) 8

## **S**

[Sample MMS object example](#) 14

[Sample SMS object example](#) 13

Security

[implementer considerations](#) 18

[parameter index](#) 18

Sequencing rules

[client](#) 12

[Standards assignments](#) 8

[Syntax](#) 9

## **T**

Timer events

[client](#) 12

Timers

[client](#) 12

[Tracking changes](#) 20

[Transport](#) 9

Triggered events - client

[creation of an SMS or MMS object](#) 12

[deletion of an SMS or MMS object](#) 12

[modification of an SMS or MMS object](#) 12

## **V**

[Vendor-extensible fields](#) 8

[Versioning](#) 8