[MS-OXPROPS]:

Exchange Server Protocols Master Property List

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation ("this documentation") for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights**. This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets**. Microsoft does not claim any trade secret rights in this documentation.
- **Patents**. Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft Open Specifications Promise or the Microsoft Community Promise. If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **License Programs**. To see all of the protocols in scope under a specific license program and the associated patents, visit the Patent Map.
- **Trademarks**. The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit www.microsoft.com/trademarks.
- **Fictitious Names**. The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

Support. For questions and support, please contact dochelp@microsoft.com.

Revision Summary

Date	Revision History	Revision Class	Comments
4/4/2008	0.1	New	Initial Availability.
4/25/2008	0.2	Minor	Revised and updated property names and other technical content.
6/27/2008	1.0	Major	Initial Release.
8/6/2008	1.01	Minor	Updated references to reflect date of initial release.
9/3/2008	1.02	Minor	Changed title of document.
10/1/2008	1.03	Minor	Revised and edited technical content.
12/3/2008	1.04	Minor	Revised and edited technical content.
2/4/2009	1.05	Minor	Revised and edited technical content.
3/4/2009	1.06	Minor	Revised and edited technical content.
4/10/2009	2.0	Major	Updated technical content and applicable product releases.
7/15/2009	3.0	Major	Revised and edited for technical content.
11/4/2009	4.0.0	Major	Updated and revised the technical content.
2/10/2010	5.0.0	Major	Updated and revised the technical content.
5/5/2010	6.0.0	Major	Updated and revised the technical content.
8/4/2010	7.0	Major	Significantly changed the technical content.
11/3/2010	8.0	Major	Significantly changed the technical content.
3/18/2011	9.0	Major	Significantly changed the technical content.
8/5/2011	10.0	Major	Significantly changed the technical content.
10/7/2011	11.0	Major	Significantly changed the technical content.
1/20/2012	12.0	Major	Significantly changed the technical content.
4/27/2012	13.0	Major	Significantly changed the technical content.
7/16/2012	13.1	Minor	Clarified the meaning of the technical content.
10/8/2012	14.0	Major	Significantly changed the technical content.
2/11/2013	15.0	Major	Significantly changed the technical content.
7/26/2013	16.0	Major	Significantly changed the technical content.
11/18/2013	16.0	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	16.0	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	16.1	Minor	Clarified the meaning of the technical content.
7/31/2014	16.2	Minor	Clarified the meaning of the technical content.

Copyright © 2025 Microsoft Corporation

Date	Revision History	Revision Class	Comments
10/30/2014	16.3	Minor	Clarified the meaning of the technical content.
3/16/2015	17.0	Major	Significantly changed the technical content.
5/26/2015	17.1	Minor	Clarified the meaning of the technical content.
9/14/2015	18.0	Major	Significantly changed the technical content.
6/13/2016	19.0	Major	Significantly changed the technical content.
9/14/2016	19.0	None	No changes to the meaning, language, or formatting of the technical content.
10/13/2017	20.0	Major	Significantly changed the technical content.
12/12/2017	20.0	None	No changes to the meaning, language, or formatting of the technical content.
7/24/2018	21.0	Major	Significantly changed the technical content.
10/1/2018	22.0	Major	Significantly changed the technical content.
3/19/2019	23.0	Major	Significantly changed the technical content.
6/18/2019	24.0	Major	Significantly changed the technical content.
8/18/2020	25.0	Major	Significantly changed the technical content.
4/22/2021	26.0	Major	Significantly changed the technical content.
8/17/2021	27.0	Major	Significantly changed the technical content.
8/20/2024	28.0	Major	Significantly changed the technical content.
11/12/2024	29.0	Major	Significantly changed the technical content.
5/20/2025	30.0	Major	Significantly changed the technical content.

Copyright © 2025 Microsoft Corporation

Table of Contents

1 Introduction ... 24
1.1 Glossary ... 24
1.2 References ... 32
1.2.1 Normative References ... 32
1.2.2 Informative References ... 34
1.3 Overview ... 34
1.3.1 Common Message Classes ... 36
1.3.2 Commonly Used Property Sets ... 37
1.3.3 Property ID Ranges ... 38
1.3.4 WebDAV Property Naming ... 39
1.3.4.1 http://schemas.microsoft.com/mapi/proptag Namespace ... 39
1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace ... 39
1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace ... 40
1.4 Relationship to Protocols and Other Structures ... 40
1.5 Applicability Statement ... 40
1.6 Versioning and Localization ... 40
1.7 Vendor-Extensible Fields ... 41

2 Structures ... 42
2.1 PidLidAddressBookProviderArrayType ... 42
2.2 PidLidAddressBookProviderEmailList ... 42
2.3 PidLidAddressCountryCode ... 42
2.4 PidLidAgingDontAgeMe ... 42
2.5 PidLidAllAttendeesString ... 43
2.6 PidLidAllowExternalCheck ... 43
2.7 PidLidAnniversaryEventEntryId ... 44
2.8 PidLidAppointmentAuxiliaryFlags ... 44
2.9 PidLidAppointmentColor ... 44
2.10 PidLidAppointmentCounterProposal ... 44
2.11 PidLidAppointmentDuration ... 45
2.12 PidLidAppointmentEndDate ... 45
2.13 PidLidAppointmentEndTime ... 45
2.14 PidLidAppointmentEndWhole ... 46
2.15 PidLidAppointmentLastSequence ... 46
2.16 PidLidAppointmentMessageClass ... 46
2.17 PidLidAppointmentNotAllowPropose ... 47
2.18 PidLidAppointmentProposalNumber ... 47
2.19 PidLidAppointmentProposedDuration ... 47
2.20 PidLidAppointmentProposedEndWhole ... 48
2.21 PidLidAppointmentProposedStartWhole ... 48
2.22 PidLidAppointmentRecur ... 48
2.23 PidLidAppointmentReplyName ... 49
2.24 PidLidAppointmentReplyTime ... 49
2.25 PidLidAppointmentSequence ... 50
2.26 PidLidAppointmentSequenceTime ... 50
2.27 PidLidAppointmentStartDate ... 50
2.28 PidLidAppointmentStartTime ... 51
2.29 PidLidAppointmentStartWhole ... 51
2.30 PidLidAppointmentStateFlags ... 51
2.31 PidLidAppointmentSubType ... 52
2.32 PidLidAppointmentTimeZoneDefinitionEndDisplay ... 52
2.33 PidLidAppointmentTimeZoneDefinitionRecur ... 52
2.34 PidLidAppointmentTimeZoneDefinitionStartDisplay ... 53
2.35 PidLidAppointmentUnsendableRecipients ... 53
2.36 PidLidAppointmentUpdateTime ... 53

Copyright © 2025 Microsoft Corporation

2.37 PidLidAttendeeCriticalChange 54
2.38 PidLidAutoFillLocation 54
2.39 PidLidAutoLog 54
2.40 PidLidAutoProcessState 55
2.41 PidLidAutoStartCheck 55
2.42 PidLidBilling 55
2.43 PidLidBirthdayEventEntryId 56
2.44 PidLidBirthdayLocal 56
2.45 PidLidBusinessCardCardPicture 56
2.46 PidLidBusinessCardDisplayDefinition 56
2.47 PidLidBusyStatus 57
2.48 PidLidCalendarType 57
2.49 PidLidCategories 58
2.50 PidLidCcAttendeesString 58
2.51 PidLidChangeHighlight 58
2.52 PidLidClassification 58
2.53 PidLidClassificationDescription 59
2.54 PidLidClassificationGuid 59
2.55 PidLidClassificationKeep 59
2.56 PidLidClassified 60
2.57 PidLidCleanGlobalObjectId 60
2.58 PidLidClientIntent 60
2.59 PidLidClipEnd 61
2.60 PidLidClipStart 61
2.61 PidLidCollaborateDoc 61
2.62 PidLidCommonEnd 62
2.63 PidLidCommonStart 62
2.64 PidLidCompanies 62
2.65 PidLidConferencingCheck 63
2.66 PidLidConferencingType 63
2.67 PidLidContactCharacterSet 63
2.68 PidLidContactItemData 64
2.69 PidLidContactLinkedGlobalAddressListEntryId 64
2.70 PidLidContactLinkEntry 64
2.71 PidLidContactLinkGlobalAddressListLinkId 65
2.72 PidLidContactLinkGlobalAddressListLinkState 65
2.73 PidLidContactLinkLinkRejectHistory 65
2.74 PidLidContactLinkName 66
2.75 PidLidContactLinkSearchKey 66
2.76 PidLidContactLinkSMTPAddressCache 66
2.77 PidLidContacts 66
2.78 PidLidContactUserField1 67
2.79 PidLidContactUserField2 67
2.80 PidLidContactUserField3 68
2.81 PidLidContactUserField4 68
2.82 PidLidConversationActionLastAppliedTime 68
2.83 PidLidConversationActionMaxDeliveryTime 69
2.84 PidLidConversationActionMoveFolderEid 69
2.85 PidLidConversationActionMoveStoreEid 69
2.86 PidLidConversationActionVersion 70
2.87 PidLidConversationProcessed 70
2.88 PidLidCurrentVersion 70
2.89 PidLidCurrentVersionName 71
2.90 PidLidDayInterval 71
2.91 PidLidDayOfMonth 71
2.92 PidLidDelegateMail 72
2.93 PidLidDepartment 72
2.94 PidLidDirectory 72

Copyright © 2025 Microsoft Corporation

2.95 PidLidDistributionListChecksum 72
2.96 PidLidDistributionListMembers 73
2.97 PidLidDistributionListName 73
2.98 PidLidDistributionListOneOffMembers 73
2.99 PidLidDistributionListStream 74
2.100 PidLidEmail1AddressType 74
2.101 PidLidEmail1DisplayName 74
2.102 PidLidEmail1EmailAddress 75
2.103 PidLidEmail1OriginalDisplayName 75
2.104 PidLidEmail1OriginalEntryId 75
2.105 PidLidEmail2AddressType 76
2.106 PidLidEmail2DisplayName 76
2.107 PidLidEmail2EmailAddress 76
2.108 PidLidEmail2OriginalDisplayName 77
2.109 PidLidEmail2OriginalEntryId 77
2.110 PidLidEmail3AddressType 77
2.111 PidLidEmail3DisplayName 78
2.112 PidLidEmail3EmailAddress 78
2.113 PidLidEmail3OriginalDisplayName 78
2.114 PidLidEmail3OriginalEntryId 79
2.115 PidLidEndRecurrenceDate 79
2.116 PidLidEndRecurrenceTime 79
2.117 PidLidExceptionReplaceTime 80
2.118 PidLidFax1AddressType 80
2.119 PidLidFax1EmailAddress 80
2.120 PidLidFax1OriginalDisplayName 80
2.121 PidLidFax1OriginalEntryId 81
2.122 PidLidFax2AddressType 81
2.123 PidLidFax2EmailAddress 81
2.124 PidLidFax2OriginalDisplayName 82
2.125 PidLidFax2OriginalEntryId 82
2.126 PidLidFax3AddressType 82
2.127 PidLidFax3EmailAddress 83
2.128 PidLidFax3OriginalDisplayName 83
2.129 PidLidFax3OriginalEntryId 83
2.130 PidLidFExceptionalAttendees 83
2.131 PidLidFExceptionalBody 84
2.132 PidLidFileUnder 84
2.133 PidLidFileUnderId 84
2.134 PidLidFileUnderList 85
2.135 PidLidFInvited 85
2.136 PidLidFlagRequest 85
2.137 PidLidFlagString 86
2.138 PidLidForwardInstance 86
2.139 PidLidForwardNotificationRecipients 86
2.140 PidLidFOthersAppointment 87
2.141 PidLidFreeBusyLocation 87
2.142 PidLidGlobalObjectId 87
2.143 PidLidHasPicture 88
2.144 PidLidHomeAddress 88
2.145 PidLidHomeAddressCountryCode 88
2.146 PidLidHtml 89
2.147 PidLidICalendarDayOfWeekMask 89
2.148 PidLidInboundICalStream 89
2.149 PidLidInfoPathFormName 90
2.150 PidLidInstantMessagingAddress 90
2.151 PidLidIntendedBusyStatus 90
2.152 PidLidInternetAccountName 91

Copyright © 2025 Microsoft Corporation

2.153 PidLidInternetAccountStamp 91
2.154 PidLidIsContactLinked 91
2.155 PidLidIsException 92
2.156 PidLidIsRecurring 92
2.157 PidLidIsSilent 92
2.158 PidLidLinkedTaskItems 93
2.159 PidLidLocation 93
2.160 PidLidLogDocumentPosted 93
2.161 PidLidLogDocumentPrinted 94
2.162 PidLidLogDocumentRouted 94
2.163 PidLidLogDocumentSaved 94
2.164 PidLidLogDuration 95
2.165 PidLidLogEnd 95
2.166 PidLidLogFlags 95
2.167 PidLidLogStart 95
2.168 PidLidLogType 96
2.169 PidLidLogTypeDesc 96
2.170 PidLidMeetingType 96
2.171 PidLidMeetingWorkspaceUrl 97
2.172 PidLidMonthInterval 97
2.173 PidLidMonthOfYear 97
2.174 PidLidMonthOfYearMask 98
2.175 PidLidNetShowUrl 98
2.176 PidLidNoEndDateFlag 98
2.177 PidLidNonSendableBcc 99
2.178 PidLidNonSendableCc 99
2.179 PidLidNonSendableTo 99
2.180 PidLidNonSendBccTrackStatus 100
2.181 PidLidNonSendCcTrackStatus 100
2.182 PidLidNonSendToTrackStatus 100
2.183 PidLidNoteColor 101
2.184 PidLidNoteHeight 101
2.185 PidLidNoteWidth 101
2.186 PidLidNoteX 102
2.187 PidLidNoteY 102
2.188 PidLidOccurrences 102
2.189 PidLidOldLocation 103
2.190 PidLidOldRecurrenceType 103
2.191 PidLidOldWhenEndWhole 103
2.192 PidLidOldWhenStartWhole 103
2.193 PidLidOnlinePassword 104
2.194 PidLidOptionalAttendees 104
2.195 PidLidOrganizerAlias 104
2.196 PidLidOriginalStoreEntryId 105
2.197 PidLidOtherAddress 105
2.198 PidLidOtherAddressCountryCode 105
2.199 PidLidOwnerCriticalChange 106
2.200 PidLidOwnerName 106
2.201 PidLidPendingStateForSiteMailboxDocument 106
2.202 PidLidPercentComplete 107
2.203 PidLidPostalAddressId 107
2.204 PidLidPostRssChannel 107
2.205 PidLidPostRssChannelLink 108
2.206 PidLidPostRssItemGuid 108
2.207 PidLidPostRssItemHash 108
2.208 PidLidPostRssItemLink 109
2.209 PidLidPostRssItemXml 109
2.210 PidLidPostRssSubscription 109

Copyright © 2025 Microsoft Corporation

2.211 PidLidPrivate 109
2.212 PidLidPromptSendUpdate 110
2.213 PidLidRecurrenceDuration 110
2.214 PidLidRecurrencePattern 110
2.215 PidLidRecurrenceType 111
2.216 PidLidRecurring 111
2.217 PidLidReferenceEntryId 111
2.218 PidLidReminderDelta 112
2.219 PidLidReminderFileParameter 112
2.220 PidLidReminderOverride 113
2.221 PidLidReminderPlaySound 113
2.222 PidLidReminderSet 113
2.223 PidLidReminderSignalTime 114
2.224 PidLidReminderTime 114
2.225 PidLidReminderTimeDate 114
2.226 PidLidReminderTimeTime 115
2.227 PidLidReminderType 115
2.228 PidLidRemoteStatus 115
2.229 PidLidRequiredAttendees 116
2.230 PidLidResourceAttendees 116
2.231 PidLidResponseStatus 116
2.232 PidLidServerProcessed 117
2.233 PidLidServerProcessingActions 117
2.234 PidLidSharingAnonymity 117
2.235 PidLidSharingBindingEntryId 118
2.236 PidLidSharingBrowseUrl 118
2.237 PidLidSharingCapabilities 118
2.238 PidLidSharingConfigurationUrl 119
2.239 PidLidSharingDataRangeEnd 119
2.240 PidLidSharingDataRangeStart 119
2.241 PidLidSharingDetail 120
2.242 PidLidSharingExtensionXml 120
2.243 PidLidSharingFilter 120
2.244 PidLidSharingFlags 120
2.245 PidLidSharingFlavor 121
2.246 PidLidSharingFolderEntryId 121
2.247 PidLidSharingIndexEntryId 121
2.248 PidLidSharingInitiatorEntryId 122
2.249 PidLidSharingInitiatorName 122
2.250 PidLidSharingInitiatorSmtp 122
2.251 PidLidSharingInstanceGuid 123
2.252 PidLidSharingLastAutoSyncTime 123
2.253 PidLidSharingLastSyncTime 123
2.254 PidLidSharingLocalComment 124
2.255 PidLidSharingLocalLastModificationTime 124
2.256 PidLidSharingLocalName 124
2.257 PidLidSharingLocalPath 125
2.258 PidLidSharingLocalStoreUid 125
2.259 PidLidSharingLocalType 125
2.260 PidLidSharingLocalUid 125
2.261 PidLidSharingOriginalMessageEntryId 126
2.262 PidLidSharingParentBindingEntryId 126
2.263 PidLidSharingParticipants 126
2.264 PidLidSharingPermissions 127
2.265 PidLidSharingProviderExtension 127
2.266 PidLidSharingProviderGuid 127
2.267 PidLidSharingProviderName 128
2.268 PidLidSharingProviderUrl 128

Copyright © 2025 Microsoft Corporation

2.269 PidLidSharingRangeEnd 128
2.270 PidLidSharingRangeStart 129
2.271 PidLidSharingReciprocation 129
2.272 PidLidSharingRemoteByteSize 129
2.273 PidLidSharingRemoteComment 130
2.274 PidLidSharingRemoteCrc 130
2.275 PidLidSharingRemoteLastModificationTime 130
2.276 PidLidSharingRemoteMessageCount 130
2.277 PidLidSharingRemoteName 131
2.278 PidLidSharingRemotePass 131
2.279 PidLidSharingRemotePath 131
2.280 PidLidSharingRemoteStoreUid 132
2.281 PidLidSharingRemoteType 132
2.282 PidLidSharingRemoteUid 132
2.283 PidLidSharingRemoteUser 133
2.284 PidLidSharingRemoteVersion 133
2.285 PidLidSharingResponseTime 133
2.286 PidLidSharingResponseType 134
2.287 PidLidSharingRoamLog 134
2.288 PidLidSharingStart 134
2.289 PidLidSharingStatus 135
2.290 PidLidSharingStop 135
2.291 PidLidSharingSyncFlags 135
2.292 PidLidSharingSyncInterval 135
2.293 PidLidSharingTimeToLive 136
2.294 PidLidSharingTimeToLiveAuto 136
2.295 PidLidSharingWorkingHoursDays 136
2.296 PidLidSharingWorkingHoursEnd 137
2.297 PidLidSharingWorkingHoursStart 137
2.298 PidLidSharingWorkingHoursTimeZone 137
2.299 PidLidSideEffects 138
2.300 PidLidSingleBodyICal 138
2.301 PidLidSmartNoAttach 138
2.302 PidLidSpamOriginalFolder 139
2.303 PidLidStartRecurrenceDate 139
2.304 PidLidStartRecurrenceTime 139
2.305 PidLidTaskAcceptanceState 140
2.306 PidLidTaskAccepted 140
2.307 PidLidTaskActualEffort 140
2.308 PidLidTaskAssigner 141
2.309 PidLidTaskAssigners 141
2.310 PidLidTaskComplete 141
2.311 PidLidTaskCustomFlags 142
2.312 PidLidTaskDateCompleted 142
2.313 PidLidTaskDeadOccurrence 142
2.314 PidLidTaskDueDate 143
2.315 PidLidTaskEstimatedEffort 143
2.316 PidLidTaskFCreator 143
2.317 PidLidTaskFFixOffline 144
2.318 PidLidTaskFRecurring 144
2.319 PidLidTaskGlobalId 144
2.320 PidLidTaskHistory 145
2.321 PidLidTaskLastDelegate 145
2.322 PidLidTaskLastUpdate 145
2.323 PidLidTaskLastUser 145
2.324 PidLidTaskMode 146
2.325 PidLidTaskMultipleRecipients 146
2.326 PidLidTaskNoCompute 146

Copyright © 2025 Microsoft Corporation

2.327 PidLidTaskOrdinal ... 147
2.328 PidLidTaskOwner ... 147
2.329 PidLidTaskOwnership ... 147
2.330 PidLidTaskRecurrence ... 148
2.331 PidLidTaskResetReminder ... 148
2.332 PidLidTaskRole ... 148
2.333 PidLidTaskStartDate ... 149
2.334 PidLidTaskState ... 149
2.335 PidLidTaskStatus ... 150
2.336 PidLidTaskStatusOnComplete ... 150
2.337 PidLidTaskUpdates ... 150
2.338 PidLidTaskVersion ... 151
2.339 PidLidTeamTask ... 151
2.340 PidLidTimeZone ... 151
2.341 PidLidTimeZoneDescription ... 152
2.342 PidLidTimeZoneStruct ... 152
2.343 PidLidToAttendeesString ... 152
2.344 PidLidToDoOrdinalDate ... 153
2.345 PidLidToDoSubOrdinal ... 153
2.346 PidLidToDoTitle ... 153
2.347 PidLidUseTnef ... 154
2.348 PidLidValidFlagStringProof ... 154
2.349 PidLidVerbResponse ... 154
2.350 PidLidVerbStream ... 155
2.351 PidLidWeddingAnniversaryLocal ... 155
2.352 PidLidWeekInterval ... 155
2.353 PidLidWhere ... 156
2.354 PidLidWorkAddress ... 156
2.355 PidLidWorkAddressCity ... 156
2.356 PidLidWorkAddressCountry ... 157
2.357 PidLidWorkAddressCountryCode ... 157
2.358 PidLidWorkAddressPostalCode ... 157
2.359 PidLidWorkAddressPostOfficeBox ... 158
2.360 PidLidWorkAddressState ... 158
2.361 PidLidWorkAddressStreet ... 158
2.362 PidLidYearInterval ... 159
2.363 PidLidYomiCompanyName ... 159
2.364 PidLidYomiFirstName ... 159
2.365 PidLidYomiLastName ... 160
2.366 PidNameAcceptLanguage ... 160
2.367 PidNameApplicationName ... 160
2.368 PidNameAttachmentMacContentType ... 160
2.369 PidNameAttachmentMacInfo ... 161
2.370 PidNameAttachmentOriginalPermissionType ... 161
2.371 PidNameAttachmentPermissionType ... 161
2.372 PidNameAttachmentProviderType ... 162
2.373 PidNameAudioNotes ... 162
2.374 PidNameAuthor ... 162
2.375 PidNameAutomaticSpeechRecognitionData ... 162
2.376 PidNameBirthdayContactAttributionDisplayName ... 163
2.377 PidNameBirthdayContactEntryId ... 163
2.378 PidNameBirthdayContactPersonGuid ... 163
2.379 PidNameByteCount ... 164
2.380 PidNameCalendarAttendeeRole ... 164
2.381 PidNameCalendarBusystatus ... 164
2.382 PidNameCalendarContact ... 164
2.383 PidNameCalendarContactUrl ... 165
2.384 PidNameCalendarCreated ... 165

Copyright © 2025 Microsoft Corporation

2.385 PidNameCalendarDescriptionUrl 165
2.386 PidNameCalendarDuration 166
2.387 PidNameCalendarExceptionDate 166
2.388 PidNameCalendarExceptionRule 166
2.389 PidNameCalendarGeoLatitude 167
2.390 PidNameCalendarGeoLongitude 167
2.391 PidNameCalendarInstanceType 167
2.392 PidNameCalendarIsOrganizer 167
2.393 PidNameCalendarLastModified 168
2.394 PidNameCalendarLocationUrl 168
2.395 PidNameCalendarMeetingStatus 168
2.396 PidNameCalendarMethod 169
2.397 PidNameCalendarProductId 169
2.398 PidNameCalendarRecurrenceIdRange 169
2.399 PidNameCalendarReminderOffset 169
2.400 PidNameCalendarResources 170
2.401 PidNameCalendarRsvp 170
2.402 PidNameCalendarSequence 170
2.403 PidNameCalendarTimeZone 171
2.404 PidNameCalendarTimeZoneId 171
2.405 PidNameCalendarTransparent 171
2.406 PidNameCalendarUid 172
2.407 PidNameCalendarVersion 172
2.408 PidNameCategory 172
2.409 PidNameCharacterCount 172
2.410 PidNameComments 173
2.411 PidNameCompany 173
2.412 PidNameContentBase 173
2.413 PidNameContentClass 174
2.414 PidNameContentType 174
2.415 PidNameCreateDateTimeReadOnly 174
2.416 PidNameCrossReference 175
2.417 PidNameDavId 175
2.418 PidNameDavIsCollection 175
2.419 PidNameDavIsStructuredDocument 176
2.420 PidNameDavParentName 176
2.421 PidNameDavUid 176
2.422 PidNameDocumentParts 176
2.423 PidNameEditTime 177
2.424 PidNameExchangeIntendedBusyStatus 177
2.425 PidNameExchangeJunkEmailMoveStamp 177
2.426 PidNameExchangeModifyExceptionStructure 178
2.427 PidNameExchangeNoModifyExceptions 178
2.428 PidNameExchangePatternEnd 178
2.429 PidNameExchangePatternStart 179
2.430 PidNameExchangeReminderInterval 179
2.431 PidNameExchDatabaseSchema 179
2.432 PidNameExchDataExpectedContentClass 179
2.433 PidNameExchDataSchemaCollectionReference 180
2.434 PidNameExtractedAddresses 180
2.435 PidNameExtractedContacts 180
2.436 PidNameExtractedEmails 181
2.437 PidNameExtractedMeetings 181
2.438 PidNameExtractedPhones 181
2.439 PidNameExtractedTasks 182
2.440 PidNameExtractedUrls 182
2.441 PidNameFrom 182
2.442 PidNameHeadingPairs 182

Copyright © 2025 Microsoft Corporation

2.443 PidNameHiddenCount ... 183
2.444 PidNameHttpmailCalendar ... 183
2.445 PidNameHttpmailHtmlDescription ... 183
2.446 PidNameHttpmailSendMessage ... 184
2.447 PidNameICalendarRecurrenceDate ... 184
2.448 PidNameICalendarRecurrenceRule ... 184
2.449 PidNameInternetSubject ... 184
2.450 PidNameIsBirthdayContactWritable ... 185
2.451 PidNameKeywords ... 185
2.452 PidNameLastAuthor ... 185
2.453 PidNameLastPrinted ... 186
2.454 PidNameLastSaveDateTime ... 186
2.455 PidNameLineCount ... 186
2.456 PidNameLinksDirty ... 187
2.457 PidNameLocationUrl ... 187
2.458 PidNameManager ... 187
2.459 PidNameMeetingDoNotForward ... 187
2.460 PidNameMSIPLabels ... 188
2.461 PidNameMultimediaClipCount ... 188
2.462 PidNameNoteCount ... 188
2.463 PidNameOMSAccountGuid ... 189
2.464 PidNameOMSMobileModel ... 189
2.465 PidNameOMSScheduleTime ... 189
2.466 PidNameOMSServiceType ... 189
2.467 PidNameOMSSourceType ... 190
2.468 PidNamePageCount ... 190
2.469 PidNameParagraphCount ... 190
2.470 PidNamePhishingStamp ... 190
2.471 PidNamePresentationFormat ... 191
2.472 PidNameQuarantineOriginalSender ... 191
2.473 PidNameRevisionNumber ... 191
2.474 PidNameRightsManagementLicense ... 192
2.475 PidNameScale ... 192
2.476 PidNameSecurity ... 192
2.477 PidNameSlideCount ... 192
2.478 PidNameSubject ... 193
2.479 PidNameTemplate ... 193
2.480 PidNameThumbnail ... 193
2.481 PidNameTitle ... 194
2.482 PidNameWordCount ... 194
2.483 PidNameXCallId ... 194
2.484 PidNameXFaxNumberOfPages ... 195
2.485 PidNameXRequireProtectedPlayOnPhone ... 195
2.486 PidNameXSenderTelephoneNumber ... 195
2.487 PidNameXSharingBrowseUrl ... 195
2.488 PidNameXSharingCapabilities ... 196
2.489 PidNameXSharingConfigUrl ... 196
2.490 PidNameXSharingExendedCaps ... 196
2.491 PidNameXSharingFlavor ... 197
2.492 PidNameXSharingInstanceGuid ... 197
2.493 PidNameXSharingLocalType ... 197
2.494 PidNameXSharingProviderGuid ... 197
2.495 PidNameXSharingProviderName ... 198
2.496 PidNameXSharingProviderUrl ... 198
2.497 PidNameXSharingRemoteName ... 198
2.498 PidNameXSharingRemotePath ... 198
2.499 PidNameXSharingRemoteStoreUid ... 199
2.500 PidNameXSharingRemoteType ... 199

Copyright © 2025 Microsoft Corporation

2.501 PidNameXSharingRemoteUid 199
2.502 PidNameXVoiceMessageAttachmentOrder 200
2.503 PidNameXVoiceMessageDuration 200
2.504 PidNameXVoiceMessageSenderName 200
2.505 PidTagAccess 200
2.506 PidTagAccessControlListData 201
2.507 PidTagAccessLevel 201
2.508 PidTagAccount 201
2.509 PidTagAdditionalRenEntryIds 202
2.510 PidTagAdditionalRenEntryIdsEx 202
2.511 PidTagAddressBookAuthorizedSenders 202
2.512 PidTagAddressBookContainerId 203
2.513 PidTagAddressBookDeliveryContentLength 203
2.514 PidTagAddressBookDisplayNamePrintable 203
2.515 PidTagAddressBookDisplayTypeExtended 203
2.516 PidTagAddressBookDistributionListExternalMemberCount 204
2.517 PidTagAddressBookDistributionListMemberCount 204
2.518 PidTagAddressBookDistributionListMemberSubmitAccepted 204
2.519 PidTagAddressBookDistributionListMemberSubmitRejected 205
2.520 PidTagAddressBookDistributionListRejectMessagesFromDLMembers 205
2.521 PidTagAddressBookEntryId 205
2.522 PidTagAddressBookExtensionAttribute1 205
2.523 PidTagAddressBookExtensionAttribute10 206
2.524 PidTagAddressBookExtensionAttribute11 206
2.525 PidTagAddressBookExtensionAttribute12 206
2.526 PidTagAddressBookExtensionAttribute13 207
2.527 PidTagAddressBookExtensionAttribute14 207
2.528 PidTagAddressBookExtensionAttribute15 207
2.529 PidTagAddressBookExtensionAttribute2 208
2.530 PidTagAddressBookExtensionAttribute3 208
2.531 PidTagAddressBookExtensionAttribute4 208
2.532 PidTagAddressBookExtensionAttribute5 208
2.533 PidTagAddressBookExtensionAttribute6 209
2.534 PidTagAddressBookExtensionAttribute7 209
2.535 PidTagAddressBookExtensionAttribute8 209
2.536 PidTagAddressBookExtensionAttribute9 210
2.537 PidTagAddressBookFolderPathname 210
2.538 PidTagAddressBookHierarchicalChildDepartments 210
2.539 PidTagAddressBookHierarchicalDepartmentMembers 210
2.540 PidTagAddressBookHierarchicalIsHierarchicalGroup 211
2.541 PidTagAddressBookHierarchicalParentDepartment 211
2.542 PidTagAddressBookHierarchicalRootDepartment 211
2.543 PidTagAddressBookHierarchicalShowInDepartments 212
2.544 PidTagAddressBookHomeMessageDatabase 212
2.545 PidTagAddressBookIsMaster 212
2.546 PidTagAddressBookIsMemberOfDistributionList 213
2.547 PidTagAddressBookManageDistributionList 213
2.548 PidTagAddressBookManager 213
2.549 PidTagAddressBookManagerDistinguishedName 213
2.550 PidTagAddressBookMember 214
2.551 PidTagAddressBookMessageId 214
2.552 PidTagAddressBookModerationEnabled 214
2.553 PidTagAddressBookNetworkAddress 215
2.554 PidTagAddressBookObjectDistinguishedName 215
2.555 PidTagAddressBookObjectGuid 215
2.556 PidTagAddressBookOrganizationalUnitRootDistinguishedName 215
2.557 PidTagAddressBookOwner 216
2.558 PidTagAddressBookOwnerBackLink 216

Copyright © 2025 Microsoft Corporation

2.559 PidTagAddressBookParentEntryId 216
2.560 PidTagAddressBookPhoneticCompanyName 217
2.561 PidTagAddressBookPhoneticDepartmentName 217
2.562 PidTagAddressBookPhoneticDisplayName 217
2.563 PidTagAddressBookPhoneticGivenName 218
2.564 PidTagAddressBookPhoneticSurname 218
2.565 PidTagAddressBookProxyAddresses 218
2.566 PidTagAddressBookPublicDelegates 219
2.567 PidTagAddressBookReports 219
2.568 PidTagAddressBookRoomCapacity 219
2.569 PidTagAddressBookRoomContainers 219
2.570 PidTagAddressBookRoomDescription 220
2.571 PidTagAddressBookSenderHintTranslations 220
2.572 PidTagAddressBookSeniorityIndex 220
2.573 PidTagAddressBookTargetAddress 221
2.574 PidTagAddressBookUnauthorizedSenders 221
2.575 PidTagAddressBookX509Certificate 221
2.576 PidTagAddressType 222
2.577 PidTagAlternateRecipientAllowed 222
2.578 PidTagAnr 222
2.579 PidTagArchiveDate 222
2.580 PidTagArchivePeriod 223
2.581 PidTagArchiveTag 223
2.582 PidTagAssistant 223
2.583 PidTagAssistantTelephoneNumber 224
2.584 PidTagAssociated 224
2.585 PidTagAttachAdditionalInformation 224
2.586 PidTagAttachContentBase 224
2.587 PidTagAttachContentId 225
2.588 PidTagAttachContentLocation 225
2.589 PidTagAttachDataBinary 225
2.590 PidTagAttachDataObject 226
2.591 PidTagAttachEncoding 226
2.592 PidTagAttachExtension 226
2.593 PidTagAttachFilename 227
2.594 PidTagAttachFlags 227
2.595 PidTagAttachLongFilename 227
2.596 PidTagAttachLongPathname 228
2.597 PidTagAttachmentContactPhoto 228
2.598 PidTagAttachmentFlags 228
2.599 PidTagAttachmentHidden 229
2.600 PidTagAttachmentLinkId 229
2.601 PidTagAttachMethod 229
2.602 PidTagAttachMimeTag 229
2.603 PidTagAttachNumber 230
2.604 PidTagAttachPathname 230
2.605 PidTagAttachPayloadClass 230
2.606 PidTagAttachPayloadProviderGuidString 231
2.607 PidTagAttachRendering 231
2.608 PidTagAttachSize 231
2.609 PidTagAttachTag 232
2.610 PidTagAttachTransportName 232
2.611 PidTagAttributeHidden 232
2.612 PidTagAttributeReadOnly 233
2.613 PidTagAutoForwardComment 233
2.614 PidTagAutoForwarded 233
2.615 PidTagAutoResponseSuppress 233
2.616 PidTagBirthday 234

Copyright © 2025 Microsoft Corporation

2.617 PidTagBlockStatus 234
2.618 PidTagBody 234
2.619 PidTagBodyContentId 235
2.620 PidTagBodyContentLocation 235
2.621 PidTagBodyHtml 235
2.622 PidTagBusiness2TelephoneNumber 236
2.623 PidTagBusiness2TelephoneNumbers 236
2.624 PidTagBusinessFaxNumber 236
2.625 PidTagBusinessHomePage 237
2.626 PidTagBusinessTelephoneNumber 237
2.627 PidTagCallbackTelephoneNumber 237
2.628 PidTagCallId 238
2.629 PidTagCarTelephoneNumber 238
2.630 PidTagCdoRecurrenceid 238
2.631 PidTagChangeKey 238
2.632 PidTagChangeNumber 239
2.633 PidTagChildrensNames 239
2.634 PidTagClientActions 239
2.635 PidTagClientActivelyEditingUntil 240
2.636 PidTagClientSubmitTime 240
2.637 PidTagCodePageId 240
2.638 PidTagComment 241
2.639 PidTagCompanyMainTelephoneNumber 241
2.640 PidTagCompanyName 241
2.641 PidTagComputerNetworkName 242
2.642 PidTagConflictEntryId 242
2.643 PidTagContainerClass 242
2.644 PidTagContainerContents 242
2.645 PidTagContainerFlags 243
2.646 PidTagContainerHierarchy 243
2.647 PidTagContentCount 243
2.648 PidTagContentFilterSpamConfidenceLevel 244
2.649 PidTagContentUnreadCount 244
2.650 PidTagConversationId 244
2.651 PidTagConversationIndex 245
2.652 PidTagConversationIndexTracking 245
2.653 PidTagConversationTopic 245
2.654 PidTagCountry 246
2.655 PidTagCreationTime 246
2.656 PidTagCreatorEntryId 246
2.657 PidTagCreatorName 246
2.658 PidTagCustomerId 247
2.659 PidTagDamBackPatched 247
2.660 PidTagDamOriginalEntryId 247
2.661 PidTagDefaultPostMessageClass 248
2.662 PidTagDeferredActionMessageOriginalEntryId 248
2.663 PidTagDeferredDeliveryTime 248
2.664 PidTagDeferredSendNumber 248
2.665 PidTagDeferredSendTime 249
2.666 PidTagDeferredSendUnits 249
2.667 PidTagDelegatedByRule 249
2.668 PidTagDelegateFlags 250
2.669 PidTagDeleteAfterSubmit 250
2.670 PidTagDeletedCountTotal 250
2.671 PidTagDeletedOn 250
2.672 PidTagDeliverTime 251
2.673 PidTagDepartmentName 251
2.674 PidTagDepth 251

Copyright © 2025 Microsoft Corporation

2.675 PidTagDisplayBcc 252
2.676 PidTagDisplayCc 252
2.677 PidTagDisplayName 252
2.678 PidTagDisplayNamePrefix 253
2.679 PidTagDisplayTo 253
2.680 PidTagDisplayType 253
2.681 PidTagDisplayTypeEx 254
2.682 PidTagEmailAddress 254
2.683 PidTagEndDate 254
2.684 PidTagEntryId 255
2.685 PidTagExceptionEndTime 255
2.686 PidTagExceptionReplaceTime 255
2.687 PidTagExceptionStartTime 255
2.688 PidTagExchangeNTSecurityDescriptor 256
2.689 PidTagExpiryNumber 256
2.690 PidTagExpiryTime 256
2.691 PidTagExpiryUnits 257
2.692 PidTagExtendedFolderFlags 257
2.693 PidTagExtendedRuleMessageActions 257
2.694 PidTagExtendedRuleMessageCondition 258
2.695 PidTagExtendedRuleSizeLimit 258
2.696 PidTagFaxNumberOfPages 258
2.697 PidTagFlagCompleteTime 258
2.698 PidTagFlagStatus 259
2.699 PidTagFlatUrlName 259
2.700 PidTagFolderAssociatedContents 259
2.701 PidTagFolderFlags 260
2.702 PidTagFolderId 260
2.703 PidTagFolderType 260
2.704 PidTagFollowupIcon 261
2.705 PidTagFreeBusyCountMonths 261
2.706 PidTagFreeBusyEntryIds 261
2.707 PidTagFreeBusyMessageEmailAddress 261
2.708 PidTagFreeBusyPublishEnd 262
2.709 PidTagFreeBusyPublishStart 262
2.710 PidTagFreeBusyRangeTimestamp 262
2.711 PidTagFtpSite 263
2.712 PidTagGatewayNeedsToRefresh 263
2.713 PidTagGender 263
2.714 PidTagGeneration 263
2.715 PidTagGivenName 264
2.716 PidTagGovernmentIdNumber 264
2.717 PidTagHasAttachments 264
2.718 PidTagHasDeferredActionMessages 265
2.719 PidTagHasNamedProperties 265
2.720 PidTagHasRules 265
2.721 PidTagHierarchyChangeNumber 265
2.722 PidTagHierRev 266
2.723 PidTagHobbies 266
2.724 PidTagHome2TelephoneNumber 266
2.725 PidTagHome2TelephoneNumbers 267
2.726 PidTagHomeAddressCity 267
2.727 PidTagHomeAddressCountry 267
2.728 PidTagHomeAddressPostalCode 267
2.729 PidTagHomeAddressPostOfficeBox 268
2.730 PidTagHomeAddressStateOrProvince 268
2.731 PidTagHomeAddressStreet 268
2.732 PidTagHomeFaxNumber 269

Copyright © 2025 Microsoft Corporation

2.733 PidTagHomeTelephoneNumber 269
2.734 PidTagHtml 269
2.735 PidTagICalendarEndTime 270
2.736 PidTagICalendarReminderNextTime 270
2.737 PidTagICalendarStartTime 270
2.738 PidTagIconIndex 270
2.739 PidTagImportance 271
2.740 PidTagInConflict 271
2.741 PidTagInitialDetailsPane 271
2.742 PidTagInitials 272
2.743 PidTagInReplyToId 272
2.744 PidTagInstanceKey 272
2.745 PidTagInstanceNum 273
2.746 PidTagInstID 273
2.747 PidTagInternetCodepage 273
2.748 PidTagInternetMailOverrideFormat 274
2.749 PidTagInternetMessageId 274
2.750 PidTagInternetReferences 274
2.751 PidTagIpmAppointmentEntryId 274
2.752 PidTagIpmArchiveEntryId 275
2.753 PidTagIpmContactEntryId 275
2.754 PidTagIpmDraftsEntryId 275
2.755 PidTagIpmJournalEntryId 276
2.756 PidTagIpmNoteEntryId 276
2.757 PidTagIpmTaskEntryId 276
2.758 PidTagIsdnNumber 276
2.759 PidTagJunkAddRecipientsToSafeSendersList 277
2.760 PidTagJunkIncludeContacts 277
2.761 PidTagJunkPermanentlyDelete 277
2.762 PidTagJunkPhishingEnableLinks 278
2.763 PidTagJunkThreshold 278
2.764 PidTagKeyword 278
2.765 PidTagLanguage 278
2.766 PidTagLastModificationTime 279
2.767 PidTagLastModifierEntryId 279
2.768 PidTagLastModifierName 279
2.769 PidTagLastVerbExecuted 280
2.770 PidTagLastVerbExecutionTime 280
2.771 PidTagListHelp 280
2.772 PidTagListSubscribe 281
2.773 PidTagListUnsubscribe 281
2.774 PidTagLocalCommitTime 281
2.775 PidTagLocalCommitTimeMax 281
2.776 PidTagLocaleId 282
2.777 PidTagLocality 282
2.778 PidTagLocation 282
2.779 PidTagMailboxOwnerEntryId 283
2.780 PidTagMailboxOwnerName 283
2.781 PidTagManagerName 283
2.782 PidTagMappingSignature 284
2.783 PidTagMaximumSubmitMessageSize 284
2.784 PidTagMemberId 284
2.785 PidTagMemberName 284
2.786 PidTagMemberRights 285
2.787 PidTagMessageAttachments 285
2.788 PidTagMessageCcMe 285
2.789 PidTagMessageClass 286
2.790 PidTagMessageCodepage 286

Copyright © 2025 Microsoft Corporation

2.791 PidTagMessageDeliveryTime ... 286
2.792 PidTagMessageEditorFormat ... 287
2.793 PidTagMessageFlags ... 287
2.794 PidTagMessageHandlingSystemCommonName ... 287
2.795 PidTagMessageLocaleId ... 288
2.796 PidTagMessageRecipientMe ... 288
2.797 PidTagMessageRecipients ... 288
2.798 PidTagMessageSize ... 288
2.799 PidTagMessageSizeExtended ... 289
2.800 PidTagMessageStatus ... 289
2.801 PidTagMessageSubmissionId ... 289
2.802 PidTagMessageToMe ... 290
2.803 PidTagMid ... 290
2.804 PidTagMiddleName ... 290
2.805 PidTagMimeSkeleton ... 291
2.806 PidTagMobileTelephoneNumber ... 291
2.807 PidTagNativeBody ... 291
2.808 PidTagNextSendAcct ... 292
2.809 PidTagNickname ... 292
2.810 PidTagNonDeliveryReportDiagCode ... 292
2.811 PidTagNonDeliveryReportReasonCode ... 292
2.812 PidTagNonDeliveryReportStatusCode ... 293
2.813 PidTagNonReceiptNotificationRequested ... 293
2.814 PidTagNormalizedSubject ... 293
2.815 PidTagObjectType ... 294
2.816 PidTagOfficeLocation ... 294
2.817 PidTagOfflineAddressBookContainerGuid ... 294
2.818 PidTagOfflineAddressBookDistinguishedName ... 295
2.819 PidTagOfflineAddressBookMessageClass ... 295
2.820 PidTagOfflineAddressBookName ... 295
2.821 PidTagOfflineAddressBookSequence ... 295
2.822 PidTagOfflineAddressBookTruncatedProperties ... 296
2.823 PidTagOrdinalMost ... 296
2.824 PidTagOrganizationalIdNumber ... 296
2.825 PidTagOriginalAuthorEntryId ... 296
2.826 PidTagOriginalAuthorName ... 297
2.827 PidTagOriginalDeliveryTime ... 297
2.828 PidTagOriginalDisplayBcc ... 297
2.829 PidTagOriginalDisplayCc ... 298
2.830 PidTagOriginalDisplayTo ... 298
2.831 PidTagOriginalEntryId ... 298
2.832 PidTagOriginalMessageClass ... 299
2.833 PidTagOriginalMessageId ... 299
2.834 PidTagOriginalSenderAddressType ... 299
2.835 PidTagOriginalSenderEmailAddress ... 299
2.836 PidTagOriginalSenderEntryId ... 300
2.837 PidTagOriginalSenderName ... 300
2.838 PidTagOriginalSenderSearchKey ... 300
2.839 PidTagOriginalSensitivity ... 301
2.840 PidTagOriginalSentRepresentingAddressType ... 301
2.841 PidTagOriginalSentRepresentingEmailAddress ... 301
2.842 PidTagOriginalSentRepresentingEntryId ... 302
2.843 PidTagOriginalSentRepresentingName ... 302
2.844 PidTagOriginalSentRepresentingSearchKey ... 302
2.845 PidTagOriginalSubject ... 302
2.846 PidTagOriginalSubmitTime ... 303
2.847 PidTagOriginatorDeliveryReportRequested ... 303
2.848 PidTagOriginatorNonDeliveryReportRequested ... 303

Copyright © 2025 Microsoft Corporation

2.849 PidTagOscSyncEnabled ... 304
2.850 PidTagOtherAddressCity ... 304
2.851 PidTagOtherAddressCountry ... 304
2.852 PidTagOtherAddressPostalCode ... 305
2.853 PidTagOtherAddressPostOfficeBox ... 305
2.854 PidTagOtherAddressStateOrProvince ... 305
2.855 PidTagOtherAddressStreet ... 306
2.856 PidTagOtherTelephoneNumber ... 306
2.857 PidTagOutOfOfficeState ... 306
2.858 PidTagOwnerAppointmentId ... 306
2.859 PidTagPagerTelephoneNumber ... 307
2.860 PidTagParentEntryId ... 307
2.861 PidTagParentFolderId ... 307
2.862 PidTagParentKey ... 308
2.863 PidTagParentSourceKey ... 308
2.864 PidTagPersonalHomePage ... 308
2.865 PidTagPolicyTag ... 308
2.866 PidTagPostalAddress ... 309
2.867 PidTagPostalCode ... 309
2.868 PidTagPostOfficeBox ... 309
2.869 PidTagPredecessorChangeList ... 310
2.870 PidTagPrimaryFaxNumber ... 310
2.871 PidTagPrimarySendAccount ... 310
2.872 PidTagPrimaryTelephoneNumber ... 311
2.873 PidTagPriority ... 311
2.874 PidTagProcessed ... 311
2.875 PidTagProfession ... 312
2.876 PidTagProhibitReceiveQuota ... 312
2.877 PidTagProhibitSendQuota ... 312
2.878 PidTagPurportedSenderDomain ... 312
2.879 PidTagRadioTelephoneNumber ... 313
2.880 PidTagRead ... 313
2.881 PidTagReadReceiptAddressType ... 313
2.882 PidTagReadReceiptEmailAddress ... 314
2.883 PidTagReadReceiptEntryId ... 314
2.884 PidTagReadReceiptName ... 314
2.885 PidTagReadReceiptRequested ... 314
2.886 PidTagReadReceiptSearchKey ... 315
2.887 PidTagReadReceiptSmtpAddress ... 315
2.888 PidTagReceiptTime ... 315
2.889 PidTagReceivedByAddressType ... 316
2.890 PidTagReceivedByEmailAddress ... 316
2.891 PidTagReceivedByEntryId ... 316
2.892 PidTagReceivedByName ... 317
2.893 PidTagReceivedBySearchKey ... 317
2.894 PidTagReceivedBySmtpAddress ... 317
2.895 PidTagReceivedRepresentingAddressType ... 317
2.896 PidTagReceivedRepresentingEmailAddress ... 318
2.897 PidTagReceivedRepresentingEntryId ... 318
2.898 PidTagReceivedRepresentingName ... 318
2.899 PidTagReceivedRepresentingSearchKey ... 319
2.900 PidTagReceivedRepresentingSmtpAddress ... 319
2.901 PidTagRecipientDisplayName ... 319
2.902 PidTagRecipientEntryId ... 319
2.903 PidTagRecipientFlags ... 320
2.904 PidTagRecipientOrder ... 320
2.905 PidTagRecipientProposed ... 320
2.906 PidTagRecipientProposedEndTime ... 321

Copyright © 2025 Microsoft Corporation

2.907 PidTagRecipientProposedStartTime ... 321
2.908 PidTagRecipientReassignmentProhibited ... 321
2.909 PidTagRecipientTrackStatus ... 321
2.910 PidTagRecipientTrackStatusTime ... 322
2.911 PidTagRecipientType ... 322
2.912 PidTagRecordKey ... 322
2.913 PidTagReferredByName ... 323
2.914 PidTagRemindersOnlineEntryId ... 323
2.915 PidTagRemoteMessageTransferAgent ... 323
2.916 PidTagRenderingPosition ... 324
2.917 PidTagReplyRecipientEntries ... 324
2.918 PidTagReplyRecipientNames ... 324
2.919 PidTagReplyRequested ... 325
2.920 PidTagReplyTemplateId ... 325
2.921 PidTagReplyTime ... 325
2.922 PidTagReportDisposition ... 325
2.923 PidTagReportDispositionMode ... 326
2.924 PidTagReportEntryId ... 326
2.925 PidTagReportingMessageTransferAgent ... 326
2.926 PidTagReportName ... 327
2.927 PidTagReportSearchKey ... 327
2.928 PidTagReportTag ... 327
2.929 PidTagReportText ... 327
2.930 PidTagReportTime ... 328
2.931 PidTagResolveMethod ... 328
2.932 PidTagResponseRequested ... 328
2.933 PidTagResponsibility ... 329
2.934 PidTagRetentionDate ... 329
2.935 PidTagRetentionFlags ... 329
2.936 PidTagRetentionPeriod ... 329
2.937 PidTagRights ... 330
2.938 PidTagRoamingDatatypes ... 330
2.939 PidTagRoamingDictionary ... 330
2.940 PidTagRoamingXmlStream ... 331
2.941 PidTagRowid ... 331
2.942 PidTagRowType ... 331
2.943 PidTagRtfCompressed ... 331
2.944 PidTagRtfInSync ... 332
2.945 PidTagRuleActionNumber ... 332
2.946 PidTagRuleActions ... 332
2.947 PidTagRuleActionType ... 333
2.948 PidTagRuleCondition ... 333
2.949 PidTagRuleError ... 333
2.950 PidTagRuleFolderEntryId ... 333
2.951 PidTagRuleId ... 334
2.952 PidTagRuleIds ... 334
2.953 PidTagRuleLevel ... 334
2.954 PidTagRuleMessageLevel ... 335
2.955 PidTagRuleMessageName ... 335
2.956 PidTagRuleMessageProvider ... 335
2.957 PidTagRuleMessageProviderData ... 335
2.958 PidTagRuleMessageSequence ... 336
2.959 PidTagRuleMessageState ... 336
2.960 PidTagRuleMessageUserFlags ... 336
2.961 PidTagRuleName ... 337
2.962 PidTagRuleProvider ... 337
2.963 PidTagRuleProviderData ... 337
2.964 PidTagRuleSequence ... 338

Copyright © 2025 Microsoft Corporation

2.965 PidTagRuleState ... 338
2.966 PidTagRuleUserFlags ... 338
2.967 PidTagRwRulesStream ... 338
2.968 PidTagScheduleInfoAppointmentTombstone ... 339
2.969 PidTagScheduleInfoAutoAcceptAppointments ... 339
2.970 PidTagScheduleInfoDelegateEntryIds ... 339
2.971 PidTagScheduleInfoDelegateNames ... 340
2.972 PidTagScheduleInfoDelegateNamesW ... 340
2.973 PidTagScheduleInfoDelegatorWantsCopy ... 340
2.974 PidTagScheduleInfoDelegatorWantsInfo ... 340
2.975 PidTagScheduleInfoDisallowOverlappingAppts ... 341
2.976 PidTagScheduleInfoDisallowRecurringAppts ... 341
2.977 PidTagScheduleInfoDontMailDelegates ... 341
2.978 PidTagScheduleInfoFreeBusy ... 342
2.979 PidTagScheduleInfoFreeBusyAway ... 342
2.980 PidTagScheduleInfoFreeBusyBusy ... 342
2.981 PidTagScheduleInfoFreeBusyMerged ... 342
2.982 PidTagScheduleInfoFreeBusyTentative ... 343
2.983 PidTagScheduleInfoMonthsAway ... 343
2.984 PidTagScheduleInfoMonthsBusy ... 343
2.985 PidTagScheduleInfoMonthsMerged ... 344
2.986 PidTagScheduleInfoMonthsTentative ... 344
2.987 PidTagScheduleInfoResourceType ... 344
2.988 PidTagSchedulePlusFreeBusyEntryId ... 344
2.989 PidTagScriptData ... 345
2.990 PidTagSearchFolderDefinition ... 345
2.991 PidTagSearchFolderEfpFlags ... 345
2.992 PidTagSearchFolderExpiration ... 345
2.993 PidTagSearchFolderId ... 346
2.994 PidTagSearchFolderLastUsed ... 346
2.995 PidTagSearchFolderRecreateInfo ... 346
2.996 PidTagSearchFolderStorageType ... 347
2.997 PidTagSearchFolderTag ... 347
2.998 PidTagSearchFolderTemplateId ... 347
2.999 PidTagSearchKey ... 347
2.1000 PidTagSecurityDescriptorAsXml ... 348
2.1001 PidTagSelectable ... 348
2.1002 PidTagSenderAddressType ... 348
2.1003 PidTagSenderEmailAddress ... 349
2.1004 PidTagSenderEntryId ... 349
2.1005 PidTagSenderIdStatus ... 349
2.1006 PidTagSenderName ... 350
2.1007 PidTagSenderSearchKey ... 350
2.1008 PidTagSenderSmtpAddress ... 350
2.1009 PidTagSenderTelephoneNumber ... 351
2.1010 PidTagSendInternetEncoding ... 351
2.1011 PidTagSendRichInfo ... 351
2.1012 PidTagSensitivity ... 352
2.1013 PidTagSentMailSvrEID ... 352
2.1014 PidTagSentRepresentingAddressType ... 352
2.1015 PidTagSentRepresentingEmailAddress ... 353
2.1016 PidTagSentRepresentingEntryId ... 353
2.1017 PidTagSentRepresentingFlags ... 353
2.1018 PidTagSentRepresentingName ... 354
2.1019 PidTagSentRepresentingSearchKey ... 354
2.1020 PidTagSentRepresentingSmtpAddress ... 354
2.1021 PidTagSerializedReplidGuidMap ... 355
2.1022 PidTagSmtpAddress ... 355

Copyright © 2025 Microsoft Corporation

2.1023 PidTagSortLocaleId 355
2.1024 PidTagSourceKey 355
2.1025 PidTagSpokenName 356
2.1026 PidTagSpouseName 356
2.1027 PidTagStartDate 356
2.1028 PidTagStartDateEtc 357
2.1029 PidTagStateOrProvince 357
2.1030 PidTagStoreEntryId 357
2.1031 PidTagStoreState 358
2.1032 PidTagStoreSupportMask 358
2.1033 PidTagStreetAddress 358
2.1034 PidTagSubfolders 358
2.1035 PidTagSubject 359
2.1036 PidTagSubjectPrefix 359
2.1037 PidTagSupplementaryInfo 359
2.1038 PidTagSurname 360
2.1039 PidTagSwappedToDoData 360
2.1040 PidTagSwappedToDoStore 360
2.1041 PidTagTargetEntryId 361
2.1042 PidTagTelecommunicationsDeviceForDeafTelephoneNumber 361
2.1043 PidTagTelexNumber 361
2.1044 PidTagTemplateData 362
2.1045 PidTagTemplateid 362
2.1046 PidTagTextAttachmentCharset 362
2.1047 PidTagThumbnailPhoto 362
2.1048 PidTagTitle 363
2.1049 PidTagTnefCorrelationKey 363
2.1050 PidTagToDoItemFlags 363
2.1051 PidTagTransmittableDisplayName 364
2.1052 PidTagTransportMessageHeaders 364
2.1053 PidTagTrustSender 364
2.1054 PidTagUserCertificate 365
2.1055 PidTagUserEntryId 365
2.1056 PidTagUserX509Certificate 365
2.1057 PidTagViewDescriptorBinary 365
2.1058 PidTagViewDescriptorName 366
2.1059 PidTagViewDescriptorStrings 366
2.1060 PidTagViewDescriptorVersion 366
2.1061 PidTagVoiceMessageAttachmentOrder 367
2.1062 PidTagVoiceMessageDuration 367
2.1063 PidTagVoiceMessageSenderName 367
2.1064 PidTagWeddingAnniversary 367
2.1065 PidTagWlinkAddressBookEID 368
2.1066 PidTagWlinkAddressBookStoreEID 368
2.1067 PidTagWlinkCalendarColor 368
2.1068 PidTagWlinkClientID 369
2.1069 PidTagWlinkEntryId 369
2.1070 PidTagWlinkFlags 369
2.1071 PidTagWlinkFolderType 369
2.1072 PidTagWlinkGroupClsid 370
2.1073 PidTagWlinkGroupHeaderID 370
2.1074 PidTagWlinkGroupName 370
2.1075 PidTagWlinkOrdinal 370
2.1076 PidTagWlinkRecordKey 371
2.1077 PidTagWlinkROGroupType 371
2.1078 PidTagWlinkSaveStamp 371
2.1079 PidTagWlinkSection 372
2.1080 PidTagWlinkStoreEntryId 372

Copyright © 2025 Microsoft Corporation

2.1081 PidTagWlinkType 372
3 Structure Examples 373
4 Security 374
4.1 Security Considerations for Implementers 374
4.2 Index of Security Fields 374
5 Appendix A: Product Behavior 375
6 Change Tracking 376
7 Index 377

Copyright © 2025 Microsoft Corporation

1 Introduction

The Exchange Server Protocols Master Property List provides implementers with a single source of information about all the properties that are described by the specifications that comprise the Exchange Server Protocols documentation. If a property is not described by the specifications included in the Exchange Server Protocols documentation, it is not included in this document.

The criteria for including a property in the Exchange Server Protocols documentation are that it is set by a client in order to affect server behavior, or that it is set by a server in order to affect client behavior. Properties that are merely stored by the server on behalf of the client, or generated by the server for its own use and ignored by the client, are not necessarily documented. As a result, the properties that are included in the Exchange Server Protocols documentation, and therefore this document, are the critical **Message object** properties used for communication between clients and servers.

This document provides implementers with a convenient catalog of all these critical properties, a source of navigation to the individual technical specifications that describe these properties in detail, and a resource for additional helpful property information that is unique to this document.

Sections 1.7 and 2 of this specification are normative. All other sections and examples in this specification are informative.

1.1 Glossary

This document uses the following terms:

8.3 name: A file name string restricted in length to 12 characters that includes a base name of up to eight characters, one character for a period, and up to three characters for a file name extension. For more information on 8.3 file names, see [MS-CIFS] section 2.2.1.1.1.

action: A discrete operation that is executed on an incoming **Message object** when all conditions in the same **rule** are TRUE. A rule contains one or more actions.

address book container: An **Address Book object** that describes an **address list**.

Address Book object: An entity in an address book that contains a set of attributes, each attribute with a set of associated values.

address list: A collection of distinct **Address Book objects**.

address type: An identifier for the type of email address, such as **SMTP** and EX.

alias: An alternate name that can be used to reference an object or element.

ambiguous name resolution (ANR): A search algorithm that permits a client to search multiple naming-related attributes on objects by way of a single clause of the form "(anr=value)" in a Lightweight Directory Access Protocol (LDAP) search filter. This permits a client to query for an object when the client possesses some identifying material related to the object but does not know which attribute of the object contains that identifying material.

Appointment object: A **Calendar object** that has an organizer but no attendees.

Archive folder: A **special folder** that is the default location for objects that have been archived.

archive tag: An element that contains information about the archive policy of a **Message object** or folder.

Copyright © 2025 Microsoft Corporation

Attachment object: A set of properties that represents a file, **Message object**, or structured storage that is attached to a Message object and is visible through the attachments table for a Message object.

Augmented Backus-Naur Form (ABNF): A modified version of Backus-Naur Form (BNF), commonly used by Internet specifications. ABNF notation balances compactness and simplicity with reasonable representational power. ABNF differs from standard BNF in its definitions and uses of naming rules, repetition, alternatives, order-independence, and value ranges. For more information, see [RFC5234].

blind carbon copy (Bcc) recipient: An addressee on a **Message object** that is not visible to recipients of the Message object.

body part: A part of an Internet message, as described in [RFC2045].

calendar: A date range that shows availability, **meetings**, and appointments for one or more users or **resources**. See also **Calendar object**.

Calendar folder: A **Folder object** that contains **Calendar objects**.

Calendar object: A **Message object** that represents an event, which can be a one-time event or a recurring event. The Calendar object includes properties that specify event details such as description, organizer, date and time, and status.

carbon copy (Cc) recipient: An address on a **Message object** that is visible to recipients of the Message object but is not necessarily expected to take any action.

class: User-defined binary data that is associated with a key.

Classification, labeling, and protection: Classification is determining that an email has sensitive or otherwise interesting content in it. Labeling is tagging the email with an administrator-defined sensitivity label that travels with the email. Protection is enforcing administrator-defined outcomes based on the sensitivity label.

common name (CN): A string attribute of a certificate that is one component of a **distinguished name (DN)**. In Microsoft Enterprise uses, a CN has to be unique within the forest where it is defined and any forests that share trust with the defining forest. The website or email address of the certificate owner is often used as a common name. Client applications often refer to a certification authority (CA) by the CN of its signing certificate.

contact: A person, company, or other entity that is stored in a directory and is associated with one or more unique identifiers and attributes, such as an Internet message address or login name.

contents table: A Table object whose rows represent the **Message objects** that are contained in a **Folder object**.

conversation: A single representation of a send/response series of email messages. A conversation appears in the Inbox as one unit and allows the user to view and read the series of related email messages in a single effort.

conversation action: A limited set of actions that a user applies to all **Message objects** that have the same PidTagConversationId value. The action is applied to all Message objects that are currently in the store or are delivered in the future.

Coordinated Universal Time (UTC): A high-precision atomic time standard that approximately tracks Universal Time (UT). It is the basis for legal, civil time all over the Earth. Time zones around the world are expressed as positive and negative offsets from UTC. In this role, it is also referred to as Zulu time (Z) and Greenwich Mean Time (GMT). In these specifications, all references to UTC refer to the time at UTC-0 (or GMT).

Copyright © 2025 Microsoft Corporation

counter proposal: A request that an attendee sends to an **organizer** when requesting a change to the date or time of a meeting.

cyclic redundancy check (CRC): An algorithm used to produce a checksum (a small, fixed number of bits) against a block of data, such as a packet of network traffic or a block of a computer file. The CRC is a broad class of functions used to detect errors after transmission or storage. A CRC is designed to catch random errors, as opposed to intentional errors. If errors might be introduced by a motivated and intelligent adversary, a cryptographic hash function has to be used instead.

Deferred Action Message (DAM): A hidden message indicating to a client that it needs to execute one or more **rules** on another user-visible message in the store.

delegate: A user or resource that has permissions to act on behalf of another user or resource.

delivery receipt: A report message that is generated and sent by a client or server to the sender of a message or another designated recipient when an email message is received by an intended recipient.

Department object: An **Address Book object** that describes a department within an organization.

departmental group: A **distribution list** that describes a department within an organization.

display name: A text string that is used to identify a principal or other object in the user interface. Also referred to as title.

display template: A template that describes how to display or allow a user to modify information about an **Address Book object**.

distinguished name (DN): A name that uniquely identifies an object by using the relative distinguished name (RDN) for the object, and the names of container objects and domains that contain the object. The distinguished name (DN) identifies the object and its location in a tree.

distribution list: A collection of users, computers, contacts, or other groups that is used only for email distribution, and addressed as a single recipient.

Document object: A **Message object** that represents a single file, such as a document generated by a word-processing application. The Message object contains the file as an **Attachment object** and includes additional properties to describe the file.

domain: A set of users and computers sharing a common namespace and management infrastructure. At least one computer member of the set has to act as a domain controller (DC) and host a member list that identifies all members of the domain, as well as optionally hosting the Active Directory service. The domain controller provides authentication of members, creating a unit of trust for its members. Each domain has an identifier that is shared among its members. For more information, see [MS-AUTHSOD] section 1.1.1.5 and [MS-ADTS].

double-byte character set (DBCS): A character set that can use more than one byte to represent a single character. A DBCS includes some characters that consist of 1 byte and some characters that consist of 2 bytes. Languages such as Chinese, Japanese, and Korean use DBCS.

Email object: A **Message object** that represents an email message in a message store and adheres to the property descriptions that are described in in [MS-OXOMSG].

entry ID: See **EntryID**.

EntryID: A sequence of bytes that is used to identify and access an object.

Exception Embedded Message object: An Embedded Message object that contains the changes for an Exception object.

Copyright © 2025 Microsoft Corporation

Exception object: An instance of a **recurring series** that differs from the rest of the recurring series, for example by start time.

File Transfer Protocol (FTP): A member of the TCP/IP suite of protocols that is used to copy files between two computers on the Internet if both computers support their respective FTP roles. One computer is an FTP client and the other is an FTP server.

flags: A set of values used to configure or report options or settings.

folder associated information (FAI): A collection of **Message objects** that are stored in a Folder object and are typically hidden from view by email applications. An FAI Message object is used to store a variety of settings and auxiliary data, including forms, views, calendar options, favorites, and category lists.

Folder object: A messaging construct that is typically used to organize data into a hierarchy of objects containing Message objects and **folder associated information (FAI)** Message objects.

free/busy status: A property of an appointment that indicates how an appointment on the **calendar** of an attendee or resource affects their availability.

Global Address List (GAL): An **address list** that conceptually represents the default address list for an address book.

globally unique identifier (GUID): A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [RFC4122] or [C706] have to be used for generating the GUID. See also universally unique identifier (UUID).

group header: A **navigation shortcut** that groups other navigation shortcuts.

Hypertext Markup Language (HTML): An application of the Standard Generalized Markup Language (SGML) that uses tags to mark elements in a document, as described in [HTML].

Hypertext Transfer Protocol (HTTP): An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

instance: A unique publication of data for a category. It enables a publisher to publish data for the same category multiple times. An example is a publisher who uses two different endpoints to publish data. These endpoints can publish the same category. However, each endpoint requires a different instance number to be considered a distinct publication by the server. An instance number is provided by the publishing client.

Integrated Services Digital Network (ISDN): A high-speed digital technology that uses existing telephone lines to provide Internet access and digital network services.

Journal object: A **Message object** that represents an entry in a journal or log and adheres to the property descriptions that are described in in [MS-OXOJRNL].

locale: A collection of rules and data that are specific to a language and a geographical area. A locale can include information about sorting rules, date and time formatting, numeric and monetary conventions, and character classification.

Logon object: A **Server object** that provides access to a private **mailbox** or a **public folder**. A client obtains a Logon object by issuing a RopLogon remote operation (ROP) to a server.

long ID (LID): A 32-bit quantity that, in combination with a GUID, defines a **named property**.

Copyright © 2025 Microsoft Corporation

mail tip: A note that is presented to the author of a message when the author is composing the message. A mail tip provides information about the recipients of a message and issues that might impact delivery of the message, such as moderation or delivery restrictions.

mail user: An **Address Book object** that represents a person or entity that can receive deliverable messages.

mailbox: A **message store** that contains email, calendar items, and other **Message objects** for a single recipient.

meeting: An event with attendees.

Meeting object: A **Calendar object** that has both an organizer and attendees.

meeting request: An instance of a **Meeting Request object**.

Meeting Request object: A **Message object** that represents an invitation from the meeting organizer to an attendee.

Meeting Response object: A **Message object** that represents an attendee's response to a meeting organizer's invitation. The response indicates whether the attendee accepted, tentatively accepted, or declined the meeting request. The response can include a proposed new date or time for the meeting.

Meeting Update object: A **Message object** that represents a meeting organizer's changes to a previously scheduled meeting. The update is categorized as either a full update or an informational update.

Meeting Workspace: A website that is created by using the Meetings Web Services protocol, as described in [MS-MEETS]. It can host documents, discussions, and other information about a meeting.

meeting-related object: A **Message object** that represents a relay of information between a meeting organizer and an attendee. It can be any of the following: **Meeting Request object**, **Meeting Update object**, Meeting Cancellation object, or **Meeting Response object**.

message body: The main message text of an email message. A few properties of a **Message object** represent its message body, with one property containing the text itself and others defining its code page and its relationship to alternative body formats.

message class: A property that loosely defines the type of a message, contact, or other Personal Information Manager (PIM) object in a mailbox.

Message object: A set of properties that represents an email message, appointment, contact, or other type of personal-information-management object. In addition to its own properties, a Message object contains recipient properties that represent the addressees to which it is addressed, and an attachments table that represents any files and other Message objects that are attached to it.

message store: A unit of containment for a single hierarchy of Folder objects, such as a mailbox or public folders.

Messaging Application Programming Interface (MAPI): A messaging architecture that enables multiple applications to interact with multiple messaging systems across a variety of hardware platforms.

messaging object: An object that exists in a **mailbox**. It can be only a **Folder object** or a **Message object**.

MIME message: A message that is as described in [RFC2045], [RFC2046], and [RFC2047].

Copyright © 2025 Microsoft Corporation

MIME part: A message part that is as described in [RFC2045], [RFC2046], and [RFC2047].

Multipurpose Internet Mail Extensions (MIME): A set of extensions that redefines and expands support for various types of content in email messages, as described in [RFC2045], [RFC2046], and [RFC2047].

name service provider interface (NSPI): A method of performing address-book-related operations on Active Directory.

named property: A property that is identified by both a GUID and either a string name or a 32-bit identifier.

navigation shortcut: An object that contains identifying information to locate a folder in a message database or an object that groups other navigation shortcuts.

non-Unicode: A character set that has a restricted set of glyphs, such as Shift_JIS or ISO-2022-JP.

Note object: A **Message object** that represents a simple text note in a messaging store and that adheres to the property descriptions that are described in [MS-OXONOTE]. A Note object functions as an electronic equivalent of a paper sticky note.

offline address book (OAB): A collection of **address lists** that are stored in a format that a client can save and use locally.

optional attendee: An attendee of an event whom the organizer lists as an optional participant.

organizer: The owner or creator of a **meeting** or appointment.

orphan instance: An instance of an event that is in a **recurring series** and is in a Calendar folder without the recurring series. For all practical purposes, this is a single instance.

Out of Office (OOF): One of the possible values for the **free/busy status** on an appointment. It indicates that the user will not be in the office during the appointment.

Permanent Entry ID: A property of an **Address Book object** that can be used to uniquely identify the object.

permission: A rule that is associated with an object and that regulates which users can gain access to the object and in what manner. See also rights.

phishing: The luring of sensitive information, such as passwords or other personal information, from a recipient by masquerading as someone who is trustworthy and has a real need for such information.

plain text: Text that does not have markup. See also plain text message body.

primary recipient: A person for whom a message is directly intended.

property ID: A 16-bit numeric identifier of a specific attribute. A property ID does not include any **property type** information.

property name: A string that, in combination with a **property set**, identifies a **named property**.

property set: A set of attributes, identified by a **GUID**. Granting access to a property set grants access to all the attributes in the set.

property type: A 16-bit quantity that specifies the data type of a property value.

public folder: A **Folder object** that is stored in a location that is publicly available.

Copyright © 2025 Microsoft Corporation

read receipt: An email message that is sent to the sender of a message to indicate that a message recipient received the message.

recipient: An entity that is in an **address list**, can receive email messages, and contains a set of attributes. Each attribute has a set of associated values.

recipient table: The part of a **Message object** that represents users to whom a message is addressed. Each row of the table is a set of properties that represents one **recipient**.

recurrence pattern: Information for a repeating event, such as the start and end time, the number of occurrences, and how occurrences are spaced, such as daily, weekly, or monthly.

Recurring Calendar object: A **Calendar object** that describes an event that repeats according to a recurrence pattern.

recurring series: An event that repeats at specific intervals of time according to a recurrence pattern.

recurring task: A series of **Task objects** that are described by a recurrence pattern.

reminder: A generally user-visible notification that a specified time has been reached. A reminder is most commonly related to the beginning of a meeting or the due time of a task but it can be applied to any object type.

replica GUID (REPLGUID): A value that represents a namespace for identifiers. If a REPLGUID is combined with a GLOBSET, the result is a set of global identifiers. A REPLGUID value has an associated **replica ID (REPLID)** that is used in its place on disk and on the wire.

replica ID (REPLID): A value that is mapped to a **replica GUID (REPLGUID)** that identifies a namespace for IDs within a given logon. REPLIDs are used on disk and on the wire for compactness, and are replaced with the corresponding REPLGUID for external consumption.

resource: Any component that a computer can access that can read, write, and process data. This includes internal components (such as a disk drive), a service, or an application running on and managed by the cluster on a network that is used to access a file.

Resource object: An **Address Book object** that represents an asset that can be reserved, such as a room or equipment.

retention tag: An element that contains information about the retention policy of a **Message object** or folder.

Rich Text Format (RTF): Text with formatting as described in [MSFT-RTF].

rights-managed email message: An email message that specifies permissions that are designed to protect its content from inappropriate access, use, and distribution.

root folder: The folder at the top of a hierarchy of folders in a list.

ROP buffer: A structure containing an array of bytes that encode a remote operation (ROP). The first byte in the buffer identifies the ROP. This byte is followed by ROP-specific fields. Multiple ROP buffers can be packed into a single remote procedure call (RPC) request or response.

rule: An item that defines a condition and an action. The condition is evaluated for each **Message object** as it is delivered, and the action is executed if the new Message object matches the condition.

Rule FAI message: A **folder associated information (FAI)** message stored in the Inbox special folder where the client can store extra rule-related information that is opaque to the server.

Copyright © 2025 Microsoft Corporation

Sent Items folder: A **special folder** that is the default location for storing copies of **Message objects** after they are submitted or sent.

server object: A class of object in the configuration naming context (config NC). A **server object** can have an nTDSDSA object as a child.

Short Message Service (SMS): A communications protocol that is designed for sending text messages between mobile phones.

signal time: The time at which a **reminder** has been specified to notify the user or an agent acting on behalf of the user. For example, the signal time for a meeting that starts at 11:00 A.M. can be 10:45 A.M., thus allowing the user 15 minutes to prepare for or travel to the meeting upon receiving the notification.

Simple Mail Transfer Protocol (SMTP): A member of the TCP/IP suite of protocols that is used to transport Internet messages, as described in [RFC5321].

site mailbox: A repository comprised of a mailbox and a web-based collaboration environment that is presented to users as a mailbox in an email client. A site mailbox uses team membership to determine which users have access to the repository.

soft delete: A process that removes an item from the system, but not permanently. If an item is soft deleted, a server retains a back-up copy of the item and a client can access, restore, or permanently delete the item. See also hard delete.

spam: An unsolicited email message.

spam filter: A filter that checks certain conditions in a message to determine a spam confidence level.

special folder: One of a default set of **Folder objects** that can be used by an implementation to store and retrieve user data objects.

stream: A flow of data from one host to another host, or the data that flows between two hosts.

tagged property: A property that is defined by a 16-bit property ID and a 16-bit property type. The property ID for a tagged property is in the range 0x001 – 0x7FFF. Property IDs in the range 0x8000 – 0x8FFF are reserved for assignment to **named properties**.

Task object: A **Message object** that represents an assignment to be completed.

task request: A **Message object** that is used to issue a task assignment.

Transmission Control Protocol (TCP): A protocol used with the Internet Protocol (IP) to send data in the form of message units between computers over the Internet. TCP handles keeping track of the individual units of data (called packets) that a message is divided into for efficient routing through the Internet.

Transport Neutral Encapsulation Format (TNEF): A binary type-length-value encoding that is used to encode properties for transport, as described in [MS-OXTNEF].

Unicode: A character encoding standard developed by the Unicode Consortium that represents almost all of the written languages of the world. The **Unicode** standard [UNICODE5.0.0/2007] provides three forms (UTF-8, UTF-16, and UTF-32) and seven schemes (UTF-8, UTF-16, UTF-16 BE, UTF-16 LE, UTF-32, UTF-32 LE, and UTF-32 BE).

Uniform Resource Identifier (URI): A string that identifies a resource. The URI is an addressing mechanism defined in Internet Engineering Task Force (IETF) Uniform Resource Identifier (URI): Generic Syntax [RFC3986].

Copyright © 2025 Microsoft Corporation

Uniform Resource Locator (URL): A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [RFC1738].

unsendable attendee: An attendee to whom a **meeting request** or meeting update is not sent.

Use License: An XrML 1.2 license that authorizes a user to gain access to a protected content file and describes the applicable usage policies. Also referred to as "End-User License (EUL)."

Web Distributed Authoring and Versioning Protocol (WebDAV): The Web Distributed Authoring and Versioning Protocol, as described in [RFC2518] or [RFC4918].

X500 DN: A distinguished name (DN), in Teletex form, of an object that is in an address book. An X500 DN can be more limited in the size and number of relative distinguished names (RDNs) than a full DN.

XML: The Extensible Markup Language, as described in [XML1.0].

XML document: A document object that is well formed, as described in [XML10/5], and might be valid. An XML document has a logical structure that is composed of declarations, elements, comments, character references, and processing instructions. It also has a physical structure that is composed of entities, starting with the root, or document, entity.

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as defined in [RFC2119]. All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the Errata.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information.

[ISO/IEC8802-3] ISO/IEC, "Information technology -- Telecommunications and information exchange between systems -- Local and metropolitan area networks -- Specific requirements -- Part 3", Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, ISO/IEC 8802-3:2000, http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=31002

[MS-OXABREF] Microsoft Corporation, "Address Book Name Service Provider Interface (NSPI) Referral Protocol".

[MS-OXBBODY] Microsoft Corporation, "Best Body Retrieval Algorithm".

[MS-OXCDATA] Microsoft Corporation, "Data Structures".

[MS-OXCEXT] Microsoft Corporation, "Client Extension Message Object Protocol".

[MS-OXCFOLD] Microsoft Corporation, "Folder Object Protocol".

[MS-OXCFXICS] Microsoft Corporation, "Bulk Data Transfer Protocol".

[MS-OXCICAL] Microsoft Corporation, "iCalendar to Appointment Object Conversion Algorithm".

Copyright © 2025 Microsoft Corporation

[MS-OXCMAIL] Microsoft Corporation, "RFC 2822 and MIME to Email Object Conversion Algorithm".

[MS-OXCMSG] Microsoft Corporation, "Message and Attachment Object Protocol".

[MS-OXCPERM] Microsoft Corporation, "Exchange Access and Operation Permissions Protocol".

[MS-OXCPRPT] Microsoft Corporation, "Property and Stream Object Protocol".

[MS-OXCROPS] Microsoft Corporation, "Remote Operations (ROP) List and Encoding Protocol".

[MS-OXCRPC] Microsoft Corporation, "Wire Format Protocol".

[MS-OXCSPAM] Microsoft Corporation, "Spam Confidence Level Protocol".

[MS-OXCSTOR] Microsoft Corporation, "Store Object Protocol".

[MS-OXCTABL] Microsoft Corporation, "Table Object Protocol".

[MS-OXLDAP] Microsoft Corporation, "Lightweight Directory Access Protocol (LDAP) Version 3 Extensions".

[MS-OXMSG] Microsoft Corporation, "Outlook Item (.msg) File Format".

[MS-OXNSPI] Microsoft Corporation, "Exchange Server Name Service Provider Interface (NSPI) Protocol".

[MS-OXOABKT] Microsoft Corporation, "Address Book User Interface Templates Protocol".

[MS-OXOABK] Microsoft Corporation, "Address Book Object Protocol".

[MS-OXOAB] Microsoft Corporation, "Offline Address Book (OAB) File Format and Schema".

[MS-OXOCAL] Microsoft Corporation, "Appointment and Meeting Object Protocol".

[MS-OXOCFG] Microsoft Corporation, "Configuration Information Protocol".

[MS-OXOCNTC] Microsoft Corporation, "Contact Object Protocol".

[MS-OXODLGT] Microsoft Corporation, "Delegate Access Configuration Protocol".

[MS-OXODOC] Microsoft Corporation, "Document Object Protocol".

[MS-OXOFLAG] Microsoft Corporation, "Informational Flagging Protocol".

[MS-OXOJRNL] Microsoft Corporation, "Journal Object Protocol".

[MS-OXOMSG] Microsoft Corporation, "Email Object Protocol".

[MS-OXONOTE] Microsoft Corporation, "Note Object Protocol".

[MS-OXOPFFB] Microsoft Corporation, "Public Folder-Based Free/Busy Protocol".

[MS-OXOPOST] Microsoft Corporation, "Post Object Protocol".

[MS-OXORMDR] Microsoft Corporation, "Reminder Settings Protocol".

[MS-OXORMMS] Microsoft Corporation, "Rights-Managed Email Object Protocol".

[MS-OXORSS] Microsoft Corporation, "RSS Object Protocol".

Copyright © 2025 Microsoft Corporation

[MS-OXORULE] Microsoft Corporation, "Email Rules Protocol".

[MS-OXOSFLD] Microsoft Corporation, "Special Folders Protocol".

[MS-OXOSMIME] Microsoft Corporation, "S/MIME Email Object Algorithm".

[MS-OXOSMMS] Microsoft Corporation, "Short Message Service (SMS) and Multimedia Messaging Service (MMS) Object Protocol".

[MS-OXOSRCH] Microsoft Corporation, "Search Folder List Configuration Protocol".

[MS-OXOTASK] Microsoft Corporation, "Task-Related Objects Protocol".

[MS-OXOUM] Microsoft Corporation, "Voice Mail and Fax Objects Protocol".

[MS-OXPFOAB] Microsoft Corporation, "Offline Address Book (OAB) Public Folder Retrieval Protocol".

[MS-OXPHISH] Microsoft Corporation, "Phishing Warning Protocol".

[MS-OXPSVAL] Microsoft Corporation, "Email Postmark Validation Algorithm".

[MS-OXRTFCP] Microsoft Corporation, "Rich Text Format (RTF) Compression Algorithm".

[MS-OXRTFEX] Microsoft Corporation, "Rich Text Format (RTF) Extensions Algorithm".

[MS-OXSHARE] Microsoft Corporation, "Sharing Message Object Protocol".

[MS-OXTNEF] Microsoft Corporation, "Transport Neutral Encapsulation Format (TNEF) Data Algorithm".

[MS-OXVCARD] Microsoft Corporation, "vCard to Contact Object Conversion Algorithm".

[MS-OXWAVLS] Microsoft Corporation, "Availability Web Service Protocol".

[MS-WMF] Microsoft Corporation, "Windows Metafile Format".

[MS-XWDCAL] Microsoft Corporation, "Web Distributed Authoring and Versioning (WebDAV) Extensions for Calendar Support".

[MS-XWDVSEC] Microsoft Corporation, "Web Distributed Authoring and Versioning (WebDAV) Protocol Security Descriptor Extensions".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, https://www.rfc-editor.org/info/rfc2119

[RFC3464] Moore, K., and Vaudreuil, G., "An Extensible Message Format for Delivery Status Notifications", RFC 3464, January 2003, http://www.rfc-editor.org/rfc/rfc3464.txt

[RFC3798] Hansen, T., and Vaudreuil, G., Eds., "Message Disposition Notification", RFC 3798, May 2004, http://www.rfc-editor.org/rfc/rfc3798.txt

1.2.2 Informative References

[MS-OXPROTO] Microsoft Corporation, "Exchange Server Protocols System Overview".

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, https://www.rfc-editor.org/info/rfc5234

Copyright © 2025 Microsoft Corporation

1.3 Overview

Each property listing in this document contains a link to the section of the technical specification in the Exchange Server Protocols documentation that acts as the defining reference for the property. The defining reference for each property contains the semantic use and definition of the property, including the property data type. The property information that is included in the defining reference for each property is required to successfully parse property data. As such, this document provides implementers with a single source of navigation to all of the critical property information that is included in the individual Exchange Server Protocols technical specifications.

This document also provides additional information about each property that is helpful to the implementer, such as the functional area where the property is used, a list of all the technical specifications that cite the property, and a list of alternate names by which the canonical property is known within the system. This information is not included in the technical specifications that describe each property, and is unique to this document. It is provided for informational purposes only.

A typical scenario for using this document is when an implementer encounters both **property IDs** and property values with no other identification coming across the wire. The property data type and the semantic definition of the property that are included in the defining reference for each property allow the implementer to correctly parse property values that show up in **ROP buffers**. The parsed values in the ROP buffers include lists of property IDs, which are typically lists of four hexadecimal characters. By searching the information in this document for those four hexadecimal characters, the implementer can quickly name the associated property and navigate to the definition of the individual property in its defining specification.

The following information is provided for each property, as appropriate.

Alternate names: Alternate names are implementation-specific names for properties that are used in source code and non-protocol-related documentation. Information about alternate names is useful when the implementer needs to refer to legacy documentation about a specific canonical property.

Area: The functional area where the property is used. Sections 1.3.1. 1.3.2, and 1.3.3 describe the general functional areas where properties are used. The listing for each property in section 2 describes the areas with more varied descriptions so as to provide more insight into property usage.

Canonical name: The name used to refer to the property in the Exchange Server Protocols documentation. The prefix of the canonical name identifies the basic characteristics of a property to the implementer.

The canonical naming structure uses three categories that are denoted by the following prefixes to the canonical **property name**:

- PidLid prefix: Properties identified by an unsigned 32-bit quantity along with a property set.
- PidName prefix: Properties identified by a string name along with a property set.
- PidTag prefix: Properties identified by an unsigned 16-bit quantity.

Description: A brief description of the contents of the property.

Data type: The property value type, as described in [MS-OXCDATA], that specifies the type of values allowed for the property.

Property ID: An unsigned 16-bit quantity that identifies a **tagged property**. Property IDs are not necessarily unique. With the exception of property IDs in the range from 0x6800 to 0x7BFF (see section 1.3.3), the combination of property ID and data type are unique. Property IDs in the range from 0x6800 to 0x7BFF are defined by the **message class**.

Property long ID (LID): An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

Copyright © 2025 Microsoft Corporation

Property name: A string that, along with the property set, identifies a named property.

Property set: A **GUID** that identifies a group of properties with a similar purpose.

Defining references: One or more technical specifications that describe the semantics and allowed values for the property.

Consuming references: One or more technical specifications that refer to the property but do not describe semantics and allowed values.

1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's **message class**. The following table describes several common message classes, the functional area to which each one corresponds, and the specification that describes each one's required and optional properties.

In the following table, an asterisk "*" denotes that any string can appear at that point.

Area name	PidTagMessageClass property values	Specification
Common	IPM.*	[MS-OXCMSG]
Email	IPM.Note, REPORT.*	[MS-OXCMSG]
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	[MS-OXOCAL]
Contact	IPM.Contact, IPM.DistList	[MS-OXOCNTC]
Task	IPM.Task, IPM.TaskRequest.*	[MS-OXOTASK]
Journal	IPM.Activity	[MS-OXOJRNL]
Sticky Note	IPM.StickyNote	[MS-OXONOTE]
Document	IPM.Document.*	[MS-OXODOC]
Post	IPM.Post	[MS-OXOPOST]
RSS Feed	IPM.Post.RSS	[MS-OXORSS]
Rights-managed Email	IPM.Note with PidNameContentClass= rpmsg.message	[MS-OXORMMS]
S/MIME Email	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	[MS-OXOSMIME]
Short Message Service (SMS) / Multimedia Message Service (MMS) Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	[MS-OXOSMMS]
Unified Messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	[MS-OXOUM]
Sharing	IPM.Sharing IPM.Sharing.*	[MS-OXSHARE]

Copyright © 2025 Microsoft Corporation

1.3.2 Commonly Used Property Sets

Each **named property** specified in the list in section 2 is listed with the **GUID** that describes its **property set**. Several of the more common property sets and their functional areas are described in the following table.

Area name	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}
Common	PSETID_Common {00062008-0000-0000-C000-000000000046}
Contact	PSETID_Address {00062004-0000-0000-C000-000000000046}
Email	PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-000000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-000000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-000000000046}
RSS feed	PSETID_PostRss {00062041-0000-0000-C000-000000000046}
Task	PSETID_Task {00062003-0000-0000-C000-000000000046}
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing {00062040-0000-0000-C000-000000000046}
Extracted entities	PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Copyright © 2025 Microsoft Corporation

Area name	Property set name and GUID value
Attachment	PSETID_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

1.3.3 Property ID Ranges

The 65,536 possible values of the **property ID** are divided into sub-ranges reserved for various purposes, as described in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an email transport protocol (such as **SMTP**), and not to any network transport protocol (such as **TCP**):

- Servers do not allow property IDs in ranges specified as non-transmittable to be submitted for transport to another server via an email transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.
- Clients can use properties in ranges described as **message class**-defined for application-defined purposes. When doing so, applications specify a value for the **PidTagMessageClass** property (section 2.789) that is distinct from any value listed in section 1.3.1.
- Clients can use any **named property** for application-defined purposes. No constraint is placed on the value of the **PidTagMessageClass** property in this case, but the property set of the named property is distinct from any value listed in section 1.3.2. Note that named properties are transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Description
0x0001	0x0BFF	**Message object** envelope property; reserved
0x0C00	0x0DFF	**Recipient** property; reserved
0x0E00	0x0FFF	Non-transmittable Message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	**Message store** property; reserved
0x3600	0x36FF	Folder and **address book container** property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	**Address Book object** property; reserved
0x3A00	0x3BFF	**Mail user** object property; reserved
0x3C00	0x3CFF	**Distribution list** property; reserved
0x3D00	0x3DFF	Profile section property; reserved

Copyright © 2025 Microsoft Corporation

Range minimum	Range maximum	Description
0x3E00	0x3EFF	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient property
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. The exceptions to this rule are some of the address book tagged properties (those with names beginning with PIDTagAddressBook). Many are static property IDs but are in this range.

1.3.4 WebDAV Property Naming

The email server is natively a **Messaging Application Programming Interface (MAPI) message store** where the vast majority of properties in it are MAPI properties. The **WebDAV** implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as described in [RFC5234], as a way to name MAPI properties, allowing Web Distributed Authoring and Versioning Protocol (WebDAV) clients to work with these properties directly.

The http://schemas.microsoft.com/mapi/ namespace is used to access MAPI properties directly on the server. The namespace consists of three sub namespaces: proptag, id, and string. The ABNF notation used to specify the format of these namespaces is described in this section.

1.3.4.1 http://schemas.microsoft.com/mapi/proptag Namespace

The http://schemas.microsoft.com/mapi/proptag namespace is used to access properties on the server that are identified by a **property ID**. The implementer can access these properties through **WebDAV** by appending the hexadecimal property ID value and the hexadecimal **property type** value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type

property-id = 4HEXDIG

property-type = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace

The http://schemas.microsoft.com/mapi/id namespace is used to access **named properties** on the server that are identified by a property **long ID (LID)**. The implementer can access these properties

Copyright © 2025 Microsoft Corporation

through WebDAV by appending the **property set** and the hexadecimal property long ID (LID) value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/x" property-long-id

property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"

property-long-id = 8HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213
(PidLidAppointmentDuration)
```

1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace

The http://schemas.microsoft.com/mapi/string namespace is used to access **named properties** on the server that are identified by a **property name**. The implementer can access these properties through WebDAV by appending the **property set** and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name

property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"

property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject
(PidNameSubject)
```

1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [MS-OXCDATA]. For tables and examples that describe property data types, and property and other error codes, see [MS-OXCDATA].

The list of properties and their descriptions included in this document provide context for many of the data structures described in [MS-OXCDATA].

The description of each property contained in this document relies on the technical specification that is cited as its defining reference.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [MS-OXPROTO].

1.5 Applicability Statement

This document provides numeric values used to encode **property names**, tags, and data types in **ROP buffers**. It also serves as a convenient index to the object type documents that define how each property is used.

Copyright © 2025 Microsoft Corporation

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

Property ID ranges, as described in section 1.3.3, describe how applications choose properties to create new **Message object** types or to add functionality to existing types.

Copyright © 2025 Microsoft Corporation

2 Structures

2.1 PidLidAddressBookProviderArrayType

Canonical name: PidLidAddressBookProviderArrayType

Description: Specifies the state of the electronic addresses of the **contact** and represents a set of bit **flags**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008029

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.12

Alternate names: dispidABPArrayType

2.2 PidLidAddressBookProviderEmailList

Canonical name: PidLidAddressBookProviderEmailList

Description: Specifies which electronic address properties are set on the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008028

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.11

Alternate names: dispidABPEmailList

2.3 PidLidAddressCountryCode

Canonical name: PidLidAddressCountryCode

Description: Specifies the country code portion of the mailing address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DD

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.6

Alternate names: dispidAddressCountryCode

Copyright © 2025 Microsoft Corporation

2.4 PidLidAgingDontAgeMe

Canonical name: PidLidAgingDontAgeMe

Description: Specifies whether to automatically archive the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000850E

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-OXCMSG] section 2.2.1.33

Consuming references: [MS-OXCFXICS], [MS-OXOCNTC], [MS-OXODOC], [MS-OXOJRNL], [MS-OXONOTE], [MS-OXOPOST], [MS-OXORMMS], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: dispidAgingDontAgeMe

2.5 PidLidAllAttendeesString

Canonical name: PidLidAllAttendeesString

Description: Specifies a list of all the attendees except for the **organizer**, including **resources** and **unsendable attendees**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008238

WebDAV: http://schemas.microsoft.com/mapi/allattendeesstring

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.16

Consuming reference: [MS-XWDCAL]

Alternate names: dispidAllAttendeesString

2.6 PidLidAllowExternalCheck

Canonical name: PidLidAllowExternalCheck

Description: This property is set to TRUE.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008246

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.5

Consuming reference: [MS-OXCICAL]

Copyright © 2025 Microsoft Corporation

Alternate names: dispidAllowExternCheck

2.7 PidLidAnniversaryEventEntryId

Canonical name: PidLidAnniversaryEventEntryId

Description: Specifies the **EntryID** of the **Appointment object** that represents an anniversary of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804E

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.5.6

Alternate names: dispidAnniversaryEventEID

2.8 PidLidAppointmentAuxiliaryFlags

Canonical name: PidLidAppointmentAuxiliaryFlags

Description: Specifies a bit field that describes the auxiliary state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008207

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.3

Alternate names: dispidApptAuxFlags

2.9 PidLidAppointmentColor

Canonical name: PidLidAppointmentColor

Description: Specifies the color to be used when displaying the **Calendar object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008214

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.50

Alternate names: dispidApptColor

2.10 PidLidAppointmentCounterProposal

Canonical name: PidLidAppointmentCounterProposal

Copyright © 2025 Microsoft Corporation

Description: Indicates whether a **Meeting Response object** is a **counter proposal**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008257

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.7

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptCounterProposal

2.11 PidLidAppointmentDuration

Canonical name: PidLidAppointmentDuration

Description: Specifies the length of the event, in minutes.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008213

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptduration

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.7

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidApptDuration

2.12 PidLidAppointmentEndDate

Canonical name: PidLidAppointmentEndDate

Description: Indicates the date that the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008211

WebDAV: http://schemas.microsoft.com/mapi/apptenddate

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.3

Alternate names: dispidApptEndDate

2.13 PidLidAppointmentEndTime

Canonical name: PidLidAppointmentEndTime

Copyright © 2025 Microsoft Corporation

Description: Indicates the time that the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008210

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptendtime

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.4

Alternate names: dispidApptEndTime

2.14 PidLidAppointmentEndWhole

Canonical name: PidLidAppointmentEndWhole

Description: Specifies the end date and time for the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820E

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptendwhole

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.6

Consuming references: [MS-OXCICAL], [MS-OXOPFFB], [MS-XWDCAL]

Alternate names: dispidApptEndWhole

2.15 PidLidAppointmentLastSequence

Canonical name: PidLidAppointmentLastSequence

Description: Indicates to the **organizer** the last sequence number that was sent to any attendee.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008203

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.2

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptLastSequence

2.16 PidLidAppointmentMessageClass

Canonical name: PidLidAppointmentMessageClass

Copyright © 2025 Microsoft Corporation

Description: Indicates the **message class** of the **Meeting object** to be generated from the **Meeting Request object**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000024

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.6

Alternate names: dispidApptMessageClass

2.17 PidLidAppointmentNotAllowPropose

Canonical name: PidLidAppointmentNotAllowPropose

Description: Indicates whether attendees are not allowed to propose a new date and/or time for the **meeting**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.26

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptNotAllowPropose

2.18 PidLidAppointmentProposalNumber

Canonical name: PidLidAppointmentProposalNumber

Description: Specifies the number of attendees who have sent **counter proposals** that have not been accepted or rejected by the **organizer**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008259

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.6

Alternate names: dispidApptProposalNum

2.19 PidLidAppointmentProposedDuration

Canonical name: PidLidAppointmentProposedDuration

Copyright © 2025 Microsoft Corporation

Description: Indicates the proposed value for the **PidLidAppointmentDuration** property (section 2.11) for a **counter proposal**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008256

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.7.5

Alternate names: dispidApptProposedDuration

2.20 PidLidAppointmentProposedEndWhole

Canonical name: PidLidAppointmentProposedEndWhole

Description: Specifies the proposed value for the **PidLidAppointmentEndWhole** property (section 2.14) for a **counter proposal**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008251

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.7.4

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptProposedEndWhole

2.21 PidLidAppointmentProposedStartWhole

Canonical name: PidLidAppointmentProposedStartWhole

Description: Specifies the proposed value for the **PidLidAppointmentStartWhole** property (section 2.29) for a **counter proposal**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008250

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.7.3

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptProposedStartWhole

2.22 PidLidAppointmentRecur

Canonical name: PidLidAppointmentRecur

Copyright © 2025 Microsoft Corporation

Description: Specifies the dates and times when a **recurring series** occurs.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008216

Data type: PtypBinary, 0x0102

WebDAV: http://schemas.microsoft.com/mapi/apptrecur

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.44

Consuming references: [MS-OXCICAL], [MS-OXORMDR], [MS-XWDCAL]

Alternate names: dispidApptRecur

2.23 PidLidAppointmentReplyName

Canonical name: PidLidAppointmentReplyName

Description: Specifies the user who last replied to the **meeting request** or **meeting** update.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008230

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/apptreplyname

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.5

Consuming reference: [MS-XWDCAL]

Alternate names: dispidApptReplyName, http://schemas.microsoft.com/mapi/apptreplyname

2.24 PidLidAppointmentReplyTime

Canonical name: PidLidAppointmentReplyTime

Description: Specifies the date and time at which the attendee responded to a received **meeting request** or **Meeting Update object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008220

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.3

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidApptReplyTime

Copyright © 2025 Microsoft Corporation

2.25 PidLidAppointmentSequence

Canonical name: PidLidAppointmentSequence

Description: Specifies the sequence number of a **Meeting object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008201

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptsequence

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.1

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidApptSequence

2.26 PidLidAppointmentSequenceTime

Canonical name: PidLidAppointmentSequenceTime

Description: Indicates the date and time at which the **PidLidAppointmentSequence** property (section 2.25) was last modified.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008202

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.1

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptSeqTime

2.27 PidLidAppointmentStartDate

Canonical name: PidLidAppointmentStartDate

Description: Identifies the date that the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008212

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptstartdate

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.10

Copyright © 2025 Microsoft Corporation

Alternate names: dispidApptStartDate

2.28 PidLidAppointmentStartTime

Canonical name: PidLidAppointmentStartTime

Description: Identifies the time that the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820F

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptstarttime

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.11

Alternate names: dispidApptStartTime

2.29 PidLidAppointmentStartWhole

Canonical name: PidLidAppointmentStartWhole

Description: Specifies the start date and time of the appointment.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820D

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptstartwhole

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.5

Consuming references: [MS-OXCICAL], [MS-OXOPFFB], [MS-XWDCAL]

Alternate names: dispidApptStartWhole

2.30 PidLidAppointmentStateFlags

Canonical name: PidLidAppointmentStateFlags

Description: Specifies a bit field that describes the state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008217

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptstateflags

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.10

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCICAL], [MS-OXORMDR], [MS-OXWAVLS], [MS-XWDCAL]

Alternate names: dispidApptStateFlags

2.31 PidLidAppointmentSubType

Canonical name: PidLidAppointmentSubType

Description: Specifies whether the event is an all-day event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008215

Data type: PtypBoolean, 0x000B

WebDAV: urn:schemas:calendar:alldayevent, http://schemas.microsoft.com/mapi/apptsubtype

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.9

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidApptSubType

2.32 PidLidAppointmentTimeZoneDefinitionEndDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionEndDisplay

Description: Specifies time zone information that indicates the time zone of the **PidLidAppointmentEndWhole** property (section 2.14).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825F

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.43

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptTZDefEndDisplay

2.33 PidLidAppointmentTimeZoneDefinitionRecur

Canonical name: PidLidAppointmentTimeZoneDefinitionRecur

Description: Specifies time zone information that describes how to convert the **meeting** date and time on a **recurring series** to and from **UTC**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008260

Data type: PtypBinary, 0x0102

Area: Calendar

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCAL] section 2.2.1.41

Consuming references: [MS-OXCICAL], [MS-OXOCFG]

Alternate names: dispidApptTZDefRecur

2.34 PidLidAppointmentTimeZoneDefinitionStartDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionStartDisplay

Description: Specifies time zone information that indicates the time zone of the **PidLidAppointmentStartWhole** property (section 2.29).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825E

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.42

Consuming reference: [MS-OXCICAL]

Alternate names: dispidApptTZDefStartDisplay

2.35 PidLidAppointmentUnsendableRecipients

Canonical name: PidLidAppointmentUnsendableRecipients

Description: Contains a list of **unsendable attendees**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825D

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.25

Alternate names: dispidApptUnsendableRecips

2.36 PidLidAppointmentUpdateTime

Canonical name: PidLidAppointmentUpdateTime

Description: Indicates the time at which the appointment was last updated.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008226

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptupdatetime

Area: Meetings

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-XWDCAL] section 2.2.7.15

Alternate names: dispidApptUpdateTime

2.37 PidLidAttendeeCriticalChange

Canonical name: PidLidAttendeeCriticalChange

Description: Specifies the date and time at which the **meeting-related object** was sent.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000001

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/attendee_critical_change

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.5.2

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: LID_ATTENDEE_CRITICAL_CHANGE

2.38 PidLidAutoFillLocation

Canonical name: PidLidAutoFillLocation

Description: Indicates whether the value of the **PidLidLocation** property (section 2.159) is set to the **PidTagDisplayName** property (section 2.677).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.8

Consuming reference: [MS-OXCICAL]

Alternate names: dispidAutoFillLocation

2.39 PidLidAutoLog

Canonical name: PidLidAutoLog

Description: Specifies to the application whether to create a **Journal object** for each **action** associated with this Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008025

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCNTC] section 2.2.1.10.19

Alternate names: dispidAutoLog

2.40 PidLidAutoProcessState

Canonical name: PidLidAutoProcessState

Description: Specifies the options used in the automatic processing of email messages.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851A

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.73

Alternate names: dispidSniffState

2.41 PidLidAutoStartCheck

Canonical name: PidLidAutoStartCheck

Description: Specifies whether to automatically start the conferencing application when a **reminder** for the start of a **meeting** is executed.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008244

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.1

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: dispidAutoStartCheck

2.42 PidLidBilling

Canonical name: PidLidBilling

Description: Specifies billing information for the **contact**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008535

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:billinginformation

Area: General Message Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.24

Copyright © 2025 Microsoft Corporation

Alternate names: dispidBilling

2.43 PidLidBirthdayEventEntryId

Canonical name: PidLidBirthdayEventEntryId

Description: Specifies the **EntryID** of an optional **Appointment object** that represents the birthday of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804D

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.5.3

Alternate names: dispidBirthdayEventEID

2.44 PidLidBirthdayLocal

Canonical name: PidLidBirthdayLocal

Description: Specifies the birthday of a **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DE

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.5.2

Alternate names: dispidApptBirthdayLocal

2.45 PidLidBusinessCardCardPicture

Canonical name: PidLidBusinessCardCardPicture

Description: Contains the image to be used on a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008041

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.7.2

Alternate names: dispidBCCardPicture

2.46 PidLidBusinessCardDisplayDefinition

Canonical name: PidLidBusinessCardDisplayDefinition

Copyright © 2025 Microsoft Corporation

Description: Contains user customization details for displaying a **contact** as a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008040

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.7.1

Consuming reference: [MS-OXVCARD]

Alternate names: dispidBCDisplayDefinition

2.47 PidLidBusyStatus

Canonical name: PidLidBusyStatus

Description: Specifies the availability of a user for the event described by the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008205

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/busystatus

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.2

Consuming references: [MS-OXCICAL], [MS-OXOPFFB], [MS-XWDCAL]

Alternate names: dispidBusyStatus

2.48 PidLidCalendarType

Canonical name: PidLidCalendarType

Description: Contains the value of the **CalendarType** field from the **PidLidAppointmentRecur** property (section 2.22).

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000001C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/calendar_type

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.11

Consuming reference: [MS-XWDCAL]

Alternate names: LID_CALENDAR_TYPE

Copyright © 2025 Microsoft Corporation

2.49 PidLidCategories

Canonical name: PidLidCategories

Description: Contains the array of text labels assigned to this **Message object**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property long ID (LID): 0x00009000

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [MS-OXCMSG] section 2.2.1.22

Consuming reference: [MS-OXVCARD]

Alternate names: dispidCategories

2.50 PidLidCcAttendeesString

Canonical name: PidLidCcAttendeesString

Description: Contains a list of all the sendable attendees who are also **optional attendees**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823C

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.18

Alternate names: dispidCCAttendeesString

2.51 PidLidChangeHighlight

Canonical name: PidLidChangeHighlight

Description: Specifies a bit field that indicates how the **Meeting object** has changed.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008204

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.2

Consuming reference: [MS-OXORMDR]

Alternate names: dispidChangeHighlight

2.52 PidLidClassification

Canonical name: PidLidClassification

Copyright © 2025 Microsoft Corporation

Description: Contains a list of the classification categories to which the associated **Message object** has been assigned.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B6

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.23

Consuming references: [MS-OXCMAIL]

Alternate names: dispidClassification

2.53 PidLidClassificationDescription

Canonical name: PidLidClassificationDescription

Description: Contains a human-readable summary of each of the classification categories included in the **PidLidClassification** property (section 2.53).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B7

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.24

Consuming reference: [MS-OXCMAIL]

Alternate names: dispidClassDesc

2.54 PidLidClassificationGuid

Canonical name: PidLidClassificationGuid

Description: Contains the **GUID** that identifies the list of email classification categories used by a **Message object**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B8

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMAIL] section 2.5.1

Alternate names: dispidClassGuid

2.55 PidLidClassificationKeep

Canonical name: PidLidClassificationKeep

Copyright © 2025 Microsoft Corporation

Description: Indicates whether the message uses any classification categories.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BA

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [MS-OXCMAIL] section 2.5.2

Alternate names: dispidClassKeep

2.56 PidLidClassified

Canonical name: PidLidClassified

Description: Indicates whether the contents of this message are regarded as classified information.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B5

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.25

Consuming references: [MS-OXCMAIL]

Alternate names: dispidClassified

2.57 PidLidCleanGlobalObjectId

Canonical name: PidLidCleanGlobalObjectId

Description: Contains the value of the **PidLidGlobalObjectId** property (section 2.142) for an object that represents an **Exception object** to a **recurring series**, where the Year, Month, and Day fields are all zero.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000023

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.28

Consuming references: [MS-OXCICAL]

Alternate names: dispidCleanGlobalObjId

2.58 PidLidClientIntent

Canonical name: PidLidClientIntent

Description: Indicates what **actions** the user has taken on this **Meeting object**.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x00000015

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.2.4

Alternate names: dispidClientIntent

2.59 PidLidClipEnd

Canonical name: PidLidClipEnd

Description: Specifies the end date and time of the event in **UTC**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008236

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.15

Alternate names: dispidClipEnd

2.60 PidLidClipStart

Canonical name: PidLidClipStart

Description: Specifies the start date and time of the event in **UTC**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008235

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.14

Alternate names: dispidClipStart

2.61 PidLidCollaborateDoc

Canonical name: PidLidCollaborateDoc

Description: Specifies the document to be launched when the user joins the **meeting**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008247

Data type: PtypString, 0x001F

Area: Conferencing

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCAL] section 2.2.1.56.7

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: dispidCollaborateDoc

2.62 PidLidCommonEnd

Canonical name: PidLidCommonEnd

Description: Indicates the end time for the **Message object**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008517

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.19

Consuming references: [MS-OXCFXICS], [MS-OXOFLAG], [MS-OXOJRNL], [MS-OXOTASK], [MS-OXOCAL]

Alternate names: dispidCommonEnd

2.63 PidLidCommonStart

Canonical name: PidLidCommonStart

Description: Indicates the start time for the **Message object**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008516

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.18

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOCAL], [MS-OXOFLAG], [MS-OXOJRNL], [MS-OXOTASK]

Alternate names: dispidCommonStart

2.64 PidLidCompanies

Canonical name: PidLidCompanies

Description: Contains a list of company names, each of which is associated with a **contact** that is specified in the PidLidContacts property ([MS-OXCMSG] section 2.2.1.59.2).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008539

Data type: PtypMultipleString, 0x101F

Copyright © 2025 Microsoft Corporation

Area: General Message Properties

Defining reference: [MS-OXOJRNL] section 2.2.2.4

Alternate names: dispidCompanies, http://schemas.microsoft.com/exchange/companies

2.65 PidLidConferencingCheck

Canonical name: PidLidConferencingCheck

Description: When set to TRUE (0x00000001), the PidLidConferencingCheck property indicates that the associated **meeting** is one of the following types:

- "Windows Media Services"
- "Windows NetMeeting"
- "Exchange Conferencing"

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008240

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.2

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: dispidConfCheck

2.66 PidLidConferencingType

Canonical name: PidLidConferencingType

Description: Specifies the type of the **meeting**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008241

Data type: PtypInteger32, 0x0003

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.3

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: dispidConfType

2.67 PidLidContactCharacterSet

Canonical name: PidLidContactCharacterSet

Description: Specifies the character set used for a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x00008023

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.18

Alternate names: dispidContactCharSet

2.68 PidLidContactItemData

Canonical name: PidLidContactItemData

Description: Specifies the visible fields in the application's user interface that are used to help display the **contact** information.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008007

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.22

Alternate names: dispidContactItemData

2.69 PidLidContactLinkedGlobalAddressListEntryId

Canonical name: PidLidContactLinkedGlobalAddressListEntryId

Description: Specifies the **EntryID** of the **GAL contact** to which the duplicate contact is linked.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E2

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.9.1

Alternate names: dispidContactLinkedGALEntryID

2.70 PidLidContactLinkEntry

Canonical name: PidLidContactLinkEntry

Description: Contains the elements of the **PidLidContacts** property (section 2.77).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008585

Data type: PtypBinary, 0x0102

Area: Contact Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXCMSG] section 2.2.1.59.1

Consuming references: [MS-OXOCNTC], [MS-OXOJRNL]

Alternate names: dispidContactLinkEntry

2.71 PidLidContactLinkGlobalAddressListLinkId

Canonical name: PidLidContactLinkGlobalAddressListLinkId

Description: Specifies the **GUID** of the **GAL contact** to which the duplicate contact is linked.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E8

Data type: **PtypGuid**, 0x0048

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.9.2

Alternate names: dispidContactLinkGALLinkID

2.72 PidLidContactLinkGlobalAddressListLinkState

Canonical name: PidLidContactLinkGlobalAddressListLinkState

Description: Specifies the state of the linking between the **GAL contact** and the duplicate contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E6

Data type: **PtypInteger32**, 0x0003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.9.3

Alternate names: dispidContactLinkGALLinkState

2.73 PidLidContactLinkLinkRejectHistory

Canonical name: PidLidContactLinkLinkRejectHistory

Description: Contains a list of **GAL contacts** that were previously rejected for linking with the duplicate contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E5

Data type: **PtypMultipleBinary**, 0x1102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.9.4

Alternate names: dispidContactLinkLinkRejectHistory

Copyright © 2025 Microsoft Corporation

2.74 PidLidContactLinkName

Canonical name: PidLidContactLinkName

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008586

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXCMSG] section 2.2.1.59.3

Consuming references: [MS-OXOCNTC], [MS-OXOJRNL]

Alternate names: dispidContactLinkName

2.75 PidLidContactLinkSearchKey

Canonical name: PidLidContactLinkSearchKey

Description: Contains the list of SearchKeys for a Contact object linked to by the **Message object**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008584

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXCMSG] section 2.2.1.59.4

Consuming references: [MS-OXOCNTC], [MS-OXOJRNL]

Alternate names: dispidContactLinkSearchKey

2.76 PidLidContactLinkSMTPAddressCache

Canonical name: PidLidContactLinkSMTPAddressCache

Description: Contains a list of the **SMTP** addresses that are used by the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E3

Data type: PtypMultipleString, 0x101F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.9.5

Alternate names: dispidContactLinkSMTPAddressCache

2.77 PidLidContacts

Canonical name: PidLidContacts

Copyright © 2025 Microsoft Corporation

Description: Contains the **PidTagDisplayName** property (section 2.677) of each Address Book **EntryID** referenced in the value of the **PidLidContactLinkEntry** property (section 2.70).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000853A

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.59.2

Consuming references: [MS-OXCICAL], [MS-OXOCAL], [MS-OXOJRNL]

Alternate names: dispidContacts

2.78 PidLidContactUserField1

Canonical name: PidLidContactUserField1

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804F

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute1

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.7.3

Consuming references: [MS-OXVCARD]

Alternate names: dispidContactUserField1

2.79 PidLidContactUserField2

Canonical name: PidLidContactUserField2

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008050

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute2

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.7.3

Consuming references: [MS-OXVCARD]

Copyright © 2025 Microsoft Corporation

Alternate names: dispidContactUserField2

2.80 PidLidContactUserField3

Canonical name: PidLidContactUserField3

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008051

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute3

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.7.3

Consuming references: [MS-OXVCARD]

Alternate names: dispidContactUserField3

2.81 PidLidContactUserField4

Canonical name: PidLidContactUserField4

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008052

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute4

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.7.3

Consuming references: [MS-OXVCARD]

Alternate names: dispidContactUserField4

2.82 PidLidConversationActionLastAppliedTime

Canonical name: PidLidConversationActionLastAppliedTime

Description: Contains the time, in **UTC**, that an **Email object** was last received in the **conversation**, or the last time that the user modified the **conversation action**, whichever occurs later.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CA

Copyright © 2025 Microsoft Corporation

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining reference: [MS-OXOCFG] section 2.2.8.1

Alternate names: dispidConvActionLastAppliedTime

2.83 PidLidConversationActionMaxDeliveryTime

Canonical name: PidLidConversationActionMaxDeliveryTime

Description: Contains the maximum value of the **PidTagMessageDeliveryTime** property (section 2.791) of all of the **Email objects** modified in response to the last time that the user changed a **conversation action** on the client.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C8

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining reference: [MS-OXOCFG] section 2.2.8.2

Alternate names: dispidConvActionMaxDeliveryTime

2.84 PidLidConversationActionMoveFolderEid

Canonical name: PidLidConversationActionMoveFolderEid

Description: Contains the **EntryID** for the destination folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C6

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining reference: [MS-OXOCFG] section 2.2.8.3

Alternate names: dispidConvActionMoveFolderEid

2.85 PidLidConversationActionMoveStoreEid

Canonical name: PidLidConversationActionMoveStoreEid

Description: Contains the **EntryID** for a move to a folder in a different **message store**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C7

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining reference: [MS-OXOCFG] section 2.2.8.4

Copyright © 2025 Microsoft Corporation

Alternate names: dispidConvActionMoveStoreEid

2.86 PidLidConversationActionVersion

Canonical name: PidLidConversationActionVersion

Description: Contains the version of the **conversation action FAI** message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CB

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

Defining reference: [MS-OXOCFG] section 2.2.8.5

Alternate names: dispidConvActionVersion

2.87 PidLidConversationProcessed

Canonical name: PidLidConversationProcessed

Description: Specifies a sequential number to be used in the processing of a **conversation action**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C9

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

Defining reference: [MS-OXOCFG] section 2.2.8.6

Alternate names: dispidConvExLegacyProcessedRand

2.88 PidLidCurrentVersion

Canonical name: PidLidCurrentVersion

Description: Specifies the build number of the client application that sent the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008552

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.34

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXTNEF], [MS-OXOTASK], [MS-OXONOTE], [MS-OXOCNTC], [MS-OXOPOST], [MS-OXORMMS], [MS-OXOJRNL]

Alternate names: dispidCurrentVersion

Copyright © 2025 Microsoft Corporation

2.89 PidLidCurrentVersionName

Canonical name: PidLidCurrentVersionName

Description: Specifies the name of the client application that sent the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008554

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.35

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXTNEF], [MS-OXOTASK], [MS-OXONOTE], [MS-OXOCNTC], [MS-OXOPOST], [MS-OXORMMS], [MS-OXOJRNL]

Alternate names: dispidCurrentVersionName

2.90 PidLidDayInterval

Canonical name: PidLidDayInterval

Description: Identifies the day interval for the **recurrence pattern**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000011

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/day_interval

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.19

Consuming references: [MS-OXOCAL]

Alternate names: LID_DAY_INTERVAL

2.91 PidLidDayOfMonth

Canonical name: PidLidDayOfMonth

Description: Identifies the day of the month for the appointment or **meeting**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001000

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/dayofmonth

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.20

Copyright © 2025 Microsoft Corporation

2.92 PidLidDelegateMail

Canonical name: PidLidDelegateMail

Description: Indicates whether a **delegate** responded to the **meeting request**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000009

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/delegate_mail

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.21

Alternate names: LID_DELEGATE_MAIL

2.93 PidLidDepartment

Canonical name: PidLidDepartment

Description: This property is ignored by the server and is set to an empty string by the client.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008010

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.6.4

Alternate names: dispidDepartment

2.94 PidLidDirectory

Canonical name: PidLidDirectory

Description: Specifies the directory server to be used.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008242

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.4

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: dispidDirectory

2.95 PidLidDistributionListChecksum

Canonical name: PidLidDistributionListChecksum

Copyright © 2025 Microsoft Corporation

Description: Specifies the 32-bit **cyclic redundancy check (CRC)** polynomial checksum, as specified in [ISO/IEC8802-3], calculated on the value of the **PidLidDistributionListMembers** property (section 2.96).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804C

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.2.2.3

Alternate names: dispidDLChecksum

2.96 PidLidDistributionListMembers

Canonical name: PidLidDistributionListMembers

Description: Specifies the list of **EntryIDs** of the objects corresponding to the members of the personal **distribution list**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008055

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.2.2.1

Alternate names: dispidDLMembers

2.97 PidLidDistributionListName

Canonical name: PidLidDistributionListName

Description: Specifies the name of the personal **distribution list**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008053

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.2.1.2

Alternate names: dispidDLName

2.98 PidLidDistributionListOneOffMembers

Canonical name: PidLidDistributionListOneOffMembers

Description: Specifies the list of one-off **EntryIDs** corresponding to the members of the personal **distribution list**.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008054

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.2.2.2

Alternate names: dispidDLOneOffMembers

2.99 PidLidDistributionListStream

Canonical name: PidLidDistributionListStream

Description: Specifies the list of **EntryIDs** and one-off EntryIDs corresponding to the members of the personal **distribution list**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008064

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.2.2.4

Alternate names: dispidDLStream

2.100 PidLidEmail1AddressType

Canonical name: PidLidEmail1AddressType

Description: Specifies the **address type** of an electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008082

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.2

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail1AddrType

2.101 PidLidEmail1DisplayName

Canonical name: PidLidEmail1DisplayName

Description: Specifies the user-readable **display name** for the email address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008080

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.1

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail1DisplayName

2.102 PidLidEmail1EmailAddress

Canonical name: PidLidEmail1EmailAddress

Description: Specifies the email address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008083

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.3

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail1EmailAddress

2.103 PidLidEmail1OriginalDisplayName

Canonical name: PidLidEmail1OriginalDisplayName

Description: Specifies the **SMTP** email address that corresponds to the email address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008084

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.4

Alternate names: dispidEmail1OriginalDisplayName, Email1OriginalDisplayName, EXSCHEMA_MAPI_EMAIL1ORIGINALDISPLAYNAME

2.104 PidLidEmail1OriginalEntryId

Canonical name: PidLidEmail1OriginalEntryId

Description: Specifies the **EntryID** of the object corresponding to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008085

Data type: PtypBinary, 0x0102

Copyright © 2025 Microsoft Corporation

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.5

Alternate names: dispidEmail1OriginalEntryID

2.105 PidLidEmail2AddressType

Canonical name: PidLidEmail2AddressType

Description: Specifies the **address type** of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008092

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.2

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail2AddrType

2.106 PidLidEmail2DisplayName

Canonical name: PidLidEmail2DisplayName

Description: Specifies the user-readable **display name** for the email address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008090

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.1

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail2DisplayName

2.107 PidLidEmail2EmailAddress

Canonical name: PidLidEmail2EmailAddress

Description: Specifies the email address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008093

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.3

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail2EmailAddress

2.108 PidLidEmail2OriginalDisplayName

Canonical name: PidLidEmail2OriginalDisplayName

Description: Specifies the **SMTP** email address that corresponds to the email address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008094

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.4

Alternate names: dispidEmail2OriginalDisplayName

2.109 PidLidEmail2OriginalEntryId

Canonical name: PidLidEmail2OriginalEntryId

Description: Specifies the **EntryID** of the object that corresponds to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008095

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.5

Alternate names: dispidEmail2OriginalEntryID

2.110 PidLidEmail3AddressType

Canonical name: PidLidEmail3AddressType

Description: Specifies the **address type** of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.2

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail3AddrType

Copyright © 2025 Microsoft Corporation

2.111 PidLidEmail3DisplayName

Canonical name: PidLidEmail3DisplayName

Description: Specifies the user-readable **display name** for the email address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A0

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.1

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail3DisplayName

2.112 PidLidEmail3EmailAddress

Canonical name: PidLidEmail3EmailAddress

Description: Specifies the email address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.3

Consuming reference: [MS-OXVCARD]

Alternate names: dispidEmail3EmailAddress

2.113 PidLidEmail3OriginalDisplayName

Canonical name: PidLidEmail3OriginalDisplayName

Description: Specifies the **SMTP** email address that corresponds to the email address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.4

Alternate names: dispidEmail3OriginalDisplayName

Copyright © 2025 Microsoft Corporation

2.114 PidLidEmail3OriginalEntryId

Canonical name: PidLidEmail3OriginalEntryId

Description: Specifies the **EntryID** of the object that corresponds to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.5

Alternate names: dispidEmail3OriginalEntryID

2.115 PidLidEndRecurrenceDate

Canonical name: PidLidEndRecurrenceDate

Description: Identifies the end date of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000F

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_date

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.22

Consuming reference: [MS-OXOCAL]

Alternate names: LID_END_RECUR_DATE

2.116 PidLidEndRecurrenceTime

Canonical name: PidLidEndRecurrenceTime

Description: Identifies the end time of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000010

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_time

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.23

Consuming reference: [MS-OXOCAL]

Alternate names: LID_END_RECUR_TIME

Copyright © 2025 Microsoft Corporation

2.117 PidLidExceptionReplaceTime

Canonical name: PidLidExceptionReplaceTime

Description: Specifies the date and time, in **UTC**, within a **recurrence pattern** that an exception will replace.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008228

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.10.2.5

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidExceptionReplaceTime

2.118 PidLidFax1AddressType

Canonical name: PidLidFax1AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.7

Alternate names: dispidFax1AddrType

2.119 PidLidFax1EmailAddress

Canonical name: PidLidFax1EmailAddress

Description: Contains a user-readable **display name**, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.8

Alternate names: dispidFax1EmailAddress

2.120 PidLidFax1OriginalDisplayName

Canonical name: PidLidFax1OriginalDisplayName

Copyright © 2025 Microsoft Corporation

Description: Contains the same value as the **PidTagNormalizedSubject** property (section 2.814).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.9

Alternate names: dispidFax1OriginalDisplayName

2.121 PidLidFax1OriginalEntryId

Canonical name: PidLidFax1OriginalEntryId

Description: Specifies a one-off **EntryID** that corresponds to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.10

Alternate names: dispidFax1OriginalEntryID

2.122 PidLidFax2AddressType

Canonical name: PidLidFax2AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.7

Alternate names: dispidFax2AddrType

2.123 PidLidFax2EmailAddress

Canonical name: PidLidFax2EmailAddress

Description: Contains a user-readable **display name**, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C3

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.8

Alternate names: dispidFax2EmailAddress

2.124 PidLidFax2OriginalDisplayName

Canonical name: PidLidFax2OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section 2.814).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.9

Alternate names: dispidFax2OriginalDisplayName

2.125 PidLidFax2OriginalEntryId

Canonical name: PidLidFax2OriginalEntryId

Description: Specifies a one-off **EntryID** corresponding to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.10

Alternate names: dispidFax2OriginalEntryID

2.126 PidLidFax3AddressType

Canonical name: PidLidFax3AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.7

Alternate names: dispidFax3AddrType

Copyright © 2025 Microsoft Corporation

2.127 PidLidFax3EmailAddress

Canonical name: PidLidFax3EmailAddress

Description: Contains a user-readable **display name**, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.8

Alternate names: dispidFax3EmailAddress

2.128 PidLidFax3OriginalDisplayName

Canonical name: PidLidFax3OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section 2.814).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.9

Alternate names: dispidFax3OriginalDisplayName

2.129 PidLidFax3OriginalEntryId

Canonical name: PidLidFax3OriginalEntryId

Description: Specifies a one-off **EntryID** that corresponds to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.10

Alternate names: dispidFax3OriginalEntryID

2.130 PidLidFExceptionalAttendees

Canonical name: PidLidFExceptionalAttendees

Copyright © 2025 Microsoft Corporation

Description: Indicates that the object is a **Recurring Calendar object** with one or more exceptions, and that at least one of the **Exception Embedded Message objects** has at least one **RecipientRow** structure, as described in [MS-OXCDATA] section 2.8.3.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822B

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.2.3

Consuming reference: [MS-OXORMDR]

Alternate names: dispidFExceptionalAttendees

2.131 PidLidFExceptionalBody

Canonical name: PidLidFExceptionalBody

Description: Indicates that the **Exception Embedded Message object** has a body that differs from the **Recurring Calendar object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008206

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.10.2.6

Alternate names: dispidFExceptionalBody

2.132 PidLidFileUnder

Canonical name: PidLidFileUnder

Description: Specifies the name under which to file a **contact** when displaying a list of contacts.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008005

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.1.11

Alternate names: dispidFileUnder

2.133 PidLidFileUnderId

Canonical name: PidLidFileUnderId

Copyright © 2025 Microsoft Corporation

Description: Specifies how to generate and recompute the value of the **PidLidFileUnder** property (section 2.132) when other **contact** name properties change.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008006

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.1.12

Alternate names: dispidFileUnderId

2.134 PidLidFileUnderList

Canonical name: PidLidFileUnderList

Description: Specifies a list of possible values for the **PidLidFileUnderId** property (section 2.133).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008026

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.1.13

Alternate names: dispidFileUnderList

2.135 PidLidFInvited

Canonical name: PidLidFInvited

Description: Indicates whether invitations have been sent for the **meeting** that this **Meeting object** represents.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008229

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/finvited

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.4

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidFInvited

2.136 PidLidFlagRequest

Canonical name: PidLidFlagRequest

Description: Contains user-specifiable text to be associated with the flag.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008530

Data type: PtypString, 0x001F

WebDAV: urn:schemas:httpmail:messageflag, http://schemas.microsoft.com/mapi/request

Area: Flagging

Defining reference: [MS-OXOFLAG] section 2.2.1.9

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-XWDCAL], [MS-OXORMDR]

Alternate names: dispidRequest

2.137 PidLidFlagString

Canonical name: PidLidFlagString

Description: Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C0

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOFLAG] section 2.2.1.10

Alternate names: dispidFlagStringEnum

2.138 PidLidForwardInstance

Canonical name: PidLidForwardInstance

Description: Indicates whether the **Meeting Request object** represents an exception to a **recurring series**, and whether it was forwarded (even when forwarded by the **organizer**) rather than being an invitation sent by the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.3

Alternate names: dispidFwrdInstance

2.139 PidLidForwardNotificationRecipients

Canonical name: PidLidForwardNotificationRecipients

Copyright © 2025 Microsoft Corporation

Description: Contains a list of **RecipientRow** structures, as described in [MS-OXCDATA] section 2.8.3, that indicate the **recipients** of a **meeting** forward.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008261

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.9.3

Alternate names: dispidForwardNotificationRecipients

2.140 PidLidFOthersAppointment

Canonical name: PidLidFOthersAppointment

Description: Indicates whether the **Calendar folder** from which the **meeting** was opened is another user's **calendar**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822F

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.26

Alternate names: dispidFOthersAppt, http://schemas.microsoft.com/mapi/fothersappt

2.141 PidLidFreeBusyLocation

Canonical name: PidLidFreeBusyLocation

Description: Specifies a **URL** path from which a client can retrieve **free/busy status** information for the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D8

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:fburl

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.10

Consuming references: [MS-OXVCARD], [MS-XWDCAL]

Alternate names: dispidFreeBusyLocation

2.142 PidLidGlobalObjectId

Canonical name: PidLidGlobalObjectId

Copyright © 2025 Microsoft Corporation

Description: Contains an ID for an object that represents an exception to a **recurring series**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000003

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.27

Consuming references: [MS-OXCICAL], [MS-OXWAVLS]

Alternate names: LID_GLOBAL_OBJID

2.143 PidLidHasPicture

Canonical name: PidLidHasPicture

Description: Specifies whether the attachment has a picture.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008015

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.8.1

Alternate names: dispidHasPicture

2.144 PidLidHomeAddress

Canonical name: PidLidHomeAddress

Description: Specifies the complete address of the home address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:homepostaladdress

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.8

Alternate names: dispidHomeAddress

2.145 PidLidHomeAddressCountryCode

Canonical name: PidLidHomeAddressCountryCode

Description: Specifies the country code portion of the home address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x000080DA

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.6

Alternate names: dispidHomeAddressCountryCode

2.146 PidLidHtml

Canonical name: PidLidHtml

Description: Specifies the business webpage URL of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802B

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.12

Alternate names: dispidHTML

2.147 PidLidICalendarDayOfWeekMask

Canonical name: PidLidICalendarDayOfWeekMask

Description: Identifies the day of the week for the appointment or **meeting**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001001

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.27

Alternate names: http://schemas.microsoft.com/mapi/dayofweekmask

2.148 PidLidInboundICalStream

Canonical name: PidLidInboundICalStream

Description: Contains the contents of the iCalendar **MIME part** of the original **MIME message**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827A

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference: [MS-OXCICAL] section 2.1.3.4.1

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-OXCMAIL]

Alternate names: InboundICalStream, dispidInboundICalStream

2.149 PidLidInfoPathFormName

Canonical name: PidLidInfoPathFormName

Description: Contains the name of the form associated with this message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B1

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXCMSG] section 2.2.1.27

Consuming reference: [MS-OXCMAIL]

2.150 PidLidInstantMessagingAddress

Canonical name: PidLidInstantMessagingAddress

Description: Specifies the instant messaging address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008062

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.6

Consuming reference: [MS-OXVCARD]

Alternate names: dispidInstMsg

2.151 PidLidIntendedBusyStatus

Canonical name: PidLidIntendedBusyStatus

Description: Contains the value of the **PidLidBusyStatus** property (section 2.47) on the **Meeting object** in the **organizer's calendar** at the time that the **Meeting Request object** or **Meeting Update object** was sent.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008224

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/intendedbusystatus

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.4

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidIntendedBusyStatus

2.152 PidLidInternetAccountName

Canonical name: PidLidInternetAccountName

Description: Specifies the user-visible email account name through which the email message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008580

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.62

Consuming references: [MS-OXCFXICS], [MS-OXOCAL]

Alternate names: dispidInetAcctName

2.153 PidLidInternetAccountStamp

Canonical name: PidLidInternetAccountStamp

Description: Specifies the email account ID through which the email message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008581

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.63

Consuming references: [MS-OXCFXICS], [MS-OXOCAL]

Alternate names: dispidInetAcctStamp

2.154 PidLidIsContactLinked

Canonical name: PidLidIsContactLinked

Description: Specifies whether the **contact** is linked to other contacts.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E0

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.9.6

Alternate names: dispidIsContactLinked

Copyright © 2025 Microsoft Corporation

2.155 PidLidIsException

Canonical name: PidLidIsException

Description: Indicates whether the object represents an exception (including an **orphan instance**).

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000A

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_exception

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.35

Consuming references: [MS-OXWAVLS], [MS-XWDCAL]

Alternate names: LID_IS_EXCEPTION

2.156 PidLidIsRecurring

Canonical name: PidLidIsRecurring

Description: Specifies whether the object is associated with a **recurring series**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000005

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_recurring

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.13

Consuming reference: [MS-XWDCAL]

Alternate names: LID_IS_RECURRING

2.157 PidLidIsSilent

Canonical name: PidLidIsSilent

Description: Indicates whether the user did not include any text in the body of the **Meeting Response object**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000004

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_silent

Area: Meetings

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCAL] section 2.2.7.7

Consuming reference: [MS-XWDCAL]

Alternate names: LID_IS_SILENT

2.158 PidLidLinkedTaskItems

Canonical name: PidLidLinkedTaskItems

Description: Indicates whether the user did not include any text in the body of the **Meeting Response object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820C

Data type: PtypMultipleBinary, 0x1102

Area: Tasks

Defining reference: [MS-OXOCAL] section 2.2.1.47

Alternate names: dispidLinkedTaskItems

2.159 PidLidLocation

Canonical name: PidLidLocation

Description: Specifies the location of the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008208

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:location

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.4

Consuming references: [MS-OXCICAL], [MS-OXORMDR], [MS-OXWAVLS], [MS-XWDCAL]

Alternate names: dispidLocation

2.160 PidLidLogDocumentPosted

Canonical name: PidLidLogDocumentPosted

Description: Indicates whether the document was sent by email or posted to a server folder during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008711

Data type: PtypBoolean, 0x000B

Area: Journal

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOJRNL] section 2.2.1.10

Alternate names: dispidLogDocPosted

2.161 PidLidLogDocumentPrinted

Canonical name: PidLidLogDocumentPrinted

Description: Indicates whether the document was printed during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870E

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.7

Alternate names: dispidLogDocPrinted

2.162 PidLidLogDocumentRouted

Canonical name: PidLidLogDocumentRouted

Description: Indicates whether the document was sent to a routing **recipient** during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008710

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.9

Alternate names: dispidLogDocRouted

2.163 PidLidLogDocumentSaved

Canonical name: PidLidLogDocumentSaved

Description: Indicates whether the document was saved during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870F

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.8

Alternate names: dispidLogDocSaved

Copyright © 2025 Microsoft Corporation

2.164 PidLidLogDuration

Canonical name: PidLidLogDuration

Description: Contains the duration, in minutes, of the activity.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008707

Data type: PtypInteger32, 0x0003

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.5

Alternate names: dispidLogDuration

2.165 PidLidLogEnd

Canonical name: PidLidLogEnd

Description: Contains the time, in **UTC**, at which the activity ended.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008708

Data type: PtypTime, 0x0040

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.4

Alternate names: dispidLogEnd

2.166 PidLidLogFlags

Canonical name: PidLidLogFlags

Description: Contains metadata about the **Journal object**.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870C

Data type: PtypInteger32, 0x0003

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.6

Alternate names: dispidLogFlags

2.167 PidLidLogStart

Canonical name: PidLidLogStart

Description: Contains the time, in **UTC**, at which the activity began.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x00008706

Data type: PtypTime, 0x0040

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.3

Alternate names: dispidLogStart

2.168 PidLidLogType

Canonical name: PidLidLogType

Description: Briefly describes the journal activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008700

Data type: PtypString, 0x001F

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.1

Alternate names: dispidLogType

2.169 PidLidLogTypeDesc

Canonical name: PidLidLogTypeDesc

Description: Contains an expanded description of the journal activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008712

Data type: PtypString, 0x001F

Area: Journal

Defining reference: [MS-OXOJRNL] section 2.2.1.2

Alternate names: dispidLogTypeDesc

2.170 PidLidMeetingType

Canonical name: PidLidMeetingType

Description: Indicates the type of **Meeting Request object** or **Meeting Update object**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000026

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.5

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-XWDCAL]

Alternate names: dispidMeetingType

2.171 PidLidMeetingWorkspaceUrl

Canonical name: PidLidMeetingWorkspaceUrl

Description: Specifies the **URL** of the **Meeting Workspace** that is associated with a **Calendar object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008209

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/meetingworkspaceurl

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.48

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidMWSURL

2.172 PidLidMonthInterval

Canonical name: PidLidMonthInterval

Description: Indicates the monthly interval of the appointment or **meeting**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000013

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/month_interval

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.33

Alternate names: LID_MONTH_INTERVAL

2.173 PidLidMonthOfYear

Canonical name: PidLidMonthOfYear

Description: Indicates the month of the year in which the appointment or **meeting** occurs.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001006

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/monthofyear

Copyright © 2025 Microsoft Corporation

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.34

2.174 PidLidMonthOfYearMask

Canonical name: PidLidMonthOfYearMask

Description: Indicates the calculated month of the year in which the appointment or **meeting** occurs.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000017

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/moy_mask

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.35

Consuming reference: [MS-OXOCAL]

Alternate names: LID_MOY_MASK

2.175 PidLidNetShowUrl

Canonical name: PidLidNetShowUrl

Description: Specifies the **URL** to be launched when the user joins the **meeting**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008248

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.8

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: dispidNetShowURL

2.176 PidLidNoEndDateFlag

Canonical name: PidLidNoEndDateFlag

Description: Indicates whether the **recurrence pattern** has an end date.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100B

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.36

Copyright © 2025 Microsoft Corporation

Alternate names: http://schemas.microsoft.com/mapi/fnoenddate

2.177 PidLidNonSendableBcc

Canonical name: PidLidNonSendableBcc

Description: Contains a list of all of the **unsendable attendee**s who are also resources.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008538

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendablebcc

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.21

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidNonSendableBCC

2.178 PidLidNonSendableCc

Canonical name: PidLidNonSendableCc

Description: Contains a list of all of the **unsendable attendees** who are also **optional attendees**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008537

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendablecc

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.20

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidNonSendableCC

2.179 PidLidNonSendableTo

Canonical name: PidLidNonSendableTo

Description: Contains a list of all of the **unsendable attendees** who are also required attendees.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008536

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendableto

Area: Meetings

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCAL] section 2.2.1.19

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidNonSendableTo

2.180 PidLidNonSendBccTrackStatus

Canonical name: PidLidNonSendBccTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008545

Data type: PtypMultipleInteger32, 0x1003

WebDAV: http://schemas.microsoft.com/mapi/nonsendbcctrackstatus

Area: General Message Properties

Defining reference: [MS-OXOCAL] section 2.2.1.24

Consuming reference: [MS-XWDCAL]

Alternate names: dispidNonSendBccTrackStatus

2.181 PidLidNonSendCcTrackStatus

Canonical name: PidLidNonSendCcTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008544

Data type: PtypMultipleInteger32, 0x1003

WebDAV: http://schemas.microsoft.com/mapi/nonsendcctrackstatus

Area: General Message Properties

Defining reference: [MS-OXOCAL] section 2.2.1.23

Consuming reference: [MS-XWDCAL]

Alternate names: dispidNonSendCcTrackStatus

2.182 PidLidNonSendToTrackStatus

Canonical name: PidLidNonSendToTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008543

Data type: PtypMultipleInteger32, 0x1003

Copyright © 2025 Microsoft Corporation

WebDAV: http://schemas.microsoft.com/mapi/nonsendtotrackstatus

Area: General Message Properties

Defining reference: [MS-OXOCAL] section 2.2.1.22

Consuming references: [MS-XWDCAL]

Alternate names: dispidNonSendToTrackStatus

2.183 PidLidNoteColor

Canonical name: PidLidNoteColor

Description: Specifies the suggested background color of the **Note object**.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B00

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [MS-OXONOTE] section 2.2.1.1

Alternate names: dispidNoteColor

2.184 PidLidNoteHeight

Canonical name: PidLidNoteHeight

Description: Specifies the height of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B03

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [MS-OXONOTE] section 2.2.1.3

Alternate names: dispidNoteHeight

2.185 PidLidNoteWidth

Canonical name: PidLidNoteWidth

Description: Specifies the width of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B02

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [MS-OXONOTE] section 2.2.1.2

Copyright © 2025 Microsoft Corporation

Alternate names: dispidNoteWidth

2.186 PidLidNoteX

Canonical name: PidLidNoteX

Description: Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a **Note object**.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B04

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [MS-OXONOTE] section 2.2.1.4

Alternate names: dispidNoteX

2.187 PidLidNoteY

Canonical name: PidLidNoteY

Description: Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a **Note object**.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B05

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [MS-OXONOTE] section 2.2.1.5

Alternate names: dispidNoteY

2.188 PidLidOccurrences

Canonical name: PidLidOccurrences

Description: Indicates the number of occurrences in the recurring appointment or **meeting**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001005

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/occurrences

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.43

Copyright © 2025 Microsoft Corporation

2.189 PidLidOldLocation

Canonical name: PidLidOldLocation

Description: Indicates the original value of the **PidLidLocation** property (section 2.159) before a **meeting** update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000028

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.7

Alternate names: dispidOldLocation

2.190 PidLidOldRecurrenceType

Canonical name: PidLidOldRecurrenceType

Description: Indicates the **recurrence pattern** for the appointment or **meeting**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000018

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/recur_type

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.44

Alternate names: LID_RECUR_TYPE

2.191 PidLidOldWhenEndWhole

Canonical name: PidLidOldWhenEndWhole

Description: Indicates the original value of the **PidLidAppointmentEndWhole** property (section 2.14) before a **meeting** update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000002A

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.9

Alternate names: dispidOldWhenEndWhole

2.192 PidLidOldWhenStartWhole

Canonical name: PidLidOldWhenStartWhole

Copyright © 2025 Microsoft Corporation

Description: Indicates the original value of the **PidLidAppointmentStartWhole** property (section 2.29) before a **meeting** update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000029

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.6.8

Alternate names: dispidOldWhenStartWhole

2.193 PidLidOnlinePassword

Canonical name: PidLidOnlinePassword

Description: Specifies the password for a **meeting** on which the **PidLidConferencingType** property (section 2.66) has the value 0x00000002.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008249

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.9

Consuming reference: [MS-OXCICAL]

Alternate names: dispidOnlinePassword

2.194 PidLidOptionalAttendees

Canonical name: PidLidOptionalAttendees

Description: Specifies **optional attendees**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000007

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/optional_attendees

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.45

Alternate names: LID_OPTIONAL_ATTENDEES

2.195 PidLidOrganizerAlias

Canonical name: PidLidOrganizerAlias

Description: Specifies the email address of the **organizer**.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008243

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [MS-OXOCAL] section 2.2.1.56.6

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: dispidOrgAlias

2.196 PidLidOriginalStoreEntryId

Canonical name: PidLidOriginalStoreEntryId

Description: Specifies the **EntryID** of the delegator's **message store**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008237

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.4.9

Alternate names: dispidOrigStoreEid, http://schemas.microsoft.com/mapi/origstoreeid

2.197 PidLidOtherAddress

Canonical name: PidLidOtherAddress

Description: Specifies the complete address of the other address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801C

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:otherpostaladdress

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.8

Alternate names: dispidOtherAddress

2.198 PidLidOtherAddressCountryCode

Canonical name: PidLidOtherAddressCountryCode

Description: Specifies the country code portion of the other address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DC

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.6

Alternate names: dispidOtherAddressCountryCode

2.199 PidLidOwnerCriticalChange

Canonical name: PidLidOwnerCriticalChange

Description: Specifies the date and time at which a **Meeting Request object** was sent by the **organizer**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000001A

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:dtstamp,
http://schemas.microsoft.com/mapi/owner_critical_change

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.34

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: LID_OWNER_CRITICAL_CHANGE

2.200 PidLidOwnerName

Canonical name: PidLidOwnerName

Description: Indicates the name of the owner of the **mailbox**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/ownername

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.47

Alternate names: dispidOwnerName

2.201 PidLidPendingStateForSiteMailboxDocument

Canonical name: PidLidPendingStateForSiteMailboxDocument

Description: Specifies the synchronization state of the **Document object** that is in the Document Libraries folder of the **site mailbox**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x000085E0

Data type: **PtypInteger32**, 0x0003

Area: Site Mailbox

Defining reference: [MS-OXODOC] section 2.2.1.34

Alternate names: dispidPendingStateforTMDocument

2.202 PidLidPercentComplete

Canonical name: PidLidPercentComplete

Description: Indicates whether a time-flagged **Message object** is complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008102

Data type: **PtypFloating64**, 0x0005

Area: Tasks

Defining reference: [MS-OXOFLAG] section 2.2.2.3

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXCMAIL], [MS-OXOTASK]

Alternate names: dispidPercentComplete

2.203 PidLidPostalAddressId

Canonical name: PidLidPostalAddressId

Description: Specifies which physical address is the mailing address for this **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008022

Data type: **PtypInteger32**, 0x0003

WebDAV: urn:schemas:contacts:mailingaddressid

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.9

Consuming references: [MS-OXVCARD]

Alternate names: dispidPostalAddressId

2.204 PidLidPostRssChannel

Canonical name: PidLidPostRssChannel

Description: Contains the contents of the title field from the **XML** of the Atom feed or RSS channel.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008904

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [MS-OXORSS] section 2.2.1.5

Alternate names: dispidPostRssChannel

2.205 PidLidPostRssChannelLink

Canonical name: PidLidPostRssChannelLink

Description: Contains the **URL** of the RSS or Atom feed from which the XML file came.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008900

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [MS-OXORSS] section 2.2.1.1

Alternate names: dispidPostRssChannelLink

2.206 PidLidPostRssItemGuid

Canonical name: PidLidPostRssItemGuid

Description: Contains a unique identifier for the RSS object.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008903

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [MS-OXORSS] section 2.2.1.4

Alternate names: dispidPostRssItemGuid

2.207 PidLidPostRssItemHash

Canonical name: PidLidPostRssItemHash

Description: Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008902

Data type: PtypInteger32, 0x0003

Area: RSS

Defining reference: [MS-OXORSS] section 2.2.1.3

Copyright © 2025 Microsoft Corporation

Alternate names: dispidPostRssItemHash

2.208 PidLidPostRssItemLink

Canonical name: PidLidPostRssItemLink

Description: Contains the **URL** of the link from an RSS or Atom item.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008901

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [MS-OXORSS] section 2.2.1.2

Alternate names: dispidPostRssItemLink

2.209 PidLidPostRssItemXml

Canonical name: PidLidPostRssItemXml

Description: Contains the item element and all of its sub-elements from an RSS feed, or the entry element and all of its sub-elements from an Atom feed.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008905

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [MS-OXORSS] section 2.2.1.6

Alternate names: dispidPostRssItemXml

2.210 PidLidPostRssSubscription

Canonical name: PidLidPostRssSubscription

Description: Contains the user's preferred name for the RSS or Atom subscription.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008906

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [MS-OXORSS] section 2.2.1.7

Alternate names: dispidPostRssSubscription

2.211 PidLidPrivate

Canonical name: PidLidPrivate

Copyright © 2025 Microsoft Corporation

Description: Indicates whether the end user wishes for this **Message object** to be hidden from other users who have access to the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008506

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.15

Consuming references: [MS-OXCFXICS], [MS-OXOCAL], [MS-OXOCNTC], [MS-OXODOC], [MS-OXTNEF], [MS-OXONOTE], [MS-OXORMMS], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXOTASK]

Alternate names: dispidPrivate

2.212 PidLidPromptSendUpdate

Canonical name: PidLidPromptSendUpdate

Description: Indicates that the **Meeting Response object** was out-of-date when it was received.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008045

Data type: PtypBoolean, 0x000B

Area: Meeting Response

Defining reference: [MS-OXOCAL] section 2.2.7.8

Alternate names: dispidPromptSendUpdate

2.213 PidLidRecurrenceDuration

Canonical name: PidLidRecurrenceDuration

Description: Identifies the length, in minutes, of the appointment or **meeting**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100D

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/recurduration

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.7.48

2.214 PidLidRecurrencePattern

Canonical name: PidLidRecurrencePattern

Description: Specifies a description of the **recurrence pattern** of the **Calendar object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x00008232

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/recurpattern

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.46

Consuming reference: [MS-XWDCAL]

Alternate names: dispidRecurPattern

2.215 PidLidRecurrenceType

Canonical name: PidLidRecurrenceType

Description: Specifies the recurrence type of the **recurring series**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008231

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/recurtype

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.45

Consuming reference: [MS-XWDCAL]

Alternate names: dispidRecurType

2.216 PidLidRecurring

Canonical name: PidLidRecurring

Description: Specifies whether the object represents a **recurring series**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008223

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/recurring

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.12

Consuming references: [MS-OXCDATA], [MS-OXOSFLD], [MS-OXWAVLS], [MS-XWDCAL]

Alternate names: dispidRecurring

2.217 PidLidReferenceEntryId

Canonical name: PidLidReferenceEntryId

Copyright © 2025 Microsoft Corporation

Description: Specifies the value of the **EntryID** of the Contact object unless the Contact object is a copy of an earlier original.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BD

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.1

Alternate names: dispidReferenceEID

2.218 PidLidReminderDelta

Canonical name: PidLidReminderDelta

Description: Specifies the interval, in minutes, between the time at which the **reminder** first becomes overdue and the start time of the **Calendar object**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008501

Data type: PtypInteger32, 0x0003

Area: Reminders

Defining reference: [MS-OXORMDR] section 2.2.1.3

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOCAL], [MS-OXODOC], [MS-OXOFLAG], [MS-OXTNEF], [MS-XWDCAL], [MS-OXONOTE], [MS-OXORMMS], [MS-OXOJRNL], [MS-OXOPOST]

Alternate names: dispidReminderDelta, http://schemas.microsoft.com/mapi/reminderdelta

2.219 PidLidReminderFileParameter

Canonical name: PidLidReminderFileParameter

Description: Specifies the filename of the sound that a client is to play when the **reminder** for that object becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851F

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/reminderfileparam

Area: Reminders

Defining reference: [MS-OXORMDR] section 2.2.1.7

Consuming reference: [MS-XWDCAL], [MS-OXOCAL]

Alternate names: dispidReminderFileParam

Copyright © 2025 Microsoft Corporation

2.220 PidLidReminderOverride

Canonical name: PidLidReminderOverride

Description: Specifies whether the client is to respect the current values of the **PidLidReminderPlaySound** property (section 2.221) and the **PidLidReminderFileParameter** property (section 2.219), or use the default values for those properties.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851C

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderoverride

Area: Reminders

Defining reference: [MS-OXORMDR] section 2.2.1.5

Consuming reference: [MS-XWDCAL], [MS-OXOCAL]

Alternate names: dispidReminderOverride

2.221 PidLidReminderPlaySound

Canonical name: PidLidReminderPlaySound

Description: Specifies whether the client is to play a sound when the **reminder** becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851E

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderplaysound

Area: Reminders

Defining reference: [MS-OXORMDR] section 2.2.1.6

Consuming reference: [MS-XWDCAL], [MS-OXOCAL]

Alternate names: dispidReminderPlaySound

2.222 PidLidReminderSet

Canonical name: PidLidReminderSet

Description: Specifies whether a **reminder** is set on the object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008503

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderset

Area: Reminders

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXORMDR] section 2.2.1.1

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOCAL], [MS-OXOCFG], [MS-OXODOC], [MS-OXOFLAG], [MS-OXOSFLD], [MS-OXOTASK], [MS-OXTNEF], [MS-OXWAVLS], [MS-XWDCAL], [MS-OXOCNTC], [MS-OXONOTE], [MS-OXORMMS], [MS-OXOPOST]

Alternate names: dispidReminderSet

2.223 PidLidReminderSignalTime

Canonical name: PidLidReminderSignalTime

Description: Specifies the point in time when a **reminder** transitions from pending to overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008560

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindernexttime

Area: Reminders

Defining reference: [MS-OXORMDR] section 2.2.1.2

Consuming references: [MS-OXCICAL], [MS-OXOCAL], [MS-OXOFLAG], [MS-XWDCAL], [MS-OXODOC]

Alternate names: dispidReminderNextTime

2.224 PidLidReminderTime

Canonical name: PidLidReminderTime

Description: Specifies the initial **signal time** for objects that are not **Calendar objects**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008502

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertime

Area: Reminders

Defining reference: [MS-OXORMDR] section 2.2.1.4

Consuming references: [MS-OXCICAL], [MS-OXOCAL], [MS-OXOFLAG], [MS-XWDCAL]

Alternate names: dispidReminderTime

2.225 PidLidReminderTimeDate

Canonical name: PidLidReminderTimeDate

Description: Indicates the time and date of the **reminder** for the appointment or **meeting**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x00008505

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertimedate

Area: Reminders

Defining reference: [MS-XWDCAL] section 2.2.7.59

Alternate names: dispidReminderTimeDate

2.226 PidLidReminderTimeTime

Canonical name: PidLidReminderTimeTime

Description: Indicates the time of the **reminder** for the appointment or **meeting**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008504

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertimetime

Area: Reminders

Defining reference: [MS-XWDCAL] section 2.2.7.60

Consuming references: [MS-OXONOTE], [MS-OXOJRNL], [MS-OXOPOST]

Alternate names: dispidReminderTimeTime

2.227 PidLidReminderType

Canonical name: PidLidReminderType

Description: This property is not set and, if set, is ignored.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851D

Data type: PtypInteger32, 0x0003

Area: Reminders

Defining reference: [MS-OXORMDR] section 2.2.1.9

Consuming reference: [MS-XWDCAL]

Alternate names: dispidReminderType, http://schemas.microsoft.com/mapi/remindertype

2.228 PidLidRemoteStatus

Canonical name: PidLidRemoteStatus

Description: Indicates the remote status of the **calendar** item.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x00008511

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/remotestatus

Area: Run-time configuration

Defining reference: [MS-XWDCAL] section 2.2.7.62

Alternate names: dispidRemoteStatus

2.229 PidLidRequiredAttendees

Canonical name: PidLidRequiredAttendees

Description: Identifies required attendees for the appointment or **meeting**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000006

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/required_attendees

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.63

Consuming references: [MS-OXOCAL]

Alternate names: LID_REQUIRED_ATTENDEES

2.230 PidLidResourceAttendees

Canonical name: PidLidResourceAttendees

Description: Identifies resource attendees for the appointment or **meeting**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000008

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/resource_attendees

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.64

Consuming references: [MS-OXOCAL]

Alternate names: LID_RESOURCE_ATTENDEES

2.231 PidLidResponseStatus

Canonical name: PidLidResponseStatus

Description: Specifies the response status of an attendee.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008218

Data type: PtypInteger32, 0x0003

WebDAV: urn:schemas:calendar:attendeestatus, http://schemas.microsoft.com/mapi/responsestatus

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.11

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidResponseStatus

2.232 PidLidServerProcessed

Canonical name: PidLidServerProcessed

Description: Indicates whether the **Meeting Request object** or **Meeting Update object** has been processed.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CC

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.5.4

Alternate names: dispidExchangeProcessed

2.233 PidLidServerProcessingActions

Canonical name: PidLidServerProcessingActions

Description: Indicates what processing **actions** have been taken on this **Meeting Request object** or **Meeting Update object**.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CD

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.5.5

Alternate names: dispidExchangeProcessingAction

2.234 PidLidSharingAnonymity

Canonical name: PidLidSharingAnonymity

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A19

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingAnonymity

2.235 PidLidSharingBindingEntryId

Canonical name: PidLidSharingBindingEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2D

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingBindingEid

2.236 PidLidSharingBrowseUrl

Canonical name: PidLidSharingBrowseUrl

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A51

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingBrowseUrl

2.237 PidLidSharingCapabilities

Canonical name: PidLidSharingCapabilities

Description: Indicates that the **Message object** relates to a **special folder**.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A17

Data type: PtypInteger32, 0x0003

Copyright © 2025 Microsoft Corporation

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.1

Alternate names: dispidSharingCaps

2.238 PidLidSharingConfigurationUrl

Canonical name: PidLidSharingConfigurationUrl

Description: Contains a zero-length string.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A24

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.3

Alternate names: dispidSharingConfigUrl

2.239 PidLidSharingDataRangeEnd

Canonical name: PidLidSharingDataRangeEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A45

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingDataRangeEnd

2.240 PidLidSharingDataRangeStart

Canonical name: PidLidSharingDataRangeStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A44

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingDataRangeStart

Copyright © 2025 Microsoft Corporation

2.241 PidLidSharingDetail

Canonical name: PidLidSharingDetail

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingDetail

2.242 PidLidSharingExtensionXml

Canonical name: PidLidSharingExtensionXml

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A21

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingExtXml

2.243 PidLidSharingFilter

Canonical name: PidLidSharingFilter

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A13

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingFilter

2.244 PidLidSharingFlags

Canonical name: PidLidSharingFlags

Copyright © 2025 Microsoft Corporation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingFlags

2.245 PidLidSharingFlavor

Canonical name: PidLidSharingFlavor

Description: Indicates the type of Sharing **Message object**.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A18

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.5

Alternate names: dispidSharingFlavor

2.246 PidLidSharingFolderEntryId

Canonical name: PidLidSharingFolderEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A15

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingFolderEid

2.247 PidLidSharingIndexEntryId

Canonical name: PidLidSharingIndexEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x00008A2E

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingIndexEid

2.248 PidLidSharingInitiatorEntryId

Canonical name: PidLidSharingInitiatorEntryId

Description: Contains the value of the **PidTagEntryId** property (section 2.684) for the **Address Book object** of the currently logged-on user.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A09

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.7

Alternate names: dispidSharingInitiatorEid

2.249 PidLidSharingInitiatorName

Canonical name: PidLidSharingInitiatorName

Description: Contains the value of the **PidTagDisplayName** property (section 2.677) from the **Address Book object** identified by the **PidLidSharingInitiatorEntryId** property (section 2.248).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A07

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.8

Alternate names: dispidSharingInitiatorName

2.250 PidLidSharingInitiatorSmtp

Canonical name: PidLidSharingInitiatorSmtp

Description: Contains the value of the **PidTagSmtpAddress** property (section 2.1022) from the **Address Book object** identified by the **PidLidSharingInitiatorEntryId** property (section 2.248).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A08

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.9

Alternate names: dispidSharingInitiatorSmtp

2.251 PidLidSharingInstanceGuid

Canonical name: PidLidSharingInstanceGuid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1C

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingInstanceGuid

2.252 PidLidSharingLastAutoSyncTime

Canonical name: PidLidSharingLastAutoSyncTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A55

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingLastAutoSync

2.253 PidLidSharingLastSyncTime

Canonical name: PidLidSharingLastSyncTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1F

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Copyright © 2025 Microsoft Corporation

Alternate names: dispidSharingLastSync

2.254 PidLidSharingLocalComment

Canonical name: PidLidSharingLocalComment

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingLocalComment

2.255 PidLidSharingLocalLastModificationTime

Canonical name: PidLidSharingLocalLastModificationTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A23

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingLocalLastMod

2.256 PidLidSharingLocalName

Canonical name: PidLidSharingLocalName

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0F

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingLocalName

Copyright © 2025 Microsoft Corporation

2.257 PidLidSharingLocalPath

Canonical name: PidLidSharingLocalPath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0E

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingLocalPath

2.258 PidLidSharingLocalStoreUid

Canonical name: PidLidSharingLocalStoreUid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A49

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingLocalStoreUid

2.259 PidLidSharingLocalType

Canonical name: PidLidSharingLocalType

Description: Contains the value of the **PidTagContainerClass** property (section 2.643) of the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A14

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.10

Alternate names: dispidSharingLocalType

2.260 PidLidSharingLocalUid

Canonical name: PidLidSharingLocalUid

Copyright © 2025 Microsoft Corporation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A10

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingLocalUid

2.261 PidLidSharingOriginalMessageEntryId

Canonical name: PidLidSharingOriginalMessageEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A29

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingOriginalMessageEid

2.262 PidLidSharingParentBindingEntryId

Canonical name: PidLidSharingParentBindingEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A5C

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingParentBindingEid

2.263 PidLidSharingParticipants

Canonical name: PidLidSharingParticipants

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1E

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingParticipants

2.264 PidLidSharingPermissions

Canonical name: PidLidSharingPermissions

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingPermissions

2.265 PidLidSharingProviderExtension

Canonical name: PidLidSharingProviderExtension

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0B

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingProviderExtension

2.266 PidLidSharingProviderGuid

Canonical name: PidLidSharingProviderGuid

Description: Contains the value "%xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.00.46".

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A01

Data type: PtypBinary, 0x0102

Copyright © 2025 Microsoft Corporation

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.12

Alternate names: dispidSharingProviderGuid

2.267 PidLidSharingProviderName

Canonical name: PidLidSharingProviderName

Description: Contains a user-displayable name of the sharing provider identified by the **PidLidSharingProviderGuid** property (section 2.266).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A02

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.14

Alternate names: dispidSharingProviderName

2.268 PidLidSharingProviderUrl

Canonical name: PidLidSharingProviderUrl

Description: Contains a **URL** related to the sharing provider identified by the **PidLidSharingProviderGuid** property (section 2.266).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A03

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.16

Alternate names: dispidSharingProviderUrl

2.269 PidLidSharingRangeEnd

Canonical name: PidLidSharingRangeEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A47

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Copyright © 2025 Microsoft Corporation

Alternate names: dispidSharingRangeEnd

2.270 PidLidSharingRangeStart

Canonical name: PidLidSharingRangeStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A46

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRangeStart

2.271 PidLidSharingReciprocation

Canonical name: PidLidSharingReciprocation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingReciprocation

2.272 PidLidSharingRemoteByteSize

Canonical name: PidLidSharingRemoteByteSize

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Consuming reference: [MS-OXSHARE]

Alternate names: dispidSharingRemoteByteSize

Copyright © 2025 Microsoft Corporation

2.273 PidLidSharingRemoteComment

Canonical name: PidLidSharingRemoteComment

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2F

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemoteComment

2.274 PidLidSharingRemoteCrc

Canonical name: PidLidSharingRemoteCrc

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4C

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemoteCrc

2.275 PidLidSharingRemoteLastModificationTime

Canonical name: PidLidSharingRemoteLastModificationTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A22

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemoteLastMod

2.276 PidLidSharingRemoteMessageCount

Canonical name: PidLidSharingRemoteMessageCount

Copyright © 2025 Microsoft Corporation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4F

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemoteMsgCount

2.277 PidLidSharingRemoteName

Canonical name: PidLidSharingRemoteName

Description: Contains the value of the **PidTagDisplayName** property (section 2.677) on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A05

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.1

Alternate names: dispidSharingRemoteName

2.278 PidLidSharingRemotePass

Canonical name: PidLidSharingRemotePass

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemotePass

2.279 PidLidSharingRemotePath

Canonical name: PidLidSharingRemotePath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A04

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemotePath

2.280 PidLidSharingRemoteStoreUid

Canonical name: PidLidSharingRemoteStoreUid

Description: Contains a hexadecimal string representation of the value of the **PidTagStoreEntryId** property (section 2.1030) on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A48

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.3

Alternate names: dispidSharingRemoteStoreUid

2.281 PidLidSharingRemoteType

Canonical name: PidLidSharingRemoteType

Description: Contains the same value as the **PidLidSharingLocalType** property (section 2.259).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.5

Alternate names: dispidSharingRemoteType

2.282 PidLidSharingRemoteUid

Canonical name: PidLidSharingRemoteUid

Description: Contains the **EntryID** of the folder being shared.

Property set: PSTID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A06

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.7

Alternate names: dispidSharingRemoteUid

2.283 PidLidSharingRemoteUser

Canonical name: PidLidSharingRemoteUser

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0C

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemoteUser

2.284 PidLidSharingRemoteVersion

Canonical name: PidLidSharingRemoteVersion

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A5B

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRemoteVersion

2.285 PidLidSharingResponseTime

Canonical name: PidLidSharingResponseTime

Description: Contains the time at which the **recipient** of the sharing request sent a sharing response.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A28

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.4.1

Copyright © 2025 Microsoft Corporation

Alternate names: dispidSharingResponseTime

2.286 PidLidSharingResponseType

Canonical name: PidLidSharingResponseType

Description: Contains the type of response with which the **recipient** of the sharing request responded.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A27

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.4.2

Alternate names: dispidSharingResponseType

2.287 PidLidSharingRoamLog

Canonical name: PidLidSharingRoamLog

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4E

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingRoamLog

2.288 PidLidSharingStart

Canonical name: PidLidSharingStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A25

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingStart

Copyright © 2025 Microsoft Corporation

2.289 PidLidSharingStatus

Canonical name: PidLidSharingStatus

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A00

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingStatus

2.290 PidLidSharingStop

Canonical name: PidLidSharingStop

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A26

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingStop

2.291 PidLidSharingSyncFlags

Canonical name: PidLidSharingSyncFlags

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A60

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingSyncFlags

2.292 PidLidSharingSyncInterval

Canonical name: PidLidSharingSyncInterval

Copyright © 2025 Microsoft Corporation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingSyncInterval

2.293 PidLidSharingTimeToLive

Canonical name: PidLidSharingTimeToLive

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2C

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingTimeToLive

2.294 PidLidSharingTimeToLiveAuto

Canonical name: PidLidSharingTimeToLiveAuto

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A56

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingTimeToLiveAuto

2.295 PidLidSharingWorkingHoursDays

Canonical name: PidLidSharingWorkingHoursDays

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A42

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingWorkingHoursDays

2.296 PidLidSharingWorkingHoursEnd

Canonical name: PidLidSharingWorkingHoursEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A41

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingWorkingHoursEnd

2.297 PidLidSharingWorkingHoursStart

Canonical name: PidLidSharingWorkingHoursStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A40

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingWorkingHoursStart

2.298 PidLidSharingWorkingHoursTimeZone

Canonical name: PidLidSharingWorkingHoursTimeZone

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A43

Copyright © 2025 Microsoft Corporation

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Alternate names: dispidSharingWorkingHoursTZ

2.299 PidLidSideEffects

Canonical name: PidLidSideEffects

Description: Specifies how a **Message object** is handled by the client in relation to certain user interface **actions** by the user, such as deleting a message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008510

Data type: PtypInteger32, 0x0003

Area: Run-time configuration

Defining reference: [MS-OXCMSG] section 2.2.1.16

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCAL], [MS-OXORSS], [MS-OXTNEF], [MS-OXOCNTC], [MS-OXONOTE], [MS-OXORMMS], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXOTASK]

Alternate names: dispidSideEffects

2.300 PidLidSingleBodyICal

Canonical name: PidLidSingleBodyICal

Description: Indicates that the original MIME message contained a single **MIME** part.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827B

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [MS-OXCICAL] section 2.1.3.4.2

Consuming reference: [MS-OXCMAIL]

Alternate names: IsSingleBodyICal, dispidIsSingleBodyICal

2.301 PidLidSmartNoAttach

Canonical name: PidLidSmartNoAttach

Description: Indicates whether the **Message object** has no end-user visible attachments.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008514

Data type: PtypBoolean, 0x000B

Copyright © 2025 Microsoft Corporation

Area: Run-time configuration

Defining reference: [MS-OXCMSG] section 2.2.1.14

Alternate names: dispidSmartNoAttach

2.302 PidLidSpamOriginalFolder

Canonical name: PidLidSpamOriginalFolder

Description: Specifies which folder a message was in before it was filtered into the Junk Email folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000859C

Data type: PtypBinary, 0x0102

Area: Spam

Defining reference: [MS-OXCSPAM] section 2.2.1.1

Alternate names: dispidSpamOriginalFolder

2.303 PidLidStartRecurrenceDate

Canonical name: PidLidStartRecurrenceDate

Description: Identifies the start date of the **recurrence pattern**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000D

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_date

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.66

Consuming reference: [MS-OXOCAL]

Alternate names: LID_START_RECUR_DATE

2.304 PidLidStartRecurrenceTime

Canonical name: PidLidStartRecurrenceTime

Description: Identifies the start time of the **recurrence pattern**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000E

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_time

Area: Meetings

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-XWDCAL] section 2.2.7.67

Consuming references: [MS-OXOCAL], [MS-OXCICAL]

Alternate names: LID_START_RECUR_TIME

2.305 PidLidTaskAcceptanceState

Canonical name: PidLidTaskAcceptanceState

Description: Indicates the acceptance state of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000812A

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.30

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST]

Alternate names: dispidTaskDelegValue

2.306 PidLidTaskAccepted

Canonical name: PidLidTaskAccepted

Description: Indicates whether a task assignee has replied to a **task request** for this **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008108

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.7

Consuming reference: [MS-OXOSFLD]

Alternate names: dispidTaskAccepted

2.307 PidLidTaskActualEffort

Canonical name: PidLidTaskActualEffort

Description: Indicates the number of minutes that the user actually spent working on a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008110

Data type: PtypInteger32, 0x0003

Area: Tasks

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOTASK] section 2.2.2.2.11

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskActualEffort

2.308 PidLidTaskAssigner

Canonical name: PidLidTaskAssigner

Description: Specifies the name of the user that last assigned the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008121

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.24

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskDelegator

2.309 PidLidTaskAssigners

Canonical name: PidLidTaskAssigners

Description: Contains a stack of entries, each of which represents a task assigner.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008117

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.16

Alternate names: dispidTaskMyDelegators

2.310 PidLidTaskComplete

Canonical name: PidLidTaskComplete

Description: Indicates that the task is complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811C

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.20

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXODOC], [MS-OXOFLAG], [MS-OXOCNTC], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskComplete

2.311 PidLidTaskCustomFlags

Canonical name: PidLidTaskCustomFlags

Description: The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008139

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.33

Alternate names: dispidTaskCustomFlags

2.312 PidLidTaskDateCompleted

Canonical name: PidLidTaskDateCompleted

Description: Specifies the date when the user completed work on the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000810F

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.9

Consuming references: [MS-OXCMAIL], [MS-OXOFLAG]

Alternate names: dispidTaskDateCompleted

2.313 PidLidTaskDeadOccurrence

Canonical name: PidLidTaskDeadOccurrence

Description: Indicates whether new occurrences remain to be generated.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008109

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.8

Alternate names: dispidTaskDeadOccur

Copyright © 2025 Microsoft Corporation

2.314 PidLidTaskDueDate

Canonical name: PidLidTaskDueDate

Description: Specifies the date by which the user expects work on the task to be complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008105

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.5

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOFLAG], [MS-OXORMDR]

Alternate names: dispidTaskDueDate

2.315 PidLidTaskEstimatedEffort

Canonical name: PidLidTaskEstimatedEffort

Description: Indicates the number of minutes that the user expects to work on a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008111

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.12

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST]

Alternate names: dispidTaskEstimatedEffort

2.316 PidLidTaskFCreator

Canonical name: PidLidTaskFCreator

Description: Indicates that the **Task object** was originally created by the **action** of the current user or user agent instead of by the processing of a **task request**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811E

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.21

Alternate names: dispidTaskFCreator

Copyright © 2025 Microsoft Corporation

2.317 PidLidTaskFFixOffline

Canonical name: PidLidTaskFFixOffline

Description: Indicates the accuracy of the **PidLidTaskOwner** property (section 2.328).

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000812C

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.31

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskFFixOffline

2.318 PidLidTaskFRecurring

Canonical name: PidLidTaskFRecurring

Description: Indicates whether the task includes a **recurrence pattern**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008126

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.28

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskFRecur

2.319 PidLidTaskGlobalId

Canonical name: PidLidTaskGlobalId

Description: Contains a unique **GUID** for this task, which is used to locate an existing task upon receipt of a task response or task update.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008519

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.32

Alternate names: dispidTaskGlobalObjId

Copyright © 2025 Microsoft Corporation

2.320 PidLidTaskHistory

Canonical name: PidLidTaskHistory

Description: Indicates the type of change that was last made to the **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811A

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.18

Alternate names: dispidTaskHistory

2.321 PidLidTaskLastDelegate

Canonical name: PidLidTaskLastDelegate

Description: Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008125

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.27

Alternate names: dispidTaskLastDelegate

2.322 PidLidTaskLastUpdate

Canonical name: PidLidTaskLastUpdate

Description: Contains the date and time of the most recent change made to the **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008115

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.10

Alternate names: dispidTaskLastUpdate

2.323 PidLidTaskLastUser

Canonical name: PidLidTaskLastUser

Description: Contains the name of the most recent user to have been the owner of the task.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008122

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.25

Alternate names: dispidTaskLastUser

2.324 PidLidTaskMode

Canonical name: PidLidTaskMode

Description: Specifies the assignment status of the embedded **Task object**.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008518

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.3.2

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXTNEF] , [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE], [MS-OXORMMS]

Alternate names: dispidTaskMode

2.325 PidLidTaskMultipleRecipients

Canonical name: PidLidTaskMultipleRecipients

Description: Provides optimization hints about the **recipients** of a **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008120

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.23

Alternate names: dispidTaskMultRecips

2.326 PidLidTaskNoCompute

Canonical name: PidLidTaskNoCompute

Description: Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008124

Copyright © 2025 Microsoft Corporation

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.35

Consuming reference: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskNoCompute

2.327 PidLidTaskOrdinal

Canonical name: PidLidTaskOrdinal

Description: Provides an aid to custom sorting of **Task objects**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008123

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.26

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskOrdinal

2.328 PidLidTaskOwner

Canonical name: PidLidTaskOwner

Description: Contains the name of the owner of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811F

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.22

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskOwner

2.329 PidLidTaskOwnership

Canonical name: PidLidTaskOwnership

Description: Indicates the role of the current user relative to the **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property long ID (LID): 0x00008129

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.29

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskOwnership

2.330 PidLidTaskRecurrence

Canonical name: PidLidTaskRecurrence

Description: Contains a **RecurrencePattern** structure that provides information about **recurring tasks**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008116

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.15

Consuming references: [MS-OXORMDR]

Alternate names: dispidTaskRecur

2.331 PidLidTaskResetReminder

Canonical name: PidLidTaskResetReminder

Description: Indicates whether future **instances** of **recurring tasks** need **reminders**, even though the value of the **PidLidReminderSet** property (section 2.222) is 0x00.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008107

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.6

Consuming references: [MS-OXORMDR]

Alternate names: dispidTaskResetReminder

2.332 PidLidTaskRole

Canonical name: PidLidTaskRole

Copyright © 2025 Microsoft Corporation

Description: Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008127

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.34

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOTASK], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskRole

2.333 PidLidTaskStartDate

Canonical name: PidLidTaskStartDate

Description: Specifies the date on which the user expects work on the task to begin.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008104

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.4

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOFLAG], [MS-OXORMDR]

Alternate names: dispidTaskStartDate

2.334 PidLidTaskState

Canonical name: PidLidTaskState

Description: Indicates the current assignment state of the **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008113

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.14

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOSFLD], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskState

Copyright © 2025 Microsoft Corporation

2.335 PidLidTaskStatus

Canonical name: PidLidTaskStatus

Description: Specifies the status of a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008101

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.2

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXODOC], [MS-OXOFLAG], [MS-OXOSFLD], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST]

Alternate names: dispidTaskStatus

2.336 PidLidTaskStatusOnComplete

Canonical name: PidLidTaskStatusOnComplete

Description: Indicates whether the task assignee has been requested to send an email message update upon completion of the assigned task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008119

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.17

Alternate names: dispidTaskSOC

2.337 PidLidTaskUpdates

Canonical name: PidLidTaskUpdates

Description: Indicates whether the task assignee has been requested to send a task update when the assigned **Task object** changes.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811B

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.19

Alternate names: dispidTaskUpdates

Copyright © 2025 Microsoft Corporation

2.338 PidLidTaskVersion

Canonical name: PidLidTaskVersion

Description: Indicates which copy is the latest update of a **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008112

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.13

Consuming references: [MS-OXCFXICS], [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE]

Alternate names: dispidTaskVersion

2.339 PidLidTeamTask

Canonical name: PidLidTeamTask

Description: This property is set by the client but is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008103

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.2.2.36

Consuming References: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXODOC]

Alternate names: dispidTeamTask

2.340 PidLidTimeZone

Canonical name: PidLidTimeZone

Description: Specifies information about the time zone of a recurring **meeting**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/time_zone

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.5.6

Consuming reference: [MS-XWDCAL]

Copyright © 2025 Microsoft Corporation

Alternate names: LID_TIME_ZONE

2.341 PidLidTimeZoneDescription

Canonical name: PidLidTimeZoneDescription

Description: Specifies a human-readable description of the time zone that is represented by the data in the **PidLidTimeZoneStruct** property (section 2.342).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008234

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/timezonedesc

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.40

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidTimeZoneDesc

2.342 PidLidTimeZoneStruct

Canonical name: PidLidTimeZoneStruct

Description: Specifies time zone information for a recurring **meeting**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008233

Data type: PtypBinary, 0x0102

WebDAV: http://schemas.microsoft.com/mapi/timezonestruct

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.1.39

Consuming references: [MS-OXCICAL], [MS-XWDCAL]

Alternate names: dispidTimeZoneStruct

2.343 PidLidToAttendeesString

Canonical name: PidLidToAttendeesString

Description: Contains a list of all of the sendable attendees who are also required attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823B

Data type: PtypString, 0x001F

Area: Meetings

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCAL] section 2.2.1.17

Alternate names: dispidToAttendeesString

2.344 PidLidToDoOrdinalDate

Canonical name: PidLidToDoOrdinalDate

Description: Contains the current time, in **UTC**, which is used to determine the sort order of objects in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A0

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [MS-OXOFLAG] section 2.2.1.13

Consuming reference: [MS-OXCFXICS]

Alternate names: dispidToDoOrdinalDate

2.345 PidLidToDoSubOrdinal

Canonical name: PidLidToDoSubOrdinal

Description: Contains the numerals 0 through 9 that are used to break a tie when the **PidLidToDoOrdinalDate** property (section 2.344) is used to perform a sort of objects.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A1

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [MS-OXOFLAG] section 2.2.1.14

Consuming reference: [MS-OXCFXICS]

Alternate names: dispidToDoSubOrdinal

2.346 PidLidToDoTitle

Canonical name: PidLidToDoTitle

Description: Contains user-specifiable text to identify this **Message object** in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A4

Data type: PtypString, 0x001F

Area: Tasks

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOFLAG] section 2.2.1.12

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL]

Alternate names: dispidToDoTitle

2.347 PidLidUseTnef

Canonical name: PidLidUseTnef

Description: Specifies whether **Transport Neutral Encapsulation Format (TNEF)** is to be included on a message when the message is converted from TNEF to **MIME** or **SMTP** format.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008582

Data type: PtypBoolean, 0x000B

Area: Run-time configuration

Defining reference: [MS-OXOMSG] section 2.2.1.66

Consuming references: [MS-OXCFXICS], [MS-OXTNEF]

Alternate names: dispidUseTNEF

2.348 PidLidValidFlagStringProof

Canonical name: PidLidValidFlagStringProof

Description: Contains the value of the **PidTagMessageDeliveryTime** property (section 2.791) when modifying the **PidLidFlagRequest** property (section 2.136).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BF

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [MS-OXOFLAG] section 2.2.1.11

Consuming references: [MS-OXODOC], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXONOTE], [MS-OXOTASK]

Alternate names: dispidValidFlagStringProof

2.349 PidLidVerbResponse

Canonical name: PidLidVerbResponse

Description: Specifies the voting option that a respondent has selected.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008524

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.75

Alternate names: dispidVerbResponse

2.350 PidLidVerbStream

Canonical name: PidLidVerbStream

Description: Specifies what voting responses the user can make in response to the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008520

Data type: PtypBinary, 0x0102

Area: Run-time configuration

Defining reference: [MS-OXOMSG] section 2.2.1.74

Alternate names: dispidVerbStream

2.351 PidLidWeddingAnniversaryLocal

Canonical name: PidLidWeddingAnniversaryLocal

Description: Specifies the wedding anniversary of the **contact**, at midnight in the client's local time zone, and is saved without any time zone conversions.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DF

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.5.5

Alternate names: dispidApptAnniversaryLocal

2.352 PidLidWeekInterval

Canonical name: PidLidWeekInterval

Description: Identifies the number of weeks that occur between each **meeting**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000012

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/week_interval

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.71

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXOCAL]

Alternate names: LID_WEEK_INTERVAL

2.353 PidLidWhere

Canonical name: PidLidWhere

Description: Contains the value of the **PidLidLocation** property (section 2.159) from the associated **Meeting object**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000002

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/where

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.5.3

Consuming reference: [MS-XWDCAL]

Alternate names: LID_WHERE

2.354 PidLidWorkAddress

Canonical name: PidLidWorkAddress

Description: Specifies the complete address of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801B

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:workaddress

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.8

Alternate names: dispidWorkAddress

2.355 PidLidWorkAddressCity

Canonical name: PidLidWorkAddressCity

Description: Specifies the city or locality portion of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008046

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:l

Copyright © 2025 Microsoft Corporation

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.2

Alternate names: dispidWorkAddressCity

2.356 PidLidWorkAddressCountry

Canonical name: PidLidWorkAddressCountry

Description: Specifies the country or region portion of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008049

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:co

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.5

Alternate names: dispidWorkAddressCountry

2.357 PidLidWorkAddressCountryCode

Canonical name: PidLidWorkAddressCountryCode

Description: Specifies the country code portion of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DB

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.6

Alternate names: dispidWorkAddressCountryCode

2.358 PidLidWorkAddressPostalCode

Canonical name: PidLidWorkAddressPostalCode

Description: Specifies the postal code (ZIP code) portion of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008048

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postalcode

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.4

Copyright © 2025 Microsoft Corporation

Alternate names: dispidWorkAddressPostalCode

2.359 PidLidWorkAddressPostOfficeBox

Canonical name: PidLidWorkAddressPostOfficeBox

Description: Specifies the post office box portion of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postofficebox

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.7

Alternate names: dispidWorkAddressPostOfficeBox

2.360 PidLidWorkAddressState

Canonical name: PidLidWorkAddressState

Description: Specifies the state or province portion of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008047

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:st

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.3

Alternate names: dispidWorkAddressState

2.361 PidLidWorkAddressStreet

Canonical name: PidLidWorkAddressStreet

Description: Specifies the street portion of the work address of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008045

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:street

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.1

Alternate names: dispidWorkAddressStreet

Copyright © 2025 Microsoft Corporation

2.362 PidLidYearInterval

Canonical name: PidLidYearInterval

Description: Indicates the yearly interval of the appointment or **meeting**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000014

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/year_interval

Area: Meetings

Defining reference: [MS-XWDCAL] section 2.2.7.73

Consuming reference: [MS-OXOCAL]

Alternate names: LID_YEAR_INTERVAL

2.363 PidLidYomiCompanyName

Canonical name: PidLidYomiCompanyName

Description: Specifies the phonetic pronunciation of the company name of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomiorganization

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.6.8

Alternate names: dispidYomiCompanyName

2.364 PidLidYomiFirstName

Canonical name: PidLidYomiFirstName

Description: Specifies the phonetic pronunciation of the given name of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802C

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomifirstname

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.1.9

Alternate names: dispidYomiFirstName

Copyright © 2025 Microsoft Corporation

2.365 PidLidYomiLastName

Canonical name: PidLidYomiLastName

Description: Specifies the phonetic pronunciation of the surname of the **contact**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802D

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomilastname

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.1.10

Alternate names: dispidYomiLastName

2.366 PidNameAcceptLanguage

Canonical name: PidNameAcceptLanguage

Description: Contains the value of the **MIME** Accept-Language header.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Accept-Language

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.42

Consuming reference: [MS-OXCMAIL]

Alternate names: AcceptLanguage

2.367 PidNameApplicationName

Canonical name: PidNameApplicationName

Description: Specifies the application used to open the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: AppName

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.9

Alternate names: urn:schemas-microsoft-com:office:office#NameOfApplication

2.368 PidNameAttachmentMacContentType

Canonical name: PidNameAttachmentMacContentType

Copyright © 2025 Microsoft Corporation

Description: Contains the Content-Type of the Mac attachment.

Property set: PSETID_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

Property name: AttachmentMacContentType

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming reference: [MS-OXCMAIL]

2.369 PidNameAttachmentMacInfo

Canonical name: PidNameAttachmentMacInfo

Description: Contains the headers and resource fork data associated with the Mac attachment.

Property set: PSETID_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

Property name: AttachmentMacInfo

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming reference: [MS-OXCMAIL]

2.370 PidNameAttachmentOriginalPermissionType

Canonical name: PidNameAttachmentOriginalPermissionType

Description: Contains the original permission type data associated with a web reference attachment.

Property set: PSETID_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

Property name: AttachmentOriginalPermissionType

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.27

2.371 PidNameAttachmentPermissionType

Canonical name: PidNameAttachmentPermissionType

Description: Contains the permission type data associated with a web reference attachment.

Property set: PSETID_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

Property name: AttachmentPermissionType

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXCMSG] section 2.2.2.28

2.372 PidNameAttachmentProviderType

Canonical name: PidNameAttachmentProviderType

Description: Contains the provider type data associated with a web reference attachment.

Property set: PSETID_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

Property name: AttachmentProviderType

Data type: PtypeString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.26

2.373 PidNameAudioNotes

Canonical name: PidNameAudioNotes

Description: Contains textual annotations to a voice message after it has been delivered to the user's **mailbox**.

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: UMAudioNotes

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.15

Alternate names: UMAudioNotes

2.374 PidNameAuthor

Canonical name: PidNameAuthor

Description: Specifies the author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Author

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.3

Alternate names: urn:schemas-microsoft-com:office:office#Author

2.375 PidNameAutomaticSpeechRecognitionData

Canonical name: PidNameAutomaticSpeechRecognitionData

Description: Contains an unprotected voice message.

Copyright © 2025 Microsoft Corporation

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: AsrData

Data type: PtypBinary, 0x0102

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.13

2.376 PidNameBirthdayContactAttributionDisplayName

Canonical name: PidNameBirthdayContactAttributionDisplayName

Description: Indicates the name of the **contact** associated with the birthday event.

Property set: PSETID_Address{00062004-0000-0000-C000-000000000046}

Property name: BirthdayContactAttributionDisplayName

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCAL] section 2.2.1.52

2.377 PidNameBirthdayContactEntryId

Canonical name: PidNameBirthdayContactEntryId

Description: Indicate the **EntryID** of the **contact** associated with the birthday event.

Property set: PSETID_Address{00062004-0000-0000-C000-000000000046}

Property name: BirthdayContactEntryId

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCAL] section 2.2.1.53

2.378 PidNameBirthdayContactPersonGuid

Canonical name: PidNameBirthdayContactPersonGuid

Description: Indicates the person ID's **GUID** of the **contact** associated with the birthday event.

Property set: PSETID_Address{00062004-0000-0000-C000-000000000046}

Property name: BirthdayContactPersonGuid

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [MS-OXOCAL] section 2.2.1.54

Copyright © 2025 Microsoft Corporation

2.379 PidNameByteCount

Canonical name: PidNameByteCount

Description: Specifies the size, in bytes, of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ByteCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.22

Alternate names: urn:schemas-microsoft-com:office:office#Bytes

2.380 PidNameCalendarAttendeeRole

Canonical name: PidNameCalendarAttendeeRole

Description: Specifies the role of the attendee.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:attendeerole

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.7

Alternate names: urn:schemas:calendar:attendeerole

2.381 PidNameCalendarBusystatus

Canonical name: PidNameCalendarBusystatus

Description: Specifies whether the attendee is busy at the time of an appointment on their **calendar**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:busystatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.8

Alternate names: urn:schemas:calendar:busystatus

2.382 PidNameCalendarContact

Canonical name: PidNameCalendarContact

Description: Identifies the name of a **contact** who is an attendee of a **meeting**.

Copyright © 2025 Microsoft Corporation

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contact

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.9

Alternate names: urn:schemas:calendar:contact

2.383 PidNameCalendarContactUrl

Canonical name: PidNameCalendarContactUrl

Description: Identifies the **URL** where you can access **contact** information in **HTML** format.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contacturl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.10

Alternate names: urn:schemas:calendar:contacturl

2.384 PidNameCalendarCreated

Canonical name: PidNameCalendarCreated

Description: Identifies the date and time, in **UTC**, when the **organizer** created the appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:created

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.11

Alternate names: urn:schemas:calendar:created

2.385 PidNameCalendarDescriptionUrl

Canonical name: PidNameCalendarDescriptionUrl

Description: Specifies the **URL** of a resource that contains a description of an appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:descriptionurl

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.12

Alternate names: urn:schemas:calendar:descriptionurl

2.386 PidNameCalendarDuration

Canonical name: PidNameCalendarDuration

Description: Identifies the duration, in seconds, of an appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:duration

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.13

Alternate names: urn:schemas:calendar:duration

2.387 PidNameCalendarExceptionDate

Canonical name: PidNameCalendarExceptionDate

Description: Identifies a list of dates that are exceptions to a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exdate

Data type: PtypMultipleTime, 0x1040

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.14

Alternate names: urn:schemas:calendar:exdate

2.388 PidNameCalendarExceptionRule

Canonical name: PidNameCalendarExceptionRule

Description: Specifies an exception **rule** for a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exrule

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.15

Alternate names: urn:schemas:calendar:exrule

Copyright © 2025 Microsoft Corporation

2.389 PidNameCalendarGeoLatitude

Canonical name: PidNameCalendarGeoLatitude

Description: Specifies the geographical latitude of the location of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolatitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.16

Alternate names: urn:schemas:calendar:geolatitude

2.390 PidNameCalendarGeoLongitude

Canonical name: PidNameCalendarGeoLongitude

Description: Specifies the geographical longitude of the location of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolongitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.17

Alternate names: urn:schemas:calendar:geolongitude

2.391 PidNameCalendarInstanceType

Canonical name: PidNameCalendarInstanceType

Description: Specifies the type of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:instancetype

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.18

Alternate names: urn:schemas:calendar:instancetype

2.392 PidNameCalendarIsOrganizer

Canonical name: PidNameCalendarIsOrganizer

Description: Specifies whether an attendee is the **organizer** of an appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property name: urn:schemas:calendar:isorganizer

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.19

Alternate names: urn:schemas:calendar:isorganizer

2.393 PidNameCalendarLastModified

Canonical name: PidNameCalendarLastModified

Description: Specifies the date and time, in **UTC**, when an appointment was last modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:lastmodified

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.20

Alternate names: urn:schemas:calendar:lastmodified

2.394 PidNameCalendarLocationUrl

Canonical name: PidNameCalendarLocationUrl

Description: Specifies a **URL** with location information in **HTML** format.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.21

Alternate names: urn:schemas:calendar:locationurl

2.395 PidNameCalendarMeetingStatus

Canonical name: PidNameCalendarMeetingStatus

Description: Specifies the status of an appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:meetingstatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.22

Copyright © 2025 Microsoft Corporation

Alternate names: urn:schemas:calendar:meetingstatus

2.396 PidNameCalendarMethod

Canonical name: PidNameCalendarMethod

Description: Specifies the **iCalendar** method that is associated with an **Appointment object**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:method

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.23

Alternate names: urn:schemas:calendar:method

2.397 PidNameCalendarProductId

Canonical name: PidNameCalendarProductId

Description: Identifies the product that created the iCalendar-formatted **stream**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:prodid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.24

Alternate names: urn:schemas:calendar:prodid

2.398 PidNameCalendarRecurrenceIdRange

Canonical name: PidNameCalendarRecurrenceIdRange

Description: Specifies which instances of a recurring appointment are being referred to.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:recurrenceidrange

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.25

Alternate names: urn:schemas:calendar:recurrenceidrange

2.399 PidNameCalendarReminderOffset

Canonical name: PidNameCalendarReminderOffset

Copyright © 2025 Microsoft Corporation

Description: Identifies the number of seconds before an appointment starts that a **reminder** is to be displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:reminderoffset

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.26

Alternate names: urn:schemas:calendar:reminderoffset

2.400 PidNameCalendarResources

Canonical name: PidNameCalendarResources

Description: Identifies a list of resources, such as rooms and video equipment, that are available for an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:resources

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.27

Alternate names: urn:schemas:calendar:resources

2.401 PidNameCalendarRsvp

Canonical name: PidNameCalendarRsvp

Description: Specifies whether the **organizer** of an appointment or **meeting** requested a response.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rsvp

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.28

Alternate names: urn:schemas:calendar:rsvp

2.402 PidNameCalendarSequence

Canonical name: PidNameCalendarSequence

Description: Specifies the sequence number of a version of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:sequence

Copyright © 2025 Microsoft Corporation

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.29

Alternate names: urn:schemas:calendar:sequence

2.403 PidNameCalendarTimeZone

Canonical name: PidNameCalendarTimeZone

Description: Specifies the time zone of an appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezone

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.30

Alternate names: urn:schemas:calendar:timezone

2.404 PidNameCalendarTimeZoneId

Canonical name: PidNameCalendarTimeZoneId

Description: Specifies the time zone identifier of an appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezoneid

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.31

Alternate names: urn:schemas:calendar:timezoneid

2.405 PidNameCalendarTransparent

Canonical name: PidNameCalendarTransparent

Description: Specifies whether an appointment or **meeting** is visible to busy time searches.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:transparent

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.32

Alternate names: urn:schemas:calendar:transparent

Copyright © 2025 Microsoft Corporation

2.406 PidNameCalendarUid

Canonical name: PidNameCalendarUid

Description: Specifies the unique identifier of an appointment or **meeting**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:uid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.33

Alternate names: urn:schemas:calendar:uid

2.407 PidNameCalendarVersion

Canonical name: PidNameCalendarVersion

Description: Identifies the version of the iCalendar specification, as specified in [MS-OXCICAL] section 2.1.3.1.1.3, that is required to correctly interpret an iCalendar object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:version

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.34

Alternate names: urn:schemas:calendar:version

2.408 PidNameCategory

Canonical name: PidNameCategory

Description: Specifies the category of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Category

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.18

Alternate names: urn:schemas-microsoft-com:office:office#Category

2.409 PidNameCharacterCount

Canonical name: PidNameCharacterCount

Description: Specifies the character count of the file attached to the Document object.

Copyright © 2025 Microsoft Corporation

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: CharCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.16

Alternate names: urn:schemas-microsoft-com:office:office#Characters

2.410 PidNameComments

Canonical name: PidNameComments

Description: Specifies the comments of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Comments

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.5

Alternate names: urn:schemas-microsoft-com:office:office#Comments

2.411 PidNameCompany

Canonical name: PidNameCompany

Description: Specifies the company for which the file was created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Company

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.21

Alternate names: urn:schemas-microsoft-com:office:office#Company

2.412 PidNameContentBase

Canonical name: PidNameContentBase

Description: Specifies the value of the **MIME** Content-Base header, which defines the base **URI** for resolving relative URLs contained within the **message body**.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Base

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.41

Consuming reference: [MS-OXCMAIL]

Alternate names: BodyContentBase

2.413 PidNameContentClass

Canonical name: PidNameContentClass

Description: Contains a string that identifies the type of content of a **Message object**.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Class

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.48

Consuming references: [MS-OXBBODY], [MS-OXCMAIL], [MS-OXORMMS], [MS-OXOSMMS], [MS-OXOUM], [MS-OXSHARE], [MS-XWDCAL]

Alternate names: DAV:contentclass, urn:schemas:mailheader:content-class

2.414 PidNameContentType

Canonical name: PidNameContentType

Description: Specifies the type of the **body part** content.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Type

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.50

Consuming reference: [MS-OXCMAIL]

Alternate names: urn:schemas:mailheader:content-type

2.415 PidNameCreateDateTimeReadOnly

Canonical name: PidNameCreateDateTimeReadOnly

Description: Specifies the time, in **UTC**, that the file was first created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: CreateDtmRo

Data type: PtypTime, 0x0040

Copyright © 2025 Microsoft Corporation

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.12

Alternate names: urn:schemas-microsoft-com:office:office#Created

2.416 PidNameCrossReference

Canonical name: PidNameCrossReference

Description: Contains the name of the host (with domains omitted) and a white-space-separated list of colon-separated pairs of newsgroup names and message numbers.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Xref

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXCMAIL] section 2.5.3

Alternate names: urn:schemas:mailheader:xref

2.417 PidNameDavId

Canonical name: PidNameDavId

Description: Specifies a unique ID for the **calendar** item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:id

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.1.2

Alternate names: DAV:id

2.418 PidNameDavIsCollection

Canonical name: PidNameDavIsCollection

Description: Indicates whether a **Calendar object** is a collection.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:iscollection

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.1.3

Alternate names: DAV:iscollection

Copyright © 2025 Microsoft Corporation

2.419 PidNameDavIsStructuredDocument

Canonical name: PidNameDavIsStructuredDocument

Description: Indicates whether a **Calendar object** is a structured document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:isstructureddocument

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.1.4

Alternate names: DAV:isstructureddocument

2.420 PidNameDavParentName

Canonical name: PidNameDavParentName

Description: Specifies the name of the **Folder object** that contains the **Calendar object**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:parentname

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.1.5

Alternate names: DAV:parentname

2.421 PidNameDavUid

Canonical name: PidNameDavUid

Description: Specifies the unique identifier for an item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:uid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.1.6

Alternate names: DAV:uid

2.422 PidNameDocumentParts

Canonical name: PidNameDocumentParts

Description: Specifies the title of each part of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property name: DocParts

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.29

Alternate names: urn:schemas-microsoft-com:office:office#PartTitles

2.423 PidNameEditTime

Canonical name: PidNameEditTime

Description: Specifies the time that the file was last edited.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: EditTime

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.10

Alternate names: urn:schemas-microsoft-com:office:office#TotalTime

2.424 PidNameExchangeIntendedBusyStatus

Canonical name: PidNameExchangeIntendedBusyStatus

Description: Specifies the intended **free/busy status** of a **meeting** in a **Meeting request**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/intendedbusystatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.8.1

Alternate names: http://schemas.microsoft.com/exchange/intendedbusystatus

2.425 PidNameExchangeJunkEmailMoveStamp

Canonical name: PidNameExchangeJunkEmailMoveStamp

Description: Indicates that the message is not to be processed by a **spam filter**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/junkemailmovestamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [MS-OXCSPAM] section 2.2.1.2

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-OXORSS]

Alternate names: http://schemas.microsoft.com/exchange/junkemailmovestamp

2.426 PidNameExchangeModifyExceptionStructure

Canonical name: PidNameExchangeModifyExceptionStructure

Description: Specifies a structure that modifies an exception to the recurrence.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/modifyexceptionstruct

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.8.2

Alternate names: http://schemas.microsoft.com/exchange/modifyexceptionstruct

2.427 PidNameExchangeNoModifyExceptions

Canonical name: PidNameExchangeNoModifyExceptions

Description: Indicates whether exceptions to a recurring appointment can be modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/nomodifyexceptions

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.8.3

Alternate names: http://schemas.microsoft.com/exchange/nomodifyexceptions

2.428 PidNameExchangePatternEnd

Canonical name: PidNameExchangePatternEnd

Description: Identifies the maximum time when an instance of a recurring appointment ends.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/patternend

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.8.4

Alternate names: http://schemas.microsoft.com/exchange/patternend

Copyright © 2025 Microsoft Corporation

2.429 PidNameExchangePatternStart

Canonical name: PidNameExchangePatternStart

Description: Identifies the absolute minimum time when an instance of a recurring appointment starts.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/patternstart

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.8.5

Alternate names: http://schemas.microsoft.com/exchange/patternstart

2.430 PidNameExchangeReminderInterval

Canonical name: PidNameExchangeReminderInterval

Description: Identifies the time, in seconds, between **reminders**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/reminderinterval

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.8.6

Consuming reference: [MS-XWDCAL]

Alternate names: http://schemas.microsoft.com/exchange/reminderinterval

2.431 PidNameExchDatabaseSchema

Canonical name: PidNameExchDatabaseSchema

Description: Specifies an array of URLs that identifies other folders within the same **message store** that contain schema definition items.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:baseschema

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.5.1

Alternate names: urn:schemas-microsoft-com:exch-data:baseschema

2.432 PidNameExchDataExpectedContentClass

Canonical name: PidNameExchDataExpectedContentClass

Copyright © 2025 Microsoft Corporation

Description: Specifies an array of names that indicates the expected content **classes** of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:expected-content-class

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.5.2

Alternate names: urn:schemas-microsoft-com:exch-data:expected-content-class

2.433 PidNameExchDataSchemaCollectionReference

Canonical name: PidNameExchDataSchemaCollectionReference

Description: Specifies an array of names that indicates the expected content classes of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:schema-collection-ref

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.5.3

Alternate names: urn:schemas-microsoft-com:exch-data:schema-collection-ref

2.434 PidNameExtractedAddresses

Canonical name: PidNameExtractedAddresses

Description: Contains an **XML document** with a single **AddressSet** element.

Property set: PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Property name: XmlExtractedAddresses

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [MS-OXCEXT] section 2.2.2.1

Alternate names: dispidXmlExtractedAddresses

2.435 PidNameExtractedContacts

Canonical name: PidNameExtractedContacts

Description: Contains an **XML document** with a single **ContactSet** element.

Property set: PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Property name: XmlExtractedContacts

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [MS-OXCEXT] section 2.2.2.2

Alternate names: dispidXmlExtractedContacts

2.436 PidNameExtractedEmails

Canonical name: PidNameExtractedEmails

Description: Contains an **XML document** with a single **EmailSet** element.

Property set: PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Property name: XmlExtractedEmails

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [MS-OXCEXT] section 2.2.2.3

Alternate names: dispidXmlExtractedEmails

2.437 PidNameExtractedMeetings

Canonical name: PidNameExtractedMeetings

Description: Contains an **XML document** with a single **MeetingSet** element.

Property set: PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Property name: XmlExtractedMeetings

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [MS-OXCEXT] section 2.2.2.4

Alternate names: dispidXmlExtractedMeetings

2.438 PidNameExtractedPhones

Canonical name: PidNameExtractedPhones

Description: Contains an **XML document** with a single **PhoneSet** element.

Property set: PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Property name: XmlExtractedPhones

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [MS-OXCEXT] section 2.2.2.5

Alternate names: dispidXmlExtractedPhones

Copyright © 2025 Microsoft Corporation

2.439 PidNameExtractedTasks

Canonical name: PidNameExtractedTasks

Description: Contains an **XML document** with a single **TaskSet** element.

Property set: PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Property name: XmlExtractedTasks

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [MS-OXCEXT] section 2.2.2.6

Alternate names: dispidXmlExtractedTasks

2.440 PidNameExtractedUrls

Canonical name: PidNameExtractedUrls

Description: Contains an **XML document** with a single **UrlSet** element.

Property set: PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

Property name: XmlExtractedUrls

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [MS-OXCEXT] section 2.2.2.7

Alternate names: dispidXmlExtractedUrls

2.441 PidNameFrom

Canonical name: PidNameFrom

Description: Specifies the **SMTP** email **alias** of the **organizer** of an appointment or **meeting**.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: From

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-XWDCAL] section 2.2.2.35

Alternate names: urn:schemas:calendar:organizer

2.442 PidNameHeadingPairs

Canonical name: PidNameHeadingPairs

Description: Specifies which group of headings are indented in the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property name: HeadingPairs

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.30

Alternate names: urn:schemas-microsoft-com:office:office#HeadingPairs

2.443 PidNameHiddenCount

Canonical name: PidNameHiddenCount

Description: Specifies the hidden value of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: HiddenCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.27

Alternate names: urn:schemas-microsoft-com:office:office#HiddenSlides

2.444 PidNameHttpmailCalendar

Canonical name: PidNameHttpmailCalendar

Description: Specifies the **URL** for the **Calendar folder** for a particular user.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:calendar

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.3.1

Alternate names: urn:schemas:httpmail:calendar

2.445 PidNameHttpmailHtmlDescription

Canonical name: PidNameHttpmailHtmlDescription

Description: Specifies the **HTML** content of the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:htmldescription

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.3.2

Copyright © 2025 Microsoft Corporation

Alternate names: urn:schemas:httpmail:htmldescription

2.446 PidNameHttpmailSendMessage

Canonical name: PidNameHttpmailSendMessage

Description: Specifies the email submission **URI** to which outgoing email is submitted.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:sendmsg

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.3.3

Alternate names: urn:schemas:httpmail:sendmsg

2.447 PidNameICalendarRecurrenceDate

Canonical name: PidNameICalendarRecurrenceDate

Description: Identifies an array of instances of a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rdate

Data type: PtypMultipleTime, 0x1040

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.36

Alternate names: urn:schemas:calendar:rdate

2.448 PidNameICalendarRecurrenceRule

Canonical name: PidNameICalendarRecurrenceRule

Description: Specifies the **rule** for the pattern that defines a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rrule

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [MS-XWDCAL] section 2.2.2.37

Alternate names: urn:schemas:calendar:rrule

2.449 PidNameInternetSubject

Canonical name: PidNameInternetSubject

Copyright © 2025 Microsoft Corporation

Description: Specifies the subject of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-XWDCAL] section 2.2.4.1

Alternate names: urn:schemas:mailheader:subject

2.450 PidNameIsBirthdayContactWritable

Canonical name: PidNameIsBirthdayContactWritable

Description: Indicates whether the **contact** associated with the birthday event is writable.

Property set: PSETID_Address{00062004-0000-0000-C000-000000000046}

Property name: IsBirthdayContactWritable

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [MS-OXOCAL] section 2.2.1.55

2.451 PidNameKeywords

Canonical name: PidNameKeywords

Description: Contains keywords or categories for the **Message object**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Keywords

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.17

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOCAL], [MS-OXOCFG], [MS-OXODOC], [MS-OXONOTE],[MS-XWDCAL]

Alternate names: urn:schemas-microsoft-com:office:office#Keywords, http://schemas.microsoft.com/exchange/keywords-utf8

2.452 PidNameLastAuthor

Canonical name: PidNameLastAuthor

Description: Specifies the most recent author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastAuthor

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.7

Alternate names: urn:schemas-microsoft-com:office:office#LastAuthor

2.453 PidNameLastPrinted

Canonical name: PidNameLastPrinted

Description: Specifies the time, in **UTC**, that the file was last printed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastPrinted

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.11

Alternate names: urn:schemas-microsoft-com:office:office#LastPrinted

2.454 PidNameLastSaveDateTime

Canonical name: PidNameLastSaveDateTime

Description: Specifies the time, in **UTC**, that the file was last saved.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastSaveDtm

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.13

Alternate names: urn:schemas-microsoft-com:office:office#LastSaved

2.455 PidNameLineCount

Canonical name: PidNameLineCount

Description: Specifies the number of lines in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LineCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.23

Alternate names: urn:schemas-microsoft-com:office:office#Lines

Copyright © 2025 Microsoft Corporation

2.456 PidNameLinksDirty

Canonical name: PidNameLinksDirty

Description: Indicates whether the links in the document are up-to-date.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LinksDirty

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.31

Alternate names: urn:schemas-microsoft-com:office:office#LinksUpToDate

2.457 PidNameLocationUrl

Canonical name: PidNameLocationUrl

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Calendar

Defining reference:

Consuming reference: [MS-OXCMAIL]

Alternate names: urn:schemas:calendar:locationurl, LocationUrl

2.458 PidNameManager

Canonical name: PidNameManager

Description: Specifies the manager of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Manager

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.20

Alternate names: urn:schemas-microsoft-com:office:office#Manager

2.459 PidNameMeetingDoNotForward

Canonical name: PidNameMeetingDoNotForward

Description: Specifies whether to allow the meeting to be forwarded.

Copyright © 2025 Microsoft Corporation

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DoNotForward

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [MS-OXOCAL] section 2.2.1.51

2.460 PidNameMSIPLabels

Canonical name: PidNameMSIPLabels

Description: Contains the string that specifies the **CLP** label information.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: msip_labels

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.56

2.461 PidNameMultimediaClipCount

Canonical name: PidNameMultimediaClipCount

Description: Specifies the number of multimedia clips in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: MMClipCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.28

Alternate names: urn:schemas-microsoft-com:office:office#MultimediaClips

2.462 PidNameNoteCount

Canonical name: PidNameNoteCount

Description: Specifies the number of notes in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: NoteCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.26

Alternate names: urn:schemas-microsoft-com:office:office#Notes

Copyright © 2025 Microsoft Corporation

2.463 PidNameOMSAccountGuid

Canonical name: PidNameOMSAccountGuid

Description: Contains the **GUID** of the **SMS** account used to deliver the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSAccountGuid

Data type: PtypString, 0x001F

Area: SMS

Defining reference: [MS-OXOSMMS] section 2.2.1.1

2.464 PidNameOMSMobileModel

Canonical name: PidNameOMSMobileModel

Description: Indicates the model of the mobile device used to send the **SMS** or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSMobileModel

Data type: PtypString, 0x001F

Area: SMS

Defining reference: [MS-OXOSMMS] section 2.2.1.6

2.465 PidNameOMSScheduleTime

Canonical name: PidNameOMSScheduleTime

Description: Contains the time, in **UTC**, at which the client requested that the service provider send the **SMS** or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSScheduleTime

Data type: PtypTime, 0x0040

Area: SMS

Defining reference: [MS-OXOSMMS] section 2.2.1.2

2.466 PidNameOMSServiceType

Canonical name: PidNameOMSServiceType

Description: Contains the type of service used to send an **SMS** or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSServiceType

Data type: PtypInteger32, 0x0003

Copyright © 2025 Microsoft Corporation

Area: SMS

Defining reference: [MS-OXOSMMS] section 2.2.1.3

2.467 PidNameOMSSourceType

Canonical name: PidNameOMSSourceType

Description: Contains the source of an **SMS** or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSSourceType

Data type: PtypInteger32, 0x0003

Area: SMS

Defining reference: [MS-OXOSMMS] section 2.2.1.4

2.468 PidNamePageCount

Canonical name: PidNamePageCount

Description: Specifies the page count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PageCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.14

Alternate names: urn:schemas-microsoft-com:office:office#Pages

2.469 PidNameParagraphCount

Canonical name: PidNameParagraphCount

Description: Specifies the number of paragraphs in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ParCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.24

Alternate names: urn:schemas-microsoft-com:office:office#Paragraphs

2.470 PidNamePhishingStamp

Canonical name: PidNamePhishingStamp

Copyright © 2025 Microsoft Corporation

Description: Indicates whether a message is likely to be **phishing**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/outlook/phishingstamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [MS-OXPHISH] section 2.2.1.1

2.471 PidNamePresentationFormat

Canonical name: PidNamePresentationFormat

Description: Specifies the presentation format of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PresFormat

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.19

Alternate names: urn:schemas-microsoft-com:office:office#PresentationFormat

2.472 PidNameQuarantineOriginalSender

Canonical name: PidNameQuarantineOriginalSender

Description: Specifies the original sender of a message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: quarantine-original-sender

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXCMAIL] section 2.5.4

2.473 PidNameRevisionNumber

Canonical name: PidNameRevisionNumber

Description: Specifies the revision number of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: RevNumber

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.8

Copyright © 2025 Microsoft Corporation

Alternate names: urn:schemas-microsoft-com:office:office#Revision

2.474 PidNameRightsManagementLicense

Canonical name: PidNameRightsManagementLicense

Description: Specifies the value used to cache the **Use License** for the **rights-managed email message**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DRMLicense

Data type: PtypMultipleBinary, 0x1102

Area: Secure Messaging Properties

Defining reference: [MS-OXORMMS] section 2.2.1.1

2.475 PidNameScale

Canonical name: PidNameScale

Description: Indicates whether the image is to be scaled or cropped.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Scale

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.32

Alternate names: urn:schemas-microsoft-com:office:office#ScaleCrop

2.476 PidNameSecurity

Canonical name: PidNameSecurity

Description: Specifies the security level of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Security

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.17

Alternate names: urn:schemas-microsoft-com:office:office#Security

2.477 PidNameSlideCount

Canonical name: PidNameSlideCount

Description: Specifies the number of slides in the file attached to the Document object.

Copyright © 2025 Microsoft Corporation

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: SlideCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.25

Alternate names: urn:schemas-microsoft-com:office:office#Slides

2.478 PidNameSubject

Canonical name: PidNameSubject

Description: Specifies the subject of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.2

Consuming reference: [MS-OXOCAL]

Alternate names: urn:schemas-microsoft-com:office:office#Subject

2.479 PidNameTemplate

Canonical name: PidNameTemplate

Description: Specifies the template of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Template

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.6

Alternate names: urn:schemas-microsoft-com:office:office#Template

2.480 PidNameThumbnail

Canonical name: PidNameThumbnail

Description: Specifies the data representing the thumbnail image of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Thumbnail

Data type: PtypBinary, 0x0102

Copyright © 2025 Microsoft Corporation

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.33

Alternate names: urn:schemas-microsoft-com:office:office#ThumbNail

2.481 PidNameTitle

Canonical name: PidNameTitle

Description: Specifies the title of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Title

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.1

Alternate names: urn:schemas-microsoft-com:office:office#Title

2.482 PidNameWordCount

Canonical name: PidNameWordCount

Description: Specifies the word count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: WordCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXODOC] section 2.2.1.15

Alternate names: urn:schemas-microsoft-com:office:office#Words

2.483 PidNameXCallId

Canonical name: PidNameXCallId

Description: Contains a unique identifier associated with the phone call.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallID

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.12

Consuming reference: [MS-OXCMAIL]

Copyright © 2025 Microsoft Corporation

2.484 PidNameXFaxNumberOfPages

Canonical name: PidNameXFaxNumberOfPages

Description: Specifies how many discrete pages are contained within an attachment representing a facsimile message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-FaxNumberOfPages

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.8

Consuming reference: [MS-OXCMAIL]

2.485 PidNameXRequireProtectedPlayOnPhone

Canonical name: PidNameXRequireProtectedPlayOnPhone

Description: Indicates that the client only renders the message on a phone.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-RequireProtectedPlayOnPhone

Data type: PtypBoolean, 0x000B

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.14

2.486 PidNameXSenderTelephoneNumber

Canonical name: PidNameXSenderTelephoneNumber

Description: Contains the telephone number of the caller associated with a voice mail message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallingTelephoneNumber

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.2

Consuming reference: [MS-OXCMAIL]

2.487 PidNameXSharingBrowseUrl

Canonical name: PidNameXSharingBrowseUrl

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Copyright © 2025 Microsoft Corporation

Property name: X-Sharing-Browse-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

2.488 PidNameXSharingCapabilities

Canonical name: PidNameXSharingCapabilities

Description: Contains a string representation of the value of the **PidLidSharingCapabilities** property (section 2.237).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Capabilities

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.2

2.489 PidNameXSharingConfigUrl

Canonical name: PidNameXSharingConfigUrl

Description: Contains the same value as the **PidLidSharingConfigurationUrl** property (section 2.238).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Config-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.4

2.490 PidNameXSharingExendedCaps

Canonical name: PidNameXSharingExendedCaps

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Exended-Caps

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

Copyright © 2025 Microsoft Corporation

2.491 PidNameXSharingFlavor

Canonical name: PidNameXSharingFlavor

Description: Contains a hexadecimal string representation of the value of the **PidLidSharingFlavor** property (section 2.245).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Flavor

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.6

2.492 PidNameXSharingInstanceGuid

Canonical name: PidNameXSharingInstanceGuid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Instance-Guid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

2.493 PidNameXSharingLocalType

Canonical name: PidNameXSharingLocalType

Description: Contains the same value as the **PidLidSharingLocalType** property (section 2.259).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Local-Type

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.11

2.494 PidNameXSharingProviderGuid

Canonical name: PidNameXSharingProviderGuid

Description: Contains the hexadecimal string representation of the value of the **PidLidSharingProviderGuid** property (section 2.266).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Guid

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.13

2.495 PidNameXSharingProviderName

Canonical name: PidNameXSharingProviderName

Description: Contains the same value as the **PidLidSharingProviderName** property (section 2.267).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Name

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.15

2.496 PidNameXSharingProviderUrl

Canonical name: PidNameXSharingProviderUrl

Description: Contains the same value as the **PidLidSharingProviderUrl** property (section 2.268).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.2.17

2.497 PidNameXSharingRemoteName

Canonical name: PidNameXSharingRemoteName

Description: Contains the same value as the **PidLidSharingRemoteName** property (section 2.277).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Name

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.2

2.498 PidNameXSharingRemotePath

Canonical name: PidNameXSharingRemotePath

Copyright © 2025 Microsoft Corporation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Path

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.6

2.499 PidNameXSharingRemoteStoreUid

Canonical name: PidNameXSharingRemoteStoreUid

Description: Contains the same value as the **PidLidSharingRemoteStoreUid** property (section 2.282).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Store-Uid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.4

2.500 PidNameXSharingRemoteType

Canonical name: PidNameXSharingRemoteType

Description: Contains the same value as the **PidLidSharingRemoteType** property (section 2.281).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Type

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.6

2.501 PidNameXSharingRemoteUid

Canonical name: PidNameXSharingRemoteUid

Description: Contains the same value as the **PidLidSharingRemoteUid** property (section 2.282).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Uid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [MS-OXSHARE] section 2.2.3.8

Copyright © 2025 Microsoft Corporation

2.502 PidNameXVoiceMessageAttachmentOrder

Canonical name: PidNameXVoiceMessageAttachmentOrder

Description: Contains the list of names for the audio file attachments that are to be played as part of a message, in reverse order.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-AttachmentOrder

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.10

Consuming reference: [MS-OXCMAIL]

2.503 PidNameXVoiceMessageDuration

Canonical name: PidNameXVoiceMessageDuration

Description: Specifies the length of the attached audio message, in seconds.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageDuration

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.4

Consuming reference: [MS-OXCMAIL]

2.504 PidNameXVoiceMessageSenderName

Canonical name: PidNameXVoiceMessageSenderName

Description: Contains the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageSenderName

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.6

Consuming reference: [MS-OXCMAIL]

2.505 PidTagAccess

Canonical name: PidTagAccess

Description: Indicates the operations available to the client for the object.

Copyright © 2025 Microsoft Corporation

Property ID: 0x0FF4

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [MS-OXCPRPT] section 2.2.1.1

Consuming references: [MS-OXCFXICS], [MS-OXCFOLD], [MS-OXCICAL], [MS-OXCMSG], [MS-OXCPRPT], [MS-OXOJRNL]

Alternate names: PR_ACCESS, ptagAccess

2.506 PidTagAccessControlListData

Canonical name: PidTagAccessControlListData

Description: Contains a **permissions** list for a folder.

Property ID: 0x3FE0

Data type: PtypBinary, 0x0102

Area: Access Control Properties

Defining reference: [MS-OXCPERM] section 2.2.3

Consuming references: [MS-OXCFOLD]

Alternate names: PR_ACL_DATA, ptagACLData

2.507 PidTagAccessLevel

Canonical name: PidTagAccessLevel

Description: Indicates the client's access level to the object.

Property ID: 0x0FF7

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [MS-OXCPRPT] section 2.2.1.2

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMSG]

Alternate names: PR_ACCESS_LEVEL, ptagAccessLevel

2.508 PidTagAccount

Canonical name: PidTagAccount

Description: Contains the **alias** of an **Address Book object**, which is an alternative name by which the object can be identified.

Property ID: 0x3A00

Data type: PtypString, 0x001F

Area: Address Book

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCNTC] section 2.2.1.10.11

Consuming references: [MS-OXCFXICS], [MS-OXOAB], [MS-OXOABK], [MS-OXOMSG]

Alternate names: PR_ACCOUNT, PR_ACCOUNT_A, PR_ACCOUNT_W, urn:schemas:contacts:account

2.509 PidTagAdditionalRenEntryIds

Canonical name: PidTagAdditionalRenEntryIds

Description: Contains the indexed entry IDs for several **special folders** related to conflicts, sync issues, local failures, server failures, junk email and **spam**.

Property ID: 0x36D8

Data type: PtypMultipleBinary, 0x1102

Area: Outlook Application

Defining reference: [MS-OXOSFLD] section 2.2.4

Consuming references: [MS-OXCSPAM], [MS-OXPHISH]

Alternate names: PR_ADDITIONAL_REN_ENTRYIDS, ptagAdditionalRenEntryIds

2.510 PidTagAdditionalRenEntryIdsEx

Canonical name: PidTagAdditionalRenEntryIdsEx

Description: Contains an array of blocks that specify the **EntryIDs** of several special folders.

Property ID: 0x36D9

Data type: PtypBinary, 0x0102

Area: Outlook Application

Defining reference: [MS-OXOSFLD] section 2.2.5

Alternate names: PR_ADDITIONAL_REN_ENTRYIDS_EX, ptagAdditionalRenEntryIdsEx

2.511 PidTagAddressBookAuthorizedSenders

Canonical name: PidTagAddressBookAuthorizedSenders

Description: Indicates whether delivery restrictions exist for a **recipient**.

Property ID: 0x8CD8

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.42

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_AUTH_ORIG

Copyright © 2025 Microsoft Corporation

2.512 PidTagAddressBookContainerId

Canonical name: PidTagAddressBookContainerId

Description: Contains the ID of a container on an **NSPI** server.

Property ID: 0xFFFD

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.2.3

Consuming references: [MS-OXNSPI]

Alternate names: PR_EMS_AB_CONTAINERID

2.513 PidTagAddressBookDeliveryContentLength

Canonical name: PidTagAddressBookDeliveryContentLength

Description: Specifies the maximum size, in bytes, of a message that a **recipient** can receive.

Property ID: 0x806A

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.27

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_DELIV_CONT_LENGTH

2.514 PidTagAddressBookDisplayNamePrintable

Canonical name: PidTagAddressBookDisplayNamePrintable

Description: Contains the printable string version of the **display name**.

Property ID: 0x39FF

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.7

Consuming reference: [MS-OXCMSG], [MS-OXOAB], [MS-OXOMSG]

Alternate names: PR_EMS_AB_DISPLAY_NAME_PRINTABLE, PR_EMS_AB_DISPLAY_NAME_PRINTABLE_A, PR_EMS_AB_DISPLAY_NAME_PRINTABLE_W, PR_7BIT_DISPLAY_NAME, PR_7BIT_DISPLAY_NAME_A, PR_7BIT_DISPLAY_NAME_W, ptagSimpleDisplayName

2.515 PidTagAddressBookDisplayTypeExtended

Canonical name: PidTagAddressBookDisplayTypeExtended

Copyright © 2025 Microsoft Corporation

Description: Contains a value that indicates how to display an **Address Book object** in a table or as a **recipient** on a message.

Property ID: 0x8C93

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.35

Alternate names: PR_EMS_AB_DISPLAY_TYPE_EX

2.516 PidTagAddressBookDistributionListExternalMemberCount

Canonical name: PidTagAddressBookDistributionListExternalMemberCount

Description: Contains the number of external **recipients** in the **distribution list**.

Property ID: 0x8CE3

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference:[MS-OXOABK] section 2.2.3.30

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_DL_EXTERNAL_MEMBER_COUNT

2.517 PidTagAddressBookDistributionListMemberCount

Canonical name: PidTagAddressBookDistributionListMemberCount

Description: Contains the total number of **recipients** in the **distribution list**.

Property ID: 0x8CE2

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.29

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_DL_TOTAL_MEMBER_COUNT

2.518 PidTagAddressBookDistributionListMemberSubmitAccepted

Canonical name: PidTagAddressBookDistributionListMemberSubmitAccepted

Description: Indicates that delivery restrictions exist for a **recipient**.

Property ID: 0x8073

Data type: PtypObject, 0x000D

Area: Address Book

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOABK] section 2.2.4.44

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL_O

2.519 PidTagAddressBookDistributionListMemberSubmitRejected

Canonical name: PidTagAddressBookDistributionListMemberSubmitRejected

Description: Indicates that delivery restrictions exist for a **recipient**.

Property ID: 0x8CDA

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.45

Consuming references: [MS-OXOAB]

Alternate names: PR_EMS_AB_DL_MEM_SUBMIT_PERMS

2.520 PidTagAddressBookDistributionListRejectMessagesFromDLMembers

Canonical name: PidTagAddressBookDistributionListRejectMessagesFromDLMembers

Description: Indicates that delivery restrictions exist for a **recipient**.

Property ID: 0x8CDB

Data type: PtypObject, 0x000D

Area: Address book

Defining reference: [MS-OXOAB] section 2.9.2.2

Alternate names: PR_EMS_AB_DL_MEM_REJECT_PERMS

2.521 PidTagAddressBookEntryId

Canonical name: PidTagAddressBookEntryId

Description: Contains the name-service **EntryID** of a directory object that refers to a **public folder**.

Property ID: 0x663B

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.4

Alternate names: PR_ADDRESS_BOOK_ENTRYID, ptagAddressBookEntryId

2.522 PidTagAddressBookExtensionAttribute1

Canonical name: PidTagAddressBookExtensionAttribute1

Copyright © 2025 Microsoft Corporation

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x802D

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_1, PR_EMS_AB_EXTENSION_ATTRIBUTE_1_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_1_W

2.523 PidTagAddressBookExtensionAttribute10

Canonical name: PidTagAddressBookExtensionAttribute10

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8036

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_10, PR_EMS_AB_EXTENSION_ATTRIBUTE_10_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_10_W

2.524 PidTagAddressBookExtensionAttribute11

Canonical name: PidTagAddressBookExtensionAttribute11

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8C57

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_11, PR_EMS_AB_EXTENSION_ATTRIBUTE_11_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_11_W

2.525 PidTagAddressBookExtensionAttribute12

Canonical name: PidTagAddressBookExtensionAttribute12

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8C58

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_12, PR_EMS_AB_EXTENSION_ATTRIBUTE_12_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_12_W

2.526 PidTagAddressBookExtensionAttribute13

Canonical name: PidTagAddressBookExtensionAttribute13

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8C59

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_13, PR_EMS_AB_EXTENSION_ATTRIBUTE_13_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_13_W

2.527 PidTagAddressBookExtensionAttribute14

Canonical name: PidTagAddressBookExtensionAttribute14

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8C60

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_14, PR_EMS_AB_EXTENSION_ATTRIBUTE_14_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_14_W

2.528 PidTagAddressBookExtensionAttribute15

Canonical name: PidTagAddressBookExtensionAttribute15

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8C61

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_15, PR_EMS_AB_EXTENSION_ATTRIBUTE_15_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_15_W

Copyright © 2025 Microsoft Corporation

2.529 PidTagAddressBookExtensionAttribute2

Canonical name: PidTagAddressBookExtensionAttribute2

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x802E

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_2, PR_EMS_AB_EXTENSION_ATTRIBUTE_2_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_2_W

2.530 PidTagAddressBookExtensionAttribute3

Canonical name: PidTagAddressBookExtensionAttribute3

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x802F

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_3, PR_EMS_AB_EXTENSION_ATTRIBUTE_3_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_3_W

2.531 PidTagAddressBookExtensionAttribute4

Canonical name: PidTagAddressBookExtensionAttribute4

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8030

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_4, PR_EMS_AB_EXTENSION_ATTRIBUTE_4_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_4_W

2.532 PidTagAddressBookExtensionAttribute5

Canonical name: PidTagAddressBookExtensionAttribute5

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Copyright © 2025 Microsoft Corporation

Property ID: 0x8031

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_5, PR_EMS_AB_EXTENSION_ATTRIBUTE_5_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_5_W

2.533 PidTagAddressBookExtensionAttribute6

Canonical name: PidTagAddressBookExtensionAttribute6

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8032

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_6, PR_EMS_AB_EXTENSION_ATTRIBUTE_6_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_6_W

2.534 PidTagAddressBookExtensionAttribute7

Canonical name: PidTagAddressBookExtensionAttribute7

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8033

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_7, PR_EMS_AB_EXTENSION_ATTRIBUTE_7_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_7_W

2.535 PidTagAddressBookExtensionAttribute8

Canonical name: PidTagAddressBookExtensionAttribute8

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8034

Data type: PtypString, 0x001F

Area: Address Book

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_8, PR_EMS_AB_EXTENSION_ATTRIBUTE_8_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_8_W

2.536 PidTagAddressBookExtensionAttribute9

Canonical name: PidTagAddressBookExtensionAttribute9

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x8035

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_9, PR_EMS_AB_EXTENSION_ATTRIBUTE_9_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_9_W

2.537 PidTagAddressBookFolderPathname

Canonical name: PidTagAddressBookFolderPathname

Description: This property is deprecated and is to be ignored.

Property ID: 0x8004

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.6.4

Alternate names: PR_EMS_AB_FOLDER_PATHNAME, PR_EMS_AB_FOLDER_PATHNAME_A, PR_EMS_AB_FOLDER_PATHNAME_W

2.538 PidTagAddressBookHierarchicalChildDepartments

Canonical name: PidTagAddressBookHierarchicalChildDepartments

Description: Contains the child departments in a hierarchy of departments.

Property ID: 0x8C9A

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.8.1

Alternate names: PR_EMS_AB_HAB_CHILD_DEPARTMENTS

2.539 PidTagAddressBookHierarchicalDepartmentMembers

Canonical name: PidTagAddressBookHierarchicalDepartmentMembers

Copyright © 2025 Microsoft Corporation

Description: Contains all of the **mail users** that belong to this department.

Property ID: 0x8C97

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.8.3

Alternate names: PR_EMS_AB_HAB_DEPARTMENT_MEMBERS

2.540 PidTagAddressBookHierarchicalIsHierarchicalGroup

Canonical name: PidTagAddressBookHierarchicalIsHierarchicalGroup

Description: Indicates whether the **distribution list** represents a **departmental group**.

Property ID: 0x8CDD

Data type: PtypBoolean, 0x000B

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.6.5

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_HAB_IS_HIERARCHICAL_GROUP, PR_EMS_AB_IS_ORGANIZATIONAL

2.541 PidTagAddressBookHierarchicalParentDepartment

Canonical name: PidTagAddressBookHierarchicalParentDepartment

Description: Contains all of the departments to which this department is a child.

Property ID: 0x8C99

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.8.2

Alternate names: PR_EMS_AB_HAB_PARENT_DEPARTMENT

2.542 PidTagAddressBookHierarchicalRootDepartment

Canonical name: PidTagAddressBookHierarchicalRootDepartment

Description: Contains the **distinguished name (DN)** of either the root **Department object** or the root **departmental group** in the department hierarchy for the organization.

Property ID: 0x8C98

Data type: PtypString8, 0x001E

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.7.2

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_HAB_ROOT_DEPARTMENT

2.543 PidTagAddressBookHierarchicalShowInDepartments

Canonical name: PidTagAddressBookHierarchicalShowInDepartments

Description: Lists all Department objects of which the **mail user** is a member.

Property ID: 0x8C94

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.5.6

Alternate names: PR_EMS_AB_HAB_SHOW_IN_DEPARTMENTS

2.544 PidTagAddressBookHomeMessageDatabase

Canonical name: PidTagAddressBookHomeMessageDatabase

Description: Contains the **DN** expressed in the **X500 DN** format. This property is returned from a **name service provider interface (NSPI)** server as a **PtypEmbeddedTable**. Otherwise, the data type is **PtypString8**.

Property ID: 0x8006

Data type: PtypString8, 0x001E**PtypEmbeddedTable,** 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.37

Consuming references: [MS-OXABREF], [MS-OXLDAP], [MS-OXOAB], [MS-OXODLGT]

Alternate names: PR_EMS_AB_HOME_MDB, PR_EMS_AB_HOME_MDB_A, PR_EMS_AB_HOME_MDB_W

2.545 PidTagAddressBookIsMaster

Canonical name: PidTagAddressBookIsMaster

Description: Contains a Boolean value of TRUE if it is possible to create **Address Book objects** in that container, and FALSE otherwise.

Property ID: 0xFFFB

Data type: PtypBoolean, 0x000B

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.2.4

Consuming reference: [MS-OXNSPI]

Alternate names: PR_EMS_AB_IS_MASTER

Copyright © 2025 Microsoft Corporation

2.546 PidTagAddressBookIsMemberOfDistributionList

Canonical name: PidTagAddressBookIsMemberOfDistributionList

Description: Lists all of the **distribution lists** for which the object is a member. This property is returned from an **NSPI** server as a **PtypEmbeddedTable**. Otherwise, the data type is **PtypString8**.

Property ID: 0x8008

Data type: PtypString8, 0x001E; **PtypEmbeddedTable**, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.5.3

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_IS_MEMBER_OF_DL, PR_EMS_AB_IS_MEMBER_OF_DL_A, PR_EMS_AB_IS_MEMBER_OF_DL_W

2.547 PidTagAddressBookManageDistributionList

Canonical name: PidTagAddressBookManageDistributionList

Description: Contains information for use in **display templates** for **distribution lists**.

Property ID: 0x6704

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.10.2

Consuming reference: [MS-OXOABKT]

Alternate names: PR_EMS_AB_MANAGE_DL

2.548 PidTagAddressBookManager

Canonical name: PidTagAddressBookManager

Description: Contains one row that references the **mail user's** manager.

Property ID: 0x8005

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.5.1

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_MANAGER, PR_EMS_AB_MANAGER_A, PR_EMS_AB_MANAGER_W

2.549 PidTagAddressBookManagerDistinguishedName

Canonical name: PidTagAddressBookManagerDistinguishedName

Description: Contains the **DN** of the **mail user's** manager.

Copyright © 2025 Microsoft Corporation

Property ID: 0x8005

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.9

Alternate names: PR_EMS_AB_MANAGER_T

2.550 PidTagAddressBookMember

Canonical name: PidTagAddressBookMember

Description: Contains the members of the **distribution list**.

Property ID: 0x8009

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.6.1

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_MEMBER, PR_EMS_AB_MEMBER_A, PR_EMS_AB_MEMBER_W

2.551 PidTagAddressBookMessageId

Canonical name: PidTagAddressBookMessageId

Description: Contains the Short-term Message ID (MID) ([MS-OXCDATA] section 2.2.1.2) of the first message in the local site's **offline address book public folder**.

Property ID: 0x674F

Data type: PtypInteger64, 0x0014

Area: ProviderDefinedNonTransmittable

Defining reference: [MS-OXCSTOR] section 2.2.2.2.2

Alternate names: ptagAddrbookMID

2.552 PidTagAddressBookModerationEnabled

Canonical name: PidTagAddressBookModerationEnabled

Description: Indicates whether moderation is enabled for the **mail user** or **distribution list**.

Property ID: 0x8CB5

Data type: PtypBoolean, 0x000B

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.28

Consuming reference: [MS-OXOAB]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_EMS_AB_ENABLE_MODERATION

2.553 PidTagAddressBookNetworkAddress

Canonical name: PidTagAddressBookNetworkAddress

Description: Contains a list of names by which a server is known to the various transports in use by the network.

Property ID: 0x8170

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.38

Alternate names: PR_EMS_AB_NETWORK_ADDRESS, PR_EMS_AB_NETWORK_ADDRESS_A, PR_EMS_AB_NETWORK_ADDRESS_W

2.554 PidTagAddressBookObjectDistinguishedName

Canonical name: PidTagAddressBookObjectDistinguishedName

Description: Contains the **DN** of the **Address Book object**.

Property ID: 0x803C

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.15

Consuming reference: [MS-OXNSPI]

Alternate names: PR_EMS_AB_OBJ_DIST_NAME, PR_EMS_AB_OBJ_DIST_NAME_A, PR_EMS_AB_OBJ_DIST_NAME_W

2.555 PidTagAddressBookObjectGuid

Canonical name: PidTagAddressBookObjectGuid

Description: Contains a **GUID** that identifies an **Address Book object**.

Property ID: 0x8C6D

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.25

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_OBJECT_GUID

2.556 PidTagAddressBookOrganizationalUnitRootDistinguishedName

Canonical name: PidTagAddressBookOrganizationalUnitRootDistinguishedName

Copyright © 2025 Microsoft Corporation

Description: Contains the **DN** of the Organization object of the **mail user's** organization.

Property ID: 0x8CA8

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.39

Alternate names: PR_EMS_AB_ORG_UNIT_ROOT_DN, msExchOURoot

2.557 PidTagAddressBookOwner

Canonical name: PidTagAddressBookOwner

Description: Contains one row that references the **distribution list**'s owner.

Property ID: 0x800C

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.6.2

Alternate names: PR_EMS_AB_OWNER_O

2.558 PidTagAddressBookOwnerBackLink

Canonical name: PidTagAddressBookOwnerBackLink

Description: Contains a list of the **distribution lists** owned by a **mail user**.

Property ID: 0x8024

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.5.4

Alternate names: PR_EMS_AB_OWNER_BL_O

2.559 PidTagAddressBookParentEntryId

Canonical name: PidTagAddressBookParentEntryId

Description: Contains the **EntryID** of the parent container in a hierarchy of **address book containers**.

Property ID: 0xFFFC

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.2.5

Consuming reference: [MS-OXNSPI]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_EMS_AB_PARENT_ENTRYID

2.560 PidTagAddressBookPhoneticCompanyName

Canonical name: PidTagAddressBookPhoneticCompanyName

Description: Contains the phonetic representation of the **PidTagCompanyName** property (section 2.640).

Property ID: 0x8C91

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.12

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_PHONETIC_COMPANY_NAME, PR_EMS_AB_PHONETIC_COMPANY_NAME_A, PR_EMS_AB_PHONETIC_COMPANY_NAME_W

2.561 PidTagAddressBookPhoneticDepartmentName

Canonical name: PidTagAddressBookPhoneticDepartmentName

Description: Contains the phonetic representation of the **PidTagDepartmentName** property (section 2.673).

Property ID: 0x8C90

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.13

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_PHONETIC_DEPARTMENT_NAME, PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_A, PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_W

2.562 PidTagAddressBookPhoneticDisplayName

Canonical name: PidTagAddressBookPhoneticDisplayName

Description: Contains the phonetic representation of the **PidTagDisplayName** property (section 2.677).

Property ID: 0x8C92

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.9

Consuming references: [MS-OXNSPI], [MS-OXOAB]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_EMS_AB_PHONETIC_DISPLAY_NAME, PR_EMS_AB_PHONETIC_DISPLAY_NAME_A, PR_EMS_AB_PHONETIC_DISPLAY_NAME_W

2.563 PidTagAddressBookPhoneticGivenName

Canonical name: PidTagAddressBookPhoneticGivenName

Description: Contains the phonetic representation of the **PidTagGivenName** property (section 2.715).

Property ID: 0x8C8E

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.10

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_PHONETIC_GIVEN_NAME, PR_EMS_AB_PHONETIC_GIVEN_NAME_A, PR_EMS_AB_PHONETIC_GIVEN_NAME_W

2.564 PidTagAddressBookPhoneticSurname

Canonical name: PidTagAddressBookPhoneticSurname

Description: Contains the phonetic representation of the **PidTagSurname** property (section 2.1038).

Property ID: 0x8C8F

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.11

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_PHONETIC_SURNAME, PR_EMS_AB_PHONETIC_SURNAME_A, PR_EMS_AB_PHONETIC_SURNAME_W

2.565 PidTagAddressBookProxyAddresses

Canonical name: PidTagAddressBookProxyAddresses

Description: Contains alternate email addresses for the **Address Book object**.

Property ID: 0x800F

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.23

Consuming references: [MS-OXLDAP], [MS-OXOAB], [MS-OXCMAIL], [MS-OXODLGT]

Alternate names: PR_EMS_AB_PROXY_ADDRESSES, PR_EMS_AB_PROXY_ADDRESSES_A, PR_EMS_AB_PROXY_ADDRESSES_W

Copyright © 2025 Microsoft Corporation

2.566 PidTagAddressBookPublicDelegates

Canonical name: PidTagAddressBookPublicDelegates

Description: Contains a list of **mail users** who are allowed to send email on behalf of the **mailbox** owner.

Property ID: 0x8015

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.5.5

Consuming reference: [MS-OXODLGT]

Alternate names: PR_EMS_AB_PUBLIC_DELEGATES, PR_EMS_AB_PUBLIC_DELEGATES_A, PR_EMS_AB_PUBLIC_DELEGATES_W

2.567 PidTagAddressBookReports

Canonical name: PidTagAddressBookReports

Description: Lists all of the **mail user**'s direct reports.

Property ID: 0x800E

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.5.2

Alternate names: PR_EMS_AB_REPORTS, PR_EMS_AB_REPORTS_A, PR_EMS_AB_REPORTS_W

2.568 PidTagAddressBookRoomCapacity

Canonical name: PidTagAddressBookRoomCapacity

Description: Contains the maximum occupancy of the room.

Property ID: 0x0807

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.9.1

Alternate names: PR_EMS_AB_ROOM_CAPACITY

2.569 PidTagAddressBookRoomContainers

Canonical name: PidTagAddressBookRoomContainers

Description: Contains a list of **DNs** that represent the **address book containers** that hold **Resource objects**, such as conference rooms and equipment.

Property ID: 0x8C96

Copyright © 2025 Microsoft Corporation

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.7.1

Alternate names: PR_EMS_AB_ROOM_CONTAINERS, PR_EMS_AB_ROOM_CONTAINERS_A, PR_EMS_AB_ROOM_CONTAINERS_W

2.570 PidTagAddressBookRoomDescription

Canonical name: PidTagAddressBookRoomDescription

Description: Contains a description of the **Resource object**.

Property ID: 0x0809

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.9.2

Alternate names: PR_EMS_AB_ROOM_DESCRIPTION, PR_EMS_AB_ROOM_DESCRIPTION_A, PR_EMS_AB_ROOM_DESCRIPTION_W

2.571 PidTagAddressBookSenderHintTranslations

Canonical name: PidTagAddressBookSenderHintTranslations

Description: Contains the **locale** ID and translations of the default **mail tip**.

Property ID: 0x8CAC

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.26

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_DL_SENDER_HINT_TRANSLATIONS_W

2.572 PidTagAddressBookSeniorityIndex

Canonical name: PidTagAddressBookSeniorityIndex

Description: Contains a signed integer that specifies the seniority order of **Address Book objects** that represent members of a department and are referenced by a Department object or **departmental group**, with larger values specifying members that are more senior.

Property ID: 0x8CA0

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.24

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-OXOAB] **Alternate names:** PR_EMS_AB_HAB_SENIORITY_INDEX, PR_EMS_AB_SENIORITY_INDEX

2.573 PidTagAddressBookTargetAddress

Canonical name: PidTagAddressBookTargetAddress

Description: Contains the foreign system email address of an **Address Book object**.

Property ID: 0x8011

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.3.22

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_TARGET_ADDRESS, PR_EMS_AB_TARGET_ADDRESS_A, PR_EMS_AB_TARGET_ADDRESS_W

2.574 PidTagAddressBookUnauthorizedSenders

Canonical name: PidTagAddressBookUnauthorizedSenders

Description: Indicates whether delivery restrictions exist for a **recipient**.

Property ID: 0x8CD9

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.43

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_UNAUTH_ORIG

2.575 PidTagAddressBookX509Certificate

Canonical name: PidTagAddressBookX509Certificate

Description: Contains the ASN_1 DER encoded X.509 certificates for the **mail user**.

Property ID: 0x8C6A

Data type: PtypMultipleBinary, 0x1102

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.35

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_X509_CERT

Copyright © 2025 Microsoft Corporation

2.576 PidTagAddressType

Canonical name: PidTagAddressType

Description: Contains the email **address type** of a **Message object**.

Property ID: 0x3002

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.3.13

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCMSG], [MS-OXOCAL], [MS-OXCSTOR], [MS-OXNSPI], [MS-OXOABKT], [MS-OXOMSG], [MS-OXORULE], [MS-OXOSRCH], [MS-OXPSVAL]

Alternate names: PR_ADDRTYPE, PR_ADDRTYPE_A, ptagAddrType, PR_ADDRTYPE_W

2.577 PidTagAlternateRecipientAllowed

Canonical name: PidTagAlternateRecipientAllowed

Description: Specifies whether the sender permits the message to be auto-forwarded.

Property ID: 0x0002

Data type: PtypBoolean, 0x000B

Area: Address Properties

Defining reference: [MS-OXCMSG] section 2.2.1.36

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXODOC], [MS-OXTNEF]

Alternate names: PR_ALTERNATE_RECIPIENT_ALLOWED, ptagAlternateRecipientAllowed

2.578 PidTagAnr

Canonical name: PidTagAnr

Description: Contains a filter value used in **ambiguous name resolution**.

Property ID: 0x360C

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.10.1

Alternate names: PR_ANR, PR_ANR_A, PR_ANR_W

2.579 PidTagArchiveDate

Canonical name: PidTagArchiveDate

Description: Specifies the date, in **UTC**, after which a **Message object** is archived by the server.

Property ID: 0x301F

Copyright © 2025 Microsoft Corporation

Data type: PtypTime, 0x0040

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.8

Alternate names: PR_ARCHIVE_DATE, ptagArchiveDate

2.580 PidTagArchivePeriod

Canonical name: PidTagArchivePeriod

Description: Specifies the number of days that a **Message object** can remain unarchived.

Property ID: 0x301E

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.7

Alternate names: PR_ARCHIVE_PERIOD, ptagArchivePeriod

2.581 PidTagArchiveTag

Canonical name: PidTagArchiveTag

Description: Specifies the **GUID** of an **archive tag**.

Property ID: 0x3018

Data type: PtypBinary, 0x0102

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.1

Alternate names: PR_ARCHIVE_TAG, ptagArchiveTag

2.582 PidTagAssistant

Canonical name: PidTagAssistant

Description: Contains the name of the **mail user's** administrative assistant.

Property ID: 0x3A30

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.8

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_ASSISTANT, PR_ASSISTANT_A, PR_ASSISTANT_W, urn:schemas:contacts:secretarycn

Copyright © 2025 Microsoft Corporation

2.583 PidTagAssistantTelephoneNumber

Canonical name: PidTagAssistantTelephoneNumber

Description: Contains the telephone number of the **mail user's** administrative assistant.

Property ID: 0x3A2E

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.31

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_ASSISTANT_TELEPHONE_NUMBER, PR_ASSISTANT_TELEPHONE_NUMBER_A, PR_ASSISTANT_TELEPHONE_NUMBER_W, urn:schemas:contacts:secretaryphone

2.584 PidTagAssociated

Canonical name: PidTagAssociated

Description: Specifies whether the message being synchronized is an **FAI** message.

Property ID: 0x67AA

Data type: PtypBoolean, 0x000B

Area: Sync

Defining reference: [MS-OXCFXICS] section 2.2.1.5

Alternate names: ptagAssociated

2.585 PidTagAttachAdditionalInformation

Canonical name: PidTagAttachAdditionalInformation

Description: Contains attachment encoding information.

Property ID: 0x370F

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.21

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_ATTACH_ADDITIONAL_INFO

2.586 PidTagAttachContentBase

Canonical name: PidTagAttachContentBase

Description: Contains the base of a relative **URI**.

Property ID: 0x3711

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming reference: [MS-OXCMAIL] **Alternate names:** PR_ATTACH_CONTENT_BASE, PR_ATTACH_CONTENT_BASE_A, PR_ATTACH_CONTENT_BASE_W

2.587 PidTagAttachContentId

Canonical name: PidTagAttachContentId

Description: Contains a content identifier unique to the **Message object** that matches a corresponding "cid:" **URI** schema reference in the **HTML** body of the Message object.

Property ID: 0x3712

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming references: [MS-OXCICAL], [MS-OXCMAIL], [MS-OXORMMS], [MS-OXOSMMS]

Alternate names: PR_ATTACH_CONTENT_ID, PR_ATTACH_CONTENT_ID_A, PR_ATTACH_CONTENT_ID_W

2.588 PidTagAttachContentLocation

Canonical name: PidTagAttachContentLocation

Description: Contains a relative or full **URI** that matches a corresponding reference in the **HTML** body of a **Message object**.

Property ID: 0x3713

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming references: [MS-OXCMAIL], [MS-OXORMMS]

Alternate names: PR_ATTACH_CONTENT_LOCATION, PR_ATTACH_CONTENT_LOCATION_A, PR_ATTACH_CONTENT_LOCATION_W

2.589 PidTagAttachDataBinary

Canonical name: PidTagAttachDataBinary

Description: Contains the contents of the file to be attached.

Property ID: 0x3701

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXCMSG] section 2.2.2.7

Consuming references: [MS-OXCICAL], [MS-OXCMAIL], [MS-OXTNEF], [MS-OXOCNTC], [MS-OXORMMS], [MS-OXOSMIME], [MS-OXOJRNL], [MS-OXOSMMS], [MS-OXVCARD]

Alternate names: PR_ATTACH_DATA_BIN, ptagAttachDataBin

2.590 PidTagAttachDataObject

Canonical name: PidTagAttachDataObject

Description: Contains the binary representation of the **Attachment object** in an application-specific format.

Property ID: 0x3701

Data type: PtypObject, 0x000D

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.8

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXORMDR], [MS-OXTNEF], [MS-OXORMMS], [MS-OXOCAL]

Alternate names: PR_ATTACH_DATA_OBJ, ptagAttachDataObj

2.591 PidTagAttachEncoding

Canonical name: PidTagAttachEncoding

Description: Contains encoding information about the **Attachment object**.

Property ID: 0x3702

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.20

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXORMDR], [MS-OXTNEF]

Alternate names: PR_ATTACH_ENCODING

2.592 PidTagAttachExtension

Canonical name: PidTagAttachExtension

Description: Contains a file name extension that indicates the document type of an attachment.

Property ID: 0x3703

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.12

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOCNTC], [MS-OXODOC], [MS-OXORMMS], [MS-OXVCARD]

Alternate names: PR_ATTACH_EXTENSION, PR_ATTACH_EXTENSION_A, PR_ATTACH_EXTENSION_W

2.593 PidTagAttachFilename

Canonical name: PidTagAttachFilename

Description: Contains the **8.3 name** of the **PidTagAttachLongFilename** property (section 2.595).

Property ID: 0x3704

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.11

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXTNEF], [MS-OXOCNTC], [MS-OXORMMS], [MS-OXOSMIME], [MS-OXPFOAB], [MS-OXVCARD]

Alternate names: PR_ATTACH_FILENAME, PR_ATTACH_FILENAME_A, ptagAttachFilename, PR_ATTACH_FILENAME_W

2.594 PidTagAttachFlags

Canonical name: PidTagAttachFlags

Description: Indicates which body formats might reference this attachment when rendering data.

Property ID: 0x3714

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.18

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXORMDR]

Alternate names: PR_ATTACH_FLAGS

2.595 PidTagAttachLongFilename

Canonical name: PidTagAttachLongFilename

Description: Contains the full filename and extension of the **Attachment object**.

Property ID: 0x3707

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.10

Consuming references: [MS-OXCICAL], [MS-OXOSMMS], [MS-OXRTFEX], [MS-OXCMAIL], [MS-OXMSG], [MS-OXORMMS], [MS-OXOSMIME], [MS-OXODOC], [MS-OXOUM], [MS-OXTNEF]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_ATTACH_LONG_FILENAME, PR_ATTACH_LONG_FILENAME_A, PR_ATTACH_LONG_FILENAME_W, urn:schemas:httpmail:attachmentfilename

2.596 PidTagAttachLongPathname

Canonical name: PidTagAttachLongPathname

Description: Contains the fully-qualified path and file name with extension.

Property ID: 0x370D

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.13

Consuming reference: [MS-OXORMMS]

Alternate names: PR_ATTACH_LONG_PATHNAME, PR_ATTACH_LONG_PATHNAME_A, ptagAttachLongPathname, PR_ATTACH_LONG_PATHNAME_W

2.597 PidTagAttachmentContactPhoto

Canonical name: PidTagAttachmentContactPhoto

Description: Indicates that a **contact** photo attachment is attached to a Contact object.

Property ID: 0x7FFF

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.8.2

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXORMDR], [MS-OXVCARD]

Alternate names: PR_ATTACHMENT_CONTACTPHOTO

2.598 PidTagAttachmentFlags

Canonical name: PidTagAttachmentFlags

Description: Indicates special handling for an **Attachment object**.

Property ID: 0x7FFD

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.23

Consuming references: [MS-OXCICAL], [MS-OXORMDR], [MS-OXOCAL], [MS-OXOJRNL]

Alternate names: PR_ATTACHMENT_FLAGS, ptagAttachmentFlags

Copyright © 2025 Microsoft Corporation

2.599 PidTagAttachmentHidden

Canonical name: PidTagAttachmentHidden

Description: Indicates whether an **Attachment object** is hidden from the end user.

Property ID: 0x7FFE

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.24

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOCAL], [MS-OXOJRNL], [MS-OXORMDR], [MS-OXOSMMS], [MS-OXOTASK], [MS-OXRTFEX]

Alternate names: PR_ATTACHMENT_HIDDEN

2.600 PidTagAttachmentLinkId

Canonical name: PidTagAttachmentLinkId

Description: Contains the type of **Message object** to which an attachment is linked.

Property ID: 0x7FFA

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.22

Consuming references: [MS-OXCICAL], [MS-OXOJRNL], [MS-OXORMDR]

Alternate names: PR_ATTACHMENT_LINKID, ptagAttachmentLinkId

2.601 PidTagAttachMethod

Canonical name: PidTagAttachMethod

Description: Represents the way the contents of an attachment are accessed.

Property ID: 0x3705

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.9

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOCAL], [MS-OXODOC], [MS-OXOJRNL], [MS-OXORMDR], [MS-OXOSMMS], [MS-OXOTASK], [MS-OXRTFEX], [MS-OXCMAIL], [MS-OXMSG], [MS-OXORMMS], [MS-OXORSS], [MS-OXOSMIME], [MS-OXPFOAB], [MS-OXTNEF]

Alternate names: PR_ATTACH_METHOD, ptagAttachMethod

2.602 PidTagAttachMimeTag

Canonical name: PidTagAttachMimeTag

Copyright © 2025 Microsoft Corporation

Description: Contains a content-type **MIME** header.

Property ID: 0x370E

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming references: [MS-OXCICAL], [MS-OXCMAIL], [MS-OXORMMS], [MS-OXOSMIME], [MS-OXOSMMS], [MS-OXOUM]

Alternate names: PR_ATTACH_MIME_TAG, PR_ATTACH_MIME_TAG_A, PR_ATTACH_MIME_TAG_W

2.603 PidTagAttachNumber

Canonical name: PidTagAttachNumber

Description: Identifies the **Attachment object** within its **Message object**.

Property ID: 0x0E21

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.6

Consuming references: [MS-OXCFXICS], [MS-OXCROPS], [MS-OXOCAL], [MS-OXRTFEX]

Alternate names: PR_ATTACH_NUM, ptagAttachNum

2.604 PidTagAttachPathname

Canonical name: PidTagAttachPathname

Description: Contains the **8.3 name** of the **PidTagAttachLongPathname** property (section 2.596).

Property ID: 0x3708

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.14

Consuming reference: [MS-OXORMMS]

Alternate names: PR_ATTACH_PATHNAME, PR_ATTACH_PATHNAME_A, ptagAttachPathname, PR_ATTACH_PATHNAME_W

2.605 PidTagAttachPayloadClass

Canonical name: PidTagAttachPayloadClass

Description: Contains the class name of an object that can display the contents of the message.

Property ID: 0x371A

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Outlook Application

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_ATTACH_PAYLOAD_CLASS, PR_ATTACH_PAYLOAD_CLASS_A, PR_ATTACH_PAYLOAD_CLASS_W, ptagAttachPayloadClass

2.606 PidTagAttachPayloadProviderGuidString

Canonical name: PidTagAttachPayloadProviderGuidString

Description: Contains the **GUID** of the software component that can display the contents of the message.

Property ID: 0x3719

Data type: PtypString, 0x001F

Area: Outlook Application

Defining reference: [MS-OXCMSG] section 2.2.2.29

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_ATTACH_PAYLOAD_PROV_GUID_STR, PR_ATTACH_PAYLOAD_PROV_GUID_STR_A, PR_ATTACH_PAYLOAD_PROV_GUID_STR_W

2.607 PidTagAttachRendering

Canonical name: PidTagAttachRendering

Description: Contains a Windows Metafile, as specified in [MS-WMF], for the **Attachment object**.

Property ID: 0x3709

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.17

Consuming references: [MS-OXCFXICS], [MS-OXTNEF]

Alternate names: PR_ATTACH_RENDERING, ptagAttachRendering

2.608 PidTagAttachSize

Canonical name: PidTagAttachSize

Description: Contains the size, in bytes, consumed by the **Attachment object** on the server.

Property ID: 0x0E20

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.5

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXORMDR]

Alternate names: PR_ATTACH_SIZE, ptagAttachSize

2.609 PidTagAttachTag

Canonical name: PidTagAttachTag

Description: Contains the identifier information for the application that supplied the **Attachment object** data.

Property ID: 0x370A

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.15

Consuming references: [MS-OXORMMS], [MS-OXTNEF]

Alternate names: PR_ATTACH_TAG

2.610 PidTagAttachTransportName

Canonical name: PidTagAttachTransportName

Description: Contains the name of an attachment file, modified so that it can be correlated with **TNEF** messages.

Property ID: 0x370C

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.19

Consuming reference: [MS-OXTNEF]

Alternate names: PR_ATTACH_TRANSPORT_NAME, PR_ATTACH_TRANSPORT_NAME_A, PR_ATTACH_TRANSPORT_NAME_W

2.611 PidTagAttributeHidden

Canonical name: PidTagAttributeHidden

Description: Specifies the hide or show status of a folder.

Property ID: 0x10F4

Data type: PtypBoolean, 0x000B

Area: Access Control Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.1

Consuming references: [MS-OXOSFLD], [MS-OXTNEF], [MS-XWDCAL]

Alternate names: PR_ATTR_HIDDEN, ptagAttrHidden, DAV:ishidden

Copyright © 2025 Microsoft Corporation

2.612 PidTagAttributeReadOnly

Canonical name: PidTagAttributeReadOnly

Description: Indicates whether an item can be modified or deleted.

Property ID: 0x10F6

Data type: PtypBoolean, 0x000B

Area: Access Control Properties

Defining reference: [MS-XWDCAL] section 2.2.1.8

Consuming references: [MS-OXTNEF]

Alternate names: PR_ATTR_READONLY, ptagAttrReadonly, DAV:isreadonly

2.613 PidTagAutoForwardComment

Canonical name: PidTagAutoForwardComment

Description: Contains text included in an automatically-generated message.

Property ID: 0x0004

Data type: PtypString, 0x001F

Area: General Report Properties

Defining reference: [MS-OXCMSG] section 2.2.1.21

Alternate names: PR_AUTO_FORWARD_COMMENT, PR_AUTO_FORWARD_COMMENT_A, PR_AUTO_FORWARD_COMMENT_W

2.614 PidTagAutoForwarded

Canonical name: PidTagAutoForwarded

Description: Indicates that a **Message object** has been automatically generated or automatically forwarded.

Property ID: 0x0005

Data type: PtypBoolean, 0x000B

Area: General Report Properties

Defining reference: [MS-OXCMSG] section 2.2.1.20

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_AUTO_FORWARDED, ptagAutoForwarded

2.615 PidTagAutoResponseSuppress

Canonical name: PidTagAutoResponseSuppress

Description: Specifies whether a client or server application will forego sending automated replies in response to this message.

Copyright © 2025 Microsoft Corporation

Property ID: 0x3FDF

Data type: PtypInteger32, 0x0003

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.77

Consuming references: [MS-OXCMAIL], [MS-OXORULE]

Alternate names: PR_AUTO_RESPONSE_SUPPRESS, ptagAutoResponseSuppress

2.616 PidTagBirthday

Canonical name: PidTagBirthday

Description: Contains the date of the **mail user's** birthday at midnight.

Property ID: 0x3A42

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.5.1

Consuming references: [MS-OXVCARD]

Alternate names: PR_BIRTHDAY, urn:schemas:contacts:bday

2.617 PidTagBlockStatus

Canonical name: PidTagBlockStatus

Description: Indicates the user's preference for viewing external content (such as links to images on an **HTTP** server) in the **message body**.

Property ID: 0x1096

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [MS-OXOMSG] section 2.2.1.1

Alternate names: PR_BLOCK_STATUS, ptagBlockStatus

2.618 PidTagBody

Canonical name: PidTagBody

Description: Contains **message body** text in **plain text** format.

Property ID: 0x1000

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.58.1

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOMSG], [MS-OXORMMS], [MS-OXRTFEX], [MS-OXBBODY], [MS-OXCDATA], [MS-OXCMAIL], [MS-OXONOTE], [MS-OXOSMMS], [MS-OXPROTO], [MS-OXTNEF], [MS-XWDCAL], [MS-OXVCARD]

Alternate names: PR_BODY, PR_BODY_A, ptagBody, PR_BODY_W, urn:schemas:httpmail:textdescription

2.619 PidTagBodyContentId

Canonical name: PidTagBodyContentId

Description: Contains a **GUID** that corresponds to the current **message body**.

Property ID: 0x1015

Data type: PtypString, 0x001F

Area: Exchange

Defining reference: [MS-OXCMSG] section 2.2.1.58.7

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_BODY_CONTENT_ID, PR_BODY_CONTENT_ID_A, PR_BODY_CONTENT_ID_W

2.620 PidTagBodyContentLocation

Canonical name: PidTagBodyContentLocation

Description: Contains a globally unique **Uniform Resource Identifier (URI)** that serves as a label for the current **message body**.

Property ID: 0x1014

Data type: PtypString, 0x001F

Area: MIME Properties

Defining reference: [MS-OXCMSG] section 2.2.1.58.8

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_BODY_CONTENT_LOCATION, PR_BODY_CONTENT_LOCATION_A, PR_BODY_CONTENT_LOCATION_W

2.621 PidTagBodyHtml

Canonical name: PidTagBodyHtml

Description: Contains the **HTML** body of the **Message object**.

Property ID: 0x1013

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.58.3

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOMSG], [MS-OXORMMS], [MS-OXRTFEX]

Alternate names: PR_BODY_HTML, PR_BODY_HTML_A, ptagBodyHtml, PR_BODY_HTML_W

2.622 PidTagBusiness2TelephoneNumber

Canonical name: PidTagBusiness2TelephoneNumber

Description: Contains a secondary telephone number at the **mail user's** place of business.

Property ID: 0x3A1B

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOABK] section 2.2.4.23

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: "PR_BUSINESS2_TELEPHONE_NUMBER, PR_BUSINESS2_TELEPHONE_NUMBER_A, PR_BUSINESS2_TELEPHONE_NUMBER_W, PR_OFFICE2_TELEPHONE_NUMBER, urn:schemas:contacts:telephonenumber2

2.623 PidTagBusiness2TelephoneNumbers

Canonical name: PidTagBusiness2TelephoneNumbers

Description: Contains secondary telephone numbers at the **mail user's** place of business.

Property ID: 0x3A1B

Data type: PtypMultipleString, 0x101F

Area: Contact Properties

Defining reference: [MS-OXOABK] section 2.2.4.24

Consuming reference: [MS-OXOAB]

Alternate names: PR_BUSINESS2_TELEPHONE_NUMBER_A_MV

2.624 PidTagBusinessFaxNumber

Canonical name: PidTagBusinessFaxNumber

Description: Contains the telephone number of the **mail user's** business fax machine.

Property ID: 0x3A24

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.2.6

Consuming references: [MS-OXVCARD]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_BUSINESS_FAX_NUMBER, PR_BUSINESS_FAX_NUMBER_A, PR_BUSINESS_FAX_NUMBER_W, urn:schemas:contacts:facsimiletelephonenumber

2.625 PidTagBusinessHomePage

Canonical name: PidTagBusinessHomePage

Description: Contains the **URL** of the **mail user's** business home page.

Property ID: 0x3A51

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.14

Consuming references: [MS-OXVCARD]

Alternate names: PR_BUSINESS_HOME_PAGE, PR_BUSINESS_HOME_PAGE_A, PR_BUSINESS_HOME_PAGE_W, urn:schemas:contacts:businesshomepageurn:schemas:contacts:businesshomepage

2.626 PidTagBusinessTelephoneNumber

Canonical name: PidTagBusinessTelephoneNumber

Description: Contains the primary telephone number of the **mail user's** place of business.

Property ID: 0x3A08

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOABK] section 2.2.4.21

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_BUSINESS_TELEPHONE_NUMBER, PR_BUSINESS_TELEPHONE_NUMBER_A, PR_BUSINESS_TELEPHONE_NUMBER_W, PR_OFFICE_TELEPHONE_NUMBER, urn:schemas:contacts:telephoneNumber

2.627 PidTagCallbackTelephoneNumber

Canonical name: PidTagCallbackTelephoneNumber

Description: Contains a telephone number to reach the **mail user**.

Property ID: 0x3A02

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.4.2

Consuming references: [MS-OXVCARD]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_CALLBACK_TELEPHONE_NUMBER, PR_CALLBACK_TELEPHONE_NUMBER_A, PR_CALLBACK_TELEPHONE_NUMBER_W, urn:schemas:contacts:callbackphone

2.628 PidTagCallId

Canonical name: PidTagCallId

Description: Contains a unique identifier associated with the phone call.

Property ID: 0x6806

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.11

Consuming reference: [MS-OXCMAIL]

Alternate names: InternalSchemaCallID

2.629 PidTagCarTelephoneNumber

Canonical name: PidTagCarTelephoneNumber

Description: Contains the **mail user's** car telephone number.

Property ID: 0x3A1E

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.4.9

Consuming references: [MS-OXVCARD]

Alternate names: PR_CAR_TELEPHONE_NUMBER, PR_CAR_TELEPHONE_NUMBER_A, PR_CAR_TELEPHONE_NUMBER_W, urn:schemas:contacts:othermobile

2.630 PidTagCdoRecurrenceid

Canonical name: PidTagCdoRecurrenceid

Description: Identifies a specific instance of a recurring appointment.

Property ID: 0x10C5

Data type: PtypTime, 0x0040

Area: Exchange

Defining reference: [MS-XWDCAL] section 2.2.2.38

Alternate names: PR_CDO_RECURRENCEID, urn:schemas:calendar:recurrenceid

2.631 PidTagChangeKey

Canonical name: PidTagChangeKey

Copyright © 2025 Microsoft Corporation

Description: Contains a structure that identifies the last change to the object.

Property ID: 0x65E2

Data type: PtypBinary, 0x0102

Area: History Properties

Defining reference: [MS-OXCFXICS] section 2.2.1.2.7

Consuming references: [MS-OXCFOLD], [MS-OXCMSG], [MS-OXCPRPT]

Alternate names: PR_CHANGE_KEY

2.632 PidTagChangeNumber

Canonical name: PidTagChangeNumber

Description: Contains a structure that identifies the last change to the message or folder that is currently being synchronized.

Property ID: 0x67A4

Data type: PtypInteger64, 0x0014

Area: Sync

Defining reference: [MS-OXCFXICS] section 2.2.1.2.3

Consuming reference: [MS-OXCSTOR]

Alternate names: ptagCn

2.633 PidTagChildrensNames

Canonical name: PidTagChildrensNames

Description: Specifies the names of the children of the **contact**.

Property ID: 0x3A58

Data type: PtypMultipleString, 0x101F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.17

Consuming references: [MS-OXVCARD]

Alternate names: PR_CHILDRENS_NAMES, PR_CHILDRENS_NAMES_A, PR_CHILDRENS_NAMES_W, urn:schemas:contacts:childrensnames

2.634 PidTagClientActions

Canonical name: PidTagClientActions

Description: Specifies the **actions** the client is required to take on the message.

Property ID: 0x6645

Data type: PtypBinary, 0x0102

Copyright © 2025 Microsoft Corporation

Area: Server-side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.6.6

Alternate names: PR_CLIENT_ACTIONS, ptagClientActions

2.635 PidTagClientActivelyEditingUntil

Canonical name: PidTagClientActivelyEditingUntil

Description: Specifies the date and time, in **UTC**, until which the client expects to be actively editing the object.

Property ID: 0x3700

Data Type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [MS-OXCMSG] section 2.2.1.57

Alternate names: PR_CLIENT_ACTIVELY_EDITING_UNTIL, ptagClientActivelyEditingUntil

2.636 PidTagClientSubmitTime

Canonical name: PidTagClientSubmitTime

Description: Contains the current time, in **UTC**, when the email message is submitted.

Property ID: 0x0039

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [MS-OXOMSG] section 2.2.3.11

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXODOC], [MS-OXORSS], [MS-OXTNEF]

Alternate names: PR_CLIENT_SUBMIT_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

2.637 PidTagCodePageId

Canonical name: PidTagCodePageId

Description: Contains the identifier for the client code page used for **Unicode** to **double-byte character set (DBCS)** string conversion.

Property ID: 0x66C3

Data type: PtypInteger32, 0x0003

Area: Exchange Profile Configuration

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.15

Alternate names: PR_CODE_PAGE_ID, ptagCodePageId

Copyright © 2025 Microsoft Corporation

2.638 PidTagComment

Canonical name: PidTagComment

Description: Contains a comment about the purpose or content of the **Address Book object**.

Property ID: 0x3004

Data type: PtypString, 0x001F

Area: Common

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.2

Consuming references: [MS-OXOAB], [MS-OXOABK], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCSTOR], [MS-XWDCAL]

Alternate names: PR_COMMENT, PR_COMMENT_A, ptagComment, PR_COMMENT_W, DAV:comment, http://schemas.microsoft.com/exchange/summary-utf8

2.639 PidTagCompanyMainTelephoneNumber

Canonical name: PidTagCompanyMainTelephoneNumber

Description: Contains the main telephone number of the **mail user's** company.

Property ID: 0x3A57

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.4.14

Consuming references: [MS-OXVCARD]

Alternate names: PR_COMPANY_MAIN_PHONE_NUMBER, PR_COMPANY_MAIN_PHONE_NUMBER_A, PR_COMPANY_MAIN_PHONE_NUMBER_W, urn:schemas:contacts:organizationmainphone

2.640 PidTagCompanyName

Canonical name: PidTagCompanyName

Description: Contains the **mail user's** company name.

Property ID: 0x3A16

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOABK] section 2.2.4.7

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_COMPANY_NAME, PR_COMPANY_NAME_A, PR_COMPANY_NAME_W, urn:schemas:contacts:o

Copyright © 2025 Microsoft Corporation

2.641 PidTagComputerNetworkName

Canonical name: PidTagComputerNetworkName

Description: Contains the name of the **mail user's** computer network.

Property ID: 0x3A49

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.16

Alternate names: PR_COMPUTER_NETWORK_NAME, PR_COMPUTER_NETWORK_NAME_A, PR_COMPUTER_NETWORK_NAME_W, urn:schemas:contacts:computernetworkname

2.642 PidTagConflictEntryId

Canonical name: PidTagConflictEntryId

Description: Contains the **EntryID** of the conflict resolve message.

Property ID: 0x3FF0

Data type: PtypBinary, 0x0102

Area: ICS

Defining reference: [MS-OXCFXICS] section 2.2.1.4.2

Alternate names: PR_CONFLICT_ENTRYID, ptagConflictEntryId

2.643 PidTagContainerClass

Canonical name: PidTagContainerClass

Description: Contains a string value that describes the type of **Message object** that a folder contains.

Property ID: 0x3613

Data type: PtypString, 0x001F

Area: Container Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.3

Consuming references: [MS-OXCICAL], [MS-OXMSG], [MS-OXOCAL], [MS-OXOCNTC], [MS-OXOSFLD], [MS-OXOSRCH], [MS-OXSHARE], [MS-XWDCAL]

Alternate names: PR_CONTAINER_CLASS, PR_CONTAINER_CLASS_A, ptagContainerClass, PR_CONTAINER_CLASS_W, http://schemas.microsoft.com/exchange/outlookfolderclasshttp://schemas.microsoft.com/exchange/outlookfolderclass

2.644 PidTagContainerContents

Canonical name: PidTagContainerContents

Copyright © 2025 Microsoft Corporation

Description: Empty. An **NSPI** server defines this value for **distribution lists** and it is not present for other objects.

Property ID: 0x360F

Data type: PtypEmbeddedTable, 0x000D

Area: Container Properties

Defining reference: [MS-OXOABK] section 2.2.6.3

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXNSPI]

Alternate names: PR_CONTAINER_CONTENTS, ptagContainerContents

2.645 PidTagContainerFlags

Canonical name: PidTagContainerFlags

Description: Contains a bitmask of **flags** that describe capabilities of an **address book container**.

Property ID: 0x3600

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.2.1

Consuming reference: [MS-OXNSPI]

Alternate names: PR_CONTAINER_FLAGS

2.646 PidTagContainerHierarchy

Canonical name: PidTagContainerHierarchy

Description: Identifies all of the subfolders of the current folder.

Property ID: 0x360E

Data type: PtypObject, 0x000D

Area: Container Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.4

Consuming references: [MS-OXCFXICS]

Alternate names: PR_CONTAINER_HIERARCHY, ptagContainerHierarchy

2.647 PidTagContentCount

Canonical name: PidTagContentCount

Description: Specifies the number of rows under the header row.

Property ID: 0x3602

Data type: PtypInteger32, 0x0003

Copyright © 2025 Microsoft Corporation

Area: Folder Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.1

Consuming references: [MS-OXCICAL], [MS-OXCSTOR], [MS-OXCTABL]

Alternate names: PR_CONTENT_COUNT, ptagContentCount, DAV:visiblecount

2.648 PidTagContentFilterSpamConfidenceLevel

Canonical name: PidTagContentFilterSpamConfidenceLevel

Description: Indicates a confidence level that the message is **spam**.

Property ID: 0x4076

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [MS-OXCSPAM] section 2.2.1.3

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOMSG], [MS-OXORULE], [MS-OXTNEF]

Alternate names: PR_CONTENT_FILTER_SCL, ptagContentFilterSCL

2.649 PidTagContentUnreadCount

Canonical name: PidTagContentUnreadCount

Description: Specifies the number of rows under the header row that have the **PidTagRead** property (section 2.880) set to FALSE.

Property ID: 0x3603

Data type: PtypInteger32, 0x0003

Area: Folder Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.2

Consuming references: [MS-OXCTABL]

Alternate names: PR_CONTENT_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

2.650 PidTagConversationId

Canonical name: PidTagConversationId

Description: Contains a computed value derived from other **conversation**-related properties.

Property ID: 0x3013

Data type: PtypBinary, 0x0102

Area: Conversations

Defining reference: [MS-OXOMSG] section 2.2.1.2

Consuming references: [MS-OXOCFG]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_CONVERSATION_ID

2.651 PidTagConversationIndex

Canonical name: PidTagConversationIndex

Description: Indicates the relative position of this message within a **conversation** thread.

Property ID: 0x0071

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.3

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOMSG], [MS-OXOPOST], [MS-OXTNEF], [MS-OXOCAL]

Alternate names: PR_CONVERSATION_INDEX, ptagConversationIndex

2.652 PidTagConversationIndexTracking

Canonical name: PidTagConversationIndexTracking

Description: Indicates whether the **GUID** portion of the **PidTagConversationIndex** property (section 2.651) is to be used to compute the **PidTagConversationId** property (section 2.650).

Property ID: 0x3016

Data type: PtypBoolean, 0x000B

Area: Conversations

Defining reference: [MS-OXOMSG] section 2.2.1.4

Alternate names: PR_CONVERSATION_INDEX_TRACKING

2.653 PidTagConversationTopic

Canonical name: PidTagConversationTopic

Description: Contains an unchanging copy of the original subject.

Property ID: 0x0070

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.5

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOPOST], [MS-OXORMDR], [MS-OXORSS], [MS-OXTNEF], [MS-OXVCARD]

Alternate names: PR_CONVERSATION_TOPIC, PR_CONVERSATION_TOPIC_A, ptagConversationTopic, PR_CONVERSATION_TOPIC_W, urn:schemas:httpmail:thread-topic

Copyright © 2025 Microsoft Corporation

2.654 PidTagCountry

Canonical name: PidTagCountry

Description: Contains the name of the **mail user's** country/region.

Property ID: 0x3A26

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOABK] section 2.2.4.19

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_COUNTRY, PR_COUNTRY_A, PR_COUNTRY_W, PR_BUSINESS_ADDRESS_COUNTRY, PR_BUSINESS_ADDRESS_COUNTRY_A, PR_BUSINESS_ADDRESS_COUNTRY_W, urn:schemas:contacts:mailingcountry

2.655 PidTagCreationTime

Canonical name: PidTagCreationTime

Description: Contains the time, in **UTC**, that the object was created.

Property ID: 0x3007

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [MS-OXCMSG] section 2.2.2.3

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCPRPT], [MS-OXOABK], [MS-OXOCFG], [MS-OXODOC], [MS-OXORMMS], [MS-OXTNEF]

Alternate names: PR_CREATION_TIME, ptagCreationTime, DAV:creationdate

2.656 PidTagCreatorEntryId

Canonical name: PidTagCreatorEntryId

Description: Specifies the original author of the message according to their Address Book **EntryID**.

Property ID: 0x3FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [MS-OXCMSG] section 2.2.1.31

Consuming reference: [MS-OXTNEF]

Alternate names: PR_CREATOR_ENTRYID, ptagCreatorEntryId

2.657 PidTagCreatorName

Canonical name: PidTagCreatorName

Copyright © 2025 Microsoft Corporation

Description: Contains the name of the creator of a **Message object**.

Property ID: 0x3FF8

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.51

Consuming references: [MS-OXCFXICS], [MS-OXTNEF]

Alternate names: PR_CREATOR_NAME, PR_CREATOR_NAME_A, ptagCreatorName, PR_CREATOR_NAME_W

2.658 PidTagCustomerId

Canonical name: PidTagCustomerId

Description: Contains the **mail user's** customer identification number.

Property ID: 0x3A4A

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.8

Alternate names: PR_CUSTOMER_ID, PR_CUSTOMER_ID_A, PR_CUSTOMER_ID_W, urn:schemas:contacts:customerid

2.659 PidTagDamBackPatched

Canonical name: PidTagDamBackPatched

Description: Indicates whether the **Deferred Action Message (DAM)** was updated by the server.

Property ID: 0x6647

Data type: PtypBoolean, 0x000B

Area: Server-side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.6.2

Alternate names: PR_DAM_BACK_PATCHED, ptagDamBackPatched

2.660 PidTagDamOriginalEntryId

Canonical name: PidTagDamOriginalEntryId

Description: Contains the **EntryID** of the delivered message that the client has to process.

Property ID: 0x6646

Data type: PtypBinary, 0x0102

Area: Server-side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.6.3

Copyright © 2025 Microsoft Corporation

Alternate names: PR_DAM_ORIGINAL_ENTRYID

2.661 PidTagDefaultPostMessageClass

Canonical name: PidTagDefaultPostMessageClass

Description: Contains the **message class** of the object.

Property ID: 0x36E5

Data type: PtypString, 0x001F

Area: MapiContainer

Defining reference: [MS-OXOCAL] section 2.2.11.2

Alternate names: PR_DEF_POST_MSGCLASS

2.662 PidTagDeferredActionMessageOriginalEntryId

Canonical name: PidTagDeferredActionMessageOriginalEntryId

Description: Contains the server **EntryID** for the **DAM**.

Property ID: 0x6741

Data type: PtypServerId, 0x00FB

Area: Server-side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.6.8

Alternate names: PR_DAM_ORIG_MSG_SVREID, ptagDamOrgMsgSvrEID

2.663 PidTagDeferredDeliveryTime

Canonical name: PidTagDeferredDeliveryTime

Description: Contains the date and time, in **UTC**, at which the sender prefers that the message be delivered.

Property ID: 0x000F

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.1.6

Alternate names: PR_DEFERRED_DELIVERY_TIME, ptagDeferredDeliveryTime, http://schemas.microsoft.com/exchange/deferred-delivery-iso

2.664 PidTagDeferredSendNumber

Canonical name: PidTagDeferredSendNumber

Description: Contains a number used in the calculation of how long to defer sending a message.

Property ID: 0x3FEB

Copyright © 2025 Microsoft Corporation

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [MS-OXOMSG] section 2.2.3.2

Alternate names: PR_DEFERRED_SEND_NUMBER

2.665 PidTagDeferredSendTime

Canonical name: PidTagDeferredSendTime

Description: Contains the amount of time after which a client would like to defer sending the message.

Property ID: 0x3FEF

Data type: PtypTime, 0x0040

Area: MapiStatus

Defining reference: [MS-OXOMSG] section 2.2.3.4

Alternate names: PR_DEFERRED_SEND_TIME, ptagDeferredSendTime

2.666 PidTagDeferredSendUnits

Canonical name: PidTagDeferredSendUnits

Description: Specifies the unit of time used as a multiplier with the **PidTagDeferredSendNumber** property (section 2.664) value.

Property ID: 0x3FEC

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [MS-OXOMSG] section 2.2.3.3

Alternate names: PR_DEFERRED_SEND_UNITS

2.667 PidTagDelegatedByRule

Canonical name: PidTagDelegatedByRule

Description: Specifies whether the message was forwarded due to the triggering of a **delegate** forward **rule**.

Property ID: 0x3FE3

Data type: PtypBoolean, 0x000B

Area: MapiStatus

Defining reference: [MS-OXOMSG] section 2.2.1.84

Consuming references: [MS-OXODLGT], [MS-OXORULE]

Alternate names: PR_DELEGATED_BY_RULE

Copyright © 2025 Microsoft Corporation

2.668 PidTagDelegateFlags

Canonical name: PidTagDelegateFlags

Description: Indicates whether **delegates** can view **Message objects** that are marked as private.

Property ID: 0x686B

Data type: PtypMultipleInteger32, 0x1003

Area: MessageClassDefinedTransmittable

Defining reference: [MS-OXODLGT] section 2.2.2.2.6

Alternate names: PR_DELEGATE_FLAGS, ptagDelegateFlags

2.669 PidTagDeleteAfterSubmit

Canonical name: PidTagDeleteAfterSubmit

Description: Indicates that the original message is to be deleted after it is sent.

Property ID: 0x0E01

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

Defining reference: [MS-OXOMSG] section 2.2.3.8

Consuming references: [MS-OXCICAL], [MS-OXCSTOR], [MS-OXODOC]

Alternate names: PR_DELETE_AFTER_SUBMIT, ptagDeleteAfterSubmit

2.670 PidTagDeletedCountTotal

Canonical name: PidTagDeletedCountTotal

Description: Contains the total count of messages that have been deleted from a folder, excluding messages deleted within subfolders.

Property ID: 0x670B

Data type: PtypInteger32, 0x0003

Area: Server

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.15

Consuming reference: [MS-OXCFXICS]

Alternate names: PR_DELETED_COUNT_TOTAL, ptagDeleteCountTotal

2.671 PidTagDeletedOn

Canonical name: PidTagDeletedOn

Description: Specifies the time, in **UTC**, when the item or folder was **soft deleted**.

Property ID: 0x668F

Copyright © 2025 Microsoft Corporation

Data type: PtypTime, 0x0040

Area: ExchangeFolder

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.3

Alternate names: PR_DELETED_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

2.672 PidTagDeliverTime

Canonical name: PidTagDeliverTime

Description: Contains the delivery time for a delivery status notification, as specified [RFC3464], or a message disposition notification, as specified in [RFC3798].

Property ID: 0x0010

Data type: PtypTime, 0x0040

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.2.29

Consuming references: [MS-OXCMAIL]

Alternate names: PR_DELIVER_TIME, ptagDeliverTime

2.673 PidTagDepartmentName

Canonical name: PidTagDepartmentName

Description: Contains a name for the department in which the **mail user** works.

Property ID: 0x3A18

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.6

Consuming references: [MS-OXNSPI], [MS-OXOAB] [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_DEPARTMENT_NAME, PR_DEPARTMENT_NAME_A, PR_DEPARTMENT_NAME_W, urn:schemas:contacts:department

2.674 PidTagDepth

Canonical name: PidTagDepth

Description: Specifies the number of nested categories in which a given row is contained.

Property ID: 0x3005

Data type: PtypInteger32, 0x0003

Area: MapiCommon

Defining reference: [MS-OXCTABL] section 2.2.1.4

Consuming references: [MS-OXNSPI], [MS-OXOABK], [MS-OXOABKT]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_DEPTH, ptagDepth

2.675 PidTagDisplayBcc

Canonical name: PidTagDisplayBcc

Description: Contains a list of **blind carbon copy (Bcc) recipient display names**.

Property ID: 0x0E02

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.7

Consuming reference: [MS-OXCMSG]

Alternate names: PR_DISPLAY_BCC, PR_DISPLAY_BCC_A, ptagDisplayBcc, PR_DISPLAY_BCC_W, urn:schemas:httpmail:displaybcc

2.676 PidTagDisplayCc

Canonical name: PidTagDisplayCc

Description: Contains a list of **carbon copy (Cc) recipient display names**.

Property ID: 0x0E03

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.8

Consuming references: [MS-OXCMSG]

Alternate names: PR_DISPLAY_CC, PR_DISPLAY_CC_A, ptagDisplayCc, PR_DISPLAY_CC_W, urn:schemas:httpmail:displaycc

2.677 PidTagDisplayName

Canonical name: PidTagDisplayName

Description: Contains the **display name** of the folder.

Property ID: 0x3001

Data type: PtypString, 0x001F

Area: MapiCommon

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.5

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCMSG], [MS-OXCPRPT], [MS-OXCSTOR], [MS-OXMSG], [MS-OXNSPI], [MS-OXOAB], [MS-OXOABK], [MS-OXOABKT], [MS-OXOCAL], [MS-OXOCNTC], [MS-OXODLGT], [MS-OXODOC], [MS-OXOPFFB], [MS-OXORMDR], [MS-OXORMMS], [MS-OXORULE], [MS-OXOSMIME], [MS-OXOSRCH], [MS-OXSHARE], [MS-OXVCARD], [MS-XWDVSEC]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_DISPLAY_NAME, PR_DISPLAY_NAME_A, ptagDisplayName, PR_DISPLAY_NAME_W, urn:schemas:contacts:cn

2.678 PidTagDisplayNamePrefix

Canonical name: PidTagDisplayNamePrefix

Description: Contains the **mail user's** honorific title.

Property ID: 0x3A45

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.1.3

Consuming references: [MS-OXVCARD]

Alternate names: PR_DISPLAY_NAME_PREFIX, PR_DISPLAY_NAME_PREFIX_A, PR_DISPLAY_NAME_PREFIX_W, urn:schemas:contacts:personaltitle

2.679 PidTagDisplayTo

Canonical name: PidTagDisplayTo

Description: Contains a list of the **primary recipient display names**, separated by semicolons, when an email message has primary recipients .

Property ID: 0x0E04

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.9

Consuming references: [MS-OXCMSG]

Alternate names: PR_DISPLAY_TO, PR_DISPLAY_TO_A, ptagDisplayTo, PR_DISPLAY_TO_W

2.680 PidTagDisplayType

Canonical name: PidTagDisplayType

Description: Contains an integer value that indicates how to display an **Address Book object** in a table or as an addressee on a message.

Property ID: 0x3900

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

Defining reference:[MS-OXOABK] section 2.2.3.11

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMSG], [MS-OXOMSG], [MS-OXLDAP], [MS-OXNSPI], [MS-OXOAB], [MS-OXOABKT], [MS-OXODLGT], [MS-OXOSRCH]

Alternate names: PR_DISPLAY_TYPE, ptagDisplayType

Copyright © 2025 Microsoft Corporation

2.681 PidTagDisplayTypeEx

Canonical name: PidTagDisplayTypeEx

Description: Contains an integer value that indicates how to display an **Address Book object** in a table or as a **recipient** on a message.

Property ID: 0x3905

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

Defining reference: [MS-OXOABK] section 2.2.3.12

Consuming references: [MS-OXCFXICS], [MS-OXCMSG], [MS-OXOMSG], [MS-OXOAB], [MS-OXODLGT], [MS-OXOSRCH]

Alternate names: PR_DISPLAY_TYPE_EX

2.682 PidTagEmailAddress

Canonical name: PidTagEmailAddress

Description: Contains the email address of a **Message object**.

Property ID: 0x3003

Data type: PtypString, 0x001F

Area: MapiCommon

Defining reference: [MS-OXOABK] section 2.2.3.14

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCMSG], [MS-OXCSPAM], [MS-OXNSPI], [MS-OXOAB], [MS-OXOABKT], [MS-OXODLGT], [MS-OXOMSG], [MS-OXOPFFB], [MS-OXORULE], [MS-OXOSRCH], [MS-OXPSVAL]

Alternate names: PR_EMAIL_ADDRESS, PR_EMAIL_ADDRESS_A, PR_EMAIL_ADDRESS_W

2.683 PidTagEndDate

Canonical name: PidTagEndDate

Description: Contains the value of the **PidLidAppointmentEndWhole** property (section 2.14).

Property ID: 0x0061

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

Defining reference: [MS-OXOCAL] section 2.2.1.31

Consuming references: [MS-OXCICAL], [MS-OXORMDR], [MS-OXTNEF], [MS-XWDCAL]

Alternate names: PR_END_DATE, http://schemas.microsoft.com/mapi/end_date

Copyright © 2025 Microsoft Corporation

2.684 PidTagEntryId

Canonical name: PidTagEntryId

Description: Contains the information to identify many different types of **messaging objects**.

Property ID: 0x0FFF

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [MS-OXCPERM] section 2.2.4

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCMSG], [MS-OXNSPI], [MS-OXOABK], [MS-OXOABKT], [MS-OXOCAL], [MS-OXOCFG], [MS-OXOCNTC], [MS-OXODLGT], [MS-OXOMSG], [MS-OXORULE], [MS-OXOSRCH], [MS-OXOTASK], [MS-OXPFOAB], [MS-OXSHARE], [MS-OXWAVLS]

Alternate names: PR_ENTRYID, ptagEntryId

2.685 PidTagExceptionEndTime

Canonical name: PidTagExceptionEndTime

Description: Contains the end date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFC

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [MS-OXOCAL] section 2.2.10.1.5

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: PR_EXCEPTION_ENDTIME, ptagExceptionEndTime

2.686 PidTagExceptionReplaceTime

Canonical name: PidTagExceptionReplaceTime

Description: Indicates the original date and time, in **UTC**, at which the instance in the **recurrence pattern** would have occurred if it were not an exception.

Property ID: 0x7FF9

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [MS-OXOCAL] section 2.2.10.1.6

Alternate names: PR_EXCEPTION_REPLACETIME

2.687 PidTagExceptionStartTime

Canonical name: PidTagExceptionStartTime

Copyright © 2025 Microsoft Corporation

Description: Contains the start date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFB

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [MS-OXOCAL] section 2.2.10.1.4

Consuming references: [MS-OXCICAL], [MS-OXORMDR]

Alternate names: PR_EXCEPTION_STARTTIME, ptagExceptionStartTime

2.688 PidTagExchangeNTSecurityDescriptor

Canonical name: PidTagExchangeNTSecurityDescriptor

Description: Contains the calculated security descriptor for the item.

Property ID: 0x0E84

Data type: PtypBinary, 0x0102

Area: Calendar Document

Defining reference: [MS-XWDCAL] section 2.2.8.8

Alternate names: http://schemas.microsoft.com/exchange/ntsecuritydescriptor, http://schemas.microsoft.com/exchange/ntsecuritydescriptor

2.689 PidTagExpiryNumber

Canonical name: PidTagExpiryNumber

Description: Contains an integer value that is used along with the **PidTagExpiryUnits** property (section 2.691) to define the expiry send time.

Property ID: 0x3FED

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference:[MS-OXOMSG] section 2.2.3.5

Alternate names: PR_EXPIRY_NUMBER

2.690 PidTagExpiryTime

Canonical name: PidTagExpiryTime

Description: Contains the time, in **UTC**, after which a client wants to receive an expiry event if the message arrives late.

Property ID: 0x0015

Data type: PtypTime, 0x0040

Copyright © 2025 Microsoft Corporation

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.3.7

Consuming references: [MS-OXCMAIL]

Alternate names: PR_EXPIRY_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date, http://schemas.microsoft.com/exchange/expiry-date-iso

2.691 PidTagExpiryUnits

Canonical name: PidTagExpiryUnits

Description: Contains the unit of time that the value of the **PidTagExpiryNumber** property (section 2.689) multiplies.

Property ID: 0x3FEE

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [MS-OXOMSG] section 2.2.3.6

Alternate names: PR_EXPIRY_UNITS

2.692 PidTagExtendedFolderFlags

Canonical name: PidTagExtendedFolderFlags

Description: Contains encoded sub-properties for a folder.

Property ID: 0x36DA

Data type: PtypBinary, 0x0102

Area: MapiContainer

Defining reference: [MS-OXOSRCH] section 2.2.2.1.2

Consuming references: [MS-OXCICAL], [MS-OXOCFG]

Alternate names: PR_EXTENDED_FOLDER_FLAGS, ptagExtendedFolderFlags

2.693 PidTagExtendedRuleMessageActions

Canonical name: PidTagExtendedRuleMessageActions

Description: Contains **action** information about named properties used in the **rule**.

Property ID: 0x0E99

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [MS-OXORULE] section 2.2.4.1.9

Consuming reference: [MS-OXCSPAM]

Alternate names: PR_EXTENDED_RULE_MSG_ACTIONS

Copyright © 2025 Microsoft Corporation

2.694 PidTagExtendedRuleMessageCondition

Canonical name: PidTagExtendedRuleMessageCondition

Description: Contains condition information about named properties used in the **rule**.

Property ID: 0x0E9A

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [MS-OXORULE] section 2.2.4.1.10

Consuming references: [MS-OXCPRPT], [MS-OXCSPAM]

Alternate names: PR_EXTENDED_RULE_MSG_CONDITION

2.695 PidTagExtendedRuleSizeLimit

Canonical name: PidTagExtendedRuleSizeLimit

Description: Contains the maximum size, in bytes, that the user is allowed to accumulate for a single extended **rule**.

Property ID: 0x0E9B

Data type: PtypInteger32, 0x0003

Area: Rules

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.1

Consuming Reference: [MS-OXORULE]

Alternate names: PR_EXTENDED_RULE_SIZE_LIMIT

2.696 PidTagFaxNumberOfPages

Canonical name: PidTagFaxNumberOfPages

Description: Contains the number of pages in a Fax object.

Property ID: 0x6804

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.7

Consuming reference: [MS-OXCMAIL]

Alternate names: InternalSchemaFaxNumberOfPages

2.697 PidTagFlagCompleteTime

Canonical name: PidTagFlagCompleteTime

Description: Specifies the date and time, in **UTC**, that the **Message object** was flagged as complete.

Copyright © 2025 Microsoft Corporation

Property ID: 0x1091

Data type: PtypTime, 0x0040

Area: Miscellaneous Properties

Defining reference: [MS-OXOFLAG] section 2.2.1.3

Consuming references: [MS-OXCMAIL], [MS-OXORMDR]

Alternate names: PR_FLAG_COMPLETE_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

2.698 PidTagFlagStatus

Canonical name: PidTagFlagStatus

Description: Specifies the flag state of the **Message object**.

Property ID: 0x1090

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [MS-OXOFLAG] section 2.2.1.1

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOCFG], [MS-OXORMDR], [MS-OXOSFLD]

Alternate names: PR_FLAG_STATUS, ptagFlagStatus

2.699 PidTagFlatUrlName

Canonical name: PidTagFlatUrlName

Description: Contains a unique identifier for an item across the **message store**.

Property ID: 0x670E

Data type: PtypString, 0x001F

Area: ExchangeAdministrative

Defining reference: [MS-XWDCAL] section 2.2.8.9

Alternate names: PR_FLAT_URL_NAME, PR_FLAT_URL_NAME_A, PR_FLAT_URL_NAME_W, ptagFlatURLName, http://schemas.microsoft.com/exchange/permanenturl

2.700 PidTagFolderAssociatedContents

Canonical name: PidTagFolderAssociatedContents

Description: Identifies all **FAI** messages in the current folder.

Property ID: 0x3610

Data type: PtypObject, 0x000D

Area: MapiContainer

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.6

Consuming references: [MS-OXCFXICS]

Alternate names: PR_FOLDER_ASSOCIATED_CONTENTS

2.701 PidTagFolderFlags

Canonical name: PidTagFolderFlags

Description: Contains a computed value to specify the type or state of a folder.

Property ID: 0x66A8

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.5

Alternate names: PR_FOLDER_FLAGS

2.702 PidTagFolderId

Canonical name: PidTagFolderId

Description: Contains the Folder ID (FID) ([MS-OXCDATA] section 2.2.1.1) of the folder.

Property ID: 0x6748

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.6

Consuming references: [MS-OXCFXICS], [MS-OXOCFG], [MS-OXCROPS], [MS-OXCTABL], [MS-OXOPFFB], [MS-OXOTASK], [MS-OXRTFEX]

Alternate names: ptagFID

2.703 PidTagFolderType

Canonical name: PidTagFolderType

Description: Specifies the type of a folder that includes the **Root folder**, Generic folder, and Search folder.

Property ID: 0x3601

Data type: PtypInteger32, 0x0003

Area: MapiContainer

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.7

Consuming references: [MS-OXCICAL], [MS-OXOSRCH]

Alternate names: PR_FOLDER_TYPE, ptagFolderType

Copyright © 2025 Microsoft Corporation

2.704 PidTagFollowupIcon

Canonical name: PidTagFollowupIcon

Description: Specifies the flag color of the **Message object**.

Property ID: 0x1095

Data type: PtypInteger32, 0x0003

Area: RenMessageFolder

Defining reference: [MS-OXOFLAG] section 2.2.1.2

Consuming references: [MS-OXCFXICS], [MS-OXOCFG], [MS-OXOSFLD]

Alternate names: PR_FOLLOWUP_ICON, ptagFollowupIcon

2.705 PidTagFreeBusyCountMonths

Canonical name: PidTagFreeBusyCountMonths

Description: Contains an integer value used to calculate the start and end dates of the range of free/busy data to be published to the **public folders**.

Property ID: 0x6869

Data type: PtypInteger32, 0x0003

Area: MessageClassDefinedTransmittable

Defining reference: [MS-OXOCAL] section 2.2.12.1

Consuming reference: [MS-OXOPFFB]

Alternate names: PR_FREEBUSY_COUNT_MONTHS

2.706 PidTagFreeBusyEntryIds

Canonical name: PidTagFreeBusyEntryIds

Description: Contains **EntryIDs** of the Delegate Information object, the free/busy message of the logged on user, and the folder with the **PidTagDisplayName** property (section 2.677) value of "Freebusy Data".

Property ID: 0x36E4

Data type: PtypMultipleBinary, 0x1102

Area: MapiContainer

Defining reference: [MS-OXOSFLD] section 2.2.6

Consuming reference: [MS-OXODLGT]

Alternate names: PR_FREEBUSY_ENTRYIDS, ptagFreeBusyEntryIds

2.707 PidTagFreeBusyMessageEmailAddress

Canonical name: PidTagFreeBusyMessageEmailAddress

Copyright © 2025 Microsoft Corporation

Description: Specifies the email address of the user or resource to whom this free/busy message applies.

Property ID: 0x6849

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference: [MS-OXOPFFB] section 2.2.1.2.12

Alternate names: PR_FREEBUSY_EMA

2.708 PidTagFreeBusyPublishEnd

Canonical name: PidTagFreeBusyPublishEnd

Description: Specifies the end time, in **UTC**, of the publishing range.

Property ID: 0x6848

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.10

Alternate names: PR_FREEBUSY_PUBLISH_END

2.709 PidTagFreeBusyPublishStart

Canonical name: PidTagFreeBusyPublishStart

Description: Specifies the start time, in **UTC**, of the publishing range.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.9

Alternate names: PR_FREEBUSY_PUBLISH_START

2.710 PidTagFreeBusyRangeTimestamp

Canonical name: PidTagFreeBusyRangeTimestamp

Description: Specifies the time, in **UTC**, that the data was published.

Property ID: 0x6868

Data type: PtypTime, 0x0040

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.11

Alternate names: PR_FREEBUSY_RANGE_TIMESTAMP

Copyright © 2025 Microsoft Corporation

2.711 PidTagFtpSite

Canonical name: PidTagFtpSite

Description: Contains the **File Transfer Protocol (FTP)** site address of the **mail user**.

Property ID: 0x3A4C

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.10.15

Alternate names: PR_FTP_SITE, PR_FTP_SITE_A, PR_FTP_SITE_W, urn:schemas:contacts:ftpsite

2.712 PidTagGatewayNeedsToRefresh

Canonical name: PidTagGatewayNeedsToRefresh

Description: This property is deprecated and SHOULD NOT be used.

Property ID: 0x6846

Data type: PtypBoolean, 0x000B

Area: MessageClassDefinedTransmittable

Defining reference: [MS-OXOPFFB] section 2.2.1.4.1

Alternate names: PR_GATEWAY_NEEDS_TO_REFRESH

2.713 PidTagGender

Canonical name: PidTagGender

Description: Contains a value that represents the **mail user's** gender.

Property ID: 0x3A4D

Data type: PtypInteger16, 0x0002

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.10.20

Alternate names: PR_GENDER, urn:schemas:contacts:gender

2.714 PidTagGeneration

Canonical name: PidTagGeneration

Description: Contains a generational abbreviation that follows the full name of the **mail user**.

Property ID: 0x3A05

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.1.2

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXVCARD]

Alternate names: PR_GENERATION, PR_GENERATION_A, PR_GENERATION_W, urn:schemas:contacts:namesuffix

2.715 PidTagGivenName

Canonical name: PidTagGivenName

Description: Contains the **mail user's** given name.

Property ID: 0x3A06

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.2

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_GIVEN_NAME, PR_GIVEN_NAME_A, PR_GIVEN_NAME_W, urn:schemas:contacts:givenName

2.716 PidTagGovernmentIdNumber

Canonical name: PidTagGovernmentIdNumber

Description: Contains a government identifier for the **mail user**.

Property ID: 0x3A07

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.10.9

Alternate names: PR_GOVERNMENT_ID_NUMBER, PR_GOVERNMENT_ID_NUMBER_A, PR_GOVERNMENT_ID_NUMBER_W, urn:schemas:contacts:governmentid

2.717 PidTagHasAttachments

Canonical name: PidTagHasAttachments

Description: Indicates whether the **Message object** contains at least one attachment.

Property ID: 0x0E1B

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties Property set

Defining reference: [MS-OXCMSG] section 2.2.1.2

Consuming references: [MS-OXCICAL], [MS-OXOCFG], [MS-XWDCAL]

Alternate names: PR_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

Copyright © 2025 Microsoft Corporation

2.718 PidTagHasDeferredActionMessages

Canonical name: PidTagHasDeferredActionMessages

Description: Indicates whether a **Message object** has a deferred **action** message associated with it.

Property ID: 0x3FEA

Data type: PtypBoolean, 0x000B

Area: Rules

Defining reference: [MS-OXORULE] section 2.2.9.1

Alternate names: PR_HAS_DAMS, ptagHasDAMs

2.719 PidTagHasNamedProperties

Canonical name: PidTagHasNamedProperties

Description: Indicates whether the **Message object** has a **named property**.

Property ID: 0x664A

Data type: PtypBoolean, 0x000B

Area: ExchangeMessageReadOnly

Defining reference: [MS-OXCMSG] section 2.2.1.39

Consuming reference: [MS-OXCFXICS]

Alternate names: PR_HAS_NAMED_PROPERTIES, ptagHasNamedProperties

2.720 PidTagHasRules

Canonical name: PidTagHasRules

Description: Indicates whether a **Folder object** has **rules**.

Property ID: 0x663A

Data type: PtypBoolean, 0x000B

Area: ExchangeFolder

Defining reference: [MS-OXORULE] section 2.2.8.1

Alternate names: PR_HAS_RULES, ptagHasRules

2.721 PidTagHierarchyChangeNumber

Canonical name: PidTagHierarchyChangeNumber

Description: Contains a number that monotonically increases every time a subfolder is added to, or deleted from, this folder.

Property ID: 0x663E

Data type: PtypInteger32, 0x0003

Copyright © 2025 Microsoft Corporation

Area: ExchangeFolder

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.8

Alternate names: PR_HIERARCHY_CHANGE_NUM

2.722 PidTagHierRev

Canonical name: PidTagHierRev

Description: Specifies the time, in **UTC**, to trigger the client in cached mode to synchronize the folder hierarchy.

Property ID: 0x4082

Data type: PtypTime, 0x0040

Area: TransportEnvelope

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.9

Alternate names: PR_HIER_REV, ptagHierRev

2.723 PidTagHobbies

Canonical name: PidTagHobbies

Description: Contains the names of the **mail user's** hobbies.

Property ID: 0x3A43

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.10.2

Consuming references: [MS-OXVCARD]

Alternate names: PR_HOBBIES, PR_HOBBIES_A, PR_HOBBIES_W, urn:schemas:contacts:hobbies

2.724 PidTagHome2TelephoneNumber

Canonical name: PidTagHome2TelephoneNumber

Description: Contains a secondary telephone number at the **mail user's** home.

Property ID: 0x3A2F

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference:[MS-OXOABK] section 2.2.4.25

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_HOME2_TELEPHONE_NUMBER, PR_HOME2_TELEPHONE_NUMBER_A, PR_HOME2_TELEPHONE_NUMBER_W, urn:schemas:contacts:homephone2

Copyright © 2025 Microsoft Corporation

2.725 PidTagHome2TelephoneNumbers

Canonical name: PidTagHome2TelephoneNumbers

Description: Contains secondary telephone numbers at the **mail user's** home.

Property ID: 0x3A2F

Data type: PtypMultipleString, 0x101F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.26

Consuming reference: [MS-OXOAB]

Alternate names: PR_HOME2_TELEPHONE_NUMBER_A_MV

2.726 PidTagHomeAddressCity

Canonical name: PidTagHomeAddressCity

Description: Contains the name of the **mail user's** home locality, such as the town or city.

Property ID: 0x3A59

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.3.2

Consuming references: [MS-OXVCARD]

Alternate names: PR_HOME_ADDRESS_CITY, PR_HOME_ADDRESS_CITY_A, PR_HOME_ADDRESS_CITY_W, urn:schemas:contacts:homeCity

2.727 PidTagHomeAddressCountry

Canonical name: PidTagHomeAddressCountry

Description: Contains the name of the **mail user's** home country/region.

Property ID: 0x3A5A

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.3.5

Consuming references: [MS-OXVCARD]

Alternate names: PR_HOME_ADDRESS_COUNTRY, PR_HOME_ADDRESS_COUNTRY_A, PR_HOME_ADDRESS_COUNTRY_W, urn:schemas:contacts:homeCountry

2.728 PidTagHomeAddressPostalCode

Canonical name: PidTagHomeAddressPostalCode

Description: Contains the postal code for the **mail user's** home postal address.

Copyright © 2025 Microsoft Corporation

Property ID: 0x3A5B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.3.4

Consuming references: [MS-OXVCARD]

Alternate names: PR_HOME_ADDRESS_POSTAL_CODE, PR_HOME_ADDRESS_POSTAL_CODE_A, PR_HOME_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:homePostalCode

2.729 PidTagHomeAddressPostOfficeBox

Canonical name: PidTagHomeAddressPostOfficeBox

Description: Contains the number or identifier of the **mail user's** home post office box.

Property ID: 0x3A5E

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.3.7

Consuming references: [MS-OXVCARD]

Alternate names: PR_HOME_ADDRESS_POST_OFFICE_BOX, PR_HOME_ADDRESS_POST_OFFICE_BOX_A, PR_HOME_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:homepostofficebox

2.730 PidTagHomeAddressStateOrProvince

Canonical name: PidTagHomeAddressStateOrProvince

Description: Contains the name of the **mail user's** home state or province.

Property ID: 0x3A5C

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.3.3

Consuming references: [MS-OXVCARD]

Alternate names: PR_HOME_ADDRESS_STATE_OR_PROVINCE, PR_HOME_ADDRESS_STATE_OR_PROVINCE_A, PR_HOME_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:homeState

2.731 PidTagHomeAddressStreet

Canonical name: PidTagHomeAddressStreet

Description: Contains the **mail user's** home street address.

Property ID: 0x3A5D

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.20

Consuming references: [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_HOME_ADDRESS_STREET, PR_HOME_ADDRESS_STREET_A, PR_HOME_ADDRESS_STREET_W, urn:schemas:contacts:homeStreet

2.732 PidTagHomeFaxNumber

Canonical name: PidTagHomeFaxNumber

Description: Contains the telephone number of the **mail user's** home fax machine.

Property ID: 0x3A25

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.2.6

Consuming references: [MS-OXVCARD]

Alternate names: PR_HOME_FAX_NUMBER, PR_HOME_FAX_NUMBER_A, PR_HOME_FAX_NUMBER_W, urn:schemas:contacts:homefax

2.733 PidTagHomeTelephoneNumber

Canonical name: PidTagHomeTelephoneNumber

Description: Contains the primary telephone number of the **mail user's** home.

Property ID: 0x3A09

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.22

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_HOME_TELEPHONE_NUMBER, PR_HOME_TELEPHONE_NUMBER_A, PR_HOME_TELEPHONE_NUMBER_W, urn:schemas:contacts:homePhone

2.734 PidTagHtml

Canonical name: PidTagHtml

Description: Contains **message body** text in **HTML** format.

Property ID: 0x1013

Data type: PtypBinary, 0x0102

Area: General Message Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXCMSG] section 2.2.1.58.9

Consuming references: [MS-OXBBODY], [MS-OXCMAIL], [MS-OXOPOST], [MS-OXORMMS], [MS-OXORSS], [MS-OXOSMMS]

Alternate names: PR_HTML, ptagHtml

2.735 PidTagICalendarEndTime

Canonical name: PidTagICalendarEndTime

Description: Contains the date and time, in **UTC**, when an appointment or **meeting** ends.

Property ID: 0x10C4

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference:[MS-XWDCAL] section 2.2.2.39

Alternate names: urn:schemas:calendar:dtend

2.736 PidTagICalendarReminderNextTime

Canonical name: PidTagICalendarReminderNextTime

Description: Contains the date and time, in UTC, for the activation of the next **reminder**.

Property ID: 0x10CA

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [MS-XWDCAL] section 2.2.2.40

Alternate names: urn:schemas:calendar:remindernexttime

2.737 PidTagICalendarStartTime

Canonical name: PidTagICalendarStartTime

Description: Contains the date and time, in **UTC**, when the appointment or **meeting** starts.

Property ID: 0x10C3

Data type: PtypTime, 0x0040

Area: Calendar Property set

Defining reference: [MS-XWDCAL] section 2.2.2.41

Alternate names: urn:schemas:calendar:dtstart

2.738 PidTagIconIndex

Canonical name: PidTagIconIndex

Copyright © 2025 Microsoft Corporation

Description: Specifies which icon is to be used by a user interface when displaying a group of **Message objects**.

Property ID: 0x1080

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.10

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOMSG], [MS-OXONOTE], [MS-OXOPOST], [MS-OXOSMMS], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_ICON_INDEX, ptagIconIndex

2.739 PidTagImportance

Canonical name: PidTagImportance

Description: Indicates the level of importance assigned by the end user to the **Message object**.

Property ID: 0x0017

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.11

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOCFG], [MS-OXODOC], [MS-OXOMSG], [MS-OXTNEF]

Alternate names: PR_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, http://schemas.microsoft.com/exchange/importance-long, http://schemas.microsoft.com/exchange/x-priority-long

2.740 PidTagInConflict

Canonical name: PidTagInConflict

Description: Specifies whether the attachment represents an alternate replica.

Property ID: 0x666C

Data type: PtypBoolean, 0x000B

Area: Conflict Note

Defining reference: [MS-OXCFXICS] section 2.2.1.4.3

Alternate names: PR_IN_CONFLICT, ptagInConflict

2.741 PidTagInitialDetailsPane

Canonical name: PidTagInitialDetailsPane

Description: Indicates which page of a **display template** to display first.

Copyright © 2025 Microsoft Corporation

Property ID: 0x3F08

Data type: PtypInteger32, 0x0003

Area: MAPI Display Tables

Defining reference: [MS-OXOABK] section 2.2.3.33

Consuming Reference: [MS-OXNSPI]

Alternate names: PR_INITIAL_DETAILS_PANE

2.742 PidTagInitials

Canonical name: PidTagInitials

Description: Contains the initials for parts of the full name of the **mail user**.

Property ID: 0x3A0A

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.3

Consuming references: [MS-OXOAB], [MS-OXOCNTC]

Alternate names: PR_INITIALS, PR_INITIALS_A, PR_INITIALS_W, urn:schemas:contacts:initials

2.743 PidTagInReplyToId

Canonical name: PidTagInReplyToId

Description: Contains the value of the original message's **PidTagInternetMessageId** property (section 2.749) value.

Property ID: 0x1042

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.13

Consuming Reference: [MS-OXCMAIL]

Alternate names: PR_IN_REPLY_TO_ID, PR_IN_REPLY_TO_ID_A, PR_IN_REPLY_TO_ID_W

2.744 PidTagInstanceKey

Canonical name: PidTagInstanceKey

Description: Contains an object on an **NSPI** server.

Property ID: 0x0FF6

Data type: PtypBinary, 0x0102

Area: Table Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOABK] section 2.2.3.6

Consuming references: [MS-OXCFXICS], [MS-OXCMSG], [MS-OXNSPI], [MS-OXOABKT]

Alternate names: PR_INSTANCE_KEY, ptagInstanceKey

2.745 PidTagInstanceNum

Canonical name: PidTagInstanceNum

Description: Contains an identifier for a single instance of a row in the table.

Property ID: 0x674E

Data type: PtypInteger32, 0x0003

Area: ProviderDefinedNonTransmittable

Defining reference: [MS-OXCTABL] section 2.2.1.2

Consuming reference: [MS-OXOPFFB]

Alternate names: ptagInstanceNum

2.746 PidTagInstID

Canonical name: PidTagInstID

Description: Contains an identifier for all instances of a row in the table.

Property ID: 0x674D

Data type: PtypInteger64, 0x0014

Area: ProviderDefinedNonTransmittable

Defining reference: [MS-OXCTABL] section 2.2.1.1

Consuming reference: [MS-OXOPFFB]

Alternate names: ptagInstID

2.747 PidTagInternetCodepage

Canonical name: PidTagInternetCodepage

Description: Indicates the code page used for the **PidTagBody** property (section 2.618) or the **PidTagBodyHtml** property (section 2.621).

Property ID: 0x3FDE

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [MS-OXCMSG] section 2.2.1.58.6

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCMSG], [MS-OXORMMS], [MS-OXORSS], [MS-OXOSMMS], [MS-OXTNEF]

Alternate names: PR_INTERNET_CPID, ptagInternetCpid

Copyright © 2025 Microsoft Corporation

2.748 PidTagInternetMailOverrideFormat

Canonical name: PidTagInternetMailOverrideFormat

Description: Indicates the encoding method and **HTML** inclusion for attachments.

Property ID: 0x5902

Data type: PtypInteger32, 0x0003

Area: MIME Properties

Defining reference: [MS-OXOMSG] section 2.2.1.11

Consuming references: [MS-OXCFXICS], [MS-OXCICAL]

Alternate names: PR_INETMAIL_OVERRIDE_FORMAT, ptagInetMailOverrideFormat

2.749 PidTagInternetMessageId

Canonical name: PidTagInternetMessageId

Description: Corresponds to the **message-id** field.

Property ID: 0x1035

Data type: PtypString, 0x001F

Area: MIME Properties

Defining reference: [MS-OXOMSG] section 2.2.1.12

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXTNEF]

Alternate names: PR_INTERNET_MESSAGE_ID, PR_INTERNET_MESSAGE_ID_A, PR_INTERNET_MESSAGE_ID_W

2.750 PidTagInternetReferences

Canonical name: PidTagInternetReferences

Description: Contains a list of message IDs that specify the messages to which this reply is related.

Property ID: 0x1039

Data type: PtypString, 0x001F

Area: MIME Properties

Defining reference: [MS-OXCMSG] section 2.2.1.26

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_INTERNET_REFERENCES, PR_INTERNET_REFERENCES_A, PR_INTERNET_REFERENCES_W

2.751 PidTagIpmAppointmentEntryId

Canonical name: PidTagIpmAppointmentEntryId

Description: Contains the **EntryID** of the **Calendar folder**.

Copyright © 2025 Microsoft Corporation

Property ID: 0x36D0

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [MS-OXOSFLD] section 2.2.3

Consuming references: [MS-OXODLGT]

Alternate names: PR_IPM_APPOINTMENT_ENTRYID

2.752 PidTagIpmArchiveEntryId

Canonical name: PidTagIpmArchiveEntryId

Description: Contains the **EntryID** of the **Archive folder**.

Property ID: 0x35FF

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [MS-OXOSFLD] section 2.2.3

Alternate names: PR_IPM_ARCHIVE_ENTRYID

2.753 PidTagIpmContactEntryId

Canonical name: PidTagIpmContactEntryId

Description: Contains the **EntryID** of the Contacts folder.

Property ID: 0x36D1

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [MS-OXOSFLD] section 2.2.3

Consuming references: [MS-OXODLGT]

Alternate names: PR_IPM_CONTACT_ENTRYID

2.754 PidTagIpmDraftsEntryId

Canonical name: PidTagIpmDraftsEntryId

Description: Contains the **EntryID** of the Drafts folder.

Property ID: 0x36D7

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [MS-OXOSFLD] section 2.2.3

Alternate names: PR_IPM_DRAFTS_ENTRYID

Copyright © 2025 Microsoft Corporation

2.755 PidTagIpmJournalEntryId

Canonical name: PidTagIpmJournalEntryId

Description: Contains the **EntryID** of the Journal folder.

Property ID: 0x36D2

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [MS-OXOSFLD] section 2.2.3

Consuming references: [MS-OXODLGT]

Alternate names: PR_IPM_JOURNAL_ENTRYID

2.756 PidTagIpmNoteEntryId

Canonical name: PidTagIpmNoteEntryId

Description: Contains the **EntryID** of the Notes folder.

Property ID: 0x36D3

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [MS-OXOSFLD] section 2.2.3

Consuming references: [MS-OXODLGT]

Alternate names: PR_IPM_NOTE_ENTRYID

2.757 PidTagIpmTaskEntryId

Canonical name: PidTagIpmTaskEntryId

Description: Contains the **EntryID** of the Tasks folder.

Property ID: 0x36D4

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [MS-OXOSFLD] section 2.2.3

Consuming references: [MS-OXODLGT]

Alternate names: PR_IPM_TASK_ENTRYID

2.758 PidTagIsdnNumber

Canonical name: PidTagIsdnNumber

Description: Contains the **Integrated Services Digital Network (ISDN)** telephone number of the **mail user**.

Copyright © 2025 Microsoft Corporation

Property ID: 0x3A2D

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.4.16

Consuming references: [MS-OXVCARD]

Alternate names: PR_ISDN_NUMBER, PR_ISDN_NUMBER_A, PR_ISDN_NUMBER_W, urn:schemas:contacts:internationalisdnnumber

2.759 PidTagJunkAddRecipientsToSafeSendersList

Canonical name: PidTagJunkAddRecipientsToSafeSendersList

Description: Indicates whether email **recipients** are to be added to the safe senders list.

Property ID: 0x6103

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [MS-OXCSPAM] section 2.2.2.1

Alternate names: PR_JUNK_ADD_RECIPS_TO_SSL

2.760 PidTagJunkIncludeContacts

Canonical name: PidTagJunkIncludeContacts

Description: Indicates whether email addresses of the **contacts** in the Contacts folder are treated in a special way with respect to the **spam filter**.

Property ID: 0x6100

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [MS-OXCSPAM] section 2.2.2.2

Alternate names: PR_JUNK_INCLUDE_CONTACTS

2.761 PidTagJunkPermanentlyDelete

Canonical name: PidTagJunkPermanentlyDelete

Description: Indicates whether messages identified as **spam** can be permanently deleted.

Property ID: 0x6102

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [MS-OXCSPAM] section 2.2.2.3

Alternate names: PR_JUNK_PERMANENTLY_DELETE

Copyright © 2025 Microsoft Corporation

2.762 PidTagJunkPhishingEnableLinks

Canonical name: PidTagJunkPhishingEnableLinks

Description: Indicated whether the **phishing** stamp on a message is to be ignored.

Property ID: 0x6107

Data type: PtypBoolean, 0x000B

Area: Spam

Defining reference: [MS-OXCSPAM] section 2.2.2.4

Consuming reference: [MS-OXPHISH]

Alternate names: PR_JUNK_PHISHING_ENABLE_LINKS

2.763 PidTagJunkThreshold

Canonical name: PidTagJunkThreshold

Description: Indicates how aggressively incoming email is to be sent to the Junk Email folder.

Property ID: 0x6101

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [MS-OXCSPAM] section 2.2.2.5

Alternate names: PR_JUNK_THRESHOLD

2.764 PidTagKeyword

Canonical name: PidTagKeyword

Description: Contains a keyword that identifies the **mail user** to the mail user's system administrator.

Property ID: 0x3A0B

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.32

Alternate names: PR_KEYWORD, PR_KEYWORD_A, PR_KEYWORD_W

2.765 PidTagLanguage

Canonical name: PidTagLanguage

Description: Contains a value that indicates the language in which the messaging user is writing messages.

Property ID: 0x3A0C

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.4

Alternate names: PR_LANGUAGE, PR_LANGUAGE_A, PR_LANGUAGE_W, urn:schemas:contacts:language

2.766 PidTagLastModificationTime

Canonical name: PidTagLastModificationTime

Description: Contains the time, in **UTC**, of the last modification to the object.

Property ID: 0x3008

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [MS-OXCMSG] section 2.2.2.2

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCPRPT], [MS-OXTNEF], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCROPS], [MS-OXOABK], [MS-OXOCFG], [MS-OXORMDR], [MS-OXORMMS], [MS-OXVCARD], [MS-XWDCAL]

Alternate names: PR_LAST_MODIFICATION_TIME, ptagLastModificationTime, urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

2.767 PidTagLastModifierEntryId

Canonical name: PidTagLastModifierEntryId

Description: Specifies the Address Book **EntryID** of the last user to modify the contents of the message.

Property ID: 0x3FFB

Data type: PtypBinary, 0x0102

Area: History Properties

Defining reference: [MS-OXCMSG] section 2.2.1.32

Consuming reference: [MS-OXTNEF]

Alternate names: PR_LAST_MODIFIER_ENTRYID, ptagLastModifierEntryId

2.768 PidTagLastModifierName

Canonical name: PidTagLastModifierName

Description: Contains the name of the last **mail user** to change the **Message object**.

Property ID: 0x3FFA

Data type: PtypString, 0x001F

Area: History Properties

Defining reference: [MS-OXCPRPT] section 2.2.1.5

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCMSG], [MS-OXTNEF]

Alternate names: PR_LAST_MODIFIER_NAME, PR_LAST_MODIFIER_NAME_A, ptagLastModifierName, PR_LAST_MODIFIER_NAME_W

2.769 PidTagLastVerbExecuted

Canonical name: PidTagLastVerbExecuted

Description: Specifies the last verb executed for the message item to which it is related.

Property ID: 0x1081

Data type: PtypInteger32, 0x0003

Area: History Properties

Defining reference: [MS-OXOMSG] section 2.2.1.14

Consuming reference: [MS-OXCICAL]

Alternate names: PR_LAST_VERB_EXECUTED, ptagLastVerbExecuted

2.770 PidTagLastVerbExecutionTime

Canonical name: PidTagLastVerbExecutionTime

Description: Contains the date and time, in **UTC**, during which the operation represented in the **PidTagLastVerbExecuted** property (section 2.769) took place.

Property ID: 0x1082

Data type: PtypTime, 0x0040

Area: History Properties

Defining reference: [MS-OXOMSG] section 2.2.1.15

Consuming Reference: [MS-OXCICAL]

Alternate names: PR_LAST_VERB_EXECUTION_TIME, ptagLastVerbExecutionTime

2.771 PidTagListHelp

Canonical name: PidTagListHelp

Description: Contains a **URI** that provides detailed help information for the mailing list from which an email message was sent.

Property ID: 0x1043

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

Defining reference: [MS-OXOMSG] section 2.2.1.81

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_LIST_HELP, PR_LIST_HELP_A, PR_LIST_HELP_W

Copyright © 2025 Microsoft Corporation

2.772 PidTagListSubscribe

Canonical name: PidTagListSubscribe

Description: Contains the **URI** that subscribes a **recipient** to a message's associated mailing list.

Property ID: 0x1044

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

Defining reference: [MS-OXOMSG] section 2.2.1.82

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_LIST_SUBSCRIBE, PR_LIST_SUBSCRIBE_A, PR_LIST_SUBSCRIBE_W

2.773 PidTagListUnsubscribe

Canonical name: PidTagListUnsubscribe

Description: Contains the **URI** that unsubscribes a **recipient** from a message's associated mailing list.

Property ID: 0x1045

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

Defining reference: [MS-OXOMSG] section 2.2.1.83

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_LIST_UNSUBSCRIBE, PR_LIST_UNSUBSCRIBE_A, PR_LIST_UNSUBSCRIBE_W

2.774 PidTagLocalCommitTime

Canonical name: PidTagLocalCommitTime

Description: Specifies the time, in **UTC**, that a **Message object** or **Folder object** was last changed.

Property ID: 0x6709

Data type: PtypTime, 0x0040

Area: Server

Defining references: [MS-OXCMSG] section 2.2.1.49; [MS-OXCFOLD] section 2.2.2.2.1.13

Alternate names: PR_LOCAL_COMMIT_TIME, ptagLocalCommitTime

2.775 PidTagLocalCommitTimeMax

Canonical name: PidTagLocalCommitTimeMax

Description: Contains the time of the most recent message change within the folder container, excluding messages changed within subfolders.

Property ID: 0x670A

Copyright © 2025 Microsoft Corporation

Data type: PtypTime, 0x0040

Area: Server

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.14

Consuming Reference: [MS-OXCFXICS]

Alternate names: PR_LOCAL_COMMIT_TIME_MAX, ptagLocalCommitTimeMax

2.776 PidTagLocaleId

Canonical name: PidTagLocaleId

Description: Contains the **Logon object** LocaleID.

Property ID: 0x66A1

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.12

Consuming references: [MS-OXCMSG]

Alternate names: PR_LOCALE_ID, ptagLocaleId

2.777 PidTagLocality

Canonical name: PidTagLocality

Description: Contains the name of the **mail user's** locality, such as the town or city.

Property ID: 0x3A27

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.16

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_LOCALITY, PR_LOCALITY_A, PR_LOCALITY_W, PR_BUSINESS_ADDRESS_LOCALITY, PR_BUSINESS_ADDRESS_LOCALITY_A, PR_BUSINESS_ADDRESS_LOCALITY_W, urn:schemas:contacts:mailingcity

2.778 PidTagLocation

Canonical name: PidTagLocation

Description: Contains the location of the **mail user**.

Property ID: 0x3A0D

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.5

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXOCAL]

Alternate names: PR_LOCATION, PR_LOCATION_A, PR_LOCATION_W, urn:schemas:contacts:location

2.779 PidTagMailboxOwnerEntryId

Canonical name: PidTagMailboxOwnerEntryId

Description: Contains the **EntryID** in the **Global Address List (GAL)** of the owner of the **mailbox**.

Property ID: 0x661B

Data type: PtypBinary, 0x0102

Area: Message Store Properties

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.7

Consuming references: [MS-OXOCAL], [MS-OXOPFFB]

Alternate names: PR_MAILBOX_OWNER_ENTRYID, ptagMailboxOwnerEntryId

2.780 PidTagMailboxOwnerName

Canonical name: PidTagMailboxOwnerName

Description: Contains the **display name** of the owner of the **mailbox**.

Property ID: 0x661C

Data type: PtypString, 0x001F

Area: Message Store Properties

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.8

Consuming reference: [MS-OXOCAL]

Alternate names: PR_MAILBOX_OWNER_NAME, PR_MAILBOX_OWNER_NAME_A, ptagMailboxOwnerName, PR_MAILBOX_OWNER_NAME_W

2.781 PidTagManagerName

Canonical name: PidTagManagerName

Description: Contains the name of the **mail user's** manager.

Property ID: 0x3A4E

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.6.6

Consuming references: [MS-OXVCARD]

Alternate names: PR_MANAGER_NAME, PR_MANAGER_NAME_A, PR_MANAGER_NAME_W, urn:schemas:contacts:manager

Copyright © 2025 Microsoft Corporation

2.782 PidTagMappingSignature

Canonical name: PidTagMappingSignature

Description: A 16-byte constant that is present on all **Address Book objects**, but is not present on objects in an offline address book.

Property ID: 0x0FF8

Data type: PtypBinary, 0x0102

Area: Miscellaneous Properties

Defining reference: [MS-OXOABK] section 2.2.3.32

Consuming reference: [MS-OXNSPI]

Alternate names: PR_MAPPING_SIGNATURE, ptagMappingSignature

2.783 PidTagMaximumSubmitMessageSize

Canonical name: PidTagMaximumSubmitMessageSize

Description: Maximum size, in kilobytes, of a message that a user is allowed to submit for transmission to another user.

Property ID: 0x666D

Data type: PtypInteger32, 0x0003

Area: Message Store Properties

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.2

Alternate names: PR_MAX_SUBMIT_MESSAGE_SIZE

2.784 PidTagMemberId

Canonical name: PidTagMemberId

Description: Contains a unique identifier that the messaging server generates for each user.

Property ID: 0x6671

Data type: PtypInteger64, 0x0014

Area: Access Control Properties

Defining reference: [MS-OXCPERM] section 2.2.5

Alternate names: PR_MEMBER_ID, ptagMemberId

2.785 PidTagMemberName

Canonical name: PidTagMemberName

Description: Contains the user-readable name of the user.

Property ID: 0x6672

Data type: PtypString, 0x001F

Copyright © 2025 Microsoft Corporation

Area: Access Control Properties

Defining reference: [MS-OXCPERM] section 2.2.6

Alternate names: PR_MEMBER_NAME, PR_MEMBER_NAME_A, ptagMemberName, PR_MEMBER_NAME_W

2.786 PidTagMemberRights

Canonical name: PidTagMemberRights

Description: Contains the **permissions** for the specified user.

Property ID: 0x6673

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [MS-OXCPERM] section 2.2.7

Consuming references: [MS-OXCFOLD], [MS-OXODLGT]

Alternate names: PR_MEMBER_RIGHTS, ptagMemberRights

2.787 PidTagMessageAttachments

Canonical name: PidTagMessageAttachments

Description: Identifies all attachments to the current message.

Property ID: 0x0E13

Data type: PtypObject, 0x000D

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.1.52

Consuming references: [MS-OXCDATA], [MS-OXCFXICS]

Alternate names: PR_MESSAGE_ATTACHMENTS, ptagMessageAttachments

2.788 PidTagMessageCcMe

Canonical name: PidTagMessageCcMe

Descripton: Indicates that the receiving **mailbox** owner is a **carbon copy (Cc) recipient** of this email message.

Property ID: 0x0058

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.18

Consuming reference: [MS-OXTNEF]

Alternate names: PR_MESSAGE_CC_ME, ptagMessageCcMe

Copyright © 2025 Microsoft Corporation

2.789 PidTagMessageClass

Canonical name: PidTagMessageClass

Description: Denotes the specific type of the **Message object**.

Property ID: 0x001A

Data type: PtypString, 0x001F

Area: Common Property set

Defining reference: [MS-OXCMSG] section 2.2.1.3

Consuming references: [MS-OXCFOLD], [MS-OXODLGT], [MS-OXCDATA], [MS-OXCFXICS], [MS-OXBBODY], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCROPS], [MS-OXOCAL], [MS-OXOCFG], [MS-OXOCNTC], [MS-OXODOC], [MS-OXOJRNL], [MS-OXOMSG], [MS-OXONOTE], [MS-OXOPFFB], [MS-OXOPOST], [MS-OXORMDR], [MS-OXORSS], [MS-OXORULE], [MS-OXOSFLD], [MS-OXOSMIME], [MS-OXOSMMS], [MS-OXOSRCH], [MS-OXOTASK], [MS-OXOUM], [MS-OXSHARE], [MS-OXTNEF], [MS-XWDCAL]

Alternate names: PR_MESSAGE_CLASS, PR_MESSAGE_CLASS_A, ptagMessageClass, PR_MESSAGE_CLASS_W, http://schemas.microsoft.com/exchange/outlookmessageclasshttp://schemas.microsoft.com/exchange/outlookmessageclass

2.790 PidTagMessageCodepage

Canonical name: PidTagMessageCodepage

Description: Specifies the code page used to encode the **non-Unicode** string properties on this **Message object**.

Property ID: 0x3FFD

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXCMSG] section 2.2.1.4

Consuming references: [MS-OXTNEF] [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXPFOAB]

Alternate names: PR_MESSAGE_CODEPAGE

2.791 PidTagMessageDeliveryTime

Canonical name: PidTagMessageDeliveryTime

Description: Specifies the time (in **UTC**) when the server received the message.

Property ID: 0x0E06

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [MS-OXOMSG] section 2.2.3.9

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCTABL], [MS-OXOCFG], [MS-OXODOC], [MS-OXOFLAG], [MS-OXPROTO], [MS-OXTNEF], [MS-OXORSS]

Alternate names: PR_MESSAGE_DELIVERY_TIME, urn:schemas:httpmail:datereceived

2.792 PidTagMessageEditorFormat

Canonical name: PidTagMessageEditorFormat

Description: Specifies the format that an email editor can use for editing the **message body**.

Property ID: 0x5909

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [MS-OXOMSG] section 2.2.1.78

Consuming references: [MS-OXCFXICS], [MS-OXTNEF]

Alternate names: PR_MSG_EDITOR_FORMAT, ptagMsgEditorFormat

2.793 PidTagMessageFlags

Canonical name: PidTagMessageFlags

Description: Specifies the status of the **Message object**.

Property ID: 0x0E07

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.6

Consuming references: [MS-OXOMSG], [MS-OXTNEF] [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXORMDR], [MS-OXORSS], [MS-OXORULE], [MS-OXOSFLD], [MS-OXOSMMS]

Alternate names: PR_MESSAGE_FLAGS, ptagMessageFlags

2.794 PidTagMessageHandlingSystemCommonName

Canonical name: PidTagMessageHandlingSystemCommonName

Description: Contains the **common name** of a messaging user for use in a message header.

Property ID: 0x3A0F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.33

Alternate names: PR_MHS_COMMON_NAME, PR_MHS_COMMON_NAME_A, PR_MHS_COMMON_NAME_W, urn:schemas:contacts:dn

Copyright © 2025 Microsoft Corporation

2.795 PidTagMessageLocaleId

Canonical name: PidTagMessageLocaleId

Description: Contains the Windows Locale ID of the end-user who created this message.

Property ID: 0x3FF1

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [MS-OXCMSG] section 2.2.1.5

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOMSG], [MS-OXTNEF]

Alternate names: PR_MESSAGE_LOCALE_ID

2.796 PidTagMessageRecipientMe

Canonical name: PidTagMessageRecipientMe

Description: Indicates that the receiving **mailbox** owner is a primary or a **carbon copy (Cc) recipient** of this email message.

Property ID: 0x0059

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.19

Consuming Reference: [MS-OXTNEF]

Alternate names: PR_MESSAGE_RECIP_ME, ptagMessageRecipMe

2.797 PidTagMessageRecipients

Canonical name: PidTagMessageRecipients

Description: Identifies all of the **recipients** of the current message.

Property ID: 0x0E12

Data type: PtypObject, 0x000D

Area: Address Properties

Defining reference: [MS-OXCMSG] section 2.2.1.47

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCSPAM], [MS-OXTNEF]

Alternate names: PR_MESSAGE_RECIPIENTS, ptagMessageRecipients

2.798 PidTagMessageSize

Canonical name: PidTagMessageSize

Description: Contains the size, in bytes, consumed by the **Message object** on the server.

Copyright © 2025 Microsoft Corporation

Property ID: 0x0E08

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.10

Consuming references: [MS-OXCSTOR], [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMSG], [MS-OXOCFG], [MS-OXPFOAB]

Alternate names: PR_MESSAGE_SIZE, ptagMessageSize

2.799 PidTagMessageSizeExtended

Canonical name: PidTagMessageSizeExtended

Description: Specifies the 64-bit version of the **PidTagMessageSize** property (section 2.798).

Property ID: 0x0E08

Data type: PtypInteger64, 0x0014

Area: General Message Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.11

Consuming reference: [MS-OXCSTOR]

Alternate names: PR_MESSAGE_SIZE_EXTENDED, ptagMessageSizeExtended

2.800 PidTagMessageStatus

Canonical name: PidTagMessageStatus

Description: Specifies the status of a message in a **contents table**.

Property ID: 0x0E17

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.8

Consuming references: [MS-OXCFXICS]

Alternate names: PR_MSG_STATUS, ptagMsgStatus

2.801 PidTagMessageSubmissionId

Canonical name: PidTagMessageSubmissionId

Description: Contains a message identifier assigned by a message transfer agent.

Property ID: 0x0047

Data type: PtypBinary, 0x0102

Area: Email

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOMSG] section 2.2.1.79

Consuming references: [MS-OXTNEF]

Alternate names: PR_MESSAGE_SUBMISSION_ID, ptagMessageSubmissionId

2.802 PidTagMessageToMe

Canonical name: PidTagMessageToMe

Description: Indicates that the receiving **mailbox** owner is one of the **primary recipients** of this email message.

Property ID: 0x0057

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.17

Consuming reference: [MS-OXTNEF]

Alternate names: PR_MESSAGE_TO_ME, ptagMessageToMe

2.803 PidTagMid

Canonical name: PidTagMid

Description: Contains a value that contains the MID of the message currently being synchronized.

Property ID: 0x674A

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [MS-OXCFXICS] section 2.2.1.2.1

Consuming references: [MS-OXCMSG], [MS-OXOCFG], [MS-OXCTABL], [MS-OXOCAL], [MS-OXOCNTC], [MS-OXOPFFB], [MS-OXOTASK], [MS-OXPROTO], [MS-OXRTFEX], [MS-OXVCARD], [MS-XWDCAL]

Alternate names: ptagMID, http://schemas.microsoft.com/exchange/mid

2.804 PidTagMiddleName

Canonical name: PidTagMiddleName

Description: Specifies the middle name(s) of the **contact**.

Property ID: 0x3A44

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.1.5

Consuming references: [MS-OXVCARD]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_MIDDLE_NAME, PR_MIDDLE_NAME_A, PR_MIDDLE_NAME_W, urn:schemas:contacts:middlename

2.805 PidTagMimeSkeleton

Canonical name: PidTagMimeSkeleton

Description: Contains the top-level **MIME** message headers, all MIME message **body part** headers, and body part content that is not already converted to **Message object** properties, including attachments.

Property ID: 0x64F0

Data type: PtypBinary, 0x0102

Area: MIME properties

Defining reference: [MS-OXCMSG] section 2.2.1.28

Consuming reference: [MS-OXCMAIL]

Alternate names: ptagMimeSkeleton

2.806 PidTagMobileTelephoneNumber

Canonical name: PidTagMobileTelephoneNumber

Description: Contains the **mail user's** cellular telephone number.

Property ID: 0x3A1C

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.27

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_MOBILE_TELEPHONE_NUMBER, PR_MOBILE_TELEPHONE_NUMBER_A, PR_MOBILE_TELEPHONE_NUMBER_W, urn:schemas:contacts:mobile

2.807 PidTagNativeBody

Canonical name: PidTagNativeBody

Description: Indicates the best available format for storing the **message body**.

Property ID: 0x1016

Data type: PtypInteger32, 0x0003

Area: BestBody

Defining reference: [MS-OXCMSG] section 2.2.1.58.2

Consuming Reference: [MS-OXBBODY]

Alternate names: PR_NATIVE_BODY_INFO, ptagNativeBodyInfo

Copyright © 2025 Microsoft Corporation

2.808 PidTagNextSendAcct

Canonical name: PidTagNextSendAcct

Description: Specifies the server that a client is currently attempting to use to send email.

Property ID: 0x0E29

Data type: PtypString, 0x001F

Area: Outlook Application

Defining reference: [MS-OXOMSG] section 2.2.1.65

Consuming Reference: [MS-OXCICAL]

Alternate names: PR_NEXT_SEND_ACCT

2.809 PidTagNickname

Canonical name: PidTagNickname

Description: Contains the **mail user's** nickname.

Property ID: 0x3A4F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.1.1

Consuming references: [MS-OXVCARD]

Alternate names: PR_NICKNAME, PR_NICKNAME_A, PR_NICKNAME_W, urn:schemas:contacts:nickname

2.810 PidTagNonDeliveryReportDiagCode

Canonical name: PidTagNonDeliveryReportDiagCode

Description: Contains the diagnostic code for a delivery status notification, as specified in [RFC3464].

Property ID: 0x0C05

Data type: PtypInteger32, 0x0003

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.2.30

Consuming references: [MS-OXCMAIL]

Alternate names: PR_NDR_DIAG_CODE, ptagNonDeliveryDiagCode

2.811 PidTagNonDeliveryReportReasonCode

Canonical name: PidTagNonDeliveryReportReasonCode

Description: Contains an integer value that indicates a reason for delivery failure.

Copyright © 2025 Microsoft Corporation

Property ID: 0x0C04

Data type: PtypInteger32, 0x0003

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.2.31

Consuming references: [MS-OXCMAIL]

Alternate names: PR_NDR_REASON_CODE, ptagNDRReasonCode

2.812 PidTagNonDeliveryReportStatusCode

Canonical name: PidTagNonDeliveryReportStatusCode

Description: Contains the value of the Status field for a delivery status notification, as specified in [RFC3464].

Property ID: 0x0C20

Data type: PtypInteger32, 0x0003

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.2.32

Consuming references: [MS-OXCMAIL]

Alternate names: PR_NDR_STATUS_CODE, ptagNDRStatusCode

2.813 PidTagNonReceiptNotificationRequested

Canonical Name: PidTagNonReceiptNotificationRequested

Description: Specifies whether the client sends a non-read receipt.

Property ID: 0x0C06

Data type: PtypBoolean, 0x000B

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.31

Alternate names: PR_NON_RECEIPT_NOTIFICATION_REQUESTED

2.814 PidTagNormalizedSubject

Canonical name: PidTagNormalizedSubject

Description: Contains the normalized subject of the message.

Property ID: 0x0E1D

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.10

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCPRPT], [MS-OXOCAL], [MS-OXOCFG], [MS-OXOCNTC], [MS-OXODLGT], [MS-OXOFLAG], [MS-OXOMSG], [MS-OXONOTE], [MS-OXOPFFB], [MS-OXOPOST], [MS-OXORMDR], [MS-OXORSS], [MS-OXOSMMS], [MS-OXSHARE], [MS-OXTNEF], [MS-OXVCARD], [MS-XWDCAL]

Alternate names: PR_NORMALIZED_SUBJECT, PR_NORMALIZED_SUBJECT_A, ptagNormalizedSubject, PR_NORMALIZED_SUBJECT_W, urn:schemas:httpmail:normalizedsubject

2.815 PidTagObjectType

Canonical name: PidTagObjectType

Description: Indicates the type of **Server object**.

Property ID: 0x0FFE

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [MS-OXCPRPT] section 2.2.1.7

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXCMSG], [MS-OXNSPI], [MS-OXOAB], [MS-OXOABK], [MS-OXOMSG], [MS-OXOSRCH]

Alternate names: PR_OBJECT_TYPE, ptagObjectType

2.816 PidTagOfficeLocation

Canonical name: PidTagOfficeLocation

Description: Contains the **mail user's** office location.

Property ID: 0x3A19

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.5

Consuming references: [MS-OXNSPI], [MS-OXOAB], [MS-OXOCNTC]

Alternate names: PR_OFFICE_LOCATION, PR_OFFICE_LOCATION_A, PR_OFFICE_LOCATION_W, urn:schemas:contacts:roomnumber

2.817 PidTagOfflineAddressBookContainerGuid

Canonical name: PidTagOfflineAddressBookContainerGuid

Description: A string-formatted **GUID** that represents the **address list** container object.

Property ID: 0x6802

Data type: PtypString8, 0x001E

Area: Offline Address Book Properties

Defining reference: [MS-OXOAB] section 2.12.1

Copyright © 2025 Microsoft Corporation

Alternate names: PR_OAB_CONTAINER_GUID, PR_OAB_CONTAINER_GUID_W

2.818 PidTagOfflineAddressBookDistinguishedName

Canonical name: PidTagOfflineAddressBookDistinguishedName

Description: Contains the **DN** of the **address list** that is contained in the OAB message.

Property ID: 0x6804

Data type: PtypString8, 0x001E

Area: Offline Address Book Properties

Defining reference: [MS-OXOAB] section 2.12.2

Alternate names: PR_OAB_DN, PR_OAB_DN_W

2.819 PidTagOfflineAddressBookMessageClass

Canonical name: PidTagOfflineAddressBookMessageClass

Description: Contains the **message class** for full OAB messages.

Property ID: 0x6803

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

Defining reference: [MS-OXPFOAB] section 2.2.2.1.1

Alternate names: PR_OAB_MESSAGE_CLASS

2.820 PidTagOfflineAddressBookName

Canonical name: PidTagOfflineAddressBookName

Description: Contains the **display name** of the **address list**.

Property ID: 0x6800

Data type: PtypString, 0x001F

Area: Offline Address Book Properties

Defining reference: [MS-OXOAB] section 2.12.3

Alternate names: PR_OAB_NAME, PR_OAB_NAME_W

2.821 PidTagOfflineAddressBookSequence

Canonical name: PidTagOfflineAddressBookSequence

Description: Contains the sequence number of the OAB.

Property ID: 0x6801

Data type: PtypInteger32, 0x0003

Copyright © 2025 Microsoft Corporation

Area: Offline Address Book Properties

Defining reference: [MS-OXOAB] section 2.12.4

Alternate names: PR_OAB_SEQUENCE

2.822 PidTagOfflineAddressBookTruncatedProperties

Canonical name: PidTagOfflineAddressBookTruncatedProperties

Description: Contains a list of the property tags that have been truncated or limited by the server.

Property ID: 0x6805

Data type: PtypMultipleInteger32, 0x1003

Area: Offline Address Book Properties

Defining reference: [MS-OXOAB] section 2.9.2.2

Alternate names: PR_OAB_TRUNCATED_PROPS

2.823 PidTagOrdinalMost

Canonical name: PidTagOrdinalMost

Description: Contains a positive number whose negative is less than or equal to the value of the **PidLidTaskOrdinal** property (section 2.327) of all of the **Task objects** in the folder.

Property ID: 0x36E2

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [MS-OXOTASK] section 2.2.1.1

Alternate names: PR_ORDINAL_MOST

2.824 PidTagOrganizationalIdNumber

Canonical name: PidTagOrganizationalIdNumber

Description: Contains an identifier for the **mail user** used within the mail user's organization.

Property ID: 0x3A10

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.10.7

Alternate names: PR_ORGANIZATIONAL_ID_NUMBER, PR_ORGANIZATIONAL_ID_NUMBER_A, PR_ORGANIZATIONAL_ID_NUMBER_W, urn:schemas:contacts:employeenumber

2.825 PidTagOriginalAuthorEntryId

Canonical name: PidTagOriginalAuthorEntryId

Copyright © 2025 Microsoft Corporation

Description: Contains an address book **EntryID** structure ([MS-OXCDATA] section 2.2.5.2) and is defined in report messages to identify the user who sent the original message.

Property ID: 0x004C

Data type: PtypBinary, 0x0102

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.32

Alternate names: PR_ORIGINAL_AUTHOR_ENTRYID

2.826 PidTagOriginalAuthorName

Canonical name: PidTagOriginalAuthorName

Description: Contains the display name of the sender of the original message referenced by a report message.

Property ID: 0x004D

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.33

Alternate names: PR_ORIGINAL_AUTHOR_NAME_W

2.827 PidTagOriginalDeliveryTime

Canonical name: PidTagOriginalDeliveryTime

Description: Contains the delivery time, in **UTC**, from the original message.

Property ID: 0x0055

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.2

Alternate names: PR_ORIGINAL_DELIVERY_TIME, ptagOriginalDeliveryTime

2.828 PidTagOriginalDisplayBcc

Canonical name: PidTagOriginalDisplayBcc

Description: Contains the value of the **PidTagDisplayBcc** property (section 2.675) from the original message.

Property ID: 0x0072

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.5

Copyright © 2025 Microsoft Corporation

Alternate names: PR_ORIGINAL_DISPLAY_BCC, PR_ORIGINAL_DISPLAY_BCC_A, ptagOriginalDisplayBcc, PR_ORIGINAL_DISPLAY_BCC_W, http://schemas.microsoft.com/exchange/originaldisplaybcc

2.829 PidTagOriginalDisplayCc

Canonical name: PidTagOriginalDisplayCc

Description: Contains the value of the **PidTagDisplayCc** property(section 2.676) from the original message.

Property ID: 0x0073

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.4

Alternate names: PR_ORIGINAL_DISPLAY_CC, PR_ORIGINAL_DISPLAY_CC_A, ptagOriginalDisplayCc, PR_ORIGINAL_DISPLAY_CC_W, http://schemas.microsoft.com/exchange/originaldisplaycc, http://schemas.microsoft.com/mapi/original_display_cc

2.830 PidTagOriginalDisplayTo

Canonical name: PidTagOriginalDisplayTo

Description: Contains the value of the **PidTagDisplayTo** property (section 2.679) from the original message.

Property ID: 0x0074

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.3

Alternate names: PR_ORIGINAL_DISPLAY_TO, PR_ORIGINAL_DISPLAY_TO_A, ptagOriginalDisplayTo, PR_ORIGINAL_DISPLAY_TO_W, http://schemas.microsoft.com/exchange/originaldisplayto, http://schemas.microsoft.com/mapi/original_display_to

2.831 PidTagOriginalEntryId

Canonical name: PidTagOriginalEntryId

Description: Contains the original **EntryID** of an object.

Property ID: 0x3A12

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [MS-OXCFXICS] section 2.2.1.2.9

Alternate names: PR_ORIGINAL_ENTRYID, ptagOriginalEntryId

Copyright © 2025 Microsoft Corporation

2.832 PidTagOriginalMessageClass

Canonical name: PidTagOriginalMessageClass

Description: Designates the **PidTagMessageClass** property ([MS-OXCMSG] section 2.2.1.3) from the original message.

Property ID: 0x004B

Data type: PtypString, 0x001F

Area: Secure Messaging Properties

Defining reference: [MS-OXOMSG] section 2.2.1.86

Consuming reference: [MS-OXTNEF]

Alternate names: PR_ORIG_MESSAGE_CLASS, PR_ORIG_MESSAGE_CLASS_A, PR_ORIG_MESSAGE_CLASS_W

2.833 PidTagOriginalMessageId

Canonical name: PidTagOriginalMessageId

Description: Contains the message ID of the original message included in replies or resent messages.

Property ID: 0x1046

Data type: PtypString, 0x001F

Area: Mail

Defining reference: [MS-OXOMSG] section 2.2.1.85

Consuming reference: [MS-OXCMAIL]

Alternate names: ptagOriginalInternetMessageID, OriginalMessageId

2.834 PidTagOriginalSenderAddressType

Canonical name: PidTagOriginalSenderAddressType

Description: Contains the value of the original message sender's **PidTagSenderAddressType** property (section 2.1002).

Property ID: 0x0066

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.6

Alternate names: PR_ORIGINAL_SENDER_ADDRTYPE, PR_ORIGINAL_SENDER_ADDRTYPE_A, ptagOriginalSenderAddrType, PR_ORIGINAL_SENDER_ADDRTYPE_W

2.835 PidTagOriginalSenderEmailAddress

Canonical name: PidTagOriginalSenderEmailAddress

Copyright © 2025 Microsoft Corporation

Description: Contains the value of the original message sender's **PidTagSenderEmailAddress** property (section 2.1003).

Property ID: 0x0067

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.7

Alternate names: PR_ORIGINAL_SENDER_EMAIL_ADDRESS, PR_ORIGINAL_SENDER_EMAIL_ADDRESS_A, PR_ORIGINAL_SENDER_EMAIL_ADDRESS_W

2.836 PidTagOriginalSenderEntryId

Canonical name: PidTagOriginalSenderEntryId

Description: Contains an address book **EntryID** that is set on delivery report messages.

Property ID: 0x005B

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.8

Alternate names: PR_ORIGINAL_SENDER_ENTRYID, ptagOriginalSenderEntryId

2.837 PidTagOriginalSenderName

Canonical name: PidTagOriginalSenderName

Description: Contains the value of the original message sender's **PidTagSenderName** property (section 2.1006), and is set on delivery report messages.

Property ID: 0x005A

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.9

Alternate names: PR_ORIGINAL_SENDER_NAME, PR_ORIGINAL_SENDER_NAME_A, ptagOriginalSenderName, PR_ORIGINAL_SENDER_NAME_W, http://schemas.microsoft.com/exchange/originalsendername

2.838 PidTagOriginalSenderSearchKey

Canonical name: PidTagOriginalSenderSearchKey

Description: Contains an address book search key set on the original email message.

Property ID: 0x005C

Data type: PtypBinary, 0x0102

Area: General Message Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOMSG] section 2.2.2.10

Alternate names: PR_ORIGINAL_SENDER_SEARCH_KEY, ptagOriginalSenderSearchKey

2.839 PidTagOriginalSensitivity

Canonical name: PidTagOriginalSensitivity

Description: Contains the sensitivity value of the original email message.

Property ID: 0x002E

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.1.22

Consuming reference: [MS-OXCICAL]

Alternate names: PR_ORIGINAL_SENSITIVITY, ptagOriginalSensitivity

2.840 PidTagOriginalSentRepresentingAddressType

Canonical name: PidTagOriginalSentRepresentingAddressType

Description: Contains the **address type** of the end user who is represented by the original email message sender.

Property ID: 0x0068

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.11

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE, PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_A, ptagOriginalSentRepresentingAddrType, PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_W

2.841 PidTagOriginalSentRepresentingEmailAddress

Canonical name: PidTagOriginalSentRepresentingEmailAddress

Description: Contains the email address of the end user who is represented by the original email message sender.

Property ID: 0x0069

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.12

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS, PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_A, PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_W

Copyright © 2025 Microsoft Corporation

2.842 PidTagOriginalSentRepresentingEntryId

Canonical name: PidTagOriginalSentRepresentingEntryId

Description: Identifies an address book **EntryID** that contains the entry identifier of the end user who is represented by the original message sender.

Property ID: 0x005E

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.13

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ENTRYID, ptagOriginalSentRepresentingEntryId

2.843 PidTagOriginalSentRepresentingName

Canonical name: PidTagOriginalSentRepresentingName

Description: Contains the **display name** of the end user who is represented by the original email message sender.

Property ID: 0x005D

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.14

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_NAME, PR_ORIGINAL_SENT_REPRESENTING_NAME_A, ptagOriginalSentRepresentingName, PR_ORIGINAL_SENT_REPRESENTING_NAME_W

2.844 PidTagOriginalSentRepresentingSearchKey

Canonical name: PidTagOriginalSentRepresentingSearchKey

Description: Identifies an address book search key that contains the SearchKey of the end user who is represented by the original message sender.

Property ID: 0x005F

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.15

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_SEARCH_KEY, ptagOriginalSentRepresentingSearchKey

2.845 PidTagOriginalSubject

Canonical name: PidTagOriginalSubject

Description: Specifies the subject of the original message.

Copyright © 2025 Microsoft Corporation

Property ID: 0x0049

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.16

Alternate names: PR_ORIGINAL_SUBJECT, PR_ORIGINAL_SUBJECT_A, ptagOriginalSubject, PR_ORIGINAL_SUBJECT_W, http://schemas.microsoft.com/exchange/originalsubject, http://schemas.microsoft.com/mapi/original_subject

2.846 PidTagOriginalSubmitTime

Canonical name: PidTagOriginalSubmitTime

Description: Specifies the original email message's submission date and time, in **UTC**.

Property ID: 0x004E

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [MS-OXOMSG] section 2.2.2.17

Alternate names: PR_ORIGINAL_SUBMIT_TIME, ptagOriginalSubmitTime, http://schemas.microsoft.com/exchange/originaldate, http://schemas.microsoft.com/mapi/original_submit_time

2.847 PidTagOriginatorDeliveryReportRequested

Canonical name: PidTagOriginatorDeliveryReportRequested

Description: Indicates whether an email sender requests an email **delivery receipt** from the messaging system.

Property ID: 0x0023

Data type: PtypBoolean, 0x000B

Area: MIME Properties

Defining reference: [MS-OXOMSG] section 2.2.1.20

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_ORIGINATOR_DELIVERY_REPORT_REQUESTED, http://schemas.microsoft.com/exchange/deliveryreportrequested

2.848 PidTagOriginatorNonDeliveryReportRequested

Canonical name: PidTagOriginatorNonDeliveryReportRequested

Description: Specifies whether an email sender requests suppression of nondelivery receipts.

Property ID: 0x0C08

Data type: PtypBoolean, 0x000B

Copyright © 2025 Microsoft Corporation

Area: MIME Properties

Defining reference: [MS-OXOMSG] section 2.2.1.21

Alternate names: PR_ORIGINATOR_NON_DELIVERY_REPORT_REQUESTED

2.849 PidTagOscSyncEnabled

Canonical name: PidTagOscSyncEnabled

Description: Specifies whether **contact** synchronization with an external source is handled by the server.

Property ID: 0x7C24

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.9.7

Alternate names: PR_OSC_SYNC_ENABLEDONSERVER

2.850 PidTagOtherAddressCity

Canonical name: PidTagOtherAddressCity

Description: Contains the name of the **mail user's** other locality, such as the town or city.

Property ID: 0x3A5F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.2

Consuming references: [MS-OXVCARD]

Alternate names: PR_OTHER_ADDRESS_CITY, PR_OTHER_ADDRESS_CITY_A, PR_OTHER_ADDRESS_CITY_W, urn:schemas:contacts:othercity

2.851 PidTagOtherAddressCountry

Canonical name: PidTagOtherAddressCountry

Description: Contains the name of the **mail user's** other country/region.

Property ID: 0x3A60

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.5

Consuming references: [MS-OXVCARD]

Alternate names: PR_OTHER_ADDRESS_COUNTRY, PR_OTHER_ADDRESS_COUNTRY_A, PR_OTHER_ADDRESS_COUNTRY_W, urn:schemas:contacts:othercountry

Copyright © 2025 Microsoft Corporation

2.852 PidTagOtherAddressPostalCode

Canonical name: PidTagOtherAddressPostalCode

Description: Contains the postal code for the **mail user's** other postal address.

Property ID: 0x3A61

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.4

Consuming references: [MS-OXVCARD]

Alternate names: PR_OTHER_ADDRESS_POSTAL_CODE, PR_OTHER_ADDRESS_POSTAL_CODE_A, PR_OTHER_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:otherpostalcode

2.853 PidTagOtherAddressPostOfficeBox

Canonical name: PidTagOtherAddressPostOfficeBox

Description: Contains the number or identifier of the **mail user's** other post office box.

Property ID: 0x3A64

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.7

Consuming references: [MS-OXVCARD]

Alternate names: PR_OTHER_ADDRESS_POST_OFFICE_BOX, PR_OTHER_ADDRESS_POST_OFFICE_BOX_A, PR_OTHER_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:otherpostofficebox

2.854 PidTagOtherAddressStateOrProvince

Canonical name: PidTagOtherAddressStateOrProvince

Description: Contains the name of the **mail user's** other state or province.

Property ID: 0x3A62

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.3

Consuming references: [MS-OXVCARD]

Alternate names: PR_OTHER_ADDRESS_STATE_OR_PROVINCE, PR_OTHER_ADDRESS_STATE_OR_PROVINCE_A, PR_OTHER_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:otherstate

Copyright © 2025 Microsoft Corporation

2.855 PidTagOtherAddressStreet

Canonical name: PidTagOtherAddressStreet

Description: Contains the **mail user's** other street address.

Property ID: 0x3A63

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.3.1

Consuming references: [MS-OXVCARD]

Alternate names: PR_OTHER_ADDRESS_STREET, PR_OTHER_ADDRESS_STREET_A, PR_OTHER_ADDRESS_STREET_W, urn:schemas:contacts:otherstreet

2.856 PidTagOtherTelephoneNumber

Canonical name: PidTagOtherTelephoneNumber

Description: Contains an alternate telephone number for the **mail user**.

Property ID: 0x3A1F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOCNTC] section 2.2.1.4.10

Consuming references: [MS-OXVCARD]

Alternate names: PR_OTHER_TELEPHONE_NUMBER, PR_OTHER_TELEPHONE_NUMBER_A, PR_OTHER_TELEPHONE_NUMBER_W, urn:schemas:contacts:otherTelephone

2.857 PidTagOutOfOfficeState

Canonical name: PidTagOutOfOfficeState

Description: Indicates whether the user is **OOF**.

Property ID: 0x661D

Data type: PtypBoolean, 0x000B

Area: Message Store Properties

Defining reference: [MS-OXCSTOR] section 2.2.2.1.2.4

Alternate names: PR_OOF_STATE, ptagOOFState

2.858 PidTagOwnerAppointmentId

Canonical name: PidTagOwnerAppointmentId

Description: Specifies a quasi-unique value among all of the **Calendar objects** in a user's **mailbox**.

Property ID: 0x0062

Copyright © 2025 Microsoft Corporation

Data type: PtypInteger32, 0x0003

Area: Appointment

Defining reference:[MS-OXOCAL] section 2.2.1.29

Consuming references: [MS-OXCICAL], [MS-OXTNEF], [MS-XWDCAL]

Alternate names: PR_OWNER_APPT_ID, http://schemas.microsoft.com/mapi/owner_appt_id

2.859 PidTagPagerTelephoneNumber

Canonical name: PidTagPagerTelephoneNumber

Description: Contains the **mail user's** pager telephone number.

Property ID: 0x3A21

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.4.28

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_PAGER_TELEPHONE_NUMBER, PR_PAGER_TELEPHONE_NUMBER_A, PR_PAGER_TELEPHONE_NUMBER_W, urn:schemas:contacts:pager

2.860 PidTagParentEntryId

Canonical name: PidTagParentEntryId

Description: Contains the **EntryID** of the folder where messages or subfolders reside.

Property ID: 0x0E09

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.7

Consuming references: [MS-OXCDATA], [MS-OXCSPAM], [MS-OXOSFLD], [MS-OXPFOAB]

Alternate names: PR_PARENT_ENTRYID, ptagParentEntryId

2.861 PidTagParentFolderId

Canonical name: PidTagParentFolderId

Description: Contains a value that contains the Folder ID (FID), as specified in [MS-OXCDATA] section 2.2.1.1, that identifies the parent folder of the **messaging object** being synchronized.

Property ID: 0x6749

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [MS-OXCFXICS] section 2.2.1.2.4

Copyright © 2025 Microsoft Corporation

Alternate names: ptagParentFID

2.862 PidTagParentKey

Canonical name: PidTagParentKey

Description: Contains the search key that is used to correlate the original message and the reports about the original message.

Property ID: 0x0025

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.2.18

Alternate names: PR_PARENT_KEY, ptagParentKey

2.863 PidTagParentSourceKey

Canonical name: PidTagParentSourceKey

Description: Contains a value on a folder that contains the **PidTagSourceKey** property (section 2.1024) of the parent folder.

Property ID: 0x65E1

Data type: PtypBinary, 0x0102

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXCFXICS] section 2.2.1.2.6

Alternate names: PR_PARENT_SOURCE_KEY

2.864 PidTagPersonalHomePage

Canonical name: PidTagPersonalHomePage

Description: Contains the **URL** of the **mail user's** personal home page.

Property ID: 0x3A50

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.10.13

Consuming references: [MS-OXVCARD]

Alternate names: PR_PERSONAL_HOME_PAGE, PR_PERSONAL_HOME_PAGE_A, PR_PERSONAL_HOME_PAGE_W, urn:schemas:contacts:personalHomePage

2.865 PidTagPolicyTag

Canonical name: PidTagPolicyTag

Description: Specifies the **GUID** of a **retention tag**.

Copyright © 2025 Microsoft Corporation

Property ID: 0x3019

Data type: PtypBinary, 0x0102

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.2

Alternate names: PR_POLICY_TAG, ptagPolicyTag

2.866 PidTagPostalAddress

Canonical name: PidTagPostalAddress

Description: Contains the **mail user's** postal address.

Property ID: 0x3A15

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.3.8

Alternate names: PR_POSTAL_ADDRESS, PR_POSTAL_ADDRESS_A, PR_POSTAL_ADDRESS_W, urn:schemas:contacts:mailingpostaladdress

2.867 PidTagPostalCode

Canonical name: PidTagPostalCode

Description: Contains the postal code for the **mail user's** postal address.

Property ID: 0x3A2A

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.18

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_POSTAL_CODE, PR_POSTAL_CODE_A, PR_POSTAL_CODE_W, PR_BUSINESS_ADDRESS_POSTAL_CODE, PR_BUSINESS_ADDRESS_POSTAL_CODE_A, PR_BUSINESS_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:mailingpostalcode

2.868 PidTagPostOfficeBox

Canonical name: PidTagPostOfficeBox

Description: Contains the number or identifier of the **mail user's** post office box.

Property ID: 0x3A2B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.15

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_POST_OFFICE_BOX, PR_POST_OFFICE_BOX_A, PR_POST_OFFICE_BOX_W, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_A, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:mailingpostofficebox

2.869 PidTagPredecessorChangeList

Canonical name: PidTagPredecessorChangeList

Description: Contains a value that contains a serialized representation of a **PredecessorChangeList** structure.

Property ID: 0x65E3

Data type: PtypBinary, 0x0102

Area: Sync

Defining reference: [MS-OXCFXICS] section 2.2.1.2.8

Alternate names: PR_PREDECESSOR_CHANGE_LIST

2.870 PidTagPrimaryFaxNumber

Canonical name: PidTagPrimaryFaxNumber

Description: Contains the telephone number of the **mail user's** primary fax machine.

Property ID: 0x3A23

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.29

Consuming references: [MS-OXOAB], [MS-OXOCNTC]

Alternate names: PR_PRIMARY_FAX_NUMBER, PR_PRIMARY_FAX_NUMBER_A, PR_PRIMARY_FAX_NUMBER_W, urn:schemas:contacts:otherfax

2.871 PidTagPrimarySendAccount

Canonical name: PidTagPrimarySendAccount

Description: Specifies the first server that a client is to use to send the email with.

Property ID: 0x0E28

Data type: PtypString, 0x001F

Area: MapiNonTransmittable

Defining reference: [MS-OXOMSG] section 2.2.1.64

Alternate names: PR_PRIMARY_SEND_ACCT

Copyright © 2025 Microsoft Corporation

2.872 PidTagPrimaryTelephoneNumber

Canonical name: PidTagPrimaryTelephoneNumber

Description: Contains the **mail user's** primary telephone number.

Property ID: 0x3A1A

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.4.5

Consuming references: [MS-OXNSPI], [MS-OXVCARD]

Alternate names: PR_PRIMARY_TELEPHONE_NUMBER, PR_PRIMARY_TELEPHONE_NUMBER_A, PR_PRIMARY_TELEPHONE_NUMBER_W

2.873 PidTagPriority

Canonical name: PidTagPriority

Description: Indicates the client's request for the priority with which the message is to be sent by the messaging system.

Property ID: 0x0026

Data type: PtypInteger32, 0x0003

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.12

Consuming references: [MS-OXCFXICS], [MS-OXOPOST], [MS-OXOTASK], [MS-OXOCNTC], [MS-OXCMAIL], [MS-OXORMMS], [MS-OXODOC], [MS-OXONOTE], [MS-OXOJRNL], [MS-XWDCAL]

Alternate names: PR_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

2.874 PidTagProcessed

Canonical name: PidTagProcessed

Description: Indicates whether a client has already processed a received task communication.

Property ID: 0x7D01

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [MS-OXOCAL] section 2.2.5.7

Consuming references: [MS-OXCICAL], [MS-OXOTASK]

Alternate names: PR_PROCESSED

Copyright © 2025 Microsoft Corporation

2.875 PidTagProfession

Canonical name: PidTagProfession

Description: Contains the name of the **mail user's** line of business.

Property ID: 0x3A46

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.6.9

Consuming references: [MS-OXVCARD]

Alternate names: PR_PROFESSION, PR_PROFESSION_A, PR_PROFESSION_W, urn:schemas:contacts:profession

2.876 PidTagProhibitReceiveQuota

Canonical name: PidTagProhibitReceiveQuota

Description: Maximum size, in kilobytes, that a user is allowed to accumulate in their **mailbox** before no further email will be delivered to their mailbox.

Property ID: 0x666A

Data type: PtypInteger32, 0x0003

Area: Exchange Administrative

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.3

Alternate names: PR_PROHIBIT_RECEIVE_QUOTA, ptagProhibitReceiveQuota

2.877 PidTagProhibitSendQuota

Canonical name: PidTagProhibitSendQuota

Description: Maximum size, in kilobytes, that a user is allowed to accumulate in their **mailbox** before the user can no longer send any more email.

Property ID: 0x666E

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.4

Alternate names: PR_PROHIBIT_SEND_QUOTA, ptagProhibitSendQuota

2.878 PidTagPurportedSenderDomain

Canonical name: PidTagPurportedSenderDomain

Description: Contains the **domain** responsible for transmitting the current message.

Property ID: 0x4083

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: TransportEnvelope

Defining reference: [MS-OXCMSG] section 2.2.1.43

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_PURPORTED_SENDER_DOMAIN

2.879 PidTagRadioTelephoneNumber

Canonical name: PidTagRadioTelephoneNumber

Description: Contains the **mail user's** radio telephone number.

Property ID: 0x3A1D

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.4.8

Consuming references: [MS-OXVCARD]

Alternate names: PR_RADIO_TELEPHONE_NUMBER, PR_RADIO_TELEPHONE_NUMBER_A, PR_RADIO_TELEPHONE_NUMBER_W

2.880 PidTagRead

Canonical name: PidTagRead

Description: Indicates whether a message has been read.

Property ID: 0x0E69

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable Property set

Defining reference: [MS-OXCMSG] section 2.2.1.53

Consuming references: [MS-OXCICAL], [MS-OXCMAIL], [MS-OXCTABL], [MS-XWDCAL]

Alternate names: PR_READ, ptagRead, urn:schemas:httpmail:read

2.881 PidTagReadReceiptAddressType

Canonical name: PidTagReadReceiptAddressType

Description: Contains the **address type** of the end user to whom a **read receipt** is directed.

Property ID: 0x4029

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference: [MS-OXOMSG] section 2.2.2.24

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-OXCMAIL]

Alternate names: ptagReadReceiptAddrType, ReadReceiptAddrType

2.882 PidTagReadReceiptEmailAddress

Canonical name: PidTagReadReceiptEmailAddress

Description: Contains the email address of the end user to whom a **read receipt** is directed.

Property ID: 0x402A

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference: [MS-OXOMSG] section 2.2.2.25

Consuming reference: [MS-OXCMAIL]

Alternate names: ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

2.883 PidTagReadReceiptEntryId

Canonical name: PidTagReadReceiptEntryId

Description: Contains an address book **EntryID**.

Property ID: 0x0046

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.2.26

Alternate names: PR_READ_RECEIPT_ENTRYID, ptagReadReceiptEntryId

2.884 PidTagReadReceiptName

Canonical name: PidTagReadReceiptName

Description: Contains the **display name** for the end user to whom a **read receipt** is directed.

Property ID: 0x402B

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference: [MS-OXOMSG] section 2.2.2.27

Consuming reference: [MS-OXCMAIL]

Alternate names: ptagReadReceiptDisplayName, ReadReceiptDisplayName

2.885 PidTagReadReceiptRequested

Canonical name: PidTagReadReceiptRequested

Copyright © 2025 Microsoft Corporation

Description: Specifies whether the email sender requests a **read receipt** from all **recipients** when this email message is read or opened.

Property ID: 0x0029

Data type: PtypBoolean, 0x000B

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.29

Consuming references: [MS-OXCMAIL], [MS-OXODOC], [MS-OXOTASK], [MS-OXOJRNL], [MS-OXOPOST], [MS-OXORMMS], [MS-OXOCNTC], [MS-OXONOTE]

Alternate names: PR_READ_RECEIPT_REQUESTED, ptagReadReceiptRequested, http://schemas.microsoft.com/exchange/readreceiptrequested

2.886 PidTagReadReceiptSearchKey

Canonical name: PidTagReadReceiptSearchKey

Description: Contains an address book search key.

Property ID: 0x0053

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.2.28

Alternate names: PR_READ_RECEIPT_SEARCH_KEY, ptagReadReceiptSearchKey

2.887 PidTagReadReceiptSmtpAddress

Canonical name: PidTagReadReceiptSmtpAddress

Description: Contains the SMTP email address of the user to whom a read receipt is directed.

Property ID: 0x5D05

Data type: PtypString, 0x001F

Area: Mail

Defining reference: [MS-OXOMSG] section 2.2.1.30

Consuming reference: [MS-OXCMAIL]

Alternate names: ptagRecipientReadReceiptSmtpAddress

2.888 PidTagReceiptTime

Canonical name: PidTagReceiptTime

Description: Contains the sent time for a message disposition notification, as specified in [RFC3798].

Property ID: 0x002A

Data type: PtypTime, 0x0040

Copyright © 2025 Microsoft Corporation

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.2.33

Consuming references: [MS-OXCMAIL]

Alternate names: PR_RECEIPT_TIME, ptagReceiptTime

2.889 PidTagReceivedByAddressType

Canonical name: PidTagReceivedByAddressType

Description: Contains the email message receiver's email **address type**.

Property ID: 0x0075

Data type: PtypString, 0x001F

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.1.36

Alternate names: PR_RECEIVED_BY_ADDRTYPE, PR_RECEIVED_BY_ADDRTYPE_A, ptagReceivedByAddrType, PR_RECEIVED_BY_ADDRTYPE_W

2.890 PidTagReceivedByEmailAddress

Canonical name: PidTagReceivedByEmailAddress

Description: Contains the email message receiver's email address.

Property ID: 0x0076

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.37

Alternate names: PR_RECEIVED_BY_EMAIL_ADDRESS, PR_RECEIVED_BY_EMAIL_ADDRESS_A, PR_RECEIVED_BY_EMAIL_ADDRESS_W

2.891 PidTagReceivedByEntryId

Canonical name: PidTagReceivedByEntryId

Description: Contains the address book **EntryID** of the **mailbox** receiving the **Email object**.

Property ID: 0x003F

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.38

Alternate names: PR_RECEIVED_BY_ENTRYID

Copyright © 2025 Microsoft Corporation

2.892 PidTagReceivedByName

Canonical name: PidTagReceivedByName

Description: Contains the email message receiver's **display name**.

Property ID: 0x0040

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.39

Alternate names: PR_RECEIVED_BY_NAME, PR_RECEIVED_BY_NAME_A, PR_RECEIVED_BY_NAME_W

2.893 PidTagReceivedBySearchKey

Canonical name: PidTagReceivedBySearchKey

Description: Identifies an address book search key that contains a binary-comparable key that is used to identify correlated objects for a search.

Property ID: 0x0051

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.40

Alternate names: PR_RECEIVED_BY_SEARCH_KEY

2.894 PidTagReceivedBySmtpAddress

Canonical name: PidTagReceivedBySmtpAddress

Description: Contains the email message receiver's SMTP email address.

Property ID: 0x5D07

Data type: PtypString, 0x001F

Area: Mail

Defining reference: [MS-OXOMSG] section 2.2.1.41

Consuming references: [MS-OXCMAIL]

Alternate names: ptagRecipientRcvdBySmtpAddress

2.895 PidTagReceivedRepresentingAddressType

Canonical name: PidTagReceivedRepresentingAddressType

Description: Contains the email **address type** for the end user represented by the receiving **mailbox** owner.

Property ID: 0x0077

Copyright © 2025 Microsoft Corporation

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.23

Alternate names: PR_RCVD_REPRESENTING_ADDRTYPE, PR_RCVD_REPRESENTING_ADDRTYPE_A, ptagRcvdRepresentingAddrType, PR_RCVD_REPRESENTING_ADDRTYPE_W

2.896 PidTagReceivedRepresentingEmailAddress

Canonical name: PidTagReceivedRepresentingEmailAddress

Description: Contains the email address for the end user represented by the receiving **mailbox** owner.

Property ID: 0x0078

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.24

Alternate names: PR_RCVD_REPRESENTING_EMAIL_ADDRESS, PR_RCVD_REPRESENTING_EMAIL_ADDRESS_A, PR_RCVD_REPRESENTING_EMAIL_ADDRESS_W

2.897 PidTagReceivedRepresentingEntryId

Canonical name: PidTagReceivedRepresentingEntryId

Description: Contains an address book **EntryID** that identifies the end user represented by the receiving **mailbox** owner.

Property ID: 0x0043

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.25

Alternate names: PR_RCVD_REPRESENTING_ENTRYID, ptagRcvdRepresentingEntryId

2.898 PidTagReceivedRepresentingName

Canonical name: PidTagReceivedRepresentingName

Description: Contains the **display name** for the end user represented by the receiving **mailbox** owner.

Property ID: 0x0044

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.26

Copyright © 2025 Microsoft Corporation

Alternate names: PR_RCVD_REPRESENTING_NAME, PR_RCVD_REPRESENTING_NAME_A, ptagRcvdRepresentingName, PR_RCVD_REPRESENTING_NAME_W

2.899 PidTagReceivedRepresentingSearchKey

Canonical name: PidTagReceivedRepresentingSearchKey

Description: Identifies an address book search key that contains a binary-comparable key of the end user represented by the receiving **mailbox** owner.

Property ID: 0x0052

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.27

Alternate names: PR_RCVD_REPRESENTING_SEARCH_KEY, ptagRcvdRepresentingSearchKey

2.900 PidTagReceivedRepresentingSmtpAddress

Canonical name: PidTagReceivedRepresentingSmtpAddress

Description: Contains the SMTP email address of the user represented by the receiving mailbox owner.

Property ID: 0x5D08

Data type: PtypString, 0x001F

Area: Mail

Defining reference: [MS-OXOMSG] section 2.2.1.28

Consuming references: [MS-OXCMAIL]

Alternate names: ptagRecipientRcvdRepresentingSmtpAddress

2.901 PidTagRecipientDisplayName

Canonical name: PidTagRecipientDisplayName

Description: Specifies the display name of the **recipient**.

Property ID: 0x5FF6

Data type: PtypString, 0x001F

Area: TransportRecipient

Defining reference: [MS-OXCMSG] section 2.2.1.54

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOMSG]

Alternate names: PR_RECIPIENT_DISPLAY_NAME, PR_RECIPIENT_DISPLAY_NAME_W

2.902 PidTagRecipientEntryId

Canonical name: PidTagRecipientEntryId

Copyright © 2025 Microsoft Corporation

Description: Identifies an **Address Book object** that specifies the **recipient**.

Property ID: 0x5FF7

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [MS-OXCMSG] section 2.2.1.55

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOMSG]

Alternate names: PR_RECIPIENT_ENTRYID, ptagRecipientEntryId

2.903 PidTagRecipientFlags

Canonical name: PidTagRecipientFlags

Description: Specifies a bit field that describes the **recipient** status.

Property ID: 0x5FFD

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [MS-OXOCAL] section 2.2.4.10.1

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMSG], [MS-OXOMSG]

Alternate names: PR_RECIPIENT_FLAGS

2.904 PidTagRecipientOrder

Canonical name: PidTagRecipientOrder

Description: Specifies the location of the current **recipient** in the **recipient table**.

Property ID: 0x5FDF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [MS-OXCMSG] section 2.2.1.40

Consuming references: [MS-OXCFXICS], [MS-OXOMSG]

Alternate names: PR_RECIPIENT_ORDER, ptagRecipientOrder

2.905 PidTagRecipientProposed

Canonical name: PidTagRecipientProposed

Description: Indicates that the attendee proposed a new date and/or time.

Property ID: 0x5FE1

Data type: PtypBoolean, 0x000B

Area: TransportRecipient

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCAL] section 2.2.4.10.4

Alternate names: PR_RECIPIENT_PROPOSED, ptagRecipientProposed

2.906 PidTagRecipientProposedEndTime

Canonical name: PidTagRecipientProposedEndTime

Description: Indicates the **meeting** end time requested by the attendee in a **counter proposal**.

Property ID: 0x5FE4

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [MS-OXOCAL] section 2.2.4.10.6

Alternate names: PR_RECIPIENT_PROPOSEDENDTIME, ptagRecipientProposedEndTime

2.907 PidTagRecipientProposedStartTime

Canonical name: PidTagRecipientProposedStartTime

Description: Indicates the **meeting** start time requested by the attendee in a **counter proposal**.

Property ID: 0x5FE3

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [MS-OXOCAL] section 2.2.4.10.5

Alternate names: PR_RECIPIENT_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

2.908 PidTagRecipientReassignmentProhibited

Canonical name: PidTagRecipientReassignmentProhibited

Description: Specifies whether adding additional or different **recipients** is prohibited for the email message when forwarding the email message.

Property ID: 0x002B

Data type: PtypBoolean, 0x000B

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.1.42

Alternate names: PR_RECIPIENT_REASSIGNMENT_PROHIBITED, ptagRecipientReassignmentProhibited

2.909 PidTagRecipientTrackStatus

Canonical name: PidTagRecipientTrackStatus

Description: Indicates the response status that is returned by the attendee.

Copyright © 2025 Microsoft Corporation

Property ID: 0x5FFF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [MS-OXOCAL] section 2.2.4.10.2

Consuming references: [MS-OXCICAL], [MS-OXCFXICS], [MS-OXCMSG], [MS-OXOMSG]

Alternate names: PR_RECIPIENT_TRACKSTATUS, ptagRecipientTrackStatus

2.910 PidTagRecipientTrackStatusTime

Canonical name: PidTagRecipientTrackStatusTime

Description: Indicates the date and time at which the attendee responded.

Property ID: 0x5FFB

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [MS-OXOCAL] section 2.2.4.10.3

Consuming reference: [MS-OXCICAL]

Alternate names: PR_RECIPIENT_TRACKSTATUS_TIME, ptagRecipientTrackStatusTime

2.911 PidTagRecipientType

Canonical name: PidTagRecipientType

Description: Represents the recipient type of a **recipient** on the message.

Property ID: 0x0C15

Data type: PtypInteger32, 0x0003

Area: MapiRecipient

Defining reference: [MS-OXOMSG] section 2.2.3.1

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXORULE], [MS-OXOSRCH], [MS-OXCMSG]

Alternate names: PR_RECIPIENT_TYPE, ptagRecipientType

2.912 PidTagRecordKey

Canonical name: PidTagRecordKey

Description: Contains a unique binary-comparable identifier for a specific object.

Property ID: 0x0FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXCPRPT] section 2.2.1.8

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCMSG], [MS-OXOCFG], [MS-OXOABK]

Alternate names: PR_RECORD_KEY, ptagRecordKey

2.913 PidTagReferredByName

Canonical name: PidTagReferredByName

Description: Contains the name of the **mail user's** referral.

Property ID: 0x3A47

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.10.21

Alternate names: PR_REFERRED_BY_NAME, PR_REFERRED_BY_NAME_A, PR_REFERRED_BY_NAME_W

2.914 PidTagRemindersOnlineEntryId

Canonical name: PidTagRemindersOnlineEntryId

Description: Contains an **EntryID** for the Reminders folder.

Property ID: 0x36D5

Data type: PtypBinary, 0x0102

Area: MapiContainer

Defining reference: [MS-OXOSFLD] section 2.2.3

Alternate names: PR_REM_ONLINE_ENTRYID, ptagRemOnlineEntryId

2.915 PidTagRemoteMessageTransferAgent

Canonical name: PidTagRemoteMessageTransferAgent

Description: Contains the value of the Remote-MTA field for a delivery status notification, as specified in [RFC3464].

Property ID: 0x0C21

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.2.34

Consuming references: [MS-OXCMAIL]

Alternate names: PR_DSN_REMOTE_MTA, ptagDsnRemoteMta

Copyright © 2025 Microsoft Corporation

2.916 PidTagRenderingPosition

Canonical name: PidTagRenderingPosition

Description: Represents an offset, in rendered characters, to use when rendering an attachment within the main message text.

Property ID: 0x370B

Data type: PtypInteger32, 0x0003

Area: MapiAttachment

Defining reference: [MS-OXCMSG] section 2.2.2.16

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXORMDR], [MS-OXCMAIL], [MS-OXOJRNL], [MS-OXORMMS], [MS-OXOTASK], [MS-OXRTFEX]

Alternate names: PR_RENDERING_POSITION, ptagRenderingPosition

2.917 PidTagReplyRecipientEntries

Canonical name: PidTagReplyRecipientEntries

Description: Identifies a **FlatEntryList** structure ([MS-OXCDATA] section 2.3.3) of address book **EntryIDs** for **recipients** that are to receive a reply.

Property ID: 0x004F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.1.43

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_REPLY_RECIPIENT_ENTRIES, ptagReplyRecipientEntries, http://schemas.microsoft.com/exchange/reply-to-base64

2.918 PidTagReplyRecipientNames

Canonical name: PidTagReplyRecipientNames

Description: Contains a list of **display names** for **recipients** that are to receive a reply.

Property ID: 0x0050

Data type: PtypString, 0x001F

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.1.44

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_REPLY_RECIPIENT_NAMES, PR_REPLY_RECIPIENT_NAMES_A, ptagReplyRecipientNames, PR_REPLY_RECIPIENT_NAMES_W

Copyright © 2025 Microsoft Corporation

2.919 PidTagReplyRequested

Canonical name: PidTagReplyRequested

Description: Indicates whether a reply is requested to a **Message object**.

Property ID: 0x0C17

Data type: PtypBoolean, 0x000B

Area: MapiRecipient

Defining reference: [MS-OXOMSG] section 2.2.1.45

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOCAL], [MS-OXOFLAG], [MS-OXOMSG], [MS-OXORMDR]

Alternate names: PR_REPLY_REQUESTED, ptagReplyRequested

2.920 PidTagReplyTemplateId

Canonical name: PidTagReplyTemplateId

Description: Contains the value of the **GUID** that points to a Reply template.

Property ID: 0x65C2

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [MS-OXORULE] section 2.2.9.2

Alternate names: PR_REPLY_TEMPLATE_ID, ptagReplyTemplateId

2.921 PidTagReplyTime

Canonical name: PidTagReplyTime

Description: Specifies the time, in **UTC**, that the sender has designated for an associated work item to be due.

Property ID: 0x0030

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [MS-OXOFLAG] section 2.2.3.1

Consuming references: [MS-OXCMAIL], [MS-OXORMDR]

Alternate names: PR_REPLY_TIME, urn:schemas:httpmail:reply-by, http://schemas.microsoft.com/exchange/reply-by-iso

2.922 PidTagReportDisposition

Canonical name: PidTagReportDisposition

Copyright © 2025 Microsoft Corporation

Description: Contains a string indicating whether the original message was displayed to the user or deleted (report messages only).

Property ID: 0x0080

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.34

Alternate names: PR_REPORT_DISPOSITION_W

2.923 PidTagReportDispositionMode

Canonical name: PidTagReportDispositionMode

Description: Contains a description of the **action** that a client has performed on behalf of a user (report messages only).

Property ID: 0x0081

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.35

Alternate names: PR_REPORT_DISPOSITION_MODE_W

2.924 PidTagReportEntryId

Canonical name: PidTagReportEntryId

Description: Specifies an **entry ID** that identifies the application that generated a report message.

Property ID: 0x0045

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.1.45

Alternate names: PR_REPORT_ENTRYID, ptagReportEntryId

2.925 PidTagReportingMessageTransferAgent

Canonical name: PidTagReportingMessageTransferAgent

Description: Contains the value of the Reporting-MTA field for a delivery status notification, as specified in [RFC3464].

Property ID: 0x6820

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.2.35

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCMAIL]

Alternate names: ptagDsnReportingMta

2.926 PidTagReportName

Canonical name: PidTagReportName

Description: Contains the **display name** for the entity (usually a server agent) that generated the report message.

Property ID: 0x003A

Data type: PtypString, 0x001F

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.2.20

Alternate names: PR_REPORT_NAME, PR_REPORT_NAME_A, PR_REPORT_NAME_W

2.927 PidTagReportSearchKey

Canonical name: PidTagReportSearchKey

Description: Contains an address book search key representing the entity (usually a server agent) that generated the report message.

Property ID: 0x0054

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.2.21

Alternate names: PR_REPORT_SEARCH_KEY, ptagReportSearchKey

2.928 PidTagReportTag

Canonical name: PidTagReportTag

Description: Contains the data that is used to correlate the report and the original message.

Property ID: 0x0031

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXOMSG] section 2.2.2.22

Alternate names: PR_REPORT_TAG, ptagReportTag

2.929 PidTagReportText

Canonical name: PidTagReportText

Description: Contains the optional text for a report message.

Copyright © 2025 Microsoft Corporation

Property ID: 0x1001

Data type: PtypString, 0x001F

Area: MapiMessage

Defining reference: [MS-OXOMSG] section 2.2.2.23

Alternate names: PR_REPORT_TEXT, PR_REPORT_TEXT_A, ptagReportText, PR_REPORT_TEXT_W

2.930 PidTagReportTime

Canonical name: PidTagReportTime

Description: Indicates the last time that the contact list that is controlled by the **PidTagJunkIncludeContacts** property (section 2.760) was updated.

Property ID: 0x0032

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

Defining reference: [MS-OXCSPAM] section 2.2.2.6

Alternate names: PR_REPORT_TIME, ptagReportTime, http://schemas.microsoft.com/exchange/reporttime

2.931 PidTagResolveMethod

Canonical name: PidTagResolveMethod

Description: Specifies how to resolve any conflicts with the message.

Property ID: 0x3FE7

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [MS-OXCFXICS] section 2.2.1.4.1

Alternate names: PR_RESOLVE_METHOD, ptagResolveMethod

2.932 PidTagResponseRequested

Canonical name: PidTagResponseRequested

Description: Indicates whether a response is requested to a **Message object**.

Property ID: 0x0063

Data type: PtypBoolean, 0x000B

Area: MapiEnvelope Property set

Defining reference: [MS-OXOMSG] section 2.2.1.46

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOCAL], [MS-OXOFLAG], [MS-OXORMDR], [MS-OXTNEF], [MS-XWDCAL]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_RESPONSE_REQUESTED, urn:schemas:calendar:responserequested, http://schemas.microsoft.com/mapi/response_requested

2.933 PidTagResponsibility

Canonical name: PidTagResponsibility

Description: Specifies whether another mail agent has ensured that the message will be delivered.

Property ID: 0x0E0F

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

Defining reference: [MS-OXCMSG] section 2.2.1.37

Consuming reference: [MS-OXCFXICS]

Alternate names: PR_RESPONSIBILITY, ptagResponsibility

2.934 PidTagRetentionDate

Canonical name: PidTagRetentionDate

Description: Specifies the date, in **UTC**, after which a **Message object** is expired by the server.

Property ID: 0x301C

Data type: PtypTime, 0x0040

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.5

Alternate names: PR_RETENTION_DATE, ptagRetentionDate

2.935 PidTagRetentionFlags

Canonical name: PidTagRetentionFlags

Description: Contains **flags** that specify the status or nature of an item's **retention tag** or archive tag.

Property ID: 0x301D

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.6

Alternate names: PR_RETENTION_FLAGS, ptagRetentionFlags

2.936 PidTagRetentionPeriod

Canonical name: PidTagRetentionPeriod

Description: Specifies the number of days that a **Message object** can remain unarchived.

Copyright © 2025 Microsoft Corporation

Property ID: 0x301A

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.3

Alternate names: PR_RETENTION_PERIOD, ptagRetentionPeriod

2.937 PidTagRights

Canonical name: PidTagRights

Description: Specifies a user's folder **permissions**.

Property ID: 0x6639

Data type: PtypInteger32, 0x0003

Area: ExchangeFolder

Defining reference: [MS-OXCFOLD] section 2.2.2.2.2.8

Consuming reference: [MS-OXCPERM]

Alternate names: PR_RIGHTS, ptagRights

2.938 PidTagRoamingDatatypes

Canonical name: PidTagRoamingDatatypes

Description: Contains a bitmask that indicates which **stream** properties exist on the message.

Property ID: 0x7C06

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.2.1

Alternate names: PR_ROAMING_DATATYPES

2.939 PidTagRoamingDictionary

Canonical name: PidTagRoamingDictionary

Description: Contains a dictionary **stream**, as specified in [MS-OXOCFG] section 2.2.5.1.

Property ID: 0x7C07

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.2.2

Alternate names: PR_ROAMING_DICTIONARY

Copyright © 2025 Microsoft Corporation

2.940 PidTagRoamingXmlStream

Canonical name: PidTagRoamingXmlStream

Description: Contains an **XML stream**, as specified in [MS-OXOCFG] section 2.2.5.2.

Property ID: 0x7C08

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.2.3

Alternate names: PR_ROAMING_XMLSTREAM

2.941 PidTagRowid

Canonical name: PidTagRowid

Description: Contains a unique identifier for a **recipient** in a message's **recipient table**.

Property ID: 0x3000

Data type: PtypInteger32, 0x0003

Area: MapiCommon

Defining reference: [MS-OXCMSG] section 2.2.1.38

Consuming reference: [MS-OXCFXICS]

Alternate names: PR_ROWID, ptagRowId

2.942 PidTagRowType

Canonical name: PidTagRowType

Description: Identifies the type of the row.

Property ID: 0x0FF5

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [MS-OXCTABL] section 2.2.1.3

Alternate names: PR_ROW_TYPE, ptagRowType

2.943 PidTagRtfCompressed

Canonical name: PidTagRtfCompressed

Description: Contains **message body** text in compressed **RTF** format.

Property ID: 0x1009

Data type: PtypBinary, 0x0102

Area: Email

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXCMSG] section 2.2.1.58.4

Consuming references: [MS-OXBBODY], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOCAL], [MS-OXOCNTC], [MS-OXOJRNL], [MS-OXOMSG], [MS-OXORMMS], [MS-OXRTFCP], [MS-OXRTFEX], [MS-OXTNEF]

Alternate names: PR_RTF_COMPRESSED, ptagRTFCompressed

2.944 PidTagRtfInSync

Canonical name: PidTagRtfInSync

Description: Indicates whether the **PidTagBody** property (section 2.618) and the **PidTagRtfCompressed** property (section 2.943) contain the same text (ignoring formatting).

Property ID: 0x0E1F

Data type: PtypBoolean, 0x000B

Area: Email

Defining reference: [MS-OXCMSG] section 2.2.1.58.5

Consuming references: [MS-OXBBODY], [MS-OXCFXICS], [MS-OXOMSG], [MS-OXORMMS], [MS-OXRTFEX]

Alternate names: PR_RTF_IN_SYNC, ptagRTFInSync

2.945 PidTagRuleActionNumber

Canonical name: PidTagRuleActionNumber

Description: Contains the index of a **rule action** that failed.

Property ID: 0x6650

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [MS-OXORULE] section 2.2.7.4

Alternate names: PR_RULE_ACTION_NUMBER, ptagRuleActionNumber

2.946 PidTagRuleActions

Canonical name: PidTagRuleActions

Description: Contains the set of **actions** associated with the **rule**.

Property ID: 0x6680

Data type: PtypRuleAction, 0x00FE

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.10

Consuming reference: [MS-OXODLGT]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_RULE_ACTIONS, ptagRuleActions

2.947 PidTagRuleActionType

Canonical name: PidTagRuleActionType

Description: Contains the **ActionType** field ([MS-OXORULE] section 2.2.5.1) of a **rule** that failed.

Property ID: 0x6649

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [MS-OXORULE] section 2.2.7.3

Alternate names: PR_RULE_ACTION_TYPE, ptagRuleActionType

2.948 PidTagRuleCondition

Canonical name: PidTagRuleCondition

Description: Defines the conditions under which a **rule action** is to be executed.

Property ID: 0x6679

Data type: PtypRestriction, 0x00FD

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.9

Consuming reference: [MS-OXODLGT]

Alternate names: PR_RULE_CONDITION, ptagRuleCondition

2.949 PidTagRuleError

Canonical name: PidTagRuleError

Description: Contains the error code that indicates the cause of an error encountered during the execution of the **rule**.

Property ID: 0x6648

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [MS-OXORULE] section 2.2.7.2

Alternate names: PR_RULE_ERROR, ptagRuleError

2.950 PidTagRuleFolderEntryId

Canonical name: PidTagRuleFolderEntryId

Description: Contains the **EntryID** of the folder where the **rule** that triggered the generation of a **DAM** is stored.

Copyright © 2025 Microsoft Corporation

Property ID: 0x6651

Data type: PtypBinary, 0x0102

Area: ExchangeMessageReadOnly

Defining reference: [MS-OXORULE] section 2.2.6.5

Alternate names: PR_RULE_FOLDER_ENTRYID, ptagRuleFolderEntryId

2.951 PidTagRuleId

Canonical name: PidTagRuleId

Description: Specifies a unique identifier that is generated by the messaging server for each **rule** when the rule is first created.

Property ID: 0x6674

Data type: PtypInteger64, 0x0014

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.1

Alternate names: PR_RULE_ID, ptagRuleId

2.952 PidTagRuleIds

Canonical name: PidTagRuleIds

Description: Contains a buffer that is obtained by concatenating the **PidTagRuleId** property (section 2.951) values from all of the **rules** contributing **actions** that are contained in the **PidTagClientActions** property (section 2.634).

Property ID: 0x6675

Data type: PtypBinary, 0x0102

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.6.7

Alternate names: PR_RULE_IDS, ptagRuleIds

2.953 PidTagRuleLevel

Canonical name: PidTagRuleLevel

Description: Contains 0x00000000. This property is not used.

Property ID: 0x6683

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.6

Consuming reference: [MS-OXODLGT]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_RULE_LEVEL, ptagRuleLevel

2.954 PidTagRuleMessageLevel

Canonical name: PidTagRuleMessageLevel

Description: Contains 0x00000000. Set on the **FAI** message.

Property ID: 0x65ED

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXORULE] section 2.2.4.1.6

Consuming reference: [MS-OXCSPAM]

Alternate names: PR_RULE_MSG_LEVEL, ptagRuleMsgLevel

2.955 PidTagRuleMessageName

Canonical name: PidTagRuleMessageName

Description: Specifies the name of the **rule**. Set on the **FAI** message.

Property ID: 0x65EC

Data type: PtypString, 0x001F

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXORULE] section 2.2.4.1.1

Consuming reference: [MS-OXCSPAM]

Alternate names: ptagRuleMsgName

2.956 PidTagRuleMessageProvider

Canonical name: PidTagRuleMessageProvider

Description: Identifies the client application that owns the **rule**. Set on the **FAI** message.

Property ID: 0x65EB

Data type: PtypString, 0x001F

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXORULE] section 2.2.4.1.7

Consuming reference: [MS-OXCSPAM]

Alternate names: ptagRuleMsgProvider

2.957 PidTagRuleMessageProviderData

Canonical name: PidTagRuleMessageProviderData

Copyright © 2025 Microsoft Corporation

Description: Contains opaque data set by the client for the exclusive use of the client. Set on the **FAI** message.

Property ID: 0x65EE

Data type: PtypBinary, 0x0102

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXORULE] section 2.2.4.1.8

Alternate names: PR_RULE_MSG_PROVIDER_DATA, ptagRuleMsgProviderData

2.958 PidTagRuleMessageSequence

Canonical name: PidTagRuleMessageSequence

Description: Contains a value used to determine the order in which **rules** are evaluated and executed. Set on the **FAI** message.

Property ID: 0x65F3

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXORULE] section 2.2.4.1.3

Consuming reference: [MS-OXCSPAM]

Alternate names: PR_RULE_MSG_SEQUENCE, ptagRuleMsgSequence

2.959 PidTagRuleMessageState

Canonical name: PidTagRuleMessageState

Description: Contains **flags** that specify the state of the **rule**. Set on the **FAI** message.

Property ID: 0x65E9

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXORULE] section 2.2.4.1.4

Consuming reference: [MS-OXCSPAM]

Alternate names: PR_RULE_MSG_STATE, ptagRuleMsgState

2.960 PidTagRuleMessageUserFlags

Canonical name: PidTagRuleMessageUserFlags

Description: Contains an opaque property that the client sets for the exclusive use of the client. Set on the **FAI** message.

Property ID: 0x65EA

Data type: PtypInteger32, 0x0003

Copyright © 2025 Microsoft Corporation

Area: ExchangeNonTransmittableReserved

Defining reference: [MS-OXORULE] section 2.2.4.1.5

Consuming reference: [MS-OXCSPAM]

Alternate names: PR_RULE_MSG_USER_FLAGS, ptagRuleMsgUserFlags

2.961 PidTagRuleName

Canonical name: PidTagRuleName

Description: Specifies the name of the **rule**.

Property ID: 0x6682

Data type: PtypString, 0x001F

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.4

Consuming reference: [MS-OXODLGT]

Alternate names: PR_RULE_NAME, PR_RULE_NAME_A, ptagRuleName, PR_RULE_NAME_W

2.962 PidTagRuleProvider

Canonical name: PidTagRuleProvider

Description: A string identifying the client application that owns a **rule**.

Property ID: 0x6681

Data type: PtypString, 0x001F

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.5

Consuming reference: [MS-OXODLGT]

Alternate names: PR_RULE_PROVIDER, ptagRuleProvider, PR_RULE_PROVIDER_W

2.963 PidTagRuleProviderData

Canonical name: PidTagRuleProviderData

Description: Contains opaque data set by the client for the exclusive use of the client.

Property ID: 0x6684

Data type: PtypBinary, 0x0102

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.8

Alternate names: PR_RULE_PROVIDER_DATA, ptagRuleProviderData

Copyright © 2025 Microsoft Corporation

2.964 PidTagRuleSequence

Canonical name: PidTagRuleSequence

Description: Contains a value used to determine the order in which **rules** are evaluated and executed.

Property ID: 0x6676

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.2

Consuming references: [MS-OXCPRPT], [MS-OXCSTOR], [MS-OXCTABL], [MS-OXODLGT]

Alternate names: PR_RULE_SEQUENCE, ptagRuleSequence

2.965 PidTagRuleState

Canonical name: PidTagRuleState

Description: Contains **flags** that specify the state of the **rule**.

Property ID: 0x6677

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.3

Consuming reference: [MS-OXODLGT]

Alternate names: PR_RULE_STATE, ptagRuleState

2.966 PidTagRuleUserFlags

Canonical name: PidTagRuleUserFlags

Description: Contains an opaque property that the client sets for the exclusive use of the client.

Property ID: 0x6678

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [MS-OXORULE] section 2.2.1.3.1.7

Consuming reference: [MS-OXODLGT]

Alternate names: PR_RULE_USER_FLAGS, ptagRuleUserFlags

2.967 PidTagRwRulesStream

Canonical name: PidTagRwRulesStream

Description: Contains additional **rule** data about the **Rule FAI message**.

Copyright © 2025 Microsoft Corporation

Property ID: 0x6802

Data type: PtypBinary, 0x0102

Area: Message Class Defined Transmittable

Defining reference: [MS-OXORULE] section 2.2.9.3

Alternate names: PR_RW_RULES_STREAM

2.968 PidTagScheduleInfoAppointmentTombstone

Canonical name: PidTagScheduleInfoAppointmentTombstone

Description: Contains a list of tombstones, where each tombstone represents a **Meeting object** that has been declined.

Property ID: 0x686A

Data type: PtypBinary, 0x0102

Area: Free/Busy Properties

Defining reference: [MS-OXOCAL] section 2.2.12.5

Alternate names: PR_SCHDINFO_APPT_TOMBSTONE

2.969 PidTagScheduleInfoAutoAcceptAppointments

Canonical name: PidTagScheduleInfoAutoAcceptAppointments

Description: Indicates whether a client or server is to automatically respond to all **meeting requests** for the attendee or resource.

Property ID: 0x686D

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [MS-OXOCAL] section 2.2.12.2

Consuming reference: [MS-OXOPFFB]

Alternate names: PR_SCHDINFO_AUTO_ACCEPT_APPTS

2.970 PidTagScheduleInfoDelegateEntryIds

Canonical name: PidTagScheduleInfoDelegateEntryIds

Description: Specifies the **EntryIDs** of the **delegates**.

Property ID: 0x6845

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [MS-OXODLGT] section 2.2.2.2.5

Alternate names: PR_SCHDINFO_DELEGATE_ENTRYIDS

Copyright © 2025 Microsoft Corporation

2.971 PidTagScheduleInfoDelegateNames

Canonical name: PidTagScheduleInfoDelegateNames

Description: Specifies the names of the **delegates**.

Property ID: 0x6844

Data type: PtypMultipleString, 0x101F

Area: Free/Busy Properties

Defining reference: [MS-OXODLGT] section 2.2.2.2.3

Consuming reference: [MS-OXMSG]

Alternate names: PR_SCHDINFO_DELEGATE_NAMES

2.972 PidTagScheduleInfoDelegateNamesW

Canonical name: PidTagScheduleInfoDelegateNamesW

Description: Specifies the names of the **delegates** in Unicode.

Property ID: 0x684A

Data type: PtypMultipleString, 0x101F

Area: Free/Busy Properties

Defining reference: [MS-OXODLGT] section 2.2.2.2.4

Alternate names: PR_SCHDINFO_DELEGATE_NAMES_W, ptagDelegateNames

2.973 PidTagScheduleInfoDelegatorWantsCopy

Canonical name: PidTagScheduleInfoDelegatorWantsCopy

Description: Indicates whether the delegator wants to receive copies of the meeting-related objects that are sent to the **delegate**.

Property ID: 0x6842

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [MS-OXODLGT] section 2.2.2.2.1

Consuming reference: [MS-OXOPFFB]

Alternate names: PR_SCHDINFO_BOSS_WANTS_COPY

2.974 PidTagScheduleInfoDelegatorWantsInfo

Canonical name: PidTagScheduleInfoDelegatorWantsInfo

Description: Indicates whether the delegator wants to receive informational updates.

Property ID: 0x684B

Copyright © 2025 Microsoft Corporation

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [MS-OXODLGT] section 2.2.2.2.2

Consuming references: [MS-OXOCAL], [MS-OXOPFFB]

Alternate names: PR_SCHDINFO_BOSS_WANTS_INFO

2.975 PidTagScheduleInfoDisallowOverlappingAppts

Canonical name: PidTagScheduleInfoDisallowOverlappingAppts

Description: Indicates whether a client or server, when automatically responding to **meeting requests**, is to decline **Meeting Request objects** that overlap with previously scheduled events.

Property ID: 0x686F

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [MS-OXOCAL] section 2.2.12.4

Consuming reference: [MS-OXOPFFB]

Alternate names: PR_SCHDINFO_DISALLOW_OVERLAPPING_APPTS

2.976 PidTagScheduleInfoDisallowRecurringAppts

Canonical name: PidTagScheduleInfoDisallowRecurringAppts

Description: Indicates whether a client or server, when automatically responding to **meeting requests**, is to decline **Meeting Request objects** that represent a **recurring series**.

Property ID: 0x686E

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [MS-OXOCAL] section 2.2.12.3

Consuming reference: [MS-OXOPFFB]

Alternate names: PR_SCHDINFO_DISALLOW_RECURRING_APPTS

2.977 PidTagScheduleInfoDontMailDelegates

Canonical name: PidTagScheduleInfoDontMailDelegates

Description: Contains a value set to TRUE by the client, regardless of user input.

Property ID: 0x6843

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [MS-OXODLGT] section 2.2.2.2.7

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXOPFFB]

Alternate names: PR_SCHDINFO_DONT_MAIL_DELEGATES

2.978 PidTagScheduleInfoFreeBusy

Canonical name: PidTagScheduleInfoFreeBusy

Description: This property is deprecated and is not to be used.

Property ID: 0x686C

Data type: PtypBinary, 0x0102

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.4.3

Alternate names: PR_SCHDINFO_FREEBUSY

2.979 PidTagScheduleInfoFreeBusyAway

Canonical name: PidTagScheduleInfoFreeBusyAway

Description: Specifies the times for which the **free/busy status** is set a value of **OOF**.

Property ID: 0x6856

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.6

Alternate names: PR_SCHDINFO_FREEBUSY_OOF

2.980 PidTagScheduleInfoFreeBusyBusy

Canonical name: PidTagScheduleInfoFreeBusyBusy

Description: Specifies the blocks of time for which the **free/busy status** is set to a value of **busy**.

Property ID: 0x6854

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.4

Alternate names: PR_SCHDINFO_FREEBUSY_BUSY

2.981 PidTagScheduleInfoFreeBusyMerged

Canonical name: PidTagScheduleInfoFreeBusyMerged

Description: Specifies the blocks for which free/busy data of type **busy** or **OOF** is present in the free/busy message.

Property ID: 0x6850

Copyright © 2025 Microsoft Corporation

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.8

Alternate names: PR_SCHDINFO_FREEBUSY_MERGED

2.982 PidTagScheduleInfoFreeBusyTentative

Canonical name: PidTagScheduleInfoFreeBusyTentative

Description: Specifies the blocks of times for which the **free/busy status** is set to a value of **tentative**.

Property ID: 0x6852

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.2

Alternate names: PR_SCHDINFO_FREEBUSY_TENTATIVE

2.983 PidTagScheduleInfoMonthsAway

Canonical name: PidTagScheduleInfoMonthsAway

Description: Specifies the months for which free/busy data of type **OOF** is present in the free/busy message.

Property ID: 0x6855

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.5

Alternate names: PR_SCHDINFO_MONTHS_OOF

2.984 PidTagScheduleInfoMonthsBusy

Canonical name: PidTagScheduleInfoMonthsBusy

Description: Specifies the months for which free/busy data of type **busy** is present in the free/busy message.

Property ID: 0x6853

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.3

Consuming reference: [MS-OXMSG]

Alternate names: PR_SCHDINFO_MONTHS_BUSY

Copyright © 2025 Microsoft Corporation

2.985 PidTagScheduleInfoMonthsMerged

Canonical name: PidTagScheduleInfoMonthsMerged

Description: Specifies the months for which free/busy data of type **busy** or **OOF** is present in the free/busy message.

Property ID: 0x684F

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.7

Alternate names: PR_SCHDINFO_MONTHS_MERGED

2.986 PidTagScheduleInfoMonthsTentative

Canonical name: PidTagScheduleInfoMonthsTentative

Description: Specifies the months for which free/busy data of type **tentative** is present in the free/busy message.

Property ID: 0x6851

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.2.1

Alternate names: PR_SCHDINFO_MONTHS_TENTATIVE

2.987 PidTagScheduleInfoResourceType

Canonical name: PidTagScheduleInfoResourceType

Description: Set to 0x00000000 when sending and is ignored on receipt.

Property ID: 0x6841

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [MS-OXOPFFB] section 2.2.1.4.2

Alternate names: PR_SCHDINFO_RESOURCE_TYPE

2.988 PidTagSchedulePlusFreeBusyEntryId

Canonical name: PidTagSchedulePlusFreeBusyEntryId

Description: Contains the **EntryID** of the folder named "SCHEDULE+ FREE BUSY" under the non-IPM subtree of the **public folder message store**.

Property ID: 0x6622

Data type: PtypBinary, 0x0102

Copyright © 2025 Microsoft Corporation

Area: ExchangeMessageStore

Defining reference: [MS-OXOPFFB] section 2.2.2.2

Alternate names: PR_SPLUS_FREE_BUSY_ENTRYID

2.989 PidTagScriptData

Canonical name: PidTagScriptData

Description: Contains a series of instructions that can be executed to format an address and the data that is needed to execute those instructions.

Property ID: 0x0004

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [MS-OXOABKT] section 2.2.2

Alternate names: PR_EMS_SCRIPT_BLOB

2.990 PidTagSearchFolderDefinition

Canonical name: PidTagSearchFolderDefinition

Description: Specifies the search criteria and search options.

Property ID: 0x6845

Data type: PtypBinary, 0x0102

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.8

Alternate names: PR_WB_SF_DEFINITION

2.991 PidTagSearchFolderEfpFlags

Canonical name: PidTagSearchFolderEfpFlags

Description: Specifies **flags** that control how a folder is displayed.

Property ID: 0x6848

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.7

Alternate names: PR_WB_SF_EFP_FLAGS

2.992 PidTagSearchFolderExpiration

Canonical name: PidTagSearchFolderExpiration

Copyright © 2025 Microsoft Corporation

Description: Contains the time, in **UTC**, at which the search folder container will be stale and has to be updated or recreated.

Property ID: 0x683A

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.5

Alternate names: PR_WB_SF_EXPIRATION

2.993 PidTagSearchFolderId

Canonical name: PidTagSearchFolderId

Description: Contains a **GUID** that identifies the search folder.

Property ID: 0x6842

Data type: PtypBinary, 0x0102

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.1

Consuming reference: [MS-OXOCFG]

Alternate names: PR_WB_SF_ID

2.994 PidTagSearchFolderLastUsed

Canonical name: PidTagSearchFolderLastUsed

Description: Contains the last time, in **UTC**, that the folder was accessed.

Property ID: 0x6834

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.4

Alternate names: PR_WB_SF_LAST_USED

2.995 PidTagSearchFolderRecreateInfo

Canonical name: PidTagSearchFolderRecreateInfo

Description: This property is not to be used.

Property ID: 0x6844

Data type: PtypBinary, 0x0102

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.9

Copyright © 2025 Microsoft Corporation

Alternate names: PR_WB_SF_RECREATE_INFO

2.996 PidTagSearchFolderStorageType

Canonical name: PidTagSearchFolderStorageType

Description: Contains **flags** that specify the binary large object (BLOB) data that appears in the **PidTagSearchFolderDefinition** (section 2.990) property.

Property ID: 0x6846

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.6

Alternate names: PR_WB_SF_STORAGE_TYPE

2.997 PidTagSearchFolderTag

Canonical name: PidTagSearchFolderTag

Description: Contains the value of the **SearchFolderTag** sub-property of the **PidTagExtendedFolderFlags** (section 2.692) property of the search folder container.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.3

Alternate names: PR_WB_SF_TAG

2.998 PidTagSearchFolderTemplateId

Canonical name: PidTagSearchFolderTemplateId

Description: Contains the ID of the template that is being used for the search.

Property ID: 0x6841

Data type: PtypInteger32, 0x0003

Area: Search

Defining reference: [MS-OXOSRCH] section 2.2.1.2.2

Alternate names: PR_WB_SF_TEMPLATE_ID

2.999 PidTagSearchKey

Canonical name: PidTagSearchKey

Description: Contains a unique binary-comparable key that identifies an object for a search.

Property ID: 0x300B

Copyright © 2025 Microsoft Corporation

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [MS-OXCPRPT] section 2.2.1.9

Consuming references: [MS-OXCFOLD], [MS-OXCFXICS], [MS-OXCMSG], [MS-OXOCFG], [MS-OXOABK], [MS-OXOJRNL], [MS-OXOMSG], [MS-OXOPOST], [MS-OXORULE], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_SEARCH_KEY, ptagSearchKey

2.1000 PidTagSecurityDescriptorAsXml

Canonical name: PidTagSecurityDescriptorAsXml

Description: Contains security attributes in **XML**.

Property ID: 0x0E6A

Data type: PtypString, 0x001F

Area: Access Control Properties

Defining reference: [MS-XWDVSEC] section 2.2.2

Consuming reference: [MS-OXCPERM]

Alternate names: PR_NT_SECURITY_DESCRIPTOR_AS_XML, PR_NT_SECURITY_DESCRIPTOR_AS_XML_A, PR_NT_SECURITY_DESCRIPTOR_AS_XML_W, http://schemas.microsoft.com/exchange/security/descriptor

2.1001 PidTagSelectable

Canonical name: PidTagSelectable

Description: This property is not set and, if set, is ignored.

Property ID: 0x3609

Data type: PtypBoolean, 0x000B

Area: AB Container

Defining reference: [MS-OXOABKT] section 2.2.1

Alternate names: PR_SELECTABLE

2.1002 PidTagSenderAddressType

Canonical name: PidTagSenderAddressType

Description: Contains the email **address type** of the sending **mailbox** owner.

Property ID: 0x0C1E

Data type: PtypString, 0x001F

Area: Address Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOMSG] section 2.2.1.48

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOTASK], [MS-OXTNEF], [MS-OXOPOST]

Alternate names: PR_SENDER_ADDRTYPE, PR_SENDER_ADDRTYPE_A, ptagSenderAddrType, PR_SENDER_ADDRTYPE_W

2.1003 PidTagSenderEmailAddress

Canonical name: PidTagSenderEmailAddress

Description: Contains the email address of the sending **mailbox** owner.

Property ID: 0x0C1F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.49

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCSPAM], [MS-OXORSS], [MS-OXOTASK], [MS-OXPSVAL], [MS-OXTNEF]

Alternate names: PR_SENDER_EMAIL_ADDRESS, PR_SENDER_EMAIL_ADDRESS_A, PR_SENDER_EMAIL_ADDRESS_W

2.1004 PidTagSenderEntryId

Canonical name: PidTagSenderEntryId

Description: Identifies an address book **EntryID** that contains the address book EntryID of the sending **mailbox** owner.

Property ID: 0x0C19

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.50

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXOPOST], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_SENDER_ENTRYID, ptagSenderEntryId

2.1005 PidTagSenderIdStatus

Canonical name: PidTagSenderIdStatus

Description: Reports the results of a Sender-ID check.

Property ID: 0x4079

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOMSG] section 2.2.1.80

Consuming reference: [MS-OXCMAIL]

Alternate names: PR_SENDER_ID_STATUS

2.1006 PidTagSenderName

Canonical name: PidTagSenderName

Description: Contains the **display name** of the sending **mailbox** owner.

Property ID: 0x0C1A

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.51

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOCAL], [MS-OXOPOST], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_SENDER_NAME, PR_SENDER_NAME_A, ptagSenderName, PR_SENDER_NAME_W, urn:schemas:httpmail:sendername, http://schemas.microsoft.com/exchange/sender-name-utf8

2.1007 PidTagSenderSearchKey

Canonical name: PidTagSenderSearchKey

Description: Identifies an address book search key.

Property ID: 0x0C1D

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.52

Consuming references: [MS-OXCFXICS], [MS-OXOCAL], [MS-OXOPOST]

Alternate names: PR_SENDER_SEARCH_KEY, ptagSenderSearchKey

2.1008 PidTagSenderSmtpAddress

Canonical name: PidTagSenderSmtpAddress

Description: Contains the **SMTP** email address format of the e–mail address of the sending **mailbox** owner.

Property ID: 0x5D01

Data type: PtypString, 0x001F

Area: Mail

Defining reference: [MS-OXOMSG] section 2.2.1.55

Copyright © 2025 Microsoft Corporation

Consuming reference: [MS-OXCMAIL]

Alternate names: SenderSmtpAddress, ptagSenderSmtpAddress

2.1009 PidTagSenderTelephoneNumber

Canonical name: PidTagSenderTelephoneNumber

Description: Contains the telephone number of the caller associated with a voice mail message.

Property ID: 0x6802

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.1

Consuming references: [MS-OXCMAIL]

Alternate names: InternalSchemaSenderTelephoneNumber

2.1010 PidTagSendInternetEncoding

Canonical name: PidTagSendInternetEncoding

Description: Contains a bitmask of message encoding preferences for email sent to an email-enabled entity that is represented by this **Address Book object**.

Property ID: 0x3A71

Data type: PtypInteger32, 0x0003

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.3.19

Consuming references: [MS-OXCMAIL], [MS-OXCMSG], [MS-OXOMSG]

Alternate names: PR_SEND_INTERNET_ENCODING, ptagSendInternetEncoding

2.1011 PidTagSendRichInfo

Canonical name: PidTagSendRichInfo

Description: Indicates whether the email-enabled entity represented by the **Address Book object** can receive all message content, including **Rich Text Format (RTF)** and other embedded objects.

Property ID: 0x3A40

Data type: PtypBoolean, 0x000B

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.3.18

Consuming references: [MS-OXOAB], [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXCMSG], [MS-OXOMSG]

Alternate names: PR_SEND_RICH_INFO, ptagSendRichInfo

Copyright © 2025 Microsoft Corporation

2.1012 PidTagSensitivity

Canonical name: PidTagSensitivity

Description: Indicates the sender's assessment of the sensitivity of the **Message object**.

Property ID: 0x0036

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.13

Consuming references: [MS-OXCFXICS], [MS-OXCICAL], [MS-OXCMAIL], [MS-OXOMSG], [MS-OXTNEF], [MS-OXOCAL], [MS-OXODLGT], [MS-OXVCARD], [MS-OXWAVLS], [MS-XWDCAL], [MS-OXOJRNL], [MS-OXOCNTC], [MS-OXONOTE], [MS-OXOPOST], [MS-OXORMMS]

Alternate names: PR_SENSITIVITY, ptagSensitivity, http://schemas.microsoft.com/exchange/sensitivity-long, http://schemas.microsoft.com/exchange/sensitivity

2.1013 PidTagSentMailSvrEID

Canonical name: PidTagSentMailSvrEID

Description: Contains an **EntryID** that represents the **Sent Items folder** for the message.

Property ID: 0x6740

Data type: PtypServerId, 0x00FB

Area: ProviderDefinedNonTransmittable

Defining reference: [MS-OXOMSG] section 2.2.3.10

Consuming reference: [MS-OXCSTOR]

Alternate names: ptagSentMailSvrEID

2.1014 PidTagSentRepresentingAddressType

Canonical name: PidTagSentRepresentingAddressType

Description: Contains an email **address type**.

Property ID: 0x0064

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.54

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXODLGT], [MS-OXOPOST], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_SENT_REPRESENTING_ADDRTYPE, PR_SENT_REPRESENTING_ADDRTYPE_A, ptagSentRepresentingAddrType, PR_SENT_REPRESENTING_ADDRTYPE_W

Copyright © 2025 Microsoft Corporation

2.1015 PidTagSentRepresentingEmailAddress

Canonical name: PidTagSentRepresentingEmailAddress

Description: Contains an email address for the end user who is represented by the sending **mailbox** owner.

Property ID: 0x0065

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.55

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_SENT_REPRESENTING_EMAIL_ADDRESS, PR_SENT_REPRESENTING_EMAIL_ADDRESS_A, PR_SENT_REPRESENTING_EMAIL_ADDRESS_W

2.1016 PidTagSentRepresentingEntryId

Canonical name: PidTagSentRepresentingEntryId

Description: Contains the identifier of the end user who is represented by the sending **mailbox** owner.

Property ID: 0x0041

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.56

Consuming references: [MS-OXCDATA], [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOCAL], [MS-OXODLGT], [MS-OXOPOST], [MS-OXOTASK], [MS-OXTNEF]

Alternate names: PR_SENT_REPRESENTING_ENTRYID, ptagSentRepresentingEntryId

2.1017 PidTagSentRepresentingFlags

Canonical name: PidTagSentRepresentingFlags

Description:

Property ID: 0x401A

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming references: [MS-OXCFXICS], [MS-OXTNEF]

Alternate names: ptagSentRepresentingFlags

Copyright © 2025 Microsoft Corporation

2.1018 PidTagSentRepresentingName

Canonical name: PidTagSentRepresentingName

Description: Contains the **display name** for the end user who is represented by the sending **mailbox** owner.

Property ID: 0x0042

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.57

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOCAL], [MS-OXOCFG], [MS-OXODLGT], [MS-OXOPOST], [MS-OXORSS], [MS-OXTNEF]

Alternate names: PR_SENT_REPRESENTING_NAME, PR_SENT_REPRESENTING_NAME_A, ptagSentRepresentingName, PR_SENT_REPRESENTING_NAME_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

2.1019 PidTagSentRepresentingSearchKey

Canonical name: PidTagSentRepresentingSearchKey

Description: Contains a binary-comparable key that represents the end user who is represented by the sending **mailbox** owner.

Property ID: 0x003B

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [MS-OXOMSG] section 2.2.1.58

Consuming references: [MS-OXCFXICS], [MS-OXOCAL], [MS-OXOPOST], [MS-OXOTASK]

Alternate names: PR_SENT_REPRESENTING_SEARCH_KEY, ptagSentRepresentingSearchKey

2.1020 PidTagSentRepresentingSmtpAddress

Canonical name: PidTagSentRepresentingSmtpAddress

Description: Contains the SMTP email address of the end user who is represented by the sending mailbox owner.

Property ID: 0x5D02

Data type: PtypString, 0x001F

Area: Mail

Defining reference: [MS-OXOMSG] section 2.2.1.59

Alternate names: ptagRecipientSentRepresentingSMTPAddress, SentRepresentingSMTPAddressXSO, PR_SENT_REPRESENTING_SMTP_ADDRESS

Copyright © 2025 Microsoft Corporation

2.1021 PidTagSerializedReplidGuidMap

Canonical name: PidTagSerializedReplidGuidMap

Description: Contains a serialized list of **REPLID** and **REPLGUID** pairs which represent all or part of the REPLID / REPLGUID mapping of the associated **Logon object**.

Property ID: 0x6638

Data type: PtypBinary, 0x0102

Area: Logon Properties

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.13

Alternate names: ptagSerializedReplidGuidMap

2.1022 PidTagSmtpAddress

Canonical name: PidTagSmtpAddress

Description: Contains the **SMTP** address of the **Message object**.

Property ID: 0x39FE

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.3.21

Consuming references: [MS-OXCMAIL], [MS-OXOMSG], [MS-OXCMSG], [MS-OXOAB], [MS-OXSHARE]

Alternate names: PR_SMTP_ADDRESS, PR_SMTP_ADDRESS_A, PR_SMTP_ADDRESS_W

2.1023 PidTagSortLocaleId

Canonical name: PidTagSortLocaleId

Description: Contains the **locale** identifier.

Property ID: 0x6705

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

Defining reference: [MS-OXCSTOR] section 2.2.2.1.1.14

Consuming reference: [MS-OXPFOAB]

Alternate names: PR_SORT_LOCALE_ID, ptagSortLocaleId

2.1024 PidTagSourceKey

Canonical name: PidTagSourceKey

Description: Contains a value that contains an internal global identifier (GID) for this folder or message.

Copyright © 2025 Microsoft Corporation

Property ID: 0x65E0

Data type: PtypBinary, 0x0102

Area: Sync

Defining reference: [MS-OXCFXICS] section 2.2.1.2.5

Alternate names: PR_SOURCE_KEY

2.1025 PidTagSpokenName

Canonical name: PidTagSpokenName

Description: Contains a recording of the **mail user's** name pronunciation.

Property ID: 0x8CC2

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.41

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_UM_SPOKEN_NAME

2.1026 PidTagSpouseName

Canonical name: PidTagSpouseName

Description: Contains the name of the **mail user's** spouse/partner.

Property ID: 0x3A48

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.10.3

Consuming references: [MS-OXVCARD]

Alternate names: PR_SPOUSE_NAME, PR_SPOUSE_NAME_A, PR_SPOUSE_NAME_W, urn:schemas:contacts:spousecn

2.1027 PidTagStartDate

Canonical name: PidTagStartDate

Description: Contains the value of the **PidLidAppointmentStartWhole** property (section 2.29).

Property ID: 0x0060

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [MS-OXOCAL] section 2.2.1.30

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXORMDR], [MS-OXTNEF], [MS-XWDCAL],

Alternate names: PR_START_DATE, http://schemas.microsoft.com/mapi/start_date

2.1028 PidTagStartDateEtc

Canonical name: PidTagStartDateEtc

Description: Contains the default retention period, and the start date from which the age of a **Message object** is calculated.

Property ID: 0x301B

Data type: PtypBinary, 0x0102

Area: Archive

Defining reference: [MS-OXCMSG] section 2.2.1.60.4

Alternate names: PR_START_DATE_ETC, ptagStartDateEtc

2.1029 PidTagStateOrProvince

Canonical name: PidTagStateOrProvince

Description: Contains the name of the **mail user's** state or province.

Property ID: 0x3A28

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.17

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_STATE_OR_PROVINCE, PR_STATE_OR_PROVINCE_A, PR_STATE_OR_PROVINCE_W, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_A, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:mailingstate

2.1030 PidTagStoreEntryId

Canonical name: PidTagStoreEntryId

Description: Contains the unique **EntryID** of the **message store** where an object resides.

Property ID: 0x0FFB

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [MS-OXCMSG] section 2.2.1.44

Consuming references: [MS-OXOFLAG], [MS-OXSHARE], [MS-OXOCFG]

Alternate names: PR_STORE_ENTRYID, ptagStoreEntryId

Copyright © 2025 Microsoft Corporation

2.1031 PidTagStoreState

Canonical name: PidTagStoreState

Description: Indicates whether a **mailbox** has any active Search folders.

Property ID: 0x340E

Data type: PtypInteger32, 0x0003

Area: MapiMessageStore

Defining reference: [MS-OXCSTOR] section 2.2.2.1

Alternate names: PR_STORE_STATE

2.1032 PidTagStoreSupportMask

Canonical name: PidTagStoreSupportMask

Description: Indicates whether string properties within the .msg file are Unicode-encoded.

Property ID: 0x340D

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [MS-OXMSG] section 2.1.1.1

Alternate names: PR_STORE_SUPPORT_MASK, ptagStoreSupportMask

2.1033 PidTagStreetAddress

Canonical name: PidTagStreetAddress

Description: Contains the **mail user's** street address.

Property ID: 0x3A29

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.14

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_STREET_ADDRESS, PR_STREET_ADDRESS_A, PR_STREET_ADDRESS_W, PR_BUSINESS_ADDRESS_STREET, PR_BUSINESS_ADDRESS_STREET_A, PR_BUSINESS_ADDRESS_STREET_W, urn:schemas:contacts:mailingstreet

2.1034 PidTagSubfolders

Canonical name: PidTagSubfolders

Description: Specifies whether a folder has subfolders.

Property ID: 0x360A

Data type: PtypBoolean, 0x000B

Copyright © 2025 Microsoft Corporation

Area: MapiContainer

Defining reference: [MS-OXCFOLD] section 2.2.2.2.1.12

Alternate names: PR_SUBFOLDERS, ptagSubFolders, DAV:hassubs

2.1035 PidTagSubject

Canonical name: PidTagSubject

Description: Contains the subject of the email message.

Property ID: 0x0037

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.46

Consuming references: [MS-OXCICAL], [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOCNTC], [MS-OXOPFFB], [MS-OXTNEF], [MS-OXCDATA], [MS-OXCSPAM], [MS-OXCTABL], [MS-OXMSG], [MS-OXOCFG], [MS-OXOJRNL], [MS-OXORULE], [MS-OXPSVAL], [MS-OXWAVLS], [MS-XWDCAL]

Alternate names: PR_SUBJECT, PR_SUBJECT_A, ptagSubject, PR_SUBJECT_W, urn:schemas:httpmail:subject, http://schemas.microsoft.com/exchange/subject-utf8

2.1036 PidTagSubjectPrefix

Canonical name: PidTagSubjectPrefix

Description: Contains the prefix for the subject of the message.

Property ID: 0x003D

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [MS-OXCMSG] section 2.2.1.9

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXCPRPT], [MS-OXOCAL], [MS-OXOCNTC], [MS-OXODLGT], [MS-OXONOTE], [MS-OXOPFFB], [MS-OXOPOST], [MS-OXORSS], [MS-OXOSMMS], [MS-OXSHARE], [MS-OXTNEF]

Alternate names: PR_SUBJECT_PREFIX, PR_SUBJECT_PREFIX_A, ptagSubjectPrefix, PR_SUBJECT_PREFIX_W

2.1037 PidTagSupplementaryInfo

Canonical name: PidTagSupplementaryInfo

Description: Contains supplementary information about a delivery status notification, as specified in [RFC3464].

Property ID: 0x0C1B

Data type: PtypString, 0x001F

Area: Email

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOMSG] section 2.2.2.36

Consuming references: [MS-OXCMAIL]

Alternate names: PR_SUPPLEMENTARY_INFO, ptagSupplementaryInfo

2.1038 PidTagSurname

Canonical name: PidTagSurname

Description: Contains the **mail user's** family name.

Property ID: 0x3A11

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.1

Consuming references: [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_SURNAME, PR_SURNAME_A, PR_SURNAME_W, urn:schemas:contacts:sn

2.1039 PidTagSwappedToDoData

Canonical name: PidTagSwappedToDoData

Description: Contains a secondary storage location for **flags** when sender flags or sender **reminders** are supported.

Property ID: 0x0E2D

Data type: PtypBinary, 0x0102

Area: MapiNonTransmittable

Defining reference: [MS-OXOFLAG] section 2.2.1.7

Consuming reference: [MS-OXORMDR]

Alternate names: PR_SWAPPED_TODO_DATA, ptagSwappedTodoData

2.1040 PidTagSwappedToDoStore

Canonical name: PidTagSwappedToDoStore

Description: Contains the value of the **PidTagStoreEntryId** property (section 2.1030) of the message when the value of the **PidTagSwappedToDoData** property (section 2.1039) is set.

Property ID: 0x0E2C

Data type: PtypBinary, 0x0102

Area: MapiNonTransmittable

Defining reference: [MS-OXOFLAG] section 2.2.1.8

Consuming reference: [MS-OXORMDR], [MS-OXOSFLD]

Alternate names: PR_SWAPPED_TODO_STORE, ptagSwappedTodoStore

Copyright © 2025 Microsoft Corporation

2.1041 PidTagTargetEntryId

Canonical name: PidTagTargetEntryId

Description: Contains the message ID of a **Message object** being submitted for optimization ([MS-OXOMSG] section 3.2.4.4).

Property ID: 0x3010

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [MS-OXOMSG] section 2.2.1.76

Consuming references: [MS-OXCFXICS], [MS-OXCRPC]

Alternate names: PR_TARGET_ENTRYID, ptagTargetEntryId

2.1042 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Canonical name: PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Description: Contains the **mail user's** telecommunication device for the deaf (TTY/TDD) telephone number.

Property ID: 0x3A4B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.4.13

Consuming references: [MS-OXVCARD]

Alternate names: PR_TTYTDD_PHONE_NUMBER, PR_TTYTDD_PHONE_NUMBER_A, PR_TTYTDD_PHONE_NUMBER_W, urn:schemas:contacts:ttytddphone

2.1043 PidTagTelexNumber

Canonical name: PidTagTelexNumber

Description: Contains the **mail user's** telex number. This property is returned from an **NSPI** server as a **PtypMultipleBinary**. Otherwise, the data type is **PtypString**.

Property ID: 0x3A2C

Data type: PtypString, 0x001F; **PtypMultipleBinary**, 0x1102

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.30

Consuming references: [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_TELEX_NUMBER, PR_TELEX_NUMBER_A, PR_TELEX_NUMBER_W, urn:schemas:contacts:telexnumber

Copyright © 2025 Microsoft Corporation

2.1044 PidTagTemplateData

Canonical name: PidTagTemplateData

Description: Describes the controls used in the template that is used to retrieve address book information.

Property ID: 0x0001

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [MS-OXOABKT] section 2.2.2

Alternate names: PR_EMS_TEMPLATE_BLOB

2.1045 PidTagTemplateid

Canonical name: PidTagTemplateid

Description: Contains the value of the **PidTagEntryId** property (section 2.684), expressed as a **Permanent Entry ID** format.

Property ID: 0x3902

Data type: PtypBinary, 0x0102

Area: MapiAddressBook

Defining reference: [MS-OXOABK] section 2.2.3.3

Alternate names: PR_TEMPLATEID

2.1046 PidTagTextAttachmentCharset

Canonical name: PidTagTextAttachmentCharset

Description: Specifies the character set of an attachment received via **MIME** with the content-type of text.

Property ID: 0x371B

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [MS-OXCMSG] section 2.2.2.25

Consuming reference: [MS-OXCMAIL]

Alternate names: ptagTextAttachmentCharset

2.1047 PidTagThumbnailPhoto

Canonical name: PidTagThumbnailPhoto

Description: Contains the **mail user's** photo in .jpg format.

Property ID: 0x8C9E

Copyright © 2025 Microsoft Corporation

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [MS-OXOABK] section 2.2.4.40

Consuming reference: [MS-OXOAB]

Alternate names: PR_EMS_AB_THUMBNAIL_PHOTO

2.1048 PidTagTitle

Canonical name: PidTagTitle

Description: Contains the **mail user's** job title.

Property ID: 0x3A17

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.4

Consuming references: [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_TITLE, PR_TITLE_A, PR_TITLE_W, urn:schemas:contacts:title

2.1049 PidTagTnefCorrelationKey

Canonical name: PidTagTnefCorrelationKey

Description: Contains a value that correlates a **Transport Neutral Encapsulation Format (TNEF)** attachment with a message.

Property ID: 0x007F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [MS-OXCMSG] section 2.2.1.29

Consuming reference: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXTNEF]

Alternate names: PR_TNEF_CORRELATION_KEY

2.1050 PidTagToDoItemFlags

Canonical name: PidTagToDoItemFlags

Description: Contains **flags** associated with objects.

Property ID: 0x0E2B

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [MS-OXOFLAG] section 2.2.1.6

Copyright © 2025 Microsoft Corporation

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL], [MS-OXOSFLD]

Alternate names: PR_TODO_ITEM_FLAGS, ptagToDoItemFlags

2.1051 PidTagTransmittableDisplayName

Canonical name: PidTagTransmittableDisplayName

Description: Contains an **Address Book object's display name** that is transmitted with the message.

Property ID: 0x3A20

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [MS-OXOABK] section 2.2.3.8

Consuming references: [MS-OXCFXICS], [MS-OXCMSG]

Alternate names: PR_TRANSMITABLE_DISPLAY_NAME, PR_TRANSMITABLE_DISPLAY_NAME_A, ptagTransmitableDisplayName, PR_TRANSMITABLE_DISPLAY_NAME_W

2.1052 PidTagTransportMessageHeaders

Canonical name: PidTagTransportMessageHeaders

Description: Contains transport-specific message envelope information for email.

Property ID: 0x007D

Data type: PtypString, 0x001F

Area: Email

Defining reference: [MS-OXOMSG] section 2.2.1.61

Consuming references: [MS-OXCFXICS], [MS-OXCMAIL]

Alternate names: PR_TRANSPORT_MESSAGE_HEADERS, PR_TRANSPORT_MESSAGE_HEADERS_A, PR_TRANSPORT_MESSAGE_HEADERS_W

2.1053 PidTagTrustSender

Canonical name: PidTagTrustSender

Description: Specifies whether the associated message was delivered through a trusted transport channel.

Property ID: 0x0E79

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [MS-OXCMSG] section 2.2.1.45

Consuming references: [MS-OXCFXICS], [MS-OXCMSG]

Copyright © 2025 Microsoft Corporation

Alternate names: PR_TRUST_SENDER, ptagTrustSender

2.1054 PidTagUserCertificate

Canonical name: PidTagUserCertificate

Description: Contains an ASN.1 authentication certificate for a messaging user.

Property ID: 0x3A22

Data type: PtypBinary, 0x0102

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.34

Consuming references: [MS-OXOAB]

Alternate names: PR_USER_CERTIFICATE, ptagUserCertificate, urn:schemas:contacts:usercertificate

2.1055 PidTagUserEntryId

Canonical name: PidTagUserEntryId

Description: Address book **EntryID** of the user logged on to the **public folders**.

Property ID: 0x6619

Data type: PtypBinary, 0x0102

Area: ExchangeMessageStore

Defining reference: [MS-OXCSTOR] section 2.2.2.1

Alternate names: PR_USER_ENTRYID, ptagUserEntryId

2.1056 PidTagUserX509Certificate

Canonical name: PidTagUserX509Certificate

Description: Contains a list of certificates for the **mail user**.

Property ID: 0x3A70

Data type: PtypMultipleBinary, 0x1102

Area: MapiMailUser

Defining reference: [MS-OXOABK] section 2.2.4.36

Consuming references: [MS-OXLDAP], [MS-OXOAB], [MS-OXOCNTC], [MS-OXVCARD]

Alternate names: PR_USER_X509_CERTIFICATE

2.1057 PidTagViewDescriptorBinary

Canonical name: PidTagViewDescriptorBinary

Description: Contains view definitions.

Copyright © 2025 Microsoft Corporation

Property ID: 0x7001

Data type: PtypBinary, 0x0102

Area: MessageClassDefinedTransmittable

Defining reference: [MS-OXOCFG] section 2.2.6.1

Alternate names: PR_VD_BINARY

2.1058 PidTagViewDescriptorName

Canonical name: PidTagViewDescriptorName

Description: Contains the view descriptor name.

Property ID: 0x7006

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference: [MS-OXOCFG] section 2.2.6.2

Alternate names: PR_VD_NAME, PR_VD_NAME_W

2.1059 PidTagViewDescriptorStrings

Canonical name: PidTagViewDescriptorStrings

Description: Contains view definitions in string format.

Property ID: 0x7002

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference: [MS-OXOCFG] section 2.2.6.3

Alternate names: PR_VD_STRINGS, PR_VD_STRINGS_W

2.1060 PidTagViewDescriptorVersion

Canonical name: PidTagViewDescriptorVersion

Description: Contains the View Descriptor version.

Property ID: 0x7007

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:[MS-OXOCFG] section 2.2.6.4

Alternate names: PR_VD_VERSION

Copyright © 2025 Microsoft Corporation

2.1061 PidTagVoiceMessageAttachmentOrder

Canonical name: PidTagVoiceMessageAttachmentOrder

Description: Contains a list of file names for the audio file attachments that are to be played as part of a message.

Property ID: 0x6805

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.9

Consuming references: [MS-OXCMAIL]

Alternate names: InternalSchemaVoiceMessageAttachmentOrder

2.1062 PidTagVoiceMessageDuration

Canonical name: PidTagVoiceMessageDuration

Description: Specifies the length of the attached audio message, in seconds.

Property ID: 0x6801

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.3

Consuming references: [MS-OXCMAIL]

Alternate names: InternalSchemaVoiceMessageDuration

2.1063 PidTagVoiceMessageSenderName

Canonical name: PidTagVoiceMessageSenderName

Description: Specifies the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

Property ID: 0x6803

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [MS-OXOUM] section 2.2.5.5

Consuming references: [MS-OXCMAIL]

Alternate names: InternalSchemaVoiceMessageSenderName

2.1064 PidTagWeddingAnniversary

Canonical name: PidTagWeddingAnniversary

Description: Contains the date of the **mail user's** wedding anniversary.

Copyright © 2025 Microsoft Corporation

Property ID: 0x3A41

Data type: PtypTime, 0x0040

Area: MapiMailUser

Defining reference: [MS-OXOCNTC] section 2.2.1.5.4

Consuming references: [MS-OXVCARD]

Alternate names: PR_WEDDING_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

2.1065 PidTagWlinkAddressBookEID

Canonical name: PidTagWlinkAddressBookEID

Description: Specifies the value of the **PidTagEntryId** property (section 2.684) of the user to whom the folder belongs.

Property ID: 0x6854

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.16

Alternate names: PR_WLINK_ABEID

2.1066 PidTagWlinkAddressBookStoreEID

Canonical name: PidTagWlinkAddressBookStoreEID

Description: Specifies the value of the **PidTagStoreEntryId** property (section 2.1030) of the current user (not the owner of the folder).

Property ID: 0x6891

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.17

Alternate names: PR_WLINK_AB_EXSTOREEID

2.1067 PidTagWlinkCalendarColor

Canonical name: PidTagWlinkCalendarColor

Description: Specifies the background color of the **calendar**.

Property ID: 0x6853

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.15

Alternate names: PR_WLINK_CALENDAR_COLOR

Copyright © 2025 Microsoft Corporation

2.1068 PidTagWlinkClientID

Canonical name: PidTagWlinkClientID

Description: Specifies the Client ID that allows the client to determine whether the shortcut was created on the current machine/user via an equality test.

Property ID: 0x6890

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.18

Alternate names: PR_WLINK_CLIENTID

2.1069 PidTagWlinkEntryId

Canonical name: PidTagWlinkEntryId

Description: Specifies the **EntryID** of the folder pointed to by the shortcut.

Property ID: 0x684C

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.8

Alternate names: PR_WLINK_ENTRYID

2.1070 PidTagWlinkFlags

Canonical name: PidTagWlinkFlags

Description: Specifies conditions associated with the shortcut.

Property ID: 0x684A

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.6

Alternate names: PR_WLINK_FLAGS

2.1071 PidTagWlinkFolderType

Canonical name: PidTagWlinkFolderType

Description: Specifies the type of folder pointed to by the shortcut.

Property ID: 0x684F

Data type: PtypBinary, 0x0102

Area: Configuration

Copyright © 2025 Microsoft Corporation

Defining reference: [MS-OXOCFG] section 2.2.9.11

Alternate names: PR_WLINK_FOLDER_TYPE

2.1072 PidTagWlinkGroupClsid

Canonical name: PidTagWlinkGroupClsid

Description: Specifies the value of the **PidTagWlinkGroupHeaderID** property (section 2.1072) of the **group header** associated with the shortcut.

Property ID: 0x6850

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.12

Alternate names: PR_WLINK_GROUP_CLSID

2.1073 PidTagWlinkGroupHeaderID

Canonical name: PidTagWlinkGroupHeaderID

Description: Specifies the ID of the **navigation shortcut** that groups other navigation shortcuts.

Property ID: 0x6842

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.3

Alternate names:

2.1074 PidTagWlinkGroupName

Canonical name: PidTagWlinkGroupName

Description: Specifies the value of the **PidTagNormalizedSubject** (section 2.814) of the **group header** associated with the shortcut.

Property ID: 0x6851

Data type: PtypString, 0x001F

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.13

Alternate names: PR_WLINK_GROUP_NAME

2.1075 PidTagWlinkOrdinal

Canonical name: PidTagWlinkOrdinal

Description: Specifies a variable-length binary property to be used to sort shortcuts lexicographically.

Copyright © 2025 Microsoft Corporation

Property ID: 0x684B

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.7

Alternate names: PR_WLINK_ORDINAL

2.1076 PidTagWlinkRecordKey

Canonical name: PidTagWlinkRecordKey

Description: Specifies the value of **PidTagRecordKey** property (section 2.912) of the folder pointed to by the shortcut.

Property ID: 0x684D

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.9

Alternate names: PR_WLINK_RECKEY

2.1077 PidTagWlinkROGroupType

Canonical name: PidTagWlinkROGroupType

Description: Specifies the type of **group header**.

Property ID: 0x6892

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.19

Alternate names: PR_WLINK_RO_GROUP_TYPE

2.1078 PidTagWlinkSaveStamp

Canonical name: PidTagWlinkSaveStamp

Description: Specifies an integer that allows a client to identify with a high probability whether the **navigation shortcut** was saved by the current client session.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.4

Alternate names:

Copyright © 2025 Microsoft Corporation

2.1079 PidTagWlinkSection

Canonical name: PidTagWlinkSection

Description: Specifies the section where the shortcut will be grouped.

Property ID: 0x6852

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.14

Alternate names: PR_WLINK_SECTION

2.1080 PidTagWlinkStoreEntryId

Canonical name: PidTagWlinkStoreEntryId

Description: Specifies the value of the **PidTagStoreEntryId** property (section 2.1030) of the folder pointed to by the shortcut.

Property ID: 0x684E

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.10

Alternate names: PR_WLINK_STORE_ENTRYID

2.1081 PidTagWlinkType

Canonical name: PidTagWlinkType

Description: Specifies the type of **navigation shortcut**.

Property ID: 0x6849

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [MS-OXOCFG] section 2.2.9.5

Alternate names: PR_WLINK_TYPE

Copyright © 2025 Microsoft Corporation

3 Structure Examples

None.

Copyright © 2025 Microsoft Corporation

4 Security

There are no security considerations unique to this specification.

4.1 Security Considerations for Implementers

None.

4.2 Index of Security Fields

None.

Copyright © 2025 Microsoft Corporation

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include updates to those products.

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Exchange Server 2016
- Microsoft Exchange Server 2019
- Microsoft Office Outlook 2003
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013
- Microsoft Outlook 2016
- Microsoft Outlook 2019
- Microsoft Outlook 2021
- Microsoft Outlook LTSC 2024
- Microsoft Exchange Server Subscription Edition

Exceptions, if any, are noted in this section. If an update version, service pack or Knowledge Base (KB) number appears with a product name, the behavior changed in that update. The new behavior also applies to subsequent updates unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms "SHOULD" or "SHOULD NOT" implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term "MAY" implies that the product does not follow the prescription.

Copyright © 2025 Microsoft Corporation

6 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as Major, Minor, or None.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements.
- A document revision that captures changes to protocol functionality.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **None** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the relevant technical content is identical to the last released version.

The changes made to this document are listed in the following table. For more information, please contact dochelp@microsoft.com.

Section	Description	Revision class
5 Appendix A: Product Behavior	Updated list of supported products.	Major

Copyright © 2025 Microsoft Corporation

7 Index

A

Applicability 40

C

Change tracking 376

E

Examples 373

F

Fields - security index 374
Fields - vendor-extensible 41

G

Glossary 24

I

Implementer - security considerations 374
Index of security fields 374
Informative references 34
Introduction 24

L

Localization 40

N

Normative references 32

O

Overview
  common message classes 36
  commonly used property sets 37
  property ID ranges 38
  WebDAV property naming 39
Overview (synopsis) 34

P

Product behavior 375

R

References 32
  informative 34
  normative 32
Relationship to protocols and other structures 40

S

Security
  field index 374
  implementer considerations 374

T

Tracking changes 376

V

Vendor-extensible fields 41
Versioning 40

Copyright © 2025 Microsoft Corporation