

# [MS-OXPROPS]: Exchange Server Protocols Master Property List

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplq@microsoft.com](mailto:iplq@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Updated references to reflect date of initial release.
09/03/2008	1.02		Changed title of document.
10/01/2008	1.03		Revised and edited technical content.
12/03/2008	1.04		Revised and edited technical content.
02/04/2009	1.05		Revised and edited technical content.
03/04/2009	1.06		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	5.0.0	Major	Updated and revised the technical content.

# Table of Contents

<b>1 Introduction</b> .....	<b>27</b>
1.1 Glossary.....	27
1.2 References.....	27
1.2.1 Normative References .....	27
1.2.2 Informative References .....	30
1.3 Structure Overview .....	30
1.3.1 Common Message Classes.....	30
1.3.2 Commonly Used Property Sets .....	32
1.3.3 Property ID Ranges .....	33
1.3.4 WebDAV Property Naming .....	34
1.3.4.1 http://schemas.microsoft.com/mapi/proptag Namespace .....	34
1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace .....	34
1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace.....	35
1.4 Relationship to Protocols and Other Structures .....	35
1.5 Applicability Statement.....	35
1.6 Versioning and Localization .....	35
1.7 Vendor-Extensible Fields .....	35
<b>2 Structures</b> .....	<b>36</b>
2.1 PidLidAddressBookProviderArrayType .....	36
2.2 PidLidAddressBookProviderEmailList .....	36
2.3 PidLidAddressCountryCode .....	36
2.4 PidLidAgingDontAgeMe.....	37
2.5 PidLidAllAttendeesList.....	37
2.6 PidLidAllAttendeesString.....	37
2.7 PidLidAllowExternalCheck.....	38
2.8 PidLidAnniversaryEventEntryId .....	38
2.9 PidLidAppointmentAuxiliaryFlags.....	38
2.10 PidLidAppointmentColor.....	38
2.11 PidLidAppointmentCounterProposal.....	39
2.12 PidLidAppointmentDuration .....	39
2.13 PidLidAppointmentEndDate.....	40
2.14 PidLidAppointmentEndTime .....	40
2.15 PidLidAppointmentEndWhole .....	40
2.16 PidLidAppointmentLastSequence.....	41
2.17 PidLidAppointmentMessageClass.....	41
2.18 PidLidAppointmentNotAllowPropose .....	41
2.19 PidLidAppointmentProposalNumber.....	42
2.20 PidLidAppointmentProposedDuration.....	42
2.21 PidLidAppointmentProposedEndWhole.....	42
2.22 PidLidAppointmentProposedStartWhole .....	43
2.23 PidLidAppointmentRecur.....	43
2.24 PidLidAppointmentReplyName .....	43
2.25 PidLidAppointmentReplyTime.....	44
2.26 PidLidAppointmentSequence.....	44
2.27 PidLidAppointmentSequenceTime .....	45
2.28 PidLidAppointmentStartDate .....	45
2.29 PidLidAppointmentStartTime.....	45
2.30 PidLidAppointmentStartWhole.....	46
2.31 PidLidAppointmentStateFlags.....	46

2.32	PidLidAppointmentSubType .....	46
2.33	PidLidAppointmentTimeZoneDefinitionEndDisplay .....	47
2.34	PidLidAppointmentTimeZoneDefinitionRecur .....	47
2.35	PidLidAppointmentTimeZoneDefinitionStartDisplay.....	48
2.36	PidLidAppointmentUnsendableRecipients.....	48
2.37	PidLidAppointmentUpdateTime .....	48
2.38	PidLidAttendeeCriticalChange .....	49
2.39	PidLidAutoFillLocation .....	49
2.40	PidLidAutoLog .....	49
2.41	PidLidAutoProcessState .....	50
2.42	PidLidAutoStartCheck .....	50
2.43	PidLidAutoStartWhen.....	50
2.44	PidLidBilling.....	51
2.45	PidLidBirthdayEventEntryId .....	51
2.46	PidLidBirthdayLocal .....	51
2.47	PidLidBusinessCardCardPicture .....	52
2.48	PidLidBusinessCardDisplayDefinition .....	52
2.49	PidLidBusyStatus.....	52
2.50	PidLidCalendarType .....	53
2.51	PidLidCategories.....	53
2.52	PidLidCcAttendeesString.....	53
2.53	PidLidChangeHighlight.....	54
2.54	PidLidClassification .....	54
2.55	PidLidClassificationDescription .....	54
2.56	PidLidClassificationGuid .....	55
2.57	PidLidClassificationKeep.....	55
2.58	PidLidClassified.....	55
2.59	PidLidCleanGlobalObjectId.....	55
2.60	PidLidClientIntent.....	56
2.61	PidLidClipEnd .....	56
2.62	PidLidClipStart.....	56
2.63	PidLidCollaborateDoc.....	57
2.64	PidLidCommonEnd.....	57
2.65	PidLidCommonStart.....	57
2.66	PidLidCompanies .....	58
2.67	PidLidConferencingCheck.....	58
2.68	PidLidConferencingType.....	58
2.69	PidLidContactCharacterSet.....	59
2.70	PidLidContactItemData .....	59
2.71	PidLidContactLinkEntry .....	59
2.72	PidLidContactLinkName .....	60
2.73	PidLidContactLinkSearchKey .....	60
2.74	PidLidContacts.....	60
2.75	PidLidContactUserField1 .....	61
2.76	PidLidContactUserField2 .....	61
2.77	PidLidContactUserField3 .....	61
2.78	PidLidContactUserField4 .....	62
2.79	PidLidConversationActionLastAppliedTime .....	62
2.80	PidLidConversationActionMaxDeliveryTime .....	63
2.81	PidLidConversationActionMoveFolderEid.....	63
2.82	PidLidConversationActionMoveStoreEid .....	63
2.83	PidLidConversationActionVersion .....	64
2.84	PidLidConversationProcessed.....	64

2.85	PidLidCurrentVersion .....	64
2.86	PidLidCurrentVersionName .....	65
2.87	PidLidDayInterval .....	65
2.88	PidLidDayOfMonth .....	65
2.89	PidLidDelegateMail .....	66
2.90	PidLidDepartment.....	66
2.91	PidLidDirectory .....	66
2.92	PidLidDistributionListChecksum.....	67
2.93	PidLidDistributionListMembers .....	67
2.94	PidLidDistributionListName .....	67
2.95	PidLidDistributionListOneOffMembers .....	68
2.96	PidLidDistributionListStream.....	68
2.97	PidLidEmail1AddressType .....	68
2.98	PidLidEmail1DisplayName.....	69
2.99	PidLidEmail1EmailAddress .....	69
2.100	PidLidEmail1OriginalDisplayName .....	69
2.101	PidLidEmail1OriginalEntryId.....	70
2.102	PidLidEmail1RichTextFormat.....	70
2.103	PidLidEmail2AddressType .....	70
2.104	PidLidEmail2DisplayName.....	71
2.105	PidLidEmail2EmailAddress .....	71
2.106	PidLidEmail2OriginalDisplayName .....	71
2.107	PidLidEmail2OriginalEntryId.....	72
2.108	PidLidEmail2RichTextFormat.....	72
2.109	PidLidEmail3AddressType .....	72
2.110	PidLidEmail3DisplayName.....	73
2.111	PidLidEmail3EmailAddress .....	73
2.112	PidLidEmail3OriginalDisplayName .....	73
2.113	PidLidEmail3OriginalEntryId.....	74
2.114	PidLidEmail3RichTextFormat.....	74
2.115	PidLidEmailList .....	74
2.116	PidLidEndRecurrenceDate .....	74
2.117	PidLidEndRecurrenceTime .....	75
2.118	PidLidExceptionReplaceTime .....	75
2.119	PidLidFax1AddressType .....	76
2.120	PidLidFax1EmailAddress .....	76
2.121	PidLidFax1OriginalDisplayName .....	76
2.122	PidLidFax1OriginalEntryId.....	77
2.123	PidLidFax2AddressType .....	77
2.124	PidLidFax2EmailAddress .....	77
2.125	PidLidFax2OriginalDisplayName .....	78
2.126	PidLidFax2OriginalEntryId.....	78
2.127	PidLidFax3AddressType .....	78
2.128	PidLidFax3EmailAddress .....	79
2.129	PidLidFax3OriginalDisplayName .....	79
2.130	PidLidFax3OriginalEntryId.....	79
2.131	PidLidFExceptionalAttendees.....	80
2.132	PidLidFExceptionalBody .....	80
2.133	PidLidFileUnder.....	80
2.134	PidLidFileUnderId.....	81
2.135	PidLidFileUnderList .....	81
2.136	PidLidFInvited.....	81
2.137	PidLidFlagRequest .....	82

2.138	PidLidFlagString.....	82
2.139	PidLidForwardInstance.....	83
2.140	PidLidForwardNotificationRecipients.....	83
2.141	PidLidFOthersAppointment.....	83
2.142	PidLidFreeBusyLocation.....	84
2.143	PidLidGlobalObjectId.....	84
2.144	PidLidHasPicture.....	84
2.145	PidLidHomeAddress.....	85
2.146	PidLidHomeAddressCountryCode.....	85
2.147	PidLidHtml.....	85
2.148	PidLidICalendarDayOfWeekMask.....	86
2.149	PidLidInboundICalStream.....	86
2.150	PidLidInfoPathFormName.....	86
2.151	PidLidInstantMessagingAddress.....	86
2.152	PidLidIntendedBusyStatus.....	87
2.153	PidLidInternetAccountName.....	87
2.154	PidLidInternetAccountStamp.....	88
2.155	PidLidIsException.....	88
2.156	PidLidIsRecurring.....	88
2.157	PidLidIsSilent.....	89
2.158	PidLidLinkedTaskItems.....	89
2.159	PidLidLocation.....	89
2.160	PidLidLogDocumentPosted.....	90
2.161	PidLidLogDocumentPrinted.....	90
2.162	PidLidLogDocumentRouted.....	90
2.163	PidLidLogDocumentSaved.....	91
2.164	PidLidLogDuration.....	91
2.165	PidLidLogEnd.....	91
2.166	PidLidLogFlags.....	92
2.167	PidLidLogStart.....	92
2.168	PidLidLogType.....	92
2.169	PidLidLogTypeDesc.....	93
2.170	PidLidMeetingType.....	93
2.171	PidLidMeetingWorkspaceUrl.....	93
2.172	PidLidMonthInterval.....	94
2.173	PidLidMonthOfYear.....	94
2.174	PidLidMonthOfYearMask.....	95
2.175	PidLidNetShowUrl.....	95
2.176	PidLidNoEndDateFlag.....	95
2.177	PidLidNonSendableBcc.....	96
2.178	PidLidNonSendableCc.....	96
2.179	PidLidNonSendableTo.....	96
2.180	PidLidNonSendBccTrackStatus.....	97
2.181	PidLidNonSendCcTrackStatus.....	97
2.182	PidLidNonSendToTrackStatus.....	97
2.183	PidLidNoteColor.....	98
2.184	PidLidNoteHeight.....	98
2.185	PidLidNoteWidth.....	98
2.186	PidLidNoteX.....	99
2.187	PidLidNoteY.....	99
2.188	PidLidOccurrences.....	99
2.189	PidLidOldLocation.....	100
2.190	PidLidOldRecurrenceType.....	100

2.191	PidLidOldWhenEndWhole	101
2.192	PidLidOldWhenStartWhole	101
2.193	PidLidOnlinePassword	101
2.194	PidLidOptionalAttendees	102
2.195	PidLidOrganizerAlias	102
2.196	PidLidOriginalStoreEntryId	102
2.197	PidLidOtherAddress	103
2.198	PidLidOtherAddressCountryCode	103
2.199	PidLidOwnerCriticalChange	103
2.200	PidLidOwnerName	104
2.201	PidLidPercentComplete	104
2.202	PidLidPostalAddressId	104
2.203	PidLidPostRssChannel	105
2.204	PidLidPostRssChannelLink	105
2.205	PidLidPostRssItemGuid	106
2.206	PidLidPostRssItemHash	106
2.207	PidLidPostRssItemLink	106
2.208	PidLidPostRssItemXml	107
2.209	PidLidPostRssSubscription	107
2.210	PidLidPrivate	107
2.211	PidLidPromptSendUpdate	108
2.212	PidLidRecurrenceDuration	108
2.213	PidLidRecurrencePattern	108
2.214	PidLidRecurrenceType	109
2.215	PidLidRecurring	109
2.216	PidLidReferenceEntryId	110
2.217	PidLidReferredBy	110
2.218	PidLidReminderDelta	110
2.219	PidLidReminderFileParameter	111
2.220	PidLidReminderOverride	111
2.221	PidLidReminderPlaySound	111
2.222	PidLidReminderSet	112
2.223	PidLidReminderSignalTime	112
2.224	PidLidReminderTime	112
2.225	PidLidReminderTimeDate	113
2.226	PidLidReminderTimeTime	113
2.227	PidLidReminderType	114
2.228	PidLidRemoteStatus	114
2.229	PidLidRequiredAttendees	114
2.230	PidLidResourceAttendees	115
2.231	PidLidResponseStatus	115
2.232	PidLidSendMeetingAsIcal	115
2.233	PidLidServerProcessed	116
2.234	PidLidServerProcessingActions	116
2.235	PidLidSharingAnonymity	116
2.236	PidLidSharingBindingEntryId	117
2.237	PidLidSharingBrowseUrl	117
2.238	PidLidSharingCapabilities	117
2.239	PidLidSharingConfigurationUrl	118
2.240	PidLidSharingDataRangeEnd	118
2.241	PidLidSharingDataRangeStart	118
2.242	PidLidSharingDetail	118
2.243	PidLidSharingExtensionXml	119

2.244	PidLidSharingFilter.....	119
2.245	PidLidSharingFlags .....	119
2.246	PidLidSharingFlavor.....	120
2.247	PidLidSharingFolderEntryId.....	120
2.248	PidLidSharingIndexEntryId .....	120
2.249	PidLidSharingInitiatorEntryId.....	120
2.250	PidLidSharingInitiatorName .....	121
2.251	PidLidSharingInitiatorSmtip .....	121
2.252	PidLidSharingInstanceGuid .....	121
2.253	PidLidSharingLastAutoSyncTime .....	122
2.254	PidLidSharingLastSyncTime .....	122
2.255	PidLidSharingLocalComment.....	122
2.256	PidLidSharingLocalLastModificationTime .....	123
2.257	PidLidSharingLocalName.....	123
2.258	PidLidSharingLocalPath.....	123
2.259	PidLidSharingLocalStoreUid.....	123
2.260	PidLidSharingLocalType .....	124
2.261	PidLidSharingLocalUid.....	124
2.262	PidLidSharingOriginalMessageEntryId .....	124
2.263	PidLidSharingParentBindingEntryId .....	125
2.264	PidLidSharingParticipants.....	125
2.265	PidLidSharingPermissions .....	125
2.266	PidLidSharingProviderExtension .....	125
2.267	PidLidSharingProviderGuid.....	126
2.268	PidLidSharingProviderName .....	126
2.269	PidLidSharingProviderUrl .....	126
2.270	PidLidSharingRangeEnd .....	127
2.271	PidLidSharingRangeStart .....	127
2.272	PidLidSharingReciprocation.....	127
2.273	PidLidSharingRemoteByteSize.....	128
2.274	PidLidSharingRemoteComment.....	128
2.275	PidLidSharingRemoteCrc.....	128
2.276	PidLidSharingRemoteLastModificationTime .....	128
2.277	PidLidSharingRemoteMessageCount.....	129
2.278	PidLidSharingRemoteName.....	129
2.279	PidLidSharingRemotePass.....	129
2.280	PidLidSharingRemotePath.....	130
2.281	PidLidSharingRemoteStoreUid.....	130
2.282	PidLidSharingRemoteType .....	130
2.283	PidLidSharingRemoteUid.....	131
2.284	PidLidSharingRemoteUser.....	131
2.285	PidLidSharingRemoteVersion .....	131
2.286	PidLidSharingResponseTime .....	131
2.287	PidLidSharingResponseType.....	132
2.288	PidLidSharingRoamLog .....	132
2.289	PidLidSharingStart.....	132
2.290	PidLidSharingStatus.....	133
2.291	PidLidSharingStop .....	133
2.292	PidLidSharingSyncFlags .....	133
2.293	PidLidSharingSyncInterval.....	134
2.294	PidLidSharingTimeToLive .....	134
2.295	PidLidSharingTimeToLiveAuto .....	134
2.296	PidLidSharingWorkingHoursDays.....	134



2.297	PidLidSharingWorkingHoursEnd .....	135
2.298	PidLidSharingWorkingHoursStart .....	135
2.299	PidLidSharingWorkingHoursTimeZone .....	135
2.300	PidLidSideEffects .....	135
2.301	PidLidSingleBodyICal .....	136
2.302	PidLidSingleInvite .....	136
2.303	PidLidSmartNoAttach .....	136
2.304	PidLidSpamOriginalFolder .....	137
2.305	PidLidStartRecurrenceDate .....	137
2.306	PidLidStartRecurrenceTime .....	137
2.307	PidLidTaskAcceptanceState .....	138
2.308	PidLidTaskAccepted .....	138
2.309	PidLidTaskActualEffort .....	139
2.310	PidLidTaskAssigner .....	139
2.311	PidLidTaskAssigners .....	139
2.312	PidLidTaskComplete .....	140
2.313	PidLidTaskCustomFlags .....	140
2.314	PidLidTaskDateCompleted .....	140
2.315	PidLidTaskDeadOccurrence .....	141
2.316	PidLidTaskDueDate .....	141
2.317	PidLidTaskEstimatedEffort .....	141
2.318	PidLidTaskFCreator .....	142
2.319	PidLidTaskFFixOffline .....	142
2.320	PidLidTaskFRecurring .....	142
2.321	PidLidTaskGlobalId .....	143
2.322	PidLidTaskHistory .....	143
2.323	PidLidTaskLastDelegate .....	143
2.324	PidLidTaskLastUpdate .....	144
2.325	PidLidTaskLastUser .....	144
2.326	PidLidTaskMode .....	144
2.327	PidLidTaskMultipleRecipients .....	145
2.328	PidLidTaskNoCompute .....	145
2.329	PidLidTaskOrdinal .....	145
2.330	PidLidTaskOwner .....	146
2.331	PidLidTaskOwnership .....	146
2.332	PidLidTaskRecurrence .....	146
2.333	PidLidTaskResetReminder .....	147
2.334	PidLidTaskRole .....	147
2.335	PidLidTaskStartDate .....	147
2.336	PidLidTaskState .....	148
2.337	PidLidTaskStatus .....	148
2.338	PidLidTaskStatusOnComplete .....	148
2.339	PidLidTaskUpdates .....	149
2.340	PidLidTaskVersion .....	149
2.341	PidLidTeamTask .....	149
2.342	PidLidTime Zone .....	150
2.343	PidLidTime ZoneDescription .....	150
2.344	PidLidTime ZoneStruct .....	150
2.345	PidLidToAttendeesString .....	151
2.346	PidLidToDoOrdinalDate .....	151
2.347	PidLidToDoSubOrdinal .....	151
2.348	PidLidToDoTitle .....	152
2.349	PidLidTrustRecipientHighlights .....	152

2.350	PidLidUseTnef.....	152
2.351	PidLidValidFlagStringProof .....	153
2.352	PidLidVerbResponse .....	153
2.353	PidLidVerbStream.....	154
2.354	PidLidWeddingAnniversaryLocal .....	154
2.355	PidLidWeekInterval.....	154
2.356	PidLidWhere .....	155
2.357	PidLidWorkAddress .....	155
2.358	PidLidWorkAddressCity .....	155
2.359	PidLidWorkAddressCountry .....	156
2.360	PidLidWorkAddressCountryCode.....	156
2.361	PidLidWorkAddressPostalCode .....	156
2.362	PidLidWorkAddressPostOfficeBox .....	157
2.363	PidLidWorkAddressState .....	157
2.364	PidLidWorkAddressStreet.....	158
2.365	PidLidYearInterval .....	158
2.366	PidLidYomiCompanyName.....	158
2.367	PidLidYomiFirstName .....	159
2.368	PidLidYomiLastName .....	159
2.369	PidNameAcceptLanguage .....	159
2.370	PidNameApplicationName .....	160
2.371	PidNameApproved .....	160
2.372	PidNameApprovalAllowedDecisionMakers .....	160
2.373	PidNameApprovalRequestor.....	160
2.374	PidNameAttachmentMacContentType.....	161
2.375	PidNameAttachmentMacInfo .....	161
2.376	PidNameAudioNotes .....	161
2.377	PidNameAuthor .....	162
2.378	PidNameAuthenticatedAs.....	162
2.379	PidNameAuthenticatedDomain.....	162
2.380	PidNameAuthenticatedMechanism.....	162
2.381	PidNameAuthenticatedSource .....	163
2.382	PidNameAutomaticSpeechRecognitionData.....	163
2.383	PidNameBcc .....	163
2.384	PidNameByteCount.....	163
2.385	PidNameCalendarAttendeeRole .....	164
2.386	PidNameCalendarBusystatus.....	164
2.387	PidNameCalendarContact.....	164
2.388	PidNameCalendarContactUrl .....	165
2.389	PidNameCalendarCreated .....	165
2.390	PidNameCalendarDescriptionUrl.....	165
2.391	PidNameCalendarDuration .....	165
2.392	PidNameCalendarExceptionDate .....	166
2.393	PidNameCalendarExceptionRule.....	166
2.394	PidNameCalendarGeoLatitude .....	166
2.395	PidNameCalendarGeoLongitude .....	167
2.396	PidNameCalendarInstanceType.....	167
2.397	PidNameCalendarIsOrganizer.....	167
2.398	PidNameCalendarLastModified .....	167
2.399	PidNameCalendarLocationUrl .....	168
2.400	PidNameCalendarMeetingStatus.....	168
2.401	PidNameCalendarMethod .....	168
2.402	PidNameCalendarProductId.....	168

2.403	PidNameCalendarRecurrenceIdRange.....	169
2.404	PidNameCalendarReminderOffset.....	169
2.405	PidNameCalendarResources.....	169
2.406	PidNameCalendarRsvp.....	170
2.407	PidNameCalendarSequence.....	170
2.408	PidNameCalendarTime Zone.....	170
2.409	PidNameCalendarTime ZoneId.....	170
2.410	PidNameCalendarTransparent.....	171
2.411	PidNameCalendarUid.....	171
2.412	PidNameCalendarVersion.....	171
2.413	PidNameCategory.....	171
2.414	PidNameCc.....	172
2.415	PidNameCharacterCount.....	172
2.416	PidNameComments.....	172
2.417	PidNameCompany.....	173
2.418	PidNameContactsAlternateRecipient.....	173
2.419	PidNameContactsCountry.....	173
2.420	PidNameContactsEmail1.....	173
2.421	PidNameContactsEmail2.....	174
2.422	PidNameContactsEmail3.....	174
2.423	PidNameContactsFileAs.....	174
2.424	PidNameContactsFileasId.....	174
2.425	PidNameContactsHomeLatitude.....	175
2.426	PidNameContactsHomeLongitude.....	175
2.427	PidNameContactsHomeTime Zone.....	175
2.428	PidNameContactsMapUrl.....	176
2.429	PidNameContactsOtherCountryCode.....	176
2.430	PidNameContactsOtherPager.....	176
2.431	PidNameContactsOtherTime Zone.....	176
2.432	PidNameContactsProxyAddresses.....	177
2.433	PidNameContactsSecretaryUrl.....	177
2.434	PidNameContactsSourceUrl.....	177
2.435	PidNameContentBase.....	177
2.436	PidNameContentClass.....	178
2.437	PidNameContentDisposition.....	178
2.438	PidNameContentID.....	178
2.439	PidNameContentLanguage.....	179
2.440	PidNameContentLocation.....	179
2.441	PidNameContentTransferEncoding.....	179
2.442	PidNameContentType.....	179
2.443	PidNameControl.....	180
2.444	PidNameCreateDateTimeReadOnly.....	180
2.445	PidNameCrossReference.....	180
2.446	PidNameDavGetContentType.....	181
2.447	PidNameDavId.....	181
2.448	PidNameDavIsCollection.....	181
2.449	PidNameDavIsStructuredDocument.....	181
2.450	PidNameDavParentName.....	182
2.451	PidNameDavResourceType.....	182
2.452	PidNameDavSearchRequest.....	182
2.453	PidNameDavSearchType.....	182
2.454	PidNameDavUid.....	183
2.455	PidNameDisposition.....	183

2.456	PidNameDispositionNotificationTo .....	183
2.457	PidNameDistribution .....	184
2.458	PidNameDocumentParts .....	184
2.459	PidNameEditTime .....	184
2.460	PidNameExchangeIntendedBusyStatus .....	184
2.461	PidNameExchangeJunkEmailMoveStamp .....	185
2.462	PidNameExchangeModifyExceptionStructure .....	185
2.463	PidNameExchangeMsexchembdefaultmailfolder .....	185
2.464	PidNameExchangeMsexchembdefaultmailfoldertype .....	185
2.465	PidNameExchangeNoModifyExceptions .....	186
2.466	PidNameExchangePatternEnd .....	186
2.467	PidNameExchangePatternStart .....	186
2.468	PidNameExchangePublicFolderEmailAddress .....	187
2.469	PidNameExchangeReminderInterval .....	187
2.470	PidNameExchDatabaseSchema .....	187
2.471	PidNameExchDataExpectedContentClass .....	187
2.472	PidNameExchDataSchemaCollectionReference .....	188
2.473	PidNameExpires .....	188
2.474	PidNameExpiryDate .....	188
2.475	PidNameFollowupTo .....	188
2.476	PidNameFrom .....	189
2.477	PidNameHeadingPairs .....	189
2.478	PidNameHiddenCount .....	189
2.479	PidNameHttpmailCalendar .....	190
2.480	PidNameHttpmailCc .....	190
2.481	PidNameHttpmailContacts .....	190
2.482	PidNameHttpmailContentMediaType .....	190
2.483	PidNameHttpmailFrom .....	191
2.484	PidNameHttpmailFromEmail .....	191
2.485	PidNameHttpmailHtmlDescription .....	191
2.486	PidNameHttpmailOutbox .....	191
2.487	PidNameHttpmailSendMessage .....	192
2.488	PidNameHttpmailSubmitted .....	192
2.489	PidNameHttpmailTo .....	192
2.490	PidNameICalendarRecurrenceDate .....	193
2.491	PidNameICalendarRecurrenceRule .....	193
2.492	PidNameImportance .....	193
2.493	PidNameInReplyTo .....	193
2.494	PidNameInstantMessagingAddress2 .....	194
2.495	PidNameInstantMessagingAddress3 .....	194
2.496	PidNameInternetComment .....	194
2.497	PidNameInternetKeywords .....	194
2.498	PidNameInternetSubject .....	195
2.499	PidNameKeywords .....	195
2.500	PidNameLastAuthor .....	195
2.501	PidNameLastPrinted .....	196
2.502	PidNameLastSaveDateTime .....	196
2.503	PidNameLineCount .....	196
2.504	PidNameLines .....	196
2.505	PidNameLinksDirty .....	197
2.506	PidNameLocationUrl .....	197
2.507	PidNameMailSubmissionUri .....	197
2.508	PidNameManager .....	198

2.509	PidNameMessageId	198
2.510	PidNameMimeVersion	198
2.511	PidNameMultimediaClipCount	198
2.512	PidNameNewsgroups	199
2.513	PidNameNntpPostingHost	199
2.514	PidNameNoteCount	199
2.515	PidNameOMSAccountGuid	199
2.516	PidNameOMSMobileModel	200
2.517	PidNameOMSScheduleTime	200
2.518	PidNameOMSServiceType	200
2.519	PidNameOMSSourceType	201
2.520	PidNameOrganization	201
2.521	PidNameOriginalRecipient	201
2.522	PidNameOriginalSpamConfidenceLevel	201
2.523	PidNameOutlookProtectionRuleOverridden	202
2.524	PidNameOutlookProtectionRuleTimestamp	202
2.525	PidNameOutlookProtectionRuleVersion	202
2.526	PidNamePageCount	202
2.527	PidNameParagraphCount	203
2.528	PidNamePath	203
2.529	PidNamePhishingStamp	203
2.530	PidNamePostingVersion	204
2.531	PidNamePresentationFormat	204
2.532	PidNamePriority	204
2.533	PidNameQuarantineOriginalSender	204
2.534	PidNameReceived	205
2.535	PidNameReferences	205
2.536	PidNameRelayVersion	205
2.537	PidNameReplyBy	205
2.538	PidNameReplyTo	206
2.539	PidNameReturnPath	206
2.540	PidNameReturnReceiptTo	206
2.541	PidNameRevisionNumber	207
2.542	PidNameRightsManagementLicense	207
2.543	PidNameRightsProtectMessage	207
2.544	PidNameScale	207
2.545	PidNameSecurity	208
2.546	PidNameSender	208
2.547	PidNameSensitivity	208
2.548	PidNameSlideCount	208
2.549	PidNameSubject	209
2.550	PidNameSummary	209
2.551	PidNameTemplate	209
2.552	PidNameThreadIndex	210
2.553	PidNameThreadTopic	210
2.554	PidNameThumbnail	210
2.555	PidNameTitle	210
2.556	PidNameTo	211
2.557	PidNameWordCount	211
2.558	PidNameXCallId	211
2.559	PidNameXFaxNumberOfPages	211
2.560	PidNameXMailer	212
2.561	PidNameXMessageCompleted	212

2.562	PidNameXMessageFlag .....	212
2.563	PidNameXRequireProtectedPlayOnPhone .....	213
2.564	PidNameXSenderTelephoneNumber .....	213
2.565	PidNameXSharingBrowseUrl .....	213
2.566	PidNameXSharingCapabilities .....	213
2.567	PidNameXSharingConfigUrl .....	214
2.568	PidNameXSharingExendedCaps .....	214
2.569	PidNameXSharingFlavor .....	214
2.570	PidNameXSharingInstanceGuid .....	214
2.571	PidNameXSharingLocalType .....	215
2.572	PidNameXSharingProviderGuid .....	215
2.573	PidNameXSharingProviderName .....	215
2.574	PidNameXSharingProviderUrl .....	216
2.575	PidNameXSharingRemoteName .....	216
2.576	PidNameXSharingRemotePath .....	216
2.577	PidNameXSharingRemoteStoreUid .....	216
2.578	PidNameXSharingRemoteType .....	217
2.579	PidNameXSharingRemoteUid .....	217
2.580	PidNameXUnifiedMessagingPartnerAssignedId .....	217
2.581	PidNameXUnifiedMessagingPartnerContent .....	217
2.582	PidNameXUnifiedMessagingPartnerContext .....	218
2.583	PidNameXUnifiedMessagingPartnerStatus .....	218
2.584	PidNameXUnsent .....	218
2.585	PidNameXVoiceMessageAttachmentOrder .....	219
2.586	PidNameXVoiceMessageDuration .....	219
2.587	PidNameXVoiceMessageSenderName .....	219
2.588	PidTag7BitDisplayName .....	219
2.589	PidTagAccess .....	220
2.590	PidTagAccessLevel .....	220
2.591	PidTagAccount .....	220
2.592	PidTagAdditionalRenEntryIds .....	220
2.593	PidTagAdditionalRenEntryIdsEx .....	221
2.594	PidTagAddressBookAuthorizedSenders .....	221
2.595	PidTagAddressBookContainerId .....	221
2.596	PidTagAddressBookDeliveryContentLength .....	221
2.597	PidTagAddressBookDisplayNamePrintable .....	222
2.598	PidTagAddressBookDisplayTypeExtended .....	222
2.599	PidTagAddressBookDistributionListExternalMemberCount .....	222
2.600	PidTagAddressBookDistributionListMemberCount .....	222
2.601	PidTagAddressBookDistributionListMemberSubmitAccepted .....	223
2.602	PidTagAddressBookDistributionListMemberSubmitRejected .....	223
2.603	PidTagAddressBookEntryId .....	223
2.604	PidTagAddressBookExtensionAttribute 1 .....	223
2.605	PidTagAddressBookExtensionAttribute 15 .....	224
2.606	PidTagAddressBookFolderPathname .....	224
2.607	PidTagAddressBookHierarchicalChildDepartments .....	224
2.608	PidTagAddressBookHierarchicalDepartmentMembers .....	224
2.609	PidTagAddressBookHierarchicalIsHierarchicalGroup .....	225
2.610	PidTagAddressBookHierarchicalParentDepartment .....	225
2.611	PidTagAddressBookHierarchicalRootDepartment .....	225
2.612	PidTagAddressBookHierarchicalShowInDepartments .....	225
2.613	PidTagAddressBookHomeMessageDatabase .....	226
2.614	PidTagAddressBookIsMaster .....	226

2.615	PidTagAddressBookIsMemberOfDistributionList .....	226
2.616	PidTagAddressBookManageDistributionList .....	226
2.617	PidTagAddressBookManager .....	227
2.618	PidTagAddressBookManagerDistinguishedName .....	227
2.619	PidTagAddressBookMember .....	227
2.620	PidTagAddressBookMessageId .....	227
2.621	PidTagAddressBookModerationEnabled .....	228
2.622	PidTagAddressBookNetworkAddress .....	228
2.623	PidTagAddressBookObjectDistinguishedName .....	228
2.624	PidTagAddressBookObjectGuid .....	228
2.625	PidTagAddressBookOrganizationalUnitRootDistinguishedName .....	229
2.626	PidTagAddressBookOwner .....	229
2.627	PidTagAddressBookOwnerBackLink .....	229
2.628	PidTagAddressBookParentEntryId .....	229
2.629	PidTagAddressBookPhoneticCompanyName .....	230
2.630	PidTagAddressBookPhoneticDepartmentName .....	230
2.631	PidTagAddressBookPhoneticDisplayName .....	230
2.632	PidTagAddressBookPhoneticGivenName .....	230
2.633	PidTagAddressBookPhoneticSurname .....	231
2.634	PidTagAddressBookProxyAddresses .....	231
2.635	PidTagAddressBookPublicDelegates .....	231
2.636	PidTagAddressBookReports .....	231
2.637	PidTagAddressBookRoomCapacity .....	232
2.638	PidTagAddressBookRoomContainers .....	232
2.639	PidTagAddressBookRoomDescription .....	232
2.640	PidTagAddressBookSenderHintTranslations .....	232
2.641	PidTagAddressBookSeniorityIndex .....	233
2.642	PidTagAddressBookTargetAddress .....	233
2.643	PidTagAddressBookUnauthorizedSenders .....	233
2.644	PidTagAddressBookX509Certificate .....	233
2.645	PidTagAddressType .....	234
2.646	PidTagAlternateRecipientAllowed .....	234
2.647	PidTagAnr .....	234
2.648	PidTagArchiveDate .....	234
2.649	PidTagArchivePeriod .....	235
2.650	PidTagArchiveTag .....	235
2.651	PidTagAssistant .....	235
2.652	PidTagAssistantTelephoneNumber .....	235
2.653	PidTagAssociated .....	236
2.654	PidTagAttachAdditionalInformation .....	236
2.655	PidTagAttachContentBase .....	236
2.656	PidTagAttachContentId .....	236
2.657	PidTagAttachContentLocation .....	237
2.658	PidTagAttachDataBinary .....	237
2.659	PidTagAttachDataObject .....	237
2.660	PidTagAttachEncoding .....	237
2.661	PidTagAttachExtension .....	238
2.662	PidTagAttachFilename .....	238
2.663	PidTagAttachFlags .....	238
2.664	PidTagAttachLongFilename .....	238
2.665	PidTagAttachLongPathname .....	239
2.666	PidTagAttachmentContactPhoto .....	239
2.667	PidTagAttachmentFlags .....	239

2.668	PidTagAttachmentHidden.....	240
2.669	PidTagAttachmentLinkId.....	240
2.670	PidTagAttachMethod.....	240
2.671	PidTagAttachMimeTag.....	240
2.672	PidTagAttachNumber.....	241
2.673	PidTagAttachPathname.....	241
2.674	PidTagAttachPayloadClass.....	241
2.675	PidTagAttachPayloadProviderGuidString.....	241
2.676	PidTagAttachRendering.....	242
2.677	PidTagAttachSize.....	242
2.678	PidTagAttachTag.....	242
2.679	PidTagAttachTransportName.....	242
2.680	PidTagAttributeHidden.....	243
2.681	PidTagAttributeReadOnly.....	243
2.682	PidTagAttributeSystem.....	243
2.683	PidTagAutoForwarded.....	243
2.684	PidTagAutoResponseSuppress.....	244
2.685	PidTagBirthday.....	244
2.686	PidTagBlockStatus.....	244
2.687	PidTagBody.....	244
2.688	PidTagBodyContentId.....	245
2.689	PidTagBodyContentLocation.....	245
2.690	PidTagBodyHtml.....	245
2.691	PidTagBusiness2TelephoneNumber.....	245
2.692	PidTagBusiness2TelephoneNumbers.....	246
2.693	PidTagBusinessFaxNumber.....	246
2.694	PidTagBusinessHomePage.....	246
2.695	PidTagBusinessTelephoneNumber.....	246
2.696	PidTagCallbackTelephoneNumber.....	247
2.697	PidTagCallId.....	247
2.698	PidTagCarTelephoneNumber.....	247
2.699	PidTagCdoRecurrenceid.....	247
2.700	PidTagChangeKey.....	248
2.701	PidTagChangeNotificationGuid.....	248
2.702	PidTagChangeNumber.....	248
2.703	PidTagChildrensNames.....	248
2.704	PidTagClientActions.....	249
2.705	PidTagClientSubmitTime.....	249
2.706	PidTagCnsetRead.....	249
2.707	PidTagCnsetSeen.....	249
2.708	PidTagCnsetSeenFAI.....	250
2.709	PidTagCodePageId.....	250
2.710	PidTagComment.....	250
2.711	PidTagCompanyMainTelephoneNumber.....	250
2.712	PidTagCompanyName.....	251
2.713	PidTagComputerNetworkName.....	251
2.714	PidTagConflictEntryId.....	251
2.715	PidTagConflictItems.....	251
2.716	PidTagContainerClass.....	252
2.717	PidTagContainerContents.....	252
2.718	PidTagContainerFlags.....	252
2.719	PidTagContainerHierarchy.....	253
2.720	PidTagContentCount.....	253



2.721	PidTagContentFilterPhishingConfidenceLevel	253
2.722	PidTagContentFilterSpamConfidenceLevel	253
2.723	PidTagContentUnreadCount	254
2.724	PidTagConversationId	254
2.725	PidTagConversationIndex	254
2.726	PidTagConversationIndexTracking	254
2.727	PidTagConversationTopic	255
2.728	PidTagCountry	255
2.729	PidTagCreationTime	255
2.730	PidTagCreatorEntryId	255
2.731	PidTagCreatorName	256
2.732	PidTagCreatorSimpleDisplayName	256
2.733	PidTagCustomerId	256
2.734	PidTagDamBackPatched	256
2.735	PidTagDamOriginalEntryId	257
2.736	PidTagDefaultPostMessageClass	257
2.737	PidTagDeferredDeliveryTime	257
2.738	PidTagDeferredSendNumber	257
2.739	PidTagDeferredSendTime	258
2.740	PidTagDeferredSendUnits	258
2.741	PidTagDelegatedByRule	258
2.742	PidTagDelegateFlags	258
2.743	PidTagDeleteAfterSubmit	259
2.744	PidTagDeletedOn	259
2.745	PidTagDepartmentName	259
2.746	PidTagDepth	259
2.747	PidTagDisplayBcc	260
2.748	PidTagDisplayCc	260
2.749	PidTagDisplayName	260
2.750	PidTagDisplayNamePrefix	260
2.751	PidTagDisplayTo	261
2.752	PidTagDisplayType	261
2.753	PidTagDisplayTypeEx	261
2.754	PidTagEcWaming	261
2.755	PidTagEmailAddress	262
2.756	PidTagEndAttach	262
2.757	PidTagEndDate	262
2.758	PidTagEndEmbed	262
2.759	PidTagEndFolder	263
2.760	PidTagEndMessage	263
2.761	PidTagEndToRecip	263
2.762	PidTagEntryId	263
2.763	PidTagExceptionEndTime	264
2.764	PidTagExceptionReplaceTime	264
2.765	PidTagExceptionStartTime	264
2.766	PidTagExchangeNTSecurityDescriptor	264
2.767	PidTagExpiryNumber	265
2.768	PidTagExpiryTime	265
2.769	PidTagExpiryUnits	265
2.770	PidTagExtendedFolderFlags	265
2.771	PidTagExtendedRuleMessageActions	266
2.772	PidTagExtendedRuleMessageCondition	266
2.773	PidTagExtendedRuleSizeLimit	266

2.774	PidTagFaxNumberOfPages .....	266
2.775	PidTagFlagCompleteTime .....	267
2.776	PidTagFlagStatus .....	267
2.777	PidTagFlatUrlName .....	267
2.778	PidTagFolderAssociatedContents .....	267
2.779	PidTagFolderId .....	268
2.780	PidTagFolderType .....	268
2.781	PidTagFollowupIcon .....	268
2.782	PidTagFreeBusyCountMonths .....	268
2.783	PidTagFreeBusyEntryIds .....	269
2.784	PidTagFreeBusyMessageEmailAddress .....	269
2.785	PidTagFreeBusyPublishEnd .....	269
2.786	PidTagFreeBusyPublishStart .....	269
2.787	PidTagFreeBusyRangeTimeStamp .....	270
2.788	PidTagFtpSite .....	270
2.789	PidTagFXDelProp .....	270
2.790	PidTagFXErrorInfo .....	270
2.791	PidTagGatewayNeedsToRefresh .....	271
2.792	PidTagGender .....	271
2.793	PidTagGeneration .....	271
2.794	PidTagGivenName .....	271
2.795	PidTagGovernmentIdNumber .....	272
2.796	PidTagHasAttachments .....	272
2.797	PidTagHasDeferredActionMessages .....	272
2.798	PidTagHasNamedProperties .....	272
2.799	PidTagHasRules .....	273
2.800	PidTagHierarchyChangeNumber .....	273
2.801	PidTagHobbies .....	273
2.802	PidTagHome2TelephoneNumber .....	273
2.803	PidTagHome2TelephoneNumbers .....	274
2.804	PidTagHomeAddressCity .....	274
2.805	PidTagHomeAddressCountry .....	274
2.806	PidTagHomeAddressPostalCode .....	274
2.807	PidTagHomeAddressPostOfficeBox .....	275
2.808	PidTagHomeAddressStateOrProvince .....	275
2.809	PidTagHomeAddressStreet .....	275
2.810	PidTagHomeFaxNumber .....	275
2.811	PidTagHomeTelephoneNumber .....	276
2.812	PidTagHtml .....	276
2.813	PidTagICalendarEndTime .....	276
2.814	PidTagICalendarReminderNextTime .....	276
2.815	PidTagICalendarStartTime .....	277
2.816	PidTagIconIndex .....	277
2.817	PidTagIdsetDeleted .....	277
2.818	PidTagIdsetExpired .....	277
2.819	PidTagIdsetGiven .....	278
2.820	PidTagIdsetRead .....	278
2.821	PidTagIdsetNoLongerInScope .....	278
2.822	PidTagIdsetUnread .....	278
2.823	PidTagImapCachedMsgsize .....	279
2.824	PidTagImportance .....	279
2.825	PidTagInConflict .....	279
2.826	PidTagIncrementalSyncMessagePartial .....	279

2.827	PidTagIncrSyncChg.....	280
2.828	PidTagIncrSyncChgPartial.....	280
2.829	PidTagIncrSyncDel.....	280
2.830	PidTagIncrSyncEnd.....	280
2.831	PidTagIncrSyncGroupId.....	281
2.832	PidTagIncrSyncGroupInfo.....	281
2.833	PidTagIncrSyncMessage.....	281
2.834	PidTagIncrSyncProgressMode.....	281
2.835	PidTagIncrSyncProgressPerMsg.....	282
2.836	PidTagIncrSyncRead.....	282
2.837	PidTagIncrSyncStateBegin.....	282
2.838	PidTagIncrSyncStateEnd.....	282
2.839	PidTagInitialDetailsPane.....	283
2.840	PidTagInitials.....	283
2.841	PidTagInReplyToId.....	283
2.842	PidTagInstanceKey.....	283
2.843	PidTagInstanceNum.....	284
2.844	PidTagInstID.....	284
2.845	PidTagInternetArticleNumber.....	284
2.846	PidTagInternetCodepage.....	284
2.847	PidTagInternetMailOverrideFormat.....	285
2.848	PidTagInternetMessageId.....	285
2.849	PidTagInternetReferences.....	285
2.850	PidTagInternetReturnPath.....	285
2.851	PidTagIpmAppointmentEntryId.....	286
2.852	PidTagIpmContactEntryId.....	286
2.853	PidTagIpmDraftsEntryId.....	286
2.854	PidTagIpmJournalEntryId.....	286
2.855	PidTagIpmNoteEntryId.....	287
2.856	PidTagIpmTaskEntryId.....	287
2.857	PidTagIsdnNumber.....	287
2.858	PidTagItemTemporaryFlags.....	287
2.859	PidTagJunkAddRecipientsToSafeSendersList.....	288
2.860	PidTagJunkIncludeContacts.....	288
2.861	PidTagJunkPermanentlyDelete.....	288
2.862	PidTagJunkPhishingEnableLinks.....	288
2.863	PidTagJunkThreshold.....	289
2.864	PidTagKeyword.....	289
2.865	PidTagLanguage.....	289
2.866	PidTagLastModificationTime.....	289
2.867	PidTagLastModifierEntryId.....	290
2.868	PidTagLastModifierName.....	290
2.869	PidTagLastModifierSimpleDisplayName.....	290
2.870	PidTagLastVerbExecuted.....	290
2.871	PidTagLastVerbExecutionTime.....	291
2.872	PidTagListHelp.....	291
2.873	PidTagListSubscribe.....	291
2.874	PidTagListUnsubscribe.....	291
2.875	PidTagLocalCommitTime.....	292
2.876	PidTagLocaleId.....	292
2.877	PidTagLocality.....	292
2.878	PidTagLocation.....	292
2.879	PidTagMailboxOwnerEntryId.....	293

2.880	PidTagMailboxOwnerName.....	293
2.881	PidTagManagerName.....	293
2.882	PidTagMappingSignature.....	293
2.883	PidTagMaximumSubmitMessageSize.....	294
2.884	PidTagMemberId.....	294
2.885	PidTagMemberName.....	294
2.886	PidTagMemberRights.....	294
2.887	PidTagMessageAttachments.....	295
2.888	PidTagMessageCcMe.....	295
2.889	PidTagMessageClass.....	295
2.890	PidTagMessageCodepage.....	295
2.891	PidTagMessageDeliveryTime.....	296
2.892	PidTagMessageEditorFormat.....	296
2.893	PidTagMessageFlags.....	296
2.894	PidTagMessageHandlingSystemCommonName.....	296
2.895	PidTagMessageLocaleId.....	297
2.896	PidTagMessageRecipientMe.....	297
2.897	PidTagMessageRecipients.....	297
2.898	PidTagMessageSize.....	297
2.899	PidTagMessageSizeExtended.....	298
2.900	PidTagMessageStatus.....	298
2.901	PidTagMessageSubmissionId.....	298
2.902	PidTagMessageToMe.....	298
2.903	PidTagMid.....	299
2.904	PidTagMiddleName.....	299
2.905	PidTagMimeSkeleton.....	299
2.906	PidTagMobileTelephoneNumber.....	299
2.907	PidTagNativeBody.....	300
2.908	PidTagNewAttach.....	300
2.909	PidTagNewFXFolder.....	300
2.910	PidTagNextSendAcct.....	300
2.911	PidTagNickname.....	301
2.912	PidTagNormalizedSubject.....	301
2.913	PidTagNormalMessageSize.....	301
2.914	PidTagObjectType.....	302
2.915	PidTagOfficeLocation.....	302
2.916	PidTagOfflineAddressBookCompressedSize.....	302
2.917	PidTagOfflineAddressBookContainerGuid.....	302
2.918	PidTagOfflineAddressBookDistinguishedName.....	303
2.919	PidTagOfflineAddressBookFileSize.....	303
2.920	PidTagOfflineAddressBookFileType.....	303
2.921	PidTagOfflineAddressBookLanguageId.....	303
2.922	PidTagOfflineAddressBookMessageClass.....	304
2.923	PidTagOfflineAddressBookName.....	304
2.924	PidTagOfflineAddressBookSequence.....	304
2.925	PidTagOfflineAddressBookShaHash.....	304
2.926	PidTagOfflineAddressBookTruncatedProperties.....	305
2.927	PidTagOrdinalMost.....	305
2.928	PidTagOrganizationalIdNumber.....	305
2.929	PidTagOriginalAuthorName.....	305
2.930	PidTagOriginalDeliveryTime.....	306
2.931	PidTagOriginalDisplayBcc.....	306
2.932	PidTagOriginalDisplayCc.....	306

2.933	PidTagOriginalDisplayName .....	306
2.934	PidTagOriginalDisplayTo .....	307
2.935	PidTagOriginalEntryId .....	307
2.936	PidTagOriginalMessageClass .....	307
2.937	PidTagOriginalMessageId .....	307
2.938	PidTagOriginalSearchKey .....	308
2.939	PidTagOriginalSenderAddressType .....	308
2.940	PidTagOriginalSenderEmailAddress .....	308
2.941	PidTagOriginalSenderEntryId .....	308
2.942	PidTagOriginalSenderName.....	309
2.943	PidTagOriginalSenderSearchKey .....	309
2.944	PidTagOriginalSensitivity .....	309
2.945	PidTagOriginalSentRepresentingAddressType.....	309
2.946	PidTagOriginalSentRepresentingEmailAddress .....	310
2.947	PidTagOriginalSentRepresentingEntryId .....	310
2.948	PidTagOriginalSentRepresentingName.....	310
2.949	PidTagOriginalSentRepresentingSearchKey .....	310
2.950	PidTagOriginalSubject.....	311
2.951	PidTagOriginalSubmitTime .....	311
2.952	PidTagOriginatorDeliveryReportRequested .....	311
2.953	PidTagOriginatorNonDeliveryReportRequested .....	312
2.954	PidTagOtherAddressCity .....	312
2.955	PidTagOtherAddressCountry .....	312
2.956	PidTagOtherAddressPostalCode.....	312
2.957	PidTagOtherAddressPostOfficeBox.....	313
2.958	PidTagOtherAddressStateOrProvince .....	313
2.959	PidTagOtherAddressStreet.....	313
2.960	PidTagOtherTelephoneNumber.....	313
2.961	PidTagOutOfOfficeState .....	314
2.962	PidTagOwnerAppointmentId .....	314
2.963	PidTagPagerTelephoneNumber.....	314
2.964	PidTagParentEntryId.....	314
2.965	PidTagParentFolderId.....	315
2.966	PidTagParentKey .....	315
2.967	PidTagParentSourceKey.....	315
2.968	PidTagPersonalHomePage.....	315
2.969	PidTagPolicyTag.....	316
2.970	PidTagPostalAddress.....	316
2.971	PidTagPostalCode .....	316
2.972	PidTagPostOfficeBox .....	316
2.973	PidTagPredecessorChangeList.....	317
2.974	PidTagPrimaryFaxNumber.....	317
2.975	PidTagPrimarySendAccount .....	317
2.976	PidTagPrimarySmtpAddress .....	317
2.977	PidTagPrimaryTelephoneNumber .....	318
2.978	PidTagPriority.....	318
2.979	PidTagProcessed.....	318
2.980	PidTagProfession .....	318
2.981	PidTagProhibitReceiveQuota.....	319
2.982	PidTagProhibitSendQuota.....	319
2.983	PidTagProviderSubmitTime .....	319
2.984	PidTagPublicFolderAdministrativeDescription.....	319
2.985	PidTagPublicFolderProxy .....	320

2.986	PidTagPurportedSenderDomain.....	320
2.987	PidTagRadioTelephoneNumber.....	320
2.988	PidTagRead.....	320
2.989	PidTagReadReceiptAddressType.....	321
2.990	PidTagReadReceiptEmailAddress.....	321
2.991	PidTagReadReceiptEntryId.....	321
2.992	PidTagReadReceiptName.....	321
2.993	PidTagReadReceiptRequested.....	322
2.994	PidTagReadReceiptSearchKey.....	322
2.995	PidTagReceivedByAddressType.....	322
2.996	PidTagReceivedByEmailAddress.....	322
2.997	PidTagReceivedByEntryId.....	323
2.998	PidTagReceivedByFlags.....	323
2.999	PidTagReceivedByName.....	323
2.1000	PidTagReceivedBySearchKey.....	323
2.1001	PidTagReceivedRepresentingAddressType.....	324
2.1002	PidTagReceivedRepresentingEmailAddress.....	324
2.1003	PidTagReceivedRepresentingEntryId.....	324
2.1004	PidTagReceivedRepresentingFlags.....	324
2.1005	PidTagReceivedRepresentingName.....	325
2.1006	PidTagReceivedRepresentingSearchKey.....	325
2.1007	PidTagReceivedRepresentingSimpleDisplayName.....	325
2.1008	PidTagRecipientDisplayName.....	325
2.1009	PidTagRecipientEntryId.....	326
2.1010	PidTagRecipientFlags.....	326
2.1011	PidTagRecipientOrder.....	326
2.1012	PidTagRecipientProposed.....	326
2.1013	PidTagRecipientProposedEndTime.....	327
2.1014	PidTagRecipientProposedStartTime.....	327
2.1015	PidTagRecipientReassignmentProhibited.....	327
2.1016	PidTagRecipientResourceState.....	327
2.1017	PidTagRecipientTrackStatus.....	328
2.1018	PidTagRecipientTrackStatusTime.....	328
2.1019	PidTagRecipientType.....	328
2.1020	PidTagRecordKey.....	328
2.1021	PidTagReferredByName.....	329
2.1022	PidTagRemindersOnlineEntryId.....	329
2.1023	PidTagRemoteHeaderLoc.....	329
2.1024	PidTagRemoteMessageTransferAgent.....	329
2.1025	PidTagRenderingPosition.....	330
2.1026	PidTagReplyRecipientEntries.....	330
2.1027	PidTagReplyRecipientNames.....	330
2.1028	PidTagReplyRequested.....	330
2.1029	PidTagReplyTemplateId.....	331
2.1030	PidTagReplyTime.....	331
2.1031	PidTagReportEntryId.....	331
2.1032	PidTagReportingMessageTransferAgent.....	331
2.1033	PidTagReportName.....	332
2.1034	PidTagReportSearchKey.....	332
2.1035	PidTagReportTag.....	332
2.1036	PidTagReportText.....	332
2.1037	PidTagReportTime.....	333
2.1038	PidTagResolveMethod.....	333

2.1039	PidTagResponseRequested.....	333
2.1040	PidTagResponsibility .....	333
2.1041	PidTagRetentionDate .....	334
2.1042	PidTagRetentionFlags.....	334
2.1043	PidTagRetentionPeriod .....	334
2.1044	PidTagRights .....	334
2.1045	PidTagRoamingDatatypes .....	335
2.1046	PidTagRoamingDictionary .....	335
2.1047	PidTagRoamingXmlStream.....	335
2.1048	PidTagRowid.....	335
2.1049	PidTagRowType .....	336
2.1050	PidTagRtfCompressed.....	336
2.1051	PidTagRtfInSync.....	336
2.1052	PidTagRtfSyncBodyCount.....	336
2.1053	PidTagRtfSyncBodyCrc.....	337
2.1054	PidTagRtfSyncBodyTag .....	337
2.1055	PidTagRtfSyncPrefixCount.....	337
2.1056	PidTagRtfSyncTrailingCount .....	337
2.1057	PidTagRuleActionNumber.....	338
2.1058	PidTagRuleActions .....	338
2.1059	PidTagRuleActionType.....	338
2.1060	PidTagRuleCondition.....	338
2.1061	PidTagRuleError.....	339
2.1062	PidTagRuleFolderEntryId.....	339
2.1063	PidTagRuleId .....	339
2.1064	PidTagRuleLevel .....	339
2.1065	PidTagRuleMessageLevel .....	340
2.1066	PidTagRuleMessageName .....	340
2.1067	PidTagRuleMessageProvider.....	340
2.1068	PidTagRuleMessageProviderData.....	340
2.1069	PidTagRuleMessageSequence.....	341
2.1070	PidTagRuleMessageState .....	341
2.1071	PidTagRuleMessageUserFlags.....	341
2.1072	PidTagRuleName .....	341
2.1073	PidTagRuleProvider.....	342
2.1074	PidTagRuleProviderData.....	342
2.1075	PidTagRuleSequence.....	342
2.1076	PidTagRuleState .....	342
2.1077	PidTagRuleUserFlags.....	343
2.1078	PidTagRwRulesStream.....	343
2.1079	PidTagScheduleInfoAppointmentTombstone .....	343
2.1080	PidTagScheduleInfoAutoAcceptAppointments .....	343
2.1081	PidTagScheduleInfoDelegateEntryIds .....	344
2.1082	PidTagScheduleInfoDelegateNames .....	344
2.1083	PidTagScheduleInfoDelegateNamesW .....	344
2.1084	PidTagScheduleInfoDelegatorWantsCopy .....	344
2.1085	PidTagScheduleInfoDelegatorWantsInfo .....	345
2.1086	PidTagScheduleInfoDisallowOverlappingAppts .....	345
2.1087	PidTagScheduleInfoDisallowRecurringAppts.....	345
2.1088	PidTagScheduleInfoDontMailDelegates .....	345
2.1089	PidTagScheduleInfoFreeBusy .....	346
2.1090	PidTagScheduleInfoFreeBusyAway .....	346
2.1091	PidTagScheduleInfoFreeBusyBusy.....	346

2.1092	PidTagScheduleInfoFreeBusyMerged	346
2.1093	PidTagScheduleInfoFreeBusyTentative	347
2.1094	PidTagScheduleInfoMonthsAway	347
2.1095	PidTagScheduleInfoMonthsBusy	347
2.1096	PidTagScheduleInfoMonthsMerged	347
2.1097	PidTagScheduleInfoMonthsTentative	348
2.1098	PidTagScheduleInfoResourceType	348
2.1099	PidTagSchedulePlusFreeBusyEntryId	348
2.1100	PidTagScriptData	348
2.1101	PidTagSearchFolderDefinition	349
2.1102	PidTagSearchFolderEfpFlags	349
2.1103	PidTagSearchFolderExpiration	349
2.1104	PidTagSearchFolderId	349
2.1105	PidTagSearchFolderLastUsed	350
2.1106	PidTagSearchFolderRecreateInfo	350
2.1107	PidTagSearchFolderStorageType	350
2.1108	PidTagSearchFolderTag	350
2.1109	PidTagSearchFolderTemplateId	351
2.1110	PidTagSearchKey	351
2.1111	PidTagSecureSubmitFlags	351
2.1112	PidTagSecurityDescriptor	351
2.1113	PidTagSecurityDescriptorAsXml	352
2.1114	PidTagSelectable	352
2.1115	PidTagSenderAddressType	352
2.1116	PidTagSenderEmailAddress	352
2.1117	PidTagSenderEntryId	353
2.1118	PidTagSenderFlags	353
2.1119	PidTagSenderIdStatus	353
2.1120	PidTagSenderName	353
2.1121	PidTagSenderSearchKey	354
2.1122	PidTagSenderSimpleDisplayName	354
2.1123	PidTagSenderSmtpAddress	354
2.1124	PidTagSenderTelephoneNumber	354
2.1125	PidTagSendInternetEncoding	355
2.1126	PidTagSendRichInfo	355
2.1127	PidTagSensitivity	355
2.1128	PidTagSentMailEntryId	355
2.1129	PidTagSentMailSvrEID	356
2.1130	PidTagSentRepresentingAddressType	356
2.1131	PidTagSentRepresentingEmailAddress	356
2.1132	PidTagSentRepresentingEntryId	356
2.1133	PidTagSentRepresentingFlags	357
2.1134	PidTagSentRepresentingName	357
2.1135	PidTagSentRepresentingSearchKey	357
2.1136	PidTagSentRepresentingSimpleDisplayName	357
2.1137	PidTagSessionInitiationProtocolUri	358
2.1138	PidTagSmtpAddress	358
2.1139	PidTagSortLocaleId	358
2.1140	PidTagSourceKey	358
2.1141	PidTagSpokenName	359
2.1142	PidTagSpouseName	359
2.1143	PidTagStartDate	359
2.1144	PidTagStartDateEtc	359



2.1145	PidTagStartEmbed	360
2.1146	PidTagStartFAIMsg	360
2.1147	PidTagStartMessage	360
2.1148	PidTagStartRecip	360
2.1149	PidTagStartSubFld	361
2.1150	PidTagStartTopFld	361
2.1151	PidTagStateOrProvince	361
2.1152	PidTagStoreEntryId	361
2.1153	PidTagStoreState	362
2.1154	PidTagStoreSupportMask	362
2.1155	PidTagStreetAddress	362
2.1156	PidTagSubfolder	362
2.1157	PidTagSubfolders	363
2.1158	PidTagSubject	363
2.1159	PidTagSubjectPrefix	363
2.1160	PidTagSubmitFlags	364
2.1161	PidTagSurname	364
2.1162	PidTagSwappedToDoData	364
2.1163	PidTagSwappedToDoStore	364
2.1164	PidTagTargetEntryId	365
2.1165	PidTagTcvConstLongOne	365
2.1166	PidTagTelecommunicationsDeviceForDeafTelephoneNumber	365
2.1167	PidTagTelexNumber	365
2.1168	PidTagTemplateData	366
2.1169	PidTagTemplateid	366
2.1170	PidTagTemporaryDefaultDocument	366
2.1171	PidTagTextAttachmentCharset	366
2.1172	PidTagThumbnailPhoto	367
2.1173	PidTagTitle	367
2.1174	PidTagTnefCorrelationKey	367
2.1175	PidTagToDoItemFlags	367
2.1176	PidTagTransmittableDisplayName	368
2.1177	PidTagTransportMessageHeaders	368
2.1178	PidTagTrustSender	368
2.1179	PidTagTtyTddPhoneNumber	368
2.1180	PidTagUrlCompName	369
2.1181	PidTagUrlCompNameSet	369
2.1182	PidTagUrlName	369
2.1183	PidTagUserCertificate	369
2.1184	PidTagUserEntryId	370
2.1185	PidTagUserX509Certificate	370
2.1186	PidTagViewDescriptorBinary	370
2.1187	PidTagViewDescriptorName	370
2.1188	PidTagViewDescriptorStrings	371
2.1189	PidTagViewDescriptorVersion	371
2.1190	PidTagVoiceMessageAttachmentOrder	371
2.1191	PidTagVoiceMessageDuration	371
2.1192	PidTagVoiceMessageSenderName	372
2.1193	PidTagWeddingAnniversary	372
2.1194	PidTagWlinkAddressBookEID	372
2.1195	PidTagWlinkAddressBookStoreEID	372
2.1196	PidTagWlinkCalendarColor	373
2.1197	PidTagWlinkClientID	373

2.1198	PidTagWlinkEntryId .....	373
2.1199	PidTagWlinkFlags.....	373
2.1200	PidTagWlinkFolderType.....	374
2.1201	PidTagWlinkGroupClsid .....	374
2.1202	PidTagWlinkGroupHeaderID .....	374
2.1203	PidTagWlinkGroupName.....	374
2.1204	PidTagWlinkOrdinal.....	375
2.1205	PidTagWlinkRecordKey .....	375
2.1206	PidTagWlinkROGroupType.....	375
2.1207	PidTagWlinkSaveStamp .....	375
2.1208	PidTagWlinkSection .....	376
2.1209	PidTagWlinkStoreEntryId .....	376
2.1210	PidTagWlinkType .....	376
<b>3</b>	<b>Structure Examples .....</b>	<b>377</b>
<b>4</b>	<b>Security Considerations .....</b>	<b>378</b>
<b>5</b>	<b>Appendix A: Product Behavior .....</b>	<b>379</b>
<b>6</b>	<b>Change Tracking .....</b>	<b>380</b>
<b>7</b>	<b>Index.....</b>	<b>388</b>

# 1 Introduction

This specification lists all properties used for communication between clients and servers, provides summary information about each property, and provides links to the documents in which the property value ranges and semantics are specified.

## 1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

**message class**  
**named property**  
**property (1)**  
**property ID**  
**property set**  
**tagged property**

The following terms are specific to this document:

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-NSPI] Microsoft Corporation, "Name Service Provider Interface (NSPI) Protocol Specification", June 2008, <http://go.microsoft.com/fwlink/?LinkID=154742>.

[MS-OXABREF] Microsoft Corporation, "[Address Book Name Service Provider Interface \(NSPI\) Referral Protocol Specification](#)", June 2008.

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Protocol Specification](#)", June 2008.

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)", June 2008.

[MS-OXCFCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)", June 2008.

[MS-OXCFCIXCS] Microsoft Corporation, "[Bulk Data Transfer Protocol Specification](#)", June 2008.

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Protocol Specification](#)", June 2008.

[MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Protocol Specification](#)", June 2008.

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)", June 2008.

[MS-OXCNOTIF] Microsoft Corporation, "[Core Notifications Protocol Specification](#)", June 2008.

[MS-OXCPerm] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol Specification](#)", June 2008.

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)", June 2008.

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)", June 2008.

[MS-OXCRCPC] Microsoft Corporation, "[Wire Format Protocol Specification](#)", June 2008.

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol Specification](#)", June 2008.

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol Specification](#)", June 2008.

[MS-OXCsync] Microsoft Corporation, "[Mailbox Synchronization Protocol Specification](#)", June 2008.

[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol Specification](#)", June 2008.

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", June 2008.

[MS-OXLDAP] Microsoft Corporation, "[Lightweight Directory Access Protocol \(LDAP\) Version 3 Extensions](#)", June 2008.

[MS-OXMSG] Microsoft Corporation, "[.MSG File Format](#)", June 2008.

[MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)", June 2008.

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)", June 2008.

[MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol Specification](#)", June 2008.

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)", June 2008.

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol Specification](#)", June 2008.

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol Specification](#)", June 2008.

[MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol Specification](#)", June 2008.

[MS-OXODOC] Microsoft Corporation, "[Document Object Protocol Specification](#)", June 2008.

[MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol Specification](#)", June 2008.

[MS-OXOJRN] Microsoft Corporation, "[Journal Object Protocol Specification](#)", June 2008.

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)", June 2008.

[MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol Specification](#)", June 2008.

[MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol Specification](#)", June 2008.

[MS-OXOPOST] Microsoft Corporation, "[Post Object Protocol Specification](#)", June 2008.

[MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol Specification](#)", June 2008.

[MS-OXORMMS] Microsoft Corporation, "[Rights-Managed E-Mail Object Protocol Specification](#)", June 2008.

[MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol Specification](#)", June 2008.

[MS-OXORULE] Microsoft Corporation, "[E-Mail Rules Protocol Specification](#)", June 2008.

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol Specification](#)", June 2008.

[MS-OXOSMIME] Microsoft Corporation, "[S/MIME E-Mail Object Protocol Specification](#)", June 2008.

[MS-OXOSMMS] Microsoft Corporation, "[Short Message Service \(SMS\) and Multimedia Messaging Service \(MMS\) Object Protocol Specification](#)", June 2008.

[MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol Specification](#)", June 2008.

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol Specification](#)", June 2008.

[MS-OXOUM] Microsoft Corporation, "[Voice Mail and Fax Objects Protocol Specification](#)", June 2008.

[MS-OXPFOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) Public Folder Retrieval Protocol Specification](#)", June 2008.

[MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol Specification](#)", June 2008.

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)", June 2008.

[MS-OXPSVAL] Microsoft Corporation, "[E-Mail Postmark Validation Protocol Specification](#)", June 2008.

[MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Protocol Specification](#)", June 2008.

[MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Specification](#)", June 2008.

[MS-OXSHARE] Microsoft Corporation, "[Sharing Message Object Protocol Specification](#)", June 2008.

[MS-OXTNEF] Microsoft Corporation, "[Transport Neutral Encapsulation Format \(TNEF\) Data Structure](#)", June 2008.

[MS-OXVCARD] Microsoft Corporation, "[vCard to Contact Object Conversion Protocol Specification](#)", June 2008.

[MS-OXWAVLS] Microsoft Corporation, "[Availability Web Service Protocol Specification](#)", June 2008.

[MS-XWDCAL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Calendar Support](#)", December 2008.

[MS-XWDCNTC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Contacts Support](#)", February 2009.

[MS-XWDDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Documents Support](#)", December 2008.

[MS-XWDFOLD] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Folders Support](#)", December 2008.

[MS-XWDMAIL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for E-Mail Support](#)", December 2008.

[MS-XWDSEARCH] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Search](#)", December 2008.

[MS-XWDSTRUCTDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Structured Documents](#)", December 2008.

[MS-XWDVSEC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Protocol Security Descriptor Extensions](#)", June 2008.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>.

[RFC4234] Crocker, D., Ed. and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 4234, October 2005, <http://www.ietf.org/rfc/rfc4234.txt>.

## 1.2.2 Informative References

None.

## 1.3 Structure Overview

This specification provides basic reference information about message object properties referenced by protocol specifications. The following information is provided for each **property**, as appropriate:

**Alternate names:** Any additional names used to refer to this property.

**Area:** A group of properties with related functionality.

**Canonical name:** The name used to refer to this property in other protocol specifications.

**Data type:** The property value type, as specified in [\[MS-OXCDATA\]](#), that specifies the type of values allowed for this property.

**Property ID:** An unsigned 16-bit quantity that identifies a **tagged property**.

**Property long ID (LID):** An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

**Property name:** A string that, along with the property set, identifies a named property.

**Property set:** A GUID that identifies a group of properties with a similar purpose.

**References:** One or more protocol documents that specify the semantics and allowed values for this property.

### 1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's **message class**. Applications handle the case where required properties are missing; treating a message object as **IPM.Note** is a common fallback strategy. The following table lists several common message classes,

the functional area to which each one corresponds, and the document that specifies each one's required and optional properties.

In this table, an asterisk "\*" denotes that any string can appear at that point.

Area	PidTagMessageClass values	Document
Common	IPM.*	<a href="#">[MS- OXCMMSG]</a>
Email	IPM.Note, REPORT.*	<a href="#">[MS- OXCMMSG]</a>
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	<a href="#">[MS- OXOCAL]</a>
Contact	IPM.Contact, IPM.DistList	<a href="#">[MS- OXOCNTC]</a>
Task	IPM.Task, IPM.TaskRequest.*	<a href="#">[MS- OXOTASK]</a>
Journal	IPM.Activity	<a href="#">[MS- OXOJRN]</a>
Sticky note	IPM.StickyNote	<a href="#">[MS- OXONOTE]</a>
Document	IPM.Document.*	<a href="#">[MS- OXODOC]</a>
Post	IPM.Post	<a href="#">[MS- OXOPOST]</a>
RSS feed	IPM.Post.RSS	<a href="#">[MS- OXORSS]</a>
Rights-managed email	IPM.Note with PidNameContentClass= rpmsg.message	<a href="#">[MS- OXORMMS]</a>
S/MIME email	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	<a href="#">[MS- OXOSMIME]</a>
Short message service / Multimedia Message Service Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	<a href="#">[MS- OXOSMMS]</a>
Unified messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	<a href="#">[MS- OXOUM]</a>
Sharing	IPM.Sharing IPM.Sharing.*	<a href="#">[MS- OXSHARE]</a>

### 1.3.2 Commonly Used Property Sets

In the property index that forms the main body of this document (section 2) each named property is listed with the GUID that defines its property set. Several of the more common property sets are listed here as a convenient reference, with their functional areas.

Area	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}
Common	PSETID_Common {00062008-0000-0000-C000-000000000046}
Contact	PSETID_Address {00062004-0000-0000-C000-000000000046}
Email	PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-000000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-000000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B-0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-000000000046}
RSS feed	PSETID_PostRss {00062041-0000-0000-C000-000000000046}
Task	PSETID_Task {00062003-0000-0000-C000-000000000046}
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing {00062040-0000-0000-C000-000000000046}



### 1.3.3 Property ID Ranges

The 65,536 possible values of the **property ID** are divided into sub-ranges reserved for various purposes, as specified in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an email transport protocol (such as SMTP), and not to any network transport protocol (such as TCP).

- Servers do not allow property ID in ranges specified as non-transmittable to be submitted for transport to another server via a mail transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.
- Clients can use properties in ranges specified as message class-defined for application-defined purposes. When doing so, applications specify a value for **PidTagMessageClass** that is distinct from any value listed in section [1.3.1](#).
- Clients can use any named property for application-defined purposes. No constraint is placed on the value of **PidTagMessageClass** in this case, but the named property's property set is distinct from any value listed in section [1.3.2](#). Note that named properties are always transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Specification
0x0001	0x0BFF	Message envelope property; reserved
0x0C00	0x0DFF	Recipient property; reserved
0x0E00	0x0FFF	Non-transmittable message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	Message store property; reserved
0x3600	0x36FF	Folder and address book container property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	Address book object property; reserved
0x3A00	0x3BFF	Mail user object property; reserved
0x3C00	0x3CFF	Distribution list property; reserved
0x3D00	0x3DFF	Profile section property; reserved
0x3E00	0x3EFF	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient property

Range minimum	Range maximum	Specification
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. See <a href="#">[MS-NSPI]</a> for more information about the static mapping of NSPI property names to property IDs that occurs in this ID range.

### 1.3.4 WebDAV Property Naming

The mail server is natively a MAPI store where the vast majority of properties in it are MAPI properties. The WebDAV implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as specified in [\[RFC4234\]](#), as a way to name MAPI properties, allowing WebDAV clients to work with these properties directly.

The `http://schemas.microsoft.com/mapi/` namespace is used to directly access MAPI properties on the server. The namespace consists of three sub namespaces: `proptag`, `id`, and `string`. The ABNF notation used to specify the format of these namespaces is described in this section.

#### 1.3.4.1 `http://schemas.microsoft.com/mapi/proptag` Namespace

This namespace is used to access properties on the server that are identified by a property ID. You can access these properties through WebDAV by appending the hexadecimal property ID value and the hexadecimal property type value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type
property-id      = 4HEXDIG
property-type    = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

#### 1.3.4.2 `http://schemas.microsoft.com/mapi/id` Namespace

This namespace is used to access named properties on the server that are identified by a **property long ID**. You can access these properties through WebDAV by appending the property set and the hexadecimal **property long ID** value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/"x" property-long-id
property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"
```

property-long-id = 8HEXDIG

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213  
(PidLidAppointmentDuration)
```

### 1.3.4.3 <http://schemas.microsoft.com/mapi/string> Namespace

This namespace is used to access named properties on the server that are identified by a **property name**. You can access these properties through WebDAV by appending the property set and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name  
property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"  
property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject  
(PidNameSubject)
```

## 1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [\[MS-OXCDATA\]](#). For tables and examples specifying property data types, and for tables specifying property and other error codes, see [\[MS-OXCDATA\]](#).

The object type specifications listed in section [1.2.1](#) depend on this document for basic information about message object properties to which they refer. Such basic information includes property IDs and **data types**. This specification, in turn, depends on each of those object type specifications to specify the behavior and semantics of the properties specific to its protocol.

## 1.5 Applicability Statement

This document provides the numeric values needed to encode property names, tags, and types in ROP buffers. It also serves as a convenient index to the object type documents that define how each property is used.

## 1.6 Versioning and Localization

None.

## 1.7 Vendor-Extensible Fields

Property ID ranges, as specified in section [1.3.3](#), describe how applications choose properties to create new message object types or to add functionality to existing types.

## 2 Structures

### 2.1 PidLidAddressBookProviderArrayType

**Canonical name:** PidLidAddressBookProviderArrayType

**Description:** Specifies the state of the contact's electronic addresses and represents a set of bit-flags.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008029

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidABPArrayType

### 2.2 PidLidAddressBookProviderEmailList

**Canonical name:** PidLidAddressBookProviderEmailList

**Description:** Specifies which electronic address properties are set on the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008028

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidABPEmailList

### 2.3 PidLidAddressCountryCode

**Canonical name:** PidLidAddressCountryCode

**Description:** Specifies the country code portion of the contact's mailing address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DD

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

## Consuming References:

**Alternate names:** dispidAddressCountryCode

### 2.4 PidLidAgingDontAgeMe

**Canonical name:** PidLidAgingDontAgeMe

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000850E

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidAgingDontAgeMe

### 2.5 PidLidAllAttendeesList

**Canonical name:** PidLidAllAttendeesList

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001D

**Data type:** PtypString, 0x001F

**Area:** Meetings

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_ALL\_ATTENDEES\_LIST

### 2.6 PidLidAllAttendeesString

**Canonical name:** PidLidAllAttendeesString

**Description:** Specifies a list of all the attendees except for the organizer, including resources and unsendable attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008238

**WebDAV:** <http://schemas.microsoft.com/mapi/allattendeesstring>

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidAllAttendeesString

## 2.7 PidLidAllowExternalCheck

**Canonical name:** PidLidAllowExternalCheck

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008246

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidAllowExternCheck

## 2.8 PidLidAnniversaryEventEntryId

**Canonical name:** PidLidAnniversaryEventEntryId

**Description:** Specifies the object EntryId of the Appointment object that represents a contact's anniversary.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804E

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Alternate names:** dispidAnniversaryEventEID

## 2.9 PidLidAppointmentAuxiliaryFlags

**Canonical name:** PidLidAppointmentAuxiliaryFlags

**Description:** Specifies a bit field that describes the auxiliary state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008207

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptAuxFlags

## 2.10 PidLidAppointmentColor

**Canonical name:** PidLidAppointmentColor

**Description:** Specifies the color to be used when displaying the Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008214

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptColor

## 2.11 PidLidAppointmentCounterProposal

**Canonical name:** PidLidAppointmentCounterProposal

**Description:** Indicates whether a Meeting Response object is a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008257

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptCounterProposal

## 2.12 PidLidAppointmentDuration

**Canonical name:** PidLidAppointmentDuration

**Description:** Specifies the length of the event, in minutes.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008213

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/apptduration>

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptDuration

### 2.13 PidLidAppointmentEndDate

**Canonical name:** PidLidAppointmentEndDate

**Description:** Indicates the date the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008211

**WebDAV:** http://schemas.microsoft.com/mapi/apptenddate

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidApptEndDate

### 2.14 PidLidAppointmentEndTime

**Canonical name:** PidLidAppointmentEndTime

**Description:** Indicates the time the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008210

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptendtime

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidApptEndTime

### 2.15 PidLidAppointmentEndWhole

**Canonical name:** PidLidAppointmentEndWhole

**Description:** Specifies the end date and time for the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820E

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptendwhole

**Area:** Calendar



**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptEndWhole

## 2.16 PidLidAppointmentLastSequence

**Canonical name:** PidLidAppointmentLastSequence

**Description:** Indicates to the organizer the last sequence number that was sent to any attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008203

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptLastSequence

## 2.17 PidLidAppointmentMessageClass

**Canonical name:** PidLidAppointmentMessageClass

**Description:** Indicates the message class of the Meeting object that is to be generated from the Meeting Request object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000024

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptMessageClass

## 2.18 PidLidAppointmentNotAllowPropose

**Canonical name:** PidLidAppointmentNotAllowPropose

**Description:** Indicates whether attendees are not allowed to propose a new date and/or time for the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptNotAllowPropose

## 2.19 PidLidAppointmentProposalNumber

**Canonical name:** PidLidAppointmentProposalNumber

**Description:** Specifies the number of attendees who have sent counter proposals that have not been accepted or rejected by the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008259

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposalNum

## 2.20 PidLidAppointmentProposedDuration

**Canonical name:** PidLidAppointmentProposedDuration

**Description:** Indicates the proposed value for PidLidAppointmentDuration for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008256

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedDuration

## 2.21 PidLidAppointmentProposedEndWhole

**Canonical name:** PidLidAppointmentProposedEndWhole

**Description:** Specifies the proposed value for PidLidAppointmentEndWhole for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008251

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedEndWhole

## 2.22 PidLidAppointmentProposedStartWhole

**Canonical name:** PidLidAppointmentProposedStartWhole

**Description:** Specifies the proposed value for PidLidAppointmentStartWhole for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008250

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedStartWhole

## 2.23 PidLidAppointmentRecur

**Canonical name:** PidLidAppointmentRecur

**Description:** Specifies the dates and times when a recurring series occurs.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008216

**Data type:** PtypBinary, 0x0102

**WebDAV:** <http://schemas.microsoft.com/mapi/apptrecur>

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptRecur

## 2.24 PidLidAppointmentReplyName

**Canonical name:** PidLidAppointmentReplyName

**Description:** Specifies the user who last replied to the meeting request or meeting update.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008230

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/apptreplyname

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptReplyName, http://schemas.microsoft.com/mapi/apptreplyname

## 2.25 PidLidAppointmentReplyTime

**Canonical name:** PidLidAppointmentReplyTime

**Description:** Specifies the date and time at which the attendee responded to a received meeting request or Meeting Update object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008220

**Data type:** PtypTime, 0x0040

**WebDAV:** urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidApptReplyTime

## 2.26 PidLidAppointmentSequence

**Canonical name:** PidLidAppointmentSequence

**Description:** Specifies the sequence number of a Meeting object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008201

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptsequence

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptSequence

## 2.27 PidLidAppointmentSequenceTime

**Canonical name:** PidLidAppointmentSequenceTime

**Description:** Indicates the date and time at which the property PidLidAppointmentSequence was last modified.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008202

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptSeqTime

## 2.28 PidLidAppointmentStartDate

**Canonical name:** PidLidAppointmentStartDate

**Description:** Identifies the date the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008212

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptstartdate>

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidApptStartDate

## 2.29 PidLidAppointmentStartTime

**Canonical name:** PidLidAppointmentStartTime

**Description:** Identifies the time the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820F

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptstarttime>

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidApptStartTime

### 2.30 PidLidAppointmentStartWhole

**Canonical name:** PidLidAppointmentStartWhole

**Description:** Specifies the start date and time of the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820D

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptstartwhole>

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStartWhole

### 2.31 PidLidAppointmentStateFlags

**Canonical name:** PidLidAppointmentStateFlags

**Description:** Specifies a bit field that describes the state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008217

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/apptstateflags>

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStateFlags

### 2.32 PidLidAppointmentSubType

**Canonical name:** PidLidAppointmentSubType

**Description:** Specifies whether the event is an all-day event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008215

**Data type:** PtypBoolean, 0x000B

**WebDAV:** urn:schemas:calendar:alldayevent, http://schemas.microsoft.com/mapi/apptsubtype

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidApptSubType

### 2.33 PidLidAppointmentTimeZoneDefinitionEndDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionEndDisplay

**Description:** Specifies time zone information that indicates the time zone of the PidLidAppointmentEndWhole property.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825F

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefEndDisplay

### 2.34 PidLidAppointmentTimeZoneDefinitionRecur

**Canonical name:** PidLidAppointmentTimeZoneDefinitionRecur

**Description:** Specifies time zone information that describes how to convert the meeting date and time on a recurring series to and from UTC.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008260

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** dispidApptTZDefRecur

## 2.35 PidLidAppointmentTimeZoneDefinitionStartDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionStartDisplay

**Description:** Specifies time zone information that indicates the time zone of the PidLidAppointmentStartWhole property.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825E

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefStartDisplay

## 2.36 PidLidAppointmentUnsendableRecipients

**Canonical name:** PidLidAppointmentUnsendableRecipients

**Description:** Contains a list of unsendable attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825D

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidApptUnsendableRecips

## 2.37 PidLidAppointmentUpdateTime

**Canonical name:** PidLidAppointmentUpdateTime

**Description:** Indicates the time at which the appointment was last updated.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008226

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptupdatetime>

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)



**Consuming References:**

**Alternate names:** dispidApptUpdateTime

### 2.38 PidLidAttendeeCriticalChange

**Canonical name:** PidLidAttendeeCriticalChange

**Description:** Specifies the date and time at which the meeting-related object was sent.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000001

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/attendee\_critical\_change

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_ATTENDEE\_CRITICAL\_CHANGE

### 2.39 PidLidAutoFillLocation

**Canonical name:** PidLidAutoFillLocation

**Description:** Indicates whether the value of the PidLidLocation property is set to the PidTagDisplayName property from the RecipientRow that represents a resource.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAutoFillLocation

### 2.40 PidLidAutoLog

**Canonical name:** PidLidAutoLog

**Description:** Specifies to the application whether to create a Journal object for each action associated with this Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008025

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidAutoLog

## 2.41 PidLidAutoProcessState

**Canonical name:** PidLidAutoProcessState

**Description:** Specifies the options used in automatic processing of email messages.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851A

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining References:** [\[MS-OXOMSG\]](#)

**Consuming References:**

**Alternate names:** dispidSniffState

## 2.42 PidLidAutoStartCheck

**Canonical name:** PidLidAutoStartCheck

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008244

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidAutoStartCheck

## 2.43 PidLidAutoStartWhen

**Canonical name:** PidLidAutoStartWhen

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008245

**Data type:** PtypInteger32, 0x0003

**Area:** Conferencing

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAutoStartWhen

## 2.44 PidLidBilling

**Canonical name:** PidLidBilling

**Description:** Specifies billing information for the contact.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008535

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:billinginformation

**Area:** General Message Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidBilling

## 2.45 PidLidBirthdayEventEntryId

**Canonical name:** PidLidBirthdayEventEntryId

**Description:** Specifies the object EntryId of an optional Appointment object that represents the contact's birthday.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804D

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidBirthdayEventEID

## 2.46 PidLidBirthdayLocal

**Canonical name:** PidLidBirthdayLocal

**Description:** Specifies the birthday of a contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DE

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidApptBirthdayLocal

## 2.47 PidLidBusinessCardCardPicture

**Canonical name:** PidLidBusinessCardCardPicture

**Description:** Contains the image to be used on a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008041

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidBCCardPicture

## 2.48 PidLidBusinessCardDisplayDefinition

**Canonical name:** PidLidBusinessCardDisplayDefinition

**Description:** Contains user customization details for displaying a contact as a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008040

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidBCDisplayDefinition

## 2.49 PidLidBusyStatus

**Canonical name:** PidLidBusyStatus

**Description:** Specifies the availability of a user for the event described by the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008205

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/busystatus>

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidBusyStatus

## 2.50 PidLidCalendarType

**Canonical name:** PidLidCalendarType

**Description:** Contains the value of the CalendarType field from the PidLidAppointmentRecur property.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/calendar\\_type](http://schemas.microsoft.com/mapi/calendar_type)

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_CALENDAR\_TYPE

## 2.51 PidLidCategories

**Canonical name:** PidLidCategories

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00009000

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** dispidCategories

## 2.52 PidLidCcAttendeesString

**Canonical name:** PidLidCcAttendeesString

**Description:** Contains a list of all the sendable attendees who are also optional attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823C

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidCCAttendeesString

### 2.53 PidLidChangeHighlight

**Canonical name:** PidLidChangeHighlight

**Description:** Specifies a bit field that indicates how the Meeting object has changed.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008204

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidChangeHighlight

### 2.54 PidLidClassification

**Canonical name:** PidLidClassification

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B6

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassification

### 2.55 PidLidClassificationDescription

**Canonical name:** PidLidClassificationDescription

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B7

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassDesc

## 2.56 PidLidClassificationGuid

**Canonical name:** PidLidClassificationGuid

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B8

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassGuid

## 2.57 PidLidClassificationKeep

**Canonical name:** PidLidClassificationKeep

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BA

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassKeep

## 2.58 PidLidClassified

**Canonical name:** PidLidClassified

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B5

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassified

## 2.59 PidLidCleanGlobalObjectId

**Canonical name:** PidLidCleanGlobalObjectId

**Description:** Contains the value of the PidLidGlobalObjectId property for an object that represents an exception to a recurring series, where the Year, Month, and Day fields are all zero.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000023

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidCleanGlobalObjId

## 2.60 PidLidClientIntent

**Canonical name:** PidLidClientIntent

**Description:** Specifies the end date and time of the event in UTC.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x00000015

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidClientIntent

## 2.61 PidLidClipEnd

**Canonical name:** PidLidClipEnd

**Description:** Specifies the end date and time of the event in UTC.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008236

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidClipEnd

## 2.62 PidLidClipStart

**Canonical name:** PidLidClipStart

**Description:** Specifies the start date and time of the event in UTC.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008235



**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidClipStart

### 2.63 PidLidCollaborateDoc

**Canonical name:** PidLidCollaborateDoc

**Description:** Specifies the document to be launched when the user joins the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008247

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidCollaborateDoc

### 2.64 PidLidCommonEnd

**Canonical name:** PidLidCommonEnd

**Description:** Indicates the end time for the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008517

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidCommonEnd

### 2.65 PidLidCommonStart

**Canonical name:** PidLidCommonStart

**Description:** Indicates the start time for the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008516

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining References:** [\[MS-OXCMSG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidCommonStart

## 2.66 PidLidCompanies

**Canonical name:** PidLidCompanies

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008539

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**References:** [\[MS-OXOJRNL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidCompanies, <http://schemas.microsoft.com/exchange/companies>

## 2.67 PidLidConferencingCheck

**Canonical name:** PidLidConferencingCheck

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008240

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfCheck

## 2.68 PidLidConferencingType

**Canonical name:** PidLidConferencingType

**Description:** Specifies the type of the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008241

**Data type:** PtypInteger32, 0x0003

**Area:** Conferencing

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfType

## 2.69 PidLidContactCharacterSet

**Canonical name:** PidLidContactCharacterSet

**Description:** Specifies the character set used for a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008023

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidContactCharSet

## 2.70 PidLidContactItemData

**Canonical name:** PidLidContactItemData

**Description:** Specifies the visible fields in the application's user interface that are used to help display the contact information.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008007

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidContactItemData

## 2.71 PidLidContactLinkEntry

**Canonical name:** PidLidContactLinkEntry

**Description:** Contains the elements of PidLidContacts.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008585

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXCMMSG\]](#)

**Consuming References:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkEntry

## 2.72 PidLidContactLinkName

**Canonical name:** PidLidContactLinkName

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008586

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkName

## 2.73 PidLidContactLinkSearchKey

**Canonical name:** PidLidContactLinkSearchKey

**Description:** Contains the list of SearchKeys for a Contact object linked to by the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008584

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXCMMSG\]](#)

**Consuming References:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkSearchKey

## 2.74 PidLidContacts

**Canonical name:** PidLidContacts

**Description:** Contains the PidTagDisplayName of each Address Book EntryID referenced in the value of PidLidContactLinkEntry.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000853A

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining References:** [\[MS-OXCMSG\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContacts

## 2.75 PidLidContactUserField1

**Canonical name:** PidLidContactUserField1

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804F

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/extensionattribute1>

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidContactUserField1

## 2.76 PidLidContactUserField2

**Canonical name:** PidLidContactUserField2

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008050

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/extensionattribute2>

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidContactUserField2

## 2.77 PidLidContactUserField3

**Canonical name:** PidLidContactUserField3

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008051

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute3

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidContactUserField3

## 2.78 PidLidContactUserField4

**Canonical name:** PidLidContactUserField4

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008052

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute4

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidContactUserField4

## 2.79 PidLidConversationActionLastAppliedTime

**Canonical name:** PidLidConversationActionLastAppliedTime

**Description:** Contains the time (in UTC) that an E-mail object was last received in the conversation, or the last time that the user modified the Conversation Action, whichever occurs later.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CA

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining References:** [\[MS-OXOCFG\]](#)

**Consuming References:**

**Alternate names:** dispidConvActionLastAppliedTime

## 2.80 PidLidConversationActionMaxDeliveryTime

**Canonical name:** PidLidConversationActionMaxDeliveryTime

**Description:** Contains the maximum value of PidTagMessageDeliveryTime of all the E-mail objects modified in response to the last time the user changed a Conversation Action on the client.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C8

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining References:** [\[MS-OXOCFG\]](#)

**Consuming References:**

**Alternate names:** dispidConvActionMaxDeliveryTime

## 2.81 PidLidConversationActionMoveFolderEid

**Canonical name:** PidLidConversationActionMoveFolderEid

**Description:** Contains the entry ID for the destination folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C6

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining References:** [\[MS-OXOCFG\]](#)

**Consuming References:**

**Alternate names:** dispidConvActionMoveFolderEid

## 2.82 PidLidConversationActionMoveStoreEid

**Canonical name:** PidLidConversationActionMoveStoreEid

**Description:** Contains the entry ID for a move to a folder in a different store.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C7

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining References:** [\[MS-OXOCFG\]](#)

**Consuming References:**

**Alternate names:** dispidConvActionMoveStoreEid

### 2.83 PidLidConversationActionVersion

**Canonical name:** PidLidConversationActionVersion

**Description:** Contains the version of the conversation action FAI message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CB

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**Defining References:** [\[MS-OXOCFG\]](#)

**Consuming References:**

**Alternate names:** dispidConvActionVersion

### 2.84 PidLidConversationProcessed

**Canonical name:** PidLidConversationProcessed

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C9

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** dispidConvExLegacyProcessedRand

### 2.85 PidLidCurrentVersion

**Canonical name:** PidLidCurrentVersion

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008552

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidCurrentVersion



## 2.86 PidLidCurrentVersionName

**Canonical name:** PidLidCurrentVersionName

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008554

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidCurrentVersionName

## 2.87 PidLidDayInterval

**Canonical name:** PidLidDayInterval

**Description:** Identifies the day interval for the recurrence pattern.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000011

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/day\\_interval](http://schemas.microsoft.com/mapi/day_interval)

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_DAY\_INTERVAL

## 2.88 PidLidDayOfMonth

**Canonical name:** PidLidDayOfMonth

**Description:** Identifies the day of the month for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001000

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/dayofmonth>

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:**

## 2.89 PidLidDelegateMail

**Canonical name:** PidLidDelegateMail

**Description:** Indicates whether a delegate responded to the meeting request.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000009

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/delegate\_mail

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_DELEGATE\_MAIL

## 2.90 PidLidDepartment

**Canonical name:** PidLidDepartment

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008010

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#)

**Alternate names:** dispidDepartment

## 2.91 PidLidDirectory

**Canonical name:** PidLidDirectory

**Description:** Specifies the directory server to be used with NetMeeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008242

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidDirectory

## 2.92 PidLidDistributionListChecksum

**Canonical name:** PidLidDistributionListChecksum

**Description:** Specifies the 32-bit cyclic redundancy check (CRC-32) polynomial checksum, as specified in [ISO/IEC 8802-3], calculated on the value of PidLidDistributionListMembers.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804C

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidDLChecksum

## 2.93 PidLidDistributionListMembers

**Canonical name:** PidLidDistributionListMembers

**Description:** Specifies the list of EntryIds of the objects corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008055

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXCDATA\]](#)

**Alternate names:** dispidDLMembers

## 2.94 PidLidDistributionListName

**Canonical name:** PidLidDistributionListName

**Description:** Specifies the name of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008053

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidDLName

## 2.95 PidLidDistributionListOneOffMembers

**Canonical name:** PidLidDistributionListOneOffMembers

**Description:** Specifies the list of one-off EntryIds corresponding to the members of the personal distribution list.

**Property set:** PSEID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008054

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidDLOneOffMembers

## 2.96 PidLidDistributionListStream

**Canonical name:** PidLidDistributionListStream

**Description:** Specifies the list of EntryIds and one-off EntryIds corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008064

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidDLStream

## 2.97 PidLidEmail1AddressType

**Canonical name:** PidLidEmail1AddressType

**Description:** Specifies the address type of an electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008082

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1AddrType

## 2.98 PidLidEmail1DisplayName

**Canonical name:** PidLidEmail1DisplayName

**Description:** Specifies the user-readable display name for the e-mail address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008080

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1DisplayName

## 2.99 PidLidEmail1EmailAddress

**Canonical name:** PidLidEmail1EmailAddress

**Description:** Specifies the e-mail address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008083

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1EmailAddress

## 2.100 PidLidEmail1OriginalDisplayName

**Canonical name:** PidLidEmail1OriginalDisplayName

**Description:** Specifies the SMTP e-mail address corresponding to the e-mail address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008084

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidEmail1OriginalDisplayName

### 2.101 PidLidEmail1OriginalEntryId

**Canonical name:** PidLidEmail1OriginalEntryId

**Description:** Specifies the EntryId of the object corresponding to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008085

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidEmail1OriginalEntryID

### 2.102 PidLidEmail1RichTextFormat

**Canonical name:** PidLidEmail1RichTextFormat

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008086

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#)

**Alternate names:** dispidEmail1RTF

### 2.103 PidLidEmail2AddressType

**Canonical name:** PidLidEmail2AddressType

**Description:** Specifies the address type of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008092

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2AddrType

## 2.104 PidLidEmail2DisplayName

**Canonical name:** PidLidEmail2DisplayName

**Description:** Specifies the user-readable display name for the e-mail address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008090

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2DisplayName

## 2.105 PidLidEmail2EmailAddress

**Canonical name:** PidLidEmail2EmailAddress

**Description:** Specifies the e-mail address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008093

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2EmailAddress

## 2.106 PidLidEmail2OriginalDisplayName

**Canonical name:** PidLidEmail2OriginalDisplayName

**Description:** Specifies the SMTP e-mail address corresponding to the e-mail address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008094

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidEmail2OriginalDisplayName

### 2.107 PidLidEmail2OriginalEntryId

**Canonical name:** PidLidEmail2OriginalEntryId

**Description:** Specifies the EntryId of the object corresponding to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008095

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidEmail2OriginalEntryID

### 2.108 PidLidEmail2RichTextFormat

**Canonical name:** PidLidEmail2RichTextFormat

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008096

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#)

**Alternate names:** dispidEmail1RTF

### 2.109 PidLidEmail3AddressType

**Canonical name:** PidLidEmail3AddressType

**Description:** Specifies the address type of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)



**Alternate names:** dispidEmail3AddrType

### 2.110 PidLidEmail3DisplayName

**Canonical name:** PidLidEmail3DisplayName

**Description:** Specifies the user-readable display name for the e-mail address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A0

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3DisplayName

### 2.111 PidLidEmail3EmailAddress

**Canonical name:** PidLidEmail3EmailAddress

**Description:** Specifies the e-mail address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3EmailAddress

### 2.112 PidLidEmail3OriginalDisplayName

**Canonical name:** PidLidEmail3OriginalDisplayName

**Description:** Specifies the SMTP e-mail address corresponding to the e-mail address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** Specifies the EntryId of the object corresponding to this electronic address.

**Alternate names:** dispidEmail3OriginalDisplayName

### 2.113 PidLidEmail3OriginalEntryId

**Canonical name:** PidLidEmail3OriginalEntryId

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#)

**Alternate names:** dispidEmail3OriginalEntryID

### 2.114 PidLidEmail3RichTextFormat

**Canonical name:** PidLidEmail3RichTextFormat

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A6

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#)

**Alternate names:** dispidEmail1RTF

### 2.115 PidLidEmailList

**Canonical name:** PidLidEmailList

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008027

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#)

**Alternate names:** dispidEmailList

### 2.116 PidLidEndRecurrenceDate

**Canonical name:** PidLidEndRecurrenceDate

**Description:** Identifies the end date of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000F

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/end\_recur\_date

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** LID\_END\_RECUR\_DATE

### 2.117 PidLidEndRecurrenceTime

**Canonical name:** PidLidEndRecurrenceTime

**Description:** Identifies the end time of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000010

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/end\_recur\_time

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** LID\_END\_RECUR\_TIME

### 2.118 PidLidExceptionReplaceTime

**Canonical name:** PidLidExceptionReplaceTime

**Description:** Specifies the date and time, in UTC, within a recurrence pattern that an exception will replace.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008228

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidExceptionReplaceTime

## 2.119 PidLidFax1AddressType

**Canonical name:** PidLidFax1AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax1AddrType

## 2.120 PidLidFax1EmailAddress

**Canonical name:** PidLidFax1EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax1EmailAddress

## 2.121 PidLidFax1OriginalDisplayName

**Canonical name:** PidLidFax1OriginalDisplayName

**Description:** Contains the same value as PidTagNormalizedSubject.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax1OriginalDisplayName

### 2.122 PidLidFax1OriginalEntryId

**Canonical name:** PidLidFax1OriginalEntryId

**Description:** Specifies a one-off EntryId corresponding to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax1OriginalEntryID

### 2.123 PidLidFax2AddressType

**Canonical name:** PidLidFax2AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax2AddrType

### 2.124 PidLidFax2EmailAddress

**Canonical name:** PidLidFax2EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax2EmailAddress

## 2.125 PidLidFax2OriginalDisplayName

**Canonical name:** PidLidFax2OriginalDisplayName

**Description:** Contains the same value as PidTagNormalizedSubject.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax2OriginalDisplayName

## 2.126 PidLidFax2OriginalEntryId

**Canonical name:** PidLidFax2OriginalEntryId

**Description:** Specifies a one-off EntryId corresponding to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax2OriginalEntryID

## 2.127 PidLidFax3AddressType

**Canonical name:** PidLidFax3AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax3AddrType

**2.128 PidLidFax3EmailAddress**

**Canonical name:** PidLidFax3EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Adrsss {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax3EmailAddress

**2.129 PidLidFax3OriginalDisplayName**

**Canonical name:** PidLidFax3OriginalDisplayName

**Description:** Contains the same value as PidTagNormalizedSubject.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax3OriginalDisplayName

**2.130 PidLidFax3OriginalEntryId**

**Canonical name:** PidLidFax3OriginalEntryId

**Description:** Specifies a one-off EntryId corresponding to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFax3OriginalEntryID

### 2.131 PidLidFExceptionalAttendees

**Canonical name:** PidLidFExceptionalAttendees

**Description:** Indicates that the object is a Recurring Calendar object with one or more exceptions, and at least one of the Exception Embeddd Message objects has at least one RecipientRow.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822B

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidFExceptionalAttendees

### 2.132 PidLidFExceptionalBody

**Canonical name:** PidLidFExceptionalBody

**Description:** Indicates that the Exception Embedded Message object has a body that differs from the Recurring Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008206

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidFExceptionalBody

### 2.133 PidLidFileUnder

**Canonical name:** PidLidFileUnder

**Description:** Specifies the name under which to file a contact when displaying a list of contacts.

**Property set:** PSETID\_Address {0006204-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008005



**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFileUnder

### 2.134 PidLidFileUnderId

**Canonical name:** PidLidFileUnderId

**Description:** Specifies how to generate and recompute the value of the PidLidFileUnder property when other Contact Name properties change.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008006

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFileUnderId

### 2.135 PidLidFileUnderList

**Canonical name:** PidLidFileUnderList

**Description:** Specifies a list of possible values for PidLidFileUnderId.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008026

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidFileUnderList

### 2.136 PidLidFInvited

**Canonical name:** PidLidFInvited

**Description:** Indicates whether invitations have been sent for the meeting that this Meeting object represents.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008229

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/invited

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFInvited

### 2.137 PidLidFlagRequest

**Canonical name:** PidLidFlagRequest

**Description:** Contains user-specifiable text to be associated with the flag.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008530

**Data type:** typString, 0x001F

**WebDAV:** urn:schemas:httpmail:messageflag, http://schemas.microsoft.com/mapi/request

**Area:** Flagging

**Defining References:** [\[MS-OXOFLAG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidRequest

### 2.138 PidLidFlagString

**Canonical name:** PidLidFlagString

**Description:** Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

**Property set:** PSETD\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C0

**Data type:** typInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOFLAG\]](#)

**Consuming References:**

**Alternate names:** dispidFlagStringEnum

## 2.139 PidLidForwardInstance

**Canonical name:** PidLidForwardInstance

**Description:** Indicates whether the Meeting Request object represents an exception to a recurring series, and it was forwarded (even when forwarded by the organizer) rather than being an invitation sent by the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidFwrInstance

## 2.140 PidLidForwardNotificationRecipients

**Canonical name:** PidLidForwardNotificationRecipients

**Description:** Contains a list of RecipientRows that indicate the recipients of a meeting forward.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008261

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidForwardNotificationRecipients

## 2.141 PidLidFOthersAppointment

**Canonical name:** PidLidFOthersAppointment

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822F

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFOthersAppt, <http://schemas.microsoft.com/mapi/fothersappt>

## 2.142 PidLidFreeBusyLocation

**Canonical name:** PidLidFreeBusyLocation

**Description:** Specifies a URL path from which a client can retrieve free/busy information for the contact.

**Property set:** PSETID\_Address{00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D8

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:fburl

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidFreeBusyLocation

## 2.143 PidLidGlobalObjectId

**Canonical name:** PidLidGlobalObjectId

**Description:** Contains the value of the PidLidGlobalObjectId property for an object that represents an exception to a recurring series.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000003

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#)

**Alternate names:** LID\_GLOBAL\_OBJID

## 2.144 PidLidHasPicture

**Canonical name:** PidLidHasPicture

**Description:** Specifies whether the attachment has a picture.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008015

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidHasPicture

**2.145 PidLidHomeAddress**

**Canonical name:** PidLidHomeAddress

**Description:** Specifies the complete address of the contact's home address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:homepostaladdress

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidHomeAddress

**2.146 PidLidHomeAddressCountryCode**

**Canonical name:** PidLidHomeAddressCountryCode

**Description:** Specifies the country code portion of the contact's home address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DA

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidHomeAddressCountryCode

**2.147 PidLidHtml**

**Canonical name:** PidLidHtml

**Description:** Specifies the contact's business web page URL.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidHTML

## 2.148 PidLidICalendarDayOfWeekMask

**Canonical name:** PidLidICalendarDayOfWeekMask

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001001

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** http://schemas.microsoft.com/mapi/dayofweekmask

## 2.149 PidLidInboundICalStream

**Canonical name:** PidLidInboundICalStream

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827A

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InboundICalStream, dispidInboundICalStream

## 2.150 PidLidInfoPathFormName

**Canonical name:** PidLidInfoPathFormName

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x85B1

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.151 PidLidInstantMessagingAddress

**Canonical name:** PidLidInstantMessagingAddress

**Description:** Specifies the contact's instant messaging address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008062

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidInstMsg

## 2.152 PidLidIntendedBusyStatus

**Canonical name:** PidLidIntendedBusyStatus

**Description:** Contains the value of the PidLidBusyStatus property on the Meeting object in the organizer's calendar at the time the Meeting Request object or Meeting Update object was sent.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008224

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/intendedbusystatus>

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidIntendedBusyStatus

## 2.153 PidLidInternetAccountName

**Canonical name:** PidLidInternetAccountName

**Description:** Specifies the user-visible email account name through which the email message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008580

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining References:** [\[MS-OXOMSG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidInetAcctName

## 2.154 PidLidInternetAccountStamp

**Canonical name:** PidLidInternetAccountStamp

**Description:** Specifies the email account ID through which the email message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008581

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining References:** [\[MS-OXOMSG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidInetAcctStamp

## 2.155 PidLidIsException

**Canonical name:** PidLidIsException

**Description:** Indicates whether the object represents an exception (including an orphan instance).

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000A

**Data type:** PtypBoolean, 0x000B

**WebDAV:** [http://schemas.microsoft.com/mapi/is\\_exception](http://schemas.microsoft.com/mapi/is_exception)

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_EXCEPTION

## 2.156 PidLidIsRecurring

**Canonical name:** PidLidIsRecurring

**Description:** Specifies whether the object is associated with a recurring series.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000005

**Data type:** PtypBoolean, 0x000B

**WebDAV:** [http://schemas.microsoft.com/mapi/is\\_recurring](http://schemas.microsoft.com/mapi/is_recurring)

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)



**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_RECURRING

## 2.157 PidLidIsSilent

**Canonical name:** PidLidIsSilent

**Description:** Indicates whether the user did not include any text in the body of the Meeting Response object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000004

**Data type:** PtypBoolean, 0x000B

**WebDAV:** [http://schemas.microsoft.com/mapi/is\\_silent](http://schemas.microsoft.com/mapi/is_silent)

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_SILENT

## 2.158 PidLidLinkedTaskItems

**Canonical name:** PidLidLinkedTaskItems

**Description:** Indicates whether the user did not include any text in the body of the Meeting Response object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820C

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Tasks

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidLinkedTaskItems

## 2.159 PidLidLocation

**Canonical name:** PidLidLocation

**Description:** Specifies the location of the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008208

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:location

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidLocation

## 2.160 PidLidLogDocumentPosted

**Canonical name:** PidLidLogDocumentPosted

**Description:** Indicates whether the document was sent by e-mail or posted to a server folder during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008711

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining References:** [\[MS-EXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogDocPosted

## 2.161 PidLidLogDocumentPrinted

**Canonical name:** PidLidLogDocumentPrinted

**Description:** Indicates whether the document was printed during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870E

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining References:** [\[MS-EXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogDocPrinted

## 2.162 PidLidLogDocumentRouted

**Canonical name:** PidLidLogDocumentRouted

**Description:** Indicates whether the document was sent to a routing recipient during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008710

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogDocRouted

### 2.163 PidLidLogDocumentSaved

**Canonical name:** PidLidLogDocumentSaved

**Description:** Indicates whether the document was saved during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870F

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogDocSaved

### 2.164 PidLidLogDuration

**Canonical name:** PidLidLogDuration

**Description:** Contains the duration in minutes of the activity.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008707

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogDuration

### 2.165 PidLidLogEnd

**Canonical name:** PidLidLogEnd

**Description:** Contains the time at which the activity ended.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008708

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogEnd

## 2.166 PidLidLogFlags

**Canonical name:** PidLidLogFlags

**Description:** Contains metadata about the Journal object.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870C

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogFlags

## 2.167 PidLidLogStart

**Canonical name:** PidLidLogStart

**Description:** Contains the time at which the activity began.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008706

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogStart

## 2.168 PidLidLogType

**Canonical name:** PidLidLogType

**Description:** Briefly describes the activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008700

**Data type:** PtyString, 0x001F

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogType

## 2.169 PidLidLogTypeDesc

**Canonical name:** PidLidLogTypeDesc

**Description:** Describes the activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008712

**Data type:** PtypString, 0x001F

**Area:** Journal

**Defining References:** [\[MS-OXOJRNL\]](#)

**Consuming References:**

**Alternate names:** dispidLogTypeDesc

## 2.170 PidLidMeetingType

**Canonical name:** PidLidMeetingType

**Description:** Indicates the type of Meeting Request object or Meeting Update object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000026

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMeetingType

## 2.171 PidLidMeetingWorkspaceUrl

**Canonical name:** PidLidMeetingWorkspaceUrl

**Description:** Specifies the URL of the Meeting Workspace that is associated with a Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008209

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/meetingworkspaceurl

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMWSURL

## 2.172 PidLidMonthInterval

**Canonical name:** PidLidMonthInterval

**Description:** Indicates the monthly interval of the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA03F1305}

**Property long ID (LID):** 0x00000013

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/month\_interval

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_MONTH\_INTERVAL

## 2.173 PidLidMonthOfYear

**Canonical name:** PidLidMonthOfYear

**Description:** Indicates the month of the year that the appointment or meeting occurs.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001006

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/monthofyear

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:**

## 2.174 PidLidMonthOfYearMask

**Canonical name:** PidLidMonthOfYearMask

**Description:** Indicates the month of the year that the appointment or meeting occurs.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000017

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/moy\_mask

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** LID\_MOY\_MASK

## 2.175 PidLidNetShowUrl

**Canonical name:** PidLidNetShowUrl

**Description:** Specifies the URL to be launched when the user joins the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008248

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidNetShowURL

## 2.176 PidLidNoEndDateFlag

**Canonical name:** PidLidNoEndDateFlag

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** http://schemas.microsoft.com/mapi/fnoenddate

## 2.177 PidLidNonSendableBcc

**Canonical name:** PidLidNonSendableBcc

**Description:** Contains a list of all the unsendable attendees who are also resources.

**Property set:** PSETID\_Common {00062008-0000-0000-C00-000000000046}

**Property long ID (LID):** 0x00008538

**Data type:** typString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendablebcc

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableBCC

## 2.178 PidLidNonSendableCc

**Canonical name:** PidLidNonSendableCc

**Description:** Contains a list of all the unsendable attendees who are also optional attendees.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008537

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendablecc

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableCC

## 2.179 PidLidNonSendableTo

**Canonical name:** PidLidNonSendableTo

**Description:** Contains a list of all the unsendable attendees who are also required attendees.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008536

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendableto

**Area:** Meetings



**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableTo

## 2.180 PidLidNonSendBccTrackStatus

**Canonical name:** PidLidNonSendBccTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008545

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendbcctrackstatus>

**Area:** General Message Properties

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendBccTrackStatus

## 2.181 PidLidNonSendCcTrackStatus

**Canonical name:** PidLidNonSendCcTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008544

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendcctrackstatus>

**Area:** General Message Properties

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendCcTrackStatus

## 2.182 PidLidNonSendToTrackStatus

**Canonical name:** PidLidNonSendToTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008543

**Data type:** typMultipleInteger32, 0x1003

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendtotrackstatus

**Area:** General Message Properties

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendToTrackStatus

### 2.183 PidLidNoteColor

**Canonical name:** PidLidNoteColor

**Description:** Specifies the suggested background color of the Note object.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B00

**Data type:** PtpInteger32, 0x0003

**Area:** Sticky Notes

**Defining References:** [\[MS-OXONOTE\]](#)

**Consuming References:**

**Alternate names:** dispidNoteColor

### 2.184 PidLidNoteHeight

**Canonical name:** PidLidNoteHeight

**Description:** Specifies the height of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B03

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining References:** [\[MS-OXONOTE\]](#)

**Consuming References:**

**Alternate names:** dispidNoteHeight

### 2.185 PidLidNoteWidth

**Canonical name:** PidLidNoteWidth

**Description:** Specifies the width of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B02

**Data type:** PtpInteger32, 0x0003

**Area:** Sticky Notes

**Defining References:** [\[MS-OXONOTE\]](#)

**Consuming References:**

**Alternate names:** dispidNoteWidth

## 2.186 PidLidNoteX

**Canonical name:** PidLidNoteX

**Description:** Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a Note object.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B04

**Data type:** PtpInteger32, 0x0003

**Area:** Sticky Notes

**Defining References:** [\[MS-OXONOTE\]](#)

**Consuming References:**

**Alternate names:** dispidNoteX

## 2.187 PidLidNoteY

**Canonical name:** PidLidNoteY

**Description:** Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a Note object.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B05

**Data type:** PtpInteger32, 0x0003

**Area:** Sticky Notes

**Defining References:** [\[MS-OXONOTE\]](#)

**Consuming References:**

**Alternate names:** dispidNoteY

## 2.188 PidLidOccurrences

**Canonical name:** PidLidOccurrences

**Description:** Indicates the number of occurrences in the recurring appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-000-C000-000000000046}

**Property long ID (LID):** 0x00001005

**Data type:** typInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/occurrences

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:**

## 2.189 PidLidOldLocation

**Canonical name:** PidLidOldLocation

**Description:** Indicates the original value of the PidLidLocation property before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000028

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidOldLocation

## 2.190 PidLidOldRecurrenceType

**Canonical name:** PidLidOldRecurrenceType

**Description:** Indicates the recurrence pattern for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000018

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/recur\_type

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** LID\_RECUR\_TYPE

## 2.191 PidLidOldWhenEndWhole

**Canonical name:** PidLidOldWhenEndWhole

**Description:** Indicates the original value of the PidLidAppointmentEndWhole property before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000002A

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidOldWhenEndWhole

## 2.192 PidLidOldWhenStartWhole

**Canonical name:** PidLidOldWhenStartWhole

**Description:** Indicates the original value of the PidLidAppointmentStartWhole property before a meeting update.

**Property set:** PSETID\_Meting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000029

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidOldWhenStartWhole

## 2.193 PidLidOnlinePassword

**Canonical name:** PidLidOnlinePassword

**Description:** Specifies the password for a meeting on which the property PidLidConferencingType has the value 0x00000002.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008249

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidOnlinePassword

## 2.194 PidLidOptionalAttendees

**Canonical name:** PidLidOptionalAttendees

**Description:** Specifies optional attendees.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000007

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/optional\_attendees

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_OPTIONAL\_ATTENDEES

## 2.195 PidLidOrganizerAlias

**Canonical name:** PidLidOrganizerAlias

**Description:** Specifies the e-mail address of the Organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008243

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidOrgAlias

## 2.196 PidLidOriginalStoreEntryId

**Canonical name:** PidLidOriginalStoreEntryId

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008237

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** dispidOrigStoreEid, <http://schemas.microsoft.com/mapi/origstoreid>

## 2.197 PidLidOtherAddress

**Canonical name:** PidLidOtherAddress

**Description:** Specifies the complete address of the contact's other address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801C

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:otherpostaladdress

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidOtherAddress

## 2.198 PidLidOtherAddressCountryCode

**Canonical name:** PidLidOtherAddressCountryCode

**Description:** Specifies the country code portion of the contact's other address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DC

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidOtherAddressCountryCode

## 2.199 PidLidOwnerCriticalChange

**Canonical name:** PidLidOwnerCriticalChange

**Description:** Specifies the date and time at which a Meeting Request object was sent by the organizer.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001A

**Data type:** PtypTime, 0x0040

**WebDAV:** urn:schemas:calendar:dtstamp,  
http://schemas.microsoft.com/mapi/owner\_critical\_change

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** LID\_OWNER\_CRITICAL\_CHANGE

## 2.200 PidLidOwnerName

**Canonical name:** PidLidOwnerName

**Description:** Indicates the name of the owner of the mailbox.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822E

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/ownername

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidOwnerName

## 2.201 PidLidPercentComplete

**Canonical name:** PidLidPercentComplete

**Description:** Indicates whether a time-flagged Message object is completed or not.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008102

**Data type:** PtypFloating64, 0x0005

**Area:** Tasks

**Defining References:** [\[MS-OXOFLAG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidPercentComplete

## 2.202 PidLidPostalAddressId

**Canonical name:** PidLidPostalAddressId



**Description:** Specifies which physical address is the mailing address for this contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008022

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:contacts:mailingaddressid

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidPostalAddressId

## 2.203 PidLidPostRssChannel

**Canonical name:** PidLidPostRssChannel

**Description:** Contains the contents of the title field from the XML of the Atom feed or RSS channel.

**Property set:** PSETID\_PostRss {0006041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008904

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining References:** [\[MS-OXORSS\]](#)

**Consuming References:**

**Alternate names:** dispidPostRssChannel

## 2.204 PidLidPostRssChannelLink

**Canonical name:** PidLidPostRssChannelLink

**Description:** Contains the URL of the RSS or Atom feed that the XML file came from.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008900

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining References:** [\[MS-OXORSS\]](#)

**Consuming References:**

**Alternate names:** dispidPostRssChannelLink

## 2.205 PidLidPostRssItemGuid

**Canonical name:** PidLidPostRssItemGuid

**Description:** Contains a unique identifier for the object, copied from one of the elements listed in the following table.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008903

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining References:** [\[MS-OXORSS\]](#)

**Consuming References:**

**Alternate names:** dispidPostRssItemGuid

## 2.206 PidLidPostRssItemHash

**Canonical name:** PidLidPostRssItemHash

**Description:** Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008902

**Data type:** PtypInteger32, 0x0003

**Area:** RSS

**Defining References:** [\[MS-OXORSS\]](#)

**Consuming References:**

**Alternate names:** dispidPostRssItemHash

## 2.207 PidLidPostRssItemLink

**Canonical name:** PidLidPostRssItemLink

**Description:** Contains the URL of the link from the item.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008901

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining References:** [\[MS-OXORSS\]](#)

**Consuming References:**

**Alternate names:** dispidPostRssItemLink

## 2.208 PidLidPostRssItemXml

**Canonical name:** PidLidPostRssItemXml

**Description:** Contains the item element and all its sub-elements from an RSS feed, or the entry element and all its sub-elements from an Ato feed.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008905

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining References:** [\[MS-OXORSS\]](#)

**Consuming References:**

**Alternate names:** dispidPostRssItemXml

## 2.209 PidLidPostRssSubscription

**Canonical name:** PidLidPostRssSubscription

**Description:** Contains the user's preferred name for the subscription.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008906

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining References:** [\[MS-OXORSS\]](#)

**Consuming References:**

**Alternate names:** dispidPostRssSubscription

## 2.210 PidLidPrivate

**Canonical name:** PidLidPrivate

**Description:** Indicates whether the end-user wishes for this Message object to be hidden from other users who have access to the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008506

**Data type:** typBoolean, 0x000B

**Area:** General Message Properties

**Defining References:** [MS-OXCMSG](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidPrivate

### 2.211 PidLidPromptSendUpdate

**Canonical name:** PidLidPromptSendUpdate

**Description:** Indicates that the Meeting Response object was out-of-date when it was received.

**Property set:** PSETID\_Common {00062008-000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypBoolean, 0x000B

**Area:** Meeting Response

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidPromptSendUpdate

### 2.212 PidLidRecurrenceDuration

**Canonical name:** PidLidRecurrenceDuration

**Description:** Identifies the length, in minutes, of the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/recurduration>

**Area:** Calendar

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:**

### 2.213 PidLidRecurrencePattern

**Canonical name:** PidLidRecurrencePattern

**Description:** Specifies a description of the recurrence pattern of the Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008232

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/recurpattern

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurPattern

## 2.214 PidLidRecurrenceType

**Canonical name:** PidLidRecurrenceType

**Description:** Specifies the recurrence type of the recurring series.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008231

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/recurtype

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurType

## 2.215 PidLidRecurring

**Canonical name:** PidLidRecurring

**Description:** Specifies whether the object represents a recurring series.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008223

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/recurring

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCADATA\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurring

## 2.216 PidLidReferenceEntryId

**Canonical name:** PidLidReferenceEntryId

**Description:** Specifies the value of the EntryId of the Contact object unless the Contact object is a copy of an earlier original.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BD

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidReferenceEID

## 2.217 PidLidReferredBy

**Canonical name:** PidLidReferredBy

**Description:** Specifies the name of the person who referred the contact to the user.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000800E

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:referredby

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidReferredBy

## 2.218 PidLidReminderDelta

**Canonical name:** PidLidReminderDelta

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008501

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderDelta, <http://schemas.microsoft.com/mapi/reminddelta>

## 2.219 PidLidReminderFileParameter

**Canonical name:** PidLidReminderFileParameter

**Description:** Specifies the filename of the sound that a client is to play when the reminder for that object becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851F

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/remindertext

**Area:** Reminders

**Defining References:** [\[MS-OXORMDR\]](#)

**Consuming References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderFileParam

## 2.220 PidLidReminderOverride

**Canonical name:** PidLidReminderOverride

**Description:** Specifies whether the client is to respect the values PidLidReminderPlaySound and PidLidReminderFileParameter, or use the default values for those properties.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851C

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/remindertext

**Area:** Reminders

**Defining References:** [\[MS-OXORMDR\]](#)

**Consuming References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderOverride

## 2.221 PidLidReminderPlaySound

**Canonical name:** PidLidReminderPlaySound

**Description:** Specifies whether the client is to play a sound when the reminder becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851E

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/remindertext

**Area:** Reminders

**Defining References:** [\[MS-OXORMDR\]](#)

**Consuming References:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderPlaySound

## 2.222 PidLidReminderSet

**Canonical name:** PidLidReminderSet

**Description:** Specifies whether a reminder is set on the object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008503

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/reminderset

**Area:** Reminders

**Defining References:** [\[MS-OXORMDR\]](#)

**Consuming References:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderSet

## 2.223 PidLidReminderSignalTime

**Canonical name:** PidLidReminderSignalTime

**Description:** Specifies the point in time when a reminder transitions from pending to overdue.

**Property set:** PSETID\_Common {00062008-000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008560

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindernexttime

**Area:** Reminders

**Defining References:** [\[MS-OXORMDR\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidReminderNextTime

## 2.224 PidLidReminderTime

**Canonical name:** PidLidReminderTime



**Description:** Specifies the initial signal time for non-Calendar objects. For Calendar objects.

**Property set:** PSETID\_Common {00062008-000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008502

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindertime

**Area:** Reminders

**Defining References:** [\[MS-OXORMDR\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderTime

## 2.225 PidLidReminderTimeDate

**Canonical name:** PidLidReminderTimeDate

**Description:** Indicates the time and date of the reminder for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008505

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindertimedate

**Area:** Reminders

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidReminderTimeDate

## 2.226 PidLidReminderTimeTime

**Canonical name:** PidLidReminderTimeTime

**Description:** Indicates the time of the reminder for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008504

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindertimetime

**Area:** Reminders

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidReminderTimeTime

## 2.227 PidLidReminderType

**Canonical name:** PidLidReminderType

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851D

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**References:** [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderType, <http://schemas.microsoft.com/mapi/remindertype>

## 2.228 PidLidRemoteStatus

**Canonical name:** PidLidRemoteStatus

**Description:** Indicates the remote status of the calendar item.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008511

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/remotestatus>

**Area:** Run-time configuration

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** dispidRemoteStatus

## 2.229 PidLidRequiredAttendees

**Canonical name:** PidLidRequiredAttendees

**Description:** Identifies required attendees for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000006

**Data type:** PtypString, 0x001F

**WebDAV:** [http://schemas.microsoft.com/mapi/required\\_attendees](http://schemas.microsoft.com/mapi/required_attendees)

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_REQUIRED\_ATTENDEES

### 2.230 PidLidResourceAttendees

**Canonical name:** PidLidResourceAttendees

**Description:** Identifies resource attendees for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000008

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/resource\_attendees

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_RESOURCE\_ATTENDEES

### 2.231 PidLidResponseStatus

**Canonical name:** PidLidResponseStatus

**Description:** Specifies the response status of an attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008218

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:calendar:attendeestatus,  
http://schemas.microsoft.com/mapi/responsestatus

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidResponseStatus

### 2.232 PidLidSendMeetingAsIcal

**Canonical name:** PidLidSendMeetingAsIcal

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008200

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidSendMtgAsICAL

### 2.233 PidLidServerProcessed

**Canonical name:** PidLidServerProcessed

**Description:** Indicates whether the Meeting Request Object or Meeting Update Object has been processed.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CC

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidExchangeProcessed

### 2.234 PidLidServerProcessingActions

**Canonical name:** PidLidServerProcessingActions

**Description:** Indicates what processing actions have been taken on this Meeting Request Object or Meeting Update Object.

**Property set:** SETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CD

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:**

**Alternate names:** dispidExchangeProcessingAction

### 2.235 PidLidSharingAnonymity

**Canonical name:** PidLidSharingAnonymity

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A19

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingAnonymity

## 2.236 PidLidSharingBindingEntryId

**Canonical name:** PidLidSharingBindingEntryId

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2D

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingBindingEid

## 2.237 PidLidSharingBrowseUrl

**Canonical name:** PidLidSharingBrowseUrl

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A51

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingBrowseUrl

## 2.238 PidLidSharingCapabilities

**Canonical name:** PidLidSharingCapabilities

**Description:** Indicates that the Sharing Message object relates to a special folder.

**Property set:** PSETID\_Sharing {00062040-0000-0000-0000-000000000046}

**Property long ID (LID):** 0x00008A17

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingCaps

## 2.239 PidLidSharingConfigurationUrl

**Canonical name:** PidLidSharingConfigurationUrl

**Description:** Contains a zero-length string.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A24

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingConfigUrl

## 2.240 PidLidSharingDataRangeEnd

**Canonical name:** PidLidSharingDataRangeEnd

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A45

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingDataRangeEnd

## 2.241 PidLidSharingDataRangeStart

**Canonical name:** PidLidSharingDataRangeStart

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A44

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingDataRangeStart

## 2.242 PidLidSharingDetail

**Canonical name:** PidLidSharingDetail

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingDetail

## 2.243 PidLidSharingExtensionXml

**Canonical name:** PidLidSharingExtensionXml

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A21

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingExtXml

## 2.244 PidLidSharingFilter

**Canonical name:** PidLidSharingFilter

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A13

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingFilter

## 2.245 PidLidSharingFlags

**Canonical name:** PidLidSharingFlags

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingFlags

## 2.246 PidLidSharingFlavor

**Canonical name:** PidLidSharingFlavor

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A18

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingFlavor

## 2.247 PidLidSharingFolderEntryId

**Canonical name:** PidLidSharingFolderEntryId

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A15

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingFolderEid

## 2.248 PidLidSharingIndexEntryId

**Canonical name:** PidLidSharingIndexEntryId

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2E

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingIndexEid

## 2.249 PidLidSharingInitiatorEntryId

**Canonical name:** PidLidSharingInitiatorEntryId

**Description:** Contains the value of PidTagEntryId for the Address Book object of the currently loggen-on user.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A09



**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingInitiatorEid

## 2.250 PidLidSharingInitiatorName

**Canonical name:** PidLidSharingInitiatorName

**Description:** Contains the value of PidTagDisplayName from the Address Book object identified by PidLidSharingInitiatorEntryId.

**Propertyset:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A07

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingInitiatorName

## 2.251 PidLidSharingInitiatorSmtip

**Canonical name:** PidLidSharingInitiatorSmtip

**Description:** Contains the value of PidTagSmtipAddress from the AddressBook object identified by PidLidSharingInitiatorEntryId.

**Property et:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A08

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingInitiatorSmtip

## 2.252 PidLidSharingInstanceGuid

**Canonical name:** PidLidSharingInstanceGuid

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingInstanceGuid

## 2.253 PidLidSharingLastAutoSyncTime

**Canonical name:** PidLidSharingLastAutoSyncTime

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A55

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLastAutoSync

## 2.254 PidLidSharingLastSyncTime

**Canonical name:** PidLidSharingLastSyncTime

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1F

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLastSync

## 2.255 PidLidSharingLocalComment

**Canonical name:** PidLidSharingLocalComment

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLocalComment

## 2.256 PidLidSharingLocalLastModificationTime

**Canonical name:** PidLidSharingLocalLastModificationTime

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A23

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLocalLastMod

## 2.257 PidLidSharingLocalName

**Canonical name:** PidLidSharingLocalName

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLocalName

## 2.258 PidLidSharingLocalPath

**Canonical name:** PidLidSharingLocalPath

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLocalPath

## 2.259 PidLidSharingLocalStoreUid

**Canonical name:** PidLidSharingLocalStoreUid

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A49

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLocalStoreUid

## 2.260 PidLidSharingLocalType

**Canonical name:** PidLidSharingLocalType

**Description:** Contains the value of PidTagContainerClass of the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A14

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingLocalType

## 2.261 PidLidSharingLocalUid

**Canonical name:** PidLidSharingLocalUid

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A10

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingLocalUid

## 2.262 PidLidSharingOriginalMessageEntry Id

**Canonical name:** PidLidSharingOriginalMessageEntryId

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A29

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingOriginalMessageEid

### 2.263 PidLidSharingParentBindingEntryId

**Canonical name:** PidLidSharingParentBindingEntryId

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingParentBindingEid

### 2.264 PidLidSharingParticipants

**Canonical name:** PidLidSharingParticipants

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingParticipants

### 2.265 PidLidSharingPermissions

**Canonical name:** PidLidSharingPermissions

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingPermissions

### 2.266 PidLidSharingProviderExtension

**Canonical name:** PidLidSharingProviderExtension

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingProviderExtension

## 2.267 PidLidSharingProviderGuid

**Canonical name:** PidLidSharingProviderGuid

**Description:** Contains the value %xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.46.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A01

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingProviderGuid

## 2.268 PidLidSharingProviderName

**Canonical name:** PidLidSharingProviderName

**Description:** Contains a user-displayable name of the sharing provider identified by PidLidSharingProviderGuid.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A02

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming Reference:**

**Alternate names:** dispidSharingProviderName

## 2.269 PidLidSharingProviderUrl

**Canonical name:** PidLidSharingProviderUrl

**Description:** Contains a URL related to the sharing provider identified by PidLidSharingProviderGuid.

**Property set:** PSETID\_Sharing {0002040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A03

**Data type:**PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingProviderUrl

## 2.270 PidLidSharingRangeEnd

**Canonical name:** PidLidSharingRangeEnd

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A47

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRangeEnd

## 2.271 PidLidSharingRangeStart

**Canonical name:** PidLidSharingRangeStart

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A46

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRangeStart

## 2.272 PidLidSharingReciprocation

**Canonical name:** PidLidSharingReciprocation

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingReciprocation

### 2.273 PidLidSharingRemoteByteSize

**Canonical name:** PidLidSharingRemoteByteSize

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemoteByteSize

### 2.274 PidLidSharingRemoteComment

**Canonical name:** PidLidSharingRemoteComment

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemoteComment

### 2.275 PidLidSharingRemoteCrc

**Canonical name:** PidLidSharingRemoteCrc

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemoteCrc

### 2.276 PidLidSharingRemoteLastModificationTime

**Canonical name:** PidLidSharingRemoteLastModificationTime

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A22

**Data type:** PtypTime, 0x0040



**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemoteLastMod

## 2.277 PidLidSharingRemoteMessageCount

**Canonical name:** PidLidSharingRemoteMessageCount

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4F

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemoteMsgCount

## 2.278 PidLidSharingRemoteName

**Canonical name:** PidLidSharingRemoteName

**Description:** Contains the value of PidTagDisplayName on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000000000000046}

**Property long ID (LID):** 0x00008A05

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingRemoteName

## 2.279 PidLidSharingRemotePass

**Canonical name:** PidLidSharingRemotePass

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemotePass

## 2.280 PidLidSharingRemotePath

**Canonical name:** PidLidSharingRemotePath

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A04

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemotePath

## 2.281 PidLidSharingRemoteStoreUid

**Canonical name:** PidLidSharingRemoteStoreUid

**Description:** Contains a hexadecimal string representation of the value of PidTagStoreEntryId on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A48

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingRemoteStoreUid

## 2.282 PidLidSharingRemoteType

**Canonical name:** PidLidSharingRemoteType

**Description:** Contains the same value as PidLidSharingLocalType.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingRemoteType

## 2.283 PidLidSharingRemoteUid

**Canonical name:** PidLidSharingRemoteUid

**Description:** Contains the hexadecimal string representation of the value of PidTagEntryId on the folder being shared.

**Property set:** PSTID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A06

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingRemoteUid

## 2.284 PidLidSharingRemoteUser

**Canonical name:** PidLidSharingRemoteUser

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0C

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemoteUser

## 2.285 PidLidSharingRemoteVersion

**Canonical name:** PidLidSharingRemoteVersion

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRemoteVersion

## 2.286 PidLidSharingResponseTime

**Canonical name:** PidLidSharingResponseTime

**Description:** Contains the time at which the recipient of the sharing request sent a sharing response.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A28

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References**

**Alternate names:** dispidSharingResponseTime

## 2.287 PidLidSharingResponseType

**Canonical name:** PidLidSharingResponseType

**Description:** Contains the type of response with which the recipient of the sharing request responded.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A27

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining References:** [\[MS-OXSHARE\]](#)

**Consuming References:**

**Alternate names:** dispidSharingResponseType

## 2.288 PidLidSharingRoamLog

**Canonical name:** PidLidSharingRoamLog

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4E

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingRoamLog

## 2.289 PidLidSharingStart

**Canonical name:** PidLidSharingStart

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A25

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingStart

## 2.290 PidLidSharingStatus

**Canonical name:** PidLidSharingStatus

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A00

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingStatus

## 2.291 PidLidSharingStop

**Canonical name:** PidLidSharingStop

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A26

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingStop

## 2.292 PidLidSharingSyncFlags

**Canonical name:** PidLidSharingSyncFlags

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A60

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingSyncFlags

## 2.293 PidLidSharingSyncInterval

**Canonical name:** PidLidSharingSyncInterval

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingSyncInterval

## 2.294 PidLidSharingTimeToLive

**Canonical name:** PidLidSharingTimeToLive

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingTimeToLive

## 2.295 PidLidSharingTimeToLiveAuto

**Canonical name:** PidLidSharingTimeToLiveAuto

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A56

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingTimeToLiveAuto

## 2.296 PidLidSharingWorkingHoursDays

**Canonical name:** PidLidSharingWorkingHoursDays

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A42

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingWorkingHoursDays

## 2.297 PidLidSharingWorkingHoursEnd

**Canonical name:** PidLidSharingWorkingHoursEnd

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A41

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingWorkingHoursEnd

## 2.298 PidLidSharingWorkingHoursStart

**Canonical name:** PidLidSharingWorkingHoursStart

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A40

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingWorkingHoursStart

## 2.299 PidLidSharingWorkingHoursTimeZone

**Canonical name:** PidLidSharingWorkingHoursTimeZone

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A43

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:** dispidSharingWorkingHoursTZ

## 2.300 PidLidSideEffects

**Canonical name:** PidLidSideEffects

**Description:** Specifies how a Message object is handled by the client when acting on end-user input.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008510

**Data type:** PtypInteger32, 0x0003

**Area:** Run-time configuration

**Defining References:** [\[MS-OXCMSG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidSideEffects

### 2.301 PidLidSingleBodyICal

**Canonical name:** PidLidSingleBodyICal

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** IsSingleBodyICal, dispidIsSingleBodyICal

### 2.302 PidLidSingleInvite

**Canonical name:** PidLidSingleInvite

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000B

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_SINGLE\_INVITE

### 2.303 PidLidSmartNoAttach

**Canonical name:** PidLidSmartNoAttach

**Description:** Indicates whether the Message object has no end-user visible attachments.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}



**Property long ID (LID):** 0x00008514

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining References:** [\[MS-OXCMSG\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** dispidSmartNoAttach

### 2.304 PidLidSpamOriginalFolder

**Canonical name:** PidLidSpamOriginalFolder

**Description:** Specifies which folder a message was in before it was filtered into the Junk E-mail folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000859C

**Data type:** PtypBinary, 0x0102

**Area:** Spam

**Defining References:** [\[MS-OXCSPAM\]](#)

**Consuming References:**

**Alternate names:** dispidSpamOriginalFolder

### 2.305 PidLidStartRecurrenceDate

**Canonical name:** PidLidStartRecurrenceDate

**Description:** Identifies the start date of the recurrence pattern.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/start\\_recur\\_date](http://schemas.microsoft.com/mapi/start_recur_date)

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** LID\_START\_RECUR\_DATE

### 2.306 PidLidStartRecurrenceTime

**Canonical name:** PidLidStartRecurrenceTime

**Description:** Identifies the start time of the recurrence pattern.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000E

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/start\_recur\_time

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:**

**Alternate names:** LID\_START\_RECUR\_TIME

### 2.307 PidLidTaskAcceptanceState

**Canonical name:** PidLidTaskAcceptanceState

**Description:** Indicates the acceptance state of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812A

**Data type:** PtpInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskDelegValue

### 2.308 PidLidTaskAccepted

**Canonical name:** PidLidTaskAccepted

**Description:** Indicates whether a task assignee has replied to a task request for this Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008108

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXOSFLD\]](#)

**Alternate names:** dispidTaskAccepted

### 2.309 PidLidTaskActualEffort

**Canonical name:** PidLidTaskActualEffort

**Description:** Indicates the number of minutes that the user actually spent working on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008110

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskActualEffort

### 2.310 PidLidTaskAssigner

**Canonical name:** PidLidTaskAssigner

**Description:** Specifies the name of the user that last assigned the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008121

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskDelegator

### 2.311 PidLidTaskAssigners

**Canonical name:** PidLidTaskAssigners

**Description:** Contains a stack of entries, each representing a task assigner.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008117

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskMyDelegators

### 2.312 PidLidTaskComplete

**Canonical name:** PidLidTaskComplete

**Description:** Indicates that the task has been completed.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811C

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#)

**Alternate names:** dispidTaskComplete

### 2.313 PidLidTaskCustomFlags

**Canonical name:** PidLidTaskCustomFlags

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008139

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**References:** [\[MS-OXOTASK\]](#)

**Alternate names:** dispidTaskActualEffort

### 2.314 PidLidTaskDateCompleted

**Canonical name:** PidLidTaskDateCompleted

**Description:** Specifies the date when the user completed work on the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000810F

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#)

**Alternate names:** dispidTaskDateCompleted

### 2.315 PidLidTaskDeadOccurrence

**Canonical name:** PidLidTaskDeadOccurrence

**Description:** Indicates whether new occurrences remain to be generated.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008109

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskDeadOccur

### 2.316 PidLidTaskDueDate

**Canonical name:** PidLidTaskDueDate

**Description:** Specifies the date by which the user expects work on the task to be complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008105

**Data type:** PtpTime, 0x0040

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskDueDate

### 2.317 PidLidTaskEstimatedEffort

**Canonical name:** PidLidTaskEstimatedEffort

**Description:** Indicates the number of minutes that the user expects to work on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C00-000000000046}

**Property long ID (LID):** 0x00008111

**Data type:** PtpInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskEstimatedEffort

### 2.318 PidLidTaskFCreator

**Canonical name:** PidLidTaskFCreator

**Description:** Indicates that the Task object was originally created by the action of the current user or user agent instead of by the processing of a task request.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811E

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskFCreator

### 2.319 PidLidTaskFFixOffline

**Canonical name:** PidLidTaskFFixOffline

**Description:** Indicates the accuracy of PidLidTaskOwner.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812C

**Data type:** PtpBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskFFixOffline

### 2.320 PidLidTaskFRecurring

**Canonical name:** PidLidTaskFRecurring

**Description:** Indicates whether the task includes a recurrence pattern.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008126

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskFRecur

### 2.321 PidLidTaskGlobalId

**Canonical name:** PidLidTaskGlobalId

**Description:** Contains a unique GUID for this task, used to locate an existing task upon receipt of a task response or task update.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008519

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskGlobalObjId

### 2.322 PidLidTaskHistory

**Canonical name:** PidLidTaskHistory

**Description:** Indicates the type of change that was last made to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811A

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskHistory

### 2.323 PidLidTaskLastDelegate

**Canonical name:** PidLidTaskLastDelegate

**Description:** Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008125

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskLastDelegate

### 2.324 PidLidTaskLastUpdate

**Canonical name:** PidLidTaskLastUpdate

**Description:** Contains the date and time of the most recent change made to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008115

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskLastUpdate

### 2.325 PidLidTaskLastUser

**Canonical name:** PidLidTaskLastUser

**Description:** Contains the name of the most recent user to have been the task owner.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008122

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskLastUser

### 2.326 PidLidTaskMode

**Canonical name:** PidLidTaskMode

**Description:** Specifies the assignment status of the embedded Task object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008518

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks



**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidTaskMode

### 2.327 PidLidTaskMultipleRecipients

**Canonical name:** PidLidTaskMultipleRecipients

**Description:** Provides optimization hints about the recipients of a Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008120

**Data type:** PtpInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskMultRecips

### 2.328 PidLidTaskNoCompute

**Canonical name:** PidLidTaskNoCompute

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008124

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskNoCompute

### 2.329 PidLidTaskOrdinal

**Canonical name:** PidLidTaskOrdinal

**Description:** Provides an aid to custom sorting of Task objects.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008123

**Data type:** PtpInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskOrdinal

### 2.330 PidLidTaskOwner

**Canonical name:** PidLidTaskOwner

**Description:** Contains the name of the task owner.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811F

**Data type:** PtpString, 0x001F

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskOwner

### 2.331 PidLidTaskOwnership

**Canonical name:** PidLidTaskOwnership

**Description:** Indicates the role of the current user relative to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008129

**Data type:** PtpInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskOwnership

### 2.332 PidLidTaskRecurrence

**Canonical name:** PidLidTaskRecurrence

**Description:** Contains a RecurrencePattern structure that provides information about recurring tasks.

**Property set:** PSETID\_Task {0006203-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008116

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskRecur

### 2.333 PidLidTaskResetReminder

**Canonical name:** PidLidTaskResetReminder

**Description:** Indicates whether future instances of recurring tasks need reminders, even though PidLidReminderSet is 0x00.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008107

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskResetReminder

### 2.334 PidLidTaskRole

**Canonical name:** PidLidTaskRole

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008127

**Data type:** PtypString, 0x001F

**Area:** Tasks

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidTaskRole

### 2.335 PidLidTaskStartDate

**Canonical name:** PidLidTaskStartDate

**Description:** Specifies the date on which the user expects work on the task to begin.

**Property set:** PSETID\_Task {00062003-0000-0000-C00-000000000046}

**Property long ID (LID):** 0x00008104

**Data type:** PtpTime, 0x0040

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskStartDate

### 2.336 PidLidTaskState

**Canonical name:** PidLidTaskState

**Description:** Indicates the current assignment state of the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-00000000004}

**Property long ID (LID):** 0x00008113

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** dispidTaskState

### 2.337 PidLidTaskStatus

**Canonical name:** PidLidTaskStatus

**Description:** Specifies the status of a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008101

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** dispidTaskStatus

### 2.338 PidLidTaskStatusOnComplete

**Canonical name:** PidLidTaskStatusOnComplete

**Description:** Indicates whether the task assignee has been requested to send an e-mail message update when the task assignee completes the assigned task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008119

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskSOC

### 2.339 PidLidTaskUpdates

**Canonical name:** PidLidTaskUpdates

**Description:** Indicates whether the task assignee has been requested to send a task update when the assigned Task object changes.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811B

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:**

**Alternate names:** dispidTaskUpdates

### 2.340 PidLidTaskVersion

**Canonical name:** PidLidTaskVersion

**Description:** Indicates which copy is the latest update of a Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008112

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining References:** [\[MS-OXOTASK\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTaskVersion

### 2.341 PidLidTeamTask

**Canonical name:** PidLidTeamTask

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008103

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTeamTask

### 2.342 PidLidTimeZone

**Canonical name:** PidLidTimeZone

**Description:** Specifies information about the time zone of a recurring meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/time\\_zone](http://schemas.microsoft.com/mapi/time_zone)

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_TIME\_ZONE

### 2.343 PidLidTimeZoneDescription

**Canonical name:** PidLidTimeZoneDescription

**Description:** Specifies a human-readable description of the time zone that is represented by the data in the PidLidTimeZoneStruct property.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008234

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/timezonedesc>

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneDesc

### 2.344 PidLidTimeZoneStruct

**Canonical name:** PidLidTimeZoneStruct

**Description:** Specifies time zone information for a recurring meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008233

**Data type:** PtypBinary, 0x0102

**WebDAV:** http://schemas.microsoft.com/mapi/timezonestruct

**Area:** Calendar

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneStruct

### 2.345 PidLidToAttendeesString

**Canonical name:** PidLidToAttendeesString

**Description:** Contains a list of all the sendable attendees who are also required attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823B

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidToAttendeesString

### 2.346 PidLidToDoOrdinalDate

**Canonical name:** PidLidToDoOrdinalDate

**Description:** Contains the current time in UTC, used to determine the sort order of objects in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A0

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining References:** [\[MS-OXOFLAG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoOrdinalDate

### 2.347 PidLidToDoSubOrdinal

**Canonical name:** PidLidToDoSubOrdinal

**Description:** Contains numerals "0" through "9" that are used to break a tie when PidLidToDoOrdinalDate is used to perform a sort of objects.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A1

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining References:** [\[MS-OXOFLAG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoSubOrdinal

### 2.348 PidLidToDoTitle

**Canonical name:** PidLidToDoTitle

**Description:** Contains user-specifiable text to identify this Message object in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A4

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining References:** [\[MS-OXOFLAG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidToDoTitle

### 2.349 PidLidTrustRecipientHighlights

**Canonical name:** PidLidTrustRecipientHighlights

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823E

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** dispidTrustRecipHighlights

### 2.350 PidLidUseTnef

**Canonical name:** PidLidUseTnef



**Description:** Specifies whether Transport Neutral Encapsulation Format (TNEF) is to be included on a message when the message is converted from TNEF to MIME or SMTP format.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008582

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining References:** [\[MS-OXOMSG\]](#)

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidUseTNEF

### 2.351 PidLidValidFlagStringProof

**Canonical name:** PidLidValidFlagStringProof

**Description:** Contains the value of PidTagMessageDeliveryTime when modifying PidLidFlagRequest.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BF

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining References:** [\[MS-OXOFLAG\]](#)

**Consuming References:** [\[MS-OXODOC\]](#)

**Alternate names:** dispidValidFlagStringProof

### 2.352 PidLidVerbResponse

**Canonical name:** PidLidVerbResponse

**Description:** Specifies the voting option that a respondent has selected.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008524

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining References:** [\[MS-OXOMSG\]](#)

**Consuming References:**

**Alternate names:** dispidVerbResponse

### 2.353 PidLidVerbStream

**Canonical name:** PidLidVerbStream

**Description:** Specifies what voting responses the user can make in response to the message.

**Property set:** PSETID\_Common {00062008-0000-000-C000-000000000046}

**Property long ID (LID):** 0x00008520

**Data type:** typBinary, 0x0102

**Area:** Run-time configuration

**Defining References:** [\[MS-OXOMSG\]](#)

**Consuming References:**

**Alternate names:** dispidVerbStream

### 2.354 PidLidWeddingAnniversaryLocal

**Canonical name:** PidLidWeddingAnniversaryLocal

**Description:** Specifies the wedding anniversary of the contact, at 0:00 in the client's local time zone and it is saved without any time zone conversions.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DF

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidApptAnniversaryLocal

### 2.355 PidLidWeekInterval

**Canonical name:** PidLidWeekInterval

**Description:** Identifies the number of weeks that occur between each meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00A003F1305}

**Property long ID (LID):** 0x00000012

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/week\\_interval](http://schemas.microsoft.com/mapi/week_interval)

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_WEEK\_INTERVAL

### 2.356 PidLidWhere

**Canonical name:** PidLidWhere

**Description:** Contains the value of the PidLidLocation property from the associated Meeting object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000002

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/where

**Area:** Meetings

**Defining References:** [\[MS-OXOCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_WHERE

### 2.357 PidLidWorkAddress

**Canonical name:** PidLidWorkAddress

**Description:** Specifies the complete address of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-00000000046}

**Property long ID (LID):** 0x0000801B

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:workaddress

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidWorkAddress

### 2.358 PidLidWorkAddressCity

**Canonical name:** PidLidWorkAddressCity

**Description:** Specifies the city or locality portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-00000000046}

**Property long ID (LID):** 0x00008046

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:l

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidWorkAddressCity

### 2.359 PidLidWorkAddressCountry

**Canonical name:** PidLidWorkAddressCountry

**Description:** Specifies the country or region portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008049

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:co

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidWorkAddressCountry

### 2.360 PidLidWorkAddressCountryCode

**Canonical name:** PidLidWorkAddressCountryCode

**Description:** Specifies the country code portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DB

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:**

**Alternate names:** dispidWorkAddressCountryCode

### 2.361 PidLidWorkAddressPostalCode

**Canonical name:** PidLidWorkAddressPostalCode

**Description:** Specifies the postal code (ZIP code) portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-000-C000-000000000046}

**Property long ID (LID):** 0x00008048

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postalcode

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidWorkAddressPostalCode

### 2.362 PidLidWorkAddressPostOfficeBox

**Canonical name:** PidLidWorkAddressPostOfficeBox

**Description:** Specifies the post office box portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C00-000000000046}

**Property long ID (LID):** 0x0000804A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postofficebox

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidWorkAddressPostOfficeBox

### 2.363 PidLidWorkAddressState

**Canonical name:** PidLidWorkAddressState

**Description:** Specifies the state or province portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008047

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:st

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#)

**Alternate names:** dispidWorkAddressState

## 2.364 PidLidWorkAddressStreet

**Canonical name:** PidLidWorkAddressStreet

**Description:** Specifies the street portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-00000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:street

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** dispidWorkAddressStreet

## 2.365 PidLidYearInterval

**Canonical name:** PidLidYearInterval

**Description:** Indicates the yearly interval of the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA00F1305}

**Property long ID (LID):** 0x00000014

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/year\_interval

**Area:** Meetings

**Defining References:** [\[MS-XWDCAL\]](#)

**Consuming References:** [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_YEAR\_INTERVAL

## 2.366 PidLidYomiCompanyName

**Canonical name:** PidLidYomiCompanyName

**Description:** Specifies the phonetic pronunciation of the contact's company name.

**Property set:** PSETID\_Address {00062004-0000-0000-C00000000000046}

**Property long ID (LID):** 0x0000802E

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/yomiorganization

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDEXT\]](#)

**Alternate names:** dispidYomiCompanyName

### 2.367 PidLidYomiFirstName

**Canonical name:** PidLidYomiFirstName

**Description:** Specifies the phonetic pronunciation of the contact's given name.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802C

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/yomifirstname>

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDEXT\]](#)

**Alternate names:** dispidYomiFirstName

### 2.368 PidLidYomiLastName

**Canonical name:** PidLidYomiLastName

**Description:** Specifies the phonetic pronunciation of the contact's surname.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802D

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/yomilastname>

**Area:** Contact Properties

**Defining References:** [\[MS-OXOCNTC\]](#)

**Consuming References:** [\[MS-XWDEXT\]](#)

**Alternate names:** dispidYomiLastName

### 2.369 PidNameAcceptLanguage

**Canonical name:** PidNameAcceptLanguage

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Accept-Language

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** AcceptLanguage

### 2.370 PidNameApplicationName

**Canonical name:** PidNameApplicationName

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** AppName

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#NameOfApplication

### 2.371 PidNameApproved

**Canonical name:** PidNameApproved

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Approved

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:approved

### 2.372 PidNameApprovalAllowedDecisionMakers

**Canonical name:** PidNameApprovalAllowedDecisionMakers

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-Approval-Allowed-Decision-Makers

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMSExchangeOrganizationDecisionMakers

### 2.373 PidNameApprovalRequestor

**Canonical name:** PidNameApprovalRequestor



**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-Approval-Requestor

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMSEExchangeOrganizationApprovalRequestor

### 2.374 PidNameAttachmentMacContentType

**Canonical name:** PidNameAttachmentMacContentType

**Property set:** PSETID\_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

**Property name:** AttachmentMacContentType

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

### 2.375 PidNameAttachmentMacInfo

**Canonical name:** PidNameAttachmentMacInfo

**Property set:** PSETID\_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

**Property name:** AttachmentMacInfo

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

### 2.376 PidNameAudioNotes

**Canonical name:** PidNameAudioNotes

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** UMAudioNotes

**Data type:** PtypString, 0x001F

**Area:** UM

**References:** [\[MS-OXOUM\]](#)

**Alternate names:** UMAudioNotes

## 2.377 PidNameAuthor

**Canonical name:** PidNameAuthor

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Author

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Authorurn:schemas-microsoft-com:office:office#Author

## 2.378 PidNameAuthenticatedAs

**Canonical name:** PidNameAuthenticatedAs

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-AuthAs

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchOrganizationAuthAs

## 2.379 PidNameAuthenticatedDomain

**Canonical name:** PidNameAuthenticatedDomain

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-AuthDomain

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchOrganizationAuthDomain

## 2.380 PidNameAuthenticatedMechanism

**Canonical name:** PidNameAuthenticatedMechanism

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-AuthMechanism

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchOrganizationAuthMechanism

### 2.381 PidNameAuthenticatedSource

**Canonical name:** PidNameAuthenticatedSource

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-AuthSource

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchOrganizationAuthSource

### 2.382 PidNameAutomaticSpeechRecognitionData

**Canonical name:** PidNameAutomaticSpeechRecognitionData

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** AsrData

**Data type:** PtypBinary, 0x0102

**Area:** UM

**References:** [\[MS-OXOUM\]](#)

**Alternate names:**

### 2.383 PidNameBcc

**Canonical name:** PidNameBcc

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Bcc

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:bcc

### 2.384 PidNameByteCount

**Canonical name:** PidNameByteCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ByteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Bytesurn:schemas-microsoft-com:office:office#Bytes

### 2.385 PidNameCalendarAttendeeRole

**Canonical name:** PidNameCalendarAttendeeRole

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:attendeerole

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:calendar:attendeerole

### 2.386 PidNameCalendarBusystatus

**Canonical name:** PidNameCalendarBusystatus

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:busystatus

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:busystatus

### 2.387 PidNameCalendarContact

**Canonical name:** PidNameCalendarContact

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contact

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:contact

### 2.388 PidNameCalendarContactUrl

**Canonical name:** PidNameCalendarContactUrl

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contacturl

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:contacturl

### 2.389 PidNameCalendarCreated

**Canonical name:** PidNameCalendarCreated

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:created

**Data type:** PtypTime, 0x0040

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:created

### 2.390 PidNameCalendarDescriptionUrl

**Canonical name:** PidNameCalendarDescriptionUrl

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:descriptionurl

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:descriptionurl

### 2.391 PidNameCalendarDuration

**Canonical name:** PidNameCalendarDuration

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:duration

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:duration

### 2.392 PidNameCalendarExceptionDate

**Canonical name:** PidNameCalendarExceptionDate

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:exdate

### 2.393 PidNameCalendarExceptionRule

**Canonical name:** PidNameCalendarExceptionRule

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:exrule

### 2.394 PidNameCalendarGeoLatitude

**Canonical name:** PidNameCalendarGeoLatitude

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolatitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:geolatitude

### 2.395 PidNameCalendarGeoLongitude

**Canonical name:** PidNameCalendarGeoLongitude

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolongitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:geolongitude

### 2.396 PidNameCalendarInstanceType

**Canonical name:** PidNameCalendarInstanceType

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:instancetype

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:instancetype

### 2.397 PidNameCalendarIsOrganizer

**Canonical name:** PidNameCalendarIsOrganizer

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:isorganizer

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:calendar:isorganizer

### 2.398 PidNameCalendarLastModified

**Canonical name:** PidNameCalendarLastModified

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:lastmodified

**Data type:** PtypTime, 0x0040

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:lastmodified

### 2.399 PidNameCalendarLocationUrl

**Canonical name:** PidNameCalendarLocationUrl

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:locationurl

### 2.400 PidNameCalendarMeetingStatus

**Canonical name:** PidNameCalendarMeetingStatus

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:meetingstatus

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:meetingstatus

### 2.401 PidNameCalendarMethod

**Canonical name:** PidNameCalendarMethod

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:method

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:method

### 2.402 PidNameCalendarProductId

**Canonical name:** PidNameCalendarProductId



**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:prodid

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:calendar:prodid

#### 2.403 PidNameCalendarRecurrenceIdRange

**Canonical name:** PidNameCalendarRecurrenceIdRange

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:recurrenceidrange

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:recurrenceidrange

#### 2.404 PidNameCalendarReminderOffset

**Canonical name:** PidNameCalendarReminderOffset

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:reminderoffset

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:reminderoffset

#### 2.405 PidNameCalendarResources

**Canonical name:** PidNameCalendarResources

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:resources

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDVSEC\]](#)

**Alternate names:** urn:schemas:calendar:resources

## 2.406 PidNameCalendarRsvp

**Canonical name:** PidNameCalendarRsvp

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rsvp

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:calendar:rsvp

## 2.407 PidNameCalendarSequence

**Canonical name:** PidNameCalendarSequence

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:sequence

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:sequence

## 2.408 PidNameCalendarTimeZone

**Canonical name:** PidNameCalendarTimeZone

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezone

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:timezone

## 2.409 PidNameCalendarTimeZoneId

**Canonical name:** PidNameCalendarTimeZoneId

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezoneid

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:timezoneid

#### 2.410 PidNameCalendarTransparent

**Canonical name:** PidNameCalendarTransparent

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:transparent

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:transparent

#### 2.411 PidNameCalendarUid

**Canonical name:** PidNameCalendarUid

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:uid

#### 2.412 PidNameCalendarVersion

**Canonical name:** PidNameCalendarVersion

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:version

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:calendar:version

#### 2.413 PidNameCategory

**Canonical name:** PidNameCategory

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Category

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Category

#### 2.414 PidNameCc

**Canonical name:** PidNameCc

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Cc

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDTEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:cc

#### 2.415 PidNameCharacterCount

**Canonical name:** PidNameCharacterCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CharCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Characters

#### 2.416 PidNameComments

**Canonical name:** PidNameComments

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Comments

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Comments

## 2.417 PidNameCompany

**Canonical name:** PidNameCompany

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Company

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Company

## 2.418 PidNameContactsAlternateRecipient

**Canonical name:** PidNameContactsAlternateRecipient

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:alternaterecipient

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#)

**Alternate names:** urn:schemas:contacts:alternaterecipient

## 2.419 PidNameContactsCountry

**Canonical name:** PidNameContactsCountry

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:c

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXI\]](#)

**Alternate names:** urn:schemas:contacts:c

## 2.420 PidNameContactsEmail1

**Canonical name:** PidNameContactsEmail1

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:email1

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:email1

#### 2.421 PidNameContactsEmail2

**Canonical name:** PidNameContactsEmail2

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:email2

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:email2

#### 2.422 PidNameContactsEmail3

**Canonical name:** PidNameContactsEmail3

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:email3

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:email3

#### 2.423 PidNameContactsFileAs

**Canonical name:** PidNameContactsFileAs

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:fileas

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#)

**Alternate names:** urn:schemas:contacts:fileas

#### 2.424 PidNameContactsFileasId

**Canonical name:** PidNameContactsFileasId

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:fileasid

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:fileasid

#### 2.425 PidNameContactsHomeLatitude

**Canonical name:** PidNameContactsHomeLatitude

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:homelatitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:homelatitude

#### 2.426 PidNameContactsHomeLongitude

**Canonical name:** PidNameContactsHomeLongitude

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:homelongitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:homelongitude

#### 2.427 PidNameContactsHomeTimeZone

**Canonical name:** PidNameContactsHomeTimeZone

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:hometimezone

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:hometimezone

## 2.428 PidNameContactsMapUrl

**Canonical name:** PidNameContactsMapUrl

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:mapurl

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:mapurl

## 2.429 PidNameContactsOtherCountryCode

**Canonical name:** PidNameContactsOtherCountryCode

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:othercountrycode

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:othercountrycode

## 2.430 PidNameContactsOtherPager

**Canonical name:** PidNameContactsOtherPager

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:otherpager

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:otherpager

## 2.431 PidNameContactsOtherTimeZone

**Canonical name:** PidNameContactsOtherTimeZone

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:othertimezone

**Data type:** PtypString, 0x001F



**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:othertimezone

### 2.432 PidNameContactsProxyAddresses

**Canonical name:** PidNameContactsProxyAddresses

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:proxyaddresses

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:proxyaddresses

### 2.433 PidNameContactsSecretaryUrl

**Canonical name:** PidNameContactsSecretaryUrl

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:secretaryurl

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:secretaryurl

### 2.434 PidNameContactsSourceUrl

**Canonical name:** PidNameContactsSourceUrl

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:contacts:sourceurl

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:contacts:sourceurl

### 2.435 PidNameContentBase

**Canonical name:** PidNameContentBase

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Base

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** BodyContentBase

## 2.436 PidNameContentClass

**Canonical name:** PidNameContentClass

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Class

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDSTRUCTDOC\]](#)

**Alternate names:** DAV:contentclassDAV:contentclass, urn:schemas:mailheader:content-class

## 2.437 PidNameContentDisposition

**Canonical name:** PidNameContentDisposition

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Disposition

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:content-disposition

## 2.438 PidNameContentID

**Canonical name:** PidNameContentID

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-ID

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:content-id

#### 2.439 PidNameContentLanguage

**Canonical name:** PidNameContentLanguage

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Language

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:content-language

#### 2.440 PidNameContentLocation

**Canonical name:** PidNameContentLocation

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Location

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:content-location

#### 2.441 PidNameContentTransferEncoding

**Canonical name:** PidNameContentTransferEncoding

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Transfer-Encoding

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-OXCICAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:content-transfer-encoding

#### 2.442 PidNameContentType

**Canonical name:** PidNameContentType

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Type

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:content-type

#### 2.443 PidNameControl

**Canonical name:** PidNameControl

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Control

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:control

#### 2.444 PidNameCreateDateTimeReadOnly

**Canonical name:** PidNameCreateDateTimeReadOnly

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CreateDtmRo

**Data type:** PtypTime, 0x0040

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Created

#### 2.445 PidNameCrossReference

**Canonical name:** PidNameCrossReference

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Xref

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-OXCMAIL\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:xref

## 2.446 PidNameDavGetContentType

**Canonical name:** PidNameDavGetContentType

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:getcontenttype

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:**

## 2.447 PidNameDavId

**Canonical name:** PidNameDavId

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:id

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** DAV:id

## 2.448 PidNameDavIsCollection

**Canonical name:** PidNameDavIsCollection

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:iscollection

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** DAV:iscollection

## 2.449 PidNameDavIsStructuredDocument

**Canonical name:** PidNameDavIsStructuredDocument

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:isstructureddocument

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** DAV:isstructureddocument

## 2.450 PidNameDavParentName

**Canonical name:** PidNameDavParentName

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:parentname

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** DAV:parentname

## 2.451 PidNameDavResourceType

**Canonical name:** PidNameDavResourceType

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:resourcetype

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#), [\[MS-XWDSTRUCTDOC\]](#)

**Alternate names:** DAV:resourcetype

## 2.452 PidNameDavSearchRequest

**Canonical name:** PidNameDavSearchRequest

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:searchrequest

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#)

**Alternate names:** DAV:searchrequest

## 2.453 PidNameDavSearchType

**Canonical name:** PidNameDavSearchType

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:searchtype

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDSEARCH\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** DAV:searchtype

#### 2.454 PidNameDavUid

**Canonical name:** PidNameDavUid

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** DAV:uid

#### 2.455 PidNameDisposition

**Canonical name:** PidNameDisposition

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Disposition

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:disposition

#### 2.456 PidNameDispositionNotificationTo

**Canonical name:** PidNameDispositionNotificationTo

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Disposition-Notification-To

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:disposition-notification-to

## 2.457 PidNameDistribution

**Canonical name:** PidNameDistribution

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Distribution

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:distribution

## 2.458 PidNameDocumentParts

**Canonical name:** PidNameDocumentParts

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DocParts

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#PartTitles

## 2.459 PidNameEditTime

**Canonical name:** PidNameEditTime

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** EditTime

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#TotalTime

## 2.460 PidNameExchangeIntendedBusyStatus

**Canonical name:** PidNameExchangeIntendedBusyStatus

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/intendedbusystatus

**Data type:** PtypString, 0x001F



**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** <http://schemas.microsoft.com/exchange/intendedbusystatus>

## 2.461 PidNameExchangeJunkEmailMoveStamp

**Canonical name:** PidNameExchangeJunkEmailMoveStamp

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** <http://schemas.microsoft.com/exchange/junkemailmovestamp>

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORSS\]](#)

**Alternate names:** <http://schemas.microsoft.com/exchange/junkemailmovestamp>

## 2.462 PidNameExchangeModifyExceptionStructure

**Canonical name:** PidNameExchangeModifyExceptionStructure

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** <http://schemas.microsoft.com/exchange/modifyexceptionstruct>

**Data type:** PtypBinary, 0x0102

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** <http://schemas.microsoft.com/exchange/modifyexceptionstruct>

## 2.463 PidNameExchangeMsexchembdefaultmailfolder

**Canonical name:** PidNameExchangeMsexchembdefaultmailfolder

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** <http://schemas.microsoft.com/exchange/msexchembdefaultmailfolder>

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDFOLD\]](#)

**Alternate names:** <http://schemas.microsoft.com/exchange/msexchembdefaultmailfolder>

## 2.464 PidNameExchangeMsexchembdefaultmailfoldertype

**Canonical name:** PidNameExchangeMsexchembdefaultmailfoldertype

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/msexchembdefaultmailfoldertype

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDFOLD\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/msexchembdefaultmailfoldertype

## 2.465 PidNameExchangeNoModifyExceptions

**Canonical name:** PidNameExchangeNoModifyExceptions

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/nomodifyexceptions

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/nomodifyexceptions

## 2.466 PidNameExchangePatternEnd

**Canonical name:** PidNameExchangePatternEnd

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/patternend

**Data type:** PtypTime, 0x0040

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/pattemend

## 2.467 PidNameExchangePatternStart

**Canonical name:** PidNameExchangePatternStart

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/patternstart

**Data type:** PtypTime, 0x0040

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/pattemstart

## 2.468 PidNameExchangePublicFolderEmailAddress

**Canonical name:** PidNameExchangePublicFolderEmailAddress

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/publicfolderemailaddress

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/publicfolderemailaddress

## 2.469 PidNameExchangeReminderInterval

**Canonical name:** PidNameExchangeReminderInterval

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/reminderinterval

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/reminderinterval

## 2.470 PidNameExchDatabaseSchema

**Canonical name:** PidNameExchDatabaseSchema

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:baseschema

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas-microsoft-com:exch-data:baseschema

## 2.471 PidNameExchDataExpectedContentClass

**Canonical name:** PidNameExchDataExpectedContentClass

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:expected-content-class

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#)

**Alternate names:** urn:schemas-microsoft-com:exch-data:expected-content-class

## 2.472 PidNameExchDataSchemaCollectionReference

**Canonical name:** PidNameExchDataSchemaCollectionReference

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

## 2.473 PidNameExpires

**Canonical name:** PidNameExpires

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Expires

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:expires

## 2.474 PidNameExpiryDate

**Canonical name:** PidNameExpiryDate

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Expiry-Date

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:expiry-date

## 2.475 PidNameFollowupTo

**Canonical name:** PidNameFollowupTo

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Followup-To

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:followup-to

#### 2.476 PidNameFrom

**Canonical name:** PidNameFrom

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** From

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:calendar:organizer

#### 2.477 PidNameHeadingPairs

**Canonical name:** PidNameHeadingPairs

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HeadingPairs

**Data type:** PtypBinary, 0x0102

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#HeadingPairs

#### 2.478 PidNameHiddenCount

**Canonical name:** PidNameHiddenCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HiddenCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#HiddenSlides

## 2.479 PidNameHttpmailCalendar

**Canonical name:** PidNameHttpmailCalendar

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:calendar

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:httpmail:calendar

## 2.480 PidNameHttpmailCc

**Canonical name:** PidNameHttpmailCc

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:cc

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:httpmail:cc

## 2.481 PidNameHttpmailContacts

**Canonical name:** PidNameHttpmailContacts

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:contacts

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDCNTC\]](#)

**Alternate names:** urn:schemas:httpmail:contacts

## 2.482 PidNameHttpmailContentMediaType

**Canonical name:** PidNameHttpmailContentMediaType

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:content-media-type

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:httpmail:content-media-type

### 2.483 PidNameHttpmailFrom

**Canonical name:** PidNameHttpmailFrom

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:from

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:httpmail:from

### 2.484 PidNameHttpmailFromEmail

**Canonical name:** PidNameHttpmailFromEmail

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:fromemail

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:httpmail:fromemail

### 2.485 PidNameHttpmailHtmlDescription

**Canonical name:** PidNameHttpmailHtmlDescription

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:htmldescription

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:httpmail:htmldescription

### 2.486 PidNameHttpmailOutbox

**Canonical name:** PidNameHttpmailOutbox

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:outbox

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:httpmail:outbox

## 2.487 PidNameHttpmailSendMessage

**Canonical name:** PidNameHttpmailSendMessage

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:sendmsg

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:httpmail:sendmsg

## 2.488 PidNameHttpmailSubmitted

**Canonical name:** PidNameHttpmailSubmitted

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:submitted

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:httpmail:submitted

## 2.489 PidNameHttpmailTo

**Canonical name:** PidNameHttpmailTo

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:to

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:httpmail:to



## 2.490 PidNameICalendarRecurrenceDate

**Canonical name:** PidNameICalendarRecurrenceDate

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:calendar:rdate

## 2.491 PidNameICalendarRecurrenceRule

**Canonical name:** PidNameICalendarRecurrenceRule

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:rrule

## 2.492 PidNameImportance

**Canonical name:** PidNameImportance

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Importance

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:importance

## 2.493 PidNameInReplyTo

**Canonical name:** PidNameInReplyTo

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** In-Reply-To

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:in-reply-to

#### 2.494 PidNameInstantMessagingAddress2

**Canonical name:** PidNameInstantMessagingAddress2

**Property set:** PSETID\_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}

**Property name:** IMAddress2

**Data type:** PtypString, 0x001F

**Area:** Sync

**References:** [\[MS-OXVCARD\]](#)

**Alternate names:** IMAddress2

#### 2.495 PidNameInstantMessagingAddress3

**Canonical name:** PidNameInstantMessagingAddress3

**Property set:** PSETID\_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}

**Property name:** IMAddress3

**Data type:** PtypString, 0x001F

**Area:** Sync

**References:** [\[MS-OXVCARD\]](#)

**Alternate names:** IMAddress3

#### 2.496 PidNameInternetComment

**Canonical name:** PidNameInternetComment

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Comment

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:comment

#### 2.497 PidNameInternetKeywords

**Canonical name:** PidNameInternetKeywords

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Keywords

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:keywords

## 2.498 PidNameInternetSubject

**Canonical name:** PidNameInternetSubject

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:subject

## 2.499 PidNameKeywords

**Canonical name:** PidNameKeywords

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Keywords

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Keywords, <http://schemas.microsoft.com/exchange/keywords-utf8>

## 2.500 PidNameLastAuthor

**Canonical name:** PidNameLastAuthor

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastAuthor

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#LastAuthor

### 2.501 PidNameLastPrinted

**Canonical name:** PidNameLastPrinted

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastPrinted

**Data type:** PtypTime, 0x0040

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#LastPrinted

### 2.502 PidNameLastSaveDateTime

**Canonical name:** PidNameLastSaveDateTime

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastSaveDtm

**Data type:** PtypTime, 0x0040

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#LastSaved

### 2.503 PidNameLineCount

**Canonical name:** PidNameLineCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LineCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Lines

### 2.504 PidNameLines

**Canonical name:** PidNameLines

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Lines

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:lines

## 2.505 PidNameLinksDirty

**Canonical name:** PidNameLinksDirty

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LinksDirty

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#LinksUpToDate

## 2.506 PidNameLocationUrl

**Canonical name:** PidNameLocationUrl

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Calendar

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:calendar:locationurl, LocationUrl

## 2.507 PidNameMailSubmissionUri

**Canonical name:** PidNameMailSubmissionUri

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** MAIL:submissionuri

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:** MAIL:submissionuri

## 2.508 PidNameManager

**Canonical name:** PidNameManager

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Manager

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Manager

## 2.509 PidNameMessageId

**Canonical name:** PidNameMessageId

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Message-ID

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:message-id

## 2.510 PidNameMimeVersion

**Canonical name:** PidNameMimeVersion

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Mime-Version

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:mime-version

## 2.511 PidNameMultimediaClipCount

**Canonical name:** PidNameMultimediaClipCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** MMClipCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#MultimediaClips

## 2.512 PidNameNewsgroups

**Canonical name:** PidNameNewsgroups

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Newsgroups

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:newsgroups

## 2.513 PidNameNntpPostingHost

**Canonical name:** PidNameNntpPostingHost

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** NNTP-Posting-Host

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:nntp-posting-host

## 2.514 PidNameNoteCount

**Canonical name:** PidNameNoteCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** NoteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Notes

## 2.515 PidNameOMSAccountGuid

**Canonical name:** PidNameOMSAccountGuid

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSAccountGuid

**Data type:** PtypString, 0x001F

**Area:** SMS

**References:** [\[MS-OXOSMMS\]](#)

**Alternate names:**

## 2.516 PidNameOMSMobileModel

**Canonical name:** PidNameOMSMobileModel

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSMobileModel

**Data type:** PtypString, 0x001F

**Area:** SMS

**References:** [\[MS-OXOSMMS\]](#)

**Alternate names:**

## 2.517 PidNameOMSScheduleTime

**Canonical name:** PidNameOMSScheduleTime

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSScheduleTime

**Data type:** PtypTime, 0x0040

**Area:** SMS

**References:** [\[MS-OXOSMMS\]](#)

**Alternate names:**

## 2.518 PidNameOMSServiceType

**Canonical name:** PidNameOMSServiceType

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSServiceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**References:** [\[MS-OXOSMMS\]](#)

**Alternate names:**



## 2.519 PidNameOMSSourceType

**Canonical name:** PidNameOMSSourceType

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSSourceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**References:** [\[MS-OXOSMMS\]](#)

**Alternate names:**

## 2.520 PidNameOrganization

**Canonical name:** PidNameOrganization

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Organization

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:organization

## 2.521 PidNameOriginalRecipient

**Canonical name:** PidNameOriginalRecipient

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Original-Recipient

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:original-recipient

## 2.522 PidNameOriginalSpamConfidenceLevel

**Canonical name:** PidNameOriginalSpamConfidenceLevel

**Property set:** PSETID\_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B-0BFF}

**Property name:** OriginalScl

**Data type:** PtypInteger32, 0x0003

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** OriginalSci

### 2.523 PidNameOutlookProtectionRuleOverridden

**Canonical name:** PidNameOutlookProtectionRuleOverridden

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-Outlook-Protection-Rule-Overridden

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMSEExchangeOutlookProtectionRuleOverridden

### 2.524 PidNameOutlookProtectionRuleTimestamp

**Canonical name:** PidNameOutlookProtectionRuleTimestamp

**Property set:**

**Property name:** X-MS-Exchange-Organization-Outlook-Protection-Rule-Config-Timestamp

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMSEExchangeOutlookProtectionRuleConfigTimestamp

### 2.525 PidNameOutlookProtectionRuleVersion

**Canonical name:** PidNameOutlookProtectionRuleVersion

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-Outlook-Protection-Rule-Addin-Version

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMSEExchangeOutlookProtectionRuleVersion

### 2.526 PidNamePageCount

**Canonical name:** PidNamePageCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PageCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Pages

## 2.527 PidNameParagraphCount

**Canonical name:** PidNameParagraphCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ParCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Paragraphs

## 2.528 PidNamePath

**Canonical name:** PidNamePath

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Path

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:path

## 2.529 PidNamePhishingStamp

**Canonical name:** PidNamePhishingStamp

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/outlook/phishingstamp

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**References:** [\[MS-OXPHISH\]](#)

**Alternate names:**

## 2.530 PidNamePostingVersion

**Canonical name:** PidNamePostingVersion

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Posting-Version

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:posting-version

## 2.531 PidNamePresentationFormat

**Canonical name:** PidNamePresentationFormat

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PresFormat

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#PresentationFormat

## 2.532 PidNamePriority

**Canonical name:** PidNamePriority

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Priority

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:priority

## 2.533 PidNameQuarantineOriginalSender

**Canonical name:** PidNameQuarantineOriginalSender

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** quarantine-original-sender

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.534 PidNameReceived

**Canonical name:** PidNameReceived

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Received

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:received

## 2.535 PidNameReferences

**Canonical name:** PidNameReferences

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** References

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:references

## 2.536 PidNameRelayVersion

**Canonical name:** PidNameRelayVersion

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Relay-Version

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:relay-version

## 2.537 PidNameReplyBy

**Canonical name:** PidNameReplyBy

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Reply-By

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:reply-by

## 2.538 PidNameReplyTo

**Canonical name:** PidNameReplyTo

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Reply-To

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:reply-to

## 2.539 PidNameReturnPath

**Canonical name:** PidNameReturnPath

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Return-Path

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:return-path

## 2.540 PidNameReturnReceiptTo

**Canonical name:** PidNameReturnReceiptTo

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Return-Receipt-To

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:return-receipt-to

### 2.541 PidNameRevisionNumber

**Canonical name:** PidNameRevisionNumber

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** RevNumber

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Revision

### 2.542 PidNameRightsManagementLicense

**Canonical name:** PidNameRightsManagementLicense

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DRMLicense

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Secure Messaging Properties

**References:** [\[MS-OXORMMS\]](#)

**Alternate names:**

### 2.543 PidNameRightsProtectMessage

**Canonical name:** PidNameRightsProtectMessage

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-MS-Exchange-Organization-RightsProtectMessage

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchangeOrganizationRightsProtectMessage

### 2.544 PidNameScale

**Canonical name:** PidNameScale

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Scale

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#ScaleCrop

## 2.545 PidNameSecurity

**Canonical name:** PidNameSecurity

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Security

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Security

## 2.546 PidNameSender

**Canonical name:** PidNameSender

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Sender

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:sender

## 2.547 PidNameSensitivity

**Canonical name:** PidNameSensitivity

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Sensitivity

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:sensitivity

## 2.548 PidNameSlideCount

**Canonical name:** PidNameSlideCount



**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** SlideCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Slides

## 2.549 PidNameSubject

**Canonical name:** PidNameSubject

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Subject

## 2.550 PidNameSummary

**Canonical name:** PidNameSummary

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Summary

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:summary

## 2.551 PidNameTemplate

**Canonical name:** PidNameTemplate

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Template

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Template

## 2.552 PidNameThreadIndex

**Canonical name:** PidNameThreadIndex

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Thread-Index

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:thread-index

## 2.553 PidNameThreadTopic

**Canonical name:** PidNameThreadTopic

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Thread-Topic

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:thread-topic

## 2.554 PidNameThumbnail

**Canonical name:** PidNameThumbnail

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Thumbnail

**Data type:** PtypBinary, 0x0102

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#ThumbNail

## 2.555 PidNameTitle

**Canonical name:** PidNameTitle

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Title

**Data type:** PtypString, 0x001F

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Title

## 2.556 PidNameTo

**Canonical name:** PidNameTo

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** To

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:to

## 2.557 PidNameWordCount

**Canonical name:** PidNameWordCount

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** WordCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Words

## 2.558 PidNameXCallId

**Canonical name:** PidNameXCallId

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallID

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.559 PidNameXFaxNumberOfPages

**Canonical name:** PidNameXFaxNumberOfPages

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-FaxNumberOfPages

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.560 PidNameXMailer

**Canonical name:** PidNameXMailer

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Mailer

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:x-mailer

## 2.561 PidNameXMessageCompleted

**Canonical name:** PidNameXMessageCompleted

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Message-Completed

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:x-message-completed

## 2.562 PidNameXMessageFlag

**Canonical name:** PidNameXMessageFlag

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Message-Flag

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:x-message-flag

## 2.563 PidNameXRequireProtectedPlayOnPhone

**Canonical name:** PidNameXRequireProtectedPlayOnPhone

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-RequireProtectedPlayOnPhone

**Data type:** PtypBoolean, 0x000B

**Area:** UM

**References:** [\[MS-OXOUM\]](#)

**Alternate names:**

## 2.564 PidNameXSenderTelephoneNumber

**Canonical name:** PidNameXSenderTelephoneNumber

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallingTelephoneNumber

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.565 PidNameXSharingBrowseUrl

**Canonical name:** PidNameXSharingBrowseUrl

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Browse-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.566 PidNameXSharingCapabilities

**Canonical name:** PidNameXSharingCapabilities

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Capabilities

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.567 PidNameXSharingConfigUrl

**Canonical name:** PidNameXSharingConfigUrl

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Config-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.568 PidNameXSharingExendedCaps

**Canonical name:** PidNameXSharingExendedCaps

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Exended-Caps

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.569 PidNameXSharingFlavor

**Canonical name:** PidNameXSharingFlavor

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Flavor

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.570 PidNameXSharingInstanceGuid

**Canonical name:** PidNameXSharingInstanceGuid

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Instance-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

### 2.571 PidNameXSharingLocalType

**Canonical name:** PidNameXSharingLocalType

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Local-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

### 2.572 PidNameXSharingProviderGuid

**Canonical name:** PidNameXSharingProviderGuid

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

### 2.573 PidNameXSharingProviderName

**Canonical name:** PidNameXSharingProviderName

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.574 PidNameXSharingProviderUrl

**Canonical name:** PidNameXSharingProviderUrl

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.575 PidNameXSharingRemoteName

**Canonical name:** PidNameXSharingRemoteName

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.576 PidNameXSharingRemotePath

**Canonical name:** PidNameXSharingRemotePath

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Path

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.577 PidNameXSharingRemoteStoreUid

**Canonical name:** PidNameXSharingRemoteStoreUid

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Store-Uid

**Data type:** PtypString, 0x001F



**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.578 PidNameXSharingRemoteType

**Canonical name:** PidNameXSharingRemoteType

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.579 PidNameXSharingRemoteUid

**Canonical name:** PidNameXSharingRemoteUid

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Uid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**References:** [\[MS-OXSHARE\]](#)

**Alternate names:**

## 2.580 PidNameXUnifiedMessagingPartnerAssignedId

**Canonical name:** PidNameXUnifiedMessagingPartnerAssignedId

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** X-MS-Exchange-UM-PartnerAssignedID

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchangeUMPartnerAssignedID

## 2.581 PidNameXUnifiedMessagingPartnerContent

**Canonical name:** PidNameXUnifiedMessagingPartnerContent

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** X-MS-Exchange-UM-PartnerContent

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchangeUMPartnerContent

## 2.582 PidNameXUnifiedMessagingPartnerContext

**Canonical name:** PidNameXUnifiedMessagingPartnerContext

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** X-MS-Exchange-UM-PartnerContext

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchangeUMPartnerContext

## 2.583 PidNameXUnifiedMessagingPartnerStatus

**Canonical name:** PidNameXUnifiedMessagingPartnerStatus

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** X-MS-Exchange-UM-PartnerStatus

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** XMsExchangeUMPartnerStatus

## 2.584 PidNameXUnsent

**Canonical name:** PidNameXUnsent

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Unsent

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:mailheader:x-unsent

## 2.585 PidNameXVoiceMessageAttachmentOrder

**Canonical name:** PidNameXVoiceMessageAttachmentOrder

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-AttachmentOrder

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.586 PidNameXVoiceMessageDuration

**Canonical name:** PidNameXVoiceMessageDuration

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageDuration

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.587 PidNameXVoiceMessageSenderName

**Canonical name:** PidNameXVoiceMessageSenderName

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageSenderName

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:**

## 2.588 PidTag7BitDisplayName

**Canonical name:** PidTag7BitDisplayName

**Property ID:** 0x39FF

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_7BIT\_DISPLAY\_NAME, PR\_7BIT\_DISPLAY\_NAME\_A, PR\_7BIT\_DISPLAY\_NAME\_W

## 2.589 PidTagAccess

**Canonical name:** PidTagAccess

**Property ID:** 0x0FF4

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** PR\_ACCESS, ptagAccess

## 2.590 PidTagAccessLevel

**Canonical name:** PidTagAccessLevel

**Property ID:** 0x0FF7

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#)

**Alternate names:** PR\_ACCESS\_LEVEL, ptagAccessLevel

## 2.591 PidTagAccount

**Canonical name:** PidTagAccount

**Property ID:** 0x3A00

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXCMSG\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_ACCOUNT, PR\_ACCOUNT\_A, PR\_ACCOUNT\_W, urn:schemas:contacts:account

## 2.592 PidTagAdditionalRenEntryIds

**Canonical name:** PidTagAdditionalRenEntryIds

**Property ID:** 0x36D8

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Outlook Application

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS, ptagAdditionalRenEntryIds

### 2.593 PidTagAdditionalRenEntryIdsEx

**Canonical name:** PidTagAdditionalRenEntryIdsEx

**Property ID:** 0x36D9

**Data type:** PtypBinary, 0x0102

**Area:** Outlook Application

**References:** [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS\_EX, ptagAdditionalRenEntryIdsEx

### 2.594 PidTagAddressBookAuthorizedSenders

**Canonical name:** PidTagAddressBookAuthorizedSenders

**Property ID:** 0x8CD8

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_AUTH\_ORIG

### 2.595 PidTagAddressBookContainerId

**Canonical name:** PidTagAddressBookContainerId

**Property ID:** 0xFFFFD

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_CONTAINERID

### 2.596 PidTagAddressBookDeliveryContentLength

**Canonical name:** PidTagAddressBookDeliveryContentLength

**Property ID:** 0x806A

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_DELIV\_CONT\_LENGTH

## 2.597 PidTagAddressBookDisplayNamePrintable

**Canonical name:** PidTagAddressBookDisplayNamePrintable

**Property ID:** 0x39FF

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE,  
PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_A, PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_W

## 2.598 PidTagAddressBookDisplayTypeExtended

**Canonical name:** PidTagAddressBookDisplayTypeExtended

**Property ID:** 0x8C93

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_TYPE\_EX

## 2.599 PidTagAddressBookDistributionListExternalMemberCount

**Canonical name:** PidTagAddressBookDistributionListExternalMemberCount

**Property ID:** 0x8CE3

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_EXTERNAL\_MEMBER\_COUNT

## 2.600 PidTagAddressBookDistributionListMemberCount

**Canonical name:** PidTagAddressBookDistributionListMemberCount

**Property ID:** 0x8CE2

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_TOTAL\_MEMBER\_COUNT

## 2.601 PidTagAddressBookDistributionListMemberSubmitAccepted

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitAccepted

**Property ID:** 0x8073

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_SUBMIT\_PERMS

## 2.602 PidTagAddressBookDistributionListMemberSubmitRejected

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitRejected

**Property ID:** 0x8CDA

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_REJECT\_PERMS

## 2.603 PidTagAddressBookEntryId

**Canonical name:** PidTagAddressBookEntryId

**Property ID:** 0x663B

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**References:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_ADDRESS\_BOOK\_ENTRYID, ptagAddressBookEntryId

## 2.604 PidTagAddressBookExtensionAttribute 1

**Canonical name:** PidTagAddressBookExtensionAttribute 1

**Property ID:** 0x802D

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_W

## 2.605 PidTagAddressBookExtensionAttribute15

**Canonical name:** PidTagAddressBookExtensionAttribute15

**Property ID:** 0x8C61

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_W

## 2.606 PidTagAddressBookFolderPathname

**Canonical name:** PidTagAddressBookFolderPathname

**Property ID:** 0x8004

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_FOLDER\_PATHNAME, PR\_EMS\_AB\_FOLDER\_PATHNAME\_A,  
PR\_EMS\_AB\_FOLDER\_PATHNAME\_W

## 2.607 PidTagAddressBookHierarchicalChildDepartments

**Canonical name:** PidTagAddressBookHierarchicalChildDepartments

**Property ID:** 0x8C9A

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_CHILD\_DEPARTMENTS

## 2.608 PidTagAddressBookHierarchicalDepartmentMembers

**Canonical name:** PidTagAddressBookHierarchicalDepartmentMembers

**Property ID:** 0x8C97

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_DEPARTMENT\_MEMBERS



## 2.609 PidTagAddressBookHierarchicalIsHierarchicalGroup

**Canonical name:** PidTagAddressBookHierarchicalIsHierarchicalGroup

**Property ID:** 0x8CDD

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_IS\_HIERARCHICAL\_GROUP,  
PR\_EMS\_AB\_IS\_ORGANIZATIONAL

## 2.610 PidTagAddressBookHierarchicalParentDepartment

**Canonical name:** PidTagAddressBookHierarchicalParentDepartment

**Property ID:** 0x8C99

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_PARENT\_DEPARTMENT

## 2.611 PidTagAddressBookHierarchicalRootDepartment

**Canonical name:** PidTagAddressBookHierarchicalRootDepartment

**Property ID:** 0x8C98

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_ROOT\_DEPARTMENT

## 2.612 PidTagAddressBookHierarchicalShowInDepartments

**Canonical name:** PidTagAddressBookHierarchicalShowInDepartments

**Property ID:** 0x8C94

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_SHOW\_IN\_DEPARTMENTS

### 2.613 PidTagAddressBookHomeMessageDatabase

**Canonical name:** PidTagAddressBookHomeMessageDatabase

**Property ID:** 0x8006

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXABREF\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_HOME\_MDB, PR\_EMS\_AB\_HOME\_MDB\_A, PR\_EMS\_AB\_HOME\_MDB\_W

### 2.614 PidTagAddressBookIsMaster

**Canonical name:** PidTagAddressBookIsMaster

**Property ID:** 0xFFFFB

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MASTER

### 2.615 PidTagAddressBookIsMemberOfDistributionList

**Canonical name:** PidTagAddressBookIsMemberOfDistributionList

**Property ID:** 0x8008

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_A, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_W

### 2.616 PidTagAddressBookManageDistributionList

**Canonical name:** PidTagAddressBookManageDistributionList

**Property ID:** 0x6704

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGE\_DL

## 2.617 PidTagAddressBookManager

**Canonical name:** PidTagAddressBookManager

**Property ID:** 0x8005

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGER, PR\_EMS\_AB\_MANAGER\_A, PR\_EMS\_AB\_MANAGER\_W

## 2.618 PidTagAddressBookManagerDistinguishedName

**Canonical name:** PidTagAddressBookManagerDistinguishedName

**Property ID:** 0x8005

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGER\_T

## 2.619 PidTagAddressBookMember

**Canonical name:** PidTagAddressBookMember

**Property ID:** 0x8009

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_MEMBER, PR\_EMS\_AB\_MEMBER\_A, PR\_EMS\_AB\_MEMBER\_W

## 2.620 PidTagAddressBookMessageId

**Canonical name:** PidTagAddressBookMessageId

**Property ID:** 0x674F

**Data type:** PtypInteger64, 0x0014

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagAddrbookMID

## 2.621 PidTagAddressBookModerationEnabled

**Canonical name:** PidTagAddressBookModerationEnabled

**Property ID:** 0x8CB5

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_ENABLE\_MODERATION

## 2.622 PidTagAddressBookNetworkAddress

**Canonical name:** PidTagAddressBookNetworkAddress

**Property ID:** 0x8170

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_NETWORK\_ADDRESS, PR\_EMS\_AB\_NETWORK\_ADDRESS\_A, PR\_EMS\_AB\_NETWORK\_ADDRESS\_W

## 2.623 PidTagAddressBookObjectDistinguishedName

**Canonical name:** PidTagAddressBookObjectDistinguishedName

**Property ID:** 0x803C

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJ\_DIST\_NAME, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_A, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_W

## 2.624 PidTagAddressBookObjectGuid

**Canonical name:** PidTagAddressBookObjectGuid

**Property ID:** 0x8C6D

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJECT\_GUID

## 2.625 PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Canonical name:** PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Property ID:** 0x8CA8

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_ORG\_UNIT\_ROOT\_DN, msExchOURoot

## 2.626 PidTagAddressBookOwner

**Canonical name:** PidTagAddressBookOwner

**Property ID:** 0x800C

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_OWNER\_O

## 2.627 PidTagAddressBookOwnerBackLink

**Canonical name:** PidTagAddressBookOwnerBackLink

**Property ID:** 0x8024

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_OWNER\_BL\_O

## 2.628 PidTagAddressBookParentEntryId

**Canonical name:** PidTagAddressBookParentEntryId

**Property ID:** 0xFFFC

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_PARENT\_ENTRYID

## 2.629 PidTagAddressBookPhoneticCompanyName

**Canonical name:** PidTagAddressBookPhoneticCompanyName

**Property ID:** 0x8C91

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME,  
PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_W

## 2.630 PidTagAddressBookPhoneticDepartmentName

**Canonical name:** PidTagAddressBookPhoneticDepartmentName

**Property ID:** 0x8C90

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME,  
PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_W

## 2.631 PidTagAddressBookPhoneticDisplayName

**Canonical name:** PidTagAddressBookPhoneticDisplayName

**Property ID:** 0x8C92

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME,  
PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_W

## 2.632 PidTagAddressBookPhoneticGivenName

**Canonical name:** PidTagAddressBookPhoneticGivenName

**Property ID:** 0x8C8E

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME,  
PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_W

### 2.633 PidTagAddressBookPhoneticSurname

**Canonical name:** PidTagAddressBookPhoneticSurname

**Property ID:** 0x8C8F

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_SURNAME, PR\_EMS\_AB\_PHONETIC\_SURNAME\_A,  
PR\_EMS\_AB\_PHONETIC\_SURNAME\_W

### 2.634 PidTagAddressBookProxyAddresses

**Canonical name:** PidTagAddressBookProxyAddresses

**Property ID:** 0x800F

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**References:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PROXY\_ADDRESSES, PR\_EMS\_AB\_PROXY\_ADDRESSES\_A,  
PR\_EMS\_AB\_PROXY\_ADDRESSES\_W

### 2.635 PidTagAddressBookPublicDelegates

**Canonical name:** PidTagAddressBookPublicDelegates

**Property ID:** 0x8015

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PUBLIC\_DELEGATES, PR\_EMS\_AB\_PUBLIC\_DELEGATES\_A,  
PR\_EMS\_AB\_PUBLIC\_DELEGATES\_W

### 2.636 PidTagAddressBookReports

**Canonical name:** PidTagAddressBookReports

**Property ID:** 0x800E

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_REPORTS, PR\_EMS\_AB\_REPORTS\_A, PR\_EMS\_AB\_REPORTS\_W

### 2.637 PidTagAddressBookRoomCapacity

**Canonical name:** PidTagAddressBookRoomCapacity

**Property ID:** 0x0807

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_ROOM\_CAPACITY

### 2.638 PidTagAddressBookRoomContainers

**Canonical name:** PidTagAddressBookRoomContainers

**Property ID:** 0x8C96

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_ROOM\_CONTAINERS, PR\_EMS\_AB\_ROOM\_CONTAINERS\_A, PR\_EMS\_AB\_ROOM\_CONTAINERS\_W

### 2.639 PidTagAddressBookRoomDescription

**Canonical name:** PidTagAddressBookRoomDescription

**Property ID:** 0x0809

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_ROOM\_DESCRIPTION, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_A, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_W

### 2.640 PidTagAddressBookSenderHintTranslations

**Canonical name:** PidTagAddressBookSenderHintTranslations

**Property ID:** 0x8CAC

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book



**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_SENDER\_HINT\_TRANSLATIONS\_W

### 2.641 PidTagAddressBookSeniorityIndex

**Canonical name:** PidTagAddressBookSeniorityIndex

**Property ID:** 0x8CA0

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_SENIORITY\_INDEX, PR\_EMS\_AB\_SENIORITY\_INDEX

### 2.642 PidTagAddressBookTargetAddress

**Canonical name:** PidTagAddressBookTargetAddress

**Property ID:** 0x8011

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_TARGET\_ADDRESS, PR\_EMS\_AB\_TARGET\_ADDRESS\_A, PR\_EMS\_AB\_TARGET\_ADDRESS\_W

### 2.643 PidTagAddressBookUnauthorizedSenders

**Canonical name:** PidTagAddressBookUnauthorizedSenders

**Property ID:** 0x8CD9

**Data type:** PtypComObject, 0x000D

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_UNAUTH\_ORIG

### 2.644 PidTagAddressBookX509Certificate

**Canonical name:** PidTagAddressBookX509Certificate

**Property ID:** 0x8C6A

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_X509\_CERT

## 2.645 PidTagAddressType

**Canonical name:** PidTagAddressType

**Property ID:** 0x3002

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-EXOABK\]](#), [\[MS-EXOABKT\]](#), [\[MS-EXOMSG\]](#), [\[MS-EXORULE\]](#), [\[MS-EXOSRCH\]](#), [\[MS-EXPSVAL\]](#)

**Alternate names:** PR\_ADDRTYPE, PR\_ADDRTYPE\_A, ptagAddrType, PR\_ADDRTYPE\_W

## 2.646 PidTagAlternateRecipientAllowed

**Canonical name:** PidTagAlternateRecipientAllowed

**Property ID:** 0x0002

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-EXODOC\]](#), [\[MS-EXTNEF\]](#)

**Alternate names:** PR\_ALTERNATE\_RECIPIENT\_ALLOWED, ptagAlternateRecipientAllowed

## 2.647 PidTagAnr

**Canonical name:** PidTagAnr

**Property ID:** 0x360C

**Data type:** PtypString, 0x001F

**Area:** Address Book

**References:** [\[MS-EXOABK\]](#)

**Alternate names:** PR\_ANR, PR\_ANR\_A, PR\_ANR\_W

## 2.648 PidTagArchiveDate

**Canonical name:** PidTagArchiveDate

**Property ID:** 0x301F

**Data type:** PtypTime, 0x0040

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_ARCHIVE\_DATE, ptagArchiveDate

## 2.649 PidTagArchivePeriod

**Canonical name:** PidTagArchivePeriod

**Property ID:** 0x301E

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_ARCHIVE\_PERIOD, ptagArchivePeriod

## 2.650 PidTagArchiveTag

**Canonical name:** PidTagArchiveTag

**Property ID:** 0x3018

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_ARCHIVE\_TAG, ptagArchiveTag

## 2.651 PidTagAssistant

**Canonical name:** PidTagAssistant

**Property ID:** 0x3A30

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_ASSISTANT, PR\_ASSISTANT\_A, PR\_ASSISTANT\_W, urn:schemas:contacts:secretarycn

## 2.652 PidTagAssistantTelephoneNumber

**Canonical name:** PidTagAssistantTelephoneNumber

**Property ID:** 0x3A2E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_ASSISTANT\_TELEPHONE\_NUMBER,  
PR\_ASSISTANT\_TELEPHONE\_NUMBER\_A, PR\_ASSISTANT\_TELEPHONE\_NUMBER\_W,  
urn:schemas:contacts:secretaryphone

### 2.653 PidTagAssociated

**Canonical name:** PidTagAssociated

**Property ID:** 0x67AA

**Data type:** PtypBoolean, 0x000B

**Area:** Sync

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagAssociated

### 2.654 PidTagAttachAdditionalInformation

**Canonical name:** PidTagAttachAdditionalInformation

**Property ID:** 0x370F

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_ATTACH\_ADDITIONAL\_INFO

### 2.655 PidTagAttachContentBase

**Canonical name:** PidTagAttachContentBase

**Property ID:** 0x3711

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_BASE, PR\_ATTACH\_CONTENT\_BASE\_A,  
PR\_ATTACH\_CONTENT\_BASE\_W

### 2.656 PidTagAttachContentId

**Canonical name:** PidTagAttachContentId

**Property ID:** 0x3712

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_ID, PR\_ATTACH\_CONTENT\_ID\_A, PR\_ATTACH\_CONTENT\_ID\_W

## 2.657 PidTagAttachContentLocation

**Canonical name:** PidTagAttachContentLocation

**Property ID:** 0x3713

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_LOCATION, PR\_ATTACH\_CONTENT\_LOCATION\_A, PR\_ATTACH\_CONTENT\_LOCATION\_W

## 2.658 PidTagAttachDataBinary

**Canonical name:** PidTagAttachDataBinary

**Property ID:** 0x3701

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_BIN, ptagAttachDataBin

## 2.659 PidTagAttachDataObject

**Canonical name:** PidTagAttachDataObject

**Property ID:** 0x3701

**Data type:** PtypComObject, 0x000D

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_OBJ, ptagAttachDataObj

## 2.660 PidTagAttachEncoding

**Canonical name:** PidTagAttachEncoding

**Property ID:** 0x3702

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_ENCODING

## 2.661 PidTagAttachExtension

**Canonical name:** PidTagAttachExtension

**Property ID:** 0x3703

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_ATTACH\_EXTENSION, PR\_ATTACH\_EXTENSION\_A, PR\_ATTACH\_EXTENSION\_W

## 2.662 PidTagAttachFilename

**Canonical name:** PidTagAttachFilename

**Property ID:** 0x3704

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-XPFOAB\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_ATTACH\_FILENAME, PR\_ATTACH\_FILENAME\_A, ptagAttachFilename, PR\_ATTACH\_FILENAME\_W

## 2.663 PidTagAttachFlags

**Canonical name:** PidTagAttachFlags

**Property ID:** 0x3714

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_ATTACH\_FLAGS

## 2.664 PidTagAttachLongFilename

**Canonical name:** PidTagAttachLongFilename

**Property ID:** 0x3707

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOUM\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_FILENAME, PR\_ATTACH\_LONG\_FILENAME\_A, PR\_ATTACH\_LONG\_FILENAME\_W, urn:schemas:httpmail:attachmentfilename

## 2.665 PidTagAttachLongPathname

**Canonical name:** PidTagAttachLongPathname

**Property ID:** 0x370D

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_PATHNAME, PR\_ATTACH\_LONG\_PATHNAME\_A, ptagAttachLongPathname, PR\_ATTACH\_LONG\_PATHNAME\_W

## 2.666 PidTagAttachmentContactPhoto

**Canonical name:** PidTagAttachmentContactPhoto

**Property ID:** 0x7FFF

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACHMENT\_CONTACTPHOTO

## 2.667 PidTagAttachmentFlags

**Canonical name:** PidTagAttachmentFlags

**Property ID:** 0x7FFD

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRN\]](#)

**Alternate names:** PR\_ATTACHMENT\_FLAGS, ptagAttachmentFlags

## 2.668 PidTagAttachmentHidden

**Canonical name:** PidTagAttachmentHidden

**Property ID:** 0x7FFE

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_ATTACHMENT\_HIDDEN

## 2.669 PidTagAttachmentLinkId

**Canonical name:** PidTagAttachmentLinkId

**Property ID:** 0x7FFA

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACHMENT\_LINKID, ptagAttachmentLinkId

## 2.670 PidTagAttachMethod

**Canonical name:** PidTagAttachMethod

**Property ID:** 0x3705

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_ATTACH\_METHOD, ptagAttachMethod

## 2.671 PidTagAttachMimeTag

**Canonical name:** PidTagAttachMimeTag

**Property ID:** 0x370E

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#)



**Alternate names:** PR\_ATTACH\_MIME\_TAG, PR\_ATTACH\_MIME\_TAG\_A, PR\_ATTACH\_MIME\_TAG\_W

## 2.672 PidTagAttachNumber

**Canonical name:** PidTagAttachNumber

**Property ID:** 0x0E21

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXRTFEX\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_ATTACH\_NUM, ptagAttachNum

## 2.673 PidTagAttachPathname

**Canonical name:** PidTagAttachPathname

**Property ID:** 0x3708

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_PATHNAME, PR\_ATTACH\_PATHNAME\_A, ptagAttachPathname, PR\_ATTACH\_PATHNAME\_W

## 2.674 PidTagAttachPayloadClass

**Canonical name:** PidTagAttachPayloadClass

**Property ID:** 0x371A

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_CLASS, PR\_ATTACH\_PAYLOAD\_CLASS\_A, PR\_ATTACH\_PAYLOAD\_CLASS\_W, ptagAttachPayloadClass

## 2.675 PidTagAttachPayloadProviderGuidString

**Canonical name:** PidTagAttachPayloadProviderGuidString

**Property ID:** 0x3719

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR,  
PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_A, PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_W

## 2.676 PidTagAttachRendering

**Canonical name:** PidTagAttachRendering

**Property ID:** 0x3709

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_RENDERING, ptagAttachRendering

## 2.677 PidTagAttachSize

**Canonical name:** PidTagAttachSize

**Property ID:** 0x0E20

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#),  
[\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_ATTACH\_SIZE, ptagAttachSize

## 2.678 PidTagAttachTag

**Canonical name:** PidTagAttachTag

**Property ID:** 0x370A

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TAG

## 2.679 PidTagAttachTransportName

**Canonical name:** PidTagAttachTransportName

**Property ID:** 0x370C

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TRANSPORT\_NAME, PR\_ATTACH\_TRANSPORT\_NAME\_A, PR\_ATTACH\_TRANSPORT\_NAME\_W

## 2.680 PidTagAttributeHidden

**Canonical name:** PidTagAttributeHidden

**Property ID:** 0x10F4

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties Property set

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_ATTR\_HIDDEN, ptagAttrHidden, DAV:ishidden

## 2.681 PidTagAttributeReadOnly

**Canonical name:** PidTagAttributeReadOnly

**Property ID:** 0x10F6

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties Property set

**References:** [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_ATTR\_READONLY, ptagAttrReadOnly, DAV:isreadonly

## 2.682 PidTagAttributeSystem

**Canonical name:** PidTagAttributeSystem

**Property ID:** 0x10F5

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTR\_SYSTEM, ptagAttrSystem

## 2.683 PidTagAutoForwarded

**Canonical name:** PidTagAutoForwarded

**Property ID:** 0x0005

**Data type:** PtypBoolean, 0x000B

**Area:** General Report Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_AUTO\_FORWARDED, ptagAutoForwarded

## 2.684 PidTagAutoResponseSuppress

**Canonical name:** PidTagAutoResponseSuppress

**Property ID:** 0x3FDF

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_AUTO\_RESPONSE\_SUPPRESS, ptagAutoResponseSuppress

## 2.685 PidTagBirthday

**Canonical name:** PidTagBirthday

**Property ID:** 0x3A42

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_BIRTHDAY, urn:schemas:contacts:bday

## 2.686 PidTagBlockStatus

**Canonical name:** PidTagBlockStatus

**Property ID:** 0x1096

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**References:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_BLOCK\_STATUS, ptagBlockStatus

## 2.687 PidTagBody

**Canonical name:** PidTagBody

**Property ID:** 0x1000

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_BODY, PR\_BODY\_A, ptagBody, PR\_BODY\_W,  
urn:schemas:httpmail:textdescription

## 2.688 PidTagBodyContentId

**Canonical name:** PidTagBodyContentId

**Property ID:** 0x1015

**Data type:** PtypString, 0x001F

**Area:** Exchange

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_ID, PR\_BODY\_CONTENT\_ID\_A, PR\_BODY\_CONTENT\_ID\_W

## 2.689 PidTagBodyContentLocation

**Canonical name:** PidTagBodyContentLocation

**Property ID:** 0x1014

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_LOCATION, PR\_BODY\_CONTENT\_LOCATION\_A,  
PR\_BODY\_CONTENT\_LOCATION\_W

## 2.690 PidTagBodyHtml

**Canonical name:** PidTagBodyHtml

**Property ID:** 0x1013

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#),  
[\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_BODY\_HTML, PR\_BODY\_HTML\_A, ptagBodyHtml, PR\_BODY\_HTML\_W

## 2.691 PidTagBusiness2TelephoneNumber

**Canonical name:** PidTagBusiness2TelephoneNumber

**Property ID:** 0x3A1B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** "PR\_BUSINESS2\_TELEPHONE\_NUMBER, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_W, PR\_OFFICE2\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephonenumber2

## 2.692 PidTagBusiness2TelephoneNumbers

**Canonical name:** PidTagBusiness2TelephoneNumbers

**Property ID:** 0x3A1B

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A\_MV

## 2.693 PidTagBusinessFaxNumber

**Canonical name:** PidTagBusinessFaxNumber

**Property ID:** 0x3A24

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_BUSINESS\_FAX\_NUMBER, PR\_BUSINESS\_FAX\_NUMBER\_A, PR\_BUSINESS\_FAX\_NUMBER\_W, urn:schemas:contacts:facsimiletelephonenumber

## 2.694 PidTagBusinessHomePage

**Canonical name:** PidTagBusinessHomePage

**Property ID:** 0x3A51

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_BUSINESS\_HOME\_PAGE, PR\_BUSINESS\_HOME\_PAGE\_A, PR\_BUSINESS\_HOME\_PAGE\_W, urn:schemas:contacts:businesshomepageurn:schemas:contacts:businesshomepage

## 2.695 PidTagBusinessTelephoneNumber

**Canonical name:** PidTagBusinessTelephoneNumber

**Property ID:** 0x3A08

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_BUSINESS\_TELEPHONE\_NUMBER, PR\_BUSINESS\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS\_TELEPHONE\_NUMBER\_W, PR\_OFFICE\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephoneNumber

## 2.696 PidTagCallbackTelephoneNumber

**Canonical name:** PidTagCallbackTelephoneNumber

**Property ID:** 0x3A02

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_CALLBACK\_TELEPHONE\_NUMBER, PR\_CALLBACK\_TELEPHONE\_NUMBER\_A, PR\_CALLBACK\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:callbackphone

## 2.697 PidTagCallId

**Canonical name:** PidTagCallId

**Property ID:** 0x6806

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaCallID

## 2.698 PidTagCarTelephoneNumber

**Canonical name:** PidTagCarTelephoneNumber

**Property ID:** 0x3A1E

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_CAR\_TELEPHONE\_NUMBER, PR\_CAR\_TELEPHONE\_NUMBER\_A, PR\_CAR\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:othermobile

## 2.699 PidTagCdoRecurrenceid

**Canonical name:** PidTagCdoRecurrenceid

**Property ID:** 0x10C5

**Data type:** PtypTime, 0x0040

**Area:** Exchange Property set

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_CDO\_RECURRENCEID, urn:schemas:calendar:recurrenceid

## 2.700 PidTagChangeKey

**Canonical name:** PidTagChangeKey

**Property ID:** 0x65E2

**Data type:** PtypBinary, 0x0102

**Area:** History Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_CHANGE\_KEY

## 2.701 PidTagChangeNotificationGuid

**Canonical name:** PidTagChangeNotificationGuid

**Property ID:** 0x6637

**Data type:** PtypGuid, 0x0048

**Area:** Exchange

**References:** [\[MS-OXCNOTIF\]](#)

**Alternate names:** PR\_CHANGE\_NOTIFICATION\_GUID

## 2.702 PidTagChangeNumber

**Canonical name:** PidTagChangeNumber

**Property ID:** 0x67A4

**Data type:** PtypInteger64, 0x0014

**Area:** Sync

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagCn

## 2.703 PidTagChildrensNames

**Canonical name:** PidTagChildrensNames

**Property ID:** 0x3A58



**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_CHILDRENS\_NAMES, PR\_CHILDRENS\_NAMES\_A, PR\_CHILDRENS\_NAMES\_W, urn:schemas:contacts:childrensnames

## 2.704 PidTagClientActions

**Canonical name:** PidTagClientActions

**Property ID:** 0x6645

**Data type:** PtypBinary, 0x0102

**Area:** Server-side Rules Properties

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_CLIENT\_ACTIONS, ptagClientActions

## 2.705 PidTagClientSubmitTime

**Canonical name:** PidTagClientSubmitTime

**Property ID:** 0x0039

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_CLIENT\_SUBMIT\_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

## 2.706 PidTagCnsetRead

**Canonical name:** PidTagCnsetRead

**Property ID:** 0x67D2

**Data type:** PtypBinary, 0x0102

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagCnsetRead

## 2.707 PidTagCnsetSeen

**Canonical name:** PidTagCnsetSeen

**Property ID:** 0x6796

**Data type:** PtypBinary, 0x0102

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagCnsetSeen

## 2.708 PidTagCnsetSeenFAI

**Canonical name:** PidTagCnsetSeenFAI

**Property ID:** 0x67DA

**Data type:** PtypBinary, 0x0102

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagCnsetSeenFAI

## 2.709 PidTagCodePageId

**Canonical name:** PidTagCodePageId

**Property ID:** 0x66C3

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange Profile Configuration

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_CODE\_PAGE\_ID, ptagCodePageId

## 2.710 PidTagComment

**Canonical name:** PidTagComment

**Property ID:** 0x3004

**Data type:** PtypString, 0x001F

**Area:** Common Property set

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_COMMENT, PR\_COMMENT\_A, ptagComment, PR\_COMMENT\_W, DAV:comment, <http://schemas.microsoft.com/exchange/summary-utf8>

## 2.711 PidTagCompanyMainTelephoneNumber

**Canonical name:** PidTagCompanyMainTelephoneNumber

**Property ID:** 0x3A57

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_COMPANY\_MAIN\_PHONE\_NUMBER, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_A, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_W, urn:schemas:contacts:organizationmainphone

## 2.712 PidTagCompanyName

**Canonical name:** PidTagCompanyName

**Property ID:** 0x3A16

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#)

**Alternate names:** PR\_COMPANY\_NAME, PR\_COMPANY\_NAME\_A, PR\_COMPANY\_NAME\_W, urn:schemas:contacts:o

## 2.713 PidTagComputerNetworkName

**Canonical name:** PidTagComputerNetworkName

**Property ID:** 0x3A49

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_COMPUTER\_NETWORK\_NAME, PR\_COMPUTER\_NETWORK\_NAME\_A, PR\_COMPUTER\_NETWORK\_NAME\_W, urn:schemas:contacts:computernetworkname

## 2.714 PidTagConflictEntryId

**Canonical name:** PidTagConflictEntryId

**Property ID:** 0x3FF0

**Data type:** PtypBinary, 0x0102

**Area:** ICS

**References:** [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_CONFLICT\_ENTRYID, ptagConflictEntryId

## 2.715 PidTagConflictItems

**Canonical name:** PidTagConflictItems

**Property ID:** 0x1098

**Data type:** PtypMultipleBinary, 0x1102

**Area:** ICS

**References:** [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_CONFLICT\_ITEMS

## 2.716 PidTagContainerClass

**Canonical name:** PidTagContainerClass

**Property ID:** 0x3613

**Data type:** PtypString, 0x001F

**Area:** Container Properties Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

**Alternate names:** PR\_CONTAINER\_CLASS, PR\_CONTAINER\_CLASS\_A, ptagContainerClass, PR\_CONTAINER\_CLASS\_W,  
<http://schemas.microsoft.com/exchange/outlookfolderclass>  
<http://schemas.microsoft.com/exchange/outlookfolderclass>

## 2.717 PidTagContainerContents

**Canonical name:** PidTagContainerContents

**Property ID:** 0x360F

**Data type:** PtypComObject, 0x000D

**Area:** Container Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_CONTAINER\_CONTENTS, ptagContainerContents

## 2.718 PidTagContainerFlags

**Canonical name:** PidTagContainerFlags

**Property ID:** 0x3600

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_CONTAINER\_FLAGS

## 2.719 PidTagContainerHierarchy

**Canonical name:** PidTagContainerHierarchy

**Property ID:** 0x360E

**Data type:** PtypComObject, 0x000D

**Area:** Container Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_CONTAINER\_HIERARCHY, ptagContainerHierarchy

## 2.720 PidTagContentCount

**Canonical name:** PidTagContentCount

**Property ID:** 0x3602

**Data type:** PtypInteger32, 0x0003

**Area:** Folder Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_CONTENT\_COUNT, ptagContentCount, DAV:visiblecount

## 2.721 PidTagContentFilterPhishingConfidenceLevel

**Canonical name:** PidTagContentFilterPhishingConfidenceLevel

**Property ID:** 0x4084

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ContentFilterPcl, PR\_CONTENT\_FILTER\_PCL

## 2.722 PidTagContentFilterSpamConfidenceLevel

**Canonical name:** PidTagContentFilterSpamConfidenceLevel

**Property ID:** 0x4076

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CONTENT\_FILTER\_SCL, ptagContentFilterSCL

### 2.723 PidTagContentUnreadCount

**Canonical name:** PidTagContentUnreadCount

**Property ID:** 0x3603

**Data type:** PtypInteger32, 0x0003

**Area:** Folder Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_CONTENT\_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

### 2.724 PidTagConversationId

**Canonical name:** PidTagConversationId

**Property ID:** 0x3013

**Data type:** PtypBinary, 0x0102

**Area:** Conversations

**References:** [\[MS-OXGLOS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_CONVERSATION\_ID

### 2.725 PidTagConversationIndex

**Canonical name:** PidTagConversationIndex

**Property ID:** 0x0071

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#),

**Alternate names:** PR\_CONVERSATION\_INDEX, ptagConversationIndex

### 2.726 PidTagConversationIndexTracking

**Canonical name:** PidTagConversationIndexTracking

**Property ID:** 0x3016

**Data type:** PtypBoolean, 0x000B

**Area:** Conversations

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_CONVERSATION\_INDEX\_TRACKING

## 2.727 PidTagConversationTopic

**Canonical name:** PidTagConversationTopic

**Property ID:** 0x0070

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_CONVERSATION\_TOPIC, PR\_CONVERSATION\_TOPIC\_A, ptagConversationTopic, PR\_CONVERSATION\_TOPIC\_W, urn:schemas:httpmail:thread-topic

## 2.728 PidTagCountry

**Canonical name:** PidTagCountry

**Property ID:** 0x3A26

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_COUNTRY, PR\_COUNTRY\_A, PR\_COUNTRY\_W, PR\_BUSINESS\_ADDRESS\_COUNTRY, PR\_BUSINESS\_ADDRESS\_COUNTRY\_A, PR\_BUSINESS\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:mailingcountry

## 2.729 PidTagCreationTime

**Canonical name:** PidTagCreationTime

**Property ID:** 0x3007

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_CREATION\_TIME, ptagCreationTime, DAV:creationdate

## 2.730 PidTagCreatorEntryId

**Canonical name:** PidTagCreatorEntryId

**Property ID:** 0x3FF9

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_ENTRYID, ptagCreatorEntryId

### 2.731 PidTagCreatorName

**Canonical name:** PidTagCreatorName

**Property ID:** 0x3FF8

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_NAME, PR\_CREATOR\_NAME\_A, ptagCreatorName, PR\_CREATOR\_NAME\_W

### 2.732 PidTagCreatorSimpleDisplay Name

**Canonical name:** PidTagCreatorSimpleDisplayName

**Property ID:** 0x4038

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** ptagCreatorSimpleDispName

### 2.733 PidTagCustomerId

**Canonical name:** PidTagCustomerId

**Property ID:** 0x3A4A

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_CUSTOMER\_ID, PR\_CUSTOMER\_ID\_A, PR\_CUSTOMER\_ID\_W, urn:schemas:contacts:customerid

### 2.734 PidTagDamBackPatched

**Canonical name:** PidTagDamBackPatched

**Property ID:** 0x6647

**Data type:** PtypBoolean, 0x000B

**Area:** Server-side Rules Properties



**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_DAM\_BACK\_PATCHED, ptagDamBackPatched

### 2.735 PidTagDamOriginalEntryId

**Canonical name:** PidTagDamOriginalEntryId

**Property ID:** 0x6646

**Data type:** PtypBinary, 0x0102

**Area:** Server-side Rules Properties

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_DAM\_ORIGINAL\_ENTRYID

### 2.736 PidTagDefaultPostMessageClass

**Canonical name:** PidTagDefaultPostMessageClass

**Property ID:** 0x36E5

**Data type:** PtypString, 0x001F

**Area:** MapiContainer

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_DEF\_POST\_MSGCLASS

### 2.737 PidTagDeferredDeliveryTime

**Canonical name:** PidTagDeferredDeliveryTime

**Property ID:** 0x000F

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_DEFERRED\_DELIVERY\_TIME, ptagDeferredDeliveryTime, <http://schemas.microsoft.com/exchange/deferred-delivery-iso>

### 2.738 PidTagDeferredSendNumber

**Canonical name:** PidTagDeferredSendNumber

**Property ID:** 0x3FEB

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_DEFERRED\_SEND\_NUMBER

### 2.739 PidTagDeferredSendTime

**Canonical name:** PidTagDeferredSendTime

**Property ID:** 0x3FEF

**Data type:** PtypTime, 0x0040

**Area:** MapiStatus

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_DEFERRED\_SEND\_TIME, ptagDeferredSendTime

### 2.740 PidTagDeferredSendUnits

**Canonical name:** PidTagDeferredSendUnits

**Property ID:** 0x3FEC

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_DEFERRED\_SEND\_UNITS

### 2.741 PidTagDelegatedByRule

**Canonical name:** PidTagDelegatedByRule

**Property ID:** 0x3FE3

**Data type:** PtypBoolean, 0x000B

**Area:** MapiStatus

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_DELEGATED\_BY\_RULE

### 2.742 PidTagDelegateFlags

**Canonical name:** PidTagDelegateFlags

**Property ID:** 0x686B

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** MessageClassDefinedTransmittable

**References:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_DELEGATE\_FLAGS, ptagDelegateFlags

### 2.743 PidTagDeleteAfterSubmit

**Canonical name:** PidTagDeleteAfterSubmit

**Property ID:** 0x0E01

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_DELETE\_AFTER\_SUBMIT, ptagDeleteAfterSubmit

### 2.744 PidTagDeletedOn

**Canonical name:** PidTagDeletedOn

**Property ID:** 0x668F

**Data type:** PtypTime, 0x0040

**Area:** ExchangeFolder Property set

**References:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_DELETED\_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

### 2.745 PidTagDepartmentName

**Canonical name:** PidTagDepartmentName

**Property ID:** 0x3A18

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_DEPARTMENT\_NAME, PR\_DEPARTMENT\_NAME\_A, PR\_DEPARTMENT\_NAME\_W, urn:schemas:contacts:department

### 2.746 PidTagDepth

**Canonical name:** PidTagDepth

**Property ID:** 0x3005

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**References:** [\[MS-NSPI\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_DEPTH, ptagDepth

## 2.747 PidTagDisplayBcc

**Canonical name:** PidTagDisplayBcc

**Property ID:** 0x0E02

**Data type:** PtypString, 0x001F

**Area:** Message Properties Property set

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_DISPLAY\_BCC, PR\_DISPLAY\_BCC\_A, ptagDisplayBcc, PR\_DISPLAY\_BCC\_W, urn:schemas:httpmail:displaybcc

## 2.748 PidTagDisplayCc

**Canonical name:** PidTagDisplayCc

**Property ID:** 0x0E03

**Data type:** PtypString, 0x001F

**Area:** Message Properties Property set

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_DISPLAY\_CC, PR\_DISPLAY\_CC\_A, ptagDisplayCc, PR\_DISPLAY\_CC\_W, urn:schemas:httpmail:displaycc

## 2.749 PidTagDisplayName

**Canonical name:** PidTagDisplayName

**Property ID:** 0x3001

**Data type:** PtypString, 0x001F

**Area:** MapiCommon

**References:** [\[MS-OXCMSG\]](#), [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDVSEC\]](#)

**Alternate names:** PR\_DISPLAY\_NAME, PR\_DISPLAY\_NAME\_A, ptagDisplayName, PR\_DISPLAY\_NAME\_W, urn:schemas:contacts:cn

## 2.750 PidTagDisplayNamePrefix

**Canonical name:** PidTagDisplayNamePrefix

**Property ID:** 0x3A45

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_DISPLAY\_NAME\_PREFIX, PR\_DISPLAY\_NAME\_PREFIX\_A, PR\_DISPLAY\_NAME\_PREFIX\_W, urn:schemas:contacts:personaltitle

### 2.751 PidTagDisplayTo

**Canonical name:** PidTagDisplayTo

**Property ID:** 0x0E04

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_DISPLAY\_TO, PR\_DISPLAY\_TO\_A, ptagDisplayTo, PR\_DISPLAY\_TO\_W

### 2.752 PidTagDisplayType

**Canonical name:** PidTagDisplayType

**Property ID:** 0x3900

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**References:** [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE, ptagDisplayType

### 2.753 PidTagDisplayTypeEx

**Canonical name:** PidTagDisplayTypeEx

**Property ID:** 0x3905

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE\_EX

### 2.754 PidTagEcWarning

**Canonical name:** PidTagEcWarning

**Property ID:** 0x400F

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagEcWarning

## 2.755 PidTagEmailAddress

**Canonical name:** PidTagEmailAddress

**Property ID:** 0x3003

**Data type:** PtypString, 0x001F

**Area:** MapiCommon

**References:** [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXPSVAL\]](#)

**Alternate names:** PR\_EMAIL\_ADDRESS, PR\_EMAIL\_ADDRESS\_A, PR\_EMAIL\_ADDRESS\_W

## 2.756 PidTagEndAttach

**Canonical name:** PidTagEndAttach

**Property ID:** 0x400E

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagEndAttach

## 2.757 PidTagEndDate

**Canonical name:** PidTagEndDate

**Property ID:** 0x0061

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_END\_DATE, [http://schemas.microsoft.com/mapi/end\\_date](http://schemas.microsoft.com/mapi/end_date)

## 2.758 PidTagEndEmbed

**Canonical name:** PidTagEndEmbed

**Property ID:** 0x4002

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagEndEmbed

## 2.759 PidTagEndFolder

**Canonical name:** PidTagEndFolder

**Property ID:** 0x400B

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagEndFolder

## 2.760 PidTagEndMessage

**Canonical name:** PidTagEndMessage

**Property ID:** 0x400D

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagEndMessage

## 2.761 PidTagEndToRecip

**Canonical name:** PidTagEndToRecip

**Property ID:** 0x4004

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagEndToRecip

## 2.762 PidTagEntryId

**Canonical name:** PidTagEntryId

**Property ID:** 0x0FFF

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPerm\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-](#)

[OXODLGT](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXWAVLS\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_ENTRYID, ptagEntryId

### 2.763 PidTagExceptionEndTime

**Canonical name:** PidTagExceptionEndTime

**Property ID:** 0x7FFC

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_ENDTIME, ptagExceptionEndTime

### 2.764 PidTagExceptionReplaceTime

**Canonical name:** PidTagExceptionReplaceTime

**Property ID:** 0x7FF9

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_EXCEPTION\_REPLACETIME

### 2.765 PidTagExceptionStartTime

**Canonical name:** PidTagExceptionStartTime

**Property ID:** 0x7FFB

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_STARTTIME, ptagExceptionStartTime

### 2.766 PidTagExchangeNTSecurityDescriptor

**Canonical name:** PidTagExchangeNTSecurityDescriptor

**Property ID:** 0x0E84

**Data type:** PtypBinary, 0x0102

**Area:** Calendar Document Property set

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)



**Alternate names:** <http://schemas.microsoft.com/exchange/ntsecuritydescriptor>,  
<http://schemas.microsoft.com/exchange/ntsecuritydescriptor>

## 2.767 PidTagExpiryNumber

**Canonical name:** PidTagExpiryNumber

**Property ID:** 0x3FED

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_EXPIRY\_NUMBER

## 2.768 PidTagExpiryTime

**Canonical name:** PidTagExpiryTime

**Property ID:** 0x0015

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_EXPIRY\_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date,  
<http://schemas.microsoft.com/exchange/expiry-date-iso>

## 2.769 PidTagExpiryUnits

**Canonical name:** PidTagExpiryUnits

**Property ID:** 0x3FEE

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_EXPIRY\_UNITS

## 2.770 PidTagExtendedFolderFlags

**Canonical name:** PidTagExtendedFolderFlags

**Property ID:** 0x36DA

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_EXTENDED\_FOLDER\_FLAGS, ptagExtendedFolderFlags

### 2.771 PidTagExtendedRuleMessageActions

**Canonical name:** PidTagExtendedRuleMessageActions

**Property ID:** 0x0E99

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_ACTIONS

### 2.772 PidTagExtendedRuleMessageCondition

**Canonical name:** PidTagExtendedRuleMessageCondition

**Property ID:** 0x0E9A

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**References:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_CONDITION

### 2.773 PidTagExtendedRuleSizeLimit

**Canonical name:** PidTagExtendedRuleSizeLimit

**Property ID:** 0x0E9B

**Data type:** PtypInteger32, 0x0003

**Area:** Rules

**References:** [\[MS-OXCSTOR\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_SIZE\_LIMIT

### 2.774 PidTagFaxNumberOfPages

**Canonical name:** PidTagFaxNumberOfPages

**Property ID:** 0x6804

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaFaxNumberOfPages

## 2.775 PidTagFlagCompleteTime

**Canonical name:** PidTagFlagCompleteTime

**Property ID:** 0x1091

**Data type:** PtypTime, 0x0040

**Area:** Miscellaneous Properties Property set

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_FLAG\_COMPLETE\_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

## 2.776 PidTagFlagStatus

**Canonical name:** PidTagFlagStatus

**Property ID:** 0x1090

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FLAG\_STATUS, ptagFlagStatus

## 2.777 PidTagFlatUrlName

**Canonical name:** PidTagFlatUrlName

**Property ID:** 0x670E

**Data type:** PtypString, 0x001F

**Area:** ExchangeAdministrative Property set

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_FLAT\_URL\_NAME, PR\_FLAT\_URL\_NAME\_A, PR\_FLAT\_URL\_NAME\_W, ptagFlatURLName, http://schemas.microsoft.com/exchange/permanenturl

## 2.778 PidTagFolderAssociatedContents

**Canonical name:** PidTagFolderAssociatedContents

**Property ID:** 0x3610

**Data type:** PtypComObject, 0x000D

**Area:** MapiContainer

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_FOLDER\_ASSOCIATED\_CONTENTS

## 2.779 PidTagFolderId

**Canonical name:** PidTagFolderId

**Property ID:** 0x6748

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** ptagFID

## 2.780 PidTagFolderType

**Canonical name:** PidTagFolderType

**Property ID:** 0x3601

**Data type:** PtypInteger32, 0x0003

**Area:** MapiContainer

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_FOLDER\_TYPE, ptagFolderType

## 2.781 PidTagFollowupIcon

**Canonical name:** PidTagFollowupIcon

**Property ID:** 0x1095

**Data type:** PtypInteger32, 0x0003

**Area:** RenMessageFolder

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FOLLOWUP\_ICON, ptagFollowupIcon

## 2.782 PidTagFreeBusyCountMonths

**Canonical name:** PidTagFreeBusyCountMonths

**Property ID:** 0x6869

**Data type:** PtypInteger32, 0x0003

**Area:** MessageClassDefinedTransmittable

**References:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_COUNT\_MONTHS

### 2.783 PidTagFreeBusyEntryIds

**Canonical name:** PidTagFreeBusyEntryIds

**Property ID:** 0x36E4

**Data type:** PtypMultipleBinary, 0x1102

**Area:** MapiContainer

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FREEBUSY\_ENTRYIDS, ptagFreeBusyEntryIds

### 2.784 PidTagFreeBusyMessageEmailAddress

**Canonical name:** PidTagFreeBusyMessageEmailAddress

**Property ID:** 0x6849

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_EMA

### 2.785 PidTagFreeBusyPublishEnd

**Canonical name:** PidTagFreeBusyPublishEnd

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_END

### 2.786 PidTagFreeBusyPublishStart

**Canonical name:** PidTagFreeBusyPublishStart

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_START

## 2.787 PidTagFreeBusyRangeTimestamp

**Canonical name:** PidTagFreeBusyRangeTimestamp

**Property ID:** 0x6868

**Data type:** PtypTime, 0x0040

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_RANGE\_TIMESTAMP

## 2.788 PidTagFtpSite

**Canonical name:** PidTagFtpSite

**Property ID:** 0x3A4C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_FTP\_SITE, PR\_FTP\_SITE\_A, PR\_FTP\_SITE\_W, urn:schemas:contacts:ftpsite

## 2.789 PidTagFXDelProp

**Canonical name:** PidTagFXDelProp

**Property ID:** 0x4016

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagFXDelProp

## 2.790 PidTagFXErrorInfo

**Canonical name:** PidTagFXErrorInfo

**Property ID:** 0x4018

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagFXErrorInfo

## 2.791 PidTagGatewayNeedsToRefresh

**Canonical name:** PidTagGatewayNeedsToRefresh

**Property ID:** 0x6846

**Data type:** PtypBoolean, 0x000B

**Area:** MessageClassDefinedTransmittable

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_GATEWAY\_NEEDS\_TO\_REFRESH

## 2.792 PidTagGender

**Canonical name:** PidTagGender

**Property ID:** 0x3A4D

**Data type:** PtypInteger16, 0x0002

**Area:** MapiMailUser

**References:** [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_GENDER, urn:schemas:contacts:gender

## 2.793 PidTagGeneration

**Canonical name:** PidTagGeneration

**Property ID:** 0x3A05

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_GENERATION, PR\_GENERATION\_A, PR\_GENERATION\_W, urn:schemas:contacts:namesuffix

## 2.794 PidTagGivenName

**Canonical name:** PidTagGivenName

**Property ID:** 0x3A06

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_GIVEN\_NAME, PR\_GIVEN\_NAME\_A, PR\_GIVEN\_NAME\_W, urn:schemas:contacts:givenName

## 2.795 PidTagGovernmentIdNumber

**Canonical name:** PidTagGovernmentIdNumber

**Property ID:** 0x3A07

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_GOVERNMENT\_ID\_NUMBER, PR\_GOVERNMENT\_ID\_NUMBER\_A, PR\_GOVERNMENT\_ID\_NUMBER\_W, urn:schemas:contacts:governmentid

## 2.796 PidTagHasAttachments

**Canonical name:** PidTagHasAttachments

**Property ID:** 0x0E1B

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

## 2.797 PidTagHasDeferredActionMessages

**Canonical name:** PidTagHasDeferredActionMessages

**Property ID:** 0x3FEA

**Data type:** PtypBoolean, 0x000B

**Area:** Rules

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_HAS\_DAMS, ptagHasDAMs

## 2.798 PidTagHasNamedProperties

**Canonical name:** PidTagHasNamedProperties

**Property ID:** 0x664A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeMessageReadOnly

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_HAS\_NAMED\_PROPERTIES, ptagHasNamedProperties



## 2.799 PidTagHasRules

**Canonical name:** PidTagHasRules

**Property ID:** 0x663A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeFolder

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_HAS\_RULES, ptagHasRules

## 2.800 PidTagHierarchyChangeNumber

**Canonical name:** PidTagHierarchyChangeNumber

**Property ID:** 0x663E

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**References:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_HIERARCHY\_CHANGE\_NUM

## 2.801 PidTagHobbies

**Canonical name:** PidTagHobbies

**Property ID:** 0x3A43

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOBBIES, PR\_HOBBIES\_A, PR\_HOBBIES\_W, urn:schemas:contacts:hobbies

## 2.802 PidTagHome2TelephoneNumber

**Canonical name:** PidTagHome2TelephoneNumber

**Property ID:** 0x3A2F

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER, PR\_HOME2\_TELEPHONE\_NUMBER\_A, PR\_HOME2\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homephone2

## 2.803 PidTagHome2TelephoneNumbers

**Canonical name:** PidTagHome2TelephoneNumbers

**Property ID:** 0x3A2F

**Data type:** PtypMultipleString, 0x101F

**Area:** MapiMailUser

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER\_A\_MV

## 2.804 PidTagHomeAddressCity

**Canonical name:** PidTagHomeAddressCity

**Property ID:** 0x3A59

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_CITY, PR\_HOME\_ADDRESS\_CITY\_A, PR\_HOME\_ADDRESS\_CITY\_W, urn:schemas:contacts:homeCity

## 2.805 PidTagHomeAddressCountry

**Canonical name:** PidTagHomeAddressCountry

**Property ID:** 0x3A5A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_COUNTRY, PR\_HOME\_ADDRESS\_COUNTRY\_A, PR\_HOME\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:homeCountry

## 2.806 PidTagHomeAddressPostalCode

**Canonical name:** PidTagHomeAddressPostalCode

**Property ID:** 0x3A5B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POSTAL\_CODE, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_A, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:homePostalCode

## 2.807 PidTagHomeAddressPostOfficeBox

**Canonical name:** PidTagHomeAddressPostOfficeBox

**Property ID:** 0x3A5E

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:homepostofficebox

## 2.808 PidTagHomeAddressStateOrProvince

**Canonical name:** PidTagHomeAddressStateOrProvince

**Property ID:** 0x3A5C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:homeState

## 2.809 PidTagHomeAddressStreet

**Canonical name:** PidTagHomeAddressStreet

**Property ID:** 0x3A5D

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STREET, PR\_HOME\_ADDRESS\_STREET\_A, PR\_HOME\_ADDRESS\_STREET\_W, urn:schemas:contacts:homeStreet

## 2.810 PidTagHomeFaxNumber

**Canonical name:** PidTagHomeFaxNumber

**Property ID:** 0x3A25

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_FAX\_NUMBER, PR\_HOME\_FAX\_NUMBER\_A, PR\_HOME\_FAX\_NUMBER\_W, urn:schemas:contacts:homefax

### 2.811 PidTagHomeTelephoneNumber

**Canonical name:** PidTagHomeTelephoneNumber

**Property ID:** 0x3A09

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_HOME\_TELEPHONE\_NUMBER, PR\_HOME\_TELEPHONE\_NUMBER\_A, PR\_HOME\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homePhone

### 2.812 PidTagHtml

**Canonical name:** PidTagHtml

**Property ID:** 0x1013

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_HTML, ptagHtml

### 2.813 PidTagICalendarEndTime

**Canonical name:** PidTagICalendarEndTime

**Property ID:** 0x10C4

**Data type:** PtypTime, 0x0040

**Area:** Calendar Property set

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:dtend

### 2.814 PidTagICalendarReminderNextTime

**Canonical name:** PidTagICalendarReminderNextTime

**Property ID:** 0x10CA

**Data type:** PtypTime, 0x0040

**Area:** Calendar Property set

**References:** [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas:calendar:remindernexttime

### 2.815 PidTagICalendarStartTime

**Canonical name:** PidTagICalendarStartTime

**Property ID:** 0x10C3

**Data type:** PtypTime, 0x0040

**Area:** Calendar Property set

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** urn:schemas:calendar:dtstart

### 2.816 PidTagIconIndex

**Canonical name:** PidTagIconIndex

**Property ID:** 0x1080

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ICON\_INDEX, ptagIconIndex

### 2.817 PidTagIdsetDeleted

**Canonical name:** PidTagIdsetDeleted

**Property ID:** 0x67E5

**Data type:** PtypBinary, 0x0102

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIdsetDeleted

### 2.818 PidTagIdsetExpired

**Canonical name:** PidTagIdsetExpired

**Property ID:** 0x6793

**Data type:** PtypBinary, 0x0102

**Area:** Sync

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagMidsetExpired

### 2.819 PidTagIdsetGiven

**Canonical name:** PidTagIdsetGiven

**Property ID:** 0x4017

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIdsetGiven

### 2.820 PidTagIdsetRead

**Canonical name:** PidTagIdsetRead

**Property ID:** 0x402D

**Data type:** PtypBinary, 0x0102

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIdsetRead

### 2.821 PidTagIdsetNoLongerInScope

**Canonical name:** PidTagIdsetNoLongerInScope

**Property ID:** 0x4021

**Data type:** PtypBinary, 0x0102

**Area:** Sync

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagSoftDeletes

### 2.822 PidTagIdsetUnread

**Canonical name:** PidTagIdsetUnread

**Property ID:** 0x402E

**Data type:** PtypBinary, 0x0102

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIdsetUnread

### 2.823 PidTagImapCachedMsgsize

**Canonical name:** PidTagImapCachedMsgsize

**Property ID:** 0x10F0

**Data type:** PtypBinary, 0x0102

**Area:** RenMessageFolder

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** ptagImapCachedMsgsize

### 2.824 PidTagImportance

**Canonical name:** PidTagImportance

**Property ID:** 0x0017

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties Property set

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, <http://schemas.microsoft.com/exchange/importance-long>, <http://schemas.microsoft.com/exchange/x-priority-long>

### 2.825 PidTagInConflict

**Canonical name:** PidTagInConflict

**Property ID:** 0x666C

**Data type:** PtypBoolean, 0x000B

**Area:** Conflict Note

**References:** [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_IN\_CONFLICT, ptagInConflict

### 2.826 PidTagIncrementalSyncMessagePartial

**Canonical name:** PidTagIncrementalSyncMessagePartial

**Property ID:** 0x407A

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncMsgPartial

## 2.827 PidTagIncrSyncChg

**Canonical name:** PidTagIncrSyncChg

**Property ID:** 0x4012

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncChg

## 2.828 PidTagIncrSyncChgPartial

**Canonical name:** PidTagIncrSyncChgPartial

**Property ID:** 0x407D

**Data type:** PtypInteger32, 0x0003

**Area:** IC

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncChgPartial

## 2.829 PidTagIncrSyncDel

**Canonical name:** PidTagIncrSyncDel

**Property ID:** 0x4013

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncDel

## 2.830 PidTagIncrSyncEnd

**Canonical name:** PidTagIncrSyncEnd

**Property ID:** 0x4014

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncEnd



### 2.831 PidTagIncrSyncGroupId

**Canonical name:** PidTagIncrSyncGroupId

**Property ID:** 0x407C

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncGroupId

### 2.832 PidTagIncrSyncGroupInfo

**Canonical name:** PidTagIncrSyncGroupInfo

**Property ID:** 0x407B

**Data type:** PtypBinary, 0x0102

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncGroupInfo

### 2.833 PidTagIncrSyncMessage

**Canonical name:** PidTagIncrSyncMessage

**Property ID:** 0x4015

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncMsg

### 2.834 PidTagIncrSyncProgressMode

**Canonical name:** PidTagIncrSyncProgressMode

**Property ID:** 0x4074

**Data type:** PtypBoolean, 0x000B

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncProgressMode

### 2.835 PidTagIncrSyncProgressPerMsg

**Canonical name:** PidTagIncrSyncProgressPerMsg

**Property ID:** 0x4075

**Data type:** PtypBoolean, 0x000B

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncProgressPerMsg

### 2.836 PidTagIncrSyncRead

**Canonical name:** PidTagIncrSyncRead

**Property ID:** 0x402F

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncRead

### 2.837 PidTagIncrSyncStateBegin

**Canonical name:** PidTagIncrSyncStateBegin

**Property ID:** 0x403A

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncStateBegin

### 2.838 PidTagIncrSyncStateEnd

**Canonical name:** PidTagIncrSyncStateEnd

**Property ID:** 0x403B

**Data type:** PtypInteger32, 0x0003

**Area:** ICS

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagIncrSyncStateEnd

## 2.839 PidTagInitialDetailsPane

**Canonical name:** PidTagInitialDetailsPane

**Property ID:** 0x3F08

**Data type:** PtypInteger32, 0x0003

**Area:** MAPI Display Tables

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_INITIAL\_DETAILS\_PANE

## 2.840 PidTagInitials

**Canonical name:** PidTagInitials

**Property ID:** 0x3A0A

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_INITIALS, PR\_INITIALS\_A, PR\_INITIALS\_W, urn:schemas:contacts:initials

## 2.841 PidTagInReplyToId

**Canonical name:** PidTagInReplyToId

**Property ID:** 0x1042

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_IN\_REPLY\_TO\_ID, PR\_IN\_REPLY\_TO\_ID\_A, PR\_IN\_REPLY\_TO\_ID\_W

## 2.842 PidTagInstanceKey

**Canonical name:** PidTagInstanceKey

**Property ID:** 0x0FF6

**Data type:** PtypBinary, 0x0102

**Area:** Table Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_INSTANCE\_KEY, ptagInstanceKey

### 2.843 PidTagInstanceNum

**Canonical name:** PidTagInstanceNum

**Property ID:** 0x674E

**Data type:** PtypInteger32, 0x0003

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstanceNum

### 2.844 PidTagInstID

**Canonical name:** PidTagInstID

**Property ID:** 0x674D

**Data type:** PtypInteger64, 0x0014

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstID

### 2.845 PidTagInternetArticleNumber

**Canonical name:** PidTagInternetArticleNumber

**Property ID:** 0x0E23

**Data type:** PtypInteger32, 0x0003

**Area:** MIME Properties

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_INTERNET\_ARTICLE\_NUMBER

### 2.846 PidTagInternetCodepage

**Canonical name:** PidTagInternetCodepage

**Property ID:** 0x3FDE

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_CPID, ptagInternetCpid

## 2.847 PidTagInternetMailOverrideFormat

**Canonical name:** PidTagInternetMailOverrideFormat

**Property ID:** 0x5902

**Data type:** PtypInteger32, 0x0003

**Area:** MIME Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_INETMAIL\_OVERRIDE\_FORMAT, ptagInetMailOverrideFormat

## 2.848 PidTagInternetMessageId

**Canonical name:** PidTagInternetMessageId

**Property ID:** 0x1035

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_MESSAGE\_ID, PR\_INTERNET\_MESSAGE\_ID\_A, PR\_INTERNET\_MESSAGE\_ID\_W

## 2.849 PidTagInternetReferences

**Canonical name:** PidTagInternetReferences

**Property ID:** 0x1039

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_INTERNET\_REFERENCES, PR\_INTERNET\_REFERENCES\_A, PR\_INTERNET\_REFERENCES\_W

## 2.850 PidTagInternetReturnPath

**Canonical name:** PidTagInternetReturnPath

**Property ID:** 0x1046

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_INTERNET\_RETURN\_PATH, PR\_INTERNET\_RETURN\_PATH\_A, PR\_INTERNET\_RETURN\_PATH\_W

## 2.851 PidTagIpmAppointmentEntryId

**Canonical name:** PidTagIpmAppointmentEntryId

**Property ID:** 0x36D0

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_IPM\_APPOINTMENT\_ENTRYID

## 2.852 PidTagIpmContactEntryId

**Canonical name:** PidTagIpmContactEntryId

**Property ID:** 0x36D1

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_IPM\_CONTACT\_ENTRYID

## 2.853 PidTagIpmDraftsEntryId

**Canonical name:** PidTagIpmDraftsEntryId

**Property ID:** 0x36D7

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**References:** [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_IPM\_DRAFTS\_ENTRYID

## 2.854 PidTagIpmJournalEntryId

**Canonical name:** PidTagIpmJournalEntryId

**Property ID:** 0x36D2

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_IPM\_JOURNAL\_ENTRYID

## 2.855 PidTagIpmNoteEntryId

**Canonical name:** PidTagIpmNoteEntryId

**Property ID:** 0x36D3

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_IPM\_NOTE\_ENTRYID

## 2.856 PidTagIpmTaskEntryId

**Canonical name:** PidTagIpmTaskEntryId

**Property ID:** 0x36D4

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_IPM\_TASK\_ENTRYID

## 2.857 PidTagIsdnNumber

**Canonical name:** PidTagIsdnNumber

**Property ID:** 0x3A2D

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_ISDN\_NUMBER, PR\_ISDN\_NUMBER\_A, PR\_ISDN\_NUMBER\_W,  
urn:schemas:contacts:internationalisdnnumber

## 2.858 PidTagItemTemporaryflags

**Canonical name:** PidTagItemTemporaryflags

**Property ID:** 0x1097

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**References:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_ITEM\_TMPFLAGS

## 2.859 PidTagJunkAddRecipientsToSafeSendersList

**Canonical name:** PidTagJunkAddRecipientsToSafeSendersList

**Property ID:** 0x6103

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**References:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_JUNK\_ADD\_RECIPS\_TO\_SSL

## 2.860 PidTagJunkIncludeContacts

**Canonical name:** PidTagJunkIncludeContacts

**Property ID:** 0x6100

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**References:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_JUNK\_INCLUDE\_CONTACTS

## 2.861 PidTagJunkPermanentlyDelete

**Canonical name:** PidTagJunkPermanentlyDelete

**Property ID:** 0x6102

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**References:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_JUNK\_PERMANENTLY\_DELETE

## 2.862 PidTagJunkPhishingEnableLinks

**Canonical name:** PidTagJunkPhishingEnableLinks

**Property ID:** 0x6107

**Data type:** PtypBoolean, 0x000B

**Area:** Spam

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_JUNK\_PHISHING\_ENABLE\_LINKS



### 2.863 PidTagJunkThreshold

**Canonical name:** PidTagJunkThreshold

**Property ID:** 0x6101

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**References:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_JUNK\_THRESHOLD

### 2.864 PidTagKeyword

**Canonical name:** PidTagKeyword

**Property ID:** 0x3A0B

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_KEYWORD, PR\_KEYWORD\_A, PR\_KEYWORD\_W

### 2.865 PidTagLanguage

**Canonical name:** PidTagLanguage

**Property ID:** 0x3A0C

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_LANGUAGE, PR\_LANGUAGE\_A, PR\_LANGUAGE\_W,  
urn:schemas:contacts:language

### 2.866 PidTagLastModificationTime

**Canonical name:** PidTagLastModificationTime

**Property ID:** 0x3008

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties Property set

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_LAST\_MODIFICATION\_TIME, ptagLastModificationTime, urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

## 2.867 PidTagLastModifierEntryId

**Canonical name:** PidTagLastModifierEntryId

**Property ID:** 0x3FFB

**Data type:** PtypBinary, 0x0102

**Area:** History Properties

**References:** [\[MS-OXCMMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_ENTRYID, ptagLastModifierEntryId

## 2.868 PidTagLastModifierName

**Canonical name:** PidTagLastModifierName

**Property ID:** 0x3FFA

**Data type:** PtypString, 0x001F

**Area:** History Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_NAME, PR\_LAST\_MODIFIER\_NAME\_A, ptagLastModifierName, PR\_LAST\_MODIFIER\_NAME\_W

## 2.869 PidTagLastModifierSimpleDisplayName

**Canonical name:** PidTagLastModifierSimpleDisplayName

**Property ID:** 0x4039

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** ptagLastModifierSimpleDispName

## 2.870 PidTagLastVerbExecuted

**Canonical name:** PidTagLastVerbExecuted

**Property ID:** 0x1081

**Data type:** PtypInteger32, 0x0003

**Area:** History Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTED, ptagLastVerbExecuted

### 2.871 PidTagLastVerbExecutionTime

**Canonical name:** PidTagLastVerbExecutionTime

**Property ID:** 0x1082

**Data type:** PtypTime, 0x0040

**Area:** History Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTION\_TIME, ptagLastVerbExecutionTime

### 2.872 PidTagListHelp

**Canonical name:** PidTagListHelp

**Property ID:** 0x1043

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_HELP, PR\_LIST\_HELP\_A, PR\_LIST\_HELP\_W

### 2.873 PidTagListSubscribe

**Canonical name:** PidTagListSubscribe

**Property ID:** 0x1044

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_SUBSCRIBE, PR\_LIST\_SUBSCRIBE\_A, PR\_LIST\_SUBSCRIBE\_W

### 2.874 PidTagListUnsubscribe

**Canonical name:** PidTagListUnsubscribe

**Property ID:** 0x1045

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_UNSUBSCRIBE, PR\_LIST\_UNSUBSCRIBE\_A, PR\_LIST\_UNSUBSCRIBE\_W

## 2.875 PidTagLocalCommitTime

**Canonical name:** PidTagLocalCommitTime

**Property ID:** 0x6709

**Data type:** PtypTime, 0x0040

**Area:** Server

**References:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_LOCAL\_COMMIT\_TIME, ptagLocalCommitTime

## 2.876 PidTagLocaleId

**Canonical name:** PidTagLocaleId

**Property ID:** 0x66A1

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_LOCALE\_ID, ptagLocaleId

## 2.877 PidTagLocality

**Canonical name:** PidTagLocality

**Property ID:** 0x3A27

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#), [\[MS-EXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-EXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_LOCALITY, PR\_LOCALITY\_A, PR\_LOCALITY\_W, PR\_BUSINESS\_ADDRESS\_LOCALITY, PR\_BUSINESS\_ADDRESS\_LOCALITY\_A, PR\_BUSINESS\_ADDRESS\_LOCALITY\_W, um:schemas:contacts:mailingcity

## 2.878 PidTagLocation

**Canonical name:** PidTagLocation

**Property ID:** 0x3A0D

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-EXOABK\]](#), [\[MS-EXOCAL\]](#), [\[MS-EXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_LOCATION, PR\_LOCATION\_A, PR\_LOCATION\_W,  
urn:schemas:contacts:location

### 2.879 PidTagMailboxOwnerEntryId

**Canonical name:** PidTagMailboxOwnerEntryId

**Property ID:** 0x661B

**Data type:** PtypBinary, 0x0102

**Area:** Message Store Properties

**References:** [\[MS-OXCSTOR\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_ENTRYID, ptagMailboxOwnerEntryId

### 2.880 PidTagMailboxOwnerName

**Canonical name:** PidTagMailboxOwnerName

**Property ID:** 0x661C

**Data type:** PtypString, 0x001F

**Area:** Message Store Properties

**References:** [\[MS-OXCSTOR\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_NAME, PR\_MAILBOX\_OWNER\_NAME\_A,  
ptagMailboxOwnerName, PR\_MAILBOX\_OWNER\_NAME\_W

### 2.881 PidTagManagerName

**Canonical name:** PidTagManagerName

**Property ID:** 0x3A4E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_MANAGER\_NAME, PR\_MANAGER\_NAME\_A, PR\_MANAGER\_NAME\_W,  
urn:schemas:contacts:manager

### 2.882 PidTagMappingSignature

**Canonical name:** PidTagMappingSignature

**Property ID:** 0x0FF8

**Data type:** PtypBinary, 0x0102

**Area:** Miscellaneous Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_MAPPING\_SIGNATURE, ptagMappingSignature

### 2.883 PidTagMaximumSubmitMessageSize

**Canonical name:** PidTagMaximumSubmitMessageSize

**Property ID:** 0x666D

**Data type:** PtypInteger32, 0x0003

**Area:** Message Store Properties

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_MAX\_SUBMIT\_MESSAGE\_SIZE

### 2.884 PidTagMemberId

**Canonical name:** PidTagMemberId

**Property ID:** 0x6671

**Data type:** PtypInteger64, 0x0014

**Area:** Access Control Properties

**References:** [\[MS-OXCPerm\]](#)

**Alternate names:** PR\_MEMBER\_ID, ptagMemberId

### 2.885 PidTagMemberName

**Canonical name:** PidTagMemberName

**Property ID:** 0x6672

**Data type:** PtypString, 0x001F

**Area:** Access Control Properties

**References:** [\[MS-OXCPerm\]](#)

**Alternate names:** PR\_MEMBER\_NAME, PR\_MEMBER\_NAME\_A, ptagMemberName, PR\_MEMBER\_NAME\_W

### 2.886 PidTagMemberRights

**Canonical name:** PidTagMemberRights

**Property ID:** 0x6673

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCPerm\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_MEMBER\_RIGHTS, ptagMemberRights

## 2.887 PidTagMessageAttachments

**Canonical name:** PidTagMessageAttachments

**Property ID:** 0x0E13

**Data type:** PtypComObject, 0x000D

**Area:** Message Attachment Properties

**References:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_MESSAGE\_ATTACHMENTS, ptagMessageAttachments

## 2.888 PidTagMessageCcMe

**Canonical name:** PidTagMessageCcMe

**Property ID:** 0x0058

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_CC\_ME, ptagMessageCcMe

## 2.889 PidTagMessageClass

**Canonical name:** PidTagMessageClass

**Property ID:** 0x001A

**Data type:** PtypString, 0x001F

**Area:** Common Property set

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_MESSAGE\_CLASS, PR\_MESSAGE\_CLASS\_A, ptagMessageClass, PR\_MESSAGE\_CLASS\_W, <http://schemas.microsoft.com/exchange/outlookmessageclass><http://schemas.microsoft.com/exchange/outlookmessageclass>

## 2.890 PidTagMessageCodepage

**Canonical name:** PidTagMessageCodepage

**Property ID:** 0x3FFD

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-OXTNEF\]](#) [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXPFOAB\]](#),

**Alternate names:** PR\_MESSAGE\_CODEPAGE

## 2.891 PidTagMessageDeliveryTime

**Canonical name:** PidTagMessageDeliveryTime

**Property ID:** 0x0E06

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties Property set

**References:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORSS\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_MESSAGE\_DELIVERY\_TIME, urn:schemas:httpmail:datereceived

## 2.892 PidTagMessageEditorFormat

**Canonical name:** PidTagMessageEditorFormat

**Property ID:** 0x5909

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MSG\_EDITOR\_FORMAT, ptagMsgEditorFormat

## 2.893 PidTagMessageFlags

**Canonical name:** PidTagMessageFlags

**Property ID:** 0x0E07

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#) [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_MESSAGE\_FLAGS, ptagMessageFlags

## 2.894 PidTagMessageHandlingSystemCommonName

**Canonical name:** PidTagMessageHandlingSystemCommonName

**Property ID:** 0x3A0F



**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_MHS\_COMMON\_NAME, PR\_MHS\_COMMON\_NAME\_A, PR\_MHS\_COMMON\_NAME\_W, urn:schemas:contacts:dn

## 2.895 PidTagMessageLocaleId

**Canonical name:** PidTagMessageLocaleId

**Property ID:** 0x3FF1

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_LOCALE\_ID

## 2.896 PidTagMessageRecipientMe

**Canonical name:** PidTagMessageRecipientMe

**Property ID:** 0x0059

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIP\_ME, ptagMessageRecipMe

## 2.897 PidTagMessageRecipients

**Canonical name:** PidTagMessageRecipients

**Property ID:** 0x0E12

**Data type:** PtypComObject, 0x000D

**Area:** Address Properties

**References:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIPIENTS, ptagMessageRecipients

## 2.898 PidTagMessageSize

**Canonical name:** PidTagMessageSize

**Property ID:** 0x0E08

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE, ptagMessageSize

## 2.899 PidTagMessageSizeExtended

**Canonical name:** PidTagMessageSizeExtended

**Property ID:** 0x0E08

**Data type:** PtypInteger64, 0x0014

**Area:** General Message Properties

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE\_EXTENDED, ptagMessageSizeExtended

## 2.900 PidTagMessageStatus

**Canonical name:** PidTagMessageStatus

**Property ID:** 0x0E17

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_MSG\_STATUS, ptagMsgStatus

## 2.901 PidTagMessageSubmissionId

**Canonical name:** PidTagMessageSubmissionId

**Property ID:** 0x0047

**Data type:** PtypBinary, 0x0102

**Area:** Email

**References:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_SUBMISSION\_ID, ptagMessageSubmissionId

## 2.902 PidTagMessageToMe

**Canonical name:** PidTagMessageToMe

**Property ID:** 0x0057

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_TO\_ME, ptagMessageToMe

### 2.903 PidTagMid

**Canonical name:** PidTagMid

**Property ID:** 0x674A

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** ptagMID, <http://schemas.microsoft.com/exchange/mid>

### 2.904 PidTagMiddleName

**Canonical name:** PidTagMiddleName

**Property ID:** 0x3A44

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_MIDDLE\_NAME, PR\_MIDDLE\_NAME\_A, PR\_MIDDLE\_NAME\_W, urn:schemas:contacts:middlename

### 2.905 PidTagMimeSkeleton

**Canonical name:** PidTagMimeSkeleton

**Property ID:** 0x0470

**Data type:** PtypBinary, 0x0102

**Area:** MIME properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagMimeSkeleton

### 2.906 PidTagMobileTelephoneNumber

**Canonical name:** PidTagMobileTelephoneNumber

**Property ID:** 0x3A1C

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_MOBILE\_TELEPHONE\_NUMBER, PR\_MOBILE\_TELEPHONE\_NUMBER\_A, PR\_MOBILE\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:mobile

## 2.907 PidTagNativeBody

**Canonical name:** PidTagNativeBody

**Property ID:** 0x1016

**Data type:** PtypInteger32, 0x0003

**Area:** BestBody

**References:** [\[MS-OXBBODY\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_NATIVE\_BODY\_INFO, ptagNativeBodyInfo

## 2.908 PidTagNewAttach

**Canonical name:** PidTagNewAttach

**Property ID:** 0x4000

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagNewAttach

## 2.909 PidTagNewFXFolder

**Canonical name:** PidTagNewFXFolder

**Property ID:** 0x4011

**Data type:** PtypBinary, 0x0102

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagNewFXFolder

## 2.910 PidTagNextSendAcct

**Canonical name:** PidTagNextSendAcct

**Property ID:** 0x0E29

**Data type:** PtypString, 0x001F

**Area:**

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_NEXT\_SEND\_ACCT

### 2.911 PidTagNickname

**Canonical name:** PidTagNickname

**Property ID:** 0x3A4F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_NICKNAME, PR\_NICKNAME\_A, PR\_NICKNAME\_W, urn:schemas:contacts:nickname

### 2.912 PidTagNormalizedSubject

**Canonical name:** PidTagNormalizedSubject

**Property ID:** 0x0E1D

**Data type:** PtypString, 0x001F

**Area:** Email Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_NORMALIZED\_SUBJECT, PR\_NORMALIZED\_SUBJECT\_A, ptagNormalizedSubject, PR\_NORMALIZED\_SUBJECT\_W, urn:schemas:httpmail:normalizedsubject

### 2.913 PidTagNormalMessageSize

**Canonical name:** PidTagNormalMessageSize

**Property ID:** 0x66B3

**Data type:** PtypInteger32, 0x0003

**Area:** Server

**References:** [\[MS-OXCFOLD\]](#), [\[MS-XWDFOLD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_NORMAL\_MESSAGE\_SIZE, http://schemas.microsoft.com/exchange/foldersize

## 2.914 PidTagObjectType

**Canonical name:** PidTagObjectType

**Property ID:** 0x0FFE

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**References:** [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_OBJECT\_TYPE, ptagObjectType

## 2.915 PidTagOfficeLocation

**Canonical name:** PidTagOfficeLocation

**Property ID:** 0x3A19

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_OFFICE\_LOCATION, PR\_OFFICE\_LOCATION\_A, PR\_OFFICE\_LOCATION\_W, urn:schemas:contacts:roomnumber

## 2.916 PidTagOfflineAddressBookCompressedSize

**Canonical name:** PidTagOfflineAddressBookCompressedSize

**Property ID:** 0x6809

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_OAB\_COMPRESSED\_SIZE

## 2.917 PidTagOfflineAddressBookContainerGuid

**Canonical name:** PidTagOfflineAddressBookContainerGuid

**Property ID:** 0x6802

**Data type:** PtypString, 0x001F

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_OAB\_CONTAINER\_GUID, PR\_OAB\_CONTAINER\_GUID\_W

## 2.918 PidTagOfflineAddressBookDistinguishedName

**Canonical name:** PidTagOfflineAddressBookDistinguishedName

**Property ID:** 0x6804

**Data type:** PtypString, 0x001F

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_OAB\_DN, PR\_OAB\_DN\_W

## 2.919 PidTagOfflineAddressBookFileSize

**Canonical name:** PidTagOfflineAddressBookFileSize

**Property ID:** 0x680A

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_OAB\_FILE\_SIZE

## 2.920 PidTagOfflineAddressBookFileType

**Canonical name:** PidTagOfflineAddressBookFileType

**Property ID:** 0x6808

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_OAB\_FILETYPE

## 2.921 PidTagOfflineAddressBookLanguageId

**Canonical name:** PidTagOfflineAddressBookLanguageId

**Property ID:** 0x6807

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_OAB\_LANGID

## 2.922 PidTagOfflineAddressBookMessageClass

**Canonical name:** PidTagOfflineAddressBookMessageClass

**Property ID:** 0x6803

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**References:** [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_OAB\_MESSAGE\_CLASS

## 2.923 PidTagOfflineAddressBookName

**Canonical name:** PidTagOfflineAddressBookName

**Property ID:** 0x6800

**Data type:** PtypString, 0x001F

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_OAB\_NAME, PR\_OAB\_NAME\_W

## 2.924 PidTagOfflineAddressBookSequence

**Canonical name:** PidTagOfflineAddressBookSequence

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_OAB\_SEQUENCE

## 2.925 PidTagOfflineAddressBookShaHash

**Canonical name:** PidTagOfflineAddressBookShaHash

**Property ID:** 0x6806

**Data type:** PtypBinary, 0x0102

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_OAB\_SHA\_HASH



## 2.926 PidTagOfflineAddressBookTruncatedProperties

**Canonical name:** PidTagOfflineAddressBookTruncatedProperties

**Property ID:** 0x6805

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Offline Address Book Properties

**References:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_OAB\_TRUNCATED\_PROPS

## 2.927 PidTagOrdinalMost

**Canonical name:** PidTagOrdinalMost

**Property ID:** 0x36E2

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**References:** [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_ORDINAL\_MOST

## 2.928 PidTagOrganizationalIdNumber

**Canonical name:** PidTagOrganizationalIdNumber

**Property ID:** 0x3A10

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_ORGANIZATIONAL\_ID\_NUMBER, PR\_ORGANIZATIONAL\_ID\_NUMBER\_A, PR\_ORGANIZATIONAL\_ID\_NUMBER\_W, urn:schemas:contacts:employeenumber

## 2.929 PidTagOriginalAuthorName

**Canonical name:** PidTagOriginalAuthorName

**Property ID:** 0x004D

**Data type:** PtypString, 0x001F

**Area:** Email

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_ORIGINAL\_AUTHOR\_NAME, PR\_ORIGINAL\_AUTHOR\_NAME\_A, ptagOriginalAuthorName, PR\_ORIGINAL\_AUTHOR\_NAME\_W

## 2.930 PidTagOriginalDeliveryTime

**Canonical name:** PidTagOriginalDeliveryTime

**Property ID:** 0x0055

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_DELIVERY\_TIME, ptagOriginalDeliveryTime

## 2.931 PidTagOriginalDisplayBcc

**Canonical name:** PidTagOriginalDisplayBcc

**Property ID:** 0x0072

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_BCC, PR\_ORIGINAL\_DISPLAY\_BCC\_A, ptagOriginalDisplayBcc, PR\_ORIGINAL\_DISPLAY\_BCC\_W, <http://schemas.microsoft.com/exchange/originaldisplaybcc>

## 2.932 PidTagOriginalDisplayCc

**Canonical name:** PidTagOriginalDisplayCc

**Property ID:** 0x0073

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_CC, PR\_ORIGINAL\_DISPLAY\_CC\_A, ptagOriginalDisplayCc, PR\_ORIGINAL\_DISPLAY\_CC\_W, <http://schemas.microsoft.com/exchange/originaldisplaycc>, [http://schemas.microsoft.com/mapi/original\\_display\\_cc](http://schemas.microsoft.com/mapi/original_display_cc)

## 2.933 PidTagOriginalDisplayName

**Canonical name:** PidTagOriginalDisplayName

**Property ID:** 0x3A13

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_NAME, PR\_ORIGINAL\_DISPLAY\_NAME\_A, ptagOriginalDisplayName, PR\_ORIGINAL\_DISPLAY\_NAME\_W

### 2.934 PidTagOriginalDisplayTo

**Canonical name:** PidTagOriginalDisplayTo

**Property ID:** 0x0074

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_TO, PR\_ORIGINAL\_DISPLAY\_TO\_A, ptagOriginalDisplayTo, PR\_ORIGINAL\_DISPLAY\_TO\_W, <http://schemas.microsoft.com/exchange/originaldisplayto>, [http://schemas.microsoft.com/mapi/original\\_display\\_to](http://schemas.microsoft.com/mapi/original_display_to)

### 2.935 PidTagOriginalEntryId

**Canonical name:** PidTagOriginalEntryId

**Property ID:** 0x3A12

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXCSYNC\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_ORIGINAL\_ENTRYID, ptagOriginalEntryId

### 2.936 PidTagOriginalMessageClass

**Canonical name:** PidTagOriginalMessageClass

**Property ID:** 0x004B

**Data type:** PtypString, 0x001F

**Area:** Secure Messaging Properties

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIG\_MESSAGE\_CLASS, PR\_ORIG\_MESSAGE\_CLASS\_A, PR\_ORIG\_MESSAGE\_CLASS\_W

### 2.937 PidTagOriginalMessageId

**Canonical name:** PidTagOriginalMessageId

**Property ID:** 0x1046

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagOriginalInternetMessageID, OriginalMessageId

## 2.938 PidTagOriginalSearchKey

**Canonical name:** PidTagOriginalSearchKey

**Property ID:** 0x3A14

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXOABK\]](#)

**Alternate names:** PR\_ORIGINAL\_SEARCH\_KEY, ptagOriginalSearchKey

## 2.939 PidTagOriginalSenderAddressType

**Canonical name:** PidTagOriginalSenderAddressType

**Property ID:** 0x0066

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENDER\_ADDRTYPE, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_A, ptagOriginalSenderAddrType, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_W

## 2.940 PidTagOriginalSenderEmailAddress

**Canonical name:** PidTagOriginalSenderEmailAddress

**Property ID:** 0x0067

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_W

## 2.941 PidTagOriginalSenderEntryId

**Canonical name:** PidTagOriginalSenderEntryId

**Property ID:** 0x005B

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENDER\_ENTRYID, ptagOriginalSenderId

## 2.942 PidTagOriginalSenderName

**Canonical name:** PidTagOriginalSenderName

**Property ID:** 0x005A

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENDER\_NAME, PR\_ORIGINAL\_SENDER\_NAME\_A, ptagOriginalSenderName, PR\_ORIGINAL\_SENDER\_NAME\_W, <http://schemas.microsoft.com/exchange/originalsendername>

## 2.943 PidTagOriginalSenderSearchKey

**Canonical name:** PidTagOriginalSenderSearchKey

**Property ID:** 0x005C

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENDER\_SEARCH\_KEY, ptagOriginalSenderSearchKey

## 2.944 PidTagOriginalSensitivity

**Canonical name:** PidTagOriginalSensitivity

**Property ID:** 0x002E

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENSITIVITY, ptagOriginalSensitivity

## 2.945 PidTagOriginalSentRepresentingAddressType

**Canonical name:** PidTagOriginalSentRepresentingAddressType

**Property ID:** 0x0068

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_A, ptagOriginalSentRepresentingAddrType, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_W

## 2.946 PidTagOriginalSentRepresentingEmailAddress

**Canonical name:** PidTagOriginalSentRepresentingEmailAddress

**Property ID:** 0x0069

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.947 PidTagOriginalSentRepresentingEntryId

**Canonical name:** PidTagOriginalSentRepresentingEntryId

**Property ID:** 0x005E

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ENTRYID, ptagOriginalSentRepresentingEntryId

## 2.948 PidTagOriginalSentRepresentingName

**Canonical name:** PidTagOriginalSentRepresentingName

**Property ID:** 0x005D

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME, PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_A, ptagOriginalSentRepresentingName, PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_W

## 2.949 PidTagOriginalSentRepresentingSearchKey

**Canonical name:** PidTagOriginalSentRepresentingSearchKey

**Property ID:** 0x005F

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_SEARCH\_KEY, ptagOriginalSentRepresentingSearchKey

## 2.950 PidTagOriginalSubject

**Canonical name:** PidTagOriginalSubject

**Property ID:** 0x0049

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXCSYNC\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SUBJECT, PR\_ORIGINAL\_SUBJECT\_A, ptagOriginalSubject, PR\_ORIGINAL\_SUBJECT\_W, <http://schemas.microsoft.com/exchange/originalsubject>, [http://schemas.microsoft.com/mapi/original\\_subject](http://schemas.microsoft.com/mapi/original_subject)

## 2.951 PidTagOriginalSubmitTime

**Canonical name:** PidTagOriginalSubmitTime

**Property ID:** 0x004E

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties Property set

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINAL\_SUBMIT\_TIME, ptagOriginalSubmitTime, <http://schemas.microsoft.com/exchange/originaldate>, [http://schemas.microsoft.com/mapi/original\\_submit\\_time](http://schemas.microsoft.com/mapi/original_submit_time)

## 2.952 PidTagOriginatorDeliveryReportRequested

**Canonical name:** PidTagOriginatorDeliveryReportRequested

**Property ID:** 0x0023

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIGINATOR\_DELIVERY\_REPORT\_REQUESTED, <http://schemas.microsoft.com/exchange/deliveryreportrequested>

## 2.953 PidTagOriginatorNonDeliveryReportRequested

**Canonical name:** PidTagOriginatorNonDeliveryReportRequested

**Property ID:** 0x0C08

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ORIGINATOR\_NON\_DELIVERY\_REPORT\_REQUESTED

## 2.954 PidTagOtherAddressCity

**Canonical name:** PidTagOtherAddressCity

**Property ID:** 0x3A5F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_CITY, PR\_OTHER\_ADDRESS\_CITY\_A, PR\_OTHER\_ADDRESS\_CITY\_W, urn:schemas:contacts:othercity

## 2.955 PidTagOtherAddressCountry

**Canonical name:** PidTagOtherAddressCountry

**Property ID:** 0x3A60

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_COUNTRY, PR\_OTHER\_ADDRESS\_COUNTRY\_A, PR\_OTHER\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:othercountry

## 2.956 PidTagOtherAddressPostalCode

**Canonical name:** PidTagOtherAddressPostalCode

**Property ID:** 0x3A61

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_POSTAL\_CODE, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_A, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:otherpostalcode



## 2.957 PidTagOtherAddressPostOfficeBox

**Canonical name:** PidTagOtherAddressPostOfficeBox

**Property ID:** 0x3A64

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:otherpostofficebox

## 2.958 PidTagOtherAddressStateOrProvince

**Canonical name:** PidTagOtherAddressStateOrProvince

**Property ID:** 0x3A62

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:otherstate

## 2.959 PidTagOtherAddressStreet

**Canonical name:** PidTagOtherAddressStreet

**Property ID:** 0x3A63

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STREET, PR\_OTHER\_ADDRESS\_STREET\_A, PR\_OTHER\_ADDRESS\_STREET\_W, urn:schemas:contacts:otherstreet

## 2.960 PidTagOtherTelephoneNumber

**Canonical name:** PidTagOtherTelephoneNumber

**Property ID:** 0x3A1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_OTHER\_TELEPHONE\_NUMBER, PR\_OTHER\_TELEPHONE\_NUMBER\_A, PR\_OTHER\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:otherTelephone

## 2.961 PidTagOutOfOfficeState

**Canonical name:** PidTagOutOfOfficeState

**Property ID:** 0x661D

**Data type:** PtypBoolean, 0x000B

**Area:** Message Store Properties

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_OOF\_STATE, ptagOOFState

## 2.962 PidTagOwnerAppointmentId

**Canonical name:** PidTagOwnerAppointmentId

**Property ID:** 0x0062

**Data type:** PtypInteger32, 0x0003

**Area:** Appointment Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_OWNER\_APPT\_ID, http://schemas.microsoft.com/mapi/owner\_appt\_id

## 2.963 PidTagPagerTelephoneNumber

**Canonical name:** PidTagPagerTelephoneNumber

**Property ID:** 0x3A21

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_PAGER\_TELEPHONE\_NUMBER, PR\_PAGER\_TELEPHONE\_NUMBER\_A, PR\_PAGER\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:pager

## 2.964 PidTagParentEntryId

**Canonical name:** PidTagParentEntryId

**Property ID:** 0x0E09

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-OXCDATA\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_PARENT\_ENTRYID, ptagParentEntryId

## 2.965 PidTagParentFolderId

**Canonical name:** PidTagParentFolderId

**Property ID:** 0x6749

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagParentFID

## 2.966 PidTagParentKey

**Canonical name:** PidTagParentKey

**Property ID:** 0x0025

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**References:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_PARENT\_KEY, ptagParentKey

## 2.967 PidTagParentSourceKey

**Canonical name:** PidTagParentSourceKey

**Property ID:** 0x65E1

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_PARENT\_SOURCE\_KEY

## 2.968 PidTagPersonalHomePage

**Canonical name:** PidTagPersonalHomePage

**Property ID:** 0x3A50

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_PERSONAL\_HOME\_PAGE, PR\_PERSONAL\_HOME\_PAGE\_A, PR\_PERSONAL\_HOME\_PAGE\_W, urn:schemas:contacts:personalHomePage

## 2.969 PidTagPolicyTag

**Canonical name:** PidTagPolicyTag

**Property ID:** 0x3019

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_POLICY\_TAG, ptagPolicyTag

## 2.970 PidTagPostalAddress

**Canonical name:** PidTagPostalAddress

**Property ID:** 0x3A15

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_POSTAL\_ADDRESS, PR\_POSTAL\_ADDRESS\_A, PR\_POSTAL\_ADDRESS\_W, urn:schemas:contacts:mailingpostaladdress

## 2.971 PidTagPostalCode

**Canonical name:** PidTagPostalCode

**Property ID:** 0x3A2A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_POSTAL\_CODE, PR\_POSTAL\_CODE\_A, PR\_POSTAL\_CODE\_W, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_A, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:mailingpostalcode

## 2.972 PidTagPostOfficeBox

**Canonical name:** PidTagPostOfficeBox

**Property ID:** 0x3A2B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_POST\_OFFICE\_BOX, PR\_POST\_OFFICE\_BOX\_A, PR\_POST\_OFFICE\_BOX\_W, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:mailingpostofficebox

## 2.973 PidTagPredecessorChangeList

**Canonical name:** PidTagPredecessorChangeList

**Property ID:** 0x65E3

**Data type:** PtypBinary, 0x0102

**Area:** Sync

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_PREDECESSOR\_CHANGE\_LIST

## 2.974 PidTagPrimaryFaxNumber

**Canonical name:** PidTagPrimaryFaxNumber

**Property ID:** 0x3A23

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_PRIMARY\_FAX\_NUMBER, PR\_PRIMARY\_FAX\_NUMBER\_A, PR\_PRIMARY\_FAX\_NUMBER\_W, urn:schemas:contacts:otherfax

## 2.975 PidTagPrimarySendAccount

**Canonical name:** PidTagPrimarySendAccount

**Property ID:** 0x0E28

**Data type:** PtypString, 0x001F

**Area:** MapiNonTransmittable

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_PRIMARY\_SEND\_ACCT

## 2.976 PidTagPrimarySmtAddress

**Canonical name:** PidTagPrimarySmtAddress

**Property ID:** 0x39FE

**Data type:** PtypString, 0x001F

**Area:** MapiAddressBook

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** ptagPrimarySMTPAddress

## 2.977 PidTagPrimaryTelephoneNumber

**Canonical name:** PidTagPrimaryTelephoneNumber

**Property ID:** 0x3A1A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-NSPI\]](#)

**Alternate names:** PR\_PRIMARY\_TELEPHONE\_NUMBER, PR\_PRIMARY\_TELEPHONE\_NUMBER\_A, PR\_PRIMARY\_TELEPHONE\_NUMBER\_W

## 2.978 PidTagPriority

**Canonical name:** PidTagPriority

**Property ID:** 0x0026

**Data type:** PtypInteger32, 0x0003

**Area:** Email Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

## 2.979 PidTagProcessed

**Canonical name:** PidTagProcessed

**Property ID:** 0x7D01

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_PROCESSED

## 2.980 PidTagProfession

**Canonical name:** PidTagProfession

**Property ID:** 0x3A46

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_PROFESSION, PR\_PROFESSION\_A, PR\_PROFESSION\_W, urn:schemas:contacts:profession

### 2.981 PidTagProhibitReceiveQuota

**Canonical name:** PidTagProhibitReceiveQuota

**Property ID:** 0x666A

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange Administrative

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_PROHIBIT\_RECEIVE\_QUOTA, ptagProhibitReceiveQuota

### 2.982 PidTagProhibitSendQuota

**Canonical name:** PidTagProhibitSendQuota

**Property ID:** 0x666E

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_PROHIBIT\_SEND\_QUOTA, ptagProhibitSendQuota

### 2.983 PidTagProviderSubmitTime

**Canonical name:** PidTagProviderSubmitTime

**Property ID:** 0x0048

**Data type:** PtypTime, 0x0040

**Area:** Email

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_PROVIDER\_SUBMIT\_TIME

### 2.984 PidTagPublicFolderAdministrativeDescription

**Canonical name:** PidTagPublicFolderAdministrativeDescription

**Property ID:** 0x671C

**Data type:** PtypString, 0x001F

**Area:** Folder Properties

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

**Alternate names:** <http://schemas.microsoft.com/exchange/adminfolderdescription>

## 2.985 PidTagPublicFolderProxy

**Canonical name:** PidTagPublicFolderProxy

**Property ID:** 0x671D

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**References:** [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

**Alternate names:** <http://schemas.microsoft.com/exchange/folderproxy>

## 2.986 PidTagPurportedSenderDomain

**Canonical name:** PidTagPurportedSenderDomain

**Property ID:** 0x4083

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**References:** [\[MS-OXCMail\]](#)

**Alternate names:** PR\_PURPORTED\_SENDER\_DOMAIN

## 2.987 PidTagRadioTelephoneNumber

**Canonical name:** PidTagRadioTelephoneNumber

**Property ID:** 0x3A1D

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_RADIO\_TELEPHONE\_NUMBER, PR\_RADIO\_TELEPHONE\_NUMBER\_A, PR\_RADIO\_TELEPHONE\_NUMBER\_W

## 2.988 PidTagRead

**Canonical name:** PidTagRead

**Property ID:** 0x0E69

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCMail\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMail\]](#)



**Alternate names:** PR\_READ, ptagRead, urn:schemas:httpmail:read

## 2.989 PidTagReadReceiptAddressType

**Canonical name:** PidTagReadReceiptAddressType

**Property ID:** 0x4029

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptAddrType, ReadReceiptAddrType

## 2.990 PidTagReadReceiptEmailAddress

**Canonical name:** PidTagReadReceiptEmailAddress

**Property ID:** 0x402A

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

## 2.991 PidTagReadReceiptEntryId

**Canonical name:** PidTagReadReceiptEntryId

**Property ID:** 0x0046

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_READ\_RECEIPT\_ENTRYID, ptagReadReceiptEntryId

## 2.992 PidTagReadReceiptName

**Canonical name:** PidTagReadReceiptName

**Property ID:** 0x402B

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptDisplayName, ReadReceiptDisplayName

## 2.993 PidTagReadReceiptRequested

**Canonical name:** PidTagReadReceiptRequested

**Property ID:** 0x0029

**Data type:** PtypBoolean, 0x000B

**Area:** Email Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_READ\_RECEIPT\_REQUESTED, ptagReadReceiptRequested, <http://schemas.microsoft.com/exchange/readreceiptrequested>

## 2.994 PidTagReadReceiptSearchKey

**Canonical name:** PidTagReadReceiptSearchKey

**Property ID:** 0x0053

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_READ\_RECEIPT\_SEARCH\_KEY, ptagReadReceiptSearchKey

## 2.995 PidTagReceivedByAddressType

**Canonical name:** PidTagReceivedByAddressType

**Property ID:** 0x0075

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RECEIVED\_BY\_ADDRTYPE, PR\_RECEIVED\_BY\_ADDRTYPE\_A, ptagReceivedByAddrType, PR\_RECEIVED\_BY\_ADDRTYPE\_W

## 2.996 PidTagReceivedByEmailAddress

**Canonical name:** PidTagReceivedByEmailAddress

**Property ID:** 0x0076

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RECEIVED\_BY\_EMAIL\_ADDRESS, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_A, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_W

### 2.997 PidTagReceivedByEntryId

**Canonical name:** PidTagReceivedByEntryId

**Property ID:** 0x003F

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RECEIVED\_BY\_ENTRYID

### 2.998 PidTagReceivedByFlags

**Canonical name:** PidTagReceivedByFlags

**Property ID:** 0x401B

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** ptagRcvdByFlags

### 2.999 PidTagReceivedByName

**Canonical name:** PidTagReceivedByName

**Property ID:** 0x0040

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RECEIVED\_BY\_NAME, PR\_RECEIVED\_BY\_NAME\_A, PR\_RECEIVED\_BY\_NAME\_W

### 2.1000 PidTagReceivedBySearchKey

**Canonical name:** PidTagReceivedBySearchKey

**Property ID:** 0x0051

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RECEIVED\_BY\_SEARCH\_KEY

## 2.1001 PidTagReceivedRepresentingAddressType

**Canonical name:** PidTagReceivedRepresentingAddressType

**Property ID:** 0x0077

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RCVD\_REPRESENTING\_ADDRTYPE, PR\_RCVD\_REPRESENTING\_ADDRTYPE\_A, ptagRcvdRepresentingAddrType, PR\_RCVD\_REPRESENTING\_ADDRTYPE\_W

## 2.1002 PidTagReceivedRepresentingEmailAddress

**Canonical name:** PidTagReceivedRepresentingEmailAddress

**Property ID:** 0x0078

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS, PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.1003 PidTagReceivedRepresentingEntryId

**Canonical name:** PidTagReceivedRepresentingEntryId

**Property ID:** 0x0043

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RCVD\_REPRESENTING\_ENTRYID, ptagRcvdRepresentingEntryId

## 2.1004 PidTagReceivedRepresentingFlags

**Canonical name:** PidTagReceivedRepresentingFlags

**Property ID:** 0x401C

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** ptagRcvdRepresentingFlags

## 2.1005 PidTagReceivedRepresentingName

**Canonical name:** PidTagReceivedRepresentingName

**Property ID:** 0x0044

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RCVD\_REPRESENTING\_NAME, PR\_RCVD\_REPRESENTING\_NAME\_A, ptagRcvdRepresentingName, PR\_RCVD\_REPRESENTING\_NAME\_W

## 2.1006 PidTagReceivedRepresentingSearchKey

**Canonical name:** PidTagReceivedRepresentingSearchKey

**Property ID:** 0x0052

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RCVD\_REPRESENTING\_SEARCH\_KEY, ptagRcvdRepresentingSearchKey

## 2.1007 PidTagReceivedRepresentingSimpleDisplayName

**Canonical name:** PidTagReceivedRepresentingSimpleDisplayName

**Property ID:** 0x4035

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** ptagRcvdRepresentingSimpleDispName

## 2.1008 PidTagRecipientDisplayName

**Canonical name:** PidTagRecipientDisplayName

**Property ID:** 0x5FF6

**Data type:** PtypString, 0x001F

**Area:** TransportRecipient

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_DISPLAY\_NAME, PR\_RECIPIENT\_DISPLAY\_NAME\_W

## 2.1009 PidTagRecipientEntryId

**Canonical name:** PidTagRecipientEntryId

**Property ID:** 0x5FF7

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ENTRYID, ptagRecipientEntryId

## 2.1010 PidTagRecipientFlags

**Canonical name:** PidTagRecipientFlags

**Property ID:** 0x5FFD

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_RECIPIENT\_FLAGS

## 2.1011 PidTagRecipientOrder

**Canonical name:** PidTagRecipientOrder

**Property ID:** 0x5FDF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ORDER, ptagRecipientOrder

## 2.1012 PidTagRecipientProposed

**Canonical name:** PidTagRecipientProposed

**Property ID:** 0x5FE1

**Data type:** PtypBoolean, 0x000B

**Area:** TransportRecipient

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_RECIPIENT\_PROPOSED, ptagRecipientProposed

### 2.1013 PidTagRecipientProposedEndTime

**Canonical name:** PidTagRecipientProposedEndTime

**Property ID:** 0x5FE4

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_RECIPIENT\_PROPOSEDENDTIME, ptagRecipientProposedEndTime

### 2.1014 PidTagRecipientProposedStartTime

**Canonical name:** PidTagRecipientProposedStartTime

**Property ID:** 0x5FE3

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_RECIPIENT\_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

### 2.1015 PidTagRecipientReassignmentProhibited

**Canonical name:** PidTagRecipientReassignmentProhibited

**Property ID:** 0x002B

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_REASSIGNMENT\_PROHIBITED, ptagRecipientReassignmentProhibited

### 2.1016 PidTagRecipientResourceState

**Canonical name:** PidTagRecipientResourceState

**Property ID:** 0x5FDE

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_RESOURCESTATE

## 2.1017 PidTagRecipientTrackStatus

**Canonical name:** PidTagRecipientTrackStatus

**Property ID:** 0x5FFF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS, ptagRecipientTrackStatus

## 2.1018 PidTagRecipientTrackStatusTime

**Canonical name:** PidTagRecipientTrackStatusTime

**Property ID:** 0x5FFB

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS\_TIME, ptagRecipientTrackStatusTime

## 2.1019 PidTagRecipientType

**Canonical name:** PidTagRecipientType

**Property ID:** 0x0C15

**Data type:** PtypInteger32, 0x0003

**Area:** MapiRecipient

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_RECIPIENT\_TYPE, ptagRecipientType

## 2.1020 PidTagRecordKey

**Canonical name:** PidTagRecordKey

**Property ID:** 0x0FF9

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_RECORD\_KEY, ptagRecordKey



## 2.1021 PidTagReferredByName

**Canonical name:** PidTagReferredByName

**Property ID:** 0x3A47

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_REferred\_BY\_NAME, PR\_REferred\_BY\_NAME\_A, PR\_REferred\_BY\_NAME\_W

## 2.1022 PidTagRemindersOnlineEntryId

**Canonical name:** PidTagRemindersOnlineEntryId

**Property ID:** 0x36D5

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**References:** [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_REM\_ONLINE\_ENTRYID, ptagRemOnlineEntryId

## 2.1023 PidTagRemoteHeaderLoc

**Canonical name:** PidTagRemoteHeaderLoc

**Property ID:** 0x0078

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**References:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_REMOTE\_HEADER\_LOC

## 2.1024 PidTagRemoteMessageTransferAgent

**Canonical name:** PidTagRemoteMessageTransferAgent

**Property ID:** 0x0C21

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagDsnRemoteMta, PR\_DSN\_REMOTE\_MTA, RemoteMta

## 2.1025 PidTagRenderingPosition

**Canonical name:** PidTagRenderingPosition

**Property ID:** 0x370B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAttachment

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_RENDERING\_POSITION, ptagRenderingPosition

## 2.1026 PidTagReplyRecipientEntries

**Canonical name:** PidTagReplyRecipientEntries

**Property ID:** 0x004F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_ENTRIES, ptagReplyRecipientEntries, <http://schemas.microsoft.com/exchange/reply-to-base64>

## 2.1027 PidTagReplyRecipientNames

**Canonical name:** PidTagReplyRecipientNames

**Property ID:** 0x0050

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_NAMES, PR\_REPLY\_RECIPIENT\_NAMES\_A, ptagReplyRecipientNames, PR\_REPLY\_RECIPIENT\_NAMES\_W

## 2.1028 PidTagReplyRequested

**Canonical name:** PidTagReplyRequested

**Property ID:** 0x0C17

**Data type:** PtypBoolean, 0x000B

**Area:** MapiRecipient

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_REQUESTED, ptagReplyRequested

## 2.1029 PidTagReplyTemplateId

**Canonical name:** PidTagReplyTemplateId

**Property ID:** 0x65C2

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_REPLY\_TEMPLATE\_ID, ptagReplyTemplateId

## 2.1030 PidTagReplyTime

**Canonical name:** PidTagReplyTime

**Property ID:** 0x0030

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_TIME, urn:schemas:httpmail:reply-by, http://schemas.microsoft.com/exchange/reply-by-iso

## 2.1031 PidTagReportEntryId

**Canonical name:** PidTagReportEntryId

**Property ID:** 0x0045

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_REPORT\_ENTRYID, ptagReportEntryId

## 2.1032 PidTagReportingMessageTransferAgent

**Canonical name:** PidTagReportingMessageTransferAgent

**Property ID:** 0x6820

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagDsnReportingMta, ReportingMta

### 2.1033 PidTagReportName

**Canonical name:** PidTagReportName

**Property ID:** 0x003A

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_REPORT\_NAME, PR\_REPORT\_NAME\_A, PR\_REPORT\_NAME\_W

### 2.1034 PidTagReportSearchKey

**Canonical name:** PidTagReportSearchKey

**Property ID:** 0x0054

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_REPORT\_SEARCH\_KEY, ptagReportSearchKey

### 2.1035 PidTagReportTag

**Canonical name:** PidTagReportTag

**Property ID:** 0x0031

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_REPORT\_TAG, ptagReportTag

### 2.1036 PidTagReportText

**Canonical name:** PidTagReportText

**Property ID:** 0x1001

**Data type:** PtypString, 0x001F

**Area:** MapiMessage

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_REPORT\_TEXT, PR\_REPORT\_TEXT\_A, ptagReportText, PR\_REPORT\_TEXT\_W

## 2.1037 PidTagReportTime

**Canonical name:** PidTagReportTime

**Property ID:** 0x0032

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_REPORT\_TIME, ptagReportTime,  
<http://schemas.microsoft.com/exchange/reporttime>

## 2.1038 PidTagResolveMethod

**Canonical name:** PidTagResolveMethod

**Property ID:** 0x3FE7

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_RESOLVE\_METHOD, ptagResolveMethod

## 2.1039 PidTagResponseRequested

**Canonical name:** PidTagResponseRequested

**Property ID:** 0x0063

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_RESPONSE\_REQUESTED, urn:schemas:calendar:responserequested,  
[http://schemas.microsoft.com/mapi/response\\_requested](http://schemas.microsoft.com/mapi/response_requested)

## 2.1040 PidTagResponsibility

**Canonical name:** PidTagResponsibility

**Property ID:** 0x0E0F

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_RESPONSIBILITY, ptagResponsibility

## 2.1041 PidTagRetentionDate

**Canonical name:** PidTagRetentionDate

**Property ID:** 0x301C

**Data type:** PtypTime, 0x0040

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_RETENTION\_DATE, ptagRetentionDate

## 2.1042 PidTagRetentionFlags

**Canonical name:** PidTagRetentionFlags

**Property ID:** 0x301D

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_RETENTION\_FLAGS, ptagRetentionFlags

## 2.1043 PidTagRetentionPeriod

**Canonical name:** PidTagRetentionPeriod

**Property ID:** 0x301A

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_RETENTION\_PERIOD, ptagRetentionPeriod

## 2.1044 PidTagRights

**Canonical name:** PidTagRights

**Property ID:** 0x6639

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**References:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_RIGHTS, ptagRights

## 2.1045 PidTagRoamingDatatypes

**Canonical name:** PidTagRoamingDatatypes

**Property ID:** 0x7C06

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_ROAMING\_DATATYPES

## 2.1046 PidTagRoamingDictionary

**Canonical name:** PidTagRoamingDictionary

**Property ID:** 0x7C07

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_ROAMING\_DICTIONARY

## 2.1047 PidTagRoamingXmlStream

**Canonical name:** PidTagRoamingXmlStream

**Property ID:** 0x7C08

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_ROAMING\_XMLSTREAM

## 2.1048 PidTagRowid

**Canonical name:** PidTagRowid

**Property ID:** 0x3000

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_ROWID, ptagRowId

## 2.1049 PidTagRowType

**Canonical name:** PidTagRowType

**Property ID:** 0x0FF5

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**References:** [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_ROW\_TYPE, ptagRowType

## 2.1050 PidTagRtfCompressed

**Canonical name:** PidTagRtfCompressed

**Property ID:** 0x1009

**Data type:** PtypBinary, 0x0102

**Area:** Email

**References:** [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFCP\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_COMPRESSED, ptagRTFCompressed

## 2.1051 PidTagRtfInSync

**Canonical name:** PidTagRtfInSync

**Property ID:** 0x0E1F

**Data type:** PtypBoolean, 0x000B

**Area:** Email

**References:** [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_RTF\_IN\_SYNC, ptagRTFInSync

## 2.1052 PidTagRtfSyncBodyCount

**Canonical name:** PidTagRtfSyncBodyCount

**Property ID:** 0x1007

**Data type:** PtypInteger32, 0x0003

**Area:** MapiMessage

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_SYNC\_BODY\_COUNT, ptagRTFSyncBodyCount



## 2.1053 PidTagRtfSyncBodyCrc

**Canonical name:** PidTagRtfSyncBodyCrc

**Property ID:** 0x1006

**Data type:** PtypInteger32, 0x0003

**Area:** MapiMessage

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_SYNC\_BODY\_CRC, ptagRTFSyncBodyCRC

## 2.1054 PidTagRtfSyncBodyTag

**Canonical name:** PidTagRtfSyncBodyTag

**Property ID:** 0x1008

**Data type:** PtypString, 0x001F

**Area:** MapiMessage

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_SYNC\_BODY\_TAG, PR\_RTF\_SYNC\_BODY\_TAG\_A, ptagRTFSyncBodyTag, PR\_RTF\_SYNC\_BODY\_TAG\_W

## 2.1055 PidTagRtfSyncPrefixCount

**Canonical name:** PidTagRtfSyncPrefixCount

**Property ID:** 0x1010

**Data type:** PtypInteger32, 0x0003

**Area:** MapiMessage

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_SYNC\_PREFIX\_COUNT

## 2.1056 PidTagRtfSyncTrailingCount

**Canonical name:** PidTagRtfSyncTrailingCount

**Property ID:** 0x1011

**Data type:** PtypInteger32, 0x0003

**Area:** MapiMessage

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_SYNC\_TRAILING\_COUNT

## 2.1057 PidTagRuleActionNumber

**Canonical name:** PidTagRuleActionNumber

**Property ID:** 0x6650

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_ACTION\_NUMBER, ptagRuleActionNumber

## 2.1058 PidTagRuleActions

**Canonical name:** PidTagRuleActions

**Property ID:** 0x6680

**Data type:** PtypRuleAction, 0x00FE

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_ACTIONS, ptagRuleActions

## 2.1059 PidTagRuleActionType

**Canonical name:** PidTagRuleActionType

**Property ID:** 0x6649

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_ACTION\_TYPE, ptagRuleActionType

## 2.1060 PidTagRuleCondition

**Canonical name:** PidTagRuleCondition

**Property ID:** 0x6679

**Data type:** PtypRestriction, 0x00FD

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_CONDITION, ptagRuleCondition

## 2.1061 PidTagRuleError

**Canonical name:** PidTagRuleError

**Property ID:** 0x6648

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_ERROR, ptagRuleError

## 2.1062 PidTagRuleFolderEntryId

**Canonical name:** PidTagRuleFolderEntryId

**Property ID:** 0x6651

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageReadOnly

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_FOLDER\_ENTRYID, ptagRuleFolderEntryId

## 2.1063 PidTagRuleId

**Canonical name:** PidTagRuleId

**Property ID:** 0x6674

**Data type:** PtypInteger64, 0x0014

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_ID, ptagRuleId

## 2.1064 PidTagRuleLevel

**Canonical name:** PidTagRuleLevel

**Property ID:** 0x6683

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_LEVEL, ptagRuleLevel

## 2.1065 PidTagRuleMessageLevel

**Canonical name:** PidTagRuleMessageLevel

**Property ID:** 0x65ED

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_MSG\_LEVEL, ptagRuleMsgLevel

## 2.1066 PidTagRuleMessageName

**Canonical name:** PidTagRuleMessageName

**Property ID:** 0x65EC

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** ptagRuleMsgName

## 2.1067 PidTagRuleMessageProvider

**Canonical name:** PidTagRuleMessageProvider

**Property ID:** 0x65EB

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** ptagRuleMsgProvider

## 2.1068 PidTagRuleMessageProviderData

**Canonical name:** PidTagRuleMessageProviderData

**Property ID:** 0x65EE

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_MSG\_PROVIDER\_DATA, ptagRuleMsgProviderData

## 2.1069 PidTagRuleMessageSequence

**Canonical name:** PidTagRuleMessageSequence

**Property ID:** 0x65F3

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_MSG\_SEQUENCE, ptagRuleMsgSequence

## 2.1070 PidTagRuleMessageState

**Canonical name:** PidTagRuleMessageState

**Property ID:** 0x65E9

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_MSG\_STATE, ptagRuleMsgState

## 2.1071 PidTagRuleMessageUserFlags

**Canonical name:** PidTagRuleMessageUserFlags

**Property ID:** 0x65EA

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**References:** [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_MSG\_USER\_FLAGS, ptagRuleMsgUserFlags

## 2.1072 PidTagRuleName

**Canonical name:** PidTagRuleName

**Property ID:** 0x6682

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_NAME, PR\_RULE\_NAME\_A, ptagRuleName, PR\_RULE\_NAME\_W

## 2.1073 PidTagRuleProvider

**Canonical name:** PidTagRuleProvider

**Property ID:** 0x6681

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_PROVIDER, ptagRuleProvider, PR\_RULE\_PROVIDER\_W

## 2.1074 PidTagRuleProviderData

**Canonical name:** PidTagRuleProviderData

**Property ID:** 0x6684

**Data type:** PtypBinary, 0x0102

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_PROVIDER\_DATA, ptagRuleProviderData

## 2.1075 PidTagRuleSequence

**Canonical name:** PidTagRuleSequence

**Property ID:** 0x6676

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]-OXPROTO](#), [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_SEQUENCE, ptagRuleSequence

## 2.1076 PidTagRuleState

**Canonical name:** PidTagRuleState

**Property ID:** 0x6677

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_STATE, ptagRuleState

## 2.1077 PidTagRuleUserFlags

**Canonical name:** PidTagRuleUserFlags

**Property ID:** 0x6678

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RULE\_USER\_FLAGS, ptagRuleUserFlags

## 2.1078 PidTagRwRulesStream

**Canonical name:** PidTagRwRulesStream

**Property ID:** 0x6802

**Data type:** PtypBinary, 0x0102

**Area:** Message Class Defined Transmittable

**References:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_RW\_RULES\_STREAM

## 2.1079 PidTagScheduleInfoAppointmentTombstone

**Canonical name:** PidTagScheduleInfoAppointmentTombstone

**Property ID:** 0x686A

**Data type:** PtypBinary, 0x0102

**Area:** Free/Busy Properties

**References:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_SCHDINFO\_APPT\_TOMBSTONE

## 2.1080 PidTagScheduleInfoAutoAcceptAppointments

**Canonical name:** PidTagScheduleInfoAutoAcceptAppointments

**Property ID:** 0x686D

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**References:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_AUTO\_ACCEPT\_APPTS

## 2.1081 PidTagScheduleInfoDelegateEntryIds

**Canonical name:** PidTagScheduleInfoDelegateEntryIds

**Property ID:** 0x6845

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**References:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_ENTRYIDS

## 2.1082 PidTagScheduleInfoDelegateNames

**Canonical name:** PidTagScheduleInfoDelegateNames

**Property ID:** 0x6844

**Data type:** PtypMultipleString, 0x101F

**Area:** Free/Busy Properties

**References:** [\[MS-OXMSG\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES

## 2.1083 PidTagScheduleInfoDelegateNamesW

**Canonical name:** PidTagScheduleInfoDelegateNamesW

**Property ID:** 0x684A

**Data type:** PtypMultipleString, 0x101F

**Area:** Free/Busy Properties

**References:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES\_W, ptagDelegateNames

## 2.1084 PidTagScheduleInfoDelegatorWantsCopy

**Canonical name:** PidTagScheduleInfoDelegatorWantsCopy

**Property ID:** 0x6842

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_COPY



## 2.1085 PidTagScheduleInfoDelegatorWantsInfo

**Canonical name:** PidTagScheduleInfoDelegatorWantsInfo

**Property ID:** 0x684B

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**References:** [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_INFO

## 2.1086 PidTagScheduleInfoDisallowOverlappingAppts

**Canonical name:** PidTagScheduleInfoDisallowOverlappingAppts

**Property ID:** 0x686F

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**References:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_OVERLAPPING\_APPTS

## 2.1087 PidTagScheduleInfoDisallowRecurringAppts

**Canonical name:** PidTagScheduleInfoDisallowRecurringAppts

**Property ID:** 0x686E

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**References:** [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_RECURRING\_APPTS

## 2.1088 PidTagScheduleInfoDontMailDelegates

**Canonical name:** PidTagScheduleInfoDontMailDelegates

**Property ID:** 0x6843

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DONT\_MAIL\_DELEGATES

## 2.1089 PidTagScheduleInfoFreeBusy

**Canonical name:** PidTagScheduleInfoFreeBusy

**Property ID:** 0x686C

**Data type:** PtypBinary, 0x0102

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_FREEBUSY

## 2.1090 PidTagScheduleInfoFreeBusyAway

**Canonical name:** PidTagScheduleInfoFreeBusyAway

**Property ID:** 0x6856

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_OOF

## 2.1091 PidTagScheduleInfoFreeBusyBusy

**Canonical name:** PidTagScheduleInfoFreeBusyBusy

**Property ID:** 0x6854

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_BUSY

## 2.1092 PidTagScheduleInfoFreeBusyMerged

**Canonical name:** PidTagScheduleInfoFreeBusyMerged

**Property ID:** 0x6850

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_MERGED

## 2.1093 PidTagScheduleInfoFreeBusyTentative

**Canonical name:** PidTagScheduleInfoFreeBusyTentative

**Property ID:** 0x6852

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_TENTATIVE

## 2.1094 PidTagScheduleInfoMonthsAway

**Canonical name:** PidTagScheduleInfoMonthsAway

**Property ID:** 0x6855

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_MONTHS\_OOF

## 2.1095 PidTagScheduleInfoMonthsBusy

**Canonical name:** PidTagScheduleInfoMonthsBusy

**Property ID:** 0x6853

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**References:** [\[MS-OXMSG\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_MONTHS\_BUSY

## 2.1096 PidTagScheduleInfoMonthsMerged

**Canonical name:** PidTagScheduleInfoMonthsMerged

**Property ID:** 0x684F

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_MONTHS\_MERGED

## 2.1097 PidTagScheduleInfoMonthsTentative

**Canonical name:** PidTagScheduleInfoMonthsTentative

**Property ID:** 0x6851

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_MONTHS\_TENTATIVE

## 2.1098 PidTagScheduleInfoResourceType

**Canonical name:** PidTagScheduleInfoResourceType

**Property ID:** 0x6841

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_RESOURCE\_TYPE

## 2.1099 PidTagSchedulePlusFreeBusyEntryId

**Canonical name:** PidTagSchedulePlusFreeBusyEntryId

**Property ID:** 0x6622

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageStore

**References:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SPLUS\_FREE\_BUSY\_ENTRYID

## 2.1100 PidTagScriptData

**Canonical name:** PidTagScriptData

**Property ID:** 0x0004

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**References:** [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_EMS\_SCRIPT\_BLOB

### 2.1101 PidTagSearchFolderDefinition

**Canonical name:** PidTagSearchFolderDefinition

**Property ID:** 0x6845

**Data type:** PtypBinary, 0x0102

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_DEFINITION

### 2.1102 PidTagSearchFolderEfpFlags

**Canonical name:** PidTagSearchFolderEfpFlags

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_EFP\_FLAGS

### 2.1103 PidTagSearchFolderExpiration

**Canonical name:** PidTagSearchFolderExpiration

**Property ID:** 0x683A

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_EXPIRATION

### 2.1104 PidTagSearchFolderId

**Canonical name:** PidTagSearchFolderId

**Property ID:** 0x6842

**Data type:** PtypBinary, 0x0102

**Area:** Search

**References:** [\[MS-OXOCFG\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_ID

### 2.1105 PidTagSearchFolderLastUsed

**Canonical name:** PidTagSearchFolderLastUsed

**Property ID:** 0x6834

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_LAST\_USED

### 2.1106 PidTagSearchFolderRecreateInfo

**Canonical name:** PidTagSearchFolderRecreateInfo

**Property ID:** 0x6844

**Data type:** PtypBinary, 0x0102

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_RECREATE\_INFO

### 2.1107 PidTagSearchFolderStorageType

**Canonical name:** PidTagSearchFolderStorageType

**Property ID:** 0x6846

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_STORAGE\_TYPE

### 2.1108 PidTagSearchFolderTag

**Canonical name:** PidTagSearchFolderTag

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_TAG

## 2.1109 PidTagSearchFolderTemplateId

**Canonical name:** PidTagSearchFolderTemplateId

**Property ID:** 0x6841

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**References:** [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_WB\_SF\_TEMPLATE\_ID

## 2.1110 PidTagSearchKey

**Canonical name:** PidTagSearchKey

**Property ID:** 0x300B

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SEARCH\_KEY, ptagSearchKey

## 2.1111 PidTagSecureSubmitFlags

**Canonical name:** PidTagSecureSubmitFlags

**Property ID:** 0x65C6

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_SECURE\_SUBMIT\_FLAGS, ptagSecureSubmitFlags

## 2.1112 PidTagSecurityDescriptor

**Canonical name:** PidTagSecurityDescriptor

**Property ID:** 0x0E27

**Data type:** PtypBinary, 0x0102

**Area:** Access Control Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXCPerm\]](#), [\[MS-XWDVSEC\]](#)

**Alternate names:** PR\_NT\_SECURITY\_DESCRIPTOR

### 2.1113 PidTagSecurityDescriptorAsXml

**Canonical name:** PidTagSecurityDescriptorAsXml

**Property ID:** 0x0E6A

**Data type:** PtypString, 0x001F

**Area:** Access Control Properties Property set

**References:** [\[MS-OXCPerm\]](#), [\[MS-XWDVSEC\]](#)

**Alternate names:** PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML, PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_A, PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_W, <http://schemas.microsoft.com/exchange/security/descriptor>

### 2.1114 PidTagSelectable

**Canonical name:** PidTagSelectable

**Property ID:** 0x3609

**Data type:** PtypBoolean, 0x000B

**Area:** AB Container

**References:** [\[MS-EXOABKT\]](#)

**Alternate names:** PR\_SELECTABLE

### 2.1115 PidTagSenderAddressType

**Canonical name:** PidTagSenderAddressType

**Property ID:** 0x0C1E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** PR\_SENDER\_ADDRTYPE, PR\_SENDER\_ADDRTYPE\_A, ptagSenderAddrType, PR\_SENDER\_ADDRTYPE\_W

### 2.1116 PidTagSenderEmailAddress

**Canonical name:** PidTagSenderEmailAddress

**Property ID:** 0x0C1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXTNEF\]](#)



**Alternate names:** PR\_SENDER\_EMAIL\_ADDRESS, PR\_SENDER\_EMAIL\_ADDRESS\_A, PR\_SENDER\_EMAIL\_ADDRESS\_W

### 2.1117 PidTagSenderEntryId

**Canonical name:** PidTagSenderEntryId

**Property ID:** 0x0C19

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_ENTRYID, ptagSenderEntryId

### 2.1118 PidTagSenderFlags

**Canonical name:** PidTagSenderFlags

**Property ID:** 0x4019

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** ptagSenderFlags

### 2.1119 PidTagSenderIdStatus

**Canonical name:** PidTagSenderIdStatus

**Property ID:** 0x4079

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_SENDER\_ID\_STATUS

### 2.1120 PidTagSenderName

**Canonical name:** PidTagSenderName

**Property ID:** 0x0C1A

**Data type:** PtypString, 0x001F

**Area:** Address Properties Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXORSS\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_SENDER\_NAME, PR\_SENDER\_NAME\_A, ptagSenderName, PR\_SENDER\_NAME\_W, urn:schemas:httpmail:sendemail, http://schemas.microsoft.com/exchange/sender-name-utf8

### 2.1121 PidTagSenderSearchKey

**Canonical name:** PidTagSenderSearchKey

**Property ID:** 0x0C1D

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_SENDER\_SEARCH\_KEY, ptagSenderSearchKey

### 2.1122 PidTagSenderSimpleDisplayName

**Canonical name:** PidTagSenderSimpleDisplayName

**Property ID:** 0x4030

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** ptagSenderSimpleDispName

### 2.1123 PidTagSenderSmtpAddress

**Canonical name:** PidTagSenderSmtpAddress

**Property ID:** 0x5D01

**Data type:** PtypString, 0x001F

**Area:** Mail

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** SenderSmtpAddress, ptagSenderSmtpAddress

### 2.1124 PidTagSenderTelephoneNumber

**Canonical name:** PidTagSenderTelephoneNumber

**Property ID:** 0x6802

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaSenderTelephoneNumber

### 2.1125 PidTagSendInternetEncoding

**Canonical name:** PidTagSendInternetEncoding

**Property ID:** 0x3A71

**Data type:** PtypInteger32, 0x0003

**Area:** Address Properties

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_INTERNET\_ENCODING, ptagSendInternetEncoding

### 2.1126 PidTagSendRichInfo

**Canonical name:** PidTagSendRichInfo

**Property ID:** 0x3A40

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**References:** [\[MS-OXOAB\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_RICH\_INFO, ptagSendRichInfo

### 2.1127 PidTagSensitivity

**Canonical name:** PidTagSensitivity

**Property ID:** 0x0036

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXODOC\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_SENSITIVITY, ptagSensitivity,  
<http://schemas.microsoft.com/exchange/sensitivity-long>,  
<http://schemas.microsoft.com/exchange/sensitivity>

### 2.1128 PidTagSentMailEntryId

**Canonical name:** PidTagSentMailEntryId

**Property ID:** 0x0E0A

**Data type:** PtypBinary, 0x0102

**Area:** MapiNonTransmittable

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_SENTMAIL\_ENTRYID, ptagSentMailEntryId

### 2.1129 PidTagSentMailSvrEID

**Canonical name:** PidTagSentMailSvrEID

**Property ID:** 0x6740

**Data type:** PtypServerId, 0x00FB

**Area:** ProviderDefinedNonTransmittable

**References:** [\[MS-OXCSTOR\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** ptagSentMailSvrEID

### 2.1130 PidTagSentRepresentingAddressType

**Canonical name:** PidTagSentRepresentingAddressType

**Property ID:** 0x0064

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ADDRTYPE, PR\_SENT\_REPRESENTING\_ADDRTYPE\_A, ptagSentRepresentingAddrType, PR\_SENT\_REPRESENTING\_ADDRTYPE\_W

### 2.1131 PidTagSentRepresentingEmailAddress

**Canonical name:** PidTagSentRepresentingEmailAddress

**Property ID:** 0x0065

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W

### 2.1132 PidTagSentRepresentingEntryId

**Canonical name:** PidTagSentRepresentingEntryId

**Property ID:** 0x0041

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMail\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ENTRYID, ptagSentRepresentingEntryId

### 2.1133 PidTagSentRepresentingFlags

**Canonical name:** PidTagSentRepresentingFlags

**Property ID:** 0x401A

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** ptagSentRepresentingFlags

### 2.1134 PidTagSentRepresentingName

**Canonical name:** PidTagSentRepresentingName

**Property ID:** 0x0042

**Data type:** PtypString, 0x001F

**Area:** Address Properties Property set

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMail\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMail\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_NAME, PR\_SENT\_REPRESENTING\_NAME\_A, ptagSentRepresentingName, PR\_SENT\_REPRESENTING\_NAME\_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

### 2.1135 PidTagSentRepresentingSearchKey

**Canonical name:** PidTagSentRepresentingSearchKey

**Property ID:** 0x003B

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_SEARCH\_KEY, ptagSentRepresentingSearchKey

### 2.1136 PidTagSentRepresentingSimpleDisplayName

**Canonical name:** PidTagSentRepresentingSimpleDisplayName

**Property ID:** 0x4031

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**References:** [\[MS-OXTNEF\]](#)

**Alternate names:** ptagSentRepresentingSimpleDispName

### 2.1137 PidTagSessionInitiationProtocolUri

**Canonical name:** PidTagSessionInitiationProtocolUri

**Property ID:** 0x5FE5

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientSipUri, SipUri

### 2.1138 PidTagSmtpAddress

**Canonical name:** PidTagSmtpAddress

**Property ID:** 0x39FE

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-NSPI\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXSHARE\]](#)

**Alternate names:** PR\_SMTP\_ADDRESS, PR\_SMTP\_ADDRESS\_A, PR\_SMTP\_ADDRESS\_W

### 2.1139 PidTagSortLocaleId

**Canonical name:** PidTagSortLocaleId

**Property ID:** 0x6705

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**References:** [\[MS-OXCSTOR\]](#), [\[MS-XPFOAB\]](#)

**Alternate names:** PR\_SORT\_LOCALE\_ID, ptagSortLocaleId

### 2.1140 PidTagSourceKey

**Canonical name:** PidTagSourceKey

**Property ID:** 0x65E0

**Data type:** PtypBinary, 0x0102

**Area:** Sync

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

**Alternate names:** PR\_SOURCE\_KEY

### 2.1141 PidTagSpokenName

**Canonical name:** PidTagSpokenName

**Property ID:** 0x8CC2

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_UM\_SPOKEN\_NAME

### 2.1142 PidTagSpouseName

**Canonical name:** PidTagSpouseName

**Property ID:** 0x3A48

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_SPOUSE\_NAME, PR\_SPOUSE\_NAME\_A, PR\_SPOUSE\_NAME\_W,  
urn:schemas:contacts:spousecn

### 2.1143 PidTagStartDate

**Canonical name:** PidTagStartDate

**Property ID:** 0x0060

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_START\_DATE, [http://schemas.microsoft.com/mapi/start\\_date](http://schemas.microsoft.com/mapi/start_date)

### 2.1144 PidTagStartDateEtc

**Canonical name:** PidTagStartDateEtc

**Property ID:** 0x301B

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**References:** [MS-OXCMSG](#)

**Alternate names:** PR\_START\_DATE\_ETC, ptagStartDateEtc

### 2.1145 PidTagStartEmbed

**Canonical name:** PidTagStartEmbed

**Property ID:** 0x4001

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagStartEmbed

### 2.1146 PidTagStartFAIMsg

**Canonical name:** PidTagStartFAIMsg

**Property ID:** 0x4010

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagStartFAIMsg

### 2.1147 PidTagStartMessage

**Canonical name:** PidTagStartMessage

**Property ID:** 0x400C

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagStartMessage

### 2.1148 PidTagStartRecip

**Canonical name:** PidTagStartRecip

**Property ID:** 0x4003

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope



**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagStartRecip

### 2.1149 PidTagStartSubFld

**Canonical name:** PidTagStartSubFld

**Property ID:** 0x400A

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagStartSubFld

### 2.1150 PidTagStartTopFld

**Canonical name:** PidTagStartTopFld

**Property ID:** 0x4009

**Data type:** PtypInteger32, 0x0003

**Area:** TransportEnvelope

**References:** [\[MS-OXCFXICS\]](#)

**Alternate names:** ptagStartTopFld

### 2.1151 PidTagStateOrProvince

**Canonical name:** PidTagStateOrProvince

**Property ID:** 0x3A28

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_STATE\_OR\_PROVINCE, PR\_STATE\_OR\_PROVINCE\_A, PR\_STATE\_OR\_PROVINCE\_W, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_W, um:schemas:contacts:mailingstate

### 2.1152 PidTagStoreEntryId

**Canonical name:** PidTagStoreEntryId

**Property ID:** 0x0FFB

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-OXOFLAG\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_STORE\_ENTRYID, ptagStoreEntryId

### 2.1153 PidTagStoreState

**Canonical name:** PidTagStoreState

**Property ID:** 0x340E

**Data type:** PtypInteger32, 0x0003

**Area:** MapiMessageStore

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_STORE\_STATE

### 2.1154 PidTagStoreSupportMask

**Canonical name:** PidTagStoreSupportMask

**Property ID:** 0x340D

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_STORE\_SUPPORT\_MASK, ptagStoreSupportMask

### 2.1155 PidTagStreetAddress

**Canonical name:** PidTagStreetAddress

**Property ID:** 0x3A29

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_STREET\_ADDRESS, PR\_STREET\_ADDRESS\_A, PR\_STREET\_ADDRESS\_W, PR\_BUSINESS\_ADDRESS\_STREET, PR\_BUSINESS\_ADDRESS\_STREET\_A, PR\_BUSINESS\_ADDRESS\_STREET\_W, urn:schemas:contacts:mailingstreet

### 2.1156 PidTagSubfolder

**Canonical name:** PidTagSubfolder

**Property ID:** 0x6708

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeAdministrative Property set

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

**Alternate names:** PR\_SUBFOLDER, ptagSubfolder, DAV:isfolder

## 2.1157 PidTagSubfolders

**Canonical name:** PidTagSubfolders

**Property ID:** 0x360A

**Data type:** PtypBoolean, 0x000B

**Area:** MapiContainer

**References:** [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-XWDFOLD\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_SUBFOLDERS, ptagSubFolders, DAV:hassubs

## 2.1158 PidTagSubject

**Canonical name:** PidTagSubject

**Property ID:** 0x0037

**Data type:** PtypString, 0x001F

**Area:** General Message Properties Property set

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_SUBJECT, PR\_SUBJECT\_A, ptagSubject, PR\_SUBJECT\_W, urn:schemas:httpmail:subject, http://schemas.microsoft.com/exchange/subject-utf8

## 2.1159 PidTagSubjectPrefix

**Canonical name:** PidTagSubjectPrefix

**Property ID:** 0x003D

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SUBJECT\_PREFIX, PR\_SUBJECT\_PREFIX\_A, ptagSubjectPrefix, PR\_SUBJECT\_PREFIX\_W

### 2.1160 PidTagSubmitFlags

**Canonical name:** PidTagSubmitFlags

**Property ID:** 0x0E14

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**References:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_SUBMIT\_FLAGS, ptagSubmitFlags

### 2.1161 PidTagSurname

**Canonical name:** PidTagSurname

**Property ID:** 0x3A11

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_SURNAME, PR\_SURNAME\_A, PR\_SURNAME\_W, urn:schemas:contacts:sn

### 2.1162 PidTagSwappedToDoData

**Canonical name:** PidTagSwappedToDoData

**Property ID:** 0x0E2D

**Data type:** PtypBinary, 0x0102

**Area:** MapiNonTransmittable

**References:** [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_DATA, ptagSwappedToDoData

### 2.1163 PidTagSwappedToDoStore

**Canonical name:** PidTagSwappedToDoStore

**Property ID:** 0x0E2C

**Data type:** PtypBinary, 0x0102

**Area:** MapiNonTransmittable

**References:** [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_STORE, ptagSwappedToDoStore

### 2.1164 PidTagTargetEntryId

**Canonical name:** PidTagTargetEntryId

**Property ID:** 0x3010

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCRPC\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_TARGET\_ENTRYID, ptagTargetEntryId

### 2.1165 PidTagTcvConstLongOne

**Canonical name:** PidTagTcvConstLongOne

**Property ID:** 0x8008

**Data type:** PtypInteger32, 0x0003

**Area:** PST Internal

**References:** [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_TCV\_CONST\_LONG\_ONE

### 2.1166 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Canonical name:** PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Property ID:** 0x3A4B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_TTYTDD\_PHONE\_NUMBER, PR\_TTYTDD\_PHONE\_NUMBER\_A, PR\_TTYTDD\_PHONE\_NUMBER\_W, urn:schemas:contacts:tytdphone

### 2.1167 PidTagTelexNumber

**Canonical name:** PidTagTelexNumber

**Property ID:** 0x3A2C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_TELEX\_NUMBER, PR\_TELEX\_NUMBER\_A, PR\_TELEX\_NUMBER\_W, urn:schemas:contacts:telexnumber

## 2.1168 PidTagTemplateData

**Canonical name:** PidTagTemplateData

**Property ID:** 0x0001

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**References:** [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_EMS\_TEMPLATE\_BLOB

## 2.1169 PidTagTemplateid

**Canonical name:** PidTagTemplateid

**Property ID:** 0x3902

**Data type:** PtypBinary, 0x0102

**Area:** MapiAddressBook

**References:** [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_TEMPLATEID

## 2.1170 PidTagTemporaryDefaultDocument

**Canonical name:** PidTagTemporaryDefaultDocument

**Property ID:** 0x3F20

**Data type:** PtypString, 0x001F

**Area:** Structured Documents Property set

**References:** [\[MS-XWDSTRUCTDOC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** DAV:defaultdocument

## 2.1171 PidTagTextAttachmentCharset

**Canonical name:** PidTagTextAttachmentCharset

**Property ID:** 0x371B

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagTextAttachmentCharset

## 2.1172 PidTagThumbnailPhoto

**Canonical name:** PidTagThumbnailPhoto

**Property ID:** 0x8C9E

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**References:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_EMS\_AB\_THUMBNAIL\_PHOTO

## 2.1173 PidTagTitle

**Canonical name:** PidTagTitle

**Property ID:** 0x3A17

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**References:** [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_TITLE, PR\_TITLE\_A, PR\_TITLE\_W, urn:schemas:contacts:title

## 2.1174 PidTagTnefCorrelationKey

**Canonical name:** PidTagTnefCorrelationKey

**Property ID:** 0x007F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_TNEF\_CORRELATION\_KEY

## 2.1175 PidTagToDoItemFlags

**Canonical name:** PidTagToDoItemFlags

**Property ID:** 0x0E2B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_TODO\_ITEM\_FLAGS, ptagToDoItemFlags

## 2.1176 PidTagTransmittableDisplayName

**Canonical name:** PidTagTransmittableDisplayName

**Property ID:** 0x3A20

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**References:** [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_TRANSMITABLE\_DISPLAY\_NAME, PR\_TRANSMITABLE\_DISPLAY\_NAME\_A, ptagTransmittableDisplayName, PR\_TRANSMITABLE\_DISPLAY\_NAME\_W

## 2.1177 PidTagTransportMessageHeaders

**Canonical name:** PidTagTransportMessageHeaders

**Property ID:** 0x007D

**Data type:** PtypString, 0x001F

**Area:** EMail

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_TRANSPORT\_MESSAGE\_HEADERS, PR\_TRANSPORT\_MESSAGE\_HEADERS\_A, PR\_TRANSPORT\_MESSAGE\_HEADERS\_W

## 2.1178 PidTagTrustSender

**Canonical name:** PidTagTrustSender

**Property ID:** 0x0E79

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_TRUST\_SENDER, ptagTrustSender

## 2.1179 PidTagTtyTddPhoneNumber

**Canonical name:** PidTagTtyTddPhoneNumber

**Property ID:** 0x3A4B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**References:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TTYTDD\_PHONE\_NUMBER



## 2.1180 PidTagUrlCompName

**Canonical name:** PidTagUrlCompName

**Property ID:** 0x10F3

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**References:** [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_URL\_COMP\_NAME, PR\_URL\_COMP\_NAME\_A, PR\_URL\_COMP\_NAME\_W, ptagURLCompName

## 2.1181 PidTagUrlCompNameSet

**Canonical name:** PidTagUrlCompNameSet

**Property ID:** 0x0E62

**Data type:** PtypBoolean, 0x000B

**Area:** ID Properties

**References:** [\[MS-OXCMSG\]](#)

**Alternate names:** ptagURLCompNameSet

## 2.1182 PidTagUrlName

**Canonical name:** PidTagUrlName

**Property ID:** 0x6707

**Data type:** PtypString, 0x001F

**Area:** ExchangeAdministrative Property set

**References:** [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

**Alternate names:** PR\_URL\_NAME, PR\_URL\_NAME\_A, PR\_URL\_NAME\_W, ptagURLName, DAV:href

## 2.1183 PidTagUserCertificate

**Canonical name:** PidTagUserCertificate

**Property ID:** 0x3A22

**Data type:** PtypBinary, 0x0102

**Area:** MapiMailUser

**References:** [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#), [\[MS-XWDCNTC\]](#)

**Alternate names:** PR\_USER\_CERTIFICATE, ptagUserCertificate, urn:schemas:contacts:usercertificate

## 2.1184 PidTagUserEntryId

**Canonical name:** PidTagUserEntryId

**Property ID:** 0x6619

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageStore

**References:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_USER\_ENTRYID, ptagUserEntryId

## 2.1185 PidTagUserX509Certificate

**Canonical name:** PidTagUserX509Certificate

**Property ID:** 0x3A70

**Data type:** PtypMultipleBinary, 0x1102

**Area:** MapiMailUser

**References:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_USER\_X509\_CERTIFICATE

## 2.1186 PidTagViewDescriptorBinary

**Canonical name:** PidTagViewDescriptorBinary

**Property ID:** 0x7001

**Data type:** PtypBinary, 0x0102

**Area:** MessageClassDefinedTransmittable

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_BINARY

## 2.1187 PidTagViewDescriptorName

**Canonical name:** PidTagViewDescriptorName

**Property ID:** 0x7006

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_NAME, PR\_VD\_NAME\_W

## 2.1188 PidTagViewDescriptorStrings

**Canonical name:** PidTagViewDescriptorStrings

**Property ID:** 0x7002

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_STRINGS, PR\_VD\_STRINGS\_W

## 2.1189 PidTagViewDescriptorVersion

**Canonical name:** PidTagViewDescriptorVersion

**Property ID:** 0x7007

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_VERSION

## 2.1190 PidTagVoiceMessageAttachmentOrder

**Canonical name:** PidTagVoiceMessageAttachmentOrder

**Property ID:** 0x6805

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#), [\[MS-OXOUM\]](#)

**Alternate names:** InternalSchemaVoiceMessageAttachmentOrder

## 2.1191 PidTagVoiceMessageDuration

**Canonical name:** PidTagVoiceMessageDuration

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageDuration

## 2.1192 PidTagVoiceMessageSenderName

**Canonical name:** PidTagVoiceMessageSenderName

**Property ID:** 0x6803

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**References:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageSenderName

## 2.1193 PidTagWeddingAnniversary

**Canonical name:** PidTagWeddingAnniversary

**Property ID:** 0x3A41

**Data type:** PtypTime, 0x0040

**Area:** MapiMailUser

**References:** [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

**Alternate names:** PR\_WEDDING\_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

## 2.1194 PidTagWlinkAddressBookEID

**Canonical name:** PidTagWlinkAddressBookEID

**Property ID:** 0x6854

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_ABEID PROP\_TAG

## 2.1195 PidTagWlinkAddressBookStoreEID

**Canonical name:** PidTagWlinkAddressBookStoreEID

**Property ID:** 0x6891

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_AB\_EXSTOREEID PROP\_TAG

## 2.1196 PidTagWlinkCalendarColor

**Canonical name:** PidTagWlinkCalendarColor

**Property ID:** 0x6853

**Data type:** PtypInteger32, 0x0003

**Area:** MS-OXOCFG

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_CALENDAR\_COLOR\_PROP\_TAG

## 2.1197 PidTagWlinkClientID

**Canonical name:** PidTagWlinkClientID

**Property ID:** 0x6890

**Data type:** PtypGuid, 0x0048

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_CLIENTID\_PROP\_TAG

## 2.1198 PidTagWlinkEntryId

**Canonical name:** PidTagWlinkEntryId

**Property ID:** 0x684C

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_ENTRYID\_PROP\_TAG

## 2.1199 PidTagWlinkFlags

**Canonical name:** PidTagWlinkFlags

**Property ID:** 0x684A

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_FLAGS\_PROP\_TAG

## 2.1200 PidTagWlinkFolderType

**Canonical name:** PidTagWlinkFolderType

**Property ID:** 0x684F

**Data type:** PtypGuid, 0x0048

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_FOLDER\_TYPE: PROP\_TAG

## 2.1201 PidTagWlinkGroupClsid

**Canonical name:** PidTagWlinkGroupClsid

**Property ID:** 0x6850

**Data type:** PtypGuid, 0x0048

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_GROUP\_CLSID PROP\_TAG

## 2.1202 PidTagWlinkGroupHeaderID

**Canonical name:** PidTagWlinkGroupHeaderID

**Property ID:** 0x6842

**Data type:** PtypGuid, 0x0048

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WB\_SF\_ID PROP\_TAG

## 2.1203 PidTagWlinkGroupName

**Canonical name:** PidTagWlinkGroupName

**Property ID:** 0x6851

**Data type:** PtypString, 0x001F

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_GROUP\_NAME PROP\_TAG

## 2.1204 PidTagWlinkOrdinal

**Canonical name:** PidTagWlinkOrdinal

**Property ID:** 0x684B

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_ORDINAL PROP\_TAG

## 2.1205 PidTagWlinkRecordKey

**Canonical name:** PidTagWlinkRecordKey

**Property ID:** 0x684D

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_RECKEY PROP\_TAG

## 2.1206 PidTagWlinkROGroupType

**Canonical name:** PidTagWlinkROGroupType

**Property ID:** 0x6892

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_RO\_GROUP\_TYPE PROP\_TAG

## 2.1207 PidTagWlinkSaveStamp

**Canonical name:** PidTagWlinkSaveStamp

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WB\_SF\_TAG PROP\_TAG

## 2.1208 PidTagWlinkSection

**Canonical name:** PidTagWlinkSection

**Property ID:** 0x6852

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_SECTION PROP\_TAG

## 2.1209 PidTagWlinkStoreEntryId

**Canonical name:** PidTagWlinkStoreEntryId

**Property ID:** 0x684E

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_STORE\_ENTRYID PROP\_TAG

## 2.1210 PidTagWlinkType

**Canonical name:** PidTagWlinkType

**Property ID:** 0x6849

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**References:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WLINK\_TYPE PROP\_TAG



### 3 Structure Examples

None.

## 4 Security Considerations

There are no security considerations unique to this specification.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following product versions. References to product versions include released service packs.

- Microsoft Office Outlook 2003
- Microsoft Exchange Server 2003
- Microsoft Office Outlook 2007
- Microsoft Exchange Server 2007
- Microsoft Outlook 2010
- Microsoft Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

## 6 Change Tracking

This section identifies changes made to [MS-OXPROPS] protocol documentation between November 2009 and February 2010 releases. Changes are classed as major, minor, or editorial.

**Major** changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- A protocol is deprecated.
- The removal of a document from the documentation set.
- Changes made for template compliance.

**Minor** changes do not affect protocol interoperability or implementation. Examples are updates to fix technical accuracy or ambiguity at the sentence, paragraph, or table level.

**Editorial** changes apply to grammatical, formatting, and style issues.

**No changes** means that the document is identical to its last release.

Major and minor changes can be described further using the following revision types:

- New content added.
- Content update.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.

- Content removed for template compliance.
- Obsolete document removed.

Editorial changes always have the revision type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

**Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.

**Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

Changes are listed in the following table. If you need further information, please contact [protocol@microsoft.com](mailto:protocol@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
<a href="#">2 Structures</a>	54768 The following properties were removed from this document because they no longer appear in a defining document: PidLidEmail1EmailType , PidLidEmail2EntryId, PidLidEmail3EntryId	Y	Content removed .
<a href="#">2.60 PidLidClientIntent</a>	54453 Added new property.	Y	New content added.
<a href="#">2.595 PidTagAddressBookContainerId</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.597 PidTagAddressBookDisplayNamePrintable</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.598 PidTagAddressBookDisplayTypeExtended</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
<a href="#">2.604 PidTagAddressBookExtensionAttribute1</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.605 PidTagAddressBookExtensionAttribute15</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.606 PidTagAddressBookFolderPathname</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.607 PidTagAddressBookHierarchicalChildDepartments</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.608 PidTagAddressBookHierarchicalDepartmentMembers</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.609 PidTagAddressBookHierarchicalIsHierarchicalGroup</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.610 PidTagAddressBookHierarchicalParentDepartment</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.611 PidTagAddressBookHierarchicalRootDepartment</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
	Book".		
<a href="#">2.612 PidTagAddressBookHierarchicalShowInDepartments</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.613 PidTagAddressBookHomeMessageDatabase</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.614 PidTagAddressBookIsMaster</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.615 PidTagAddressBookIsMemberOfDistributionList</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.616 PidTagAddressBookManageDistributionList</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.617 PidTagAddressBookManager</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.618 PidTagAddressBookManagerDistinguishedName</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.619 PidTagAddressBookMember</a>	50453 Updated Area information from	N	Content update.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
	"Exchange Address Book" to "Address Book".		
<a href="#">2.622</a> <a href="#">PidTagAddressBookNetworkAddress</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.623</a> <a href="#">PidTagAddressBookObjectDistinguishedName</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.624</a> <a href="#">PidTagAddressBookObjectGuid</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.625</a> <a href="#">PidTagAddressBookOrganizationalUnitRootDistinguishedName</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.626</a> <a href="#">PidTagAddressBookOwner</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.627</a> <a href="#">PidTagAddressBookOwnerBackLink</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.628</a> <a href="#">PidTagAddressBookParentEntryId</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.629</a>	50453	N	Content



Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
<a href="#">PidTagAddressBookPhoneticCompanyName</a>	Updated Area information from "Exchange Address Book" to "Address Book".		update.
2.630 <a href="#">PidTagAddressBookPhoneticDepartmentName</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
2.631 <a href="#">PidTagAddressBookPhoneticDisplayName</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
2.632 <a href="#">PidTagAddressBookPhoneticGivenName</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
2.633 <a href="#">PidTagAddressBookPhoneticSurname</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
2.634 <a href="#">PidTagAddressBookProxyAddresses</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
2.635 <a href="#">PidTagAddressBookPublicDelegates</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
2.636 <a href="#">PidTagAddressBookReports</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
<a href="#">2.637</a> <a href="#">PidTagAddressBookRoomCapacity</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.638</a> <a href="#">PidTagAddressBookRoomContainers</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.639</a> <a href="#">PidTagAddressBookRoomDescription</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.642</a> <a href="#">PidTagAddressBookTargetAddress</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.644</a> <a href="#">PidTagAddressBookX509Certificate</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.664</a> <a href="#">PidTagAttachLongFilename</a>	53147 Added reference to [MS-OXTNEF].	N	Content update.
<a href="#">2.697</a> <a href="#">PidTagCallId</a>	54170 Removed "properties" from area name.	N	Content update.
<a href="#">2.774</a> <a href="#">PidTagFaxNumberOfPages</a>	54170 Removed "properties" from area name.	N	Content update.
<a href="#">2.1065</a> <a href="#">PidTagRuleMessageLevel</a>	50878 Updated property and canonical name.	N	Content update.
<a href="#">2.1066</a> <a href="#">PidTagRuleMessageName</a>	50878 Updated property and	N	Content update.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
	canonical name.		
<a href="#">2.1067</a> <a href="#">PidTagRuleMessageProvider</a>	50878 Updated property and canonical name.	N	Content update.
<a href="#">2.1068</a> <a href="#">PidTagRuleMessageProviderData</a>	50878 Updated property and canonical name.	N	Content update.
<a href="#">2.1069</a> <a href="#">PidTagRuleMessageSequence</a>	50878 Updated property and canonical name.	N	Content update.
<a href="#">2.1071</a> <a href="#">PidTagRuleMessageUserFlags</a>	50878 Updated property and canonical name.	N	Content update.
<a href="#">2.1100</a> <a href="#">PidTagScriptData</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.1124</a> <a href="#">PidTagSenderTelephoneNumber</a>	54170 Removed "properties" from area name.	N	Content update.
<a href="#">2.1168</a> <a href="#">PidTagTemplateData</a>	50453 Updated Area information from "Exchange Address Book" to "Address Book".	N	Content update.
<a href="#">2.1190</a> <a href="#">PidTagVoiceMessageAttachmentOrder</a>	54170 Removed "properties" from area name.	N	Content update.
<a href="#">2.1191</a> <a href="#">PidTagVoiceMessageDuration</a>	54170 Removed "properties" from area name.	N	Content update.
<a href="#">2.1192</a> <a href="#">PidTagVoiceMessageSenderName</a>	54170 Removed "properties" from area name.	N	Content update.

## 7 Index

### A

[Applicability](#) 35

### C

[Change tracking](#) 380

### F

[Fields - vendor-extensible](#) 35

### G

[Glossary](#) 27

### I

[Implementer - security considerations](#) 378

[Introduction](#) 27

### N

[Normative references](#) 27

### O

[Overview](#) 30

### P

[Product behavior](#) 379

### R

References

[normative](#) 27

[Relationship to protocols and other structures](#) 35

### S

[Security - implementer considerations](#) 378

### T

[Tracking changes](#) 380

### V

[Vendor-extensible fields](#) 35