

[MS-OXPROPS]: Exchange Server Protocols Master Property List

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft's Open Specification Promise (available here: <http://www.microsoft.com/interop/osp>) or the Community Promise (available here: <http://www.microsoft.com/interop/cp/default.mspx>). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Updated references to reflect date of initial release.
09/03/2008	1.02		Changed title of document.
10/01/2008	1.03		Revised and edited technical content.
12/03/2008	1.04		Revised and edited technical content.
02/04/2009	1.05		Revised and edited technical content.
03/04/2009	1.06		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	5.0.0	Major	Updated and revised the technical content.
05/05/2010	6.0.0	Major	Updated and revised the technical content.

Table of Contents

1	Introduction	27
1.1	Glossary	27
1.2	References	27
1.2.1	Normative References	27
1.2.2	Informative References	30
1.3	Overview	30
1.3.1	Common Message Classes	31
1.3.2	Commonly Used Property Sets	32
1.3.3	Property ID Ranges	33
1.3.4	WebDAV Property Naming	34
1.3.4.1	http://schemas.microsoft.com/mapi/proptag Namespace	34
1.3.4.2	http://schemas.microsoft.com/mapi/id Namespace	34
1.3.4.3	http://schemas.microsoft.com/mapi/string Namespace	35
1.4	Relationship to Protocols and Other Structures	35
1.5	Applicability Statement	35
1.6	Versioning and Localization	35
1.7	Vendor-Extensible Fields	35
2	Structures	36
2.1	PidLidAddressBookProviderArrayType	36
2.2	PidLidAddressBookProviderEmailList	36
2.3	PidLidAddressCountryCode	36
2.4	PidLidAgingDontAgeMe	37
2.5	PidLidAllAttendeesList	37
2.6	PidLidAllAttendeesString	37
2.7	PidLidAllowExternalCheck	38
2.8	PidLidAnniversaryEventEntryId	38
2.9	PidLidAppointmentAuxiliaryFlags	38
2.10	PidLidAppointmentColor	38
2.11	PidLidAppointmentCounterProposal	39
2.12	PidLidAppointmentDuration	39
2.13	PidLidAppointmentEndDate	40
2.14	PidLidAppointmentEndTime	40
2.15	PidLidAppointmentEndWhole	40
2.16	PidLidAppointmentLastSequence	41
2.17	PidLidAppointmentMessageClass	41
2.18	PidLidAppointmentNotAllowPropose	41
2.19	PidLidAppointmentProposalNumber	42
2.20	PidLidAppointmentProposedDuration	42
2.21	PidLidAppointmentProposedEndWhole	42
2.22	PidLidAppointmentProposedStartWhole	43
2.23	PidLidAppointmentRecur	43
2.24	PidLidAppointmentReplyName	43
2.25	PidLidAppointmentReplyTime	44
2.26	PidLidAppointmentSequence	44
2.27	PidLidAppointmentSequenceTime	45
2.28	PidLidAppointmentStartDate	45
2.29	PidLidAppointmentStartTime	45
2.30	PidLidAppointmentStartWhole	46
2.31	PidLidAppointmentStateFlags	46

2.32	PidLidAppointmentSubType	46
2.33	PidLidAppointmentTimeZoneDefinitionEndDisplay	47
2.34	PidLidAppointmentTimeZoneDefinitionRecur	47
2.35	PidLidAppointmentTimeZoneDefinitionStartDisplay	48
2.36	PidLidAppointmentUnsendableRecipients	48
2.37	PidLidAppointmentUpdateTime	48
2.38	PidLidAttendeeCriticalChange	49
2.39	PidLidAutoFillLocation	49
2.40	PidLidAutoLog	49
2.41	PidLidAutoProcessState	50
2.42	PidLidAutoStartCheck	50
2.43	PidLidAutoStartWhen	50
2.44	PidLidBilling	51
2.45	PidLidBirthdayEventEntryId	51
2.46	PidLidBirthdayLocal	51
2.47	PidLidBusinessCardCardPicture	52
2.48	PidLidBusinessCardDisplayDefinition	52
2.49	PidLidBusyStatus	52
2.50	PidLidCalendarType	53
2.51	PidLidCategories	53
2.52	PidLidCcAttendeesString	53
2.53	PidLidChangeHighlight	54
2.54	PidLidClassification	54
2.55	PidLidClassificationDescription	54
2.56	PidLidClassificationGuid	55
2.57	PidLidClassificationKeep	55
2.58	PidLidClassified	55
2.59	PidLidCleanGlobalObjectId	55
2.60	PidLidClientIntent	56
2.61	PidLidClipEnd	56
2.62	PidLidClipStart	56
2.63	PidLidCollaborateDoc	57
2.64	PidLidCommonEnd	57
2.65	PidLidCommonStart	57
2.66	PidLidCompanies	58
2.67	PidLidConferencingCheck	58
2.68	PidLidConferencingType	58
2.69	PidLidContactCharacterSet	59
2.70	PidLidContactItemData	59
2.71	PidLidContactLinkEntry	59
2.72	PidLidContactLinkName	60
2.73	PidLidContactLinkSearchKey	60
2.74	PidLidContacts	60
2.75	PidLidContactUserField1	61
2.76	PidLidContactUserField2	61
2.77	PidLidContactUserField3	61
2.78	PidLidContactUserField4	62
2.79	PidLidConversationActionLastAppliedTime	62
2.80	PidLidConversationActionMaxDeliveryTime	63
2.81	PidLidConversationActionMoveFolderEid	63
2.82	PidLidConversationActionMoveStoreEid	63
2.83	PidLidConversationActionVersion	64
2.84	PidLidConversationProcessed	64

2.85	PidLidCurrentVersion	64
2.86	PidLidCurrentVersionName	65
2.87	PidLidDayInterval	65
2.88	PidLidDayOfMonth	65
2.89	PidLidDelegateMail	66
2.90	PidLidDepartment	66
2.91	PidLidDirectory	66
2.92	PidLidDistributionListChecksum	67
2.93	PidLidDistributionListMembers	67
2.94	PidLidDistributionListName	67
2.95	PidLidDistributionListOneOffMembers	68
2.96	PidLidDistributionListStream	68
2.97	PidLidEmail1AddressType	68
2.98	PidLidEmail1DisplayName	69
2.99	PidLidEmail1EmailAddress	69
2.100	PidLidEmail1OriginalDisplayName	69
2.101	PidLidEmail1OriginalEntryId	70
2.102	PidLidEmail1RichTextFormat	70
2.103	PidLidEmail2AddressType	70
2.104	PidLidEmail2DisplayName	71
2.105	PidLidEmail2EmailAddress	71
2.106	PidLidEmail2OriginalDisplayName	71
2.107	PidLidEmail2OriginalEntryId	72
2.108	PidLidEmail2RichTextFormat	72
2.109	PidLidEmail3AddressType	72
2.110	PidLidEmail3DisplayName	73
2.111	PidLidEmail3EmailAddress	73
2.112	PidLidEmail3OriginalDisplayName	73
2.113	PidLidEmail3OriginalEntryId	74
2.114	PidLidEmail3RichTextFormat	74
2.115	PidLidEmailList	74
2.116	PidLidEndRecurrenceDate	74
2.117	PidLidEndRecurrenceTime	75
2.118	PidLidExceptionReplaceTime	75
2.119	PidLidFax1AddressType	76
2.120	PidLidFax1EmailAddress	76
2.121	PidLidFax1OriginalDisplayName	76
2.122	PidLidFax1OriginalEntryId	77
2.123	PidLidFax2AddressType	77
2.124	PidLidFax2EmailAddress	77
2.125	PidLidFax2OriginalDisplayName	78
2.126	PidLidFax2OriginalEntryId	78
2.127	PidLidFax3AddressType	78
2.128	PidLidFax3EmailAddress	79
2.129	PidLidFax3OriginalDisplayName	79
2.130	PidLidFax3OriginalEntryId	79
2.131	PidLidFExceptionalAttendees	80
2.132	PidLidFExceptionalBody	80
2.133	PidLidFileUnder	80
2.134	PidLidFileUnderId	81
2.135	PidLidFileUnderList	81
2.136	PidLidFInvited	81
2.137	PidLidFlagRequest	82

2.138	PidLidFlagString	82
2.139	PidLidForwardInstance	83
2.140	PidLidForwardNotificationRecipients	83
2.141	PidLidFOthersAppointment.....	83
2.142	PidLidFreeBusyLocation	84
2.143	PidLidGlobalObjectId.....	84
2.144	PidLidHasPicture.....	84
2.145	PidLidHomeAddress	85
2.146	PidLidHomeAddressCountryCode	85
2.147	PidLidHtml.....	85
2.148	PidLidICalendarDayOfWeekMask	86
2.149	PidLidInboundICalStream	86
2.150	PidLidInfoPathFormName	86
2.151	PidLidInstantMessagingAddress.....	86
2.152	PidLidIntendedBusyStatus	87
2.153	PidLidInternetAccountName	87
2.154	PidLidInternetAccountStamp.....	88
2.155	PidLidIsException	88
2.156	PidLidIsRecurring	88
2.157	PidLidIsSilent.....	89
2.158	PidLidLinkedTaskItems.....	89
2.159	PidLidLocation.....	89
2.160	PidLidLogDocumentPosted	90
2.161	PidLidLogDocumentPrinted	90
2.162	PidLidLogDocumentRouted	90
2.163	PidLidLogDocumentSaved	91
2.164	PidLidLogDuration	91
2.165	PidLidLogEnd	91
2.166	PidLidLogFlags	92
2.167	PidLidLogStart	92
2.168	PidLidLogType.....	92
2.169	PidLidLogTypeDesc.....	93
2.170	PidLidMeetingType.....	93
2.171	PidLidMeetingWorkspaceUrl	93
2.172	PidLidMonthInterval.....	94
2.173	PidLidMonthOfYear	94
2.174	PidLidMonthOfYearMask	95
2.175	PidLidNetShowUrl.....	95
2.176	PidLidNoEndDateFlag	95
2.177	PidLidNonSendableBcc	96
2.178	PidLidNonSendableCc.....	96
2.179	PidLidNonSendableTo.....	96
2.180	PidLidNonSendBccTrackStatus	97
2.181	PidLidNonSendCcTrackStatus.....	97
2.182	PidLidNonSendToTrackStatus.....	97
2.183	PidLidNoteColor.....	98
2.184	PidLidNoteHeight.....	98
2.185	PidLidNoteWidth.....	98
2.186	PidLidNoteX.....	99
2.187	PidLidNoteY	99
2.188	PidLidOccurrences	99
2.189	PidLidOldLocation	100
2.190	PidLidOldRecurrenceType	100

2.191	PidLidOldWhenEndWhole	101
2.192	PidLidOldWhenStartWhole	101
2.193	PidLidOnlinePassword	101
2.194	PidLidOptionalAttendees.....	102
2.195	PidLidOrganizerAlias	102
2.196	PidLidOriginalStoreEntryId.....	102
2.197	PidLidOtherAddress	103
2.198	PidLidOtherAddressCountryCode	103
2.199	PidLidOwnerCriticalChange	103
2.200	PidLidOwnerName	104
2.201	PidLidPercentComplete.....	104
2.202	PidLidPostalAddressId	104
2.203	PidLidPostRssChannel	105
2.204	PidLidPostRssChannelLink.....	105
2.205	PidLidPostRssItemGuid.....	106
2.206	PidLidPostRssItemHash	106
2.207	PidLidPostRssItemLink	106
2.208	PidLidPostRssItemXml.....	107
2.209	PidLidPostRssSubscription	107
2.210	PidLidPrivate.....	107
2.211	PidLidPromptSendUpdate	108
2.212	PidLidRecurrenceDuration.....	108
2.213	PidLidRecurrencePattern.....	108
2.214	PidLidRecurrenceType	109
2.215	PidLidRecurring	109
2.216	PidLidReferenceEntryId	110
2.217	PidLidReferredBy	110
2.218	PidLidReminderDelta.....	110
2.219	PidLidReminderFileParameter.....	111
2.220	PidLidReminderOverride	111
2.221	PidLidReminderPlaySound	111
2.222	PidLidReminderSet	112
2.223	PidLidReminderSignalTime	112
2.224	PidLidReminderTime	112
2.225	PidLidReminderTimeDate.....	113
2.226	PidLidReminderTimeTime	113
2.227	PidLidReminderType	114
2.228	PidLidRemoteStatus.....	114
2.229	PidLidRequiredAttendees	114
2.230	PidLidResourceAttendees.....	115
2.231	PidLidResponseStatus	115
2.232	PidLidSendMeetingAsIcal	115
2.233	PidLidServerProcessed	116
2.234	PidLidServerProcessingActions	116
2.235	PidLidSharingAnonymity.....	116
2.236	PidLidSharingBindingEntryId.....	117
2.237	PidLidSharingBrowseUrl	117
2.238	PidLidSharingCapabilities.....	117
2.239	PidLidSharingConfigurationUrl.....	118
2.240	PidLidSharingDataRangeEnd	118
2.241	PidLidSharingDataRangeStart	118
2.242	PidLidSharingDetail	118
2.243	PidLidSharingExtensionXml.....	119

2.244	PidLidSharingFilter	119
2.245	PidLidSharingFlags	119
2.246	PidLidSharingFlavor	120
2.247	PidLidSharingFolderEntryId	120
2.248	PidLidSharingIndexEntryId	120
2.249	PidLidSharingInitiatorEntryId	120
2.250	PidLidSharingInitiatorName	121
2.251	PidLidSharingInitiatorSmtpt	121
2.252	PidLidSharingInstanceGuid	121
2.253	PidLidSharingLastAutoSyncTime	122
2.254	PidLidSharingLastSyncTime	122
2.255	PidLidSharingLocalComment	122
2.256	PidLidSharingLocalLastModificationTime	123
2.257	PidLidSharingLocalName	123
2.258	PidLidSharingLocalPath	123
2.259	PidLidSharingLocalStoreUid	123
2.260	PidLidSharingLocalType	124
2.261	PidLidSharingLocalUid	124
2.262	PidLidSharingOriginalMessageEntryId	124
2.263	PidLidSharingParentBindingEntryId	125
2.264	PidLidSharingParticipants	125
2.265	PidLidSharingPermissions	125
2.266	PidLidSharingProviderExtension	125
2.267	PidLidSharingProviderGuid	126
2.268	PidLidSharingProviderName	126
2.269	PidLidSharingProviderUrl	126
2.270	PidLidSharingRangeEnd	127
2.271	PidLidSharingRangeStart	127
2.272	PidLidSharingReciprocation	127
2.273	PidLidSharingRemoteByteSize	128
2.274	PidLidSharingRemoteComment	128
2.275	PidLidSharingRemoteCrc	128
2.276	PidLidSharingRemoteLastModificationTime	128
2.277	PidLidSharingRemoteMessageCount	129
2.278	PidLidSharingRemoteName	129
2.279	PidLidSharingRemotePass	129
2.280	PidLidSharingRemotePath	130
2.281	PidLidSharingRemoteStoreUid	130
2.282	PidLidSharingRemoteType	130
2.283	PidLidSharingRemoteUid	131
2.284	PidLidSharingRemoteUser	131
2.285	PidLidSharingRemoteVersion	131
2.286	PidLidSharingResponseTime	131
2.287	PidLidSharingResponseType	132
2.288	PidLidSharingRoamLog	132
2.289	PidLidSharingStart	132
2.290	PidLidSharingStatus	133
2.291	PidLidSharingStop	133
2.292	PidLidSharingSyncFlags	133
2.293	PidLidSharingSyncInterval	134
2.294	PidLidSharingTimeToLive	134
2.295	PidLidSharingTimeToLiveAuto	134
2.296	PidLidSharingWorkingHoursDays	134

2.297	PidLidSharingWorkingHoursEnd	135
2.298	PidLidSharingWorkingHoursStart	135
2.299	PidLidSharingWorkingHoursTimeZone	135
2.300	PidLidSideEffects	135
2.301	PidLidSingleBodyICal	136
2.302	PidLidSingleInvite	136
2.303	PidLidSmartNoAttach	136
2.304	PidLidSpamOriginalFolder	137
2.305	PidLidStartRecurrenceDate	137
2.306	PidLidStartRecurrenceTime	137
2.307	PidLidTaskAcceptanceState	138
2.308	PidLidTaskAccepted	138
2.309	PidLidTaskActualEffort	139
2.310	PidLidTaskAssigner	139
2.311	PidLidTaskAssigners	139
2.312	PidLidTaskComplete	140
2.313	PidLidTaskCustomFlags	140
2.314	PidLidTaskDateCompleted	140
2.315	PidLidTaskDeadOccurrence	141
2.316	PidLidTaskDueDate	141
2.317	PidLidTaskEstimatedEffort	141
2.318	PidLidTaskFCreator	142
2.319	PidLidTaskFFixOffline	142
2.320	PidLidTaskFRecurring	142
2.321	PidLidTaskGlobalId	143
2.322	PidLidTaskHistory	143
2.323	PidLidTaskLastDelegate	143
2.324	PidLidTaskLastUpdate	144
2.325	PidLidTaskLastUser	144
2.326	PidLidTaskMode	144
2.327	PidLidTaskMultipleRecipients	145
2.328	PidLidTaskNoCompute	145
2.329	PidLidTaskOrdinal	145
2.330	PidLidTaskOwner	146
2.331	PidLidTaskOwnership	146
2.332	PidLidTaskRecurrence	146
2.333	PidLidTaskResetReminder	147
2.334	PidLidTaskRole	147
2.335	PidLidTaskStartDate	147
2.336	PidLidTaskState	148
2.337	PidLidTaskStatus	148
2.338	PidLidTaskStatusOnComplete	148
2.339	PidLidTaskUpdates	149
2.340	PidLidTaskVersion	149
2.341	PidLidTeamTask	149
2.342	PidLidTimeZone	150
2.343	PidLidTimeZoneDescription	150
2.344	PidLidTimeZoneStruct	150
2.345	PidLidToAttendeesString	151
2.346	PidLidToDoOrdinalDate	151
2.347	PidLidToDoSubOrdinal	151
2.348	PidLidToDoTitle	152
2.349	PidLidTrustRecipientHighlights	152

2.350	PidLidUseTnef	152
2.351	PidLidValidFlagStringProof	153
2.352	PidLidVerbResponse.....	153
2.353	PidLidVerbStream.....	154
2.354	PidLidWeddingAnniversaryLocal	154
2.355	PidLidWeekInterval.....	154
2.356	PidLidWhere	155
2.357	PidLidWorkAddress	155
2.358	PidLidWorkAddressCity.....	155
2.359	PidLidWorkAddressCountry	156
2.360	PidLidWorkAddressCountryCode	156
2.361	PidLidWorkAddressPostalCode.....	156
2.362	PidLidWorkAddressPostOfficeBox	157
2.363	PidLidWorkAddressState.....	157
2.364	PidLidWorkAddressStreet	158
2.365	PidLidYearInterval	158
2.366	PidLidYomiCompanyName	158
2.367	PidLidYomiFirstName	159
2.368	PidLidYomiLastName.....	159
2.369	PidNameAcceptLanguage	159
2.370	PidNameApplicationName	160
2.371	PidNameApproved	160
2.372	PidNameApprovalAllowedDecisionMakers.....	160
2.373	PidNameApprovalRequestor.....	161
2.374	PidNameAttachmentMacContentType	161
2.375	PidNameAttachmentMacInfo	161
2.376	PidNameAudioNotes	161
2.377	PidNameAuthor	162
2.378	PidNameAuthenticatedAs.....	162
2.379	PidNameAuthenticatedDomain	162
2.380	PidNameAuthenticatedMechanism	163
2.381	PidNameAuthenticatedSource	163
2.382	PidNameAutomaticSpeechRecognitionData	163
2.383	PidNameBcc	163
2.384	PidNameByteCount.....	164
2.385	PidNameCalendarAttendeeRole	164
2.386	PidNameCalendarBusystatus.....	164
2.387	PidNameCalendarContact	165
2.388	PidNameCalendarContactUrl	165
2.389	PidNameCalendarCreated	165
2.390	PidNameCalendarDescriptionUrl	166
2.391	PidNameCalendarDuration	166
2.392	PidNameCalendarExceptionDate.....	166
2.393	PidNameCalendarExceptionRule	166
2.394	PidNameCalendarGeoLatitude	167
2.395	PidNameCalendarGeoLongitude.....	167
2.396	PidNameCalendarInstanceType	167
2.397	PidNameCalendarIsOrganizer.....	168
2.398	PidNameCalendarLastModified	168
2.399	PidNameCalendarLocationUrl	168
2.400	PidNameCalendarMeetingStatus	169
2.401	PidNameCalendarMethod.....	169
2.402	PidNameCalendarProductId	169

2.403	PidNameCalendarRecurrenceIdRange.....	170
2.404	PidNameCalendarReminderOffset	170
2.405	PidNameCalendarResources.....	170
2.406	PidNameCalendarRsvp	171
2.407	PidNameCalendarSequence	171
2.408	PidNameCalendarTimeZone	171
2.409	PidNameCalendarTimeZoneId	171
2.410	PidNameCalendarTransparent	172
2.411	PidNameCalendarUid	172
2.412	PidNameCalendarVersion	172
2.413	PidNameCategory.....	173
2.414	PidNameCc.....	173
2.415	PidNameCharacterCount	173
2.416	PidNameComments	174
2.417	PidNameCompany	174
2.418	PidNameContactsAlternateRecipient.....	174
2.419	PidNameContactsCountry	175
2.420	PidNameContactsEmail1.....	175
2.421	PidNameContactsEmail2.....	175
2.422	PidNameContactsEmail3.....	175
2.423	PidNameContactsFileAs	176
2.424	PidNameContactsFileasId	176
2.425	PidNameContactsHomeLatitude.....	176
2.426	PidNameContactsHomeLongitude	176
2.427	PidNameContactsHomeTimeZone	177
2.428	PidNameContactsMapUrl	177
2.429	PidNameContactsOtherCountryCode	177
2.430	PidNameContactsOtherPager	178
2.431	PidNameContactsOtherTimeZone	178
2.432	PidNameContactsProxyAddresses	178
2.433	PidNameContactsSecretaryUrl.....	178
2.434	PidNameContactsSourceUrl.....	179
2.435	PidNameContentBase.....	179
2.436	PidNameContentClass	179
2.437	PidNameContentDisposition	180
2.438	PidNameContentID	180
2.439	PidNameContentLanguage.....	180
2.440	PidNameContentLocation.....	180
2.441	PidNameContentTransferEncoding	181
2.442	PidNameContentType.....	181
2.443	PidNameControl	181
2.444	PidNameCreateDateTimeReadOnly	182
2.445	PidNameCrossReference.....	182
2.446	PidNameDavGetContentType	182
2.447	PidNameDavId	183
2.448	PidNameDavIsCollection.....	183
2.449	PidNameDavIsStructuredDocument	183
2.450	PidNameDavParentName.....	184
2.451	PidNameDavResourceType	184
2.452	PidNameDavSearchRequest.....	184
2.453	PidNameDavSearchType	184
2.454	PidNameDavUid	185
2.455	PidNameDisposition	185

2.456	PidNameDispositionNotificationTo	185
2.457	PidNameDistribution	186
2.458	PidNameDocumentParts	186
2.459	PidNameEditTime	186
2.460	PidNameExchangeIntendedBusyStatus	187
2.461	PidNameExchangeJunkEmailMoveStamp	187
2.462	PidNameExchangeModifyExceptionStructure	187
2.463	PidNameExchangeMsexchembdefaultmailfolder	187
2.464	PidNameExchangeMsexchembdefaultmailfoldertype	188
2.465	PidNameExchangeNoModifyExceptions	188
2.466	PidNameExchangePatternEnd	188
2.467	PidNameExchangePatternStart	189
2.468	PidNameExchangePublicFolderEmailAddress	189
2.469	PidNameExchangeReminderInterval	189
2.470	PidNameExchDatabaseSchema	190
2.471	PidNameExchDataExpectedContentClass	190
2.472	PidNameExchDataSchemaCollectionReference	190
2.473	PidNameExpires	191
2.474	PidNameExpiryDate	191
2.475	PidNameFollowupTo	191
2.476	PidNameFrom	191
2.477	PidNameHeadingPairs	192
2.478	PidNameHiddenCount	192
2.479	PidNameHttpmailCalendar	192
2.480	PidNameHttpmailCc	193
2.481	PidNameHttpmailContacts	193
2.482	PidNameHttpmailContentMediaType	193
2.483	PidNameHttpmailFrom	194
2.484	PidNameHttpmailFromEmail	194
2.485	PidNameHttpmailHtmlDescription	194
2.486	PidNameHttpmailOutbox	194
2.487	PidNameHttpmailSendMessage	195
2.488	PidNameHttpmailSubmitted	195
2.489	PidNameHttpmailTo	195
2.490	PidNameICalendarRecurrenceDate	196
2.491	PidNameICalendarRecurrenceRule	196
2.492	PidNameImportance	196
2.493	PidNameInReplyTo	197
2.494	PidNameInstantMessagingAddress2	197
2.495	PidNameInstantMessagingAddress3	197
2.496	PidNameInternetComment	197
2.497	PidNameInternetKeywords	198
2.498	PidNameInternetSubject	198
2.499	PidNameKeywords	198
2.500	PidNameLastAuthor	199
2.501	PidNameLastPrinted	199
2.502	PidNameLastSaveDateTime	199
2.503	PidNameLineCount	200
2.504	PidNameLines	200
2.505	PidNameLinksDirty	200
2.506	PidNameLocationUrl	201
2.507	PidNameMailSubmissionUri	201
2.508	PidNameManager	201

2.509	PidNameMessageId	201
2.510	PidNameMimeVersion	202
2.511	PidNameMultimediaClipCount	202
2.512	PidNameNewsgroups	202
2.513	PidNameNntpPostingHost	203
2.514	PidNameNoteCount	203
2.515	PidNameOMSAccountGuid	203
2.516	PidNameOMSMobileModel	204
2.517	PidNameOMSScheduleTime	204
2.518	PidNameOMSServiceType	204
2.519	PidNameOMSSourceType	205
2.520	PidNameOrganization	205
2.521	PidNameOriginalRecipient	205
2.522	PidNameOriginalSpamConfidenceLevel	205
2.523	PidNameOutlookProtectionRuleOverridden	206
2.524	PidNameOutlookProtectionRuleTimestamp	206
2.525	PidNameOutlookProtectionRuleVersion	206
2.526	PidNamePageCount	207
2.527	PidNameParagraphCount	207
2.528	PidNamePath	207
2.529	PidNamePhishingStamp	207
2.530	PidNamePostingVersion	208
2.531	PidNamePresentationFormat	208
2.532	PidNamePriority	208
2.533	PidNameQuarantineOriginalSender	209
2.534	PidNameReceived	209
2.535	PidNameReferences	209
2.536	PidNameRelayVersion	210
2.537	PidNameReplyBy	210
2.538	PidNameReplyTo	210
2.539	PidNameReturnPath	210
2.540	PidNameReturnReceiptTo	211
2.541	PidNameRevisionNumber	211
2.542	PidNameRightsManagementLicense	211
2.543	PidNameRightsProtectMessage	212
2.544	PidNameScale	212
2.545	PidNameSecurity	212
2.546	PidNameSender	213
2.547	PidNameSensitivity	213
2.548	PidNameSlideCount	213
2.549	PidNameSubject	214
2.550	PidNameSummary	214
2.551	PidNameTemplate	214
2.552	PidNameThreadIndex	214
2.553	PidNameThreadTopic	215
2.554	PidNameThumbnail	215
2.555	PidNameTitle	215
2.556	PidNameTo	216
2.557	PidNameWordCount	216
2.558	PidNameXCallId	216
2.559	PidNameXFaxNumberOfPages	217
2.560	PidNameXMailer	217
2.561	PidNameXMessageCompleted	217

2.562	PidNameXMessageFlag.....	217
2.563	PidNameXRequireProtectedPlayOnPhone	218
2.564	PidNameXSenderTelephoneNumber	218
2.565	PidNameXSharingBrowseUrl	218
2.566	PidNameXSharingCapabilities.....	219
2.567	PidNameXSharingConfigUrl.....	219
2.568	PidNameXSharingExendedCaps	219
2.569	PidNameXSharingFlavor	219
2.570	PidNameXSharingInstanceGuid	220
2.571	PidNameXSharingLocalType.....	220
2.572	PidNameXSharingProviderGuid.....	220
2.573	PidNameXSharingProviderName	221
2.574	PidNameXSharingProviderUrl	221
2.575	PidNameXSharingRemoteName	221
2.576	PidNameXSharingRemotePath.....	222
2.577	PidNameXSharingRemoteStoreUid.....	222
2.578	PidNameXSharingRemoteType	222
2.579	PidNameXSharingRemoteUid	222
2.580	PidNameXUnifiedMessagingPartnerAssignedId.....	223
2.581	PidNameXUnifiedMessagingPartnerContent	223
2.582	PidNameXUnifiedMessagingPartnerContext	223
2.583	PidNameXUnifiedMessagingPartnerStatus	224
2.584	PidNameXUnsent.....	224
2.585	PidNameXVoiceMessageAttachmentOrder.....	224
2.586	PidNameXVoiceMessageDuration	224
2.587	PidNameXVoiceMessageSenderName	225
2.588	PidTag7BitDisplayName	225
2.589	PidTagAccess	225
2.590	PidTagAccessLevel.....	226
2.591	PidTagAccount	226
2.592	PidTagAdditionalRenEntryIds	226
2.593	PidTagAdditionalRenEntryIdsEx.....	226
2.594	PidTagAddressBookAuthorizedSenders	227
2.595	PidTagAddressBookContainerId	227
2.596	PidTagAddressBookDeliveryContentLength	227
2.597	PidTagAddressBookDisplayNamePrintable.....	228
2.598	PidTagAddressBookDisplayTypeExtended	228
2.599	PidTagAddressBookDistributionListExternalMemberCount	228
2.600	PidTagAddressBookDistributionListMemberCount	228
2.601	PidTagAddressBookDistributionListMemberSubmitAccepted	229
2.602	PidTagAddressBookDistributionListMemberSubmitRejected	229
2.603	PidTagAddressBookEntryId	229
2.604	PidTagAddressBookExtensionAttribute1	230
2.605	PidTagAddressBookExtensionAttribute15	230
2.606	PidTagAddressBookFolderPathname.....	230
2.607	PidTagAddressBookHierarchicalChildDepartments.....	230
2.608	PidTagAddressBookHierarchicalDepartmentMembers	231
2.609	PidTagAddressBookHierarchicalIsHierarchicalGroup	231
2.610	PidTagAddressBookHierarchicalParentDepartment	231
2.611	PidTagAddressBookHierarchicalRootDepartment.....	232
2.612	PidTagAddressBookHierarchicalShowInDepartments	232
2.613	PidTagAddressBookHomeMessageDatabase	232
2.614	PidTagAddressBookIsMaster	232

2.615	PidTagAddressBookIsMemberOfDistributionList	233
2.616	PidTagAddressBookManageDistributionList	233
2.617	PidTagAddressBookManager	233
2.618	PidTagAddressBookManagerDistinguishedName	234
2.619	PidTagAddressBookMember	234
2.620	PidTagAddressBookMessageId	234
2.621	PidTagAddressBookModerationEnabled.....	234
2.622	PidTagAddressBookNetworkAddress	235
2.623	PidTagAddressBookObjectDistinguishedName	235
2.624	PidTagAddressBookObjectGuid	235
2.625	PidTagAddressBookOrganizationalUnitRootDistinguishedName	236
2.626	PidTagAddressBookOwner	236
2.627	PidTagAddressBookOwnerBackLink.....	236
2.628	PidTagAddressBookParentEntryId	236
2.629	PidTagAddressBookPhoneticCompanyName	237
2.630	PidTagAddressBookPhoneticDepartmentName.....	237
2.631	PidTagAddressBookPhoneticDisplayName	237
2.632	PidTagAddressBookPhoneticGivenName	238
2.633	PidTagAddressBookPhoneticSurname	238
2.634	PidTagAddressBookProxyAddresses	238
2.635	PidTagAddressBookPublicDelegates	238
2.636	PidTagAddressBookReports	239
2.637	PidTagAddressBookRoomCapacity	239
2.638	PidTagAddressBookRoomContainers	239
2.639	PidTagAddressBookRoomDescription.....	240
2.640	PidTagAddressBookSenderHintTranslations.....	240
2.641	PidTagAddressBookSeniorityIndex	240
2.642	PidTagAddressBookTargetAddress	240
2.643	PidTagAddressBookUnauthorizedSenders	241
2.644	PidTagAddressBookX509Certificate.....	241
2.645	PidTagAddressType	241
2.646	PidTagAlternateRecipientAllowed	242
2.647	PidTagAnr	242
2.648	PidTagArchiveDate	242
2.649	PidTagArchivePeriod	242
2.650	PidTagArchiveTag	243
2.651	PidTagAssistant.....	243
2.652	PidTagAssistantTelephoneNumber	243
2.653	PidTagAssociated	244
2.654	PidTagAttachAdditionalInformation	244
2.655	PidTagAttachContentBase.....	244
2.656	PidTagAttachContentId	244
2.657	PidTagAttachContentLocation.....	245
2.658	PidTagAttachDataBinary	245
2.659	PidTagAttachDataObject.....	245
2.660	PidTagAttachEncoding	246
2.661	PidTagAttachExtension.....	246
2.662	PidTagAttachFilename	246
2.663	PidTagAttachFlags	247
2.664	PidTagAttachLongFilename	247
2.665	PidTagAttachLongPathname.....	247
2.666	PidTagAttachmentContactPhoto	247
2.667	PidTagAttachmentFlags	248

2.668	PidTagAttachmentHidden	248
2.669	PidTagAttachmentLinkId	248
2.670	PidTagAttachMethod	249
2.671	PidTagAttachMimeType	249
2.672	PidTagAttachNumber	249
2.673	PidTagAttachPathname	249
2.674	PidTagAttachPayloadClass	250
2.675	PidTagAttachPayloadProviderGuidString	250
2.676	PidTagAttachRendering	250
2.677	PidTagAttachSize	251
2.678	PidTagAttachTag	251
2.679	PidTagAttachTransportName.....	251
2.680	PidTagAttributeHidden	251
2.681	PidTagAttributeReadOnly.....	252
2.682	PidTagAttributeSystem.....	252
2.683	PidTagAutoForwarded	252
2.684	PidTagAutoResponseSuppress.....	252
2.685	PidTagBirthday	253
2.686	PidTagBlockStatus.....	253
2.687	PidTagBody	253
2.688	PidTagBodyContentId	254
2.689	PidTagBodyContentLocation.....	254
2.690	PidTagBodyHtml.....	254
2.691	PidTagBusiness2TelephoneNumber.....	254
2.692	PidTagBusiness2TelephoneNumberS	255
2.693	PidTagBusinessFaxNumber	255
2.694	PidTagBusinessHomePage	255
2.695	PidTagBusinessTelephoneNumber.....	256
2.696	PidTagCallbackTelephoneNumber	256
2.697	PidTagCallId	256
2.698	PidTagCarTelephoneNumber	256
2.699	PidTagCdoRecurrenceid	257
2.700	PidTagChangeKey.....	257
2.701	PidTagChangeNotificationGuid.....	257
2.702	PidTagChangeNumber.....	257
2.703	PidTagChildrensNames.....	258
2.704	PidTagClientActions	258
2.705	PidTagClientSubmitTime	258
2.706	PidTagCnsetRead	259
2.707	PidTagCnsetSeen	259
2.708	PidTagCnsetSeenFAI.....	259
2.709	PidTagCodePageId.....	260
2.710	PidTagComment.....	260
2.711	PidTagCompanyMainTelephoneNumber	260
2.712	PidTagCompanyName	260
2.713	PidTagComputerNetworkName.....	261
2.714	PidTagConflictEntryId	261
2.715	PidTagConflictItems	261
2.716	PidTagContainerClass	261
2.717	PidTagContainerContents	262
2.718	PidTagContainerFlags.....	262
2.719	PidTagContainerHierarchy	262
2.720	PidTagContentCount	263

2.721	PidTagContentFilterPhishingConfidenceLevel	263
2.722	PidTagContentFilterSpamConfidenceLevel	263
2.723	PidTagContentUnreadCount	263
2.724	PidTagConversationId	264
2.725	PidTagConversationIndex	264
2.726	PidTagConversationIndexTracking	264
2.727	PidTagConversationTopic	265
2.728	PidTagCountry	265
2.729	PidTagCreationTime	265
2.730	PidTagCreatorEntryId	265
2.731	PidTagCreatorName	266
2.732	PidTagCreatorSimpleDisplayName	266
2.733	PidTagCustomerId	266
2.734	PidTagDamBackPatched	267
2.735	PidTagDamOriginalEntryId	267
2.736	PidTagDefaultPostMessageClass	267
2.737	PidTagDeferredDeliveryTime	267
2.738	PidTagDeferredSendNumber	268
2.739	PidTagDeferredSendTime	268
2.740	PidTagDeferredSendUnits	268
2.741	PidTagDelegatedByRule	268
2.742	PidTagDelegateFlags	269
2.743	PidTagDeleteAfterSubmit	269
2.744	PidTagDeletedOn	269
2.745	PidTagDepartmentName	269
2.746	PidTagDepth	270
2.747	PidTagDisplayBcc	270
2.748	PidTagDisplayCc	270
2.749	PidTagDisplayName	271
2.750	PidTagDisplayNamePrefix	271
2.751	PidTagDisplayTo	271
2.752	PidTagDisplayType	272
2.753	PidTagDisplayTypeEx	272
2.754	PidTagEcWarning	272
2.755	PidTagEmailAddress	272
2.756	PidTagEndAttach	273
2.757	PidTagEndDate	273
2.758	PidTagEndEmbed	273
2.759	PidTagEndFolder	274
2.760	PidTagEndMessage	274
2.761	PidTagEndToRecip	274
2.762	PidTagEntryId	274
2.763	PidTagExceptionEndTime	275
2.764	PidTagExceptionReplaceTime	275
2.765	PidTagExceptionStartTime	275
2.766	PidTagExchangeNTSecurityDescriptor	275
2.767	PidTagExpiryNumber	276
2.768	PidTagExpiryTime	276
2.769	PidTagExpiryUnits	276
2.770	PidTagExtendedFolderFlags	277
2.771	PidTagExtendedRuleMessageActions	277
2.772	PidTagExtendedRuleMessageCondition	277
2.773	PidTagExtendedRuleSizeLimit	277

2.774	PidTagFaxNumberOfPages	278
2.775	PidTagFlagCompleteTime	278
2.776	PidTagFlagStatus	278
2.777	PidTagFlatUrlName	278
2.778	PidTagFolderAssociatedContents	279
2.779	PidTagFolderId	279
2.780	PidTagFolderType	279
2.781	PidTagFollowupIcon	279
2.782	PidTagFreeBusyCountMonths	280
2.783	PidTagFreeBusyEntryIds	280
2.784	PidTagFreeBusyMessageEmailAddress	280
2.785	PidTagFreeBusyPublishEnd	281
2.786	PidTagFreeBusyPublishStart	281
2.787	PidTagFreeBusyRangeTimestamp	281
2.788	PidTagFtpSite	281
2.789	PidTagFXDelProp	282
2.790	PidTagFXErrorInfo	282
2.791	PidTagGatewayNeedsToRefresh	282
2.792	PidTagGender	282
2.793	PidTagGeneration	283
2.794	PidTagGivenName	283
2.795	PidTagGovernmentIdNumber	283
2.796	PidTagHasAttachments	283
2.797	PidTagHasDeferredActionMessages	284
2.798	PidTagHasNamedProperties	284
2.799	PidTagHasRules	284
2.800	PidTagHierarchyChangeNumber	284
2.801	PidTagHobbies	285
2.802	PidTagHome2TelephoneNumber	285
2.803	PidTagHome2TelephoneNumbers	285
2.804	PidTagHomeAddressCity	286
2.805	PidTagHomeAddressCountry	286
2.806	PidTagHomeAddressPostalCode	286
2.807	PidTagHomeAddressPostOfficeBox	286
2.808	PidTagHomeAddressStateOrProvince	287
2.809	PidTagHomeAddressStreet	287
2.810	PidTagHomeFaxNumber	287
2.811	PidTagHomeTelephoneNumber	288
2.812	PidTagHtml	288
2.813	PidTagICalendarEndTime	288
2.814	PidTagICalendarReminderNextTime	289
2.815	PidTagICalendarStartTime	289
2.816	PidTagIconIndex	289
2.817	PidTagIdsetDeleted	289
2.818	PidTagIdsetExpired	290
2.819	PidTagIdsetGiven	290
2.820	PidTagIdsetRead	290
2.821	PidTagIdsetNoLongerInScope	291
2.822	PidTagIdsetUnread	291
2.823	PidTagImapCachedMsgsize	291
2.824	PidTagImportance	291
2.825	PidTagInConflict	292
2.826	PidTagIncrementalSyncMessagePartial	292

2.827	PidTagIncrSyncChg	292
2.828	PidTagIncrSyncChgPartial.....	292
2.829	PidTagIncrSyncDel	293
2.830	PidTagIncrSyncEnd	293
2.831	PidTagIncrSyncGroupId.....	293
2.832	PidTagIncrSyncGroupInfo	293
2.833	PidTagIncrSyncMessage	294
2.834	PidTagIncrSyncProgressMode	294
2.835	PidTagIncrSyncProgressPerMsg	294
2.836	PidTagIncrSyncRead	294
2.837	PidTagIncrSyncStateBegin.....	295
2.838	PidTagIncrSyncStateEnd	295
2.839	PidTagInitialDetailsPane	295
2.840	PidTagInitials	295
2.841	PidTagInReplyToId	296
2.842	PidTagInstanceKey	296
2.843	PidTagInstanceNum	296
2.844	PidTagInstID	297
2.845	PidTagInternetArticleNumber	297
2.846	PidTagInternetCodepage	297
2.847	PidTagInternetMailOverrideFormat	297
2.848	PidTagInternetMessageId	298
2.849	PidTagInternetReferences	298
2.850	PidTagInternetReturnPath	298
2.851	PidTagIpmAppointmentEntryId	298
2.852	PidTagIpmContactEntryId.....	299
2.853	PidTagIpmDraftsEntryId	299
2.854	PidTagIpmJournalEntryId	299
2.855	PidTagIpmNoteEntryId.....	299
2.856	PidTagIpmTaskEntryId	300
2.857	PidTagIsdnNumber	300
2.858	PidTagItemTemporaryFlags	300
2.859	PidTagJunkAddRecipientsToSafeSendersList	300
2.860	PidTagJunkIncludeContacts	301
2.861	PidTagJunkPermanentlyDelete	301
2.862	PidTagJunkPhishingEnableLinks.....	301
2.863	PidTagJunkThreshold	301
2.864	PidTagKeyword	302
2.865	PidTagLanguage.....	302
2.866	PidTagLastModificationTime	302
2.867	PidTagLastModifierEntryId	303
2.868	PidTagLastModifierName	303
2.869	PidTagLastModifierSimpleDisplayName.....	303
2.870	PidTagLastVerbExecuted	303
2.871	PidTagLastVerbExecutionTime.....	304
2.872	PidTagListHelp	304
2.873	PidTagListSubscribe	304
2.874	PidTagListUnsubscribe	304
2.875	PidTagLocalCommitTime	305
2.876	PidTagLocaleId.....	305
2.877	PidTagLocality.....	305
2.878	PidTagLocation.....	306
2.879	PidTagMailboxOwnerEntryId	306

2.880	PidTagMailboxOwnerName	306
2.881	PidTagManagerName	306
2.882	PidTagMappingSignature	307
2.883	PidTagMaximumSubmitMessageSize	307
2.884	PidTagMemberId	307
2.885	PidTagMemberName	308
2.886	PidTagMemberRights	308
2.887	PidTagMessageAttachments.....	308
2.888	PidTagMessageCcMe	308
2.889	PidTagMessageClass	309
2.890	PidTagMessageCodepage	309
2.891	PidTagMessageDeliveryTime	309
2.892	PidTagMessageEditorFormat	310
2.893	PidTagMessageFlags	310
2.894	PidTagMessageHandlingSystemCommonName	310
2.895	PidTagMessageLocaleId.....	311
2.896	PidTagMessageRecipientMe.....	311
2.897	PidTagMessageRecipients	311
2.898	PidTagMessageSize.....	311
2.899	PidTagMessageSizeExtended.....	312
2.900	PidTagMessageStatus	312
2.901	PidTagMessageSubmissionId	312
2.902	PidTagMessageToMe	313
2.903	PidTagMid	313
2.904	PidTagMiddleName	313
2.905	PidTagMimeSkeleton.....	313
2.906	PidTagMobileTelephoneNumber	314
2.907	PidTagNativeBody	314
2.908	PidTagNewAttach	314
2.909	PidTagNewFXFolder	315
2.910	PidTagNextSendAcct	315
2.911	PidTagNickname.....	315
2.912	PidTagNormalizedSubject	315
2.913	PidTagNormalMessageSize	316
2.914	PidTagObjectType	316
2.915	PidTagOfficeLocation.....	316
2.916	PidTagOfflineAddressBookCompressedSize	317
2.917	PidTagOfflineAddressBookContainerGuid	317
2.918	PidTagOfflineAddressBookDistinguishedName	317
2.919	PidTagOfflineAddressBookFileSize.....	317
2.920	PidTagOfflineAddressBookFileType.....	318
2.921	PidTagOfflineAddressBookLanguageId	318
2.922	PidTagOfflineAddressBookMessageClass	318
2.923	PidTagOfflineAddressBookName	319
2.924	PidTagOfflineAddressBookSequence.....	319
2.925	PidTagOfflineAddressBookShaHash	319
2.926	PidTagOfflineAddressBookTruncatedProperties	319
2.927	PidTagOrdinalMost.....	320
2.928	PidTagOrganizationalIdNumber	320
2.929	PidTagOriginalAuthorName	320
2.930	PidTagOriginalDeliveryTime	320
2.931	PidTagOriginalDisplayBcc	321
2.932	PidTagOriginalDisplayCc.....	321

2.933	PidTagOriginalDisplayName	321
2.934	PidTagOriginalDisplayTo	322
2.935	PidTagOriginalEntryId	322
2.936	PidTagOriginalMessageClass	322
2.937	PidTagOriginalMessageId	323
2.938	PidTagOriginalSearchKey	323
2.939	PidTagOriginalSenderAddressType	323
2.940	PidTagOriginalSenderEmailAddress	323
2.941	PidTagOriginalSenderEntryId	324
2.942	PidTagOriginalSenderName	324
2.943	PidTagOriginalSenderSearchKey	324
2.944	PidTagOriginalSensitivity	325
2.945	PidTagOriginalSentRepresentingAddressType	325
2.946	PidTagOriginalSentRepresentingEmailAddress	325
2.947	PidTagOriginalSentRepresentingEntryId	325
2.948	PidTagOriginalSentRepresentingName	326
2.949	PidTagOriginalSentRepresentingSearchKey	326
2.950	PidTagOriginalSubject	326
2.951	PidTagOriginalSubmitTime	327
2.952	PidTagOriginatorDeliveryReportRequested	327
2.953	PidTagOriginatorNonDeliveryReportRequested	327
2.954	PidTagOtherAddressCity	328
2.955	PidTagOtherAddressCountry	328
2.956	PidTagOtherAddressPostalCode	328
2.957	PidTagOtherAddressPostOfficeBox	328
2.958	PidTagOtherAddressStateOrProvince	329
2.959	PidTagOtherAddressStreet	329
2.960	PidTagOtherTelephoneNumber	329
2.961	PidTagOutOfOfficeState	330
2.962	PidTagOwnerAppointmentId	330
2.963	PidTagPagerTelephoneNumber	330
2.964	PidTagParentEntryId	331
2.965	PidTagParentFolderId	331
2.966	PidTagParentKey	331
2.967	PidTagParentSourceKey	331
2.968	PidTagPersonalHomePage	332
2.969	PidTagPolicyTag	332
2.970	PidTagPostalAddress	332
2.971	PidTagPostalCode	333
2.972	PidTagPostOfficeBox	333
2.973	PidTagPredecessorChangeList	333
2.974	PidTagPrimaryFaxNumber	333
2.975	PidTagPrimarySendAccount	334
2.976	PidTagPrimarySmtpAddress	334
2.977	PidTagPrimaryTelephoneNumber	334
2.978	PidTagPriority	335
2.979	PidTagProcessed	335
2.980	PidTagProfession	335
2.981	PidTagProhibitReceiveQuota	335
2.982	PidTagProhibitSendQuota	336
2.983	PidTagProviderSubmitTime	336
2.984	PidTagPublicFolderAdministrativeDescription	336
2.985	PidTagPublicFolderProxy	337

2.986	PidTagPurportedSenderDomain	337
2.987	PidTagRadioTelephoneNumber	337
2.988	PidTagRead	337
2.989	PidTagReadReceiptAddressType	338
2.990	PidTagReadReceiptEmailAddress	338
2.991	PidTagReadReceiptEntryId	338
2.992	PidTagReadReceiptName	338
2.993	PidTagReadReceiptRequested	339
2.994	PidTagReadReceiptSearchKey	339
2.995	PidTagReceivedByAddressType	339
2.996	PidTagReceivedByEmailAddress	339
2.997	PidTagReceivedByEntryId	340
2.998	PidTagReceivedByFlags	340
2.999	PidTagReceivedByName	340
2.1000	PidTagReceivedBySearchKey	341
2.1001	PidTagReceivedRepresentingAddressType	341
2.1002	PidTagReceivedRepresentingEmailAddress	341
2.1003	PidTagReceivedRepresentingEntryId	342
2.1004	PidTagReceivedRepresentingFlags	342
2.1005	PidTagReceivedRepresentingName	342
2.1006	PidTagReceivedRepresentingSearchKey	342
2.1007	PidTagReceivedRepresentingSimpleDisplayName	343
2.1008	PidTagRecipientDisplayName	343
2.1009	PidTagRecipientEntryId	343
2.1010	PidTagRecipientFlags	343
2.1011	PidTagRecipientOrder	344
2.1012	PidTagRecipientProposed	344
2.1013	PidTagRecipientProposedEndTime	344
2.1014	PidTagRecipientProposedStartTime	344
2.1015	PidTagRecipientReassignmentProhibited	345
2.1016	PidTagRecipientResourceState	345
2.1017	PidTagRecipientTrackStatus	345
2.1018	PidTagRecipientTrackStatusTime	345
2.1019	PidTagRecipientType	346
2.1020	PidTagRecordKey	346
2.1021	PidTagReferredByName	346
2.1022	PidTagRemindersOnlineEntryId	347
2.1023	PidTagRemoteHeaderLoc	347
2.1024	PidTagRemoteMessageTransferAgent	347
2.1025	PidTagRenderingPosition	347
2.1026	PidTagReplyRecipientEntries	348
2.1027	PidTagReplyRecipientNames	348
2.1028	PidTagReplyRequested	348
2.1029	PidTagReplyTemplateId	348
2.1030	PidTagReplyTime	349
2.1031	PidTagReportEntryId	349
2.1032	PidTagReportingMessageTransferAgent	349
2.1033	PidTagReportName	349
2.1034	PidTagReportSearchKey	350
2.1035	PidTagReportTag	350
2.1036	PidTagReportText	350
2.1037	PidTagReportTime	351
2.1038	PidTagResolveMethod	351

2.1039	PidTagResponseRequested	351
2.1040	PidTagResponsibility	351
2.1041	PidTagRetentionDate.....	352
2.1042	PidTagRetentionFlags	352
2.1043	PidTagRetentionPeriod	352
2.1044	PidTagRights.....	352
2.1045	PidTagRoamingDatatypes	353
2.1046	PidTagRoamingDictionary	353
2.1047	PidTagRoamingXmlStream.....	353
2.1048	PidTagRowid	353
2.1049	PidTagRowType	354
2.1050	PidTagRtfCompressed	354
2.1051	PidTagRtfInSync.....	354
2.1052	PidTagRtfSyncBodyCount	355
2.1053	PidTagRtfSyncBodyCrc	355
2.1054	PidTagRtfSyncBodyTag.....	355
2.1055	PidTagRtfSyncPrefixCount.....	355
2.1056	PidTagRtfSyncTrailingCount	356
2.1057	PidTagRuleActionNumber.....	356
2.1058	PidTagRuleActions	356
2.1059	PidTagRuleActionType	356
2.1060	PidTagRuleCondition	357
2.1061	PidTagRuleError	357
2.1062	PidTagRuleFolderEntryId	357
2.1063	PidTagRuleId	357
2.1064	PidTagRuleLevel	358
2.1065	PidTagRuleMessageLevel	358
2.1066	PidTagRuleMessageName	358
2.1067	PidTagRuleMessageProvider.....	358
2.1068	PidTagRuleMessageProviderData	359
2.1069	PidTagRuleMessageSequence	359
2.1070	PidTagRuleMessageState.....	359
2.1071	PidTagRuleMessageUserFlags.....	359
2.1072	PidTagRuleName	360
2.1073	PidTagRuleProvider	360
2.1074	PidTagRuleProviderData	360
2.1075	PidTagRuleSequence	360
2.1076	PidTagRuleState	361
2.1077	PidTagRuleUserFlags	361
2.1078	PidTagRwRulesStream	361
2.1079	PidTagScheduleInfoAppointmentTombstone.....	361
2.1080	PidTagScheduleInfoAutoAcceptAppointments	362
2.1081	PidTagScheduleInfoDelegateEntryIds	362
2.1082	PidTagScheduleInfoDelegateNames	362
2.1083	PidTagScheduleInfoDelegateNamesW.....	362
2.1084	PidTagScheduleInfoDelegatorWantsCopy	363
2.1085	PidTagScheduleInfoDelegatorWantsInfo	363
2.1086	PidTagScheduleInfoDisallowOverlappingAppts	363
2.1087	PidTagScheduleInfoDisallowRecurringAppts	363
2.1088	PidTagScheduleInfoDontMailDelegates	364
2.1089	PidTagScheduleInfoFreeBusy	364
2.1090	PidTagScheduleInfoFreeBusyAway	364
2.1091	PidTagScheduleInfoFreeBusyBusy.....	364

2.1092	PidTagScheduleInfoFreeBusyMerged	365
2.1093	PidTagScheduleInfoFreeBusyTentative	365
2.1094	PidTagScheduleInfoMonthsAway	365
2.1095	PidTagScheduleInfoMonthsBusy	365
2.1096	PidTagScheduleInfoMonthsMerged	366
2.1097	PidTagScheduleInfoMonthsTentative	366
2.1098	PidTagScheduleInfoResourceType	366
2.1099	PidTagSchedulePlusFreeBusyEntryId	366
2.1100	PidTagScriptData	367
2.1101	PidTagSearchFolderDefinition	367
2.1102	PidTagSearchFolderEfpFlags	367
2.1103	PidTagSearchFolderExpiration	367
2.1104	PidTagSearchFolderId	368
2.1105	PidTagSearchFolderLastUsed	368
2.1106	PidTagSearchFolderRecreateInfo	368
2.1107	PidTagSearchFolderStorageType	368
2.1108	PidTagSearchFolderTag	369
2.1109	PidTagSearchFolderTemplateId	369
2.1110	PidTagSearchKey	369
2.1111	PidTagSecureSubmitFlags	369
2.1112	PidTagSecurityDescriptor	370
2.1113	PidTagSecurityDescriptorAsXml	370
2.1114	PidTagSelectable	370
2.1115	PidTagSenderAddressType	370
2.1116	PidTagSenderEmailAddress	371
2.1117	PidTagSenderEntryId	371
2.1118	PidTagSenderFlags	371
2.1119	PidTagSenderIdStatus	372
2.1120	PidTagSenderName	372
2.1121	PidTagSenderSearchKey	372
2.1122	PidTagSenderSimpleDisplayName	372
2.1123	PidTagSenderSmtpAddress	373
2.1124	PidTagSenderTelephoneNumber	373
2.1125	PidTagSendInternetEncoding	373
2.1126	PidTagSendRichInfo	373
2.1127	PidTagSensitivity	374
2.1128	PidTagSentMailEntryId	374
2.1129	PidTagSentMailSvrEID	374
2.1130	PidTagSentRepresentingAddressType	375
2.1131	PidTagSentRepresentingEmailAddress	375
2.1132	PidTagSentRepresentingEntryId	375
2.1133	PidTagSentRepresentingFlags	376
2.1134	PidTagSentRepresentingName	376
2.1135	PidTagSentRepresentingSearchKey	376
2.1136	PidTagSentRepresentingSimpleDisplayName	376
2.1137	PidTagSessionInitiationProtocolUri	377
2.1138	PidTagSmtpAddress	377
2.1139	PidTagSortLocaleId	377
2.1140	PidTagSourceKey	377
2.1141	PidTagSpokenName	378
2.1142	PidTagSpouseName	378
2.1143	PidTagStartDate	378
2.1144	PidTagStartDateEtc	379

2.1145	PidTagStartEmbed	379
2.1146	PidTagStartFAIMsg	379
2.1147	PidTagStartMessage.....	379
2.1148	PidTagStartRecip	380
2.1149	PidTagStartSubFld	380
2.1150	PidTagStartTopFld	380
2.1151	PidTagStateOrProvince	380
2.1152	PidTagStoreEntryId.....	381
2.1153	PidTagStoreState.....	381
2.1154	PidTagStoreSupportMask.....	381
2.1155	PidTagStreetAddress	381
2.1156	PidTagSubfolder	382
2.1157	PidTagSubfolders.....	382
2.1158	PidTagSubject	382
2.1159	PidTagSubjectPrefix	383
2.1160	PidTagSubmitFlags	383
2.1161	PidTagSurname	383
2.1162	PidTagSwappedToDoData	383
2.1163	PidTagSwappedToDoStore	384
2.1164	PidTagTargetEntryId	384
2.1165	PidTagTcvConstLongOne	384
2.1166	PidTagTelecommunicationsDeviceForDeafTelephoneNumber	384
2.1167	PidTagTelexNumber	385
2.1168	PidTagTemplateData	385
2.1169	PidTagTemplateid	385
2.1170	PidTagTemporaryDefaultDocument	386
2.1171	PidTagTextAttachmentCharset	386
2.1172	PidTagThumbnailPhoto	386
2.1173	PidTagTitle	386
2.1174	PidTagTnefCorrelationKey.....	387
2.1175	PidTagToDoItemFlags	387
2.1176	PidTagTransmittableDisplayName	387
2.1177	PidTagTransportMessageHeaders.....	387
2.1178	PidTagTrustSender	388
2.1179	PidTagTtyTddPhoneNumber	388
2.1180	PidTagUrlCompName	388
2.1181	PidTagUrlCompNameSet.....	388
2.1182	PidTagUrlName	389
2.1183	PidTagUserCertificate	389
2.1184	PidTagUserEntryId	389
2.1185	PidTagUserX509Certificate.....	390
2.1186	PidTagViewDescriptorBinary.....	390
2.1187	PidTagViewDescriptorName	390
2.1188	PidTagViewDescriptorStrings.....	390
2.1189	PidTagViewDescriptorVersion	391
2.1190	PidTagVoiceMessageAttachmentOrder	391
2.1191	PidTagVoiceMessageDuration	391
2.1192	PidTagVoiceMessageSenderName	391
2.1193	PidTagWeddingAnniversary.....	392
2.1194	PidTagWlinkAddressBookEID	392
2.1195	PidTagWlinkAddressBookStoreEID	392
2.1196	PidTagWlinkCalendarColor	392
2.1197	PidTagWlinkClientID.....	393

2.1198	PidTagWlinkEntryId	393
2.1199	PidTagWlinkFlags.....	393
2.1200	PidTagWlinkFolderType	394
2.1201	PidTagWlinkGroupClsid.....	394
2.1202	PidTagWlinkGroupHeaderID	394
2.1203	PidTagWlinkGroupName	394
2.1204	PidTagWlinkOrdinal.....	395
2.1205	PidTagWlinkRecordKey	395
2.1206	PidTagWlinkROGroupType	395
2.1207	PidTagWlinkSaveStamp.....	395
2.1208	PidTagWlinkSection	396
2.1209	PidTagWlinkStoreEntryId	396
2.1210	PidTagWlinkType	396
3	Structure Examples	397
4	Security Considerations.....	398
5	Appendix A: Product Behavior	399
6	Change Tracking.....	400
7	Index	402

1 Introduction

This specification lists all properties used for communication between clients and servers, provides summary information about each property, and provides links to the documents in which the property value ranges and semantics are specified.

1.1 Glossary

The following terms are defined in [\[MS-OXGLOS\]](#):

message class
named property
property (1)
property ID
property set
tagged property

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[MS-NSPI] Microsoft Corporation, "Name Service Provider Interface (NSPI) Protocol Specification", April 2008, <http://go.microsoft.com/fwlink/?LinkID=154742>

[MS-OXABREF] Microsoft Corporation, "[Address Book Name Service Provider Interface \(NSPI\) Referral Protocol Specification](#)", April 2008.

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Protocol Specification](#)", April 2008.

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)", April 2008.

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)", April 2008.

[MS-OXCFXICS] Microsoft Corporation, "[Bulk Data Transfer Protocol Specification](#)", April 2008.

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Protocol Specification](#)", April 2008.

[MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Protocol Specification](#)", April 2008.

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)", April 2008.

[MS-OXCNOTIF] Microsoft Corporation, "[Core Notifications Protocol Specification](#)", April 2008.

[MS-OXCPERM] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol Specification](#)", April 2008.

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)", April 2008.

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)", April 2008.

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol Specification](#)", April 2008.

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol Specification](#)", April 2008.

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol Specification](#)", April 2008.

[MS-OXCSYNC] Microsoft Corporation, "[Mailbox Synchronization Protocol Specification](#)", April 2008.

[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol Specification](#)", April 2008.

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)", April 2008.

[MS-OXLDAP] Microsoft Corporation, "[Lightweight Directory Access Protocol \(LDAP\) Version 3 Extensions](#)", April 2008.

[MS-OXMSG] Microsoft Corporation, "[.MSG File Format](#)", April 2008.

[MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)", April 2008.

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)", April 2008.

[MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol Specification](#)", April 2008.

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)", April 2008.

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol Specification](#)", April 2008.

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol Specification](#)", April 2008.

[MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol Specification](#)", April 2008.

[MS-OXODOC] Microsoft Corporation, "[Document Object Protocol Specification](#)", April 2008.

[MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol Specification](#)", April 2008.

[MS-OXOJRN] Microsoft Corporation, "[Journal Object Protocol Specification](#)", April 2008.

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)", April 2008.

[MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol Specification](#)", April 2008.

[MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol Specification](#)", April 2008.

[MS-OXOPOST] Microsoft Corporation, "[Post Object Protocol Specification](#)", April 2008.

[MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol Specification](#)", April 2008.

[MS-OXORMMS] Microsoft Corporation, "[Rights-Managed E-Mail Object Protocol Specification](#)", April 2008.

[MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol Specification](#)", April 2008.

[MS-OXORULE] Microsoft Corporation, "[E-Mail Rules Protocol Specification](#)", April 2008.

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol Specification](#)", April 2008.

[MS-OXOSMIME] Microsoft Corporation, "[S/MIME E-Mail Object Protocol Specification](#)", April 2008.

[MS-OXOSMMS] Microsoft Corporation, "[Short Message Service \(SMS\) and Multimedia Messaging Service \(MMS\) Object Protocol Specification](#)", April 2008.

[MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol Specification](#)", April 2008.

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol Specification](#)", April 2008.

[MS-OXOUM] Microsoft Corporation, "[Voice Mail and Fax Objects Protocol Specification](#)", April 2008.

[MS-OXPFOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) Public Folder Retrieval Protocol Specification](#)", April 2008.

[MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol Specification](#)", April 2008.

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)", April 2008.

[MS-OXPSVAL] Microsoft Corporation, "[E-Mail Postmark Validation Protocol Specification](#)", April 2008.

[MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Protocol Specification](#)", April 2008.

[MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Specification](#)", April 2008.

[MS-OXSHARE] Microsoft Corporation, "[Sharing Message Object Protocol Specification](#)", April 2008.

[MS-OXTNEF] Microsoft Corporation, "[Transport Neutral Encapsulation Format \(TNEF\) Data Structure](#)", April 2008.

[MS-OXVCARD] Microsoft Corporation, "[vCard to Contact Object Conversion Protocol Specification](#)", April 2008.

[MS-OXWAVLS] Microsoft Corporation, "[Availability Web Service Protocol Specification](#)", April 2008.

[MS-XWDCAL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Calendar Support](#)", December 2008.

[MS-XWDCNTC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Contacts Support](#)", February 2009.

[MS-XWDDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Documents Support](#)", December 2008.

[MS-XWDFOLD] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Folders Support](#)", December 2008.

[MS-XWDMAIL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for E-Mail Support](#)", December 2008.

[MS-XWDSEARCH] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Search](#)", December 2008.

[MS-XWDSTRUCTDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Structured Documents](#)", December 2008.

[MS-XWDVSEC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Protocol Security Descriptor Extensions](#)", April 2008.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", RFC 2119, BCP 14, March 1997, <http://www.ietf.org/rfc/rfc2119.txt>

[RFC4234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", RFC 4234, October 2005, <http://www.ietf.org/rfc/rfc4234.txt>

1.2.2 Informative References

None.

1.3 Overview

This specification provides basic reference information about message object properties referenced by protocol specifications. The following information is provided for each **property**, as appropriate:

Alternate names: Any additional names used to refer to this property.

Area: A group of properties with related functionality.

Canonical name: The name used to refer to this property in other protocol specifications.

Description: A brief description of the contents of the property. Properties that are not defined in the core protocol documents do not have descriptions.

Data type: The property value type, as specified in [\[MS-OXCDATA\]](#), that specifies the type of values allowed for this property.

Property ID: An unsigned 16-bit quantity that identifies a **tagged property**.

Property long ID (LID): An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

Property name: A string that, along with the property set, identifies a named property.

Property set: A GUID that identifies a group of properties with a similar purpose.

References: One or more protocol documents that specify the semantics and allowed values for this property.

1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's **message class**. Applications handle the case where required properties are missing; treating a message object as **IPM.Note** is a common fallback strategy. The following table lists several common message classes, the functional area to which each one corresponds, and the document that specifies each one's required and optional properties.

In this table, an asterisk "*" denotes that any string can appear at that point.

Area	PidTagMessageClass values	Document
Common	IPM.*	[MS-OXCMMSG]
Email	IPM.Note, REPORT.*	[MS-OXCMMSG]
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	[MS-OXOCAL]
Contact	IPM.Contact, IPM.DistList	[MS-OXOCNTC]
Task	IPM.Task, IPM.TaskRequest.*	[MS-OXOTASK]
Journal	IPM.Activity	[MS-OXOJRNL]
Sticky note	IPM.StickyNote	[MS-OXONOTE]
Document	IPM.Document.*	[MS-OXODOC]
Post	IPM.Post	[MS-OXOPOST]
RSS feed	IPM.Post.RSS	[MS-OXORSS]
Rights-managed email	IPM.Note with PidNameContentClass= rpmsg.message	[MS-OXORMMS]
S/MIME email	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	[MS-OXOSMIME]
Short message service / Multimedia Message Service Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	[MS-OXOSMMS]
Unified messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	[MS-OXOUM]
Sharing	IPM.Sharing IPM.Sharing.*	[MS-OXSHARE]

1.3.2 Commonly Used Property Sets

In the property index that forms the main body of this document (section [2](#)) each named property is listed with the GUID that defines its property set. Several of the more common property sets are listed here as a convenient reference, with their functional areas.

Area	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}
Common	PSETID_Common {00062008-0000-0000-C000-000000000046}
Contact	PSETID_Address {00062004-0000-0000-C000-000000000046}
Email	PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-000000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-000000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-000000000046}
RSS feed	PSETID_PostRss {00062041-0000-0000-C000-000000000046}
Task	PSETID_Task {00062003-0000-0000-C000-000000000046}
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing {00062040-0000-0000-C000-000000000046}

1.3.3 Property ID Ranges

The 65,536 possible values of the **property ID** are divided into sub-ranges reserved for various purposes, as specified in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an email transport protocol (such as SMTP), and not to any network transport protocol (such as TCP).

- Servers do not allow property ID in ranges specified as non-transmittable to be submitted for transport to another server via a mail transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.
- Clients can use properties in ranges specified as message class-defined for application-defined purposes. When doing so, applications specify a value for **PidTagMessageClass** that is distinct from any value listed in section [1.3.1](#).
- Clients can use any named property for application-defined purposes. No constraint is placed on the value of **PidTagMessageClass** in this case, but the named property's property set is distinct from any value listed in section [1.3.2](#). Note that named properties are always transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Specification
0x0001	0x0BFF	Message envelope property; reserved
0x0C00	0x0DFF	Recipient property; reserved
0x0E00	0x0FFF	Non-transmittable message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	Message store property; reserved
0x3600	0x36FF	Folder and address book container property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	Address book object property; reserved
0x3A00	0x3BFF	Mail user object property; reserved
0x3C00	0x3CFF	Distribution list property; reserved
0x3D00	0x3DFF	Profile section property; reserved
0x3E00	0x3EFF	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient property

Range minimum	Range maximum	Specification
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. See [MS-NSPI] for more information about the static mapping of NSPI property names to property IDs that occurs in this ID range.

1.3.4 WebDAV Property Naming

The mail server is natively a MAPI store where the vast majority of properties in it are MAPI properties. The WebDAV implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as specified in [\[RFC4234\]](#), as a way to name MAPI properties, allowing WebDAV clients to work with these properties directly.

The `http://schemas.microsoft.com/mapi/` namespace is used to directly access MAPI properties on the server. The namespace consists of three sub namespaces: `proptag`, `id`, and `string`. The ABNF notation used to specify the format of these namespaces is described in this section.

1.3.4.1 `http://schemas.microsoft.com/mapi/proptag` Namespace

This namespace is used to access properties on the server that are identified by a property ID. You can access these properties through WebDAV by appending the hexadecimal property ID value and the hexadecimal property type value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type
property-id      = 4HEXDIG
property-type    = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

1.3.4.2 `http://schemas.microsoft.com/mapi/id` Namespace

This namespace is used to access named properties on the server that are identified by a **property long ID**. You can access these properties through WebDAV by appending the property set and the hexadecimal **property long ID** value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/"x" property-long-id
property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"
```

property-long-id = 8HEXDIG

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213  
(PidLidAppointmentDuration)
```

1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace

This namespace is used to access named properties on the server that are identified by a **property name**. You can access these properties through WebDAV by appending the property set and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name  
property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"  
property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject  
(PidNameSubject)
```

1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [\[MS-OXCADATA\]](#). For tables and examples specifying property data types, and for tables specifying property and other error codes, see [\[MS-OXCADATA\]](#).

The object type specifications listed in section [1.2.1](#) depend on this document for basic information about message object properties to which they refer. Such basic information includes property IDs and **data types**. This specification, in turn, depends on each of those object type specifications to specify the behavior and semantics of the properties specific to its protocol.

1.5 Applicability Statement

This document provides the numeric values needed to encode property names, tags, and types in ROP buffers. It also serves as a convenient index to the object type documents that define how each property is used.

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

Property ID ranges, as specified in section [1.3.3](#), describe how applications choose properties to create new message object types or to add functionality to existing types.

2 Structures

2.1 PidLidAddressBookProviderArrayType

Canonical name: PidLidAddressBookProviderArrayType

Description: Specifies the state of the contact's electronic addresses and represents a set of bit-flags.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008029

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidABPArrayType

2.2 PidLidAddressBookProviderEmailList

Canonical name: PidLidAddressBookProviderEmailList

Description: Specifies which electronic address properties are set on the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008028

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidABPEmailList

2.3 PidLidAddressCountryCode

Canonical name: PidLidAddressCountryCode

Description: Specifies the country code portion of the contact's mailing address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DD

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidAddressCountryCode

2.4 PidLidAgingDontAgeMe

Canonical name: PidLidAgingDontAgeMe

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000850E

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidAgingDontAgeMe

2.5 PidLidAllAttendeesList

Canonical name: PidLidAllAttendeesList

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000001D

Data type: PtypString, 0x001F

Area: Meetings

References: [\[MS-OXCICAL\]](#)

Alternate names: LID_ALL_ATTENDEES_LIST

2.6 PidLidAllAttendeesString

Canonical name: PidLidAllAttendeesString

Description: Specifies a list of all the attendees except for the organizer, including resources and unsendable attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008238

WebDAV: <http://schemas.microsoft.com/mapi/allattendeesstring>

Data type: PtypString, 0x001F

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidAllAttendeesString

2.7 PidLidAllowExternalCheck

Canonical name: PidLidAllowExternalCheck

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008246

Data type: PtypBoolean, 0x000B

Area: Conferencing

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidAllowExternCheck

2.8 PidLidAnniversaryEventEntryId

Canonical name: PidLidAnniversaryEventEntryId

Description: Specifies the object EntryId of the Appointment object that represents a contact's anniversary.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804E

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Alternate names: dispidAnniversaryEventEID

2.9 PidLidAppointmentAuxiliaryFlags

Canonical name: PidLidAppointmentAuxiliaryFlags

Description: Specifies a bit field that describes the auxiliary state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008207

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptAuxFlags

2.10 PidLidAppointmentColor

Canonical name: PidLidAppointmentColor

Description: Specifies the color to be used when displaying the Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008214

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptColor

2.11 PidLidAppointmentCounterProposal

Canonical name: PidLidAppointmentCounterProposal

Description: Indicates whether a Meeting Response object is a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008257

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptCounterProposal

2.12 PidLidAppointmentDuration

Canonical name: PidLidAppointmentDuration

Description: Specifies the length of the event, in minutes.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008213

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/apptduration>

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptDuration

2.13 PidLidAppointmentEndDate

Canonical name: PidLidAppointmentEndDate

Description: Indicates the date the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008211

WebDAV: http://schemas.microsoft.com/mapi/apptenddate

Data type: PtypTime, 0x0040

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidApptEndDate

2.14 PidLidAppointmentEndTime

Canonical name: PidLidAppointmentEndTime

Description: Indicates the time the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008210

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptendtime

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidApptEndTime

2.15 PidLidAppointmentEndWhole

Canonical name: PidLidAppointmentEndWhole

Description: Specifies the end date and time for the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820E

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/apptendwhole

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptEndWhole

2.16 PidLidAppointmentLastSequence

Canonical name: PidLidAppointmentLastSequence

Description: Indicates to the organizer the last sequence number that was sent to any attendee.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008203

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptLastSequence

2.17 PidLidAppointmentMessageClass

Canonical name: PidLidAppointmentMessageClass

Description: Indicates the message class of the Meeting object that is to be generated from the Meeting Request object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000024

Data type: PtypString, 0x001F

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptMessageClass

2.18 PidLidAppointmentNotAllowPropose

Canonical name: PidLidAppointmentNotAllowPropose

Description: Indicates whether attendees are not allowed to propose a new date and/or time for the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptNotAllowPropose

2.19 PidLidAppointmentProposalNumber

Canonical name: PidLidAppointmentProposalNumber

Description: Specifies the number of attendees who have sent counter proposals that have not been accepted or rejected by the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008259

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposalNum

2.20 PidLidAppointmentProposedDuration

Canonical name: PidLidAppointmentProposedDuration

Description: Indicates the proposed value for PidLidAppointmentDuration for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008256

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposedDuration

2.21 PidLidAppointmentProposedEndWhole

Canonical name: PidLidAppointmentProposedEndWhole

Description: Specifies the proposed value for PidLidAppointmentEndWhole for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008251

Data type: PtypTime, 0x0040

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposedEndWhole

2.22 PidLidAppointmentProposedStartWhole

Canonical name: PidLidAppointmentProposedStartWhole

Description: Specifies the proposed value for PidLidAppointmentStartWhole for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008250

Data type: PtypTime, 0x0040

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposedStartWhole

2.23 PidLidAppointmentRecur

Canonical name: PidLidAppointmentRecur

Description: Specifies the dates and times when a recurring series occurs.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008216

Data type: PtypBinary, 0x0102

WebDAV: <http://schemas.microsoft.com/mapi/apptrecur>

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptRecur

2.24 PidLidAppointmentReplyName

Canonical name: PidLidAppointmentReplyName

Description: Specifies the user who last replied to the meeting request or meeting update.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008230

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/apptreplyname

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-XWDCAL\]](#)

Alternate names: dispidApptReplyName, http://schemas.microsoft.com/mapi/apptreplyname

2.25 PidLidAppointmentReplyTime

Canonical name: PidLidAppointmentReplyTime

Description: Specifies the date and time at which the attendee responded to a received meeting request or Meeting Update object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008220

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidApptReplyTime

2.26 PidLidAppointmentSequence

Canonical name: PidLidAppointmentSequence

Description: Specifies the sequence number of a Meeting object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008201

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptsequence

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptSequence

2.27 PidLidAppointmentSequenceTime

Canonical name: PidLidAppointmentSequenceTime

Description: Indicates the date and time at which the property PidLidAppointmentSequence was last modified.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008202

Data type: PtypTime, 0x0040

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptSeqTime

2.28 PidLidAppointmentStartDate

Canonical name: PidLidAppointmentStartDate

Description: Identifies the date the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008212

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptstartdate>

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidApptStartDate

2.29 PidLidAppointmentStartTime

Canonical name: PidLidAppointmentStartTime

Description: Identifies the time the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820F

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptstarttime>

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidApptStartTime

2.30 PidLidAppointmentStartWhole

Canonical name: PidLidAppointmentStartWhole

Description: Specifies the start date and time of the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820D

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptstartwhole>

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptStartWhole

2.31 PidLidAppointmentStateFlags

Canonical name: PidLidAppointmentStateFlags

Description: Specifies a bit field that describes the state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008217

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/apptstateflags>

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptStateFlags

2.32 PidLidAppointmentSubType

Canonical name: PidLidAppointmentSubType

Description: Specifies whether the event is an all-day event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008215

Data type: PtypBoolean, 0x000B

WebDAV: urn:schemas:calendar:alldayevent, http://schemas.microsoft.com/mapi/apptsubtype

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidApptSubType

2.33 PidLidAppointmentTimeZoneDefinitionEndDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionEndDisplay

Description: Specifies time zone information that indicates the time zone of the PidLidAppointmentEndWhole property.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825F

Data type: PtypBinary, 0x0102

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptTZDefEndDisplay

2.34 PidLidAppointmentTimeZoneDefinitionRecur

Canonical name: PidLidAppointmentTimeZoneDefinitionRecur

Description: Specifies time zone information that describes how to convert the meeting date and time on a recurring series to and from UTC.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008260

Data type: PtypBinary, 0x0102

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

Alternate names: dispidApptTZDefRecur

2.35 PidLidAppointmentTimeZoneDefinitionStartDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionStartDisplay

Description: Specifies time zone information that indicates the time zone of the PidLidAppointmentStartWhole property.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825E

Data type: PtypBinary, 0x0102

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptTZDefStartDisplay

2.36 PidLidAppointmentUnsendableRecipients

Canonical name: PidLidAppointmentUnsendableRecipients

Description: Contains a list of unsendable attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825D

Data type: PtypBinary, 0x0102

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidApptUnsendableRecips

2.37 PidLidAppointmentUpdateTime

Canonical name: PidLidAppointmentUpdateTime

Description: Indicates the time at which the appointment was last updated.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008226

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptupdatetime>

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidApptUpdateTime

2.38 PidLidAttendeeCriticalChange

Canonical name: PidLidAttendeeCriticalChange

Description: Specifies the date and time at which the meeting-related object was sent.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000001

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/attendee_critical_change

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_ATTENDEE_CRITICAL_CHANGE

2.39 PidLidAutoFillLocation

Canonical name: PidLidAutoFillLocation

Description: Indicates whether the value of the PidLidLocation property is set to the PidTagDisplayName property from the RecipientRow that represents a resource.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidAutoFillLocation

2.40 PidLidAutoLog

Canonical name: PidLidAutoLog

Description: Specifies to the application whether to create a Journal object for each action associated with this Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008025

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidAutoLog

2.41 PidLidAutoProcessState

Canonical name: PidLidAutoProcessState

Description: Specifies the options used in automatic processing of email messages.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851A

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining References: [\[MS-OXOMSG\]](#)

Consuming References:

Alternate names: dispidSniffState

2.42 PidLidAutoStartCheck

Canonical name: PidLidAutoStartCheck

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008244

Data type: PtypBoolean, 0x000B

Area: Conferencing

References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidAutoStartCheck

2.43 PidLidAutoStartWhen

Canonical name: PidLidAutoStartWhen

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008245

Data type: PtypInteger32, 0x0003

Area: Conferencing

References: [\[MS-OXCICAL\]](#)

Alternate names: dispidAutoStartWhen

2.44 PidLidBilling

Canonical name: PidLidBilling

Description: Specifies billing information for the contact.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008535

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:billinginformation

Area: General Message Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidBilling

2.45 PidLidBirthdayEventEntryId

Canonical name: PidLidBirthdayEventEntryId

Description: Specifies the object EntryId of an optional Appointment object that represents the contact's birthday.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804D

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidBirthdayEventEID

2.46 PidLidBirthdayLocal

Canonical name: PidLidBirthdayLocal

Description: Specifies the birthday of a contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DE

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidApptBirthdayLocal

2.47 PidLidBusinessCardCardPicture

Canonical name: PidLidBusinessCardCardPicture

Description: Contains the image to be used on a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008041

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidBCCardPicture

2.48 PidLidBusinessCardDisplayDefinition

Canonical name: PidLidBusinessCardDisplayDefinition

Description: Contains user customization details for displaying a contact as a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008040

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidBCDisplayDefinition

2.49 PidLidBusyStatus

Canonical name: PidLidBusyStatus

Description: Specifies the availability of a user for the event described by the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008205

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/busystatus>

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidBusyStatus

2.50 PidLidCalendarType

Canonical name: PidLidCalendarType

Description: Contains the value of the CalendarType field from the PidLidAppointmentRecur property.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000001C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/calendar_type

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_CALENDAR_TYPE

2.51 PidLidCategories

Canonical name: PidLidCategories

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property long ID (LID): 0x00009000

Data type: PtypMultipleString, 0x101F

Area: Common

References: [\[MS-OXCMAIL\]](#), [\[MS-OXVCARD\]](#)

Alternate names: dispidCategories

2.52 PidLidCcAttendeesString

Canonical name: PidLidCcAttendeesString

Description: Contains a list of all the sendable attendees who are also optional attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823C

Data type: PtypString, 0x001F

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidCCAttendeesString

2.53 PidLidChangeHighlight

Canonical name: PidLidChangeHighlight

Description: Specifies a bit field that indicates how the Meeting object has changed.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008204

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidChangeHighlight

2.54 PidLidClassification

Canonical name: PidLidClassification

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B6

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassification

2.55 PidLidClassificationDescription

Canonical name: PidLidClassificationDescription

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B7

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassDesc

2.56 PidLidClassificationGuid

Canonical name: PidLidClassificationGuid

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B8

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassGuid

2.57 PidLidClassificationKeep

Canonical name: PidLidClassificationKeep

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BA

Data type: PtypBoolean, 0x000B

Area: General Message Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassKeep

2.58 PidLidClassified

Canonical name: PidLidClassified

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B5

Data type: PtypBoolean, 0x000B

Area: General Message Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassified

2.59 PidLidCleanGlobalObjectId

Canonical name: PidLidCleanGlobalObjectId

Description: Contains the value of the PidLidGlobalObjectId property for an object that represents an exception to a recurring series, where the Year, Month, and Day fields are all zero.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000023

Data type: PtypBinary, 0x0102

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidCleanGlobalObjId

2.60 PidLidClientIntent

Canonical name: PidLidClientIntent

Description: Specifies the end date and time of the event in UTC.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x00000015

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidClientIntent

2.61 PidLidClipEnd

Canonical name: PidLidClipEnd

Description: Specifies the end date and time of the event in UTC.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008236

Data type: PtypTime, 0x0040

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidClipEnd

2.62 PidLidClipStart

Canonical name: PidLidClipStart

Description: Specifies the start date and time of the event in UTC.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008235

Data type: PtypTime, 0x0040

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidClipStart

2.63 PidLidCollaborateDoc

Canonical name: PidLidCollaborateDoc

Description: Specifies the document to be launched when the user joins the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008247

Data type: PtypString, 0x001F

Area: Conferencing

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidCollaborateDoc

2.64 PidLidCommonEnd

Canonical name: PidLidCommonEnd

Description: Indicates the end time for the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008517

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidCommonEnd

2.65 PidLidCommonStart

Canonical name: PidLidCommonStart

Description: Indicates the start time for the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008516

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining References: [\[MS-OXCMSG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidCommonStart

2.66 PidLidCompanies

Canonical name: PidLidCompanies

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008539

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

References: [\[MS-OXOJRNL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidCompanies, <http://schemas.microsoft.com/exchange/companies>

2.67 PidLidConferencingCheck

Canonical name: PidLidConferencingCheck

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008240

Data type: PtypBoolean, 0x000B

Area: Conferencing

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidConfCheck

2.68 PidLidConferencingType

Canonical name: PidLidConferencingType

Description: Specifies the type of the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008241

Data type: PtypInteger32, 0x0003

Area: Conferencing

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidConfType

2.69 PidLidContactCharacterSet

Canonical name: PidLidContactCharacterSet

Description: Specifies the character set used for a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008023

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidContactCharSet

2.70 PidLidContactItemData

Canonical name: PidLidContactItemData

Description: Specifies the visible fields in the application's user interface that are used to help display the contact information.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008007

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidContactItemData

2.71 PidLidContactLinkEntry

Canonical name: PidLidContactLinkEntry

Description: Contains the elements of PidLidContacts.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008585

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXCMMSG\]](#)

Consuming References: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkEntry

2.72 PidLidContactLinkName

Canonical name: PidLidContactLinkName

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008586

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMMSG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkName

2.73 PidLidContactLinkSearchKey

Canonical name: PidLidContactLinkSearchKey

Description: Contains the list of SearchKeys for a Contact object linked to by the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008584

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXCMMSG\]](#)

Consuming References: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkSearchKey

2.74 PidLidContacts

Canonical name: PidLidContacts

Description: Contains the PidTagDisplayName of each Address Book EntryID referenced in the value of PidLidContactLinkEntry.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000853A

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining References: [\[MS-OXCMSG\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContacts

2.75 PidLidContactUserField1

Canonical name: PidLidContactUserField1

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804F

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/exchange/extensionattribute1>

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField1

2.76 PidLidContactUserField2

Canonical name: PidLidContactUserField2

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008050

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/exchange/extensionattribute2>

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField2

2.77 PidLidContactUserField3

Canonical name: PidLidContactUserField3

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008051

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute3

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField3

2.78 PidLidContactUserField4

Canonical name: PidLidContactUserField4

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008052

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute4

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField4

2.79 PidLidConversationActionLastAppliedTime

Canonical name: PidLidConversationActionLastAppliedTime

Description: Contains the time (in UTC) that an E-mail object was last received in the conversation, or the last time that the user modified the Conversation Action, whichever occurs later.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CA

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining References: [\[MS-OXOCFG\]](#)

Consuming References:

Alternate names: dispidConvActionLastAppliedTime

2.80 PidLidConversationActionMaxDeliveryTime

Canonical name: PidLidConversationActionMaxDeliveryTime

Description: Contains the maximum value of PidTagMessageDeliveryTime of all the E-mail objects modified in response to the last time the user changed a Conversation Action on the client.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C8

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining References: [\[MS-OXOCFG\]](#)

Consuming References:

Alternate names: dispidConvActionMaxDeliveryTime

2.81 PidLidConversationActionMoveFolderEid

Canonical name: PidLidConversationActionMoveFolderEid

Description: Contains the entry ID for the destination folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C6

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining References: [\[MS-OXOCFG\]](#)

Consuming References:

Alternate names: dispidConvActionMoveFolderEid

2.82 PidLidConversationActionMoveStoreEid

Canonical name: PidLidConversationActionMoveStoreEid

Description: Contains the entry ID for a move to a folder in a different store.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C7

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining References: [\[MS-OXOCFG\]](#)

Consuming References:

Alternate names: dispidConvActionMoveStoreEid

2.83 PidLidConversationActionVersion

Canonical name: PidLidConversationActionVersion

Description: Contains the version of the conversation action FAI message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CB

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

Defining References: [\[MS-OXOCFG\]](#)

Consuming References:

Alternate names: dispidConvActionVersion

2.84 PidLidConversationProcessed

Canonical name: PidLidConversationProcessed

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C9

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

References: [\[MS-OXOCFG\]](#)

Alternate names: dispidConvExLegacyProcessedRand

2.85 PidLidCurrentVersion

Canonical name: PidLidCurrentVersion

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008552

Data type: PtypInteger32, 0x0003

Area: General Message Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidCurrentVersion

2.86 PidLidCurrentVersionName

Canonical name: PidLidCurrentVersionName

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008554

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidCurrentVersionName

2.87 PidLidDayInterval

Canonical name: PidLidDayInterval

Description: Identifies the day interval for the recurrence pattern.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000011

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/day_interval

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_DAY_INTERVAL

2.88 PidLidDayOfMonth

Canonical name: PidLidDayOfMonth

Description: Identifies the day of the month for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001000

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/dayofmonth>

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names:

2.89 PidLidDelegateMail

Canonical name: PidLidDelegateMail

Description: Indicates whether a delegate responded to the meeting request.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000009

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/delegate_mail

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_DELEGATE_MAIL

2.90 PidLidDepartment

Canonical name: PidLidDepartment

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008010

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#)

Alternate names: dispidDepartment

2.91 PidLidDirectory

Canonical name: PidLidDirectory

Description: Specifies the directory server to be used with NetMeeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008242

Data type: PtypString, 0x001F

Area: Conferencing

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidDirectory

2.92 PidLidDistributionListChecksum

Canonical name: PidLidDistributionListChecksum

Description: Specifies the 32-bit cyclic redundancy check (CRC-32) polynomial checksum, as specified in [ISO/IEC 8802-3], calculated on the value of PidLidDistributionListMembers.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804C

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidDLChecksum

2.93 PidLidDistributionListMembers

Canonical name: PidLidDistributionListMembers

Description: Specifies the list of EntryIds of the objects corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008055

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXCDATA\]](#)

Alternate names: dispidDLMembers

2.94 PidLidDistributionListName

Canonical name: PidLidDistributionListName

Description: Specifies the name of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008053

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidDLName

2.95 PidLidDistributionListOneOffMembers

Canonical name: PidLidDistributionListOneOffMembers

Description: Specifies the list of one-off EntryIds corresponding to the members of the personal distribution list.

Property set: PSEID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008054

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidDLOneOffMembers

2.96 PidLidDistributionListStream

Canonical name: PidLidDistributionListStream

Description: Specifies the list of EntryIds and one-off EntryIds corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008064

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidDLStream

2.97 PidLidEmail1AddressType

Canonical name: PidLidEmail1AddressType

Description: Specifies the address type of an electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008082

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1AddrType

2.98 PidLidEmail1DisplayName

Canonical name: PidLidEmail1DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008080

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1DisplayName

2.99 PidLidEmail1EmailAddress

Canonical name: PidLidEmail1EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008083

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1EmailAddress

2.100 PidLidEmail1OriginalDisplayName

Canonical name: PidLidEmail1OriginalDisplayName

Description: Specifies the SMTP e-mail address corresponding to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008084

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidEmail1OriginalDisplayName

2.101 PidLidEmail1OriginalEntryId

Canonical name: PidLidEmail1OriginalEntryId

Description: Specifies the EntryId of the object corresponding to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008085

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidEmail1OriginalEntryID

2.102 PidLidEmail1RichTextFormat

Canonical name: PidLidEmail1RichTextFormat

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008086

Data type: PtypBoolean, 0x000B

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#)

Alternate names: dispidEmail1RTF

2.103 PidLidEmail2AddressType

Canonical name: PidLidEmail2AddressType

Description: Specifies the address type of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008092

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2AddrType

2.104 PidLidEmail2DisplayName

Canonical name: PidLidEmail2DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008090

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2DisplayName

2.105 PidLidEmail2EmailAddress

Canonical name: PidLidEmail2EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008093

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2EmailAddress

2.106 PidLidEmail2OriginalDisplayName

Canonical name: PidLidEmail2OriginalDisplayName

Description: Specifies the SMTP e-mail address corresponding to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008094

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidEmail2OriginalDisplayName

2.107 PidLidEmail2OriginalEntryId

Canonical name: PidLidEmail2OriginalEntryId

Description: Specifies the EntryId of the object corresponding to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008095

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidEmail2OriginalEntryID

2.108 PidLidEmail2RichTextFormat

Canonical name: PidLidEmail2RichTextFormat

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008096

Data type: PtypBoolean, 0x000B

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#)

Alternate names: dispidEmail1RTF

2.109 PidLidEmail3AddressType

Canonical name: PidLidEmail3AddressType

Description: Specifies the address type of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3AddrType

2.110 PidLidEmail3DisplayName

Canonical name: PidLidEmail3DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A0

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3DisplayName

2.111 PidLidEmail3EmailAddress

Canonical name: PidLidEmail3EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3EmailAddress

2.112 PidLidEmail3OriginalDisplayName

Canonical name: PidLidEmail3OriginalDisplayName

Description: Specifies the SMTP e-mail address corresponding to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: Specifies the EntryId of the object corresponding to this electronic address.

Alternate names: dispidEmail3OriginalDisplayName

2.113 PidLidEmail3OriginalEntryId

Canonical name: PidLidEmail3OriginalEntryId

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A5

Data type: PtypBinary, 0x0102

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#)

Alternate names: dispidEmail3OriginalEntryID

2.114 PidLidEmail3RichTextFormat

Canonical name: PidLidEmail3RichTextFormat

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A6

Data type: PtypBoolean, 0x000B

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#)

Alternate names: dispidEmail1RTF

2.115 PidLidEmailList

Canonical name: PidLidEmailList

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008027

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#)

Alternate names: dispidEmailList

2.116 PidLidEndRecurrenceDate

Canonical name: PidLidEndRecurrenceDate

Description: Identifies the end date of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000F

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_date

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: LID_END_RECUR_DATE

2.117 PidLidEndRecurrenceTime

Canonical name: PidLidEndRecurrenceTime

Description: Identifies the end time of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000010

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_time

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: LID_END_RECUR_TIME

2.118 PidLidExceptionReplaceTime

Canonical name: PidLidExceptionReplaceTime

Description: Specifies the date and time, in UTC, within a recurrence pattern that an exception will replace.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008228

Data type: PtypTime, 0x0040

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidExceptionReplaceTime

2.119 PidLidFax1AddressType

Canonical name: PidLidFax1AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax1AddrType

2.120 PidLidFax1EmailAddress

Canonical name: PidLidFax1EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax1EmailAddress

2.121 PidLidFax1OriginalDisplayName

Canonical name: PidLidFax1OriginalDisplayName

Description: Contains the same value as PidTagNormalizedSubject.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax1OriginalDisplayName

2.122 PidLidFax1OriginalEntryId

Canonical name: PidLidFax1OriginalEntryId

Description: Specifies a one-off EntryId corresponding to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax1OriginalEntryID

2.123 PidLidFax2AddressType

Canonical name: PidLidFax2AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax2AddrType

2.124 PidLidFax2EmailAddress

Canonical name: PidLidFax2EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax2EmailAddress

2.125 PidLidFax2OriginalDisplayName

Canonical name: PidLidFax2OriginalDisplayName

Description: Contains the same value as PidTagNormalizedSubject.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax2OriginalDisplayName

2.126 PidLidFax2OriginalEntryId

Canonical name: PidLidFax2OriginalEntryId

Description: Specifies a one-off EntryId corresponding to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax2OriginalEntryID

2.127 PidLidFax3AddressType

Canonical name: PidLidFax3AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax3AddrType

2.128 PidLidFax3EmailAddress

Canonical name: PidLidFax3EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Adrsss {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax3EmailAddress

2.129 PidLidFax3OriginalDisplayName

Canonical name: PidLidFax3OriginalDisplayName

Description: Contains the same value as PidTagNormalizedSubject.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax3OriginalDisplayName

2.130 PidLidFax3OriginalEntryId

Canonical name: PidLidFax3OriginalEntryId

Description: Specifies a one-off EntryId corresponding to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFax3OriginalEntryID

2.131 PidLidFExceptionalAttendees

Canonical name: PidLidFExceptionalAttendees

Description: Indicates that the object is a Recurring Calendar object with one or more exceptions, and at least one of the Exception Embeddd Message objects has at least one RecipientRow.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822B

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidFExceptionalAttendees

2.132 PidLidFExceptionalBody

Canonical name: PidLidFExceptionalBody

Description: Indicates that the Exception Embedded Message object has a body that differs from the Recurring Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008206

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidFExceptionalBody

2.133 PidLidFileUnder

Canonical name: PidLidFileUnder

Description: Specifies the name under which to file a contact when displaying a list of contacts.

Property set: PSETID_Address {0006204-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008005

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFileUnder

2.134 PidLidFileUnderId

Canonical name: PidLidFileUnderId

Description: Specifies how to generate and recompute the value of the PidLidFileUnder property when other Contact Name properties change.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008006

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFileUnderId

2.135 PidLidFileUnderList

Canonical name: PidLidFileUnderList

Description: Specifies a list of possible values for PidLidFileUnderId.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008026

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidFileUnderList

2.136 PidLidFInvited

Canonical name: PidLidFInvited

Description: Indicates whether invitations have been sent for the meeting that this Meeting object represents.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008229

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/finvited

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidFInvited

2.137 PidLidFlagRequest

Canonical name: PidLidFlagRequest

Description: Contains user-specifiable text to be associated with the flag.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008530

Data type: typString, 0x001F

WebDAV: urn:schemas:httpmail:messageflag, http://schemas.microsoft.com/mapi/request

Area: Flagging

Defining References: [\[MS-OXOFLAG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidRequest

2.138 PidLidFlagString

Canonical name: PidLidFlagString

Description: Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

Property set: PSETD_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C0

Data type: typInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOFLAG\]](#)

Consuming References:

Alternate names: dispidFlagStringEnum

2.139 PidLidForwardInstance

Canonical name: PidLidForwardInstance

Description: Indicates whether the Meeting Request object represents an exception to a recurring series, and it was forwarded (even when forwarded by the organizer) rather than being an invitation sent by the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidFwrInstance

2.140 PidLidForwardNotificationRecipients

Canonical name: PidLidForwardNotificationRecipients

Description: Contains a list of RecipientRows that indicate the recipients of a meeting forward.

Property set: PSETID_Appointment {0062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008261

Data type: PtypBinary, 0x0102

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidForwardNotificationRecipients

2.141 PidLidFOthersAppointment

Canonical name: PidLidFOthersAppointment

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822F

Data type: PtypBoolean, 0x000B

Area: Meetings

References: [\[MS-XWDCAL\]](#)

Alternate names: dispidFOthersAppt, <http://schemas.microsoft.com/mapi/fothersappt>

2.142 PidLidFreeBusyLocation

Canonical name: PidLidFreeBusyLocation

Description: Specifies a URL path from which a client can retrieve free/busy information for the contact.

Property set: PSETID_Address{00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D8

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:fburl

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidFreeBusyLocation

2.143 PidLidGlobalObjectId

Canonical name: PidLidGlobalObjectId

Description: Contains the value of the PidLidGlobalObjectId property for an object that represents an exception to a recurring series.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000003

Data type: PtypBinary, 0x0102

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#)

Alternate names: LID_GLOBAL_OBJID

2.144 PidLidHasPicture

Canonical name: PidLidHasPicture

Description: Specifies whether the attachment has a picture.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008015

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidHasPicture

2.145 PidLidHomeAddress

Canonical name: PidLidHomeAddress

Description: Specifies the complete address of the contact's home address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:homepostaladdress

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidHomeAddress

2.146 PidLidHomeAddressCountryCode

Canonical name: PidLidHomeAddressCountryCode

Description: Specifies the country code portion of the contact's home address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DA

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidHomeAddressCountryCode

2.147 PidLidHtml

Canonical name: PidLidHtml

Description: Specifies the contact's business web page URL.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802B

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidHTML

2.148 PidLidICalendarDayOfWeekMask

Canonical name: PidLidICalendarDayOfWeekMask

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001001

Data type: PtypInteger32, 0x0003

Area: Calendar

References: [\[MS-XWDCAL\]](#)

Alternate names: http://schemas.microsoft.com/mapi/dayofweekmask

2.149 PidLidInboundICalStream

Canonical name: PidLidInboundICalStream

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827A

Data type: PtypBinary, 0x0102

Area: Calendar

References: [\[MS-OXCMAIL\]](#)

Alternate names: InboundICalStream, dispidInboundICalStream

2.150 PidLidInfoPathFormName

Canonical name: PidLidInfoPathFormName

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x85B1

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.151 PidLidInstantMessagingAddress

Canonical name: PidLidInstantMessagingAddress

Description: Specifies the contact's instant messaging address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008062

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#)

Alternate names: dispidInstMsg

2.152 PidLidIntendedBusyStatus

Canonical name: PidLidIntendedBusyStatus

Description: Contains the value of the PidLidBusyStatus property on the Meeting object in the organizer's calendar at the time the Meeting Request object or Meeting Update object was sent.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008224

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/intendedbusystatus>

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidIntendedBusyStatus

2.153 PidLidInternetAccountName

Canonical name: PidLidInternetAccountName

Description: Specifies the user-visible email account name through which the email message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008580

Data type: PtypString, 0x001F

Area: General Message Properties

Defining References: [\[MS-OXOMSG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#)

Alternate names: dispidInetAcctName

2.154 PidLidInternetAccountStamp

Canonical name: PidLidInternetAccountStamp

Description: Specifies the email account ID through which the email message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008581

Data type: PtypString, 0x001F

Area: General Message Properties

Defining References: [\[MS-OXOMSG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#)

Alternate names: dispidInetAcctStamp

2.155 PidLidIsException

Canonical name: PidLidIsException

Description: Indicates whether the object represents an exception (including an orphan instance).

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000A

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_exception

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_EXCEPTION

2.156 PidLidIsRecurring

Canonical name: PidLidIsRecurring

Description: Specifies whether the object is associated with a recurring series.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000005

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_recurring

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_RECURRING

2.157 PidLidIsSilent

Canonical name: PidLidIsSilent

Description: Indicates whether the user did not include any text in the body of the Meeting Response object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000004

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_silent

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_SILENT

2.158 PidLidLinkedTaskItems

Canonical name: PidLidLinkedTaskItems

Description: Indicates whether the user did not include any text in the body of the Meeting Response object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820C

Data type: PtypMultipleBinary, 0x1102

Area: Tasks

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidLinkedTaskItems

2.159 PidLidLocation

Canonical name: PidLidLocation

Description: Specifies the location of the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008208

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:location

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidLocation

2.160 PidLidLogDocumentPosted

Canonical name: PidLidLogDocumentPosted

Description: Indicates whether the document was sent by e-mail or posted to a server folder during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008711

Data type: PtypBoolean, 0x000B

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogDocPosted

2.161 PidLidLogDocumentPrinted

Canonical name: PidLidLogDocumentPrinted

Description: Indicates whether the document was printed during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870E

Data type: PtypBoolean, 0x000B

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogDocPrinted

2.162 PidLidLogDocumentRouted

Canonical name: PidLidLogDocumentRouted

Description: Indicates whether the document was sent to a routing recipient during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008710

Data type: PtypBoolean, 0x000B

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogDocRouted

2.163 PidLidLogDocumentSaved

Canonical name: PidLidLogDocumentSaved

Description: Indicates whether the document was saved during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870F

Data type: PtypBoolean, 0x000B

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogDocSaved

2.164 PidLidLogDuration

Canonical name: PidLidLogDuration

Description: Contains the duration in minutes of the activity.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008707

Data type: PtypInteger32, 0x0003

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogDuration

2.165 PidLidLogEnd

Canonical name: PidLidLogEnd

Description: Contains the time at which the activity ended.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008708

Data type: PtypTime, 0x0040

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogEnd

2.166 PidLidLogFlags

Canonical name: PidLidLogFlags

Description: Contains metadata about the Journal object.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870C

Data type: PtypInteger32, 0x0003

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogFlags

2.167 PidLidLogStart

Canonical name: PidLidLogStart

Description: Contains the time at which the activity began.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008706

Data type: PtypTime, 0x0040

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogStart

2.168 PidLidLogType

Canonical name: PidLidLogType

Description: Briefly describes the activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008700

Data type: PtyString, 0x001F

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogType

2.169 PidLidLogTypeDesc

Canonical name: PidLidLogTypeDesc

Description: Describes the activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008712

Data type: PtypString, 0x001F

Area: Journal

Defining References: [\[MS-OXOJRNLI\]](#)

Consuming References:

Alternate names: dispidLogTypeDesc

2.170 PidLidMeetingType

Canonical name: PidLidMeetingType

Description: Indicates the type of Meeting Request object or Meeting Update object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000026

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidMeetingType

2.171 PidLidMeetingWorkspaceUrl

Canonical name: PidLidMeetingWorkspaceUrl

Description: Specifies the URL of the Meeting Workspace that is associated with a Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008209

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/meetingworkspaceurl

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidMWSURL

2.172 PidLidMonthInterval

Canonical name: PidLidMonthInterval

Description: Indicates the monthly interval of the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA03F1305}

Property long ID (LID): 0x00000013

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/month_interval

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_MONTH_INTERVAL

2.173 PidLidMonthOfYear

Canonical name: PidLidMonthOfYear

Description: Indicates the month of the year that the appointment or meeting occurs.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001006

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/monthofyear

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names:

2.174 PidLidMonthOfYearMask

Canonical name: PidLidMonthOfYearMask

Description: Indicates the month of the year that the appointment or meeting occurs.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000017

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/moy_mask

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: LID_MOY_MASK

2.175 PidLidNetShowUrl

Canonical name: PidLidNetShowUrl

Description: Specifies the URL to be launched when the user joins the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008248

Data type: PtypString, 0x001F

Area: Conferencing

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-oxcical\]](#), [\[MS-oxormdr\]](#)

Alternate names: dispidNetShowURL

2.176 PidLidNoEndDateFlag

Canonical name: PidLidNoEndDateFlag

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100B

Data type: PtypBoolean, 0x000B

Area: Calendar

References: [\[MS-XWDCAL\]](#)

Alternate names: http://schemas.microsoft.com/mapi/fnoenddate

2.177 PidLidNonSendableBcc

Canonical name: PidLidNonSendableBcc

Description: Contains a list of all the unsendable attendees who are also resources.

Property set: PSETID_Common {00062008-0000-0000-C00-000000000046}

Property long ID (LID): 0x00008538

Data type: typString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendablebcc

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableBCC

2.178 PidLidNonSendableCc

Canonical name: PidLidNonSendableCc

Description: Contains a list of all the unsendable attendees who are also optional attendees.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008537

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendablecc

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableCC

2.179 PidLidNonSendableTo

Canonical name: PidLidNonSendableTo

Description: Contains a list of all the unsendable attendees who are also required attendees.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008536

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/nonsendableto

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableTo

2.180 PidLidNonSendBccTrackStatus

Canonical name: PidLidNonSendBccTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008545

Data type: PtypMultipleInteger32, 0x1003

WebDAV: <http://schemas.microsoft.com/mapi/nonsendbcctrackstatus>

Area: General Message Properties

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendBccTrackStatus

2.181 PidLidNonSendCcTrackStatus

Canonical name: PidLidNonSendCcTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008544

Data type: PtypMultipleInteger32, 0x1003

WebDAV: <http://schemas.microsoft.com/mapi/nonsendcctrackstatus>

Area: General Message Properties

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendCcTrackStatus

2.182 PidLidNonSendToTrackStatus

Canonical name: PidLidNonSendToTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008543

Data type: typMultipleInteger32, 0x1003

WebDAV: http://schemas.microsoft.com/mapi/nonsendtotrackstatus

Area: General Message Properties

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendToTrackStatus

2.183 PidLidNoteColor

Canonical name: PidLidNoteColor

Description: Specifies the suggested background color of the Note object.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B00

Data type: PtpInteger32, 0x0003

Area: Sticky Notes

Defining References: [\[MS-OXONOTE\]](#)

Consuming References:

Alternate names: dispidNoteColor

2.184 PidLidNoteHeight

Canonical name: PidLidNoteHeight

Description: Specifies the height of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B03

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining References: [\[MS-OXONOTE\]](#)

Consuming References:

Alternate names: dispidNoteHeight

2.185 PidLidNoteWidth

Canonical name: PidLidNoteWidth

Description: Specifies the width of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B02

Data type: PtpInteger32, 0x0003

Area: Sticky Notes

Defining References: [\[MS-OXONOTE\]](#)

Consuming References:

Alternate names: dispidNoteWidth

2.186 PidLidNoteX

Canonical name: PidLidNoteX

Description: Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a Note object.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B04

Data type: PtpInteger32, 0x0003

Area: Sticky Notes

Defining References: [\[MS-OXONOTE\]](#)

Consuming References:

Alternate names: dispidNoteX

2.187 PidLidNoteY

Canonical name: PidLidNoteY

Description: Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a Note object.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B05

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining References: [\[MS-OXONOTE\]](#)

Consuming References:

Alternate names: dispidNoteY

2.188 PidLidOccurrences

Canonical name: PidLidOccurrences

Description: Indicates the number of occurrences in the recurring appointment or meeting.

Property set: PSETID_Common {00062008-0000-000-C000-000000000046}

Property long ID (LID): 0x00001005

Data type: typInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/occurrences

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names:

2.189 PidLidOldLocation

Canonical name: PidLidOldLocation

Description: Indicates the original value of the PidLidLocation property before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000028

Data type: PtypString, 0x001F

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidOldLocation

2.190 PidLidOldRecurrenceType

Canonical name: PidLidOldRecurrenceType

Description: Indicates the recurrence pattern for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000018

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/recur_type

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: LID_RECUR_TYPE

2.191 PidLidOldWhenEndWhole

Canonical name: PidLidOldWhenEndWhole

Description: Indicates the original value of the PidLidAppointmentEndWhole property before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000002A

Data type: PtypTime, 0x0040

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidOldWhenEndWhole

2.192 PidLidOldWhenStartWhole

Canonical name: PidLidOldWhenStartWhole

Description: Indicates the original value of the PidLidAppointmentStartWhole property before a meeting update.

Property set: PSETID_Meting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000029

Data type: PtypTime, 0x0040

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidOldWhenStartWhole

2.193 PidLidOnlinePassword

Canonical name: PidLidOnlinePassword

Description: Specifies the password for a meeting on which the property PidLidConferencingType has the value 0x00000002.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008249

Data type: PtypString, 0x001F

Area: Conferencing

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidOnlinePassword

2.194 PidLidOptionalAttendees

Canonical name: PidLidOptionalAttendees

Description: Specifies optional attendees.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000007

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/optional_attendees

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_OPTIONAL_ATTENDEES

2.195 PidLidOrganizerAlias

Canonical name: PidLidOrganizerAlias

Description: Specifies the e-mail address of the Organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008243

Data type: PtypString, 0x001F

Area: Conferencing

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidOrgAlias

2.196 PidLidOriginalStoreEntryId

Canonical name: PidLidOriginalStoreEntryId

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008237

Data type: PtypBinary, 0x0102

Area: Meetings

References: [\[MS-OXOCAL\]](#)

Alternate names: dispidOrigStoreEid, <http://schemas.microsoft.com/mapi/origstoreeid>

2.197 PidLidOtherAddress

Canonical name: PidLidOtherAddress

Description: Specifies the complete address of the contact's other address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801C

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:otherpostaladdress

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidOtherAddress

2.198 PidLidOtherAddressCountryCode

Canonical name: PidLidOtherAddressCountryCode

Description: Specifies the country code portion of the contact's other address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DC

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidOtherAddressCountryCode

2.199 PidLidOwnerCriticalChange

Canonical name: PidLidOwnerCriticalChange

Description: Specifies the date and time at which a Meeting Request object was sent by the organizer.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000001A

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:dtstamp,
http://schemas.microsoft.com/mapi/owner_critical_change

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: LID_OWNER_CRITICAL_CHANGE

2.200 PidLidOwnerName

Canonical name: PidLidOwnerName

Description: Indicates the name of the owner of the mailbox.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/ownername

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidOwnerName

2.201 PidLidPercentComplete

Canonical name: PidLidPercentComplete

Description: Indicates whether a time-flagged Message object is completed or not.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008102

Data type: PtypFloating64, 0x0005

Area: Tasks

Defining References: [\[MS-OXOFLAG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidPercentComplete

2.202 PidLidPostalAddressId

Canonical name: PidLidPostalAddressId

Description: Specifies which physical address is the mailing address for this contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008022

Data type: PtypInteger32, 0x0003

WebDAV: urn:schemas:contacts:mailingaddressid

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidPostalAddressId

2.203 PidLidPostRssChannel

Canonical name: PidLidPostRssChannel

Description: Contains the contents of the title field from the XML of the Atom feed or RSS channel.

Property set: PSETID_PostRss {0006041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008904

Data type: PtypString, 0x001F

Area: RSS

Defining References: [\[MS-OXORSS\]](#)

Consuming References:

Alternate names: dispidPostRssChannel

2.204 PidLidPostRssChannelLink

Canonical name: PidLidPostRssChannelLink

Description: Contains the URL of the RSS or Atom feed that the XML file came from.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008900

Data type: PtypString, 0x001F

Area: RSS

Defining References: [\[MS-OXORSS\]](#)

Consuming References:

Alternate names: dispidPostRssChannelLink

2.205 PidLidPostRssItemGuid

Canonical name: PidLidPostRssItemGuid

Description: Contains a unique identifier for the RSS object.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008903

Data type: PtypString, 0x001F

Area: RSS

Defining References: [\[MS-OXORSS\]](#)

Consuming References:

Alternate names: dispidPostRssItemGuid

2.206 PidLidPostRssItemHash

Canonical name: PidLidPostRssItemHash

Description: Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008902

Data type: PtypInteger32, 0x0003

Area: RSS

Defining References: [\[MS-OXORSS\]](#)

Consuming References:

Alternate names: dispidPostRssItemHash

2.207 PidLidPostRssItemLink

Canonical name: PidLidPostRssItemLink

Description: Contains the URL of the link from the item.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008901

Data type: PtypString, 0x001F

Area: RSS

Defining References: [\[MS-OXORSS\]](#)

Consuming References:

Alternate names: dispidPostRssItemLink

2.208 PidLidPostRssItemXml

Canonical name: PidLidPostRssItemXml

Description: Contains the item element and all its sub-elements from an RSS feed, or the entry element and all its sub-elements from an Ato feed.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008905

Data type: PtypString, 0x001F

Area: RSS

Defining References: [\[MS-OXORSS\]](#)

Consuming References:

Alternate names: dispidPostRssItemXml

2.209 PidLidPostRssSubscription

Canonical name: PidLidPostRssSubscription

Description: Contains the user's preferred name for the subscription.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008906

Data type: PtypString, 0x001F

Area: RSS

Defining References: [\[MS-OXORSS\]](#)

Consuming References:

Alternate names: dispidPostRssSubscription

2.210 PidLidPrivate

Canonical name: PidLidPrivate

Description: Indicates whether the end-user wishes for this Message object to be hidden from other users who have access to the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008506

Data type: typBoolean, 0x000B

Area: General Message Properties

Defining References: [MS-OXCMSG](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidPrivate

2.211 PidLidPromptSendUpdate

Canonical name: PidLidPromptSendUpdate

Description: Indicates that the Meeting Response object was out-of-date when it was received.

Property set: PSETID_Common {00062008-000-0000-C000-000000000046}

Property long ID (LID): 0x00008045

Data type: PtypBoolean, 0x000B

Area: Meeting Response

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidPromptSendUpdate

2.212 PidLidRecurrenceDuration

Canonical name: PidLidRecurrenceDuration

Description: Identifies the length, in minutes, of the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100D

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/recurduration>

Area: Calendar

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names:

2.213 PidLidRecurrencePattern

Canonical name: PidLidRecurrencePattern

Description: Specifies a description of the recurrence pattern of the Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008232

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/recurpattern

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurPattern

2.214 PidLidRecurrenceType

Canonical name: PidLidRecurrenceType

Description: Specifies the recurrence type of the recurring series.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008231

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/recurtype

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurType

2.215 PidLidRecurring

Canonical name: PidLidRecurring

Description: Specifies whether the object represents a recurring series.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008223

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/recurring

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCADATA\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurring

2.216 PidLidReferenceEntryId

Canonical name: PidLidReferenceEntryId

Description: Specifies the value of the EntryId of the Contact object unless the Contact object is a copy of an earlier original.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BD

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidReferenceEID

2.217 PidLidReferredBy

Canonical name: PidLidReferredBy

Description: Specifies the name of the person who referred the contact to the user.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000800E

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:referredby

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidReferredBy

2.218 PidLidReminderDelta

Canonical name: PidLidReminderDelta

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008501

Data type: PtypInteger32, 0x0003

Area: Reminders

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderDelta, <http://schemas.microsoft.com/mapi/reminddelta>

2.219 PidLidReminderFileParameter

Canonical name: PidLidReminderFileParameter

Description: Specifies the filename of the sound that a client is to play when the reminder for that object becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851F

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/reminderfileparam>

Area: Reminders

Defining References: [\[MS-OXORMDR\]](#)

Consuming References: [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderFileParam

2.220 PidLidReminderOverride

Canonical name: PidLidReminderOverride

Description: Specifies whether the client is to respect the values PidLidReminderPlaySound and PidLidReminderFileParameter, or use the default values for those properties.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851C

Data type: PtypBoolean, 0x000B

WebDAV: <http://schemas.microsoft.com/mapi/reminderoverride>

Area: Reminders

Defining References: [\[MS-OXORMDR\]](#)

Consuming References: [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderOverride

2.221 PidLidReminderPlaySound

Canonical name: PidLidReminderPlaySound

Description: Specifies whether the client is to play a sound when the reminder becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851E

Data type: PtypBoolean, 0x000B

WebDAV: <http://schemas.microsoft.com/mapi/reminderplaysound>

Area: Reminders

Defining References: [\[MS-OXORMDR\]](#)

Consuming References: [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderPlaySound

2.222 PidLidReminderSet

Canonical name: PidLidReminderSet

Description: Specifies whether a reminder is set on the object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008503

Data type: PtypBoolean, 0x000B

WebDAV: <http://schemas.microsoft.com/mapi/reminderset>

Area: Reminders

Defining References: [\[MS-OXORMDR\]](#)

Consuming References: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderSet

2.223 PidLidReminderSignalTime

Canonical name: PidLidReminderSignalTime

Description: Specifies the point in time when a reminder transitions from pending to overdue.

Property set: PSETID_Common {00062008-000-0000-C000-000000000046}

Property long ID (LID): 0x00008560

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/remindernexttime>

Area: Reminders

Defining References: [\[MS-OXORMDR\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidReminderNextTime

2.224 PidLidReminderTime

Canonical name: PidLidReminderTime

Description: Specifies the initial signal time for non-Calendar objects. For Calendar objects.

Property set: PSETID_Common {00062008-000-0000-C000-000000000046}

Property long ID (LID): 0x00008502

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertime

Area: Reminders

Defining References: [\[MS-OXORMDR\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderTime

2.225 PidLidReminderTimeDate

Canonical name: PidLidReminderTimeDate

Description: Indicates the time and date of the reminder for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008505

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertimedate

Area: Reminders

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidReminderTimeDate

2.226 PidLidReminderTimeTime

Canonical name: PidLidReminderTimeTime

Description: Indicates the time of the reminder for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008504

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertimetime

Area: Reminders

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidReminderTimeTime

2.227 PidLidReminderType

Canonical name: PidLidReminderType

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851D

Data type: PtypInteger32, 0x0003

Area: Reminders

References: [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderType, <http://schemas.microsoft.com/mapi/remindertype>

2.228 PidLidRemoteStatus

Canonical name: PidLidRemoteStatus

Description: Indicates the remote status of the calendar item.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008511

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/remotestatus>

Area: Run-time configuration

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: dispidRemoteStatus

2.229 PidLidRequiredAttendees

Canonical name: PidLidRequiredAttendees

Description: Identifies required attendees for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000006

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/required_attendees

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_REQUIRED_ATTENDEES

2.230 PidLidResourceAttendees

Canonical name: PidLidResourceAttendees

Description: Identifies resource attendees for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000008

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/resource_attendees

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_RESOURCE_ATTENDEES

2.231 PidLidResponseStatus

Canonical name: PidLidResponseStatus

Description: Specifies the response status of an attendee.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008218

Data type: PtypInteger32, 0x0003

WebDAV: urn:schemas:calendar:attendeestatus,
http://schemas.microsoft.com/mapi/responsestatus

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidResponseStatus

2.232 PidLidSendMeetingAsIcal

Canonical name: PidLidSendMeetingAsIcal

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008200

Data type: PtypBoolean, 0x000B

Area: Conferencing

References: [\[MS-OXCICAL\]](#)

Alternate names: dispidSendMtgAsICAL

2.233 PidLidServerProcessed

Canonical name: PidLidServerProcessed

Description: Indicates whether the Meeting Request Object or Meeting Update Object has been processed.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CC

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidExchangeProcessed

2.234 PidLidServerProcessingActions

Canonical name: PidLidServerProcessingActions

Description: Indicates what processing actions have been taken on this Meeting Request Object or Meeting Update Object.

Property set: SETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CD

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References:

Alternate names: dispidExchangeProcessingAction

2.235 PidLidSharingAnonymity

Canonical name: PidLidSharingAnonymity

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A19

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingAnonymity

2.236 PidLidSharingBindingEntryId

Canonical name: PidLidSharingBindingEntryId

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2D

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingBindingEid

2.237 PidLidSharingBrowseUrl

Canonical name: PidLidSharingBrowseUrl

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A51

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingBrowseUrl

2.238 PidLidSharingCapabilities

Canonical name: PidLidSharingCapabilities

Description: Indicates that the Sharing Message object relates to a special folder.

Property set: PSETID_Sharing {00062040-0000-0000-0000-000000000046}

Property long ID (LID): 0x00008A17

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingCaps

2.239 PidLidSharingConfigurationUrl

Canonical name: PidLidSharingConfigurationUrl

Description: Contains a zero-length string.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A24

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingConfigUrl

2.240 PidLidSharingDataRangeEnd

Canonical name: PidLidSharingDataRangeEnd

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A45

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingDataRangeEnd

2.241 PidLidSharingDataRangeStart

Canonical name: PidLidSharingDataRangeStart

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A44

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingDataRangeStart

2.242 PidLidSharingDetail

Canonical name: PidLidSharingDetail

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2B

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingDetail

2.243 PidLidSharingExtensionXml

Canonical name: PidLidSharingExtensionXml

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A21

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingExtXml

2.244 PidLidSharingFilter

Canonical name: PidLidSharingFilter

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A13

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingFilter

2.245 PidLidSharingFlags

Canonical name: PidLidSharingFlags

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0A

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingFlags

2.246 PidLidSharingFlavor

Canonical name: PidLidSharingFlavor

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A18

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingFlavor

2.247 PidLidSharingFolderEntryId

Canonical name: PidLidSharingFolderEntryId

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A15

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingFolderEid

2.248 PidLidSharingIndexEntryId

Canonical name: PidLidSharingIndexEntryId

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2E

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingIndexEid

2.249 PidLidSharingInitiatorEntryId

Canonical name: PidLidSharingInitiatorEntryId

Description: Contains the value of PidTagEntryId for the Address Book object of the currently loggen-on user.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A09

Data type: PtypBinary, 0x0102

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingInitiatorEid

2.250 PidLidSharingInitiatorName

Canonical name: PidLidSharingInitiatorName

Description: Contains the value of PidTagDisplayName from the Address Book object identified by PidLidSharingInitiatorEntryId.

Propertyset: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A07

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingInitiatorName

2.251 PidLidSharingInitiatorSntp

Canonical name: PidLidSharingInitiatorSntp

Description: Contains the value of PidTagSntpAddress from the AddressBook object identified by PidLidSharingInitiatorEntryId.

Property et: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A08

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingInitiatorSntp

2.252 PidLidSharingInstanceGuid

Canonical name: PidLidSharingInstanceGuid

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1C

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingInstanceGuid

2.253 PidLidSharingLastAutoSyncTime

Canonical name: PidLidSharingLastAutoSyncTime

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A55

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLastAutoSync

2.254 PidLidSharingLastSyncTime

Canonical name: PidLidSharingLastSyncTime

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1F

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLastSync

2.255 PidLidSharingLocalComment

Canonical name: PidLidSharingLocalComment

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4D

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLocalComment

2.256 PidLidSharingLocalLastModificationTime

Canonical name: PidLidSharingLocalLastModificationTime

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A23

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLocalLastMod

2.257 PidLidSharingLocalName

Canonical name: PidLidSharingLocalName

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0F

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLocalName

2.258 PidLidSharingLocalPath

Canonical name: PidLidSharingLocalPath

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0E

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLocalPath

2.259 PidLidSharingLocalStoreUid

Canonical name: PidLidSharingLocalStoreUid

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A49

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLocalStoreUid

2.260 PidLidSharingLocalType

Canonical name: PidLidSharingLocalType

Description: Contains the value of PidTagContainerClass of the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A14

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingLocalType

2.261 PidLidSharingLocalUid

Canonical name: PidLidSharingLocalUid

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A10

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingLocalUid

2.262 PidLidSharingOriginalMessageEntryId

Canonical name: PidLidSharingOriginalMessageEntryId

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A29

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingOriginalMessageEid

2.263 PidLidSharingParentBindingEntryId

Canonical name: PidLidSharingParentBindingEntryId

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A5C

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingParentBindingEid

2.264 PidLidSharingParticipants

Canonical name: PidLidSharingParticipants

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1E

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingParticipants

2.265 PidLidSharingPermissions

Canonical name: PidLidSharingPermissions

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1B

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingPermissions

2.266 PidLidSharingProviderExtension

Canonical name: PidLidSharingProviderExtension

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0B

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingProviderExtension

2.267 PidLidSharingProviderGuid

Canonical name: PidLidSharingProviderGuid

Description: Contains the value %xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.46.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A01

Data type: PtypBinary, 0x0102

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingProviderGuid

2.268 PidLidSharingProviderName

Canonical name: PidLidSharingProviderName

Description: Contains a user-displayable name of the sharing provider identified by PidLidSharingProviderGuid.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A02

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming Reference:

Alternate names: dispidSharingProviderName

2.269 PidLidSharingProviderUrl

Canonical name: PidLidSharingProviderUrl

Description: Contains a URL related to the sharing provider identified by PidLidSharingProviderGuid.

Property set: PSETID_Sharing {0002040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A03

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingProviderUrl

2.270 PidLidSharingRangeEnd

Canonical name: PidLidSharingRangeEnd

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A47

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRangeEnd

2.271 PidLidSharingRangeStart

Canonical name: PidLidSharingRangeStart

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A46

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRangeStart

2.272 PidLidSharingReciprocation

Canonical name: PidLidSharingReciprocation

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1A

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingReciprocation

2.273 PidLidSharingRemoteByteSize

Canonical name: PidLidSharingRemoteByteSize

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4B

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemoteByteSize

2.274 PidLidSharingRemoteComment

Canonical name: PidLidSharingRemoteComment

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2F

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemoteComment

2.275 PidLidSharingRemoteCrc

Canonical name: PidLidSharingRemoteCrc

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4C

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemoteCrc

2.276 PidLidSharingRemoteLastModificationTime

Canonical name: PidLidSharingRemoteLastModificationTime

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A22

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemoteLastMod

2.277 PidLidSharingRemoteMessageCount

Canonical name: PidLidSharingRemoteMessageCount

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4F

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemoteMsgCount

2.278 PidLidSharingRemoteName

Canonical name: PidLidSharingRemoteName

Description: Contains the value of PidTagDisplayName on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000000000000046}

Property long ID (LID): 0x00008A05

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingRemoteName

2.279 PidLidSharingRemotePass

Canonical name: PidLidSharingRemotePass

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0D

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemotePass

2.280 PidLidSharingRemotePath

Canonical name: PidLidSharingRemotePath

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A04

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemotePath

2.281 PidLidSharingRemoteStoreUid

Canonical name: PidLidSharingRemoteStoreUid

Description: Contains a hexadecimal string representation of the value of PidTagStoreEntryId on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A48

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingRemoteStoreUid

2.282 PidLidSharingRemoteType

Canonical name: PidLidSharingRemoteType

Description: Contains the same value as PidLidSharingLocalType.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1D

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingRemoteType

2.283 PidLidSharingRemoteUid

Canonical name: PidLidSharingRemoteUid

Description: Contains the hexadecimal string representation of the value of PidTagEntryId on the folder being shared.

Property set: PSTID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A06

Data type: PtypString, 0x001F

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingRemoteUid

2.284 PidLidSharingRemoteUser

Canonical name: PidLidSharingRemoteUser

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0C

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemoteUser

2.285 PidLidSharingRemoteVersion

Canonical name: PidLidSharingRemoteVersion

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A5B

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRemoteVersion

2.286 PidLidSharingResponseTime

Canonical name: PidLidSharingResponseTime

Description: Contains the time at which the recipient of the sharing request sent a sharing response.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A28

Data type: PtypTime, 0x0040

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References

Alternate names: dispidSharingResponseTime

2.287 PidLidSharingResponseType

Canonical name: PidLidSharingResponseType

Description: Contains the type of response with which the recipient of the sharing request responded.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A27

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining References: [\[MS-OXSHARE\]](#)

Consuming References:

Alternate names: dispidSharingResponseType

2.288 PidLidSharingRoamLog

Canonical name: PidLidSharingRoamLog

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4E

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingRoamLog

2.289 PidLidSharingStart

Canonical name: PidLidSharingStart

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A25

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingStart

2.290 PidLidSharingStatus

Canonical name: PidLidSharingStatus

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A00

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingStatus

2.291 PidLidSharingStop

Canonical name: PidLidSharingStop

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A26

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingStop

2.292 PidLidSharingSyncFlags

Canonical name: PidLidSharingSyncFlags

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A60

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingSyncFlags

2.293 PidLidSharingSyncInterval

Canonical name: PidLidSharingSyncInterval

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2A

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingSyncInterval

2.294 PidLidSharingTimeToLive

Canonical name: PidLidSharingTimeToLive

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2C

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingTimeToLive

2.295 PidLidSharingTimeToLiveAuto

Canonical name: PidLidSharingTimeToLiveAuto

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A56

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingTimeToLiveAuto

2.296 PidLidSharingWorkingHoursDays

Canonical name: PidLidSharingWorkingHoursDays

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A42

Data type: PtypInteger32, 0x0003

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingWorkingHoursDays

2.297 PidLidSharingWorkingHoursEnd

Canonical name: PidLidSharingWorkingHoursEnd

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A41

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingWorkingHoursEnd

2.298 PidLidSharingWorkingHoursStart

Canonical name: PidLidSharingWorkingHoursStart

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A40

Data type: PtypTime, 0x0040

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingWorkingHoursStart

2.299 PidLidSharingWorkingHoursTimeZone

Canonical name: PidLidSharingWorkingHoursTimeZone

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A43

Data type: PtypBinary, 0x0102

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names: dispidSharingWorkingHoursTZ

2.300 PidLidSideEffects

Canonical name: PidLidSideEffects

Description: Specifies how a Message object is handled by the client when acting on end-user input.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008510

Data type: PtypInteger32, 0x0003

Area: Run-time configuration

Defining References: [\[MS-OXCMSG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidSideEffects

2.301 PidLidSingleBodyICal

Canonical name: PidLidSingleBodyICal

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827B

Data type: PtypBoolean, 0x000B

Area: Calendar

References: [\[MS-OXCMAIL\]](#)

Alternate names: IsSingleBodyICal, dispidIsSingleBodyICal

2.302 PidLidSingleInvite

Canonical name: PidLidSingleInvite

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000B

Data type: PtypBoolean, 0x000B

Area: Meetings

References: [\[MS-OXCICAL\]](#)

Alternate names: LID_SINGLE_INVITE

2.303 PidLidSmartNoAttach

Canonical name: PidLidSmartNoAttach

Description: Indicates whether the Message object has no end-user visible attachments.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008514

Data type: PtypBoolean, 0x000B

Area: Run-time configuration

Defining References: [\[MS-OXCMSG\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: dispidSmartNoAttach

2.304 PidLidSpamOriginalFolder

Canonical name: PidLidSpamOriginalFolder

Description: Specifies which folder a message was in before it was filtered into the Junk E-mail folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000859C

Data type: PtypBinary, 0x0102

Area: Spam

Defining References: [\[MS-OXCSPAM\]](#)

Consuming References:

Alternate names: dispidSpamOriginalFolder

2.305 PidLidStartRecurrenceDate

Canonical name: PidLidStartRecurrenceDate

Description: Identifies the start date of the recurrence pattern.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000D

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_date

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: LID_START_RECUR_DATE

2.306 PidLidStartRecurrenceTime

Canonical name: PidLidStartRecurrenceTime

Description: Identifies the start time of the recurrence pattern.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000E

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_time

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References:

Alternate names: LID_START_RECUR_TIME

2.307 PidLidTaskAcceptanceState

Canonical name: PidLidTaskAcceptanceState

Description: Indicates the acceptance state of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000812A

Data type: PtpInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskDelegValue

2.308 PidLidTaskAccepted

Canonical name: PidLidTaskAccepted

Description: Indicates whether a task assignee has replied to a task request for this Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008108

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXOSFLD\]](#)

Alternate names: dispidTaskAccepted

2.309 PidLidTaskActualEffort

Canonical name: PidLidTaskActualEffort

Description: Indicates the number of minutes that the user actually spent working on a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008110

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskActualEffort

2.310 PidLidTaskAssigner

Canonical name: PidLidTaskAssigner

Description: Specifies the name of the user that last assigned the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008121

Data type: PtypString, 0x001F

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskDelegator

2.311 PidLidTaskAssigners

Canonical name: PidLidTaskAssigners

Description: Contains a stack of entries, each representing a task assigner.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008117

Data type: PtypBinary, 0x0102

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskMyDelegators

2.312 PidLidTaskComplete

Canonical name: PidLidTaskComplete

Description: Indicates that the task has been completed.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811C

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#)

Alternate names: dispidTaskComplete

2.313 PidLidTaskCustomFlags

Canonical name: PidLidTaskCustomFlags

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008139

Data type: PtypInteger32, 0x0003

Area: Tasks

References: [\[MS-OXOTASK\]](#)

Alternate names: dispidTaskActualEffort

2.314 PidLidTaskDateCompleted

Canonical name: PidLidTaskDateCompleted

Description: Specifies the date when the user completed work on the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000810F

Data type: PtypTime, 0x0040

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#)

Alternate names: dispidTaskDateCompleted

2.315 PidLidTaskDeadOccurrence

Canonical name: PidLidTaskDeadOccurrence

Description: Indicates whether new occurrences remain to be generated.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008109

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskDeadOccur

2.316 PidLidTaskDueDate

Canonical name: PidLidTaskDueDate

Description: Specifies the date by which the user expects work on the task to be complete.

Property set: PSETID_Task {00062003-0000-000-C000-000000000046}

Property long ID (LID): 0x00008105

Data type: PtpTime, 0x0040

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskDueDate

2.317 PidLidTaskEstimatedEffort

Canonical name: PidLidTaskEstimatedEffort

Description: Indicates the number of minutes that the user expects to work on a task.

Property set: PSETID_Task {00062003-0000-0000-C00-000000000046}

Property long ID (LID): 0x00008111

Data type: PtpInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskEstimatedEffort

2.318 PidLidTaskFCreator

Canonical name: PidLidTaskFCreator

Description: Indicates that the Task object was originally created by the action of the current user or user agent instead of by the processing of a task request.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811E

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskFCreator

2.319 PidLidTaskFFixOffline

Canonical name: PidLidTaskFFixOffline

Description: Indicates the accuracy of PidLidTaskOwner.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property lng ID (LID): 0x0000812C

Data type: PtpBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskFFixOffline

2.320 PidLidTaskFRecurring

Canonical name: PidLidTaskFRecurring

Description: Indicates whether the task includes a recurrence pattern.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008126

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskFRecur

2.321 PidLidTaskGlobalId

Canonical name: PidLidTaskGlobalId

Description: Contains a unique GUID for this task, used to locate an existing task upon receipt of a task response or task update.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008519

Data type: PtypBinary, 0x0102

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskGlobalObjId

2.322 PidLidTaskHistory

Canonical name: PidLidTaskHistory

Description: Indicates the type of change that was last made to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811A

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskHistory

2.323 PidLidTaskLastDelegate

Canonical name: PidLidTaskLastDelegate

Description: Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008125

Data type: PtypString, 0x001F

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskLastDelegate

2.324 PidLidTaskLastUpdate

Canonical name: PidLidTaskLastUpdate

Description: Contains the date and time of the most recent change made to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008115

Data type: PtypTime, 0x0040

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskLastUpdate

2.325 PidLidTaskLastUser

Canonical name: PidLidTaskLastUser

Description: Contains the name of the most recent user to have been the task owner.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008122

Data type: PtypString, 0x001F

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskLastUser

2.326 PidLidTaskMode

Canonical name: PidLidTaskMode

Description: Specifies the assignment status of the embedded Task object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008518

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidTaskMode

2.327 PidLidTaskMultipleRecipients

Canonical name: PidLidTaskMultipleRecipients

Description: Provides optimization hints about the recipients of a Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008120

Data type: PtpInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskMultRecips

2.328 PidLidTaskNoCompute

Canonical name: PidLidTaskNoCompute

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008124

Data type: PtypBoolean, 0x000B

Area: Tasks

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskNoCompute

2.329 PidLidTaskOrdinal

Canonical name: PidLidTaskOrdinal

Description: Provides an aid to custom sorting of Task objects.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008123

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskOrdinal

2.330 PidLidTaskOwner

Canonical name: PidLidTaskOwner

Description: Contains the name of the task owner.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID(LID): 0x0000811F

Data type: PtpString, 0x001F

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskOwner

2.331 PidLidTaskOwnership

Canonical name: PidLidTaskOwnership

Description: Indicates the role of the current user relative to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008129

Data type: PtpInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskOwnership

2.332 PidLidTaskRecurrence

Canonical name: PidLidTaskRecurrence

Description: Contains a RecurrencePattern structure that provides information about recurring tasks.

Property set: PSETID_Task {0006203-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008116

Data type: PtypBinary, 0x0102

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskRecur

2.333 PidLidTaskResetReminder

Canonical name: PidLidTaskResetReminder

Description: Indicates whether future instances of recurring tasks need reminders, even though PidLidReminderSet is 0x00.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008107

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskResetReminder

2.334 PidLidTaskRole

Canonical name: PidLidTaskRole

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008127

Data type: PtypString, 0x001F

Area: Tasks

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidTaskRole

2.335 PidLidTaskStartDate

Canonical name: PidLidTaskStartDate

Description: Specifies the date on which the user expects work on the task to begin.

Property set: PSETID_Task {00062003-0000-0000-C00-000000000046}

Property long ID (LID): 0x00008104

Data type: PtpTime, 0x0040

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskStartDate

2.336 PidLidTaskState

Canonical name: PidLidTaskState

Description: Indicates the current assignment state of the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000004}

Property long ID (LID): 0x00008113

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: dispidTaskState

2.337 PidLidTaskStatus

Canonical name: PidLidTaskStatus

Description: Specifies the status of a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008101

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: dispidTaskStatus

2.338 PidLidTaskStatusOnComplete

Canonical name: PidLidTaskStatusOnComplete

Description: Indicates whether the task assignee has been requested to send an e-mail message update when the task assignee completes the assigned task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008119

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskSOC

2.339 PidLidTaskUpdates

Canonical name: PidLidTaskUpdates

Description: Indicates whether the task assignee has been requested to send a task update when the assigned Task object changes.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811B

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References:

Alternate names: dispidTaskUpdates

2.340 PidLidTaskVersion

Canonical name: PidLidTaskVersion

Description: Indicates which copy is the latest update of a Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008112

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining References: [\[MS-OXOTASK\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTaskVersion

2.341 PidLidTeamTask

Canonical name: PidLidTeamTask

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008103

Data type: PtypBoolean, 0x000B

Area: Tasks

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTeamTask

2.342 PidLidTimeZone

Canonical name: PidLidTimeZone

Description: Specifies information about the time zone of a recurring meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/time_zone

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_TIME_ZONE

2.343 PidLidTimeZoneDescription

Canonical name: PidLidTimeZoneDescription

Description: Specifies a human-readable description of the time zone that is represented by the data in the PidLidTimeZoneStruct property.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008234

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/timezonedesc>

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidTimeZoneDesc

2.344 PidLidTimeZoneStruct

Canonical name: PidLidTimeZoneStruct

Description: Specifies time zone information for a recurring meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008233

Data type: PtypBinary, 0x0102

WebDAV: http://schemas.microsoft.com/mapi/timezonestruct

Area: Calendar

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidTimeZoneStruct

2.345 PidLidToAttendeesString

Canonical name: PidLidToAttendeesString

Description: Contains a list of all the sendable attendees who are also required attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823B

Data type: PtypString, 0x001F

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: dispidToAttendeesString

2.346 PidLidToDoOrdinalDate

Canonical name: PidLidToDoOrdinalDate

Description: Contains the current time in UTC, used to determine the sort order of objects in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A0

Data type: PtypTime, 0x0040

Area: Tasks

Defining References: [\[MS-OXOFLAG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#)

Alternate names: dispidToDoOrdinalDate

2.347 PidLidToDoSubOrdinal

Canonical name: PidLidToDoSubOrdinal

Description: Contains numerals "0" through "9" that are used to break a tie when PidLidToDoOrdinalDate is used to perform a sort of objects.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A1

Data type: PtypString, 0x001F

Area: Tasks

Defining References: [\[MS-OXOFLAG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#)

Alternate names: dispidToDoSubOrdinal

2.348 PidLidToDoTitle

Canonical name: PidLidToDoTitle

Description: Contains user-specifiable text to identify this Message object in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A4

Data type: PtypString, 0x001F

Area: Tasks

Defining References: [\[MS-OXOFLAG\]](#)

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

Alternate names: dispidToDoTitle

2.349 PidLidTrustRecipientHighlights

Canonical name: PidLidTrustRecipientHighlights

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823E

Data type: PtypBoolean, 0x000B

Area: Meetings

References: [\[MS-OXOCAL\]](#)

Alternate names: dispidTrustRecipHighlights

2.350 PidLidUseTnef

Canonical name: PidLidUseTnef

Description: Specifies whether Transport Neutral Encapsulation Format (TNEF) is to be included on a message when the message is converted from TNEF to MIME or SMTP format.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008582

Data type: PtypBoolean, 0x000B

Area: Run-time configuration

Defining References: [\[MS-OXOMSG\]](#)

Consuming References: [\[MS-OXCFCICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidUseTNEF

2.351 PidLidValidFlagStringProof

Canonical name: PidLidValidFlagStringProof

Description: Contains the value of PidTagMessageDeliveryTime when modifying PidLidFlagRequest.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BF

Data type: PtypTime, 0x0040

Area: Tasks

Defining References: [\[MS-OXOFLAG\]](#)

Consuming References: [\[MS-OXODOC\]](#)

Alternate names: dispidValidFlagStringProof

2.352 PidLidVerbResponse

Canonical name: PidLidVerbResponse

Description: Specifies the voting option that a respondent has selected.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008524

Data type: PtypString, 0x001F

Area: General Message Properties

Defining References: [\[MS-OXOMSG\]](#)

Consuming References:

Alternate names: dispidVerbResponse

2.353 PidLidVerbStream

Canonical name: PidLidVerbStream

Description: Specifies what voting responses the user can make in response to the message.

Property set: PSETID_Common {00062008-0000-000-C000-000000000046}

Property long ID (LID): 0x00008520

Data type: typBinary, 0x0102

Area: Run-time configuration

Defining References: [\[MS-OXOMSG\]](#)

Consuming References:

Alternate names: dispidVerbStream

2.354 PidLidWeddingAnniversaryLocal

Canonical name: PidLidWeddingAnniversaryLocal

Description: Specifies the wedding anniversary of the contact, at 0:00 in the client's local time zone and it is saved without any time zone conversions.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DF

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidApptAnniversaryLocal

2.355 PidLidWeekInterval

Canonical name: PidLidWeekInterval

Description: Identifies the number of weeks that occur between each meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00A003F1305}

Property long ID (LID): 0x00000012

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/week_interval

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_WEEK_INTERVAL

2.356 PidLidWhere

Canonical name: PidLidWhere

Description: Contains the value of the PidLidLocation property from the associated Meeting object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000002

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/where

Area: Meetings

Defining References: [\[MS-OXOCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_WHERE

2.357 PidLidWorkAddress

Canonical name: PidLidWorkAddress

Description: Specifies the complete address of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-00000000046}

Property long ID (LID): 0x0000801B

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:workaddress

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddress

2.358 PidLidWorkAddressCity

Canonical name: PidLidWorkAddressCity

Description: Specifies the city or locality portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-00000000046}

Property long ID (LID): 0x00008046

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:l

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressCity

2.359 PidLidWorkAddressCountry

Canonical name: PidLidWorkAddressCountry

Description: Specifies the country or region portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008049

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:co

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressCountry

2.360 PidLidWorkAddressCountryCode

Canonical name: PidLidWorkAddressCountryCode

Description: Specifies the country code portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DB

Data type: PtypString, 0x001F

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References:

Alternate names: dispidWorkAddressCountryCode

2.361 PidLidWorkAddressPostalCode

Canonical name: PidLidWorkAddressPostalCode

Description: Specifies the postal code (ZIP code) portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008048

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postalcode

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressPostalCode

2.362 PidLidWorkAddressPostOfficeBox

Canonical name: PidLidWorkAddressPostOfficeBox

Description: Specifies the post office box portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C00-000000000046}

Property long ID (LID): 0x0000804A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postofficebox

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressPostOfficeBox

2.363 PidLidWorkAddressState

Canonical name: PidLidWorkAddressState

Description: Specifies the state or province portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008047

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:st

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#)

Alternate names: dispidWorkAddressState

2.364 PidLidWorkAddressStreet

Canonical name: PidLidWorkAddressStreet

Description: Specifies the street portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008045

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:street

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressStreet

2.365 PidLidYearInterval

Canonical name: PidLidYearInterval

Description: Indicates the yearly interval of the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA00F1305}

Property long ID (LID): 0x00000014

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/year_interval

Area: Meetings

Defining References: [\[MS-XWDCAL\]](#)

Consuming References: [\[MS-OXCICAL\]](#)

Alternate names: LID_YEAR_INTERVAL

2.366 PidLidYomiCompanyName

Canonical name: PidLidYomiCompanyName

Description: Specifies the phonetic pronunciation of the contact's company name.

Property set: PSETID_Address {00062004-0000-0000-C000000000000046}

Property long ID (LID): 0x0000802E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomiorganization

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiCompanyName

2.367 PidLidYomiFirstName

Canonical name: PidLidYomiFirstName

Description: Specifies the phonetic pronunciation of the contact's given name.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802C

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/exchange/yomifirstname>

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiFirstName

2.368 PidLidYomiLastName

Canonical name: PidLidYomiLastName

Description: Specifies the phonetic pronunciation of the contact's surname.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802D

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/exchange/yomilastname>

Area: Contact Properties

Defining References: [\[MS-OXOCNTC\]](#)

Consuming References: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiLastName

2.369 PidNameAcceptLanguage

Canonical name: PidNameAcceptLanguage

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Accept-Language

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-OXCMAIL\]](#)

Alternate names: AcceptLanguage

2.370 PidNameApplicationName

Canonical name: PidNameApplicationName

Description: Specifies the application used to open the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: AppName

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#NameOfApplication

2.371 PidNameApproved

Canonical name: PidNameApproved

Description: Specifies the address of the moderator that approved and posted a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Approved

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:approved

2.372 PidNameApprovalAllowedDecisionMakers

Canonical name: PidNameApprovalAllowedDecisionMakers

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Approval-Allowed-Decision-Makers

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMSExchangeOrganizationDecisionMakers

2.373 PidNameApprovalRequestor

Canonical name: PidNameApprovalRequestor

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Approval-Requestor

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMSExchangeOrganizationApprovalRequestor

2.374 PidNameAttachmentMacContentType

Canonical name: PidNameAttachmentMacContentType

Property set: PSETID_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

Property name: AttachmentMacContentType

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.375 PidNameAttachmentMacInfo

Canonical name: PidNameAttachmentMacInfo

Property set: PSETID_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

Property name: AttachmentMacInfo

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.376 PidNameAudioNotes

Canonical name: PidNameAudioNotes

Description: Contains textual annotations to a voice message after it has been delivered to the user's mailbox.

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: UMAudioNotes

Data type: PtypString, 0x001F

Area: UM

References: [\[MS-OXOUM\]](#)

Alternate names: UMAudioNotes

2.377 PidNameAuthor

Canonical name: PidNameAuthor

Description: Specifies the author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Author

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Authorurn:schemas-microsoft-com:office:office#Author

2.378 PidNameAuthenticatedAs

Canonical name: PidNameAuthenticatedAs

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthAs

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthAs

2.379 PidNameAuthenticatedDomain

Canonical name: PidNameAuthenticatedDomain

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthDomain

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthDomain

2.380 PidNameAuthenticatedMechanism

Canonical name: PidNameAuthenticatedMechanism

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthMechanism

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthMechanism

2.381 PidNameAuthenticatedSource

Canonical name: PidNameAuthenticatedSource

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-AuthSource

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchOrganizationAuthSource

2.382 PidNameAutomaticSpeechRecognitionData

Canonical name: PidNameAutomaticSpeechRecognitionData

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: AsrData

Data type: PtypBinary, 0x0102

Area: UM

References: [\[MS-OXOUM\]](#)

Alternate names:

2.383 PidNameBcc

Canonical name: PidNameBcc

Description: Specifies the blind carbon copy addressees of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Bcc

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:bcc

2.384 PidNameByteCount

Canonical name: PidNameByteCount

Description: Specifies the size, in bytes, of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ByteCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Bytesurn:schemas-microsoft-com:office:office#Bytes

2.385 PidNameCalendarAttendeeRole

Canonical name: PidNameCalendarAttendeeRole

Description: Specifies the role of the attendee.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:attendeerole

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:calendar:attendeerole

2.386 PidNameCalendarBusystatus

Canonical name: PidNameCalendarBusystatus

Description: Specifies whether the attendee is busy at the time of an appointment on their calendar. .

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:busystatus

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:busystatus

2.387 PidNameCalendarContact

Canonical name: PidNameCalendarContact

Description: Identifies the name of a contact who is an attendee of a meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contact

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:contact

2.388 PidNameCalendarContactUrl

Canonical name: PidNameCalendarContactUrl

Description: Identifies the URL where you can access contact information in HTML format..

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contacturl

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:contacturl

2.389 PidNameCalendarCreated

Canonical name: PidNameCalendarCreated

Description: Identifies the date and time that the organizer created the appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:created

Data type: PtypTime, 0x0040

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:created

2.390 PidNameCalendarDescriptionUrl

Canonical name: PidNameCalendarDescriptionUrl

Description: Specifies the URL of a resource that contains a description of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:descriptionurl

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:descriptionurl

2.391 PidNameCalendarDuration

Canonical name: PidNameCalendarDuration

Description: Identifies the duration, in seconds, of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:duration

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:duration

2.392 PidNameCalendarExceptionDate

Canonical name: PidNameCalendarExceptionDate

Description: Identifies a list of dates that are exceptions to a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exdate

Data type: PtypMultipleTime, 0x1040

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:exdate

2.393 PidNameCalendarExceptionRule

Canonical name: PidNameCalendarExceptionRule

Description: Specifies an exception rule for a recurring appointment. .

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exrule

Data type: PtypMultipleString, 0x101F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:exrule

2.394 PidNameCalendarGeoLatitude

Canonical name: PidNameCalendarGeoLatitude

Description: Specifies the geographical latitude of the location of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolatitude

Data type: PtypFloating64, 0x0005

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:geolatitude

2.395 PidNameCalendarGeoLongitude

Canonical name: PidNameCalendarGeoLongitude

Description: Specifies the geographical longitude of the location of an appointment. .

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolongitude

Data type: PtypFloating64, 0x0005

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:geolongitude

2.396 PidNameCalendarInstanceType

Canonical name: PidNameCalendarInstanceType

Description: Specifies the type of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:instancetype

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:instancetype

2.397 PidNameCalendarIsOrganizer

Canonical name: PidNameCalendarIsOrganizer

Description: Specifies whether an attendee is the organizer of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:isorganizer

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:calendar:isorganizer

2.398 PidNameCalendarLastModified

Canonical name: PidNameCalendarLastModified

Description: Specifies the date and time when an appointment was last modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:lastmodified

Data type: PtypTime, 0x0040

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:lastmodified

2.399 PidNameCalendarLocationUrl

Canonical name: PidNameCalendarLocationUrl

Description: Specifies a URL where you can access location information in HTML format.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:locationurl

2.400 PidNameCalendarMeetingStatus

Canonical name: PidNameCalendarMeetingStatus

Description: Specifies the status of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:meetingstatus

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:meetingstatus

2.401 PidNameCalendarMethod

Canonical name: PidNameCalendarMethod

Description: Specifies the iCalendar method that is associated with an appointment object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:method

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:method

2.402 PidNameCalendarProductId

Canonical name: PidNameCalendarProductId

Description: Identifies the product that created the iCalendar-formatted stream.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:prodid

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:calendar:prodid

2.403 PidNameCalendarRecurrenceIdRange

Canonical name: PidNameCalendarRecurrenceIdRange

Description: Specifies which instances of a recurring appointment are being referred to.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:recurrenceidrange

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:recurrenceidrange

2.404 PidNameCalendarReminderOffset

Canonical name: PidNameCalendarReminderOffset

Description: Identifies the number of seconds before an appointment starts that a reminder is to be displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:reminderoffset

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:reminderoffset

2.405 PidNameCalendarResources

Canonical name: PidNameCalendarResources

Description: Identifies a list of resources, such as rooms and video equipment, which are available for an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:resources

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDVSEC\]](#)

Alternate names: urn:schemas:calendar:resources

2.406 PidNameCalendarRsvp

Canonical name: PidNameCalendarRsvp

Description: Specifies whether the organizer of an appointment or meeting requested a response..

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rsvp

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:calendar:rsvp

2.407 PidNameCalendarSequence

Canonical name: PidNameCalendarSequence

Description: Specifies the sequence number of a version of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:sequence

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:sequence

2.408 PidNameCalendarTimeZone

Canonical name: PidNameCalendarTimeZone

Description: Specifies the time zone of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezone

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:timezone

2.409 PidNameCalendarTimeZoneId

Canonical name: PidNameCalendarTimeZoneId

Description: Specifies the timezone identifier of an appointment or meeting..

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezoneid

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:timezoneid

2.410 PidNameCalendarTransparent

Canonical name: PidNameCalendarTransparent

Description: Specifies whether an appointment or meeting is visible to busy time searches.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:transparent

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:transparent

2.411 PidNameCalendarUid

Canonical name: PidNameCalendarUid

Description: Specifies the unique identifier of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:uid

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:uid

2.412 PidNameCalendarVersion

Canonical name: PidNameCalendarVersion

Description: Identifies the version of the iCalendar specification that is required to correctly interpret an iCalendar object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:version

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:calendar:version

2.413 PidNameCategory

Canonical name: PidNameCategory

Description: Specifies the category of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Category

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Category

2.414 PidNameCc

Canonical name: PidNameCc

Description: Specifies the carbon copy addressees of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Cc

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:cc

2.415 PidNameCharacterCount

Canonical name: PidNameCharacterCount

Description: Specifies the character count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: CharCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Characters

2.416 PidNameComments

Canonical name: PidNameComments

Description: Specifies the comments of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Comments

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Comments

2.417 PidNameCompany

Canonical name: PidNameCompany

Description: Specifies the company for which the file was created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Company

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Company

2.418 PidNameContactsAlternateRecipient

Canonical name: PidNameContactsAlternateRecipient

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:alternaterecipient

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#)

Alternate names: urn:schemas:contacts:alternaterecipient

2.419 PidNameContactsCountry

Canonical name: PidNameContactsCountry

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:c

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:c

2.420 PidNameContactsEmail1

Canonical name: PidNameContactsEmail1

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email1

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email1

2.421 PidNameContactsEmail2

Canonical name: PidNameContactsEmail2

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email2

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email2

2.422 PidNameContactsEmail3

Canonical name: PidNameContactsEmail3

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email3

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email3

2.423 PidNameContactsFileAs

Canonical name: PidNameContactsFileAs

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:fileas

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#)

Alternate names: urn:schemas:contacts:fileas

2.424 PidNameContactsFileasId

Canonical name: PidNameContactsFileasId

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:fileasid

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:fileasid

2.425 PidNameContactsHomeLatitude

Canonical name: PidNameContactsHomeLatitude

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:homelatitude

Data type: PtypFloating64, 0x0005

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:homelatitude

2.426 PidNameContactsHomeLongitude

Canonical name: PidNameContactsHomeLongitude

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:homelongitude

Data type: PtypFloating64, 0x0005

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:homelongitude

2.427 PidNameContactsHomeTimeZone

Canonical name: PidNameContactsHomeTimeZone

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:hometimezone

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:hometimezone

2.428 PidNameContactsMapUrl

Canonical name: PidNameContactsMapUrl

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:mapurl

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:mapurl

2.429 PidNameContactsOtherCountryCode

Canonical name: PidNameContactsOtherCountryCode

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:othercountrycode

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:othercountrycode

2.430 PidNameContactsOtherPager

Canonical name: PidNameContactsOtherPager

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:otherpager

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:otherpager

2.431 PidNameContactsOtherTimeZone

Canonical name: PidNameContactsOtherTimeZone

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:othertimezone

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:othertimezone

2.432 PidNameContactsProxyAddresses

Canonical name: PidNameContactsProxyAddresses

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:proxyaddresses

Data type: PtypMultipleString, 0x101F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:proxyaddresses

2.433 PidNameContactsSecretaryUrl

Canonical name: PidNameContactsSecretaryUrl

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:secretaryurl

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:secretaryurl

2.434 PidNameContactsSourceUrl

Canonical name: PidNameContactsSourceUrl

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:sourceurl

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:sourceurl

2.435 PidNameContentBase

Canonical name: PidNameContentBase

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Base

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-OXCMAIL\]](#)

Alternate names: BodyContentBase

2.436 PidNameContentClass

Canonical name: PidNameContentClass

Description: Contains the string value "Sharing".

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Class

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDSTRUCTDOC\]](#)

Alternate names: DAV:contentclassDAV:contentclass, urn:schemas:mailheader:content-class

2.437 PidNameContentDisposition

Canonical name: PidNameContentDisposition

Description: Specifies the intended disposition of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Disposition

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-disposition

2.438 PidNameContentID

Canonical name: PidNameContentID

Description: Specifies a unique identifier for the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-ID

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-id

2.439 PidNameContentLanguage

Canonical name: PidNameContentLanguage

Description: Specifies the language identifier for the text content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Language

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-language

2.440 PidNameContentLocation

Canonical name: PidNameContentLocation

Description: Specifies the Uniform Resource Identifier (URI) that corresponds to the content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Location

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-location

2.441 PidNameContentTransferEncoding

Canonical name: PidNameContentTransferEncoding

Description: Specifies the encoding mechanism used to encode the content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Transfer-Encoding

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-OXCICAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:content-transfer-encoding

2.442 PidNameContentType

Canonical name: PidNameContentType

Description: Specifies the type of the body part's content.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Type

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:content-type

2.443 PidNameControl

Canonical name: PidNameControl

Description: Specifies a Usenet control command.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Control

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:control

2.444 PidNameCreateDateTimeReadOnly

Canonical name: PidNameCreateDateTimeReadOnly

Description: Specifies the time that the file was first created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: CreateDtmRo

Data type: PtypTime, 0x0040

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Created

2.445 PidNameCrossReference

Canonical name: PidNameCrossReference

Description: Contains the name of the host (with domains omitted) and a white-space-separated list of colon-separated pairs of newsgroup names and message numbers.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Xref

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-OXCMAIL\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:xref

2.446 PidNameDavGetContentType

Canonical name: PidNameDavGetContentType

Description: Specifies the type of the message's content.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:getcontenttype

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDMAIL\]](#)

Alternate names:

2.447 PidNameDavId

Canonical name: PidNameDavId

Description: Specifies a unique ID for the calendar item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:id

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:id

2.448 PidNameDavIsCollection

Canonical name: PidNameDavIsCollection

Description: Indicates whether a Calendar object is a collection.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:iscollection

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:iscollection

2.449 PidNameDavIsStructuredDocument

Canonical name: PidNameDavIsStructuredDocument

Description: Indicates whether a Calendar object is a structured document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:isstructureddocument

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:isstructureddocument

2.450 PidNameDavParentName

Canonical name: PidNameDavParentName

Description: Specifies the name of the folder that contains the Calendar object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:parentname

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:parentname

2.451 PidNameDavResourceType

Canonical name: PidNameDavResourceType

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:resourcetype

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#), [\[MS-XWDSTRUCTDOC\]](#)

Alternate names: DAV:resourcetype

2.452 PidNameDavSearchRequest

Canonical name: PidNameDavSearchRequest

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:searchrequest

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#)

Alternate names: DAV:searchrequest

2.453 PidNameDavSearchType

Canonical name: PidNameDavSearchType

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:searchtype

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDSEARCH\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:searchtype

2.454 PidNameDavUid

Canonical name: PidNameDavUid

Description: Specifies the unique identifier for an item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:uid

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:uid

2.455 PidNameDisposition

Canonical name: PidNameDisposition

Description: Specifies the Mail Delivery Notification (MDN) status for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Disposition

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:disposition

2.456 PidNameDispositionNotificationTo

Canonical name: PidNameDispositionNotificationTo

Description: Specifies the destination to which disposition notifications should be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Disposition-Notification-To

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:disposition-notification-to

2.457 PidNameDistribution

Canonical name: PidNameDistribution

Description: Contains a comma-separated list, similar to the Newsgroups header field, intended to restrict the distribution of a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Distribution

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:distribution

2.458 PidNameDocumentParts

Canonical name: PidNameDocumentParts

Description: Specifies the title of each part of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DocParts

Data type: PtypMultipleString, 0x101F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#PartTitles

2.459 PidNameEditTime

Canonical name: PidNameEditTime

Description: Specifies the time that the file was last edited.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: EditTime

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#TotalTime

2.460 PidNameExchangeIntendedBusyStatus

Canonical name: PidNameExchangeIntendedBusyStatus

Description: Specifies the busy status of the user during an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/intendedbusystatus

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: http://schemas.microsoft.com/exchange/intendedbusystatus

2.461 PidNameExchangeJunkEmailMoveStamp

Canonical name: PidNameExchangeJunkEmailMoveStamp

Description: Indicates that the message MUST NOT be processed by a spam filter.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/junkemailmovestamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORSS\]](#)

Alternate names: http://schemas.microsoft.com/exchange/junkemailmovestamp

2.462 PidNameExchangeModifyExceptionStructure

Canonical name: PidNameExchangeModifyExceptionStructure

Description: Specifies a structure that modifies an exception to the recurrence.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/modifyexceptionstruct

Data type: PtypBinary, 0x0102

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: http://schemas.microsoft.com/exchange/modifyexceptionstruct

2.463 PidNameExchangeMsexchembdefaultmailfolder

Canonical name: PidNameExchangeMsexchembdefaultmailfolder

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/msexchembdefaultmailfolder

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDFOLD\]](#)

Alternate names: http://schemas.microsoft.com/exchange/msexchembdefaultmailfolder

2.464 PidNameExchangeMsexchembdefaultmailfoldertype

Canonical name: PidNameExchangeMsexchembdefaultmailfoldertype

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/msexchembdefaultmailfoldertype

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDFOLD\]](#)

Alternate names: http://schemas.microsoft.com/exchange/msexchembdefaultmailfoldertype

2.465 PidNameExchangeNoModifyExceptions

Canonical name: PidNameExchangeNoModifyExceptions

Description: Indicates whether exceptions to a recurring appointment can be modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/nomodifyexceptions

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: http://schemas.microsoft.com/exchange/nomodifyexceptions

2.466 PidNameExchangePatternEnd

Canonical name: PidNameExchangePatternEnd

Description: Identifies the maximum time when an instance of a recurring appointment ends.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/patternend

Data type: PtypTime, 0x0040

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/patternend>

2.467 PidNameExchangePatternStart

Canonical name: PidNameExchangePatternStart

Description: Identifies the absolute minimum time when an instance of a recurring appointment starts.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: <http://schemas.microsoft.com/exchange/patternstart>

Data type: PtypTime, 0x0040

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/patternstart>

2.468 PidNameExchangePublicFolderEmailAddress

Canonical name: PidNameExchangePublicFolderEmailAddress

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: <http://schemas.microsoft.com/exchange/publicfolderemailaddress>

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/publicfolderemailaddress>

2.469 PidNameExchangeReminderInterval

Canonical name: PidNameExchangeReminderInterval

Description: Identifies the time, in seconds, between reminders.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: <http://schemas.microsoft.com/exchange/reminderinterval>

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/reminderinterval>

2.470 PidNameExchDatabaseSchema

Canonical name: PidNameExchDatabaseSchema

Description: Specifies an array of URLs identifying other folders within the same store that contain schema definition items.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:baseschema

Data type: PtypMultipleString, 0x101F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:baseschema

2.471 PidNameExchDataExpectedContentClass

Canonical name: PidNameExchDataExpectedContentClass

Description: Specifies an array of names indicating the expected content classes of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:expected-content-class

Data type: PtypMultipleString, 0x101F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:expected-content-class

2.472 PidNameExchDataSchemaCollectionReference

Canonical name: PidNameExchDataSchemaCollectionReference

Description: Specifies an array of names indicating the expected content classes of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:schema-collection-ref

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:schema-collection-ref

2.473 PidNameExpires

Canonical name: PidNameExpires

Description: This property specifies the date on which the message expires.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Expires

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:expires

2.474 PidNameExpiryDate

Canonical name: PidNameExpiryDate

Description: This property specifies the expiry date of a message in a mail header.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Expiry-Date

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:expiry-date

2.475 PidNameFollowupTo

Canonical name: PidNameFollowupTo

Description: This property specifies the newsgroups to which follow-up messages are to be posted.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Followup-To

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:followup-to

2.476 PidNameFrom

Canonical name: PidNameFrom

Description: Specifies the SMTP e-mail alias of the organizer of an appointment or meeting.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: From

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDCAL\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:calendar:organizer

2.477 PidNameHeadingPairs

Canonical name: PidNameHeadingPairs

Description: Specifies which group of headings are indented in the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: HeadingPairs

Data type: PtypBinary, 0x0102

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#HeadingPairs

2.478 PidNameHiddenCount

Canonical name: PidNameHiddenCount

Description: Specifies the hidden value of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: HiddenCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#HiddenSlides

2.479 PidNameHttpmailCalendar

Canonical name: PidNameHttpmailCalendar

Description: Specifies the URL for the calendar folder for a particular user.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:calendar

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:httpmail:calendar

2.480 PidNameHttpmailCc

Canonical name: PidNameHttpmailCc

Description: Specifies the carbon copy (CC) recipients of the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:cc

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:cc

2.481 PidNameHttpmailContacts

Canonical name: PidNameHttpmailContacts

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:contacts

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDCNTCT\]](#)

Alternate names: urn:schemas:httpmail:contacts

2.482 PidNameHttpmailContentMediaType

Canonical name: PidNameHttpmailContentMediaType

Description: Specifies the content media type for the body part.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:content-media-type

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:content-media-type

2.483 PidNameHttpmailFrom

Canonical name: PidNameHttpmailFrom

Description: Specifies the person from whom the message was sent.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:from

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXCMAIL\]](#)

Alternate names: urn:schemas:httpmail:from

2.484 PidNameHttpmailFromEmail

Canonical name: PidNameHttpmailFromEmail

Description: Specifies the e-mail address from which the message was sent.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:fromemail

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:fromemail

2.485 PidNameHttpmailHtmlDescription

Canonical name: PidNameHttpmailHtmlDescription

Description: Specifies the HTML content of the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:htmldescription

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:httpmail:htmldescription

2.486 PidNameHttpmailOutbox

Canonical name: PidNameHttpmailOutbox

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:outbox

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:httpmail:outbox

2.487 PidNameHttpmailSendMessage

Canonical name: PidNameHttpmailSendMessage

Description: Specifies the mail submission URI to which outgoing mail is submitted.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:sendmsg

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:httpmail:sendmsg

2.488 PidNameHttpmailSubmitted

Canonical name: PidNameHttpmailSubmitted

Description: Specifies whether a message has been submitted to the Outbox.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:submitted

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:submitted

2.489 PidNameHttpmailTo

Canonical name: PidNameHttpmailTo

Description: Specifies the principle (To) message addressees.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:to

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:to

2.490 PidNameICalendarRecurrenceDate

Canonical name: PidNameICalendarRecurrenceDate

Description: Identifies an array of instances of a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rdate

Data type: PtypMultipleTime, 0x1040

Area: Common

References: [\[MS-XWDEXT\]](#), [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:calendar:rdate

2.491 PidNameICalendarRecurrenceRule

Canonical name: PidNameICalendarRecurrenceRule

Description: Specifies the rule for the pattern that defines a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rrule

Data type: PtypMultipleString, 0x101F

Area: Common

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:rrule

2.492 PidNameImportance

Canonical name: PidNameImportance

Description: Indicates the level of importance for a message as either low, normal, or high.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Importance

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:importance

2.493 PidNameInReplyTo

Canonical name: PidNameInReplyTo

Description: Specifies the message to which another message is a reply.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: In-Reply-To

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:in-reply-to

2.494 PidNameInstantMessagingAddress2

Canonical name: PidNameInstantMessagingAddress2

Property set: PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}

Property name: IMAddress2

Data type: PtypString, 0x001F

Area: Sync

References: [\[MS-OXVCARD\]](#)

Alternate names: IMAddress2

2.495 PidNameInstantMessagingAddress3

Canonical name: PidNameInstantMessagingAddress3

Property set: PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}

Property name: IMAddress3

Data type: PtypString, 0x001F

Area: Sync

References: [\[MS-OXVCARD\]](#)

Alternate names: IMAddress3

2.496 PidNameInternetComment

Canonical name: PidNameInternetComment

Description: Contains a comment about the purpose or content of the folder.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Comment

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:comment

2.497 PidNameInternetKeywords

Canonical name: PidNameInternetKeywords

Description: Specifies the key words for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Keywords

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:keywords

2.498 PidNameInternetSubject

Canonical name: PidNameInternetSubject

Description: Specifies the subject of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:subject

2.499 PidNameKeywords

Canonical name: PidNameKeywords

Description: Contains keywords or categories for the Message object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Keywords

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Keywords,
http://schemas.microsoft.com/exchange/keywords-utf8

2.500 PidNameLastAuthor

Canonical name: PidNameLastAuthor

Description: Specifies the most recent author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastAuthor

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastAuthor

2.501 PidNameLastPrinted

Canonical name: PidNameLastPrinted

Description: Specifies the time that the file was last printed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastPrinted

Data type: PtypTime, 0x0040

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastPrinted

2.502 PidNameLastSaveDateTime

Canonical name: PidNameLastSaveDateTime

Description: Specifies the time that the file was last saved.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastSaveDtm

Data type: PtypTime, 0x0040

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastSaved

2.503 PidNameLineCount

Canonical name: PidNameLineCount

Description: Specifies the number of lines in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LineCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Lines

2.504 PidNameLines

Canonical name: PidNameLines

Description: Specifies the number of lines in the body of a newsgroup message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Lines

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:lines

2.505 PidNameLinksDirty

Canonical name: PidNameLinksDirty

Description: Indicates whether the links in the document are up-to-date.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LinksDirty

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LinksUpToDate

2.506 PidNameLocationUrl

Canonical name: PidNameLocationUrl

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Calendar

References: [\[MS-OXCMAIL\]](#)

Alternate names: urn:schemas:calendar:locationurl, LocationUrl

2.507 PidNameMailSubmissionUri

Canonical name: PidNameMailSubmissionUri

Description: Specifies the URI that is used for mail submission.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: MAIL:submissionuri

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-XWDMAIL\]](#)

Alternate names: MAIL:submissionuri

2.508 PidNameManager

Canonical name: PidNameManager

Description: Specifies the manager of the file attached to the document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Manager

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Manager

2.509 PidNameMessageId

Canonical name: PidNameMessageId

Description: Specifies a unique identifier for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Message-ID

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:message-id

2.510 PidNameMimeVersion

Canonical name: PidNameMimeVersion

Description: Specifies the version of Multipurpose Internet Mail Extensions (MIME) that is used to format the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Mime-Version

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:mime-version

2.511 PidNameMultimediaClipCount

Canonical name: PidNameMultimediaClipCount

Description: Specifies the number of multimedia clips in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: MMClipCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#MultimediaClips

2.512 PidNameNewsgroups

Canonical name: PidNameNewsgroups

Description: Specifies the newsgroup addressees for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Newsgroups

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:newsgroups

2.513 PidNameNntpPostingHost

Canonical name: PidNameNntpPostingHost

Description: Specifies the initial host to which the USENET feed was posted.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: NNTP-Posting-Host

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:nntp-posting-host

2.514 PidNameNoteCount

Canonical name: PidNameNoteCount

Description: Specifies the number of notes in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: NoteCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Notes

2.515 PidNameOMSAccountGuid

Canonical name: PidNameOMSAccountGuid

Description: Contains the GUID of the SMS account used to deliver the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSAccountGuid

Data type: PtypString, 0x001F

Area: SMS

References: [\[MS-OXOSMMS\]](#)

Alternate names:

2.516 PidNameOMSMobileModel

Canonical name: PidNameOMSMobileModel

Description: Indicates the model of the mobile device used to send the SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSMobileModel

Data type: PtypString, 0x001F

Area: SMS

References: [\[MS-OXOSMMS\]](#)

Alternate names:

2.517 PidNameOMSScheduleTime

Canonical name: PidNameOMSScheduleTime

Description: Contains the time at which the client requested that the service provider send the SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSScheduleTime

Data type: PtypTime, 0x0040

Area: SMS

References: [\[MS-OXOSMMS\]](#)

Alternate names:

2.518 PidNameOMSServiceType

Canonical name: PidNameOMSServiceType

Description: Contains the type of service used to send an SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSServiceType

Data type: PtypInteger32, 0x0003

Area: SMS

References: [\[MS-OXOSMMS\]](#)

Alternate names:

2.519 PidNameOMSSourceType

Canonical name: PidNameOMSSourceType

Description: Contains the source of an SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSSourceType

Data type: PtypInteger32, 0x0003

Area: SMS

References: [\[MS-OXOSMMS\]](#)

Alternate names:

2.520 PidNameOrganization

Canonical name: PidNameOrganization

Description: Specifies the organization to which the sender belongs.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Organization

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:organization

2.521 PidNameOriginalRecipient

Canonical name: PidNameOriginalRecipient

Description: Specifies the e-mail address of an original recipient of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Original-Recipient

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:original-recipient

2.522 PidNameOriginalSpamConfidenceLevel

Canonical name: PidNameOriginalSpamConfidenceLevel

Property set: PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}

Property name: OriginalScl

Data type: PtypInteger32, 0x0003

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: OriginalScl

2.523 PidNameOutlookProtectionRuleOverridden

Canonical name: PidNameOutlookProtectionRuleOverridden

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Outlook-Protection-Rule-Overridden

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMSEExchangeOutlookProtectionRuleOverridden

2.524 PidNameOutlookProtectionRuleTimestamp

Canonical name: PidNameOutlookProtectionRuleTimestamp

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-Organization-Outlook-Protection-Rule-Config-Timestamp

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMSEExchangeOutlookProtectionRuleConfigTimestamp

2.525 PidNameOutlookProtectionRuleVersion

Canonical name: PidNameOutlookProtectionRuleVersion

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-Outlook-Protection-Rule-Addin-Version

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMSEExchangeOutlookProtectionRuleVersion

2.526 PidNamePageCount

Canonical name: PidNamePageCount

Description: Specifies the page count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PageCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Pages

2.527 PidNameParagraphCount

Canonical name: PidNameParagraphCount

Description: Specifies the number of paragraphs in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ParCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Paragraphs

2.528 PidNamePath

Canonical name: PidNamePath

Description: Specifies the list of Network News Transfer Protocol (NNTP) hosts through which this message was relayed before arriving at the current host.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Path

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:path

2.529 PidNamePhishingStamp

Canonical name: PidNamePhishingStamp

Description: Indicates whether a message is likely to be phishing.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/outlook/phishingstamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

References: [\[MS-OXPHISH\]](#)

Alternate names:

2.530 PidNamePostingVersion

Canonical name: PidNamePostingVersion

Description: Identifies the software that is used to post the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Posting-Version

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:posting-version

2.531 PidNamePresentationFormat

Canonical name: PidNamePresentationFormat

Description: Specifies the presentation format of the file attached to the document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PresFormat

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#PresentationFormat

2.532 PidNamePriority

Canonical name: PidNamePriority

Description: Specifies the priority of a message or appointment.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Priority

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:priority

2.533 PidNameQuarantineOriginalSender

Canonical name: PidNameQuarantineOriginalSender

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: quarantine-original-sender

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.534 PidNameReceived

Canonical name: PidNameReceived

Description: Specifies the SMTP host received headers for a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Received

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:received

2.535 PidNameReferences

Canonical name: PidNameReferences

Description: Specifies the USENET header used to correlate replies with their original messages.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: References

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:references

2.536 PidNameRelayVersion

Canonical name: PidNameRelayVersion

Description: Specifies the version of the program responsible for transmitting an item over the immediate link.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Relay-Version

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:relay-version

2.537 PidNameReplyBy

Canonical name: PidNameReplyBy

Description: Indicates when there should be a reply to a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Reply-By

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:reply-by

2.538 PidNameReplyTo

Canonical name: PidNameReplyTo

Description: Specifies the address to which replies are to be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Reply-To

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:reply-to

2.539 PidNameReturnPath

Canonical name: PidNameReturnPath

Description: Specifies the address of the message originator.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Return-Path

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:return-path

2.540 PidNameReturnReceiptTo

Canonical name: PidNameReturnReceiptTo

Description: Specifies the address to which return receipts are to be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Return-Receipt-To

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:return-receipt-to

2.541 PidNameRevisionNumber

Canonical name: PidNameRevisionNumber

Description: Specifies the revision number of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: RevNumber

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Revision

2.542 PidNameRightsManagementLicense

Canonical name: PidNameRightsManagementLicense

Description: Specifies the value used to cache the Use License for the rights-managed e-mail message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DRMLicense

Data type: PtypMultipleBinary, 0x1102

Area: Secure Messaging Properties

References: [\[MS-OXORMMS\]](#)

Alternate names:

2.543 PidNameRightsProtectMessage

Canonical name: PidNameRightsProtectMessage

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-MS-Exchange-Organization-RightsProtectMessage

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeOrganizationRightsProtectMessage

2.544 PidNameScale

Canonical name: PidNameScale

Description: Indicates whether the image is to be scaled or cropped.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Scale

Data type: PtypBoolean, 0x000B

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#ScaleCrop

2.545 PidNameSecurity

Canonical name: PidNameSecurity

Description: Specifies the security level of the file attached to the document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Security

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Security

2.546 PidNameSender

Canonical name: PidNameSender

Description: Specifies the sender of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Sender

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:sender

2.547 PidNameSensitivity

Canonical name: PidNameSensitivity

Description: Specifies the sensitivity of the message or appointment.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Sensitivity

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:sensitivity

2.548 PidNameSlideCount

Canonical name: PidNameSlideCount

Description: Specifies the number of slides in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: SlideCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Slides

2.549 PidNameSubject

Canonical name: PidNameSubject

Description: Specifies the subject of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#), [\[MS-OXOCAL\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Subject

2.550 PidNameSummary

Canonical name: PidNameSummary

Description: Contains a summary of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Summary

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:summary

2.551 PidNameTemplate

Canonical name: PidNameTemplate

Description: Specifies the template of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Template

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Template

2.552 PidNameThreadIndex

Canonical name: PidNameThreadIndex

Description: Identifies a particular conversation thread.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Thread-Index

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:thread-index

2.553 PidNameThreadTopic

Canonical name: PidNameThreadTopic

Description: Specifies the topic of a discussion thread.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Thread-Topic

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:thread-topic

2.554 PidNameThumbnail

Canonical name: PidNameThumbnail

Description: Specifies the data representing the thumbnail image of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Thumbnail

Data type: PtypBinary, 0x0102

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#ThumbNail

2.555 PidNameTitle

Canonical name: PidNameTitle

Description: Specifies the title of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Title

Data type: PtypString, 0x001F

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Title

2.556 PidNameTo

Canonical name: PidNameTo

Description: Specifies the principal message addressees.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: To

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:to

2.557 PidNameWordCount

Canonical name: PidNameWordCount

Description: Specifies the word count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: WordCount

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Words

2.558 PidNameXCallId

Canonical name: PidNameXCallId

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallID

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.559 PidNameXFaxNumberOfPages

Canonical name: PidNameXFaxNumberOfPages

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-FaxNumberOfPages

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.560 PidNameXMailer

Canonical name: PidNameXMailer

Description: Specifies the name of the software used to send the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Mailer

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:x-mailer

2.561 PidNameXMessageCompleted

Canonical name: PidNameXMessageCompleted

Description: Contains the header for message flag completion.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Message-Completed

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:x-message-completed

2.562 PidNameXMessageFlag

Canonical name: PidNameXMessageFlag

Description: Specifies message flags that indicate special characteristics of a particular message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Message-Flag

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:x-message-flag

2.563 PidNameXRequireProtectedPlayOnPhone

Canonical name: PidNameXRequireProtectedPlayOnPhone

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-RequireProtectedPlayOnPhone

Data type: PtypBoolean, 0x000B

Area: UM

References: [\[MS-OXOUM\]](#)

Alternate names:

2.564 PidNameXSenderTelephoneNumber

Canonical name: PidNameXSenderTelephoneNumber

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallingTelephoneNumber

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.565 PidNameXSharingBrowseUrl

Canonical name: PidNameXSharingBrowseUrl

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Browse-Url

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.566 PidNameXSharingCapabilities

Canonical name: PidNameXSharingCapabilities

Description: Contains a string representation of the value of the PidLidSharingCapabilities property.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Capabilities

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.567 PidNameXSharingConfigUrl

Canonical name: PidNameXSharingConfigUrl

Description: Contains the same value as the PidLidSharingConfigurationUrl property.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Config-Url

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.568 PidNameXSharingExendedCaps

Canonical name: PidNameXSharingExendedCaps

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Exended-Caps

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.569 PidNameXSharingFlavor

Canonical name: PidNameXSharingFlavor

Description: Contains a hexadecimal string representation of the value of the PidLidSharingFlavor property.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Flavor

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.570 PidNameXSharingInstanceGuid

Canonical name: PidNameXSharingInstanceGuid

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Instance-Guid

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.571 PidNameXSharingLocalType

Canonical name: PidNameXSharingLocalType

Description: Contains the same value as PidLidSharingLocalType.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Local-Type

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.572 PidNameXSharingProviderGuid

Canonical name: PidNameXSharingProviderGuid

Description: Contains the hexadecimal string representation of the value of PidLidSharingProviderGuid.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Guid

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.573 PidNameXSharingProviderName

Canonical name: PidNameXSharingProviderName

Description: Contains the same value as PidLidSharingProviderName.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Name

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.574 PidNameXSharingProviderUrl

Canonical name: PidNameXSharingProviderUrl

Description: Contains the same value as PidLidSharingProviderUrl.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Url

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.575 PidNameXSharingRemoteName

Canonical name: PidNameXSharingRemoteName

Description: Contains the same value as PidLidSharingRemoteName.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Name

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.576 PidNameXSharingRemotePath

Canonical name: PidNameXSharingRemotePath

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Path

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.577 PidNameXSharingRemoteStoreUid

Canonical name: PidNameXSharingRemoteStoreUid

Description: Contains the same value as PidLidSharingRemoteStoreUid.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Store-Uid

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.578 PidNameXSharingRemoteType

Canonical name: PidNameXSharingRemoteType

Description: Contains the same value as PidLidSharingRemoteType.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Type

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.579 PidNameXSharingRemoteUid

Canonical name: PidNameXSharingRemoteUid

Description: Contains the same value as PidLidSharingRemoteUid.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Uid

Data type: PtypString, 0x001F

Area: Sharing

References: [\[MS-OXSHARE\]](#)

Alternate names:

2.580 PidNameXUnifiedMessagingPartnerAssignedId

Canonical name: PidNameXUnifiedMessagingPartnerAssignedId

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerAssignedID

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerAssignedID

2.581 PidNameXUnifiedMessagingPartnerContent

Canonical name: PidNameXUnifiedMessagingPartnerContent

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerContent

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerContent

2.582 PidNameXUnifiedMessagingPartnerContext

Canonical name: PidNameXUnifiedMessagingPartnerContext

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerContext

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerContext

2.583 PidNameXUnifiedMessagingPartnerStatus

Canonical name: PidNameXUnifiedMessagingPartnerStatus

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerStatus

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerStatus

2.584 PidNameXUnsent

Canonical name: PidNameXUnsent

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Unsent

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-unsent

2.585 PidNameXVoiceMessageAttachmentOrder

Canonical name: PidNameXVoiceMessageAttachmentOrder

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-AttachmentOrder

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.586 PidNameXVoiceMessageDuration

Canonical name: PidNameXVoiceMessageDuration

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageDuration

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.587 PidNameXVoiceMessageSenderName

Canonical name: PidNameXVoiceMessageSenderName

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageSenderName

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names:

2.588 PidTag7BitDisplayName

Canonical name: PidTag7BitDisplayName

Description: Contains a displayable form of the Address Book object that can be rendered in the client user's own code page.

Property ID: 0x39FF

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_7BIT_DISPLAY_NAME, PR_7BIT_DISPLAY_NAME_A, PR_7BIT_DISPLAY_NAME_W

2.589 PidTagAccess

Canonical name: PidTagAccess

Description: Indicates the operations available to the client for the object.

Property ID: 0x0FF4

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOJRN\]](#)

Alternate names: PR_ACCESS, ptagAccess

2.590 PidTagAccessLevel

Canonical name: PidTagAccessLevel

Description: Indicates the client's access level to the object.

Property ID: 0x0FF7

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#)

Alternate names: PR_ACCESS_LEVEL, ptagAccessLevel

2.591 PidTagAccount

Canonical name: PidTagAccount

Description: Contains the Address Book object's alias, which is an alternative name by which the object can be identified.

Property ID: 0x3A00

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXCFXICS\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXCMSG\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ACCOUNT, PR_ACCOUNT_A, PR_ACCOUNT_W,
urn:schemas:contacts:account

2.592 PidTagAdditionalRenEntryIds

Canonical name: PidTagAdditionalRenEntryIds

Description: Contains the indexed entry IDs for several special folders related to conflicts, sync issues, local failures, server failures, junk E-mail and spam.

Property ID: 0x36D8

Data type: PtypMultipleBinary, 0x1102

Area: Outlook Application

References: [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPHISH\]](#)

Alternate names: PR_ADDITIONAL_REN_ENTRYIDS, ptagAdditionalRenEntryIds

2.593 PidTagAdditionalRenEntryIdsEx

Canonical name: PidTagAdditionalRenEntryIdsEx

Description: Contains an array of blocks that contain the entry IDs for folders related to RSS Feeds folders, Tracked Mail Processing folder, To-Do Search folder, and Conversation Action Settings folder.

Property ID: 0x36D9

Data type: PtypBinary, 0x0102

Area: Outlook Application

References: [\[MS-OXOSFLD\]](#)

Alternate names: PR_ADDITIONAL_REN_ENTRYIDS_EX, ptagAdditionalRenEntryIdsEx

2.594 PidTagAddressBookAuthorizedSenders

Canonical name: PidTagAddressBookAuthorizedSenders

Description: Indicates whether delivery restrictions exist for a recipient.

Property ID: 0x8CD8

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_AUTH_ORIG

2.595 PidTagAddressBookContainerId

Canonical name: PidTagAddressBookContainerId

Description: Contains the ID of a container on an NSPI server.

Property ID: 0xFFFFD

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_CONTAINERID

2.596 PidTagAddressBookDeliveryContentLength

Canonical name: PidTagAddressBookDeliveryContentLength

Property ID: 0x806A

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_DELIV_CONT_LENGTH

2.597 PidTagAddressBookDisplayNamePrintable

Canonical name: PidTagAddressBookDisplayNamePrintable

Property ID: 0x39FF

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_EMS_AB_DISPLAY_NAME_PRINTABLE,
PR_EMS_AB_DISPLAY_NAME_PRINTABLE_A, PR_EMS_AB_DISPLAY_NAME_PRINTABLE_W

2.598 PidTagAddressBookDisplayTypeExtended

Canonical name: PidTagAddressBookDisplayTypeExtended

Description: Contains a value that indicates how to display an Address Book object in a table or as a recipient on a message.

Property ID: 0x8C93

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_DISPLAY_TYPE_EX

2.599 PidTagAddressBookDistributionListExternalMemberCount

Canonical name: PidTagAddressBookDistributionListExternalMemberCount

Description: Contains the number of external recipients in the distribution list.

Property ID: 0x8CE3

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_DL_EXTERNAL_MEMBER_COUNT

2.600 PidTagAddressBookDistributionListMemberCount

Canonical name: PidTagAddressBookDistributionListMemberCount

Description: Contains the total number of recipients in the distribution list.

Property ID: 0x8CE2

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_DL_TOTAL_MEMBER_COUNT

2.601 PidTagAddressBookDistributionListMemberSubmitAccepted

Canonical name: PidTagAddressBookDistributionListMemberSubmitAccepted

Description: Indicates that delivery restrictions exist for a recipient.

Property ID: 0x8073

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_DL_MEM_SUBMIT_PERMS

2.602 PidTagAddressBookDistributionListMemberSubmitRejected

Canonical name: PidTagAddressBookDistributionListMemberSubmitRejected

Description: Indicates that delivery restrictions exist for a recipient.

Property ID: 0x8CDA

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_DL_MEM_REJECT_PERMS

2.603 PidTagAddressBookEntryId

Canonical name: PidTagAddressBookEntryId

Description: Contains the name-service EntryID of a directory object that refers to a public folder.

Property ID: 0x663B

Data type: PtypBinary, 0x0102

Area: Address Book

References: [\[MS-OXCFOLD\]](#)

Alternate names: PR_ADDRESS_BOOK_ENTRYID, ptagAddressBookEntryId

2.604 PidTagAddressBookExtensionAttribute1

Canonical name: PidTagAddressBookExtensionAttribute1

Description: Contains information to be added to display templates.

Property ID: 0x802D

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_1,
PR_EMS_AB_EXTENSION_ATTRIBUTE_1_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_1_W

2.605 PidTagAddressBookExtensionAttribute15

Canonical name: PidTagAddressBookExtensionAttribute15

Description: Contains information to be added to display templates.

Property ID: 0x8C61

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_15,
PR_EMS_AB_EXTENSION_ATTRIBUTE_15_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_15_W

2.606 PidTagAddressBookFolderPathname

Canonical name: PidTagAddressBookFolderPathname

Description: This property has been deprecated and is to be ignored.

Property ID: 0x8004

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_FOLDER_PATHNAME, PR_EMS_AB_FOLDER_PATHNAME_A,
PR_EMS_AB_FOLDER_PATHNAME_W

2.607 PidTagAddressBookHierarchicalChildDepartments

Canonical name: PidTagAddressBookHierarchicalChildDepartments

Description: Contains the child departments in a hierarchy of departments.

Property ID: 0x8C9A

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_HAB_CHILD_DEPARTMENTS

2.608 PidTagAddressBookHierarchicalDepartmentMembers

Canonical name: PidTagAddressBookHierarchicalDepartmentMembers

Description: Contains all the mail users that belong to this department.

Property ID: 0x8C97

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_HAB_DEPARTMENT_MEMBERS

2.609 PidTagAddressBookHierarchicalIsHierarchicalGroup

Canonical name: PidTagAddressBookHierarchicalIsHierarchicalGroup

Description: Indicates whether the distribution list represents a departmental group.

Property ID: 0x8CDD

Data type: PtypBoolean, 0x000B

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_HAB_IS_HIERARCHICAL_GROUP,
PR_EMS_AB_IS_ORGANIZATIONAL

2.610 PidTagAddressBookHierarchicalParentDepartment

Canonical name: PidTagAddressBookHierarchicalParentDepartment

Description: Contains all the departments to which this department is a child.

Property ID: 0x8C99

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_HAB_PARENT_DEPARTMENT

2.611 PidTagAddressBookHierarchicalRootDepartment

Canonical name: PidTagAddressBookHierarchicalRootDepartment

Description: Contains either the root Department object or the root departmental group in the department hierarchy for the organization.

Property ID: 0x8C98

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_HAB_ROOT_DEPARTMENT

2.612 PidTagAddressBookHierarchicalShowInDepartments

Canonical name: PidTagAddressBookHierarchicalShowInDepartments

Description: Lists all Department objects of which the mail user is a member.

Property ID: 0x8C94

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_HAB_SHOW_IN_DEPARTMENTS

2.613 PidTagAddressBookHomeMessageDatabase

Canonical name: PidTagAddressBookHomeMessageDatabase

Description: Contains the DN expressed in the x500-dn format specification.

Property ID: 0x8006

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXABREF\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_HOME_MDB, PR_EMS_AB_HOME_MDB_A, PR_EMS_AB_HOME_MDB_W

2.614 PidTagAddressBookIsMaster

Canonical name: PidTagAddressBookIsMaster

Description: Contains a boolean that is TRUE if it is possible to create Address Book objects in that container, and FALSE otherwise.

Property ID: 0xFFFFB

Data type: PtypBoolean, 0x000B

Area: Address Book

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_IS_MASTER

2.615 PidTagAddressBookIsMemberOfDistributionList

Canonical name: PidTagAddressBookIsMemberOfDistributionList

Description: List all the distribution lists for which this object is a member.

Property ID: 0x8008

Data type: PtypMultipleString, 0x101F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_IS_MEMBER_OF_DL, PR_EMS_AB_IS_MEMBER_OF_DL_A, PR_EMS_AB_IS_MEMBER_OF_DL_W

2.616 PidTagAddressBookManageDistributionList

Canonical name: PidTagAddressBookManageDistributionList

Description: Contains information for use in display templates for distribution lists.

Property ID: 0x6704

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

Alternate names: PR_EMS_AB_MANAGE_DL

2.617 PidTagAddressBookManager

Canonical name: PidTagAddressBookManager

Description: Contains one row that references the mail user's manager.

Property ID: 0x8005

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_MANAGER, PR_EMS_AB_MANAGER_A, PR_EMS_AB_MANAGER_W

2.618 PidTagAddressBookManagerDistinguishedName

Canonical name: PidTagAddressBookManagerDistinguishedName

Description: Contains the distinguished name (DN) of the mail user's manager.

Property ID: 0x8005

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_MANAGER_T

2.619 PidTagAddressBookMember

Canonical name: PidTagAddressBookMember

Description: Contains the members of the distribution list.

Property ID: 0x8009

Data type: PtypMultipleString, 0x101F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_MEMBER, PR_EMS_AB_MEMBER_A, PR_EMS_AB_MEMBER_W

2.620 PidTagAddressBookMessageId

Canonical name: PidTagAddressBookMessageId

Description: Short-term MID of the first message in the local site's offline address book public folder.

Property ID: 0x674F

Data type: PtypInteger64, 0x0014

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCSTOR\]](#)

Alternate names: ptagAddrbookMID

2.621 PidTagAddressBookModerationEnabled

Canonical name: PidTagAddressBookModerationEnabled

Description: Indicates whether moderation is enabled for the mail user of the distribution list.

Property ID: 0x8CB5

Data type: PtypBoolean, 0x000B

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_ENABLE_MODERATION

2.622 PidTagAddressBookNetworkAddress

Canonical name: PidTagAddressBookNetworkAddress

Description: Contains a list of names by which a server is known to the various transports in use by the network.

Property ID: 0x8170

Data type: PtypMultipleString, 0x101F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_NETWORK_ADDRESS, PR_EMS_AB_NETWORK_ADDRESS_A, PR_EMS_AB_NETWORK_ADDRESS_W

2.623 PidTagAddressBookObjectDistinguishedName

Canonical name: PidTagAddressBookObjectDistinguishedName

Description: Contains the distinguished name (DN) of the Address Book object in DN format, as specified in section 2.

Property ID: 0x803C

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_OBJ_DIST_NAME, PR_EMS_AB_OBJ_DIST_NAME_A, PR_EMS_AB_OBJ_DIST_NAME_W

2.624 PidTagAddressBookObjectGuid

Canonical name: PidTagAddressBookObjectGuid

Description: Contains a GUID that uniquely identifies an Address Book object.

Property ID: 0x8C6D

Data type: PtypBinary, 0x0102

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_OBJECT_GUID

2.625 PidTagAddressBookOrganizationalUnitRootDistinguishedName

Canonical name: PidTagAddressBookOrganizationalUnitRootDistinguishedName

Description: Contains the distinguished name (DN) of the Organization object of the mail user's organization.

Property ID: 0x8CA8

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_ORG_UNIT_ROOT_DN, msExchOURoot

2.626 PidTagAddressBookOwner

Canonical name: PidTagAddressBookOwner

Description: Contains one row that references the distribution list's owner.

Property ID: 0x800C

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_OWNER_O

2.627 PidTagAddressBookOwnerBackLink

Canonical name: PidTagAddressBookOwnerBackLink

Property ID: 0x8024

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_OWNER_BL_O

2.628 PidTagAddressBookParentEntryId

Canonical name: PidTagAddressBookParentEntryId

Description: Contains the Entry ID of the parent container in a hierarchy of address book containers.

Property ID: 0xFFFC

Data type: PtypBinary, 0x0102

Area: Address Book

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_PARENT_ENTRYID

2.629 PidTagAddressBookPhoneticCompanyName

Canonical name: PidTagAddressBookPhoneticCompanyName

Description: Contains the phonetic representation of the PidTagCompanyName property.

Property ID: 0x8C91

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_PHONETIC_COMPANY_NAME,
PR_EMS_AB_PHONETIC_COMPANY_NAME_A, PR_EMS_AB_PHONETIC_COMPANY_NAME_W

2.630 PidTagAddressBookPhoneticDepartmentName

Canonical name: PidTagAddressBookPhoneticDepartmentName

Description: Contains the phonetic representation of the PidTagDepartmentName property.

Property ID: 0x8C90

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_PHONETIC_DEPARTMENT_NAME,
PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_A, PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_W

2.631 PidTagAddressBookPhoneticDisplayName

Canonical name: PidTagAddressBookPhoneticDisplayName

Description: Contains the phonetic representation of the PidTagDisplayName property.

Property ID: 0x8C92

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_PHONETIC_DISPLAY_NAME,
PR_EMS_AB_PHONETIC_DISPLAY_NAME_A, PR_EMS_AB_PHONETIC_DISPLAY_NAME_W

2.632 PidTagAddressBookPhoneticGivenName

Canonical name: PidTagAddressBookPhoneticGivenName

Description: Contains the phonetic representation of the PidTagGivenName property.

Property ID: 0x8C8E

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_PHONETIC_GIVEN_NAME, PR_EMS_AB_PHONETIC_GIVEN_NAME_A, PR_EMS_AB_PHONETIC_GIVEN_NAME_W

2.633 PidTagAddressBookPhoneticSurname

Canonical name: PidTagAddressBookPhoneticSurname

Description: Contains the phonetic representation of the PidTagSurname property.

Property ID: 0x8C8F

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_PHONETIC_SURNAME, PR_EMS_AB_PHONETIC_SURNAME_A, PR_EMS_AB_PHONETIC_SURNAME_W

2.634 PidTagAddressBookProxyAddresses

Canonical name: PidTagAddressBookProxyAddresses

Description: Contains alternate e-mail addresses for the Address Book object.

Property ID: 0x800F

Data type: PtypMultipleString, 0x101F

Area: Address Book

References: [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_PROXY_ADDRESSES, PR_EMS_AB_PROXY_ADDRESSES_A, PR_EMS_AB_PROXY_ADDRESSES_W

2.635 PidTagAddressBookPublicDelegates

Canonical name: PidTagAddressBookPublicDelegates

Description: Contains a list of mail users who are allowed to send mail on behalf of the mailbox owner.

Property ID: 0x8015

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_PUBLIC_DELEGATES, PR_EMS_AB_PUBLIC_DELEGATES_A, PR_EMS_AB_PUBLIC_DELEGATES_W

2.636 PidTagAddressBookReports

Canonical name: PidTagAddressBookReports

Description: Lists all a mail user's direct reports.

Property ID: 0x800E

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_REPORTS, PR_EMS_AB_REPORTS_A, PR_EMS_AB_REPORTS_W

2.637 PidTagAddressBookRoomCapacity

Canonical name: PidTagAddressBookRoomCapacity

Description: Contains the maximum occupancy of the room.

Property ID: 0x0807

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_ROOM_CAPACITY

2.638 PidTagAddressBookRoomContainers

Canonical name: PidTagAddressBookRoomContainers

Description: Contains a list of DNs that represent the address book containers that hold Resource objects, such as conference rooms and equipment.

Property ID: 0x8C96

Data type: PtypMultipleString, 0x101F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_ROOM_CONTAINERS, PR_EMS_AB_ROOM_CONTAINERS_A, PR_EMS_AB_ROOM_CONTAINERS_W

2.639 PidTagAddressBookRoomDescription

Canonical name: PidTagAddressBookRoomDescription

Description: Contains a description of the Resource object.

Property ID: 0x0809

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_ROOM_DESCRIPTION, PR_EMS_AB_ROOM_DESCRIPTION_A, PR_EMS_AB_ROOM_DESCRIPTION_W

2.640 PidTagAddressBookSenderHintTranslations

Canonical name: PidTagAddressBookSenderHintTranslations

Description: Contains the locale ID and translations of the default mail tip.

Property ID: 0x8CAC

Data type: PtypMultipleString, 0x101F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_DL_SENDER_HINT_TRANSLATIONS_W

2.641 PidTagAddressBookSeniorityIndex

Canonical name: PidTagAddressBookSeniorityIndex

Description: Contains a signed integer that specifies the seniority order of Address Book objects that represent members of a department and are referenced by a Department object or departmental group, with larger values specifying members that are more senior.

Property ID: 0x8CA0

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_HAB_SENIORITY_INDEX, PR_EMS_AB_SENIORITY_INDEX

2.642 PidTagAddressBookTargetAddress

Canonical name: PidTagAddressBookTargetAddress

Description: Contains the foreign system e-mail address of an Address Book object.

Property ID: 0x8011

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_TARGET_ADDRESS, PR_EMS_AB_TARGET_ADDRESS_A, PR_EMS_AB_TARGET_ADDRESS_W

2.643 PidTagAddressBookUnauthorizedSenders

Canonical name: PidTagAddressBookUnauthorizedSenders

Description: Indicates whether delivery restrictions exist for this recipient.

Property ID: 0x8CD9

Data type: PtypComObject, 0x000D

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_UNAUTH_ORIG

2.644 PidTagAddressBookX509Certificate

Canonical name: PidTagAddressBookX509Certificate

Description: Contains the ASN_1 DER encoded X_509 certificates for the mail user.

Property ID: 0x8C6A

Data type: PtypMultipleBinary, 0x1102

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_X509_CERT

2.645 PidTagAddressType

Canonical name: PidTagAddressType

Description: Contains the Address Book object's e-mail address type.

Property ID: 0x3002

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

Alternate names: PR_ADDRTYPE, PR_ADDRTYPE_A, ptagAddrType, PR_ADDRTYPE_W

2.646 PidTagAlternateRecipientAllowed

Canonical name: PidTagAlternateRecipientAllowed

Property ID: 0x0002

Data type: PtypBoolean, 0x000B

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ALTERNATE_RECIPIENT_ALLOWED, ptagAlternateRecipientAllowed

2.647 PidTagAnr

Canonical name: PidTagAnr

Description: Contains a filter value used in ambiguous name resolution.

Property ID: 0x360C

Data type: PtypString, 0x001F

Area: Address Book

References: [\[MS-OXOABK\]](#)

Alternate names: PR_ANR, PR_ANR_A, PR_ANR_W

2.648 PidTagArchiveDate

Canonical name: PidTagArchiveDate

Property ID: 0x301F

Data type: PtypTime, 0x0040

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_ARCHIVE_DATE, ptagArchiveDate

2.649 PidTagArchivePeriod

Canonical name: PidTagArchivePeriod

Property ID: 0x301E

Data type: PtypInteger32, 0x0003

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_ARCHIVE_PERIOD, ptagArchivePeriod

2.650 PidTagArchiveTag

Canonical name: PidTagArchiveTag

Property ID: 0x3018

Data type: PtypBinary, 0x0102

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_ARCHIVE_TAG, ptagArchiveTag

2.651 PidTagAssistant

Canonical name: PidTagAssistant

Description: Contains the name of the mail user's administrative assistant.

Property ID: 0x3A30

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ASSISTANT, PR_ASSISTANT_A, PR_ASSISTANT_W,
urn:schemas:contacts:secretarycn

2.652 PidTagAssistantTelephoneNumber

Canonical name: PidTagAssistantTelephoneNumber

Description: Contains the telephone number of the mail user's administrative assistant.

Property ID: 0x3A2E

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ASSISTANT_TELEPHONE_NUMBER,
PR_ASSISTANT_TELEPHONE_NUMBER_A, PR_ASSISTANT_TELEPHONE_NUMBER_W,
urn:schemas:contacts:secretaryphone

2.653 PidTagAssociated

Canonical name: PidTagAssociated

Description: Specifies whether the message being synchronized is an FAI message.

Property ID: 0x67AA

Data type: PtypBoolean, 0x000B

Area: Sync

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagAssociated

2.654 PidTagAttachAdditionalInformation

Canonical name: PidTagAttachAdditionalInformation

Description: Contains attachment encoding information.

Property ID: 0x370F

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

References: [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_ATTACH_ADDITIONAL_INFO

2.655 PidTagAttachContentBase

Canonical name: PidTagAttachContentBase

Description: Contains the base of a relative URI.

Property ID: 0x3711

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_ATTACH_CONTENT_BASE, PR_ATTACH_CONTENT_BASE_A, PR_ATTACH_CONTENT_BASE_W

2.656 PidTagAttachContentId

Canonical name: PidTagAttachContentId

Description: Contains a content identifier unique to the Message object that matches a corresponding "cid:" URI scheme reference in the HTML body of the Message object.

Property ID: 0x3712

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_ATTACH_CONTENT_ID, PR_ATTACH_CONTENT_ID_A, PR_ATTACH_CONTENT_ID_W

2.657 PidTagAttachContentLocation

Canonical name: PidTagAttachContentLocation

Description: Contains a relative or full URI that matches a corresponding reference in the HTML body of a Message object.

Property ID: 0x3713

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#)

Alternate names: PR_ATTACH_CONTENT_LOCATION, PR_ATTACH_CONTENT_LOCATION_A, PR_ATTACH_CONTENT_LOCATION_W

2.658 PidTagAttachDataBinary

Canonical name: PidTagAttachDataBinary

Description: Contains the contents of the file to be attached.

Property ID: 0x3701

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_ATTACH_DATA_BIN, ptagAttachDataBin

2.659 PidTagAttachDataObject

Canonical name: PidTagAttachDataObject

Description: Contains the binary representation of the Attachment object in an application-specific format.

Property ID: 0x3701

Data type: PtypComObject, 0x000D

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCAL\]](#)

Alternate names: PR_ATTACH_DATA_OBJ, ptagAttachDataObj

2.660 PidTagAttachEncoding

Canonical name: PidTagAttachEncoding

Description: Contains encoding information about the Attachment object.

Property ID: 0x3702

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_ENCODING

2.661 PidTagAttachExtension

Canonical name: PidTagAttachExtension

Description: Contains a filename extension that indicates the document type of an attachment.

Property ID: 0x3703

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_EXTENSION, PR_ATTACH_EXTENSION_A, PR_ATTACH_EXTENSION_W

2.662 PidTagAttachFilename

Canonical name: PidTagAttachFilename

Description: Contains the 8.3 name of PidTagAttachLongFilename.

Property ID: 0x3704

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_FILENAME, PR_ATTACH_FILENAME_A, ptagAttachFilename, PR_ATTACH_FILENAME_W

2.663 PidTagAttachFlags

Canonical name: PidTagAttachFlags

Description: Indicates which body formats might reference this attachment when rendering data.

Property ID: 0x3714

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_FLAGS

2.664 PidTagAttachLongFilename

Canonical name: PidTagAttachLongFilename

Description: Contains the full filename and extension of the Attachment object.

Property ID: 0x3707

Data type: PtypString, 0x001F

Area: Message Attachment Properties Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOUM\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_LONG_FILENAME, PR_ATTACH_LONG_FILENAME_A, PR_ATTACH_LONG_FILENAME_W, urn:schemas:httpmail:attachmentfilename

2.665 PidTagAttachLongPathname

Canonical name: PidTagAttachLongPathname

Description: Contains the fully qualified path and filename with extension.

Property ID: 0x370D

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#)

Alternate names: PR_ATTACH_LONG_PATHNAME, PR_ATTACH_LONG_PATHNAME_A, ptagAttachLongPathname, PR_ATTACH_LONG_PATHNAME_W

2.666 PidTagAttachmentContactPhoto

Canonical name: PidTagAttachmentContactPhoto

Description: Indicates that a contact photo attachment is attached to a Contact object.

Property ID: 0x7FFF

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_ATTACHMENT_CONTACTPHOTO

2.667 PidTagAttachmentFlags

Canonical name: PidTagAttachmentFlags

Description: Indicates special handling for an Attachment object.

Property ID: 0x7FFD

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: PR_ATTACHMENT_FLAGS, ptagAttachmentFlags

2.668 PidTagAttachmentHidden

Canonical name: PidTagAttachmentHidden

Description: Indicates whether an Attachment object is hidden from the end user.

Property ID: 0x7FFE

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_ATTACHMENT_HIDDEN

2.669 PidTagAttachmentLinkId

Canonical name: PidTagAttachmentLinkId

Description: Contains the type of Message object to which this attachment is linked.

Property ID: 0x7FFA

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_ATTACHMENT_LINKID, ptagAttachmentLinkId

2.670 PidTagAttachMethod

Canonical name: PidTagAttachMethod

Description: Represents the way the contents of an attachment are accessed.

Property ID: 0x3705

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-XPFOAB\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_METHOD, ptagAttachMethod

2.671 PidTagAttachMimeTag

Canonical name: PidTagAttachMimeTag

Description: Contains a content-type MIME header.

Property ID: 0x370E

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#)

Alternate names: PR_ATTACH_MIME_TAG, PR_ATTACH_MIME_TAG_A, PR_ATTACH_MIME_TAG_W

2.672 PidTagAttachNumber

Canonical name: PidTagAttachNumber

Description: Identifies the Attachment object within its Message object.

Property ID: 0x0E21

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXRTFEX\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_NUM, ptagAttachNum

2.673 PidTagAttachPathname

Canonical name: PidTagAttachPathname

Description: Contains the 8.3 name of PidTagAttachLongPathname.

Property ID: 0x3708

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#)

Alternate names: PR_ATTACH_PATHNAME, PR_ATTACH_PATHNAME_A, ptagAttachPathname, PR_ATTACH_PATHNAME_W

2.674 PidTagAttachPayloadClass

Canonical name: PidTagAttachPayloadClass

Property ID: 0x371A

Data type: PtypString, 0x001F

Area: Outlook Application

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_PAYLOAD_CLASS, PR_ATTACH_PAYLOAD_CLASS_A, PR_ATTACH_PAYLOAD_CLASS_W, ptagAttachPayloadClass

2.675 PidTagAttachPayloadProviderGuidString

Canonical name: PidTagAttachPayloadProviderGuidString

Property ID: 0x3719

Data type: PtypString, 0x001F

Area: Outlook Application

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_PAYLOAD_PROV_GUID_STR, PR_ATTACH_PAYLOAD_PROV_GUID_STR_A, PR_ATTACH_PAYLOAD_PROV_GUID_STR_W

2.676 PidTagAttachRendering

Canonical name: PidTagAttachRendering

Description: Contains a Windows Metafile as specified in [MS-WMF] for the Attachment object.

Property ID: 0x3709

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_RENDERING, ptagAttachRendering

2.677 PidTagAttachSize

Canonical name: PidTagAttachSize

Description: Contains the size in bytes consumed by the Attachment object on the server.

Property ID: 0x0E20

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_SIZE, ptagAttachSize

2.678 PidTagAttachTag

Canonical name: PidTagAttachTag

Description: Contains the identifier information for the application which supplied the Attachment object's data.

Property ID: 0x370A

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_TAG

2.679 PidTagAttachTransportName

Canonical name: PidTagAttachTransportName

Description: Contains the name of an attachment file, modified so that it can be correlated with TNEF messages.

Property ID: 0x370C

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_TRANSPORT_NAME, PR_ATTACH_TRANSPORT_NAME_A, PR_ATTACH_TRANSPORT_NAME_W

2.680 PidTagAttributeHidden

Canonical name: PidTagAttributeHidden

Description: Specifies the hide or show status of a folder.

Property ID: 0x10F4

Data type: PtypBoolean, 0x000B

Area: Access Control Properties Property set

References: [\[MS-OXCFOLD\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ATTR_HIDDEN, ptagAttrHidden, DAV:ishidden

2.681 PidTagAttributeReadOnly

Canonical name: PidTagAttributeReadOnly

Property ID: 0x10F6

Data type: PtypBoolean, 0x000B

Area: Access Control Properties Property set

References: [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ATTR_READONLY, ptagAttrReadOnly, DAV:isreadonly

2.682 PidTagAttributeSystem

Canonical name: PidTagAttributeSystem

Property ID: 0x10F5

Data type: PtypBoolean, 0x000B

Area: Access Control Properties

References: [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTR_SYSTEM, ptagAttrSystem

2.683 PidTagAutoForwarded

Canonical name: PidTagAutoForwarded

Property ID: 0x0005

Data type: PtypBoolean, 0x000B

Area: General Report Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_AUTO_FORWARDED, ptagAutoForwarded

2.684 PidTagAutoResponseSuppress

Canonical name: PidTagAutoResponseSuppress

Property ID: 0x3FDF

Data type: PtypInteger32, 0x0003

Area: Email

References: [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_AUTO_RESPONSE_SUPPRESS, ptagAutoResponseSuppress

2.685 PidTagBirthday

Canonical name: PidTagBirthday

Description: Contains the date of the mail user's birthday at 12:00 AM.

Property ID: 0x3A42

Data type: PtypTime, 0x0040

Area: Contact Properties

References: [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BIRTHDAY, urn:schemas:contacts:bday

2.686 PidTagBlockStatus

Canonical name: PidTagBlockStatus

Description: Indicates the user's preference for viewing external content (such as links to images on an HTTP server) in the message body.

Property ID: 0x1096

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

References: [\[MS-OXCMSG\]](#)

Alternate names: PR_BLOCK_STATUS, ptagBlockStatus

2.687 PidTagBody

Canonical name: PidTagBody

Description: Contains message body text in plain text format.

Property ID: 0x1000

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BODY, PR_BODY_A, ptagBody, PR_BODY_W,
urn:schemas:httpmail:textdescription

2.688 PidTagBodyContentId

Canonical name: PidTagBodyContentId

Property ID: 0x1015

Data type: PtypString, 0x001F

Area: Exchange

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_BODY_CONTENT_ID, PR_BODY_CONTENT_ID_A, PR_BODY_CONTENT_ID_W

2.689 PidTagBodyContentLocation

Canonical name: PidTagBodyContentLocation

Property ID: 0x1014

Data type: PtypString, 0x001F

Area: MIME Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_BODY_CONTENT_LOCATION, PR_BODY_CONTENT_LOCATION_A,
PR_BODY_CONTENT_LOCATION_W

2.690 PidTagBodyHtml

Canonical name: PidTagBodyHtml

Property ID: 0x1013

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#),
[\[MS-OXRTFEX\]](#)

Alternate names: PR_BODY_HTML, PR_BODY_HTML_A, ptagBodyHtml, PR_BODY_HTML_W

2.691 PidTagBusiness2TelephoneNumber

Canonical name: PidTagBusiness2TelephoneNumber

Description: Contains a secondary telephone number at the mail user's place of business.

Property ID: 0x3A1B

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: "PR_BUSINESS2_TELEPHONE_NUMBER, PR_BUSINESS2_TELEPHONE_NUMBER_A, PR_BUSINESS2_TELEPHONE_NUMBER_W, PR_OFFICE2_TELEPHONE_NUMBER, urn:schemas:contacts:telephonenumber2

2.692 PidTagBusiness2TelephoneNumbers

Canonical name: PidTagBusiness2TelephoneNumbers

Description: Contains secondary telephone numbers at the mail user's place of business.

Property ID: 0x3A1B

Data type: PtypMultipleString, 0x101F

Area: Contact Properties

References: [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#)

Alternate names: PR_BUSINESS2_TELEPHONE_NUMBER_A_MV

2.693 PidTagBusinessFaxNumber

Canonical name: PidTagBusinessFaxNumber

Description: Contains the telephone number of the mail user's business fax machine.

Property ID: 0x3A24

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_FAX_NUMBER, PR_BUSINESS_FAX_NUMBER_A, PR_BUSINESS_FAX_NUMBER_W, urn:schemas:contacts:facsimiletelephonenumber

2.694 PidTagBusinessHomePage

Canonical name: PidTagBusinessHomePage

Description: Contains the Web address (URL) of the mail user's business home page.

Property ID: 0x3A51

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-EXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_HOME_PAGE, PR_BUSINESS_HOME_PAGE_A, PR_BUSINESS_HOME_PAGE_W, urn:schemas:contacts:businesshomepageurn:schemas:contacts:businesshomepage

2.695 PidTagBusinessTelephoneNumber

Canonical name: PidTagBusinessTelephoneNumber

Description: Contains the primary telephone number of the mail user's place of business.

Property ID: 0x3A08

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_TELEPHONE_NUMBER, PR_BUSINESS_TELEPHONE_NUMBER_A, PR_BUSINESS_TELEPHONE_NUMBER_W, PR_OFFICE_TELEPHONE_NUMBER, urn:schemas:contacts:telephoneNumber

2.696 PidTagCallbackTelephoneNumber

Canonical name: PidTagCallbackTelephoneNumber

Description: Contains a telephone number to reach the mail user.

Property ID: 0x3A02

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CALLBACK_TELEPHONE_NUMBER, PR_CALLBACK_TELEPHONE_NUMBER_A, PR_CALLBACK_TELEPHONE_NUMBER_W, urn:schemas:contacts:callbackphone

2.697 PidTagCallId

Canonical name: PidTagCallId

Property ID: 0x6806

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaCallID

2.698 PidTagCarTelephoneNumber

Canonical name: PidTagCarTelephoneNumber

Description: Contains the mail user's car telephone number.

Property ID: 0x3A1E

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CAR_TELEPHONE_NUMBER, PR_CAR_TELEPHONE_NUMBER_A, PR_CAR_TELEPHONE_NUMBER_W, urn:schemas:contacts:othermobile

2.699 PidTagCdoRecurrenceid

Canonical name: PidTagCdoRecurrenceid

Property ID: 0x10C5

Data type: PtypTime, 0x0040

Area: Exchange Property set

References: [\[MS-XWDCAL\]](#)

Alternate names: PR_CDO_RECURRENCEID, urn:schemas:calendar:recurrenceid

2.700 PidTagChangeKey

Canonical name: PidTagChangeKey

Description: Contains a global identifier (GID) indicating the last change to the object.

Property ID: 0x65E2

Data type: PtypBinary, 0x0102

Area: History Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_CHANGE_KEY

2.701 PidTagChangeNotificationGuid

Canonical name: PidTagChangeNotificationGuid

Property ID: 0x6637

Data type: PtypGuid, 0x0048

Area: Exchange

References: [\[MS-OXCNOTIF\]](#)

Alternate names: PR_CHANGE_NOTIFICATION_GUID

2.702 PidTagChangeNumber

Canonical name: PidTagChangeNumber

Description: Contains a value that identifies the last change to the message or folder that is currently being synchronized.

Property ID: 0x67A4

Data type: PtypInteger64, 0x0014

Area: Sync

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCSTOR\]](#)

Alternate names: ptagCn

2.703 PidTagChildrensNames

Canonical name: PidTagChildrensNames

Property ID: 0x3A58

Data type: PtypMultipleString, 0x101F

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CHILDRENS_NAMES, PR_CHILDRENS_NAMES_A, PR_CHILDRENS_NAMES_W, urn:schemas:contacts:childrensnames

2.704 PidTagClientActions

Canonical name: PidTagClientActions

Property ID: 0x6645

Data type: PtypBinary, 0x0102

Area: Server-side Rules Properties

References: [\[MS-OXORULE\]](#)

Alternate names: PR_CLIENT_ACTIONS, ptagClientActions

2.705 PidTagClientSubmitTime

Canonical name: PidTagClientSubmitTime

Description: Contains the current time (in UTC) when the email message is submitted.

Property ID: 0x0039

Data type: PtypTime, 0x0040

Area: Message Time Properties Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_CLIENT_SUBMIT_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

2.706 PidTagCnsetRead

Canonical name: PidTagCnsetRead

Description: Contains an IDSET of CNs tracking changes to the read state for messages in the current synchronization scope that have been previously communicated to the client, and are reflected in its local replica.

Property ID: 0x67D2

Data type: PtypBinary, 0x0102

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagCnsetRead

2.707 PidTagCnsetSeen

Canonical name: PidTagCnsetSeen

Description: Contains an IDSET of CNs for folders or normal messages in the current synchronization scope that have been previously communicated to a client, and are reflected in its local replica.

Property ID: 0x6796

Data type: PtypBinary, 0x0102

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagCnsetSeen

2.708 PidTagCnsetSeenFAI

Canonical name: PidTagCnsetSeenFAI

Description: Contains IDs for folder associated information (FAI) messages and is therefore only used in contents synchronization.

Property ID: 0x67DA

Data type: PtypBinary, 0x0102

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagCnsetSeenFAI

2.709 PidTagCodePageId

Canonical name: PidTagCodePageId

Property ID: 0x66C3

Data type: PtypInteger32, 0x0003

Area: Exchange Profile Configuration

References: [\[MS-OXCSTOR\]](#)

Alternate names: PR_CODE_PAGE_ID, ptagCodePageId

2.710 PidTagComment

Canonical name: PidTagComment

Description: Contains a comment about the purpose or content of the Address Book object.

Property ID: 0x3004

Data type: PtypString, 0x001F

Area: Common Property set

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMMENT, PR_COMMENT_A, ptagComment, PR_COMMENT_W, DAV:comment, <http://schemas.microsoft.com/exchange/summary-utf8>

2.711 PidTagCompanyMainTelephoneNumber

Canonical name: PidTagCompanyMainTelephoneNumber

Description: Contains the main telephone number of the mail user's company.

Property ID: 0x3A57

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMPANY_MAIN_PHONE_NUMBER, PR_COMPANY_MAIN_PHONE_NUMBER_A, PR_COMPANY_MAIN_PHONE_NUMBER_W, urn:schemas:contacts:organizationmainphone

2.712 PidTagCompanyName

Canonical name: PidTagCompanyName

Description: Contains the mail user's company name.

Property ID: 0x3A16

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#)

Alternate names: PR_COMPANY_NAME, PR_COMPANY_NAME_A, PR_COMPANY_NAME_W, urn:schemas:contacts:o

2.713 PidTagComputerNetworkName

Canonical name: PidTagComputerNetworkName

Description: Contains the name of the mail user's computer network.

Property ID: 0x3A49

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMPUTER_NETWORK_NAME, PR_COMPUTER_NETWORK_NAME_A, PR_COMPUTER_NETWORK_NAME_W, urn:schemas:contacts:computernetworkname

2.714 PidTagConflictEntryId

Canonical name: PidTagConflictEntryId

Property ID: 0x3FF0

Data type: PtypBinary, 0x0102

Area: ICS

References: [\[MS-OXCSYNC\]](#)

Alternate names: PR_CONFLICT_ENTRYID, ptagConflictEntryId

2.715 PidTagConflictItems

Canonical name: PidTagConflictItems

Property ID: 0x1098

Data type: PtypMultipleBinary, 0x1102

Area: ICS

References: [\[MS-OXCSYNC\]](#)

Alternate names: PR_CONFLICT_ITEMS

2.716 PidTagContainerClass

Canonical name: PidTagContainerClass

Description: Contains a value that describes the type of Message object that a folder contains.

Property ID: 0x3613

Data type: PtypString, 0x001F

Area: Container Properties Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

Alternate names: PR_CONTAINER_CLASS, PR_CONTAINER_CLASS_A, ptagContainerClass, PR_CONTAINER_CLASS_W,
<http://schemas.microsoft.com/exchange/outlookfolderclass>
<http://schemas.microsoft.com/exchange/outlookfolderclass>

2.717 PidTagContainerContents

Canonical name: PidTagContainerContents

Description: Always empty - an NSPI server MUST define this value for distribution lists and is not present for all other objects.

Property ID: 0x360F

Data type: PtypComObject, 0x000D

Area: Container Properties

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_CONTAINER_CONTENTS, ptagContainerContents

2.718 PidTagContainerFlags

Canonical name: PidTagContainerFlags

Description: Contains a bitmask of flags that describe capabilities of an address book container.

Property ID: 0x3600

Data type: PtypInteger32, 0x0003

Area: Address Book

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_CONTAINER_FLAGS

2.719 PidTagContainerHierarchy

Canonical name: PidTagContainerHierarchy

Description: Identifies all subfolders of the current folder.

Property ID: 0x360E

Data type: PtypComObject, 0x000D

Area: Container Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_CONTAINER_HIERARCHY, ptagContainerHierarchy

2.720 PidTagContentCount

Canonical name: PidTagContentCount

Description: Specifies the number of rows under the header row.

Property ID: 0x3602

Data type: PtypInteger32, 0x0003

Area: Folder Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CONTENT_COUNT, ptagContentCount, DAV:visiblecount

2.721 PidTagContentFilterPhishingConfidenceLevel

Canonical name: PidTagContentFilterPhishingConfidenceLevel

Property ID: 0x4084

Data type: PtypInteger32, 0x0003

Area: Secure Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: ContentFilterPcl, PR_CONTENT_FILTER_PCL

2.722 PidTagContentFilterSpamConfidenceLevel

Canonical name: PidTagContentFilterSpamConfidenceLevel

Description: Indicates a confidence level that the message is spam.

Property ID: 0x4076

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CONTENT_FILTER_SCL, ptagContentFilterSCL

2.723 PidTagContentUnreadCount

Canonical name: PidTagContentUnreadCount

Description: Specifies the number of rows under the header row that have the PidTagRead property set to FALSE.

Property ID: 0x3603

Data type: PtypInteger32, 0x0003

Area: Folder Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CONTENT_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

2.724 PidTagConversationId

Canonical name: PidTagConversationId

Property ID: 0x3013

Data type: PtypBinary, 0x0102

Area: Conversations

References: [\[MS-OXGLOS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_CONVERSATION_ID

2.725 PidTagConversationIndex

Canonical name: PidTagConversationIndex

Description: Indicates the relative position of this message within a conversation thread.

Property ID: 0x0071

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#),

Alternate names: PR_CONVERSATION_INDEX, ptagConversationIndex

2.726 PidTagConversationIndexTracking

Canonical name: PidTagConversationIndexTracking

Property ID: 0x3016

Data type: PtypBoolean, 0x000B

Area: Conversations

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_CONVERSATION_INDEX_TRACKING

2.727 PidTagConversationTopic

Canonical name: PidTagConversationTopic

Description: Contains an unchanging copy of the original subject.

Property ID: 0x0070

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_CONVERSATION_TOPIC, PR_CONVERSATION_TOPIC_A, ptagConversationTopic, PR_CONVERSATION_TOPIC_W, urn:schemas:httpmail:thread-topic

2.728 PidTagCountry

Canonical name: PidTagCountry

Description: Contains the name of the mail user's country/region.

Property ID: 0x3A26

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COUNTRY, PR_COUNTRY_A, PR_COUNTRY_W, PR_BUSINESS_ADDRESS_COUNTRY, PR_BUSINESS_ADDRESS_COUNTRY_A, PR_BUSINESS_ADDRESS_COUNTRY_W, urn:schemas:contacts:mailingcountry

2.729 PidTagCreationTime

Canonical name: PidTagCreationTime

Description: Contains the time the object was created in UTC.

Property ID: 0x3007

Data type: PtypTime, 0x0040

Area: Message Time Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CREATION_TIME, ptagCreationTime, DAV:creationdate

2.730 PidTagCreatorEntryId

Canonical name: PidTagCreatorEntryId

Property ID: 0x3FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CREATOR_ENTRYID, ptagCreatorEntryId

2.731 PidTagCreatorName

Canonical name: PidTagCreatorName

Description: Contains the name of a Message object.

Property ID: 0x3FF8

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CREATOR_NAME, PR_CREATOR_NAME_A, ptagCreatorName, PR_CREATOR_NAME_W

2.732 PidTagCreatorSimpleDisplayName

Canonical name: PidTagCreatorSimpleDisplayName

Property ID: 0x4038

Data type: PtypString, 0x001F

Area: TransportEnvelope

References: [\[MS-OXTNEF\]](#)

Alternate names: ptagCreatorSimpleDispName

2.733 PidTagCustomerId

Canonical name: PidTagCustomerId

Description: Contains the mail user's customer identification number.

Property ID: 0x3A4A

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CUSTOMER_ID, PR_CUSTOMER_ID_A, PR_CUSTOMER_ID_W, urn:schemas:contacts:customerid

2.734 PidTagDamBackPatched

Canonical name: PidTagDamBackPatched

Property ID: 0x6647

Data type: PtypBoolean, 0x000B

Area: Server-side Rules Properties

References: [\[MS-OXORULE\]](#)

Alternate names: PR_DAM_BACK_PATCHED, ptagDamBackPatched

2.735 PidTagDamOriginalEntryId

Canonical name: PidTagDamOriginalEntryId

Property ID: 0x6646

Data type: PtypBinary, 0x0102

Area: Server-side Rules Properties

References: [\[MS-OXORULE\]](#)

Alternate names: PR_DAM_ORIGINAL_ENTRYID

2.736 PidTagDefaultPostMessageClass

Canonical name: PidTagDefaultPostMessageClass

Description: Contains the message class of the object.

Property ID: 0x36E5

Data type: PtypString, 0x001F

Area: MapiContainer

References: [\[MS-OXOCAL\]](#)

Alternate names: PR_DEF_POST_MSGCLASS

2.737 PidTagDeferredDeliveryTime

Canonical name: PidTagDeferredDeliveryTime

Description: Contains the date and time, in UTC, at which the sender prefers the message to be delivered.

Property ID: 0x000F

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_DEFERRED_DELIVERY_TIME, ptagDeferredDeliveryTime,
<http://schemas.microsoft.com/exchange/deferred-delivery-iso>

2.738 PidTagDeferredSendNumber

Canonical name: PidTagDeferredSendNumber

Description: Contains a number used in the calculation of how long to defer sending a message.

Property ID: 0x3FEB

Data type: PtypInteger32, 0x0003

Area: MapiStatus

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_DEFERRED_SEND_NUMBER

2.739 PidTagDeferredSendTime

Canonical name: PidTagDeferredSendTime

Description: Contains the amount of time after which a client would like to defer sending the message.

Property ID: 0x3FEF

Data type: PtypTime, 0x0040

Area: MapiStatus

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_DEFERRED_SEND_TIME, ptagDeferredSendTime

2.740 PidTagDeferredSendUnits

Canonical name: PidTagDeferredSendUnits

Description: Specifies the unit of time that the PidTagDeferredSendNumber property value SHOULD be multiplied by.

Property ID: 0x3FEC

Data type: PtypInteger32, 0x0003

Area: MapiStatus

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_DEFERRED_SEND_UNITS

2.741 PidTagDelegatedByRule

Canonical name: PidTagDelegatedByRule

Property ID: 0x3FE3

Data type: PtypBoolean, 0x000B

Area: MapiStatus

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_DELEGATED_BY_RULE

2.742 PidTagDelegateFlags

Canonical name: PidTagDelegateFlags

Property ID: 0x686B

Data type: PtypMultipleInteger32, 0x1003

Area: MessageClassDefinedTransmittable

References: [\[MS-OXODLGT\]](#)

Alternate names: PR_DELEGATE_FLAGS, ptagDelegateFlags

2.743 PidTagDeleteAfterSubmit

Canonical name: PidTagDeleteAfterSubmit

Description: Indicates that the original message is to be deleted after the message is sent.

Property ID: 0x0E01

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

References: [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_DELETE_AFTER_SUBMIT, ptagDeleteAfterSubmit

2.744 PidTagDeletedOn

Canonical name: PidTagDeletedOn

Description: Specifies the time when the item or folder was soft deleted.

Property ID: 0x668F

Data type: PtypTime, 0x0040

Area: ExchangeFolder Property set

References: [\[MS-OXCFOLD\]](#)

Alternate names: PR_DELETED_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

2.745 PidTagDepartmentName

Canonical name: PidTagDepartmentName

Description: Contains a name for the department in which the mail user works.

Property ID: 0x3A18

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_DEPARTMENT_NAME, PR_DEPARTMENT_NAME_A, PR_DEPARTMENT_NAME_W, urn:schemas:contacts:department

2.746 PidTagDepth

Canonical name: PidTagDepth

Description: Specifies the number of nested categories in which a given row is contained.

Property ID: 0x3005

Data type: PtypInteger32, 0x0003

Area: MapiCommon

References: [\[MS-NSPI\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

Alternate names: PR_DEPTH, ptagDepth

2.747 PidTagDisplayBcc

Canonical name: PidTagDisplayBcc

Description: Contains a list of blind carbon copy (Bcc) recipient display names.

Property ID: 0x0E02

Data type: PtypString, 0x001F

Area: Message Properties Property set

References: [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_DISPLAY_BCC, PR_DISPLAY_BCC_A, ptagDisplayBcc, PR_DISPLAY_BCC_W, urn:schemas:httpmail:displaybcc

2.748 PidTagDisplayCc

Canonical name: PidTagDisplayCc

Description: Contains list of carbon copy (Cc) recipient display names.

Property ID: 0x0E03

Data type: PtypString, 0x001F

Area: Message Properties Property set

References: [\[MS-OXCMMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_DISPLAY_CC, PR_DISPLAY_CC_A, ptagDisplayCc, PR_DISPLAY_CC_W, urn:schemas:httpmail:displaycc

2.749 PidTagDisplayName

Canonical name: PidTagDisplayName

Description: Contains the name of the attachment as input by the end user.

Property ID: 0x3001

Data type: PtypString, 0x001F

Area: MapiCommon

References: [\[MS-OXCMMSG\]](#), [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDVSEC\]](#)

Alternate names: PR_DISPLAY_NAME, PR_DISPLAY_NAME_A, ptagDisplayName, PR_DISPLAY_NAME_W, urn:schemas:contacts:cn

2.750 PidTagDisplayNamePrefix

Canonical name: PidTagDisplayNamePrefix

Description: Contains the mail user's honorific title.

Property ID: 0x3A45

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_DISPLAY_NAME_PREFIX, PR_DISPLAY_NAME_PREFIX_A, PR_DISPLAY_NAME_PREFIX_W, urn:schemas:contacts:personaltitle

2.751 PidTagDisplayTo

Canonical name: PidTagDisplayTo

Description: Contains a list of the primary recipient display names, separated by semicolons, if an email message has primary recipient.

Property ID: 0x0E04

Data type: PtypString, 0x001F

Area: Message Properties

References: [\[MS-OXCMMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_DISPLAY_TO, PR_DISPLAY_TO_A, ptagDisplayTo, PR_DISPLAY_TO_W

2.752 PidTagDisplayType

Canonical name: PidTagDisplayType

Description: Contains a value that indicates how to display an Address Book object in a table or as an addressee on a message.

Property ID: 0x3900

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

References: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_DISPLAY_TYPE, ptagDisplayType

2.753 PidTagDisplayTypeEx

Canonical name: PidTagDisplayTypeEx

Description: Contains a value that indicates how to display an Address Book object in a table or as a recipient on a message.

Property ID: 0x3905

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_DISPLAY_TYPE_EX

2.754 PidTagEcWarning

Canonical name: PidTagEcWarning

Description: Contains a value that conveys a warning that occurred when producing output for an element in context.

Property ID: 0x400F

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagEcWarning

2.755 PidTagEmailAddress

Canonical name: PidTagEmailAddress

Description: Contains the Address Book object's e-mail address.

Property ID: 0x3003

Data type: PtypString, 0x001F

Area: MapiCommon

References: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXPSVAL\]](#)

Alternate names: PR_EMAIL_ADDRESS, PR_EMAIL_ADDRESS_A, PR_EMAIL_ADDRESS_W

2.756 PidTagEndAttach

Canonical name: PidTagEndAttach

Property ID: 0x400E

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagEndAttach

2.757 PidTagEndDate

Canonical name: PidTagEndDate

Description: Contains the value of the PidLidAppointmentEndWhole property.

Property ID: 0x0061

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: PR_END_DATE, http://schemas.microsoft.com/mapi/end_date

2.758 PidTagEndEmbed

Canonical name: PidTagEndEmbed

Property ID: 0x4002

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagEndEmbed

2.759 PidTagEndFolder

Canonical name: PidTagEndFolder

Property ID: 0x400B

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagEndFolder

2.760 PidTagEndMessage

Canonical name: PidTagEndMessage

Property ID: 0x400D

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagEndMessage

2.761 PidTagEndToRecip

Canonical name: PidTagEndToRecip

Property ID: 0x4004

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagEndToRecip

2.762 PidTagEntryId

Canonical name: PidTagEntryId

Description: Contains the information to identify many different types of messaging objects, including objects that are not in an address book.

Property ID: 0x0FFF

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPerm\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-](#)

[OXODLGT](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXWAVLS\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_ENTRYID, ptagEntryId

2.763 PidTagExceptionEndTime

Canonical name: PidTagExceptionEndTime

Description: Contains the start date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFC

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_EXCEPTION_ENDTIME, ptagExceptionEndTime

2.764 PidTagExceptionReplaceTime

Canonical name: PidTagExceptionReplaceTime

Property ID: 0x7FF9

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

References: [\[MS-OXOCAL\]](#)

Alternate names: PR_EXCEPTION_REPLACETIME

2.765 PidTagExceptionStartTime

Canonical name: PidTagExceptionStartTime

Description: Contains the end date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFB

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_EXCEPTION_STARTTIME, ptagExceptionStartTime

2.766 PidTagExchangeNTSecurityDescriptor

Canonical name: PidTagExchangeNTSecurityDescriptor

Property ID: 0x0E84

Data type: PtypBinary, 0x0102

Area: Calendar Document Property set

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/ntsecuritydescriptor>,
<http://schemas.microsoft.com/exchange/ntsecuritydescriptor>

2.767 PidTagExpiryNumber

Canonical name: PidTagExpiryNumber

Description: Used along with PidTagExpiryUnits to define the expiry send time.

Property ID: 0x3FED

Data type: PtypInteger32, 0x0003

Area: MapiStatus

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_EXPIRY_NUMBER

2.768 PidTagExpiryTime

Canonical name: PidTagExpiryTime

Description: Contains the time after which a client wants to receive an expiry event if the message arrives late.

Property ID: 0x0015

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_EXPIRY_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date,
<http://schemas.microsoft.com/exchange/expiry-date-iso>

2.769 PidTagExpiryUnits

Canonical name: PidTagExpiryUnits

Description: Used to describe the unit of time that PidTagExpiryNumber multiplies.

Property ID: 0x3FEE

Data type: PtypInteger32, 0x0003

Area: MapiStatus

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_EXPIRY_UNITS

2.770 PidTagExtendedFolderFlags

Canonical name: PidTagExtendedFolderFlags

Description: Contains encoded sub-properties for a folder.

Property ID: 0x36DA

Data type: PtypBinary, 0x0102

Area: MapiContainer

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_EXTENDED_FOLDER_FLAGS, ptagExtendedFolderFlags

2.771 PidTagExtendedRuleMessageActions

Canonical name: PidTagExtendedRuleMessageActions

Property ID: 0x0E99

Data type: PtypBinary, 0x0102

Area: Rules

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_EXTENDED_RULE_MSG_ACTIONS

2.772 PidTagExtendedRuleMessageCondition

Canonical name: PidTagExtendedRuleMessageCondition

Property ID: 0x0E9A

Data type: PtypBinary, 0x0102

Area: Rules

References: [\[MS-OXCPRPT\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_EXTENDED_RULE_MSG_CONDITION

2.773 PidTagExtendedRuleSizeLimit

Canonical name: PidTagExtendedRuleSizeLimit

Property ID: 0x0E9B

Data type: PtypInteger32, 0x0003

Area: Rules

References: [\[MS-OXCSTOR\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_EXTENDED_RULE_SIZE_LIMIT

2.774 PidTagFaxNumberOfPages

Canonical name: PidTagFaxNumberOfPages

Property ID: 0x6804

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaFaxNumberOfPages

2.775 PidTagFlagCompleteTime

Canonical name: PidTagFlagCompleteTime

Description: Specifies the date and time in UTC that the Message object was flagged completed.

Property ID: 0x1091

Data type: PtypTime, 0x0040

Area: Miscellaneous Properties Property set

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_FLAG_COMPLETE_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

2.776 PidTagFlagStatus

Canonical name: PidTagFlagStatus

Description: Specifies the flag state of the Message object.

Property ID: 0x1090

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FLAG_STATUS, ptagFlagStatus

2.777 PidTagFlatUrlName

Canonical name: PidTagFlatUrlName

Property ID: 0x670E

Data type: PtypString, 0x001F

Area: ExchangeAdministrative Property set

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_FLAT_URL_NAME, PR_FLAT_URL_NAME_A, PR_FLAT_URL_NAME_W, ptagFlatURLName, <http://schemas.microsoft.com/exchange/permanenturl>

2.778 PidTagFolderAssociatedContents

Canonical name: PidTagFolderAssociatedContents

Description: Identifies all FAI messages in the current folder.

Property ID: 0x3610

Data type: PtypComObject, 0x000D

Area: MapiContainer

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_FOLDER_ASSOCIATED_CONTENTS

2.779 PidTagFolderId

Canonical name: PidTagFolderId

Description: Contains the FID of the folder.

Property ID: 0x6748

Data type: PtypInteger64, 0x0014

Area: ID Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: ptagFID

2.780 PidTagFolderType

Canonical name: PidTagFolderType

Description: Specifies the type of a folder, that includes root folder, generic fold, and search folder.

Property ID: 0x3601

Data type: PtypInteger32, 0x0003

Area: MapiContainer

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_FOLDER_TYPE, ptagFolderType

2.781 PidTagFollowupIcon

Canonical name: PidTagFollowupIcon

Description: Specifies the flag color of the Message object.

Property ID: 0x1095

Data type: PtypInteger32, 0x0003

Area: RenMessageFolder

References: [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FOLLOWUP_ICON, ptagFollowupIcon

2.782 PidTagFreeBusyCountMonths

Canonical name: PidTagFreeBusyCountMonths

Description: Contains a value used to calculate the start and end dates of the range of free/busy data to be published to the public folders.

Property ID: 0x6869

Data type: PtypInteger32, 0x0003

Area: MessageClassDefinedTransmittable

References: [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_FREEBUSY_COUNT_MONTHS

2.783 PidTagFreeBusyEntryIds

Canonical name: PidTagFreeBusyEntryIds

Property ID: 0x36E4

Data type: PtypMultipleBinary, 0x1102

Area: MapiContainer

References: [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FREEBUSY_ENTRYIDS, ptagFreeBusyEntryIds

2.784 PidTagFreeBusyMessageEmailAddress

Canonical name: PidTagFreeBusyMessageEmailAddress

Property ID: 0x6849

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_FREEBUSY_EMA

2.785 PidTagFreeBusyPublishEnd

Canonical name: PidTagFreeBusyPublishEnd

Property ID: 0x6848

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_FREEBUSY_PUBLISH_END

2.786 PidTagFreeBusyPublishStart

Canonical name: PidTagFreeBusyPublishStart

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_FREEBUSY_PUBLISH_START

2.787 PidTagFreeBusyRangeTimestamp

Canonical name: PidTagFreeBusyRangeTimestamp

Property ID: 0x6868

Data type: PtypTime, 0x0040

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_FREEBUSY_RANGE_TIMESTAMP

2.788 PidTagFtpSite

Canonical name: PidTagFtpSite

Description: Contains the mail user's File Transfer Protocol (FTP) site address.

Property ID: 0x3A4C

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_FTP_SITE, PR_FTP_SITE_A, PR_FTP_SITE_W, urn:schemas:contacts:ftpsite

2.789 PidTagFXDelProp

Canonical name: PidTagFXDelProp

Description: Contains a value that represents a directive to a client to delete specific subobjects of the object in context.

Property ID: 0x4016

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagFXDelProp

2.790 PidTagFXErrorInfo

Canonical name: PidTagFXErrorInfo

Property ID: 0x4018

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagFXErrorInfo

2.791 PidTagGatewayNeedsToRefresh

Canonical name: PidTagGatewayNeedsToRefresh

Property ID: 0x6846

Data type: PtypBoolean, 0x000B

Area: MessageClassDefinedTransmittable

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_GATEWAY_NEEDS_TO_REFRESH

2.792 PidTagGender

Canonical name: PidTagGender

Description: Contains a value that represents the mail user's gender.

Property ID: 0x3A4D

Data type: PtypInteger16, 0x0002

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GENDER, urn:schemas:contacts:gender

2.793 PidTagGeneration

Canonical name: PidTagGeneration

Description: Contains a generational abbreviation that follows the full name of the mail user.

Property ID: 0x3A05

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GENERATION, PR_GENERATION_A, PR_GENERATION_W, urn:schemas:contacts:namesuffix

2.794 PidTagGivenName

Canonical name: PidTagGivenName

Description: Contains the mail user's given name.

Property ID: 0x3A06

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GIVEN_NAME, PR_GIVEN_NAME_A, PR_GIVEN_NAME_W, urn:schemas:contacts:givenName

2.795 PidTagGovernmentIdNumber

Canonical name: PidTagGovernmentIdNumber

Description: Contains a government identifier for the mail user.

Property ID: 0x3A07

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GOVERNMENT_ID_NUMBER, PR_GOVERNMENT_ID_NUMBER_A, PR_GOVERNMENT_ID_NUMBER_W, urn:schemas:contacts:governmentid

2.796 PidTagHasAttachments

Canonical name: PidTagHasAttachments

Description: Indicates whether the Message object contains at least one attachment.

Property ID: 0x0E1B

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

2.797 PidTagHasDeferredActionMessages

Canonical name: PidTagHasDeferredActionMessages

Property ID: 0x3FEA

Data type: PtypBoolean, 0x000B

Area: Rules

References: [\[MS-OXORULE\]](#)

Alternate names: PR_HAS_DAMS, ptagHasDAMs

2.798 PidTagHasNamedProperties

Canonical name: PidTagHasNamedProperties

Property ID: 0x664A

Data type: PtypBoolean, 0x000B

Area: ExchangeMessageReadOnly

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_HAS_NAMED_PROPERTIES, ptagHasNamedProperties

2.799 PidTagHasRules

Canonical name: PidTagHasRules

Property ID: 0x663A

Data type: PtypBoolean, 0x000B

Area: ExchangeFolder

References: [\[MS-OXORULE\]](#)

Alternate names: PR_HAS_RULES, ptagHasRules

2.800 PidTagHierarchyChangeNumber

Canonical name: PidTagHierarchyChangeNumber

Description: Contains a number that monotonically increases every time a subfolder is added to or deleted from this folder.

Property ID: 0x663E

Data type: PtypInteger32, 0x0003

Area: ExchangeFolder

References: [\[MS-OXCFOLD\]](#)

Alternate names: PR_HIERARCHY_CHANGE_NUM

2.801 PidTagHobbies

Canonical name: PidTagHobbies

Description: Contains the names of the mail user's hobbies.

Property ID: 0x3A43

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOBBIES, PR_HOBBIES_A, PR_HOBBIES_W, urn:schemas:contacts:hobbies

2.802 PidTagHome2TelephoneNumber

Canonical name: PidTagHome2TelephoneNumber

Description: Contains a secondary telephone number at the mail user's home.

Property ID: 0x3A2F

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME2_TELEPHONE_NUMBER, PR_HOME2_TELEPHONE_NUMBER_A, PR_HOME2_TELEPHONE_NUMBER_W, urn:schemas:contacts:homephone2

2.803 PidTagHome2TelephoneNumbers

Canonical name: PidTagHome2TelephoneNumbers

Description: Contains secondary telephone numbers at the mail user's home.

Property ID: 0x3A2F

Data type: PtypMultipleString, 0x101F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_HOME2_TELEPHONE_NUMBER_A_MV

2.804 PidTagHomeAddressCity

Canonical name: PidTagHomeAddressCity

Description: Contains the name of the mail user's home locality, such as the town or city.

Property ID: 0x3A59

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_CITY, PR_HOME_ADDRESS_CITY_A, PR_HOME_ADDRESS_CITY_W, urn:schemas:contacts:homeCity

2.805 PidTagHomeAddressCountry

Canonical name: PidTagHomeAddressCountry

Description: Contains the name of the mail user's home country/region.

Property ID: 0x3A5A

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_COUNTRY, PR_HOME_ADDRESS_COUNTRY_A, PR_HOME_ADDRESS_COUNTRY_W, urn:schemas:contacts:homeCountry

2.806 PidTagHomeAddressPostalCode

Canonical name: PidTagHomeAddressPostalCode

Description: Contains the postal code for the mail user's home postal address.

Property ID: 0x3A5B

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_POSTAL_CODE, PR_HOME_ADDRESS_POSTAL_CODE_A, PR_HOME_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:homePostalCode

2.807 PidTagHomeAddressPostOfficeBox

Canonical name: PidTagHomeAddressPostOfficeBox

Description: Contains the number or identifier of the mail user's home post office box.

Property ID: 0x3A5E

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_POST_OFFICE_BOX, PR_HOME_ADDRESS_POST_OFFICE_BOX_A, PR_HOME_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:homepostofficebox

2.808 PidTagHomeAddressStateOrProvince

Canonical name: PidTagHomeAddressStateOrProvince

Description: Contains the name of the mail user's home state or province.

Property ID: 0x3A5C

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_STATE_OR_PROVINCE, PR_HOME_ADDRESS_STATE_OR_PROVINCE_A, PR_HOME_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:homeState

2.809 PidTagHomeAddressStreet

Canonical name: PidTagHomeAddressStreet

Description: Contains the mail user's home street address.

Property ID: 0x3A5D

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_STREET, PR_HOME_ADDRESS_STREET_A, PR_HOME_ADDRESS_STREET_W, urn:schemas:contacts:homeStreet

2.810 PidTagHomeFaxNumber

Canonical name: PidTagHomeFaxNumber

Description: Contains the telephone number of the mail user's home fax machine.

Property ID: 0x3A25

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_FAX_NUMBER, PR_HOME_FAX_NUMBER_A, PR_HOME_FAX_NUMBER_W, urn:schemas:contacts:homefax

2.811 PidTagHomeTelephoneNumber

Canonical name: PidTagHomeTelephoneNumber

Description: Contains the primary telephone number of the mail user's home.

Property ID: 0x3A09

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_TELEPHONE_NUMBER, PR_HOME_TELEPHONE_NUMBER_A, PR_HOME_TELEPHONE_NUMBER_W, urn:schemas:contacts:homePhone

2.812 PidTagHtml

Canonical name: PidTagHtml

Description: Contains message body text in HTML format.

Property ID: 0x1013

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_HTML, ptagHtml

2.813 PidTagICalendarEndTime

Canonical name: PidTagICalendarEndTime

Property ID: 0x10C4

Data type: PtypTime, 0x0040

Area: Calendar Property set

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:dtend

2.814 PidTagICalendarReminderNextTime

Canonical name: PidTagICalendarReminderNextTime

Property ID: 0x10CA

Data type: PtypTime, 0x0040

Area: Calendar Property set

References: [\[MS-XWDCAL\]](#)

Alternate names: urn:schemas:calendar:remindernexttime

2.815 PidTagICalendarStartTime

Canonical name: PidTagICalendarStartTime

Property ID: 0x10C3

Data type: PtypTime, 0x0040

Area: Calendar Property set

References: [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:dtstart

2.816 PidTagIconIndex

Canonical name: PidTagIconIndex

Description: Specifies which icon is to be used by a user interface when displaying a group of Note objects.

Property ID: 0x1080

Data type: PtypInteger32, 0x0003

Area: General Message Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ICON_INDEX, ptagIconIndex

2.817 PidTagIdsetDeleted

Canonical name: PidTagIdsetDeleted

Description: Contains a serialization of REPLID-based IDSETs.

Property ID: 0x67E5

Data type: PtypBinary, 0x0102

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIdsetDeleted

2.818 PidTagIdsetExpired

Canonical name: PidTagIdsetExpired

Description: Contains a serialization of a REPLID-based IDSETs that contains IDs that expired since the last synchronization identified by the initial ICS state.

Property ID: 0x6793

Data type: PtypBinary, 0x0102

Area: Sync

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagMidsetExpired

2.819 PidTagIdsetGiven

Canonical name: PidTagIdsetGiven

Description: Contains a value that contains a serialized IDSET of folder IDs (FIDs) for hierarchy synchronization, or message IDs (MIDs) for contents synchronization, that exist in the local replica of the client.

Property ID: 0x4017

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIdsetGiven

2.820 PidTagIdsetRead

Canonical name: PidTagIdsetRead

Description: Contains a serialization of a REPLID-based IDSETs that contain IDs of messages that were marked as read since the last synchronization identified by the initial ICS state.

Property ID: 0x402D

Data type: PtypBinary, 0x0102

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIdsetRead

2.821 PidTagIdsetNoLongerInScope

Canonical name: PidTagIdsetNoLongerInScope

Description: Contains a serialization of a REPLID-based IDSET that contains the IDs of messages that got out of synchronization scope since the last synchronization identified by the initial ICS state.

Property ID: 0x4021

Data type: PtypBinary, 0x0102

Area: Sync

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagSoftDeletes

2.822 PidTagIdsetUnread

Canonical name: PidTagIdsetUnread

Description: Contains a serialization of a REPLID-based IDSET that contains IDs of messages that were marked as unread since the last synchronization identified by the initial ICS state.

Property ID: 0x402E

Data type: PtypBinary, 0x0102

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIdsetUnread

2.823 PidTagImapCachedMsgsize

Canonical name: PidTagImapCachedMsgsize

Property ID: 0x10F0

Data type: PtypBinary, 0x0102

Area: RenMessageFolder

References: [\[MS-OXTNEF\]](#)

Alternate names: ptagImapCachedMsgsize

2.824 PidTagImportance

Canonical name: PidTagImportance

Description: Indicates the level of importance assigned by the end user to the Message object.

Property ID: 0x0017

Data type: PtypInteger32, 0x0003

Area: General Message Properties Property set

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, <http://schemas.microsoft.com/exchange/importance-long>, <http://schemas.microsoft.com/exchange/x-priority-long>

2.825 PidTagInConflict

Canonical name: PidTagInConflict

Property ID: 0x666C

Data type: PtypBoolean, 0x000B

Area: Conflict Note

References: [\[MS-OXCSYNC\]](#)

Alternate names: PR_IN_CONFLICT, ptagInConflict

2.826 PidTagIncrementalSyncMessagePartial

Canonical name: PidTagIncrementalSyncMessagePartial

Description: Contains a value that specifies an index of a property group within a property group mapping currently in context.

Property ID: 0x407A

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncMsgPartial

2.827 PidTagIncrSyncChg

Canonical name: PidTagIncrSyncChg

Property ID: 0x4012

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncChg

2.828 PidTagIncrSyncChgPartial

Canonical name: PidTagIncrSyncChgPartial

Property ID: 0x407D

Data type: PtypInteger32, 0x0003

Area: IC

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncChgPartial

2.829 PidTagIncrSyncDel

Canonical name: PidTagIncrSyncDel

Property ID: 0x4013

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncDel

2.830 PidTagIncrSyncEnd

Canonical name: PidTagIncrSyncEnd

Property ID: 0x4014

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncEnd

2.831 PidTagIncrSyncGroupId

Canonical name: PidTagIncrSyncGroupId

Property ID: 0x407C

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncGroupId

2.832 PidTagIncrSyncGroupInfo

Canonical name: PidTagIncrSyncGroupInfo

Property ID: 0x407B

Data type: PtypBinary, 0x0102

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncGroupInfo

2.833 PidTagIncrSyncMessage

Canonical name: PidTagIncrSyncMessage

Property ID: 0x4015

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncMsg

2.834 PidTagIncrSyncProgressMode

Canonical name: PidTagIncrSyncProgressMode

Property ID: 0x4074

Data type: PtypBoolean, 0x000B

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncProgressMode

2.835 PidTagIncrSyncProgressPerMsg

Canonical name: PidTagIncrSyncProgressPerMsg

Property ID: 0x4075

Data type: PtypBoolean, 0x000B

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncProgressPerMsg

2.836 PidTagIncrSyncRead

Canonical name: PidTagIncrSyncRead

Property ID: 0x402F

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncRead

2.837 PidTagIncrSyncStateBegin

Canonical name: PidTagIncrSyncStateBegin

Property ID: 0x403A

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncStateBegin

2.838 PidTagIncrSyncStateEnd

Canonical name: PidTagIncrSyncStateEnd

Property ID: 0x403B

Data type: PtypInteger32, 0x0003

Area: ICS

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagIncrSyncStateEnd

2.839 PidTagInitialDetailsPane

Canonical name: PidTagInitialDetailsPane

Description: Contains which page of a display template to display first.

Property ID: 0x3F08

Data type: PtypInteger32, 0x0003

Area: MAPI Display Tables

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_INITIAL_DETAILS_PANE

2.840 PidTagInitials

Canonical name: PidTagInitials

Description: Contains the initials for parts of the full name of the mail user.

Property ID: 0x3A0A

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_INITIALS, PR_INITIALS_A, PR_INITIALS_W, urn:schemas:contacts:initials

2.841 PidTagInReplyToId

Canonical name: PidTagInReplyToId

Description: Contains the original message's PidTagInternetMessageId value.

Property ID: 0x1042

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_IN_REPLY_TO_ID, PR_IN_REPLY_TO_ID_A, PR_IN_REPLY_TO_ID_W

2.842 PidTagInstanceKey

Canonical name: PidTagInstanceKey

Description: Contains an object on an NSPI server.

Property ID: 0x0FF6

Data type: PtypBinary, 0x0102

Area: Table Properties

References: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

Alternate names: PR_INSTANCE_KEY, ptagInstanceKey

2.843 PidTagInstanceNum

Canonical name: PidTagInstanceNum

Description: Contains an identifier for a single instance of a row in the table.

Property ID: 0x674E

Data type: PtypInteger32, 0x0003

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: ptagInstanceNum

2.844 PidTagInstID

Canonical name: PidTagInstID

Description: Contains an identifier for all instances of a row in the table.

Property ID: 0x674D

Data type: PtypInteger64, 0x0014

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: ptagInstID

2.845 PidTagInternetArticleNumber

Canonical name: PidTagInternetArticleNumber

Property ID: 0x0E23

Data type: PtypInteger32, 0x0003

Area: MIME Properties

References: [\[MS-OXCFXICS\]](#)

Alternate names: PR_INTERNET_ARTICLE_NUMBER

2.846 PidTagInternetCodepage

Canonical name: PidTagInternetCodepage

Property ID: 0x3FDE

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_INTERNET_CPID, ptagInternetCpid

2.847 PidTagInternetMailOverrideFormat

Canonical name: PidTagInternetMailOverrideFormat

Description: Indicates the encoding method and HTML inclusion for attachments.

Property ID: 0x5902

Data type: PtypInteger32, 0x0003

Area: MIME Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_INETMAIL_OVERRIDE_FORMAT, ptagInetMailOverrideFormat

2.848 PidTagInternetMessageId

Canonical name: PidTagInternetMessageId

Description: Corresponds to the message-id field.

Property ID: 0x1035

Data type: PtypString, 0x001F

Area: MIME Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_INTERNET_MESSAGE_ID, PR_INTERNET_MESSAGE_ID_A, PR_INTERNET_MESSAGE_ID_W

2.849 PidTagInternetReferences

Canonical name: PidTagInternetReferences

Property ID: 0x1039

Data type: PtypString, 0x001F

Area: MIME Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_INTERNET_REFERENCES, PR_INTERNET_REFERENCES_A, PR_INTERNET_REFERENCES_W

2.850 PidTagInternetReturnPath

Canonical name: PidTagInternetReturnPath

Property ID: 0x1046

Data type: PtypString, 0x001F

Area: MIME Properties

References: [\[MS-OXCICAL\]](#)

Alternate names: PR_INTERNET_RETURN_PATH, PR_INTERNET_RETURN_PATH_A, PR_INTERNET_RETURN_PATH_W

2.851 PidTagIpmAppointmentEntryId

Canonical name: PidTagIpmAppointmentEntryId

Property ID: 0x36D0

Data type: PtypBinary, 0x0102

Area: Folder Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_IPM_APPOINTMENT_ENTRYID

2.852 PidTagIpmContactEntryId

Canonical name: PidTagIpmContactEntryId

Property ID: 0x36D1

Data type: PtypBinary, 0x0102

Area: Folder Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_IPM_CONTACT_ENTRYID

2.853 PidTagIpmDraftsEntryId

Canonical name: PidTagIpmDraftsEntryId

Property ID: 0x36D7

Data type: PtypBinary, 0x0102

Area: Folder Properties

References: [\[MS-OXOSFLD\]](#)

Alternate names: PR_IPM_DRAFTS_ENTRYID

2.854 PidTagIpmJournalEntryId

Canonical name: PidTagIpmJournalEntryId

Property ID: 0x36D2

Data type: PtypBinary, 0x0102

Area: Folder Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_IPM_JOURNAL_ENTRYID

2.855 PidTagIpmNoteEntryId

Canonical name: PidTagIpmNoteEntryId

Property ID: 0x36D3

Data type: PtypBinary, 0x0102

Area: Folder Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_IPM_NOTE_ENTRYID

2.856 PidTagIpmTaskEntryId

Canonical name: PidTagIpmTaskEntryId

Property ID: 0x36D4

Data type: PtypBinary, 0x0102

Area: Folder Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_IPM_TASK_ENTRYID

2.857 PidTagIsdnNumber

Canonical name: PidTagIsdnNumber

Description: Contains the mail user's ISDN-capable telephone number.

Property ID: 0x3A2D

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ISDN_NUMBER, PR_ISDN_NUMBER_A, PR_ISDN_NUMBER_W,
urn:schemas:contacts:internationalisdnnumber

2.858 PidTagItemTemporaryflags

Canonical name: PidTagItemTemporaryflags

Property ID: 0x1097

Data type: PtypInteger32, 0x0003

Area: General Message Properties

References: [\[MS-OXCFOLD\]](#)

Alternate names: PR_ITEM_TMPFLAGS

2.859 PidTagJunkAddRecipientsToSafeSendersList

Canonical name: PidTagJunkAddRecipientsToSafeSendersList

Description: Indicates whether mail recipients are to be added to the safe senders list or not.

Property ID: 0x6103

Data type: PtypInteger32, 0x0003

Area: Spam

References: [\[MS-OXCSPAM\]](#)

Alternate names: PR_JUNK_ADD_RECIPS_TO_SSL

2.860 PidTagJunkIncludeContacts

Canonical name: PidTagJunkIncludeContacts

Description: Indicates whether e-mail addresses of the contacts in the Contacts folder are treated in a special way with respect to the spam filter.

Property ID: 0x6100

Data type: PtypInteger32, 0x0003

Area: Spam

References: [\[MS-OXCSPAM\]](#)

Alternate names: PR_JUNK_INCLUDE_CONTACTS

2.861 PidTagJunkPermanentlyDelete

Canonical name: PidTagJunkPermanentlyDelete

Description: Indicates whether messages identified as spam can be permanently deleted.

Property ID: 0x6102

Data type: PtypInteger32, 0x0003

Area: Spam

References: [\[MS-OXCSPAM\]](#)

Alternate names: PR_JUNK_PERMANENTLY_DELETE

2.862 PidTagJunkPhishingEnableLinks

Canonical name: PidTagJunkPhishingEnableLinks

Description: Indicated whether the phishing stamp on a message is to be ignored.

Property ID: 0x6107

Data type: PtypBoolean, 0x000B

Area: Spam

References: [\[MS-OXCSPAM\]](#), [\[MS-OXPHISH\]](#)

Alternate names: PR_JUNK_PHISHING_ENABLE_LINKS

2.863 PidTagJunkThreshold

Canonical name: PidTagJunkThreshold

Description: Indicates how aggressively incoming mail SHOULD be sent to the Junk E-mail folder.

Property ID: 0x6101

Data type: PtypInteger32, 0x0003

Area: Spam

References: [\[MS-OXCSPAM\]](#)

Alternate names: PR_JUNK_THRESHOLD

2.864 PidTagKeyword

Canonical name: PidTagKeyword

Description: Contains a keyword that identifies the mail user to the mail user's system administrator.

Property ID: 0x3A0B

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_KEYWORD, PR_KEYWORD_A, PR_KEYWORD_W

2.865 PidTagLanguage

Canonical name: PidTagLanguage

Description: Contains a value that indicates the language in which the messaging user is writing messages.

Property ID: 0x3A0C

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LANGUAGE, PR_LANGUAGE_A, PR_LANGUAGE_W, urn:schemas:contacts:language

2.866 PidTagLastModificationTime

Canonical name: PidTagLastModificationTime

Description: Contains the time of the last modification to the object in UTC.

Property ID: 0x3008

Data type: PtypTime, 0x0040

Area: Message Time Properties Property set

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCSYNC\]](#), [\[MS-EXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LAST_MODIFICATION_TIME, ptagLastModificationTime, urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

2.867 PidTagLastModifierEntryId

Canonical name: PidTagLastModifierEntryId

Property ID: 0x3FFB

Data type: PtypBinary, 0x0102

Area: History Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_LAST_MODIFIER_ENTRYID, ptagLastModifierEntryId

2.868 PidTagLastModifierName

Canonical name: PidTagLastModifierName

Description: Contains the name of the last mail user to modify the object.

Property ID: 0x3FFA

Data type: PtypString, 0x001F

Area: History Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_LAST_MODIFIER_NAME, PR_LAST_MODIFIER_NAME_A, ptagLastModifierName, PR_LAST_MODIFIER_NAME_W

2.869 PidTagLastModifierSimpleDisplayName

Canonical name: PidTagLastModifierSimpleDisplayName

Property ID: 0x4039

Data type: PtypString, 0x001F

Area: TransportEnvelope

References: [\[MS-OXTNEF\]](#)

Alternate names: ptagLastModifierSimpleDispName

2.870 PidTagLastVerbExecuted

Canonical name: PidTagLastVerbExecuted

Description: Specifies the last verb executed for the message item to which it is related.

Property ID: 0x1081

Data type: PtypInteger32, 0x0003

Area: History Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_LAST_VERB_EXECUTED, ptagLastVerbExecuted

2.871 PidTagLastVerbExecutionTime

Canonical name: PidTagLastVerbExecutionTime

Description: Contains the date and time, in UTC, during which the operation represented in PidTagLastVerbExecuted took place.

Property ID: 0x1082

Data type: PtypTime, 0x0040

Area: History Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_LAST_VERB_EXECUTION_TIME, ptagLastVerbExecutionTime

2.872 PidTagListHelp

Canonical name: PidTagListHelp

Property ID: 0x1043

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_HELP, PR_LIST_HELP_A, PR_LIST_HELP_W

2.873 PidTagListSubscribe

Canonical name: PidTagListSubscribe

Property ID: 0x1044

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_SUBSCRIBE, PR_LIST_SUBSCRIBE_A, PR_LIST_SUBSCRIBE_W

2.874 PidTagListUnsubscribe

Canonical name: PidTagListUnsubscribe

Property ID: 0x1045

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_UNSUBSCRIBE, PR_LIST_UNSUBSCRIBE_A, PR_LIST_UNSUBSCRIBE_W

2.875 PidTagLocalCommitTime

Canonical name: PidTagLocalCommitTime

Description: Contains the time a RopCreateMessage was processed.

Property ID: 0x6709

Data type: PtypTime, 0x0040

Area: Server

References: [\[MS-OXCMSG\]](#)

Alternate names: PR_LOCAL_COMMIT_TIME, ptagLocalCommitTime

2.876 PidTagLocaleId

Canonical name: PidTagLocaleId

Description: Contains the logon object LocaleID.

Property ID: 0x66A1

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXCSTOR\]](#)

Alternate names: PR_LOCALE_ID, ptagLocaleId

2.877 PidTagLocality

Canonical name: PidTagLocality

Description: Contains the name of the mail user's locality, such as the town or city.

Property ID: 0x3A27

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LOCALITY, PR_LOCALITY_A, PR_LOCALITY_W, PR_BUSINESS_ADDRESS_LOCALITY, PR_BUSINESS_ADDRESS_LOCALITY_A, PR_BUSINESS_ADDRESS_LOCALITY_W, urn:schemas:contacts:mailingcity

2.878 PidTagLocation

Canonical name: PidTagLocation

Description: Contains the location of the mail user in a format that is useful to the mail user's organization.

Property ID: 0x3A0D

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LOCATION, PR_LOCATION_A, PR_LOCATION_W, urn:schemas:contacts:location

2.879 PidTagMailboxOwnerEntryId

Canonical name: PidTagMailboxOwnerEntryId

Description: The EntryID in the Global Address List of the owner of the mailbox.

Property ID: 0x661B

Data type: PtypBinary, 0x0102

Area: Message Store Properties

References: [\[MS-OXCSTOR\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_MAILBOX_OWNER_ENTRYID, ptagMailboxOwnerEntryId

2.880 PidTagMailboxOwnerName

Canonical name: PidTagMailboxOwnerName

Description: Display name of the owner of the mailbox.

Property ID: 0x661C

Data type: PtypString, 0x001F

Area: Message Store Properties

References: [\[MS-OXCSTOR\]](#), [\[MS-OXOCAL\]](#)

Alternate names: PR_MAILBOX_OWNER_NAME, PR_MAILBOX_OWNER_NAME_A, ptagMailboxOwnerName, PR_MAILBOX_OWNER_NAME_W

2.881 PidTagManagerName

Canonical name: PidTagManagerName

Description: Contains the name of the mail user's manager.

Property ID: 0x3A4E

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MANAGER_NAME, PR_MANAGER_NAME_A, PR_MANAGER_NAME_W, urn:schemas:contacts:manager

2.882 PidTagMappingSignature

Canonical name: PidTagMappingSignature

Description: A 16-byte constant that is present on all Address Book objects, but is not present on objects in an offline address book.

Property ID: 0x0FF8

Data type: PtypBinary, 0x0102

Area: Miscellaneous Properties

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_MAPPING_SIGNATURE, ptagMappingSignature

2.883 PidTagMaximumSubmitMessageSize

Canonical name: PidTagMaximumSubmitMessageSize

Description: Maximum size, in kilobytes, of a message a user is allowed to submit for transmission to another user.

Property ID: 0x666D

Data type: PtypInteger32, 0x0003

Area: Message Store Properties

References: [\[MS-OXCSTOR\]](#)

Alternate names: PR_MAX_SUBMIT_MESSAGE_SIZE

2.884 PidTagMemberId

Canonical name: PidTagMemberId

Description: Contains a unique identifier that the messaging server generates for each user.

Property ID: 0x6671

Data type: PtypInteger64, 0x0014

Area: Access Control Properties

References: [\[MS-OXCPERM\]](#)

Alternate names: PR_MEMBER_ID, ptagMemberId

2.885 PidTagMemberName

Canonical name: PidTagMemberName

Description: Contains the user-readable name of the user.

Property ID: 0x6672

Data type: PtypString, 0x001F

Area: Access Control Properties

References: [\[MS-OXCPERM\]](#)

Alternate names: PR_MEMBER_NAME, PR_MEMBER_NAME_A, ptagMemberName, PR_MEMBER_NAME_W

2.886 PidTagMemberRights

Canonical name: PidTagMemberRights

Description: Contains the permissions for the specified user.

Property ID: 0x6673

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCPERM\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_MEMBER_RIGHTS, ptagMemberRights

2.887 PidTagMessageAttachments

Canonical name: PidTagMessageAttachments

Description: Identifies all attachments to the current message.

Property ID: 0x0E13

Data type: PtypComObject, 0x000D

Area: Message Attachment Properties

References: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#)

Alternate names: PR_MESSAGE_ATTACHMENTS, ptagMessageAttachments

2.888 PidTagMessageCcMe

Canonical name: PidTagMessageCcMe

Descriptor: Indicates that the receiving mailbox owner is a carbon copy (Cc) recipient of this email message.

Property ID: 0x0058

Data type: PtypBoolean, 0x000B

Area: General Message Properties

References: [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_CC_ME, ptagMessageCcMe

2.889 PidTagMessageClass

Canonical name: PidTagMessageClass

Description: Denotes the specific type of the Message object.

Property ID: 0x001A

Data type: PtypString, 0x001F

Area: Common Property set

References: [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MESSAGE_CLASS, PR_MESSAGE_CLASS_A, ptagMessageClass, PR_MESSAGE_CLASS_W, <http://schemas.microsoft.com/exchange/outlookmessageclass><http://schemas.microsoft.com/exchange/outlookmessageclass>

2.890 PidTagMessageCodepage

Canonical name: PidTagMessageCodepage

Description: Specifies the code page used to encode the non-Unicode string properties on this Message object.

Property ID: 0x3FFD

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-OXTNEF\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXPFOAB\]](#),

Alternate names: PR_MESSAGE_CODEPAGE

2.891 PidTagMessageDeliveryTime

Canonical name: PidTagMessageDeliveryTime

Description: Contains the posting date of the item or entry.

Property ID: 0x0E06

Data type: PtypTime, 0x0040

Area: Message Time Properties Property set

References: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORSS\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_MESSAGE_DELIVERY_TIME, urn:schemas:httpmail:datereceived

2.892 PidTagMessageEditorFormat

Canonical name: PidTagMessageEditorFormat

Property ID: 0x5909

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MSG_EDITOR_FORMAT, ptagMsgEditorFormat

2.893 PidTagMessageFlags

Canonical name: PidTagMessageFlags

Description: Specifies the status of the Message object.

Property ID: 0x0E07

Data type: PtypInteger32, 0x0003

Area: General Message Properties

References: [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_MESSAGE_FLAGS, ptagMessageFlags

2.894 PidTagMessageHandlingSystemCommonName

Canonical name: PidTagMessageHandlingSystemCommonName

Description: Contains the common name of a messaging user for use in a message header.

Property ID: 0x3A0F

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MHS_COMMON_NAME, PR_MHS_COMMON_NAME_A, PR_MHS_COMMON_NAME_W, urn:schemas:contacts:dn

2.895 PidTagMessageLocaleId

Canonical name: PidTagMessageLocaleId

Description: Contains the Windows LCID of the end-user who created this message.

Property ID: 0x3FF1

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_LOCALE_ID

2.896 PidTagMessageRecipientMe

Canonical name: PidTagMessageRecipientMe

Description: Indicates that the receiving mailbox owner is a primary or a carbon copy (Cc) recipient of this email message.

Property ID: 0x0059

Data type: PtypBoolean, 0x000B

Area: General Message Properties

References: [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_RECIP_ME, ptagMessageRecipMe

2.897 PidTagMessageRecipients

Canonical name: PidTagMessageRecipients

Description: Identifies all recipients of the current message.

Property ID: 0x0E12

Data type: PtypComObject, 0x000D

Area: Address Properties

References: [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_RECIPIENTS, ptagMessageRecipients

2.898 PidTagMessageSize

Canonical name: PidTagMessageSize

Description: Contains the size in bytes consumed by the Message object on the server.

Property ID: 0x0E08

Data type: PtypInteger32, 0x0003

Area: General Message Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_MESSAGE_SIZE, ptagMessageSize

2.899 PidTagMessageSizeExtended

Canonical name: PidTagMessageSizeExtended

Description: Specifies the 64-bit version of the PidTagNormalMessageSize property.

Property ID: 0x0E08

Data type: PtypInteger64, 0x0014

Area: General Message Properties

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCSTOR\]](#)

Alternate names: PR_MESSAGE_SIZE_EXTENDED, ptagMessageSizeExtended

2.900 PidTagMessageStatus

Canonical name: PidTagMessageStatus

Description: Specifies the status of a message in a contents table.

Property ID: 0x0E17

Data type: PtypInteger32, 0x0003

Area: General Message Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_MSG_STATUS, ptagMsgStatus

2.901 PidTagMessageSubmissionId

Canonical name: PidTagMessageSubmissionId

Property ID: 0x0047

Data type: PtypBinary, 0x0102

Area: Email

References: [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_SUBMISSION_ID, ptagMessageSubmissionId

2.902 PidTagMessageToMe

Canonical name: PidTagMessageToMe

Description: Indicates that the receiving mailbox owner is one of the primary recipients of this email message.

Property ID: 0x0057

Data type: PtypBoolean, 0x000B

Area: General Message Properties

References: [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_TO_ME, ptagMessageToMe

2.903 PidTagMid

Canonical name: PidTagMid

Description: Contains a value that contains the MID of the message currently being synchronized.

Property ID: 0x674A

Data type: PtypInteger64, 0x0014

Area: ID Properties Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: ptagMID, <http://schemas.microsoft.com/exchange/mid>

2.904 PidTagMiddleName

Canonical name: PidTagMiddleName

Description: Specifies the middle name(s) of the contact.

Property ID: 0x3A44

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MIDDLE_NAME, PR_MIDDLE_NAME_A, PR_MIDDLE_NAME_W, urn:schemas:contacts:middlename

2.905 PidTagMimeSkeleton

Canonical name: PidTagMimeSkeleton

Property ID: 0x0470

Data type: PtypBinary, 0x0102

Area: MIME properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagMimeSkeleton

2.906 PidTagMobileTelephoneNumber

Canonical name: PidTagMobileTelephoneNumber

Description: Contains the mail user's cellular telephone number.

Property ID: 0x3A1C

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#), [\[MS-EXOCNTC\]](#), [\[MS-EXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MOBILE_TELEPHONE_NUMBER, PR_MOBILE_TELEPHONE_NUMBER_A, PR_MOBILE_TELEPHONE_NUMBER_W, urn:schemas:contacts:mobile

2.907 PidTagNativeBody

Canonical name: PidTagNativeBody

Description: Indicates the best available format for storing the message body.

Property ID: 0x1016

Data type: PtypInteger32, 0x0003

Area: BestBody

References: [\[MS-OXBBODY\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_NATIVE_BODY_INFO, ptagNativeBodyInfo

2.908 PidTagNewAttach

Canonical name: PidTagNewAttach

Property ID: 0x4000

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagNewAttach

2.909 PidTagNewFXFolder

Canonical name: PidTagNewFXFolder

Description: Contains a value that provides information about alternative replicas for a public folder in context.

Property ID: 0x4011

Data type: PtypBinary, 0x0102

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagNewFXFolder

2.910 PidTagNextSendAcct

Canonical name: PidTagNextSendAcct

Description: Specifies the server that a client is currently attempting to use to send mail.

Property ID: 0x0E29

Data type: PtypString, 0x001F

Area:

References: [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_NEXT_SEND_ACCT

2.911 PidTagNickname

Canonical name: PidTagNickname

Description: Contains the mail user's nickname.

Property ID: 0x3A4F

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_NICKNAME, PR_NICKNAME_A, PR_NICKNAME_W, urn:schemas:contacts:nickname

2.912 PidTagNormalizedSubject

Canonical name: PidTagNormalizedSubject

Description: Contains the normalized subject of the message.

Property ID: 0x0E1D

Data type: PtypString, 0x001F

Area: Email Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_NORMALIZED_SUBJECT, PR_NORMALIZED_SUBJECT_A, ptagNormalizedSubject, PR_NORMALIZED_SUBJECT_W, urn:schemas:httpmail:normalizedsubject

2.913 PidTagNormalMessageSize

Canonical name: PidTagNormalMessageSize

Property ID: 0x66B3

Data type: PtypInteger32, 0x0003

Area: Server

References: [\[MS-OXCFOLD\]](#), [\[MS-XWDFOLD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_NORMAL_MESSAGE_SIZE, <http://schemas.microsoft.com/exchange/foldersize>

2.914 PidTagObjectType

Canonical name: PidTagObjectType

Description: Indicates the type of server object.

Property ID: 0x0FFE

Data type: PtypInteger32, 0x0003

Area: Common

References: [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_OBJECT_TYPE, ptagObjectType

2.915 PidTagOfficeLocation

Canonical name: PidTagOfficeLocation

Description: Contains the mail user's office location.

Property ID: 0x3A19

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OFFICE_LOCATION, PR_OFFICE_LOCATION_A, PR_OFFICE_LOCATION_W, urn:schemas:contacts:roomnumber

2.916 PidTagOfflineAddressBookCompressedSize

Canonical name: PidTagOfflineAddressBookCompressedSize

Description: Contains the compressed size of the offline address book.

Property ID: 0x6809

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_OAB_COMPRESSED_SIZE

2.917 PidTagOfflineAddressBookContainerGuid

Canonical name: PidTagOfflineAddressBookContainerGuid

Description: A string formatted GUID that represents the address list container object.

Property ID: 0x6802

Data type: PtypString, 0x001F

Area: Offline Address Book Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_CONTAINER_GUID, PR_OAB_CONTAINER_GUID_W

2.918 PidTagOfflineAddressBookDistinguishedName

Canonical name: PidTagOfflineAddressBookDistinguishedName

Description: The addresslist-X500-dn of the address list container object.

Property ID: 0x6804

Data type: PtypString, 0x001F

Area: Offline Address Book Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_DN, PR_OAB_DN_W

2.919 PidTagOfflineAddressBookFileSize

Canonical name: PidTagOfflineAddressBookFileSize

Description: Contains the uncompressed size of the offline address book.

Property ID: 0x680A

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_OAB_FILE_SIZE

2.920 PidTagOfflineAddressBookFileType

Canonical name: PidTagOfflineAddressBookFileType

Description: Contains the file type of the offline address book.

Property ID: 0x6808

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_OAB_FILETYPE

2.921 PidTagOfflineAddressBookLanguageId

Canonical name: PidTagOfflineAddressBookLanguageId

Description: Contains the language id used in the offline address book.

Property ID: 0x6807

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_OAB_LANGID

2.922 PidTagOfflineAddressBookMessageClass

Canonical name: PidTagOfflineAddressBookMessageClass

Description: Contains the message class for full OAB messages.

Property ID: 0x6803

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

References: [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_MESSAGE_CLASS

2.923 PidTagOfflineAddressBookName

Canonical name: PidTagOfflineAddressBookName

Description: Contains the display name of the address list.

Property ID: 0x6800

Data type: PtypString, 0x001F

Area: Offline Address Book Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_NAME, PR_OAB_NAME_W

2.924 PidTagOfflineAddressBookSequence

Canonical name: PidTagOfflineAddressBookSequence

Description: The sequence number of the OAB.

Property ID: 0x6801

Data type: PtypInteger32, 0x0003

Area: Offline Address Book Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_OAB_SEQUENCE

2.925 PidTagOfflineAddressBookShaHash

Canonical name: PidTagOfflineAddressBookShaHash

Description: Contains the hash function used to encode objects in the offline address book.

Property ID: 0x6806

Data type: PtypBinary, 0x0102

Area: Offline Address Book Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_OAB_SHA_HASH

2.926 PidTagOfflineAddressBookTruncatedProperties

Canonical name: PidTagOfflineAddressBookTruncatedProperties

Description: Contains a list of the property tags that have been truncated or limited by the server.

Property ID: 0x6805

Data type: PtypMultipleInteger32, 0x1003

Area: Offline Address Book Properties

References: [\[MS-OXOAB\]](#)

Alternate names: PR_OAB_TRUNCATED_PROPS

2.927 PidTagOrdinalMost

Canonical name: PidTagOrdinalMost

Description: Contains a positive number whose negative is less than or equal to the value of PidLidTaskOrdinal of all Task objects in the folder.

Property ID: 0x36E2

Data type: PtypInteger32, 0x0003

Area: Tasks

References: [\[MS-OXOTASK\]](#)

Alternate names: PR_ORDINAL_MOST

2.928 PidTagOrganizationalIdNumber

Canonical name: PidTagOrganizationalIdNumber

Description: Contains an identifier for the mail user used within the mail user's organization.

Property ID: 0x3A10

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ORGANIZATIONAL_ID_NUMBER, PR_ORGANIZATIONAL_ID_NUMBER_A, PR_ORGANIZATIONAL_ID_NUMBER_W, urn:schemas:contacts:employeenumber

2.929 PidTagOriginalAuthorName

Canonical name: PidTagOriginalAuthorName

Property ID: 0x004D

Data type: PtypString, 0x001F

Area: Email

References: [\[MS-OXCICAL\]](#)

Alternate names: PR_ORIGINAL_AUTHOR_NAME, PR_ORIGINAL_AUTHOR_NAME_A, ptagOriginalAuthorName, PR_ORIGINAL_AUTHOR_NAME_W

2.930 PidTagOriginalDeliveryTime

Canonical name: PidTagOriginalDeliveryTime

Description: Contains the delivery time from the original message.

Property ID: 0x0055

Data type: PtypTime, 0x0040

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_DELIVERY_TIME, ptagOriginalDeliveryTime

2.931 PidTagOriginalDisplayBcc

Canonical name: PidTagOriginalDisplayBcc

Description: Contains the value of PidTagDisplayBcc from the original message.

Property ID: 0x0072

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_DISPLAY_BCC, PR_ORIGINAL_DISPLAY_BCC_A, ptagOriginalDisplayBcc, PR_ORIGINAL_DISPLAY_BCC_W, <http://schemas.microsoft.com/exchange/originaldisplaybcc>

2.932 PidTagOriginalDisplayCc

Canonical name: PidTagOriginalDisplayCc

Description: Contains the value of PidTagDisplayCc from the original message.

Property ID: 0x0073

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_DISPLAY_CC, PR_ORIGINAL_DISPLAY_CC_A, ptagOriginalDisplayCc, PR_ORIGINAL_DISPLAY_CC_W, <http://schemas.microsoft.com/exchange/originaldisplaycc>, http://schemas.microsoft.com/mapi/original_display_cc

2.933 PidTagOriginalDisplayName

Canonical name: PidTagOriginalDisplayName

Description: Contains a display name.

Property ID: 0x3A13

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_ORIGINAL_DISPLAY_NAME, PR_ORIGINAL_DISPLAY_NAME_A, ptagOriginalDisplayName, PR_ORIGINAL_DISPLAY_NAME_W

2.934 PidTagOriginalDisplayTo

Canonical name: PidTagOriginalDisplayTo

Description: Contains the value of PidTagDisplayTo from the original message.

Property ID: 0x0074

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_DISPLAY_TO, PR_ORIGINAL_DISPLAY_TO_A, ptagOriginalDisplayTo, PR_ORIGINAL_DISPLAY_TO_W, <http://schemas.microsoft.com/exchange/originaldisplayto>, http://schemas.microsoft.com/mapi/original_display_to

2.935 PidTagOriginalEntryId

Canonical name: PidTagOriginalEntryId

Description: Contains the original entry ID of an object.

Property ID: 0x3A12

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXCSYNC\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_ORIGINAL_ENTRYID, ptagOriginalEntryId

2.936 PidTagOriginalMessageClass

Canonical name: PidTagOriginalMessageClass

Property ID: 0x004B

Data type: PtypString, 0x001F

Area: Secure Messaging Properties

References: [\[MS-OXTNEF\]](#)

Alternate names: PR_ORIG_MESSAGE_CLASS, PR_ORIG_MESSAGE_CLASS_A, PR_ORIG_MESSAGE_CLASS_W

2.937 PidTagOriginalMessageId

Canonical name: PidTagOriginalMessageId

Property ID: 0x1046

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagOriginalInternetMessageID, OriginalMessageId

2.938 PidTagOriginalSearchKey

Canonical name: PidTagOriginalSearchKey

Description: Contains a search key.

Property ID: 0x3A14

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXOABK\]](#)

Alternate names: PR_ORIGINAL_SEARCH_KEY, ptagOriginalSearchKey

2.939 PidTagOriginalSenderAddressType

Canonical name: PidTagOriginalSenderAddressType

Description: Contains the value of the original message sender's PidTagSenderAddressType.

Property ID: 0x0066

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENDER_ADDRTYPE, PR_ORIGINAL_SENDER_ADDRTYPE_A, ptagOriginalSenderAddrType, PR_ORIGINAL_SENDER_ADDRTYPE_W

2.940 PidTagOriginalSenderEmailAddress

Canonical name: PidTagOriginalSenderEmailAddress

Description: Contains the value of the original message sender's PidTagSenderEmailAddress property.

Property ID: 0x0067

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENDER_EMAIL_ADDRESS,
PR_ORIGINAL_SENDER_EMAIL_ADDRESS_A, PR_ORIGINAL_SENDER_EMAIL_ADDRESS_W

2.941 PidTagOriginalSenderId

Canonical name: PidTagOriginalSenderId

Description: Contains an address book Entry ID that is set on delivery report messages, to the value of the PidTagSenderId property from the original message.

Property ID: 0x005B

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENDER_ENTRYID, ptagOriginalSenderId

2.942 PidTagOriginalSenderName

Canonical name: PidTagOriginalSenderName

Description: Contains the value of the original message sender's PidTagSenderName property, and is set on delivery report messages.

Property ID: 0x005A

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENDER_NAME, PR_ORIGINAL_SENDER_NAME_A,
ptagOriginalSenderName, PR_ORIGINAL_SENDER_NAME_W,
<http://schemas.microsoft.com/exchange/originalsendername>

2.943 PidTagOriginalSenderSearchKey

Canonical name: PidTagOriginalSenderSearchKey

Description: Contains an address book search key set on the original email message.

Property ID: 0x005C

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENDER_SEARCH_KEY, ptagOriginalSenderSearchKey

2.944 PidTagOriginalSensitivity

Canonical name: PidTagOriginalSensitivity

Description: Contains the sensitivity value of the original email message.

Property ID: 0x002E

Data type: PtypInteger32, 0x0003

Area: General Message Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENSITIVITY, ptagOriginalSensitivity

2.945 PidTagOriginalSentRepresentingAddressType

Canonical name: PidTagOriginalSentRepresentingAddressType

Description: Contains the address type of the end user who is represented by the original email message sender.

Property ID: 0x0068

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE, PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_A, ptagOriginalSentRepresentingAddrType, PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_W

2.946 PidTagOriginalSentRepresentingEmailAddress

Canonical name: PidTagOriginalSentRepresentingEmailAddress

Description: Contains the email address of the end user who is represented by the original email message sender.

Property ID: 0x0069

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS, PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_A, PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_W

2.947 PidTagOriginalSentRepresentingEntryId

Canonical name: PidTagOriginalSentRepresentingEntryId

Description: Identifies an address book EntryID that contains the entry identifier of the end user who is represented by the original message sender.

Property ID: 0x005E

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ENTRYID, ptagOriginalSentRepresentingEntryId

2.948 PidTagOriginalSentRepresentingName

Canonical name: PidTagOriginalSentRepresentingName

Description: Contains the display name of the end user who is represented by the original email message sender.

Property ID: 0x005D

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_NAME, PR_ORIGINAL_SENT_REPRESENTING_NAME_A, ptagOriginalSentRepresentingName, PR_ORIGINAL_SENT_REPRESENTING_NAME_W

2.949 PidTagOriginalSentRepresentingSearchKey

Canonical name: PidTagOriginalSentRepresentingSearchKey

Description: Identifies an address book search key that contains the SearchKey of the end user who is represented by the original message sender.

Property ID: 0x005F

Data type: PtypBinary, 0x0102

Area: General Message Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_SEARCH_KEY, ptagOriginalSentRepresentingSearchKey

2.950 PidTagOriginalSubject

Canonical name: PidTagOriginalSubject

Description: Specifies the subject of the original message.

Property ID: 0x0049

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXCSYNC\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SUBJECT, PR_ORIGINAL_SUBJECT_A, ptagOriginalSubject, PR_ORIGINAL_SUBJECT_W, <http://schemas.microsoft.com/exchange/originalsubject>, http://schemas.microsoft.com/mapi/original_subject

2.951 PidTagOriginalSubmitTime

Canonical name: PidTagOriginalSubmitTime

Description: Specifies the original email message's submission date and time.

Property ID: 0x004E

Data type: PtypTime, 0x0040

Area: General Message Properties Property set

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINAL_SUBMIT_TIME, ptagOriginalSubmitTime, <http://schemas.microsoft.com/exchange/originaldate>, http://schemas.microsoft.com/mapi/original_submit_time

2.952 PidTagOriginatorDeliveryReportRequested

Canonical name: PidTagOriginatorDeliveryReportRequested

Description: Indicates whether an email sender requests an email delivery receipt from the messaging system

Property ID: 0x0023

Data type: PtypBoolean, 0x000B

Area: MIME Properties Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ORIGINATOR_DELIVERY_REPORT_REQUESTED, <http://schemas.microsoft.com/exchange/deliveryreportrequested>

2.953 PidTagOriginatorNonDeliveryReportRequested

Canonical name: PidTagOriginatorNonDeliveryReportRequested

Description: Specifies whether an email sender requests suppression of nondelivery receipts.

Property ID: 0x0C08

Data type: PtypBoolean, 0x000B

Area: MIME Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_ORIGINATOR_NON_DELIVERY_REPORT_REQUESTED

2.954 PidTagOtherAddressCity

Canonical name: PidTagOtherAddressCity

Description: Contains the name of the mail user's other locality, such as the town or city.

Property ID: 0x3A5F

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_CITY, PR_OTHER_ADDRESS_CITY_A, PR_OTHER_ADDRESS_CITY_W, urn:schemas:contacts:othercity

2.955 PidTagOtherAddressCountry

Canonical name: PidTagOtherAddressCountry

Description: Contains the name of the mail user's other country/region.

Property ID: 0x3A60

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_OTHER_ADDRESS_COUNTRY, PR_OTHER_ADDRESS_COUNTRY_A, PR_OTHER_ADDRESS_COUNTRY_W, urn:schemas:contacts:othercountry

2.956 PidTagOtherAddressPostalCode

Canonical name: PidTagOtherAddressPostalCode

Description: Contains the postal code for the mail user's other postal address.

Property ID: 0x3A61

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_POSTAL_CODE, PR_OTHER_ADDRESS_POSTAL_CODE_A, PR_OTHER_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:otherpostalcode

2.957 PidTagOtherAddressPostOfficeBox

Canonical name: PidTagOtherAddressPostOfficeBox

Description: Contains the number or identifier of the mail user's other post office box.

Property ID: 0x3A64

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_POST_OFFICE_BOX, PR_OTHER_ADDRESS_POST_OFFICE_BOX_A, PR_OTHER_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:otherpostofficebox

2.958 PidTagOtherAddressStateOrProvince

Canonical name: PidTagOtherAddressStateOrProvince

Description: Contains the name of the mail user's other state or province.

Property ID: 0x3A62

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_STATE_OR_PROVINCE, PR_OTHER_ADDRESS_STATE_OR_PROVINCE_A, PR_OTHER_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:otherstate

2.959 PidTagOtherAddressStreet

Canonical name: PidTagOtherAddressStreet

Description: Contains the mail user's other street address.

Property ID: 0x3A63

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_STREET, PR_OTHER_ADDRESS_STREET_A, PR_OTHER_ADDRESS_STREET_W, urn:schemas:contacts:otherstreet

2.960 PidTagOtherTelephoneNumber

Canonical name: PidTagOtherTelephoneNumber

Description: Contains an alternate telephone number for the mail user.

Property ID: 0x3A1F

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_TELEPHONE_NUMBER, PR_OTHER_TELEPHONE_NUMBER_A, PR_OTHER_TELEPHONE_NUMBER_W, urn:schemas:contacts:otherTelephone

2.961 PidTagOutOfOfficeState

Canonical name: PidTagOutOfOfficeState

Description: Indicates whether the user is OOF.

Property ID: 0x661D

Data type: PtypBoolean, 0x000B

Area: Message Store Properties

References: [\[MS-OXCSTOR\]](#)

Alternate names: PR_OOF_STATE, ptagOOFState

2.962 PidTagOwnerAppointmentId

Canonical name: PidTagOwnerAppointmentId

Description: Specifies a quasi-unique value among all Calendar objects in a user's mailbox.

Property ID: 0x0062

Data type: PtypInteger32, 0x0003

Area: Appointment Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: PR_OWNER_APPT_ID, http://schemas.microsoft.com/mapi/owner_appt_id

2.963 PidTagPagerTelephoneNumber

Canonical name: PidTagPagerTelephoneNumber

Description: Contains the mail user's pager telephone number.

Property ID: 0x3A21

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PAGER_TELEPHONE_NUMBER, PR_PAGER_TELEPHONE_NUMBER_A, PR_PAGER_TELEPHONE_NUMBER_W, urn:schemas:contacts:pager

2.964 PidTagParentEntryId

Canonical name: PidTagParentEntryId

Description: Contains the entry ID of the folder where messages reside.

Property ID: 0x0E09

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-OXCDATA\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_PARENT_ENTRYID, ptagParentEntryId

2.965 PidTagParentFolderId

Canonical name: PidTagParentFolderId

Description: Contains a value that contains the FID that identifies the parent folder of the messaging object being synchronized.

Property ID: 0x6749

Data type: PtypInteger64, 0x0014

Area: ID Properties

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagParentFID

2.966 PidTagParentKey

Canonical name: PidTagParentKey

Description: Contains the search key that is used to correlate the original message and the reports about the original message.

Property ID: 0x0025

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_PARENT_KEY, ptagParentKey

2.967 PidTagParentSourceKey

Canonical name: PidTagParentSourceKey

Description: Contains a value on a folder that contains the PidTagSourceKey of the parent folder.

Property ID: 0x65E1

Data type: PtypBinary, 0x0102

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_PARENT_SOURCE_KEY

2.968 PidTagPersonalHomePage

Canonical name: PidTagPersonalHomePage

Description: Contains the Web address (URL) of the mail user's personal home page.

Property ID: 0x3A50

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PERSONAL_HOME_PAGE, PR_PERSONAL_HOME_PAGE_A, PR_PERSONAL_HOME_PAGE_W, urn:schemas:contacts:personalHomePage

2.969 PidTagPolicyTag

Canonical name: PidTagPolicyTag

Property ID: 0x3019

Data type: PtypBinary, 0x0102

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_POLICY_TAG, ptagPolicyTag

2.970 PidTagPostalAddress

Canonical name: PidTagPostalAddress

Description: Contains the mail user's postal address.

Property ID: 0x3A15

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POSTAL_ADDRESS, PR_POSTAL_ADDRESS_A, PR_POSTAL_ADDRESS_W, urn:schemas:contacts:mailingpostaladdress

2.971 PidTagPostalCode

Canonical name: PidTagPostalCode

Description: Contains the postal code for the mail user's postal address.

Property ID: 0x3A2A

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POSTAL_CODE, PR_POSTAL_CODE_A, PR_POSTAL_CODE_W, PR_BUSINESS_ADDRESS_POSTAL_CODE, PR_BUSINESS_ADDRESS_POSTAL_CODE_A, PR_BUSINESS_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:mailingpostalcode

2.972 PidTagPostOfficeBox

Canonical name: PidTagPostOfficeBox

Description: Contains the number or identifier of the mail user's post office box.

Property ID: 0x3A2B

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POST_OFFICE_BOX, PR_POST_OFFICE_BOX_A, PR_POST_OFFICE_BOX_W, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_A, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:mailingpostofficebox

2.973 PidTagPredecessorChangeList

Canonical name: PidTagPredecessorChangeList

Description: Contains a value that contains a serialized representation of a PredecessorChangeList structure.

Property ID: 0x65E3

Data type: PtypBinary, 0x0102

Area: Sync

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_PREDECESSOR_CHANGE_LIST

2.974 PidTagPrimaryFaxNumber

Canonical name: PidTagPrimaryFaxNumber

Description: Contains the telephone number of the mail user's primary fax machine.

Property ID: 0x3A23

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PRIMARY_FAX_NUMBER, PR_PRIMARY_FAX_NUMBER_A, PR_PRIMARY_FAX_NUMBER_W, urn:schemas:contacts:otherfax

2.975 PidTagPrimarySendAccount

Canonical name: PidTagPrimarySendAccount

Description: Specifies the first server that a client SHOULD attempt to send the mail with.

Property ID: 0x0E28

Data type: PtypString, 0x001F

Area: MapiNonTransmittable

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_PRIMARY_SEND_ACCT

2.976 PidTagPrimarySmtpAddress

Canonical name: PidTagPrimarySmtpAddress

Property ID: 0x39FE

Data type: PtypString, 0x001F

Area: MapiAddressBook

References: [\[MS-OXCFXICS\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: ptagPrimarySMTPAddress

2.977 PidTagPrimaryTelephoneNumber

Canonical name: PidTagPrimaryTelephoneNumber

Description: Contains the mail user's primary telephone number.

Property ID: 0x3A1A

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-NSPI\]](#)

Alternate names: PR_PRIMARY_TELEPHONE_NUMBER, PR_PRIMARY_TELEPHONE_NUMBER_A, PR_PRIMARY_TELEPHONE_NUMBER_W

2.978 PidTagPriority

Canonical name: PidTagPriority

Description: Indicates the client's request for the priority at which the message is to be sent by the messaging system.

Property ID: 0x0026

Data type: PtypInteger32, 0x0003

Area: Email Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

2.979 PidTagProcessed

Canonical name: PidTagProcessed

Description: Indicates whether a client has already processed a received task communication.

Property ID: 0x7D01

Data type: PtypBoolean, 0x000B

Area: Calendar

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: PR_PROCESSED

2.980 PidTagProfession

Canonical name: PidTagProfession

Description: Contains the name of the mail user's line of business.

Property ID: 0x3A46

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PROFESSION, PR_PROFESSION_A, PR_PROFESSION_W, urn:schemas:contacts:profession

2.981 PidTagProhibitReceiveQuota

Canonical name: PidTagProhibitReceiveQuota

Description: Maximum size, in kilobytes, a user is allowed to accumulate in their mailbox, before no further mail will be delivered.

Property ID: 0x666A

Data type: PtypInteger32, 0x0003

Area: Exchange Administrative

References: [\[MS-OXCSTOR\]](#)

Alternate names: PR_PROHIBIT_RECEIVE_QUOTA, ptagProhibitReceiveQuota

2.982 PidTagProhibitSendQuota

Canonical name: PidTagProhibitSendQuota

Description: Maximum size, in kilobytes, a user is allowed to accumulate in their mailbox, before the user can no longer submit any more mail.

Property ID: 0x666E

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

References: [\[MS-OXCSTOR\]](#)

Alternate names: PR_PROHIBIT_SEND_QUOTA, ptagProhibitSendQuota

2.983 PidTagProviderSubmitTime

Canonical name: PidTagProviderSubmitTime

Property ID: 0x0048

Data type: PtypTime, 0x0040

Area: Email

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_PROVIDER_SUBMIT_TIME

2.984 PidTagPublicFolderAdministrativeDescription

Canonical name: PidTagPublicFolderAdministrativeDescription

Property ID: 0x671C

Data type: PtypString, 0x001F

Area: Folder Properties

References: [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

Alternate names: http://schemas.microsoft.com/exchange/adminfolderdescription

2.985 PidTagPublicFolderProxy

Canonical name: PidTagPublicFolderProxy

Property ID: 0x671D

Data type: PtypBinary, 0x0102

Area: Folder Properties

References: [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/folderproxy>

2.986 PidTagPurportedSenderDomain

Canonical name: PidTagPurportedSenderDomain

Property ID: 0x4083

Data type: PtypString, 0x001F

Area: TransportEnvelope

References: [\[MS-OXCMAIL\]](#)

Alternate names: PR_PURPORTED_SENDER_DOMAIN

2.987 PidTagRadioTelephoneNumber

Canonical name: PidTagRadioTelephoneNumber

Description: Contains the mail user's radio telephone number.

Property ID: 0x3A1D

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_RADIO_TELEPHONE_NUMBER, PR_RADIO_TELEPHONE_NUMBER_A, PR_RADIO_TELEPHONE_NUMBER_W

2.988 PidTagRead

Canonical name: PidTagRead

Property ID: 0x0E69

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_READ, ptagRead, urn:schemas:httpmail:read

2.989 PidTagReadReceiptAddressType

Canonical name: PidTagReadReceiptAddressType

Property ID: 0x4029

Data type: PtypString, 0x001F

Area: Transport Envelope

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptAddrType, ReadReceiptAddrType

2.990 PidTagReadReceiptEmailAddress

Canonical name: PidTagReadReceiptEmailAddress

Property ID: 0x402A

Data type: PtypString, 0x001F

Area: Transport Envelope

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

2.991 PidTagReadReceiptEntryId

Canonical name: PidTagReadReceiptEntryId

Description: Contains an address book EntryID.

Property ID: 0x0046

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_READ_RECEIPT_ENTRYID, ptagReadReceiptEntryId

2.992 PidTagReadReceiptName

Canonical name: PidTagReadReceiptName

Property ID: 0x402B

Data type: PtypString, 0x001F

Area: Transport Envelope

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptDisplayName, ReadReceiptDisplayName

2.993 PidTagReadReceiptRequested

Canonical name: PidTagReadReceiptRequested

Description: Specifies whether the email sender requests a read receipt from all recipients when this email message is read or opened.

Property ID: 0x0029

Data type: PtypBoolean, 0x000B

Area: Email Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_READ_RECEIPT_REQUESTED, ptagReadReceiptRequested, <http://schemas.microsoft.com/exchange/readreceiptrequested>

2.994 PidTagReadReceiptSearchKey

Canonical name: PidTagReadReceiptSearchKey

Description: Contains an address book search key.

Property ID: 0x0053

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_READ_RECEIPT_SEARCH_KEY, ptagReadReceiptSearchKey

2.995 PidTagReceivedByAddressType

Canonical name: PidTagReceivedByAddressType

Description: Contains the email message receiver's email address type.

Property ID: 0x0075

Data type: PtypString, 0x001F

Area: MapiEnvelope

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RECEIVED_BY_ADDRTYPE, PR_RECEIVED_BY_ADDRTYPE_A, ptagReceivedByAddrType, PR_RECEIVED_BY_ADDRTYPE_W

2.996 PidTagReceivedByEmailAddress

Canonical name: PidTagReceivedByEmailAddress

Description: Contains the email message receiver's email address.

Property ID: 0x0076

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RECEIVED_BY_EMAIL_ADDRESS, PR_RECEIVED_BY_EMAIL_ADDRESS_A, PR_RECEIVED_BY_EMAIL_ADDRESS_W

2.997 PidTagReceivedByEntryId

Canonical name: PidTagReceivedByEntryId

Description: Identifies an address book EntryID that contains the email message receiver of the Email object.

Property ID: 0x003F

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RECEIVED_BY_ENTRYID

2.998 PidTagReceivedByFlags

Canonical name: PidTagReceivedByFlags

Property ID: 0x401B

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagRcvdByFlags

2.999 PidTagReceivedByName

Canonical name: PidTagReceivedByName

Description: Contains the email message receiver's display name.

Property ID: 0x0040

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RECEIVED_BY_NAME, PR_RECEIVED_BY_NAME_A, PR_RECEIVED_BY_NAME_W

2.1000 PidTagReceivedBySearchKey

Canonical name: PidTagReceivedBySearchKey

Description: Identifies an address book search key that contains a binary-comparable key that is used to identify correlated objects for a search.

Property ID: 0x0051

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RECEIVED_BY_SEARCH_KEY

2.1001 PidTagReceivedRepresentingAddressType

Canonical name: PidTagReceivedRepresentingAddressType

Description: Contains the email address type for the end user represented by the receiving mailbox owner.

Property ID: 0x0077

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RCVD_REPRESENTING_ADDRTYPE, PR_RCVD_REPRESENTING_ADDRTYPE_A, ptagRcvdRepresentingAddrType, PR_RCVD_REPRESENTING_ADDRTYPE_W

2.1002 PidTagReceivedRepresentingEmailAddress

Canonical name: PidTagReceivedRepresentingEmailAddress

Description: Contains the email address for the end user represented by the receiving mailbox owner.

Property ID: 0x0078

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RCVD_REPRESENTING_EMAIL_ADDRESS, PR_RCVD_REPRESENTING_EMAIL_ADDRESS_A, PR_RCVD_REPRESENTING_EMAIL_ADDRESS_W

2.1003 PidTagReceivedRepresentingEntryId

Canonical name: PidTagReceivedRepresentingEntryId

Description: Contains an address book EntryID that identifies the end user represented by the receiving mailbox owner.

Property ID: 0x0043

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RCVD_REPRESENTING_ENTRYID, ptagRcvdRepresentingEntryId

2.1004 PidTagReceivedRepresentingFlags

Canonical name: PidTagReceivedRepresentingFlags

Property ID: 0x401C

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagRcvdRepresentingFlags

2.1005 PidTagReceivedRepresentingName

Canonical name: PidTagReceivedRepresentingName

Description: Contains the display name, for the end user represented by the receiving mailbox owner.

Property ID: 0x0044

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RCVD_REPRESENTING_NAME, PR_RCVD_REPRESENTING_NAME_A, ptagRcvdRepresentingName, PR_RCVD_REPRESENTING_NAME_W

2.1006 PidTagReceivedRepresentingSearchKey

Canonical name: PidTagReceivedRepresentingSearchKey

Description: Identifies an address book search key that contains a binary-comparable key of the end user represented by the receiving mailbox owner.

Property ID: 0x0052

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RCVD_REPRESENTING_SEARCH_KEY, ptagRcvdRepresentingSearchKey

2.1007 PidTagReceivedRepresentingSimpleDisplayName

Canonical name: PidTagReceivedRepresentingSimpleDisplayName

Property ID: 0x4035

Data type: PtypString, 0x001F

Area: TransportEnvelope

References: [\[MS-OXTNEF\]](#)

Alternate names: ptagRcvdRepresentingSimpleDispName

2.1008 PidTagRecipientDisplayName

Canonical name: PidTagRecipientDisplayName

Property ID: 0x5FF6

Data type: PtypString, 0x001F

Area: TransportRecipient

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_DISPLAY_NAME, PR_RECIPIENT_DISPLAY_NAME_W

2.1009 PidTagRecipientEntryId

Canonical name: PidTagRecipientEntryId

Property ID: 0x5FF7

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_ENTRYID, ptagRecipientEntryId

2.1010 PidTagRecipientFlags

Canonical name: PidTagRecipientFlags

Property ID: 0x5FFD

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOCAL\]](#)

Alternate names: PR_RECIPIENT_FLAGS

2.1011 PidTagRecipientOrder

Canonical name: PidTagRecipientOrder

Property ID: 0x5FDF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_ORDER, ptagRecipientOrder

2.1012 PidTagRecipientProposed

Canonical name: PidTagRecipientProposed

Property ID: 0x5FE1

Data type: PtypBoolean, 0x000B

Area: TransportRecipient

References: [\[MS-OXOCAL\]](#)

Alternate names: PR_RECIPIENT_PROPOSED, ptagRecipientProposed

2.1013 PidTagRecipientProposedEndTime

Canonical name: PidTagRecipientProposedEndTime

Property ID: 0x5FE4

Data type: PtypTime, 0x0040

Area: TransportRecipient

References: [\[MS-OXOCAL\]](#)

Alternate names: PR_RECIPIENT_PROPOSEDENDTIME, ptagRecipientProposedEndTime

2.1014 PidTagRecipientProposedStartTime

Canonical name: PidTagRecipientProposedStartTime

Property ID: 0x5FE3

Data type: PtypTime, 0x0040

Area: TransportRecipient

References: [\[MS-OXOCAL\]](#)

Alternate names: PR_RECIPIENT_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

2.1015 PidTagRecipientReassignmentProhibited

Canonical name: PidTagRecipientReassignmentProhibited

Description: Specifies whether adding additional or different recipients is prohibited for the email message, when forwarding the email message.

Property ID: 0x002B

Data type: PtypBoolean, 0x000B

Area: MapiEnvelope

References: [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_REASSIGNMENT_PROHIBITED, ptagRecipientReassignmentProhibited

2.1016 PidTagRecipientResourceState

Canonical name: PidTagRecipientResourceState

Property ID: 0x5FDE

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_RESOURCESTATE

2.1017 PidTagRecipientTrackStatus

Canonical name: PidTagRecipientTrackStatus

Property ID: 0x5FFF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

References: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_TRACKSTATUS, ptagRecipientTrackStatus

2.1018 PidTagRecipientTrackStatusTime

Canonical name: PidTagRecipientTrackStatusTime

Property ID: 0x5FFB

Data type: PtypTime, 0x0040

Area: TransportRecipient

References: [\[MS-OXOCAL\]](#)

Alternate names: PR_RECIPIENT_TRACKSTATUS_TIME, ptagRecipientTrackStatusTime

2.1019 PidTagRecipientType

Canonical name: PidTagRecipientType

Description: Represents the recipient type of a recipient on the message.

Property ID: 0x0C15

Data type: PtypInteger32, 0x0003

Area: MapiRecipient

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_RECIPIENT_TYPE, ptagRecipientType

2.1020 PidTagRecordKey

Canonical name: PidTagRecordKey

Description: Contains a unique binary-comparable identifier for a specific object.

Property ID: 0x0FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_RECORD_KEY, ptagRecordKey

2.1021 PidTagReferredByName

Canonical name: PidTagReferredByName

Description: Contains the name of the mail user's referral.

Property ID: 0x3A47

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#)

Alternate names: PR_REFERRED_BY_NAME, PR_REFERRED_BY_NAME_A, PR_REFERRED_BY_NAME_W

2.1022 PidTagRemindersOnlineEntryId

Canonical name: PidTagRemindersOnlineEntryId

Property ID: 0x36D5

Data type: PtypBinary, 0x0102

Area: MapiContainer

References: [\[MS-OXOSFLD\]](#)

Alternate names: PR_REM_ONLINE_ENTRYID, ptagRemOnlineEntryId

2.1023 PidTagRemoteHeaderLoc

Canonical name: PidTagRemoteHeaderLoc

Property ID: 0x0078

Data type: PtypString, 0x001F

Area: MapiEnvelope

References: [\[MS-OXODLGT\]](#)

Alternate names: PR_REMOTE_HEADER_LOC

2.1024 PidTagRemoteMessageTransferAgent

Canonical name: PidTagRemoteMessageTransferAgent

Property ID: 0x0C21

Data type: PtypString, 0x001F

Area: Transport Envelope

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagDsnRemoteMta, PR_DSN_REMOTE_MTA, RemoteMta

2.1025 PidTagRenderingPosition

Canonical name: PidTagRenderingPosition

Description: Represents an offset, in rendered characters, to use when rendering an attachment within the main message text.

Property ID: 0x370B

Data type: PtypInteger32, 0x0003

Area: MapiAttachment

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_RENDERING_POSITION, ptagRenderingPosition

2.1026 PidTagReplyRecipientEntries

Canonical name: PidTagReplyRecipientEntries

Description: Identifies a FlatEntryList of address book EntryIDs for recipients that are to get a reply.

Property ID: 0x004F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope Property set

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_REPLY_RECIPIENT_ENTRIES, ptagReplyRecipientEntries, <http://schemas.microsoft.com/exchange/reply-to-base64>

2.1027 PidTagReplyRecipientNames

Canonical name: PidTagReplyRecipientNames

Description: Contains a list of display names for recipients that are to get a reply.

Property ID: 0x0050

Data type: PtypString, 0x001F

Area: MapiEnvelope

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_REPLY_RECIPIENT_NAMES, PR_REPLY_RECIPIENT_NAMES_A, ptagReplyRecipientNames, PR_REPLY_RECIPIENT_NAMES_W

2.1028 PidTagReplyRequested

Canonical name: PidTagReplyRequested

Description: Indicates whether a reply is requested to a Message object.

Property ID: 0x0C17

Data type: PtypBoolean, 0x000B

Area: MapiRecipient

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_REPLY_REQUESTED, ptagReplyRequested

2.1029 PidTagReplyTemplateId

Canonical name: PidTagReplyTemplateId

Property ID: 0x65C2

Data type: PtypBinary, 0x0102

Area: Rules

References: [\[MS-OXORULE\]](#)

Alternate names: PR_REPLY_TEMPLATE_ID, ptagReplyTemplateId

2.1030 PidTagReplyTime

Canonical name: PidTagReplyTime

Description: Specifies the due time that the sender wants for an associated work item.

Property ID: 0x0030

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_REPLY_TIME, urn:schemas:httpmail:reply-by, http://schemas.microsoft.com/exchange/reply-by-iso

2.1031 PidTagReportEntryId

Canonical name: PidTagReportEntryId

Property ID: 0x0045

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_REPORT_ENTRYID, ptagReportEntryId

2.1032 PidTagReportingMessageTransferAgent

Canonical name: PidTagReportingMessageTransferAgent

Property ID: 0x6820

Data type: PtypString, 0x001F

Area: Transport Envelope

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagDsnReportingMta, ReportingMta

2.1033 PidTagReportName

Canonical name: PidTagReportName

Property ID: 0x003A

Data type: PtypString, 0x001F

Area: MapiEnvelope

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_REPORT_NAME, PR_REPORT_NAME_A, PR_REPORT_NAME_W

2.1034 PidTagReportSearchKey

Canonical name: PidTagReportSearchKey

Property ID: 0x0054

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_REPORT_SEARCH_KEY, ptagReportSearchKey

2.1035 PidTagReportTag

Canonical name: PidTagReportTag

Description: Contains the data that is used to correlate the report and the original message.

Property ID: 0x0031

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_REPORT_TAG, ptagReportTag

2.1036 PidTagReportText

Canonical name: PidTagReportText

Description: Contains the optional text for a report message.

Property ID: 0x1001

Data type: PtypString, 0x001F

Area: MapiMessage

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_REPORT_TEXT, PR_REPORT_TEXT_A, ptagReportText, PR_REPORT_TEXT_W

2.1037 PidTagReportTime

Canonical name: PidTagReportTime

Description: Indicates the last time the contact list that is controlled by PidTagJunkIncludeContacts was updated.

Property ID: 0x0032

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

References: [\[MS-OXCSPAM\]](#)

Alternate names: PR_REPORT_TIME, ptagReportTime, <http://schemas.microsoft.com/exchange/reporttime>

2.1038 PidTagResolveMethod

Canonical name: PidTagResolveMethod

Property ID: 0x3FE7

Data type: PtypInteger32, 0x0003

Area: MapiStatus

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_RESOLVE_METHOD, ptagResolveMethod

2.1039 PidTagResponseRequested

Canonical name: PidTagResponseRequested

Description: Indicates whether a response is requested to a Message object.

Property ID: 0x0063

Data type: PtypBoolean, 0x000B

Area: MapiEnvelope Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_RESPONSE_REQUESTED, urn:schemas:calendar:responserequested, http://schemas.microsoft.com/mapi/response_requested

2.1040 PidTagResponsibility

Canonical name: PidTagResponsibility

Property ID: 0x0E0F

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

References: [\[MS-OXCFXICS\]](#)

Alternate names: PR_RESPONSIBILITY, ptagResponsibility

2.1041 PidTagRetentionDate

Canonical name: PidTagRetentionDate

Description: Specifies the date, in UTC, after which a Message object is expired by the server.

Property ID: 0x301C

Data type: PtypTime, 0x0040

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_RETENTION_DATE, ptagRetentionDate

2.1042 PidTagRetentionFlags

Canonical name: PidTagRetentionFlags

Property ID: 0x301D

Data type: PtypInteger32, 0x0003

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_RETENTION_FLAGS, ptagRetentionFlags

2.1043 PidTagRetentionPeriod

Canonical name: PidTagRetentionPeriod

Property ID: 0x301A

Data type: PtypInteger32, 0x0003

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_RETENTION_PERIOD, ptagRetentionPeriod

2.1044 PidTagRights

Canonical name: PidTagRights

Description: Specifies a user's folder permissions.

Property ID: 0x6639

Data type: PtypInteger32, 0x0003

Area: ExchangeFolder

References: [\[MS-OXCFOOLD\]](#)

Alternate names: PR_RIGHTS, ptagRights

2.1045 PidTagRoamingDatatypes

Canonical name: PidTagRoamingDatatypes

Property ID: 0x7C06

Data type: PtypInteger32, 0x0003

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_ROAMING_DATATYPES

2.1046 PidTagRoamingDictionary

Canonical name: PidTagRoamingDictionary

Property ID: 0x7C07

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_ROAMING_DICTIONARY

2.1047 PidTagRoamingXmlStream

Canonical name: PidTagRoamingXmlStream

Property ID: 0x7C08

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_ROAMING_XMLSTREAM

2.1048 PidTagRowid

Canonical name: PidTagRowid

Property ID: 0x3000

Data type: PtypInteger32, 0x0003

Area: MapiCommon

References: [\[MS-OXCFXICS\]](#)

Alternate names: PR_ROWID, ptagRowId

2.1049 PidTagRowType

Canonical name: PidTagRowType

Description: Identifies the type of the row.

Property ID: 0x0FF5

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

References: [\[MS-OXCTABL\]](#)

Alternate names: PR_ROW_TYPE, ptagRowType

2.1050 PidTagRtfCompressed

Canonical name: PidTagRtfCompressed

Description: Contains message body text in RTF format.

Property ID: 0x1009

Data type: PtypBinary, 0x0102

Area: Email

References: [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFCP\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_RTF_COMPRESSED, ptagRTFCompressed

2.1051 PidTagRtfInSync

Canonical name: PidTagRtfInSync

Description: Indicates whether the PidTagBody and PidTagRtfCompressed properties contain the same text (ignoring formatting).

Property ID: 0x0E1F

Data type: PtypBoolean, 0x000B

Area: Email

References: [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_RTF_IN_SYNC, ptagRTFInSync

2.1052 PidTagRtfSyncBodyCount

Canonical name: PidTagRtfSyncBodyCount

Property ID: 0x1007

Data type: PtypInteger32, 0x0003

Area: MapiMessage

References: [\[MS-OXTNEF\]](#)

Alternate names: PR_RTF_SYNC_BODY_COUNT, ptagRTFSyncBodyCount

2.1053 PidTagRtfSyncBodyCrc

Canonical name: PidTagRtfSyncBodyCrc

Property ID: 0x1006

Data type: PtypInteger32, 0x0003

Area: MapiMessage

References: [\[MS-OXTNEF\]](#)

Alternate names: PR_RTF_SYNC_BODY_CRC, ptagRTFSyncBodyCRC

2.1054 PidTagRtfSyncBodyTag

Canonical name: PidTagRtfSyncBodyTag

Property ID: 0x1008

Data type: PtypString, 0x001F

Area: MapiMessage

References: [\[MS-OXTNEF\]](#)

Alternate names: PR_RTF_SYNC_BODY_TAG, PR_RTF_SYNC_BODY_TAG_A, ptagRTFSyncBodyTag, PR_RTF_SYNC_BODY_TAG_W

2.1055 PidTagRtfSyncPrefixCount

Canonical name: PidTagRtfSyncPrefixCount

Property ID: 0x1010

Data type: PtypInteger32, 0x0003

Area: MapiMessage

References: [\[MS-OXTNEF\]](#)

Alternate names: PR_RTF_SYNC_PREFIX_COUNT

2.1056 PidTagRtfSyncTrailingCount

Canonical name: PidTagRtfSyncTrailingCount

Property ID: 0x1011

Data type: PtypInteger32, 0x0003

Area: MapiMessage

References: [\[MS-OXTNEF\]](#)

Alternate names: PR_RTF_SYNC_TRAILING_COUNT

2.1057 PidTagRuleActionNumber

Canonical name: PidTagRuleActionNumber

Property ID: 0x6650

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_ACTION_NUMBER, ptagRuleActionNumber

2.1058 PidTagRuleActions

Canonical name: PidTagRuleActions

Property ID: 0x6680

Data type: PtypRuleAction, 0x00FE

Area: Server-Side Rules Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_ACTIONS, ptagRuleActions

2.1059 PidTagRuleActionType

Canonical name: PidTagRuleActionType

Property ID: 0x6649

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_ACTION_TYPE, ptagRuleActionType

2.1060 PidTagRuleCondition

Canonical name: PidTagRuleCondition

Property ID: 0x6679

Data type: PtypRestriction, 0x00FD

Area: Server-Side Rules Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_CONDITION, ptagRuleCondition

2.1061 PidTagRuleError

Canonical name: PidTagRuleError

Property ID: 0x6648

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_ERROR, ptagRuleError

2.1062 PidTagRuleFolderEntryId

Canonical name: PidTagRuleFolderEntryId

Property ID: 0x6651

Data type: PtypBinary, 0x0102

Area: ExchangeMessageReadOnly

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_FOLDER_ENTRYID, ptagRuleFolderEntryId

2.1063 PidTagRuleId

Canonical name: PidTagRuleId

Property ID: 0x6674

Data type: PtypInteger64, 0x0014

Area: Server-Side Rules Properties

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_ID, ptagRuleId

2.1064 PidTagRuleLevel

Canonical name: PidTagRuleLevel

Property ID: 0x6683

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_LEVEL, ptagRuleLevel

2.1065 PidTagRuleMessageLevel

Canonical name: PidTagRuleMessageLevel

Property ID: 0x65ED

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_MSG_LEVEL, ptagRuleMsgLevel

2.1066 PidTagRuleMessageName

Canonical name: PidTagRuleMessageName

Property ID: 0x65EC

Data type: PtypString, 0x001F

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: ptagRuleMsgName

2.1067 PidTagRuleMessageProvider

Canonical name: PidTagRuleMessageProvider

Property ID: 0x65EB

Data type: PtypString, 0x001F

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: ptagRuleMsgProvider

2.1068 PidTagRuleMessageProviderData

Canonical name: PidTagRuleMessageProviderData

Property ID: 0x65EE

Data type: PtypBinary, 0x0102

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_MSG_PROVIDER_DATA, ptagRuleMsgProviderData

2.1069 PidTagRuleMessageSequence

Canonical name: PidTagRuleMessageSequence

Property ID: 0x65F3

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_MSG_SEQUENCE, ptagRuleMsgSequence

2.1070 PidTagRuleMessageState

Canonical name: PidTagRuleMessageState

Property ID: 0x65E9

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_MSG_STATE, ptagRuleMsgState

2.1071 PidTagRuleMessageUserFlags

Canonical name: PidTagRuleMessageUserFlags

Property ID: 0x65EA

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

References: [\[MS-OXCSPAM\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_MSG_USER_FLAGS, ptagRuleMsgUserFlags

2.1072 PidTagRuleName

Canonical name: PidTagRuleName

Property ID: 0x6682

Data type: PtypString, 0x001F

Area: Server-Side Rules Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_NAME, PR_RULE_NAME_A, ptagRuleName, PR_RULE_NAME_W

2.1073 PidTagRuleProvider

Canonical name: PidTagRuleProvider

Property ID: 0x6681

Data type: PtypString, 0x001F

Area: Server-Side Rules Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_PROVIDER, ptagRuleProvider, PR_RULE_PROVIDER_W

2.1074 PidTagRuleProviderData

Canonical name: PidTagRuleProviderData

Property ID: 0x6684

Data type: PtypBinary, 0x0102

Area: Server-Side Rules Properties

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_PROVIDER_DATA, ptagRuleProviderData

2.1075 PidTagRuleSequence

Canonical name: PidTagRuleSequence

Property ID: 0x6676

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

References: [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]-OXPROTO](#), [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_SEQUENCE, ptagRuleSequence

2.1076 PidTagRuleState

Canonical name: PidTagRuleState

Property ID: 0x6677

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_STATE, ptagRuleState

2.1077 PidTagRuleUserFlags

Canonical name: PidTagRuleUserFlags

Property ID: 0x6678

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_RULE_USER_FLAGS, ptagRuleUserFlags

2.1078 PidTagRwRulesStream

Canonical name: PidTagRwRulesStream

Property ID: 0x6802

Data type: PtypBinary, 0x0102

Area: Message Class Defined Transmittable

References: [\[MS-OXORULE\]](#)

Alternate names: PR_RW_RULES_STREAM

2.1079 PidTagScheduleInfoAppointmentTombstone

Canonical name: PidTagScheduleInfoAppointmentTombstone

Description: Contains a list of tombstones, where each tombstone represents a Meeting object that has been declined.

Property ID: 0x686A

Data type: PtypBinary, 0x0102

Area: Free/Busy Properties

References: [\[MS-OXOCAL\]](#)

Alternate names: PR_SCHDINFO_APPT_TOMBSTONE

2.1080 PidTagScheduleInfoAutoAcceptAppointments

Canonical name: PidTagScheduleInfoAutoAcceptAppointments

Description: Indicates whether a client or server is to automatically respond to all meeting requests for the attendee or resource.

Property ID: 0x686D

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

References: [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_AUTO_ACCEPT_APPTS

2.1081 PidTagScheduleInfoDelegateEntryIds

Canonical name: PidTagScheduleInfoDelegateEntryIds

Property ID: 0x6845

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

References: [\[MS-OXODLGT\]](#)

Alternate names: PR_SCHDINFO_DELEGATE_ENTRYIDS

2.1082 PidTagScheduleInfoDelegateNames

Canonical name: PidTagScheduleInfoDelegateNames

Property ID: 0x6844

Data type: PtypMultipleString, 0x101F

Area: Free/Busy Properties

References: [\[MS-OXMSG\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_SCHDINFO_DELEGATE_NAMES

2.1083 PidTagScheduleInfoDelegateNamesW

Canonical name: PidTagScheduleInfoDelegateNamesW

Property ID: 0x684A

Data type: PtypMultipleString, 0x101F

Area: Free/Busy Properties

References: [\[MS-OXODLGT\]](#)

Alternate names: PR_SCHDINFO_DELEGATE_NAMES_W, ptagDelegateNames

2.1084 PidTagScheduleInfoDelegatorWantsCopy

Canonical name: PidTagScheduleInfoDelegatorWantsCopy

Property ID: 0x6842

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_BOSS_WANTS_COPY

2.1085 PidTagScheduleInfoDelegatorWantsInfo

Canonical name: PidTagScheduleInfoDelegatorWantsInfo

Property ID: 0x684B

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

References: [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_BOSS_WANTS_INFO

2.1086 PidTagScheduleInfoDisallowOverlappingAppts

Canonical name: PidTagScheduleInfoDisallowOverlappingAppts

Description: Indicates whether a client or server, when automatically responding to meeting requests, is to decline instances that overlap with previously scheduled events.

Property ID: 0x686F

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

References: [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_DISALLOW_OVERLAPPING_APPTS

2.1087 PidTagScheduleInfoDisallowRecurringAppts

Canonical name: PidTagScheduleInfoDisallowRecurringAppts

Description: Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that represent a recurring series.

Property ID: 0x686E

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

References: [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_DISALLOW_RECURRING_APPTS

2.1088 PidTagScheduleInfoDontMailDelegates

Canonical name: PidTagScheduleInfoDontMailDelegates

Property ID: 0x6843

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_DONT_MAIL_DELEGATES

2.1089 PidTagScheduleInfoFreeBusy

Canonical name: PidTagScheduleInfoFreeBusy

Property ID: 0x686C

Data type: PtypBinary, 0x0102

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_FREEBUSY

2.1090 PidTagScheduleInfoFreeBusyAway

Canonical name: PidTagScheduleInfoFreeBusyAway

Property ID: 0x6856

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_FREEBUSY_OOF

2.1091 PidTagScheduleInfoFreeBusyBusy

Canonical name: PidTagScheduleInfoFreeBusyBusy

Property ID: 0x6854

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_FREEBUSY_BUSY

2.1092 PidTagScheduleInfoFreeBusyMerged

Canonical name: PidTagScheduleInfoFreeBusyMerged

Property ID: 0x6850

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_FREEBUSY_MERGED

2.1093 PidTagScheduleInfoFreeBusyTentative

Canonical name: PidTagScheduleInfoFreeBusyTentative

Property ID: 0x6852

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_FREEBUSY_TENTATIVE

2.1094 PidTagScheduleInfoMonthsAway

Canonical name: PidTagScheduleInfoMonthsAway

Property ID: 0x6855

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_MONTHS_OOF

2.1095 PidTagScheduleInfoMonthsBusy

Canonical name: PidTagScheduleInfoMonthsBusy

Property ID: 0x6853

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

References: [\[MS-OXMSG\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_MONTHS_BUSY

2.1096 PidTagScheduleInfoMonthsMerged

Canonical name: PidTagScheduleInfoMonthsMerged

Property ID: 0x684F

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_MONTHS_MERGED

2.1097 PidTagScheduleInfoMonthsTentative

Canonical name: PidTagScheduleInfoMonthsTentative

Property ID: 0x6851

Data type: PtypMultipleInteger32, 0x1003

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_MONTHS_TENTATIVE

2.1098 PidTagScheduleInfoResourceType

Canonical name: PidTagScheduleInfoResourceType

Property ID: 0x6841

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_RESOURCE_TYPE

2.1099 PidTagSchedulePlusFreeBusyEntryId

Canonical name: PidTagSchedulePlusFreeBusyEntryId

Property ID: 0x6622

Data type: PtypBinary, 0x0102

Area: ExchangeMessageStore

References: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SPLUS_FREE_BUSY_ENTRYID

2.1100 PidTagScriptData

Canonical name: PidTagScriptData

Property ID: 0x0004

Data type: PtypBinary, 0x0102

Area: Address Book

References: [\[MS-OXOABKT\]](#)

Alternate names: PR_EMS_SCRIPT_BLOB

2.1101 PidTagSearchFolderDefinition

Canonical name: PidTagSearchFolderDefinition

Property ID: 0x6845

Data type: PtypBinary, 0x0102

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_DEFINITION

2.1102 PidTagSearchFolderEfpFlags

Canonical name: PidTagSearchFolderEfpFlags

Property ID: 0x6848

Data type: PtypInteger32, 0x0003

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_EFP_FLAGS

2.1103 PidTagSearchFolderExpiration

Canonical name: PidTagSearchFolderExpiration

Property ID: 0x683A

Data type: PtypInteger32, 0x0003

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_EXPIRATION

2.1104 PidTagSearchFolderId

Canonical name: PidTagSearchFolderId

Property ID: 0x6842

Data type: PtypBinary, 0x0102

Area: Search

References: [\[MS-OXOCFG\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_ID

2.1105 PidTagSearchFolderLastUsed

Canonical name: PidTagSearchFolderLastUsed

Property ID: 0x6834

Data type: PtypInteger32, 0x0003

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_LAST_USED

2.1106 PidTagSearchFolderRecreateInfo

Canonical name: PidTagSearchFolderRecreateInfo

Property ID: 0x6844

Data type: PtypBinary, 0x0102

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_RECREATE_INFO

2.1107 PidTagSearchFolderStorageType

Canonical name: PidTagSearchFolderStorageType

Property ID: 0x6846

Data type: PtypInteger32, 0x0003

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_STORAGE_TYPE

2.1108 PidTagSearchFolderTag

Canonical name: PidTagSearchFolderTag

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_TAG

2.1109 PidTagSearchFolderTemplateId

Canonical name: PidTagSearchFolderTemplateId

Property ID: 0x6841

Data type: PtypInteger32, 0x0003

Area: Search

References: [\[MS-OXOSRCH\]](#)

Alternate names: PR_WB_SF_TEMPLATE_ID

2.1110 PidTagSearchKey

Canonical name: PidTagSearchKey

Description: Contains a unique binary-comparable key that identifies an object for a search.

Property ID: 0x300B

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SEARCH_KEY, ptagSearchKey

2.1111 PidTagSecureSubmitFlags

Canonical name: PidTagSecureSubmitFlags

Property ID: 0x65C6

Data type: PtypInteger32, 0x0003

Area: Exchange

References: [\[MS-OXCFXICS\]](#)

Alternate names: PR_SECURE_SUBMIT_FLAGS, ptagSecureSubmitFlags

2.1112 PidTagSecurityDescriptor

Canonical name: PidTagSecurityDescriptor

Property ID: 0x0E27

Data type: PtypBinary, 0x0102

Area: Access Control Properties

References: [\[MS-OXCMMSG\]](#), [\[MS-OXCPerm\]](#), [\[MS-XWDVSEC\]](#)

Alternate names: PR_NT_SECURITY_DESCRIPTOR

2.1113 PidTagSecurityDescriptorAsXml

Canonical name: PidTagSecurityDescriptorAsXml

Property ID: 0x0E6A

Data type: PtypString, 0x001F

Area: Access Control Properties Property set

References: [\[MS-OXCPerm\]](#), [\[MS-XWDVSEC\]](#)

Alternate names: PR_NT_SECURITY_DESCRIPTOR_AS_XML,
PR_NT_SECURITY_DESCRIPTOR_AS_XML_A, PR_NT_SECURITY_DESCRIPTOR_AS_XML_W,
<http://schemas.microsoft.com/exchange/security/descriptor>

2.1114 PidTagSelectable

Canonical name: PidTagSelectable

Property ID: 0x3609

Data type: PtypBoolean, 0x000B

Area: AB Container

References: [\[MS-OXOABKT\]](#)

Alternate names: PR_SELECTABLE

2.1115 PidTagSenderAddressType

Canonical name: PidTagSenderAddressType

Description: Contains the sending mailbox owner's email address type.

Property ID: 0x0C1E

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOPOST\]](#)

Alternate names: PR_SENDER_ADDRTYPE, PR_SENDER_ADDRTYPE_A, ptagSenderAddrType, PR_SENDER_ADDRTYPE_W

2.1116 PidTagSenderEmailAddress

Canonical name: PidTagSenderEmailAddress

Description: Contains the contents of the <email> element of the <author> element in an Atom item if it exists.

Property ID: 0x0C1F

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENDER_EMAIL_ADDRESS, PR_SENDER_EMAIL_ADDRESS_A, PR_SENDER_EMAIL_ADDRESS_W

2.1117 PidTagSenderEntryId

Canonical name: PidTagSenderEntryId

Description: Identifies an address book EntryID that MUST contain the sending mailbox owner's address book EntryID.

Property ID: 0x0C19

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENDER_ENTRYID, ptagSenderEntryId

2.1118 PidTagSenderFlags

Canonical name: PidTagSenderFlags

Property ID: 0x4019

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagSenderFlags

2.1119 PidTagSenderIdStatus

Canonical name: PidTagSenderIdStatus

Description: Reports the results of a Sender-ID check.

Property ID: 0x4079

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

References: [\[MS-OXCMAIL\]](#), [\[MS-OXCSPAM\]](#)

Alternate names: PR_SENDER_ID_STATUS

2.1120 PidTagSenderName

Canonical name: PidTagSenderName

Description: Contains the sending Mailbox owner's display name

Property ID: 0x0C1A

Data type: PtypString, 0x001F

Area: Address Properties Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXORSS\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_SENDER_NAME, PR_SENDER_NAME_A, ptagSenderName, PR_SENDER_NAME_W, urn:schemas:httpmail:sendername, http://schemas.microsoft.com/exchange/sender-name-utf8

2.1121 PidTagSenderSearchKey

Canonical name: PidTagSenderSearchKey

Description: Identifies an address book search key.

Property ID: 0x0C1D

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: PR_SENDER_SEARCH_KEY, ptagSenderSearchKey

2.1122 PidTagSenderSimpleDisplayName

Canonical name: PidTagSenderSimpleDisplayName

Property ID: 0x4030

Data type: PtypString, 0x001F

Area: TransportEnvelope

References: [\[MS-OXTNEF\]](#)

Alternate names: ptagSenderSimpleDispName

2.1.123 PidTagSenderSmtpAddress

Canonical name: PidTagSenderSmtpAddress

Property ID: 0x5D01

Data type: PtypString, 0x001F

Area: Mail

References: [\[MS-OXCMAIL\]](#)

Alternate names: SenderSmtpAddress, ptagSenderSmtpAddress

2.1.124 PidTagSenderTelephoneNumber

Canonical name: PidTagSenderTelephoneNumber

Property ID: 0x6802

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaSenderTelephoneNumber

2.1.125 PidTagSendInternetEncoding

Canonical name: PidTagSendInternetEncoding

Description: Contains a bitmask of message encoding preferences for mail sent to an e-mail-enabled entity that is represented by this Address Book object.

Property ID: 0x3A71

Data type: PtypInteger32, 0x0003

Area: Address Properties

References: [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_SEND_INTERNET_ENCODING, ptagSendInternetEncoding

2.1.126 PidTagSendRichInfo

Canonical name: PidTagSendRichInfo

Description: Contains TRUE if the e-mail-enabled entity represented by the Address Book object can receive all message content, including Rich Text Format (RTF) and other embedded objects.

Property ID: 0x3A40

Data type: PtypBoolean, 0x000B

Area: Address Properties

References: [\[MS-OXOAB\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_SEND_RICH_INFO, ptagSendRichInfo

2.1127 PidTagSensitivity

Canonical name: PidTagSensitivity

Description: Indicates the sender's assessment of the sensitivity of the Message object.

Property ID: 0x0036

Data type: PtypInteger32, 0x0003

Area: General Message Properties Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXODOC\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDMail\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SENSITIVITY, ptagSensitivity,
<http://schemas.microsoft.com/exchange/sensitivity-long>,
<http://schemas.microsoft.com/exchange/sensitivity>

2.1128 PidTagSentMailEntryId

Canonical name: PidTagSentMailEntryId

Property ID: 0x0E0A

Data type: PtypBinary, 0x0102

Area: MapiNonTransmittable

References: [\[MS-OXCICAL\]](#)

Alternate names: PR_SENTMAIL_ENTRYID, ptagSentMailEntryId

2.1129 PidTagSentMailSvrEID

Canonical name: PidTagSentMailSvrEID

Description: Contains an EntryID that represents the Sent Items folder for the message.

Property ID: 0x6740

Data type: PtypServerId, 0x00FB

Area: ProviderDefinedNonTransmittable

References: [\[MS-OXCSTOR\]](#), [\[MS-OXOMSG\]](#)

Alternate names: ptagSentMailSvrEID

2.1130 PidTagSentRepresentingAddressType

Canonical name: PidTagSentRepresentingAddressType

Description: Contains an email address type.

Property ID: 0x0064

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_ADDRTYPE, PR_SENT_REPRESENTING_ADDRTYPE_A, ptagSentRepresentingAddrType, PR_SENT_REPRESENTING_ADDRTYPE_W

2.1131 PidTagSentRepresentingEmailAddress

Canonical name: PidTagSentRepresentingEmailAddress

Description: Contains the contents of the <email> element of the <author> element in an Atom item, if it exists.

Property ID: 0x0065

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_EMAIL_ADDRESS, PR_SENT_REPRESENTING_EMAIL_ADDRESS_A, PR_SENT_REPRESENTING_EMAIL_ADDRESS_W

2.1132 PidTagSentRepresentingEntryId

Canonical name: PidTagSentRepresentingEntryId

Description: Identifies an address book EntryID.

Property ID: 0x0041

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_ENTRYID, ptagSentRepresentingEntryId

2.1133 PidTagSentRepresentingFlags

Canonical name: PidTagSentRepresentingFlags

Property ID: 0x401A

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagSentRepresentingFlags

2.1134 PidTagSentRepresentingName

Canonical name: PidTagSentRepresentingName

Description: Contains the display name for the end user who is represented by the sending Mailbox owner.

Property ID: 0x0042

Data type: PtypString, 0x001F

Area: Address Properties Property set

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_SENT_REPRESENTING_NAME, PR_SENT_REPRESENTING_NAME_A, ptagSentRepresentingName, PR_SENT_REPRESENTING_NAME_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

2.1135 PidTagSentRepresentingSearchKey

Canonical name: PidTagSentRepresentingSearchKey

Description: Identifies an address book search key.

Property ID: 0x003B

Data type: PtypBinary, 0x0102

Area: Address Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: PR_SENT_REPRESENTING_SEARCH_KEY, ptagSentRepresentingSearchKey

2.1136 PidTagSentRepresentingSimpleDisplayName

Canonical name: PidTagSentRepresentingSimpleDisplayName

Property ID: 0x4031

Data type: PtypString, 0x001F

Area: TransportEnvelope

References: [\[MS-OXTNEF\]](#)

Alternate names: ptagSentRepresentingSimpleDispName

2.1137 PidTagSessionInitiationProtocolUri

Canonical name: PidTagSessionInitiationProtocolUri

Property ID: 0x5FE5

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagRecipientSipUri, SipUri

2.1138 PidTagSmtpAddress

Canonical name: PidTagSmtpAddress

Description: Contains the AddressBook object's SMTP address.

Property ID: 0x39FE

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-NSPI\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXSHARE\]](#)

Alternate names: PR_SMTP_ADDRESS, PR_SMTP_ADDRESS_A, PR_SMTP_ADDRESS_W

2.1139 PidTagSortLocaleId

Canonical name: PidTagSortLocaleId

Property ID: 0x6705

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

References: [\[MS-OXCSTOR\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_SORT_LOCALE_ID, ptagSortLocaleId

2.1140 PidTagSourceKey

Canonical name: PidTagSourceKey

Description: Contains a value that contains an internal identifier (GID) for this folder or message.

Property ID: 0x65E0

Data type: PtypBinary, 0x0102

Area: Sync

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCSYNC\]](#)

Alternate names: PR_SOURCE_KEY

2.1141 PidTagSpokenName

Canonical name: PidTagSpokenName

Property ID: 0x8CC2

Data type: PtypBinary, 0x0102

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_UM_SPOKEN_NAME

2.1142 PidTagSpouseName

Canonical name: PidTagSpouseName

Description: Contains the name of the mail user's spouse/partner.

Property ID: 0x3A48

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SPOUSE_NAME, PR_SPOUSE_NAME_A, PR_SPOUSE_NAME_W,
urn:schemas:contacts:spousecn

2.1143 PidTagStartDate

Canonical name: PidTagStartDate

Description: Contains the value of the PidLidAppointmentStartWhole property.

Property ID: 0x0060

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: PR_START_DATE, http://schemas.microsoft.com/mapi/start_date

2.1144 PidTagStartDateEtc

Canonical name: PidTagStartDateEtc

Description: Contains two pieces of information: the default retention period, and the start date from which the Message object's age is calculated.

Property ID: 0x301B

Data type: PtypBinary, 0x0102

Area: Archive

References: [MS-OXCMSG](#)

Alternate names: PR_START_DATE_ETC, ptagStartDateEtc

2.1145 PidTagStartEmbed

Canonical name: PidTagStartEmbed

Property ID: 0x4001

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagStartEmbed

2.1146 PidTagStartFAIMsg

Canonical name: PidTagStartFAIMsg

Property ID: 0x4010

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagStartFAIMsg

2.1147 PidTagStartMessage

Canonical name: PidTagStartMessage

Property ID: 0x400C

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagStartMessage

2.1148 PidTagStartRecip

Canonical name: PidTagStartRecip

Property ID: 0x4003

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagStartRecip

2.1149 PidTagStartSubFld

Canonical name: PidTagStartSubFld

Property ID: 0x400A

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagStartSubFld

2.1150 PidTagStartTopFld

Canonical name: PidTagStartTopFld

Property ID: 0x4009

Data type: PtypInteger32, 0x0003

Area: TransportEnvelope

References: [\[MS-OXCFXICS\]](#)

Alternate names: ptagStartTopFld

2.1151 PidTagStateOrProvince

Canonical name: PidTagStateOrProvince

Description: Contains the name of the mail user's state or province.

Property ID: 0x3A28

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_STATE_OR_PROVINCE, PR_STATE_OR_PROVINCE_A, PR_STATE_OR_PROVINCE_W, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_A, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:mailingstate

2.1152 PidTagStoreEntryId

Canonical name: PidTagStoreEntryId

Property ID: 0x0FFB

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-OXOFLAG\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_STORE_ENTRYID, ptagStoreEntryId

2.1153 PidTagStoreState

Canonical name: PidTagStoreState

Property ID: 0x340E

Data type: PtypInteger32, 0x0003

Area: MapiMessageStore

References: [\[MS-OXCSTOR\]](#)

Alternate names: PR_STORE_STATE

2.1154 PidTagStoreSupportMask

Canonical name: PidTagStoreSupportMask

Property ID: 0x340D

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXOMSG\]](#)

Alternate names: PR_STORE_SUPPORT_MASK, ptagStoreSupportMask

2.1155 PidTagStreetAddress

Canonical name: PidTagStreetAddress

Description: Contains the mail user's street address.

Property ID: 0x3A29

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_STREET_ADDRESS, PR_STREET_ADDRESS_A, PR_STREET_ADDRESS_W, PR_BUSINESS_ADDRESS_STREET, PR_BUSINESS_ADDRESS_STREET_A, PR_BUSINESS_ADDRESS_STREET_W, urn:schemas:contacts:mailingstreet

2.1156 PidTagSubfolder

Canonical name: PidTagSubfolder

Property ID: 0x6708

Data type: PtypBoolean, 0x000B

Area: ExchangeAdministrative Property set

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

Alternate names: PR_SUBFOLDER, ptagSubfolder, DAV:isfolder

2.1157 PidTagSubfolders

Canonical name: PidTagSubfolders

Description: Specifies whether a folder has any subfolders.

Property ID: 0x360A

Data type: PtypBoolean, 0x000B

Area: MapiContainer

References: [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-XWDFOLD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SUBFOLDERS, ptagSubFolders, DAV:hassubs

2.1158 PidTagSubject

Canonical name: PidTagSubject

Property ID: 0x0037

Data type: PtypString, 0x001F

Area: General Message Properties Property set

References: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SUBJECT, PR_SUBJECT_A, ptagSubject, PR_SUBJECT_W, urn:schemas:httpmail:subject, http://schemas.microsoft.com/exchange/subject-utf8

2.1159 PidTagSubjectPrefix

Canonical name: PidTagSubjectPrefix

Description: Contains the prefix for the subject of the message.

Property ID: 0x003D

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SUBJECT_PREFIX, PR_SUBJECT_PREFIX_A, ptagSubjectPrefix, PR_SUBJECT_PREFIX_W

2.1160 PidTagSubmitFlags

Canonical name: PidTagSubmitFlags

Property ID: 0x0E14

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

References: [\[MS-OXCICAL\]](#)

Alternate names: PR_SUBMIT_FLAGS, ptagSubmitFlags

2.1161 PidTagSurname

Canonical name: PidTagSurname

Description: Contains the mail user's family name.

Property ID: 0x3A11

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SURNAME, PR_SURNAME_A, PR_SURNAME_W, urn:schemas:contacts:sn

2.1162 PidTagSwappedToDoData

Canonical name: PidTagSwappedToDoData

Description: Contains a secondary flag storage location if sender flags or sender reminders are supported.

Property ID: 0x0E2D

Data type: PtypBinary, 0x0102

Area: MapiNonTransmittable

References: [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_SWAPPED_TODO_DATA, ptagSwappedToDoData

2.1163 PidTagSwappedToDoStore

Canonical name: PidTagSwappedToDoStore

Description: Contains the value of PidTagStoreEntryId of the message if PidTagSwappedToDoData is set.

Property ID: 0x0E2C

Data type: PtypBinary, 0x0102

Area: MapiNonTransmittable

References: [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_SWAPPED_TODO_STORE, ptagSwappedToDoStore

2.1164 PidTagTargetEntryId

Canonical name: PidTagTargetEntryId

Description: Used in conjunction with an optimizing send client.

Property ID: 0x3010

Data type: PtypBinary, 0x0102

Area: ID Properties

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCRPC\]](#), [\[MS-OXCSYNC\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_TARGET_ENTRYID, ptagTargetEntryId

2.1165 PidTagTcvConstLongOne

Canonical name: PidTagTcvConstLongOne

Property ID: 0x8008

Data type: PtypInteger32, 0x0003

Area: PST Internal

References: [\[MS-OXCTABL\]](#)

Alternate names: PR_TCV_CONST_LONG_ONE

2.1166 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Canonical name: PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Description: Contains the mail user's telecommunication device for the deaf (TTYTDD) telephone number.

Property ID: 0x3A4B

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_TTYTDD_PHONE_NUMBER, PR_TTYTDD_PHONE_NUMBER_A, PR_TTYTDD_PHONE_NUMBER_W, urn:schemas:contacts:ttyddphone

2.1167 PidTagTelexNumber

Canonical name: PidTagTelexNumber

Description: Contains the mail user's telex number.

Property ID: 0x3A2C

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_TELEX_NUMBER, PR_TELEX_NUMBER_A, PR_TELEX_NUMBER_W, urn:schemas:contacts:telexnumber

2.1168 PidTagTemplateData

Canonical name: PidTagTemplateData

Property ID: 0x0001

Data type: PtypBinary, 0x0102

Area: Address Book

References: [\[MS-OXOABKT\]](#)

Alternate names: PR_EMS_TEMPLATE_BLOB

2.1169 PidTagTemplateid

Canonical name: PidTagTemplateid

Description: Contains the PidTagEntryId, expressed as a Permanent Entry ID format.

Property ID: 0x3902

Data type: PtypBinary, 0x0102

Area: MapiAddressBook

References: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_TEMPLATEID

2.1170 PidTagTemporaryDefaultDocument

Canonical name: PidTagTemporaryDefaultDocument

Property ID: 0x3F20

Data type: PtypString, 0x001F

Area: Structured Documents Property set

References: [\[MS-XWDSTRUCTDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:defaultdocument

2.1171 PidTagTextAttachmentCharset

Canonical name: PidTagTextAttachmentCharset

Property ID: 0x371B

Data type: PtypString, 0x001F

Area: Message Attachment Properties

References: [\[MS-OXCMAIL\]](#)

Alternate names: ptagTextAttachmentCharset

2.1172 PidTagThumbnailPhoto

Canonical name: PidTagThumbnailPhoto

Description: Contain an image of the mail user's photo in .jpg format.

Property ID: 0x8C9E

Data type: PtypBinary, 0x0102

Area: Address Book

References: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_EMS_AB_THUMBNAIL_PHOTO

2.1173 PidTagTitle

Canonical name: PidTagTitle

Description: Contains the mail user's job title.

Property ID: 0x3A17

Data type: PtypString, 0x001F

Area: MapiMailUser

References: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_TITLE, PR_TITLE_A, PR_TITLE_W, urn:schemas:contacts:title

2.1174 PidTagTnefCorrelationKey

Canonical name: PidTagTnefCorrelationKey

Property ID: 0x007F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_TNEF_CORRELATION_KEY

2.1175 PidTagToDoItemFlags

Canonical name: PidTagToDoItemFlags

Property ID: 0x0E2B

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_TODO_ITEM_FLAGS, ptagToDoItemFlags

2.1176 PidTagTransmittableDisplayName

Canonical name: PidTagTransmittableDisplayName

Description: Contains an Address Book object's display name that is transmitted with the message.

Property ID: 0x3A20

Data type: PtypString, 0x001F

Area: Address Properties

References: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_TRANSMITTABLE_DISPLAY_NAME, PR_TRANSMITTABLE_DISPLAY_NAME_A, ptagTransmittableDisplayName, PR_TRANSMITTABLE_DISPLAY_NAME_W

2.1177 PidTagTransportMessageHeaders

Canonical name: PidTagTransportMessageHeaders

Description: Contains transport-specific message envelope information for email.

Property ID: 0x007D

Data type: PtypString, 0x001F

Area: EMail

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_TRANSPORT_MESSAGE_HEADERS, PR_TRANSPORT_MESSAGE_HEADERS_A, PR_TRANSPORT_MESSAGE_HEADERS_W

2.1178 PidTagTrustSender

Canonical name: PidTagTrustSender

Property ID: 0x0E79

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

References: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_TRUST_SENDER, ptagTrustSender

2.1179 PidTagTtyTddPhoneNumber

Canonical name: PidTagTtyTddPhoneNumber

Description: Specifies the telephone number for the contact's text telephone (TTY) or telecommunication device for the deaf (TDD).

Property ID: 0x3A4B

Data type: PtypString, 0x001F

Area: Contact Properties

References: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_TTYTDD_PHONE_NUMBER

2.1180 PidTagUrlCompName

Canonical name: PidTagUrlCompName

Property ID: 0x10F3

Data type: PtypString, 0x001F

Area: General Message Properties

References: [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_URL_COMP_NAME, PR_URL_COMP_NAME_A, PR_URL_COMP_NAME_W, ptagURLCompName

2.1181 PidTagUrlCompNameSet

Canonical name: PidTagUrlCompNameSet

Property ID: 0x0E62

Data type: PtypBoolean, 0x000B

Area: ID Properties

References: [\[MS-OXCMSG\]](#)

Alternate names: ptagURLCompNameSet

2.1182 PidTagUrlName

Canonical name: PidTagUrlName

Description: Contains the URL of an object.

Property ID: 0x6707

Data type: PtypString, 0x001F

Area: ExchangeAdministrative Property set

References: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_URL_NAME, PR_URL_NAME_A, PR_URL_NAME_W, ptagURLName, DAV:href

2.1183 PidTagUserCertificate

Canonical name: PidTagUserCertificate

Description: Contains an ASN.1 authentication certificate for a messaging user.

Property ID: 0x3A22

Data type: PtypBinary, 0x0102

Area: MapiMailUser

References: [\[MS-EXOAB\]](#), [\[MS-EXOABK\]](#), [\[MS-XWDCNTC\]](#)

Alternate names: PR_USER_CERTIFICATE, ptagUserCertificate, urn:schemas:contacts:usercertificate

2.1184 PidTagUserEntryId

Canonical name: PidTagUserEntryId

Description: Address book EntryID of the user logged on to the public folders.

Property ID: 0x6619

Data type: PtypBinary, 0x0102

Area: ExchangeMessageStore

References: [\[MS-OXCSTOR\]](#)

Alternate names: PR_USER_ENTRYID, ptagUserEntryId

2.1185 PidTagUserX509Certificate

Canonical name: PidTagUserX509Certificate

Description: Contains a list certificates for the mail user.

Property ID: 0x3A70

Data type: PtypMultipleBinary, 0x1102

Area: MapiMailUser

References: [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_USER_X509_CERTIFICATE

2.1186 PidTagViewDescriptorBinary

Canonical name: PidTagViewDescriptorBinary

Description: Contains view definitions.

Property ID: 0x7001

Data type: PtypBinary, 0x0102

Area: MessageClassDefinedTransmittable

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_BINARY

2.1187 PidTagViewDescriptorName

Canonical name: PidTagViewDescriptorName

Property ID: 0x7006

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_NAME, PR_VD_NAME_W

2.1188 PidTagViewDescriptorStrings

Canonical name: PidTagViewDescriptorStrings

Description: Contains view definitions in string format.

Property ID: 0x7002

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_STRINGS, PR_VD_STRINGS_W

2.1189 PidTagViewDescriptorVersion

Canonical name: PidTagViewDescriptorVersion

Description: Contains the View Descriptor version.

Property ID: 0x7007

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_VERSION

2.1190 PidTagVoiceMessageAttachmentOrder

Canonical name: PidTagVoiceMessageAttachmentOrder

Description: Contains a list of filenames for the audio file attachments that are to be played as part of a message.

Property ID: 0x6805

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#), [\[MS-OXOUM\]](#)

Alternate names: InternalSchemaVoiceMessageAttachmentOrder

2.1191 PidTagVoiceMessageDuration

Canonical name: PidTagVoiceMessageDuration

Property ID: 0x6801

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaVoiceMessageDuration

2.1192 PidTagVoiceMessageSenderName

Canonical name: PidTagVoiceMessageSenderName

Property ID: 0x6803

Data type: PtypString, 0x001F

Area: Unified Messaging

References: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaVoiceMessageSenderName

2.1193 PidTagWeddingAnniversary

Canonical name: PidTagWeddingAnniversary

Description: Contains the date of the mail user's wedding anniversary at 12:00 A.M.

Property ID: 0x3A41

Data type: PtypTime, 0x0040

Area: MapiMailUser

References: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_WEDDING_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

2.1194 PidTagWlinkAddressBookEID

Canonical name: PidTagWlinkAddressBookEID

Description: Specifies the value of PidTagEntryId of the user that the folder belongs to.

Property ID: 0x6854

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_ABEID PROP_TAG

2.1195 PidTagWlinkAddressBookStoreEID

Canonical name: PidTagWlinkAddressBookStoreEID

Description: Specifies the value of PidTagStoreEntryId of the current user (not the owner of the folder).

Property ID: 0x6891

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_AB_EXSTOREEID PROP_TAG

2.1196 PidTagWlinkCalendarColor

Canonical name: PidTagWlinkCalendarColor

Description: Specifies the background color of the calendar.

Property ID: 0x6853

Data type: PtypInteger32, 0x0003

Area: MS-OXOCFG

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_CALENDAR_COLOR_PROP_TAG

2.1197 PidTagWlinkClientID

Canonical name: PidTagWlinkClientID

Description: Specifies the Client ID that allows the client to determine whether the shortcut was created on the current machine/user via an equality test.

Property ID: 0x6890

Data type: PtypGuid, 0x0048

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_CLIENTID_PROP_TAG

2.1198 PidTagWlinkEntryId

Canonical name: PidTagWlinkEntryId

Property ID: 0x684C

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_ENTRYID_PROP_TAG

2.1199 PidTagWlinkFlags

Canonical name: PidTagWlinkFlags

Property ID: 0x684A

Data type: PtypInteger32, 0x0003

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_FLAGS_PROP_TAG

2.1200 PidTagWlinkFolderType

Canonical name: PidTagWlinkFolderType

Property ID: 0x684F

Data type: PtypGuid, 0x0048

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_FOLDER_TYPE: PROP_TAG

2.1201 PidTagWlinkGroupClsid

Canonical name: PidTagWlinkGroupClsid

Property ID: 0x6850

Data type: PtypGuid, 0x0048

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_GROUP_CLSID PROP_TAG

2.1202 PidTagWlinkGroupHeaderID

Canonical name: PidTagWlinkGroupHeaderID

Description: Specifies the ID of the Navigation shortcut which groups other Navigation shortcuts.

Property ID: 0x6842

Data type: PtypGuid, 0x0048

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WB_SF_ID PROP_TAG

2.1203 PidTagWlinkGroupName

Canonical name: PidTagWlinkGroupName

Property ID: 0x6851

Data type: PtypString, 0x001F

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_GROUP_NAME PROP_TAG

2.1204 PidTagWlinkOrdinal

Canonical name: PidTagWlinkOrdinal

Property ID: 0x684B

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_ORDINAL PROP_TAG

2.1205 PidTagWlinkRecordKey

Canonical name: PidTagWlinkRecordKey

Description: Specifies the value of PidTagRecordKey of the folder pointed to by the shortcut.

Property ID: 0x684D

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_RECKEY PROP_TAG

2.1206 PidTagWlinkROGroupType

Canonical name: PidTagWlinkROGroupType

Description: Specifies the type of group header.

Property ID: 0x6892

Data type: PtypInteger32, 0x0003

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_RO_GROUP_TYPE PROP_TAG

2.1207 PidTagWlinkSaveStamp

Canonical name: PidTagWlinkSaveStamp

Description: Specifies an integer that allows a client to identify with a high probability whether the Navigation shortcut was saved by the current client session.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WB_SF_TAG PROP_TAG

2.1208 PidTagWlinkSection

Canonical name: PidTagWlinkSection

Property ID: 0x6852

Data type: PtypInteger32, 0x0003

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_SECTION PROP_TAG

2.1209 PidTagWlinkStoreEntryId

Canonical name: PidTagWlinkStoreEntryId

Property ID: 0x684E

Data type: PtypBinary, 0x0102

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_STORE_ENTRYID PROP_TAG

2.1210 PidTagWlinkType

Canonical name: PidTagWlinkType

Property ID: 0x6849

Data type: PtypInteger32, 0x0003

Area: Configuration

References: [\[MS-OXOCFG\]](#)

Alternate names: PR_WLINK_TYPE PROP_TAG

3 Structure Examples

None.

4 Security Considerations

There are no security considerations unique to this specification.

5 Appendix A: Product Behavior

The information in this specification is applicable to the following product versions. References to product versions include released service packs.

- Microsoft® Office Outlook® 2003
- Microsoft® Exchange Server 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Exchange Server 2007
- Microsoft® Outlook® 2010
- Microsoft® Exchange Server 2010

Exceptions, if any, are noted below. If a service pack number appears with the product version, behavior changed in that service pack. The new behavior also applies to subsequent service packs of the product unless otherwise specified.

Unless otherwise specified, any statement of optional behavior in this specification prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that product does not follow the prescription.

6 Change Tracking

This section identifies changes made to [MS-OXPROPS] protocol documentation between February 2010 and May 2010 releases. Changes are classed as major, minor, or editorial.

Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- A protocol is deprecated.
- The removal of a document from the documentation set.
- Changes made for template compliance.

Minor changes do not affect protocol interoperability or implementation. Examples are updates to fix technical accuracy or ambiguity at the sentence, paragraph, or table level.

Editorial changes apply to grammatical, formatting, and style issues.

No changes means that the document is identical to its last release.

Major and minor changes can be described further using the following revision types:

- New content added.
- Content update.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.

- Content removed for template compliance.
- Obsolete document removed.

Editorial changes always have the revision type "Editorially updated."

Some important terms used in revision type descriptions are defined as follows:

Protocol syntax refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.

Protocol revision refers to changes made to a protocol that affect the bits that are sent over the wire.

Changes are listed in the following table. If you need further information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Revision Type
1.3 Overview	30293 Defined the "Description" heading used in the property structures.	Y	New content added.
1.3 Overview	Updated the section title.	N	Content updated for template compliance.
1.3.2 Commonly Used Property Sets	54278 Updated Messaging property set GUID.	N	Content update.
2 Structures	30293 Added one-line descriptions to several property structures defined in this section.	Y	New content added.
2.522 PidNameOriginalSpamConfidenceLevel	54278 Updated property set GUID.	N	Content update.
2.524 PidNameOutlookProtectionRuleTimestamp	54278 Added property set information.	Y	New content added.
2.966 PidTagParentKey	54999 Removed [MS-OXTNEF] from the list of references using this property.	Y	Content removed.

7 Index

A

[Applicability](#) 35

C

[Change tracking](#) 400

F

[Fields - vendor-extensible](#) 35

G

[Glossary](#) 27

I

[Implementer - security considerations](#) 398

[Introduction](#) 27

N

[Normative references](#) 27

O

[Overview](#) 30

P

[Product behavior](#) 399

R

References

[normative](#) 27

[Relationship to protocols and other structures](#) 35

S

[Security - implementer considerations](#) 398

T

[Tracking changes](#) 400

V

[Vendor-extensible fields](#) 35