

[MS-OXPROPS]: Exchange Server Protocols Master Property List

Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting iplg@microsoft.com.
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights.
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

Reservation of Rights. All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

Tools. The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

Preliminary Documentation. This Open Specification provides documentation for past and current releases and/or for the pre-release (beta) version of this technology. This Open Specification is final

documentation for past or current releases as specifically noted in the document, as applicable; it is preliminary documentation for the pre-release (beta) versions. Microsoft will release final documentation in connection with the commercial release of the updated or new version of this technology. As the documentation may change between this preliminary version and the final version of this technology, there are risks in relying on preliminary documentation. To the extent that you incur additional development obligations or any other costs as a result of relying on this preliminary documentation, you do so at your own risk.

Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Updated references to reflect date of initial release.
09/03/2008	1.02		Changed title of document.
10/01/2008	1.03		Revised and edited technical content.
12/03/2008	1.04		Revised and edited technical content.
02/04/2009	1.05		Revised and edited technical content.
03/04/2009	1.06		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	5.0.0	Major	Updated and revised the technical content.
05/05/2010	6.0.0	Major	Updated and revised the technical content.
08/04/2010	7.0	Major	Significantly changed the technical content.
11/03/2010	8.0	Major	Significantly changed the technical content.
03/18/2011	9.0	Major	Significantly changed the technical content.
08/05/2011	10.0	Major	Significantly changed the technical content.
10/07/2011	11.0	Major	Significantly changed the technical content.
01/20/2012	12.0	Major	Significantly changed the technical content.
04/27/2012	13.0	Major	Significantly changed the technical content.

Preliminary

Table of Contents

1 Introduction	27
1.1 Glossary	27
1.2 References	30
1.2.1 Normative References	30
1.2.2 Informative References	32
1.3 Overview	33
1.3.1 Common Message Classes	34
1.3.2 Commonly Used Property Sets	35
1.3.3 Property ID Ranges	36
1.3.4 WebDAV Property Naming	37
1.3.4.1 http://schemas.microsoft.com/mapi/proptag Namespace	37
1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace	38
1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace	38
1.4 Relationship to Protocols and Other Structures	38
1.5 Applicability Statement	39
1.6 Versioning and Localization	39
1.7 Vendor-Extensible Fields	39
2 Structures	40
2.1 PidLidAddressBookProviderArrayType	40
2.2 PidLidAddressBookProviderEmailList	40
2.3 PidLidAddressCountryCode	40
2.4 PidLidAgingDontAgeMe	41
2.5 PidLidAllAttendeesString	41
2.6 PidLidAllowExternalCheck	41
2.7 PidLidAnniversaryEventEntryId	42
2.8 PidLidAppointmentAuxiliaryFlags	42
2.9 PidLidAppointmentColor	42
2.10 PidLidAppointmentCounterProposal	43
2.11 PidLidAppointmentDuration	43
2.12 PidLidAppointmentEndDate	43
2.13 PidLidAppointmentEndTime	44
2.14 PidLidAppointmentEndWhole	44
2.15 PidLidAppointmentLastSequence	44
2.16 PidLidAppointmentMessageClass	45
2.17 PidLidAppointmentNotAllowPropose	45
2.18 PidLidAppointmentProposalNumber	45
2.19 PidLidAppointmentProposedDuration	46
2.20 PidLidAppointmentProposedEndWhole	46
2.21 PidLidAppointmentProposedStartWhole	46
2.22 PidLidAppointmentRecur	47
2.23 PidLidAppointmentReplyName	47
2.24 PidLidAppointmentReplyTime	47
2.25 PidLidAppointmentSequence	48
2.26 PidLidAppointmentSequenceTime	48
2.27 PidLidAppointmentStartDate	49
2.28 PidLidAppointmentStartTime	49
2.29 PidLidAppointmentStartWhole	49
2.30 PidLidAppointmentStateFlags	50
2.31 PidLidAppointmentSubType	50

2.32	PidLidAppointmentTimeZoneDefinitionEndDisplay	50
2.33	PidLidAppointmentTimeZoneDefinitionRecur	51
2.34	PidLidAppointmentTimeZoneDefinitionStartDisplay	51
2.35	PidLidAppointmentUnsendableRecipients	51
2.36	PidLidAppointmentUpdateTime	52
2.37	PidLidAttendeeCriticalChange	52
2.38	PidLidAutoFillLocation	52
2.39	PidLidAutoLog	53
2.40	PidLidAutoProcessState	53
2.41	PidLidAutoStartCheck	53
2.42	PidLidBilling	54
2.43	PidLidBirthdayEventEntryId	54
2.44	PidLidBirthdayLocal	54
2.45	PidLidBusinessCardCardPicture	55
2.46	PidLidBusinessCardDisplayDefinition	55
2.47	PidLidBusyStatus	55
2.48	PidLidCalendarType	56
2.49	PidLidCategories	56
2.50	PidLidCcAttendeesString	57
2.51	PidLidChangeHighlight	57
2.52	PidLidClassification	57
2.53	PidLidClassificationDescription	58
2.54	PidLidClassificationGuid	58
2.55	PidLidClassificationKeep	58
2.56	PidLidClassified	59
2.57	PidLidCleanGlobalObjectId	59
2.58	PidLidClientIntent	59
2.59	PidLidClipEnd	60
2.60	PidLidClipStart	60
2.61	PidLidCollaborateDoc	60
2.62	PidLidCommonEnd	61
2.63	PidLidCommonStart	61
2.64	PidLidCompanies	61
2.65	PidLidConferencingCheck	62
2.66	PidLidConferencingType	62
2.67	PidLidContactCharacterSet	62
2.68	PidLidContactItemData	63
2.69	PidLidContactLinkedGlobalAddressListEntryId	63
2.70	PidLidContactLinkEntry	63
2.71	PidLidContactLinkGlobalAddressListLinkId	64
2.72	PidLidContactLinkGlobalAddressListLinkState	64
2.73	PidLidContactLinkLinkRejectHistory	64
2.74	PidLidContactLinkName	65
2.75	PidLidContactLinkSearchKey	65
2.76	PidLidContactLinkSMTPAddressCache	65
2.77	PidLidContacts	66
2.78	PidLidContactUserField1	66
2.79	PidLidContactUserField2	66
2.80	PidLidContactUserField3	67
2.81	PidLidContactUserField4	67
2.82	PidLidConversationActionLastAppliedTime	68
2.83	PidLidConversationActionMaxDeliveryTime	68
2.84	PidLidConversationActionMoveFolderEid	68

2.85	PidLidConversationActionMoveStoreEid	69
2.86	PidLidConversationActionVersion	69
2.87	PidLidConversationProcessed	69
2.88	PidLidCurrentVersion	70
2.89	PidLidCurrentVersionName	70
2.90	PidLidDayInterval	70
2.91	PidLidDayOfMonth	71
2.92	PidLidDelegateMail	71
2.93	PidLidDepartment	71
2.94	PidLidDirectory	72
2.95	PidLidDistributionListChecksum	72
2.96	PidLidDistributionListMembers	72
2.97	PidLidDistributionListName	73
2.98	PidLidDistributionListOneOffMembers	73
2.99	PidLidDistributionListStream	73
2.100	PidLidEmail1AddressType	74
2.101	PidLidEmail1DisplayName	74
2.102	PidLidEmail1EmailAddress	74
2.103	PidLidEmail1OriginalDisplayName	75
2.104	PidLidEmail1OriginalEntryId	75
2.105	PidLidEmail2AddressType	75
2.106	PidLidEmail2DisplayName	76
2.107	PidLidEmail2EmailAddress	76
2.108	PidLidEmail2OriginalDisplayName	76
2.109	PidLidEmail2OriginalEntryId	77
2.110	PidLidEmail3AddressType	77
2.111	PidLidEmail3DisplayName	77
2.112	PidLidEmail3EmailAddress	78
2.113	PidLidEmail3OriginalDisplayName	78
2.114	PidLidEmail3OriginalEntryId	78
2.115	PidLidEndRecurrenceDate	79
2.116	PidLidEndRecurrenceTime	79
2.117	PidLidExceptionReplaceTime	79
2.118	PidLidFax1AddressType	80
2.119	PidLidFax1EmailAddress	80
2.120	PidLidFax1OriginalDisplayName	80
2.121	PidLidFax1OriginalEntryId	81
2.122	PidLidFax2AddressType	81
2.123	PidLidFax2EmailAddress	81
2.124	PidLidFax2OriginalDisplayName	82
2.125	PidLidFax2OriginalEntryId	82
2.126	PidLidFax3AddressType	82
2.127	PidLidFax3EmailAddress	82
2.128	PidLidFax3OriginalDisplayName	83
2.129	PidLidFax3OriginalEntryId	83
2.130	PidLidFExceptionalAttendees	83
2.131	PidLidFExceptionalBody	84
2.132	PidLidFileUnder	84
2.133	PidLidFileUnderId	84
2.134	PidLidFileUnderList	85
2.135	PidLidFInvited	85
2.136	PidLidFlagRequest	85
2.137	PidLidFlagString	86

2.138	PidLidForwardInstance	86
2.139	PidLidForwardNotificationRecipients	86
2.140	PidLidFOthersAppointment.....	87
2.141	PidLidFreeBusyLocation	87
2.142	PidLidGlobalObjectId.....	88
2.143	PidLidHasPicture.....	88
2.144	PidLidHomeAddress	88
2.145	PidLidHomeAddressCountryCode	89
2.146	PidLidHtml.....	89
2.147	PidLidICalendarDayOfWeekMask	89
2.148	PidLidInboundICalStream	89
2.149	PidLidInfoPathFormName	90
2.150	PidLidInstantMessagingAddress.....	90
2.151	PidLidIntendedBusyStatus	90
2.152	PidLidInternetAccountName.....	91
2.153	PidLidInternetAccountStamp.....	91
2.154	PidLidIsException	92
2.155	PidLidIsRecurring	92
2.156	PidLidIsContactLinked	92
2.157	PidLidIsSilent.....	93
2.158	PidLidLinkedTaskItems.....	93
2.159	PidLidLocation.....	93
2.160	PidLidLogDocumentPosted	94
2.161	PidLidLogDocumentPrinted	94
2.162	PidLidLogDocumentRouted	94
2.163	PidLidLogDocumentSaved	95
2.164	PidLidLogDuration	95
2.165	PidLidLogEnd	95
2.166	PidLidLogFlags	96
2.167	PidLidLogStart	96
2.168	PidLidLogType.....	96
2.169	PidLidLogTypeDesc.....	97
2.170	PidLidMeetingType.....	97
2.171	PidLidMeetingWorkspaceUrl	97
2.172	PidLidMonthInterval.....	98
2.173	PidLidMonthOfYear	98
2.174	PidLidMonthOfYearMask	98
2.175	PidLidNetShowUrl.....	99
2.176	PidLidNoEndDateFlag	99
2.177	PidLidNonSendableBcc.....	99
2.178	PidLidNonSendableCc.....	100
2.179	PidLidNonSendableTo.....	100
2.180	PidLidNonSendBccTrackStatus	100
2.181	PidLidNonSendCcTrackStatus.....	101
2.182	PidLidNonSendToTrackStatus.....	101
2.183	PidLidNoteColor.....	101
2.184	PidLidNoteHeight.....	102
2.185	PidLidNoteWidth.....	102
2.186	PidLidNoteX.....	102
2.187	PidLidNoteY	103
2.188	PidLidOccurrences	103
2.189	PidLidOldLocation	103
2.190	PidLidOldRecurrenceType	104

2.191	PidLidOldWhenEndWhole	104
2.192	PidLidOldWhenStartWhole	104
2.193	PidLidOnlinePassword	105
2.194	PidLidOptionalAttendees	105
2.195	PidLidOrganizerAlias	105
2.196	PidLidOriginalStoreEntryId	106
2.197	PidLidOtherAddress	106
2.198	PidLidOtherAddressCountryCode	106
2.199	PidLidOwnerCriticalChange	107
2.200	PidLidOwnerName	107
2.201	PidLidPendingStateForTeamMailboxDocument	107
2.202	PidLidPercentComplete	108
2.203	PidLidPostalAddressId	108
2.204	PidLidPostRssChannel	109
2.205	PidLidPostRssChannelLink	109
2.206	PidLidPostRssItemGuid	109
2.207	PidLidPostRssItemHash	109
2.208	PidLidPostRssItemLink	110
2.209	PidLidPostRssItemXml	110
2.210	PidLidPostRssSubscription	110
2.211	PidLidPrivate	111
2.212	PidLidPromptSendUpdate	111
2.213	PidLidRecurrenceDuration	111
2.214	PidLidRecurrencePattern	112
2.215	PidLidRecurrenceType	112
2.216	PidLidRecurring	112
2.217	PidLidReferenceEntryId	113
2.218	PidLidReferredBy	113
2.219	PidLidReminderDelta	114
2.220	PidLidReminderFileParameter	114
2.221	PidLidReminderOverride	114
2.222	PidLidReminderPlaySound	115
2.223	PidLidReminderSet	115
2.224	PidLidReminderSignalTime	116
2.225	PidLidReminderTime	116
2.226	PidLidReminderTimeDate	116
2.227	PidLidReminderTimeTime	117
2.228	PidLidReminderType	117
2.229	PidLidRemoteStatus	117
2.230	PidLidRequiredAttendees	118
2.231	PidLidResourceAttendees	118
2.232	PidLidResponseStatus	118
2.233	PidLidServerProcessed	119
2.234	PidLidServerProcessingActions	119
2.235	PidLidSharingAnonymity	119
2.236	PidLidSharingBindingEntryId	120
2.237	PidLidSharingBrowseUrl	120
2.238	PidLidSharingCapabilities	120
2.239	PidLidSharingConfigurationUrl	121
2.240	PidLidSharingDataRangeEnd	121
2.241	PidLidSharingDataRangeStart	121
2.242	PidLidSharingDetail	122
2.243	PidLidSharingExtensionXml	122

2.244	PidLidSharingFilter	122
2.245	PidLidSharingFlags	123
2.246	PidLidSharingFlavor	123
2.247	PidLidSharingFolderEntryId	123
2.248	PidLidSharingIndexEntryId	124
2.249	PidLidSharingInitiatorEntryId	124
2.250	PidLidSharingInitiatorName	124
2.251	PidLidSharingInitiatorSmtip	125
2.252	PidLidSharingInstanceGuid	125
2.253	PidLidSharingLastAutoSyncTime	125
2.254	PidLidSharingLastSyncTime	126
2.255	PidLidSharingLocalComment	126
2.256	PidLidSharingLocalLastModificationTime	126
2.257	PidLidSharingLocalName	127
2.258	PidLidSharingLocalPath	127
2.259	PidLidSharingLocalStoreUid	127
2.260	PidLidSharingLocalType	128
2.261	PidLidSharingLocalUid	128
2.262	PidLidSharingOriginalMessageEntryId	128
2.263	PidLidSharingParentBindingEntryId	129
2.264	PidLidSharingParticipants	129
2.265	PidLidSharingPermissions	129
2.266	PidLidSharingProviderExtension	130
2.267	PidLidSharingProviderGuid	130
2.268	PidLidSharingProviderName	130
2.269	PidLidSharingProviderUrl	131
2.270	PidLidSharingRangeEnd	131
2.271	PidLidSharingRangeStart	131
2.272	PidLidSharingReciprocation	132
2.273	PidLidSharingRemoteByteSize	132
2.274	PidLidSharingRemoteComment	132
2.275	PidLidSharingRemoteCrc	133
2.276	PidLidSharingRemoteLastModificationTime	133
2.277	PidLidSharingRemoteMessageCount	133
2.278	PidLidSharingRemoteName	134
2.279	PidLidSharingRemotePass	134
2.280	PidLidSharingRemotePath	134
2.281	PidLidSharingRemoteStoreUid	135
2.282	PidLidSharingRemoteType	135
2.283	PidLidSharingRemoteUid	135
2.284	PidLidSharingRemoteUser	135
2.285	PidLidSharingRemoteVersion	136
2.286	PidLidSharingResponseTime	136
2.287	PidLidSharingResponseType	136
2.288	PidLidSharingRoamLog	137
2.289	PidLidSharingStart	137
2.290	PidLidSharingStatus	137
2.291	PidLidSharingStop	138
2.292	PidLidSharingSyncFlags	138
2.293	PidLidSharingSyncInterval	138
2.294	PidLidSharingTimeToLive	139
2.295	PidLidSharingTimeToLiveAuto	139
2.296	PidLidSharingWorkingHoursDays	139

2.297	PidLidSharingWorkingHoursEnd	140
2.298	PidLidSharingWorkingHoursStart	140
2.299	PidLidSharingWorkingHoursTimeZone	140
2.300	PidLidSideEffects	141
2.301	PidLidSingleBodyICal	141
2.302	PidLidSmartNoAttach	142
2.303	PidLidSpamOriginalFolder	142
2.304	PidLidStartRecurrenceDate	142
2.305	PidLidStartRecurrenceTime	143
2.306	PidLidTaskAcceptanceState	143
2.307	PidLidTaskAccepted	143
2.308	PidLidTaskActualEffort	144
2.309	PidLidTaskAssigner	144
2.310	PidLidTaskAssigners	144
2.311	PidLidTaskComplete	145
2.312	PidLidTaskCustomFlags	145
2.313	PidLidTaskDateCompleted	145
2.314	PidLidTaskDeadOccurrence	146
2.315	PidLidTaskDueDate	146
2.316	PidLidTaskEstimatedEffort	146
2.317	PidLidTaskFCreator	147
2.318	PidLidTaskFFixOffline	147
2.319	PidLidTaskFRecurring	147
2.320	PidLidTaskGlobalId	148
2.321	PidLidTaskHistory	148
2.322	PidLidTaskLastDelegate	148
2.323	PidLidTaskLastUpdate	149
2.324	PidLidTaskLastUser	149
2.325	PidLidTaskMode	149
2.326	PidLidTaskMultipleRecipients	150
2.327	PidLidTaskNoCompute	150
2.328	PidLidTaskOrdinal	150
2.329	PidLidTaskOwner	151
2.330	PidLidTaskOwnership	151
2.331	PidLidTaskRecurrence	151
2.332	PidLidTaskResetReminder	152
2.333	PidLidTaskRole	152
2.334	PidLidTaskStartDate	152
2.335	PidLidTaskState	153
2.336	PidLidTaskStatus	153
2.337	PidLidTaskStatusOnComplete	154
2.338	PidLidTaskUpdates	154
2.339	PidLidTaskVersion	154
2.340	PidLidTeamTask	155
2.341	PidLidTimeZone	155
2.342	PidLidTimeZoneDescription	155
2.343	PidLidTimeZoneStruct	156
2.344	PidLidToAttendeesString	156
2.345	PidLidToDoOrdinalDate	156
2.346	PidLidToDoSubOrdinal	157
2.347	PidLidToDoTitle	157
2.348	PidLidTrustRecipientHighlights	157
2.349	PidLidUseTnef	158

2.350	PidLidValidFlagStringProof	158
2.351	PidLidVerbResponse.....	158
2.352	PidLidVerbStream.....	159
2.353	PidLidWeddingAnniversaryLocal	159
2.354	PidLidWeekInterval.....	159
2.355	PidLidWhere	160
2.356	PidLidWorkAddress	160
2.357	PidLidWorkAddressCity.....	161
2.358	PidLidWorkAddressCountry	161
2.359	PidLidWorkAddressCountryCode	161
2.360	PidLidWorkAddressPostalCode.....	162
2.361	PidLidWorkAddressPostOfficeBox	162
2.362	PidLidWorkAddressState.....	162
2.363	PidLidWorkAddressStreet	163
2.364	PidLidYearInterval	163
2.365	PidLidYomiCompanyName	163
2.366	PidLidYomiFirstName	164
2.367	PidLidYomiLastName.....	164
2.368	PidNameAcceptLanguage	165
2.369	PidNameApplicationName	165
2.370	PidNameApproved	165
2.371	PidNameAttachmentMacContentType	166
2.372	PidNameAttachmentMacInfo	166
2.373	PidNameAudioNotes	166
2.374	PidNameAuthor	166
2.375	PidNameAutomaticSpeechRecognitionData	167
2.376	PidNameBcc	167
2.377	PidNameByteCount.....	167
2.378	PidNameCalendarAttendeeRole	168
2.379	PidNameCalendarBusystatus.....	168
2.380	PidNameCalendarContact	168
2.381	PidNameCalendarContactUrl	169
2.382	PidNameCalendarCreated	169
2.383	PidNameCalendarDescriptionUrl	169
2.384	PidNameCalendarDuration	170
2.385	PidNameCalendarExceptionDate.....	170
2.386	PidNameCalendarExceptionRule	171
2.387	PidNameCalendarGeoLatitude	171
2.388	PidNameCalendarGeoLongitude.....	171
2.389	PidNameCalendarInstanceType	172
2.390	PidNameCalendarIsOrganizer	172
2.391	PidNameCalendarLastModified	172
2.392	PidNameCalendarLocationUrl	173
2.393	PidNameCalendarMeetingStatus	173
2.394	PidNameCalendarMethod.....	173
2.395	PidNameCalendarProductId	174
2.396	PidNameCalendarRecurrenceIdRange.....	174
2.397	PidNameCalendarReminderOffset	174
2.398	PidNameCalendarResources.....	175
2.399	PidNameCalendarRsvp	175
2.400	PidNameCalendarSequence	175
2.401	PidNameCalendarTimeZone	176
2.402	PidNameCalendarTimeZoneId	176

2.403	PidNameCalendarTransparent	176
2.404	PidNameCalendarUid	177
2.405	PidNameCalendarVersion	177
2.406	PidNameCategory	177
2.407	PidNameCc	178
2.408	PidNameCharacterCount	178
2.409	PidNameComments	178
2.410	PidNameCompany	179
2.411	PidNameContactsAlternateRecipient	179
2.412	PidNameContactsCountry	179
2.413	PidNameContactsEmail1	180
2.414	PidNameContactsEmail2	180
2.415	PidNameContactsEmail3	180
2.416	PidNameContactsFileAs	181
2.417	PidNameContactsFileAsId	181
2.418	PidNameContactsHomeLatitude	181
2.419	PidNameContactsHomeLongitude	182
2.420	PidNameContactsHomeTimeZone	182
2.421	PidNameContactsMapUrl	182
2.422	PidNameContactsOtherCountryCode	183
2.423	PidNameContactsOtherPager	183
2.424	PidNameContactsOtherTimeZone	183
2.425	PidNameContactsProxyAddresses	184
2.426	PidNameContactsSecretaryUrl	184
2.427	PidNameContactsSourceUrl	184
2.428	PidNameContentBase	185
2.429	PidNameContentClass	185
2.430	PidNameContentDisposition	185
2.431	PidNameContentID	186
2.432	PidNameContentLanguage	186
2.433	PidNameContentLocation	186
2.434	PidNameContentTransferEncoding	187
2.435	PidNameContentType	187
2.436	PidNameControl	187
2.437	PidNameCreateDateTimeReadOnly	188
2.438	PidNameCrossReference	188
2.439	PidNameDavGetContentType	188
2.440	PidNameDavId	189
2.441	PidNameDavIsCollection	189
2.442	PidNameDavIsStructuredDocument	189
2.443	PidNameDavParentName	190
2.444	PidNameDavResourceType	190
2.445	PidNameDavSearchRequest	190
2.446	PidNameDavSearchType	191
2.447	PidNameDavUid	191
2.448	PidNameDisposition	191
2.449	PidNameDispositionNotificationTo	192
2.450	PidNameDistribution	192
2.451	PidNameDocumentParts	192
2.452	PidNameEditTime	193
2.453	PidNameExchangeIntendedBusyStatus	193
2.454	PidNameExchangeJunkEmailMoveStamp	193
2.455	PidNameExchangeModifyExceptionStructure	194

2.456	PidNameExchangeNoModifyExceptions	194
2.457	PidNameExchangePatternEnd	194
2.458	PidNameExchangePatternStart	195
2.459	PidNameExchangePublicFolderEmailAddress	195
2.460	PidNameExchangeReminderInterval	195
2.461	PidNameExchDatabaseSchema	196
2.462	PidNameExchDataExpectedContentClass	196
2.463	PidNameExchDataSchemaCollectionReference	196
2.464	PidNameExpires	197
2.465	PidNameExpiryDate	197
2.466	PidNameExtractedAddresses	197
2.467	PidNameExtractedContacts	198
2.468	PidNameExtractedEmails	198
2.469	PidNameExtractedMeetings	198
2.470	PidNameExtractedPhones	199
2.471	PidNameExtractedTasks	199
2.472	PidNameExtractedUrls	199
2.473	PidNameFollowupTo	199
2.474	PidNameFrom	200
2.475	PidNameHeadingPairs	200
2.476	PidNameHiddenCount	200
2.477	PidNameHttpmailCalendar	201
2.478	PidNameHttpmailCc	201
2.479	PidNameHttpmailContacts	201
2.480	PidNameHttpmailContentMediaType	202
2.481	PidNameHttpmailFrom	202
2.482	PidNameHttpmailFromEmail	202
2.483	PidNameHttpmailHtmlDescription	203
2.484	PidNameHttpmailOutbox	203
2.485	PidNameHttpmailSendMessage	203
2.486	PidNameHttpmailSubmitted	204
2.487	PidNameHttpmailTo	204
2.488	PidNameICalendarRecurrenceDate	204
2.489	PidNameICalendarRecurrenceRule	205
2.490	PidNameImportance	205
2.491	PidNameInReplyTo	205
2.492	PidNameInternetComment	206
2.493	PidNameInternetKeywords	206
2.494	PidNameInternetSubject	206
2.495	PidNameKeywords	207
2.496	PidNameLastAuthor	207
2.497	PidNameLastPrinted	207
2.498	PidNameLastSaveDateTime	208
2.499	PidNameLineCount	208
2.500	PidNameLines	208
2.501	PidNameLinksDirty	209
2.502	PidNameLocationUrl	209
2.503	PidNameMailSubmissionUri	209
2.504	PidNameManager	210
2.505	PidNameMessageId	210
2.506	PidNameMimeVersion	210
2.507	PidNameMultimediaClipCount	211
2.508	PidNameNewsgroups	211

2.509	PidNameNntpPostingHost	211
2.510	PidNameNoteCount	212
2.511	PidNameOMSAccountGuid	212
2.512	PidNameOMSMobileModel.....	212
2.513	PidNameOMSScheduleTime	212
2.514	PidNameOMSServiceType.....	213
2.515	PidNameOMSSourceType	213
2.516	PidNameOrganization.....	213
2.517	PidNameOriginalRecipient.....	214
2.518	PidNamePageCount	214
2.519	PidNameParagraphCount.....	214
2.520	PidNamePath	215
2.521	PidNamePhishingStamp.....	215
2.522	PidNamePostingVersion.....	215
2.523	PidNamePresentationFormat.....	216
2.524	PidNamePriority	216
2.525	PidNameQuarantineOriginalSender	216
2.526	PidNameReceived.....	217
2.527	PidNameReferences.....	217
2.528	PidNameRelayVersion	217
2.529	PidNameReplyBy	218
2.530	PidNameReplyTo	218
2.531	PidNameReturnPath.....	218
2.532	PidNameReturnReceiptTo	219
2.533	PidNameRevisionNumber	219
2.534	PidNameRightsManagementLicense	219
2.535	PidNameScale.....	220
2.536	PidNameSecurity.....	220
2.537	PidNameSender	220
2.538	PidNameSensitivity.....	221
2.539	PidNameSlideCount	221
2.540	PidNameSubject.....	221
2.541	PidNameSummary.....	222
2.542	PidNameTemplate	222
2.543	PidNameThreadIndex.....	222
2.544	PidNameThreadTopic.....	223
2.545	PidNameThumbnail.....	223
2.546	PidNameTitle	223
2.547	PidNameTo.....	224
2.548	PidNameWordCount.....	224
2.549	PidNameXCallId	224
2.550	PidNameXFaxNumberOfPages	225
2.551	PidNameXMailer.....	225
2.552	PidNameXMessageCompleted	225
2.553	PidNameXMessageFlag.....	226
2.554	PidNameXRequireProtectedPlayOnPhone	226
2.555	PidNameXSenderTelephoneNumber	226
2.556	PidNameXSharingBrowseUrl	226
2.557	PidNameXSharingCapabilities.....	227
2.558	PidNameXSharingConfigUrl.....	227
2.559	PidNameXSharingExendedCaps	227
2.560	PidNameXSharingFlavor	228
2.561	PidNameXSharingInstanceGuid	228

2.562	PidNameXSharingLocalType	228
2.563	PidNameXSharingProviderGuid	229
2.564	PidNameXSharingProviderName	229
2.565	PidNameXSharingProviderUrl	229
2.566	PidNameXSharingRemoteName	229
2.567	PidNameXSharingRemotePath	230
2.568	PidNameXSharingRemoteStoreUid	230
2.569	PidNameXSharingRemoteType	230
2.570	PidNameXSharingRemoteUid	231
2.571	PidNameXUnifiedMessagingPartnerAssignedId	231
2.572	PidNameXUnifiedMessagingPartnerContent	231
2.573	PidNameXUnifiedMessagingPartnerContext	232
2.574	PidNameXUnifiedMessagingPartnerStatus	232
2.575	PidNameXUnsent	232
2.576	PidNameXVoiceMessageAttachmentOrder	233
2.577	PidNameXVoiceMessageDuration	233
2.578	PidNameXVoiceMessageSenderName	233
2.579	PidTagAccess	234
2.580	PidTagAccessControlListData	234
2.581	PidTagAccessLevel	234
2.582	PidTagAccount	234
2.583	PidTagAdditionalRenEntryIds	235
2.584	PidTagAdditionalRenEntryIdsEx	235
2.585	PidTagAddressBookAuthorizedSenders	235
2.586	PidTagAddressBookContainerId	236
2.587	PidTagAddressBookDeliveryContentLength	236
2.588	PidTagAddressBookDisplayNamePrintable	236
2.589	PidTagAddressBookDisplayTypeExtended	237
2.590	PidTagAddressBookDistributionListExternalMemberCount	237
2.591	PidTagAddressBookDistributionListMemberCount	237
2.592	PidTagAddressBookDistributionListMemberSubmitAccepted	238
2.593	PidTagAddressBookDistributionListMemberSubmitRejected	238
2.594	PidTagAddressBookDistributionListRejectMessagesFromDLMembers	238
2.595	PidTagAddressBookEntryId	239
2.596	PidTagAddressBookExtensionAttribute1	239
2.597	PidTagAddressBookExtensionAttribute2	239
2.598	PidTagAddressBookExtensionAttribute3	239
2.599	PidTagAddressBookExtensionAttribute4	240
2.600	PidTagAddressBookExtensionAttribute5	240
2.601	PidTagAddressBookExtensionAttribute6	240
2.602	PidTagAddressBookExtensionAttribute7	241
2.603	PidTagAddressBookExtensionAttribute8	241
2.604	PidTagAddressBookExtensionAttribute9	241
2.605	PidTagAddressBookExtensionAttribute10	242
2.606	PidTagAddressBookExtensionAttribute11	242
2.607	PidTagAddressBookExtensionAttribute12	242
2.608	PidTagAddressBookExtensionAttribute13	243
2.609	PidTagAddressBookExtensionAttribute14	243
2.610	PidTagAddressBookExtensionAttribute15	243
2.611	PidTagAddressBookFolderPathname	243
2.612	PidTagAddressBookHierarchicalChildDepartments	244
2.613	PidTagAddressBookHierarchicalDepartmentMembers	244
2.614	PidTagAddressBookHierarchicalIsHierarchicalGroup	244

2.615	PidTagAddressBookHierarchicalParentDepartment	245
2.616	PidTagAddressBookHierarchicalRootDepartment	245
2.617	PidTagAddressBookHierarchicalShowInDepartments	245
2.618	PidTagAddressBookHomeMessageDatabase	246
2.619	PidTagAddressBookIsMaster	246
2.620	PidTagAddressBookIsMemberOfDistributionList	246
2.621	PidTagAddressBookManageDistributionList	247
2.622	PidTagAddressBookManager	247
2.623	PidTagAddressBookManagerDistinguishedName	247
2.624	PidTagAddressBookMember	247
2.625	PidTagAddressBookMessageId	248
2.626	PidTagAddressBookModerationEnabled	248
2.627	PidTagAddressBookNetworkAddress	248
2.628	PidTagAddressBookObjectDistinguishedName	249
2.629	PidTagAddressBookObjectGuid	249
2.630	PidTagAddressBookOrganizationalUnitRootDistinguishedName	249
2.631	PidTagAddressBookOwner	250
2.632	PidTagAddressBookOwnerBackLink	250
2.633	PidTagAddressBookParentEntryId	250
2.634	PidTagAddressBookPhoneticCompanyName	250
2.635	PidTagAddressBookPhoneticDepartmentName	251
2.636	PidTagAddressBookPhoneticDisplayName	251
2.637	PidTagAddressBookPhoneticGivenName	252
2.638	PidTagAddressBookPhoneticSurname	252
2.639	PidTagAddressBookProxyAddresses	252
2.640	PidTagAddressBookPublicDelegates	253
2.641	PidTagAddressBookReports	253
2.642	PidTagAddressBookRoomCapacity	253
2.643	PidTagAddressBookRoomContainers	253
2.644	PidTagAddressBookRoomDescription	254
2.645	PidTagAddressBookSenderHintTranslations	254
2.646	PidTagAddressBookSeniorityIndex	254
2.647	PidTagAddressBookTargetAddress	255
2.648	PidTagAddressBookUnauthorizedSenders	255
2.649	PidTagAddressBookX509Certificate	255
2.650	PidTagAddressType	256
2.651	PidTagAlternateRecipientAllowed	256
2.652	PidTagAnr	256
2.653	PidTagArchiveDate	257
2.654	PidTagArchivePeriod	257
2.655	PidTagArchiveTag	257
2.656	PidTagAssistant	257
2.657	PidTagAssistantTelephoneNumber	258
2.658	PidTagAssociated	258
2.659	PidTagAttachAdditionalInformation	258
2.660	PidTagAttachContentBase	259
2.661	PidTagAttachContentId	259
2.662	PidTagAttachContentLocation	259
2.663	PidTagAttachDataBinary	260
2.664	PidTagAttachDataObject	260
2.665	PidTagAttachEncoding	260
2.666	PidTagAttachExtension	261
2.667	PidTagAttachFilename	261

2.668	PidTagAttachFlags	261
2.669	PidTagAttachLongFilename	262
2.670	PidTagAttachLongPathname	262
2.671	PidTagAttachmentContactPhoto	262
2.672	PidTagAttachmentFlags	263
2.673	PidTagAttachmentHidden	263
2.674	PidTagAttachmentLinkId	263
2.675	PidTagAttachMethod	264
2.676	PidTagAttachMimeType	264
2.677	PidTagAttachNumber	264
2.678	PidTagAttachPathname	265
2.679	PidTagAttachPayloadClass	265
2.680	PidTagAttachPayloadProviderGuidString	265
2.681	PidTagAttachRendering	266
2.682	PidTagAttachSize	266
2.683	PidTagAttachTag	266
2.684	PidTagAttachTransportName	267
2.685	PidTagAttributeHidden	267
2.686	PidTagAttributeReadOnly	267
2.687	PidTagAutoForwarded	268
2.688	PidTagAutoForwardComment	268
2.689	PidTagAutoResponseSuppress	268
2.690	PidTagBirthday	268
2.691	PidTagBlockStatus	269
2.692	PidTagBody	269
2.693	PidTagBodyContentId	269
2.694	PidTagBodyContentLocation	270
2.695	PidTagBodyHtml	270
2.696	PidTagBusiness2TelephoneNumber	270
2.697	PidTagBusiness2TelephoneNumbers	271
2.698	PidTagBusinessFaxNumber	271
2.699	PidTagBusinessHomePage	271
2.700	PidTagBusinessTelephoneNumber	272
2.701	PidTagCallbackTelephoneNumber	272
2.702	PidTagCallId	272
2.703	PidTagCarTelephoneNumber	273
2.704	PidTagCdoRecurrenceid	273
2.705	PidTagChangeKey	273
2.706	PidTagChangeNumber	274
2.707	PidTagChildrensNames	274
2.708	PidTagClientActions	274
2.709	PidTagClientSubmitTime	275
2.710	PidTagCodePageId	275
2.711	PidTagComment	275
2.712	PidTagCompanyMainTelephoneNumber	276
2.713	PidTagCompanyName	276
2.714	PidTagComputerNetworkName	276
2.715	PidTagConflictEntryId	277
2.716	PidTagContainerClass	277
2.717	PidTagContainerContents	277
2.718	PidTagContainerFlags	278
2.719	PidTagContainerHierarchy	278
2.720	PidTagContentCount	278

2.721	PidTagContentFilterSpamConfidenceLevel.....	278
2.722	PidTagContentUnreadCount	279
2.723	PidTagConversationId	279
2.724	PidTagConversationIndex	279
2.725	PidTagConversationIndexTracking	280
2.726	PidTagConversationTopic.....	280
2.727	PidTagCountry	280
2.728	PidTagCreationTime.....	281
2.729	PidTagCreatorEntryId	281
2.730	PidTagCreatorName.....	281
2.731	PidTagCurrentDraftEntryId	282
2.732	PidTagCustomerId	282
2.733	PidTagDamBackPatched	282
2.734	PidTagDamOriginalEntryId.....	283
2.735	PidTagDefaultPostMessageClass	283
2.736	PidTagDeferredActionMessageOriginalEntryId	283
2.737	PidTagDeferredDeliveryTime.....	283
2.738	PidTagDeferredSendNumber	284
2.739	PidTagDeferredSendTime	284
2.740	PidTagDeferredSendUnits	284
2.741	PidTagDelegatedByRule	285
2.742	PidTagDelegateFlags.....	285
2.743	PidTagDeleteAfterSubmit	285
2.744	PidTagDeletedOn.....	285
2.745	PidTagDepartmentName	286
2.746	PidTagDepth	286
2.747	PidTagDisplayBcc	286
2.748	PidTagDisplayCc.....	287
2.749	PidTagDisplayName	287
2.750	PidTagDisplayNamePrefix	287
2.751	PidTagDisplayTo.....	288
2.752	PidTagDisplayType	288
2.753	PidTagDisplayTypeEx	288
2.754	PidTagEmailAddress	289
2.755	PidTagEndDate	289
2.756	PidTagEntryId	289
2.757	PidTagExceptionEndTime.....	290
2.758	PidTagExceptionReplaceTime	290
2.759	PidTagExceptionStartTime	290
2.760	PidTagExchangeNTSecurityDescriptor	291
2.761	PidTagExpiryNumber	291
2.762	PidTagExpiryTime.....	291
2.763	PidTagExpiryUnits	292
2.764	PidTagExtendedFolderFlags	292
2.765	PidTagExtendedRuleMessageActions	292
2.766	PidTagExtendedRuleMessageCondition	293
2.767	PidTagExtendedRuleSizeLimit	293
2.768	PidTagFaxNumberOfPages	293
2.769	PidTagFlagCompleteTime	294
2.770	PidTagFlagStatus.....	294
2.771	PidTagFlatUrlName	294
2.772	PidTagFolderAssociatedContents	295
2.773	PidTagFolderId.....	295

2.774	PidTagFolderType	295
2.775	PidTagFollowupIcon	296
2.776	PidTagFreeBusyCountMonths	296
2.777	PidTagFreeBusyEntryIds	296
2.778	PidTagFreeBusyMessageEmailAddress	297
2.779	PidTagFreeBusyPublishEnd	297
2.780	PidTagFreeBusyPublishStart	297
2.781	PidTagFreeBusyRangeTimestamp	297
2.782	PidTagFtpSite	298
2.783	PidTagGatewayNeedsToRefresh	298
2.784	PidTagGender	298
2.785	PidTagGeneration	299
2.786	PidTagGivenName	299
2.787	PidTagGovernmentIdNumber	299
2.788	PidTagHasAttachments	300
2.789	PidTagHasDeferredActionMessages	300
2.790	PidTagHasNamedProperties	300
2.791	PidTagHasRules	300
2.792	PidTagHierarchyChangeNumber	301
2.793	PidTagHobbies	301
2.794	PidTagHome2TelephoneNumber	301
2.795	PidTagHome2TelephoneNumbers	302
2.796	PidTagHomeAddressCity	302
2.797	PidTagHomeAddressCountry	302
2.798	PidTagHomeAddressPostalCode	303
2.799	PidTagHomeAddressPostOfficeBox	303
2.800	PidTagHomeAddressStateOrProvince	303
2.801	PidTagHomeAddressStreet	304
2.802	PidTagHomeFaxNumber	304
2.803	PidTagHomeTelephoneNumber	304
2.804	PidTagHtml	305
2.805	PidTagICalendarEndTime	305
2.806	PidTagICalendarReminderNextTime	305
2.807	PidTagICalendarStartTime	306
2.808	PidTagIconIndex	306
2.809	PidTagImportance	306
2.810	PidTagInConflict	307
2.811	PidTagInitialDetailsPane	307
2.812	PidTagInitials	307
2.813	PidTagInReplyToId	308
2.814	PidTagInstanceKey	308
2.815	PidTagInstanceNum	308
2.816	PidTagInstID	308
2.817	PidTagInternetArticleNumber	309
2.818	PidTagInternetCodepage	309
2.819	PidTagInternetMailOverrideFormat	309
2.820	PidTagInternetMessageId	310
2.821	PidTagInternetReferences	310
2.822	PidTagIpmAppointmentEntryId	310
2.823	PidTagIpmContactEntryId	311
2.824	PidTagIpmDraftsEntryId	311
2.825	PidTagIpmJournalEntryId	311
2.826	PidTagIpmNoteEntryId	312

2.827	PidTagIpmTaskEntryId	312
2.828	PidTagIsdnNumber	312
2.829	PidTagJunkAddRecipientsToSafeSendersList	313
2.830	PidTagJunkIncludeContacts	313
2.831	PidTagJunkPermanentlyDelete	313
2.832	PidTagJunkPhishingEnableLinks	313
2.833	PidTagJunkThreshold	314
2.834	PidTagKeyword	314
2.835	PidTagLanguage	314
2.836	PidTagLastModificationTime	315
2.837	PidTagLastModifierEntryId	315
2.838	PidTagLastModifierName	315
2.839	PidTagLastVerbExecuted	316
2.840	PidTagLastVerbExecutionTime	316
2.841	PidTagListHelp	316
2.842	PidTagListSubscribe	317
2.843	PidTagListUnsubscribe	317
2.844	PidTagLocalCommitTime	317
2.845	PidTagLocaleId	318
2.846	PidTagLocality	318
2.847	PidTagLocation	318
2.848	PidTagMailboxOwnerEntryId	319
2.849	PidTagMailboxOwnerName	319
2.850	PidTagManagerName	319
2.851	PidTagMappingSignature	320
2.852	PidTagMaximumSubmitMessageSize	320
2.853	PidTagMemberId	320
2.854	PidTagMemberName	320
2.855	PidTagMemberRights	321
2.856	PidTagMessageAttachments	321
2.857	PidTagMessageCcMe	321
2.858	PidTagMessageClass	322
2.859	PidTagMessageCodepage	322
2.860	PidTagMessageDeliveryTime	322
2.861	PidTagMessageEditorFormat	323
2.862	PidTagMessageFlags	323
2.863	PidTagMessageHandlingSystemCommonName	323
2.864	PidTagMessageLocaleId	324
2.865	PidTagMessageRecipientMe	324
2.866	PidTagMessageRecipients	324
2.867	PidTagMessageSize	325
2.868	PidTagMessageSizeExtended	325
2.869	PidTagMessageStatus	325
2.870	PidTagMessageSubmissionId	326
2.871	PidTagMessageToMe	326
2.872	PidTagMid	326
2.873	PidTagMiddleName	327
2.874	PidTagMimeSkeleton	327
2.875	PidTagMobileTelephoneNumber	327
2.876	PidTagNativeBody	328
2.877	PidTagNextSendAcct	328
2.878	PidTagNickname	328
2.879	PidTagNonReceiptNotificationRequested	329

2.880	PidTagNormalizedSubject	329
2.881	PidTagNormalMessageSize	329
2.882	PidTagObjectType	330
2.883	PidTagOfficeLocation.....	330
2.884	PidTagOfflineAddressBookContainerGuid	330
2.885	PidTagOfflineAddressBookDistinguishedName	331
2.886	PidTagOfflineAddressBookMessageClass	331
2.887	PidTagOfflineAddressBookName	331
2.888	PidTagOfflineAddressBookSequence.....	331
2.889	PidTagOfflineAddressBookTruncatedProperties	332
2.890	PidTagOrdinalMost.....	332
2.891	PidTagOrganizationalIdNumber	332
2.892	PidTagOriginalAuthorEntryId.....	333
2.893	PidTagOriginalAuthorName	333
2.894	PidTagOriginalDeliveryTime	333
2.895	PidTagOriginalDisplayBcc	333
2.896	PidTagOriginalDisplayCc.....	334
2.897	PidTagOriginalDisplayTo.....	334
2.898	PidTagOriginalEntryId	334
2.899	PidTagOriginalMessageClass	335
2.900	PidTagOriginalMessageId.....	335
2.901	PidTagOriginalSenderAddressType.....	335
2.902	PidTagOriginalSenderEmailAddress.....	336
2.903	PidTagOriginalSenderEntryId	336
2.904	PidTagOriginalSenderName	336
2.905	PidTagOriginalSenderSearchKey.....	337
2.906	PidTagOriginalSensitivity	337
2.907	PidTagOriginalSentRepresentingAddressType.....	337
2.908	PidTagOriginalSentRepresentingEmailAddress.....	337
2.909	PidTagOriginalSentRepresentingEntryId	338
2.910	PidTagOriginalSentRepresentingName.....	338
2.911	PidTagOriginalSentRepresentingSearchKey.....	338
2.912	PidTagOriginalSubject	339
2.913	PidTagOriginalSubmitTime.....	339
2.914	PidTagOriginatorDeliveryReportRequested	339
2.915	PidTagOriginatorNonDeliveryReportRequested	340
2.916	PidTagOscSyncEnabled	340
2.917	PidTagOtherAddressCity	340
2.918	PidTagOtherAddressCountry	341
2.919	PidTagOtherAddressPostalCode	341
2.920	PidTagOtherAddressPostOfficeBox	341
2.921	PidTagOtherAddressStateOrProvince.....	342
2.922	PidTagOtherAddressStreet.....	342
2.923	PidTagOtherTelephoneNumber	342
2.924	PidTagOutOfOfficeState.....	343
2.925	PidTagOwnerAppointmentId	343
2.926	PidTagPagerTelephoneNumber.....	343
2.927	PidTagParentEntryId	344
2.928	PidTagParentFolderId.....	344
2.929	PidTagParentKey	344
2.930	PidTagParentSourceKey	345
2.931	PidTagPersonalHomePage.....	345
2.932	PidTagPolicyTag	345

2.933	PidTagPostalAddress	345
2.934	PidTagPostalCode	346
2.935	PidTagPostOfficeBox	346
2.936	PidTagPredecessorChangeList	346
2.937	PidTagPrimaryFaxNumber	347
2.938	PidTagPrimarySendAccount	347
2.939	PidTagPrimaryTelephoneNumber	347
2.940	PidTagPriority	348
2.941	PidTagProcessed	348
2.942	PidTagProfession	348
2.943	PidTagProhibitReceiveQuota	349
2.944	PidTagProhibitSendQuota	349
2.945	PidTagProviderSubmitTime	349
2.946	PidTagPublicFolderAdministrativeDescription	350
2.947	PidTagPublicFolderProxy	350
2.948	PidTagPurportedSenderDomain	350
2.949	PidTagRadioTelephoneNumber	351
2.950	PidTagRead	351
2.951	PidTagReadReceiptAddressType	351
2.952	PidTagReadReceiptEmailAddress	352
2.953	PidTagReadReceiptEntryId	352
2.954	PidTagReadReceiptName	352
2.955	PidTagReadReceiptRequested	352
2.956	PidTagReadReceiptSearchKey	353
2.957	PidTagReceivedByAddressType	353
2.958	PidTagReceivedByEmailAddress	353
2.959	PidTagReceivedByEntryId	354
2.960	PidTagReceivedByName	354
2.961	PidTagReceivedBySearchKey	354
2.962	PidTagReceivedRepresentingAddressType	354
2.963	PidTagReceivedRepresentingEmailAddress	355
2.964	PidTagReceivedRepresentingEntryId	355
2.965	PidTagReceivedRepresentingName	355
2.966	PidTagReceivedRepresentingSearchKey	356
2.967	PidTagRecipientDisplayName	356
2.968	PidTagRecipientEntryId	356
2.969	PidTagRecipientFlags	357
2.970	PidTagRecipientOrder	357
2.971	PidTagRecipientProposed	357
2.972	PidTagRecipientProposedEndTime	358
2.973	PidTagRecipientProposedStartTime	358
2.974	PidTagRecipientReassignmentProhibited	358
2.975	PidTagRecipientResourceState	358
2.976	PidTagRecipientTrackStatus	359
2.977	PidTagRecipientTrackStatusTime	359
2.978	PidTagRecipientType	359
2.979	PidTagRecordKey	360
2.980	PidTagReferredByName	360
2.981	PidTagRemindersOnlineEntryId	360
2.982	PidTagRenderingPosition	361
2.983	PidTagReplyRecipientEntries	361
2.984	PidTagReplyRecipientNames	361
2.985	PidTagReplyRequested	362

2.986	PidTagReplyTemplateId	362
2.987	PidTagReplyTime	362
2.988	PidTagReportDisposition	362
2.989	PidTagReportDispositionMode	363
2.990	PidTagReportEntryId	363
2.991	PidTagReportName	363
2.992	PidTagReportSearchKey	364
2.993	PidTagReportTag	364
2.994	PidTagReportText	364
2.995	PidTagReportTime	364
2.996	PidTagResolveMethod	365
2.997	PidTagResponseRequested	365
2.998	PidTagResponsibility	365
2.999	PidTagRetentionDate	366
2.1000	PidTagRetentionFlags	366
2.1001	PidTagRetentionPeriod	366
2.1002	PidTagRights	367
2.1003	PidTagRoamingDatatypes	367
2.1004	PidTagRoamingDictionary	367
2.1005	PidTagRoamingXmlStream	367
2.1006	PidTagRowid	368
2.1007	PidTagRowType	368
2.1008	PidTagRtfCompressed	368
2.1009	PidTagRtfInSync	369
2.1010	PidTagRuleActionNumber	369
2.1011	PidTagRuleActions	369
2.1012	PidTagRuleActionType	370
2.1013	PidTagRuleCondition	370
2.1014	PidTagRuleError	370
2.1015	PidTagRuleFolderEntryId	370
2.1016	PidTagRuleId	371
2.1017	PidTagRuleIds	371
2.1018	PidTagRuleLevel	371
2.1019	PidTagRuleMessageLevel	372
2.1020	PidTagRuleMessageName	372
2.1021	PidTagRuleMessageProvider	372
2.1022	PidTagRuleMessageProviderData	373
2.1023	PidTagRuleMessageSequence	373
2.1024	PidTagRuleMessageState	373
2.1025	PidTagRuleMessageUserFlags	374
2.1026	PidTagRuleName	374
2.1027	PidTagRuleProvider	374
2.1028	PidTagRuleProviderData	374
2.1029	PidTagRuleSequence	375
2.1030	PidTagRuleState	375
2.1031	PidTagRuleUserFlags	375
2.1032	PidTagRwRulesStream	376
2.1033	PidTagScheduleInfoAppointmentTombstone	376
2.1034	PidTagScheduleInfoAutoAcceptAppointments	376
2.1035	PidTagScheduleInfoDelegateEntryIds	377
2.1036	PidTagScheduleInfoDelegateNames	377
2.1037	PidTagScheduleInfoDelegateNamesW	377
2.1038	PidTagScheduleInfoDelegatorWantsCopy	377

2.1039	PidTagScheduleInfoDelegatorWantsInfo	378
2.1040	PidTagScheduleInfoDisallowOverlappingAppts	378
2.1041	PidTagScheduleInfoDisallowRecurringAppts	378
2.1042	PidTagScheduleInfoDontMailDelegates	379
2.1043	PidTagScheduleInfoFreeBusy	379
2.1044	PidTagScheduleInfoFreeBusyAway	379
2.1045	PidTagScheduleInfoFreeBusyBusy	380
2.1046	PidTagScheduleInfoFreeBusyMerged	380
2.1047	PidTagScheduleInfoFreeBusyTentative	380
2.1048	PidTagScheduleInfoMonthsAway	380
2.1049	PidTagScheduleInfoMonthsBusy	381
2.1050	PidTagScheduleInfoMonthsMerged	381
2.1051	PidTagScheduleInfoMonthsTentative	381
2.1052	PidTagScheduleInfoResourceType	382
2.1053	PidTagSchedulePlusFreeBusyEntryId	382
2.1054	PidTagScriptData	382
2.1055	PidTagSearchFolderDefinition	382
2.1056	PidTagSearchFolderEfpFlags	383
2.1057	PidTagSearchFolderExpiration	383
2.1058	PidTagSearchFolderId	383
2.1059	PidTagSearchFolderLastUsed	384
2.1060	PidTagSearchFolderRecreateInfo	384
2.1061	PidTagSearchFolderStorageType	384
2.1062	PidTagSearchFolderTag	384
2.1063	PidTagSearchFolderTemplateId	385
2.1064	PidTagSearchKey	385
2.1065	PidTagSecurityDescriptor	385
2.1066	PidTagSecurityDescriptorAsXml	386
2.1067	PidTagSelectable	386
2.1068	PidTagSenderAddressType	386
2.1069	PidTagSenderEmailAddress	387
2.1070	PidTagSenderEntryId	387
2.1071	PidTagSenderIdStatus	387
2.1072	PidTagSenderName	388
2.1073	PidTagSenderSearchKey	388
2.1074	PidTagSenderSmtpAddress	388
2.1075	PidTagSenderTelephoneNumber	389
2.1076	PidTagSendInternetEncoding	389
2.1077	PidTagSendRichInfo	389
2.1078	PidTagSensitivity	390
2.1079	PidTagSentMailSvrEID	390
2.1080	PidTagSentRepresentingAddressType	390
2.1081	PidTagSentRepresentingEmailAddress	391
2.1082	PidTagSentRepresentingEntryId	391
2.1083	PidTagSentRepresentingFlags	391
2.1084	PidTagSentRepresentingName	392
2.1085	PidTagSentRepresentingSearchKey	392
2.1086	PidTagSmtpAddress	392
2.1087	PidTagSortLocaleId	393
2.1088	PidTagSourceKey	393
2.1089	PidTagSpokenName	393
2.1090	PidTagSpouseName	394
2.1091	PidTagStartDate	394

2.1092	PidTagStartDateEtc.....	394
2.1093	PidTagStateOrProvince.....	395
2.1094	PidTagStoreEntryId.....	395
2.1095	PidTagStoreState.....	395
2.1096	PidTagStoreSupportMask.....	396
2.1097	PidTagStreetAddress.....	396
2.1098	PidTagSubfolder.....	396
2.1099	PidTagSubfolders.....	396
2.1100	PidTagSubject.....	397
2.1101	PidTagSubjectPrefix.....	397
2.1102	PidTagSurname.....	398
2.1103	PidTagSwappedToDoData.....	398
2.1104	PidTagSwappedToDoStore.....	398
2.1105	PidTagTargetEntryId.....	399
2.1106	PidTagTelecommunicationsDeviceForDeafTelephoneNumber.....	399
2.1107	PidTagTelexNumber.....	399
2.1108	PidTagTemplateData.....	400
2.1109	PidTagTemplateid.....	400
2.1110	PidTagTemporaryDefaultDocument.....	400
2.1111	PidTagTextAttachmentCharset.....	400
2.1112	PidTagThumbnailPhoto.....	401
2.1113	PidTagTitle.....	401
2.1114	PidTagTnefCorrelationKey.....	401
2.1115	PidTagToDoItemFlags.....	402
2.1116	PidTagTransmittableDisplayName.....	402
2.1117	PidTagTransportMessageHeaders.....	402
2.1118	PidTagTrustSender.....	403
2.1119	PidTagUrlCompName.....	403
2.1120	PidTagUrlCompNameSet.....	403
2.1121	PidTagUrlName.....	404
2.1122	PidTagUserCertificate.....	404
2.1123	PidTagUserEntryId.....	404
2.1124	PidTagUserX509Certificate.....	405
2.1125	PidTagViewDescriptorBinary.....	405
2.1126	PidTagViewDescriptorName.....	405
2.1127	PidTagViewDescriptorStrings.....	405
2.1128	PidTagViewDescriptorVersion.....	406
2.1129	PidTagVoiceMessageAttachmentOrder.....	406
2.1130	PidTagVoiceMessageDuration.....	406
2.1131	PidTagVoiceMessageSenderName.....	407
2.1132	PidTagWeddingAnniversary.....	407
2.1133	PidTagWlinkAddressBookEID.....	407
2.1134	PidTagWlinkAddressBookStoreEID.....	408
2.1135	PidTagWlinkCalendarColor.....	408
2.1136	PidTagWlinkClientID.....	408
2.1137	PidTagWlinkEntryId.....	408
2.1138	PidTagWlinkFlags.....	409
2.1139	PidTagWlinkFolderType.....	409
2.1140	PidTagWlinkGroupClsid.....	409
2.1141	PidTagWlinkGroupHeaderID.....	410
2.1142	PidTagWlinkGroupName.....	410
2.1143	PidTagWlinkOrdinal.....	410
2.1144	PidTagWlinkRecordKey.....	410

2.1145	PidTagWlinkROGroupType	411
2.1146	PidTagWlinkSaveStamp	411
2.1147	PidTagWlinkSection	411
2.1148	PidTagWlinkStoreEntryId	412
2.1149	PidTagWlinkType	412
3	Structure Examples	413
4	Security Considerations.....	414
5	Appendix A: Product Behavior	415
6	Change Tracking.....	416
7	Index	422

Preliminary

1 Introduction

The Exchange Server Protocols Master Property List provides implementers with a single source of information about all the properties that are described by the specifications that comprise the Exchange Server Protocols documentation. If a property is not described by the specifications included in the Exchange Server Protocols documentation, it is not included in this document.

The criteria for including a property in the Exchange Server Protocols documentation are that it is set by a client in order to affect server behavior, or that it is set by a server in order to affect client behavior. Properties that are merely stored by the server on behalf of the client, or generated by the server for its own use and ignored by the client, are not necessarily documented. As a result, the properties that are included in the Exchange Server Protocols documentation, and therefore this document, are the critical **Message object** properties used for communication between clients and servers.

This document provides implementers with a convenient catalog of all these critical properties, a source of navigation to the individual technical specifications that describe these properties in detail, and a resource for additional helpful property information that is unique to this document.

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. All other sections and examples in this specification are informative.

1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

- 8.3 name**
- ambiguous name resolution (ANR)**
- Augmented Backus-Naur Form (ABNF)**
- class**
- common name (CN)**
- Coordinated Universal Time (UTC)**
- cyclic redundancy check (CRC)**
- distinguished name (DN)**
- domain**
- flags**
- GUID**
- Hypertext Transfer Protocol (HTTP)**
- name service provider interface (NSPI)**
- property set**
- resource**
- Transmission Control Protocol (TCP)**
- Unicode**
- XML**

The following terms are defined in [\[MS-OXGLOS\]](#):

- address book container**
- Address Book object**
- address list**
- address type**
- alias**
- Appointment object**
- Attachment object**

base64 encoding
blind carbon copy (Bcc) recipient
body part
calendar
Calendar folder
Calendar object
carbon copy (Cc) recipient
contents table
conversation
conversation action
counter proposal
Deferred Action Message (DAM)
delivery receipt
departmental group
display name
display template
distribution list
Document object
double-byte character set (DBCS)
E-mail object
EntryID
Exception Embedded Message object
Exception object
File Transfer Protocol (FTP)
folder associated information (FAI)
Folder object
free/busy status
Global Address List (GAL)
group header
Hypertext Markup Language (HTML)
instance
Integrated Services Digital Network (ISDN)
Journal object
locale
Logon object
long ID (LID)
mail tip
mail user
mailbox
meeting
Meeting object
meeting request
Meeting Request object
Meeting Response object
Meeting Update object
Meeting Workspace
meeting-related object
message body
message class
Message object
Messaging Application Programming Interface (MAPI)
messaging object
Multipurpose Internet Mail Extensions (MIME)
named property
navigation shortcut

Network News Transfer Protocol (NNTP)
non-Unicode
Note object
offline address book (OAB)
optional attendee
organizer
orphan instance
Out of Office (OOF)
Outbox folder
Permanent Entry ID
permission
phishing
plain text
primary recipient
property ID
property name
property type
public folder
read receipt
recipient
recipient table
recurrence pattern
Recurring Calendar object
recurring series
recurring task
reminder
Resource object
retention tag
Rich Text Format (RTF)
rights-managed e-mail message
Root folder
ROP buffer
Sent Items folder
Server object
Short Message Service (SMS)
signal time
Simple Mail Transfer Protocol (SMTP)
soft delete
spam
spam filter
special folder
store
tagged property
Task object
task request
Transport Neutral Encapsulation Format (TNEF)
Uniform Resource Identifier (URI)
Uniform Resource Locator (URL)
unsendable attendee
Use License
Web Distributed Authoring and Versioning Protocol (WebDAV)
X500 DN
XML document

The following terms are specific to this document:

MAY, SHOULD, MUST, SHOULD NOT, MUST NOT: These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact dochelp@microsoft.com. We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[ISO/IEC8802-3] ISO/IEC, "Information technology -- Telecommunications and information exchange between systems -- Local and metropolitan area networks -- Specific requirements -- Part 3", Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, ISO/IEC 8802-3:2000, http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=31002

[MS-NSPI] Microsoft Corporation, "[Name Service Provider Interface \(NSPI\) Protocol Specification](#)".

[MS-OXABREF] Microsoft Corporation, "[Address Book Name Service Provider Interface \(NSPI\) Referral Protocol Specification](#)".

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Algorithm](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCEXT] Microsoft Corporation, "[Client Extension Message Object Protocol Specification](#)".

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol Specification](#)".

[MS-OXCFXICS] Microsoft Corporation, "[Bulk Data Transfer Protocol Specification](#)".

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Algorithm](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC2822 and MIME to E-Mail Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol Specification](#)".

[MS-OXCPerm] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol Specification](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol Specification](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol Specification](#)".

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol Specification](#)".

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol Specification](#)".

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol Specification](#)".

[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol Specification](#)".

[MS-OXLDAP] Microsoft Corporation, "[Lightweight Directory Access Protocol \(LDAP\) Version 3 Extensions](#)".

[MS-OXMSG] Microsoft Corporation, "[Outlook Item \(.msg\) File Format](#)".

[MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol Specification](#)".

[MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol Specification](#)".

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol Specification](#)".

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol Specification](#)".

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol Specification](#)".

[MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol Specification](#)".

[MS-OXODOC] Microsoft Corporation, "[Document Object Protocol Specification](#)".

[MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol Specification](#)".

[MS-OXOJRN] Microsoft Corporation, "[Journal Object Protocol Specification](#)".

[MS-OXOMSG] Microsoft Corporation, "[E-Mail Object Protocol Specification](#)".

[MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol Specification](#)".

[MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol Specification](#)".

[MS-OXOPOST] Microsoft Corporation, "[Post Object Protocol Specification](#)".

[MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol Specification](#)".

[MS-OXORMMS] Microsoft Corporation, "[Rights-Managed E-Mail Object Protocol Specification](#)".

[MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol Specification](#)".

[MS-OXORULE] Microsoft Corporation, "[E-Mail Rules Protocol Specification](#)".

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol Specification](#)".

[MS-OXOSMIME] Microsoft Corporation, "[S/MIME E-Mail Object Algorithm](#)".

[MS-OXOSMMS] Microsoft Corporation, "[Short Message Service \(SMS\) and Multimedia Messaging Service \(MMS\) Object Protocol Specification](#)".

[MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol Specification](#)".

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol Specification](#)".

[MS-OXOUM] Microsoft Corporation, "[Voice Mail and Fax Objects Protocol Specification](#)".

[MS-OXPFOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) Public Folder Retrieval Protocol Specification](#)".

[MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol Specification](#)".

[MS-OXPSVAL] Microsoft Corporation, "[E-Mail Postmark Validation Algorithm](#)".

[MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Algorithm](#)".

[MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Algorithm](#)".

[MS-OXSHARE] Microsoft Corporation, "[Sharing Message Object Protocol Specification](#)".

[MS-OXTNEF] Microsoft Corporation, "[Transport Neutral Encapsulation Format \(TNEF\) Data Algorithm](#)".

[MS-OXVCARD] Microsoft Corporation, "[vCard to Contact Object Conversion Algorithm](#)".

[MS-OXWAVLS] Microsoft Corporation, "[Availability Web Service Protocol Specification](#)".

[MS-WMF] Microsoft Corporation, "[Windows Metafile Format](#)".

[MS-XWDCAL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Calendar Support](#)".

[MS-XWDCNTC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Contacts Support](#)".

[MS-XWDDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Documents Support](#)".

[MS-XWDEXT] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Core Extensions](#)".

[MS-XWDFOLD] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Folders Support](#)".

[MS-XWDMAIL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for E-Mail Support](#)".

[MS-XWDSEARCH] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Search](#)".

[MS-XWDSTRUCTDOC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Structured Documents](#)".

[MS-XWDVSEC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Protocol Security Descriptor Extensions](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

1.2.2 Informative References

[MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".

[MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".

[MS-OXNSPI] Microsoft Corporation, "[Exchange Server Name Service Provider Interface \(NSPI\) Protocol Specification](#)".

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

1.3 Overview

Each property listing in this document contains a link to the section of the technical specification in the Exchange Server Protocols documentation that acts as the defining reference for the property. The defining reference for each property contains the semantic use and definition of the property, including the property data type. The property information that is included in the defining reference for each property is required to successfully parse property data. As such, this document provides implementers with a single source of navigation to all of the critical property information that is included in the individual Exchange Server Protocols technical specifications.

This document also provides additional information about each property that is helpful to the implementer, such as the functional area where the property is used, a list of all the technical specifications that cite the property, and a list of alternate names by which the canonical property is known within the system. This information is not included in the technical specifications that describe each property, and is unique to this document. It is provided for informational purposes only.

A typical scenario for using this document is when an implementer encounters both **property IDs** and property values with no other identification coming across the wire. The property data type and the semantic definition of the property that are included in the defining reference for each property allow the implementer to correctly parse property values that show up in **ROP buffers**. The parsed values in the ROP buffers include lists of property IDs, which are typically lists of four hexadecimal characters. By searching the information in this document for those four hexadecimal characters, the implementer can quickly name the associated property and navigate to the definition of the individual property in its defining specification.

The following information is provided for each property, as appropriate.

Alternate names: Alternate names are implementation-specific names for properties that are used in source code and non-protocol-related documentation. Information about alternate names is useful when the implementer needs to refer to legacy documentation about a specific canonical property.

Area: The functional area where the property is used. Sections [1.3.1](#), [1.3.2](#), and [1.3.3](#) describe the general functional areas where properties are used. The listing for each property in section [2](#) describes the areas with more varied descriptions so as to provide more insight into property usage.

Canonical name: The name used to refer to the property in the Exchange Server Protocols documentation. The prefix of the canonical name identifies the basic characteristics of a property to the implementer.

The canonical naming structure uses three categories that are denoted by the following prefixes to the canonical **property name**:

- PidLid prefix: Properties identified by an unsigned 32-bit quantity along with a property set.
- PidName prefix: Properties identified by a string name along with a property set.
- PidTag prefix: Properties identified by an unsigned 16-bit quantity.

Description: A brief description of the contents of the property.

Data type: The property value type, as described in [\[MS-OXCDATA\]](#), that specifies the type of values allowed for the property.

Property ID: An unsigned 16-bit quantity that identifies a **tagged property**. Property IDs are not necessarily unique. With the exception of property IDs in the range from 0x6800 to 0x7BFF (see section [1.3.3](#)), the combination of property ID and data type are unique. Property IDs in the range from 0x6800 to 0x7BFF are defined by the **message class**.

Property long ID (LID): An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

Property name: A string that, along with the property set, identifies a named property.

Property set: A **GUID** that identifies a group of properties with a similar purpose.

Defining references: One or more technical specifications that describe the semantics and allowed values for the property.

Consuming references: One or more technical specifications that refer to the property but do not describe semantics and allowed values.

1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's message class. The following table describes several common message classes, the functional area to which each one corresponds, and the specification that describes each one's required and optional properties.

In the following table, an asterisk "*" denotes that any string can appear at that point.

Area name	PidTagMessageClass property values	Specification
Common	IPM.*	[MS-OXCMSG]
E-mail	IPM.Note, REPORT.*	[MS-OXCMSG]
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	[MS-OXOCAL]
Contact	IPM.Contact, IPM.DistList	[MS- OXOCNTC]
Task	IPM.Task, IPM.TaskRequest.*	[MS- OXOTASK]
Journal	IPM.Activity	[MS- OXOJRNL]
Sticky Note	IPM.StickyNote	[MS- OXONOTE]
Document	IPM.Document.*	[MS-OXODOC]
Post	IPM.Post	[MS- OXOPOST]

Area name	PidTagMessageClass property values	Specification
RSS Feed	IPM.Post.RSS	[MS-OXORSS]
Rights-managed E-mail	IPM.Note with PidNameContentClass= rpmsg.message	[MS-OXORMMS]
S/MIME E-mail	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	[MS-OXOSMIME]
Short Message Service (SMS) / Multimedia Message Service (MMS) Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	[MS-OXOSMMS]
Unified Messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	[MS-OXOUM]
Sharing	IPM.Sharing IPM.Sharing.*	[MS-OXSHARE]

1.3.2 Commonly Used Property Sets

In the property list that forms the main body of this document (section 2), each named property is listed with the GUID that describes its property set. Several of the more common property sets and their functional areas are described in the following table.

Area name	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}
Common	PSETID_Common {00062008-0000-0000-C000-000000000046}
Contact	PSETID_Address {00062004-0000-0000-C000-000000000046}
E-mail	PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-000000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-000000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-000000000046}
RSS feed	PSETID_PostRss

Area name	Property set name and GUID value
	{00062041-0000-0000-C000-000000000046}
Task	PSETID_Task {00062003-0000-0000-C000-000000000046}
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing {00062040-0000-0000-C000-000000000046}
Extracted entities	PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

1.3.3 Property ID Ranges

The 65,536 possible values of the property ID are divided into sub-ranges reserved for various purposes, as described in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an e-mail transport protocol (such as **SMTP**), and not to any network transport protocol (such as **TCP**):

- Servers do not allow property IDs in ranges specified as non-transmittable to be submitted for transport to another server via an e-mail transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.
- Clients can use properties in ranges described as message class-defined for application-defined purposes. When doing so, applications specify a value for the **PidTagMessageClass** property (section [2.858](#)) that is distinct from any value listed in section [1.3.1](#).
- Clients can use any named property for application-defined purposes. No constraint is placed on the value of the **PidTagMessageClass** property in this case, but the property set of the named property is distinct from any value listed in section [1.3.2](#). Note that named properties are always transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Description
0x0001	0x0BFF	Message object envelope property; reserved
0x0C00	0x0DFF	Recipient (1) property; reserved

Range minimum	Range maximum	Description
0x0E00	0x0FFF	Non-transmittable Message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	Message store property; reserved
0x3600	0x36FF	Folder and address book container property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	Address Book object property; reserved
0x3A00	0x3BFF	Mail user object property; reserved
0x3C00	0x3CFF	Distribution list property; reserved
0x3D00	0x3DFF	Profile section property; reserved
0x3E00	0x3EFF	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient (1) property
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. For more information about the static mapping of NSPI property names to property IDs that occurs in this ID range, see [MS-OXNSPI] .

1.3.4 WebDAV Property Naming

The e-mail server is natively a **Messaging Application Programming Interface (MAPI)** store where the vast majority of properties in it are MAPI properties. The **WebDAV** implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as described in [\[RFC5234\]](#), as a way to name MAPI properties, allowing Web Distributed Authoring and Versioning Protocol (WebDAV) clients to work with these properties directly.

The <http://schemas.microsoft.com/mapi/> namespace is used to access MAPI properties directly on the server. The namespace consists of three sub namespaces: proptag, id, and string. The ABNF notation used to specify the format of these namespaces is described in this section.

1.3.4.1 <http://schemas.microsoft.com/mapi/proptag> Namespace

The <http://schemas.microsoft.com/mapi/proptag> namespace is used to access properties on the server that are identified by a property ID. The implementer can access these properties through WebDAV by appending the hexadecimal property ID value and the hexadecimal **property type** value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type
property-id = 4HEXDIG
property-type = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace

The `http://schemas.microsoft.com/mapi/id` namespace is used to access named properties on the server that are identified by a property **long ID (LID)**. The implementer can access these properties through WebDAV by appending the property set and the hexadecimal property long ID (LID) value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/" property-long-id
property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"
property-long-id = 8HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213
(PidLidAppointmentDuration)
```

1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace

The `http://schemas.microsoft.com/mapi/string` namespace is used to access named properties on the server that are identified by a property name. The implementer can access these properties through WebDAV by appending the property set and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name
property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"
property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject
(PidNameSubject)
```

1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [\[MS-OXCADATA\]](#). For tables and examples that describe property data types, and property and other error codes, see [\[MS-OXCADATA\]](#).

The list of properties and their descriptions included in this document provide context for many of the data structures described in [MS-OXCADATA].

The description of each property contained in this document relies on the technical specification that is cited as its defining reference.

1.5 Applicability Statement

This document provides numeric values used to encode property names, tags, and data types in ROP buffers. It also serves as a convenient index to the object type documents that define how each property is used.

1.6 Versioning and Localization

None.

1.7 Vendor-Extensible Fields

Property ID ranges, as described in section [1.3.3](#), describe how applications choose properties to create new Message object types or to add functionality to existing types.

2 Structures

2.1 PidLidAddressBookProviderArrayType

Canonical name: PidLidAddressBookProviderArrayType

Description: Specifies the state of the contact's electronic addresses and represents a set of bit **flags**.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008029

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.12

Alternate names: dispidABPArrayType

2.2 PidLidAddressBookProviderEmailList

Canonical name: PidLidAddressBookProviderEmailList

Description: Specifies which electronic address properties are set on the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008028

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.11

Alternate names: dispidABPEmailList

2.3 PidLidAddressCountryCode

Canonical name: PidLidAddressCountryCode

Description: Specifies the country code portion of the contact's mailing address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DD

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidAddressCountryCode

2.4 PidLidAgingDontAgeMe

Canonical name: PidLidAgingDontAgeMe

Description: Specifies whether to automatically archive the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000850E

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.33

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidAgingDontAgeMe

2.5 PidLidAllAttendeesString

Canonical name: PidLidAllAttendeesString

Description: Specifies a list of all the attendees except for the **organizer**, including **resources** and **unsendable attendees**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008238

WebDAV: <http://schemas.microsoft.com/mapi/allattendeesstring>

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.16

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidAllAttendeesString

2.6 PidLidAllowExternalCheck

Canonical name: PidLidAllowExternalCheck

Description: This property is set to TRUE.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008246

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.5

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidAllowExternCheck

2.7 PidLidAnniversaryEventEntryId

Canonical name: PidLidAnniversaryEventEntryId

Description: Specifies the **EntryID** of the **Appointment object** that represents a contact's anniversary.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804E

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.6

Alternate names: dispidAnniversaryEventEID

2.8 PidLidAppointmentAuxiliaryFlags

Canonical name: PidLidAppointmentAuxiliaryFlags

Description: Specifies a bit field that describes the auxiliary state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008207

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.3

Alternate names: dispidApptAuxFlags

2.9 PidLidAppointmentColor

Canonical name: PidLidAppointmentColor

Description: Specifies the color to be used when displaying the **Calendar object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008214

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference:

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: dispidApptColor

2.10 PidLidAppointmentCounterProposal

Canonical name: PidLidAppointmentCounterProposal

Description: Indicates whether a **Meeting Response object** is a **counter proposal**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008257

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.7

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptCounterProposal

2.11 PidLidAppointmentDuration

Canonical name: PidLidAppointmentDuration

Description: Specifies the length of the event, in minutes.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008213

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/apptduration>

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptDuration

2.12 PidLidAppointmentEndDate

Canonical name: PidLidAppointmentEndDate

Description: Indicates the date that the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008211

WebDAV: <http://schemas.microsoft.com/mapi/apptenddate>

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.3

Alternate names: dispidApptEndDate

2.13 PidLidAppointmentEndTime

Canonical name: PidLidAppointmentEndTime

Description: Indicates the time that the appointment ends.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008210

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptendtime>

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.4

Alternate names: dispidApptEndTime

2.14 PidLidAppointmentEndWhole

Canonical name: PidLidAppointmentEndWhole

Description: Specifies the end date and time for the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820E

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptendwhole>

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.6

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptEndWhole

2.15 PidLidAppointmentLastSequence

Canonical name: PidLidAppointmentLastSequence

Description: Indicates to the organizer the last sequence number that was sent to any attendee.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008203

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.2

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptLastSequence

2.16 PidLidAppointmentMessageClass

Canonical name: PidLidAppointmentMessageClass

Description: Indicates the message class of the **Meeting object** to be generated from the **Meeting Request object**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000024

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.6

Alternate names: dispidApptMessageClass

2.17 PidLidAppointmentNotAllowPropose

Canonical name: PidLidAppointmentNotAllowPropose

Description: Indicates whether attendees are not allowed to propose a new date and/or time for the **meeting**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.26

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptNotAllowPropose

2.18 PidLidAppointmentProposalNumber

Canonical name: PidLidAppointmentProposalNumber

Description: Specifies the number of attendees who have sent counter proposals that have not been accepted or rejected by the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008259

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.6

Alternate names: dispidApptProposalNum

2.19 PidLidAppointmentProposedDuration

Canonical name: PidLidAppointmentProposedDuration

Description: Indicates the proposed value for the **PidLidAppointmentDuration** property (section [2.11](#)) for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008256

Data type: **PtypInteger32**, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.5

Alternate names: dispidApptProposedDuration

2.20 PidLidAppointmentProposedEndWhole

Canonical name: PidLidAppointmentProposedEndWhole

Description: Specifies the proposed value for the **PidLidAppointmentEndWhole** property (section [2.14](#)) for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008251

Data type: **PtypTime**, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.4

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposedEndWhole

2.21 PidLidAppointmentProposedStartWhole

Canonical name: PidLidAppointmentProposedStartWhole

Description: Specifies the proposed value for the **PidLidAppointmentStartWhole** property (section [2.29](#)) for a counter proposal.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008250

Data type: **PtypTime**, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.3

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptProposedStartWhole

2.22 PidLidAppointmentRecur

Canonical name: PidLidAppointmentRecur

Description: Specifies the dates and times when a **recurring series** occurs.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008216

Data type: PtypBinary, 0x0102

WebDAV: <http://schemas.microsoft.com/mapi/apptrecur>

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.44

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptRecur

2.23 PidLidAppointmentReplyName

Canonical name: PidLidAppointmentReplyName

Description: Specifies the user who last replied to the **meeting request** or meeting update.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008230

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/apptreplyname>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.5

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidApptReplyName, <http://schemas.microsoft.com/mapi/apptreplyname>

2.24 PidLidAppointmentReplyTime

Canonical name: PidLidAppointmentReplyTime

Description: Specifies the date and time at which the attendee responded to a received meeting request or **Meeting Update object**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008220

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.3

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidApptReplyTime

2.25 PidLidAppointmentSequence

Canonical name: PidLidAppointmentSequence

Description: Specifies the sequence number of a Meeting object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008201

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptsequence

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptSequence

2.26 PidLidAppointmentSequenceTime

Canonical name: PidLidAppointmentSequenceTime

Description: Indicates the date and time at which the **PidLidAppointmentSequence** property (section [2.25](#)) was last modified.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008202

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.1

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptSeqTime

2.27 PidLidAppointmentStartDate

Canonical name: PidLidAppointmentStartDate

Description: Identifies the date that the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008212

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptstartdate>

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.10

Alternate names: dispidApptStartDate

2.28 PidLidAppointmentStartTime

Canonical name: PidLidAppointmentStartTime

Description: Identifies the time that the appointment starts.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820F

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptstarttime>

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.11

Alternate names: dispidApptStartTime

2.29 PidLidAppointmentStartWhole

Canonical name: PidLidAppointmentStartWhole

Description: Specifies the start date and time of the appointment.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820D

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptstartwhole>

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptStartWhole

2.30 PidLidAppointmentStateFlags

Canonical name: PidLidAppointmentStateFlags

Description: Specifies a bit field that describes the state of the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008217

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/apptstateflags

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.10

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidApptStateFlags

2.31 PidLidAppointmentSubType

Canonical name: PidLidAppointmentSubType

Description: Specifies whether the event is an all-day event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008215

Data type: PtypBoolean, 0x000B

WebDAV: urn:schemas:calendar:alldayevent, http://schemas.microsoft.com/mapi/apptsubtype

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidApptSubType

2.32 PidLidAppointmentTimeZoneDefinitionEndDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionEndDisplay

Description: Specifies time zone information that indicates the time zone of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825F

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.43

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptTZDefEndDisplay

2.33 PidLidAppointmentTimeZoneDefinitionRecur

Canonical name: PidLidAppointmentTimeZoneDefinitionRecur

Description: Specifies time zone information that describes how to convert the meeting date and time on a recurring series to and from **UTC**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008260

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.41

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

Alternate names: dispidApptTZDefRecur

2.34 PidLidAppointmentTimeZoneDefinitionStartDisplay

Canonical name: PidLidAppointmentTimeZoneDefinitionStartDisplay

Description: Specifies time zone information that indicates the time zone of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825E

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.42

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidApptTZDefStartDisplay

2.35 PidLidAppointmentUnsendableRecipients

Canonical name: PidLidAppointmentUnsendableRecipients

Description: Contains a list of unsendable attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000825D

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.25

Alternate names: dispidApptUnsendableRecips

2.36 PidLidAppointmentUpdateTime

Canonical name: PidLidAppointmentUpdateTime

Description: Indicates the time at which the appointment was last updated.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008226

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/apptupdatetime>

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.15

Alternate names: dispidApptUpdateTime

2.37 PidLidAttendeeCriticalChange

Canonical name: PidLidAttendeeCriticalChange

Description: Specifies the date and time at which the **meeting-related object** was sent.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000001

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/attendee_critical_change

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_ATTENDEE_CRITICAL_CHANGE

2.38 PidLidAutoFillLocation

Canonical name: PidLidAutoFillLocation

Description: Indicates whether the value of the **PidLidLocation** property (section [2.159](#)) is set to the **PidTagDisplayName** property (section [2.749](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.8

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidAutoFillLocation

2.39 PidLidAutoLog

Canonical name: PidLidAutoLog

Description: Specifies to the application whether to create a **Journal object** for each action associated with this Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008025

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.19

Alternate names: dispidAutoLog

2.40 PidLidAutoProcessState

Canonical name: PidLidAutoProcessState

Description: Specifies the options used in the automatic processing of e-mail messages.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851A

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.69

Alternate names: dispidSniffState

2.41 PidLidAutoStartCheck

Canonical name: PidLidAutoStartCheck

Description: Specifies whether to automatically start the conferencing application when a **reminder** for the start of a meeting is executed.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008244

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference:

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidAutoStartCheck

2.42 PidLidBilling

Canonical name: PidLidBilling

Description: Specifies billing information for the contact.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008535

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:billinginformation

Area: General Message Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.24

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidBilling

2.43 PidLidBirthdayEventEntryId

Canonical name: PidLidBirthdayEventEntryId

Description: Specifies the EntryID of an optional Appointment object that represents the contact's birthday.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804D

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.3

Alternate names: dispidBirthdayEventEID

2.44 PidLidBirthdayLocal

Canonical name: PidLidBirthdayLocal

Description: Specifies the birthday of a contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DE

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.2

Alternate names: dispidApptBirthdayLocal

2.45 PidLidBusinessCardCardPicture

Canonical name: PidLidBusinessCardCardPicture

Description: Contains the image to be used on a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008041

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.2

Alternate names: dispidBCCardPicture

2.46 PidLidBusinessCardDisplayDefinition

Canonical name: PidLidBusinessCardDisplayDefinition

Description: Contains user customization details for displaying a contact as a business card.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008040

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidBCDisplayDefinition

2.47 PidLidBusyStatus

Canonical name: PidLidBusyStatus

Description: Specifies the availability of a user for the event described by the object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008205

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/busystatus

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidBusyStatus

2.48 PidLidCalendarType

Canonical name: PidLidCalendarType

Description: Contains the value of the **CalendarType** field from the **PidLidAppointmentRecur** property (section [2.22](#)).

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000001C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/calendar_type

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.11

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_CALENDAR_TYPE

2.49 PidLidCategories

Canonical name: PidLidCategories

Description: Contains the array of text labels assigned to this Message object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property long ID (LID): 0x00009000

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.22

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidCategories

2.50 PidLidCcAttendeesString

Canonical name: PidLidCcAttendeesString

Description: Contains a list of all the sendable attendees who are also **optional attendees**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823C

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.18

Alternate names: dispidCCAttendeesString

2.51 PidLidChangeHighlight

Canonical name: PidLidChangeHighlight

Description: Specifies a bit field that indicates how the Meeting object has changed.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008204

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.2

Consuming reference: [\[MS-OXORMDR\]](#)

Alternate names: dispidChangeHighlight

2.52 PidLidClassification

Canonical name: PidLidClassification

Description: Contains a list of the classification categories to which the associated Message object has been assigned.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B6

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.23

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassification

2.53 PidLidClassificationDescription

Canonical name: PidLidClassificationDescription

Description: Contains a human-readable summary of each of the classification categories included in the **PidLidClassification** property (section [2.53](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B7

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.24

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassDesc

2.54 PidLidClassificationGuid

Canonical name: PidLidClassificationGuid

Description: Contains the GUID that identifies the list of e-mail classification categories used by a Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B8

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMAIL\]](#) section 2.5.1

Alternate names: dispidClassGuid

2.55 PidLidClassificationKeep

Canonical name: PidLidClassificationKeep

Description: Indicates whether the message uses any classification categories.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BA

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXCMAIL\]](#) section 2.5.2

Alternate names: dispidClassKeep

2.56 PidLidClassified

Canonical name: PidLidClassified

Description: Indicates whether the contents of this message are regarded as classified information.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085B5

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.25

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: dispidClassified

2.57 PidLidCleanGlobalObjectId

Canonical name: PidLidCleanGlobalObjectId

Description: Contains the value of the **PidLidGlobalObjectId** property (section [2.142](#)) for an object that represents an **Exception object** to a recurring series, where the Year, Month, and Day fields are all zero.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000023

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.28

Consuming references: [\[MS-OXCICAL\]](#)

Alternate names: dispidCleanGlobalObjId

2.58 PidLidClientIntent

Canonical name: PidLidClientIntent

Description: Indicates what actions the user has taken on this Meeting object.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x00000015

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.2.4

Alternate names: dispidClientIntent

2.59 PidLidClipEnd

Canonical name: PidLidClipEnd

Description: Specifies the end date and time of the event in UTC.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008236

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.15

Alternate names: dispidClipEnd

2.60 PidLidClipStart

Canonical name: PidLidClipStart

Description: Specifies the start date and time of the event in UTC.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008235

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.14

Alternate names: dispidClipStart

2.61 PidLidCollaborateDoc

Canonical name: PidLidCollaborateDoc

Description: Specifies the document to be launched when the user joins the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008247

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidCollaborateDoc

2.62 PidLidCommonEnd

Canonical name: PidLidCommonEnd

Description: Indicates the end time for the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008517

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.19

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidCommonEnd

2.63 PidLidCommonStart

Canonical name: PidLidCommonStart

Description: Indicates the start time for the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008516

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.18

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidCommonStart

2.64 PidLidCompanies

Canonical name: PidLidCompanies

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008539

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference:

Consuming references: [\[MS-OXOJRNL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidCompanies, <http://schemas.microsoft.com/exchange/companies>

2.65 PidLidConferencingCheck

Canonical name: PidLidConferencingCheck

Description:

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008240

Data type: PtypBoolean, 0x000B

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidConfCheck

2.66 PidLidConferencingType

Canonical name: PidLidConferencingType

Description: Specifies the type of the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008241

Data type: PtypInteger32, 0x0003

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.3

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidConfType

2.67 PidLidContactCharacterSet

Canonical name: PidLidContactCharacterSet

Description: Specifies the character set used for a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008023

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.18

Alternate names: dispidContactCharSet

2.68 PidLidContactItemData

Canonical name: PidLidContactItemData

Description: Specifies the visible fields in the application's user interface that are used to help display the contact information.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008007

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.22

Alternate names: dispidContactItemData

2.69 PidLidContactLinkedGlobalAddressListEntryId

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

Canonical name: PidLidContactLinkedGlobalAddressListEntryId

Description: Specifies the EntryID of the **GAL** contact to which the duplicate contact is linked.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E2

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.1

Alternate names: dispidContactLinkedGAEntryID

2.70 PidLidContactLinkEntry

Canonical name: PidLidContactLinkEntry

Description: Contains the elements of the **PidLidContacts** property (section [2.77](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008585

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.49.1

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkEntry

2.71 PidLidContactLinkGlobalAddressListLinkId

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

Canonical name: PidLidContactLinkGlobalAddressListLinkId

Description: Specifies the GUID of the GAL contact to which the duplicate contact is linked.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E8

Data type: PtypGuid, 0x0048

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.2

Alternate names: dispidContactLinkGALLinkID

2.72 PidLidContactLinkGlobalAddressListLinkState

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

Canonical name: PidLidContactLinkGlobalAddressListLinkState

Description: Specifies the state of the linking between the GAL contact and the duplicate contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E6

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.3

Alternate names: dispidContactLinkGALLinkState

2.73 PidLidContactLinkLinkRejectHistory

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

Canonical name: PidLidContactLinkLinkRejectHistory

Description: Contains a list of GAL contacts that were previously rejected for linking with the duplicate contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E5

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.4

Alternate names: dispidContactLinkLinkRejectHistory

2.74 PidLidContactLinkName

Canonical name: PidLidContactLinkName

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008586

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.49.3

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkName

2.75 PidLidContactLinkSearchKey

Canonical name: PidLidContactLinkSearchKey

Description: Contains the list of SearchKeys for a Contact object linked to by the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008584

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.49.4

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContactLinkSearchKey

2.76 PidLidContactLinkSMTPAddressCache

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

Canonical name: PidLidContactLinkSMTPAddressCache

Description: Contains a list of the SMTP addresses that are used by the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E3

Data type: PtypMultipleString, 0x101F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.5

Alternate names: dispidContactLinkSMTPAddressCache

2.77 PidLidContacts

Canonical name: PidLidContacts

Description: Contains the **PidTagDisplayName** property (section [2.749](#)) of each Address Book EntryID referenced in the value of the **PidLidContactLinkEntry** property (section [2.70](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000853A

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.49.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidContacts

2.78 PidLidContactUserField1

Canonical name: PidLidContactUserField1

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804F

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute1

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField1

2.79 PidLidContactUserField2

Canonical name: PidLidContactUserField2

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008050

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute2

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField2

2.80 PidLidContactUserField3

Canonical name: PidLidContactUserField3

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008051

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute3

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField3

2.81 PidLidContactUserField4

Canonical name: PidLidContactUserField4

Description: Contains text used to add custom text to a business card representation of a Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008052

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/extensionattribute4

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidContactUserField4

2.82 PidLidConversationActionLastAppliedTime

Canonical name: PidLidConversationActionLastAppliedTime

Description: Contains the time, in UTC, that an **E-mail object** was last received in the **conversation**, or the last time that the user modified the **conversation action**, whichever occurs later.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CA

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.1

Alternate names: dispidConvActionLastAppliedTime

2.83 PidLidConversationActionMaxDeliveryTime

Canonical name: PidLidConversationActionMaxDeliveryTime

Description: Contains the maximum value of the **PidTagMessageDeliveryTime** property (section [2.860](#)) of all of the E-mail objects modified in response to the last time that the user changed a conversation action on the client.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C8

Data type: PtypTime, 0x0040

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.2

Alternate names: dispidConvActionMaxDeliveryTime

2.84 PidLidConversationActionMoveFolderEid

Canonical name: PidLidConversationActionMoveFolderEid

Description: Contains the EntryID for the destination folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C6

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.3

Alternate names: dispidConvActionMoveFolderEid

2.85 PidLidConversationActionMoveStoreEid

Canonical name: PidLidConversationActionMoveStoreEid

Description: Contains the EntryID for a move to a folder in a different store.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C7

Data type: PtypBinary, 0x0102

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.4

Alternate names: dispidConvActionMoveStoreEid

2.86 PidLidConversationActionVersion

Canonical name: PidLidConversationActionVersion

Description: Contains the version of the conversation action **FAI** message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085CB

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.8.5

Alternate names: dispidConvActionVersion

2.87 PidLidConversationProcessed

Canonical name: PidLidConversationProcessed

Description:

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C9

Data type: PtypInteger32, 0x0003

Area: Conversation Actions

Defining reference:

Consuming references: [\[MS-OXOCFG\]](#)

Alternate names: dispidConvExLegacyProcessedRand

2.88 PidLidCurrentVersion

Canonical name: PidLidCurrentVersion

Description: Specifies the build number of the client application that sent the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008552

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.34

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidCurrentVersion

2.89 PidLidCurrentVersionName

Canonical name: PidLidCurrentVersionName

Description: Specifies the name of the client application that sent the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008554

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.35

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: dispidCurrentVersionName

2.90 PidLidDayInterval

Canonical name: PidLidDayInterval

Description: Identifies the day interval for the **recurrence pattern**.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000011

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/day_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.19

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_DAY_INTERVAL

2.91 PidLidDayOfMonth

Canonical name: PidLidDayOfMonth

Description: Identifies the day of the month for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001000

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/dayofmonth>

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.20

2.92 PidLidDelegateMail

Canonical name: PidLidDelegateMail

Description: Indicates whether a delegate responded to the meeting request.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000009

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/delegate_mail

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.21

Alternate names: LID_DELEGATE_MAIL

2.93 PidLidDepartment

Canonical name: PidLidDepartment

Description: This property is ignored by the server and is set to an empty string by the client.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008010

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.6.4

Alternate names: dispidDepartment

2.94 PidLidDirectory

Canonical name: PidLidDirectory

Description: Specifies the directory server to be used.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008242

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidDirectory

2.95 PidLidDistributionListChecksum

Canonical name: PidLidDistributionListChecksum

Description: Specifies the 32-bit **cyclic redundancy check (CRC)** polynomial checksum, as specified in [\[ISO/IEC8802-3\]](#), calculated on the value of the **PidLidDistributionListMembers** property (section [2.96](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000804C

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.3

Alternate names: dispidDLChecksum

2.96 PidLidDistributionListMembers

Canonical name: PidLidDistributionListMembers

Description: Specifies the list of EntryIDs of the objects corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008055

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.1

Alternate names: dispidDLMembers

2.97 PidLidDistributionListName

Canonical name: PidLidDistributionListName

Description: Specifies the name of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008053

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.1.2

Alternate names: dispidDLName

2.98 PidLidDistributionListOneOffMembers

Canonical name: PidLidDistributionListOneOffMembers

Description: Specifies the list of one-off EntryIDs corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008054

Data type: PtypMultipleBinary, 0x1102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.2

Alternate names: dispidDLOneOffMembers

2.99 PidLidDistributionListStream

Canonical name: PidLidDistributionListStream

Description: Specifies the list of EntryIDs and one-off EntryIDs corresponding to the members of the personal distribution list.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008064

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.2.2.4

Alternate names: dispidDLStream

2.100 PidLidEmail1AddressType

Canonical name: PidLidEmail1AddressType

Description: Specifies the **address type** of an electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008082

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1AddrType

2.101 PidLidEmail1DisplayName

Canonical name: PidLidEmail1DisplayName

Description: Specifies the user-readable **display name** for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008080

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1DisplayName

2.102 PidLidEmail1EmailAddress

Canonical name: PidLidEmail1EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008083

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail1EmailAddress

2.103 PidLidEmail1OriginalDisplayName

Canonical name: PidLidEmail1OriginalDisplayName

Description: Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008084

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

Alternate names: dispidEmail1OriginalDisplayName, Email1OriginalDisplayName, EXSCHEMA_MAPI_EMAIL1ORIGINALDISPLAYNAME

2.104 PidLidEmail1OriginalEntryId

Canonical name: PidLidEmail1OriginalEntryId

Description: Specifies the EntryID of the object corresponding to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008085

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

Alternate names: dispidEmail1OriginalEntryID

2.105 PidLidEmail2AddressType

Canonical name: PidLidEmail2AddressType

Description: Specifies the address type of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008092

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2AddrType

2.106 PidLidEmail2DisplayName

Canonical name: PidLidEmail2DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008090

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2DisplayName

2.107 PidLidEmail2EmailAddress

Canonical name: PidLidEmail2EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008093

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail2EmailAddress

2.108 PidLidEmail2OriginalDisplayName

Canonical name: PidLidEmail2OriginalDisplayName

Description: Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008094

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

Alternate names: dispidEmail2OriginalDisplayName

2.109 PidLidEmail2OriginalEntryId

Canonical name: PidLidEmail2OriginalEntryId

Description: Specifies the EntryID of the object that corresponds to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008095

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

Alternate names: dispidEmail2OriginalEntryID

2.110 PidLidEmail3AddressType

Canonical name: PidLidEmail3AddressType

Description: Specifies the address type of the electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3AddrType

2.111 PidLidEmail3DisplayName

Canonical name: PidLidEmail3DisplayName

Description: Specifies the user-readable display name for the e-mail address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A0

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3DisplayName

2.112 PidLidEmail3EmailAddress

Canonical name: PidLidEmail3EmailAddress

Description: Specifies the e-mail address of the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidEmail3EmailAddress

2.113 PidLidEmail3OriginalDisplayName

Canonical name: PidLidEmail3OriginalDisplayName

Description: Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

Alternate names: dispidEmail3OriginalDisplayName

2.114 PidLidEmail3OriginalEntryId

Canonical name: PidLidEmail3OriginalEntryId

Description: Specifies the EntryID of the object that corresponds to this electronic address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080A5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

Alternate names: dispidEmail3OriginalEntryID

2.115 PidLidEndRecurrenceDate

Canonical name: PidLidEndRecurrenceDate

Description: Identifies the end date of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000F

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_date

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.22

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_END_RECUR_DATE

2.116 PidLidEndRecurrenceTime

Canonical name: PidLidEndRecurrenceTime

Description: Identifies the end time of the recurrence range.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000010

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/end_recur_time

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.23

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_END_RECUR_TIME

2.117 PidLidExceptionReplaceTime

Canonical name: PidLidExceptionReplaceTime

Description: Specifies the date and time, in UTC, within a recurrence pattern that an exception will replace.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008228

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.2.5

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidExceptionReplaceTime

2.118 PidLidFax1AddressType

Canonical name: PidLidFax1AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

Alternate names: dispidFax1AddrType

2.119 PidLidFax1EmailAddress

Canonical name: PidLidFax1EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

Alternate names: dispidFax1EmailAddress

2.120 PidLidFax1OriginalDisplayName

Canonical name: PidLidFax1OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section [2.880](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

Alternate names: dispidFax1OriginalDisplayName

2.121 PidLidFax1OriginalEntryId

Canonical name: PidLidFax1OriginalEntryId

Description: Specifies a one-off EntryID that corresponds to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080B5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

Alternate names: dispidFax1OriginalEntryID

2.122 PidLidFax2AddressType

Canonical name: PidLidFax2AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

Alternate names: dispidFax2AddrType

2.123 PidLidFax2EmailAddress

Canonical name: PidLidFax2EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

Alternate names: dispidFax2EmailAddress

2.124 PidLidFax2OriginalDisplayName

Canonical name: PidLidFax2OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section [2.880](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

Alternate names: dispidFax2OriginalDisplayName

2.125 PidLidFax2OriginalEntryID

Canonical name: PidLidFax2OriginalEntryID

Description: Specifies a one-off EntryID corresponding to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080C5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

Alternate names: dispidFax2OriginalEntryID

2.126 PidLidFax3AddressType

Canonical name: PidLidFax3AddressType

Description: Contains the string value "FAX".

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D2

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

Alternate names: dispidFax3AddrType

2.127 PidLidFax3EmailAddress

Canonical name: PidLidFax3EmailAddress

Description: Contains a user-readable display name, followed by the "@" character, followed by a fax number.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D3

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

Alternate names: dispidFax3EmailAddress

2.128 PidLidFax3OriginalDisplayName

Canonical name: PidLidFax3OriginalDisplayName

Description: Contains the same value as the **PidTagNormalizedSubject** property (section [2.880](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D4

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

Alternate names: dispidFax3OriginalDisplayName

2.129 PidLidFax3OriginalEntryId

Canonical name: PidLidFax3OriginalEntryId

Description: Specifies a one-off EntryID that corresponds to this fax address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D5

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

Alternate names: dispidFax3OriginalEntryID

2.130 PidLidFExceptionalAttendees

Canonical name: PidLidFExceptionalAttendees

Description: Indicates that the object is a **Recurring Calendar object** with one or more exceptions, and that at least one of the **Exception Embedded Message objects** has at least one **RecipientRow** structure, as described in [\[MS-OXCDATA\]](#) section 2.8.3.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822B

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.2.3

Consuming reference: [\[MS-OXORMDR\]](#)

Alternate names: dispidFExceptionalAttendees

2.131 PidLidFExceptionalBody

Canonical name: PidLidFExceptionalBody

Description: Indicates that the Exception Embedded Message object has a body that differs from the Recurring Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008206

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.2.6

Alternate names: dispidFExceptionalBody

2.132 PidLidFileUnder

Canonical name: PidLidFileUnder

Description: Specifies the name under which to file a contact when displaying a list of contacts.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008005

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.11

Alternate names: dispidFileUnder

2.133 PidLidFileUnderId

Canonical name: PidLidFileUnderId

Description: Specifies how to generate and recompute the value of the **PidLidFileUnder** property (section [2.132](#)) when other contact name properties change.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008006

Data type: PtypInteger32, 0x0003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.12

Alternate names: dispidFileUnderId

2.134 PidLidFileUnderList

Canonical name: PidLidFileUnderList

Description: Specifies a list of possible values for the **PidLidFileUnderId** property (section [2.133](#)).

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008026

Data type: PtypMultipleInteger32, 0x1003

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.13

Alternate names: dispidFileUnderList

2.135 PidLidFInvited

Canonical name: PidLidFInvited

Description: Indicates whether invitations have been sent for the meeting that this Meeting object represents.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008229

Data type: PtypBoolean, 0x000B

WebDAV: <http://schemas.microsoft.com/mapi/finvited>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidFInvited

2.136 PidLidFlagRequest

Canonical name: PidLidFlagRequest

Description: Contains user-specifiable text to be associated with the flag.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008530

Data type: PtypString, 0x001F

WebDAV: urn:schemas:httpmail:messageflag, http://schemas.microsoft.com/mapi/request

Area: Flagging

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidRequest

2.137 PidLidFlagString

Canonical name: PidLidFlagString

Description: Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085C0

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.10

Alternate names: dispidFlagStringEnum

2.138 PidLidForwardInstance

Canonical name: PidLidForwardInstance

Description: Indicates whether the Meeting Request object represents an exception to a recurring series, and whether it was forwarded (even when forwarded by the organizer) rather than being an invitation sent by the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820A

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.3

Alternate names: dispidFwrInstance

2.139 PidLidForwardNotificationRecipients

Canonical name: PidLidForwardNotificationRecipients

Description: Contains a list of **RecipientRow** structures, as described in [\[MS-OXCADATA\]](#) section 2.8.3, that indicate the recipients (2) of a meeting forward.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008261

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.9.3

Alternate names: dispidForwardNotificationRecipients

2.140 PidLidFOthersAppointment

Canonical name: PidLidFOthersAppointment

Description: Indicates whether the **Calendar folder** from which the meeting was opened is another user's **calendar**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822F

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.26

Alternate names: dispidFOthersAppt, <http://schemas.microsoft.com/mapi/fothersappt>

2.141 PidLidFreeBusyLocation

Canonical name: PidLidFreeBusyLocation

Description: Specifies a **URL** path from which a client can retrieve **free/busy status** information for the contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080D8

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:fburl

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.10

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidFreeBusyLocation

2.142 PidLidGlobalObjectId

Canonical name: PidLidGlobalObjectId

Description: Contains an ID for an object that represents an exception to a recurring series.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000003

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.27

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#)

Alternate names: LID_GLOBAL_OBJID

2.143 PidLidHasPicture

Canonical name: PidLidHasPicture

Description: Specifies whether the attachment has a picture.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008015

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.8.1

Alternate names: dispidHasPicture

2.144 PidLidHomeAddress

Canonical name: PidLidHomeAddress

Description: Specifies the complete address of the contact's home address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:homepostaladdress

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidHomeAddress

2.145 PidLidHomeAddressCountryCode

Canonical name: PidLidHomeAddressCountryCode

Description: Specifies the country code portion of the contact's home address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DA

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidHomeAddressCountryCode

2.146 PidLidHtml

Canonical name: PidLidHtml

Description: Specifies the contact's business webpage URL.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802B

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.12

Alternate names: dispidHTML

2.147 PidLidICalendarDayOfWeekMask

Canonical name: PidLidICalendarDayOfWeekMask

Description: Identifies the day of the week for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001001

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.27

Alternate names: <http://schemas.microsoft.com/mapi/dayofweekmask>

2.148 PidLidInboundICalStream

Canonical name: PidLidInboundICalStream

Description:

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827A

Data type: PtypBinary, 0x0102

Area: Calendar

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: InboundICalStream, dispidInboundICalStream

2.149 PidLidInfoPathFormName

Canonical name: PidLidInfoPathFormName

Description: Contains the name of the form associated with this message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x85B1

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.27

Consuming reference: [\[MS-OXCMAIL\]](#)

2.150 PidLidInstantMessagingAddress

Canonical name: PidLidInstantMessagingAddress

Description: Specifies the contact's instant messaging address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008062

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.6

Consuming reference: [\[MS-OXVCARD\]](#)

Alternate names: dispidInstMsg

2.151 PidLidIntendedBusyStatus

Canonical name: PidLidIntendedBusyStatus

Description: Contains the value of the **PidLidBusyStatus** property (section [2.47](#)) on the Meeting object in the organizer's calendar at the time that the Meeting Request object or Meeting Update object was sent.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008224

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/intendedbusystatus>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidIntendedBusyStatus

2.152 PidLidInternetAccountName

Canonical name: PidLidInternetAccountName

Description: Specifies the user-visible e-mail account name through which the e-mail message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008580

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.58

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidInetAcctName

2.153 PidLidInternetAccountStamp

Canonical name: PidLidInternetAccountStamp

Description: Specifies the e-mail account ID through which the e-mail message is sent.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008581

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.59

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidInetAcctStamp

2.154 PidLidIsException

Canonical name: PidLidIsException

Description: Indicates whether the object represents an exception (including an **orphan instance**).

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000A

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_exception

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.35

Consuming references: [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_EXCEPTION

2.155 PidLidIsRecurring

Canonical name: PidLidIsRecurring

Description: Specifies whether the object is associated with a recurring series.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000005

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_recurring

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.13

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_RECURREING

2.156 PidLidIsContactLinked

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

Canonical name: PidLidIsContactLinked

Description: Specifies whether the contact is linked to other contacts.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080E0

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.6

Alternate names: dispidIsContactLinked

2.157 PidLidIsSilent

Canonical name: PidLidIsSilent

Description: Indicates whether the user did not include any text in the body of the Meeting Response object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000004

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/is_silent

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.7

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_IS_SILENT

2.158 PidLidLinkedTaskItems

Canonical name: PidLidLinkedTaskItems

Description: Indicates whether the user did not include any text in the body of the Meeting Response object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000820C

Data type: PtypMultipleBinary, 0x1102

Area: Tasks

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.47

Alternate names: dispidLinkedTaskItems

2.159 PidLidLocation

Canonical name: PidLidLocation

Description: Specifies the location of the event.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008208

Data type: PtypString, 0x001F

WebDAV: urn:schemas:calendar:location

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidLocation

2.160 PidLidLogDocumentPosted

Canonical name: PidLidLogDocumentPosted

Description: Indicates whether the document was sent by e-mail or posted to a server folder during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008711

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRN\]](#) section 2.2.1.10

Alternate names: dispidLogDocPosted

2.161 PidLidLogDocumentPrinted

Canonical name: PidLidLogDocumentPrinted

Description: Indicates whether the document was printed during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870E

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRN\]](#) section 2.2.1.7

Alternate names: dispidLogDocPrinted

2.162 PidLidLogDocumentRouted

Canonical name: PidLidLogDocumentRouted

Description: Indicates whether the document was sent to a routing recipient (1) during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008710

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.9

Alternate names: dispidLogDocRouted

2.163 PidLidLogDocumentSaved

Canonical name: PidLidLogDocumentSaved

Description: Indicates whether the document was saved during journaling.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870F

Data type: PtypBoolean, 0x000B

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.8

Alternate names: dispidLogDocSaved

2.164 PidLidLogDuration

Canonical name: PidLidLogDuration

Description: Contains the duration, in minutes, of the activity.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008707

Data type: PtypInteger32, 0x0003

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.5

Alternate names: dispidLogDuration

2.165 PidLidLogEnd

Canonical name: PidLidLogEnd

Description: Contains the time, in UTC, at which the activity ended.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008708

Data type: PtypTime, 0x0040

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.4

Alternate names: dispidLogEnd

2.166 PidLidLogFlags

Canonical name: PidLidLogFlags

Description: Contains metadata about the Journal object.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000870C

Data type: PtypInteger32, 0x0003

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.6

Alternate names: dispidLogFlags

2.167 PidLidLogStart

Canonical name: PidLidLogStart

Description: Contains the time, in UTC, at which the activity began.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008706

Data type: PtypTime, 0x0040

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.3

Alternate names: dispidLogStart

2.168 PidLidLogType

Canonical name: PidLidLogType

Description: Briefly describes the journal activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008700

Data type: PtypString, 0x001F

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.1

Alternate names: dispidLogType

2.169 PidLidLogTypeDesc

Canonical name: PidLidLogTypeDesc

Description: Contains an expanded description of the journal activity that is being recorded.

Property set: PSETID_Log {0006200A-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008712

Data type: PtypString, 0x001F

Area: Journal

Defining reference: [\[MS-OXOJRNL\]](#) section 2.2.1.2

Alternate names: dispidLogTypeDesc

2.170 PidLidMeetingType

Canonical name: PidLidMeetingType

Description: Indicates the type of Meeting Request object or Meeting Update object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000026

Data type: PtypInteger32, 0x0003

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.5

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidMeetingType

2.171 PidLidMeetingWorkspaceUrl

Canonical name: PidLidMeetingWorkspaceUrl

Description: Specifies the URL of the **Meeting Workspace** that is associated with a Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008209

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/meetingworkspaceurl>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.48

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidMWSURL

2.172 PidLidMonthInterval

Canonical name: PidLidMonthInterval

Description: Indicates the monthly interval of the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000013

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/month_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.33

Alternate names: LID_MONTH_INTERVAL

2.173 PidLidMonthOfYear

Canonical name: PidLidMonthOfYear

Description: Indicates the month of the year in which the appointment or meeting occurs.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001006

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/monthofyear>

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.34

2.174 PidLidMonthOfYearMask

Canonical name: PidLidMonthOfYearMask

Description: Indicates the calculated month of the year in which the appointment or meeting occurs.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000017

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/moy_mask

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.35

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_MOY_MASK

2.175 PidLidNetShowUrl

Canonical name: PidLidNetShowUrl

Description: Specifies the URL to be launched when the user joins the meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008248

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.8

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidNetShowURL

2.176 PidLidNoEndDateFlag

Canonical name: PidLidNoEndDateFlag

Description: Indicates whether the recurrence pattern has an end date.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100B

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.36

Alternate names: <http://schemas.microsoft.com/mapi/fnoenddate>

2.177 PidLidNonSendableBcc

Canonical name: PidLidNonSendableBcc

Description: Contains a list of all of the unsendable attendees who are also resources.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008538

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/nonsendablebcc>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.21

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableBCC

2.178 PidLidNonSendableCc

Canonical name: PidLidNonSendableCc

Description: Contains a list of all of the unsendable attendees who are also optional attendees.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008537

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/nonsendablecc>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.20

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableCC

2.179 PidLidNonSendableTo

Canonical name: PidLidNonSendableTo

Description: Contains a list of all of the unsendable attendees who are also required attendees.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008536

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/nonsendableto>

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.19

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendableTo

2.180 PidLidNonSendBccTrackStatus

Canonical name: PidLidNonSendBccTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008545

Data type: PtypMultipleInteger32, 0x1003

WebDAV: <http://schemas.microsoft.com/mapi/nonsendbcctrackstatus>

Area: General Message Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.24

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendBccTrackStatus

2.181 PidLidNonSendCcTrackStatus

Canonical name: PidLidNonSendCcTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008544

Data type: PtypMultipleInteger32, 0x1003

WebDAV: <http://schemas.microsoft.com/mapi/nonsendcctrackstatus>

Area: General Message Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.23

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendCcTrackStatus

2.182 PidLidNonSendToTrackStatus

Canonical name: PidLidNonSendToTrackStatus

Description: Contains the value from the response table.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008543

Data type: PtypMultipleInteger32, 0x1003

WebDAV: <http://schemas.microsoft.com/mapi/nonsendtotrackstatus>

Area: General Message Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.22

Consuming references: [\[MS-XWDCAL\]](#)

Alternate names: dispidNonSendToTrackStatus

2.183 PidLidNoteColor

Canonical name: PidLidNoteColor

Description: Specifies the suggested background color of the **Note object**.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B00

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.1

Alternate names: dispidNoteColor

2.184 PidLidNoteHeight

Canonical name: PidLidNoteHeight

Description: Specifies the height of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B03

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.3

Alternate names: dispidNoteHeight

2.185 PidLidNoteWidth

Canonical name: PidLidNoteWidth

Description: Specifies the width of the visible message window in pixels.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B02

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.2

Alternate names: dispidNoteWidth

2.186 PidLidNoteX

Canonical name: PidLidNoteX

Description: Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a Note object.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B04

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.4

Alternate names: dispidNoteX

2.187 PidLidNoteY

Canonical name: PidLidNoteY

Description: Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a Note object.

Property set: PSETID_Note {0006200E-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008B05

Data type: PtypInteger32, 0x0003

Area: Sticky Notes

Defining reference: [\[MS-OXONOTE\]](#) section 2.2.1.5

Alternate names: dispidNoteY

2.188 PidLidOccurrences

Canonical name: PidLidOccurrences

Description: Indicates the number of occurrences in the recurring appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00001005

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/occurrences>

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.43

2.189 PidLidOldLocation

Canonical name: PidLidOldLocation

Description: Indicates the original value of the **PidLidLocation** property (section [2.159](#)) before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000028

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.7

Alternate names: dispidOldLocation

2.190 PidLidOldRecurrenceType

Canonical name: PidLidOldRecurrenceType

Description: Indicates the recurrence pattern for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000018

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/recur_type

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.44

Alternate names: LID_RECUR_TYPE

2.191 PidLidOldWhenEndWhole

Canonical name: PidLidOldWhenEndWhole

Description: Indicates the original value of the **PidLidAppointmentEndWhole** property (section [2.14](#)) before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000002A

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.9

Alternate names: dispidOldWhenEndWhole

2.192 PidLidOldWhenStartWhole

Canonical name: PidLidOldWhenStartWhole

Description: Indicates the original value of the **PidLidAppointmentStartWhole** property (section [2.29](#)) before a meeting update.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000029

Data type: PtypTime, 0x0040

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.6.8

Alternate names: dispidOldWhenStartWhole

2.193 PidLidOnlinePassword

Canonical name: PidLidOnlinePassword

Description: Specifies the password for a meeting on which the **PidLidConferencingType** property (section [2.66](#)) has the value 0x00000002.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008249

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.9

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: dispidOnlinePassword

2.194 PidLidOptionalAttendees

Canonical name: PidLidOptionalAttendees

Description: Specifies optional attendees.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000007

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/optional_attendees

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.45

Alternate names: LID_OPTIONAL_ATTENDEES

2.195 PidLidOrganizerAlias

Canonical name: PidLidOrganizerAlias

Description: Specifies the e-mail address of the organizer.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008243

Data type: PtypString, 0x001F

Area: Conferencing

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.50.6

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidOrgAlias

2.196 PidLidOriginalStoreEntryId

Canonical name: PidLidOriginalStoreEntryId

Description: Specifies the EntryID of the delegator's store.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008237

Data type: PtypBinary, 0x0102

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.9

Alternate names: dispidOrigStoreEid, <http://schemas.microsoft.com/mapi/origstoreid>

2.197 PidLidOtherAddress

Canonical name: PidLidOtherAddress

Description: Specifies the complete address of the contact's other address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801C

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:otherpostaladdress

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidOtherAddress

2.198 PidLidOtherAddressCountryCode

Canonical name: PidLidOtherAddressCountryCode

Description: Specifies the country code portion of the contact's other address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DC

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidOtherAddressCountryCode

2.199 PidLidOwnerCriticalChange

Canonical name: PidLidOwnerCriticalChange

Description: Specifies the date and time at which a Meeting Request object was sent by the organizer.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000001A

Data type: PtypTime, 0x0040

WebDAV: urn:schemas:calendar:dtstamp,
http://schemas.microsoft.com/mapi/owner_critical_change

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.34

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: LID_OWNER_CRITICAL_CHANGE

2.200 PidLidOwnerName

Canonical name: PidLidOwnerName

Description: Indicates the name of the owner of the **mailbox**.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000822E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/ownername

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.47

Alternate names: dispidOwnerName

2.201 PidLidPendingStateForTeamMailboxDocument

Note *All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.*

Canonical name: PidLidPendingStateForTeamMailboxDocument

Description: Specifies the synchronization state of the **Document object** that is in the Document Libraries folder of the team mailbox.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085E0

Data type: PtypInteger32, 0x0004

Area: Team Mailbox

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.34

Alternate names: dispidPendingStateforTMDocument

2.202 PidLidPercentComplete

Canonical name: PidLidPercentComplete

Description: Indicates whether a time-flagged Message object is complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008102

Data type: PtypFloating64, 0x0005

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.2.3

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidPercentComplete

2.203 PidLidPostalAddressId

Canonical name: PidLidPostalAddressId

Description: Specifies which physical address is the mailing address for this contact.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008022

Data type: PtypInteger32, 0x0003

WebDAV: urn:schemas:contacts:mailingaddressid

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.9

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidPostalAddressId

2.204 PidLidPostRssChannel

Canonical name: PidLidPostRssChannel

Description: Contains the contents of the title field from the **XML** of the Atom feed or RSS channel.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008904

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.5

Alternate names: dispidPostRssChannel

2.205 PidLidPostRssChannelLink

Canonical name: PidLidPostRssChannelLink

Description: Contains the URL of the RSS or Atom feed from which the XML file came.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008900

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.1

Alternate names: dispidPostRssChannelLink

2.206 PidLidPostRssItemGuid

Canonical name: PidLidPostRssItemGuid

Description: Contains a unique identifier for the RSS object.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008903

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.4

Alternate names: dispidPostRssItemGuid

2.207 PidLidPostRssItemHash

Canonical name: PidLidPostRssItemHash

Description: Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008902

Data type: PtypInteger32, 0x0003

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.3

Alternate names: dispidPostRssItemHash

2.208 PidLidPostRssItemLink

Canonical name: PidLidPostRssItemLink

Description: Contains the URL of the link from an RSS or Atom item.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008901

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.2

Alternate names: dispidPostRssItemLink

2.209 PidLidPostRssItemXml

Canonical name: PidLidPostRssItemXml

Description: Contains the item element and all of its sub-elements from an RSS feed, or the entry element and all of its sub-elements from an Atom feed.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008905

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.6

Alternate names: dispidPostRssItemXml

2.210 PidLidPostRssSubscription

Canonical name: PidLidPostRssSubscription

Description: Contains the user's preferred name for the RSS or Atom subscription.

Property set: PSETID_PostRss {00062041-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008906

Data type: PtypString, 0x001F

Area: RSS

Defining reference: [\[MS-OXORSS\]](#) section 2.2.1.7

Alternate names: dispidPostRssSubscription

2.211 PidLidPrivate

Canonical name: PidLidPrivate

Description: Indicates whether the end user wishes for this Message object to be hidden from other users who have access to the Message object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008506

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.15

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidPrivate

2.212 PidLidPromptSendUpdate

Canonical name: PidLidPromptSendUpdate

Description: Indicates that the Meeting Response object was out-of-date when it was received.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008045

Data type: PtypBoolean, 0x000B

Area: Meeting Response

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.7.8

Alternate names: dispidPromptSendUpdate

2.213 PidLidRecurrenceDuration

Canonical name: PidLidRecurrenceDuration

Description: Identifies the length, in minutes, of the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000100D

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/recurduration

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.48

2.214 PidLidRecurrencePattern

Canonical name: PidLidRecurrencePattern

Description: Specifies a description of the recurrence pattern of the Calendar object.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008232

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/recurpattern

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.46

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurPattern

2.215 PidLidRecurrenceType

Canonical name: PidLidRecurrenceType

Description: Specifies the recurrence type of the recurring series.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008231

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/recurtype

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.45

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurType

2.216 PidLidRecurring

Canonical name: PidLidRecurring

Description: Specifies whether the object represents a recurring series.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008223

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/recurring

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidRecurring

2.217 PidLidReferenceEntryId

Canonical name: PidLidReferenceEntryId

Description: Specifies the value of the EntryID of the Contact object unless the Contact object is a copy of an earlier original.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BD

Data type: PtypBinary, 0x0102

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.1

Alternate names: dispidReferenceEID

2.218 PidLidReferredBy

Canonical name: PidLidReferredBy

Description: Specifies the name of the person who referred the contact to the user.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000800E

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:referredby

Area: Contact Properties

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.5

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidReferredBy

2.219 PidLidReminderDelta

Canonical name: PidLidReminderDelta

Description: Specifies the interval, in minutes, between the time at which the reminder first becomes overdue and the start time of the Calendar object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008501

Data type: PtypInteger32, 0x0003

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidReminderDelta, <http://schemas.microsoft.com/mapi/reminddelta>

2.220 PidLidReminderFileParameter

Canonical name: PidLidReminderFileParameter

Description: Specifies the filename of the sound that a client is to play when the reminder for that object becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851F

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/reminderfileparam>

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.7

Consuming reference: [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidReminderFileParam

2.221 PidLidReminderOverride

Canonical name: PidLidReminderOverride

Description: Specifies whether the client is to respect the current values of the **PidLidReminderPlaySound** property (section [2.222](#)) and the **PidLidReminderFileParameter** property (section [2.220](#)), or use the default values for those properties.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851C

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderoverride

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.5

Consuming reference: [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidReminderOverride

2.222 PidLidReminderPlaySound

Canonical name: PidLidReminderPlaySound

Description: Specifies whether the client is to play a sound when the reminder becomes overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851E

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderplaysound

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.6

Consuming reference: [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

Alternate names: dispidReminderPlaySound

2.223 PidLidReminderSet

Canonical name: PidLidReminderSet

Description: Specifies whether a reminder is set on the object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008503

Data type: PtypBoolean, 0x000B

WebDAV: http://schemas.microsoft.com/mapi/reminderset

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidReminderSet

2.224 PidLidReminderSignalTime

Canonical name: PidLidReminderSignalTime

Description: Specifies the point in time when a reminder transitions from pending to overdue.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008560

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindernexttime

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidReminderNextTime

2.225 PidLidReminderTime

Canonical name: PidLidReminderTime

Description: Specifies the initial **signal time** for objects that are not Calendar objects.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008502

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertime

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderTime

2.226 PidLidReminderTimeDate

Canonical name: PidLidReminderTimeDate

Description: Indicates the time and date of the reminder for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008505

Data type: PtypTime, 0x0040

WebDAV: http://schemas.microsoft.com/mapi/remindertimedate

Area: Reminders

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.59

Alternate names: dispidReminderTimeDate

2.227 PidLidReminderTimeTime

Canonical name: PidLidReminderTimeTime

Description: Indicates the time of the reminder for the appointment or meeting.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008504

Data type: PtypTime, 0x0040

WebDAV: <http://schemas.microsoft.com/mapi/remindertime>

Area: Reminders

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.60

Consuming references: [\[MS-OXONOTE\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidReminderTimeTime

2.228 PidLidReminderType

Canonical name: PidLidReminderType

Description: This property is not set and, if set, is ignored.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000851D

Data type: PtypInteger32, 0x0003

Area: Reminders

Defining reference: [\[MS-OXORMDR\]](#) section 2.2.1.9

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: dispidReminderType, <http://schemas.microsoft.com/mapi/remindertype>

2.229 PidLidRemoteStatus

Canonical name: PidLidRemoteStatus

Description: Indicates the remote status of the calendar item.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008511

Data type: PtypInteger32, 0x0003

WebDAV: <http://schemas.microsoft.com/mapi/remotestatus>

Area: Run-time configuration

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.62

Alternate names: dispidRemoteStatus

2.230 PidLidRequiredAttendees

Canonical name: PidLidRequiredAttendees

Description: Identifies required attendees for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000006

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/required_attendees

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.63

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_REQUIRED_ATTENDEES

2.231 PidLidResourceAttendees

Canonical name: PidLidResourceAttendees

Description: Identifies resource attendees for the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000008

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/resource_attendees

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.64

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_RESOURCE_ATTENDEES

2.232 PidLidResponseStatus

Canonical name: PidLidResponseStatus

Description: Specifies the response status of an attendee.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008218

Data type: PtypInteger32, 0x0003

WebDAV: urn:schemas:calendar:attendeestatus,
http://schemas.microsoft.com/mapi/responsestatus

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.11

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidResponseStatus

2.233 PidLidServerProcessed

Canonical name: PidLidServerProcessed

Description: Indicates whether the Meeting Request object or Meeting Update object has been processed.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CC

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.4

Alternate names: dispidExchangeProcessed

2.234 PidLidServerProcessingActions

Canonical name: PidLidServerProcessingActions

Description: Indicates what processing actions have been taken on this Meeting Request object or Meeting Update object.

Property set: PSETID_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

Property long ID (LID): 0x000085CD

Data type: PtypInteger32, 0x0003

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.5

Alternate names: dispidExchangeProcessingAction

2.235 PidLidSharingAnonymity

Canonical name: PidLidSharingAnonymity

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A19

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingAnonymity

2.236 PidLidSharingBindingEntryId

Canonical name: PidLidSharingBindingEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2D

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingBindingEid

2.237 PidLidSharingBrowseUrl

Canonical name: PidLidSharingBrowseUrl

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A51

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingBrowseUrl

2.238 PidLidSharingCapabilities

Canonical name: PidLidSharingCapabilities

Description: Indicates that the Message object relates to a **special folder**.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A17

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.1

Alternate names: dispidSharingCaps

2.239 PidLidSharingConfigurationUrl

Canonical name: PidLidSharingConfigurationUrl

Description: Contains a zero-length string.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A24

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.3

Alternate names: dispidSharingConfigUrl

2.240 PidLidSharingDataRangeEnd

Canonical name: PidLidSharingDataRangeEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A45

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingDataRangeEnd

2.241 PidLidSharingDataRangeStart

Canonical name: PidLidSharingDataRangeStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A44

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingDataRangeStart

2.242 PidLidSharingDetail

Canonical name: PidLidSharingDetail

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingDetail

2.243 PidLidSharingExtensionXml

Canonical name: PidLidSharingExtensionXml

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A21

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingExtXml

2.244 PidLidSharingFilter

Canonical name: PidLidSharingFilter

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A13

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingFilter

2.245 PidLidSharingFlags

Canonical name: PidLidSharingFlags

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingFlags

2.246 PidLidSharingFlavor

Canonical name: PidLidSharingFlavor

Description: Indicates the type of Sharing Message object.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A18

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.5

Alternate names: dispidSharingFlavor

2.247 PidLidSharingFolderEntryId

Canonical name: PidLidSharingFolderEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A15

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingFolderEid

2.248 PidLidSharingIndexEntryId

Canonical name: PidLidSharingIndexEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2E

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingIndexEid

2.249 PidLidSharingInitiatorEntryId

Canonical name: PidLidSharingInitiatorEntryId

Description: Contains the value of the **PidTagEntryId** property (section [2.756](#)) for the Address Book object of the currently logged-on user.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A09

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.7

Alternate names: dispidSharingInitiatorEid

2.250 PidLidSharingInitiatorName

Canonical name: PidLidSharingInitiatorName

Description: Contains the value of the **PidTagDisplayName** property (section [2.749](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.249](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A07

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.8

Alternate names: dispidSharingInitiatorName

2.251 PidLidSharingInitiatorSntp

Canonical name: PidLidSharingInitiatorSntp

Description: Contains the value of the **PidTagSntpAddress** property (section [2.1086](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.249](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A08

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.9

Alternate names: dispidSharingInitiatorSntp

2.252 PidLidSharingInstanceGuid

Canonical name: PidLidSharingInstanceGuid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1C

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingInstanceGuid

2.253 PidLidSharingLastAutoSyncTime

Canonical name: PidLidSharingLastAutoSyncTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A55

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLastAutoSync

2.254 PidLidSharingLastSyncTime

Canonical name: PidLidSharingLastSyncTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1F

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLastSync

2.255 PidLidSharingLocalComment

Canonical name: PidLidSharingLocalComment

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLocalComment

2.256 PidLidSharingLocalLastModificationTime

Canonical name: PidLidSharingLocalLastModificationTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A23

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLocalLastMod

2.257 PidLidSharingLocalName

Canonical name: PidLidSharingLocalName

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0F

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLocalName

2.258 PidLidSharingLocalPath

Canonical name: PidLidSharingLocalPath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0E

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLocalPath

2.259 PidLidSharingLocalStoreUid

Canonical name: PidLidSharingLocalStoreUid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A49

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLocalStoreUid

2.260 PidLidSharingLocalType

Canonical name: PidLidSharingLocalType

Description: Contains the value of the **PidTagContainerClass** property (section [2.716](#)) of the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A14

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.10

Alternate names: dispidSharingLocalType

2.261 PidLidSharingLocalUid

Canonical name: PidLidSharingLocalUid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A10

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingLocalUid

2.262 PidLidSharingOriginalMessageEntryId

Canonical name: PidLidSharingOriginalMessageEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A29

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingOriginalMessageEid

2.263 PidLidSharingParentBindingEntryId

Canonical name: PidLidSharingParentBindingEntryId

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A5C

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingParentBindingEid

2.264 PidLidSharingParticipants

Canonical name: PidLidSharingParticipants

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1E

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingParticipants

2.265 PidLidSharingPermissions

Canonical name: PidLidSharingPermissions

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingPermissions

2.266 PidLidSharingProviderExtension

Canonical name: PidLidSharingProviderExtension

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0B

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingProviderExtension

2.267 PidLidSharingProviderGuid

Canonical name: PidLidSharingProviderGuid

Description: Contains the value "%xAE.F0.06.00.00.00.00.C0.00.00.00.00.00.46".

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A01

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.12

Alternate names: dispidSharingProviderGuid

2.268 PidLidSharingProviderName

Canonical name: PidLidSharingProviderName

Description: Contains a user-displayable name of the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.267](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A02

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.14

Alternate names: dispidSharingProviderName

2.269 PidLidSharingProviderUrl

Canonical name: PidLidSharingProviderUrl

Description: Contains a URL related to the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.267](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A03

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.16

Alternate names: dispidSharingProviderUrl

2.270 PidLidSharingRangeEnd

Canonical name: PidLidSharingRangeEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A47

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRangeEnd

2.271 PidLidSharingRangeStart

Canonical name: PidLidSharingRangeStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A46

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRangeStart

2.272 PidLidSharingReciprocation

Canonical name: PidLidSharingReciprocation

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingReciprocation

2.273 PidLidSharingRemoteByteSize

Canonical name: PidLidSharingRemoteByteSize

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4B

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Consuming reference: [MS-OXSHARE]

Alternate names: dispidSharingRemoteByteSize

2.274 PidLidSharingRemoteComment

Canonical name: PidLidSharingRemoteComment

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2F

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemoteComment

2.275 PidLidSharingRemoteCrc

Canonical name: PidLidSharingRemoteCrc

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4C

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemoteCrc

2.276 PidLidSharingRemoteLastModificationTime

Canonical name: PidLidSharingRemoteLastModificationTime

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A22

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemoteLastMod

2.277 PidLidSharingRemoteMessageCount

Canonical name: PidLidSharingRemoteMessageCount

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4F

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemoteMsgCount

2.278 PidLidSharingRemoteName

Canonical name: PidLidSharingRemoteName

Description: Contains the value of the **PidTagDisplayName** property (section [2.749](#)) on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A05

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.1

Alternate names: dispidSharingRemoteName

2.279 PidLidSharingRemotePass

Canonical name: PidLidSharingRemotePass

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemotePass

2.280 PidLidSharingRemotePath

Canonical name: PidLidSharingRemotePath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A04

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemotePath

2.281 PidLidSharingRemoteStoreUid

Canonical name: PidLidSharingRemoteStoreUid

Description: Contains a hexadecimal string representation of the value of the **PidTagStoreEntryId** property (section [2.1094](#)) on the folder being shared.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A48

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.3

Alternate names: dispidSharingRemoteStoreUid

2.282 PidLidSharingRemoteType

Canonical name: PidLidSharingRemoteType

Description: Contains the same value as the **PidLidSharingLocalType** property (section [2.260](#)).

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A1D

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.5

Alternate names: dispidSharingRemoteType

2.283 PidLidSharingRemoteUid

Canonical name: PidLidSharingRemoteUid

Description: Contains the EntryID of the folder being shared.

Property set: PSTID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A06

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.7

Alternate names: dispidSharingRemoteUid

2.284 PidLidSharingRemoteUser

Canonical name: PidLidSharingRemoteUser

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A0C

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemoteUser

2.285 PidLidSharingRemoteVersion

Canonical name: PidLidSharingRemoteVersion

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A5B

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRemoteVersion

2.286 PidLidSharingResponseTime

Canonical name: PidLidSharingResponseTime

Description: Contains the time at which the recipient (1) of the sharing request sent a sharing response.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A28

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.1

Alternate names: dispidSharingResponseTime

2.287 PidLidSharingResponseType

Canonical name: PidLidSharingResponseType

Description: Contains the type of response with which the recipient (1) of the sharing request responded.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A27

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.4.2

Alternate names: dispidSharingResponseType

2.288 PidLidSharingRoamLog

Canonical name: PidLidSharingRoamLog

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A4E

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingRoamLog

2.289 PidLidSharingStart

Canonical name: PidLidSharingStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A25

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingStart

2.290 PidLidSharingStatus

Canonical name: PidLidSharingStatus

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A00

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingStatus

2.291 PidLidSharingStop

Canonical name: PidLidSharingStop

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A26

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingStop

2.292 PidLidSharingSyncFlags

Canonical name: PidLidSharingSyncFlags

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A60

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingSyncFlags

2.293 PidLidSharingSyncInterval

Canonical name: PidLidSharingSyncInterval

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2A

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingSyncInterval

2.294 PidLidSharingTimeToLive

Canonical name: PidLidSharingTimeToLive

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A2C

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingTimeToLive

2.295 PidLidSharingTimeToLiveAuto

Canonical name: PidLidSharingTimeToLiveAuto

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A56

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingTimeToLiveAuto

2.296 PidLidSharingWorkingHoursDays

Canonical name: PidLidSharingWorkingHoursDays

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A42

Data type: PtypInteger32, 0x0003

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingWorkingHoursDays

2.297 PidLidSharingWorkingHoursEnd

Canonical name: PidLidSharingWorkingHoursEnd

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A41

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingWorkingHoursEnd

2.298 PidLidSharingWorkingHoursStart

Canonical name: PidLidSharingWorkingHoursStart

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A40

Data type: PtypTime, 0x0040

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingWorkingHoursStart

2.299 PidLidSharingWorkingHoursTimeZone

Canonical name: PidLidSharingWorkingHoursTimeZone

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PSETID_Sharing {00062040-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008A43

Data type: PtypBinary, 0x0102

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

Alternate names: dispidSharingWorkingHoursTZ

2.300 PidLidSideEffects

Canonical name: PidLidSideEffects

Description: Specifies how a Message object is handled by the client in relation to certain user interface actions by the user, such as deleting a message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008510

Data type: PtypInteger32, 0x0003

Area: Run-time configuration

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.16

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidSideEffects

2.301 PidLidSingleBodyICal

Canonical name: PidLidSingleBodyICal

Description: Indicates that the original MIME message contained a single **MIME** part.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000827B

Data type: PtypBoolean, 0x000B

Area: Calendar

Defining reference: [\[MS-OXCICAL\]](#) section 2.2.2

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: IsSingleBodyICal, dispidIsSingleBodyICal

2.302 PidLidSmartNoAttach

Canonical name: PidLidSmartNoAttach

Description: Indicates whether the Message object has no end-user visible attachments.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008514

Data type: PtypBoolean, 0x000B

Area: Run-time configuration

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.14

Alternate names: dispidSmartNoAttach

2.303 PidLidSpamOriginalFolder

Canonical name: PidLidSpamOriginalFolder

Description: Specifies which folder a message was in before it was filtered into the Junk E-mail folder.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000859C

Data type: PtypBinary, 0x0102

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.1.1

Alternate names: dispidSpamOriginalFolder

2.304 PidLidStartRecurrenceDate

Canonical name: PidLidStartRecurrenceDate

Description: Identifies the start date of the recurrence pattern.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000D

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_date

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.66

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_START_RECUR_DATE

2.305 PidLidStartRecurrenceTime

Canonical name: PidLidStartRecurrenceTime

Description: Identifies the start time of the recurrence pattern.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000E

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/start_recur_time

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.67

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXCICAL\]](#)

Alternate names: LID_START_RECUR_TIME

2.306 PidLidTaskAcceptanceState

Canonical name: PidLidTaskAcceptanceState

Description: Indicates the acceptance state of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000812A

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.30

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidTaskDelegValue

2.307 PidLidTaskAccepted

Canonical name: PidLidTaskAccepted

Description: Indicates whether a task assignee has replied to a **task request** for this **Task object**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008108

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.7

Consuming reference: [\[MS-OXOSFLD\]](#)

Alternate names: dispidTaskAccepted

2.308 PidLidTaskActualEffort

Canonical name: PidLidTaskActualEffort

Description: Indicates the number of minutes that the user actually spent working on a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008110

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskActualEffort

2.309 PidLidTaskAssigner

Canonical name: PidLidTaskAssigner

Description: Specifies the name of the user that last assigned the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008121

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.24

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskDelegator

2.310 PidLidTaskAssigners

Canonical name: PidLidTaskAssigners

Description: Contains a stack of entries, each of which represents a task assigner.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008117

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.16

Alternate names: dispidTaskMyDelegators

2.311 PidLidTaskComplete

Canonical name: PidLidTaskComplete

Description: Indicates that the task is complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811C

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.20

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskComplete

2.312 PidLidTaskCustomFlags

Canonical name: PidLidTaskCustomFlags

Description: The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008139

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.33

Alternate names: dispidTaskCustomFlags

2.313 PidLidTaskDateCompleted

Canonical name: PidLidTaskDateCompleted

Description: Specifies the date when the user completed work on the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000810F

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.9

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#)

Alternate names: dispidTaskDateCompleted

2.314 PidLidTaskDeadOccurrence

Canonical name: PidLidTaskDeadOccurrence

Description: Indicates whether new occurrences remain to be generated.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008109

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.8

Alternate names: dispidTaskDeadOccur

2.315 PidLidTaskDueDate

Canonical name: PidLidTaskDueDate

Description: Specifies the date by which the user expects work on the task to be complete.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008105

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskDueDate

2.316 PidLidTaskEstimatedEffort

Canonical name: PidLidTaskEstimatedEffort

Description: Indicates the number of minutes that the user expects to work on a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008111

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidTaskEstimatedEffort

2.317 PidLidTaskFCreator

Canonical name: PidLidTaskFCreator

Description: Indicates that the Task object was originally created by the action of the current user or user agent instead of by the processing of a task request.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811E

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.21

Alternate names: dispidTaskFCreator

2.318 PidLidTaskFFixOffline

Canonical name: PidLidTaskFFixOffline

Description: Indicates the accuracy of the **PidLidTaskOwner** property (section [2.329](#)).

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000812C

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.31

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskFFixOffline

2.319 PidLidTaskFRecurring

Canonical name: PidLidTaskFRecurring

Description: Indicates whether the task includes a recurrence pattern.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008126

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.28

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskFRecur

2.320 PidLidTaskGlobalId

Canonical name: PidLidTaskGlobalId

Description: Contains a unique GUID for this task, which is used to locate an existing task upon receipt of a task response or task update.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008519

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.32

Alternate names: dispidTaskGlobalObjId

2.321 PidLidTaskHistory

Canonical name: PidLidTaskHistory

Description: Indicates the type of change that was last made to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811A

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.18

Alternate names: dispidTaskHistory

2.322 PidLidTaskLastDelegate

Canonical name: PidLidTaskLastDelegate

Description: Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008125

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.27

Alternate names: dispidTaskLastDelegate

2.323 PidLidTaskLastUpdate

Canonical name: PidLidTaskLastUpdate

Description: Contains the date and time of the most recent change made to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008115

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.10

Alternate names: dispidTaskLastUpdate

2.324 PidLidTaskLastUser

Canonical name: PidLidTaskLastUser

Description: Contains the name of the most recent user to have been the owner of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008122

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.25

Alternate names: dispidTaskLastUser

2.325 PidLidTaskMode

Canonical name: PidLidTaskMode

Description: Specifies the assignment status of the embedded Task object.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008518

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.3.2

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#)

Alternate names: dispidTaskMode

2.326 PidLidTaskMultipleRecipients

Canonical name: PidLidTaskMultipleRecipients

Description: Provides optimization hints about the recipients (2) of a Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008120

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.23

Alternate names: dispidTaskMultRecips

2.327 PidLidTaskNoCompute

Canonical name: PidLidTaskNoCompute

Description: Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008124

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.35

Consuming reference: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskNoCompute

2.328 PidLidTaskOrdinal

Canonical name: PidLidTaskOrdinal

Description: Provides an aid to custom sorting of Task objects.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008123

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.26

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskOrdinal

2.329 PidLidTaskOwner

Canonical name: PidLidTaskOwner

Description: Contains the name of the owner of the task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811F

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.22

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskOwner

2.330 PidLidTaskOwnership

Canonical name: PidLidTaskOwnership

Description: Indicates the role of the current user relative to the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008129

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.29

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskOwnership

2.331 PidLidTaskRecurrence

Canonical name: PidLidTaskRecurrence

Description: Contains a **RecurrencePattern** structure that provides information about **recurring tasks**.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008116

Data type: PtypBinary, 0x0102

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.15

Consuming references: [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskRecur

2.332 PidLidTaskResetReminder

Canonical name: PidLidTaskResetReminder

Description: Indicates whether future **instances** of recurring tasks need reminders, even though the value of the **PidLidReminderSet** property (section [2.223](#)) is 0x00.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008107

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.6

Consuming references: [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskResetReminder

2.333 PidLidTaskRole

Canonical name: PidLidTaskRole

Description: Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008127

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.34

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskRole

2.334 PidLidTaskStartDate

Canonical name: PidLidTaskStartDate

Description: Specifies the date on which the user expects work on the task to begin.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008104

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.4

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: dispidTaskStartDate

2.335 PidLidTaskState

Canonical name: PidLidTaskState

Description: Indicates the current assignment state of the Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008113

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.14

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskState

2.336 PidLidTaskStatus

Canonical name: PidLidTaskStatus

Description: Specifies the status of a task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008101

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.2

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: dispidTaskStatus

2.337 PidLidTaskStatusOnComplete

Canonical name: PidLidTaskStatusOnComplete

Description: Indicates whether the task assignee has been requested to send an e-mail message update upon completion of the assigned task.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008119

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.17

Alternate names: dispidTaskSOC

2.338 PidLidTaskUpdates

Canonical name: PidLidTaskUpdates

Description: Indicates whether the task assignee has been requested to send a task update when the assigned Task object changes.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000811B

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.19

Alternate names: dispidTaskUpdates

2.339 PidLidTaskVersion

Canonical name: PidLidTaskVersion

Description: Indicates which copy is the latest update of a Task object.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008112

Data type: PtypInteger32, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.13

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

Alternate names: dispidTaskVersion

2.340 PidLidTeamTask

Canonical name: PidLidTeamTask

Description: This property is set by the client but is ignored by the server.

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008103

Data type: PtypBoolean, 0x000B

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.2.2.36

Consuming References: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

Alternate names: dispidTeamTask

2.341 PidLidTimeZone

Canonical name: PidLidTimeZone

Description: Specifies information about the time zone of a recurring meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x0000000C

Data type: PtypInteger32, 0x0003

WebDAV: http://schemas.microsoft.com/mapi/time_zone

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.6

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_TIME_ZONE

2.342 PidLidTimeZoneDescription

Canonical name: PidLidTimeZoneDescription

Description: Specifies a human-readable description of the time zone that is represented by the data in the **PidLidTimeZoneStruct** property (section [2.343](#)).

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008234

Data type: PtypString, 0x001F

WebDAV: <http://schemas.microsoft.com/mapi/timezonedesc>

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.40

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidTimeZoneDesc

2.343 PidLidTimeZoneStruct

Canonical name: PidLidTimeZoneStruct

Description: Specifies time zone information for a recurring meeting.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008233

Data type: PtypBinary, 0x0102

WebDAV: <http://schemas.microsoft.com/mapi/timezonestruct>

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.39

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

Alternate names: dispidTimeZoneStruct

2.344 PidLidToAttendeesString

Canonical name: PidLidToAttendeesString

Description: Contains a list of all of the sendable attendees who are also required attendees.

Property set: PSETID_Appointment {00062002-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823B

Data type: PtypString, 0x001F

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.17

Alternate names: dispidToAttendeesString

2.345 PidLidToDoOrdinalDate

Canonical name: PidLidToDoOrdinalDate

Description: Contains the current time, in UTC, which is used to determine the sort order of objects in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A0

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.13

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: dispidToDoOrdinalDate

2.346 PidLidToDoSubOrdinal

Canonical name: PidLidToDoSubOrdinal

Description: Contains the numerals 0 through 9 that are used to break a tie when the **PidLidToDoOrdinalDate** property (section [2.345](#)) is used to perform a sort of objects.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A1

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.14

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: dispidToDoSubOrdinal

2.347 PidLidToDoTitle

Canonical name: PidLidToDoTitle

Description: Contains user-specifiable text to identify this Message object in a consolidated to-do list.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085A4

Data type: PtypString, 0x001F

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

Alternate names: dispidToDoTitle

2.348 PidLidTrustRecipientHighlights

Canonical name: PidLidTrustRecipientHighlights

Description:

Property set: PSETID_Task {00062003-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000823E

Data type: PtypBoolean, 0x000B

Area: Meetings

Defining reference:

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: dispidTrustRecipHighlights

2.349 PidLidUseTnef

Canonical name: PidLidUseTnef

Description: Specifies whether **Transport Neutral Encapsulation Format (TNEF)** is to be included on a message when the message is converted from TNEF to MIME or SMTP format.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008582

Data type: PtypBoolean, 0x000B

Area: Run-time configuration

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.62

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: dispidUseTNEF

2.350 PidLidValidFlagStringProof

Canonical name: PidLidValidFlagStringProof

Description: Contains the value of the **PidTagMessageDeliveryTime** property (section [2.860](#)) when modifying the **PidLidFlagRequest** property (section [2.136](#)).

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x000085BF

Data type: PtypTime, 0x0040

Area: Tasks

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.11

Consuming references: [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOTASK\]](#)

Alternate names: dispidValidFlagStringProof

2.351 PidLidVerbResponse

Canonical name: PidLidVerbResponse

Description: Specifies the voting option that a respondent has selected.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008524

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.71

Alternate names: dispidVerbResponse

2.352 PidLidVerbStream

Canonical name: PidLidVerbStream

Description: Specifies what voting responses the user can make in response to the message.

Property set: PSETID_Common {00062008-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008520

Data type: PtypBinary, 0x0102

Area: Run-time configuration

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.70

Alternate names: dispidVerbStream

2.353 PidLidWeddingAnniversaryLocal

Canonical name: PidLidWeddingAnniversaryLocal

Description: Specifies the wedding anniversary of the contact, at midnight in the client's local time zone, and is saved without any time zone conversions.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DF

Data type: PtypTime, 0x0040

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.5.5

Alternate names: dispidApptAnniversaryLocal

2.354 PidLidWeekInterval

Canonical name: PidLidWeekInterval

Description: Identifies the number of weeks that occur between each meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000012

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/week_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.71

Consuming references: [\[MS-OXOCAL\]](#)

Alternate names: LID_WEEK_INTERVAL

2.355 PidLidWhere

Canonical name: PidLidWhere

Description: Contains the value of the **PidLidLocation** property (section [2.159](#)) from the associated Meeting object.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000002

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/mapi/where

Area: Meetings

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.3

Consuming reference: [\[MS-XWDCAL\]](#)

Alternate names: LID_WHERE

2.356 PidLidWorkAddress

Canonical name: PidLidWorkAddress

Description: Specifies the complete address of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000801B

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:workaddress

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddress

2.357 PidLidWorkAddressCity

Canonical name: PidLidWorkAddressCity

Description: Specifies the city or locality portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008046

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:l

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressCity

2.358 PidLidWorkAddressCountry

Canonical name: PidLidWorkAddressCountry

Description: Specifies the country or region portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008049

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:co

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressCountry

2.359 PidLidWorkAddressCountryCode

Canonical name: PidLidWorkAddressCountryCode

Description: Specifies the country code portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x000080DB

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

Alternate names: dispidWorkAddressCountryCode

2.360 PidLidWorkAddressPostalCode

Canonical name: PidLidWorkAddressPostalCode

Description: Specifies the postal code (ZIP code) portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008048

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postalcode

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressPostalCode

2.361 PidLidWorkAddressPostOfficeBox

Canonical name: PidLidWorkAddressPostOfficeBox

Description: Specifies the post office box portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C00-000000000046}

Property long ID (LID): 0x0000804A

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:postofficebox

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressPostOfficeBox

2.362 PidLidWorkAddressState

Canonical name: PidLidWorkAddressState

Description: Specifies the state or province portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008047

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:st

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

Consuming references: [\[MS-XWDCNTC\]](#)

Alternate names: dispidWorkAddressState

2.363 PidLidWorkAddressStreet

Canonical name: PidLidWorkAddressStreet

Description: Specifies the street portion of the contact's work address.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x00008045

Data type: PtypString, 0x001F

WebDAV: urn:schemas:contacts:street

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: dispidWorkAddressStreet

2.364 PidLidYearInterval

Canonical name: PidLidYearInterval

Description: Indicates the yearly interval of the appointment or meeting.

Property set: PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

Property long ID (LID): 0x00000014

Data type: PtypInteger16, 0x0002

WebDAV: http://schemas.microsoft.com/mapi/year_interval

Area: Meetings

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.7.73

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: LID_YEAR_INTERVAL

2.365 PidLidYomiCompanyName

Canonical name: PidLidYomiCompanyName

Description: Specifies the phonetic pronunciation of the contact's company name.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802E

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomiorganization

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.6.8

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiCompanyName

2.366 PidLidYomiFirstName

Canonical name: PidLidYomiFirstName

Description: Specifies the phonetic pronunciation of the contact's given name.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802C

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomifirstname

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.9

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiFirstName

2.367 PidLidYomiLastName

Canonical name: PidLidYomiLastName

Description: Specifies the phonetic pronunciation of the contact's surname.

Property set: PSETID_Address {00062004-0000-0000-C000-000000000046}

Property long ID (LID): 0x0000802D

Data type: PtypString, 0x001F

WebDAV: http://schemas.microsoft.com/exchange/yomilastname

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.10

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: dispidYomiLastName

2.368 PidNameAcceptLanguage

Canonical name: PidNameAcceptLanguage

Description: Contains the value of the MIME Accept-Language header.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Accept-Language

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.42

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: AcceptLanguage

2.369 PidNameApplicationName

Canonical name: PidNameApplicationName

Description: Specifies the application used to open the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: AppName

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.9

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#NameOfApplication

2.370 PidNameApproved

Canonical name: PidNameApproved

Description: Specifies the address of the moderator that approved and posted a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Approved

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:approved

2.371 PidNameAttachmentMacContentType

Canonical name: PidNameAttachmentMacContentType

Description: Contains the Content-Type of the Mac attachment.

Property set: PSETID_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

Property name: AttachmentMacContentType

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

2.372 PidNameAttachmentMacInfo

Canonical name: PidNameAttachmentMacInfo

Description: Contains the headers and resource fork data associated with the Mac attachment.

Property set: PSETID_Attachment {96357f7f-59e1-47d0-99a7-46515c183b54}

Property name: AttachmentMacInfo

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

2.373 PidNameAudioNotes

Canonical name: PidNameAudioNotes

Description: Contains textual annotations to a voice message after it has been delivered to the user's mailbox.

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: UMAudioNotes

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.15

Alternate names: UMAudioNotes

2.374 PidNameAuthor

Canonical name: PidNameAuthor

Description: Specifies the author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Author

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.3

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Author

2.375 PidNameAutomaticSpeechRecognitionData

Canonical name: PidNameAutomaticSpeechRecognitionData

Description: Contains an unprotected voice message.

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: AsrData

Data type: PtypBinary, 0x0102

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.13

2.376 PidNameBcc

Canonical name: PidNameBcc

Description: Specifies the blind carbon copy addressees of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Bcc

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.2

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:bcc

2.377 PidNameByteCount

Canonical name: PidNameByteCount

Description: Specifies the size, in bytes, of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ByteCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.22

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Bytes

2.378 PidNameCalendarAttendeeRole

Canonical name: PidNameCalendarAttendeeRole

Description: Specifies the role of the attendee.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:attendeerole

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.7

Alternate names: urn:schemas:calendar:attendeerole

2.379 PidNameCalendarBusystatus

Canonical name: PidNameCalendarBusystatus

Description: Specifies whether the attendee is busy at the time of an appointment on their calendar.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:busystatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.8

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:busystatus

2.380 PidNameCalendarContact

Canonical name: PidNameCalendarContact

Description: Identifies the name of a contact who is an attendee of a meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contact

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.9

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:contact

2.381 PidNameCalendarContactUrl

Canonical name: PidNameCalendarContactUrl

Description: Identifies the URL where you can access contact information in **HTML** format.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:contacturl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.10

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:contacturl

2.382 PidNameCalendarCreated

Canonical name: PidNameCalendarCreated

Description: Identifies the date and time, in UTC, when the organizer created the appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:created

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.11

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:created

2.383 PidNameCalendarDescriptionUrl

Canonical name: PidNameCalendarDescriptionUrl

Description: Specifies the URL of a resource that contains a description of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:descriptionurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.12

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:descriptionurl

2.384 PidNameCalendarDuration

Canonical name: PidNameCalendarDuration

Description: Identifies the duration, in seconds, of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:duration

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.13

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:duration

2.385 PidNameCalendarExceptionDate

Canonical name: PidNameCalendarExceptionDate

Description: Identifies a list of dates that are exceptions to a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exdate

Data type: PtypMultipleTime, 0x1040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.14

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:exdate

2.386 PidNameCalendarExceptionRule

Canonical name: PidNameCalendarExceptionRule

Description: Specifies an exception rule for a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:exrule

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.15

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:exrule

2.387 PidNameCalendarGeoLatitude

Canonical name: PidNameCalendarGeoLatitude

Description: Specifies the geographical latitude of the location of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolatitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.16

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:geolatitude

2.388 PidNameCalendarGeoLongitude

Canonical name: PidNameCalendarGeoLongitude

Description: Specifies the geographical longitude of the location of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:geolongitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.17

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:geolongitude

2.389 PidNameCalendarInstanceType

Canonical name: PidNameCalendarInstanceType

Description: Specifies the type of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:instancetype

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.18

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:instancetype

2.390 PidNameCalendarIsOrganizer

Canonical name: PidNameCalendarIsOrganizer

Description: Specifies whether an attendee is the organizer of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:isorganizer

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.19

Alternate names: urn:schemas:calendar:isorganizer

2.391 PidNameCalendarLastModified

Canonical name: PidNameCalendarLastModified

Description: Specifies the date and time, in UTC, when an appointment was last modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:lastmodified

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.20

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:lastmodified

2.392 PidNameCalendarLocationUrl

Canonical name: PidNameCalendarLocationUrl

Description: Specifies a URL with location information in HTML format.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.21

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:locationurl

2.393 PidNameCalendarMeetingStatus

Canonical name: PidNameCalendarMeetingStatus

Description: Specifies the status of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:meetingstatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.22

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:meetingstatus

2.394 PidNameCalendarMethod

Canonical name: PidNameCalendarMethod

Description: Specifies the **iCalendar** method that is associated with an Appointment object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:method

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.23

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:method

2.395 PidNameCalendarProductId

Canonical name: PidNameCalendarProductId

Description: Identifies the product that created the iCalendar-formatted stream.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:prodid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.24

Alternate names: urn:schemas:calendar:prodid

2.396 PidNameCalendarRecurrenceIdRange

Canonical name: PidNameCalendarRecurrenceIdRange

Description: Specifies which instances of a recurring appointment are being referred to.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:recurrenceidrange

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.25

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:recurrenceidrange

2.397 PidNameCalendarReminderOffset

Canonical name: PidNameCalendarReminderOffset

Description: Identifies the number of seconds before an appointment starts that a reminder is to be displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:reminderoffset

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.26

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:reminderoffset

2.398 PidNameCalendarResources

Canonical name: PidNameCalendarResources

Description: Identifies a list of resources, such as rooms and video equipment, that are available for an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:resources

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.27

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:resources

2.399 PidNameCalendarRsvp

Canonical name: PidNameCalendarRsvp

Description: Specifies whether the organizer of an appointment or meeting requested a response.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rsvp

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.28

Alternate names: urn:schemas:calendar:rsvp

2.400 PidNameCalendarSequence

Canonical name: PidNameCalendarSequence

Description: Specifies the sequence number of a version of an appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:sequence

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.29

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:sequence

2.401 PidNameCalendarTimeZone

Canonical name: PidNameCalendarTimeZone

Description: Specifies the time zone of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezone

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.30

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:timezone

2.402 PidNameCalendarTimeZoneId

Canonical name: PidNameCalendarTimeZoneId

Description: Specifies the time zone identifier of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:timezoneid

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.31

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:timezoneid

2.403 PidNameCalendarTransparent

Canonical name: PidNameCalendarTransparent

Description: Specifies whether an appointment or meeting is visible to busy time searches.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:transparent

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.32

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:transparent

2.404 PidNameCalendarUid

Canonical name: PidNameCalendarUid

Description: Specifies the unique identifier of an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:uid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.33

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:uid

2.405 PidNameCalendarVersion

Canonical name: PidNameCalendarVersion

Description: Identifies the version of the iCalendar specification, as specified in [\[MS-OXCICAL\]](#) section 2.1.3.1.1.3, that is required to correctly interpret an iCalendar object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:version

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.34

Alternate names: urn:schemas:calendar:version

2.406 PidNameCategory

Canonical name: PidNameCategory

Description: Specifies the category of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Category

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.18

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Category

2.407 PidNameCc

Canonical name: PidNameCc

Description: Specifies the carbon copy addressees of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Cc

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.3

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:cc

2.408 PidNameCharacterCount

Canonical name: PidNameCharacterCount

Description: Specifies the character count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: CharCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.16

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Characters

2.409 PidNameComments

Canonical name: PidNameComments

Description: Specifies the comments of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Comments

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.5

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Comments

2.410 PidNameCompany

Canonical name: PidNameCompany

Description: Specifies the company for which the file was created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Company

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.21

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Company

2.411 PidNameContactsAlternateRecipient

Canonical name: PidNameContactsAlternateRecipient

Description: Specifies a secondary e-mail address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:alternaterecipient

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.13

Alternate names: urn:schemas:contacts:alternaterecipient

2.412 PidNameContactsCountry

Canonical name: PidNameContactsCountry

Description: Specifies the country/region code for the contact's work address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:c

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.14

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:c

2.413 PidNameContactsEmail1

Canonical name: PidNameContactsEmail1

Description: Specifies the primary e-mail address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email1

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.15

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email1

2.414 PidNameContactsEmail2

Canonical name: PidNameContactsEmail2

Description: Specifies a secondary e-mail address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email2

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.16

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email2

2.415 PidNameContactsEmail3

Canonical name: PidNameContactsEmail3

Description: Specifies a third e-mail address of the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:email3

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.17

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:email3

2.416 PidNameContactsFileAs

Canonical name: PidNameContactsFileAs

Description: Specifies the contact information in the format in which it is to be displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:fileas

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.18

Alternate names: urn:schemas:contacts:fileas

2.417 PidNameContactsFileasId

Canonical name: PidNameContactsFileasId

Description: Specifies a numeric value that determines how the contact information is displayed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:fileasid

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.19

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:fileasid

2.418 PidNameContactsHomeLatitude

Canonical name: PidNameContactsHomeLatitude

Description: Specifies the latitude of the contact's home address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:homelatitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.20

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:homelatitude

2.419 PidNameContactsHomeLongitude

Canonical name: PidNameContactsHomeLongitude

Description: Specifies the longitude of the contact's home address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:homelongitude

Data type: PtypFloating64, 0x0005

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.21

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:homelongitude

2.420 PidNameContactsHomeTimeZone

Canonical name: PidNameContactsHomeTimeZone

Description: Specifies the time zone of the contact's home address.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:hometimezone

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.22

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:hometimezone

2.421 PidNameContactsMapUrl

Canonical name: PidNameContactsMapUrl

Description: Specifies the map URL for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:mapurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.23

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:mapurl

2.422 PidNameContactsOtherCountryCode

Canonical name: PidNameContactsOtherCountryCode

Description: Specifies an alternative, two-letter country/region code for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:othercountrycode

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.24

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:othercountrycode

2.423 PidNameContactsOtherPager

Canonical name: PidNameContactsOtherPager

Description: Specifies a pager telephone number for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:otherpager

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.25

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:otherpager

2.424 PidNameContactsOtherTimeZone

Canonical name: PidNameContactsOtherTimeZone

Description: Specifies an alternate time zone for the contact.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:othertimezone

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.26

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:othertimezone

2.425 PidNameContactsProxyAddresses

Canonical name: PidNameContactsProxyAddresses

Description: Specifies one or more of the contact's e-mail addresses.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:proxyaddresses

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.27

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:proxyaddresses

2.426 PidNameContactsSecretaryUrl

Canonical name: PidNameContactsSecretaryUrl

Description: Specifies the URL to the contact's secretary.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:secretaryurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.28

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:secretaryurl

2.427 PidNameContactsSourceUrl

Canonical name: PidNameContactsSourceUrl

Description: Specifies the URL of the source from which the contact's information was obtained.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:contacts:sourceurl

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.3.29

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:contacts:sourceurl

2.428 PidNameContentBase

Canonical name: PidNameContentBase

Description: Specifies the value of the MIME Content-Base header, which defines the base **URI** for resolving relative URLs contained within the **message body (2)**.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Base

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.41

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: BodyContentBase

2.429 PidNameContentClass

Canonical name: PidNameContentClass

Description: Indicates the intent of an e-mail message based on the context of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Class

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.5.1

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDSTRUCTDOC\]](#)

Alternate names: DAV:contentclassDAV:contentclass, urn:schemas:mailheader:content-class

2.430 PidNameContentDisposition

Canonical name: PidNameContentDisposition

Description: Specifies the intended disposition of the **body part**.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Disposition

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.6

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-disposition

2.431 PidNameContentID

Canonical name: PidNameContentID

Description: Specifies a unique identifier for the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-ID

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.7

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-id

2.432 PidNameContentLanguage

Canonical name: PidNameContentLanguage

Description: Specifies the language identifier for the text content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Language

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.8

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-language

2.433 PidNameContentLocation

Canonical name: PidNameContentLocation

Description: Specifies the Uniform Resource Identifier (URI) that corresponds to the content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Location

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.9

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-location

2.434 PidNameContentTransferEncoding

Canonical name: PidNameContentTransferEncoding

Description: Specifies the encoding mechanism used to encode the content of the body part.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Transfer-Encoding

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.10

Alternate names: urn:schemas:mailheader:content-transfer-encoding

2.435 PidNameContentType

Canonical name: PidNameContentType

Description: Specifies the type of the body part content.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Content-Type

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.11

Consuming reference: [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:content-type

2.436 PidNameControl

Canonical name: PidNameControl

Description: Specifies a Usenet control command.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Control

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.12

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:control

2.437 PidNameCreateDateTimeReadOnly

Canonical name: PidNameCreateDateTimeReadOnly

Description: Specifies the time, in UTC, that the file was first created.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: CreateDtmRo

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.12

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Created

2.438 PidNameCrossReference

Canonical name: PidNameCrossReference

Description: Contains the name of the host (with **domains** omitted) and a white-space-separated list of colon-separated pairs of newsgroup names and message numbers.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Xref

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.51

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:xref

2.439 PidNameDavGetContentType

Canonical name: PidNameDavGetContentType

Description: Specifies the type of the Message object content.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:getcontenttype

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.1.3

2.440 PidNameDavId

Canonical name: PidNameDavId

Description: Specifies a unique ID for the calendar item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:id

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.2

Consuming reference: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:id

2.441 PidNameDavIsCollection

Canonical name: PidNameDavIsCollection

Description: Indicates whether a Calendar object is a collection.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:iscollection

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.3

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:iscollection

2.442 PidNameDavIsStructuredDocument

Canonical name: PidNameDavIsStructuredDocument

Description: Indicates whether a Calendar object is a structured document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:isstructureddocument

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.4

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:isstructureddocument

2.443 PidNameDavParentName

Canonical name: PidNameDavParentName

Description: Specifies the name of the **Folder object** that contains the Calendar object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:parentname

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.5

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:parentname

2.444 PidNameDavResourceType

Canonical name: PidNameDavResourceType

Description: Specifies that the Folder object is a search folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:resourcetype

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDSEARCH\]](#) section 2.2.3.3

Consuming references: [\[MS-XWDEXT\]](#), [\[MS-XWDSTRUCTDOC\]](#)

Alternate names: DAV:resourcetype

2.445 PidNameDavSearchRequest

Canonical name: PidNameDavSearchRequest

Description: Indicates the search that the search folder performs.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:searchrequest

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDSEARCH\]](#) section 2.2.3.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: DAV:searchrequest

2.446 PidNameDavSearchType

Canonical name: PidNameDavSearchType

Description: Indicates the type of search that the search folder performs.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:searchtype

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDSEARCH\]](#) section 2.2.3.2

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: DAV:searchtype

2.447 PidNameDavUid

Canonical name: PidNameDavUid

Description: Specifies the unique identifier for an item.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DAV:uid

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.6

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: DAV:uid

2.448 PidNameDisposition

Canonical name: PidNameDisposition

Description: Specifies the Mail Delivery Notification (MDN) status for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Disposition

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.14

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:disposition

2.449 PidNameDispositionNotificationTo

Canonical name: PidNameDispositionNotificationTo

Description: Specifies the destination to which disposition notifications should be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Disposition-Notification-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.15

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:disposition-notification-to

2.450 PidNameDistribution

Canonical name: PidNameDistribution

Description: Contains a comma-separated list, similar to the Newsgroups header field, which is intended to restrict the distribution of a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Distribution

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.16

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:distribution

2.451 PidNameDocumentParts

Canonical name: PidNameDocumentParts

Description: Specifies the title of each part of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DocParts

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.29

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#PartTitles

2.452 PidNameEditTime

Canonical name: PidNameEditTime

Description: Specifies the time that the file was last edited.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: EditTime

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.10

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#TotalTime

2.453 PidNameExchangeIntendedBusyStatus

Canonical name: PidNameExchangeIntendedBusyStatus

Description: Specifies the busy status of the user during an appointment or meeting.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/intendedbusystatus

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.1

Alternate names: http://schemas.microsoft.com/exchange/intendedbusystatus

2.454 PidNameExchangeJunkEmailMoveStamp

Canonical name: PidNameExchangeJunkEmailMoveStamp

Description: Indicates that the message is not to be processed by a **spam filter**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/junkemailmovestamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.1.2

Consuming reference: [\[MS-OXORSS\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/junkemailmovestamp>

2.455 PidNameExchangeModifyExceptionStructure

Canonical name: PidNameExchangeModifyExceptionStructure

Description: Specifies a structure that modifies an exception to the recurrence.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: <http://schemas.microsoft.com/exchange/modifyexceptionstruct>

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.2

Alternate names: <http://schemas.microsoft.com/exchange/modifyexceptionstruct>

2.456 PidNameExchangeNoModifyExceptions

Canonical name: PidNameExchangeNoModifyExceptions

Description: Indicates whether exceptions to a recurring appointment can be modified.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: <http://schemas.microsoft.com/exchange/nomodifyexceptions>

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.3

Alternate names: <http://schemas.microsoft.com/exchange/nomodifyexceptions>

2.457 PidNameExchangePatternEnd

Canonical name: PidNameExchangePatternEnd

Description: Identifies the maximum time when an instance of a recurring appointment ends.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: <http://schemas.microsoft.com/exchange/patternend>

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.4

Alternate names: <http://schemas.microsoft.com/exchange/patternend>

2.458 PidNameExchangePatternStart

Canonical name: PidNameExchangePatternStart

Description: Identifies the absolute minimum time when an instance of a recurring appointment starts.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/patternstart

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.5

Alternate names: http://schemas.microsoft.com/exchange/patternstart

2.459 PidNameExchangePublicFolderEmailAddress

Canonical name: PidNameExchangePublicFolderEmailAddress

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/publicfolderemailaddress

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.7

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: http://schemas.microsoft.com/exchange/publicfolderemailaddress

2.460 PidNameExchangeReminderInterval

Canonical name: PidNameExchangeReminderInterval

Description: Identifies the time, in seconds, between reminders.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/exchange/reminderinterval

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.6

Consuming reference: [MS-XWDCAL]

Alternate names: http://schemas.microsoft.com/exchange/reminderinterval

2.461 PidNameExchDatabaseSchema

Canonical name: PidNameExchDatabaseSchema

Description: Specifies an array of URLs that identifies other folders within the same store that contain schema definition items.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:baseschema

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.5.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:baseschema

2.462 PidNameExchDataExpectedContentClass

Canonical name: PidNameExchDataExpectedContentClass

Description: Specifies an array of names that indicates the expected content **classes** of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:expected-content-class

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.5.2

Consuming references: [\[MS-XWDEXT\]](#), [\[MS-XWDSEARCH\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:expected-content-class

2.463 PidNameExchDataSchemaCollectionReference

Canonical name: PidNameExchDataSchemaCollectionReference

Description: Specifies an array of names that indicates the expected content classes of items within a folder.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas-microsoft-com:exch-data:schema-collection-ref

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.5.3

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas-microsoft-com:exch-data:schema-collection-ref

2.464 PidNameExpires

Canonical name: PidNameExpires

Description: This property specifies the date on which the message expires.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Expires

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.17

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:expires

2.465 PidNameExpiryDate

Canonical name: PidNameExpiryDate

Description: This property specifies the expiry date of a message in an e-mail header.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Expiry-Date

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.18

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:expiry-date

2.466 PidNameExtractedAddresses

Canonical name: PidNameExtractedAddresses

Description: Contains an **XML document** with a single **AddressSet** element.

Property set: PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

Property name: XmlExtractedAddresses

Data type: PtypString, 0x001F

Area: Extracted Entities

Defining reference: [\[MS-OXCEXT\]](#) section 2.2.1.1

Alternate names: dispidXmlExtractedAddresses

2.467 PidNameExtractedContacts

Canonical name: PidNameExtractedContacts

Description: Contains an XML document with a single **ContactSet** element.

Property set: PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

Property name: XmlExtractedContacts

Data type: **PtypString**, 0x001F

Area: Extracted Entities

Defining reference: [\[MS-OXCEXT\]](#) section 2.2.1.2

Alternate names: dispidXmlExtractedContacts

2.468 PidNameExtractedEmails

Canonical name: PidNameExtractedEmails

Description: Contains an XML document with a single **EmailSet** element.

Property set: PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

Property name: XmlExtractedEmails

Data type: **PtypString**, 0x001F

Area: Extracted Entities

Defining reference: [\[MS-OXCEXT\]](#) section 2.2.1.3

Alternate names: dispidXmlExtractedEmails

2.469 PidNameExtractedMeetings

Canonical name: PidNameExtractedMeetings

Description: Contains an XML document with a single **MeetingSet** element.

Property set: PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

Property name: XmlExtractedMeetings

Data type: **PtypString**, 0x001F

Area: Extracted Entities

Defining reference: [\[MS-OXCEXT\]](#) section 2.2.1.4

Alternate names: dispidXmlExtractedMeetings

2.470 PidNameExtractedPhones

Canonical name: PidNameExtractedPhones

Description: Contains an XML document with a single **PhoneSet** element.

Property set: PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

Property name: XmlExtractedPhones

Data type: **PtypString**, 0x001F

Area: Extracted Entities

Defining reference: [\[MS-OXCEXT\]](#) section 2.2.1.5

Alternate names: dispidXmlExtractedPhones

2.471 PidNameExtractedTasks

Canonical name: PidNameExtractedTasks

Description: Contains an XML document with a single **TaskSet** element.

Property set: PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

Property name: XmlExtractedTasks

Data type: **PtypString**, 0x001F

Area: Extracted Entities

Defining reference: [\[MS-OXCEXT\]](#) section 2.2.1.6

Alternate names: dispidXmlExtractedTasks

2.472 PidNameExtractedUrls

Canonical name: PidNameExtractedUrls

Description: Contains an XML document with a single **UrlSet** element.

Property set: PSETID_XmlExtractedEntities {23239608 - 685D - 4732 - 9C55 - 4C95CB4E8E33}

Property name: XmlExtractedUrls

Data type: **PtypString**, 0x001F

Area: Extracted Entities

Defining reference: [\[MS-OXCEXT\]](#) section 2.2.1.7

Alternate names: dispidXmlExtractedUrls

2.473 PidNameFollowupTo

Canonical name: PidNameFollowupTo

Description: This property specifies the newsgroups to which follow-up messages are to be posted.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Followup-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.19

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:followup-to

2.474 PidNameFrom

Canonical name: PidNameFrom

Description: Specifies the SMTP e-mail **alias** of the organizer of an appointment or meeting.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: From

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.35

Consuming reference: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:calendar:organizer

2.475 PidNameHeadingPairs

Canonical name: PidNameHeadingPairs

Description: Specifies which group of headings are indented in the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: HeadingPairs

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.30

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#HeadingPairs

2.476 PidNameHiddenCount

Canonical name: PidNameHiddenCount

Description: Specifies the hidden value of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: HiddenCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.27

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#HiddenSlides

2.477 PidNameHttpmailCalendar

Canonical name: PidNameHttpmailCalendar

Description: Specifies the URL for the Calendar folder for a particular user.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:calendar

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.3.1

Alternate names: urn:schemas:httpmail:calendar

2.478 PidNameHttpmailCc

Canonical name: PidNameHttpmailCc

Description: Specifies the **carbon copy (Cc) recipients** of the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:cc

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.2

Alternate names: urn:schemas:httpmail:cc

2.479 PidNameHttpmailContacts

Canonical name: PidNameHttpmailContacts

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:contacts

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCNTC\]](#) section 2.2.1.4.1

Alternate names: urn:schemas:httpmail:contacts

2.480 PidNameHttpmailContentMediaType

Canonical name: PidNameHttpmailContentMediaType

Description: Specifies the content media type for the body part.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:content-media-type

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.3

Alternate names: urn:schemas:httpmail:content-media-type

2.481 PidNameHttpmailFrom

Canonical name: PidNameHttpmailFrom

Description: Specifies the person from whom the message was sent.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:from

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.8

Alternate names: urn:schemas:httpmail:from

2.482 PidNameHttpmailFromEmail

Canonical name: PidNameHttpmailFromEmail

Description: Specifies the e-mail address from which the message was sent.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:fromemail

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.9

Alternate names: urn:schemas:httpmail:fromemail

2.483 PidNameHttpmailHtmlDescription

Canonical name: PidNameHttpmailHtmlDescription

Description: Specifies the HTML content of the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:htmldescription

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.3.2

Consuming references: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:htmldescription

2.484 PidNameHttpmailOutbox

Canonical name: PidNameHttpmailOutbox

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:outbox

Data type: PtypString, 0x001F

Area: Common

Defining reference:

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:httpmail:outbox

2.485 PidNameHttpmailSendMessage

Canonical name: PidNameHttpmailSendMessage

Description: Specifies the e-mail submission URI to which outgoing e-mail is submitted.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:sendmsg

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.3.3

Consuming reference: [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:httpmail:sendmsg

2.486 PidNameHttpmailSubmitted

Canonical name: PidNameHttpmailSubmitted

Description: Specifies whether a message has been submitted to the **Outbox folder**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:submitted

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.20

Alternate names: urn:schemas:httpmail:submitted

2.487 PidNameHttpmailTo

Canonical name: PidNameHttpmailTo

Description: Specifies the principle (To) message addressees.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:httpmail:to

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.23

Alternate names: urn:schemas:httpmail:to

2.488 PidNameICalendarRecurrenceDate

Canonical name: PidNameICalendarRecurrenceDate

Description: Identifies an array of instances of a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rdate

Data type: PtypMultipleTime, 0x1040

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.36

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:rdate

2.489 PidNameICalendarRecurrenceRule

Canonical name: PidNameICalendarRecurrenceRule

Description: Specifies the rule for the pattern that defines a recurring appointment.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:rrule

Data type: PtypMultipleString, 0x101F

Area: Common

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.37

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:rrule

2.490 PidNameImportance

Canonical name: PidNameImportance

Description: Indicates the level of importance for a message as either low, normal, or high.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Importance

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.13

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:importance

2.491 PidNameInReplyTo

Canonical name: PidNameInReplyTo

Description: Specifies the message to which another message is a reply.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: In-Reply-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.22

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:in-reply-to

2.492 PidNameInternetComment

Canonical name: PidNameInternetComment

Description: Contains a comment about the purpose or content of the folder.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Comment

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.4

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:comment

2.493 PidNameInternetKeywords

Canonical name: PidNameInternetKeywords

Description: Specifies the key words for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Keywords

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.23

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:keywords

2.494 PidNameInternetSubject

Canonical name: PidNameInternetSubject

Description: Specifies the subject of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.4.1

Consuming reference: [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: urn:schemas:mailheader:subject

2.495 PidNameKeywords

Canonical name: PidNameKeywords

Description: Contains keywords or categories for the Message object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Keywords

Data type: PtypMultipleString, 0x101F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.17

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXONOTE\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Keywords, <http://schemas.microsoft.com/exchange/keywords-utf8>

2.496 PidNameLastAuthor

Canonical name: PidNameLastAuthor

Description: Specifies the most recent author of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastAuthor

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.7

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastAuthor

2.497 PidNameLastPrinted

Canonical name: PidNameLastPrinted

Description: Specifies the time, in UTC, that the file was last printed.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastPrinted

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.11

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastPrinted

2.498 PidNameLastSaveDateTime

Canonical name: PidNameLastSaveDateTime

Description: Specifies the time, in UTC, that the file was last saved.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LastSaveDtm

Data type: PtypTime, 0x0040

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.13

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LastSaved

2.499 PidNameLineCount

Canonical name: PidNameLineCount

Description: Specifies the number of lines in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LineCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.23

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Lines

2.500 PidNameLines

Canonical name: PidNameLines

Description: Specifies the number of lines in the body of a newsgroup message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Lines

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.24

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:lines

2.501 PidNameLinksDirty

Canonical name: PidNameLinksDirty

Description: Indicates whether the links in the document are up-to-date.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: LinksDirty

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.31

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#LinksUpToDate

2.502 PidNameLocationUrl

Canonical name: PidNameLocationUrl

Description:

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: urn:schemas:calendar:locationurl

Data type: PtypString, 0x001F

Area: Calendar

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: urn:schemas:calendar:locationurl, LocationUrl

2.503 PidNameMailSubmissionUri

Canonical name: PidNameMailSubmissionUri

Description: Specifies the URI that is used for e-mail submissions.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: MAIL:submissionuri

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.4.1

2.504 PidNameManager

Canonical name: PidNameManager

Description: Specifies the manager of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Manager

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.20

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Manager

2.505 PidNameMessageId

Canonical name: PidNameMessageId

Description: Specifies a unique identifier for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Message-ID

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.25

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:message-id

2.506 PidNameMimeVersion

Canonical name: PidNameMimeVersion

Description: Specifies the version of Multipurpose Internet Mail Extensions (MIME) that is used to format the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Mime-Version

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.26

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:mime-version

2.507 PidNameMultimediaClipCount

Canonical name: PidNameMultimediaClipCount

Description: Specifies the number of multimedia clips in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: MMClipCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.28

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#MultimediaClips

2.508 PidNameNewsgroups

Canonical name: PidNameNewsgroups

Description: Specifies the newsgroup addressees for the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Newsgroups

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.27

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:newsgroups

2.509 PidNameNntpPostingHost

Canonical name: PidNameNntpPostingHost

Description: Specifies the initial host to which the USENET feed was posted.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: NNTP-Posting-Host

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.28

Alternate names: urn:schemas:mailheader:nntp-posting-host

2.510 PidNameNoteCount

Canonical name: PidNameNoteCount

Description: Specifies the number of notes in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: NoteCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.26

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Notes

2.511 PidNameOMSAccountGuid

Canonical name: PidNameOMSAccountGuid

Description: Contains the GUID of the **SMS** account used to deliver the message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSAccountGuid

Data type: PtypString, 0x001F

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.1

2.512 PidNameOMSMobileModel

Canonical name: PidNameOMSMobileModel

Description: Indicates the model of the mobile device used to send the SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSMobileModel

Data type: PtypString, 0x001F

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.6

2.513 PidNameOMSScheduleTime

Canonical name: PidNameOMSScheduleTime

Description: Contains the time, in UTC, at which the client requested that the service provider send the SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSScheduleTime

Data type: PtypTime, 0x0040

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.2

2.514 PidNameOMSServiceType

Canonical name: PidNameOMSServiceType

Description: Contains the type of service used to send an SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSServiceType

Data type: PtypInteger32, 0x0003

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.3

2.515 PidNameOMSSourceType

Canonical name: PidNameOMSSourceType

Description: Contains the source of an SMS or MMS message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: OMSSourceType

Data type: PtypInteger32, 0x0003

Area: SMS

Defining reference: [\[MS-OXOSMMS\]](#) section 2.2.1.4

2.516 PidNameOrganization

Canonical name: PidNameOrganization

Description: Specifies the organization to which the sender belongs.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Organization

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.29

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:organization

2.517 PidNameOriginalRecipient

Canonical name: PidNameOriginalRecipient

Description: Specifies the e-mail address of an original recipient (1) of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Original-Recipient

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.30

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:original-recipient

2.518 PidNamePageCount

Canonical name: PidNamePageCount

Description: Specifies the page count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PageCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.14

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Pages

2.519 PidNameParagraphCount

Canonical name: PidNameParagraphCount

Description: Specifies the number of paragraphs in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: ParCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.24

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Paragraphs

2.520 PidNamePath

Canonical name: PidNamePath

Description: Specifies the list of **Network News Transfer Protocol (NNTP)** hosts through which this message was relayed before arriving at the current host.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Path

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.31

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:path

2.521 PidNamePhishingStamp

Canonical name: PidNamePhishingStamp

Description: Indicates whether a message is likely to be **phishing**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: http://schemas.microsoft.com/outlook/phishingstamp

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXPHISH\]](#) section 2.2.1.1

2.522 PidNamePostingVersion

Canonical name: PidNamePostingVersion

Description: Identifies the software that is used to post the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Posting-Version

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.32

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:posting-version

2.523 PidNamePresentationFormat

Canonical name: PidNamePresentationFormat

Description: Specifies the presentation format of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: PresFormat

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.19

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#PresentationFormat

2.524 PidNamePriority

Canonical name: PidNamePriority

Description: Specifies the priority of a message or appointment.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Priority

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.33

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:priority

2.525 PidNameQuarantineOriginalSender

Canonical name: PidNameQuarantineOriginalSender

Description: Specifies the original sender of a message.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: quarantine-original-sender

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXCMAIL\]](#) section 2.5.3

2.526 PidNameReceived

Canonical name: PidNameReceived

Description: Specifies the SMTP host received headers for a message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Received

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.34

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:received

2.527 PidNameReferences

Canonical name: PidNameReferences

Description: Specifies the USENET header used to correlate replies with their original messages.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: References

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.35

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:references

2.528 PidNameRelayVersion

Canonical name: PidNameRelayVersion

Description: Specifies the version of the program responsible for transmitting an item over the immediate link.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Relay-Version

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.36

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:relay-version

2.529 PidNameReplyBy

Canonical name: PidNameReplyBy

Description: Indicates when a reply to a message is expected.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Reply-By

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.37

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:reply-by

2.530 PidNameReplyTo

Canonical name: PidNameReplyTo

Description: Specifies the address to which replies are to be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Reply-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.38

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:reply-to

2.531 PidNameReturnPath

Canonical name: PidNameReturnPath

Description: Specifies the address of the message originator.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Return-Path

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.39

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:return-path

2.532 PidNameReturnReceiptTo

Canonical name: PidNameReturnReceiptTo

Description: Specifies the address to which return receipts are to be sent.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Return-Receipt-To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.40

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:return-receipt-to

2.533 PidNameRevisionNumber

Canonical name: PidNameRevisionNumber

Description: Specifies the revision number of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: RevNumber

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.8

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Revision

2.534 PidNameRightsManagementLicense

Canonical name: PidNameRightsManagementLicense

Description: Specifies the value used to cache the **Use License** for the **rights-managed e-mail message**.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: DRMLicense

Data type: PtypMultipleBinary, 0x1102

Area: Secure Messaging Properties

Defining reference: [\[MS-OXORMMS\]](#) section 2.2.1.1

2.535 PidNameScale

Canonical name: PidNameScale

Description: Indicates whether the image is to be scaled or cropped.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Scale

Data type: PtypBoolean, 0x000B

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.32

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#ScaleCrop

2.536 PidNameSecurity

Canonical name: PidNameSecurity

Description: Specifies the security level of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Security

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.17

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Security

2.537 PidNameSender

Canonical name: PidNameSender

Description: Specifies the sender of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Sender

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.41

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:sender

2.538 PidNameSensitivity

Canonical name: PidNameSensitivity

Description: Specifies the sensitivity of the message or appointment.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Sensitivity

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.42

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:sensitivity

2.539 PidNameSlideCount

Canonical name: PidNameSlideCount

Description: Specifies the number of slides in the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: SlideCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.25

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Slides

2.540 PidNameSubject

Canonical name: PidNameSubject

Description: Specifies the subject of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Subject

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.2

Consuming reference: [\[MS-XWDDOC\]](#), [\[MS-OXOCAL\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Subject

2.541 PidNameSummary

Canonical name: PidNameSummary

Description: Contains a summary of the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Summary

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.44

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:summary

2.542 PidNameTemplate

Canonical name: PidNameTemplate

Description: Specifies the template of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Template

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.6

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Template

2.543 PidNameThreadIndex

Canonical name: PidNameThreadIndex

Description: Identifies a particular conversation thread.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Thread-Index

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.45

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:thread-index

2.544 PidNameThreadTopic

Canonical name: PidNameThreadTopic

Description: Specifies the topic of a discussion thread.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: Thread-Topic

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.46

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:thread-topic

2.545 PidNameThumbnail

Canonical name: PidNameThumbnail

Description: Specifies the data representing the thumbnail image of the document.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Thumbnail

Data type: PtypBinary, 0x0102

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.33

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#ThumbNail

2.546 PidNameTitle

Canonical name: PidNameTitle

Description: Specifies the title of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: Title

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.1

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Title

2.547 PidNameTo

Canonical name: PidNameTo

Description: Specifies the principal message addressees.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: To

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.47

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:to

2.548 PidNameWordCount

Canonical name: PidNameWordCount

Description: Specifies the word count of the file attached to the Document object.

Property set: PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}

Property name: WordCount

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXODOC\]](#) section 2.2.1.15

Consuming reference: [\[MS-XWDDOC\]](#)

Alternate names: urn:schemas-microsoft-com:office:office#Words

2.549 PidNameXCallId

Canonical name: PidNameXCallId

Description: Contains a unique identifier associated with the phone call.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallID

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.12

Consuming reference: [\[MS-OXCMAIL\]](#)

2.550 PidNameXFaxNumberOfPages

Canonical name: PidNameXFaxNumberOfPages

Description: Specifies how many discrete pages are contained within an attachment representing a facsimile message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-FaxNumberOfPages

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.8

Consuming reference: [\[MS-OXCMAIL\]](#)

2.551 PidNameXMailer

Canonical name: PidNameXMailer

Description: Specifies the name of the software used to send the message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Mailer

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.48

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-mailer

2.552 PidNameXMessageCompleted

Canonical name: PidNameXMessageCompleted

Description: Contains the header for message flag completion.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Message-Completed

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.49

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-message-completed

2.553 PidNameXMessageFlag

Canonical name: PidNameXMessageFlag

Description: Specifies message flags that indicate special characteristics of a particular message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Message-Flag

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.7.50

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-message-flag

2.554 PidNameXRequireProtectedPlayOnPhone

Canonical name: PidNameXRequireProtectedPlayOnPhone

Description: Indicates that the client only renders the message on a phone.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-RequireProtectedPlayOnPhone

Data type: PtypBoolean, 0x000B

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.14

2.555 PidNameXSenderTelephoneNumber

Canonical name: PidNameXSenderTelephoneNumber

Description: Contains the telephone number of the caller associated with a voice mail message.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-CallingTelephoneNumber

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.2

Consuming reference: [\[MS-OXCMAIL\]](#)

2.556 PidNameXSharingBrowseUrl

Canonical name: PidNameXSharingBrowseUrl

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Browse-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

2.557 PidNameXSharingCapabilities

Canonical name: PidNameXSharingCapabilities

Description: Contains a string representation of the value of the **PidLidSharingCapabilities** property (section [2.238](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Capabilities

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.2

2.558 PidNameXSharingConfigUrl

Canonical name: PidNameXSharingConfigUrl

Description: Contains the same value as the **PidLidSharingConfigurationUrl** property (section [2.239](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Config-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.4

2.559 PidNameXSharingExendedCaps

Canonical name: PidNameXSharingExendedCaps

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Exended-Caps

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

2.560 PidNameXSharingFlavor

Canonical name: PidNameXSharingFlavor

Description: Contains a hexadecimal string representation of the value of the **PidLidSharingFlavor** property (section [2.246](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Flavor

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.6

2.561 PidNameXSharingInstanceGuid

Canonical name: PidNameXSharingInstanceGuid

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Instance-Guid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

2.562 PidNameXSharingLocalType

Canonical name: PidNameXSharingLocalType

Description: Contains the same value as the **PidLidSharingLocalType** property (section [2.260](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Local-Type

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.11

2.563 PidNameXSharingProviderGuid

Canonical name: PidNameXSharingProviderGuid

Description: Contains the hexadecimal string representation of the value of the **PidLidSharingProviderGuid** property (section [2.267](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Guid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.13

2.564 PidNameXSharingProviderName

Canonical name: PidNameXSharingProviderName

Description: Contains the same value as the **PidLidSharingProviderName** property (section [2.268](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Name

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.15

2.565 PidNameXSharingProviderUrl

Canonical name: PidNameXSharingProviderUrl

Description: Contains the same value as the **PidLidSharingProviderUrl** property (section [2.269](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Provider-Url

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.2.17

2.566 PidNameXSharingRemoteName

Canonical name: PidNameXSharingRemoteName

Description: Contains the same value as the **PidLidSharingRemoteName** property (section [2.278](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Name

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.2

2.567 PidNameXSharingRemotePath

Canonical name: PidNameXSharingRemotePath

Description: Contains a value that is ignored by the server no matter what value is generated by the client.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Path

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.6

2.568 PidNameXSharingRemoteStoreUid

Canonical name: PidNameXSharingRemoteStoreUid

Description: Contains the same value as the **PidLidSharingRemoteStoreUid** property (section [2.283](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Store-Uid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.4

2.569 PidNameXSharingRemoteType

Canonical name: PidNameXSharingRemoteType

Description: Contains the same value as the **PidLidSharingRemoteType** property (section [2.282](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Type

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.6

2.570 PidNameXSharingRemoteUid

Canonical name: PidNameXSharingRemoteUid

Description: Contains the same value as the **PidLidSharingRemoteUid** property (section [2.283](#)).

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Sharing-Remote-Uid

Data type: PtypString, 0x001F

Area: Sharing

Defining reference: [\[MS-OXSHARE\]](#) section 2.2.3.8

2.571 PidNameXUnifiedMessagingPartnerAssignedId

Canonical name: PidNameXUnifiedMessagingPartnerAssignedId

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerAssignedID

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerAssignedID

2.572 PidNameXUnifiedMessagingPartnerContent

Canonical name: PidNameXUnifiedMessagingPartnerContent

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerContent

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerContent

2.573 PidNameXUnifiedMessagingPartnerContext

Canonical name: PidNameXUnifiedMessagingPartnerContext

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerContext

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerContext

2.574 PidNameXUnifiedMessagingPartnerStatus

Canonical name: PidNameXUnifiedMessagingPartnerStatus

Description:

Property set: PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

Property name: X-MS-Exchange-UM-PartnerStatus

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: XMsExchangeUMPartnerStatus

2.575 PidNameXUnsent

Canonical name: PidNameXUnsent

Description:

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-Unsent

Data type: PtypString, 0x001F

Area: E-mail

Defining reference:

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:mailheader:x-unsent

2.576 PidNameXVoiceMessageAttachmentOrder

Canonical name: PidNameXVoiceMessageAttachmentOrder

Description: Contains the list of names for the audio file attachments that are to be played as part of a message, in reverse order.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-AttachmentOrder

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.10

Consuming reference: [\[MS-OXCMAIL\]](#)

2.577 PidNameXVoiceMessageDuration

Canonical name: PidNameXVoiceMessageDuration

Description: Specifies the length of the attached audio message, in seconds.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageDuration

Data type: PtypInteger16, 0x0002

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.4

Consuming reference: [\[MS-OXCMAIL\]](#)

2.578 PidNameXVoiceMessageSenderName

Canonical name: PidNameXVoiceMessageSenderName

Description: Contains the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

Property set: PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}

Property name: X-VoiceMessageSenderName

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.6

Consuming reference: [\[MS-OXCMAIL\]](#)

2.579 PidTagAccess

Canonical name: PidTagAccess

Description: Indicates the operations available to the client for the object.

Property ID: 0x0FF4

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOJRN\]](#)

Alternate names: PR_ACCESS, ptagAccess

2.580 PidTagAccessControlListData

Canonical name: PidTagAccessControlListData

Description: Contains a **permissions** list for a folder.

Property ID: 0x3FE0

Data type: PtypBinary, 0x0102

Area: Access Control Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.3

Consuming references: [\[MS-OXCFOLD\]](#)

Alternate names: PR_ACL_DATA, ptagACLData

2.581 PidTagAccessLevel

Canonical name: PidTagAccessLevel

Description: Indicates the client's access level to the object.

Property ID: 0x0FF7

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_ACCESS_LEVEL, ptagAccessLevel

2.582 PidTagAccount

Canonical name: PidTagAccount

Description: Contains the alias of an Address Book object, which is an alternative name by which the object can be identified.

Property ID: 0x3A00

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOMSG\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_ACCOUNT, PR_ACCOUNT_A, PR_ACCOUNT_W, urn:schemas:contacts:account

2.583 PidTagAdditionalRenEntryIds

Canonical name: PidTagAdditionalRenEntryIds

Description: Contains the indexed entry IDs for several special folders related to conflicts, sync issues, local failures, server failures, junk e-mail and **spam**.

Property ID: 0x36D8

Data type: **PtypMultipleBinary**, 0x1102

Area: Outlook Application

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.4

Consuming references: [\[MS-OXCSPAM\]](#), [\[MS-OXPHISH\]](#)

Alternate names: PR_ADDITIONAL_REN_ENTRYIDS, ptagAdditionalRenEntryIds

2.584 PidTagAdditionalRenEntryIdsEx

Canonical name: PidTagAdditionalRenEntryIdsEx

Description: Contains an array of blocks that contain the EntryIDs for folders related to RSS feed folders, and the Tracked Mail Processing folder, To-Do Search folder, and Conversation Action Settings folder.

Property ID: 0x36D9

Data type: **PtypBinary**, 0x0102

Area: Outlook Application

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.5

Alternate names: PR_ADDITIONAL_REN_ENTRYIDS_EX, ptagAdditionalRenEntryIdsEx

2.585 PidTagAddressBookAuthorizedSenders

Canonical name: PidTagAddressBookAuthorizedSenders

Description: Indicates whether delivery restrictions exist for a recipient (1).

Property ID: 0x8CD8

Data type: **PtypObject**, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.84

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_AUTH_ORIG

2.586 PidTagAddressBookContainerId

Canonical name: PidTagAddressBookContainerId

Description: Contains the ID of a container on an NSPI server.

Property ID: 0xFFFFD

Data type: **PtypInteger32**, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.3

Consuming references: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_CONTAINERID

2.587 PidTagAddressBookDeliveryContentLength

Canonical name: PidTagAddressBookDeliveryContentLength

Description: Specifies the maximum size, in bytes, of a message that a recipient (1) can receive.

Property ID: 0x806A

Data type: **PtypInteger32**, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.27

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DELIV_CONT_LENGTH

2.588 PidTagAddressBookDisplayNamePrintable

Canonical name: PidTagAddressBookDisplayNamePrintable

Description: Contains the printable string version of the display name.

Property ID: 0x39FF

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.7

Consuming reference: [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_EMS_AB_DISPLAY_NAME_PRINTABLE,
PR_EMS_AB_DISPLAY_NAME_PRINTABLE_A, PR_EMS_AB_DISPLAY_NAME_PRINTABLE_W,
PR_7BIT_DISPLAY_NAME, PR_7BIT_DISPLAY_NAME_A, PR_7BIT_DISPLAY_NAME_W,
ptagSimpleDisplayName

2.589 PidTagAddressBookDisplayTypeExtended

Canonical name: PidTagAddressBookDisplayTypeExtended

Description: Contains a value that indicates how to display an Address Book object in a table or as a recipient (1) on a message.

Property ID: 0x8C93

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.35

Alternate names: PR_EMS_AB_DISPLAY_TYPE_EX

2.590 PidTagAddressBookDistributionListExternalMemberCount

Canonical name: PidTagAddressBookDistributionListExternalMemberCount

Description: Contains the number of external recipients (1) in the distribution list.

Property ID: 0x8CE3

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.30

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_EXTERNAL_MEMBER_COUNT

2.591 PidTagAddressBookDistributionListMemberCount

Canonical name: PidTagAddressBookDistributionListMemberCount

Description: Contains the total number of recipients (1) in the distribution list.

Property ID: 0x8CE2

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.29

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_TOTAL_MEMBER_COUNT

2.592 PidTagAddressBookDistributionListMemberSubmitAccepted

Canonical name: PidTagAddressBookDistributionListMemberSubmitAccepted

Description: Indicates that delivery restrictions exist for a recipient (1).

Property ID: 0x8073

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.86

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_MEM_SUBMIT_PERMS_BL_O

2.593 PidTagAddressBookDistributionListMemberSubmitRejected

Canonical name: PidTagAddressBookDistributionListMemberSubmitRejected

Description: Indicates that delivery restrictions exist for a recipient (1).

Property ID: 0x8CDA

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.87

Consuming references: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_MEM_SUBMIT_PERMS

2.594 PidTagAddressBookDistributionListRejectMessagesFromDLMembers

Canonical name: PidTagAddressBookDistributionListRejectMessagesFromDLMembers

Description: Indicates that delivery restrictions exist for a recipient (1).

Property ID: 0x8CDB

Data type: PtypObject, 0x000D

Area: Address book

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.2

Alternate names: PR_EMS_AB_DL_MEM_REJECT_PERMS

2.595 PidTagAddressBookEntryId

Canonical name: PidTagAddressBookEntryId

Description: Contains the name-service EntryID of a directory object that refers to a **public folder**.

Property ID: 0x663B

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.4

Alternate names: PR_ADDRESS_BOOK_ENTRYID, ptagAddressBookEntryId

2.596 PidTagAddressBookExtensionAttribute1

Canonical name: PidTagAddressBookExtensionAttribute1

Description: Contains custom values defined and populated by the organization that modified the **display templates**.

Property ID: 0x802D

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_1, PR_EMS_AB_EXTENSION_ATTRIBUTE_1_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_1_W

2.597 PidTagAddressBookExtensionAttribute2

Canonical name: PidTagAddressBookExtensionAttribute2

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x802E

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_2, PR_EMS_AB_EXTENSION_ATTRIBUTE_2_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_2_W

2.598 PidTagAddressBookExtensionAttribute3

Canonical name: PidTagAddressBookExtensionAttribute3

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x802F

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_3,
PR_EMS_AB_EXTENSION_ATTRIBUTE_3_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_3_W

2.599 PidTagAddressBookExtensionAttribute4

Canonical name: PidTagAddressBookExtensionAttribute4

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8030

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_4,
PR_EMS_AB_EXTENSION_ATTRIBUTE_4_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_4_W

2.600 PidTagAddressBookExtensionAttribute5

Canonical name: PidTagAddressBookExtensionAttribute5

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8031

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_5,
PR_EMS_AB_EXTENSION_ATTRIBUTE_5_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_5_W

2.601 PidTagAddressBookExtensionAttribute6

Canonical name: PidTagAddressBookExtensionAttribute6

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8032

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_6,
PR_EMS_AB_EXTENSION_ATTRIBUTE_6_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_6_W

2.602 PidTagAddressBookExtensionAttribute7

Canonical name: PidTagAddressBookExtensionAttribute7

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8033

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_7,
PR_EMS_AB_EXTENSION_ATTRIBUTE_7_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_7_W

2.603 PidTagAddressBookExtensionAttribute8

Canonical name: PidTagAddressBookExtensionAttribute8

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8034

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_8,
PR_EMS_AB_EXTENSION_ATTRIBUTE_8_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_8_W

2.604 PidTagAddressBookExtensionAttribute9

Canonical name: PidTagAddressBookExtensionAttribute9

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8035

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_9,
PR_EMS_AB_EXTENSION_ATTRIBUTE_9_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_9_W

2.605 PidTagAddressBookExtensionAttribute10

Canonical name: PidTagAddressBookExtensionAttribute10

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8036

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_10,
PR_EMS_AB_EXTENSION_ATTRIBUTE_10_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_10_W

2.606 PidTagAddressBookExtensionAttribute11

Canonical name: PidTagAddressBookExtensionAttribute11

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8C57

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_11,
PR_EMS_AB_EXTENSION_ATTRIBUTE_11_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_11_W

2.607 PidTagAddressBookExtensionAttribute12

Canonical name: PidTagAddressBookExtensionAttribute12

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8C58

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_12,
PR_EMS_AB_EXTENSION_ATTRIBUTE_12_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_12_W

2.608 PidTagAddressBookExtensionAttribute13

Canonical name: PidTagAddressBookExtensionAttribute13

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8C59

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_13,
PR_EMS_AB_EXTENSION_ATTRIBUTE_13_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_13_W

2.609 PidTagAddressBookExtensionAttribute14

Canonical name: PidTagAddressBookExtensionAttribute14

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8C60

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_14,
PR_EMS_AB_EXTENSION_ATTRIBUTE_14_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_14_W

2.610 PidTagAddressBookExtensionAttribute15

Canonical name: PidTagAddressBookExtensionAttribute15

Description: Contains custom values defined and populated by the organization that modified the display templates.

Property ID: 0x8C61

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.34

Alternate names: PR_EMS_AB_EXTENSION_ATTRIBUTE_15,
PR_EMS_AB_EXTENSION_ATTRIBUTE_15_A, PR_EMS_AB_EXTENSION_ATTRIBUTE_15_W

2.611 PidTagAddressBookFolderPathname

Canonical name: PidTagAddressBookFolderPathname

Description: This property is deprecated and is to be ignored.

Property ID: 0x8004

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.4

Alternate names: PR_EMS_AB_FOLDER_PATHNAME, PR_EMS_AB_FOLDER_PATHNAME_A, PR_EMS_AB_FOLDER_PATHNAME_W

2.612 PidTagAddressBookHierarchicalChildDepartments

Canonical name: PidTagAddressBookHierarchicalChildDepartments

Description: Contains the child departments in a hierarchy of departments.

Property ID: 0x8C9A

Data type: **PtypEmbeddedTable**, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.8.1

Alternate names: PR_EMS_AB_HAB_CHILD_DEPARTMENTS

2.613 PidTagAddressBookHierarchicalDepartmentMembers

Canonical name: PidTagAddressBookHierarchicalDepartmentMembers

Description: Contains all of the mail users that belong to this department.

Property ID: 0x8C97

Data type: **PtypEmbeddedTable**, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.8.3

Alternate names: PR_EMS_AB_HAB_DEPARTMENT_MEMBERS

2.614 PidTagAddressBookHierarchicalIsHierarchicalGroup

Canonical name: PidTagAddressBookHierarchicalIsHierarchicalGroup

Description: Indicates whether the distribution list represents a **departmental group**.

Property ID: 0x8CDD

Data type: **PtypBoolean**, 0x000B

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.5

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_HAB_IS_HIERARCHICAL_GROUP,
PR_EMS_AB_IS_ORGANIZATIONAL

2.615 PidTagAddressBookHierarchicalParentDepartment

Canonical name: PidTagAddressBookHierarchicalParentDepartment

Description: Contains all of the departments to which this department is a child.

Property ID: 0x8C99

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.8.2

Alternate names: PR_EMS_AB_HAB_PARENT_DEPARTMENT

2.616 PidTagAddressBookHierarchicalRootDepartment

Canonical name: PidTagAddressBookHierarchicalRootDepartment

Description: Contains the **DN** of the root departmental group in the department hierarchy for the organization.

Property ID: 0x8C98

Data type: PtypString8, 0x001E

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.7.2

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_HAB_ROOT_DEPARTMENT

2.617 PidTagAddressBookHierarchicalShowInDepartments

Canonical name: PidTagAddressBookHierarchicalShowInDepartments

Description: Lists all Department objects of which the mail user is a member.

Property ID: 0x8C94

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.6

Alternate names: PR_EMS_AB_HAB_SHOW_IN_DEPARTMENTS

2.618 PidTagAddressBookHomeMessageDatabase

Canonical name: PidTagAddressBookHomeMessageDatabase

Description: Contains the DN expressed in the **X500 DN** format.

Property ID: 0x8006

Data type: PtypString8, 0x001E

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.67

Consuming references: [\[MS-OXABREF\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_HOME_MDB, PR_EMS_AB_HOME_MDB_A, PR_EMS_AB_HOME_MDB_W

2.619 PidTagAddressBookIsMaster

Canonical name: PidTagAddressBookIsMaster

Description: Contains a Boolean value of TRUE if it is possible to create Address Book objects in that container, and FALSE otherwise.

Property ID: 0xFFFFB

Data type: PtypBoolean, 0x000B

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.4

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_IS_MASTER

2.620 PidTagAddressBookIsMemberOfDistributionList

Canonical name: PidTagAddressBookIsMemberOfDistributionList

Description: List all the distribution lists for which this object is a member.

Property ID: 0x8008

Data type: PtypString8, 0x001E

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.3

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_IS_MEMBER_OF_DL, PR_EMS_AB_IS_MEMBER_OF_DL_A, PR_EMS_AB_IS_MEMBER_OF_DL_W

2.621 PidTagAddressBookManageDistributionList

Canonical name: PidTagAddressBookManageDistributionList

Description: Contains information for use in display templates for distribution lists.

Property ID: 0x6704

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.10.2

Consuming reference: [\[MS-OXOABKT\]](#)

Alternate names: PR_EMS_AB_MANAGE_DL

2.622 PidTagAddressBookManager

Canonical name: PidTagAddressBookManager

Description: Contains one row that references the mail user's manager.

Property ID: 0x8005

Data type: PtypObject, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.1

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_MANAGER, PR_EMS_AB_MANAGER_A, PR_EMS_AB_MANAGER_W

2.623 PidTagAddressBookManagerDistinguishedName

Canonical name: PidTagAddressBookManagerDistinguishedName

Description: Contains the **distinguished name (DN) (1)** of the mail user's manager.

Property ID: 0x8005

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.13

Alternate names: PR_EMS_AB_MANAGER_T

2.624 PidTagAddressBookMember

Canonical name: PidTagAddressBookMember

Description: Contains the members of the distribution list.

Property ID: 0x8009

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.1

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_MEMBER, PR_EMS_AB_MEMBER_A, PR_EMS_AB_MEMBER_W

2.625 PidTagAddressBookMessageId

Canonical name: PidTagAddressBookMessageId

Description: Contains the Short-term Message ID (MID) ([\[MS-OXCDATA\]](#) section 2.2.1.2) of the first message in the local site's **offline address book** public folder.

Property ID: 0x674F

Data type: PtypInteger64, 0x0014

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.2

Alternate names: ptagAddrbookMID

2.626 PidTagAddressBookModerationEnabled

Canonical name: PidTagAddressBookModerationEnabled

Description: Indicates whether moderation is enabled for the mail user of the distribution list.

Property ID: 0x8CB5

Data type: PtypBoolean, 0x000B

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.28

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_ENABLE_MODERATION

2.627 PidTagAddressBookNetworkAddress

Canonical name: PidTagAddressBookNetworkAddress

Description: Contains a list of names by which a server is known to the various transports in use by the network.

Property ID: 0x8170

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.68

Alternate names: PR_EMS_AB_NETWORK_ADDRESS, PR_EMS_AB_NETWORK_ADDRESS_A, PR_EMS_AB_NETWORK_ADDRESS_W

2.628 PidTagAddressBookObjectDistinguishedName

Canonical name: PidTagAddressBookObjectDistinguishedName

Description: Contains the distinguished name (DN) (1) of the Address Book object.

Property ID: 0x803C

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.15

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_OBJ_DIST_NAME, PR_EMS_AB_OBJ_DIST_NAME_A, PR_EMS_AB_OBJ_DIST_NAME_W

2.629 PidTagAddressBookObjectGuid

Canonical name: PidTagAddressBookObjectGuid

Description: Contains a GUID that identifies an Address Book object.

Property ID: 0x8C6D

Data type: **PtypBinary**, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.25

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_OBJECT_GUID

2.630 PidTagAddressBookOrganizationalUnitRootDistinguishedName

Canonical name: PidTagAddressBookOrganizationalUnitRootDistinguishedName

Description: Contains the distinguished name (DN) (1) of the Organization object of the mail user's organization.

Property ID: 0x8CA8

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.81

Alternate names: PR_EMS_AB_ORG_UNIT_ROOT_DN, msExchOURoot

2.631 PidTagAddressBookOwner

Canonical name: PidTagAddressBookOwner

Description: Contains one row that references the distribution list's owner.

Property ID: 0x800C

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.2

Alternate names: PR_EMS_AB_OWNER_O

2.632 PidTagAddressBookOwnerBackLink

Canonical name: PidTagAddressBookOwnerBackLink

Description: Contains a list of the distribution lists owned by a mail user.

Property ID: 0x8024

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.4

Alternate names: PR_EMS_AB_OWNER_BL_O

2.633 PidTagAddressBookParentEntryId

Canonical name: PidTagAddressBookParentEntryId

Description: Contains the EntryID of the parent container in a hierarchy of address book containers.

Property ID: 0xFFFC

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.5

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_EMS_AB_PARENT_ENTRYID

2.634 PidTagAddressBookPhoneticCompanyName

Canonical name: PidTagAddressBookPhoneticCompanyName

Description: Contains the phonetic representation of the **PidTagCompanyName** property (section [2.713](#)).

Property ID: 0x8C91

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.16

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_COMPANY_NAME,
PR_EMS_AB_PHONETIC_COMPANY_NAME_A, PR_EMS_AB_PHONETIC_COMPANY_NAME_W

2.635 PidTagAddressBookPhoneticDepartmentName

Canonical name: PidTagAddressBookPhoneticDepartmentName

Description: Contains the phonetic representation of the **PidTagDepartmentName** property (section [2.745](#)).

Property ID: 0x8C90

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.17

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_DEPARTMENT_NAME,
PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_A, PR_EMS_AB_PHONETIC_DEPARTMENT_NAME_W

2.636 PidTagAddressBookPhoneticDisplayName

Canonical name: PidTagAddressBookPhoneticDisplayName

Description: Contains the phonetic representation of the **PidTagDisplayName** property (section [2.749](#)).

Property ID: 0x8C92

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.9

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_DISPLAY_NAME,
PR_EMS_AB_PHONETIC_DISPLAY_NAME_A, PR_EMS_AB_PHONETIC_DISPLAY_NAME_W

2.637 PidTagAddressBookPhoneticGivenName

Canonical name: PidTagAddressBookPhoneticGivenName

Description: Contains the phonetic representation of the **PidTagGivenName** property (section [2.786](#)).

Property ID: 0x8C8E

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.14

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_GIVEN_NAME, PR_EMS_AB_PHONETIC_GIVEN_NAME_A, PR_EMS_AB_PHONETIC_GIVEN_NAME_W

2.638 PidTagAddressBookPhoneticSurname

Canonical name: PidTagAddressBookPhoneticSurname

Description: Contains the phonetic representation of the **PidTagSurname** property (section [2.1102](#)).

Property ID: 0x8C8F

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.15

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_PHONETIC_SURNAME, PR_EMS_AB_PHONETIC_SURNAME_A, PR_EMS_AB_PHONETIC_SURNAME_W

2.639 PidTagAddressBookProxyAddresses

Canonical name: PidTagAddressBookProxyAddresses

Description: Contains alternate e-mail addresses for the Address Book object.

Property ID: 0x800F

Data type: **PtypMultipleString**, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.23

Consuming references: [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_PROXY_ADDRESSES, PR_EMS_AB_PROXY_ADDRESSES_A, PR_EMS_AB_PROXY_ADDRESSES_W

2.640 PidTagAddressBookPublicDelegates

Canonical name: PidTagAddressBookPublicDelegates

Description: Contains a list of mail users who are allowed to send e-mail on behalf of the mailbox owner.

Property ID: 0x8015

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.5

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_EMS_AB_PUBLIC_DELEGATES, PR_EMS_AB_PUBLIC_DELEGATES_A, PR_EMS_AB_PUBLIC_DELEGATES_W

2.641 PidTagAddressBookReports

Canonical name: PidTagAddressBookReports

Description: Lists all the people who report to a mail user.

Property ID: 0x800E

Data type: PtypEmbeddedTable, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.5.2

Alternate names: PR_EMS_AB_REPORTS, PR_EMS_AB_REPORTS_A, PR_EMS_AB_REPORTS_W

2.642 PidTagAddressBookRoomCapacity

Canonical name: PidTagAddressBookRoomCapacity

Description: Contains the maximum occupancy of the room.

Property ID: 0x0807

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.9.1

Alternate names: PR_EMS_AB_ROOM_CAPACITY

2.643 PidTagAddressBookRoomContainers

Canonical name: PidTagAddressBookRoomContainers

Description: Contains a list of DNs that represent the address book containers that hold **Resource objects**, such as conference rooms and equipment.

Property ID: 0x8C96

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.7.1

Alternate names: PR_EMS_AB_ROOM_CONTAINERS, PR_EMS_AB_ROOM_CONTAINERS_A, PR_EMS_AB_ROOM_CONTAINERS_W

2.644 PidTagAddressBookRoomDescription

Canonical name: PidTagAddressBookRoomDescription

Description: Contains a description of the Resource object.

Property ID: 0x0809

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.9.2

Alternate names: PR_EMS_AB_ROOM_DESCRIPTION, PR_EMS_AB_ROOM_DESCRIPTION_A, PR_EMS_AB_ROOM_DESCRIPTION_W

2.645 PidTagAddressBookSenderHintTranslations

Canonical name: PidTagAddressBookSenderHintTranslations

Description: Contains the **locale** ID and translations of the default **mail tip**.

Property ID: 0x8CAC

Data type: PtypMultipleString, 0x101F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.26

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_DL_SENDER_HINT_TRANSLATIONS_W

2.646 PidTagAddressBookSeniorityIndex

Canonical name: PidTagAddressBookSeniorityIndex

Description: Contains a signed integer that specifies the seniority order of Address Book objects that represent members of a department and are referenced by a Department object or departmental group, with larger values specifying members that are more senior.

Property ID: 0x8CA0

Data type: PtypInteger32, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.24

Consuming reference: [\[MS-OXOAB\]](#) **Alternate names:** PR_EMS_AB_HAB_SENIORITY_INDEX, PR_EMS_AB_SENIORITY_INDEX

2.647 PidTagAddressBookTargetAddress

Canonical name: PidTagAddressBookTargetAddress

Description: Contains the foreign system e-mail address of an Address Book object.

Property ID: 0x8011

Data type: **PtypString**, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.22

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_TARGET_ADDRESS, PR_EMS_AB_TARGET_ADDRESS_A, PR_EMS_AB_TARGET_ADDRESS_W

2.648 PidTagAddressBookUnauthorizedSenders

Canonical name: PidTagAddressBookUnauthorizedSenders

Description: Indicates whether delivery restrictions exist for a recipient (1).

Property ID: 0x8CD9

Data type: **PtypObject**, 0x000D

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.85

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_UNAUTH_ORIG

2.649 PidTagAddressBookX509Certificate

Canonical name: PidTagAddressBookX509Certificate

Description: Contains the ASN_1 DER encoded X.509 certificates for the mail user.

Property ID: 0x8C6A

Data type: **PtypMultipleBinary**, 0x1102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.66

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_X509_CERT

2.650 PidTagAddressType

Canonical name: PidTagAddressType

Description: Contains the e-mail address type of a Message object.

Property ID: 0x3002

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.13

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

Alternate names: PR_ADDRTYPE, PR_ADDRTYPE_A, ptagAddrType, PR_ADDRTYPE_W

2.651 PidTagAlternateRecipientAllowed

Canonical name: PidTagAlternateRecipientAllowed

Description: Specifies whether the sender permits the message to be auto-forwarded.

Property ID: 0x0002

Data type: PtypBoolean, 0x000B

Area: Address Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.36

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ALTERNATE_RECIPIENT_ALLOWED, ptagAlternateRecipientAllowed

2.652 PidTagAnr

Canonical name: PidTagAnr

Description: Contains a filter value used in **ambiguous name resolution**.

Property ID: 0x360C

Data type: PtypString, 0x001F

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.10.1

Alternate names: PR_ANR, PR_ANR_A, PR_ANR_W

2.653 PidTagArchiveDate

Canonical name: PidTagArchiveDate

Property ID: 0x301F

Data type: PtypTime, 0x0040

Area: Archive

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.50.8

Alternate names: PR_ARCHIVE_DATE, ptagArchiveDate

2.654 PidTagArchivePeriod

Canonical name: PidTagArchivePeriod

Property ID: 0x301E

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.50.7

Alternate names: PR_ARCHIVE_PERIOD, ptagArchivePeriod

2.655 PidTagArchiveTag

Canonical name: PidTagArchiveTag

Property ID: 0x3018

Data type: PtypBinary, 0x0102

Area: Archive

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.50.1

Alternate names: PR_ARCHIVE_TAG, ptagArchiveTag

2.656 PidTagAssistant

Canonical name: PidTagAssistant

Description: Contains the name of the mail user's administrative assistant.

Property ID: 0x3A30

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.11

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ASSISTANT, PR_ASSISTANT_A, PR_ASSISTANT_W,
urn:schemas:contacts:secretarycn

2.657 PidTagAssistantTelephoneNumber

Canonical name: PidTagAssistantTelephoneNumber

Description: Contains the telephone number of the mail user's administrative assistant.

Property ID: 0x3A2E

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.57

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ASSISTANT_TELEPHONE_NUMBER,
PR_ASSISTANT_TELEPHONE_NUMBER_A, PR_ASSISTANT_TELEPHONE_NUMBER_W,
urn:schemas:contacts:secretaryphone

2.658 PidTagAssociated

Canonical name: PidTagAssociated

Description: Specifies whether the message being synchronized is an FAI message.

Property ID: 0x67AA

Data type: PtypBoolean, 0x000B

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.5

Alternate names: ptagAssociated

2.659 PidTagAttachAdditionalInformation

Canonical name: PidTagAttachAdditionalInformation

Description: Contains attachment encoding information.

Property ID: 0x370F

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.21

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_ADDITIONAL_INFO

2.660 PidTagAttachContentBase

Canonical name: PidTagAttachContentBase

Description: Contains the base of a relative URI.

Property ID: 0x3711

Data type: **PtypString**, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#) **Alternate names:** PR_ATTACH_CONTENT_BASE, PR_ATTACH_CONTENT_BASE_A, PR_ATTACH_CONTENT_BASE_W

2.661 PidTagAttachContentId

Canonical name: PidTagAttachContentId

Description: Contains a content identifier unique to the Message object that matches a corresponding "cid:" URI schema reference in the HTML body of the Message object.

Property ID: 0x3712

Data type: **PtypString**, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_ATTACH_CONTENT_ID, PR_ATTACH_CONTENT_ID_A, PR_ATTACH_CONTENT_ID_W

2.662 PidTagAttachContentLocation

Canonical name: PidTagAttachContentLocation

Description: Contains a relative or full URI that matches a corresponding reference in the HTML body of a Message object.

Property ID: 0x3713

Data type: **PtypString**, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#)

Alternate names: PR_ATTACH_CONTENT_LOCATION, PR_ATTACH_CONTENT_LOCATION_A, PR_ATTACH_CONTENT_LOCATION_W

2.663 PidTagAttachDataBinary

Canonical name: PidTagAttachDataBinary

Description: Contains the contents of the file to be attached.

Property ID: 0x3701

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_ATTACH_DATA_BIN, ptagAttachDataBin

2.664 PidTagAttachDataObject

Canonical name: PidTagAttachDataObject

Description: Contains the binary representation of the **Attachment object** in an application-specific format.

Property ID: 0x3701

Data type: PtypObject, 0x000D

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.8

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCAL\]](#)

Alternate names: PR_ATTACH_DATA_OBJ, ptagAttachDataObj

2.665 PidTagAttachEncoding

Canonical name: PidTagAttachEncoding

Description: Contains encoding information about the Attachment object.

Property ID: 0x3702

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.20

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_ENCODING

2.666 PidTagAttachExtension

Canonical name: PidTagAttachExtension

Description: Contains a file name extension that indicates the document type of an attachment.

Property ID: 0x3703

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.12

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_EXTENSION, PR_ATTACH_EXTENSION_A, PR_ATTACH_EXTENSION_W

2.667 PidTagAttachFilename

Canonical name: PidTagAttachFilename

Description: Contains the **8.3 name** of the **PidTagAttachLongFilename** property (section [2.669](#)).

Property ID: 0x3704

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OPFOAB\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_FILENAME, PR_ATTACH_FILENAME_A, ptagAttachFilename, PR_ATTACH_FILENAME_W

2.668 PidTagAttachFlags

Canonical name: PidTagAttachFlags

Description: Indicates which body formats might reference this attachment when rendering data.

Property ID: 0x3714

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.18

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_FLAGS

2.669 PidTagAttachLongFilename

Canonical name: PidTagAttachLongFilename

Description: Contains the full filename and extension of the Attachment object.

Property ID: 0x3707

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.10

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOUM\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_LONG_FILENAME, PR_ATTACH_LONG_FILENAME_A, PR_ATTACH_LONG_FILENAME_W, urn:schemas:httpmail:attachmentfilename

2.670 PidTagAttachLongPathname

Canonical name: PidTagAttachLongPathname

Description: Contains the fully-qualified path and file name with extension.

Property ID: 0x370D

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.13

Consuming reference: [\[MS-OXORMMS\]](#)

Alternate names: PR_ATTACH_LONG_PATHNAME, PR_ATTACH_LONG_PATHNAME_A, ptagAttachLongPathname, PR_ATTACH_LONG_PATHNAME_W

2.671 PidTagAttachmentContactPhoto

Canonical name: PidTagAttachmentContactPhoto

Description: Indicates that a contact photo attachment is attached to a Contact object.

Property ID: 0x7FFF

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_ATTACHMENT_CONTACTPHOTO

2.672 PidTagAttachmentFlags

Canonical name: PidTagAttachmentFlags

Description: Indicates special handling for an Attachment object.

Property ID: 0x7FFD

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.23

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#)

Alternate names: PR_ATTACHMENT_FLAGS, ptagAttachmentFlags

2.673 PidTagAttachmentHidden

Canonical name: PidTagAttachmentHidden

Description: Indicates whether an Attachment object is hidden from the end user.

Property ID: 0x7FFE

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.24

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_ATTACHMENT_HIDDEN

2.674 PidTagAttachmentLinkId

Canonical name: PidTagAttachmentLinkId

Description: Contains the type of Message object to which an attachment is linked.

Property ID: 0x7FFA

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.22

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_ATTACHMENT_LINKID, ptagAttachmentLinkId

2.675 PidTagAttachMethod

Canonical name: PidTagAttachMethod

Description: Represents the way the contents of an attachment are accessed.

Property ID: 0x3705

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.9

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_METHOD, ptagAttachMethod

2.676 PidTagAttachMimeTag

Canonical name: PidTagAttachMimeTag

Description: Contains a content-type MIME header.

Property ID: 0x370E

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#)

Alternate names: PR_ATTACH_MIME_TAG, PR_ATTACH_MIME_TAG_A, PR_ATTACH_MIME_TAG_W

2.677 PidTagAttachNumber

Canonical name: PidTagAttachNumber

Description: Identifies the Attachment object within its Message object.

Property ID: 0x0E21

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.6

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXRTFEX\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_NUM, ptagAttachNum

2.678 PidTagAttachPathname

Canonical name: PidTagAttachPathname

Description: Contains the 8.3 name of the **PidTagAttachLongPathname** property (section [2.670](#)).

Property ID: 0x3708

Data type: **PtypString**, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.14

Consuming reference: [\[MS-OXORMMS\]](#)

Alternate names: PR_ATTACH_PATHNAME, PR_ATTACH_PATHNAME_A, ptagAttachPathname, PR_ATTACH_PATHNAME_W

2.679 PidTagAttachPayloadClass

Canonical name: PidTagAttachPayloadClass

Description: Contains the class name of an object that can display the contents of the message.

Property ID: 0x371A

Data type: **PtypString**, 0x001F

Area: Outlook Application

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_PAYLOAD_CLASS, PR_ATTACH_PAYLOAD_CLASS_A, PR_ATTACH_PAYLOAD_CLASS_W, ptagAttachPayloadClass

2.680 PidTagAttachPayloadProviderGuidString

Canonical name: PidTagAttachPayloadProviderGuidString

Description: Contains the GUID of the software component that can display the contents of the message.

Property ID: 0x3719

Data type: **PtypString**, 0x001F

Area: Outlook Application

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.26

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_ATTACH_PAYLOAD_PROV_GUID_STR, PR_ATTACH_PAYLOAD_PROV_GUID_STR_A, PR_ATTACH_PAYLOAD_PROV_GUID_STR_W

2.681 PidTagAttachRendering

Canonical name: PidTagAttachRendering

Description: Contains a Windows Metafile, as specified in [\[MS-WMF\]](#), for the Attachment object.

Property ID: 0x3709

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.17

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_RENDERING, ptagAttachRendering

2.682 PidTagAttachSize

Canonical name: PidTagAttachSize

Description: Contains the size, in bytes, consumed by the Attachment object on the server.

Property ID: 0x0E20

Data type: PtypInteger32, 0x0003

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_ATTACH_SIZE, ptagAttachSize

2.683 PidTagAttachTag

Canonical name: PidTagAttachTag

Description: Contains the identifier information for the application that supplied the Attachment object data.

Property ID: 0x370A

Data type: PtypBinary, 0x0102

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.15

Consuming references: [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_TAG

2.684 PidTagAttachTransportName

Canonical name: PidTagAttachTransportName

Description: Contains the name of an attachment file, modified so that it can be correlated with TNEF messages.

Property ID: 0x370C

Data type: PtypString, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.19

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_ATTACH_TRANSPORT_NAME, PR_ATTACH_TRANSPORT_NAME_A, PR_ATTACH_TRANSPORT_NAME_W

2.685 PidTagAttributeHidden

Canonical name: PidTagAttributeHidden

Description: Specifies the hide or show status of a folder.

Property ID: 0x10F4

Data type: PtypBoolean, 0x000B

Area: Access Control Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1

Consuming references: [\[MS-OXOSFLD\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ATTR_HIDDEN, ptagAttrHidden, DAV:ishidden

2.686 PidTagAttributeReadOnly

Canonical name: PidTagAttributeReadOnly

Description:

Property ID: 0x10F6

Data type: PtypBoolean, 0x000B

Area: Access Control Properties

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.1.8

Consuming references: [\[MS-OXTNEF\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ATTR_READONLY, ptagAttrReadOnly, DAV:isreadonly

2.687 PidTagAutoForwarded

Canonical name: PidTagAutoForwarded

Description:

Property ID: 0x0005

Data type: PtypBoolean, 0x000B

Area: General Report Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.20

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_AUTO_FORWARDED, ptagAutoForwarded

2.688 PidTagAutoForwardComment

Canonical name: PidTagAutoForwardComment

Description: Contains text included in an automatically-generated message.

Property ID: 0x0004

Data type: PtypString, 0x001F

Area: General Report Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.21

Alternate names: PR_AUTO_FORWARD_COMMENT, PR_AUTO_FORWARD_COMMENT_A, PR_AUTO_FORWARD_COMMENT_W

2.689 PidTagAutoResponseSuppress

Canonical name: PidTagAutoResponseSuppress

Description: Specifies whether a client or server application should forego sending automated replies in response to this message.

Property ID: 0x3FDF

Data type: PtypInteger32, 0x0003

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.73

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_AUTO_RESPONSE_SUPPRESS, ptagAutoResponseSuppress

2.690 PidTagBirthday

Canonical name: PidTagBirthday

Description: Contains the date of the mail user's birthday at midnight.

Property ID: 0x3A42

Data type: **PtypTime**, 0x0040

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.79

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BIRTHDAY, urn:schemas:contacts:bday

2.691 PidTagBlockStatus

Canonical name: PidTagBlockStatus

Description: Indicates the user's preference for viewing external content (such as links to images on an **HTTP** server) in the message body (2).

Property ID: 0x1096

Data type: **PtypInteger32**, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.1

Alternate names: PR_BLOCK_STATUS, ptagBlockStatus

2.692 PidTagBody

Canonical name: PidTagBody

Description: Contains message body (2) text in **plain text** format.

Property ID: 0x1000

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BODY, PR_BODY_A, ptagBody, PR_BODY_W, urn:schemas:httpmail:textdescription

2.693 PidTagBodyContentId

Canonical name: PidTagBodyContentId

Description: Contains a GUID that corresponds to the current message body (2).

Property ID: 0x1015

Data type: PtypString, 0x001F

Area: Exchange

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.7

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_BODY_CONTENT_ID, PR_BODY_CONTENT_ID_A, PR_BODY_CONTENT_ID_W

2.694 PidTagBodyContentLocation

Canonical name: PidTagBodyContentLocation

Description: Contains a globally unique Uniform Resource Identifier (URI) that serves as a label for the current message body (2).

Property ID: 0x1014

Data type: PtypString, 0x001F

Area: MIME Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.8

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_BODY_CONTENT_LOCATION, PR_BODY_CONTENT_LOCATION_A, PR_BODY_CONTENT_LOCATION_W

2.695 PidTagBodyHtml

Canonical name: PidTagBodyHtml

Property ID: 0x1013

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.3

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_BODY_HTML, PR_BODY_HTML_A, ptagBodyHtml, PR_BODY_HTML_W

2.696 PidTagBusiness2TelephoneNumber

Canonical name: PidTagBusiness2TelephoneNumber

Description: Contains a secondary telephone number at the mail user's place of business.

Property ID: 0x3A1B

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.40

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: "PR_BUSINESS2_TELEPHONE_NUMBER, PR_BUSINESS2_TELEPHONE_NUMBER_A, PR_BUSINESS2_TELEPHONE_NUMBER_W, PR_OFFICE2_TELEPHONE_NUMBER, urn:schemas:contacts:telephonenumber2

2.697 PidTagBusiness2TelephoneNumbers

Canonical name: PidTagBusiness2TelephoneNumbers

Description: Contains secondary telephone numbers at the mail user's place of business.

Property ID: 0x3A1B

Data type: **PtypMultipleString**, 0x101F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.41

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_BUSINESS2_TELEPHONE_NUMBER_A_MV

2.698 PidTagBusinessFaxNumber

Canonical name: PidTagBusinessFaxNumber

Description: Contains the telephone number of the mail user's business fax machine.

Property ID: 0x3A24

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.51

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_FAX_NUMBER, PR_BUSINESS_FAX_NUMBER_A, PR_BUSINESS_FAX_NUMBER_W, urn:schemas:contacts:facsimiletelephonenumber

2.699 PidTagBusinessHomePage

Canonical name: PidTagBusinessHomePage

Description: Contains the URL of the mail user's business home page.

Property ID: 0x3A51

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.78

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_HOME_PAGE, PR_BUSINESS_HOME_PAGE_A, PR_BUSINESS_HOME_PAGE_W, urn:schemas:contacts:businesshomepage

2.700 PidTagBusinessTelephoneNumber

Canonical name: PidTagBusinessTelephoneNumber

Description: Contains the primary telephone number of the mail user's place of business.

Property ID: 0x3A08

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.38

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_BUSINESS_TELEPHONE_NUMBER, PR_BUSINESS_TELEPHONE_NUMBER_A, PR_BUSINESS_TELEPHONE_NUMBER_W, PR_OFFICE_TELEPHONE_NUMBER, urn:schemas:contacts:telephoneNumber

2.701 PidTagCallbackTelephoneNumber

Canonical name: PidTagCallbackTelephoneNumber

Description: Contains a telephone number to reach the mail user.

Property ID: 0x3A02

Data type: **PtypString**, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.44

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CALLBACK_TELEPHONE_NUMBER, PR_CALLBACK_TELEPHONE_NUMBER_A, PR_CALLBACK_TELEPHONE_NUMBER_W, urn:schemas:contacts:callbackphone

2.702 PidTagCallId

Canonical name: PidTagCallId

Description: Contains a unique identifier associated with the phone call.

Property ID: 0x6806

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.11

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaCallID

2.703 PidTagCarTelephoneNumber

Canonical name: PidTagCarTelephoneNumber

Description: Contains the mail user's car telephone number.

Property ID: 0x3A1E

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.47

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CAR_TELEPHONE_NUMBER, PR_CAR_TELEPHONE_NUMBER_A, PR_CAR_TELEPHONE_NUMBER_W, urn:schemas:contacts:othermobile

2.704 PidTagCdoRecurrenceid

Canonical name: PidTagCdoRecurrenceid

Description:

Property ID: 0x10C5

Data type: PtypTime, 0x0040

Area: Exchange

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.38

Alternate names: PR_CDO_RECURRENCEID, urn:schemas:calendar:recurrenceid

2.705 PidTagChangeKey

Canonical name: PidTagChangeKey

Description: Contains a structure that identifies the last change to the object.

Property ID: 0x65E2

Data type: PtypBinary, 0x0102

Area: History Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.7

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#)

Alternate names: PR_CHANGE_KEY

2.706 PidTagChangeNumber

Canonical name: PidTagChangeNumber

Description: Contains a structure that identifies the last change to the message or folder that is currently being synchronized.

Property ID: 0x67A4

Data type: **PtypInteger64**, 0x0014

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: ptagCn

2.707 PidTagChildrensNames

Canonical name: PidTagChildrensNames

Description:

Property ID: 0x3A58

Data type: **PtypMultipleString**, 0x101F

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.10.17

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CHILDRENS_NAMES, PR_CHILDRENS_NAMES_A, PR_CHILDRENS_NAMES_W, urn:schemas:contacts:childrensnames

2.708 PidTagClientActions

Canonical name: PidTagClientActions

Property ID: 0x6645

Data type: **PtypBinary**, 0x0102

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.6

Alternate names: PR_CLIENT_ACTIONS, ptagClientActions

2.709 PidTagClientSubmitTime

Canonical name: PidTagClientSubmitTime

Description: Contains the current time, in UTC, when the e-mail message is submitted.

Property ID: 0x0039

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_CLIENT_SUBMIT_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

2.710 PidTagCodePageId

Canonical name: PidTagCodePageId

Description: Contains the identifier for the client code page used for **Unicode** to **double-byte character set (DBCS)** string conversion.

Property ID: 0x66C3

Data type: PtypInteger32, 0x0003

Area: Exchange Profile Configuration

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_CODE_PAGE_ID, ptagCodePageId

2.711 PidTagComment

Canonical name: PidTagComment

Description: Contains a comment about the purpose or content of the Address Book object.

Property ID: 0x3004

Data type: PtypString, 0x001F

Area: Common

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.2

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMMENT, PR_COMMENT_A, ptagComment, PR_COMMENT_W, DAV:comment, http://schemas.microsoft.com/exchange/summary-utf8

2.712 PidTagCompanyMainTelephoneNumber

Canonical name: PidTagCompanyMainTelephoneNumber

Description: Contains the main telephone number of the mail user's company.

Property ID: 0x3A57

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.53

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMPANY_MAIN_PHONE_NUMBER, PR_COMPANY_MAIN_PHONE_NUMBER_A, PR_COMPANY_MAIN_PHONE_NUMBER_W, urn:schemas:contacts:organizationmainphone

2.713 PidTagCompanyName

Canonical name: PidTagCompanyName

Description: Contains the mail user's company name.

Property ID: 0x3A16

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.10

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#)

Alternate names: PR_COMPANY_NAME, PR_COMPANY_NAME_A, PR_COMPANY_NAME_W, urn:schemas:contacts:o

2.714 PidTagComputerNetworkName

Canonical name: PidTagComputerNetworkName

Description: Contains the name of the mail user's computer network.

Property ID: 0x3A49

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.74

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COMPUTER_NETWORK_NAME, PR_COMPUTER_NETWORK_NAME_A, PR_COMPUTER_NETWORK_NAME_W, urn:schemas:contacts:computernetworkname

2.715 PidTagConflictEntryId

Canonical name: PidTagConflictEntryId

Description: Contains the EntryID of the conflict resolve message.

Property ID: 0x3FF0

Data type: PtypBinary, 0x0102

Area: ICS

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.4.2

Alternate names: PR_CONFLICT_ENTRYID, ptagConflictEntryId

2.716 PidTagContainerClass

Canonical name: PidTagContainerClass

Description: Contains a string value that describes the type of Message object that a folder contains.

Property ID: 0x3613

Data type: PtypString, 0x001F

Area: Container Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.11.1

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDFOLD\]](#)

Alternate names: PR_CONTAINER_CLASS, PR_CONTAINER_CLASS_A, ptagContainerClass, PR_CONTAINER_CLASS_W,
<http://schemas.microsoft.com/exchange/outlookfolderclass>
<http://schemas.microsoft.com/exchange/outlookfolderclass>

2.717 PidTagContainerContents

Canonical name: PidTagContainerContents

Description: Always empty. An NSPI server defines this value for distribution lists and it is not present for other objects.

Property ID: 0x360F

Data type: PtypEmbeddedTable, 0x000D

Area: Container Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.6.3

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_CONTAINER_CONTENTS, ptagContainerContents

2.718 PidTagContainerFlags

Canonical name: PidTagContainerFlags

Description: Contains a bitmask of flags that describe capabilities of an address book container.

Property ID: 0x3600

Data type: **PtypInteger32**, 0x0003

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.2.1

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_CONTAINER_FLAGS

2.719 PidTagContainerHierarchy

Canonical name: PidTagContainerHierarchy

Description: Identifies all of the subfolders of the current folder.

Property ID: 0x360E

Data type: **PtypObject**, 0x000D

Area: Container Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_CONTAINER_HIERARCHY, ptagContainerHierarchy

2.720 PidTagContentCount

Canonical name: PidTagContentCount

Description: Specifies the number of rows under the header row.

Property ID: 0x3602

Data type: **PtypInteger32**, 0x0003

Area: Folder Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.1

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CONTENT_COUNT, ptagContentCount, DAV:visiblecount

2.721 PidTagContentFilterSpamConfidenceLevel

Canonical name: PidTagContentFilterSpamConfidenceLevel

Description: Indicates a confidence level that the message is spam.

Property ID: 0x4076

Data type: **PtypInteger32**, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMail\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CONTENT_FILTER_SCL, ptagContentFilterSCL

2.722 PidTagContentUnreadCount

Canonical name: PidTagContentUnreadCount

Description: Specifies the number of rows under the header row that have the **PidTagRead** property (section [2.950](#)) set to FALSE.

Property ID: 0x3603

Data type: **PtypInteger32**, 0x0003

Area: Folder Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.2

Consuming references: [\[MS-OXCTABL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CONTENT_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

2.723 PidTagConversationId

Canonical name: PidTagConversationId

Description: Contains a computed value derived from other conversation-related properties.

Property ID: 0x3013

Data type: **PtypBinary**, 0x0102

Area: Conversations

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.2

Consuming references: [\[MS-OXGLOS\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_CONVERSATION_ID

2.724 PidTagConversationIndex

Canonical name: PidTagConversationIndex

Description: Indicates the relative position of this message within a conversation thread.

Property ID: 0x0071

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#)

Alternate names: PR_CONVERSATION_INDEX, ptagConversationIndex

2.725 PidTagConversationIndexTracking

Canonical name: PidTagConversationIndexTracking

Description: Indicates whether the GUID portion of the **PidTagConversationIndex** property (section [2.724](#)) is to be used to compute the **PidTagConversationId** property (section [2.723](#)).

Property ID: 0x3016

Data type: PtypBoolean, 0x000B

Area: Conversations

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.4

Alternate names: PR_CONVERSATION_INDEX_TRACKING

2.726 PidTagConversationTopic

Canonical name: PidTagConversationTopic

Description: Contains an unchanging copy of the original subject.

Property ID: 0x0070

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_CONVERSATION_TOPIC, PR_CONVERSATION_TOPIC_A, ptagConversationTopic, PR_CONVERSATION_TOPIC_W, urn:schemas:httpmail:thread-topic

2.727 PidTagCountry

Canonical name: PidTagCountry

Description: Contains the name of the mail user's country/region.

Property ID: 0x3A26

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.24

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_COUNTRY, PR_COUNTRY_A, PR_COUNTRY_W, PR_BUSINESS_ADDRESS_COUNTRY, PR_BUSINESS_ADDRESS_COUNTRY_A, PR_BUSINESS_ADDRESS_COUNTRY_W, urn:schemas:contacts:mailingcountry

2.728 PidTagCreationTime

Canonical name: PidTagCreationTime

Description: Contains the time, in UTC, that the object was created.

Property ID: 0x3007

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.2.3

Consuming references: [\[MS-OXCFCAL\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CREATION_TIME, ptagCreationTime, DAV:creationdate

2.729 PidTagCreatorEntryId

Canonical name: PidTagCreatorEntryId

Description: Specifies the original author of the message according to their Address Book EntryID.

Property ID: 0x3FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.31

Consuming reference: [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CREATOR_ENTRYID, ptagCreatorEntryId

2.730 PidTagCreatorName

Canonical name: PidTagCreatorName

Description: Contains the name of a Message object.

Property ID: 0x3FF8

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_CREATOR_NAME, PR_CREATOR_NAME_A, ptagCreatorName, PR_CREATOR_NAME_W

2.731 PidTagCurrentDraftEntryId

Canonical name: PidTagCurrentDraftEntryId

Description: Contains an EntryID for the message corresponding to the unsent reply to another message.

Property ID:

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.81

Alternate name: dispidCurrentDraftEntryId

2.732 PidTagCustomerId

Canonical name: PidTagCustomerId

Description: Contains the mail user's customer identification number.

Property ID: 0x3A4A

Data type: PtypString, 0x001F

Area: Contact Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.75

Consuming references: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_CUSTOMER_ID, PR_CUSTOMER_ID_A, PR_CUSTOMER_ID_W, urn:schemas:contacts:customerid

2.733 PidTagDamBackPatched

Canonical name: PidTagDamBackPatched

Description: Indicates whether the **Deferred Action Message (DAM)** was updated by the server.

Property ID: 0x6647

Data type: PtypBoolean, 0x000B

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.2

Alternate names: PR_DAM_BACK_PATCHED, ptagDamBackPatched

2.734 PidTagDamOriginalEntryId

Canonical name: PidTagDamOriginalEntryId

Description: Contains the EntryID of the delivered message that the client has to process.

Property ID: 0x6646

Data type: PtypBinary, 0x0102

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.3

Alternate names: PR_DAM_ORIGINAL_ENTRYID

2.735 PidTagDefaultPostMessageClass

Canonical name: PidTagDefaultPostMessageClass

Description: Contains the message class of the object.

Property ID: 0x36E5

Data type: PtypString, 0x001F

Area: MapiContainer

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.11.2

Alternate names: PR_DEF_POST_MSGCLASS

2.736 PidTagDeferredActionMessageOriginalEntryId

Canonical name: PidTagDeferredActionMessageOriginalEntryId

Description: Contains the server EntryID for the DAM.

Property ID: 0x6741

Data type: PtypServerId, 0x00FB

Area: Server-side Rules Properties

Defining reference: [\[MS-OXORULE\]](#)

Alternate names: PR_DAM_ORIG_MSG_SVREID, ptagDamOrgMsgSvrEID

2.737 PidTagDeferredDeliveryTime

Canonical name: PidTagDeferredDeliveryTime

Description: Contains the date and time, in UTC, at which the sender prefers that the message be delivered.

Property ID: 0x000F

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.6

Alternate names: PR_DEFERRED_DELIVERY_TIME, ptagDeferredDeliveryTime, <http://schemas.microsoft.com/exchange/deferred-delivery-iso>

2.738 PidTagDeferredSendNumber

Canonical name: PidTagDeferredSendNumber

Description: Contains a number used in the calculation of how long to defer sending a message.

Property ID: 0x3FEB

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.2

Alternate names: PR_DEFERRED_SEND_NUMBER

2.739 PidTagDeferredSendTime

Canonical name: PidTagDeferredSendTime

Description: Contains the amount of time after which a client would like to defer sending the message.

Property ID: 0x3FEF

Data type: PtypTime, 0x0040

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.4

Alternate names: PR_DEFERRED_SEND_TIME, ptagDeferredSendTime

2.740 PidTagDeferredSendUnits

Canonical name: PidTagDeferredSendUnits

Description: Specifies the unit of time used as a multiplier with the **PidTagDeferredSendNumber** property (section [2.738](#)) value.

Property ID: 0x3FEC

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.3

Alternate names: PR_DEFERRED_SEND_UNITS

2.741 PidTagDelegatedByRule

Canonical name: PidTagDelegatedByRule

Description: Specifies whether the message was forwarded due to the triggering of a delegate forward rule.

Property ID: 0x3FE3

Data type: PtypBoolean, 0x000B

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.80

Consuming references: [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

Alternate names: PR_DELEGATED_BY_RULE

2.742 PidTagDelegateFlags

Canonical name: PidTagDelegateFlags

Description:

Property ID: 0x686B

Data type: PtypMultipleInteger32, 0x1003

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.6

Alternate names: PR_DELEGATE_FLAGS, ptagDelegateFlags

2.743 PidTagDeleteAfterSubmit

Canonical name: PidTagDeleteAfterSubmit

Description: Indicates that the original message is to be deleted after it is sent.

Property ID: 0x0E01

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.8

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXODOC\]](#)

Alternate names: PR_DELETE_AFTER_SUBMIT, ptagDeleteAfterSubmit

2.744 PidTagDeletedOn

Canonical name: PidTagDeletedOn

Description: Specifies the time, in UTC, when the item or folder was **soft deleted**.

Property ID: 0x668F

Data type: **PtypTime**, 0x0040

Area: ExchangeFolder

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.3

Alternate names: PR_DELETED_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

2.745 PidTagDepartmentName

Canonical name: PidTagDepartmentName

Description: Contains a name for the department in which the mail user works.

Property ID: 0x3A18

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.9

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_DEPARTMENT_NAME, PR_DEPARTMENT_NAME_A, PR_DEPARTMENT_NAME_W, urn:schemas:contacts:department

2.746 PidTagDepth

Canonical name: PidTagDepth

Description: Specifies the number of nested categories in which a given row is contained.

Property ID: 0x3005

Data type: **PtypInteger32**, 0x0003

Area: MapiCommon

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.4

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

Alternate names: PR_DEPTH, ptagDepth

2.747 PidTagDisplayBcc

Canonical name: PidTagDisplayBcc

Description: Contains a list of **blind carbon copy (Bcc) recipient** display names.

Property ID: 0x0E02

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.7

Consuming reference: [\[MS-OXCMSG\]](#)

Alternate names: PR_DISPLAY_BCC, PR_DISPLAY_BCC_A, ptagDisplayBcc, PR_DISPLAY_BCC_W, urn:schemas:httpmail:displaybcc

2.748 PidTagDisplayCc

Canonical name: PidTagDisplayCc

Description: Contains a list of carbon copy (Cc) recipient display names.

Property ID: 0x0E03

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_DISPLAY_CC, PR_DISPLAY_CC_A, ptagDisplayCc, PR_DISPLAY_CC_W, urn:schemas:httpmail:displaycc

2.749 PidTagDisplayName

Canonical name: PidTagDisplayName

Description: Contains the display name of the folder.

Property ID: 0x3001

Data type: PtypString, 0x001F

Area: MapiCommon

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.4

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDVSEC\]](#)

Alternate names: PR_DISPLAY_NAME, PR_DISPLAY_NAME_A, ptagDisplayName, PR_DISPLAY_NAME_W, urn:schemas:contacts:cn

2.750 PidTagDisplayNamePrefix

Canonical name: PidTagDisplayNamePrefix

Description: Contains the mail user's honorific title.

Property ID: 0x3A45

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.4

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_DISPLAY_NAME_PREFIX, PR_DISPLAY_NAME_PREFIX_A, PR_DISPLAY_NAME_PREFIX_W, urn:schemas:contacts:personaltitle

2.751 PidTagDisplayTo

Canonical name: PidTagDisplayTo

Description: Contains a list of the **primary recipient** display names, separated by semicolons, when an e-mail message has primary recipients (1).

Property ID: 0x0E04

Data type: PtypString, 0x001F

Area: Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_DISPLAY_TO, PR_DISPLAY_TO_A, ptagDisplayTo, PR_DISPLAY_TO_W

2.752 PidTagDisplayType

Canonical name: PidTagDisplayType

Description: Contains an integer value that indicates how to display an Address Book object in a table or as an addressee on a message.

Property ID: 0x3900

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.11

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_DISPLAY_TYPE, ptagDisplayType

2.753 PidTagDisplayTypeEx

Canonical name: PidTagDisplayTypeEx

Description: Contains an integer value that indicates how to display an Address Book object in a table or as a recipient (1) on a message.

Property ID: 0x3905

Data type: PtypInteger32, 0x0003

Area: MapiAddressBook

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_DISPLAY_TYPE_EX

2.754 PidTagEmailAddress

Canonical name: PidTagEmailAddress

Description: Contains the e-mail address of a Message object.

Property ID: 0x3003

Data type: PtypString, 0x001F

Area: MapiCommon

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.14

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXPSVAL\]](#)

Alternate names: PR_EMAIL_ADDRESS, PR_EMAIL_ADDRESS_A, PR_EMAIL_ADDRESS_W

2.755 PidTagEndDate

Canonical name: PidTagEndDate

Description: Contains the value of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

Property ID: 0x0061

Data type: PtypTime, 0x0040

Area: MapiEnvelope Property set

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.31

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: PR_END_DATE, http://schemas.microsoft.com/mapi/end_date

2.756 PidTagEntryId

Canonical name: PidTagEntryId

Description: Contains the information to identify many different types of **messaging objects**.

Property ID: 0x0FFF

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.4

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXWAVLS\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_ENTRYID, ptagEntryId

2.757 PidTagExceptionEndTime

Canonical name: PidTagExceptionEndTime

Description: Contains the start date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFC

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.1.5

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_EXCEPTION_ENDTIME, ptagExceptionEndTime

2.758 PidTagExceptionReplaceTime

Canonical name: PidTagExceptionReplaceTime

Description: Indicates the original date and time, in UTC, at which the instance in the recurrence pattern would have occurred if it were not an exception.

Property ID: 0x7FF9

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.1.6

Alternate names: PR_EXCEPTION_REPLACETIME

2.759 PidTagExceptionStartTime

Canonical name: PidTagExceptionStartTime

Description: Contains the end date and time of the exception in the local time zone of the computer when the exception is created.

Property ID: 0x7FFB

Data type: PtypTime, 0x0040

Area: MessageClassDefinedNonTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.10.1.4

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_EXCEPTION_STARTTIME, ptagExceptionStartTime

2.760 PidTagExchangeNTSecurityDescriptor

Canonical name: PidTagExchangeNTSecurityDescriptor

Description: Contains the calculated security descriptor for the item.

Property ID: 0x0E84

Data type: PtypBinary, 0x0102

Area: Calendar Document

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.8

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/ntsecuritydescriptor>,
<http://schemas.microsoft.com/exchange/ntsecuritydescriptor>

2.761 PidTagExpiryNumber

Canonical name: PidTagExpiryNumber

Description: Contains an integer value that is used along with the **PidTagExpiryUnits** property (section [2.763](#)) to define the expiry send time.

Property ID: 0x3FED

Data type: PtypInteger32, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.5

Alternate names: PR_EXPIRY_NUMBER

2.762 PidTagExpiryTime

Canonical name: PidTagExpiryTime

Description: Contains the time, in UTC, after which a client wants to receive an expiry event if the message arrives late.

Property ID: 0x0015

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.7

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_EXPIRY_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date, http://schemas.microsoft.com/exchange/expiry-date-iso

2.763 PidTagExpiryUnits

Canonical name: PidTagExpiryUnits

Description: Contains the unit of time that the value of the **PidTagExpiryNumber** property (section [2.761](#)) multiplies.

Property ID: 0x3FEE

Data type: **PtypInteger32**, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.6

Alternate names: PR_EXPIRY_UNITS

2.764 PidTagExtendedFolderFlags

Canonical name: PidTagExtendedFolderFlags

Description: Contains encoded sub-properties for a folder.

Property ID: 0x36DA

Data type: **PtypBinary**, 0x0102

Area: MapiContainer

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_EXTENDED_FOLDER_FLAGS, ptagExtendedFolderFlags

2.765 PidTagExtendedRuleMessageActions

Canonical name: PidTagExtendedRuleMessageActions

Description: Contains action information about named properties used in the rule.

Property ID: 0x0E99

Data type: **PtypBinary**, 0x0102

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.9

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_EXTENDED_RULE_MSG_ACTIONS

2.766 PidTagExtendedRuleMessageCondition

Canonical name: PidTagExtendedRuleMessageCondition

Description: Contains condition information about named properties used in the rule.

Property ID: 0x0E9A

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.10

Consuming references: [\[MS-OXCPRPT\]](#), [\[MS-OXCSPAM\]](#)

Alternate names: PR_EXTENDED_RULE_MSG_CONDITION

2.767 PidTagExtendedRuleSizeLimit

Canonical name: PidTagExtendedRuleSizeLimit

Description: Contains the maximum size, in bytes, that the user is allowed to accumulate for a single extended rule.

Property ID: 0x0E9B

Data type: PtypInteger32, 0x0003

Area: Rules

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Consuming Reference: [\[MS-OXORULE\]](#)

Alternate names: PR_EXTENDED_RULE_SIZE_LIMIT

2.768 PidTagFaxNumberOfPages

Canonical name: PidTagFaxNumberOfPages

Description: Contains the number of pages in a Fax object.

Property ID: 0x6804

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.7

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaFaxNumberOfPages

2.769 PidTagFlagCompleteTime

Canonical name: PidTagFlagCompleteTime

Description: Specifies the date and time, in UTC, that the Message object was flagged as complete.

Property ID: 0x1091

Data type: PtypTime, 0x0040

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_FLAG_COMPLETE_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

2.770 PidTagFlagStatus

Canonical name: PidTagFlagStatus

Description: Specifies the flag state of the Message object.

Property ID: 0x1090

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FLAG_STATUS, ptagFlagStatus

2.771 PidTagFlatUrlName

Canonical name: PidTagFlatUrlName

Description: Contains a unique identifier for an item across the store.

Property ID: 0x670E

Data type: PtypString, 0x001F

Area: ExchangeAdministrative

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.8.9

Consuming references: [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_FLAT_URL_NAME, PR_FLAT_URL_NAME_A, PR_FLAT_URL_NAME_W, ptagFlatURLName, http://schemas.microsoft.com/exchange/permanenturl

2.772 PidTagFolderAssociatedContents

Canonical name: PidTagFolderAssociatedContents

Description: Identifies all FAI messages in the current folder.

Property ID: 0x3610

Data type: PtypObject, 0x000D

Area: MapiContainer

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_FOLDER_ASSOCIATED_CONTENTS

2.773 PidTagFolderId

Canonical name: PidTagFolderId

Description: Contains the Folder ID (FID) ([\[MS-OXCDATA\]](#) section 2.2.1.1) of the folder.

Property ID: 0x6748

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: ptagFID

2.774 PidTagFolderType

Canonical name: PidTagFolderType

Description: Specifies the type of a folder that includes the **Root folder**, Generic folder, and Search folder.

Property ID: 0x3601

Data type: PtypInteger32, 0x0003

Area: MapiContainer

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.5

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_FOLDER_TYPE, ptagFolderType

2.775 PidTagFollowupIcon

Canonical name: PidTagFollowupIcon

Description: Specifies the flag color of the Message object.

Property ID: 0x1095

Data type: **PtypInteger32**, 0x0003

Area: RenMessageFolder

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_FOLLOWUP_ICON, ptagFollowupIcon

2.776 PidTagFreeBusyCountMonths

Canonical name: PidTagFreeBusyCountMonths

Description: Contains an integer value used to calculate the start and end dates of the range of free/busy data to be published to the public folders.

Property ID: 0x6869

Data type: **PtypInteger32**, 0x0003

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.1

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_FREEBUSY_COUNT_MONTHS

2.777 PidTagFreeBusyEntryIds

Canonical name: PidTagFreeBusyEntryIds

Description: Contains EntryIDs of the Delegate Information object, the free/busy message of the logged on user, and the folder with the **PidTagDisplayName** property (section [2.749](#)) value of "Freebusy Data".

Property ID: 0x36E4

Data type: **PtypMultipleBinary**, 0x1102

Area: MapiContainer

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.6

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_FREEBUSY_ENTRYIDS, ptagFreeBusyEntryIds

2.778 PidTagFreeBusyMessageEmailAddress

Canonical name: PidTagFreeBusyMessageEmailAddress

Description: Specifies the e-mail address of the user to whom this free/busy message applies.

Property ID: 0x6849

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.12

Alternate names: PR_FREEBUSY_EMA

2.779 PidTagFreeBusyPublishEnd

Canonical name: PidTagFreeBusyPublishEnd

Description: Specifies the end time, in UTC, of the publishing range.

Property ID: 0x6848

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.10

Alternate names: PR_FREEBUSY_PUBLISH_END

2.780 PidTagFreeBusyPublishStart

Canonical name: PidTagFreeBusyPublishStart

Description: Specifies the start time, in UTC, of the publishing range.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.9

Alternate names: PR_FREEBUSY_PUBLISH_START

2.781 PidTagFreeBusyRangeTimestamp

Canonical name: PidTagFreeBusyRangeTimestamp

Description: Specifies the time, in UTC, that the data was published.

Property ID: 0x6868

Data type: PtypTime, 0x0040

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.11

Alternate names: PR_FREEBUSY_RANGE_TIMESTAMP

2.782 PidTagFtpSite

Canonical name: PidTagFtpSite

Description: Contains the **File Transfer Protocol (FTP)** site address of the mail user.

Property ID: 0x3A4C

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.76

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_FTP_SITE, PR_FTP_SITE_A, PR_FTP_SITE_W, urn:schemas:contacts:ftpsite

2.783 PidTagGatewayNeedsToRefresh

Canonical name: PidTagGatewayNeedsToRefresh

Description: This property is deprecated and SHOULD NOT be used.

Property ID: 0x6846

Data type: PtypBoolean, 0x000B

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.4.1

Alternate names: PR_GATEWAY_NEEDS_TO_REFRESH

2.784 PidTagGender

Canonical name: PidTagGender

Description: Contains a value that represents the mail user's gender.

Property ID: 0x3A4D

Data type: PtypInteger16, 0x0002

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.73

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GENDER, urn:schemas:contacts:gender

2.785 PidTagGeneration

Canonical name: PidTagGeneration

Description: Contains a generational abbreviation that follows the full name of the mail user.

Property ID: 0x3A05

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.6

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GENERATION, PR_GENERATION_A, PR_GENERATION_W, urn:schemas:contacts:namesuffix

2.786 PidTagGivenName

Canonical name: PidTagGivenName

Description: Contains the mail user's given name.

Property ID: 0x3A06

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.2

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GIVEN_NAME, PR_GIVEN_NAME_A, PR_GIVEN_NAME_W, urn:schemas:contacts:givenName

2.787 PidTagGovernmentIdNumber

Canonical name: PidTagGovernmentIdNumber

Description: Contains a government identifier for the mail user.

Property ID: 0x3A07

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.59

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_GOVERNMENT_ID_NUMBER, PR_GOVERNMENT_ID_NUMBER_A, PR_GOVERNMENT_ID_NUMBER_W, urn:schemas:contacts:governmentid

2.788 PidTagHasAttachments

Canonical name: PidTagHasAttachments

Description: Indicates whether the Message object contains at least one attachment.

Property ID: 0x0E1B

Data type: PtypBoolean, 0x000B

Area: Message Attachment Properties Property set

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

2.789 PidTagHasDeferredActionMessages

Canonical name: PidTagHasDeferredActionMessages

Description: Indicates whether a Message object has a deferred action message associated with it.

Property ID: 0x3FEA

Data type: PtypBoolean, 0x000B

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.9.1

Alternate names: PR_HAS_DAMS, ptagHasDAMs

2.790 PidTagHasNamedProperties

Canonical name: PidTagHasNamedProperties

Description: Indicates whether the Message object has a named property.

Property ID: 0x664A

Data type: PtypBoolean, 0x000B

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.39

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_HAS_NAMED_PROPERTIES, ptagHasNamedProperties

2.791 PidTagHasRules

Canonical name: PidTagHasRules

Description: Indicates whether a Folder object has rules.

Property ID: 0x663A

Data type: PtypBoolean, 0x000B

Area: ExchangeFolder

Defining reference: [\[MS-OXORULE\]](#) section 2.2.8.1

Alternate names: PR_HAS_RULES, ptagHasRules

2.792 PidTagHierarchyChangeNumber

Canonical name: PidTagHierarchyChangeNumber

Description: Contains a number that monotonically increases every time a subfolder is added to, or deleted from, this folder.

Property ID: 0x663E

Data type: PtypInteger32, 0x0003

Area: ExchangeFolder

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.7

Alternate names: PR_HIERARCHY_CHANGE_NUM

2.793 PidTagHobbies

Canonical name: PidTagHobbies

Description: Contains the names of the mail user's hobbies.

Property ID: 0x3A43

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.69

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOBBIES, PR_HOBBIES_A, PR_HOBBIES_W, urn:schemas:contacts:hobbies

2.794 PidTagHome2TelephoneNumber

Canonical name: PidTagHome2TelephoneNumber

Description: Contains a secondary telephone number at the mail user's home.

Property ID: 0x3A2F

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.42

Consuming references: [\[MS-OXOAB\]](#), [MS-OXOABK], [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME2_TELEPHONE_NUMBER, PR_HOME2_TELEPHONE_NUMBER_A, PR_HOME2_TELEPHONE_NUMBER_W, urn:schemas:contacts:homephone2

2.795 PidTagHome2TelephoneNumbers

Canonical name: PidTagHome2TelephoneNumbers

Description: Contains secondary telephone numbers at the mail user's home.

Property ID: 0x3A2F

Data type: PtypMultipleString, 0x101F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.43

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_HOME2_TELEPHONE_NUMBER_A_MV

2.796 PidTagHomeAddressCity

Canonical name: PidTagHomeAddressCity

Description: Contains the name of the mail user's home locality, such as the town or city.

Property ID: 0x3A59

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.27

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_CITY, PR_HOME_ADDRESS_CITY_A, PR_HOME_ADDRESS_CITY_W, urn:schemas:contacts:homeCity

2.797 PidTagHomeAddressCountry

Canonical name: PidTagHomeAddressCountry

Description: Contains the name of the mail user's home country/region.

Property ID: 0x3A5A

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.30

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_COUNTRY, PR_HOME_ADDRESS_COUNTRY_A, PR_HOME_ADDRESS_COUNTRY_W, urn:schemas:contacts:homeCountry

2.798 PidTagHomeAddressPostalCode

Canonical name: PidTagHomeAddressPostalCode

Description: Contains the postal code for the mail user's home postal address.

Property ID: 0x3A5B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.29

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_POSTAL_CODE, PR_HOME_ADDRESS_POSTAL_CODE_A, PR_HOME_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:homePostalCode

2.799 PidTagHomeAddressPostOfficeBox

Canonical name: PidTagHomeAddressPostOfficeBox

Description: Contains the number or identifier of the mail user's home post office box.

Property ID: 0x3A5E

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.26

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_POST_OFFICE_BOX, PR_HOME_ADDRESS_POST_OFFICE_BOX_A, PR_HOME_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:homepostofficebox

2.800 PidTagHomeAddressStateOrProvince

Canonical name: PidTagHomeAddressStateOrProvince

Description: Contains the name of the mail user's home state or province.

Property ID: 0x3A5C

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.28

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_STATE_OR_PROVINCE, PR_HOME_ADDRESS_STATE_OR_PROVINCE_A, PR_HOME_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:homeState

2.801 PidTagHomeAddressStreet

Canonical name: PidTagHomeAddressStreet

Description: Contains the mail user's home street address.

Property ID: 0x3A5D

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.25

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_ADDRESS_STREET, PR_HOME_ADDRESS_STREET_A, PR_HOME_ADDRESS_STREET_W, urn:schemas:contacts:homeStreet

2.802 PidTagHomeFaxNumber

Canonical name: PidTagHomeFaxNumber

Description: Contains the telephone number of the mail user's home fax machine.

Property ID: 0x3A25

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.52

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_FAX_NUMBER, PR_HOME_FAX_NUMBER_A, PR_HOME_FAX_NUMBER_W, urn:schemas:contacts:homefax

2.803 PidTagHomeTelephoneNumber

Canonical name: PidTagHomeTelephoneNumber

Description: Contains the primary telephone number of the mail user's home.

Property ID: 0x3A09

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.39

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_HOME_TELEPHONE_NUMBER, PR_HOME_TELEPHONE_NUMBER_A, PR_HOME_TELEPHONE_NUMBER_W, urn:schemas:contacts:homePhone

2.804 PidTagHtml

Canonical name: PidTagHtml

Description: Contains message body (2) text in HTML format.

Property ID: 0x1013

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.48.9

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_HTML, ptagHtml

2.805 PidTagICalendarEndTime

Canonical name: PidTagICalendarEndTime

Description: Contains the date and time, in UTC, when an appointment or meeting ends.

Property ID: 0x10C4

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.39

Consuming Reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:dtend

2.806 PidTagICalendarReminderNextTime

Canonical name: PidTagICalendarReminderNextTime

Description: Contains the date and time, in UTC, for the activation of the next reminder.

Property ID: 0x10CA

Data type: PtypTime, 0x0040

Area: Calendar

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.40

Alternate names: urn:schemas:calendar:remindernexttime

2.807 PidTagICalendarStartTime

Canonical name: PidTagICalendarStartTime

Description: Contains the date and time, in UTC, when the appointment or meeting starts.

Property ID: 0x10C3

Data type: PtypTime, 0x0040

Area: Calendar Property set

Defining reference: [\[MS-XWDCAL\]](#) section 2.2.2.41

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: urn:schemas:calendar:dtstart

2.808 PidTagIconIndex

Canonical name: PidTagIconIndex

Description: Specifies which icon is to be used by a user interface when displaying a group of Note objects.

Property ID: 0x1080

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.10

Consuming references: [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ICON_INDEX, ptagIconIndex

2.809 PidTagImportance

Canonical name: PidTagImportance

Description: Indicates the level of importance assigned by the end user to the Message object.

Property ID: 0x0017

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.11

Consuming references: [\[MS-OXCFCOLD\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, http://schemas.microsoft.com/exchange/importance-long, http://schemas.microsoft.com/exchange/x-priority-long

2.810 PidTagInConflict

Canonical name: PidTagInConflict

Description: Specifies whether the attachment represents an alternate replica.

Property ID: 0x666C

Data type: **PtypBoolean**, 0x000B

Area: Conflict Note

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.4.3

Alternate names: PR_IN_CONFLICT, ptagInConflict

2.811 PidTagInitialDetailsPane

Canonical name: PidTagInitialDetailsPane

Description: Indicates which page of a display template to display first.

Property ID: 0x3F08

Data type: **PtypInteger32**, 0x0003

Area: MAPI Display Tables

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.33

Consuming Reference: [\[MS-NSPI\]](#)

Alternate names: PR_INITIAL_DETAILS_PANE

2.812 PidTagInitials

Canonical name: PidTagInitials

Description: Contains the initials for parts of the full name of the mail user.

Property ID: 0x3A0A

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.5

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_INITIALS, PR_INITIALS_A, PR_INITIALS_W, urn:schemas:contacts:initials

2.813 PidTagInReplyToId

Canonical name: PidTagInReplyToId

Description: Contains the value of the original message's **PidTagInternetMessageId** property (section [2.820](#)) value.

Property ID: 0x1042

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.13

Consuming Reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_IN_REPLY_TO_ID, PR_IN_REPLY_TO_ID_A, PR_IN_REPLY_TO_ID_W

2.814 PidTagInstanceKey

Canonical name: PidTagInstanceKey

Description: Contains an object on an NSPI server.

Property ID: 0x0FF6

Data type: **PtypBinary**, 0x0102

Area: Table Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.6

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOABKT\]](#)

Alternate names: PR_INSTANCE_KEY, ptagInstanceKey

2.815 PidTagInstanceNum

Canonical name: PidTagInstanceNum

Description: Contains an identifier for a single instance of a row in the table.

Property ID: 0x674E

Data type: **PtypInteger32**, 0x0003

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.2

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: ptagInstanceNum

2.816 PidTagInstID

Canonical name: PidTagInstID

Description: Contains an identifier for all instances of a row in the table.

Property ID: 0x674D

Data type: **PtypInteger64**, 0x0014

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.1

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: ptagInstID

2.817 PidTagInternetArticleNumber

Canonical name: PidTagInternetArticleNumber

Description:

Property ID: 0x0E23

Data type: **PtypInteger32**, 0x0003

Area: MIME Properties

Defining reference:

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_INTERNET_ARTICLE_NUMBER

2.818 PidTagInternetCodepage

Canonical name: PidTagInternetCodepage

Description: Indicates the code page used for the **PidTagBody** property (section [2.692](#)) or the **PidTagBodyHtml** property (section [2.695](#)).

Property ID: 0x3FDE

Data type: **PtypInteger32**, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.6

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_INTERNET_CPID, ptagInternetCpid

2.819 PidTagInternetMailOverrideFormat

Canonical name: PidTagInternetMailOverrideFormat

Description: Indicates the encoding method and HTML inclusion for attachments.

Property ID: 0x5902

Data type: **PtypInteger32**, 0x0003

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.11

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

Alternate names: PR_INETMAIL_OVERRIDE_FORMAT, ptagInetMailOverrideFormat

2.820 PidTagInternetMessageId

Canonical name: PidTagInternetMessageId

Description: Corresponds to the **message-id** field.

Property ID: 0x1035

Data type: **PtypString**, 0x001F

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_INTERNET_MESSAGE_ID, PR_INTERNET_MESSAGE_ID_A, PR_INTERNET_MESSAGE_ID_W

2.821 PidTagInternetReferences

Canonical name: PidTagInternetReferences

Description: Contains a list of message IDs that specify the messages to which this reply is related.

Property ID: 0x1039

Data type: **PtypString**, 0x001F

Area: MIME Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.26

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_INTERNET_REFERENCES, PR_INTERNET_REFERENCES_A, PR_INTERNET_REFERENCES_W

2.822 PidTagIpmAppointmentEntryId

Canonical name: PidTagIpmAppointmentEntryId

Description: Contains the EntryID of the Calendar folder.

Property ID: 0x36D0

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_APPOINTMENT_ENTRYID

2.823 PidTagIpmContactEntryId

Canonical name: PidTagIpmContactEntryId

Description: Contains the EntryID of the Contacts folder.

Property ID: 0x36D1

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_CONTACT_ENTRYID

2.824 PidTagIpmDraftsEntryId

Canonical name: PidTagIpmDraftsEntryId

Description: Contains the EntryID of the Drafts folder.

Property ID: 0x36D7

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Alternate names: PR_IPM_DRAFTS_ENTRYID

2.825 PidTagIpmJournalEntryId

Canonical name: PidTagIpmJournalEntryId

Description: Contains the EntryID of the Journal folder.

Property ID: 0x36D2

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_JOURNAL_ENTRYID

2.826 PidTagIpmNoteEntryId

Canonical name: PidTagIpmNoteEntryId

Description: Contains the EntryID of the Notes folder.

Property ID: 0x36D3

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_NOTE_ENTRYID

2.827 PidTagIpmTaskEntryId

Canonical name: PidTagIpmTaskEntryId

Description: Contains the EntryID of the Tasks folder.

Property ID: 0x36D4

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Consuming references: [\[MS-OXODLGT\]](#)

Alternate names: PR_IPM_TASK_ENTRYID

2.828 PidTagIsdnNumber

Canonical name: PidTagIsdnNumber

Description: Contains the **Integrated Services Digital Network (ISDN)** telephone number of the mail user.

Property ID: 0x3A2D

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.56

Consuming references: [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ISDN_NUMBER, PR_ISDN_NUMBER_A, PR_ISDN_NUMBER_W, urn:schemas:contacts:internationalisdnnumber

2.829 PidTagJunkAddRecipientsToSafeSendersList

Canonical name: PidTagJunkAddRecipientsToSafeSendersList

Description: Indicates whether e-mail recipients (1) are to be added to the safe senders list.

Property ID: 0x6103

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.1

Alternate names: PR_JUNK_ADD_RECIPS_TO_SSL

2.830 PidTagJunkIncludeContacts

Canonical name: PidTagJunkIncludeContacts

Description: Indicates whether e-mail addresses of the contacts in the Contacts folder are treated in a special way with respect to the spam filter.

Property ID: 0x6100

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.2

Alternate names: PR_JUNK_INCLUDE_CONTACTS

2.831 PidTagJunkPermanentlyDelete

Canonical name: PidTagJunkPermanentlyDelete

Description: Indicates whether messages identified as spam can be permanently deleted.

Property ID: 0x6102

Data type: PtypInteger32, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.3

Alternate names: PR_JUNK_PERMANENTLY_DELETE

2.832 PidTagJunkPhishingEnableLinks

Canonical name: PidTagJunkPhishingEnableLinks

Description: Indicated whether the phishing stamp on a message is to be ignored.

Property ID: 0x6107

Data type: PtypBoolean, 0x000B

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.4

Consuming reference: [\[MS-OXPHISH\]](#)

Alternate names: PR_JUNK_PHISHING_ENABLE_LINKS

2.833 PidTagJunkThreshold

Canonical name: PidTagJunkThreshold

Description: Indicates how aggressively incoming e-mail is to be sent to the Junk E-mail folder.

Property ID: 0x6101

Data type: **PtypInteger32**, 0x0003

Area: Spam

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.5

Alternate names: PR_JUNK_THRESHOLD

2.834 PidTagKeyword

Canonical name: PidTagKeyword

Description: Contains a keyword that identifies the mail user to the mail user's system administrator.

Property ID: 0x3A0B

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.58

Alternate names: PR_KEYWORD, PR_KEYWORD_A, PR_KEYWORD_W

2.835 PidTagLanguage

Canonical name: PidTagLanguage

Description: Contains a value that indicates the language in which the messaging user is writing messages.

Property ID: 0x3A0C

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.61

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LANGUAGE, PR_LANGUAGE_A, PR_LANGUAGE_W,
urn:schemas:contacts:language

2.836 PidTagLastModificationTime

Canonical name: PidTagLastModificationTime

Description: Contains the time, in UTC, of the last modification to the object.

Property ID: 0x3008

Data type: PtypTime, 0x0040

Area: Message Time Properties **Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.2

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LAST_MODIFICATION_TIME, ptagLastModificationTime,
urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

2.837 PidTagLastModifierEntryId

Canonical name: PidTagLastModifierEntryId

Description: Specifies the Address Book EntryID of the last user to modify the contents of the message.

Property ID: 0x3FFB

Data type: PtypBinary, 0x0102

Area: History Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.32

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_LAST_MODIFIER_ENTRYID, ptagLastModifierEntryId

2.838 PidTagLastModifierName

Canonical name: PidTagLastModifierName

Description: Contains the name of the last mail user to change the Message object.

Property ID: 0x3FFA

Data type: PtypString, 0x001F

Area: History Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_LAST_MODIFIER_NAME, PR_LAST_MODIFIER_NAME_A, ptagLastModifierName, PR_LAST_MODIFIER_NAME_W

2.839 PidTagLastVerbExecuted

Canonical name: PidTagLastVerbExecuted

Description: Specifies the last verb executed for the message item to which it is related.

Property ID: 0x1081

Data type: PtypInteger32, 0x0003

Area: History Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.14

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_LAST_VERB_EXECUTED, ptagLastVerbExecuted

2.840 PidTagLastVerbExecutionTime

Canonical name: PidTagLastVerbExecutionTime

Description: Contains the date and time, in UTC, during which the operation represented in the **PidTagLastVerbExecuted** property (section [2.839](#)) took place.

Property ID: 0x1082

Data type: PtypTime, 0x0040

Area: History Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.15

Consuming Reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_LAST_VERB_EXECUTION_TIME, ptagLastVerbExecutionTime

2.841 PidTagListHelp

Canonical name: PidTagListHelp

Description: Contains a URI that provides detailed help information for the mailing list from which an e-mail message was sent.

Property ID: 0x1043

Data type: PtypString, 0x001F

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.77

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_HELP, PR_LIST_HELP_A, PR_LIST_HELP_W

2.842 PidTagListSubscribe

Canonical name: PidTagListSubscribe

Description: Contains the URI that subscribes a recipient (2) to a message's associated mailing list.

Property ID: 0x1044

Data type: **PtypString**, 0x001F

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.78

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_SUBSCRIBE, PR_LIST_SUBSCRIBE_A, PR_LIST_SUBSCRIBE_W

2.843 PidTagListUnsubscribe

Canonical name: PidTagListUnsubscribe

Description: Contains the URI that unsubscribes a recipient (2) from a message's associated mailing list.

Property ID: 0x1045

Data type: **PtypString**, 0x001F

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.79

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_LIST_UNSUBSCRIBE, PR_LIST_UNSUBSCRIBE_A, PR_LIST_UNSUBSCRIBE_W

2.844 PidTagLocalCommitTime

Canonical name: PidTagLocalCommitTime

Description: Contains the time, in UTC, that a **RopCreateMessage** remote operation (ROP) ([\[MS-OXCROPS\]](#) section 2.2.6.2) was processed.

Property ID: 0x6709

Data type: **PtypTime**, 0x0040

Area: Server

Defining reference:

Consuming Reference: [\[MS-OXCMSG\]](#)

Alternate names: PR_LOCAL_COMMIT_TIME, ptagLocalCommitTime

2.845 PidTagLocaleId

Canonical name: PidTagLocaleId

Description: Contains the **Logon object** LocaleID.

Property ID: 0x66A1

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-OXCSTOR\]](#)

Alternate names: PR_LOCALE_ID, ptagLocaleId

2.846 PidTagLocality

Canonical name: PidTagLocality

Description: Contains the name of the mail user's locality, such as the town or city.

Property ID: 0x3A27

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.21

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LOCALITY, PR_LOCALITY_A, PR_LOCALITY_W, PR_BUSINESS_ADDRESS_LOCALITY, PR_BUSINESS_ADDRESS_LOCALITY_A, PR_BUSINESS_ADDRESS_LOCALITY_W, urn:schemas:contacts:mailingcity

2.847 PidTagLocation

Canonical name: PidTagLocation

Description: Contains the location of the mail user.

Property ID: 0x3A0D

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.62

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_LOCATION, PR_LOCATION_A, PR_LOCATION_W, urn:schemas:contacts:location

2.848 PidTagMailboxOwnerEntryId

Canonical name: PidTagMailboxOwnerEntryId

Description: Contains the EntryID in the Global Address List (GAL) of the owner of the mailbox.

Property ID: 0x661B

Data type: PtypBinary, 0x0102

Area: Message Store Properties

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_MAILBOX_OWNER_ENTRYID, ptagMailboxOwnerEntryId

2.849 PidTagMailboxOwnerName

Canonical name: PidTagMailboxOwnerName

Description: Contains the display name of the owner of the mailbox.

Property ID: 0x661C

Data type: PtypString, 0x001F

Area: Message Store Properties

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Consuming reference: [\[MS-OXOCAL\]](#)

Alternate names: PR_MAILBOX_OWNER_NAME, PR_MAILBOX_OWNER_NAME_A, ptagMailboxOwnerName, PR_MAILBOX_OWNER_NAME_W

2.850 PidTagManagerName

Canonical name: PidTagManagerName

Description: Contains the name of the mail user's manager.

Property ID: 0x3A4E

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.12

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MANAGER_NAME, PR_MANAGER_NAME_A, PR_MANAGER_NAME_W, urn:schemas:contacts:manager

2.851 PidTagMappingSignature

Canonical name: PidTagMappingSignature

Description: A 16-byte constant that is present on all Address Book objects, but is not present on objects in an offline address book.

Property ID: 0x0FF8

Data type: PtypBinary, 0x0102

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.32

Consuming reference: [\[MS-NSPI\]](#)

Alternate names: PR_MAPPING_SIGNATURE, ptagMappingSignature

2.852 PidTagMaximumSubmitMessageSize

Canonical name: PidTagMaximumSubmitMessageSize

Description: Maximum size, in kilobytes, of a message that a user is allowed to submit for transmission to another user.

Property ID: 0x666D

Data type: PtypInteger32, 0x0003

Area: Message Store Properties

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_MAX_SUBMIT_MESSAGE_SIZE

2.853 PidTagMemberId

Canonical name: PidTagMemberId

Description: Contains a unique identifier that the messaging server generates for each user.

Property ID: 0x6671

Data type: PtypInteger64, 0x0014

Area: Access Control Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.5

Alternate names: PR_MEMBER_ID, ptagMemberId

2.854 PidTagMemberName

Canonical name: PidTagMemberName

Description: Contains the user-readable name of the user.

Property ID: 0x6672

Data type: PtypString, 0x001F

Area: Access Control Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.6

Alternate names: PR_MEMBER_NAME, PR_MEMBER_NAME_A, ptagMemberName, PR_MEMBER_NAME_W

2.855 PidTagMemberRights

Canonical name: PidTagMemberRights

Description: Contains the permissions for the specified user.

Property ID: 0x6673

Data type: PtypInteger32, 0x0003

Area: Access Control Properties

Defining reference: [\[MS-OXCPERM\]](#) section 2.2.7

Consuming references: [\[MS-OXCFOOLD\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_MEMBER_RIGHTS, ptagMemberRights

2.856 PidTagMessageAttachments

Canonical name: PidTagMessageAttachments

Description: Identifies all attachments to the current message.

Property ID: 0x0E13

Data type: PtypObject, 0x000D

Area: Message Attachment Properties

Defining reference:

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#)

Alternate names: PR_MESSAGE_ATTACHMENTS, ptagMessageAttachments

2.857 PidTagMessageCcMe

Canonical name: PidTagMessageCcMe

Description: Indicates that the receiving mailbox owner is a carbon copy (Cc) recipient of this e-mail message.

Property ID: 0x0058

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.18

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_CC_ME, ptagMessageCcMe

2.858 PidTagMessageClass

Canonical name: PidTagMessageClass

Description: Denotes the specific type of the Message object.

Property ID: 0x001A

Data type: **PtypString**, 0x001F

Area: Common Property set

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.3

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MESSAGE_CLASS, PR_MESSAGE_CLASS_A, ptagMessageClass, PR_MESSAGE_CLASS_W,
<http://schemas.microsoft.com/exchange/outlookmessageclass>
<http://schemas.microsoft.com/exchange/outlookmessageclass>

2.859 PidTagMessageCodepage

Canonical name: PidTagMessageCodepage

Description: Specifies the code page used to encode the **non-Unicode** string properties on this Message object.

Property ID: 0x3FFD

Data type: **PtypInteger32**, 0x0003

Area: Common

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.4

Consuming references: [\[MS-OXTNEF\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_MESSAGE_CODEPAGE

2.860 PidTagMessageDeliveryTime

Canonical name: PidTagMessageDeliveryTime

Description: Contains the posting date of the item or entry.

Property ID: 0x0E06

Data type: PtypTime, 0x0040

Area: Message Time Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.9

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORSS\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_MESSAGE_DELIVERY_TIME, urn:schemas:httpmail:datereceived

2.861 PidTagMessageEditorFormat

Canonical name: PidTagMessageEditorFormat

Description: Specifies the format that an e-mail editor can use for editing the message body (2).

Property ID: 0x5909

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.74

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MSG_EDITOR_FORMAT, ptagMsgEditorFormat

2.862 PidTagMessageFlags

Canonical name: PidTagMessageFlags

Description: Specifies the status of the Message object.

Property ID: 0x0E07

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.6

Consuming references: [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMMS\]](#)

Alternate names: PR_MESSAGE_FLAGS, ptagMessageFlags

2.863 PidTagMessageHandlingSystemCommonName

Canonical name: PidTagMessageHandlingSystemCommonName

Description: Contains the **common name** of a messaging user for use in a message header.

Property ID: 0x3A0F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.60

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MHS_COMMON_NAME, PR_MHS_COMMON_NAME_A, PR_MHS_COMMON_NAME_W, urn:schemas:contacts:dn

2.864 PidTagMessageLocaleId

Canonical name: PidTagMessageLocaleId

Description: Contains the Windows Locale ID of the end-user who created this message.

Property ID: 0x3FF1

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.5

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_LOCALE_ID

2.865 PidTagMessageRecipientMe

Canonical name: PidTagMessageRecipientMe

Description: Indicates that the receiving mailbox owner is a primary or a carbon copy (Cc) recipient of this e-mail message.

Property ID: 0x0059

Data type: PtypBoolean, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.19

Consuming Reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_RECIP_ME, ptagMessageRecipMe

2.866 PidTagMessageRecipients

Canonical name: PidTagMessageRecipients

Description: Identifies all of the recipients (1) of the current message.

Property ID: 0x0E12

Data type: PtypObject, 0x000D

Area: Address Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.47

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_RECIPIENTS, ptagMessageRecipients

2.867 PidTagMessageSize

Canonical name: PidTagMessageSize

Description: Contains the size, in bytes, consumed by the Message object on the server.

Property ID: 0x0E08

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.8

Consuming references: [\[MS-OXCSTOR\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_MESSAGE_SIZE, ptagMessageSize

2.868 PidTagMessageSizeExtended

Canonical name: PidTagMessageSizeExtended

Description: Specifies the 64-bit version of the **PidTagNormalMessageSize** property (section [2.881](#)).

Property ID: 0x0E08

Data type: PtypInteger64, 0x0014

Area: General Message Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.9

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_MESSAGE_SIZE_EXTENDED, ptagMessageSizeExtended

2.869 PidTagMessageStatus

Canonical name: PidTagMessageStatus

Description: Specifies the status of a message in a **contents table**.

Property ID: 0x0E17

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCFXICS\]](#)

Alternate names: PR_MSG_STATUS, ptagMsgStatus

2.870 PidTagMessageSubmissionId

Canonical name: PidTagMessageSubmissionId

Description: Contains a message identifier assigned by a message transfer agent.

Property ID: 0x0047

Data type: **PtypBinary**, 0x0102

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.75

Consuming references: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_SUBMISSION_ID, ptagMessageSubmissionId

2.871 PidTagMessageToMe

Canonical name: PidTagMessageToMe

Description: Indicates that the receiving mailbox owner is one of the primary recipients of this e-mail message.

Property ID: 0x0057

Data type: **PtypBoolean**, 0x000B

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.17

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_MESSAGE_TO_ME, ptagMessageToMe

2.872 PidTagMid

Canonical name: PidTagMid

Description: Contains a value that contains the MID of the message currently being synchronized.

Property ID: 0x674A

Data type: **PtypInteger64**, 0x0014

Area: ID Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.1

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: ptagMID, <http://schemas.microsoft.com/exchange/mid>

2.873 PidTagMiddleName

Canonical name: PidTagMiddleName

Description: Specifies the middle name(s) of the contact.

Property ID: 0x3A44

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.1.5

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MIDDLE_NAME, PR_MIDDLE_NAME_A, PR_MIDDLE_NAME_W, urn:schemas:contacts:middlename

2.874 PidTagMimeSkeleton

Canonical name: PidTagMimeSkeleton

Description: Contains the top-level MIME message headers, all MIME message body part headers, and body part content that is not already converted to Message object properties, including attachments.

Property ID: 0x64F0

Data type: PtypBinary, 0x0102

Area: MIME properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.28

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagMimeSkeleton

2.875 PidTagMobileTelephoneNumber

Canonical name: PidTagMobileTelephoneNumber

Description: Contains the mail user's cellular telephone number.

Property ID: 0x3A1C

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-EXOABK\]](#) section 2.2.4.45

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_MOBILE_TELEPHONE_NUMBER, PR_MOBILE_TELEPHONE_NUMBER_A, PR_MOBILE_TELEPHONE_NUMBER_W, urn:schemas:contacts:mobile

2.876 PidTagNativeBody

Canonical name: PidTagNativeBody

Description: Indicates the best available format for storing the message body (2).

Property ID: 0x1016

Data type: PtypInteger32, 0x0003

Area: BestBody

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.2

Consuming Reference: [\[MS-OXBBODY\]](#)

Alternate names: PR_NATIVE_BODY_INFO, ptagNativeBodyInfo

2.877 PidTagNextSendAcct

Canonical name: PidTagNextSendAcct

Description: Specifies the server that a client is currently attempting to use to send e-mail.

Property ID: 0x0E29

Data type: PtypString, 0x001F

Area: Outlook Application

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.61

Consuming Reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_NEXT_SEND_ACCT

2.878 PidTagNickname

Canonical name: PidTagNickname

Description: Contains the mail user's nickname.

Property ID: 0x3A4F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.3

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_NICKNAME, PR_NICKNAME_A, PR_NICKNAME_W, urn:schemas:contacts:nickname

2.879 PidTagNonReceiptNotificationRequested

Canonical Name: PidTagNonReceiptNotificationRequested

Description: Specifies whether the client sends a non-read receipt.

Property ID: 0x0C06

Data type: **PtypBoolean**, 0x000B

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.29

Alternate names: PR_NON_RECEIPT_NOTIFICATION_REQUESTED

2.880 PidTagNormalizedSubject

Canonical name: PidTagNormalizedSubject

Description: Contains the normalized subject of the message.

Property ID: 0x0E1D

Data type: **PtypString**, 0x001F

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.10

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_NORMALIZED_SUBJECT, PR_NORMALIZED_SUBJECT_A, ptagNormalizedSubject, PR_NORMALIZED_SUBJECT_W, urn:schemas:httpmail:normalizedsubject

2.881 PidTagNormalMessageSize

Canonical name: PidTagNormalMessageSize

Description: Contains the aggregate size of Message objects in a folder.

Property ID: 0x66B3

Data type: **PtypInteger32**, 0x0003

Area: Server

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.6

Consuming references: [\[MS-XWDEXT\]](#)

Alternate names: PR_NORMAL_MESSAGE_SIZE,
<http://schemas.microsoft.com/exchange/foldersize>

2.882 PidTagObjectType

Canonical name: PidTagObjectType

Description: Indicates the type of **Server object**.

Property ID: 0x0FFE

Data type: PtypInteger32, 0x0003

Area: Common

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.7

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOSRCH\]](#)

Alternate names: PR_OBJECT_TYPE, ptagObjectType

2.883 PidTagOfficeLocation

Canonical name: PidTagOfficeLocation

Description: Contains the mail user's office location.

Property ID: 0x3A19

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.8

Consuming references: [\[MS-NSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OFFICE_LOCATION, PR_OFFICE_LOCATION_A, PR_OFFICE_LOCATION_W,
urn:schemas:contacts:roomnumber

2.884 PidTagOfflineAddressBookContainerGuid

Canonical name: PidTagOfflineAddressBookContainerGuid

Description: A string formatted GUID that represents the **address list** container object.

Property ID: 0x6802

Data type: PtypString8, 0x001E

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.12.1

Alternate names: PR_OAB_CONTAINER_GUID, PR_OAB_CONTAINER_GUID_W

2.885 PidTagOfflineAddressBookDistinguishedName

Canonical name: PidTagOfflineAddressBookDistinguishedName

Description: Contains the distinguished name (DN) (1) of the address list that is contained in the OAB message.

Property ID: 0x6804

Data type: **PtypString8**, 0x001E

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.12.2

Alternate names: PR_OAB_DN, PR_OAB_DN_W

2.886 PidTagOfflineAddressBookMessageClass

Canonical name: PidTagOfflineAddressBookMessageClass

Description: Contains the message class for full OAB messages.

Property ID: 0x6803

Data type: **PtypInteger32**, 0x0003

Area: Offline Address Book Properties

Defining reference: [\[MS-OXPFOAB\]](#) section 2.2.2.1.1

Alternate names: PR_OAB_MESSAGE_CLASS

2.887 PidTagOfflineAddressBookName

Canonical name: PidTagOfflineAddressBookName

Description: Contains the display name of the address list.

Property ID: 0x6800

Data type: **PtypString**, 0x001F

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.12.3

Alternate names: PR_OAB_NAME, PR_OAB_NAME_W

2.888 PidTagOfflineAddressBookSequence

Canonical name: PidTagOfflineAddressBookSequence

Description: Contains the sequence number of the OAB.

Property ID: 0x6801

Data type: **PtypInteger32**, 0x0003

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.12.4

Alternate names: PR_OAB_SEQUENCE

2.889 PidTagOfflineAddressBookTruncatedProperties

Canonical name: PidTagOfflineAddressBookTruncatedProperties

Description: Contains a list of the property tags that have been truncated or limited by the server.

Property ID: 0x6805

Data type: **PtypMultipleInteger32**, 0x1003

Area: Offline Address Book Properties

Defining reference: [\[MS-OXOAB\]](#) section 2.9.2.2

Alternate names: PR_OAB_TRUNCATED_PROPS

2.890 PidTagOrdinalMost

Canonical name: PidTagOrdinalMost

Description: Contains a positive number whose negative is less than or equal to the value of the **PidLidTaskOrdinal** property (section [2.328](#)) of all of the Task objects in the folder.

Property ID: 0x36E2

Data type: **PtypInteger32**, 0x0003

Area: Tasks

Defining reference: [\[MS-OXOTASK\]](#) section 2.2.1.1

Alternate names: PR_ORDINAL_MOST

2.891 PidTagOrganizationalIdNumber

Canonical name: PidTagOrganizationalIdNumber

Description: Contains an identifier for the mail user used within the mail user's organization.

Property ID: 0x3A10

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.63

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_ORGANIZATIONAL_ID_NUMBER, PR_ORGANIZATIONAL_ID_NUMBER_A, PR_ORGANIZATIONAL_ID_NUMBER_W, urn:schemas:contacts:employeenumber

2.892 PidTagOriginalAuthorEntryId

Canonical name: PidTagOriginalAuthorEntryId

Description: Contains an address book EntryID structure ([\[MS-OXCDATA\]](#) section 2.2.5.2) and is defined in report messages to identify the user who sent the original message.

Property ID: 0x004C

Data type: PtypBinary, 0x0102

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.30

Alternate names: PR_ORIGINAL_AUTHOR_ENTRYID

2.893 PidTagOriginalAuthorName

Canonical name: PidTagOriginalAuthorName

Description: Contains the display name of the sender of the original message referenced by a report message.

Property ID: 0x004D

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.31

Alternate names: PR_ORIGINAL_AUTHOR_NAME_W

2.894 PidTagOriginalDeliveryTime

Canonical name: PidTagOriginalDeliveryTime

Description: Contains the delivery time, in UTC, from the original message.

Property ID: 0x0055

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.2

Alternate names: PR_ORIGINAL_DELIVERY_TIME, ptagOriginalDeliveryTime

2.895 PidTagOriginalDisplayBcc

Canonical name: PidTagOriginalDisplayBcc

Description: Contains the value of the **PidTagDisplayBcc** property (section [2.747](#)) from the original message.

Property ID: 0x0072

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.5

Alternate names: PR_ORIGINAL_DISPLAY_BCC, PR_ORIGINAL_DISPLAY_BCC_A, ptagOriginalDisplayBcc, PR_ORIGINAL_DISPLAY_BCC_W, <http://schemas.microsoft.com/exchange/originaldisplaybcc>

2.896 PidTagOriginalDisplayCc

Canonical name: PidTagOriginalDisplayCc

Description: Contains the value of the **PidTagDisplayCc** property (section [2.748](#)) from the original message.

Property ID: 0x0073

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.4

Alternate names: PR_ORIGINAL_DISPLAY_CC, PR_ORIGINAL_DISPLAY_CC_A, ptagOriginalDisplayCc, PR_ORIGINAL_DISPLAY_CC_W, <http://schemas.microsoft.com/exchange/originaldisplaycc>, http://schemas.microsoft.com/mapi/original_display_cc

2.897 PidTagOriginalDisplayTo

Canonical name: PidTagOriginalDisplayTo

Description: Contains the value of the **PidTagDisplayTo** property (section [2.751](#)) from the original message.

Property ID: 0x0074

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.3

Alternate names: PR_ORIGINAL_DISPLAY_TO, PR_ORIGINAL_DISPLAY_TO_A, ptagOriginalDisplayTo, PR_ORIGINAL_DISPLAY_TO_W, <http://schemas.microsoft.com/exchange/originaldisplayto>, http://schemas.microsoft.com/mapi/original_display_to

2.898 PidTagOriginalEntryId

Canonical name: PidTagOriginalEntryId

Description: Contains the original EntryID of an object.

Property ID: 0x3A12

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.9

Alternate names: PR_ORIGINAL_ENTRYID, ptagOriginalEntryId

2.899 PidTagOriginalMessageClass

Canonical name: PidTagOriginalMessageClass

Property ID: 0x004B

Data type: PtypString, 0x001F

Area: Secure Messaging Properties

Defining reference:

Consuming reference: [\[MS-OXTNEF\]](#)

Alternate names: PR_ORIG_MESSAGE_CLASS, PR_ORIG_MESSAGE_CLASS_A, PR_ORIG_MESSAGE_CLASS_W

2.900 PidTagOriginalMessageId

Canonical name: PidTagOriginalMessageId

Description:

Property ID: 0x1046

Data type: PtypString, 0x001F

Area: Mail

Defining reference:

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagOriginalInternetMessageID, OriginalMessageId

2.901 PidTagOriginalSenderAddressType

Canonical name: PidTagOriginalSenderAddressType

Description: Contains the value of the original message sender's **PidTagSenderAddressType** property (section [2.1068](#)).

Property ID: 0x0066

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.6

Alternate names: PR_ORIGINAL_SENDER_ADDRTYPE, PR_ORIGINAL_SENDER_ADDRTYPE_A, ptagOriginalSenderAddrType, PR_ORIGINAL_SENDER_ADDRTYPE_W

2.902 PidTagOriginalSenderEmailAddress

Canonical name: PidTagOriginalSenderEmailAddress

Description: Contains the value of the original message sender's **PidTagSenderEmailAddress** property (section [2.1069](#)).

Property ID: 0x0067

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.7

Alternate names: PR_ORIGINAL_SENDER_EMAIL_ADDRESS, PR_ORIGINAL_SENDER_EMAIL_ADDRESS_A, PR_ORIGINAL_SENDER_EMAIL_ADDRESS_W

2.903 PidTagOriginalSenderEntryId

Canonical name: PidTagOriginalSenderEntryId

Description: Contains an address book EntryID that is set on delivery report messages.

Property ID: 0x005B

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.8

Alternate names: PR_ORIGINAL_SENDER_ENTRYID, ptagOriginalSenderEntryId

2.904 PidTagOriginalSenderName

Canonical name: PidTagOriginalSenderName

Description: Contains the value of the original message sender's **PidTagSenderName** property (section [2.1072](#)), and is set on delivery report messages.

Property ID: 0x005A

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.9

Alternate names: PR_ORIGINAL_SENDER_NAME, PR_ORIGINAL_SENDER_NAME_A, ptagOriginalSenderName, PR_ORIGINAL_SENDER_NAME_W, <http://schemas.microsoft.com/exchange/originalsendername>

2.905 PidTagOriginalSenderSearchKey

Canonical name: PidTagOriginalSenderSearchKey

Description: Contains an address book search key set on the original e-mail message.

Property ID: 0x005C

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.10

Alternate names: PR_ORIGINAL_SENDER_SEARCH_KEY, ptagOriginalSenderSearchKey

2.906 PidTagOriginalSensitivity

Canonical name: PidTagOriginalSensitivity

Description: Contains the sensitivity value of the original e-mail message.

Property ID: 0x002E

Data type: PtypInteger32, 0x0003

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.22

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_ORIGINAL_SENSITIVITY, ptagOriginalSensitivity

2.907 PidTagOriginalSentRepresentingAddressType

Canonical name: PidTagOriginalSentRepresentingAddressType

Description: Contains the address type of the end user who is represented by the original e-mail message sender.

Property ID: 0x0068

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.11

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE, PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_A, ptagOriginalSentRepresentingAddrType, PR_ORIGINAL_SENT_REPRESENTING_ADDRTYPE_W

2.908 PidTagOriginalSentRepresentingEmailAddress

Canonical name: PidTagOriginalSentRepresentingEmailAddress

Description: Contains the e-mail address of the end user who is represented by the original e-mail message sender.

Property ID: 0x0069

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.12

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS,
PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_A,
PR_ORIGINAL_SENT_REPRESENTING_EMAIL_ADDRESS_W

2.909 PidTagOriginalSentRepresentingEntryId

Canonical name: PidTagOriginalSentRepresentingEntryId

Description: Identifies an address book EntryID that contains the entry identifier of the end user who is represented by the original message sender.

Property ID: 0x005E

Data type: **PtypBinary**, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.13

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_ENTRYID,
ptagOriginalSentRepresentingEntryId

2.910 PidTagOriginalSentRepresentingName

Canonical name: PidTagOriginalSentRepresentingName

Description: Contains the display name of the end user who is represented by the original e-mail message sender.

Property ID: 0x005D

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.14

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_NAME,
PR_ORIGINAL_SENT_REPRESENTING_NAME_A, ptagOriginalSentRepresentingName,
PR_ORIGINAL_SENT_REPRESENTING_NAME_W

2.911 PidTagOriginalSentRepresentingSearchKey

Canonical name: PidTagOriginalSentRepresentingSearchKey

Description: Identifies an address book search key that contains the SearchKey of the end user who is represented by the original message sender.

Property ID: 0x005F

Data type: PtypBinary, 0x0102

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.15

Alternate names: PR_ORIGINAL_SENT_REPRESENTING_SEARCH_KEY, ptagOriginalSentRepresentingSearchKey

2.912 PidTagOriginalSubject

Canonical name: PidTagOriginalSubject

Description: Specifies the subject of the original message.

Property ID: 0x0049

Data type: PtypString, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.16

Alternate names: PR_ORIGINAL_SUBJECT, PR_ORIGINAL_SUBJECT_A, ptagOriginalSubject, PR_ORIGINAL_SUBJECT_W, <http://schemas.microsoft.com/exchange/originalsubject>, http://schemas.microsoft.com/mapi/original_subject

2.913 PidTagOriginalSubmitTime

Canonical name: PidTagOriginalSubmitTime

Description: Specifies the original e-mail message's submission date and time, in UTC.

Property ID: 0x004E

Data type: PtypTime, 0x0040

Area: General Message Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.17

Alternate names: PR_ORIGINAL_SUBMIT_TIME, ptagOriginalSubmitTime, <http://schemas.microsoft.com/exchange/originaldate>, http://schemas.microsoft.com/mapi/original_submit_time

2.914 PidTagOriginatorDeliveryReportRequested

Canonical name: PidTagOriginatorDeliveryReportRequested

Description: Indicates whether an e-mail sender requests an e-mail **delivery receipt** from the messaging system.

Property ID: 0x0023

Data type: PtypBoolean, 0x000B

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.20

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_ORIGINATOR_DELIVERY_REPORT_REQUESTED,
<http://schemas.microsoft.com/exchange/deliveryreportrequested>

2.915 PidTagOriginatorNonDeliveryReportRequested

Canonical name: PidTagOriginatorNonDeliveryReportRequested

Description: Specifies whether an e-mail sender requests suppression of nondelivery receipts.

Property ID: 0x0C08

Data type: PtypBoolean, 0x000B

Area: MIME Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.21

Alternate names: PR_ORIGINATOR_NON_DELIVERY_REPORT_REQUESTED

2.916 PidTagOscSyncEnabled

Note All of the information in this section is subject to change because it applies to a preliminary implementation of the protocol or structure.

Canonical name: PidTagOscSyncEnabled

Description: Specifies whether contact synchronization with an external source is handled by the server.

Property ID: 0x7C24

Data type: PtypBoolean, 0x000B

Area: Contact Properties

Defining reference: [\[MS-OXOCNTC\]](#) section 2.2.1.9.8

Alternate names: PR_OSC_SYNC_ENABLEDONSERVER

2.917 PidTagOtherAddressCity

Canonical name: PidTagOtherAddressCity

Description: Contains the name of the mail user's other locality, such as the town or city.

Property ID: 0x3A5F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.33

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_CITY, PR_OTHER_ADDRESS_CITY_A, PR_OTHER_ADDRESS_CITY_W, urn:schemas:contacts:othercity

2.918 PidTagOtherAddressCountry

Canonical name: PidTagOtherAddressCountry

Description: Contains the name of the mail user's other country/region.

Property ID: 0x3A60

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.36

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_OTHER_ADDRESS_COUNTRY, PR_OTHER_ADDRESS_COUNTRY_A, PR_OTHER_ADDRESS_COUNTRY_W, urn:schemas:contacts:othercountry

2.919 PidTagOtherAddressPostalCode

Canonical name: PidTagOtherAddressPostalCode

Description: Contains the postal code for the mail user's other postal address.

Property ID: 0x3A61

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.35

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_POSTAL_CODE, PR_OTHER_ADDRESS_POSTAL_CODE_A, PR_OTHER_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:otherpostalcode

2.920 PidTagOtherAddressPostOfficeBox

Canonical name: PidTagOtherAddressPostOfficeBox

Description: Contains the number or identifier of the mail user's other post office box.

Property ID: 0x3A64

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.32

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#), [MS-XWDEXT]

Alternate names: PR_OTHER_ADDRESS_POST_OFFICE_BOX, PR_OTHER_ADDRESS_POST_OFFICE_BOX_A, PR_OTHER_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:otherpostofficebox

2.921 PidTagOtherAddressStateOrProvince

Canonical name: PidTagOtherAddressStateOrProvince

Description: Contains the name of the mail user's other state or province.

Property ID: 0x3A62

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.34

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_STATE_OR_PROVINCE, PR_OTHER_ADDRESS_STATE_OR_PROVINCE_A, PR_OTHER_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:otherstate

2.922 PidTagOtherAddressStreet

Canonical name: PidTagOtherAddressStreet

Description: Contains the mail user's other street address.

Property ID: 0x3A63

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.31

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_ADDRESS_STREET, PR_OTHER_ADDRESS_STREET_A, PR_OTHER_ADDRESS_STREET_W, urn:schemas:contacts:otherstreet

2.923 PidTagOtherTelephoneNumber

Canonical name: PidTagOtherTelephoneNumber

Description: Contains an alternate telephone number for the mail user.

Property ID: 0x3A1F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.48

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_OTHER_TELEPHONE_NUMBER, PR_OTHER_TELEPHONE_NUMBER_A, PR_OTHER_TELEPHONE_NUMBER_W, urn:schemas:contacts:otherTelephone

2.924 PidTagOutOfOfficeState

Canonical name: PidTagOutOfOfficeState

Description: Indicates whether the user is **OOF**.

Property ID: 0x661D

Data type: PtypBoolean, 0x000B

Area: Message Store Properties

Defining reference:

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_OOF_STATE, ptagOOFState

2.925 PidTagOwnerAppointmentId

Canonical name: PidTagOwnerAppointmentId

Description: Specifies a quasi-unique value among all of the Calendar objects in a user's mailbox.

Property ID: 0x0062

Data type: PtypInteger32, 0x0003

Area: Appointment

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.29

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

Alternate names: PR_OWNER_APPT_ID, http://schemas.microsoft.com/mapi/owner_appt_id

2.926 PidTagPagerTelephoneNumber

Canonical name: PidTagPagerTelephoneNumber

Description: Contains the mail user's pager telephone number.

Property ID: 0x3A21

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.49

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PAGER_TELEPHONE_NUMBER, PR_PAGER_TELEPHONE_NUMBER_A, PR_PAGER_TELEPHONE_NUMBER_W, urn:schemas:contacts:pager

2.927 PidTagParentEntryId

Canonical name: PidTagParentEntryId

Description: Contains the EntryID of the folder where messages reside.

Property ID: 0x0E09

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.6

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPFOAB\]](#)

Alternate names: PR_PARENT_ENTRYID, ptagParentEntryId

2.928 PidTagParentFolderId

Canonical name: PidTagParentFolderId

Description: Contains a value that contains the Folder ID (FID), as specified in [\[MS-OXCDATA\]](#) section 2.2.1.1, that identifies the parent folder of the messaging object being synchronized.

Property ID: 0x6749

Data type: PtypInteger64, 0x0014

Area: ID Properties

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.4

Alternate names: ptagParentFID

2.929 PidTagParentKey

Canonical name: PidTagParentKey

Description: Contains the search key that is used to correlate the original message and the reports about the original message.

Property ID: 0x0025

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.18

Alternate names: PR_PARENT_KEY, ptagParentKey

2.930 PidTagParentSourceKey

Canonical name: PidTagParentSourceKey

Description: Contains a value on a folder that contains the **PidTagSourceKey** property (section [2.1088](#)) of the parent folder.

Property ID: 0x65E1

Data type: **PtypBinary**, 0x0102

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.6

Alternate names: PR_PARENT_SOURCE_KEY

2.931 PidTagPersonalHomePage

Canonical name: PidTagPersonalHomePage

Description: Contains the URL of the mail user's personal home page.

Property ID: 0x3A50

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.77

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PERSONAL_HOME_PAGE, PR_PERSONAL_HOME_PAGE_A, PR_PERSONAL_HOME_PAGE_W, urn:schemas:contacts:personalHomePage

2.932 PidTagPolicyTag

Canonical name: PidTagPolicyTag

Description: Specifies the GUID of a **retention tag**.

Property ID: 0x3019

Data type: **PtypBinary**, 0x0102

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.2

Alternate names: PR_POLICY_TAG, ptagPolicyTag

2.933 PidTagPostalAddress

Canonical name: PidTagPostalAddress

Description: Contains the mail user's postal address.

Property ID: 0x3A15

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.18

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POSTAL_ADDRESS, PR_POSTAL_ADDRESS_A, PR_POSTAL_ADDRESS_W, urn:schemas:contacts:mailingpostaladdress

2.934 PidTagPostalCode

Canonical name: PidTagPostalCode

Description: Contains the postal code for the mail user's postal address.

Property ID: 0x3A2A

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.23

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POSTAL_CODE, PR_POSTAL_CODE_A, PR_POSTAL_CODE_W, PR_BUSINESS_ADDRESS_POSTAL_CODE, PR_BUSINESS_ADDRESS_POSTAL_CODE_A, PR_BUSINESS_ADDRESS_POSTAL_CODE_W, urn:schemas:contacts:mailingpostalcode

2.935 PidTagPostOfficeBox

Canonical name: PidTagPostOfficeBox

Description: Contains the number or identifier of the mail user's post office box.

Property ID: 0x3A2B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.20

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_POST_OFFICE_BOX, PR_POST_OFFICE_BOX_A, PR_POST_OFFICE_BOX_W, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_A, PR_BUSINESS_ADDRESS_POST_OFFICE_BOX_W, urn:schemas:contacts:mailingpostofficebox

2.936 PidTagPredecessorChangeList

Canonical name: PidTagPredecessorChangeList

Description: Contains a value that contains a serialized representation of a **PredecessorChangeList** structure.

Property ID: 0x65E3

Data type: **PtypBinary**, 0x0102

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.8

Alternate names: PR_PREDECESSOR_CHANGE_LIST

2.937 PidTagPrimaryFaxNumber

Canonical name: PidTagPrimaryFaxNumber

Description: Contains the telephone number of the mail user's primary fax machine.

Property ID: 0x3A23

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.50

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PRIMARY_FAX_NUMBER, PR_PRIMARY_FAX_NUMBER_A, PR_PRIMARY_FAX_NUMBER_W, urn:schemas:contacts:otherfax

2.938 PidTagPrimarySendAccount

Canonical name: PidTagPrimarySendAccount

Description: Specifies the first server that a client is to use to send the e-mail with.

Property ID: 0x0E28

Data type: **PtypString**, 0x001F

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.60

Alternate names: PR_PRIMARY_SEND_ACCT

2.939 PidTagPrimaryTelephoneNumber

Canonical name: PidTagPrimaryTelephoneNumber

Description: Contains the mail user's primary telephone number.

Property ID: 0x3A1A

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.37

Consuming references: [\[MS-OXVCARD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-NSPI\]](#)

Alternate names: PR_PRIMARY_TELEPHONE_NUMBER, PR_PRIMARY_TELEPHONE_NUMBER_A, PR_PRIMARY_TELEPHONE_NUMBER_W

2.940 PidTagPriority

Canonical name: PidTagPriority

Description: Indicates the client's request for the priority with which the message is to be sent by the messaging system.

Property ID: 0x0026

Data type: **PtypInteger32**, 0x0003

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.12

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOJRN\]](#), [\[MS-XWDMail\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

2.941 PidTagProcessed

Canonical name: PidTagProcessed

Description: Indicates whether a client has already processed a received task communication.

Property ID: 0x7D01

Data type: **PtypBoolean**, 0x000B

Area: Calendar

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.5.7

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#)

Alternate names: PR_PROCESSED

2.942 PidTagProfession

Canonical name: PidTagProfession

Description: Contains the name of the mail user's line of business.

Property ID: 0x3A46

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.70

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_PROFESSION, PR_PROFESSION_A, PR_PROFESSION_W,
urn:schemas:contacts:profession

2.943 PidTagProhibitReceiveQuota

Canonical name: PidTagProhibitReceiveQuota

Description: Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before no further e-mail will be delivered to their mailbox.

Property ID: 0x666A

Data type: PtypInteger32, 0x0003

Area: Exchange Administrative

Defining reference:

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_PROHIBIT_RECEIVE_QUOTA, ptagProhibitReceiveQuota

2.944 PidTagProhibitSendQuota

Canonical name: PidTagProhibitSendQuota

Description: Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before the user can no longer send any more e-mail.

Property ID: 0x666E

Data type: PtypInteger32, 0x0003

Area: ExchangeAdministrative

Defining reference:

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: PR_PROHIBIT_SEND_QUOTA, ptagProhibitSendQuota

2.945 PidTagProviderSubmitTime

Canonical name: PidTagProviderSubmitTime

Description:

Property ID: 0x0048

Data type: PtypTime, 0x0040

Area: E-mail

Defining reference:

Consuming reference: [\[MS-OXOMSG\]](#)

Alternate names: PR_PROVIDER_SUBMIT_TIME

2.946 PidTagPublicFolderAdministrativeDescription

Canonical name: PidTagPublicFolderAdministrativeDescription

Description: Contains a text description of a public folder.

Property ID: 0x671C

Data type: PtypString, 0x001F

Area: Folder Properties

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.4

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/adminfolderdescription>

2.947 PidTagPublicFolderProxy

Canonical name: PidTagPublicFolderProxy

Description: Contains the **base64 encoding** of the Object GUID for a mail-enabled public folder.

Property ID: 0x671D

Data type: PtypBinary, 0x0102

Area: Folder Properties

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.5

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: <http://schemas.microsoft.com/exchange/folderproxy>

2.948 PidTagPurportedSenderDomain

Canonical name: PidTagPurportedSenderDomain

Description: Contains the domain responsible for transmitting the current message.

Property ID: 0x4083

Data type: PtypString, 0x001F

Area: TransportEnvelope

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.43

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_PURPORTED_SENDER_DOMAIN

2.949 PidTagRadioTelephoneNumber

Canonical name: PidTagRadioTelephoneNumber

Description: Contains the mail user's radio telephone number.

Property ID: 0x3A1D

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.46

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_RADIO_TELEPHONE_NUMBER, PR_RADIO_TELEPHONE_NUMBER_A, PR_RADIO_TELEPHONE_NUMBER_W

2.950 PidTagRead

Canonical name: PidTagRead

Description: Indicates whether a message has been read.

Property ID: 0x0E69

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable Property set

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.6.16

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_READ, ptagRead, urn:schemas:httpmail:read

2.951 PidTagReadReceiptAddressType

Canonical name: PidTagReadReceiptAddressType

Description: Contains the address type of the end user to whom a **read receipt** is directed.

Property ID: 0x4029

Data type: PtypString, 0x001F

Area: Transport Envelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.24

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptAddrType, ReadReceiptAddrType

2.952 PidTagReadReceiptEmailAddress

Canonical name: PidTagReadReceiptEmailAddress

Description: Contains the e-mail address of the end user to whom a read receipt is directed.

Property ID: 0x402A

Data type: **PtypString**, 0x001F

Area: Transport Envelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.25

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

2.953 PidTagReadReceiptEntryId

Canonical name: PidTagReadReceiptEntryId

Description: Contains an address book EntryID.

Property ID: 0x0046

Data type: **PtypBinary**, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.26

Alternate names: PR_READ_RECEIPT_ENTRYID, ptagReadReceiptEntryId

2.954 PidTagReadReceiptName

Canonical name: PidTagReadReceiptName

Description: Contains the display name for the end user to whom a read receipt is directed.

Property ID: 0x402B

Data type: **PtypString**, 0x001F

Area: Transport Envelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.27

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagReadReceiptDisplayName, ReadReceiptDisplayName

2.955 PidTagReadReceiptRequested

Canonical name: PidTagReadReceiptRequested

Description: Specifies whether the e-mail sender requests a read receipt from all recipients (1) when this e-mail message is read or opened.

Property ID: 0x0029

Data type: PtypBoolean, 0x000B

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.28

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#)

Alternate names: PR_READ_RECEIPT_REQUESTED, ptagReadReceiptRequested, <http://schemas.microsoft.com/exchange/readreceiptrequested>

2.956 PidTagReadReceiptSearchKey

Canonical name: PidTagReadReceiptSearchKey

Description: Contains an address book search key.

Property ID: 0x0053

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.28

Alternate names: PR_READ_RECEIPT_SEARCH_KEY, ptagReadReceiptSearchKey

2.957 PidTagReceivedByAddressType

Canonical name: PidTagReceivedByAddressType

Description: Contains the e-mail message receiver's e-mail address type.

Property ID: 0x0075

Data type: PtypString, 0x001F

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.34

Alternate names: PR_RECEIVED_BY_ADDRTYPE, PR_RECEIVED_BY_ADDRTYPE_A, ptagReceivedByAddrType, PR_RECEIVED_BY_ADDRTYPE_W

2.958 PidTagReceivedByEmailAddress

Canonical name: PidTagReceivedByEmailAddress

Description: Contains the e-mail message receiver's e-mail address.

Property ID: 0x0076

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.35

Alternate names: PR_RECEIVED_BY_EMAIL_ADDRESS, PR_RECEIVED_BY_EMAIL_ADDRESS_A, PR_RECEIVED_BY_EMAIL_ADDRESS_W

2.959 PidTagReceivedByEntryId

Canonical name: PidTagReceivedByEntryId

Description: Contains the address book EntryID of the mailbox receiving the E-mail object.

Property ID: 0x003F

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.36

Alternate names: PR_RECEIVED_BY_ENTRYID

2.960 PidTagReceivedByName

Canonical name: PidTagReceivedByName

Description: Contains the e-mail message receiver's display name.

Property ID: 0x0040

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.37

Alternate names: PR_RECEIVED_BY_NAME, PR_RECEIVED_BY_NAME_A, PR_RECEIVED_BY_NAME_W

2.961 PidTagReceivedBySearchKey

Canonical name: PidTagReceivedBySearchKey

Description: Identifies an address book search key that contains a binary-comparable key that is used to identify correlated objects for a search.

Property ID: 0x0051

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.38

Alternate names: PR_RECEIVED_BY_SEARCH_KEY

2.962 PidTagReceivedRepresentingAddressType

Canonical name: PidTagReceivedRepresentingAddressType

Description: Contains the e-mail address type for the end user represented by the receiving mailbox owner.

Property ID: 0x0077

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.23

Alternate names: PR_RCVD_REPRESENTING_ADDRTYPE, PR_RCVD_REPRESENTING_ADDRTYPE_A, ptagRcvdRepresentingAddrType, PR_RCVD_REPRESENTING_ADDRTYPE_W

2.963 PidTagReceivedRepresentingEmailAddress

Canonical name: PidTagReceivedRepresentingEmailAddress

Description: Contains the e-mail address for the end user represented by the receiving mailbox owner.

Property ID: 0x0078

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.24

Alternate names: PR_RCVD_REPRESENTING_EMAIL_ADDRESS, PR_RCVD_REPRESENTING_EMAIL_ADDRESS_A, PR_RCVD_REPRESENTING_EMAIL_ADDRESS_W

2.964 PidTagReceivedRepresentingEntryId

Canonical name: PidTagReceivedRepresentingEntryId

Description: Contains an address book EntryID that identifies the end user represented by the receiving mailbox owner.

Property ID: 0x0043

Data type: **PtypBinary**, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.25

Alternate names: PR_RCVD_REPRESENTING_ENTRYID, ptagRcvdRepresentingEntryId

2.965 PidTagReceivedRepresentingName

Canonical name: PidTagReceivedRepresentingName

Description: Contains the display name for the end user represented by the receiving mailbox owner.

Property ID: 0x0044

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.26

Alternate names: PR_RCVD_REPRESENTING_NAME, PR_RCVD_REPRESENTING_NAME_A, ptagRcvdRepresentingName, PR_RCVD_REPRESENTING_NAME_W

2.966 PidTagReceivedRepresentingSearchKey

Canonical name: PidTagReceivedRepresentingSearchKey

Description: Identifies an address book search key that contains a binary-comparable key of the end user represented by the receiving mailbox owner.

Property ID: 0x0052

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.27

Alternate names: PR_RCVD_REPRESENTING_SEARCH_KEY, ptagRcvdRepresentingSearchKey

2.967 PidTagRecipientDisplayName

Canonical name: PidTagRecipientDisplayName

Description:

Property ID: 0x5FF6

Data type: PtypString, 0x001F

Area: TransportRecipient

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_DISPLAY_NAME, PR_RECIPIENT_DISPLAY_NAME_W

2.968 PidTagRecipientEntryId

Canonical name: PidTagRecipientEntryId

Description:

Property ID: 0x5FF7

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_ENTRYID, ptagRecipientEntryId

2.969 PidTagRecipientFlags

Canonical name: PidTagRecipientFlags

Description: Specifies a bit field that describes the recipient (1) status.

Property ID: 0x5FFD

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_FLAGS

2.970 PidTagRecipientOrder

Canonical name: PidTagRecipientOrder

Description: Specifies the location of the current recipient (1) in the **recipient table**.

Property ID: 0x5FDF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.40

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_ORDER, ptagRecipientOrder

2.971 PidTagRecipientProposed

Canonical name: PidTagRecipientProposed

Description: Indicates that the attendee proposed a new date and/or time.

Property ID: 0x5FE1

Data type: PtypBoolean, 0x000B

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.4

Alternate names: PR_RECIPIENT_PROPOSED, ptagRecipientProposed

2.972 PidTagRecipientProposedEndTime

Canonical name: PidTagRecipientProposedEndTime

Description: Indicates the meeting end time requested by the attendee in a counter proposal.

Property ID: 0x5FE4

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.6

Alternate names: PR_RECIPIENT_PROPOSEDENDTIME, ptagRecipientProposedEndTime

2.973 PidTagRecipientProposedStartTime

Canonical name: PidTagRecipientProposedStartTime

Description: Indicates the meeting start time requested by the attendee in a counter proposal.

Property ID: 0x5FE3

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.5

Alternate names: PR_RECIPIENT_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

2.974 PidTagRecipientReassignmentProhibited

Canonical name: PidTagRecipientReassignmentProhibited

Description: Specifies whether adding additional or different recipients (1) is prohibited for the e-mail message when forwarding the e-mail message.

Property ID: 0x002B

Data type: PtypBoolean, 0x000B

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.39

Alternate names: PR_RECIPIENT_REASSIGNMENT_PROHIBITED, ptagRecipientReassignmentProhibited

2.975 PidTagRecipientResourceState

Canonical name: PidTagRecipientResourceState

Description:

Property ID: 0x5FDE

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_RECIPIENT_RESOURCESTATE

2.976 PidTagRecipientTrackStatus

Canonical name: PidTagRecipientTrackStatus

Description: Indicates the response status that is returned by the attendee.

Property ID: 0x5FFF

Data type: PtypInteger32, 0x0003

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.2

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_RECIPIENT_TRACKSTATUS, ptagRecipientTrackStatus

2.977 PidTagRecipientTrackStatusTime

Canonical name: PidTagRecipientTrackStatusTime

Description: Indicates the date and time at which the attendee responded.

Property ID: 0x5FFB

Data type: PtypTime, 0x0040

Area: TransportRecipient

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.4.10.3

Consuming reference: [\[MS-OXCICAL\]](#)

Alternate names: PR_RECIPIENT_TRACKSTATUS_TIME, ptagRecipientTrackStatusTime

2.978 PidTagRecipientType

Canonical name: PidTagRecipientType

Description: Represents the recipient (1) type of a recipient (1) on the message.

Property ID: 0x0C15

Data type: PtypInteger32, 0x0003

Area: MapiRecipient

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.1

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_RECIPIENT_TYPE, ptagRecipientType

2.979 PidTagRecordKey

Canonical name: PidTagRecordKey

Description: Contains a unique binary-comparable identifier for a specific object.

Property ID: 0x0FF9

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.8

Consuming references: [\[MS-OXCFCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#)

Alternate names: PR_RECORD_KEY, ptagRecordKey

2.980 PidTagReferredByName

Canonical name: PidTagReferredByName

Description: Contains the name of the mail user's referral.

Property ID: 0x3A47

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.71

Consuming reference: [\[MS-OXOCNTC\]](#)

Alternate names: PR_REFERRED_BY_NAME, PR_REFERRED_BY_NAME_A, PR_REFERRED_BY_NAME_W

2.981 PidTagRemindersOnlineEntryId

Canonical name: PidTagRemindersOnlineEntryId

Description: Contains an EntryID for the Reminders folder.

Property ID: 0x36D5

Data type: PtypBinary, 0x0102

Area: MapiContainer

Defining reference: [\[MS-OXOSFLD\]](#) section 2.2.3

Alternate names: PR_REM_ONLINE_ENTRYID, ptagRemOnlineEntryId

2.982 PidTagRenderingPosition

Canonical name: PidTagRenderingPosition

Description: Represents an offset, in rendered characters, to use when rendering an attachment within the main message text.

Property ID: 0x370B

Data type: PtypInteger32, 0x0003

Area: MapiAttachment

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.16

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), , [\[MS-XWDEXT\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_RENDERING_POSITION, ptagRenderingPosition

2.983 PidTagReplyRecipientEntries

Canonical name: PidTagReplyRecipientEntries

Description: Identifies a **FlatEntryList** structure ([\[MS-OXCADATA\]](#) section 2.3.3) of address book EntryIDs for recipients (1) that are to receive a reply.

Property ID: 0x004F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.40

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_REPLY_RECIPIENT_ENTRIES, ptagReplyRecipientEntries, <http://schemas.microsoft.com/exchange/reply-to-base64>

2.984 PidTagReplyRecipientNames

Canonical name: PidTagReplyRecipientNames

Description: Contains a list of display names for recipients (1) that are to receive a reply.

Property ID: 0x0050

Data type: PtypString, 0x001F

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.41

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_REPLY_RECIPIENT_NAMES, PR_REPLY_RECIPIENT_NAMES_A, ptagReplyRecipientNames, PR_REPLY_RECIPIENT_NAMES_W

2.985 PidTagReplyRequested

Canonical name: PidTagReplyRequested

Description: Indicates whether a reply is requested to a Message object.

Property ID: 0x0C17

Data type: PtypBoolean, 0x000B

Area: MapiRecipient

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.42

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_REPLY_REQUESTED, ptagReplyRequested

2.986 PidTagReplyTemplateId

Canonical name: PidTagReplyTemplateId

Description: Contains the value of the GUID that points to a Reply template.

Property ID: 0x65C2

Data type: PtypBinary, 0x0102

Area: Rules

Defining reference: [\[MS-OXORULE\]](#) section 2.2.9.2

Alternate names: PR_REPLY_TEMPLATE_ID, ptagReplyTemplateId

2.987 PidTagReplyTime

Canonical name: PidTagReplyTime

Description: Specifies the time, in UTC, that the sender has designated for an associated work item to be due.

Property ID: 0x0030

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.3.1

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

Alternate names: PR_REPLY_TIME, urn:schemas:httpmail:reply-by, <http://schemas.microsoft.com/exchange/reply-by-iso>

2.988 PidTagReportDisposition

Canonical name: PidTagReportDisposition

Description: Contains a string indicating whether the original message was displayed to the user or deleted (report messages only).

Property ID: 0x0080

Data type: **PtypString**, 0x001F

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.32

Alternate names: PR_REPORT_DISPOSITION_W

2.989 PidTagReportDispositionMode

Canonical name: PidTagReportDispositionMode

Description: Contains a description of the action that a client has performed on behalf of a user (report messages only).

Property ID: 0x0081

Data type: **PtypString**, 0x001F

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.33

Alternate names: PR_REPORT_DISPOSITION_MODE_W

2.990 PidTagReportEntryId

Canonical name: PidTagReportEntryId

Description: Specifies whether a reply to the e-mail message is requested by the e-mail message's sender.

Property ID: 0x0045

Data type: **PtypBinary**, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.42

Alternate names: PR_REPORT_ENTRYID, ptagReportEntryId

2.991 PidTagReportName

Canonical name: PidTagReportName

Description: Contains the display name for the entity (usually a server agent) that generated the report message.

Property ID: 0x003A

Data type: **PtypString**, 0x001F

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.20

Alternate names: PR_REPORT_NAME, PR_REPORT_NAME_A, PR_REPORT_NAME_W

2.992 PidTagReportSearchKey

Canonical name: PidTagReportSearchKey

Description: Contains an address book search key representing the entity (usually a server agent) that generated the report message.

Property ID: 0x0054

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.21

Alternate names: PR_REPORT_SEARCH_KEY, ptagReportSearchKey

2.993 PidTagReportTag

Canonical name: PidTagReportTag

Description: Contains the data that is used to correlate the report and the original message.

Property ID: 0x0031

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.22

Alternate names: PR_REPORT_TAG, ptagReportTag

2.994 PidTagReportText

Canonical name: PidTagReportText

Description: Contains the optional text for a report message.

Property ID: 0x1001

Data type: PtypString, 0x001F

Area: MapiMessage

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.2.23

Alternate names: PR_REPORT_TEXT, PR_REPORT_TEXT_A, ptagReportText, PR_REPORT_TEXT_W

2.995 PidTagReportTime

Canonical name: PidTagReportTime

Description: Indicates the last time that the contact list that is controlled by the **PidTagJunkIncludeContacts** property (section [2.830](#)) was updated.

Property ID: 0x0032

Data type: **PtypTime**, 0x0040

Area: MapiEnvelope Property set

Defining reference: [\[MS-OXCSPAM\]](#) section 2.2.2.6

Alternate names: PR_REPORT_TIME, ptagReportTime, <http://schemas.microsoft.com/exchange/reporttime>

2.996 PidTagResolveMethod

Canonical name: PidTagResolveMethod

Description: Specifies how to resolve any conflicts with the message.

Property ID: 0x3FE7

Data type: **PtypInteger32**, 0x0003

Area: MapiStatus

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.4.1

Alternate names: PR_RESOLVE_METHOD, ptagResolveMethod

2.997 PidTagResponseRequested

Canonical name: PidTagResponseRequested

Description: Indicates whether a response is requested to a Message object.

Property ID: 0x0063

Data type: **PtypBoolean**, 0x000B

Area: MapiEnvelope Property set

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.43

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_RESPONSE_REQUESTED, urn:schemas:calendar:responserequested, http://schemas.microsoft.com/mapi/response_requested

2.998 PidTagResponsibility

Canonical name: PidTagResponsibility

Description: Specifies whether another mail agent has ensured that the message will be delivered.

Property ID: 0x0E0F

Data type: PtypBoolean, 0x000B

Area: MapiNonTransmittable

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.37

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_RESPONSIBILITY, ptagResponsibility

2.999 PidTagRetentionDate

Canonical name: PidTagRetentionDate

Description: Specifies the date, in UTC, after which a Message object is expired by the server.

Property ID: 0x301C

Data type: PtypTime, 0x0040

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.5

Alternate names: PR_RETENTION_DATE, ptagRetentionDate

2.1000 PidTagRetentionFlags

Canonical name: PidTagRetentionFlags

Description: Contains flags that specify the status or nature of an item's retention tag or archive tag.

Property ID: 0x301D

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.6

Alternate names: PR_RETENTION_FLAGS, ptagRetentionFlags

2.1001 PidTagRetentionPeriod

Canonical name: PidTagRetentionPeriod

Description: Specifies the number of days that a Message object can remain unarchived.

Property ID: 0x301A

Data type: PtypInteger32, 0x0003

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.3

Alternate names: PR_RETENTION_PERIOD, ptagRetentionPeriod

2.1002 PidTagRights

Canonical name: PidTagRights

Description: Specifies a user's folder permissions.

Property ID: 0x6639

Data type: **PtypInteger32**, 0x0003

Area: ExchangeFolder

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.6

Consuming reference: [\[MS-OXCPERM\]](#)

Alternate names: PR_RIGHTS, ptagRights

2.1003 PidTagRoamingDatatypes

Canonical name: PidTagRoamingDatatypes

Description: Contains a bitmask that indicates which stream properties exist on the message.

Property ID: 0x7C06

Data type: **PtypInteger32**, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.2.1

Alternate names: PR_ROAMING_DATATYPES

2.1004 PidTagRoamingDictionary

Canonical name: PidTagRoamingDictionary

Description: Contains a dictionary stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.1.

Property ID: 0x7C07

Data type: **PtypBinary**, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.2.2

Alternate names: PR_ROAMING_DICTIONARY

2.1005 PidTagRoamingXmlStream

Canonical name: PidTagRoamingXmlStream

Description: Contains an XML stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.2.

Property ID: 0x7C08

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.2.3

Alternate names: PR_ROAMING_XMLSTREAM

2.1006 PidTagRowid

Canonical name: PidTagRowid

Description: Contains a unique identifier for a recipient (2) in a message's recipient table.

Property ID: 0x3000

Data type: PtypInteger32, 0x0003

Area: MapiCommon

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.38

Consuming reference: [\[MS-OXCFXICS\]](#)

Alternate names: PR_ROWID, ptagRowId

2.1007 PidTagRowType

Canonical name: PidTagRowType

Description: Identifies the type of the row.

Property ID: 0x0FF5

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [\[MS-OXCTABL\]](#) section 2.2.1.3

Alternate names: PR_ROW_TYPE, ptagRowType

2.1008 PidTagRtfCompressed

Canonical name: PidTagRtfCompressed

Description: Contains message body (2) text in compressed **RTF** format.

Property ID: 0x1009

Data type: PtypBinary, 0x0102

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.4

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFCP\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEEF\]](#)

Alternate names: PR_RTF_COMPRESSED, ptagRTFCompressed

2.1009 PidTagRtfInSync

Canonical name: PidTagRtfInSync

Description: Indicates whether the **PidTagBody** property (section [2.692](#)) and the **PidTagRtfCompressed** property (section [2.1008](#)) contain the same text (ignoring formatting).

Property ID: 0x0E1F

Data type: PtypBoolean, 0x000B

Area: E-mail

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.48.5

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

Alternate names: PR_RTF_IN_SYNC, ptagRTFInSync

2.1010 PidTagRuleActionNumber

Canonical name: PidTagRuleActionNumber

Description: Contains the index of a rule action that failed.

Property ID: 0x6650

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.7.4

Alternate names: PR_RULE_ACTION_NUMBER, ptagRuleActionNumber

2.1011 PidTagRuleActions

Canonical name: PidTagRuleActions

Description: Contains the set of actions associated with the rule.

Property ID: 0x6680

Data type: PtypRuleAction, 0x00FE

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.10

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_ACTIONS, ptagRuleActions

2.1012 PidTagRuleActionType

Canonical name: PidTagRuleActionType

Description: Contains the **ActionType** field ([\[MS-OXORULE\]](#) section 2.2.5.1.1) of a rule that failed.

Property ID: 0x6649

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.7.3

Alternate names: PR_RULE_ACTION_TYPE, ptagRuleActionType

2.1013 PidTagRuleCondition

Canonical name: PidTagRuleCondition

Description: Defines the conditions under which a rule's action is to be executed.

Property ID: 0x6679

Data type: PtypRestriction, 0x00FD

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.9

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_CONDITION, ptagRuleCondition

2.1014 PidTagRuleError

Canonical name: PidTagRuleError

Description: Contains the error code that indicates the cause of an error encountered during the execution of the rule.

Property ID: 0x6648

Data type: PtypInteger32, 0x0003

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.7.2

Alternate names: PR_RULE_ERROR, ptagRuleError

2.1015 PidTagRuleFolderEntryId

Canonical name: PidTagRuleFolderEntryId

Description: Contains the EntryID of the folder where the rule that triggered the generation of a DAM is stored.

Property ID: 0x6651

Data type: PtypBinary, 0x0102

Area: ExchangeMessageReadOnly

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.5

Alternate names: PR_RULE_FOLDER_ENTRYID, ptagRuleFolderEntryId

2.1016 PidTagRuleId

Canonical name: PidTagRuleId

Description: Specifies a unique identifier that is generated by the messaging server for each rule when the rule is first created.

Property ID: 0x6674

Data type: PtypInteger64, 0x0014

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.1

Alternate names: PR_RULE_ID, ptagRuleId

2.1017 PidTagRuleIds

Canonical name: PidTagRuleIds

Description: Contains a buffer that is obtained by concatenating the **PidTagRuleId** property (section [2.1016](#)) values from all of the rules contributing actions that are contained in the **PidTagClientActions** property (section [2.708](#)).

Property ID: 0x6675

Data type: PtypBinary, 0x0102

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.6.7

Alternate names: PR_RULE_IDS, ptagRuleIds

2.1018 PidTagRuleLevel

Canonical name: PidTagRuleLevel

Description: Contains 0x00000000. This property is not used.

Property ID: 0x6683

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.6

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_LEVEL, ptagRuleLevel

2.1019 PidTagRuleMessageLevel

Canonical name: PidTagRuleMessageLevel

Description: Contains 0x00000000. Set on the FAI message.

Property ID: 0x65ED

Data type: **PtypInteger32**, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.6

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_LEVEL, ptagRuleMsgLevel

2.1020 PidTagRuleMessageName

Canonical name: PidTagRuleMessageName

Description: Specifies the name of the rule. Set on the FAI message.

Property ID: 0x65EC

Data type: **PtypString**, 0x001F

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.1

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: ptagRuleMsgName

2.1021 PidTagRuleMessageProvider

Canonical name: PidTagRuleMessageProvider

Description: Identifies the client application that owns the rule. Set on the FAI message.

Property ID: 0x65EB

Data type: **PtypString**, 0x001F

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.7

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: ptagRuleMsgProvider

2.1022 PidTagRuleMessageProviderData

Canonical name: PidTagRuleMessageProviderData

Description: Contains opaque data set by the client for the exclusive use of the client. Set on the FAI message.

Property ID: 0x65EE

Data type: PtypBinary, 0x0102

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.8

Alternate names: PR_RULE_MSG_PROVIDER_DATA, ptagRuleMsgProviderData

2.1023 PidTagRuleMessageSequence

Canonical name: PidTagRuleMessageSequence

Description: Contains a value used to determine the order in which rules are evaluated and executed. Set on the FAI message.

Property ID: 0x65F3

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.3

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_SEQUENCE, ptagRuleMsgSequence

2.1024 PidTagRuleMessageState

Canonical name: PidTagRuleMessageState

Description: Contains flags that specify the state of the rule. Set on the FAI message.

Property ID: 0x65E9

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.4

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_STATE, ptagRuleMsgState

2.1025 PidTagRuleMessageUserFlags

Canonical name: PidTagRuleMessageUserFlags

Description: Contains an opaque property that the client sets for the exclusive use of the client. Set on the FIA message.

Property ID: 0x65EA

Data type: PtypInteger32, 0x0003

Area: ExchangeNonTransmittableReserved

Defining reference: [\[MS-OXORULE\]](#) section 2.2.4.1.5

Consuming reference: [\[MS-OXCSPAM\]](#)

Alternate names: PR_RULE_MSG_USER_FLAGS, ptagRuleMsgUserFlags

2.1026 PidTagRuleName

Canonical name: PidTagRuleName

Description: Specifies the name of the rule.

Property ID: 0x6682

Data type: PtypString, 0x001F

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.4

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_NAME, PR_RULE_NAME_A, ptagRuleName, PR_RULE_NAME_W

2.1027 PidTagRuleProvider

Canonical name: PidTagRuleProvider

Description: Contains opaque data set by the client for the exclusive use of the client.

Property ID: 0x6681

Data type: PtypString, 0x001F

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.5

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_PROVIDER, ptagRuleProvider, PR_RULE_PROVIDER_W

2.1028 PidTagRuleProviderData

Canonical name: PidTagRuleProviderData

Description: Contains opaque data set by the client for the exclusive use of the client.

Property ID: 0x6684

Data type: PtypBinary, 0x0102

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.8

Alternate names: PR_RULE_PROVIDER_DATA, ptagRuleProviderData

2.1029 PidTagRuleSequence

Canonical name: PidTagRuleSequence

Description: Contains a value used to determine the order in which rules are evaluated and executed.

Property ID: 0x6676

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.2

Consuming references: [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_SEQUENCE, ptagRuleSequence

2.1030 PidTagRuleState

Canonical name: PidTagRuleState

Description: Contains flags that specify the state of the rule.

Property ID: 0x6677

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.3

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_STATE, ptagRuleState

2.1031 PidTagRuleUserFlags

Canonical name: PidTagRuleUserFlags

Description: Contains an opaque property that the client sets for the exclusive use of the client.

Property ID: 0x6678

Data type: PtypInteger32, 0x0003

Area: Server-Side Rules Properties

Defining reference: [\[MS-OXORULE\]](#) section 2.2.1.3.1.7

Consuming reference: [\[MS-OXODLGT\]](#)

Alternate names: PR_RULE_USER_FLAGS, ptagRuleUserFlags

2.1032 PidTagRwRulesStream

Canonical name: PidTagRwRulesStream

Description: Contains additional rule data that is opaque to the server.

Property ID: 0x6802

Data type: PtypBinary, 0x0102

Area: Message Class Defined Transmittable

Defining reference:

Consuming reference: [\[MS-OXORULE\]](#)

Alternate names: PR_RW_RULES_STREAM

2.1033 PidTagScheduleInfoAppointmentTombstone

Canonical name: PidTagScheduleInfoAppointmentTombstone

Description: Contains a list of tombstones, where each tombstone represents a Meeting object that has been declined.

Property ID: 0x686A

Data type: PtypBinary, 0x0102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.5

Alternate names: PR_SCHDINFO_APPT_TOMBSTONE

2.1034 PidTagScheduleInfoAutoAcceptAppointments

Canonical name: PidTagScheduleInfoAutoAcceptAppointments

Description: Indicates whether a client or server is to automatically respond to all meeting requests for the attendee or resource.

Property ID: 0x686D

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.2

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_AUTO_ACCEPT_APPTS

2.1035 PidTagScheduleInfoDelegateEntryIds

Canonical name: PidTagScheduleInfoDelegateEntryIds

Description: Specifies the EntryIDs of the delegates.

Property ID: 0x6845

Data type: **PtypMultipleBinary**, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.5

Alternate names: PR_SCHDINFO_DELEGATE_ENTRYIDS

2.1036 PidTagScheduleInfoDelegateNames

Canonical name: PidTagScheduleInfoDelegateNames

Description: Specifies the names of the delegates.

Property ID: 0x6844

Data type: **PtypMultipleString**, 0x101F

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.3

Consuming reference: [\[MS-OXMSG\]](#)

Alternate names: PR_SCHDINFO_DELEGATE_NAMES

2.1037 PidTagScheduleInfoDelegateNamesW

Canonical name: PidTagScheduleInfoDelegateNamesW

Description: Specifies the names of the delegates in Unicode.

Property ID: 0x684A

Data type: **PtypMultipleString**, 0x101F

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.4

Alternate names: PR_SCHDINFO_DELEGATE_NAMES_W, ptagDelegateNames

2.1038 PidTagScheduleInfoDelegatorWantsCopy

Canonical name: PidTagScheduleInfoDelegatorWantsCopy

Description: Indicates whether the delegator wants to receive copies of the meeting-related objects that are sent to the delegate.

Property ID: 0x6842

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.1

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_BOSS_WANTS_COPY

2.1039 PidTagScheduleInfoDelegatorWantsInfo

Canonical name: PidTagScheduleInfoDelegatorWantsInfo

Description: Indicates whether the delegator wants to receive informational updates.

Property ID: 0x684B

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXODLGT\]](#) section 2.2.2.2.2

Consuming references: [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_BOSS_WANTS_INFO

2.1040 PidTagScheduleInfoDisallowOverlappingAppts

Canonical name: PidTagScheduleInfoDisallowOverlappingAppts

Description: Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that overlap with previously scheduled events.

Property ID: 0x686F

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.4

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_DISALLOW_OVERLAPPING_APPTS

2.1041 PidTagScheduleInfoDisallowRecurringAppts

Canonical name: PidTagScheduleInfoDisallowRecurringAppts

Description: Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that represent a recurring series.

Property ID: 0x686E

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.12.3

Consuming reference: [\[MS-OXOPFFB\]](#)

Alternate names: PR_SCHDINFO_DISALLOW_RECURRING_APPTS

2.1042 PidTagScheduleInfoDontMailDelegates

Canonical name: PidTagScheduleInfoDontMailDelegates

Description:

Property ID: 0x6843

Data type: PtypBoolean, 0x000B

Area: Free/Busy Properties

Defining reference:

Consuming references: [\[MS-OXOPFFB\]](#), [\[MS-OXODLGT\]](#)

Alternate names: PR_SCHDINFO_DONT_MAIL_DELEGATES

2.1043 PidTagScheduleInfoFreeBusy

Canonical name: PidTagScheduleInfoFreeBusy

Description: This property is deprecated and is not to be used.

Property ID: 0x686C

Data type: PtypBinary, 0x0102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.4.3

Alternate names: PR_SCHDINFO_FREEBUSY

2.1044 PidTagScheduleInfoFreeBusyAway

Canonical name: PidTagScheduleInfoFreeBusyAway

Description: Specifies the times for which the free/busy status is set a value of OOF.

Property ID: 0x6856

Data type: PtypMultipleBinary, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.6

Alternate names: PR_SCHDINFO_FREEBUSY_OOF

2.1045 PidTagScheduleInfoFreeBusyBusy

Canonical name: PidTagScheduleInfoFreeBusyBusy

Description: Specifies the blocks of time for which the free/busy status is set to a value of **busy**.

Property ID: 0x6854

Data type: **PtypMultipleBinary**, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.4

Alternate names: PR_SCHDINFO_FREEBUSY_BUSY

2.1046 PidTagScheduleInfoFreeBusyMerged

Canonical name: PidTagScheduleInfoFreeBusyMerged

Description: Specifies the months for which free/busy data of type **busy** or OOF is present in the free/busy message.

Property ID: 0x6850

Data type: **PtypMultipleBinary**, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.8

Alternate names: PR_SCHDINFO_FREEBUSY_MERGED

2.1047 PidTagScheduleInfoFreeBusyTentative

Canonical name: PidTagScheduleInfoFreeBusyTentative

Description: Specifies the blocks of times for which the free/busy status is set to a value of **tentative**.

Property ID: 0x6852

Data type: **PtypMultipleBinary**, 0x1102

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.2

Alternate names: PR_SCHDINFO_FREEBUSY_TENTATIVE

2.1048 PidTagScheduleInfoMonthsAway

Canonical name: PidTagScheduleInfoMonthsAway

Description: Specifies the months for which free/busy data of type OOF is present in the free/busy message.

Property ID: 0x6855

Data type: **PtypMultipleInteger32**, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.5

Alternate names: PR_SCHDINFO_MONTHS_OOF

2.1049 PidTagScheduleInfoMonthsBusy

Canonical name: PidTagScheduleInfoMonthsBusy

Description: Specifies the months for which free/busy data of type **busy** is present in the free/busy message.

Property ID: 0x6853

Data type: **PtypMultipleInteger32**, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.3

Consuming reference: [\[MS-OXMSG\]](#)

Alternate names: PR_SCHDINFO_MONTHS_BUSY

2.1050 PidTagScheduleInfoMonthsMerged

Canonical name: PidTagScheduleInfoMonthsMerged

Description: Specifies the months for which free/busy data of type **busy** or OOF is present in the free/busy message.

Property ID: 0x684F

Data type: **PtypMultipleInteger32**, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.7

Alternate names: PR_SCHDINFO_MONTHS_MERGED

2.1051 PidTagScheduleInfoMonthsTentative

Canonical name: PidTagScheduleInfoMonthsTentative

Description: Specifies the months for which free/busy data of type **tentative** is present in the free/busy message.

Property ID: 0x6851

Data type: **PtypMultipleInteger32**, 0x1003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.2.1

Alternate names: PR_SCHDINFO_MONTHS_TENTATIVE

2.1052 PidTagScheduleInfoResourceType

Canonical name: PidTagScheduleInfoResourceType

Description: Set to 0x00000000 when sending and is ignored on receipt.

Property ID: 0x6841

Data type: **PtypInteger32**, 0x0003

Area: Free/Busy Properties

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.1.4.2

Alternate names: PR_SCHDINFO_RESOURCE_TYPE

2.1053 PidTagSchedulePlusFreeBusyEntryId

Canonical name: PidTagSchedulePlusFreeBusyEntryId

Description: Contains the EntryID of the folder named "SCHEDULE+ FREE BUSY" under the non-IPM subtree of the public folder store.

Property ID: 0x6622

Data type: **PtypBinary**, 0x0102

Area: ExchangeMessageStore

Defining reference: [\[MS-OXOPFFB\]](#) section 2.2.2.2

Alternate names: PR_SPLUS_FREE_BUSY_ENTRYID

2.1054 PidTagScriptData

Canonical name: PidTagScriptData

Description: Contains a series of instructions that can be executed to format an address and the data that is needed to execute those instructions.

Property ID: 0x0004

Data type: **PtypBinary**, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABKT\]](#) section 2.2.2

Alternate names: PR_EMS_SCRIPT_BLOB

2.1055 PidTagSearchFolderDefinition

Canonical name: PidTagSearchFolderDefinition

Description: Specifies the search criteria and search options.

Property ID: 0x6845

Data type: **PtypBinary**, 0x0102

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.8

Alternate names: PR_WB_SF_DEFINITION

2.1056 PidTagSearchFolderEfpFlags

Canonical name: PidTagSearchFolderEfpFlags

Description: Specifies flags that control how a folder is displayed.

Property ID: 0x6848

Data type: **PtypInteger32**, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.7

Alternate names: PR_WB_SF_EFP_FLAGS

2.1057 PidTagSearchFolderExpiration

Canonical name: PidTagSearchFolderExpiration

Description: Contains the time, in UTC, at which the search folder container will be stale and has to be updated or recreated.

Property ID: 0x683A

Data type: **PtypInteger32**, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.5

Alternate names: PR_WB_SF_EXPIRATION

2.1058 PidTagSearchFolderId

Canonical name: PidTagSearchFolderId

Description: Contains a GUID that identifies the search folder.

Property ID: 0x6842

Data type: **PtypBinary**, 0x0102

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.1

Consuming reference: [\[MS-OXOCFG\]](#)

Alternate names: PR_WB_SF_ID

2.1059 PidTagSearchFolderLastUsed

Canonical name: PidTagSearchFolderLastUsed

Description: Contains the last time, in UTC, that the folder was accessed.

Property ID: 0x6834

Data type: **PtypInteger32**, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.4

Alternate names: PR_WB_SF_LAST_USED

2.1060 PidTagSearchFolderRecreateInfo

Canonical name: PidTagSearchFolderRecreateInfo

Description: This property is not to be used.

Property ID: 0x6844

Data type: **PtypBinary**, 0x0102

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.9

Alternate names: PR_WB_SF_RECREATE_INFO

2.1061 PidTagSearchFolderStorageType

Canonical name: PidTagSearchFolderStorageType

Description: Contains flags that specify the binary large object (BLOB) data that appears in the **PidTagSearchFolderDefinition** (section [2.1055](#)) property.

Property ID: 0x6846

Data type: **PtypInteger32**, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.6

Alternate names: PR_WB_SF_STORAGE_TYPE

2.1062 PidTagSearchFolderTag

Canonical name: PidTagSearchFolderTag

Description: Contains the value of the **SearchFolderTag** sub-property of the **PidTagExtendedFolderFlags** (section [2.764](#)) property of the search folder container.

Property ID: 0x6847

Data type: **PtypInteger32**, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.3

Alternate names: PR_WB_SF_TAG

2.1063 PidTagSearchFolderTemplateId

Canonical name: PidTagSearchFolderTemplateId

Description: Contains the ID of the template that is being used for the search.

Property ID: 0x6841

Data type: **PtypInteger32**, 0x0003

Area: Search

Defining reference: [\[MS-OXOSRCH\]](#) section 2.2.1.2.2

Alternate names: PR_WB_SF_TEMPLATE_ID

2.1064 PidTagSearchKey

Canonical name: PidTagSearchKey

Description: Contains a unique binary-comparable key that identifies an object for a search.

Property ID: 0x300B

Data type: **PtypBinary**, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCPRPT\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SEARCH_KEY, ptagSearchKey

2.1065 PidTagSecurityDescriptor

Canonical name: PidTagSecurityDescriptor

Description: Contains security attributes.

Property ID: 0x0E27

Data type: **PtypBinary**, 0x0102

Area: Access Control Properties

Defining reference:

Consuming reference: [\[MS-OXCMSG\]](#)

Alternate names: PR_NT_SECURITY_DESCRIPTOR

2.1066 PidTagSecurityDescriptorAsXml

Canonical name: PidTagSecurityDescriptorAsXml

Description: Contains security attributes in XML.

Property ID: 0x0E6A

Data type: PtypString, 0x001F

Area: Access Control Properties

Defining reference: [\[MS-XWDVSEC\]](#) section 2.2.2

Consuming reference: [\[MS-OXCPERM\]](#)

Alternate names: PR_NT_SECURITY_DESCRIPTOR_AS_XML, PR_NT_SECURITY_DESCRIPTOR_AS_XML_A, PR_NT_SECURITY_DESCRIPTOR_AS_XML_W, <http://schemas.microsoft.com/exchange/security/descriptor>

2.1067 PidTagSelectable

Canonical name: PidTagSelectable

Description: This property is not set and, if set, is ignored.

Property ID: 0x3609

Data type: PtypBoolean, 0x000B

Area: AB Container

Defining reference: [\[MS-OXOABKT\]](#) section 2.2.1

Alternate names: PR_SELECTABLE

2.1068 PidTagSenderAddressType

Canonical name: PidTagSenderAddressType

Description: Contains the e-mail address type of the sending mailbox owner.

Property ID: 0x0C1E

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.45

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOPOST\]](#)

Alternate names: PR_SENDER_ADDRTYPE, PR_SENDER_ADDRTYPE_A, ptagSenderAddrType, PR_SENDER_ADDRTYPE_W

2.1069 PidTagSenderEmailAddress

Canonical name: PidTagSenderEmailAddress

Description: Contains the e-mail address of the sending mailbox owner.

Property ID: 0x0C1F

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.46

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENDER_EMAIL_ADDRESS, PR_SENDER_EMAIL_ADDRESS_A, PR_SENDER_EMAIL_ADDRESS_W

2.1070 PidTagSenderEntryId

Canonical name: PidTagSenderEntryId

Description: Identifies an address book EntryID that contains the address book EntryID of the sending mailbox owner.

Property ID: 0x0C19

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.47

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENDER_ENTRYID, ptagSenderEntryId

2.1071 PidTagSenderIdStatus

Canonical name: PidTagSenderIdStatus

Description: Reports the results of a Sender-ID check.

Property ID: 0x4079

Data type: PtypInteger32, 0x0003

Area: Secure Messaging Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.76

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: PR_SENDER_ID_STATUS

2.1072 PidTagSenderName

Canonical name: PidTagSenderName

Description: Contains the display name of the sending mailbox owner.

Property ID: 0x0C1A

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.48

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_SENDER_NAME, PR_SENDER_NAME_A, ptagSenderName, PR_SENDER_NAME_W, urn:schemas:httpmail:sendername, http://schemas.microsoft.com/exchange/sender-name-utf8

2.1073 PidTagSenderSearchKey

Canonical name: PidTagSenderSearchKey

Description: Identifies an address book search key.

Property ID: 0x0C1D

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.49

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#)

Alternate names: PR_SENDER_SEARCH_KEY, ptagSenderSearchKey

2.1074 PidTagSenderSmtpAddress

Canonical name: PidTagSenderSmtpAddress

Description: Contains the SMTP e-mail address format of the e-mail address of the sending mailbox owner.

Property ID: 0x5D01

Data type: PtypString, 0x001F

Area: Mail

Defining reference: [MS-OXOMSG] section [2.2.1.52](#)

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: SenderSmtptAddress, ptagSenderSmtptAddress

2.1075 PidTagSenderTelephoneNumber

Canonical name: PidTagSenderTelephoneNumber

Description: Contains the telephone number of the caller associated with a voice mail message.

Property ID: 0x6802

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.1

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaSenderTelephoneNumber

2.1076 PidTagSendInternetEncoding

Canonical name: PidTagSendInternetEncoding

Description: Contains a bitmask of message encoding preferences for e-mail sent to an e-mail-enabled entity that is represented by this Address Book object.

Property ID: 0x3A71

Data type: PtypInteger32, 0x0003

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.19

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_SEND_INTERNET_ENCODING, ptagSendInternetEncoding

2.1077 PidTagSendRichInfo

Canonical name: PidTagSendRichInfo

Description: Indicates whether the e-mail-enabled entity represented by the Address Book object can receive all message content, including Rich Text Format (RTF) and other embedded objects.

Property ID: 0x3A40

Data type: PtypBoolean, 0x000B

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.18

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

Alternate names: PR_SEND_RICH_INFO, ptagSendRichInfo

2.1078 PidTagSensitivity

Canonical name: PidTagSensitivity

Description: Indicates the sender's assessment of the sensitivity of the Message object.

Property ID: 0x0036

Data type: PtypInteger32, 0x0003

Area: General Message Properties **Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.13

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#)

Alternate names: PR_SENSITIVITY, ptagSensitivity,
<http://schemas.microsoft.com/exchange/sensitivity-long>,
<http://schemas.microsoft.com/exchange/sensitivity>

2.1079 PidTagSentMailSvrEID

Canonical name: PidTagSentMailSvrEID

Description: Contains an EntryID that represents the **Sent Items folder** for the message.

Property ID: 0x6740

Data type: PtypServerId, 0x00FB

Area: ProviderDefinedNonTransmittable

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.3.10

Consuming reference: [\[MS-OXCSTOR\]](#)

Alternate names: ptagSentMailSvrEID

2.1080 PidTagSentRepresentingAddressType

Canonical name: PidTagSentRepresentingAddressType

Description: Contains an e-mail address type.

Property ID: 0x0064

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.51

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_ADDRTYPE, PR_SENT_REPRESENTING_ADDRTYPE_A, ptagSentRepresentingAddrType, PR_SENT_REPRESENTING_ADDRTYPE_W

2.1081 PidTagSentRepresentingEmailAddress

Canonical name: PidTagSentRepresentingEmailAddress

Description: Contains an e-mail address for the end user who is represented by the sending mailbox owner.

Property ID: 0x0065

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.52

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_EMAIL_ADDRESS, PR_SENT_REPRESENTING_EMAIL_ADDRESS_A, PR_SENT_REPRESENTING_EMAIL_ADDRESS_W

2.1082 PidTagSentRepresentingEntryId

Canonical name: PidTagSentRepresentingEntryId

Description: Contains the identifier of the end user who is represented by the sending mailbox owner.

Property ID: 0x0041

Data type: PtypBinary, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.53

Consuming references: [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SENT_REPRESENTING_ENTRYID, ptagSentRepresentingEntryId

2.1083 PidTagSentRepresentingFlags

Canonical name: PidTagSentRepresentingFlags

Description:

Property ID: 0x401A

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

Alternate names: ptagSentRepresentingFlags

2.1084 PidTagSentRepresentingName

Canonical name: PidTagSentRepresentingName

Description: Contains the display name for the end user who is represented by the sending mailbox owner.

Property ID: 0x0042

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.54

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDMAIL\]](#)

Alternate names: PR_SENT_REPRESENTING_NAME, PR_SENT_REPRESENTING_NAME_A, ptagSentRepresentingName, PR_SENT_REPRESENTING_NAME_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

2.1085 PidTagSentRepresentingSearchKey

Canonical name: PidTagSentRepresentingSearchKey

Description: Contains a binary-comparable key that represents the end user who is represented by the sending mailbox owner.

Property ID: 0x003B

Data type: **PtypBinary**, 0x0102

Area: Address Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.55

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

Alternate names: PR_SENT_REPRESENTING_SEARCH_KEY, ptagSentRepresentingSearchKey

2.1086 PidTagSmtpAddress

Canonical name: PidTagSmtpAddress

Description: Contains the SMTP address of the Message object.

Property ID: 0x39FE

Data type: **PtypString**, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.21

Consuming references: [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXSHARE\]](#)

Alternate names: PR_SMTP_ADDRESS, PR_SMTP_ADDRESS_A, PR_SMTP_ADDRESS_W

2.1087 PidTagSortLocaleId

Canonical name: PidTagSortLocaleId

Description: Contains the locale identifier.

Property ID: 0x6705

Data type: **PtypInteger32**, 0x0003

Area: ExchangeAdministrative

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1.2.7

Consuming reference: [\[MS-OXPFOAB\]](#)

Alternate names: PR_SORT_LOCALE_ID, ptagSortLocaleId

2.1088 PidTagSourceKey

Canonical name: PidTagSourceKey

Description: Contains a value that contains an internal global identifier (GID) for this folder or message.

Property ID: 0x65E0

Data type: **PtypBinary**, 0x0102

Area: Sync

Defining reference: [\[MS-OXCFXICS\]](#) section 2.2.1.2.5

Alternate names: PR_SOURCE_KEY

2.1089 PidTagSpokenName

Canonical name: PidTagSpokenName

Description: Contains a recording of the mail user's name pronunciation.

Property ID: 0x8CC2

Data type: **PtypBinary**, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.83

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_UM_SPOKEN_NAME

2.1090 PidTagSpouseName

Canonical name: PidTagSpouseName

Description: Contains the name of the mail user's spouse/partner.

Property ID: 0x3A48

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.72

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SPOUSE_NAME, PR_SPOUSE_NAME_A, PR_SPOUSE_NAME_W,
urn:schemas:contacts:spousecn

2.1091 PidTagStartDate

Canonical name: PidTagStartDate

Description: Contains the value of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

Property ID: 0x0060

Data type: PtypTime, 0x0040

Area: MapiEnvelope

Defining reference: [\[MS-OXOCAL\]](#) section 2.2.1.30

Consuming references: [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#),

Alternate names: PR_START_DATE, http://schemas.microsoft.com/mapi/start_date

2.1092 PidTagStartDateEtc

Canonical name: PidTagStartDateEtc

Description: Contains the default retention period, and the start date from which the age of a Message object is calculated.

Property ID: 0x301B

Data type: PtypBinary, 0x0102

Area: Archive

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.50.4

Alternate names: PR_START_DATE_ETC, ptagStartDateEtc

2.1093 PidTagStateOrProvince

Canonical name: PidTagStateOrProvince

Description: Contains the name of the mail user's state or province.

Property ID: 0x3A28

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.22

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_STATE_OR_PROVINCE, PR_STATE_OR_PROVINCE_A, PR_STATE_OR_PROVINCE_W, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_A, PR_BUSINESS_ADDRESS_STATE_OR_PROVINCE_W, urn:schemas:contacts:mailingstate

2.1094 PidTagStoreEntryId

Canonical name: PidTagStoreEntryId

Description: Contains the unique EntryID of the message store where an object resides.

Property ID: 0x0FFB

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.44

Consuming references: [\[MS-OXOFLAG\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXOCFG\]](#)

Alternate names: PR_STORE_ENTRYID, ptagStoreEntryId

2.1095 PidTagStoreState

Canonical name: PidTagStoreState

Description: Indicates whether a mailbox has any active Search folders.

Property ID: 0x340E

Data type: PtypInteger32, 0x0003

Area: MapiMessageStore

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_STORE_STATE

2.1096 PidTagStoreSupportMask

Canonical name: PidTagStoreSupportMask

Description: Indicates whether string properties within the .msg file are Unicode-encoded.

Property ID: 0x340D

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference: [\[MS-OXMSG\]](#) section 2.1.1.1

Alternate names: PR_STORE_SUPPORT_MASK, ptagStoreSupportMask

2.1097 PidTagStreetAddress

Canonical name: PidTagStreetAddress

Description: Contains the mail user's street address.

Property ID: 0x3A29

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.19

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_STREET_ADDRESS, PR_STREET_ADDRESS_A, PR_STREET_ADDRESS_W, PR_BUSINESS_ADDRESS_STREET, PR_BUSINESS_ADDRESS_STREET_A, PR_BUSINESS_ADDRESS_STREET_W, urn:schemas:contacts:mailingstreet

2.1098 PidTagSubfolder

Canonical name: PidTagSubfolder

Description: Indicates whether the resource is a folder as displayed to end users.

Property ID: 0x6708

Data type: PtypBoolean, 0x000B

Area: ExchangeAdministrative Property set

Defining reference: [\[MS-XWDFOLD\]](#) section 2.2.1

Consuming references: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SUBFOLDER, ptagSubfolder, DAV:isfolder

2.1099 PidTagSubfolders

Canonical name: PidTagSubfolders

Description: Specifies whether a folder has subfolders.

Property ID: 0x360A

Data type: **PtypBoolean**, 0x000B

Area: MapiContainer

Defining reference: [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.10

Consuming references: [\[MS-XWDFOLD\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SUBFOLDERS, ptagSubFolders, DAV:hassubs

2.1100 PidTagSubject

Canonical name: PidTagSubject

Description: Contains the subject of the e-mail message.

Property ID: 0x0037

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.46

Consuming references: [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SUBJECT, PR_SUBJECT_A, ptagSubject, PR_SUBJECT_W, urn:schemas:httpmail:subject, http://schemas.microsoft.com/exchange/subject-utf8

2.1101 PidTagSubjectPrefix

Canonical name: PidTagSubjectPrefix

Description: Contains the prefix for the subject of the message.

Property ID: 0x003D

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.9

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_SUBJECT_PREFIX, PR_SUBJECT_PREFIX_A, ptagSubjectPrefix, PR_SUBJECT_PREFIX_W

2.1102 PidTagSurname

Canonical name: PidTagSurname

Description: Contains the mail user's family name.

Property ID: 0x3A11

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.1

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_SURNAME, PR_SURNAME_A, PR_SURNAME_W, urn:schemas:contacts:sn

2.1103 PidTagSwappedToDoData

Canonical name: PidTagSwappedToDoData

Description: Contains a secondary storage location for flags when sender flags or sender reminders are supported.

Property ID: 0x0E2D

Data type: PtypBinary, 0x0102

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.7

Consuming reference: [\[MS-OXORMDR\]](#)

Alternate names: PR_SWAPPED_TODO_DATA, ptagSwappedToDoData

2.1104 PidTagSwappedToDoStore

Canonical name: PidTagSwappedToDoStore

Description: Contains the value of the **PidTagStoreEntryId** property (section [2.1094](#)) of the message when the value of the **PidTagSwappedToDoData** property (section [2.1103](#)) is set.

Property ID: 0x0E2C

Data type: PtypBinary, 0x0102

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.8

Consuming reference: [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_SWAPPED_TODO_STORE, ptagSwappedToDoStore

2.1105 PidTagTargetEntryId

Canonical name: PidTagTargetEntryId

Description: Contains the message ID of a Message object being submitted for optimization ([\[MS-OXOMSG\]](#) section 3.2.4.4).

Property ID: 0x3010

Data type: PtypBinary, 0x0102

Area: ID Properties

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.72

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCRPC\]](#),

Alternate names: PR_TARGET_ENTRYID, ptagTargetEntryId

2.1106 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Canonical name: PidTagTelecommunicationsDeviceForDeafTelephoneNumber

Description: Contains the mail user's telecommunication device for the deaf (TTY/TDD) telephone number.

Property ID: 0x3A4B

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.54

Consuming references: [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_TTYTDD_PHONE_NUMBER, PR_TTYTDD_PHONE_NUMBER_A, PR_TTYTDD_PHONE_NUMBER_W, urn:schemas:contacts:tytddphone

2.1107 PidTagTelexNumber

Canonical name: PidTagTelexNumber

Description: Contains the mail user's telex number.

Property ID: 0x3A2C

Data type: PtypString, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.55

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_TELEX_NUMBER, PR_TELEX_NUMBER_A, PR_TELEX_NUMBER_W, urn:schemas:contacts:telexnumber

2.1108 PidTagTemplateData

Canonical name: PidTagTemplateData

Description: Describes the controls used in the template that is used to retrieve address book information.

Property ID: 0x0001

Data type: PtypBinary, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABKT\]](#) section 2.2.2

Alternate names: PR_EMS_TEMPLATE_BLOB

2.1109 PidTagTemplateid

Canonical name: PidTagTemplateid

Description: Contains the value of the **PidTagEntryId** property (section [2.756](#)), expressed as a **Permanent Entry ID** format.

Property ID: 0x3902

Data type: PtypBinary, 0x0102

Area: MapiAddressBook

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.3

Alternate names: PR_TEMPLATEID

2.1110 PidTagTemporaryDefaultDocument

Canonical name: PidTagTemporaryDefaultDocument

Description: Indicates the relative URI of the default document contained in the structured document.

Property ID: 0x3F20

Data type: PtypString, 0x001F

Area: Structured Documents

Defining reference: [\[MS-XWDSTRUCTDOC\]](#) section 2.2.1.1

Consuming reference: [\[MS-XWDEXT\]](#)

Alternate names: DAV:defaultdocument

2.1111 PidTagTextAttachmentCharset

Canonical name: PidTagTextAttachmentCharset

Description: Specifies the character set of an attachment received via MIME with the content-type of text.

Property ID: 0x371B

Data type: **PtypString**, 0x001F

Area: Message Attachment Properties

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.2.25

Consuming reference: [\[MS-OXCMAIL\]](#)

Alternate names: ptagTextAttachmentCharset

2.1112 PidTagThumbnailPhoto

Canonical name: PidTagThumbnailPhoto

Description: Contains the mail user's photo in .jpg format.

Property ID: 0x8C9E

Data type: **PtypBinary**, 0x0102

Area: Address Book

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.82

Consuming reference: [\[MS-OXOAB\]](#)

Alternate names: PR_EMS_AB_THUMBNAIL_PHOTO

2.1113 PidTagTitle

Canonical name: PidTagTitle

Description: Contains the mail user's job title.

Property ID: 0x3A17

Data type: **PtypString**, 0x001F

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.7

Consuming references: [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_TITLE, PR_TITLE_A, PR_TITLE_W, urn:schemas:contacts:title

2.1114 PidTagTnefCorrelationKey

Canonical name: PidTagTnefCorrelationKey

Description: Contains a value that correlates a Transport Neutral Encapsulation Format (TNEF) attachment with a message.

Property ID: 0x007F

Data type: PtypBinary, 0x0102

Area: MapiEnvelope

Defining reference: [\[MS-OXCMMSG\]](#) section 2.2.1.29

Consuming reference: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_TNEF_CORRELATION_KEY

2.1115 PidTagToDoItemFlags

Canonical name: PidTagToDoItemFlags

Description: Contains flags associated with objects.

Property ID: 0x0E2B

Data type: PtypInteger32, 0x0003

Area: MapiNonTransmittable

Defining reference: [\[MS-OXOFLAG\]](#) section 2.2.1.6

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOSFLD\]](#)

Alternate names: PR_TODO_ITEM_FLAGS, ptagToDoItemFlags

2.1116 PidTagTransmittableDisplayName

Canonical name: PidTagTransmittableDisplayName

Description: Contains an Address Book object's display name that is transmitted with the message.

Property ID: 0x3A20

Data type: PtypString, 0x001F

Area: Address Properties

Defining reference: [\[MS-OXOABK\]](#) section 2.2.3.8

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMMSG\]](#)

Alternate names: PR_TRANSMITABLE_DISPLAY_NAME, PR_TRANSMITABLE_DISPLAY_NAME_A, ptagTransmittableDisplayName, PR_TRANSMITABLE_DISPLAY_NAME_W

2.1117 PidTagTransportMessageHeaders

Canonical name: PidTagTransportMessageHeaders

Description: Contains transport-specific message envelope information for e-mail.

Property ID: 0x007D

Data type: PtypString, 0x001F

Area: E-mail

Defining reference: [\[MS-OXOMSG\]](#) section 2.2.1.57

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

Alternate names: PR_TRANSPORT_MESSAGE_HEADERS, PR_TRANSPORT_MESSAGE_HEADERS_A, PR_TRANSPORT_MESSAGE_HEADERS_W

2.1118 PidTagTrustSender

Canonical name: PidTagTrustSender

Description: Specifies whether the associated message was delivered through a trusted transport channel.

Property ID: 0x0E79

Data type: **PtypInteger32**, 0x0003

Area: MapiNonTransmittable

Defining reference: [\[MS-OXCMSG\]](#) section 2.2.1.45

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

Alternate names: PR_TRUST_SENDER, ptagTrustSender

2.1119 PidTagUrlCompName

Canonical name: PidTagUrlCompName

Description: Contains the composite URL name.

Property ID: 0x10F3

Data type: **PtypString**, 0x001F

Area: General Message Properties

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.1.2

Consuming references: [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

Alternate names: PR_URL_COMP_NAME, PR_URL_COMP_NAME_A, PR_URL_COMP_NAME_W, ptagURLCompName

2.1120 PidTagUrlCompNameSet

Canonical name: PidTagUrlCompNameSet

Description:

Property ID: 0x0E62

Data type: **PtypBoolean**, 0x000B

Area: ID Properties

Defining reference:

Consuming reference: [\[MS-OXCMSG\]](#)

Alternate names: ptagURLCompNameSet

2.1121 PidTagUrlName

Canonical name: PidTagUrlName

Description: Contains the URL of an object.

Property ID: 0x6707

Data type: PtypString, 0x001F

Area: ExchangeAdministrative

Defining reference: [\[MS-XWDMAIL\]](#) section 2.2.2.1.4

Consuming references: [\[MS-XWDCAL\]](#), [\[MS-XWDDOC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_URL_NAME, PR_URL_NAME_A, PR_URL_NAME_W, ptagURLName, DAV:href

2.1122 PidTagUserCertificate

Canonical name: PidTagUserCertificate

Description: Contains an ASN.1 authentication certificate for a messaging user.

Property ID: 0x3A22

Data type: PtypBinary, 0x0102

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.64

Consuming references: [\[MS-OXOAB\]](#), [\[MS-XWDCNTC\]](#)

Alternate names: PR_USER_CERTIFICATE, ptagUserCertificate, urn:schemas:contacts:usercertificate

2.1123 PidTagUserEntryId

Canonical name: PidTagUserEntryId

Description: Address book EntryID of the user logged on to the public folders.

Property ID: 0x6619

Data type: PtypBinary, 0x0102

Area: ExchangeMessageStore

Defining reference: [\[MS-OXCSTOR\]](#) section 2.2.2.1

Alternate names: PR_USER_ENTRYID, ptagUserEntryId

2.1124 PidTagUserX509Certificate

Canonical name: PidTagUserX509Certificate

Description: Contains a list of certificates for the mail user.

Property ID: 0x3A70

Data type: PtypMultipleBinary, 0x1102

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.66

Consuming references: [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

Alternate names: PR_USER_X509_CERTIFICATE

2.1125 PidTagViewDescriptorBinary

Canonical name: PidTagViewDescriptorBinary

Description: Contains view definitions.

Property ID: 0x7001

Data type: PtypBinary, 0x0102

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.6.1

Alternate names: PR_VD_BINARY

2.1126 PidTagViewDescriptorName

Canonical name: PidTagViewDescriptorName

Description:

Property ID: 0x7006

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference:

Consuming reference: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_NAME, PR_VD_NAME_W

2.1127 PidTagViewDescriptorStrings

Canonical name: PidTagViewDescriptorStrings

Description: Contains view definitions in string format.

Property ID: 0x7002

Data type: PtypString, 0x001F

Area: MessageClassDefinedTransmittable

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.6.2

Alternate names: PR_VD_STRINGS, PR_VD_STRINGS_W

2.1128 PidTagViewDescriptorVersion

Canonical name: PidTagViewDescriptorVersion

Description: Contains the View Descriptor version.

Property ID: 0x7007

Data type: PtypInteger32, 0x0003

Area: Miscellaneous Properties

Defining reference:

Consuming reference: [\[MS-OXOCFG\]](#)

Alternate names: PR_VD_VERSION

2.1129 PidTagVoiceMessageAttachmentOrder

Canonical name: PidTagVoiceMessageAttachmentOrder

Description: Contains a list of file names for the audio file attachments that are to be played as part of a message.

Property ID: 0x6805

Data type: PtypString, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.9

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaVoiceMessageAttachmentOrder

2.1130 PidTagVoiceMessageDuration

Canonical name: PidTagVoiceMessageDuration

Description: Specifies the length of the attached audio message, in seconds.

Property ID: 0x6801

Data type: PtypInteger32, 0x0003

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.3

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaVoiceMessageDuration

2.1131 PidTagVoiceMessageSenderName

Canonical name: PidTagVoiceMessageSenderName

Description: Specifies the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

Property ID: 0x6803

Data type: **PtypString**, 0x001F

Area: Unified Messaging

Defining reference: [\[MS-OXOUM\]](#) section 2.2.5.5

Consuming references: [\[MS-OXCMAIL\]](#)

Alternate names: InternalSchemaVoiceMessageSenderName

2.1132 PidTagWeddingAnniversary

Canonical name: PidTagWeddingAnniversary

Description: Contains the date of the mail user's wedding anniversary.

Property ID: 0x3A41

Data type: **PtypTime**, 0x0040

Area: MapiMailUser

Defining reference: [\[MS-OXOABK\]](#) section 2.2.4.80

Consuming references: [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCNTC\]](#), [\[MS-XWDEXT\]](#)

Alternate names: PR_WEDDING_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

2.1133 PidTagWlinkAddressBookEID

Canonical name: PidTagWlinkAddressBookEID

Description: Specifies the value of the **PidTagEntryId** property (section [2.756](#)) of the user to whom the folder belongs.

Property ID: 0x6854

Data type: **PtypBinary**, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.16

Alternate names: PR_WLINK_ABEID

2.1134 PidTagWlinkAddressBookStoreEID

Canonical name: PidTagWlinkAddressBookStoreEID

Description: Specifies the value of the **PidTagStoreEntryId** property (section [2.1094](#)) of the current user (not the owner of the folder).

Property ID: 0x6891

Data type: **PtypBinary**, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.17

Alternate names: PR_WLINK_AB_EXSTOREEID

2.1135 PidTagWlinkCalendarColor

Canonical name: PidTagWlinkCalendarColor

Description: Specifies the background color of the calendar.

Property ID: 0x6853

Data type: **PtypInteger32**, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.15

Alternate names: PR_WLINK_CALENDAR_COLOR

2.1136 PidTagWlinkClientID

Canonical name: PidTagWlinkClientID

Description: Specifies the Client ID that allows the client to determine whether the shortcut was created on the current machine/user via an equality test.

Property ID: 0x6890

Data type: **PtypGuid**, 0x0048

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.18

Alternate names: PR_WLINK_CLIENTID

2.1137 PidTagWlinkEntryId

Canonical name: PidTagWlinkEntryId

Description: Specifies the EntryID of the folder pointed to by the shortcut.

Property ID: 0x684C

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.8

Alternate names: PR_WLINK_ENTRYID

2.1138 PidTagWlinkFlags

Canonical name: PidTagWlinkFlags

Description: Specifies conditions associated with the shortcut.

Property ID: 0x684A

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.6

Alternate names: PR_WLINK_FLAGS

2.1139 PidTagWlinkFolderType

Canonical name: PidTagWlinkFolderType

Description: Specifies the type of folder pointed to by the shortcut.

Property ID: 0x684F

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.11

Alternate names: PR_WLINK_FOLDER_TYPE

2.1140 PidTagWlinkGroupClsid

Canonical name: PidTagWlinkGroupClsid

Description: Specifies the value of the **PidTagWlinkGroupHeaderID** property (section [2.1140](#)) of the **group header** associated with the shortcut.

Property ID: 0x6850

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.12

Alternate names: PR_WLINK_GROUP_CLSID

2.1141 PidTagWlinkGroupHeaderID

Canonical name: PidTagWlinkGroupHeaderID

Description: Specifies the ID of the **navigation shortcut** that groups other navigation shortcuts.

Property ID: 0x6842

Data type: PtypGuid, 0x0048

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.3

Alternate names:

2.1142 PidTagWlinkGroupName

Canonical name: PidTagWlinkGroupName

Description: Specifies the value of the **PidTagNormalizedSubject** (section [2.880](#)) of the group header associated with the shortcut.

Property ID: 0x6851

Data type: PtypString, 0x001F

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.13

Alternate names: PR_WLINK_GROUP_NAME

2.1143 PidTagWlinkOrdinal

Canonical name: PidTagWlinkOrdinal

Description: Specifies a variable-length binary property to be used to sort shortcuts lexicographically.

Property ID: 0x684B

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.7

Alternate names: PR_WLINK_ORDINAL

2.1144 PidTagWlinkRecordKey

Canonical name: PidTagWlinkRecordKey

Description: Specifies the value of **PidTagRecordKey** property (section [2.979](#)) of the folder pointed to by the shortcut.

Property ID: 0x684D

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.9

Alternate names: PR_WLINK_RECKEY

2.1145 PidTagWlinkROGroupType

Canonical name: PidTagWlinkROGroupType

Description: Specifies the type of group header.

Property ID: 0x6892

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.19

Alternate names: PR_WLINK_RO_GROUP_TYPE

2.1146 PidTagWlinkSaveStamp

Canonical name: PidTagWlinkSaveStamp

Description: Specifies an integer that allows a client to identify with a high probability whether the navigation shortcut was saved by the current client session.

Property ID: 0x6847

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.4

Alternate names:

2.1147 PidTagWlinkSection

Canonical name: PidTagWlinkSection

Description: Specifies the section where the shortcut should be grouped.

Property ID: 0x6852

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.14

Alternate names: PR_WLINK_SECTION

2.1148 PidTagWlinkStoreEntryId

Canonical name: PidTagWlinkStoreEntryId

Description: Specifies the value of the **PidTagStoreEntryId** property (section [2.1094](#)) of the folder pointed to by the shortcut.

Property ID: 0x684E

Data type: PtypBinary, 0x0102

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.10

Alternate names: PR_WLINK_STORE_ENTRYID

2.1149 PidTagWlinkType

Canonical name: PidTagWlinkType

Description: Specifies the type of navigation shortcut.

Property ID: 0x6849

Data type: PtypInteger32, 0x0003

Area: Configuration

Defining reference: [\[MS-OXOCFG\]](#) section 2.2.9.5

Alternate names: PR_WLINK_TYPE

3 Structure Examples

None.

Preliminary

4 Security Considerations

There are no security considerations unique to this specification.

Preliminary

5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft® Exchange Server 2003
- Microsoft® Exchange Server 2007
- Microsoft® Exchange Server 2010
- Microsoft® Exchange Server 15 Technical Preview
- Microsoft® Office Outlook® 2003
- Microsoft® Office Outlook® 2007
- Microsoft® Outlook® 2010
- Microsoft® Outlook® 15 Technical Preview

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

6 Change Tracking

This section identifies changes that were made to the [MS-OXPROPS] protocol document between the January 2012 and April 2012 releases. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- An extensive rewrite, addition, or deletion of major portions of content.
- The removal of a document from the documentation set.
- Changes made for template compliance.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the language and formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical or language changes were introduced. The technical content of the document is identical to the last released version, but minor editorial and formatting changes, as well as updates to the header and footer information, and to the revision summary, may have been made.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.

- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- New content added for template compliance.
- Content updated for template compliance.
- Content removed for template compliance.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact protocol@microsoft.com.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
1.3.2 Commonly Used Property Sets	Added new property set GUID for extracted entity named properties.	Y	New content added.
2.54 PidLidClassificationGuid	Added [MS-OXCMAIL] as the defining reference; added the property description; removed [MS-OXCMAIL] as a consuming reference.	N	Content updated.
2.55 PidLidClassificationKeep	Added [MS-OXCMAIL] as the defining reference; added the property description; removed [MS-OXCMAIL] as a consuming reference.	N	Content updated.
2.103 PidLidEmail1OriginalDisplayName	Added Email1OriginalDisplayName and EXSCHEMA_MAPI_EMAIL1ORIGINALDISPLAYNAME as additional alternate names.	N	Content updated.
2.466 PidNameExtractedAddresses	Added new section.	Y	New content added.
2.467 PidNameExtractedContacts	Added new section.	Y	New content added.
2.468 PidNameExtractedEmails	Added new section.	Y	New content added.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.469 PidNameExtractedMeetings	Added new section.	Y	New content added.
2.470 PidNameExtractedPhones	Added new section.	Y	New content added.
2.471 PidNameExtractedTasks	Added new section.	Y	New content added.
2.472 PidNameExtractedUrls	Added new section.	Y	New content added.
2.525 PidNameQuarantineOriginalSender	Added [MS-OXCMAIL] as the defining reference; added the property description; removed [MS-OXCMAIL] as a consuming reference.	N	Content updated .
2.596 PidTagAddressBookExtensionAttribute1	Revised the property description.	N	Content updated .
2.597 PidTagAddressBookExtensionAttribute2	Revised the property description.	N	Content updated .
2.598 PidTagAddressBookExtensionAttribute3	Revised the property description.	N	Content updated .
2.599 PidTagAddressBookExtensionAttribute4	Revised the property description.	N	Content updated .
2.600 PidTagAddressBookExtensionAttribute5	Revised the property description.	N	Content updated .
2.601 PidTagAddressBookExtensionAttribute6	Revised the property description.	N	Content updated .
2.602 PidTagAddressBookExtensionAttribute7	Revised the property description.	N	Content updated .
2.603 PidTagAddressBookExtensionAttribute8	Revised the property description.	N	Content updated .
2.604 PidTagAddressBookExtensionAttribute9	Revised the property description.	N	Content updated

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
			.
2.605 PidTagAddressBookExtensionAttribute10	Revised the property description.	N	Content updated.
2.606 PidTagAddressBookExtensionAttribute11	Revised the property description.	N	Content updated.
2.607 PidTagAddressBookExtensionAttribute12	Revised the property description.	N	Content updated.
2.608 PidTagAddressBookExtensionAttribute13	Revised the property description.	N	Content updated.
2.609 PidTagAddressBookExtensionAttribute14	Revised the property description.	N	Content updated.
2.610 PidTagAddressBookExtensionAttribute15	Revised the property description.	N	Content updated.
2.622 PidTagAddressBookManager	Changed the property data type from PtypEmbeddedTable to PtypObject.	Y	Content updated.
2.624 PidTagAddressBookMember	Revised data type from PtypMultipleString8 to PtypEmbeddedTable.	N	Content updated.
2.777 PidTagFreeBusyEntryIds	Revised the defining reference to be [MS-OXOSFLD] section 2.2.6 and removed [MS-OXOSFLD] from the list of consuming references.	N	Content updated.
2.879 PidTagNonReceiptNotificationRequested	Added section describing the PidTagNonReceiptNotificationRequested property.	Y	New content added.
2.884 PidTagOfflineAddressBookContainerGuid	Removed [MS-OXPFOAB] as a consuming reference.	N	Content updated.
2.885 PidTagOfflineAddressBookDistinguishedName	Removed [MS-OXPFOAB] as a consuming reference.	N	Content updated.
2.887 PidTagOfflineAddressBookName	Removed [MS-OXPFOAB] as a consuming reference.	N	Content updated.

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
2.888 PidTagOfflineAddressBookSequence	Removed [MS-OXPFOAB] as a consuming reference.	N	Content updated.
2.892 PidTagOriginalAuthorEntryId	Added section to describe the PidTagOriginalAuthorEntryId property.	Y	New content added.
2.893 PidTagOriginalAuthorName	Added section to describe the PidTagOriginalAuthorName property.	Y	New content added.
2.927 PidTagParentEntryId	Moved [MS-OXPFOAB] from the defining reference to a consuming reference, and moved [MS-OXCFOAD] from consuming reference to defining reference.	N	Content updated.
2.988 PidTagReportDisposition	Added section to describe the PidTagReportDisposition property.	Y	New content added.
2.989 PidTagReportDispositionMode	Added section to describe the PidTagReportDispositionMode property.	Y	New content added.
2.1087 PidTagSortLocaleId	Added [MS-OXCSTOR] as the defining reference; moved [MS-OXPFOAB] to consuming reference.	N	Content updated.
	Removed the following sections: PidTagSenderFlags, PidTagReceivedByFlags, PidTagReceivedRepresentingFlags, PidNameApprovalAllowedDecisionMakers, PidNameApprovalRequestor, PidNameAuthenticatedAs.	Y	Content removed.
	Removed the following sections: PidNameAuthenticatedDomain, PidNameAuthenticatedMechanism, PidNameAuthenticatedSource, PidNameOriginalSpamConfidenceLevel, PidNameOutlookProtectionRuleOverridden.	Y	Content removed.
	Removed the following sections: PidNameOutlookProtectionRuleTimestamp, PidNameOutlookProtectionRuleVersion, PidNameRightsProtectMessage.	Y	Content removed.
	Removed the following property sections: PidTagReportingMessageTransferAgent, PidTagContentFilterPhishingConfidenceLevel, PidTagRemoteMessageTransferAgent, and PidTagSessionInitiationProtocolUri.	Y	Content removed.
	Removed property section	Y	Content

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
	PidTagSecureSubmitFlags.		removed.

Preliminary

7 Index

A

[Applicability](#) 39

[Vendor-extensible fields](#) 39
[Versioning](#) 39

C

[Change tracking](#) 416

E

[Examples](#) 413

F

[Fields - vendor-extensible](#) 39

G

[Glossary](#) 27

I

[Implementer - security considerations](#) 414

[Informative references](#) 32

[Introduction](#) 27

L

[Localization](#) 39

N

[Normative references](#) 30

O

[Overview \(synopsis\)](#) 33

P

[Product behavior](#) 415

R

[References](#) 30

[informative](#) 32

[normative](#) 30

[Relationship to protocols and other structures](#) 38

S

[Security - implementer considerations](#) 414

T

[Tracking changes](#) 416

V