

# [MS-OXPROPS]: Exchange Server Protocols Master Property List

---

## Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation for protocols, file formats, languages, standards as well as overviews of the interaction among each of these technologies.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you may make copies of it in order to develop implementations of the technologies described in the Open Specifications and may distribute portions of it in your implementations using these technologies or your documentation as necessary to properly document the implementation. You may also distribute in your implementation, with or without modification, any schema, IDL's, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that may cover your implementations of the technologies described in the Open Specifications. Neither this notice nor Microsoft's delivery of the documentation grants any licenses under those or any other Microsoft patents. However, a given Open Specification may be covered by Microsoft [Open Specification Promise](#) or the [Community Promise](#). If you would prefer a written license, or if the technologies described in the Open Specifications are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation may be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications do not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments you are free to take advantage of them. Certain Open Specifications are intended for use in conjunction with publicly available standard specifications and network programming art, and assumes that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
04/04/2008	0.1		Initial Availability.
04/25/2008	0.2		Revised and updated property names and other technical content.
06/27/2008	1.0		Initial Release.
08/06/2008	1.01		Updated references to reflect date of initial release.
09/03/2008	1.02		Changed title of document.
10/01/2008	1.03		Revised and edited technical content.
12/03/2008	1.04		Revised and edited technical content.
02/04/2009	1.05		Revised and edited technical content.
03/04/2009	1.06		Revised and edited technical content.
04/10/2009	2.0		Updated technical content and applicable product releases.
07/15/2009	3.0	Major	Revised and edited for technical content.
11/04/2009	4.0.0	Major	Updated and revised the technical content.
02/10/2010	5.0.0	Major	Updated and revised the technical content.
05/05/2010	6.0.0	Major	Updated and revised the technical content.
08/04/2010	7.0	Major	Significantly changed the technical content.
11/03/2010	8.0	Major	Significantly changed the technical content.
03/18/2011	9.0	Major	Significantly changed the technical content.
08/05/2011	10.0	Major	Significantly changed the technical content.
10/07/2011	11.0	Major	Significantly changed the technical content.
01/20/2012	12.0	Major	Significantly changed the technical content.
04/27/2012	13.0	Major	Significantly changed the technical content.
07/16/2012	13.1	Minor	Clarified the meaning of the technical content.
10/08/2012	14.0	Major	Significantly changed the technical content.
02/11/2013	15.0	Major	Significantly changed the technical content.
07/26/2013	16.0	Major	Significantly changed the technical content.
11/18/2013	16.0	No change	No changes to the meaning, language, or formatting of

Date	Revision History	Revision Class	Comments
			the technical content.

# Table of Contents

<b>1 Introduction</b>	<b>25</b>
1.1 Glossary	25
1.2 References	28
1.2.1 Normative References	28
1.2.2 Informative References	30
1.3 Overview	30
1.3.1 Common Message Classes	32
1.3.2 Commonly Used Property Sets	33
1.3.3 Property ID Ranges	34
1.3.4 WebDAV Property Naming	35
1.3.4.1 http://schemas.microsoft.com/mapi/proptag Namespace	35
1.3.4.2 http://schemas.microsoft.com/mapi/id Namespace	36
1.3.4.3 http://schemas.microsoft.com/mapi/string Namespace	36
1.4 Relationship to Protocols and Other Structures	36
1.5 Applicability Statement	37
1.6 Versioning and Localization	37
1.7 Vendor-Extensible Fields	37
<b>2 Structures</b>	<b>38</b>
2.1 PidLidAddressBookProviderArrayType	38
2.2 PidLidAddressBookProviderEmailList	38
2.3 PidLidAddressCountryCode	38
2.4 PidLidAgingDontAgeMe	39
2.5 PidLidAllAttendeesString	39
2.6 PidLidAllowExternalCheck	39
2.7 PidLidAnniversaryEventEntryId	40
2.8 PidLidAppointmentAuxiliaryFlags	40
2.9 PidLidAppointmentColor	40
2.10 PidLidAppointmentCounterProposal	41
2.11 PidLidAppointmentDuration	41
2.12 PidLidAppointmentEndDate	41
2.13 PidLidAppointmentEndTime	42
2.14 PidLidAppointmentEndWhole	42
2.15 PidLidAppointmentLastSequence	42
2.16 PidLidAppointmentMessageClass	43
2.17 PidLidAppointmentNotAllowPropose	43
2.18 PidLidAppointmentProposalNumber	43
2.19 PidLidAppointmentProposedDuration	44
2.20 PidLidAppointmentProposedEndWhole	44
2.21 PidLidAppointmentProposedStartWhole	44
2.22 PidLidAppointmentRecur	45
2.23 PidLidAppointmentReplyName	45
2.24 PidLidAppointmentReplyTime	45
2.25 PidLidAppointmentSequence	46
2.26 PidLidAppointmentSequenceTime	46
2.27 PidLidAppointmentStartDate	47
2.28 PidLidAppointmentStartTime	47
2.29 PidLidAppointmentStartWhole	47
2.30 PidLidAppointmentStateFlags	48
2.31 PidLidAppointmentSubType	48

2.32	PidLidAppointmentTimeZoneDefinitionEndDisplay .....	48
2.33	PidLidAppointmentTimeZoneDefinitionRecur .....	49
2.34	PidLidAppointmentTimeZoneDefinitionStartDisplay .....	49
2.35	PidLidAppointmentUnsendableRecipients .....	49
2.36	PidLidAppointmentUpdateTime .....	50
2.37	PidLidAttendeeCriticalChange .....	50
2.38	PidLidAutoFillLocation .....	50
2.39	PidLidAutoLog .....	51
2.40	PidLidAutoProcessState .....	51
2.41	PidLidAutoStartCheck .....	51
2.42	PidLidBilling .....	52
2.43	PidLidBirthdayEventEntryId .....	52
2.44	PidLidBirthdayLocal .....	52
2.45	PidLidBusinessCardCardPicture .....	53
2.46	PidLidBusinessCardDisplayDefinition .....	53
2.47	PidLidBusyStatus .....	53
2.48	PidLidCalendarType .....	54
2.49	PidLidCategories .....	54
2.50	PidLidCcAttendeesString .....	54
2.51	PidLidChangeHighlight .....	55
2.52	PidLidClassification .....	55
2.53	PidLidClassificationDescription .....	55
2.54	PidLidClassificationGuid .....	56
2.55	PidLidClassificationKeep .....	56
2.56	PidLidClassified .....	56
2.57	PidLidCleanGlobalObjectId .....	57
2.58	PidLidClientIntent .....	57
2.59	PidLidClipEnd .....	58
2.60	PidLidClipStart .....	58
2.61	PidLidCollaborateDoc .....	58
2.62	PidLidCommonEnd .....	59
2.63	PidLidCommonStart .....	59
2.64	PidLidCompanies .....	59
2.65	PidLidConferencingCheck .....	60
2.66	PidLidConferencingType .....	60
2.67	PidLidContactCharacterSet .....	60
2.68	PidLidContactItemData .....	61
2.69	PidLidContactLinkedGlobalAddressListEntryId .....	61
2.70	PidLidContactLinkEntry .....	61
2.71	PidLidContactLinkGlobalAddressListLinkId .....	62
2.72	PidLidContactLinkGlobalAddressListLinkState .....	62
2.73	PidLidContactLinkLinkRejectHistory .....	62
2.74	PidLidContactLinkName .....	62
2.75	PidLidContactLinkSearchKey .....	63
2.76	PidLidContactLinkSMTPAddressCache .....	63
2.77	PidLidContacts .....	63
2.78	PidLidContactUserField1 .....	64
2.79	PidLidContactUserField2 .....	64
2.80	PidLidContactUserField3 .....	65
2.81	PidLidContactUserField4 .....	65
2.82	PidLidConversationActionLastAppliedTime .....	65
2.83	PidLidConversationActionMaxDeliveryTime .....	66
2.84	PidLidConversationActionMoveFolderEid .....	66

2.85	PidLidConversationActionMoveStoreEid	66
2.86	PidLidConversationActionVersion	67
2.87	PidLidConversationProcessed	67
2.88	PidLidCurrentVersion	67
2.89	PidLidCurrentVersionName	68
2.90	PidLidDayInterval	68
2.91	PidLidDayOfMonth	68
2.92	PidLidDelegateMail	69
2.93	PidLidDepartment	69
2.94	PidLidDirectory	69
2.95	PidLidDistributionListChecksum	70
2.96	PidLidDistributionListMembers	70
2.97	PidLidDistributionListName	70
2.98	PidLidDistributionListOneOffMembers	71
2.99	PidLidDistributionListStream	71
2.100	PidLidEmail1AddressType	71
2.101	PidLidEmail1DisplayName	72
2.102	PidLidEmail1EmailAddress	72
2.103	PidLidEmail1OriginalDisplayName	72
2.104	PidLidEmail1OriginalEntryId	73
2.105	PidLidEmail2AddressType	73
2.106	PidLidEmail2DisplayName	73
2.107	PidLidEmail2EmailAddress	74
2.108	PidLidEmail2OriginalDisplayName	74
2.109	PidLidEmail2OriginalEntryId	74
2.110	PidLidEmail3AddressType	75
2.111	PidLidEmail3DisplayName	75
2.112	PidLidEmail3EmailAddress	75
2.113	PidLidEmail3OriginalDisplayName	76
2.114	PidLidEmail3OriginalEntryId	76
2.115	PidLidEndRecurrenceDate	76
2.116	PidLidEndRecurrenceTime	77
2.117	PidLidExceptionReplaceTime	77
2.118	PidLidFax1AddressType	77
2.119	PidLidFax1EmailAddress	78
2.120	PidLidFax1OriginalDisplayName	78
2.121	PidLidFax1OriginalEntryId	78
2.122	PidLidFax2AddressType	79
2.123	PidLidFax2EmailAddress	79
2.124	PidLidFax2OriginalDisplayName	79
2.125	PidLidFax2OriginalEntryId	80
2.126	PidLidFax3AddressType	80
2.127	PidLidFax3EmailAddress	80
2.128	PidLidFax3OriginalDisplayName	80
2.129	PidLidFax3OriginalEntryId	81
2.130	PidLidFExceptionalAttendees	81
2.131	PidLidFExceptionalBody	81
2.132	PidLidFileUnder	82
2.133	PidLidFileUnderId	82
2.134	PidLidFileUnderList	82
2.135	PidLidFInvited	83
2.136	PidLidFlagRequest	83
2.137	PidLidFlagString	84

2.138	PidLidForwardInstance .....	84
2.139	PidLidForwardNotificationRecipients .....	84
2.140	PidLidFOthersAppointment.....	85
2.141	PidLidFreeBusyLocation .....	85
2.142	PidLidGlobalObjectId.....	85
2.143	PidLidHasPicture.....	86
2.144	PidLidHomeAddress .....	86
2.145	PidLidHomeAddressCountryCode .....	86
2.146	PidLidHtml.....	87
2.147	PidLidICalendarDayOfWeekMask .....	87
2.148	PidLidInboundICalStream .....	87
2.149	PidLidInfoPathFormName .....	88
2.150	PidLidInstantMessagingAddress.....	88
2.151	PidLidIntendedBusyStatus .....	88
2.152	PidLidInternetAccountName.....	89
2.153	PidLidInternetAccountStamp.....	89
2.154	PidLidIsContactLinked .....	89
2.155	PidLidIsException .....	90
2.156	PidLidIsRecurring .....	90
2.157	PidLidIsSilent.....	90
2.158	PidLidLinkedTaskItems.....	91
2.159	PidLidLocation.....	91
2.160	PidLidLogDocumentPosted .....	91
2.161	PidLidLogDocumentPrinted .....	92
2.162	PidLidLogDocumentRouted .....	92
2.163	PidLidLogDocumentSaved .....	92
2.164	PidLidLogDuration .....	93
2.165	PidLidLogEnd .....	93
2.166	PidLidLogFlags .....	93
2.167	PidLidLogStart .....	94
2.168	PidLidLogType.....	94
2.169	PidLidLogTypeDesc.....	94
2.170	PidLidMeetingType.....	95
2.171	PidLidMeetingWorkspaceUrl .....	95
2.172	PidLidMonthInterval.....	95
2.173	PidLidMonthOfYear .....	96
2.174	PidLidMonthOfYearMask .....	96
2.175	PidLidNetShowUrl.....	96
2.176	PidLidNoEndDateFlag .....	97
2.177	PidLidNonSendableBcc .....	97
2.178	PidLidNonSendableCc.....	97
2.179	PidLidNonSendableTo.....	98
2.180	PidLidNonSendBccTrackStatus .....	98
2.181	PidLidNonSendCcTrackStatus.....	98
2.182	PidLidNonSendToTrackStatus.....	99
2.183	PidLidNoteColor.....	99
2.184	PidLidNoteHeight.....	99
2.185	PidLidNoteWidth.....	100
2.186	PidLidNoteX.....	100
2.187	PidLidNoteY .....	100
2.188	PidLidOccurrences .....	101
2.189	PidLidOldLocation .....	101
2.190	PidLidOldRecurrenceType .....	101

2.191	PidLidOldWhenEndWhole	102
2.192	PidLidOldWhenStartWhole	102
2.193	PidLidOnlinePassword	102
2.194	PidLidOptionalAttendees	103
2.195	PidLidOrganizerAlias	103
2.196	PidLidOriginalStoreEntryId	103
2.197	PidLidOtherAddress	104
2.198	PidLidOtherAddressCountryCode	104
2.199	PidLidOwnerCriticalChange	104
2.200	PidLidOwnerName	105
2.201	PidLidPendingStateForSiteMailboxDocument	105
2.202	PidLidPercentComplete	105
2.203	PidLidPostalAddressId	106
2.204	PidLidPostRssChannel	106
2.205	PidLidPostRssChannelLink	106
2.206	PidLidPostRssItemGuid	107
2.207	PidLidPostRssItemHash	107
2.208	PidLidPostRssItemLink	107
2.209	PidLidPostRssItemXml	108
2.210	PidLidPostRssSubscription	108
2.211	PidLidPrivate	108
2.212	PidLidPromptSendUpdate	109
2.213	PidLidRecurrenceDuration	109
2.214	PidLidRecurrencePattern	109
2.215	PidLidRecurrenceType	110
2.216	PidLidRecurring	110
2.217	PidLidReferenceEntryId	110
2.218	PidLidReminderDelta	111
2.219	PidLidReminderFileParameter	111
2.220	PidLidReminderOverride	112
2.221	PidLidReminderPlaySound	112
2.222	PidLidReminderSet	112
2.223	PidLidReminderSignalTime	113
2.224	PidLidReminderTime	113
2.225	PidLidReminderTimeDate	113
2.226	PidLidReminderTimeTime	114
2.227	PidLidReminderType	114
2.228	PidLidRemoteStatus	115
2.229	PidLidRequiredAttendees	115
2.230	PidLidResourceAttendees	115
2.231	PidLidResponseStatus	116
2.232	PidLidServerProcessed	116
2.233	PidLidServerProcessingActions	116
2.234	PidLidSharingAnonymity	117
2.235	PidLidSharingBindingEntryId	117
2.236	PidLidSharingBrowseUrl	117
2.237	PidLidSharingCapabilities	118
2.238	PidLidSharingConfigurationUrl	118
2.239	PidLidSharingDataRangeEnd	118
2.240	PidLidSharingDataRangeStart	119
2.241	PidLidSharingDetail	119
2.242	PidLidSharingExtensionXml	119
2.243	PidLidSharingFilter	120



2.244	PidLidSharingFlags	120
2.245	PidLidSharingFlavor	120
2.246	PidLidSharingFolderEntryId	121
2.247	PidLidSharingIndexEntryId	121
2.248	PidLidSharingInitiatorEntryId	121
2.249	PidLidSharingInitiatorName	122
2.250	PidLidSharingInitiatorSmtp	122
2.251	PidLidSharingInstanceGuid	122
2.252	PidLidSharingLastAutoSyncTime	123
2.253	PidLidSharingLastSyncTime	123
2.254	PidLidSharingLocalComment	123
2.255	PidLidSharingLocalLastModificationTime	124
2.256	PidLidSharingLocalName	124
2.257	PidLidSharingLocalPath	124
2.258	PidLidSharingLocalStoreUid	125
2.259	PidLidSharingLocalType	125
2.260	PidLidSharingLocalUid	125
2.261	PidLidSharingOriginalMessageEntryId	126
2.262	PidLidSharingParentBindingEntryId	126
2.263	PidLidSharingParticipants	126
2.264	PidLidSharingPermissions	127
2.265	PidLidSharingProviderExtension	127
2.266	PidLidSharingProviderGuid	127
2.267	PidLidSharingProviderName	128
2.268	PidLidSharingProviderUrl	128
2.269	PidLidSharingRangeEnd	128
2.270	PidLidSharingRangeStart	129
2.271	PidLidSharingReciprocation	129
2.272	PidLidSharingRemoteByteSize	129
2.273	PidLidSharingRemoteComment	130
2.274	PidLidSharingRemoteCrc	130
2.275	PidLidSharingRemoteLastModificationTime	130
2.276	PidLidSharingRemoteMessageCount	131
2.277	PidLidSharingRemoteName	131
2.278	PidLidSharingRemotePass	131
2.279	PidLidSharingRemotePath	132
2.280	PidLidSharingRemoteStoreUid	132
2.281	PidLidSharingRemoteType	132
2.282	PidLidSharingRemoteUid	133
2.283	PidLidSharingRemoteUser	133
2.284	PidLidSharingRemoteVersion	133
2.285	PidLidSharingResponseTime	134
2.286	PidLidSharingResponseType	134
2.287	PidLidSharingRoamLog	134
2.288	PidLidSharingStart	135
2.289	PidLidSharingStatus	135
2.290	PidLidSharingStop	135
2.291	PidLidSharingSyncFlags	136
2.292	PidLidSharingSyncInterval	136
2.293	PidLidSharingTimeToLive	136
2.294	PidLidSharingTimeToLiveAuto	137
2.295	PidLidSharingWorkingHoursDays	137
2.296	PidLidSharingWorkingHoursEnd	137

2.297	PidLidSharingWorkingHoursStart	138
2.298	PidLidSharingWorkingHoursTimeZone	138
2.299	PidLidSideEffects	138
2.300	PidLidSingleBodyICal	139
2.301	PidLidSmartNoAttach	139
2.302	PidLidSpamOriginalFolder	139
2.303	PidLidStartRecurrenceDate	140
2.304	PidLidStartRecurrenceTime	140
2.305	PidLidTaskAcceptanceState	140
2.306	PidLidTaskAccepted	141
2.307	PidLidTaskActualEffort	141
2.308	PidLidTaskAssigner	141
2.309	PidLidTaskAssigners	142
2.310	PidLidTaskComplete	142
2.311	PidLidTaskCustomFlags	142
2.312	PidLidTaskDateCompleted	143
2.313	PidLidTaskDeadOccurrence	143
2.314	PidLidTaskDueDate	143
2.315	PidLidTaskEstimatedEffort	144
2.316	PidLidTaskFCreator	144
2.317	PidLidTaskFFixOffline	144
2.318	PidLidTaskFREcurring	145
2.319	PidLidTaskGlobalId	145
2.320	PidLidTaskHistory	145
2.321	PidLidTaskLastDelegate	146
2.322	PidLidTaskLastUpdate	146
2.323	PidLidTaskLastUser	146
2.324	PidLidTaskMode	147
2.325	PidLidTaskMultipleRecipients	147
2.326	PidLidTaskNoCompute	147
2.327	PidLidTaskOrdinal	148
2.328	PidLidTaskOwner	148
2.329	PidLidTaskOwnership	148
2.330	PidLidTaskRecurrence	149
2.331	PidLidTaskResetReminder	149
2.332	PidLidTaskRole	149
2.333	PidLidTaskStartDate	150
2.334	PidLidTaskState	150
2.335	PidLidTaskStatus	151
2.336	PidLidTaskStatusOnComplete	151
2.337	PidLidTaskUpdates	151
2.338	PidLidTaskVersion	152
2.339	PidLidTeamTask	152
2.340	PidLidTimeZone	152
2.341	PidLidTimeZoneDescription	153
2.342	PidLidTimeZoneStruct	153
2.343	PidLidToAttendeesString	153
2.344	PidLidToDoOrdinalDate	154
2.345	PidLidToDoSubOrdinal	154
2.346	PidLidToDoTitle	154
2.347	PidLidUseTnef	155
2.348	PidLidValidFlagStringProof	155
2.349	PidLidVerbResponse	155

2.350	PidLidVerbStream.....	156
2.351	PidLidWeddingAnniversaryLocal .....	156
2.352	PidLidWeekInterval.....	156
2.353	PidLidWhere .....	157
2.354	PidLidWorkAddress .....	157
2.355	PidLidWorkAddressCity.....	158
2.356	PidLidWorkAddressCountry .....	158
2.357	PidLidWorkAddressCountryCode .....	158
2.358	PidLidWorkAddressPostalCode.....	159
2.359	PidLidWorkAddressPostOfficeBox .....	159
2.360	PidLidWorkAddressState.....	159
2.361	PidLidWorkAddressStreet .....	160
2.362	PidLidYearInterval .....	160
2.363	PidLidYomiCompanyName .....	160
2.364	PidLidYomiFirstName .....	161
2.365	PidLidYomiLastName.....	161
2.366	PidNameAcceptLanguage .....	161
2.367	PidNameApplicationName .....	162
2.368	PidNameAttachmentMacContentType .....	162
2.369	PidNameAttachmentMacInfo .....	162
2.370	PidNameAudioNotes .....	163
2.371	PidNameAuthor .....	163
2.372	PidNameAutomaticSpeechRecognitionData .....	163
2.373	PidNameByteCount.....	163
2.374	PidNameCalendarAttendeeRole .....	164
2.375	PidNameCalendarBusystatus.....	164
2.376	PidNameCalendarContact .....	164
2.377	PidNameCalendarContactUrl .....	165
2.378	PidNameCalendarCreated .....	165
2.379	PidNameCalendarDescriptionUrl .....	165
2.380	PidNameCalendarDuration .....	166
2.381	PidNameCalendarExceptionDate.....	166
2.382	PidNameCalendarExceptionRule .....	166
2.383	PidNameCalendarGeoLatitude .....	167
2.384	PidNameCalendarGeoLongitude.....	167
2.385	PidNameCalendarInstanceType .....	167
2.386	PidNameCalendarIsOrganizer.....	167
2.387	PidNameCalendarLastModified .....	168
2.388	PidNameCalendarLocationUrl .....	168
2.389	PidNameCalendarMeetingStatus .....	168
2.390	PidNameCalendarMethod.....	169
2.391	PidNameCalendarProductId .....	169
2.392	PidNameCalendarRecurrenceIdRange.....	169
2.393	PidNameCalendarReminderOffset .....	170
2.394	PidNameCalendarResources.....	170
2.395	PidNameCalendarRsvp .....	170
2.396	PidNameCalendarSequence .....	171
2.397	PidNameCalendarTimeZone .....	171
2.398	PidNameCalendarTimeZoneId .....	171
2.399	PidNameCalendarTransparent .....	171
2.400	PidNameCalendarUid .....	172
2.401	PidNameCalendarVersion .....	172
2.402	PidNameCategory.....	172

2.403	PidNameCharacterCount .....	173
2.404	PidNameComments .....	173
2.405	PidNameCompany .....	173
2.406	PidNameContentBase.....	174
2.407	PidNameContentClass .....	174
2.408	PidNameContentType.....	174
2.409	PidNameCreateDateTimeReadOnly .....	175
2.410	PidNameCrossReference.....	175
2.411	PidNameDavId .....	175
2.412	PidNameDavIsCollection.....	176
2.413	PidNameDavIsStructuredDocument .....	176
2.414	PidNameDavParentName.....	176
2.415	PidNameDavUid .....	177
2.416	PidNameDocumentParts .....	177
2.417	PidNameEditTime .....	177
2.418	PidNameExchangeIntendedBusyStatus.....	177
2.419	PidNameExchangeJunkEmailMoveStamp .....	178
2.420	PidNameExchangeModifyExceptionStructure .....	178
2.421	PidNameExchangeNoModifyExceptions .....	178
2.422	PidNameExchangePatternEnd .....	179
2.423	PidNameExchangePatternStart.....	179
2.424	PidNameExchangeReminderInterval .....	179
2.425	PidNameExchDatabaseSchema .....	180
2.426	PidNameExchDataExpectedContentClass .....	180
2.427	PidNameExchDataSchemaCollectionReference .....	180
2.428	PidNameExtractedAddresses .....	181
2.429	PidNameExtractedContacts.....	181
2.430	PidNameExtractedEmails .....	181
2.431	PidNameExtractedMeetings.....	182
2.432	PidNameExtractedPhones .....	182
2.433	PidNameExtractedTasks .....	182
2.434	PidNameExtractedUrls.....	182
2.435	PidNameFrom .....	183
2.436	PidNameHeadingPairs .....	183
2.437	PidNameHiddenCount .....	183
2.438	PidNameHttpmailCalendar .....	184
2.439	PidNameHttpmailHtmlDescription .....	184
2.440	PidNameHttpmailSendMessage .....	184
2.441	PidNameICalendarRecurrenceDate .....	185
2.442	PidNameICalendarRecurrenceRule .....	185
2.443	PidNameInternetSubject .....	185
2.444	PidNameKeywords.....	186
2.445	PidNameLastAuthor .....	186
2.446	PidNameLastPrinted.....	186
2.447	PidNameLastSaveDateTime .....	187
2.448	PidNameLineCount .....	187
2.449	PidNameLinksDirty .....	187
2.450	PidNameLocationUrl.....	187
2.451	PidNameManager .....	188
2.452	PidNameMultimediaClipCount.....	188
2.453	PidNameNoteCount .....	188
2.454	PidNameOMSAccountGuid .....	189
2.455	PidNameOMSMobileModel.....	189

2.456	PidNameOMSScheduleTime .....	189
2.457	PidNameOMSServiceType .....	190
2.458	PidNameOMSSourceType .....	190
2.459	PidNamePageCount .....	190
2.460	PidNameParagraphCount .....	190
2.461	PidNamePhishingStamp .....	191
2.462	PidNamePresentationFormat .....	191
2.463	PidNameQuarantineOriginalSender .....	191
2.464	PidNameRevisionNumber .....	192
2.465	PidNameRightsManagementLicense .....	192
2.466	PidNameScale .....	192
2.467	PidNameSecurity .....	192
2.468	PidNameSlideCount .....	193
2.469	PidNameSubject .....	193
2.470	PidNameTemplate .....	193
2.471	PidNameThumbnail .....	194
2.472	PidNameTitle .....	194
2.473	PidNameWordCount .....	194
2.474	PidNameXCallId .....	195
2.475	PidNameXFaxNumberOfPages .....	195
2.476	PidNameXRequireProtectedPlayOnPhone .....	195
2.477	PidNameXSenderTelephoneNumber .....	195
2.478	PidNameXSharingBrowseUrl .....	196
2.479	PidNameXSharingCapabilities .....	196
2.480	PidNameXSharingConfigUrl .....	196
2.481	PidNameXSharingExendedCaps .....	197
2.482	PidNameXSharingFlavor .....	197
2.483	PidNameXSharingInstanceGuid .....	197
2.484	PidNameXSharingLocalType .....	198
2.485	PidNameXSharingProviderGuid .....	198
2.486	PidNameXSharingProviderName .....	198
2.487	PidNameXSharingProviderUrl .....	198
2.488	PidNameXSharingRemoteName .....	199
2.489	PidNameXSharingRemotePath .....	199
2.490	PidNameXSharingRemoteStoreUid .....	199
2.491	PidNameXSharingRemoteType .....	200
2.492	PidNameXSharingRemoteUid .....	200
2.493	PidNameXVoiceMessageAttachmentOrder .....	200
2.494	PidNameXVoiceMessageDuration .....	200
2.495	PidNameXVoiceMessageSenderName .....	201
2.496	PidTagAccess .....	201
2.497	PidTagAccessControlListData .....	201
2.498	PidTagAccessLevel .....	202
2.499	PidTagAccount .....	202
2.500	PidTagAdditionalRenEntryIds .....	202
2.501	PidTagAdditionalRenEntryIdsEx .....	203
2.502	PidTagAddressBookAuthorizedSenders .....	203
2.503	PidTagAddressBookContainerId .....	203
2.504	PidTagAddressBookDeliveryContentLength .....	204
2.505	PidTagAddressBookDisplayNamePrintable .....	204
2.506	PidTagAddressBookDisplayTypeExtended .....	204
2.507	PidTagAddressBookDistributionListExternalMemberCount .....	205
2.508	PidTagAddressBookDistributionListMemberCount .....	205

2.509	PidTagAddressBookDistributionListMemberSubmitAccepted	205
2.510	PidTagAddressBookDistributionListMemberSubmitRejected	206
2.511	PidTagAddressBookDistributionListRejectMessagesFromDLMembers	206
2.512	PidTagAddressBookEntryId	206
2.513	PidTagAddressBookExtensionAttribute1	206
2.514	PidTagAddressBookExtensionAttribute10	207
2.515	PidTagAddressBookExtensionAttribute11	207
2.516	PidTagAddressBookExtensionAttribute12	207
2.517	PidTagAddressBookExtensionAttribute13	208
2.518	PidTagAddressBookExtensionAttribute14	208
2.519	PidTagAddressBookExtensionAttribute15	208
2.520	PidTagAddressBookExtensionAttribute2	209
2.521	PidTagAddressBookExtensionAttribute3	209
2.522	PidTagAddressBookExtensionAttribute4	209
2.523	PidTagAddressBookExtensionAttribute5	210
2.524	PidTagAddressBookExtensionAttribute6	210
2.525	PidTagAddressBookExtensionAttribute7	210
2.526	PidTagAddressBookExtensionAttribute8	210
2.527	PidTagAddressBookExtensionAttribute9	211
2.528	PidTagAddressBookFolderPathname	211
2.529	PidTagAddressBookHierarchicalChildDepartments	211
2.530	PidTagAddressBookHierarchicalDepartmentMembers	212
2.531	PidTagAddressBookHierarchicalIsHierarchicalGroup	212
2.532	PidTagAddressBookHierarchicalParentDepartment	212
2.533	PidTagAddressBookHierarchicalRootDepartment	213
2.534	PidTagAddressBookHierarchicalShowInDepartments	213
2.535	PidTagAddressBookHomeMessageDatabase	213
2.536	PidTagAddressBookIsMaster	213
2.537	PidTagAddressBookIsMemberOfDistributionList	214
2.538	PidTagAddressBookManageDistributionList	214
2.539	PidTagAddressBookManager	214
2.540	PidTagAddressBookManagerDistinguishedName	215
2.541	PidTagAddressBookMember	215
2.542	PidTagAddressBookMessageId	215
2.543	PidTagAddressBookModerationEnabled	216
2.544	PidTagAddressBookNetworkAddress	216
2.545	PidTagAddressBookObjectDistinguishedName	216
2.546	PidTagAddressBookObjectGuid	217
2.547	PidTagAddressBookOrganizationalUnitRootDistinguishedName	217
2.548	PidTagAddressBookOwner	217
2.549	PidTagAddressBookOwnerBackLink	217
2.550	PidTagAddressBookParentEntryId	218
2.551	PidTagAddressBookPhoneticCompanyName	218
2.552	PidTagAddressBookPhoneticDepartmentName	218
2.553	PidTagAddressBookPhoneticDisplayName	219
2.554	PidTagAddressBookPhoneticGivenName	219
2.555	PidTagAddressBookPhoneticSurname	219
2.556	PidTagAddressBookProxyAddresses	220
2.557	PidTagAddressBookPublicDelegates	220
2.558	PidTagAddressBookReports	220
2.559	PidTagAddressBookRoomCapacity	221
2.560	PidTagAddressBookRoomContainers	221
2.561	PidTagAddressBookRoomDescription	221

2.562	PidTagAddressBookSenderHintTranslations.....	222
2.563	PidTagAddressBookSeniorityIndex.....	222
2.564	PidTagAddressBookTargetAddress.....	222
2.565	PidTagAddressBookUnauthorizedSenders.....	223
2.566	PidTagAddressBookX509Certificate.....	223
2.567	PidTagAddressType.....	223
2.568	PidTagAlternateRecipientAllowed.....	224
2.569	PidTagAnr.....	224
2.570	PidTagArchiveDate.....	224
2.571	PidTagArchivePeriod.....	224
2.572	PidTagArchiveTag.....	225
2.573	PidTagAssistant.....	225
2.574	PidTagAssistantTelephoneNumber.....	225
2.575	PidTagAssociated.....	226
2.576	PidTagAttachAdditionalInformation.....	226
2.577	PidTagAttachContentBase.....	226
2.578	PidTagAttachContentId.....	226
2.579	PidTagAttachContentLocation.....	227
2.580	PidTagAttachDataBinary.....	227
2.581	PidTagAttachDataObject.....	227
2.582	PidTagAttachEncoding.....	228
2.583	PidTagAttachExtension.....	228
2.584	PidTagAttachFilename.....	228
2.585	PidTagAttachFlags.....	229
2.586	PidTagAttachLongFilename.....	229
2.587	PidTagAttachLongPathname.....	229
2.588	PidTagAttachmentContactPhoto.....	230
2.589	PidTagAttachmentFlags.....	230
2.590	PidTagAttachmentHidden.....	230
2.591	PidTagAttachmentLinkId.....	231
2.592	PidTagAttachMethod.....	231
2.593	PidTagAttachMimeTag.....	231
2.594	PidTagAttachNumber.....	232
2.595	PidTagAttachPathname.....	232
2.596	PidTagAttachPayloadClass.....	232
2.597	PidTagAttachPayloadProviderGuidString.....	233
2.598	PidTagAttachRendering.....	233
2.599	PidTagAttachSize.....	233
2.600	PidTagAttachTag.....	234
2.601	PidTagAttachTransportName.....	234
2.602	PidTagAttributeHidden.....	234
2.603	PidTagAttributeReadOnly.....	235
2.604	PidTagAutoForwardComment.....	235
2.605	PidTagAutoForwarded.....	235
2.606	PidTagAutoResponseSuppress.....	236
2.607	PidTagBirthday.....	236
2.608	PidTagBlockStatus.....	236
2.609	PidTagBody.....	236
2.610	PidTagBodyContentId.....	237
2.611	PidTagBodyContentLocation.....	237
2.612	PidTagBodyHtml.....	237
2.613	PidTagBusiness2TelephoneNumber.....	238
2.614	PidTagBusiness2TelephoneNumbers.....	238

2.615	PidTagBusinessFaxNumber .....	238
2.616	PidTagBusinessHomePage .....	239
2.617	PidTagBusinessTelephoneNumber.....	239
2.618	PidTagCallbackTelephoneNumber .....	239
2.619	PidTagCallId .....	240
2.620	PidTagCarTelephoneNumber .....	240
2.621	PidTagCdoRecurrenceid .....	240
2.622	PidTagChangeKey.....	241
2.623	PidTagChangeNumber .....	241
2.624	PidTagChildrensNames.....	241
2.625	PidTagClientActions .....	242
2.626	PidTagClientSubmitTime .....	242
2.627	PidTagCodePageId.....	242
2.628	PidTagComment.....	243
2.629	PidTagCompanyMainTelephoneNumber .....	243
2.630	PidTagCompanyName .....	243
2.631	PidTagComputerNetworkName .....	244
2.632	PidTagConflictEntryId .....	244
2.633	PidTagContainerClass .....	244
2.634	PidTagContainerContents .....	245
2.635	PidTagContainerFlags.....	245
2.636	PidTagContainerHierarchy .....	245
2.637	PidTagContentCount .....	245
2.638	PidTagContentFilterSpamConfidenceLevel.....	246
2.639	PidTagContentUnreadCount .....	246
2.640	PidTagConversationId .....	246
2.641	PidTagConversationIndex .....	247
2.642	PidTagConversationIndexTracking .....	247
2.643	PidTagConversationTopic.....	247
2.644	PidTagCountry .....	248
2.645	PidTagCreationTime.....	248
2.646	PidTagCreatorEntryId .....	248
2.647	PidTagCreatorName .....	249
2.648	PidTagCustomerId .....	249
2.649	PidTagDamBackPatched .....	249
2.650	PidTagDamOriginalEntryId.....	250
2.651	PidTagDefaultPostMessageClass .....	250
2.652	PidTagDeferredActionMessageOriginalEntryId .....	250
2.653	PidTagDeferredDeliveryTime .....	250
2.654	PidTagDeferredSendNumber .....	251
2.655	PidTagDeferredSendTime .....	251
2.656	PidTagDeferredSendUnits .....	251
2.657	PidTagDelegatedByRule .....	252
2.658	PidTagDelegateFlags.....	252
2.659	PidTagDeleteAfterSubmit .....	252
2.660	PidTagDeletedCountTotal .....	252
2.661	PidTagDeletedOn.....	253
2.662	PidTagDeliverTime.....	253
2.663	PidTagDepartmentName .....	253
2.664	PidTagDepth .....	254
2.665	PidTagDisplayBcc .....	254
2.666	PidTagDisplayCc.....	254
2.667	PidTagDisplayName .....	255



2.668	PidTagDisplayNamePrefix .....	255
2.669	PidTagDisplayTo .....	255
2.670	PidTagDisplayType .....	256
2.671	PidTagDisplayTypeEx .....	256
2.672	PidTagEmailAddress .....	256
2.673	PidTagEndDate .....	257
2.674	PidTagEntryId .....	257
2.675	PidTagExceptionEndTime .....	257
2.676	PidTagExceptionReplaceTime .....	258
2.677	PidTagExceptionStartTime .....	258
2.678	PidTagExchangeNTSecurityDescriptor .....	258
2.679	PidTagExpiryNumber .....	259
2.680	PidTagExpiryTime .....	259
2.681	PidTagExpiryUnits .....	259
2.682	PidTagExtendedFolderFlags .....	260
2.683	PidTagExtendedRuleMessageActions .....	260
2.684	PidTagExtendedRuleMessageCondition .....	260
2.685	PidTagExtendedRuleSizeLimit .....	261
2.686	PidTagFaxNumberOfPages .....	261
2.687	PidTagFlagCompleteTime .....	261
2.688	PidTagFlagStatus .....	262
2.689	PidTagFlatUrlName .....	262
2.690	PidTagFolderAssociatedContents .....	262
2.691	PidTagFolderId .....	262
2.692	PidTagFolderType .....	263
2.693	PidTagFollowupIcon .....	263
2.694	PidTagFreeBusyCountMonths .....	263
2.695	PidTagFreeBusyEntryIds .....	264
2.696	PidTagFreeBusyMessageEmailAddress .....	264
2.697	PidTagFreeBusyPublishEnd .....	264
2.698	PidTagFreeBusyPublishStart .....	265
2.699	PidTagFreeBusyRangeTimestamp .....	265
2.700	PidTagFtpSite .....	265
2.701	PidTagGatewayNeedsToRefresh .....	265
2.702	PidTagGender .....	266
2.703	PidTagGeneration .....	266
2.704	PidTagGivenName .....	266
2.705	PidTagGovernmentIdNumber .....	267
2.706	PidTagHasAttachments .....	267
2.707	PidTagHasDeferredActionMessages .....	267
2.708	PidTagHasNamedProperties .....	268
2.709	PidTagHasRules .....	268
2.710	PidTagHierarchyChangeNumber .....	268
2.711	PidTagHobbies .....	268
2.712	PidTagHome2TelephoneNumber .....	269
2.713	PidTagHome2TelephoneNumbers .....	269
2.714	PidTagHomeAddressCity .....	269
2.715	PidTagHomeAddressCountry .....	270
2.716	PidTagHomeAddressPostalCode .....	270
2.717	PidTagHomeAddressPostOfficeBox .....	270
2.718	PidTagHomeAddressStateOrProvince .....	271
2.719	PidTagHomeAddressStreet .....	271
2.720	PidTagHomeFaxNumber .....	271

2.721	PidTagHomeTelephoneNumber.....	272
2.722	PidTagHtml.....	272
2.723	PidTagICalendarEndTime.....	272
2.724	PidTagICalendarReminderNextTime.....	273
2.725	PidTagICalendarStartTime.....	273
2.726	PidTagIconIndex.....	273
2.727	PidTagImportance.....	273
2.728	PidTagInConflict.....	274
2.729	PidTagInitialDetailsPane.....	274
2.730	PidTagInitials.....	274
2.731	PidTagInReplyToId.....	275
2.732	PidTagInstanceKey.....	275
2.733	PidTagInstanceNum.....	275
2.734	PidTagInstID.....	276
2.735	PidTagInternetCodepage.....	276
2.736	PidTagInternetMailOverrideFormat.....	276
2.737	PidTagInternetMessageId.....	277
2.738	PidTagInternetReferences.....	277
2.739	PidTagIpmAppointmentEntryId.....	277
2.740	PidTagIpmContactEntryId.....	278
2.741	PidTagIpmDraftsEntryId.....	278
2.742	PidTagIpmJournalEntryId.....	278
2.743	PidTagIpmNoteEntryId.....	278
2.744	PidTagIpmTaskEntryId.....	279
2.745	PidTagIsdnNumber.....	279
2.746	PidTagJunkAddRecipientsToSafeSendersList.....	279
2.747	PidTagJunkIncludeContacts.....	280
2.748	PidTagJunkPermanentlyDelete.....	280
2.749	PidTagJunkPhishingEnableLinks.....	280
2.750	PidTagJunkThreshold.....	281
2.751	PidTagKeyword.....	281
2.752	PidTagLanguage.....	281
2.753	PidTagLastModificationTime.....	281
2.754	PidTagLastModifierEntryId.....	282
2.755	PidTagLastModifierName.....	282
2.756	PidTagLastVerbExecuted.....	282
2.757	PidTagLastVerbExecutionTime.....	283
2.758	PidTagListHelp.....	283
2.759	PidTagListSubscribe.....	283
2.760	PidTagListUnsubscribe.....	284
2.761	PidTagLocalCommitTime.....	284
2.762	PidTagLocalCommitTimeMax.....	284
2.763	PidTagLocaleId.....	285
2.764	PidTagLocality.....	285
2.765	PidTagLocation.....	285
2.766	PidTagMailboxOwnerEntryId.....	286
2.767	PidTagMailboxOwnerName.....	286
2.768	PidTagManagerName.....	286
2.769	PidTagMappingSignature.....	287
2.770	PidTagMaximumSubmitMessageSize.....	287
2.771	PidTagMemberId.....	287
2.772	PidTagMemberName.....	287
2.773	PidTagMemberRights.....	288

2.774	PidTagMessageAttachments	288
2.775	PidTagMessageCcMe	288
2.776	PidTagMessageClass	289
2.777	PidTagMessageCodepage	289
2.778	PidTagMessageDeliveryTime	289
2.779	PidTagMessageEditorFormat	290
2.780	PidTagMessageFlags	290
2.781	PidTagMessageHandlingSystemCommonName	290
2.782	PidTagMessageLocaleId	291
2.783	PidTagMessageRecipientMe	291
2.784	PidTagMessageRecipients	291
2.785	PidTagMessageSize	292
2.786	PidTagMessageSizeExtended	292
2.787	PidTagMessageStatus	292
2.788	PidTagMessageSubmissionId	293
2.789	PidTagMessageToMe	293
2.790	PidTagMid	293
2.791	PidTagMiddleName	294
2.792	PidTagMimeSkeleton	294
2.793	PidTagMobileTelephoneNumber	294
2.794	PidTagNativeBody	295
2.795	PidTagNextSendAcct	295
2.796	PidTagNickname	295
2.797	PidTagNonDeliveryReportDiagCode	296
2.798	PidTagNonDeliveryReportReasonCode	296
2.799	PidTagNonDeliveryReportStatusCode	296
2.800	PidTagNonReceiptNotificationRequested	297
2.801	PidTagNormalizedSubject	297
2.802	PidTagObjectType	297
2.803	PidTagOfficeLocation	298
2.804	PidTagOfflineAddressBookContainerGuid	298
2.805	PidTagOfflineAddressBookDistinguishedName	298
2.806	PidTagOfflineAddressBookMessageClass	298
2.807	PidTagOfflineAddressBookName	299
2.808	PidTagOfflineAddressBookSequence	299
2.809	PidTagOfflineAddressBookTruncatedProperties	299
2.810	PidTagOrdinalMost	300
2.811	PidTagOrganizationalIdNumber	300
2.812	PidTagOriginalAuthorEntryId	300
2.813	PidTagOriginalAuthorName	300
2.814	PidTagOriginalDeliveryTime	301
2.815	PidTagOriginalDisplayBcc	301
2.816	PidTagOriginalDisplayCc	301
2.817	PidTagOriginalDisplayTo	302
2.818	PidTagOriginalEntryId	302
2.819	PidTagOriginalMessageClass	302
2.820	PidTagOriginalMessageId	303
2.821	PidTagOriginalSenderAddressType	303
2.822	PidTagOriginalSenderEmailAddress	303
2.823	PidTagOriginalSenderEntryId	304
2.824	PidTagOriginalSenderName	304
2.825	PidTagOriginalSenderSearchKey	304
2.826	PidTagOriginalSensitivity	304

2.827	PidTagOriginalSentRepresentingAddressType	305
2.828	PidTagOriginalSentRepresentingEmailAddress	305
2.829	PidTagOriginalSentRepresentingEntryId	305
2.830	PidTagOriginalSentRepresentingName	306
2.831	PidTagOriginalSentRepresentingSearchKey	306
2.832	PidTagOriginalSubject	306
2.833	PidTagOriginalSubmitTime	307
2.834	PidTagOriginatorDeliveryReportRequested	307
2.835	PidTagOriginatorNonDeliveryReportRequested	307
2.836	PidTagOscSyncEnabled	308
2.837	PidTagOtherAddressCity	308
2.838	PidTagOtherAddressCountry	308
2.839	PidTagOtherAddressPostalCode	309
2.840	PidTagOtherAddressPostOfficeBox	309
2.841	PidTagOtherAddressStateOrProvince	309
2.842	PidTagOtherAddressStreet	310
2.843	PidTagOtherTelephoneNumber	310
2.844	PidTagOutOfOfficeState	310
2.845	PidTagOwnerAppointmentId	310
2.846	PidTagPagerTelephoneNumber	311
2.847	PidTagParentEntryId	311
2.848	PidTagParentFolderId	311
2.849	PidTagParentKey	312
2.850	PidTagParentSourceKey	312
2.851	PidTagPersonalHomePage	312
2.852	PidTagPolicyTag	313
2.853	PidTagPostalAddress	313
2.854	PidTagPostalCode	313
2.855	PidTagPostOfficeBox	314
2.856	PidTagPredecessorChangeList	314
2.857	PidTagPrimaryFaxNumber	314
2.858	PidTagPrimarySendAccount	315
2.859	PidTagPrimaryTelephoneNumber	315
2.860	PidTagPriority	315
2.861	PidTagProcessed	316
2.862	PidTagProfession	316
2.863	PidTagProhibitReceiveQuota	316
2.864	PidTagProhibitSendQuota	316
2.865	PidTagPurportedSenderDomain	317
2.866	PidTagRadioTelephoneNumber	317
2.867	PidTagRead	317
2.868	PidTagReadReceiptAddressType	318
2.869	PidTagReadReceiptEmailAddress	318
2.870	PidTagReadReceiptEntryId	318
2.871	PidTagReadReceiptName	319
2.872	PidTagReadReceiptRequested	319
2.873	PidTagReadReceiptSearchKey	319
2.874	PidTagReadReceiptSmtAddress	320
2.875	PidTagReceiptTime	320
2.876	PidTagReceivedByAddressType	320
2.877	PidTagReceivedByEmailAddress	320
2.878	PidTagReceivedByEntryId	321
2.879	PidTagReceivedByName	321

2.880	PidTagReceivedBySearchKey .....	321
2.881	PidTagReceivedBySmtpAddress .....	322
2.882	PidTagReceivedRepresentingAddressType .....	322
2.883	PidTagReceivedRepresentingEmailAddress .....	322
2.884	PidTagReceivedRepresentingEntryId .....	323
2.885	PidTagReceivedRepresentingName .....	323
2.886	PidTagReceivedRepresentingSearchKey .....	323
2.887	PidTagReceivedRepresentingSmtpAddress .....	323
2.888	PidTagRecipientDisplayName .....	324
2.889	PidTagRecipientEntryId .....	324
2.890	PidTagRecipientFlags .....	324
2.891	PidTagRecipientOrder .....	325
2.892	PidTagRecipientProposed .....	325
2.893	PidTagRecipientProposedEndTime .....	325
2.894	PidTagRecipientProposedStartTime .....	326
2.895	PidTagRecipientReassignmentProhibited .....	326
2.896	PidTagRecipientTrackStatus .....	326
2.897	PidTagRecipientTrackStatusTime .....	326
2.898	PidTagRecipientType .....	327
2.899	PidTagRecordKey .....	327
2.900	PidTagReferredByName .....	327
2.901	PidTagRemindersOnlineEntryId .....	328
2.902	PidTagRemoteMessageTransferAgent .....	328
2.903	PidTagRenderingPosition .....	328
2.904	PidTagReplyRecipientEntries .....	329
2.905	PidTagReplyRecipientNames .....	329
2.906	PidTagReplyRequested .....	329
2.907	PidTagReplyTemplateId .....	330
2.908	PidTagReplyTime .....	330
2.909	PidTagReportDisposition .....	330
2.910	PidTagReportDispositionMode .....	331
2.911	PidTagReportEntryId .....	331
2.912	PidTagReportingMessageTransferAgent .....	331
2.913	PidTagReportName .....	331
2.914	PidTagReportSearchKey .....	332
2.915	PidTagReportTag .....	332
2.916	PidTagReportText .....	332
2.917	PidTagReportTime .....	333
2.918	PidTagResolveMethod .....	333
2.919	PidTagResponseRequested .....	333
2.920	PidTagResponsibility .....	334
2.921	PidTagRetentionDate .....	334
2.922	PidTagRetentionFlags .....	334
2.923	PidTagRetentionPeriod .....	334
2.924	PidTagRights .....	335
2.925	PidTagRoamingDatatypes .....	335
2.926	PidTagRoamingDictionary .....	335
2.927	PidTagRoamingXmlStream .....	336
2.928	PidTagRowid .....	336
2.929	PidTagRowType .....	336
2.930	PidTagRtfCompressed .....	336
2.931	PidTagRtfInSync .....	337
2.932	PidTagRuleActionNumber .....	337

2.933	PidTagRuleActions	337
2.934	PidTagRuleActionType	338
2.935	PidTagRuleCondition	338
2.936	PidTagRuleError	338
2.937	PidTagRuleFolderEntryId	339
2.938	PidTagRuleId	339
2.939	PidTagRuleIds	339
2.940	PidTagRuleLevel	339
2.941	PidTagRuleMessageLevel	340
2.942	PidTagRuleMessageName	340
2.943	PidTagRuleMessageProvider	340
2.944	PidTagRuleMessageProviderData	341
2.945	PidTagRuleMessageSequence	341
2.946	PidTagRuleMessageState	341
2.947	PidTagRuleMessageUserFlags	342
2.948	PidTagRuleName	342
2.949	PidTagRuleProvider	342
2.950	PidTagRuleProviderData	343
2.951	PidTagRuleSequence	343
2.952	PidTagRuleState	343
2.953	PidTagRuleUserFlags	343
2.954	PidTagRwRulesStream	344
2.955	PidTagScheduleInfoAppointmentTombstone	344
2.956	PidTagScheduleInfoAutoAcceptAppointments	344
2.957	PidTagScheduleInfoDelegateEntryIds	345
2.958	PidTagScheduleInfoDelegateNames	345
2.959	PidTagScheduleInfoDelegateNamesW	345
2.960	PidTagScheduleInfoDelegatorWantsCopy	346
2.961	PidTagScheduleInfoDelegatorWantsInfo	346
2.962	PidTagScheduleInfoDisallowOverlappingAppts	346
2.963	PidTagScheduleInfoDisallowRecurringAppts	347
2.964	PidTagScheduleInfoDontMailDelegates	347
2.965	PidTagScheduleInfoFreeBusy	347
2.966	PidTagScheduleInfoFreeBusyAway	347
2.967	PidTagScheduleInfoFreeBusyBusy	348
2.968	PidTagScheduleInfoFreeBusyMerged	348
2.969	PidTagScheduleInfoFreeBusyTentative	348
2.970	PidTagScheduleInfoMonthsAway	349
2.971	PidTagScheduleInfoMonthsBusy	349
2.972	PidTagScheduleInfoMonthsMerged	349
2.973	PidTagScheduleInfoMonthsTentative	349
2.974	PidTagScheduleInfoResourceType	350
2.975	PidTagSchedulePlusFreeBusyEntryId	350
2.976	PidTagScriptData	350
2.977	PidTagSearchFolderDefinition	351
2.978	PidTagSearchFolderEfpFlags	351
2.979	PidTagSearchFolderExpiration	351
2.980	PidTagSearchFolderId	351
2.981	PidTagSearchFolderLastUsed	352
2.982	PidTagSearchFolderRecreateInfo	352
2.983	PidTagSearchFolderStorageType	352
2.984	PidTagSearchFolderTag	353
2.985	PidTagSearchFolderTemplateId	353

2.986	PidTagSearchKey .....	353
2.987	PidTagSecurityDescriptorAsXml .....	353
2.988	PidTagSelectable .....	354
2.989	PidTagSenderAddressType .....	354
2.990	PidTagSenderEmailAddress .....	354
2.991	PidTagSenderEntryId .....	355
2.992	PidTagSenderIdStatus .....	355
2.993	PidTagSenderName .....	355
2.994	PidTagSenderSearchKey .....	356
2.995	PidTagSenderSmtpAddress .....	356
2.996	PidTagSenderTelephoneNumber .....	356
2.997	PidTagSendInternetEncoding .....	357
2.998	PidTagSendRichInfo .....	357
2.999	PidTagSensitivity .....	357
2.1000	PidTagSentMailSvrEID .....	358
2.1001	PidTagSentRepresentingAddressType .....	358
2.1002	PidTagSentRepresentingEmailAddress .....	358
2.1003	PidTagSentRepresentingEntryId .....	359
2.1004	PidTagSentRepresentingFlags .....	359
2.1005	PidTagSentRepresentingName .....	359
2.1006	PidTagSentRepresentingSearchKey .....	360
2.1007	PidTagSentRepresentingSmtpAddress .....	360
2.1008	PidTagSmtpAddress .....	360
2.1009	PidTagSortLocaleId .....	361
2.1010	PidTagSourceKey .....	361
2.1011	PidTagSpokenName .....	361
2.1012	PidTagSpouseName .....	362
2.1013	PidTagStartDate .....	362
2.1014	PidTagStartDateEtc .....	362
2.1015	PidTagStateOrProvince .....	363
2.1016	PidTagStoreEntryId .....	363
2.1017	PidTagStoreState .....	363
2.1018	PidTagStoreSupportMask .....	364
2.1019	PidTagStreetAddress .....	364
2.1020	PidTagSubfolders .....	364
2.1021	PidTagSubject .....	364
2.1022	PidTagSubjectPrefix .....	365
2.1023	PidTagSupplementaryInfo .....	365
2.1024	PidTagSurname .....	365
2.1025	PidTagSwappedToDoData .....	366
2.1026	PidTagSwappedToDoStore .....	366
2.1027	PidTagTargetEntryId .....	366
2.1028	PidTagTelecommunicationsDeviceForDeafTelephoneNumber .....	367
2.1029	PidTagTelexNumber .....	367
2.1030	PidTagTemplateData .....	367
2.1031	PidTagTemplateid .....	368
2.1032	PidTagTextAttachmentCharset .....	368
2.1033	PidTagThumbnailPhoto .....	368
2.1034	PidTagTitle .....	369
2.1035	PidTagTnefCorrelationKey .....	369
2.1036	PidTagToDoItemFlags .....	369
2.1037	PidTagTransmittableDisplayName .....	370
2.1038	PidTagTransportMessageHeaders .....	370

2.1039	PidTagTrustSender .....	370
2.1040	PidTagUserCertificate .....	371
2.1041	PidTagUserEntryId .....	371
2.1042	PidTagUserX509Certificate .....	371
2.1043	PidTagViewDescriptorBinary .....	371
2.1044	PidTagViewDescriptorName .....	372
2.1045	PidTagViewDescriptorStrings .....	372
2.1046	PidTagViewDescriptorVersion .....	372
2.1047	PidTagVoiceMessageAttachmentOrder .....	373
2.1048	PidTagVoiceMessageDuration .....	373
2.1049	PidTagVoiceMessageSenderName .....	373
2.1050	PidTagWeddingAnniversary .....	374
2.1051	PidTagWlinkAddressBookEID .....	374
2.1052	PidTagWlinkAddressBookStoreEID .....	374
2.1053	PidTagWlinkCalendarColor .....	374
2.1054	PidTagWlinkClientID .....	375
2.1055	PidTagWlinkEntryId .....	375
2.1056	PidTagWlinkFlags .....	375
2.1057	PidTagWlinkFolderType .....	376
2.1058	PidTagWlinkGroupClsid .....	376
2.1059	PidTagWlinkGroupHeaderID .....	376
2.1060	PidTagWlinkGroupName .....	376
2.1061	PidTagWlinkOrdinal .....	377
2.1062	PidTagWlinkRecordKey .....	377
2.1063	PidTagWlinkROGroupType .....	377
2.1064	PidTagWlinkSaveStamp .....	378
2.1065	PidTagWlinkSection .....	378
2.1066	PidTagWlinkStoreEntryId .....	378
2.1067	PidTagWlinkType .....	378
<b>3</b>	<b>Structure Examples .....</b>	<b>380</b>
<b>4</b>	<b>Security Considerations .....</b>	<b>381</b>
<b>5</b>	<b>Appendix A: Product Behavior .....</b>	<b>382</b>
<b>6</b>	<b>Change Tracking .....</b>	<b>383</b>
<b>7</b>	<b>Index .....</b>	<b>384</b>



# 1 Introduction

The Exchange Server Protocols Master Property List provides implementers with a single source of information about all the properties that are described by the specifications that comprise the Exchange Server Protocols documentation. If a property is not described by the specifications included in the Exchange Server Protocols documentation, it is not included in this document.

The criteria for including a property in the Exchange Server Protocols documentation are that it is set by a client in order to affect server behavior, or that it is set by a server in order to affect client behavior. Properties that are merely stored by the server on behalf of the client, or generated by the server for its own use and ignored by the client, are not necessarily documented. As a result, the properties that are included in the Exchange Server Protocols documentation, and therefore this document, are the critical **Message object** properties used for communication between clients and servers.

This document provides implementers with a convenient catalog of all these critical properties, a source of navigation to the individual technical specifications that describe these properties in detail, and a resource for additional helpful property information that is unique to this document.

Sections 1.7 and 2 of this specification are normative and can contain the terms MAY, SHOULD, MUST, MUST NOT, and SHOULD NOT as defined in RFC 2119. All other sections and examples in this specification are informative.

## 1.1 Glossary

The following terms are defined in [\[MS-GLOS\]](#):

- 8.3 name**
- ambiguous name resolution (ANR)**
- Augmented Backus-Naur Form (ABNF)**
- class**
- common name (CN)**
- Coordinated Universal Time (UTC)**
- cyclic redundancy check (CRC)**
- distinguished name (DN)**
- domain**
- flags**
- GUID**
- Hypertext Transfer Protocol (HTTP)**
- name service provider interface (NSPI)**
- property set**
- resource**
- Transmission Control Protocol (TCP)**
- Unicode**
- XML**

The following terms are defined in [\[MS-OXGLOS\]](#):

- action**
- address book container**
- Address Book object**
- address list**
- address type**
- alias**
- Appointment object**

archive tag  
Attachment object  
blind carbon copy (Bcc) recipient  
body part  
calendar  
Calendar folder  
Calendar object  
carbon copy (Cc) recipient  
contact  
contents table  
conversation  
conversation action  
counter proposal  
Deferred Action Message (DAM)  
delegate  
delivery receipt  
departmental group  
display name  
display template  
distribution list  
Document object  
double-byte character set (DBCS)  
Email object  
EntryID  
Exception Embedded Message object  
Exception object  
File Transfer Protocol (FTP)  
folder associated information (FAI)  
Folder object  
free/busy status  
Global Address List (GAL)  
group header  
Hypertext Markup Language (HTML)  
instance  
Integrated Services Digital Network (ISDN)  
Journal object  
locale  
Logon object  
long ID (LID)  
mail tip  
mail user  
mailbox  
meeting  
Meeting object  
meeting request  
Meeting Request object  
Meeting Response object  
Meeting Update object  
Meeting Workspace  
meeting-related object  
message body  
message class  
Message object  
message store  
Messaging Application Programming Interface (MAPI)

**messaging object**  
**MIME message**  
**MIME part**  
**Multipurpose Internet Mail Extensions (MIME)**  
**named property**  
**navigation shortcut**  
**non-Unicode**  
**Note object**  
**offline address book (OAB)**  
**optional attendee**  
**organizer**  
**orphan instance**  
**Out of Office (OOF)**  
**Permanent Entry ID**  
**permission**  
**phishing**  
**plain text**  
**primary recipient**  
**property ID**  
**property name**  
**property type**  
**public folder**  
**read receipt**  
**recipient**  
**recipient table**  
**recurrence pattern**  
**Recurring Calendar object**  
**recurring series**  
**recurring task**  
**reminder**  
**Resource object**  
**retention tag**  
**Rich Text Format (RTF)**  
**rights-managed email message**  
**Root folder**  
**ROP buffer**  
**Rule FAI message**  
**Sent Items folder**  
**Server object**  
**Short Message Service (SMS)**  
**signal time**  
**Simple Mail Transfer Protocol (SMTP)**  
**site mailbox**  
**soft delete**  
**spam**  
**spam filter**  
**special folder**  
**tagged property**  
**Task object**  
**task request**  
**Transport Neutral Encapsulation Format (TNEF)**  
**Uniform Resource Identifier (URI)**  
**Uniform Resource Locator (URL)**  
**unsendable attendee**  
**Use License**

**Web Distributed Authoring and Versioning Protocol (WebDAV)  
X500 DN  
XML document**

The following terms are specific to this document:

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as described in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

References to Microsoft Open Specifications documentation do not include a publishing year because links are to the latest version of the documents, which are updated frequently. References to other documents include a publishing year when one is available.

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information. Please check the archive site, <http://msdn2.microsoft.com/en-us/library/E4BD6494-06AD-4aed-9823-445E921C9624>, as an additional source.

[ISO/IEC8802-3] ISO/IEC, "Information technology -- Telecommunications and information exchange between systems -- Local and metropolitan area networks -- Specific requirements -- Part 3", Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, ISO/IEC 8802-3:2000, [http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=31002](http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=31002)

[MS-OXABREF] Microsoft Corporation, "[Address Book Name Service Provider Interface \(NSPI\) Referral Protocol](#)".

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Algorithm](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCEXT] Microsoft Corporation, "[Client Extension Message Object Protocol](#)".

[MS-OXCFCAL] Microsoft Corporation, "[Folder Object Protocol](#)".

[MS-OXCFCICS] Microsoft Corporation, "[Bulk Data Transfer Protocol](#)".

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Algorithm](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC 2822 and MIME to Email Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol](#)".

[MS-OXCPERM] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol](#)".

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol](#)".

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol](#)".

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol](#)".

[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol](#)".

[MS-OXLDAP] Microsoft Corporation, "[Lightweight Directory Access Protocol \(LDAP\) Version 3 Extensions](#)".

[MS-OXMSG] Microsoft Corporation, "[Outlook Item \(.msg\) File Format](#)".

[MS-OXNSPI] Microsoft Corporation, "[Exchange Server Name Service Provider Interface \(NSPI\) Protocol](#)".

[MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol](#)".

[MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol](#)".

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol](#)".

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol](#)".

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol](#)".

[MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol](#)".

[MS-OXODOC] Microsoft Corporation, "[Document Object Protocol](#)".

[MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol](#)".

[MS-OXOJRNL] Microsoft Corporation, "[Journal Object Protocol](#)".

[MS-OXOMSG] Microsoft Corporation, "[Email Object Protocol](#)".

[MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol](#)".

[MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol](#)".

[MS-OXOPOST] Microsoft Corporation, "[Post Object Protocol](#)".

[MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol](#)".

[MS-OXORMMS] Microsoft Corporation, "[Rights-Managed Email Object Protocol](#)".

[MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol](#)".

[MS-OXORULE] Microsoft Corporation, "[Email Rules Protocol](#)".

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol](#)".

[MS-OXOSMIME] Microsoft Corporation, "[S/MIME Email Object Algorithm](#)".

[MS-OXOSMMS] Microsoft Corporation, "[Short Message Service \(SMS\) and Multimedia Messaging Service \(MMS\) Object Protocol](#)".

[MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol](#)".

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol](#)".

[MS-OXOUM] Microsoft Corporation, "[Voice Mail and Fax Objects Protocol](#)".

- [MS-OXPFOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) Public Folder Retrieval Protocol](#)".
- [MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol](#)".
- [MS-OXPSVAL] Microsoft Corporation, "[Email Postmark Validation Algorithm](#)".
- [MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Algorithm](#)".
- [MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Algorithm](#)".
- [MS-OXSHARE] Microsoft Corporation, "[Sharing Message Object Protocol](#)".
- [MS-OXTNEF] Microsoft Corporation, "[Transport Neutral Encapsulation Format \(TNEF\) Data Algorithm](#)".
- [MS-OXVCARD] Microsoft Corporation, "[vCard to Contact Object Conversion Algorithm](#)".
- [MS-OXWAVLS] Microsoft Corporation, "[Availability Web Service Protocol](#)".
- [MS-WMF] Microsoft Corporation, "[Windows Metafile Format](#)".
- [MS-XWDCAL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Calendar Support](#)".
- [MS-XWDVSEC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Protocol Security Descriptor Extensions](#)".
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>
- [RFC3464] Moore, K., and Vaudreuil, G., "An Extensible Message Format for Delivery Status Notifications", RFC 3464, January 2003, <http://www.rfc-editor.org/rfc/rfc3464.txt>
- [RFC3798] Hansen, T., and Vaudreuil, G., Eds., "Message Disposition Notification", RFC 3798, May 2004, <http://www.rfc-editor.org/rfc/rfc3798.txt>

### 1.2.2 Informative References

- [MS-GLOS] Microsoft Corporation, "[Windows Protocols Master Glossary](#)".
- [MS-OXGLOS] Microsoft Corporation, "[Exchange Server Protocols Master Glossary](#)".
- [MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".
- [RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

### 1.3 Overview

Each property listing in this document contains a link to the section of the technical specification in the Exchange Server Protocols documentation that acts as the defining reference for the property. The defining reference for each property contains the semantic use and definition of the property, including the property data type. The property information that is included in the defining reference for each property is required to successfully parse property data. As such, this document provides implementers with a single source of navigation to all of the critical property information that is included in the individual Exchange Server Protocols technical specifications.

This document also provides additional information about each property that is helpful to the implementer, such as the functional area where the property is used, a list of all the technical specifications that cite the property, and a list of alternate names by which the canonical property is known within the system. This information is not included in the technical specifications that describe each property, and is unique to this document. It is provided for informational purposes only.

A typical scenario for using this document is when an implementer encounters both **property IDs** and property values with no other identification coming across the wire. The property data type and the semantic definition of the property that are included in the defining reference for each property allow the implementer to correctly parse property values that show up in **ROP buffers**. The parsed values in the ROP buffers include lists of property IDs, which are typically lists of four hexadecimal characters. By searching the information in this document for those four hexadecimal characters, the implementer can quickly name the associated property and navigate to the definition of the individual property in its defining specification.

The following information is provided for each property, as appropriate.

**Alternate names:** Alternate names are implementation-specific names for properties that are used in source code and non-protocol-related documentation. Information about alternate names is useful when the implementer needs to refer to legacy documentation about a specific canonical property.

**Area:** The functional area where the property is used. Sections [1.3.1](#), [1.3.2](#), and [1.3.3](#) describe the general functional areas where properties are used. The listing for each property in section [2](#) describes the areas with more varied descriptions so as to provide more insight into property usage.

**Canonical name:** The name used to refer to the property in the Exchange Server Protocols documentation. The prefix of the canonical name identifies the basic characteristics of a property to the implementer.

The canonical naming structure uses three categories that are denoted by the following prefixes to the canonical **property name**:

- PidLid prefix: Properties identified by an unsigned 32-bit quantity along with a property set.
- PidName prefix: Properties identified by a string name along with a property set.
- PidTag prefix: Properties identified by an unsigned 16-bit quantity.

**Description:** A brief description of the contents of the property.

**Data type:** The property value type, as described in [\[MS-OXCDATA\]](#), that specifies the type of values allowed for the property.

**Property ID:** An unsigned 16-bit quantity that identifies a **tagged property**. Property IDs are not necessarily unique. With the exception of property IDs in the range from 0x6800 to 0x7BFF (see section [1.3.3](#)), the combination of property ID and data type are unique. Property IDs in the range from 0x6800 to 0x7BFF are defined by the **message class**.

**Property long ID (LID):** An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

**Property name:** A string that, along with the property set, identifies a named property.

**Property set:** A **GUID** that identifies a group of properties with a similar purpose.

**Defining references:** One or more technical specifications that describe the semantics and allowed values for the property.

**Consuming references:** One or more technical specifications that refer to the property but do not describe semantics and allowed values.

### 1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's message class. The following table describes several common message classes, the functional area to which each one corresponds, and the specification that describes each one's required and optional properties.

In the following table, an asterisk "\*" denotes that any string can appear at that point.

Area name	PidTagMessageClass property values	Specification
Common	IPM.*	<a href="#">[MS-OXCMSG]</a>
E-mail	IPM.Note, REPORT.*	[MS-OXCMSG]
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	<a href="#">[MS-OXOCAL]</a>
Contact	IPM.Contact, IPM DistList	<a href="#">[MS- OXOCNTC]</a>
Task	IPM.Task, IPM.TaskRequest.*	<a href="#">[MS- OXOTASK]</a>
Journal	IPM.Activity	<a href="#">[MS- OXOJRN]</a>
Sticky Note	IPM.StickyNote	<a href="#">[MS- OXONOTE]</a>
Document	IPM.Document.*	<a href="#">[MS-OXODOC]</a>
Post	IPM.Post	<a href="#">[MS- OXOPOST]</a>
RSS Feed	IPM.Post.RSS	<a href="#">[MS-OXORSS]</a>
Rights-managed E-mail	IPM.Note with PidNameContentClass= rmsg.message	<a href="#">[MS- OXORMMS]</a>
S/MIME E-mail	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	<a href="#">[MS- OXOSMIME]</a>
Short Message Service (SMS) / Multimedia Message Service (MMS) Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	<a href="#">[MS- OXOSMMS]</a>
Unified Messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	<a href="#">[MS-OXOUM]</a>
Sharing	IPM.Sharing	<a href="#">[MS-</a>



Area name	PidTagMessageClass property values	Specification
	IPM.Sharing.*	<a href="#">OXSHAREJ</a>

### 1.3.2 Commonly Used Property Sets

In the property list that forms the main body of this document (section [2](#)), each named property is listed with the GUID that describes its property set. Several of the more common property sets and their functional areas are described in the following table.

Area name	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}
Common	PSETID_Common {00062008-0000-0000-C000-000000000046}
Contact	PSETID_Address {00062004-0000-0000-C000-000000000046}
E-mail	PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-000000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-000000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-000000000046}
RSS feed	PSETID_PostRss {00062041-0000-0000-C000-000000000046}
Task	PSETID_Task {00062003-0000-0000-C000-000000000046}
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing

Area name	Property set name and GUID value
	{00062040-0000-0000-C000-000000000046}
Extracted entities	PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

### 1.3.3 Property ID Ranges

The 65,536 possible values of the property ID are divided into sub-ranges reserved for various purposes, as described in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an e-mail transport protocol (such as **SMTP**), and not to any network transport protocol (such as **TCP**):

- Servers do not allow property IDs in ranges specified as non-transmittable to be submitted for transport to another server via an e-mail transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.
- Clients can use properties in ranges described as message class-defined for application-defined purposes. When doing so, applications specify a value for the **PidTagMessageClass** property (section 2.776) that is distinct from any value listed in section 1.3.1.
- Clients can use any named property for application-defined purposes. No constraint is placed on the value of the **PidTagMessageClass** property in this case, but the property set of the named property is distinct from any value listed in section 1.3.2. Note that named properties are always transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Description
0x0001	0x0BFF	Message object envelope property; reserved
0x0C00	0x0DFF	<b>Recipient (1)</b> property; reserved
0x0E00	0x0FFF	Non-transmittable Message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	<b>Message store</b> property; reserved
0x3600	0x36FF	Folder and <b>address book container</b> property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	<b>Address Book object</b> property; reserved
0x3A00	0x3BFF	<b>Mail user</b> object property; reserved
0x3C00	0x3CFF	<b>Distribution list</b> property; reserved

Range minimum	Range maximum	Description
0x3D00	0x3DFF	Profile section property; reserved
0x3E00	0x3EFF	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient (1) property
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. For more information about the static mapping of <b>NSPI</b> property names to property IDs that occurs in this ID range, see <a href="#">[MS-OXNSPI]</a> .

### 1.3.4 WebDAV Property Naming

The e-mail server is natively a **Messaging Application Programming Interface (MAPI)** message store where the vast majority of properties in it are MAPI properties. The **WebDAV** implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as described in [\[RFC5234\]](#), as a way to name MAPI properties, allowing Web Distributed Authoring and Versioning Protocol (WebDAV) clients to work with these properties directly.

The `http://schemas.microsoft.com/mapi/` namespace is used to access MAPI properties directly on the server. The namespace consists of three sub namespaces: `proptag`, `id`, and `string`. The ABNF notation used to specify the format of these namespaces is described in this section.

#### 1.3.4.1 `http://schemas.microsoft.com/mapi/proptag` Namespace

The `http://schemas.microsoft.com/mapi/proptag` namespace is used to access properties on the server that are identified by a property ID. The implementer can access these properties through WebDAV by appending the hexadecimal property ID value and the hexadecimal **property type** value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type
property-id      = 4HEXDIG
property-type    = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

### 1.3.4.2 <http://schemas.microsoft.com/mapi/id> Namespace

The <http://schemas.microsoft.com/mapi/id> namespace is used to access named properties on the server that are identified by a property **long ID (LID)**. The implementer can access these properties through WebDAV by appending the property set and the hexadecimal property long ID (LID) value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/"x" property-long-id
property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"
property-long-id = 8HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213
(PidLidAppointmentDuration)
```

### 1.3.4.3 <http://schemas.microsoft.com/mapi/string> Namespace

The <http://schemas.microsoft.com/mapi/string> namespace is used to access named properties on the server that are identified by a property name. The implementer can access these properties through WebDAV by appending the property set and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name
property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"
property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject
(PidNameSubject)
```

## 1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [\[MS-OXCADATA\]](#). For tables and examples that describe property data types, and property and other error codes, see [\[MS-OXCADATA\]](#).

The list of properties and their descriptions included in this document provide context for many of the data structures described in [\[MS-OXCADATA\]](#).

The description of each property contained in this document relies on the technical specification that is cited as its defining reference.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

## 1.5 Applicability Statement

This document provides numeric values used to encode property names, tags, and data types in ROP buffers. It also serves as a convenient index to the object type documents that define how each property is used.

## 1.6 Versioning and Localization

None.

## 1.7 Vendor-Extensible Fields

Property ID ranges, as described in section [1.3.3](#), describe how applications choose properties to create new Message object types or to add functionality to existing types.

## 2 Structures

### 2.1 PidLidAddressBookProviderArrayType

**Canonical name:** PidLidAddressBookProviderArrayType

**Description:** Specifies the state of the contact's electronic addresses and represents a set of bit **flags**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008029

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.12

**Alternate names:** dispidABPArrayType

### 2.2 PidLidAddressBookProviderEmailList

**Canonical name:** PidLidAddressBookProviderEmailList

**Description:** Specifies which electronic address properties are set on the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008028

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.11

**Alternate names:** dispidABPEmailList

### 2.3 PidLidAddressCountryCode

**Canonical name:** PidLidAddressCountryCode

**Description:** Specifies the country code portion of the contact's mailing address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DD

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidAddressCountryCode

## 2.4 PidLidAgingDontAgeMe

**Canonical name:** PidLidAgingDontAgeMe

**Description:** Specifies whether to automatically archive the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000850E

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.33

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidAgingDontAgeMe

## 2.5 PidLidAllAttendeesString

**Canonical name:** PidLidAllAttendeesString

**Description:** Specifies a list of all the attendees except for the **organizer**, including **resources** and **unsendable attendees**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008238

**WebDAV:** <http://schemas.microsoft.com/mapi/allattendeesstring>

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.16

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidAllAttendeesString

## 2.6 PidLidAllowExternalCheck

**Canonical name:** PidLidAllowExternalCheck

**Description:** This property is set to TRUE.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008246

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.5

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAllowExternCheck

## 2.7 PidLidAnniversaryEventEntryId

**Canonical name:** PidLidAnniversaryEventEntryId

**Description:** Specifies the **EntryID** of the **Appointment object** that represents a contact's anniversary.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804E

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.6

**Alternate names:** dispidAnniversaryEventEID

## 2.8 PidLidAppointmentAuxiliaryFlags

**Canonical name:** PidLidAppointmentAuxiliaryFlags

**Description:** Specifies a bit field that describes the auxiliary state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008207

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.3

**Alternate names:** dispidApptAuxFlags

## 2.9 PidLidAppointmentColor

**Canonical name:** PidLidAppointmentColor

**Description:** Specifies the color to be used when displaying the **Calendar object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008214

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.50

**Alternate names:** dispidApptColor



## 2.10 PidLidAppointmentCounterProposal

**Canonical name:** PidLidAppointmentCounterProposal

**Description:** Indicates whether a **Meeting Response object** is a **counter proposal**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008257

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.7

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptCounterProposal

## 2.11 PidLidAppointmentDuration

**Canonical name:** PidLidAppointmentDuration

**Description:** Specifies the length of the event, in minutes.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008213

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/apptduration>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptDuration

## 2.12 PidLidAppointmentEndDate

**Canonical name:** PidLidAppointmentEndDate

**Description:** Indicates the date that the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008211

**WebDAV:** <http://schemas.microsoft.com/mapi/apptenddate>

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.3

**Alternate names:** dispidApptEndDate

### 2.13 PidLidAppointmentEndTime

**Canonical name:** PidLidAppointmentEndTime

**Description:** Indicates the time that the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008210

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptendtime>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.4

**Alternate names:** dispidApptEndTime

### 2.14 PidLidAppointmentEndWhole

**Canonical name:** PidLidAppointmentEndWhole

**Description:** Specifies the end date and time for the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820E

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptendwhole>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptEndWhole

### 2.15 PidLidAppointmentLastSequence

**Canonical name:** PidLidAppointmentLastSequence

**Description:** Indicates to the organizer the last sequence number that was sent to any attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008203

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.2

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptLastSequence

## 2.16 PidLidAppointmentMessageClass

**Canonical name:** PidLidAppointmentMessageClass

**Description:** Indicates the message class of the **Meeting object** to be generated from the **Meeting Request object**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000024

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.6

**Alternate names:** dispidApptMessageClass

## 2.17 PidLidAppointmentNotAllowPropose

**Canonical name:** PidLidAppointmentNotAllowPropose

**Description:** Indicates whether attendees are not allowed to propose a new date and/or time for the **meeting**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.26

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptNotAllowPropose

## 2.18 PidLidAppointmentProposalNumber

**Canonical name:** PidLidAppointmentProposalNumber

**Description:** Specifies the number of attendees who have sent counter proposals that have not been accepted or rejected by the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008259

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.6

**Alternate names:** dispidApptProposalNum

## 2.19 PidLidAppointmentProposedDuration

**Canonical name:** PidLidAppointmentProposedDuration

**Description:** Indicates the proposed value for the **PidLidAppointmentDuration** property (section [2.11](#)) for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008256

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.5

**Alternate names:** dispidApptProposedDuration

## 2.20 PidLidAppointmentProposedEndWhole

**Canonical name:** PidLidAppointmentProposedEndWhole

**Description:** Specifies the proposed value for the **PidLidAppointmentEndWhole** property (section [2.14](#)) for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008251

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.4

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedEndWhole

## 2.21 PidLidAppointmentProposedStartWhole

**Canonical name:** PidLidAppointmentProposedStartWhole

**Description:** Specifies the proposed value for the **PidLidAppointmentStartWhole** property (section [2.29](#)) for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008250

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.3

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedStartWhole

## 2.22 PidLidAppointmentRecur

**Canonical name:** PidLidAppointmentRecur

**Description:** Specifies the dates and times when a **recurring series** occurs.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008216

**Data type:** PtypBinary, 0x0102

**WebDAV:** <http://schemas.microsoft.com/mapi/apptrecur>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.44

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptRecur

## 2.23 PidLidAppointmentReplyName

**Canonical name:** PidLidAppointmentReplyName

**Description:** Specifies the user who last replied to the **meeting request** or meeting update.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008230

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/apptreplyname>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.5

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptReplyName, <http://schemas.microsoft.com/mapi/apptreplyname>

## 2.24 PidLidAppointmentReplyTime

**Canonical name:** PidLidAppointmentReplyTime

**Description:** Specifies the date and time at which the attendee responded to a received meeting request or **Meeting Update object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008220

**Data type:** PtypTime, 0x0040

**WebDAV:** urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptReplyTime

## 2.25 PidLidAppointmentSequence

**Canonical name:** PidLidAppointmentSequence

**Description:** Specifies the sequence number of a Meeting object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008201

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptsequence

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptSequence

## 2.26 PidLidAppointmentSequenceTime

**Canonical name:** PidLidAppointmentSequenceTime

**Description:** Indicates the date and time at which the **PidLidAppointmentSequence** property (section [2.25](#)) was last modified.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008202

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.1

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptSeqTime

## 2.27 PidLidAppointmentStartDate

**Canonical name:** PidLidAppointmentStartDate

**Description:** Identifies the date that the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008212

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptstartdate>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.10

**Alternate names:** dispidApptStartDate

## 2.28 PidLidAppointmentStartTime

**Canonical name:** PidLidAppointmentStartTime

**Description:** Identifies the time that the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820F

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptstarttime>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.11

**Alternate names:** dispidApptStartTime

## 2.29 PidLidAppointmentStartWhole

**Canonical name:** PidLidAppointmentStartWhole

**Description:** Specifies the start date and time of the appointment.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820D

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptstartwhole>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStartWhole

### 2.30 PidLidAppointmentStateFlags

**Canonical name:** PidLidAppointmentStateFlags

**Description:** Specifies a bit field that describes the state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008217

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptstateflags

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStateFlags

### 2.31 PidLidAppointmentSubType

**Canonical name:** PidLidAppointmentSubType

**Description:** Specifies whether the event is an all-day event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008215

**Data type:** PtypBoolean, 0x000B

**WebDAV:** urn:schemas:calendar:alldayevent, http://schemas.microsoft.com/mapi/apptsubtype

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptSubType

### 2.32 PidLidAppointmentTimeZoneDefinitionEndDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionEndDisplay

**Description:** Specifies time zone information that indicates the time zone of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825F

**Data type:** PtypBinary, 0x0102



**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefEndDisplay

### 2.33 PidLidAppointmentTimeZoneDefinitionRecur

**Canonical name:** PidLidAppointmentTimeZoneDefinitionRecur

**Description:** Specifies time zone information that describes how to convert the meeting date and time on a recurring series to and from **UTC**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008260

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.41

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** dispidApptTZDefRecur

### 2.34 PidLidAppointmentTimeZoneDefinitionStartDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionStartDisplay

**Description:** Specifies time zone information that indicates the time zone of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825E

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.42

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefStartDisplay

### 2.35 PidLidAppointmentUnsendableRecipients

**Canonical name:** PidLidAppointmentUnsendableRecipients

**Description:** Contains a list of unsendable attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825D

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.25

**Alternate names:** dispidApptUnsendableRecips

## 2.36 PidLidAppointmentUpdateTime

**Canonical name:** PidLidAppointmentUpdateTime

**Description:** Indicates the time at which the appointment was last updated.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008226

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptupdatetime>

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.15

**Alternate names:** dispidApptUpdateTime

## 2.37 PidLidAttendeeCriticalChange

**Canonical name:** PidLidAttendeeCriticalChange

**Description:** Specifies the date and time at which the **meeting-related object** was sent.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000001

**Data type:** PtypTime, 0x0040

**WebDAV:** [http://schemas.microsoft.com/mapi/attendee\\_critical\\_change](http://schemas.microsoft.com/mapi/attendee_critical_change)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_ATTENDEE\_CRITICAL\_CHANGE

## 2.38 PidLidAutoFillLocation

**Canonical name:** PidLidAutoFillLocation

**Description:** Indicates whether the value of the **PidLidLocation** property (section [2.159](#)) is set to the **PidTagDisplayName** property (section [2.667](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.8

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAutoFillLocation

## 2.39 PidLidAutoLog

**Canonical name:** PidLidAutoLog

**Description:** Specifies to the application whether to create a **Journal object** for each action associated with this Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008025

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.19

**Alternate names:** dispidAutoLog

## 2.40 PidLidAutoProcessState

**Canonical name:** PidLidAutoProcessState

**Description:** Specifies the options used in the automatic processing of e-mail messages.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851A

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.73

**Alternate names:** dispidSniffState

## 2.41 PidLidAutoStartCheck

**Canonical name:** PidLidAutoStartCheck

**Description:** Specifies whether to automatically start the conferencing application when a **reminder** for the start of a meeting is executed.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008244

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidAutoStartCheck

## 2.42 PidLidBilling

**Canonical name:** PidLidBilling

**Description:** Specifies billing information for the contact.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008535

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:billinginformation

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.24

**Alternate names:** dispidBilling

## 2.43 PidLidBirthdayEventEntryId

**Canonical name:** PidLidBirthdayEventEntryId

**Description:** Specifies the EntryID of an optional Appointment object that represents the contact's birthday.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804D

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.3

**Alternate names:** dispidBirthdayEventEID

## 2.44 PidLidBirthdayLocal

**Canonical name:** PidLidBirthdayLocal

**Description:** Specifies the birthday of a contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DE

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.2

**Alternate names:** dispidApptBirthdayLocal

## 2.45 PidLidBusinessCardCardPicture

**Canonical name:** PidLidBusinessCardCardPicture

**Description:** Contains the image to be used on a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008041

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.2

**Alternate names:** dispidBCCardPicture

## 2.46 PidLidBusinessCardDisplayDefinition

**Canonical name:** PidLidBusinessCardDisplayDefinition

**Description:** Contains user customization details for displaying a contact as a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008040

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidBCDisplayDefinition

## 2.47 PidLidBusyStatus

**Canonical name:** PidLidBusyStatus

**Description:** Specifies the availability of a user for the event described by the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008205

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/busystatus

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidBusyStatus

## 2.48 PidLidCalendarType

**Canonical name:** PidLidCalendarType

**Description:** Contains the value of the **CalendarType** field from the **PidLidAppointmentRecur** property (section [2.22](#)).

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/calendar\_type

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.11

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_CALENDAR\_TYPE

## 2.49 PidLidCategories

**Canonical name:** PidLidCategories

**Description:** Contains the array of text labels assigned to this Message object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00009000

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.22

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidCategories

## 2.50 PidLidCcAttendeesString

**Canonical name:** PidLidCcAttendeesString

**Description:** Contains a list of all the sendable attendees who are also **optional attendees**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823C

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.18

**Alternate names:** dispidCCAttendeesString

## 2.51 PidLidChangeHighlight

**Canonical name:** PidLidChangeHighlight

**Description:** Specifies a bit field that indicates how the Meeting object has changed.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008204

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.2

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidChangeHighlight

## 2.52 PidLidClassification

**Canonical name:** PidLidClassification

**Description:** Contains a list of the classification categories to which the associated Message object has been assigned.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B6

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.23

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassification

## 2.53 PidLidClassificationDescription

**Canonical name:** PidLidClassificationDescription

**Description:** Contains a human-readable summary of each of the classification categories included in the **PidLidClassification** property (section [2.53](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B7

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.24

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassDesc

## 2.54 PidLidClassificationGuid

**Canonical name:** PidLidClassificationGuid

**Description:** Contains the GUID that identifies the list of e-mail classification categories used by a Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B8

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.1

**Alternate names:** dispidClassGuid

## 2.55 PidLidClassificationKeep

**Canonical name:** PidLidClassificationKeep

**Description:** Indicates whether the message uses any classification categories.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BA

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.2

**Alternate names:** dispidClassKeep

## 2.56 PidLidClassified

**Canonical name:** PidLidClassified



**Description:** Indicates whether the contents of this message are regarded as classified information.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B5

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.25

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassified

## 2.57 PidLidCleanGlobalObjectId

**Canonical name:** PidLidCleanGlobalObjectId

**Description:** Contains the value of the **PidLidGlobalObjectId** property (section [2.142](#)) for an object that represents an **Exception object** to a recurring series, where the Year, Month, and Day fields are all zero.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000023

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.28

**Consuming references:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidCleanGlobalObjId

## 2.58 PidLidClientIntent

**Canonical name:** PidLidClientIntent

**Description:** Indicates what actions the user has taken on this Meeting object.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x00000015

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.2.4

**Alternate names:** dispidClientIntent

## 2.59 PidLidClipEnd

**Canonical name:** PidLidClipEnd

**Description:** Specifies the end date and time of the event in UTC.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008236

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.15

**Alternate names:** dispidClipEnd

## 2.60 PidLidClipStart

**Canonical name:** PidLidClipStart

**Description:** Specifies the start date and time of the event in UTC.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008235

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.14

**Alternate names:** dispidClipStart

## 2.61 PidLidCollaborateDoc

**Canonical name:** PidLidCollaborateDoc

**Description:** Specifies the document to be launched when the user joins the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008247

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidCollaborateDoc

## 2.62 PidLidCommonEnd

**Canonical name:** PidLidCommonEnd

**Description:** Indicates the end time for the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008517

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.19

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidCommonEnd

## 2.63 PidLidCommonStart

**Canonical name:** PidLidCommonStart

**Description:** Indicates the start time for the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008516

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.18

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidCommonStart

## 2.64 PidLidCompanies

**Canonical name:** PidLidCompanies

**Description:** Contains a list of company names, each of which is associated with a **contact (3)** that is specified in the PidLidContacts property ([\[MS-OXCMSG\]](#) section 2.2.1.57.2).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008539

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.2.4

**Alternate names:** dispidCompanies, <http://schemas.microsoft.com/exchange/companies>

## 2.65 PidLidConferencingCheck

**Canonical name:** PidLidConferencingCheck

**Description:**

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008240

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfCheck

## 2.66 PidLidConferencingType

**Canonical name:** PidLidConferencingType

**Description:** Specifies the type of the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008241

**Data type:** PtypInteger32, 0x0003

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfType

## 2.67 PidLidContactCharacterSet

**Canonical name:** PidLidContactCharacterSet

**Description:** Specifies the character set used for a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008023

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.18

**Alternate names:** dispidContactCharSet

## 2.68 PidLidContactItemData

**Canonical name:** PidLidContactItemData

**Description:** Specifies the visible fields in the application's user interface that are used to help display the contact information.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008007

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.22

**Alternate names:** dispidContactItemData

## 2.69 PidLidContactLinkedGlobalAddressListEntryId

**Canonical name:** PidLidContactLinkedGlobalAddressListEntryId

**Description:** Specifies the EntryID of the **GAL** contact to which the duplicate contact is linked.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E2

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.1

**Alternate names:** dispidContactLinkedGAEntryID

## 2.70 PidLidContactLinkEntry

**Canonical name:** PidLidContactLinkEntry

**Description:** Contains the elements of the **PidLidContacts** property (section [2.77](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008585

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.1

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidContactLinkEntry

## 2.71 PidLidContactLinkGlobalAddressListLinkId

**Canonical name:** PidLidContactLinkGlobalAddressListLinkId

**Description:** Specifies the GUID of the GAL contact to which the duplicate contact is linked.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E8

**Data type:** PtypGuid, 0x0048

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.2

**Alternate names:** dispidContactLinkGALLinkID

## 2.72 PidLidContactLinkGlobalAddressListLinkState

**Canonical name:** PidLidContactLinkGlobalAddressListLinkState

**Description:** Specifies the state of the linking between the GAL contact and the duplicate contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E6

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.3

**Alternate names:** dispidContactLinkGALLinkState

## 2.73 PidLidContactLinkLinkRejectHistory

**Canonical name:** PidLidContactLinkLinkRejectHistory

**Description:** Contains a list of GAL contacts that were previously rejected for linking with the duplicate contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E5

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.4

**Alternate names:** dispidContactLinkLinkRejectHistory

## 2.74 PidLidContactLinkName

**Canonical name:** PidLidContactLinkName

**Description:**

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008586

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.3

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidContactLinkName

## 2.75 PidLidContactLinkSearchKey

**Canonical name:** PidLidContactLinkSearchKey

**Description:** Contains the list of SearchKeys for a Contact object linked to by the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008584

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.4

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidContactLinkSearchKey

## 2.76 PidLidContactLinkSMTPAddressCache

**Canonical name:** PidLidContactLinkSMTPAddressCache

**Description:** Contains a list of the SMTP addresses that are used by the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E3

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.5

**Alternate names:** dispidContactLinkSMTPAddressCache

## 2.77 PidLidContacts

**Canonical name:** PidLidContacts

**Description:** Contains the **PidTagDisplayName** property (section [2.667](#)) of each Address Book EntryID referenced in the value of the **PidLidContactLinkEntry** property (section [2.70](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000853A

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidContacts

## 2.78 PidLidContactUserField1

**Canonical name:** PidLidContactUserField1

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804F

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/extensionattribute1>

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField1

## 2.79 PidLidContactUserField2

**Canonical name:** PidLidContactUserField2

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008050

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/extensionattribute2>

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3



**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField2

## 2.80 PidLidContactUserField3

**Canonical name:** PidLidContactUserField3

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008051

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/extensionattribute3>

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField3

## 2.81 PidLidContactUserField4

**Canonical name:** PidLidContactUserField4

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008052

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/extensionattribute4>

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField4

## 2.82 PidLidConversationActionLastAppliedTime

**Canonical name:** PidLidConversationActionLastAppliedTime

**Description:** Contains the time, in UTC, that an **E-mail object** was last received in the **conversation**, or the last time that the user modified the **conversation action**, whichever occurs later.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CA

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.1

**Alternate names:** dispidConvActionLastAppliedTime

## 2.83 PidLidConversationActionMaxDeliveryTime

**Canonical name:** PidLidConversationActionMaxDeliveryTime

**Description:** Contains the maximum value of the **PidTagMessageDeliveryTime** property (section [2.778](#)) of all of the E-mail objects modified in response to the last time that the user changed a conversation action on the client.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C8

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.2

**Alternate names:** dispidConvActionMaxDeliveryTime

## 2.84 PidLidConversationActionMoveFolderEid

**Canonical name:** PidLidConversationActionMoveFolderEid

**Description:** Contains the EntryID for the destination folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C6

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.3

**Alternate names:** dispidConvActionMoveFolderEid

## 2.85 PidLidConversationActionMoveStoreEid

**Canonical name:** PidLidConversationActionMoveStoreEid

**Description:** Contains the EntryID for a move to a folder in a different message store.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C7

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.4

**Alternate names:** dispidConvActionMoveStoreEid

## 2.86 PidLidConversationActionVersion

**Canonical name:** PidLidConversationActionVersion

**Description:** Contains the version of the conversation action **FAI** message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CB

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.5

**Alternate names:** dispidConvActionVersion

## 2.87 PidLidConversationProcessed

**Canonical name:** PidLidConversationProcessed

**Description:** Specifies a sequential number to be used in the processing of a conversation action.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C9

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.6

**Alternate names:** dispidConvExLegacyProcessedRand

## 2.88 PidLidCurrentVersion

**Canonical name:** PidLidCurrentVersion

**Description:** Specifies the build number of the client application that sent the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008552

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.34

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidCurrentVersion

## 2.89 PidLidCurrentVersionName

**Canonical name:** PidLidCurrentVersionName

**Description:** Specifies the name of the client application that sent the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008554

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.35

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidCurrentVersionName

## 2.90 PidLidDayInterval

**Canonical name:** PidLidDayInterval

**Description:** Identifies the day interval for the **recurrence pattern**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000011

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/day\\_interval](http://schemas.microsoft.com/mapi/day_interval)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.19

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_DAY\_INTERVAL

## 2.91 PidLidDayOfMonth

**Canonical name:** PidLidDayOfMonth

**Description:** Identifies the day of the month for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001000

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/dayofmonth

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.20

## 2.92 PidLidDelegateMail

**Canonical name:** PidLidDelegateMail

**Description:** Indicates whether a **delegate** responded to the meeting request.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000009

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/delegate\_mail

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.21

**Alternate names:** LID\_DELEGATE\_MAIL

## 2.93 PidLidDepartment

**Canonical name:** PidLidDepartment

**Description:** This property is ignored by the server and is set to an empty string by the client.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008010

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.4

**Alternate names:** dispidDepartment

## 2.94 PidLidDirectory

**Canonical name:** PidLidDirectory

**Description:** Specifies the directory server to be used.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008242

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidDirectory

## 2.95 PidLidDistributionListChecksum

**Canonical name:** PidLidDistributionListChecksum

**Description:** Specifies the 32-bit **cyclic redundancy check (CRC)** polynomial checksum, as specified in [\[ISO/IEC8802-3\]](#), calculated on the value of the **PidLidDistributionListMembers** property (section [2.96](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804C

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.3

**Alternate names:** dispidDLChecksum

## 2.96 PidLidDistributionListMembers

**Canonical name:** PidLidDistributionListMembers

**Description:** Specifies the list of EntryIDs of the objects corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008055

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.1

**Alternate names:** dispidDLMembers

## 2.97 PidLidDistributionListName

**Canonical name:** PidLidDistributionListName

**Description:** Specifies the name of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008053

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.1.2

**Alternate names:** dispidDLName

## 2.98 PidLidDistributionListOneOffMembers

**Canonical name:** PidLidDistributionListOneOffMembers

**Description:** Specifies the list of one-off EntryIDs corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008054

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.2

**Alternate names:** dispidDLOneOffMembers

## 2.99 PidLidDistributionListStream

**Canonical name:** PidLidDistributionListStream

**Description:** Specifies the list of EntryIDs and one-off EntryIDs corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008064

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.4

**Alternate names:** dispidDLStream

## 2.100 PidLidEmail1AddressType

**Canonical name:** PidLidEmail1AddressType

**Description:** Specifies the **address type** of an electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008082

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1AddrType

## 2.101 PidLidEmail1DisplayName

**Canonical name:** PidLidEmail1DisplayName

**Description:** Specifies the user-readable **display name** for the e-mail address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008080

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1DisplayName

## 2.102 PidLidEmail1EmailAddress

**Canonical name:** PidLidEmail1EmailAddress

**Description:** Specifies the e-mail address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008083

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1EmailAddress

## 2.103 PidLidEmail1OriginalDisplayName

**Canonical name:** PidLidEmail1OriginalDisplayName

**Description:** Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008084

**Data type:** PtypString, 0x001F



**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail1OriginalDisplayName, Email1OriginalDisplayName, EXSCHEMA\_MAPI\_EMAIL1ORIGINALDISPLAYNAME

## 2.104 PidLidEmail1OriginalEntryId

**Canonical name:** PidLidEmail1OriginalEntryId

**Description:** Specifies the EntryID of the object corresponding to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008085

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail1OriginalEntryID

## 2.105 PidLidEmail2AddressType

**Canonical name:** PidLidEmail2AddressType

**Description:** Specifies the address type of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008092

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2AddrType

## 2.106 PidLidEmail2DisplayName

**Canonical name:** PidLidEmail2DisplayName

**Description:** Specifies the user-readable display name for the e-mail address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008090

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2DisplayName

## 2.107 PidLidEmail2EmailAddress

**Canonical name:** PidLidEmail2EmailAddress

**Description:** Specifies the e-mail address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008093

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2EmailAddress

## 2.108 PidLidEmail2OriginalDisplayName

**Canonical name:** PidLidEmail2OriginalDisplayName

**Description:** Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008094

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail2OriginalDisplayName

## 2.109 PidLidEmail2OriginalEntryId

**Canonical name:** PidLidEmail2OriginalEntryId

**Description:** Specifies the EntryID of the object that corresponds to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008095

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail2OriginalEntryID

### 2.110 PidLidEmail3AddressType

**Canonical name:** PidLidEmail3AddressType

**Description:** Specifies the address type of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3AddrType

### 2.111 PidLidEmail3DisplayName

**Canonical name:** PidLidEmail3DisplayName

**Description:** Specifies the user-readable display name for the e-mail address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A0

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3DisplayName

### 2.112 PidLidEmail3EmailAddress

**Canonical name:** PidLidEmail3EmailAddress

**Description:** Specifies the e-mail address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3EmailAddress

### 2.113 PidLidEmail3OriginalDisplayName

**Canonical name:** PidLidEmail3OriginalDisplayName

**Description:** Specifies the SMTP e-mail address that corresponds to the e-mail address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail3OriginalDisplayName

### 2.114 PidLidEmail3OriginalEntryId

**Canonical name:** PidLidEmail3OriginalEntryId

**Description:** Specifies the EntryID of the object that corresponds to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail3OriginalEntryID

### 2.115 PidLidEndRecurrenceDate

**Canonical name:** PidLidEndRecurrenceDate

**Description:** Identifies the end date of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000F

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/end\\_recur\\_date](http://schemas.microsoft.com/mapi/end_recur_date)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.22

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_END\_RECUR\_DATE

### 2.116 PidLidEndRecurrenceTime

**Canonical name:** PidLidEndRecurrenceTime

**Description:** Identifies the end time of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000010

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/end\\_recur\\_time](http://schemas.microsoft.com/mapi/end_recur_time)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.23

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_END\_RECUR\_TIME

### 2.117 PidLidExceptionReplaceTime

**Canonical name:** PidLidExceptionReplaceTime

**Description:** Specifies the date and time, in UTC, within a recurrence pattern that an exception will replace.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008228

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.2.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidExceptionReplaceTime

### 2.118 PidLidFax1AddressType

**Canonical name:** PidLidFax1AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax1AddrType

### 2.119 PidLidFax1EmailAddress

**Canonical name:** PidLidFax1EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax1EmailAddress

### 2.120 PidLidFax1OriginalDisplayName

**Canonical name:** PidLidFax1OriginalDisplayName

**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.801](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax1OriginalDisplayName

### 2.121 PidLidFax1OriginalEntryId

**Canonical name:** PidLidFax1OriginalEntryId

**Description:** Specifies a one-off EntryID that corresponds to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax1OriginalEntryID

## 2.122 PidLidFax2AddressType

**Canonical name:** PidLidFax2AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax2AddrType

## 2.123 PidLidFax2EmailAddress

**Canonical name:** PidLidFax2EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax2EmailAddress

## 2.124 PidLidFax2OriginalDisplayName

**Canonical name:** PidLidFax2OriginalDisplayName

**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.801](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax2OriginalDisplayName

## 2.125 PidLidFax2OriginalEntryId

**Canonical name:** PidLidFax2OriginalEntryId

**Description:** Specifies a one-off EntryID corresponding to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax2OriginalEntryID

## 2.126 PidLidFax3AddressType

**Canonical name:** PidLidFax3AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax3AddrType

## 2.127 PidLidFax3EmailAddress

**Canonical name:** PidLidFax3EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax3EmailAddress

## 2.128 PidLidFax3OriginalDisplayName

**Canonical name:** PidLidFax3OriginalDisplayName



**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.801](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax3OriginalDisplayName

## 2.129 PidLidFax3OriginalEntryId

**Canonical name:** PidLidFax3OriginalEntryId

**Description:** Specifies a one-off EntryID that corresponds to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax3OriginalEntryID

## 2.130 PidLidFExceptionalAttendees

**Canonical name:** PidLidFExceptionalAttendees

**Description:** Indicates that the object is a **Recurring Calendar object** with one or more exceptions, and that at least one of the **Exception Embedded Message objects** has at least one **RecipientRow** structure, as described in [\[MS-OXCDATA\]](#) section 2.8.3.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822B

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.2.3

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidFExceptionalAttendees

## 2.131 PidLidFExceptionalBody

**Canonical name:** PidLidFExceptionalBody

**Description:** Indicates that the Exception Embedded Message object has a body that differs from the Recurring Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008206

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.2.6

**Alternate names:** dispidFExceptionalBody

## 2.132 PidLidFileUnder

**Canonical name:** PidLidFileUnder

**Description:** Specifies the name under which to file a contact when displaying a list of contacts.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008005

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.11

**Alternate names:** dispidFileUnder

## 2.133 PidLidFileUnderId

**Canonical name:** PidLidFileUnderId

**Description:** Specifies how to generate and recompute the value of the **PidLidFileUnder** property (section [2.132](#)) when other contact name properties change.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008006

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.12

**Alternate names:** dispidFileUnderId

## 2.134 PidLidFileUnderList

**Canonical name:** PidLidFileUnderList

**Description:** Specifies a list of possible values for the **PidLidFileUnderId** property (section [2.133](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008026

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.13

**Alternate names:** dispidFileUnderList

## 2.135 PidLidFInvited

**Canonical name:** PidLidFInvited

**Description:** Indicates whether invitations have been sent for the meeting that this Meeting object represents.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008229

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/finvited>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFInvited

## 2.136 PidLidFlagRequest

**Canonical name:** PidLidFlagRequest

**Description:** Contains user-specifiable text to be associated with the flag.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008530

**Data type:** PtypString, 0x001F

**WebDAV:** <urn:schemas:httpmail:messageflag>, <http://schemas.microsoft.com/mapi/request>

**Area:** Flagging

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidRequest

## 2.137 PidLidFlagString

**Canonical name:** PidLidFlagString

**Description:** Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C0

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.10

**Alternate names:** dispidFlagStringEnum

## 2.138 PidLidForwardInstance

**Canonical name:** PidLidForwardInstance

**Description:** Indicates whether the Meeting Request object represents an exception to a recurring series, and whether it was forwarded (even when forwarded by the organizer) rather than being an invitation sent by the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.3

**Alternate names:** dispidFwrInstance

## 2.139 PidLidForwardNotificationRecipients

**Canonical name:** PidLidForwardNotificationRecipients

**Description:** Contains a list of **RecipientRow** structures, as described in [\[MS-OXCDATA\]](#) section 2.8.3, that indicate the recipients (2) of a meeting forward.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008261

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.9.3

**Alternate names:** dispidForwardNotificationRecipients

## 2.140 PidLidFOthersAppointment

**Canonical name:** PidLidFOthersAppointment

**Description:** Indicates whether the **Calendar folder** from which the meeting was opened is another user's **calendar**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822F

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.26

**Alternate names:** dispidFOthersAppt, <http://schemas.microsoft.com/mapi/fothersappt>

## 2.141 PidLidFreeBusyLocation

**Canonical name:** PidLidFreeBusyLocation

**Description:** Specifies a **URL** path from which a client can retrieve **free/busy status** information for the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D8

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:fburl

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.10

**Consuming references:** [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFreeBusyLocation

## 2.142 PidLidGlobalObjectId

**Canonical name:** PidLidGlobalObjectId

**Description:** Contains an ID for an object that represents an exception to a recurring series.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000003

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.27

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#)

**Alternate names:** LID\_GLOBAL\_OBJID

### 2.143 PidLidHasPicture

**Canonical name:** PidLidHasPicture

**Description:** Specifies whether the attachment has a picture.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008015

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.8.1

**Alternate names:** dispidHasPicture

### 2.144 PidLidHomeAddress

**Canonical name:** PidLidHomeAddress

**Description:** Specifies the complete address of the contact's home address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:homepostaladdress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidHomeAddress

### 2.145 PidLidHomeAddressCountryCode

**Canonical name:** PidLidHomeAddressCountryCode

**Description:** Specifies the country code portion of the contact's home address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DA

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidHomeAddressCountryCode

## 2.146 PidLidHtml

**Canonical name:** PidLidHtml

**Description:** Specifies the contact's business webpage URL.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.12

**Alternate names:** dispidHTML

## 2.147 PidLidICalendarDayOfWeekMask

**Canonical name:** PidLidICalendarDayOfWeekMask

**Description:** Identifies the day of the week for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001001

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.27

**Alternate names:** <http://schemas.microsoft.com/mapi/dayofweekmask>

## 2.148 PidLidInboundICalStream

**Canonical name:** PidLidInboundICalStream

**Description:** Contains the contents of the iCalendar **MIME part** of the original **MIME message**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827A

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXCICAL\]](#) section 2.2.1

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InboundICalStream, dispidInboundICalStream

## 2.149 PidLidInfoPathFormName

**Canonical name:** PidLidInfoPathFormName

**Description:** Contains the name of the form associated with this message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x85B1

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.27

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.150 PidLidInstantMessagingAddress

**Canonical name:** PidLidInstantMessagingAddress

**Description:** Specifies the contact's instant messaging address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008062

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.6

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidInstMsg

## 2.151 PidLidIntendedBusyStatus

**Canonical name:** PidLidIntendedBusyStatus

**Description:** Contains the value of the **PidLidBusyStatus** property (section [2.47](#)) on the Meeting object in the organizer's calendar at the time that the Meeting Request object or Meeting Update object was sent.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008224

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/intendedbusystatus>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)



**Alternate names:** dispidIntendedBusyStatus

## 2.152 PidLidInternetAccountName

**Canonical name:** PidLidInternetAccountName

**Description:** Specifies the user-visible e-mail account name through which the e-mail message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008580

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.62

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidInetAcctName

## 2.153 PidLidInternetAccountStamp

**Canonical name:** PidLidInternetAccountStamp

**Description:** Specifies the e-mail account ID through which the e-mail message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008581

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.63

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidInetAcctStamp

## 2.154 PidLidIsContactLinked

**Canonical name:** PidLidIsContactLinked

**Description:** Specifies whether the contact is linked to other contacts.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E0

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.6

**Alternate names:** dispidIsContactLinked

## 2.155 PidLidIsException

**Canonical name:** PidLidIsException

**Description:** Indicates whether the object represents an exception (including an **orphan instance**).

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000A

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/is\_exception

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.35

**Consuming references:** [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_EXCEPTION

## 2.156 PidLidIsRecurring

**Canonical name:** PidLidIsRecurring

**Description:** Specifies whether the object is associated with a recurring series.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000005

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/is\_recurring

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.13

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_RECURREN

## 2.157 PidLidIsSilent

**Canonical name:** PidLidIsSilent

**Description:** Indicates whether the user did not include any text in the body of the Meeting Response object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000004

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/is\_silent

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.7

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_SILENT

## 2.158 PidLidLinkedTaskItems

**Canonical name:** PidLidLinkedTaskItems

**Description:** Indicates whether the user did not include any text in the body of the Meeting Response object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820C

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Tasks

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.47

**Alternate names:** dispidLinkedTaskItems

## 2.159 PidLidLocation

**Canonical name:** PidLidLocation

**Description:** Specifies the location of the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008208

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:location

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidLocation

## 2.160 PidLidLogDocumentPosted

**Canonical name:** PidLidLogDocumentPosted

**Description:** Indicates whether the document was sent by e-mail or posted to a server folder during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008711

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRN\]](#) section 2.2.1.10

**Alternate names:** dispidLogDocPosted

### 2.161 PidLidLogDocumentPrinted

**Canonical name:** PidLidLogDocumentPrinted

**Description:** Indicates whether the document was printed during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870E

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRN\]](#) section 2.2.1.7

**Alternate names:** dispidLogDocPrinted

### 2.162 PidLidLogDocumentRouted

**Canonical name:** PidLidLogDocumentRouted

**Description:** Indicates whether the document was sent to a routing recipient (1) during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008710

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRN\]](#) section 2.2.1.9

**Alternate names:** dispidLogDocRouted

### 2.163 PidLidLogDocumentSaved

**Canonical name:** PidLidLogDocumentSaved

**Description:** Indicates whether the document was saved during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870F

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.8

**Alternate names:** dispidLogDocSaved

## 2.164 PidLidLogDuration

**Canonical name:** PidLidLogDuration

**Description:** Contains the duration, in minutes, of the activity.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008707

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.5

**Alternate names:** dispidLogDuration

## 2.165 PidLidLogEnd

**Canonical name:** PidLidLogEnd

**Description:** Contains the time, in UTC, at which the activity ended.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008708

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.4

**Alternate names:** dispidLogEnd

## 2.166 PidLidLogFlags

**Canonical name:** PidLidLogFlags

**Description:** Contains metadata about the Journal object.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870C

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.6

**Alternate names:** dispidLogFlags

## 2.167 PidLidLogStart

**Canonical name:** PidLidLogStart

**Description:** Contains the time, in UTC, at which the activity began.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008706

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.3

**Alternate names:** dispidLogStart

## 2.168 PidLidLogType

**Canonical name:** PidLidLogType

**Description:** Briefly describes the journal activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008700

**Data type:** PtypString, 0x001F

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.1

**Alternate names:** dispidLogType

## 2.169 PidLidLogTypeDesc

**Canonical name:** PidLidLogTypeDesc

**Description:** Contains an expanded description of the journal activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008712

**Data type:** PtypString, 0x001F

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.2

**Alternate names:** dispidLogTypeDesc

## 2.170 PidLidMeetingType

**Canonical name:** PidLidMeetingType

**Description:** Indicates the type of Meeting Request object or Meeting Update object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000026

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.5

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMeetingType

## 2.171 PidLidMeetingWorkspaceUrl

**Canonical name:** PidLidMeetingWorkspaceUrl

**Description:** Specifies the URL of the **Meeting Workspace** that is associated with a Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008209

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/meetingworkspaceurl>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.48

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMWSURL

## 2.172 PidLidMonthInterval

**Canonical name:** PidLidMonthInterval

**Description:** Indicates the monthly interval of the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000013

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/month\\_interval](http://schemas.microsoft.com/mapi/month_interval)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.33

**Alternate names:** LID\_MONTH\_INTERVAL

### 2.173 PidLidMonthOfYear

**Canonical name:** PidLidMonthOfYear

**Description:** Indicates the month of the year in which the appointment or meeting occurs.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001006

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/monthofyear>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.34

### 2.174 PidLidMonthOfYearMask

**Canonical name:** PidLidMonthOfYearMask

**Description:** Indicates the calculated month of the year in which the appointment or meeting occurs.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000017

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/moy\\_mask](http://schemas.microsoft.com/mapi/moy_mask)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.35

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_MOY\_MASK

### 2.175 PidLidNetShowUrl

**Canonical name:** PidLidNetShowUrl

**Description:** Specifies the URL to be launched when the user joins the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008248

**Data type:** PtypString, 0x001F

**Area:** Conferencing



**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.8

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidNetShowURL

## 2.176 PidLidNoEndDateFlag

**Canonical name:** PidLidNoEndDateFlag

**Description:** Indicates whether the recurrence pattern has an end date.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.36

**Alternate names:** <http://schemas.microsoft.com/mapi/fnoenddate>

## 2.177 PidLidNonSendableBcc

**Canonical name:** PidLidNonSendableBcc

**Description:** Contains a list of all of the unsendable attendees who are also resources.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008538

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendablebcc>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.21

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableBCC

## 2.178 PidLidNonSendableCc

**Canonical name:** PidLidNonSendableCc

**Description:** Contains a list of all of the unsendable attendees who are also optional attendees.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008537

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendablecc>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.20

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableCC

### 2.179 PidLidNonSendableTo

**Canonical name:** PidLidNonSendableTo

**Description:** Contains a list of all of the unsendable attendees who are also required attendees.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008536

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendableto>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.19

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableTo

### 2.180 PidLidNonSendBccTrackStatus

**Canonical name:** PidLidNonSendBccTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008545

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** <http://schemas.microsoft.com/mapi/nonsendbcctrackstatus>

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.24

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendBccTrackStatus

### 2.181 PidLidNonSendCcTrackStatus

**Canonical name:** PidLidNonSendCcTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008544

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendcctrackstatus

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.23

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendCcTrackStatus

## 2.182 PidLidNonSendToTrackStatus

**Canonical name:** PidLidNonSendToTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008543

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendtotrackstatus

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.22

**Consuming references:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendToTrackStatus

## 2.183 PidLidNoteColor

**Canonical name:** PidLidNoteColor

**Description:** Specifies the suggested background color of the **Note object**.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B00

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.1

**Alternate names:** dispidNoteColor

## 2.184 PidLidNoteHeight

**Canonical name:** PidLidNoteHeight

**Description:** Specifies the height of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B03

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.3

**Alternate names:** dispidNoteHeight

## 2.185 PidLidNoteWidth

**Canonical name:** PidLidNoteWidth

**Description:** Specifies the width of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B02

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.2

**Alternate names:** dispidNoteWidth

## 2.186 PidLidNoteX

**Canonical name:** PidLidNoteX

**Description:** Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a Note object.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B04

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.4

**Alternate names:** dispidNoteX

## 2.187 PidLidNoteY

**Canonical name:** PidLidNoteY

**Description:** Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a Note object.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B05

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.5

**Alternate names:** dispidNoteY

## 2.188 PidLidOccurrences

**Canonical name:** PidLidOccurrences

**Description:** Indicates the number of occurrences in the recurring appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001005

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/occurrences>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.43

## 2.189 PidLidOldLocation

**Canonical name:** PidLidOldLocation

**Description:** Indicates the original value of the **PidLidLocation** property (section [2.159](#)) before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000028

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.7

**Alternate names:** dispidOldLocation

## 2.190 PidLidOldRecurrenceType

**Canonical name:** PidLidOldRecurrenceType

**Description:** Indicates the recurrence pattern for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000018

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/recur\\_type](http://schemas.microsoft.com/mapi/recur_type)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.44

**Alternate names:** LID\_RECUR\_TYPE

### 2.191 PidLidOldWhenEndWhole

**Canonical name:** PidLidOldWhenEndWhole

**Description:** Indicates the original value of the **PidLidAppointmentEndWhole** property (section [2.14](#)) before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000002A

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.9

**Alternate names:** dispidOldWhenEndWhole

### 2.192 PidLidOldWhenStartWhole

**Canonical name:** PidLidOldWhenStartWhole

**Description:** Indicates the original value of the **PidLidAppointmentStartWhole** property (section [2.29](#)) before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000029

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.8

**Alternate names:** dispidOldWhenStartWhole

### 2.193 PidLidOnlinePassword

**Canonical name:** PidLidOnlinePassword

**Description:** Specifies the password for a meeting on which the **PidLidConferencingType** property (section [2.66](#)) has the value 0x00000002.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008249

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.9

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidOnlinePassword

## 2.194 PidLidOptionalAttendees

**Canonical name:** PidLidOptionalAttendees

**Description:** Specifies optional attendees.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000007

**Data type:** PtypString, 0x001F

**WebDAV:** [http://schemas.microsoft.com/mapi/optional\\_attendees](http://schemas.microsoft.com/mapi/optional_attendees)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.45

**Alternate names:** LID\_OPTIONAL\_ATTENDEES

## 2.195 PidLidOrganizerAlias

**Canonical name:** PidLidOrganizerAlias

**Description:** Specifies the e-mail address of the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008243

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.6

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidOrgAlias

## 2.196 PidLidOriginalStoreEntryId

**Canonical name:** PidLidOriginalStoreEntryId

**Description:** Specifies the EntryID of the delegator's message store.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008237

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.9

**Alternate names:** dispidOrigStoreEid, <http://schemas.microsoft.com/mapi/origstoreid>

## 2.197 PidLidOtherAddress

**Canonical name:** PidLidOtherAddress

**Description:** Specifies the complete address of the contact's other address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801C

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:otherpostaladdress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidOtherAddress

## 2.198 PidLidOtherAddressCountryCode

**Canonical name:** PidLidOtherAddressCountryCode

**Description:** Specifies the country code portion of the contact's other address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DC

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidOtherAddressCountryCode

## 2.199 PidLidOwnerCriticalChange

**Canonical name:** PidLidOwnerCriticalChange

**Description:** Specifies the date and time at which a Meeting Request object was sent by the organizer.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001A

**Data type:** PtypTime, 0x0040



**WebDAV:** urn:schemas:calendar:dtstamp,  
http://schemas.microsoft.com/mapi/owner\_critical\_change

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.34

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_OWNER\_CRITICAL\_CHANGE

## 2.200 PidLidOwnerName

**Canonical name:** PidLidOwnerName

**Description:** Indicates the name of the owner of the **mailbox**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822E

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/ownername

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.47

**Alternate names:** dispidOwnerName

## 2.201 PidLidPendingStateForSiteMailboxDocument

**Canonical name:** PidLidPendingStateForSiteMailboxDocument

**Description:** Specifies the synchronization state of the **Document object** that is in the Document Libraries folder of the **site mailbox**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085E0

**Data type:** PtypInteger32, 0x0003

**Area:** Site Mailbox

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.34

**Alternate names:** dispidPendingStateforTMDocument

## 2.202 PidLidPercentComplete

**Canonical name:** PidLidPercentComplete

**Description:** Indicates whether a time-flagged Message object is complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008102

**Data type:** PtypFloating64, 0x0005

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidPercentComplete

## 2.203 PidLidPostalAddressId

**Canonical name:** PidLidPostalAddressId

**Description:** Specifies which physical address is the mailing address for this contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008022

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:contacts:mailingaddressid

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidPostalAddressId

## 2.204 PidLidPostRssChannel

**Canonical name:** PidLidPostRssChannel

**Description:** Contains the contents of the title field from the **XML** of the Atom feed or RSS channel.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008904

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.5

**Alternate names:** dispidPostRssChannel

## 2.205 PidLidPostRssChannelLink

**Canonical name:** PidLidPostRssChannelLink

**Description:** Contains the URL of the RSS or Atom feed from which the XML file came.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008900

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.1

**Alternate names:** dispidPostRssChannellink

## 2.206 PidLidPostRssItemGuid

**Canonical name:** PidLidPostRssItemGuid

**Description:** Contains a unique identifier for the RSS object.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008903

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.4

**Alternate names:** dispidPostRssItemGuid

## 2.207 PidLidPostRssItemHash

**Canonical name:** PidLidPostRssItemHash

**Description:** Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008902

**Data type:** PtypInteger32, 0x0003

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.3

**Alternate names:** dispidPostRssItemHash

## 2.208 PidLidPostRssItemLink

**Canonical name:** PidLidPostRssItemLink

**Description:** Contains the URL of the link from an RSS or Atom item.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008901

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.2

**Alternate names:** dispidPostRssItemLink

## 2.209 PidLidPostRssItemXml

**Canonical name:** PidLidPostRssItemXml

**Description:** Contains the item element and all of its sub-elements from an RSS feed, or the entry element and all of its sub-elements from an Atom feed.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008905

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.6

**Alternate names:** dispidPostRssItemXml

## 2.210 PidLidPostRssSubscription

**Canonical name:** PidLidPostRssSubscription

**Description:** Contains the user's preferred name for the RSS or Atom subscription.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008906

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.7

**Alternate names:** dispidPostRssSubscription

## 2.211 PidLidPrivate

**Canonical name:** PidLidPrivate

**Description:** Indicates whether the end user wishes for this Message object to be hidden from other users who have access to the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008506

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.15

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidPrivate

## 2.212 PidLidPromptSendUpdate

**Canonical name:** PidLidPromptSendUpdate

**Description:** Indicates that the Meeting Response object was out-of-date when it was received.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypBoolean, 0x000B

**Area:** Meeting Response

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.8

**Alternate names:** dispidPromptSendUpdate

## 2.213 PidLidRecurrenceDuration

**Canonical name:** PidLidRecurrenceDuration

**Description:** Identifies the length, in minutes, of the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/recurduration>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.48

## 2.214 PidLidRecurrencePattern

**Canonical name:** PidLidRecurrencePattern

**Description:** Specifies a description of the recurrence pattern of the Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008232

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/recurpattern>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.46

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurPattern

## 2.215 PidLidRecurrenceType

**Canonical name:** PidLidRecurrenceType

**Description:** Specifies the recurrence type of the recurring series.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008231

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/recurtype>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.45

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurType

## 2.216 PidLidRecurring

**Canonical name:** PidLidRecurring

**Description:** Specifies whether the object represents a recurring series.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008223

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/recurring>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurring

## 2.217 PidLidReferenceEntryId

**Canonical name:** PidLidReferenceEntryId

**Description:** Specifies the value of the EntryID of the Contact object unless the Contact object is a copy of an earlier original.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BD

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.1

**Alternate names:** dispidReferenceEID

## 2.218 PidLidReminderDelta

**Canonical name:** PidLidReminderDelta

**Description:** Specifies the interval, in minutes, between the time at which the reminder first becomes overdue and the start time of the Calendar object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008501

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderDelta, <http://schemas.microsoft.com/mapi/reminddelta>

## 2.219 PidLidReminderFileParameter

**Canonical name:** PidLidReminderFileParameter

**Description:** Specifies the filename of the sound that a client is to play when the reminder for that object becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851F

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderfileparam>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderFileParam

## 2.220 PidLidReminderOverride

**Canonical name:** PidLidReminderOverride

**Description:** Specifies whether the client is to respect the current values of the **PidLidReminderPlaySound** property (section [2.221](#)) and the **PidLidReminderFileParameter** property (section [2.219](#)), or use the default values for those properties.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851C

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderoverride>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.5

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderOverride

## 2.221 PidLidReminderPlaySound

**Canonical name:** PidLidReminderPlaySound

**Description:** Specifies whether the client is to play a sound when the reminder becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851E

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderplaysound>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.6

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderPlaySound

## 2.222 PidLidReminderSet

**Canonical name:** PidLidReminderSet

**Description:** Specifies whether a reminder is set on the object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008503

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderset>



**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFCXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderSet

## 2.223 PidLidReminderSignalTime

**Canonical name:** PidLidReminderSignalTime

**Description:** Specifies the point in time when a reminder transitions from pending to overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008560

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindernexttime>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidReminderNextTime

## 2.224 PidLidReminderTime

**Canonical name:** PidLidReminderTime

**Description:** Specifies the initial **signal time** for objects that are not Calendar objects.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008502

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindertime>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderTime

## 2.225 PidLidReminderTimeDate

**Canonical name:** PidLidReminderTimeDate

**Description:** Indicates the time and date of the reminder for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008505

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindertimedate>

**Area:** Reminders

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.59

**Alternate names:** dispidReminderTimeDate

## 2.226 PidLidReminderTimeTime

**Canonical name:** PidLidReminderTimeTime

**Description:** Indicates the time of the reminder for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008504

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindertimetime>

**Area:** Reminders

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.60

**Consuming references:** [\[MS-OXONOTE\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderTimeTime

## 2.227 PidLidReminderType

**Canonical name:** PidLidReminderType

**Description:** This property is not set and, if set, is ignored.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851D

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.9

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderType, <http://schemas.microsoft.com/mapi/remindertype>

## 2.228 PidLidRemoteStatus

**Canonical name:** PidLidRemoteStatus

**Description:** Indicates the remote status of the calendar item.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008511

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/remotestatus>

**Area:** Run-time configuration

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.62

**Alternate names:** dispidRemoteStatus

## 2.229 PidLidRequiredAttendees

**Canonical name:** PidLidRequiredAttendees

**Description:** Identifies required attendees for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000006

**Data type:** PtypString, 0x001F

**WebDAV:** [http://schemas.microsoft.com/mapi/required\\_attendees](http://schemas.microsoft.com/mapi/required_attendees)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.63

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_REQUIRED\_ATTENDEES

## 2.230 PidLidResourceAttendees

**Canonical name:** PidLidResourceAttendees

**Description:** Identifies resource attendees for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000008

**Data type:** PtypString, 0x001F

**WebDAV:** [http://schemas.microsoft.com/mapi/resource\\_attendees](http://schemas.microsoft.com/mapi/resource_attendees)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.64

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_RESOURCE\_ATTENDEES

### 2.231 PidLidResponseStatus

**Canonical name:** PidLidResponseStatus

**Description:** Specifies the response status of an attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008218

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:calendar:attendeestatus,  
http://schemas.microsoft.com/mapi/responsestatus

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidResponseStatus

### 2.232 PidLidServerProcessed

**Canonical name:** PidLidServerProcessed

**Description:** Indicates whether the Meeting Request object or Meeting Update object has been processed.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CC

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.4

**Alternate names:** dispidExchangeProcessed

### 2.233 PidLidServerProcessingActions

**Canonical name:** PidLidServerProcessingActions

**Description:** Indicates what processing actions have been taken on this Meeting Request object or Meeting Update object.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CD

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.5

**Alternate names:** dispidExchangeProcessingAction

## 2.234 PidLidSharingAnonymity

**Canonical name:** PidLidSharingAnonymity

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A19

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingAnonymity

## 2.235 PidLidSharingBindingEntryId

**Canonical name:** PidLidSharingBindingEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2D

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingBindingEid

## 2.236 PidLidSharingBrowseUrl

**Canonical name:** PidLidSharingBrowseUrl

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A51

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingBrowseUrl

### 2.237 PidLidSharingCapabilities

**Canonical name:** PidLidSharingCapabilities

**Description:** Indicates that the Message object relates to a **special folder**.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A17

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.1

**Alternate names:** dispidSharingCaps

### 2.238 PidLidSharingConfigurationUrl

**Canonical name:** PidLidSharingConfigurationUrl

**Description:** Contains a zero-length string.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A24

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.3

**Alternate names:** dispidSharingConfigUrl

### 2.239 PidLidSharingDataRangeEnd

**Canonical name:** PidLidSharingDataRangeEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A45

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDataRangeEnd

## 2.240 PidLidSharingDataRangeStart

**Canonical name:** PidLidSharingDataRangeStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A44

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDataRangeStart

## 2.241 PidLidSharingDetail

**Canonical name:** PidLidSharingDetail

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDetail

## 2.242 PidLidSharingExtensionXml

**Canonical name:** PidLidSharingExtensionXml

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A21

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingExtXml

## 2.243 PidLidSharingFilter

**Canonical name:** PidLidSharingFilter

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A13

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFilter

## 2.244 PidLidSharingFlags

**Canonical name:** PidLidSharingFlags

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFlags

## 2.245 PidLidSharingFlavor

**Canonical name:** PidLidSharingFlavor

**Description:** Indicates the type of Sharing Message object.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A18

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.5

**Alternate names:** dispidSharingFlavor



## 2.246 PidLidSharingFolderEntryId

**Canonical name:** PidLidSharingFolderEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A15

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFolderEid

## 2.247 PidLidSharingIndexEntryId

**Canonical name:** PidLidSharingIndexEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2E

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingIndexEid

## 2.248 PidLidSharingInitiatorEntryId

**Canonical name:** PidLidSharingInitiatorEntryId

**Description:** Contains the value of the **PidTagEntryId** property (section [2.674](#)) for the Address Book object of the currently logged-on user.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A09

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.7

**Alternate names:** dispidSharingInitiatorEid

## 2.249 PidLidSharingInitiatorName

**Canonical name:** PidLidSharingInitiatorName

**Description:** Contains the value of the **PidTagDisplayName** property (section [2.667](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.248](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A07

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.8

**Alternate names:** dispidSharingInitiatorName

## 2.250 PidLidSharingInitiatorSntp

**Canonical name:** PidLidSharingInitiatorSntp

**Description:** Contains the value of the **PidTagSntpAddress** property (section [2.1008](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.248](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A08

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.9

**Alternate names:** dispidSharingInitiatorSntp

## 2.251 PidLidSharingInstanceGuid

**Canonical name:** PidLidSharingInstanceGuid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingInstanceGuid

## 2.252 PidLidSharingLastAutoSyncTime

**Canonical name:** PidLidSharingLastAutoSyncTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A55

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLastAutoSync

## 2.253 PidLidSharingLastSyncTime

**Canonical name:** PidLidSharingLastSyncTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1F

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLastSync

## 2.254 PidLidSharingLocalComment

**Canonical name:** PidLidSharingLocalComment

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalComment

## 2.255 PidLidSharingLocalLastModificationTime

**Canonical name:** PidLidSharingLocalLastModificationTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A23

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalLastMod

## 2.256 PidLidSharingLocalName

**Canonical name:** PidLidSharingLocalName

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalName

## 2.257 PidLidSharingLocalPath

**Canonical name:** PidLidSharingLocalPath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalPath

## 2.258 PidLidSharingLocalStoreUid

**Canonical name:** PidLidSharingLocalStoreUid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A49

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalStoreUid

## 2.259 PidLidSharingLocalType

**Canonical name:** PidLidSharingLocalType

**Description:** Contains the value of the **PidTagContainerClass** property (section [2.633](#)) of the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A14

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.10

**Alternate names:** dispidSharingLocalType

## 2.260 PidLidSharingLocalUid

**Canonical name:** PidLidSharingLocalUid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A10

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalUid

## 2.261 PidLidSharingOriginalMessageEntryId

**Canonical name:** PidLidSharingOriginalMessageEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A29

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingOriginalMessageEid

## 2.262 PidLidSharingParentBindingEntryId

**Canonical name:** PidLidSharingParentBindingEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingParentBindingEid

## 2.263 PidLidSharingParticipants

**Canonical name:** PidLidSharingParticipants

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingParticipants

## 2.264 PidLidSharingPermissions

**Canonical name:** PidLidSharingPermissions

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingPermissions

## 2.265 PidLidSharingProviderExtension

**Canonical name:** PidLidSharingProviderExtension

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingProviderExtension

## 2.266 PidLidSharingProviderGuid

**Canonical name:** PidLidSharingProviderGuid

**Description:** Contains the value "%xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.46".

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A01

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.12

**Alternate names:** dispidSharingProviderGuid

## 2.267 PidLidSharingProviderName

**Canonical name:** PidLidSharingProviderName

**Description:** Contains a user-displayable name of the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A02

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.14

**Alternate names:** dispidSharingProviderName

## 2.268 PidLidSharingProviderUrl

**Canonical name:** PidLidSharingProviderUrl

**Description:** Contains a URL related to the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A03

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.16

**Alternate names:** dispidSharingProviderUrl

## 2.269 PidLidSharingRangeEnd

**Canonical name:** PidLidSharingRangeEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A47

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRangeEnd



## 2.270 PidLidSharingRangeStart

**Canonical name:** PidLidSharingRangeStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A46

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRangeStart

## 2.271 PidLidSharingReciprocation

**Canonical name:** PidLidSharingReciprocation

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingReciprocation

## 2.272 PidLidSharingRemoteByteSize

**Canonical name:** PidLidSharingRemoteByteSize

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Consuming reference:** [MS-OXSHARE]

**Alternate names:** dispidSharingRemoteByteSize

## 2.273 PidLidSharingRemoteComment

**Canonical name:** PidLidSharingRemoteComment

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteComment

## 2.274 PidLidSharingRemoteCrc

**Canonical name:** PidLidSharingRemoteCrc

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteCrc

## 2.275 PidLidSharingRemoteLastModificationTime

**Canonical name:** PidLidSharingRemoteLastModificationTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A22

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteLastMod

## 2.276 PidLidSharingRemoteMessageCount

**Canonical name:** PidLidSharingRemoteMessageCount

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4F

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteMsgCount

## 2.277 PidLidSharingRemoteName

**Canonical name:** PidLidSharingRemoteName

**Description:** Contains the value of the **PidTagDisplayName** property (section [2.667](#)) on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A05

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.1

**Alternate names:** dispidSharingRemoteName

## 2.278 PidLidSharingRemotePass

**Canonical name:** PidLidSharingRemotePass

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemotePass

## 2.279 PidLidSharingRemotePath

**Canonical name:** PidLidSharingRemotePath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A04

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemotePath

## 2.280 PidLidSharingRemoteStoreUid

**Canonical name:** PidLidSharingRemoteStoreUid

**Description:** Contains a hexadecimal string representation of the value of the **PidTagStoreEntryId** property (section [2.1016](#)) on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A48

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.3

**Alternate names:** dispidSharingRemoteStoreUid

## 2.281 PidLidSharingRemoteType

**Canonical name:** PidLidSharingRemoteType

**Description:** Contains the same value as the **PidLidSharingLocalType** property (section [2.259](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.5

**Alternate names:** dispidSharingRemoteType

## 2.282 PidLidSharingRemoteUid

**Canonical name:** PidLidSharingRemoteUid

**Description:** Contains the EntryID of the folder being shared.

**Property set:** PSTID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A06

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.7

**Alternate names:** dispidSharingRemoteUid

## 2.283 PidLidSharingRemoteUser

**Canonical name:** PidLidSharingRemoteUser

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0C

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteUser

## 2.284 PidLidSharingRemoteVersion

**Canonical name:** PidLidSharingRemoteVersion

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteVersion

## 2.285 PidLidSharingResponseTime

**Canonical name:** PidLidSharingResponseTime

**Description:** Contains the time at which the recipient (1) of the sharing request sent a sharing response.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A28

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.4.1

**Alternate names:** dispidSharingResponseTime

## 2.286 PidLidSharingResponseType

**Canonical name:** PidLidSharingResponseType

**Description:** Contains the type of response with which the recipient (1) of the sharing request responded.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A27

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.4.2

**Alternate names:** dispidSharingResponseType

## 2.287 PidLidSharingRoamLog

**Canonical name:** PidLidSharingRoamLog

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4E

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRoamLog

## 2.288 PidLidSharingStart

**Canonical name:** PidLidSharingStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A25

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStart

## 2.289 PidLidSharingStatus

**Canonical name:** PidLidSharingStatus

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A00

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStatus

## 2.290 PidLidSharingStop

**Canonical name:** PidLidSharingStop

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A26

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStop

## 2.291 PidLidSharingSyncFlags

**Canonical name:** PidLidSharingSyncFlags

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A60

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingSyncFlags

## 2.292 PidLidSharingSyncInterval

**Canonical name:** PidLidSharingSyncInterval

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingSyncInterval

## 2.293 PidLidSharingTimeToLive

**Canonical name:** PidLidSharingTimeToLive

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingTimeToLive



## 2.294 PidLidSharingTimeToLiveAuto

**Canonical name:** PidLidSharingTimeToLiveAuto

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A56

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingTimeToLiveAuto

## 2.295 PidLidSharingWorkingHoursDays

**Canonical name:** PidLidSharingWorkingHoursDays

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A42

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursDays

## 2.296 PidLidSharingWorkingHoursEnd

**Canonical name:** PidLidSharingWorkingHoursEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A41

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursEnd

## 2.297 PidLidSharingWorkingHoursStart

**Canonical name:** PidLidSharingWorkingHoursStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A40

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursStart

## 2.298 PidLidSharingWorkingHoursTimeZone

**Canonical name:** PidLidSharingWorkingHoursTimeZone

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A43

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursTZ

## 2.299 PidLidSideEffects

**Canonical name:** PidLidSideEffects

**Description:** Specifies how a Message object is handled by the client in relation to certain user interface actions by the user, such as deleting a message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008510

**Data type:** PtypInteger32, 0x0003

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.16

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidSideEffects

### 2.300 PidLidSingleBodyICal

**Canonical name:** PidLidSingleBodyICal

**Description:** Indicates that the original MIME message contained a single **MIME** part.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXCICAL\]](#) section 2.2.2

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** IsSingleBodyICal, dispidIsSingleBodyICal

### 2.301 PidLidSmartNoAttach

**Canonical name:** PidLidSmartNoAttach

**Description:** Indicates whether the Message object has no end-user visible attachments.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008514

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.14

**Alternate names:** dispidSmartNoAttach

### 2.302 PidLidSpamOriginalFolder

**Canonical name:** PidLidSpamOriginalFolder

**Description:** Specifies which folder a message was in before it was filtered into the Junk E-mail folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000859C

**Data type:** PtypBinary, 0x0102

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.1

**Alternate names:** dispidSpamOriginalFolder

### 2.303 PidLidStartRecurrenceDate

**Canonical name:** PidLidStartRecurrenceDate

**Description:** Identifies the start date of the recurrence pattern.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/start\_recur\_date

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.66

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_START\_RECUR\_DATE

### 2.304 PidLidStartRecurrenceTime

**Canonical name:** PidLidStartRecurrenceTime

**Description:** Identifies the start time of the recurrence pattern.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000E

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/start\_recur\_time

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.67

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_START\_RECUR\_TIME

### 2.305 PidLidTaskAcceptanceState

**Canonical name:** PidLidTaskAcceptanceState

**Description:** Indicates the acceptance state of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812A

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.30

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskDelegValue

### 2.306 PidLidTaskAccepted

**Canonical name:** PidLidTaskAccepted

**Description:** Indicates whether a task assignee has replied to a **task request** for this **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008108

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.7

**Consuming reference:** [\[MS-OXOSFLD\]](#)

**Alternate names:** dispidTaskAccepted

### 2.307 PidLidTaskActualEffort

**Canonical name:** PidLidTaskActualEffort

**Description:** Indicates the number of minutes that the user actually spent working on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008110

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskActualEffort

### 2.308 PidLidTaskAssigner

**Canonical name:** PidLidTaskAssigner

**Description:** Specifies the name of the user that last assigned the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008121

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.24

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskDelegator

### 2.309 PidLidTaskAssigners

**Canonical name:** PidLidTaskAssigners

**Description:** Contains a stack of entries, each of which represents a task assigner.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008117

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.16

**Alternate names:** dispidTaskMyDelegators

### 2.310 PidLidTaskComplete

**Canonical name:** PidLidTaskComplete

**Description:** Indicates that the task is complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811C

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskComplete

### 2.311 PidLidTaskCustomFlags

**Canonical name:** PidLidTaskCustomFlags

**Description:** The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008139

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.33

**Alternate names:** dispidTaskCustomFlags

### 2.312 PidLidTaskDateCompleted

**Canonical name:** PidLidTaskDateCompleted

**Description:** Specifies the date when the user completed work on the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000810F

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.9

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#)

**Alternate names:** dispidTaskDateCompleted

### 2.313 PidLidTaskDeadOccurrence

**Canonical name:** PidLidTaskDeadOccurrence

**Description:** Indicates whether new occurrences remain to be generated.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008109

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.8

**Alternate names:** dispidTaskDeadOccur

### 2.314 PidLidTaskDueDate

**Canonical name:** PidLidTaskDueDate

**Description:** Specifies the date by which the user expects work on the task to be complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008105

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskDueDate

### 2.315 PidLidTaskEstimatedEffort

**Canonical name:** PidLidTaskEstimatedEffort

**Description:** Indicates the number of minutes that the user expects to work on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008111

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskEstimatedEffort

### 2.316 PidLidTaskFCreator

**Canonical name:** PidLidTaskFCreator

**Description:** Indicates that the Task object was originally created by the action of the current user or user agent instead of by the processing of a task request.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811E

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.21

**Alternate names:** dispidTaskFCreator

### 2.317 PidLidTaskFFixOffline

**Canonical name:** PidLidTaskFFixOffline

**Description:** Indicates the accuracy of the **PidLidTaskOwner** property (section [2.328](#)).

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812C

**Data type:** PtypBoolean, 0x000B



**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.31

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskFFixOffline

### 2.318 PidLidTaskFRecurring

**Canonical name:** PidLidTaskFRecurring

**Description:** Indicates whether the task includes a recurrence pattern.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008126

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.28

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskFRecur

### 2.319 PidLidTaskGlobalId

**Canonical name:** PidLidTaskGlobalId

**Description:** Contains a unique GUID for this task, which is used to locate an existing task upon receipt of a task response or task update.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008519

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.32

**Alternate names:** dispidTaskGlobalObjId

### 2.320 PidLidTaskHistory

**Canonical name:** PidLidTaskHistory

**Description:** Indicates the type of change that was last made to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811A

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.18

**Alternate names:** dispidTaskHistory

### 2.321 PidLidTaskLastDelegate

**Canonical name:** PidLidTaskLastDelegate

**Description:** Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008125

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.27

**Alternate names:** dispidTaskLastDelegate

### 2.322 PidLidTaskLastUpdate

**Canonical name:** PidLidTaskLastUpdate

**Description:** Contains the date and time of the most recent change made to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008115

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.10

**Alternate names:** dispidTaskLastUpdate

### 2.323 PidLidTaskLastUser

**Canonical name:** PidLidTaskLastUser

**Description:** Contains the name of the most recent user to have been the owner of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008122

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.25

**Alternate names:** dispidTaskLastUser

### 2.324 PidLidTaskMode

**Canonical name:** PidLidTaskMode

**Description:** Specifies the assignment status of the embedded Task object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008518

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.3.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** dispidTaskMode

### 2.325 PidLidTaskMultipleRecipients

**Canonical name:** PidLidTaskMultipleRecipients

**Description:** Provides optimization hints about the recipients (2) of a Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008120

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.23

**Alternate names:** dispidTaskMultRecips

### 2.326 PidLidTaskNoCompute

**Canonical name:** PidLidTaskNoCompute

**Description:** Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008124

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.35

**Consuming reference:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskNoCompute

### 2.327 PidLidTaskOrdinal

**Canonical name:** PidLidTaskOrdinal

**Description:** Provides an aid to custom sorting of Task objects.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008123

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.26

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOrdinal

### 2.328 PidLidTaskOwner

**Canonical name:** PidLidTaskOwner

**Description:** Contains the name of the owner of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811F

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.22

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOwner

### 2.329 PidLidTaskOwnership

**Canonical name:** PidLidTaskOwnership

**Description:** Indicates the role of the current user relative to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008129

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.29

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOwnership

### 2.330 PidLidTaskRecurrence

**Canonical name:** PidLidTaskRecurrence

**Description:** Contains a **RecurrencePattern** structure that provides information about **recurring tasks**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008116

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.15

**Consuming references:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskRecur

### 2.331 PidLidTaskResetReminder

**Canonical name:** PidLidTaskResetReminder

**Description:** Indicates whether future **instances** of recurring tasks need reminders, even though the value of the **PidLidReminderSet** property (section [2.222](#)) is 0x00.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008107

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.6

**Consuming references:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskResetReminder

### 2.332 PidLidTaskRole

**Canonical name:** PidLidTaskRole

**Description:** Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008127

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.34

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskRole

### 2.333 PidLidTaskStartDate

**Canonical name:** PidLidTaskStartDate

**Description:** Specifies the date on which the user expects work on the task to begin.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008104

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.4

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskStartDate

### 2.334 PidLidTaskState

**Canonical name:** PidLidTaskState

**Description:** Indicates the current assignment state of the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008113

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.14

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskState

### 2.335 PidLidTaskStatus

**Canonical name:** PidLidTaskStatus

**Description:** Specifies the status of a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008101

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskStatus

### 2.336 PidLidTaskStatusOnComplete

**Canonical name:** PidLidTaskStatusOnComplete

**Description:** Indicates whether the task assignee has been requested to send an e-mail message update upon completion of the assigned task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008119

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.17

**Alternate names:** dispidTaskSOC

### 2.337 PidLidTaskUpdates

**Canonical name:** PidLidTaskUpdates

**Description:** Indicates whether the task assignee has been requested to send a task update when the assigned Task object changes.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811B

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.19

**Alternate names:** dispidTaskUpdates

### 2.338 PidLidTaskVersion

**Canonical name:** PidLidTaskVersion

**Description:** Indicates which copy is the latest update of a Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008112

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.13

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskVersion

### 2.339 PidLidTeamTask

**Canonical name:** PidLidTeamTask

**Description:** This property is set by the client but is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008103

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.36

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTeamTask

### 2.340 PidLidTimeZone

**Canonical name:** PidLidTimeZone

**Description:** Specifies information about the time zone of a recurring meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/time\\_zone](http://schemas.microsoft.com/mapi/time_zone)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.6



**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_TIME\_ZONE

### 2.341 PidLidTimeZoneDescription

**Canonical name:** PidLidTimeZoneDescription

**Description:** Specifies a human-readable description of the time zone that is represented by the data in the **PidLidTimeZoneStruct** property (section [2.342](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008234

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/timezonedesc>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.40

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneDesc

### 2.342 PidLidTimeZoneStruct

**Canonical name:** PidLidTimeZoneStruct

**Description:** Specifies time zone information for a recurring meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008233

**Data type:** PtypBinary, 0x0102

**WebDAV:** <http://schemas.microsoft.com/mapi/timezonestruct>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.39

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneStruct

### 2.343 PidLidToAttendeesString

**Canonical name:** PidLidToAttendeesString

**Description:** Contains a list of all of the sendable attendees who are also required attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823B

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.17

**Alternate names:** dispidToAttendeesString

#### 2.344 PidLidToDoOrdinalDate

**Canonical name:** PidLidToDoOrdinalDate

**Description:** Contains the current time, in UTC, which is used to determine the sort order of objects in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A0

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.13

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoOrdinalDate

#### 2.345 PidLidToDoSubOrdinal

**Canonical name:** PidLidToDoSubOrdinal

**Description:** Contains the numerals 0 through 9 that are used to break a tie when the **PidLidToDoOrdinalDate** property (section [2.344](#)) is used to perform a sort of objects.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A1

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.14

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoSubOrdinal

#### 2.346 PidLidToDoTitle

**Canonical name:** PidLidToDoTitle

**Description:** Contains user-specifiable text to identify this Message object in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A4

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidToDoTitle

## 2.347 PidLidUseTnef

**Canonical name:** PidLidUseTnef

**Description:** Specifies whether **Transport Neutral Encapsulation Format (TNEF)** is to be included on a message when the message is converted from TNEF to MIME or SMTP format.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008582

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.66

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidUseTNEF

## 2.348 PidLidValidFlagStringProof

**Canonical name:** PidLidValidFlagStringProof

**Description:** Contains the value of the **PidTagMessageDeliveryTime** property (section [2.778](#)) when modifying the **PidLidFlagRequest** property (section [2.136](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BF

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidValidFlagStringProof

## 2.349 PidLidVerbResponse

**Canonical name:** PidLidVerbResponse

**Description:** Specifies the voting option that a respondent has selected.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008524

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.75

**Alternate names:** dispidVerbResponse

## 2.350 PidLidVerbStream

**Canonical name:** PidLidVerbStream

**Description:** Specifies what voting responses the user can make in response to the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008520

**Data type:** PtypBinary, 0x0102

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.74

**Alternate names:** dispidVerbStream

## 2.351 PidLidWeddingAnniversaryLocal

**Canonical name:** PidLidWeddingAnniversaryLocal

**Description:** Specifies the wedding anniversary of the contact, at midnight in the client's local time zone, and is saved without any time zone conversions.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DF

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.5

**Alternate names:** dispidApptAnniversaryLocal

## 2.352 PidLidWeekInterval

**Canonical name:** PidLidWeekInterval

**Description:** Identifies the number of weeks that occur between each meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000012

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/week\_interval

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.71

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_WEEK\_INTERVAL

### 2.353 PidLidWhere

**Canonical name:** PidLidWhere

**Description:** Contains the value of the **PidLidLocation** property (section [2.159](#)) from the associated Meeting object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000002

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/where

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.3

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_WHERE

### 2.354 PidLidWorkAddress

**Canonical name:** PidLidWorkAddress

**Description:** Specifies the complete address of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801B

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:workaddress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidWorkAddress

## 2.355 PidLidWorkAddressCity

**Canonical name:** PidLidWorkAddressCity

**Description:** Specifies the city or locality portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008046

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:l

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Alternate names:** dispidWorkAddressCity

## 2.356 PidLidWorkAddressCountry

**Canonical name:** PidLidWorkAddressCountry

**Description:** Specifies the country or region portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008049

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:co

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Alternate names:** dispidWorkAddressCountry

## 2.357 PidLidWorkAddressCountryCode

**Canonical name:** PidLidWorkAddressCountryCode

**Description:** Specifies the country code portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DB

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidWorkAddressCountryCode

## 2.358 PidLidWorkAddressPostalCode

**Canonical name:** PidLidWorkAddressPostalCode

**Description:** Specifies the postal code (ZIP code) portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008048

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postalcode

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Alternate names:** dispidWorkAddressPostalCode

## 2.359 PidLidWorkAddressPostOfficeBox

**Canonical name:** PidLidWorkAddressPostOfficeBox

**Description:** Specifies the post office box portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postofficebox

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Alternate names:** dispidWorkAddressPostOfficeBox

## 2.360 PidLidWorkAddressState

**Canonical name:** PidLidWorkAddressState

**Description:** Specifies the state or province portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008047

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:st

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Alternate names:** dispidWorkAddressState

### 2.361 PidLidWorkAddressStreet

**Canonical name:** PidLidWorkAddressStreet

**Description:** Specifies the street portion of the contact's work address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:street

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

**Alternate names:** dispidWorkAddressStreet

### 2.362 PidLidYearInterval

**Canonical name:** PidLidYearInterval

**Description:** Indicates the yearly interval of the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000014

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/year\_interval

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.73

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_YEAR\_INTERVAL

### 2.363 PidLidYomiCompanyName

**Canonical name:** PidLidYomiCompanyName

**Description:** Specifies the phonetic pronunciation of the contact's company name.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802E

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/yomiorganization

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.8



**Alternate names:** dispidYomiCompanyName

### 2.364 PidLidYomiFirstName

**Canonical name:** PidLidYomiFirstName

**Description:** Specifies the phonetic pronunciation of the contact's given name.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802C

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/yomifirstname

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.9

**Alternate names:** dispidYomiFirstName

### 2.365 PidLidYomiLastName

**Canonical name:** PidLidYomiLastName

**Description:** Specifies the phonetic pronunciation of the contact's surname.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802D

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/yomilastname

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.10

**Alternate names:** dispidYomiLastName

### 2.366 PidNameAcceptLanguage

**Canonical name:** PidNameAcceptLanguage

**Description:** Contains the value of the MIME Accept-Language header.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Accept-Language

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.42

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** AcceptLanguage

### 2.367 PidNameApplicationName

**Canonical name:** PidNameApplicationName

**Description:** Specifies the application used to open the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** AppName

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.9

**Alternate names:** urn:schemas-microsoft-com:office:office#NameOfApplication

### 2.368 PidNameAttachmentMacContentType

**Canonical name:** PidNameAttachmentMacContentType

**Description:** Contains the Content-Type of the Mac attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentMacContentType

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.369 PidNameAttachmentMacInfo

**Canonical name:** PidNameAttachmentMacInfo

**Description:** Contains the headers and resource fork data associated with the Mac attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentMacInfo

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.370 PidNameAudioNotes

**Canonical name:** PidNameAudioNotes

**Description:** Contains textual annotations to a voice message after it has been delivered to the user's mailbox.

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** UMAudioNotes

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.15

**Alternate names:** UMAudioNotes

## 2.371 PidNameAuthor

**Canonical name:** PidNameAuthor

**Description:** Specifies the author of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Author

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.3

**Alternate names:** urn:schemas-microsoft-com:office:office#Author

## 2.372 PidNameAutomaticSpeechRecognitionData

**Canonical name:** PidNameAutomaticSpeechRecognitionData

**Description:** Contains an unprotected voice message.

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** AsrData

**Data type:** PtypBinary, 0x0102

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.13

## 2.373 PidNameByteCount

**Canonical name:** PidNameByteCount

**Description:** Specifies the size, in bytes, of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ByteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.22

**Alternate names:** urn:schemas-microsoft-com:office:office#Bytes

### 2.374 PidNameCalendarAttendeeRole

**Canonical name:** PidNameCalendarAttendeeRole

**Description:** Specifies the role of the attendee.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:attendeerole

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.7

**Alternate names:** urn:schemas:calendar:attendeerole

### 2.375 PidNameCalendarBusystatus

**Canonical name:** PidNameCalendarBusystatus

**Description:** Specifies whether the attendee is busy at the time of an appointment on their calendar.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:busystatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.8

**Alternate names:** urn:schemas:calendar:busystatus

### 2.376 PidNameCalendarContact

**Canonical name:** PidNameCalendarContact

**Description:** Identifies the name of a contact who is an attendee of a meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contact

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.9

**Alternate names:** urn:schemas:calendar:contact

### 2.377 PidNameCalendarContactUrl

**Canonical name:** PidNameCalendarContactUrl

**Description:** Identifies the URL where you can access contact information in **HTML** format.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contacturl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.10

**Alternate names:** urn:schemas:calendar:contacturl

### 2.378 PidNameCalendarCreated

**Canonical name:** PidNameCalendarCreated

**Description:** Identifies the date and time, in UTC, when the organizer created the appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:created

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.11

**Alternate names:** urn:schemas:calendar:created

### 2.379 PidNameCalendarDescriptionUrl

**Canonical name:** PidNameCalendarDescriptionUrl

**Description:** Specifies the URL of a resource that contains a description of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:descriptionurl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.12

**Alternate names:** urn:schemas:calendar:descriptionurl

### 2.380 PidNameCalendarDuration

**Canonical name:** PidNameCalendarDuration

**Description:** Identifies the duration, in seconds, of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:duration

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.13

**Alternate names:** urn:schemas:calendar:duration

### 2.381 PidNameCalendarExceptionDate

**Canonical name:** PidNameCalendarExceptionDate

**Description:** Identifies a list of dates that are exceptions to a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.14

**Alternate names:** urn:schemas:calendar:exdate

### 2.382 PidNameCalendarExceptionRule

**Canonical name:** PidNameCalendarExceptionRule

**Description:** Specifies an exception rule for a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.15

**Alternate names:** urn:schemas:calendar:exrule

### 2.383 PidNameCalendarGeoLatitude

**Canonical name:** PidNameCalendarGeoLatitude

**Description:** Specifies the geographical latitude of the location of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolatitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.16

**Alternate names:** urn:schemas:calendar:geolatitude

### 2.384 PidNameCalendarGeoLongitude

**Canonical name:** PidNameCalendarGeoLongitude

**Description:** Specifies the geographical longitude of the location of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolongitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.17

**Alternate names:** urn:schemas:calendar:geolongitude

### 2.385 PidNameCalendarInstanceType

**Canonical name:** PidNameCalendarInstanceType

**Description:** Specifies the type of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:instancetype

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.18

**Alternate names:** urn:schemas:calendar:instancetype

### 2.386 PidNameCalendarIsOrganizer

**Canonical name:** PidNameCalendarIsOrganizer

**Description:** Specifies whether an attendee is the organizer of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:isorganizer

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.19

**Alternate names:** urn:schemas:calendar:isorganizer

### 2.387 PidNameCalendarLastModified

**Canonical name:** PidNameCalendarLastModified

**Description:** Specifies the date and time, in UTC, when an appointment was last modified.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:lastmodified

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.20

**Alternate names:** urn:schemas:calendar:lastmodified

### 2.388 PidNameCalendarLocationUrl

**Canonical name:** PidNameCalendarLocationUrl

**Description:** Specifies a URL with location information in HTML format.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.21

**Alternate names:** urn:schemas:calendar:locationurl

### 2.389 PidNameCalendarMeetingStatus

**Canonical name:** PidNameCalendarMeetingStatus

**Description:** Specifies the status of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:meetingstatus



**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.22

**Alternate names:** urn:schemas:calendar:meetingstatus

### 2.390 PidNameCalendarMethod

**Canonical name:** PidNameCalendarMethod

**Description:** Specifies the **iCalendar** method that is associated with an Appointment object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:method

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.23

**Alternate names:** urn:schemas:calendar:method

### 2.391 PidNameCalendarProductId

**Canonical name:** PidNameCalendarProductId

**Description:** Identifies the product that created the iCalendar-formatted stream.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:prodid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.24

**Alternate names:** urn:schemas:calendar:prodid

### 2.392 PidNameCalendarRecurrenceIdRange

**Canonical name:** PidNameCalendarRecurrenceIdRange

**Description:** Specifies which instances of a recurring appointment are being referred to.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:recurrenceidrange

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.25

**Alternate names:** urn:schemas:calendar:recurrenceidrange

### 2.393 PidNameCalendarReminderOffset

**Canonical name:** PidNameCalendarReminderOffset

**Description:** Identifies the number of seconds before an appointment starts that a reminder is to be displayed.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:reminderoffset

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.26

**Alternate names:** urn:schemas:calendar:reminderoffset

### 2.394 PidNameCalendarResources

**Canonical name:** PidNameCalendarResources

**Description:** Identifies a list of resources, such as rooms and video equipment, that are available for an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:resources

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.27

**Alternate names:** urn:schemas:calendar:resources

### 2.395 PidNameCalendarRsvp

**Canonical name:** PidNameCalendarRsvp

**Description:** Specifies whether the organizer of an appointment or meeting requested a response.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rsvp

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.28

**Alternate names:** urn:schemas:calendar:rsvp

## 2.396 PidNameCalendarSequence

**Canonical name:** PidNameCalendarSequence

**Description:** Specifies the sequence number of a version of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:sequence

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.29

**Alternate names:** urn:schemas:calendar:sequence

## 2.397 PidNameCalendarTimeZone

**Canonical name:** PidNameCalendarTimeZone

**Description:** Specifies the time zone of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezone

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.30

**Alternate names:** urn:schemas:calendar:timezone

## 2.398 PidNameCalendarTimeZoneId

**Canonical name:** PidNameCalendarTimeZoneId

**Description:** Specifies the time zone identifier of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezoneid

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.31

**Alternate names:** urn:schemas:calendar:timezoneid

## 2.399 PidNameCalendarTransparent

**Canonical name:** PidNameCalendarTransparent

**Description:** Specifies whether an appointment or meeting is visible to busy time searches.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:transparent

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.32

**Alternate names:** urn:schemas:calendar:transparent

## 2.400 PidNameCalendarUid

**Canonical name:** PidNameCalendarUid

**Description:** Specifies the unique identifier of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.33

**Alternate names:** urn:schemas:calendar:uid

## 2.401 PidNameCalendarVersion

**Canonical name:** PidNameCalendarVersion

**Description:** Identifies the version of the iCalendar specification, as specified in [\[MS-OXCICAL\]](#) section 2.1.3.1.1.3, that is required to correctly interpret an iCalendar object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:version

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.34

**Alternate names:** urn:schemas:calendar:version

## 2.402 PidNameCategory

**Canonical name:** PidNameCategory

**Description:** Specifies the category of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Category

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.18

**Alternate names:** urn:schemas-microsoft-com:office:office#Category

#### 2.403 PidNameCharacterCount

**Canonical name:** PidNameCharacterCount

**Description:** Specifies the character count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CharCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.16

**Alternate names:** urn:schemas-microsoft-com:office:office#Characters

#### 2.404 PidNameComments

**Canonical name:** PidNameComments

**Description:** Specifies the comments of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Comments

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.5

**Alternate names:** urn:schemas-microsoft-com:office:office#Comments

#### 2.405 PidNameCompany

**Canonical name:** PidNameCompany

**Description:** Specifies the company for which the file was created.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Company

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.21

**Alternate names:** urn:schemas-microsoft-com:office:office#Company

## 2.406 PidNameContentBase

**Canonical name:** PidNameContentBase

**Description:** Specifies the value of the MIME Content-Base header, which defines the base **URI** for resolving relative URLs contained within the **message body (2)**.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Base

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.41

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** BodyContentBase

## 2.407 PidNameContentClass

**Canonical name:** PidNameContentClass

**Description:** Contains a string that identifies the type of content of a Message object.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Class

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.48

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** DAV:contentclass, urn:schemas:mailheader:content-class

## 2.408 PidNameContentType

**Canonical name:** PidNameContentType

**Description:** Specifies the type of the **body part** content.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Type

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.50

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:content-type

#### 2.409 PidNameCreateDateTimeReadOnly

**Canonical name:** PidNameCreateDateTimeReadOnly

**Description:** Specifies the time, in UTC, that the file was first created.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CreateDtmRo

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.12

**Alternate names:** urn:schemas-microsoft-com:office:office#Created

#### 2.410 PidNameCrossReference

**Canonical name:** PidNameCrossReference

**Description:** Contains the name of the host (with [domains](#) omitted) and a white-space-separated list of colon-separated pairs of newsgroup names and message numbers.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Xref

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.3

**Alternate names:** urn:schemas:mailheader:xref

#### 2.411 PidNameDavId

**Canonical name:** PidNameDavId

**Description:** Specifies a unique ID for the calendar item.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:id

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.2

**Alternate names:** DAV:id

#### 2.412 PidNameDavIsCollection

**Canonical name:** PidNameDavIsCollection

**Description:** Indicates whether a Calendar object is a collection.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:iscollection

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.3

**Alternate names:** DAV:iscollection

#### 2.413 PidNameDavIsStructuredDocument

**Canonical name:** PidNameDavIsStructuredDocument

**Description:** Indicates whether a Calendar object is a structured document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:isstructureddocument

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.4

**Alternate names:** DAV:isstructureddocument

#### 2.414 PidNameDavParentName

**Canonical name:** PidNameDavParentName

**Description:** Specifies the name of the **Folder object** that contains the Calendar object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:parentname

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.5

**Alternate names:** DAV:parentname



## 2.415 PidNameDavUid

**Canonical name:** PidNameDavUid

**Description:** Specifies the unique identifier for an item.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.6

**Alternate names:** DAV:uid

## 2.416 PidNameDocumentParts

**Canonical name:** PidNameDocumentParts

**Description:** Specifies the title of each part of the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DocParts

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.29

**Alternate names:** urn:schemas-microsoft-com:office:office#PartTitles

## 2.417 PidNameEditTime

**Canonical name:** PidNameEditTime

**Description:** Specifies the time that the file was last edited.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** EditTime

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.10

**Alternate names:** urn:schemas-microsoft-com:office:office#TotalTime

## 2.418 PidNameExchangeIntendedBusyStatus

**Canonical name:** PidNameExchangeIntendedBusyStatus

**Description:** Specifies the busy status of the user during an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/intendedbusystatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.1

**Alternate names:** http://schemas.microsoft.com/exchange/intendedbusystatus

#### 2.419 PidNameExchangeJunkEmailMoveStamp

**Canonical name:** PidNameExchangeJunkEmailMoveStamp

**Description:** Indicates that the message is not to be processed by a **spam filter**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/junkemailmovestamp

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXORSS\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/junkemailmovestamp

#### 2.420 PidNameExchangeModifyExceptionStructure

**Canonical name:** PidNameExchangeModifyExceptionStructure

**Description:** Specifies a structure that modifies an exception to the recurrence.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/modifyexceptionstruct

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.2

**Alternate names:** http://schemas.microsoft.com/exchange/modifyexceptionstruct

#### 2.421 PidNameExchangeNoModifyExceptions

**Canonical name:** PidNameExchangeNoModifyExceptions

**Description:** Indicates whether exceptions to a recurring appointment can be modified.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/nomodifyexceptions

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.3

**Alternate names:** http://schemas.microsoft.com/exchange/nomodifyexceptions

## 2.422 PidNameExchangePatternEnd

**Canonical name:** PidNameExchangePatternEnd

**Description:** Identifies the maximum time when an instance of a recurring appointment ends.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/patternend

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.4

**Alternate names:** http://schemas.microsoft.com/exchange/patternend

## 2.423 PidNameExchangePatternStart

**Canonical name:** PidNameExchangePatternStart

**Description:** Identifies the absolute minimum time when an instance of a recurring appointment starts.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/patternstart

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.5

**Alternate names:** http://schemas.microsoft.com/exchange/patternstart

## 2.424 PidNameExchangeReminderInterval

**Canonical name:** PidNameExchangeReminderInterval

**Description:** Identifies the time, in seconds, between reminders.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/reminderinterval

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.6

**Consuming reference:** [MS-XWDCAL]

**Alternate names:** <http://schemas.microsoft.com/exchange/reminderinterval>

## 2.425 PidNameExchDatabaseSchema

**Canonical name:** PidNameExchDatabaseSchema

**Description:** Specifies an array of URLs that identifies other folders within the same message store that contain schema definition items.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:baseschema

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.1

**Alternate names:** urn:schemas-microsoft-com:exch-data:baseschema

## 2.426 PidNameExchDataExpectedContentClass

**Canonical name:** PidNameExchDataExpectedContentClass

**Description:** Specifies an array of names that indicates the expected content **classes** of items within a folder.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:expected-content-class

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.2

**Alternate names:** urn:schemas-microsoft-com:exch-data:expected-content-class

## 2.427 PidNameExchDataSchemaCollectionReference

**Canonical name:** PidNameExchDataSchemaCollectionReference

**Description:** Specifies an array of names that indicates the expected content classes of items within a folder.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.3

**Alternate names:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

## 2.428 PidNameExtractedAddresses

**Canonical name:** PidNameExtractedAddresses

**Description:** Contains an **XML document** with a single **AddressSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedAddresses

**Data type:** **PtypString**, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.1

**Alternate names:** dispidXmlExtractedAddresses

## 2.429 PidNameExtractedContacts

**Canonical name:** PidNameExtractedContacts

**Description:** Contains an XML document with a single **ContactSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedContacts

**Data type:** **PtypString**, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.2

**Alternate names:** dispidXmlExtractedContacts

## 2.430 PidNameExtractedEmails

**Canonical name:** PidNameExtractedEmails

**Description:** Contains an XML document with a single **EmailSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedEmails

**Data type:** **PtypString**, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.3

**Alternate names:** dispidXmlExtractedEmails

## 2.431 PidNameExtractedMeetings

**Canonical name:** PidNameExtractedMeetings

**Description:** Contains an XML document with a single **MeetingSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedMeetings

**Data type:** **PtypString**, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.4

**Alternate names:** dispidXmlExtractedMeetings

## 2.432 PidNameExtractedPhones

**Canonical name:** PidNameExtractedPhones

**Description:** Contains an XML document with a single **PhoneSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedPhones

**Data type:** **PtypString**, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.5

**Alternate names:** dispidXmlExtractedPhones

## 2.433 PidNameExtractedTasks

**Canonical name:** PidNameExtractedTasks

**Description:** Contains an XML document with a single **TaskSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedTasks

**Data type:** **PtypString**, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.6

**Alternate names:** dispidXmlExtractedTasks

## 2.434 PidNameExtractedUrls

**Canonical name:** PidNameExtractedUrls

**Description:** Contains an XML document with a single **UrlSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedUrls

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.7

**Alternate names:** dispidXmlExtractedUrls

## 2.435 PidNameFrom

**Canonical name:** PidNameFrom

**Description:** Specifies the SMTP e-mail **alias** of the organizer of an appointment or meeting.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** From

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.35

**Alternate names:** urn:schemas:calendar:organizer

## 2.436 PidNameHeadingPairs

**Canonical name:** PidNameHeadingPairs

**Description:** Specifies which group of headings are indented in the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HeadingPairs

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.30

**Alternate names:** urn:schemas-microsoft-com:office:office#HeadingPairs

## 2.437 PidNameHiddenCount

**Canonical name:** PidNameHiddenCount

**Description:** Specifies the hidden value of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HiddenCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.27

**Alternate names:** urn:schemas-microsoft-com:office:office#HiddenSlides

## 2.438 PidNameHttpmailCalendar

**Canonical name:** PidNameHttpmailCalendar

**Description:** Specifies the URL for the Calendar folder for a particular user.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:calendar

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.1

**Alternate names:** urn:schemas:httpmail:calendar

## 2.439 PidNameHttpmailHtmlDescription

**Canonical name:** PidNameHttpmailHtmlDescription

**Description:** Specifies the HTML content of the message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:htmldescription

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.2

**Alternate names:** urn:schemas:httpmail:htmldescription

## 2.440 PidNameHttpmailSendMessage

**Canonical name:** PidNameHttpmailSendMessage

**Description:** Specifies the e-mail submission URI to which outgoing e-mail is submitted.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:sendmsg

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.3



**Alternate names:** urn:schemas:httpmail:sendmsg

#### 2.441 PidNameICalendarRecurrenceDate

**Canonical name:** PidNameICalendarRecurrenceDate

**Description:** Identifies an array of instances of a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.36

**Alternate names:** urn:schemas:calendar:rdate

#### 2.442 PidNameICalendarRecurrenceRule

**Canonical name:** PidNameICalendarRecurrenceRule

**Description:** Specifies the rule for the pattern that defines a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.37

**Alternate names:** urn:schemas:calendar:rrule

#### 2.443 PidNameInternetSubject

**Canonical name:** PidNameInternetSubject

**Description:** Specifies the subject of the message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.4.1

**Alternate names:** urn:schemas:mailheader:subject

## 2.444 PidNameKeywords

**Canonical name:** PidNameKeywords

**Description:** Contains keywords or categories for the Message object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Keywords

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.17

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Keywords,  
<http://schemas.microsoft.com/exchange/keywords-utf8>

## 2.445 PidNameLastAuthor

**Canonical name:** PidNameLastAuthor

**Description:** Specifies the most recent author of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastAuthor

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.7

**Alternate names:** urn:schemas-microsoft-com:office:office#LastAuthor

## 2.446 PidNameLastPrinted

**Canonical name:** PidNameLastPrinted

**Description:** Specifies the time, in UTC, that the file was last printed.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastPrinted

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.11

**Alternate names:** urn:schemas-microsoft-com:office:office#LastPrinted

## 2.447 PidNameLastSaveDateTime

**Canonical name:** PidNameLastSaveDateTime

**Description:** Specifies the time, in UTC, that the file was last saved.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastSaveDtm

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.13

**Alternate names:** urn:schemas-microsoft-com:office:office#LastSaved

## 2.448 PidNameLineCount

**Canonical name:** PidNameLineCount

**Description:** Specifies the number of lines in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LineCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.23

**Alternate names:** urn:schemas-microsoft-com:office:office#Lines

## 2.449 PidNameLinksDirty

**Canonical name:** PidNameLinksDirty

**Description:** Indicates whether the links in the document are up-to-date.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LinksDirty

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.31

**Alternate names:** urn:schemas-microsoft-com:office:office#LinksUpToDate

## 2.450 PidNameLocationUrl

**Canonical name:** PidNameLocationUrl

**Description:**

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Calendar

**Defining reference:**

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:calendar:locationurl, LocationUrl

## 2.451 PidNameManager

**Canonical name:** PidNameManager

**Description:** Specifies the manager of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Manager

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.20

**Alternate names:** urn:schemas-microsoft-com:office:office#Manager

## 2.452 PidNameMultimediaClipCount

**Canonical name:** PidNameMultimediaClipCount

**Description:** Specifies the number of multimedia clips in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** MMClipCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.28

**Alternate names:** urn:schemas-microsoft-com:office:office#MultimediaClips

## 2.453 PidNameNoteCount

**Canonical name:** PidNameNoteCount

**Description:** Specifies the number of notes in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** NoteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.26

**Alternate names:** urn:schemas-microsoft-com:office:office#Notes

#### 2.454 PidNameOMSAccountGuid

**Canonical name:** PidNameOMSAccountGuid

**Description:** Contains the GUID of the **SMS** account used to deliver the message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSAccountGuid

**Data type:** PtypString, 0x001F

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.1

#### 2.455 PidNameOMSMobileModel

**Canonical name:** PidNameOMSMobileModel

**Description:** Indicates the model of the mobile device used to send the SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSMobileModel

**Data type:** PtypString, 0x001F

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.6

#### 2.456 PidNameOMSScheduleTime

**Canonical name:** PidNameOMSScheduleTime

**Description:** Contains the time, in UTC, at which the client requested that the service provider send the SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSScheduleTime

**Data type:** PtypTime, 0x0040

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.2

## 2.457 PidNameOMSServiceType

**Canonical name:** PidNameOMSServiceType

**Description:** Contains the type of service used to send an SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSServiceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.3

## 2.458 PidNameOMSSourceType

**Canonical name:** PidNameOMSSourceType

**Description:** Contains the source of an SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSSourceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.4

## 2.459 PidNamePageCount

**Canonical name:** PidNamePageCount

**Description:** Specifies the page count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PageCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.14

**Alternate names:** urn:schemas-microsoft-com:office:office#Pages

## 2.460 PidNameParagraphCount

**Canonical name:** PidNameParagraphCount

**Description:** Specifies the number of paragraphs in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ParCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.24

**Alternate names:** urn:schemas-microsoft-com:office:office#Paragraphs

## 2.461 PidNamePhishingStamp

**Canonical name:** PidNamePhishingStamp

**Description:** Indicates whether a message is likely to be **phishing**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/outlook/phishingstamp

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXPHISH\]](#) section 2.2.1.1

## 2.462 PidNamePresentationFormat

**Canonical name:** PidNamePresentationFormat

**Description:** Specifies the presentation format of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PresFormat

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.19

**Alternate names:** urn:schemas-microsoft-com:office:office#PresentationFormat

## 2.463 PidNameQuarantineOriginalSender

**Canonical name:** PidNameQuarantineOriginalSender

**Description:** Specifies the original sender of a message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** quarantine-original-sender

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.4

## 2.464 PidNameRevisionNumber

**Canonical name:** PidNameRevisionNumber

**Description:** Specifies the revision number of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** RevNumber

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.8

**Alternate names:** urn:schemas-microsoft-com:office:office#Revision

## 2.465 PidNameRightsManagementLicense

**Canonical name:** PidNameRightsManagementLicense

**Description:** Specifies the value used to cache the **Use License** for the **rights-managed e-mail message**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DRMLicense

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXORMMS\]](#) section 2.2.1.1

## 2.466 PidNameScale

**Canonical name:** PidNameScale

**Description:** Indicates whether the image is to be scaled or cropped.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Scale

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.32

**Alternate names:** urn:schemas-microsoft-com:office:office#ScaleCrop

## 2.467 PidNameSecurity

**Canonical name:** PidNameSecurity

**Description:** Specifies the security level of the file attached to the Document object.



**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Security

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.17

**Alternate names:** urn:schemas-microsoft-com:office:office#Security

## 2.468 PidNameSlideCount

**Canonical name:** PidNameSlideCount

**Description:** Specifies the number of slides in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** SlideCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.25

**Alternate names:** urn:schemas-microsoft-com:office:office#Slides

## 2.469 PidNameSubject

**Canonical name:** PidNameSubject

**Description:** Specifies the subject of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Subject

## 2.470 PidNameTemplate

**Canonical name:** PidNameTemplate

**Description:** Specifies the template of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Template

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.6

**Alternate names:** urn:schemas-microsoft-com:office:office#Template

#### 2.471 PidNameThumbnail

**Canonical name:** PidNameThumbnail

**Description:** Specifies the data representing the thumbnail image of the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Thumbnail

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.33

**Alternate names:** urn:schemas-microsoft-com:office:office#ThumbNail

#### 2.472 PidNameTitle

**Canonical name:** PidNameTitle

**Description:** Specifies the title of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Title

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.1

**Alternate names:** urn:schemas-microsoft-com:office:office#Title

#### 2.473 PidNameWordCount

**Canonical name:** PidNameWordCount

**Description:** Specifies the word count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** WordCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.15

**Alternate names:** urn:schemas-microsoft-com:office:office#Words

#### 2.474 PidNameXCallId

**Canonical name:** PidNameXCallId

**Description:** Contains a unique identifier associated with the phone call.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallID

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.12

**Consuming reference:** [\[MS-OXCMAIL\]](#)

#### 2.475 PidNameXFaxNumberOfPages

**Canonical name:** PidNameXFaxNumberOfPages

**Description:** Specifies how many discrete pages are contained within an attachment representing a facsimile message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-FaxNumberOfPages

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.8

**Consuming reference:** [\[MS-OXCMAIL\]](#)

#### 2.476 PidNameXRequireProtectedPlayOnPhone

**Canonical name:** PidNameXRequireProtectedPlayOnPhone

**Description:** Indicates that the client only renders the message on a phone.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-RequireProtectedPlayOnPhone

**Data type:** PtypBoolean, 0x000B

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.14

#### 2.477 PidNameXSenderTelephoneNumber

**Canonical name:** PidNameXSenderTelephoneNumber

**Description:** Contains the telephone number of the caller associated with a voice mail message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallingTelephoneNumber

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.2

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.478 PidNameXSharingBrowseUrl

**Canonical name:** PidNameXSharingBrowseUrl

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Browse-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.479 PidNameXSharingCapabilities

**Canonical name:** PidNameXSharingCapabilities

**Description:** Contains a string representation of the value of the **PidLidSharingCapabilities** property (section [2.237](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Capabilities

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.2

## 2.480 PidNameXSharingConfigUrl

**Canonical name:** PidNameXSharingConfigUrl

**Description:** Contains the same value as the **PidLidSharingConfigurationUrl** property (section [2.238](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Config-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.4

### 2.481 PidNameXSharingExendedCaps

**Canonical name:** PidNameXSharingExendedCaps

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Exended-Caps

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

### 2.482 PidNameXSharingFlavor

**Canonical name:** PidNameXSharingFlavor

**Description:** Contains a hexadecimal string representation of the value of the **PidLidSharingFlavor** property (section [2.245](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Flavor

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.6

### 2.483 PidNameXSharingInstanceGuid

**Canonical name:** PidNameXSharingInstanceGuid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Instance-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.484 PidNameXSharingLocalType

**Canonical name:** PidNameXSharingLocalType

**Description:** Contains the same value as the **PidLidSharingLocalType** property (section [2.259](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Local-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.11

## 2.485 PidNameXSharingProviderGuid

**Canonical name:** PidNameXSharingProviderGuid

**Description:** Contains the hexadecimal string representation of the value of the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.13

## 2.486 PidNameXSharingProviderName

**Canonical name:** PidNameXSharingProviderName

**Description:** Contains the same value as the **PidLidSharingProviderName** property (section [2.267](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.15

## 2.487 PidNameXSharingProviderUrl

**Canonical name:** PidNameXSharingProviderUrl

**Description:** Contains the same value as the **PidLidSharingProviderUrl** property (section [2.268](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.17

## 2.488 PidNameXSharingRemoteName

**Canonical name:** PidNameXSharingRemoteName

**Description:** Contains the same value as the **PidLidSharingRemoteName** property (section [2.277](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.2

## 2.489 PidNameXSharingRemotePath

**Canonical name:** PidNameXSharingRemotePath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Path

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.490 PidNameXSharingRemoteStoreUid

**Canonical name:** PidNameXSharingRemoteStoreUid

**Description:** Contains the same value as the **PidLidSharingRemoteStoreUid** property (section [2.282](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Store-Uid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.4

## 2.491 PidNameXSharingRemoteType

**Canonical name:** PidNameXSharingRemoteType

**Description:** Contains the same value as the **PidLidSharingRemoteType** property (section [2.281](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.6

## 2.492 PidNameXSharingRemoteUid

**Canonical name:** PidNameXSharingRemoteUid

**Description:** Contains the same value as the **PidLidSharingRemoteUid** property (section [2.282](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Uid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.8

## 2.493 PidNameXVoiceMessageAttachmentOrder

**Canonical name:** PidNameXVoiceMessageAttachmentOrder

**Description:** Contains the list of names for the audio file attachments that are to be played as part of a message, in reverse order.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-AttachmentOrder

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.10

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.494 PidNameXVoiceMessageDuration

**Canonical name:** PidNameXVoiceMessageDuration

**Description:** Specifies the length of the attached audio message, in seconds.



**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageDuration

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.4

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.495 PidNameXVoiceMessageSenderName

**Canonical name:** PidNameXVoiceMessageSenderName

**Description:** Contains the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageSenderName

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.6

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.496 PidTagAccess

**Canonical name:** PidTagAccess

**Description:** Indicates the operations available to the client for the object.

**Property ID:** 0x0FF4

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** PR\_ACCESS, ptagAccess

## 2.497 PidTagAccessControlListData

**Canonical name:** PidTagAccessControlListData

**Description:** Contains a **permissions** list for a folder.

**Property ID:** 0x3FE0

**Data type:** PtypBinary, 0x0102

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.3

**Consuming references:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_ACL\_DATA, ptagACLData

## 2.498 PidTagAccessLevel

**Canonical name:** PidTagAccessLevel

**Description:** Indicates the client's access level to the object.

**Property ID:** 0x0FF7

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_ACCESS\_LEVEL, ptagAccessLevel

## 2.499 PidTagAccount

**Canonical name:** PidTagAccount

**Description:** Contains the alias of an Address Book object, which is an alternative name by which the object can be identified.

**Property ID:** 0x3A00

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ACCOUNT, PR\_ACCOUNT\_A, PR\_ACCOUNT\_W,  
urn:schemas:contacts:account

## 2.500 PidTagAdditionalRenEntryIds

**Canonical name:** PidTagAdditionalRenEntryIds

**Description:** Contains the indexed entry IDs for several special folders related to conflicts, sync issues, local failures, server failures, junk e-mail and **spam**.

**Property ID:** 0x36D8

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.4

**Consuming references:** [\[MS-OXCSPAM\]](#), [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS, ptagAdditionalRenEntryIds

### 2.501 PidTagAdditionalRenEntryIdsEx

**Canonical name:** PidTagAdditionalRenEntryIdsEx

**Description:** Contains an array of blocks that contain the EntryIDs for folders related to RSS feed folders, and the Tracked Mail Processing folder, To-Do Search folder, and Conversation Action Settings folder.

**Property ID:** 0x36D9

**Data type:** **PtypBinary**, 0x0102

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.5

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS\_EX, ptagAdditionalRenEntryIdsEx

### 2.502 PidTagAddressBookAuthorizedSenders

**Canonical name:** PidTagAddressBookAuthorizedSenders

**Description:** Indicates whether delivery restrictions exist for a recipient (1).

**Property ID:** 0x8CD8

**Data type:** **PtypObject**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.42

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_AUTH\_ORIG

### 2.503 PidTagAddressBookContainerId

**Canonical name:** PidTagAddressBookContainerId

**Description:** Contains the ID of a container on an NSPI server.

**Property ID:** 0xFFFFD

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_CONTAINERID

## 2.504 PidTagAddressBookDeliveryContentLength

**Canonical name:** PidTagAddressBookDeliveryContentLength

**Description:** Specifies the maximum size, in bytes, of a message that a recipient (1) can receive.

**Property ID:** 0x806A

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.27

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DELIV\_CONT\_LENGTH

## 2.505 PidTagAddressBookDisplayNamePrintable

**Canonical name:** PidTagAddressBookDisplayNamePrintable

**Description:** Contains the printable string version of the display name.

**Property ID:** 0x39FF

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.7

**Consuming reference:** [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE, PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_A, PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_W, PR\_7BIT\_DISPLAY\_NAME, PR\_7BIT\_DISPLAY\_NAME\_A, PR\_7BIT\_DISPLAY\_NAME\_W, ptagSimpleDisplayName

## 2.506 PidTagAddressBookDisplayTypeExtended

**Canonical name:** PidTagAddressBookDisplayTypeExtended

**Description:** Contains a value that indicates how to display an Address Book object in a table or as a recipient (1) on a message.

**Property ID:** 0x8C93

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.35

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_TYPE\_EX

## 2.507 PidTagAddressBookDistributionListExternalMemberCount

**Canonical name:** PidTagAddressBookDistributionListExternalMemberCount

**Description:** Contains the number of external recipients (1) in the distribution list.

**Property ID:** 0x8CE3

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.30

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_EXTERNAL\_MEMBER\_COUNT

## 2.508 PidTagAddressBookDistributionListMemberCount

**Canonical name:** PidTagAddressBookDistributionListMemberCount

**Description:** Contains the total number of recipients (1) in the distribution list.

**Property ID:** 0x8CE2

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.29

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_TOTAL\_MEMBER\_COUNT

## 2.509 PidTagAddressBookDistributionListMemberSubmitAccepted

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitAccepted

**Description:** Indicates that delivery restrictions exist for a recipient (1).

**Property ID:** 0x8073

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.44

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_SUBMIT\_PERMS\_BL\_O

## 2.510 PidTagAddressBookDistributionListMemberSubmitRejected

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitRejected

**Description:** Indicates that delivery restrictions exist for a recipient (1).

**Property ID:** 0x8CDA

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.45

**Consuming references:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_SUBMIT\_PERMS

## 2.511 PidTagAddressBookDistributionListRejectMessagesFromDLMembers

**Canonical name:** PidTagAddressBookDistributionListRejectMessagesFromDLMembers

**Description:** Indicates that delivery restrictions exist for a recipient (1).

**Property ID:** 0x8CDB

**Data type:** PtypObject, 0x000D

**Area:** Address book

**Defining reference:** [\[MS-OXOAB\]](#) section 2.9.2.2

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_REJECT\_PERMS

## 2.512 PidTagAddressBookEntryId

**Canonical name:** PidTagAddressBookEntryId

**Description:** Contains the name-service EntryID of a directory object that refers to a **public folder**.

**Property ID:** 0x663B

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.4

**Alternate names:** PR\_ADDRESS\_BOOK\_ENTRYID, ptagAddressBookEntryId

## 2.513 PidTagAddressBookExtensionAttribute1

**Canonical name:** PidTagAddressBookExtensionAttribute1

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x802D

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_W

## 2.514 PidTagAddressBookExtensionAttribute10

**Canonical name:** PidTagAddressBookExtensionAttribute10

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8036

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10\_W

## 2.515 PidTagAddressBookExtensionAttribute11

**Canonical name:** PidTagAddressBookExtensionAttribute11

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C57

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11\_W

## 2.516 PidTagAddressBookExtensionAttribute12

**Canonical name:** PidTagAddressBookExtensionAttribute12

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C58

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12\_W

### 2.517 PidTagAddressBookExtensionAttribute13

**Canonical name:** PidTagAddressBookExtensionAttribute13

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C59

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13\_W

### 2.518 PidTagAddressBookExtensionAttribute14

**Canonical name:** PidTagAddressBookExtensionAttribute14

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C60

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14\_W

### 2.519 PidTagAddressBookExtensionAttribute15

**Canonical name:** PidTagAddressBookExtensionAttribute15

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C61

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34



**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_W

## 2.520 PidTagAddressBookExtensionAttribute2

**Canonical name:** PidTagAddressBookExtensionAttribute2

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x802E

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2\_W

## 2.521 PidTagAddressBookExtensionAttribute3

**Canonical name:** PidTagAddressBookExtensionAttribute3

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x802F

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3\_W

## 2.522 PidTagAddressBookExtensionAttribute4

**Canonical name:** PidTagAddressBookExtensionAttribute4

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8030

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4\_W

## 2.523 PidTagAddressBookExtensionAttribute5

**Canonical name:** PidTagAddressBookExtensionAttribute5

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8031

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5\_W

## 2.524 PidTagAddressBookExtensionAttribute6

**Canonical name:** PidTagAddressBookExtensionAttribute6

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8032

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6\_W

## 2.525 PidTagAddressBookExtensionAttribute7

**Canonical name:** PidTagAddressBookExtensionAttribute7

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8033

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7\_W

## 2.526 PidTagAddressBookExtensionAttribute8

**Canonical name:** PidTagAddressBookExtensionAttribute8

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8034

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8\_W

## 2.527 PidTagAddressBookExtensionAttribute9

**Canonical name:** PidTagAddressBookExtensionAttribute9

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8035

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9\_W

## 2.528 PidTagAddressBookFolderPathname

**Canonical name:** PidTagAddressBookFolderPathname

**Description:** This property is deprecated and is to be ignored.

**Property ID:** 0x8004

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.4

**Alternate names:** PR\_EMS\_AB\_FOLDER\_PATHNAME, PR\_EMS\_AB\_FOLDER\_PATHNAME\_A,  
PR\_EMS\_AB\_FOLDER\_PATHNAME\_W

## 2.529 PidTagAddressBookHierarchicalChildDepartments

**Canonical name:** PidTagAddressBookHierarchicalChildDepartments

**Description:** Contains the child departments in a hierarchy of departments.

**Property ID:** 0x8C9A

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.1

**Alternate names:** PR\_EMS\_AB\_HAB\_CHILD\_DEPARTMENTS

### 2.530 PidTagAddressBookHierarchicalDepartmentMembers

**Canonical name:** PidTagAddressBookHierarchicalDepartmentMembers

**Description:** Contains all of the mail users that belong to this department.

**Property ID:** 0x8C97

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.3

**Alternate names:** PR\_EMS\_AB\_HAB\_DEPARTMENT\_MEMBERS

### 2.531 PidTagAddressBookHierarchicalIsHierarchicalGroup

**Canonical name:** PidTagAddressBookHierarchicalIsHierarchicalGroup

**Description:** Indicates whether the distribution list represents a **departmental group**.

**Property ID:** 0x8CDD

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.5

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_IS\_HIERARCHICAL\_GROUP,  
PR\_EMS\_AB\_IS\_ORGANIZATIONAL

### 2.532 PidTagAddressBookHierarchicalParentDepartment

**Canonical name:** PidTagAddressBookHierarchicalParentDepartment

**Description:** Contains all of the departments to which this department is a child.

**Property ID:** 0x8C99

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.2

**Alternate names:** PR\_EMS\_AB\_HAB\_PARENT\_DEPARTMENT

### 2.533 PidTagAddressBookHierarchicalRootDepartment

**Canonical name:** PidTagAddressBookHierarchicalRootDepartment

**Description:** Contains the **DN** of the root departmental group in the department hierarchy for the organization.

**Property ID:** 0x8C98

**Data type:** **PtypString8**, 0x001E

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.7.2

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_ROOT\_DEPARTMENT

### 2.534 PidTagAddressBookHierarchicalShowInDepartments

**Canonical name:** PidTagAddressBookHierarchicalShowInDepartments

**Description:** Lists all Department objects of which the mail user is a member.

**Property ID:** 0x8C94

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.6

**Alternate names:** PR\_EMS\_AB\_HAB\_SHOW\_IN\_DEPARTMENTS

### 2.535 PidTagAddressBookHomeMessageDatabase

**Canonical name:** PidTagAddressBookHomeMessageDatabase

**Description:** Contains the DN expressed in the **X500 DN** format.

**Property ID:** 0x8006

**Data type:** **PtypString8**, 0x001E

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.37

**Consuming references:** [\[MS-OXABREF\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_HOME\_MDB, PR\_EMS\_AB\_HOME\_MDB\_A, PR\_EMS\_AB\_HOME\_MDB\_W

### 2.536 PidTagAddressBookIsMaster

**Canonical name:** PidTagAddressBookIsMaster

**Description:** Contains a Boolean value of TRUE if it is possible to create Address Book objects in that container, and FALSE otherwise.

**Property ID:** 0xFFFFB

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.4

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MASTER

### 2.537 PidTagAddressBookIsMemberOfDistributionList

**Canonical name:** PidTagAddressBookIsMemberOfDistributionList

**Description:** List all the distribution lists for which this object is a member.

**Property ID:** 0x8008

**Data type:** PtypString8, 0x001E

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.3

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_A, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_W

### 2.538 PidTagAddressBookManageDistributionList

**Canonical name:** PidTagAddressBookManageDistributionList

**Description:** Contains information for use in display templates for distribution lists.

**Property ID:** 0x6704

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.10.2

**Consuming reference:** [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGE\_DL

### 2.539 PidTagAddressBookManager

**Canonical name:** PidTagAddressBookManager

**Description:** Contains one row that references the mail user's manager.

**Property ID:** 0x8005

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.1

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGER, PR\_EMS\_AB\_MANAGER\_A, PR\_EMS\_AB\_MANAGER\_W

## 2.540 PidTagAddressBookManagerDistinguishedName

**Canonical name:** PidTagAddressBookManagerDistinguishedName

**Description:** Contains the **distinguished name (DN) (1)** of the mail user's manager.

**Property ID:** 0x8005

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.9

**Alternate names:** PR\_EMS\_AB\_MANAGER\_T

## 2.541 PidTagAddressBookMember

**Canonical name:** PidTagAddressBookMember

**Description:** Contains the members of the distribution list.

**Property ID:** 0x8009

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.1

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_MEMBER, PR\_EMS\_AB\_MEMBER\_A, PR\_EMS\_AB\_MEMBER\_W

## 2.542 PidTagAddressBookMessageId

**Canonical name:** PidTagAddressBookMessageId

**Description:** Contains the Short-term Message ID (MID) ([\[MS-OXCDATA\]](#) section 2.2.1.2) of the first message in the local site's **offline address book** public folder.

**Property ID:** 0x674F

**Data type:** PtypInteger64, 0x0014

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.2

**Alternate names:** ptagAddrbookMID

## 2.543 PidTagAddressBookModerationEnabled

**Canonical name:** PidTagAddressBookModerationEnabled

**Description:** Indicates whether moderation is enabled for the mail user of the distribution list.

**Property ID:** 0x8CB5

**Data type:** **PtypBoolean**, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.28

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_ENABLE\_MODERATION

## 2.544 PidTagAddressBookNetworkAddress

**Canonical name:** PidTagAddressBookNetworkAddress

**Description:** Contains a list of names by which a server is known to the various transports in use by the network.

**Property ID:** 0x8170

**Data type:** **PtypMultipleString**, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.38

**Alternate names:** PR\_EMS\_AB\_NETWORK\_ADDRESS, PR\_EMS\_AB\_NETWORK\_ADDRESS\_A, PR\_EMS\_AB\_NETWORK\_ADDRESS\_W

## 2.545 PidTagAddressBookObjectDistinguishedName

**Canonical name:** PidTagAddressBookObjectDistinguishedName

**Description:** Contains the distinguished name (DN) (1) of the Address Book object.

**Property ID:** 0x803C

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.15

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJ\_DIST\_NAME, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_A, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_W



## 2.546 PidTagAddressBookObjectGuid

**Canonical name:** PidTagAddressBookObjectGuid

**Description:** Contains a GUID that identifies an Address Book object.

**Property ID:** 0x8C6D

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.25

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJECT\_GUID

## 2.547 PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Canonical name:** PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Description:** Contains the distinguished name (DN) (1) of the Organization object of the mail user's organization.

**Property ID:** 0x8CA8

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.39

**Alternate names:** PR\_EMS\_AB\_ORG\_UNIT\_ROOT\_DN, msExchOURoot

## 2.548 PidTagAddressBookOwner

**Canonical name:** PidTagAddressBookOwner

**Description:** Contains one row that references the distribution list's owner.

**Property ID:** 0x800C

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.2

**Alternate names:** PR\_EMS\_AB\_OWNER\_O

## 2.549 PidTagAddressBookOwnerBackLink

**Canonical name:** PidTagAddressBookOwnerBackLink

**Description:** Contains a list of the distribution lists owned by a mail user.

**Property ID:** 0x8024

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.4

**Alternate names:** PR\_EMS\_AB\_OWNER\_BL\_O

## 2.550 PidTagAddressBookParentEntryId

**Canonical name:** PidTagAddressBookParentEntryId

**Description:** Contains the EntryID of the parent container in a hierarchy of address book containers.

**Property ID:** 0xFFFC

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.5

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_PARENT\_ENTRYID

## 2.551 PidTagAddressBookPhoneticCompanyName

**Canonical name:** PidTagAddressBookPhoneticCompanyName

**Description:** Contains the phonetic representation of the **PidTagCompanyName** property (section [2.630](#)).

**Property ID:** 0x8C91

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.12

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME,  
PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_W

## 2.552 PidTagAddressBookPhoneticDepartmentName

**Canonical name:** PidTagAddressBookPhoneticDepartmentName

**Description:** Contains the phonetic representation of the **PidTagDepartmentName** property (section [2.663](#)).

**Property ID:** 0x8C90

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.13

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME,  
PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_W

### 2.553 PidTagAddressBookPhoneticDisplayName

**Canonical name:** PidTagAddressBookPhoneticDisplayName

**Description:** Contains the phonetic representation of the **PidTagDisplayName** property (section [2.667](#)).

**Property ID:** 0x8C92

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.9

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME,  
PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_W

### 2.554 PidTagAddressBookPhoneticGivenName

**Canonical name:** PidTagAddressBookPhoneticGivenName

**Description:** Contains the phonetic representation of the **PidTagGivenName** property (section [2.704](#)).

**Property ID:** 0x8C8E

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.10

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME,  
PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_W

### 2.555 PidTagAddressBookPhoneticSurname

**Canonical name:** PidTagAddressBookPhoneticSurname

**Description:** Contains the phonetic representation of the **PidTagSurname** property (section [2.1024](#)).

**Property ID:** 0x8C8F

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.11

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_SURNAME, PR\_EMS\_AB\_PHONETIC\_SURNAME\_A, PR\_EMS\_AB\_PHONETIC\_SURNAME\_W

## 2.556 PidTagAddressBookProxyAddresses

**Canonical name:** PidTagAddressBookProxyAddresses

**Description:** Contains alternate e-mail addresses for the Address Book object.

**Property ID:** 0x800F

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.23

**Consuming references:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PROXY\_ADDRESSES, PR\_EMS\_AB\_PROXY\_ADDRESSES\_A, PR\_EMS\_AB\_PROXY\_ADDRESSES\_W

## 2.557 PidTagAddressBookPublicDelegates

**Canonical name:** PidTagAddressBookPublicDelegates

**Description:** Contains a list of mail users who are allowed to send e-mail on behalf of the mailbox owner.

**Property ID:** 0x8015

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.5

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PUBLIC\_DELEGATES, PR\_EMS\_AB\_PUBLIC\_DELEGATES\_A, PR\_EMS\_AB\_PUBLIC\_DELEGATES\_W

## 2.558 PidTagAddressBookReports

**Canonical name:** PidTagAddressBookReports

**Description:** Lists all the people who report to a mail user.

**Property ID:** 0x800E

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.2

**Alternate names:** PR\_EMS\_AB\_REPORTS, PR\_EMS\_AB\_REPORTS\_A, PR\_EMS\_AB\_REPORTS\_W

## 2.559 PidTagAddressBookRoomCapacity

**Canonical name:** PidTagAddressBookRoomCapacity

**Description:** Contains the maximum occupancy of the room.

**Property ID:** 0x0807

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.9.1

**Alternate names:** PR\_EMS\_AB\_ROOM\_CAPACITY

## 2.560 PidTagAddressBookRoomContainers

**Canonical name:** PidTagAddressBookRoomContainers

**Description:** Contains a list of DNs that represent the address book containers that hold **Resource objects**, such as conference rooms and equipment.

**Property ID:** 0x8C96

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.7.1

**Alternate names:** PR\_EMS\_AB\_ROOM\_CONTAINERS, PR\_EMS\_AB\_ROOM\_CONTAINERS\_A, PR\_EMS\_AB\_ROOM\_CONTAINERS\_W

## 2.561 PidTagAddressBookRoomDescription

**Canonical name:** PidTagAddressBookRoomDescription

**Description:** Contains a description of the Resource object.

**Property ID:** 0x0809

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.9.2

**Alternate names:** PR\_EMS\_AB\_ROOM\_DESCRIPTION, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_A, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_W

## 2.562 PidTagAddressBookSenderHintTranslations

**Canonical name:** PidTagAddressBookSenderHintTranslations

**Description:** Contains the **locale** ID and translations of the default **mail tip**.

**Property ID:** 0x8CAC

**Data type:** **PtypMultipleString**, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.26

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_SENDER\_HINT\_TRANSLATIONS\_W

## 2.563 PidTagAddressBookSeniorityIndex

**Canonical name:** PidTagAddressBookSeniorityIndex

**Description:** Contains a signed integer that specifies the seniority order of Address Book objects that represent members of a department and are referenced by a Department object or departmental group, with larger values specifying members that are more senior.

**Property ID:** 0x8CA0

**Data type:** **PtypInteger32**, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.24

**Consuming reference:** [\[MS-OXOAB\]](#) **Alternate names:** PR\_EMS\_AB\_HAB\_SENIORITY\_INDEX, PR\_EMS\_AB\_SENIORITY\_INDEX

## 2.564 PidTagAddressBookTargetAddress

**Canonical name:** PidTagAddressBookTargetAddress

**Description:** Contains the foreign system e-mail address of an Address Book object.

**Property ID:** 0x8011

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.22

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_TARGET\_ADDRESS, PR\_EMS\_AB\_TARGET\_ADDRESS\_A, PR\_EMS\_AB\_TARGET\_ADDRESS\_W

## 2.565 PidTagAddressBookUnauthorizedSenders

**Canonical name:** PidTagAddressBookUnauthorizedSenders

**Description:** Indicates whether delivery restrictions exist for a recipient (1).

**Property ID:** 0x8CD9

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.43

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_UNAUTH\_ORIG

## 2.566 PidTagAddressBookX509Certificate

**Canonical name:** PidTagAddressBookX509Certificate

**Description:** Contains the ASN\_1 DER encoded X.509 certificates for the mail user.

**Property ID:** 0x8C6A

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.36

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_X509\_CERT

## 2.567 PidTagAddressType

**Canonical name:** PidTagAddressType

**Description:** Contains the e-mail address type of a Message object.

**Property ID:** 0x3002

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.13

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

**Alternate names:** PR\_ADDRTYPE, PR\_ADDRTYPE\_A, ptagAddrType, PR\_ADDRTYPE\_W

## 2.568 PidTagAlternateRecipientAllowed

**Canonical name:** PidTagAlternateRecipientAllowed

**Description:** Specifies whether the sender permits the message to be auto-forwarded.

**Property ID:** 0x0002

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.36

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ALTERNATE\_RECIPIENT\_ALLOWED, ptagAlternateRecipientAllowed

## 2.569 PidTagAnr

**Canonical name:** PidTagAnr

**Description:** Contains a filter value used in **ambiguous name resolution**.

**Property ID:** 0x360C

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.10.1

**Alternate names:** PR\_ANR, PR\_ANR\_A, PR\_ANR\_W

## 2.570 PidTagArchiveDate

**Canonical name:** PidTagArchiveDate

**Description:** Specifies the date, in UTC, after which a Message object is archived by the server.

**Property ID:** 0x301F

**Data type:** PtypTime, 0x0040

**Area:** Archive

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.58.8

**Alternate names:** PR\_ARCHIVE\_DATE, ptagArchiveDate

## 2.571 PidTagArchivePeriod

**Canonical name:** PidTagArchivePeriod

**Description:** Specifies the number of days that a Message object can remain unarchived.

**Property ID:** 0x301E



**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.7

**Alternate names:** PR\_ARCHIVE\_PERIOD, ptagArchivePeriod

## 2.572 PidTagArchiveTag

**Canonical name:** PidTagArchiveTag

**Description:** Specifies the GUID of an **archive tag**.

**Property ID:** 0x3018

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.1

**Alternate names:** PR\_ARCHIVE\_TAG, ptagArchiveTag

## 2.573 PidTagAssistant

**Canonical name:** PidTagAssistant

**Description:** Contains the name of the mail user's administrative assistant.

**Property ID:** 0x3A30

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.8

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ASSISTANT, PR\_ASSISTANT\_A, PR\_ASSISTANT\_W, urn:schemas:contacts:secretarycn

## 2.574 PidTagAssistantTelephoneNumber

**Canonical name:** PidTagAssistantTelephoneNumber

**Description:** Contains the telephone number of the mail user's administrative assistant.

**Property ID:** 0x3A2E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.31

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ASSISTANT\_TELEPHONE\_NUMBER, PR\_ASSISTANT\_TELEPHONE\_NUMBER\_A, PR\_ASSISTANT\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:secretaryphone

### 2.575 PidTagAssociated

**Canonical name:** PidTagAssociated

**Description:** Specifies whether the message being synchronized is an FAI message.

**Property ID:** 0x67AA

**Data type:** PtypBoolean, 0x000B

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.5

**Alternate names:** ptagAssociated

### 2.576 PidTagAttachAdditionalInformation

**Canonical name:** PidTagAttachAdditionalInformation

**Description:** Contains attachment encoding information.

**Property ID:** 0x370F

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.21

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_ADDITIONAL\_INFO

### 2.577 PidTagAttachContentBase

**Canonical name:** PidTagAttachContentBase

**Description:** Contains the base of a relative URI.

**Property ID:** 0x3711

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#) **Alternate names:** PR\_ATTACH\_CONTENT\_BASE, PR\_ATTACH\_CONTENT\_BASE\_A, PR\_ATTACH\_CONTENT\_BASE\_W

### 2.578 PidTagAttachContentId

**Canonical name:** PidTagAttachContentId

**Description:** Contains a content identifier unique to the Message object that matches a corresponding "cid:" URI schema reference in the HTML body of the Message object.

**Property ID:** 0x3712

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_ID, PR\_ATTACH\_CONTENT\_ID\_A, PR\_ATTACH\_CONTENT\_ID\_W

## 2.579 PidTagAttachContentLocation

**Canonical name:** PidTagAttachContentLocation

**Description:** Contains a relative or full URI that matches a corresponding reference in the HTML body of a Message object.

**Property ID:** 0x3713

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_LOCATION, PR\_ATTACH\_CONTENT\_LOCATION\_A, PR\_ATTACH\_CONTENT\_LOCATION\_W

## 2.580 PidTagAttachDataBinary

**Canonical name:** PidTagAttachDataBinary

**Description:** Contains the contents of the file to be attached.

**Property ID:** 0x3701

**Data type:** **PtypBinary**, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_BIN, ptagAttachDataBin

## 2.581 PidTagAttachDataObject

**Canonical name:** PidTagAttachDataObject

**Description:** Contains the binary representation of the **Attachment object** in an application-specific format.

**Property ID:** 0x3701

**Data type:** **PtypObject**, 0x000D

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.8

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_OBJ, ptagAttachDataObj

## 2.582 PidTagAttachEncoding

**Canonical name:** PidTagAttachEncoding

**Description:** Contains encoding information about the Attachment object.

**Property ID:** 0x3702

**Data type:** **PtypBinary**, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_ENCODING

## 2.583 PidTagAttachExtension

**Canonical name:** PidTagAttachExtension

**Description:** Contains a file name extension that indicates the document type of an attachment.

**Property ID:** 0x3703

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.12

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_EXTENSION, PR\_ATTACH\_EXTENSION\_A, PR\_ATTACH\_EXTENSION\_W

## 2.584 PidTagAttachFilename

**Canonical name:** PidTagAttachFilename

**Description:** Contains the **8.3 name** of the **PidTagAttachLongFilename** property (section [2.586](#)).

**Property ID:** 0x3704

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-XPFOAB\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_FILENAME, PR\_ATTACH\_FILENAME\_A, ptagAttachFilename, PR\_ATTACH\_FILENAME\_W

## 2.585 PidTagAttachFlags

**Canonical name:** PidTagAttachFlags

**Description:** Indicates which body formats might reference this attachment when rendering data.

**Property ID:** 0x3714

**Data type:** **PtypInteger32**, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.18

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACH\_FLAGS

## 2.586 PidTagAttachLongFilename

**Canonical name:** PidTagAttachLongFilename

**Description:** Contains the full filename and extension of the Attachment object.

**Property ID:** 0x3707

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.10

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOUM\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_FILENAME, PR\_ATTACH\_LONG\_FILENAME\_A, PR\_ATTACH\_LONG\_FILENAME\_W, urn:schemas:httpmail:attachmentfilename

## 2.587 PidTagAttachLongPathname

**Canonical name:** PidTagAttachLongPathname

**Description:** Contains the fully-qualified path and file name with extension.

**Property ID:** 0x370D

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.13

**Consuming reference:** [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_PATHNAME, PR\_ATTACH\_LONG\_PATHNAME\_A, ptagAttachLongPathname, PR\_ATTACH\_LONG\_PATHNAME\_W

## 2.588 PidTagAttachmentContactPhoto

**Canonical name:** PidTagAttachmentContactPhoto

**Description:** Indicates that a contact photo attachment is attached to a Contact object.

**Property ID:** 0x7FFF

**Data type:** **PtypBoolean**, 0x000B

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACHMENT\_CONTACTPHOTO

## 2.589 PidTagAttachmentFlags

**Canonical name:** PidTagAttachmentFlags

**Description:** Indicates special handling for an Attachment object.

**Property ID:** 0x7FFD

**Data type:** **PtypInteger32**, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.23

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** PR\_ATTACHMENT\_FLAGS, ptagAttachmentFlags

## 2.590 PidTagAttachmentHidden

**Canonical name:** PidTagAttachmentHidden

**Description:** Indicates whether an Attachment object is hidden from the end user.

**Property ID:** 0x7FFE

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.24

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_ATTACHMENT\_HIDDEN

## 2.591 PidTagAttachmentLinkId

**Canonical name:** PidTagAttachmentLinkId

**Description:** Contains the type of Message object to which an attachment is linked.

**Property ID:** 0x7FFA

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.22

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACHMENT\_LINKID, ptagAttachmentLinkId

## 2.592 PidTagAttachMethod

**Canonical name:** PidTagAttachMethod

**Description:** Represents the way the contents of an attachment are accessed.

**Property ID:** 0x3705

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_METHOD, ptagAttachMethod

## 2.593 PidTagAttachMimeTag

**Canonical name:** PidTagAttachMimeTag

**Description:** Contains a content-type MIME header.

**Property ID:** 0x370E

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.26

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#)

**Alternate names:** PR\_ATTACH\_MIME\_TAG, PR\_ATTACH\_MIME\_TAG\_A, PR\_ATTACH\_MIME\_TAG\_W

## 2.594 PidTagAttachNumber

**Canonical name:** PidTagAttachNumber

**Description:** Identifies the Attachment object within its Message object.

**Property ID:** 0x0E21

**Data type:** **PtypInteger32**, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_ATTACH\_NUM, ptagAttachNum

## 2.595 PidTagAttachPathname

**Canonical name:** PidTagAttachPathname

**Description:** Contains the 8.3 name of the **PidTagAttachLongPathname** property (section [2.587](#)).

**Property ID:** 0x3708

**Data type:** **PtypString**, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.14

**Consuming reference:** [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_PATHNAME, PR\_ATTACH\_PATHNAME\_A, ptagAttachPathname, PR\_ATTACH\_PATHNAME\_W

## 2.596 PidTagAttachPayloadClass

**Canonical name:** PidTagAttachPayloadClass

**Description:** Contains the class name of an object that can display the contents of the message.

**Property ID:** 0x371A

**Data type:** **PtypString**, 0x001F

**Area:** Outlook Application



**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_CLASS, PR\_ATTACH\_PAYLOAD\_CLASS\_A, PR\_ATTACH\_PAYLOAD\_CLASS\_W, ptagAttachPayloadClass

## 2.597 PidTagAttachPayloadProviderGuidIdString

**Canonical name:** PidTagAttachPayloadProviderGuidIdString

**Description:** Contains the GUID of the software component that can display the contents of the message.

**Property ID:** 0x3719

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR, PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_A, PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_W

## 2.598 PidTagAttachRendering

**Canonical name:** PidTagAttachRendering

**Description:** Contains a Windows Metafile, as specified in [\[MS-WMF\]](#), for the Attachment object.

**Property ID:** 0x3709

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.17

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_RENDERING, ptagAttachRendering

## 2.599 PidTagAttachSize

**Canonical name:** PidTagAttachSize

**Description:** Contains the size, in bytes, consumed by the Attachment object on the server.

**Property ID:** 0x0E20

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACH\_SIZE, ptagAttachSize

## 2.600 PidTagAttachTag

**Canonical name:** PidTagAttachTag

**Description:** Contains the identifier information for the application that supplied the Attachment object data.

**Property ID:** 0x370A

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.15

**Consuming references:** [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TAG

## 2.601 PidTagAttachTransportName

**Canonical name:** PidTagAttachTransportName

**Description:** Contains the name of an attachment file, modified so that it can be correlated with TNEF messages.

**Property ID:** 0x370C

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.19

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TRANSPORT\_NAME, PR\_ATTACH\_TRANSPORT\_NAME\_A, PR\_ATTACH\_TRANSPORT\_NAME\_W

## 2.602 PidTagAttributeHidden

**Canonical name:** PidTagAttributeHidden

**Description:** Specifies the hide or show status of a folder.

**Property ID:** 0x10F4

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.1

**Consuming references:** [\[MS-OXOSFLD\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_ATTR\_HIDDEN, ptagAttrHidden, DAV:ishidden

### 2.603 PidTagAttributeReadOnly

**Canonical name:** PidTagAttributeReadOnly

**Description:** Indicates whether an item can be modified or deleted.

**Property ID:** 0x10F6

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTR\_READONLY, ptagAttrReadOnly, DAV:isreadonly

### 2.604 PidTagAutoForwardComment

**Canonical name:** PidTagAutoForwardComment

**Description:** Contains text included in an automatically-generated message.

**Property ID:** 0x0004

**Data type:** PtypString, 0x001F

**Area:** General Report Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.21

**Alternate names:** PR\_AUTO\_FORWARD\_COMMENT, PR\_AUTO\_FORWARD\_COMMENT\_A, PR\_AUTO\_FORWARD\_COMMENT\_W

### 2.605 PidTagAutoForwarded

**Canonical name:** PidTagAutoForwarded

**Description:** Indicates that a Message object has been automatically generated or automatically forwarded.

**Property ID:** 0x0005

**Data type:** PtypBoolean, 0x000B

**Area:** General Report Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.20

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_AUTO\_FORWARDED, ptagAutoForwarded

## 2.606 PidTagAutoResponseSuppress

**Canonical name:** PidTagAutoResponseSuppress

**Description:** Specifies whether a client or server application should forego sending automated replies in response to this message.

**Property ID:** 0x3FDF

**Data type:** PtypInteger32, 0x0003

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.77

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_AUTO\_RESPONSE\_SUPPRESS, ptagAutoResponseSuppress

## 2.607 PidTagBirthday

**Canonical name:** PidTagBirthday

**Description:** Contains the date of the mail user's birthday at midnight.

**Property ID:** 0x3A42

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BIRTHDAY, urn:schemas:contacts:bday

## 2.608 PidTagBlockStatus

**Canonical name:** PidTagBlockStatus

**Description:** Indicates the user's preference for viewing external content (such as links to images on an **HTTP** server) in the message body (2).

**Property ID:** 0x1096

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.1

**Alternate names:** PR\_BLOCK\_STATUS, ptagBlockStatus

## 2.609 PidTagBody

**Canonical name:** PidTagBody

**Description:** Contains message body (2) text in **plain text** format.

**Property ID:** 0x1000

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BODY, PR\_BODY\_A, ptagBody, PR\_BODY\_W, urn:schemas:httpmail:textdescription

## 2.610 PidTagBodyContentId

**Canonical name:** PidTagBodyContentId

**Description:** Contains a GUID that corresponds to the current message body (2).

**Property ID:** 0x1015

**Data type:** **PtypString**, 0x001F

**Area:** Exchange

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.7

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_ID, PR\_BODY\_CONTENT\_ID\_A, PR\_BODY\_CONTENT\_ID\_W

## 2.611 PidTagBodyContentLocation

**Canonical name:** PidTagBodyContentLocation

**Description:** Contains a globally unique Uniform Resource Identifier (URI) that serves as a label for the current message body (2).

**Property ID:** 0x1014

**Data type:** **PtypString**, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.8

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_LOCATION, PR\_BODY\_CONTENT\_LOCATION\_A, PR\_BODY\_CONTENT\_LOCATION\_W

## 2.612 PidTagBodyHtml

**Canonical name:** PidTagBodyHtml

**Description:** Contains the HTML body of the Message object.

**Property ID:** 0x1013

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_BODY\_HTML, PR\_BODY\_HTML\_A, ptagBodyHtml, PR\_BODY\_HTML\_W

### 2.613 PidTagBusiness2TelephoneNumber

**Canonical name:** PidTagBusiness2TelephoneNumber

**Description:** Contains a secondary telephone number at the mail user's place of business.

**Property ID:** 0x3A1B

**Data type:** **PtypString**, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.23

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** "PR\_BUSINESS2\_TELEPHONE\_NUMBER, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_W, PR\_OFFICE2\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephonenumber2

### 2.614 PidTagBusiness2TelephoneNumbers

**Canonical name:** PidTagBusiness2TelephoneNumbers

**Description:** Contains secondary telephone numbers at the mail user's place of business.

**Property ID:** 0x3A1B

**Data type:** **PtypMultipleString**, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.24

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A\_MV

### 2.615 PidTagBusinessFaxNumber

**Canonical name:** PidTagBusinessFaxNumber

**Description:** Contains the telephone number of the mail user's business fax machine.

**Property ID:** 0x3A24

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_FAX\_NUMBER, PR\_BUSINESS\_FAX\_NUMBER\_A, PR\_BUSINESS\_FAX\_NUMBER\_W, urn:schemas:contacts:facsimiletelephonenumber

## 2.616 PidTagBusinessHomePage

**Canonical name:** PidTagBusinessHomePage

**Description:** Contains the URL of the mail user's business home page.

**Property ID:** 0x3A51

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.14

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_HOME\_PAGE, PR\_BUSINESS\_HOME\_PAGE\_A, PR\_BUSINESS\_HOME\_PAGE\_W, urn:schemas:contacts:businesshomepageurn:schemas:contacts:businesshomepage

## 2.617 PidTagBusinessTelephoneNumber

**Canonical name:** PidTagBusinessTelephoneNumber

**Description:** Contains the primary telephone number of the mail user's place of business.

**Property ID:** 0x3A08

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.21

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_TELEPHONE\_NUMBER, PR\_BUSINESS\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS\_TELEPHONE\_NUMBER\_W, PR\_OFFICE\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephoneNumber

## 2.618 PidTagCallbackTelephoneNumber

**Canonical name:** PidTagCallbackTelephoneNumber

**Description:** Contains a telephone number to reach the mail user.

**Property ID:** 0x3A02

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CALLBACK\_TELEPHONE\_NUMBER, PR\_CALLBACK\_TELEPHONE\_NUMBER\_A, PR\_CALLBACK\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:callbackphone

## 2.619 PidTagCallId

**Canonical name:** PidTagCallId

**Description:** Contains a unique identifier associated with the phone call.

**Property ID:** 0x6806

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.11

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaCallID

## 2.620 PidTagCarTelephoneNumber

**Canonical name:** PidTagCarTelephoneNumber

**Description:** Contains the mail user's car telephone number.

**Property ID:** 0x3A1E

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CAR\_TELEPHONE\_NUMBER, PR\_CAR\_TELEPHONE\_NUMBER\_A, PR\_CAR\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:othermobile

## 2.621 PidTagCdoRecurrenceid

**Canonical name:** PidTagCdoRecurrenceid

**Description:** Identifies a specific instance of a recurring appointment.

**Property ID:** 0x10C5



**Data type:** PtypTime, 0x0040

**Area:** Exchange

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.38

**Alternate names:** PR\_CDO\_RECURRENCEID, urn:schemas:calendar:recurrenceid

## 2.622 PidTagChangeKey

**Canonical name:** PidTagChangeKey

**Description:** Contains a structure that identifies the last change to the object.

**Property ID:** 0x65E2

**Data type:** PtypBinary, 0x0102

**Area:** History Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#)

**Alternate names:** PR\_CHANGE\_KEY

## 2.623 PidTagChangeNumber

**Canonical name:** PidTagChangeNumber

**Description:** Contains a structure that identifies the last change to the message or folder that is currently being synchronized.

**Property ID:** 0x67A4

**Data type:** PtypInteger64, 0x0014

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagCn

## 2.624 PidTagChildrensNames

**Canonical name:** PidTagChildrensNames

**Description:** Specifies the names of the contact's (3) children.

**Property ID:** 0x3A58

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.17

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CHILDRENS\_NAMES, PR\_CHILDRENS\_NAMES\_A, PR\_CHILDRENS\_NAMES\_W, urn:schemas:contacts:childrensnames

## 2.625 PidTagClientActions

**Canonical name:** PidTagClientActions

**Description:** Specifies the **actions (3)** the client is required to take on the message.

**Property ID:** 0x6645

**Data type:** PtypBinary, 0x0102

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.6

**Alternate names:** PR\_CLIENT\_ACTIONS, ptagClientActions

## 2.626 PidTagClientSubmitTime

**Canonical name:** PidTagClientSubmitTime

**Description:** Contains the current time, in UTC, when the e-mail message is submitted.

**Property ID:** 0x0039

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEFI\]](#)

**Alternate names:** PR\_CLIENT\_SUBMIT\_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

## 2.627 PidTagCodePageId

**Canonical name:** PidTagCodePageId

**Description:** Contains the identifier for the client code page used for **Unicode** to **double-byte character set (DBCS)** string conversion.

**Property ID:** 0x66C3

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange Profile Configuration

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_CODE\_PAGE\_ID, ptagCodePageId

## 2.628 PidTagComment

**Canonical name:** PidTagComment

**Description:** Contains a comment about the purpose or content of the Address Book object.

**Property ID:** 0x3004

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.2

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_COMMENT, PR\_COMMENT\_A, ptagComment, PR\_COMMENT\_W, DAV:comment, <http://schemas.microsoft.com/exchange/summary-utf8>

## 2.629 PidTagCompanyMainTelephoneNumber

**Canonical name:** PidTagCompanyMainTelephoneNumber

**Description:** Contains the main telephone number of the mail user's company.

**Property ID:** 0x3A57

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.14

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COMPANY\_MAIN\_PHONE\_NUMBER, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_A, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_W, urn:schemas:contacts:organizationmainphone

## 2.630 PidTagCompanyName

**Canonical name:** PidTagCompanyName

**Description:** Contains the mail user's company name.

**Property ID:** 0x3A16

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.7

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COMPANY\_NAME, PR\_COMPANY\_NAME\_A, PR\_COMPANY\_NAME\_W, urn:schemas:contacts:o

## 2.631 PidTagComputerNetworkName

**Canonical name:** PidTagComputerNetworkName

**Description:** Contains the name of the mail user's computer network.

**Property ID:** 0x3A49

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.16

**Alternate names:** PR\_COMPUTER\_NETWORK\_NAME, PR\_COMPUTER\_NETWORK\_NAME\_A, PR\_COMPUTER\_NETWORK\_NAME\_W, urn:schemas:contacts:computernetworkname

## 2.632 PidTagConflictEntryId

**Canonical name:** PidTagConflictEntryId

**Description:** Contains the EntryID of the conflict resolve message.

**Property ID:** 0x3FF0

**Data type:** PtypBinary, 0x0102

**Area:** ICS

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.2

**Alternate names:** PR\_CONFLICT\_ENTRYID, ptagConflictEntryId

## 2.633 PidTagContainerClass

**Canonical name:** PidTagContainerClass

**Description:** Contains a string value that describes the type of Message object that a folder contains.

**Property ID:** 0x3613

**Data type:** PtypString, 0x001F

**Area:** Container Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_CONTAINER\_CLASS, PR\_CONTAINER\_CLASS\_A, ptagContainerClass, PR\_CONTAINER\_CLASS\_W, <http://schemas.microsoft.com/exchange/outlookfolderclass><http://schemas.microsoft.com/exchange/outlookfolderclass>

## 2.634 PidTagContainerContents

**Canonical name:** PidTagContainerContents

**Description:** Always empty. An NSPI server defines this value for distribution lists and it is not present for other objects.

**Property ID:** 0x360F

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Container Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_CONTAINER\_CONTENTS, ptagContainerContents

## 2.635 PidTagContainerFlags

**Canonical name:** PidTagContainerFlags

**Description:** Contains a bitmask of flags that describe capabilities of an address book container.

**Property ID:** 0x3600

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.1

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_CONTAINER\_FLAGS

## 2.636 PidTagContainerHierarchy

**Canonical name:** PidTagContainerHierarchy

**Description:** Identifies all of the subfolders of the current folder.

**Property ID:** 0x360E

**Data type:** PtypObject, 0x000D

**Area:** Container Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.4

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_CONTAINER\_HIERARCHY, ptagContainerHierarchy

## 2.637 PidTagContentCount

**Canonical name:** PidTagContentCount

**Description:** Specifies the number of rows under the header row.

**Property ID:** 0x3602

**Data type:** **PtypInteger32**, 0x0003

**Area:** Folder Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_CONTENT\_COUNT, ptagContentCount, DAV:visiblecount

## 2.638 PidTagContentFilterSpamConfidenceLevel

**Canonical name:** PidTagContentFilterSpamConfidenceLevel

**Description:** Indicates a confidence level that the message is spam.

**Property ID:** 0x4076

**Data type:** **PtypInteger32**, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CONTENT\_FILTER\_SCL, ptagContentFilterSCL

## 2.639 PidTagContentUnreadCount

**Canonical name:** PidTagContentUnreadCount

**Description:** Specifies the number of rows under the header row that have the **PidTagRead** property (section [2.867](#)) set to FALSE.

**Property ID:** 0x3603

**Data type:** **PtypInteger32**, 0x0003

**Area:** Folder Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.2

**Consuming references:** [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_CONTENT\_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

## 2.640 PidTagConversationId

**Canonical name:** PidTagConversationId

**Description:** Contains a computed value derived from other conversation-related properties.

**Property ID:** 0x3013

**Data type:** PtypBinary, 0x0102

**Area:** Conversations

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXGLOS\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_CONVERSATION\_ID

## 2.641 PidTagConversationIndex

**Canonical name:** PidTagConversationIndex

**Description:** Indicates the relative position of this message within a conversation thread.

**Property ID:** 0x0071

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_CONVERSATION\_INDEX, ptagConversationIndex

## 2.642 PidTagConversationIndexTracking

**Canonical name:** PidTagConversationIndexTracking

**Description:** Indicates whether the GUID portion of the **PidTagConversationIndex** property (section [2.641](#)) is to be used to compute the **PidTagConversationId** property (section [2.640](#)).

**Property ID:** 0x3016

**Data type:** PtypBoolean, 0x000B

**Area:** Conversations

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.4

**Alternate names:** PR\_CONVERSATION\_INDEX\_TRACKING

## 2.643 PidTagConversationTopic

**Canonical name:** PidTagConversationTopic

**Description:** Contains an unchanging copy of the original subject.

**Property ID:** 0x0070

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CONVERSATION\_TOPIC, PR\_CONVERSATION\_TOPIC\_A, ptagConversationTopic, PR\_CONVERSATION\_TOPIC\_W, urn:schemas:httpmail:thread-topic

## 2.644 PidTagCountry

**Canonical name:** PidTagCountry

**Description:** Contains the name of the mail user's country/region.

**Property ID:** 0x3A26

**Data type:** **PtypString**, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.19

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COUNTRY, PR\_COUNTRY\_A, PR\_COUNTRY\_W, PR\_BUSINESS\_ADDRESS\_COUNTRY, PR\_BUSINESS\_ADDRESS\_COUNTRY\_A, PR\_BUSINESS\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:mailingcountry

## 2.645 PidTagCreationTime

**Canonical name:** PidTagCreationTime

**Description:** Contains the time, in UTC, that the object was created.

**Property ID:** 0x3007

**Data type:** **PtypTime**, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATION\_TIME, ptagCreationTime, DAV:creationdate

## 2.646 PidTagCreatorEntryId

**Canonical name:** PidTagCreatorEntryId

**Description:** Specifies the original author of the message according to their Address Book EntryID.

**Property ID:** 0x3FF9

**Data type:** **PtypBinary**, 0x0102



**Area:** ID Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.31

**Consuming reference:** [\[MS-OXCMMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_ENTRYID, ptagCreatorEntryId

## 2.647 PidTagCreatorName

**Canonical name:** PidTagCreatorName

**Description:** Contains the name of the creator of a Message object.

**Property ID:** 0x3FF8

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.51

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_NAME, PR\_CREATOR\_NAME\_A, ptagCreatorName, PR\_CREATOR\_NAME\_W

## 2.648 PidTagCustomerId

**Canonical name:** PidTagCustomerId

**Description:** Contains the mail user's customer identification number.

**Property ID:** 0x3A4A

**Data type:** **PtypString**, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.8

**Alternate names:** PR\_CUSTOMER\_ID, PR\_CUSTOMER\_ID\_A, PR\_CUSTOMER\_ID\_W, urn:schemas:contacts:customerid

## 2.649 PidTagDamBackPatched

**Canonical name:** PidTagDamBackPatched

**Description:** Indicates whether the **Deferred Action Message (DAM)** was updated by the server.

**Property ID:** 0x6647

**Data type:** **PtypBoolean**, 0x000B

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.2

**Alternate names:** PR\_DAM\_BACK\_PATCHED, ptagDamBackPatched

## 2.650 PidTagDamOriginalEntryId

**Canonical name:** PidTagDamOriginalEntryId

**Description:** Contains the EntryID of the delivered message that the client has to process.

**Property ID:** 0x6646

**Data type:** PtypBinary, 0x0102

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.3

**Alternate names:** PR\_DAM\_ORIGINAL\_ENTRYID

## 2.651 PidTagDefaultPostMessageClass

**Canonical name:** PidTagDefaultPostMessageClass

**Description:** Contains the message class of the object.

**Property ID:** 0x36E5

**Data type:** PtypString, 0x001F

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.11.2

**Alternate names:** PR\_DEF\_POST\_MSGCLASS

## 2.652 PidTagDeferredActionMessageOriginalEntryId

**Canonical name:** PidTagDeferredActionMessageOriginalEntryId

**Description:** Contains the server EntryID for the DAM.

**Property ID:** 0x6741

**Data type:** PtypServerId, 0x00FB

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_DAM\_ORIG\_MSG\_SVREID, ptagDamOrgMsgSvrEID

## 2.653 PidTagDeferredDeliveryTime

**Canonical name:** PidTagDeferredDeliveryTime

**Description:** Contains the date and time, in UTC, at which the sender prefers that the message be delivered.

**Property ID:** 0x000F

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.6

**Alternate names:** PR\_DEFERRED\_DELIVERY\_TIME, ptagDeferredDeliveryTime, <http://schemas.microsoft.com/exchange/deferred-delivery-iso>

## 2.654 PidTagDeferredSendNumber

**Canonical name:** PidTagDeferredSendNumber

**Description:** Contains a number used in the calculation of how long to defer sending a message.

**Property ID:** 0x3FEB

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.2

**Alternate names:** PR\_DEFERRED\_SEND\_NUMBER

## 2.655 PidTagDeferredSendTime

**Canonical name:** PidTagDeferredSendTime

**Description:** Contains the amount of time after which a client would like to defer sending the message.

**Property ID:** 0x3FEF

**Data type:** PtypTime, 0x0040

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.4

**Alternate names:** PR\_DEFERRED\_SEND\_TIME, ptagDeferredSendTime

## 2.656 PidTagDeferredSendUnits

**Canonical name:** PidTagDeferredSendUnits

**Description:** Specifies the unit of time used as a multiplier with the **PidTagDeferredSendNumber** property (section [2.654](#)) value.

**Property ID:** 0x3FEC

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.3

**Alternate names:** PR\_DEFERRED\_SEND\_UNITS

## 2.657 PidTagDelegatedByRule

**Canonical name:** PidTagDelegatedByRule

**Description:** Specifies whether the message was forwarded due to the triggering of a delegate forward rule.

**Property ID:** 0x3FE3

**Data type:** PtypBoolean, 0x000B

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.84

**Consuming references:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_DELEGATED\_BY\_RULE

## 2.658 PidTagDelegateFlags

**Canonical name:** PidTagDelegateFlags

**Description:** Indicates whether delegates can view Message objects that are marked as private.

**Property ID:** 0x686B

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.6

**Alternate names:** PR\_DELEGATE\_FLAGS, ptagDelegateFlags

## 2.659 PidTagDeleteAfterSubmit

**Canonical name:** PidTagDeleteAfterSubmit

**Description:** Indicates that the original message is to be deleted after it is sent.

**Property ID:** 0x0E01

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.8

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** PR\_DELETE\_AFTER\_SUBMIT, ptagDeleteAfterSubmit

## 2.660 PidTagDeletedCountTotal

**Canonical name:** PidTagDeletedCountTotal

**Description:** Contains the total count of messages that have been deleted from a folder, excluding messages deleted within subfolders.

**Property ID:** 0x670B

**Data type:** **PtypInteger32**, 0x0003

**Area:** Server

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.13

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_DELETED\_COUNT\_TOTAL, ptagDeleteCountTotal

## 2.661 PidTagDeletedOn

**Canonical name:** PidTagDeletedOn

**Description:** Specifies the time, in UTC, when the item or folder was **soft deleted**.

**Property ID:** 0x668F

**Data type:** **PtypTime**, 0x0040

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.3

**Alternate names:** PR\_DELETED\_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

## 2.662 PidTagDeliverTime

**Canonical name:** PidTagDeliverTime

**Description:** Contains the delivery time for a delivery status notification, as specified [\[RFC3464\]](#), or a message disposition notification, as specified in [\[RFC3798\]](#).

**Property ID:** 0x0010

**Data type:** **PtypTime**, 0x0040

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.29

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_DELIVER\_TIME, ptagDeliverTime

## 2.663 PidTagDepartmentName

**Canonical name:** PidTagDepartmentName

**Description:** Contains a name for the department in which the mail user works.

**Property ID:** 0x3A18

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.6

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#) [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_DEPARTMENT\_NAME, PR\_DEPARTMENT\_NAME\_A, PR\_DEPARTMENT\_NAME\_W, urn:schemas:contacts:department

## 2.664 PidTagDepth

**Canonical name:** PidTagDepth

**Description:** Specifies the number of nested categories in which a given row is contained.

**Property ID:** 0x3005

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_DEPTH, ptagDepth

## 2.665 PidTagDisplayBcc

**Canonical name:** PidTagDisplayBcc

**Description:** Contains a list of **blind carbon copy (Bcc) recipient** display names.

**Property ID:** 0x0E02

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_BCC, PR\_DISPLAY\_BCC\_A, ptagDisplayBcc, PR\_DISPLAY\_BCC\_W, urn:schemas:httpmail:displaybcc

## 2.666 PidTagDisplayCc

**Canonical name:** PidTagDisplayCc

**Description:** Contains a list of **carbon copy (Cc) recipient** display names.

**Property ID:** 0x0E03

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_CC, PR\_DISPLAY\_CC\_A, ptagDisplayCc, PR\_DISPLAY\_CC\_W, urn:schemas:httpmail:displaycc

## 2.667 PidTagDisplayName

**Canonical name:** PidTagDisplayName

**Description:** Contains the display name of the folder.

**Property ID:** 0x3001

**Data type:** **PtypString**, 0x001F

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.5

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDVSEC\]](#)

**Alternate names:** PR\_DISPLAY\_NAME, PR\_DISPLAY\_NAME\_A, ptagDisplayName, PR\_DISPLAY\_NAME\_W, urn:schemas:contacts:cn

## 2.668 PidTagDisplayNamePrefix

**Canonical name:** PidTagDisplayNamePrefix

**Description:** Contains the mail user's honorific title.

**Property ID:** 0x3A45

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_DISPLAY\_NAME\_PREFIX, PR\_DISPLAY\_NAME\_PREFIX\_A, PR\_DISPLAY\_NAME\_PREFIX\_W, urn:schemas:contacts:personaltitle

## 2.669 PidTagDisplayTo

**Canonical name:** PidTagDisplayTo

**Description:** Contains a list of the **primary recipient** display names, separated by semicolons, when an e-mail message has primary recipients (1).

**Property ID:** 0x0E04

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_TO, PR\_DISPLAY\_TO\_A, ptagDisplayTo, PR\_DISPLAY\_TO\_W

## 2.670 PidTagDisplayType

**Canonical name:** PidTagDisplayType

**Description:** Contains an integer value that indicates how to display an Address Book object in a table or as an addressee on a message.

**Property ID:** 0x3900

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**Defining reference:**[\[MS-OXOABK\]](#) section 2.2.3.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE, ptagDisplayType

## 2.671 PidTagDisplayTypeEx

**Canonical name:** PidTagDisplayTypeEx

**Description:** Contains an integer value that indicates how to display an Address Book object in a table or as a recipient (1) on a message.

**Property ID:** 0x3905

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE\_EX

## 2.672 PidTagEmailAddress

**Canonical name:** PidTagEmailAddress

**Description:** Contains the e-mail address of a Message object.



**Property ID:** 0x3003

**Data type:** PtypString, 0x001F

**Area:** MapiCommon

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.14

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFCXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

**Alternate names:** PR\_EMAIL\_ADDRESS, PR\_EMAIL\_ADDRESS\_A, PR\_EMAIL\_ADDRESS\_W

## 2.673 PidTagEndDate

**Canonical name:** PidTagEndDate

**Description:** Contains the value of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

**Property ID:** 0x0061

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.31

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_END\_DATE, [http://schemas.microsoft.com/mapi/end\\_date](http://schemas.microsoft.com/mapi/end_date)

## 2.674 PidTagEntryId

**Canonical name:** PidTagEntryId

**Description:** Contains the information to identify many different types of **messaging objects**.

**Property ID:** 0x0FFF

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.4

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFCXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXWAVLS\]](#)

**Alternate names:** PR\_ENTRYID, ptagEntryId

## 2.675 PidTagExceptionEndTime

**Canonical name:** PidTagExceptionEndTime

**Description:** Contains the start date and time of the exception in the local time zone of the computer when the exception is created.

**Property ID:** 0x7FFC

**Data type:** **PtypTime**, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_ENDTIME, ptagExceptionEndTime

## 2.676 PidTagExceptionReplaceTime

**Canonical name:** PidTagExceptionReplaceTime

**Description:** Indicates the original date and time, in UTC, at which the instance in the recurrence pattern would have occurred if it were not an exception.

**Property ID:** 0x7FF9

**Data type:** **PtypTime**, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.6

**Alternate names:** PR\_EXCEPTION\_REPLACETIME

## 2.677 PidTagExceptionStartTime

**Canonical name:** PidTagExceptionStartTime

**Description:** Contains the end date and time of the exception in the local time zone of the computer when the exception is created.

**Property ID:** 0x7FFB

**Data type:** **PtypTime**, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_STARTTIME, ptagExceptionStartTime

## 2.678 PidTagExchangeNTSecurityDescriptor

**Canonical name:** PidTagExchangeNTSecurityDescriptor

**Description:** Contains the calculated security descriptor for the item.

**Property ID:** 0x0E84

**Data type:** PtypBinary, 0x0102

**Area:** Calendar Document

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.8

**Alternate names:** <http://schemas.microsoft.com/exchange/ntsecuritydescriptor>,  
<http://schemas.microsoft.com/exchange/ntsecuritydescriptor>

## 2.679 PidTagExpiryNumber

**Canonical name:** PidTagExpiryNumber

**Description:** Contains an integer value that is used along with the **PidTagExpiryUnits** property (section [2.681](#)) to define the expiry send time.

**Property ID:** 0x3FED

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.5

**Alternate names:** PR\_EXPIRY\_NUMBER

## 2.680 PidTagExpiryTime

**Canonical name:** PidTagExpiryTime

**Description:** Contains the time, in UTC, after which a client wants to receive an expiry event if the message arrives late.

**Property ID:** 0x0015

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.7

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_EXPIRY\_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date,  
<http://schemas.microsoft.com/exchange/expiry-date-iso>

## 2.681 PidTagExpiryUnits

**Canonical name:** PidTagExpiryUnits

**Description:** Contains the unit of time that the value of the **PidTagExpiryNumber** property (section [2.679](#)) multiplies.

**Property ID:** 0x3FEE

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.6

**Alternate names:** PR\_EXPIRY\_UNITS

## 2.682 PidTagExtendedFolderFlags

**Canonical name:** PidTagExtendedFolderFlags

**Description:** Contains encoded sub-properties for a folder.

**Property ID:** 0x36DA

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_EXTENDED\_FOLDER\_FLAGS, ptagExtendedFolderFlags

## 2.683 PidTagExtendedRuleMessageActions

**Canonical name:** PidTagExtendedRuleMessageActions

**Description:** Contains action information about named properties used in the rule.

**Property ID:** 0x0E99

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.9

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_ACTIONS

## 2.684 PidTagExtendedRuleMessageCondition

**Canonical name:** PidTagExtendedRuleMessageCondition

**Description:** Contains condition information about named properties used in the rule.

**Property ID:** 0x0E9A

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.10

**Consuming references:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_CONDITION

## 2.685 PidTagExtendedRuleSizeLimit

**Canonical name:** PidTagExtendedRuleSizeLimit

**Description:** Contains the maximum size, in bytes, that the user is allowed to accumulate for a single extended rule.

**Property ID:** 0x0E9B

**Data type:** PtypInteger32, 0x0003

**Area:** Rules

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Consuming Reference:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_SIZE\_LIMIT

## 2.686 PidTagFaxNumberOfPages

**Canonical name:** PidTagFaxNumberOfPages

**Description:** Contains the number of pages in a Fax object.

**Property ID:** 0x6804

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.7

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaFaxNumberOfPages

## 2.687 PidTagFlagCompleteTime

**Canonical name:** PidTagFlagCompleteTime

**Description:** Specifies the date and time, in UTC, that the Message object was flagged as complete.

**Property ID:** 0x1091

**Data type:** PtypTime, 0x0040

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_FLAG\_COMPLETE\_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

## 2.688 PidTagFlagStatus

**Canonical name:** PidTagFlagStatus

**Description:** Specifies the flag state of the Message object.

**Property ID:** 0x1090

**Data type:** **PtypInteger32**, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FLAG\_STATUS, ptagFlagStatus

## 2.689 PidTagFlatUrlName

**Canonical name:** PidTagFlatUrlName

**Description:** Contains a unique identifier for an item across the message store.

**Property ID:** 0x670E

**Data type:** **PtypString**, 0x001F

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.9

**Alternate names:** PR\_FLAT\_URL\_NAME, PR\_FLAT\_URL\_NAME\_A, PR\_FLAT\_URL\_NAME\_W, ptagFlatURLName, <http://schemas.microsoft.com/exchange/permanenturl>

## 2.690 PidTagFolderAssociatedContents

**Canonical name:** PidTagFolderAssociatedContents

**Description:** Identifies all FAI messages in the current folder.

**Property ID:** 0x3610

**Data type:** **PtypObject**, 0x000D

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.6

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_FOLDER\_ASSOCIATED\_CONTENTS

## 2.691 PidTagFolderId

**Canonical name:** PidTagFolderId

**Description:** Contains the Folder ID (FID) ([\[MS-OXCDATA\]](#) section 2.2.1.1) of the folder.

**Property ID:** 0x6748

**Data type:** **PtypInteger64**, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** ptagFID

## 2.692 PidTagFolderType

**Canonical name:** PidTagFolderType

**Description:** Specifies the type of a folder that includes the **Root folder**, Generic folder, and Search folder.

**Property ID:** 0x3601

**Data type:** **PtypInteger32**, 0x0003

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_FOLDER\_TYPE, ptagFolderType

## 2.693 PidTagFollowupIcon

**Canonical name:** PidTagFollowupIcon

**Description:** Specifies the flag color of the Message object.

**Property ID:** 0x1095

**Data type:** **PtypInteger32**, 0x0003

**Area:** RenMessageFolder

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FOLLOWUP\_ICON, ptagFollowupIcon

## 2.694 PidTagFreeBusyCountMonths

**Canonical name:** PidTagFreeBusyCountMonths

**Description:** Contains an integer value used to calculate the start and end dates of the range of free/busy data to be published to the public folders.

**Property ID:** 0x6869

**Data type:** PtypInteger32, 0x0003

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_COUNT\_MONTHS

## 2.695 PidTagFreeBusyEntryIds

**Canonical name:** PidTagFreeBusyEntryIds

**Description:** Contains EntryIDs of the Delegate Information object, the free/busy message of the logged on user, and the folder with the **PidTagDisplayName** property (section [2.667](#)) value of "Freebusy Data".

**Property ID:** 0x36E4

**Data type:** PtypMultipleBinary, 0x1102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.6

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_FREEBUSY\_ENTRYIDS, ptagFreeBusyEntryIds

## 2.696 PidTagFreeBusyMessageEmailAddress

**Canonical name:** PidTagFreeBusyMessageEmailAddress

**Description:** Specifies the e-mail address of the user to whom this free/busy message applies.

**Property ID:** 0x6849

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.12

**Alternate names:** PR\_FREEBUSY\_EMA

## 2.697 PidTagFreeBusyPublishEnd

**Canonical name:** PidTagFreeBusyPublishEnd

**Description:** Specifies the end time, in UTC, of the publishing range.

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003



**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.10

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_END

## 2.698 PidTagFreeBusyPublishStart

**Canonical name:** PidTagFreeBusyPublishStart

**Description:** Specifies the start time, in UTC, of the publishing range.

**Property ID:** 0x6847

**Data type:** **PtypInteger32**, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.9

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_START

## 2.699 PidTagFreeBusyRangeTimestamp

**Canonical name:** PidTagFreeBusyRangeTimestamp

**Description:** Specifies the time, in UTC, that the data was published.

**Property ID:** 0x6868

**Data type:** **PtypTime**, 0x0040

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.11

**Alternate names:** PR\_FREEBUSY\_RANGE\_TIMESTAMP

## 2.700 PidTagFtpSite

**Canonical name:** PidTagFtpSite

**Description:** Contains the **File Transfer Protocol (FTP)** site address of the mail user.

**Property ID:** 0x3A4C

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.15

**Alternate names:** PR\_FTP\_SITE, PR\_FTP\_SITE\_A, PR\_FTP\_SITE\_W, urn:schemas:contacts:ftpsite

## 2.701 PidTagGatewayNeedsToRefresh

**Canonical name:** PidTagGatewayNeedsToRefresh

**Description:** This property is deprecated and SHOULD NOT be used.

**Property ID:** 0x6846

**Data type:** **PtypBoolean**, 0x000B

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.1

**Alternate names:** PR\_GATEWAY\_NEEDS\_TO\_REFRESH

## 2.702 PidTagGender

**Canonical name:** PidTagGender

**Description:** Contains a value that represents the mail user's gender.

**Property ID:** 0x3A4D

**Data type:** **PtypInteger16**, 0x0002

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.20

**Alternate names:** PR\_GENDER, urn:schemas:contacts:gender

## 2.703 PidTagGeneration

**Canonical name:** PidTagGeneration

**Description:** Contains a generational abbreviation that follows the full name of the mail user.

**Property ID:** 0x3A05

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_GENERATION, PR\_GENERATION\_A, PR\_GENERATION\_W,  
urn:schemas:contacts:namesuffix

## 2.704 PidTagGivenName

**Canonical name:** PidTagGivenName

**Description:** Contains the mail user's given name.

**Property ID:** 0x3A06

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.2

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_GIVEN\_NAME, PR\_GIVEN\_NAME\_A, PR\_GIVEN\_NAME\_W, urn:schemas:contacts:givenName

## 2.705 PidTagGovernmentIdNumber

**Canonical name:** PidTagGovernmentIdNumber

**Description:** Contains a government identifier for the mail user.

**Property ID:** 0x3A07

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.9

**Alternate names:** PR\_GOVERNMENT\_ID\_NUMBER, PR\_GOVERNMENT\_ID\_NUMBER\_A, PR\_GOVERNMENT\_ID\_NUMBER\_W, urn:schemas:contacts:governmentid

## 2.706 PidTagHasAttachments

**Canonical name:** PidTagHasAttachments

**Description:** Indicates whether the Message object contains at least one attachment.

**Property ID:** 0x0E1B

**Data type:** **PtypBoolean**, 0x000B

**Area:** Message Attachment Properties Property set

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

## 2.707 PidTagHasDeferredActionMessages

**Canonical name:** PidTagHasDeferredActionMessages

**Description:** Indicates whether a Message object has a deferred action message associated with it.

**Property ID:** 0x3FEA

**Data type:** **PtypBoolean**, 0x000B

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.1

**Alternate names:** PR\_HAS\_DAMS, ptagHasDAMs

## 2.708 PidTagHasNamedProperties

**Canonical name:** PidTagHasNamedProperties

**Description:** Indicates whether the Message object has a named property.

**Property ID:** 0x664A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.39

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_HAS\_NAMED\_PROPERTIES, ptagHasNamedProperties

## 2.709 PidTagHasRules

**Canonical name:** PidTagHasRules

**Description:** Indicates whether a Folder object has rules.

**Property ID:** 0x663A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.8.1

**Alternate names:** PR\_HAS\_RULES, ptagHasRules

## 2.710 PidTagHierarchyChangeNumber

**Canonical name:** PidTagHierarchyChangeNumber

**Description:** Contains a number that monotonically increases every time a subfolder is added to, or deleted from, this folder.

**Property ID:** 0x663E

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.7

**Alternate names:** PR\_HIERARCHY\_CHANGE\_NUM

## 2.711 PidTagHobbies

**Canonical name:** PidTagHobbies

**Description:** Contains the names of the mail user's hobbies.

**Property ID:** 0x3A43

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOBBIES, PR\_HOBBIES\_A, PR\_HOBBIES\_W, urn:schemas:contacts:hobbies

## 2.712 PidTagHome2TelephoneNumber

**Canonical name:** PidTagHome2TelephoneNumber

**Description:** Contains a secondary telephone number at the mail user's home.

**Property ID:** 0x3A2F

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.25

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER, PR\_HOME2\_TELEPHONE\_NUMBER\_A, PR\_HOME2\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homephone2

## 2.713 PidTagHome2TelephoneNumbers

**Canonical name:** PidTagHome2TelephoneNumbers

**Description:** Contains secondary telephone numbers at the mail user's home.

**Property ID:** 0x3A2F

**Data type:** PtypMultipleString, 0x101F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.26

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER\_A\_MV

## 2.714 PidTagHomeAddressCity

**Canonical name:** PidTagHomeAddressCity

**Description:** Contains the name of the mail user's home locality, such as the town or city.

**Property ID:** 0x3A59

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_CITY, PR\_HOME\_ADDRESS\_CITY\_A, PR\_HOME\_ADDRESS\_CITY\_W, urn:schemas:contacts:homeCity

## 2.715 PidTagHomeAddressCountry

**Canonical name:** PidTagHomeAddressCountry

**Description:** Contains the name of the mail user's home country/region.

**Property ID:** 0x3A5A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_COUNTRY, PR\_HOME\_ADDRESS\_COUNTRY\_A, PR\_HOME\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:homeCountry

## 2.716 PidTagHomeAddressPostalCode

**Canonical name:** PidTagHomeAddressPostalCode

**Description:** Contains the postal code for the mail user's home postal address.

**Property ID:** 0x3A5B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POSTAL\_CODE, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_A, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:homePostalCode

## 2.717 PidTagHomeAddressPostOfficeBox

**Canonical name:** PidTagHomeAddressPostOfficeBox

**Description:** Contains the number or identifier of the mail user's home post office box.

**Property ID:** 0x3A5E

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:homepostofficebox

## 2.718 PidTagHomeAddressStateOrProvince

**Canonical name:** PidTagHomeAddressStateOrProvince

**Description:** Contains the name of the mail user's home state or province.

**Property ID:** 0x3A5C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:homeState

## 2.719 PidTagHomeAddressStreet

**Canonical name:** PidTagHomeAddressStreet

**Description:** Contains the mail user's home street address.

**Property ID:** 0x3A5D

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.20

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STREET, PR\_HOME\_ADDRESS\_STREET\_A, PR\_HOME\_ADDRESS\_STREET\_W, urn:schemas:contacts:homeStreet

## 2.720 PidTagHomeFaxNumber

**Canonical name:** PidTagHomeFaxNumber

**Description:** Contains the telephone number of the mail user's home fax machine.

**Property ID:** 0x3A25

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_FAX\_NUMBER, PR\_HOME\_FAX\_NUMBER\_A, PR\_HOME\_FAX\_NUMBER\_W, urn:schemas:contacts:homefax

## 2.721 PidTagHomeTelephoneNumber

**Canonical name:** PidTagHomeTelephoneNumber

**Description:** Contains the primary telephone number of the mail user's home.

**Property ID:** 0x3A09

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.22

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_TELEPHONE\_NUMBER, PR\_HOME\_TELEPHONE\_NUMBER\_A, PR\_HOME\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homePhone

## 2.722 PidTagHtml

**Canonical name:** PidTagHtml

**Description:** Contains message body (2) text in HTML format.

**Property ID:** 0x1013

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.9

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_HTML, ptagHtml

## 2.723 PidTagICalendarEndTime

**Canonical name:** PidTagICalendarEndTime

**Description:** Contains the date and time, in UTC, when an appointment or meeting ends.

**Property ID:** 0x10C4

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:**[\[MS-XWDCAL\]](#) section 2.2.2.39

**Alternate names:** urn:schemas:calendar:dtend



## 2.724 PidTagICalendarReminderNextTime

**Canonical name:** PidTagICalendarReminderNextTime

**Description:** Contains the date and time, in UTC, for the activation of the next reminder.

**Property ID:** 0x10CA

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.40

**Alternate names:** urn:schemas:calendar:remindernexttime

## 2.725 PidTagICalendarStartTime

**Canonical name:** PidTagICalendarStartTime

**Description:** Contains the date and time, in UTC, when the appointment or meeting starts.

**Property ID:** 0x10C3

**Data type:** PtypTime, 0x0040

**Area:** Calendar Property set

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.41

**Alternate names:** urn:schemas:calendar:dtstart

## 2.726 PidTagIconIndex

**Canonical name:** PidTagIconIndex

**Description:** Specifies which icon is to be used by a user interface when displaying a group of Message objects.

**Property ID:** 0x1080

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ICON\_INDEX, ptagIconIndex

## 2.727 PidTagImportance

**Canonical name:** PidTagImportance

**Description:** Indicates the level of importance assigned by the end user to the Message object.

**Property ID:** 0x0017

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, <http://schemas.microsoft.com/exchange/importance-long>, <http://schemas.microsoft.com/exchange/x-priority-long>

## 2.728 PidTagInConflict

**Canonical name:** PidTagInConflict

**Description:** Specifies whether the attachment represents an alternate replica.

**Property ID:** 0x666C

**Data type:** PtypBoolean, 0x000B

**Area:** Conflict Note

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.3

**Alternate names:** PR\_IN\_CONFLICT, ptagInConflict

## 2.729 PidTagInitialDetailsPane

**Canonical name:** PidTagInitialDetailsPane

**Description:** Indicates which page of a display template to display first.

**Property ID:** 0x3F08

**Data type:** PtypInteger32, 0x0003

**Area:** MAPI Display Tables

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.33

**Consuming Reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_INITIAL\_DETAILS\_PANE

## 2.730 PidTagInitials

**Canonical name:** PidTagInitials

**Description:** Contains the initials for parts of the full name of the mail user.

**Property ID:** 0x3A0A

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.3

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_INITIALS, PR\_INITIALS\_A, PR\_INITIALS\_W, urn:schemas:contacts:initials

### 2.731 PidTagInReplyToId

**Canonical name:** PidTagInReplyToId

**Description:** Contains the value of the original message's **PidTagInternetMessageId** property (section [2.737](#)) value.

**Property ID:** 0x1042

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.13

**Consuming Reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_IN\_REPLY\_TO\_ID, PR\_IN\_REPLY\_TO\_ID\_A, PR\_IN\_REPLY\_TO\_ID\_W

### 2.732 PidTagInstanceKey

**Canonical name:** PidTagInstanceKey

**Description:** Contains an object on an NSPI server.

**Property ID:** 0x0FF6

**Data type:** **PtypBinary**, 0x0102

**Area:** Table Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_INSTANCE\_KEY, ptagInstanceKey

### 2.733 PidTagInstanceNum

**Canonical name:** PidTagInstanceNum

**Description:** Contains an identifier for a single instance of a row in the table.

**Property ID:** 0x674E

**Data type:** **PtypInteger32**, 0x0003

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstanceNum

## 2.734 PidTagInstID

**Canonical name:** PidTagInstID

**Description:** Contains an identifier for all instances of a row in the table.

**Property ID:** 0x674D

**Data type:** **PtypInteger64**, 0x0014

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstID

## 2.735 PidTagInternetCodepage

**Canonical name:** PidTagInternetCodepage

**Description:** Indicates the code page used for the **PidTagBody** property (section [2.609](#)) or the **PidTagBodyHtml** property (section [2.612](#)).

**Property ID:** 0x3FDE

**Data type:** **PtypInteger32**, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_CPID, ptagInternetCpid

## 2.736 PidTagInternetMailOverrideFormat

**Canonical name:** PidTagInternetMailOverrideFormat

**Description:** Indicates the encoding method and HTML inclusion for attachments.

**Property ID:** 0x5902

**Data type:** **PtypInteger32**, 0x0003

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_INETMAIL\_OVERRIDE\_FORMAT, ptagInetMailOverrideFormat

### 2.737 PidTagInternetMessageId

**Canonical name:** PidTagInternetMessageId

**Description:** Corresponds to the **message-id** field.

**Property ID:** 0x1035

**Data type:** **PtypString**, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_MESSAGE\_ID, PR\_INTERNET\_MESSAGE\_ID\_A, PR\_INTERNET\_MESSAGE\_ID\_W

### 2.738 PidTagInternetReferences

**Canonical name:** PidTagInternetReferences

**Description:** Contains a list of message IDs that specify the messages to which this reply is related.

**Property ID:** 0x1039

**Data type:** **PtypString**, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_INTERNET\_REFERENCES, PR\_INTERNET\_REFERENCES\_A, PR\_INTERNET\_REFERENCES\_W

### 2.739 PidTagIpmAppointmentEntryId

**Canonical name:** PidTagIpmAppointmentEntryId

**Description:** Contains the EntryID of the Calendar folder.

**Property ID:** 0x36D0

**Data type:** **PtypBinary**, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_APPOINTMENT\_ENTRYID

## 2.740 PidTagIpmContactEntryId

**Canonical name:** PidTagIpmContactEntryId

**Description:** Contains the EntryID of the Contacts folder.

**Property ID:** 0x36D1

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_CONTACT\_ENTRYID

## 2.741 PidTagIpmDraftsEntryId

**Canonical name:** PidTagIpmDraftsEntryId

**Description:** Contains the EntryID of the Drafts folder.

**Property ID:** 0x36D7

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Alternate names:** PR\_IPM\_DRAFTS\_ENTRYID

## 2.742 PidTagIpmJournalEntryId

**Canonical name:** PidTagIpmJournalEntryId

**Description:** Contains the EntryID of the Journal folder.

**Property ID:** 0x36D2

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_JOURNAL\_ENTRYID

## 2.743 PidTagIpmNoteEntryId

**Canonical name:** PidTagIpmNoteEntryId

**Description:** Contains the EntryID of the Notes folder.

**Property ID:** 0x36D3

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_NOTE\_ENTRYID

## 2.744 PidTagIpmTaskEntryId

**Canonical name:** PidTagIpmTaskEntryId

**Description:** Contains the EntryID of the Tasks folder.

**Property ID:** 0x36D4

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_TASK\_ENTRYID

## 2.745 PidTagIsdnNumber

**Canonical name:** PidTagIsdnNumber

**Description:** Contains the **Integrated Services Digital Network (ISDN)** telephone number of the mail user.

**Property ID:** 0x3A2D

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.16

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ISDN\_NUMBER, PR\_ISDN\_NUMBER\_A, PR\_ISDN\_NUMBER\_W, urn:schemas:contacts:internationalisdnnumber

## 2.746 PidTagJunkAddRecipientsToSafeSendersList

**Canonical name:** PidTagJunkAddRecipientsToSafeSendersList

**Description:** Indicates whether e-mail recipients (1) are to be added to the safe senders list.

**Property ID:** 0x6103

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.1

**Alternate names:** PR\_JUNK\_ADD\_RECIPS\_TO\_SSL

## 2.747 PidTagJunkIncludeContacts

**Canonical name:** PidTagJunkIncludeContacts

**Description:** Indicates whether e-mail addresses of the contacts in the Contacts folder are treated in a special way with respect to the spam filter.

**Property ID:** 0x6100

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.2

**Alternate names:** PR\_JUNK\_INCLUDE\_CONTACTS

## 2.748 PidTagJunkPermanentlyDelete

**Canonical name:** PidTagJunkPermanentlyDelete

**Description:** Indicates whether messages identified as spam can be permanently deleted.

**Property ID:** 0x6102

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.3

**Alternate names:** PR\_JUNK\_PERMANENTLY\_DELETE

## 2.749 PidTagJunkPhishingEnableLinks

**Canonical name:** PidTagJunkPhishingEnableLinks

**Description:** Indicated whether the phishing stamp on a message is to be ignored.

**Property ID:** 0x6107

**Data type:** PtypBoolean, 0x000B

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.4

**Consuming reference:** [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_JUNK\_PHISHING\_ENABLE\_LINKS



## 2.750 PidTagJunkThreshold

**Canonical name:** PidTagJunkThreshold

**Description:** Indicates how aggressively incoming e-mail is to be sent to the Junk E-mail folder.

**Property ID:** 0x6101

**Data type:** **PtypInteger32**, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.5

**Alternate names:** PR\_JUNK\_THRESHOLD

## 2.751 PidTagKeyword

**Canonical name:** PidTagKeyword

**Description:** Contains a keyword that identifies the mail user to the mail user's system administrator.

**Property ID:** 0x3A0B

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.32

**Alternate names:** PR\_KEYWORD, PR\_KEYWORD\_A, PR\_KEYWORD\_W

## 2.752 PidTagLanguage

**Canonical name:** PidTagLanguage

**Description:** Contains a value that indicates the language in which the messaging user is writing messages.

**Property ID:** 0x3A0C

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.4

**Alternate names:** PR\_LANGUAGE, PR\_LANGUAGE\_A, PR\_LANGUAGE\_W,  
urn:schemas:contacts:language

## 2.753 PidTagLastModificationTime

**Canonical name:** PidTagLastModificationTime

**Description:** Contains the time, in UTC, of the last modification to the object.

**Property ID:** 0x3008

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.2

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-EXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_LAST\_MODIFICATION\_TIME, ptagLastModificationTime, urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

## 2.754 PidTagLastModifierEntryId

**Canonical name:** PidTagLastModifierEntryId

**Description:** Specifies the Address Book EntryID of the last user to modify the contents of the message.

**Property ID:** 0x3FFB

**Data type:** PtypBinary, 0x0102

**Area:** History Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.32

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_ENTRYID, ptagLastModifierEntryId

## 2.755 PidTagLastModifierName

**Canonical name:** PidTagLastModifierName

**Description:** Contains the name of the last mail user to change the Message object.

**Property ID:** 0x3FFA

**Data type:** PtypString, 0x001F

**Area:** History Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_NAME, PR\_LAST\_MODIFIER\_NAME\_A, ptagLastModifierName, PR\_LAST\_MODIFIER\_NAME\_W

## 2.756 PidTagLastVerbExecuted

**Canonical name:** PidTagLastVerbExecuted

**Description:** Specifies the last verb executed for the message item to which it is related.

**Property ID:** 0x1081

**Data type:** PtypInteger32, 0x0003

**Area:** History Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.14

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTED, ptagLastVerbExecuted

## 2.757 PidTagLastVerbExecutionTime

**Canonical name:** PidTagLastVerbExecutionTime

**Description:** Contains the date and time, in UTC, during which the operation represented in the **PidTagLastVerbExecuted** property (section [2.756](#)) took place.

**Property ID:** 0x1082

**Data type:** PtypTime, 0x0040

**Area:** History Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.15

**Consuming Reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTION\_TIME, ptagLastVerbExecutionTime

## 2.758 PidTagListHelp

**Canonical name:** PidTagListHelp

**Description:** Contains a URI that provides detailed help information for the mailing list from which an e-mail message was sent.

**Property ID:** 0x1043

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.81

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_HELP, PR\_LIST\_HELP\_A, PR\_LIST\_HELP\_W

## 2.759 PidTagListSubscribe

**Canonical name:** PidTagListSubscribe

**Description:** Contains the URI that subscribes a recipient (2) to a message's associated mailing list.

**Property ID:** 0x1044

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.82

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_SUBSCRIBE, PR\_LIST\_SUBSCRIBE\_A, PR\_LIST\_SUBSCRIBE\_W

## 2.760 PidTagListUnsubscribe

**Canonical name:** PidTagListUnsubscribe

**Description:** Contains the URI that unsubscribes a recipient (2) from a message's associated mailing list.

**Property ID:** 0x1045

**Data type:** **PtypString**, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.83

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_UNSUBSCRIBE, PR\_LIST\_UNSUBSCRIBE\_A, PR\_LIST\_UNSUBSCRIBE\_W

## 2.761 PidTagLocalCommitTime

**Canonical name:** PidTagLocalCommitTime

**Description:** Specifies the time, in UTC, that a Message object or Folder object was last changed.

**Property ID:** 0x6709

**Data type:** **PtypTime**, 0x0040

**Area:** Server

**Defining references:** [\[MS-OXCMSG\]](#) section 2.2.1.49; [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.11

**Consuming Reference:**

**Alternate names:** PR\_LOCAL\_COMMIT\_TIME, ptagLocalCommitTime

## 2.762 PidTagLocalCommitTimeMax

**Canonical name:** PidTagLocalCommitTimeMax

**Description:** Contains the time of the most recent message change within the folder container, excluding messages changed within subfolders.

**Property ID:** 0x670A

**Data type:** **PtypTime**, 0x0040

**Area:** Server

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.12

**Consuming Reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_LOCAL\_COMMIT\_TIME\_MAX, ptagLocalCommitTimeMax

### 2.763 PidTagLocaleId

**Canonical name:** PidTagLocaleId

**Description:** Contains the **Logon object** LocaleID.

**Property ID:** 0x66A1

**Data type:** **PtypInteger32**, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.12

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_LOCALE\_ID, ptagLocaleId

### 2.764 PidTagLocality

**Canonical name:** PidTagLocality

**Description:** Contains the name of the mail user's locality, such as the town or city.

**Property ID:** 0x3A27

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.16

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_LOCALITY, PR\_LOCALITY\_A, PR\_LOCALITY\_W, PR\_BUSINESS\_ADDRESS\_LOCALITY, PR\_BUSINESS\_ADDRESS\_LOCALITY\_A, PR\_BUSINESS\_ADDRESS\_LOCALITY\_W, urn:schemas:contacts:mailingcity

### 2.765 PidTagLocation

**Canonical name:** PidTagLocation

**Description:** Contains the location of the mail user.

**Property ID:** 0x3A0D

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.5

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_LOCATION, PR\_LOCATION\_A, PR\_LOCATION\_W,  
urn:schemas:contacts:location

## 2.766 PidTagMailboxOwnerEntryId

**Canonical name:** PidTagMailboxOwnerEntryId

**Description:** Contains the EntryID in the Global Address List (GAL) of the owner of the mailbox.

**Property ID:** 0x661B

**Data type:** PtypBinary, 0x0102

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_ENTRYID, ptagMailboxOwnerEntryId

## 2.767 PidTagMailboxOwnerName

**Canonical name:** PidTagMailboxOwnerName

**Description:** Contains the display name of the owner of the mailbox.

**Property ID:** 0x661C

**Data type:** PtypString, 0x001F

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_NAME, PR\_MAILBOX\_OWNER\_NAME\_A,  
ptagMailboxOwnerName, PR\_MAILBOX\_OWNER\_NAME\_W

## 2.768 PidTagManagerName

**Canonical name:** PidTagManagerName

**Description:** Contains the name of the mail user's manager.

**Property ID:** 0x3A4E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MANAGER\_NAME, PR\_MANAGER\_NAME\_A, PR\_MANAGER\_NAME\_W, urn:schemas:contacts:manager

## 2.769 PidTagMappingSignature

**Canonical name:** PidTagMappingSignature

**Description:** A 16-byte constant that is present on all Address Book objects, but is not present on objects in an offline address book.

**Property ID:** 0x0FF8

**Data type:** PtypBinary, 0x0102

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.32

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_MAPPING\_SIGNATURE, ptagMappingSignature

## 2.770 PidTagMaximumSubmitMessageSize

**Canonical name:** PidTagMaximumSubmitMessageSize

**Description:** Maximum size, in kilobytes, of a message that a user is allowed to submit for transmission to another user.

**Property ID:** 0x666D

**Data type:** PtypInteger32, 0x0003

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_MAX\_SUBMIT\_MESSAGE\_SIZE

## 2.771 PidTagMemberId

**Canonical name:** PidTagMemberId

**Description:** Contains a unique identifier that the messaging server generates for each user.

**Property ID:** 0x6671

**Data type:** PtypInteger64, 0x0014

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.5

**Alternate names:** PR\_MEMBER\_ID, ptagMemberId

## 2.772 PidTagMemberName

**Canonical name:** PidTagMemberName

**Description:** Contains the user-readable name of the user.

**Property ID:** 0x6672

**Data type:** **PtypString**, 0x001F

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.6

**Alternate names:** PR\_MEMBER\_NAME, PR\_MEMBER\_NAME\_A, ptagMemberName, PR\_MEMBER\_NAME\_W

### 2.773 PidTagMemberRights

**Canonical name:** PidTagMemberRights

**Description:** Contains the permissions for the specified user.

**Property ID:** 0x6673

**Data type:** **PtypInteger32**, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_MEMBER\_RIGHTS, ptagMemberRights

### 2.774 PidTagMessageAttachments

**Canonical name:** PidTagMessageAttachments

**Description:** Identifies all attachments to the current message.

**Property ID:** 0x0E13

**Data type:** **PtypObject**, 0x000D

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.52

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_MESSAGE\_ATTACHMENTS, ptagMessageAttachments

### 2.775 PidTagMessageCcMe

**Canonical name:** PidTagMessageCcMe

**Description:** Indicates that the receiving mailbox owner is a carbon copy (Cc) recipient of this e-mail message.

**Property ID:** 0x0058



**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.18

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_CC\_ME, ptagMessageCcMe

## 2.776 PidTagMessageClass

**Canonical name:** PidTagMessageClass

**Description:** Denotes the specific type of the Message object.

**Property ID:** 0x001A

**Data type:** PtypString, 0x001F

**Area:** Common Property set

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFCOLD\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFCXICS\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_MESSAGE\_CLASS, PR\_MESSAGE\_CLASS\_A, ptagMessageClass, PR\_MESSAGE\_CLASS\_W, <http://schemas.microsoft.com/exchange/outlookmessageclass><http://schemas.microsoft.com/exchange/outlookmessageclass>

## 2.777 PidTagMessageCodepage

**Canonical name:** PidTagMessageCodepage

**Description:** Specifies the code page used to encode the **non-Unicode** string properties on this Message object.

**Property ID:** 0x3FFD

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXTNEF\]](#) [\[MS-OXCFCXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_MESSAGE\_CODEPAGE

## 2.778 PidTagMessageDeliveryTime

**Canonical name:** PidTagMessageDeliveryTime

**Description:** Contains the posting date of the item or entry.

**Property ID:** 0x0E06

**Data type:** **PtypTime**, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.9

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORSS\]](#)

**Alternate names:** PR\_MESSAGE\_DELIVERY\_TIME, urn:schemas:httpmail:datereceived

## 2.779 PidTagMessageEditorFormat

**Canonical name:** PidTagMessageEditorFormat

**Description:** Specifies the format that an e-mail editor can use for editing the message body (2).

**Property ID:** 0x5909

**Data type:** **PtypInteger32**, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.78

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MSG\_EDITOR\_FORMAT, ptagMsgEditorFormat

## 2.780 PidTagMessageFlags

**Canonical name:** PidTagMessageFlags

**Description:** Specifies the status of the Message object.

**Property ID:** 0x0E07

**Data type:** **PtypInteger32**, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_MESSAGE\_FLAGS, ptagMessageFlags

## 2.781 PidTagMessageHandlingSystemCommonName

**Canonical name:** PidTagMessageHandlingSystemCommonName

**Description:** Contains the **common name** of a messaging user for use in a message header.

**Property ID:** 0x3A0F

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.33

**Alternate names:** PR\_MHS\_COMMON\_NAME, PR\_MHS\_COMMON\_NAME\_A, PR\_MHS\_COMMON\_NAME\_W, urn:schemas:contacts:dn

## 2.782 PidTagMessageLocaleId

**Canonical name:** PidTagMessageLocaleId

**Description:** Contains the Windows Locale ID of the end-user who created this message.

**Property ID:** 0x3FF1

**Data type:** **PtypInteger32**, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_LOCALE\_ID

## 2.783 PidTagMessageRecipientMe

**Canonical name:** PidTagMessageRecipientMe

**Description:** Indicates that the receiving mailbox owner is a primary or a carbon copy (Cc) recipient of this e-mail message.

**Property ID:** 0x0059

**Data type:** **PtypBoolean**, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.19

**Consuming Reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIP\_ME, ptagMessageRecipMe

## 2.784 PidTagMessageRecipients

**Canonical name:** PidTagMessageRecipients

**Description:** Identifies all of the recipients (1) of the current message.

**Property ID:** 0x0E12

**Data type:** PtypObject, 0x000D

**Area:** Address Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.47

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIPIENTS, ptagMessageRecipients

## 2.785 PidTagMessageSize

**Canonical name:** PidTagMessageSize

**Description:** Contains the size, in bytes, consumed by the Message object on the server.

**Property ID:** 0x0E08

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.8

**Consuming references:** [\[MS-OXCSTOR\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE, ptagMessageSize

## 2.786 PidTagMessageSizeExtended

**Canonical name:** PidTagMessageSizeExtended

**Description:** Specifies the 64-bit version of the **PidTagMessageSize** property (section [2.785](#)).

**Property ID:** 0x0E08

**Data type:** PtypInteger64, 0x0014

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.9

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE\_EXTENDED, ptagMessageSizeExtended

## 2.787 PidTagMessageStatus

**Canonical name:** PidTagMessageStatus

**Description:** Specifies the status of a message in a **contents table**.

**Property ID:** 0x0E17

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_MSG\_STATUS, ptagMsgStatus

## 2.788 PidTagMessageSubmissionId

**Canonical name:** PidTagMessageSubmissionId

**Description:** Contains a message identifier assigned by a message transfer agent.

**Property ID:** 0x0047

**Data type:** PtypBinary, 0x0102

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.79

**Consuming references:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_SUBMISSION\_ID, ptagMessageSubmissionId

## 2.789 PidTagMessageToMe

**Canonical name:** PidTagMessageToMe

**Description:** Indicates that the receiving mailbox owner is one of the primary recipients of this e-mail message.

**Property ID:** 0x0057

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.17

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_TO\_ME, ptagMessageToMe

## 2.790 PidTagMid

**Canonical name:** PidTagMid

**Description:** Contains a value that contains the MID of the message currently being synchronized.

**Property ID:** 0x674A

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.1

**Consuming references:** [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** ptagMID, <http://schemas.microsoft.com/exchange/mid>

## 2.791 PidTagMiddleName

**Canonical name:** PidTagMiddleName

**Description:** Specifies the middle name(s) of the contact.

**Property ID:** 0x3A44

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MIDDLE\_NAME, PR\_MIDDLE\_NAME\_A, PR\_MIDDLE\_NAME\_W, urn:schemas:contacts:middlename

## 2.792 PidTagMimeSkeleton

**Canonical name:** PidTagMimeSkeleton

**Description:** Contains the top-level MIME message headers, all MIME message body part headers, and body part content that is not already converted to Message object properties, including attachments.

**Property ID:** 0x64F0

**Data type:** PtypBinary, 0x0102

**Area:** MIME properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.28

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagMimeSkeleton

## 2.793 PidTagMobileTelephoneNumber

**Canonical name:** PidTagMobileTelephoneNumber

**Description:** Contains the mail user's cellular telephone number.

**Property ID:** 0x3A1C

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-EXOABK\]](#) section 2.2.4.27

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MOBILE\_TELEPHONE\_NUMBER, PR\_MOBILE\_TELEPHONE\_NUMBER\_A, PR\_MOBILE\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:mobile

## 2.794 PidTagNativeBody

**Canonical name:** PidTagNativeBody

**Description:** Indicates the best available format for storing the message body (2).

**Property ID:** 0x1016

**Data type:** PtypInteger32, 0x0003

**Area:** BestBody

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.2

**Consuming Reference:** [\[MS-OXBBODY\]](#)

**Alternate names:** PR\_NATIVE\_BODY\_INFO, ptagNativeBodyInfo

## 2.795 PidTagNextSendAcct

**Canonical name:** PidTagNextSendAcct

**Description:** Specifies the server that a client is currently attempting to use to send e-mail.

**Property ID:** 0x0E29

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.65

**Consuming Reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_NEXT\_SEND\_ACCT

## 2.796 PidTagNickname

**Canonical name:** PidTagNickname

**Description:** Contains the mail user's nickname.

**Property ID:** 0x3A4F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.1

**Consuming references:** [\[MS-OXOMSG\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_NICKNAME, PR\_NICKNAME\_A, PR\_NICKNAME\_W,  
urn:schemas:contacts:nickname

## 2.797 PidTagNonDeliveryReportDiagCode

**Canonical name:** PidTagNonDeliveryReportDiagCode

**Description:** Contains the diagnostic code for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C05

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.30

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_DIAG\_CODE, ptagNonDeliveryDiagCode

## 2.798 PidTagNonDeliveryReportReasonCode

**Canonical name:** PidTagNonDeliveryReportReasonCode

**Description:** Contains an integer value that indicates a reason for delivery failure.

**Property ID:** 0x0C04

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.31

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_REASON\_CODE, ptagNDRReasonCode

## 2.799 PidTagNonDeliveryReportStatusCode

**Canonical name:** PidTagNonDeliveryReportStatusCode

**Description:** Contains the value of the Status field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C20

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.32

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_STATUS\_CODE, ptagNDRStatusCode



## 2.800 PidTagNonReceiptNotificationRequested

**Canonical Name:** PidTagNonReceiptNotificationRequested

**Description:** Specifies whether the client sends a non-read receipt.

**Property ID:** 0x0C06

**Data type:** PtypBoolean, 0x000B

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.31

**Alternate names:** PR\_NON\_RECEIPT\_NOTIFICATION\_REQUESTED

## 2.801 PidTagNormalizedSubject

**Canonical name:** PidTagNormalizedSubject

**Description:** Contains the normalized subject of the message.

**Property ID:** 0x0E1D

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_NORMALIZED\_SUBJECT, PR\_NORMALIZED\_SUBJECT\_A, ptagNormalizedSubject, PR\_NORMALIZED\_SUBJECT\_W, urn:schemas:httpmail:normalizedsubject

## 2.802 PidTagObjectType

**Canonical name:** PidTagObjectType

**Description:** Indicates the type of **Server object**.

**Property ID:** 0x0FFE

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_OBJECT\_TYPE, ptagObjectType

## 2.803 PidTagOfficeLocation

**Canonical name:** PidTagOfficeLocation

**Description:** Contains the mail user's office location.

**Property ID:** 0x3A19

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.5

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_OFFICE\_LOCATION, PR\_OFFICE\_LOCATION\_A, PR\_OFFICE\_LOCATION\_W, urn:schemas:contacts:roomnumber

## 2.804 PidTagOfflineAddressBookContainerGuid

**Canonical name:** PidTagOfflineAddressBookContainerGuid

**Description:** A string formatted GUID that represents the **address list** container object.

**Property ID:** 0x6802

**Data type:** PtypString8, 0x001E

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.1

**Alternate names:** PR\_OAB\_CONTAINER\_GUID, PR\_OAB\_CONTAINER\_GUID\_W

## 2.805 PidTagOfflineAddressBookDistinguishedName

**Canonical name:** PidTagOfflineAddressBookDistinguishedName

**Description:** Contains the distinguished name (DN) (1) of the address list that is contained in the OAB message.

**Property ID:** 0x6804

**Data type:** PtypString8, 0x001E

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.2

**Alternate names:** PR\_OAB\_DN, PR\_OAB\_DN\_W

## 2.806 PidTagOfflineAddressBookMessageClass

**Canonical name:** PidTagOfflineAddressBookMessageClass

**Description:** Contains the message class for full OAB messages.

**Property ID:** 0x6803

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXPFOAB\]](#) section 2.2.2.1.1

**Alternate names:** PR\_OAB\_MESSAGE\_CLASS

## 2.807 PidTagOfflineAddressBookName

**Canonical name:** PidTagOfflineAddressBookName

**Description:** Contains the display name of the address list.

**Property ID:** 0x6800

**Data type:** PtypString, 0x001F

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.3

**Alternate names:** PR\_OAB\_NAME, PR\_OAB\_NAME\_W

## 2.808 PidTagOfflineAddressBookSequence

**Canonical name:** PidTagOfflineAddressBookSequence

**Description:** Contains the sequence number of the OAB.

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.4

**Alternate names:** PR\_OAB\_SEQUENCE

## 2.809 PidTagOfflineAddressBookTruncatedProperties

**Canonical name:** PidTagOfflineAddressBookTruncatedProperties

**Description:** Contains a list of the property tags that have been truncated or limited by the server.

**Property ID:** 0x6805

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.9.2.2

**Alternate names:** PR\_OAB\_TRUNCATED\_PROPS

## 2.810 PidTagOrdinalMost

**Canonical name:** PidTagOrdinalMost

**Description:** Contains a positive number whose negative is less than or equal to the value of the **PidLidTaskOrdinal** property (section [2.327](#)) of all of the Task objects in the folder.

**Property ID:** 0x36E2

**Data type:** **PtypInteger32**, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.1.1

**Alternate names:** PR\_ORDINAL\_MOST

## 2.811 PidTagOrganizationalIdNumber

**Canonical name:** PidTagOrganizationalIdNumber

**Description:** Contains an identifier for the mail user used within the mail user's organization.

**Property ID:** 0x3A10

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.7

**Alternate names:** PR\_ORGANIZATIONAL\_ID\_NUMBER, PR\_ORGANIZATIONAL\_ID\_NUMBER\_A, PR\_ORGANIZATIONAL\_ID\_NUMBER\_W, urn:schemas:contacts:employeenumber

## 2.812 PidTagOriginalAuthorEntryId

**Canonical name:** PidTagOriginalAuthorEntryId

**Description:** Contains an address book EntryID structure ([\[MS-OXCDATA\]](#) section 2.2.5.2) and is defined in report messages to identify the user who sent the original message.

**Property ID:** 0x004C

**Data type:** **PtypBinary**, 0x0102

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.32

**Alternate names:** PR\_ORIGINAL\_AUTHOR\_ENTRYID

## 2.813 PidTagOriginalAuthorName

**Canonical name:** PidTagOriginalAuthorName

**Description:** Contains the display name of the sender of the original message referenced by a report message.

**Property ID:** 0x004D

**Data type:** **PtypString**, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.33

**Alternate names:** PR\_ORIGINAL\_AUTHOR\_NAME\_W

## 2.814 PidTagOriginalDeliveryTime

**Canonical name:** PidTagOriginalDeliveryTime

**Description:** Contains the delivery time, in UTC, from the original message.

**Property ID:** 0x0055

**Data type:** **PtypTime**, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.2

**Alternate names:** PR\_ORIGINAL\_DELIVERY\_TIME, ptagOriginalDeliveryTime

## 2.815 PidTagOriginalDisplayBcc

**Canonical name:** PidTagOriginalDisplayBcc

**Description:** Contains the value of the **PidTagDisplayBcc** property (section [2.665](#)) from the original message.

**Property ID:** 0x0072

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.5

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_BCC, PR\_ORIGINAL\_DISPLAY\_BCC\_A, ptagOriginalDisplayBcc, PR\_ORIGINAL\_DISPLAY\_BCC\_W, <http://schemas.microsoft.com/exchange/originaldisplaybcc>

## 2.816 PidTagOriginalDisplayCc

**Canonical name:** PidTagOriginalDisplayCc

**Description:** Contains the value of the **PidTagDisplayCc** property (section [2.666](#)) from the original message.

**Property ID:** 0x0073

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.4

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_CC, PR\_ORIGINAL\_DISPLAY\_CC\_A, ptagOriginalDisplayCc, PR\_ORIGINAL\_DISPLAY\_CC\_W, <http://schemas.microsoft.com/exchange/originaldisplaycc>, [http://schemas.microsoft.com/mapi/original\\_display\\_cc](http://schemas.microsoft.com/mapi/original_display_cc)

## 2.817 PidTagOriginalDisplayTo

**Canonical name:** PidTagOriginalDisplayTo

**Description:** Contains the value of the **PidTagDisplayTo** property (section [2.669](#)) from the original message.

**Property ID:** 0x0074

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.3

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_TO, PR\_ORIGINAL\_DISPLAY\_TO\_A, ptagOriginalDisplayTo, PR\_ORIGINAL\_DISPLAY\_TO\_W, <http://schemas.microsoft.com/exchange/originaldisplayto>, [http://schemas.microsoft.com/mapi/original\\_display\\_to](http://schemas.microsoft.com/mapi/original_display_to)

## 2.818 PidTagOriginalEntryId

**Canonical name:** PidTagOriginalEntryId

**Description:** Contains the original EntryID of an object.

**Property ID:** 0x3A12

**Data type:** **PtypBinary**, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.9

**Alternate names:** PR\_ORIGINAL\_ENTRYID, ptagOriginalEntryId

## 2.819 PidTagOriginalMessageClass

**Canonical name:** PidTagOriginalMessageClass

**Description:** Designates the **PidTagMessageClass** property ([\[MS-OXCMSG\]](#) section 2.2.1.3) from the original message.

**Property ID:** 0x004B

**Data type:** **PtypString**, 0x001F

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.86

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIG\_MESSAGE\_CLASS, PR\_ORIG\_MESSAGE\_CLASS\_A, PR\_ORIG\_MESSAGE\_CLASS\_W

## 2.820 PidTagOriginalMessageId

**Canonical name:** PidTagOriginalMessageId

**Description:** Contains the message ID of the original message included in replies or resent messages.

**Property ID:** 0x1046

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.85

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagOriginalInternetMessageID, OriginalMessageId

## 2.821 PidTagOriginalSenderAddressType

**Canonical name:** PidTagOriginalSenderAddressType

**Description:** Contains the value of the original message sender's **PidTagSenderAddressType** property (section [2.989](#)).

**Property ID:** 0x0066

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.6

**Alternate names:** PR\_ORIGINAL\_SENDER\_ADDRTYPE, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_A, ptagOriginalSenderAddrType, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_W

## 2.822 PidTagOriginalSenderEmailAddress

**Canonical name:** PidTagOriginalSenderEmailAddress

**Description:** Contains the value of the original message sender's **PidTagSenderEmailAddress** property (section [2.990](#)).

**Property ID:** 0x0067

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.7

**Alternate names:** PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_W

### 2.823 PidTagOriginalSenderId

**Canonical name:** PidTagOriginalSenderId

**Description:** Contains an address book EntryID that is set on delivery report messages.

**Property ID:** 0x005B

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.8

**Alternate names:** PR\_ORIGINAL\_SENDER\_ENTRYID, ptagOriginalSenderId

### 2.824 PidTagOriginalSenderName

**Canonical name:** PidTagOriginalSenderName

**Description:** Contains the value of the original message sender's **PidTagSenderName** property (section [2.993](#)), and is set on delivery report messages.

**Property ID:** 0x005A

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.9

**Alternate names:** PR\_ORIGINAL\_SENDER\_NAME, PR\_ORIGINAL\_SENDER\_NAME\_A, ptagOriginalSenderName, PR\_ORIGINAL\_SENDER\_NAME\_W, <http://schemas.microsoft.com/exchange/originalsendername>

### 2.825 PidTagOriginalSenderSearchKey

**Canonical name:** PidTagOriginalSenderSearchKey

**Description:** Contains an address book search key set on the original e-mail message.

**Property ID:** 0x005C

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.10

**Alternate names:** PR\_ORIGINAL\_SENDER\_SEARCH\_KEY, ptagOriginalSenderSearchKey

### 2.826 PidTagOriginalSensitivity

**Canonical name:** PidTagOriginalSensitivity



**Description:** Contains the sensitivity value of the original e-mail message.

**Property ID:** 0x002E

**Data type:** **PtypInteger32**, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.22

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_ORIGINAL\_SENSITIVITY, ptagOriginalSensitivity

## 2.827 PidTagOriginalSentRepresentingAddressType

**Canonical name:** PidTagOriginalSentRepresentingAddressType

**Description:** Contains the address type of the end user who is represented by the original e-mail message sender.

**Property ID:** 0x0068

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.11

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_A, ptagOriginalSentRepresentingAddrType, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_W

## 2.828 PidTagOriginalSentRepresentingEmailAddress

**Canonical name:** PidTagOriginalSentRepresentingEmailAddress

**Description:** Contains the e-mail address of the end user who is represented by the original e-mail message sender.

**Property ID:** 0x0069

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.12

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.829 PidTagOriginalSentRepresentingEntryId

**Canonical name:** PidTagOriginalSentRepresentingEntryId

**Description:** Identifies an address book EntryID that contains the entry identifier of the end user who is represented by the original message sender.

**Property ID:** 0x005E

**Data type:** **PtypBinary**, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.13

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ENTRYID,  
ptagOriginalSentRepresentingEntryId

## 2.830 PidTagOriginalSentRepresentingName

**Canonical name:** PidTagOriginalSentRepresentingName

**Description:** Contains the display name of the end user who is represented by the original e-mail message sender.

**Property ID:** 0x005D

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.14

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME,  
PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_A, ptagOriginalSentRepresentingName,  
PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_W

## 2.831 PidTagOriginalSentRepresentingSearchKey

**Canonical name:** PidTagOriginalSentRepresentingSearchKey

**Description:** Identifies an address book search key that contains the SearchKey of the end user who is represented by the original message sender.

**Property ID:** 0x005F

**Data type:** **PtypBinary**, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.15

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_SEARCH\_KEY,  
ptagOriginalSentRepresentingSearchKey

## 2.832 PidTagOriginalSubject

**Canonical name:** PidTagOriginalSubject

**Description:** Specifies the subject of the original message.

**Property ID:** 0x0049

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.16

**Alternate names:** PR\_ORIGINAL\_SUBJECT, PR\_ORIGINAL\_SUBJECT\_A, ptagOriginalSubject, PR\_ORIGINAL\_SUBJECT\_W, <http://schemas.microsoft.com/exchange/originalsubject>, [http://schemas.microsoft.com/mapi/original\\_subject](http://schemas.microsoft.com/mapi/original_subject)

### 2.833 PidTagOriginalSubmitTime

**Canonical name:** PidTagOriginalSubmitTime

**Description:** Specifies the original e-mail message's submission date and time, in UTC.

**Property ID:** 0x004E

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.17

**Alternate names:** PR\_ORIGINAL\_SUBMIT\_TIME, ptagOriginalSubmitTime, <http://schemas.microsoft.com/exchange/originaldate>, [http://schemas.microsoft.com/mapi/original\\_submit\\_time](http://schemas.microsoft.com/mapi/original_submit_time)

### 2.834 PidTagOriginatorDeliveryReportRequested

**Canonical name:** PidTagOriginatorDeliveryReportRequested

**Description:** Indicates whether an e-mail sender requests an e-mail **delivery receipt** from the messaging system.

**Property ID:** 0x0023

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIGINATOR\_DELIVERY\_REPORT\_REQUESTED, <http://schemas.microsoft.com/exchange/deliveryreportrequested>

### 2.835 PidTagOriginatorNonDeliveryReportRequested

**Canonical name:** PidTagOriginatorNonDeliveryReportRequested

**Description:** Specifies whether an e-mail sender requests suppression of nondelivery receipts.

**Property ID:** 0x0C08

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.21

**Alternate names:** PR\_ORIGINATOR\_NON\_DELIVERY\_REPORT\_REQUESTED

## 2.836 PidTagOscSyncEnabled

**Canonical name:** PidTagOscSyncEnabled

**Description:** Specifies whether contact synchronization with an external source is handled by the server.

**Property ID:** 0x7C24

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.7

**Alternate names:** PR\_OSC\_SYNC\_ENABLEDONSERVER

## 2.837 PidTagOtherAddressCity

**Canonical name:** PidTagOtherAddressCity

**Description:** Contains the name of the mail user's other locality, such as the town or city.

**Property ID:** 0x3A5F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_CITY, PR\_OTHER\_ADDRESS\_CITY\_A, PR\_OTHER\_ADDRESS\_CITY\_W, urn:schemas:contacts:othercity

## 2.838 PidTagOtherAddressCountry

**Canonical name:** PidTagOtherAddressCountry

**Description:** Contains the name of the mail user's other country/region.

**Property ID:** 0x3A60

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_COUNTRY, PR\_OTHER\_ADDRESS\_COUNTRY\_A, PR\_OTHER\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:othercountry

## 2.839 PidTagOtherAddressPostalCode

**Canonical name:** PidTagOtherAddressPostalCode

**Description:** Contains the postal code for the mail user's other postal address.

**Property ID:** 0x3A61

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_POSTAL\_CODE, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_A, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:otherpostalcode

## 2.840 PidTagOtherAddressPostOfficeBox

**Canonical name:** PidTagOtherAddressPostOfficeBox

**Description:** Contains the number or identifier of the mail user's other post office box.

**Property ID:** 0x3A64

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:otherpostofficebox

## 2.841 PidTagOtherAddressStateOrProvince

**Canonical name:** PidTagOtherAddressStateOrProvince

**Description:** Contains the name of the mail user's other state or province.

**Property ID:** 0x3A62

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:otherstate

## 2.842 PidTagOtherAddressStreet

**Canonical name:** PidTagOtherAddressStreet

**Description:** Contains the mail user's other street address.

**Property ID:** 0x3A63

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STREET, PR\_OTHER\_ADDRESS\_STREET\_A, PR\_OTHER\_ADDRESS\_STREET\_W, urn:schemas:contacts:otherstreet

## 2.843 PidTagOtherTelephoneNumber

**Canonical name:** PidTagOtherTelephoneNumber

**Description:** Contains an alternate telephone number for the mail user.

**Property ID:** 0x3A1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.10

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_TELEPHONE\_NUMBER, PR\_OTHER\_TELEPHONE\_NUMBER\_A, PR\_OTHER\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:otherTelephone

## 2.844 PidTagOutOfOfficeState

**Canonical name:** PidTagOutOfOfficeState

**Description:** Indicates whether the user is **OOF**.

**Property ID:** 0x661D

**Data type:** PtypBoolean, 0x000B

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.2.4

**Alternate names:** PR\_OOF\_STATE, ptagOOFState

## 2.845 PidTagOwnerAppointmentId

**Canonical name:** PidTagOwnerAppointmentId

**Description:** Specifies a quasi-unique value among all of the Calendar objects in a user's mailbox.

**Property ID:** 0x0062

**Data type:** **PtypInteger32**, 0x0003

**Area:** Appointment

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.29

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_OWNER\_APPT\_ID, [http://schemas.microsoft.com/mapi/owner\\_appt\\_id](http://schemas.microsoft.com/mapi/owner_appt_id)

## 2.846 PidTagPagerTelephoneNumber

**Canonical name:** PidTagPagerTelephoneNumber

**Description:** Contains the mail user's pager telephone number.

**Property ID:** 0x3A21

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.28

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PAGER\_TELEPHONE\_NUMBER, PR\_PAGER\_TELEPHONE\_NUMBER\_A, PR\_PAGER\_TELEPHONE\_NUMBER\_W, <urn:schemas:contacts:pager>

## 2.847 PidTagParentEntryId

**Canonical name:** PidTagParentEntryId

**Description:** Contains the EntryID of the folder where messages reside.

**Property ID:** 0x0E09

**Data type:** **PtypBinary**, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.6

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_PARENT\_ENTRYID, ptagParentEntryId

## 2.848 PidTagParentFolderId

**Canonical name:** PidTagParentFolderId

**Description:** Contains a value that contains the Folder ID (FID), as specified in [\[MS-OXCDATA\]](#) section 2.2.1.1, that identifies the parent folder of the messaging object being synchronized.

**Property ID:** 0x6749

**Data type:** **PtypInteger64**, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.4

**Alternate names:** ptagParentFID

## 2.849 PidTagParentKey

**Canonical name:** PidTagParentKey

**Description:** Contains the search key that is used to correlate the original message and the reports about the original message.

**Property ID:** 0x0025

**Data type:** **PtypBinary**, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.18

**Alternate names:** PR\_PARENT\_KEY, ptagParentKey

## 2.850 PidTagParentSourceKey

**Canonical name:** PidTagParentSourceKey

**Description:** Contains a value on a folder that contains the **PidTagSourceKey** property (section [2.1010](#)) of the parent folder.

**Property ID:** 0x65E1

**Data type:** **PtypBinary**, 0x0102

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.6

**Alternate names:** PR\_PARENT\_SOURCE\_KEY

## 2.851 PidTagPersonalHomePage

**Canonical name:** PidTagPersonalHomePage

**Description:** Contains the URL of the mail user's personal home page.

**Property ID:** 0x3A50

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.13



**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PERSONAL\_HOME\_PAGE, PR\_PERSONAL\_HOME\_PAGE\_A, PR\_PERSONAL\_HOME\_PAGE\_W, urn:schemas:contacts:personalHomePage

## 2.852 PidTagPolicyTag

**Canonical name:** PidTagPolicyTag

**Description:** Specifies the GUID of a **retention tag**.

**Property ID:** 0x3019

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.58.2

**Alternate names:** PR\_POLICY\_TAG, ptagPolicyTag

## 2.853 PidTagPostalAddress

**Canonical name:** PidTagPostalAddress

**Description:** Contains the mail user's postal address.

**Property ID:** 0x3A15

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** PR\_POSTAL\_ADDRESS, PR\_POSTAL\_ADDRESS\_A, PR\_POSTAL\_ADDRESS\_W, urn:schemas:contacts:mailingpostaladdress

## 2.854 PidTagPostalCode

**Canonical name:** PidTagPostalCode

**Description:** Contains the postal code for the mail user's postal address.

**Property ID:** 0x3A2A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.18

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_POSTAL\_CODE, PR\_POSTAL\_CODE\_A, PR\_POSTAL\_CODE\_W, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_A, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:mailingpostalcode

## 2.855 PidTagPostOfficeBox

**Canonical name:** PidTagPostOfficeBox

**Description:** Contains the number or identifier of the mail user's post office box.

**Property ID:** 0x3A2B

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.15

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_POST\_OFFICE\_BOX, PR\_POST\_OFFICE\_BOX\_A, PR\_POST\_OFFICE\_BOX\_W, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:mailingpostofficebox

## 2.856 PidTagPredecessorChangeList

**Canonical name:** PidTagPredecessorChangeList

**Description:** Contains a value that contains a serialized representation of a **PredecessorChangeList** structure.

**Property ID:** 0x65E3

**Data type:** **PtypBinary**, 0x0102

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.8

**Alternate names:** PR\_PREDECESSOR\_CHANGE\_LIST

## 2.857 PidTagPrimaryFaxNumber

**Canonical name:** PidTagPrimaryFaxNumber

**Description:** Contains the telephone number of the mail user's primary fax machine.

**Property ID:** 0x3A23

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.29

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_PRIMARY\_FAX\_NUMBER, PR\_PRIMARY\_FAX\_NUMBER\_A, PR\_PRIMARY\_FAX\_NUMBER\_W, urn:schemas:contacts:otherfax

## 2.858 PidTagPrimarySendAccount

**Canonical name:** PidTagPrimarySendAccount

**Description:** Specifies the first server that a client is to use to send the e-mail with.

**Property ID:** 0x0E28

**Data type:** **PtypString**, 0x001F

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.64

**Alternate names:** PR\_PRIMARY\_SEND\_ACCT

## 2.859 PidTagPrimaryTelephoneNumber

**Canonical name:** PidTagPrimaryTelephoneNumber

**Description:** Contains the mail user's primary telephone number.

**Property ID:** 0x3A1A

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.5

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PRIMARY\_TELEPHONE\_NUMBER, PR\_PRIMARY\_TELEPHONE\_NUMBER\_A, PR\_PRIMARY\_TELEPHONE\_NUMBER\_W

## 2.860 PidTagPriority

**Canonical name:** PidTagPriority

**Description:** Indicates the client's request for the priority with which the message is to be sent by the messaging system.

**Property ID:** 0x0026

**Data type:** **PtypInteger32**, 0x0003

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOJRNL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

## 2.861 PidTagProcessed

**Canonical name:** PidTagProcessed

**Description:** Indicates whether a client has already processed a received task communication.

**Property ID:** 0x7D01

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_PROCESSED

## 2.862 PidTagProfession

**Canonical name:** PidTagProfession

**Description:** Contains the name of the mail user's line of business.

**Property ID:** 0x3A46

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PROFESSION, PR\_PROFESSION\_A, PR\_PROFESSION\_W,  
urn:schemas:contacts:profession

## 2.863 PidTagProhibitReceiveQuota

**Canonical name:** PidTagProhibitReceiveQuota

**Description:** Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before no further e-mail will be delivered to their mailbox.

**Property ID:** 0x666A

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange Administrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.3

**Alternate names:** PR\_PROHIBIT\_RECEIVE\_QUOTA, ptagProhibitReceiveQuota

## 2.864 PidTagProhibitSendQuota

**Canonical name:** PidTagProhibitSendQuota

**Description:** Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before the user can no longer send any more e-mail.

**Property ID:** 0x666E

**Data type:** **PtypInteger32**, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.4

**Alternate names:** PR\_PROHIBIT\_SEND\_QUOTA, ptagProhibitSendQuota

## 2.865 PidTagPurportedSenderDomain

**Canonical name:** PidTagPurportedSenderDomain

**Description:** Contains the **domain** responsible for transmitting the current message.

**Property ID:** 0x4083

**Data type:** **PtypString**, 0x001F

**Area:** TransportEnvelope

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_PURPORTED\_SENDER\_DOMAIN

## 2.866 PidTagRadioTelephoneNumber

**Canonical name:** PidTagRadioTelephoneNumber

**Description:** Contains the mail user's radio telephone number.

**Property ID:** 0x3A1D

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.8

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_RADIO\_TELEPHONE\_NUMBER, PR\_RADIO\_TELEPHONE\_NUMBER\_A, PR\_RADIO\_TELEPHONE\_NUMBER\_W

## 2.867 PidTagRead

**Canonical name:** PidTagRead

**Description:** Indicates whether a message has been read.

**Property ID:** 0x0E69

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable Property set

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.53

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_READ, ptagRead, urn:schemas:httpmail:read

## 2.868 PidTagReadReceiptAddressType

**Canonical name:** PidTagReadReceiptAddressType

**Description:** Contains the address type of the end user to whom a **read receipt** is directed.

**Property ID:** 0x4029

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.24

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptAddrType, ReadReceiptAddrType

## 2.869 PidTagReadReceiptEmailAddress

**Canonical name:** PidTagReadReceiptEmailAddress

**Description:** Contains the e-mail address of the end user to whom a read receipt is directed.

**Property ID:** 0x402A

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.25

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

## 2.870 PidTagReadReceiptEntryId

**Canonical name:** PidTagReadReceiptEntryId

**Description:** Contains an address book EntryID.

**Property ID:** 0x0046

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.26

**Alternate names:** PR\_READ\_RECEIPT\_ENTRYID, ptagReadReceiptEntryId

## 2.871 PidTagReadReceiptName

**Canonical name:** PidTagReadReceiptName

**Description:** Contains the display name for the end user to whom a read receipt is directed.

**Property ID:** 0x402B

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.27

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptDisplayName, ReadReceiptDisplayName

## 2.872 PidTagReadReceiptRequested

**Canonical name:** PidTagReadReceiptRequested

**Description:** Specifies whether the e-mail sender requests a read receipt from all recipients (1) when this e-mail message is read or opened.

**Property ID:** 0x0029

**Data type:** PtypBoolean, 0x000B

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.29

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** PR\_READ\_RECEIPT\_REQUESTED, ptagReadReceiptRequested, <http://schemas.microsoft.com/exchange/readreceiptrequested>

## 2.873 PidTagReadReceiptSearchKey

**Canonical name:** PidTagReadReceiptSearchKey

**Description:** Contains an address book search key.

**Property ID:** 0x0053

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.28

**Alternate names:** PR\_READ\_RECEIPT\_SEARCH\_KEY, ptagReadReceiptSearchKey

## 2.874 PidTagReadReceiptSntpAddress

**Canonical name:** PidTagReadReceiptSntpAddress

**Description:** Contains the SMTP email address of the user to whom a read receipt is directed.

**Property ID:** 0x5D05

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.30

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientReadReceiptSntpAddress

## 2.875 PidTagReceiptTime

**Canonical name:** PidTagReceiptTime

**Description:** Contains the sent time for a message disposition notification, as specified in [\[RFC3798\]](#).

**Property ID:** 0x002A

**Data type:** PtypTime, 0x0040

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.33

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_RECEIPT\_TIME, ptagReceiptTime

## 2.876 PidTagReceivedByAddressType

**Canonical name:** PidTagReceivedByAddressType

**Description:** Contains the e-mail message receiver's e-mail address type.

**Property ID:** 0x0075

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.36

**Alternate names:** PR\_RECEIVED\_BY\_ADDRTYPE, PR\_RECEIVED\_BY\_ADDRTYPE\_A, ptagReceivedByAddrType, PR\_RECEIVED\_BY\_ADDRTYPE\_W

## 2.877 PidTagReceivedByEmailAddress

**Canonical name:** PidTagReceivedByEmailAddress



**Description:** Contains the e-mail message receiver's e-mail address.

**Property ID:** 0x0076

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.37

**Alternate names:** PR\_RECEIVED\_BY\_EMAIL\_ADDRESS, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_A, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_W

## 2.878 PidTagReceivedByEntryId

**Canonical name:** PidTagReceivedByEntryId

**Description:** Contains the address book EntryID of the mailbox receiving the E-mail object.

**Property ID:** 0x003F

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.38

**Alternate names:** PR\_RECEIVED\_BY\_ENTRYID

## 2.879 PidTagReceivedByName

**Canonical name:** PidTagReceivedByName

**Description:** Contains the e-mail message receiver's display name.

**Property ID:** 0x0040

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.39

**Alternate names:** PR\_RECEIVED\_BY\_NAME, PR\_RECEIVED\_BY\_NAME\_A, PR\_RECEIVED\_BY\_NAME\_W

## 2.880 PidTagReceivedBySearchKey

**Canonical name:** PidTagReceivedBySearchKey

**Description:** Identifies an address book search key that contains a binary-comparable key that is used to identify correlated objects for a search.

**Property ID:** 0x0051

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.40

**Alternate names:** PR\_RECEIVED\_BY\_SEARCH\_KEY

## 2.881 PidTagReceivedBySmtpAddress

**Canonical name:** PidTagReceivedBySmtpAddress

**Description:** Contains the email message receiver's SMTP email address.

**Property ID:** 0x5D07

**Data type:** **PtypString**, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.41

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientRcvdBySmtpAddress

## 2.882 PidTagReceivedRepresentingAddressType

**Canonical name:** PidTagReceivedRepresentingAddressType

**Description:** Contains the e-mail address type for the end user represented by the receiving mailbox owner.

**Property ID:** 0x0077

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.23

**Alternate names:** PR\_RCVD\_REPRESENTING\_ADDRTYPE,  
PR\_RCVD\_REPRESENTING\_ADDRTYPE\_A, ptagRcvdRepresentingAddrType,  
PR\_RCVD\_REPRESENTING\_ADDRTYPE\_W

## 2.883 PidTagReceivedRepresentingEmailAddress

**Canonical name:** PidTagReceivedRepresentingEmailAddress

**Description:** Contains the e-mail address for the end user represented by the receiving mailbox owner.

**Property ID:** 0x0078

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.24

**Alternate names:** PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS,  
PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.884 PidTagReceivedRepresentingEntryId

**Canonical name:** PidTagReceivedRepresentingEntryId

**Description:** Contains an address book EntryID that identifies the end user represented by the receiving mailbox owner.

**Property ID:** 0x0043

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.25

**Alternate names:** PR\_RCVD\_REPRESENTING\_ENTRYID, ptagRcvdRepresentingEntryId

## 2.885 PidTagReceivedRepresentingName

**Canonical name:** PidTagReceivedRepresentingName

**Description:** Contains the display name for the end user represented by the receiving mailbox owner.

**Property ID:** 0x0044

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.26

**Alternate names:** PR\_RCVD\_REPRESENTING\_NAME, PR\_RCVD\_REPRESENTING\_NAME\_A, ptagRcvdRepresentingName, PR\_RCVD\_REPRESENTING\_NAME\_W

## 2.886 PidTagReceivedRepresentingSearchKey

**Canonical name:** PidTagReceivedRepresentingSearchKey

**Description:** Identifies an address book search key that contains a binary-comparable key of the end user represented by the receiving mailbox owner.

**Property ID:** 0x0052

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.27

**Alternate names:** PR\_RCVD\_REPRESENTING\_SEARCH\_KEY, ptagRcvdRepresentingSearchKey

## 2.887 PidTagReceivedRepresentingSmtpAddress

**Canonical name:** PidTagReceivedRepresentingSmtpAddress

**Description:** Contains the SMTP email address of the user represented by the receiving mailbox owner.

**Property ID:** 0x5D08

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.28

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientRcvdRepresentingSmtptAddress

## 2.888 PidTagRecipientDisplayName

**Canonical name:** PidTagRecipientDisplayName

**Description:** Specifies the display name of the recipient.

**Property ID:** 0x5FF6

**Data type:** PtypString, 0x001F

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.54

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_DISPLAY\_NAME, PR\_RECIPIENT\_DISPLAY\_NAME\_W

## 2.889 PidTagRecipientEntryId

**Canonical name:** PidTagRecipientEntryId

**Description:** Identifies an Address Book object that specifies the recipient (2).

**Property ID:** 0x5FF7

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.55

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ENTRYID, ptagRecipientEntryId

## 2.890 PidTagRecipientFlags

**Canonical name:** PidTagRecipientFlags

**Description:** Specifies a bit field that describes the recipient (1) status.

**Property ID:** 0x5FFD

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_FLAGS

## 2.891 PidTagRecipientOrder

**Canonical name:** PidTagRecipientOrder

**Description:** Specifies the location of the current recipient (1) in the **recipient table**.

**Property ID:** 0x5FDF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.40

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ORDER, ptagRecipientOrder

## 2.892 PidTagRecipientProposed

**Canonical name:** PidTagRecipientProposed

**Description:** Indicates that the attendee proposed a new date and/or time.

**Property ID:** 0x5FE1

**Data type:** PtypBoolean, 0x000B

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.4

**Alternate names:** PR\_RECIPIENT\_PROPOSED, ptagRecipientProposed

## 2.893 PidTagRecipientProposedEndTime

**Canonical name:** PidTagRecipientProposedEndTime

**Description:** Indicates the meeting end time requested by the attendee in a counter proposal.

**Property ID:** 0x5FE4

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.6

**Alternate names:** PR\_RECIPIENT\_PROPOSEDENDTIME, ptagRecipientProposedEndTime

## 2.894 PidTagRecipientProposedStartTime

**Canonical name:** PidTagRecipientProposedStartTime

**Description:** Indicates the meeting start time requested by the attendee in a counter proposal.

**Property ID:** 0x5FE3

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.5

**Alternate names:** PR\_RECIPIENT\_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

## 2.895 PidTagRecipientReassignmentProhibited

**Canonical name:** PidTagRecipientReassignmentProhibited

**Description:** Specifies whether adding additional or different recipients (1) is prohibited for the e-mail message when forwarding the e-mail message.

**Property ID:** 0x002B

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.42

**Alternate names:** PR\_RECIPIENT\_REASSIGNMENT\_PROHIBITED, ptagRecipientReassignmentProhibited

## 2.896 PidTagRecipientTrackStatus

**Canonical name:** PidTagRecipientTrackStatus

**Description:** Indicates the response status that is returned by the attendee.

**Property ID:** 0x5FFF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS, ptagRecipientTrackStatus

## 2.897 PidTagRecipientTrackStatusTime

**Canonical name:** PidTagRecipientTrackStatusTime

**Description:** Indicates the date and time at which the attendee responded.

**Property ID:** 0x5FFB

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.3

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS\_TIME, ptagRecipientTrackStatusTime

## 2.898 PidTagRecipientType

**Canonical name:** PidTagRecipientType

**Description:** Represents the recipient (1) type of a recipient (1) on the message.

**Property ID:** 0x0C15

**Data type:** PtypInteger32, 0x0003

**Area:** MapiRecipient

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_TYPE, ptagRecipientType

## 2.899 PidTagRecordKey

**Canonical name:** PidTagRecordKey

**Description:** Contains a unique binary-comparable identifier for a specific object.

**Property ID:** 0x0FF9

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_RECORD\_KEY, ptagRecordKey

## 2.900 PidTagReferredByName

**Canonical name:** PidTagReferredByName

**Description:** Contains the name of the mail user's referral.

**Property ID:** 0x3A47

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.21

**Alternate names:** PR\_REferred\_BY\_NAME, PR\_REferred\_BY\_NAME\_A, PR\_REferred\_BY\_NAME\_W

## 2.901 PidTagRemindersOnlineEntryId

**Canonical name:** PidTagRemindersOnlineEntryId

**Description:** Contains an EntryID for the Reminders folder.

**Property ID:** 0x36D5

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Alternate names:** PR\_REM\_ONLINE\_ENTRYID, ptagRemOnlineEntryId

## 2.902 PidTagRemoteMessageTransferAgent

**Canonical name:** PidTagRemoteMessageTransferAgent

**Description:** Contains the value of the Remote-MTA field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C21

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.34

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_DSN\_REMOTE\_MTA, ptagDsnRemoteMta

## 2.903 PidTagRenderingPosition

**Canonical name:** PidTagRenderingPosition

**Description:** Represents an offset, in rendered characters, to use when rendering an attachment within the main message text.

**Property ID:** 0x370B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAttachment

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.16



**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_RENDERING\_POSITION, ptagRenderingPosition

## 2.904 PidTagReplyRecipientEntries

**Canonical name:** PidTagReplyRecipientEntries

**Description:** Identifies a **FlatEntryList** structure ([\[MS-OXCDATA\]](#) section 2.3.3) of address book EntryIDs for recipients (1) that are to receive a reply.

**Property ID:** 0x004F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_ENTRIES, ptagReplyRecipientEntries, <http://schemas.microsoft.com/exchange/reply-to-base64>

## 2.905 PidTagReplyRecipientNames

**Canonical name:** PidTagReplyRecipientNames

**Description:** Contains a list of display names for recipients (1) that are to receive a reply.

**Property ID:** 0x0050

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.44

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_NAMES, PR\_REPLY\_RECIPIENT\_NAMES\_A, ptagReplyRecipientNames, PR\_REPLY\_RECIPIENT\_NAMES\_W

## 2.906 PidTagReplyRequested

**Canonical name:** PidTagReplyRequested

**Description:** Indicates whether a reply is requested to a Message object.

**Property ID:** 0x0C17

**Data type:** PtypBoolean, 0x000B

**Area:** MapiRecipient

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.45

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_REQUESTED, ptagReplyRequested

## 2.907 PidTagReplyTemplateId

**Canonical name:** PidTagReplyTemplateId

**Description:** Contains the value of the GUID that points to a Reply template.

**Property ID:** 0x65C2

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.2

**Alternate names:** PR\_REPLY\_TEMPLATE\_ID, ptagReplyTemplateId

## 2.908 PidTagReplyTime

**Canonical name:** PidTagReplyTime

**Description:** Specifies the time, in UTC, that the sender has designated for an associated work item to be due.

**Property ID:** 0x0030

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.3.1

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_TIME, urn:schemas:httpmail:reply-by, <http://schemas.microsoft.com/exchange/reply-by-iso>

## 2.909 PidTagReportDisposition

**Canonical name:** PidTagReportDisposition

**Description:** Contains a string indicating whether the original message was displayed to the user or deleted (report messages only).

**Property ID:** 0x0080

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.34

**Alternate names:** PR\_REPORT\_DISPOSITION\_W

## 2.910 PidTagReportDispositionMode

**Canonical name:** PidTagReportDispositionMode

**Description:** Contains a description of the action that a client has performed on behalf of a user (report messages only).

**Property ID:** 0x0081

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.35

**Alternate names:** PR\_REPORT\_DISPOSITION\_MODE\_W

## 2.911 PidTagReportEntryId

**Canonical name:** PidTagReportEntryId

**Description:** Specifies whether a reply to the e-mail message is requested by the e-mail message's sender.

**Property ID:** 0x0045

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.45

**Alternate names:** PR\_REPORT\_ENTRYID, ptagReportEntryId

## 2.912 PidTagReportingMessageTransferAgent

**Canonical name:** PidTagReportingMessageTransferAgent

**Description:** Contains the value of the Reporting-MTA field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x6820

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.35

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagDsnReportingMta

## 2.913 PidTagReportName

**Canonical name:** PidTagReportName

**Description:** Contains the display name for the entity (usually a server agent) that generated the report message.

**Property ID:** 0x003A

**Data type:** **PtypString**, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.20

**Alternate names:** PR\_REPORT\_NAME, PR\_REPORT\_NAME\_A, PR\_REPORT\_NAME\_W

## 2.914 PidTagReportSearchKey

**Canonical name:** PidTagReportSearchKey

**Description:** Contains an address book search key representing the entity (usually a server agent) that generated the report message.

**Property ID:** 0x0054

**Data type:** **PtypBinary**, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.21

**Alternate names:** PR\_REPORT\_SEARCH\_KEY, ptagReportSearchKey

## 2.915 PidTagReportTag

**Canonical name:** PidTagReportTag

**Description:** Contains the data that is used to correlate the report and the original message.

**Property ID:** 0x0031

**Data type:** **PtypBinary**, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.22

**Alternate names:** PR\_REPORT\_TAG, ptagReportTag

## 2.916 PidTagReportText

**Canonical name:** PidTagReportText

**Description:** Contains the optional text for a report message.

**Property ID:** 0x1001

**Data type:** **PtypString**, 0x001F

**Area:** MapiMessage

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.23

**Alternate names:** PR\_REPORT\_TEXT, PR\_REPORT\_TEXT\_A, ptagReportText, PR\_REPORT\_TEXT\_W

## 2.917 PidTagReportTime

**Canonical name:** PidTagReportTime

**Description:** Indicates the last time that the contact list that is controlled by the **PidTagJunkIncludeContacts** property (section [2.747](#)) was updated.

**Property ID:** 0x0032

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.6

**Alternate names:** PR\_REPORT\_TIME, ptagReportTime, <http://schemas.microsoft.com/exchange/reporttime>

## 2.918 PidTagResolveMethod

**Canonical name:** PidTagResolveMethod

**Description:** Specifies how to resolve any conflicts with the message.

**Property ID:** 0x3FE7

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.1

**Alternate names:** PR\_RESOLVE\_METHOD, ptagResolveMethod

## 2.919 PidTagResponseRequested

**Canonical name:** PidTagResponseRequested

**Description:** Indicates whether a response is requested to a Message object.

**Property ID:** 0x0063

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.46

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_RESPONSE\_REQUESTED, urn:schemas:calendar:responserequested, [http://schemas.microsoft.com/mapi/response\\_requested](http://schemas.microsoft.com/mapi/response_requested)

## 2.920 PidTagResponsibility

**Canonical name:** PidTagResponsibility

**Description:** Specifies whether another mail agent has ensured that the message will be delivered.

**Property ID:** 0x0E0F

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.37

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_RESPONSIBILITY, ptagResponsibility

## 2.921 PidTagRetentionDate

**Canonical name:** PidTagRetentionDate

**Description:** Specifies the date, in UTC, after which a Message object is expired by the server.

**Property ID:** 0x301C

**Data type:** PtypTime, 0x0040

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.5

**Alternate names:** PR\_RETENTION\_DATE, ptagRetentionDate

## 2.922 PidTagRetentionFlags

**Canonical name:** PidTagRetentionFlags

**Description:** Contains flags that specify the status or nature of an item's retention tag or archive tag.

**Property ID:** 0x301D

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.6

**Alternate names:** PR\_RETENTION\_FLAGS, ptagRetentionFlags

## 2.923 PidTagRetentionPeriod

**Canonical name:** PidTagRetentionPeriod

**Description:** Specifies the number of days that a Message object can remain unarchived.

**Property ID:** 0x301A

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.3

**Alternate names:** PR\_RETENTION\_PERIOD, ptagRetentionPeriod

## 2.924 PidTagRights

**Canonical name:** PidTagRights

**Description:** Specifies a user's folder permissions.

**Property ID:** 0x6639

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.8

**Consuming reference:** [\[MS-OXCPERM\]](#)

**Alternate names:** PR\_RIGHTS, ptagRights

## 2.925 PidTagRoamingDatatypes

**Canonical name:** PidTagRoamingDatatypes

**Description:** Contains a bitmask that indicates which stream properties exist on the message.

**Property ID:** 0x7C06

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.1

**Alternate names:** PR\_ROAMING\_DATATYPES

## 2.926 PidTagRoamingDictionary

**Canonical name:** PidTagRoamingDictionary

**Description:** Contains a dictionary stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.1.

**Property ID:** 0x7C07

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.2

**Alternate names:** PR\_ROAMING\_DICTIONARY

## 2.927 PidTagRoamingXmlStream

**Canonical name:** PidTagRoamingXmlStream

**Description:** Contains an XML stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.2.

**Property ID:** 0x7C08

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.3

**Alternate names:** PR\_ROAMING\_XMLSTREAM

## 2.928 PidTagRowid

**Canonical name:** PidTagRowid

**Description:** Contains a unique identifier for a recipient (2) in a message's recipient table.

**Property ID:** 0x3000

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.38

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_ROWID, ptagRowId

## 2.929 PidTagRowType

**Canonical name:** PidTagRowType

**Description:** Identifies the type of the row.

**Property ID:** 0x0FF5

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.3

**Alternate names:** PR\_ROW\_TYPE, ptagRowType

## 2.930 PidTagRtfCompressed

**Canonical name:** PidTagRtfCompressed

**Description:** Contains message body (2) text in compressed **RTF** format.

**Property ID:** 0x1009



**Data type:** PtypBinary, 0x0102

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.4

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFCP\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_COMPRESSED, ptagRTFCompressed

## 2.931 PidTagRtfInSync

**Canonical name:** PidTagRtfInSync

**Description:** Indicates whether the **PidTagBody** property (section [2.609](#)) and the **PidTagRtfCompressed** property (section [2.930](#)) contain the same text (ignoring formatting).

**Property ID:** 0x0E1F

**Data type:** PtypBoolean, 0x000B

**Area:** E-mail

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.5

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_RTF\_IN\_SYNC, ptagRTFInSync

## 2.932 PidTagRuleActionNumber

**Canonical name:** PidTagRuleActionNumber

**Description:** Contains the index of a rule action that failed.

**Property ID:** 0x6650

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.4

**Alternate names:** PR\_RULE\_ACTION\_NUMBER, ptagRuleActionNumber

## 2.933 PidTagRuleActions

**Canonical name:** PidTagRuleActions

**Description:** Contains the set of actions associated with the rule.

**Property ID:** 0x6680

**Data type:** PtypRuleAction, 0x00FE

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.10

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_ACTIONS, ptagRuleActions

## 2.934 PidTagRuleActionType

**Canonical name:** PidTagRuleActionType

**Description:** Contains the **ActionType** field ([\[MS-OXORULE\]](#) section 2.2.5.1) of a rule that failed.

**Property ID:** 0x6649

**Data type:** **PtypInteger32**, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.3

**Alternate names:** PR\_RULE\_ACTION\_TYPE, ptagRuleActionType

## 2.935 PidTagRuleCondition

**Canonical name:** PidTagRuleCondition

**Description:** Defines the conditions under which a rule's action is to be executed.

**Property ID:** 0x6679

**Data type:** **PtypRestriction**, 0x00FD

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.9

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_CONDITION, ptagRuleCondition

## 2.936 PidTagRuleError

**Canonical name:** PidTagRuleError

**Description:** Contains the error code that indicates the cause of an error encountered during the execution of the rule.

**Property ID:** 0x6648

**Data type:** **PtypInteger32**, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.2

**Alternate names:** PR\_RULE\_ERROR, ptagRuleError

## 2.937 PidTagRuleFolderEntryId

**Canonical name:** PidTagRuleFolderEntryId

**Description:** Contains the EntryID of the folder where the rule that triggered the generation of a DAM is stored.

**Property ID:** 0x6651

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.5

**Alternate names:** PR\_RULE\_FOLDER\_ENTRYID, ptagRuleFolderEntryId

## 2.938 PidTagRuleId

**Canonical name:** PidTagRuleId

**Description:** Specifies a unique identifier that is generated by the messaging server for each rule when the rule is first created.

**Property ID:** 0x6674

**Data type:** PtypInteger64, 0x0014

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.1

**Alternate names:** PR\_RULE\_ID, ptagRuleId

## 2.939 PidTagRuleIds

**Canonical name:** PidTagRuleIds

**Description:** Contains a buffer that is obtained by concatenating the **PidTagRuleId** property (section [2.938](#)) values from all of the rules contributing actions that are contained in the **PidTagClientActions** property (section [2.625](#)).

**Property ID:** 0x6675

**Data type:** PtypBinary, 0x0102

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.7

**Alternate names:** PR\_RULE\_IDS, ptagRuleIds

## 2.940 PidTagRuleLevel

**Canonical name:** PidTagRuleLevel

**Description:** Contains 0x00000000. This property is not used.

**Property ID:** 0x6683

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.6

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_LEVEL, ptagRuleLevel

## 2.941 PidTagRuleMessageLevel

**Canonical name:** PidTagRuleMessageLevel

**Description:** Contains 0x00000000. Set on the FAI message.

**Property ID:** 0x65ED

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.6

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_LEVEL, ptagRuleMsgLevel

## 2.942 PidTagRuleMessageName

**Canonical name:** PidTagRuleMessageName

**Description:** Specifies the name of the rule. Set on the FAI message.

**Property ID:** 0x65EC

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.1

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** ptagRuleMsgName

## 2.943 PidTagRuleMessageProvider

**Canonical name:** PidTagRuleMessageProvider

**Description:** Identifies the client application that owns the rule. Set on the FAI message.

**Property ID:** 0x65EB

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.7

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** ptagRuleMsgProvider

## 2.944 PidTagRuleMessageProviderData

**Canonical name:** PidTagRuleMessageProviderData

**Description:** Contains opaque data set by the client for the exclusive use of the client. Set on the FAI message.

**Property ID:** 0x65EE

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.8

**Alternate names:** PR\_RULE\_MSG\_PROVIDER\_DATA, ptagRuleMsgProviderData

## 2.945 PidTagRuleMessageSequence

**Canonical name:** PidTagRuleMessageSequence

**Description:** Contains a value used to determine the order in which rules are evaluated and executed. Set on the FAI message.

**Property ID:** 0x65F3

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.3

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_SEQUENCE, ptagRuleMsgSequence

## 2.946 PidTagRuleMessageState

**Canonical name:** PidTagRuleMessageState

**Description:** Contains flags that specify the state of the rule. Set on the FAI message.

**Property ID:** 0x65E9

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.4

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_STATE, ptagRuleMsgState

## 2.947 PidTagRuleMessageUserFlags

**Canonical name:** PidTagRuleMessageUserFlags

**Description:** Contains an opaque property that the client sets for the exclusive use of the client. Set on the FIA message.

**Property ID:** 0x65EA

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.5

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_USER\_FLAGS, ptagRuleMsgUserFlags

## 2.948 PidTagRuleName

**Canonical name:** PidTagRuleName

**Description:** Specifies the name of the rule.

**Property ID:** 0x6682

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.4

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_NAME, PR\_RULE\_NAME\_A, ptagRuleName, PR\_RULE\_NAME\_W

## 2.949 PidTagRuleProvider

**Canonical name:** PidTagRuleProvider

**Description:** Contains opaque data set by the client for the exclusive use of the client.

**Property ID:** 0x6681

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.5

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_PROVIDER, ptagRuleProvider, PR\_RULE\_PROVIDER\_W

## 2.950 PidTagRuleProviderData

**Canonical name:** PidTagRuleProviderData

**Description:** Contains opaque data set by the client for the exclusive use of the client.

**Property ID:** 0x6684

**Data type:** PtypBinary, 0x0102

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.8

**Alternate names:** PR\_RULE\_PROVIDER\_DATA, ptagRuleProviderData

## 2.951 PidTagRuleSequence

**Canonical name:** PidTagRuleSequence

**Description:** Contains a value used to determine the order in which rules are evaluated and executed.

**Property ID:** 0x6676

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.2

**Consuming references:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_SEQUENCE, ptagRuleSequence

## 2.952 PidTagRuleState

**Canonical name:** PidTagRuleState

**Description:** Contains flags that specify the state of the rule.

**Property ID:** 0x6677

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.3

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_STATE, ptagRuleState

## 2.953 PidTagRuleUserFlags

**Canonical name:** PidTagRuleUserFlags

**Description:** Contains an opaque property that the client sets for the exclusive use of the client.

**Property ID:** 0x6678

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.7

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_USER\_FLAGS, ptagRuleUserFlags

## 2.954 PidTagRwRulesStream

**Canonical name:** PidTagRwRulesStream

**Description:** Contains additional rule data about the **Rule FAI message**.

**Property ID:** 0x6802

**Data type:** PtypBinary, 0x0102

**Area:** Message Class Defined Transmittable

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.3

**Alternate names:** PR\_RW\_RULES\_STREAM

## 2.955 PidTagScheduleInfoAppointmentTombstone

**Canonical name:** PidTagScheduleInfoAppointmentTombstone

**Description:** Contains a list of tombstones, where each tombstone represents a Meeting object that has been declined.

**Property ID:** 0x686A

**Data type:** PtypBinary, 0x0102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.5

**Alternate names:** PR\_SCHDINFO\_APPT\_TOMBSTONE

## 2.956 PidTagScheduleInfoAutoAcceptAppointments

**Canonical name:** PidTagScheduleInfoAutoAcceptAppointments

**Description:** Indicates whether a client or server is to automatically respond to all meeting requests for the attendee or resource.

**Property ID:** 0x686D

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties



**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.2

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_AUTO\_ACCEPT\_APPTS

## 2.957 PidTagScheduleInfoDelegateEntryIds

**Canonical name:** PidTagScheduleInfoDelegateEntryIds

**Description:** Specifies the EntryIDs of the delegates.

**Property ID:** 0x6845

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.5

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_ENTRYIDS

## 2.958 PidTagScheduleInfoDelegateNames

**Canonical name:** PidTagScheduleInfoDelegateNames

**Description:** Specifies the names of the delegates.

**Property ID:** 0x6844

**Data type:** PtypMultipleString, 0x101F

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.3

**Consuming reference:** [\[MS-OXMSG\]](#)

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES

## 2.959 PidTagScheduleInfoDelegateNamesW

**Canonical name:** PidTagScheduleInfoDelegateNamesW

**Description:** Specifies the names of the delegates in Unicode.

**Property ID:** 0x684A

**Data type:** PtypMultipleString, 0x101F

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.4

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES\_W, ptagDelegateNames

## 2.960 PidTagScheduleInfoDelegatorWantsCopy

**Canonical name:** PidTagScheduleInfoDelegatorWantsCopy

**Description:** Indicates whether the delegator wants to receive copies of the meeting-related objects that are sent to the delegate.

**Property ID:** 0x6842

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_COPY

## 2.961 PidTagScheduleInfoDelegatorWantsInfo

**Canonical name:** PidTagScheduleInfoDelegatorWantsInfo

**Description:** Indicates whether the delegator wants to receive informational updates.

**Property ID:** 0x684B

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.2

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_INFO

## 2.962 PidTagScheduleInfoDisallowOverlappingAppts

**Canonical name:** PidTagScheduleInfoDisallowOverlappingAppts

**Description:** Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that overlap with previously scheduled events.

**Property ID:** 0x686F

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.4

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_OVERLAPPING\_APPTS

## 2.963 PidTagScheduleInfoDisallowRecurringAppts

**Canonical name:** PidTagScheduleInfoDisallowRecurringAppts

**Description:** Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that represent a recurring series.

**Property ID:** 0x686E

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.3

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_RECURRING\_APPTS

## 2.964 PidTagScheduleInfoDontMailDelegates

**Canonical name:** PidTagScheduleInfoDontMailDelegates

**Description:** Contains a value set to TRUE by the client, regardless of user input.

**Property ID:** 0x6843

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.7

**Consuming references:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DONT\_MAIL\_DELEGATES

## 2.965 PidTagScheduleInfoFreeBusy

**Canonical name:** PidTagScheduleInfoFreeBusy

**Description:** This property is deprecated and is not to be used.

**Property ID:** 0x686C

**Data type:** PtypBinary, 0x0102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.3

**Alternate names:** PR\_SCHDINFO\_FREEBUSY

## 2.966 PidTagScheduleInfoFreeBusyAway

**Canonical name:** PidTagScheduleInfoFreeBusyAway

**Description:** Specifies the times for which the free/busy status is set a value of OOF.

**Property ID:** 0x6856

**Data type:** **PtypMultipleBinary**, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.6

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_OOF

## 2.967 PidTagScheduleInfoFreeBusyBusy

**Canonical name:** PidTagScheduleInfoFreeBusyBusy

**Description:** Specifies the blocks of time for which the free/busy status is set to a value of **busy**.

**Property ID:** 0x6854

**Data type:** **PtypMultipleBinary**, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.4

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_BUSY

## 2.968 PidTagScheduleInfoFreeBusyMerged

**Canonical name:** PidTagScheduleInfoFreeBusyMerged

**Description:** Specifies the months for which free/busy data of type **busy** or OOF is present in the free/busy message.

**Property ID:** 0x6850

**Data type:** **PtypMultipleBinary**, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.8

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_MERGED

## 2.969 PidTagScheduleInfoFreeBusyTentative

**Canonical name:** PidTagScheduleInfoFreeBusyTentative

**Description:** Specifies the blocks of times for which the free/busy status is set to a value of **tentative**.

**Property ID:** 0x6852

**Data type:** **PtypMultipleBinary**, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.2

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_TENTATIVE

## 2.970 PidTagScheduleInfoMonthsAway

**Canonical name:** PidTagScheduleInfoMonthsAway

**Description:** Specifies the months for which free/busy data of type OOF is present in the free/busy message.

**Property ID:** 0x6855

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.5

**Alternate names:** PR\_SCHDINFO\_MONTHS\_OOF

## 2.971 PidTagScheduleInfoMonthsBusy

**Canonical name:** PidTagScheduleInfoMonthsBusy

**Description:** Specifies the months for which free/busy data of type **busy** is present in the free/busy message.

**Property ID:** 0x6853

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXMSG\]](#)

**Alternate names:** PR\_SCHDINFO\_MONTHS\_BUSY

## 2.972 PidTagScheduleInfoMonthsMerged

**Canonical name:** PidTagScheduleInfoMonthsMerged

**Description:** Specifies the months for which free/busy data of type **busy** or OOF is present in the free/busy message.

**Property ID:** 0x684F

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.7

**Alternate names:** PR\_SCHDINFO\_MONTHS\_MERGED

## 2.973 PidTagScheduleInfoMonthsTentative

**Canonical name:** PidTagScheduleInfoMonthsTentative

**Description:** Specifies the months for which free/busy data of type **tentative** is present in the free/busy message.

**Property ID:** 0x6851

**Data type:** **PtypMultipleInteger32**, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.1

**Alternate names:** PR\_SCHDINFO\_MONTHS\_TENTATIVE

## 2.974 PidTagScheduleInfoResourceType

**Canonical name:** PidTagScheduleInfoResourceType

**Description:** Set to 0x00000000 when sending and is ignored on receipt.

**Property ID:** 0x6841

**Data type:** **PtypInteger32**, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.2

**Alternate names:** PR\_SCHDINFO\_RESOURCE\_TYPE

## 2.975 PidTagSchedulePlusFreeBusyEntryId

**Canonical name:** PidTagSchedulePlusFreeBusyEntryId

**Description:** Contains the EntryID of the folder named "SCHEDULE+ FREE BUSY" under the non-IPM subtree of the public folder message store.

**Property ID:** 0x6622

**Data type:** **PtypBinary**, 0x0102

**Area:** ExchangeMessageStore

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.2.2

**Alternate names:** PR\_SPLUS\_FREE\_BUSY\_ENTRYID

## 2.976 PidTagScriptData

**Canonical name:** PidTagScriptData

**Description:** Contains a series of instructions that can be executed to format an address and the data that is needed to execute those instructions.

**Property ID:** 0x0004

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.2

**Alternate names:** PR\_EMS\_SCRIPT\_BLOB

## 2.977 PidTagSearchFolderDefinition

**Canonical name:** PidTagSearchFolderDefinition

**Description:** Specifies the search criteria and search options.

**Property ID:** 0x6845

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.8

**Alternate names:** PR\_WB\_SF\_DEFINITION

## 2.978 PidTagSearchFolderEfpFlags

**Canonical name:** PidTagSearchFolderEfpFlags

**Description:** Specifies flags that control how a folder is displayed.

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.7

**Alternate names:** PR\_WB\_SF\_EFP\_FLAGS

## 2.979 PidTagSearchFolderExpiration

**Canonical name:** PidTagSearchFolderExpiration

**Description:** Contains the time, in UTC, at which the search folder container will be stale and has to be updated or recreated.

**Property ID:** 0x683A

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.5

**Alternate names:** PR\_WB\_SF\_EXPIRATION

## 2.980 PidTagSearchFolderId

**Canonical name:** PidTagSearchFolderId

**Description:** Contains a GUID that identifies the search folder.

**Property ID:** 0x6842

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WB\_SF\_ID

## 2.981 PidTagSearchFolderLastUsed

**Canonical name:** PidTagSearchFolderLastUsed

**Description:** Contains the last time, in UTC, that the folder was accessed.

**Property ID:** 0x6834

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.4

**Alternate names:** PR\_WB\_SF\_LAST\_USED

## 2.982 PidTagSearchFolderRecreateInfo

**Canonical name:** PidTagSearchFolderRecreateInfo

**Description:** This property is not to be used.

**Property ID:** 0x6844

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.9

**Alternate names:** PR\_WB\_SF\_RECREATE\_INFO

## 2.983 PidTagSearchFolderStorageType

**Canonical name:** PidTagSearchFolderStorageType

**Description:** Contains flags that specify the binary large object (BLOB) data that appears in the **PidTagSearchFolderDefinition** (section [2.977](#)) property.

**Property ID:** 0x6846

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.6



**Alternate names:** PR\_WB\_SF\_STORAGE\_TYPE

## 2.984 PidTagSearchFolderTag

**Canonical name:** PidTagSearchFolderTag

**Description:** Contains the value of the **SearchFolderTag** sub-property of the **PidTagExtendedFolderFlags** (section [2.682](#)) property of the search folder container.

**Property ID:** 0x6847

**Data type:** **PtypInteger32**, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.3

**Alternate names:** PR\_WB\_SF\_TAG

## 2.985 PidTagSearchFolderTemplateId

**Canonical name:** PidTagSearchFolderTemplateId

**Description:** Contains the ID of the template that is being used for the search.

**Property ID:** 0x6841

**Data type:** **PtypInteger32**, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.2

**Alternate names:** PR\_WB\_SF\_TEMPLATE\_ID

## 2.986 PidTagSearchKey

**Canonical name:** PidTagSearchKey

**Description:** Contains a unique binary-comparable key that identifies an object for a search.

**Property ID:** 0x300B

**Data type:** **PtypBinary**, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SEARCH\_KEY, ptagSearchKey

## 2.987 PidTagSecurityDescriptorAsXml

**Canonical name:** PidTagSecurityDescriptorAsXml

**Description:** Contains security attributes in XML.

**Property ID:** 0x0E6A

**Data type:** **PtypString**, 0x001F

**Area:** Access Control Properties

**Defining reference:** [\[MS-XWDVSEC\]](#) section 2.2.2

**Consuming reference:** [\[MS-OXCPERM\]](#)

**Alternate names:** PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML, PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_A, PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_W, <http://schemas.microsoft.com/exchange/security/descriptor>

## 2.988 PidTagSelectable

**Canonical name:** PidTagSelectable

**Description:** This property is not set and, if set, is ignored.

**Property ID:** 0x3609

**Data type:** **PtypBoolean**, 0x000B

**Area:** AB Container

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.1

**Alternate names:** PR\_SELECTABLE

## 2.989 PidTagSenderAddressType

**Canonical name:** PidTagSenderAddressType

**Description:** Contains the e-mail address type of the sending mailbox owner.

**Property ID:** 0x0C1E

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.48

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** PR\_SENDER\_ADDRTYPE, PR\_SENDER\_ADDRTYPE\_A, ptagSenderAddrType, PR\_SENDER\_ADDRTYPE\_W

## 2.990 PidTagSenderEmailAddress

**Canonical name:** PidTagSenderEmailAddress

**Description:** Contains the e-mail address of the sending mailbox owner.

**Property ID:** 0x0C1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.49

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_EMAIL\_ADDRESS, PR\_SENDER\_EMAIL\_ADDRESS\_A, PR\_SENDER\_EMAIL\_ADDRESS\_W

## 2.991 PidTagSenderEntryId

**Canonical name:** PidTagSenderEntryId

**Description:** Identifies an address book EntryID that contains the address book EntryID of the sending mailbox owner.

**Property ID:** 0x0C19

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.50

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_ENTRYID, ptagSenderEntryId

## 2.992 PidTagSenderIdStatus

**Canonical name:** PidTagSenderIdStatus

**Description:** Reports the results of a Sender-ID check.

**Property ID:** 0x4079

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.80

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_SENDER\_ID\_STATUS

## 2.993 PidTagSenderName

**Canonical name:** PidTagSenderName

**Description:** Contains the display name of the sending mailbox owner.

**Property ID:** 0x0C1A

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.51

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_NAME, PR\_SENDER\_NAME\_A, ptagSenderName, PR\_SENDER\_NAME\_W, urn:schemas:httpmail:sendername, http://schemas.microsoft.com/exchange/sender-name-utf8

## 2.994 PidTagSenderSearchKey

**Canonical name:** PidTagSenderSearchKey

**Description:** Identifies an address book search key.

**Property ID:** 0x0C1D

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.52

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** PR\_SENDER\_SEARCH\_KEY, ptagSenderSearchKey

## 2.995 PidTagSenderSmtpAddress

**Canonical name:** PidTagSenderSmtpAddress

**Description:** Contains the SMTP e-mail address format of the e-mail address of the sending mailbox owner.

**Property ID:** 0x5D01

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section [2.2.1.55](#)

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** SenderSmtpAddress, ptagSenderSmtpAddress

## 2.996 PidTagSenderTelephoneNumber

**Canonical name:** PidTagSenderTelephoneNumber

**Description:** Contains the telephone number of the caller associated with a voice mail message.

**Property ID:** 0x6802

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.1

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaSenderTelephoneNumber

## 2.997 PidTagSendInternetEncoding

**Canonical name:** PidTagSendInternetEncoding

**Description:** Contains a bitmask of message encoding preferences for e-mail sent to an e-mail-enabled entity that is represented by this Address Book object.

**Property ID:** 0x3A71

**Data type:** PtypInteger32, 0x0003

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.19

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_INTERNET\_ENCODING, ptagSendInternetEncoding

## 2.998 PidTagSendRichInfo

**Canonical name:** PidTagSendRichInfo

**Description:** Indicates whether the e-mail-enabled entity represented by the Address Book object can receive all message content, including Rich Text Format (RTF) and other embedded objects.

**Property ID:** 0x3A40

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.18

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_RICH\_INFO, ptagSendRichInfo

## 2.999 PidTagSensitivity

**Canonical name:** PidTagSensitivity

**Description:** Indicates the sender's assessment of the sensitivity of the Message object.

**Property ID:** 0x0036

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.13

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_SENSITIVITY, ptagSensitivity, <http://schemas.microsoft.com/exchange/sensitivity-long>, <http://schemas.microsoft.com/exchange/sensitivity>

## 2.1000 PidTagSentMailSvrEID

**Canonical name:** PidTagSentMailSvrEID

**Description:** Contains an EntryID that represents the **Sent Items folder** for the message.

**Property ID:** 0x6740

**Data type:** PtypServerId, 0x00FB

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.10

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagSentMailSvrEID

## 2.1001 PidTagSentRepresentingAddressType

**Canonical name:** PidTagSentRepresentingAddressType

**Description:** Contains an e-mail address type.

**Property ID:** 0x0064

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.54

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ADDRTYPE, PR\_SENT\_REPRESENTING\_ADDRTYPE\_A, ptagSentRepresentingAddrType, PR\_SENT\_REPRESENTING\_ADDRTYPE\_W

## 2.1002 PidTagSentRepresentingEmailAddress

**Canonical name:** PidTagSentRepresentingEmailAddress

**Description:** Contains an e-mail address for the end user who is represented by the sending mailbox owner.

**Property ID:** 0x0065

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.55

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.1003 PidTagSentRepresentingEntryId

**Canonical name:** PidTagSentRepresentingEntryId

**Description:** Contains the identifier of the end user who is represented by the sending mailbox owner.

**Property ID:** 0x0041

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.56

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ENTRYID, ptagSentRepresentingEntryId

## 2.1004 PidTagSentRepresentingFlags

**Canonical name:** PidTagSentRepresentingFlags

**Description:**

**Property ID:** 0x401A

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:**

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** ptagSentRepresentingFlags

## 2.1005 PidTagSentRepresentingName

**Canonical name:** PidTagSentRepresentingName

**Description:** Contains the display name for the end user who is represented by the sending mailbox owner.

**Property ID:** 0x0042

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.57

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_NAME, PR\_SENT\_REPRESENTING\_NAME\_A, ptagSentRepresentingName, PR\_SENT\_REPRESENTING\_NAME\_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

## 2.1006 PidTagSentRepresentingSearchKey

**Canonical name:** PidTagSentRepresentingSearchKey

**Description:** Contains a binary-comparable key that represents the end user who is represented by the sending mailbox owner.

**Property ID:** 0x003B

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.58

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_SEARCH\_KEY, ptagSentRepresentingSearchKey

## 2.1007 PidTagSentRepresentingSmtpAddress

**Canonical name:** PidTagSentRepresentingSmtpAddress

**Description:** Contains the SMTP e-mail address of the end user who is represented by the sending mailbox owner.

**Property ID:** 0x5D02

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.59

**Alternate names:** ptagRecipientSentRepresentingSMTPAddress, SentRepresentingSMTPAddressXSO, PR\_SENT\_REPRESENTING\_SMTP\_ADDRESS

## 2.1008 PidTagSmtpAddress

**Canonical name:** PidTagSmtpAddress

**Description:** Contains the SMTP address of the Message object.



**Property ID:** 0x39FE

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.21

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXSHARE\]](#)

**Alternate names:** PR\_SMTP\_ADDRESS, PR\_SMTP\_ADDRESS\_A, PR\_SMTP\_ADDRESS\_W

## 2.1009 PidTagSortLocaleId

**Canonical name:** PidTagSortLocaleId

**Description:** Contains the locale identifier.

**Property ID:** 0x6705

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.13

**Consuming reference:** [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_SORT\_LOCALE\_ID, ptagSortLocaleId

## 2.1010 PidTagSourceKey

**Canonical name:** PidTagSourceKey

**Description:** Contains a value that contains an internal global identifier (GID) for this folder or message.

**Property ID:** 0x65E0

**Data type:** PtypBinary, 0x0102

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.5

**Alternate names:** PR\_SOURCE\_KEY

## 2.1011 PidTagSpokenName

**Canonical name:** PidTagSpokenName

**Description:** Contains a recording of the mail user's name pronunciation.

**Property ID:** 0x8CC2

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.41

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_UM\_SPOKEN\_NAME

## 2.1012 PidTagSpouseName

**Canonical name:** PidTagSpouseName

**Description:** Contains the name of the mail user's spouse/partner.

**Property ID:** 0x3A48

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_SPOUSE\_NAME, PR\_SPOUSE\_NAME\_A, PR\_SPOUSE\_NAME\_W,  
urn:schemas:contacts:spousecn

## 2.1013 PidTagStartDate

**Canonical name:** PidTagStartDate

**Description:** Contains the value of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

**Property ID:** 0x0060

**Data type:** **PtypTime**, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.30

**Consuming references:** [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#),

**Alternate names:** PR\_START\_DATE, [http://schemas.microsoft.com/mapi/start\\_date](http://schemas.microsoft.com/mapi/start_date)

## 2.1014 PidTagStartDateEtc

**Canonical name:** PidTagStartDateEtc

**Description:** Contains the default retention period, and the start date from which the age of a Message object is calculated.

**Property ID:** 0x301B

**Data type:** **PtypBinary**, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.4

**Alternate names:** PR\_START\_DATE\_ETC, ptagStartDateEtc

## 2.1015 PidTagStateOrProvince

**Canonical name:** PidTagStateOrProvince

**Description:** Contains the name of the mail user's state or province.

**Property ID:** 0x3A28

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.17

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_STATE\_OR\_PROVINCE, PR\_STATE\_OR\_PROVINCE\_A, PR\_STATE\_OR\_PROVINCE\_W, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:mailingstate

## 2.1016 PidTagStoreEntryId

**Canonical name:** PidTagStoreEntryId

**Description:** Contains the unique EntryID of the message store where an object resides.

**Property ID:** 0x0FFB

**Data type:** **PtypBinary**, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.44

**Consuming references:** [\[MS-OXOFLAG\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_STORE\_ENTRYID, ptagStoreEntryId

## 2.1017 PidTagStoreState

**Canonical name:** PidTagStoreState

**Description:** Indicates whether a mailbox has any active Search folders.

**Property ID:** 0x340E

**Data type:** **PtypInteger32**, 0x0003

**Area:** MapiMessageStore

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_STORE\_STATE

## 2.1018 PidTagStoreSupportMask

**Canonical name:** PidTagStoreSupportMask

**Description:** Indicates whether string properties within the .msg file are Unicode-encoded.

**Property ID:** 0x340D

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXMSG\]](#) section 2.1.1.1

**Alternate names:** PR\_STORE\_SUPPORT\_MASK, ptagStoreSupportMask

## 2.1019 PidTagStreetAddress

**Canonical name:** PidTagStreetAddress

**Description:** Contains the mail user's street address.

**Property ID:** 0x3A29

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.14

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_STREET\_ADDRESS, PR\_STREET\_ADDRESS\_A, PR\_STREET\_ADDRESS\_W, PR\_BUSINESS\_ADDRESS\_STREET, PR\_BUSINESS\_ADDRESS\_STREET\_A, PR\_BUSINESS\_ADDRESS\_STREET\_W, urn:schemas:contacts:mailingstreet

## 2.1020 PidTagSubfolders

**Canonical name:** PidTagSubfolders

**Description:** Specifies whether a folder has subfolders.

**Property ID:** 0x360A

**Data type:** PtypBoolean, 0x000B

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.10

**Alternate names:** PR\_SUBFOLDERS, ptagSubFolders, DAV:hassubs

## 2.1021 PidTagSubject

**Canonical name:** PidTagSubject

**Description:** Contains the subject of the e-mail message.

**Property ID:** 0x0037

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.46

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXORULE\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_SUBJECT, PR\_SUBJECT\_A, ptagSubject, PR\_SUBJECT\_W, urn:schemas:httpmail:subject, http://schemas.microsoft.com/exchange/subject-utf8

## 2.1022 PidTagSubjectPrefix

**Canonical name:** PidTagSubjectPrefix

**Description:** Contains the prefix for the subject of the message.

**Property ID:** 0x003D

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SUBJECT\_PREFIX, PR\_SUBJECT\_PREFIX\_A, ptagSubjectPrefix, PR\_SUBJECT\_PREFIX\_W

## 2.1023 PidTagSupplementaryInfo

**Canonical name:** PidTagSupplementaryInfo

**Description:** Contains supplementary information about a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C1B

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.36

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_SUPPLEMENTARY\_INFO, ptagSupplementaryInfo

## 2.1024 PidTagSurname

**Canonical name:** PidTagSurname

**Description:** Contains the mail user's family name.

**Property ID:** 0x3A11

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.1

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_SURNAME, PR\_SURNAME\_A, PR\_SURNAME\_W, urn:schemas:contacts:sn

## 2.1025 PidTagSwappedToDoData

**Canonical name:** PidTagSwappedToDoData

**Description:** Contains a secondary storage location for flags when sender flags or sender reminders are supported.

**Property ID:** 0x0E2D

**Data type:** **PtypBinary**, 0x0102

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_DATA, ptagSwappedToDoData

## 2.1026 PidTagSwappedToDoStore

**Canonical name:** PidTagSwappedToDoStore

**Description:** Contains the value of the **PidTagStoreEntryId** property (section [2.1016](#)) of the message when the value of the **PidTagSwappedToDoData** property (section [2.1025](#)) is set.

**Property ID:** 0x0E2C

**Data type:** **PtypBinary**, 0x0102

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.8

**Consuming reference:** [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_STORE, ptagSwappedToDoStore

## 2.1027 PidTagTargetEntryId

**Canonical name:** PidTagTargetEntryId

**Description:** Contains the message ID of a Message object being submitted for optimization ([\[MS-OXOMSG\]](#) section 3.2.4.4).

**Property ID:** 0x3010

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.76

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCRPC\]](#)

**Alternate names:** PR\_TARGET\_ENTRYID, ptagTargetEntryId

## 2.1028 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Canonical name:** PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Description:** Contains the mail user's telecommunication device for the deaf (TTY/TDD) telephone number.

**Property ID:** 0x3A4B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.13

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TTYTDD\_PHONE\_NUMBER, PR\_TTYTDD\_PHONE\_NUMBER\_A, PR\_TTYTDD\_PHONE\_NUMBER\_W, urn:schemas:contacts:tytddphone

## 2.1029 PidTagTelexNumber

**Canonical name:** PidTagTelexNumber

**Description:** Contains the mail user's telex number.

**Property ID:** 0x3A2C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.30

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TELEX\_NUMBER, PR\_TELEX\_NUMBER\_A, PR\_TELEX\_NUMBER\_W, urn:schemas:contacts:telexnumber

## 2.1030 PidTagTemplateData

**Canonical name:** PidTagTemplateData

**Description:** Describes the controls used in the template that is used to retrieve address book information.

**Property ID:** 0x0001

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.2

**Alternate names:** PR\_EMS\_TEMPLATE\_BLOB

### 2.1031 PidTagTemplateid

**Canonical name:** PidTagTemplateid

**Description:** Contains the value of the **PidTagEntryId** property (section [2.674](#)), expressed as a **Permanent Entry ID** format.

**Property ID:** 0x3902

**Data type:** PtypBinary, 0x0102

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.3

**Alternate names:** PR\_TEMPLATEID

### 2.1032 PidTagTextAttachmentCharset

**Canonical name:** PidTagTextAttachmentCharset

**Description:** Specifies the character set of an attachment received via MIME with the content-type of text.

**Property ID:** 0x371B

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.25

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagTextAttachmentCharset

### 2.1033 PidTagThumbnailPhoto

**Canonical name:** PidTagThumbnailPhoto

**Description:** Contains the mail user's photo in .jpg format.

**Property ID:** 0x8C9E

**Data type:** PtypBinary, 0x0102

**Area:** Address Book



**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.40

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_THUMBNAIL\_PHOTO

## 2.1034 PidTagTitle

**Canonical name:** PidTagTitle

**Description:** Contains the mail user's job title.

**Property ID:** 0x3A17

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.4

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TITLE, PR\_TITLE\_A, PR\_TITLE\_W, urn:schemas:contacts:title

## 2.1035 PidTagTnefCorrelationKey

**Canonical name:** PidTagTnefCorrelationKey

**Description:** Contains a value that correlates a Transport Neutral Encapsulation Format (TNEF) attachment with a message.

**Property ID:** 0x007F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.29

**Consuming reference:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_TNEF\_CORRELATION\_KEY

## 2.1036 PidTagToDoItemFlags

**Canonical name:** PidTagToDoItemFlags

**Description:** Contains flags associated with objects.

**Property ID:** 0x0E2B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_TODO\_ITEM\_FLAGS, ptagToDoItemFlags

## 2.1037 PidTagTransmittableDisplayName

**Canonical name:** PidTagTransmittableDisplayName

**Description:** Contains an Address Book object's display name that is transmitted with the message.

**Property ID:** 0x3A20

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.8

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_TRANSMITABLE\_DISPLAY\_NAME, PR\_TRANSMITABLE\_DISPLAY\_NAME\_A, ptagTransmittableDisplayName, PR\_TRANSMITABLE\_DISPLAY\_NAME\_W

## 2.1038 PidTagTransportMessageHeaders

**Canonical name:** PidTagTransportMessageHeaders

**Description:** Contains transport-specific message envelope information for e-mail.

**Property ID:** 0x007D

**Data type:** PtypString, 0x001F

**Area:** E-mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.61

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_TRANSPORT\_MESSAGE\_HEADERS, PR\_TRANSPORT\_MESSAGE\_HEADERS\_A, PR\_TRANSPORT\_MESSAGE\_HEADERS\_W

## 2.1039 PidTagTrustSender

**Canonical name:** PidTagTrustSender

**Description:** Specifies whether the associated message was delivered through a trusted transport channel.

**Property ID:** 0x0E79

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.45

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_TRUST\_SENDER, ptagTrustSender

## 2.1040 PidTagUserCertificate

**Canonical name:** PidTagUserCertificate

**Description:** Contains an ASN.1 authentication certificate for a messaging user.

**Property ID:** 0x3A22

**Data type:** PtypBinary, 0x0102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.34

**Consuming references:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_USER\_CERTIFICATE, ptagUserCertificate, urn:schemas:contacts:usercertificate

## 2.1041 PidTagUserEntryId

**Canonical name:** PidTagUserEntryId

**Description:** Address book EntryID of the user logged on to the public folders.

**Property ID:** 0x6619

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageStore

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_USER\_ENTRYID, ptagUserEntryId

## 2.1042 PidTagUserX509Certificate

**Canonical name:** PidTagUserX509Certificate

**Description:** Contains a list of certificates for the mail user.

**Property ID:** 0x3A70

**Data type:** PtypMultipleBinary, 0x1102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.36

**Consuming references:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_USER\_X509\_CERTIFICATE

## 2.1043 PidTagViewDescriptorBinary

**Canonical name:** PidTagViewDescriptorBinary

**Description:** Contains view definitions.

**Property ID:** 0x7001

**Data type:** PtypBinary, 0x0102

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.6.1

**Alternate names:** PR\_VD\_BINARY

## 2.1044 PidTagViewDescriptorName

**Canonical name:** PidTagViewDescriptorName

**Description:**

**Property ID:** 0x7006

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:**

**Consuming reference:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_NAME, PR\_VD\_NAME\_W

## 2.1045 PidTagViewDescriptorStrings

**Canonical name:** PidTagViewDescriptorStrings

**Description:** Contains view definitions in string format.

**Property ID:** 0x7002

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.6.2

**Alternate names:** PR\_VD\_STRINGS, PR\_VD\_STRINGS\_W

## 2.1046 PidTagViewDescriptorVersion

**Canonical name:** PidTagViewDescriptorVersion

**Description:** Contains the View Descriptor version.

**Property ID:** 0x7007

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:**

**Consuming reference:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_VERSION

## 2.1047 PidTagVoiceMessageAttachmentOrder

**Canonical name:** PidTagVoiceMessageAttachmentOrder

**Description:** Contains a list of file names for the audio file attachments that are to be played as part of a message.

**Property ID:** 0x6805

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.9

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageAttachmentOrder

## 2.1048 PidTagVoiceMessageDuration

**Canonical name:** PidTagVoiceMessageDuration

**Description:** Specifies the length of the attached audio message, in seconds.

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.3

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageDuration

## 2.1049 PidTagVoiceMessageSenderName

**Canonical name:** PidTagVoiceMessageSenderName

**Description:** Specifies the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

**Property ID:** 0x6803

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.5

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageSenderName

## 2.1050 PidTagWeddingAnniversary

**Canonical name:** PidTagWeddingAnniversary

**Description:** Contains the date of the mail user's wedding anniversary.

**Property ID:** 0x3A41

**Data type:** PtypTime, 0x0040

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_WEDDING\_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

## 2.1051 PidTagWlinkAddressBookEID

**Canonical name:** PidTagWlinkAddressBookEID

**Description:** Specifies the value of the **PidTagEntryId** property (section [2.674](#)) of the user to whom the folder belongs.

**Property ID:** 0x6854

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.16

**Alternate names:** PR\_WLINK\_ABEID

## 2.1052 PidTagWlinkAddressBookStoreEID

**Canonical name:** PidTagWlinkAddressBookStoreEID

**Description:** Specifies the value of the **PidTagStoreEntryId** property (section [2.1016](#)) of the current user (not the owner of the folder).

**Property ID:** 0x6891

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.17

**Alternate names:** PR\_WLINK\_AB\_EXSTOREEID

## 2.1053 PidTagWlinkCalendarColor

**Canonical name:** PidTagWlinkCalendarColor

**Description:** Specifies the background color of the calendar.

**Property ID:** 0x6853

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.15

**Alternate names:** PR\_WLINK\_CALENDAR\_COLOR

## 2.1054 PidTagWlinkClientID

**Canonical name:** PidTagWlinkClientID

**Description:** Specifies the Client ID that allows the client to determine whether the shortcut was created on the current machine/user via an equality test.

**Property ID:** 0x6890

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.18

**Alternate names:** PR\_WLINK\_CLIENTID

## 2.1055 PidTagWlinkEntryId

**Canonical name:** PidTagWlinkEntryId

**Description:** Specifies the EntryID of the folder pointed to by the shortcut.

**Property ID:** 0x684C

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.8

**Alternate names:** PR\_WLINK\_ENTRYID

## 2.1056 PidTagWlinkFlags

**Canonical name:** PidTagWlinkFlags

**Description:** Specifies conditions associated with the shortcut.

**Property ID:** 0x684A

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.6

**Alternate names:** PR\_WLINK\_FLAGS

## 2.1057 PidTagWlinkFolderType

**Canonical name:** PidTagWlinkFolderType

**Description:** Specifies the type of folder pointed to by the shortcut.

**Property ID:** 0x684F

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.11

**Alternate names:** PR\_WLINK\_FOLDER\_TYPE

## 2.1058 PidTagWlinkGroupClsid

**Canonical name:** PidTagWlinkGroupClsid

**Description:** Specifies the value of the **PidTagWlinkGroupHeaderID** property (section [2.1058](#)) of the **group header** associated with the shortcut.

**Property ID:** 0x6850

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.12

**Alternate names:** PR\_WLINK\_GROUP\_CLSID

## 2.1059 PidTagWlinkGroupHeaderID

**Canonical name:** PidTagWlinkGroupHeaderID

**Description:** Specifies the ID of the **navigation shortcut** that groups other navigation shortcuts.

**Property ID:** 0x6842

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.3

**Alternate names:**

## 2.1060 PidTagWlinkGroupName

**Canonical name:** PidTagWlinkGroupName

**Description:** Specifies the value of the **PidTagNormalizedSubject** (section [2.801](#)) of the group header associated with the shortcut.

**Property ID:** 0x6851



**Data type:** PtypString, 0x001F

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.13

**Alternate names:** PR\_WLINK\_GROUP\_NAME

## 2.1061 PidTagWlinkOrdinal

**Canonical name:** PidTagWlinkOrdinal

**Description:** Specifies a variable-length binary property to be used to sort shortcuts lexicographically.

**Property ID:** 0x684B

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.7

**Alternate names:** PR\_WLINK\_ORDINAL

## 2.1062 PidTagWlinkRecordKey

**Canonical name:** PidTagWlinkRecordKey

**Description:** Specifies the value of **PidTagRecordKey** property (section [2.899](#)) of the folder pointed to by the shortcut.

**Property ID:** 0x684D

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.9

**Alternate names:** PR\_WLINK\_RECKEY

## 2.1063 PidTagWlinkROGroupType

**Canonical name:** PidTagWlinkROGroupType

**Description:** Specifies the type of group header.

**Property ID:** 0x6892

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.19

**Alternate names:** PR\_WLINK\_RO\_GROUP\_TYPE

## 2.1064 PidTagWlinkSaveStamp

**Canonical name:** PidTagWlinkSaveStamp

**Description:** Specifies an integer that allows a client to identify with a high probability whether the navigation shortcut was saved by the current client session.

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.4

**Alternate names:**

## 2.1065 PidTagWlinkSection

**Canonical name:** PidTagWlinkSection

**Description:** Specifies the section where the shortcut should be grouped.

**Property ID:** 0x6852

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.14

**Alternate names:** PR\_WLINK\_SECTION

## 2.1066 PidTagWlinkStoreEntryId

**Canonical name:** PidTagWlinkStoreEntryId

**Description:** Specifies the value of the **PidTagStoreEntryId** property (section [2.1016](#)) of the folder pointed to by the shortcut.

**Property ID:** 0x684E

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.10

**Alternate names:** PR\_WLINK\_STORE\_ENTRYID

## 2.1067 PidTagWlinkType

**Canonical name:** PidTagWlinkType

**Description:** Specifies the type of navigation shortcut.

**Property ID:** 0x6849

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.5

**Alternate names:** PR\_WLINK\_TYPE

### 3 Structure Examples

None.

## 4 Security Considerations

There are no security considerations unique to this specification.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs:

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Office Outlook 2003
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 6 Change Tracking

No table of changes is available. The document is either new or has had no changes since its last release.

## 7 Index

### A

[Applicability](#) 37

[Vendor-extensible fields](#) 37  
[Versioning](#) 37

### C

[Change tracking](#) 383

### E

[Examples](#) 380

### F

[Fields - vendor-extensible](#) 37

### G

[Glossary](#) 25

### I

[Implementer - security considerations](#) 381

[Informative references](#) 30

[Introduction](#) 25

### L

[Localization](#) 37

### N

[Normative references](#) 28

### O

[Overview \(synopsis\)](#) 30

### P

[Product behavior](#) 382

### R

[References](#) 28

[informative](#) 30

[normative](#) 28

[Relationship to protocols and other structures](#) 36

### S

[Security - implementer considerations](#) 381

### T

[Tracking changes](#) 383

### V