

# [MS-OXPROPS]:

## Exchange Server Protocols Master Property List

---

### Intellectual Property Rights Notice for Open Specifications Documentation

- **Technical Documentation.** Microsoft publishes Open Specifications documentation (“this documentation”) for protocols, file formats, data portability, computer languages, and standards support. Additionally, overview documents cover inter-protocol relationships and interactions.
- **Copyrights.** This documentation is covered by Microsoft copyrights. Regardless of any other terms that are contained in the terms of use for the Microsoft website that hosts this documentation, you can make copies of it in order to develop implementations of the technologies that are described in this documentation and can distribute portions of it in your implementations that use these technologies or in your documentation as necessary to properly document the implementation. You can also distribute in your implementation, with or without modification, any schemas, IDLs, or code samples that are included in the documentation. This permission also applies to any documents that are referenced in the Open Specifications documentation.
- **No Trade Secrets.** Microsoft does not claim any trade secret rights in this documentation.
- **Patents.** Microsoft has patents that might cover your implementations of the technologies described in the Open Specifications documentation. Neither this notice nor Microsoft's delivery of this documentation grants any licenses under those patents or any other Microsoft patents. However, a given Open Specifications document might be covered by the Microsoft [Open Specifications Promise](#) or the [Microsoft Community Promise](#). If you would prefer a written license, or if the technologies described in this documentation are not covered by the Open Specifications Promise or Community Promise, as applicable, patent licenses are available by contacting [iplg@microsoft.com](mailto:iplg@microsoft.com).
- **Trademarks.** The names of companies and products contained in this documentation might be covered by trademarks or similar intellectual property rights. This notice does not grant any licenses under those rights. For a list of Microsoft trademarks, visit [www.microsoft.com/trademarks](http://www.microsoft.com/trademarks).
- **Fictitious Names.** The example companies, organizations, products, domain names, email addresses, logos, people, places, and events that are depicted in this documentation are fictitious. No association with any real company, organization, product, domain name, email address, logo, person, place, or event is intended or should be inferred.

**Reservation of Rights.** All other rights are reserved, and this notice does not grant any rights other than as specifically described above, whether by implication, estoppel, or otherwise.

**Tools.** The Open Specifications documentation does not require the use of Microsoft programming tools or programming environments in order for you to develop an implementation. If you have access to Microsoft programming tools and environments, you are free to take advantage of them. Certain Open Specifications documents are intended for use in conjunction with publicly available standards specifications and network programming art and, as such, assume that the reader either is familiar with the aforementioned material or has immediate access to it.

## Revision Summary

Date	Revision History	Revision Class	Comments
4/4/2008	0.1	New	Initial Availability.
4/25/2008	0.2	Minor	Revised and updated property names and other technical content.
6/27/2008	1.0	Major	Initial Release.
8/6/2008	1.01	Minor	Updated references to reflect date of initial release.
9/3/2008	1.02	Minor	Changed title of document.
10/1/2008	1.03	Minor	Revised and edited technical content.
12/3/2008	1.04	Minor	Revised and edited technical content.
2/4/2009	1.05	Minor	Revised and edited technical content.
3/4/2009	1.06	Minor	Revised and edited technical content.
4/10/2009	2.0	Major	Updated technical content and applicable product releases.
7/15/2009	3.0	Major	Revised and edited for technical content.
11/4/2009	4.0.0	Major	Updated and revised the technical content.
2/10/2010	5.0.0	Major	Updated and revised the technical content.
5/5/2010	6.0.0	Major	Updated and revised the technical content.
8/4/2010	7.0	Major	Significantly changed the technical content.
11/3/2010	8.0	Major	Significantly changed the technical content.
3/18/2011	9.0	Major	Significantly changed the technical content.
8/5/2011	10.0	Major	Significantly changed the technical content.
10/7/2011	11.0	Major	Significantly changed the technical content.
1/20/2012	12.0	Major	Significantly changed the technical content.
4/27/2012	13.0	Major	Significantly changed the technical content.
7/16/2012	13.1	Minor	Clarified the meaning of the technical content.
10/8/2012	14.0	Major	Significantly changed the technical content.
2/11/2013	15.0	Major	Significantly changed the technical content.
7/26/2013	16.0	Major	Significantly changed the technical content.
11/18/2013	16.0	None	No changes to the meaning, language, or formatting of the technical content.
2/10/2014	16.0	None	No changes to the meaning, language, or formatting of the technical content.
4/30/2014	16.1	Minor	Clarified the meaning of the technical content.
7/31/2014	16.2	Minor	Clarified the meaning of the technical content.

<b>Date</b>	<b>Revision History</b>	<b>Revision Class</b>	<b>Comments</b>
10/30/2014	16.3	Minor	Clarified the meaning of the technical content.
3/16/2015	17.0	Major	Significantly changed the technical content.
5/26/2015	17.1	Minor	Clarified the meaning of the technical content.
9/14/2015	18.0	Major	Significantly changed the technical content.
6/13/2016	19.0	Major	Significantly changed the technical content.

# Table of Contents

<b>1</b>	<b>Introduction .....</b>	<b>23</b>
1.1	Glossary .....	23
1.2	References .....	31
1.2.1	Normative References .....	31
1.2.2	Informative References .....	33
1.3	Overview .....	33
1.3.1	Common Message Classes .....	34
1.3.2	Commonly Used Property Sets .....	35
1.3.3	Property ID Ranges.....	36
1.3.4	WebDAV Property Naming .....	38
1.3.4.1	http://schemas.microsoft.com/mapi/proptag Namespace.....	38
1.3.4.2	http://schemas.microsoft.com/mapi/id Namespace .....	38
1.3.4.3	http://schemas.microsoft.com/mapi/string Namespace .....	38
1.4	Relationship to Protocols and Other Structures .....	39
1.5	Applicability Statement .....	39
1.6	Versioning and Localization .....	39
1.7	Vendor-Extensible Fields .....	39
<b>2</b>	<b>Structures .....</b>	<b>40</b>
2.1	PidLidAddressBookProviderArrayType .....	40
2.2	PidLidAddressBookProviderEmailList .....	40
2.3	PidLidAddressCountryCode .....	40
2.4	PidLidAgingDontAgeMe .....	40
2.5	PidLidAllAttendeesString .....	41
2.6	PidLidAllowExternalCheck.....	41
2.7	PidLidAnniversaryEventEntryId .....	42
2.8	PidLidAppointmentAuxiliaryFlags .....	42
2.9	PidLidAppointmentColor .....	42
2.10	PidLidAppointmentCounterProposal .....	42
2.11	PidLidAppointmentDuration .....	43
2.12	PidLidAppointmentEndDate.....	43
2.13	PidLidAppointmentEndTime .....	43
2.14	PidLidAppointmentEndWhole .....	44
2.15	PidLidAppointmentLastSequence .....	44
2.16	PidLidAppointmentMessageClass .....	44
2.17	PidLidAppointmentNotAllowPropose .....	45
2.18	PidLidAppointmentProposalNumber .....	45
2.19	PidLidAppointmentProposedDuration .....	45
2.20	PidLidAppointmentProposedEndWhole.....	46
2.21	PidLidAppointmentProposedStartWhole .....	46
2.22	PidLidAppointmentRecur .....	46
2.23	PidLidAppointmentReplyName .....	47
2.24	PidLidAppointmentReplyTime.....	47
2.25	PidLidAppointmentSequence .....	48
2.26	PidLidAppointmentSequenceTime .....	48
2.27	PidLidAppointmentStartDate .....	48
2.28	PidLidAppointmentStartTime.....	49
2.29	PidLidAppointmentStartWhole.....	49
2.30	PidLidAppointmentStateFlags.....	49
2.31	PidLidAppointmentSubType .....	50
2.32	PidLidAppointmentTimeZoneDefinitionEndDisplay .....	50
2.33	PidLidAppointmentTimeZoneDefinitionRecur .....	50
2.34	PidLidAppointmentTimeZoneDefinitionStartDisplay .....	51
2.35	PidLidAppointmentUnsendableRecipients .....	51
2.36	PidLidAppointmentUpdateTime.....	51

2.37	PidLidAttendeeCriticalChange.....	52
2.38	PidLidAutoFillLocation .....	52
2.39	PidLidAutoLog .....	52
2.40	PidLidAutoProcessState .....	53
2.41	PidLidAutoStartCheck .....	53
2.42	PidLidBilling.....	53
2.43	PidLidBirthdayEventEntryId .....	54
2.44	PidLidBirthdayLocal .....	54
2.45	PidLidBusinessCardCardPicture .....	54
2.46	PidLidBusinessCardDisplayDefinition .....	54
2.47	PidLidBusyStatus .....	55
2.48	PidLidCalendarType .....	55
2.49	PidLidCategories .....	56
2.50	PidLidCcAttendeesString .....	56
2.51	PidLidChangeHighlight .....	56
2.52	PidLidClassification .....	56
2.53	PidLidClassificationDescription .....	57
2.54	PidLidClassificationGuid.....	57
2.55	PidLidClassificationKeep .....	57
2.56	PidLidClassified .....	58
2.57	PidLidCleanGlobalObjectId.....	58
2.58	PidLidClientIntent.....	58
2.59	PidLidClipEnd.....	59
2.60	PidLidClipStart .....	59
2.61	PidLidCollaborateDoc .....	59
2.62	PidLidCommonEnd .....	60
2.63	PidLidCommonStart.....	60
2.64	PidLidCompanies.....	60
2.65	PidLidConferencingCheck .....	61
2.66	PidLidConferencingType .....	61
2.67	PidLidContactCharacterSet .....	61
2.68	PidLidContactItemData .....	62
2.69	PidLidContactLinkedGlobalAddressListEntryId .....	62
2.70	PidLidContactLinkEntry .....	62
2.71	PidLidContactLinkGlobalAddressListLinkId .....	63
2.72	PidLidContactLinkGlobalAddressListLinkState .....	63
2.73	PidLidContactLinkLinkRejectHistory .....	63
2.74	PidLidContactLinkName.....	63
2.75	PidLidContactLinkSearchKey .....	64
2.76	PidLidContactLinkSMTPAddressCache.....	64
2.77	PidLidContacts .....	64
2.78	PidLidContactUserField1 .....	65
2.79	PidLidContactUserField2 .....	65
2.80	PidLidContactUserField3 .....	65
2.81	PidLidContactUserField4 .....	66
2.82	PidLidConversationActionLastAppliedTime .....	66
2.83	PidLidConversationActionMaxDeliveryTime .....	67
2.84	PidLidConversationActionMoveFolderEid .....	67
2.85	PidLidConversationActionMoveStoreEid .....	67
2.86	PidLidConversationActionVersion .....	67
2.87	PidLidConversationProcessed .....	68
2.88	PidLidCurrentVersion .....	68
2.89	PidLidCurrentVersionName .....	68
2.90	PidLidDayInterval .....	69
2.91	PidLidDayOfMonth .....	69
2.92	PidLidDelegateMail .....	69
2.93	PidLidDepartment.....	70
2.94	PidLidDirectory .....	70

2.95	PidLidDistributionListChecksum .....	70
2.96	PidLidDistributionListMembers .....	71
2.97	PidLidDistributionListName .....	71
2.98	PidLidDistributionListOneOffMembers .....	71
2.99	PidLidDistributionListStream .....	72
2.100	PidLidEmail1AddressType .....	72
2.101	PidLidEmail1DisplayName .....	72
2.102	PidLidEmail1EmailAddress .....	73
2.103	PidLidEmail1OriginalDisplayName .....	73
2.104	PidLidEmail1OriginalEntryId .....	73
2.105	PidLidEmail2AddressType .....	73
2.106	PidLidEmail2DisplayName .....	74
2.107	PidLidEmail2EmailAddress .....	74
2.108	PidLidEmail2OriginalDisplayName .....	74
2.109	PidLidEmail2OriginalEntryId .....	75
2.110	PidLidEmail3AddressType .....	75
2.111	PidLidEmail3DisplayName .....	75
2.112	PidLidEmail3EmailAddress .....	76
2.113	PidLidEmail3OriginalDisplayName .....	76
2.114	PidLidEmail3OriginalEntryId .....	76
2.115	PidLidEndRecurrenceDate .....	77
2.116	PidLidEndRecurrenceTime .....	77
2.117	PidLidExceptionReplaceTime .....	77
2.118	PidLidFax1AddressType .....	78
2.119	PidLidFax1EmailAddress .....	78
2.120	PidLidFax1OriginalDisplayName .....	78
2.121	PidLidFax1OriginalEntryId .....	79
2.122	PidLidFax2AddressType .....	79
2.123	PidLidFax2EmailAddress .....	79
2.124	PidLidFax2OriginalDisplayName .....	80
2.125	PidLidFax2OriginalEntryId .....	80
2.126	PidLidFax3AddressType .....	80
2.127	PidLidFax3EmailAddress .....	80
2.128	PidLidFax3OriginalDisplayName .....	81
2.129	PidLidFax3OriginalEntryId .....	81
2.130	PidLidFExceptionalAttendees .....	81
2.131	PidLidFExceptionalBody .....	82
2.132	PidLidFileUnder .....	82
2.133	PidLidFileUnderId .....	82
2.134	PidLidFileUnderList .....	83
2.135	PidLidFInvited .....	83
2.136	PidLidFlagRequest .....	83
2.137	PidLidFlagString .....	84
2.138	PidLidForwardInstance .....	84
2.139	PidLidForwardNotificationRecipients .....	84
2.140	PidLidFOthersAppointment .....	85
2.141	PidLidFreeBusyLocation .....	85
2.142	PidLidGlobalObjectId .....	85
2.143	PidLidHasPicture .....	86
2.144	PidLidHomeAddress .....	86
2.145	PidLidHomeAddressCountryCode .....	86
2.146	PidLidHtml .....	87
2.147	PidLidICalendarDayOfWeekMask .....	87
2.148	PidLidInboundICalStream .....	87
2.149	PidLidInfoPathFormName .....	87
2.150	PidLidInstantMessagingAddress .....	88
2.151	PidLidIntendedBusyStatus .....	88
2.152	PidLidInternetAccountName .....	88

2.153	PidLidInternetAccountStamp	89
2.154	PidLidIsContactLinked	89
2.155	PidLidIsException	89
2.156	PidLidIsRecurring	90
2.157	PidLidIsSilent	90
2.158	PidLidLinkedTaskItems	90
2.159	PidLidLocation	91
2.160	PidLidLogDocumentPosted	91
2.161	PidLidLogDocumentPrinted	91
2.162	PidLidLogDocumentRouted	92
2.163	PidLidLogDocumentSaved	92
2.164	PidLidLogDuration	92
2.165	PidLidLogEnd	93
2.166	PidLidLogFlags	93
2.167	PidLidLogStart	93
2.168	PidLidLogType	94
2.169	PidLidLogTypeDesc	94
2.170	PidLidMeetingType	94
2.171	PidLidMeetingWorkspaceUrl	94
2.172	PidLidMonthInterval	95
2.173	PidLidMonthOfYear	95
2.174	PidLidMonthOfYearMask	95
2.175	PidLidNetShowUrl	96
2.176	PidLidNoEndDateFlag	96
2.177	PidLidNonSendableBcc	96
2.178	PidLidNonSendableCc	97
2.179	PidLidNonSendableTo	97
2.180	PidLidNonSendBccTrackStatus	97
2.181	PidLidNonSendCcTrackStatus	98
2.182	PidLidNonSendToTrackStatus	98
2.183	PidLidNoteColor	99
2.184	PidLidNoteHeight	99
2.185	PidLidNoteWidth	99
2.186	PidLidNoteX	99
2.187	PidLidNoteY	100
2.188	PidLidOccurrences	100
2.189	PidLidOldLocation	100
2.190	PidLidOldRecurrenceType	101
2.191	PidLidOldWhenEndWhole	101
2.192	PidLidOldWhenStartWhole	101
2.193	PidLidOnlinePassword	102
2.194	PidLidOptionalAttendees	102
2.195	PidLidOrganizerAlias	102
2.196	PidLidOriginalStoreEntryId	103
2.197	PidLidOtherAddress	103
2.198	PidLidOtherAddressCountryCode	103
2.199	PidLidOwnerCriticalChange	104
2.200	PidLidOwnerName	104
2.201	PidLidPendingStateForSiteMailboxDocument	104
2.202	PidLidPercentComplete	105
2.203	PidLidPostalAddressId	105
2.204	PidLidPostRssChannel	105
2.205	PidLidPostRssChannelLink	106
2.206	PidLidPostRssItemGuid	106
2.207	PidLidPostRssItemHash	106
2.208	PidLidPostRssItemLink	106
2.209	PidLidPostRssItemXml	107
2.210	PidLidPostRssSubscription	107

2.211	PidLidPrivate.....	107
2.212	PidLidPromptSendUpdate .....	108
2.213	PidLidRecurrenceDuration .....	108
2.214	PidLidRecurrencePattern .....	108
2.215	PidLidRecurrenceType .....	109
2.216	PidLidRecurring .....	109
2.217	PidLidReferenceEntryId .....	109
2.218	PidLidReminderDelta .....	110
2.219	PidLidReminderFileParameter.....	110
2.220	PidLidReminderOverride .....	110
2.221	PidLidReminderPlaySound .....	111
2.222	PidLidReminderSet .....	111
2.223	PidLidReminderSignalTime .....	112
2.224	PidLidReminderTime .....	112
2.225	PidLidReminderTimeDate .....	112
2.226	PidLidReminderTimeTime .....	113
2.227	PidLidReminderType .....	113
2.228	PidLidRemoteStatus.....	113
2.229	PidLidRequiredAttendees.....	114
2.230	PidLidResourceAttendees .....	114
2.231	PidLidResponseStatus .....	114
2.232	PidLidServerProcessed .....	115
2.233	PidLidServerProcessingActions .....	115
2.234	PidLidSharingAnonymity .....	115
2.235	PidLidSharingBindingEntryId.....	116
2.236	PidLidSharingBrowseUrl .....	116
2.237	PidLidSharingCapabilities .....	116
2.238	PidLidSharingConfigurationUrl.....	117
2.239	PidLidSharingDataRangeEnd .....	117
2.240	PidLidSharingDataRangeStart .....	117
2.241	PidLidSharingDetail .....	118
2.242	PidLidSharingExtensionXml.....	118
2.243	PidLidSharingFilter .....	118
2.244	PidLidSharingFlags .....	118
2.245	PidLidSharingFlavor .....	119
2.246	PidLidSharingFolderEntryId .....	119
2.247	PidLidSharingIndexEntryId .....	119
2.248	PidLidSharingInitiatorEntryId .....	120
2.249	PidLidSharingInitiatorName .....	120
2.250	PidLidSharingInitiatorSmtip.....	120
2.251	PidLidSharingInstanceGuid .....	121
2.252	PidLidSharingLastAutoSyncTime.....	121
2.253	PidLidSharingLastSyncTime .....	121
2.254	PidLidSharingLocalComment.....	122
2.255	PidLidSharingLocalLastModificationTime .....	122
2.256	PidLidSharingLocalName .....	122
2.257	PidLidSharingLocalPath .....	123
2.258	PidLidSharingLocalStoreUid .....	123
2.259	PidLidSharingLocalType.....	123
2.260	PidLidSharingLocalUid .....	123
2.261	PidLidSharingOriginalMessageEntryId .....	124
2.262	PidLidSharingParentBindingEntryId.....	124
2.263	PidLidSharingParticipants .....	124
2.264	PidLidSharingPermissions .....	125
2.265	PidLidSharingProviderExtension .....	125
2.266	PidLidSharingProviderGuid.....	125
2.267	PidLidSharingProviderName.....	126
2.268	PidLidSharingProviderUrl .....	126



2.269	PidLidSharingRangeEnd .....	126
2.270	PidLidSharingRangeStart.....	127
2.271	PidLidSharingReciprocation.....	127
2.272	PidLidSharingRemoteByteSize.....	127
2.273	PidLidSharingRemoteComment .....	128
2.274	PidLidSharingRemoteCrc .....	128
2.275	PidLidSharingRemoteLastModificationTime .....	128
2.276	PidLidSharingRemoteMessageCount.....	128
2.277	PidLidSharingRemoteName.....	129
2.278	PidLidSharingRemotePass .....	129
2.279	PidLidSharingRemotePath.....	129
2.280	PidLidSharingRemoteStoreUid.....	130
2.281	PidLidSharingRemoteType .....	130
2.282	PidLidSharingRemoteUid .....	130
2.283	PidLidSharingRemoteUser .....	131
2.284	PidLidSharingRemoteVersion .....	131
2.285	PidLidSharingResponseTime .....	131
2.286	PidLidSharingResponseType .....	132
2.287	PidLidSharingRoamLog .....	132
2.288	PidLidSharingStart .....	132
2.289	PidLidSharingStatus .....	132
2.290	PidLidSharingStop .....	133
2.291	PidLidSharingSyncFlags .....	133
2.292	PidLidSharingSyncInterval.....	133
2.293	PidLidSharingTimeToLive.....	134
2.294	PidLidSharingTimeToLiveAuto .....	134
2.295	PidLidSharingWorkingHoursDays .....	134
2.296	PidLidSharingWorkingHoursEnd.....	135
2.297	PidLidSharingWorkingHoursStart.....	135
2.298	PidLidSharingWorkingHoursTimeZone .....	135
2.299	PidLidSideEffects.....	136
2.300	PidLidSingleBodyICal .....	136
2.301	PidLidSmartNoAttach .....	136
2.302	PidLidSpamOriginalFolder.....	137
2.303	PidLidStartRecurrenceDate .....	137
2.304	PidLidStartRecurrenceTime.....	137
2.305	PidLidTaskAcceptanceState.....	138
2.306	PidLidTaskAccepted .....	138
2.307	PidLidTaskActualEffort .....	138
2.308	PidLidTaskAssigner .....	139
2.309	PidLidTaskAssigners .....	139
2.310	PidLidTaskComplete.....	139
2.311	PidLidTaskCustomFlags .....	140
2.312	PidLidTaskDateCompleted .....	140
2.313	PidLidTaskDeadOccurrence.....	140
2.314	PidLidTaskDueDate.....	140
2.315	PidLidTaskEstimatedEffort .....	141
2.316	PidLidTaskFCreator.....	141
2.317	PidLidTaskFFixOffline .....	141
2.318	PidLidTaskFRecurring .....	142
2.319	PidLidTaskGlobalId .....	142
2.320	PidLidTaskHistory .....	142
2.321	PidLidTaskLastDelegate.....	143
2.322	PidLidTaskLastUpdate .....	143
2.323	PidLidTaskLastUser.....	143
2.324	PidLidTaskMode .....	144
2.325	PidLidTaskMultipleRecipients.....	144
2.326	PidLidTaskNoCompute .....	144

2.327	PidLidTaskOrdinal	145
2.328	PidLidTaskOwner	145
2.329	PidLidTaskOwnership	145
2.330	PidLidTaskRecurrence	146
2.331	PidLidTaskResetReminder	146
2.332	PidLidTaskRole	146
2.333	PidLidTaskStartDate	147
2.334	PidLidTaskState	147
2.335	PidLidTaskStatus	147
2.336	PidLidTaskStatusOnComplete	148
2.337	PidLidTaskUpdates	148
2.338	PidLidTaskVersion	148
2.339	PidLidTeamTask	149
2.340	PidLidTimeZone	149
2.341	PidLidTimeZoneDescription	149
2.342	PidLidTimeZoneStruct	150
2.343	PidLidToAttendeesString	150
2.344	PidLidToDoOrdinalDate	150
2.345	PidLidToDoSubOrdinal	151
2.346	PidLidToDoTitle	151
2.347	PidLidUseTnef	151
2.348	PidLidValidFlagStringProof	152
2.349	PidLidVerbResponse	152
2.350	PidLidVerbStream	152
2.351	PidLidWeddingAnniversaryLocal	153
2.352	PidLidWeekInterval	153
2.353	PidLidWhere	153
2.354	PidLidWorkAddress	154
2.355	PidLidWorkAddressCity	154
2.356	PidLidWorkAddressCountry	154
2.357	PidLidWorkAddressCountryCode	155
2.358	PidLidWorkAddressPostalCode	155
2.359	PidLidWorkAddressPostOfficeBox	155
2.360	PidLidWorkAddressState	156
2.361	PidLidWorkAddressStreet	156
2.362	PidLidYearInterval	156
2.363	PidLidYomiCompanyName	157
2.364	PidLidYomiFirstName	157
2.365	PidLidYomiLastName	157
2.366	PidNameAcceptLanguage	158
2.367	PidNameApplicationName	158
2.368	PidNameAttachmentMacContentType	158
2.369	PidNameAttachmentMacInfo	159
2.370	PidNameAudioNotes	159
2.371	PidNameAuthor	159
2.372	PidNameAutomaticSpeechRecognitionData	159
2.373	PidNameByteCount	160
2.374	PidNameCalendarAttendeeRole	160
2.375	PidNameCalendarBusystatus	160
2.376	PidNameCalendarContact	161
2.377	PidNameCalendarContactUrl	161
2.378	PidNameCalendarCreated	161
2.379	PidNameCalendarDescriptionUrl	161
2.380	PidNameCalendarDuration	162
2.381	PidNameCalendarExceptionDate	162
2.382	PidNameCalendarExceptionRule	162
2.383	PidNameCalendarGeoLatitude	163
2.384	PidNameCalendarGeoLongitude	163

2.385	PidNameCalendarInstanceType	163
2.386	PidNameCalendarIsOrganizer	164
2.387	PidNameCalendarLastModified	164
2.388	PidNameCalendarLocationUrl	164
2.389	PidNameCalendarMeetingStatus	164
2.390	PidNameCalendarMethod	165
2.391	PidNameCalendarProductId	165
2.392	PidNameCalendarRecurrenceIdRange	165
2.393	PidNameCalendarReminderOffset	166
2.394	PidNameCalendarResources	166
2.395	PidNameCalendarRsvp	166
2.396	PidNameCalendarSequence	167
2.397	PidNameCalendarTimeZone	167
2.398	PidNameCalendarTimeZoneId	167
2.399	PidNameCalendarTransparent	167
2.400	PidNameCalendarUid	168
2.401	PidNameCalendarVersion	168
2.402	PidNameCategory	168
2.403	PidNameCharacterCount	169
2.404	PidNameComments	169
2.405	PidNameCompany	169
2.406	PidNameContentBase	170
2.407	PidNameContentClass	170
2.408	PidNameContentType	170
2.409	PidNameCreateDateTimeReadOnly	171
2.410	PidNameCrossReference	171
2.411	PidNameDavId	171
2.412	PidNameDavIsCollection	171
2.413	PidNameDavIsStructuredDocument	172
2.414	PidNameDavParentName	172
2.415	PidNameDavUid	172
2.416	PidNameDocumentParts	173
2.417	PidNameEditTime	173
2.418	PidNameExchangeIntendedBusyStatus	173
2.419	PidNameExchangeJunkEmailMoveStamp	174
2.420	PidNameExchangeModifyExceptionStructure	174
2.421	PidNameExchangeNoModifyExceptions	174
2.422	PidNameExchangePatternEnd	174
2.423	PidNameExchangePatternStart	175
2.424	PidNameExchangeReminderInterval	175
2.425	PidNameExchDatabaseSchema	175
2.426	PidNameExchDataExpectedContentClass	176
2.427	PidNameExchDataSchemaCollectionReference	176
2.428	PidNameExtractedAddresses	176
2.429	PidNameExtractedContacts	177
2.430	PidNameExtractedEmails	177
2.431	PidNameExtractedMeetings	177
2.432	PidNameExtractedPhones	177
2.433	PidNameExtractedTasks	178
2.434	PidNameExtractedUrls	178
2.435	PidNameFrom	178
2.436	PidNameHeadingPairs	179
2.437	PidNameHiddenCount	179
2.438	PidNameHttpmailCalendar	179
2.439	PidNameHttpmailHtmlDescription	180
2.440	PidNameHttpmailSendMessage	180
2.441	PidNameICalendarRecurrenceDate	180
2.442	PidNameICalendarRecurrenceRule	180

2.443	PidNameInternetSubject .....	181
2.444	PidNameKeywords.....	181
2.445	PidNameLastAuthor .....	181
2.446	PidNameLastPrinted.....	182
2.447	PidNameLastSaveDateTime .....	182
2.448	PidNameLineCount .....	182
2.449	PidNameLinksDirty .....	183
2.450	PidNameLocationUrl.....	183
2.451	PidNameManager .....	183
2.452	PidNameMultimediaClipCount .....	183
2.453	PidNameNoteCount .....	184
2.454	PidNameOMSAccountGuid .....	184
2.455	PidNameOMSMobileModel.....	184
2.456	PidNameOMSScheduleTime .....	185
2.457	PidNameOMSServiceType.....	185
2.458	PidNameOMSSourceType .....	185
2.459	PidNamePageCount .....	185
2.460	PidNameParagraphCount.....	186
2.461	PidNamePhishingStamp .....	186
2.462	PidNamePresentationFormat.....	186
2.463	PidNameQuarantineOriginalSender .....	187
2.464	PidNameRevisionNumber .....	187
2.465	PidNameRightsManagementLicense .....	187
2.466	PidNameScale.....	187
2.467	PidNameSecurity.....	188
2.468	PidNameSlideCount .....	188
2.469	PidNameSubject.....	188
2.470	PidNameTemplate .....	189
2.471	PidNameThumbnail.....	189
2.472	PidNameTitle .....	189
2.473	PidNameWordCount.....	189
2.474	PidNameXCallId .....	190
2.475	PidNameXFaxNumberOfPages .....	190
2.476	PidNameXRequireProtectedPlayOnPhone .....	190
2.477	PidNameXSenderTelephoneNumber .....	191
2.478	PidNameXSharingBrowseUrl .....	191
2.479	PidNameXSharingCapabilities .....	191
2.480	PidNameXSharingConfigUrl.....	192
2.481	PidNameXSharingExendedCaps.....	192
2.482	PidNameXSharingFlavor .....	192
2.483	PidNameXSharingInstanceGuid .....	192
2.484	PidNameXSharingLocalType.....	193
2.485	PidNameXSharingProviderGuid.....	193
2.486	PidNameXSharingProviderName .....	193
2.487	PidNameXSharingProviderUrl .....	194
2.488	PidNameXSharingRemoteName.....	194
2.489	PidNameXSharingRemotePath.....	194
2.490	PidNameXSharingRemoteStoreUid.....	194
2.491	PidNameXSharingRemoteType .....	195
2.492	PidNameXSharingRemoteUid .....	195
2.493	PidNameXVoiceMessageAttachmentOrder.....	195
2.494	PidNameXVoiceMessageDuration.....	195
2.495	PidNameXVoiceMessageSenderName .....	196
2.496	PidTagAccess.....	196
2.497	PidTagAccessControlListData .....	196
2.498	PidTagAccessLevel.....	197
2.499	PidTagAccount .....	197
2.500	PidTagAdditionalRenEntryIds .....	197

2.501	PidTagAdditionalRenEntryIdsEx .....	198
2.502	PidTagAddressBookAuthorizedSenders .....	198
2.503	PidTagAddressBookContainerId .....	198
2.504	PidTagAddressBookDeliveryContentLength .....	198
2.505	PidTagAddressBookDisplayNamePrintable .....	199
2.506	PidTagAddressBookDisplayTypeExtended .....	199
2.507	PidTagAddressBookDistributionListExternalMemberCount .....	199
2.508	PidTagAddressBookDistributionListMemberCount .....	200
2.509	PidTagAddressBookDistributionListMemberSubmitAccepted .....	200
2.510	PidTagAddressBookDistributionListMemberSubmitRejected .....	200
2.511	PidTagAddressBookDistributionListRejectMessagesFromDLMembers .....	201
2.512	PidTagAddressBookEntryId .....	201
2.513	PidTagAddressBookExtensionAttribute1 .....	201
2.514	PidTagAddressBookExtensionAttribute10 .....	201
2.515	PidTagAddressBookExtensionAttribute11 .....	202
2.516	PidTagAddressBookExtensionAttribute12 .....	202
2.517	PidTagAddressBookExtensionAttribute13 .....	202
2.518	PidTagAddressBookExtensionAttribute14 .....	203
2.519	PidTagAddressBookExtensionAttribute15 .....	203
2.520	PidTagAddressBookExtensionAttribute2 .....	203
2.521	PidTagAddressBookExtensionAttribute3 .....	203
2.522	PidTagAddressBookExtensionAttribute4 .....	204
2.523	PidTagAddressBookExtensionAttribute5 .....	204
2.524	PidTagAddressBookExtensionAttribute6 .....	204
2.525	PidTagAddressBookExtensionAttribute7 .....	205
2.526	PidTagAddressBookExtensionAttribute8 .....	205
2.527	PidTagAddressBookExtensionAttribute9 .....	205
2.528	PidTagAddressBookFolderPathname .....	206
2.529	PidTagAddressBookHierarchicalChildDepartments .....	206
2.530	PidTagAddressBookHierarchicalDepartmentMembers .....	206
2.531	PidTagAddressBookHierarchicalIsHierarchicalGroup .....	206
2.532	PidTagAddressBookHierarchicalParentDepartment .....	207
2.533	PidTagAddressBookHierarchicalRootDepartment .....	207
2.534	PidTagAddressBookHierarchicalShowInDepartments .....	207
2.535	PidTagAddressBookHomeMessageDatabase .....	207
2.536	PidTagAddressBookIsMaster .....	208
2.537	PidTagAddressBookIsMemberOfDistributionList .....	208
2.538	PidTagAddressBookManageDistributionList .....	208
2.539	PidTagAddressBookManager .....	209
2.540	PidTagAddressBookManagerDistinguishedName .....	209
2.541	PidTagAddressBookMember .....	209
2.542	PidTagAddressBookMessageId .....	210
2.543	PidTagAddressBookModerationEnabled .....	210
2.544	PidTagAddressBookNetworkAddress .....	210
2.545	PidTagAddressBookObjectDistinguishedName .....	210
2.546	PidTagAddressBookObjectGuid .....	211
2.547	PidTagAddressBookOrganizationalUnitRootDistinguishedName .....	211
2.548	PidTagAddressBookOwner .....	211
2.549	PidTagAddressBookOwnerBackLink .....	212
2.550	PidTagAddressBookParentEntryId .....	212
2.551	PidTagAddressBookPhoneticCompanyName .....	212
2.552	PidTagAddressBookPhoneticDepartmentName .....	213
2.553	PidTagAddressBookPhoneticDisplayName .....	213
2.554	PidTagAddressBookPhoneticGivenName .....	213
2.555	PidTagAddressBookPhoneticSurname .....	214
2.556	PidTagAddressBookProxyAddresses .....	214
2.557	PidTagAddressBookPublicDelegates .....	214
2.558	PidTagAddressBookReports .....	215

2.559	PidTagAddressBookRoomCapacity .....	215
2.560	PidTagAddressBookRoomContainers .....	215
2.561	PidTagAddressBookRoomDescription .....	215
2.562	PidTagAddressBookSenderHintTranslations.....	216
2.563	PidTagAddressBookSeniorityIndex .....	216
2.564	PidTagAddressBookTargetAddress .....	216
2.565	PidTagAddressBookUnauthorizedSenders .....	217
2.566	PidTagAddressBookX509Certificate .....	217
2.567	PidTagAddressType .....	217
2.568	PidTagAlternateRecipientAllowed .....	217
2.569	PidTagAnr .....	218
2.570	PidTagArchiveDate .....	218
2.571	PidTagArchivePeriod .....	218
2.572	PidTagArchiveTag .....	219
2.573	PidTagAssistant.....	219
2.574	PidTagAssistantTelephoneNumber .....	219
2.575	PidTagAssociated .....	219
2.576	PidTagAttachAdditionalInformation .....	220
2.577	PidTagAttachContentBase.....	220
2.578	PidTagAttachContentId .....	220
2.579	PidTagAttachContentLocation.....	221
2.580	PidTagAttachDataBinary .....	221
2.581	PidTagAttachDataObject.....	221
2.582	PidTagAttachEncoding.....	222
2.583	PidTagAttachExtension.....	222
2.584	PidTagAttachFilename.....	222
2.585	PidTagAttachFlags .....	223
2.586	PidTagAttachLongFilename .....	223
2.587	PidTagAttachLongPathname .....	223
2.588	PidTagAttachmentContactPhoto .....	223
2.589	PidTagAttachmentFlags .....	224
2.590	PidTagAttachmentHidden .....	224
2.591	PidTagAttachmentLinkId .....	224
2.592	PidTagAttachMethod .....	225
2.593	PidTagAttachMimeTag.....	225
2.594	PidTagAttachNumber .....	225
2.595	PidTagAttachPathname .....	226
2.596	PidTagAttachPayloadClass .....	226
2.597	PidTagAttachPayloadProviderGuidString .....	226
2.598	PidTagAttachRendering .....	227
2.599	PidTagAttachSize .....	227
2.600	PidTagAttachTag .....	227
2.601	PidTagAttachTransportName.....	228
2.602	PidTagAttributeHidden .....	228
2.603	PidTagAttributeReadOnly.....	228
2.604	PidTagAutoForwardComment .....	228
2.605	PidTagAutoForwarded .....	229
2.606	PidTagAutoResponseSuppress.....	229
2.607	PidTagBirthday .....	229
2.608	PidTagBlockStatus.....	230
2.609	PidTagBody .....	230
2.610	PidTagBodyContentId .....	230
2.611	PidTagBodyContentLocation.....	231
2.612	PidTagBodyHtml.....	231
2.613	PidTagBusiness2TelephoneNumber.....	231
2.614	PidTagBusiness2TelephoneNumbers .....	232
2.615	PidTagBusinessFaxNumber .....	232
2.616	PidTagBusinessHomePage .....	232

2.617	PidTagBusinessTelephoneNumber	232
2.618	PidTagCallbackTelephoneNumber	233
2.619	PidTagCallId	233
2.620	PidTagCarTelephoneNumber	233
2.621	PidTagCdoRecurrenceid	234
2.622	PidTagChangeKey	234
2.623	PidTagChangeNumber	234
2.624	PidTagChildrensNames	235
2.625	PidTagClientActions	235
2.626	PidTagClientSubmitTime	235
2.627	PidTagCodePageId	235
2.628	PidTagComment	236
2.629	PidTagCompanyMainTelephoneNumber	236
2.630	PidTagCompanyName	236
2.631	PidTagComputerNetworkName	237
2.632	PidTagConflictEntryId	237
2.633	PidTagContainerClass	237
2.634	PidTagContainerContents	238
2.635	PidTagContainerFlags	238
2.636	PidTagContainerHierarchy	238
2.637	PidTagContentCount	239
2.638	PidTagContentFilterSpamConfidenceLevel	239
2.639	PidTagContentUnreadCount	239
2.640	PidTagConversationId	239
2.641	PidTagConversationIndex	240
2.642	PidTagConversationIndexTracking	240
2.643	PidTagConversationTopic	240
2.644	PidTagCountry	241
2.645	PidTagCreationTime	241
2.646	PidTagCreatorEntryId	241
2.647	PidTagCreatorName	242
2.648	PidTagCustomerId	242
2.649	PidTagDamBackPatched	242
2.650	PidTagDamOriginalEntryId	242
2.651	PidTagDefaultPostMessageClass	243
2.652	PidTagDeferredActionMessageOriginalEntryId	243
2.653	PidTagDeferredDeliveryTime	243
2.654	PidTagDeferredSendNumber	244
2.655	PidTagDeferredSendTime	244
2.656	PidTagDeferredSendUnits	244
2.657	PidTagDelegatedByRule	244
2.658	PidTagDelegateFlags	245
2.659	PidTagDeleteAfterSubmit	245
2.660	PidTagDeletedCountTotal	245
2.661	PidTagDeletedOn	246
2.662	PidTagDeliverTime	246
2.663	PidTagDepartmentName	246
2.664	PidTagDepth	246
2.665	PidTagDisplayBcc	247
2.666	PidTagDisplayCc	247
2.667	PidTagDisplayName	247
2.668	PidTagDisplayNamePrefix	248
2.669	PidTagDisplayTo	248
2.670	PidTagDisplayType	248
2.671	PidTagDisplayTypeEx	249
2.672	PidTagEmailAddress	249
2.673	PidTagEndDate	249
2.674	PidTagEntryId	250

2.675	PidTagExceptionEndTime.....	250
2.676	PidTagExceptionReplaceTime.....	250
2.677	PidTagExceptionStartTime.....	251
2.678	PidTagExchangeNTSecurityDescriptor.....	251
2.679	PidTagExpiryNumber.....	251
2.680	PidTagExpiryTime.....	251
2.681	PidTagExpiryUnits.....	252
2.682	PidTagExtendedFolderFlags.....	252
2.683	PidTagExtendedRuleMessageActions.....	252
2.684	PidTagExtendedRuleMessageCondition.....	253
2.685	PidTagExtendedRuleSizeLimit.....	253
2.686	PidTagFaxNumberOfPages.....	253
2.687	PidTagFlagCompleteTime.....	254
2.688	PidTagFlagStatus.....	254
2.689	PidTagFlatUrlName.....	254
2.690	PidTagFolderAssociatedContents.....	254
2.691	PidTagFolderId.....	255
2.692	PidTagFolderFlags.....	255
2.693	PidTagFolderType.....	255
2.694	PidTagFollowupIcon.....	256
2.695	PidTagFreeBusyCountMonths.....	256
2.696	PidTagFreeBusyEntryIds.....	256
2.697	PidTagFreeBusyMessageEmailAddress.....	257
2.698	PidTagFreeBusyPublishEnd.....	257
2.699	PidTagFreeBusyPublishStart.....	257
2.700	PidTagFreeBusyRangeTimestamp.....	257
2.701	PidTagFtpSite.....	258
2.702	PidTagGatewayNeedsToRefresh.....	258
2.703	PidTagGender.....	258
2.704	PidTagGeneration.....	258
2.705	PidTagGivenName.....	259
2.706	PidTagGovernmentIdNumber.....	259
2.707	PidTagHasAttachments.....	259
2.708	PidTagHasDeferredActionMessages.....	260
2.709	PidTagHasNamedProperties.....	260
2.710	PidTagHasRules.....	260
2.711	PidTagHierarchyChangeNumber.....	260
2.712	PidTagHierRev.....	261
2.713	PidTagHobbies.....	261
2.714	PidTagHome2TelephoneNumber.....	261
2.715	PidTagHome2TelephoneNumbers.....	262
2.716	PidTagHomeAddressCity.....	262
2.717	PidTagHomeAddressCountry.....	262
2.718	PidTagHomeAddressPostalCode.....	263
2.719	PidTagHomeAddressPostOfficeBox.....	263
2.720	PidTagHomeAddressStateOrProvince.....	263
2.721	PidTagHomeAddressStreet.....	264
2.722	PidTagHomeFaxNumber.....	264
2.723	PidTagHomeTelephoneNumber.....	264
2.724	PidTagHtml.....	264
2.725	PidTagICalendarEndTime.....	265
2.726	PidTagICalendarReminderNextTime.....	265
2.727	PidTagICalendarStartTime.....	265
2.728	PidTagIconIndex.....	266
2.729	PidTagImportance.....	266
2.730	PidTagInConflict.....	266
2.731	PidTagInitialDetailsPane.....	267
2.732	PidTagInitials.....	267



2.733	PidTagInReplyToId .....	267
2.734	PidTagInstanceKey .....	267
2.735	PidTagInstanceNum .....	268
2.736	PidTagInstID .....	268
2.737	PidTagInternetCodepage .....	268
2.738	PidTagInternetMailOverrideFormat .....	269
2.739	PidTagInternetMessageId .....	269
2.740	PidTagInternetReferences .....	269
2.741	PidTagIpmAppointmentEntryId .....	270
2.742	PidTagIpmContactEntryId .....	270
2.743	PidTagIpmDraftsEntryId .....	270
2.744	PidTagIpmJournalEntryId .....	270
2.745	PidTagIpmNoteEntryId .....	271
2.746	PidTagIpmTaskEntryId .....	271
2.747	PidTagIsdnNumber .....	271
2.748	PidTagJunkAddRecipientsToSafeSendersList .....	272
2.749	PidTagJunkIncludeContacts .....	272
2.750	PidTagJunkPermanentlyDelete .....	272
2.751	PidTagJunkPhishingEnableLinks .....	272
2.752	PidTagJunkThreshold .....	273
2.753	PidTagKeyword .....	273
2.754	PidTagLanguage .....	273
2.755	PidTagLastModificationTime .....	274
2.756	PidTagLastModifierEntryId .....	274
2.757	PidTagLastModifierName .....	274
2.758	PidTagLastVerbExecuted .....	275
2.759	PidTagLastVerbExecutionTime .....	275
2.760	PidTagListHelp .....	275
2.761	PidTagListSubscribe .....	276
2.762	PidTagListUnsubscribe .....	276
2.763	PidTagLocalCommitTime .....	276
2.764	PidTagLocalCommitTimeMax .....	276
2.765	PidTagLocaleId .....	277
2.766	PidTagLocality .....	277
2.767	PidTagLocation .....	277
2.768	PidTagMailboxOwnerEntryId .....	278
2.769	PidTagMailboxOwnerName .....	278
2.770	PidTagManagerName .....	278
2.771	PidTagMappingSignature .....	279
2.772	PidTagMaximumSubmitMessageSize .....	279
2.773	PidTagMemberId .....	279
2.774	PidTagMemberName .....	279
2.775	PidTagMemberRights .....	280
2.776	PidTagMessageAttachments .....	280
2.777	PidTagMessageCcMe .....	280
2.778	PidTagMessageClass .....	281
2.779	PidTagMessageCodepage .....	281
2.780	PidTagMessageDeliveryTime .....	281
2.781	PidTagMessageEditorFormat .....	282
2.782	PidTagMessageFlags .....	282
2.783	PidTagMessageHandlingSystemCommonName .....	282
2.784	PidTagMessageLocaleId .....	283
2.785	PidTagMessageRecipientMe .....	283
2.786	PidTagMessageRecipients .....	283
2.787	PidTagMessageSize .....	283
2.788	PidTagMessageSizeExtended .....	284
2.789	PidTagMessageStatus .....	284
2.790	PidTagMessageSubmissionId .....	284

2.791	PidTagMessageToMe	285
2.792	PidTagMid	285
2.793	PidTagMiddleName	285
2.794	PidTagMimeSkeleton	286
2.795	PidTagMobileTelephoneNumber	286
2.796	PidTagNativeBody	286
2.797	PidTagNextSendAcct	287
2.798	PidTagNickname	287
2.799	PidTagNonDeliveryReportDiagCode	287
2.800	PidTagNonDeliveryReportReasonCode	287
2.801	PidTagNonDeliveryReportStatusCode	288
2.802	PidTagNonReceiptNotificationRequested	288
2.803	PidTagNormalizedSubject	288
2.804	PidTagObjectType	289
2.805	PidTagOfficeLocation	289
2.806	PidTagOfflineAddressBookContainerGuid	289
2.807	PidTagOfflineAddressBookDistinguishedName	290
2.808	PidTagOfflineAddressBookMessageClass	290
2.809	PidTagOfflineAddressBookName	290
2.810	PidTagOfflineAddressBookSequence	290
2.811	PidTagOfflineAddressBookTruncatedProperties	291
2.812	PidTagOrdinalMost	291
2.813	PidTagOrganizationalIdNumber	291
2.814	PidTagOriginalAuthorEntryId	291
2.815	PidTagOriginalAuthorName	292
2.816	PidTagOriginalDeliveryTime	292
2.817	PidTagOriginalDisplayBcc	292
2.818	PidTagOriginalDisplayCc	293
2.819	PidTagOriginalDisplayTo	293
2.820	PidTagOriginalEntryId	293
2.821	PidTagOriginalMessageClass	294
2.822	PidTagOriginalMessageId	294
2.823	PidTagOriginalSenderAddressType	294
2.824	PidTagOriginalSenderEmailAddress	294
2.825	PidTagOriginalSenderEntryId	295
2.826	PidTagOriginalSenderName	295
2.827	PidTagOriginalSenderSearchKey	295
2.828	PidTagOriginalSensitivity	296
2.829	PidTagOriginalSentRepresentingAddressType	296
2.830	PidTagOriginalSentRepresentingEmailAddress	296
2.831	PidTagOriginalSentRepresentingEntryId	297
2.832	PidTagOriginalSentRepresentingName	297
2.833	PidTagOriginalSentRepresentingSearchKey	297
2.834	PidTagOriginalSubject	297
2.835	PidTagOriginalSubmitTime	298
2.836	PidTagOriginatorDeliveryReportRequested	298
2.837	PidTagOriginatorNonDeliveryReportRequested	298
2.838	PidTagOscSyncEnabled	299
2.839	PidTagOtherAddressCity	299
2.840	PidTagOtherAddressCountry	299
2.841	PidTagOtherAddressPostalCode	300
2.842	PidTagOtherAddressPostOfficeBox	300
2.843	PidTagOtherAddressStateOrProvince	300
2.844	PidTagOtherAddressStreet	301
2.845	PidTagOtherTelephoneNumber	301
2.846	PidTagOutOfOfficeState	301
2.847	PidTagOwnerAppointmentId	301
2.848	PidTagPagerTelephoneNumber	302

2.849	PidTagParentEntryId	302
2.850	PidTagParentFolderId	302
2.851	PidTagParentKey	303
2.852	PidTagParentSourceKey	303
2.853	PidTagPersonalHomePage	303
2.854	PidTagPolicyTag	303
2.855	PidTagPostalAddress	304
2.856	PidTagPostalCode	304
2.857	PidTagPostOfficeBox	304
2.858	PidTagPredecessorChangeList	305
2.859	PidTagPrimaryFaxNumber	305
2.860	PidTagPrimarySendAccount	305
2.861	PidTagPrimaryTelephoneNumber	306
2.862	PidTagPriority	306
2.863	PidTagProcessed	306
2.864	PidTagProfession	307
2.865	PidTagProhibitReceiveQuota	307
2.866	PidTagProhibitSendQuota	307
2.867	PidTagPurportedSenderDomain	307
2.868	PidTagRadioTelephoneNumber	308
2.869	PidTagRead	308
2.870	PidTagReadReceiptAddressType	308
2.871	PidTagReadReceiptEmailAddress	309
2.872	PidTagReadReceiptEntryId	309
2.873	PidTagReadReceiptName	309
2.874	PidTagReadReceiptRequested	309
2.875	PidTagReadReceiptSearchKey	310
2.876	PidTagReadReceiptSmtpAddress	310
2.877	PidTagReceiptTime	310
2.878	PidTagReceivedByAddressType	311
2.879	PidTagReceivedByEmailAddress	311
2.880	PidTagReceivedByEntryId	311
2.881	PidTagReceivedByName	312
2.882	PidTagReceivedBySearchKey	312
2.883	PidTagReceivedBySmtpAddress	312
2.884	PidTagReceivedRepresentingAddressType	312
2.885	PidTagReceivedRepresentingEmailAddress	313
2.886	PidTagReceivedRepresentingEntryId	313
2.887	PidTagReceivedRepresentingName	313
2.888	PidTagReceivedRepresentingSearchKey	314
2.889	PidTagReceivedRepresentingSmtpAddress	314
2.890	PidTagRecipientDisplayName	314
2.891	PidTagRecipientEntryId	314
2.892	PidTagRecipientFlags	315
2.893	PidTagRecipientOrder	315
2.894	PidTagRecipientProposed	315
2.895	PidTagRecipientProposedEndTime	316
2.896	PidTagRecipientProposedStartTime	316
2.897	PidTagRecipientReassignmentProhibited	316
2.898	PidTagRecipientTrackStatus	316
2.899	PidTagRecipientTrackStatusTime	317
2.900	PidTagRecipientType	317
2.901	PidTagRecordKey	317
2.902	PidTagReferredByName	318
2.903	PidTagRemindersOnlineEntryId	318
2.904	PidTagRemoteMessageTransferAgent	318
2.905	PidTagRenderingPosition	318
2.906	PidTagReplyRecipientEntries	319

2.907	PidTagReplyRecipientNames .....	319
2.908	PidTagReplyRequested .....	319
2.909	PidTagReplyTemplateId .....	320
2.910	PidTagReplyTime .....	320
2.911	PidTagReportDisposition .....	320
2.912	PidTagReportDispositionMode .....	321
2.913	PidTagReportEntryId .....	321
2.914	PidTagReportingMessageTransferAgent .....	321
2.915	PidTagReportName .....	321
2.916	PidTagReportSearchKey .....	322
2.917	PidTagReportTag .....	322
2.918	PidTagReportText .....	322
2.919	PidTagReportTime .....	323
2.920	PidTagResolveMethod .....	323
2.921	PidTagResponseRequested .....	323
2.922	PidTagResponsibility .....	323
2.923	PidTagRetentionDate .....	324
2.924	PidTagRetentionFlags .....	324
2.925	PidTagRetentionPeriod .....	324
2.926	PidTagRights .....	325
2.927	PidTagRoamingDatatypes .....	325
2.928	PidTagRoamingDictionary .....	325
2.929	PidTagRoamingXmlStream .....	325
2.930	PidTagRowid .....	326
2.931	PidTagRowType .....	326
2.932	PidTagRtfCompressed .....	326
2.933	PidTagRtfInSync .....	327
2.934	PidTagRuleActionNumber .....	327
2.935	PidTagRuleActions .....	327
2.936	PidTagRuleActionType .....	327
2.937	PidTagRuleCondition .....	328
2.938	PidTagRuleError .....	328
2.939	PidTagRuleFolderEntryId .....	328
2.940	PidTagRuleId .....	329
2.941	PidTagRuleIds .....	329
2.942	PidTagRuleLevel .....	329
2.943	PidTagRuleMessageLevel .....	329
2.944	PidTagRuleMessageName .....	330
2.945	PidTagRuleMessageProvider .....	330
2.946	PidTagRuleMessageProviderData .....	330
2.947	PidTagRuleMessageSequence .....	331
2.948	PidTagRuleMessageState .....	331
2.949	PidTagRuleMessageUserFlags .....	331
2.950	PidTagRuleName .....	332
2.951	PidTagRuleProvider .....	332
2.952	PidTagRuleProviderData .....	332
2.953	PidTagRuleSequence .....	332
2.954	PidTagRuleState .....	333
2.955	PidTagRuleUserFlags .....	333
2.956	PidTagRwRulesStream .....	333
2.957	PidTagScheduleInfoAppointmentTombstone .....	334
2.958	PidTagScheduleInfoAutoAcceptAppointments .....	334
2.959	PidTagScheduleInfoDelegateEntryIds .....	334
2.960	PidTagScheduleInfoDelegateNames .....	334
2.961	PidTagScheduleInfoDelegateNamesW .....	335
2.962	PidTagScheduleInfoDelegatorWantsCopy .....	335
2.963	PidTagScheduleInfoDelegatorWantsInfo .....	335
2.964	PidTagScheduleInfoDisallowOverlappingAppts .....	336

2.965	PidTagScheduleInfoDisallowRecurringAppts .....	336
2.966	PidTagScheduleInfoDontMailDelegates .....	336
2.967	PidTagScheduleInfoFreeBusy .....	336
2.968	PidTagScheduleInfoFreeBusyAway .....	337
2.969	PidTagScheduleInfoFreeBusyBusy .....	337
2.970	PidTagScheduleInfoFreeBusyMerged .....	337
2.971	PidTagScheduleInfoFreeBusyTentative .....	338
2.972	PidTagScheduleInfoMonthsAway .....	338
2.973	PidTagScheduleInfoMonthsBusy .....	338
2.974	PidTagScheduleInfoMonthsMerged .....	338
2.975	PidTagScheduleInfoMonthsTentative .....	339
2.976	PidTagScheduleInfoResourceType .....	339
2.977	PidTagSchedulePlusFreeBusyEntryId .....	339
2.978	PidTagScriptData .....	340
2.979	PidTagSearchFolderDefinition .....	340
2.980	PidTagSearchFolderEfpFlags .....	340
2.981	PidTagSearchFolderExpiration .....	340
2.982	PidTagSearchFolderId .....	341
2.983	PidTagSearchFolderLastUsed .....	341
2.984	PidTagSearchFolderRecreateInfo .....	341
2.985	PidTagSearchFolderStorageType .....	341
2.986	PidTagSearchFolderTag .....	342
2.987	PidTagSearchFolderTemplateId .....	342
2.988	PidTagSearchKey .....	342
2.989	PidTagSecurityDescriptorAsXml .....	343
2.990	PidTagSelectable .....	343
2.991	PidTagSenderAddressType .....	343
2.992	PidTagSenderEmailAddress .....	344
2.993	PidTagSenderEntryId .....	344
2.994	PidTagSenderIdStatus .....	344
2.995	PidTagSenderName .....	345
2.996	PidTagSenderSearchKey .....	345
2.997	PidTagSenderSmtpAddress .....	345
2.998	PidTagSenderTelephoneNumber .....	346
2.999	PidTagSendInternetEncoding .....	346
2.1000	PidTagSendRichInfo .....	346
2.1001	PidTagSensitivity .....	346
2.1002	PidTagSentMailSvrEID .....	347
2.1003	PidTagSentRepresentingAddressType .....	347
2.1004	PidTagSentRepresentingEmailAddress .....	347
2.1005	PidTagSentRepresentingEntryId .....	348
2.1006	PidTagSentRepresentingFlags .....	348
2.1007	PidTagSentRepresentingName .....	348
2.1008	PidTagSentRepresentingSearchKey .....	349
2.1009	PidTagSentRepresentingSmtpAddress .....	349
2.1010	PidTagSmtpAddress .....	349
2.1011	PidTagSortLocaleId .....	350
2.1012	PidTagSourceKey .....	350
2.1013	PidTagSpokenName .....	350
2.1014	PidTagSpouseName .....	351
2.1015	PidTagStartDate .....	351
2.1016	PidTagStartDateEtc .....	351
2.1017	PidTagStateOrProvince .....	351
2.1018	PidTagStoreEntryId .....	352
2.1019	PidTagStoreState .....	352
2.1020	PidTagStoreSupportMask .....	352
2.1021	PidTagStreetAddress .....	353
2.1022	PidTagSubfolders .....	353

2.1023	PidTagSubject.....	353
2.1024	PidTagSubjectPrefix.....	354
2.1025	PidTagSupplementaryInfo .....	354
2.1026	PidTagSurname.....	354
2.1027	PidTagSwappedToDoData.....	355
2.1028	PidTagSwappedToDoStore.....	355
2.1029	PidTagTargetEntryId.....	355
2.1030	PidTagTelecommunicationsDeviceForDeafTelephoneNumber .....	355
2.1031	PidTagTelexNumber.....	356
2.1032	PidTagTemplateData.....	356
2.1033	PidTagTemplateid.....	356
2.1034	PidTagTextAttachmentCharset .....	357
2.1035	PidTagThumbnailPhoto.....	357
2.1036	PidTagTitle .....	357
2.1037	PidTagTnefCorrelationKey .....	358
2.1038	PidTagToDoItemFlags .....	358
2.1039	PidTagTransmittableDisplayName.....	358
2.1040	PidTagTransportMessageHeaders .....	359
2.1041	PidTagTrustSender .....	359
2.1042	PidTagUserCertificate.....	359
2.1043	PidTagUserEntryId .....	359
2.1044	PidTagUserX509Certificate .....	360
2.1045	PidTagViewDescriptorBinary .....	360
2.1046	PidTagViewDescriptorName .....	360
2.1047	PidTagViewDescriptorStrings .....	361
2.1048	PidTagViewDescriptorVersion.....	361
2.1049	PidTagVoiceMessageAttachmentOrder.....	361
2.1050	PidTagVoiceMessageDuration.....	361
2.1051	PidTagVoiceMessageSenderName.....	362
2.1052	PidTagWeddingAnniversary .....	362
2.1053	PidTagWlinkAddressBookEID .....	362
2.1054	PidTagWlinkAddressBookStoreEID .....	363
2.1055	PidTagWlinkCalendarColor .....	363
2.1056	PidTagWlinkClientID .....	363
2.1057	PidTagWlinkEntryId .....	363
2.1058	PidTagWlinkFlags .....	364
2.1059	PidTagWlinkFolderType .....	364
2.1060	PidTagWlinkGroupClsid .....	364
2.1061	PidTagWlinkGroupHeaderID.....	364
2.1062	PidTagWlinkGroupName .....	365
2.1063	PidTagWlinkOrdinal .....	365
2.1064	PidTagWlinkRecordKey.....	365
2.1065	PidTagWlinkROGroupType .....	366
2.1066	PidTagWlinkSaveStamp .....	366
2.1067	PidTagWlinkSection .....	366
2.1068	PidTagWlinkStoreEntryId.....	366
2.1069	PidTagWlinkType.....	367
<b>3</b>	<b>Structure Examples .....</b>	<b>368</b>
<b>4</b>	<b>Security.....</b>	<b>369</b>
4.1	Security Considerations for Implementers .....	369
4.2	Index of Security Fields .....	369
<b>5</b>	<b>Appendix A: Product Behavior .....</b>	<b>370</b>
<b>6</b>	<b>Change Tracking.....</b>	<b>371</b>
<b>7</b>	<b>Index.....</b>	<b>373</b>



# 1 Introduction

The Exchange Server Protocols Master Property List provides implementers with a single source of information about all the properties that are described by the specifications that comprise the Exchange Server Protocols documentation. If a property is not described by the specifications included in the Exchange Server Protocols documentation, it is not included in this document.

The criteria for including a property in the Exchange Server Protocols documentation are that it is set by a client in order to affect server behavior, or that it is set by a server in order to affect client behavior. Properties that are merely stored by the server on behalf of the client, or generated by the server for its own use and ignored by the client, are not necessarily documented. As a result, the properties that are included in the Exchange Server Protocols documentation, and therefore this document, are the critical **Message object** properties used for communication between clients and servers.

This document provides implementers with a convenient catalog of all these critical properties, a source of navigation to the individual technical specifications that describe these properties in detail, and a resource for additional helpful property information that is unique to this document.

Sections 1.7 and 2 of this specification are normative. All other sections and examples in this specification are informative.

## 1.1 Glossary

This document uses the following terms:

**8.3 name:** A file name string restricted in length to 12 characters that includes a base name of up to eight characters, one character for a period, and up to three characters for a file name extension. For more information on 8.3 file names, see [\[MS-CIFS\]](#) section 2.2.1.1.1.

**action:** A discrete operation that is executed on an incoming **Message object** when all conditions in the same **rule** are TRUE. A rule contains one or more actions.

**address book container:** An **Address Book object** that describes an **address list**.

**Address Book object:** An entity in an address book that contains a set of attributes, each attribute with a set of associated values.

**address list:** A collection of distinct **Address Book objects**.

**address type:** An identifier for the type of email address, such as **SMTP** and EX.

**alias:** An alternate name that can be used to reference an object or element.

**ambiguous name resolution (ANR):** A search algorithm that permits a client to search multiple naming-related attributes (2) on objects by way of a single clause of the form "(anr=value)" in a Lightweight Directory Access Protocol (LDAP) search filter. This permits a client to query for an object when the client possesses some identifying material related to the object but does not know which attribute of the object contains that identifying material.

**Appointment object:** A **Calendar object** that has an organizer but no attendees.

**archive tag:** An element that contains information about the archive policy of a **Message object** or folder.

**Attachment object:** A set of properties that represents a file, **Message object**, or structured storage that is attached to a Message object and is visible through the attachments table for a Message object.



**Augmented Backus-Naur Form (ABNF):** A modified version of Backus-Naur Form (BNF), commonly used by Internet specifications. ABNF notation balances compactness and simplicity with reasonable representational power. ABNF differs from standard BNF in its definitions and uses of naming rules, repetition, alternatives, order-independence, and value ranges. For more information, see [\[RFC5234\]](#).

**blind carbon copy (Bcc) recipient:** An addressee on a **Message object** that is not visible to recipients of the Message object.

**body part:** A part of an Internet message, as described in [\[RFC2045\]](#).

**calendar:** A date range that shows availability, **meetings**, and appointments for one or more users or **resources**. See also **Calendar object**.

**Calendar folder:** A **Folder object** that contains **Calendar objects**.

**Calendar object:** A **Message object** that represents an event, which can be a one-time event or a recurring event. The Calendar object includes properties that specify event details such as description, organizer, date and time, and status.

**carbon copy (Cc) recipient:** An address on a **Message object** that is visible to recipients of the Message object but is not necessarily expected to take any action.

**class:** User-defined binary data that is associated with a key.

**common name (CN):** A string attribute of a certificate (1) that is one component of a **distinguished name (DN)**. In Microsoft Enterprise uses, a CN must be unique within the forest where it is defined and any forests that share trust with the defining forest. The website or email address of the certificate owner is often used as a common name. Client applications often refer to a certification authority (CA) by the CN of its signing certificate.

**contact:** A person, company, or other entity that is stored in a directory and is associated with one or more unique identifiers and attributes (2), such as an Internet message address or login name.

**contents table:** A Table object whose rows represent the **Message objects** that are contained in a **Folder object**.

**conversation:** A single representation of a send/response series of email messages. A conversation appears in the Inbox as one unit and allows the user to view and read the series of related email messages in a single effort.

**conversation action:** A limited set of actions that a user applies to all **Message objects** that have the same PidTagConversationId value. The action is applied to all Message objects that are currently in the store or are delivered in the future.

**Coordinated Universal Time (UTC):** A high-precision atomic time standard that approximately tracks Universal Time (UT). It is the basis for legal, civil time all over the Earth. Time zones around the world are expressed as positive and negative offsets from UTC. In this role, it is also referred to as Zulu time (Z) and Greenwich Mean Time (GMT). In these specifications, all references to UTC refer to the time at UTC-0 (or GMT).

**counter proposal:** A request that an attendee sends to an **organizer** when requesting a change to the date or time of a meeting.

**cyclic redundancy check (CRC):** An algorithm used to produce a checksum (a small, fixed number of bits) against a block of data, such as a packet of network traffic or a block of a computer file. The CRC is a broad class of functions used to detect errors after transmission or storage. A CRC is designed to catch random errors, as opposed to intentional errors. If errors

might be introduced by a motivated and intelligent adversary, a cryptographic hash function should be used instead.

**Deferred Action Message (DAM):** A hidden message indicating to a client that it needs to execute one or more **rules** on another user-visible message in the store.

**delegate:** A user or resource that has permissions to act on behalf of another user or resource.

**delivery receipt:** A report message that is generated and sent by a client or server to the sender of a message or another designated recipient when an email message is received by an intended recipient.

**Department object:** An **Address Book object** that describes a department within an organization.

**departmental group:** A **distribution list** that describes a department within an organization.

**display name:** A text string that is used to identify a principal or other object in the user interface. Also referred to as title.

**display template:** A template that describes how to display or allow a user to modify information about an **Address Book object**.

**distinguished name (DN):** A name that uniquely identifies an object by using the relative distinguished name (RDN) for the object, and the names of container objects and domains that contain the object. The distinguished name (DN) identifies the object and its location in a tree.

**distribution list:** A collection of users, computers, contacts, or other groups that is used only for email distribution, and addressed as a single recipient.

**Document object:** A **Message object** that represents a single file, such as a document generated by a word-processing application. The Message object contains the file as an **Attachment object** and includes additional properties to describe the file.

**domain:** A set of users and computers sharing a common namespace and management infrastructure. At least one computer member of the set must act as a domain controller (DC) and host a member list that identifies all members of the domain, as well as optionally hosting the Active Directory service. The domain controller provides authentication (2) of members, creating a unit of trust for its members. Each domain has an identifier that is shared among its members. For more information, see [\[MS-AUTHSOD\]](#) section 1.1.1.5 and [\[MS-ADTS\]](#).

**double-byte character set (DBCS):** A character set (1) that can use more than one byte to represent a single character. A DBCS includes some characters that consist of 1 byte and some characters that consist of 2 bytes. Languages such as Chinese, Japanese, and Korean use DBCS.

**Email object:** A **Message object** that represents an email message in a message store and adheres to the property descriptions that are described in [\[MS-OXOMSG\]](#).

**entry ID:** See **EntryID**.

**EntryID:** A sequence of bytes that is used to identify and access an object.

**Exception Embedded Message object:** An Embedded Message object that contains the changes for an Exception object.

**Exception object:** An instance of a **recurring series** that differs from the rest of the recurring series, for example by start time.

**File Transfer Protocol (FTP):** A member of the TCP/IP suite of protocols that is used to copy files between two computers on the Internet if both computers support their respective FTP roles. One computer is an FTP client and the other is an FTP server.

**flags:** A set of values used to configure or report options or settings.

**folder associated information (FAI):** A collection of **Message objects** that are stored in a Folder object and are typically hidden from view by email applications. An FAI Message object is used to store a variety of settings and auxiliary data, including forms, views, calendar options, favorites, and category lists.

**Folder object:** A messaging construct that is typically used to organize data into a hierarchy of objects containing Message objects and **folder associated information (FAI)** Message objects.

**free/busy status:** A property of an appointment that indicates how an appointment on the **calendar** of an attendee or resource affects their availability.

**Global Address List (GAL):** An **address list** that conceptually represents the default address list for an address book.

**globally unique identifier (GUID):** A term used interchangeably with universally unique identifier (UUID) in Microsoft protocol technical documents (TDs). Interchanging the usage of these terms does not imply or require a specific algorithm or mechanism to generate the value. Specifically, the use of this term does not imply or require that the algorithms described in [\[RFC4122\]](#) or [\[C706\]](#) must be used for generating the **GUID**. See also universally unique identifier (UUID).

**group header:** A **navigation shortcut** that groups other navigation shortcuts.

**Hypertext Markup Language (HTML):** An application of the Standard Generalized Markup Language (SGML) that uses tags to mark elements in a document, as described in [\[HTML\]](#).

**Hypertext Transfer Protocol (HTTP):** An application-level protocol for distributed, collaborative, hypermedia information systems (text, graphic images, sound, video, and other multimedia files) on the World Wide Web.

**instance:** A unique publication of data for a category (4). It enables a publisher to publish data for the same category multiple times. An example is a publisher who uses two different endpoints (5) to publish data. These endpoints can publish the same category. However, each endpoint requires a different instance number to be considered a distinct publication by the server (2). An instance number is provided by the publishing client.

**Integrated Services Digital Network (ISDN):** A high-speed digital technology that uses existing telephone lines to provide Internet access and digital network services.

**Journal object:** A **Message object** that represents an entry in a journal or log and adheres to the property descriptions that are described in in [\[MS-OXOJRN\]](#).

**locale:** A collection of rules and data that are specific to a language and a geographical area. A locale can include information about sorting rules, date and time formatting, numeric and monetary conventions, and character classification.

**Logon object:** A **Server object** that provides access to a private **mailbox** or a **public folder**. A client obtains a Logon object by issuing a RopLogon remote operation (ROP) to a server.

**long ID (LID):** A 32-bit quantity that, in combination with a GUID, defines a **named property**.

**mail tip:** A note that is presented to the author of a message when the author is composing the message. A mail tip provides information about the recipients of a message and issues that might impact delivery of the message, such as moderation or delivery restrictions.

**mail user:** An **Address Book object** that represents a person or entity that can receive deliverable messages.

**mailbox:** A **message store** that contains email, calendar items, and other **Message objects** for a single recipient.

**meeting:** An event with attendees.

**Meeting object:** A **Calendar object** that has both an organizer and attendees.

**meeting request:** An instance of a **Meeting Request object**.

**Meeting Request object:** A **Message object** that represents an invitation from the meeting organizer to an attendee.

**Meeting Response object:** A **Message object** that represents an attendee's response to a meeting organizer's invitation. The response indicates whether the attendee accepted, tentatively accepted, or declined the meeting request. The response can include a proposed new date or time for the meeting.

**Meeting Update object:** A **Message object** that represents a meeting organizer's changes to a previously scheduled meeting. The update is categorized as either a full update or an informational update.

**Meeting Workspace:** A website that is created by using the Meetings Web Services protocol, as described in [\[MS-MEETS\]](#). It can host documents, discussions, and other information about a meeting.

**meeting-related object:** A **Message object** that represents a relay of information between a meeting organizer and an attendee. It can be any of the following: **Meeting Request object**, **Meeting Update object**, Meeting Cancellation object, or **Meeting Response object**.

**message body:** The main message text of an email message. A few properties of a **Message object** represent its message body, with one property containing the text itself and others defining its code page and its relationship to alternative body formats.

**message class:** A property that loosely defines the type of a message, contact, or other Personal Information Manager (PIM) object in a mailbox.

**Message object:** A set of properties that represents an email message, appointment, contact, or other type of personal-information-management object. In addition to its own properties, a Message object contains recipient properties that represent the addressees to which it is addressed, and an attachments table that represents any files and other Message objects that are attached to it.

**message store:** A unit of containment for a single hierarchy of Folder objects, such as a mailbox or public folders.

**Messaging Application Programming Interface (MAPI):** A messaging architecture that enables multiple applications to interact with multiple messaging systems across a variety of hardware platforms.

**messaging object:** An object that exists in a **mailbox**. It can be only a **Folder object** or a **Message object**.

**MIME message:** A message that is as described in [RFC2045], [\[RFC2046\]](#), and [\[RFC2047\]](#).

**MIME part:** A message part that is as described in [RFC2045], [RFC2046], and [RFC2047].

**Multipurpose Internet Mail Extensions (MIME):** A set of extensions that redefines and expands support for various types of content in email messages, as described in [RFC2045], [RFC2046], and [RFC2047].

**name service provider interface (NSPI):** A method of performing address-book-related operations on Active Directory.

**named property:** A property that is identified by both a GUID and either a string name or a 32-bit identifier.

**navigation shortcut:** An object that contains identifying information to locate a folder in a message database or an object that groups other navigation shortcuts.

**non-Unicode:** A character set (1) that has a restricted set of glyphs, such as Shift\_JIS or ISO-2022-JP.

**Note object:** A **Message object** that represents a simple text note in a messaging store and that adheres to the property descriptions that are described in [\[MS-OXONOTE\]](#). A Note object functions as an electronic equivalent of a paper sticky note.

**offline address book (OAB):** A collection of **address lists** that are stored in a format that a client can save and use locally.

**optional attendee:** An attendee of an event whom the organizer lists as an optional participant.

**organizer:** The owner or creator of a **meeting** or appointment.

**orphan instance:** An instance of an event that is in a **recurring series** and is in a Calendar folder without the recurring series. For all practical purposes, this is a single instance.

**Out of Office (OOF):** One of the possible values for the **free/busy status** on an appointment. It indicates that the user will not be in the office during the appointment.

**Permanent Entry ID:** A property of an **Address Book object** that can be used to uniquely identify the object.

**permission:** A rule that is associated with an object and that regulates which users can gain access to the object and in what manner. See also rights.

**phishing:** The luring of sensitive information, such as passwords or other personal information, from a recipient by masquerading as someone who is trustworthy and has a real need for such information.

**plain text:** Text that does not have markup. See also plain text message body.

**primary recipient:** A person for whom a message is directly intended.

**property ID:** A 16-bit numeric identifier of a specific attribute (1). A property ID does not include any **property type** information.

**property name:** A string that, in combination with a **property set**, identifies a **named property**.

**property set:** A set of attributes (1), identified by a **GUID**. Granting access to a property set grants access to all the attributes in the set.

**property type:** A 16-bit quantity that specifies the data type of a property value.

**public folder:** A **Folder object** that is stored in a location that is publicly available.

**read receipt:** An email message that is sent to the sender of a message to indicate that a message recipient received the message.

**recipient:** An entity that is in an **address list**, can receive email messages, and contains a set of attributes (1). Each attribute has a set of associated values.

**recipient table:** The part of a **Message object** that represents users to whom a message is addressed. Each row of the table is a set of properties that represents one **recipient**.

**recurrence pattern:** Information for a repeating event, such as the start and end time, the number of occurrences, and how occurrences are spaced, such as daily, weekly, or monthly.

**Recurring Calendar object:** A **Calendar object** that describes an event that repeats according to a recurrence pattern.

**recurring series:** An event that repeats at specific intervals of time according to a recurrence pattern.

**recurring task:** A series of **Task objects** that are described by a recurrence pattern.

**reminder:** A generally user-visible notification that a specified time has been reached. A reminder is most commonly related to the beginning of a meeting or the due time of a task but it can be applied to any object type.

**resource:** Any component that a computer can access where data can be read, written, or processed. This resource could be an internal component such as a disk drive, or another computer on a network that is used to access a file.

**Resource object:** An **Address Book object** that represents an asset that can be reserved, such as a room or equipment.

**retention tag:** An element that contains information about the retention policy of a **Message object** or folder.

**Rich Text Format (RTF):** Text with formatting as described in [\[MSFT-RTF\]](#).

**rights-managed email message:** An email message that specifies permissions that are designed to protect its content from inappropriate access, use, and distribution.

**Root folder:** The **special folder** that is the top-level folder in a message store hierarchy. It contains all other **Folder objects** in that message store.

**ROP buffer:** A structure containing an array of bytes that encode a remote operation (ROP). The first byte in the buffer identifies the ROP. This byte is followed by ROP-specific fields. Multiple ROP buffers can be packed into a single remote procedure call (RPC) request or response.

**rule:** An item that defines a condition and an action. The condition is evaluated for each **Message object** as it is delivered, and the action is executed if the new Message object matches the condition.

**Rule FAI message:** A **folder associated information (FAI)** message stored in the Inbox special folder where the client can store extra rule-related information that is opaque to the server.

**Sent Items folder:** A **special folder** that is the default location for storing copies of **Message objects** after they are submitted or sent.

**Server object:** An object on a server that is used as input or created as output for remote operations (ROPs).

**Short Message Service (SMS):** A communications protocol that is designed for sending text messages between mobile phones.

**signal time:** The time at which a **reminder** has been specified to notify the user or an agent acting on behalf of the user. For example, the signal time for a meeting that starts at 11:00 A.M. can be 10:45 A.M., thus allowing the user 15 minutes to prepare for or travel to the meeting upon receiving the notification.



**Simple Mail Transfer Protocol (SMTP):** A member of the TCP/IP suite of protocols that is used to transport Internet messages, as described in [\[RFC5321\]](#).

**site mailbox:** A repository comprised of a mailbox and a web-based collaboration environment that is presented to users as a mailbox in an email client. A site mailbox uses team membership to determine which users have access to the repository.

**soft delete:** A process that removes an item from the system, but not permanently. If an item is soft deleted, a server retains a back-up copy of the item and a client can access, restore, or permanently delete the item. See also hard delete.

**spam:** An unsolicited email message.

**spam filter:** A filter that checks certain conditions in a message to determine a spam confidence level.

**special folder:** One of a default set of **Folder objects** that can be used by an implementation to store and retrieve user data objects.

**stream:** A flow of data from one host to another host, or the data that flows between two hosts.

**tagged property:** A property that is defined by a 16-bit property ID and a 16-bit property type. The property ID for a tagged property is in the range 0x001 – 0x7FFF. Property IDs in the range 0x8000 – 0x8FFF are reserved for assignment to **named properties**.

**Task object:** A **Message object** that represents an assignment to be completed.

**task request:** A **Message object** that is used to issue a task assignment.

**Transmission Control Protocol (TCP):** A protocol used with the Internet Protocol (IP) to send data in the form of message units between computers over the Internet. TCP handles keeping track of the individual units of data (called packets) that a message is divided into for efficient routing through the Internet.

**Transport Neutral Encapsulation Format (TNEF):** A binary type-length-value encoding that is used to encode properties for transport, as described in [\[MS-OXTNEF\]](#).

**Unicode:** A character encoding standard developed by the Unicode Consortium that represents almost all of the written languages of the world. The **Unicode** standard [\[UNICODE5.0.0/2007\]](#) provides three forms (UTF-8, UTF-16, and UTF-32) and seven schemes (UTF-8, UTF-16, UTF-16 BE, UTF-16 LE, UTF-32, UTF-32 LE, and UTF-32 BE).

**Uniform Resource Identifier (URI):** A string that identifies a resource. The URI is an addressing mechanism defined in Internet Engineering Task Force (IETF) Uniform Resource Identifier (URI): Generic Syntax [\[RFC3986\]](#).

**Uniform Resource Locator (URL):** A string of characters in a standardized format that identifies a document or resource on the World Wide Web. The format is as specified in [\[RFC1738\]](#).

**unsendable attendee:** An attendee to whom a **meeting request** or meeting update is not sent.

**Use License:** An XrML 1.2 license that authorizes a user to gain access to a protected content file and describes the applicable usage policies. Also referred to as "End-User License (EUL)."

**Web Distributed Authoring and Versioning Protocol (WebDAV):** The Web Distributed Authoring and Versioning Protocol, as described in [\[RFC2518\]](#) or [\[RFC4918\]](#).

**X500 DN:** A distinguished name (DN), in Teletex form, of an object that is in an address book. An X500 DN can be more limited in the size and number of relative distinguished names (RDNs) than a full DN.

**XML:** The Extensible Markup Language, as described in [\[XML1.0\]](#).

**XML document:** A document object that is well formed, as described in [\[XML10/5\]](#), and might be valid. An XML document has a logical structure that is composed of declarations, elements, comments, character references, and processing instructions. It also has a physical structure that is composed of entities, starting with the root, or document, entity.

**MAY, SHOULD, MUST, SHOULD NOT, MUST NOT:** These terms (in all caps) are used as defined in [\[RFC2119\]](#). All statements of optional behavior use either MAY, SHOULD, or SHOULD NOT.

## 1.2 References

Links to a document in the Microsoft Open Specifications library point to the correct section in the most recently published version of the referenced document. However, because individual documents in the library are not updated at the same time, the section numbers in the documents may not match. You can confirm the correct section numbering by checking the [Errata](#).

### 1.2.1 Normative References

We conduct frequent surveys of the normative references to assure their continued availability. If you have any issue with finding a normative reference, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com). We will assist you in finding the relevant information.

[ISO/IEC8802-3] ISO/IEC, "Information technology -- Telecommunications and information exchange between systems -- Local and metropolitan area networks -- Specific requirements -- Part 3", Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications, ISO/IEC 8802-3:2000, [http://www.iso.org/iso/iso\\_catalogue/catalogue\\_tc/catalogue\\_detail.htm?csnumber=31002](http://www.iso.org/iso/iso_catalogue/catalogue_tc/catalogue_detail.htm?csnumber=31002)

[MS-OXABREF] Microsoft Corporation, "[Address Book Name Service Provider Interface \(NSPI\) Referral Protocol](#)".

[MS-OXBBODY] Microsoft Corporation, "[Best Body Retrieval Algorithm](#)".

[MS-OXCDATA] Microsoft Corporation, "[Data Structures](#)".

[MS-OXCEXT] Microsoft Corporation, "[Client Extension Message Object Protocol](#)".

[MS-OXCFOLD] Microsoft Corporation, "[Folder Object Protocol](#)".

[MS-OXCFXICS] Microsoft Corporation, "[Bulk Data Transfer Protocol](#)".

[MS-OXCICAL] Microsoft Corporation, "[iCalendar to Appointment Object Conversion Algorithm](#)".

[MS-OXCMAIL] Microsoft Corporation, "[RFC 2822 and MIME to Email Object Conversion Algorithm](#)".

[MS-OXCMSG] Microsoft Corporation, "[Message and Attachment Object Protocol](#)".

[MS-OXCPerm] Microsoft Corporation, "[Exchange Access and Operation Permissions Protocol](#)".

[MS-OXCPRPT] Microsoft Corporation, "[Property and Stream Object Protocol](#)".

[MS-OXCROPS] Microsoft Corporation, "[Remote Operations \(ROP\) List and Encoding Protocol](#)".

[MS-OXCRPC] Microsoft Corporation, "[Wire Format Protocol](#)".

[MS-OXCSPAM] Microsoft Corporation, "[Spam Confidence Level Protocol](#)".

[MS-OXCSTOR] Microsoft Corporation, "[Store Object Protocol](#)".



[MS-OXCTABL] Microsoft Corporation, "[Table Object Protocol](#)".

[MS-OXLDAP] Microsoft Corporation, "[Lightweight Directory Access Protocol \(LDAP\) Version 3 Extensions](#)".

[MS-OXMSG] Microsoft Corporation, "[Outlook Item \(.msg\) File Format](#)".

[MS-OXNSPI] Microsoft Corporation, "[Exchange Server Name Service Provider Interface \(NSPI\) Protocol](#)".

[MS-OXOABKT] Microsoft Corporation, "[Address Book User Interface Templates Protocol](#)".

[MS-OXOABK] Microsoft Corporation, "[Address Book Object Protocol](#)".

[MS-OXOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) File Format and Schema](#)".

[MS-OXOCAL] Microsoft Corporation, "[Appointment and Meeting Object Protocol](#)".

[MS-OXOCFG] Microsoft Corporation, "[Configuration Information Protocol](#)".

[MS-OXOCNTC] Microsoft Corporation, "[Contact Object Protocol](#)".

[MS-OXODLGT] Microsoft Corporation, "[Delegate Access Configuration Protocol](#)".

[MS-OXODOC] Microsoft Corporation, "[Document Object Protocol](#)".

[MS-OXOFLAG] Microsoft Corporation, "[Informational Flagging Protocol](#)".

[MS-OXOJRNL] Microsoft Corporation, "[Journal Object Protocol](#)".

[MS-OXOMSG] Microsoft Corporation, "[Email Object Protocol](#)".

[MS-OXONOTE] Microsoft Corporation, "[Note Object Protocol](#)".

[MS-OXOPFFB] Microsoft Corporation, "[Public Folder-Based Free/Busy Protocol](#)".

[MS-OXOPOST] Microsoft Corporation, "[Post Object Protocol](#)".

[MS-OXORMDR] Microsoft Corporation, "[Reminder Settings Protocol](#)".

[MS-OXORMMS] Microsoft Corporation, "[Rights-Managed Email Object Protocol](#)".

[MS-OXORSS] Microsoft Corporation, "[RSS Object Protocol](#)".

[MS-OXORULE] Microsoft Corporation, "[Email Rules Protocol](#)".

[MS-OXOSFLD] Microsoft Corporation, "[Special Folders Protocol](#)".

[MS-OXOSMIME] Microsoft Corporation, "[S/MIME Email Object Algorithm](#)".

[MS-OXOSMMS] Microsoft Corporation, "[Short Message Service \(SMS\) and Multimedia Messaging Service \(MMS\) Object Protocol](#)".

[MS-OXOSRCH] Microsoft Corporation, "[Search Folder List Configuration Protocol](#)".

[MS-OXOTASK] Microsoft Corporation, "[Task-Related Objects Protocol](#)".

[MS-OXOUM] Microsoft Corporation, "[Voice Mail and Fax Objects Protocol](#)".

[MS-OXPFOAB] Microsoft Corporation, "[Offline Address Book \(OAB\) Public Folder Retrieval Protocol](#)".

[MS-OXPHISH] Microsoft Corporation, "[Phishing Warning Protocol](#)".

[MS-OXPSVAL] Microsoft Corporation, "[Email Postmark Validation Algorithm](#)".

[MS-OXRTFCP] Microsoft Corporation, "[Rich Text Format \(RTF\) Compression Algorithm](#)".

[MS-OXRTFEX] Microsoft Corporation, "[Rich Text Format \(RTF\) Extensions Algorithm](#)".

[MS-OXSHARE] Microsoft Corporation, "[Sharing Message Object Protocol](#)".

[MS-OXTNEF] Microsoft Corporation, "[Transport Neutral Encapsulation Format \(TNEF\) Data Algorithm](#)".

[MS-OXVCARD] Microsoft Corporation, "[vCard to Contact Object Conversion Algorithm](#)".

[MS-OXWAVLS] Microsoft Corporation, "[Availability Web Service Protocol](#)".

[MS-WMF] Microsoft Corporation, "[Windows Metafile Format](#)".

[MS-XWDCAL] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Extensions for Calendar Support](#)".

[MS-XWDVSEC] Microsoft Corporation, "[Web Distributed Authoring and Versioning \(WebDAV\) Protocol Security Descriptor Extensions](#)".

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997, <http://www.rfc-editor.org/rfc/rfc2119.txt>

[RFC3464] Moore, K., and Vaudreuil, G., "An Extensible Message Format for Delivery Status Notifications", RFC 3464, January 2003, <http://www.rfc-editor.org/rfc/rfc3464.txt>

[RFC3798] Hansen, T., and Vaudreuil, G., Eds., "Message Disposition Notification", RFC 3798, May 2004, <http://www.rfc-editor.org/rfc/rfc3798.txt>

### 1.2.2 Informative References

[MS-OXPROTO] Microsoft Corporation, "[Exchange Server Protocols System Overview](#)".

[RFC5234] Crocker, D., Ed., and Overell, P., "Augmented BNF for Syntax Specifications: ABNF", STD 68, RFC 5234, January 2008, <http://www.rfc-editor.org/rfc/rfc5234.txt>

### 1.3 Overview

Each property listing in this document contains a link to the section of the technical specification in the Exchange Server Protocols documentation that acts as the defining reference for the property. The defining reference for each property contains the semantic use and definition of the property, including the property data type. The property information that is included in the defining reference for each property is required to successfully parse property data. As such, this document provides implementers with a single source of navigation to all of the critical property information that is included in the individual Exchange Server Protocols technical specifications.

This document also provides additional information about each property that is helpful to the implementer, such as the functional area where the property is used, a list of all the technical specifications that cite the property, and a list of alternate names by which the canonical property is known within the system. This information is not included in the technical specifications that describe each property, and is unique to this document. It is provided for informational purposes only.

A typical scenario for using this document is when an implementer encounters both **property IDs** and property values with no other identification coming across the wire. The property data type and the semantic definition of the property that are included in the defining reference for each property allow

the implementer to correctly parse property values that show up in **ROP buffers**. The parsed values in the ROP buffers include lists of property IDs, which are typically lists of four hexadecimal characters. By searching the information in this document for those four hexadecimal characters, the implementer can quickly name the associated property and navigate to the definition of the individual property in its defining specification.

The following information is provided for each property, as appropriate.

**Alternate names:** Alternate names are implementation-specific names for properties that are used in source code and non-protocol-related documentation. Information about alternate names is useful when the implementer needs to refer to legacy documentation about a specific canonical property.

**Area:** The functional area where the property is used. Sections [1.3.1](#), [1.3.2](#), and [1.3.3](#) describe the general functional areas where properties are used. The listing for each property in section [2](#) describes the areas with more varied descriptions so as to provide more insight into property usage.

**Canonical name:** The name used to refer to the property in the Exchange Server Protocols documentation. The prefix of the canonical name identifies the basic characteristics of a property to the implementer.

The canonical naming structure uses three categories that are denoted by the following prefixes to the canonical **property name**:

- PidLid prefix: Properties identified by an unsigned 32-bit quantity along with a property set.
- PidName prefix: Properties identified by a string name along with a property set.
- PidTag prefix: Properties identified by an unsigned 16-bit quantity.

**Description:** A brief description of the contents of the property.

**Data type:** The property value type, as described in [\[MS-OXCADATA\]](#), that specifies the type of values allowed for the property.

**Property ID:** An unsigned 16-bit quantity that identifies a **tagged property**. Property IDs are not necessarily unique. With the exception of property IDs in the range from 0x6800 to 0x7BFF (see section 1.3.3), the combination of property ID and data type are unique. Property IDs in the range from 0x6800 to 0x7BFF are defined by the **message class**.

**Property long ID (LID):** An unsigned 32-bit quantity that, along with the **property set**, identifies a **named property**.

**Property name:** A string that, along with the property set, identifies a named property.

**Property set:** A **GUID** that identifies a group of properties with a similar purpose.

**Defining references:** One or more technical specifications that describe the semantics and allowed values for the property.

**Consuming references:** One or more technical specifications that refer to the property but do not describe semantics and allowed values.

### 1.3.1 Common Message Classes

Applications set certain required properties corresponding to the object's message class. The following table describes several common message classes, the functional area to which each one corresponds, and the specification that describes each one's required and optional properties.

In the following table, an asterisk "\*" denotes that any string can appear at that point.

Area name	PidTagMessageClass property values	Specification
Common	IPM.*	<a href="#">[MS-OXCMSG]</a>
Email	IPM.Note, REPORT.*	[MS-OXCMSG]
Calendar	IPM.Appointment, IPM.Schedule.Meeting.Request, IPM.Schedule.Meeting.Resp.*, IPM.Schedule.Meeting.Canceled, IPM.Schedule.Meeting.Notification	<a href="#">[MS-OXOCAL]</a>
Contact	IPM.Contact, IPM DistList	<a href="#">[MS- OXOCNTC]</a>
Task	IPM.Task, IPM.TaskRequest.*	<a href="#">[MS- OXOTASK]</a>
Journal	IPM.Activity	<a href="#">[MS- OXOJRNL]</a>
Sticky Note	IPM.StickyNote	<a href="#">[MS- OXONOTE]</a>
Document	IPM.Document.*	<a href="#">[MS-OXODOC]</a>
Post	IPM.Post	<a href="#">[MS- OXOPOST]</a>
RSS Feed	IPM.Post.RSS	<a href="#">[MS-OXORSS]</a>
Rights-managed Email	IPM.Note with PidNameContentClass= rmsg.message	<a href="#">[MS- OXORMMS]</a>
S/MIME Email	IPM.Note.SMIME, IPM.Note.SMIME.MultipartSigned	<a href="#">[MS- OXOSMIME]</a>
Short Message Service (SMS) / Multimedia Message Service (MMS) Message	IPM.Note.Mobile.SMS, IPM.Note.Mobile.MMS	<a href="#">[MS- OXOSMMS]</a>
Unified Messaging	IPM.Note.Microsoft.Voicemail, IPM.Note.Microsoft.Fax	<a href="#">[MS-OXOUM]</a>
Sharing	IPM.Sharing IPM.Sharing.*	<a href="#">[MS- OXSHARE]</a>

### 1.3.2 Commonly Used Property Sets

In the property list that forms the main body of this document (section 2), each named property is listed with the GUID that describes its property set. Several of the more common property sets and their functional areas are described in the following table.

Area name	Property set name and GUID value
Common	PS_PUBLIC_STRINGS {00020329-0000-0000-C000-000000000046}
Common	PSETID_Common {00062008-0000-0000-C000-000000000046}

Area name	Property set name and GUID value
Contact	PSETID_Address {00062004-0000-0000-C000-000000000046}
Email	PS_INTERNET_HEADERS {00020386-0000-0000-C000-000000000046}
Calendar	PSETID_Appointment {00062002-0000-0000-C000-000000000046}
Calendar	PSETID_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}
Journal	PSETID_Log {0006200A-0000-0000-C000-000000000046}
Messaging	PSETID_Messaging {41F28F13-83F4-4114-A584-EEDB5A6B0BFF}
Sticky note	PSETID_Note {0006200E-0000-0000-C000-000000000046}
RSS feed	PSETID_PostRss {00062041-0000-0000-C000-000000000046}
Task	PSETID_Task {00062003-0000-0000-C000-000000000046}
Unified messaging	PSETID_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}
Common	PS_MAPI {00020328-0000-0000-C000-000000000046}
Sync	PSETID_AirSync {71035549-0739-4DCB-9163-00F0580DBBDF}
Sharing	PSETID_Sharing {00062040-0000-0000-C000-000000000046}
Extracted entities	PSETID_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

### 1.3.3 Property ID Ranges

The 65,536 possible values of the property ID are divided into sub-ranges reserved for various purposes, as described in the following table.

In this context, the term "non-transmittable" refers specifically to transmission via an email transport protocol (such as **SMTP**), and not to any network transport protocol (such as **TCP**):

- Servers do not allow property IDs in ranges specified as non-transmittable to be submitted for transport to another server via an email transport protocol. Property IDs in ranges not specified as non-transmittable are submitted for transport to another server.

- Clients can use properties in ranges described as message class-defined for application-defined purposes. When doing so, applications specify a value for the **PidTagMessageClass** property (section [2.778](#)) that is distinct from any value listed in section [1.3.1](#).
- Clients can use any named property for application-defined purposes. No constraint is placed on the value of the **PidTagMessageClass** property in this case, but the property set of the named property is distinct from any value listed in section [1.3.2](#). Note that named properties are always transmittable.
- Clients can use properties in ranges specified as transport-defined, but they cannot define new properties in those ranges.
- Clients can use and define properties in ranges specified as user-defined, but need to avoid conflicts with alternate definitions of the same property ID.

Range minimum	Range maximum	Description
0x0001	0x0BFF	Message object envelope property; reserved
0x0C00	0x0DFF	<b>Recipient</b> property; reserved
0x0E00	0x0FFF	Non-transmittable Message property; reserved
0x1000	0x2FFF	Message content property; reserved
0x3000	0x33FF	Multi-purpose property that can appear on all or most objects; reserved
0x3400	0x35FF	<b>Message store</b> property; reserved
0x3600	0x36FF	Folder and <b>address book container</b> property; reserved
0x3700	0x38FF	Attachment property; reserved
0x3900	0x39FF	<b>Address Book object</b> property; reserved
0x3A00	0x3BFF	<b>Mail user</b> object property; reserved
0x3C00	0x3CFF	<b>Distribution list</b> property; reserved
0x3D00	0x3DFF	Profile section property; reserved
0x3E00	0x3EFF	Status object property; reserved
0x4000	0x57FF	Transport-defined envelope property
0x5800	0x5FFF	Transport-defined recipient property
0x6000	0x65FF	User-defined non-transmittable property
0x6600	0x67FF	Provider-defined internal non-transmittable property
0x6800	0x7BFF	Message class-defined content property
0x7C00	0x7FFF	Message class-defined non-transmittable property
0x8000	0xFFFF	Reserved for mapping to named properties. The exceptions to this rule are some of the address book tagged properties (those with names beginning with PIDTagAddressBook). Many are static property ids but are in this range.

### 1.3.4 WebDAV Property Naming

The email server is natively a **Messaging Application Programming Interface (MAPI)** message store where the vast majority of properties in it are MAPI properties. The **WebDAV** implementation uses the **Augmented Backus-Naur Form (ABNF)** notation, as described in [\[RFC5234\]](#), as a way to name MAPI properties, allowing Web Distributed Authoring and Versioning Protocol (WebDAV) clients to work with these properties directly.

The `http://schemas.microsoft.com/mapi/` namespace is used to access MAPI properties directly on the server. The namespace consists of three sub namespaces: `proptag`, `id`, and `string`. The ABNF notation used to specify the format of these namespaces is described in this section.

#### 1.3.4.1 `http://schemas.microsoft.com/mapi/proptag` Namespace

The `http://schemas.microsoft.com/mapi/proptag` namespace is used to access properties on the server that are identified by a property ID. The implementer can access these properties through WebDAV by appending the hexadecimal property ID value and the hexadecimal **property type** value to the namespace prefix.

```
proptag-specifier = "http://schemas.microsoft.com/mapi/proptag/x" property-id property-type
property-id      = 4HEXDIG
property-type    = 4HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/proptag/x0037001f (PidTagSubject)
```

#### 1.3.4.2 `http://schemas.microsoft.com/mapi/id` Namespace

The `http://schemas.microsoft.com/mapi/id` namespace is used to access named properties on the server that are identified by a property **long ID (LID)**. The implementer can access these properties through WebDAV by appending the property set and the hexadecimal property long ID (LID) value to the namespace prefix.

```
id-specifier = "http://schemas.microsoft.com/mapi/id/" property-set "/" property-long-id
property-set = "{" 8HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 4HEXDIG "-" 12HEXDIG "}"
property-long-id = 8HEXDIG
```

Example:

```
http://schemas.microsoft.com/mapi/id/{00062002-0000-0000-C000-000000000046}/x00008213
(PidLidAppointmentDuration)
```

#### 1.3.4.3 `http://schemas.microsoft.com/mapi/string` Namespace

The `http://schemas.microsoft.com/mapi/string` namespace is used to access named properties on the server that are identified by a property name. The implementer can access these properties through WebDAV by appending the property set and the property name to the namespace prefix.

```
string-specifier = "http://schemas.microsoft.com/mapi/string/" property-set "/" property-name
```

```
property-set = "{" 8*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 4*HEXDIG "-" 12*HEXDIG "}"  
property-name = 1*CHAR
```

Example:

```
http://schemas.microsoft.com/mapi/string/{00020329-0000-0000-C000-000000000046}/Subject  
(PidNameSubject)
```

## 1.4 Relationship to Protocols and Other Structures

This document relies on property data type and error code definitions in [\[MS-OXCDATA\]](#). For tables and examples that describe property data types, and property and other error codes, see [\[MS-OXCDATA\]](#).

The list of properties and their descriptions included in this document provide context for many of the data structures described in [\[MS-OXCDATA\]](#).

The description of each property contained in this document relies on the technical specification that is cited as its defining reference.

For conceptual background information and overviews of the relationships and interactions between this and other protocols, see [\[MS-OXPROTO\]](#).

## 1.5 Applicability Statement

This document provides numeric values used to encode property names, tags, and data types in ROP buffers. It also serves as a convenient index to the object type documents that define how each property is used.

## 1.6 Versioning and Localization

None.

## 1.7 Vendor-Extensible Fields

Property ID ranges, as described in section [1.3.3](#), describe how applications choose properties to create new Message object types or to add functionality to existing types.



## 2 Structures

### 2.1 PidLidAddressBookProviderArrayType

**Canonical name:** PidLidAddressBookProviderArrayType

**Description:** Specifies the state of the electronic addresses of the **contact** and represents a set of bit **flags**.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008029

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.12

**Alternate names:** dispidABPArrayType

### 2.2 PidLidAddressBookProviderEmailList

**Canonical name:** PidLidAddressBookProviderEmailList

**Description:** Specifies which electronic address properties are set on the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008028

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.11

**Alternate names:** dispidABPEmailList

### 2.3 PidLidAddressCountryCode

**Canonical name:** PidLidAddressCountryCode

**Description:** Specifies the country code portion of the mailing address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DD

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidAddressCountryCode

## 2.4 PidLidAgingDontAgeMe

**Canonical name:** PidLidAgingDontAgeMe

**Description:** Specifies whether to automatically archive the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000850E

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.33

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidAgingDontAgeMe

## 2.5 PidLidAllAttendeesString

**Canonical name:** PidLidAllAttendeesString

**Description:** Specifies a list of all the attendees except for the **organizer**, including **resources** and **unsendable attendees**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008238

**WebDAV:** <http://schemas.microsoft.com/mapi/allattendeesstring>

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.16

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidAllAttendeesString

## 2.6 PidLidAllowExternalCheck

**Canonical name:** PidLidAllowExternalCheck

**Description:** This property is set to TRUE.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008246

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.5

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAllowExternCheck

## 2.7 PidLidAnniversaryEventEntryId

**Canonical name:** PidLidAnniversaryEventEntryId

**Description:** Specifies the **EntryID** of the **Appointment object** that represents an anniversary of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804E

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.6

**Alternate names:** dispidAnniversaryEventEID

## 2.8 PidLidAppointmentAuxiliaryFlags

**Canonical name:** PidLidAppointmentAuxiliaryFlags

**Description:** Specifies a bit field that describes the auxiliary state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008207

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.3

**Alternate names:** dispidApptAuxFlags

## 2.9 PidLidAppointmentColor

**Canonical name:** PidLidAppointmentColor

**Description:** Specifies the color to be used when displaying the **Calendar object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008214

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.50

**Alternate names:** dispidApptColor

## 2.10 PidLidAppointmentCounterProposal

**Canonical name:** PidLidAppointmentCounterProposal

**Description:** Indicates whether a **Meeting Response object** is a **counter proposal**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008257

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.7

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptCounterProposal

## 2.11 PidLidAppointmentDuration

**Canonical name:** PidLidAppointmentDuration

**Description:** Specifies the length of the event, in minutes.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008213

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptduration

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptDuration

## 2.12 PidLidAppointmentEndDate

**Canonical name:** PidLidAppointmentEndDate

**Description:** Indicates the date that the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008211

**WebDAV:** http://schemas.microsoft.com/mapi/apptenddate

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.3

**Alternate names:** dispidApptEndDate

## 2.13 PidLidAppointmentEndTime

**Canonical name:** PidLidAppointmentEndTime

**Description:** Indicates the time that the appointment ends.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008210

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptendtime

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.4

**Alternate names:** dispidApptEndTime

## 2.14 PidLidAppointmentEndWhole

**Canonical name:** PidLidAppointmentEndWhole

**Description:** Specifies the end date and time for the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820E

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptendwhole

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptEndWhole

## 2.15 PidLidAppointmentLastSequence

**Canonical name:** PidLidAppointmentLastSequence

**Description:** Indicates to the organizer the last sequence number that was sent to any attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008203

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.2

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptLastSequence

## 2.16 PidLidAppointmentMessageClass

**Canonical name:** PidLidAppointmentMessageClass

**Description:** Indicates the message class of the **Meeting object** to be generated from the **Meeting Request object**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000024

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.6

**Alternate names:** dispidApptMessageClass

## 2.17 PidLidAppointmentNotAllowPropose

**Canonical name:** PidLidAppointmentNotAllowPropose

**Description:** Indicates whether attendees are not allowed to propose a new date and/or time for the **meeting**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.26

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptNotAllowPropose

## 2.18 PidLidAppointmentProposalNumber

**Canonical name:** PidLidAppointmentProposalNumber

**Description:** Specifies the number of attendees who have sent counter proposals that have not been accepted or rejected by the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008259

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.6

**Alternate names:** dispidApptProposalNum

## 2.19 PidLidAppointmentProposedDuration

**Canonical name:** PidLidAppointmentProposedDuration

**Description:** Indicates the proposed value for the **PidLidAppointmentDuration** property (section [2.11](#)) for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008256

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.5

**Alternate names:** dispidApptProposedDuration

## 2.20 PidLidAppointmentProposedEndWhole

**Canonical name:** PidLidAppointmentProposedEndWhole

**Description:** Specifies the proposed value for the **PidLidAppointmentEndWhole** property (section [2.14](#)) for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008251

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.4

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedEndWhole

## 2.21 PidLidAppointmentProposedStartWhole

**Canonical name:** PidLidAppointmentProposedStartWhole

**Description:** Specifies the proposed value for the **PidLidAppointmentStartWhole** property (section [2.29](#)) for a counter proposal.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008250

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.3

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptProposedStartWhole

## 2.22 PidLidAppointmentRecur

**Canonical name:** PidLidAppointmentRecur

**Description:** Specifies the dates and times when a **recurring series** occurs.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008216

**Data type:** PtypBinary, 0x0102

**WebDAV:** http://schemas.microsoft.com/mapi/apptrecur

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.44

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptRecur

## 2.23 PidLidAppointmentReplyName

**Canonical name:** PidLidAppointmentReplyName

**Description:** Specifies the user who last replied to the **meeting request** or meeting update.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008230

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/apptreplyname

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.5

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptReplyName, http://schemas.microsoft.com/mapi/apptreplyname

## 2.24 PidLidAppointmentReplyTime

**Canonical name:** PidLidAppointmentReplyTime

**Description:** Specifies the date and time at which the attendee responded to a received meeting request or **Meeting Update object**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008220

**Data type:** PtypTime, 0x0040

**WebDAV:** urn:schemas:calendar:replytime, http://schemas.microsoft.com/mapi/apptreplytime

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptReplyTime



## 2.25 PidLidAppointmentSequence

**Canonical name:** PidLidAppointmentSequence

**Description:** Specifies the sequence number of a Meeting object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008201

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptsequence

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptSequence

## 2.26 PidLidAppointmentSequenceTime

**Canonical name:** PidLidAppointmentSequenceTime

**Description:** Indicates the date and time at which the **PidLidAppointmentSequence** property (section [2.25](#)) was last modified.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008202

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.1

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptSeqTime

## 2.27 PidLidAppointmentStartDate

**Canonical name:** PidLidAppointmentStartDate

**Description:** Identifies the date that the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008212

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptstartdate

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.10

**Alternate names:** dispidApptStartDate

## 2.28 PidLidAppointmentStartTime

**Canonical name:** PidLidAppointmentStartTime

**Description:** Identifies the time that the appointment starts.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820F

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptstarttime

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.11

**Alternate names:** dispidApptStartTime

## 2.29 PidLidAppointmentStartWhole

**Canonical name:** PidLidAppointmentStartWhole

**Description:** Specifies the start date and time of the appointment.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820D

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/apptstartwhole

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStartWhole

## 2.30 PidLidAppointmentStateFlags

**Canonical name:** PidLidAppointmentStateFlags

**Description:** Specifies a bit field that describes the state of the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008217

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/apptstateflags

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptStateFlags

### 2.31 PidLidAppointmentSubType

**Canonical name:** PidLidAppointmentSubType

**Description:** Specifies whether the event is an all-day event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008215

**Data type:** PtypBoolean, 0x000B

**WebDAV:** urn:schemas:calendar:alldayevent, <http://schemas.microsoft.com/mapi/apptsubtype>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidApptSubType

### 2.32 PidLidAppointmentTimeZoneDefinitionEndDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionEndDisplay

**Description:** Specifies time zone information that indicates the time zone of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825F

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefEndDisplay

### 2.33 PidLidAppointmentTimeZoneDefinitionRecur

**Canonical name:** PidLidAppointmentTimeZoneDefinitionRecur

**Description:** Specifies time zone information that describes how to convert the meeting date and time on a recurring series to and from **UTC**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008260

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.41

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** dispidApptTZDefRecur

### 2.34 PidLidAppointmentTimeZoneDefinitionStartDisplay

**Canonical name:** PidLidAppointmentTimeZoneDefinitionStartDisplay

**Description:** Specifies time zone information that indicates the time zone of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825E

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.42

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidApptTZDefStartDisplay

### 2.35 PidLidAppointmentUnsendableRecipients

**Canonical name:** PidLidAppointmentUnsendableRecipients

**Description:** Contains a list of unsendable attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000825D

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.25

**Alternate names:** dispidApptUnsendableRecips

### 2.36 PidLidAppointmentUpdateTime

**Canonical name:** PidLidAppointmentUpdateTime

**Description:** Indicates the time at which the appointment was last updated.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008226

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/apptupdatetime>

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.15

**Alternate names:** dispidApptUpdateTime

### 2.37 PidLidAttendeeCriticalChange

**Canonical name:** PidLidAttendeeCriticalChange

**Description:** Specifies the date and time at which the **meeting-related object** was sent.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000001

**Data type:** PtypTime, 0x0040

**WebDAV:** [http://schemas.microsoft.com/mapi/attendee\\_critical\\_change](http://schemas.microsoft.com/mapi/attendee_critical_change)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_ATTENDEE\_CRITICAL\_CHANGE

### 2.38 PidLidAutoFillLocation

**Canonical name:** PidLidAutoFillLocation

**Description:** Indicates whether the value of the **PidLidLocation** property (section [2.159](#)) is set to the **PidTagDisplayName** property (section [2.667](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.8

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidAutoFillLocation

### 2.39 PidLidAutoLog

**Canonical name:** PidLidAutoLog

**Description:** Specifies to the application whether to create a **Journal object** for each **action** associated with this Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008025

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.19

**Alternate names:** dispidAutoLog

## 2.40 PidLidAutoProcessState

**Canonical name:** PidLidAutoProcessState

**Description:** Specifies the options used in the automatic processing of email messages.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851A

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.73

**Alternate names:** dispidSniffState

## 2.41 PidLidAutoStartCheck

**Canonical name:** PidLidAutoStartCheck

**Description:** Specifies whether to automatically start the conferencing application when a **reminder** for the start of a meeting is executed.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008244

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidAutoStartCheck

## 2.42 PidLidBilling

**Canonical name:** PidLidBilling

**Description:** Specifies billing information for the contact.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008535

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:billinginformation

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.24

**Alternate names:** dispidBilling

### 2.43 PidLidBirthdayEventEntryId

**Canonical name:** PidLidBirthdayEventEntryId

**Description:** Specifies the EntryID of an optional Appointment object that represents the birthday of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804D

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.3

**Alternate names:** dispidBirthdayEventEID

### 2.44 PidLidBirthdayLocal

**Canonical name:** PidLidBirthdayLocal

**Description:** Specifies the birthday of a contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DE

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.2

**Alternate names:** dispidApptBirthdayLocal

### 2.45 PidLidBusinessCardCardPicture

**Canonical name:** PidLidBusinessCardCardPicture

**Description:** Contains the image to be used on a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008041

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.2

**Alternate names:** dispidBCCardPicture

### 2.46 PidLidBusinessCardDisplayDefinition

**Canonical name:** PidLidBusinessCardDisplayDefinition

**Description:** Contains user customization details for displaying a contact as a business card.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008040

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidBCDisplayDefinition

## 2.47 PidLidBusyStatus

**Canonical name:** PidLidBusyStatus

**Description:** Specifies the availability of a user for the event described by the object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008205

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/busystatus>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidBusyStatus

## 2.48 PidLidCalendarType

**Canonical name:** PidLidCalendarType

**Description:** Contains the value of the **CalendarType** field from the **PidLidAppointmentRecur** property (section [2.22](#)).

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/calendar\\_type](http://schemas.microsoft.com/mapi/calendar_type)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.11

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_CALENDAR\_TYPE



## 2.49 PidLidCategories

**Canonical name:** PidLidCategories

**Description:** Contains the array of text labels assigned to this Message object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00009000

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.22

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidCategories

## 2.50 PidLidCcAttendeesString

**Canonical name:** PidLidCcAttendeesString

**Description:** Contains a list of all the sendable attendees who are also **optional attendees**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823C

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.18

**Alternate names:** dispidCCAttendeesString

## 2.51 PidLidChangeHighlight

**Canonical name:** PidLidChangeHighlight

**Description:** Specifies a bit field that indicates how the Meeting object has changed.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008204

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.2

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidChangeHighlight

## 2.52 PidLidClassification

**Canonical name:** PidLidClassification

**Description:** Contains a list of the classification categories to which the associated Message object has been assigned.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B6

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.23

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassification

### 2.53 PidLidClassificationDescription

**Canonical name:** PidLidClassificationDescription

**Description:** Contains a human-readable summary of each of the classification categories included in the **PidLidClassification** property (section 2.53).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B7

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.24

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassDesc

### 2.54 PidLidClassificationGuid

**Canonical name:** PidLidClassificationGuid

**Description:** Contains the GUID that identifies the list of email classification categories used by a Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B8

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.1

**Alternate names:** dispidClassGuid

### 2.55 PidLidClassificationKeep

**Canonical name:** PidLidClassificationKeep

**Description:** Indicates whether the message uses any classification categories.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BA

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.2

**Alternate names:** dispidClassKeep

## 2.56 PidLidClassified

**Canonical name:** PidLidClassified

**Description:** Indicates whether the contents of this message are regarded as classified information.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B5

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.25

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidClassified

## 2.57 PidLidCleanGlobalObjectId

**Canonical name:** PidLidCleanGlobalObjectId

**Description:** Contains the value of the **PidLidGlobalObjectId** property (section [2.142](#)) for an object that represents an **Exception object** to a recurring series, where the Year, Month, and Day fields are all zero.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000023

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.28

**Consuming references:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidCleanGlobalObjId

## 2.58 PidLidClientIntent

**Canonical name:** PidLidClientIntent

**Description:** Indicates what actions the user has taken on this Meeting object.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x00000015

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.2.4

**Alternate names:** dispidClientIntent

## 2.59 PidLidClipEnd

**Canonical name:** PidLidClipEnd

**Description:** Specifies the end date and time of the event in UTC.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008236

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.15

**Alternate names:** dispidClipEnd

## 2.60 PidLidClipStart

**Canonical name:** PidLidClipStart

**Description:** Specifies the start date and time of the event in UTC.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008235

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.14

**Alternate names:** dispidClipStart

## 2.61 PidLidCollaborateDoc

**Canonical name:** PidLidCollaborateDoc

**Description:** Specifies the document to be launched when the user joins the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008247

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidCollaborateDoc

## 2.62 PidLidCommonEnd

**Canonical name:** PidLidCommonEnd

**Description:** Indicates the end time for the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008517

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.19

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidCommonEnd

## 2.63 PidLidCommonStart

**Canonical name:** PidLidCommonStart

**Description:** Indicates the start time for the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008516

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.18

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidCommonStart

## 2.64 PidLidCompanies

**Canonical name:** PidLidCompanies

**Description:** Contains a list of company names, each of which is associated with a contact that is specified in the PidLidContacts property ([\[MS-OXCMSG\]](#) section 2.2.1.57.2).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008539

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.2.4

**Alternate names:** dispidCompanies, <http://schemas.microsoft.com/exchange/companies>

## 2.65 PidLidConferencingCheck

**Canonical name:** PidLidConferencingCheck

**Description:**

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008240

**Data type:** PtypBoolean, 0x000B

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfCheck

## 2.66 PidLidConferencingType

**Canonical name:** PidLidConferencingType

**Description:** Specifies the type of the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008241

**Data type:** PtypInteger32, 0x0003

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidConfType

## 2.67 PidLidContactCharacterSet

**Canonical name:** PidLidContactCharacterSet

**Description:** Specifies the character set used for a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008023

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.18

**Alternate names:** dispidContactCharSet

## 2.68 PidLidContactItemData

**Canonical name:** PidLidContactItemData

**Description:** Specifies the visible fields in the application's user interface that are used to help display the contact information.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008007

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.22

**Alternate names:** dispidContactItemData

## 2.69 PidLidContactLinkedGlobalAddressListEntryId

**Canonical name:** PidLidContactLinkedGlobalAddressListEntryId

**Description:** Specifies the EntryID of the **GAL** contact to which the duplicate contact is linked.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E2

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.1

**Alternate names:** dispidContactLinkedGALEntryID

## 2.70 PidLidContactLinkEntry

**Canonical name:** PidLidContactLinkEntry

**Description:** Contains the elements of the **PidLidContacts** property (section [2.77](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008585

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.1

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkEntry

## 2.71 PidLidContactLinkGlobalAddressListLinkId

**Canonical name:** PidLidContactLinkGlobalAddressListLinkId

**Description:** Specifies the GUID of the GAL contact to which the duplicate contact is linked.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E8

**Data type:** PtypGuid, 0x0048

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.2

**Alternate names:** dispidContactLinkGALLinkID

## 2.72 PidLidContactLinkGlobalAddressListLinkState

**Canonical name:** PidLidContactLinkGlobalAddressListLinkState

**Description:** Specifies the state of the linking between the GAL contact and the duplicate contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E6

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.3

**Alternate names:** dispidContactLinkGALLinkState

## 2.73 PidLidContactLinkLinkRejectHistory

**Canonical name:** PidLidContactLinkLinkRejectHistory

**Description:** Contains a list of GAL contacts that were previously rejected for linking with the duplicate contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E5

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.4

**Alternate names:** dispidContactLinkLinkRejectHistory

## 2.74 PidLidContactLinkName

**Canonical name:** PidLidContactLinkName

**Description:**



**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008586

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.3

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkName

## 2.75 PidLidContactLinkSearchKey

**Canonical name:** PidLidContactLinkSearchKey

**Description:** Contains the list of SearchKeys for a Contact object linked to by the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008584

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.4

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContactLinkSearchKey

## 2.76 PidLidContactLinkSMTPAddressCache

**Canonical name:** PidLidContactLinkSMTPAddressCache

**Description:** Contains a list of the SMTP addresses that are used by the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E3

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.5

**Alternate names:** dispidContactLinkSMTPAddressCache

## 2.77 PidLidContacts

**Canonical name:** PidLidContacts

**Description:** Contains the **PidTagDisplayName** property (section [2.667](#)) of each Address Book EntryID referenced in the value of the **PidLidContactLinkEntry** property (section [2.70](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000853A

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.57.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRNLI\]](#)

**Alternate names:** dispidContacts

## 2.78 PidLidContactUserField1

**Canonical name:** PidLidContactUserField1

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804F

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute1

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField1

## 2.79 PidLidContactUserField2

**Canonical name:** PidLidContactUserField2

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008050

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute2

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField2

## 2.80 PidLidContactUserField3

**Canonical name:** PidLidContactUserField3

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008051

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute3

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField3

## 2.81 PidLidContactUserField4

**Canonical name:** PidLidContactUserField4

**Description:** Contains text used to add custom text to a business card representation of a Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008052

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/exchange/extensionattribute4

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.7.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidContactUserField4

## 2.82 PidLidConversationActionLastAppliedTime

**Canonical name:** PidLidConversationActionLastAppliedTime

**Description:** Contains the time, in UTC, that an **Email object** was last received in the **conversation**, or the last time that the user modified the **conversation action**, whichever occurs later.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CA

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.1

**Alternate names:** dispidConvActionLastAppliedTime

## 2.83 PidLidConversationActionMaxDeliveryTime

**Canonical name:** PidLidConversationActionMaxDeliveryTime

**Description:** Contains the maximum value of the **PidTagMessageDeliveryTime** property (section [2.780](#)) of all of the Email objects modified in response to the last time that the user changed a conversation action on the client.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C8

**Data type:** PtypTime, 0x0040

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.2

**Alternate names:** dispidConvActionMaxDeliveryTime

## 2.84 PidLidConversationActionMoveFolderEid

**Canonical name:** PidLidConversationActionMoveFolderEid

**Description:** Contains the EntryID for the destination folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C6

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.3

**Alternate names:** dispidConvActionMoveFolderEid

## 2.85 PidLidConversationActionMoveStoreEid

**Canonical name:** PidLidConversationActionMoveStoreEid

**Description:** Contains the EntryID for a move to a folder in a different message store.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C7

**Data type:** PtypBinary, 0x0102

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.4

**Alternate names:** dispidConvActionMoveStoreEid

## 2.86 PidLidConversationActionVersion

**Canonical name:** PidLidConversationActionVersion

**Description:** Contains the version of the conversation action **FAI** message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085CB

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.5

**Alternate names:** dispidConvActionVersion

## 2.87 PidLidConversationProcessed

**Canonical name:** PidLidConversationProcessed

**Description:** Specifies a sequential number to be used in the processing of a conversation action.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C9

**Data type:** PtypInteger32, 0x0003

**Area:** Conversation Actions

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.8.6

**Alternate names:** dispidConvExLegacyProcessedRand

## 2.88 PidLidCurrentVersion

**Canonical name:** PidLidCurrentVersion

**Description:** Specifies the build number of the client application that sent the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008552

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.34

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidCurrentVersion

## 2.89 PidLidCurrentVersionName

**Canonical name:** PidLidCurrentVersionName

**Description:** Specifies the name of the client application that sent the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008554

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.35

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** dispidCurrentVersionName

## 2.90 PidLidDayInterval

**Canonical name:** PidLidDayInterval

**Description:** Identifies the day interval for the **recurrence pattern**.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000011

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/day\_interval

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.19

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_DAY\_INTERVAL

## 2.91 PidLidDayOfMonth

**Canonical name:** PidLidDayOfMonth

**Description:** Identifies the day of the month for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001000

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/dayofmonth

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.20

## 2.92 PidLidDelegateMail

**Canonical name:** PidLidDelegateMail

**Description:** Indicates whether a **delegate** responded to the meeting request.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000009

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/delegate\_mail

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.21

**Alternate names:** LID\_DELEGATE\_MAIL

## 2.93 PidLidDepartment

**Canonical name:** PidLidDepartment

**Description:** This property is ignored by the server and is set to an empty string by the client.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008010

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.4

**Alternate names:** dispidDepartment

## 2.94 PidLidDirectory

**Canonical name:** PidLidDirectory

**Description:** Specifies the directory server to be used.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008242

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidDirectory

## 2.95 PidLidDistributionListChecksum

**Canonical name:** PidLidDistributionListChecksum

**Description:** Specifies the 32-bit **cyclic redundancy check (CRC)** polynomial checksum, as specified in [\[ISO/IEC8802-3\]](#), calculated on the value of the **PidLidDistributionListMembers** property (section [2.96](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804C

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.3

**Alternate names:** dispidDLChecksum

## 2.96 PidLidDistributionListMembers

**Canonical name:** PidLidDistributionListMembers

**Description:** Specifies the list of EntryIDs of the objects corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008055

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.1

**Alternate names:** dispidDLMembers

## 2.97 PidLidDistributionListName

**Canonical name:** PidLidDistributionListName

**Description:** Specifies the name of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008053

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.1.2

**Alternate names:** dispidDLName

## 2.98 PidLidDistributionListOneOffMembers

**Canonical name:** PidLidDistributionListOneOffMembers

**Description:** Specifies the list of one-off EntryIDs corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008054

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.2

**Alternate names:** dispidDLOneOffMembers



## 2.99 PidLidDistributionListStream

**Canonical name:** PidLidDistributionListStream

**Description:** Specifies the list of EntryIDs and one-off EntryIDs corresponding to the members of the personal distribution list.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008064

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.2.2.4

**Alternate names:** dispidDLStream

## 2.100 PidLidEmail1AddressType

**Canonical name:** PidLidEmail1AddressType

**Description:** Specifies the **address type** of an electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008082

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1AddrType

## 2.101 PidLidEmail1DisplayName

**Canonical name:** PidLidEmail1DisplayName

**Description:** Specifies the user-readable **display name** for the email address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008080

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1DisplayName

## 2.102 PidLidEmail1EmailAddress

**Canonical name:** PidLidEmail1EmailAddress

**Description:** Specifies the email address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008083

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail1EmailAddress

## 2.103 PidLidEmail1OriginalDisplayName

**Canonical name:** PidLidEmail1OriginalDisplayName

**Description:** Specifies the SMTP email address that corresponds to the email address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008084

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail1OriginalDisplayName, Email1OriginalDisplayName, EXSCHEMA\_MAPI\_EMAIL1ORIGINALDISPLAYNAME

## 2.104 PidLidEmail1OriginalEntryId

**Canonical name:** PidLidEmail1OriginalEntryId

**Description:** Specifies the EntryID of the object corresponding to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008085

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail1OriginalEntryID

## 2.105 PidLidEmail2AddressType

**Canonical name:** PidLidEmail2AddressType

**Description:** Specifies the address type of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008092

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2AddrType

## 2.106 PidLidEmail2DisplayName

**Canonical name:** PidLidEmail2DisplayName

**Description:** Specifies the user-readable display name for the email address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008090

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2DisplayName

## 2.107 PidLidEmail2EmailAddress

**Canonical name:** PidLidEmail2EmailAddress

**Description:** Specifies the email address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008093

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail2EmailAddress

## 2.108 PidLidEmail2OriginalDisplayName

**Canonical name:** PidLidEmail2OriginalDisplayName

**Description:** Specifies the SMTP email address that corresponds to the email address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008094

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail2OriginalDisplayName

### 2.109 PidLidEmail2OriginalEntryId

**Canonical name:** PidLidEmail2OriginalEntryId

**Description:** Specifies the EntryID of the object that corresponds to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008095

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail2OriginalEntryID

### 2.110 PidLidEmail3AddressType

**Canonical name:** PidLidEmail3AddressType

**Description:** Specifies the address type of the electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.2

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3AddrType

### 2.111 PidLidEmail3DisplayName

**Canonical name:** PidLidEmail3DisplayName

**Description:** Specifies the user-readable display name for the email address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A0

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3DisplayName

### 2.112 PidLidEmail3EmailAddress

**Canonical name:** PidLidEmail3EmailAddress

**Description:** Specifies the email address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidEmail3EmailAddress

### 2.113 PidLidEmail3OriginalDisplayName

**Canonical name:** PidLidEmail3OriginalDisplayName

**Description:** Specifies the SMTP email address that corresponds to the email address for the Contact object.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.4

**Alternate names:** dispidEmail3OriginalDisplayName

### 2.114 PidLidEmail3OriginalEntryId

**Canonical name:** PidLidEmail3OriginalEntryId

**Description:** Specifies the EntryID of the object that corresponds to this electronic address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080A5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.5

**Alternate names:** dispidEmail3OriginalEntryID

### 2.115 PidLidEndRecurrenceDate

**Canonical name:** PidLidEndRecurrenceDate

**Description:** Identifies the end date of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000F

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/end\\_recur\\_date](http://schemas.microsoft.com/mapi/end_recur_date)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.22

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_END\_RECUR\_DATE

### 2.116 PidLidEndRecurrenceTime

**Canonical name:** PidLidEndRecurrenceTime

**Description:** Identifies the end time of the recurrence range.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000010

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/end\\_recur\\_time](http://schemas.microsoft.com/mapi/end_recur_time)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.23

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_END\_RECUR\_TIME

### 2.117 PidLidExceptionReplaceTime

**Canonical name:** PidLidExceptionReplaceTime

**Description:** Specifies the date and time, in UTC, within a recurrence pattern that an exception will replace.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008228

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.2.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidExceptionReplaceTime

### 2.118 PidLidFax1AddressType

**Canonical name:** PidLidFax1AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax1AddrType

### 2.119 PidLidFax1EmailAddress

**Canonical name:** PidLidFax1EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax1EmailAddress

### 2.120 PidLidFax1OriginalDisplayName

**Canonical name:** PidLidFax1OriginalDisplayName

**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.803](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax1OriginalDisplayName

### 2.121 PidLidFax1OriginalEntryId

**Canonical name:** PidLidFax1OriginalEntryId

**Description:** Specifies a one-off EntryID that corresponds to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080B5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax1OriginalEntryID

### 2.122 PidLidFax2AddressType

**Canonical name:** PidLidFax2AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax2AddrType

### 2.123 PidLidFax2EmailAddress

**Canonical name:** PidLidFax2EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax2EmailAddress



## 2.124 PidLidFax2OriginalDisplayName

**Canonical name:** PidLidFax2OriginalDisplayName

**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.803](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax2OriginalDisplayName

## 2.125 PidLidFax2OriginalEntryId

**Canonical name:** PidLidFax2OriginalEntryId

**Description:** Specifies a one-off EntryID corresponding to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080C5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax2OriginalEntryID

## 2.126 PidLidFax3AddressType

**Canonical name:** PidLidFax3AddressType

**Description:** Contains the string value "FAX".

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D2

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.7

**Alternate names:** dispidFax3AddrType

## 2.127 PidLidFax3EmailAddress

**Canonical name:** PidLidFax3EmailAddress

**Description:** Contains a user-readable display name, followed by the "@" character, followed by a fax number.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D3

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.8

**Alternate names:** dispidFax3EmailAddress

### 2.128 PidLidFax3OriginalDisplayName

**Canonical name:** PidLidFax3OriginalDisplayName

**Description:** Contains the same value as the **PidTagNormalizedSubject** property (section [2.803](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D4

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.9

**Alternate names:** dispidFax3OriginalDisplayName

### 2.129 PidLidFax3OriginalEntryId

**Canonical name:** PidLidFax3OriginalEntryId

**Description:** Specifies a one-off EntryID that corresponds to this fax address.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D5

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.10

**Alternate names:** dispidFax3OriginalEntryID

### 2.130 PidLidFExceptionalAttendees

**Canonical name:** PidLidFExceptionalAttendees

**Description:** Indicates that the object is a **Recurring Calendar object** with one or more exceptions, and that at least one of the **Exception Embedded Message objects** has at least one **RecipientRow** structure, as described in [\[MS-OXCDATA\]](#) section 2.8.3.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822B

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.2.3

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidFExceptionalAttendees

### 2.131 PidLidFExceptionalBody

**Canonical name:** PidLidFExceptionalBody

**Description:** Indicates that the Exception Embedded Message object has a body that differs from the Recurring Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008206

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.2.6

**Alternate names:** dispidFExceptionalBody

### 2.132 PidLidFileUnder

**Canonical name:** PidLidFileUnder

**Description:** Specifies the name under which to file a contact when displaying a list of contacts.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008005

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.11

**Alternate names:** dispidFileUnder

### 2.133 PidLidFileUnderId

**Canonical name:** PidLidFileUnderId

**Description:** Specifies how to generate and recompute the value of the **PidLidFileUnder** property (section [2.132](#)) when other contact name properties change.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008006

**Data type:** PtypInteger32, 0x0003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.12

**Alternate names:** dispidFileUnderId

### 2.134 PidLidFileUnderList

**Canonical name:** PidLidFileUnderList

**Description:** Specifies a list of possible values for the **PidLidFileUnderId** property (section [2.133](#)).

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008026

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.13

**Alternate names:** dispidFileUnderList

### 2.135 PidLidFInvited

**Canonical name:** PidLidFInvited

**Description:** Indicates whether invitations have been sent for the meeting that this Meeting object represents.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008229

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/invited

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFInvited

### 2.136 PidLidFlagRequest

**Canonical name:** PidLidFlagRequest

**Description:** Contains user-specifiable text to be associated with the flag.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008530

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:httpmail:messageflag, http://schemas.microsoft.com/mapi/request

**Area:** Flagging

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidRequest

### 2.137 PidLidFlagString

**Canonical name:** PidLidFlagString

**Description:** Contains an index identifying one of a set of pre-defined text strings to be associated with the flag.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085C0

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.10

**Alternate names:** dispidFlagStringEnum

### 2.138 PidLidForwardInstance

**Canonical name:** PidLidForwardInstance

**Description:** Indicates whether the Meeting Request object represents an exception to a recurring series, and whether it was forwarded (even when forwarded by the organizer) rather than being an invitation sent by the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820A

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.3

**Alternate names:** dispidFwrInstance

### 2.139 PidLidForwardNotificationRecipients

**Canonical name:** PidLidForwardNotificationRecipients

**Description:** Contains a list of **RecipientRow** structures, as described in [\[MS-OXCDATA\]](#) section 2.8.3, that indicate the recipients of a meeting forward.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008261

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.9.3

**Alternate names:** dispidForwardNotificationRecipients

### 2.140 PidLidFOthersAppointment

**Canonical name:** PidLidFOthersAppointment

**Description:** Indicates whether the **Calendar folder** from which the meeting was opened is another user's **calendar**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822F

**Data type:** PtypBoolean, 0x000B

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.26

**Alternate names:** dispidFOthersAppt, <http://schemas.microsoft.com/mapi/fothersappt>

### 2.141 PidLidFreeBusyLocation

**Canonical name:** PidLidFreeBusyLocation

**Description:** Specifies a **URL** path from which a client can retrieve **free/busy status** information for the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080D8

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:fburl

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.10

**Consuming references:** [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidFreeBusyLocation

### 2.142 PidLidGlobalObjectId

**Canonical name:** PidLidGlobalObjectId

**Description:** Contains an ID for an object that represents an exception to a recurring series.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000003

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.27

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXWAVLS\]](#)

**Alternate names:** LID\_GLOBAL\_OBJID

### 2.143 PidLidHasPicture

**Canonical name:** PidLidHasPicture

**Description:** Specifies whether the attachment has a picture.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008015

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.8.1

**Alternate names:** dispidHasPicture

### 2.144 PidLidHomeAddress

**Canonical name:** PidLidHomeAddress

**Description:** Specifies the complete address of the home address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:homepostaladdress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidHomeAddress

### 2.145 PidLidHomeAddressCountryCode

**Canonical name:** PidLidHomeAddressCountryCode

**Description:** Specifies the country code portion of the home address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DA

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidHomeAddressCountryCode

## 2.146 PidLidHtml

**Canonical name:** PidLidHtml

**Description:** Specifies the business webpage URL of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.12

**Alternate names:** dispidHTML

## 2.147 PidLidICalendarDayOfWeekMask

**Canonical name:** PidLidICalendarDayOfWeekMask

**Description:** Identifies the day of the week for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001001

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.27

**Alternate names:** <http://schemas.microsoft.com/mapi/dayofweekmask>

## 2.148 PidLidInboundICalStream

**Canonical name:** PidLidInboundICalStream

**Description:** Contains the contents of the iCalendar **MIME part** of the original **MIME message**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827A

**Data type:** PtypBinary, 0x0102

**Area:** Calendar

**Defining reference:** [\[MS-OXCICAL\]](#) section 2.2.1

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InboundICalStream, dispidInboundICalStream

## 2.149 PidLidInfoPathFormName

**Canonical name:** PidLidInfoPathFormName

**Description:** Contains the name of the form associated with this message.



**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085B1

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.27

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.150 PidLidInstantMessagingAddress

**Canonical name:** PidLidInstantMessagingAddress

**Description:** Specifies the instant messaging address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008062

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.6

**Consuming reference:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidInstMsg

### 2.151 PidLidIntendedBusyStatus

**Canonical name:** PidLidIntendedBusyStatus

**Description:** Contains the value of the **PidLidBusyStatus** property (section [2.47](#)) on the Meeting object in the organizer's calendar at the time that the Meeting Request object or Meeting Update object was sent.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008224

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/intendedbusystatus>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidIntendedBusyStatus

### 2.152 PidLidInternetAccountName

**Canonical name:** PidLidInternetAccountName

**Description:** Specifies the user-visible email account name through which the email message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008580

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.62

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidInetAcctName

### 2.153 PidLidInternetAccountStamp

**Canonical name:** PidLidInternetAccountStamp

**Description:** Specifies the email account ID through which the email message is sent.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008581

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.63

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidInetAcctStamp

### 2.154 PidLidIsContactLinked

**Canonical name:** PidLidIsContactLinked

**Description:** Specifies whether the contact is linked to other contacts.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080E0

**Data type:** PtypBoolean, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.6

**Alternate names:** dispidIsContactLinked

### 2.155 PidLidIsException

**Canonical name:** PidLidIsException

**Description:** Indicates whether the object represents an exception (including an **orphan instance**).

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000A

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/is\_exception

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.35

**Consuming references:** [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_EXCEPTION

## 2.156 PidLidIsRecurring

**Canonical name:** PidLidIsRecurring

**Description:** Specifies whether the object is associated with a recurring series.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000005

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/is\_recurring

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.13

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_RECURRING

## 2.157 PidLidIsSilent

**Canonical name:** PidLidIsSilent

**Description:** Indicates whether the user did not include any text in the body of the Meeting Response object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000004

**Data type:** PtypBoolean, 0x000B

**WebDAV:** http://schemas.microsoft.com/mapi/is\_silent

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.7

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_IS\_SILENT

## 2.158 PidLidLinkedTaskItems

**Canonical name:** PidLidLinkedTaskItems

**Description:** Indicates whether the user did not include any text in the body of the Meeting Response object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000820C

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Tasks

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.47

**Alternate names:** dispidLinkedTaskItems

## 2.159 PidLidLocation

**Canonical name:** PidLidLocation

**Description:** Specifies the location of the event.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008208

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:calendar:location

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidLocation

## 2.160 PidLidLogDocumentPosted

**Canonical name:** PidLidLogDocumentPosted

**Description:** Indicates whether the document was sent by email or posted to a server folder during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008711

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.10

**Alternate names:** dispidLogDocPosted

## 2.161 PidLidLogDocumentPrinted

**Canonical name:** PidLidLogDocumentPrinted

**Description:** Indicates whether the document was printed during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870E

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.7

**Alternate names:** dispidLogDocPrinted

## 2.162 PidLidLogDocumentRouted

**Canonical name:** PidLidLogDocumentRouted

**Description:** Indicates whether the document was sent to a routing recipient during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008710

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.9

**Alternate names:** dispidLogDocRouted

## 2.163 PidLidLogDocumentSaved

**Canonical name:** PidLidLogDocumentSaved

**Description:** Indicates whether the document was saved during journaling.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870F

**Data type:** PtypBoolean, 0x000B

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.8

**Alternate names:** dispidLogDocSaved

## 2.164 PidLidLogDuration

**Canonical name:** PidLidLogDuration

**Description:** Contains the duration, in minutes, of the activity.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008707

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.5

**Alternate names:** dispidLogDuration

## 2.165 PidLidLogEnd

**Canonical name:** PidLidLogEnd

**Description:** Contains the time, in UTC, at which the activity ended.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008708

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.4

**Alternate names:** dispidLogEnd

## 2.166 PidLidLogFlags

**Canonical name:** PidLidLogFlags

**Description:** Contains metadata about the Journal object.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000870C

**Data type:** PtypInteger32, 0x0003

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.6

**Alternate names:** dispidLogFlags

## 2.167 PidLidLogStart

**Canonical name:** PidLidLogStart

**Description:** Contains the time, in UTC, at which the activity began.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008706

**Data type:** PtypTime, 0x0040

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.3

**Alternate names:** dispidLogStart

## 2.168 PidLidLogType

**Canonical name:** PidLidLogType

**Description:** Briefly describes the journal activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008700

**Data type:** PtypString, 0x001F

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.1

**Alternate names:** dispidLogType

## 2.169 PidLidLogTypeDesc

**Canonical name:** PidLidLogTypeDesc

**Description:** Contains an expanded description of the journal activity that is being recorded.

**Property set:** PSETID\_Log {0006200A-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008712

**Data type:** PtypString, 0x001F

**Area:** Journal

**Defining reference:** [\[MS-OXOJRNL\]](#) section 2.2.1.2

**Alternate names:** dispidLogTypeDesc

## 2.170 PidLidMeetingType

**Canonical name:** PidLidMeetingType

**Description:** Indicates the type of Meeting Request object or Meeting Update object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000026

**Data type:** PtypInteger32, 0x0003

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.5

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMeetingType

## 2.171 PidLidMeetingWorkspaceUrl

**Canonical name:** PidLidMeetingWorkspaceUrl

**Description:** Specifies the URL of the **Meeting Workspace** that is associated with a Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008209

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/meetingworkspaceurl

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.48

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidMWSURL

## 2.172 PidLidMonthInterval

**Canonical name:** PidLidMonthInterval

**Description:** Indicates the monthly interval of the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000013

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/month\_interval

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.33

**Alternate names:** LID\_MONTH\_INTERVAL

## 2.173 PidLidMonthOfYear

**Canonical name:** PidLidMonthOfYear

**Description:** Indicates the month of the year in which the appointment or meeting occurs.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001006

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/monthofyear

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.34

## 2.174 PidLidMonthOfYearMask

**Canonical name:** PidLidMonthOfYearMask

**Description:** Indicates the calculated month of the year in which the appointment or meeting occurs.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}



**Property long ID (LID):** 0x00000017

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/moy\_mask

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.35

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_MOY\_MASK

## 2.175 PidLidNetShowUrl

**Canonical name:** PidLidNetShowUrl

**Description:** Specifies the URL to be launched when the user joins the meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008248

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.8

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidNetShowURL

## 2.176 PidLidNoEndDateFlag

**Canonical name:** PidLidNoEndDateFlag

**Description:** Indicates whether the recurrence pattern has an end date.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.36

**Alternate names:** http://schemas.microsoft.com/mapi/fnoenddate

## 2.177 PidLidNonSendableBcc

**Canonical name:** PidLidNonSendableBcc

**Description:** Contains a list of all of the unsendable attendees who are also resources.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008538

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendablebcc

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.21

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableBCC

### 2.178 PidLidNonSendableCc

**Canonical name:** PidLidNonSendableCc

**Description:** Contains a list of all of the unsendable attendees who are also optional attendees.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008537

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendablebcc

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.20

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableCC

### 2.179 PidLidNonSendableTo

**Canonical name:** PidLidNonSendableTo

**Description:** Contains a list of all of the unsendable attendees who are also required attendees.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008536

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendableto

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.19

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendableTo

### 2.180 PidLidNonSendBccTrackStatus

**Canonical name:** PidLidNonSendBccTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008545

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendbcctrackstatus

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.24

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendBccTrackStatus

### 2.181 PidLidNonSendCcTrackStatus

**Canonical name:** PidLidNonSendCcTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008544

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendccctrackstatus

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.23

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendCcTrackStatus

### 2.182 PidLidNonSendToTrackStatus

**Canonical name:** PidLidNonSendToTrackStatus

**Description:** Contains the value from the response table.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008543

**Data type:** PtypMultipleInteger32, 0x1003

**WebDAV:** http://schemas.microsoft.com/mapi/nonsendtoctrackstatus

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.22

**Consuming references:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidNonSendToTrackStatus

### 2.183 PidLidNoteColor

**Canonical name:** PidLidNoteColor

**Description:** Specifies the suggested background color of the **Note object**.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B00

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.1

**Alternate names:** dispidNoteColor

### 2.184 PidLidNoteHeight

**Canonical name:** PidLidNoteHeight

**Description:** Specifies the height of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B03

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.3

**Alternate names:** dispidNoteHeight

### 2.185 PidLidNoteWidth

**Canonical name:** PidLidNoteWidth

**Description:** Specifies the width of the visible message window in pixels.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B02

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.2

**Alternate names:** dispidNoteWidth

### 2.186 PidLidNoteX

**Canonical name:** PidLidNoteX

**Description:** Specifies the distance, in pixels, from the left edge of the screen that a user interface displays a Note object.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B04

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.4

**Alternate names:** dispidNoteX

## 2.187 PidLidNoteY

**Canonical name:** PidLidNoteY

**Description:** Specifies the distance, in pixels, from the top edge of the screen that a user interface displays a Note object.

**Property set:** PSETID\_Note {0006200E-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008B05

**Data type:** PtypInteger32, 0x0003

**Area:** Sticky Notes

**Defining reference:** [\[MS-OXONOTE\]](#) section 2.2.1.5

**Alternate names:** dispidNoteY

## 2.188 PidLidOccurrences

**Canonical name:** PidLidOccurrences

**Description:** Indicates the number of occurrences in the recurring appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00001005

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/occurrences>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.43

## 2.189 PidLidOldLocation

**Canonical name:** PidLidOldLocation

**Description:** Indicates the original value of the **PidLidLocation** property (section [2.159](#)) before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000028

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.7

**Alternate names:** dispidOldLocation

### 2.190 PidLidOldRecurrenceType

**Canonical name:** PidLidOldRecurrenceType

**Description:** Indicates the recurrence pattern for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000018

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/recur\_type

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.44

**Alternate names:** LID\_RECUR\_TYPE

### 2.191 PidLidOldWhenEndWhole

**Canonical name:** PidLidOldWhenEndWhole

**Description:** Indicates the original value of the **PidLidAppointmentEndWhole** property (section [2.14](#)) before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000002A

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.9

**Alternate names:** dispidOldWhenEndWhole

### 2.192 PidLidOldWhenStartWhole

**Canonical name:** PidLidOldWhenStartWhole

**Description:** Indicates the original value of the **PidLidAppointmentStartWhole** property (section [2.29](#)) before a meeting update.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000029

**Data type:** PtypTime, 0x0040

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.6.8

**Alternate names:** dispidOldWhenStartWhole

### 2.193 PidLidOnlinePassword

**Canonical name:** PidLidOnlinePassword

**Description:** Specifies the password for a meeting on which the **PidLidConferencingType** property (section [2.66](#)) has the value 0x00000002.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008249

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.9

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** dispidOnlinePassword

### 2.194 PidLidOptionalAttendees

**Canonical name:** PidLidOptionalAttendees

**Description:** Specifies optional attendees.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000007

**Data type:** PtypString, 0x001F

**WebDAV:** [http://schemas.microsoft.com/mapi/optional\\_attendees](http://schemas.microsoft.com/mapi/optional_attendees)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.45

**Alternate names:** LID\_OPTIONAL\_ATTENDEES

### 2.195 PidLidOrganizerAlias

**Canonical name:** PidLidOrganizerAlias

**Description:** Specifies the email address of the organizer.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008243

**Data type:** PtypString, 0x001F

**Area:** Conferencing

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.51.6

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidOrgAlias

## 2.196 PidLidOriginalStoreEntryId

**Canonical name:** PidLidOriginalStoreEntryId

**Description:** Specifies the EntryID of the delegator's message store.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008237

**Data type:** PtypBinary, 0x0102

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.9

**Alternate names:** dispidOrigStoreEid, <http://schemas.microsoft.com/mapi/origstoreeid>

## 2.197 PidLidOtherAddress

**Canonical name:** PidLidOtherAddress

**Description:** Specifies the complete address of the other address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801C

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:otherpostaladdress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidOtherAddress

## 2.198 PidLidOtherAddressCountryCode

**Canonical name:** PidLidOtherAddressCountryCode

**Description:** Specifies the country code portion of the other address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DC

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidOtherAddressCountryCode



## 2.199 PidLidOwnerCriticalChange

**Canonical name:** PidLidOwnerCriticalChange

**Description:** Specifies the date and time at which a Meeting Request object was sent by the organizer.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000001A

**Data type:** PtypTime, 0x0040

**WebDAV:** urn:schemas:calendar:dtstamp,  
http://schemas.microsoft.com/mapi/owner\_critical\_change

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.34

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_OWNER\_CRITICAL\_CHANGE

## 2.200 PidLidOwnerName

**Canonical name:** PidLidOwnerName

**Description:** Indicates the name of the owner of the **mailbox**.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000822E

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/ownername

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.47

**Alternate names:** dispidOwnerName

## 2.201 PidLidPendingStateForSiteMailboxDocument

**Canonical name:** PidLidPendingStateForSiteMailboxDocument

**Description:** Specifies the synchronization state of the **Document object** that is in the Document Libraries folder of the **site mailbox**.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085E0

**Data type:** PtypInteger32, 0x0003

**Area:** Site Mailbox

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.34

**Alternate names:** dispidPendingStateforTMDocument

## 2.202 PidLidPercentComplete

**Canonical name:** PidLidPercentComplete

**Description:** Indicates whether a time-flagged Message object is complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008102

**Data type:** PtypFloating64, 0x0005

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidPercentComplete

## 2.203 PidLidPostalAddressId

**Canonical name:** PidLidPostalAddressId

**Description:** Specifies which physical address is the mailing address for this contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008022

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:contacts:mailingaddressid

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** dispidPostalAddressId

## 2.204 PidLidPostRssChannel

**Canonical name:** PidLidPostRssChannel

**Description:** Contains the contents of the title field from the **XML** of the Atom feed or RSS channel.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008904

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.5

**Alternate names:** dispidPostRssChannel

## 2.205 PidLidPostRssChannelLink

**Canonical name:** PidLidPostRssChannelLink

**Description:** Contains the URL of the RSS or Atom feed from which the XML file came.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008900

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.1

**Alternate names:** dispidPostRssChannelLink

## 2.206 PidLidPostRssItemGuid

**Canonical name:** PidLidPostRssItemGuid

**Description:** Contains a unique identifier for the RSS object.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008903

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.4

**Alternate names:** dispidPostRssItemGuid

## 2.207 PidLidPostRssItemHash

**Canonical name:** PidLidPostRssItemHash

**Description:** Contains a hash of the feed XML computed by using an implementation-dependent algorithm.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008902

**Data type:** PtypInteger32, 0x0003

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.3

**Alternate names:** dispidPostRssItemHash

## 2.208 PidLidPostRssItemLink

**Canonical name:** PidLidPostRssItemLink

**Description:** Contains the URL of the link from an RSS or Atom item.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008901

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.2

**Alternate names:** dispidPostRssItemLink

## 2.209 PidLidPostRssItemXml

**Canonical name:** PidLidPostRssItemXml

**Description:** Contains the item element and all of its sub-elements from an RSS feed, or the entry element and all of its sub-elements from an Atom feed.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008905

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.6

**Alternate names:** dispidPostRssItemXml

## 2.210 PidLidPostRssSubscription

**Canonical name:** PidLidPostRssSubscription

**Description:** Contains the user's preferred name for the RSS or Atom subscription.

**Property set:** PSETID\_PostRss {00062041-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008906

**Data type:** PtypString, 0x001F

**Area:** RSS

**Defining reference:** [\[MS-OXORSS\]](#) section 2.2.1.7

**Alternate names:** dispidPostRssSubscription

## 2.211 PidLidPrivate

**Canonical name:** PidLidPrivate

**Description:** Indicates whether the end user wishes for this Message object to be hidden from other users who have access to the Message object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008506

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.15

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidPrivate

## 2.212 PidLidPromptSendUpdate

**Canonical name:** PidLidPromptSendUpdate

**Description:** Indicates that the Meeting Response object was out-of-date when it was received.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypBoolean, 0x000B

**Area:** Meeting Response

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.7.8

**Alternate names:** dispidPromptSendUpdate

## 2.213 PidLidRecurrenceDuration

**Canonical name:** PidLidRecurrenceDuration

**Description:** Identifies the length, in minutes, of the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000100D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/recurduration>

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.48

## 2.214 PidLidRecurrencePattern

**Canonical name:** PidLidRecurrencePattern

**Description:** Specifies a description of the recurrence pattern of the Calendar object.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008232

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/recurpattern>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.46

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurPattern

## 2.215 PidLidRecurrenceType

**Canonical name:** PidLidRecurrenceType

**Description:** Specifies the recurrence type of the recurring series.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008231

**Data type:** PtypInteger32, 0x0003

**WebDAV:** <http://schemas.microsoft.com/mapi/recurtype>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.45

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurType

## 2.216 PidLidRecurring

**Canonical name:** PidLidRecurring

**Description:** Specifies whether the object represents a recurring series.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008223

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/recurring>

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidRecurring

## 2.217 PidLidReferenceEntryId

**Canonical name:** PidLidReferenceEntryId

**Description:** Specifies the value of the EntryID of the Contact object unless the Contact object is a copy of an earlier original.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BD

**Data type:** PtypBinary, 0x0102

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.1

**Alternate names:** dispidReferenceEID

## 2.218 PidLidReminderDelta

**Canonical name:** PidLidReminderDelta

**Description:** Specifies the interval, in minutes, between the time at which the reminder first becomes overdue and the start time of the Calendar object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008501

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderDelta, <http://schemas.microsoft.com/mapi/reminderdelta>

## 2.219 PidLidReminderFileParameter

**Canonical name:** PidLidReminderFileParameter

**Description:** Specifies the filename of the sound that a client is to play when the reminder for that object becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851F

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderfileparam>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderFileParam

## 2.220 PidLidReminderOverride

**Canonical name:** PidLidReminderOverride

**Description:** Specifies whether the client is to respect the current values of the **PidLidReminderPlaySound** property (section [2.221](#)) and the **PidLidReminderFileParameter** property (section [2.219](#)), or use the default values for those properties.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851C

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderoverride>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.5

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderOverride

## 2.221 PidLidReminderPlaySound

**Canonical name:** PidLidReminderPlaySound

**Description:** Specifies whether the client is to play a sound when the reminder becomes overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851E

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderplaysound>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.6

**Consuming reference:** [\[MS-XWDCAL\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** dispidReminderPlaySound

## 2.222 PidLidReminderSet

**Canonical name:** PidLidReminderSet

**Description:** Specifies whether a reminder is set on the object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008503

**Data type:** PtypBoolean, 0x000B

**WebDAV:** <http://schemas.microsoft.com/mapi/reminderset>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.1



**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderSet

### 2.223 PidLidReminderSignalTime

**Canonical name:** PidLidReminderSignalTime

**Description:** Specifies the point in time when a reminder transitions from pending to overdue.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008560

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindernexttime>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidReminderNextTime

### 2.224 PidLidReminderTime

**Canonical name:** PidLidReminderTime

**Description:** Specifies the initial **signal time** for objects that are not Calendar objects.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008502

**Data type:** PtypTime, 0x0040

**WebDAV:** <http://schemas.microsoft.com/mapi/remindertime>

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderTime

### 2.225 PidLidReminderTimeDate

**Canonical name:** PidLidReminderTimeDate

**Description:** Indicates the time and date of the reminder for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008505

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindertimedate

**Area:** Reminders

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.59

**Alternate names:** dispidReminderTimeDate

## 2.226 PidLidReminderTimeTime

**Canonical name:** PidLidReminderTimeTime

**Description:** Indicates the time of the reminder for the appointment or meeting.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008504

**Data type:** PtypTime, 0x0040

**WebDAV:** http://schemas.microsoft.com/mapi/remindertimetime

**Area:** Reminders

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.60

**Consuming references:** [\[MS-OXONOTE\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidReminderTimeTime

## 2.227 PidLidReminderType

**Canonical name:** PidLidReminderType

**Description:** This property is not set and, if set, is ignored.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000851D

**Data type:** PtypInteger32, 0x0003

**Area:** Reminders

**Defining reference:** [\[MS-OXORMDR\]](#) section 2.2.1.9

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** dispidReminderType, http://schemas.microsoft.com/mapi/remindertype

## 2.228 PidLidRemoteStatus

**Canonical name:** PidLidRemoteStatus

**Description:** Indicates the remote status of the calendar item.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008511

**Data type:** PtypInteger32, 0x0003

**WebDAV:** http://schemas.microsoft.com/mapi/remotestatus

**Area:** Run-time configuration

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.62

**Alternate names:** dispidRemoteStatus

## 2.229 PidLidRequiredAttendees

**Canonical name:** PidLidRequiredAttendees

**Description:** Identifies required attendees for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000006

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/required\_attendees

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.63

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_REQUIRED\_ATTENDEES

## 2.230 PidLidResourceAttendees

**Canonical name:** PidLidResourceAttendees

**Description:** Identifies resource attendees for the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000008

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/resource\_attendees

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.64

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_RESOURCE\_ATTENDEES

## 2.231 PidLidResponseStatus

**Canonical name:** PidLidResponseStatus

**Description:** Specifies the response status of an attendee.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008218

**Data type:** PtypInteger32, 0x0003

**WebDAV:** urn:schemas:calendar:attendeestatus, http://schemas.microsoft.com/mapi/responsestatus

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidResponseStatus

## 2.232 PidLidServerProcessed

**Canonical name:** PidLidServerProcessed

**Description:** Indicates whether the Meeting Request object or Meeting Update object has been processed.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CC

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.4

**Alternate names:** dispidExchangeProcessed

## 2.233 PidLidServerProcessingActions

**Canonical name:** PidLidServerProcessingActions

**Description:** Indicates what processing actions have been taken on this Meeting Request object or Meeting Update object.

**Property set:** PSETID\_CalendarAssistant {11000E07-B51B-40D6-AF21-CAA85EDAB1D0}

**Property long ID (LID):** 0x000085CD

**Data type:** PtypInteger32, 0x0003

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.5

**Alternate names:** dispidExchangeProcessingAction

## 2.234 PidLidSharingAnonymity

**Canonical name:** PidLidSharingAnonymity

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A19

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingAnonymity

### 2.235 PidLidSharingBindingEntryId

**Canonical name:** PidLidSharingBindingEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2D

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingBindingEid

### 2.236 PidLidSharingBrowseUrl

**Canonical name:** PidLidSharingBrowseUrl

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A51

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingBrowseUrl

### 2.237 PidLidSharingCapabilities

**Canonical name:** PidLidSharingCapabilities

**Description:** Indicates that the Message object relates to a **special folder**.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A17

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.1

**Alternate names:** dispidSharingCaps

### 2.238 PidLidSharingConfigurationUrl

**Canonical name:** PidLidSharingConfigurationUrl

**Description:** Contains a zero-length string.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A24

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.3

**Alternate names:** dispidSharingConfigUrl

### 2.239 PidLidSharingDataRangeEnd

**Canonical name:** PidLidSharingDataRangeEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A45

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDataRangeEnd

### 2.240 PidLidSharingDataRangeStart

**Canonical name:** PidLidSharingDataRangeStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A44

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDataRangeStart

## 2.241 PidLidSharingDetail

**Canonical name:** PidLidSharingDetail

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingDetail

## 2.242 PidLidSharingExtensionXml

**Canonical name:** PidLidSharingExtensionXml

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A21

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingExtXml

## 2.243 PidLidSharingFilter

**Canonical name:** PidLidSharingFilter

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A13

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFilter

## 2.244 PidLidSharingFlags

**Canonical name:** PidLidSharingFlags

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFlags

## 2.245 PidLidSharingFlavor

**Canonical name:** PidLidSharingFlavor

**Description:** Indicates the type of Sharing Message object.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A18

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.5

**Alternate names:** dispidSharingFlavor

## 2.246 PidLidSharingFolderEntryId

**Canonical name:** PidLidSharingFolderEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A15

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingFolderEid

## 2.247 PidLidSharingIndexEntryId

**Canonical name:** PidLidSharingIndexEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}



**Property long ID (LID):** 0x00008A2E

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingIndexEid

## 2.248 PidLidSharingInitiatorEntryId

**Canonical name:** PidLidSharingInitiatorEntryId

**Description:** Contains the value of the **PidTagEntryId** property (section [2.674](#)) for the Address Book object of the currently logged-on user.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A09

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.7

**Alternate names:** dispidSharingInitiatorEid

## 2.249 PidLidSharingInitiatorName

**Canonical name:** PidLidSharingInitiatorName

**Description:** Contains the value of the **PidTagDisplayName** property (section [2.667](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.248](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A07

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.8

**Alternate names:** dispidSharingInitiatorName

## 2.250 PidLidSharingInitiatorSmtip

**Canonical name:** PidLidSharingInitiatorSmtip

**Description:** Contains the value of the **PidTagSmtipAddress** property (section [2.1010](#)) from the Address Book object identified by the **PidLidSharingInitiatorEntryId** property (section [2.248](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A08

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.9

**Alternate names:** dispidSharingInitiatorSntp

### 2.251 PidLidSharingInstanceGuid

**Canonical name:** PidLidSharingInstanceGuid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingInstanceGuid

### 2.252 PidLidSharingLastAutoSyncTime

**Canonical name:** PidLidSharingLastAutoSyncTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A55

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLastAutoSync

### 2.253 PidLidSharingLastSyncTime

**Canonical name:** PidLidSharingLastSyncTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1F

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLastSync

## 2.254 PidLidSharingLocalComment

**Canonical name:** PidLidSharingLocalComment

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalComment

## 2.255 PidLidSharingLocalLastModificationTime

**Canonical name:** PidLidSharingLocalLastModificationTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A23

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalLastMod

## 2.256 PidLidSharingLocalName

**Canonical name:** PidLidSharingLocalName

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalName

## 2.257 PidLidSharingLocalPath

**Canonical name:** PidLidSharingLocalPath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalPath

## 2.258 PidLidSharingLocalStoreUid

**Canonical name:** PidLidSharingLocalStoreUid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A49

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalStoreUid

## 2.259 PidLidSharingLocalType

**Canonical name:** PidLidSharingLocalType

**Description:** Contains the value of the **PidTagContainerClass** property (section [2.633](#)) of the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A14

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.10

**Alternate names:** dispidSharingLocalType

## 2.260 PidLidSharingLocalUid

**Canonical name:** PidLidSharingLocalUid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A10

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingLocalUid

### 2.261 PidLidSharingOriginalMessageEntryId

**Canonical name:** PidLidSharingOriginalMessageEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A29

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingOriginalMessageEid

### 2.262 PidLidSharingParentBindingEntryId

**Canonical name:** PidLidSharingParentBindingEntryId

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5C

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingParentBindingEid

### 2.263 PidLidSharingParticipants

**Canonical name:** PidLidSharingParticipants

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1E

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingParticipants

## 2.264 PidLidSharingPermissions

**Canonical name:** PidLidSharingPermissions

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingPermissions

## 2.265 PidLidSharingProviderExtension

**Canonical name:** PidLidSharingProviderExtension

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingProviderExtension

## 2.266 PidLidSharingProviderGuid

**Canonical name:** PidLidSharingProviderGuid

**Description:** Contains the value "%xAE.F0.06.00.00.00.00.00.C0.00.00.00.00.00.46".

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A01

**Data type:** PtypBinary, 0x0102

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.12

**Alternate names:** dispidSharingProviderGuid

## 2.267 PidLidSharingProviderName

**Canonical name:** PidLidSharingProviderName

**Description:** Contains a user-displayable name of the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A02

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.14

**Alternate names:** dispidSharingProviderName

## 2.268 PidLidSharingProviderUrl

**Canonical name:** PidLidSharingProviderUrl

**Description:** Contains a URL related to the sharing provider identified by the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A03

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.16

**Alternate names:** dispidSharingProviderUrl

## 2.269 PidLidSharingRangeEnd

**Canonical name:** PidLidSharingRangeEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A47

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRangeEnd

## 2.270 PidLidSharingRangeStart

**Canonical name:** PidLidSharingRangeStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A46

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRangeStart

## 2.271 PidLidSharingReciprocation

**Canonical name:** PidLidSharingReciprocation

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingReciprocation

## 2.272 PidLidSharingRemoteByteSize

**Canonical name:** PidLidSharingRemoteByteSize

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4B

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Consuming reference:** [MS-OXSHARE]

**Alternate names:** dispidSharingRemoteByteSize



### 2.273 PidLidSharingRemoteComment

**Canonical name:** PidLidSharingRemoteComment

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2F

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteComment

### 2.274 PidLidSharingRemoteCrc

**Canonical name:** PidLidSharingRemoteCrc

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteCrc

### 2.275 PidLidSharingRemoteLastModificationTime

**Canonical name:** PidLidSharingRemoteLastModificationTime

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A22

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteLastMod

### 2.276 PidLidSharingRemoteMessageCount

**Canonical name:** PidLidSharingRemoteMessageCount

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4F

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteMsgCount

### 2.277 PidLidSharingRemoteName

**Canonical name:** PidLidSharingRemoteName

**Description:** Contains the value of the **PidTagDisplayName** property (section [2.667](#)) on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A05

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.1

**Alternate names:** dispidSharingRemoteName

### 2.278 PidLidSharingRemotePass

**Canonical name:** PidLidSharingRemotePass

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemotePass

### 2.279 PidLidSharingRemotePath

**Canonical name:** PidLidSharingRemotePath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A04

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemotePath

## 2.280 PidLidSharingRemoteStoreUid

**Canonical name:** PidLidSharingRemoteStoreUid

**Description:** Contains a hexadecimal string representation of the value of the **PidTagStoreEntryId** property (section [2.1018](#)) on the folder being shared.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A48

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.3

**Alternate names:** dispidSharingRemoteStoreUid

## 2.281 PidLidSharingRemoteType

**Canonical name:** PidLidSharingRemoteType

**Description:** Contains the same value as the **PidLidSharingLocalType** property (section [2.259](#)).

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A1D

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.5

**Alternate names:** dispidSharingRemoteType

## 2.282 PidLidSharingRemoteUid

**Canonical name:** PidLidSharingRemoteUid

**Description:** Contains the EntryID of the folder being shared.

**Property set:** PSTID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A06

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.7

**Alternate names:** dispidSharingRemoteUid

### 2.283 PidLidSharingRemoteUser

**Canonical name:** PidLidSharingRemoteUser

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A0C

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteUser

### 2.284 PidLidSharingRemoteVersion

**Canonical name:** PidLidSharingRemoteVersion

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A5B

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRemoteVersion

### 2.285 PidLidSharingResponseTime

**Canonical name:** PidLidSharingResponseTime

**Description:** Contains the time at which the recipient of the sharing request sent a sharing response.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A28

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.4.1

**Alternate names:** dispidSharingResponseTime

## 2.286 PidLidSharingResponseType

**Canonical name:** PidLidSharingResponseType

**Description:** Contains the type of response with which the recipient of the sharing request responded.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A27

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.4.2

**Alternate names:** dispidSharingResponseType

## 2.287 PidLidSharingRoamLog

**Canonical name:** PidLidSharingRoamLog

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A4E

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingRoamLog

## 2.288 PidLidSharingStart

**Canonical name:** PidLidSharingStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A25

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStart

## 2.289 PidLidSharingStatus

**Canonical name:** PidLidSharingStatus

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A00

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStatus

## 2.290 PidLidSharingStop

**Canonical name:** PidLidSharingStop

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A26

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingStop

## 2.291 PidLidSharingSyncFlags

**Canonical name:** PidLidSharingSyncFlags

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A60

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingSyncFlags

## 2.292 PidLidSharingSyncInterval

**Canonical name:** PidLidSharingSyncInterval

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2A

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingSyncInterval

### 2.293 PidLidSharingTimeToLive

**Canonical name:** PidLidSharingTimeToLive

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A2C

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingTimeToLive

### 2.294 PidLidSharingTimeToLiveAuto

**Canonical name:** PidLidSharingTimeToLiveAuto

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A56

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingTimeToLiveAuto

### 2.295 PidLidSharingWorkingHoursDays

**Canonical name:** PidLidSharingWorkingHoursDays

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A42

**Data type:** PtypInteger32, 0x0003

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursDays

## 2.296 PidLidSharingWorkingHoursEnd

**Canonical name:** PidLidSharingWorkingHoursEnd

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A41

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursEnd

## 2.297 PidLidSharingWorkingHoursStart

**Canonical name:** PidLidSharingWorkingHoursStart

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A40

**Data type:** PtypTime, 0x0040

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursStart

## 2.298 PidLidSharingWorkingHoursTimeZone

**Canonical name:** PidLidSharingWorkingHoursTimeZone

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PSETID\_Sharing {00062040-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008A43

**Data type:** PtypBinary, 0x0102

**Area:** Sharing



**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

**Alternate names:** dispidSharingWorkingHoursTZ

## 2.299 PidLidSideEffects

**Canonical name:** PidLidSideEffects

**Description:** Specifies how a Message object is handled by the client in relation to certain user interface actions by the user, such as deleting a message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008510

**Data type:** PtypInteger32, 0x0003

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.16

Consuming references: [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidSideEffects

## 2.300 PidLidSingleBodyICal

**Canonical name:** PidLidSingleBodyICal

**Description:** Indicates that the original MIME message contained a single **MIME** part.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000827B

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXCICAL\]](#) section 2.2.2

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** IsSingleBodyICal, dispidIsSingleBodyICal

## 2.301 PidLidSmartNoAttach

**Canonical name:** PidLidSmartNoAttach

**Description:** Indicates whether the Message object has no end-user visible attachments.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008514

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.14

**Alternate names:** dispidSmartNoAttach

### 2.302 PidLidSpamOriginalFolder

**Canonical name:** PidLidSpamOriginalFolder

**Description:** Specifies which folder a message was in before it was filtered into the Junk Email folder.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000859C

**Data type:** PtypBinary, 0x0102

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.1

**Alternate names:** dispidSpamOriginalFolder

### 2.303 PidLidStartRecurrenceDate

**Canonical name:** PidLidStartRecurrenceDate

**Description:** Identifies the start date of the recurrence pattern.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000D

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/start\\_recur\\_date](http://schemas.microsoft.com/mapi/start_recur_date)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.66

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_START\_RECUR\_DATE

### 2.304 PidLidStartRecurrenceTime

**Canonical name:** PidLidStartRecurrenceTime

**Description:** Identifies the start time of the recurrence pattern.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000E

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/start\\_recur\\_time](http://schemas.microsoft.com/mapi/start_recur_time)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.67

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** LID\_START\_RECUR\_TIME

### 2.305 PidLidTaskAcceptanceState

**Canonical name:** PidLidTaskAcceptanceState

**Description:** Indicates the acceptance state of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812A

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.30

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskDelegValue

### 2.306 PidLidTaskAccepted

**Canonical name:** PidLidTaskAccepted

**Description:** Indicates whether a task assignee has replied to a **task request** for this **Task object**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008108

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.7

**Consuming reference:** [\[MS-OXOSFLD\]](#)

**Alternate names:** dispidTaskAccepted

### 2.307 PidLidTaskActualEffort

**Canonical name:** PidLidTaskActualEffort

**Description:** Indicates the number of minutes that the user actually spent working on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008110

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskActualEffort

### 2.308 PidLidTaskAssigner

**Canonical name:** PidLidTaskAssigner

**Description:** Specifies the name of the user that last assigned the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008121

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.24

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskDelegator

### 2.309 PidLidTaskAssigners

**Canonical name:** PidLidTaskAssigners

**Description:** Contains a stack of entries, each of which represents a task assigner.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008117

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.16

**Alternate names:** dispidTaskMyDelegators

### 2.310 PidLidTaskComplete

**Canonical name:** PidLidTaskComplete

**Description:** Indicates that the task is complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811C

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskComplete

### 2.311 PidLidTaskCustomFlags

**Canonical name:** PidLidTaskCustomFlags

**Description:** The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008139

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.33

**Alternate names:** dispidTaskCustomFlags

### 2.312 PidLidTaskDateCompleted

**Canonical name:** PidLidTaskDateCompleted

**Description:** Specifies the date when the user completed work on the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000810F

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.9

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#)

**Alternate names:** dispidTaskDateCompleted

### 2.313 PidLidTaskDeadOccurrence

**Canonical name:** PidLidTaskDeadOccurrence

**Description:** Indicates whether new occurrences remain to be generated.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008109

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.8

**Alternate names:** dispidTaskDeadOccur

### 2.314 PidLidTaskDueDate

**Canonical name:** PidLidTaskDueDate

**Description:** Specifies the date by which the user expects work on the task to be complete.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008105

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskDueDate

### 2.315 PidLidTaskEstimatedEffort

**Canonical name:** PidLidTaskEstimatedEffort

**Description:** Indicates the number of minutes that the user expects to work on a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008111

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskEstimatedEffort

### 2.316 PidLidTaskFCreator

**Canonical name:** PidLidTaskFCreator

**Description:** Indicates that the Task object was originally created by the action of the current user or user agent instead of by the processing of a task request.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811E

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.21

**Alternate names:** dispidTaskFCreator

### 2.317 PidLidTaskFFixOffline

**Canonical name:** PidLidTaskFFixOffline

**Description:** Indicates the accuracy of the **PidLidTaskOwner** property (section [2.328](#)).

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000812C

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.31

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskFFixOffline

### 2.318 PidLidTaskFRecurring

**Canonical name:** PidLidTaskFRecurring

**Description:** Indicates whether the task includes a recurrence pattern.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008126

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.28

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskFRecur

### 2.319 PidLidTaskGlobalId

**Canonical name:** PidLidTaskGlobalId

**Description:** Contains a unique GUID for this task, which is used to locate an existing task upon receipt of a task response or task update.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008519

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.32

**Alternate names:** dispidTaskGlobalObjId

### 2.320 PidLidTaskHistory

**Canonical name:** PidLidTaskHistory

**Description:** Indicates the type of change that was last made to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811A

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.18

**Alternate names:** dispidTaskHistory

### 2.321 PidLidTaskLastDelegate

**Canonical name:** PidLidTaskLastDelegate

**Description:** Contains the name of the user who most recently assigned the task, or the user to whom it was most recently assigned.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008125

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.27

**Alternate names:** dispidTaskLastDelegate

### 2.322 PidLidTaskLastUpdate

**Canonical name:** PidLidTaskLastUpdate

**Description:** Contains the date and time of the most recent change made to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008115

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.10

**Alternate names:** dispidTaskLastUpdate

### 2.323 PidLidTaskLastUser

**Canonical name:** PidLidTaskLastUser

**Description:** Contains the name of the most recent user to have been the owner of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008122

**Data type:** PtypString, 0x001F



**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.25

**Alternate names:** dispidTaskLastUser

### 2.324 PidLidTaskMode

**Canonical name:** PidLidTaskMode

**Description:** Specifies the assignment status of the embedded Task object.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008518

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.3.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** dispidTaskMode

### 2.325 PidLidTaskMultipleRecipients

**Canonical name:** PidLidTaskMultipleRecipients

**Description:** Provides optimization hints about the recipients of a Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008120

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.23

**Alternate names:** dispidTaskMultRecips

### 2.326 PidLidTaskNoCompute

**Canonical name:** PidLidTaskNoCompute

**Description:** Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008124

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.35

**Consuming reference:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskNoCompute

### 2.327 PidLidTaskOrdinal

**Canonical name:** PidLidTaskOrdinal

**Description:** Provides an aid to custom sorting of Task objects.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008123

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.26

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOrdinal

### 2.328 PidLidTaskOwner

**Canonical name:** PidLidTaskOwner

**Description:** Contains the name of the owner of the task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811F

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.22

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOwner

### 2.329 PidLidTaskOwnership

**Canonical name:** PidLidTaskOwnership

**Description:** Indicates the role of the current user relative to the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008129

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.29

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskOwnership

### 2.330 PidLidTaskRecurrence

**Canonical name:** PidLidTaskRecurrence

**Description:** Contains a **RecurrencePattern** structure that provides information about **recurring tasks**.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008116

**Data type:** PtypBinary, 0x0102

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.15

**Consuming references:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskRecur

### 2.331 PidLidTaskResetReminder

**Canonical name:** PidLidTaskResetReminder

**Description:** Indicates whether future **instances** of recurring tasks need reminders, even though the value of the **PidLidReminderSet** property (section [2.222](#)) is 0x00.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008107

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.6

**Consuming references:** [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskResetReminder

### 2.332 PidLidTaskRole

**Canonical name:** PidLidTaskRole

**Description:** Not used. The client can set this property, but it has no impact on the Task-Related Objects Protocol and is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008127

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.34

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskRole

### 2.333 PidLidTaskStartDate

**Canonical name:** PidLidTaskStartDate

**Description:** Specifies the date on which the user expects work on the task to begin.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008104

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.4

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** dispidTaskStartDate

### 2.334 PidLidTaskState

**Canonical name:** PidLidTaskState

**Description:** Indicates the current assignment state of the Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008113

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.14

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskState

### 2.335 PidLidTaskStatus

**Canonical name:** PidLidTaskStatus

**Description:** Specifies the status of a task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008101

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** dispidTaskStatus

### 2.336 PidLidTaskStatusOnComplete

**Canonical name:** PidLidTaskStatusOnComplete

**Description:** Indicates whether the task assignee has been requested to send an email message update upon completion of the assigned task.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008119

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.17

**Alternate names:** dispidTaskSOC

### 2.337 PidLidTaskUpdates

**Canonical name:** PidLidTaskUpdates

**Description:** Indicates whether the task assignee has been requested to send a task update when the assigned Task object changes.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000811B

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.19

**Alternate names:** dispidTaskUpdates

### 2.338 PidLidTaskVersion

**Canonical name:** PidLidTaskVersion

**Description:** Indicates which copy is the latest update of a Task object.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008112

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.13

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** dispidTaskVersion

### 2.339 PidLidTeamTask

**Canonical name:** PidLidTeamTask

**Description:** This property is set by the client but is ignored by the server.

**Property set:** PSETID\_Task {00062003-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008103

**Data type:** PtypBoolean, 0x000B

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.2.2.36

**Consuming References:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** dispidTeamTask

### 2.340 PidLidTimeZone

**Canonical name:** PidLidTimeZone

**Description:** Specifies information about the time zone of a recurring meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x0000000C

**Data type:** PtypInteger32, 0x0003

**WebDAV:** [http://schemas.microsoft.com/mapi/time\\_zone](http://schemas.microsoft.com/mapi/time_zone)

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.6

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_TIME\_ZONE

### 2.341 PidLidTimeZoneDescription

**Canonical name:** PidLidTimeZoneDescription

**Description:** Specifies a human-readable description of the time zone that is represented by the data in the **PidLidTimeZoneStruct** property (section [2.342](#)).

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008234

**Data type:** PtypString, 0x001F

**WebDAV:** http://schemas.microsoft.com/mapi/timezonedesc

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.40

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneDesc

### 2.342 PidLidTimeZoneStruct

**Canonical name:** PidLidTimeZoneStruct

**Description:** Specifies time zone information for a recurring meeting.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008233

**Data type:** PtypBinary, 0x0102

**WebDAV:** http://schemas.microsoft.com/mapi/timezonestruct

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.39

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** dispidTimeZoneStruct

### 2.343 PidLidToAttendeesString

**Canonical name:** PidLidToAttendeesString

**Description:** Contains a list of all of the sendable attendees who are also required attendees.

**Property set:** PSETID\_Appointment {00062002-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000823B

**Data type:** PtypString, 0x001F

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.17

**Alternate names:** dispidToAttendeesString

### 2.344 PidLidToDoOrdinalDate

**Canonical name:** PidLidToDoOrdinalDate

**Description:** Contains the current time, in UTC, which is used to determine the sort order of objects in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A0

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.13

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoOrdinalDate

### 2.345 PidLidToDoSubOrdinal

**Canonical name:** PidLidToDoSubOrdinal

**Description:** Contains the numerals 0 through 9 that are used to break a tie when the **PidLidToDoOrdinalDate** property (section [2.344](#)) is used to perform a sort of objects.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A1

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.14

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** dispidToDoSubOrdinal

### 2.346 PidLidToDoTitle

**Canonical name:** PidLidToDoTitle

**Description:** Contains user-specifiable text to identify this Message object in a consolidated to-do list.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085A4

**Data type:** PtypString, 0x001F

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

**Alternate names:** dispidToDoTitle

### 2.347 PidLidUseTnef

**Canonical name:** PidLidUseTnef

**Description:** Specifies whether **Transport Neutral Encapsulation Format (TNEF)** is to be included on a message when the message is converted from TNEF to MIME or SMTP format.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}



**Property long ID (LID):** 0x00008582

**Data type:** PtypBoolean, 0x000B

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.66

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** dispidUseTNEF

### 2.348 PidLidValidFlagStringProof

**Canonical name:** PidLidValidFlagStringProof

**Description:** Contains the value of the **PidTagMessageDeliveryTime** property (section [2.780](#)) when modifying the **PidLidFlagRequest** property (section [2.136](#)).

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000085BF

**Data type:** PtypTime, 0x0040

**Area:** Tasks

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXODOC\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** dispidValidFlagStringProof

### 2.349 PidLidVerbResponse

**Canonical name:** PidLidVerbResponse

**Description:** Specifies the voting option that a respondent has selected.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008524

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.75

**Alternate names:** dispidVerbResponse

### 2.350 PidLidVerbStream

**Canonical name:** PidLidVerbStream

**Description:** Specifies what voting responses the user can make in response to the message.

**Property set:** PSETID\_Common {00062008-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008520

**Data type:** PtypBinary, 0x0102

**Area:** Run-time configuration

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.74

**Alternate names:** dispidVerbStream

### 2.351 PidLidWeddingAnniversaryLocal

**Canonical name:** PidLidWeddingAnniversaryLocal

**Description:** Specifies the wedding anniversary of the contact, at midnight in the client's local time zone, and is saved without any time zone conversions.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DF

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.5

**Alternate names:** dispidApptAnniversaryLocal

### 2.352 PidLidWeekInterval

**Canonical name:** PidLidWeekInterval

**Description:** Identifies the number of weeks that occur between each meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000012

**Data type:** PtypInteger16, 0x0002

**WebDAV:** [http://schemas.microsoft.com/mapi/week\\_interval](http://schemas.microsoft.com/mapi/week_interval)

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.71

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_WEEK\_INTERVAL

### 2.353 PidLidWhere

**Canonical name:** PidLidWhere

**Description:** Contains the value of the **PidLidLocation** property (section [2.159](#)) from the associated Meeting object.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000002

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/mapi/where>

**Area:** Meetings

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.3

**Consuming reference:** [\[MS-XWDCAL\]](#)

**Alternate names:** LID\_WHERE

### 2.354 PidLidWorkAddress

**Canonical name:** PidLidWorkAddress

**Description:** Specifies the complete address of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000801B

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:workaddress

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** dispidWorkAddress

### 2.355 PidLidWorkAddressCity

**Canonical name:** PidLidWorkAddressCity

**Description:** Specifies the city or locality portion of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008046

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:l

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Alternate names:** dispidWorkAddressCity

### 2.356 PidLidWorkAddressCountry

**Canonical name:** PidLidWorkAddressCountry

**Description:** Specifies the country or region portion of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008049

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:co

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Alternate names:** dispidWorkAddressCountry

### 2.357 PidLidWorkAddressCountryCode

**Canonical name:** PidLidWorkAddressCountryCode

**Description:** Specifies the country code portion of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x000080DB

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.6

**Alternate names:** dispidWorkAddressCountryCode

### 2.358 PidLidWorkAddressPostalCode

**Canonical name:** PidLidWorkAddressPostalCode

**Description:** Specifies the postal code (ZIP code) portion of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008048

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postalcode

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Alternate names:** dispidWorkAddressPostalCode

### 2.359 PidLidWorkAddressPostOfficeBox

**Canonical name:** PidLidWorkAddressPostOfficeBox

**Description:** Specifies the post office box portion of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000804A

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:postofficebox

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Alternate names:** dispidWorkAddressPostOfficeBox

### 2.360 PidLidWorkAddressState

**Canonical name:** PidLidWorkAddressState

**Description:** Specifies the state or province portion of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008047

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:st

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Alternate names:** dispidWorkAddressState

### 2.361 PidLidWorkAddressStreet

**Canonical name:** PidLidWorkAddressStreet

**Description:** Specifies the street portion of the work address of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x00008045

**Data type:** PtypString, 0x001F

**WebDAV:** urn:schemas:contacts:street

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

**Alternate names:** dispidWorkAddressStreet

### 2.362 PidLidYearInterval

**Canonical name:** PidLidYearInterval

**Description:** Indicates the yearly interval of the appointment or meeting.

**Property set:** PSETID\_Meeting {6ED8DA90-450B-101B-98DA-00AA003F1305}

**Property long ID (LID):** 0x00000014

**Data type:** PtypInteger16, 0x0002

**WebDAV:** http://schemas.microsoft.com/mapi/year\_interval

**Area:** Meetings

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.7.73

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** LID\_YEAR\_INTERVAL

### 2.363 PidLidYomiCompanyName

**Canonical name:** PidLidYomiCompanyName

**Description:** Specifies the phonetic pronunciation of the company name of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802E

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/yomiorganization>

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.8

**Alternate names:** dispidYomiCompanyName

### 2.364 PidLidYomiFirstName

**Canonical name:** PidLidYomiFirstName

**Description:** Specifies the phonetic pronunciation of the given name of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802C

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/yomifirstname>

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.9

**Alternate names:** dispidYomiFirstName

### 2.365 PidLidYomiLastName

**Canonical name:** PidLidYomiLastName

**Description:** Specifies the phonetic pronunciation of the surname of the contact.

**Property set:** PSETID\_Address {00062004-0000-0000-C000-000000000046}

**Property long ID (LID):** 0x0000802D

**Data type:** PtypString, 0x001F

**WebDAV:** <http://schemas.microsoft.com/exchange/yomilastname>

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.10

**Alternate names:** dispidYomiLastName

### 2.366 PidNameAcceptLanguage

**Canonical name:** PidNameAcceptLanguage

**Description:** Contains the value of the MIME Accept-Language header.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Accept-Language

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.42

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** AcceptLanguage

### 2.367 PidNameApplicationName

**Canonical name:** PidNameApplicationName

**Description:** Specifies the application used to open the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** AppName

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.9

**Alternate names:** urn:schemas-microsoft-com:office:office#NameOfApplication

### 2.368 PidNameAttachmentMacContentType

**Canonical name:** PidNameAttachmentMacContentType

**Description:** Contains the Content-Type of the Mac attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentMacContentType

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.369 PidNameAttachmentMacInfo

**Canonical name:** PidNameAttachmentMacInfo

**Description:** Contains the headers and resource fork data associated with the Mac attachment.

**Property set:** PSETID\_Attachment {96357F7F-59E1-47D0-99A7-46515C183B54}

**Property name:** AttachmentMacInfo

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.370 PidNameAudioNotes

**Canonical name:** PidNameAudioNotes

**Description:** Contains textual annotations to a voice message after it has been delivered to the user's mailbox.

**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** UMAudioNotes

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.15

**Alternate names:** UMAudioNotes

### 2.371 PidNameAuthor

**Canonical name:** PidNameAuthor

**Description:** Specifies the author of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Author

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.3

**Alternate names:** urn:schemas-microsoft-com:office:office#Author

### 2.372 PidNameAutomaticSpeechRecognitionData

**Canonical name:** PidNameAutomaticSpeechRecognitionData

**Description:** Contains an unprotected voice message.



**Property set:** PSETID\_UnifiedMessaging {4442858E-A9E3-4E80-B900-317A210CC15B}

**Property name:** AsrData

**Data type:** PtypBinary, 0x0102

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.13

### 2.373 PidNameByteCount

**Canonical name:** PidNameByteCount

**Description:** Specifies the size, in bytes, of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ByteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.22

**Alternate names:** urn:schemas-microsoft-com:office:office#Bytes

### 2.374 PidNameCalendarAttendeeRole

**Canonical name:** PidNameCalendarAttendeeRole

**Description:** Specifies the role of the attendee.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:attendeerole

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.7

**Alternate names:** urn:schemas:calendar:attendeerole

### 2.375 PidNameCalendarBusystatus

**Canonical name:** PidNameCalendarBusystatus

**Description:** Specifies whether the attendee is busy at the time of an appointment on their calendar.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:busystatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.8

**Alternate names:** urn:schemas:calendar:busystatus

### 2.376 PidNameCalendarContact

**Canonical name:** PidNameCalendarContact

**Description:** Identifies the name of a contact who is an attendee of a meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contact

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.9

**Alternate names:** urn:schemas:calendar:contact

### 2.377 PidNameCalendarContactUrl

**Canonical name:** PidNameCalendarContactUrl

**Description:** Identifies the URL where you can access contact information in **HTML** format.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:contacturl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.10

**Alternate names:** urn:schemas:calendar:contacturl

### 2.378 PidNameCalendarCreated

**Canonical name:** PidNameCalendarCreated

**Description:** Identifies the date and time, in UTC, when the organizer created the appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:created

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.11

**Alternate names:** urn:schemas:calendar:created

### 2.379 PidNameCalendarDescriptionUrl

**Canonical name:** PidNameCalendarDescriptionUrl

**Description:** Specifies the URL of a resource that contains a description of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:descriptionurl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.12

**Alternate names:** urn:schemas:calendar:descriptionurl

### 2.380 PidNameCalendarDuration

**Canonical name:** PidNameCalendarDuration

**Description:** Identifies the duration, in seconds, of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:duration

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.13

**Alternate names:** urn:schemas:calendar:duration

### 2.381 PidNameCalendarExceptionDate

**Canonical name:** PidNameCalendarExceptionDate

**Description:** Identifies a list of dates that are exceptions to a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.14

**Alternate names:** urn:schemas:calendar:exdate

### 2.382 PidNameCalendarExceptionRule

**Canonical name:** PidNameCalendarExceptionRule

**Description:** Specifies an exception **rule** for a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:exrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.15

**Alternate names:** urn:schemas:calendar:exrule

### 2.383 PidNameCalendarGeoLatitude

**Canonical name:** PidNameCalendarGeoLatitude

**Description:** Specifies the geographical latitude of the location of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolatitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.16

**Alternate names:** urn:schemas:calendar:geolatitude

### 2.384 PidNameCalendarGeoLongitude

**Canonical name:** PidNameCalendarGeoLongitude

**Description:** Specifies the geographical longitude of the location of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:geolongitude

**Data type:** PtypFloating64, 0x0005

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.17

**Alternate names:** urn:schemas:calendar:geolongitude

### 2.385 PidNameCalendarInstanceType

**Canonical name:** PidNameCalendarInstanceType

**Description:** Specifies the type of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:instancetype

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.18

**Alternate names:** urn:schemas:calendar:instancetype

### 2.386 PidNameCalendarIsOrganizer

**Canonical name:** PidNameCalendarIsOrganizer

**Description:** Specifies whether an attendee is the organizer of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:isorganizer

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.19

**Alternate names:** urn:schemas:calendar:isorganizer

### 2.387 PidNameCalendarLastModified

**Canonical name:** PidNameCalendarLastModified

**Description:** Specifies the date and time, in UTC, when an appointment was last modified.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:lastmodified

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.20

**Alternate names:** urn:schemas:calendar:lastmodified

### 2.388 PidNameCalendarLocationUrl

**Canonical name:** PidNameCalendarLocationUrl

**Description:** Specifies a URL with location information in HTML format.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.21

**Alternate names:** urn:schemas:calendar:locationurl

### 2.389 PidNameCalendarMeetingStatus

**Canonical name:** PidNameCalendarMeetingStatus

**Description:** Specifies the status of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:meetingstatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.22

**Alternate names:** urn:schemas:calendar:meetingstatus

### 2.390 PidNameCalendarMethod

**Canonical name:** PidNameCalendarMethod

**Description:** Specifies the **iCalendar** method that is associated with an Appointment object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:method

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.23

**Alternate names:** urn:schemas:calendar:method

### 2.391 PidNameCalendarProductId

**Canonical name:** PidNameCalendarProductId

**Description:** Identifies the product that created the iCalendar-formatted **stream**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:prodid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.24

**Alternate names:** urn:schemas:calendar:prodid

### 2.392 PidNameCalendarRecurrenceIdRange

**Canonical name:** PidNameCalendarRecurrenceIdRange

**Description:** Specifies which instances of a recurring appointment are being referred to.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:recurrenceidrange

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.25

**Alternate names:** urn:schemas:calendar:recurrenceidrange

### 2.393 PidNameCalendarReminderOffset

**Canonical name:** PidNameCalendarReminderOffset

**Description:** Identifies the number of seconds before an appointment starts that a reminder is to be displayed.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:reminderoffset

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.26

**Alternate names:** urn:schemas:calendar:reminderoffset

### 2.394 PidNameCalendarResources

**Canonical name:** PidNameCalendarResources

**Description:** Identifies a list of resources, such as rooms and video equipment, that are available for an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:resources

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.27

**Alternate names:** urn:schemas:calendar:resources

### 2.395 PidNameCalendarRsvp

**Canonical name:** PidNameCalendarRsvp

**Description:** Specifies whether the organizer of an appointment or meeting requested a response.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rsvp

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.28

**Alternate names:** urn:schemas:calendar:rsvp

### 2.396 PidNameCalendarSequence

**Canonical name:** PidNameCalendarSequence

**Description:** Specifies the sequence number of a version of an appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:sequence

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.29

**Alternate names:** urn:schemas:calendar:sequence

### 2.397 PidNameCalendarTimeZone

**Canonical name:** PidNameCalendarTimeZone

**Description:** Specifies the time zone of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezone

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.30

**Alternate names:** urn:schemas:calendar:timezone

### 2.398 PidNameCalendarTimeZoneId

**Canonical name:** PidNameCalendarTimeZoneId

**Description:** Specifies the time zone identifier of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:timezoneid

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.31

**Alternate names:** urn:schemas:calendar:timezoneid

### 2.399 PidNameCalendarTransparent

**Canonical name:** PidNameCalendarTransparent

**Description:** Specifies whether an appointment or meeting is visible to busy time searches.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}



**Property name:** urn:schemas:calendar:transparent

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.32

**Alternate names:** urn:schemas:calendar:transparent

## 2.400 PidNameCalendarUid

**Canonical name:** PidNameCalendarUid

**Description:** Specifies the unique identifier of an appointment or meeting.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.33

**Alternate names:** urn:schemas:calendar:uid

## 2.401 PidNameCalendarVersion

**Canonical name:** PidNameCalendarVersion

**Description:** Identifies the version of the iCalendar specification, as specified in [\[MS-OXCICAL\]](#) section 2.1.3.1.1.3, that is required to correctly interpret an iCalendar object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:version

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.34

**Alternate names:** urn:schemas:calendar:version

## 2.402 PidNameCategory

**Canonical name:** PidNameCategory

**Description:** Specifies the category of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Category

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.18

**Alternate names:** urn:schemas-microsoft-com:office:office#Category

### 2.403 PidNameCharacterCount

**Canonical name:** PidNameCharacterCount

**Description:** Specifies the character count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CharCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.16

**Alternate names:** urn:schemas-microsoft-com:office:office#Characters

### 2.404 PidNameComments

**Canonical name:** PidNameComments

**Description:** Specifies the comments of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Comments

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.5

**Alternate names:** urn:schemas-microsoft-com:office:office#Comments

### 2.405 PidNameCompany

**Canonical name:** PidNameCompany

**Description:** Specifies the company for which the file was created.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Company

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.21

**Alternate names:** urn:schemas-microsoft-com:office:office#Company

## 2.406 PidNameContentBase

**Canonical name:** PidNameContentBase

**Description:** Specifies the value of the MIME Content-Base header, which defines the base **URI** for resolving relative URLs contained within the **message body**.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Base

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.41

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** BodyContentBase

## 2.407 PidNameContentClass

**Canonical name:** PidNameContentClass

**Description:** Contains a string that identifies the type of content of a Message object.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Class

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.48

Consuming references: [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** DAV:contentclass, urn:schemas:mailheader:content-class

## 2.408 PidNameContentType

**Canonical name:** PidNameContentType

**Description:** Specifies the type of the **body part** content.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Content-Type

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.50

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:mailheader:content-type

## 2.409 PidNameCreateDateTimeReadOnly

**Canonical name:** PidNameCreateDateTimeReadOnly

**Description:** Specifies the time, in UTC, that the file was first created.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** CreateDtmRo

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.12

**Alternate names:** urn:schemas-microsoft-com:office:office#Created

## 2.410 PidNameCrossReference

**Canonical name:** PidNameCrossReference

**Description:** Contains the name of the host (with domains omitted) and a white-space-separated list of colon-separated pairs of newsgroup names and message numbers.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Xref

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.3

**Alternate names:** urn:schemas:mailheader:xref

## 2.411 PidNameDavId

**Canonical name:** PidNameDavId

**Description:** Specifies a unique ID for the calendar item.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:id

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.2

**Alternate names:** DAV:id

## 2.412 PidNameDavIsCollection

**Canonical name:** PidNameDavIsCollection

**Description:** Indicates whether a Calendar object is a collection.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:iscollection

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.3

**Alternate names:** DAV:iscollection

### 2.413 PidNameDavIsStructuredDocument

**Canonical name:** PidNameDavIsStructuredDocument

**Description:** Indicates whether a Calendar object is a structured document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:isstructureddocument

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.4

**Alternate names:** DAV:isstructureddocument

### 2.414 PidNameDavParentName

**Canonical name:** PidNameDavParentName

**Description:** Specifies the name of the **Folder object** that contains the Calendar object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:parentname

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.5

**Alternate names:** DAV:parentname

### 2.415 PidNameDavUid

**Canonical name:** PidNameDavUid

**Description:** Specifies the unique identifier for an item.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DAV:uid

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.6

**Alternate names:** DAV:uid

#### 2.416 PidNameDocumentParts

**Canonical name:** PidNameDocumentParts

**Description:** Specifies the title of each part of the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DocParts

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.29

**Alternate names:** urn:schemas-microsoft-com:office:office#PartTitles

#### 2.417 PidNameEditTime

**Canonical name:** PidNameEditTime

**Description:** Specifies the time that the file was last edited.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** EditTime

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.10

**Alternate names:** urn:schemas-microsoft-com:office:office#TotalTime

#### 2.418 PidNameExchangeIntendedBusyStatus

**Canonical name:** PidNameExchangeIntendedBusyStatus

**Description:** Specifies the intended free/busy status of a meeting in a Meeting request.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/intendedbusystatus

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.1

**Alternate names:** http://schemas.microsoft.com/exchange/intendedbusystatus

## 2.419 PidNameExchangeJunkEmailMoveStamp

**Canonical name:** PidNameExchangeJunkEmailMoveStamp

**Description:** Indicates that the message is not to be processed by a **spam filter**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/junkemailmovestamp

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXORSS\]](#)

**Alternate names:** http://schemas.microsoft.com/exchange/junkemailmovestamp

## 2.420 PidNameExchangeModifyExceptionStructure

**Canonical name:** PidNameExchangeModifyExceptionStructure

**Description:** Specifies a structure that modifies an exception to the recurrence.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/modifyexceptionstruct

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.2

**Alternate names:** http://schemas.microsoft.com/exchange/modifyexceptionstruct

## 2.421 PidNameExchangeNoModifyExceptions

**Canonical name:** PidNameExchangeNoModifyExceptions

**Description:** Indicates whether exceptions to a recurring appointment can be modified.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/nomodifyexceptions

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.3

**Alternate names:** http://schemas.microsoft.com/exchange/nomodifyexceptions

## 2.422 PidNameExchangePatternEnd

**Canonical name:** PidNameExchangePatternEnd

**Description:** Identifies the maximum time when an instance of a recurring appointment ends.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/patternend

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.4

**Alternate names:** http://schemas.microsoft.com/exchange/patternend

### 2.423 PidNameExchangePatternStart

**Canonical name:** PidNameExchangePatternStart

**Description:** Identifies the absolute minimum time when an instance of a recurring appointment starts.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/patternstart

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.5

**Alternate names:** http://schemas.microsoft.com/exchange/patternstart

### 2.424 PidNameExchangeReminderInterval

**Canonical name:** PidNameExchangeReminderInterval

**Description:** Identifies the time, in seconds, between reminders.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/exchange/reminderinterval

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.6

**Consuming reference:** [MS-XWDCAL]

**Alternate names:** http://schemas.microsoft.com/exchange/reminderinterval

### 2.425 PidNameExchDatabaseSchema

**Canonical name:** PidNameExchDatabaseSchema

**Description:** Specifies an array of URLs that identifies other folders within the same message store that contain schema definition items.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:baseschema



**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.1

**Alternate names:** urn:schemas-microsoft-com:exch-data:baseschema

## 2.426 PidNameExchDataExpectedContentClass

**Canonical name:** PidNameExchDataExpectedContentClass

**Description:** Specifies an array of names that indicates the expected content **classes** of items within a folder.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:expected-content-class

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.2

**Alternate names:** urn:schemas-microsoft-com:exch-data:expected-content-class

## 2.427 PidNameExchDataSchemaCollectionReference

**Canonical name:** PidNameExchDataSchemaCollectionReference

**Description:** Specifies an array of names that indicates the expected content classes of items within a folder.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.5.3

**Alternate names:** urn:schemas-microsoft-com:exch-data:schema-collection-ref

## 2.428 PidNameExtractedAddresses

**Canonical name:** PidNameExtractedAddresses

**Description:** Contains an **XML document** with a single **AddressSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedAddresses

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.1

**Alternate names:** dispidXmlExtractedAddresses

## 2.429 PidNameExtractedContacts

**Canonical name:** PidNameExtractedContacts

**Description:** Contains an XML document with a single **ContactSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedContacts

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.2

**Alternate names:** dispidXmlExtractedContacts

## 2.430 PidNameExtractedEmails

**Canonical name:** PidNameExtractedEmails

**Description:** Contains an XML document with a single **EmailSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedEmails

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.3

**Alternate names:** dispidXmlExtractedEmails

## 2.431 PidNameExtractedMeetings

**Canonical name:** PidNameExtractedMeetings

**Description:** Contains an XML document with a single **MeetingSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedMeetings

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.4

**Alternate names:** dispidXmlExtractedMeetings

## 2.432 PidNameExtractedPhones

**Canonical name:** PidNameExtractedPhones

**Description:** Contains an XML document with a single **PhoneSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedPhones

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.5

**Alternate names:** dispidXmlExtractedPhones

### 2.433 PidNameExtractedTasks

**Canonical name:** PidNameExtractedTasks

**Description:** Contains an XML document with a single **TaskSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedTasks

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.6

**Alternate names:** dispidXmlExtractedTasks

### 2.434 PidNameExtractedUrls

**Canonical name:** PidNameExtractedUrls

**Description:** Contains an XML document with a single **UriSet** element.

**Property set:** PSETID\_XmlExtractedEntities {23239608-685D-4732-9C55-4C95CB4E8E33}

**Property name:** XmlExtractedUrls

**Data type:** PtypString, 0x001F

**Area:** Extracted Entities

**Defining reference:** [\[MS-OXCEXT\]](#) section 2.2.2.7

**Alternate names:** dispidXmlExtractedUrls

### 2.435 PidNameFrom

**Canonical name:** PidNameFrom

**Description:** Specifies the SMTP email **alias** of the organizer of an appointment or meeting.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** From

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.35

**Alternate names:** urn:schemas:calendar:organizer

### 2.436 PidNameHeadingPairs

**Canonical name:** PidNameHeadingPairs

**Description:** Specifies which group of headings are indented in the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HeadingPairs

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.30

**Alternate names:** urn:schemas-microsoft-com:office:office#HeadingPairs

### 2.437 PidNameHiddenCount

**Canonical name:** PidNameHiddenCount

**Description:** Specifies the hidden value of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** HiddenCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.27

**Alternate names:** urn:schemas-microsoft-com:office:office#HiddenSlides

### 2.438 PidNameHttpmailCalendar

**Canonical name:** PidNameHttpmailCalendar

**Description:** Specifies the URL for the Calendar folder for a particular user.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:calendar

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.1

**Alternate names:** urn:schemas:httpmail:calendar

## 2.439 PidNameHttpmailHtmlDescription

**Canonical name:** PidNameHttpmailHtmlDescription

**Description:** Specifies the HTML content of the message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:htmldescription

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.2

**Alternate names:** urn:schemas:httpmail:htmldescription

## 2.440 PidNameHttpmailSendMessage

**Canonical name:** PidNameHttpmailSendMessage

**Description:** Specifies the email submission URI to which outgoing email is submitted.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:httpmail:sendmsg

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.3.3

**Alternate names:** urn:schemas:httpmail:sendmsg

## 2.441 PidNameICalendarRecurrenceDate

**Canonical name:** PidNameICalendarRecurrenceDate

**Description:** Identifies an array of instances of a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rdate

**Data type:** PtypMultipleTime, 0x1040

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.36

**Alternate names:** urn:schemas:calendar:rdate

## 2.442 PidNameICalendarRecurrenceRule

**Canonical name:** PidNameICalendarRecurrenceRule

**Description:** Specifies the rule for the pattern that defines a recurring appointment.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:rrule

**Data type:** PtypMultipleString, 0x101F

**Area:** Common

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.37

**Alternate names:** urn:schemas:calendar:rrule

### 2.443 PidNameInternetSubject

**Canonical name:** PidNameInternetSubject

**Description:** Specifies the subject of the message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.4.1

**Alternate names:** urn:schemas:mailheader:subject

### 2.444 PidNameKeywords

**Canonical name:** PidNameKeywords

**Description:** Contains keywords or categories for the Message object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Keywords

**Data type:** PtypMultipleString, 0x101F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.17

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Keywords,  
<http://schemas.microsoft.com/exchange/keywords-utf8>

### 2.445 PidNameLastAuthor

**Canonical name:** PidNameLastAuthor

**Description:** Specifies the most recent author of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastAuthor

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.7

**Alternate names:** urn:schemas-microsoft-com:office:office#LastAuthor

#### 2.446 PidNameLastPrinted

**Canonical name:** PidNameLastPrinted

**Description:** Specifies the time, in UTC, that the file was last printed.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastPrinted

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.11

**Alternate names:** urn:schemas-microsoft-com:office:office#LastPrinted

#### 2.447 PidNameLastSaveDateTime

**Canonical name:** PidNameLastSaveDateTime

**Description:** Specifies the time, in UTC, that the file was last saved.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LastSaveDtm

**Data type:** PtypTime, 0x0040

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.13

**Alternate names:** urn:schemas-microsoft-com:office:office#LastSaved

#### 2.448 PidNameLineCount

**Canonical name:** PidNameLineCount

**Description:** Specifies the number of lines in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LineCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.23

**Alternate names:** urn:schemas-microsoft-com:office:office#Lines

## 2.449 PidNameLinksDirty

**Canonical name:** PidNameLinksDirty

**Description:** Indicates whether the links in the document are up-to-date.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** LinksDirty

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.31

**Alternate names:** urn:schemas-microsoft-com:office:office#LinksUpToDate

## 2.450 PidNameLocationUrl

**Canonical name:** PidNameLocationUrl

**Description:**

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** urn:schemas:calendar:locationurl

**Data type:** PtypString, 0x001F

**Area:** Calendar

**Defining reference:**

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** urn:schemas:calendar:locationurl, LocationUrl

## 2.451 PidNameManager

**Canonical name:** PidNameManager

**Description:** Specifies the manager of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Manager

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.20

**Alternate names:** urn:schemas-microsoft-com:office:office#Manager

## 2.452 PidNameMultimediaClipCount

**Canonical name:** PidNameMultimediaClipCount

**Description:** Specifies the number of multimedia clips in the file attached to the Document object.



**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** MMClipCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.28

**Alternate names:** urn:schemas-microsoft-com:office:office#MultimediaClips

### 2.453 PidNameNoteCount

**Canonical name:** PidNameNoteCount

**Description:** Specifies the number of notes in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** NoteCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.26

**Alternate names:** urn:schemas-microsoft-com:office:office#Notes

### 2.454 PidNameOMSAccountGuid

**Canonical name:** PidNameOMSAccountGuid

**Description:** Contains the GUID of the **SMS** account used to deliver the message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSAccountGuid

**Data type:** PtypString, 0x001F

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.1

### 2.455 PidNameOMSMobileModel

**Canonical name:** PidNameOMSMobileModel

**Description:** Indicates the model of the mobile device used to send the SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSMobileModel

**Data type:** PtypString, 0x001F

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.6

## 2.456 PidNameOMSScheduleTime

**Canonical name:** PidNameOMSScheduleTime

**Description:** Contains the time, in UTC, at which the client requested that the service provider send the SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSScheduleTime

**Data type:** PtypTime, 0x0040

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.2

## 2.457 PidNameOMSServiceType

**Canonical name:** PidNameOMSServiceType

**Description:** Contains the type of service used to send an SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSServiceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.3

## 2.458 PidNameOMSSourceType

**Canonical name:** PidNameOMSSourceType

**Description:** Contains the source of an SMS or MMS message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** OMSSourceType

**Data type:** PtypInteger32, 0x0003

**Area:** SMS

**Defining reference:** [\[MS-OXOSMMS\]](#) section 2.2.1.4

## 2.459 PidNamePageCount

**Canonical name:** PidNamePageCount

**Description:** Specifies the page count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PageCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.14

**Alternate names:** urn:schemas-microsoft-com:office:office#Pages

## 2.460 PidNameParagraphCount

**Canonical name:** PidNameParagraphCount

**Description:** Specifies the number of paragraphs in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** ParCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.24

**Alternate names:** urn:schemas-microsoft-com:office:office#Paragraphs

## 2.461 PidNamePhishingStamp

**Canonical name:** PidNamePhishingStamp

**Description:** Indicates whether a message is likely to be **phishing**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** http://schemas.microsoft.com/outlook/phishingstamp

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXPHISH\]](#) section 2.2.1.1

## 2.462 PidNamePresentationFormat

**Canonical name:** PidNamePresentationFormat

**Description:** Specifies the presentation format of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** PresFormat

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.19

**Alternate names:** urn:schemas-microsoft-com:office:office#PresentationFormat

## 2.463 PidNameQuarantineOriginalSender

**Canonical name:** PidNameQuarantineOriginalSender

**Description:** Specifies the original sender of a message.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** quarantine-original-sender

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCMAIL\]](#) section 2.5.4

## 2.464 PidNameRevisionNumber

**Canonical name:** PidNameRevisionNumber

**Description:** Specifies the revision number of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** RevNumber

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.8

**Alternate names:** urn:schemas-microsoft-com:office:office#Revision

## 2.465 PidNameRightsManagementLicense

**Canonical name:** PidNameRightsManagementLicense

**Description:** Specifies the value used to cache the **Use License** for the **rights-managed email message**.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** DRMLicense

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXORMMS\]](#) section 2.2.1.1

## 2.466 PidNameScale

**Canonical name:** PidNameScale

**Description:** Indicates whether the image is to be scaled or cropped.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Scale

**Data type:** PtypBoolean, 0x000B

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.32

**Alternate names:** urn:schemas-microsoft-com:office:office#ScaleCrop

## 2.467 PidNameSecurity

**Canonical name:** PidNameSecurity

**Description:** Specifies the security level of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Security

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.17

**Alternate names:** urn:schemas-microsoft-com:office:office#Security

## 2.468 PidNameSlideCount

**Canonical name:** PidNameSlideCount

**Description:** Specifies the number of slides in the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** SlideCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.25

**Alternate names:** urn:schemas-microsoft-com:office:office#Slides

## 2.469 PidNameSubject

**Canonical name:** PidNameSubject

**Description:** Specifies the subject of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Subject

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** urn:schemas-microsoft-com:office:office#Subject

## 2.470 PidNameTemplate

**Canonical name:** PidNameTemplate

**Description:** Specifies the template of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Template

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.6

**Alternate names:** urn:schemas-microsoft-com:office:office#Template

## 2.471 PidNameThumbnail

**Canonical name:** PidNameThumbnail

**Description:** Specifies the data representing the thumbnail image of the document.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Thumbnail

**Data type:** PtypBinary, 0x0102

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.33

**Alternate names:** urn:schemas-microsoft-com:office:office#ThumbNail

## 2.472 PidNameTitle

**Canonical name:** PidNameTitle

**Description:** Specifies the title of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** Title

**Data type:** PtypString, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.1

**Alternate names:** urn:schemas-microsoft-com:office:office#Title

## 2.473 PidNameWordCount

**Canonical name:** PidNameWordCount

**Description:** Specifies the word count of the file attached to the Document object.

**Property set:** PS\_PUBLIC\_STRINGS {00020329-0000-0000-C000-000000000046}

**Property name:** WordCount

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXODOC\]](#) section 2.2.1.15

**Alternate names:** urn:schemas-microsoft-com:office:office#Words

## 2.474 PidNameXCallId

**Canonical name:** PidNameXCallId

**Description:** Contains a unique identifier associated with the phone call.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallID

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.12

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.475 PidNameXFaxNumberOfPages

**Canonical name:** PidNameXFaxNumberOfPages

**Description:** Specifies how many discrete pages are contained within an attachment representing a facsimile message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-FaxNumberOfPages

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.8

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.476 PidNameXRequireProtectedPlayOnPhone

**Canonical name:** PidNameXRequireProtectedPlayOnPhone

**Description:** Indicates that the client only renders the message on a phone.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-RequireProtectedPlayOnPhone

**Data type:** PtypBoolean, 0x000B

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.14

### 2.477 PidNameXSenderTelephoneNumber

**Canonical name:** PidNameXSenderTelephoneNumber

**Description:** Contains the telephone number of the caller associated with a voice mail message.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-CallingTelephoneNumber

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.2

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### 2.478 PidNameXSharingBrowseUrl

**Canonical name:** PidNameXSharingBrowseUrl

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Browse-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

### 2.479 PidNameXSharingCapabilities

**Canonical name:** PidNameXSharingCapabilities

**Description:** Contains a string representation of the value of the **PidLidSharingCapabilities** property (section [2.237](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Capabilities

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.2



## 2.480 PidNameXSharingConfigUrl

**Canonical name:** PidNameXSharingConfigUrl

**Description:** Contains the same value as the **PidLidSharingConfigurationUrl** property (section [2.238](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Config-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.4

## 2.481 PidNameXSharingExendedCaps

**Canonical name:** PidNameXSharingExendedCaps

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Exended-Caps

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.482 PidNameXSharingFlavor

**Canonical name:** PidNameXSharingFlavor

**Description:** Contains a hexadecimal string representation of the value of the **PidLidSharingFlavor** property (section [2.245](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Flavor

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.6

## 2.483 PidNameXSharingInstanceGuid

**Canonical name:** PidNameXSharingInstanceGuid

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Instance-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

#### 2.484 PidNameXSharingLocalType

**Canonical name:** PidNameXSharingLocalType

**Description:** Contains the same value as the **PidLidSharingLocalType** property (section [2.259](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Local-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.11

#### 2.485 PidNameXSharingProviderGuid

**Canonical name:** PidNameXSharingProviderGuid

**Description:** Contains the hexadecimal string representation of the value of the **PidLidSharingProviderGuid** property (section [2.266](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Guid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.13

#### 2.486 PidNameXSharingProviderName

**Canonical name:** PidNameXSharingProviderName

**Description:** Contains the same value as the **PidLidSharingProviderName** property (section [2.267](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.15

## 2.487 PidNameXSharingProviderUrl

**Canonical name:** PidNameXSharingProviderUrl

**Description:** Contains the same value as the **PidLidSharingProviderUrl** property (section [2.268](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Provider-Url

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.2.17

## 2.488 PidNameXSharingRemoteName

**Canonical name:** PidNameXSharingRemoteName

**Description:** Contains the same value as the **PidLidSharingRemoteName** property (section [2.277](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Name

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.2

## 2.489 PidNameXSharingRemotePath

**Canonical name:** PidNameXSharingRemotePath

**Description:** Contains a value that is ignored by the server no matter what value is generated by the client.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Path

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.6

## 2.490 PidNameXSharingRemoteStoreUid

**Canonical name:** PidNameXSharingRemoteStoreUid

**Description:** Contains the same value as the **PidLidSharingRemoteStoreUid** property (section [2.282](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Store-Uid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.4

### **2.491 PidNameXSharingRemoteType**

**Canonical name:** PidNameXSharingRemoteType

**Description:** Contains the same value as the **PidLidSharingRemoteType** property (section [2.281](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Type

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.6

### **2.492 PidNameXSharingRemoteUid**

**Canonical name:** PidNameXSharingRemoteUid

**Description:** Contains the same value as the **PidLidSharingRemoteUid** property (section [2.282](#)).

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-Sharing-Remote-Uid

**Data type:** PtypString, 0x001F

**Area:** Sharing

**Defining reference:** [\[MS-OXSHARE\]](#) section 2.2.3.8

### **2.493 PidNameXVoiceMessageAttachmentOrder**

**Canonical name:** PidNameXVoiceMessageAttachmentOrder

**Description:** Contains the list of names for the audio file attachments that are to be played as part of a message, in reverse order.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-AttachmentOrder

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.10

**Consuming reference:** [\[MS-OXCMAIL\]](#)

### **2.494 PidNameXVoiceMessageDuration**

**Canonical name:** PidNameXVoiceMessageDuration

**Description:** Specifies the length of the attached audio message, in seconds.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageDuration

**Data type:** PtypInteger16, 0x0002

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.4

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.495 PidNameXVoiceMessageSenderName

**Canonical name:** PidNameXVoiceMessageSenderName

**Description:** Contains the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

**Property set:** PS\_INTERNET\_HEADERS {00020386-0000-0000-C000-000000000046}

**Property name:** X-VoiceMessageSenderName

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.6

**Consuming reference:** [\[MS-OXCMAIL\]](#)

## 2.496 PidTagAccess

**Canonical name:** PidTagAccess

**Description:** Indicates the operations available to the client for the object.

**Property ID:** 0x0FF4

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCFOLD\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOJRNL\]](#)

**Alternate names:** PR\_ACCESS, ptagAccess

## 2.497 PidTagAccessControlListData

**Canonical name:** PidTagAccessControlListData

**Description:** Contains a **permissions** list for a folder.

**Property ID:** 0x3FE0

**Data type:** PtypBinary, 0x0102

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.3

**Consuming references:** [\[MS-OXCFOLD\]](#)

**Alternate names:** PR\_ACL\_DATA, ptagACLData

## 2.498 PidTagAccessLevel

**Canonical name:** PidTagAccessLevel

**Description:** Indicates the client's access level to the object.

**Property ID:** 0x0FF7

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_ACCESS\_LEVEL, ptagAccessLevel

## 2.499 PidTagAccount

**Canonical name:** PidTagAccount

**Description:** Contains the alias of an Address Book object, which is an alternative name by which the object can be identified.

**Property ID:** 0x3A00

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_ACCOUNT, PR\_ACCOUNT\_A, PR\_ACCOUNT\_W, urn:schemas:contacts:account

## 2.500 PidTagAdditionalRenEntryIds

**Canonical name:** PidTagAdditionalRenEntryIds

**Description:** Contains the indexed entry IDs for several special folders related to conflicts, sync issues, local failures, server failures, junk email and **spam**.

**Property ID:** 0x36D8

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.4

**Consuming references:** [\[MS-OXCSPAM\]](#), [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS, ptagAdditionalRenEntryIds

## 2.501 PidTagAdditionalRenEntryIdsEx

**Canonical name:** PidTagAdditionalRenEntryIdsEx

**Description:** Contains an array of blocks that specify the EntryIDs of several special folders.

**Property ID:** 0x36D9

**Data type:** PtypBinary, 0x0102

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.5

**Alternate names:** PR\_ADDITIONAL\_REN\_ENTRYIDS\_EX, ptagAdditionalRenEntryIdsEx

## 2.502 PidTagAddressBookAuthorizedSenders

**Canonical name:** PidTagAddressBookAuthorizedSenders

**Description:** Indicates whether delivery restrictions exist for a recipient.

**Property ID:** 0x8CD8

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.42

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_AUTH\_ORIG

## 2.503 PidTagAddressBookContainerId

**Canonical name:** PidTagAddressBookContainerId

**Description:** Contains the ID of a container on an **NSPI** server.

**Property ID:** 0xFFFFD

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_CONTAINERID

## 2.504 PidTagAddressBookDeliveryContentLength

**Canonical name:** PidTagAddressBookDeliveryContentLength

**Description:** Specifies the maximum size, in bytes, of a message that a recipient can receive.

**Property ID:** 0x806A

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.27

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DELIV\_CONT\_LENGTH

## 2.505 PidTagAddressBookDisplayNamePrintable

**Canonical name:** PidTagAddressBookDisplayNamePrintable

**Description:** Contains the printable string version of the display name.

**Property ID:** 0x39FF

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.7

**Consuming reference:** [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE,  
PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_A, PR\_EMS\_AB\_DISPLAY\_NAME\_PRINTABLE\_W,  
PR\_7BIT\_DISPLAY\_NAME, PR\_7BIT\_DISPLAY\_NAME\_A, PR\_7BIT\_DISPLAY\_NAME\_W,  
ptagSimpleDisplayName

## 2.506 PidTagAddressBookDisplayTypeExtended

**Canonical name:** PidTagAddressBookDisplayTypeExtended

**Description:** Contains a value that indicates how to display an Address Book object in a table or as a recipient on a message.

**Property ID:** 0x8C93

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.35

**Alternate names:** PR\_EMS\_AB\_DISPLAY\_TYPE\_EX

## 2.507 PidTagAddressBookDistributionListExternalMemberCount

**Canonical name:** PidTagAddressBookDistributionListExternalMemberCount

**Description:** Contains the number of external recipients in the distribution list.

**Property ID:** 0x8CE3

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.30



**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_EXTERNAL\_MEMBER\_COUNT

## **2.508 PidTagAddressBookDistributionListMemberCount**

**Canonical name:** PidTagAddressBookDistributionListMemberCount

**Description:** Contains the total number of recipients in the distribution list.

**Property ID:** 0x8CE2

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.29

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_TOTAL\_MEMBER\_COUNT

## **2.509 PidTagAddressBookDistributionListMemberSubmitAccepted**

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitAccepted

**Description:** Indicates that delivery restrictions exist for a recipient.

**Property ID:** 0x8073

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.44

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_SUBMIT\_PERMS\_BL\_O

## **2.510 PidTagAddressBookDistributionListMemberSubmitRejected**

**Canonical name:** PidTagAddressBookDistributionListMemberSubmitRejected

**Description:** Indicates that delivery restrictions exist for a recipient.

**Property ID:** 0x8CDA

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.45

**Consuming references:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_SUBMIT\_PERMS

## 2.511 PidTagAddressBookDistributionListRejectMessagesFromDLMembers

**Canonical name:** PidTagAddressBookDistributionListRejectMessagesFromDLMembers

**Description:** Indicates that delivery restrictions exist for a recipient.

**Property ID:** 0x8CDB

**Data type:** PtypObject, 0x000D

**Area:** Address book

**Defining reference:** [\[MS-OXOAB\]](#) section 2.9.2.2

**Alternate names:** PR\_EMS\_AB\_DL\_MEM\_REJECT\_PERMS

## 2.512 PidTagAddressBookEntryId

**Canonical name:** PidTagAddressBookEntryId

**Description:** Contains the name-service EntryID of a directory object that refers to a **public folder**.

**Property ID:** 0x663B

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.4

**Alternate names:** PR\_ADDRESS\_BOOK\_ENTRYID, ptagAddressBookEntryId

## 2.513 PidTagAddressBookExtensionAttribute1

**Canonical name:** PidTagAddressBookExtensionAttribute1

**Description:** Contains custom values defined and populated by the organization that modified the **display templates**.

**Property ID:** 0x802D

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_1\_W

## 2.514 PidTagAddressBookExtensionAttribute10

**Canonical name:** PidTagAddressBookExtensionAttribute10

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8036

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_10\_W

### **2.515 PidTagAddressBookExtensionAttribute11**

**Canonical name:** PidTagAddressBookExtensionAttribute11

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C57

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_11\_W

### **2.516 PidTagAddressBookExtensionAttribute12**

**Canonical name:** PidTagAddressBookExtensionAttribute12

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C58

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_12\_W

### **2.517 PidTagAddressBookExtensionAttribute13**

**Canonical name:** PidTagAddressBookExtensionAttribute13

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C59

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_13\_W

## 2.518 PidTagAddressBookExtensionAttribute14

**Canonical name:** PidTagAddressBookExtensionAttribute14

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C60

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_14\_W

## 2.519 PidTagAddressBookExtensionAttribute15

**Canonical name:** PidTagAddressBookExtensionAttribute15

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8C61

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_15\_W

## 2.520 PidTagAddressBookExtensionAttribute2

**Canonical name:** PidTagAddressBookExtensionAttribute2

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x802E

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_2\_W

## 2.521 PidTagAddressBookExtensionAttribute3

**Canonical name:** PidTagAddressBookExtensionAttribute3

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x802F

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_3\_W

## 2.522 PidTagAddressBookExtensionAttribute4

**Canonical name:** PidTagAddressBookExtensionAttribute4

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8030

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_4\_W

## 2.523 PidTagAddressBookExtensionAttribute5

**Canonical name:** PidTagAddressBookExtensionAttribute5

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8031

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_5\_W

## 2.524 PidTagAddressBookExtensionAttribute6

**Canonical name:** PidTagAddressBookExtensionAttribute6

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8032

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_6\_W

### 2.525 PidTagAddressBookExtensionAttribute7

**Canonical name:** PidTagAddressBookExtensionAttribute7

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8033

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_7\_W

### 2.526 PidTagAddressBookExtensionAttribute8

**Canonical name:** PidTagAddressBookExtensionAttribute8

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8034

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_8\_W

### 2.527 PidTagAddressBookExtensionAttribute9

**Canonical name:** PidTagAddressBookExtensionAttribute9

**Description:** Contains custom values defined and populated by the organization that modified the display templates.

**Property ID:** 0x8035

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.34

**Alternate names:** PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9,  
PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9\_A, PR\_EMS\_AB\_EXTENSION\_ATTRIBUTE\_9\_W

## 2.528 PidTagAddressBookFolderPathname

**Canonical name:** PidTagAddressBookFolderPathname

**Description:** This property is deprecated and is to be ignored.

**Property ID:** 0x8004

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.4

**Alternate names:** PR\_EMS\_AB\_FOLDER\_PATHNAME, PR\_EMS\_AB\_FOLDER\_PATHNAME\_A, PR\_EMS\_AB\_FOLDER\_PATHNAME\_W

## 2.529 PidTagAddressBookHierarchicalChildDepartments

**Canonical name:** PidTagAddressBookHierarchicalChildDepartments

**Description:** Contains the child departments in a hierarchy of departments.

**Property ID:** 0x8C9A

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.1

**Alternate names:** PR\_EMS\_AB\_HAB\_CHILD\_DEPARTMENTS

## 2.530 PidTagAddressBookHierarchicalDepartmentMembers

**Canonical name:** PidTagAddressBookHierarchicalDepartmentMembers

**Description:** Contains all of the mail users that belong to this department.

**Property ID:** 0x8C97

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.3

**Alternate names:** PR\_EMS\_AB\_HAB\_DEPARTMENT\_MEMBERS

## 2.531 PidTagAddressBookHierarchicalIsHierarchicalGroup

**Canonical name:** PidTagAddressBookHierarchicalIsHierarchicalGroup

**Description:** Indicates whether the distribution list represents a **departmental group**.

**Property ID:** 0x8CDD

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.5

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_IS\_HIERARCHICAL\_GROUP, PR\_EMS\_AB\_IS\_ORGANIZATIONAL

### 2.532 PidTagAddressBookHierarchicalParentDepartment

**Canonical name:** PidTagAddressBookHierarchicalParentDepartment

**Description:** Contains all of the departments to which this department is a child.

**Property ID:** 0x8C99

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.8.2

**Alternate names:** PR\_EMS\_AB\_HAB\_PARENT\_DEPARTMENT

### 2.533 PidTagAddressBookHierarchicalRootDepartment

**Canonical name:** PidTagAddressBookHierarchicalRootDepartment

**Description:** Contains the **distinguished name (DN)** of either the root **Department object** or the root departmental group in the department hierarchy for the organization.

**Property ID:** 0x8C98

**Data type:** PtypString8, 0x001E

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.7.2

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_HAB\_ROOT\_DEPARTMENT

### 2.534 PidTagAddressBookHierarchicalShowInDepartments

**Canonical name:** PidTagAddressBookHierarchicalShowInDepartments

**Description:** Lists all Department objects of which the mail user is a member.

**Property ID:** 0x8C94

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.6

**Alternate names:** PR\_EMS\_AB\_HAB\_SHOW\_IN\_DEPARTMENTS

### 2.535 PidTagAddressBookHomeMessageDatabase

**Canonical name:** PidTagAddressBookHomeMessageDatabase



**Description:** Contains the DN expressed in the **X500 DN** format. This property is returned from a name service provider interface (NSPI) server as a **PtypEmbeddedTable**. Otherwise, the data type is **PtypString8**.

**Property ID:** 0x8006

**Data type:** **PtypString8**, 0x001E**PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.37

**Consuming references:** [\[MS-OXABREF\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_HOME\_MDB, PR\_EMS\_AB\_HOME\_MDB\_A, PR\_EMS\_AB\_HOME\_MDB\_W

## 2.536 PidTagAddressBookIsMaster

**Canonical name:** PidTagAddressBookIsMaster

**Description:** Contains a Boolean value of TRUE if it is possible to create Address Book objects in that container, and FALSE otherwise.

**Property ID:** 0xFFFFB

**Data type:** **PtypBoolean**, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.4

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MASTER

## 2.537 PidTagAddressBookIsMemberOfDistributionList

**Canonical name:** PidTagAddressBookIsMemberOfDistributionList

**Description:** Lists all of the distribution lists for which the object is a member. This property is returned from an NSPI server as a **PtypEmbeddedTable**. Otherwise, the data type is **PtypString8**.

**Property ID:** 0x8008

**Data type:** **PtypString8**, 0x001E; **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.3

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_A, PR\_EMS\_AB\_IS\_MEMBER\_OF\_DL\_W

## 2.538 PidTagAddressBookManageDistributionList

**Canonical name:** PidTagAddressBookManageDistributionList

**Description:** Contains information for use in display templates for distribution lists.

**Property ID:** 0x6704

**Data type:** **PtypObject**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.10.2

**Consuming reference:** [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGE\_DL

### **2.539 PidTagAddressBookManager**

**Canonical name:** PidTagAddressBookManager

**Description:** Contains one row that references the mail user's manager.

**Property ID:** 0x8005

**Data type:** **PtypObject**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.1

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_MANAGER, PR\_EMS\_AB\_MANAGER\_A, PR\_EMS\_AB\_MANAGER\_W

### **2.540 PidTagAddressBookManagerDistinguishedName**

**Canonical name:** PidTagAddressBookManagerDistinguishedName

**Description:** Contains the DN of the mail user's manager.

**Property ID:** 0x8005

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.9

**Alternate names:** PR\_EMS\_AB\_MANAGER\_T

### **2.541 PidTagAddressBookMember**

**Canonical name:** PidTagAddressBookMember

**Description:** Contains the members of the distribution list.

**Property ID:** 0x8009

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.1

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_MEMBER, PR\_EMS\_AB\_MEMBER\_A, PR\_EMS\_AB\_MEMBER\_W

## 2.542 PidTagAddressBookMessageId

**Canonical name:** PidTagAddressBookMessageId

**Description:** Contains the Short-term Message ID (MID) ([\[MS-OXCDATA\]](#) section 2.2.1.2) of the first message in the local site's **offline address book** public folder.

**Property ID:** 0x674F

**Data type:** PtypInteger64, 0x0014

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.2.2

**Alternate names:** ptagAddrbookMID

## 2.543 PidTagAddressBookModerationEnabled

**Canonical name:** PidTagAddressBookModerationEnabled

**Description:** Indicates whether moderation is enabled for the mail user or distribution list.

**Property ID:** 0x8CB5

**Data type:** PtypBoolean, 0x000B

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.28

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_ENABLE\_MODERATION

## 2.544 PidTagAddressBookNetworkAddress

**Canonical name:** PidTagAddressBookNetworkAddress

**Description:** Contains a list of names by which a server is known to the various transports in use by the network.

**Property ID:** 0x8170

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.38

**Alternate names:** PR\_EMS\_AB\_NETWORK\_ADDRESS, PR\_EMS\_AB\_NETWORK\_ADDRESS\_A, PR\_EMS\_AB\_NETWORK\_ADDRESS\_W

## 2.545 PidTagAddressBookObjectDistinguishedName

**Canonical name:** PidTagAddressBookObjectDistinguishedName

**Description:** Contains the DN of the Address Book object.

**Property ID:** 0x803C

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.15

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJ\_DIST\_NAME, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_A, PR\_EMS\_AB\_OBJ\_DIST\_NAME\_W

## 2.546 PidTagAddressBookObjectGuid

**Canonical name:** PidTagAddressBookObjectGuid

**Description:** Contains a GUID that identifies an Address Book object.

**Property ID:** 0x8C6D

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.25

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_OBJECT\_GUID

## 2.547 PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Canonical name:** PidTagAddressBookOrganizationalUnitRootDistinguishedName

**Description:** Contains the DN of the Organization object of the mail user's organization.

**Property ID:** 0x8CA8

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.39

**Alternate names:** PR\_EMS\_AB\_ORG\_UNIT\_ROOT\_DN, msExchOURoot

## 2.548 PidTagAddressBookOwner

**Canonical name:** PidTagAddressBookOwner

**Description:** Contains one row that references the distribution list's owner.

**Property ID:** 0x800C

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.2

**Alternate names:** PR\_EMS\_AB\_OWNER\_O

### **2.549 PidTagAddressBookOwnerBackLink**

**Canonical name:** PidTagAddressBookOwnerBackLink

**Description:** Contains a list of the distribution lists owned by a mail user.

**Property ID:** 0x8024

**Data type:** **PtypEmbeddedTable**, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.4

**Alternate names:** PR\_EMS\_AB\_OWNER\_BL\_O

### **2.550 PidTagAddressBookParentEntryId**

**Canonical name:** PidTagAddressBookParentEntryId

**Description:** Contains the EntryID of the parent container in a hierarchy of address book containers.

**Property ID:** 0xFFFC

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.5

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_EMS\_AB\_PARENT\_ENTRYID

### **2.551 PidTagAddressBookPhoneticCompanyName**

**Canonical name:** PidTagAddressBookPhoneticCompanyName

**Description:** Contains the phonetic representation of the **PidTagCompanyName** property (section [2.630](#)).

**Property ID:** 0x8C91

**Data type:** **PtypString**, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.12

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME,  
PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_COMPANY\_NAME\_W

## 2.552 PidTagAddressBookPhoneticDepartmentName

**Canonical name:** PidTagAddressBookPhoneticDepartmentName

**Description:** Contains the phonetic representation of the **PidTagDepartmentName** property (section [2.663](#)).

**Property ID:** 0x8C90

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.13

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME, PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DEPARTMENT\_NAME\_W

## 2.553 PidTagAddressBookPhoneticDisplayName

**Canonical name:** PidTagAddressBookPhoneticDisplayName

**Description:** Contains the phonetic representation of the **PidTagDisplayName** property (section [2.667](#)).

**Property ID:** 0x8C92

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.9

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME, PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_DISPLAY\_NAME\_W

## 2.554 PidTagAddressBookPhoneticGivenName

**Canonical name:** PidTagAddressBookPhoneticGivenName

**Description:** Contains the phonetic representation of the **PidTagGivenName** property (section [2.705](#)).

**Property ID:** 0x8C8E

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.10

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME, PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_A, PR\_EMS\_AB\_PHONETIC\_GIVEN\_NAME\_W

## 2.555 PidTagAddressBookPhoneticSurname

**Canonical name:** PidTagAddressBookPhoneticSurname

**Description:** Contains the phonetic representation of the **PidTagSurname** property (section [2.1026](#)).

**Property ID:** 0x8C8F

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.11

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_PHONETIC\_SURNAME, PR\_EMS\_AB\_PHONETIC\_SURNAME\_A, PR\_EMS\_AB\_PHONETIC\_SURNAME\_W

## 2.556 PidTagAddressBookProxyAddresses

**Canonical name:** PidTagAddressBookProxyAddresses

**Description:** Contains alternate email addresses for the Address Book object.

**Property ID:** 0x800F

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.23

**Consuming references:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PROXY\_ADDRESSES, PR\_EMS\_AB\_PROXY\_ADDRESSES\_A, PR\_EMS\_AB\_PROXY\_ADDRESSES\_W

## 2.557 PidTagAddressBookPublicDelegates

**Canonical name:** PidTagAddressBookPublicDelegates

**Description:** Contains a list of mail users who are allowed to send email on behalf of the mailbox owner.

**Property ID:** 0x8015

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.5

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_EMS\_AB\_PUBLIC\_DELEGATES, PR\_EMS\_AB\_PUBLIC\_DELEGATES\_A, PR\_EMS\_AB\_PUBLIC\_DELEGATES\_W

## 2.558 PidTagAddressBookReports

**Canonical name:** PidTagAddressBookReports

**Description:** Lists all of the mail user's direct reports.

**Property ID:** 0x800E

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.5.2

**Alternate names:** PR\_EMS\_AB\_REPORTS, PR\_EMS\_AB\_REPORTS\_A, PR\_EMS\_AB\_REPORTS\_W

## 2.559 PidTagAddressBookRoomCapacity

**Canonical name:** PidTagAddressBookRoomCapacity

**Description:** Contains the maximum occupancy of the room.

**Property ID:** 0x0807

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.9.1

**Alternate names:** PR\_EMS\_AB\_ROOM\_CAPACITY

## 2.560 PidTagAddressBookRoomContainers

**Canonical name:** PidTagAddressBookRoomContainers

**Description:** Contains a list of DNs that represent the address book containers that hold **Resource objects**, such as conference rooms and equipment.

**Property ID:** 0x8C96

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.7.1

**Alternate names:** PR\_EMS\_AB\_ROOM\_CONTAINERS, PR\_EMS\_AB\_ROOM\_CONTAINERS\_A, PR\_EMS\_AB\_ROOM\_CONTAINERS\_W

## 2.561 PidTagAddressBookRoomDescription

**Canonical name:** PidTagAddressBookRoomDescription

**Description:** Contains a description of the Resource object.

**Property ID:** 0x0809

**Data type:** PtypString, 0x001F

**Area:** Address Book



**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.9.2

**Alternate names:** PR\_EMS\_AB\_ROOM\_DESCRIPTION, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_A, PR\_EMS\_AB\_ROOM\_DESCRIPTION\_W

## 2.562 PidTagAddressBookSenderHintTranslations

**Canonical name:** PidTagAddressBookSenderHintTranslations

**Description:** Contains the **locale** ID and translations of the default **mail tip**.

**Property ID:** 0x8CAC

**Data type:** PtypMultipleString, 0x101F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.26

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_DL\_SENDER\_HINT\_TRANSLATIONS\_W

## 2.563 PidTagAddressBookSeniorityIndex

**Canonical name:** PidTagAddressBookSeniorityIndex

**Description:** Contains a signed integer that specifies the seniority order of Address Book objects that represent members of a department and are referenced by a Department object or departmental group, with larger values specifying members that are more senior.

**Property ID:** 0x8CA0

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.24

**Consuming reference:** [\[MS-OXOAB\]](#) **Alternate names:** PR\_EMS\_AB\_HAB\_SENIORITY\_INDEX, PR\_EMS\_AB\_SENIORITY\_INDEX

## 2.564 PidTagAddressBookTargetAddress

**Canonical name:** PidTagAddressBookTargetAddress

**Description:** Contains the foreign system email address of an Address Book object.

**Property ID:** 0x8011

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.22

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_TARGET\_ADDRESS, PR\_EMS\_AB\_TARGET\_ADDRESS\_A, PR\_EMS\_AB\_TARGET\_ADDRESS\_W

## 2.565 PidTagAddressBookUnauthorizedSenders

**Canonical name:** PidTagAddressBookUnauthorizedSenders

**Description:** Indicates whether delivery restrictions exist for a recipient.

**Property ID:** 0x8CD9

**Data type:** PtypObject, 0x000D

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.43

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_UNAUTH\_ORIG

## 2.566 PidTagAddressBookX509Certificate

**Canonical name:** PidTagAddressBookX509Certificate

**Description:** Contains the ASN\_1 DER encoded X.509 certificates for the mail user.

**Property ID:** 0x8C6A

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.35

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_X509\_CERT

## 2.567 PidTagAddressType

**Canonical name:** PidTagAddressType

**Description:** Contains the email address type of a Message object.

**Property ID:** 0x3002

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.13

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

**Alternate names:** PR\_ADDRTYPE, PR\_ADDRTYPE\_A, ptagAddrType, PR\_ADDRTYPE\_W

## 2.568 PidTagAlternateRecipientAllowed

**Canonical name:** PidTagAlternateRecipientAllowed

**Description:** Specifies whether the sender permits the message to be auto-forwarded.

**Property ID:** 0x0002

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.36

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ALTERNATE\_RECIPIENT\_ALLOWED, ptagAlternateRecipientAllowed

## 2.569 PidTagAnr

**Canonical name:** PidTagAnr

**Description:** Contains a filter value used in **ambiguous name resolution**.

**Property ID:** 0x360C

**Data type:** PtypString, 0x001F

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.10.1

**Alternate names:** PR\_ANR, PR\_ANR\_A, PR\_ANR\_W

## 2.570 PidTagArchiveDate

**Canonical name:** PidTagArchiveDate

**Description:** Specifies the date, in UTC, after which a Message object is archived by the server.

**Property ID:** 0x301F

**Data type:** PtypTime, 0x0040

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.8

**Alternate names:** PR\_ARCHIVE\_DATE, ptagArchiveDate

## 2.571 PidTagArchivePeriod

**Canonical name:** PidTagArchivePeriod

**Description:** Specifies the number of days that a Message object can remain unarchived.

**Property ID:** 0x301E

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.7

**Alternate names:** PR\_ARCHIVE\_PERIOD, ptagArchivePeriod

## 2.572 PidTagArchiveTag

**Canonical name:** PidTagArchiveTag

**Description:** Specifies the GUID of an **archive tag**.

**Property ID:** 0x3018

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.58.1

**Alternate names:** PR\_ARCHIVE\_TAG, ptagArchiveTag

## 2.573 PidTagAssistant

**Canonical name:** PidTagAssistant

**Description:** Contains the name of the mail user's administrative assistant.

**Property ID:** 0x3A30

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.8

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ASSISTANT, PR\_ASSISTANT\_A, PR\_ASSISTANT\_W, urn:schemas:contacts:secretarycn

## 2.574 PidTagAssistantTelephoneNumber

**Canonical name:** PidTagAssistantTelephoneNumber

**Description:** Contains the telephone number of the mail user's administrative assistant.

**Property ID:** 0x3A2E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.31

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ASSISTANT\_TELEPHONE\_NUMBER, PR\_ASSISTANT\_TELEPHONE\_NUMBER\_A, PR\_ASSISTANT\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:secretaryphone

## 2.575 PidTagAssociated

**Canonical name:** PidTagAssociated

**Description:** Specifies whether the message being synchronized is an FAI message.

**Property ID:** 0x67AA

**Data type:** PtypBoolean, 0x000B

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.5

**Alternate names:** ptagAssociated

## 2.576 PidTagAttachAdditionalInformation

**Canonical name:** PidTagAttachAdditionalInformation

**Description:** Contains attachment encoding information.

**Property ID:** 0x370F

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.21

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_ADDITIONAL\_INFO

## 2.577 PidTagAttachContentBase

**Canonical name:** PidTagAttachContentBase

**Description:** Contains the base of a relative URI.

**Property ID:** 0x3711

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#) **Alternate names:** PR\_ATTACH\_CONTENT\_BASE, PR\_ATTACH\_CONTENT\_BASE\_A, PR\_ATTACH\_CONTENT\_BASE\_W

## 2.578 PidTagAttachContentId

**Canonical name:** PidTagAttachContentId

**Description:** Contains a content identifier unique to the Message object that matches a corresponding "cid:" URI schema reference in the HTML body of the Message object.

**Property ID:** 0x3712

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_ID, PR\_ATTACH\_CONTENT\_ID\_A, PR\_ATTACH\_CONTENT\_ID\_W

## 2.579 PidTagAttachContentLocation

**Canonical name:** PidTagAttachContentLocation

**Description:** Contains a relative or full URI that matches a corresponding reference in the HTML body of a Message object.

**Property ID:** 0x3713

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_CONTENT\_LOCATION, PR\_ATTACH\_CONTENT\_LOCATION\_A, PR\_ATTACH\_CONTENT\_LOCATION\_W

## 2.580 PidTagAttachDataBinary

**Canonical name:** PidTagAttachDataBinary

**Description:** Contains the contents of the file to be attached.

**Property ID:** 0x3701

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_BIN, ptagAttachDataBin

## 2.581 PidTagAttachDataObject

**Canonical name:** PidTagAttachDataObject

**Description:** Contains the binary representation of the **Attachment object** in an application-specific format.

**Property ID:** 0x3701

**Data type:** PtypObject, 0x000D

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.8

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_ATTACH\_DATA\_OBJ, ptagAttachDataObj

## 2.582 PidTagAttachEncoding

**Canonical name:** PidTagAttachEncoding

**Description:** Contains encoding information about the Attachment object.

**Property ID:** 0x3702

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_ENCODING

## 2.583 PidTagAttachExtension

**Canonical name:** PidTagAttachExtension

**Description:** Contains a file name extension that indicates the document type of an attachment.

**Property ID:** 0x3703

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.12

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_EXTENSION, PR\_ATTACH\_EXTENSION\_A, PR\_ATTACH\_EXTENSION\_W

## 2.584 PidTagAttachFilename

**Canonical name:** PidTagAttachFilename

**Description:** Contains the **8.3 name** of the **PidTagAttachLongFilename** property (section [2.586](#)).

**Property ID:** 0x3704

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACH\_FILENAME, PR\_ATTACH\_FILENAME\_A, ptagAttachFilename, PR\_ATTACH\_FILENAME\_W

## 2.585 PidTagAttachFlags

**Canonical name:** PidTagAttachFlags

**Description:** Indicates which body formats might reference this attachment when rendering data.

**Property ID:** 0x3714

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.18

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACH\_FLAGS

## 2.586 PidTagAttachLongFilename

**Canonical name:** PidTagAttachLongFilename

**Description:** Contains the full filename and extension of the Attachment object.

**Property ID:** 0x3707

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.10

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOUM\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_FILENAME, PR\_ATTACH\_LONG\_FILENAME\_A, PR\_ATTACH\_LONG\_FILENAME\_W, urn:schemas:httpmail:attachmentfilename

## 2.587 PidTagAttachLongPathname

**Canonical name:** PidTagAttachLongPathname

**Description:** Contains the fully-qualified path and file name with extension.

**Property ID:** 0x370D

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.13

**Consuming reference:** [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_LONG\_PATHNAME, PR\_ATTACH\_LONG\_PATHNAME\_A, ptagAttachLongPathname, PR\_ATTACH\_LONG\_PATHNAME\_W

## 2.588 PidTagAttachmentContactPhoto

**Canonical name:** PidTagAttachmentContactPhoto



**Description:** Indicates that a contact photo attachment is attached to a Contact object.

**Property ID:** 0x7FFF

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.8.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ATTACHMENT\_CONTACTPHOTO

## 2.589 PidTagAttachmentFlags

**Canonical name:** PidTagAttachmentFlags

**Description:** Indicates special handling for an Attachment object.

**Property ID:** 0x7FFD

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.23

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRN\]](#)

**Alternate names:** PR\_ATTACHMENT\_FLAGS, ptagAttachmentFlags

## 2.590 PidTagAttachmentHidden

**Canonical name:** PidTagAttachmentHidden

**Description:** Indicates whether an Attachment object is hidden from the end user.

**Property ID:** 0x7FFE

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.24

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_ATTACHMENT\_HIDDEN

## 2.591 PidTagAttachmentLinkId

**Canonical name:** PidTagAttachmentLinkId

**Description:** Contains the type of Message object to which an attachment is linked.

**Property ID:** 0x7FFA

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.22

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-EXOJRNL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACHMENT\_LINKID, ptagAttachmentLinkId

## 2.592 PidTagAttachMethod

**Canonical name:** PidTagAttachMethod

**Description:** Represents the way the contents of an attachment are accessed.

**Property ID:** 0x3705

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODOC\]](#), [\[MS-EXOJRNL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_METHOD, ptagAttachMethod

## 2.593 PidTagAttachMimeTag

**Canonical name:** PidTagAttachMimeTag

**Description:** Contains a content-type MIME header.

**Property ID:** 0x370E

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-EXOUM\]](#)

**Alternate names:** PR\_ATTACH\_MIME\_TAG, PR\_ATTACH\_MIME\_TAG\_A, PR\_ATTACH\_MIME\_TAG\_W

## 2.594 PidTagAttachNumber

**Canonical name:** PidTagAttachNumber

**Description:** Identifies the Attachment object within its Message object.

**Property ID:** 0x0E21

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_ATTACH\_NUM, ptagAttachNum

## 2.595 PidTagAttachPathname

**Canonical name:** PidTagAttachPathname

**Description:** Contains the 8.3 name of the **PidTagAttachLongPathname** property (section [2.587](#)).

**Property ID:** 0x3708

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.14

**Consuming reference:** [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_ATTACH\_PATHNAME, PR\_ATTACH\_PATHNAME\_A, ptagAttachPathname, PR\_ATTACH\_PATHNAME\_W

## 2.596 PidTagAttachPayloadClass

**Canonical name:** PidTagAttachPayloadClass

**Description:** Contains the class name of an object that can display the contents of the message.

**Property ID:** 0x371A

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_CLASS, PR\_ATTACH\_PAYLOAD\_CLASS\_A, PR\_ATTACH\_PAYLOAD\_CLASS\_W, ptagAttachPayloadClass

## 2.597 PidTagAttachPayloadProviderGuidString

**Canonical name:** PidTagAttachPayloadProviderGuidString

**Description:** Contains the GUID of the software component that can display the contents of the message.

**Property ID:** 0x3719

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR, PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_A, PR\_ATTACH\_PAYLOAD\_PROV\_GUID\_STR\_W

## 2.598 PidTagAttachRendering

**Canonical name:** PidTagAttachRendering

**Description:** Contains a Windows Metafile, as specified in [\[MS-WMF\]](#), for the Attachment object.

**Property ID:** 0x3709

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.17

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_RENDERING, ptagAttachRendering

## 2.599 PidTagAttachSize

**Canonical name:** PidTagAttachSize

**Description:** Contains the size, in bytes, consumed by the Attachment object on the server.

**Property ID:** 0x0E20

**Data type:** PtypInteger32, 0x0003

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_ATTACH\_SIZE, ptagAttachSize

## 2.600 PidTagAttachTag

**Canonical name:** PidTagAttachTag

**Description:** Contains the identifier information for the application that supplied the Attachment object data.

**Property ID:** 0x370A

**Data type:** PtypBinary, 0x0102

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.15

**Consuming references:** [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TAG

## 2.601 PidTagAttachTransportName

**Canonical name:** PidTagAttachTransportName

**Description:** Contains the name of an attachment file, modified so that it can be correlated with TNEF messages.

**Property ID:** 0x370C

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.19

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTACH\_TRANSPORT\_NAME, PR\_ATTACH\_TRANSPORT\_NAME\_A, PR\_ATTACH\_TRANSPORT\_NAME\_W

## 2.602 PidTagAttributeHidden

**Canonical name:** PidTagAttributeHidden

**Description:** Specifies the hide or show status of a folder.

**Property ID:** 0x10F4

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.1

**Consuming references:** [\[MS-OXOSFLD\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_ATTR\_HIDDEN, ptagAttrHidden, DAV:ishidden

## 2.603 PidTagAttributeReadOnly

**Canonical name:** PidTagAttributeReadOnly

**Description:** Indicates whether an item can be modified or deleted.

**Property ID:** 0x10F6

**Data type:** PtypBoolean, 0x000B

**Area:** Access Control Properties

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ATTR\_READONLY, ptagAttrReadOnly, DAV:isreadonly

## 2.604 PidTagAutoForwardComment

**Canonical name:** PidTagAutoForwardComment

**Description:** Contains text included in an automatically-generated message.

**Property ID:** 0x0004

**Data type:** PtypString, 0x001F

**Area:** General Report Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.21

**Alternate names:** PR\_AUTO\_FORWARD\_COMMENT, PR\_AUTO\_FORWARD\_COMMENT\_A, PR\_AUTO\_FORWARD\_COMMENT\_W

## 2.605 PidTagAutoForwarded

**Canonical name:** PidTagAutoForwarded

**Description:** Indicates that a Message object has been automatically generated or automatically forwarded.

**Property ID:** 0x0005

**Data type:** PtypBoolean, 0x000B

**Area:** General Report Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.20

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_AUTO\_FORWARDED, ptagAutoForwarded

## 2.606 PidTagAutoResponseSuppress

**Canonical name:** PidTagAutoResponseSuppress

**Description:** Specifies whether a client or server application should forego sending automated replies in response to this message.

**Property ID:** 0x3FDF

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.77

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_AUTO\_RESPONSE\_SUPPRESS, ptagAutoResponseSuppress

## 2.607 PidTagBirthday

**Canonical name:** PidTagBirthday

**Description:** Contains the date of the mail user's birthday at midnight.

**Property ID:** 0x3A42

**Data type:** PtypTime, 0x0040

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BIRTHDAY, urn:schemas:contacts:bday

## 2.608 PidTagBlockStatus

**Canonical name:** PidTagBlockStatus

**Description:** Indicates the user's preference for viewing external content (such as links to images on an **HTTP** server) in the message body.

**Property ID:** 0x1096

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.1

**Alternate names:** PR\_BLOCK\_STATUS, ptagBlockStatus

## 2.609 PidTagBody

**Canonical name:** PidTagBody

**Description:** Contains message body text in **plain text** format.

**Property ID:** 0x1000

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BODY, PR\_BODY\_A, ptagBody, PR\_BODY\_W, urn:schemas:httpmail:textdescription

## 2.610 PidTagBodyContentId

**Canonical name:** PidTagBodyContentId

**Description:** Contains a GUID that corresponds to the current message body.

**Property ID:** 0x1015

**Data type:** PtypString, 0x001F

**Area:** Exchange

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.7

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_ID, PR\_BODY\_CONTENT\_ID\_A, PR\_BODY\_CONTENT\_ID\_W

## 2.611 PidTagBodyContentLocation

**Canonical name:** PidTagBodyContentLocation

**Description:** Contains a globally unique Uniform Resource Identifier (URI) that serves as a label for the current message body.

**Property ID:** 0x1014

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.8

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_BODY\_CONTENT\_LOCATION, PR\_BODY\_CONTENT\_LOCATION\_A, PR\_BODY\_CONTENT\_LOCATION\_W

## 2.612 PidTagBodyHtml

**Canonical name:** PidTagBodyHtml

**Description:** Contains the HTML body of the Message object.

**Property ID:** 0x1013

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_BODY\_HTML, PR\_BODY\_HTML\_A, ptagBodyHtml, PR\_BODY\_HTML\_W

## 2.613 PidTagBusiness2TelephoneNumber

**Canonical name:** PidTagBusiness2TelephoneNumber

**Description:** Contains a secondary telephone number at the mail user's place of business.

**Property ID:** 0x3A1B

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.23

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** "PR\_BUSINESS2\_TELEPHONE\_NUMBER, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS2\_TELEPHONE\_NUMBER\_W, PR\_OFFICE2\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephonenumber2



## 2.614 PidTagBusiness2TelephoneNumbers

**Canonical name:** PidTagBusiness2TelephoneNumbers

**Description:** Contains secondary telephone numbers at the mail user's place of business.

**Property ID:** 0x3A1B

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.24

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_BUSINESS2\_TELEPHONE\_NUMBER\_A\_MV

## 2.615 PidTagBusinessFaxNumber

**Canonical name:** PidTagBusinessFaxNumber

**Description:** Contains the telephone number of the mail user's business fax machine.

**Property ID:** 0x3A24

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_FAX\_NUMBER, PR\_BUSINESS\_FAX\_NUMBER\_A, PR\_BUSINESS\_FAX\_NUMBER\_W, urn:schemas:contacts:facsimiletelephonenumber

## 2.616 PidTagBusinessHomePage

**Canonical name:** PidTagBusinessHomePage

**Description:** Contains the URL of the mail user's business home page.

**Property ID:** 0x3A51

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.14

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_HOME\_PAGE, PR\_BUSINESS\_HOME\_PAGE\_A, PR\_BUSINESS\_HOME\_PAGE\_W, urn:schemas:contacts:businesshomepageurn:schemas:contacts:businesshomepage

## 2.617 PidTagBusinessTelephoneNumber

**Canonical name:** PidTagBusinessTelephoneNumber

**Description:** Contains the primary telephone number of the mail user's place of business.

**Property ID:** 0x3A08

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.21

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_BUSINESS\_TELEPHONE\_NUMBER, PR\_BUSINESS\_TELEPHONE\_NUMBER\_A, PR\_BUSINESS\_TELEPHONE\_NUMBER\_W, PR\_OFFICE\_TELEPHONE\_NUMBER, urn:schemas:contacts:telephoneNumber

## 2.618 PidTagCallbackTelephoneNumber

**Canonical name:** PidTagCallbackTelephoneNumber

**Description:** Contains a telephone number to reach the mail user.

**Property ID:** 0x3A02

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CALLBACK\_TELEPHONE\_NUMBER, PR\_CALLBACK\_TELEPHONE\_NUMBER\_A, PR\_CALLBACK\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:callbackphone

## 2.619 PidTagCallId

**Canonical name:** PidTagCallId

**Description:** Contains a unique identifier associated with the phone call.

**Property ID:** 0x6806

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.11

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaCallID

## 2.620 PidTagCarTelephoneNumber

**Canonical name:** PidTagCarTelephoneNumber

**Description:** Contains the mail user's car telephone number.

**Property ID:** 0x3A1E

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CAR\_TELEPHONE\_NUMBER, PR\_CAR\_TELEPHONE\_NUMBER\_A, PR\_CAR\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:othermobile

## 2.621 PidTagCdoRecurrenceid

**Canonical name:** PidTagCdoRecurrenceid

**Description:** Identifies a specific instance of a recurring appointment.

**Property ID:** 0x10C5

**Data type:** PtypTime, 0x0040

**Area:** Exchange

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.38

**Alternate names:** PR\_CDO\_RECURRENCEID, urn:schemas:calendar:recurrenceid

## 2.622 PidTagChangeKey

**Canonical name:** PidTagChangeKey

**Description:** Contains a structure that identifies the last change to the object.

**Property ID:** 0x65E2

**Data type:** PtypBinary, 0x0102

**Area:** History Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#)

**Alternate names:** PR\_CHANGE\_KEY

## 2.623 PidTagChangeNumber

**Canonical name:** PidTagChangeNumber

**Description:** Contains a structure that identifies the last change to the message or folder that is currently being synchronized.

**Property ID:** 0x67A4

**Data type:** PtypInteger64, 0x0014

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagCn

## 2.624 PidTagChildrensNames

**Canonical name:** PidTagChildrensNames

**Description:** Specifies the names of the children of the contact.

**Property ID:** 0x3A58

**Data type:** PtypMultipleString, 0x101F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.17

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CHILDRENS\_NAMES, PR\_CHILDRENS\_NAMES\_A, PR\_CHILDRENS\_NAMES\_W, urn:schemas:contacts:childrensnames

## 2.625 PidTagClientActions

**Canonical name:** PidTagClientActions

**Description:** Specifies the actions the client is required to take on the message.

**Property ID:** 0x6645

**Data type:** PtypBinary, 0x0102

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.6

**Alternate names:** PR\_CLIENT\_ACTIONS, ptagClientActions

## 2.626 PidTagClientSubmitTime

**Canonical name:** PidTagClientSubmitTime

**Description:** Contains the current time, in UTC, when the email message is submitted.

**Property ID:** 0x0039

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CLIENT\_SUBMIT\_TIME, urn:schemas:httpmail:date, http://schemas.microsoft.com/exchange/date-iso

## 2.627 PidTagCodePageId

**Canonical name:** PidTagCodePageId

**Description:** Contains the identifier for the client code page used for **Unicode** to **double-byte character set (DBCS)** string conversion.

**Property ID:** 0x66C3

**Data type:** **PtypInteger32**, 0x0003

**Area:** Exchange Profile Configuration

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.14

**Alternate names:** PR\_CODE\_PAGE\_ID, ptagCodePageId

## 2.628 PidTagComment

**Canonical name:** PidTagComment

**Description:** Contains a comment about the purpose or content of the Address Book object.

**Property ID:** 0x3004

**Data type:** **PtypString**, 0x001F

**Area:** Common

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.2

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_COMMENT, PR\_COMMENT\_A, ptagComment, PR\_COMMENT\_W, DAV:comment, <http://schemas.microsoft.com/exchange/summary-utf8>

## 2.629 PidTagCompanyMainTelephoneNumber

**Canonical name:** PidTagCompanyMainTelephoneNumber

**Description:** Contains the main telephone number of the mail user's company.

**Property ID:** 0x3A57

**Data type:** **PtypString**, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.14

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COMPANY\_MAIN\_PHONE\_NUMBER, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_A, PR\_COMPANY\_MAIN\_PHONE\_NUMBER\_W, <urn:schemas:contacts:organizationmainphone>

## 2.630 PidTagCompanyName

**Canonical name:** PidTagCompanyName

**Description:** Contains the mail user's company name.

**Property ID:** 0x3A16

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.7

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COMPANY\_NAME, PR\_COMPANY\_NAME\_A, PR\_COMPANY\_NAME\_W, urn:schemas:contacts:o

### 2.631 PidTagComputerNetworkName

**Canonical name:** PidTagComputerNetworkName

**Description:** Contains the name of the mail user's computer network.

**Property ID:** 0x3A49

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.16

**Alternate names:** PR\_COMPUTER\_NETWORK\_NAME, PR\_COMPUTER\_NETWORK\_NAME\_A, PR\_COMPUTER\_NETWORK\_NAME\_W, urn:schemas:contacts:computernetworkname

### 2.632 PidTagConflictEntryId

**Canonical name:** PidTagConflictEntryId

**Description:** Contains the EntryID of the conflict resolve message.

**Property ID:** 0x3FF0

**Data type:** PtypBinary, 0x0102

**Area:** ICS

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.2

**Alternate names:** PR\_CONFLICT\_ENTRYID, ptagConflictEntryId

### 2.633 PidTagContainerClass

**Canonical name:** PidTagContainerClass

**Description:** Contains a string value that describes the type of Message object that a folder contains.

**Property ID:** 0x3613

**Data type:** PtypString, 0x001F

**Area:** Container Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.3

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_CONTAINER\_CLASS, PR\_CONTAINER\_CLASS\_A, ptagContainerClass, PR\_CONTAINER\_CLASS\_W, <http://schemas.microsoft.com/exchange/outlookfolderclass><http://schemas.microsoft.com/exchange/outlookfolderclass>

### 2.634 PidTagContainerContents

**Canonical name:** PidTagContainerContents

**Description:** Always empty. An NSPI server defines this value for distribution lists and it is not present for other objects.

**Property ID:** 0x360F

**Data type:** PtypEmbeddedTable, 0x000D

**Area:** Container Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.6.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_CONTAINER\_CONTENTS, ptagContainerContents

### 2.635 PidTagContainerFlags

**Canonical name:** PidTagContainerFlags

**Description:** Contains a bitmask of flags that describe capabilities of an address book container.

**Property ID:** 0x3600

**Data type:** PtypInteger32, 0x0003

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.2.1

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_CONTAINER\_FLAGS

### 2.636 PidTagContainerHierarchy

**Canonical name:** PidTagContainerHierarchy

**Description:** Identifies all of the subfolders of the current folder.

**Property ID:** 0x360E

**Data type:** PtypObject, 0x000D

**Area:** Container Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.4

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_CONTAINER\_HIERARCHY, ptagContainerHierarchy

## 2.637 PidTagContentCount

**Canonical name:** PidTagContentCount

**Description:** Specifies the number of rows under the header row.

**Property ID:** 0x3602

**Data type:** PtypInteger32, 0x0003

**Area:** Folder Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.1

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_CONTENT\_COUNT, ptagContentCount, DAV:visiblecount

## 2.638 PidTagContentFilterSpamConfidenceLevel

**Canonical name:** PidTagContentFilterSpamConfidenceLevel

**Description:** Indicates a confidence level that the message is spam.

**Property ID:** 0x4076

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CONTENT\_FILTER\_SCL, ptagContentFilterSCL

## 2.639 PidTagContentUnreadCount

**Canonical name:** PidTagContentUnreadCount

**Description:** Specifies the number of rows under the header row that have the **PidTagRead** property (section [2.869](#)) set to FALSE.

**Property ID:** 0x3603

**Data type:** PtypInteger32, 0x0003

**Area:** Folder Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.2

**Consuming references:** [\[MS-OXCTABL\]](#)

**Alternate names:** PR\_CONTENT\_UNREAD, ptagContentUnread, urn:schemas:httpmail:unreadcount

## 2.640 PidTagConversationId

**Canonical name:** PidTagConversationId

**Description:** Contains a computed value derived from other conversation-related properties.



**Property ID:** 0x3013

**Data type:** PtypBinary, 0x0102

**Area:** Conversations

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_CONVERSATION\_ID

## 2.641 PidTagConversationIndex

**Canonical name:** PidTagConversationIndex

**Description:** Indicates the relative position of this message within a conversation thread.

**Property ID:** 0x0071

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [MS-OXOMSG], [\[MS-OXOPOST\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_CONVERSATION\_INDEX, ptagConversationIndex

## 2.642 PidTagConversationIndexTracking

**Canonical name:** PidTagConversationIndexTracking

**Description:** Indicates whether the GUID portion of the **PidTagConversationIndex** property (section [2.641](#)) is to be used to compute the **PidTagConversationId** property (section [2.640](#)).

**Property ID:** 0x3016

**Data type:** PtypBoolean, 0x000B

**Area:** Conversations

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.4

**Alternate names:** PR\_CONVERSATION\_INDEX\_TRACKING

## 2.643 PidTagConversationTopic

**Canonical name:** PidTagConversationTopic

**Description:** Contains an unchanging copy of the original subject.

**Property ID:** 0x0070

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_CONVERSATION\_TOPIC, PR\_CONVERSATION\_TOPIC\_A, ptagConversationTopic, PR\_CONVERSATION\_TOPIC\_W, urn:schemas:httpmail:thread-topic

## 2.644 PidTagCountry

**Canonical name:** PidTagCountry

**Description:** Contains the name of the mail user's country/region.

**Property ID:** 0x3A26

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.19

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_COUNTRY, PR\_COUNTRY\_A, PR\_COUNTRY\_W, PR\_BUSINESS\_ADDRESS\_COUNTRY, PR\_BUSINESS\_ADDRESS\_COUNTRY\_A, PR\_BUSINESS\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:mailingcountry

## 2.645 PidTagCreationTime

**Canonical name:** PidTagCreationTime

**Description:** Contains the time, in UTC, that the object was created.

**Property ID:** 0x3007

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.3

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATION\_TIME, ptagCreationTime, DAV:creationdate

## 2.646 PidTagCreatorEntryId

**Canonical name:** PidTagCreatorEntryId

**Description:** Specifies the original author of the message according to their Address Book EntryID.

**Property ID:** 0x3FF9

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.31

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_ENTRYID, ptagCreatorEntryId

## 2.647 PidTagCreatorName

**Canonical name:** PidTagCreatorName

**Description:** Contains the name of the creator of a Message object.

**Property ID:** 0x3FF8

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.51

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_CREATOR\_NAME, PR\_CREATOR\_NAME\_A, ptagCreatorName, PR\_CREATOR\_NAME\_W

## 2.648 PidTagCustomerId

**Canonical name:** PidTagCustomerId

**Description:** Contains the mail user's customer identification number.

**Property ID:** 0x3A4A

**Data type:** PtypString, 0x001F

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.8

**Alternate names:** PR\_CUSTOMER\_ID, PR\_CUSTOMER\_ID\_A, PR\_CUSTOMER\_ID\_W, urn:schemas:contacts:customerid

## 2.649 PidTagDamBackPatched

**Canonical name:** PidTagDamBackPatched

**Description:** Indicates whether the **Deferred Action Message (DAM)** was updated by the server.

**Property ID:** 0x6647

**Data type:** PtypBoolean, 0x000B

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.2

**Alternate names:** PR\_DAM\_BACK\_PATCHED, ptagDamBackPatched

## 2.650 PidTagDamOriginalEntryId

**Canonical name:** PidTagDamOriginalEntryId

**Description:** Contains the EntryID of the delivered message that the client has to process.

**Property ID:** 0x6646

**Data type:** PtypBinary, 0x0102

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.3

**Alternate names:** PR\_DAM\_ORIGINAL\_ENTRYID

## 2.651 PidTagDefaultPostMessageClass

**Canonical name:** PidTagDefaultPostMessageClass

**Description:** Contains the message class of the object.

**Property ID:** 0x36E5

**Data type:** PtypString, 0x001F

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.11.2

**Alternate names:** PR\_DEF\_POST\_MSGCLASS

## 2.652 PidTagDeferredActionMessageOriginalEntryId

**Canonical name:** PidTagDeferredActionMessageOriginalEntryId

**Description:** Contains the server EntryID for the DAM.

**Property ID:** 0x6741

**Data type:** PtypServerId, 0x00FB

**Area:** Server-side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.8

**Alternate names:** PR\_DAM\_ORIG\_MSG\_SVREID, ptagDamOrgMsgSvrEID

## 2.653 PidTagDeferredDeliveryTime

**Canonical name:** PidTagDeferredDeliveryTime

**Description:** Contains the date and time, in UTC, at which the sender prefers that the message be delivered.

**Property ID:** 0x000F

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.6

**Alternate names:** PR\_DEFERRED\_DELIVERY\_TIME, ptagDeferredDeliveryTime, <http://schemas.microsoft.com/exchange/deferred-delivery-iso>

## 2.654 PidTagDeferredSendNumber

**Canonical name:** PidTagDeferredSendNumber

**Description:** Contains a number used in the calculation of how long to defer sending a message.

**Property ID:** 0x3FEB

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.2

**Alternate names:** PR\_DEFERRED\_SEND\_NUMBER

## 2.655 PidTagDeferredSendTime

**Canonical name:** PidTagDeferredSendTime

**Description:** Contains the amount of time after which a client would like to defer sending the message.

**Property ID:** 0x3FEF

**Data type:** PtypTime, 0x0040

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.4

**Alternate names:** PR\_DEFERRED\_SEND\_TIME, ptagDeferredSendTime

## 2.656 PidTagDeferredSendUnits

**Canonical name:** PidTagDeferredSendUnits

**Description:** Specifies the unit of time used as a multiplier with the **PidTagDeferredSendNumber** property (section [2.654](#)) value.

**Property ID:** 0x3FEC

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.3

**Alternate names:** PR\_DEFERRED\_SEND\_UNITS

## 2.657 PidTagDelegatedByRule

**Canonical name:** PidTagDelegatedByRule

**Description:** Specifies whether the message was forwarded due to the triggering of a delegate forward rule.

**Property ID:** 0x3FE3

**Data type:** PtypBoolean, 0x000B

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.84

**Consuming references:** [\[MS-OXODLGT\]](#), [\[MS-OXORULE\]](#)

**Alternate names:** PR\_DELEGATED\_BY\_RULE

## 2.658 PidTagDelegateFlags

**Canonical name:** PidTagDelegateFlags

**Description:** Indicates whether delegates can view Message objects that are marked as private.

**Property ID:** 0x686B

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.6

**Alternate names:** PR\_DELEGATE\_FLAGS, ptagDelegateFlags

## 2.659 PidTagDeleteAfterSubmit

**Canonical name:** PidTagDeleteAfterSubmit

**Description:** Indicates that the original message is to be deleted after it is sent.

**Property ID:** 0x0E01

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.8

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXODOC\]](#)

**Alternate names:** PR\_DELETE\_AFTER\_SUBMIT, ptagDeleteAfterSubmit

## 2.660 PidTagDeletedCountTotal

**Canonical name:** PidTagDeletedCountTotal

**Description:** Contains the total count of messages that have been deleted from a folder, excluding messages deleted within subfolders.

**Property ID:** 0x670B

**Data type:** PtypInteger32, 0x0003

**Area:** Server

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.15

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_DELETED\_COUNT\_TOTAL, ptagDeleteCountTotal

## 2.661 PidTagDeletedOn

**Canonical name:** PidTagDeletedOn

**Description:** Specifies the time, in UTC, when the item or folder was **soft deleted**.

**Property ID:** 0x668F

**Data type:** PtypTime, 0x0040

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.3

**Alternate names:** PR\_DELETED\_ON, ptagDeletedOn, urn:schemas:httpmail:deletedon

## 2.662 PidTagDeliverTime

**Canonical name:** PidTagDeliverTime

**Description:** Contains the delivery time for a delivery status notification, as specified [\[RFC3464\]](#), or a message disposition notification, as specified in [\[RFC3798\]](#).

**Property ID:** 0x0010

**Data type:** PtypTime, 0x0040

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.29

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_DELIVER\_TIME, ptagDeliverTime

## 2.663 PidTagDepartmentName

**Canonical name:** PidTagDepartmentName

**Description:** Contains a name for the department in which the mail user works.

**Property ID:** 0x3A18

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.6

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#) [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_DEPARTMENT\_NAME, PR\_DEPARTMENT\_NAME\_A, PR\_DEPARTMENT\_NAME\_W, urn:schemas:contacts:department

## 2.664 PidTagDepth

**Canonical name:** PidTagDepth

**Description:** Specifies the number of nested categories in which a given row is contained.

**Property ID:** 0x3005

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_DEPTH, ptagDepth

## 2.665 PidTagDisplayBcc

**Canonical name:** PidTagDisplayBcc

**Description:** Contains a list of **blind carbon copy (Bcc) recipient** display names.

**Property ID:** 0x0E02

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_BCC, PR\_DISPLAY\_BCC\_A, ptagDisplayBcc, PR\_DISPLAY\_BCC\_W, urn:schemas:httpmail:displaybcc

## 2.666 PidTagDisplayCc

**Canonical name:** PidTagDisplayCc

**Description:** Contains a list of **carbon copy (Cc) recipient** display names.

**Property ID:** 0x0E03

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_CC, PR\_DISPLAY\_CC\_A, ptagDisplayCc, PR\_DISPLAY\_CC\_W, urn:schemas:httpmail:displaycc

## 2.667 PidTagDisplayName

**Canonical name:** PidTagDisplayName

**Description:** Contains the display name of the folder.

**Property ID:** 0x3001

**Data type:** PtypString, 0x001F

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.5



**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDVSEC\]](#)

**Alternate names:** PR\_DISPLAY\_NAME, PR\_DISPLAY\_NAME\_A, ptagDisplayName, PR\_DISPLAY\_NAME\_W, urn:schemas:contacts:cn

## 2.668 PidTagDisplayNamePrefix

**Canonical name:** PidTagDisplayNamePrefix

**Description:** Contains the mail user's honorific title.

**Property ID:** 0x3A45

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_DISPLAY\_NAME\_PREFIX, PR\_DISPLAY\_NAME\_PREFIX\_A, PR\_DISPLAY\_NAME\_PREFIX\_W, urn:schemas:contacts:personaltitle

## 2.669 PidTagDisplayTo

**Canonical name:** PidTagDisplayTo

**Description:** Contains a list of the **primary recipient** display names, separated by semicolons, when an email message has primary recipients .

**Property ID:** 0x0E04

**Data type:** PtypString, 0x001F

**Area:** Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_DISPLAY\_TO, PR\_DISPLAY\_TO\_A, ptagDisplayTo, PR\_DISPLAY\_TO\_W

## 2.670 PidTagDisplayType

**Canonical name:** PidTagDisplayType

**Description:** Contains an integer value that indicates how to display an Address Book object in a table or as an addressee on a message.

**Property ID:** 0x3900

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXLDAP\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE, ptagDisplayType

## 2.671 PidTagDisplayTypeEx

**Canonical name:** PidTagDisplayTypeEx

**Description:** Contains an integer value that indicates how to display an Address Book object in a table or as a recipient on a message.

**Property ID:** 0x3905

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_DISPLAY\_TYPE\_EX

## 2.672 PidTagEmailAddress

**Canonical name:** PidTagEmailAddress

**Description:** Contains the email address of a Message object.

**Property ID:** 0x3003

**Data type:** PtypString, 0x001F

**Area:** MapiCommon

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.14

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXPSVAL\]](#)

**Alternate names:** PR\_EMAIL\_ADDRESS, PR\_EMAIL\_ADDRESS\_A, PR\_EMAIL\_ADDRESS\_W

## 2.673 PidTagEndDate

**Canonical name:** PidTagEndDate

**Description:** Contains the value of the **PidLidAppointmentEndWhole** property (section [2.14](#)).

**Property ID:** 0x0061

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.31

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_END\_DATE, [http://schemas.microsoft.com/mapi/end\\_date](http://schemas.microsoft.com/mapi/end_date)

## 2.674 PidTagEntryId

**Canonical name:** PidTagEntryId

**Description:** Contains the information to identify many different types of **messaging objects**.

**Property ID:** 0x0FFF

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.4

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFCICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOABKT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPFOAB\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXWAVLS\]](#)

**Alternate names:** PR\_ENTRYID, ptagEntryId

## 2.675 PidTagExceptionEndTime

**Canonical name:** PidTagExceptionEndTime

**Description:** Contains the end date and time of the exception in the local time zone of the computer when the exception is created.

**Property ID:** 0x7FFC

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.5

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_ENDTIME, ptagExceptionEndTime

## 2.676 PidTagExceptionReplaceTime

**Canonical name:** PidTagExceptionReplaceTime

**Description:** Indicates the original date and time, in UTC, at which the instance in the recurrence pattern would have occurred if it were not an exception.

**Property ID:** 0x7FF9

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.6

**Alternate names:** PR\_EXCEPTION\_REPLACETIME

## 2.677 PidTagExceptionStartTime

**Canonical name:** PidTagExceptionStartTime

**Description:** Contains the start date and time of the exception in the local time zone of the computer when the exception is created.

**Property ID:** 0x7FFB

**Data type:** PtypTime, 0x0040

**Area:** MessageClassDefinedNonTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.10.1.4

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_EXCEPTION\_STARTTIME, ptagExceptionStartTime

## 2.678 PidTagExchangeNTSecurityDescriptor

**Canonical name:** PidTagExchangeNTSecurityDescriptor

**Description:** Contains the calculated security descriptor for the item.

**Property ID:** 0x0E84

**Data type:** PtypBinary, 0x0102

**Area:** Calendar Document

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.8

**Alternate names:** <http://schemas.microsoft.com/exchange/ntsecuritydescriptor>,  
<http://schemas.microsoft.com/exchange/ntsecuritydescriptor>

## 2.679 PidTagExpiryNumber

**Canonical name:** PidTagExpiryNumber

**Description:** Contains an integer value that is used along with the **PidTagExpiryUnits** property (section [2.681](#)) to define the expiry send time.

**Property ID:** 0x3FED

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.5

**Alternate names:** PR\_EXPIRY\_NUMBER

## 2.680 PidTagExpiryTime

**Canonical name:** PidTagExpiryTime

**Description:** Contains the time, in UTC, after which a client wants to receive an expiry event if the message arrives late.

**Property ID:** 0x0015

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.7

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_EXPIRY\_TIME, ptagExpiryTime, urn:schemas:httpmail:expiry-date, <http://schemas.microsoft.com/exchange/expiry-date-iso>

## 2.681 PidTagExpiryUnits

**Canonical name:** PidTagExpiryUnits

**Description:** Contains the unit of time that the value of the **PidTagExpiryNumber** property (section [2.679](#)) multiplies.

**Property ID:** 0x3FEE

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.6

**Alternate names:** PR\_EXPIRY\_UNITS

## 2.682 PidTagExtendedFolderFlags

**Canonical name:** PidTagExtendedFolderFlags

**Description:** Contains encoded sub-properties for a folder.

**Property ID:** 0x36DA

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_EXTENDED\_FOLDER\_FLAGS, ptagExtendedFolderFlags

## 2.683 PidTagExtendedRuleMessageActions

**Canonical name:** PidTagExtendedRuleMessageActions

**Description:** Contains action information about named properties used in the rule.

**Property ID:** 0x0E99

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.9

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_ACTIONS

## 2.684 PidTagExtendedRuleMessageCondition

**Canonical name:** PidTagExtendedRuleMessageCondition

**Description:** Contains condition information about named properties used in the rule.

**Property ID:** 0x0E9A

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.10

**Consuming references:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_MSG\_CONDITION

## 2.685 PidTagExtendedRuleSizeLimit

**Canonical name:** PidTagExtendedRuleSizeLimit

**Description:** Contains the maximum size, in bytes, that the user is allowed to accumulate for a single extended rule.

**Property ID:** 0x0E9B

**Data type:** PtypInteger32, 0x0003

**Area:** Rules

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.1

**Consuming Reference:** [\[MS-OXORULE\]](#)

**Alternate names:** PR\_EXTENDED\_RULE\_SIZE\_LIMIT

## 2.686 PidTagFaxNumberOfPages

**Canonical name:** PidTagFaxNumberOfPages

**Description:** Contains the number of pages in a Fax object.

**Property ID:** 0x6804

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.7

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaFaxNumberOfPages

## 2.687 PidTagFlagCompleteTime

**Canonical name:** PidTagFlagCompleteTime

**Description:** Specifies the date and time, in UTC, that the Message object was flagged as complete.

**Property ID:** 0x1091

**Data type:** PtypTime, 0x0040

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_FLAG\_COMPLETE\_TIME, ptagFlagCompleteTime, urn:schemas:httpmail:flagcompleted

## 2.688 PidTagFlagStatus

**Canonical name:** PidTagFlagStatus

**Description:** Specifies the flag state of the Message object.

**Property ID:** 0x1090

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FLAG\_STATUS, ptagFlagStatus

## 2.689 PidTagFlatUrlName

**Canonical name:** PidTagFlatUrlName

**Description:** Contains a unique identifier for an item across the message store.

**Property ID:** 0x670E

**Data type:** PtypString, 0x001F

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.8.9

**Alternate names:** PR\_FLAT\_URL\_NAME, PR\_FLAT\_URL\_NAME\_A, PR\_FLAT\_URL\_NAME\_W, ptagFlatURLName, http://schemas.microsoft.com/exchange/permanenturl

## 2.690 PidTagFolderAssociatedContents

**Canonical name:** PidTagFolderAssociatedContents

**Description:** Identifies all FAI messages in the current folder.

**Property ID:** 0x3610

**Data type:** PtypObject, 0x000D

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.6

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_FOLDER\_ASSOCIATED\_CONTENTS

## 2.691 PidTagFolderId

**Canonical name:** PidTagFolderId

**Description:** Contains the Folder ID (FID) ([\[MS-OXCDATA\]](#) section 2.2.1.1) of the folder.

**Property ID:** 0x6748

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** ptagFID

## 2.692 PidTagFolderFlags

**Canonical name:** PidTagFolderFlags

**Description:** Contains a computed value to specify the type or state of a folder.

**Property ID:** 0x66A8

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.5

**Alternate names:** PR\_FOLDER\_FLAGS

## 2.693 PidTagFolderType

**Canonical name:** PidTagFolderType

**Description:** Specifies the type of a folder that includes the **Root folder**, Generic folder, and Search folder.

**Property ID:** 0x3601

**Data type:** PtypInteger32, 0x0003

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.2.7



**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_FOLDER\_TYPE, ptagFolderType

## 2.694 PidTagFollowupIcon

**Canonical name:** PidTagFollowupIcon

**Description:** Specifies the flag color of the Message object.

**Property ID:** 0x1095

**Data type:** **PtypInteger32**, 0x0003

**Area:** RenMessageFolder

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_FOLLOWUP\_ICON, ptagFollowupIcon

## 2.695 PidTagFreeBusyCountMonths

**Canonical name:** PidTagFreeBusyCountMonths

**Description:** Contains an integer value used to calculate the start and end dates of the range of free/busy data to be published to the public folders.

**Property ID:** 0x6869

**Data type:** **PtypInteger32**, 0x0003

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_FREEBUSY\_COUNT\_MONTHS

## 2.696 PidTagFreeBusyEntryIds

**Canonical name:** PidTagFreeBusyEntryIds

**Description:** Contains EntryIDs of the Delegate Information object, the free/busy message of the logged on user, and the folder with the **PidTagDisplayName** property (section [2.667](#)) value of "Freebusy Data".

**Property ID:** 0x36E4

**Data type:** **PtypMultipleBinary**, 0x1102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.6

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_FREEBUSY\_ENTRYIDS, ptagFreeBusyEntryIds

## 2.697 PidTagFreeBusyMessageEmailAddress

**Canonical name:** PidTagFreeBusyMessageEmailAddress

**Description:** Specifies the email address of the user or resource to whom this free/busy message applies.

**Property ID:** 0x6849

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.12

**Alternate names:** PR\_FREEBUSY\_EMA

## 2.698 PidTagFreeBusyPublishEnd

**Canonical name:** PidTagFreeBusyPublishEnd

**Description:** Specifies the end time, in UTC, of the publishing range.

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.10

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_END

## 2.699 PidTagFreeBusyPublishStart

**Canonical name:** PidTagFreeBusyPublishStart

**Description:** Specifies the start time, in UTC, of the publishing range.

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.9

**Alternate names:** PR\_FREEBUSY\_PUBLISH\_START

## 2.700 PidTagFreeBusyRangeTimestamp

**Canonical name:** PidTagFreeBusyRangeTimestamp

**Description:** Specifies the time, in UTC, that the data was published.

**Property ID:** 0x6868

**Data type:** PtypTime, 0x0040

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.11

**Alternate names:** PR\_FREEBUSY\_RANGE\_TIMESTAMP

## 2.701 PidTagFtpSite

**Canonical name:** PidTagFtpSite

**Description:** Contains the **File Transfer Protocol (FTP)** site address of the mail user.

**Property ID:** 0x3A4C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.15

**Alternate names:** PR\_FTP\_SITE, PR\_FTP\_SITE\_A, PR\_FTP\_SITE\_W, urn:schemas:contacts:ftpsite

## 2.702 PidTagGatewayNeedsToRefresh

**Canonical name:** PidTagGatewayNeedsToRefresh

**Description:** This property is deprecated and SHOULD NOT be used.

**Property ID:** 0x6846

**Data type:** PtypBoolean, 0x000B

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.1

**Alternate names:** PR\_GATEWAY\_NEEDS\_TO\_REFRESH

## 2.703 PidTagGender

**Canonical name:** PidTagGender

**Description:** Contains a value that represents the mail user's gender.

**Property ID:** 0x3A4D

**Data type:** PtypInteger16, 0x0002

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.20

**Alternate names:** PR\_GENDER, urn:schemas:contacts:gender

## 2.704 PidTagGeneration

**Canonical name:** PidTagGeneration

**Description:** Contains a generational abbreviation that follows the full name of the mail user.

**Property ID:** 0x3A05

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_GENERATION, PR\_GENERATION\_A, PR\_GENERATION\_W, urn:schemas:contacts:namesuffix

## 2.705 PidTagGivenName

**Canonical name:** PidTagGivenName

**Description:** Contains the mail user's given name.

**Property ID:** 0x3A06

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.2

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_GIVEN\_NAME, PR\_GIVEN\_NAME\_A, PR\_GIVEN\_NAME\_W, urn:schemas:contacts:givenName

## 2.706 PidTagGovernmentIdNumber

**Canonical name:** PidTagGovernmentIdNumber

**Description:** Contains a government identifier for the mail user.

**Property ID:** 0x3A07

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.9

**Alternate names:** PR\_GOVERNMENT\_ID\_NUMBER, PR\_GOVERNMENT\_ID\_NUMBER\_A, PR\_GOVERNMENT\_ID\_NUMBER\_W, urn:schemas:contacts:governmentid

## 2.707 PidTagHasAttachments

**Canonical name:** PidTagHasAttachments

**Description:** Indicates whether the Message object contains at least one attachment.

**Property ID:** 0x0E1B

**Data type:** PtypBoolean, 0x000B

**Area:** Message Attachment Properties Property set

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_HASATTACH, ptagHasAttach, urn:schemas:httpmail:hasattachment

## 2.708 PidTagHasDeferredActionMessages

**Canonical name:** PidTagHasDeferredActionMessages

**Description:** Indicates whether a Message object has a deferred action message associated with it.

**Property ID:** 0x3FEA

**Data type:** PtypBoolean, 0x000B

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.1

**Alternate names:** PR\_HAS\_DAMS, ptagHasDAMs

## 2.709 PidTagHasNamedProperties

**Canonical name:** PidTagHasNamedProperties

**Description:** Indicates whether the Message object has a named property.

**Property ID:** 0x664A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.39

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_HAS\_NAMED\_PROPERTIES, ptagHasNamedProperties

## 2.710 PidTagHasRules

**Canonical name:** PidTagHasRules

**Description:** Indicates whether a Folder object has rules.

**Property ID:** 0x663A

**Data type:** PtypBoolean, 0x000B

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.8.1

**Alternate names:** PR\_HAS\_RULES, ptagHasRules

## 2.711 PidTagHierarchyChangeNumber

**Canonical name:** PidTagHierarchyChangeNumber

**Description:** Contains a number that monotonically increases every time a subfolder is added to, or deleted from, this folder.

**Property ID:** 0x663E

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.8

**Alternate names:** PR\_HIERARCHY\_CHANGE\_NUM

## 2.712 PidTagHierRev

**Canonical name:** PidTagHierRev

**Description:** Specifies the time, in UTC, to trigger the client in cached mode to synchronize the folder hierarchy.

**Property ID:** 0x4082

**Data type:** PtypTime, 0x0040

**Area:** TransportEnvelope

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.9

**Alternate names:** PR\_HIER\_REV, ptagHierRev

## 2.713 PidTagHobbies

**Canonical name:** PidTagHobbies

**Description:** Contains the names of the mail user's hobbies.

**Property ID:** 0x3A43

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOBBIES, PR\_HOBBIES\_A, PR\_HOBBIES\_W, urn:schemas:contacts:hobbies

## 2.714 PidTagHome2TelephoneNumber

**Canonical name:** PidTagHome2TelephoneNumber

**Description:** Contains a secondary telephone number at the mail user's home.

**Property ID:** 0x3A2F

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.25

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER, PR\_HOME2\_TELEPHONE\_NUMBER\_A, PR\_HOME2\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homephone2

## 2.715 PidTagHome2TelephoneNumbers

**Canonical name:** PidTagHome2TelephoneNumbers

**Description:** Contains secondary telephone numbers at the mail user's home.

**Property ID:** 0x3A2F

**Data type:** PtypMultipleString, 0x101F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.26

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_HOME2\_TELEPHONE\_NUMBER\_A\_MV

## 2.716 PidTagHomeAddressCity

**Canonical name:** PidTagHomeAddressCity

**Description:** Contains the name of the mail user's home locality, such as the town or city.

**Property ID:** 0x3A59

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_CITY, PR\_HOME\_ADDRESS\_CITY\_A, PR\_HOME\_ADDRESS\_CITY\_W, urn:schemas:contacts:homeCity

## 2.717 PidTagHomeAddressCountry

**Canonical name:** PidTagHomeAddressCountry

**Description:** Contains the name of the mail user's home country/region.

**Property ID:** 0x3A5A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_COUNTRY, PR\_HOME\_ADDRESS\_COUNTRY\_A, PR\_HOME\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:homeCountry

## 2.718 PidTagHomeAddressPostalCode

**Canonical name:** PidTagHomeAddressPostalCode

**Description:** Contains the postal code for the mail user's home postal address.

**Property ID:** 0x3A5B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POSTAL\_CODE, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_A, PR\_HOME\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:homePostalCode

## 2.719 PidTagHomeAddressPostOfficeBox

**Canonical name:** PidTagHomeAddressPostOfficeBox

**Description:** Contains the number or identifier of the mail user's home post office box.

**Property ID:** 0x3A5E

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_HOME\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:homepostofficebox

## 2.720 PidTagHomeAddressStateOrProvince

**Canonical name:** PidTagHomeAddressStateOrProvince

**Description:** Contains the name of the mail user's home state or province.

**Property ID:** 0x3A5C

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_HOME\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:homeState



## 2.721 PidTagHomeAddressStreet

**Canonical name:** PidTagHomeAddressStreet

**Description:** Contains the mail user's home street address.

**Property ID:** 0x3A5D

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.20

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_ADDRESS\_STREET, PR\_HOME\_ADDRESS\_STREET\_A, PR\_HOME\_ADDRESS\_STREET\_W, urn:schemas:contacts:homeStreet

## 2.722 PidTagHomeFaxNumber

**Canonical name:** PidTagHomeFaxNumber

**Description:** Contains the telephone number of the mail user's home fax machine.

**Property ID:** 0x3A25

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.2.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_FAX\_NUMBER, PR\_HOME\_FAX\_NUMBER\_A, PR\_HOME\_FAX\_NUMBER\_W, urn:schemas:contacts:homefax

## 2.723 PidTagHomeTelephoneNumber

**Canonical name:** PidTagHomeTelephoneNumber

**Description:** Contains the primary telephone number of the mail user's home.

**Property ID:** 0x3A09

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.22

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_HOME\_TELEPHONE\_NUMBER, PR\_HOME\_TELEPHONE\_NUMBER\_A, PR\_HOME\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:homePhone

## 2.724 PidTagHtml

**Canonical name:** PidTagHtml

**Description:** Contains message body text in HTML format.

**Property ID:** 0x1013

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.9

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_HTML, ptagHtml

## 2.725 PidTagICalendarEndTime

**Canonical name:** PidTagICalendarEndTime

**Description:** Contains the date and time, in UTC, when an appointment or meeting ends.

**Property ID:** 0x10C4

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.39

**Alternate names:** urn:schemas:calendar:dtend

## 2.726 PidTagICalendarReminderNextTime

**Canonical name:** PidTagICalendarReminderNextTime

**Description:** Contains the date and time, in UTC, for the activation of the next reminder.

**Property ID:** 0x10CA

**Data type:** PtypTime, 0x0040

**Area:** Calendar

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.40

**Alternate names:** urn:schemas:calendar:remindernexttime

## 2.727 PidTagICalendarStartTime

**Canonical name:** PidTagICalendarStartTime

**Description:** Contains the date and time, in UTC, when the appointment or meeting starts.

**Property ID:** 0x10C3

**Data type:** PtypTime, 0x0040

**Area:** Calendar Property set

**Defining reference:** [\[MS-XWDCAL\]](#) section 2.2.2.41

**Alternate names:** urn:schemas:calendar:dtstart

## 2.728 PidTagIconIndex

**Canonical name:** PidTagIconIndex

**Description:** Specifies which icon is to be used by a user interface when displaying a group of Message objects.

**Property ID:** 0x1080

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ICON\_INDEX, ptagIconIndex

## 2.729 PidTagImportance

**Canonical name:** PidTagImportance

**Description:** Indicates the level of importance assigned by the end user to the Message object.

**Property ID:** 0x0017

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_IMPORTANCE, ptagImportance, urn:schemas:httpmail:importance, <http://schemas.microsoft.com/exchange/importance-long>, <http://schemas.microsoft.com/exchange/x-priority-long>

## 2.730 PidTagInConflict

**Canonical name:** PidTagInConflict

**Description:** Specifies whether the attachment represents an alternate replica.

**Property ID:** 0x666C

**Data type:** PtypBoolean, 0x000B

**Area:** Conflict Note

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.3

**Alternate names:** PR\_IN\_CONFLICT, ptagInConflict

## 2.731 PidTagInitialDetailsPane

**Canonical name:** PidTagInitialDetailsPane

**Description:** Indicates which page of a display template to display first.

**Property ID:** 0x3F08

**Data type:** PtypInteger32, 0x0003

**Area:** MAPI Display Tables

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.33

**Consuming Reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_INITIAL\_DETAILS\_PANE

## 2.732 PidTagInitials

**Canonical name:** PidTagInitials

**Description:** Contains the initials for parts of the full name of the mail user.

**Property ID:** 0x3A0A

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.3

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_INITIALS, PR\_INITIALS\_A, PR\_INITIALS\_W, urn:schemas:contacts:initials

## 2.733 PidTagInReplyToId

**Canonical name:** PidTagInReplyToId

**Description:** Contains the value of the original message's **PidTagInternetMessageId** property (section [2.739](#)) value.

**Property ID:** 0x1042

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.13

**Consuming Reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_IN\_REPLY\_TO\_ID, PR\_IN\_REPLY\_TO\_ID\_A, PR\_IN\_REPLY\_TO\_ID\_W

## 2.734 PidTagInstanceKey

**Canonical name:** PidTagInstanceKey

**Description:** Contains an object on an NSPI server.

**Property ID:** 0x0FF6

**Data type:** PtypBinary, 0x0102

**Area:** Table Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOABKT\]](#)

**Alternate names:** PR\_INSTANCE\_KEY, ptagInstanceKey

### 2.735 PidTagInstanceNum

**Canonical name:** PidTagInstanceNum

**Description:** Contains an identifier for a single instance of a row in the table.

**Property ID:** 0x674E

**Data type:** PtypInteger32, 0x0003

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.2

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstanceNum

### 2.736 PidTagInstID

**Canonical name:** PidTagInstID

**Description:** Contains an identifier for all instances of a row in the table.

**Property ID:** 0x674D

**Data type:** PtypInteger64, 0x0014

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** ptagInstID

### 2.737 PidTagInternetCodepage

**Canonical name:** PidTagInternetCodepage

**Description:** Indicates the code page used for the **PidTagBody** property (section [2.609](#)) or the **PidTagBodyHtml** property (section [2.612](#)).

**Property ID:** 0x3FDE

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_CPID, ptagInternetCpid

### 2.738 PidTagInternetMailOverrideFormat

**Canonical name:** PidTagInternetMailOverrideFormat

**Description:** Indicates the encoding method and HTML inclusion for attachments.

**Property ID:** 0x5902

**Data type:** PtypInteger32, 0x0003

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.11

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_INETMAIL\_OVERRIDE\_FORMAT, ptagInetMailOverrideFormat

### 2.739 PidTagInternetMessageId

**Canonical name:** PidTagInternetMessageId

**Description:** Corresponds to the **message-id** field.

**Property ID:** 0x1035

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_INTERNET\_MESSAGE\_ID, PR\_INTERNET\_MESSAGE\_ID\_A, PR\_INTERNET\_MESSAGE\_ID\_W

### 2.740 PidTagInternetReferences

**Canonical name:** PidTagInternetReferences

**Description:** Contains a list of message IDs that specify the messages to which this reply is related.

**Property ID:** 0x1039

**Data type:** PtypString, 0x001F

**Area:** MIME Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.26

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_INTERNET\_REFERENCES, PR\_INTERNET\_REFERENCES\_A, PR\_INTERNET\_REFERENCES\_W

### 2.741 PidTagIpmAppointmentEntryId

**Canonical name:** PidTagIpmAppointmentEntryId

**Description:** Contains the EntryID of the Calendar folder.

**Property ID:** 0x36D0

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_APPOINTMENT\_ENTRYID

### 2.742 PidTagIpmContactEntryId

**Canonical name:** PidTagIpmContactEntryId

**Description:** Contains the EntryID of the Contacts folder.

**Property ID:** 0x36D1

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_CONTACT\_ENTRYID

### 2.743 PidTagIpmDraftsEntryId

**Canonical name:** PidTagIpmDraftsEntryId

**Description:** Contains the EntryID of the Drafts folder.

**Property ID:** 0x36D7

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Alternate names:** PR\_IPM\_DRAFTS\_ENTRYID

### 2.744 PidTagIpmJournalEntryId

**Canonical name:** PidTagIpmJournalEntryId

**Description:** Contains the EntryID of the Journal folder.

**Property ID:** 0x36D2

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_JOURNAL\_ENTRYID

### 2.745 PidTagIpmNoteEntryId

**Canonical name:** PidTagIpmNoteEntryId

**Description:** Contains the EntryID of the Notes folder.

**Property ID:** 0x36D3

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_NOTE\_ENTRYID

### 2.746 PidTagIpmTaskEntryId

**Canonical name:** PidTagIpmTaskEntryId

**Description:** Contains the EntryID of the Tasks folder.

**Property ID:** 0x36D4

**Data type:** PtypBinary, 0x0102

**Area:** Folder Properties

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Consuming references:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_IPM\_TASK\_ENTRYID

### 2.747 PidTagIsdnNumber

**Canonical name:** PidTagIsdnNumber

**Description:** Contains the **Integrated Services Digital Network (ISDN)** telephone number of the mail user.

**Property ID:** 0x3A2D

**Data type:** PtypString, 0x001F

**Area:** Address Properties



**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.16

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_ISDN\_NUMBER, PR\_ISDN\_NUMBER\_A, PR\_ISDN\_NUMBER\_W,  
urn:schemas:contacts:internationalisdnumber

## 2.748 PidTagJunkAddRecipientsToSafeSendersList

**Canonical name:** PidTagJunkAddRecipientsToSafeSendersList

**Description:** Indicates whether email recipients are to be added to the safe senders list.

**Property ID:** 0x6103

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.1

**Alternate names:** PR\_JUNK\_ADD\_RECIPS\_TO\_SSL

## 2.749 PidTagJunkIncludeContacts

**Canonical name:** PidTagJunkIncludeContacts

**Description:** Indicates whether email addresses of the contacts in the Contacts folder are treated in a special way with respect to the spam filter.

**Property ID:** 0x6100

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.2

**Alternate names:** PR\_JUNK\_INCLUDE\_CONTACTS

## 2.750 PidTagJunkPermanentlyDelete

**Canonical name:** PidTagJunkPermanentlyDelete

**Description:** Indicates whether messages identified as spam can be permanently deleted.

**Property ID:** 0x6102

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.3

**Alternate names:** PR\_JUNK\_PERMANENTLY\_DELETE

## 2.751 PidTagJunkPhishingEnableLinks

**Canonical name:** PidTagJunkPhishingEnableLinks

**Description:** Indicated whether the phishing stamp on a message is to be ignored.

**Property ID:** 0x6107

**Data type:** PtypBoolean, 0x000B

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.4

**Consuming reference:** [\[MS-OXPHISH\]](#)

**Alternate names:** PR\_JUNK\_PHISHING\_ENABLE\_LINKS

## 2.752 PidTagJunkThreshold

**Canonical name:** PidTagJunkThreshold

**Description:** Indicates how aggressively incoming email is to be sent to the Junk Email folder.

**Property ID:** 0x6101

**Data type:** PtypInteger32, 0x0003

**Area:** Spam

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.5

**Alternate names:** PR\_JUNK\_THRESHOLD

## 2.753 PidTagKeyword

**Canonical name:** PidTagKeyword

**Description:** Contains a keyword that identifies the mail user to the mail user's system administrator.

**Property ID:** 0x3A0B

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.32

**Alternate names:** PR\_KEYWORD, PR\_KEYWORD\_A, PR\_KEYWORD\_W

## 2.754 PidTagLanguage

**Canonical name:** PidTagLanguage

**Description:** Contains a value that indicates the language in which the messaging user is writing messages.

**Property ID:** 0x3A0C

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.4

**Alternate names:** PR\_LANGUAGE, PR\_LANGUAGE\_A, PR\_LANGUAGE\_W,  
urn:schemas:contacts:language

## 2.755 PidTagLastModificationTime

**Canonical name:** PidTagLastModificationTime

**Description:** Contains the time, in UTC, of the last modification to the object.

**Property ID:** 0x3008

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.2

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-EXOABK\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_LAST\_MODIFICATION\_TIME, ptagLastModificationTime,  
urn:schemas:calendar:lastmodifiedtime, DAV:getlastmodified

## 2.756 PidTagLastModifierEntryId

**Canonical name:** PidTagLastModifierEntryId

**Description:** Specifies the Address Book EntryID of the last user to modify the contents of the message.

**Property ID:** 0x3FFB

**Data type:** PtypBinary, 0x0102

**Area:** History Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.32

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_ENTRYID, ptagLastModifierEntryId

## 2.757 PidTagLastModifierName

**Canonical name:** PidTagLastModifierName

**Description:** Contains the name of the last mail user to change the Message object.

**Property ID:** 0x3FFA

**Data type:** PtypString, 0x001F

**Area:** History Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_LAST\_MODIFIER\_NAME, PR\_LAST\_MODIFIER\_NAME\_A, ptagLastModifierName, PR\_LAST\_MODIFIER\_NAME\_W

## 2.758 PidTagLastVerbExecuted

**Canonical name:** PidTagLastVerbExecuted

**Description:** Specifies the last verb executed for the message item to which it is related.

**Property ID:** 0x1081

**Data type:** PtypInteger32, 0x0003

**Area:** History Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.14

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTED, ptagLastVerbExecuted

## 2.759 PidTagLastVerbExecutionTime

**Canonical name:** PidTagLastVerbExecutionTime

**Description:** Contains the date and time, in UTC, during which the operation represented in the **PidTagLastVerbExecuted** property (section [2.758](#)) took place.

**Property ID:** 0x1082

**Data type:** PtypTime, 0x0040

**Area:** History Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.15

**Consuming Reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_LAST\_VERB\_EXECUTION\_TIME, ptagLastVerbExecutionTime

## 2.760 PidTagListHelp

**Canonical name:** PidTagListHelp

**Description:** Contains a URI that provides detailed help information for the mailing list from which an email message was sent.

**Property ID:** 0x1043

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.81

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_HELP, PR\_LIST\_HELP\_A, PR\_LIST\_HELP\_W

## 2.761 PidTagListSubscribe

**Canonical name:** PidTagListSubscribe

**Description:** Contains the URI that subscribes a recipient to a message's associated mailing list.

**Property ID:** 0x1044

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.82

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_SUBSCRIBE, PR\_LIST\_SUBSCRIBE\_A, PR\_LIST\_SUBSCRIBE\_W

## 2.762 PidTagListUnsubscribe

**Canonical name:** PidTagListUnsubscribe

**Description:** Contains the URI that unsubscribes a recipient from a message's associated mailing list.

**Property ID:** 0x1045

**Data type:** PtypString, 0x001F

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.83

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_LIST\_UNSUBSCRIBE, PR\_LIST\_UNSUBSCRIBE\_A, PR\_LIST\_UNSUBSCRIBE\_W

## 2.763 PidTagLocalCommitTime

**Canonical name:** PidTagLocalCommitTime

**Description:** Specifies the time, in UTC, that a Message object or Folder object was last changed.

**Property ID:** 0x6709

**Data type:** PtypTime, 0x0040

**Area:** Server

**Defining references:** [\[MS-OXCMSG\]](#) section 2.2.1.49; [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.13

**Alternate names:** PR\_LOCAL\_COMMIT\_TIME, ptagLocalCommitTime

## 2.764 PidTagLocalCommitTimeMax

**Canonical name:** PidTagLocalCommitTimeMax

**Description:** Contains the time of the most recent message change within the folder container, excluding messages changed within subfolders.

**Property ID:** 0x670A

**Data type:** PtypTime, 0x0040

**Area:** Server

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.14

**Consuming Reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_LOCAL\_COMMIT\_TIME\_MAX, ptagLocalCommitTimeMax

## 2.765 PidTagLocaleId

**Canonical name:** PidTagLocaleId

**Description:** Contains the **Logon object** LocaleID.

**Property ID:** 0x66A1

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.12

**Consuming references:** [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_LOCALE\_ID, ptagLocaleId

## 2.766 PidTagLocality

**Canonical name:** PidTagLocality

**Description:** Contains the name of the mail user's locality, such as the town or city.

**Property ID:** 0x3A27

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.16

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_LOCALITY, PR\_LOCALITY\_A, PR\_LOCALITY\_W, PR\_BUSINESS\_ADDRESS\_LOCALITY, PR\_BUSINESS\_ADDRESS\_LOCALITY\_A, PR\_BUSINESS\_ADDRESS\_LOCALITY\_W, urn:schemas:contacts:mailingcity

## 2.767 PidTagLocation

**Canonical name:** PidTagLocation

**Description:** Contains the location of the mail user.

**Property ID:** 0x3A0D

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.5

**Consuming references:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_LOCATION, PR\_LOCATION\_A, PR\_LOCATION\_W,  
urn:schemas:contacts:location

## 2.768 PidTagMailboxOwnerEntryId

**Canonical name:** PidTagMailboxOwnerEntryId

**Description:** Contains the EntryID in the Global Address List (GAL) of the owner of the mailbox.

**Property ID:** 0x661B

**Data type:** PtypBinary, 0x0102

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.7

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_ENTRYID, ptagMailboxOwnerEntryId

## 2.769 PidTagMailboxOwnerName

**Canonical name:** PidTagMailboxOwnerName

**Description:** Contains the display name of the owner of the mailbox.

**Property ID:** 0x661C

**Data type:** PtypString, 0x001F

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.8

**Consuming reference:** [\[MS-OXOCAL\]](#)

**Alternate names:** PR\_MAILBOX\_OWNER\_NAME, PR\_MAILBOX\_OWNER\_NAME\_A,  
ptagMailboxOwnerName, PR\_MAILBOX\_OWNER\_NAME\_W

## 2.770 PidTagManagerName

**Canonical name:** PidTagManagerName

**Description:** Contains the name of the mail user's manager.

**Property ID:** 0x3A4E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.6

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MANAGER\_NAME, PR\_MANAGER\_NAME\_A, PR\_MANAGER\_NAME\_W,  
urn:schemas:contacts:manager

## 2.771 PidTagMappingSignature

**Canonical name:** PidTagMappingSignature

**Description:** A 16-byte constant that is present on all Address Book objects, but is not present on objects in an offline address book.

**Property ID:** 0x0FF8

**Data type:** PtypBinary, 0x0102

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.32

**Consuming reference:** [\[MS-OXNSPI\]](#)

**Alternate names:** PR\_MAPPING\_SIGNATURE, ptagMappingSignature

## 2.772 PidTagMaximumSubmitMessageSize

**Canonical name:** PidTagMaximumSubmitMessageSize

**Description:** Maximum size, in kilobytes, of a message that a user is allowed to submit for transmission to another user.

**Property ID:** 0x666D

**Data type:** PtypInteger32, 0x0003

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.2

**Alternate names:** PR\_MAX\_SUBMIT\_MESSAGE\_SIZE

## 2.773 PidTagMemberId

**Canonical name:** PidTagMemberId

**Description:** Contains a unique identifier that the messaging server generates for each user.

**Property ID:** 0x6671

**Data type:** PtypInteger64, 0x0014

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.5

**Alternate names:** PR\_MEMBER\_ID, ptagMemberId

## 2.774 PidTagMemberName

**Canonical name:** PidTagMemberName

**Description:** Contains the user-readable name of the user.

**Property ID:** 0x6672

**Data type:** PtypString, 0x001F



**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.6

**Alternate names:** PR\_MEMBER\_NAME, PR\_MEMBER\_NAME\_A, ptagMemberName, PR\_MEMBER\_NAME\_W

## 2.775 PidTagMemberRights

**Canonical name:** PidTagMemberRights

**Description:** Contains the permissions for the specified user.

**Property ID:** 0x6673

**Data type:** PtypInteger32, 0x0003

**Area:** Access Control Properties

**Defining reference:** [\[MS-OXCPERM\]](#) section 2.2.7

**Consuming references:** [\[MS-OXCFCOLD\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_MEMBER\_RIGHTS, ptagMemberRights

## 2.776 PidTagMessageAttachments

**Canonical name:** PidTagMessageAttachments

**Description:** Identifies all attachments to the current message.

**Property ID:** 0x0E13

**Data type:** PtypObject, 0x000D

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.52

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCXICS\]](#)

**Alternate names:** PR\_MESSAGE\_ATTACHMENTS, ptagMessageAttachments

## 2.777 PidTagMessageCcMe

**Canonical name:** PidTagMessageCcMe

**Description:** Indicates that the receiving mailbox owner is a carbon copy (Cc) recipient of this email message.

**Property ID:** 0x0058

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.18

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_CC\_ME, ptagMessageCcMe

## 2.778 PidTagMessageClass

**Canonical name:** PidTagMessageClass

**Description:** Denotes the specific type of the Message object.

**Property ID:** 0x001A

**Data type:** PtypString, 0x001F

**Area:** Common Property set

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.3

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCROPS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMIME\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOUM\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_MESSAGE\_CLASS, PR\_MESSAGE\_CLASS\_A, ptagMessageClass, PR\_MESSAGE\_CLASS\_W,  
<http://schemas.microsoft.com/exchange/outlookmessageclass>  
<http://schemas.microsoft.com/exchange/outlookmessageclass>

## 2.779 PidTagMessageCodepage

**Canonical name:** PidTagMessageCodepage

**Description:** Specifies the code page used to encode the **non-Unicode** string properties on this Message object.

**Property ID:** 0x3FFD

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.4

**Consuming references:** [\[MS-OXTNEF\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_MESSAGE\_CODEPAGE

## 2.780 PidTagMessageDeliveryTime

**Canonical name:** PidTagMessageDeliveryTime

**Description:** Specifies the time (in UTC) when the server received the message.

**Property ID:** 0x0E06

**Data type:** PtypTime, 0x0040

**Area:** Message Time Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.9

**Consuming references:** [\[MS-OXCDATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXORSS\]](#)

**Alternate names:** PR\_MESSAGE\_DELIVERY\_TIME, urn:schemas:httpmail:datereceived

## 2.781 PidTagMessageEditorFormat

**Canonical name:** PidTagMessageEditorFormat

**Description:** Specifies the format that an email editor can use for editing the message body.

**Property ID:** 0x5909

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.78

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MSG\_EDITOR\_FORMAT, ptagMsgEditorFormat

## 2.782 PidTagMessageFlags

**Canonical name:** PidTagMessageFlags

**Description:** Specifies the status of the Message object.

**Property ID:** 0x0E07

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXOSMMS\]](#)

**Alternate names:** PR\_MESSAGE\_FLAGS, ptagMessageFlags

## 2.783 PidTagMessageHandlingSystemCommonName

**Canonical name:** PidTagMessageHandlingSystemCommonName

**Description:** Contains the **common name** of a messaging user for use in a message header.

**Property ID:** 0x3A0F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.33

**Alternate names:** PR\_MHS\_COMMON\_NAME, PR\_MHS\_COMMON\_NAME\_A, PR\_MHS\_COMMON\_NAME\_W, urn:schemas:contacts:dn

## 2.784 PidTagMessageLocaleId

**Canonical name:** PidTagMessageLocaleId

**Description:** Contains the Windows Locale ID of the end-user who created this message.

**Property ID:** 0x3FF1

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.5

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_LOCALE\_ID

## 2.785 PidTagMessageRecipientMe

**Canonical name:** PidTagMessageRecipientMe

**Description:** Indicates that the receiving mailbox owner is a primary or a carbon copy (Cc) recipient of this email message.

**Property ID:** 0x0059

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.19

**Consuming Reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIP\_ME, ptagMessageRecipMe

## 2.786 PidTagMessageRecipients

**Canonical name:** PidTagMessageRecipients

**Description:** Identifies all of the recipients of the current message.

**Property ID:** 0x0E12

**Data type:** PtypObject, 0x000D

**Area:** Address Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.47

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_RECIPIENTS, ptagMessageRecipients

## 2.787 PidTagMessageSize

**Canonical name:** PidTagMessageSize

**Description:** Contains the size, in bytes, consumed by the Message object on the server.

**Property ID:** 0x0E08

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.10

**Consuming references:** [\[MS-OXCSTOR\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE, ptagMessageSize

## 2.788 PidTagMessageSizeExtended

**Canonical name:** PidTagMessageSizeExtended

**Description:** Specifies the 64-bit version of the **PidTagMessageSize** property (section [2.787](#)).

**Property ID:** 0x0E08

**Data type:** PtypInteger64, 0x0014

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.11

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** PR\_MESSAGE\_SIZE\_EXTENDED, ptagMessageSizeExtended

## 2.789 PidTagMessageStatus

**Canonical name:** PidTagMessageStatus

**Description:** Specifies the status of a message in a **contents table**.

**Property ID:** 0x0E17

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_MSG\_STATUS, ptagMsgStatus

## 2.790 PidTagMessageSubmissionId

**Canonical name:** PidTagMessageSubmissionId

**Description:** Contains a message identifier assigned by a message transfer agent.

**Property ID:** 0x0047

**Data type:** PtypBinary, 0x0102

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.79

**Consuming references:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_SUBMISSION\_ID, ptagMessageSubmissionId

## 2.791 PidTagMessageToMe

**Canonical name:** PidTagMessageToMe

**Description:** Indicates that the receiving mailbox owner is one of the primary recipients of this email message.

**Property ID:** 0x0057

**Data type:** PtypBoolean, 0x000B

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.17

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_MESSAGE\_TO\_ME, ptagMessageToMe

## 2.792 PidTagMid

**Canonical name:** PidTagMid

**Description:** Contains a value that contains the MID of the message currently being synchronized.

**Property ID:** 0x674A

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.1

**Consuming references:** [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPROTO\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** ptagMID, <http://schemas.microsoft.com/exchange/mid>

## 2.793 PidTagMiddleName

**Canonical name:** PidTagMiddleName

**Description:** Specifies the middle name(s) of the contact.

**Property ID:** 0x3A44

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MIDDLE\_NAME, PR\_MIDDLE\_NAME\_A, PR\_MIDDLE\_NAME\_W, urn:schemas:contacts:middlename

## 2.794 PidTagMimeSkeleton

**Canonical name:** PidTagMimeSkeleton

**Description:** Contains the top-level MIME message headers, all MIME message body part headers, and body part content that is not already converted to Message object properties, including attachments.

**Property ID:** 0x64F0

**Data type:** PtypBinary, 0x0102

**Area:** MIME properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.28

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagMimeSkeleton

## 2.795 PidTagMobileTelephoneNumber

**Canonical name:** PidTagMobileTelephoneNumber

**Description:** Contains the mail user's cellular telephone number.

**Property ID:** 0x3A1C

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.27

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_MOBILE\_TELEPHONE\_NUMBER, PR\_MOBILE\_TELEPHONE\_NUMBER\_A, PR\_MOBILE\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:mobile

## 2.796 PidTagNativeBody

**Canonical name:** PidTagNativeBody

**Description:** Indicates the best available format for storing the message body.

**Property ID:** 0x1016

**Data type:** PtypInteger32, 0x0003

**Area:** BestBody

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.2

**Consuming Reference:** [\[MS-OXBBODY\]](#)

**Alternate names:** PR\_NATIVE\_BODY\_INFO, ptagNativeBodyInfo

## 2.797 PidTagNextSendAcct

**Canonical name:** PidTagNextSendAcct

**Description:** Specifies the server that a client is currently attempting to use to send email.

**Property ID:** 0x0E29

**Data type:** PtypString, 0x001F

**Area:** Outlook Application

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.65

**Consuming Reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_NEXT\_SEND\_ACCT

## 2.798 PidTagNickname

**Canonical name:** PidTagNickname

**Description:** Contains the mail user's nickname.

**Property ID:** 0x3A4F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.1.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_NICKNAME, PR\_NICKNAME\_A, PR\_NICKNAME\_W,  
urn:schemas:contacts:nickname

## 2.799 PidTagNonDeliveryReportDiagCode

**Canonical name:** PidTagNonDeliveryReportDiagCode

**Description:** Contains the diagnostic code for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C05

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.30

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_DIAG\_CODE, ptagNonDeliveryDiagCode

## 2.800 PidTagNonDeliveryReportReasonCode

**Canonical name:** PidTagNonDeliveryReportReasonCode

**Description:** Contains an integer value that indicates a reason for delivery failure.



**Property ID:** 0x0C04

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.31

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_REASON\_CODE, ptagNDRReasonCode

## 2.801 PidTagNonDeliveryReportStatusCode

**Canonical name:** PidTagNonDeliveryReportStatusCode

**Description:** Contains the value of the Status field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C20

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.32

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_NDR\_STATUS\_CODE, ptagNDRStatusCode

## 2.802 PidTagNonReceiptNotificationRequested

**Canonical Name:** PidTagNonReceiptNotificationRequested

**Description:** Specifies whether the client sends a non-read receipt.

**Property ID:** 0x0C06

**Data type:** PtypBoolean, 0x000B

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.31

**Alternate names:** PR\_NON\_RECEIPT\_NOTIFICATION\_REQUESTED

## 2.803 PidTagNormalizedSubject

**Canonical name:** PidTagNormalizedSubject

**Description:** Contains the normalized subject of the message.

**Property ID:** 0x0E1D

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.10

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXVCARD\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_NORMALIZED\_SUBJECT, PR\_NORMALIZED\_SUBJECT\_A, ptagNormalizedSubject, PR\_NORMALIZED\_SUBJECT\_W, urn:schemas:httpmail:normalizedsubject

## 2.804 PidTagObjectType

**Canonical name:** PidTagObjectType

**Description:** Indicates the type of **Server object**.

**Property ID:** 0x0FFE

**Data type:** PtypInteger32, 0x0003

**Area:** Common

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.7

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOSRCH\]](#)

**Alternate names:** PR\_OBJECT\_TYPE, ptagObjectType

## 2.805 PidTagOfficeLocation

**Canonical name:** PidTagOfficeLocation

**Description:** Contains the mail user's office location.

**Property ID:** 0x3A19

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.5

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_OFFICE\_LOCATION, PR\_OFFICE\_LOCATION\_A, PR\_OFFICE\_LOCATION\_W, urn:schemas:contacts:roomnumber

## 2.806 PidTagOfflineAddressBookContainerGuid

**Canonical name:** PidTagOfflineAddressBookContainerGuid

**Description:** A string-formatted GUID that represents the **address list** container object.

**Property ID:** 0x6802

**Data type:** PtypString8, 0x001E

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.1

**Alternate names:** PR\_OAB\_CONTAINER\_GUID, PR\_OAB\_CONTAINER\_GUID\_W

### **2.807 PidTagOfflineAddressBookDistinguishedName**

**Canonical name:** PidTagOfflineAddressBookDistinguishedName

**Description:** Contains the DN of the address list that is contained in the OAB message.

**Property ID:** 0x6804

**Data type:** PtypString8, 0x001E

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.2

**Alternate names:** PR\_OAB\_DN, PR\_OAB\_DN\_W

### **2.808 PidTagOfflineAddressBookMessageClass**

**Canonical name:** PidTagOfflineAddressBookMessageClass

**Description:** Contains the message class for full OAB messages.

**Property ID:** 0x6803

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXPFOAB\]](#) section 2.2.2.1.1

**Alternate names:** PR\_OAB\_MESSAGE\_CLASS

### **2.809 PidTagOfflineAddressBookName**

**Canonical name:** PidTagOfflineAddressBookName

**Description:** Contains the display name of the address list.

**Property ID:** 0x6800

**Data type:** PtypString, 0x001F

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.3

**Alternate names:** PR\_OAB\_NAME, PR\_OAB\_NAME\_W

### **2.810 PidTagOfflineAddressBookSequence**

**Canonical name:** PidTagOfflineAddressBookSequence

**Description:** Contains the sequence number of the OAB.

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.12.4

**Alternate names:** PR\_OAB\_SEQUENCE

### 2.811 PidTagOfflineAddressBookTruncatedProperties

**Canonical name:** PidTagOfflineAddressBookTruncatedProperties

**Description:** Contains a list of the property tags that have been truncated or limited by the server.

**Property ID:** 0x6805

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Offline Address Book Properties

**Defining reference:** [\[MS-OXOAB\]](#) section 2.9.2.2

**Alternate names:** PR\_OAB\_TRUNCATED\_PROPS

### 2.812 PidTagOrdinalMost

**Canonical name:** PidTagOrdinalMost

**Description:** Contains a positive number whose negative is less than or equal to the value of the **PidLidTaskOrdinal** property (section [2.327](#)) of all of the Task objects in the folder.

**Property ID:** 0x36E2

**Data type:** PtypInteger32, 0x0003

**Area:** Tasks

**Defining reference:** [\[MS-OXOTASK\]](#) section 2.2.1.1

**Alternate names:** PR\_ORDINAL\_MOST

### 2.813 PidTagOrganizationalIdNumber

**Canonical name:** PidTagOrganizationalIdNumber

**Description:** Contains an identifier for the mail user used within the mail user's organization.

**Property ID:** 0x3A10

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.7

**Alternate names:** PR\_ORGANIZATIONAL\_ID\_NUMBER, PR\_ORGANIZATIONAL\_ID\_NUMBER\_A, PR\_ORGANIZATIONAL\_ID\_NUMBER\_W, urn:schemas:contacts:employeeenumber

### 2.814 PidTagOriginalAuthorEntryId

**Canonical name:** PidTagOriginalAuthorEntryId

**Description:** Contains an address book EntryID structure ([\[MS-OXCDATA\]](#) section 2.2.5.2) and is defined in report messages to identify the user who sent the original message.

**Property ID:** 0x004C

**Data type:** PtypBinary, 0x0102

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.32

**Alternate names:** PR\_ORIGINAL\_AUTHOR\_ENTRYID

### 2.815 PidTagOriginalAuthorName

**Canonical name:** PidTagOriginalAuthorName

**Description:** Contains the display name of the sender of the original message referenced by a report message.

**Property ID:** 0x004D

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.33

**Alternate names:** PR\_ORIGINAL\_AUTHOR\_NAME\_W

### 2.816 PidTagOriginalDeliveryTime

**Canonical name:** PidTagOriginalDeliveryTime

**Description:** Contains the delivery time, in UTC, from the original message.

**Property ID:** 0x0055

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.2

**Alternate names:** PR\_ORIGINAL\_DELIVERY\_TIME, ptagOriginalDeliveryTime

### 2.817 PidTagOriginalDisplayBcc

**Canonical name:** PidTagOriginalDisplayBcc

**Description:** Contains the value of the **PidTagDisplayBcc** property (section [2.665](#)) from the original message.

**Property ID:** 0x0072

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.5

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_BCC, PR\_ORIGINAL\_DISPLAY\_BCC\_A, ptagOriginalDisplayBcc, PR\_ORIGINAL\_DISPLAY\_BCC\_W, <http://schemas.microsoft.com/exchange/originaldisplaybcc>

## 2.818 PidTagOriginalDisplayCc

**Canonical name:** PidTagOriginalDisplayCc

**Description:** Contains the value of the **PidTagDisplayCc** property (section [2.666](#)) from the original message.

**Property ID:** 0x0073

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.4

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_CC, PR\_ORIGINAL\_DISPLAY\_CC\_A, ptagOriginalDisplayCc, PR\_ORIGINAL\_DISPLAY\_CC\_W, <http://schemas.microsoft.com/exchange/originaldisplaycc>, [http://schemas.microsoft.com/mapi/original\\_display\\_cc](http://schemas.microsoft.com/mapi/original_display_cc)

## 2.819 PidTagOriginalDisplayTo

**Canonical name:** PidTagOriginalDisplayTo

**Description:** Contains the value of the **PidTagDisplayTo** property (section [2.669](#)) from the original message.

**Property ID:** 0x0074

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.3

**Alternate names:** PR\_ORIGINAL\_DISPLAY\_TO, PR\_ORIGINAL\_DISPLAY\_TO\_A, ptagOriginalDisplayTo, PR\_ORIGINAL\_DISPLAY\_TO\_W, <http://schemas.microsoft.com/exchange/originaldisplayto>, [http://schemas.microsoft.com/mapi/original\\_display\\_to](http://schemas.microsoft.com/mapi/original_display_to)

## 2.820 PidTagOriginalEntryId

**Canonical name:** PidTagOriginalEntryId

**Description:** Contains the original EntryID of an object.

**Property ID:** 0x3A12

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.9

**Alternate names:** PR\_ORIGINAL\_ENTRYID, ptagOriginalEntryId

## 2.821 PidTagOriginalMessageClass

**Canonical name:** PidTagOriginalMessageClass

**Description:** Designates the **PidTagMessageClass** property ([\[MS-OXCMMSG\]](#) section 2.2.1.3) from the original message.

**Property ID:** 0x004B

**Data type:** PtypString, 0x001F

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.86

**Consuming reference:** [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIG\_MESSAGE\_CLASS, PR\_ORIG\_MESSAGE\_CLASS\_A, PR\_ORIG\_MESSAGE\_CLASS\_W

## 2.822 PidTagOriginalMessageId

**Canonical name:** PidTagOriginalMessageId

**Description:** Contains the message ID of the original message included in replies or resent messages.

**Property ID:** 0x1046

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.85

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagOriginalInternetMessageID, OriginalMessageId

## 2.823 PidTagOriginalSenderAddressType

**Canonical name:** PidTagOriginalSenderAddressType

**Description:** Contains the value of the original message sender's **PidTagSenderAddressType** property (section [2.991](#)).

**Property ID:** 0x0066

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.6

**Alternate names:** PR\_ORIGINAL\_SENDER\_ADDRTYPE, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_A, ptagOriginalSenderAddrType, PR\_ORIGINAL\_SENDER\_ADDRTYPE\_W

## 2.824 PidTagOriginalSenderEmailAddress

**Canonical name:** PidTagOriginalSenderEmailAddress

**Description:** Contains the value of the original message sender's **PidTagSenderEmailAddress** property (section [2.992](#)).

**Property ID:** 0x0067

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.7

**Alternate names:** PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENDER\_EMAIL\_ADDRESS\_W

## 2.825 PidTagOriginalSenderEntryId

**Canonical name:** PidTagOriginalSenderEntryId

**Description:** Contains an address book EntryID that is set on delivery report messages.

**Property ID:** 0x005B

**Data type:** **PtypBinary**, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.8

**Alternate names:** PR\_ORIGINAL\_SENDER\_ENTRYID, ptagOriginalSenderEntryId

## 2.826 PidTagOriginalSenderName

**Canonical name:** PidTagOriginalSenderName

**Description:** Contains the value of the original message sender's **PidTagSenderName** property (section [2.995](#)), and is set on delivery report messages.

**Property ID:** 0x005A

**Data type:** **PtypString**, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.9

**Alternate names:** PR\_ORIGINAL\_SENDER\_NAME, PR\_ORIGINAL\_SENDER\_NAME\_A, ptagOriginalSenderName, PR\_ORIGINAL\_SENDER\_NAME\_W, <http://schemas.microsoft.com/exchange/originaisendername>

## 2.827 PidTagOriginalSenderSearchKey

**Canonical name:** PidTagOriginalSenderSearchKey

**Description:** Contains an address book search key set on the original email message.

**Property ID:** 0x005C

**Data type:** **PtypBinary**, 0x0102

**Area:** General Message Properties



**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.10

**Alternate names:** PR\_ORIGINAL\_SENDER\_SEARCH\_KEY, ptagOriginalSenderSearchKey

## 2.828 PidTagOriginalSensitivity

**Canonical name:** PidTagOriginalSensitivity

**Description:** Contains the sensitivity value of the original email message.

**Property ID:** 0x002E

**Data type:** PtypInteger32, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.22

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_ORIGINAL\_SENSITIVITY, ptagOriginalSensitivity

## 2.829 PidTagOriginalSentRepresentingAddressType

**Canonical name:** PidTagOriginalSentRepresentingAddressType

**Description:** Contains the address type of the end user who is represented by the original email message sender.

**Property ID:** 0x0068

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.11

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_A, ptagOriginalSentRepresentingAddrType, PR\_ORIGINAL\_SENT\_REPRESENTING\_ADDRTYPE\_W

## 2.830 PidTagOriginalSentRepresentingEmailAddress

**Canonical name:** PidTagOriginalSentRepresentingEmailAddress

**Description:** Contains the email address of the end user who is represented by the original email message sender.

**Property ID:** 0x0069

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.12

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_ORIGINAL\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.831 PidTagOriginalSentRepresentingEntryId

**Canonical name:** PidTagOriginalSentRepresentingEntryId

**Description:** Identifies an address book EntryID that contains the entry identifier of the end user who is represented by the original message sender.

**Property ID:** 0x005E

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.13

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_ENTRYID, ptagOriginalSentRepresentingEntryId

## 2.832 PidTagOriginalSentRepresentingName

**Canonical name:** PidTagOriginalSentRepresentingName

**Description:** Contains the display name of the end user who is represented by the original email message sender.

**Property ID:** 0x005D

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.14

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME, PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_A, ptagOriginalSentRepresentingName, PR\_ORIGINAL\_SENT\_REPRESENTING\_NAME\_W

## 2.833 PidTagOriginalSentRepresentingSearchKey

**Canonical name:** PidTagOriginalSentRepresentingSearchKey

**Description:** Identifies an address book search key that contains the SearchKey of the end user who is represented by the original message sender.

**Property ID:** 0x005F

**Data type:** PtypBinary, 0x0102

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.15

**Alternate names:** PR\_ORIGINAL\_SENT\_REPRESENTING\_SEARCH\_KEY, ptagOriginalSentRepresentingSearchKey

## 2.834 PidTagOriginalSubject

**Canonical name:** PidTagOriginalSubject

**Description:** Specifies the subject of the original message.

**Property ID:** 0x0049

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.16

**Alternate names:** PR\_ORIGINAL\_SUBJECT, PR\_ORIGINAL\_SUBJECT\_A, ptagOriginalSubject, PR\_ORIGINAL\_SUBJECT\_W, <http://schemas.microsoft.com/exchange/originalsubject>, [http://schemas.microsoft.com/mapi/original\\_subject](http://schemas.microsoft.com/mapi/original_subject)

## 2.835 PidTagOriginalSubmitTime

**Canonical name:** PidTagOriginalSubmitTime

**Description:** Specifies the original email message's submission date and time, in UTC.

**Property ID:** 0x004E

**Data type:** PtypTime, 0x0040

**Area:** General Message Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.17

**Alternate names:** PR\_ORIGINAL\_SUBMIT\_TIME, ptagOriginalSubmitTime, <http://schemas.microsoft.com/exchange/originaldate>, [http://schemas.microsoft.com/mapi/original\\_submit\\_time](http://schemas.microsoft.com/mapi/original_submit_time)

## 2.836 PidTagOriginatorDeliveryReportRequested

**Canonical name:** PidTagOriginatorDeliveryReportRequested

**Description:** Indicates whether an email sender requests an email **delivery receipt** from the messaging system.

**Property ID:** 0x0023

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.20

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_ORIGINATOR\_DELIVERY\_REPORT\_REQUESTED, <http://schemas.microsoft.com/exchange/deliveryreportrequested>

## 2.837 PidTagOriginatorNonDeliveryReportRequested

**Canonical name:** PidTagOriginatorNonDeliveryReportRequested

**Description:** Specifies whether an email sender requests suppression of nondelivery receipts.

**Property ID:** 0x0C08

**Data type:** PtypBoolean, 0x000B

**Area:** MIME Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.21

**Alternate names:** PR\_ORIGINATOR\_NON\_DELIVERY\_REPORT\_REQUESTED

### 2.838 PidTagOscSyncEnabled

**Canonical name:** PidTagOscSyncEnabled

**Description:** Specifies whether contact synchronization with an external source is handled by the server.

**Property ID:** 0x7C24

**Data type:** **PtypBoolean**, 0x000B

**Area:** Contact Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.9.7

**Alternate names:** PR\_OSC\_SYNC\_ENABLEDONSERVER

### 2.839 PidTagOtherAddressCity

**Canonical name:** PidTagOtherAddressCity

**Description:** Contains the name of the mail user's other locality, such as the town or city.

**Property ID:** 0x3A5F

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.2

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_CITY, PR\_OTHER\_ADDRESS\_CITY\_A, PR\_OTHER\_ADDRESS\_CITY\_W, urn:schemas:contacts:othercity

### 2.840 PidTagOtherAddressCountry

**Canonical name:** PidTagOtherAddressCountry

**Description:** Contains the name of the mail user's other country/region.

**Property ID:** 0x3A60

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.5

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_COUNTRY, PR\_OTHER\_ADDRESS\_COUNTRY\_A, PR\_OTHER\_ADDRESS\_COUNTRY\_W, urn:schemas:contacts:othercountry

## 2.841 PidTagOtherAddressPostalCode

**Canonical name:** PidTagOtherAddressPostalCode

**Description:** Contains the postal code for the mail user's other postal address.

**Property ID:** 0x3A61

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_POSTAL\_CODE, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_A, PR\_OTHER\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:otherpostalcode

## 2.842 PidTagOtherAddressPostOfficeBox

**Canonical name:** PidTagOtherAddressPostOfficeBox

**Description:** Contains the number or identifier of the mail user's other post office box.

**Property ID:** 0x3A64

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.7

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_OTHER\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:otherpostofficebox

## 2.843 PidTagOtherAddressStateOrProvince

**Canonical name:** PidTagOtherAddressStateOrProvince

**Description:** Contains the name of the mail user's other state or province.

**Property ID:** 0x3A62

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_OTHER\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:otherstate

## 2.844 PidTagOtherAddressStreet

**Canonical name:** PidTagOtherAddressStreet

**Description:** Contains the mail user's other street address.

**Property ID:** 0x3A63

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.1

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_ADDRESS\_STREET, PR\_OTHER\_ADDRESS\_STREET\_A, PR\_OTHER\_ADDRESS\_STREET\_W, urn:schemas:contacts:otherstreet

## 2.845 PidTagOtherTelephoneNumber

**Canonical name:** PidTagOtherTelephoneNumber

**Description:** Contains an alternate telephone number for the mail user.

**Property ID:** 0x3A1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.10

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_OTHER\_TELEPHONE\_NUMBER, PR\_OTHER\_TELEPHONE\_NUMBER\_A, PR\_OTHER\_TELEPHONE\_NUMBER\_W, urn:schemas:contacts:otherTelephone

## 2.846 PidTagOutOfOfficeState

**Canonical name:** PidTagOutOfOfficeState

**Description:** Indicates whether the user is **OOF**.

**Property ID:** 0x661D

**Data type:** PtypBoolean, 0x000B

**Area:** Message Store Properties

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.2.4

**Alternate names:** PR\_OOF\_STATE, ptagOOFState

## 2.847 PidTagOwnerAppointmentId

**Canonical name:** PidTagOwnerAppointmentId

**Description:** Specifies a quasi-unique value among all of the Calendar objects in a user's mailbox.

**Property ID:** 0x0062

**Data type:** PtypInteger32, 0x0003

**Area:** Appointment

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.29

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_OWNER\_APPT\_ID, [http://schemas.microsoft.com/mapi/owner\\_appt\\_id](http://schemas.microsoft.com/mapi/owner_appt_id)

## 2.848 PidTagPagerTelephoneNumber

**Canonical name:** PidTagPagerTelephoneNumber

**Description:** Contains the mail user's pager telephone number.

**Property ID:** 0x3A21

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.28

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PAGER\_TELEPHONE\_NUMBER, PR\_PAGER\_TELEPHONE\_NUMBER\_A, PR\_PAGER\_TELEPHONE\_NUMBER\_W, <urn:schemas:contacts:pager>

## 2.849 PidTagParentEntryId

**Canonical name:** PidTagParentEntryId

**Description:** Contains the EntryID of the folder where messages or subfolders reside.

**Property ID:** 0x0E09

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.7

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXOSFLD\]](#), [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_PARENT\_ENTRYID, ptagParentEntryId

## 2.850 PidTagParentFolderId

**Canonical name:** PidTagParentFolderId

**Description:** Contains a value that contains the Folder ID (FID), as specified in [\[MS-OXCADATA\]](#) section 2.2.1.1, that identifies the parent folder of the messaging object being synchronized.

**Property ID:** 0x6749

**Data type:** PtypInteger64, 0x0014

**Area:** ID Properties

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.4

**Alternate names:** ptagParentFID

## 2.851 PidTagParentKey

**Canonical name:** PidTagParentKey

**Description:** Contains the search key that is used to correlate the original message and the reports about the original message.

**Property ID:** 0x0025

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.18

**Alternate names:** PR\_PARENT\_KEY, ptagParentKey

## 2.852 PidTagParentSourceKey

**Canonical name:** PidTagParentSourceKey

**Description:** Contains a value on a folder that contains the **PidTagSourceKey** property (section [2.1012](#)) of the parent folder.

**Property ID:** 0x65E1

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.6

**Alternate names:** PR\_PARENT\_SOURCE\_KEY

## 2.853 PidTagPersonalHomePage

**Canonical name:** PidTagPersonalHomePage

**Description:** Contains the URL of the mail user's personal home page.

**Property ID:** 0x3A50

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.13

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PERSONAL\_HOME\_PAGE, PR\_PERSONAL\_HOME\_PAGE\_A, PR\_PERSONAL\_HOME\_PAGE\_W, urn:schemas:contacts:personalHomePage

## 2.854 PidTagPolicyTag

**Canonical name:** PidTagPolicyTag

**Description:** Specifies the GUID of a **retention tag**.



**Property ID:** 0x3019

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.2

**Alternate names:** PR\_POLICY\_TAG, ptagPolicyTag

## 2.855 PidTagPostalAddress

**Canonical name:** PidTagPostalAddress

**Description:** Contains the mail user's postal address.

**Property ID:** 0x3A15

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.3.8

**Alternate names:** PR\_POSTAL\_ADDRESS, PR\_POSTAL\_ADDRESS\_A, PR\_POSTAL\_ADDRESS\_W, urn:schemas:contacts:mailingpostaladdress

## 2.856 PidTagPostalCode

**Canonical name:** PidTagPostalCode

**Description:** Contains the postal code for the mail user's postal address.

**Property ID:** 0x3A2A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.18

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_POSTAL\_CODE, PR\_POSTAL\_CODE\_A, PR\_POSTAL\_CODE\_W, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_A, PR\_BUSINESS\_ADDRESS\_POSTAL\_CODE\_W, urn:schemas:contacts:mailingpostalcode

## 2.857 PidTagPostOfficeBox

**Canonical name:** PidTagPostOfficeBox

**Description:** Contains the number or identifier of the mail user's post office box.

**Property ID:** 0x3A2B

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.15

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_POST\_OFFICE\_BOX, PR\_POST\_OFFICE\_BOX\_A, PR\_POST\_OFFICE\_BOX\_W, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_A, PR\_BUSINESS\_ADDRESS\_POST\_OFFICE\_BOX\_W, urn:schemas:contacts:mailingpostofficebox

## 2.858 PidTagPredecessorChangeList

**Canonical name:** PidTagPredecessorChangeList

**Description:** Contains a value that contains a serialized representation of a **PredecessorChangeList** structure.

**Property ID:** 0x65E3

**Data type:** **PtypBinary**, 0x0102

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.8

**Alternate names:** PR\_PREDECESSOR\_CHANGE\_LIST

## 2.859 PidTagPrimaryFaxNumber

**Canonical name:** PidTagPrimaryFaxNumber

**Description:** Contains the telephone number of the mail user's primary fax machine.

**Property ID:** 0x3A23

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.29

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#)

**Alternate names:** PR\_PRIMARY\_FAX\_NUMBER, PR\_PRIMARY\_FAX\_NUMBER\_A, PR\_PRIMARY\_FAX\_NUMBER\_W, urn:schemas:contacts:otherfax

## 2.860 PidTagPrimarySendAccount

**Canonical name:** PidTagPrimarySendAccount

**Description:** Specifies the first server that a client is to use to send the email with.

**Property ID:** 0x0E28

**Data type:** **PtypString**, 0x001F

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.64

**Alternate names:** PR\_PRIMARY\_SEND\_ACCT

## 2.861 PidTagPrimaryTelephoneNumber

**Canonical name:** PidTagPrimaryTelephoneNumber

**Description:** Contains the mail user's primary telephone number.

**Property ID:** 0x3A1A

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.5

**Consuming references:** [\[MS-OXNSPI\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PRIMARY\_TELEPHONE\_NUMBER, PR\_PRIMARY\_TELEPHONE\_NUMBER\_A, PR\_PRIMARY\_TELEPHONE\_NUMBER\_W

## 2.862 PidTagPriority

**Canonical name:** PidTagPriority

**Description:** Indicates the client's request for the priority with which the message is to be sent by the messaging system.

**Property ID:** 0x0026

**Data type:** PtypInteger32, 0x0003

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.12

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXODOC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOJRN\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_PRIORITY, ptagPriority, urn:schemas:httpmail:priority, urn:schemas:httpmail:priority

## 2.863 PidTagProcessed

**Canonical name:** PidTagProcessed

**Description:** Indicates whether a client has already processed a received task communication.

**Property ID:** 0x7D01

**Data type:** PtypBoolean, 0x000B

**Area:** Calendar

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.5.7

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_PROCESSED

## 2.864 PidTagProfession

**Canonical name:** PidTagProfession

**Description:** Contains the name of the mail user's line of business.

**Property ID:** 0x3A46

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.6.9

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_PROFESSION, PR\_PROFESSION\_A, PR\_PROFESSION\_W,  
urn:schemas:contacts:profession

## 2.865 PidTagProhibitReceiveQuota

**Canonical name:** PidTagProhibitReceiveQuota

**Description:** Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before no further email will be delivered to their mailbox.

**Property ID:** 0x666A

**Data type:** PtypInteger32, 0x0003

**Area:** Exchange Administrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.3

**Alternate names:** PR\_PROHIBIT\_RECEIVE\_QUOTA, ptagProhibitReceiveQuota

## 2.866 PidTagProhibitSendQuota

**Canonical name:** PidTagProhibitSendQuota

**Description:** Maximum size, in kilobytes, that a user is allowed to accumulate in their mailbox before the user can no longer send any more email.

**Property ID:** 0x666E

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.4

**Alternate names:** PR\_PROHIBIT\_SEND\_QUOTA, ptagProhibitSendQuota

## 2.867 PidTagPurportedSenderDomain

**Canonical name:** PidTagPurportedSenderDomain

**Description:** Contains the **domain** responsible for transmitting the current message.

**Property ID:** 0x4083

**Data type:** PtypString, 0x001F

**Area:** TransportEnvelope

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_PURPORTED\_SENDER\_DOMAIN

## 2.868 PidTagRadioTelephoneNumber

**Canonical name:** PidTagRadioTelephoneNumber

**Description:** Contains the mail user's radio telephone number.

**Property ID:** 0x3A1D

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.8

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_RADIO\_TELEPHONE\_NUMBER, PR\_RADIO\_TELEPHONE\_NUMBER\_A, PR\_RADIO\_TELEPHONE\_NUMBER\_W

## 2.869 PidTagRead

**Canonical name:** PidTagRead

**Description:** Indicates whether a message has been read.

**Property ID:** 0x0E69

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable Property set

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.53

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCTABL\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_READ, ptagRead, urn:schemas:httpmail:read

## 2.870 PidTagReadReceiptAddressType

**Canonical name:** PidTagReadReceiptAddressType

**Description:** Contains the address type of the end user to whom a **read receipt** is directed.

**Property ID:** 0x4029

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.24

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptAddrType, ReadReceiptAddrType

## 2.871 PidTagReadReceiptEmailAddress

**Canonical name:** PidTagReadReceiptEmailAddress

**Description:** Contains the email address of the end user to whom a read receipt is directed.

**Property ID:** 0x402A

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.25

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptEmailAddr, ReadReceiptEmailAddress

## 2.872 PidTagReadReceiptEntryId

**Canonical name:** PidTagReadReceiptEntryId

**Description:** Contains an address book EntryID.

**Property ID:** 0x0046

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.26

**Alternate names:** PR\_READ\_RECEIPT\_ENTRYID, ptagReadReceiptEntryId

## 2.873 PidTagReadReceiptName

**Canonical name:** PidTagReadReceiptName

**Description:** Contains the display name for the end user to whom a read receipt is directed.

**Property ID:** 0x402B

**Data type:** PtypString, 0x001F

**Area:** Transport Envelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.27

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagReadReceiptDisplayName, ReadReceiptDisplayName

## 2.874 PidTagReadReceiptRequested

**Canonical name:** PidTagReadReceiptRequested

**Description:** Specifies whether the email sender requests a read receipt from all recipients when this email message is read or opened.

**Property ID:** 0x0029

**Data type:** PtypBoolean, 0x000B

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.29

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXODOC\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#)

**Alternate names:** PR\_READ\_RECEIPT\_REQUESTED, ptagReadReceiptRequested, <http://schemas.microsoft.com/exchange/readreceiptrequested>

## 2.875 PidTagReadReceiptSearchKey

**Canonical name:** PidTagReadReceiptSearchKey

**Description:** Contains an address book search key.

**Property ID:** 0x0053

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.28

**Alternate names:** PR\_READ\_RECEIPT\_SEARCH\_KEY, ptagReadReceiptSearchKey

## 2.876 PidTagReadReceiptSmtpAddress

**Canonical name:** PidTagReadReceiptSmtpAddress

**Description:** Contains the SMTP email address of the user to whom a read receipt is directed.

**Property ID:** 0x5D05

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.30

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientReadReceiptSmtpAddress

## 2.877 PidTagReceiptTime

**Canonical name:** PidTagReceiptTime

**Description:** Contains the sent time for a message disposition notification, as specified in [\[RFC3798\]](#).

**Property ID:** 0x002A

**Data type:** PtypTime, 0x0040

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.33

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_RECEIPT\_TIME, ptagReceiptTime

## 2.878 PidTagReceivedByAddressType

**Canonical name:** PidTagReceivedByAddressType

**Description:** Contains the email message receiver's email address type.

**Property ID:** 0x0075

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.36

**Alternate names:** PR\_RECEIVED\_BY\_ADDRTYPE, PR\_RECEIVED\_BY\_ADDRTYPE\_A, ptagReceivedByAddrType, PR\_RECEIVED\_BY\_ADDRTYPE\_W

## 2.879 PidTagReceivedByEmailAddress

**Canonical name:** PidTagReceivedByEmailAddress

**Description:** Contains the email message receiver's email address.

**Property ID:** 0x0076

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.37

**Alternate names:** PR\_RECEIVED\_BY\_EMAIL\_ADDRESS, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_A, PR\_RECEIVED\_BY\_EMAIL\_ADDRESS\_W

## 2.880 PidTagReceivedByEntryId

**Canonical name:** PidTagReceivedByEntryId

**Description:** Contains the address book EntryID of the mailbox receiving the Email object.

**Property ID:** 0x003F

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.38

**Alternate names:** PR\_RECEIVED\_BY\_ENTRYID



## 2.881 PidTagReceivedByName

**Canonical name:** PidTagReceivedByName

**Description:** Contains the email message receiver's display name.

**Property ID:** 0x0040

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.39

**Alternate names:** PR\_RECEIVED\_BY\_NAME, PR\_RECEIVED\_BY\_NAME\_A, PR\_RECEIVED\_BY\_NAME\_W

## 2.882 PidTagReceivedBySearchKey

**Canonical name:** PidTagReceivedBySearchKey

**Description:** Identifies an address book search key that contains a binary-comparable key that is used to identify correlated objects for a search.

**Property ID:** 0x0051

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.40

**Alternate names:** PR\_RECEIVED\_BY\_SEARCH\_KEY

## 2.883 PidTagReceivedBySmtptAddress

**Canonical name:** PidTagReceivedBySmtptAddress

**Description:** Contains the email message receiver's SMTP email address.

**Property ID:** 0x5D07

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.41

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientRcvdBySmtptAddress

## 2.884 PidTagReceivedRepresentingAddressType

**Canonical name:** PidTagReceivedRepresentingAddressType

**Description:** Contains the email address type for the end user represented by the receiving mailbox owner.

**Property ID:** 0x0077

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.23

**Alternate names:** PR\_RCVD\_REPRESENTING\_ADDRTYPE, PR\_RCVD\_REPRESENTING\_ADDRTYPE\_A, ptagRcvdRepresentingAddrType, PR\_RCVD\_REPRESENTING\_ADDRTYPE\_W

## 2.885 PidTagReceivedRepresentingEmailAddress

**Canonical name:** PidTagReceivedRepresentingEmailAddress

**Description:** Contains the email address for the end user represented by the receiving mailbox owner.

**Property ID:** 0x0078

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.24

**Alternate names:** PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS, PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_RCVD\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.886 PidTagReceivedRepresentingEntryId

**Canonical name:** PidTagReceivedRepresentingEntryId

**Description:** Contains an address book EntryID that identifies the end user represented by the receiving mailbox owner.

**Property ID:** 0x0043

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.25

**Alternate names:** PR\_RCVD\_REPRESENTING\_ENTRYID, ptagRcvdRepresentingEntryId

## 2.887 PidTagReceivedRepresentingName

**Canonical name:** PidTagReceivedRepresentingName

**Description:** Contains the display name for the end user represented by the receiving mailbox owner.

**Property ID:** 0x0044

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.26

**Alternate names:** PR\_RCVD\_REPRESENTING\_NAME, PR\_RCVD\_REPRESENTING\_NAME\_A, ptagRcvdRepresentingName, PR\_RCVD\_REPRESENTING\_NAME\_W

## 2.888 PidTagReceivedRepresentingSearchKey

**Canonical name:** PidTagReceivedRepresentingSearchKey

**Description:** Identifies an address book search key that contains a binary-comparable key of the end user represented by the receiving mailbox owner.

**Property ID:** 0x0052

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.27

**Alternate names:** PR\_RCVD\_REPRESENTING\_SEARCH\_KEY, ptagRcvdRepresentingSearchKey

## 2.889 PidTagReceivedRepresentingSmtpAddress

**Canonical name:** PidTagReceivedRepresentingSmtpAddress

**Description:** Contains the SMTP email address of the user represented by the receiving mailbox owner.

**Property ID:** 0x5D08

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.28

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagRecipientRcvdRepresentingSmtpAddress

## 2.890 PidTagRecipientDisplayName

**Canonical name:** PidTagRecipientDisplayName

**Description:** Specifies the display name of the recipient.

**Property ID:** 0x5FF6

**Data type:** PtypString, 0x001F

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.54

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_DISPLAY\_NAME, PR\_RECIPIENT\_DISPLAY\_NAME\_W

## 2.891 PidTagRecipientEntryId

**Canonical name:** PidTagRecipientEntryId

**Description:** Identifies an Address Book object that specifies the recipient.

**Property ID:** 0x5FF7

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.55

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ENTRYID, ptagRecipientEntryId

## 2.892 PidTagRecipientFlags

**Canonical name:** PidTagRecipientFlags

**Description:** Specifies a bit field that describes the recipient status.

**Property ID:** 0x5FFD

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_FLAGS

## 2.893 PidTagRecipientOrder

**Canonical name:** PidTagRecipientOrder

**Description:** Specifies the location of the current recipient in the **recipient table**.

**Property ID:** 0x5FDF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.40

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_ORDER, ptagRecipientOrder

## 2.894 PidTagRecipientProposed

**Canonical name:** PidTagRecipientProposed

**Description:** Indicates that the attendee proposed a new date and/or time.

**Property ID:** 0x5FE1

**Data type:** PtypBoolean, 0x000B

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.4

**Alternate names:** PR\_RECIPIENT\_PROPOSED, ptagRecipientProposed

## 2.895 PidTagRecipientProposedEndTime

**Canonical name:** PidTagRecipientProposedEndTime

**Description:** Indicates the meeting end time requested by the attendee in a counter proposal.

**Property ID:** 0x5FE4

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.6

**Alternate names:** PR\_RECIPIENT\_PROPOSEDENDTIME, ptagRecipientProposedEndTime

## 2.896 PidTagRecipientProposedStartTime

**Canonical name:** PidTagRecipientProposedStartTime

**Description:** Indicates the meeting start time requested by the attendee in a counter proposal.

**Property ID:** 0x5FE3

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.5

**Alternate names:** PR\_RECIPIENT\_PROPOSEDSTARTTIME, ptagRecipientProposedStartTime

## 2.897 PidTagRecipientReassignmentProhibited

**Canonical name:** PidTagRecipientReassignmentProhibited

**Description:** Specifies whether adding additional or different recipients is prohibited for the email message when forwarding the email message.

**Property ID:** 0x002B

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.42

**Alternate names:** PR\_RECIPIENT\_REASSIGNMENT\_PROHIBITED, ptagRecipientReassignmentProhibited

## 2.898 PidTagRecipientTrackStatus

**Canonical name:** PidTagRecipientTrackStatus

**Description:** Indicates the response status that is returned by the attendee.

**Property ID:** 0x5FFF

**Data type:** PtypInteger32, 0x0003

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.2

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS, ptagRecipientTrackStatus

## 2.899 PidTagRecipientTrackStatusTime

**Canonical name:** PidTagRecipientTrackStatusTime

**Description:** Indicates the date and time at which the attendee responded.

**Property ID:** 0x5FFB

**Data type:** PtypTime, 0x0040

**Area:** TransportRecipient

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.4.10.3

**Consuming reference:** [\[MS-OXCICAL\]](#)

**Alternate names:** PR\_RECIPIENT\_TRACKSTATUS\_TIME, ptagRecipientTrackStatusTime

## 2.900 PidTagRecipientType

**Canonical name:** PidTagRecipientType

**Description:** Represents the recipient type of a recipient on the message.

**Property ID:** 0x0C15

**Data type:** PtypInteger32, 0x0003

**Area:** MapiRecipient

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.1

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOSRCH\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_RECIPIENT\_TYPE, ptagRecipientType

## 2.901 PidTagRecordKey

**Canonical name:** PidTagRecordKey

**Description:** Contains a unique binary-comparable identifier for a specific object.

**Property ID:** 0x0FF9

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.8

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#)

**Alternate names:** PR\_RECORD\_KEY, ptagRecordKey

## 2.902 PidTagReferredByName

**Canonical name:** PidTagReferredByName

**Description:** Contains the name of the mail user's referral.

**Property ID:** 0x3A47

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.21

**Alternate names:** PR\_REferred\_BY\_NAME, PR\_REferred\_BY\_NAME\_A, PR\_REferred\_BY\_NAME\_W

## 2.903 PidTagRemindersOnlineEntryId

**Canonical name:** PidTagRemindersOnlineEntryId

**Description:** Contains an EntryID for the Reminders folder.

**Property ID:** 0x36D5

**Data type:** PtypBinary, 0x0102

**Area:** MapiContainer

**Defining reference:** [\[MS-OXOSFLD\]](#) section 2.2.3

**Alternate names:** PR\_REM\_ONLINE\_ENTRYID, ptagRemOnlineEntryId

## 2.904 PidTagRemoteMessageTransferAgent

**Canonical name:** PidTagRemoteMessageTransferAgent

**Description:** Contains the value of the Remote-MTA field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C21

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.34

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_DSN\_REMOTE\_MTA, ptagDsnRemoteMta

## 2.905 PidTagRenderingPosition

**Canonical name:** PidTagRenderingPosition

**Description:** Represents an offset, in rendered characters, to use when rendering an attachment within the main message text.

**Property ID:** 0x370B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiAttachment

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.2.16

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_RENDERING\_POSITION, ptagRenderingPosition

## 2.906 PidTagReplyRecipientEntries

**Canonical name:** PidTagReplyRecipientEntries

**Description:** Identifies a **FlatEntryList** structure ([\[MS-OXCDATA\]](#) section 2.3.3) of address book EntryIDs for recipients that are to receive a reply.

**Property ID:** 0x004F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.43

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_ENTRIES, ptagReplyRecipientEntries, <http://schemas.microsoft.com/exchange/reply-to-base64>

## 2.907 PidTagReplyRecipientNames

**Canonical name:** PidTagReplyRecipientNames

**Description:** Contains a list of display names for recipients that are to receive a reply.

**Property ID:** 0x0050

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.44

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_REPLY\_RECIPIENT\_NAMES, PR\_REPLY\_RECIPIENT\_NAMES\_A, ptagReplyRecipientNames, PR\_REPLY\_RECIPIENT\_NAMES\_W

## 2.908 PidTagReplyRequested

**Canonical name:** PidTagReplyRequested

**Description:** Indicates whether a reply is requested to a Message object.

**Property ID:** 0x0C17

**Data type:** PtypBoolean, 0x000B



**Area:** MapiRecipient

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.45

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [MS-OXOMSG], [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_REQUESTED, ptagReplyRequested

## 2.909 PidTagReplyTemplateId

**Canonical name:** PidTagReplyTemplateId

**Description:** Contains the value of the GUID that points to a Reply template.

**Property ID:** 0x65C2

**Data type:** PtypBinary, 0x0102

**Area:** Rules

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.2

**Alternate names:** PR\_REPLY\_TEMPLATE\_ID, ptagReplyTemplateId

## 2.910 PidTagReplyTime

**Canonical name:** PidTagReplyTime

**Description:** Specifies the time, in UTC, that the sender has designated for an associated work item to be due.

**Property ID:** 0x0030

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.3.1

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_REPLY\_TIME, urn:schemas:httpmail:reply-by, <http://schemas.microsoft.com/exchange/reply-by-iso>

## 2.911 PidTagReportDisposition

**Canonical name:** PidTagReportDisposition

**Description:** Contains a string indicating whether the original message was displayed to the user or deleted (report messages only).

**Property ID:** 0x0080

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.34

**Alternate names:** PR\_REPORT\_DISPOSITION\_W

## 2.912 PidTagReportDispositionMode

**Canonical name:** PidTagReportDispositionMode

**Description:** Contains a description of the action that a client has performed on behalf of a user (report messages only).

**Property ID:** 0x0081

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.35

**Alternate names:** PR\_REPORT\_DISPOSITION\_MODE\_W

## 2.913 PidTagReportEntryId

**Canonical name:** PidTagReportEntryId

**Description:** Specifies an **entry ID** that identifies the application that generated a report message.

**Property ID:** 0x0045

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.45

**Alternate names:** PR\_REPORT\_ENTRYID, ptagReportEntryId

## 2.914 PidTagReportingMessageTransferAgent

**Canonical name:** PidTagReportingMessageTransferAgent

**Description:** Contains the value of the Reporting-MTA field for a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x6820

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.35

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagDsnReportingMta

## 2.915 PidTagReportName

**Canonical name:** PidTagReportName

**Description:** Contains the display name for the entity (usually a server agent) that generated the report message.

**Property ID:** 0x003A

**Data type:** PtypString, 0x001F

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.20

**Alternate names:** PR\_REPORT\_NAME, PR\_REPORT\_NAME\_A, PR\_REPORT\_NAME\_W

## 2.916 PidTagReportSearchKey

**Canonical name:** PidTagReportSearchKey

**Description:** Contains an address book search key representing the entity (usually a server agent) that generated the report message.

**Property ID:** 0x0054

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.21

**Alternate names:** PR\_REPORT\_SEARCH\_KEY, ptagReportSearchKey

## 2.917 PidTagReportTag

**Canonical name:** PidTagReportTag

**Description:** Contains the data that is used to correlate the report and the original message.

**Property ID:** 0x0031

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.22

**Alternate names:** PR\_REPORT\_TAG, ptagReportTag

## 2.918 PidTagReportText

**Canonical name:** PidTagReportText

**Description:** Contains the optional text for a report message.

**Property ID:** 0x1001

**Data type:** PtypString, 0x001F

**Area:** MapiMessage

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.23

**Alternate names:** PR\_REPORT\_TEXT, PR\_REPORT\_TEXT\_A, ptagReportText, PR\_REPORT\_TEXT\_W

## 2.919 PidTagReportTime

**Canonical name:** PidTagReportTime

**Description:** Indicates the last time that the contact list that is controlled by the **PidTagJunkIncludeContacts** property (section [2.749](#)) was updated.

**Property ID:** 0x0032

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXCSPAM\]](#) section 2.2.2.6

**Alternate names:** PR\_REPORT\_TIME, ptagReportTime, <http://schemas.microsoft.com/exchange/reporttime>

## 2.920 PidTagResolveMethod

**Canonical name:** PidTagResolveMethod

**Description:** Specifies how to resolve any conflicts with the message.

**Property ID:** 0x3FE7

**Data type:** PtypInteger32, 0x0003

**Area:** MapiStatus

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.4.1

**Alternate names:** PR\_RESOLVE\_METHOD, ptagResolveMethod

## 2.921 PidTagResponseRequested

**Canonical name:** PidTagResponseRequested

**Description:** Indicates whether a response is requested to a Message object.

**Property ID:** 0x0063

**Data type:** PtypBoolean, 0x000B

**Area:** MapiEnvelope Property set

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.46

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOFLAG\]](#), [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_RESPONSE\_REQUESTED, urn:schemas:calendar:responserequested, [http://schemas.microsoft.com/mapi/response\\_requested](http://schemas.microsoft.com/mapi/response_requested)

## 2.922 PidTagResponsibility

**Canonical name:** PidTagResponsibility

**Description:** Specifies whether another mail agent has ensured that the message will be delivered.

**Property ID:** 0x0E0F

**Data type:** PtypBoolean, 0x000B

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.37

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_RESPONSIBILITY, ptagResponsibility

### 2.923 PidTagRetentionDate

**Canonical name:** PidTagRetentionDate

**Description:** Specifies the date, in UTC, after which a Message object is expired by the server.

**Property ID:** 0x301C

**Data type:** PtypTime, 0x0040

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.5

**Alternate names:** PR\_RETENTION\_DATE, ptagRetentionDate

### 2.924 PidTagRetentionFlags

**Canonical name:** PidTagRetentionFlags

**Description:** Contains flags that specify the status or nature of an item's retention tag or archive tag.

**Property ID:** 0x301D

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.6

**Alternate names:** PR\_RETENTION\_FLAGS, ptagRetentionFlags

### 2.925 PidTagRetentionPeriod

**Canonical name:** PidTagRetentionPeriod

**Description:** Specifies the number of days that a Message object can remain unarchived.

**Property ID:** 0x301A

**Data type:** PtypInteger32, 0x0003

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.3

**Alternate names:** PR\_RETENTION\_PERIOD, ptagRetentionPeriod

## 2.926 PidTagRights

**Canonical name:** PidTagRights

**Description:** Specifies a user's folder permissions.

**Property ID:** 0x6639

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeFolder

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.8

**Consuming reference:** [\[MS-OXCPERM\]](#)

**Alternate names:** PR\_RIGHTS, ptagRights

## 2.927 PidTagRoamingDatatypes

**Canonical name:** PidTagRoamingDatatypes

**Description:** Contains a bitmask that indicates which stream properties exist on the message.

**Property ID:** 0x7C06

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.1

**Alternate names:** PR\_ROAMING\_DATATYPES

## 2.928 PidTagRoamingDictionary

**Canonical name:** PidTagRoamingDictionary

**Description:** Contains a dictionary stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.1.

**Property ID:** 0x7C07

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.2.2

**Alternate names:** PR\_ROAMING\_DICTIONARY

## 2.929 PidTagRoamingXmlStream

**Canonical name:** PidTagRoamingXmlStream

**Description:** Contains an XML stream, as specified in [\[MS-OXOCFG\]](#) section 2.2.5.2.

**Property ID:** 0x7C08

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [MS-OXOCFG] section 2.2.2.3

**Alternate names:** PR\_ROAMING\_XMLSTREAM

## 2.930 PidTagRowid

**Canonical name:** PidTagRowid

**Description:** Contains a unique identifier for a recipient in a message's recipient table.

**Property ID:** 0x3000

**Data type:** PtypInteger32, 0x0003

**Area:** MapiCommon

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.38

**Consuming reference:** [\[MS-OXCFXICS\]](#)

**Alternate names:** PR\_ROWID, ptagRowId

## 2.931 PidTagRowType

**Canonical name:** PidTagRowType

**Description:** Identifies the type of the row.

**Property ID:** 0x0FF5

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCTABL\]](#) section 2.2.1.3

**Alternate names:** PR\_ROW\_TYPE, ptagRowType

## 2.932 PidTagRtfCompressed

**Canonical name:** PidTagRtfCompressed

**Description:** Contains message body text in compressed **RTF** format.

**Property ID:** 0x1009

**Data type:** PtypBinary, 0x0102

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.4

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFCP\]](#), [\[MS-OXRTFEX\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_RTF\_COMPRESSED, ptagRTFCompressed

### 2.933 PidTagRtfInSync

**Canonical name:** PidTagRtfInSync

**Description:** Indicates whether the **PidTagBody** property (section [2.609](#)) and the **PidTagRtfCompressed** property (section [2.932](#)) contain the same text (ignoring formatting).

**Property ID:** 0x0E1F

**Data type:** PtypBoolean, 0x000B

**Area:** Email

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.56.5

**Consuming references:** [\[MS-OXBBODY\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXORMMS\]](#), [\[MS-OXRTFEX\]](#)

**Alternate names:** PR\_RTF\_IN\_SYNC, ptagRTFInSync

### 2.934 PidTagRuleActionNumber

**Canonical name:** PidTagRuleActionNumber

**Description:** Contains the index of a rule action that failed.

**Property ID:** 0x6650

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.4

**Alternate names:** PR\_RULE\_ACTION\_NUMBER, ptagRuleActionNumber

### 2.935 PidTagRuleActions

**Canonical name:** PidTagRuleActions

**Description:** Contains the set of actions associated with the rule.

**Property ID:** 0x6680

**Data type:** PtypRuleAction, 0x00FE

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.10

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_ACTIONS, ptagRuleActions

### 2.936 PidTagRuleActionType

**Canonical name:** PidTagRuleActionType

**Description:** Contains the **ActionType** field ([\[MS-OXORULE\]](#) section 2.2.5.1) of a rule that failed.

**Property ID:** 0x6649



**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [MS-OXORULE] section 2.2.7.3

**Alternate names:** PR\_RULE\_ACTION\_TYPE, ptagRuleActionType

### 2.937 PidTagRuleCondition

**Canonical name:** PidTagRuleCondition

**Description:** Defines the conditions under which a rule action is to be executed.

**Property ID:** 0x6679

**Data type:** PtypRestriction, 0x00FD

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.9

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_CONDITION, ptagRuleCondition

### 2.938 PidTagRuleError

**Canonical name:** PidTagRuleError

**Description:** Contains the error code that indicates the cause of an error encountered during the execution of the rule.

**Property ID:** 0x6648

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.7.2

**Alternate names:** PR\_RULE\_ERROR, ptagRuleError

### 2.939 PidTagRuleFolderEntryId

**Canonical name:** PidTagRuleFolderEntryId

**Description:** Contains the EntryID of the folder where the rule that triggered the generation of a DAM is stored.

**Property ID:** 0x6651

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageReadOnly

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.5

**Alternate names:** PR\_RULE\_FOLDER\_ENTRYID, ptagRuleFolderEntryId

## 2.940 PidTagRuleId

**Canonical name:** PidTagRuleId

**Description:** Specifies a unique identifier that is generated by the messaging server for each rule when the rule is first created.

**Property ID:** 0x6674

**Data type:** PtypInteger64, 0x0014

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.1

**Alternate names:** PR\_RULE\_ID, ptagRuleId

## 2.941 PidTagRuleIds

**Canonical name:** PidTagRuleIds

**Description:** Contains a buffer that is obtained by concatenating the **PidTagRuleId** property (section [2.940](#)) values from all of the rules contributing actions that are contained in the **PidTagClientActions** property (section [2.625](#)).

**Property ID:** 0x6675

**Data type:** PtypBinary, 0x0102

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.6.7

**Alternate names:** PR\_RULE\_IDS, ptagRuleIds

## 2.942 PidTagRuleLevel

**Canonical name:** PidTagRuleLevel

**Description:** Contains 0x00000000. This property is not used.

**Property ID:** 0x6683

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.6

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_LEVEL, ptagRuleLevel

## 2.943 PidTagRuleMessageLevel

**Canonical name:** PidTagRuleMessageLevel

**Description:** Contains 0x00000000. Set on the FAI message.

**Property ID:** 0x65ED

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.6

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_LEVEL, ptagRuleMsgLevel

## 2.944 PidTagRuleMessageName

**Canonical name:** PidTagRuleMessageName

**Description:** Specifies the name of the rule. Set on the FAI message.

**Property ID:** 0x65EC

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.1

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** ptagRuleMsgName

## 2.945 PidTagRuleMessageProvider

**Canonical name:** PidTagRuleMessageProvider

**Description:** Identifies the client application that owns the rule. Set on the FAI message.

**Property ID:** 0x65EB

**Data type:** PtypString, 0x001F

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.7

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** ptagRuleMsgProvider

## 2.946 PidTagRuleMessageProviderData

**Canonical name:** PidTagRuleMessageProviderData

**Description:** Contains opaque data set by the client for the exclusive use of the client. Set on the FAI message.

**Property ID:** 0x65EE

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.8

**Alternate names:** PR\_RULE\_MSG\_PROVIDER\_DATA, ptagRuleMsgProviderData

## 2.947 PidTagRuleMessageSequence

**Canonical name:** PidTagRuleMessageSequence

**Description:** Contains a value used to determine the order in which rules are evaluated and executed. Set on the FAI message.

**Property ID:** 0x65F3

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.3

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_SEQUENCE, ptagRuleMsgSequence

## 2.948 PidTagRuleMessageState

**Canonical name:** PidTagRuleMessageState

**Description:** Contains flags that specify the state of the rule. Set on the FAI message.

**Property ID:** 0x65E9

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.4

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_STATE, ptagRuleMsgState

## 2.949 PidTagRuleMessageUserFlags

**Canonical name:** PidTagRuleMessageUserFlags

**Description:** Contains an opaque property that the client sets for the exclusive use of the client. Set on the FAI message.

**Property ID:** 0x65EA

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeNonTransmittableReserved

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.4.1.5

**Consuming reference:** [\[MS-OXCSPAM\]](#)

**Alternate names:** PR\_RULE\_MSG\_USER\_FLAGS, ptagRuleMsgUserFlags

## 2.950 PidTagRuleName

**Canonical name:** PidTagRuleName

**Description:** Specifies the name of the rule.

**Property ID:** 0x6682

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.4

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_NAME, PR\_RULE\_NAME\_A, ptagRuleName, PR\_RULE\_NAME\_W

## 2.951 PidTagRuleProvider

**Canonical name:** PidTagRuleProvider

**Description:** A string identifying the client application that owns a rule.

**Property ID:** 0x6681

**Data type:** PtypString, 0x001F

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.5

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_PROVIDER, ptagRuleProvider, PR\_RULE\_PROVIDER\_W

## 2.952 PidTagRuleProviderData

**Canonical name:** PidTagRuleProviderData

**Description:** Contains opaque data set by the client for the exclusive use of the client.

**Property ID:** 0x6684

**Data type:** PtypBinary, 0x0102

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.8

**Alternate names:** PR\_RULE\_PROVIDER\_DATA, ptagRuleProviderData

## 2.953 PidTagRuleSequence

**Canonical name:** PidTagRuleSequence

**Description:** Contains a value used to determine the order in which rules are evaluated and executed.

**Property ID:** 0x6676

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.2

**Consuming references:** [\[MS-OXCPRPT\]](#), [\[MS-OXCSTOR\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_SEQUENCE, ptagRuleSequence

## 2.954 PidTagRuleState

**Canonical name:** PidTagRuleState

**Description:** Contains flags that specify the state of the rule.

**Property ID:** 0x6677

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.3

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_STATE, ptagRuleState

## 2.955 PidTagRuleUserFlags

**Canonical name:** PidTagRuleUserFlags

**Description:** Contains an opaque property that the client sets for the exclusive use of the client.

**Property ID:** 0x6678

**Data type:** PtypInteger32, 0x0003

**Area:** Server-Side Rules Properties

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.1.3.1.7

**Consuming reference:** [\[MS-OXODLGT\]](#)

**Alternate names:** PR\_RULE\_USER\_FLAGS, ptagRuleUserFlags

## 2.956 PidTagRwRulesStream

**Canonical name:** PidTagRwRulesStream

**Description:** Contains additional rule data about the **Rule FAI message**.

**Property ID:** 0x6802

**Data type:** PtypBinary, 0x0102

**Area:** Message Class Defined Transmittable

**Defining reference:** [\[MS-OXORULE\]](#) section 2.2.9.3

**Alternate names:** PR\_RW\_RULES\_STREAM

## 2.957 PidTagScheduleInfoAppointmentTombstone

**Canonical name:** PidTagScheduleInfoAppointmentTombstone

**Description:** Contains a list of tombstones, where each tombstone represents a Meeting object that has been declined.

**Property ID:** 0x686A

**Data type:** PtypBinary, 0x0102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.5

**Alternate names:** PR\_SCHDINFO\_APPT\_TOMBSTONE

## 2.958 PidTagScheduleInfoAutoAcceptAppointments

**Canonical name:** PidTagScheduleInfoAutoAcceptAppointments

**Description:** Indicates whether a client or server is to automatically respond to all meeting requests for the attendee or resource.

**Property ID:** 0x686D

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.2

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_AUTO\_ACCEPT\_APPTS

## 2.959 PidTagScheduleInfoDelegateEntryIds

**Canonical name:** PidTagScheduleInfoDelegateEntryIds

**Description:** Specifies the EntryIDs of the delegates.

**Property ID:** 0x6845

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.5

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_ENTRYIDS

## 2.960 PidTagScheduleInfoDelegateNames

**Canonical name:** PidTagScheduleInfoDelegateNames

**Description:** Specifies the names of the delegates.

**Property ID:** 0x6844

**Data type:** PtypMultipleString, 0x101F

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.3

**Consuming reference:** [\[MS-OXMSG\]](#)

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES

### **2.961 PidTagScheduleInfoDelegateNamesW**

**Canonical name:** PidTagScheduleInfoDelegateNamesW

**Description:** Specifies the names of the delegates in Unicode.

**Property ID:** 0x684A

**Data type:** **PtypMultipleString**, 0x101F

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.4

**Alternate names:** PR\_SCHDINFO\_DELEGATE\_NAMES\_W, ptagDelegateNames

### **2.962 PidTagScheduleInfoDelegatorWantsCopy**

**Canonical name:** PidTagScheduleInfoDelegatorWantsCopy

**Description:** Indicates whether the delegator wants to receive copies of the meeting-related objects that are sent to the delegate.

**Property ID:** 0x6842

**Data type:** **PtypBoolean**, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.1

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_COPY

### **2.963 PidTagScheduleInfoDelegatorWantsInfo**

**Canonical name:** PidTagScheduleInfoDelegatorWantsInfo

**Description:** Indicates whether the delegator wants to receive informational updates.

**Property ID:** 0x684B

**Data type:** **PtypBoolean**, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.2

**Consuming references:** [\[MS-OXOCAL\]](#), [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_BOSS\_WANTS\_INFO



## 2.964 PidTagScheduleInfoDisallowOverlappingAppts

**Canonical name:** PidTagScheduleInfoDisallowOverlappingAppts

**Description:** Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that overlap with previously scheduled events.

**Property ID:** 0x686F

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.4

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_OVERLAPPING\_APPTS

## 2.965 PidTagScheduleInfoDisallowRecurringAppts

**Canonical name:** PidTagScheduleInfoDisallowRecurringAppts

**Description:** Indicates whether a client or server, when automatically responding to meeting requests, is to decline Meeting Request objects that represent a recurring series.

**Property ID:** 0x686E

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.12.3

**Consuming reference:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DISALLOW\_RECURRING\_APPTS

## 2.966 PidTagScheduleInfoDontMailDelegates

**Canonical name:** PidTagScheduleInfoDontMailDelegates

**Description:** Contains a value set to TRUE by the client, regardless of user input.

**Property ID:** 0x6843

**Data type:** PtypBoolean, 0x000B

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXODLGT\]](#) section 2.2.2.2.7

**Consuming references:** [\[MS-OXOPFFB\]](#)

**Alternate names:** PR\_SCHDINFO\_DONT\_MAIL\_DELEGATES

## 2.967 PidTagScheduleInfoFreeBusy

**Canonical name:** PidTagScheduleInfoFreeBusy

**Description:** This property is deprecated and is not to be used.

**Property ID:** 0x686C

**Data type:** PtypBinary, 0x0102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.3

**Alternate names:** PR\_SCHDINFO\_FREEBUSY

## **2.968 PidTagScheduleInfoFreeBusyAway**

**Canonical name:** PidTagScheduleInfoFreeBusyAway

**Description:** Specifies the times for which the free/busy status is set a value of OOF.

**Property ID:** 0x6856

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.6

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_OOF

## **2.969 PidTagScheduleInfoFreeBusyBusy**

**Canonical name:** PidTagScheduleInfoFreeBusyBusy

**Description:** Specifies the blocks of time for which the free/busy status is set to a value of **busy**.

**Property ID:** 0x6854

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.4

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_BUSY

## **2.970 PidTagScheduleInfoFreeBusyMerged**

**Canonical name:** PidTagScheduleInfoFreeBusyMerged

**Description:** Specifies the blocks for which free/busy data of type **busy** or OOF is present in the free/busy message.

**Property ID:** 0x6850

**Data type:** PtypMultipleBinary, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.8

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_MERGED

## 2.971 PidTagScheduleInfoFreeBusyTentative

**Canonical name:** PidTagScheduleInfoFreeBusyTentative

**Description:** Specifies the blocks of times for which the free/busy status is set to a value of **tentative**.

**Property ID:** 0x6852

**Data type:** **PtypMultipleBinary**, 0x1102

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.2

**Alternate names:** PR\_SCHDINFO\_FREEBUSY\_TENTATIVE

## 2.972 PidTagScheduleInfoMonthsAway

**Canonical name:** PidTagScheduleInfoMonthsAway

**Description:** Specifies the months for which free/busy data of type OOF is present in the free/busy message.

**Property ID:** 0x6855

**Data type:** **PtypMultipleInteger32**, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.5

**Alternate names:** PR\_SCHDINFO\_MONTHS\_OOF

## 2.973 PidTagScheduleInfoMonthsBusy

**Canonical name:** PidTagScheduleInfoMonthsBusy

**Description:** Specifies the months for which free/busy data of type **busy** is present in the free/busy message.

**Property ID:** 0x6853

**Data type:** **PtypMultipleInteger32**, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.3

**Consuming reference:** [\[MS-OXMSG\]](#)

**Alternate names:** PR\_SCHDINFO\_MONTHS\_BUSY

## 2.974 PidTagScheduleInfoMonthsMerged

**Canonical name:** PidTagScheduleInfoMonthsMerged

**Description:** Specifies the months for which free/busy data of type **busy** or OOF is present in the free/busy message.

**Property ID:** 0x684F

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.7

**Alternate names:** PR\_SCHDINFO\_MONTHS\_MERGED

## 2.975 PidTagScheduleInfoMonthsTentative

**Canonical name:** PidTagScheduleInfoMonthsTentative

**Description:** Specifies the months for which free/busy data of type **tentative** is present in the free/busy message.

**Property ID:** 0x6851

**Data type:** PtypMultipleInteger32, 0x1003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.2.1

**Alternate names:** PR\_SCHDINFO\_MONTHS\_TENTATIVE

## 2.976 PidTagScheduleInfoResourceType

**Canonical name:** PidTagScheduleInfoResourceType

**Description:** Set to 0x00000000 when sending and is ignored on receipt.

**Property ID:** 0x6841

**Data type:** PtypInteger32, 0x0003

**Area:** Free/Busy Properties

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.1.4.2

**Alternate names:** PR\_SCHDINFO\_RESOURCE\_TYPE

## 2.977 PidTagSchedulePlusFreeBusyEntryId

**Canonical name:** PidTagSchedulePlusFreeBusyEntryId

**Description:** Contains the EntryID of the folder named "SCHEDULE+ FREE BUSY" under the non-IPM subtree of the public folder message store.

**Property ID:** 0x6622

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageStore

**Defining reference:** [\[MS-OXOPFFB\]](#) section 2.2.2.2

**Alternate names:** PR\_SPLUS\_FREE\_BUSY\_ENTRYID

## 2.978 PidTagScriptData

**Canonical name:** PidTagScriptData

**Description:** Contains a series of instructions that can be executed to format an address and the data that is needed to execute those instructions.

**Property ID:** 0x0004

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.2

**Alternate names:** PR\_EMS\_SCRIPT\_BLOB

## 2.979 PidTagSearchFolderDefinition

**Canonical name:** PidTagSearchFolderDefinition

**Description:** Specifies the search criteria and search options.

**Property ID:** 0x6845

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.8

**Alternate names:** PR\_WB\_SF\_DEFINITION

## 2.980 PidTagSearchFolderEfpFlags

**Canonical name:** PidTagSearchFolderEfpFlags

**Description:** Specifies flags that control how a folder is displayed.

**Property ID:** 0x6848

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.7

**Alternate names:** PR\_WB\_SF\_EFP\_FLAGS

## 2.981 PidTagSearchFolderExpiration

**Canonical name:** PidTagSearchFolderExpiration

**Description:** Contains the time, in UTC, at which the search folder container will be stale and has to be updated or recreated.

**Property ID:** 0x683A

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.5

**Alternate names:** PR\_WB\_SF\_EXPIRATION

## 2.982 PidTagSearchFolderId

**Canonical name:** PidTagSearchFolderId

**Description:** Contains a GUID that identifies the search folder.

**Property ID:** 0x6842

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.1

**Consuming reference:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_WB\_SF\_ID

## 2.983 PidTagSearchFolderLastUsed

**Canonical name:** PidTagSearchFolderLastUsed

**Description:** Contains the last time, in UTC, that the folder was accessed.

**Property ID:** 0x6834

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.4

**Alternate names:** PR\_WB\_SF\_LAST\_USED

## 2.984 PidTagSearchFolderRecreateInfo

**Canonical name:** PidTagSearchFolderRecreateInfo

**Description:** This property is not to be used.

**Property ID:** 0x6844

**Data type:** PtypBinary, 0x0102

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.9

**Alternate names:** PR\_WB\_SF\_RECREATE\_INFO

## 2.985 PidTagSearchFolderStorageType

**Canonical name:** PidTagSearchFolderStorageType

**Description:** Contains flags that specify the binary large object (BLOB) data that appears in the **PidTagSearchFolderDefinition** (section [2.979](#)) property.

**Property ID:** 0x6846

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.6

**Alternate names:** PR\_WB\_SF\_STORAGE\_TYPE

## 2.986 PidTagSearchFolderTag

**Canonical name:** PidTagSearchFolderTag

**Description:** Contains the value of the **SearchFolderTag** sub-property of the **PidTagExtendedFolderFlags** (section [2.682](#)) property of the search folder container.

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.3

**Alternate names:** PR\_WB\_SF\_TAG

## 2.987 PidTagSearchFolderTemplateId

**Canonical name:** PidTagSearchFolderTemplateId

**Description:** Contains the ID of the template that is being used for the search.

**Property ID:** 0x6841

**Data type:** PtypInteger32, 0x0003

**Area:** Search

**Defining reference:** [\[MS-OXOSRCH\]](#) section 2.2.1.2.2

**Alternate names:** PR\_WB\_SF\_TEMPLATE\_ID

## 2.988 PidTagSearchKey

**Canonical name:** PidTagSearchKey

**Description:** Contains a unique binary-comparable key that identifies an object for a search.

**Property ID:** 0x300B

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCPRPT\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFOLD\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOABK\]](#), [\[MS-OXOJRN\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORULE\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SEARCH\_KEY, ptagSearchKey

## 2.989 PidTagSecurityDescriptorAsXml

**Canonical name:** PidTagSecurityDescriptorAsXml

**Description:** Contains security attributes in XML.

**Property ID:** 0x0E6A

**Data type:** PtypString, 0x001F

**Area:** Access Control Properties

**Defining reference:** [\[MS-XWDVSEC\]](#) section 2.2.2

**Consuming reference:** [\[MS-OXCPERM\]](#)

**Alternate names:** PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML,  
PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_A, PR\_NT\_SECURITY\_DESCRIPTOR\_AS\_XML\_W,  
<http://schemas.microsoft.com/exchange/security/descriptor>

## 2.990 PidTagSelectable

**Canonical name:** PidTagSelectable

**Description:** This property is not set and, if set, is ignored.

**Property ID:** 0x3609

**Data type:** PtypBoolean, 0x000B

**Area:** AB Container

**Defining reference:** [\[MS-EXOABKT\]](#) section 2.2.1

**Alternate names:** PR\_SELECTABLE

## 2.991 PidTagSenderAddressType

**Canonical name:** PidTagSenderAddressType

**Description:** Contains the email address type of the sending mailbox owner.

**Property ID:** 0x0C1E

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.48

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** PR\_SENDER\_ADDRTYPE, PR\_SENDER\_ADDRTYPE\_A, ptagSenderAddrType,  
PR\_SENDER\_ADDRTYPE\_W



## 2.992 PidTagSenderEmailAddress

**Canonical name:** PidTagSenderEmailAddress

**Description:** Contains the email address of the sending mailbox owner.

**Property ID:** 0x0C1F

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.49

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_EMAIL\_ADDRESS, PR\_SENDER\_EMAIL\_ADDRESS\_A, PR\_SENDER\_EMAIL\_ADDRESS\_W

## 2.993 PidTagSenderEntryId

**Canonical name:** PidTagSenderEntryId

**Description:** Identifies an address book EntryID that contains the address book EntryID of the sending mailbox owner.

**Property ID:** 0x0C19

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.50

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_ENTRYID, ptagSenderEntryId

## 2.994 PidTagSenderIdStatus

**Canonical name:** PidTagSenderIdStatus

**Description:** Reports the results of a Sender-ID check.

**Property ID:** 0x4079

**Data type:** PtypInteger32, 0x0003

**Area:** Secure Messaging Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.80

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_SENDER\_ID\_STATUS

## 2.995 PidTagSenderName

**Canonical name:** PidTagSenderName

**Description:** Contains the display name of the sending mailbox owner.

**Property ID:** 0x0C1A

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.51

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENDER\_NAME, PR\_SENDER\_NAME\_A, ptagSenderName, PR\_SENDER\_NAME\_W, urn:schemas:httpmail:sendername, http://schemas.microsoft.com/exchange/sender-name-utf8

## 2.996 PidTagSenderSearchKey

**Canonical name:** PidTagSenderSearchKey

**Description:** Identifies an address book search key.

**Property ID:** 0x0C1D

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.52

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#)

**Alternate names:** PR\_SENDER\_SEARCH\_KEY, ptagSenderSearchKey

## 2.997 PidTagSenderSmtpAddress

**Canonical name:** PidTagSenderSmtpAddress

**Description:** Contains the SMTP email address format of the e-mail address of the sending mailbox owner.

**Property ID:** 0x5D01

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.55

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** SenderSmtpAddress, ptagSenderSmtpAddress

## 2.998 PidTagSenderTelephoneNumber

**Canonical name:** PidTagSenderTelephoneNumber

**Description:** Contains the telephone number of the caller associated with a voice mail message.

**Property ID:** 0x6802

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.1

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaSenderTelephoneNumber

## 2.999 PidTagSendInternetEncoding

**Canonical name:** PidTagSendInternetEncoding

**Description:** Contains a bitmask of message encoding preferences for email sent to an email-enabled entity that is represented by this Address Book object.

**Property ID:** 0x3A71

**Data type:** PtypInteger32, 0x0003

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.19

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_INTERNET\_ENCODING, ptagSendInternetEncoding

## 2.1000 PidTagSendRichInfo

**Canonical name:** PidTagSendRichInfo

**Description:** Indicates whether the email-enabled entity represented by the Address Book object can receive all message content, including Rich Text Format (RTF) and other embedded objects.

**Property ID:** 0x3A40

**Data type:** PtypBoolean, 0x000B

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.18

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOMSG\]](#)

**Alternate names:** PR\_SEND\_RICH\_INFO, ptagSendRichInfo

## 2.1001 PidTagSensitivity

**Canonical name:** PidTagSensitivity

**Description:** Indicates the sender's assessment of the sensitivity of the Message object.

**Property ID:** 0x0036

**Data type:** **PtypInteger32**, 0x0003

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.13

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCICAL\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXVCARD\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#), [\[MS-OXOJRNLI\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORMMS\]](#)

**Alternate names:** PR\_SENSITIVITY, ptagSensitivity,  
<http://schemas.microsoft.com/exchange/sensitivity-long>,  
<http://schemas.microsoft.com/exchange/sensitivity>

## 2.1002 PidTagSentMailSvrEID

**Canonical name:** PidTagSentMailSvrEID

**Description:** Contains an EntryID that represents the **Sent Items folder** for the message.

**Property ID:** 0x6740

**Data type:** **PtypServerId**, 0x00FB

**Area:** ProviderDefinedNonTransmittable

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.3.10

**Consuming reference:** [\[MS-OXCSTOR\]](#)

**Alternate names:** ptagSentMailSvrEID

## 2.1003 PidTagSentRepresentingAddressType

**Canonical name:** PidTagSentRepresentingAddressType

**Description:** Contains an email address type.

**Property ID:** 0x0064

**Data type:** **PtypString**, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.54

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ADDRTYPE, PR\_SENT\_REPRESENTING\_ADDRTYPE\_A,  
ptagSentRepresentingAddrType, PR\_SENT\_REPRESENTING\_ADDRTYPE\_W

## 2.1004 PidTagSentRepresentingEmailAddress

**Canonical name:** PidTagSentRepresentingEmailAddress

**Description:** Contains an email address for the end user who is represented by the sending mailbox owner.

**Property ID:** 0x0065

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.55

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_A, PR\_SENT\_REPRESENTING\_EMAIL\_ADDRESS\_W

## 2.1005 PidTagSentRepresentingEntryId

**Canonical name:** PidTagSentRepresentingEntryId

**Description:** Contains the identifier of the end user who is represented by the sending mailbox owner.

**Property ID:** 0x0041

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.56

**Consuming references:** [\[MS-OXCADATA\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_ENTRYID, ptagSentRepresentingEntryId

## 2.1006 PidTagSentRepresentingFlags

**Canonical name:** PidTagSentRepresentingFlags

**Description:**

**Property ID:** 0x401A

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:**

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** ptagSentRepresentingFlags

## 2.1007 PidTagSentRepresentingName

**Canonical name:** PidTagSentRepresentingName

**Description:** Contains the display name for the end user who is represented by the sending mailbox owner.

**Property ID:** 0x0042

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.57

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_NAME, PR\_SENT\_REPRESENTING\_NAME\_A, ptagSentRepresentingName, PR\_SENT\_REPRESENTING\_NAME\_W, urn:schemas:httpmail:fromname, http://schemas.microsoft.com/exchange/from-name-utf8

## 2.1008 PidTagSentRepresentingSearchKey

**Canonical name:** PidTagSentRepresentingSearchKey

**Description:** Contains a binary-comparable key that represents the end user who is represented by the sending mailbox owner.

**Property ID:** 0x003B

**Data type:** PtypBinary, 0x0102

**Area:** Address Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.58

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXOTASK\]](#)

**Alternate names:** PR\_SENT\_REPRESENTING\_SEARCH\_KEY, ptagSentRepresentingSearchKey

## 2.1009 PidTagSentRepresentingSmtpAddress

**Canonical name:** PidTagSentRepresentingSmtpAddress

**Description:** Contains the SMTP email address of the end user who is represented by the sending mailbox owner.

**Property ID:** 0x5D02

**Data type:** PtypString, 0x001F

**Area:** Mail

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.59

**Alternate names:** ptagRecipientSentRepresentingSMTPAddress, SentRepresentingSMTPAddressXSO, PR\_SENT\_REPRESENTING\_SMTP\_ADDRESS

## 2.1010 PidTagSmtpAddress

**Canonical name:** PidTagSmtpAddress

**Description:** Contains the SMTP address of the Message object.

**Property ID:** 0x39FE

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.21

**Consuming references:** [\[MS-OXCMAIL\]](#), [\[MS-OXOMSG\]](#), [\[MS-OXCMSG\]](#), [\[MS-OXOAB\]](#), [\[MS-OXSHARE\]](#)

**Alternate names:** PR\_SMTP\_ADDRESS, PR\_SMTP\_ADDRESS\_A, PR\_SMTP\_ADDRESS\_W

## 2.1011 PidTagSortLocaleId

**Canonical name:** PidTagSortLocaleId

**Description:** Contains the locale identifier.

**Property ID:** 0x6705

**Data type:** PtypInteger32, 0x0003

**Area:** ExchangeAdministrative

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1.1.13

**Consuming reference:** [\[MS-OXPFOAB\]](#)

**Alternate names:** PR\_SORT\_LOCALE\_ID, ptagSortLocaleId

## 2.1012 PidTagSourceKey

**Canonical name:** PidTagSourceKey

**Description:** Contains a value that contains an internal global identifier (GID) for this folder or message.

**Property ID:** 0x65E0

**Data type:** PtypBinary, 0x0102

**Area:** Sync

**Defining reference:** [\[MS-OXCFXICS\]](#) section 2.2.1.2.5

**Alternate names:** PR\_SOURCE\_KEY

## 2.1013 PidTagSpokenName

**Canonical name:** PidTagSpokenName

**Description:** Contains a recording of the mail user's name pronunciation.

**Property ID:** 0x8CC2

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.41

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_UM\_SPOKEN\_NAME

## 2.1014 PidTagSpouseName

**Canonical name:** PidTagSpouseName

**Description:** Contains the name of the mail user's spouse/partner.

**Property ID:** 0x3A48

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.10.3

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_SPOUSE\_NAME, PR\_SPOUSE\_NAME\_A, PR\_SPOUSE\_NAME\_W,  
urn:schemas:contacts:spousecn

## 2.1015 PidTagStartDate

**Canonical name:** PidTagStartDate

**Description:** Contains the value of the **PidLidAppointmentStartWhole** property (section [2.29](#)).

**Property ID:** 0x0060

**Data type:** PtypTime, 0x0040

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXOCAL\]](#) section 2.2.1.30

**Consuming references:** [\[MS-OXORMDR\]](#), [\[MS-OXTNEF\]](#), [\[MS-XWDCAL\]](#),

**Alternate names:** PR\_START\_DATE, [http://schemas.microsoft.com/mapi/start\\_date](http://schemas.microsoft.com/mapi/start_date)

## 2.1016 PidTagStartDateEtc

**Canonical name:** PidTagStartDateEtc

**Description:** Contains the default retention period, and the start date from which the age of a Message object is calculated.

**Property ID:** 0x301B

**Data type:** PtypBinary, 0x0102

**Area:** Archive

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.58.4

**Alternate names:** PR\_START\_DATE\_ETC, ptagStartDateEtc

## 2.1017 PidTagStateOrProvince

**Canonical name:** PidTagStateOrProvince



**Description:** Contains the name of the mail user's state or province.

**Property ID:** 0x3A28

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.17

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_STATE\_OR\_PROVINCE, PR\_STATE\_OR\_PROVINCE\_A, PR\_STATE\_OR\_PROVINCE\_W, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_A, PR\_BUSINESS\_ADDRESS\_STATE\_OR\_PROVINCE\_W, urn:schemas:contacts:mailingstate

## 2.1018 PidTagStoreEntryId

**Canonical name:** PidTagStoreEntryId

**Description:** Contains the unique EntryID of the message store where an object resides.

**Property ID:** 0x0FFB

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.44

**Consuming references:** [\[MS-OXOFLAG\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_STORE\_ENTRYID, ptagStoreEntryId

## 2.1019 PidTagStoreState

**Canonical name:** PidTagStoreState

**Description:** Indicates whether a mailbox has any active Search folders.

**Property ID:** 0x340E

**Data type:** PtypInteger32, 0x0003

**Area:** MapiMessageStore

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_STORE\_STATE

## 2.1020 PidTagStoreSupportMask

**Canonical name:** PidTagStoreSupportMask

**Description:** Indicates whether string properties within the .msg file are Unicode-encoded.

**Property ID:** 0x340D

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:** [\[MS-OXMSG\]](#) section 2.1.1.1

**Alternate names:** PR\_STORE\_SUPPORT\_MASK, ptagStoreSupportMask

## 2.1021 PidTagStreetAddress

**Canonical name:** PidTagStreetAddress

**Description:** Contains the mail user's street address.

**Property ID:** 0x3A29

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.14

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_STREET\_ADDRESS, PR\_STREET\_ADDRESS\_A, PR\_STREET\_ADDRESS\_W, PR\_BUSINESS\_ADDRESS\_STREET, PR\_BUSINESS\_ADDRESS\_STREET\_A, PR\_BUSINESS\_ADDRESS\_STREET\_W, urn:schemas:contacts:mailingstreet

## 2.1022 PidTagSubfolders

**Canonical name:** PidTagSubfolders

**Description:** Specifies whether a folder has subfolders.

**Property ID:** 0x360A

**Data type:** PtypBoolean, 0x000B

**Area:** MapiContainer

**Defining reference:** [\[MS-OXCFOLD\]](#) section 2.2.2.2.1.12

**Alternate names:** PR\_SUBFOLDERS, ptagSubFolders, DAV:hassubs

## 2.1023 PidTagSubject

**Canonical name:** PidTagSubject

**Description:** Contains the subject of the email message.

**Property ID:** 0x0037

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.46

**Consuming references:** [\[MS-OXCICAL\]](#), [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXTNEF\]](#), [\[MS-OXCDATA\]](#), [\[MS-OXCSPAM\]](#), [\[MS-OXCTABL\]](#), [\[MS-OXMSG\]](#), [\[MS-OXOCFG\]](#), [\[MS-OXOJRNL\]](#), [\[MS-OXORULE\]](#), [\[MS-OXPSVAL\]](#), [\[MS-OXWAVLS\]](#), [\[MS-XWDCAL\]](#)

**Alternate names:** PR\_SUBJECT, PR\_SUBJECT\_A, ptagSubject, PR\_SUBJECT\_W, urn:schemas:httpmail:subject, <http://schemas.microsoft.com/exchange/subject-utf8>

## 2.1024 PidTagSubjectPrefix

**Canonical name:** PidTagSubjectPrefix

**Description:** Contains the prefix for the subject of the message.

**Property ID:** 0x003D

**Data type:** PtypString, 0x001F

**Area:** General Message Properties

**Defining reference:** [\[MS-OXCMMSG\]](#) section 2.2.1.9

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXCPRPT\]](#), [\[MS-OXOCAL\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXODLGT\]](#), [\[MS-OXONOTE\]](#), [\[MS-OXOPFFB\]](#), [\[MS-OXOPOST\]](#), [\[MS-OXORSS\]](#), [\[MS-OXOSMMS\]](#), [\[MS-OXSHARE\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_SUBJECT\_PREFIX, PR\_SUBJECT\_PREFIX\_A, ptagSubjectPrefix, PR\_SUBJECT\_PREFIX\_W

## 2.1025 PidTagSupplementaryInfo

**Canonical name:** PidTagSupplementaryInfo

**Description:** Contains supplementary information about a delivery status notification, as specified in [\[RFC3464\]](#).

**Property ID:** 0x0C1B

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.2.36

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_SUPPLEMENTARY\_INFO, ptagSupplementaryInfo

## 2.1026 PidTagSurname

**Canonical name:** PidTagSurname

**Description:** Contains the mail user's family name.

**Property ID:** 0x3A11

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.1

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_SURNAME, PR\_SURNAME\_A, PR\_SURNAME\_W, urn:schemas:contacts:sn

## 2.1027 PidTagSwappedToDoData

**Canonical name:** PidTagSwappedToDoData

**Description:** Contains a secondary storage location for flags when sender flags or sender reminders are supported.

**Property ID:** 0x0E2D

**Data type:** PtypBinary, 0x0102

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.7

**Consuming reference:** [\[MS-OXORMDR\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_DATA, ptagSwappedToDoData

## 2.1028 PidTagSwappedToDoStore

**Canonical name:** PidTagSwappedToDoStore

**Description:** Contains the value of the **PidTagStoreEntryId** property (section [2.1018](#)) of the message when the value of the **PidTagSwappedToDoData** property (section [2.1027](#)) is set.

**Property ID:** 0x0E2C

**Data type:** PtypBinary, 0x0102

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.8

**Consuming reference:** [\[MS-OXORMDR\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_SWAPPED\_TODO\_STORE, ptagSwappedToDoStore

## 2.1029 PidTagTargetEntryId

**Canonical name:** PidTagTargetEntryId

**Description:** Contains the message ID of a Message object being submitted for optimization ([\[MS-OXOMSG\]](#) section 3.2.4.4).

**Property ID:** 0x3010

**Data type:** PtypBinary, 0x0102

**Area:** ID Properties

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.76

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCRPC\]](#)

**Alternate names:** PR\_TARGET\_ENTRYID, ptagTargetEntryId

## 2.1030 PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Canonical name:** PidTagTelecommunicationsDeviceForDeafTelephoneNumber

**Description:** Contains the mail user's telecommunication device for the deaf (TTY/TDD) telephone number.

**Property ID:** 0x3A4B

**Data type:** **PtypString**, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.4.13

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TTYTDD\_PHONE\_NUMBER, PR\_TTYTDD\_PHONE\_NUMBER\_A, PR\_TTYTDD\_PHONE\_NUMBER\_W, urn:schemas:contacts:tytddphone

## 2.1031 PidTagTelexNumber

**Canonical name:** PidTagTelexNumber

**Description:** Contains the mail user's telex number. This property is returned from an NSPI server as a **PtypMultipleBinary**. Otherwise, the data type is **PtypString**.

**Property ID:** 0x3A2C

**Data type:** **PtypString**, 0x001F; **PtypMultipleBinary**, 0x1102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.30

**Consuming references:** [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TELEX\_NUMBER, PR\_TELEX\_NUMBER\_A, PR\_TELEX\_NUMBER\_W, urn:schemas:contacts:telexnumber

## 2.1032 PidTagTemplateData

**Canonical name:** PidTagTemplateData

**Description:** Describes the controls used in the template that is used to retrieve address book information.

**Property ID:** 0x0001

**Data type:** **PtypBinary**, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABKT\]](#) section 2.2.2

**Alternate names:** PR\_EMS\_TEMPLATE\_BLOB

## 2.1033 PidTagTemplateid

**Canonical name:** PidTagTemplateid

**Description:** Contains the value of the **PidTagEntryId** property (section [2.674](#)), expressed as a **Permanent Entry ID** format.

**Property ID:** 0x3902

**Data type:** PtypBinary, 0x0102

**Area:** MapiAddressBook

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.3

**Alternate names:** PR\_TEMPLATEID

## 2.1034 PidTagTextAttachmentCharset

**Canonical name:** PidTagTextAttachmentCharset

**Description:** Specifies the character set of an attachment received via MIME with the content-type of text.

**Property ID:** 0x371B

**Data type:** PtypString, 0x001F

**Area:** Message Attachment Properties

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.2.25

**Consuming reference:** [\[MS-OXCMAIL\]](#)

**Alternate names:** ptagTextAttachmentCharset

## 2.1035 PidTagThumbnailPhoto

**Canonical name:** PidTagThumbnailPhoto

**Description:** Contains the mail user's photo in .jpg format.

**Property ID:** 0x8C9E

**Data type:** PtypBinary, 0x0102

**Area:** Address Book

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.40

**Consuming reference:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_EMS\_AB\_THUMBNAIL\_PHOTO

## 2.1036 PidTagTitle

**Canonical name:** PidTagTitle

**Description:** Contains the mail user's job title.

**Property ID:** 0x3A17

**Data type:** PtypString, 0x001F

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.4

**Consuming references:** [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_TITLE, PR\_TITLE\_A, PR\_TITLE\_W, urn:schemas:contacts:title

## 2.1037 PidTagTnefCorrelationKey

**Canonical name:** PidTagTnefCorrelationKey

**Description:** Contains a value that correlates a Transport Neutral Encapsulation Format (TNEF) attachment with a message.

**Property ID:** 0x007F

**Data type:** PtypBinary, 0x0102

**Area:** MapiEnvelope

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.29

**Consuming reference:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXTNEF\]](#)

**Alternate names:** PR\_TNEF\_CORRELATION\_KEY

## 2.1038 PidTagToDoItemFlags

**Canonical name:** PidTagToDoItemFlags

**Description:** Contains flags associated with objects.

**Property ID:** 0x0E2B

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXOFLAG\]](#) section 2.2.1.6

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#), [\[MS-OXOSFLD\]](#)

**Alternate names:** PR\_TODO\_ITEM\_FLAGS, ptagToDoItemFlags

## 2.1039 PidTagTransmittableDisplayName

**Canonical name:** PidTagTransmittableDisplayName

**Description:** Contains an Address Book object's display name that is transmitted with the message.

**Property ID:** 0x3A20

**Data type:** PtypString, 0x001F

**Area:** Address Properties

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.3.8

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_TRANSMITTABLE\_DISPLAY\_NAME, PR\_TRANSMITTABLE\_DISPLAY\_NAME\_A, ptagTransmittableDisplayName, PR\_TRANSMITTABLE\_DISPLAY\_NAME\_W

## 2.1040 PidTagTransportMessageHeaders

**Canonical name:** PidTagTransportMessageHeaders

**Description:** Contains transport-specific message envelope information for email.

**Property ID:** 0x007D

**Data type:** PtypString, 0x001F

**Area:** Email

**Defining reference:** [\[MS-OXOMSG\]](#) section 2.2.1.61

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMAIL\]](#)

**Alternate names:** PR\_TRANSPORT\_MESSAGE\_HEADERS, PR\_TRANSPORT\_MESSAGE\_HEADERS\_A, PR\_TRANSPORT\_MESSAGE\_HEADERS\_W

## 2.1041 PidTagTrustSender

**Canonical name:** PidTagTrustSender

**Description:** Specifies whether the associated message was delivered through a trusted transport channel.

**Property ID:** 0x0E79

**Data type:** PtypInteger32, 0x0003

**Area:** MapiNonTransmittable

**Defining reference:** [\[MS-OXCMSG\]](#) section 2.2.1.45

**Consuming references:** [\[MS-OXCFXICS\]](#), [\[MS-OXCMSG\]](#)

**Alternate names:** PR\_TRUST\_SENDER, ptagTrustSender

## 2.1042 PidTagUserCertificate

**Canonical name:** PidTagUserCertificate

**Description:** Contains an ASN.1 authentication certificate for a messaging user.

**Property ID:** 0x3A22

**Data type:** PtypBinary, 0x0102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.34

**Consuming references:** [\[MS-OXOAB\]](#)

**Alternate names:** PR\_USER\_CERTIFICATE, ptagUserCertificate, urn:schemas:contacts:usercertificate

## 2.1043 PidTagUserEntryId

**Canonical name:** PidTagUserEntryId

**Description:** Address book EntryID of the user logged on to the public folders.



**Property ID:** 0x6619

**Data type:** PtypBinary, 0x0102

**Area:** ExchangeMessageStore

**Defining reference:** [\[MS-OXCSTOR\]](#) section 2.2.2.1

**Alternate names:** PR\_USER\_ENTRYID, ptagUserEntryId

## **2.1044 PidTagUserX509Certificate**

**Canonical name:** PidTagUserX509Certificate

**Description:** Contains a list of certificates for the mail user.

**Property ID:** 0x3A70

**Data type:** PtypMultipleBinary, 0x1102

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOABK\]](#) section 2.2.4.36

**Consuming references:** [\[MS-OXLDAP\]](#), [\[MS-OXOAB\]](#), [\[MS-OXOCNTC\]](#), [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_USER\_X509\_CERTIFICATE

## **2.1045 PidTagViewDescriptorBinary**

**Canonical name:** PidTagViewDescriptorBinary

**Description:** Contains view definitions.

**Property ID:** 0x7001

**Data type:** PtypBinary, 0x0102

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.6.1

**Alternate names:** PR\_VD\_BINARY

## **2.1046 PidTagViewDescriptorName**

**Canonical name:** PidTagViewDescriptorName

**Description:**

**Property ID:** 0x7006

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:**

**Consuming reference:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_NAME, PR\_VD\_NAME\_W

## 2.1047 PidTagViewDescriptorStrings

**Canonical name:** PidTagViewDescriptorStrings

**Description:** Contains view definitions in string format.

**Property ID:** 0x7002

**Data type:** PtypString, 0x001F

**Area:** MessageClassDefinedTransmittable

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.6.2

**Alternate names:** PR\_VD\_STRINGS, PR\_VD\_STRINGS\_W

## 2.1048 PidTagViewDescriptorVersion

**Canonical name:** PidTagViewDescriptorVersion

**Description:** Contains the View Descriptor version.

**Property ID:** 0x7007

**Data type:** PtypInteger32, 0x0003

**Area:** Miscellaneous Properties

**Defining reference:**

**Consuming reference:** [\[MS-OXOCFG\]](#)

**Alternate names:** PR\_VD\_VERSION

## 2.1049 PidTagVoiceMessageAttachmentOrder

**Canonical name:** PidTagVoiceMessageAttachmentOrder

**Description:** Contains a list of file names for the audio file attachments that are to be played as part of a message.

**Property ID:** 0x6805

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.9

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageAttachmentOrder

## 2.1050 PidTagVoiceMessageDuration

**Canonical name:** PidTagVoiceMessageDuration

**Description:** Specifies the length of the attached audio message, in seconds.

**Property ID:** 0x6801

**Data type:** PtypInteger32, 0x0003

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.3

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageDuration

## 2.1051 PidTagVoiceMessageSenderName

**Canonical name:** PidTagVoiceMessageSenderName

**Description:** Specifies the name of the caller who left the attached voice message, as provided by the voice network's caller ID system.

**Property ID:** 0x6803

**Data type:** PtypString, 0x001F

**Area:** Unified Messaging

**Defining reference:** [\[MS-OXOUM\]](#) section 2.2.5.5

**Consuming references:** [\[MS-OXCMAIL\]](#)

**Alternate names:** InternalSchemaVoiceMessageSenderName

## 2.1052 PidTagWeddingAnniversary

**Canonical name:** PidTagWeddingAnniversary

**Description:** Contains the date of the mail user's wedding anniversary.

**Property ID:** 0x3A41

**Data type:** PtypTime, 0x0040

**Area:** MapiMailUser

**Defining reference:** [\[MS-OXOCNTC\]](#) section 2.2.1.5.4

**Consuming references:** [\[MS-OXVCARD\]](#)

**Alternate names:** PR\_WEDDING\_ANNIVERSARY, urn:schemas:contacts:weddinganniversary

## 2.1053 PidTagWlinkAddressBookEID

**Canonical name:** PidTagWlinkAddressBookEID

**Description:** Specifies the value of the **PidTagEntryId** property (section [2.674](#)) of the user to whom the folder belongs.

**Property ID:** 0x6854

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.16

**Alternate names:** PR\_WLINK\_ABEID

## **2.1054      PidTagWlinkAddressBookStoreEID**

**Canonical name:** PidTagWlinkAddressBookStoreEID

**Description:** Specifies the value of the **PidTagStoreEntryId** property (section [2.1018](#)) of the current user (not the owner of the folder).

**Property ID:** 0x6891

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.17

**Alternate names:** PR\_WLINK\_AB\_EXSTOREEID

## **2.1055      PidTagWlinkCalendarColor**

**Canonical name:** PidTagWlinkCalendarColor

**Description:** Specifies the background color of the calendar.

**Property ID:** 0x6853

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.15

**Alternate names:** PR\_WLINK\_CALENDAR\_COLOR

## **2.1056      PidTagWlinkClientID**

**Canonical name:** PidTagWlinkClientID

**Description:** Specifies the Client ID that allows the client to determine whether the shortcut was created on the current machine/user via an equality test.

**Property ID:** 0x6890

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.18

**Alternate names:** PR\_WLINK\_CLIENTID

## **2.1057      PidTagWlinkEntryId**

**Canonical name:** PidTagWlinkEntryId

**Description:** Specifies the EntryID of the folder pointed to by the shortcut.

**Property ID:** 0x684C

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.8

**Alternate names:** PR\_WLINK\_ENTRYID

## **2.1058 PidTagWlinkFlags**

**Canonical name:** PidTagWlinkFlags

**Description:** Specifies conditions associated with the shortcut.

**Property ID:** 0x684A

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.6

**Alternate names:** PR\_WLINK\_FLAGS

## **2.1059 PidTagWlinkFolderType**

**Canonical name:** PidTagWlinkFolderType

**Description:** Specifies the type of folder pointed to by the shortcut.

**Property ID:** 0x684F

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.11

**Alternate names:** PR\_WLINK\_FOLDER\_TYPE

## **2.1060 PidTagWlinkGroupClsid**

**Canonical name:** PidTagWlinkGroupClsid

**Description:** Specifies the value of the **PidTagWlinkGroupHeaderID** property (section 2.1060) of the **group header** associated with the shortcut.

**Property ID:** 0x6850

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.12

**Alternate names:** PR\_WLINK\_GROUP\_CLSID

## **2.1061 PidTagWlinkGroupHeaderID**

**Canonical name:** PidTagWlinkGroupHeaderID

**Description:** Specifies the ID of the **navigation shortcut** that groups other navigation shortcuts.

**Property ID:** 0x6842

**Data type:** **PtypBinary**, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.3

**Alternate names:**

## **2.1062      PidTagWlinkGroupName**

**Canonical name:** PidTagWlinkGroupName

**Description:** Specifies the value of the **PidTagNormalizedSubject** (section [2.803](#)) of the group header associated with the shortcut.

**Property ID:** 0x6851

**Data type:** **PtypString**, 0x001F

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.13

**Alternate names:** PR\_WLINK\_GROUP\_NAME

## **2.1063      PidTagWlinkOrdinal**

**Canonical name:** PidTagWlinkOrdinal

**Description:** Specifies a variable-length binary property to be used to sort shortcuts lexicographically.

**Property ID:** 0x684B

**Data type:** **PtypBinary**, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.7

**Alternate names:** PR\_WLINK\_ORDINAL

## **2.1064      PidTagWlinkRecordKey**

**Canonical name:** PidTagWlinkRecordKey

**Description:** Specifies the value of **PidTagRecordKey** property (section [2.901](#)) of the folder pointed to by the shortcut.

**Property ID:** 0x684D

**Data type:** **PtypBinary**, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.9

**Alternate names:** PR\_WLINK\_RECKEY

## 2.1065 **PidTagWlinkROGroupType**

**Canonical name:** PidTagWlinkROGroupType

**Description:** Specifies the type of group header.

**Property ID:** 0x6892

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.19

**Alternate names:** PR\_WLINK\_RO\_GROUP\_TYPE

## 2.1066 **PidTagWlinkSaveStamp**

**Canonical name:** PidTagWlinkSaveStamp

**Description:** Specifies an integer that allows a client to identify with a high probability whether the navigation shortcut was saved by the current client session.

**Property ID:** 0x6847

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.4

**Alternate names:**

## 2.1067 **PidTagWlinkSection**

**Canonical name:** PidTagWlinkSection

**Description:** Specifies the section where the shortcut should be grouped.

**Property ID:** 0x6852

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.14

**Alternate names:** PR\_WLINK\_SECTION

## 2.1068 **PidTagWlinkStoreEntryId**

**Canonical name:** PidTagWlinkStoreEntryId

**Description:** Specifies the value of the **PidTagStoreEntryId** property (section [2.1018](#)) of the folder pointed to by the shortcut.

**Property ID:** 0x684E

**Data type:** PtypBinary, 0x0102

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.10

**Alternate names:** PR\_WLINK\_STORE\_ENTRYID

## **2.1069      PidTagWlinkType**

**Canonical name:** PidTagWlinkType

**Description:** Specifies the type of navigation shortcut.

**Property ID:** 0x6849

**Data type:** PtypInteger32, 0x0003

**Area:** Configuration

**Defining reference:** [\[MS-OXOCFG\]](#) section 2.2.9.5

**Alternate names:** PR\_WLINK\_TYPE



### 3 Structure Examples

None.

## **4 Security**

There are no security considerations unique to this specification.

### **4.1 Security Considerations for Implementers**

None.

### **4.2 Index of Security Fields**

None.

## 5 Appendix A: Product Behavior

The information in this specification is applicable to the following Microsoft products or supplemental software. References to product versions include released service packs.

- Microsoft Exchange Server 2003
- Microsoft Exchange Server 2007
- Microsoft Exchange Server 2010
- Microsoft Exchange Server 2013
- Microsoft Exchange Server 2016
- Microsoft Office Outlook 2003
- Microsoft Office Outlook 2007
- Microsoft Outlook 2010
- Microsoft Outlook 2013
- Microsoft Outlook 2016

Exceptions, if any, are noted below. If a service pack or Quick Fix Engineering (QFE) number appears with the product version, behavior changed in that service pack or QFE. The new behavior also applies to subsequent service packs of the product unless otherwise specified. If a product edition appears with the product version, behavior is different in that product edition.

Unless otherwise specified, any statement of optional behavior in this specification that is prescribed using the terms SHOULD or SHOULD NOT implies product behavior in accordance with the SHOULD or SHOULD NOT prescription. Unless otherwise specified, the term MAY implies that the product does not follow the prescription.

## 6 Change Tracking

This section identifies changes that were made to this document since the last release. Changes are classified as New, Major, Minor, Editorial, or No change.

The revision class **New** means that a new document is being released.

The revision class **Major** means that the technical content in the document was significantly revised. Major changes affect protocol interoperability or implementation. Examples of major changes are:

- A document revision that incorporates changes to interoperability requirements or functionality.
- The removal of a document from the documentation set.

The revision class **Minor** means that the meaning of the technical content was clarified. Minor changes do not affect protocol interoperability or implementation. Examples of minor changes are updates to clarify ambiguity at the sentence, paragraph, or table level.

The revision class **Editorial** means that the formatting in the technical content was changed. Editorial changes apply to grammatical, formatting, and style issues.

The revision class **No change** means that no new technical changes were introduced. Minor editorial and formatting changes may have been made, but the technical content of the document is identical to the last released version.

Major and minor changes can be described further using the following change types:

- New content added.
- Content updated.
- Content removed.
- New product behavior note added.
- Product behavior note updated.
- Product behavior note removed.
- New protocol syntax added.
- Protocol syntax updated.
- Protocol syntax removed.
- New content added due to protocol revision.
- Content updated due to protocol revision.
- Content removed due to protocol revision.
- New protocol syntax added due to protocol revision.
- Protocol syntax updated due to protocol revision.
- Protocol syntax removed due to protocol revision.
- Obsolete document removed.

Editorial changes are always classified with the change type **Editorially updated**.

Some important terms used in the change type descriptions are defined as follows:

- **Protocol syntax** refers to data elements (such as packets, structures, enumerations, and methods) as well as interfaces.
- **Protocol revision** refers to changes made to a protocol that affect the bits that are sent over the wire.

The changes made to this document are listed in the following table. For more information, please contact [dochelp@microsoft.com](mailto:dochelp@microsoft.com).

Section	Tracking number (if applicable) and description	Major change (Y or N)	Change type
<a href="#">2.692</a> PidTagFolderFlags	Added a new section for property PidTagFolderFlags.	Y	New content added.
<a href="#">2.712</a> PidTagHierRev	Added new section for property PidTagHierRev.	Y	New content added.

## 7 Index

### A

[Applicability](#) 39

### C

[Change tracking](#) 371

### E

[Examples](#) 368

### F

[Fields - security index](#) 369

[Fields - vendor-extensible](#) 39

### G

[Glossary](#) 23

### I

[Implementer - security considerations](#) 369

[Index of security fields](#) 369

[Informative references](#) 33

[Introduction](#) 23

### L

[Localization](#) 39

### N

[Normative references](#) 31

### O

Overview

[common message classes](#) 34

[commonly used property sets](#) 35

[property ID ranges](#) 36

[WebDAV property naming](#) 38

[Overview \(synopsis\)](#) 33

### P

[Product behavior](#) 370

### R

[References](#) 31

[informative](#) 33

[normative](#) 31

[Relationship to protocols and other structures](#) 39

### S

Security

[field index](#) 369

[implementer considerations](#) 369

### T

[Tracking changes](#) 371

### V

[Vendor-extensible fields](#) 39

[Versioning](#) 39